© Copyright Gatemaster 2026

GATE SAFETY RESTRAINER





Proven to withstand 500kg in weight

Stainless steel

Suitable for metal gate frames.

INCLUDED IN THE BOX

- Gate safety restrainer
- Plastic cover brushes

MADE IN BRITAIN

Made from flexible braided stainless steel wire and stainless steel end stops for robust performance making it ideal for all outdoor environments. Compatible with any box section gate and can be easily retrofitted to existing gates.

Product code	Description
GRS03	For gates up to 260kg, 220mm operational length
GRS04	For gates up to 500kg, 275mm operational length

HELP & SUPPORT

Need further assistance? Our customer support team can help with order queries, product identification, spare parts, warranty information and general after-care.

UK: +44 1243 558580 US: +1 214 872 9687

www.gatemasterlocks.com support@gatemasterlocks.com

INSTALLATION INSTRUCTIONS

IMPORTANT: Strict installation and usage conditions apply. Some gate configurations will not be made safe using this device, refer to conditions of use below.
IMPORTANT: The cable must move freely as the gate opens and closes. Repeated bending or creasing can cause fatigue and failure. For box section 40 mm or less, mount the restrainer on the side the gate swings towards — inside for inward-opening gates, outside for outward-opening gates.

1. Drill a 13mm hole into the gate and the post, 30-50mm above or below the top hinge.
2. Slot the 2 end stops into the holes and push on the plastic bushes. These protect the gate from scratches and allow the wire to slide in and out easily

CONDITIONS OF USE

*Check condition of restrainer every 6 months and replace if damaged.
**The device is designed to prevent the gate falling sideways rather than taking its full weight. If the restraining device becomes taut before the bottom of the gate rests on the ground, this device is not suitable for your gate.





