

DENTAL EQUIPMENT CATALOGUE

Advanced Solutions
For Modern Clinics



Overhead Delivery Unit
With Large Instrument Tray



Premium Dental Chair

UNICORN DenMart®
Behind The Best Indian Dentists

Ultimate Patient Comfort

Premium American Leather with Memory Foam



Doctor's Stool



Overhead Delivery Unit
With Large Instrument Tray

CE / EC EN ISO 13485:2016

DCI USA LED Light 3 axis rotation: International-grade illumination with balanced colour temperature for precise shade matching and photography.

Double-Arm Assistant Console: The elevated dual-arm design keeps pipes off the floor for better hygiene while allowing assistants full access from all sides, boosting speed & comfort in four-handed dentistry.

Advanced Disinfection: State-of-the-art disinfection system for comprehensive hygiene.

5-Second Suction Delay: Ensures saliva and blood are fully evacuated before auto-shutoff-keeps lines clear and odour-free.

Extra Cushions for more comfort

Premium American Leather Upholstery with Memory Foam: Made with soft memory foam and high-quality leather, the chair looks stylish, resists scratches, & is easy to clean every day.

Top-Fill Water Bottle: Refill chair water without detaching the bottle.

Rust-Free Aluminum Casting: Superior durability and zero corrosion worries guarantee long-term reliability, even in high-moisture clinical settings.



180° Rotatable Side Cabinet



Elegant and beautiful integrated hidden switch



Sleek & Elegant curved arm design



Thicker chair frame



Stable Ultra large chassis



*Underhanging Delivery Unit option also available

Multiple color choices of leather cushion



Smooth, Sturdy, Comfortably Smart Technology Built To Last



Doctor's Stool

- ✦ Stable and heavier base
- ✦ Comfortable memory foam leather
- ✦ Anti crushing system
- ✦ Emergency safety switch
- ✦ Sensor based triple axis movable LED operating light
- ✦ Adjustable Dual color light (white & yellow) source with digital display
- ✦ Bilateral pneumatic control design
- ✦ Low & High VAC suction with delay function
- ✦ Multifunctional additional movable tray
- ✦ Easily cleaned Removable instrument tray
- ✦ Anti spill, Anti splash detachable glass spittoon
- ✦ Multifunctional rotatable handpiece holder
- ✦ Max. load bearing capacity - 180kg



Boutique & fashionable
waist headrest



Extra cushions for
more comfort



High & low suction
filtration system



Sensor Based Led Light
With Digital Display



Safety Protection
System Switch



State-of-the-art
disinfection system

Multiple color choices of leather cushion



Smooth, Sturdy, Comfortably Smart Technology Built To Last



Doctor's Stool

- ✦ Stable and heavier base
- ✦ Comfortable memory foam leather
- ✦ Anti crushing system
- ✦ Emergency safety switch
- ✦ Sensor based triple axis movable LED operating light
- ✦ Adjustable Dual color light (white & yellow) source with digital display
- ✦ Bilateral pneumatic control design
- ✦ Low & High VAC suction with delay function
- ✦ Multifunctional additional movable tray
- ✦ Easily cleaned Removable instrument tray
- ✦ Anti spill, Anti splash detachable glass spittoon
- ✦ Multifunctional rotatable handpiece holder
- ✦ Max. load bearing capacity - 180kg

Multiple color choices of leather cushion



Boutique & fashionable
waist headrest



Extra cushions for
more comfort



High & low suction
filtration system



Sensor Based Led Light
With Digital Display



Safety Protection
System Switch



State-of-the-art
disinfection system

AUTOCLAVE

European B Class Autoclave

FENG 23L TOUCH SCREEN AUTOCLAVE

Redefining The Sterilization Excellence

- ✦ B type fully automatic front-loading autoclave powered by triple vacuum cycle
- ✦ Temperature Selection - 121° C / 134° C/ B+
- ✦ Double door lock system for safety
- ✦ 5 Programs for sterilization of all types of instruments – Solid/ Hollow, Porous/Non-Porous etc.
- ✦ Built-in water quality sensor
- ✦ Bow and Dick test qualified
- ✦ Touch screen control panel
- ✦ Big open tank, easy to clean
- ✦ Data storage facility with USB functioning (2000 cycles)
- ✦ Steam generator cleaning program to increase the efficiency of the autoclave
- ✦ Chamber size: 250 mm x 450 mm
- ✦ 9 nos. error codes for self diagnosis
- ✦ Inbuilt USB & printer port with micro printer (optional)
- ✦ Product Size: 594X468X453mm
- ✦ Net Weight: 50Kg
- ✦ Voltage: 230 V 50/60Hz
- ✦ Power: 1800W
- ✦ Water tank capacity: 4.5Ltr.
- ✦ One cycle water consumption: 600ml



Work Mode Chart

Cycle Mode	Ster. Temp (degree)	Ster. Press (Kpa)	Ster. Time (Min)	Drying Time (Min)	Complete Time (min)
Unwrapped Cycle	134	210	4	10	35
Universal B Cycle	134	210	6	15	50
Rubber & Plastic unwrapped cycle	121	110	16	10	45
Rubber & Plastic wrapped cycle	121	110	20	15	60
18 min B cycle (Prion)	134	210	18	15	60
Ster. Result Testing Cycle (B&D Test)	-	-	-	-	30
Vaccum Leackage Testing Cycle	-	-	-	-	20

23 Ltr Touch Screen B-Type front loading Fully automatic with USB RECORDER



USB Record Read



Six Layer Pot Body Structure



Heat Dissipation Structure



Double Door Lock Protection

RAPICLAVE

RAPICLAVE 5L B CLASS AUTOCLAVE

Compact Power. Complete Protection

Rapid Sterilization

The whole process of the unwrapped sterilization cycle only takes 10 minutes; Instant sterilization, suitable for continuous surgeries, improve clinical work efficiency; Meet emergency sterilization needs & solve instant infection control problems; Speed up the use of instrument turnover & reduce the investment of surgical instruments.

Touch Button



- ✦ The LCD displays the data of the sterilization process with a curve, which is clear at a glance.
- ✦ Customers can customize the language, date & time.
- ✦ Omron keys with service: Life of tens of thousands of times

Multiple Program Options

- ✦ 8 sterilization programs for free options
- ✦ Precise temperature control
- ✦ No harms to instruments
- ✦ Extend instrument service life & reduce costs

Work Mode Chart

Sterilization Program	Sterilization Temp (degree)	Sterilization Time (min)
Class S Fast	134	10
Class S Standard	134	15
Class B Fast	134	12
Class B Standard	134	22
Class S Fast	121	25
Class S Standard	121	30
Class B Fast	121	26
Class B Standard	121	37

Born for sterilization of implant



Sterilize in as rapid as 10 minutes



3 Pulses Vacuum



Small Volume but large capacity

Item	Specification
Size	500 X 310 X 320
Chamber Size (mm)	192 X 96 X 300
Chamber Volume (L)	5L
Chamber Type	B
Rated Voltage	AC220v/50Hz
Input Power (VA)	1800VA
Initial Default Pressure	-0.1/0.3Mpa
Initial Default Temperature	140°C
Water Tank Volume (L)	1L
Water consumption for one sterilization (ml)	200mL
Minimum Water Supply	250mL
Ambient Temperature (°C)	+5°C-40°C
Relative Humidity Range	≤85%
NW	26Kg
GW	30 Kg
Residual humidity after drying of the device ≤0.2%	
Residual humidity after drying of the dressing ≤1%	
The highest vacuum ≤-0.92Kpa	

WATER DISTILLER

The water distiller is the best in its class. This distiller completes one litre of pure steam-distilled water in 1 hour. The boil chamber and condensing coils are high-grade 304 Stainless Steel. It comes with a high-quality plastic collection bottle, the lid and handle are made of food-grade polypropylene, and the lid is removable for convenience. Distilling your own water can't get any easier, simply fill the boiling chamber, press the start button, and walk away, the distiller will automatically shut off at the end of the cycle. It's very easy and convenient.

- ✦ Easy to use, produces pure steam distilled water
- ✦ Lightweight compact design, great for home and for medical use
- ✦ Eliminates plastic bottles from the store & saves you money
- ✦ Capacity - 4 Litres
- ✦ High-quality collection bottle for the purest water



DENTAL SEALER- SEAL-120

- ✦ Power: 100 W
- ✦ Power Supply: 230 V | 50-60 Hz
- ✦ Sealing Temperature: 200°C ±10°C
- ✦ Indentation Width: 12 mm
- ✦ Maximum Seal Width: 280 mm
- ✦ Package Dimensions: 500 × 400 × 210 mm
- ✦ Net Weight: 4.8 kg



Ray 98p (Gun Type) Handheld Portable X-Ray

IMAGING IN MY CONTROL

MODERN MEDICAL IMAGING TECHNOLOGY
More accurate and more flexible.



Smart Camera
Angle Assistance



Ergonomic
Design



Long Battery Life

Technical Specifications

Tube Voltage	70kV±10%
Tube Current	2mA + 20%
Input Voltage	100V-240V
Frequency	50 -60Hz
Anode Angle	12.5°
Focus	0.4mm
Exposure Time Range	0.04s -2.0s
Leak Emissivity	1 meter 0.25mGy/h
Machine Weight	1.7kg
Relative Humidity	30%RH-75%RH



WHERE **TRUST** COMES **FIRST**



**Warranty Ke Saath Bhi
Warranty Ke Baad Bhi**

For any Sales & Support

 9821184441, 8448398852

 sales@unicorndenmart.com

Customer Care

Register Your Complaint with A Missed Call: **7065-558-558**

 011-45551250, 51, 55  9717012081, 95994 48518

 care@unicorndenmart.com | care1@unicorndenmart.com

Connect With



Unicorn DenMart



Corporate Office: 3 Local Shopping Centre, MOR Land, Near J Block DDA Market,
New Rajender Nagar, New Delhi – 110060



* Accessories shown may not be a part of standard equipment. Specifications are subject to change without notice.

Ver 8/2026