

SUPERHINGE HEAVY DUTY GATE HINGE



Weld-on 20-year warranty*

Tested up to 500,000 openings

Suitable for metal gate frames.

- Low-friction design makes it ideal for use with automated gates.
- Features adjustable bolt for accurate on-site fitting.
- Corner Lug version available.
- Offset / Incline version available.



Built for strength, reliability and long-term performance, the Gatemaster Superhinge is engineered for demanding heavy-duty gates. Tested to 500,000 openings with minimal wear, it features low-friction brass bearings for smooth, consistent movement throughout its service life. Backed by our 20-year guarantee, the Superhinge is made to keep gates operating reliably for years to come.

Product code	Description
SH16	M16 thread, 150kg weight limit per pair of hinges
SH20	M20 thread, 300kg weight limit per pair of hinges
SH25	M25 thread, 450kg weight limit per pair of hinges
SH30	M30 thread, 900kg weight limit per pair of hinges

HELP & SUPPORT

Need further assistance? Our customer support team can help with order queries, product identification, spare parts, warranty information and general after-care.

UK: +44 1243 558580 US: +1 214 872 9687

www.gatemasterlocks.com support@gatemasterlocks.com

*The warranty covers defects in materials and manufacture and does not cover installation workmanship, including welding, or damage resulting from incorrect installation.

INSTALLATION INSTRUCTIONS

1. With the hinge still assembled, weld the 2 lugs to the gate post, then unscrew the break-off nut and disassemble the hinge
2. Drill a hole through the gate frame to suit the thread size
3. Once the gate has been galvanized or painted, reassemble the hinge without the sacrificial 1.8mm washer. Tighten the break-off nut until the hex breaks off.
4. Hang the gate on the threaded portion with a nut on each side and adjust as necessary.

MAINTENANCE: Lubricate during fitting and once every 6 months to ensure maximum product life.

PRODUCT DIMENSIONS

Product code	Thread size	A	B	C	D	E	F
SH16	M16	37mm	36mm	55mm	15mm	58mm	100mm
SH20	M20	44mm	40mm	63mm	16mm	66mm	125mm
SH25	M24	57mm	40mm	69mm	20mm	81mm	150mm
SH30	M30	64mm	45mm	77mm	24mm	94mm	200mm

