

TREADS OF
EXCELLENCE
AWAIT YOU!

NEXT-GEN TYRES TO RULE ALL TERRAINS



INDEX

RADIAL

TORQUEMAX	1
FARMAX HPT	2
SPRAYMAX	3
FARMAX R65	4
FARMAX R65 X3	5
FARMAX R70/R75	6
FARMAX R80	7
FARMAX R85/R85 R2	8
FARMAX R90/R90 R2	9
MULTILOADMAX	10
YIELDMAX	11
FARMAX RC	12
FLOATMAX FT	13
FLOATMAX RT	14
FLOATMAX CARGO PLUS	15
FLOATMAX VF X3	15
FARM IMPLEMENT 800R	16
HI-FLEX IMPLEMENT	16
LAWNMAX	17
LOAD PRO HARD SURFACE	17
LOAD PRO	18
LIFT PRO	18

BIAS

FARMAX R1	19
FARMAX R2	20
FARMAX F2	20
FARMAX X3 TF	21
FARMAX F2M	21
FARMAX R1 HD	22
YIELDMAX 23°	22
FARMAX AS	23
FARM IMPLEMENT AWI 305	23
FARM IMPLEMENT 404	24
FARM IMPLEMENT LP	24
HIGHWAY IMPLEMENT T422	25
FLOTATION PLUS	25
FLOTATION T422	26

T422 VALUE-PRO	26
FLOTATION TX440	27
TR 800	27
IRROGATOR	28
TURF XL	28
LOGGER XL	29
FOREST XL	29
GM LOADER HD	30
GRIP X HD	30
GRIP XL 5	31
LOADER PRO HD	31
MPT 503	32
MPT 602	32
MPT 800	33
MPT 808	33
TYROCK	34
TYROCK SUPER	34
TYROCK SUPER X3	35
GRIPMASTER EX	35
GRADER XL	36
GRADER XL PLUS	36
GRIP MASTER - ND	37
LOADER XL	37
TRAC XL	38
C 305	38
LOAD PRO	39
ROCK XL	39
GM XL	40
PORT PRO RX	40
PORT PRO TX	41
PORT XL PLUS	41
PORT PRO SL	42
SLICK 404	42
SLICK 431	43
ELEVETA X3	43
ELEVETA PLUS	44
LOAD INDEX & SPEED SYMBOL	45

TORQUEMAX

For High Power Tractors, Grain Carts & Air Seeders



Stepped lug design

Better grip



Tilted lug tip

Lower vibration at high speed



Wider tread width

Lower compaction




Stronger & wider lugs

Longer life



Lower lug angle at the shoulder

Better traction



Rounded shoulder

Less crop damage



SIZES

- VF620/70 R 26 173D TL SB
- VF600/65 R 28 163D TL SB
- VF600/60 R 28 157D TL SB
- IF600/70 R 30 165D TL
- VF540/65 R 30 NRO 163D TL SB
- VF600/70 R 30 170D TL
- VF600/70 R 30 170D TL SB
- VF600/60 R 30 NRO 162D TL SB
- VF710/60 R 30 171D TL SB
- VF620/70R30 175D TL SB
- VF620/75R30 172D TL SB
- VF710/55R30 165D TL SB
- VF380/85R34 149D TL SB
- VF710/60R34 173D TL SB
- IF600/70 R 34 160D TL
- IF600/70 R 34 167D TL
- IF650/60 R 34 159D TL
- VF650/60 R 34 168D TL
- VF650/60 R 34 168D TL SB
- VF650/65 R 34 NRO 167D TL SB
- VF650/65 R 34 NRO 170D TL SB
- VF580/80 R 34 178D TL SB
- VF650/60R38 173D TL SB
- IF800/70 R 38 190D TL SB
- IF520/85 R 38 167D TL
- IF710/70 R 38 178D TL
- VF650/65 R 38 175D TL SB
- IF710/70 R 38 181A8/178B FB TL
- VF520/85 R 38 170D TL
- VF520/85 R 38 170D TL SB
- VF710/60 R 38 NRO 171D TL SB
- VF710/70 R 38 178D TL
- VF800/70 R 38 187D TL SB
- VF900/60 R 38 193D TL SB
- VF650/85 R 38 182D TL SB
- IF800/70 R 38 CFO 190D TL SB
- VF900/60R42 189D TL SB
- IF710/70 R 42 179D TL
- IF710/75 R 42 176D TL
- IF710/75 R 42 176D TL SB
- IF850/75 R 42 186D TL SB
- VF520/85 R 42 174D/177A8 TL
- VF520/85 R 42 174D/177A8 TL SB
- VF650/65 R 42 174D TL
- VF650/65 R 42 174D TL SB
- VF710/70 R 42 185D TL
- VF710/70 R 42 185D TL SB
- VF710/75 R 42 184D TL
- VF710/75 R 42 184D TL SB
- VF710/60 R 42 NRO 176D TL SB
- VF520/85R46 179D TL SB
- VF750/75 R 46 189D TL SB
- VF 520/60R28*
- VF580/85R42*
- VF900/65R46*
- VF620/70R46*

*Upcoming Sizes

FARMAX HPT

For High Power Tractors



Stepped lug tip

Increase the grip and reducing the tractor slip



Extra wide tread

Higher footprint which gives better stability



Rounded shoulder

Provides less soil damage & better grip



Lug base tie bar

Additional support to lugs and also helps to remove mud from lugs



50° lug angle at centre

Smoother road driving comfort, less noise and vibration




SIZES

- 600/70 R 28 157D/160A8 TL
- 600/65R28 154D TL
- 600/70 R 30 158D/161A8 TL
- 600/70 R 30 168D/171A8 TL
- 600/70 R 34 160D TL
- 650/65 R 34 161D TL
- 650/75 R 38 169D TL
- 650/85 R 38 170D/173A8 TL
- 650/85 R 38 173D/176A8 TL
- 710/70 R 38 171D TL
- 710/70 R 38 178D/181A8 TL
- 800/70 R 38 178D TL
- 800/70R38 187D/190A8 TL SB
- 710/70 R 42 173D TL
- 710/70 R 42 176D/179A8 TL
- 710/75 R 42 175D TL
- 710/75 R 42 181D TL
- 480/80 R 50 159D/162A8 TL
- 480/80 R 50 165D/168A8 TL
- 480/80 R 50 176D TL
- 850/80R38*

*Upcoming Sizes

SPRAYMAX

For Sprayers




Higher NSD

Longer life



Stepped lug design

Better grip & traction



Rounded shoulder

Prevents less soil and crop damage

Advanced VF technology

40% more load carrying capability than standard radial



SIZES

- VF 380/80R38 167D TL SB
- VF320/85R38 155D TL SB
- VF480/80 R 42 162D TL
- VF480/80 R 42 162D TL SB
- VF480/80 R 42 176D TL
- VF480/80 R 42 176D TL SB
- VF320/90R42 163D TL SB
- VF380/90 R 46 173D TL
- VF380/90 R 46 173D TL SB
- VF480/80 R 46 164D TL
- VF480/80 R 46 164D TL SB
- VF480/80 R 46 177D TL
- VF480/80 R 46 177D TL SB
- VF750/60 R 46 189D TL SB
- VF380/105 R 50 179D TL SB
- VF380/90 R 50 175D TL
- VF380/90 R 50 175D TL SB
- VF480/80 R 50 179D TL
- VF480/80 R 50 179D TL SB
- VF420/95 R 50 177D TL SB
- VF380/90 R 54 176D TL
- VF380/90 R 54 176D TL SB
- VF480/95 R 54 180D TL SB
- VF380/105 R 54 168D TL SB
- VF320/90R54 168D TL SB
- VF380/105R54 180D TL SB
- VF320/90R50*
- VF480/95R50*

*Upcoming Sizes

FARMAX R65

For Low To Mid HP Tractors



Tilted lug tip

Lesser vibration & noise



Mud breaker

Better self cleaning




Higher angle & lug overlap at centre

Better roadability




Wider tread larger inner volume

Reduced soil compaction




R1-W tread depth

Longer tyre life



Lower angle at shoulder

Superior traction



Rounded shoulder

Lesser damage to soil & crop

SIZES

- 320/65 R 16 117D TL
- 320/65 R 18 109D TL
- 340/65 R 18 122D TL
- 340/65 R 20 124D TL
- 420/65 R 20 135D TL
- 440/65 R 20 138D TL
- 420/65 R 24 138D TL
- 440/65 R 24 128D TL
- 440/65 R 24 135D/138A8 TL
- 480/65 R 24 133D TL
- 480/65 R 24 140D/143A8 TL
- 540/65 R 24 140D TL
- 540/65 R 24 146D TL
- 540/65R26 141D TL
- 440/65 R 28 138D TL
- 480/65 R 28 136D TL
- 480/65 R 28 142D/145A8 TL
- 540/65 R 28 142D TL
- 540/65 R 28 149D TL
- 600/65 R 28 147D/150A8 TL
- 600/65 R 28 154D TL
- 540/65 R 30 143D TL
- 540/65 R 30 150D TL
- 600/65 R 30 149D TL
- 600/65 R 30 155D TL
- 540/65 R 34 145D TL
- 540/65 R 34 152D TL
- 600/65 R 34 151D TL
- 600/65 R 34 157D TL
- 540/65 R 38 147D TL
- 540/65 R 38 153D TL
- 600/65 R 38 153D TL
- 650/65 R 38 157D TL
- 650/65 R 38 163D TL
- 650/65 R 42 158D TL
- 650/65 R 42 165D TL
- 650/65 R 42 170D TL
- 540/65R28*

*Upcoming Sizes

FARMAX R65 X3

For Low To Mid HP Tractors



Directional & robust lugs

Provides higher traction



Robust centre blocks

Low noise & smooth rides



Rounded shoulders

Less soil damage



Through grooves

Better self-cleaning

Higher OD

More mileage



SIZES

▪ 650/65R42*

▪ 540/65R30*

▪ 650/65R38*

▪ 540/65R28*

*Upcoming Sizes

FARMAX R70/ R75

For Low To Mid HP Tractors



Tilted lug tip

Lesser vibration & noise



Mud breaker

Better self cleaning




Higher angle & lug overlap at centre

Better roadability




Wider tread larger inner volume

Reduced soil compaction




R1-W tread depth

Longer tyre life



Lower angle at shoulder

Superior traction



Rounded shoulder

Lesser damage to soil & crop

SIZES

- 200/70 R 16 94D/97A8 TL
- 240/70 R 16 104A8/B TL
- 260/70 R 16 104A8/B TL
- 280/70 R 16 112D/115A8 TL
- 280/70 R 18 114A8/B TL
- 260/70 R 20 113A8/B TL
- 280/70 R 20 116A8/B TL
- 300/70 R 20 TL 110D/113A8
- 300/70 R 20 TL 120D/123A8
- 320/70 R 20 113A8/B TL
- 320/70 R 20 123A8/B TL
- 360/70 R 20 120A8/B TL
- 360/70 R 20 129A8/B TL
- 380/70 R 20 122A8/B TL
- 380/70 R 20 132A8/B TL
- 320/70 R 24 116A8/B TL
- 360/70 R 24 122A8/B TL
- 380/70 R 24 125A8/B TL
- 380/70 R 24 125D TL
- 420/70 R 24 130A8/B TL
- 420/70 R 24 130D TL
- 480/70 R 24 138A8/B TL
- 320/70 R 28 119A8/B TL
- 360/70 R 28 125A8/B TL
- 380/70 R 28 127A8/B TL
- 420/70 R 28 133A8/B TL
- 420/70 R 28 133D TL
- 480/70 R 28 TL 140D/143A8
- 480/70 R 28 TL 151D/154A8
- 600/70 R 28 161A8/B TL
- 420/70 R 30 134A8/B TL
- 480/70 R 30 141A8/B TL
- 480/70 R 30 147D/150A8 TL
- 520/70 R 30 145A8/B TL
- 600/70 R 30 152A8/B TL
- 600/70 R 30 158D TL
- 480/70 R 34 TL 143D/146A8
- 480/70 R 34 149A8/B TL
- 480/70 R 34 155D/158A8 TL
- 520/70 R 34 148A8/B TL
- 520/70 R 34 168A8/B TL
- 480/70 R 38 TL 145D/148A8
- 520/70 R 38 150A8/B TL
- 520/70 R 38 150D TL
- 580/70 R 38 TL 155D/158A8
- 580/70 R 38 170D/173A8 TL
- 580/70 R 38 180D/183A8 TL
- 710/70 R 38 172A8/B TL
- 710/70 R 38 178A8/B TL
- 710/70 R 38 178D TL
- 400/75 R 38 138D/141A8
- 580/70 R 42 158A8/B TL
- 580/70 R 42 158D/161A8 TL
- 620/70 R 42 166A8/B TL
- 620/70 R 42 173A8/B TL
- 710/70 R 42 173A8/B TL
- 710/70 R 42 173D TL


FARMAX R80

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life



Higher angle and lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduced soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction



SIZES

- 480/80R26 143D/146A8 TL
- 480/80 R 26 143A8/B TL
- 380/80 R 38 142A8/B TL
- 380/80 R 38 152A8/B TL
- 380/80 R 38 154D/157A8 TL
- 480/80 R 42 151A8/B TL
- 480/80 R 42 153A8/B TL
- 480/80 R 42 169A8/B TL
- 480/80R42 151D/154A8 TL
- 480/80R42 153D/156A8 TL
- 480/80R42 169D/172A8 TL
- 420/80 R 46 151D/154A8 TL
- 420/80 R 46 159D/162A8 TL
- 480/80R46 158D/161A8 TL
- 480/80R46 164D/167A8 TL
- 480/80 R 46 158A8/B TL
- 480/80 R 46 164A8/B TL


FARMAX R85/R85 R2

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life




Higher angle and lug overlap at centre

Better roadability




Wider tread larger inner volume

Reduced soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction

SIZES

- 250/85 R 20 116A8/B TL
- 280/85 R 20 112A8/B TL
- 320/85 R 20 119A8/B TL
- 250/85 R 20 TL 116D/119A8
- 280/85R20 TL 112D/115A8
- 320/85R20 TL 119D/122A8
- 250/85 R 24 109A8/B TL
- 280/85 R 24 TL 115D/118A8
- 320/85 R 24 TL 122D/125A8
- 320/85 R 24 TL 142D/145A8
- 340/85 R 24 125A8/B TL
- 340/85 R 24 125D TL
- 380/85 R 24 131A8/B TL
- 380/85 R 24 131D TL
- 420/85 R 24 137A8/B TL
- 250/85R24 TL 109D/112A8
- 420/85R24 TL 137D/140A8
- 250/85 R 28 112A8/B TL
- 280/85 R 28 118A8/B TL
- 320/85 R 28 124A8/B TL
- 340/85 R 28 127A8/B TL
- 380/85 R 28 133A8/B TL
- 380/85 R 28 133D TL
- 420/85 R 28 139A8/B TL
- 250/85R28 TL 112D/115A8
- 280/85R28 TL 118D/121A8
- 320/85R28 TL 124D/127A8
- 340/85R28 TL 127D/130A8
- 420/85R28 TL 139D/142A8
- 380/85 R 30 135A8/B TL
- 420/85 R 30 140A8/B TL
- 420/85 R 30 140D TL
- 420/85 R 30 147A8/B TL
- 460/85 R 30 145A8/B TL
- 380/85R30 TL 135D/138A8
- 420/85R30 TL 147D/150A8
- 460/85R30 TL 145D/148A8
- 320/85 R 32 126A8/B TL
- 320/85 R 32 142A8/B TL
- 320/85 R 32 145A8/B TL
- 320/85R32 TL 126D/129A8
- 320/85R32 TL 142D/145A8
- 320/85R32 145D/148A8 TL
- 320/85 R 34 141A8/B TL
- 380/85 R 34 TL 137D/140A8
- 420/85 R 34 142A8/B TL
- 420/85 R 34 142D TL
- 420/85 R 34 TL 147D/150A8
- 460/85 R 34 TL 147D/150A8
- 460/85 R 34 TL 157D/160A8
- 320/85R34 TL 141D/144A8
- 320/85 R 36 128A8/B TL
- 340/85 R 36 132A8/B TL
- 320/85R36 TL 128D/131A8
- 340/85R36 TL 132D/135A8
- 320/85 R 38 143A8/B TL
- 340/85 R 38 133A8/B TL
- 340/85 R 38 148A8/B TL
- 340/85 R 38 151A8/B TL
- 420/85 R 38 144A8/B TL
- 460/85 R 38 149A8/B TL
- 460/85 R 38 153D/156A8 TL
- 460/85 R 38 TL 167D/170A8
- 520/85 R 38 155A8/B TL
- 520/85 R 38 169A8/B TL
- 340/85R38 TL 133D/136A8
- 320/85 R 38 143D/146A8 TL
- 340/85R38 TL 148D/151A8
- 340/85 R 38 151D/154A8 TL
- 420/85R38 TL 144D/147A8
- 460/85R38 TL 149D/152A8
- 520/85R38 TL 155D/158A8
- 520/85 R38 TL 169D/172A8
- 520/85 R 42 157A8/B TL
- 520/85 R 42 169A8/B TL
- 520/85 R 42 169D/172A8 TL
- 520/85R42 TL 157D/160A8
- 520/85 R 46 158A8/B TL
- 520/85 R 46 174A8/B TL
- 520/85R46 TL 158D/161A8
- 520/85R46 TL 174D/177A8
- 520/85 R 42 R2 157A8/B TL
- 420/85R26(16.9R26)*

*Upcoming Sizes

FARMAX R90

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life




Higher angle and lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduced soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction

SIZES

- 420/90 R 30 142A8/B TL
- 420/90R30 142D/145A8 TL
- 420/90 R 30 147A8/B TL
- 420/90R30 147D/150A8 TL

FARMAX R90 R2

For Low To Mid HP Tractors



Extra-deep tread, with curved tread bars

Better self cleaning & traction in wet soil



Flatter tread

Reduces soil compaction



Dual step tie bar

Prevents mud clogging while adding traction & side hill slip resistance



Stepped lug design

Good grip in wet & moist soil



Buttressed bar base

Better self cleaning

SIZES

- 420/90 R 30 142A8/B TL R2

MULTILOADMAX

For Multipurpose Application



Big centre block

Gives better stability on road



Unique angular grooves

Better driving comfort & self cleaning



Steel belted carcass

Uniform load distribution and good puncture & impact resistance



Robust block design

Good traction on-road & off-road



SIZES

- | | | |
|------------------------------|------------------------------|------------------------------|
| ▪ 250/80R16 123D/127A8 TL | ▪ 360/80R20 143D/147A8 TL SB | ▪ 600/70R30 166D/171A8 TL SB |
| ▪ 265/70R16.5 130A2 TL SB | ▪ 360/80R24 145D/150A8 TL SB | ▪ 440/80R34 155D/159A8 TL SB |
| ▪ 305/70R16.5 141A5 TL SB | ▪ 400/80R24 151D/156A8 TL SB | ▪ 480/80R34 159D/164A8 TL SB |
| ▪ 400/70R18 143D/147A8 TL SB | ▪ 500/70R24 159D/164A8 TL SB | ▪ 480/80R38 161D/166A8 TL SB |
| ▪ 340/80R18 138D/143A8 TL SB | ▪ 360/80R28 142D/146A8 TL SB | ▪ 710/70R42 180D/185A8 TL SB |
| ▪ 360/70R20 131D/136A8 TL SB | ▪ 400/80R28 153D/158A8 TL SB | ▪ 440/80R24* |
| ▪ 400/70R20 144D/149A8 TL SB | ▪ 440/80R28 158D/163A8 TL SB | |

*Upcoming Sizes

YIELDMAX

For Combine Harvesters



R1-W pattern

Longer tyre life




Dual lug angle

Higher traction and better stability



Higher lug overlap

Enhanced roadability and loadability



Strong and sharp shoulders

Better grip



Wide open shoulders

Better self-cleaning



Rounded lug base

Stubble resistance

SIZES

- 620/75 R 26 CHO 166A8/B TL
- 620/75 R 26 CHO 166 A8/B TL SB
- 750/65 R 26(28L R 26) 173A8/170B TL
- 620/75 R 30 CHO 169A8/B TL SB
- 650/75 R 32 CHO 172A8/B TL
- 650/75 R 32 CHO 172A8/B TL SB
- 800/65 R 32 CHO 181A8/B TL
- 800/65 R 32 CHO 181A8/B TL SB
- 900/60 R 32 193A8/B TL SB
- 1050/50 R 32 184A8/B TL SB
- 620/75 R 34 CHO 170A8/B TL SB
- 800/70R32*
- VF 1000/55R32*
- IF1250/50R32*

*Upcoming Sizes

FARMAX RC

For Row Crop



Higher angle and lug overlap at center

Better roadability and stability



Rounded shoulder

Reduced damage to soil and crops



Higher number of lugs

Superior traction

Strong carcass and bead

Higher load carrying capacity




SIZES

- 230/95 R 32 128D/131A8 TL
- 270/95 R 32 133D/136A8 TL
- 270/80R32 131D/134A8 TL
- 270/80R32 131D/134A8 TL
- 210/95 R 36 118D/121A8 TL
- 230/95 R 36 127D/130A8 TL
- 230/95 R 36 130D/133A8 TL
- 270/95 R 36 136D/139A8/B TL
- 270/95 R 38 137D/140 A8 TL
- 270/95 R 38 140D/143A8 TL
- 230/95 R 40 132D/135A8 TL
- 230/95 R 42 133D/136A8 TL
- 270/95 R 42 137D/140A8 TL
- 270/95 R 42 139D/142A8 TL
- 320/80 R 42 141A8/B TL
- 320/90 R 42 136D/139A8 TL
- 320/90 R 42 144D/147A8 TL
- 210/95 R 44 120D/123A8 TL
- 230/95 R 44 129D/132A8 TL
- 230/95 R 44 134D/137A8 TL
- 270/95 R 44 142D/145A8 TL
- 270/95 R 44 140D/143A8 TL
- 270/95 R 46 141D/144 A8 TL
- 300/95 R 46 143D/146A8 TL
- 300/95 R 46 148D/151A8 TL
- 320/90 R 46 146D/149A8 TL
- 340/85 R 46 147D/150A8 TL
- 340/85 R 46 150D/153A8 TL
- 380/90 R 46 159D/162A8 TL
- 380/90 R 46 162D/165A8 TL
- 380/90 R 46 165A8/B TL
- 320/90R46 148D/151A8 TL
- 230/95 R 48 136D/139A8 TL
- 270/95 R 48 142D/145A8 TL
- 340/85 R 48 148D/151A8 TL
- 340/85 R 48 156D/159A8 TL
- 320/90 R 50 150D/153A8 TL
- 380/105 R 50 168D/171A8 TL
- 380/90 R 50 151D/154A8 TL
- 380/90 R 50 158D/161A8 TL
- 300/95 R 52 149D/152A8 TL
- 270/95 R 54 146D/149A8 TL
- 320/90 R 54 153D/156A8 TL

FLOATMAX FT

For Tankers & Trailers




Directional lug

Superior traction




Robust centre blocks

Better stability & roadability



Wider & flatter crown

Better floating characteristics



Rounded shoulder

Lesser damage to soil & crop



SIZES

- 500/60 R 22.5 155D TL
- 500/60 R 22.5 155D TL SB
- 500/60R22.5 163D TL SB
- 560/45 R 22.5 152D TL
- 560/45 R 22.5 152D TL SB
- 560/60 R 22.5 161D TL
- 560/60 R 22.5 164D TL SB
- 580/65 R 22.5 166D TL SB
- 600/50 R 22.5 159D TL
- 600/50 R 22.5 159D TL SB
- 710/45 R 22.5 165D TL SB
- 600/55 R 26.5 165D TL
- 600/55 R 26.5 165D TL SB
- 650/55 R 26.5 178D TL SB
- 650/60 R 26.5 173D TL SB
- 650/65 R 26.5 174D TL SB
- 710/50 R 26.5 170D TL SB
- 750/45 R 26.5 170D TL SB
- 800/45 R 26.5 174D TL SB
- 850/40R26.5 173D TL SB
- 750/60 R 30.5 181D TL SB
- 710/50 R 30.5 176D TL SB
- 850/50 R 30.5 182D TL SB
- 650/65 R 30.5 176D TL SB
- 800/60 R 32 185D TL SB
- 800/40R22.5*
- 800/40R22.5*

*Upcoming Sizes

FLOATMAX RT

For Spreaders, Tankers & Trailers



Directional lug

Higher traction, comfortable ride




Robust centre blocks

Low noise and smooth run on hard surface



Flatter crown width

Larger footprint, lower compaction



Rounded shoulder

Less damage to soil and crops



Interconnected grooves

Better self-cleaning properties



SIZES

- 385/65 R 22.5 164D TL SB
- 500/60 R 22.5 155D TL SB
- 500/60R22.5 163DTL SB
- 560/45 R 22.5 152D TL SB
- 560/60 R 22.5 165D TL SB
- 560/60R22.5 169D TL SB
- 580/65 R 22.5 166D TL SB
- 650/50 R 22.5 163D TL SB
- 600/55 R 26.5 165D TL SB
- 600/55R26.5 178D TL SB
- 650/55 R 26.5 178D TL SB
- 710/50 R 26.5 172D TL SB
- 600/60R30.5 173D TL SB
- 650/65R30.5 176D TL SB
- 850/50R30.5 182D TL SB
- 710/50R30.5*
- 750/60R30.5*

*Upcoming Sizes

FLOATMAX CARGO PLUS

For Spreaders, Tankers & Trailers



Non-directional and robust lugs

High traction



Robust center blocks

Reduced noise & improved comfort on hard surfaces



Rounded shoulder

Reduced crop damage



Flat crown width

Larger footprint for improved floatation



SIZES

- 28LR26(750/65 R 26) 176D TL SB
- 620/75R26 176D TL
- VF900/65 R 32 197D TL SB

FLOATMAX VF X3

For Tankers, Trailers & Agri-trucks



Distinctive tread pattern

Superior handling and self-cleaning



Robust center block

Improved stability

Steel-belted carcass

Enhanced impact protection

VF Casing

Reduced soil compaction



SIZES

- VF560/60 R 22.5 TL SB
- VF600/55R26.5*

*Upcoming Sizes

FARM IMPLEMENT 800R

For Implements



Rib pattern

Wider footprint & lower ground pressure



Lugs with rounded shoulders

Excellent self-cleaning capabilities



Special shoulder design

Strong grip

Steel belted construction

Protection from punctures




SIZES

- 380/55 R 16.5 800R 150A8/B TL SB
- 340/60 R 16.5 800R 145A8 TL SB
- 440/55 R 18 800R 159A8/B TL SB
- 620/50R22.5 800R 161D TL SB
- 445/50R22.5 800 R 167D TL SB
- 620/40R22.5 R 154D TL SB
- 500/50R17*

*Upcoming Sizes

HI-FLEX IMPLEMENT

For Balers, Seeders & Grain Carts



Reinforced sidewall & bead

Longer tyre life



Rounded Shoulder

Less damage to soil and crops

Steel belt at crown

Puncture resistance

IF Construction

Carry heavier load at low inflation pressure



SIZES

- IF240/80R15 125D TL
- IF280/70 R 15 137D TL SB
- IF265/85R15 129D TL SB
- IF320/70 R 15 146D TL SB

LAWNMAX

For Lawn & Turf



Higher tread depth

Provides superior traction and longer life



Rounded shoulder design

Helps with low soil compaction



Lawnmax tread design

Better self-cleaning



Directional tread pattern

Minimizes wear



SIZES

- 360/70R24 122A8/B TL
- 280/70R16 112A8/B TL
- 280/70R18 114A8/B TL
- 300/70R20 110A8/B TL
- 380/70R24 125A8/B TL
- 320/85R28 124A8/B TL FB

- 340/85R28 127A8/B TL
- 220/55R12 82A8/B TL
- 240/60R12 89A8/B TL
- 215/65R14 90A8/B TL
- 200/60R15 83A8/B TL
- 260/70R18 114A8/B TL FB

- 380/70R20*
- 260/70R16*
- 420/70R24*
- 320/65R18*

*Upcoming Sizes

LOADPRO HARD SURFACE

For Telehandlers



Non-directional

For better traction and strong grip



Center of tie bar

Outstanding comfort



Higher base width

Better roadability and high traction



SIZES

- 405/70R18 147A8/B TL SB
- 460/70 R 24 159 A8/B TL SB

- 405/70R20 149A8/B TL SB
- 500/70 R 24 164A8/B TL SB

LOADPRO

For Telehandlers



Greater lug overlap and more lugs in footprint

Uniform load distribution



Extra reinforced sidewalls

Additional lateral stability



Strong bead

Better carcass strength and load carrying capacity



SIZES

- 340/80 R 18 R-4 143A8/B TL SB
- 3280/80 R 18 R-4 132A8/B TL SB
- 300/75 R 18 R-4 142A8/B TL SB
- 280/80 R 20 R-4 133A8/B TL SB
- 380/75 R 20 R-4 148A8/B TL SB
- 400/70 R 20(16.0/70R20) R-4 149A8/B TL SB
- 405/70R24 LOADPRO R-4 152A8/B TL SB
- 400/80-24 LOADPRO 162A8 TL
- 460/70 R 24(17.5LR24) R-4 159 A8/B TL SB

- 440/80-24 168A8 TL
- 440/80 R 24 R-4 161A8/B TL SB
- 500/70 R 24 (19.5LR24) R-4 164A8/B TL SB
- 480/80 R 26(18.4R26) R-4 160A8/B TL SB
- 480/80 R 26(18.4R26) R-4 167A8/B TL SB
- 440/80-28(16.9-28) 156A8 TL
- 440/80 R 28(16.9R28) R-4 156A8/B TL SB
- 500/70 R 28 R-4 164A8/B TL SB

LIFTPRO

For Telehandlers & Boom Lifters




Unique R1 pattern

Excellent traction



Deep under tread

Improved puncture resistance



Strong nylon casing & thick sidewall

High radial & lateral stability



SIZES

- 460/70 R 24 159A8/B TL
- 15.5/80-24 16PR TL

FARMAX R1

For Harvester & Tractor



Triple angle lug

Enhanced traction & roadability



High centre lug overlap & tie bar

Improved stability



SIZES

- 7.00-12 10PR TL
- 6.50-16 6PR TT
- 7.50-16 6PR TT
- 8.25-16 6PR TT
- 12.4-16 6PR TL
- 9.5-16 12PR TL
- 8-16 8PR TL
- 9.5-16 8PR TL
- 7.50-16 8PR TT
- 250/80-18 8PR TT
- 9.5-20 8PR TT
- 9.5-22 8PR TT
- 8.3-24 8PR TT
- 9.5-24 8PR TT
- 11.2-24 8PR TT
- 11.2-24 8PR TL
- 11.2-24 10PR TT
- 12.4-24 8PR TT
- 13.6-24 8PR TT
- 14.9-24 8PR TT
- 14.9-24 8PR TL
- 16.9-24 8PR TT
- 8.3-24 8PR TL
- 9.5-24 8PR TL
- 12.4-24 8PR TL
- 12.4-24 12PR TT
- 13.6-24 8PR TL
- 14.9-24 12PR TT
- 16.9-24 8PR TL
- 12.4-24 10PR TT
- 14.9-24 10PR TT
- 13.6-24 10PR TL
- 18.4-26 12PR TL
- 18.4-26 12PR TT
- 23.1-26 16PR TL
- 14.9-26 12PR TL
- 16.9-26 8PR TT
- 14.9-26 8PR TL
- 13.6-28 12PR TT
- 11.2-28 8PR TL
- 11.2-28 8PR TT
- 12.4-28 8PR TT
- 13.6-28 8PR TT
- 13.6-28 12PR TL
- 14.9-28 8PR TT
- 14.9-28 12PR TL
- 16.9-28 8PR TT
- 16.9-28 12PR TT
- 16.9-28 12PR TL
- 14.9-28 12PR TT
- 12.4-28 8PR TL
- 14.9-28 8PR TL
- 12.4-28 4PR TL
- 14.9-28 10PR TL
- 11.2-28 10PR TL
- 16.9-30 8PR TT
- 16.9-30 10PR TT
- 16.9-30 12PR TL
- 18.4-30 8PR TT
- 18.4-30 8PR TL
- 18.4-30 12PR TT
- 18.4-30 14PR TT
- 14.9-30 8PR TT
- 16.9-30 12PR TT
- 23.1-30 12PR TL
- 14.9-30 8PR TL
- 18.4-30 14PR TL
- 16.9-30 6PR TL
- 12.4-32 8PR TT
- 24.5-32 12PR TL
- 16.9-34 8PR TT
- 18.4-34 8PR TT
- 18.4-34 12PR TT
- 18.4-34 14PR TT
- 16.9-34 8PR TL
- 16.9-34 10PR TT
- 16.9-34 14PR TT
- 18.4-34 10PR TT
- 18.4-34 14PR TL
- 12.4-36 8PR TT
- 12.4-36 12PR TT
- 13.6-36 8PR TT
- 12.4-36 8PR TL
- 13.6-36 8PR TL
- 12.4-36 12PR TT
- 15.5-38 8PR TT
- 15.5-38 10PR TT
- 15.5-38 12PR TT
- 16.9-38 8PR TT
- 16.9-38 10PR TT
- 16.9-38 12PR TT
- 16.9-38 12PR TL
- 18.4-38 8PR TT
- 18.4-38 12PR TT
- 13.6-38 8PR TT
- 13.6-38 8PR TL
- 15.5-38 8PR TL
- 18.4-38 8PR TL
- 20.8-38 10PR TT
- 20.8-38 14PR TL
- 12.4-38 8PR TT
- 12.4-38 14PR TT
- 13.6-38 14PR TT
- 20.8-38 10PR TL
- 13.6-38 10PR TL
- 7.50-20 8PR TT
- 8.00-20 8PR TT
- 7.00-14*

*Upcoming Sizes

FARMAX R2

For Tractors used in Rice & Sugarcane Farming



Extra-deep tread with curved tread bars

Better self cleaning & traction in wet soil



Tie bar at the center

Strengthened lug base for better stability



Stepped lug design

Added grip in wet & moist soil



Buttressed bar base

Better self cleaning



Bolstered nose at tread center

Improved wear and performance



SIZES

- 18.4-38 12PR TL
- 14.9-24 6PR TT
- 14.9-24 8PR TT
- 18.4-26 10PR TT
- 23.1-26 10PR TT
- 14.9-28 8PR TT
- 14.9-28 10PR TT
- 23.1-30 10PR TT
- 20.8-38 10PR TT

FARMAX F2

For Implements & Tractors



3 Rib front wheel design

Easy steering

Strong nylon casing

Designed for two wheel drive tractors



SIZES

- 5.00-15
- 5.50-16
- 6.00-16
- 6.50-16
- 7.50-16
- 10.00-16
- 11.00-16
- 7.50-18
- 4.00-19
- 7.50-20

FARMAX X3 TF

For Implements & Tractors



Unique tread design with grooves on the central rib and notches in the shoulder

Superior traction



Angular & open shoulder blocks

Better self-cleaning & longer life



4-Rib pattern

Driving comfort on and off road

Superior tread compound

Resistance to chips and tears
Excellent steering ability



SIZES

- 6.50-16
- 6.00-16
- 7.50-16
- 5.50-16
- 7.50-20
- 6.50-20

FARMAX F2M

For Implements



Multi rib design

Easy steering

Cut-resistant compound

Improved tyre life



SIZES

- 10.00-16 8PR TT
- 11.00-16 8PR TT
- 10.00-16 8PR TL
- 11.00-16 8PR TL
- 11.00-16 12PR TL
- 10.00-16 10PR TL

FARMAX R1 HD

For Harvesters



Robust deep lugs

Superior haulage on all terrains



Dual-angle lug design

Optimal traction for peak performance



Open buttress design

Improved self-cleaning

Tough nylon casing

Reliable stability, puncture resistance



SIZES


▪ 18.4-26 10PR TT

▪ 23.1-26 12PR TL

▪ 18.4-38 12PR TT


YIELDMAX 23°

For Harvesters




Stepped sidewall design

Improved performance on slopes




Tie bar at the center

Strengthened lug base for better stability



23° tread Bars

Best in class traction



Buttressed bar base

Better self-cleaning

Stronger carcass

To carry heavier loads



SIZES

▪ 28L-26 12PR TL

▪ 24.5-32 12PR TL

▪ 30.5L-32 14PR TL

▪ 24.5-32 14PR TL

FARMAX AS

For Implements & Agri Utility Tractors



Robust lug design

High traction and long life

Superior tread compound

Resistance to chips and tears

Reinforced carcass

Better loadability & longer life



SIZES

- 6.5/80-12 6PR TT
- 10.0/75-15.3 10PR TL
- 23X10.50-12 12PR TL
- 11.5/80-15.3 12PR TL
- 10.0/75-15.3 14PR TL
- 5.00-10 8PR TT*

*Upcoming Sizes

FARM IMPLEMENT AWI 305

For Implements



Non directional tread pattern

Prevents skidding while turning



Lugs are open & angled at the shoulder

Ensures maximum stability



Larger footprint

Designed for agricultural use



SIZES

- 7.00-12 6PR TL
- 10.0/80-12 8PR TL
- 10.0/75-15.3 10PR TL
- 11.5/80-15.3 10PR TL
- 10.0/75-15.3 10PR TT
- 10.0/80-12 10PR TL
- 13.0/55-16 12PR TL
- 12.5/80-18 12PR TL
- 12.5/80-15.3 12PR TL
- 10.0/75-15.3 12PR TL
- 11.5/80-15.3 12PR TL
- 11.5/80-15.3 12PR TT
- 10.0/75-15.3 12PR TT
- 10.0/75-15.3 12PR TL NEW
- 13.0/55-16 14PR TL
- 12.5/80-18 14PR TL
- 10.0/75-15.3 14PR TL
- 11.5/80-15.3 14PR TL
- 10.0/75-15.3 14PR TT
- 400/60-15.5 14PR TL
- 13.0/65-18 16PR TL
- 12.5/80-18 16PR TL
- 11.5/80-15.3 16PR TL
- 11.5/80-15.3 16PR TT
- 400/60-15.5 16PR TL
- 10.0/75-15.3 18PR TL
- 12.5/80-18 18PR TL
- 13.0/55-16 18PR TL

FARM IMPLEMENT 404

For Trailers & Implements



Multi rib low section design

High flotation with minimum soil compaction



Extra wide tread & high volume

High load carrying capacity



Non directional tread pattern

Prevents skidding while turning



Lugs are open & angled at the shoulder

Ensures maximum stability



Large contact area

Designed for both on & off-road application

SIZES

- 14.0/65-16 10PR TL
- 14.0/65-16 14PR TL
- 15.0/70-18 16PR TL
- 500/50-17 10PR TL
- 15.0/55-17 14PR TL
- 15.0/70-18 16PR TL
- 15.0/55-17 10 PR TL
- 500/50-17 14PR TL
- 15.0/55-17 18 PR TL

FARM IMPLEMENT LP

For Implements



Advanced tread design

Long life



Rounded shoulder

Reduce soil compaction



Multi-rib design

Effortless steering control



SIZES

- 16.5L-16.1SL LP 10PR TL
- 16.5L-16.1SL LP 14PR TL

HIGHWAY IMPLEMENT T422

For Trailers



Higher land area

Uniform wear & longer tyre life



Heavily grooved ribs

Easy steering and overall stability of the equipment

Heavy carcass

High load carrying capacity

Specially designed compound

Suitable for higher speed



SIZES

▪ 9.5L-15FI D TL

▪ 11L-15FI F TL

▪ 12.5L-15FI F TL

FLOTATION PLUS

For Trailers



Larger volume & footprint

Reduced compaction

Rounded shoulder

Reduced damage to crops



SIZES

▪ 480/45-17 (19.0/45-17) 10PR TL

▪ 480/45-17 (19.0/45-17) 14PR TL

▪ 560/60-22.5 16PR TL

▪ 700/50-22.5 16PR TL

▪ 500/50-17 14PR TL

▪ 480/45-17 (19.0/45-17) 16PR TL

▪ 600/55-22.5 16PR TL

▪ 480/45-17 (19.0/45-17) 18PR TL

FLOTATION T422

For Trailers



Larger volume & footprint

Reduced compaction

**Tough nylon casing,
Strong bead bundle**

Improved performance on slopes

Rounded shoulder

Reduced damage to crops



SIZES

- 800/45-26.5 12PR TL
- 550/60-22.5 16PR TL
- 700/50-22.5 16PR TL
- 600/55-26.5 16PR TL
- 500/50-17 16PR TL
- 550/45-22.5 20PR TL
- 500/60-22.5 16PR TL
- 600/50-22.5 16PR TL
- 600/55-22.5 16PR TL
- 700/50-26.5 16PR TL
- 500/50-17 18PR TL
- 400/55-17.5*
- 550/45-22.5 16PR TL
- 700/40-22.5 16PR TL
- 550/60-22.5 20PR TL
- 800/45-26.5 16PR TL
- 700/40-22.5 18PR

*Upcoming Sizes

T422 VALUE PRO

For Trailers



Larger volume & footprint

Reduced compaction

Rounded shoulder

Reduced damage to crops



SIZES

- 400/60-15.5 16PR TL
- 400/55-22.5 16PR TL
- 500/45-22.5 16PR TL
- 550/60-22.5 16PR TL
- 400/60-15.5 20PR TL
- 400/55-22.5 18PR TL
- 500/60-22.5 16PR TL
- 400/55-22.5 20PR TL
- 400/55-22.5 12PR TL
- 500/45-22.5 12PR TL
- 550/45-22.5 16PR TL

FLOTATION TX440

For Trailers & Excavators



Larger volume & footprint

Reduced compaction

Rounded shoulder

Reduced damage to crops



SIZES

- 500/60-22.5 16PR TL
- 550/60-22.5 16PR TL
- 600/50-22.5 16PR TL
- 700/40-22.5 16PR TL
- 600/50-22.5 18PR TL
- 700/40-22.5 18PR TL

TR800

For Implements



Rounded shoulder

Reduced damage to crops



Larger volume & footprint

Reduced compaction



SIZES

- 400/60-15.5 14PR TL
- 400/60-15.5 18PR TL

IRROGATOR

For Irrigation Machines



Optimised lug angle with lug overlap

Uniform wear

Strong nylon casing

Excellent stability & increased service life



SIZES

- 11.2-24 4PR TT
- 11.2-24 6PR TL
- 11.2-38 6PR TT
- 11.2-38 6PR TL
- 14.9-24 6PR TL
- 14.9-24 8PR TT


TURF XL

For Turf & Utility Tractor




More rubber on the contact surface

Better performance in all soil and turf conditions



High tread depth

Better performance in all soil and turf conditions



Unique rounded shoulder block design

No turf damage and ease while turning



Enlarged contact area

Improving stability and traction



SIZES

- 26X12.00-12 4PR TL
- 26X12.00-12 10PR TL
- 23X8.50-12 6PR
- 13.6-16 4PR TL
- 23X10.50-12 8PR TL
- 26X12.00-12 12PR TL
- 24X8.5-14 4PR TL
- 38X14-20 4PR TL
- 26X12.00-12 8PR TL
- 23X8.50-12 4PR
- 25X8.5-14 6PR TL

LOGGER XL

For Forestry Log Skidder




Strong and straight lugs

High traction across all surfaces



Reinforced sidewall & shoulder deflector

Protection against impacts & cuts



Deep and open shoulder

Better self cleaning



Rim protector

Protects bead against stub damage



Multi-layer Nylon carcass with wide steel breakers

Excellent puncture resistance

SIZES


▪ 23.1-26 16PR TT STEEL SHIELD

▪ 28L-26 20PR TL

▪ 30.5L-32 26PR TL

FOREST XL

For Forwarder & Harvester



Wide & robust Lug Design

Excellent traction & support for track use



Larger tread Width

Ensures wider footprint resulting in low ground pressure

Steel belted construction

Superior puncture resistance & load carrying capacity

Uniquely designed bead area

Prevents rim slippage



Specially designed tread and sidewall compound

Provides protection to the tyre from cuts & tears and durability in rough terrain

SIZES

▪ 710/45-26.5 20PR TL STEEL SHIELD

GM LOADER HD

For Skid Steer



Higher tread depth with extra thick sidewall

Improved traction & puncture resistance

Strong nylon casing

Excellent durability

Specially designed rim guards

Greater protection of rim flange area



SIZES

▪ 10-16.5 10PR TL

▪ 12-16.5 12PR TL

▪ 12-16.5 14PR TL

▪ 27x10.50-15NHS*

*Upcoming Sizes


GRIP X HD

For Skid Steer



Multi-use tread pattern

Heavy duty service



Extra deep tread

Long tyre life

Specially formulated compound

Cut & chip resistance

Strong nylon casing

Excellent durability



Specially designed rim guards

Greater protection of rim flange area

SIZES

▪ 10-16.5 12PR TL

▪ 12-16.5 14PR TL

GRIP XL 5

For Skid Steer



High abrasion-resistant compound

Enhanced durability



Deep treads

Better longevity



Broad lugs

Superior stability and improved self-cleaning



Specially designed rim guard

Protection against flats and rim flange damage



Strong nylon casing

Improved lateral stability

SIZES

- 10-16.5 NHS 5 10PR TL
- 12-16.5 5 12PR TL

LOADER PRO HD

For Skid Steer



Solid centre lug with

Deep shoulders



Deeper tread depth

Excellent traction & puncture resistant

Strong nylon casing

Excellent durability

Step down lugs

Self cleaning

Rim guard

Cut & chip resistant



Skid steer for industrial & construction applications

Heavy duty service

SIZES

- 14-17.5 14PR TL
- 15-19.5 6PR TL
- 15-19.5 14PR TL

MPT 503

For Multipurpose Tractor & Telehandler



Special tread pattern

Excellent traction



Extra sidewall

Prevents sidewall damage



Tie bar

Enhanced stability



Wider tread width

Better performance



SIZES

▪ 18-19.5 16PR TL

▪ 18-19.5 18PR TL

▪ 18-22.5 16PR TL

MPT 602

For Multipurpose Tractor, Excavator & Dumper

Wide diagonal lug design

Excellent traction & improved stability

Strong nylon casing

High load carrying capacity

Specially formulated compound

Heat, cut & weather resistance



SIZES

▪ 12.5-18 12PR TL

▪ 10.00-20 16PR TT

▪ 405/70-20 20PR TL

▪ 12.5-18 16PR TL

▪ 405/70-20 14PR TL

▪ 405/70-24 14PR TL

▪ 12.5-20 12PR TL

▪ 405/70-20 18PR TL

▪ 405/70-24 16PR TL

MPT 800

For Telehandler & Loader



Superior tread compound

Cut & chip resistance

Robust casing

Better lateral stability



SIZES

■ 405/70-20 14PR TL

■ 405/70-24 14PR TL

■ 405/70-24 16PR TL

MPT 808

For Multipurpose Tractor & Telehandler



Specially designed wide lugs

Better self-cleaning



Superior tread compound

Resistance to tearing & cracking

Strong nylon casing

Higher strength and stability



SIZES

■ 10.0/75-15.3 14PR TL

■ 12.0/75-18 12PR TL

■ 10.5-20 12PR TL

■ 18-19.5 18PR TL

■ 11.5/80-15.3 14PR TL

■ 12.5-18 12PR TL

■ 12.5-20 12PR TL

■ 405/70-20 18PR TL

■ 12.0-18 12PR TL

■ 10.5-18 12PR TL

■ 14.5-20 14PR TL

TYROCK

For Backhoe loader & Wheel Loader



Wider lugs

Offers excellent traction

Unique tread pattern

Specially designed for front wheel of Backhoe Loaders and Wheel Loaders

Strong Nylon Casing

High load carrying capacity

Industrial tread compound

Cut & chip resistance



SIZES

- 12.5/80-18 12PR IND TT
- 12.5/80-18 10PR TL
- 19.5L-24 12PR 80 TL
- 18.4-26 16PR R4 TL
- 12.5/80-18 12PR IND TL
- 12.5/80-18 18PR IND TL
- 18.4-26 12PR R4 TL
- 12.5/80-18 14PR IND TL
- 19.5L-24 10PR 80 TL
- 18.4-26 14PR R4 TL

TYROCK SUPER

For Backhoe loader & Telehandler



Open shoulders

Improved self-cleaning



Specially designed tread with heavy center mass

Heavy duty service



Large wide centre lugs

Excellent ground contact for maximum stability



Heat & cut resistant compound

Improved product life

SIZES

- 16.9-28 8PR TL
- 16.9-28 12PR TL
- 16.9-28 14PR TL
- 16.9-30 14PR TL

TYROCK SUPER X3

For Backhoe loader, Telehandler, Compact Utility Tractors



Specially designed tread with heavy center mass

Suitable for heavy duty service



Extra deep tread with special compound

Resistance to cuts and chipping
Higher durability



Extra deep thread

Higher Durability



SIZES

- 26x12.00-12 4PR TL
- 23X8.5-14 4PR TL
- 12.4-16 4PR TL
- 16.0/70-20 (400/70-20) 16PR TL
- 43x16.00-20 4PR TL
- 16.9-24 (440/80-24) 12PR TL
- 17.5L-24 12PR TL
- 19.5L-24 12PR TL
- 18.4-28 12PR TL
- 23X8.50-12 12PR TL
- 27X8.5-15 6PR TL
- 10.5/80-18 8PR TL
- 15-19.5 6PR TL
- 16.9-24 (440/80-24) 8PR TL
- 17.5L-24 8PR TL
- 18.4-24 12PR TL
- 440/80-24(16.9-24) 18PR TL

GRIP MASTER EX

For Excavator



Wide diagonal lug design

Excellent traction & improved stability

Strong nylon casing

High load carrying capacity

Specially formulated compound

Heat, cut & weather resistance



SIZES

- 9.00-20 14PR TT E-2
- 8.25-20 14PR TT E-2
- 10.00-20 16PR TT E-2
- 11.00-20 16PR TT E-2

GRADER XL

For Grader, Loader



Superior tread & sidewall compound

Heat, cut & weather resistant

Sturdy & robust tyre for the drive wheel application

Smooth & trouble-free service in severe conditions

Strong nylon casing

High loadability



SIZES

- 13.00-24 12PR G2/L2 TL
- 13.00-24 16PR G2/L2 TL
- 14.00-24 12PR G2/L2 TL
- 14.00-24 16PR G2 TL
- 17.5-25 12PR G2/L2 TL
- 17.5-25 16PR G2/L2 TL
- 17.5-25 24PR TL G2/L2


GRADER XL PLUS

For Grader, Loader



More number of lugs

Provides better traction



Strong carcass

Reduces mechanical failure

Specially formulated compound

Heat, cut & weather resistant



SIZES

- 13.00-24 16PR PLUS G2/L2 TT

GRIP MASTER-ND

For Grader Backhoe Loader, Dump Truck



Sturdy & robust tyre for the drive wheel application

Smooth & trouble-free service in severe conditions

Superior tread & sidewall compound

Heat, cut & weather resistant

Strong nylon casing

High loadability



SIZES

- | | | |
|---------------------------|---------------------------|------------------------------|
| ▪ 14.00-24 24PR E3 TT | ▪ 14.00-24 28PR E3 TT | ▪ 14.00-24 16PR GRADER G3 TT |
| ▪ 14.00-24 28PR E3 IND TT | ▪ 14.00-24 28PR E3 IND TL | ▪ 14.00-25 12PR L3 TT |
| ▪ 14.00-25 20PR E3 TT | ▪ 14.00-25 20PR L3 TT | ▪ 14.00-25 20PR E3 TL |
| ▪ 14.00-25 24PR E3 TT | ▪ 18.00-25 32PR E3 TL | ▪ 18.00-25 40PR E3 TL |
| ▪ 18.00-25 40PR E3 IND TL | | |

LOADER XL

For Loader



R4 tread pattern

Suitable on & off the road



Tough wide base

Excellent traction & handling response

Superior compound

Designed for crane & rescue vehicles

Strong nylon casing

Capable to run at high speeds



SIZES

- | | | |
|-------------------------|-------------------------|-----------------------------|
| ▪ 15.5-25 12PR G2/L2 TL | ▪ 17.5-25 12PR G2/L2 TL | ▪ 17.5-25 16PR G2/L2 TL |
| ▪ 20.5-25 12PR G2/L2 TL | ▪ 20.5-25 16PR G2/L2 TL | ▪ 17.5-25 16PR TL DUAL BEAD |
| ▪ 17.5-25 G 16PR TL | ▪ 17.5-25 24PR TL L2 | |

TRAC XL

For Articulated Dump Truck & Loader



Wide centre lugs

Excellent ground contact for maximum stability



Non direction tread pattern

Excellent traction & grip

Specially formulated compound

Provides heat resistance & cut protection



SIZES

- 405/70-20 16PR TL
- 17.5-25 20PR E3/L3 TL
- 23.5-25 20PR E3/L3 TL
- 29.5-25 32PR E3/L3 TL
- 17.5-25 16PR E3/L3 TL
- 17.5-25 32PR E3/L3 TL
- 26.5-25 24PR TL
- 17.5-25 20PR E3/L3 TT
- 23.5-25 20PR E3/L3 TT
- 26.5-25 28PR E3/L3 TL

C305

For Compactor



Strong nylon casing & increased tread depth

Flat & wide footprint makes it suitable for industrial & road construction applications

Rugged design for multipurpose drive wheel tyre

Provides higher flotation on soft soil with minimum ground disturbance

High modulus compound

Longer service life in several operating conditions



SIZES

- 23.1-26 12PR R3 TL IND
- 23.1-26 16PR R3 TL IND
- 23.1-26 18PR TL DUAL BEAD

LOADPRO

For Telehandler



Greater lug overlaps and more lugs in footprint

Uniform load distribution

Extra reinforced Sidewalls

Additional lateral stability

Strong bead

Better carcass strength and load carrying capacity



SIZES

- 400/80-24 162A8 TL
- 440/80-24 168A8 TL
- 440/80-28(16.9-28) 156A8 TL

ROCK XL

For Dump Truck



Strong bead bundle

Minimized bead failure



Higher under tread

Resistance to puncture

Strong nylon casing

High load carrying capacity

Specially formulated compound

Resistance to cuts, snags & bruises



SIZES

- 18.00-25 40PR E4 TL
- 18.00-25 40PR IND TL
- 21.00-35 36PR E4 TL
- 21.00-25 40PR E4 TL
- 18.00-33 40PR E4 TL
- 24.00-35 48PR E4 TL
- 16.00-25 32PR E3 IND TL
- 18.00-33 40PR E4 IND TL

GRIP MASTER XL

For Dump Truck



Extra deep tread & robust casing

Ideal for heavy duty application in mining, quarrying & rock excavation

Strong nylon casing

High load carrying capacity

Specially formulated compound

Heat, cut & weather resistance



SIZES

▪ 18.00-25 32PR E4 TL

PORT PRO RX

For Reach Stacker



Strong bead bundle

Minimized bead failure



Higher under tread

Resistance to puncture

Specially formulated compound

Resistance to cuts, snags & bruises

Strong nylon casing

High load carrying capacity



SIZES

▪ 18.00-25 40PR IND4 TL

▪ 18.00-33 40PR IND4 TL

PORT PRO TX

For RTG Crane



Larger footprint

High ground contact area with improved stability



Higher under tread

Resistance to puncture

Strong nylon casing

High load carrying capacity

Specially formulated compound

Resistance to cuts, snags & bruises



SIZES

▪ 18.00-25 40PR IND3 TL

▪ 21.00-25 40PR IND3 TL

▪ 21.00-35 40PR IND3 TL

PORT XL PLUS

For Reach Stacker



Better resistance to puncture and impact due to deep tread depth and under tread

Extra deep tread promotes longer life

Carries heavy loads under extreme working conditions

Special wear resistant compound gives extra life

Ideal for heavy duty application at ports and container handling application on hard and improved surfaces like concrete and asphalt

Can also be used for intermittent highway surface



SIZES

▪ 18.00-25 40PR IND4.5 TL

PORT PRO SL

Reach Stacker



Flat tread with large width

Self cleaning properties

Specially formulated tread compound

High ground contact area for good traction on paved surface

Reinforced sidewall

Improved penetration resistance



SIZES

■ 18.00-25 40PR IND4 TL

■ 18.00-25 40PR IND5 TL

■ 18.00-33 40PR IND4 TL

SLICK 404

For RTG Crane & Reach Stacker



Reinforced Sidewall

Long service life



Flatter & larger tread width

Higher ground contact area & traction

Specially formulated tread compound

Improved penetration and heat resistance



SIZES

■ 14.00-24 28PR L5S IND TT

■ 18.00-25 40PR L5S IND5 TL

SLICK 431

For RTG Crane



Reinforced Sidewall

Long service life



Flatter & larger tread width

Higher ground contact area & traction

Specially formulated tread compound

Improved penetration and heat resistance



SIZES

- 16.00-25 32PR L4S IND TL

ELEVETA X3

For Forklift



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



SIZES

- | | | |
|---|---|---|
| <ul style="list-style-type: none"> 5.00-8 NHS 10PR TT 6.50-10 NHS 14PR TT 7.00-12 NHS 14PR TT 8.25-15 NHS 16PR TT 7.50-16* 21x8-9NHS* | <ul style="list-style-type: none"> 6.00-9 NHS 10PR TT 6.50-10 NHS 10PR TT 28X9-15(8.15-15) NHS 14PR TT 7.00-15 NHS 12PR TT 18x7-8NHS* 250-15 16PR TT* | <ul style="list-style-type: none"> 6.50-10 NHS 12PR TT 7.00-12 NHS 12PR TT 8.25-15 NHS 14PR TT 7.50-15 NHS 12PR TT 5.00-8 10PR* 300-15 20PR TT* |
|---|---|---|

*Upcoming Sizes

ELEVETA PLUS

For Heavy Duty Forklift



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



SIZES

- 11.00-20 18PR TT
- 12.00-20 20PR TT

- 9.00-20 14PR TT
- 12.00-20 28PR TT

- 10.00-20 16PR TT

LOAD INDEX & SPEED SYMBOL

According to ETRTO (The European Tyre & Rim Technical Organization), as well as to ECE (Economic Commission for Europe-UN Institution Geneva), the maximum load capacity, as well as the maximum speed are indicated by load index & speed symbol.

The following table shows the meaning of each speed symbol & the load in kg/lbs corresponding to each load index:

Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Speed Symbol	Kmph / mph
102	850 / 1874	129	1850 / 4078	156	4000 / 8818	183	8750 / 19290	A1	5 / 3
103	875 / 1929	130	1900 / 4189	157	4125 / 9094	184	9000 / 19841	A2	10 / 6
104	900 / 1984	131	1950 / 4299	158	4250 / 9369	185	9250 / 20392	A3	15 / 9
105	925 / 2039	132	2000 / 4409	159	4375 / 9645	186	9500 / 20944	A4	20 / 12
106	950 / 2094	133	2060 / 4541	160	4500 / 9921	187	9750 / 21495	A5	25 / 16
107	975 / 2149	134	2120 / 4674	161	4625 / 10196	188	10000 / 22046	A6	30 / 19
108	1000 / 2205	135	2180 / 4806	162	4750 / 10472	189	10300 / 22707	A7	35 / 22
109	1030 / 2271	136	2240 / 4938	163	4875 / 10747	190	10600 / 23369	A8	40 / 25
110	1060 / 2337	137	2300 / 5071	164	5000 / 11023	191	10900 / 24030	B	50 / 31
111	1090 / 2403	138	2360 / 5203	165	5150 / 11354	192	11200 / 24691	C	60 / 37
112	1120 / 2469	139	2430 / 5357	166	5300 / 11684	193	11500 / 25353	D	65 / 40
113	1150 / 2535	140	2500 / 5511	167	5450 / 12015	194	11800 / 26014	E	70 / 44
114	1180 / 2601	141	2575 / 5677	168	5600 / 12346	195	12150 / 26786	F	80 / 48
115	1215 / 2679	142	2650 / 5842	169	5800 / 12787	196	12500 / 27557	G	90 / 56
116	1250 / 2756	143	2725 / 6007	170	6000 / 13228	197	12850 / 28329	J	100 / 62
117	1285 / 2833	144	2800 / 6173	171	6150 / 13558	198	13200 / 29101	K	110 / 68
118	1320 / 2910	145	2900 / 6393	172	6300 / 13889	199	13600 / 29982	L	120 / 75
119	1360 / 2998	146	3000 / 6614	173	6500 / 14330	200	14000 / 30864	M	130 / 81
120	1400 / 3086	147	3075 / 6779	174	6700 / 14771	201	14500 / 31966	N	140 / 87
121	1450 / 3197	148	3150 / 6944	175	6900 / 15212	202	15000 / 33069	P	150 / 93
122	1500 / 3307	149	3250 / 7165	176	7100 / 15653	203	15500 / 34171	Q	160 / 99
123	1550 / 3417	150	3350 / 7385	177	7300 / 16093	204	16000 / 35273	R	170 / 106
124	1600 / 3527	151	3450 / 7606	178	7500 / 16534	205	16500 / 36376	S	180 / 112
125	1650 / 3638	152	3550 / 7826	179	7750 / 17086	206	17000 / 37478		
126	1700 / 3748	153	3650 / 8047	180	8000 / 17637	207	17500 / 38580		
127	1750 / 3858	154	3750 / 8267	181	8250 / 18188	208	18000 / 39683		
128	1800 / 3968	155	3875 / 8543	182	8500 / 18739	209	18500 / 40785		



www.ceatspecialty.com