hydraBOND®
REFINISH

AUTOMOTIVE FINISH CATALOG

CATÁLOGO DE ACABADOS AUTOMOTRICES

PROFESSIONAL

SOLUTIONS FOR CAR REFINISHING!

¡SOLUCIONES PARA EL REACABADO DE COCHES!

hydraBOND®_Refinish-Catalog_No.EN-08152024-V.04



PRODUCT CATALOGUE

CB +plus™

ADHESION PROMOTER

LAUNCH MOBILE SITE

Made In Japan





Fields

- **Compatible With WATER And SOLVENT Base-coat Systems!**
  Es compatible con pintura bicapa con base al agua y disolvente!
- **Complies with SCAQMD Rule 1151**
  Cumple con la (norma 1151 S.C.A.Q.M.D. en Los Estados Unidos)
- **Ready to Paint in 3-10 Minutes**
  Listo para pintar en 3-10 minutos
- **Makes Paint Stick to PLASTIC BUMPERS**
  Hace que la pintura se pegue a los parachoques de plástico

✓ HB6681D 200 LITERS DRUM
Pallet with 4 drums of 200 liters
Pallet Weight: 1600lbs (725kg)
Pallet Dim. Inches: 42" x 42"
Pallet Dim. cm: 106.68 x 106.68 cm

✓ HB6681 1 GAL. 128OZ
4 gallon jugs/case,
Box Weight: 33 lbs (15 kg)
Box Dim. Inches: 13.5" x 8.5" x 10.5"
Box Dim. in cm: 34.29 x 21.59 x 26.67 cm

✓ HB6674 Quart. 32 ounces
6 ¼ Gallon Cans/Case
Box Weight: 13 lbs (5.8kg)
Box Dim. Inches: 10.875" x 8 .125" x 9.5"
Box Dim. in cm: 27.62x20.96x23.50 cm

✓ HB6711 14 OUNCE SPRAY
12 Aerosol Cans of 14 oz (396.8grams) per Box
Box Weight: 14 lbs (6.35 kg)
Box Dim. Inches: 11.25" x 8.5" x 10"
Box Dim. in cm: 28.58 x 20.96 x 25.4 cm

✓ HB6681D TAMBOR DE 200 LITROS
Paleta con 4 tambores de 200 litros
Peso de Paleta: 1600lbs (725kg)
Dim. de Paleta Inches: 42" x 42"
Dim. de Paleta cm: 106,68 x 106,68 cm

✓ HB6681 1 GALÓN. 128OZ
4 botes de un galón/caja,
Peso De la Caja: 33 lbs (15 kg)
Dim. De la Caja Inches: 13.5" x 8.5" x 10.5"
Dim. De la Caja in cm: 34,29 x 21,59 x 26,67 cm

✓ HB6674 Cuarto GALÓN. 32 onzas
6 botes de un ¼ de galón/Caja
Peso De la Caja:13 lbs (5.8kg)
Dim. De la Caja Inches: 10.875" x 8 .125" x 9.5"
Dim. De la Caja in cm: 27,62x20,96x23,50 cm

✓ AEROSOL HB6711 DE 14 ONZAS
12 Botes de aerosol de 14 oz (396.8grams) por Caja
Peso De la Caja:14 lbs (6,35 kg)
Dim. De la Caja Inches: 11,25" x 8,5" x 10"
Dim. De la Caja in cm: 28,58 x 20,96 x 25,4 cm

⚠ **ADVERTENCIA**: Este producto puede exponerlo a productos químicos, que el estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite *www.P65Warnings.ca.gov*. Por favor consulte la Ficha de Datos de Seguridad. Se recomienda encarecidamente utilizar equipo de protección personal adecuado durante la aplicación.

hydraBOND® refinish

S+plus™

From JAPAN NEW! 5 in ONE! Nano Technology!



S+Plus Concentrate

S+Plus Is a fluid, single component
ADHESION PROMOTER primer that is very easy to apply

MUST BE REDUCED 1:1 WITH 100% VIRGIN ACETONE

MAIN FEATURES

- Superior Adhesion For A Strong And Long Lasting Repair
- Saves Time And Money - No Adhesion Promoter Necessary

Compatible With:

- Tile & Ceramics
- Problematic Plastics
- PPO & LDPE
- Polypropylene
- Zinc & Magnesium
- Stainless Steel
- Aluminum & Glass
- Hot Dip Galvanized Steel
- Chrome Plating
- Leather Wood & Vinyl

LAUNCH MOBILE SITE

Made In Japan

- **Self Etching Primer**
- **Primer Sealer**
- **Flexible Primer**
- **DTM "Direct to Metal"**
- **Primer Surfacer**

SHAKE WELL BEFORE SPRAYING
Complies With
SCAQMD Regulations 1151 In California
see TDS & SDS for information

✓ **HB6964 S+Plus 1 Gal (3.79 L)**
4/1 Gal/Case, Wt: 44 lb (19.96 kg)
Case Dim.: 13.5"x13.5"x7.75" (34.2x34.2x19.1cm)

✓ **HB6827 S+Plus 1/4 gal (946.4 ml)**
6/1quart/Case, Wt: 12.5 lb (5.6 kg)
Case Dim: 12.875"X8.5"X5" (32.7x21.6x12.7 cm)

✓ **HB6964D S+Plus 200 Liters/Drum!**
4x200 Liter Drums@605 lb/Drum (274.42 kg)
Total Weight: 2420 (1,097.69 kg)
Pallet Dim: 42"X42" (106.68x106.68 cm)

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

S+Plus es un fluido monocomponente Imprimación con
PROMOTOR DE ADHESIÓN de muy fácil aplicación

¡DEBE REDUCIRSE 1:1 CON ACETONA 100% VIRGEN!

PRINCIPALES CARACTERÍSTICAS

- Adhesión superior para una fuerte Y reparación duradera
- Ahorra tiempo y dinero - No se necesita promotor de adhesión

COMPATIBLE CON:

- Azulejos y Cerámica
- Plásticos problemáticos
- PPO y LDPE
- Polipropileno
- Zinc y magnesio
- Acero inoxidable
- Aluminio y Vidrio
- Acero Galvanizado en Caliente
- Revestimiento de cromo
- Cuero Madera y Vinilo

Andas de prisa o en la carrera?

LANZAR DESCRIPCIÓN DEL SITIO MÓVIL

Hecho En Japón

- **Imprimación Autograbante**
- **Sellador De Imprimación**
- **Imprimación flexible**
- **DTM "Directo a Metal"**
- **Aparejo De Imprimación**

¡AGITAR BIEN ANTES DE USAR!
Cumple con las regulaciones
1151 de SCAQMD en California
Consulte TDS y SDS para obtener información

✓ **HB6964 S+Plus 1 Galón (3,79 L)**
4/1 gal/caja, peso: 44 lb (19,96 kg)
Dimensiones de la caja:
13,5"x13,5"x7,75" (34,2x34,2x19,1 cm)

✓ **HB6827 S+Plus 1/4 galón (946,4 ml)**
6/1 cant./caja, Peso: 12,5 lb (5,6 kg)
Dimensiones de la caja:
12,875"X8,5"X5" (32,7x21,6x12,7 cm)

✓ **HB6964D S+Plus 200 litros/Tambor!**
4 tambores de 200 litros a 605 lb/tambor (274,42 kg)
Peso total: 2420 (1.097,69 kg)
Dimensiones de la tarima: 42"X42" (106,68x106,68 cm)

⚠ **ADVERTENCIA**: Este producto puede exponerlo a productos químicos, que el estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite *www.P65Warnings.ca.gov.* Por favor consulte la Ficha de Datos de Seguridad. Se recomienda encarecidamente utilizar equipo de protección personal adecuado durante la aplicación.

hydraBOND® refinish

HB 777 Series

euro clearcoat

Premium Clear coat



DESCRIPTION

HB777 EURO CLEAR: 2:1:1, 2.1 VOC, Made with the highest quality European-style resins, HB777 euro clear 2.1 VOC offer performance in a range of formulations to suit a variety of shop conditions and specialized applications.

ADVANTAGES

- 5 Liter Can Produces 33% More Material Than Standard U.S. Gallon.
- U.V. resistant high build finish with excellent gloss retention
- Can be applied over most water and solvent borne basecoat paint systems
- Excellent scratch and abrasion resistance
- Excellent flow and non-sag properties
- Easy to apply - can be used for spot, panel or overall repairs
- Air dry, low bake or IR cure
- Easy to sand and buff
- Excellent Build (Over 50% Solids)
- VOC 2.1 lbs./gal. - 250 gms./ltr.

((When Using Low VOC Activator and Reducer)

PRODUCT DETAILS

- High Quality "Euro"Finish
- Exceptional Gloss And DOI
- Superior Flow-Out
- MIX RATIO 2:1:1

or Reduce as per painters' consistency requirements

- Unsurpassed Quality

On the run?
LAUNCH MOBILE SITE

✓ **HB777 euro clear: 2:1:1 VOC 2.1**
4-5L/Case, Wt: 51 Lbs (2.32 kg), Dim: 13 ¼"x8¼"x12¼"

✓ **B774 euro FAST ACTIVATOR**
4-2.5L/Case, Wt: 26 Lbs (11.79 kg), Dim: 17¼"x7"x7¼"

✓ **HB775 euro MEDIUM ACTIVATOR**
4-2.5L/Case, Wt: 28 Lbs (12.7 kg), Dim: 17¼"x7"x7¼"

✓ **HB776 euro SLOW ACTIVATOR**
4-2.5L/Case, Wt: 29 Lbs (13.2 kg), Dim: 17¼"x7

DESCRIPCIÓN

HB777 euro clear: 2:1:1 COV 2.1 Es fabricado con resinas de estilo europeo de la más alta calidad, HB777 euro clear 2.1 COV ofrece rendimiento en una gama de formulaciones para adaptarse a una variedad de condiciones de taller y aplicaciones especializadas.

VENTAJAS

- La lata de 5 litros produce un 33% más de material que el galón estándar de EE. UU.
- Acabado resistente al U.V. y con excelente retención de brillo
- Se puede aplicar sobre la mayoría de los sistemas de pintura-base de base agua y solvente
- Excelente resistencia a los arañazos y a la abrasión.
- Excelente flujo y propiedades antideslizantes
- Fácil de aplicar: se puede usar para reparaciones de manchas, paneles o en general
- Secado al aire, bajo horneado o curado IR
- Fácil de lijar y pulir
- Excelente construcción (más del 50% de sólidos)
- VOC 2.1 lbs./gal. - 250 gms./ltr.

(Cuando se utiliza el activador y reductor de bajo COV)

DETALLES DE PRODUCTO

- Acabado "Euro" de alta calidad
- Brillo y DOI excepcionales
- Flujo de salida superior
- PROPORCIÓN DE MEZCLA 2:1:1

o Reducir según los requisitos de consistencia de los pintores

- Calidad insuperable

Andas de prisa o en la carrera?
LANZAR DESCRIPCIÓN DEL SITIO MÓVIL

✓ **HB777 euro clear: 2:1:1 VOC 2.1**
4-5L/Caja, Peso: 51 Lbs (2.32 kg), Dim: 13¼"x8¼"x12¼"

✓ **HB774 euro ACTIVADOR RÁPIDO**
4-2.5L/Caja, Peso: 26 Lbs (11.79 kg), Dim: 17¼"x7"x7¼"

✓ **HB775 euro ACTIVADOR MEDIO**
4-2.5L/Caja, Peso: 28 Lbs (12.7 kg), Dim: 17¼"x7"x7¼"

✓ **HB776 euro ACTIVADOR LENTO**
4-2.5L/Caja, Peso: 29 Lbs (13.2 kg), Dim: 17¼"x7"x7¼

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

hydraBOND® refinish

HB™ SERIES Autoclear



Production Clear coat

On the run?
LAUNCH MOBILE SITE

DESCRIPTION:
HB SERIES 4:1 AUTOCLEAR CLEARCOAT, 2.1 VOC Is a premium automotive production clear coat, designed to achieve significantly firm hardness, which is required in certain areas requiring low VOC properties.

ADVANTAGES
- U.V. resistant high build finish with excellent gloss retention
- Can be applied over most water and solvent borne basecoa paint systems
- Excellent scratch and abrasion resistance
- Excellent flow and non-sag properties
- Easy to apply - can be used for spot, panel or overall repairs
- Easy to sand and buff
- VOC 2.1 lbs./gal. - 250 gms./ltr.

(When Using Low VOC Activator and Reducer)

PRODUCT DETAILS
- High Quality Finish
- Exceptional Gloss And DOI
- Superior Flow-Out
- Mix Ratio: 4:1 **(Optional, 0–5% HB781 - 777 Series Medium Reducer)**

✓ **HBC21 HB SERIES AUTOCLEAR CLEAR-COAT**
4 1 Gal/Case, Wt: 36.5 Lbs (16.6 kg), Dim: 13.25"x8.5"x10.5"

✓ **HB065 HB SERIES AUTOCLEAR FAST ACTIVATOR**
4 Quarts/Case, Wt: 8 Lbs (3.6 kg), Dim: 7"x7"x8"

✓ **HB075 HB SERIES AUTOCLEAR MEDIUM ACTIVATOR**
4 Quarts/Case, Wt: 9 Lbs (4 kg), Dim: 7"x7"x8"

✓ **HB085 HB SERIES AUTOCLEAR SLOW ACTIVATOR**
4 Quarts/Case, Wt: 10 Lbs (4.53 kg), Dim: 7"x7"x8"

DESCRIPCIÓN:
El HB Series TRANSPARENTE AUTOCLEAR 4: 1 2.1 VOC
Es una capa transparente de producción automotriz premium, diseñada para lograr una dureza significativamente firme, que se requiere en ciertas áreas que requieren propiedades de bajo COV.

VENTAJAS
- Acabado resistente al U.V. con excelente retención de brillo
- Se puede aplicar sobre la mayoría de los sistemas de pintura base de base agua y solvente
- Excelente resistencia a los arañazos y a la abrasión
- Excelente flujo y propiedades antideslizantes Fórmula no deformable
- Fácil de aplicar: Para el pintado de pequeñas piezas , pequeñas áreas de reparación o retoques.
- Secado al aire, bajo horneado o curado IR (Infra rojo)
- Fácil de lijar y pulir
- VOC 2.1 lbs./gal. - 250 gms./ltr.

(Cuando se utiliza el activador y reductor de bajo COV)

DETALLES DEL PRODUCTO
- Acabado de alta calidad
- Excepcional brillo y Distinción de Imagen Reflectiva
- Flujo superior
- Proporciones de Mezcla: 4:1

Opcional: 0-5% HB781 - Series 777 Reductor Medio

Andas de prisa o en la carrera?
LANZAR DESCRIPCIÓN DEL SITIO MÓVIL

✓ **HBC21 CAPA TRANSPARENTE AUTOCLEAR (SERIES HB)**
4 1 Gal/Caja, Peso: 36,5 Lb (16,6 Kg), Dim: 13,25"X8,5"X10,5"

✓ **HB065 ACTIVADOR RÁPIDO AUTOCLEAR (SERIES HB)**
4 1 Gal/Caja, Peso: 36,5 Lb (16,6 Kg), Dim: 13,25"X8,5"X10,5"

✓ **HB075 ACTIVADOR MEDIO AUTOCLEAR (SERIES HB)**
4 Cuartos/Caja, Peso: 9 Lb (4 Kg), Dim: 7"X7"X8"

✓ **HB085ACTIVADOR LENTO AUTOCLEAR (SERIES HB)**
4 Cuartos/Caja, Peso: 10 Lb (4,53 Kg), Dim: 7"X7"X8"

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

hydraBOND® refinish

Base-Coats & Binder

HB™ SERIES



Base Coat

DESCRIPTION

A base coat VOC-compliant, solvent-borne base coat designed for overall repairs to OEM base coat/ clear coat finishes.It delivers excellent color accuracy, easy blending, and excellent coverage.

FEATURES

- Excellent color accuracy
- Easy to blend
- Excellent coverage

PRODUCT DETAILS

- Type Base coat
- Technology Urethane
- VOC 3.5 lb/gal (420 g/l)

Refer to the technical datasheet

AVAILABLE SIZES

- Size 1 GALLON
- Case Qty: 4

On the run?
LAUNCH MOBILE SITE

✓ **HB6612 HB-SERIES, BASECOAT BINDER**
4-1 Gal/Case, Wt.: 37 Lbs (17 kg), Dim.: 13.5"x13.5"x7.75"

✓ **HB6667 HB-SERIES BASECOAT WHITE**
4-1 Gal/Case, Wt.: 44 Lbs (20 kg), Dim.: 13.5"x13.5"x7.75"

✓ **HB6650 HB-SERIES, BASECOAT G-BLACK**
4-1 Gal/Case, Wt.: 44 Lbs (20 kg), Dim.: 13.5"x13.5"x7.75"

✓ **HB6651 HB-SERIES, BASECOAT Jet-BLACK**
4-1 Gal/Case, Wt.: 39 Lbs (17.6 kg), Dim.: 13.5"x13.5"x7.75"

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

Bicapas y Aglutinante

DESCRIPCIÓN

Una capa base que cumple con VOC, capa base a base de solvente diseñada para reparaciones generales de acabados de capa base / capa transparente OEM.
Ofrece una precisión de color excelente, una mezcla fácil y una cobertura excelente.

CARACTERISTICAS

- Excelente precisión de color
- Fácil de mezclar
- excelente cobertura

DETALLES DEL PRODUCTO

- Tipo de capa base
- Tecnología de uretano
- VOC 3.5 lb/gal (420 g/l)

Consulte la hoja de datos técnicos

TAMAÑOS DISPONIBLES

- Tamaño 1 GALÓN
- Cantidad por caja: 4

Andas de prisa o en la carrera?

LANZAR DESCRIPCIÓN DEL SITIO MÓVIL

✓ **HB6612 HB-SERIES AGLUTINANTE DE PINTURA BICAPA**
4-1 Galón/Caja, Peso: 37 Lbs (17 Kg), Dim .:13.5"x13.5"x7.75"

✓ **HB6667 HB-SERIES BICAPA BLANCO**
4-1 Galón/Caja, Peso: 44 Lbs (20 Kg), Dim.: 13.5"X13.5"X7.75"

✓ **HB6650 HB-SERIES BICAPA NEGRO-G**
4-1 Galón/Caja, Peso: 39 Lbs (17.6 Kg), Dim.: 13.5"X13.5"X7.75"

✓ **HB6651 HB-SERIES BICAPA NEGRO-Jet**
4-1 Galón/Caja, Peso: 39 Lbs (17.6 Kg), Dim.: 13.5"X13.5"X7.75"

⚠ **ADVERTENCIA**: Este producto puede exponerlo a productos químicos, que el estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite *www.P65Warnings.ca.gov.* Por favor consulte la Ficha de Datos de Seguridad. Se recomienda encarecidamente utilizar equipo de protección personal adecuado durante la aplicación.

hydraBOND® REFINISH

24 Series Additives

For PROFESSIONAL USE ONLY!

¡SOLO PARA USO PROFESIONAL!

24series URETHANE UNIVERSAL ACCELERATOR

ACELERADOR UNIVERSAL DE URETANO 24series

On the run?
LAUNCH MOBILE SITE





Andas de prisa o en la carrera?

LANZAR DESCRIPCIÓN
DEL SITIO MÓVIL

✓ HB6346 24series URETHANE UNIVERSAL ACCELERATOR

12 8 Fl. Oz (236.6 Ml)/Box, Wt: 7.3 Lbs (3.3 Kg)
Box Dim: 11"X8 ¼ "X4 5⁄8" (27.94x20.96x11.75 Cm)

The accelerator is designed to accelerate the curing, dust, tack, and tape times of hydraBOND® finishes HB777 series euro clear, HBC21 series Clear Coat and other famous brands, of Acrylic Urethane Primers, single-stage paint, and Clear Coats with no sacrifice of pot life.
SPECIAL NOTE: Application on large areas and horizontal surfaces (e.g. bonnets) can lead to technological disadvantages.
When the accelerator is used according to the directions, it can save time and cost, by improving shop productivity.

✓ HB6346 ACELERADOR UNIVERSAL DE URETANO series 24

12 8 fl. Oz (236.6 Ml)/Caja, Peso: 7.3 Lbs (3.3 Kg)
Dimensiones de la Caja: 11"x8 ¼ "x4 5⁄8" (27.94x20.96x11.75 cm)

El acelerador está diseñado para acelerar los tiempos de curado, polvo, pegajosidad y encintado de acabados hydraBOND® series HB777 euro transparente, capa transparente serie HBC21 y otras marcas famosas, imprimadores de uretano acrílico, pintura de una sola etapa y capas transparentes sin sacrificar nada. de la vida útil.
NOTA ESPECIAL: La aplicación en áreas grandes y superficies horizontales (por ejemplo, capós) puede generar desventajas tecnológicas.
Cuando el acelerador se usa de acuerdo con las instrucciones, puede ahorrar tiempo y costos al mejorar la productividad del taller.

24Series FISH-EYE ELIMINATOR

ELIMINADOR DE OJO DE PEZ 24series

On the run?
LAUNCH MOBILE SITE





Andas de prisa o en la carrera?

LANZAR DESCRIPCIÓN
DEL SITIO MÓVIL

✓ HB6353 24Series UNIVERSAL FISH-EYE

12 8 Fl. Oz (236.6 Ml)/Box, Wt: 7.3 Lbs (3.3 Kg)
Box Dim: 11"x8 ¼ "x4 5⁄8" (27.94x20.96x11.75 cm)

The best defense against fish eyes is a properly prepared surface and clean work environment; however, sometimes, despite efforts to keep things clean, contamination appears. Use for a smooth finish over surfaces that show evidence of fish-eying, usually due to contamination. Fish-eye Remover can be used with virtually all types of urethane and non-urethane 2K topcoats.

- Eliminates fish eyes without causing orange peel.
- Use in 2k clear coats and 2k Topcoats only.
- Do not use in Base coats or undercoats.
- Add 2 oz. per gallon of RFU clear coat or 2k Topcoats.

IMPORTANT: Only Use When Absolutely Necessary And Never Exceed The Recommended Quantities. See Technical Data Sheet (HDT) For More Information. **SPECIAL NOTES**: Antisilicone is not recommended as a preventive measure. Overspray from a top coat mixed with antisilicone must not come into contact with other surfaces which are still to be painted.

✓ HB6353 Serie 24 Anti - OJO DE PEZ UNIVERSAL

12 8 fl. Oz (236.6 Ml)/Caja, Peso: 7.3 Lbs (3.3 Kg)
Dimensiones de la Caja: 11"x8 ¼ "x4 5⁄8" (27.94x20.96x11.75 cm)

La mejor defensa contra los ojos de pez es una superficie debidamente preparada y un ambiente de trabajo limpio; sin embargo, a veces, a pesar de los esfuerzos por mantener las cosas limpias, aparece la contaminación. Úselo para un acabado liso sobre superficies que muestren evidencia de ojos de pez, generalmente debido a la contaminación. Fish-eye Remover se puede usar con prácticamente todos los tipos de acabados 2K de uretano y sin uretano.

- Elimina los ojos de pescado sin causar piel de naranja.
- Úselo en capas transparentes 2k y capas finales 2k únicamente.
- No lo use en Capas base o capas inferiores.
- Agregue 2 oz. por galón de capa transparente RFU o capas finales 2k.

IMPORTANTE: Usar solo cuando sea absolutamente necesario y nunca exceder las cantidades recomendadas. Consulte la Hoja de datos técnicos (HDT) para obtener más información. **NOTAS ESPECIALES**: Antisilicone no se recomienda como medida preventiva. El exceso de rociado de una capa superior mezclada con antisilicona no debe entrar en contacto con otras superficies que aún deben pintarse..

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

hydraBOND® refinish

24 Series
Masking Products



PU Foam Tape

24series Polyurethane Smooth Edge Foam Masking Tape
With A 28kg/M3 For Professional Body Shops

Polyurethane Smooth Edge Foam Masking Tape

DESCRIPTION
A strip of adhesive foam for protecting door edges, trunk, hood and other openings on the vehicle,speeding up the protection process prior to painting, acting as a barrier preventing dust and paint from entering the inside of the vehicle. The sealing strip is easy and quick to apply and facilitates the whole repair process..

MAIN FEATURES
- Easy application with no residue left.
- Applications: Car refinishing and repairing
- For use on B and C, D apertures
- Reduces levels of hard paint edges
- More absorbent
- Economical
- Easy to apply and remove
- Can be repositioned
- Comfortable and leave no residue
- Supplied in protective dispenser box

TECHNICAL DATA
- Color of the tape: white
- Waterproof
- IR process suitable
- Temperature resistance 4
- Works with solvent and waterborne paints
- Auto-Adhesive Masking Foam Tape
- With A 28kg/M3 Density



On the run?
LAUNCH MOBILE SITE



✓ **HB6902 24Series POLYURETHANE SMOOTH EDGE FOAM MASKING TAPE 13MMX50M (1/2"X54 YARD)**

1 Unit/Case, Wt: 4 Lbs (1.8 Kg), Box Dim: 54.6x50x34.3cm (21.5"X20"X13.5")

✓ **HB6903 24Series POLYURETHANE SMOOTH EDGE FOAM MASKING TAPE 18MMX50M (3/4"X54 YARD)**

1 Unit/Case Wt: 4.5 Lbs (2.04 Kg), Box Dim: 54.6x50x34.3cm (21.5"X20"X13.5"

DESCRIPCIÓN:
Burlete de espuma de poliuretano para proteger los cantos de puertas, maleteros, capós y otras aberturas del vehículo, acelerando su protección antes de pintar el vehículo y actuando como barrera contra la penetración de polvo o pintura en el interior. El Burlete de Enmascarar es de fácil y rápida aplicación y facilita todo el proceso de reparación.

PRINCIPALES CARACTERÍSTICAS
- Fácil Aplicación Sin Dejar Residuos.
- Aplicaciones: Reparación Y Reparación De Automóviles.
- Para Usar En Aberturas B Y C, D
- Reduce Los Niveles De Bordes De Pintura Dura
- Más Absorbente
- Económico
- Fácil De Aplicar Y Remover
- Se Puede Reposicionar
- Se Suministra En Caja Dispensadora
- Con una densidad de 28 kg/M3

DATOS TÉCNICOS
- Color De La Cinta: Blanco.
- Impermeable
- Proceso Ir Adecuado
- Resistencia A La Temperatura 4
- Funciona Con Solventes Y Pinturas Al Agua



Andas de prisa o en la carrera?
LANZAR DESCRIPCIÓN DEL SITIO MÓVIL



✓ **HB6902 24SERIES BURLETE DE ESPUMA DE POLIURETANO CON BORDE SUAVE 13MMX50M (1/2"X54 YARDAS)**

1 Unidad/Caja, Peso: 4 Lbs (1.8 Kg), Dim. De caja: 54.6x50x34.3cm (21.5"X20"X13.5")

✓ **HB6903 24SERIES BURLETE DE ESPUMA DE POLIURETANO CON BORDE SUAVE 18MMX50M (3/4 "X54 YARDAS)**

1 Unidad/Caja, Peso: 4.5 Lb (2.04 Kg), Dim. De Caja: 54.6x50x34.3cm (21.5 "X20" X13.5")

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet It is strongly recommended to use appropriate personal protective equipment during application

hydraBOND® Tapes

new

Automotive Attachment Acrylic Tape

On the run?
LAUNCH MOBILE SITE





hydraBOND® Automotive Attachment Acrylic Tape is a gray 1.1 mils thick double-sided closed-cell pressure-sensitive acrylic foam tape.
It also offers an extremely powerful long-term holding capability, resists UV light, and extreme temperatures & offers weather sealing abilities.
It is often used in the automotive aftermarket industry as well as in a wide variety of applications..

✓ **HB6903 hydraBOND® Automotive Attachment Acrylic Tape**
1/4" X 20 YD/V X 0.45" (6.3 mm x 18,2 m x 1,1 mm)
18 ROLLS/CTN DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, WT: 5.63 KG (12.40 LBS)

✓ **HB6904 hydraBOND® Automotive Attachment Acrylic Tape**
1/2" X 20 YD/V X 0.45" (12,7 mm x 18,2 m x 1,1 mm)
18 ROLLS/CTN DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, WT: 5.63 KG (12.40 LBS)

✓ **HB6905 hydraBOND® Automotive Attachment Acrylic Tape**
7/8" X 20 YD/V X 0.45" (22,2 mm x 18,2 m x 1,1 mm)
10 ROLLS/CTN DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, WT: 5.63 KG (12.40 LBS)

hydraBOND® Tapes

NUEVO

Cinta Acrílica Para Fijación Automotriz

⚠**WARNING:** This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to *www.P65Warnings.ca.gov.* Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protective equipment during application.

LANZAR DESCRIPCIÓN DEL SITIO MÓVIL





La cinta acrílica para fijación automotriz hydraBOND® es una cinta de espuma acrílica sensible a la presión de celda cerrada de doble cara de color gris de 1,1 mils de espesor.
También ofrece una capacidad de retención a largo plazo extremadamente poderosa, resiste la luz ultravioleta y las temperaturas extremas y ofrece capacidades de sellado contra la intemperie.
A menudo se utiliza en la industria del mercado de repuestos de automóviles, así como en una amplia variedad de aplicaciones.

✓ **HB6903 Cinta Acrílica De Fijación Automotriz hydraBOND®**
1/4" X 20 YD/V X 0,45" (6,3 mm x 18,2 m x 1,1 mm)
18 ROLLOS/CAJA DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, PESO: 5.63 KG (12.40 LBS)

✓ **HB6904 Cinta Acrílica De Fijación Automotriz hydraBOND®**
1/2" X 20 YD/V X 0.45" (12,7 mm x 18,2 m x 1,1 mm)
18 ROLLOS/CAJA DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, PESO: 5.63 KG (12.40 LBS)

✓ **HB6905 Cinta Acrílica De Fijación Automotriz hydraBOND®**
7/8" X 20 YD/V X 0.45" (22,2 mm x 18,2 m x 1,1 mm))
10 ROLLOS/CAJA DIM: (9.65"*9.65"*10.43") 245MM*245MM*265MM, PESO: 5.63 KG (12.40 LBS)

⚠ **ADVERTENCIA**: Este producto puede exponerlo a productos químicos, que el estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite *www.P65Warnings.ca.gov.* Por favor consulte la Ficha de Datos de Seguridad. Se recomienda encarecidamente utilizar equipo de protección personal adecuado durante la aplicación.

hydraBOND® tape

Made In Italy

hydrabond.com

WARNING: THIS PRODUCT CAN EXPOSE YOU TO CHEMICALS INCLUDING BENZENE, WHICH IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. PLEASE WASH YOUR HANDS. FOR MORE INFORMATION GO TO www.P65warnings.ca.gov

Scan Qr code or visit https://hydrabond.com/tapes more information dowload Masking Tapes SDS

Masking Tape

At BHG Import Export Inc, we are committed to delivering high-quality masking tapes designed to meet the rigorous demands of professionals in the automotive refinishing and repair industry.

Our product range is engineered to provide superior performance in various temperature conditions, ensuring precision and reliability in every application. We are pleased to introduce our three versatile series:ur next project and experience the quality and reliability that professionals trust. Scan Qr code or visit https://hydrabond.com/tapes for more information dowload Masking Tapes SDS

HB121

The HB121 Series is a waterproof, high-temperature single sided masking tape ideal for demanding automotive refinishing and repair tasks. With a temperature resistance of up to 120°C (248°F) for 30 minutes, it ensures reliable performance in critical applications. The tape's distinctive yellow color provides clear contrast for precise masking. Available part numbers:

- **HB12118** 18mmx55m (0.70"x60.1 yds) 48 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB12124** 24mmx55m (0.94"x60.1 yds) 36 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB12136** 36mmx55m (1.42"x 60.1 yds) 24 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Case/Pallet
- **HB12148** 48mmx55m (1.875"x60.1 yds) 24 Rolls/Case
  Wt: 15.88 Lbs (7.2 kg), Dim.: 10.75"x10.75"x12.25", 72/Case/Pallet



On the run?
LAUNCH MOBILE SITE

HB98G

The HB98G Series is our high-performance masking tape for the most demanding applications, including automotive painting and powder coating. With a temperature resistance of up to (90°C) 194°F for 30 minutes, this tape provides excellent adhesion and clean removal, even under extreme conditions.The tape's distinctive Green color provides clear contrast for precise masking. Available part numbers:

- **HB9818** 18mmx55m (0.70"x60.1 yds) 48 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB9824** 24mmx55m (0.94"x60.1 yds) 36 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB9836** 36mmx55m (1.42"x 60.1 yds) 24 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Case/Pallet
- **HB9848** 48mmx55m (1.875"x60.1 yds) 24 Rolls/Case
  Wt: 15.88 Lbs (7.2 kg), Dim.: 10.75"x10.75"x12.25", 72/Case/Pallet



On the run?
LAUNCH MOBILE SITE

HB62

The HB6200 Series is a general-purpose masking tape designed for body shops. It offers reliable performance in temperatures up to 80°C (176°F) for 60 minutes, making it suitable for most car repair tasks. This tape is easy to remove without breaking, ensuring a clean finish every time. The tape's distinctive semi crepe pale yellow color provides clear contrast for precise masking. Available part numbers:

- **HB6218** 18mmx55m (0.70"x60.1 yds) 48 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB6224** 24mmx55m (0.94"x60.1 yds) 36 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Cases/Pallet
- **HB6236** 36mmx55m (1.42"x 60.1 yds) 24 Rolls/Case
  Wt: 14.88 Lbs (6.7 kg), Dim.: 10.75"x10.75"x9.25", 96/Case/Pallet
- **HB6248** 48mmx55m (1.875"x60.1 yds) 24 Rolls/Case
  Wt: 15.88 Lbs (7.2 kg), Dim.: 10.75"x10.75"x12.25", 72/Case/Pallet



On the run?
LAUNCH MOBILE SITE

hydraBOND® refinish

GM™ Containers Inc



Emmty Paint Cans

American Style Paint Cans Packaged For Paint Stores!

Latas De Pintura Estilo Americano ¡Empaquetadas Para Tiendas De Pintura!

DESCRIPTION:
STEEL CAN, PAIL AND COVER INTERIOR COATINGS
Interior Coatings – We offer several different interior coating options that are compatible with a wide variety of products. If requested , we can assist you in selecting the proper interior coating for your products.We strongly recommend that our customers conduct testing on the interior coating to determine final compatibility for your products.

GOLD EPOXY-PHENOLIC
Gold phenolic linings are unmodified phenolics and as such, have a high degree of acid and solvent resistance, and are not recommended for alkaline products. In general, they are designed for holding products that have a pH range of 3.0–7.0. A properly cured lining will exhibit good adhesion, however; compared to the red and green phenolic lining it is less flexible. Typical products which do not affect the lining are acid compounds, agricultural chemicals, insecticides, corrosive chemicals, solvents and solvent containing materials, nitrocellulose lacquers and inks, food products, essentialoils and petroleum products

DESCRIPCIÓN:
REVESTIMIENTOS INTERIORES DE LA TAPA Y LA CUBETA Y BOTE DE ACERO
Recubrimientos interiores – Ofrecemos diferentes opciones de recubrimientos interiores que son compatibles con una amplia variedad de productos. Si lo solicita, podemos ayudarlo a seleccionar el revestimiento interior adecuado para sus productos. Recomendamos, especialmente, que nuestros clientes realicen evaluaciones sobre el revestimiento interior para determinar la compatibilidad de sus productos.

FENÓLICO DORADO
Los recubrimientos fenólicos dorados son fenólicos no modificados y, como tales, tienen un alto grado de resistencia a los ácidos y los solventes, y no se recomiendan para los productos alcalinos. En general, están diseñados para mantener productos que tienen un rango de pH de 3.0-7.0. Un recubrimiento curado adecuadamente mostrará una buena adherencia, no obstante, en comparación con el recubrimiento de fenólicos rojo y verde es menos flexible. Los productos típicos que no afectan el recubrimiento son compuestos ácidos, químicos agrícolas, insecticidas, químicos corrosivos, solventes y materiales que contienen solventes, tintas y lacas de nitrocelulosa, productos alimenticios, aceites esenciales y productos derivados del petróleo

- ✓ **GM08G 1/2 PINT METAL PAINT CAN WITH LID, GOLD PHENOLIC LINED**
  Case-Dim: 14.5"X13.75"X14.5", Pallet (72 Cases), Case Pack: 120 ea. Wt: 17 Lbs (7.7 kg)
- ✓ **GM16G 1 PINT METAL PAINT CAN WITH LID, GOLD PHENOLIC LINED**
  Case-Dim: 20.75"X15.75"X8.75", Pallet (72 Cases), Case Pack: 50 ea. Wt: 11 Lbs (5 kg)
- ✓ **GM32G 1 QUART METAL PAINT CAN WITH LID, GOLD PHENOLIC LINED**
  Case-Dim: 25.75"X21.5"X10.75", Pallet (36 Cases), Case Pack: 56 Ea. Wt: 18 Lbs (8.1 Kg)
- ✓ **GM128G 1 GALLON METAL PAINT CAN WITH LID, GOLD EPOXY LINED**
  Case-Dim: 26.75"X20.5"X23.5", Pallet (16 Cases), Case Pack: 34 Ea. Wt: 25 Lbs (11 Kg)



On the run?

LAUNCH MOBILE SITE

- ✓ **GM08U 1/2 PINT METAL PAINT CAN WITH LID, ULINED**
  Case-Dim: 14.5"X13.75"X14.5", Pallet (72 Cases), Case Pack: 120 ea. Wt: 17 Lbs (7.7 kg)
- ✓ **GM16U 1 PINT METAL PAINT CAN WITH LID, ULINED**
  Case-Dim: 20.75"X15.75"X8.75", Pallet (72 Cases), Case Pack: 50 ea. Wt: 11 Lbs (5 kg)
- ✓ **GM32U 1 QUART METAL PAINT CAN WITH LID, ULINED**
  Case-Dim: 25.75"X21.5"X10.75", Pallet (36 Cases), Case Pack: 56 Ea. Wt: 18 Lbs (8.1 Kg)
- ✓ **GM128U 1 GALLON METAL PAINT CAN WITH LID, ULINED**
  Case-Dim: 26.75"X20.5"X23.5", Pallet (16 Cases), Case Pack: 34 Ea. Wt: 25 Lbs (11 Kg)



Andas de prisa o en la carrera?

LANZAR DESCRIPCIÓN DEL SITIO MÓVIL