



Input Power	1 Phase, 60 Hz.	Electrode Speed	Electrode Diameters	Number of Rollers	Dimensions in (mm)	Weight lb (kg)
24 VAC	10 A AC	Min: 1.9 m/min (75 plg/min) Max: 24.5 m/min (1000 plg/min)	Min: 0.6 mm (0.023") Max: 3.2 mm (1/8")	4	H: 13.6 (346) W: 11 (278) L: 25.5 (646)	Net: 43 (19.5) Ship: 47.3 (21.5)

Process:

- Micro wire electrode MIG (GMAW) diameters of 0.6 a and 1.2 mm (0.023" to 0.045").
- Tubular electrode with fluxed core FCAW with or without gas, diameters of 0.8 to 3.2 mm (0.030" to 5/32").

Comes With:

- Set of rollers of 0.9 and 1.2 mm (0.035" and 0.045").
- Wire voltage and speed control.
- Wire cutter.
- Owner manual: operation guide, maintenance guide, parts list and warranty policy.

Applications:

- Shipbuilding.
- Construction.
- Metal structures for advertisements.
- Field maintenance or on-site fabrication.
- For use with constant potential sources, with 24 V ac output for power supply and sufficient current capacity for the specified electrode diameters and speeds.

Suitable for:

- HBCP303_PRO, HB300MM





Potencia de entrada	1 fase, 60 Hz.	Electrodo Velocidad	Electrodo Diámetros	Número de Rodillos	Dimensiones en (mm)	Peso libras (kg)
24 VCA	10 A CA	Mínimo: 1,9 m/min (75 plg/min) máx.: 24,5 m/min (1000 plg/min)	Mínimo: 0,6 mm (0,023") máx.: 3,2 mm (1/8")	4	Alto: 13,6 (346) M: 11 (278) Largo: 25,5 (646)	Neto: 43 (19,5) De Entrega: 47,3 (21,5)

Proceso:

- Electrodo de microalambre MIG (GMAW) diámetros de 0,6 a y 1,2 mm (0,023" a 0,045").
- Electrodo tubular con núcleo fundente FCAW con o sin gas, diámetros de 0,8 a 3,2 mm (0,030" a 5/32").

Viene con:

- Juego de rodillos de 0,9 y 1,2 mm (0,035" y 0,045").
- Control de voltaje y velocidad del cable.
- Cortador de cables.
- Manual del propietario: guía de operación, guía de mantenimiento, lista de piezas y política de garantía.

Aplicaciones:

- Construcción naval.
- Construcción.
- Estructuras metálicas para anuncios.
- Mantenimiento de campo o fabricación in situ.
- Para uso con fuentes de potencial constante, con salida de 24 V CA para fuente de alimentación y capacidad de corriente suficiente para los diámetros y velocidades de electrodos especificados.

Adecuado para:

- HBCP303_PRO, HB300MM

