

FAC

Fluid-Air Components Ltd

PNEUMATICS

HYDRAULICS

INDUSTRIAL VALVES

CONTROL & INSTRUMENTATION

NEW WEBSITE!

www.pneumatics.co.uk

BRANDS

We offer industry leading brands and expertly engineered solutions for all your **Fluid Power** needs.



Fluid-Air Components Ltd

1	Hydraulics	3-284
2	Hydraulic Quick Release Couplings	285-320
3	Pneumatic Quick Release Couplings	321-406
4	Monitor & Test	407-446
5	Pneumatic & Vacuum	447-762
6	Push-in Fittings & Tubing	763-918
7	Valves & Actuation	919-1060
8	Ring Main	1061-1136
9	Hose Tails, Adaptors, Fittings & Manifolds	1137-1224
10	Stainless Steel	1225-1332
11	Malleable Iron	1333-1398
12	Hose, Couplings, Ducting & Hose Reels	1399-1510
13	Clips & Clamps	1511-1558
14	Paint, Sprays & Adhesives	1559-1590
15	Blow Guns, Vacuum & Nozzles	1591-1616
16	Fuelling, Lubrication, Wash Down & Misting	1617-1696
17	Compressors & Air Tools	1697-1726
18	Hand Tools & PPE	1727-1765

SECTION 1

Hydraulics

1.01	Hydraulic Hose & Inserts	6-41
1.02	Hose Retention, Sleeves & Cleaning	42-51
1.03	Hydraulic Threaded Adaptors & Flanges	52-108
1.04	Hydraulic Seals & Caps	109-114
1.05	Hydraulic Compression Fittings	115-178
1.06	Tube & Clamps	179-201
1.07	Valves, Pumps & Motors	202-237
1.08	Hydraulic Threaded Valves	238-246
1.09	Test, Flow Filtration & Cooling	247-273
1.10	Lifting Equipment, Spill & Oils	274-284

SECTION 1

1.01 Hydraulic Hose & Inserts

6-41

- Hydraulic Hose Range
- Breaker Hose Assemblies, Hose Ferrules
- Hose Connectors
- Interlock Hose Connectors
- Stainless Steel Ferrules
- Stainless Steel Adaptors & Hose Fittings
- Push Style Hose System
- Reusable Fittings



1.02 Hose Retention, Sleeves & Cleaning

42-51

- Retention Systems
- Protective Hose Sleeves
- Hose & Pipe Cleaning Kits
- Service Plugs



1.03 Hydraulic Threaded Adaptors & Flanges

52-108

- Adaptors
- ORFS
- JIC & High Pressure Adaptors
- Stainless Steel Adaptors
- 316 Precision Instrumentation Pipe Fittings
- 10,000 psi 316 Stainless Steel Adaptors
- 37° JIC Stainless Steel Flare Fittings
- SAE Flanges



1.04 Hydraulic Seals & Caps

109-114

- Seals, Plastic Caps & Plugs



1.05 Hydraulic Compression Fittings

115-178

- Component Parts
- Male Stud Couplings
- Male Stud Elbows & Reducing Bushes
- Tube to Tube Couplings
- Banjo Couplings
- Welding Couplings
- Adjustable Stud Couplings
- Swivel Couplings
- Female Stud & Gauge Couplings
- Reducing Couplings
- Din 2353 Body Only Fittings
- Flange Couplings
- Valves
- Standpipe Adaptors
- High Pressure Metric Tube Couplings
- Imperial Compression Fittings
- 316 Stainless Steel Tube Fittings
- Stainless Steel Component Parts
- 316 Stainless Steel Twin Ferrule Tube Fittings (Imperial & Metric)




Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

Hydraulics

1.06 Tubes & Clamps

179-201

- Hydraulic Tubing (Imperial & Metric)
- Hydraulic Tube Clamps & Accessories
- Pipe Clamping Systems



1.07 Valves, Pumps & Motors

202-237


- CETOP Directional Control Valves
- CETOP Manifold & Auxiliary Plates
- Hydraulic Directional Control Valves
- System Stack Valves
- CETOP Valve Coils
- Industrial Vane Pumps
- Hydraulic Piston Pumps
- Gear Pumps
- Gear Motors
- Hand Pumps
- Control Valves



1.08 Hydraulic Threaded Valves

238-246

- Hydraulic Ball Valves
- Non-return Valves
- Flow Control Valves
- Stainless Steel Hydraulic Valves
- Needle Valves
- Diverter Valves
- Threaded Hydraulic Valves



1.09 Test, Flow Filtration & Cooling

247-273

- Hydraulic Filtration
- High Pressure Hydraulic Filtration
- Flow Metering
- Hydraulic Accessories
- Hydraulic Pressure Gauges
- Test Point Couplings
- Hydraulic Oil Coolers



1.10 Lifting Equipment, Spill & Oils

274-284

- Hydraulic Cylinders
- Hydraulic Pumps
- Hydraulic Cylinder Kits
- Hydraulic Tooling & Lifting Accessories
- Bottle Jacks
- Toe Jacks
- Spill Absorbents
- Chemical Spill Absorbents
- Spill Kits, Spill Trays
- Drain Cover, Drum Pallets
- Absorbent Dispensing Station



HYDRAULIC HOSE RANGE

EN853-1, DIN20022 (Exceeds SAE 100R1AT)

Application:
Medium pressure hydraulic applications
Specification:
DIN 20022, EN853 – 1 Exceeds 100 R1AT
Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 1 single steel wire braid
Outer cover: oil and weather resistant synthetic rubber
Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based . uids, air and water

NB: For air above 17 bar, the hose cover must be pin-pricked

Available per 1 metre
Smooth cover available on request

Working Temperature:
-40°C to +100°C



1 Wire, 100 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R1AT-03-100	3/16"	12.5	250	90	1000
100R1AT-04-100	1/4"	14.1	225	100	900
100R1AT-05-100	5/16"	15.7	215	115	850
100R1AT-06-100	3/8"	18.1	180	130	720
100R1AT-08-100	1/2"	21.4	160	180	640
100R1AT-10-100	5/8"	24.5	130	200	520
100R1AT-12-100	3/4"	28.5	105	240	420
100R1AT-16-100	1"	36.6	88	300	350
Tech Sheet 5001					

1 Wire, 40 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R1AT-20-40	1.1/4"	44.8	63	420	250
100R1AT-24-40	1.1/2"	52	50	500	200
100R1AT-32-40	2"	65.9	40	630	160
Tech Sheet 5001					

Technical Data

Hydraulic Hose, EN853, DIN20022, SAE100R1AT

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	FT3 Type Ferrule	Swage Dia. in mm	mm	mm	mm	mm
100R1AT-03	4.7	3/16	250	3625	1000	14503	3.54	90	FT3-12-03CF	15	2.89	3.05	2.80	2.93
100R1AT-04	6.3	1/4	225	3260	900	13050	3.94	100	FT3-12-04CF	17.8	3.86	3.67	3.67	3.45
100R1AT-05	8	5/16	215	3120	850	12325	4.53	115	FT3-12-05CF	20.5	5.29	5.11	5.11	4.91
100R1AT-06	10	3/8	180	2610	720	10440	5.12	130	FT3-12-06CF	21.6	6.78	6.42	6.42	6.13
100R1AT-08	12.5	1/2	160	2320	640	9280	7.09	180	FT3-12-08CF	24	9.21	8.86	8.86	8.4
100R1AT-10	16	5/8	130	1885	520	7540	7.87	200	FT3-12-10CF	28.7	12.09	11.59	11.59	10.99
100R1AT-12	19	3/4	105	1520	420	6090	9.45	240	FT3-12-12CF	31.3	14.46	13.91	13.91	13.31
100R1AT-16	25	1	88	1280	350	5075	11.81	300	FT3-12-16CF	41	18.89	18.29	18.29	17.68
100R1AT-20	31.5	1.1/4	63	910	250	3625	16.54	420	FT3-12-20CF	48.5	25.4	24.69	24.69	23.8
100R1AT-24	38	1.1/2	50	725	200	2900	19.69	500	FT3-12-24CF	58.5	31.4	30.6	30.6	29.8
100R1AT-32	51	2	40	580	160	2320	24.8	630	FT3-12-32CF	70	41.4	40.6	40.6	30.8

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC HOSE RANGE

EN853-2, DIN20022 (Exceeds SAE 100R2AT)

Application:
Medium pressure hydraulic applications
Specification:
DIN 20022, EN853-2, exceeds SAE100 R2AT
Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 2 single steel wire braids
Outer cover: oil and weather resistant synthetic rubber
Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

NB: For air above 17 bar, the hose cover must be pin-pricked

Available per 1 metre
Smooth cover available on request

Working Temperature:
-40°C to +100°C



2 Wire, 100 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R2AT-03-100	3/16"	14.1	415	90	1650
100R2AT-04-100	1/4"	15.7	400	100	1600
100R2AT-05-100	5/16"	17.3	350	115	1400
100R2AT-06-100	3/8"	19.7	330	130	1320
100R2AT-08-100	1/2"	23.0	275	180	1100
100R2AT-10-100	5/8"	26.2	250	200	1000
100R2AT-12-100	3/4"	30.1	215	240	850
100R2AT-16-100	1"	38.9	165	300	650
Tech Sheet 5002					

2 Wire, 40 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R2AT-20-40	1.1/4"	49.6	125	420	500
100R2AT-24-40	1.1/2"	56.0	90	500	360
100R2AT-32-40	2"	68.6	80	630	320
Tech Sheet 5002					

Technical Data

Hydraulic Hose, EN853, DIN20022, SAE100R2AT

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	FT3 Type Ferrule	Swage Dia. in mm	mm	mm	mm	mm
100R2AT-03	4.7	3/16	415	6019	1650	23931	3.54	90	FT3-12-03CF	16.4	2.89	3.05	2.80	2.93
100R2AT-04	6.3	1/4	400	5800	1600	23200	3.94	100	FT3-12-04CF	18.1	3.86	3.67	3.67	3.45
100R2AT-05	8	5/16	350	5075	1400	20300	4.53	115	FT3-12-05CF	19.7	5.29	5.11	5.11	4.91
100R2AT-06	10	3/8	330	4785	1320	19140	5.12	130	FT3-12-06CF	22.1	6.78	6.42	6.42	6.13
100R2AT-08	12.5	1/2	275	3990	1100	15950	7.09	180	FT3-12-08CF	24.6	9.21	8.86	8.86	8.4
100R2AT-10	16	5/8	250	3625	1000	14500	7.87	200	FT3-12-10CF	28.2	12.09	11.59	11.59	10.99
100R2AT-12	19	3/4	215	3120	850	12325	9.45	240	FT3-12-12CF	32.5	14.46	13.91	13.91	13.31
100R2AT-16	25	1	165	2390	650	9425	11.81	300	FT3-12-16CF	40.3	18.89	18.29	18.29	17.68
100R2AT-20	31.5	1.1/4	125	1810	500	7250	16.54	420	FT3-12-20CF	51.5	25.4	24.69	24.69	23.8
100R2AT-24	38	1.1/2	90	1305	360	5220	19.69	500	FT3-12-24CF	59.7	31.4	30.6	30.6	29.8
100R2AT-32	51	2	80	1160	320	4640	24.8	630	FT3-12-32CF	73.4	41.4	40.6	40.6	30.8

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC HOSE RANGE

Compact Hydraulic Hose, EN857-1SC

1 Wire Compact Hose

Application:
Medium pressure hydraulic applications with space constraints and greater flexibility is required

Specification:
EN857 – 1SC

Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 1 single steel wire braid
Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

NB: For air above 17 bar, the hose cover must be pin-pricked

Available per 1 metre

Smooth cover available on request

Working Temperature:
-40°C to +100°C





1 Wire, 100 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
1SC-04-100	1/4"	13.5	225	75	900
1SC-06-100	3/8"	16.9	180	90	720
1SC-08-100	1/2"	20.4	160	130	640
1SC-12-100	3/4"	26.7	105	180	420
Tech Sheet 5003					

Technical Data

1 Wire Compact Hose, EN857- 1SC

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	FR79 Type Ferrule	Swage Dia. in mm	mm	mm	mm	mm
1SC-04	6.3	1/4	225	3260	900	13050	2.95	75	FR79-04	14.7	3.86	3.67	3.67	3.45
1SC-06	10	3/8	180	2610	720	10440	3.54	90	FR79-06	19	6.78	6.42	6.42	6.13
1SC-08	12.5	1/2	160	2320	640	9280	5.12	130	FR79-08	23.3	9.21	8.86	8.86	8.40
1SC-12	19	3/4	105	1520	420	6090	7.09	180	FR79-12	30.8	14.46	13.91	13.91	13.31

Danfoss Waltech



For **full range of Danfoss Waltech couplings** see pages **115-137**

Fluid-Air Components Ltd

Compact Hydraulic Hose, EN857-2SC

2 Wire Compact Hose

Application:

Medium pressure hydraulic applications with space constraints and greater flexibility is required

Specification:
EN857 – 2SC

Construction:

Inner tube: oil resistant synthetic rubber (NBR)

Reinforcement: 2 single steel wire braids

Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:

Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

NB: For air above 17 bar, the hose cover must be pin-pricked

Available per 1 metre

Smooth cover available on request

Working Temperature:
-40°C to +100°C





2 Wire, 100 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
2SC-04-100	1/4"	14.2	400	75	1600
2SC-06-100	3/8"	18.3	330	90	1320
2SC-08-100	1/2"	21.5	275	130	1100
2SC-12-100	3/4"	28.6	215	200	860
2SC-16-100	1"	36.6	165	250	660
Tech Sheet 5004					

Technical Data

2 Wire Compact Hose, EN857- 2SC

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	F2SC Type Ferrule	Swage Dia. in mm	mm	mm	mm	mm
2SC-04	6.3	1/4	400	5800	1600	23200	2.95	75	F2SC-04	17.6	3.86	3.67	3.67	3.45
2SC-06	10	3/8	330	4785	1320	19140	3.54	90	F2SC-06	20.5	5.29	5.11	5.11	4.91
2SC-08	12.5	1/2	275	3990	1100	15950	5.12	130	F2SC-08	24.3	6.78	6.42	6.42	6.13
2SC-12	19	3/4	214	3120	860	12470	7.86	200	F2SC-12	31.5	9.20	8.86	8.86	8.40
2SC-16	25	1	165	2390	660	9570	9.84	250	F2SC-16	39	18.89	18.29	18.29	17.68

For **Fire Sleeves** see pages **44-45**



Fluid-Air Components Ltd

HYDRAULIC HOSE RANGE

MSHA Approved, EN853, DIN20022 (Exceeds SAE 100R2AT)

2 Wire Compact Hose

Application:
Medium pressure hydraulic applications were MSHA approval and certification is required

Specification:
MSHA Approved, DIN 20022, EN853 – 2SN, exceeds SAE100 R2AT

Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 2 single steel wire braids
Outer cover: MSHA approved oil and weather resistant synthetic rubber

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

NB: For air above 17 bar, the hose cover must be pin-pricked

Available per 1 metre

Smooth cover available on request

Working Temperature:
-40°C to +100°C



2 Wire, 100 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
MSHAR2AT-04-100	1/4"	15.7	400	100	1600
MSHAR2AT-06-100	3/8"	19.7	330	125	1320
MSHAR2AT-08-100	1/2"	23.1	275	180	1100
Tech Sheet 5015					

2 Wire, 50 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
MSHAR2AT-12-50	3/4"	30.2	215	240	850
MSHAR2AT-16-50	1"	38.9	165	300	650
Tech Sheet 5015					

Technical Data

Hydraulic Hose, MSHA R2AT

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	FT3 Type Ferrule	Swage Dia. in mm	mm	mm	mm	mm
MSHAR2AT-04	6.3	1/4	400	5800	1600	23200	3.94	10	FT3-12-04CF	19.1	3.86	3.67	3.67	3.45
MSHAR2AT-06	10	3/8	330	4785	1320	19140	5.12	130	FT3-12-06CF	22	6.78	6.42	6.42	6.13
MSHAR2AT-08	12.5	1/2	275	3990	1100	15950	7.09	180	FT3-12-08CF	24.5	9.21	8.86	8.86	8.40
MSHAR2AT-12	19	3/4	215	3120	850	12325	9.45	240	FT3-12-12CF	32	14.46	13.91	13.91	13.31
MSHAR2AT-16	25	1	165	2390	650	9425	11.81	300	FT3-12-16CF	41	18.89	18.29	18.29	17.68
MSHAR2AT-20	31.5	1.1/4	125	1810	500	7250	16.54	420	FT3-12-20CF	51.5	25.40	24.69	24.69	23.8
MSHAR2AT-24	38	1.1/2	90	1305	360	5220	19.69	500	FT3-12-24CF	59.7	31.40	30.60	30.60	29.80
MSHAR2AT-32	51	2	80	1160	320	4640	24.80	630	FT3-12-32CF	73.4	41.40	40.60	40.60	30.80

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Multi Spiral, EN856-4SP

Standard hydraulic adaptors do not adhere to the working pressure of multi spiral hose. Please use KR500 Hydraulic Adaptors for high pressure and multi spiral applications.

Application:
High pressure hydraulic applications
Specification:
EN856-4SP
Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 4 high tensile steel spirals
Outer cover: oil and weather resistant synthetic rubber
NB: External skive required
Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Available per 1 metre
Smooth cover available on request

Working Temperature:
-40°C to +100°C



40 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
4SP-04-40	1/4"	18.7	450	150	1800
4SP-06-40	3/8"	22.2	445	180	1780
4SP-08-40	1/2"	25.4	415	230	1660
4SP-10-40	5/8"	29.0	350	250	1400
4SP-12-40	3/4"	33.0	350	300	1480
4SP-16-40	1"	40.9	280	340	1120
4SP-20-40	1.1/4"	52.4	210	460	840
4SP-24-40	1.1/2"	58.8	185	560	740
4SP-32-40	2"	71.4	165	660	660
Tech Sheet 5006					

Technical Data

Multi Spiral Hydraulic Hose, EN856-4SP

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Swaging Dimensions		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Skive Length JMF56 in mm	Skive Length JMF57 in mm	Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	JMF57 Type Ferrule	Swage Dia. in mm	mm	mm	External	External	mm	mm
4SP-04	6.3	1/4	450	6525	1800	26100	5.91	150								
4SP-06	10	3/8	445	6450	1780	25810	7.09	180	JMF57-06CF	23	6.78	6.42	27	–	6.42	6.13
4SP-08	12.5	1/2	415	6020	1660	24070	9.06	230	JMF57-08CF	26.5	9.21	8.86	28	32	8.86	8.40
4SP-10	16	5/8	350	5075	1400	20300	9.84	250	JMF57-10CF	29.7	12.09	11.59	33	–	11.59	10.99
4SP-12	19	3/4	350	5075	1480	21460	11.81	300	JMF57-12CF	34	14.46	13.91	32	40	13.91	13.31
4SP-16	25	1	280	4060	1120	16240	13.39	340	JMF57-16CF	43	18.89	18.29	42	48	18.29	17.68
4SP-20	31.5	1.1/4	210	3045	840	12180	18.11	460	JMF57-20CF	53	25.40	24.69	48	55	24.69	23.80
4SP-24	38	1.1/2	185	2680	740	10730	22.05	560	JMF57-24CF	60.5	31.40	30.60	60	68	30.60	29.80
4SP-32	51	2	165	2390	660	9570	25.98	660	JMF57-32CF	74.5	41.40	40.60	61	73	40.60	30.80

Fluid-Air Components Ltd

HYDRAULIC HOSE RANGE

Multi Spiral, EN856-4SH

Application:
High pressure hydraulic applications, for use with interlock fittings

Specification:
EN856-4SH

Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 4 high tensile steel spirals
Outer cover: oil and weather resistant synthetic rubber

NB: External and internal skive required

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Working Temperature:
-40°C to +100°C





40 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
4SH-12-40	3/4"	33.0	420	280	1680
4SH-16-40	1"	39.9	380	340	1520
Tech Sheet 5007					

Technical Data

Multi Spiral Hydraulic Hose, EN856-4SH

Part Number	Size		Working Pressure		Burst Pressure		Bend Radius		Tail ID Top Tolerance	Tail ID Bottom Tolerance	Swaging Dimensions		Skive Length in mm		Swaged No Go	Swaged Go
	mm	inch	bar	psi	bar	psi	Inch	mm	mm	mm	JMF4SH Type Ferrule	Swage Dia. in mm	Internal	External	mm	mm
4SH-12	19	3/4	420	6090	1680	24360	11.02	280	14.46	13.91	JMF4SH-12CF	35.1	16	43	13.91	13.31
4SH-16	25	1	380	5510	1520	22040	13.39	340	18.89	18.29	JMF4SH-16CF	43.4	18	59	18.29	17.68

Other sizes available on request.
A minimum order quantity will apply. Lead times will be given at point of enquiry



For **full range of Hydraulic QRC's** see pages **289-320**

Fluid-Air Components Ltd

HYDRAULIC HOSE RANGE

Thermoplastic, SAE 100R7

100R7 Hose

Application:
Thermoplastic hose with perforated cover for use on medium pressure hydraulic applications.
Specification: SAE100 R7
Construction:
Inner tube: thermoplastic elastomer
Reinforcement: 2 single textile yarn braids
Outer cover: high abrasion resistant polyurethane

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, lubricating oils, solvent and gas transfer

Available per 1 metre

Working Temperature:
-40°C to +100°C.



75 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R7-03-75	3/16"	10.8	210	75	840
100R7-04-75	1/4"	13.0	210	100	840
100R7-05-75	5/16"	15.1	175	115	700
100R7-06-75	3/8"	17.0	155	125	620
100R7-08-75	1/2"	20.7	140	175	560
Tech Sheet 5011					

25 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R7-03-25	3/16"	10.8	210	75	840
100R7-04-25	1/4"	13.0	210	100	840
100R7-05-25	5/16"	15.1	175	115	700
100R7-06-25	3/8"	17.0	155	125	620
100R7-08-25	1/2"	20.7	140	175	560
Tech Sheet 5011					

Twin Line Thermoplastic, SAE 100R7

100R7 Twin Hose

Application:
Thermoplastic hose with perforated cover for use on medium pressure hydraulic applications.
Specification: SAE100 R7
Construction:
Inner tube: thermoplastic elastomer
Reinforcement: 2 single textile yarn braids
Outer cover: high abrasion resistant polyurethane

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, lubricating oils, solvent and gas transfer

Available per 1 metre

Working Temperature:
-40°C to +100°C.



75 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R7-04-75-TWIN	1/4"	13.0	210	100	840
100R7-05-75-TWIN	5/16"	15.1	175	115	700
100R7-06-75-TWIN	3/8"	17.0	155	125	620
100R7-08-75-TWIN	1/2"	20.7	140	175	560
Tech Sheet 5011					

25 Metre Coils

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R7-04-25-TWIN	1/4"	13.0	210	100	840
100R7-05-25-TWIN	5/16"	15.1	175	115	700
100R7-06-25-TWIN	3/8"	17.0	155	125	620
100R7-08-25-TWIN	1/2"	20.7	140	175	560
Tech Sheet 5011					

Technical Data

Thermoplastic, SAE 100R7

Part Number	Size			OD	Working Pressure			Burst Pressure			Bend Radius	Weight	Swaging Dimensions	
	mm	inch	SAE	mm	Mpa	psi	bar	Mpa	psi	bar	mm	Kg/mtr	FR79 Type Ferrules	Swage Dia. in mm
100R7-03	5	3/16"	-3	10.8	20.7	3000	210	82.7	12000	840	75	0.046	100R7-03	12.25
100R7-04	6.3	1/4"	-4	13	20.7	3000	210	82.7	12000	840	100	0.057	100R7-04	14.7
100R7-05	8	5/16"	-5	15.1	17.2	2500	175	68.9	10000	700	115	0.069	100R7-05	17
100R7-06	10	3/8"	-6	17	15.5	2250	155	62.1	9000	620	125	0.095	100R7-06	19.4
100R7-08	12.5	1/2"	-8	20.7	13.8	2000	140	55.2	8000	560	175	0.141	100R7-08	23.8

Fluid-Air Components Ltd

HYDRAULIC HOSE RANGE

Oil Suction & Delivery Hose

Application:
General low pressure suction and delivery applications

Construction:
Inner tube: oil resistant synthetic rubber (NBR)

Reinforcement: woven textile yarn braids with a suitable spiral of steel to prevent collapse under vacuum

Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, lubricating oils, air and water

Available per 1 metre

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
10 bar



10 Metre Coils

0303	ID mm	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R4-19-10	19	31	10	125	30
100R4-25-10	25	38	10	150	30
100R4-32-10	32	46	10	200	30
100R4-38-10	38	52	10	255	30
100R4-51-10	51	64	10	300	30
100R4-64-10	64	81	10	355	30
100R4-76-10	76	93	10	460	30
100R4-89-10	89	109	10	530	30
100R4-102-10	102	122	10	610	30
100R4-115-10	115	135	10	625	30
100R4-127-10	127	148	10	750	30
100R4-152-10	152	180	10	960	30
Tech Sheet 5012					

20 Metre Coils

0303	ID mm	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R4-19-20	19	31	10	125	30
100R4-25-20	25	38	10	150	30
100R4-32-20	32	46	10	200	30
100R4-38-20	38	52	10	255	30
100R4-51-20	51	64	10	300	30
100R4-64-20	64	81	10	355	30
100R4-76-20	76	93	10	460	30
100R4-89-20	89	109	10	530	30
100R4-102-20	102	122	10	610	30
100R4-127-20	127	148	10	750	30
100R4-152-20	152	180	10	960	30
Tech Sheet 5012					

40 Metre Coils

0303	ID mm	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R4-19-40	19	31	10	125	30
100R4-25-40	25	38	10	150	30
100R4-32-40	32	46	10	200	30
100R4-38-40	38	52	10	255	30
100R4-51-40	51	64	10	300	30
Tech Sheet 5012					

Technical Data

Oil Suction & Delivery Hose, 100R4

Part Number	Size	ID	OD	Working Pressure		Burst Pressure		Vacuum Pressure	Bend Radius	Weight
	Inch	mm	mm	bar	psi	bar	psi	bar	mm	gr/m
100R4-19	3/4"	19	30	10	145	30	450	-0.92	90	600
100R4-25	1"	25.4	35	10	145	30	450	-0.92	110	650
100R4-32	1.1/4"	32	42	10	145	30	450	-0.92	140	835
100R4-38	1.1/2"	38	48	10	145	30	450	-0.92	170	1050
100R4-51	2"	50.8	61	10	145	30	450	-0.92	250	1495
100R4-64	2.1/2"	63.5	74	10	145	30	450	-0.92	310	2010
100R4-76	3"	76.2	87	10	145	30	450	-0.92	380	2337
100R4-89	3.1/2"	90	102	10	145	30	450	-0.92	450	2940
100R4-102	4"	101.6	115	10	145	30	450	-0.92	510	3440
100R4-127	5"	127	145	10	145	30	450	-0.92	650	6195
100R4-152	6"	152	170	10	145	30	450	-0.92	752	7050

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

BREAKER HOSE ASSEMBLIES

1/2" EN853-2 Breaker Hoses

Comprising of 2 x 6 metre clamped together lengths of high quality 1/2" EN853-2 hydraulic hose, complete with 1/2" BSPP male end fittings.



1/2" BSPP Male x Male, 6 Metre

0400
BH08-08M08M-06MT
Tech Sheet 20002

Comprising of 2 x 9 metre clamped together lengths of high quality 1/2" EN853-2 hydraulic hose, complete with 1/2" BSPP male end fittings.



1/2" BSPP Male x Male, 9 Metre

0400
BH08-08M08M-09MT
Tech Sheet 20002

Comprising of 2 x 6 metre clamped together lengths of high quality 1/2" EN853-2 hydraulic hose, complete with 2 sets of flat face QRCs.



Flat Face Quick Release Couplings, 6 Metre

0400
BH08-08Q08P-06MT
Tech Sheet 20002

Other lengths available on request

Comprising of 2 x 9 metre clamped together lengths of high quality 1/2" EN853-2 hydraulic hose, complete with 2 sets of flat face QRCs.



Flat Face Quick Release Couplings, 9 Metre

0400
BH08-08Q08P-09MT
Tech Sheet 20002

Leader hoses comprising of 2 x 0.5 metre clamped together lengths of high quality 1/2" EN853-2 hydraulic hose, complete with 1 set of flat face QRCs one end and 1/2" BSPP males the other.



Leader Hose, Flat Face QRC x 1/2" BSPP Male, 0.5 Metre

0400
BH08-08Q08M-.5MT
Tech Sheet 20002

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC HOSE FERRULES

Ferrules



R1AT & R2AT Dual, Non-skive

0309	To Suit Hose ID
FT3-12-03CF	3/16"
FT3-12-04CF	1/4"
FT3-12-05CF	5/16"
FT3-12-06CF	3/8"
FT3-12-08CF	1/2"
FT3-12-10CF	5/8"
FT3-12-12CF	3/4"
FT3-12-16CF	1"
FT3-12-20CF	1.1/4"
FT3-12-24CF	1.1/2"
FT3-12-32CF	2"
Tech Sheet 3152	



2SC

0309	To Suit Hose ID
F2SC-04	1/4"
F2SC-06	3/8"
F2SC-08	1/2"
F2SC-12	3/4"
F2SC-16	1"
Tech Sheet 3152	



4SP Multi Spiral

0309	To Suit Hose ID
JMF57-06CF	3/8"
JMF57-08CF	1/2"
JMF57-10CF	5/8"
JMF57-12CF	3/4"
JMF57-16CF	1"
JMF57-20CF	1.1/4"
JMF57-24CF	1.1/2"
JMF57-32CF	2"
Tech Sheet 3152	

For all swage guide settings see Tech Sheets.



R7, R8 & 1SC

0309	To Suit Hose ID
FR79-03	3/16"
FR79-04	1/4"
FR79-05	5/16"
FR79-06	3/8"
FR79-08	1/2"
FR79-12	3/4"
Tech Sheet 3152	



R4

0309	To Suit Hose ID
R4F2-12	3/4"
R4F2-16	1"
R4F2-20	1.1/4"
R4F2-24	1.1/2"
R4F2-32	2"
Tech Sheet 3152	



PTFE, Smooth & Convoluted Bore

0309	To Suit Hose ID
PTFEF-03	3/16"
PTFEF-04	1/4"
PTFEF-05	5/16"
PTFEF-06	3/8"
PTFEF-08	1/2"
PTFEF-10	5/8"
PTFEF-12	3/4"
PTFEF-16	1"
Tech Sheet 3152	



4SH

0309	To Suit Hose ID
JMF4SH-12CF	3/4"
JMF4SH-16CF	1"
Tech Sheet 3152	

Go/No Go Gauge

Hydraulic hose collapse mandrels are used to check if the ferrules have collapsed enough after swaging. By placing this mandrel inside the fittings orifice after swaging, if it is not possible to push all the way though, the ferrule has been swagged enough. If it is still possible to push the mandrel all the way through, the ferrule needs swaging more.



Collapse Mandrel

0499	To Suit Hose ID
HOSEMAND-14	1/4"
HOSEMAND-38	3/8"
HOSEMAND-12	1/2"
HOSEMAND-58	5/8"
HOSEMAND-34	3/4"
HOSEMAND-1	1"

Fluid-Air Components Ltd

BSP

Hexavalent chromium free plating



Male, 60° Cone Inserts, BSPP

0309	Thread	To Suit Hose ID
BM0203CF	1/8"	3/16"
BM0204CF	1/8"	1/4"
BM0403CF	1/4"	3/16"
BM0404CF	1/4"	1/4"
BM0405CF	1/4"	5/16"
BM0406CF	1/4"	3/8"
BM0604CF	3/8"	1/4"
BM0605CF	3/8"	5/16"
BM0606CF	3/8"	3/8"
BM0608CF	3/8"	1/2"
BM0804CF	1/2"	1/4"
BM0806CF	1/2"	3/8"
BM0808CF	1/2"	1/2"
BM0810CF	1/2"	5/8"
BM1008CF	5/8"	1/2"
BM1010CF	5/8"	5/8"
BM1208CF	3/4"	1/2"
BM1210CF	3/4"	5/8"
BM1212CF	3/4"	3/4"
BM1612CF	1"	3/4"
BM1616CF	1"	1"
BM2016CF	1.1/4"	1"
BM2020CF	1.1/4"	1.1/4"
BM2420CF	1.1/2"	1.1/4"
BM2424CF	1.1/2"	1.1/2"
BM3232CF	2"	2"



Swivel Female, 60° Cone Inserts, BSPP

0309	Thread	To Suit Hose ID
BF0203CF	1/8"	3/16"
BF0204CF	1/8"	1/4"
BF0206CF	1/8"	3/8"
BF0403CF	1/4"	3/16"
BF0404CF	1/4"	1/4"
BF0405CF	1/4"	5/16"
BF0406CF	1/4"	3/8"
BF0604CF	3/8"	1/4"
BF0605CF	3/8"	5/16"
BF0606CF	3/8"	3/8"
BF0608CF	3/8"	1/2"
BF0804CF	1/2"	1/4"
BF0805CF	1/2"	5/16"
BF0806CF	1/2"	3/8"
BF0808CF	1/2"	1/2"
BF1008CF	5/8"	1/2"
BF1010CF	5/8"	5/8"
BF1208CF	3/4"	1/2"
BF1210CF	3/4"	5/8"
BF1212CF	3/4"	3/4"
BF1612CF	1"	3/4"
BF1616CF	1"	1"
BF2016CF	1.1/4"	1"
BF2020CF	1.1/4"	1.1/4"
BF2420CF	1.1/2"	1.1/4"
BF2424CF	1.1/2"	1.1/2"
BF3232CF	2"	2"



Female Swept 90°, 60° Cone Inserts, BSPP

0309	Thread	To Suit Hose ID
BF029003CF	1/8"	3/16"
BF029004CF	1/8"	1/4"
BF049003CF	1/4"	3/16"
BF049004CF	1/4"	1/4"
BF049005CF	1/4"	5/16"
BF049006CF	1/4"	3/8"
BF069004CF	3/8"	1/4"
BF069005CF	3/8"	5/16"
BF069006CF	3/8"	3/8"
BF069008CF	3/8"	1/2"
BF089006CF	1/2"	3/8"
BF089008CF	1/2"	1/2"
BF109008CF	5/8"	1/2"
BF109010CF	5/8"	5/8"
BF129008CF	3/4"	1/2"
BF129010CF	3/4"	5/8"
BF129012CF	3/4"	3/4"
BF169012CF	1"	3/4"
BF169016CF	1"	1"
BF209016CF	1.1/4"	1"
BF209020CF	1.1/4"	1.1/4"
BF249020CF	1.1/2"	1.1/4"
BF249024CF	1.1/2"	1.1/2"
BF329032CF	2"	2"



Female 45°, 60° Cone Inserts, BSPP

0309	Thread	To Suit Hose ID
BF024503CF	1/8"	3/16"
BF024504CF	1/8"	1/4"
BF044503CF	1/4"	3/16"
BF044504CF	1/4"	1/4"
BF044505CF	1/4"	5/16"
BF064504CF	3/8"	1/4"
BF064505CF	3/8"	5/16"
BF064506CF	3/8"	3/8"
BF064508CF	3/8"	1/2"
BF084506CF	1/2"	3/8"
BF084508CF	1/2"	1/2"
BF084510CF	1/2"	5/8"
BF104505CF	5/8"	5/16"
BF104508CF	5/8"	1/2"
BF104510CF	5/8"	5/8"
BF124508CF	3/4"	1/2"
BF124510CF	3/4"	5/8"
BF124512CF	3/4"	3/4"
BF164516CF	1"	1"
BF204520CF	1.1/4"	1.1/4"
BF244524CF	1.1/2"	1.1/2"
BF324532CF	2"	2"



Female 90° Compact, 60° Cone Inserts, BSPP

0309	Thread	To Suit Hose ID
BF0490C04CF	1/4"	1/4"
BF0690C06CF	3/8"	3/8"
BF0890C08CF	1/2"	1/2"
BF1290C12CF	3/4"	3/4"
BF1690C16CF	1"	1"

Fluid-Air Components Ltd

HYDRAULIC HOSE CONNECTORS

BSP

Hexavalent chromium free plating



Flat Faced, Female Inserts, BSPP

0309	Thread	To Suit Hose ID
BFF0404CF	1/4"	1/4"
BFF0406CF	1/4"	3/8"
BFF0604CF	3/8"	1/4"
BFF0605CF	3/8"	5/16"
BFF0606CF	3/8"	3/8"
BFF0608CF	3/8"	1/2"
BFF0806CF	1/2"	3/8"
BFF0808CF	1/2"	1/2"
BFF1008CF	5/8"	1/2"
BFF1010CF	5/8"	5/8"
BFF1208CF	3/4"	1/2"
BFF1210CF	3/4"	5/8"
BFF1212CF	3/4"	3/4"
BFF1612CF	1"	3/4"
BFF1616CF	1"	1"
BFF2020CF	1.1/4"	1.1/4"
BFF2424CF	1.1/2"	1.1/2"
BFF3232CF	2"	2"



Flat Faced, Female Swept 45° Elbow, BSPP

0309	Thread	To Suit Hose ID
BFF044504CF	1/4"	1/4"
BFF064506CF	3/8"	3/8"
BFF084508CF	1/2"	1/2"
BFF124512CF	3/4"	3/4"
BFF164516CF	1"	1"



Flat Faced, Female Swept 90° Elbow, BSPP

0309	Thread	To Suit Hose ID
BFF049004CF	1/4"	1/4"
BFF069006CF	3/8"	3/8"
BFF089008CF	1/2"	1/2"
BFF129012CF	3/4"	3/4"
BFF169016CF	1"	1"



Female O-Ring Face, 60° Cone Inserts, BSPP


0309	Thread	To Suit Hose ID
BF0404CF-OR	1/4"	1/4"
BF0604CF-OR	3/8"	1/4"
BF0606CF-OR	3/8"	3/8"
BF0806CF-OR	1/2"	3/8"
BF0808CF-OR	1/2"	1/2"
BF1008CF-OR	5/8"	1/2"
BF1010CF-OR	5/8"	5/8"
BF1212CF-OR	3/4"	3/4"
BF1616CF-OR	1"	1"



Taper Male Inserts, BSPT

0309	Thread	To Suit Hose ID
BMT0203CF	1/8"	3/16"
BMT0204CF	1/8"	1/4"
BMT0403CF	1/4"	3/16"
BMT0404CF	1/4"	1/4"
BMT0405CF	1/4"	5/16"
BMT0406CF	1/4"	3/8"
BMT0604CF	3/8"	1/4"
BMT0605CF	3/8"	5/16"
BMT0606CF	3/8"	3/8"
BMT0608CF	3/8"	1/2"
BMT0806CF	1/2"	3/8"
BMT0808CF	1/2"	1/2"
BMT0810CF	1/2"	5/8"
BMT1010CF	5/8"	5/8"
BMT1208CF	3/4"	1/2"
BMT1210CF	3/4"	5/8"
BMT1212CF	3/4"	3/4"
BMT1612CF	1"	3/4"
BMT1616CF	1"	1"
BMT2016CF	1.1/4"	1"
BMT2020CF	1.1/4"	1.1/4"
BMT2420CF	1.1/2"	1.1/4"
BMT2424CF	1.1/2"	1.1/2"
BMT3224CF	2"	1.1/2"
BMT3232CF	2"	2"

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER



For **Hydraulic Adaptors** see pages **52-81**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

JIC

Hexavalent chromium free plating



JIC 37° Male Inserts

0309	Thread	To Suit Hose ID
JM0403CF	7/16"	3/16"
JM0404CF	7/16"	1/4"
JM0504CF	1/2"	1/4"
JM0505CF	1/2"	5/16"
JM0604CF	9/16"	1/4"
JM0605CF	9/16"	5/16"
JM0606CF	9/16"	3/8"
JM0608CF	9/16"	1/2"
JM0805CF	3/4"	5/16"
JM0806CF	3/4"	3/8"
JM0808CF	3/4"	1/2"
JM1006CF	7/8"	3/8"
JM1008CF	7/8"	1/2"
JM1010CF	7/8"	5/8"
JM1012CF	7/8"	3/4"
JM1208CF	3/4"	1/2"
JM1210CF	1.1/16"	5/8"
JM1212CF	1.1/16"	3/4"
JM1216CF	1.1/16"	1"
JM1412CF	1.3/16"	3/4"
JM1416CF	1.3/16"	1"
JM1612CF	1.5/16"	3/4"
JM1616CF	1.5/16"	1"
JM2016CF	1.5/8"	1"
JM2020CF	1.5/8"	1.1/4"
JM2420CF	1.7/8"	1.1/4"
JM2424CF	1.7/8"	1.1/2"
JM3232CF	2.1/2"	2"



JIC 37° Swivel Female Inserts

0309	Thread	To Suit Hose ID
JF0403CF	7/16"	3/16"
JF0404CF	7/16"	1/4"
JF0406CF	7/16"	3/8
JF0503CF	1/2"	3/16"
JF0504CF	1/2"	1/4"
JF0505CF	1/2"	5/16"
JF0506CF	1/2"	3/8"
JF0604CF	9/16"	1/4"
JF0605CF	9/16"	5/16"
JF0606CF	9/16"	3/8"
JF0805CF	3/4"	5/16"
JF0806CF	3/4"	3/8"
JF0808CF	3/4"	1/2"
JF1006CF	7/8"	3/8"
JF1008CF	7/8"	1/2"
JF1010CF	7/8"	5/8"
JF1012CF	7/8"	3/4"
JF1208CF	1.1/16"	1/2"
JF1210CF	1.1/16"	5/8"
JF1212CF	1.1/16"	3/4"
JF1216CF	1.1/16"	1"
JF1412CF	1.3/16"	3/4"
JF1416CF	1.3/16"	1"
JF1612CF	1.5/16"	3/4"
JF1616CF	1.5/16"	1"
JF2016CF	1.5/8"	1"
JF2020CF	1.5/8"	1.1/4"
JF2420CF	1.7/8"	1.1/4"
JF2424CF	1.7/8"	1.1/2"
JF3232CF	2.1/2"	2"



JIC 37° Female Swept Elbow Inserts

0309	Thread	To Suit Hose ID
JF049003CF	7/16"	3/16"
JF049004CF	7/16"	1/4"
JF059003CF	1/2"	3/16"
JF059004CF	1/2"	1/4"
JF059005CF	1/2"	5/16"
JF059006CF	1/2"	3/8"
JF069004CF	9/16"	1/4"
JF069005CF	9/16"	5/16"
JF069006CF	9/16"	3/8"
JF089005CF	3/4"	5/16"
JF089006CF	3/4"	3/8"
JF089008CF	3/4"	1/2"
JF109006CF	7/8"	3/8"
JF109008CF	7/8"	1/2"
JF109010CF	7/8"	5/8"
JF109012CF	7/8"	3/4"
JF129008CF	1.1/16"	1/2"
JF129010CF	1.1/16"	5/8"
JF129012CF	1.1/16"	3/4"
JF129016CF	1.1/16"	1"
JF149012CF	1.3/16"	3/4"
JF149016CF	1.3/16"	1"
JF169012CF	1.5/16"	3/4"
JF169016CF	1.5/16"	1"
JF209016CF	1.5/8"	1"
JF209020CF	1.5/8"	1.1/4"
JF249020CF	1.7/8"	1.1/4"
JF249024CF	1.7/8"	1.1/2"
JF329032CF	2.1/2"	2"

JIC 37° Female Swept Elbow Inserts

0309	Thread	To Suit Hose ID
JF044503CF	7/16"	3/16"
JF044504CF	7/16"	1/4"
JF054504CF	1/2"	1/4"
JF054505CF	1/2"	5/16"
JF054506CF	1/2"	3/8"
JF064504CF	9/16"	1/4"
JF064505CF	9/16"	5/16"
JF064506CF	9/16"	3/8"
JF084506CF	3/4"	3/8"
JF084508CF	3/4"	1/2"
JF104506CF	7/8"	3/8"
JF104508CF	7/8"	1/2"
JF104510CF	7/8"	5/8"



0309	Thread	To Suit Hose ID
JF104512CF	7/8"	3/4"
JF124508CF	1.1/16"	1/2"
JF124510CF	1.1/16"	5/8"
JF124512CF	1.1/16"	3/4"
JF124516CF	1.1/16"	1"
JF144512CF	1.3/16"	3/4"
JF144516CF	1.3/16"	1"
JF164512CF	1.5/16"	3/4"
JF164516CF	1.5/16"	1"
JF204516CF	1.5/8"	1"
JF204520CF	1.5/8"	1.1/4"
JF244524CF	1.7/8"	1.1/2"
JF324532CF	2.1/2"	2"



JIC 37° Female Compact 90° Elbow Inserts

0309	Thread	To Suit Hose ID
JF0490K04CF	7/16"	1/4"
JF0690K04CF	9/16"	1/4"
JF0690K06CF	9/16"	3/8"
JF0890K06CF	3/4"	3/8"
JF0890K08CF	3/4"	1/2"
JF1090K08CF	7/8"	1/2"
JF1090K10CF	7/8"	5/8"
JF1290K12CF	1.1/16"	3/4"
JF1690K16CF	1.5/16"	1"

Fluid-Air Components Ltd

HYDRAULIC HOSE CONNECTORS

Metric Light Series

Hexavalent chromium free plating



Metric Male 24° Cone Seat, L Series, DIN 3853

0309	Thread	To Suit Hose ID	Size
HMML03-M12CF	M12 x 1.5	3/16"	6L
HMML04-M12CF	M12 x 1.5	1/4"	6L
HMML04-M14CF	M14 x 1.5	1/4"	8L
HMML04-M16CF	M16 x 1.5	1/4"	10L
HMML04-M18CF	M18 x 1.5	1/4"	12L
HMML05-M14CF	M14 x 1.5	5/16"	8L
HMML05-M16CF	M16 x 1.5	5/16"	10L
HMML05-M18CF	M18 x 1.5	5/16"	12L
HMML05-M22CF	M22 x 1.5	5/16"	15L
HMML06-M16CF	M16 x 1.5	3/8"	10L
HMML06-M18CF	M18 x 1.5	3/8"	12L
HMML06-M22CF	M22 x 1.5	3/8"	15L
HMML08-M18CF	M18 x 1.5	1/2"	12L
HMML08-M22CF	M22 x 1.5	1/2"	15L
HMML08-M26CF	M26 x 1.5	1/2"	18L
HMML10-M22CF	M22 x 1.5	5/8"	15L
HMML10-M26CF	M26 x 1.5	5/8"	18L
HMML10-M30CF	M30 x 2	5/8"	22L
HMML12-M26CF	M26 x 1.5	3/4"	18L
HMML12-M30CF	M30 x 2	3/4"	22L
HMML16-M36CF	M36 x 2	1"	28L
HMML20-M45CF	M45 x 2	1.1/4"	35L
HMML24-M45CF	M45 x 2	1.1/2"	35L
HMML24-M52CF	M52 x 2	1.1/2"	42L



Metric Female 24° Cone Seat, L Series with O-Ring, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMFL03-M12CF	M12 x 1.5	3/16"	6L
HMFL04-M12CF	M12 x 1.5	1/4"	6L
HMFL04-M14CF	M14 x 1.5	1/4"	8L
HMFL04-M16CF	M16 x 1.5	1/4"	10L
HMFL04-M18CF	M18 x 1.5	1/4"	12L
HMFL06-M16CF	M16 x 1.5	3/8"	10L
HMFL05-M16CF	M16 x 1.5	5/16"	10L
HMFL06-M18CF	M18 x 1.5	3/8"	12L
HMFL06-M22CF	M22 x 1.5	3/8"	15L
HMFL08-M22CF	M22 x 1.5	1/2"	15L
HMFL08-M26CF	M26 x 1.5	1/2"	18L
HMFL10-M26CF	M26 x 1.5	5/8"	18L
HMFL10-M30CF	M30 x 1.5	5/8"	22L
HMFL12-M30CF	M30 x 2	3/4"	22L
HMFL12-M36CF	M36 x 2	3/4"	28L
HMFL16-M36CF	M36 x 2	1"	28L
HMFL20-M45CF	M45 x 2	1.1/4"	35L
HMFL24-M52CF	M52 x 2	1.1/2"	42L



90° Metric Female 24° Cone Seat, L Series with O-Ring, DIN 3853

0309	Thread	To Suit Hose ID	Size
HMFL0390-M12CF	M12 x 1.5	3/16"	6L
HMFL0490-M12CF	M12 x 1.5	1/4"	6L
HMFL0490-M14CF	M14 x 1.5	1/4"	8L
HMFL0490-M16CF	M16 x 1.5	1/4"	10L
HMFL0490-M18CF	M18 x 1.5	1/4"	12L
HMFL0590-M18CF	M18 x 1.5	5/16"	12L
HMFL0690-M16CF	M16 x 1.5	3/8"	10L
HMFL0690-M18CF	M18 x 1.5	3/8"	12L
HMFL0890-M22CF	M22 x 1.5	1/2"	15L
HMFL0890-M26CF	M26 x 1.5	1/2"	18L
HMFL1090-M26CF	M26 x 1.5	5/8"	18L
HMFL1090-M30CF	M30 x 2	5/8"	22L
HMFL1290-M26CF	M26 x 1.5	3/4"	18L
HMFL1290-M30CF	M30 x 2	3/4"	22L
HMFL1690-M36CF	M36 x 2	1"	28L
HMFL2090-M45CF	M45 x 2	1.1/4"	35L
HMFL2490-M52CF	M52 x 2	1.1/2"	42L



45° Metric Female 24° Cone Seat, L Series with O-Ring, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMFL03-45-M12CF	M12 x 1.5	3/16"	6L
HMFL04-45-M12CF	M12 x 1.5	1/4"	6L
HMFL04-45-M14CF	M14 x 1.5	1/4"	8L
HMFL04-45-M16CF	M16 x 1.5	1/4"	10L
HMFL05-45-M16CF	M16 x 1.5	5/16"	10L
HMFL05-45-M18CF	M18 x 1.5	5/16"	12L
HMFL06-45-M16CF	M16 x 1.5	3/8"	10L
HMFL06-45-M18CF	M18 x 1.5	3/8"	12L
HMFL08-45-M22CF	M22 x 1.5	1/2"	15L
HMFL08-45-M26CF	M26 x 1.5	1/2"	18L
HMFL10-45-M26CF	M26 x 1.5	5/8"	18L
HMFL12-45-M30CF	M30 x 2	3/4"	22L
HMFL16-45-M36CF	M36 x 2	1"	28L
HMFL20-45-M45CF	M45 x 2	1.1/4"	35L
HMFL24-45-M52CF	M52 x 2	1.1/2"	42L



Standpipe, L Series

0309	OD mm	To Suit Hose ID
HSSP04-06CF	6	1/4"
HSSP04-08CF	8	1/4"
HSSP06-10CF	10	3/8"
HSSP06-12CF	12	3/8"
HSSP06-15CF	15	3/8"
HSSP08-15CF	15	1/2"
HSSP08-18CF	18	1/2"
HSSP10-18CF	18	5/8"
HSSP10-22CF	22	5/8"
HSSP12-22CF	22	3/4"
HSSP16-28CF	28	1"
HSSP20-35CF	35	1.1/4"
HSSP24-42CF	42	1.1/2"



45° Standpipe, L Series

0309	OD mm	To Suit Hose ID
HSP04-45-06CF	6	1/4"
HSP05-45-08CF	8	5/16"
HSP06-45-08CF	8	3/8"
HSP05-45-10CF	10	5/16"
HSP06-45-10CF	10	3/8"
HSP06-45-12CF	12	3/8"
HSP06-45-15CF	15	3/8"
HSP08-45-15CF	15	1/2"
HSP08-45-18CF	18	1/2"
HSP10-45-18CF	18	5/8"
HSP10-45-22CF	22	5/8"
HSP12-45-22CF	22	3/4"
HSP16-45-28CF	28	1"
HSP20-45-35CF	35	1.1/4"



90° Standpipe, L Series

0309	OD mm	To Suit Hose ID
HSP04-90-06CF	6	1/4"
HSP04-90-08CF	8	1/4"
HSP06-90-10CF	10	3/8"
HSP06-90-12CF	12	3/8"
HSP08-90-15CF	15	1/2"
HSP08-90-18CF	18	1/2"
HSP10-90-18CF	18	5/8"
HSP12-90-22CF	22	3/4"
HSP16-90-28CF	28	1"
HSP20-90-35CF	35	1.1/4"

Fluid-Air Components Ltd

Metric Heavy Series

Hexavalent chromium free plating



Metric Male 24° Cone Seat, S Series, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMMS03-M16CF	M16 x 1.5	3/16"	8S
HMMS04-M14CF	M14 x 1.5	1/4"	6S
HMMS04-M16CF	M16 x 1.5	1/4"	8S
HMMS04-M18CF	M18 x 1.5	1/4"	10S
HMMS05-M18CF	M18 x 1.5	5/16"	10S
HMMS05-M20CF	M20 x 1.5	5/16"	12S
HMMS06-M18CF	M18 x 1.5	3/8"	10S
HMMS06-M20CF	M20 x 1.5	3/8"	12S
HMMS06-M22CF	M22 x 1.5	3/8"	14S
HMMS06-M24CF	M24 x 1.5	3/8"	16S
HMMS08-M24CF	M24 x 1.5	1/2"	16S
HMMS10-M30CF	M30 x 2	5/8"	20S
HMMS12-M30CF	M30 x 2	3/4"	20S
HMMS12-M36CF	M36 x 2	3/4"	25S
HMMS16-M36CF	M36 x 1.5	1"	25S
HMMS16-M42CF	M42 x 2	1"	30S
HMMS20-M42CF	M42 x 2	1.1/4"	30S
HMMS20-M52CF	M52 x 2	1.1/4"	38S
HMMS24-M52CF	M52 x 2	1.1/2"	38S



Metric Female 24° Cone Seat, S Series, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMFS03-M16CF	M16 x 1.5	3/16"	8S
HMFS04-M14CF	M14 x 1.5	1/4"	6S
HMFS04-M16CF	M16 x 1.5	1/4"	8S
HMFS04-M18CF	M18 x 1.5	1/4"	10S
HMFS05-M18CF	M18 x 1.5	5/16"	10S
HMFS05-M20CF	M20 x 1.5	5/16"	12S
HMFS06-M16CF	M16 x 1.5	3/8"	8S
HMFS06-M18CF	M18 x 1.5	3/8"	10S
HMFS06-M20CF	M20 x 1.5	3/8"	12S
HMFS06-M22CF	M22 x 1.5	3/8"	14S
HMFS08-M22CF	M22 x 1.5	1/2"	14S
HMFS08-M24CF	M24 x 1.5	1/2"	16S
HMFS08-M30CF	M30 x 2	1/2"	20S
HMFS10-M24CF	M24 x 1.5	5/8"	16S
HMFS10-M30CF	M30 x 2	5/8"	20S
HMFS12-M30CF	M30 x 2	3/4"	20S
HMFS12-M36CF	M36 x 2	3/4"	25S
HMFS16-M36CF	M36 x 2	1"	25S
HMFS16-M42CF	M42 x 2	1"	30S
HMFS20-M52CF	M52 x 2	1.1/4"	38S
HMFS24-M52CF	M52 x 2	1.1/2"	38S



90° Metric Female 24° Cone Seat, S Series, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMFS0390-M16CF	M16 x 1.5	3/16"	8S
HMFS0490-M14CF	M14 x 1.5	1/4"	6S
HMFS0490-M16CF	M16 x 1.5	1/4"	8S
HMFS0490-M18CF	M18 x 1.5	1/4"	10S
HMFS0490-M20CF	M20 x 1.5	1/4"	12S
HMFS0590-M18CF	M18 x 1.5	5/16"	10S
HMFS0590-M20CF	M20 x 1.5	5/16"	12S
HMFS0690-M18CF	M18 x 1.5	3/8"	10S
HMFS0690-M20CF	M20 x 1.5	3/8"	12S
HMFS0690-M22CF	M22 x 1.5	3/8"	14S
HMFS0890-M24CF	M24 x 1.5	1/2"	16S
HMFS1090-M24CF	M24 x 1.5	5/8"	16S
HMFS1090-M30CF	M30 x 2	5/8"	20S
HMFS1290-M30CF	M30 x 2	3/4"	20S
HMFS1290-M36CF	M36 x 2	3/4"	25S
HMFS1690-M36CF	M36 x 2	1"	25S
HMFS1690-M42CF	M42 x 2	1"	30S
HMFS2090-M52CF	M52 x 2	1.1/4"	38S
HMFS2490-M52CF	M52 x 2	1.1/2"	38S



45° Metric Female 24° Cone Seat, S Series, DIN 3865

0309	Thread	To Suit Hose ID	Size
HMFS03-45-M16CF	M16 x 1.5	3/16"	8S
HMFS04-45-M14CF	M14 x 1.5	1/4"	6S
HMFS04-45-M16CF	M16 x 1.5	1/4"	8S
HMFS04-45-M18CF	M18 x 1.5	1/4"	10S
HMFS05-45-M18CF	M18 x 1.5	5/16"	10S
HMFS05-45-M20CF	M20 x 1.5	5/16"	12S
HMFS06-45-M20CF	M20 x 1.5	3/8"	12S
HMFS06-45-M22CF	M22 x 1.5	3/8"	14S
HMFS08-45-M24CF	M24 x 1.5	1/2"	16S
HMFS10-45-M30CF	M30 x 2	5/8"	20S
HMFS12-45-M30CF	M30 x 2	3/4"	20S
HMFS12-45-M36CF	M36 x 2	3/4"	25S
HMFS16-45-M36CF	M36 x 2	1"	25S
HMFS16-45-M42CF	M42 x 2	1"	30S
HMFS20-45-M52CF	M52 x 2	1.1/4"	38S
HMFS24-45-M52CF	M52 x 2	1.1/2"	38S



Standpipe, S Series

0309	OD mm	To Suit Hose ID
HSSP04-10CF	10	1/4"
HSSP06-14CF	14	3/8"
HSSP08-16CF	16	1/2"
HSSP10-20CF	20	5/8"
HSSP12-20CF	20	3/4"
HSSP12-25CF	25	3/4"
HSSP16-25CF	25	1"
HSSP16-30CF	30	1"
HSSP20-38CF	38	1.1/4"



45° Standpipe, S Series

0309	OD mm	To Suit Hose ID
HSSP04-45-08CF	8	1/4"
HSSP04-45-10CF	10	1/4"
HSSP04-45-12CF	12	1/4"
HSSP05-45-12CF	12	5/16"
HSSP06-45-14CF	14	3/8"
HSSP08-45-14CF	14	1/2"
HSSP08-45-16CF	16	1/2"
HSSP10-45-16CF	16	5/8"
HSSP10-45-20CF	20	5/8"
HSSP12-45-20CF	20	3/4"
HSSP12-45-25CF	25	3/4"
HSSP16-45-25CF	25	1"
HSSP16-45-30CF	30	1"
HSSP16-45-38CF	38	1"
HSSP20-45-30CF	30	1.1/4"
HSSP20-45-38CF	38	1.1/4"



90° Standpipe, S Series

0309	OD mm	To Suit Hose ID
HSSP04-90-08CF	8	1/4"
HSSP04-90-10CF	10	1/4"
HSSP06-90-14CF	14	3/8"
HSSP08-90-16CF	16	1/2"
HSSP10-90-20CF	20	5/8"
HSSP12-90-20CF	20	3/4"
HSSP12-90-25CF	25	3/4"
HSSP16-90-25CF	25	1"
HSSP16-90-30CF	30	1"

Fluid-Air Components Ltd

HYDRAULIC HOSE CONNECTORS

ORFS

Hexavalent chromium free plating



ORFS Male (O-Ring Face)

0309	Thread	To Suit Hose ID
ORFSM0404CF	9/16"	1/4"
ORFSM0604CF	11/16"	1/4"
ORFSM0605CF	11/16"	5/16"
ORFSM0606CF	11/16"	3/8"
ORFSM0806CF	13/16"	3/8"
ORFSM0808CF	13/16"	1/2"
ORFSM1008CF	1"	1/2"
ORFSM1010CF	1"	5/8"
ORFSM1208CF	1.3/16"	1/2"
ORFSM1210CF	1.3/16"	5/8"
ORFSM1212CF	1.3/16"	3/4"
ORFSM1612CF	1.7/16"	3/4"
ORFSM1616CF	1.7/16"	1"
ORFSM2020CF	1.11/16"	1.1/4"
ORFSM2424CF	2"	1.1/2"



ORFS Female 45º Elbow Inserts

0309	Thread	To Suit Hose ID
ORFSF044504CF	9/16"	1/4"
ORFSF064504CF	11/16"	1/4"
ORFSF064505CF	11/16"	5/16"
ORFSF064506CF	11/16"	3/8"
ORFSF084506CF	13/16"	3/8"
ORFSF084508CF	13/16"	1/2"
ORFSF104508CF	1"	1/2"
ORFSF104510CF	1"	5/8"
ORFSF104512CF	1"	3/4"
ORFSF124508CF	1.3/16"	1/2"
ORFSF124510CF	1.3/16"	5/8"
ORFSF124512CF	1.3/16"	3/4"
ORFSF164512CF	1.7/16"	3/4"
ORFSF164516CF	1.7/16"	1"
ORFSF204520CF	1.11/16"	1.1/4"
ORFSF244524CF	2"	1.1/2"



ORFS Female Insert

0309	Thread	To Suit Hose ID
ORFSF0404CF	9/16"	1/4"
ORFSF0604CF	11/16"	1/4"
ORFSF0605CF	11/16"	5/16"
ORFSF0606CF	11/16"	3/8"
ORFSF0806CF	13/16"	3/8"
ORFSF0808CF	13/16"	1/2"
ORFSF1008CF	1"	1/2"
ORFSF1010CF	1"	5/8"
ORFSF1012CF	1"	3/4"
ORFSF1208CF	1.3/16"	1/2"
ORFSF1210CF	1.3/16"	5/8"
ORFSF1212CF	1.3/16"	3/4"
ORFSF1612CF	1.7/16"	3/4"
ORFSF1616CF	1.7/16"	1"
ORFSF2020CF	1.11/16"	1.1/4"
ORFSF2424CF	2"	1.1/2"



ORFS Female 90º Elbow Insert

0309	Thread	To Suit Hose ID
ORFSF049004CF	9/16"	1/4"
ORFSF069004CF	11/16"	1/4"
ORFSF069005CF	11/16"	5/16"
ORFSF069006CF	11/16"	3/8"
ORFSF089006CF	13/16"	3/8"
ORFSF089008CF	13/16"	1/2"
ORFSF109008CF	1"	1/2"
ORFSF109010CF	1"	5/8"
ORFSF109012CF	1"	3/4"
ORFSF129008CF	1.3/16"	1/2"
ORFSF129010CF	1.3/16"	5/8"
ORFSF129012CF	1.3/16"	3/4"
ORFSF169012CF	1.7/16"	3/4"
ORFSF169016CF	1.7/16"	1"
ORFSF209016CF	1.11/16"	1"
ORFSF209020CF	1.11/16"	1.1/4"
ORFSF249024CF	2"	1.1/2"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC HOSE CONNECTORS

Banjos

Hexavalent chromium free plating



BSPP Banjo Bolts

0309	Thread
BB02CF	1/8"
BB04CF	1/4"
BB06CF	3/8"
BB08CF	1/2"
BB10CF	5/8"
BB12CF	3/4"
BB16CF	1"



BSPP Banjo Inserts

0309	To Suit Bolt Thread	To Suit Hose ID
B0203CF	1/8"	3/16"
B0204CF	1/8"	1/4"
B0403CF	1/4"	3/16"
B0404CF	1/4"	1/4"
B0405CF	1/4"	5/16"
B0406CF	1/4"	3/8"
B0604CF	3/8"	1/4"
B0605CF	3/8"	5/16"
B0606CF	3/8"	3/8"
B0608CF	3/8"	1/2"
B0806CF	1/2"	3/8"
B0808CF	1/2"	1/2"
B1008CF	5/8"	1/2"
B1010CF	5/8"	5/8"
B1210CF	3/4"	5/8"
B1212CF	3/4"	3/4"
B1612CF	1"	3/4"
B1616CF	1"	1"



Metric Banjo Bolts

0309	Thread
BBJM-10-15	M10 x 1.0
BBJM-12-15	M12 x 1.5
BBJM-14-15	M14 x 1.5
BBJM-16-15	M16 x 1.5
BBJM-18-15	M18 x 1.5
BBJM-20-15	M20 x 1.5
BBJM-22-15	M22 x 1.5
BBJM-26-15	M26 x 1.5
BBJM-30-15	M30 x 1.5



Metric Banjo Inserts

0309	To Suit Bolt Thread	To Suit Hose ID
BJM-03-10	M10 x 1.0	3/16"
BJM-03-12	M12 x 1.5	3/16
BJM-04-10	M10 x 1.5	1/4"
BJM-04-12	M12 x 1.5	1/4"
BJM-04-14	M14 x 1.5	1/4"
BJM-05-14	M14 x 1.5	5/16"
BJM-05-16	M16 x 1.5	5/16"
BJM-05-18	M18 x 1.5	5/16"
BJM-06-14	M14 x 1.5	3/8"
BJM-06-16	M16 x 1.5	3/8"
BJM-06-18	M18 x 1.5	3/8"
BJM-06-22	M22 x 1.5	3/8"
BJM-08-16	M16 x 1.5	1/2"
BJM-08-18	M18 x 1.5	1/2"
BJM-08-22	M22 x 1.5	1/2"
BJM-10-22	M22 x 1.5	5/8"
BJM-10-26	M26 x 1.5	5/8"
BJM-12-22	M22 x 1.5	3/4"
BJM-12-26	M26 x 1.5	3/4"
BJM-16-30	M30 x 1.5	1"

NPT



Male Inserts

0309	Thread	To Suit Hose ID
NPTM0203CF	1/8"	3/16"
NPTM0204CF	1/8"	1/4"
NPTM0403CF	1/4"	3/16"
NPTM0404CF	1/4"	1/4"
NPTM0405CF	1/4"	5/16"
NPTM0406CF	1/4"	3/8"
NPTM0604CF	3/8"	1/4"
NPTM0605CF	3/8"	5/16"
NPTM0606CF	3/8"	3/8"
NPTM0608CF	3/8"	1/2"
NPTM0805CF	1/2"	5/16"
NPTM0806CF	1/2"	3/8"
NPTM0808CF	1/2"	1/2"
NPTM0810CF	1/2"	5/8"
NPTM0812CF	1/2"	3/4"
NPTM1208CF	3/4"	1/2"
NPTM1210CF	3/4"	5/8"
NPTM1212CF	3/4"	3/4"
NPTM1616CF	1"	1"
NPTM1620CF	1"	1.1/4"
NPTM2016CF	1.1/4"	1"
NPTM2020CF	1.1/4"	1.1/4"
NPTM2424CF	1.1/2"	1.1/2"
NPTM3232CF	2"	2"

Hose Joint



Equal

0309	To Suit Hose ID
HJ0404CF	1/4"
HJ0505CF	5/16"
HJ0606CF	3/8"
HJ0808CF	1/2"
HJ1010CF	5/8"
HJ1212CF	3/4"
HJ1616CF	1"

Complete banjo fitting sets require self centering bonded seals, see page 110

Fluid-Air Components Ltd

HYDRAULIC HOSE CONNECTORS

SAE 3000 PSI (3K)

Hexavalent chromium free plating



Straight Flanges

0309	Flange ND	To Suit Hose ID
HFL3-08-08CF	1/2"	1/2"
HFL3-08-12CF	3/4"	1/2"
HFL3-10-12CF	3/4"	5/8"
HFL3-12-12CF	3/4"	3/4"
HFL3-12-16CF	1"	3/4"
HFL3-16-16CF	1"	1"
HFL3-16-20CF	1.1/4"	1"
HFL3-20-20CF	1.1/4"	1.1/4"
HFL3-20-24CF	1.1/2"	1.1/4"
HFL3-24-24CF	1.1/2"	1.1/2"
HFL3-24-32CF	2"	1.1/2"
HFL3-32-32CF	2"	2"



90° Flanges

0309	Flange ND	To Suit Hose ID
HFL390-08-08CF	1/2"	1/2"
HFL390-08-12CF	3/4"	1/2"
HFL390-12-12CF	3/4"	3/4"
HFL390-12-16CF	1"	3/4"
HFL390-16-16CF	1"	1"
HFL390-16-20CF	1.1/4"	1"
HFL390-20-20CF	1.1/4"	1.1/4"
HFL390-20-24CF	1.1/2"	1.1/4"
HFL390-24-24CF	1.1/2"	1.1/2"
HFL390-24-32CF	2"	1.1/2"
HFL390-32-32CF	2"	2"



45° Flanges

0309	Flange ND	To Suit Hose ID
HFL345-12-12CF	3/4"	3/4"
HFL345-16-12CF	3/4"	1"
HFL345-16-16CF	1"	1"
HFL345-16-20CF	1.1/4"	1"
HFL345-20-20CF	1.1/4"	1.1/4"
HFL345-20-24CF	1.1/2"	1.1/4"
HFL345-24-24CF	1.1/2"	1.1/2"
HFL345-24-32CF	2"	1.1/2"
HFL345-32-32CF	2"	2"

SAE 6000 PSI (6K)



Straight Flanges

0309	Flange ND	To Suit Hose ID
HFL6-08-08CF	1/2"	1/2"
HFL6-12-12CF	3/4"	3/4"
HFL6-12-16CF	1"	3/4"
HFL6-16-16CF	1"	1"
HFL6-16-20CF	1.1/4"	1"
HFL6-20-20CF	1.1/4"	1.1/4"
HFL6-20-24CF	1.1/2"	1.1/4"
HFL6-24-24CF	1.1/2"	1.1/2"
HFL6-32-32CF	2"	2"



90° Flanges

0309	Flange ND	To Suit Hose ID
HFL690-08-08CF	1/2"	1/2"
HFL690-08-12CF	3/4"	1/2"
HFL690-12-12CF	3/4"	3/4"
HFL690-12-16CF	1"	3/4"
HFL690-16-16CF	1"	1"
HFL690-16-20CF	1.1/4"	1"
HFL690-20-20CF	1.1/4"	1.1/4"
HFL690-20-24CF	1.1/2"	1.1/4"
HFL690-24-24CF	1.1/2"	1.1/2"
HFL690-32-32CF	2"	2"



45° Flanges

0309	Flange ND	To Suit Hose ID
HFL645-08-08CF	1/2"	1/2"
HFL645-08-12CF	3/4"	1/2"
HFL645-12-12CF	3/4"	3/4"
HFL645-12-16CF	1"	3/4"
HFL645-16-16CF	1"	1"
HFL645-16-20CF	1.1/4"	1"
HFL645-20-20CF	1.1/4"	1.1/4"
HFL645-20-24CF	1.1/2"	1.1/4"
HFL645-24-24CF	1.1/2"	1.1/2"
HFL645-32-32CF	2"	2"

Split Flange Half

Sold as Halves



3000 psi

0300	Flange Size	Bolt Type Metric	Bolt Type UNC
FH3001	1/2"	M8 x 25	5/16" x 1.1/4"
FH3002	3/4"	M10 x 30	3/8" x 1.1/4"
FH3003	1"	M10 x 30	3/8" x 1.1/4"
FH3004	1.1/4"	M10 x 35	7/16" x 1.1/2"
FH3005	1.1/2"	M12 x 35	1/2" x 1.1/2"
FH3006	2"	M12 x 35	1/2" x 1.1/2"
FH3007	2.1/2"	M12 x 40	1/2" x 1.1/2"
FH3011	5"	M16 x 50	5/8" x 2"
Tech Sheet 1626			

Sold as Halves



6000 psi

0300	Flange Size	Bolt Type Metric	Bolt Type UNC
FH6001	1/2"	M8 x 30	5/16" x 1.1/4"
FH6002	3/4"	M10 x 35	3/8" x 1.1/2"
FH6003	1"	M12 x 45	-
FH6013	1"	-	7/16" x 1.1/4"
FH6004	1.1/4"	M14 x 50	-
FH6044	1.1/4"	-	1/2" x 1.3/4"
FH6005	1.1/2"	M16 x 55	5/8" x 2"
FH6006	2"	M20 x 65	3/4" x 2.1/2"
Tech Sheet 1626			

Bolts, washers and O-rings are not included and must be purchased separately, see page 108

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INTERLOCK HOSE CONNECTORS

Standard hydraulic adaptors do not adhere to the working pressure of multi spiral hose. Please use KR500 Hydraulic Adaptors for high pressure and multi spiral applications.
See pages **82-84**

Ferrule



4SH

0309	To Suit Hose ID
JMF4SH-12CF	3/4"
JMF4SH-16CF	1"
Tech Sheet 3152	



For **Hydraulic Test Kits** see page **272**

BSPP



Female

0309	Thread	To Suit Hose ID
JMBSPF-12-12CF	3/4"	3/4"
JMBSPF-16-12CF	1"	3/4"
JMBSPF-16-16CF	1"	1"
JMBSPF-20-16CF	1.1/4"	1"



Male

0309	Thread	To Suit Hose ID
JMBSPM-12-12CF	3/4"	3/4"
JMBSPM-16-12CF	1"	3/4"
JMBSPM-16-16CF	1"	1"
JMBSPM-20-16CF	1.1/4"	1"



45° Elbow

0309	Thread	To Suit Hose ID
JMBSPF45-12-12CF	3/4"	3/4"
JMBSPF45-16-12CF	1"	3/4"
JMBSPF45-16-16CF	1"	1"
JMBSPF45-20-16CF	1.1/4"	1"



90° Elbow

0309	Thread	To Suit Hose ID
JMBSPF90-12-12CF	3/4"	3/4"
JMBSPF90-16-12CF	1"	3/4"
JMBSPF90-16-16CF	1"	1"
JMBSPF90-20-16CF	1.1/4"	1"

JIC



Female

0309	Thread	To Suit Hose ID
JMJICF-17-12CF	1.1/16"	3/4"
JMJICF-21-12CF	1.5/16"	3/4"
JMJICM-21-16CF	1.5/16"	1"
JMJICF-26-16CF	1.5/8"	1"



Male

0309	Thread	To Suit Hose ID
JMJICMM-17-12CF	1.1/16"	3/4"
JMJICMM-21-12CF	1.5/16"	3/4"
JMJICMM-21-16CF	1.5/16"	1"
JMJICMM-26-16CF	1.5/8"	1"



45° Elbow

0309	Thread	To Suit Hose ID
JMJICF45-17-12CF	1.1/16"	3/4"
JMJICF45-21-12CF	1.5/16"	3/4"
JMJICF45-21-16CF	1.5/16"	1"
JMJICF45-26-16CF	1.5/8"	1"



90° Elbow

0309	Thread	To Suit Hose ID
JMJICF90-17-12CF	1.1/16"	3/4"
JMJICF90-21-12CF	1.5/16"	3/4"
JMJICF90-21-16CF	1.5/16"	1"
JMJICF90-26-16CF	1.5/8"	1"

Fluid-Air Components Ltd

INTERLOCK HOSE CONNECTORS

Metric Heavy



Male

0309	Thread	To Suit Hose ID
JMDKOSM-26-12CF	25S-36 x 2	3/4"
JMDKOSM-42-16CF	30S-42 x 2	1"



Female

0309	Thread	To Suit Hose ID
JMDKOSF-36-12CF	25S-36 x 2	3/4"
JMDKOSF-42-16CF	30S-42 x 2	1"



45° Elbow

0309	Thread	To Suit Hose ID
JMDKOS45-36-12CF	25S-36 x 2	3/4"
JMDKOS45-42-16CF	30S-42 x 2	1"



90° Elbow

0309	Thread	To Suit Hose ID
JMDKOS90-26-12CF	25S-36 x 2	3/4"
JMDKOS90-42-16CF	30S-42 x 2	1"

ORFS



Female

0309	Thread	To Suit Hose ID
JMORFSF1212CF	1.3/16"	3/4"
JMORFSF1616CF	1.7/16"	1"



45° Elbow

0309	Thread	To Suit Hose ID
JMORFSF451212CF	1.3/16"	3/4"
JMORFSF451616CF	1.7/16"	1"



90° Elbow

0309	Thread	To Suit Hose ID
JMORFSF901212CF	1.3/16"	3/4"
JMORFSF901616CF	1.7/16"	1"

Poclain Style Flange



Male

0309	Flange ND	To Suit Hose ID
JMPOCM-12-12CF	3/4"	3/4"
JMPOCM-16-16CF	1"	1"



Female

0309	Flange ND	To Suit Hose ID
JMPOCF-12-12CF	3/4"	3/4"
JMPOCF-16-16CF	1"	1"

PORTWEST



For **PPE**
see pages **1750-1760**

Fluid-Air Components Ltd

INTERLOCK HOSE CONNECTORS

CAT Style Flange



Straight

0309	ND	To Suit Hose ID
JMCAT12-12CF	3/4"	3/4"
JMCAT16-12CF	1"	3/4"
JMCAT16-16CF	1"	1"
JMCAT20-16CF	1.1/4"	1"
Tech Sheet 10047		



45° Elbow

0309	ND	To Suit Hose ID
JMCAT4512-12CF	3/4"	3/4"
JMCAT4516-12CF	1"	3/4"
JMCAT4516-16CF	1"	1"
JMCAT4520-16CF	1.1/4"	1"
Tech Sheet 10047		



90° Elbow

0309	ND	To Suit Hose ID
JMCAT9012-12CF	3/4"	3/4"
JMCAT9016-12CF	1"	3/4"
JMCAT9016-16CF	1"	1"
JMCAT9020-16CF	1.1/4"	1"
Tech Sheet 10047		

SAE 3000 PSI Flange



Straight

0309	ND	To Suit Hose ID
JMFL3-12-12CF	3/4"	3/4"
JMFL3-16-12CF	1"	3/4"
JMFL3-16-16CF	1"	1"
JMFL3-20-16CF	1.1/4"	1"



45° Elbow

0309	ND	To Suit Hose ID
JMFL345-12-12CF	3/4"	3/4"
JMFL345-16-12CF	1"	3/4"
JMFL345-16-16CF	1"	1"
JMFL345-20-12CF	1.1/4"	1"



90° Elbow

0309	ND	To Suit Hose ID
JMFL390-12-12CF	3/4"	3/4"
JMFL390-16-12CF	1"	3/4"
JMFL390-16-16CF	1"	1"
JMFL390-20-16CF	1.1/4"	1"

SAE 6000 PSI Flange



Straight

0309	ND	To Suit Hose ID
JMFL6-12-12CF	3/4"	3/4"
JMFL6-16-12CF	1"	3/4"
JMFL6-16-16CF	1"	1"
JMFL6-20-16CF	1.1/4"	1"



45° Elbow

0309	ND	To Suit Hose ID
JMFL645-12-12CF	3/4"	3/4"
JMFL645-16-12CF	1"	3/4"
JMFL645-16-16CF	1"	1"
JMFL645-20-12CF	1.1/4"	1"



90° Elbow


0309	ND	To Suit Hose ID
JMFL690-12-12CF	3/4"	3/4"
JMFL690-16-12CF	1"	3/4"
JMFL690-16-16CF	1"	1"
JMFL690-20-16CF	1.1/4"	1"



For **Split flanges**
see page **24**

Fluid-Air Components Ltd

EDELSTAHL / STAINLESS STEEL
VERBINDUNGSTECHNIK
FLUID CONNECTORS



SINCE 1982 STAINLESS STEEL CONNECTORS FROM PH.

HYDRAULIC HOSE COUPLINGS AND COMPRESSION FITTINGS MADE FROM STAINLESS STEEL AISI 316 TI **ONLY.**

WHY PH?

HIGHEST PRECISION
WIDE RANGE OF PRODUCTS
STANDARDS AND NORMS
MAXIMUM AVAILABILITY
TRACEABILITY 100 %
TYPE APPROVALS

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC STAINLESS STEEL FERRULES

stainless steel

Ferrules

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



R1AT Non-skive

0044	To Suit Hose ID
SFR1-05	3/16"
SFR1-06	1/4"
SFR1-08	5/16"
SFR1-10	3/8"
SFR1-12	1/2"
SFR1-16	5/8"
SFR1-20	3/4"
SFR1-25	1"
SFR1-31	1.1/4"
SFR1-38	1.1/2"
SFR1-51	2"
Tech Sheet 60587	

EN857-1SC Non-skive

0044	To Suit Hose ID
SFR1-06SC	1/4"
SFR1-08SC	5/16"
SFR1-10SC	3/8"
SFR1-12SC	1/2"
Tech Sheet 60587	



R2AT Non-skive

0044	To Suit Hose ID
SFR2-05	3/16"
SFR2-06	1/4"
SFR2-08	5/16"
SFR2-10	3/8"
SFR2-12	1/2"
SFR2-16	5/8"
SFR2-20	3/4"
SFR2-25	1"
SFR2-31	1.1/4"
SFR2-38	1.1/2"
SFR2-51	2"
Tech Sheet 60588	

EN857-2SC Non-skive

0044	To Suit Hose ID
SFR2-06SC	1/4"
SFR2-08SC	5/16"
SFR2-10SC	3/8"
SFR2-12SC	1/2"
SFR2-16SC	5/8"
SFR2-20SC	3/4"
SFR2-25SC	1"
Tech Sheet 60587	



R1AT & R2AT Dual, Non-skive

0044	To Suit Hose ID
SFR3-06	1/4"
SFR3-08	5/16"
SFR3-10	3/8"
SFR3-12	1/2"
SFR3-16	5/8"
SFR3-20	3/4"
SFR3-25	1"
Tech Sheet 60587	



PTFE, Smooth Bore

0044	To Suit Hose ID
SFPTFE-05	3/16"
SFPTFE-06	1/4"
SFPTFE-08	5/16"
SFPTFE-10	3/8"
SFPTFE-12	1/2"
SFPTFE-16	5/8"
SFPTFE-20	3/4"
SFPTFE-25	1"
Tech Sheet 60586	



PTFE, Convoluted Bore

0044	To Suit Hose ID
SCFPTFE-06	1/4"
SCFPTFE-08	5/16"
SCFPTFE-10	3/8"
SCFPTFE-12	1/2"
SCFPTFE-16	5/8"
SCFPTFE-20	3/4"
SCFPTFE-25	1"
Tech Sheet 60585	

For **Full range of Hydraulic Hose** see pages **6-14**



Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

BSP

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Male Inserts, BSPP



0044	Thread	To Suit Hose ID
SMI05-14	1/4"	3/16"
SMI06-18	1/8"	1/4"
SMI06-14	1/4"	1/4"
SMI06-38	3/8"	1/4"
SMI06-12	1/2"	1/4"
SMI08-14	1/4"	5/16"
SMI08-38	3/8"	5/16"
SMI08-12	1/2"	5/16"
SMI10-14	1/4"	3/8"
SMI10-38	3/8"	3/8"
SMI10-12	1/2"	3/8"
SMI12-38	3/8"	1/2"
SMI12-12	1/2"	1/2"
SMI12-34	3/4"	1/2"
SMI16-12	1/2"	5/8"
SMI16-58	5/8"	5/8"
SMI16-34	3/4"	5/8"
SMI20-34	3/4"	3/4"
SMI20-1	1"	3/4"
SMI25-1	1"	1"
SMI25-34	3/4"	1"
SMI25-114	1.1/4"	1"
SMI31-114	1.1/4"	1.1/4"
SMI31-112	1.1/2"	1.1/4"
SMI38-112	1.1/2"	1.1/2"
SMI51-2	2"	2"

Tech Sheet 60593

Male Inserts, BSPT



0044	Thread	To Suit Hose ID
AGRK-1/8-DN05	1/8"	3/16"
AGRK-1/8-DN06	1/8"	1/4"
AGRK-1/4-DN05	1/4"	3/16"
AGRK-1/4-DN06	1/4"	1/4"
AGRK-1/4-DN10	1/4"	3/8"
AGRK-1/4-DN08	1/4"	5/16"
AGRK-3/8-DN06	3/8"	1/4"
AGRK-3/8-DN08	3/8"	5/16"
AGRK-3/8-DN10	3/8"	3/8"
AGRK-3/8-DN12	3/8"	1/2"
AGRK-1/2-DN10	1/2"	3/8"
AGRK-1/2-DN12	1/2"	1/2"
AGRK-1/2-DN19	1/2"	3/4"
AGRK-3/4-DN12	3/4"	1/2"
AGRK-3/4-DN16	3/4"	5/8"
AGRK-3/4-DN19	3/4"	3/4"
AGRK-3/4-DN25	3/4"	1"
AGRK-1-DN19	1"	3/4"
AGRK-1-DN25	1"	1"
AGRK-11/4-DN31	1.1/4"	1.1/4"
AGRK-11/2-DN38	1.1/2"	1.1/2"
AGRK-2-DN51	2"	2"

Tech Sheet 60589

Swivel Female Inserts, BSPP



0044	Thread	To Suit Hose ID
SFI05-18	1/8"	3/16"
SFI05-14	1/4"	3/16"
SFI06-18	1/8"	1/4"
SFI06-14	1/4"	1/4"
SFI06-38	3/8"	1/4"
SFI06-12	1/2"	1/4"
SFI08-14	1/4"	5/16"
SFI08-38	3/8"	5/16"
SFI08-12	1/2"	5/16"
SFI10-14	1/4"	3/8"
SFI10-38	3/8"	3/8"
SFI10-12	1/2"	3/8"
SFI12-38	3/8"	1/2"
SFI12-12	1/2"	1/2"
SFI12-58	5/8"	1/2"
SFI16-12	1/2"	5/8"
SFI16-58	5/8"	5/8"
SFI16-34	3/4"	5/8"
SFI20-12	1/2"	3/4"
SFI20-34	3/4"	3/4"
SFI20-1	1"	3/4"
SFI20-114	1.1/4"	3/4"
SFI25-1	1"	1"
SFI25-34	3/4"	1"
SFI25-114	1.1/4"	1"
SFI31-1	1"	1.1/4"
SFI31-114	1.1/4"	1.1/4"
SFI31-112	1.1/2"	1.1/4"
SFI38-112	1.1/2"	1.1/2"
SFI38-2	2"	1.1/2"
SFI51-2	2"	2"

Tech Sheet 60592

Female Swept 90° Inserts, BSPP



0044	Thread	To Suit Hose ID
SEI05-14	1/4"	3/16"
SEI05-18	1/8"	3/16"
SEI06-18	1/8"	1/4"
SEI06-14	1/4"	1/4"
SEI06-38	3/8"	1/4"
SEI08-14	1/4"	5/16"
SEI08-38	3/8"	5/16"
SEI10-14	1/4"	3/8"
SEI10-38	3/8"	3/8"
SEI10-12	1/2"	3/8"
SEI12-38	3/8"	1/2"
SEI12-12	1/2"	1/2"
SEI12-58	5/8"	1/2"
SEI16-12	1/2"	5/8"
SEI16-58	5/8"	5/8"
SEI16-34	3/4"	5/8"
SEI20-34	3/4"	3/4"
SEI20-1	1"	3/4"
SEI25-1	1"	1"
SEI25-114	1.1/4"	1"
SEI31-114	1.1/4"	1.1/4"
SEI31-112	1.1/2"	1.1/4"
SEI38-112	1.1/2"	1.1/2"
SEI38-2	2"	1.1/2"
SEI51-2	2"	2"

Tech Sheet 60591

Female Swept 45° Inserts, BSPP



0044	Thread	To Suit Hose ID
DKR-1/8-45-DN05	1/8"	3/16"
DKR-1/8-45-DN06	1/8"	1/4"
DKR-1/4-45-DN05	1/4"	3/16"
DKR-1/4-45-DN06	1/4"	1/4"
DKR-1/4-45-DN08	1/4"	5/16"
DKR-1/4-45-DN10	1/4"	3/8"
DKR-3/8-45-DN06	3/8"	1/4"
DKR-3/8-45-DN08	3/8"	5/16"
DKR-3/8-45-DN10	3/8"	3/8"
DKR-3/8-45-DN12	3/8"	1/2"
DKR-1/2-45-DN10	1/2"	3/8"
DKR-1/2-45-DN12	1/2"	1/2"
DKR-1/2-45-DN16	1/2"	5/8"
DKR-5/8-45-DN12	5/8"	1/2"
DKR-5/8-45-DN16	5/8"	5/8"
DKR-3/4-45-DN12	3/4"	1/2"
DKR-3/4-45-DN16	3/4"	5/8"
DKR-3/4-45-DN19	3/4"	3/4"
DKR-1-45-DN19	1"	3/4"
DKR-1-45-DN25	1"	1"
DKR-11/4-45-DN25	1.1/4"	1"
DKR-11/4-45-DN31	1.1/4"	1.1/4"
DKR-11/2-45-DN31	1.1/2"	1.1/4"
DKR-11/2-45-DN38	1.1/2"	1.1/2"
DKR-2-45-DN38	2"	1.1/2"
DKR-2-45-DN51	2"	2"

Tech Sheet 60590

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

JIC 37°

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Male Inserts

0044	Thread	To Suit Hose ID
AGJ-7/16-DN05	7/16"	3/16"
AGJ-7/16-DN06	7/16"	1/4"
AGJ-1/2-DN05	1/2"	3/16"
AGJ-1/2-DN06	1/2"	1/4"
AGJ-1/2-DN08	1/2"	5/16"
AGJ-9/16-DN05	9/16"	3/16"
AGJ-9/16-DN06	9/16"	1/4"
AGJ-9/16-DN08	9/16"	5/16"
AGJ-9/16-DN10	9/16"	3/8"
AGJ-3/4-DN10	3/4"	3/8"
AGJ-3/4-DN12	3/4"	1/2"
AGJ-7/8-DN10	7/8"	3/8"
AGJ-7/8-DN12	7/8"	1/2"
AGJ-7/8-DN16	7/8"	5/8"
AGJ-11/16-DN12	1.1/16"	1/2"
AGJ-11/16-DN16	1.1/16"	5/8"
AGJ-11/16-DN19	1.1/16"	3/4"
AGJ-15/16-DN19	1.5/16"	3/4"
AGJ-15/16-DN25	1.5/16"	1"
AGJ-15/8-DN25	1.5/8"	1"
AGJ-15/8-DN31	1.5/8"	1.1/4"
AGJ-17/8-DN31	1.7/8"	1.1/4"
AGJ-17/8-DN38	1.7/8"	1.1/2"
AGJ-21/2-DN38	2.1/2"	1.1/2"
AGJ-21/2-DN51	2.1/2"	2"

Tech Sheet 60594



Female Swivel Inserts

0044	Thread	To Suit Hose ID
DKJ7/16-DN05	7/16"	3/16"
DKJ7/16-DN06	7/16"	1/4"
DKJ1/2-DN05	1/2"	3/16"
DKJ1/2-DN06	1/2"	1/4"
DKJ1/2-DN08	1/2"	5/16"
DKJ9/16-DN05	9/16"	3/16"
DKJ9/16-DN06	9/16"	1/4"
DKJ9/16-DN08	9/16"	5/16"
DKJ9/16-DN10	9/16"	3/8"
DKJ9/16-DN12	9/16"	1/2"
DKJ3/4-DN06	3/4"	1/4"
DKJ3/4-DN08	3/4"	5/16"
DKJ3/4-DN10	3/4"	3/8"
DKJ3/4-DN12	3/4"	1/2"
DKJ3/4-DN16	3/4"	5/8"
DKJ3/4-DN19	3/4"	3/4"
DKJ7/8-DN10	7/8"	3/8"
DKJ7/8-DN12	7/8"	1/2"
DKJ7/8-DN16	7/8"	5/8"
DKJ7/8-DN19	7/8"	3/4"
DKJ11/16-DN12	1.1/16"	1/2"
DKJ11/16-DN16	1.1/16"	5/8"
DKJ11/16-DN19	1.1/16"	3/4"
DKJ11/16-DN25	1.1/16"	1"
DKJ15/16-DN16	1.5/16"	5/8"
DKJ15/16-DN25	1.5/16"	1"
DKJ15/8-DN25	1.5/8"	1"
DKJ15/8-DN31	1.5/8"	1.1/4"
DKJ17/8-DN31	1.7/8"	1.1/4"
DKJ17/8-DN38	1.7/8"	1.1/2"
DKJ21/2-DN38	2.1/2"	1.1/2"
DKJ21/2-DN51	2.1/2"	2"


Tech Sheet 60597



Female Swept 90° Inserts

0044	Thread	To Suit Hose ID
DKJ7/16-90-DN05	7/16"	3/16"
DKJ7/16-90-DN06	7/16"	1/4"
DKJ1/2-90-DN05	1/2"	3/16"
DKJ1/2-90-DN06	1/2"	1/4"
DKJ1/2-90-DN08	1/2"	5/16"
DKJ9/16-90-DN05	9/16"	3/16"
DKJ9/16-90-DN06	9/16"	1/4"
DKJ9/16-90-DN08	9/16"	5/16"
DKJ9/16-90-DN10	9/16"	3/8"
DKJ3/4-90-DN10	3/4"	3/8"
DKJ3/4-90-DN12	3/4"	1/2"
DKJ7/8-90-DN10	7/8"	3/8"
DKJ7/8-90-DN12	7/8"	1/2"
DKJ7/8-90-DN16	7/8"	5/8"
DKJ11/16-90-DN12	1.1/16"	1/2"
DKJ11/16-90-DN16	1.1/16"	5/8"
DKJ11/16-90-DN19	1.1/16"	3/4"
DKJ15/16-90-DN19	1.5/16"	3/4"
DKJ15/16-90-DN25	1.5/16"	1"
DKJ1.5/8-90-DN25	1.5/8"	1"
DKJ15/8-90-DN31	1.5/8"	1.1/4"
DKJ17/8-90-DN31	1.7/8"	1.1/4"
DKJ17/8-90-DN38	1.7/8"	1.1/2"
DKJ21/2-90-DN38	2.1/2"	1.1/2"
DKJ21/2-90-DN51	2.1/2"	2"

Tech Sheet 60596



Female Swept 45° Inserts

0044	Thread	To Suit Hose ID
DKJ-7/16-45-DN06	7/16"	1/4"
DKJ-1/2-45-DN06	1/2"	1/4"
DKJ-1/2-45-DN08	1/2"	5/16"
DKJ-9/16-45-DN06	9/16"	1/4"
DKJ-9/16-45-DN08	9/16"	5/16"
DKJ-9/16-45-DN10	9/16"	3/8"
DKJ-3/4-45-DN10	3/4"	3/8"
DKJ-3/4-45-DN12	3/4"	1/2"
DKJ-7/8-45-DN10	7/8"	3/8"
DKJ-7/8-45-DN12	7/8"	1/2"
DKJ-7/8-45-DN16	7/8"	5/8"
DKJ-1116-45-DN12	1.1/16	1/2"
DKJ-1116-45-DN16	1.1/16	5/8"
DKJ-1116-45-DN19	1.1/16	3/4"
DKJ-1516-45-DN19	1.5/16"	3/4"
DKJ-1516-45-DN25	1.5/16"	1"
DKJ-15/8-45-DN25	1.5/8"	1"
DKJ-15/8-45-DN31	1.5/8"	1.1/4"
DKJ-17/8-45-DN31	1.7/8"	1.1/4"
DKJ-17/8-45-DN38	1.7/8"	1.1/2"
DKJ-21/2-45-DN38	2.1/2"	1.1/2"
DKJ-21/2-45-DN51	2.1/2"	2"

Tech Sheet 60595

FT PRO



For **Hose & Pipe Cleaning** see page **49**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

Metric Light Series

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Metric Male 24° Cone Seat, L Series DIN 2353

0044	Thread	To Suit Hose ID
CEL-06-DN05	M12 x 1.5	3/16"
CEL-06-DN06	M12 x 1.5	1/4"
CEL-08-DN05	M14 x 1.5	3/16"
CEL-08-DN06	M14 x 1.5	1/4"
CEL-10-DN06	M16 x 1.5	1/4"
CEL-10-DN08	M16 x 1.5	5/16"
CEL-10-DN10	M16 x 1.5	3/8"
CEL-12-DN06	M18 x 1.5	1/4"
CEL-12-DN08	M18 x 1.5	5/16"
CEL-12-DN10	M18 x 1.5	3/8"
CEL-12-DN12	M18 x 1.5	1/2"
CEL-15-DN10	M22 x 1.5	3/8"
CEL-15-DN12	M22 x 1.5	1/2"
CEL-18-DN12	M26 x 1.5	1/2"
CEL-18-DN16	M26 x 1.5	5/8"
CEL-18-DN19	M26 x 1.5	3/4"
CEL-22-DN16	M30 x 2	5/8"
CEL-22-DN19	M30 x 2	3/4"
CEL-28-DN19	M36 x 2	3/4"
CEL-28-DN25	M36 x 2	1"
CEL-35-DN31	M45 x 2	1.1/4"
CEL-42-DN38	M52 x 2	1.1/2"

Tech Sheet 60598



Metric Female 24° Cone Seat, L Series with O-Ring, DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-DN05	M12 x 1.5	3/16"
DKOL-06-DN06	M12 x 1.5	1/4"
DKOL-08-DN05	M14 x 1.5	3/16"
DKOL-08-DN06	M14 x 1.5	1/4"
DKOL-08-DN08	M14 x 1.5	5/16"
DKOL-08-DN10	M14 x 1.5	3/8"
DKOL-10-DN06	M16 x 1.5	1/4"
DKOL-10-DN08	M16 x 1.5	5/16"
DKOL-10-DN10	M16 x 1.5	3/8"
DKOL-12-DN06	M18 x 1.5	1/4"
DKOL-12-DN08	M18 x 1.5	5/16"
DKOL-12-DN10	M18 x 1.5	3/8"
DKOL-12-DN12	M18 x 1.5	1/2"
DKOL-15-DN06	M22 x 1.5	1/4"
DKOL-15-DN08	M22 x 1.5	5/16"
DKOL-15-DN10	M22 x 1.5	3/8"
DKOL-15-DN12	M22 x 1.5	1/2"
DKOL-15-DN16	M22 x 1.5	5/8"
DKOL-18-DN10	M26 x 1.5	3/8"
DKOL-18-DN12	M26 x 1.5	1/2"
DKOL-18-DN16	M26 x 1.5	5/8"
DKOL-18-DN19	M26 x 1.5	3/4"
DKOL-22-DN12	M30 x 2	1/2"
DKOL-22-DN16	M30 x 2	5/8"
DKOL-22-DN19	M30 x 2	3/4"
DKOL-22-DN25	M30 x 2	1"
DKOL-28-DN16	M36 x 2	5/8"
DKOL-28-DN19	M36 x 2	3/4"
DKOL-28-DN25	M36 x 2	1"
DKOL-35-DN25	M45 x 2	1"
DKOL-35-DN31	M45 x 2	1.1/4"
DKOL-42-DN31	M52 x 2	1.1/4"
DKOL-42-DN38	M52 x 2	1.1/2"

Tech Sheet 60601



90° Metric Female 24° Cone Seat, L Series with O-Ring DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-90-DN05	M12 X 1.5	3/16"
DKOL-06-90-DN06	M12 x 1.5	1/4"
DKOL-08-90-DN06	M14 x 1.5	1/4"
DKOL-08-90-DN08	M14 x 1.5	5/16"
DKOL-10-90-DN06	M16 x 1.5	1/4"
DKOL-10-90-DN08	M16 x 1.5	5/16"
DKOL-10-90-DN10	M16 x 1.5	3/8"
DKOL-12-90-DN06	M18 x 1.5	1/4"
DKOL-12-90-DN08	M18 x 1.5	5/16"
DKOL-12-90-DN10	M18 x 1.5	3/8"
DKOL-12-90-DN12	M18 x 1.5	1/2"
DKOL-15-90-DN10	M22 x 1.5	3/8"
DKOL-15-90-DN12	M22 x 1.5	1/2"
DKOL-18-90-DN12	M26 x 1.5	1/2"
DKOL-18-90-DN16	M26 x 1.5	5/8"
DKOL-22-90-DN16	M30 x 2	5/8"
DKOL-22-90-DN19	M30 x 2	3/4"
DKOL-28-90-DN19	M36 x 2	3/4"
DKOL-28-90-DN25	M36 x 2	1"
DKOL-35-90-DN31	M45 x 2	1.1/4"
DKOL-42-90-DN38	M52 x 2	1.1/2"

Tech Sheet 60600



45° Metric Female 24° Cone Seat, L Series with O-Ring DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-45-DN05	M12 x 1.5	3/16"
DKOL-06-45-DN06	M12 x 1.5	1/4"
DKOL-08-45-DN05	M14 x 1.5	3/16"
DKOL-08-45-DN06	M14 x 1.5	1/4"
DKOL-08-45-DN08	M14 x 1.5	5/16"
DKOL-10-45-DN06	M16 x 1.5	1/4"
DKOL-10-45-DN08	M16 x 1.5	5/16"
DKOL-10-45-DN10	M16 x 1.5	3/8"
DKOL-12-45-DN06	M18 x 1.5	1/4"
DKOL-12-45-DN08	M18 x 1.5	5/16"
DKOL-12-45-DN10	M18 x 1.5	3/8"
DKOL-12-45-DN12	M18 x 1.5	1/2"
DKOL-15-45-DN10	M22 x 1.5	3/8"
DKOL-15-45-DN12	M22 x 1.5	1/2"
DKOL-18-45-DN12	M26 x 1.5	1/2"
DKOL-18-45-DN16	M26 x 1.5	5/8"
DKOL-22-45-DN16	M30 x 2	5/8"
DKOL-22-45-DN19	M30 x 2	3/4"
DKOL-28-45-DN19	M36 x 2	3/4"
DKOL-28-45-DN25	M36 x 2	1"
DKOL-35-45-DN31	M45 x 2	1.1/4"
DKOL-42-45-DN38	M52 x 2	1.1/2"

Tech Sheet 60599

FT PRO



For **Polypropylene Protective Hose Sleeves** see pages **47-48**

FAC Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

Metric Heavy Series

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Metric Male 24° Cone Seat, S Series DIN 2353

0044	Thread	To Suit Hose ID
CES-06-DN06	M14 x 1.5	1/4"
CES-08-DN06	M16 x 1.5	1/4"
CES-10-DN06	M18 x 1.5	1/4"
CES-10-DN08	M18 x 1.5	5/16"
CES-10-DN10	M18 x 1.5	3/8"
CES-12-DN08	M20 x 1.5	5/16"
CES-12-DN10	M20 x 1.5	3/8"
CES-14-DN08	M22 x 1.5	5/16"
CES-14-DN10	M22 x 1.5	3/8"
CES-16-DN10	M24 x 1.5	3/8"
CES-16-DN12	M24 x 1.5	1/2"
CES-20-DN12	M30 x 2	1/2"
CES-20-DN16	M30 x 2	5/8"
CES-20-DN19	M30 x 2	3/4"
CES-25-DN19	M36 x 2	3/4"
CES-25-DN25	M36 x 2	1"
CES-38-DN31	M52 x 2	1.1/4"
CES-30-DN25	M42 x 2	1"
Tech Sheet 60602		



Metric Female 24° Cone Seat, S Series, DIN 2353

0044	Thread	To Suit Hose ID
DKOS-06-DN05	M14 x 1.5	3/16"
DKOS-06-DN06	M14 x 1.5	1/4"
DKOS-08-DN05	M16 x 1.5	3/16"
DKOS-08-DN06	M16 x 1.5	1/4"
DKOS-08-DN08	M16 x 1.5	5/16"
DKOS-08-DN10	M16 x 1.5	3/8"
DKOS-10-DN06	M18 x 1.5	1/4"
DKOS-10-DN08	M18 x 1.5	5/16"
DKOS-10-DN10	M18 x 1.5	3/8"
DKOS-12-DN06	M20 x 1.5	1/4"
DKOS-12-DN08	M20 x 1.5	5/16"
DKOS-12-DN10	M20 x 1.5	3/8"
DKOS-12-DN12	M20 x 1.5	1/2"
DKOS-14-DN08	M22 x 1.5	5/16"
DKOS-14-DN10	M22 x 1.5	3/8"
DKOS-16-DN06	M24 x 1.5	1/4"
DKOS-16-DN08	M24 x 1.5	5/16"
DKOS-16-DN10	M24 x 1.5	3/8"
DKOS-16-DN12	M24 x 1.5	1/2"
DKOS-16-DN16	M24 x 1.5	5/8"
DKOS-20-DN10	M30 x 2	3/8"
DKOS-20-DN12	M30 x 2	1/2"
DKOS-20-DN16	M30 x 2	5/8"
DKOS-20-DN19	M30 x 2	3/4"
DKOS-25-DN12	M36 x 2	1/2"
DKOS-25-DN16	M36 x 2	5/8"
DKOS-25-DN19	M36 x 2	3/4"
DKOS-25-DN25	M36 x 2	1"
DKOS-30-DN19	M42 x 2	3/4"
DKOS-30-DN25	M42 x 2	1"
DKOS-38-DN25	M52 x 2	1"
DKOS-38-DN31	M52 x 2	1.1/4"
DKOS-50-DN38	M68 x 2	1.1/2"
Tech Sheet 60605		



90° Metric Female 24° Cone Seat, S Series with O-Ring, DIN 2353


0044	Thread	To Suit Hose ID
DKOS-06-90-DN06	M14 x 1.5	1/4"
DKOS-08-90-DN06	M16 x 1.5	1/4"
DKOS-08-90-DN08	M16 x 1.5	5/16"
DKOS-10-90-DN06	M18 x 1.5	1/4"
DKOS-10-90-DN08	M18 x 1.5	5/16"
DKOS-10-90-DN10	M18 x 1.5	3/8"
DKOS-12-90-DN06	M20 x 1.5	1/4"
DKOS-12-90-DN08	M20 x 1.5	5/16"
DKOS-12-90-DN10	M20 x 1.5	3/8"
DKOS-12-90-DN12	M20 x 1.5	1/2"
DKOS-14-90-DN10	M22 x 1.5	3/8"
DKOS-16-90-DN10	M24 x 1.5	3/8"
DKOS-16-90-DN12	M24 x 1.5	1/2"
DKOS-20-90-DN12	M30 x 2	1/2"
DKOS-20-90-DN16	M30 x 2	5/8"
DKOS-20-90-DN19	M30 x 2	3/4"
DKOS-25-90-DN19	M36 x 2	3/4"
DKOS-25-90-DN25	M36 x 2	1"
DKOS-30-90-DN19	M42 x 2	3/4"
DKOS-30-90-DN25	M42 x 2	1"
DKOS-38-90-DN25	M52 x 2	1"
DKOS-38-90-DN31	M52 x 2	1.1/4"
Tech Sheet 60604		



45° Metric Female 24° Cone Seat, S Series with O-Ring, DIN 2353

0044	Thread	To Suit Hose ID
DKOS-06-45-DN06	M14 x 1.5	1/4"
DKOS-08-45-DN06	M16 x 1.5	1/4"
DKOS-08-45-DN08	M16 x 1.5	5/16"
DKOS-10-45-DN06	M18 x 1.5	1/4"
DKOS-10-45-DN08	M18 x 1.5	5/16"
DKOS-10-45-DN10	M18 x 1.5	3/8"
DKOS-12-45-DN06	M20 x 1.5	1/4"
DKOS-12-45-DN08	M20 x 1.5	5/16"
DKOS-12-45-DN10	M20 x 1.5	3/8"
DKOS-12-45-DN12	M20 x 1.5	1/2"
DKOS-14-45-DN10	M22 x 1.5	3/8"
DKOS-16-45-DN10	M24 x 1.5	3/8"
DKOS-16-45-DN12	M24 x 1.5	1/2"
DKOS-20-45-DN12	M30 x 2	1/2"
DKOS-20-45-DN16	M30 x 2	5/8"
DKOS-20-45-DN19	M30 x 2	3/4"
DKOS-25-45-DN19	M36 x 2	3/4"
DKOS-25-45-DN25	M36 x 2	1"
DKOS-30-45-DN19	M42 x 2	3/4"
DKOS-30-45-DN25	M42 x 2	1"
DKOS-38-45-DN25	M52 x 2	1"
DKOS-38-45-DN31	M52 x 2	1.1/4"
Tech Sheet 60603		

STOPflex FOR PRESSURE HOSES



For **Hose Retention System** see pages **42-43**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel


Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

ORFS



Male (O-Ring Face) Inserts

0044	Thread	To Suit Hose ID
ORFSM0404SS	9/16"	1/4"
ORFSM0606SS	11/16"	3/8"
ORFSM0808SS	13/16"	1/2"
ORFSM1010SS	1"	5/8"
ORFSM1212SS	1.3/16"	3/4"
ORFSM1616SS	1.7/16"	1"
ORFSM2020SS	1.11/16"	1.1/4"
ORFSM2424SS	2"	1.1/2"
Tech Sheet 60610		



Female Inserts


0044	Thread	To Suit Hose ID
ORFSF0404SS	9/16"	1/4"
ORFSF0604SS	11/16"	1/4"
ORFSF0605SS	11/16"	5/16"
ORFSF0606SS	11/16"	3/8"
ORFSF0806SS	13/16"	3/8"
ORFSF0808SS	13/16"	1/2"
ORFSF1008SS	1"	1/2"
ORFSF1010SS	1"	5/8"
ORFSF1012SS	1"	3/4"
ORFSF1208SS	1.3/16"	1/2"
ORFSF1210SS	1.3/16"	5/8"
ORFSF1212SS	1.7/16"	3/4"
ORFSF1612SS	1.7/16"	3/4"
ORFSF1616SS	1.7/16"	1"
ORFSF2020SS	1.11/16"	1.1/4"
ORFSF2424SS	2"	1.1/2"
Tech Sheet 60607		

Jet Wash Female



M22 x 1.5

0044	To Suit Hose ID
DKO-KA-DN06	1/4"
DKO-KA-DN08	5/16"
DKO-KA-DN10	3/8"
DKO-KA-DN12	1/2"
Tech Sheet 60627	



Female Swept 90° Elbow Inserts

0044	Thread	To Suit Hose ID
ORFSF049004SS	9/16"	1/4"
ORFSF069004SS	11/16"	1/4"
ORFSF069005SS	11/16"	5/16"
ORFSF069006SS	11/16"	3/8"
ORFSF089006SS	13/16"	3/8"
ORFSF089008SS	13/16"	1/2"
ORFSF109010SS	1"	5/8"
ORFSF109012SS	1"	3/4"
ORFSF129012SS	1.7/16"	3/4"
ORFSF169012SS	1.7/16"	3/4"
ORFSF169016SS	1.7/16"	1"
ORFSF209020SS	1.11/16"	1.1/4"
ORFSF209024SS	2"	1.1/2"
Tech Sheet 60609		



Female Swept 45° Elbow Inserts

0044	Thread	To Suit Hose ID
ORFSF044504SS	9/16"	1/4"
ORFSF064504SS	11/16"	1/4"
ORFSF064505SS	11/16"	5/16"
ORFSF064506SS	11/16"	3/8"
ORFSF084506SS	13/16"	3/8"
ORFSF084508SS	13/16"	1/2"
ORFSF104510SS	1"	5/8"
ORFSF104512SS	1"	3/4"
ORFSF124512SS	1.7/16"	3/4"
ORFSF164516SS	1.7/16"	1"
ORFSF204520SS	1.11/16"	1.1/4"
ORFSF204524SS	2"	1.1/2"
Tech Sheet 60608		

Banjos



Bolt, Metric

0044	Thread
HS-M10X1	M10 x 1
HS-M12X1.5	M12 x 1.5
HS-M14X1.5	M14 x 1.5
HS-M16X1.5	M16 x 1.5
HS-M18X1.5	M18 x 1.5
HS-M22X1.5	M22 x 1.5
HS-M26X1.5	M26 x 1.5
Tech Sheet 60606	

Bolt, Imperial

0044	Thread
HS-G1/8	1/8"
HS-G1/4	1/4"
HS-G3/8	3/8"
HS-G1/2	1/2"
HS-G3/4	3/4"
Tech Sheet 60606	



Inserts, Metric/Imperial

0044	Thread	Thread	To Suit Hose ID
RGN-10-DN06	M10 x 1	1/8"	1/4"
RGN-10-DN08	M10 x 1	1/8"	5/16"
RGN-12-DN06	M12 x 1.5	-	1/4"
RGN-12-DN08	M12 x 1.5	-	5/16"
RGN-14-DN06	M14 x 1.5	-	1/4"
RGN-1/4-DN06	-	1/4"	1/4"
RGN-14-DN08	M14 x 1.5	-	5/16"
RGN-14-DN10	M14 x 1.5	-	3/8"
RGN-16-DN08	M16 x 1.5	3/8"	5/16"
RGN-16-DN10	M16 x 1.5	3/8"	3/8"
RGN-16-DN12	M16 x 1.5	3/8"	1/2"
RGN-18-DN10	M18 x 1.5	-	3/8"
RGN-1/2-DN10	-	1/2"	3/8"
RGN-1/2-DN12	-	1/2"	1/2"
RGN-18-DN12	M18 x 1.5	-	1/2"
RGN-22-DN12	M22 x 1.5	-	1/2"
RGN-22-DN16	M22 x 1.5	-	5/8"
RGN-26-DN19	M26 x 1.5	3/4"	3/4"
Tech Sheet 60611			

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Standpipes



Straight, L Series

0044	OD mm	To Suit Hose ID
BEL-06-DN05	6	3/16"
BEL-06-DN06	6	1/4"
BEL-08-DN05	8	3/16"
BEL-08-DN06	8	1/4"
BEL-08-DN08	8	5/16"
BEL-10-DN08	10	5/16"
BEL-10-DN10	10	3/8"
BEL-12-DN10	12	3/8"
BEL-12-DN12	12	1/2"
BEL-15-DN10	15	3/8"
BEL-15-DN12	15	1/2"
BEL-18-DN12	18	1/2"
BEL-18-DN16	18	5/8"
BEL-22-DN16	22	5/8"
BEL-22-DN19	22	3/4"
BEL-28-DN25	28	1"
BEL-35-DN31	35	1.1/4"
BEL-42-DN38	42	1.1/2"
Tech Sheet 60615		

Straight, S Series

0044	OD mm	To Suit Hose ID
BES-06-DN05	6	3/16"
BES-06-DN06	6	1/4"
BES-08-DN06	8	1/4"
BES-08-DN08	8	5/16"
BES-10-DN06	10	1/4"
BES-10-DN08	10	5/16"
BES-10-DN10	10	3/8"
BES-12-DN06	12	1/4"
BES-12-DN08	12	5/16"
BES-12-DN10	12	3/8"
BES-12-DN12	12	1/2"
BES-14-DN10	14	3/8"
BES-16-DN12	16	1/2"
BES-20-DN12	20	1/2"
BES-20-DN16	20	5/8"
BES-20-DN19	20	3/4"
BES-25-DN19	25	3/4"
BES-25-DN25	25	1"
BES-30-DN25	30	1"
BES-38-DN31	38	1.1/4"
Tech Sheet 60616		

Straight, Imperial

0044	OD	To Suit Hose ID
BE-14-DN06	1/4"	1/4"
BE-516-DN08	5/16"	5/16"
BE-38-DN10	3/8"	3/8"
BE-12-DN12	1/2"	1/2"
BE-58-DN16	5/8"	5/8"
BE-34-DN19	3/4"	3/4"
BE-1-DN25	1"	1"
BE-114-DN31	1.1/4"	1.1/4"
BE-112-DN38	1.1/2"	1.1/2"
Tech Sheet 60612		



Swept 90°, L Series

0044	OD mm	To Suit Hose ID
BEL-06-90-DN05	6	3/16"
BEL-06-90-DN06	6	1/4"
BEL-08-90-DN06	8	1/4"
BEL-10-90-DN06	10	1/4"
BEL-10-90-DN08	10	5/16"
BEL-10-90-DN10	10	3/8"
BEL-12-90-DN08	12	5/16"
BEL-12-90-DN10	12	3/8"
BEL-12-90-DN12	12	1/2"
BEL-15-90-DN12	15	1/2"
BEL-18-90-DN16	18	5/8"
BEL-22-90-DN19	22	3/4"
BEL-28-90-DN25	28	1"
BEL-35-90-DN31	35	1.1/4"
BEL-42-90-DN38	42	1.1/2"
Tech Sheet 60614		

Swept 90°, S Series

0044	OD mm	To Suit Hose ID
BES-06-90-DN05	6	3/16"
BES-06-90-DN06	6	1/4"
BES-08-90-DN06	8	1/4"
BES-10-90-DN06	10	1/4"
BES-10-90-DN08	10	5/16"
BES-10-90-DN10	10	3/8"
BES-12-90-DN08	12	5/16"
BES-12-90-DN10	12	3/8"
BES-14-90-DN10	14	3/8"
BES-16-90-DN12	16	1/2"
BES-20-90-DN16	20	5/8"
BES-25-90-DN19	25	3/4"
BES-30-90-DN25	30	1"
BES-38-90-DN31	38	1.1/4"
Tech Sheet 60614		



Swept 45°, L Series

0044	OD mm	To Suit Hose ID
BEL-06-45-DN05	6	3/16"
BEL-06-45-DN06	6	1/4"
BEL-08-45-DN06	8	1/4"
BEL-10-45-DN06	10	1/4"
BEL-10-45-DN08	10	5/16"
BEL-10-45-DN10	10	3/8"
BEL-12-45-DN08	12	5/16"
BEL-12-45-DN10	12	3/8"
BEL-15-45-DN12	15	1/2"
BEL-18-45-DN16	18	5/8"
BEL-22-45-DN19	22	3/4"
BEL-28-45-DN25	28	1"
BEL-35-45-DN31	35	1.1/4"
BEL-42-45-DN38	42	1.1/2"
Tech Sheet 60613		

Swept 45°, S Series

0044	OD mm	To Suit Hose ID
BES-06-45-DN05	6	3/16"
BES-06-45-DN06	6	1/4"
BES-08-45-DN06	8	1/4"
BES-10-45-DN06	10	1/4"
BES-10-45-DN08	10	5/16"
BES-10-45-DN10	10	3/8"
BES-12-45-DN08	12	5/16"
BES-14-45-DN10	14	3/8"
BES-16-45-DN12	16	1/2"
BES-20-45-DN16	20	5/8"
BES-25-45-DN19	25	3/4"
BES-30-45-DN25	30	1"
BES-38-45-DN31	38	1.1/4"
Tech Sheet 60613		

FT PRO



For **Hose & Assemblies** see page **15**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS & HOSE FITTINGS

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)

SAE 3000 psi (3k)



Straight Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-DN12	1/2"	1/2"
SFL3-1/2-DN16	1/2"	5/8"
SFL3-3/4-DN12	3/4"	1/2"
SFL3-3/4-DN16	3/4"	5/8"
SFL3-3/4-DN19	3/4"	3/4"
SFL3-1-DN19	1"	3/4"
SFL3-1-DN25	1"	1"
SFL3-11/4-DN25	1.1/4"	1"
SFL3-11/4-DN31	1.1/4"	1.1/4"
SFL3-11/2-DN31	1.1/2"	1.1/4"
SFL3-11/2-DN38	1.1/2"	1.1/2"
SFL3-2-DN38	2"	1.1/2"
SFL3-2-DN51	2"	2"

Tech Sheet 60618



90° Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-90-DN12	1/2"	1/2"
SFL3-1/2-90-DN16	1/2"	5/8"
SFL3-3/4-90-DN12	3/4"	1/2"
SFL3-3/4-90-DN16	3/4"	5/8"
SFL3-3/4-90-DN19	3/4"	3/4"
SFL3-1-90-DN19	1"	3/4"
SFL3-1-90-DN25	1"	1"
SFL3-114-90-DN25	1.1/4"	1"
SFL3-114-90-DN31	1.1/4"	1.1/4"
SFL3-112-90-DN31	1.1/2"	1.1/4"
SFL3-112-90-DN38	1.1/2"	1.1/2"
SFL3-2-90-DN38	2"	1.1/2"
SFL3-2-90-DN51	2"	2"

Tech Sheet 60620



45° Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-45-DN12	1/2"	1/2"
SFL3-1/2-45-DN16	1/2"	5/8"
SFL3-3/4-45-DN12	3/4"	1/2"
SFL3-3/4-45-DN16	3/4"	5/8"
SFL3-3/4-45-DN19	3/4"	3/4"
SFL3-1-45-DN19	1"	3/4"
SFL3-1-45-DN25	1"	1"
SFL3-114-45-DN25	1.1/4"	1"
SFL3-114-45-DN31	1.1/4"	1.1/4"
SFL3-112-45-DN31	1.1/2"	1.1/4"
SFL3-112-45-DN38	1.1/2"	1.1/2"
SFL3-2-45-DN38	2"	1.1/2"
SFL3-2-45-DN51	2"	2"

Tech Sheet 60619

SAE 6000 psi (6k)



Straight Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-DN12	1/2"	1/2"
SFS6-1/2-DN16	1/2"	5/8"
SFS6-3/4-DN12	3/4"	1/2"
SFS6-3/4-DN16	3/4"	5/8"
SFS6-3/4-DN19	3/4"	3/4"
SFS6-1-DN19	1"	3/4"
SFS6-1-DN25	1"	1"
SFS6-11/4-DN25	1.1/4"	1"
SFS6-11/4-DN31	1.1/4"	1.1/4"
SFS6-11/2-DN31	1.1/2"	1.1/4"
SFS6-11/2-DN38	1.1/2"	1.1/2"
SFS6-2-DN38	2"	1.1/2"
SFS6-2-DN51	2"	2"

Tech Sheet 60618



90° Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-90-DN12	1/2"	1/2"
SFS6-1/2-90-DN16	1/2"	5/8"
SFS6-3/4-90-DN12	3/4"	1/2"
SFS6-3/4-90-DN16	3/4"	5/8"
SFS6-3/4-90-DN19	3/4"	3/4"
SFS6-1-90-DN19	1"	3/4"
SFS6-1-90-DN25	1"	1"
SFS6-114-90-DN25	1.1/4"	1"
SFS6-114-90-DN31	1.1/4"	1.1/4"
SFS6-112-90-DN31	1.1/2"	1.1/4"
SFS6-112-90-DN38	1.1/2"	1.1/2"
SFS6-2-90-DN38	2"	1.1/2"
SFS6-2-90-DN51	2"	2"

Tech Sheet 60620



45° Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-45-DN12	1/2"	1/2"
SFS6-1/2-45-DN16	1/2"	5/8"
SFS6-3/4-45-DN12	3/4"	1/2"
SFS6-3/4-45-DN16	3/4"	5/8"
SFS6-3/4-45-DN19	3/4"	3/4"
SFS6-1-45-DN19	1"	3/4"
SFS6-1-45-DN25	1"	1"
SFS6-114-45-DN25	1.1/4"	1"
SFS6-114-45-DN31	1.1/4"	1.1/4"
SFS6-112-45-DN31	1.1/2"	1.1/4"
SFS6-112-45-DN38	1.1/2"	1.1/2"
SFS6-2-45-DN38	2"	1.1/2"
SFS6-2-45-DN51	2"	2"

Tech Sheet 60619



Split Flanges

0044	Flange Size	Bolt Type Metric	Bolt Type UNC
FLH-3-1/2	1/2"	M8 x 25	5/16" x 1.1/4"
FLH-3-3/4	3/4"	M10 x 30	3/8" x 1.1/4"
FLH-3-1	1"	M10 x 30	3/8" x 1.1/4"
FLH-3-1.1/4	1.1/4"	M10 x 30	7/16" x 1.1/2"
FLH-3-1.1/2	1.1/2"	M12 x 35	1/2" x 1.1/2"
FLH-3-2	2"	M12 x 35	1/2" x 1.1/2"

Tech Sheet 60617

Sold as halves, two halves required for each flange insert.



Split Flanges

0044	Flange Size	Bolt Type Metric	Bolt Type UNC
FLH-6-1/2	1/2"	M8 x 30	5/16" x 1.1/4"
FLH-6-3/4	3/4"	M10 x 35	3/8" x 1.1/4"
FLH-6-1	1"	M12 x 45	-
FLH-6-1.1/4	1.1/4"	M14 x 50	-
FLH-6-1.1/2	1.1/2"	M16 x 55	5/8" x 2"
FLH-6-2	2"	M20 x 65	3/4" x 2.1/2"

Tech Sheet 60617


Sold as halves, two halves required for each flange insert.

Bolts, washers and O-rings are not included and must be purchased separately

Fluid-Air Components Ltd

FT PRO®

PUSH STYLE HOSE SYSTEM



This range of quality hose and fittings has been designed and tested to fully comply to the specification of our SAE 100R6 hose.

The self grip style tail eliminates the requirement for swaged ferrules.

Hoses are available in a range of four colours, with standard end configurations of Metric DIN 2523, BSPP and JIC with A3C plated steel (other thread types and materials available upon request).

BENEFITS OF PUSH STYLE SYSTEM:

- High quality, complete low pressure hose system
- Fittings fully reusable
- No tooling required for assembly
- Fittings available in steel (stainless steel and brass available upon request)
- Static conducting hose available upon request
- System suitable for use with hydraulic oil, water, compressed air and water glycol based fluids at low pressure

FOUR COLOURS AS STANDARD FOR:

- Easy identification
- Identification of a particular medium by colour selected
- Colour-coded maintenance intervals

100R6-04-50 - EN854 - SAE 100R6 - 1/4" - 06MM -

Working Temperature:
-40°C to +100°C.

Maximum Working Pressure:
28 bar

HYDRAULIC HOSE RANGE

Oil Return/Fuel Hose SAE 100R6

100R6 Hose

Application:
Low pressure hydraulic applications,
for use with push style fittings. See page 40

Specification:
SAE100 R6, exceeds EN854

Construction:
Inner tube: oil resistant synthetic rubber (Nbr)
Reinforcement: 1 single textile yarn braid
Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Available per 1 metre

Working Temperature:
-40°C to +100°C.

50 Metre Coils, Black

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-04-50	1/4"	13.5	28	65	112
100R6-05-50	5/16"	15.1	28	75	112
100R6-06-50	3/8"	16.7	28	75	112
100R6-08-50	1/2"	20.6	28	100	112
100R6-10-50	5/8"	23.8	24	125	98
Page Tech Sheet 5010					



25 Metre Coils, Black

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-12-25	3/4"	27.8	21	150	84
100R6-16-25	1"	32.5	20	205	80
Page Tech Sheet 5010					

50 Metre Coils, Red

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-04-R-50	1/4"	13.5	28	65	112
100R6-06-R-50	3/8"	16.7	28	75	112
100R6-08-R-50	1/2"	20.6	28	100	112
Page Tech Sheet 5010					



25 Metre Coils, Red

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-12-R-25	3/4"	27.8	21	150	84
100R6-16-R-25	1"	32.5	20	205	80
Page Tech Sheet 5010					

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Oil Return/Fuel Hose SAE 100R6

100R6 Hose

Application:
Low pressure hydraulic applications,
for use with push style fittings. See page 40

Specification:
SAE100 R6, exceeds EN854

Construction:
Inner tube: oil resistant synthetic rubber (NBR)
Reinforcement: 1 single textile yarn braid
Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:
Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Available per 1 metre

Working Temperature:
-40°C to +100°C

50 Metre Coils, Blue

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-04-B-50	1/4"	13.5	28	65	112
100R6-06-B-50	3/8"	16.7	28	75	112
100R6-08-B-50	1/2"	20.6	28	100	112
Page Tech Sheet 5010					



25 Metre Coils, Blue

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-12-B-25	3/4"	27.8	21	150	84
100R6-16-B-25	1"	32.5	20	205	80
Page Tech Sheet 5010					

50 Metre Coils, Green

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-04-G-50	1/4"	13.5	28	65	112
100R6-06-G-50	3/8"	16.7	28	75	112
100R6-08-G-50	1/2"	20.6	28	100	112
Page Tech Sheet 5010					



25 Metre Coils, Green

0303	ID	OD mm	Max Pressure Bar	Bend Radius mm	Burst Pressure Bar
100R6-12-G-25	3/4"	27.8	21	150	84
100R6-16-G-25	1"	32.5	20	205	80
Page Tech Sheet 5010					

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PUSH STYLE HOSE SYSTEM


FT PRO

BSPP



Female

0309	Thread	To Suit Hose ID
PSBF0404CF	1/4"	1/4"
PSBF0606CF	3/8"	3/8"
PSBF0808CF	1/2"	1/2"
PSBF1212CF	3/4"	3/4"
PSBF1616CF	1"	1"



45° Elbow

0309	Thread	To Suit Hose ID
PSBF044504CF	1/4"	1/4"
PSBF064506CF	3/8"	3/8"
PSBF084508CF	1/2"	1/2"
PSBF124512CF	3/4"	3/4"
PSBF164516CF	1"	1"



90° Elbow

0309	Thread	To Suit Hose ID
PSBF049004CF	1/4"	1/4"
PSBF069006CF	3/8"	3/8"
PSBF089008CF	1/2"	1/2"
PSBF129012CF	3/4"	3/4"
PSBF169016CF	1"	1"

Metric Light



Female

0309	Thread	To Suit Hose ID
PSMFL06-04CF	6L (M12 x 1.5)	1/4"
PSMFL08-04CF	8L (M14 x 1.5)	1/4"
PSMFL10-06CF	10L (M16 x 1.5)	3/8"
PSMFL12-06CF	12L (M18 x 1.5)	3/8"
PSMFL15-08CF	15L (M22 x 1.5)	1/2"
PSMFL22-12CF	22L (M30 x 2.0)	3/4"



45° Elbow

0309	Thread	To Suit Hose ID
PSMFL06-45-04CF	6L (M12 x 1.5)	1/4"
PSMFL08-45-04CF	8L (M14 x 1.5)	1/4"
PSMFL10-45-06CF	10L (M16 x 1.5)	3/8"
PSMFL12-45-06CF	12L (M18 x 1.5)	3/8"
PSMFL15-45-08CF	15L (M22 x 1.5)	1/2"
PSMFL22-45-12CF	22L (M30 x 2.0)	3/4"



90° Elbow


0309	Thread	To Suit Hose ID
PSMFL06-90-04CF	6L (M12 x 1.5)	1/4"
PSMFL08-90-04CF	8L (M14 x 1.5)	1/4"
PSMFL10-90-06CF	10L (M16 x 1.5)	3/8"
PSMFL12-90-06CF	12L (M18 x 1.5)	3/8"
PSMFL15-90-08CF	15L (M22 x 1.5)	1/2"
PSMFL22-90-12CF	22L (M30 x 2.0)	3/4"

JIC



Female

0309	Thread	To Suit Hose ID
PSJF0404CF	7/16"	1/4"
PSJF0606CF	9/16"	3/8"
PSJF0808CF	3/4"	1/2"
PSJF1212CF	1.1/16"	3/4"



45° Elbow

0309	Thread	To Suit Hose ID
PSJF044504CF	7/16"	1/4"
PSJF064506CF	9/16"	3/8"
PSJF084508CF	3/4"	1/2"
PSJF124512CF	1.1/16"	3/4"



90° Elbow

0309	Thread	To Suit Hose ID
PSJF049004CF	7/16"	1/4"
PSJF069006CF	9/16"	3/8"
PSJF089008CF	3/4"	1/2"
PSJF129012CF	1.1/16"	3/4"

Designed and tested to work to the full specification of the 100R6 hose.

FAC
Fluid-Air Components Ltd

HYDRAULIC REUSABLE FITTINGS

Mild Steel Reusable Fittings



BSPP Male

0300	To Suit Hose ID	Thread
2024-8746	1/4"	1/4"
2024-8761	3/8"	3/8"
2024-8779	1/2"	1/2"
2024-8787	5/8"	5/8"
2024-8795	3/4"	3/4"
2024-8803	1"	1"



BSPP Female

0300	To Suit Hose ID	Thread
2024-8811	1/4"	1/4"
2182-7985	1/4"	3/8"
2182-7977	3/8"	1/4"
2024-8829	3/8"	3/8"
2182-7993	3/8"	1/2"
2024-8837	1/2"	1/2"
2024-8845	5/8"	5/8"
2024-8852	3/4"	3/4"
2024-8860	1"	1"



BSPP Female, 45° Elbow

0300	To Suit Hose ID	Thread
2182-8009	1/4"	1/4"
2024-8944	3/8"	3/8"
2024-8951	1/2"	1/2"
2024-8969	5/8"	5/8"
2182-8025	1"	1"



BSPP Female, 90° Elbow

0300	To Suit Hose ID	Thread
2024-8878	1/4"	1/4"
2024-8886	3/8"	3/8"
2024-8894	1/2"	1/2"
2024-8902	5/8"	5/8"
2024-8910	3/4"	3/4"
2024-8928	1"	1"



BSPP, Female Compact 90° Elbow

0300	To Suit Hose ID	Thread
2182-8033	1/4"	1/4"
2182-8041	3/8"	3/8"
2182-8058	1/2"	1/2"



JIC, Male

0300	To Suit Hose ID	Thread
2036-7330	1/4"	1/2"
2036-7355	3/8"	9/16"
2182-8215	1/2"	7/8"
2182-8223	3/4"	1.1/16"
2182-8231	1"	1.5/16"



JIC, Female

0300	To Suit Hose ID	Thread
2036-7405	1/4"	7/16"
2182-8173	1/4"	1/2"
2036-7413	1/4"	9/16"
2036-7439	3/8"	9/16"
2036-7447	3/8"	3/4"
2036-7454	1/2"	3/4"
2182-8181	1/2"	7/8"
2182-8199	3/4"	1.1/16"
2182-8207	1"	1.5/16"



JIC, Female 90° Elbow

0300	To Suit Hose ID	Thread
2036-7504	1/4"	7/16"
2036-7520	1/4"	9/16"
2182-8249	3/8"	9/16"
2182-8256	3/8"	3/4"
2036-7538	1/2"	3/4"
2182-8272	1/2"	7/8"
2036-7579	3/4"	1.3/16"
2182-8280	3/4"	1.1/16"
2182-8306	1"	1.5/16"

Stainless Steel Reusable Inserts

stainless steel



Swivel Female Insert, BSPP

0044	To Suit Hose ID	Thread
RU0404FSS	1/4"	1/4"
RU0606FSS	3/8"	3/8"
RU0808FSS	1/2"	1/2"
RU1616FSS	1"	1"

Mild Steel Reusable Ferrules



R1AT Non-skive

0300	To Suit Hose ID
2028-5078	1/4"
2028-5086	3/8"
2028-5094	1/2"
2028-5102	5/8"
2028-5110	3/4"
2028-5128	1"



R2AT Non-skive

0300	To Suit Hose ID
2024-8993	1/4"
2024-9009	3/8"
2024-9017	1/2"
2024-9025	5/8"
2024-9033	3/4"
2024-9041	1"



R1A Skive

0300	To Suit Hose ID
2182-8066	1/4"
2182-8074	3/8"
2182-8082	1/2"
2182-8108	1"



R2A Skive

0300	To Suit Hose ID
2182-8116	1/4"
2182-8124	3/8"
2182-8132	1/2"
2182-8140	3/4"
2182-8157	1"

Stainless Steel Reusable Sockets

stainless steel



R1AT, Reusable Socket

0044	To Suit Hose ID
R1-04SS	1/4"
R1-06SS	3/8"
R1-08SS	1/2"
R1-16SS	1"

FAC
Fluid-Air Components Ltd

STOPflex®
FOR PRESSURE HOSES

RETENTION SYSTEM FOR PRESSURE HOSES


Prevent whipping of a pressurised hose in the event of the hose separating from its fitting



Suitable for various applications, including:
- DIN and BSP Fittings
- JIC Fittings
- SAE Flanges

- Protects both the operator and components
- Recommended by the International Hydraulic Safety Authority - the world leader in hydraulic safety training
- Suitable for all kinds of flexible hose
- Tested protection: compliant with EN 853, EN 854, EN 855, EN 856, EN 857, SAE J517

How it works…



1: Disengagement:
A hose disengages from its ferrule.



2: Release/venting of pressure
The pressurised oil exits from the hose and the release of energy results in the hose gaining considerable velocity, triggering a hazardous "whip effect" which is very dangerous to anyone or anything in its vicinity.



Step 3: Restraint
This is where the Stopflex system gets into operation: the stainless steel cable is tensioned and restrains the hose, preventing it from 'whipping'. The plate cuts into the rubber of the hose, to ensure that the clamp remains firmly attached. The hose clamp and plate absorb the force released from the travel of the flexible hose. This critical step occurs within just a few seconds.

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STOPFLEX

Retention System for Pressure Hoses



To suit DIN & BSP Fittings

0466	To Suit	Diameter mm	Length mm
STOPFUDIN145	8L - 1/4"	14.5	300
STOPFUDIN17	8S - 10L - 3/8"	17	300
STOPFUDIN185	10S - 12L	18.5	300
STOPFUDIN205	12S	20.5	300
STOPFUDIN225	14S - 15L - 1/2"	22.5	300
STOPFUDIN245	16S - 5/8"	24.5	300
STOPFUDIN265	18L - 3/4"	26.5	300
STOPFUDIN305	20S - 22L	30.5	300
STOPFUDIN34	1"	34	450
STOPFUDIN365	25S - 28L	36.5	450
STOPFUDIN425	30S - 1.1/4"	42.5	450
STOPFUDIN455	35L	45.5	450
STOPFUDIN49	1.1/2"	49	450
STOPFUDIN525	38S - 42L	52.5	450
STOPFUDIN60	2"	60	450
Tech Sheet 60137			



To suit JIC Fittings

0466	To Suit	Diameter mm	Length mm
STOPFUJIC115	7/16"	11.5	300
STOPFUJIC132	1/2"	13.2	300
STOPFUJIC148	9/16"	14.8	300
STOPFUJIC195	3/4"	19.5	300
STOPFUJIC228	7/8"	22.8	300
STOPFUJIC275	1.1/16"	27.5	300
STOPFUJIC307	1.3/16"	30.7	300
STOPFUJIC34	1.5/16"	34	450
STOPFUJIC415	1.5/8"	41.5	450
STOPFUJIC48	1.7/8"	48	450
STOPFUJIC64	2.1/2"	64	450
Tech Sheet 60137			



To suit SAE Flanges

0466	To Suit	Diameter mm	Length mm
STOPFUSAE085	1/2" - 3000 psi	8.5	300
STOPFUSAE105	3/4" - 1.1/4" 3000 psi, 3/4" 6000 psi	10.5	450
STOPFUSAE125	1.1/2" - 2" 3000 psi, 1" 6000 psi	12.5	450
STOPFUSAE145	1.1/4" - 6000 psi	14.5	450
STOPFUSAE165	1.1/2" - 6000 psi	16.5	450
STOPFUSAE205	2" - 6000 psi	20.5	450
Tech Sheet 60137			



To suit Various Applications

0466	To Suit	Diameter mm	Length mm
STOPFUVARIE	Large Plate	13	450
STOPFUVARIES	Small Plate	13	450
Tech Sheet 60137			



Hose Band


0466	Minimum Diameter mm	Maximum Diameter mm	Thread
STOPFA11115	11	11.5	M6
STOPFA12125	12	12.5	M6
STOPFA13135	13	13.5	M6
STOPFA1415	14	15	M6
STOPFA1617	16	17	M6
STOPFA1718	17	18	M6
STOPFA1819	18	19	M6
STOPFA2021	20	21	M6
STOPFA2122	21	22	M6
STOPFA2223	22	23	M6
STOPFA2425	24	25	M6
STOPFA2526	25	26	M6
STOPFA2627	26	27	M6
STOPFA2728	27	28	M6
STOPFA2829	28	29	M6
STOPFA3031	30	31	M6
STOPFA3233	32	33	M6
STOPFA3435	34	35	M6
STOPFA3637	36	37	M6
STOPFA3839	38	39	M6
STOPFA3940	39	40	M6
STOPFA4041	40	41	M6
STOPFA4243	42	43	M6
STOPFA4344	43	44	M6
STOPFA4445	44	45	M8
STOPFA4547	45	47	M8
STOPFA4850	48	50	M8
STOPFA5153	51	53	M8
STOPFA5354	53	54	M8
STOPFA5456	54	56	M8
STOPFA5759	57	59	M8
STOPFA6062	60	62	M8
STOPFA6365	63	65	M8
STOPFA6668	66	68	M8
STOPFA6971	69	71	M8
STOPFA7274	72	74	M8
STOPFA7577	75	77	M8
STOPFA7880	78	80	M8
STOPFA8183	81	83	M8
STOPFA8486	84	86	M8
STOPFA8789	87	89	M8
STOPFA9092	90	92	M8
STOPFA9395	93	95	M8
Tech Sheet 60137			

Fluid-Air Components Ltd

FIRE SLEEVE

FT PRO®

Shield your hoses from extreme temperatures



The protective sleeve is easily installed whilst assembling a hose or can also be retro-fitted during maintenance and repair activities.

In addition to defending critical equipment in harsh environmental conditions, the sleeve also mitigates health and safety risks by eliminating temperature extreme hazards so that scorching and burning injuries are avoided.

- Continuous protection at 260°C ambient temperatures
- Withstands molten metal splash at 1200°C
- UL94 flammability V-0
- Worker safety protection against lines that carry hot or volatile fluids
- Resistant to tears and abrasion
- Highly flexible and easily fitted
- MSHA approved
- RoHS 3 compliant









FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PROTECTIVE HOSE SLEEVES

Fire Sleeve MSHA UL 94 V-0



Red Oxide Per Metre

0319	ID mm	OD mm	SAE Size
FS-06-R	6	11	-04
FS-10-R	10	15	-06
FS-12-R	12	17	-08
FS-14-R	14	19	-09
FS-16-R	16	21	-10
FS-19-R	19	24	-12
FS-22-R	22	27	-14
FS-25-R	25	30	-16
FS-28-R	28	33	-18
FS-32-R	32	37	-20
FS-35-R	35	40	-22
FS-38-R	38	43	-24
FS-41-R	41	46	-26
FS-44-R	44	49	-28
FS-51-R	51	56	-32
FS-57-R	57	62	-
FS-63-R	63	68	-40
FS-70-R	70	75	-
FS-76-R	76	81	-48
FS-83-R	83	88	-
FS-89-R	89	94	-56
FS-95-R	95	100	-60
FS-102-R	102	107	-
FS-114-R	114	119	-72
FS-127-R	127	132	-

Tech Sheet 70055



Red Oxide 15 Metre Coils

0319	ID mm	OD mm	SAE Size
FS-06-R-15	6	11	-04
FS-10-R-15	10	15	-06
FS-12-R-15	12	17	-08
FS-14-R-15	14	19	-09
FS-16-R-15	16	21	-10
FS-19-R-15	19	24	-12
FS-22-R-15	22	27	-14
FS-25-R-15	25	30	-16
FS-28-R-15	28	33	-18
FS-32-R-15	32	37	-20
FS-35-R-15	35	40	-22
FS-38-R-15	38	43	-24
FS-41-R-15	41	46	-26
FS-44-R-15	44	49	-28
FS-51-R-15	51	56	-32
FS-57-R-15	57	62	-
FS-63-R-15	63	68	-40
FS-70-R-15	70	75	-
FS-76-R-15	76	81	-48
FS-83-R-15	83	88	-
FS-89-R-15	89	94	-56
FS-95-R-15	95	100	-60
FS-102-R-15	102	107	-
FS-114-R-15	114	119	-72
FS-127-R-15	127	132	-

Tech Sheet 70055



Self Amalgamating Tape 11 Metre Roll

0319	Colour	Width mm
FS-TAPE-25-N-11	Black	25
FS-TAPE-25-R-11	Red	25

Tech Sheet 70056

Galvanised Steel Spring Hose Guard

Open coil spring guard is a very effective and economic means of protecting hoses from expensive abrasive and crush damage.

Manufactured from high tensile spring steel wire.

Available in other sizes on request.

These products cannot be ordered online, please contact our sales office.



10 Metre Coils

0362	ID mm	Wall Thickness mm
SHG-18	18	1.6
SHG-20	20	1.6
SHG-22	22	2.0
SHG-24	24	2.0
SHG-25	25	2.0
SHG-26	26	2.0
SHG-29	29	2.0
SHG-31	31	3.2
SHG-33	33	3.2
SHG-37	37	3.2
SHG-41	41	3.2
SHG-43	43	3.2
SHG-45	45	3.2
SHG-49	49	3.2
SHG-51	51	3.2
SHG-54	54	3.2
SHG-56	56	3.2
SHG-60	60	3.2
SHG-63	63	3.2
SHG-70	70	3.2

HEAT SHRINK

2:1 Ratio (min) Thin Wall UL 224 VW-1



Crosslinked Polyolefin, 50 Metre Reel

0319	Colour	ID mm
HS2T-6-R-50	Red	6.35-12.7
HS2T-8-R-50	Red	8-16
HS2T-10-R-50	Red	9.5-19.1
HS2T-13-R-50	Red	12.7-25.4
HS2T-16-R-50	Red	16-32
HS2T-19-R-50	Red	19.00-38.1
HS2T-6-N-50	Black	6.35-12.7
HS2T-8-N-50	Black	8-16
HS2T-10-N-50	Black	9.5-19.1
HS2T-13-N-50	Black	12.7-25.4
HS2T-16-N-50	Black	16-32
HS2T-19-N-50	Black	19.00-38.1

Tech Sheet 70057



Crosslinked Polyolefin, 30 Metre Reel

0319	Colour	ID mm
HS2T-25-R-30	Red	25.4-50.8
HS2T-38-R-30	Red	38.1-76.2
HS2T-51-R-30	Red	50.8-101.6
HS2T-25-N-30	Black	25.4-50.8
HS2T-38-N-30	Black	38.1-76.2
HS2T-51-N-30	Black	50.8-101.6

Tech Sheet 70057

Fluid-Air Components Ltd

PROTECTIVE HOSE SLEEVES

Hose Protection Sleeve

The most economical option for managing, containing and protecting your hose, cables and other equipment.

Applications include protection for hose assemblies, ropes and wire harnesses.

- MSHA approved for underground mines, IC 171/1
- ISO 6945 abrasion standard, minimum 50,000 cycles
- Melting point: +220°C
- Resists mildew and bacterial growth
- Non-toxic
- Excellent resistance to UV ageing
- Very good chemical compatibility






20 Metre Coils

0460	ID mm
LGSLEEVE-18	18
LGSLEEVE-21	21
LGSLEEVE-25	25
LGSLEEVE-31	31
LGSLEEVE-36	36
LGSLEEVE-40	40
LGSLEEVE-45	45
LGSLEEVE-52	52
LGSLEEVE-60	60
LGSLEEVE-73	73
LGSLEEVE-85	85
LGSLEEVE-93	93
Tech Sheet 20377	

Nylon Hose Protection Sleeve

This textile sleeve consists of nylon multifilament. Complying with European standards, it has excellent abrasion resistance, and is ideal for protecting people, environment and machinery against any possible hydraulic hose oil leakage or spill.

- Material: nylon (polyamide)
- Thickness: 0.8mm (European standard)
- Melting point: +230°C
- MSHA approved: IC 293-1
- ISO 6945 abrasion standard, minimum 50,000 cycles
- UV solar protected: BS EN 13758-1
- Burst and leakage protected: SAE J343/ISO 3457
- Conductivity requirement: ISO 8031 approved
- Pin hole test approved



Working Temperature: -40°C to +125°C (the sleeve loses 10% of its resistance at +125°C)

20 Metre Coils

0672	ID mm
FPSLEEVE-017	17
FPSLEEVE-020	20
FPSLEEVE-023	23
FPSLEEVE-027	27
FPSLEEVE-031	31
FPSLEEVE-036	36
FPSLEEVE-040	40
FPSLEEVE-044	44
FPSLEEVE-055	55
FPSLEEVE-060	60
FPSLEEVE-066	66
FPSLEEVE-073	73
FPSLEEVE-093	93
FPSLEEVE-112	112
Tech Sheet 68268	


Hose Burst Guard

Our highest performance sleeve, designed to control and dissipate fluids from dangerous hose bursts.

For use in line-of-sight applications, to help protect personnel and equipment from the effects of a hose failure.

- MSHA approved IC171/1
- Outer layer withstands a minimum 350,000 cycles, abrasion tested using ISO 6945 test method
- Controls bursts up to 13,000 psi
- Two-layer structure with inner yellow layer acting as an abrasion indicator
- Meets ISO 3457, 4413, 6945, 6805, EN 414, MDG 41 and MSHA IC171/2
- Excellent resistance to UV ageing
- 40 metre lengths available on request
- Melting point: +215°C

Maximum Burst Control Pressure: 890 bar





30 Metre Coils

0460	ID mm
BUSLEEVE-31	31
BUSLEEVE-36	36
BUSLEEVE-42	42
BUSLEEVE-46	46
BUSLEEVE-54	54
Tech Sheet 60335	

10 Metre Coils

0460	ID mm
BUSLEEVE-31-10	31
BUSLEEVE-36-10	36
BUSLEEVE-42-10	42
BUSLEEVE-46-10	46
BUSLEEVE-54-10	54
Tech Sheet 60335	

Hose Wrap Sleeve

Ideal for hose bundling, adding abrasion protection post assembly or replacing damaged existing sleeves.

- Quick assembly
- Lightweight
- Proprietary bonding process allows cutting without fraying
- Meets ISO 6945 abrasion standard
- Excellent UV resistance
- Velcro fastening with shear strength of 22 psi
- Maximum temperature without degradation: +225°C



45 Metre Coils


0460	ID mm
WRSLEEVE-25	25
WRSLEEVE-75	75
WRSLEEVE-100	100
WRSLEEVE-125	125
WRSLEEVE-150	150
WRSLEEVE-175	175
WRSLEEVE-200	200
Tech Sheet 60336	

Fluid-Air Components Ltd



Spiral Hose Guard Features

- Provides high strength abrasion resistance for most types of hydraulic, pneumatic and industrial hose assemblies across a wide range of industries including: mining, forestry, drill rigs, plant and agricultural machinery, automotive, marine and offshore
- Exceptional anti-crushing performance
- High abrasion resistance
- Good UV resistance
- Easy installation and routing
- Proven in arduous conditions
- Conveniently coiled and packed in cartons for easy storage
- Suitable for wrapping single hoses or multiple hose looms



	Hose Type								
Hose I.D.	R1AT	R2AT	1SC	2SC	4SP	4SH	R13	R15	R17
3/16"	A	A							
1/4"	B	B	B	B	C				B
5/16"	B	C							B
3/8"	C	C	C	C	D			D	C
1/2"	D	D	D	D	E			E	D
5/8"	D	E							E
3/4"	E	E	E	E	E	E	E	E	E
1"	F	F		F	F	F	F	F	F
1.1/4"	G	G			G	G	G	G	
1.1/2"	G	H			H	H	H		
2"	I	I			I	I	I	I	

Fluid-Air Components Ltd

PROTECTIVE HOSE SLEEVES

Polypropylene Protective Hose Sleeves


Working Temperature:
-40°C to +90°C

Available in various colours on request.



Flat Type Black, Polypropylene

0369	ID mm	Length Metres	To Suit
FSG-10	10	20	A
FSG-12	12	20	B
FSG-14	14	20	-
FSG-16	16	20	C
FSG-20	20	20	D
FSG-25	25	20	E
FSG-32	32	20	F
FSG-42	42	10	G
FSG-50	50	10	H
FSG-60	60	10	I
FSG-74	74	10	-
FSG-80	80	10	-
FSG-88	88	10	-
FSG-100	100	10	-
FSG-130	130	10	-
FSG-150	150	10	-
FSG-200	200	2	-
Tech Sheet 10265			



Flat Type Yellow, Polypropylene

0369	ID mm	Length Metres	To Suit
FYSG-10	10	20	A
FYSG-12	12	20	B
FYSG-16	16	20	C
FYSG-20	20	20	D
FYSG-25	25	20	E
FYSG-32	32	20	F
FYSG-42	42	10	G
FYSG-50	50	10	H
FYSG-60	60	10	I
Tech Sheet 10265			



Round Type Black, Polypropylene

0369	ID mm	Length Metres	To Suit
RSG-10	10	20	A
RSG-12	12	20	B
RSG-16	16	20	C
RSG-20	20	20	D
RSG-25	25	20	E
RSG-32	32	20	F
RSG-42	42	10	G
RSG-50	50	10	H
RSG-60	60	10	I
Tech Sheet 10265			



Flat Type Hi-Viz Green, Polypropylene

0369	ID mm	Length	To Suit
FGSG-10	10	20	A
FGSG-12	12	20	B
FGSG-14	14	20	-
FGSG-16	16	20	C
FGSG-20	20	20	D
FGSG-25	25	20	E
FGSG-32	32	20	F
FGSG-42	42	10	G
FGSG-50	50	10	H
FGSG-60	60	10	I
Tech Sheet 10265			

Larger sizes are available; speak to your account manager for further information.

Fluid-Air Components Ltd

HOSE & PIPE CLEANING KITS

The pellet launcher uses compressed air to fire a foam pellet through tube, pipe and hose, clearing soft deposits and loose debris as it travels through.

The pellet launcher is designed to operate at 80-110 psi and should be connected, by a 3/8" (10mm) ID air line, to an air source NOT exceeding 150 psi.

Maximum Working Pressure:
. 0 bar

Pellet Launcher Kits

The mobile kit is specifically for use with hose, tube and pipe from 5mm to 50mm. The hose nozzle fits over the tube, hose or pipe to be cleaned.

The specially designed and extremely robust pellet launcher controls the air flow. It attaches to a 50mm crimp head through a patented interlocking system. The nozzles are inserted into the head. These are designed to reduce the pellet in size for insertion into the pipe.

All nozzles fit into the 50mm crimp head. All kits come in a case with instruction manuals and a pellet usage chart for identifying the correct pellets to use with your application.

This kit consist of the following:

- AM-1™ hand piece
- 50mm crimp head
- Adapter ring
- White hose nozzles: 6, 8, 10, 13, 16, 19, 25, 32, 38 and 50mm



Pellets used in the system will travel through 90° angles, tee joints, coils, U tubes, bore and straight-through valves.

The specially designed and extremely robust pellet launcher controls the air flow. It attaches to the 32mm and 50mm heads through a patented interlocking system. The nozzles are inserted into the head. These are designed to reduce the pellet in size for insertion into the pipe.

All nozzles fit into either the 32mm or 50mm heads. All kits come in a case with instruction manuals and a pellet usage chart for identifying the correct pellets to use with your application.

This kit consist of the following:

- AM-1™ hand piece
- 32mm and 50mm heads
- White hose nozzles: 6, 8, 10, 13, 16, 19, 25, 32, 38 and 50mm
- Green tube and JIC nozzles: 5, 6, 8, 10, 13, 16, 19, 22, 25, 32, 38 and 50mm
- Blue BSP nozzles: 6, 10, 13, 16, 19, 25 and 32mm



Mobile Kit

0489	Thread	Nozzle Quantity	Nozzle Hole Size
MOBI-KIT	1/4"	10 x Hose Nozzles	6mm to 50mm
		Tech Sheet 60438	

Full Kit

0489	Thread	Nozzle Quantity	Nozzle Hole Size
FULL-KIT	1/4"	31 x Hose Nozzles	6mm to 50mm
		Tech Sheet 60439	

Foam Pellets

Standard pellets are designed for removal of debris from all hose, tube or pipe, without fittings. Pellets are manufactured from foam and should be approximately 15-20% larger than the ID of the hose, tube or pipe being cleaned. Please select the pellet closest to the size required from the list.



These multipurpose pellets are designed for use in complex assemblies, hoses with fittings and to eliminate fine particles of contamination. Pellets are manufactured from foam and should be approximately 15-20% larger than the ID of the hose, tube or pipe being cleaned. Please select the pellet closest to the size required from the list.



Standard

0490	OD mm
NSP007	7
NSP008	8
NSP010	10
NSP012	12
NSP014	14
NSP016	16
NSP018	18
NSP020	20
NSP022	22
NSP024	24
NSP026	26
NSP028	28
NSP030	30
NSP033	33
NSP035	35
NSP040	40
NSP045	45
NSP050	50
NSP055	55
NSP060	60

General Purpose

0490	OD mm
MPP007	7
MPP008	8
MPP010	10
MPP012	12
MPP014	14
MPP016	16
MPP018	18
MPP020	20
MPP022	22
MPP024	24
MPP026	26
MPP028	28
MPP030	30
MPP033	33
MPP035	35
MPP040	40
MPP045	45
MPP050	50
MPP055	55
MPP060	60

Fluid-Air Components Ltd

Plugtite Industrial

Designed and used to prevent the leakage and contamination of various fluids, including hydraulics and chemicals, during the service, maintenance and storage of machinery and equipment. Used in industrial areas such as hydraulic, chemical, processing, MRO, HVAC, mining and heavy equipment.



Made from a special compound in our own factory

The **Plugtite** aperture has been designed and engineered to give the plug greater compression than standard solid plugs, ensuring a perfect seal whilst still being able to be cut to size if needed.

- Greater resistance to most oils within the temperature range of -25°C to +90°C
- Does not shrink, leak or discolour
- Resistant to sunlight for greater shelf life; does not split/crack or deteriorate
- Easy to use; insert, squeeze, press home and release
- The compressed rubber ensures a tight fit

3 Standard Apertures
Plugtite Small 2mm to 14mm
Plugtite Medium 6mm to 24mm
Plugtite Large 15mm to 45mm

Other Members of the Plugtite Family

Plugtite - Hygiene FDA Approved
This plug is specifically produced for use in the food and beverage processing industry.
The use of the plugs helps to ensure that sensitive working areas are kept free of contamination from oils and other fluids by preventing leakage when cleaning and servicing machinery and equipment.

Plugtite - Heat Resistant
For use in operations such as electrostatic lines, die casting, etc, where high heat resistance is a requirement.



Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

The new generation of service and maintenance plugs

SERVICE PLUGS

Spill Prevention

- Stop contamination
- Plugtite products are used to prevent contamination of all sorts of chemical compounds into the surrounding environment

Working Temperature:
-25°C to +90°C

NEW ECO FRIENDLY CARDBOARD PACKAGING






Standard Pack

0709	Size mm	Box Quantity
PLUGTITE-STD-10	6-24	10
	Tech Sheet 68083	



XL Pack

0709	Size mm	Box Quantity
PLUGTITE-MAX-4	15-45	4
	Tech Sheet 68083	



Micro Pack

0709	Size mm	Box Quantity
PLUGTITE-MINI-20	2-14	20
	Tech Sheet 68083	



Mix Pack

0709	Size mm	Box Quantity
PLUGTITE-MIX-9	2-45	9
	Tech Sheet 68083	

Fluid-Air Components Ltd

BURNETT & HILLMAN

HYDRAULIC ADAPTOR UK MANUFACTURER



Our extensive range of adaptors includes stock of more than 3000 different variations of JIC, SAE, Metric, BSP, BSPT, NPTF and NPSM made from mild steel (BS EN 10277:3:199 – 230M07Pb).



We specialise in not just one type of product – we have the flexibility to produce special requirements alongside our standard product ranges. This diversity of ranges and sizes, combines with our unparalleled customer service and technical assistance.

The market for hydraulic adaptors is a truly diverse one. Hydraulics are used in almost every facet of industry: Agriculture, Transport, Waste, Defence, Manufacturing, Marine, Construction, Mining, Engineering, etc. Hydraulic power plays a crucial global role in keeping these and other industries moving.

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



THREADS AND DIMENSIONS

- BSP adaptor dimensions are compatible with ISO 8434-6 and BS 5200.
- BSP DIN spec adaptors are to DIN 3852 Form A.
- BSPP and NCB threads are to BS EN ISO 228-1.
- BSPT threads are to BS EN 10226-1.
- JIC adaptors are to SAE J514.
- JIC and SAE threads are to BS 1580.
- JIS are to JIS B 8363
- Metric threads are to BS 3643-2.
- NPTF threads are to ANSI B1 20.3

PLATING

- Acid zinc plating is to ISO 2081, Fe/Zn8/A/T2.
- Fe = Ferrous substrate.
- Zn8 = Zinc coating 8 microns thick.
- A = Clear passivate.
- T2 = Application of organic or inorganic sealants.

MATERIAL

- Steel used for stock parts is 230M07Pb/11SMnPb37 as to BE EN 10277-3.
- Stainless is grade 316 to BS EN 10277-1.

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Male/Male Adaptors

Equal BSPP Male x BSPP Male 60° Cone



0014	Thread	Thread
1BP0202	1/8"	1/8"
1BP0404	1/4"	1/4"
1BP0606	3/8"	3/8"
1BP0808	1/2"	1/2"
1BP1010	5/8"	5/8"
1BP1212	3/4"	3/4"
1BP1616	1"	1"
1BP2020	1.1/4"	1.1/4"
1BP2424	1.1/2"	1.1/2"
1BP2828	1.3/4"	1.3/4"
1BP3232	2"	2"
1BP4040	2.1/2"	2.1/2"
1BP4848	3"	3"
1BP6464	4"	4"
Tech Sheet 20000		

Unequal BSPP Male x BSPP Male 60° Cone



0014	Thread	Thread
1BP0204	1/8"	1/4"
1BP0206	1/8"	3/8"
1BP0208	1/8"	1/2"
1BP0406	1/4"	3/8"
1BP0408	1/4"	1/2"
1BP0410	1/4"	5/8"
1BP0412	1/4"	3/4"
1BP0416	1/4"	1"
1BP0420	1/4"	1.1/4"
1BP0432	1/4"	2"
1BP0608	3/8"	1/2"
1BP0610	3/8"	5/8"
1BP0612	3/8"	3/4"
1BP0616	3/8"	1"
1BP0620	3/8"	1.1/4"
1BP0624	3/8"	1.1/2"
1BP0810	1/2"	5/8"
1BP0812	1/2"	3/4"
1BP0816	1/2"	1"
1BP0820	1/2"	1.1/4"
1BP0824	1/2"	1.1/2"
1BP0832	1/2"	2"
1BP1012	5/8"	3/4"
1BP1016	5/8"	1"
1BP1020	5/8"	1.1/4"
1BP1216	3/4"	1"
1BP1220	3/4"	1.1/4"
1BP1224	3/4"	1.1/2"
1BP1232	3/4"	2"
1BP1620	1"	1.1/4"
1BP1624	1"	1.1/2"
1BP1632	1"	2"
1BP1640	1"	2.1/2"
1BP2024	1.1/4"	1.1/2"
1BP2032	1.1/4"	2"
1BP2428	1.1/2"	1.3/4"
1BP2432	1.1/2"	2"
1BP2440	1.1/2"	2.1/2"
1BP2832	1.3/4"	2"
Tech Sheet 20000		

BSPP Male x BSPP Male 60° Cone DIN 3852 Form A



0014	Thread	Thread
1BPA0202	1/8"	1/8"
1BPA0204	1/8"	1/4"
1BPA0404	1/4"	1/4"
1BPA0406	1/4"	3/8"
1BPA0408	1/4"	1/2"
1BPA0606	3/8"	3/8"
1BPA0608	3/8"	1/2"
1BPA0808	1/2"	1/2"
1BPA0812	1/2"	3/4"
1BPA0816	1/2"	1"
1BPA1212	3/4"	3/4"
1BPA1216	3/4"	1"
1BPA1616	1"	1"
1BPA1620	1"	1.1/4"
1BPA1624	1"	1.1/2"
1BPA2020	1.1/4"	1.1/4"
1BPA2024	1.1/4"	1.1/2"
1BPA2424	1.1/2"	1.1/2"
1BPA2432	1.1/2"	2"
1BPA3232	2"	2"
Tech Sheet 20000		

BSPP Male x BSPP Male 60° Cone with Restrictor



0014	Thread	Thread	Restrictor
1BPR0404-1/32	1/4"	1/4"	1/32"
1BPR0404-1	1/4"	1/4"	1mm
1BPR0404-1/16	1/4"	1/4"	1/16"
1BPR0406-1/32	1/4"	3/8"	1/32"
1BPR0406-1	1/4"	3/8"	1mm
1BPR0406-1/16	1/4"	3/8"	1/16"
1BPR0408-1/32	1/4"	1/2"	1/32"
1BPR0408-1/16	1/4"	1/2"	1/16"
1BPR0606-1/32	3/8"	3/8"	1/32"
1BPR0606-1	3/8"	3/8"	1mm
1BPR0606-1/16	3/8"	3/8"	1/16"
1BPR0608-1/32	3/8"	1/2"	1/32"
1BPR0608-1	3/8"	1/2"	1mm
1BPR0608-3	3/8"	1/2"	3mm
1BPR0612-1/16	3/8"	3/4"	1/16"
1BPR0808-1/32	1/2"	1/2"	1/32"
1BPR0808-1	1/2"	1/2"	1mm
1BPR0808-1/16	1/2"	1/2"	1/16"
Tech Sheet 20000			

BSPP Male x BSPP Male 60° Cone 174 Spec.



0014	Thread	Thread
00100	1/8"	1/4"
00114	1/4"	1/4"
00117	1/4"	3/8"
00101	1/4"	1/2"
00120	3/8"	3/8"
00102	3/8"	1/2"
00103	3/8"	3/4"
00125	1/2"	1/2"
00104	1/2"	3/4"
00116	1/2"	1"
00115	3/4"	3/4"
00106	3/4"	1"
00118	1"	1"
00119	1"	1.1/4"
00109	1.1/4"	1.1/4"
00110	1.1/4"	1.1/2"
00129	1.1/4"	2"
00111	1.1/2"	1.1/2"
00112	1.1/2"	2"
00113	2"	2"
Tech Sheet 20000		

BSPP Male x BSPP Male 60° Cone BS5200



0014	Thread	Thread
52021	1/2"	1/2"
Tech Sheet 20000		

BSPP Male x BSPP Male 60° Cone with Restrictor Blank Only



0014	Thread	Thread mm
13080	1/4"	1/4"
13081	1/4"	3/8"
13082	1/4"	1/2"
13083	3/8"	3/8"
13084	3/8"	1/2"
13089	3/8"	3/4"
13085	1/2"	1/2"
13086	1/2"	3/4"
13088	3/4"	1"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Male Adaptors



BSPP Male 60° Cone x BSPT Male

0014	Thread	Thread
1BP02T02	1/8"	1/8"
1BP02T04	1/8"	1/4"
1BP02T06	1/8"	3/8"
1BP04T02	1/4"	1/8"
1BP04T04	1/4"	1/4"
1BP04T06	1/4"	3/8"
1BP04T08	1/4"	1/2"
1BP04T12	1/4"	3/4"
1BP06T02	3/8"	1/8"
1BP06T04	3/8"	1/4"
1BP06T06	3/8"	3/8"
1BP06T08	3/8"	1/2"
1BP06T12	3/8"	3/4"
1BP06T16	3/8"	1"
1BP08T02	1/2"	1/8"
1BP08T04	1/2"	1/4"
1BP08T06	1/2"	3/8"
1BP08T08	1/2"	1/2"
1BP08T10	1/2"	5/8"
1BP08T12	1/2"	3/4"
1BP08T16	1/2"	1"
1BP08T20	1/2"	1.1/4"
1BP10T06	5/8"	3/8"
1BP10T08	5/8"	1/2"
1BP10T10	5/8"	5/8"
1BP10T12	5/8"	3/4"
1BP12T04	3/4"	1/4"
1BP12T06	3/4"	3/8"
1BP12T08	3/4"	1/2"
1BP12T12	3/4"	3/4"
1BP12T16	3/4"	1"
1BP12T20	3/4"	1.1/4"
1BP12T24	3/4"	1.1/2"
1BP16T06	1"	3/8"
1BP16T08	1"	1/2"
1BP16T12	1"	3/4"
1BP16T16	1"	1"
1BP16T20	1"	1.1/4"
1BP16T24	1"	1.1/2"
1BP16T32	1"	2"
1BP20T16	1.1/4"	1"
1BP20T20	1.1/4"	1.1/4"
1BP20T24	1.1/4"	1.1/2"
1BP20T32	1.1/4"	2"
1BP24T16	1.1/2"	1"
1BP24T20	1.1/2"	1.1/4"
1BP24T24	1.1/2"	1.1/2"
1BP24T32	1.1/2"	2"
1BP32T16	2"	1"
1BP32T20	2"	1.1/4"
1BP32T24	2"	1.1/2"
1BP32T32	2"	2"
1BP32T40	2"	2.1/2"
1BP32T48	2"	3"
1BP40T40	2.1/2"	2.1/2"
Tech Sheet 20000		



BSPP Male 60° Cone x SAE O-Ring Face Seal Male

0014	Thread	Thread
74005	1/8"	9/16"
74000	1/4"	9/16"
74006	1/4"	11/16"
74001	3/8"	11/16"
74007	3/8"	13/16"
74015	1/2"	11/16"
74002	1/2"	13/16"
74008	1/2"	1"
74011	1/2"	1.3/16"
74014	5/8"	1.3/16"
74009	3/4"	1"
74003	3/4"	1.3/16"
74004	1"	1.7/16"
74012	1"	1.11/16"
74010	1.1/4"	1.11/16"
Tech Sheet 20000		



BSPP Male 60° Cone x SAE Male 45° External Flare

0014	Thread	Thread
13200	3/8"	5/8"
Tech Sheet 20000		



BSPT Male x JIS Male (BSPP Threads)

0014	Thread	Thread
00313-JIS	3/8"	3/8"
Tech Sheet 20000		



BSPT Male x NPTF Male

0014	Thread	Thread
1BNT0204	1/8"	1/4"
1BNT0402	1/4"	1/8"
1BNT0404	1/4"	1/4"
1BNT0406	1/4"	3/8"
1BNT0606	3/8"	3/8"
1BNT0604	3/8"	1/4"
1BNT0808	1/2"	1/2"
1BNT1212	3/4"	3/4"
1BNT1616	1"	1"
1BNT2420	1.1/2"	1.1/4"
1BNT2424	1.1/2"	1.1/2"
1BNT3232	2"	2"
1BNT4040	2.1/2"	2.1/2"
Tech Sheet 20000		



BSPT Male x BSPT Male

0014	Thread	Thread
1BT0202	1/8"	1/8"
1BT0204	1/8"	1/4"
1BT0404	1/4"	1/4"
1BT0406	1/4"	3/8"
1BT0408	1/4"	1/2"
1BT0606	3/8"	3/8"
1BT0608	3/8"	1/2"
1BT0808	1/2"	1/2"
1BT0812	1/2"	3/4"
1BT1212	3/4"	3/4"
1BT1216	3/4"	1"
1BT1220	3/4"	1.1/4"
1BT1616	1"	1"
1BT1620	1"	1.1/4"
1BT1624	1"	1.1/2"
1BT2020	1.1/4"	1.1/4"
1BT2024	1.1/4"	1.1/2"
1BT2032	1.1/4"	2"
1BT2424	1.1/2"	1.1/2"
1BT2432	1.1/2"	2"
1BT3232	2"	2"
1BT4040	2.1/2"	2.1/2"
1BT4848	3"	3"
Tech Sheet 20000		



JIS Male x JIS Male 30° Cone (Metric Threads)

0014	Thread mm
9741-14	14
9741-18	18
9741-22	22
9741-24	24
9741-30	30
9741-33	33
Tech Sheet 20000	



JIS Male x JIS Male 30° Cone (BSPP Threads)

0014	Thread
7801-04-04	1/4"
7801-06-06	3/8"
7801-08-08	1/2"
7801-12-12	3/4"
Tech Sheet 20000	

Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Male Adaptors



NPTF Male x BSPP Male 60° Cone

0014	Thread	Thread
1NB0202	1/8"	1/8"
1NB0204	1/8"	1/4"
1NB0206	1/8"	3/8"
1NB0208	1/8"	1/2"
1NB0402	1/4"	1/8"
1NB0404	1/4"	1/4"
1NB0406	1/4"	3/8"
1NB0408	1/4"	1/2"
1NB0412	1/4"	3/4"
1NB0602	3/8"	1/8"
1NB0604	3/8"	1/4"
1NB0606	3/8"	3/8"
1NB0608	3/8"	1/2"
1NB0610	3/8"	5/8"
1NB0612	3/8"	3/4"
1NB0802	1/2"	1/8"
1NB0804	1/2"	1/4"
1NB0806	1/2"	3/8"
1NB0808	1/2"	1/2"
1NB0810	1/2"	5/8"
1NB0812	1/2"	3/4"
1NB0816	1/2"	1"
1NB1204	3/4"	1/4"
1NB1206	3/4"	3/8"
1NB1208	3/4"	1/2"
1NB1210	3/4"	5/8"
1NB1212	3/4"	3/4"
1NB1216	3/4"	1"
1NB1220	3/4"	1.1/4"
1NB1224	3/4"	1.1/2"
1NB1604	1"	1/4"
1NB1606	1"	3/8"
1NB1608	1"	1/2"
1NB1612	1"	3/4"
1NB1616	1"	1"
1NB1620	1"	1.1/4"
1NB2012	1.1/4"	3/4"
1NB2016	1.1/4"	1"
1NB2020	1.1/4"	1.1/4"
1NB2024	1.1/4"	1.1/2"
1NB2032	1.1/4"	2"
1NB2416	1.1/2"	1"
1NB2420	1.1/2"	1.1/4"
1NB2424	1.1/2"	1.1/2"
1NB2432	1.1/2"	2"
1NB3216	2"	1"
1NB3220	2"	1.1/4"
1NB3224	2"	1.1/2"
1NB3232	2"	2"
1NB3240	2"	2.1/2"
1NB4032	2.1/2"	2"
1NB4040	2.1/2"	2.1/2"
1NB4832	3"	2"
1NB4840	3"	2.1/2"
Tech Sheet 20000		



NPTF Male x NPTF Male

0014	Thread	Thread
1N0202	1/8"	1/8"
1N0204	1/8"	1/4"
1N0208	1/8"	1/2"
1N0404	1/4"	1/4"
1N0406	1/4"	3/8"
1N0408	1/4"	1/2"
1N0412	1/4"	3/4"
1N0606	3/8"	3/8"
1N0608	3/8"	1/2"
1N0808	1/2"	1/2"
1N0812	1/2"	3/4"
1N0816	1/2"	1"
1N0820	1/2"	1.1/4"
1N0824	1/2"	1.1/2"
1N1212	3/4"	3/4"
1N1216	3/4"	1"
1N1220	3/4"	1.1/4"
1N1616	1"	1"
1N1620	1"	1.1/4"
1N2020	1.1/4"	1.1/4"
1N2024	1.1/4"	1.1/2"
1N2032	1.1/4"	2"
1N2432	1.1/2"	2"
1N4040	2.1/2"	2.1/2"
Tech Sheet 20000		



Metric Male x BSPP Male 60° Cone

0014	Thread	Thread
10542	M8 x 1	1/8"
10544	M10 x 1	1/8"
10545	M10 x 1	1/4"
10548	M10 x 1	3/8"
10543	M12 x 1	1/8"
10546	M12 x 1	1/4"
10541	M14 x 1	1/4"
Tech Sheet 20000		



Metric Male x BSPP Male 60° Cone to DIN 3852 Form A

0014	Thread	Thread
60500	M22 x 1.5	1/2"
Tech Sheet 20000		



Metric Male x Metric Male

0014	Thread	Thread
1MP1010	M10 x 1.5	M10 x 1.5
1MP1012	M10 x 1.5	M12 x 1.5
1MP1014	M10 x 1.5	M14 x 1.5
1MP1212	M12 x 1.5	M12 x 1.5
1MP1214	M12 x 1.5	M14 x 1.5
1MP1216	M12 x 1.5	M16 x 1.5
1MP1414	M14 x 1.5	M14 x 1.5
1MP1416	M14 x 1.5	M16 x 1.5
1MP1418	M14 x 1.5	M18 x 1.5
1MP1420	M14 x 1.5	M20 x 1.5
1MP1616	M16 x 1.5	M16 x 1.5
1MP1618	M16 x 1.5	M18 x 1.5
1MP1620	M16 x 1.5	M20 x 1.5
1MP1622	M16 x 1.5	M22 x 1.5
1MP1626	M16 x 1.5	M26 x 1.5
1MP1818	M18 x 1.5	M18 x 1.5
1MP1820	M18 x 1.5	M20 x 1.5
1MP1822	M18 x 1.5	M22 x 1.5
1MP1824	M18 x 1.5	M24 x 1.5
1MP1826	M18 x 1.5	M26 x 1.5
1MP2020	M20 x 1.5	M20 x 1.5
1MP2022	M20 x 1.5	M22 x 1.5
1MP2024	M20 x 1.5	M24 x 1.5
1MP2026	M20 x 1.5	M26 x 1.5
1MP2222	M22 x 1.5	M22 x 1.5
1MP2224	M22 x 1.5	M24 x 1.5
1MP2226	M22 x 1.5	M26 x 1.5
1MP2230	M22 x 1.5	M30 x 1.5
1MP2424	M24 x 1.5	M24 x 1.5
1MP2626	M26 x 1.5	M26 x 1.5
1MP3030	M30 x 1.5	M30 x 1.5
1MP3038	M30 x 1.5	M38 x 1.5
1MP3838	M38 x 1.5	M38 x 1.5
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Male/Male Adaptors



Metric Male x BSPP Male 60° Cone

0014	Thread	Thread
1MBP1004	M10 x 1.5	1/4"
1MBP1202	M12 x 1.5	1/8"
1MBP1204	M12 x 1.5	1/4"
1MBP1206	M12 x 1.5	3/8"
1MBP1208	M12 x 1.5	1/2"
1MBP1402	M14 x 1.5	1/8"
1MBP1404	M14 x 1.5	1/4"
1MBP1406	M14 x 1.5	3/8"
1MBP1408	M14 x 1.5	1/2"
1MBP1410	M14 x 1.5	5/8"
1MBP1604	M16 x 1.5	1/4"
1MBP1606	M16 x 1.5	3/8"
1MBP1608	M16 x 1.5	1/2"
1MBP1610	M16 x 1.5	5/8"
1MBP1612	M16 x 1.5	3/4"
1MBP1804	M18 x 1.5	1/4"
1MBP1806	M18 x 1.5	3/8"
1MBP1808	M18 x 1.5	1/2"
1MBP1810	M18 x 1.5	5/8"
1MBP1812	M18 x 1.5	3/4"
1MBP1816	M18 x 1.5	1"
1MBP2004	M20 x 1.5	1/4"
1MBP2006	M20 x 1.5	3/8"
1MBP2008	M20 x 1.5	1/2"
1MBP2012	M20 x 1.5	3/4"
1MBP2204	M22 x 1.5	1/4"
1MBP2206	M22 x 1.5	3/8"
1MBP2208	M22 x 1.5	1/2"
1MBP2212	M22 x 1.5	3/4"
1MBP2216	M22 x 1.5	1"
1MBP2406	M24 x 1.5	3/8"
1MBP2408	M24 x 1.5	1/2"
1MBP2412	M24 x 1.5	3/4"
1MBP2608	M26 x 1.5	1/2"
1MBP2610	M26 x 1.5	5/8"
1MBP2612	M26 x 1.5	3/4"
1MBP2616	M26 x 1.5	1"
1MBP3012	M30 x 1.5	3/4"
1MBP3016	M30 x 1.5	1"
1MBP3020	M30 x 1.5	1.1/4"
1MBP3616	M36 x 1.5	1"
1MBP3816	M38 x 1.5	1"
1MBP3820	M38 x 1.5	1.1/4"
Tech Sheet 20000		



SAE O-Ring Boss Male x BSPP Male 60° Cone Less O-Ring

0014	Thread	Thread
01329	1/4"	1/8"
01326	1/4"	1/4"
01300	3/8"	1/4"
01323	3/8"	3/8"
01309	7/16"	1/8"
01301	7/16"	1/4"
01303	7/16"	3/8"
01302	7/16"	1/2"
01304	1/2"	1/4"
01305	1/2"	3/8"
01341	1/2"	1/2"
01306	9/16"	1/4"
01307	9/16"	3/8"
01308	9/16"	1/2"
01310	3/4"	1/4"
01311	3/4"	3/8"
01312	3/4"	1/2"
01313	3/4"	5/8"
01314	3/4"	3/4"
01315	5/8"	1/4"
01316	5/8"	3/8"
01344	5/8"	1/2"
01346	7/8"	1/4"
01317	7/8"	3/8"
01318	7/8"	1/2"
01319	7/8"	5/8"
01320	7/8"	3/4"
01335	7/8"	1"
01321	1.1/16"	3/8"
01322	1.1/16"	1/2"
01337	1.1/16"	5/8"
01324	1.1/16"	3/4"
01325	1.1/16"	1"
01348	1.1/16"	1.1/4"
01345	1.3/16"	3/4"
01343	1.5/16"	1/2"
01327	1.5/16"	3/4"
01328	1.5/16"	1"
01338	1.5/16"	1.1/4"
01330	1.5/16"	1.1/2"
01331	1.5/8"	3/4"
01332	1.5/8"	1"
01333	1.5/8"	1.1/4"
01339	1.5/8"	1.1/2"
01342	1.7/8"	1.1/4"
01340	1.7/8"	1.1/2"
Tech Sheet 20000		



NPT Male x SAE Male 45° External Flare

0014	Thread	Thread
01050	1/8"	7/16"
01052	1/4"	7/16"
01054	1/4"	5/8"
01056	3/8"	7/16"
01058	3/8"	5/8"
01057	3/8"	3/4"
01060	1/2"	5/8"
01061	1/2"	3/4"
01062	1/2"	7/8"
01063	1/2"	1.1/16"
01065	3/4"	3/4"
01066	3/4"	7/8"
01064	3/4"	1.5/8"
01067	3/4"	1.1/16"
Tech Sheet 20000		



SAE O-Ring Boss Male x SAE O-Ring Face Seal Male Less O-Rings

0014	Thread	Thread
21300	7/16"	9/16"
21301	7/16"	11/16"
21302	9/16"	11/16"
21303	9/16"	13/16"
21304	3/4"	11/16"
21305	3/4"	13/16"
21307	7/8"	13/16"
21308	7/8"	1"
21310	1.1/16"	1.3/16"
21311	1.1/16"	1.7/16"
21312	1.5/16"	1.3/16"
21313	1.5/16"	1.7/16"
Tech Sheet 20000		

Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Fixed Female Adaptors



BSPP Male 60° Cone x BSPP Fixed Female Extended

0014	Male Thread	Female Thread
4BX02	1/8"	1/8"
4BX0204	1/8"	1/4"
4BX0206	1/8"	3/8"
4BX0208	1/8"	1/2"
4BX0402	1/4"	1/8"
4BX04	1/4"	1/4"
4BX0406	1/4"	3/8"
4BX0408	1/4"	1/2"
4BX0412	1/4"	3/4"
4BX0604	3/8"	1/4"
4BX06	3/8"	3/8"
4BX0608	3/8"	1/2"
4BX0612	3/8"	3/4"
4BX0806	1/2"	3/8"
4BX08	1/2"	1/2"
4BX0812	1/2"	3/4"
4BX0816	1/2"	1"
4BX0820	1/2"	1.1/4"
4BX1208	3/4"	1/2"
4BX12	3/4"	3/4"
4BX1216	3/4"	1"
4BX1220	3/4"	1.1/4"
4BX1224	3/4"	1.1/2"
4BX1612	1"	3/4"
4BX16	1"	1"
4BX1620	1"	1.1/4"
4BX1624	1"	1.1/2"
4BX2020	1.1/4"	1.1/4"
4BX2024	1.1/4"	1.1/2"
4BX2032	1.1/4"	2"
4BX2420	1.1/2"	1.1/4"
4BX24	1.1/2"	1.1/2"
Tech Sheet 20000		



BSPP Male 60° Cone x BSPT Female Extended

0014	Male Thread	Female Thread
16091	1/4"	1/8"
16090	1/4"	1/4"
16092	3/8"	1/4"
16093	3/8"	3/8"
16089	3/8"	1/2"
16094	1/2"	1/2"
16102	3/4"	1/2"
16095	3/4"	3/4"
16103	3/4"	1"
16096	1"	1"
Tech Sheet 20000		



BSPP Male 60° Cone x Metric Female 1.5mm Pitch Extended

0014	Male Thread	Female Thread mm
19803	1/4"	12
19804	1/4"	14
19800	1/2"	16
19801	1/2"	22
19802	3/4"	22
Tech Sheet 20000		



BSPP Male 60° Cone x NPT Female Extended

0014	Male Thread	Female Thread
16060	1/8"	1/8"
16061	1/4"	1/8"
16062	1/4"	1/4"
16073	1/4"	3/8"
16085	1/4"	1/2"
16072	3/8"	1/4"
16063	3/8"	3/8"
16065	1/2"	3/8"
16066	1/2"	1/2"
16082	1/2"	3/4"
16067	3/4"	3/4"
16083	1"	3/4"
16068	1"	1"
16084	1"	1.1/2"
16069	1.1/4"	1.1/4"
16075	1.1/2"	1.1/4"
16070	1.1/2"	1.1/2"
16071	2"	2"
Tech Sheet 20000		



NPT Male x BSPP Female Extended

0014	Male Thread	Female Thread
16170	1/8"	1/8"
16178	1/8"	1/4"
16171	1/4"	1/4"
16173	3/8"	3/8"
16172	1/2"	3/8"
16174	1/2"	1/2"
16175	3/4"	3/4"
16176	1"	1"
16169	1.1/4"	1.1/4"
16366	1.1/2"	1.1/4"
Tech Sheet 20000		



NPT Male x NPT Female Extended

0014	Male Thread	Female Thread
00820	1/8"	1/8"
00821	1/8"	1/4"
00822	1/4"	1/4"
00823	1/4"	3/8"
00843	1/4"	1"
00824	3/8"	3/8"
00842	3/8"	1/2"
00841	3/8"	3/4"
00826	1/2"	1/2"
00850	1/2"	3/4"
00829	3/4"	3/4"
00844	3/4"	1"
00849	3/4"	1.1/4"
00831	1"	1"
00825	1"	1.1/4"
Tech Sheet 20000		

RSB

For **Hydraulic Tube Clamps** see pages **184-200**



FAC Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Bushes

BSPP Male 60° Cone x BSPP Fixed Female Bush



0014	Male Thread	Female Thread
4B0602	3/8"	1/8"
4B0802	1/2"	1/8"
4B0804	1/2"	1/4"
4B1204	3/4"	1/4"
4B1206	3/4"	3/8"
4B1604	1"	1/4"
4B1606	1"	3/8"
4B1608	1"	1/2"
4B2008	1.1/4"	1/2"
4B2012	1.1/4"	3/4"
4B2016	1.1/4"	1"
4B2408	1.1/2"	1/2"
4B2412	1.1/2"	3/4"
4B2416	1.1/2"	1"
4B3216	2"	1"
4B3220	2"	1.1/4"
4B3224	2"	1.1/2"
4B4024	2.1/2"	1.1/2"
4B4032	2.1/2"	2"
4B4832	3"	2"
Tech Sheet 20000		

BSPP Male 60° Cone x NPT Fixed Female Bush



0014	Male Thread	Female Thread
4BN0802	1/2"	1/8"
4BN0804	1/2"	1/4"
4BN1206	3/4"	3/8"
4BN1604	1"	1/4"
4BN1608	1"	1/2"
4BN2016	1.1/4"	1"
4BN2416	1.1/2"	1"
4BN4032	2.1/2"	2"
4BN4832	3"	2"
Tech Sheet 20000		

BSPT Male x BSPP Female Bush



0014	Male Thread	Female Thread
16121	3/8"	1/8"
16122	3/8"	1/4"
16125	1/2"	1/4"
16123	3/4"	1/4"
16124	3/4"	3/8"
16137	3/4"	1/2"
16126	1"	1/4"
16117	1"	3/8"
16127	1"	1/2"
16128	1"	3/4"
16136	1.1/4"	1"
16142	1.1/2"	1/2"
Tech Sheet 20000		

BSPP Male x BSPP Female Bush (Not Coned)



0014	Male Thread	Female Thread
00780	3/8"	1/8"
00781	1/2"	1/8"
00782	1/2"	1/4"
00783	5/8"	1/4"
00784	5/8"	3/8"
00785	3/4"	1/8"
00786	3/4"	1/4"
00787	3/4"	3/8"
00788	1"	1/4"
00789	1"	3/8"
00790	1"	1/2"
00791	1"	5/8"
00792	1.1/4"	1/4"
00793	1.1/4"	3/8"
00794	1.1/4"	1/2"
00795	1.1/4"	3/4"
00796	1.1/4"	1"
00801	1.1/2"	3/4"
00802	1.1/2"	1"
00805	2"	1/2"
00806	2"	5/8"
00807	2"	3/4"
00808	2"	1"
00809	2"	1.1/4"
00810	2"	1.1/2"
Tech Sheet 20000		

BSPT Male x BSPT Female Bush



0014	Male Thread	Female Thread
16180	1/4"	1/8"
16181	3/8"	1/8"
16182	3/8"	1/4"
16183	1/2"	1/4"
16184	1/2"	3/8"
16186	3/4"	3/8"
16187	3/4"	1/2"
16190	1"	1/2"
16191	1"	3/4"
Tech Sheet 20000		

NPT Male x BSPP Female Bush



0014	Male Thread	Female Thread
16350	1/4"	1/8"
16351	3/8"	1/4"
16352	1/2"	1/4"
16354	3/4"	1/4"
16355	3/4"	3/8"
16356	3/4"	1/2"
16359	1"	1/2"
16360	1"	3/4"
16365	2"	1"
Tech Sheet 20000		

BSPP Male 60° Cone x BSPT Fixed Female Bush



0014	Male Thread	Female Thread
16601	1/2"	1/4"
Tech Sheet 20000		

NPT Male x NPT Female Bush



0014	Male Thread	Female Thread
01001	1/4"	1/8"
01002	3/8"	1/8"
01003	3/8"	1/4"
01018	1/2"	1/8"
01004	1/2"	1/4"
01005	1/2"	3/8"
01032	3/4"	1/8"
01006	3/4"	1/4"
01007	3/4"	3/8"
01008	3/4"	1/2"
01022	1"	1/4"
01011	1"	3/8"
01009	1"	1/2"
01010	1"	3/4"
01023	1.1/4"	1/4"
01025	1.1/4"	3/8"
01026	1.1/4"	1/2"
01019	1.1/4"	3/4"
01012	1.1/4"	1"
01024	1.1/2"	1/4"
01027	1.1/2"	3/8"
01028	1.1/2"	1/2"
01013	1.1/2"	3/4"
01015	1.1/2"	1"
01021	1.1/2"	1.1/4"
01031	2"	1/4"
01030	2"	1/2"
01029	2"	3/4"
01014	2"	1"
01017	2"	1.1/4"
01016	2"	1.1/2"
01033	2.1/2"	2"
Tech Sheet 20000		

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER


Gauge Adaptors



BSPP Male 60° Cone x BSPP Fixed Female Gauge

0014	Male Thread	Female Thread
4BG02	1/8"	1/8"
4BG0204	1/8"	1/4"
4BG0206	1/8"	3/8"
4BG0402	1/4"	1/8"
4BG04	1/4"	1/4"
4BG0406	1/4"	3/8"
4BG0408	1/4"	1/2"
4BG0602	3/8"	1/8"
4BG0604	3/8"	1/4"
4BG06	3/8"	3/8"
4BG0608	3/8"	1/2"
4BG0804	1/2"	1/4"
4BG0806	1/2"	3/8"
4BG08	1/2"	1/2"
4BG0812	1/2"	3/4"
4BG0816	1/2"	1"
4BG1208	3/4"	1/2"
4BG1612	1"	3/4"
Tech Sheet 20000		

FT PRO®



For **Push Style Hose System** see pages **37-39**

Female Hose Inserts



Female Swivel Straight BSPP

0014	Thread	To Suit Hose ID
09240	1/4"	1/4"
09241	3/8"	3/8"
09242	1/2"	1/2"
09243	5/8"	5/8"
09244	3/4"	3/4"
09245	1"	1"
Tech Sheet 20000		



Female Fixed Straight NPT

0014	Thread	To Suit Hose ID
16301	3/8"	3/8"
16302	1/2"	1/2"
Tech Sheet 20000		



BSPP Swivel Female 60° Cone x Hose Tail Straight

0014	Thread	To Suit Hose ID
93100	1/4"	1/4"
93101	3/8"	3/8"
93102	1/2"	1/2"
93103	5/8"	5/8"
93104	3/4"	3/4"
93105	1"	1"
93107	1.1/2"	1.1/2"
93108	2"	2"
Tech Sheet 20000		

Male Hose Inserts



Male Straight BSPP 60° Cone

0014	Thread	To Suit Hose ID
09220	1/4"	1/4"
09221	3/8"	3/8"
09222	1/2"	1/2"
09223	3/4"	3/4"
09224	1"	1"
Tech Sheet 20000		



Male Straight BSPT

0014	Thread	To Suit Hose ID
09258	1/8"	1/4"
09250	1/4"	1/4"
09251	3/8"	3/8"
09252	3/8"	1/2"
09253	1/2"	1/2"
09254	3/4"	3/4"
09255	1"	1"
Tech Sheet 20000		



BSPP Male 60° Cone x Hose Tail Straight

0014	Thread	To Suit Hose ID
19920	1/4"	1/4"
19921	3/8"	3/8"
19922	1/2"	1/2"
19923	5/8"	5/8"
19924	3/4"	3/4"
19925	1"	1"
19927	1.1/4"	1.1/4"
Tech Sheet 20000		



BSPP Male 60° Cone x Hose Tail 90° Swept

0014	Thread	To Suit Hose ID
19930	1/4"	1/4"
19931	3/8"	3/8"
19932	1/2"	1/2"
19933	5/8"	5/8"
19934	3/4"	3/4"
19935	1"	1"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Male/Female Swivel Adaptors



BSPP Male 60° Cone x BSPP Swivel Female 60° Cone

0014	Male Thread	Female Thread
2B0202	1/8"	1/8"
2B0204	1/8"	1/4"
2B0206	1/8"	3/8"
2B0402	1/4"	1/8"
2B0404	1/4"	1/4"
2B0406	1/4"	3/8"
2B0408	1/4"	1/2"
2B0412	1/4"	3/4"
2B0602	3/8"	1/8"
2B0604	3/8"	1/4"
2B0606	3/8"	3/8"
2B0608	3/8"	1/2"
2B0610	3/8"	5/8"
2B0612	3/8"	3/4"
2B0616	3/8"	1"
2B0804	1/2"	1/4"
2B0806	1/2"	3/8"
2B0808	1/2"	1/2"
2B0810	1/2"	5/8"
2B0812	1/2"	3/4"
2B0816	1/2"	1"
2B1004	5/8"	1/4"
2B1006	5/8"	3/8"
2B1008	5/8"	1/2"
2B1010	5/8"	5/8"
2B1012	5/8"	3/4"
2B1204	3/4"	1/4"
2B1206	3/4"	3/8"
2B1208	3/4"	1/2"
2B1210	3/4"	5/8"
2B1212	3/4"	3/4"
2B1216	3/4"	1"
2B1220	3/4"	1.1/4"
2B1224	3/4"	1.1/2"
2B1606	1"	3/8"
2B1608	1"	1/2"
2B1612	1"	3/4"
2B1616	1"	1"
2B1620	1"	1.1/4"
2B1624	1"	1.1/2"
2B1632	1"	2"
2B2008	1.1/4"	1/2"
2B2012	1.1/4"	3/4"
2B2016	1.1/4"	1"
2B2020	1.1/4"	1.1/4"
2B2024	1.1/4"	1.1/2"
2B2416	1.1/2"	1"
2B2420	1.1/2"	1.1/4"
2B2424	1.1/2"	1.1/2"
2B2432	1.1/2"	2"
2B3224	2"	1.1/2"
2B3232	2"	2"
Tech Sheet 20000		



BSPP Male 60° Cone x SAE O-Ring Swivel Female

0014	Male Thread	Female Thread
96400	1/4"	9/16"
96410	1/4"	11/16"
96420	3/8"	9/16"
96430	3/8"	11/16"
96440	3/8"	13/16"
96450	1/2"	13/16"
96460	1/2"	1"
96470	3/4"	1.3/16"
96480	3/4"	1.7/16"
96490	1"	1.7/16"
96500	1.1/4"	1.11/16"
Tech Sheet 20000		



BSPP Male 60° Cone x Metric Swivel Female

0014	Male Thread	Female Thread
2BM0412	1/4"	M12 x 1.5
2BM0414	1/4"	M14 x 1.5
2BM0416	1/4"	M16 x 1.5
2BM0418	1/4"	M18 x 1.5
2BM0614	3/8"	M14 x 1.5
2BM0616	3/8"	M16 x 1.5
2BM0618	3/8"	M18 x 1.5
2BM0620	3/8"	M20 x 1.5
2BM0622	3/8"	M22 x 1.5
2BM0816	1/2"	M16 x 1.5
2BM0818	1/2"	M18 x 1.5
2BM0820	1/2"	M20 x 1.5
2BM0822	1/2"	M22x 1.5
2BM0824	1/2"	M24 x 1.5
2BM0826	1/2"	M26 x 1.5
2BM1022	5/8"	M22 x 1.5
2BM1222	3/4"	M22 x 1.5
Tech Sheet 20000		



BSPP Male 60° Cone DIN 3852 Form A x BSPP Swivel Female 60° Cone

0014	Male Thread	Female Thread
61400	1/8"	1/8"
61402	1/8"	3/8"
61403	1/4"	1/8"
61404	1/4"	1/4"
61405	1/4"	3/8"
61406	1/4"	1/2"
61410	3/8"	3/8"
61411	3/8"	1/2"
61417	1/2"	1/2"
61419	1/2"	3/4"
61420	1/2"	1"
61429	3/4"	1/2"
61431	3/4"	3/4"
61432	3/4"	1"
61433	3/4"	1.1/4"
61434	1"	1/2"
61436	1"	3/4"
61437	1"	1"
61438	1"	1.1/4"
61439	1"	1.1/2"
61443	1.1/4"	1.1/4"
61444	1.1/4"	1.1/2"
61445	1.1/4"	2"
61448	1.1/2"	1.1/2"
61449	1.1/2"	2"
Tech Sheet 20000		



BSPP Male 60° Cone x NPSM Swivel Female

0014	Male Thread	Female Thread
31427	1/4"	1/4"
31429	1/4"	3/8"
31433	3/8"	1/4"
31434	3/8"	3/8"
Tech Sheet 20000		



BSPT Male x BSPP Swivel Female 60° Cone

0014	Male Thread	Female Thread
01875	1/8"	1/8"
01876	1/4"	1/4"
01877	3/8"	3/8"
01885	3/8"	1/2"
01884	1/2"	3/8"
01878	1/2"	1/2"
01879	5/8"	5/8"
01880	3/4"	1/2"
01881	3/4"	3/4"
01887	3/4"	1"
01882	1"	3/4"
01883	1"	1"
01889	1.1/4"	1.1/4"
01888	1.1/2"	1.1/2"
01886	2"	2"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Female Swivel Adaptors



Metric Male x BSPP Swivel Female 60˚ Cone

0014	Male Thread	Female Thread
2MB1204	M12 x 1.5	1/4"
2MB1404	M14 x 1.5	1/4"
2MB1406	M14 x 1.5	3/8"
2MB1604	M16 x 1.5	1/4"
2MB1606	M16 x 1.5	3/8"
2MB1608	M16 x 1.5	1/2"
2MB1612	M16 x 1.5	3/4"
2MB1806	M18 x 1.5	3/8"
2MB1808	M18 x 1.5	1/2"
2MB2006	M20 x 1.5	3/8"
2MB2008	M20 x 1.5	1/2"
2MB2012	M20 x 1.5	3/4"
2MB2208	M22 x 1.5	1/2"
2MB2212	M22 x 1.5	3/4"
2MB2606	M26 x 1.5	3/8"
2MB3008	M30 x 1.5	1/2"

Tech Sheet 20000



Metric Male x Metric Swivel Female

0014	Male Thread	Female Thread
2M1414	M14 x 1.5	M14 x 1.5
2M1616	M16 x 1.5	M16 x 1.5
2M1618	M16 x 1.5	M18 x 1.5
2M1818	M18 x 1.5	M18 x 1.5
2M2020	M20 x 1.5	M20 x 1.5
2M2022	M20 x 1.5	M22 x 1.5
2M2218	M22 x 1.5	M18 x 1.5
2M2220	M22 x 1.5	M20 x 1.5
2M2222	M22 x 1.5	M22 x 1.5

Tech Sheet 20000



NPT Male x BSPP Swivel Female 60° Cone

0014	Male Thread	Female Thread
11875	1/8"	1/8"
11876	1/4"	1/4"
11885	3/8"	1/4"
11877	3/8"	3/8"
11884	3/8"	1/2"
11874	1/2"	3/8"
11878	1/2"	1/2"
11880	3/4"	1/2"
11881	3/4"	3/4"
11882	1"	3/4"
11883	1"	1"

Tech Sheet 20000

Swivel Females



BSPP Swivel Female x BSPP Swivel Female 60° Cone

0014	Thread	Thread
3B0202	1/8"	1/8"
3B0204	1/8"	1/4"
3B0206	1/8"	3/8"
3B0404	1/4"	1/4"
3B0406	1/4"	3/8"
3B0606	3/8"	3/8"
3B0612	3/8"	3/4"
3B0616	3/8"	1"
3B0804	1/2"	1/4"
3B0806	1/2"	3/8"
3B0808	1/2"	1/2"
3B0810	1/2"	5/8"
3B0812	1/2"	3/4"
3B1006	5/8"	3/8"
3B1010	5/8"	5/8"
3B1210	3/4"	5/8"
3B1212	3/4"	3/4"
3B1216	3/4"	1"
3B1608	1"	1/2"
3B1616	1"	1"
3B1620	1"	1.1/4"
3B1624	1"	1.1/2"
3B2012	1.1/4"	3/4"
3B2020	1.1/4"	1.1/4"
3B2424	1.1/2"	1.1/2"
3B2432	1.1/2"	2"
3B3232	2"	2"

Tech Sheet 20000



BSPP Swivel Female 60° Cone x Metric Swivel Female

0014	Thread	Thread
3BM0412	1/4"	M12 x 1.5
3BM0414	1/4"	M14 x 1.5
3BM0612	3/8"	M12 x 1.5
3BM0614	3/8"	M14 x 1.5
3BM0616	3/8"	M16 x 1.5
3BM0618	3/8"	M18 x 1.5
3BM0620	3/8"	M20 x 1.5
3BM0622	3/8"	M22 x 1.5
3BM0816	1/2"	M16 x 1.5
3BM0818	1/2"	M18 x 1.5
3BM0822	1/2"	M22 x 1.5

Tech Sheet 20000




Metric Swivel Female x Metric Swivel Female

0014	Thread	Thread
01775	M12 x 1.5	M12 x 1.5
01785	M12 x 1.5	M14 x 1.5
01776	M14 x 1.5	M14 x 1.5
01777	M16 x 1.5	M16 x 1.5
01782	M16 x 1.5	M18 x 1.5
01778	M18 x 1.5	M18 x 1.5
01783	M18 x 1.5	M20 x 1.5
01779	M18 x 1.5	M22 x 1.5
01780	M20 x 1.5	M20 x 1.5
01784	M20 x 1.5	M22 x 1.5
01781	M22 x 1.5	M22 x 1.5

Tech Sheet 20000

Hexagon Female Sockets



BSPP Fixed Female x BSPP Fixed Female

0014	Thread
7B02	1/8"
7B04	1/4"
7B06	3/8"
7B08	1/2"
7B10	5/8"
7B12	3/4"
7B16	1"
7B20	1.1/4"
7B24	1.1/2"
7B32	2"

Tech Sheet 20000



BSPP Fixed Female x BSPP Fixed Female Reducing

0014	Thread	Thread
7B0204	1/8"	1/4"
7B0406	1/4"	3/8"
7B0408	1/4"	1/2"
7B0608	3/8"	1/2"
7B0812	1/2"	3/4"
7B0810	1/2"	5/8"
7B1216	3/4"	1"

Tech Sheet 20000



NPT Fixed Female x NPT Fixed Female

0014	Thread
7N02	1/8"
7N04	1/4"
7N06	3/8"
7N08	1/2"
7N12	3/4"
7N16	1"
7N24	1.1/2"

Tech Sheet 20000

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

90º Elbows



BSPP Male x BSPP Male 90° Swept Elbow 60° Cone

0014	Thread
EBM04	1/4"
EBM06	3/8"
EBM08	1/2"
EBM10	5/8"
EBM12	3/4"
EBM16	1"
EBM32	2"

Tech Sheet 20000



BSPP Male 60° Cone x BSPP Male 90° Positional Forged Elbow

0014	Thread
03051FDPOS	1/4"
03053FDPOS	3/8"
03054FDPOS	1/2"
03056FDPOS	3/4"
03057FDPOS	1"
03058FDPOS	1.1/4"

Tech Sheet 20000



BSPP Male x BSPP Swivel Female 90° Swept Elbow 60° Cone

0014	Thread
EBMF04	1/4"
EBMF06	3/8"
EBMF08	1/2"
EBMF10	5/8"
EBMF12	3/4"
EBMF16	1"
EBMF20	1.1/4"
EBMF24	1.1/2"
EBMF32	2"

Tech Sheet 20000



BSPP Swivel Female x BSPP Swivel Female 90° Swept Elbow 60° Cone

0014	Thread
EBF04	1/4"
EBF06	3/8"
EBF08	1/2"
EBF10	5/8"
EBF12	3/4"
EBF16	1"
EBF20	1.1/4"
EBF24	1.1/2"

Tech Sheet 20000



BSPP Swivel Female 60° Cone x Hose Tail 90° Swept Elbow

0014	Thread	To Suit Hose ID
93000	1/4"	1/4"
93001	3/8"	3/8"
93002	1/2"	1/2"
93003	5/8"	5/8"
93004	3/4"	3/4"
93005	1"	1"
93006	1.1/4"	1.1/4"

Tech Sheet 20000



Female Elbow 90° BSPP 60° Cone

0014	Thread	To Suit Hose ID
09280	1/4"	1/4"
09281	3/8"	3/8"
09282	1/2"	1/2"
09283	5/8"	5/8"
09284	3/4"	3/4"
09285	1"	1"

Tech Sheet 20000



BSPP Swivel Female 60° Cone x Hose Tail 90° Compact

0014	Thread	To Suit Hose ID
80001	1/4"	1/4"
80002	3/8"	3/8"
80008	1/2"	3/8"
80003	1/2"	1/2"
80004	5/8"	5/8"
80005	3/4"	3/4"
80006	1"	1"

Tech Sheet 20000

90º Compact Elbows



BSPP Male x BSPP Male 90° Compact Elbow 60° Cone

0014	Thread	Thread
XMB0404	1/4"	1/4"
XMB0406	1/4"	3/8"
XMB0606	3/8"	3/8"
XMB0608	3/8"	1/2"
XMB0808	1/2"	1/2"
XMB0812	1/2"	3/4"
XMB1212	3/4"	3/4"
XMB1616	1"	1"
XMB3232	2"	2"

Tech Sheet 20000



BSPP Male x BSPP Male 90° Compact Elbow for Bonded Seal 60° Cone

0014	Thread	Thread
XMBS0202	1/8"	1/8"
XMBS0402	1/4"	1/8"
XMBS0404	1/4"	1/4"
XMBS0606	3/8"	3/8"
XMBS0808	1/2"	1/2"
XMBS1212	3/4"	3/4"
XMBS1612	1"	3/4"
XMBS1616	1"	1"
XMBS2020	1.1/4"	1.1/4"

Tech Sheet 20000



BSPP Male 60° Cone x BSPT Male 90° Compact Elbow

0014	Thread	Thread
XMBP02T02	1/8"	1/8"
XMBP04T02	1/4"	1/8"
XMBP04T04	1/4"	1/4"
XMBP06T06	3/8"	3/8"
XMBP08T06	1/2"	3/8"
XMBP08T08	1/2"	1/2"
XMBP12T12	3/4"	3/4"
XMBP16T16	1"	1"

Tech Sheet 20000

Pressure ratings are not applicable to swept elbows or push-in fittings

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

90º Compact Elbows



BSPP Male 60°Cone x NPT Male 90° Compact Elbow

0014	Thread	Thread
XMB04N04	1/4"	1/4"
XMB06N06	3/8"	3/8"
XMB08N08	1/2"	1/2"
Tech Sheet 20000		



BSPP Male for Bonded Seal x BSPP Swivel Female 90° Compact Elbow 60° Cone

0014	Male Thread	Female Thread
XBMBF0202	1/8"	1/8"
XBMBF0404	1/4"	1/4"
XBMBF0606	3/8"	3/8"
XBMBF0604	3/8"	1/4"
XBMBF0806	1/2"	3/8"
XBMBF0808	1/2"	1/2"
XBMBF0812	1/2"	3/4"
XBMBF1010	5/8"	5/8"
XBMBF1212	3/4"	3/4"
XBMBF1616	1"	1"
XBMBF2020	1.1/4"	1.1/4"
XBMBF2424	1.1/2"	1.1/2"
XBMBF3232	2"	2"
Tech Sheet 20000		



BSPP Male for Cone Seal x BSPP Swivel Female 90° Compact Elbow 60° Cone

0014	Male Thread	Female Thread
XBMF0402	1/4"	1/8"
XBMF0404	1/4"	1/4"
XBMF0406	1/4"	3/8"
XBMF0604	3/8"	1/4"
XBMF0606	3/8"	3/8"
XBMF0608	3/8"	1/2"
XBMF0612	3/8"	3/4"
XBMF0806	1/2"	3/8"
XBMF0808	1/2"	1/2"
XBMF0812	1/2"	3/4"
XBMF0816	1/2"	1"
XBMF1212	3/4"	3/4"
XBMF1216	3/4"	1"
XBMF1612	1"	3/4"
XBMF1616	1"	1"
XBMF2424	1.1/2"	1.1/2"
XBMF3232	2"	2"
Tech Sheet 20000		



BSPP Female x BSPP Female 90° Compact Elbow

0014	Thread
15026	1/4"
15027	3/8"
15028	1/2"
15030	3/4"
15031	1"
15032	1.1/4"
Tech Sheet 20000	



BSPP Swivel Female x BSPP Swivel Female 90° Compact Elbow 60° Cone

0014	Thread	Thread
XBF0202	1/8"	1/8"
XBF0204	1/8"	1/4"
XBF0404	1/4"	1/4"
XBF0406	1/4"	3/8"
XBF0408	1/4"	1/2"
XBF0606	3/8"	3/8"
XBF0608	3/8"	1/2"
XBF0808	1/2"	1/2"
XBF1010	5/8"	5/8"
XBF1212	3/4"	3/4"
XBF1216	3/4"	1"
XBF1616	1"	1"
XBF2020	1.1/4"	1.1/4"
XBF2424	1.1/2"	1.1/2"
XBF3232	2"	2"
Tech Sheet 20000		



BSPP Swivel Female x BSPP Swivel Female 90° Forged Compact Elbow 60° Cone

0014	Thread
05026FD	1/4"
05027FD	3/8"
05028FD	1/2"
05030FD	3/4"
05031FD	1"
Tech Sheet 20000	



BSPP Male x BSPP Swivel Female 90° Forged Compact Elbow 60° Cone

0014	Thread
05000FD	1/4"
05001FD	3/8"
05002FD	1/2"
05004FD	3/4"
05005FD	1"
05018FD	1.1/4"
05007FD	1.1/2"
Tech Sheet 20000	



BSPT Male x BSPT Male 90° Compact Elbow

0014	Thread
83000	1/4"
83001	3/8"
83002	1/2"
83003	3/4"
83004	1"
83005	1.1/4"
Tech Sheet 20000	



BSPT Male x BSPP Swivel Female 90° Compact Elbow 60° Cone

0014	Male Thread	Female Thread
09410	1/8"	1/8"
09405	1/4"	1/4"
09406	3/8"	3/8"
09407	1/2"	1/2"
09411	3/4"	1/2"
09408	3/4"	3/4"
09409	1"	1"
09412	1.1/2"	1.1/2"
Tech Sheet 20000		



NPT Male x BSPP Swivel Female 90° Compact Elbow 60° Cone

0014	Male Thread	Female Thread
09397	1/8"	1/8"
09400	1/4"	1/4"
09401	3/8"	3/8"
09402	1/2"	1/2"
09403	3/4"	3/4"
09404	1"	1"
09398	1.1/4"	1.1/4"
09399	1.1/2"	1.1/2"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

90º Compact Elbows

NPT Male x NPT Male 90° Compact Elbow



0014	Thread	Thread
XMN04	1/4"	1/4"
XMN06	3/8"	3/8"
XMN08	1/2"	1/2"
XMN12	3/4"	3/4"
XMN16	1"	1"
XMN20	1.1/4"	1.1/4"
XMN24	1.1/2"	1.1/2"
XMN32	2"	2"
Tech Sheet 20000		

NPT Male x NPT Fixed Female 90° Compact Elbow



0014	Male Thread	Female Thread
XNMF0202	1/8"	1/8"
XNMF0404	1/4"	1/4"
XNMF0604	3/8"	1/4"
XNMF0606	3/8"	3/8"
XNMF0806	1/2"	3/8"
XNMF0808	1/2"	1/2"
XNMF1212	3/4"	3/4"
XNMF1616	1"	1"
XNMF2020	1.1/4"	1.1/4"
XNMF2424	1.1/2"	1.1/2"
Tech Sheet 20000		

NPT Fixed Female x NPT Fixed Female 90° Compact Elbow



0014	Thread	Thread
XFN0202	1/8"	1/8"
XFN0404	1/4"	1/4"
XFN0606	3/8"	3/8"
XFN0608	3/8"	1/2"
XFN0808	1/2"	1/2"
XFN1212	3/4"	3/4"
XFN1616	1"	1"
XFN2020	1.1/4"	1.1/4"
XFN2424	1.1/2"	1.1/2"
XFN3232	2"	2"
Tech Sheet 20000		

45º Elbows

BSPP Male x BSPP Male 45° Swept Elbow 60° Cone



0014	Thread
SEBM04	1/4"
SEBM06	3/8"
SEBM08	1/2"
SEBM10	5/8"
SEBM24	1.1/2"
Tech Sheet 20000	

BSPP Male x BSPP Swivel Female 45° Swept Elbow 60° Cone



0014	Thread
SEBMF04	1/4"
SEBMF06	3/8"
SEBMF08	1/2"
SEBMF10	5/8"
SEBMF12	3/4"
SEBMF16	1"
SEBMF20	1.1/4"
SEBMF24	1.1/2"
SEBMF32	2"
Tech Sheet 20000	

BSPP Swivel Female x Hose Tail 45° Swept 60° Cone



0014	Thread	To Suit Hose ID
94505	1"	1"
Tech Sheet 20000		

BSPP Swivel Female x BSPP Swivel Female 45° Swept Elbow 60° Cone



0014	Thread
SEBF04	1/4"
SEBF06	3/8"
SEBF08	1/2"
SEBF10	5/8"
SEBF12	3/4"
SEBF16	1"
SEBF20	1.1/4"
SEBF24	1.1/2"
SEBF32	2"
Tech Sheet 20000	

BSPP Male x BSPP Male 45° Positional Forged Elbow



0014	Thread
03051FDPOS-45	1/4"
03053FDPOS-45	3/8"
03054FDPOS-45	1/2"
03056FDPOS-45	3/4"
03057FDPOS-45	1"
Tech Sheet 20000	

Female Elbow 45° BSPP 60° Cone



0014	Thread	To Suit Hose ID
19280	1/4"	1/4"
19281	3/8"	3/8"
19282	1/2"	1/2"
19283	5/8"	5/8"
19284	3/4"	3/4"
19285	1"	1"
Tech Sheet 20000		

45º Compact Elbows



BSPP Male x BSPP Swivel Female 45° Forged Compact Elbow 60° Cone

0014	Thread
05000/45FD	1/4"
05001/45FD	3/8"
05002/45FD	1/2"
05004/45FD	3/4"
05005/45FD	1"
Tech Sheet 20000	

Pressure ratings are not applicable to swept elbows or push-in fittings

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Tees



BSPP Male x BSPP Male x BSPP Swivel Female Branch Tee 60° Cone

0014	Thread
ZMMFB02	1/8"
ZMMFB04	1/4"
ZMMFB06	3/8"
ZMMFB08	1/2"
ZMMFB12	3/4"
ZMMFB16	1"
ZMMFB20	1.1/4"
Tech Sheet 20000	



BSPP Male x BSPP Swivel Female x BSPP Male Branch Tee 60° Cone

0014	Thread
ZMFMB02	1/8"
ZMFMB04	1/4"
ZMFMB06	3/8"
ZMFMB08	1/2"
ZMFMB10	5/8"
ZMFMB12	3/4"
ZMFMB16	1"
ZMFMB20	1.1/4"
Tech Sheet 20000	



BSPP Male x BSPP Swivel Female x BSPP Swivel Female Branch Tee 60° Cone

0014	Thread
ZMFFB02	1/8"
ZMFFB04	1/4"
ZMFFB06	3/8"
ZMFFB08	1/2"
ZMFFB10	5/8"
ZMFFB12	3/4"
ZMFFB16	1"
ZMFFB20	1.1/4"
Tech Sheet 20000	



BSPP Male x BSPP Swivel Female x BSPP Male Branch Tee Reducing on Branch 60° Cone

0014	Thread A	Thread B	Thread C
02035	3/8"	3/8"	1/4"
02032	1/2"	1/2"	1/4"
02031	1/2"	1/2"	3/8"
02022	3/4"	3/4"	1/4"
02039	3/4"	3/4"	3/8"
02037	3/4"	3/4"	1/2"
02023	1"	1"	1/4"
02018	1"	1"	3/4"
Tech Sheet 20000			



BSPP Male x BSPP Swivel Female x BSPP Male Branch Tee Reducing on Run 60° Cone

0014	Thread A	Thread B	Thread C
02036	3/8	1/2"	1/2"
Tech Sheet 20000			



BSPP Male x BSPP Swivel Female x BSPP Male Branch Tee Enlarging on Branch 60° Cone

0014	Thread A	Thread B	Thread C
02017	3/8"	3/8"	1/2"
Tech Sheet 20000			



BSPP Swivel Female x BSPP Swivel Female x BSPP Male Branch Tee 60° Cone

0014	Thread
ZFFMB04	1/4"
ZFFMB06	3/8"
ZFFMB08	1/2"
ZFFMB10	5/8"
ZFFMB12	3/4"
ZFFMB16	1"
ZFFMB20	1.1/4"
Tech Sheet 20000	



NPT Male x NPT Female x NPT Male Branch Tee

0014	Thread
08010	1/4"
08011	3/8"
08012	1/2"
08013	3/4"
08014	1"
08015	1.1/4"
08016	1.1/2"
Tech Sheet 20000	



NPT Male x NPT Female x NPT Female Branch Tee

0014	Thread
07059	1/8"
07060	1/4"
07061	3/8"
07062	1/2"
07063	3/4"
07064	1"
07065	1.1/4"
07066	1.1/2"
Tech Sheet 20000	



NPT Female x NPT Female x NPT Male Branch Tee


0014	Thread
07080	1/4"
07081	3/8"
07082	1/2"
07083	3/4"
07084	1"
07085	1.1/4"
07086	1.1/2"
Tech Sheet 20000	

Fluid-Air Components Ltd

HYDRAULIC ADAPTORS


BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Tees



BSPP Male x BSPP Male x BSPP Swivel Female Branch Unequal Tee 60° Cone

0014	Thread A	Thread B	Thread C
01998	3/8"	1/2"	1/2"
02014	1/4"	1/2"	1/2"
01999	1/2"	3/4"	3/4"
02013	1/2"	3/4"	1"
Tech Sheet 20000			



BSPP Male Tee 60° Cone Seating Enlarging on Branch

0014	Thread A	Thread B
01913	3/8"	1/2"
Tech Sheet 20000		



NPT Male Tee

0014	Thread
ZMN02	1/8"
ZMN04	1/4"
ZMN06	3/8"
ZMN08	1/2"
Tech Sheet 20000	



BSPP Swivel Female Tee 60° Cone

0014	Thread
ZFB02	1/8"
ZFB04	1/4"
ZFB06	3/8"
ZFB08	1/2"
ZFB10	5/8"
ZFB12	3/4"
ZFB16	1"
ZFB20	1.1/4"
ZFB24	1.1/2"
ZFB32	2"
Tech Sheet 20000	




BSPP Female Tee

0014	Thread
11975	1/8"
11976	1/4"
11977	3/8"
11978	1/2"
11979	5/8"
11980	3/4"
11981	1"
11982	1.1/4"
11985	1.1/2"
11984	2"
Tech Sheet 20000	



NPTF Female Tee

0014	Thread
07000	1/8"
07001	1/4"
07002	3/8"
07003	1/2"
07004	3/4"
07005	1"
07006	1.1/4"
07007	1.1/2"
07008	2"
Tech Sheet 20000	



BSPP Male Tee Reducing on Branch 60° Cone

0014	Thread A	Thread B	Thread C
RZMB0402BS	1/4"	1/4"	1/8"
RZMB0604BS	3/8"	3/8"	1/4"
RZMB0804BS	1/2"	1/2"	1/4"
RZMB1008BS	5/8"	5/8"	1/2"
RZMB1204BS	3/4"	3/4"	1/4"
RZMB1208BS	3/4"	3/4"	1/2"
RZMB1612BS	1"	1"	3/4"
RZMB2012BS	1.1/4"	1.1/4"	3/4"
RZMB2016BS	1.1/4"	1.1/4"	1"
Tech Sheet 20000			



BSPP Male Tee for Bonded Seal 60° Cone

0014	Thread
ZMB02BS	1/8"
ZMB04BS	1/4"
ZMB06BS	3/8"
ZMB08BS	1/2"
ZMB10BS	5/8"
ZMB12BS	3/4"
ZMB16BS	1"
ZMB24BS	1.1/4"
Tech Sheet 20000	



BSPP Male Tee 60° Cone Seating

0014	Thread
ZMB04	1/4"
ZMB06	3/8"
ZMB08	1/2"
ZMB12	3/4"
ZMB16	1"
ZMB24	1.1/2"
ZMB32	2"
Tech Sheet 20000	

Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Bulkheads



BSPP Male x BSPP Male Bulkhead complete with Locknut 60° Cone

0014	Thread A	Thread B
09500	1/8"	1/8"
09501	1/4"	1/4"
09512	1/4"	3/8"
09513	3/8"	1/4"
09502	3/8"	3/8"
09505	3/8"	1/2"
09511	1/2"	3/8"
09503	1/2"	1/2"
09514	1/2"	3/4"
09504	5/8"	5/8"
09515	3/4"	1/2"
09506	3/4"	3/4"
09507	1"	1"
09508	1.1/4"	1.1/4"
09521	1.1/2"	1"
09509	1.1/2"	1.1/2"
09510	2"	2"
09516	2.1/2"	2.1/2"
09517	3"	3"
Tech Sheet 20000		



BSPP Male x BSPP Male Extended Bulkhead 60° Cone complete with Locknut

0014	Thread A	Thread B
8BPX0404	1/4"	1/4"
8BPX0606	3/8"	3/8"
8BPX0608	3/8"	1/2"
8BPX0806	1/2"	3/8"
8BPX0808	1/2"	1/2"
8BPX1010	5/8"	5/8"
8BPX1208	3/4"	1/2"
8BPX1212	3/4"	3/4"
8BPX1616	1"	1"
Tech Sheet 20000		



For **Hydraulic Seals** see pages **109-112**



BSPP Male x BSPP Male Bulkhead 60° Cone No Locknut

0014	Thread A	Thread B
8BP0202	1/8"	1/8"
8BP0404	1/4"	1/4"
8BP0606	3/8"	3/8"
8BP0808	1/2"	1/2"
8BP1010	5/8"	5/8"
8BP1212	3/4"	3/4"
8BP1616	1"	1"
8BP2020	1.1/4"	1.1/4"
8BP2424	1.1/2"	1.1/2"
8BP3232	2"	2"
8BP0406	1/4"	3/8"
8BP0604	3/8"	1/4"
8BP0608	3/8"	1/2"
8BP0806	1/2"	3/8"
8BP0812	1/2"	3/4"
8BP1208	3/4"	1/2"
Tech Sheet 20000		



Metric Male x Metric Male Bulkhead No Locknut

0014	Thread	Thread
8MP1212	M12 x 1.5	M12 x 1.5
8MP1414	M14 x 1.5	M14 x 1.5
8MP1616	M16 x 1.5	M16 x 1.5
8MP1818	M18 x 1.5	M18 x 1.5
8MP2020	M20 x 1.5	M20 x 1.5
8MP2222	M22 x 1.5	M22 x 1.5
8MP2424	M24 x 1.5	M24 x 1.5
Tech Sheet 20000		



Metric Male x Metric Male Bulkhead complete with Locknut

0014	Thread
09550	M12 x 1.5
09551	M14 x 1.5
09552	M16 x 1.5
09553	M18 x 1.5
09554	M20 x 1.5
09555	M22 x 1.5
09556	M24 x 1.5
Tech Sheet 20000	

Plugs



BSPP Solid Plug

0014	Thread
6BS02	1/8"
6BS04	1/4"
6BS06	3/8"
6BS08	1/2"
6BS10	5/8"
6BS12	3/4"
6BS16	1"
6BS20	1.1/4"
6BS24	1.1/2"
6BS32	2"
Tech Sheet 20000	



BSPP 60° Coned Plug

0014	Thread
6BC02	1/8"
6BC04	1/4"
6BC06	3/8"
6BC08	1/2"
6BC10	5/8"
6BC12	3/4"
6BC16	1"
6BC20	1.1/4"
6BC24	1.1/2"
6BC32	2"
6BC40	2.1/2"
Tech Sheet 20000	



BSPP 60° Coned Plug to DIN 3852 Form A

0014	Thread
69001	1/4"
69002	3/8"
69003	1/2"
69005	3/4"
69006	1"
69009	2"
Tech Sheet 20000	

FAC Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Plugs



BSPP Socket Headed Plug for Bonded Seal

0014	Thread
09025-02-SPG	1/8"
09026-04-SPG	1/4"
09027-06-SPG	3/8"
09028-08-SPG	1/2"
09030-12-SPG	3/4"
Tech Sheet 20000	



BSPP Socket Headed Plug with 3869 Seal

0014	Thread
3869-02-SPG	1/8"
3869-04-SPG	1/4"
3869-06-SPG	3/8"
3869-08-SPG	1/2"
3869-12-SPG	3/4"
Tech Sheet 20000	



BSPT Solid Plug

0014	Thread
6BT02	1/8"
6BT04	1/4"
6BT06	3/8"
6BT08	1/2"
6BT10	5/8"
6BT12	3/4"
6BT16	1"
6BT24	1.1/2"
6BT32	2"
Tech Sheet 20000	



Metric Solid Plug 1mm Pitch

0014	Thread
09169	M8 x 1
09179	M10 x 1
09168	M12 x 1
Tech Sheet 20000	



Metric Solid Plug 1.5mm Pitch

0014	Thread
6M10	M10 x 1.5
6M12	M12 x 1.5
6M14	M14 x 1.5
6M16	M16 x 1.5
6M18	M18 x 1.5
6M20	M20 x 1.5
6M22	M22 x 1.5
6M24	M24 x 1.5
6M26	M26 x 1.5
Tech Sheet 20000	



Metric Socket Headed Plug for Bonded Seal

0014	Thread
09179-M10-SPG	M10 x 1
09173-M14-SPG	M14 x 1.5
09170-M16-SPG	M16 x 1.5
09176-M22-SPG	M22 x 1.5
Tech Sheet 20000	



Metric Socket Headed Plug with 3869 Seal

0014	Thread
3869-M10-SPG	M10 x 1
3869-M14-SPG	M14 x 1.5
3869-M16-SPG	M16 x 1.5
3869-M22-SPG	M22 x 1.5
3869-M26-SPG	M26 x 1.5
Tech Sheet 20000	



NPT Socket Headed Plug

0014	Thread
09100/HD	1/8"
09101/HD	1/4"
09102/HD	3/8"
09103/HD	1/2"
09105/HD	3/4"
09106/HD	1"
Tech Sheet 20000	



NPT Solid Plug

0014	Thread
6N02	1/8"
6N04	1/4"
6N06	3/8"
6N08	1/2"
6N12	3/4"
6N16	1"
6N20	1.1/4"
6N24	1.1/2"
6N32	2"
6N40	2.1/2"
6N48	3"
Tech Sheet 20000	



SAE Boss Socket Head Male Plug with O-Ring

0014	Thread
7238-04	7/16"
7238-05	1/2"
7238-06	9/16"
7238-08	3/4"
7238-10	7/8"
7238-12	1.1/16"
7238-14	1.3/16"
7238-16	1.5/16"
Tech Sheet 20000	

Fluid-Air Components Ltd

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Plugs



SAE O-Ring Boss Male Solid Plug with O-Ring

0014	Thread
19162	5/16"
19150	7/16"
19151	1/2"
19152	9/16"
19153	3/4"
19154	7/8"
19155	1.1/16"
19156	1.3/16"
19157	1.5/16"
19158	1.5/8"
19159	1.7/8"
19160	2.1/2"
Tech Sheet 20000	



SAE O-Ring Face Plug with O-Ring

0014	Thread
96000	9/16"
96001	11/16"
96002	13/16"
96003	1"
96004	1.3/16"
96005	1.7/16"
Tech Sheet 20000	



JIS Solid Plug 30° Cone (BSPP Threads)

0014	Thread
7681-04	1/4"
7681-06	3/8"
7681-08	1/2"
7681-12	3/4"
Tech Sheet 20000	



JIS Solid Plug 30° Cone (Metric Threads)

0014	Thread
9711-14	M14 x 1.5
9711-18	M18 x 1.5
9711-22	M22 x 1.5
9711-24	M24 x 1.5
9711-30	M30 x 1.5
Tech Sheet 20000	

Crosses



BSPP Male Cross 60° Cone for Bonded Seal

0014	Thread
03007	1/8"
03000	1/4"
03001	3/8"
03002	1/2"
03003	5/8"
03004	3/4"
03005	1"
03006	1.1/4"
Tech Sheet 20000	



BSPP Female Cross

0014	Thread
13023	1/8"
13020	1/4"
13021	3/8"
13022	1/2"
13024	3/4"
13025	1"
13026	1.1/4"
Tech Sheet 20000	



BSPP Swivel Female Cross 60° Cone

0014	Thread
Z4MB02	1/8"
Z4MB04	1/4"
Z4MB06	3/8"
Z4MB08	1/2"
Z4MB10	5/8"
Z4MB12	3/4"
Z4MB16	1"
Z4MB20	1.1/4"
Z4MB24	1.1/2"
Tech Sheet 20000	



NPT Female Cross

0014	Thread
37000	1/4"
37001	3/8"
37002	1/2"
37004	1"
37006	1.1/2"
Tech Sheet 20000	


Ferrules



R2AT Non-skive Ferrule


0014	ID
19951	3/8"
19953	5/8"
19955	1"
Tech Sheet 20000	

Locknuts



BSPP Locknut

0014	Thread
BLN02	1/8"
BLN04	1/4"
BLN06	3/8"
BLN08	1/2"
BLN10	5/8"
BLN12	3/4"
BLN16	1"
BLN20	1.1/4"
BLN24	1.1/2"
BLN32	2"
Tech Sheet 20000	



Metric Locknut

0014	Thread
MLN12	M12 x 1.5
MLN14	M14 x 1.5
MLN16	M16 x 1.5
MLN18	M18 x 1.5
MLN20	M20 x 1.5
MLN22	M22 x 1.5
MLN24	M24 x 1.5
Tech Sheet 20000	

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Blanking Caps



BSPP Swivel 60° Coned Blanking Cap

0014	Thread
7BSBC02	1/8"
7BSBC04	1/4"
7BSBC06	3/8"
7BSBC08	1/2"
7BSBC10	5/8"
7BSBC12	3/4"
7BSBC16	1"
7BSBC20	1.1/4"
7BSBC24	1.1/2"
7BSBC32	2"
Tech Sheet 20000	



Metric Swivel Blanking Cap

0014	Thread
7M12	M12 x 1.5
7M14	M14 x 1.5
7M16	M16 x 1.5
7M18	M18 x 1.5
7M20	M20 x 1.5
7M22	M22 x 1.5
Tech Sheet 20000	



JIS Female Cap (BSPP Threads)

0014	Thread
7691-04	1/4"
7691-06	3/8"
7691-08	1/2"
7691-12	3/4"
Tech Sheet 20000	



JIS Female Cap (Metric Threads)

0014	Thread
9721-14	M14 x 1.5
9721-18	M18 x 1.5
9721-22	M22 x 1.5
9721-24	M24 x 1.5
9721-30	M30 x 1.5
Tech Sheet 20000	

Crimp Nuts



BSPP Crimp Nut

0014	Thread
708021	1/4"
708023	1/2"
708024	5/8"
708025	3/4"
708026	1"
708027	1.1/4"
708028	1.1/2"
708029	2"
Tech Sheet 20000	



Metric Crimp Nut

0014	Thread
708049	M10 x 1.5
708050	M12 x 1.5
708051	M14 x 1.5
708053	M18 x 1.5
Tech Sheet 20000	



NPSM Crimp Nut

0014	Thread
18004	1/8"
18000	1/4"
18001	3/8"
18002	1/2"
18003	3/4"
18005	1"
18007	1.1/4"
18008	1.1/2"
18009	2"
Tech Sheet 20000	

Test Point Adaptors



BSPP Male x Swivel Female, 1/8" BSP Test Point

0014	Thread
01425-TP-B02	1/8"
01427-TP-B02	1/4"
01434-TP-B02	3/8"
01440-TP-B02	1/2"
01451-TP-B02	3/4"
01458-TP-B02	1"
Tech Sheet 20000	



1/8" BSPP Male, M16x2 Test Point Fitting

0014	Thread
MTP/B02-M16/2S	1/8"
Tech Sheet 20000	

FT PRO®



For **Threaded Hydraulic Valves** see pages **244-246**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Male Adaptors

NPTF Male x JIC Male 37° Cone



0014	Thread	Thread
1NJ0207	1/8"	7/16"
1NJ0208	1/8"	1/2"
1NJ0209	1/8"	9/16"
1NJ0407	1/4"	7/16"
1NJ0408	1/4"	1/2"
1NJ0409	1/4"	9/16"
1NJ0412	1/4"	3/4"
1NJ0414	1/4"	7/8"
1NJ0607	3/8"	7/16"
1NJ0608	3/8"	1/2"
1NJ0609	3/8"	9/16"
1NJ0612	3/8"	3/4"
1NJ0614	3/8"	7/8"
1NJ0807	1/2"	7/16"
1NJ0809	1/2"	9/16"
1NJ0812	1/2"	3/4"
1NJ0814	1/2"	7/8"
1NJ0817	1/2"	1.1/16"
1NJ0821	1/2"	1.5/16"
1NJ1207	3/4"	7/16"
1NJ1209	3/4"	9/16"
1NJ1214	3/4"	7/8"
1NJ1217	3/4"	1.1/16"
1NJ1226	3/4"	1.5/8"
1NJ1612	1"	3/4"
1NJ1614	1"	7/8"
1NJ1621	1"	1.5/16"
1NJ1626	1"	1.5/8"
1NJ1630	1"	1.7/8"
1NJ2017	1.1/4"	1.1/16"
1NJ2021	1.1/4"	1.5/16"
1NJ2030	1.1/4"	1.7/8"
1NJ2040	1.1/4"	2.1/2"
1NJ2417	1.1/2"	1.1/16"
1NJ2421	1.1/2"	1.5/16"
1NJ2426	1.1/2"	1.5/8"
1NJ2430	1.1/2"	1.7/8"
1NJ2440	1.1/2"	2.1/2"
1NJ3226	2"	1.5/8"
1NJ3230	2"	1.7/8"
1NJ3240	2"	2.1/2"
Tech Sheet 20000		

BSPP Male x JIC Male 37° Cone Restrictor Blank Only



0014	Thread	Thread
13230	1/4"	9/16"
13231	3/8"	7/16"
13232	3/8"	9/16"
13233	1/2"	9/16"
Tech Sheet 20000		

BSPT Male x JIC Male 37° Cone



0014	Thread	Thread
1BTJ0207	1/8"	7/16"
1BTJ0208	1/8"	1/2"
1BTJ0209	1/8"	9/16"
1BTJ0407	1/4"	7/16"
1BTJ0408	1/4"	1/2"
1BTJ0409	1/4"	9/16"
1BTJ0412	1/4"	3/4"
1BTJ0607	3/8"	7/16"
1BTJ0608	3/8"	1/2"
1BTJ0609	3/8"	9/16"
1BTJ0612	3/8"	3/4"
1BTJ0809	1/2"	9/16"
1BTJ0812	1/2"	3/4"
1BTJ0814	1/2"	7/8"
1BTJ0817	1/2"	1.1/16"
1BTJ1212	3/4"	3/4"
1BTJ1214	3/4"	7/8"
1BTJ1217	3/4"	1.1/16"
1BTJ1219	3/4"	1.3/16"
1BTJ1221	3/4"	1.5/16"
1BTJ1612	1"	3/4"
1BTJ1617	1"	1.1/16"
1BTJ1621	1"	1.5/16"
1BTJ1626	1"	1.5/8"
1BTJ2021	1.1/4"	1.5/16"
1BTJ2026	1.1/4"	1.5/8"
1BTJ2426	1.1/2"	1.5/8"
1BTJ2430	1.1/2"	1.7/8"
1BTJ3230	2"	1.7/8"
1BTJ3240	2"	2.1/2"
Tech Sheet 20000		

JIC Male x JIC Male 37° Cone



0014	Thread	Thread
1JP0505	5/16"	5/16"
1JP0507	5/16"	7/16"
1JP0707	7/16"	7/16"
1JP0709	7/16"	9/16"
1JP0807	1/2"	7/16"
1JP0808	1/2"	1/2"
1JP0809	1/2"	9/16"
1JP0812	1/2"	3/4"
1JP0814	1/2"	7/8"
1JP0909	9/16"	9/16"
1JP0914	9/16"	7/8"
1JP0917	9/16"	1.1/16"
1JP0919	9/16"	1.3/16"
1JP1207	3/4"	7/16"
1JP1209	3/4"	9/16"
1JP1212	3/4"	3/4"
1JP1214	3/4"	7/8"
1JP1414	7/8"	7/8"
1JP1417	7/8"	1.1/16"
1JP1421	7/8"	1.5/16"
1JP1717	1.1/16"	1.1/16"
1JP1721	1.1/16"	1.5/16"
1JP1919	1.3/16"	1.3/16"
1JP2121	1.5/16"	1.5/16"
1JP2126	1.5/16"	1.5/8"
1JP2130	1.5/16"	1.7/8"
1JP2626	1.5/8"	1.5/8"
1JP3030	1.7/8"	1.7/8"
1JP4040	2.1/2"	2.1/2"
Tech Sheet 20000		

JIC Male 37° Cone x JIS Male 30° Cone (BSPP Threads)



0014	Thread	Thread
6811-04-04	7/16"	1/4"
6811-06-06	9/16"	3/8"
6811-08-08	3/4"	1/2"
Tech Sheet 20000		

JIC Male 37° Cone x JIS Male 30° Cone (Metric Threads)



0014	Thread	Thread
8751-04-14	7/16"	M14 x 1.5
8751-06-18	9/16"	M18 x 1.5
8751-08-22	3/4"	M22 x 1.5
8751-10-24	7/8"	M24 x 1.5
8751-12-30	1.1/16"	M30 x 1.5
8751-16-33	1.5/16"	M33 x 1.5
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Male Adaptors



Metric Male x JIC Male 37° Cone

0014	Thread	Thread
01265	M10 x 1.5	7/16"
01274	M12 x 1.5	7/16"
01284	M12 x 1.5	9/16"
01286	M12 x 1.5	3/4"
01268	M14 x 1.5	3/8"
01291	M14 x 1.5	7/16"
01287	M14 x 1.5	9/16"
01288	M14 x 1.5	3/4"
01272	M14 x 1.5	7/8"
01295	M16 x 1.5	7/16"
01280	M16 x 1.5	9/16"
01275	M16 x 1.5	3/4"
01289	M16 x 1.5	7/8"
01299	M18 x 1.5	7/16"
01276	M18 x 1.5	9/16"
01281	M18 x 1.5	3/4"
01283	M18 x 1.5	7/8"
01298	M18 x 1.5	1.1/16"
01282	M20 x 1.5	9/16"
01277	M20 x 1.5	3/4"
01290	M20 x 1.5	7/8"
01270	M20 x 1.5	1.1/16"
01285	M22 x 1.5	9/16"
01278	M22 x 1.5	3/4"
01279	M22 x 1.5	7/8"
01294	M22 x 1.5	1.1/16"
01267	M24 x 1.5	1.1/16"
01297	M26 x 1.5	7/8"
01292	M26 x 1.5	1.1/16"
Tech Sheet 20000		



BSPP Male 60° Cone x JIC 37° Cone Male

0014	Thread	Thread
1BJP0207	1/8"	7/16"
1BJP0208	1/8"	1/2"
1BJP0209	1/8"	9/16"
1BJP0407	1/4"	7/16"
1BJP0408	1/4"	1/2"
1BJP0409	1/4"	9/16"
1BJP0412	1/4"	3/4"
1BJP0414	1/4"	7/8"
1BJP0417	1/4"	1.1/16"
1BJP0421	1/4"	1.5/16"
1BJP0607	3/8"	7/16"
1BJP0608	3/8"	1/2"
1BJP0609	3/8"	9/16"
1BJP0612	3/8"	3/4"
1BJP0614	3/8"	7/8"
1BJP0617	3/8"	1.1/16"
1BJP0621	3/8"	1.5/16"
1BJP0807	1/2"	7/16"
1BJP0808	1/2"	1/2"
1BJP0809	1/2"	9/16"
1BJP0812	1/2"	3/4"
1BJP0814	1/2"	7/8"
1BJP0817	1/2"	1.1/16"
1BJP0821	1/2"	1.5/16"
1BJP1009	5/8"	9/16"
1BJP1012	5/8"	3/4"
1BJP1014	5/8"	7/8"
1BJP1017	5/8"	1.1/16"
1BJP1019	5/8"	1.3/16"
1BJP1021	5/8"	1.5/16"
1BJP1207	3/4"	7/16"
1BJP1208	3/4"	1/2"
1BJP1209	3/4"	9/16"
1BJP1212	3/4"	3/4"
1BJP1214	3/4"	7/8"
1BJP1217	3/4"	1.1/16"
1BJP1219	3/4"	1.3/16"
1BJP1221	3/4"	1.5/16"
1BJP1226	3/4"	1.5/8"
1BJP1230	3/4"	1.7/8"
1BJP1612	1"	3/4"
1BJP1614	1"	7/8"
1BJP1617	1"	1.1/16"
1BJP1619	1"	1.3/16"
1BJP1621	1"	1.5/16"
1BJP1626	1"	1.5/8"
1BJP1630	1"	1.7/8"
1BJP2017	1.1/4"	1.1/16"
1BJP2021	1.1/4"	1.5/16"
1BJP2026	1.1/4"	1.5/8"
1BJP2030	1.1/4"	1.7/8"
1BJP2040	1.1/4"	2.1/2"
1BJP2421	1.1/2"	1.5/16"
1BJP2426	1.1/2"	1.5/8"
1BJP2430	1.1/2"	1.7/8"
1BJP2440	1.1/2"	2.1/2"
1BJP3230	2"	1.7/8"
1BJP3240	2"	2.1/2"
Tech Sheet 20000		



Metric Male 24° Cone x JIC Male 37° Cone

0014	To Fit Tube Size mm	Thread	Thread
01-06L04J	6	M12 x 1.5	7/16"
01-06S04J	6	M14 x 1.5	7/16"
01-08L04J	8	M14 x 1.5	7/16"
01-08S04J	8	M16 x 1.5	7/16"
01-10L06J	8	M16 x 1.5	9/16"
01-08S08J	10	M16 x 1.5	9/16"
41275-10	10	M16 x 1.5	3/4"
01-10S06J	10	M18 x 1.5	9/16"
01-12L06J	12	M18 x 1.5	9/16"
01-10S08J	10	M18 x 1.5	3/4"
01-12L08J	12	M18 x 1.5	3/4"
01-12S08J	12	M20 x 1.5	3/4"
01-14S08J	14	M20 x 1.5	3/4"
01-15L08J	15	M22 x 1.5	3/4"
01-15L12J	15	M22 x 1.5	1.1/16"
41270-20	20	M30 x 1.5	1.1/16"
41270-22	22	M30 x 1.5	1.1/16"
41262-28	28	M36 x 1.5	1.1/16"
01-35LX216J	35	M45 x 1.5	1.5/16"
Tech Sheet 20000			

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Male/Male Adaptors



SAE Boss Male x JIC Male 37° Coneless O-Ring

0014	Thread	Thread
01350	7/16"	7/16"
01353	7/16"	1/2"
01351	7/16"	9/16"
01392	1/2"	7/16"
01352	1/2"	1/2"
01388	1/2"	9/16"
01354	9/16"	7/16"
01355	9/16"	1/2"
01356	9/16"	9/16"
01357	9/16"	3/4"
01358	9/16"	7/8"
01389	3/4"	7/16"
01361	3/4"	9/16"
01362	3/4"	3/4"
01363	3/4"	7/8"
01364	3/4"	1.1/16"
01386	7/8"	9/16"
01365	7/8"	3/4"
01366	7/8"	7/8"
01367	7/8"	1.1/16"
01395	1.1/16"	9/16"
01368	1.1/16"	3/4"
01370	1.1/16"	7/8"
01371	1.1/16"	1.1/16"
01373	1.1/16"	1.5/16"
01391	1.3/16"	1.3/16"
01394	1.5/16"	3/4"
01396	1.5/16"	7/8"
01377	1.5/16"	1.1/16"
01378	1.5/16"	1.5/16"
01379	1.5/16"	1.5/8"
01380	1.5/8"	1.5/16"
01381	1.5/8"	1.5/8"
01387	1.5/8"	1.7/8"
01397	1.7/8"	1.5/16"
01383	1.7/8"	1.5/8"
01384	1.7/8"	1.7/8"
01369	1.7/8"	2.1/2"
01385	2.1/2"	2.1/2"
Tech Sheet 20000		



Metric Male 24° Cone x JIC Male 37° Cone

0014	To Fit Tube Size mm	Thread	Thread
01-22LX212J	22	M30 x 2	1.1/16"
01-25SX212J	25	M36 x 2	1.1/16"
01-30SX220J	30	M42 x 2	1.5/8"
01-35LX216J	35	M45 x 2	1.5/16"
01-38SX220J	38	M52 x 2	1.5/8"
Tech Sheet 20000			

Male/Female Fixed Adaptors



JIC Male 37° Cone x BSPP Female Extended

0014	Male Thread	Female Thread
17004	7/16"	1/8"
17001	7/16"	1/4"
Tech Sheet 20000		



JIC Male x 37° Cone NPT Female Extended

0014	Male Thread	Female Thread
16261	7/16"	1/8"
16250	7/16"	1/4"
16249	7/16"	3/8"
16251	9/16"	1/4"
16257	9/16"	3/8"
16258	9/16"	1/2"
16256	3/4"	3/8"
16252	3/4"	1/2"
16253	7/8"	1/2"
16254	1.1/16"	3/4"
16255	1.5/16"	1"
Tech Sheet 20000		



JIC Male 37° Cone x JIS Female Extended 60° Internal Seat (Metric Threads)

0014	Male Thread	Female Thread
8701-04-14	7/16"	M14 x 1.5
8701-06-18	9/16"	M18 x 1.5
8701-08-22	3/4"	M22 x 1.5
8701-12-30	1.1/16"	M30 x 1.5
8701-16-33	1.5/16"	M33 x 1.5
Tech Sheet 20000		

Male/Female Swivel Adaptors



NPT Male x JIC Swivel Female 37° Cone

0014	Male Thread	Female Thread
11201	1/4"	9/16"
11202	3/8"	3/4"
11203	1/2"	7/8"
11204	3/4"	1.1/16"
11205	1"	1.5/16"
Tech Sheet 20000		



BSPP Male 60° Cone x JIC Swivel Female 37° Cone

0014	Male Thread	Female Thread
2BJ0207	1/8"	7/16"
2BJ0407	1/4"	7/16"
2BJ0408	1/4"	1/2"
2BJ0409	1/4"	9/16"
2BJ0412	1/4"	3/4"
2BJ0607	3/8"	7/16"
2BJ0608	3/8"	1/2"
2BJ0609	3/8"	9/16"
2BJ0612	3/8"	3/4"
2BJ0614	3/8"	7/8"
2BJ0807	1/2"	7/16"
2BJ0808	1/2"	1/2"
2BJ0809	1/2"	9/16"
2BJ0812	1/2"	3/4"
2BJ0814	1/2"	7/8"
2BJ0817	1/2"	1.1/16"
2BJ1012	5/8"	3/4"
2BJ1014	5/8"	7/8"
2BJ1017	5/8"	1.1/16"
2BJ1212	3/4"	3/4"
2BJ1214	3/4"	7/8"
2BJ1217	3/4"	1.1/16"
2BJ1219	3/4"	1.3/16"
2BJ1221	3/4"	1.5/16"
2BJ1617	1"	1.1/16"
2BJ1619	1"	1.3/16"
2BJ1621	1"	1.5/16"
2BJ1626	1"	1.5/8"
2BJ2021	1.1/4"	1.5/16"
2BJ2026	1.1/4"	1.5/8"
2BJ3230	2"	1.7/8"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Male/Female Swivel Adaptors

JIC Male 37° Cone x BSPP Swivel Female 60° Cone



0014	Male Thread	Female Thread
2JB0702	7/16"	1/8"
2JB0704	7/16"	1/4"
2JB0706	7/16"	3/8"
2JB0708	7/16"	1/2"
2JB0804	1/2"	1/4"
2JB0806	1/2"	3/8"
2JB0808	1/2"	1/2"
2JB0904	9/16"	1/4"
2JB0906	9/16"	3/8"
2JB1206	3/4"	3/8"
2JB1208	3/4"	1/2"
2JB1210	3/4"	5/8"
2JB1212	3/4"	3/4"
2JB1406	7/8"	3/8"
2JB1408	7/8"	1/2"
2JB1410	7/8"	5/8"
2JB1412	7/8"	3/4"
2JB1712	1.1/16"	3/4"
2JB2116	1.5/16"	1"
2JB2620	1.5/8"	1.1/4"
Tech Sheet 20000		

JIC Male 37° Cone x Metric Swivel Female



0014	Male Thread	Female Thread
01664	7/16"	M12 x 1.5
01651	9/16"	M14 x 1.5
01652	9/16"	M16 x 1.5
01653	9/16"	M18 x 1.5
01654	9/16"	M20 x 1.5
01655	9/16"	M22 x 1.5
01656	3/4"	M16 x 1.5
01657	3/4"	M18 x 1.5
01659	3/4"	M22 x 1.5
01661	7/8"	M18 x 1.5
01662	7/8"	M20 x 1.5
01663	7/8"	M22 x 1.5
Tech Sheet 20000		

JIC Male 37° Cone x JIC Swivel Female 37° Cone



0014	Male Thread	Female Thread
2J0707	7/16"	7/16"
2J0709	7/16"	9/16"
2J0712	7/16"	3/4"
2J0714	7/16"	7/8"
2J0808	1/2"	1/2"
2J0809	1/2"	9/16"
2J0907	9/16"	7/16"
2J0908	9/16"	1/2"
2J0909	9/16"	9/16"
2J0912	9/16"	3/4"
2J0914	9/16"	7/8"
2J1209	3/4"	9/16"
2J1212	3/4"	3/4"
2J1214	3/4"	7/8"
2J1217	3/4"	1.1/16"
2J1412	7/8"	3/4"
2J1414	7/8"	7/8"
2J1417	7/8"	1.1/16"
2J1712	1.1/16"	3/4"
2J1714	1.1/16"	7/8"
2J1717	1.1/16"	1.1/16"
2J1721	1.1/16"	1.5/16"
2J1919	1.3/16"	1.3/16"
2J2126	1.5/16"	1.5/8"
2J2626	1.5/8"	1.5/8"
2J2630	1.5/8"	1.7/8"
Tech Sheet 20000		

Metric Male x JIC Swivel Female 37° Cone



0014	Male Thread	Female Thread
01625	M12 x 1.5	1/2"
01626	M14 x 1.5	9/16"
01627	M16 x 1.5	9/16"
01628	M16 x 1.5	3/4"
01631	M18 x 1.5	3/4"
Tech Sheet 20000		

Danfoss Waltech



For **ABF Anti Bloc Grease** see page **164**

BSPP Swivel Female 60° Cone x JIC Swivel Female 37° Cone



0014	Thread	Thread
3BJ0407	1/4"	7/16"
3BJ0408	1/4"	1/2"
3BJ0409	1/4"	9/16"
3BJ0607	3/8"	7/16"
3BJ0608	3/8"	1/2"
3BJ0609	3/8"	9/16"
3BJ0612	3/8"	3/4"
3BJ0614	3/8"	7/8"
3BJ0809	1/2"	9/16"
3BJ0812	1/2"	3/4"
3BJ0814	1/2"	7/8"
3BJ0817	1/2"	1.1/16"
3BJ1014	5/8"	7/8"
3BJ1212	3/4"	3/4"
3BJ1217	3/4"	1.1/16"
3BJ1221	3/4"	1.5/16"
3BJ1617	1"	1.1/16"
3BJ1621	1"	1.5/16"
3BJ2026	1.1/4"	1.5/8"
Tech Sheet 20000		

Female Swivel Adaptors

JIC Swivel Female 37° Cone x JIC Swivel Female 37° Cone



0014	Thread	Thread
3J0707	7/16"	7/16"
3J0709	7/16"	9/16"
3J0712	7/16"	3/4"
3J0808	1/2"	1/2"
3J0809	1/2"	9/16"
3J0909	9/16"	9/16"
3J0912	9/16"	3/4"
3J1212	3/4"	3/4"
3J1409	7/8"	9/16"
3J1412	7/8"	3/4"
3J1414	7/8"	7/8"
3J1717	1.1/16"	1.1/16"
3J1721	1.1/16"	1.5/16"
3J1919	1.3/16"	1.3/16"
3J2121	1.5/16"	1.5/16"
3J2626	1.5/8"	1.5/8"
Tech Sheet 20000		

Fluid-Air Components Ltd

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

90º Elbows

JIC Male x JIC Male 90° Forged Compact Elbow



0014	Thread
03085FD	7/16"
03086FD	1/2"
03087FD	9/16"
03088FD	3/4"
03089FD	7/8"
03090FD	1.1/16"
03091FD	1.3/16"
Tech Sheet 20000	

NPTF Male x JIC Male 90° Forged Compact Elbow



0014	Thread	Thread
04050FD	1/8"	7/16"
04053FD	1/4"	7/16"
04059FD	3/8"	9/16"
04060FD	3/8"	3/4"
04065FD	1/2"	3/4"
04073FD	3/4"	1.1/16"
04076FD	1"	1.5/16"
Tech Sheet 20000		

JIC Male x Male Bulkhead 90° Forged



0014	Thread
10525-03	3/8"
10525-04	7/16"
10525-05	1/2"
10525-06	9/16"
10525-08	3/4"
10525-10	7/8"
10525-12	1.1/16"
10525-16	1.5/16"
Tech Sheet 20000	



JIC Male 37° Cone x BSPP Male 90° Positional Forged Elbow

0014	Thread	Thread
27070FDPOS	7/16"	1/4"
27072FDPOS	9/16"	1/4"
27073FDPOS	9/16"	3/8"
27077FDPOS	3/4"	3/8"
27074FDPOS	3/4"	1/2"
27079FDPOS	7/8"	1/2"
27075FDPOS	1.1/16"	3/4"
27076FDPOS	1.5/16"	1"
Tech Sheet 20000		

JIC Male x JIC Swivel Female 90° Forged Compact Elbow 37° Cone



0014	Thread
05050FD	7/16"
05051FD	1/2"
05052FD	9/16"
05053FD	3/4"
05054FD	7/8"
05055FD	1.1/16"
05056FD	1.5/16"
Tech Sheet 20000	

NPT Male x JIC Male 90° Compact Elbow 37° Cone



0014	Thread	Thread
04086	1/8"	5/16"
04050	1/8"	7/16"
04051	1/8"	1/2"
04052	1/8"	9/16"
04053	1/4"	7/16"
04054	1/4"	1/2"
04055	1/4"	9/16"
04056	1/4"	3/4"
04087	3/8"	3/8"
04057	3/8"	7/16"
04058	3/8"	1/2"
04059	3/8"	9/16"
04060	3/8"	3/4"
04061	3/8"	7/8"
04048	3/8"	1.1/16"
04062	1/2"	7/16"
04063	1/2"	1/2"
04064	1/2"	9/16"
04065	1/2"	3/4"
04066	1/2"	7/8"
04082	1/2"	1.1/16"
04070	3/4"	9/16"
04071	3/4"	3/4"
04072	3/4"	7/8"
04073	3/4"	1.1/16"
04075	3/4"	1.5/16"
04085	1"	3/4"
04089	1"	7/8"
04074	1"	1.1/16"
04076	1"	1.5/16"
04077	1"	1.5/8"
04078	1.1/4"	1.5/16"
04079	1.1/4"	1.5/8"
04083	1.1/4"	1.7/8"
04084	1.1/2"	1.5/8"
04080	1.1/2"	1.7/8"
04088	1.1/2"	2.1/2"
04081	2"	2.1/2"
Tech Sheet 20000		

JIC Swivel Female x JIC Swivel Female 90° Compact Elbow 37° Cone



0014	Thread	Thread
XJF0707	7/16"	7/16"
XJF0909	9/16"	9/16"
XJF1212	3/4"	3/4"
XJF1414	7/8"	7/8"
XJF1717	1.1/16"	1.1/16"
XJF1919	1.3/16"	1.3/16"
XJF2121	1.5/16"	1.5/16"
Tech Sheet 20000		



NPT Male x JIC Swivel Female 90° Compact Elbow 37° Cone

0014	Male Thread	Female Thread
99001	3/8"	9/16"
Tech Sheet 20000		



NPT Male x SAE Male 90° Compact Elbow 45° Cone

0014	Thread	Thread
07020	1/8"	7/16"
07021	1/8"	1/2"
07022	1/4"	7/16"
07023	1/4"	1/2"
07024	1/4"	5/8"
07025	1/4"	3/4"
07026	3/8"	7/16"
07027	3/8"	1/2"
07028	3/8"	5/8"
07029	3/8"	3/4"
07030	3/8"	7/8"
07031	1/2"	5/8"
Tech Sheet 20000		

flaretite



For **Flaretite Seals** see page **111**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

90º Elbows

JIC Male 37° Cone x Metric Male 90° Positional Forged Elbow



0014	Thread	Thread
29500FDPOS	7/16"	M12 x 1.5
29501FDPOS	7/16"	M14 x 1.5
29502FDPOS	9/16"	M16 x 1.5
29503FDPOS	9/16"	M18 x 1.5
29505FDPOS	3/4"	M18 x 1.5
29506FDPOS	3/4"	M20 x 1.5
29507FDPOS	3/4"	M22 x 1.5
29508FDPOS	7/8"	M22 x 1.5
29509FDPOS	1.1/16"	M22 x 1.5
Tech Sheet 20000		

JIC Male 37° Cone x JIC Swivel Female 90° Swept Elbow



0014	Thread
10900	7/16"
10902	9/16"
10903	3/4"
10904	7/8"
10905	1.1/16"
10907	1.5/16"
10908	1.5/8"
Tech Sheet 20000	

JIC Male 37° Cone x UNF Male 90° Positional Forged Elbow



0014	Thread	Thread
03085FDPOS	7/16"	7/16"
03087FDPOS	9/16"	9/16"
03088FDPOS	3/4"	3/4"
03089FDPOS	7/8"	7/8"
03090FDPOS	1.1/16"	1.1/16"
03092FDPOS	1.5/16"	1.5/16"
Tech Sheet 20000		

BSPP Male 60° Cone x JIC Swivel Female 37° Cone 90° Compact Elbow



0014	Male Thread	Female Thread
XBMJF0409	1/4"	9/16"
XBMJF0609	3/8"	9/16"
XBMJF0612	3/8"	3/4"
XBMJF0812	1/2"	3/4"
XBMJF0814	1/2"	7/8"
XBMJF1014	5/8"	7/8"
XBMJF1217	3/4"	1.1/16"
Tech Sheet 20000		

BSPP Male 60° Cone x JIC Male 90° Compact Elbow 37° Cone



0014	Thread	Thread
XMB04J07	1/4"	7/16"
XMB04J08	1/4"	1/2"
XMB04J09	1/4"	9/16"
XMB06J09	3/8"	9/16"
XMB06J12	3/8"	3/4"
XMB08J12	1/2"	3/4"
XMB08J14	1/2"	7/8"
XMB12J14	3/4"	7/8"
XMB12J17	3/4"	1.1/16"
XMB16J17	1"	1.1/16"
XMB16J21	1"	1.5/16"
XMB20J26	1.1/4"	1.5/8"
XMB24J30	1.1/2"	1.7/8"
Tech Sheet 20000		

BSPT Male x JIC Male 90° Compact Elbow 37° Cone



0014	Thread	Thread
08550	1/8"	7/16"
08551	1/8"	1/2"
08552	1/8"	9/16"
08553	1/4"	7/16"
08554	1/4"	1/2"
08555	1/4"	9/16"
08556	1/4"	3/4"
08557	3/8"	7/16"
08558	3/8"	1/2"
08559	3/8"	9/16"
08560	3/8"	3/4"
08561	3/8"	7/8"
08562	1/2"	7/16"
08564	1/2"	9/16"
08565	1/2"	3/4"
08566	1/2"	7/8"
08567	1/2"	1.1/16"
08584	1/2"	1.5/16"
08568	3/4"	9/16"
08569	3/4"	3/4"
08570	3/4"	7/8"
08571	3/4"	1.1/16"
08572	3/4"	1.5/16"
08573	1"	3/4"
08585	1"	7/8"
08574	1"	1.1/16"
08575	1"	1.5/16"
08576	1"	1.5/8"
08577	1.1/4"	1.5/16"
08578	1.1/4"	1.5/8"
08579	1.1/4"	1.7/8"
08580	1.1/2"	1.5/8"
08581	1.1/2"	1.7/8"
08582	2"	2.1/2"
Tech Sheet 20000		

JIC Male 37° Cone x BSPP Swivel Female 90° Compact Elbow 60° Cone



0014	Male Thread	Female Thread
09612	7/16"	1/4"
09605	9/16"	3/8"
09608	3/4"	3/8"
09606	3/4"	1/2"
09607	1.1/16"	3/4"
09609	1.5/16"	1"
09610	1.7/8"	1.1/2"
Tech Sheet 20000		

JIC Male 37° Cone x JIC Male 90° Compact Elbow



0014	Thread	Thread
XMJ0909	9/16"	9/16"
XMJ1212	3/4"	3/4"
XMJ1414	7/8"	7/8"
XMJ1717	1.1/16"	1.1/16"
XMJ1919	1.3/16"	1.3/16"
XMJ2121	1.5/16"	1.5/16"
XMJ2626	1.5/8"	1.5/8"
XMJ3030	1.7/8"	1.7/8"
Tech Sheet 20000		

JIC Male 37° Cone x JIC Swivel Female 90° Compact Elbow



0014	Thread	Thread
XJMF0707	7/16"	7/16"
XJMF0808	1/2"	1/2"
XJMF0909	9/16"	9/16"
XJMF1212	3/4"	3/4"
XJMF1414	7/8"	7/8"
XJMF1717	1.1/16"	1.1/16"
XJMF2121	1.5/16"	1.5/16"
XJMF2626	1.5/8"	1.5/8"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

45º Elbows

JIC Male x JIC Swivel Female 45° Swept Elbow



0014	Thread
11905	1.1/16"
11907	1.5/16"

Tech Sheet 20000

JIC Male x JIC Male Bulkhead 45° Forged



0014	Thread
10375-04	7/16"
10375-05	1/2"
10375-06	9/16"
10375-08	3/4"
10375-10	7/8"
10375-12	1.1/16"
10375-16	1.5/16"

Tech Sheet 20000

JIC Male 37° Cone x UNF Male 45° Positional Forged Elbow



0014	Thread	Thread
03085FDPOS-45	7/16"	7/16"
03087FDPOS-45	9/16"	9/16"
03088FDPOS-45	3/4"	3/4"
03089FDPOS-45	7/8"	7/8"
03090FDPOS-45	1.1/16"	1.1/16"
03092FDPOS-45	1.5/16"	1.5/16"

Tech Sheet 20000

JIC Male x JIC Swivel Female 45° Forged Compact Elbow 37° Cone



0014	Thread
05050/45FD	7/16"
05052/45FD	9/16"
05053/45FD	3/4"
05054/45FD	7/8"
05055/45FD	1.1/16"
05056/45FD	1.5/16"

Tech Sheet 20000

JIC Male x JIC Swivel Female 45° Compact Elbow 37° Cone



0014	Thread
05050/45	7/16"
05052/45	9/16"
05053/45	3/4"
05055/45	1.1/16"
05056/45	1.5/16"
05059/45	1.7/8"

Tech Sheet 20000

NPT Male x JIC Male 45° Forged Compact Elbow 37° Cone



0014	Thread	Thread
04053/45FD	1/4"	7/16"
04059/45FD	3/8"	9/16"
04060/45FD	3/8"	3/4"
04065/45FD	1/2"	3/4"
04066/45FD	1/2"	7/8"
04073/45FD	3/4"	1.1/16"
04076/45FD	1"	1.5/16"

Tech Sheet 20000

Bulkheads

JIC Male x JIC Male Bulkhead 37° Cone complete with Locknut



0014	Thread
00236	3/8"
00225	7/16"
00226	1/2"
00227	9/16"
00228	3/4"
00229	7/8"
00230	1.1/16"
00234	1.3/16"
00231	1.5/16"
00232	1.5/8"
00233	1.7/8"

Tech Sheet 20000

JIC Male x JIC Male Bulkhead 37° Cone No Locknut



0014	Thread
8JP0707	7/16"
8JP0808	1/2"
8JP0909	9/16"
8JP1212	3/4"
8JP1414	7/8"
8JP1717	1.1/16"
8JP2121	1.5/16"

Tech Sheet 20000

Tees

JIC Male x JIC Male x UNF Male Forced Positional On Run with O-Ring



0014	Thread
10716-04-04-04	7/16"
10716-05-05-05	1/2"
10716-06-06-06	9/16"
10716-08-08-08	3/4"
10716-10-10-10	7/8"
10716-12-12-12	1.1/16"

Tech Sheet 20000

JIC Male x JIC Swivel Female x JIC Male Branch Tee 37° Cone



0014	Thread
ZMFMJ07	7/16"
ZMFMJ08	1/2"
ZMFMJ09	9/16"
ZMFMJ12	3/4"
ZMFMJ14	7/8"
ZMFMJ17	1.1/16"
ZMFMJ21	1.5/16"
ZMFMJ26	1.5/8"
ZMFMJ30	1.7/8"

Tech Sheet 20000

JIC Male x JIC Swivel Female x JIC Swivel Female Branch Tee 37° Cone



0014	Thread
ZMFFJ07	7/16"
ZMFFJ08	1/2"
ZMFFJ09	9/16"
ZMFFJ12	3/4"
ZMFFJ14	7/8"
ZMFFJ17	1.1/16"
ZMFFJ21	1.5/16"

Tech Sheet 20000

JIC Swivel Female x JIC Swivel Female x JIC Male Branch Tee 37° Cone



0014	Thread
ZFFMJ07	7/16"
ZFFMJ08	1/2"
ZFFMJ09	9/16"
ZFFMJ12	3/4"
ZFFMJ14	7/8"
ZFFMJ17	1.1/16"
ZFFMJ21	1.5/16"

Tech Sheet 20000

Fluid-Air Components Ltd

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER

Tees

JIC Male x JIC Male x UNF Male Forged Positional On Branch with O-Ring



0014	Thread
10715-04-04-04	7/16"
10715-05-05-05	1/2"
10715-06-06-06	9/16"
10715-08-08-08	3/4"
10715-10-10-10	7/8"
10715-12-12-12	1.1/16"

Tech Sheet 20000

JIC Male Tee 37° Cone



0014	Thread
ZMJ07	7/16"
ZMJ09	9/16"
ZMJ12	3/4"
ZMJ14	7/8"
ZMJ17	1.1/16"
ZMJ19	1.3/16"
ZMJ21	1.5/16"

Tech Sheet 20000

JIC Male x JIC Male x JIC Swivel Female Branch Tee 37° Cone



0014	Thread
ZMMFJ07	7/16"
ZMMFJ09	9/16"
ZMMFJ12	3/4"
ZMMFJ14	7/8"
ZMMFJ17	1.1/16"
ZMMFJ21	1.5/16"
ZMMFJ26	1.5/8"

Tech Sheet 20000

JIC Swivel Female Tee 37° Cone



0014	Thread
ZFJ07	7/16"
ZFJ08	1/2"
ZFJ09	9/16"
ZFJ12	3/4"
ZFJ14	7/8"
ZFJ17	1.1/16"
ZFJ21	1.5/16"

Tech Sheet 20000

Crosses



JIC Male Cross 37° Cone

0014	Thread
03030	7/16"
03031	1/2"
03032	9/16"
03033	3/4"
03034	7/8"
03036	1.1/16"
03035	1.5/16"
03037	1.5/8"

Tech Sheet 20000

Plugs



JIC Solid Plug 37° Cone

0014	Thread
6J05	5/16"
6J07	7/16"
6J08	1/2"
6J09	9/16"
6J12	3/4"
6J14	7/8"
6J17	1.1/16"
6J19	1.3/16"
6J21	1.5/16"
6J26	1.5/8"
6J30	1.7/8"
6J40	2.1/2"

Tech Sheet 20000

Blanking Caps



JIC Swivel 37° Coned Blanking Cap

0014	Thread
7J07	7/16"
7J08	1/2"
7J09	9/16"
7J12	3/4"
7J14	7/8"
7J17	1.1/16"
7J19	1.3/16"
7J21	1.5/16"
7J26	1.5/8"
7J30	1.7/8"
7J40	2.1/2"

Tech Sheet 20000

Locknuts



JIC Locknut

0014	Thread
JLN07	7/16"
JLN08	1/2"
JLN09	9/16"
JLN12	3/4"
JLN14	7/8"
JLN17	1.1/16"
JLN21	1.5/16"
JLN26	1.5/8"
JLN30	1.7/8"

Tech Sheet 20000

Crimp Nuts



JIC Crimp Nut

0014	Thread
708075	7/16"
708076	1/2"
708077	9/16"
708078	5/8"
708079	3/4"
708080	7/8"
708084	1.3/16"
708081	1.5/16"
708083	1.5/8"
708082	1.7/8"
708085	2.1/2"

Tech Sheet 20000

Hose Inserts



JIC Male 37° Cone x Push-in Straight

0014	Thread	To Suit Hose ID
09711	7/16"	1/4"
09712	9/16"	3/8"

Tech Sheet 20000



JIC Swivel Female 37° Cone x Push-in Straight

0014	Thread	To Suit Hose ID
09700	7/16"	1/4"
09701	9/16"	3/8"
09705	3/4"	3/8"
09702	3/4"	1/2"
09703	7/8"	5/8"
09704	1.1/16"	3/4"
09707	1.5/16"	1"

Tech Sheet 20000



JIC Swivel Female 37° Cone x Push-in 90° Swept Elbow

0014	Thread	To Suit Hose ID
09301	7/16"	1/4"
09302	9/16"	3/8"
09303	3/4"	1/2"
09300	7/8"	5/8"
09304	1.1/16"	3/4"
09305	1.5/16"	1"

Tech Sheet 20000



JIC Swivel Female x Push-in 45° Swept Elbow 37° Cone

0014	Thread	To Suit Hose ID
09320	7/16"	1/4"
09321	9/16"	3/8"
09322	3/4"	1/2"
09323	7/8"	5/8"
09324	1.1/16"	3/4"

Tech Sheet 20000

FAC
Fluid-Air Components Ltd

JIC HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Tube Nuts



Universal Metric & Imperial

0014	Thread	To Suit Tube OD mm	To Suit Tube OD
4JTN	7/16"	6	1/4"
5JTN	1/2"	8	5/16"
6JTN	9/16"	10	3/8"
8JTN	3/4"	12	1/2"
10JTN	7/8"	14,15 &16	5/8"
12JTN	1.1/16"	18 & 20	3/4"
16JTN	1.5/16"	25	1"
20JTN	1.5/8"	28, 30 & 32	1.1/4"
24JTN	1.7/8"	35 & 38	1.1/2"
Tech Sheet 20000			

Tube Sleeves



Imperial

0014	To Suit Tube OD
4JITS	1/4"
5JITS	5/16"
6JITS	3/8"
8JITS	1/2"
10JITS	5/8"
12JITS	3/4"
16JITS	1"
20JITS	1.1/4"
24JITS	1.1/2"
Tech Sheet 20000	



Metric

0014	To Suit Tube OD mm
6JMTS	6
8JMTS	8
10JMTS	10
12JMTS	12
14JMTS	14
15JMTS	15
16JMTS	16
18JMTS	18
20JMTS	20
25JMTS	25
30JMTS	30
38JMTS	38
Tech Sheet 20000	

ORFS HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

Straight Adaptors



Male x Male Adaptor

0014	Thread
9305-04	9/16"
9305-06	11/16"
9305-08	13/16"
9305-10	1"
9305-12	1.3/16"
9305-16	1.7/16"
9305-20	1.11/16"
Tech Sheet 20000	



Male x Male Bulkhead Only

0014	Thread
9325-04	9/16"
9325-06	11/16"
9325-08	13/16"
9325-10	1"
9325-12	1.3/16"
9325-16	1.7/16"
9325-20	1.11/16"
Tech Sheet 20000	



Bulkhead Locknut

0014	Thread
9925-04	9/16"
9925-06	11/16"
9925-08	13/16"
9925-10	1"
9925-12	1.3/16"
9925-16	1.7/16"
9925-20	1.11/16"
Tech Sheet 20000	



Male x Swivel Female

0014	Male Thread	Female Thread
9015-04-06AS	9/16"	11/16"
9015-06-08AS	11/16"	13/16"
9015-10-12AS	1"	1.3/16"
9015-12-16AS	1.3/16"	1.7/16"
9015-16-20AS	1.7/16"	1.11/16"
9015-08-10AS	13/16"	1"
9015-04-12AS	9/16"	13/16"
9015-06-12AS	11/16"	1.3/16"
Tech Sheet 20000		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ORFS HYDRAULIC ADAPTORS

BURNETT & HILLMAN
HYDRAULIC ADAPTOR & UK MANUFACTURER

90º Elbows

Male x Male 90° Forged Compact Elbow



0014	Thread
9505-04-04	9/16"
9505-06-06	11/16"
9505-08-08	13/16"
9505-10-10	1"
9505-12-12	1.3/16"
9505-16-16	1.7/16"
Tech Sheet 20000	

Male x Male 90° Forged Bulkhead



0014	Thread
9525-04-04	9/16"
9525-06-06	11/16"
9525-08-08	13/16"
9525-10-10	1"
9525-12-12	1.3/16"
Tech Sheet 20000	

Male x Swivel Female 90° Forged Compact Elbow



0014	Thread
9506-04-04	9/16"
9506-06-06	11/16"
9506-08-08	13/16"
9506-10-10	1"
9506-12-12	1.3/16"
9506-16-16	1.7/16"
9506-20-20	1.11/16"
9506-24-24	2"
Tech Sheet 20000	

Male x UNF Male 90° Positional Forged Elbow with O-Ring



0014	Thread	Thread
9515-04-04	9/16"	7/16"
9515-04-06	9/16"	9/16"
9515-06-06	11/16"	9/16"
9515-08-08	13/16"	3/4"
9515-10-10	1"	7/8"
9515-10-12	1"	1.1/16"
9515-12-08	1.3/16"	3/4"
9515-12-12	1.3/16"	1.1/16"
9515-16-16	1.7/16"	1.5/16"
Tech Sheet 20000		

Male x BSPP Male 90° Positional Forged Elbow with O-Ring



0014	Thread	Thread
9515-04-04B	9/16"	1/4"
9515-08-06B	13/16"	3/8"
9515-10-08B	1"	1/2"
9515-12-12B	1.3/16"	3/4"
9515-16-16B	1.7/16"	1"
Tech Sheet 20000		

45º Elbows

Male x Swivel Female 45° Forged Compact Elbow



0014	Thread
9356-04-04	9/16"
9356-06-06	11/16"
9356-08-08	13/16"
9356-10-10	1"
9356-12-12	1.3/16"
9356-16-16	1.7/16"
9356-20-20	1.11/16"
9356-24-24	2"
Tech Sheet 20000	

Tees

Seal: Nitrile

Forged Male Tee



0014	Thread
9705-04-04-04	9/16"
9705-06-06-06	11/16"
9705-08-08-08	13/16"
9705-10-10-10	1"
9705-12-12-12	1.3/16"
9705-16-16-16	1.7/16"
Tech Sheet 20000	

Male x Male x Swivel Female Forged Branch Tee




0014	Thread
9707-04-04-04	9/16"
9707-06-06-06	11/16"
9707-08-08-08	13/16"
9707-10-10-10	1"
9707-12-12-12	1.3/16"
9707-16-16-16	1.7/16"
9707-20-20-20	1.11/16"
Tech Sheet 20000	

Male x Female x Male Swivel Forged Run Tee



0014	Thread
9706-04-04-04	9/16"
9706-06-06-06	11/16"
9706-08-08-08	13/16"
9706-10-10-10	1"
9706-12-12-12	1.3/16"
9706-16-16-16	1.7/16"
9706-20-20-20	1.11/16"
Tech Sheet 20000	

Male Tee UNF Positional on Branch Forged with O-Ring



0014	Thread A	Thread B	Thread C
9715-06-06-06	11/16"	11/16"	9/16"
9715-08-08-08	13/16"	13/16"	3/4"
9715-10-10-10	1"	1"	7/8"
9715-12-12-12	1.3/16"	1.3/16"	1.1/16"
Tech Sheet 20000			

Male Tee UNF Positional on Run with O-Ring



0014	Thread A	Thread B	Thread C
9716-04-04-04	9/16"	9/16"	7/16"
9716-06-06-06	11/16"	11/16"	9/16"
9716-08-08-08	13/16"	13/16"	3/4"
9716-10-10-10	1"	1"	7/8"
9716-12-12-12	1.3/16"	1.3/16"	1.1/16"
Tech Sheet 20000			

Caps



Female Thread

0014	Thread
9129-04	9/16"
9129-06	11/16"
9129-08	13/16"
9129-10	1"
9129-12	1.3/16"
9129-16	1.7/16"
9129-20	1.11/16"
9129-24	2"
Tech Sheet 20000	

FAC
Fluid-Air Components Ltd



HYDRAULIC ADAPTORS
1/8"-3/4" 680 BAR 1"-2" 500 BAR

Standard hydraulic adaptors do not adhere to the working pressure of multi spiral hose. Please use KR500 Hydraulic Adaptors for high pressure and multi spiral applications.
Also available in stainless steel and Hiduron upon request.

Maximum Working Pressure:
1/8" to 3/4" 680 bar
1" to 2" 500 bar

Equal Male Unions



BSPP

0450	Thread
KREU2	1/8"
KREU4	1/4"
KREU6	3/8"
KREU8	1/2"
KREU10	5/8"
KREU12	3/4"
KREU16	1"
KREU20	1.1/4"
KREU24	1.1/2"
KREU32	2"
Tech Sheet 10728	



BSPP x BSPT

0450	Thread
KREUPT2	1/8"
KREUPT4	1/4"
KREUPT6	3/8"
KREUPT8	1/2"
KREUPT12	3/4"
KREUPT16	1"
KREUPT20	1.1/4"
KREUPT24	1.1/2"
KREUPT32	2"
Tech Sheet 10729	



BSPP x NPT

0450	Thread
KREUPAT2	1/8"
KREUPAT4	1/4"
KREUPAT6	3/8"
KREUPAT8	1/2"
KREUPAT12	3/4"
KREUPAT16	1"
KREUPAT20	1.1/4"
Tech Sheet 10730	

Unequal Male Unions



BSPP

0450	Thread	Thread
KRUU4-2	1/4"	1/8"
KRUU6-4	3/8"	1/4"
KRUU8-4	1/2"	1/4"
KRUU8-6	1/2"	3/8"
KRUU10-4	5/8"	1/4"
KRUU10-6	5/8"	3/8"
KRUU10-8	5/8"	1/2"
KRUU12-6	3/4"	3/8"
KRUU12-8	3/4"	1/2"
KRUU12-10	3/4"	5/8"
KRUU16-8	1"	1/2"
KRUU16-10	1"	5/8"
KRUU16-12	1"	3/4"
KRUU16-14	1"	7/8"
KRUU20-12	1.1/4"	3/4"
KRUU20-16	1.1/4"	1"
KRUU24-16	1.1/2"	1"
KRUU24-20	1.1/2"	1.1/4"
KRUU32-16	2"	1"
KRUU32-20	2"	1.1/4"
KRUU32-24	2"	1.1/2"
Tech Sheet 10731		

Equal Male Bulkhead Unions



BSPP

0450	Thread
KREUBH4	1/4"
KREUBH6	3/8"
KREUBH8	1/2"
KREUBH10	5/8"
KREUBH12	3/4"
KREUBH16	1"
KREUBH20	1.1/4"
KREUBH24	1.1/2"
Tech Sheet 10732	

Reducing Bushes



BSPP

0450	Thread	Thread
KRRB4-2	1/4"	1/8"
KRRB6-2	3/8"	1/8"
KRRB6-4	3/8"	1/4"
KRRB8-2	1/2"	1/8"
KRRB8-4	1/2"	1/4"
KRRB8-6	1/2"	3/8"
KRRB10-8	5/8"	1/2"
KRRB12-4	3/4"	1/4"
KRRB12-6	3/4"	3/8"
KRRB12-8	3/4"	1/2"
KRRB16-4	1"	1/4"
KRRB16-6	1"	3/8"
KRRB16-8	1"	1/2"
KRRB16-12	1"	3/4"
KRRB20-4	1.1/4"	1/4"
KRRB20-6	1.1/4"	3/8"
KRRB20-8	1.1/4"	1/2"
KRRB20-12	1.1/4"	3/4"
KRRB20-16	1.1/4"	1"
KRRB24-8	1.1/2"	1/2"
KRRB24-12	1.1/2"	3/4"
KRRB24-16	1.1/2"	1"
KRRB24-20	1.1/2"	1.1/4"
KRRB32-16	2"	1"
KRRB32-20	2"	1.1/4"
KRRB32-24	2"	1.1/2"
Tech Sheet 10733		

Bleed Valve



BSPP

0450	Thread
KRBV2	1/8"
Tech Sheet 10799	

Minimum order quantity on selected items may apply

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Over 2. years of proven high performance with a comprehensive history of product approvals and 3rd party accreditations.



HYDRAULIC ADAPTORS
1/8"-3/4" 680 BAR 1"-2" 500 BAR

KR 500

Standard hydraulic adaptors do not adhere to the working pressure of multi spiral hose. Please use KR500 Hydraulic Adaptors for high pressure and multi spiral applications.
Also available in stainless steel and Hiduron upon request.

Maximum Working Pressure:
1/8" to 3/4" 680 bar
1" to 2" 500 bar

Male Elbows



BSPP

0450	Thread
KREME4	1/4"
KREME6	3/8"
KREME8	1/2"
KREME12	3/4"
KREME16	1"
KREME20	1.1/4"
KREME24	1.1/2"
Tech Sheet 10734	

Fixed Bushes



BSPT Male x BSPP Female

0450	Male Thread	Female Thread
KRAB4T-4	1/4"	1/4"
KRAB6T-4	3/8"	1/4"
KRAB6T-6	3/8"	3/8"
KRAB8T-8	1/2"	1/2"
KRAB12T-12	3/4"	3/4"
KRAB16T-16	1"	1"
KRAB24T-24	1.1/2"	1.1/2"
Tech Sheet 10736		

Female Tees



BSPP

0450	Thread
KREFT2	1/8"
KREFT4	1/4"
KREFT6	3/8"
KREFT8	1/2"
KREFT12	3/4"
KREFT16	1"
KREFT20	1.1/4"
KREFT24	1.1/2"
KREFT32	2"
Tech Sheet 10738	

Female Elbows



BSPP

0450	Thread
KREFE2	1/8"
KREFE4	1/4"
KREFE6	3/8"
KREFE8	1/2"
KREFE12	3/4"
KREFE16	1"
KREFE20	1.1/4"
KREFE24	1.1/2"
KREFE32	2"
Tech Sheet 10735	

Female Hexagon Sockets



BSPP

0450	Thread	Thread
KRFA4-2	1/4"	1/8"
KRFA4-4	1/4"	1/4"
KRFA6-2	3/8"	1/8"
KRFA6-4	3/8"	1/4"
KRFA6-6	3/8"	3/8"
KRFA8-2	1/2"	1/8"
KRFA8-4	1/2"	1/4"
KRFA8-6	1/2"	3/8"
KRFA8-8	1/2"	1/2"
KRFA12-12	3/4"	3/4"
KRFA16-16	1"	1"
KRFA20-20	1.1/4"	1.1/4"
Tech Sheet 10737		

Female Branch Tees



BSPP

0450	Thread
KRFOMT4	1/4"
KRFOMT6	3/8"
KRFOMT8	1/2"
KRFOMT12	3/4"
KRFOMT16	1"
KRFOMT20	1.1/4"
KRFOMT24	1.1/2"
Tech Sheet 10739	

Minimum order quantity on selected items may apply

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC ADAPTORS
1/8"-3/4" 680 BAR 1"-2" 500 BAR

Standard hydraulic adaptors do not adhere to the working pressure of multi spiral hose. Please use KR500 Hydraulic Adaptors for high pressure and multi spiral applications.
Also available in stainless steel and Hiduron upon request.

Maximum Working Pressure:
1/8" to 3/4" 680 bar
1" to 2" 500 bar

Plugs



BSPP


0450	Thread
KRP2	1/8"
KRP4	1/4"
KRP6	3/8"
KRP8	1/2"
KRP10	5/8"
KRP12	3/4"
KRP16	1"
KRP20	1.1/4"
KRP24	1.1/2"
KRP32	2"
Tech Sheet 10740	



BSPT

0450	Thread
KRPT2	1/8"
KRPT4	1/4"
KRPT6	3/8"
KRPT8	1/2"
KRPT12	3/4"
KRPT16	1"
KRPT20	1.1/4"
Tech Sheet 10741	

Stud Standpipes



OD Imperial to BSPP

0450	OD	Thread
KR4-2SSAR	1/4"	1/8"
KR4-4SSAR	1/4"	1/4"
KR5-2SSAR	5/16"	1/8"
KR5-4SSAR	5/16"	1/4"
KR5-6SSAR	5/16"	3/8"
KR6-4SSAR	3/8"	1/4"
KR6-6SSAR	3/8"	3/8"
KR8-4SSAR	1/2"	1/4"
KR8-6SSAR	1/2"	3/8"
KR8-8SSAR	1/2"	1/2"
KR10-6SSAR	5/8"	3/8"
KR10-8SSAR	5/8"	1/2"
KR10-12SSAR	5/8"	3/4"
KR12-8SSAR	3/4"	1/2"
KR12-12SSAR	3/4"	3/4"
KR14-8SSAR	7/8"	1/2"
KR14-12SSAR	7/8"	3/4"
KR14-16SSAR	7/8"	1"
KR16-12SSAR	1"	3/4"
KR16-16SSAR	1"	1"
KR20-12SSAR	1.1/4"	3/4"
KR20-16SSAR	1.1/4"	1"
KR20-20SSAR	1.1/4"	1.1/4"
KR32-24SSAR	2"	1.1/2"
KR32-32SSAR	2"	2"
Tech Sheet 10743		



OD Metric to BSPP

0450	OD mm	Thread
KRM6-2SSAR	6	1/8"
KRM6-4SSAR	6	1/4"
KRM8-2SSAR	8	1/8"
KRM8-4SSAR	8	1/4"
KRM8-6SSAR	8	3/8"
KRM10-4SSAR	10	1/4"
KRM10-6SSAR	10	3/8"
KRM12-4SSAR	12	1/4"
KRM12-6SSAR	12	3/8"
KRM12-8SSAR	12	1/2"
KRM16-6SSAR	16	3/8"
KRM16-8SSAR	16	1/2"
KRM16-12SSAR	16	3/4"
KRM20-8SSAR	20	1/2"
KRM20-12SSAR	20	3/4"
KRM22-8SSAR	22	1/2"
KRM22-12SSAR	22	3/4"
KRM22-16SSAR	22	1"
KRM25-12SSAR	25	3/4"
KRM25-16SSAR	25	1"
KRM30-12SSAR	30	3/4"
KRM30-16SSAR	30	1"
KRM30-20SSAR	30	1.1/4"
KRM38-16SSAR	38	1"
KRM38-20SSAR	38	1.1/4"
KRM38-24SSAR	38	1.1/2"
KRM50-24SSAR	50	1.1/2"
KRM50-32SSAR	50	2"
Tech Sheet 10744		

Gauge Adaptors



BSPP

0450	Thread	Thread
KRGA4-4	1/4"	1/4"
KRGA6-4	3/8"	1/4"
KRGA8-4	1/2"	1/4"
Tech Sheet 10742		

Banjos

Seals sold separately



BSPP

0450	Thread
KRA4-4BJ	1/4"
KRA6-6BJ	3/8"
KRA8-8BJ	1/2"
KRA12-12BJ	3/4"
Tech Sheet 10745	

Bleed Plugs (Air)



BSPP

0450	Thread
KRP2AB	1/8"
Tech Sheet 10746	

Minimum order quantity on selected items may apply

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PANAM

Stainless Steel Adaptors





HYDRAULIC STAINLESS STEEL ADAPTORS

stainless steel

PANAM

Male x Male Straight Adaptors



BSPP x BSPP

0044	Thread	Thread
2025-1401	1/8"	1/8"
2025-1419	1/4"	1/8"
2025-1427	1/4"	1/4"
2025-1435	3/8"	1/8"
2025-1443	3/8"	1/4"
2025-1450	3/8"	3/8"
2025-1468	1/2"	1/4"
2025-1476	1/2"	3/8"
2025-1484	1/2"	1/2"
2025-1495	5/8"	1/2"
2025-1505	5/8"	5/8"
2025-1520	3/4"	1/4"
2025-1526	3/4"	3/8"
2025-1534	3/4"	1/2"
2025-1538	3/4"	5/8"
2025-1559	3/4"	3/4"
2025-1567	1"	1/2"
2025-1572	1"	5/8"
2025-1583	1"	3/4"
2025-1591	1"	1"
2025-1595	1.1/4"	3/4"
2025-1600	1.1/4"	1"
2025-1609	1.1/4"	1.1/4"
2025-1611	1.1/2"	1"
2025-1615	1.1/2"	1.1/4"
2025-1617	1.1/2"	1.1/2"
2025-1620	2"	1.1/2"
2025-1625	2"	2"
Tech Sheet 20884		



BSPP x BSPT

0044	Thread
2033-9693	1/4"
2033-9761	3/8"
2033-9719	1/2"
2033-9727	3/4"
2033-9735	1"
Tech Sheet 20884	



BSPP x NPT

0044	BSPP Thread	NPT Thread
2025-1633	1/8"	1/8"
2025-1636	1/8"	1/4"
2025-1639	1/4"	1/8"
2025-1641	1/4"	1/4"
2025-1643	1/4"	3/8"
2025-1656	3/8"	1/4"
2025-1658	3/8"	3/8"
2025-1661	3/8"	1/2"
2025-1671	1/2"	3/8"
2025-1674	1/2"	1/2"
2025-1677	5/8"	1/2"
2025-1679	5/8"	3/4"
2025-1681	3/4"	1/2"
2025-1682	3/4"	3/4"
2025-1684	3/4"	1"
2025-1687	1"	3/4"
2025-1690	1"	1"
2025-1700	1.1/4"	1.1/4"
2025-1710	1.1/2"	1.1/2"
2025-1720	2"	2"
Tech Sheet 20884		



BSPT x BSPT

0044	Thread	Thread
2025-1708	1/8"	1/8"
2025-1715	1/4"	1/8"
2025-1724	1/4"	1/4"
2025-1727	3/8"	1/8"
2025-1732	3/8"	1/4"
2025-1740	3/8"	3/8"
2025-1845	1/2"	1/8"
2025-1852	1/2"	1/4"
2025-1856	1/2"	3/8"
2025-1865	1/2"	1/2"
2025-1881	3/4"	1/8"
2025-1885	3/4"	1/4"
2025-1889	3/4"	3/8"
2025-1894	3/4"	1/2"
2025-1898	3/4"	3/4"
2025-1905	1"	1/8"
2025-1910	1"	1/4"
2025-1915	1"	3/8"
2025-1920	1"	1/2"
2025-1925	1"	3/4"
2025-1931	1"	1"
2025-1935	1.1/4"	1"
2025-1940	1.1/4"	1.1/4"
2025-1945	1.1/2"	1"
2025-1950	1.1/2"	1.1/2"
2025-1956	2"	1"
2025-1960	2"	1.1/2"
2025-1965	2"	2"
Tech Sheet 20884		

Male x Female Straight Adaptors



Male x Female Swivel, BSPP

0044	Male Thread	Female Thread
2025-1930	1/8"	1/8"
2025-1948	1/4"	1/4"
2025-1955	1/4"	3/8"
2025-1961	1/4"	1/2"
2025-1963	3/8"	1/4"
2025-1971	3/8"	3/8"
2025-1989	3/8"	1/2"
2025-1997	1/2"	3/8"
2025-2003	1/2"	1/2"
2025-2020	1/2"	3/4"
2025-2029	3/4"	1/2"
2025-2037	3/4"	3/4"
2025-2043	3/4"	1"
2025-2060	1"	1"
Tech Sheet 20884		

Female Swivel, BSPP x BSPT Male

0044	Thread
2033-9862	1/8"
2033-9867	1/4"
2033-9875	3/8"
2033-9883	1/2"
2033-9891	3/4"
2033-9896	1"
Tech Sheet 20884	



Male x Female Fixed, BSPP

0044	Male Thread	Female Thread
2025-8121	1/8"	1/8"
2025-8131	1/4"	1/8"
2025-8142	1/4"	1/4"
2025-8151	3/8"	1/8"
2025-8161	3/8"	1/4"
2025-8171	3/8"	3/8"
2025-8181	1/2"	1/4"
2025-8201	1/2"	3/8"
2025-8211	1/2"	1/2"
2025-8191	3/4"	1/4"
2025-8221	3/4"	3/8"
2025-8231	3/4"	1/2"
2025-8241	3/4"	3/4"
2025-8251	1"	1/2"
2025-8261	1"	1"
2025-8271	1"	3/4"
2025-8281	1.1/4"	1/2"
2025-8291	1.1/4"	3/4"
2025-8301	1.1/4"	1"
2025-8311	1.1/4"	1.1/4"
2025-8321	1.1/2"	3/4"
2025-8331	1.1/2"	1"
2025-8341	1.1/2"	1.1/2"
2025-8351	1.1/2"	1.1/4"
2025-8361	2"	2"
Tech Sheet 20884		

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS

stainless steel

PANAM

Female x Female Straight Adaptors



Swivel, BSPP

0044	Thread	Thread
2025-2078	1/4"	1/4"
2025-2082	3/8"	1/4"
2025-2086	3/8"	3/8"
2025-2089	1/2"	1/4"
2025-2093	1/2"	3/8"
2025-2094	1/2"	1/2"
2025-2100	5/8"	5/8"
2025-2122	3/4"	1/2"
2025-2132	3/4"	3/4"
2025-2110	1"	1"

Tech Sheet 20884

Fixed Female Hexagon Socket, BSPP



0044	Thread
2025-2466	1/8"
2025-2474	1/4"
2025-2482	3/8"
2025-2490	1/2"
2025-2508	3/4"
2025-2516	1"

Tech Sheet 20884

Elbows



Equal Elbow, BSPP

0044	Thread
2033-9922	1/8"
2033-9933	1/4"
2033-9941	3/8"
2033-9958	1/2"
2033-9962	5/8"
2033-9963	3/4"
2033-9974	1"
2033-9982	1.1/4"
2033-9992	1.1/2"

Tech Sheet 20884

Male x Female Swivel, BSPP



0044	Thread
2025-2185	1/8"
2025-2193	1/4"
2025-2201	3/8"
2025-2219	1/2"
2025-2223	5/8"
2025-2227	3/4"
2025-2232	1"
2025-2240	1.1/4"
2025-2245	1.1/2"

Tech Sheet 20884

Female Swivel, BSPP



0044	Thread
2025-2128	1/8"
2025-2136	1/4"
2025-2151	1/2"
2025-2169	3/4"

Tech Sheet 20884

Tees



Male, BSPP

0044	Thread
2025-2321	1/8"
2025-2326	1/4"
2025-2334	3/8"
2025-2342	1/2"
2025-2449	3/4"
2025-2354	1"

Tech Sheet 20884



Female Swivel, BSPP

0044	Thread
2025-2250	1/4"
2025-2258	3/8"
2025-2263	1/2"
2025-2273	5/8"
2025-2283	3/4"
2025-2293	1"

Tech Sheet 20884



Female Swivel Branch, BSPP

0044	Thread
2025-4001	1/8"
2025-4011	1/4"
2025-4021	3/8"
2025-4031	1/2"
2025-4041	3/4"
2025-4051	1"

Tech Sheet 20884



Female Swivel Run, BSPP

0044	Thread
2025-4501	1/8"
2025-4511	1/4"
2025-4521	3/8"
2025-4531	1/2"
2025-4541	3/4"
2025-4551	1"

Tech Sheet 20884

Bulkhead complete with Locknut



BSPP

0044	Thread
2025-2391	1/4"
2025-2409	3/8"
2025-2417	1/2"
2025-2425	5/8"
2025-2433	3/4"
2025-2441	1"
2025-2445	1.1/4"
2025-2450	1.1/2"

Tech Sheet 20884

Plugs



BSPP

0044	Thread
2033-4002	1/8"
2033-4012	1/4"
2033-4022	3/8"
2033-4032	1/2"
2033-4042	5/8"
2033-4052	3/4"
2033-4062	1"
2033-4072	1.1/4"
2033-4082	1.1/2"
2033-4092	2"

Tech Sheet 20884



BSPT

0044	Thread
2025-2524	1/8"
2025-2532	1/4"
2025-2540	3/8"
2025-2557	1/2"
2025-2565	3/4"
2025-2573	1"
2025-2582	1.1/4"
2025-2592	1.1/2"
2025-2602	2"

Tech Sheet 20884

Caps



BSPP

0044	Thread
2033-8301	1/8"
2033-8311	1/4"
2033-8321	3/8"
2033-8331	1/2"
2033-8341	3/4"
2033-8351	1"

Tech Sheet 20884

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 PRECISION INSTRUMENTATION PIPE FITTINGS

stainless steel

PANAM

Hexagon Nipples



Male x Male, NPT

0342	Thread
PHN-01	1/16"
PHN-02	1/8"
PHN-04	1/4"
PHN-06	3/8"
PHN-08	1/2"
PHN-12	3/4"
PHN-16	1"
Tech Sheet 20885	

Hexagon Nipples, Long



Male x Male, NPT

0342	Thread	Length
PHNL-02-L1.5	1/8"	1.5"
PHNL-02-L2	1/8"	2"
PHNL-02-L3	1/8"	3"
PHNL-02-L4	1/8"	4"
PHNL-02-L6	1/8"	6"
PHNL-04-L1.5	1/4"	1.5"
PHNL-04-L2	1/4"	2"
PHNL-04-L3	1/4"	3"
PHNL-04-L4	1/4"	4"
PHNL-04-L6	1/4"	6"
PHNL-06-L1.5	3/8"	1.5"
PHNL-06-L2	3/8"	2"
PHNL-06-L3	3/8"	3"
PHNL-06-L4	3/8"	4"
PHNL-06-L6	3/8"	6"
PHNL-08-L1.5	1/2"	1.5"
PHNL-08-L2	1/2"	2"
PHNL-08-L3	1/2"	3"
PHNL-08-L4	1/2"	4"
PHNL-08-L6	1/2"	6"
PHNL-12-L2	3/4"	2"
PHNL-12-L3	3/4"	3"
PHNL-12-L4	3/4"	4"
PHNL-12-L6	3/4"	6"
PHNL-16-L1.5	1"	1.5"
PHNL-16-L2	1"	2"
PHNL-16-L3	1"	3"
PHNL-16-L4	1"	4"
PHNL-16-L6	1"	6"
Tech Sheet 20885		

Reducing Hexagon Nipples



Male x Male, NPT

0342	Thread	Thread
PRHN-02-01	1/8"	1/16"
PRHN-04-02	1/4"	1/8"
PRHN-06-02	3/8"	1/8"
PRHN-06-04	3/8"	1/4"
PRHN-08-02	1/2"	1/8"
PRHN-08-04	1/2"	1/4"
PRHN-08-06	1/2"	3/8"
PRHN-12-06	3/4"	1/4"
PRHN-12-08	3/4"	1/2"
PRHN-16-08	1"	1/2"
PRHN-16-12	1"	3/4"
Tech Sheet 20885		

Hexagon Coupling



Female x Female, NPT

0342	Thread
PHC-02	1/8"
PHC-04	1/4"
PHC-06	3/8"
PHC-08	1/2"
PHC-12	3/4"
PHC-16	1"
Tech Sheet 20885	

Reducing Hexagon Couplings



Female x Female, NPT

0342	Thread	Thread
PRC-04-02	1/4"	1/8"
PRC-06-04	3/8"	1/4"
PRC-08-02	1/2"	1/8"
PRC-08-04	1/2"	1/4"
PRC-08-06	1/2"	3/8"
PRC-12-04	3/4"	1/4"
PRC-12-08	3/4"	1/2"
PRC-16-08	1"	1/2"
Tech Sheet 20885		

Equal Male x Female Adaptors



Male x Female, NPT

0342	Thread
PPA-02	1/8"
PPA-04	1/4"
PPA-06	3/8"
PPA-08	1/2"
PPA-12	3/4"
PPA-16	1"
Tech Sheet 20885	

Reducing Male x Female Adaptors



Male x Female, NPT

0342	Male Thread	Female Thread
PRA-02-01	1/16"	1/8"
PRA-04-02	1/8"	1/4"
PRA-06-02	1/8"	3/8"
PRA-06-04	1/4"	3/8"
PRA-08-02	1/8"	1/2"
PRA-08-04	1/4"	1/2"
PRA-08-06	3/8"	1/2"
PRA-12-04	1/4"	3/4"
PRA-12-06	3/8"	3/4"
PRA-12-08	1/2"	3/4"
PRA-16-04	1/4"	1"
PRA-16-08	1/2"	1"
PRA-16-12	3/4"	1"
Tech Sheet 20885		

Gauge Adaptor



Male NPT x Female, BSPP

0342	Male Thread	Female Thread
PGA-04-04	1/4"	1/4"
PGA-06-06	3/8"	3/8"
PGA-08-08	1/2"	1/2"
Tech Sheet 20885		

FAC
Fluid-Air Components Ltd

316 PRECISION INSTRUMENTATION PIPE FITTINGS

stainless steel

PANAM

Reducing Bushes



Male x Female, NPT

0342	Male Thread	Female Thread
PRB-02-01	1/8"	1/16"
PRB-04-02	1/4"	1/8"
PRB-06-02	3/8"	1/8"
PRB-06-04	3/8"	1/4"
PRB-08-02	1/2"	1/8"
PRB-08-04	1/2"	1/4"
PRB-08-06	1/2"	3/8"
PRB-12-04	3/4"	1/4"
PRB-12-06	3/4"	3/8"
PRB-12-08	3/4"	1/2"
PRB-16-04	1"	1/4"
PRB-16-06	1"	3/8"
PRB-16-08	1"	1/2"
PRB-16-12	1"	3/4"
Tech Sheet 20885		

Pipe Caps



NPT

0342	Thread
PCP-02	1/8"
PCP-04	1/4"
PCP-06	3/8"
PCP-08	1/2"
PCP-12	3/4"
PCP-16	1"
Tech Sheet 20885	

Pipe Plugs



NPT

0342	Thread
PP-01	1/16"
PP-02	1/8"
PP-04	1/4"
PP-06	3/8"
PP-08	1/2"
PP-12	3/4"
PP-16	1"
Tech Sheet 20885	

Equal Elbows



Female, NPT

0342	Thread
PPFE-02	1/8"
PPFE-04	1/4"
PPFE-06	3/8"
PPFE-08	1/2"
PPFE-12	3/4"
PPFE-16	1"
Tech Sheet 20885	



Male, NPT

0342	Thread
PPME-02	1/8"
PPME-04	1/4"
PPME-06	3/8"
PPME-08	1/2"
Tech Sheet 20885	



Male x Female, NPT

0342	Thread
PSE-01	1/16"
PSE-02	1/8"
PSE-04	1/4"
PSE-06	3/8"
PSE-08	1/2"
PSE-12	3/4"
PSE-16	1"
Tech Sheet 20885	

Equal Tees



Female, NPT

0342	Thread
PFT-02	1/8"
PFT-04	1/4"
PFT-06	3/8"
PFT-08	1/2"
PFT-12	3/4"
PFT-16	1"
Tech Sheet 20885	



Male, NPT

0342	Thread
PMT-02	1/8"
PMT-04	1/4"
PMT-06	3/8"
PMT-08	1/2"
Tech Sheet 20885	

Branch Tees



Female x Male, NPT

0342	Thread
PBT-02	1/8"
PBT-04	1/4"
PBT-06	3/8"
PBT-08	1/2"
Tech Sheet 20885	

Equal Crosses



Female, NPT

0342	Thread
PPC-02	1/8"
PPC-04	1/4"
PPC-06	3/8"
PPC-08	1/2"
PPC-12	3/4"
PPC-16	1"
Tech Sheet 20885	

FAC
Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

Male x Male Straight Adaptors



BSPP x BSPP

0339	Thread	Thread
2G-2G-MM-10K	1/8"	1/8"
2G-4G-MM-10K	1/8"	1/4"
2G-6G-MM-10K	1/8"	3/8"
2G-8G-MM-10K	1/8"	1/2"
2G-12G-MM-10K	1/8"	3/4"
2G-16G-MM-10K	1/8"	1"
4G-4G-MM-10K	1/4"	1/4"
4G-6G-MM-10K	1/4"	3/8"
4G-8G-MM-10K	1/4"	1/2"
4G-12G-MM-10K	1/4"	3/4"
4G-16G-MM-10K	1/4"	1"
6G-6G-MM-10K	3/8"	3/8"
6G-8G-MM-10K	3/8"	1/2"
6G-12G-MM-10K	3/8"	3/4"
6G-16G-MM-10K	3/8"	1"
8G-8G-MM-10K	1/2"	1/2"
8G-12G-MM-10K	1/2"	3/4"
8G-16G-MM-10K	1/2"	1"
12G-12G-MM-10K	3/4"	3/4"
12G-16G-MM-10K	3/4"	1"
16G-16G-MM-10K	1"	1"
Tech Sheet 20887		



BSPP x NPT

0339	Thread	Thread
2G-2N-MM-10K	1/8"	1/8"
2G-4N-MM-10K	1/8"	1/4"
2G-6N-MM-10K	1/8"	3/8"
2G-8N-MM-10K	1/8"	1/2"
2G-12N-MM-10K	1/8"	3/4"
2G-16N-MM-10K	1/8"	1"
4G-2N-MM-10K	1/4"	1/8"
4G-4N-MM-10K	1/4"	1/4"
4G-6N-MM-10K	1/4"	3/8"
4G-8N-MM-10K	1/4"	1/2"
4G-12N-MM-10K	1/4"	3/4"
4G-16N-MM-10K	1/4"	1"
6G-4N-MM-10K	3/8"	1/4"
6G-6N-MM-10K	3/8"	3/8"
6G-8N-MM-10K	3/8"	1/2"
6G-12N-MM-10K	3/8"	3/4"
6G-16N-MM-10K	3/8"	1"
8G-4N-MM-10K	1/2"	1/4"
8G-6N-MM-10K	1/2"	3/8"
8G-8N-MM-10K	1/2"	1/2"
8G-12N-MM-10K	1/2"	3/4"
8G-16N-MM-10K	1/2"	1"
12G-12N-MM-10K	3/4"	3/4"
12G-16N-MM-10K	3/4"	1"
16G-16N-MM-10K	1"	1"
Tech Sheet 20887		



BSPP x JIC

0339	Thread	Thread
2G-4J-MM-10K	1/8"	7/16"
2G-6J-MM-10K	1/8"	9/16"
4G-4J-MM-10K	1/4"	7/16"
4G-6J-MM-10K	1/4"	9/16"
4G-8J-MM-10K	1/4"	3/4"
6G-4J-MM-10K	3/8"	7/16"
6G-6J-MM-10K	3/8"	9/16"
6G-8J-MM-10K	3/8"	3/4"
6G-10J-MM-10K	3/8"	7/8"
6G-12J-MM-10K	3/8"	1.1/16"
8G-4J-MM-10K	1/2"	7/16"
8G-8J-MM-10K	1/2"	3/4"
8G-10J-MM-10K	1/2"	7/8"
8G-12J-MM-10K	1/2"	1.1/16"
8G-16J-MM-10K	1/2"	1.5/16"
12G-8J-MM-10K	3/4"	3/4"
12G-10J-MM-10K	3/4"	7/8"
12G-12J-MM-10K	3/4"	1.1/16"
12G-16J-MM-10K	3/4"	1.5/16"
16G-10J-MM-10K	1"	7/8"
16G-12J-MM-10K	1"	1.1/16"
16G-16J-MM-10K	1"	1.5/16"
Tech Sheet 20887		



NPT x NPT

0339	Thread	Thread
2N-2N-MM-10K	1/8"	1/8"
2N-4N-MM-10K	1/8"	1/4"
4N-4N-MM-10K	1/4"	1/4"
4N-6N-MM-10K	1/4"	3/8"
4N-8N-MM-10K	1/4"	1/2"
6N-2N-MM-10K	3/8"	1/8"
6N-6N-MM-10K	3/8"	3/8"
6N-8N-MM-10K	3/8"	1/2"
8N-2N-MM-10K	1/2"	1/8"
8N-8N-MM-10K	1/2"	1/2"
12N-2N-MM-10K	3/4"	1/8"
12N-4N-MM-10K	3/4"	1/4"
12N-6N-MM-10K	3/4"	3/8"
12N-8N-MM-10K	3/4"	1/2"
12N-12N-MM-10K	3/4"	3/4"
16N-2N-MM-10K	1"	1/8"
16N-4N-MM-10K	1"	1/4"
16N-6N-MM-10K	1"	3/8"
16N-8N-MM-10K	1"	1/2"
16N-12N-MM-10K	1"	3/4"
16N-16N-MM-10K	1"	1"
Tech Sheet 20887		

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)



NPT x JIC

0339	Thread	Thread
2N-2J-MM-10K	1/8"	5/16"
2N-4J-MM-10K	1/8"	7/16"
4N-4J-MM-10K	1/4"	7/16"
4N-6J-MM-10K	1/4"	9/16"
4N-8J-MM-10K	1/4"	3/4"
6N-4J-MM-10K	3/8"	7/16"
6N-6J-MM-10K	3/8"	9/16"
6N-8J-MM-10K	3/8"	3/4"
6N-12J-MM-10K	3/8"	1.1/16"
8N-4J-MM-10K	1/2"	7/16"
8N-6J-MM-10K	1/2"	9/16"
8N-8J-MM-10K	1/2"	3/4"
8N-12J-MM-10K	1/2"	1.1/16"
12N-8J-MM-10K	3/4"	3/4"
12N-12J-MM-10K	3/4"	1.1/16"
12N-16J-MM-10K	3/4"	1.5/16"
16N-12J-MM-10K	1"	1.1/16"
16N-16J-MM-10K	1"	1.5/16"
Tech Sheet 20887		



JIC x JIC

0339	Thread	Thread
4J-4J-MM-10K	7/16"	7/16"
4J-6J-MM-10K	7/16"	9/16"
4J-8J-MM-10K	7/16"	3/4"
6J-6J-MM-10K	9/16"	9/16"
6J-8J-MM-10K	9/16"	3/4"
6J-10J-MM-10K	9/16"	7/8"
8J-8J-MM-10K	3/4"	3/4"
8J-10J-MM-10K	3/4"	7/8"
8J-12J-MM-10K	3/4"	1.1/16"
10J-10J-MM-10K	7/8"	7/8"
10J-12J-MM-10K	7/8"	1.1/16"
10J-16J-MM-10K	7/8"	1.5/16"
12J-16J-MM-10K	1.1/16"	1.5/16"
16J-16J-MM-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

FAC
Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Straight Adaptors



BSPP x BSPP

0339	Male Thread	Female Thread
2G-2G-MF-A-10K	1/8"	1/8"
2G-4G-MF-A-10K	1/8"	1/4"
2G-6G-MF-A-10K	1/8"	3/8"
2G-8G-MF-A-10K	1/8"	1/2"
2G-12G-MF-A-10K	1/8"	3/4"
4G-4G-MF-A-10K	1/4"	1/4"
4G-6G-MF-A-10K	1/4"	3/8"
4G-8G-MF-A-10K	1/4"	1/2"
4G-12G-MF-A-10K	1/4"	3/4"
4G-16G-MF-A-10K	1/4"	1"
6G-6G-MF-A-10K	3/8"	3/8"
6G-8G-MF-A-10K	3/8"	1/2"
6G-12G-MF-A-10K	3/8"	3/4"
6G-16G-MF-A-10K	3/8"	1"
8G-8G-MF-A-10K	1/2"	1/2"
8G-12G-MF-A-10K	1/2"	3/4"
8G-16G-MF-A-10K	1/2"	1"
12G-12G-MF-A-10K	3/4"	3/4"
12G-16G-MF-A-10K	3/4"	1"
16G-16G-MF-A-10K	1"	1"
Tech Sheet 20887		



NPT x NPT

0339	Male Thread	Female Thread
2N-2N-MF-A-10K	1/8"	1/8"
2N-4N-MF-A-10K	1/8"	1/4"
2N-6N-MF-A-10K	1/8"	3/8"
2N-8N-MF-A-10K	1/8"	1/2"
2N-12N-MF-A-10K	1/8"	3/4"
4N-4N-MF-A-10K	1/4"	1/4"
4N-6N-MF-A-10K	1/4"	3/8"
4N-8N-MF-A-10K	1/4"	1/2"
4N-12N-MF-A-10K	1/4"	3/4"
4N-16N-MF-A-10K	1/4"	1"
6N-6N-MF-A-10K	3/8"	3/8"
6N-8N-MF-A-10K	3/8"	1/2"
6N-12N-MF-A-10K	3/8"	3/4"
6N-16N-MF-A-10K	3/8"	1"
8N-8N-MF-A-10K	1/2"	1/2"
8N-12N-MF-A-10K	1/2"	3/4"
8N-16N-MF-A-10K	1/2"	1"
12N-12N-MF-A-10K	3/4"	3/4"
12N-16N-MF-A-10K	3/4"	1"
16N-16N-MF-A-10K	1"	1"
Tech Sheet 20887		



JIC x NPT

0339	Male Thread	Female Thread
4J-2N-MF-A-10K	7/16"-20	1/8"
4J-4N-MF-A-10K	7/16"-20	1/4"
6J-4N-MF-A-10K	9/16"-18	1/4"
4J-6N-MF-A-10K	7/16"-20	3/8"
6J-6N-MF-A-10K	9/16"-18	3/8"
8J-6N-MF-A-10K	3/4"-16	3/8"
8J-8N-MF-A-10K	9/16"-18	1/2"
10J-8N-MF-A-10K	3/4"-16	1/2"
12J-8N-MF-A-10K	7/8"-14	1/2"
12J-12N-MF-A-10K	3/4"-16	1/2"
16J-16N-MF-A-10K	7/8"-14	1/2"
Tech Sheet 20887		



BSPP x JIC, Swivel

0339	Male Thread	Female Thread
4G-4J-MF-10K	1/4"	7/16"
4G-5J-MF-10K	1/4"	1/2"
4G-6J-MF-10K	1/4"	9/16"
6G-6J-MF-10K	3/8"	9/16"
8G-6J-MF-10K	1/2"	9/16"
6G-8J-MF-10K	3/8"	3/4"
8G-8J-MF-10K	1/2"	3/4"
6G-10J-MF-10K	3/8"	7/8"
8G-10J-MF-10K	1/2"	7/8"
12G-10J-MF-10K	3/4"	7/8"
8G-12J-MF-10K	1/2"	1.1/16"
12G-12J-MF-10K	3/4"	1.1/16"
16G-12J-MF-10K	1"	1.1/16"
12G-16J-MF-10K	3/4"	1.5/16"
16G-16J-MF-10K	1"	1.5/16"
Tech Sheet 20887		



NPT x JIC, Swivel

0339	Male Thread	Female Thread
4N-4J-MF-10K	1/4"	7/16"
6N-6J-MF-10K	3/8"	9/16"
6N-8J-MF-10K	3/8"	3/4"
8N-10J-MF-10K	1/2"	7/8"
8N-12J-MF-10K	1/2"	1.1/16"
12N-12J-MF-10K	3/4"	1.1/16"
12N-14J-MF-10K	3/4"	1.3/16"
12N-16J-MF-10K	3/4"	1.5/16"
16N-16J-MF-10K	1"	1.5/16"
Tech Sheet 20887		



JIC x JIC, Swivel

0339	Male Thread	Female Thread
4J-4J-MF-10K	7/16"	7/16"
4J-6J-MF-10K	7/16"	9/16"
4J-8J-MF-10K	7/16"	3/4"
6J-4J-MF-10K	9/16"	7/16"
6J-6J-MF-10K	9/16"	9/16"
6J-8J-MF-10K	9/16"	3/4"
8J-4J-MF-10K	3/4"	7/16"
8J-6J-MF-10K	3/4"	9/16"
10J-8J-MF-10K	7/8"	3/4"
12J-8J-MF-10K	1.1/16"	3/4"
12J-12J-MF-10K	1.1/16"	1.1/16"
14J-12J-MF-10K	1.3/16"	1.1/16"
16J-12J-MF-10K	1.5/16"	1.1/16"
16J-16J-MF-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

KR 500



For **Hydraulic Adaptors** see pages **82-84**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Straight Reducers



BSPP

0339	Male Thread	Female Thread
4G-2G-MF-B-10K	1/4"	1/8"
6G-2G-MF-B-10K	3/8"	1/8"
6G-4G-MF-B-10K	3/8"	1/4"
8G-2G-MF-B-10K	1/2"	1/8"
8G-4G-MF-B-10K	1/2"	1/4"
8G-6G-MF-B-10K	1/2"	3/8"
12G-2G-MF-B-10K	3/4"	1/8"
12G-4G-MF-B-10K	3/4"	1/4"
12G-6G-MF-B-10K	3/4"	3/8"
12G-8G-MF-B-10K	3/4"	1/2"
16G-2G-MF-B-10K	1"	1/8"
16G-4G-MF-B-10K	1"	1/4"
16G-6G-MF-B-10K	1"	3/8"
16G-8G-MF-B-10K	1"	1/2"
16G-12G-MF-B-10K	1"	3/4"
Tech Sheet 20887		



NPT

0339	Male Thread	Female Thread
4N-2N-MF-B-10K	1/4"	1/8"
6N-2N-MF-B-10K	3/8"	1/8"
6N-4N-MF-B-10K	3/8"	1/4"
8N-2N-MF-B-10K	1/2"	1/8"
8N-4N-MF-B-10K	1/2"	1/4"
8N-6N-MF-B-10K	1/2"	3/8"
12N-2N-MF-B-10K	3/4"	1/8"
12N-4N-MF-B-10K	3/4"	1/4"
12N-6N-MF-B-10K	3/4"	3/8"
12N-8N-MF-B-10K	3/4"	1/2"
16N-2N-MF-B-10K	1"	1/8"
16N-4N-MF-B-10K	1"	1/4"
16N-6N-MF-B-10K	1"	3/8"
16N-8N-MF-B-10K	1"	1/2"
16N-12N-MF-B-10K	1"	3/4"
Tech Sheet 20887		

Female x Female Straight Adaptors



Swivel, BSPP

0339	Thread	Thread
4G-4G-FF-10K	1/4"	1/4"
4G-6G-FF-10K	1/4"	3/8"
4G-8G-FF-10K	1/4"	1/2"
6G-6G-FF-10K	3/8"	3/8"
6G-8G-FF-10K	3/8"	1/2"
8G-8G-FF-10K	1/2"	1/2"
12G-12G-FF-10K	3/4"	3/4"
16G-16G-FF-10K	1"	1"
Tech Sheet 20887		



Fixed, NPT

0339	Thread	Thread
2N-2N-FF-10K	1/8"	1/8"
2N-4N-FF-10K	1/8"	1/4"
2N-6N-FF-10K	1/8"	3/8"
2N-8N-FF-10K	1/8"	1/2"
2N-12N-FF-10K	1/8"	3/4"
2N-16N-FF-10K	1/8"	1"
4N-4N-FF-10K	1/4"	1/4"
4N-6N-FF-10K	1/4"	3/8"
4N-8N-FF-10K	1/4"	1/2"
4N-12N-FF-10K	1/4"	3/4"
4N-16N-FF-10K	1/4"	1"
6N-6N-FF-10K	3/8"	3/8"
6N-8N-FF-10K	3/8"	1/2"
6N-12N-FF-10K	3/8"	3/4"
6N-16N-FF-10K	3/8"	1"
8N-8N-FF-10K	1/2"	1/2"
8N-12N-FF-10K	1/2"	3/4"
8N-16N-FF-10K	1/2"	1"
12N-12N-FF-10K	3/4"	3/4"
12N-16N-FF-10K	3/4"	1"
16N-16N-FF-10K	1"	1"
Tech Sheet 20887		



Swivel, JIC

0339	Thread	Thread
4J-4J-FF-10K	7/16"	7/16"
4J-6J-FF-10K	7/16"	9/16"
4J-8J-FF-10K	9/16"	3/4"
6J-6J-FF-10K	9/16"	9/16"
6J-8J-FF-10K	9/16"	3/4"
8J-8J-FF-10K	3/4"	3/4"
12J-12J-FF-10K	1.1/16"	1.1/16"
16J-16J-FF-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

Male x Male Elbows



BSPP

0339	Thread
2G-E-MM-10K	1/8"
4G-E-MM-10K	1/4"
6G-E-MM-10K	3/8"
8G-E-MM-10K	1/2"
12G-E-MM-10K	3/4"
16G-E-MM-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-E-MM-10K	1/8"
4N-E-MM-10K	1/4"
6N-E-MM-10K	3/8"
8N-E-MM-10K	1/2"
12N-E-MM-10K	3/4"
16N-E-MM-10K	1"
Tech Sheet 20887	

FAC
Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Elbows



Swivel, BSPP

0339	Thread
2G-E-MF-10K	1/8"
4G-E-MF-10K	1/4"
6G-E-MF-10K	3/8"
8G-E-MF-10K	1/2"
12G-E-MF-10K	3/4"
16G-E-MF-10K	1"
Tech Sheet 20887	



Fixed, NPT

0339	Thread
2N-E-MF-10K	1/8"
4N-E-MF-10K	1/4"
6N-E-MF-10K	3/8"
8N-E-MF-10K	1/2"
12N-E-MF-10K	3/4"
16N-E-MF-10K	1"
Tech Sheet 20887	



Swivel, JIC

0339	Thread
4J-E-MF-10K	7/16"
6J-E-MF-10K	9/16"
8J-E-MF-10K	3/4"
10J-E-MF-10K	7/8"
12J-E-MF-10K	1.1/16"
16J-E-MF-10K	1.5/16"
Tech Sheet 20887	



NPT x JIC

0339	Male Thread	Female Thread
4N-4J-E-MF-10K	1/4"	7/16"
6N-6J-E-MF-10K	3/8"	9/16"
8N-8J-E-MF-10K	1/2"	3/4"
12N-12J-E-MF-10K	3/4"	1.1/16"
Tech Sheet 20887		

Female x Female Elbows



BSPP

0339	Thread
2G-E-FF-10K	1/8"
4G-E-FF-10K	1/4"
6G-E-FF-10K	3/8"
8G-E-FF-10K	1/2"
12G-E-FF-10K	3/4"
16G-E-FF-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-E-10K	1/8"
4N-E-10K	1/4"
6N-E-10K	3/8"
8N-E-10K	1/2"
12N-E-10K	3/4"
16N-E-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
2J-E-FF-10K	7/16"
4J-E-FF-10K	9/16"
6J-E-FF-10K	3/4"
8J-E-FF-10K	7/8"
12J-E-FF-10K	1.1/16"
16J-E-FF-10K	1.5/16"
Tech Sheet 20887	

Male x Male Tees



BSPP

0339	Thread
2G-T-MM-10K	1/8"
4G-T-MM-10K	1/4"
6G-T-MM-10K	3/8"
8G-T-MM-10K	1/2"
12G-T-MM-10K	3/4"
16G-T-MM-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-T-MM-10K	1/8"
4N-T-MM-10K	1/4"
6N-T-MM-10K	3/8"
8N-T-MM-10K	1/2"
12N-T-MM-10K	3/4"
16N-T-MM-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
4J-T-MM-10K	7/16"
5J-T-MM-10K	1/2"
6J-T-MM-10K	9/16"
8J-T-MM-10K	3/4"
10J-T-MM-10K	7/8"
12J-T-MM-10K	1.1/16"
14J-T-MM-10K	1.3/16"
16J-T-MM-10K	1.5/16"
Tech Sheet 20887	

FT PRO®

stainless steel



For **Stainless Steel Gauges**
see pages **414-416**

FAC
Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Female x Female Tees



BSPP

0339	Thread
2G-T-FF-10K	1/8"
4G-T-FF-10K	1/4"
6G-T-FF-10K	3/8"
8G-T-FF-10K	1/2"
12G-T-FF-10K	3/4"
16G-T-FF-10K	1"

Tech Sheet 20887



NPT

0339	Thread
2N-T-10K	1/8"
4N-T-10K	1/4"
6N-T-10K	3/8"
8N-T-10K	1/2"
12N-T-10K	3/4"

Tech Sheet 20887



JIC

0339	Thread
2J-T-FF-10K	7/16"
4J-T-FF-10K	9/16"
6J-T-FF-10K	3/4"
8J-T-FF-10K	7/8"
12J-T-FF-10K	1.1/16"
16J-T-FF-10K	1.5/16"

Tech Sheet 20887

Female Equal Cross



NPT

0339	Thread
2N-X-10K	1/8"
4N-X-10K	1/4"
6N-X-10K	3/8"
8N-X-10K	1/2"
12N-X-10K	3/4"
16N-X-10K	1"

Tech Sheet 20887

Plugs



BSPP

0339	Thread
2G-P-10K	1/8"
4G-P-10K	1/4"
6G-P-10K	3/8"
8G-P-10K	1/2"
12G-P-10K	3/4"
16G-P-10K	1"

Tech Sheet 20887



NPT

0339	Thread
2N-P-10K	1/8"
4N-P-10K	1/4"
6N-P-10K	3/8"
8N-P-10K	1/2"
12N-P-10K	3/4"
16N-P-10K	1"

Tech Sheet 20887



JIC

0339	Thread
4J-P-10K	7/16"
6J-P-10K	9/16"
8J-P-10K	3/4"
10J-P-10K	7/8"
12J-P-10K	1.1/16"
16J-P-10K	1.5/16"

Tech Sheet 20887

Caps



BSPP

0339	Thread
2G-C-10K	1/8"
4G-C-10K	1/4"
6G-C-10K	3/8"
8G-C-10K	1/2"
12G-C-10K	3/4"
16G-C-10K	1"

Tech Sheet 20887



NPT

0339	Thread
2N-C-10K	1/8"
4N-C-10K	1/4"
6N-C-10K	3/8"
8N-C-10K	1/2"
12N-C-10K	3/4"
16N-C-10K	1"

Tech Sheet 20887



JIC

0339	Thread
4J-C-10K	7/16"
6J-C-10K	9/16"
8J-C-10K	3/4"
10J-C-10K	7/8"
12J-C-10K	1.1/16"
16J-C-10K	1.5/16"

Tech Sheet 20887

FT PRO



For **Glycerine Gauges & Accessories** see pages **263-264**

FAC Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Male Stud Couplings

UNF



0215	Thread
205BM6	7/16"-20
205BM8	1/2"-20
205BM10	9/16"-18
205BM12	3/4"-16
205BM16	7/8"-14
205BM20	1.1/16"-12
205BM22	1.3/16"-12
205BM25	1.5/16"-12
205BM32	1.5/8"-12
Tech Sheet 20886	

UNF x BSPT



0215	Thread	Thread
210BM6R18	7/16"-20	1/8"
210BM6R14	7/16"-20	1/4"
210BM6R12	7/16"-20	1/2"
210BM8R18	1/2"-20	1/8"
210BM8R14	1/2"-20	1/4"
210BM10R14	9/16"-18	1/4"
210BM10R18	9/16"-18	1/8"
210BM10R38	9/16"-18	3/8"
210BM10R12	9/16"-18	1/2"
210BM12R14	3/4"-16	1/4"
210BM12R38	3/4"-16	3/8"
210BM12R12	3/4"-16	1/2"
210BM16R12	7/8"-14	1/2"
210BM16R34	7/8"-14	3/4"
210BM20R12	1.1/16"-12	1/2"
210BM20R34	1.1/16"-12	3/4"
210BM20R1	1.1/16"-12	1"
210BM22R34	1.3/16"-12	3/4"
210BM25R34	1.5/16"-12	3/4"
210BM25R1	1.5/16"-12	1"
210BM32R1	1.5/8"-12	1"
210BM32R114	1.5/8"-12	1.1/4"
210BM38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

UNF x BSPP



0215	Thread	Thread
210SM6G18	7/16"-20	1/8"
210SM6G14	7/16"-20	1/4"
210SM6G38	7/16"-20	3/8"
210SM6G12	7/16"-20	1/2"
210SM8G18	1/2"-20	1/8"
210SM8G14	1/2"-20	1/4"
210SM8G38	1/2"-20	3/8"
210SM10G18	9/16"-18	1/8"
210SM10G14	9/16"-18	1/4"
210SM10G38	9/16"-18	3/8"
210SM10G12	9/16"-18	1/2"
210SM12G14	3/4"-16	1/4"
210SM12G38	3/4"-16	3/8"
210SM12G12	3/4"-16	1/2"
210SM12G34	3/4"-16	3/4"
210SM16G38	7/8"-14	3/8"
210SM16G12	7/8"-14	1/2"
210SM16G34	7/8"-14	3/4"
210SM20G12	1.1/16"-12	1/2"
210SM20G34	1.1/16"-12	3/4"
210SM20G1	1.1/16"-12	1"
210SM22G34	1.3/16"-12	3/4"
210SM25G34	1.5/16"-12	3/4"
210SM25G1	1.5/16"-12	1"
210SM25G114	1.5/16"-12	1.1/4"
210SM32G1	1.5/8"-12	1"
210SM32G114	1.5/8"-12	1.1/4"
210SM38G114	1.7/8"-12	1.1/4"
210SM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

UNF x NPT



0215	Thread	Thread
214BM6N18	7/16"-20	1/8"
214BM6N14	7/16"-20	1/4"
214BM8N18	1/2"-20	1/8"
214BM8N14	1/2"-20	1/4"
214BM10N18	9/16"-18	1/8"
214BM10N14	9/16"-18	1/4"
214BM10N38	9/16"-18	3/8"
214BM10N12	9/16"-18	1/2"
214BM12N14	3/4"-16	1/4"
214BM12N38	3/4"-16	3/8"
214BM12N12	3/4"-16	1/2"
214BM12N34	3/4"-16	3/4"
214BM16N12	7/8"-14	1/2"
214BM20N12	1.1/16"-12	1/2"
214BM20N34	1.1/16"-12	3/4"
214BM20N1	1.1/16"-12	1"
214BM25N34	1.5/16"-12	3/4"
214BM25N1	1.5/16"-12	1"
214BM32N1	1.5/8"-12	1"
214BM32N114	1.5/8"-12	1.1/4"
214BM38N114	1.7/8"-12	1.1/4"
214BM38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

stainless steel



For **316 Stainless Steel Tubing** see page **183**

For Flaretite Seals see page 111

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Female Stud Couplings



Male UNF x Female BSPP

0215	Male Thread	Female Thread
230BM6G18	7/16"-20	1/8"
230BM6G14	7/16"-20	1/4"
230BM6G12	7/16"-20	1/2"
230BM8G14	1/2"-20	1/4"
230BM10G18	9/16"-18	1/8"
230BM10G14	9/16"-18	1/4"
230BM10G38	9/16"-18	3/8"
230BM10G12	9/16"-18	1/2"
230BM12G14	3/4"-16	1/4"
230BM12G38	3/4"-16	3/8"
230BM12G12	3/4"-16	1/2"
230BM12G34	3/4"-16	3/4"
230BM16G38	7/8"-14	3/8"
230BM16G12	7/8"-14	1/2"
230BM16G34	7/8"-14	3/4"
230BM18G1	1.1/16"-12	1"
230BM22G34	1.3/16"-12	3/4"
230BM25G34	1.5/16"-12	3/4"
230BM25G1	1.5/16"-12	1"
230BM32G1	1.5/8"-12	1"
230BM32G114	1.5/8"-12	1.1/4"
230BM38G114	1.7/8"-12	1.1/2"
230BM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Male UNF x Female NPT

0215	Male Thread	Female Thread
232BM6N18	7/16"-20	1/8"
232BM6N14	7/16"-20	1/4"
232BM8N14	1/2"-20	1/4"
232BM10N14	9/16"-18	1/4"
232BM10N38	9/16"-18	3/8"
232BM12N12	3/4"-16	1/2"
232BM20N12	1.1/16"-12	1/2"
232BM20N34	1.1/16"-12	3/4"
232BM25N1	1.5/16"-12	1"
232BM32N114	1.5/8"-12	1.1/4"
232BM38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Male UNF x Female BSPT

0215	Male Thread	Female Thread
231M6R18	7/16"-20	1/8"
231M6R14	7/16"-20	1/4"
231M6R12	7/16"-20	1/2"
231M8R18	1/2"-20	1/8"
231M8R14	1/2"-20	1/4"
231M10R18	9/16"-18	1/8"
231M10R14	9/16"-18	1/4"
231M10R38	9/16"-18	3/8"
231M10R12	9/16"-18	1/2"
231M12R14	3/4"-16	1/4"
231M12R38	3/4"-16	3/8"
231M12R12	3/4"-16	1/2"
231M12R34	3/4"-16	3/4"
231M16R38	7/8"-14	3/8"
231M16R12	7/8"-14	1/2"
231M16R34	7/8"-14	3/4"
231M18R34	1.1/16"-12	3/4"
231M18R1	1.1/16"-12	1"
231M22R34	1.3/16"-12	3/4"
231M25R34	1.5/16"-12	3/4"
231M25R1	1.5/16"-12	1"
231M32R1	1.5/8"-12	1"
231M32R114	1.5/8"-12	1.1/4"
231M38R114	1.7/8"-12	1.1/4"
231M38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Female Swivel Connectors



Male UNF x Female UNF

0215	Male Thread	Female Thread
273M6U716	7/16"-20	7/16"-20
273M8U716	1/2"-20	7/16"-20
273M8U12	1/2"-20	1/2"-20
273M10U716	9/16"-18	7/16"-20
273M10U916	9/16"-18	9/16"-18
273M12U916	3/4"-16	9/16"-18
273M16U34	7/8"-14	3/4"-16
273M18U34	1.1/16"-12	3/4"-16
273M18U1116	1.1/16"-12	1.1/16"-12
273M22U1116	1.3/16"-12	1.1/16"-12
273M25U1116	1.5/16"-12	1.1/16"-12
273M25U1516	1.5/16"-12	1.5/16"-12
Tech Sheet 20886		



Male BSPP x Female UNF

0215	Male Thread	Female Thread
273M6G18	1/8"	7/16"-20
273M8G18	1/8"	1/2"-20
273M8G14	1/4"	1/2"-20
273M10G14	1/4"	9/16"-18
273M10G38	3/8"	9/16"-18
273M12G38	3/8"	3/4"-16
273M16G12	1/2"	7/8"-14
273M20G34	3/4"	1.1/16"-12
273M22G34	3/4"	1.3/16"-12
273M25G1	1"	1.5/16"-12
273M32G114	1.1/4"	1.5/8"-12
273M38G112	1.1/2"	1.7/8"-12
Tech Sheet 20886		



Male NPT x Female UNF

0215	Male Thread	Female Thread
276M6N18	1/8"	7/16"-20
276M8N18	1/8"	1/2"-20
276M6N14	1/4"	7/16"-20
276M8N14	1/4"	1/2"-20
276M10N14	1/4"	9/16"-18
276M10N38	3/8"	9/16"-18
276M12N38	3/8"	3/4"-16
276M16N12	1/2"	7/8"-14
276M20N12	1/2"	1.1/16"-12
276M20N34	3/4"	1.1/16"-12
276M22N34	3/4"	1.3/16"-12
276M25N34	3/4"	1.5/16"-12
276M25N1	1"	1.5/16"-12
276M32N114	1.1/4"	1.5/8"-12
276M38N112	1.1/2"	1.7/8"-12
Tech Sheet 20886		



Male BSPT x Female UNF

0215	Male Thread	Female Thread
273M6R18	1/8"	7/16"-20
273M8R14	1/4"	1/2"-20
273M10R14	1/4"	9/16"-18
273M12R14	1/4"	3/4"-16
273M12R38	3/8"	3/4"-16
273M16R12	1/2"	7/8"-14
273M20R12	1/2"	1.1/16"-12
273M20R34	3/4"	1.1/16"-12
273M22R34	3/4"	1.3/16"-12
273M25R34	3/4"	1.5/16"-12
273M25R1	1"	1.5/16"-12
273M32R114	1.1/4"	1.5/8"-12
273M38R112	1.1/2"	1.7/8"-12
Tech Sheet 20886		

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Bulkhead Unions



Bulkhead complete with Locknut, UNF

0215	Thread
204M6U716	7/16"-20
204M8U12	1/2"-20
204M10U916	9/16"-18
204M12U34	3/4"-16
204M16U78	7/8"-14
204M18U1116	1.1/16"-12
204M22U1316	1.3/16"-12
204M25U1516	1.5/16"-12
204M32U158	1.5/8"-12
204M38U178	1.7/8"-12
Tech Sheet 20886	

Bulkhead Locknuts

0215	Thread
199M6U716	7/16"-20
199M8U12	1/2"-20
199M10U916	9/16"-18
199M12U34	3/4"-16
199M16U78	7/8"-14
199M18U1116	1.1/16"-12
199M22U1316	1.3/16"-12
199M25U1516	1.5/16"-12
199M32U158	1.5/8"-12
199M38U178	1.7/8"-12
Tech Sheet 20886	

Fixed Elbows



UNF

0215	Thread
206BM6	7/16"-20
206BM8	1/2"-20
206BM12	3/4"-16
206BM20	1.1/16"-12
206BM22	1.3/16"-12
206BM25	1.5/16"-12
206BM32	1.5/8"-12
206BM38	1.7/8"-12
Tech Sheet 20886	

UNF Male x BSPT Male

0215	Thread	Thread
206M6R18	7/16"-20	1/8"
206M6R14	7/16"-20	1/4"
206M6R12	7/16"-20	1/2"
206M8R18	1/2"-20	1/8"
206M8R14	1/2"-20	1/4"
206M10R18	9/16"-18	1/8"
206M10R14	9/16"-18	1/4"
206M10R38	9/16"-18	3/8"
206M10R12	9/16"-18	1/2"
206M12R14	3/4"-16	1/4"
206M12R38	3/4"-16	3/8"
206M12R12	3/4"-16	1/2"
206M12R34	3/4"-16	3/4"
206M16R38	7/8"-14	3/8"
206M16R12	7/8"-14	1/2"
206M16R34	7/8"-14	3/4"
206M18R34	1.1/16"-12	3/4"
206M18R1	1.1/16"-12	1"
206M22R34	1.3/16"-12	3/4"
206M25R34	1.5/16"-12	3/4"
206M25R1	1.5/16"-12	1"
206M32R1	1.5/8"-12	1"
206M32R114	1.5/8"-12	1.1/4"
206M38R114	1.7/8"-12	1.1/4"
206M38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

UNF Male x 45° NPT Male

0215	Thread	Thread
285M6N18	7/16"-20	1/8"
285M8N14	1/2"-20	1/8"
285M10N12	9/16"-18	1/2"
285M12N18	3/4"-16	3/8"
285M16N14	7/8"-14	1/2"
285M18N18	1.1/16"-12	3/4"
285M22N14	1.3/16"-12	3/4"
285M25N38	1.5/16"-12	1"
285M32N12	1.5/8"-12	1.1/4"
285M38N14	1.7/8"-12	1.1/2"
Tech Sheet 20886		



For **Hydraulic Oil** see page **283**

For Flaretite Seals see page 111

FAC Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Swivel Elbows



Male x Female, UNF

0215	Thread
275M6U716	7/16"-20
275M8U12	1/2"-20
275M10U916	9/16"-18
275M12U34	3/4"-16
275M16U78	7/8"-14
275M18U1116	1.1/16"-12
275M22U1316	1.3/16"-12
275M25U1516	1.5/16"-12
275M32U158	1.5/8"-12
275M38U178	1.7/8"-12
Tech Sheet 20886	



NPT Male x UNF Female

0215	Thread	Thread
275M6N18	7/16"-20	1/8"
275M6N14	7/16"-20	1/4"
275M6N12	7/16"-20	1/2"
275M8N18	1/2"-20	1/8"
275M8N14	1/2"-20	1/4"
275M10N18	9/16"-18	1/8"
275M10N14	9/16"-18	1/4"
275M10N38	9/16"-18	3/8"
275M10N12	9/16"-18	1/2"
275M12N14	3/4"-16	1/4"
275M12N38	3/4"-16	3/8"
275M12N12	3/4"-16	1/2"
275M12N34	3/4"-16	3/4"
275M16N38	7/8"-14	3/8"
275M16N12	7/8"-14	1/2"
275M16N34	7/8"-14	3/4"
275M18N34	1.1/16"-12	3/4"
275M18N1	1.1/16"-12	1"
275M22N34	1.3/16"-12	3/4"
275M25N34	1.5/16"-12	3/4"
275M25N1	1.5/16"-12	1"
275M32N1	1.5/8"-12	1"
275M32N114	1.5/8"-12	1.1/4"
275M38N114	1.7/8"-12	1.1/4"
275M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		



Equal Female, UNF

0215	Thread
265M6U716	7/16"-20
265M8U12	1/2"-20
265M10U916	9/16"-18
265M12U34	3/4"-16
265M16U78	7/8"-14
265M18U1116	1.1/16"-12
265M22U1316	1.3/16"-12
265M25U1516	1.5/16"-12
265M32U158	1.5/8"-12
265M38U178	1.7/8"-12
Tech Sheet 20886	

90º Position Elbows



UNF x BSPP

0215	Thread	Thread
216SM6G18	7/16"-20	1/8"
216SM6G14	7/16"-20	1/4"
216SM8G18	1/2"-20	1/8"
216SM10G38	9/16"-18	3/8"
216SM12G14	3/4"-16	1/4"
216SM12G38	3/4"-16	3/8"
216SM12G12	3/4"-16	1/2"
216SM12G34	3/4"-16	3/4"
216SM16G14	7/8"-14	1/4"
216SM16G38	7/8"-14	3/8"
216SM16G12	7/8"-14	1/2"
216SM16G34	7/8"-14	3/4"
216SM20G12	1.1/16"-12	1/2"
216SM20G34	1.1/16"-12	3/4"
216SM22G12	1.3/16"-12	1/2"
216SM22G34	1.3/16"-12	3/4"
216SM22G1	1.3/16"-12	1/2"
216SM25G12	1.5/16"-12	1/2"
216SM25G1	1.5/16"-12	1"
216SM32G1	1.5/8"-12	1"
216SM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Fixed Tees



UNF

0215	Thread
207BM6	7/16"-20
207BM8	1/2"-20
207BM10	9/16"-18
207BM12	3/4"-16
207BM16	7/8"-14
207BM20	1.1/16"-12
207BM22	1.3/16"-12
207BM25	1.5/16"-12
207BM32	1.5/8"-12
Tech Sheet 20886	



UNF Male x NPT Male Branch

0215	Thread	Thread
307M6N18	7/16"-20	1/8"
307M6N14	7/16"-20	1/4"
307M6N12	7/16"-20	1/2"
307M8N18	1/2"-20	1/8"
307M8N14	1/2"-20	1/4"
307M10N18	9/16"-18	1/8"
307M10N14	9/16"-18	1/4"
307M10N38	9/16"-18	3/8"
307M10N12	9/16"-18	1/2"
307M12N14	3/4"-16	1/4"
307M12N38	3/4"-16	3/8"
307M12N12	3/4"-16	1/2"
307M12N34	3/4"-16	3/4"
307M16N38	7/8"-14	3/8"
307M16N12	7/8"-14	1/2"
307M16N34	7/8"-14	3/4"
307M18N34	1.1/16"-12	3/4"
307M18N1	1.1/16"-12	1"
307M22N34	1.3/16"-12	3/4"
307M25N34	1.5/16"-12	3/4"
307M25N1	1.5/16"-12	1"
307M32N1	1.5/8"-12	1"
307M32N114	1.5/8"-12	1.1/4"
307M38N114	1.7/8"-12	1.1/4"
307M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

For Flaretite Seals see page 111

FAC
Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Fixed Tees



UNF Male x NPT Male Run

0215	Thread	Thread
309M6N18	7/16"-20	1/8"
309M6N14	7/16"-20	1/4"
309M6N12	7/16"-20	1/2"
309M8N18	1/2"-20	1/8"
309M8N14	1/2"-20	1/4"
309M10N18	9/16"-18	1/8"
309M10N14	9/16"-18	1/4"
309M10N38	9/16"-18	3/8"
309M10N12	9/16"-18	1/2"
309M12N14	3/4"-16	1/4"
309M12N38	3/4"-16	3/8"
309M12N12	3/4"-16	1/2"
309M12N34	3/4"-16	3/4"
309M16N38	7/8"-14	3/8"
309M16N12	7/8"-14	1/2"
309M16N34	7/8"-14	3/4"
309M18N34	1.1/16"-12	3/4"
309M18N1	1.1/16"-12	1"
309M22N34	1.3/16"-12	3/4"
309M25N34	1.5/16"-12	3/4"
309M25N1	1.5/16"-12	1"
309M32N1	1.5/8"-12	1"
309M32N114	1.5/8"-12	1.1/4"
309M38N114	1.7/8"-12	1.1/4"
309M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Swivel Tees



Female Swivel, UNF

0215	Thread
310M6U716	7/16"-20
310M8U12	1/2"-20
310M10U916	9/16"-18
310M12U34	3/4"-16
310M16U78	7/8"-14
310M18U1116	1.1/16"-12
310M22U1316	1.3/16"-12
310M25U1516	1.5/16"-12
310M32U158	1.5/8"-12
310M38U178	1.7/8"-12
Tech Sheet 20886	



Female Swivel Branch, UNF

0215	Thread
314M6U716	7/16"-20
314M8U12	1/2"-20
314M10U916	9/16"-18
314M12U34	3/4"-16
314M16U78	7/8"-14
314M18U1116	1.1/16"-12
314M22U1316	1.3/16"-12
314M25U1516	1.5/16"-12
314M32U158	1.5/8"-12
314M38U178	1.7/8"-12
Tech Sheet 20886	



Female Swivel Run, UNF

0215	Thread
312M6U716	7/16"-20
312M8U12	1/2"-20
312M10U916	9/16"-18
312M12U34	3/4"-16
312M16U78	7/8"-14
312M18U1116	1.1/16"-12
312M22U1316	1.3/16"-12
312M25U1516	1.5/16"-12
312M32U158	1.5/8"-12
312M38U178	1.7/8"-12
Tech Sheet 20886	

Position Tees



UNF Male x BSPP Male

0215	Thread	Thread
308M6G18	7/16"-20	1/8"
308M6G14	7/16"-20	1/4"
308M8G18	1/2"-20	1/8"
308M8G14	1/2"-20	1/4"
308M10G14	9/16"-18	1/4"
308M10G38	9/16"-18	3/8"
308M12G14	3/4"-16	1/4"
308M12G38	3/4"-16	3/8"
308M12G12	3/4"-16	1/2"
308M12G34	3/4"-16	3/4"
308M16G14	7/8"-14	1/4"
308M16G38	7/8"-14	3/8"
308M16G12	7/8"-14	1/2"
308M16G34	7/8"-14	3/4"
308M20G12	1.1/16"-12	1/2"
308M20G34	1.1/16"-12	3/4"
308M22G34	1.3/16"-12	1/2"
308M22G1	1.3/16"-12	3/4"
308M22G12	1.3/16"-12	1"
308M25G34	1.5/16"-12	1/2"
308M25G1	1.5/16"-12	3/4"
308M32G1	1.5/8"-12	1"
308M32G114	1.5/8"-12	1"
308M38G114	1.7/8"-12	1.1/4"
308M38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Cross



Male, UNF

0215	Thread
320M6U716	7/16"-20
320M8U12	1/2"-20
320M10U916	9/16"-18
320M12U34	3/4"-16
320M16U78	7/8"-14
320M18U1116	1.1/16"-12
320M22U1316	1.3/16"-12
320M25U1516	1.5/16"-12
320M32U158	1.5/8"-12
320M38U178	1.7/8"-12
Tech Sheet 20886	

For Flaretite Seals see page 111

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Swivel Caps



UNF

0215	Thread
289M6U716	7/16"-20
289M8U12	1/2"-20
289M10U916	9/16"-18
289M12U34	3/4"-16
289M16U78	7/8"-14
289M22U1316	1.3/16"-12
289M25U1516	1.5/16"-12
289M32U158	1.5/8"-12
289M38U178	1.7/8"-12

Tech Sheet 20886

Blanking Plugs



UNF

0215	Thread
299M6	7/16"-20
299M8	1/2"-20
299M10	9/16"-18
299M12	3/4"-16
299M16	7/8"-14
299M20	1.1/16"-12
299M22	1.3/16"-12
299M25	1.5/16"-12
299M32	1.5/8"-12
299M38	1.7/8"-12

Tech Sheet 20886

Reducing Adaptors



UNF Tube x UNF Male

0215	OD mm	OD mm	Male Thread
303M6U716	10	6	7/16"-20
303M6U34	12	6	3/4"-16
303M10U34	12	10	3/4"-16
303M6U78	16	6	7/8"-14
303M10U78	16	10	7/8"-14
303M6U1116	18	6	1.1/16"-12
303M10U1116	18	10	1.1/16"-12
303M12U1116	18	12	1.1/16"-12
303M10U1316	22	10	1.3/16"-12
303M16U1316	22	16	1.3/16"-12
303M6U1516	25	6	1.5/16"-12
303M10U1516	25	10	1.5/16"-12
303M12U1516	25	12	1.5/16"-12
303M16U1516	25	16	1.5/16"-12
303M18U1516	25	18	1.5/16"-12
303M18U158	32	18	1.5/8"-12
303M25U158	32	25	1.5/8"-12
303M12U178	38	12	1.7/8"-12
303M18U178	38	18	1.7/8"-12
303M25U178	38	25	1.7/8"-12

Tech Sheet 20886

Tube Nuts



UNF

0215	Thread
201M6U716	7/16"-20
201M8U12	1/2"-20
201M10U916	9/16"-18
201M12U34	3/4"-16
201M16U78	7/8"-14
201M20U1116	1.1/16"-12
201M22U1316	1.3/16"-12
201M25U1516	1.5/16"-12
201M32U158	1.5/8"-12
201M38U178	1.7/8"-12

Tech Sheet 20886

Flare Sleeves



Metric

0215	OD mm
203M6	6
203M8	8
203M10	10
203M12	12
203M14	14
203M15	15
203M16Z58	16
203M18	18
203M20	20
203M25	25
203M30	30
203M32	32
203M38Z112	38

Tech Sheet 20886

Imperial

0215	OD
203Z14	1/4"
203Z516	5/16"
203Z38	3/8"
203Z12	1/2"
203M15Z58	5/8"
203Z34	3/4"
203Z1	1"

Tech Sheet 20886

For Flaretite Seals see page 111

FAC
Fluid-Air Components Ltd

SAE FLANGES

havIT



- Closed Flanges
- Split Flange Half
- 90° Threaded Flanges
- Threaded Flanges
- Threaded Flanges-Companion (Counter)
- Socket Weld Flanges
- Socket Weld Flanges 90°
- Butt Weld Flanges
- Butt Weld Flanges 90°
- Butt Weld Flanges-Companion (Counter)
- Socket Weld Coupling Set
- Bolts & Spring Washers
- O-Rings

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAE FLANGES

havit

Closed Flanges

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi

0300	Flange Size	Bolt Type Metric
AFC080	1/2"	M8 x 30
AFC100	3/4"	M10 x 35
AFC102	1"	M10 x 35
AFC104	1.1/4"	M10 x 40
AFC106	1.1/2"	M12 x 45
AFC108	2"	M12 x 45
AFC110	2.1/2"	M12 x 45
AFC112	3"	M16 x 50
AFC114	3.1/2"	M16 x 50
AFC116	4"	M16 x 50
AFC118	5"	M16 x 50
Tech Sheet 1625		

6000 psi

0300	Flange Size	Bolt Type Metric
AFC401	1/2"	M8 x 30
AFC402	3/4"	M10 x 35
AFC403	1"	M12 x 45
AFC404	1.1/4"	M14 x 45
AFC405	1.1/2"	M16 x 50
AFC406	2"	M20 x 65
AFC407	2.1/2"	M24 x 80
Tech Sheet 1625		

Split Flange Half

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi

0300	Flange Size	Bolt Type Metric	Bolt Type UNC
FH3001	1/2"	M8 x 25	5/16" x 1.1/4"
FH3002	3/4"	M10 x 30	3/8" x 1.1/4"
FH3003	1"	M10 x 30	3/8" x 1.1/4"
FH3004	1.1/4"	M10 x 35	7/16" x 1.1/2"
FH3005	1.1/2"	M12 x 35	1/2" x 1.1/2"
FH3006	2"	M12 x 35	1/2" x 1.1/2"
FH3007	2.1/2"	M12 x 40	1/2" x 1.1/2"
FH3011	5"	M16 x 50	5/8" x 2"
Tech Sheet 1626			

6000 psi

0300	Flange Size	Bolt Type Metric	Bolt Type UNC
FH6001	1/2"	M8 x 30	5/16" x 1.1/4"
FH6002	3/4"	M10 x 35	3/8" x 1.1/2"
FH6003	1"	M12 x 45	-
FH6013	1"	-	7/16" x 1.1/4"
FH6004	1.1/4"	M14 x 50	-
FH6044	1.1/4"	-	1/2" x 1.3/4"
FH6005	1.1/2"	M16 x 55	5/8" x 2"
FH6006	2"	M20 x 65	3/4" x 2.1/2"
Tech Sheet 1626			

90º Threaded Flanges

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi, BSPP

0300	Flange Size	Thread	Bolt Typ Metric	Bolt Type UNC
AFS080/90G-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS100/90G	3/4"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS102/90G	1"	1"	M10 x 35	3/8" x 1.1/2"
AFS104/90G	1.1/4"	1.1/4"	M10 x 35	3/8" x 1.1/2"
AFS106/90G	1.1/2"	1.1/2"	M12 x 45	1/2" x 1.3/4"
AFS/90G	2"	2"	M12 x 45	1/2" x 1.3/4"
Tech Sheet 1628				

6000 psi, BSPP

0300	Flange Size	Thread	Bolt Type Metric	Bolt Type UNC
AFS401/90G-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS401/90G-012	1/2"	1/2"	M8 x 30	5/16" x 1.1/4"
AFS402/90G	3/4"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS403/90G	1"	1"	M12 x 45	7/16" x 1.3/4"
AFS405/90G	1.1/2"	1.1/2"	M16 x 50	5/8" x 2"
AFS406/90G	2"	2"	M20 x 110	-
Tech Sheet 1628				

Code Information: AFS = Flange with O-Ring Groove
GFS = Flange with Flat Face



For **Hydraulic Hose Connectors**
see pages **17-24**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAE FLANGES

Threaded Flanges

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi, BSPP

0300	Flange Size	Thread	Bolt Type Metric	Bolt Type UNC
AFS080G-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS080G	1/2"	1/2"	M8 x 30	5/16" x 1.1/4"
AFS100G-012	3/4"	1/2"	M10 x 35	3/8 "x 1.1/2"
AFS100G	3/4"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS102G-012	1"	1/2"	M10 x 35	3/8" x 1.1/2"
AFS102G-034	1"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS102G	1"	1"	M10 x 35	3/8" x 1.1/2"
AFS104G-034	1.1/4"	3/4"	M10 x 40	7/16" x 1.1/2"
AFS104G-100	1.1/4"	1"	M10 x 40	7/16" x 1.3/4"
AFS104G	1.1/4"	1.1/4"	M10 x 40	7/16" x 1.1/2"
AFS106G-034	1.1/2"	3/4"	M12 x 45	1/2" x 1.3/4"
AFS106G-100	1.1/2"	1"	M12 x 45	1/2" x 1.3/4"
AFS106G-114	1.1/2"	1.1/4"	M12 x 45	1/2" x 1.3/4"
AFS106G	1.1/2"	1.1/2"	M12 x 45	1/2" x 1.3/4"
AFS108G-100	2"	1"	M12 x 45	1/2" x 1.3/4"
AFS108G-114	2"	1.1/4"	M12 x 45	1/2" x 1.3/4"
AFS108G-112	2"	1.1/2"	M12 x 45	1/2" x 1.3/4"
AFS108G	2"	2"	M12 x 45	1/2" x 1.3/4"
AFS110G-200	2.1/2"	2"	M12 x 45	1/2" x 1.3/4"
AFS110G	2.1/2"	2.1/2"	M12 x 45	1/2" x 1.3/4"
AFS112G-212	3"	2.1/2"	M16 x 50	5/8" x 2"
AFS112G	3"	3"	M16 x 50	5/8" x 2"
AFS114G-300	3.1/2"	3"	M16 x 50	5/8" x 2"
AFS114G	3.1/2"	3.1/2"	M16 x 50	5/8" x 2"
AFS116G-312	4"	3.1/2"	M16 x 50	5/8" x 2"
AFS116G	4"	4"	M16 x 50	5/8" x 2"
Tech Sheet 1629				

6000 psi, BSPP

0300	Flange Size	Thread	Bolt Type Metric	Bolt Type UNC
AFS401G-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS401G-012	1/2"	1/2"	M8 x 30	5/16" x 1.1/4"
AFS402G-012	3/4"	1/2"	M10 x 35	3/8" x 1.1/2"
AFS402G	3/4"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS403G-034	1"	3/4"	M12 x 45	7/16" x 1.3/4"
AFS403G	1"	1"	M12 x 45	7/16" x 1.3/4"
AFS404G-100	1.1/4"	1"	M14 x 45	1/2" x 1.3/4"
AFS404G	1.1/4"	1.1/4"	M14 x 45	1/2" x 1.3/4"
AFS405G-114	1.1/2"	1.1/4"	M16 x 50	5/8" x 2"
AFS405G	1.1/2"	1.1/2"	M16 x 50	5/8" x 2"
AFS406G-112	2"	1.1/2"	M20 x 65	3/4" x 2.1/2"
AFS406G	2"	2"	M20 x 65	3/4" x 2.1/2"
Tech Sheet 1629				

3000 psi, NPT

0300	Flange Size	Thread	Bolt Type Metric	Bolt Type UNC
AFS080N-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS080N	1/2"	1/2"	M8 x 30	5/16" x 1.1/4"
AFS100N-012	3/4"	1/2"	M10 x 35	3/8" x 1.1/2"
AFS102N-034	1"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS102N	1"	1"	M10 x 35	3/8" x 1.1/2"
AFS104N-100	1.1/4"	1"	M10 x 40	7/16" x 1.1/2"
AFS104N	1.1/4"	1.1/4"	M10 x 40	7/16" x 1.1/2"
AFS106N-114	1.1/2"	1.1/4"	M12 x 45	1/2" x 1.3/4"
AFS106N	1.1/2"	1.1/2"	M12 x 45	1/2" x 1.3/4"
AFS108N-112	2"	1.1/2"	M12 x 45	1/2" x 1.3/4"
AFS108N	2"	2"	M12 x 45	1/2" x 1.3/4"
AFS110N	2.1/2"	2.1/2"	M12 x 45	1/2" x 1.3/4"
AFS112N	3"	3"	M16 x 50	5/8" x 2"
AFS114N	3.1/2"	3.1/2"	M16 x 50	5/8" x 2"
AFS116N	4"	4"	M16 x 50	5/8" x 2"
Tech Sheet 1629				

6000 psi, NPT

0300	Flange Size	Thread	Bolt Type Metric	Bolt Type UNC
AFS401N-038	1/2"	3/8"	M8 x 30	5/16" x 1.1/4"
AFS401N-012	1/2"	1/2"	M8 x 30	5/16" x 1.1/4"
AFS402N-012	3/4"	1/2"	M10 x 35	3/8" x 1.1/2"
AFS402N	3/4"	3/4"	M10 x 35	3/8" x 1.1/2"
AFS403N-034	1"	3/4"	M12 x 45	7/16" x 1.3/4"
AFS403N	1"	1"	M12 x 45	7/16" x 1.3/4"
AFS404N-100	1.1/4"	1"	M14 x 45	1/2" x 1.3/4"
AFS405N-114	1.1/2"	1.1/4"	M16 x 50	5/8" x 2"
AFS405N	1.1/2"	1.1/2"	M16 x 50	5/8" x 2"
AFS406N-112	2"	1.1/2"	M20 x 65	3/4" x 2.1/2"
AFS406N	2"	2"	M20 x 65	3/4" x 2.1/2"
Tech Sheet 1629				

Code Information: AFS = Flange with O-Ring Groove GFS = Flange with Flat Face

Fluid-Air Components Ltd

SAE FLANGES

Threaded Flanges-Companion (Counter)

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi, BSPP, Metric Mount

0300	Flange Size	Thread	Bolt Type Metric
GFS080GM-038	1/2"	3/8"	M8
GFS080GM	1/2"	1/2"	M8
GFS100GM-012	3/4"	1/2"	M10
GFS100GM	3/4"	3/4"	M10
GFS102GM-034	1"	3/4"	M10
GFS102GM	1"	1"	M10
GFS104GM-100	1.1/4"	1"	M10
GFS104GM	1.1/4"	1.1/4"	M10
GFS106GM-114	1.1/2"	1.1/4"	M12
GFS106GM	1.1/2"	1.1/2"	M12
GFS108GM-112	2"	1.1/2"	M12
GFS108GM	2"	2"	M12
GFS110GM-200	2.1/2"	2"	M12
GFS110GM	2.1/2"	2.1/2"	M12
GFS112GM-212	3"	2.1/2"	M16
GFS112GM	3"	3"	M16
GFS114GM-300	3.1/2"	3"	M16
GFS114GM	3.1/2"	3.1/2"	M16
GFS116GM-312	4"	3.1/2"	M16
GFS116GM	4"	4"	M16
Tech Sheet 1631			

3000 psi, BSPP, UNC Mount

0300	Flange Size	Thread	Bolt Type Metric
GFS080GU-038	1/2"	3/8"	5/16"
GFS100GU-012	3/4"	1/2"	3/8"
GFS100GU	3/4"	3/4"	3/8"
GFS102GU-034	1"	3/4"	3/8"
GFS102GU	1"	1"	3/8"
GFS104GU-100	1.1/4"	1"	7/16"
GFS104GU	1.1/4"	1.1/4"	7/16"
GFS106GU-114	1.1/2"	1.1/4"	1/2"
GFS106GU	1.1/2"	1.1/2"	1/2"
GFS108GU-112	2"	1.1/2"	1/2"
GFS108GU	2"	2"	1/2"
GFS110GU-200	2.1/2"	2"	1/2"
GFS110GU	2.1/2"	2.1/2"	1/2"
GFS112GU-212	3"	2.1/2"	5/8"
GFS112GU	3"	3"	5/8"
GFS114GU-300	3.1/2"	3"	5/8"
GFS114GU	3.1/2"	3.1/2"	5/8"
GFS116GU-312	4"	3.1/2"	5/8"
GFS116GU	4"	4"	5/8"
Tech Sheet 1631			

6000 psi, BSPP, Metric Mount

0300	Flange Size	Thread	Bolt Type Metric
GFS401GM-038	1/2"	3/8"	M8
GFS401GM-012	1/2"	1/2"	M8
GFS402GM-012	3/4"	1/2"	M10
GFS402GM	3/4"	3/4"	M10
GFS403GM	1"	1"	M12
GFS404GM-100	1.1/4"	1"	M14
GFS404GM	1.1/4"	1.1/4"	M14
GFS405GM-114	1.1/2"	1.1/4"	M16
GFS405GM	1.1/2"	1.1/2"	M16
GFS406GM-112	2"	1.1/2"	M20
GFS406GM	2"	2"	M20
Tech Sheet 1631			

6000 psi, BSPP, UNC Mount

0300	Flange Size	Thread	Bolt Type Metric
GFS401GU-038	1/2"	3/8"	1/2"
GFS401GU-012	1/2"	1/2"	5/16"
GFS402GU-012	3/4"	1/2"	3/8"
GFS402GU	3/4"	3/4"	3/8"
GFS403GU	1"	1"	7/16"
GFS404GU-100	1.1/4"	1"	1/2"
GFS404GU	1.1/4"	1.1/4"	1/2"
GFS405GU-114	1.1/2"	1.1/4"	5/8"
GFS405GU	1.1/2"	1.1/2"	5/8"
GFS406GU-112	2"	1.1/2"	3/4"
GFS406GU	2"	2"	3/4"
Tech Sheet 1631			

Code Information: AFS = Flange with O-Ring Groove GFS = Flange with Flat Face

Fluid-Air Components Ltd

SAE FLANGES

Socket Weld Flanges



Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108

3000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS080SM-038	1/2"	17.5	M8
GFS080SM-A20	1/2"	20.3	M8
GFS080SM	1/2"	21.6	M8
GFS100SM-A25	3/4"	25.3	M10
GFS100SM	3/4"	27.2	M10
GFS102SM-A30	1"	30.3	M10
GFS102SM	1"	34	M10
GFS104SM-A38	1.1/4"	38.3	M10
GFS104SM	1.1/4"	42.8	M10
GFS106SM	1.1/2"	48.6	M12
GFS106SM-A50	1.1/2"	50.5	M12
GFS108S	2"	61	M12
GFS110SM	2.1/2"	76.6	M12
GFS112SM	3"	90.5	M16
GFS114SM	3.1/2"	103	M16
GFS116SM	4"	115.5	M16
Tech Sheet 1632			

3000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS080SU-038	1/2"	17.5	5/16"
GFS080SU-A20	1/2"	20.3	5/16"
GFS080SU	1/2"	21.6	5/16"
GFS100SU-A25	3/4"	25.3	3/8"
GFS100SU	3/4"	27.2	3/8"
GFS102SU-A30	1"	30.3	3/8"
GFS102SU	1"	34	3/8"
GFS104SU-A38	1.1/4"	38.3	7/16"
GFS104SU	1.1/4"	42.8	7/16"
GFS106SU	1.1/2"	48.6	1/2"
GFS106SU-A50	1.1/2"	50.5	1/2"
GFS108SU	2"	61	1/2"
GFS110SU	2.1/2"	76.6	1/2"
GFS112SU	3"	90.5	5/8"
GFS114SU	3.1/2"	103	5/8"
GFS116SU	4"	115.5	5/8"
Tech Sheet 1632			

6000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS401SM-038	1/2"	17.5	M8
GFS401SM-A20	1/2"	20.3	M8
GFS401SM-012	1/2"	21.6	M8
GFS402SM-A25	3/4"	25.3	M10
GFS402SM	3/4"	27.2	M10
GFS403SM-A30	1"	30.3	M12
GFS403SM	1"	34	M12
GFS404SM-A38	1.1/4"	38.3	M14
GFS404SM	1.1/4"	42.8	M14
GFS405SM	1.1/2"	48.6	M16
GFS405SM-A50	1.1/2"	50.5	M16
GFS406SM	1.1/2"	61	M20
GFS407SM	2.1/2"	76.6	M24
Tech Sheet 1632			

6000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS401SU-038	1/2"	17.5	5/16"
GFS401SU-A20	1/2"	20.3	5/16"
GFS401SU-012	1/2"	21.6	5/16"
GFS402SU-A25	3/4"	25.3	3/8"
GFS402SU	3/4"	27.2	3/8"
GFS403SU-A30	1"	30.3	7/16"
GFS403SU	1"	34	7/16"
GFS404SU-A38	1.1/4"	38.3	1/2"
GFS404SU	1.1/4"	42.8	1/2"
GFS405SU	1.1/2"	48.6	5/8"
GFS405SU-A50	1.1/2"	50.5	5/8"
GFS406SU	1.1/2"	61	3/4"
Tech Sheet 1632			

Socket Weld Flanges



Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108

3000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS080S-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS080S-A20	1/2"	20.3	M8 x 30	5/16" x 1.1/4"
AFS080S	1/2"	21.6	M8 x 30	5/16" x 1.1/4"
AFS100S-A25	3/4"	25.3	M10 x 35	3/8" x 1.1/2"
AFS100S	3/4"	27.2	M10 x 35	3/8" x 1.1/2"
AFS102S-A30	1"	30.3	M10 x 35	3/8" x 1.1/2"
AFS102S	1"	34	M10 x 35	3/8" x 1.1/2"
AFS104S-A38	1.1/4"	38.3	M10 x 40	7/16" x 1.1/2"
AFS106S	1.1/2"	48.6	M12 x 45	1/2" x 1.3/4"
AFS106S-A50	1.1/2"	50.5	M12 x 45	1/2" x 1.3/4"
AFS108S	2"	61	M12 x 45	1/2" x 1.3/4"
AFS110S	2.1/2"	76.6	M12 x 45	1/2" x 1.3/4"
AFS114S	3.1/2"	103	M16 x 50	5/8" x 2"
AFS116S	4"	115.5	M16 x 50	5/8" x 2"
Tech Sheet 1633				

6000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS401S-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS401S-A20	1/2"	20.3	M8 x 30	5/16" x 1.1/4"
AFS401S-012	1/2"	21.6	M8 x 30	5/16" x 1.1/4"
AFS402S-A25	3/4"	25.3	M10 x 35	3/8" x 1.1/2"
AFS402S	3/4"	27.2	M10 x 35	3/8" x 1.1/2"
AFS403S-A30	1"	30.3	M12 x 45	7/16" x 1.3/4"
AFS403S	1"	34	M12 x 45	7/16" x 1.3/4"
AFS404S-A38	1.1/4"	38.3	M14 x 45	1/2" x 1.3/4"
AFS404S	1.1/4"	42.8	M14 x 45	1/2" x 1.3/4"
AFS405S	1.1/2"	48.6	M16 x 50	5/8" x 2"
AFS405S-A50	1.1/2"	50.5	M16 x 50	5/8" x 2"
AFS406S	2"	61	M20 x 65	3/4" x 2.1/2"
Tech Sheet 1633				

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAE FLANGES

havIT

Socket Weld Flanges 90º

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi, Metric

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS080/90S-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS080/90S	1/2"	21.6	M8 x 30	5/16" x 1.1/4"
AFS100/90S	3/4"	27.2	M10 x 35	3/8" x 1.1/2"
AFS106/90S	1.1/2"	48.6	M12 x 45	7/16" x 1.3/4"
		Tech Sheet 1634		

6000 psi, Metric

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS401/90S-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS401/90S-012	1/2"	21.6	M8 x 30	5/16" x 1.1/4"
AFS402/90S	3/4"	27.2	M10 x 35	3/8" x 1.1/2"
AFS403/90S	1"	34	M12 x 45	7/16" x 1.3/4"
AFS404/90S	1.1/4"	42.8	M14 x 50	1/2" x 1.3/4"
AFS405/90S	1.1/2"	48.6	M16 x 50	5/8" x 2"
AFS406/90S	2"	61	M20 x 110	-
		Tech Sheet 1634		

Butt Weld Flanges

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS080ST-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS080ST	1/2"	21.5	M8 x 30	5/16" x 1.1/4"
AFS100ST	3/4"	28	M10 x 35	3/8" x 1.1/2"
AFS102ST	1"	34	M10 x 35	3/8" x 1.1/2"
AFS104ST	1.1/4"	42.8	M10 x 40	7/16" x 1.1/2"
AFS106ST	1.1/2"	48.6	M12 x 45	1/2" x 1.3/4"
AFS108ST	2"	61	M12 x 45	1/2" x 1.3/4"
AFS110ST	2.1/2"	77	M12 x 45	1/2" x 1.3/4"
AFS112ST	3"	92	M16 x 50	5/8" x 2"
AFS114ST	3.1/2"	103	M16 x 50	5/8" x 2"
AFS116ST	4"	115.5	M16 x 50	5/8" x 2"
		Tech Sheet 1635		

6000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bolt Type UNC
AFS401ST-038	1/2"	17.5	M8 x 30	5/16" x 1.1/4"
AFS401ST-012	1/2"	21.5	M8 x 30	5/16" x 1.1/4"
AFS402ST	3/4"	28	M10 x 35	3/8" x 1.1/2"
AFS403ST	1"	34	M12 x 45	7/16" x 1.3/4"
AFS404ST	1.1/4"	42.8	M14 x 45	1/2" x 1.3/4"
AFS405ST	1.1/2"	48.6	M16 x 50	5/8" x 2"
AFS406ST	2"	61	M20 x 65	3/4" x 2.1/2"
		Tech Sheet 1635		

Butt Weld Flanges 90º

Bolts, washers and O-Rings are not included and must be purchased separately
Please see page 108



3000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bore Size mm
AFS200/90ST	3/4"	27	M10 x 40	27
AFS202/90ST	1"	34.5	M10 x 45	34.5
AFS204/90ST	1.1/4"	43	M10 x 45	43
AFS206/90ST	1.1/2"	50	M12 x 50	50
AFS208/90ST	2"	65	M12 x 70	65
		Tech Sheet 1636		

6000 psi

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric	Bore Size mm
AFS700/90ST	3/4"	28	M10 x 35	28
AFS702/90ST	1"	34	M12 x 45	34
AFS704/90ST	1.1/4"	42	M14 x 50	42
AFS706/90ST	1.1/2"	48	M16 x 50	48
AFS708/90ST	2"	65	M20 x 110	65
		Tech Sheet 1636		

Code Information: AFS = Flange with O-Ring Groove
GFS = Flange with Flat Face



For **Bolts, Spring Washers & O-Rings** see page **108**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAE FLANGES

Butt Weld Flanges-Companion (Counter)

Bolts, washers and O-Rings are not included
and must be purchased separately
Please see page 108



3000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS080STM-038	1/2"	17.5	M8
GFS080STM	1/2"	21.5	M8
GFS100STM	3/4"	28	M10
GFS102STM	1"	34	M10
GFS104STM	1.1/4"	42.8	M10
GFS106STM	1.1/2"	48.6	M12
GFS108STM	2"	61	M12
GFS110STM	2.1/2"	77	M12
GFS112STM	3"	92	M16
GFS114STM	3.1/2"	103	M16
GFS116STM	4"	115.5	M16
Tech Sheet 1637			

3000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type UNC
GFS080STU-038	1/2"	17.5	5/16"
GFS080STU	1/2"	21.5	5/16"
GFS100STU	3/4"	28	3/8"
GFS102STU	1"	34	3/8"
GFS104STU	1.1/4"	42.8	7/16"
GFS106STU	1.1/2"	48.6	1/2"
GFS108STU	2"	61	1/2"
GFS110STU	2.1/2"	77	1/2"
GFS112STU	3"	92	5/8"
GFS114STU	3.1/2"	103	5/8"
GFS116STU	4"	115.5	5/8"
Tech Sheet 1637			

6000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
GFS401STM-038	1/2"	17.5	M8
GFS401STM-012	1/2"	21.5	M8
GFS402STM	3/4"	28	M10
GFS403STM	1"	34	M12
GFS404STM	1.1/4"	42.8	M14
GFS405STM	1.1/2"	48.6	M16
GFS406STM	2"	61	M20
Tech Sheet 1637			

6000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type UNC
GFS401STU-038	1/2"	17.5	5/16"
GFS401STU-012	1/2"	21.5	5/16"
GFS402STU	3/4"	28	3/8"
GFS403STU	1"	34	7/16"
GFS404STU	1.1/4"	42.8	1/2"
GFS405STU	1.1/2"	48.6	5/8"
GFS406STU	2"	61	3/4"
Tech Sheet 1637			

Code Information: AFS = Flange with O-Ring Groove GFS = Flange with Flat Face



For **Hydraulic Tubing**
see pages **179-183**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAE FLANGES

havit

Socket Weld Coupling Set



Bolts, washers and O-Rings included

3000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
DFS080SM-038	1/2"	17.5	M8
DFS080SM-A20	1/2"	20.3	M8
DFS080SM	1/2"	21.6	M8
DFS100SM-A25	3/4"	25.3	M10
DFS100SM	3/4"	27.2	M10
DFS102SM-A30	1"	30.3	M10
DFS102SM	1"	34	M10
DFS104SM-A38	1.1/4"	38.3	M10
DFS104SM	1.1/4"	42.8	M10
DFS106SM	1.1/2"	48.6	M12
DFS106SM-A50	1.1/2"	50.5	M12
DFS108SM	2"	61	M12
DFS110SM	2.1/2"	76.6	M12
DFS112SM	3"	90.5	M16
DFS114SM	3.1/2"	103	M16
DFS116SM	4"	115.5	M16
Tech Sheet 1638			

3000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type UNC
DFS080SU-038	1/2"	17.5	5/16"
DFS080SU-A20	1/2"	20.3	5/16"
DFS080SU	1/2"	21.6	5/16"
DFS100SU-A25	3/4"	25.3	3/8"
DFS100SU	3/4"	27.2	3/8"
DFS102SU-A30	1"	30.3	3/8"
DFS102SU	1"	34	3/8"
DFS104SU-A38	1.1/4"	38.3	7/16"
DFS104SU	1.1/4"	42.8	7/16"
DFS106SU	1.1/2"	48.6	1/2"
DFS106SU-A50	1.1/2"	50.5	1/2"
DFS108SU	2"	61	1/2"
DFS110SU	2.1/2"	76.6	1/2"
DFS112SU	3"	90.5	5/8"
DFS114SU	3.1/2"	103	5/8"
DFS116SU	4"	115.5	5/8"
Tech Sheet 1638			

6000 psi, Metric Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type Metric
DFS401SM-038	1/2"	17.5	M8
DFS401SM-A20	1/2"	20.3	M8
DFS401SM-012	1/2"	21.6	M8
DFS402SM-A25	3/4"	25.3	M10
DFS402SM	3/4"	27.2	M10
DFS403SM-A30	1"	30.3	M10
DFS403SM	1"	34	M10
DFS404SM-A38	1.1/4"	38.3	M10
DFS404SM	1.1/4"	42.8	M10
DFS405SM	1.1/2"	48.6	M12
DFS405SM-A50	1.1/2"	50.5	M12
DFS406SM	2"	61	M12
Tech Sheet 1638			

6000 psi, UNC Mount

0300	Flange Size	Boss Weld Diameter mm	Bolt Type UNC
DFS401SU-038	1/2"	17.5	5/16"
DFS401SU-A20	1/2"	20.3	5/16"
DFS401SU-012	1/2"	21.6	5/16"
DFS402SU-A25	3/4"	25.3	3/8"
DFS402SU	3/4"	27.2	3/8"
DFS403SU-A30	1"	30.3	3/8"
DFS403SU	1"	34	3/8"
DFS404SU-A38	1.1/4"	38.3	7/16"
DFS404SU	1.1/4"	42.8	7/16"
DFS405SU	1.1/2"	48.6	1/2"
DFS405SU-A50	1.1/2"	50.5	1/2"
DFS406SU	2"	61	1/2"
Tech Sheet 1638			

Bolts & Spring Washers

Metric, Set of 4

0300	Thread
M8X25	M8 x 25
M8X30	M8 x 30
M10X30	M10 x 30
M10X35	M10 x 35
M10X40	M10 x 40
M10X45	M10 x 45
M12X35	M12 x 35
M12X45	M12 x 45
M12X50	M12 x 50
M12X70	M12 x 70
M14X45	M14 x 45
M14X50	M14 x 50
M16X55	M16 x 55
M20X60	M20 x 60
M20X65	M20 x 65
M20X70	M20 x 70
M20X110	M20 x 110



UNC, Set of 4

0300	Thread
UNC3/8X11/4	3/8" x 1.1/4"
UNC3/8X11/2	3/8" x 1.1/2"
UNC7/16X11/2	7/16" x 1.1/2"
UNC7/16X13/4	7/16" x 1.3/4"
UNC1/2X13/4	1/2" x 1.3/4"
UNC1/2X11/2	1/2" x 1.1/2"
UNC5/8X2	5/8" x 2"
UNC5/16X11/4	5/16" x 1.1/4"
UNC3/4X21/2	3/4" x 2.1/2"

O-Rings



Buna

0300	Size
1/2-ORING	1/2"
3/4-ORING	3/4"
1-ORING	1"
11/4-ORING	1.1/4"
11/2-ORING	1.1/2"
2-ORING	2"
21/2-ORING	2.1/2"
3-ORING	3"
31/2-ORING	3.1/2"
4-ORING	4"
5-ORING	5"
Tech Sheet 1639	

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


HYDRAULIC SEALS



Self Centering Bonded Seals
Standard Bonded Seals
Fibre Washers
Washers
Bonded Seals
O-Rings
Flaretite
SAE Flange Seals
ORFS Seal Kit
CAT Flange Seals
Splicing Kit
Seal Kits

HYDRAULIC SEALS

Self Centering Bonded Seals



Mild Steel, Nitrile, to suit BSPP Threads

1005	To Suit
BS-18	1/8"
BS-14	1/4"
BS-38	3/8"
BS-12	1/2"
BS-34	3/4"
BS-1	1"
BS-114	1.1/4"
BS-112	1.1/2"
BS-2	2"
Tech Sheet 10513	

Mild Steel, Viton, to suit BSPP Threads

1005	To Suit
BSV-18	1/8"
BSV-14	1/4"
BSV-38	3/8"
BSV-12	1/2"
BSV-58	5/8"
BSV-34	3/4"
BSV-1	1"
BSV-114	1.1/4"
BSV-112	1.1/2"
BSV-2	2"
Tech Sheet 10513	

316 Stainless Steel, Nitrile

1005	To Suit
BS-18N	1/8"
BS-14N	1/4"
BS-38N	3/8"
BS-12N	1/2"
BS-34N	3/4"
BS-1N	1"
BS-114N	1.1/4"
BS-112N	1.1/2"
BS-2N	2"
Tech Sheet 10513	

316 Stainless Steel, Viton

1005	To Suit
BS-14V	1/4"
BS-38V	3/8"
BS-12V	1/2"
BS-34V	3/4"
BS-1V	1"
BS-112V	1.1/2"
Tech Sheet 10513	

Mild Steel, Nitrile, to suit Metric Threads

1005	To Suit
BS-M8	M8
BS-M10	M10
BS-M12	M12
BS-M14	M14
BS-M16	M16
BS-M18	M18
BS-M22	M22

Standard Bonded Seals (Not Self Centering)



Mild Steel, Nitrile, to suit JIC/UNF Thread Form

1005	To Suit
BS-14JIC	1/4"
BS-516JIC	5/16"
BS-716JIC	7/16"
BS-12JIC	1/2"
BS-916JIC	9/16"
BS-58JIC	5/8"
BS-1116JIC	11/16"
BS-34JIC	3/4"
BS-1516JIC	15/16"
BS-1-116JIC	1.1/16"
BS-1-18JIC	1.1/8"
BS-1-14JIC	1.1/4"
Tech Sheet 10513	

Mild Steel, Nitrile, to suit JIC/UNF Thread Form

1005	To Suit
BS-6BA	6BA
BS-4BA	4BA
BS-2BA	2BA

Fibre Washers



1005	To Suit
FW5M	M5
FW18	1/8"
FW14	1/4"
FW38	3/8"
FW12	1/2"
FW34	3/4"
FW1	1"
FW114	1.1/4"
FW112	1.1/2"
FW2	2"
Tech Sheet 20357	

Washers



Flat Copper Washer, Metric

1300	BSPP Male Thread	OD ID x Thickness
CWM8	M8	11 x 8 x 0.9
CWM10	M10	16 x 10 x 1
CWM12	M12	16 x 12 x 1
CWM14	M14	18 x 14 x 1
CWM16	M16	20 x 16 x 1.5
CWM18	M18	24 x 18 x 1.5
CWM22	M22	27 x 22 x 1.75



Copper Washers for BSPP Stud Ends

1300	Male Thread	Female Thread
CW18	1/8"	3/8"
CW14	1/4"	1/2"
CW38	3/8"	3/4"
CW12	1/2"	7/8"
CW34	3/4"	-
CW1	1"	-
CW114	1.1/4"	-
CW112	1.1/2"	-
CW2	2"	-
Tech Sheet 20358		



Nylon, Notched

1030	Thread
D11X-5M	M5
D11X-1/8	1/8"
D11X-1/4	1/4"
D11X-3/8	3/8"
D11X-1/2	1/2"
D11X-3/4	3/4"
Tech Sheet 10705	

Bonded Seals



Stainless Steel, Nitrile, to suit Metric Threads

1005	To Suit
SSBSM04N	M4
SSBSM06N	M6
SSBSM08N	M8
SSBSM10N	M10
SSBSM12N	M12
SSBSM14N	M14
SSBSM16N	M16
SSBSM20N	M20

Fluid-Air Components Ltd

HYDRAULIC SEALS

O-Rings



Imperial O-Rings, Nitrile 70 Shore, Per Pack of 100

1005	ID	Wall Thickness Imperial
ORING-BS006N	1/8"	0.07
ORING-BS007N	5/32"	0.07
ORING-BS008N	3/16"	0.07
ORING-BS009N	7/32"	0.07
ORING-BS010N	1/4"	0.07
ORING-BS011N	5/16"	0.07
ORING-BS012N	3/8"	0.07
ORING-BS110N	3/8"	0.103
ORING-BS111N	7/16"	0.103
ORING-BS112N	1/2"	0.103
ORING-BS113N	9/16"	0.103
ORING-BS114N	5/8"	0.103
ORING-BS115N	11/16"	0.103
ORING-BS116N	3/4"	0.103
ORING-BS210N	3/4"	0.139
ORING-BS211N	13/16"	0.139
ORING-BS212N	7/8"	0.139
ORING-BS213N	15/16"	0.139
ORING-BS214N	1"	0.139
ORING-BS215N	1.1/16"	0.139
ORING-BS216N	1.1/8"	0.139
ORING-BS217N	1.3/16"	0.139
ORING-BS218N	1.1/4"	0.139
ORING-BS219N	1.5/16"	0.139
ORING-BS220N	1.3/8"	0.139
ORING-BS221N	1.7/16"	0.139
ORING-BS222N	1.1/2"	0.139
ORING-BS325N	1.1/2"	0.21
ORING-BS326N	1.5/8"	0.21
ORING-BS327N	1.3/4"	0.21

Imperial O-Rings, Viton 75 Shore, Per Pack of 100

1005	ID	Wall Thickness Imperial
ORING-BS006V	1/8"	0.07
ORING-BS008V	3/16"	0.07
ORING-BS009V	7/32"	0.07
ORING-BS010V	1/4"	0.07
ORING-BS011V	5/16"	0.07
ORING-BS012V	3/8"	0.07
ORING-BS110V	3/8"	0.103
ORING-BS112V	1/2"	0.103
ORING-BS116V	3/4"	0.103
ORING-BS211V	13/16"	0.139
ORING-BS212V	7/8"	0.139
ORING-BS218V	1.1/4"	0.139
ORING-BS221V	1.7/16"	0.139

Metric O-Rings, Nitrile 70 Shore, Per Pack of 100

1005	ID mm	Wall Thickness mm
M-3X2	3	2
M-4X2	4	2
M-5X2	5	2
M-6X2	6	2
M-7X2	7	2
M-8X2	8	2
M-10X2	10	2
M-10X2.5	10	2.5
M-11X2.5	11	2.5
M-12X2.5	12	2.5
M-14X2.5	14	2.5
M-16X2.5	16	2.5
M-17X2.5	17	2.5
M-19X2.5	19	2.5
M-19X3	19	3
M-20X3	20	3
M-22X3	22	3
M-24X3	24	3
M-25X3	25	3
M-27X3	27	3
M-28X3	28	3
M-30X3	30	3
M-32X3	32	3
M-33X3	33	3
M-35X3	35	3
M-36X3	36	3
M-38X3	38	3
M-38X4	38	4
M-41X4	41	4
M-44X4	44	4

Flaretite



The Flaretite Seal is a metal stamping, designed with multiple, concentric sealing rings.

The entire seal is coated with a **dry-to-the-touch**, baked-on Loctite™ sealant. When inserted into a fitting, the concentric rings form multiple seals down the face of the flare, while the Loctite™ coating fills minor imperfections, dramatically increasing the integrity of the fitting. New ISO and NFPA standards strongly recommend seals for all fittings.

- **Fits all standard JIC/SAE/JIS** flare fittings, hydraulic and pneumatic
- Has a **user-friendly tab to clip the seal** onto the fitting
- **Protects against weeping** on new and damaged fittings
- Creates a perfect **leak-free clip-on seal, guaranteed**
- Complies with latest international standards

Other seals available on request.

Working Temperature:
-40°C to +150°C



Flaretite Seal Installed

Flaretite 304 Stainless Steel, JIC 37°

0266	JIC Thread
FF13267	7/16"
FF13268	9/16"
FF13269	3/4"
FF13270	7/8"
FF13271	1.1/16"
FF13272	1.5/16"
FF13273	1.5/8"
FF13570	1.7/8"
FF13571	2.1/2"
Tech Sheet 20353	

For **JIC Adaptors** see pages **72-80**

HYDRAULIC SEALS

SAE Flange Seals

Designed to fit the SAE J518 location grooves. Made from high performance grade of polyurethane, the material provides excellent resistance-to-gap extrusion. Covers a wide temperature range from -40°C to +110°C at pressures up to 400 bar.

Contents:
10 x 1/2"
10 x 3/4"
10 x 1"
10 x 1.1/4"
10 x 1.1/2"
10 x 2"



1005	No. of Parts	Type
SAE-KIT01	60	SAE Flange
Tech Sheet 68214		

CAT Flange Seals

CAT D-Rings provide a high pressure seal between flange and port face on C T hose assemblies. Can be used in conjunction with CAT XT-5 and XT-6 type flanges.

Material: Nitrile
Contents:
10 x 3/4"
10 x 1"
10 x 1.1/4"
10 x 1.1/2"
10 x 2"



1005	No. of Parts	Type
CAT-KIT01	50	CAT Flange
Tech Sheet 68216		

ORFS Seal Kit

O-Ring face seal kit to suit ORFS male fittings

Material: Nitrile
Contents:
50 x 9/16"
50 x 11/16"
30 x 13/16"
30 x 1"
30 x 1.3/16
20 x 1.7/16"
20 x 1.11/16"



1005	No. of Parts	Type
ORFS-KIT01	230	ORFS
Tech Sheet 68215		

Splicing Kit

Ideal for repairing or replacing damaged O-Ring seals.

Material: Nitrile
Contents:
14 x standard sizes of O-Ring cord
1 x tape measure
1 x cutting block
(for butt or scarf joins)
1 x cutting knife
1 x tube glue

Rubber Cord:
2 metres of each size:
1.78, 2, 2.4, 2.62, 3, 3.53, 4, 4.5, 5, 5.33, 5.7, 6, 7 and 8mm.



O-Ring Splicing Kit

1005
SPLICING-KIT01
Tech Sheet 68213

Seal Kits



Assorted Bonded Seals

1005	No. of Parts	Type
BSK-1	140	Imperial
BSK-2	140	Metric
Tech Sheet 20372		



Assorted O-Rings

1005	No. of Parts	Type
IOK-1	382	Imperial
MOK-1	404	Metric
Tech Sheet 20373		

Fluid-Air Components Ltd

PLASTIC CAPS & PLUGS

SR 1077 Threaded Fitting Plugs

- Knurled head for easy application
- Ideal for sealing 37° flare fittin



Red LDPE, UNF Thread

0307	Thread
110228	5/16"
110177	3/8"
110178	7/16"
110179	1/2"
110180	9/16"
110181	5/8"
110182	3/4"
110183	7/8"
110184	1.1/16"



For **Hydraulic Adaptors** see pages **52-108**

SR 1002 Threaded Protection Plugs

- Easy to grip head
- Thread ensures secure fi
- Excellent protection from dirt, moisture and corrosion
- Widely used in hydraulic, pneumatic and general engineering industries



Red LDPE, UNF/JIC Thread

0307	Thread
10692	3/8"
10763	7/16"
10696	1/2"
10668	9/16"
10940	5/8"
10575	3/4"
12827	13/16"
10326	7/8"
12785	1"
10460	1.1/16"
11506	1.3/16"
10671	1.5/16"
11752	1.5/8"
11755	1.7/8"

Red LDPE, Metric Thread

0307	Thread
12011	M8 x 1
12012	M10 x 1
12013	M12 x 1
12017	M12 x 1.5
12018	M14 x 1.5
12019	M16 x 1.5
10458	M18 x 1.5
12020	M20 x 1.5
10128	M22 x 1.5
12021	M24 x 1.5
12022	M25 x 1.5
12023	M26 x 1.5

Red LDPE, BSP/Gas

0307	Thread
10651	1/8" x 28
10588	1/4" x 19
10996	3/8" x 19
10590	1/2" x 14
10511	5/8" x 14
10731	3/4" x 14
10810	1" x 11
10459	1.1/4" x 11
11242	1.1/2" x 11

SR 1018 Threaded Protection Caps

- Used throughout the automotive, fluid power and engineering industries
- Protect threaded components from dust, moisture and damage



Red LDPE, UNF/JIC Thread

0307	Thread
10251	3/8"
12652	7/16"
10332	7/16"
10528	1/2"
11041	9/16"
10653	5/18"
12847	3/4"
11089	7/8"
12075	7/8"
12826	1"
10685	1.1/16"
10163	1.3/16"
10151	1.5/16"

Red LDPE, Metric Thread

0307	Thread
12100	M8 x 1
12101	M10 x 1
12102	M12 x 1
12103	M12 x 1.5
12104	M14 x 1.5
12650	M14 x 1.5
12105	M16 x 1.5
12106	M18 x 1.5
12107	M20 x 1.5
12845	M22 x 1.5
12109	M24 x 1.5
12110	M25 x 1.5
12967	M28 x 1.5
12122	M30 x 2
12123	M36 x 2
12124	M42 x 2
12126	M52 x 2

Red LDPE, BSP/Gas

0307	Thread
10392	1/8" x 28
10559	1/4" x 19
10104	3/8" x 19
10198	1/2" x 14
11157	5/8" x 14
10205	3/4" x 14
10204	1" x 11
10167	1.1/4" x 11
10432	1.1/2" x 11
10968	2" x 11

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PLASTIC CAPS & PLUGS

SR 1000 Tapered Caps/Plugs

- Use as cap or plug
- Easy fitting and remova
- Provide excellent protection from damage, dirt, moisture and corrosion during storage and transport



Red LDPE

0307	To Suit Hose ID	To Suit Hose OD
10991	6.1	4.4
10727	7.6	6.2
10549	9.1	7.7
10289	10	8.4
10750	11.8	10
10114	12.3	10.9
10438	15.3	13.6
10342	16	14.2
10424	17	14.7
11139	18.3	16.4
10394	20	17.8
10136	26.4	23.4
10732	27.7	24.7
10272	32.6	30
10181	37.2	33.3
10491	40.6	36.9
10485	42.7	39.6



For **Hydraulic Tube** see pages **179-183**

SR 1125 O-Ring Threaded Plugs

- Can be applied by spanner, screwdriver or socket; manually or with power tool



Yellow HDPE, Metric Thread

0307	Thread
467087	M8 x 1
467088	M10 x 1
467089	M12 x 1
467090	M10 x 1.5
467091	M12 x 1.5
467092	M14 x 1.5
467093	M16 x 1.5
467094	M18 x 1.5
467095	M20 x 1.5
467096	M22 x 1.5

Yellow HDPE, UNF Thread

0307	Thread
467114	3/8" x 24
467115	7/16" x 20
467116	1/2" x 20
467117	9/16" x 18
467118	5/8" x 18
467119	3/4" x 16
467120	7/8" x 14
467121	1" x 14

Yellow HDPE, BSP Thread

0307	Thread
467127	1/8" x 28
467128	1/4" x 19
467129	3/8" x 19
467130	1/2" x 14
467131	5/8" x 14
467133	7/8" x 14
467134	1" x 11

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Walform® Machine Hire



Most popular cold forming tube fitting system in the world!

Hassle free hire includes:

- **Walform machine**
- **Tooling**
- **Shipping and Collection**

Hire available now with an order for Danfoss Waltech compression fittings, tube and clamps

Contact your Account Manager to discuss your requirements

Danfoss's Waltech Trilogy

- Simple final in service assembly with prefabricated tube ends
- Best in class performance
- Maximum system stability and safety
- Superior quality
- Global availability


WALPRO®



WALRING



WALFORM™



Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

COMPONENT PARTS

Threaded Plugs

Captive nitrile seal.



BSPP

0350	Thread
VSR1/8WD	1/8"
VSR1/4WD	1/4"
VSR3/8WD	3/8"
VSR1/2WD	1/2"
VSR3/4WD	3/4"
VSR1WD	1"
VSR11/4WD	1.1/4"
VSR11/2WD	1.1/2"
Tech Sheet 1656	

Captive nitrile seal



Metric

0350	Thread
VSM8X1.0WD	M8 x 1.0
VSM12X1.5WD	M12 x 1.5
VSM14X1.5WD	M14 x 1.5
VSM16X1.5WD	M16 x 1.5
VSM18X1.5WD	M18 x 1.5
VSM20X1.5WD	M20 x 1.5
VSM22X1.5WD	M22 x 1.5
VSM26X1.5WD	M26 x 1.5
VSM27X2WD	M27 x 2
VSM33X2WD	M33 x 2
VSM42X2WD	M42 x 2
VSM48X2WD	M48 x 2
Tech Sheet 1656	

Blanking Plugs



Extra Light-duty

0350	To Suit Tube OD mm
VSD4LLMMB	4
VSD6LLMMD	6
VSD8LLMMD	8
Tech Sheet 1657	

Light-duty

0350	To Suit Tube OD mm
VSD6L/SMMB	6
VSD8L/SMMB	8
VSD10L/SMMB	10
VSD12L/SMMB	12
VSD15LMMB	15
VSD18LMMB	18
VSD22LMMB	22
VSD28LMMB	28
VSD35LMMB	35
VSD42LMMB	42
Tech Sheet 1657	

Heavy-duty

0350	To Suit Tube OD mm
VSD14SMMB	14
VSD16SMMB	16
VSD20SMMB	20
VSD25SMMB	25
VSD30SMMB	30
VSD38SMMB	38
Tech Sheet 1657	

Blanking Ends

Suitable for swivel end connectors.



Light-duty

0350	OD mm	Max Pressure Bar
VSK6L	6	500
VSK8L	8	500
VSK10L	10	500
VSK12L	12	400
VSK15L	15	400
VSK18L	18	400
VSK22L	22	250
VSK28L	28	250
VSK35L	35	250
VSK42L	42	250
Tech Sheet 1658		

Heavy-duty

0350	OD mm	Max Pressure Bar
VSK6S	6	800
VSK8S	8	800
VSK10S	10	800
VSK12S	12	630
VSK14S	14	630
VSK16S	16	630
VSK20S	20	420
VSK25S	25	420
VSK30S	30	420
VSK38S	38	420
Tech Sheet 1658		

For **Hose & Pipe Cleaning Kits** see page **49**



Fluid-Air Components Ltd

COMPONENT PARTS

Walring Nuts c/w Profile Ring & O-Ring



Metric, Light-duty Viton

0350	Thread	OD mm	Max Pressure Bar
WR6LVIA2M	M12 x 1.5	6	500
WR8LVIA2M	M14 x 1.5	8	500
WR10LVIA2M	M16 x 1.5	10	500
WR12LVIA2M	M18 x 1.5	12	400
WR15LVIA2M	M22 x 1.5	15	400
WR18LVIA2M	M26 x 1.5	18	400
WR22LVIA2M	M30 x 2	22	250
WR28LVIA2M	M36 x 2	28	250
WR35LVIA2M	M45 x 2	35	250
WR42LVIA2M	M52 x 2	42	250
Tech Sheet 1660			

Metric, Heavy-duty Viton

0350	Thread	OD mm	Max Pressure Bar
WR6SVIA2M	M14 x 1.5	6	800
WR8SVIA2M	M16 x 1.5	8	800
WR12SVIA2M	M20 x 1.5	12	630
WR16SVIA2M	M24 x 1.5	16	630
WR20SVIA2M	M30 x 2	20	420
WR25SVIA2M	M36 x 2	25	420
WR30SVIA2M	M42 x 2	30	420
WR38SVIA2M	M52 x 2	38	420
Tech Sheet 1660			

Metric, Light-duty Nitrile

0350	Thread	OD mm	Max Pressure Bar
WR6LA2M	M12 x 1.5	6	500
WR8LA2M	M14 x 1.5	8	500
WR10LA2M	M16 x 1.5	10	500
WR12LA2M	M18 x 1.5	12	400
WR15LA2M	M22 x 1.5	15	400
WR18LA2M	M26 x 1.5	18	400
WR22LA2M	M30 x 2	22	250
WR28LA2M	M36 x 2	28	250
WR35LA2M	M45 x 2	35	250
WR42LA2M	M52 x 2	42	250
Tech Sheet 1660			

Metric, Heavy-duty Nitrile

0350	Thread	OD mm	Max Pressure Bar
WR6SA2M	M14 x 1.5	6	800
WR10SA2M	M18 x 1.5	10	800
WR12SA2M	M20 x 1.5	12	630
WR16SA2M	M24 x 1.5	16	630
WR20SA2M	M30 x 2	20	420
WR25SA2M	M36 x 2	25	420
WR38SA2M	M52 x 2	38	420
Tech Sheet 1660			

DIN 2353 Walform Nuts



Light-duty

0350	Thread	OD mm	Max Pressure Bar
M-6L	M12 x 1.5	6	500
M-8L	M14 x 1.5	8	500
M-10L	M16 x 1.5	10	500
M-12L	M18 x 1.5	12	400
M-15L	M22 x 1.5	15	400
M-18L	M26 x 1.5	18	400
M-22L	M30 x 2	22	250
M-28L	M36 x 2	28	250
M-35L	M45 x 2	35	250
M-42L	M52 x 2	42	250

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
M6S	M14 x 1.5	6	800
M8S	M16 x 1.5	8	800
M10S	M18 x 1.5	10	800
M12S	M20 x 1.5	12	630
M14S	M22 x 1.5	14	630
M16S	M24 x 1.5	16	420
M20S	M30 x 2	20	420
M25S	M36 x 2	25	420
M30S	M42 x 2	30	420
M38S	M52 x 2	38	420

Walpro Nut & Profile Ring



Extra Light-duty

0350	OD mm	Max Pressure Bar
SR-M 4 LL	4	100
SR-M 6 LL	6	100
SR-M 8 LL	8	100


Light-duty

0350	OD mm	Max Pressure Bar
PR-M 6 L	6	500
PR-M 8 L	8	500
PR-M 10 L	10	500
PR-M 12 L	12	400
PR-M 15 L	15	400
PR-M 18 L	18	400
PR-M 22 L	22	250
PR-M 28 L	28	250
PR-M 35 L	35	250
PR-M 42 L	42	250

Heavy-duty

0350	OD mm	Max Pressure Bar
PR-M 6 S	6	800
PR-M 8 S	8	800
PR-M 10 S	10	800
PR-M 12 S	12	630
PR-M 14 S	14	630
PR-M 16 S	16	420
PR-M 20 S	20	420
PR-M 25 S	25	420
PR-M 30 S	30	420
PR-M 38 S	38	420

FT PRO®



You might also need
CETOP 3 Manifold
see page **208**

Fluid-Air Components Ltd

COMPONENT PARTS

Walform Plus Viton Captive Seal



Light-duty

0350	To Suit Nut
WF-WD18LVI	18L
WF-WD22LVI	22L
WF-WD28LVI	28L
WF-WD35LVI	35L
WF-WD42LVI	42L
Tech Sheet 1660	

Heavy-duty

0350	To Suit Nut
WF-WD16SVI	16S
WF-WD20SVI	20S
WF-WD25SVI	25S
WF-WD30SVI	30S
WF-WD38SVI	38S
Tech Sheet 1660	

Walform Plus Nitrile Captive Seal



Light/Heavy-duty

0350	To Suit Nut
WF-WD6L/S	6L/S
WF-WD8L/S	8L/S
WF-WD10L/S	10L/S
WF-WD12L/S	12L/S
WF-WD15L	15L
WF-WD16S	16S
WF-WD18L	18L
WF-WD20S	20S
WF-WD22L	22L
WF-WD25S	25S
WF-WD28L	28L
WF-WD30S	30S
WF-WD35L	35L
WF-WD38S	38S
WF-WD42L	42L
Tech Sheet 1660	

Walform Nut & Seal



Light-duty, Viton

0350	OD mm
WF-M 6 L VI	6
WF-M 8 L VI	8
WF-M 10 L VI	10
WF-M 12 L VI	12
WF-M 15 L VI	15
WF-M 18 L VI	18
WF-M 22 L VI	22
WF-M 28 L VI	28
WF-M 35 L VI	35
WF-M 42 L VI	42

Light-duty, Nitrile

0350	OD mm
WF-M 6 L NBR	6
WF-M 8 L NBR	8
WF-M 10 L NBR	10
WF-M 12 L NBR	12
WF-M 15 L NBR	15
WF-M 18 L NBR	18
WF-M 22 L NBR	22
WF-M 28 L NBR	28
WF-M 35 L NBR	35
WF-M 42 L NBR	42

Heavy-duty, Viton

0350	OD mm
WF-M 6 S VI	6
WF-M 8 S VI	8
WF-M 10 S VI	10
WF-M 12 S VI	12
WF-M 16 S VI	16
WF-M 20 S VI	20
WF-M 25 S VI	25
WF-M 30 S VI	30
WF-M 38 S VI	38

Heavy-duty, Nitrile

0350	OD mm
WF-M 6 S NBR	6
WF-M 8 S NBR	8
WF-M 10 S NBR	10
WF-M 12 S NBR	12
WF-M 16 S NBR	16
WF-M 20 S NBR	20
WF-M 25 S NBR	25
WF-M 30 S NBR	30
WF-M 38 S NBR	38

Walform Machine Hire



Hire available with an order for Danfoss Waltech compression fittings, tube and clamp

Hassle free hire includes:
- **Walform machine**
- **Tooling**
- **Shipping and Collection**

Hire available now with order for Danfoss Waltech compression fittings

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

MALE STUD COUPLINGS

CUTTING RING COUPLINGS DIN 2353/ISO 8434-1

Waltech Hydraulic BITE TYPE Fittings

Waltech offer a complete product range and highest quality:
Based on this principle Waltech offers one of the most comprehensive product ranges for tube coupling systems.

The Waltech programme includes cutting ring, soft seal, flared coupling and flange couplings, plus a wide range of accessories

The Waltech range of hydraulic compression fittings cover sizes fro 6mm od to 42mm od in light-duty and from 6mm od to 38mm od in heavy-duty.

Manufactured to DIN 2353 standard, mild steel with C6F free surface coating, each compression fitting is supplied complete with cutting ring and nut

Pressure Range Guide:

Light-duty
6mm OD-18mm OD= 400 bar
22mm OD-42mm OD= 250 bar

Heavy-duty
6mm OD-16mm OD = 630 bar
20mm OD-25mm OD = 400 bar
30mm OD-38mm= 250 bar

These pressures are for guide purposes only and please consult our technical department for specific applications

BSPP 60° Cone



Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6LRFOA	1/8"	6	400
GEV8LR1/8FOA	1/8"	8	400
GEV6LR1/4FOA	1/4"	6	400
GEV8LRFOA	1/4"	8	400
GEV10LRFOA	1/4"	10	400
GEV12LR1/4FOA	1/4"	12	400
GEV6LR3/8FOA	3/8"	6	400
GEV8LR3/8FOA	3/8"	8	400
GEV10LR3/8FOA	3/8"	10	400
GEV12LRFOA	3/8"	12	400
GEV15LR3/8FOA	3/8"	15	400
GEV10LR1/2FOA	1/2"	10	400
GEV12LR1/2FOA	1/2"	12	400
GEV15LRFOA	1/2"	15	400
GEV18LRFOA	1/2"	18	400
GEV22LR1/2FOA	1/2"	22	250
GEV18LR3/4FOA	3/4"	18	400
GEV22LRFOA	3/4"	22	250
GEV28LR3/4FOA	3/4"	28	250
GEV28LRFOA	1"	28	250
GEV35LRFOA	1.1/4"	35	250
Tech Sheet 20898			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV8SRFOA	1/4"	8	630
GEV10SR1/4FOA	1/4"	10	630
GEV12SR1/4FOA	1/4"	12	630
GEV10SRFOA	3/8"	10	630
GEV12SRFOA	3/8"	12	630
GEV16SR3/8FOA	3/8"	16	630
GEV12SR1/2FOA	1/2"	12	630
GEV14SRFOA	1/2"	14	630
GEV16SRFOA	1/2"	16	630
GEV20SR1/2FOA	1/2"	20	400
GEV16SR3/4FOA	3/4"	16	630
GEV20SRFOA	3/4"	20	400
GEV25SR3/4FOA	3/4"	25	400
GEV25SRFOA	1"	25	400
GEV30SR1FOA	1"	30	250
GEV38SR1FOA	1"	38	250
GEV38SRFOA	1.1/2"	38	250
GEV30SR11/4FOA	1.1/4"	30	250
GEV38SR11/4FOA	1.1/4"	38	250
Tech Sheet 20898			

BSPT



Extra Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV4LLRK	1/8"	4	100
GEV6LLRK	1/8"	6	100
GEV8LLRK	1/8"	8	100
Tech Sheet 1661			

Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV8LRK	1/4"	8	250
GEV10LRK	1/4"	10	250
GEV12LR1/4K	1/4"	12	250
GEV10LR3/8K	3/8"	10	250
GEV12LRK	3/8"	12	250
GEV15LRK	1/2"	15	250
Tech Sheet 1661			

Form B, Metric



Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6LM12X1.5	M12 x 1.5	6	400
GEV8LM	M12 x 1.5	8	400
GEV10LM	M14 x 1.5	10	400
GEV8LM16X1.5	M16 x 1.5	8	400
GEV10LM16X1.5	M16 x 1.5	10	400
GEV12LM	M16 x 1.5	12	400
GEV10LM18X1.5	M18 x 1.5	10	400
GEV12LM18X1.5	M18 x 1.5	12	400
GEV15LM	M18 x 1.5	15	400
GEV18LM18X1.5	M18 x 1.5	18	400
GEV10LM22X1.5	M22 x 1.5	10	400
GEV12LM22X1.5	M22 x 1.5	12	400
GEV15LM22X1.5	M22 x 1.5	15	400
GEV18LM	M22 x 1.5	18	400
GEV22LM	M26 x 1.5	22	250
GEV28LM	M33 x 2	28	250
GEV35LM	M42 x 2	35	250
GEV42LM	M48 x 2	42	250
Tech Sheet 1662			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6SM	M12 x 1.5	6	630
GEV8SM	M14 x 1.5	8	630
GEV10SM	M16 x 1.5	10	630
GEV12SM	M18 x 1.5	12	630
GEV16SM18X1.5	M18 x 1.5	16	630
GEV14SM	M20 x 1.5	14	630
GEV16SM	M22 x 1.5	16	630
GEV20SM	M27 x 2	20	400
GEV25SM	M33 x 2	25	400
GEV30SM	M42 x 2	30	250
GEV38SM	M48 x 2	38	250
Tech Sheet 1662			

Fluid-Air Components Ltd

MALE STUD COUPLINGS

Form B, BSPP



Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6LR	1/8"	6	400
GEV8LR1/8	1/8"	8	400
GEV6LR1/4	1/4"	6	400
GEV8LR	1/4"	8	400
GEV10LR	1/4"	10	400
GEV12LR1/4	1/4"	12	400
GEV6LR3/8	3/8"	6	400
GEV8LR3/8	3/8"	8	400
GEV10LR3/8	3/8"	10	400
GEV12LR	3/8"	12	400
GEV15LR3/8	3/8"	15	400
GEV18LR3/8	3/8"	18	400
GEV8LR1/2	1/2"	8	400
GEV10LR1/2	1/2"	10	400
GEV12LR1/2	1/2"	12	400
GEV15LR	1/2"	15	400
GEV18LR	1/2"	18	400
GEV22LR1/2	1/2"	22	250
GEV15LR3/4	3/4"	15	400
GEV18LR3/4	3/4"	18	400
GEV22LR	3/4"	22	250
GEV28LR3/4	3/4"	28	250
GEV22LR1	1"	22	250
GEV28LR	1"	28	250
GEV35LR1	1"	35	250
GEV42LR	1.1/2"	42	250
Tech Sheet 1663			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6SR	1/4"	6	630
GEV8SR	1/4"	8	630
GEV10SR1/4	1/4"	10	630
GEV12SR1/4	1/4"	12	630
GEV8SR3/8	3/8"	8	630
GEV10SR	3/8"	10	630
GEV12SR	3/8"	12	630
GEV14SR3/8	3/8"	14	630
GEV16SR3/8	3/8"	16	630
GEV8SR1/2	1/2"	8	630
GEV10SR1/2	1/2"	10	630
GEV12SR1/2	1/2"	12	630
GEV14SR	1/2"	14	630
GEV16SR	1/2"	16	630
GEV20SR1/2	1/2"	20	400
GEV16SR3/4	3/4"	16	630
GEV20SR	3/4"	20	400
GEV25SR3/4	3/4"	25	400
GEV30SR3/4	3/4"	30	250
GEV20SR1	1"	20	400
GEV25SR	1"	25	400
GEV30SR1	1"	30	250
GEV30SR	1.1/4"	30	250
GEV38SR11/4	1.1/4"	38	250
GEV38SR	1.1/2"	38	250
Tech Sheet 1663			

Form E, Metric



Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6LMWD	M10 x 1	6	500
GEV8LMWD	M12 x 1.5	8	500
GEV10LMWD	M14 x 1.5	10	500
GEV12LMWD	M16 x 1.5	12	400
GEV12LM18X1.5WD	M18 x 1.5	12	400
GEV15LMD	M18 x 1.5	15	400
GEV18LM18X1.5WD	M18 x 1.5	18	400
GEV12LM22X1.5WD	M22 x 1.5	12	400
GEV15LM22X1.5WD	M22 x 1.5	15	400
GEV18LMWD	M22 x 1.5	18	400
GEV22LMWD	M26 x 1.5	22	250
GEV28LMWD	M33 x 2	28	250
GEV35LMWD	M42 x 2	35	250
Tech Sheet 1664			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6SMWD	M12 x 1.5	6	800
GEV8SMWD	M14 x 1.5	8	800
GEV10SMWD	M16 x 1.5	10	800
GEV12SMWD	M18 x 1.5	12	630
GEV14SMWD	M20 x 1.5	14	630
GEV16SMWD	M22 x 1.5	16	630
GEV20SMWD	M27 x 2	20	420
GEV25SMWD	M33 x 2	25	420
GEV30SMWD	M42 x 2	30	420
GEV38SMWD	M48 x 2	38	420
Tech Sheet 1664			

Form E, BSPP




Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6LRWD	1/8"	6	500
GEV8LR1/8WD	1/8"	8	500
GEV6LR1/4WD	1/4"	6	500
GEV8LRWD	1/4"	8	500
GEV10LRWD	1/4"	10	500
GEV12LR1/4WD	1/4"	12	400
GEV8LR3/8WD	3/8"	8	500
GEV10LR3/8WD	3/8"	10	500
GEV12LRWD	3/8"	12	400
GEV15LR3/8WD	3/8"	15	400
GEV10LR1/2WD	1/2"	10	500
GEV12LR1/2WD	1/2"	12	400
GEV15LRWD	1/2"	15	400
GEV18LRWD	1/2"	18	400
GEV18LR3/4WD	3/4"	18	400
GEV22LRWD	3/4"	22	250
GEV28LRWD	1"	28	250
GEV35LRWD	1.1/4"	35	250
GEV42LRWD	1.1/2"	42	250
Tech Sheet 1665			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6SRWD	1/4"	6	800
GEV8SRWD	1/4"	8	800
GEV10SR1/4WD	1/4"	10	800
GEV12SR1/4WD	1/4"	12	630
GEV8SR3/8WD	3/8"	8	800
GEV10SRWD	3/8"	10	800
GEV12SRWD	3/8"	12	630
GEV16SR3/8WD	3/8"	16	630
GEV10SR1/2WD	1/2"	10	800
GEV12SR1/2WD	1/2"	12	630
GEV14SRWD	1/2"	14	630
GEV16SRWD	1/2"	16	630
GEV16SR3/4WD	3/4"	16	630
GEV20SRWD	3/4"	20	420
GEV25SR3/4WD	3/4"	25	420
GEV25SRWD	1"	25	420
GEV30SRWD	1.1/4"	30	420
GEV38SRWD	1.1/2"	38	420
Tech Sheet 1665			

For **Hydraulic Tube Clamps** see pages **184-200**



Fluid-Air Components Ltd

MALE STUD COUPLINGS

NPT



Extra Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV4LL1/8NPT	1/8"	4	100
GEV6LL1/8NPT	1/8"	6	100
GEV8LL1/8NPT	1/8"	8	100
Tech Sheet 1666			

Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV6L1/8NPT	1/8"	6	315
GEV6L1/4NPT	1/4"	6	315
GEV8L1/4NPT	1/4"	8	315
GEV10L1/4NPT	1/4"	10	315
GEV12L1/4NPT	1/4"	12	315
GEV10L3/8NPT	3/8"	10	315
GEV12L3/8NPT	3/8"	12	315
GEV12L1/2NPT	1/2"	12	315
GEV15L1/2NPT	1/2"	15	315
GEV18L1/2NPT	1/2"	18	315
GEV22L3/4NPT	3/4"	22	160
GEV28L1NPT	1"	28	160
GEV35L11/4NPT	1.1/4"	35	160
GEV42L11/2NPT	1.1/2"	42	160
Tech Sheet 1666			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV8S1/4NPT	1/4"	8	630
GEV10S1/4NPT	1/4"	10	630
GEV12S1/4NPT	1/4"	12	630
GEV10S3/8NPT	3/8"	10	630
GEV12S3/8NPT	3/8"	12	630
GEV12S1/2NPT	1/2"	12	630
GEV14S1/2NPT	1/2"	14	630
GEV16S1/2NPT	1/2"	16	400
GEV25S1NPT	1"	25	400
GEV38S11/2NPT	1.1/2"	38	315
Tech Sheet 1666			

UNF



Light-duty

0350	Thread	OD mm	Max Pressure Bar
GEV8L7/16-20UNF	7/16-20 UNF	8	400
GEV10L7/16-20UNF	7/16-20 UNF	10	400
GEV8L9/16-18UNF	9/16-18 UNF	8	400
GEV10L9/16-18UNF	9/16-18 UNF	10	400
GEV12L9/16-18UNF	9/16-18 UNF	12	400
GEV12L3/4-16UNF	3/4-16 UNF	12	400
GEV15L3/4-16UNF	3/4-16 UNF	15	400
GEV18L3/4-16UNF	3/4-16 UNF	18	400
GEV12L7/8-14UNF	7/8-14 UNF	12	400
GEV15L7/8-14UNF	7/8-14 UNF	15	400
GEV18L7/8-14UNF	7/8-14 UNF	18	400
GEV22L7/8-14UNF	7/8-14 UNF	22	250
GEV28L7/8-14UNF	7/8-14 UNF	28	250
GEV22L11/16-12UN	1.1/16-12 UN	22	250
GEV28L15/16-12UN	1.5/16-12 UN	28	250
GEV35L15/16-12UN	1.5/16-12 UN	35	250
GEV35L15/8-12UN	1.5/8-12 UN	35	250
Tech Sheet 1667			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GEV10S9/16-18UNF	9/16-18 UNF	10	630
GEV12S3/4-16UNF	3/4-16 UNF	12	630
GEV16S3/4-16UNF	3/4-16 UNF	16	630
GEV20S3/4-16UNF	3/4-16 UNF	20	400
GEV16S7/8-14UNF	7/8-14 UNF	16	630
GEV20S7/8-14UNF	7/8-14 UNF	20	400
GEV20S11/16-12UN	1.1/16-10 UN	20	400
GEV30S15/8-12UN	1.5/8-12 UN	30	315
Tech Sheet 1667			

For **Hydraulic Ball Valves**
see pages **238-240**



Fluid-Air Components Ltd

MALE STUD ELBOWS & REDUCING BUSHES

Elbows



BSPT, Extra Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV4LLRK	1/8"	4	100
WEV6LLRK	1/8"	6	100
WEV8LLRK	1/8"	8	100
Tech Sheet 1668			

BSPT, Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6LRK	1/8"	6	250
WEV6LR1/4K	1/4"	6	250
WEV8LRK	1/4"	8	250
WEV12LR1/4K	1/4"	12	250
WEV10LRK	1/4"	10	250
WEV10LR3/8K	3/8"	10	250
WEV12LRK	3/8"	12	250
WEV15LR3/8K	3/8"	15	250
WEV12LR1/2K	1/2"	12	250
WEV15LRK	1/2"	15	250
WEV18LRK	1/2"	18	160
Tech Sheet 1668			

BSPT, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6SRK	1/4"	6	630
WEV8SRK	1/4"	8	630
WEV12SRK	3/8"	12	630
WEV14SRK	1/2"	14	630
WEV16SRK	1/2"	16	400
Tech Sheet 1668			



Metric Taper, Extra Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV4LLMK	M8 x 1	4	100
WEV6LLMK	M10 x 1	6	100
WEV8LLMK	M10 x 1	8	100
Tech Sheet 1669			

Metric Taper, Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6LMK	M10 x 1	6	250
WEV8LMK	M12 x 1.5	8	250
WEV10LMK	M14 x 1.5	10	250
WEV12LMK	M16 x 1.5	12	250
WEV15LMK	M18 x 1.5	15	250
WEV18LMK	M22 x 1.5	18	160
Tech Sheet 1669			

Metric Taper, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6SMK	M12 x 1.5	6	630
WEV8SMK	M14 x 1.5	8	630
WEV10SMK	M16 x 1.5	10	630
WEV12SMK	M18 x 1.5	12	630
WEV16SMK	M22 x 1.5	16	400
Tech Sheet 1669			



NPT, Extra Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV4LL1/8NPT	1/8"	4	100
WEV6LL1/8NPT	1/8"	6	100
WEV8LL1/8NPT	1/8"	8	100
Tech Sheet 1670			

NPT, Light-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6L1/8NPT	1/8"	6	250
WEV8L1/4NPT	1/4"	8	250
WEV10L1/4NPT	1/4"	10	250
WEV12L1/4NPT	1/4"	12	250
WEV12L3/8NPT	3/8"	12	250
WEV15L1/2NPT	1/2"	15	250
WEV18L1/2NPT	1/2"	18	160
WEV22L3/4NPT	3/4"	22	160
WEV28L1NPT	1"	28	100
Tech Sheet 1670			

NPT, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
WEV6S1/4NPT	1/4"	6	630
WEV8S1/4NPT	1/4"	8	630
WEV10S3/8NPT	3/8"	10	630
WEV12S3/8NPT	3/8"	12	630
WEV14S1/2NPT	1/2"	14	630
WEV16S1/2NPT	1/2"	16	400
WEV20S3/4NPT	3/4"	20	400
WEV25S1NPT	1"	25	400
Tech Sheet 1670			

BSPP, Reducing Bushes

Captive NBR seal



BSPP, Compact

0350	Male Thread	Female Thread	Max Pressure Bar
REDR3/8X1/8	3/8"	1/8"	630
REDR1/2X1/8	1/2"	1/8"	630
REDR1/2X1/4	1/2"	1/4"	630
REDR3/4X1/4	3/4"	1/4"	400
REDR3/4X3/8	3/4"	3/8"	400
REDR1X1/4	1"	1/4"	400
REDR1X3/8	1"	3/8"	400
REDR1X1/2	1"	1/2"	400
REDR11/4X1/2	1.1/4"	1/2"	400
REDR11/4X3/4	1.1/4"	3/4"	400
REDR11/2X1/2	1.1/2"	1/2"	400
REDR11/2X3/4	1.1/2"	3/4"	400
REDR11/2X1	1.1/2"	1"	400
Tech Sheet 1671			

Captive NBR seal



BSPP

0350	Male Thread	Female Thread	Max Pressure Bar
REDR1/8X1/4	1/8"	1/4"	400
REDR1/8X3/8	1/8"	3/8"	400
REDR1/4X1/8	1/4"	1/8"	400
REDR1/4X3/8	1/4"	3/8"	400
REDR1/4X1/2	1/4"	1/2"	400
REDR1/4X3/4	1/4"	3/4"	400
REDR3/8X1/4	3/8"	1/4"	400
REDR3/8X1/2	3/8"	1/2"	400
REDR3/8X3/4	3/8"	3/4"	400
REDR1/2X3/8	1/2"	3/8"	400
REDR1/2X3/4	1/2"	3/4"	400

0350	Male Thread	Female Thread	Max Pressure Bar
REDR1/2X1	1/2"	1"	400
REDR3/4X1/2	3/4"	1/2"	400
REDR3/4X1	3/4"	1"	400
REDR3/4X11/4	3/4"	1.1/4"	250
REDR3/4X11/2	3/4"	1.1/2"	250
REDR1X3/4	1"	3/4"	400
REDR1X11/4	1"	1.1/4"	250
REDR1X11/2	1"	1.1/2"	250
REDR11/4X1	1.1/4"	1"	400
REDR11/4X11/2	1.1/4"	1.1/2"	250
REDR11/2X11/4	1.1/2"	1.1/4"	250
Tech Sheet 1672			

Fluid-Air Components Ltd

TUBE TO TUBE COUPLINGS

Equal Elbows



Extra Light-duty

0350	OD mm	Max Pressure Bar
WV4LL	4	100
WV6LL	6	100
WV8LL	8	100
Tech Sheet 1673		

Light-duty

0350	OD mm	Max Pressure Bar
WV6L	6	500
WV8L	8	500
WV10L	10	500
WV12L	12	400
WV15L	15	400
WV18L	18	400
WV22L	22	250
WV28L	28	250
WV35L	35	250
WV42L	42	250
Tech Sheet 1673		

Heavy-duty

0350	OD mm	Max Pressure Bar
WV06S	6	800
WV08S	8	800
WV10S	10	800
WV12S	12	630
WV14S	14	630
WV16S	16	630
WV20S	20	420
WV25S	25	420
WV30S	30	420
WV38S	38	400
Tech Sheet 1673		

Bulkhead Elbows



Light-duty

0350	Thread	OD mm	Max Pressure Bar
WSV6L	M12 x 1.5	6	500
WSV8L	M14 x 1.5	8	500
WSV10L	M16 x 1.5	10	500
WSV12L	M18 x 1.5	12	400
WSV15L	M22 x 1.5	15	400
WSV18L	M26 x 1.5	18	400
WSV22L	M30 x 2	22	250
WSV28L	M36 x 2	28	250
WSV35L	M45 x 2	35	250
WSV42L	M52 x 2	42	250
Tech Sheet 1674			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
WSV6S	M14 x 1.5	6	800
WSV8S	M16 x 1.5	8	800
WSV10S	M18 x 1.5	10	800
WSV12S	M20 x 1.5	12	630
WSV14S	M22 x 1.5	14	630
WSV16S	M24 x 1.5	16	630
WSV20S	M30 x 2	20	400
WSV25S	M36 x 2	25	400
WSV30S	M42 x 2	30	400
WSV38S	M52 x 2	38	400
Tech Sheet 1674			

Reducing Elbows



Light-duty

0350	OD mm	OD mm	Max Pressure Bar
REDWV8L-6L	8	6	315
REDWV10L-8L	10	8	315
REDWV10L-6L	10	6	315
REDWV12L-10L	12	10	315
REDWV12L-8L	12	8	315
REDWV12L-6L	12	6	315
REDWV15L-12L	15	12	315
REDWV15L-10L	15	10	315
REDWV15L-8L	15	8	315
REDWV15L-6L	15	6	315
REDWV18L-15L	18	15	315
REDWV18L-12L	18	12	315
REDWV18L-10L	18	10	315
REDWV18L-8L	18	8	315
REDWV18L-6L	18	6	315
REDWV22L-18L	22	18	160
REDWV22L-15L	22	15	160
REDWV22L-12L	22	12	160
REDWV22L-10L	22	10	160
REDWV22L-8L	22	8	160
REDWV28L-22L	28	22	160
REDWV28L-18L	28	18	160
REDWV28L-15L	28	15	160
REDWV28L-12L	28	12	160
REDWV28L-10L	28	10	160
REDWV35-28L	35	28	160
REDWV35L-22L	35	22	160
REDWV35L-18L	35	18	160
REDWV35L-15L	35	15	160
REDWV42L-35L	42	35	160
REDWV42L-22L	42	22	160
REDWV42L-18L	42	18	160
REDWV42L-15L	42	15	160

Heavy-duty

0350	OD mm	OD mm	Max Pressure Bar
REDWV8S-6S	8	6	630
REDWV10S-8S	10	8	630
REDWV10S-6S	10	6	630
REDWV12S-10S	12	10	630
REDWV12S-8S	12	8	630
REDWV12S-6S	12	6	630
REDWV14S-12S	14	12	630
REDWV14S-10S	14	10	630
REDWV14S-8S	14	8	630
REDWV14S-6S	14	6	630
REDWV16S-14S	16	14	400
REDWV16S-12S	16	12	400
REDWV16S-10S	16	10	400
REDWV16S-8S	16	8	400
REDWV16S-6S	16	6	400
REDWV20S-16S	20	16	400
REDWV20S-14S	20	14	400
REDWV20S-12S	20	12	400
REDWV20S-10S	20	10	400
REDWV20S-8S	20	8	400
REDWV20S-6S	20	6	400
REDWV25S-20S	25	20	400
REDWV25S-16S	25	16	400
REDWV25S-14S	25	14	400
REDWV25S-12S	25	12	400
REDWV25S-10S	25	10	400
REDWV25S-8S	25	8	400
REDWV30S-25S	30	25	400
REDWV30S-20S	30	20	400
REDWV30S-16S	30	16	400
REDWV30S-14S	30	14	400
REDWV30S-12S	30	12	400
REDWV38S-30S	38	30	315
REDWV38S-25S	38	25	315
REDWV38S-20S	38	20	315
REDWV38S-16S	38	16	315
REDWV38S-10S	38	10	315

Fluid-Air Components Ltd

TUBE TO TUBE COUPLINGS

Equal Tees



Extra Light-duty

0350	OD mm	Max Pressure Bar
TV4LL	4	100
TV6LL	6	100
TV8LL	8	100
Tech Sheet 1676		


Light-duty

0350	OD mm	Max Pressure Bar
TV6L	6	500
TV8L	8	500
TV10L	10	500
TV12L	12	400
TV15L	15	400
TV18L	18	400
TV22L	22	250
TV28L	28	250
TV35L	35	250
TV42L	42	250
Tech Sheet 1676		

Heavy-duty

0350	OD mm	Max Pressure Bar
TV6S	6	800
TV8S	8	800
TV10S	10	800
TV12S	12	630
TV14S	14	630
TV16S	16	630
TV20S	20	420
TV25S	25	420
TV30S	30	420
TV38S	38	400
Tech Sheet 1676		


Reducing Tees



Light-duty

0350	OD A mm	OD B mm	OD C mm	Max Pressure Bar
TV10/10/6L	10	6	10	500
TV10/10/8L	10	8	10	500
TV12/12/8L	12	8	12	400
TV12/12/10L	12	10	12	400
TV12/12/15L	12	15	12	400
TV15/12/12L	15	12	12	400
TV18/18/10L	18	10	18	400
TV18/18/12L	18	12	18	400
TV22/22/10L	22	10	22	250
TV22/22/15L	22	15	22	250
Tech Sheet 1677				

Adjustable Reducing Tees



Light-duty

0350	OD A mm	OD B mm	OD C mm	Max Pressure Bar
TV8/8/6L	8	8	6	315
TV12/12/6L	12	12	6	315
TV15/15/12L	15	15	12	315
TV15/15/10L	15	15	10	315
TV15/15/8L	15	15	8	315
TV15/15/6L	15	15	6	315
TV18/18/15L	18	18	15	315
TV18/18/8L	18	18	8	315
TV18/18/6L	18	18	6	315
TV22/22/18L	22	22	18	160
TV22/22/12L	22	22	12	160
TV22/22/8L	22	22	8	160
TV28/28/22L	28	28	22	160
TV28/28/18L	28	28	18	160
TV28/28/15L	28	28	15	160
TV28/28/12L	28	28	12	160
TV28/28/10L	28	28	10	160
TV35/35/28L	35	35	28	160
TV35/35/22L	35	35	22	160
TV35/35/18L	35	35	18	160
TV35/35/15L	35	35	15	160
TV42/42/35L	42	42	35	160
TV42/42/22L	42	42	22	160
TV42/42/18L	42	42	18	160
TV42/42/15L	42	42	15	160

Heavy-duty

0350	OD A mm	OD B mm	OD C mm	Max Pressure Bar
TV8/8/6S	8	6	8	630
TV10/10/8S	10	8	10	630
TV10/10/6S	10	6	10	630
TV12/12/10S	12	10	12	630
TV12/12/8S	12	8	12	630
TV12/12/6S	12	6	12	630
TV14/14/12S	14	12	14	630
TV14/14/10S	14	10	14	630
TV14/14/8S	14	8	14	630
TV14/14/6S	14	6	14	630
TV16/16/14S	16	14	16	400
TV16/16/12S	16	12	16	400
TV16/16/10S	16	10	16	400
TV16/16/8S	16	8	16	400
TV16/16/6S	16	6	16	400
TV20/20/16S	20	16	20	400
TV20/20/14S	20	14	20	400
TV20/20/12S	20	12	20	400
TV20/20/10S	20	10	20	400
TV20/20/8S	20	8	20	400
TV20/20/6S	20	6	20	400
TV25/25/20S	25	20	25	400
TV25/25/16S	25	16	25	400
TV25/25/14S	25	14	25	400
TV25/25/12S	25	12	25	400
TV25/25/10S	25	10	25	400
TV25/25/8S	25	8	25	400
TV30/30/25S	30	25	30	400
TV30/30/20S	30	20	30	400
TV30/30/16S	30	16	30	400
TV30/30/14S	30	14	30	400
TV30/30/12S	30	12	30	400
TV38/38/30S	38	30	38	315
TV38/38/25S	38	25	38	315
TV38/38/20S	38	20	38	315
TV38/38/16S	38	16	38	315
TV38/38/10S	38	10	38	315

stainless steel



You might also need
316 Stainless Steel Tube
see page **183**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TUBE TO TUBE COUPLINGS

Bulkhead Couplings



Straight, Light-duty

0350	Thread	OD mm	Max Pressure Bar
GSV6L	M12 x 1.5	6	500
GSV8L	M14 x 1.5	8	500
GSV10L	M16 x 1.5	10	500
GSV12L	M18 x 1.5	12	400
GSV15L	M22 x 1.5	15	400
GSV18L	M26 x 1.5	18	400
GSV22L	M30 x 2	22	250
GSV28L	M36 x 2	28	250
GSV35L	M45 x 2	35	250
GSV42L	M52 x 2	42	250
Tech Sheet 1675			

Straight, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GSV6S	M14 x 1.5	6	800
GSV8S	M16 x 1.5	8	800
GSV10S	M18 x 1.5	10	800
GSV12S	M20 x 1.5	12	630
GSV14S	M22 x 1.5	14	630
GSV16S	M24 x 1.5	16	630
GSV20S	M30 x 2	20	630
GSV25S	M36 x 2	25	630
GSV30S	M42 x 2	30	630
GSV38S	M52 x 2	38	400
Tech Sheet 1675			

Straight Couplings



Equal Straight, Extra Light-duty

0350	OD mm	Max Pressure Bar
GV4LL	4	100
GV6LL	6	100
GV8LL	8	100
Tech Sheet 1678		

Equal Straight, Light-duty

0350	OD mm	Max Pressure Bar
GV-6L	6	500
GV-8L	8	500
GV-10L	10	500
GV-12L	12	400
GV-15L	15	400
GV-18L	18	400
GV-22L	22	250
GV-28L	28	250
GV-35L	35	250
GV-42L	42	250
Tech Sheet 1678		

Equal Straight, Heavy-duty

0350	OD mm	Max Pressure Bar
GV6S	6	800
GV8S	8	800
GV10S	10	800
GV12S	12	630
GV14S	14	630
GV16S	16	630
GV20S	20	420
GV25S	25	420
GV30S	30	420
GV38S	38	420
Tech Sheet 1678		

Reducing Couplings



Unequal Straight, Extra Light-duty

0350	OD mm	OD mm	Max Pressure Bar
GV6/4LL	6	4	100
Tech Sheet 1679			

Unequal Straight, Light-duty

0350	OD mm	OD mm	Max Pressure Bar
GV8/6L	8	6	500
GV10/6L	10	6	500
GV10/8L	10	8	500
GV12/6L	12	6	400
GV12/8L	12	8	400
GV12/10L	12	10	400
GV15/10L	15	10	400
GV15/12L	15	12	400
GV18/10L	18	10	400
GV18/12L	18	12	400
GV18/15L	18	15	400
GV22/15L	22	15	250
GV22/18L	22	18	250
Tech Sheet 1679			

Unequal Straight, Heavy-duty

0350	OD mm	OD mm	Max Pressure Bar
GV16/12S	16	12	620
GV20/16S	20	16	420
GV25/16S	25	16	420
GV25/20S	25	20	420
Tech Sheet 1679			

Tube to Tube Equal Crosses



Extra Light-duty

0350	OD mm	Max Pressure Bar
KV4LL	4	100
KV6LL	6	100
KV8LL	8	100
Tech Sheet 1680		

Light-duty

0350	OD mm	Max Pressure Bar
KV6L	6	500
KV8L	8	500
KV10L	10	500
KV12L	12	400
KV15L	15	400
KV18L	18	400
KV22L	22	250
KV28L	28	250
KV35L	35	250
KV42L	42	250
Tech Sheet 1680		

Heavy-duty

0350	OD mm	Max Pressure Bar
KV6S	6	800
KV8S	8	800
KV10S	10	800
KV12S	12	630
KV14S	14	630
KV16S	16	630
KV20S	20	420
KV25S	25	420
KV30S	30	420
KV38S	38	400
Tech Sheet 1680		

Fluid-Air Components Ltd

BANJO COUPLINGS

Banjo Couplings



Low restrictive

Banjo Seal Edge Metric, Light-duty

0350	Thread	OD mm	Max Pressure Bar
RSWV6LM	M10 x 1	6	500
RSWV8LM	M12 x 1.5	8	500
RSWV10LM	M14 x 1.5	10	500
RSWV12LM	M16 x 1.5	12	400
RSWV12LM18X1.5	M18 x 1.5	12	315
RSWV15LM	M18 x 1.5	15	400
RSWV18LM	M22 x 1.5	18	400
RSWV22LM	M26 x 1.5	22	250
RSWV28LM	M33 x 2	28	250
RSWV35LM	M42 x 2	35	250
RSWV42LM	M48 x 2	42	250
Tech Sheets 1681 & 1682			

Banjo Seal Edge Metric, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
RSWV6SM	M12 x 1.5	6	500
RSWV8SM	M14 x 1.5	8	500
RSWV10SM	M16 x 1.5	10	500
RSWV12SM	M18 x 1.5	12	400
RSWV14SM	M20 x 1.5	14	400
RSWV16SM	M22 x 1.5	16	400
RSWV20SM	M27 x 2	20	315
RSWV25SM	M33 x 2	25	250
RSWV30SM	M42 x 2	30	250
RSWV38SM	M48 x 2	38	250
Tech Sheets 1681 & 1682			

Banjo Seal Edge BSPP, Light-duty

0350	Thread	OD mm	Max Pressure Bar
RSWV6LR	1/8"	6	500
RSWV8LR	1/4"	8	500
RSWV10LR	1/4"	10	500
RSWV12LR	3/8"	12	400
RSWV15LR	1/2"	15	400
RSWV18LR	1/2"	18	400
RSWV22LR	3/4"	22	250
RSWV28LR	1"	28	250
RSWV35LR	1.1/4"	35	250
RSWV42LR	1.1/2"	42	250
Tech Sheets 1681 & 1682			

Banjo Seal Edge BSPP, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
RSWV6SR	1/4"	6	500
RSWV8SR	1/4"	8	500
RSWV10SR	3/8"	10	500
RSWV12SR	3/8"	12	400
RSWV14SR	1/2"	14	400
RSWV16SR	1/2"	16	400
RSWV20SR	3/4"	20	315
RSWV25SR	1"	25	250
RSWV30SR	1.1/4"	30	250
RSWV38SR	1.1/2"	38	250
Tech Sheets 1681 & 1682			

Double Banjo Couplings



Double Banjo Metric, Light-duty with Elastomer Seal

0350	Thread	OD mm	Max Pressure Bar
P-RSTV6LM-WD	M10 x 1	6	500
P-RSTV8LM-WD	M12 x 1.5	8	500
P-RSTV10LM-WD	M14 x 1.5	10	500
P-RSTV12LM-WD	M16 x 1.5	12	400
P-RSTV15LM-WD	M18 x 1.5	15	400
P-RSTV18LM-WD	M22 x 1.5	18	400
P-RSTV22LM-WD	M26 x 1.5	22	250
P-RSTV28LM-WD	M33 x 2	28	250
P-RSTV35LM-WD	M42 x 2	35	250
Tech Sheets 1683 & 1684			

Double Banjo Metric, Heavy-duty with Elastomer Seal

0350	Thread	OD mm	Max Pressure Bar
P-RSTV6SM-WD	M12 x 1.5	6	500
P-RSTV8SM-WD	M14 x 1.5	8	500
P-RSTV16SM-WD	M22 x 1.5	16	400
P-RSTV20SM-WD	M27 x 2	20	315
P-RSTV25SM-WD	M33 x 2	25	250
P-RSTV30SM-WD	M42 x 2	30	250
P-RSTV38SM-WD	M48 x 2	38	250
Tech Sheets 1683 & 1684			

Double Banjo BSPP, Light-duty with Elastomer Seal

0350	Thread	OD mm	Max Pressure Bar
P-RSTV6LR-WD	1/8"	6	500
P-RSTV8LR-WD	1/4"	8	500
P-RSTV10LR-WD	1/4"	10	500
P-RSTV12LR-WD	3/8"	12	400
P-RSTV15LR-WD	1/2"	15	400
P-RSTV18LR-WD	1/2"	18	400
P-RSTV35LR-WD	1.1/4"	35	250
P-RSTV42LR-WD	1.1/2"	42	250
Tech Sheets 1683 & 1684			

Double Banjo BSPP, Heavy-duty with Elastomer Seal

0350	Thread	OD mm	Max Pressure Bar
P-RSTV6SR-WD	1/4"	6	500
P-RSTV8SR-WD	1/4"	8	500
P-RSTV10SR-WD	3/8"	10	500
P-RSTV12SR-WD	3/8"	12	400
P-RSTV16SR-WD	1/2"	16	400
P-RSTV20SR-WD	3/4"	20	315
P-RSTV25SR-WD	1"	25	250
P-RSTV30SR-WD	1.1/4"	30	250
P-RSTV38SR-WD	1.1/2"	38	250
Tech Sheets 1683 & 1684			

Swivel Elbow Banjo Coupling, Tube to Tube



Light-duty

0350	OD mm	Max Pressure Bar
DGWV6L	6	250
DGWV8L	8	250
DGWV10L	10	250
DGWV12L	12	250
DGWV18L	18	160
DGWV22L	22	160
DGWV28L	28	100
DGWV35L	35	100
DGWV42L	42	100
Tech Sheet 1685		

Heavy-duty

0350	OD mm	Max Pressure Bar
DGWV6S	6	400
DGWV8S	8	400
DGWV10S	10	400
DGWV14S	14	400
DGWV16S	16	400
DGWV20S	20	250
DGWV25S	25	250
DGWV30S	30	250
DGWV38S	38	250
Tech Sheet 1685		

Swivel Banjo Couplings



BSPP, Light-duty

0350	Thread	OD mm	Max Pressure Bar
DGWEV6LRWD	1/8"	6	250
DGWEV6LR1/4WD	1/4"	6	250
DGWEV8LRWD	1/4"	8	250
DGWEV10LRWD	1/4"	10	250
DGWEV10LR3/8WD	3/8"	10	250
DGWEV12LRWD	3/8"	12	250
DGWEV12LR1/2WD	1/2"	12	250
DGWEV15LRWD	1/2"	15	250
DGWEV18LRWD	1/2"	18	160
DGWEV22LRWD	3/4"	22	160
DGWEV28LRWD	1"	28	100
DGWEV35LRWD	1.1/4"	35	100
DGWEV42LRWD	1.1/2"	42	100
Tech Sheet 1686			

BSPP, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
DGWEV6SRWD	1/4"	6	400
DGWEV8SRWD	1/4"	8	400
DGWEV10SRWD	3/8"	10	400
DGWEV12SRWD	3/8"	12	400
DGWEV16SRWD	1/2"	16	400
DGWEV20SRWD	3/4"	20	250
DGWEV25SRWD	1"	25	250
DGWEV30SRWD	1.1/4"	30	250
DGWEV38SRWD	1.1/2"	38	250
Tech Sheet 1686			

Swivel banjos are connecting components between pipe work and equipment to allow swivel movement and slow speed rotation. These connections have a low starting torque and are leak-free and require no maintenance.

Fluid-Air Components Ltd

WELDING COUPLINGS

Welding Couplings





Bosses, Light-duty

0350	OD mm	Max Pressure Bar
ASV6L	6	500
ASV8L	8	500
ASV10L	10	500
ASV12L	12	400
ASV15L	15	400
ASV18L	18	400
ASV22L	22	250
ASV28L	28	250
ASV35L	35	250
ASV42L	42	250
Tech Sheet 1687		

Bosses, Heavy-duty

0350	OD mm	Max Pressure Bar
ASV6S	6	800
ASV8S	8	800
ASV12S	12	630
ASV14S	14	630
ASV16S	16	630
ASV20S	20	420
ASV25S	25	420
ASV30S	30	420
ASV38S	38	420
Tech Sheet 1687		

Bulkhead, Light-duty

0350	OD mm	Max Pressure Bar
ESV6L	6	500
ESV8L	8	500
ESV10L	10	500
ESV12L	12	400
ESV15L	15	400
ESV18L	18	400
ESV22L	22	250
ESV28L	28	250
ESV35L	35	250
ESV42L	42	250
Tech Sheet 1688		

Bulkhead, Heavy-duty

0350	OD mm	Max Pressure Bar
ESV8S	8	800
ESV10S	10	800
ESV12S	12	630
ESV14S	14	630
ESV16S	16	630
ESV20S	20	420
ESV25S	25	420
ESV30S	30	420
ESV38S	38	420
Tech Sheet 1688		

Welding Nipples

Without tube centring



With O-Ring Seal

0350	To Suit Tube OD mm	Max Pressure Bar
SN8X2	8 x 2	400
SN10X1.5	10 x 1.5	400
SN10X2	10 x 2	400
SN12X2.5	12 x 2.5	400
SN16X2	16 x 2	400
SN16X3	16 x 3	400
SN20X3	20 x 3	250
SN25X3	25 x 3	250
SN25X4	25 x 4	315
SN30X4	30 x 4	250
SN30X5	30 x 5	315
SN38X4	38 x 4	160
SN38X5	38 x 5	250
SN38X6	38 x 6	315
Tech Sheet 1689		

PORTWEST




For **PPE**
see pages **1750-1760**

Fluid-Air Components Ltd

ADJUSTABLE STUD COUPLINGS

Standpipes, Metric




Captive Seal, Light-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6LMWD	M10 x 1	6	500
EGESD8LMWD	M12 x 1.5	8	500
EGESD10LMWD	M14 x 1.5	10	500
EGESD12LMWD	M16 x 1.5	12	400
EGESD15LMWD	M18 x 1.5	15	400
EGESD18LMWD	M22 x 1.5	18	400
EGESD22LMWD	M26 x 1.5	22	250
EGESD28LMWD	M33 x 2	28	250
EGESD35LMWD	M42 x 2	35	250
EGESD42LMWD	M48 x 2	42	250
Tech Sheet 1690			

Captive Seal, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6SMWD	M12 x 1.5	6	800
EGESD8SMWD	M14 x 1.5	8	800
EGESD10SMWD	M16 x 1.5	10	800
EGESD12SMWD	M18 x 1.5	12	630
EGESD14SMWD	M20 x 1.5	14	630
EGESD16SMWD	M22 x 1.5	16	630
EGESD20SMWD	M27 x 2	20	420
EGESD25SMWD	M33 x 2	25	420
EGESD30SMWD	M42 x 2	30	400
EGESD38SMWD	M48 x 2	38	400
Tech Sheet 1690			

Standpipes, BSPP



Captive Seal, Light-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6LRWD	1/8"	6	500
EGESD8LRWD	1/4"	8	500
EGESD10LRWD	1/4"	10	500
EGESD12LRWD	3/8"	12	400
EGESD15LRWD	1/2"	15	400
EGESD18LRWD	1/2"	18	400
EGESD22LRWD	3/4"	22	250
EGESD28LRWD	1"	28	250
EGESD35LRWD	1.1/4"	35	250
EGESD42LRWD	1.1/2"	42	250
Tech Sheet 1691			

Captive Seal, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6SRWD	1/4"	6	800
EGESD8SRWD	1/4"	8	800
EGESD12SRWD	3/8"	12	630
EGESD10SRWD	3/8"	10	800
EGESD12SR1/2WD	1/2"	12	630
EGESD14SRWD	1/2"	14	630
EGESD16SRWD	1/2"	16	630
EGESD20SRWD	3/4"	20	420
EGESD25SRWD	1"	25	420
EGESD30SRWD	1.1/4"	30	400
EGESD38SRWD	1.1/2"	38	400
Tech Sheet 1691			

Standpipes, NPT



Light-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6L1/8NPT	1/8"	6	250
EGESD8L1/4NPT	1/4"	8	250
EGESD10L1/4NPT	1/4"	10	250
EGESD12L3/8NPT	3/8"	12	250
EGESD15L1/2NPT	1/2"	15	250
EGESD18L1/2NPT	1/2"	18	160
EGESD22L3/4NPT	3/4"	22	160
EGESD28L1NPT	1"	28	100
Tech Sheet 1692			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
EGESD6S1/4NPT	1/4"	6	630
EGESD8S1/4NPT	1/4"	8	630
EGESD10S3/8NPT	3/8"	10	630
EGESD12S3/8NPT	3/8"	12	630
EGESD16S1/2NPT	1/2"	16	400
EGESD20S3/4NPT	3/4"	20	400
EGESD25S1NPT	1"	25	400
EGESD30S11/4NPT	1.1/4"	30	250
EGESD38S11/2NPT	1.1/2"	38	250
Tech Sheet 1692			

Straight Couplings

Nuts on either side are retractable to back of O-Ring groove, but only one at a time.



Equal Straight, Light-duty

0350	OD mm	Max Pressure Bar
SNV6L	6	500
SNV8L	8	500
SNV10L	10	500
SNV12L	12	400
SNV15L	15	400
SNV18L	18	400
SNV22L	22	250
SNV28L	28	250
SNV35L	35	250
SNV42L	42	250
Tech Sheet 1693		

Equal Straight, Heavy-duty


0350	OD mm	Max Pressure Bar
SNV6S	6	800
SNV8S	8	800
SNV10S	10	800
SNV12S	12	630
SNV14S	14	630
SNV16S	16	630
SNV20S	20	420
SNV25S	25	420
SNV30S	30	400
SNV38S	38	400
Tech Sheet 1693		

You might also need
Hydraulic Tubing
see pages **179-183**



RSB

For **Hydraulic Tube Clamps**
see pages **184-200**



Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

SWIVEL COUPLINGS

Straight Couplings

Nuts on either side are retractable to back of O-Ring groove

Unequal Straight, Light-duty

0350	OD mm	OD mm	Max Pressure Bar
SNV8/6L	8	6	500
SNV10/6L	10	6	500
SNV10/8L	10	8	500
SNV12/6L	12	6	400
SNV12/8L	12	8	400
SNV12/10L	12	10	400
SNV15/8L	15	8	400
SNV15/10L	15	10	400
SNV15/12L	15	12	400
SNV18/10L	18	10	400
SNV18/12L	18	12	400
SNV18/15L	18	15	400
SNV22/12L	22	12	250
SNV22/15L	22	15	250
SNV28/15L	28	15	250
SNV28/18L	28	18	250
SNV28/22L	28	22	250
SNV35/18L	35	18	250
SNV35/22L	35	22	250
SNV35/28L	35	28	250
SNV42/22L	42	22	250
SNV42/28L	42	28	250
SNV42/35L	42	35	250
Tech Sheet 1694			



Unequal Straight, Heavy-duty

0350	OD mm	OD mm	Max Pressure Bar
SNV8/6S	8	6	800
SNV10/6S	10	6	800
SNV10/8S	10	8	800
SNV12/6S	12	6	630
SNV12/8S	12	8	630
SNV12/10S	12	10	630
SNV16/10S	16	10	630
SNV16/12S	16	12	630
SNV20/12S	20	12	420
SNV20/16S	20	16	420
SNV25/16S	25	16	420
SNV25/20S	25	20	420
SNV30/16S	30	16	400
SNV30/20S	30	20	400
SNV30/25S	30	25	400
SNV38/20S	38	20	400
SNV38/25S	38	25	400
SNV38/30S	38	30	400
Tech Sheet 1694			



Unequal Straight, Light to Heavy-duty

0350	OD mm	OD mm	Max Pressure Bar
SNV6L/6S	6	6	400
SNV8L/8S	8	8	400
SNV10L/10S	10	10	400
SNV12L/12S	12	12	400
SNV18L/16S	18	16	400
SNV22L/20S	22	20	250
SNV28L/25S	28	25	250
SNV35L/30S	35	30	250
SNV42L/38S	42	38	250
Tech Sheet 1695			

Unequal Straight, Heavy to Light-duty

0350	OD mm	OD mm	Max Pressure Bar
SNV16S/15L	16	15	400
SNV20S/18L	20	18	400
SNV25S/22L	25	22	250
SNV30S/28L	30	28	250
SNV38S/35L	38	35	250
Tech Sheet 1695			

Adjustable Swivel Elbows



Light-duty

0350	Thread	OD mm	Max Pressure Bar
EWVD6L	M12 x 1.5	6	500
EWVD8L	M14 x 1.5	8	500
EWVD10L	M16 x 1.5	10	500
EWVD12L	M18 x 1.5	12	400
EWVD15L	M22 x 1.5	15	400
EWVD18L	M26 x 1.5	18	400
EWVD22L	M30 x 2	22	250
EWVD28L	M36 x 2	28	250
EWVD35L	M45 x 2	35	250
EWVD42L	M52 x 2	42	250
Tech Sheet 1696			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
EWVD6S	M14 x 1.5	6	800
EWVD8S	M16 x 1.5	8	800
EWVD10S	M18 x 1.5	10	800
EWVD12S	M20 x 1.5	12	630
EWVD14S	M22 x 1.5	14	630
EWVD16S	M24 x 1.5	16	630
EWVD20S	M30 x 2	20	420
EWVD25S	M36 x 2	25	420
EWVD30S	M42 x 2	30	400
EWVD38S	M52 x 2	38	400
Tech Sheet 1696			

Adjustable Run Tees



Light-duty

0350	Thread	OD mm	Max Pressure Bar
ELVD6L	M12 x 1.5	6	500
ELVD8L	M14 x 1.5	8	500
ELVD10L	M16 x 1.5	10	500
ELVD12L	M18 x 1.5	12	400
ELVD15L	M22 x 1.5	15	400
ELVD18L	M26 x 1.5	18	400
ELVD22L	M30 x 2	22	250
ELVD28L	M36 x 2	28	250
ELVD35L	M45 x 2	35	250
ELVD42L	M52 x 2	42	250
Tech Sheet 1697			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
ELVD6S	M14 x 1.5	6	800
ELVD8S	M16 x 1.5	8	800
ELVD10S	M18 x 1.5	10	800
ELVD12S	M20 x 1.5	12	630
ELVD14S	M22 x 1.5	14	630
ELVD16S	M24 x 1.5	16	630
ELVD20S	M30 x 2	20	420
ELVD25S	M36 x 2	25	420
ELVD30S	M42 x 2	30	400
ELVD38S	M52 x 2	38	400
Tech Sheet 1697			

Adjustable Branch Tees



Light-duty

0350	Thread	OD mm	Max Pressure Bar
ETVD6L	M12 x 1.5	6	500
ETVD8L	M14 x 1.5	8	500
ETVD10L	M16 x 1.5	10	500
ETVD12L	M18 x 1.5	12	400
ETVD15L	M22 x 1.5	15	400
ETVD18L	M26 x 1.5	18	400
ETVD22L	M30 x 2	22	250
ETVD28L	M36 x 2	28	250
ETVD35L	M45 x 2	35	250
ETVD42L	M52 x 2	42	250
Tech Sheet 1698			

Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
ETVD6S	M14 x 1.5	6	800
ETVD8S	M16 x 1.5	8	800
ETVD10S	M18 x 1.5	10	800
ETVD12S	M20 x 1.5	12	630
ETVD14S	M22 x 1.5	14	630
ETVD16S	M24 x 1.5	16	630
ETVD20S	M30 x 2	20	420
ETVD25S	M36 x 2	25	420
ETVD30S	M42 x 2	30	400
ETVD38S	M52 x 2	38	400
Tech Sheet 1698			

Fluid-Air Components Ltd

FEMALE STUD & GAUGE COUPLINGS

Female Stud Couplings

Female Stud Metric, Light-duty



0350	Thread	OD mm	Max Pressure Bar
GAV6LM	M10 x 1	6	250
GAV8LM	M12 x 1.5	8	250
GAV10LM	M14 x 1.5	10	250
GAV12LM	M16 x 1.5	12	250
GAV15LM	M18 x 1.5	15	250
GAV18LM	M22 x 1.5	18	160
GAV22LM	M26 x 1.5	22	160
Tech Sheet 1699			

Female Stud Metric, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GAV6SM	M12 x 1.5	6	630
GAV8SM	M14 x 1.5	8	630
GAV10SM	M16 x 1.5	10	630
GAV12SM	M18 x 1.5	12	630
GAV14SM	M20 x 1.5	14	630
GAV16SM	M22 x 1.5	16	400
GAV20SM	M27 x 2	20	400
Tech Sheet 1699			

Female Stud BSPP, Light-duty



0350	Thread	OD mm	Max Pressure Bar
GAV6LR	1/8"	6	250
GAV8LR	1/4"	8	250
GAV10LR	1/4"	10	250
GAV12LR1/4	1/4"	12	250
GAV12LR	3/8"	12	250
GAV15LR	1/2"	15	250
GAV18LR	1/2"	18	160
GAV22LR	3/4"	22	160
GAV28LR	1"	28	100
GAV35LR	1.1/4"	35	100
GAV42LR	1.1/2"	42	100
Tech Sheet 1700			

Female Stud BSPP, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
GAV6SR	1/4"	6	630
GAV8SR	1/4"	8	630
GAV10SR	3/8"	10	630
GAV12SR	3/8"	12	630
GAV14SR	1/2"	14	630
GAV16SR	1/2"	16	400
GAV20SR	3/4"	20	400
GAV25SR	1"	25	400
GAV30SR	1.1/4"	30	250
GAV38SR	1.1/2"	38	250
Tech Sheet 1700			

Female Gauge Couplings



Female Gauge BSPP, Tube, Light-duty

0350	Thread	OD mm	Max Pressure Bar
MAV6LR	1/4"	6	500
MAV8LR	1/4"	8	500
MAV10LR	1/4"	10	500
MAV12LR	1/4"	12	400
Tech Sheet 1701			

Female Gauge BSPP, Tube, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
MAV6SR	1/2"	6	800
MAV8SR	1/2"	8	800
MAV10SR	1/2"	10	800
MAV12SR	1/2"	12	630
Tech Sheet 1701			



Female Gauge BSPP, Swivel, Light-duty

0350	Thread	OD mm	Max Pressure Bar
EMASD6LR	1/4"	6	500
EMASD8LR	1/4"	8	500
EMASD10LR	1/4"	10	500
EMASD12LR	1/4"	12	400
Tech Sheet 1702			

Female Gauge BSPP, Swivel, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
EMASD6SR	1/2"	6	630
EMASD8SR	1/2"	8	630
EMASD10SR	1/2"	10	630
EMASD12SR	1/2"	12	630
Tech Sheet 1702			

Sealing Ring for Gauge Coupling



Steel

0350	To Suit
DKRR1/4MANOM.A3L	1/4"
DKRR1/2MANOM.A3L	1/2"



Customers who bought from this page also purchased **Glycerine Gauges** see pages **414-416**

Fluid-Air Components Ltd

REDUCING COUPLINGS

Reducing Inserts



Light-duty

0350	OD mm	OD mm	Max Pressure Bar
REDVDN8/6L	8	6	500
REDVDN10/8L	10	8	500
REDVDN10/6L	10	6	500
REDVDN12/10L	12	10	400
REDVDN12/8L	12	8	400
REDVDN12/6L	12	6	400
REDVDN15/12L	15	12	400
REDVDN15/10L	15	10	400
REDVDN15/8L	15	8	400
REDVDN15/6L	15	6	400
REDVDN18/15L	18	15	400
REDVDN18/12L	18	12	400
REDVDN18/10L	18	10	400
REDVDN18/8L	18	8	400
REDVDN18/6L	18	6	400
REDVDN22/18L	22	18	250
REDVDN22/15L	22	15	250
REDVDN22/12L	22	12	250
REDVDN22/10L	22	10	250
REDVDN22/8L	22	8	250
REDVDN28/22L	28	22	250
REDVDN28/18L	28	18	250
REDVDN28/15L	28	15	250
REDVDN28/12L	28	12	250
REDVDN28/10L	28	10	250
REDVDN35/28L	35	28	250
REDVDN35/22L	35	22	250
REDVDN35/18L	35	18	250
REDVDN35/15L	35	15	250
REDVDN42/35L	42	35	250
REDVDN42/22L	42	22	250
REDVDN42/18L	42	18	250
REDVDN42/15L	42	15	250
Tech Sheet 1703			



Heavy-duty

0350	OD mm	OD mm	Max Pressure Bar
REDVDN8/6S	8	6	800
REDVDN10/8S	10	8	800
REDVDN10/6S	10	6	800
REDVDN12/10S	12	10	630
REDVDN12/8S	12	8	630
REDVDN12/6S	12	6	630
REDVDN14/12S	14	12	630
REDVDN14/10S	14	10	630
REDVDN14/8S	14	8	630
REDVDN14/6S	14	6	630
REDVDN16/14S	16	14	630
REDVDN16/12S	16	12	630
REDVDN16/10S	16	10	630
REDVDN16/8S	16	8	630
REDVDN16/6S	16	6	630
REDVDN20/16S	20	16	420
REDVDN20/14S	20	14	420
REDVDN20/12S	20	12	420
REDVDN20/10S	20	10	420
REDVDN20/8S	20	8	420
REDVDN20/6S	20	6	420
REDVDN25/20S	25	20	420
REDVDN25/16S	25	16	420
REDVDN25/14S	25	14	420
REDVDN25/12S	25	12	420
REDVDN25/10S	25	10	420
REDVDN25/8S	25	8	420
REDVDN30/25S	30	25	400
REDVDN30/20S	30	20	400
REDVDN30/16S	30	16	400
REDVDN30/14S	30	14	400
REDVDN30/12S	30	12	400
REDVDN38/30S	38	30	400
REDVDN38/25S	38	25	400
REDVDN38/20S	38	20	400
REDVDN38/16S	38	16	400
REDVDN38/10S	38	10	400
Tech Sheet 1704			

For **Bonded Seals**
see pages **109-112**



Fluid-Air Components Ltd

DIN 2353 BODY ONLY FITTINGS

Male Stud Coupling



Light-duty, Form B, BSPP

0350	Thread	OD mm
GES 6 LR	1/8"	6
GES 6 LR 1/4	1/4"	6
GES 8 LR 1/8	1/8"	8
GES 8 LR	1/4"	8
GES 8 LR 3/8	3/8"	8
GES 10 LR	1/4"	10
GES 10 LR 3/8	3/8"	10
GES 10 LR 1/2	1/2"	10
GES 12 LR 1/4	1/4"	12
GES 12 LR	3/8"	12
GES 12 LR 1/2	1/2"	12
GES 15 LR	1/2"	15
GES 15 LR 3/4	3/4"	15
GES 18 LR	1/2"	18
GES 22 LR 1/2	1/2"	22
GES 22 LR	3/4"	22
GES 28 LR 3/4	3/4"	28
GES 28 LR	1"	28
GES 35 LR	1.1/4"	35
GES 42 LR	1.1/2"	42

Heavy-duty, Form B, BSPP

0350	Thread	OD mm
GES 6 SR	1/4"	6
GES 8 SR	1/4"	8
GES 8 SR 3/8	3/8"	8
GES 10 SR 1/4	1/4"	10
GES 10 SR	3/8"	10
GES 10 SR 1/2	1/2"	12
GES 12 SR 1/4	1/4"	12
GES 12 SR	3/8"	12
GES 12 SR 1/2	1/2"	12
GES 14 SR	1/2"	14
GES 16 SR 3/8	3/8"	16
GES 16 SR	1/2"	16
GES 16 SR 3/4	3/4"	16
GES 20 SR 1/2	1/2"	20
GES 20 SR	3/4"	20
GES 25 SR 3/4	3/4"	25
GES 25 SR	1"	25
GES 30 SR	1.1/4"	30
GES 38 SR 1.1/4	1.1/4"	38
GES 38 SR	1.1/2"	38



Light-duty, WD Seal, BSPP

0350	Thread	OD mm
GES 6 LR-WD	1/8"	6
GES 6 LR 1/4-WD	1/4"	6
GES 8 LR 1/8-WD	1/8"	8
GES 8 LR-WD	1/4"	8
GES 8 LR 3/8-WD	3/8"	8
GES 10 LR-WD	1/4"	10
GES 10 LR 3/8-WD	3/8"	10
GES 10 LR 1/2-WD	1/2"	10
GES 12 LR 1/4-WD	1/4"	12
GES 12 LR-WD	3/8"	12
GES 12 LR 1/2-WD	1/2"	12
GES 15 LR-WD	1/2"	15
GES 18 LR-WD	1/2"	18
GES 22 LR-WD	3/4"	22
GES 28 LR-WD	1"	28
GES 35 LR-WD	1.1/4"	35
GES 42 LR-WD	1.1/2"	42

Heavy-duty, WD Seal, BSPP

0350	Thread	OD mm
GES 6 SR-WD	1/4"	6
GES 8 SR-WD	1/4"	8
GES 8 SR 3/8-WD	3/8"	8
GES 10 SR 1/4-WD	1/4"	10
GES 10 SR-WD	3/8"	10
GES 10 SR 1/2-WD	1/2"	10
GES 12 SR 1/4-WD	1/4"	12
GES 12 SR-WD	3/8"	12
GES 12 SR 1/2-WD	1/2"	12
GES 14 SR-WD	1/2"	14
GES 16 SR 3/8-WD	3/8"	16
GES 16 SR-WD	1/2"	16
GES 16 SR 3/4-WD	3/4"	16
GES 20 SR-WD	3/4"	20
GES 25 SR 3/4-WD	3/4"	25
GES 25 SR-WD	1"	25
GES 30 SR-WD	1.1/4"	30
GES 38 SR-WD	1.1/2"	38



Light-duty, 60° Cone, BSPP

0350	Thread	OD mm
GES6 LRFOA	1/8"	6
GES6 LR 1/4FOA	1/4"	6
GES6 LR 3/8FOA	3/8"	6
GES8 LR 1/8FOA	1/8"	8
GES8 LRFOA	1/4"	8
GES8 LR 3/8FOA	3/8"	8
GES10 LRFOA	1/4"	10
GES10 LR 3/8FOA	3/8"	10
GES10 LR 1/2FOA	1/2"	10
GES12 LRFOA	3/8"	12
GES12 LR 1/4FOA	1/4"	12
GES12 LR 1/2FOA	1/2"	12
GES15 LR 3/8FOA	3/8"	15
GES15 LRFOA	1/2"	15
GES18 LRFOA	1/2"	18
GES18 LR 3/4FOA	3/4"	18
GES22 LR 1/2FOA	1/2"	22
GES22 LRFOA	3/4"	22
GES28 LR 3/4FOA	3/4"	28
GES28 LRFOA	1"	28

Heavy-duty, 60° Cone, BSPP

0350	Thread	OD mm
GES8 SRFOA	1/4"	8
GES10 SR 1/4FOA	1/4"	10
GES10 SRFOA	3/8"	10
GES12 SR 1/4FOA	1/4"	12
GES12 SRFOA	3/8"	12
GES12 SR 1/2FOA	1/2"	12
GES14 SRFOA	1/2"	14
GES16 SR 3/8FOA	3/8"	16
GES16 SRFOA	1/2"	16
GES16 SR 3/4FOA	3/4"	16
GES20 SR 1/2FOA	1/2"	20
GES20 SRFOA	3/4"	20
GES25 SR 3/4FOA	3/4"	25
GES25 SRFOA	1"	25
GES30 SR 1FOA	1"	30
GES35 LRFOA	1.1/4"	35
GES38 SR 1FOA	1"	38
GES38 SR 11/4FOA	1.1/4"	38

Fluid-Air Components Ltd

DIN 2353 BODY ONLY FITTINGS

Straight Coupling



Light-duty

0350	OD mm
GS 6 L	6
GS 8 L	8
GS 10 L	10
GS 12 L	12
GS 15 L	15
GS 18 L	18
GS 22 L	22
GS 28 L	28
GS 35 L	35
GS 42 L	42

Heavy-duty

0350	OD mm
GS 6 S	6
GS 8 S	8
GS 10 S	10
GS 12 S	12
GS 14 S	14
GS 16 S	16
GS 20 S	20
GS 25 S	25
GS 30 S	30
GS 38 S	38

Straight Bulkhead Coupling



Light-duty

0350	OD mm
GSS 6 L	6
GSS 8 L	8
GSS 10 L	10
GSS 12 L	12
GSS 15 L	15
GSS 18 L	18
GSS 22 L	22
GSS 28 L	28
GSS 35 L	35
GSS 42 L	42

Heavy-duty

0350	OD mm
GSS 6 S	6
GSS 8 S	8
GSS 10 S	10
GSS 12 S	12
GSS 14 S	14
GSS 16 S	16
GSS 20 S	20
GSS 25 S	25
GSS 30 S	30
GSS 38 S	38

Female Stud Coupling



Light-duty, BSPP

0350	Thread	OD mm
GAS 6 LR	1/8"	6
GAS 8 LR	1/4"	8
GAS 10 LR	1/4"	10
GAS 12 LR 1/4	1/4"	12
GAS 12 LR	3/8"	12
GAS 15 LR	1/2"	15
GAS 18 LR	1/2"	18
GAS 22 LR	3/4"	22
GAS 28 LR	1"	28
GAS 35 LR	1.1/4"	35
GAS 42 LR	1.1/2"	42

Heavy-duty, BSPP

0350	Thread	OD mm
GAS 6 SR	1/4"	6
GAS 8 SR	1/4"	8
GAS 10 SR	3/8"	10
GAS 12 SR	3/8"	12
GAS 14 SR	1/2"	14
GAS 16 SR	1/2"	16
GAS 20 SR	3/4"	20
GAS 25 SR	1"	25
GAS 30 SR	1.1/4"	30
GAS 38 SR	1.1/2"	38

Equal Elbow



Light-duty

0350	OD mm
WS 6 L	6
WS 8 L	8
WS 10 L	10
WS 12 L	12
WS 15 L	15
WS 18 L	18
WS 22 L	22
WS 28 L	28
WS 35 L	35
WS 42 L	42

Heavy-duty

0350	OD mm
WS 6 S	6
WS 8 S	8
WS 12 S	12
WS 16 S	16
WS 20 S	20
WS 25 S	25
WS 30 S	30
WS 38 S	38

Equal Tee



Light-duty

0350	OD mm
TS 6 L	6
TS 8 L	8
TS 10 L	10
TS 12 L	12
TS 15 L	15
TS 18 L	18
TS 22 L	22
TS 28 L	28
TS 35 L	35
TS 42 L	42

Heavy-duty

0350	OD mm
TS 6 S	6
TS 8 S	8
TS 10 S	10
TS 12 S	12
TS 14 S	14
TS 16 S	16
TS 20 S	20
TS 25 S	25
TS 30 S	30
TS 38 S	38

Fluid-Air Components Ltd

DIN 2353 BODY ONLY FITTINGS

90° Swivel Elbow



Light-duty

0350	OD mm
EWSD 6 L	6
EWSD 8 L	8
EWSD 10 L	10
EWSD 12 L	12
EWSD 15 L	15
EWSD 18 L	18
EWSD 22 L	22
EWSD 28 L	28
EWSD 35 L	35
EWSD 42 L	42

Heavy-duty

0350	OD mm
EWSD 6 S	6
EWSD 8 S	8
EWSD 10 S	10
EWSD 12 S	12
EWSD 14 S	14
EWSD 16 S	16
EWSD 20 S	20
EWSD 25 S	25
EWSD 30 S	30
EWSD 38 S	38

45° Swivel Elbow



Light-duty

0350	OD mm
EWSD 45 6 L	6
EWSD 45 8 L	8
EWSD 45 10 L	10
EWSD 45 12 L	12
EWSD 45 15 L	15
EWSD 45 18 L	18
EWSD 45 22 L	22
EWSD 45 28 L	28
EWSD 45 35 L	35
EWSD 45 42 L	42

Heavy-duty

0350	OD mm
EWSD 45 6 S	6
EWSD 45 8 S	8
EWSD 45 10 S	10
EWSD 45 12 S	12
EWSD 45 16 S	16
EWSD 45 20 S	20
EWSD 45 25 S	25
EWSD 45 30 S	30
EWSD 45 38 S	38

Male Stud Elbow



Light-duty, BSPT

0350	Thread	OD mm
WES 6 LRK	1/8"	6
WES 6 LRK 1/4	1/4"	6
WES 8 LRK	1/4"	8
WES 10 LRK	1/4"	10
WES 10 LRK 3/8	3/8"	10
WES 12 LRK 1/4	1/4"	12
WES 12 LRK	3/8"	12
WES 15 LRK	1/2"	15
WES 18 LRK	1/2"	18

Heavy-duty, BSPT

0350	Thread	OD mm
WES 6 SRK	1/4"	6
WES 8 SRK	1/4"	8
WES 10 SRK	3/8"	10
WES 12 SRK	3/8"	12
WES 14 SRK	1/2"	14
WES 16 SRK	1/2"	16

Swivel Branch Tee



Light-duty

0350	OD mm
ETSD 6 L	6
ETSD 8 L	8
ETSD 10 L	10
ETSD 12 L	12
ETSD 15 L	15
ETSD 18 L	18
ETSD 22 L	22
ETSD 28 L	28
ETSD 35 L	35
ETSD 42 L	42

Heavy-duty

0350	OD mm
ETSD 6 S	6
ETSD 8 S	8
ETSD 10 S	10
ETSD 12 S	12
ETSD 14 S	14
ETSD 16 S	16
ETSD 20 S	20
ETSD 25 S	25
ETSD 30 S	30
ETSD 38 S	38

Swivel Run Tee



Light-duty

0350	OD mm
ELSD 6 L	6
ELSD 8 L	8
ELSD 10 L	10
ELSD 12 L	12
ELSD 15 L	15
ELSD 18 L	18
ELSD 22 L	22
ELSD 28 L	28
ELSD 35 L	35
ELSD 42 L	42

Heavy-duty

0350	OD mm
ELSD 6 S	6
ELSD 8 S	8
ELSD 10 S	10
ELSD 12 S	12
ELSD 14 S	14
ELSD 16 S	16
ELSD 20 S	20
ELSD 25 S	25
ELSD 30 S	30
ELSD 38 S	38



For **Nuts & Olives**
see pages **117-118**

Fluid-Air Components Ltd

FLANGE COUPLINGS

Straight Flange Couplings

- O-Rings, spring washers and hexagon nuts must be purchased separately
- Comes complete with profile nut onl



35 Series

0350	OD mm	Max Pressure Bar
GFV10L35	10	315
GFV12L35	12	315
GFV15L35	15	250
GFV16L35	16	315
Tech Sheet 1705		

40 Series

0350	OD mm	Max Pressure Bar
GFV15L40	15	100
GFV18L40	18	100
GFV22L40	22	100
GFV28L40	28	100
Tech Sheet 1705		

55 Series

0350	OD mm	Max Pressure Bar
GFV20S55	20	250
Tech Sheet 1705		

Elbow Flange Couplings



35 Series

0350	OD mm	Max Pressure Bar
WFV10L35	10	315
WFV12L35	12	315
WFV15L35	15	250
WFV16S35	16	315
WFV20S35	20	250
Tech Sheet 1706		

40 Series

0350	OD mm	Max Pressure Bar
WFV15L40	15	100
WFV18L40	18	100
WFV22L40	22	100
WFV28L40	28	100
WFV35L40	35	100
WFV20S40	20	250
Tech Sheet 1706		

55 Series

0350	OD mm	Max Pressure Bar
WFV22L55	22	100
WFV35L55	35	100
WFV42L55	42	100
WFV20S55	20	250
WFV25S55	25	250
WFV30S55	30	250
Tech Sheet 1706		

O-Rings

- Sold as singles
- 1 required per unit



0350	To Suit
WAL610519	35 Series
WAL610499	40 Series
WAL610500	55 Series
Tech Sheet 1707	

Spring Washers

- Sold as singles
- 4 required per unit



0350	To Suit
WAL020102	35/40 Series
WAL020104	55 Series

Hexagon Sockets

- Sold as singles
- 4 required per unit



0350	To Suit
WAL020309	35/40 Series
WAL020324	55 Series
Tech Sheet 1707	

TOTAL

For **Industrial Grade Hand Tools**
see pages **1729-1741**



Fluid-Air Components Ltd

VALVES

Non-return Valves

Tube to BSPP, Light-duty




0350	Thread	OD mm	Max Pressure Bar
RVV6LRWD	1/8"	6	400
RVV8LRWD	1/4"	8	400
RVV10LRWD	1/4"	10	400
RVV12LRWD	3/8"	12	400
RVV15LRWD	1/2"	15	400
RVV18LRWD	1/2"	18	400
RVV22LRWD	3/4"	22	250
RVV28LRWD	1"	28	250
RVV35LRWD	1.1/4"	35	250
RVV42LRWD	1.1/2"	42	250
Tech Sheet 1708			

Tube to BSPP, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
RVV6SRWD	1/4"	6	400
RVV8SRWD	1/4"	8	400
RVV10SRWD	3/8"	10	400
RVV12SRWD	3/8"	12	400
RVV14SRWD	1/2"	14	400
RVV16SRWD	1/2"	16	400
RVV20SRWD	3/4"	20	400
RVV25SRWD	1"	25	250
RVV30SRWD	1.1/4"	30	250
RVV38SRWD	1.1/2"	38	250
Tech Sheet 1708			

1 bar cracking pressure.

Tube to Tube, Light-duty



0350	OD mm	Max Pressure Bar
RV6L	6	400
RV8L	8	400
RV10L	10	400
RV12L	12	400
RV15L	15	400
RV18L	18	400
RV22L	22	250
RV28L	28	250
RV35L	35	250
RV42L	42	250
Tech Sheet 1709		

Tube to Tube, Heavy-duty

0350	OD mm	Max Pressure Bar
RV6S	6	400
RV8S	8	400
RV10S	10	400
RV12S	12	400
RV14S	14	400
RV16S	16	400
RV20S	20	400
RV25S	25	250
RV30S	30	250
RV38S	38	250
Tech Sheet 1709		

Flow from tube to male

BSPP x Tube, Light-duty




0350	Thread	OD mm	Max Pressure Bar
RVZ6LRWD	1/8"	6	400
RVZ8LRWD	1/4"	8	400
RVZ10LRWD	1/4"	10	400
RVZ12LRWD	3/8"	12	400
RVZ15LRWD	1/2"	15	400
RVZ18LRWD	1/2"	18	400
RVZ22LRWD	3/4"	22	250
RVZ28LRWD	1"	28	250
RVZ35LRWD	1.1/4"	35	250
RVZ42LRWD	1.1/2"	42	250
Tech Sheet 1710			

BSPP x Tube, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
RVZ6SRWD	1/4"	6	400
RVZ8SRWD	1/4"	8	400
RVZ10SRWD	3/8"	10	400
RVZ12SRWD	3/8"	12	400
RVZ14SRWD	1/2"	14	400
RVZ16SRWD	1/2"	16	400
RVZ20SRWD	3/4"	20	400
RVZ25SRWD	1"	25	250
RVZ30SRWD	1.1/4"	30	250
RVZ38SRWD	1.1/2"	38	250
Tech Sheet 1710			

Metric x Tube, Light-duty



0350	Thread	OD mm	Max Pressure Bar
RVZ6LMWD	M10 x 1	6	400
RVZ8LMWD	M12 x 1.5	8	400
RVZ10LMWD	M14 x 1.5	10	400
RVZ12LMWD	M16 x 1.5	12	400
RVZ15LMWD	M18 x 1.5	15	400
RVZ18LMWD	M22 x 1.5	18	400
RVZ22LMWD	M26 x 1.5	22	250
RVZ28LMWD	M33 x 2	28	250
RVZ35LMWD	M42 x 2	35	250
RVZ42LMWD	M48 x 2	42	250
Tech Sheet 1711			

Metric x Tube, Heavy-duty

0350	Thread	OD mm	Max Pressure Bar
RVZ8SMWD	M14 x 1.5	8	400
RVZ10SMWD	M16 x 1.5	10	400
RVZ12SMWD	M18 x 1.5	12	400
RVZ14SMWD	M20 x 1.5	14	400
RVZ16SMWD	M22 x 1.5	16	400
RVZ20SMWD	M27 x 2	20	400
RVZ25SMWD	M33 x 2	25	250
RVZ30SMWD	M42 x 2	30	250
RVZ38SMWD	M48 x 2	38	250
Tech Sheet 1711			

Shuttle Valves



Ball Seat, Light-duty


0350	OD mm	Max Pressure Bar
TWV8L	8	250
TWV10L	10	250
TWV12L	12	250
Tech Sheet 1712		

Fluid-Air Components Ltd

VALVES

Compression Ball Valves

Tube connection both ends. The ball seal is pre-loaded, which ensures tight sealing even at lower pressures. Owing to the ball's floating position, any rise in pressure will progressively push the ball closer to the seal. Handles can be fitted in any position at 45° angles.



Light-duty

0350	OD mm	Max Pressure Bar
KHV6L	6	400
KHV8L	8	400
KHV10L	10	400
KHV12L	12	400
KHV15L	15	400
KHV18L	18	400
KHV22L	22	250
KHV28L	28	250
KHV35L	35	250
KHV42L	42	210
Tech Sheet 1713		

Heavy-duty

0350	OD mm	Max Pressure Bar
KHV8S	8	500
KHV10S	10	500
KHV12S	12	500
KHV14S	14	500
KHV16S	16	500
KHV20S	20	500
KHV25S	25	400
KHV30S	30	315
KHV38S	38	315
Tech Sheet 1713		

Compression L Ported Ball Valves

Tube connection all ports.

Warning: Port A must always be in the open position. Pressure may only be applied from this side. Application of pressure through the other ports is not permissible and may cause malfunction.



L Ported, Light-duty

0350	OD mm	Max Pressure Bar
KH3KV8L-LPORT	8	400
KH3KV10L-LPORT	10	400
KH3KV12L-LPORT	12	350
KH3KV15L-LPORT	15	350
Tech Sheet 1714		

Compression T Ported Ball Valves



T Ported, Light-duty

0350	OD mm	Max Pressure Bar
KH3KV10L-TPORT	10	400
KH3KV12L-TPORT	12	350
KH3KV15L-TPORT	15	350
Tech Sheet 1714		

STANDPIPE ADAPTORS

Metric Standpipe Adaptors, Mild Steel, BSPP

L Series

0023	Thread	OD mm
2101-7991	1/8"	6
2101-8007	1/4"	8
2135-2869	3/8"	8
2135-2885	1/8"	10
2101-8023	1/4"	10
2135-2893	1/4"	12
2101-8031	3/8"	12
2135-2901	1/2"	12
2135-3206	3/8"	15
2135-3214	3/8"	18
2135-3222	3/4"	18
2101-8049	1/2"	15
2101-8064	1/2"	18
2101-8072	3/4"	22
2135-3230	3/4"	28
2101-8080	1"	28
2101-8098	1.1/4"	35
2101-8114	1.1/2"	42

BSPP Threads internal 60° coned as standard.



S Series

0023	Thread	OD mm
2101-8122	1/4"	6
2101-8130	1/4"	8
2135-3321	3/8"	8
2101-8148	3/8"	10
2135-3339	1/4"	12
2101-8163	3/8"	12
2135-3347	1/2"	12
2101-8189	1/2"	14
2135-3354	3/8"	16
2101-8197	1/2"	16

0023	Thread	OD mm
2135-3362	3/4"	16
2135-3388	1/2"	20
2101-8205	3/4"	20
2135-3396	1"	20
2135-3404	3/4"	25
2101-8213	1"	25
2135-3412	1"	30
2101-8221	1.1/4"	30
2101-8239	1.1/2"	38

Fluid-Air Components Ltd

HIGH PRESSURE METRIC TUBE COUPLINGS

Benefits:
- Leak free O-Ring seal
- Safe joint every time
- Low tightening torque and clamping force rises with the internal pressure
- Low installed cost, no welding (so inert gas purging, NDT and excessive flushing are not required), minimal tube preparation and no special assembly equipment required
- Demountable and reusable, can be used with most tube materials

Features:
- Body – mild steel, stainless steel or cupro-nickel. Compatible with most fluids and environments. Locates O-Ring and tube.
- O-Ring – nitrile, FPM (Viton), EP or FEP encapsulated FPM. Compatible with most fluids. Highly resistant to leakage even under severe vibration, pressure pulsation and temperature cycling. Provides diametric seal between tube OD and body cavity.
- Nut – mild steel, stainless steel or cupro-nickel. Compatible with most environments. Closes split collet and retains sealing mechanism.
- Back-up washer – mild steel, stainless steel, or cupro-nickel. Provides additional support from the tube and locates the O-Ring.
- Split collet – mild steel, stainless steel or cupro-nickel. Clamping force rises with pressure. Large clamping area ensures minimal deformation of the tube. Retains tube in position.

Technical:
- 3:1 safety factor
- Derate by 50% for high pressure gas systems
- Pressure ratings based on the tube OD tolerance to BS3602 and DIN2391C

All fittings also available in the following materials upon request:
- Stainless steel
- Cupro-nickel

Seals available on request:
- EP (ethylene propylene)
- FEP encapsulated FPM

All fittings supplied with Nitrile seals as standard.

Working Temperature:
Nitrile: -40°C to +100°C
Viton: -20°C to +150°C

Maximum Working Pressure:
6mm to 22mm: 680 bar
25mm to 50mm: 500 bar

Straight Couplings



Tube x Tube

0459	OD mm
KRAM6CR	6
KRAM8CR	8
KRAM10CR	10
KRAM12CR	12
KRAM16CR	16
KRAM20CR	20
KRAM22CR	22
KRAM25CR	25
KRAM30CR	30
KRAM38CR	38
KRAM50CR	50

Tech Sheet 20544

Equal Bulkheads



Tube x Tube

0459	OD mm
KRAM6BPR	6
KRAM8BPR	8
KRAM10BPR	10
KRAM12BPR	12
KRAM16BPR	16
KRAM20BPR	20
KRAM22BPR	22
KRAM25BPR	25
KRAM30BPR	30
KRAM38BPR	38
KRAM50BPR	50

Tech Sheet 20545

Reducing Branch Tees



Tube x Tube

0459	OD mm	OD mm
KRAM12-M8ROTR	12	8
KRAM16-M8ROTR	16	8
KRAM20-M8ROTR	20	8
KRAM25-M12ROTR	25	12
KRAM25-M16ROTR	25	16
KRAM30-M16ROTR	30	16
KRAM38-M20ROTR	38	20

Tech Sheet 20548

Equal Elbows



Tube x Tube

0459	OD mm
KRAM6ER	6
KRAM8ER	8
KRAM10ER	10
KRAM12ER	12
KRAM16ER	16
KRAM20ER	20
KRAM22ER	22
KRAM25ER	25
KRAM30ER	30
KRAM38ER	38
KRAM50ER	50

Tech Sheet 20546

Equal Tees



Tube x Tube

0459	OD mm
KRAM6TR	6
KRAM8TR	8
KRAM10TR	10
KRAM12TR	12
KRAM16TR	16
KRAM20TR	20
KRAM22TR	22
KRAM25TR	25
KRAM30TR	30
KRAM38TR	38
KRAM50TR	50

Tech Sheet 20547

Minimum order quantity on selected items may apply

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HIGH PRESSURE METRIC TUBE COUPLINGS

Male Stud Couplings



BSPP

0459	OD mm	Thread
KRAM6-2MSCR	6	1/8"
KRAM6-4MSCR	6	1/4"
KRAM6-6MSCR	6	3/8"
KRAM8-2MSCR	8	1/8"
KRAM8-4MSCR	8	1/4"
KRAM8-6MSCR	8	3/8"
KRAM10-4MSCR	10	1/4"
KRAM10-6MSCR	10	3/8"
KRAM10-8MSCR	10	1/2"
KRAM12-4MSCR	12	1/4"
KRAM12-6MSCR	12	3/8"
KRAM12-8MSCR	12	1/2"
KRAM12-12MSCR	12	3/4"
KRAM16-6MSCR	16	3/8"
KRAM16-8MSCR	16	1/2"
KRAM16-12MSCR	16	3/4"
KRAM20-8MSCR	20	1/2"
KRAM20-12MSCR	20	3/4"
KRAM20-16MSCR	20	1"
KRAM25-12MSCR	25	3/4"
KRAM25-16MSCR	25	1"
KRAM25-20MSCR	25	1.1/4"
KRAM30-16MSCR	30	1"
KRAM30-20MSCR	30	1.1/4"
KRAM38-16MSCR	38	1"
KRAM38-20MSCR	38	1.1/4"
KRAM38-24MSCR	38	1.1/2"
KRAM50-20MSCR	50	1.1/4"
KRAM50-24MSCR	50	1.1/2"
KRAM50-32MSCR	50	2"
Tech Sheet 20549		

Male Stud Bulkheads



BSPP

0459	OD mm	Thread
KRAM8-4BHR	8	1/4"
KRAM10-6BHR	10	3/8"
KRAM12-6BHR	12	3/8"
KRAM16-8BHR	16	1/2"
KRAM20-12BHR	20	3/4"
KRAM25-16BHR	25	1"
KRAM38-20BHR	38	1.1/4"
KRAM38-24BHR	38	1.1/2"
Tech Sheet 20555		

Female Stud Couplings



BSPP

0459	OD mm	Thread
KRAM6-4FSCR	6	1/4"
KRAM8-6FSCR	8	3/8"
KRAM12-6FSCR	12	3/8"
KRAM16-8FSCR	16	1/2"
KRAM20-12FSCR	20	3/4"
KRAM25-16FSCR	25	1"
KRAM30-20FSCR	30	1.1/4"
KRAM38-24FSCR	38	1.1/2"
KRAM50-32FSCR	50	2"
Tech Sheet 20550		

Banjos



BSPP

0459	OD mm	Thread
KRAM6-4BJR	6	1/4"
KRAM8-4BJR	8	1/4"
KRAM10-6BJR	10	3/8"
KRAM12-6BJR	12	3/8"
KRAM16-8BJR	16	1/2"
KRAM20-12BJR	20	3/4"
KRAM25-16BJR	25	3/4"
KRAM30-20BJR	30	1.1/4"
KRAM38-24BJR	38	1.1/2"
Tech Sheet 20556		

Female Branch Tees



BSPP

0459	OD mm	Thread
KRAM10-6FOTR	10	3/8"
KRAM12-6FOTR	12	3/8"
KRAM16-8FOTR	16	1/2"
KRAM30-20FOTR	30	1.1/4"
KRAM38-20FOTR	38	1.1/4"
KRAM38-24FOTR	38	1.1/2"
KRAM50-24FOTR	50	1.1/2"
Tech Sheet 20551		

Breakaway Adaptors



OD


0459	OD mm
KRAM8BCR	8
KRAM10BCR	10
KRAM12BCR	12
KRAM16BCR	16
KRAM20BCR	20
KRAM22BCR	22
KRAM25BCR	25
KRAM30BCR	30
KRAM38BCR	38
KRAM50BCR	50
Tech Sheet 20552	

You might also need
Hydraulic Tubing
see pages **179-183**



RSB

For **Hydraulic Tube Clamps**
see pages **184-200**



Minimum order quantity on selected items may apply

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HIGH PRESSURE METRIC TUBE COUPLINGS

Reducing Nut Adaptors



Tube x Tube

0459	OD mm	OD mm
KRAM10-M6RNR	10	6
KRAM10-M8RNR	10	8
KRAM12-M8RNR	12	8
KRAM12-M10RNR	12	10
KRAM16-M8RNR	16	8
KRAM16-M12RNR	16	12
KRAM20-M10RNR	20	10
KRAM20-M12RNR	20	12
KRAM20-M16RNR	20	16
KRAM25-M12RNR	25	12
KRAM25-M16RNR	25	16
KRAM25-M20RNR	25	20
KRAM30-M25RNR	30	25
KRAM38-M20RNR	38	20
KRAM38-M25RNR	38	25
KRAM38-M30RNR	38	30
KRAM50-M25RNR	50	25
KRAM50-M30RNR	50	30
KRAM50-M38RNR	50	38

Tech Sheet 20557

Blanking End Plugs



OD

0459	OD mm
KRM6BPGR	6
KRM8BPGR	8
KRM10BPGR	10
KRM20BPGR	20
KRM22BPGR	22
KRM25BPGR	25
KRM30BPGR	30
KRM38BPGR	38
KRM50BPGR	50

Tech Sheet 20553

Washers



OD

0459	OD mm
KRM6W	6
KRM8W	8
KRM10W	10
KRM12W	12
KRM16W	16
KRM20W	20
KRM22W	22
KRM25W	25
KRM30W	30
KRM38W	38
KRM50W	50

Tech Sheet 20553

Collets



OD

0459	OD mm
KRM6R	6
KRM8R	8
KRM10R	10
KRM12R	12
KRM16R	16
KRM20R	20
KRM22R	22
KRM25R	25
KRM30R	30
KRM38R	38
KRM50R	50

Tech Sheet 20553

Nuts



OD

0459	OD mm
KRM6NCR	6
KRM8NCR	8
KRM10NCR	10
KRM12NCR	12
KRM16NCR	16
KRM20NCR	20
KRM22NCR	22
KRM25NCR	25
KRM30NCR	30
KRM38NCR	38
KRM50NCR	50

Tech Sheet 20553

O-Rings



Viton

0459	OD mm
KR200-010-9790	6
KR200-011-9790	8
KR200-613-9790	10
KR200-614-9790	12
KR200-114-9790	16
KR200-211-9790	20
KR200-212-9790	22
KR200-214-9790	25
KR200-217-9790	30
KR200-222-9790	38
KR207-071-9790	50

Tech Sheet 20554



Nitrile

0459	OD mm
KR200-010-4490	6
KR200-011-4490	8
KR200-613-4490	10
KR200-614-4490	12
KR200-114-4490	16
KR200-211-4490	20
KR200-212-4490	22
KR200-214-4490	25
KR200-217-4490	30
KR200-222-4490	38
KR207-071-4490	50

Tech Sheet 20554

Minimum order quantity on selected items may apply

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC IMPERIAL COMPRESSION FITTINGS

Steel Fittings for O.D. & N.B.



Nuts O.D. Tube

0023	OD
N4	1/4"
N6	3/8"
N8	1/2"
N10	5/8"
N12	3/4"
N14	7/8"
N16	1"
N20	1.1/4"
Tech Sheet 20133	



Nuts N.B. Tube

0023	OD
NN4	1/4"
NN6	3/8"
NN8	1/2"
NN12	3/4"
NN16	1"
NN20	1.1/4"
Tech Sheet 20133	



Ferrules N.B. Tube

0023	NB
NF4	1/4"
NF6	3/8"
NF8	1/2"
NF12	3/4"
NF16	1"
NF20	1.1/4"
Tech Sheet 20133	



Ferrules O.D. Tube

0023	NB
F4	1/4"
F5	5/16"
F6	3/8"
F8	1/2"
F10	5/8"
F12	3/4"
F16	1"
F20	1.1/4"
F24	1.1/2"
Tech Sheet 20133	

Technical Data:

1" O.D. 690 bar (10,000 psi) hydraulic or 345 bar (5,000 psi) gas.
1.1/4" O.D. 552 bar (8,000 psi) hydraulic or 276 bar (4,000 psi) gas.

N.B. Couplings are suitable for the following pressures, up to and including:

3/4" N.B. 690 bar (10,000 psi) hydraulic or 345 bar (5,000 psi) gas.
1" N.B. 552 bar (8,000 psi) hydraulic or 276 bar (4,000 psi) gas.
1.1/2" N.B. 345 bar (5,000 psi) hydraulic or 173 bar (2,500 psi) gas.



Straight Couplings O.D. Tube

0023	OD
SC4	1/4"
SC5	5/16"
SC6	3/8"
SC8	1/2"
SC10	5/8"
SC12	3/4"
SC14	7/8"
SC16	1"
SC20	1.1/4"
Tech Sheet 20134	



Straight Couplings N.B. Tube

0023	NB
NSC4	1/4"
NSC6	3/8"
NSC8	1/2"
NSC12	3/4"
NSC16	1"
NSC24	1.1/2"
Tech Sheet 20134	



BSPP Female Stud Couplings O.D. Tube

0023	OD	Thread
FC4-4	1/4"	1/4"
FC6-4	3/8"	1/4"
FC6-6	3/8"	3/8"
FC6-8	3/8"	1/2"
FC8-4	1/2"	1/4"
FC8-6	1/2"	3/8"
FC8-8	1/2"	1/2"
FC10-8	5/8"	1/2"
FC12-12	3/4"	3/4"
FC14-12	7/8"	3/4"
FC16-16	1"	1"
FC20-20	1.1/4"	1.1/4"
FC24-24	1.1/2"	1.1/2"
Tech Sheet 20135		



BSPP Female Stud Couplings N.B. Tube

0023	NB	Thread
NFC4-2	1/4"	1/8"
NFC4-8	1/4"	1/2"
NFC6-8	3/8"	1/2"
NFC8-6	1/2"	3/8"
NFC8-8	1/2"	1/2"
NFC8-12	1/2"	3/4"
NFC16-16	1"	1"
Tech Sheet 20135		



BSPP Male Stud Couplings O.D. Tube

0023	OD	Thread
MC4-2	1/4"	1/8"
MC4-4	1/4"	1/4"
MC4-6	1/4"	3/8"
MC6-4	3/8"	1/4"
MC6-6	3/8"	3/8"
MC6-8	3/8"	1/2"
MC8-4	1/2"	1/4"
MC8-6	1/2"	3/8"
MC8-8	1/2"	1/2"
MC8-12	1/2"	3/4"
MC10-8	5/8"	1/2"
MC10-12	5/8"	3/4"
MC12-8	3/4"	1/2"
MC12-12	3/4"	3/4"
MC14-12	7/8"	3/4"
MC16-12	1"	3/4"
MC16-16	1"	1"
MC16-20	1"	1.1/4"
MC20-16	1.1/4"	1"
MC20-20	1.1/4"	1.1/4"
MC20-24	1.1/4"	1.1/2"
MC24-20	1.1/2"	1.1/4"
MC24-24	1.1/2"	1.1/2"
Tech Sheet 20136		

Fluid-Air Components Ltd

HYDRAULIC IMPERIAL COMPRESSION FITTINGS

Steel Fittings for O.D. & N.B.



BSPP Male Stud Couplings N.B. Tube

0023	NB	Thread
NMC4-4	1/4"	1/4"
NMC4-6	1/4"	3/8"
NMC6-4	3/8"	1/4"
NMC6-6	3/8"	3/8"
NMC8-6	1/2"	3/8"
NMC8-8	1/2"	1/2"
NMC8-12	1/2"	3/4"
NMC8-16	1/2"	1"
NMC12-12	3/4"	3/4"
NMC16-12	1"	3/4"
NMC16-16	1"	1"
NMC16-20	1"	1.1/4"
NMC20-16	1.1/4"	1"
NMC20-20	1.1/4"	1.1/4"
NMC24-24	1.1/2"	1.1/2"
Tech Sheet 20137		



BSPT Male Stud Couplings O.D. Tube

0023	OD	Thread
MC4-4T	1/4"	1/4"
MC6-4T	3/8"	1/4"
MC6-6T	3/8"	3/8"
MC8-4T	1/2"	1/4"
MC8-6T	1/2"	3/8"
MC8-8T	1/2"	1/2"
MC10-8T	5/8"	1/2"
MC12-8T	3/4"	1/2"
MC12-12T	3/4"	3/4"
MC16-12T	1"	3/4"
MC16-16T	1"	1"
MC20-16T	1.1/4"	1"
MC24-24T	1.1/2"	1.1/2"
Tech Sheet 20138		



BSPT Male Stud Couplings N.B. Tube

0023	NB	Thread
NMC4-4T	1/4"	1/4"
NMC4-8T	1/4"	1/2"
NMC6-6T	3/8"	3/8"
NMC8-6T	1/2"	3/8"
NMC8-8T	1/2"	1/2"
NMC8-12T	1/2"	3/4"
NMC12-12T	3/4"	3/4"
NMC12-16T	3/4"	1"
NMC16-16T	1"	1"
NMC20-20T	1.1/4"	1.1/4"
NMC24-24T	1.1/2"	1.1/2"
Tech Sheet 20139		



BSPT Male Stud Elbows O.D. Tube

0023	OD	Thread
ME4-2T	1/4"	1/8"
ME4-4T	1/4"	1/4"
ME6-4T	3/8"	1/4"
ME6-6T	3/8"	3/8"
ME8-6T	1/2"	3/8"
ME12-8T	3/4"	1/2"
ME16-12T	1"	3/4"
ME16-16T	1"	1"
Tech Sheet 20140		



BSPP Male Stud Elbows N.B. Tube

0023	NB	Thread
NME6-6	3/8"	3/8"
NME8-8	1/2"	1/2"
Tech Sheet 20141		



BSPP Male Stud Elbows O.D. Tube

0023	OD	Thread
ME4-2	1/4"	1/8"
ME4-4	1/4"	1/4"
ME8-6	1/2"	3/8"
ME8-8	1/2"	1/2"
ME10-8	5/8"	1/2"
ME12-8	3/4"	1/2"
ME12-12	3/4"	3/4"
Tech Sheet 20141		



Equal Elbows O.D. Tube

0023	OD
E4	1/4"
E5	5/16"
E6	3/8"
E8	1/2"
E10	5/8"
E12	3/4"
E14	7/8"
E16	1"
E20	1.1/4"
E24	1.1/2"
Tech Sheet 20143	



Bulkhead Couplings O.D. Tube

0023	OD
BH6	3/8"
BH8	1/2"
BH10	5/8"
BH12	3/4"
Tech Sheet 20144	



BSPP Banjo Couplings O.D. Tube

0023	OD	Thread
BJ4-4	1/4"	1/4"
BJ6-4	3/8"	1/4"
BJ6-6	3/8"	3/8"
BJ8-6	1/2"	3/8"
BJ8-8	1/2"	1/2"
BJ10-8	5/8"	1/2"
Tech Sheet 20146		



Equal Tees O.D. Tube

0023	OD
T4	1/4"
T5	5/16"
T6	3/8"
T8	1/2"
T12	3/4"
T16	1"
T24	1.1/2"
Tech Sheet 20145	

Fluid-Air Components Ltd

HYDRAULIC IMPERIAL COMPRESSION FITTINGS

Steel Fittings for O.D. & N.B.



BSPT Male Stud Elbows N.B. Tube

0023	NB	Thread
NME4-4T	1/4"	1/4"
NME4-6T	1/4"	1/8"
NME6-6T	3/8"	3/8"
Tech Sheet 20140		



Equal Elbows N.B. Tube

0023	NB
NE4	1/4"
NE6	3/8"
NE8	1/2"
NE12	3/4"
NE16	1"
NE20	1.1/4"
Tech Sheet 20143	



BSPP Banjo Couplings N.B. Tube

0023	NB	Thread
NBJ2-2	1/8"	1/8"
NBJ8-8	1/2"	1/2"
Tech Sheet 20146		



Equal Tees N.B. Tube

0023	NB
NT4	1/4"
NT6	3/8"
NT8	1/2"
NT12	3/4"
NT20	1.1/4"
NT24	1.1/2"
Tech Sheet 20145	



BSPP Male Stud Standpipe Adaptors N.B. Fitting

0023	NB	Thread
NSA4-4	1/4"	1/4"
NSA6-4	1/4"	3/8"
NSA6-6	3/8"	3/8"
NSA8-6	3/8"	1/2"
NSA8-8	1/2"	1/2"
NSA12-8	1/2"	3/4"
NSA12-12	3/4"	3/4"
NSA12-16	1"	3/4"
NSA16-16	1"	1"
NSA16-20	1.1/4"	1"
NSA20-16	1"	1.1/4"
NSA20-20	1.1/4"	1.1/4"
Tech Sheet 20148		



BSPP Male Stud Standpipe Adaptors O.D. Fitting

0023	OD	Thread
SA4-4	1/4"	1/4"
SA4-6	3/8"	1/4"
SA6-6	3/8"	3/8"
SA6-8	1/2"	3/8"
SA8-8	1/2"	1/2"
SA8-12	3/4"	1/2"
SA12-12	3/4"	3/4"
SA12-16	1"	3/4"
SA16-16	1"	1"
SA20-20	1.1/4"	1.1/4"
Tech Sheet 20148		



Blanking Plugs O.D. Tube


0023	OD
BP4	1/4"
BP6	3/8"
BP8	1/2"
BP12	3/4"
BP20	1.1/4"
Tech Sheet 20149	



Blanking Plugs N.B. Tube

0023	NB
NBP4	1/4"
NBP6	3/8"
NBP8	1/2"
NBP12	3/4"
Tech Sheet 20149	

You might also need
Imperial Hydraulic Tubing
see page **182**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series, BSPP (Captive Seal)

0291	OD mm	Thread
GE-6L-2EO	6	1/8"
GE-6L-4EO	6	1/4"
GE-6L-6EO	6	3/8"
GE-6L-8EO	6	1/2"
GE-8L-2EO	8	1/8"
GE-8L-4EO	8	1/4"
GE-8L-6EO	8	3/8"
GE-8L-8EO	8	1/2"
GE-10L-2EO	10	1/8"
GE-10L-4EO	10	1/4"
GE-10L-6EO	10	3/8"
GE-10L-8EO	10	1/2"
GE-10L-12EO	10	3/4"
GE-12L-2EO	12	1/8"
GE-12L-4EO	12	1/4"
GE-12L-6EO	12	3/8"
GE-12L-8EO	12	1/2"
GE-12L-12EO	12	3/4"
GE-15L-4EO	15	1/4"
GE-15L-6EO	15	3/8"
GE-15L-8EO	15	1/2"
GE-15L-12EO	15	3/4"
GE-15L-16EO	15	1"
GE-18L-6EO	18	3/8"
GE-18L-8EO	18	1/2"
GE-18L-12EO	18	3/4"
GE-18L-16EO	18	1"
GE-22L-6EO	22	3/8"
GE-22L-8EO	22	1/2"
GE-22L-12EO	22	3/4"
GE-22L-16EO	22	1"
GE-22L-20EO	22	1.1/4"
GE-28L-8EO	28	1/2"
GE-28L-12EO	28	3/4"
GE-28L-16EO	28	1"
GE-28L-20EO	28	1.1/4"
GE-28L-24EO	28	1.1/2"
GE-35L-12EO	35	3/4"
GE-35L-16EO	35	1"
GE-35L-20EO	35	1.1/4"
GE-35L-24EO	35	1.1/2"
GE-42L-16EO	42	1"
GE-42L-20EO	42	1.1/4"
GE-42L-24EO	42	1.1/2"
GE-42L-32EO	42	2"
Tech Sheet 10585		

S Series, BSPP (Captive Seal)

0291	OD mm	Thread
GE-6S-2EO	6	1/8"
GE-6S-4EO	6	1/4"
GE-6S-6EO	6	3/8"
GE-6S-8EO	6	1/2"
GE-8S-2EO	8	1/8"
GE-8S-4EO	8	1/4"
GE-8S-6EO	8	3/8"
GE-8S-8EO	8	1/2"
GE-10S-2EO	10	1/8"
GE-10S-4EO	10	1/4"
GE-10S-6EO	10	3/8"
GE-10S-8EO	10	1/2"
GE-10S-12EO	10	3/4"
GE-12S-4EO	12	1/4"
GE-12S-6EO	12	3/8"
GE-12S-8EO	12	1/2"
GE-12S-12EO	12	3/4"
GE-14S-6EO	14	3/8"
GE-14S-8EO	14	1/2"
GE-14S-12EO	14	3/4"
GE-16S-4EO	16	1/4"
GE-16S-6EO	16	3/8"
GE-16S-8EO	16	1/2"
GE-16S-12EO	16	3/4"
GE-16S-16EO	16	1"
GE-20S-6EO	20	3/8"
GE-20S-8EO	20	1/2"
GE-20S-12EO	20	3/4"
GE-20S-16EO	20	1"
GE-20S-20EO	20	1.1/4"
GE-25S-8EO	25	1/2"
GE-25S-12EO	25	3/4"
GE-25S-16EO	25	1"
GE-25S-20EO	25	1.1/4"
GE-30S-12EO	30	3/4"
GE-30S-16EO	30	1"
GE-30S-20EO	30	1.1/4"
GE-30S-24EO	30	1.1/2"
GE-38S-16EO	38	1"
GE-38S-20EO	38	1.1/4"
GE-38S-24EO	38	1.1/2"
Tech Sheet 10585		

L Series, Metric (Captive Seal)

0291	OD mm	Thread
GE-6L-10MEO	6	M10 x 1
GE-6L-12MEO	6	M12 x 1.5
GE-6L-14MEO	6	M14 x 1.5
GE-8L-10MEO	8	M10 x 1.0
GE-8L-12MEO	8	M12 x 1.5
GE-8L-14MEO	8	M14 x 1.5
GE-8L-16MEO	8	M16 x 1.5
GE-8L-18MEO	8	M18 x 1.5
GE-10L-10MEO	10	M10 x 1.0
GE-10L-12MEO	10	M12 x 1.5
GE-10L-14MEO	10	M14 x 1.5
GE-10L-16MEO	10	M16 x 1.5
GE-10L-18MEO	10	M18 x 1.5
GE-10L-22MEO	10	M22 x 1.5
GE-12L-12MEO	12	M12 x 1.5
GE-12L-14MEO	12	M14 x 1.5
GE-12L-16MEO	12	M16 x 1.5
GE-12L-18MEO	12	M18 x 1.5
GE-12L-22MEO	12	M22 x 1.5
GE-15L-16MEO	15	M16 x 1.5
GE-15L-18MEO	15	M18 x 1.5
GE-15L-22MEO	15	M22 x 1.5
GE-18L-18MEO	18	M18 x 1.5
GE-18L-22MEO	18	M22 x 1.5
GE-18L-26MEO	18	M26 x 1.5
GE-22L-22MEO	22	M22 x 1.5
GE-22L-26MEO	22	M26 x 1.5
GE-28L-33MEO	28	M33 x 2
GE-35L-42MEO	35	M42 x 2.0
GE-42L-48MEO	42	M48 x 2.0
Tech Sheet 10586		

S Series, Metric (Captive Seal)

0291	OD mm	Thread
GE-6S-12MEO	6	M12 x 1.5
GE-6S-14MEO	6	M14 x 1.5
GE-8S-12MEO	8	M12 x 1.5
GE-8S-14MEO	8	M14 x 1.5
GE-8S-16MEO	8	M16 x 1.5
GE-10S-14MEO	10	M14 x 1.5
GE-10S-16MEO	10	M16 x 1.5
GE-10S-18MEO	10	M18 x 1.5
GE-12S-14MEO	12	M14 x 1.5
GE-12S-16MEO	12	M16 x 1.5
GE-12S-18MEO	12	M18 x 1.5
GE-12S-20MEO	12	M20 x 1.5
GE-12S-22MEO	12	M22 x 1.5
GE-14S-20MEO	14	M20 x 1.5
GE-14S-22MEO	14	M22 x 1.5
GE-16S-18MEO	16	M18 x 1.5
GE-16S-22MEO	16	M22 x 1.5
GE-20S-27MEO	20	M27 x 2
GE-25S-33MEO	25	M33 x 2
GE-30S-42MEO	30	M42 x 2
GE-38S-48MEO	38	M48 x 2
Tech Sheet 10586		

For **Bonded Seals** see pages **109-112**



Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series, BSPP, Form B Sealing

0291	OD mm	Thread
GE-6L-2RP	6	1/8"
GE-6L-4RP	6	1/4"
GE-6L-6RP	6	3/8"
GE-6L-8RP	6	1/2"
GE-8L-2RP	8	1/8"
GE-8L-4RP	8	1/4"
GE-8L-6RP	8	3/8"
GE-8L-8RP	8	1/2"
GE-10L-2RP	10	1/8"
GE-10L-4RP	10	1/4"
GE-10L-6RP	10	3/8"
GE-10L-8RP	10	1/2"
GE-10L-12RP	10	3/4"
GE-12L-2RP	12	1/8"
GE-12L-4RP	12	1/4"
GE-12L-6RP	12	3/8"
GE-12L-8RP	12	1/2"
GE-12L-12RP	12	3/4"
GE-15L-4RP	15	1/4"
GE-15L-6RP	15	3/8"
GE-15L-8RP	15	1/2"
GE-15L-12RP	15	3/4"
GE-18L-6RP	18	3/8"
GE-18L-8RP	18	1/2"
GE-18L-12RP	18	3/4"
GE-18L-16RP	18	1"
GE-22L-6RP	22	3/8"
GE-22L-8RP	22	1/2"
GE-22L-12RP	22	3/4"
GE-22L-16RP	22	1"
GE-22L-20RP	22	1.1/4"
GE-28L-8RP	28	1/2"
GE-28L-12RP	28	3/4"
GE-28L-16RP	28	1"
GE-28L-20RP	28	1.1/4"
GE-28L-24RP	28	1.1/2"
GE-35L-12RP	35	3/4"
GE-35L-16RP	35	1"
GE-35L-20RP	35	1.1/4"
GE-35L-24RP	35	1.1/2"
GE-42L-16RP	42	1"
GE-42L-20RP	42	1.1/4"
GE-42L-24RP	42	1.1/2"
Tech Sheet 20796		

S Series, BSPP, Form B Sealing

0291	OD mm	Thread
GE-6S-2RP	6	1/8"
GE-6S-4RP	6	1/4"
GE-6S-6RP	6	3/8"
GE-6S-8RP	6	1/2"
GE-8S-2RP	8	1/8"
GE-8S-4RP	8	1/4"
GE-8S-6RP	8	3/8"
GE-8S-8RP	8	1/2"
GE-10S-2RP	10	1/8"
GE-10S-4RP	10	1/4"
GE-10S-6RP	10	3/8"
GE-10S-8RP	10	1/2"
GE-10S-12RP	10	3/4"
GE-12S-4RP	12	1/4"
GE-12S-6RP	12	3/8"
GE-12S-8RP	12	1/2"
GE-12S-12RP	12	3/4"
GE-14S-4RP	14	1/4"
GE-14S-6RP	14	3/8"
GE-14S-8RP	14	1/2"
GE-14S-12RP	14	3/4"
GE-16S-4RP	16	1/4"
GE-16S-6RP	16	3/8"
GE-16S-8RP	16	1/2"
GE-16S-12RP	16	3/4"
GE-16S-16RP	16	1"
GE-20S-6RP	20	3/8"
GE-20S-8RP	20	1/2"
GE-20S-12RP	20	3/4"
GE-20S-16RP	20	1"
GE-20S-20RP	20	1.1/4"
GE-25S-8RP	25	1/2"
GE-25S-12RP	25	3/4"
GE-25S-16RP	25	1"
GE-25S-20RP	25	1.1/4"
GE-30S-12RP	30	3/4"
GE-30S-16RP	30	1"
GE-30S-20RP	30	1.1/4"
GE-30S-24RP	30	1.1/2"
GE-38S-16RP	38	1"
GE-38S-20RP	38	1.1/4"
GE-38S-24RP	38	1.1/2"
Tech Sheet 20796		

L Series, Metric Parallel, Form B Sealing

0291	OD mm	Thread
GE-6L-10MPB	6	M10 x 1
GE-6L-12MPB	6	M12 x 1.5
GE-6L-14MPB	6	M14 x 1.5
GE-8L-10MPB	8	M10 x 1.0
GE-8L-12MPB	8	M12 x 1.5
GE-8L-14MPB	8	M14 x 1.5
GE-8L-18MPB	8	M18 x 1.5
GE-8L-16MPB	8	M16 x 1.5
GE-10L-10MPB	10	M16 x 1.5
GE-10L-14MPB	10	M14 x 1.5
GE-10L-12MPB	10	M12 x 1.5
GE-10L-16MPB	10	M16 x 1.5
GE-10L-18MPB	10	M18 x 1.5
GE-10L-22MPB	10	M22 x 1.5
GE-12L-14MPB	12	M14 x 1.5
GE-12L-12MPB	12	M12 x 1.5
GE-12L-16MPB	12	M16 x 1.5
GE-12L-18MPB	12	M18 x 1.5
GE-12L-22MPB	12	M22 x 1.5
GE-15L-16MPB	15	M16 x 1.5
GE-15L-18MPB	15	M18 x 1.5
GE-15L-22MPB	15	M22 x 1.5
GE-18L-18MPB	18	M18 x 1.5
GE-18L-22MPB	18	M22 x 1.5
GE-18L-26MPB	18	M26 x 1.5
GE-22L-22MPB	22	M22 x 1.5
GE-22L-26MPB	22	M26 x 1.5
GE-28L-33MPB	28	M33 x 1.5
GE-35L-42MPB	35	M42 x 2
GE-42L-48MPB	42	M48 x 2
Tech Sheet 10587		

S Series, Metric Parallel, Form B Sealing

0291	OD mm	Thread
GE-6S-12MPB	6	M12 x 1.5
GE-6S-14MPB	6	M14 x 1.5
GE-8S-14MPB	8	M14 x 1.5
GE-10S-16MPB	10	M16 x 1.5
GE-10S-18MPB	10	M18 x 1.5
GE-12S-14MPB	12	M14 x 1.5
GE-12S-16MPB	12	M16 x 1.5
GE-12S-18MPB	12	M18 x 1.5
GE-12S-22MPB	12	M22 x 1.5
GE-14S-20MPB	14	M20 x 1.5
GE-16S-18MPB	16	M18 x 1.5
GE-16S-22MPB	16	M22 x 1.5
GE-20S-27MPB	20	M27 x 2
GE-25S-33MPB	25	M33 x 2
GE-30S-42MPB	30	M42 x 2
GE-38S-48MPB	38	M48 x 2
Tech Sheet 10587		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings

L Series, BSPT

0291	OD mm	Thread
GE-6L-2RT	6	1/8"
GE-6L-4RT	6	1/4"
GE-6L-6RT	6	3/8"
GE-6L-8RT	6	1/2"
GE-8L-2RT	8	1/8"
GE-8L-4RT	8	1/4"
GE-8L-6RT	8	3/8"
GE-8L-8RT	8	1/2"
GE-10L-2RT	10	1/8"
GE-10L-4RT	10	1/4"
GE-10L-6RT	10	3/8"
GE-10L-8RT	10	1/2"
GE-12L-2RT	12	1/8"
GE-12L-4RT	12	1/4"
GE-12L-6RT	12	3/8"
GE-12L-8RT	12	1/2"
GE-12L-12RT	12	3/4"
GE-15L-4RT	15	1/4"
GE-15L-6RT	15	3/8"
GE-15L-8RT	15	1/2"
GE-15L-12RT	15	3/4"
GE-18L-6RT	18	3/8"
GE-18L-8RT	18	1/2"
GE-18L-12RT	18	3/4"
GE-22L-6RT	22	3/8"
GE-22L-8RT	22	1/2"
GE-22L-12RT	22	3/4"
GE-22L-16RT	22	1"
GE-28L-8RT	28	1/2"
GE-28L-12RT	28	3/4"
GE-28L-16RT	28	1"
GE-28L-20RT	28	1.1/4"
GE-35L-16RT	35	1"
GE-35L-20RT	35	1.1/4"
GE-35L-24RT	35	1.1/2"
GE-42L-20RT	42	1.1/4"
GE-42L-24RT	42	1.1/2"
Tech Sheet 10588		

S Series, BSPT

0291	OD mm	Thread
GE-6S-2RT	6	1/8"
GE-6S-4RT	6	1/4"
GE-6S-6RT	6	3/8"
GE-8S-2RT	8	1/8"
GE-8S-4RT	8	1/4"
GE-8S-6RT	8	3/8"
GE-10S-4RT	10	1/4"
GE-10S-6RT	10	3/8"
GE-12S-4RT	12	1/4"
GE-12S-6RT	12	3/8"
GE-12S-8RT	12	1/2"
GE-14S-6RT	14	3/8"
GE-14S-8RT	14	1/2"
GE-16S-6RT	16	3/8"
GE-16S-8RT	16	1/2"
GE-16S-12RT	16	3/4"
GE-20S-8RT	20	1/2"
GE-20S-12RT	20	3/4"
GE-25S-12RT	25	3/4"
GE-25S-16RT	25	1"
GE-30S-20RT	30	1.1/4"
GE-38S-24RT	38	1.1/2"
Tech Sheet 10588		



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series, NPT

0291	OD mm	Thread
GE-6L-2N	6	1/8"
GE-6L-4N	6	1/4"
GE-6L-6N	6	3/8"
GE-6L-8N	6	1/2"
GE-8L-2N	8	1/8"
GE-8L-4N	8	1/4"
GE-8L-6N	8	3/8"
GE-8L-8N	8	1/2"
GE-10L-2N	10	1/8"
GE-10L-4N	10	1/4"
GE-10L-6N	10	3/8"
GE-10L-8N	10	1/2"
GE-10L-12N	10	3/4"
GE-12L-2N	12	1/8"
GE-12L-4N	12	1/4"
GE-12L-6N	12	3/8"
GE-12L-8N	12	1/2"
GE-12L-12N	12	3/4"
GE-15L-4N	15	1/4"
GE-15L-6N	15	3/8"
GE-15L-8N	15	1/2"
GE-15L-12N	15	3/4"
GE-18L-6N	18	3/8"
GE-18L-8N	18	1/2"
GE-18L-12N	18	3/4"
GE-18L-16N	18	1"
GE-22L-6N	22	3/8"
GE-22L-8N	22	1/2"
GE-22L-12N	22	3/4"
GE-22L-16N	22	1"
GE-22L-20N	22	1.1/4"
GE-28L-8N	28	1/2"
GE-28L-12N	28	3/4"
GE-28L-16N	28	1"
GE-28L-20N	28	1.1/4"
GE-35L-16N	35	1"
GE-35L-20N	35	1.1/4"
GE-35L-24N	35	1.1/2"
GE-42L-16N	42	1"
GE-42L-20N	42	1.1/4"
GE-42L-24N	42	1.1/2"
Tech Sheet 10589		

S Series, NPT

0291	OD mm	Thread
GE-6S-2N	6	1/8"
GE-6S-4N	6	1/4"
GE-6S-6N	6	3/8"
GE-6S-8N	6	1/2"
GE-8S-2N	8	1/8"
GE-8S-4N	8	1/4"
GE-8S-6N	8	3/8"
GE-8S-8N	8	1/2"
GE-10S-2N	10	1/8"
GE-10S-4N	10	1/4"
GE-10S-6N	10	3/8"
GE-10S-8N	10	1/2"
GE-10S-12N	10	3/4"
GE-12S-4N	12	1/4"
GE-12S-6N	12	3/8"
GE-12S-8N	12	1/2"
GE-12S-12N	12	3/4"
GE-14S-6N	14	3/8"
GE-14S-8N	14	1/2"
GE-14S-12N	14	3/4"
GE-16S-6N	16	3/8"
GE-16S-8N	16	1/2"
GE-16S-12N	16	3/4"
GE-16S-16N	16	1"
GE-20S-6N	20	3/8"
GE-20S-12N	20	3/4"
GE-20S-16N	20	1"
GE-20S-20N	20	1.1/4"
GE-25S-8N	25	1/2"
GE-25S-12N	25	3/4"
GE-25S-16N	25	1"
GE-25S-20N	25	1.1/4"
GE-30S-12N	30	3/4"
GE-30S-16N	30	1"
GE-30S-20N	30	1.1/4"
GE-30S-24N	30	1.1/2"
GE-38S-16N	38	1"
GE-38S-20N	38	1.1/4"
GE-38S-24N	38	1.1/2"
Tech Sheet 10589		

stainless steel



For **Stainless Steel Component parts** see page **1255**

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings



L Series, UNF, O-Ring Sealing

0291	OD mm	Thread
GE-6L-7/16UNF	6	7/16"
GE-6L-1/2UNF	6	1/2"
GE-6L-9/16UNF	6	9/16"
GE-8L-7/16UNF	8	7/16"
GE-8L-1/2UNF	8	1/2"
GE-8L-9/16UNF	8	9/16"
GE-10L-7/16UNF	10	7/16"
GE-10L-1/2UNF	10	1/2"
GE-10L-9/16UNF	10	9/16"
GE-10L-3/4UNF	10	3/4"
GE-12L-9/16UNF	12	9/16"
GE-12L-3/4UNF	12	3/4"
GE-12L-7/8UNF	12	7/8"
GE-15L-9/16UNF	15	9/16"
GE-15L-3/4UNF	15	3/4"
GE-15L-7/8UNF	15	7/8"
GE-18L-3/4UNF	18	3/4"
GE-18L-7/8UNF	18	7/8"
GE-18L-11/16UNF	18	1.1/16"
GE-22L-3/4UNF	22	3/4"
GE-22L-7/8UNF	22	7/8"
GE-22L-11/16UNF	22	1.1/16"
GE-22L-15/16UNF	22	1.5/16"
GE-28L-11/16UNF	28	1.1/16"
GE-28L-15/16UNF	28	1.5/16"
GE-28L-15/8UNF	28	1.5/8"
GE-35L-15/16UNF	35	1.5/16"
GE-35L-15/8UNF	35	1.5/8"
GE-42L-15/8UNF	42	1.5/8"
GE-42L-17/8UNF	42	1.7/8"
Tech Sheet 20797		

S Series, UNF, O-Ring Sealing

0291	OD mm	Thread
GE-6S-7/16UNF	6	7/16"
GE-8S-1/2UNF	8	1/2"
GE-8S-7/16UNF	8	7/16"
GE-8S-9/16UNF	8	9/16"
GE-10S-3/4UNF	10	3/4"
GE-12S-9/16UNF	12	9/16"
GE-12S-3/4UNF	12	3/4"
GE-12S-7/8UNF	12	7/8"
GE-14S-3/4UNF	14	3/4"
GE-16S-3/4UNF	16	3/4"
GE-16S-7/8UNF	16	7/8"
GE-16S-11/16UNF	16	1.1/16"
GE-20S-3/4UNF	20	3/4"
GE-20S-7/8UNF	20	7/8"
GE-20S-11/16UNF	20	1.1/16
GE-20S-15/16UNF	20	1.5/16"
GE-25S-11/16UNF	25	1.1/16
GE-25S-15/16UNF	25	1.5/16"
GE-30S-11/16UNF	30	1.1/16"
GE-30S-15/16UNF	30	1.5/16"
GE-30S-15/8UNF	30	1.5/8"
GE-38S-15/8UNF	38	1.5/8"
GE-38S-17/8UNF	38	1.7/8"

Female Stud Couplings



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series, BSPP

0291	OD mm	Thread
GAI-6L-2RG	6	1/8"
GAI-6L-4RG	6	1/4"
GAI-6L-6RG	6	3/8"
GAI-6L-8RG	6	1/2"
GAI-8L-2RG	8	1/8"
GAI-8L-4RG	8	1/4"
GAI-8L-6RG	8	3/8"
GAI-8L-8RG	8	1/2"
GAI-10L-2RG	10	1/8"
GAI-10L-4RG	10	1/4"
GAI-10L-6RG	10	3/8"
GAI-10L-8RG	10	1/2"
GAI-12L-4RG	12	1/4"
GAI-12L-6RG	12	3/8"
GAI-12L-8RG	12	1/2"
GAI-15L-6RG	15	3/8"
GAI-15L-8RG	15	1/2"
GAI-15L-12RG	15	3/4"
GAI-18L-6RG	18	3/8"
GAI-18L-8RG	18	1/2"
GAI-18L-12RG	18	3/4"
GAI-22L-8RG	22	1/2"
GAI-22L-12RG	22	3/4"
GAI-28L-16RG	28	1"
GAI-35L-20RG	35	1.1/4"
GAI-42L-24RG	42	1.1/2"
Tech Sheet 10590		

S Series, BSPP

0291	OD mm	Thread
GAI-6S-4RG	6	1/4"
GAI-8S-4RG	8	1/4"
GAI-8S-6RG	8	3/8"
GAI-8S-8RG	8	1/2"
GAI-10S-6RG	10	3/8"
GAI-10S-8RG	10	1/2"
GAI-12S-4RG	12	1/4"
GAI-12S-6RG	12	3/8"
GAI-12S-8RG	12	1/2"
GAI-14S-6RG	14	3/8"
GAI-14S-8RG	14	1/2"
GAI-16S-6RG	16	3/8"
GAI-16S-8RG	16	1/2"
GAI-20S-8RG	20	1/2"
GAI-20S-12RG	20	3/4"
GAI-25S-12RG	25	3/4"
GAI-25S-16RG	25	1"
GAI-30S-20RG	30	1.1/4"
GAI-38S-24RG	38	1.1/2"

L Series, NPT

0291	OD mm	Thread
GAI-6L-2N	6	1/8"
GAI-6L-4N	6	1/4"
GAI-8L-4N	8	1/4"
GAI-10L-4N	10	1/4"
GAI-10L-6N	10	3/8"
GAI-10L-8N	10	1/2"
GAI-12L-4N	12	1/4"
GAI-12L-6N	12	3/8"
GAI-12L-8N	12	1/2"
GAI-15L-8N	15	1/2"
GAI-18L-8N	18	1/2"
GAI-22L-12N	22	3/4"
GAI-28L-16N	28	1"
GAI-35L-20N	35	1.1/4"
GAI-42L-24N	42	1.1/2"

S Series, NPT

0291	OD mm	Thread
GAI-6S-4N	6	1/4"
GAI-8S-4N	8	1/4"
GAI-10S-6N	10	3/8"
GAI-12S-6N	12	3/8"
GAI-12S-8N	12	1/2"
GAI-14S-8N	14	1/2"
GAI-16S-6N	16	3/8"
GAI-16S-8N	16	1/2"
GAI-20S-12N	20	3/4"
GAI-25S-16N	25	1"
GAI-30S-20N	30	1.1/4"
GAI-38S-24N	38	1.1/2"

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Straight Stud Standpipes



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series, BSPP (Captive Seal)

0291	OD mm	Thread
EVGE-6L-2EO	6	1/8"
EVGE-8L-4EO	8	1/4"
EVGE-8L-6EO	8	3/8"
EVGE-10L-4EO	10	1/4"
EVGE-10L-6EO	10	3/8"
EVGE-10L-8EO	10	1/2"
EVGE-12L-4EO	12	1/4"
EVGE-12L-6EO	12	3/8"
EVGE-12L-8EO	12	1/2"
EVGE-15L-6EO	15	3/8"
EVGE-15L-8EO	15	1/2"
EVGE-18L-6EO	18	3/8"
EVGE-18L-8EO	18	1/2"
EVGE-18L-12EO	18	3/4"
EVGE-22L-6EO	22	3/8"
EVGE-22L-8EO	22	1/2"
EVGE-22L-12EO	22	3/4"
EVGE-28L-12EO	28	3/4"
EVGE-28L-16EO	28	1"
EVGE-35L-20EO	35	1.1/4"
EVGE-42L-24EO	42	1.1/2"
Tech Sheet 10591		

S Series, BSPP (Captive Seal)

0291	OD mm	Thread
EVGE-6S-2EO	6	1/8"
EVGE-6S-4EO	6	1/4"
EVGE-8S-4EO	8	1/4"
EVGE-8S-6EO	8	3/8"
EVGE-10S-4EO	10	1/4"
EVGE-10S-6EO	10	3/8"
EVGE-10S-8EO	10	1/2"
EVGE-12S-4EO	12	1/4"
EVGE-12S-6EO	12	3/8"
EVGE-12S-8EO	12	1/2"
EVGE-14S-8EO	14	1/2"
EVGE-16S-6EO	16	3/8"
EVGE-16S-8EO	16	1/2"
EVGE-16S-12EO	16	3/4"
EVGE-20S-8EO	20	1/2"
EVGE-20S-12EO	20	3/4"
EVGE-25S-12EO	25	3/4"
EVGE-25S-16EO	25	1"
EVGE-30S-20EO	30	1.1/4"
EVGE-38S-24EO	38	1.1/2"
Tech Sheet 10591		

L Series, Metric Parallel (Captive Seal)

0291	OD mm	Thread
EVGE-6L-10MEO	6	M10 x 1
EVGE-8L-12MEO	8	M12 x 1.5
EVGE-10L-14MEO	10	M14 x 1.5
EVGE-15L-18MEO	15	M18 x 1.5
EVGE-18L-22MEO	18	M22 x 1.5
EVGE-22L-26MEO	22	M26 x 1.5
EVGE-28L-33MEO	28	M33 x 2
EVGE-35L-42MEO	35	M42 x 2
EVGE-42L-48MEO	42	M48 x 2
Tech Sheet 10592		

S Series, Metric Parallel (Captive Seal)

0291	OD mm	Thread
EVGE-6S-12MEO	6	M12 x 1.5
EVGE-8S-14MEO	8	M14 x 1.5
EVGE-10S-16MEO	10	M16 x 1.5
EVGE-12S-18MEO	12	M18 x 1.5
EVGE-14S-20MEO	14	M20 x 1.5
EVGE-16S-22MEO	16	M22 x 1.5
EVGE-20S-27MEO	20	M27 x 2
EVGE-30S-42MEO	30	M42 x 2
EVGE-38S-48MEO	38	M48 x 2
Tech Sheet 10592		

Reducing Adaptors



Male x Female, BSPP

0291	OD mm	Thread
GRI-2-4RG	1/8"	1/4"
GRI-2-6RG	1/8"	3/8"
GRI-4-2RG	1/4"	1/8"
GRI-4-6RG	1/4"	3/8"
GRI-4-8RG	1/4"	1/2"
GRI-4-12RG	1/4"	3/4"
GRI-6-4RG	3/8"	1/4"
GRI-6-8RG	3/8"	1/2"
GRI-6-12RG	3/8"	3/4"
GRI-6-16RG	3/8"	1"
GRI-8-6RG	1/2"	3/8"
GRI-8-12RG	1/2"	3/4"
GRI-8-16RG	1/2"	1"
GRI-8-20RG	1/2"	1.1/4"
GRI-12-8RG	3/4"	1/2"
GRI-12-16RG	3/4"	1"
GRI-12-20RG	3/4"	1.1/4"
GRI-12-24RG	3/4"	1.1/2"
GRI-16-12RG	1"	3/4"
GRI-16-20RG	1"	1.1/4"
GRI-16-24RG	1"	1.1/2"
GRI-20-16RG	1.1/4"	1"
GRI-24-20RG	1.1/2"	1.1/4"
GRI-20-24RG	1.1/4"	1.1/2"
Tech Sheet 10593		

Reducing Bush



Male x Female, BSPP

0291	OD mm	Thread
GRI-6-2RG	3/8"	1/8"
GRI-8-2RG	1/2"	1/8"
GRI-8-4RG	1/2"	1/4"
GRI-12-2RG	3/4"	1/8"
GRI-12-4RG	3/4"	1/4"
GRI-12-6RG	3/4"	3/8"
GRI-16-4RG	1"	1/4"
GRI-16-6RG	1"	3/8"
GRI-16-8RG	1"	1/2"
GRI-20-6RG	1.1/4"	3/8"
GRI-20-8RG	1.1/4"	1/2"
GRI-20-12RG	1.1/4"	3/4"
GRI-24-8RG	1.1/2"	1/2"
GRI-24-12RG	1.1/2"	3/4"
GRI-24-16RG	1.1/2"	1"
GRI-32-8RG	2"	1/2"
GRI-32-12RG	2"	3/4"
GRI-32-16RG	2"	1"
GRI-32-20RG	2"	1.1/4"
GRI-32-24RG	2"	1.1/2"
Tech Sheet 10593		

Adjustable Branch Tees

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C
(DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C
(FPM/Viton)



L Series, Metric, Female Thread

0291	OD mm	Thread
EVT-6L	6	M12 x 1.5
EVT-8L	8	M14 x 1.5
EVT-10L	10	M16 x 1.5
EVT-12L	12	M18 x 1.5
EVT-15L	15	M22 x 1.5
EVT-18L	18	M26 x 1.5
EVT-22L	22	M30 x 2
EVT-28L	28	M36 x 2
EVT-35L	35	M45 x 2
EVT-42L	42	M52 x 2
Tech Sheet 10594		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVT-6S	6	M14 x 1.5
EVT-8S	8	M16 x 1.5
EVT-10S	10	M18 x 1.5
EVT-12S	12	M20 x 1.5
EVT-14S	14	M22 x 1.5
EVT-16S	16	M24 x 1.5
EVT-20S	20	M30 x 2
EVT-25S	25	M36 x 2
EVT-30S	30	M42 x 2
EVT-38S	38	M52 x 2
Tech Sheet 10594		

FAC
Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Adjustable Run Tees

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)



L Series, Metric, Female Thread

0291	OD mm	Thread
EVL-6L	6	M12 x 1.5
EVL-8L	8	M14 x 1.5
EVL-10L	10	M16 x 1.5
EVL-12L	12	M18 x 1.5
EVL-15L	15	M22 x 1.5
EVL-18L	18	M26 x 1.5
EVL-22L	22	M30 x 2
EVL-28L	28	M36 x 2
EVL-35L	35	M45 x 2
EVL-42L	42	M52 x 2
Tech Sheet 10597		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVL-6S	6	M14 x 1.5
EVL-8S	8	M16 x 1.5
EVL-10S	10	M18 x 1.5
EVL-12S	12	M20 x 1.5
EVL-14S	14	M22 x 1.5
EVL-16S	16	M24 x 1.5
EVL-20S	20	M30 x 2
EVL-25S	25	M36 x 2
EVL-30S	30	M42 x 2
EVL-38S	38	M52 x 2
Tech Sheet 10597		

stainless steel



For **Stainless Steel Tubing** see page **1287**

Male Stud Elbows

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)



L Series, BSPT

0291	OD mm	Thread
WE6L-2RT	6	1/8"
WE6L-4RT	6	1/4"
WE6L-6RT	6	3/8"
WE6L-8RT	6	1/2"
WE8L-2RT	8	1/8"
WE8L-4RT	8	1/4"
WE8L-6RT	8	3/8"
WE8L-8RT	8	1/2"
WE10L-2RT	10	1/8"
WE10L-4RT	10	1/4"
WE10L-6RT	10	3/8"
WE10L-8RT	10	1/2"
WE12L-2RT	12	1/8"
WE12L-4RT	12	1/4"
WE12L-6RT	12	3/8"
WE12L-8RT	12	1/2"
WE15L-4RT	15	1/4"
WE15L-6RT	15	3/8"
WE15L-8RT	15	1/2"
WE15L-12RT	15	3/4"
WE18L-6RT	18	3/8"
WE18L-8RT	18	1/2"
WE18L-12RT	18	3/4"
WE22L-8RT	22	1/2"
WE22L-12RT	22	3/4"
WE28L-16RT	28	1"
WE35L-20RT	35	1.1/4"
Tech Sheet 10600		

S Series, BSPT

0291	OD mm	Thread
WE6S-2RT	6	1/8"
WE6S-4RT	6	1/4"
WE6S-6RT	6	3/8"
WE6S-8RT	6	1/2"
WE8S-4RT	8	1/4"
WE8S-6RT	8	3/8"
WE8S-8RT	8	1/2"
WE10S-4RT	10	1/4"
WE10S-6RT	10	3/8"
WE10S-8RT	10	1/2"
WE12S-4RT	12	1/4"
WE12S-6RT	12	3/8"
WE12S-8RT	12	1/2"
WE14S-6RT	14	3/8"
WE14S-8RT	14	1/2"
WE16S-6RT	16	3/8"
WE16S-8RT	16	1/2"
WE16S-12RT	16	3/4"
WE20S-8RT	20	1/2"
WE20S-12RT	20	3/4"
Tech Sheet 10600		

L Series, NPT

0291	OD mm	Thread
WE6L-2N	6	1/8"
WE6L-4N	6	1/4"
WE6L-6N	6	3/8"
WE6L-8N	6	1/2"
WE8L-2N	8	1/8"
WE8L-4N	8	1/4"
WE8L-6N	8	3/8"
WE8L-8N	8	1/2"
WE10L-2N	10	1/8"
WE10L-4N	10	1/4"
WE10L-8N	10	1/2"
WE12L-4N	12	1/4"
WE12L-6N	12	3/8"
WE12L-8N	12	1/2"
WE15L-6N	15	3/8"
WE15L-8N	15	1/2"
WE15L-12N	15	3/4"
WE18L-6N	18	3/8"
WE18L-8N	18	1/2"
WE18L-12N	18	3/4"
WE22L-8N	22	1/2"
WE22L-12N	22	3/4"
WE28L-12N	28	3/4"
WE28L-16N	28	1"
WE35L-20N	35	1.1/4"
WE42L-24N	42	1.1/2"
Tech Sheet 10601		

S Series, NPT

0291	OD mm	Thread
WE6S-4N	6	1/4"
WE6S-6N	6	3/8"
WE6S-8N	6	1/2"
WE8S-4N	8	1/4"
WE8S-6N	8	3/8"
WE8S-8N	8	1/2"
WE10S-4N	8	1/4"
WE10S-6N	10	3/8"
WE10S-8N	10	1/2"
WE12S-4N	12	1/4"
WE12S-6N	12	3/8"
WE12S-8N	12	1/2"
WE14S-6N	14	3/8"
WE14S-8N	14	1/2"
WE16S-6N	16	3/8"
WE16S-8N	16	1/2"
WE16S-12N	16	3/4"
WE20S-8N	20	1/2"
WE20S-12N	20	3/4"
WE25S-16N	25	1"
WE30S-20N	30	1.1/4"
WE38S-24N	38	1.1/2"
Tech Sheet 10601		

Fluid-Air Components Ltd



For Stainless Steel 304 & 316

see section **10** page **1225**

Many of our products are produced in stainless steel (304 or 316) so if that is your focus and to simplify product selection, we have all our products regardless of type or application grouped in section 10 (coded yellow) **of our catalogue.**



Food safety starts with rigorous hygiene and nickel-containing stainless steels are the superior, reliable standard at every link of the food and industry supply chain. Though it may not be inherently antimicrobial, stainless steel, particularly 304 or 316 stainless steels, are one of the best materials to use in a food and beverage processing environment.

Industries

- Food
- Brewing
- Transport
- Pharmaceuticals
- Chemicals

Stainless steel is commonly used in the food industry because of its non-toxicity and ease of cleaning. This material does not react chemically with other substances and can be cleaned with high temperatures. In the process of disinfection, we can also use most of the available detergents. Stainless steel is not absorbent and after rinsing its surface with water, you can freely use it for food processing. This material is extremely durable and does not require regular and expensive maintenance. Although stainless steel can be slightly more expensive than other raw materials, it is an excellent compromise between the interests of the consumer and manufacturer.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Adjustable Elbows



L Series, Metric, Female Thread

0291	OD mm	Thread
EVW-6L	6	M12 x 1.5
EVW-8L	8	M14 x 1.5
EVW-10L	10	M16 x 1.5
EVW-12L	12	M18 x 1.5
EVW-15L	15	M22 x 1.5
EVW-18L	18	M26 x 1.5
EVW-22L	22	M30 x 2
EVW-28L	28	M36 x 2
EVW-35L	35	M45 x 2
EVW-42L	42	M52 x 2
Tech Sheet 10602		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVW-6S	6	M14 x 1.5
EVW-8S	8	M16 x 1.5
EVW-10S	10	M18 x 1.5
EVW-12S	12	M20 x 1.5
EVW-14S	14	M22 x 1.5
EVW-16S	16	M24 x 1.5
EVW-20S	20	M30 x 2
EVW-25S	25	M36 x 2
EVW-30S	30	M42 x 2
EVW-38S	38	M52 x 2
Tech Sheet 10602		

Straights



L Series

0291	OD mm
G6-UL	6
G8-UL	8
G10-UL	10
G12-UL	12
G15-UL	15
G18-UL	18
G22-UL	22
G28-UL	28
G35-UL	35
G42-UL	42
Tech Sheet 10605	

S Series

0291	OD mm
G6-US	6
G8-US	8
G10-US	10
G12-US	12
G14-US	14
G16-US	16
G20-US	20
G25-US	25
G30-US	30
G38-US	38
Tech Sheet 10605	

Straight Reducers



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series

0291	OD mm	OD mm
GR-8L-6L	8	6
GR-10L-6L	10	6
GR-10L-8L	10	8
GR-12L-6L	12	6
GR-12L-8L	12	8
GR-12L-10L	12	10
GR-15L-6L	15	6
GR-15L-8L	15	8
GR-15L-10L	15	10
GR-15L-12L	15	12
GR-18L-8L	18	8
GR-18L-10L	18	10
GR-18L-12L	18	12
GR-18L-15L	18	15
GR-22L-8L	22	8
GR-22L-10L	22	10
GR-22L-12L	22	12
GR-22L-15L	22	15
GR-22L-18L	22	18
GR-28L-10L	28	10
GR-28L-12L	28	12
GR-28L-15L	28	15
GR-28L-18L	28	18
GR-28L-22L	28	22
GR-35L-15L	35	15
GR-35L-18L	35	18
GR-35L-22L	35	22
GR-35L-28L	35	28
GR-42L-15L	42	15
GR-42L-18L	42	18
GR-42L-22L	42	22
GR-42L-28L	42	28
GR-42L-35L	42	35
Tech Sheet 10606		

S Series

0291	OD mm	OD mm
GR-8S-6S	8	6
GR-10S-6S	10	6
GR-10S-8S	10	8
GR-12S-6S	12	6
GR-12S-8S	12	8
GR-12S-10S	12	10
GR-14S-6S	14	6
GR-14S-8S	14	8
GR-14S-10S	14	10
GR-14S-12S	14	12
GR-16S-6S	16	6
GR-16S-8S	16	8
GR-16S-10S	16	10
GR-16S-12S	16	12
GR-16S-14S	16	14
GR-20S-6S	20	6
GR-20S-8S	20	8
GR-20S-10S	20	10
GR-20S-12S	20	12
GR-20S-14S	20	14
GR-20S-16S	20	16
GR-25S-8S	25	8
GR-25S-10S	25	10
GR-25S-12S	25	12
GR-25S-14S	25	14
GR-25S-16S	25	16
GR-25S-20S	25	20
GR-30S-10S	30	10
GR-30S-12S	30	12
GR-30S-14S	30	14
GR-30S-16S	30	16
GR-30S-20S	30	20
GR-30S-25S	30	25
GR-38S-10S	38	10
GR-38S-12S	38	12
GR-38S-14S	38	14
GR-38S-16S	38	16
GR-38S-20S	38	20
GR-38S-25S	38	25
GR-38S-30S	38	30
Tech Sheet 10606		

stainless steel



For **Stainless Steel Check Valves** see page **1300**

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

90° Compact Adjustable Elbows

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Temperature Range:
-20°C to +200°C (FPM/Viton)



L Series, Metric, BSPP Male Thread with Viton O-Ring

0291	OD mm	Thread
WEEV-06L-1/8	6	1/8"
WEEV-08L-1/4	8	1/4"
WEEV-10L-1/4	10	1/4"
WEEV-12L-3/8	12	3/8"
WEEV-15L-1/2	15	1/2"
WEEV-18L-1/2	18	1/2"
WEEV-22L-3/4	22	3/4"
WEEV-28L-1	28	1"
WEEV-35L-114	35	1.1/4"
Tech Sheet 67962		

45° Adjustable Elbows



L Series, Metric, BSPP Female Thread with Viton O-Ring

0291	OD mm	Thread
EV-DKOL-06	6	M12 x 1.5
EV-DKOL-08	8	M14 x 1.5
EV-DKOL-10	10	M16 x 1.5
EV-DKOL-12	12	M18 x 1.5
EV-DKOL-15	15	M22 x 1.5
EV-DKOL-18	18	M26 x 1.5
EV-DKOL-22	22	M30 x 2
EV-DKOL-28	28	M36 x 2
EV-DKOL-35	35	M45 x 2
EV-DKOL-42	42	M52 x 2
Tech Sheet 67963		

Soft Sealed Cutting Ring



L Series Sealing Ring with Viton Seal

0291	OD mm
ES4-L-06-WD	6
ES4-L-08-WD	8
ES4-L-10-WD	10
ES4-L-12-WD	12
ES4-L-15-WD	15
ES4-L-18-WD	18
ES4-L-22-WD	22
ES4-L-28-WD	28
ES4-L-35-WD	35
ES4-L-42-WD	42
Tech Sheet 67964	

S Series Sealing Ring with Viton Seal

0291	OD mm
ES4-S-06-WD	6
ES4-S-08-WD	8
ES4-S-10-WD	10
ES4-S-12-WD	12
ES4-S-14-WD	14
ES4-S-16-WD	16
ES4-S-20-WD	20
ES4-S-25-WD	25
ES4-S-30-WD	30
ES4-S-38-WD	38
Tech Sheet 67964	

stainless steel



For **Stainless Steel Tubing** see page **183**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Equal Elbows



L Series

0291	OD mm
W6-UEL	6
W8-UEL	8
W10-UEL	10
W12-UEL	12
W15-UEL	15
W18-UEL	18
W22-UEL	22
W28-UEL	28
W35-UEL	35
W42-UEL	42
Tech Sheet 10607	

S Series

0291	OD mm
W6-UES	6
W8-UES	8
W10-UES	10
W12-UES	12
W14-UES	14
W16-UES	16
W20-UES	20
W25-UES	25
W30-UES	30
W38-UES	38
Tech Sheet 10607	

Equal Tees



L Series

0291	OD mm
T6-UTL	6
T8-UTL	8
T10-UTL	10
T12-UTL	12
T15-UTL	15
T18-UTL	18
T22-UTL	22
T28-UTL	28
T35-UTL	35
T42-UTL	42
Tech Sheet 10608	

S Series

0291	OD mm
T6-UTS	6
T8-UTS	8
T10-UTS	10
T12-UTS	12
T14-UTS	14
T16-UTS	16
T20-UTS	20
T25-UTS	25
T30-UTS	30
T38-UTS	38
Tech Sheet 10608	

Equal Crosses



L Series

0291	OD mm
K6-UCL	6
K8-UCL	8
K10-UCL	10
K12-UCL	12
K15-UCL	15
K18-UCL	18
K22-UCL	22
K28-UCL	28
K35-UCL	35
K42-UCL	42
Tech Sheet 10609	

S Series

0291	OD mm
K6-UCS	6
K8-UCS	8
K10-UCS	10
K12-UCS	12
K14-UCS	14
K16-UCS	16
K20-UCS	20
K25-UCS	25
K30-UCS	30
K38-UCS	38
Tech Sheet 10609	

stainless steel



For **Stainless Steel Gauges**
see pages **414-415**

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Reducing Standpipes

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature:
-20°C to +200°C (FPM/Viton)



L Series

0291	OD mm	OD mm
KOR-8L-6L	8	6
KOR-10L-6L	10	6
KOR-10L-8L	10	8
KOR-12L-6L	12	6
KOR-12L-8L	12	8
KOR-12L-10L	12	10
KOR-15L-6L	15	6
KOR-15L-8L	15	8
KOR-15L-10L	15	10
KOR-15L-12L	15	12
KOR-18L-6L	18	6
KOR-18L-8L	18	8
KOR-18L-10L	18	10
KOR-18L-12L	18	12
KOR-18L-15L	18	15
KOR-22L-6L	22	6
KOR-22L-8L	22	8
KOR-22L-10L	22	10
KOR-22L-12L	22	12
KOR-22L-15L	22	15
KOR-22L-18L	22	18
KOR-28L-6L	28	6
KOR-28L-8L	28	8

0291	OD mm	OD mm
KOR-28L-10L	28	10
KOR-28L-12L	28	12
KOR-28L-15L	28	15
KOR-28L-18L	28	18
KOR-28L-22L	28	22
KOR-35L-6L	35	6
KOR-35L-8L	35	8
KOR-35L-10L	35	10
KOR-35L-12L	35	12
KOR-35L-15L	35	15
KOR-35L-18L	35	18
KOR-35L-22L	35	22
KOR-35L-28L	35	28
KOR-42L-10L	42	10
KOR-42L-12L	42	12
KOR-42L-15L	42	15
KOR-42L-18L	42	18
KOR-42L-22L	42	22
KOR-42L-28L	42	28
KOR-42L-35L	42	35

Tech Sheet 10610

S Series

0291	OD mm	OD mm
KOR-8S-6S	8	6
KOR-10S-6S	10	6
KOR-10S-8S	10	8
KOR-12S-6S	12	6
KOR-12S-8S	12	8
KOR-12S-10S	12	10
KOR-14S-6S	14	6
KOR-14S-8S	14	8
KOR-14S-10S	14	10
KOR-14S-12S	14	12
KOR-16S-6S	16	6
KOR-16S-8S	16	8
KOR-16S-10S	16	10
KOR-16S-12S	16	12
KOR-16S-14S	16	14
KOR-20S-6S	20	6
KOR-20S-8S	20	8
KOR-20S-10S	20	10
KOR-20S-12S	20	12
KOR-20S-14S	20	14
KOR-20S-16S	20	16
KOR-25S-6S	25	6
KOR-25S-8S	25	8

0291	OD mm	OD mm
KOR-25S-10S	25	10
KOR-25S-12S	25	12
KOR-25S-14S	25	14
KOR-25S-16S	25	16
KOR-25S-20S	25	20
KOR-30S-6S	30	6
KOR-30S-8S	30	8
KOR-30S-10S	30	10
KOR-30S-12S	30	12
KOR-30S-14S	30	14
KOR-30S-16S	30	16
KOR-30S-20S	30	20
KOR-30S-25S	30	25
KOR-38S-6S	38	6
KOR-38S-8S	38	8
KOR-38S-10S	38	10
KOR-38S-12S	38	12
KOR-38S-14S	38	14
KOR-38S-16S	38	16
KOR-38S-20S	38	20
KOR-38S-25S	38	25
KOR-38S-30S	38	30

Tech Sheet 10610

stainless steel




For **Stainless Steel Tube**
see page **183**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Tee Reducers



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

L Series

0291	OD A mm	OD B mm	OD C mm
TR-6-8-6L	6	8	6
TR-6-10-6L	6	10	6
TR-8-6-8L	8	6	8
TR-8-10-8L	8	10	8
TR-8-12-8L	8	12	8
TR-10-6-10L	10	6	10
TR-10-8-10L	10	8	10
TR-10-10-6L	10	10	6
TR-10-12-10L	10	12	10
TR-10-15-10L	10	15	10
TR-12-6-12L	12	6	12
TR-12-8-8L	12	8	8
TR-12-8-12L	12	8	12
TR-12-10-10L	12	10	10
TR-12-10-12L	12	10	12
TR-12-12-10L	12	12	10
TR-12-15-12L	12	15	12
TR-12-18-12L	12	18	12
TR-15-6-15L	15	6	15
TR-15-10-15L	15	10	15
TR-15-12-12L	15	12	12
TR-15-12-15L	15	12	15
TR-15-15-12L	15	15	12
TR-18-10-10L	18	10	10
TR-18-10-18L	18	10	18
TR-18-12-18L	18	12	18
TR-18-15-18L	18	15	18
TR-18-18-10L	18	18	10
TR-22-10-22L	22	10	22
TR-22-12-22L	22	12	22
TR-22-15-15L	22	15	15
TR-22-15-22L	22	15	22
TR-22-18-18L	22	18	18
TR-22-18-22L	22	18	22
TR-22-22-18L	22	22	18
TR-28-10-28L	28	10	28
TR-28-12-28L	28	12	28
TR-28-15-28L	28	15	28
TR-28-18-28L	28	18	28
TR-28-22-22L	28	22	22
TR-28-22-28L	28	22	28
TR-28-35-28L	28	35	28
TR-35-12-35L	35	12	35
TR-35-15-35L	35	15	35
TR-35-18-35L	35	18	35
TR-35-22-35L	35	22	35
TR-35-28-35L	35	28	35
TR-35-42-35L	35	42	35
TR-42-15-42L	42	15	42
TR-42-18-42L	42	18	42
TR-42-22-42L	42	22	42
TR-42-28-42L	42	28	42
TR-42-35-42L	42	35	42


Tech Sheet 10611

S Series

0291	OD A mm	OD B mm	OD C mm
TR-8-6-8S	8	6	8
TR-10-6-10S	10	6	10
TR-10-8-10S	10	8	10
TR-12-6-12S	12	6	12
TR-12-8-8S	12	8	8
TR-12-8-12S	12	8	12
TR-12-10-12S	12	10	12
TR-12-16-12S	12	16	12
TR-14-8-14S	14	8	14
TR-14-10-14S	14	10	14
TR-16-6-16S	16	6	16
TR-16-8-16S	16	8	16
TR-16-10-16S	16	10	16
TR-16-12-16S	16	12	16
TR-16-14-16S	16	14	16
TR-16-20-16S	16	20	16
TR-20-8-20S	20	08	20
TR-20-10-20S	20	10	20
TR-20-12-20S	20	12	20
TR-20-14-20S	20	14	20
TR-20-16-20S	20	16	20
TR-20-25-20S	20	25	20
TR-25-10-25S	25	10	25
TR-25-12-25S	25	12	25
TR-25-14-25S	25	14	25
TR-25-16-25S	25	16	25
TR-25-20-25S	25	20	25
TR-25-30-25S	25	30	25
TR-30-12-30S	30	12	30
TR-30-16-30S	30	16	30
TR-30-20-30S	30	20	30
TR-30-25-30S	30	25	30
TR-30-38-30S	30	38	30
TR-38-16-38S	38	16	38
TR-38-20-38S	38	20	38
TR-38-25-38S	38	25	38
TR-38-30-38S	38	30	38

Tech Sheet 10611

Straight Bulkheads



L Series

0291	OD mm
SV-6L	6
SV-8L	8
SV-10L	10
SV-12L	12
SV-15L	15
SV-18L	18
SV-22L	22
SV-28L	28
SV-35L	35
SV-42L	42


Tech Sheet 10612

S Series

0291	OD mm
SV-6S	6
SV-8S	8
SV-10S	10
SV-12S	12
SV-14S	14
SV-16S	16
SV-20S	20
SV-25S	25
SV-30S	30
SV-38S	38

Tech Sheet 10612

Weld Bulkheads



L Series

0291	OD mm
ESV-6L-FT	6
ESV-8L-FT	8
ESV-10L-FT	10
ESV-12L-FT	12
ESV-15L-FT	15
ESV-18L-FT	18
ESV-20L-FT	20
ESV-28L-FT	28

Tech Sheet 10613

S Series

0291	OD mm
ESV-6S-FT	6
ESV-8S-FT	8
ESV-10S-FT	10
ESV-12S-FT	12
ESV-14S-FT	14
ESV-16S-FT	16
ESV-20S-FT	20
ESV-25S-FT	25

Tech Sheet 10613

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Bulkhead Elbows



L Series

0291	OD mm
WSV-6L-FT	6
WSV-8L-FT	8
WSV-10L-FT	10
WSV-12L-FT	12
WSV-15L-FT	15
WSV-18L-FT	18
WSV-22L-FT	22
WSV-28L-FT	28
WSV-35L-FT	35
WSV-42L-FT	42
Tech Sheet 10614	

S Series

0291	OD mm
WSV-6S-FT	6
WSV-8S-FT	8
WSV-10S-FT	10
WSV-12S-FT	12
WSV-14S-FT	14
WSV-16S-FT	16
WSV-20S-FT	20
WSV-25S-FT	25
WSV-30S-FT	30
WSV-38S-FT	38
Tech Sheet 10614	

Weld Nipples



O-Ring Sealing, Nitrile

0291	OD mm	Diameter mm
SKA-108	10	8
SKA-107	10	7
SKA-106	10	6
SKA-129	12	9
SKA-128	12	8
SKA-127	12	7
SKA-1613	16	13
SKA-1612	16	12
SKA-1611	16	11
SKA-1610	16	10
SKA-2016	20	16
SKA-2015	20	15
SKA-2014	20	14
SKA-2012	20	12
SKA-2519	25	19
SKA-2517	25	17
SKA-2515	25	15
Tech Sheet 10615		

Butt Weld Fittings



L Series

0291	OD mm
AS-6L	6
AS-8L	8
AS-10L	10
AS-12L	12
AS-15L	15
AS-18L	18
AS-22L	22
AS-28L	28
Tech Sheet 10616	

S Series

0291	OD mm
AS-6S	6
AS-8S	8
AS-10S	10
AS-12S	12
AS-14S	14
AS-16S	16
AS-20S	20
AS-25S	25
Tech Sheet 10616	



Weld Standpipe

0291	OD mm	Diameter mm
ASK-108	10	8
ASK-107	10	7
ASK-106	10	6
ASK-129	12	9
ASK-128	12	8
ASK-127	12	7
ASK-1612	16	12
ASK-1611	16	11
ASK-1610	16	10
ASK-2016	20	16
ASK-2015	20	15
ASK-2014	20	14
ASK-2012	20	12
ASK-2519	25	19
ASK-2517	25	17
ASK-2515	25	15
Tech Sheet 10617		

Special Weld Nipples (Reducers)



O-Ring Sealing, Nitrile

0291	OD mm	Diameter mm
SKAR-10-6	10	6
SKAR-10-8	10	8
SKAR-12-8	12	8
SKAR-12-10	12	10
SKAR-16-12	16	12
SKAR-20-12	20	12
SKAR-20-16	20	16
SKAR-25-16	25	16
SKAR-25-20	25	20
SKAR-25-15	25	15
Tech Sheet 10618		

Metric Standpipe Adaptors, BSPP



L Series

0291	Thread	OD mm
2101-8247	1/8"	6
2101-8254	1/4"	8
2101-8262	1/4"	10
2101-8270	3/8"	12
2101-8288	1/2"	15
2101-8296	1/2"	18
2101-8304	3/4"	22
2101-8312	1"	28
2101-8445	1.1/4"	35
2101-8338	1.1/2"	42
Tech Sheet 20799		

S Series

0291	Thread	OD mm
2101-8346	1/4"	6
2101-8353	1/4"	8
2101-8361	3/8"	10
2101-8379	3/8"	12
2101-8387	1/2"	14
2101-8395	1/2"	16
2101-8403	3/4"	20
2101-8411	1"	25
2101-8429	1.1/4"	30
2101-8437	1.1/2"	38
Tech Sheet 20799		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Banjo Elbows



L Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
WHV-6L-2RG	6	1/8"
WHV-8L-4RG	8	1/4"
WHV-10L-4RG	10	1/4"
WHV-10L-6G	10	3/8"
WHV-12L-4RG	12	1/4"
WHV-12L-6RG	12	3/8"
WHV-12L-8RG	12	1/2"
WHV-15L-8RG	15	1/2"
WHV-18L-8RG	18	1/2"
WHV-22L-12RG	22	3/4"
WHV-28L-16RG	28	1"
WHV-35L-20RG	35	1.1/4"
WHV-42L-24RG	42	1.1/2"
Tech Sheet 20736		

S Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
WHV-6S-4RG	6	1/4"
WHV-8S-4RG	8	1/4"
WHV-10S-4RG	10	1/4"
WHV-10S-6G	10	3/8"
WHV-12S-6RG	12	3/8"
WHV-14S-8RG	14	1/2"
WHV-16S-8RG	16	1/2"
WHV-20S-12RG	20	3/4"
WHV-25S-16RG	25	1"
WHV-30S-20RG	30	1.1/4"
WHV-38S-24RG	38	1.1/2"
Tech Sheet 20736		

Gauge Couplings



L Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
MV-6L-4RG	6	1/4"
MV-6L-8RG	6	1/2"
MV-8L-4RG	8	1/4"
MV-8L-8RG	8	1/2"
MV-10L-4RG	10	1/4"
MV-10L-8RG	10	1/2"
MV-12L-4RG	12	1/4"
MV-12L-8RG	12	1/2"
Tech Sheet 20737		



S Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
MV-6S-8RG	6	1/2"
MV-8S-4RG	8	1/4"
MV-8S-8RG	8	1/2"
MV-10S-4RG	10	1/4"
MV-10S-8RG	10	1/2"
MV-12S-4RG	12	1/4"
MV-12S-8RG	12	1/2"
Tech Sheet 20737		



L Series, NPT

0291	OD mm	Thread
MV-6L-4N	6	1/4"
MV-6L-8N	6	1/2"
MV-8L-4N	8	1/4"
MV-8L-8N	8	1/2"
MV-10L-4N	10	1/4"
MV-10L-8N	10	1/2"
MV-12L-4N	12	1/4"
MV-12L-8N	12	1/2"
Tech Sheet 20901		



S Series, NPT

0291	OD mm	Thread
MV-6S-8N	6	1/2"
MV-8S-8N	8	1/2"
MV-10S-8N	10	1/2"
MV-12S-8N	12	1/2"
Tech Sheet 20901		

For **Hydraulic Tube Clamps** see pages **184-200**



Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Non-return Valves

All valves supplied with 1 bar cracking pressure unless stated, other pressures available on request are 0.2, 0.5, 2.0 and 3.0

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

L Series, BSPP, Flow Towards Thread



0291	OD mm	Thread
RZ-6L-2RG	6	1/8"
RZ-8L-4RG	8	1/4"
RZ-10L-4RG	10	1/4"
RZ-12L-6RG	12	3/8"
RZ-15L-8RG	15	1/2"
RZ-18L-8RG	18	1/2"
RZ-22L-12RG	22	3/4"
RZ-28L-16RG	28	1"
RZ-35L-20RG	35	1.1/4"
RZ-42L-24RG	42	1.1/2"
Tech Sheet 20352		

S Series, BSPP, Flow Towards Thread

0291	OD mm	Thread
RZ-6S-2RG	6	1/8"
RZ-8S-4RG	8	1/4"
RZ-10S-4RG	10	1/4"
RZ-12S-6RG	12	3/8"
RZ-14S-8RG	14	1/2"
RZ-16S-8RG	16	1/2"
RZ-20S-12RG	20	3/4"
RZ-25S-16RG	25	1"
RZ-30S-20RG	30	1.1/4"
RZ-38S-24RG	38	1.1/2"

L Series, BSPP, Flow Away From Thread



0291	OD mm	Thread
RV-6L-2RG	6	1/8"
RV-8L-4RG	8	1/4"
RV-10L-4RG	10	1/4"
RV-12L-6RG	12	3/8"
RV-15L-8RG	15	1/2"
RV-18L-8RG	18	1/2"
RV-22L-12RG	22	3/4"
RV-28L-16RG	28	1"
RV-35L-20RG	35	1.1/4"
RV-42L-24RG	42	1.1/2"
Tech Sheet 20352		

S Series, BSPP, Flow Away From Thread

0291	OD mm	Thread
RV-6S-2RG	6	1/8"
RV-8S-4RG	8	1/4"
RV-10S-4RG	10	1/4"
RV-12S-6RG	12	3/8"
RV-14S-8RG	14	1/2"
RV-16S-8RG	16	1/2"
RV-20S-12RG	20	3/4"
RV-25S-16RG	25	1"
RV-30S-20RG	30	1.1/4"
RV-38S-24RG	38	1.1/2"

L Series, Tube x Tube



0291	OD mm	Cracking Pressure Bar
770-0606	6	0.5
770-0808	8	0.5
770-1010	10	0.5
770-1212	12	0.5
770-1515	15	0.5
770-1818	18	0.5
770-2222	22	0.5
770-2828	28	0.5
770-3535	35	0.5
770-4242	42	0.5
Tech Sheet 10619		

S Series, Tube x Tube

0291	OD mm
RD-6S	6
RD-8S	8
RD-10S	10
RD-12S	12
RD-14S	14
RD-16S	16
RD-20S	20
RD-25S	25
RD-30S	30
RD-38S	38
Tech Sheet 10619	

Blanking Plugs, Threaded



BSPP

0291	Thread
VSTI-2EO	1/8"
VSTI-4EO	1/4"
VSTI-6EO	3/8"
VSTI-8EO	1/2"
VSTI-12EO	3/4"
VSTI-16EO	1"
VSTI-20EO	1.1/4"
VSTI-24EO	1.1/2"
Tech Sheet 10620	

Metric

0291	Thread
VSTI-10M	M10 x 1
VSTI-12M	M12 x 1.5
VSTI-14M	M14 x 1.5
VSTI-16M	M16 x 1.5
VSTI-18M	M18 x 1.5
VSTI-20M	M20 x 1.5
VSTI-22M	M22 x 1.5
VSTI-26M	M26 x 1.5
VSTI-27M	M27 x 2
VSTI-33M	M33 x 2
VSTI-42M	M42 x 2
VSTI-48M	M48 x 2
Tech Sheet 10620	

Blanking Plugs



L Series

0291	OD mm
VKA-6L	6
VKA-8L	8
VKA-10L	10
VKA-12L	12
VKA-15L	15
VKA-18L	18
VKA-22L	22
VKA-28L	28
VKA-35L	35
VKA-42L	42
Tech Sheet 10621	

S Series

0291	OD mm
VKA-6S	6
VKA-8S	8
VKA-10S	10
VKA-12S	12
VKA-14S	14
VKA-16S	16
VKA-20S	20
VKA-25S	25
VKA-30S	30
VKA-38S	38
Tech Sheet 10621	

Blanking Ends



L Series

0291	OD mm
ROV-6L	6
ROV-8L	8
ROV-10L	10
ROV-12L	12
ROV-15L	15
ROV-18L	18
ROV-22L	22
ROV-28L	28
ROV-35L	35
ROV-42L	42
Tech Sheet 10622	

S Series

0291	OD mm
ROV-6S	6
ROV-8S	8
ROV-10S	10
ROV-12S	12
ROV-14S	14
ROV-16S	16
ROV-20S	20
ROV-25S	25
ROV-30S	30
ROV-38S	38
Tech Sheet 10622	

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Nut



L Series

0291	OD mm
M-6L-FT	6
M-8L-FT	8
M-10L-FT	10
M-12L-FT	12
M-15L-FT	15
M-18L-FT	18
M-22L-FT	22
M-28L-FT	28
M-35L-FT	35
M-42L-FT	42
Tech Sheet 10623	

S Series

0291	OD mm
M-6S-FT	6
M-8S-FT	8
M-10S-FT	10
M-12S-FT	12
M-14S-FT	14
M-16S-FT	16
M-20S-FT	20
M-25S-FT	25
M-30S-FT	30
M-38S-FT	38
Tech Sheet 10623	

Compression Ring

- Hardened, nickel plated.



L Series

0291	OD mm
DPR-6L	6
DPR-8L	8
DPR-10L	10
DPR-12L	12
DPR-15L	15
DPR-18L	18
DPR-22L	22
DPR-28L	28
DPR-35L	35
DPR-42L	42
Tech Sheet 10624	

S Series

0291	OD mm
DPR-6S	6
DPR-8S	8
DPR-10S	10
DPR-12S	12
DPR-14S	14
DPR-16S	16
DPR-20S	20
DPR-25S	25
DPR-30S	30
DPR-38S	38
Tech Sheet 10624	

Seals



Banjo Couplings

0291	Thread
DKR-2RG	1/8"
DKR-4RG	1/4"
DKR-6RG	3/8"
DKR-8RG	1/2"
DKR-12RG	3/4"
DKR-16RG	1"
DKR-20RG	1.1/4"
DKR-24RG	1.1/2"



Gauge Couplings

0291	Thread
DKRI-4RG	1/4"
DKRI-8RG	1/2"



Viton

0291	Thread
WD-10X1	M10 x 1 (1/8")
WD-12X1.5	M12 x 1.5
WD-14X1.5	M14 x 1.5 (1/4")
WD-16X1.5	M16 x 1.5
WD-3/8	3/8"
WD-18X1.5	M18 x 1.5
WD-20X1.5	M20 x 1.5
WD-1/2	1/2"
WD-26X1.5	M26 x 1.5 (3/4")
WD-22X1.5	M22 x 1.5
WD-27X2	M27 x 2 (3/4")
WD-33X2	M33 x 2 (1")
WD-42X2	M42 x 2 (1.1/4")
WD-48X2	M48 x 2 (1.1/2")

For **Hose & Pipe Cleaning Kits** see page **49**



Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Technical details of ISO 8434-1 24° Fittings
Cone sealing couplings with 24° Cone and O-ring - FPM

There are several advantages to using DKO couplings:
- They are simple to assemble with low torque requirements.
- There is a wide variety of couplings to choose from.
- They are also easy to combine with each other.
- Additionally, DKO couplings have a super low leakage rate thanks to the O-ring sealing.

Straight Swivel Unions - DKO



L Series

0291	OD mm	Thread
GV-DKOL-06	6	M12 x 1.5
GV-DKOL-08	8	M 4 x 1.5
GV-DKOL-10	10	M16 x 1.5
GV-DKOL-12	12	M18 x 1.5
GV-DKOL-15	15	M22 x 1.5
GV-DKOL-18	18	M26 x 1.5
GV-DKOL-22	22	M30 x 2
GV-DKOL-28	28	M36 x 2
GV-DKOL-35	35	M45 x 2
GV-DKOL-42	42	M52 x 2
Tech Sheet 71713		

S Series

0291	OD mm	Thread
GV-DKOS-06	6	M14 x 1.5
GV-DKOS-08	8	M16 x 1.5
GV-DKOS-10	10	M18 x 1.5
GV-DKOS-12	12	M20 x 1.5
GV-DKOS-14	14	M22 x 1.5
GV-DKOS-16	16	M24 x 1.5
GV-DKOS-20	20	M30 x 2
GV-DKOS-25	25	M36 x 2
GV-DKOS-30	30	M42 x 2
GV-DKOS-38	38	M52 x 2
Tech Sheet 71713		

Straight Swivel Reducers - DKO



L/L Series

0291	OD mm	OD mm
GVR-DKO-08L/06L	8	6
GVR-DKO-10L/06L	10	6
GVR-DKO-10L/08L	10	8
GVR-DKO-12L/06L	12	6
GVR-DKO-12L/08L	12	8
GVR-DKO-12L/10L	12	10
GVR-DKO-15L/08L	15	8
GVR-DKO-15L/10L	15	10
GVR-DKO-15L/12L	15	12
GVR-DKO-18L/10L	18	10
GVR-DKO-18L/12L	18	12
GVR-DKO-18L/15L	18	15
GVR-DKO-22L/12L	22	12
GVR-DKO-22L/15L	22	15
GVR-DKO-22L/18L	22	18
GVR-DKO-28L/15L	28	15
GVR-DKO-28L/18L	28	18
GVR-DKO-28L/22L	28	22
GVR-DKO-35L/18L	35	18
GVR-DKO-35L/22L	35	22
GVR-DKO-35L/28L	35	28
GVR-DKO-42L/22L	42	22
GVR-DKO-42L/28L	42	28
GVR-DKO-42L/35L	42	35
Tech Sheet 71714		

S/S Series

0291	OD mm	OD mm
GVR-DKO-08S/06S	8	6
GVR-DKO-10S/06S	10	6
GVR-DKO-10S/08S	10	8
GVR-DKO-12S/06S	12	6
GVR-DKO-12S/08S	12	8
GVR-DKO-12S/10S	12	10
GVR-DKO-16S/10S	16	10
GVR-DKO-16S/12S	16	12
GVR-DKO-16S/14S	16	14
GVR-DKO-20S/12S	20	12
GVR-DKO-20S/14S	20	14
GVR-DKO-20S/16S	20	16
GVR-DKO-25S/16S	25	16
GVR-DKO-25S/20S	25	20
GVR-DKO-30S/16S	30	16
GVR-DKO-30S/20S	30	20
GVR-DKO-30S/25S	30	25
GVR-DKO-38S/20S	38	20
GVR-DKO-38S/25S	38	25
GVR-DKO-38S/30S	38	30
Tech Sheet 71714		

L/S Series

0291	OD mm	OD mm
GVR-DKO-06L/06S	6	6
GVR-DKO-08L/06S	8	6
GVR-DKO-08L/08S	8	8
GVR-DKO-10L/10S	10	10
GVR-DKO-12L/10S	12	10
GVR-DKO-12L/12S	12	12
GVR-DKO-15L/12S	15	12
GVR-DKO-15L/14S	15	14
GVR-DKO-18L/16S	18	16
GVR-DKO-22L/20S	22	20
GVR-DKO-28L/25S	28	25
GVR-DKO-35L/30S	35	30
GVR-DKO-42L/38S	42	38
Tech Sheet 71715		

S/L Series

0291	OD mm	OD mm
GVR-DKO-10S/08L	10	8
GVR-DKO-12S/08L	12	8
GVR-DKO-12S/10L	12	10
GVR-DKO-16S/10L	16	10
GVR-DKO-16S/12L	16	12
GVR-DKO-16S/15L	16	15
GVR-DKO-20S/18L	20	18
GVR-DKO-25S/18L	25	18
GVR-DKO-25S/22L	25	22
GVR-DKO-30S/28L	30	28
GVR-DKO-38S/35L	38	35
Tech Sheet 71715		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Adjustable Elbows - DKO




L Series, Metric, Female Thread

0291	OD mm	Thread
EW-DKOL-06	6	M12 x 1,5
EW-DKOL-08	8	M14 x 1,5
EW-DKOL-10	10	M16 x 1,5
EW-DKOL-12	12	M18 x 1,5
EW-DKOL-15	15	M22 x 1,5
EW-DKOL-18	18	M26 x 1,5
EW-DKOL-22	22	M30 x 2
EW-DKOL-28	28	M36 x 2
EW-DKOL-35	35	M45 x 2
EW-DKOL-42	42	M52 x 2
Tech Sheet 71716		

S Series, Metric, Female Thread

0291	OD mm	Thread
EW-DKOS-06	6	M14 x 1,5
EW-DKOS-08	8	M16 x 1,5
EW-DKOS-10	10	M18 x 1,5
EW-DKOS-12	12	M20 x 1,5
EW-DKOS-14	14	M22 x 1,5
EW-DKOS-16	16	M24 x 1,5
EW-DKOS-20	20	M30 x 2
EW-DKOS-25	25	M36 x 2
EW-DKOS-30	30	M42 x 2
EW-DKOS-38	38	M52 x 2
Tech Sheet 71716		

Adjustable Branch Tees - DKO



L Series, Metric, Female Thread

0291	OD mm	Thread
ET-DKOL-06	6	M12 x 1,5
ET-DKOL-08	8	M14 x 1,5
ET-DKOL-10	10	M16 x 1,5
ET-DKOL-12	12	M18 x 1,5
ET-DKOL-15	15	M22 x 1,5
ET-DKOL-18	18	M26 x 1,5
ET-DKOL-22	22	M30 x 2
ET-DKOL-28	28	M36 x 2
ET-DKOL-35	35	M45 x 2
ET-DKOL-42	42	M52 x 2
Tech Sheet 71717		

S Series, Metric, Female Thread

0291	OD mm	OD mm
ET-DKOS-06	6	M14 x 1,5
ET-DKOS-08	8	M16 x 1,5
ET-DKOS-10	10	M18 x 1,5
ET-DKOS-12	12	M20 x 1,5
ET-DKOS-14	14	M22 x 1,5
ET-DKOS-16	16	M24 x 1,5
ET-DKOS-20	20	M30 x 2
ET-DKOS-25	25	M36 x 2
ET-DKOS-30	30	M42 x 2
ET-DKOS-38	38	M52 x 2
Tech Sheet 71717		

Adjustable Run Tees - DKO



L Series, Metric, Female Thread

0291	OD mm	Thread
EL-DKOL-06	6	M12 x 1,5
EL-DKOL-08	8	M14 x 1,5
EL-DKOL-10	10	M16 x 1,5
EL-DKOL-12	12	M18 x 1,5
EL-DKOL-15	15	M22 x 1,5
EL-DKOL-18	18	M26 x 1,5
EL-DKOL-22	22	M30 x 2
EL-DKOL-28	28	M36 x 2
EL-DKOL-35	35	M45 x 2
EL-DKOL-42	42	M52 x 2
Tech Sheet 71718		

S Series, Metric, Female Thread

0291	OD mm	Thread
EL-DKOS-06	6	M14 x 1,5
EL-DKOS-08	8	M16 x 1,5
EL-DKOS-10	10	M18 x 1,5
EL-DKOS-12	12	M20 x 1,5
EL-DKOS-14	14	M22 x 1,5
EL-DKOS-16	16	M24 x 1,5
EL-DKOS-20	20	M30 x 2
EL-DKOS-25	25	M36 x 2
EL-DKOS-30	30	M42 x 2
EL-DKOS-38	38	M52 x 2
Tech Sheet 71718		

stainless steel

For **Stainless Steel Hydraulic Ball Valves** see page **242**



Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Reducing Couplings - DKO



L Series

0291	OD mm	OD mm
RED-DKOL-08/06	8	6
RED-DKOL-10/06	10	6
RED-DKOL-10/08	10	8
RED-DKOL-12/06	12	6
RED-DKOL-12/08	12	8
RED-DKOL-12/10	12	10
RED-DKOL-15/06	15	6
RED-DKOL-15/08	15	8
RED-DKOL-15/10	15	10
RED-DKOL-15/12	15	12
RED-DKOL-18/06	18	6
RED-DKOL-18/08	18	8
RED-DKOL-18/10	18	10
RED-DKOL-18/12	18	12
RED-DKOL-18/15	18	15
RED-DKOL-22/06	22	6
RED-DKOL-22/08	22	8
RED-DKOL-22/10	22	10
RED-DKOL-22/12	22	12
RED-DKOL-22/15	22	15
RED-DKOL-22/18	22	18
RED-DKOL-28/06	28	6
RED-DKOL-28/08	28	8
RED-DKOL-28/10	28	10
RED-DKOL-28/12	28	12
RED-DKOL-28/15	28	15
RED-DKOL-28/18	28	18
RED-DKOL-28/22	28	22
RED-DKOL-35/06	35	6
RED-DKOL-35/08	35	8
RED-DKOL-35/10	35	10
RED-DKOL-35/12	35	12
RED-DKOL-35/15	35	15
RED-DKOL-35/18	35	18
RED-DKOL-35/22	35	22
RED-DKOL-35/28	35	28
RED-DKOL-42/06	42	6
RED-DKOL-42/08	42	8
RED-DKOL-42/10	42	10
RED-DKOL-42/12	42	12
RED-DKOL-42/15	42	15
RED-DKOL-42/18	42	18
RED-DKOL-42/22	42	22
RED-DKOL-42/28	42	28
RED-DKOL-42/35	42	35

Tech Sheet 71719

S Series

0291	OD mm	OD mm
RED-DKOS-08/06	8	6
RED-DKOS-10/06	10	6
RED-DKOS-10/08	10	8
RED-DKOS-12/06	12	6
RED-DKOS-12/08	12	8
RED-DKOS-12/10	12	10
RED-DKOS-14/06	14	6
RED-DKOS-14/08	14	8
RED-DKOS-14/10	14	10
RED-DKOS-14/12	14	12
RED-DKOS-16/06	16	6
RED-DKOS-16/08	16	8
RED-DKOS-16/10	16	10
RED-DKOS-16/12	16	12
RED-DKOS-16/14	16	14
RED-DKOS-20/06	20	6
RED-DKOS-20/08	20	8
RED-DKOS-20/10	20	10
RED-DKOS-20/12	20	12
RED-DKOS-20/14	20	14
RED-DKOS-20/16	20	16
RED-DKOS-25/06	25	6
RED-DKOS-25/08	25	8
RED-DKOS-25/10	25	10
RED-DKOS-25/12	25	12
RED-DKOS-25/14	25	14
RED-DKOS-25/16	25	16
RED-DKOS-25/20	25	20
RED-DKOS-30/06	30	6
RED-DKOS-30/08	30	8
RED-DKOS-30/10	30	10
RED-DKOS-30/12	30	12
RED-DKOS-30/14	30	14
RED-DKOS-30/16	30	16
RED-DKOS-30/20	30	20
RED-DKOS-30/25	30	25
RED-DKOS-38/06	38	6
RED-DKOS-38/08	38	8
RED-DKOS-38/10	38	10
RED-DKOS-38/12	38	12
RED-DKOS-38/14	38	14
RED-DKOS-38/16	38	16
RED-DKOS-38/20	38	20
RED-DKOS-38/25	38	25
RED-DKOS-38/30	38	30

Tech Sheet 71720

Swivel Female - Male, Connectors - DKO



L Series

0291	OD mm	Thread BSPP
EGE-DKO-06L-2EO	6	1/8"
EGE-DKO-06L-4EO	6	1/4"
EGE-DKO-06L-6EO	6	3/8"
EGE-DKO-08L-2EO	8	1/8"
EGE-DKO-08L-4EO	8	1/4"
EGE-DKO-08L-6EO	8	3/8"
EGE-DKO-08L-8EO	8	1/2"
EGE-DKO-10L-2EO	10	1/8"
EGE-DKO-10L-4EO	10	1/4"
EGE-DKO-10L-6EO	10	3/8"
EGE-DKO-10L-8EO	10	1/2"
EGE-DKO-12L-2EO	12	1/8"
EGE-DKO-12L-4EO	12	1/4"
EGE-DKO-12L-6EO	12	3/8"
EGE-DKO-12L-8EO	12	1/2"
EGE-DKO-15L-6EO	15	3/8"
EGE-DKO-15L-8EO	15	1/2"
EGE-DKO-15L-12EO	15	3/4"
EGE-DKO-18L-6EO	18	3/8"
EGE-DKO-18L-8EO	18	1/2"
EGE-DKO-18L-12EO	18	3/4"
EGE-DKO-22L-8EO	22	1/2"
EGE-DKO-22L-12EO	22	3/4"
EGE-DKO-22L-16EO	22	1"
EGE-DKO-28L-12EO	28	3/4"
EGE-DKO-28L-16EO	28	1"
EGE-DKO-35L-20EO	35	1.1/4"
EGE-DKO-42L-20EO	42	1.1/4"
EGE-DKO-42L-24EO	42	1.1/2"

Tech Sheet 71721

S Series

0291	OD mm	Thread BSPP
EGE-DKO-06S-4EO	6	1/4"
EGE-DKO-08S-4EO	8	1/4"
EGE-DKO-08S-6EO	8	3/8"
EGE-DKO-10S-4EO	10	1/4"
EGE-DKO-10S-6EO	10	3/8"
EGE-DKO-10S-8EO	10	1/2"
EGE-DKO-12S-4EO	12	1/4"
EGE-DKO-12S-6EO	12	3/8"
EGE-DKO-12S-8EO	12	1/2"
EGE-DKO-14S-8EO	14	1/2"
EGE-DKO-16S-6EO	16	3/8"
EGE-DKO-16S-8EO	16	1/2"
EGE-DKO-16S-12EO	16	3/4"
EGE-DKO-20S-8EO	20	1/2"
EGE-DKO-20S-12EO	20	3/4"
EGE-DKO-20S-16EO	20	1"
EGE-DKO-25S-12EO	25	3/4"
EGE-DKO-25S-16EO	25	1"
EGE-DKO-30S-16EO	30	1"
EGE-DKO-30S-20EO	30	1.1/4"
EGE-DKO-38S-24EO	38	1.1/2"

Tech Sheet 71721

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature:
-20°C to +200°C (FPM/Viton)

Banjo Elbows



LL Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-4LL-2EO-WDS	4	1/8"
WHV-6LL-2EO-WDS	6	1/8"
WHV-8LL-2EO-WDS	8	1/8"
Tech Sheet 71722		

L Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-06L-2EO-WDS	6	1/8"
WHV-08L-4EO-WDS	8	1/4"
WHV-10L-4EO-WDS	10	1/4"
WHV-10L-6EO-WDS	10	3/8"
WHV-12L-4EO-WDS	12	1/4"
WHV-12L-6EO-WDS	12	3/8"
WHV-12L-8EO-WDS	12	1/2"
WHV-15L-8EO-WDS	15	1/2"
WHV-18L-8EO-WDS	18	1/2"
WHV-22L-12EO-WDS	22	3/4"
WHV-28L-16EO-WDS	28	1"
WHV-35L-20EO-WDS	35	1.1/4"
WHV-42L-24EO-WDS	42	1.1/2"
Tech Sheet 71722		

S Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-06S-4EO-WDS	6	1/4"
WHV-08S-4EO-WDS	8	1/4"
WHV-10S-4EO-WDS	10	1/4"
WHV-10S-6EO-WDS	10	3/8"
WHV-12S-6EO-WDS	12	3/8"
WHV-14S-8EO-WDS	14	1/2"
WHV-16S-8EO-WDS	16	1/2"
WHV-20S-12EO-WDS	20	3/4"
WHV-25S-16EO-WDS	25	1"
WHV-30S-20EO-WDS	30	1.1/4"
WHV-38S-24EO-WDS	38	1.1/2"
Tech Sheet 71722		

Banjo Tees



LL Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-4LL-2EO-WDS	4	1/8"
THV-6LL-2EO-WDS	6	1/8"
THV-8LL-2EO-WDS	8	1/8"
Tech Sheet 71723		

L Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-06L-2EO-WDS	6	1/8"
THV-08L-4EO-WDS	8	1/4"
THV-10L-4EO-WDS	10	1/4"
THV-12L-4EO-WDS	12	1/4"
THV-12L-6EO-WDS	12	3/8"
THV-15L-8EO-WDS	15	1/2"
THV-18L-8EO-WDS	18	1/2"
THV-22L-12EO-WDS	22	3/4"
THV-28L-16EO-WDS	28	1"
THV-35L-20EO-WDS	35	1.1/4"
THV-42L-24EO-WDS	42	1.1/2"
Tech Sheet 71723		

S Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-06S-4EO-WDS	6	1/4"
THV-08S-4EO-WDS	8	1/4"
THV-10S-4EO-WDS	10	1/4"
THV-10S-6EO-WDS	10	3/8"
THV-12S-6EO-WDS	12	3/8"
THV-14S-8EO-WDS	14	1/2"
THV-16S-8EO-WDS	16	1/2"
THV-20S-12EO-WDS	20	3/4"
THV-25S-16EO-WDS	25	1"
THV-30S-20EO-WDS	30	1.1/4"
THV-38S-24EO-WDS	38	1.1/2"
Tech Sheet 71723		

One-Bite Cutting Rings - SPH Finish



LL Series Sealing Ring with SPH Finish

0291	OD mm
SR-LL-04/1 K-SPH	4
SR-LL-06/1 K-SPH	6
SR-LL-08/1 K-SPH	8
Tech Sheet 71724	

Double-Bite Cutting Rings - SPH Finish



L Series Sealing Ring with SPH Finish

0291	OD mm
SR-L-06/2 K-SPH	6
SR-L-08/2 K-SPH	8
SR-L-10/2 K-SPH	10
SR-L-12/2 K-SPH	12
SR-L-15/2 K-SPH	15
SR-L-18/2 K-SPH	18
SR-L-22/2 K-SPH	22
SR-L-28/2 K-SPH	28
SR-L-35/2 K-SPH	35
SR-L-42/2 K-SPH	42
Tech Sheet 71724	

S Series Sealing Ring with SPH Finish

0291	OD mm
SR-S-06/2 K-SPH	6
SR-S-08/2 K-SPH	8
SR-S-10/2 K-SPH	10
SR-S-12/2 K-SPH	12
SR-S-16/2 K-SPH	16
SR-S-20/2 K-SPH	20
SR-S-25/2 K-SPH	25
SR-S-30/2 K-SPH	30
SR-S-38/2 K-SPH	38
Tech Sheet 71724	

Fluid-Air Components Ltd

STAINLESS STEEL COMPONENT PARTS

stainless steel

Silver Plated Stainless Steel Nuts (AGP)

There is a high risk for cold welding (gripping) at the threads without silver-coating.
Together with ABF-grease easy assembly due to reduction in tightening torque by up to 70%.
Reduced torsion load to the coupling body.
Applications: Marine industry.



Light-duty

0294	Thread	OD mm
M18L-1.4571AGP	M26 x 1.5	18
M22L-1.4571AGP	M30 x 2	22
M28L-1.4571AGP	M36 x 2	28
M35L-1.4571AGP	M45 x 2	35

Heavy-duty

0294	Thread	OD mm
M20S-1.4571AGP	M30 x 2	20
M25S-1.4571AGP	M36 x 2	25
M30S-1.4571AGP	M42 x 2	30
M38S-1.4571AGP	M52 x 2	38

ABF Anti Bloc Grease

Special grease for the installation of stainless couplings, material 1.4571.

Applications: Marine industry.
To avoid gripping and reduce the coefficient of friction.



1000g Can

0294	Grams
ANTI-BLOC 1KG	1000



100g Tube

0294	Grams
ANTI-BLOC 100G	100

stainless steel

For **Stainless Steel Tubing** see page **183**



Fluid-Air Components Ltd

INTRODUCING TWIN FERRULE TUBE COMPRESSION FITTINGS

stainless steel

PANAM


Panam Instrumentation tube fittings provide a zero leak proof seal which will withstand high pressure, impulse, vibration and temperature. These features offer high safety and maintenance free smooth working. Each component is precision machined to the most accurate tolerance; maintain TQM practices throughout manufacturing process.

The fittings are manufactured in accordance with ISO9001 quality standards and CE marking requirements with complete traceability records available upon request.

Available in 316 SS, Brass, CS, Monel materials in a variety of end connections. Straight fittings are machined from bar stock and shaped bodies are machined from forgings.

The fittings are used on instrumentation process control systems, analysers and environmental equipment in oil and gas, Petro-chemical, Power generation, Pulp and Paper industry and many more.

Functions



Compression nut Threads are silver plated which prevents galling.

Back Ferrule locks together the fittings and tube forms a primary Seal which absorbs the pressure pulses and vibration.

Front Ferrule Forms a secondary seal which connects tube and fitting and guarantees a bubble tight Zero Leak Sealing.

Rugged body construction, high precision machined surface and standardised tolerances provides maximum trouble free service life in severe working conditions.

The above illustrates sealing action of a Tube Fitting assembly which takes place after the assembly is fully tightened

Assembly Instructions

SIZE M6 thru M25 (6mm-25mm)



1-1/4 Turns from Finger Tight

SIZE M3 thru M4 (3mm-4mm)




Only 3/4 Turn from Finger Tight is necessary to seal and will result in additional remakes of the fitting

1 Insert the tubing in to the Tube Fitting until it comes up to the tube stop.

2 Ensure that the nut is finger tight and tighten the nut 1-1/4 turns as shown in figure.

3 For 1/8" and 3/16 Fittings only 3/4 turns as shown in Fig-3.

Identification of Twin Ferrule Fittings



The Metric size of the Fittings have extra stepped shoulder on the body and nut to distinguish them from imperial size.

All Dimensions are in mm unless otherwise stated. Dimensions are for reference only, subject to change.

Material Standards

Material	Bar Stock a	Forging b	Tubing
316 Stainless Steel	ASTM A276 ASME SA479	ASTM A182 ASME SA182	ASME-SA-213 / ASTM-A-213/ ASTM-A-249 / ASTM-A-269 / MIL T-88504 / MIL T-8506
Brass	ASTRM B16	ASTM B283	ASTM-B75 / ASME-SB75 (TEMPER "O")
Alloy 400	ASTM B164 ASMESB164	ASTM B564 ASME SB564	
Alloy 600	ASTM B166 ASME SB166	ASTM B564 ASME SB564	ASTM-B-163
Alloy C-276	ASTM B574	ASTM SB564	ASTM-B-622 / ASTM-B-626
Carbon Steel	ASTM A108		SAE J524b / SAE J525b / ASTM-A-179
PTFE	ASTM D1710	ASTM D3293	

A includes straight configuration **B** includes all elbows, crosses and tees

Stress Values based on ASME B31.3 Code for Process Piping

Material	Allowable Stress Value Psig	Allowable Stress Value bar	Design Factor	Ultimate Tensile Strength Psig	Ultimate Tensile Strength bar
316SS	20000	1378	3.75:1	75000	5170
Brass	10000	689	4:1	40000	2760
Steel	20000	1378	3:1	60000	4140

Pipe End Pressure Ratings

Calculations based on ASME B31.3 code for Process Piping

NPT/ISO Pipe Size Inches	316 SS and Carbon Steel Male Psig	316 SS and Carbon Steel Male bar	316 SS and Carbon Steel Female Psig	316 SS and Carbon Steel Female bar	Brass Male Psig	Brass Male bar	Brass Female Psig	Brass Female bar
1/16	11000	760	6700	460	5500	380	3300	230
1/8	10000	690	6500	440	5000	340	3200	220
1/4	8000	550	6600	450	4000	270	3300	220
S3/8	7800	540	5300	360	3900	270	2600	180
1/2	7700	530	4900	330	3800	260	2400	160
3/4	7300	500	4600	320	3600	250	2300	160
1	5300	370	4400	300	2600	180	2200	150
1.1/4	6000	410	5000	350	3000	200	2500	170
1.1/2	5000	340	4600	310	2500	170	2300	150
2	3900	270	3900	270	1900	130	1900	130

To determine working pressure ratings in accordance with ASME B31.1 Power Piping For 316 stainless steel, multiply psig by 0.94; for carbon steel multiply psig by 0.75; Brass ratings remain the same. To determine working pressure kPa multiply psig by 6.89

SAE Pressure Ratings

Pressure Ratings are from SAE J1926/3

SAE/MS Thread Size	316 SS and Carbon Steel (Nonpositionable) Psig	316 SS and Carbon Steel (Nonpositionable) bar	316 SS and Carbon Steel (Positionable) Psig	316 SS and Carbon Steel (Positionable) bar
5/16-24	4568	315	4568	315
7/16-20				
1/2-20				
9/16-18			3626	250
3/4-16				
7/8-14	3626	250	2900	200
1.1/16-12				
1.3/16-12	2900	200	2320	160
1.5/16-12				
1.5/8-12	2320	160	1813	125
1.7/8-12				
1.1/2-12	1813	125	1450	100

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Connectors



Male Thread, NPT

0292	OD	Thread
MC-125-125N	1/8"	1/8"
MC-125-250N	1/8"	1/4"
MC-125-375N	1/8"	3/8"
MC-125-500N	1/8"	1/2"
MC-187-125N	3/16"	1/8"
MC-187-250N	3/16"	1/4"
MC-250-125N	1/4"	1/8"
MC-250-250N	1/4"	1/4"
MC-250-375N	1/4"	3/8"
MC-250-500N	1/4"	1/2"
MC-250-750N	1/4"	3/4"
MC-312-125N	5/16"	1/8"
MC-312-250N	5/16"	1/4"
MC-312-375N	5/16"	3/8"
MC-312-500N	5/16"	1/2"
MC-375-125N	5/16"	1/8"
MC-375-250N	3/8"	1/4"
MC-375-375N	3/8"	3/8"
MC-375-500N	3/8"	1/2"
MC-375-750N	3/8"	3/4"
MC-500-125N	1/2"	1/8"
MC-500-250N	1/2"	1/4"
MC-500-375N	1/2"	3/8"
MC-500-500N	1/2"	1/2"
MC-500-750N	1/2"	3/4"
MC-500-1000N	1/2"	1"
MC-625-375N	5/8"	3/8"
MC-625-500N	5/8"	1/2"
MC-625-750N	5/8"	3/4"
MC-750-500N	3/4"	1/2"
MC-750-750N	3/4"	3/4"
MC-750-1000N	3/4"	1"
MC-875-750N	7/8"	3/4"
MC-875-1000N	7/8"	1"
MC-1000-500N	1"	1/2"
MC-1000-750N	1"	3/4"
MC-1000-1000N	1"	1"
Tech Sheet 20234		



Male Thread, BSPT

0292	OD	Thread
MC-125-125RT	1/8"	1/8"
MC-125-250RT	1/8"	1/4"
MC-250-125RT	1/4"	1/8"
MC-250-250RT	1/4"	1/4"
MC-250-375RT	1/4"	3/8"
MC-250-500RT	1/4"	1/2"
MC-312-125RT	5/16"	1/8"
MC-312-250RT	5/16"	1/4"
MC-375-125RT	3/8"	1/8"
MC-375-250RT	3/8"	1/4"
MC-375-375RT	3/8"	3/8"
MC-375-500RT	3/8"	1/2"
MC-500-250RT	1/2"	1/4"
MC-500-375RT	1/2"	3/8"
MC-500-500RT	1/2"	1/2"
MC-500-750RT	1/2"	3/4"
MC-750-750RT	3/4"	3/4"
MC-1000-1000RT	1"	1"
Tech Sheet 20233		



Male Thread, SAE/MS

0292	OD	Thread
MC-125-312SE	1/8"	5/16"-24
MC-125-562SE	1/8"	9/16"-18
MC-250-437SE	1/4"	7/16"-20
MC-250-750SE	1/4"	3/4"-16
MC-250-875SE	1/4"	7/8"-14
MC-312-500SE	5/16"	1/2"-20
MC-375-437SE	3/8"	7/16"-20
MC-375-562SE	3/8"	9/16"-18
MC-375-750SE	3/8"	3/4"-16
MC-375-875SE	3/8"	7/8"-14
MC-500-562SE	1/2"	9/16"-18
MC-500-750SE	1/2"	3/4"-16
MC-500-875SE	1/2"	7/8"-14
MC-500-1062SE	1/2"	1.1/16"-12
MC-625-750SE	5/8"	3/4"-16
MC-625-875SE	5/8"	7/8"-14
MC-750-750SE	3/4"	3/4"-16
MC-750-1062SE	3/4"	1.1/16"-12
MC-875-1187SE	7/8"	1.3/16"-12
MC-1000-1062SE	1"	1.1/16"-12
MC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20807		



Male Thread, SAE/MS (Long)

0292	OD	Thread
LMC-250-437SE	1/4"	7/16"-20
LMC-312-500SE	5/16"	1/2"-20
LMC-375-562SE	3/8"	9/16"-18
LMC-500-750SE	1/2"	3/4"-16
LMC-625-875SE	5/8"	7/8"-14
LMC-750-1062SE	3/4"	1.1/16"-12
LMC-875-1187SE	7/8"	1.3/16"-12
LMC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20808		



Male Thread, SAE/MS (Captive Seal)

0292	OD	Thread
OMC-125-312SE	1/8"	5/16"-24
OMC-187-375SE	3/16"	3/8"-24
OMC-250-437SE	1/4"	7/16"-20
OMC-312-500SE	5/16"	1/2"-20
OMC-375-562SE	3/8"	9/16"-18
OMC-500-750SE	1/2"	3/4"-16
OMC-750-1062SE	3/4"	1.1/16"-12
OMC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20809		

Male Thread, BSPP (Captive Seal)

0292	OD	Thread
OMC-250-250EO	1/4"	1/4"
OMC-250-500EO	1/4"	1/2"
OMC-375-375EO	3/8"	3/8"
OMC-500-250EO	1/2"	1/4"
OMC-500-375EO	1/2"	3/8"
OMC-500-500EO	1/2"	1/2"
OMC-750-750EO	3/4"	3/4"
Tech Sheet 20809		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Connectors

Stainless steel washer with a Viton inner ring.



Male Thread-RS, BSPP

0292	OD	Thread
MC-125-125RS	1/8"	1/8"
MC-125-250RS	1/8"	1/4"
MC-125-375RS	1/8"	3/8"
MC-250-125RS	1/4"	1/8"
MC-250-250RS	1/4"	1/4"
MC-250-375RS	1/4"	3/8"
MC-250-500RS	1/4"	1/2"
MC-375-250RS	3/8"	1/4"
MC-375-375RS	3/8"	3/8"
MC-375-500RS	3/8"	1/2"
MC-500-250RS	1/2"	1/4"
MC-500-375RS	1/2"	3/8"
MC-500-500RS	1/2"	1/2"
MC-750-500RS	3/4"	1/2"
MC-750-750RS	3/4"	3/4"
MC-1000-500RS	1"	1/2"
MC-1000-1000RS	1"	1"

Tech Sheet 20810

LOCTITE



For **Threadlockers** see page **1584**

Female Connectors



Female Thread, NPT

0292	OD	Thread
FC-125-125N	1/8"	1/8"
FC-125-250N	1/8"	1/4"
FC-187-125N	3/16"	1/8"
FC-250-125N	1/4"	1/8"
FC-250-250N	1/4"	1/4"
FC-250-375N	1/4"	3/8"
FC-250-500N	1/4"	1/2"
FC-312-125N	5/16"	1/8"
FC-312-250N	5/16"	1/4"
FC-312-375N	5/16"	3/8"
FC-375-125N	3/8"	1/8"
FC-375-250N	3/8"	1/4"
FC-375-375N	3/8"	3/8"
FC-375-500N	3/8"	1/2"
FC-375-750N	3/8"	3/4"
FC-500-250N	1/2"	1/4"
FC-500-375N	1/2"	3/8"
FC-500-500N	1/2"	1/2"
FC-500-750N	1/2"	3/4"
FC-625-375N	5/8"	3/8"
FC-625-500N	5/8"	1/2"
FC-625-750N	5/8"	3/4"
FC-750-500N	3/4"	1/2"
FC-750-750N	3/4"	3/4"
FC-875-750N	7/8"	3/4"
FC-1000-750N	1"	3/4"
FC-1000-1000N	1"	1"

Tech Sheet 20235

Female Thread, BSPT

0292	OD	Thread
FC-250-125RT	1/4"	1/8"
FC-250-250RT	1/4"	1/4"
FC-250-375RT	1/4"	3/8"
FC-250-500RT	1/4"	1/2"
FC-375-250RT	3/8"	1/4"
FC-375-375RT	3/8"	3/8"
FC-375-500RT	3/8"	1/2"
FC-500-250RT	1/2"	1/4"
FC-500-375RT	1/2"	3/8"
FC-500-500RT	1/2"	1/2"

Tech Sheet 20237

Female Thread, BSPP

0292	OD	Thread
FC-250-250RG	1/4"	1/4"
FC-250-375RG	1/4"	3/8"
FC-250-500RG	1/4"	1/2"
FC-312-250RG	5/16"	1/4"
FC-312-500RG	5/16"	1/2"
FC-375-250RG	3/8"	1/4"
FC-375-375RG	3/8"	3/8"
FC-375-500RG	3/8"	1/2"
FC-500-375RG	1/2"	3/8"
FC-500-500RG	1/2"	1/2"

Tech Sheet 20236

Bulkhead Male Connectors



Male Thread, NPT

0292	OD	Thread
BMC-125-125N	1/8"	1/8"
BMC-187-125N	3/16"	1/8"
BMC-250-125N	1/4"	1/8"
BMC-250-250N	1/4"	1/4"
BMC-250-375N	1/4"	3/8"
BMC-250-500N	1/4"	1/2"
BMC-312-125N	5/16"	1/8"
BMC-312-250N	5/16"	1/4"
BMC-375-125N	3/8"	1/8"
BMC-375-250N	3/8"	1/4"
BMC-375-375N	3/8"	3/8"
BMC-500-250N	1/2"	1/4"
BMC-500-375N	1/2"	3/8"
BMC-500-500N	1/2"	1/2"
BMC-500-750N	1/2"	3/4"
BMC-625-375N	5/8"	3/8"
BMC-625-500N	5/8"	1/2"
BMC-750-500N	3/4"	1/2"
BMC-750-750N	3/4"	3/4"
BMC-875-750N	7/8"	3/4"
BMC-1000-750N	1"	3/4"

Tech Sheet 20814

Bulkhead Female Connectors



Female Thread, NPT

0292	OD	Thread
BFC-125-125N	1/8"	1/8"
BFC-187-125N	3/16"	1/8"
BFC-250-125N	1/4"	1/8"
BFC-250-250N	1/4"	1/4"
BFC-312-125N	5/16"	1/8"
BFC-375-250N	3/8"	1/4"
BFC-500-375N	1/2"	3/8"
BFC-500-500N	1/2"	1/2"
BFC-625-500N	5/8"	1/2"
BFC-750-750N	3/4"	3/4"
BFC-875-750N	7/8"	3/4"
BFC-1000-1000N	1"	1"

Tech Sheet 20815

FAC
Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Unions



Tube x Tube

0292	OD
U-125	1/8"
U-187	3/16"
U-250	1/4"
U-312	5/16"
U-375	3/8"
U-500	1/2"
U-625	5/8"
U-750	3/4"
U-875	7/8"
U-1000	1"

Tech Sheet 20297



Metric Tube x Imperial Tube

0292	OD mm	OD
U-3-125	3	1/8"
U-4-125	4	1/8"
U-4-250	4	1/4"
U-6-125	6	1/8"
U-6-250	6	1/4"
U-6-312	6	5/16"
U-8-250	8	1/4"
U-8-375	8	3/8"
U-10-125	10	1/8"
U-10-250	10	1/4"
U-10-312	10	5/16"
U-10-375	10	3/8"
U-12-312	12	5/16"
U-12-375	12	3/8"
U-12-500	12	1/2"
U-15-500	15	1/2"
U-18-750	18	3/4"
U-20-500	20	1/2"
U-20-1000	20	1"
U-25-1000	25	1"

Tech Sheet 20817

Reducing Unions



Tube x Tube

0292	OD	OD
RU-187-125	3/16"	1/8"
RU-250-125	1/4"	1/8"
RU-250-187	1/4"	3/16"
RU-312-125	5/16"	1/8"
RU-312-250	5/16"	1/4"
RU-375-125	3/8"	1/8"
RU-375-250	3/8"	1/4"
RU-375-312	3/8"	5/16"
RU-500-125	1/2"	1/8"
RU-500-250	1/2"	1/4"
RU-500-375	1/2"	3/8"
RU-625-375	5/8"	3/8"
RU-625-500	5/8"	1/2"
RU-750-250	3/4"	1/4"
RU-750-375	3/4"	3/8"
RU-750-500	3/4"	1/2"
RU-750-625	3/4"	5/8"
RU-1000-500	1"	1/2"
RU-1000-750	1"	3/4"

Tech Sheet 20298

Bulkhead Unions



Tube x Tube

0292	OD
BU-125	1/8"
BU-187	3/16"
BU-250	1/4"
BU-312	5/16"
BU-375	3/8"
BU-500	1/2"
BU-625	5/8"
BU-750	3/4"
BU-1000	1"

Tech Sheet 20238

Male Branch Tees



Male Thread, NPT

0292	OD	Thread
MBT-125-125N	1/8"	1/8"
MBT-125-250N	1/8"	1/4"
MBT-187-125N	3/16"	1/8"
MBT-250-125N	1/4"	1/8"
MBT-250-250N	1/4"	1/4"
MBT-312-125N	5/16"	1/8"
MBT-375-250N	3/8"	1/4"
MBT-375-375N	3/8"	3/8"
MBT-500-375N	1/2"	3/8"
MBT-500-500N	1/2"	1/2"
MBT-625-500N	5/8"	1/2"
MBT-750-750N	3/4"	3/4"

Tech Sheet 20240

Male Positionable Branch Tees



Male Thread, SAE/MS

0292	OD	Thread
MBTP-250-437SE	1/4"	7/16"-20
MBTP-375-562SE	3/8"	9/16"-18
MBTP-500-750SE	1/2"	3/4"-16
MBTP-750-1062SE	3/4"	1.1/16"-12
MBTP-1000-1312SE	1"	1.5/16"-12

Tech Sheet 20821

Male Thread, BSPP

0292	OD	Thread
MBTP-250-125PR	1/4"	1/8"
MBTP-250-250PR	1/4"	1/4"
MBTP-375-250PR	3/8"	1/4"
MBTP-500-375PR	1/2"	3/8"
MBTP-500-500PR	1/2"	1/2"
MBTP-625-500PR	5/8"	1/2"
MBTP-750-500PR	3/4"	1/2"
MBTP-750-750PR	3/4"	3/4"
MBTP-1000-1000PR	1"	1"

Tech Sheet 20822

Male Run Tees



Male Thread, NPT

0292	OD	Thread
MRT-125-125N	1/8"	1/8"
MRT-125-250N	1/8"	1/4"
MRT-187-125N	3/16"	1/8"
MRT-250-125N	1/4"	1/8"
MRT-250-250N	1/4"	1/4"
MRT-312-125N	5/16"	1/8"
MRT-375-250N	3/8"	1/4"
MRT-375-375N	3/8"	3/8"
MRT-500-375N	1/2"	3/8"
MRT-500-500N	1/2"	1/2"
MRT-625-500N	5/8"	1/2"
MRT-750-750N	3/4"	3/4"

Tech Sheet 20299

FAC
Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Positionable Run Tees



Male Thread, SAE/MS

0292	OD	Thread
MRTP-250-437SE	1/4"	7/16"-20
MRTP-375-562SE	3/8"	9/16"-18
MRTP-500-750SE	1/2"	3/4"-16
MRTP-750-1062SE	3/4"	1.1/16"-12
MRTP-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20824		

Male Thread, BSPP

0292	OD	Thread
MRTP-250-125PR	1/4"	1/8"
MRTP-250-250PR	1/4"	1/4"
MRTP-375-250PR	3/8"	1/4"
MRTP-500-375PR	1/2"	3/8"
MRTP-500-500PR	1/2"	1/2"
MRTP-625-500PR	5/8"	1/2"
MRTP-750-500PR	3/4"	1/2"
MRTP-750-750PR	3/4"	3/4"
MRTP-1000-1000PR	1"	1"
Tech Sheet 20825		

Female Branch Tees



Female Thread, NPT

0292	OD	Thread
FBT-125-125N	1/8"	1/8"
FBT-250-125N	1/4"	1/8"
FBT-250-250N	1/4"	1/4"
FBT-375-250N	3/8"	1/4"
FBT-375-375N	3/8"	3/8"
FBT-375-500N	3/8"	1/2"
FBT-500-250N	1/2"	1/4"
FBT-500-375N	1/2"	3/8"
FBT-500-500N	1/2"	1/2"
FBT-625-500N	5/8"	1/2"
FBT-750-750N	3/4"	3/4"
FBT-1000-750N	1"	3/4"
FBT-1000-1000N	1"	1"
Tech Sheet 20826		

Female Run Tees



Female Thread, NPT

0292	OD	Thread
FRT-125-125N	1/8"	1/8"
FRT-250-125N	1/4"	1/8"
FRT-250-250N	1/4"	1/4"
FRT-375-250N	3/8"	1/4"
FRT-500-375N	1/2"	3/8"
FRT-500-500N	1/2"	1/2"
FRT-750-750N	3/4"	3/4"
FRT-1000-750N	1"	3/4"
FRT-1000-1000N	1"	1"
Tech Sheet 20239		

Male Elbows



Male Thread, NPT

0292	OD	Thread
ME-125-125N	1/8"	1/8"
ME-125-250N	1/8"	1/4"
ME-187-125N	3/16"	1/8"
ME-187-250N	3/16"	1/4"
ME-250-125N	1/4"	1/8"
ME-250-250N	1/4"	1/4"
ME-250-375N	1/4"	3/8"
ME-250-500N	1/4"	1/2"
ME-312-125N	5/16"	1/8"
ME-312-250N	5/16"	1/4"
ME-312-375N	5/16"	3/8"
ME-375-125N	3/8"	1/8"
ME-375-250N	3/8"	1/4"
ME-375-375N	3/8"	3/8"
ME-375-500N	3/8"	1/2"
ME-375-750N	3/8"	3/4"
ME-500-250N	1/2"	1/4"
ME-500-375N	1/2"	3/8"
ME-500-500N	1/2"	1/2"
ME-500-750N	1/2"	3/4"
ME-625-375N	5/8"	3/8"
ME-625-500N	5/8"	1/2"
ME-625-750N	5/8"	3/4"
ME-750-500N	3/4"	1/2"
ME-750-750N	3/4"	3/4"
ME-875-750N	7/8"	3/4"
ME-1000-750N	1"	3/4"
ME-1000-1000N	1"	1"
Tech Sheet 20295		

Male Thread, BSPT

0292	OD	Thread
ME-250-125RT	1/4"	1/8"
ME-250-250RT	1/4"	1/4"
ME-250-375RT	1/4"	3/8"
ME-250-500RT	1/4"	1/2"
ME-312-250RT	5/16"	1/4"
ME-375-250RT	3/8"	1/4"
ME-375-375RT	3/8"	3/8"
Tech Sheet 20294		

Female Elbows



Female Thread, NPT

0292	OD	Thread
FE-125-125N	1/8"	1/8"
FE-125-250N	1/8"	1/4"
FE-187-125N	3/16"	1/8"
FE-250-125N	1/4"	1/8"
FE-250-250N	1/4"	1/4"
FE-250-375N	1/4"	3/8"
FE-250-500N	1/4"	1/2"
FE-312-125N	5/16"	1/8"
FE-312-250N	5/16"	1/4"
FE-375-125N	3/8"	1/8"
FE-375-250N	3/8"	1/4"
FE-375-375N	3/8"	3/8"
FE-375-500N	3/8"	1/2"
FE-500-250N	1/2"	1/4"
FE-500-375N	1/2"	3/8"
FE-500-500N	1/2"	1/2"
FE-625-375N	5/8"	3/8"
FE-625-500N	5/8"	1/2"
FE-750-500N	3/4"	1/2"
FE-750-750N	3/4"	3/4"
FE-875-750N	7/8"	3/4"
FE-1000-750N	1"	3/4"
FE-1000-1000N	1"	1"
Tech Sheet 20296		

Positionable Elbows



Male Thread, SAE/MS

0292	OD	Thread
MEP-250-437SE	1/4"	7/16"-20
MEP-250-562SE	1/4"	9/16"-18
MEP-312-500SE	5/16"	1/2"-20
MEP-375-562SE	3/8"	9/16"-18
MEP-375-750SE	3/8"	3/4"-16
MEP-500-750SE	1/2"	3/4"-16
MEP-625-875SE	5/8"	7/8"-14
MEP-750-1062SE	3/4"	1.1/16"-12
MEP-875-1187SE	7/8"	1.3/16"-12
MEP-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20831		

Male Thread, BSPP

0292	OD	Thread
MEP-250-125PR	1/4"	1/8"
MEP-250-250PR	1/4"	1/4"
MEP-375-250PR	3/8"	1/4"
MEP-375-375PR	3/8"	3/8"
MEP-500-250PR	1/2"	1/4"
MEP-500-375PR	1/2"	3/8"
MEP-500-500PR	1/2"	1/2"
MEP-625-500PR	5/8"	1/2"
MEP-750-500PR	3/4"	1/2"
MEP-750-750PR	3/4"	3/4"
MEP-1000-750PR	1"	3/4"
MEP-1000-1000PR	1"	1"
Tech Sheet 20832		

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Bulkhead Reducing Unions



Tube x Tube

0292	OD	OD
RBU-250-125	1/4"	1/8"
RBU-375-250	3/8"	1/4"
RBU-500-250	1/2"	1/4"
Tech Sheet 20833		

Union Elbows



Tube x Tube

0292	OD
UE-125	1/8"
UE-187	3/16"
UE-250	1/4"
UE-312	5/16"
UE-375	3/8"
UE-500	1/2"
UE-625	5/8"
UE-750	3/4"
UE-875	7/8"
UE-1000	1"
Tech Sheet 20289	

Reducing Union Elbows



Tube x Tube

0292	OD	OD
RUE-187-125	3/16"	1/8"
RUE-250-125	1/4"	1/8"
RUE-312-125	5/16"	1/8"
RUE-312-250	5/16"	1/4"
RUE-375-125	3/8"	1/8"
RUE-375-250	3/8"	1/4"
RUE-375-312	3/8"	5/16"
RUE-500-250	1/2"	1/4"
RUE-500-312	1/2"	5/16"
RUE-500-375	1/2"	3/8"
RUE-625-375	5/8"	3/8"
RUE-625-500	5/8"	1/2"
RUE-750-250	3/4"	1/4"
RUE-750-375	3/4"	3/8"
RUE-750-500	3/4"	1/2"
RUE-875-250	7/8"	1/4"
RUE-1000-500	1"	1/2"
RUE-1000-750	1"	3/4"
Tech Sheet 20835		

Union Tees



Tube x Tube

0292	OD
UT-125	1/8"
UT-187	3/16"
UT-250	1/4"
UT-312	5/16"
UT-375	3/8"
UT-500	1/2"
UT-625	5/8"
UT-750	3/4"
UT-875	7/8"
UT-1000	1"
Tech Sheet 20288	

Reducing Branch, Union Tees



Tube x Tube

0292	OD	OD
RUT-375-250	3/8"	1/4"
RUT-500-250	1/2"	1/4"
RUT-500-375	1/2"	3/8"
RUT-625-375	5/8"	3/8"
RUT-750-375	3/4"	3/8"
RUT-750-500	3/4"	1/2"
RUT-1000-375	1"	3/8"
RUT-1000-500	1"	1/2"
RUT-1000-750	1"	3/4"
Tech Sheet 20837		

Union Crosses



Tube x Tube

0292	OD
UC-125	1/8"
UC-250	1/4"
UC-312	5/16"
UC-375	3/8"
UC-500	1/2"
UC-750	3/4"
UC-1000	1"
Tech Sheet 20290	

AN Unions



Male Thread, AN

0292	OD	Thread
NU-125-125AN	1/8"	5/16"
NU-125-250AN	1/8"	7/16"
NU-250-250AN	1/4"	7/16"
NU-312-312AN	5/16"	1/2"
NU-375-250AN	3/8"	7/16"
NU-375-375AN	3/8"	9/16"
NU-500-500AN	1/2"	3/4"
NU-750-750AN	3/4"	1.1/16"
NU-1000-1000AN	1"	1.5/16"
Tech Sheet 20839		

AN Bulkhead Unions



Male Thread, AN

0292	OD	Thread
ABU-250-250AN	1/4"	7/16"
ABU-375-375AN	3/8"	9/16"
ABU-500-500AN	1/2"	3/4"
ABU-750-750AN	3/4"	1.1/16"
ABU-1000-1000AN	1"	1.5/16"
Tech Sheet 20840		

Weld Union, Sockets



Tube x Tube

0292	OD
SWU-125	1/8"
SWU-250	1/4"
SWU-375	3/8"
SWU-500	1/2"
SWU-750	3/4"
SWU-1000	1"
Tech Sheet 20841	

Weld Elbow, Sockets



Tube x Tube

0292	OD
SWE-250	1/4"
SWE-375	3/8"
SWE-500	1/2"
SWE-750	3/4"
SWE-1000	1"
Tech Sheet 20842	

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Weld Union, Connectors



Tube x Tube

0292	OD	Stem OD
MWC-125-125	1/8"	1/8"
MWC-187-125	3/16"	1/8"
MWC-250-125	1/4"	1/8"
MWC-250-250	1/4"	1/4"
MWC-312-125	5/16"	1/8"
MWC-312-250	5/16"	1/4"
MWC-375-250	3/8"	1/4"
MWC-375-375	3/8"	3/8"
MWC-375-500	3/8"	1/2"
MWC-375-750	3/8"	3/4"
MWC-500-375	1/2"	3/8"
MWC-500-500	1/2"	1/2"
MWC-500-750	1/2"	3/4"
MWC-625-500	5/8"	1/2"
MWC-750-750	3/4"	3/4"
MWC-1000-1000	1"	1"
Tech Sheet 20843		

Weld Elbow, Connectors



Tube x Tube

0292	OD	Stem OD
MWE-250-125	1/4"	1/8"
MWE-250-250	1/4"	1/4"
MWE-375-250	3/8"	1/4"
MWE-500-500	1/2"	1/2"
MWE-750-750	3/4"	3/4"
Tech Sheet 20844		

Bulkhead Reducers



Tube x Tube

0292	OD
BR-125	1/8"
BR-250	1/4"
BR-375	3/8"
BR-500	1/2"
BR-625	5/8"
BR-1000	1"
Tech Sheet 20287	

Reducers



Tube x Tube

0292	OD	Stem OD
R-125-125	1/8"	1/8"
R-125-187	1/8"	3/16"
R-125-250	1/8"	1/4"
R-125-375	1/8"	3/8"
R-125-500	1/8"	1/2"
R-187-125	3/16"	1/8"
R-187-250	3/16"	1/4"
R-250-125	1/4"	1/8"
R-250-187	1/4"	3/16"
R-250-250	1/4"	1/4"
R-250-312	1/4"	5/16"
R-250-375	1/4"	3/8"
R-250-500	1/4"	1/2"
R-250-625	1/4"	5/8"
R-250-750	1/4"	3/4"
R-312-375	5/16"	3/8"
R-312-500	5/16"	1/2"
R-375-250	3/8"	1/4"
R-375-375	3/8"	3/8"
R-375-500	3/8"	1/2"
R-375-625	3/8"	5/8"
R-375-750	3/8"	3/4"
R-500-250	1/2"	1/4"
R-500-375	1/2"	3/8"
R-500-500	1/2"	1/2"
R-500-625	1/2"	5/8"
R-500-750	1/2"	3/4"
R-500-1000	1/2"	1"
R-625-750	5/8"	3/4"
R-625-875	5/8"	7/8"
R-625-1000	5/8"	1"
R-750-500	3/4"	1/2"
R-750-1000	3/4"	1"
Tech Sheet 20286		

Port Connectors



Tube x Tube

0292	OD
PC-125	1/8"
PC-250	1/4"
PC-312	5/16"
PC-375	3/8"
PC-500	1/2"
PC-750	3/4"
PC-1000	1"
Tech Sheet 20378	

Reducing Port Connectors



Tube x Tube

0292	OD	Stem OD
RPC-250-125	1/4"	1/8"
RPC-375-125	3/8"	1/8"
RPC-375-250	3/8"	1/4"
RPC-500-250	1/2"	1/4"
RPC-750-500	3/4"	1/2"
RPC-1000-500	1"	1/2"
RPC-1000-750	1"	3/4"
Tech Sheet 20849		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Caps



Tube

0292	OD
C-125-FT	1/8"
C-187	3/16"
C-250	1/4"
C-312	5/16"
C-375	3/8"
C-500	1/2"
C-625	5/8"
C-750	3/4"
C-875	7/8"
C-1000	1"

Tech Sheet 20284

Nuts



Tube

0292	OD
N-125-FT	1/8"
N-187	3/16"
N-250	1/4"
N-312	5/16"
N-375	3/8"
N-500	1/2"
N-625	5/8"
N-750	3/4"
N-875	7/8"
N-1000	1"

Tech Sheet 20283

Front Ferrules



Tube

0292	OD
FF-125	1/8"
FF-187	3/16"
FF-250	1/4"
FF-312	5/16"
FF-375	3/8"
FF-500	1/2"
FF-625	5/8"
FF-750	3/4"
FF-875	7/8"
FF-1000	1"

Tech Sheet 20854

Plugs



Tube

0292	OD
P-125	1/8"
P-187	3/16"
P-250	1/4"
P-312	5/16"
P-375	3/8"
P-500	1/2"
P-625	5/8"
P-750	3/4"
P-875	7/8"
P-1000	1"

Tech Sheet 20282

Back Ferrules



Tube

0292	OD
BF-125	1/8"
BF-187	3/16"
BF-250	1/4"
BF-312	5/16"
BF-375	3/8"
BF-500	1/2"
BF-625	5/8"
BF-750	3/4"
BF-875	7/8"
BF-1000	1"

Tech Sheet 20285

Lock Nuts



To suit Bulkheads

0292	OD
BLN-125	1/8"
BLN-187	3/16"
BLN-250	1/4"
BLN-312	5/16"
BLN-375	3/8"
BLN-500	1/2"
BLN-625	5/8"
BLN-750	3/4"
BLN-875	7/8"
BLN-1000	1"

Tech Sheet 20855

Jubilee®



For **Jubilee® Workshop Pack** see page **1520**

FAC Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Male Connectors



Male Thread, NPT

0292	OD mm	Thread
MC-3-125N	3	1/8"
MC-3-250N	3	1/4"
MC-4-125N	4	1/8"
MC-4-250N	4	1/4"
MC-6-125N	6	1/8"
MC-6-250N	6	1/4"
MC-6-375N	6	3/8"
MC-6-500N	6	1/2"
MC-8-125N	8	1/8"
MC-8-250N	8	1/4"
MC-8-375N	8	3/8"
MC-8-500N	8	1/2"
MC-10-125N	10	1/8"
MC-10-250N	10	1/4"
MC-10-375N	10	3/8"
MC-10-500N	10	1/2"
MC-10-750N	10	3/4"
MC-12-125N	12	1/8"
MC-12-250N	12	1/4"
MC-12-375N	12	3/8"
MC-12-500N	12	1/2"
MC-12-750N	12	3/4"
MC-14-250N	14	1/4"
MC-14-375N	14	3/8"
MC-14-500N	14	1/2"
MC-15-500N	15	1/2"
MC-16-375N	16	3/8"
MC-16-500N	16	1/2"
MC-16-750N	16	3/4"
MC-18-500N	18	1/2"
MC-18-750N	18	3/4"
MC-20-500N	20	1/2"
MC-20-750N	20	3/4"
MC-22-750N	22	3/4"
MC-22-1000N	22	1"
MC-25-500N	25	1/2"
MC-25-750N	25	3/4"
MC-25-1000N	25	1"

Tech Sheet 20281



Male Thread, BSPT

0292	OD mm	Thread
MC-3-125RT	3	1/8"
MC-3-250RT	3	1/4"
MC-4-125RT	4	1/8"
MC-4-250RT	4	1/4"
MC-6-125RT	6	1/8"
MC-6-250RT	6	1/4"
MC-6-375RT	6	3/8"
MC-6-500RT	6	1/2"
MC-8-125RT	8	1/8"
MC-8-250RT	8	1/4"
MC-8-375RT	8	3/8"
MC-8-500RT	8	1/2"
MC-10-125RT	10	1/8"
MC-10-250RT	10	1/4"
MC-10-375RT	10	3/8"
MC-10-500RT	10	1/2"
MC-12-125RT	12	1/8"
MC-12-250RT	12	1/4"
MC-12-375RT	12	3/8"
MC-12-500RT	12	1/2"
MC-12-750RT	12	3/4"
MC-15-500RT	15	1/2"
MC-16-250RT	16	1/4"
MC-16-375RT	16	3/8"
MC-16-500RT	16	1/2"
MC-16-750RT	16	3/4"
MC-18-500RT	18	1/2"
MC-18-750RT	18	3/4"
MC-20-500RT	20	1/2"
MC-20-750RT	20	3/4"
MC-22-750RT	22	3/4"
MC-22-1000RT	22	1"
MC-25-750RT	25	3/4"
MC-25-1000RT	25	1"

Tech Sheet 20278



Male Thread, BSPP (Captive Seal)

0292	OD mm	Thread
OMC-6-125EO	6	1/8"
OMC-6-250EO	6	1/4"
OMC-6-375EO	6	3/8"
OMC-6-500EO	6	1/2"
OMC-10-250EO	10	1/4"
OMC-10-375EO	10	3/8"
OMC-10-500EO	10	1/2"
OMC-12-250EO	12	1/4"
OMC-12-375EO	12	3/8"
OMC-12-500EO	12	1/2"

Tech Sheet 20856



Male Thread-RS, BSPP

0292	OD mm	Thread
MC-3-125RS	3	1/8"
MC-3-250RS	3	1/4"
MC-4-125RS	4	1/8"
MC-6-125RS	6	1/8"
MC-6-250RS	6	1/4"
MC-6-375RS	6	3/8"
MC-6-500RS	6	1/2"
MC-8-125RS	8	1/8"
MC-8-250RS	8	1/4"
MC-8-375RS	8	3/8"
MC-8-500RS	8	1/2"
MC-10-250RS	10	1/4"
MC-10-375RS	10	3/8"
MC-10-500RS	10	1/2"
MC-12-250RS	12	1/4"
MC-12-375RS	12	3/8"
MC-12-500RS	12	1/2"
MC-12-750RS	12	3/4"
MC-16-375RS	16	3/8"
MC-16-500RS	16	1/2"
MC-18-500RS	18	1/2"
MC-18-750RS	18	3/4"
MC-20-500RS	20	1/2"
MC-20-750RS	20	3/4"
MC-22-750RS	22	3/4"
MC-22-1000RS	22	1"
MC-25-750RS	25	3/4"
MC-25-1000RS	25	1"

Tech Sheet 20279

stainless steel



You might also need
Stainless Steel Tubing
see page **183**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Female Connectors



Female Thread, NPT

0292	OD mm	Thread
FC-3-125N	3	1/8"
FC-3-250N	3	1/4"
FC-4-125N	4	1/8"
FC-6-125N	6	1/8"
FC-6-250N	6	1/4"
FC-6-375N	6	3/8"
FC-6-500N	6	1/2"
FC-8-125N	8	1/8"
FC-8-250N	8	1/4"
FC-8-375N	8	3/8"
FC-8-500N	8	1/2"
FC-10-250N	10	1/4"
FC-10-375N	10	3/8"
FC-10-500N	10	1/2"
FC-12-250N	12	1/4"
FC-12-375N	12	3/8"
FC-12-500N	12	1/2"
FC-15-500N	15	1/2"
FC-16-500N	16	1/2"
FC-20-500N	20	1/2"
FC-20-750N	20	3/4"
FC-22-750N	22	3/4"
FC-22-1000N	22	1"
FC-25-750N	25	3/4"
FC-25-1000N	25	1"
Tech Sheet 20275		

Female Thread, BSPT

0292	OD mm	Thread
FC-3-125RT	3	1/8"
FC-6-125RT	6	1/8"
FC-6-250RT	6	1/4"
FC-6-375RT	6	3/8"
FC-6-500RT	6	1/2"
FC-8-125RT	8	1/8"
FC-8-250RT	8	1/4"
FC-8-375RT	8	3/8"
FC-8-500RT	8	1/2"
FC-10-125RT	10	1/8"
FC-10-250RT	10	1/4"
FC-10-375RT	10	3/8"
FC-10-500RT	10	1/2"
FC-12-125RT	12	1/8"
FC-12-250RT	12	1/4"
FC-12-375RT	12	3/8"
FC-12-500RT	12	1/2"
FC-12-750RT	12	3/4"
FC-15-375RT	15	3/8"
FC-15-500RT	15	1/2"
FC-20-500RT	20	1/2"
FC-20-750RT	20	3/4"
FC-22-750RT	22	3/4"
FC-22-1000RT	22	1"
FC-25-750RT	25	3/4"
FC-25-1000RT	25	1"
Tech Sheet 20274		



Female Thread, BSPP

0292	OD mm	Thread
FC-3-250RG	3	1/4"
FC-6-250RG	6	1/4"
FC-6-375RG	6	3/8"
FC-6-500RG	6	1/2"
FC-8-250RG	8	1/4"
FC-8-375RG	8	3/8"
FC-8-500RG	8	1/2"
FC-10-250RG	10	1/4"
FC-10-375RG	10	3/8"
FC-10-500RG	10	1/2"
FC-12-250RG	12	1/4"
FC-12-375RG	12	3/8"
FC-12-500RG	12	1/2"
FC-20-500RG	20	1/2"
FC-22-500RG	22	1/2"
Tech Sheet 20273		

Bulkhead Male Connectors



Male Thread, NPT

0292	OD mm	Thread
BMC-6-125N	6	1/8"
BMC-6-250N	6	1/4"
BMC-8-125N	8	1/8"
BMC-8-250N	8	1/4"
BMC-10-250N	10	1/4"
BMC-10-375N	10	3/8"
BMC-10-500N	10	1/2"
BMC-12-250N	12	1/4"
BMC-12-375N	12	3/8"
BMC-12-500N	12	1/2"
Tech Sheet 20276		

Bulkhead Female Connectors



Female Thread, NPT

0292	OD mm	Thread
BFC-6-125N	6	1/8"
BFC-6-250N	6	1/4"
BFC-8-125N	8	1/8"
BFC-10-250N	10	1/4"
BFC-12-375N	12	3/8"
BFC-12-500N	12	1/2"
Tech Sheet 20277		

For **PTFE Tape** see page **1391**



Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Unions



Tube x Tube

0292	OD mm
U-3	3
U-4	4
U-6	6
U-8	8
U-10	10
U-12	12
U-15	15
U-16	16
U-18	18
U-20-FT	20
U-22	22
U-25	25

Tech Sheet 20266

Reducing Unions



Tube x Tube

0292	OD mm	OD mm
RU-6-3	6	3
RU-6-4	6	4
RU-8-6	8	6
RU-10-6	10	6
RU-10-8	10	8
RU-12-6	12	6
RU-12-8	12	8
RU-12-10	12	10
RU-16-10	16	10
RU-16-12	16	12
RU-18-12	18	12
RU-25-18	25	18
RU-25-20	25	20

Tech Sheet 20267

Bulkhead Unions



Tube x Tube

0292	OD mm
BU-3-FT	3
BU-4	4
BU-6	6
BU-8	8
BU-10	10
BU-12-FT	12
BU-14	14
BU-15	15
BU-16	16
BU-18	18
BU-20	20

Tech Sheet 20272

Male Branch Tees



Male Thread, NPT

0292	OD mm	Thread
MBT-6-125N	6	1/8"
MBT-6-250N	6	1/4"
MBT-8-125N	8	1/8"
MBT-8-250N	8	1/4"
MBT-10-250N	10	1/4"
MBT-12-250N	12	1/4"
MBT-12-375N	12	3/8"
MBT-12-500N	12	1/2"
MBT-16-500N	16	1/2"

Tech Sheet 20269

Male Positionable Branch Tees



Male Thread, BSPP

0292	OD mm	Thread
MBTP-6-125PR	6	1/8"
MBTP-6-250PR	6	1/4"
MBTP-8-125PR	8	1/8"
MBTP-8-250PR	8	1/4"
MBTP-10-250PR	10	1/4"
MBTP-12-375PR	12	3/8"
MBTP-12-500PR	12	1/2"

Tech Sheet 20861

Male Run Tees



Male Thread, NPT

0292	OD mm	Thread
MRT-6-125N	6	1/8"
MRT-6-250N	6	1/4"
MRT-8-250N	8	1/4"
MRT-12-250N	12	1/4"
MRT-12-375N	12	3/8"
MRT-12-500N	12	1/2"
MRT-16-500N	16	1/2"

Tech Sheet 20268

Male Positionable Run Tees



Male Thread, BSPP

0292	OD mm	Thread
MRTP-6-125PR	6	1/8"
MRTP-6-250PR	6	1/4"
MRTP-8-125PR	8	1/8"
MRTP-8-250PR	8	1/4"
MRTP-10-250PR	10	1/4"
MRTP-12-375PR	12	3/8"
MRTP-12-500PR	12	1/2"

Tech Sheet 20863

Female Branch Tees



Female Thread, NPT

0292	OD mm	Thread
FBT-6-125N	6	1/8"
FBT-6-250N	6	1/4"
FBT-8-125N	8	1/8"
FBT-8-250N	8	1/4"
FBT-10-250N	10	1/4"
FBT-12-250N	12	1/4"
FBT-12-375N	12	3/8"
FBT-16-500N	16	1/2"

Tech Sheet 20271

Female Run Tees



Female Thread, NPT

0292	OD mm	Thread
FRT-6-125N	6	1/8"
FRT-6-250N	6	1/4"
FRT-8-125N	8	1/8"
FRT-8-250N	8	1/4"
FRT-10-250N	10	1/4"
FRT-12-250N	12	1/4"
FRT-12-375N	12	3/8"
FRT-16-500N	16	1/2"

Tech Sheet 20270

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Male Elbows



Male Thread, NPT

0292	OD mm	Thread
ME-3-250N	3	1/4"
ME-4-125N	4	1/8"
ME-4-250N	4	1/4"
ME-6-125N	6	1/8"
ME-6-250N	6	1/4"
ME-6-375N	6	3/8"
ME-6-500N	6	1/2"
ME-8-125N	8	1/8"
ME-8-250N	8	1/4"
ME-8-375N	8	3/8"
ME-8-500N	8	1/2"
ME-10-250N	10	1/4"
ME-10-375N	10	3/8"
ME-10-500N	10	1/2"
ME-12-250N	12	1/4"
ME-12-375N	12	3/8"
ME-12-500N	12	1/2"
ME-12-750N	12	3/4"
ME-15-500N	15	1/2"
ME-16-375N	16	3/8"
ME-16-500N	16	1/2"
ME-16-750N	16	3/4"
ME-18-500N	18	1/2"
ME-18-750N	18	3/4"
ME-20-500N	20	1/2"
ME-22-750N	22	3/4"
ME-22-1000N	22	1"
ME-25-750N	25	3/4"
ME-25-1000N	25	1"

Tech Sheet 20264



Male Thread, BSPT

0292	OD mm	Thread
ME-3-125RT	3	1/8"
ME-3-250RT	3	1/4"
ME-4-125RT	4	1/8"
ME-4-250RT	4	1/4"
ME-6-125RT	6	1/8"
ME-6-250RT	6	1/4"
ME-6-375RT	6	3/8"
ME-6-500RT	6	1/2"
ME-8-125RT	8	1/8"
ME-8-250RT	8	1/4"
ME-8-375RT	8	3/8"
ME-8-500RT	8	1/2"
ME-10-250RT	10	1/4"
ME-10-375RT	10	3/8"
ME-10-500RT	10	1/2"
ME-12-250RT	12	1/4"
ME-12-375RT	12	3/8"
ME-12-500RT	12	1/2"
ME-12-750RT	12	3/4"
ME-16-375RT	16	3/8"
ME-16-500RT	16	1/2"
ME-18-500RT	18	1/2"
ME-18-750RT	18	3/4"
ME-20-500RT	20	1/2"
ME-20-750RT	20	3/4"
ME-22-750RT	22	3/4"
ME-22-1000RT	22	1"
ME-25-750RT	25	3/4"
ME-25-1000RT	25	1"

Tech Sheet 20263

Female Elbows



Female Thread, NPT

0292	OD mm	Thread
FE-6-125N	6	1/8"
FE-6-250N	6	1/4"
FE-6-500N	6	1/2"
FE-8-250N	8	1/4"
FE-10-125N	10	1/8"
FE-10-250N	10	1/4"
FE-12-250N	12	1/4"
FE-12-375N	12	3/8"
FE-12-500N	12	1/2"
FE-16-500N	16	1/2"

Tech Sheet 20265

Positionable Elbows



Male Thread, BSPP

0292	OD mm	Thread
MEP-6-125PR	6	1/8"
MEP-6-250PR	6	1/4"
MEP-8-125PR	8	1/8"
MEP-8-250PR	8	1/4"
MEP-10-250PR	10	1/4"
MEP-10-375PR	10	3/8"
MEP-12-250PR	12	1/4"
MEP-12-375PR	12	3/8"
MEP-12-500PR	12	1/2"
MEP-12-750PR	12	3/4"

Tech Sheet 20265

Union Elbows



Tube x Tube

0292	OD mm
UE-3	3
UE-4	4
UE-6	6
UE-8	8
UE-10	10
UE-12	12
UE-14	14
UE-15	15
UE-16	16
UE-18	18
UE-20	20
UE-22	22
UE-25	25

Tech Sheet 20261

Union Tees



Tube x Tube

0292	OD mm
UT-3	3
UT-4	4
UT-6	6
UT-8	8
UT-10	10
UT-12	12
UT-14	14
UT-15	15
UT-16	16
UT-18	18
UT-20	20
UT-22	22
UT-25	25

Tech Sheet 20260

Union Crosses



Tube x Tube

0292	OD mm
UC-3	3
UC-6	6
UC-8	8
UC-10	10
UC-12	12
UC-16	16
UC-18	18
UC-20	20
UC-25	25

Tech Sheet 20262

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Weld Union, Connectors



Tube x Tube

0292	OD mm	Stem OD
MWC-3-125	3	1/8"
MWC-4-125	4	1/8"
MWC-6-125	6	1/8"
MWC-6-250	6	1/4"
MWC-8-125	8	1/8"
MWC-8-250	8	1/4"
MWC-8-500	8	1/2"
MWC-10-250	10	1/4"
MWC-10-500	10	1/2"
MWC-12-250	12	1/4"
MWC-12-375	12	3/8"
MWC-12-500	12	1/2"
MWC-14-375	14	3/8"
MWC-15-500	15	1/2"
MWC-16-500	16	1/2"
MWC-18-500	18	1/2"

Tech Sheet 20873

Port Connectors



Tube x Tube

0292	OD mm
PC-3	3
PC-6	6
PC-8	8
PC-10	10
PC-12-FT	12
PC-15-FT	15
PC-16	16
PC-18-FT	18
PC-20	20
PC-25	25

Tech Sheet 20874

Reducing Port Connectors



Tube x Tube

0292	OD mm	Stem OD mm
RPC-6-3	6	3
RPC-8-6	8	6
RPC-10-6	10	6
RPC-10-8	10	8
RPC-12-6	12	6
RPC-12-8	12	8
RPC-12-10	12	10
RPC-16-12	16	12

Tech Sheet 20875

Reducers



Tube x Tube

0292	OD mm	Stem OD mm
R-3-4	3	4
R-3-6	3	6
R-3-10	3	10
R-4-6	4	6
R-6-3	6	3
R-6-8	6	8
R-6-10	6	10
R-6-12	6	12
R-6-18	6	18
R-8-6	8	6
R-8-10	8	10
R-8-12	8	12
R-10-6	10	6
R-10-12	10	12
R-10-15	10	15
R-10-18	10	18
R-12-6	12	6
R-12-8	12	8
R-12-10	12	10
R-12-16	12	16
R-12-18	12	18
R-12-20	12	20
R-12-22	12	22
R-12-25	12	25
R-16-12	16	12
R-18-12	18	12
R-18-16	18	16
R-18-20	18	20
R-18-22	18	22
R-18-25	18	25
R-20-16	20	16
R-20-22	20	22
R-20-25	20	25
R-22-18	22	18
R-22-20	22	20
R-22-25	22	25
R-25-18	25	18
R-25-20	25	20

Tech Sheet 20258



Metric Tube x Imperial Tube

0292	OD mm	Stem OD
R-3-125	3	1/8"
R-3-250	3	1/4"
R-4-250	4	1/4"
R-6-125	6	1/8"
R-6-250	6	1/4"
R-6-312	6	5/16"
R-6-375	6	3/8"
R-6-500	6	1/2"
R-8-375	8	3/8"
R-8-500	8	1/2"
R-10-375	10	3/8"
R-10-500	10	1/2"
R-12-500	12	1/2"
R-12-750	12	3/4"
R-18-750	18	3/4"
R-25-1000	25	1"

Tech Sheet 20877

Caps



Tube

0292	OD mm
C-3	3
C-4	4
C-6	6
C-8	8
C-10	10
C-12	12
C-14	14
C-15	15
C-16	16
C-18	18
C-20	20
C-22	22
C-25	25

Tech Sheet 20259

FAC
Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Plugs



Tube

0292	OD mm
P-3-FT	3
P-4	4
P-6-FT	6
P-8	8
P-10	10
P-12	12
P-15	15
P-16	16
P-18	18
P-20	20
P-22	22
P-25	25

Tech Sheet 20254

Nuts



Tube

0292	OD mm
N-3	3
N-4	4
N-6	6
N-8	8
N-10	10
N-12	12
N-15	15
N-16	16
N-18	18
N-20	20
N-25	25

Tech Sheet 20255

Back Ferrules



Tube

0292	OD mm
BF-3	3
BF-4	4
BF-6	6
BF-8	8
BF-10	10
BF-12	12
BF-14	14
BF-15	15
BF-16	16
BF-18	18
BF-20	20
BF-22	22
BF-25	25

Tech Sheet 20257

Front Ferrules



Tube

0292	OD mm
FF-3	3
FF-4	4
FF-6	6
FF-8	8
FF-10	10
FF-12	12
FF-14	14
FF-15	15
FF-16	16
FF-18	18
FF-20	20
FF-22	22
FF-25	25

Tech Sheet 20256

Lock Nuts



To suit Bulkheads


0292	OD mm
BLN-3	3
BLN-4	4
BLN-6	6
BLN-8	8
BLN-10-FT	10
BLN-12-FT	12
BLN-14	14
BLN-16-FT	16
BLN-18	18
BLN-20-FT	20

Tech Sheet 20883



For **Needle Valves** see pages **982-983**

Fluid-Air Components Ltd



Metric Hydraulic Tubing

Bright - DIN 2391/C ST37.4, 3 & 6 Metre Lengths
Chrome 6 Free, 3 & 6 Metre Lengths
Chrome 6 Free, 6 Metre Lengths

Imperial Hydraulic Tubing

Imperial - DIN 2391/C ST37.4, 3 & 6 Metre Lengths

Reinforcing Tube Inserts

Manual Tube Benders

316 Stainless Steel Tube

Seamless ASTM A269, Metric, 3 & 6 Metre Lengths
Seamless ASTM A269, Imperial, 3 & 6 Metre Lengths

HYDRAULIC TUBE

METRIC HYDRAULIC TUBING

Hydraulic Tubing

Maximum working pressure has been determined according to DIN 2413 scope of application 1, for primarily static load at temperatures up to 120°C.

3 metre lengths next day.

6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.

For full details please contact our Business Development Team.

Minimum of 10 Lengths is advised up to 8mm to prevent damage in transit.



Bright - DIN 2391/C ST37.4, 3 Metre Lengths

0201	OD mm	Wall Thickness mm	Pressure Kg/cm²
HST4X1.0	4	1.0	624
HST6X1.0	6	1.0	365
HST6X1.5	6	1.5	624
HST6X2.0	6	2.0	989
HST8X2.0	8	2.0	624
HST12X2.5	12	2.5	485
HST14X1.5	14	1.5	217
HST14X2.0	14	2.0	303
HST16X2.5	16	2.5	337
HST18X2.0	18	2.0	226
HST18X2.5	18	2.5	300
HST20X2.5	20	2.5	259
HST20X3.0	20	3.0	321
HST20X3.5	20	3.5	388
HST22X1.5	22	1.5	132
HST22X2.0	22	2.0	181
HST25X1.5	25	1.5	115
HST25X2.0	25	2.0	157
HST25X2.5	25	2.5	201
HST25X3.0	25	3.0	257
HST28X1.5	28	1.5	102
HST28X2.5	28	2.5	177
HST28X3.0	28	3.0	217
HST30X2.5	30	2.5	164
HST30X4.0	30	4.0	279
HST35X2.0	35	2.0	109
HST35X2.5	35	2.5	139
HST35X3.0	35	3.0	169
HST35X5.0	35	5.0	303
HST38X3.0	38	3.0	155
HST38X5.0	38	5.0	275
HST42X3.0	42	3.0	139
HST42X4.0	42	4.0	190

Bright - DIN 2391/C ST37.4, 6 Metre Lengths

0201	OD mm	Wall Thickness mm	Pressure Kg/cm²
HST4X1.0-6M	4	1.0	624
HST6X1.0-6M	6	1.0	365
HST6X1.5-6M	6	1.5	624
HST6X2.0-6M	6	2.0	989
HST8X2.0-6M	8	2.0	624
HST12X2.5-6M	12	2.5	485
HST14X1.5-6M	14	1.5	217
HST14X2.0-6M	14	2.0	303
HST16X2.5-6M	16	2.5	337
HST18X2.0-6M	18	2.0	226
HST18X2.5-6M	18	2.5	300
HST20X2.5-6M	20	2.5	259
HST20X3.0-6M	20	3.0	321
HST20X3.5-6M	20	3.5	388
HST22X1.5-6M	22	1.5	132
HST22X2.0-6M	22	2.0	181
HST25X1.5-6M	25	1.5	115
HST25X2.0-6M	25	2.0	157
HST25X2.5-6M	25	2.5	201
HST25X3.0-6M	25	3.0	247
HST28X1.5-6M	28	1.5	102
HST28X2.5-6M	28	2.5	177
HST28X3.0-6M	28	3.0	217
HST30X2.5-6M	30	2.5	164
HST30X4.0-6M	30	4.0	279
HST35X2.0-6M	35	2.0	109
HST35X2.5-6M	35	2.5	139
HST35X3.0-6M	35	3	169
HST35X5.0-6M	35	5	303
HST38X3.0-6M	38	3.0	155
HST38X5.0-6M	38	5.0	275
HST42X3.0-6M	42	3.0	139
HST42X4.0-6M	42	4	190

See page 181 for chrome 6 free tube

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

METRIC HYDRAULIC TUBING


Hydraulic Tubing

3 metre lengths next day.

6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.

For full details please contact our Business Development Team.

Minimum of 10 Lengths is advised up to 8mm to prevent damage in transit.



Chrome 6 Free, 3 Metre Lengths

0201	OD mm	Wall Thickness mm	Pressure Kg/cm²
HST4X1.0-C6F	4	1	624
HST6X1.0-C6F	6	1	365
HST6X1.5-C6F	6	1.5	624
HST6X2.0-C6F	6	2	989
HST8X1.0-C6F	8	1	259
HST8X1.5-C6F	8	1.5	423
HST8X2.0-C6F	8	2	624
HST10X1.0-C6F	10	1	201
HST10X1.5-C6F	10	1.5	321
HST10X2.0-C6F	10	2	460
HST12X1.0-C6F	12	1	164
HST12X1.5-C6F	12	1.5	259
HST12X2.0-C6F	12	2	365
HST14X1.5-C6F	14	1.5	217
HST14X2.0-C6F	14	2	303
HST15X1.5-C6F	15	1.5	201
HST15X2.0-C6F	15	2	279
HST16X1.5-C6F	16	1.5	187
HST16X2.0-C6F	16	2	259
HST16X2.5-C6F	16	2.5	337
HST16X3.0-C6F	16	3	423
HST18X1.5-C6F	18	1.5	164
HST18X2.0-C6F	18	2	226
HST18X2.5-C6F	18	2.5	300
HST20X2.0-C6F	20	2	201
HST20X2.5-C6F	20	2.5	259
HST20X3.0-C6F	20	3	321
HST20X3.5-C6F	20	3.5	388
HST20X4.0-C6F	20	4	460
HST22X1.5-C6F	22	1.5	132
HST22X2.0-C6F	22	2	181
HST22X2.5-C6F	22	2.5	232
HST25X1.5-C6F	25	1.5	115
HST25X2.0-C6F	25	2	157
HST25X2.5-C6F	25	2.5	201
HST25X3.0-C6F	25	3	247
HST25X4.0-C6F	25	4	347
HST28X1.5-C6F	28	1.5	102
HST28X2.0-C6F	28	2	139
HST28X2.5-C6F	28	2.5	177
HST28X3.0-C6F	28	3	217
HST30X2.5-C6F	30	2.5	164
HST30X3.0-C6F	30	3	201
HST30X4.0-C6F	30	4	279
HST35X2.0-C6F	35	2	109
HST35X2.5-C6F	35	2.5	139
HST35X3.0-C6F	35	3	169
HST35X5.0-C6F	35	5	303
HST38X3.0-C6F	38	3	155
HST38X4.0-C6F	38	4	213
HST42X3.0-C6F	42	3	139
HST42X4.0-C6F	42	4	190
HST50X3.0-C6F	50	3	115
HST50X5.0-C6F	50	5	201
HST50X6.0-C6F	50	6	247

Chrome 6 Free, 6 Metre Lengths

0201	OD mm	Wall Thickness mm	Pressure Kg/cm²
HST10X1.0-C6F-6M	10	1	201
HST10X1.5-C6F-6M	10	1.5	321
HST10X2.0-C6F-6M	10	2	460
HST12X1.0-C6F-6M	12	1	164
HST12X1.5-C6F-6M	12	1.5	259
HST12X2.0-C6F-6M	12	2	365
HST14X1.5-C6F-6M	14	1.5	217
HST14X2.0-C6F-6M	14	2	303
HST15X1.5-C6F-6M	15	1.5	201
HST15X2.0-C6F-6M	15	2	279
HST16X1.5-C6F-6M	16	1.5	187
HST16X2.0-C6F-6M	16	2	259
HST16X2.5-C6F-6M	16	2.5	337
HST16X3.0-C6F-6M	16	3	423
HST18X1.5-C6F-6M	18	1.5	164
HST18X2.0-C6F-6M	18	2	226
HST18X2.5-C6F-6M	18	2.5	392
HST20X2.0-C6F-6M	20	2	201
HST20X2.5-C6F-6M	20	2.5	259
HST20X3.0-C6F-6M	20	3	321
HST20X3.5-C6F-6M	20	3.5	388
HST20X4.0-C6F-6M	20	4	460
HST22X1.5-C6F-6M	22	1.5	132
HST22X2.0-C6F-6M	22	2	181
HST22X2.5-C6F-6M	22	2.5	232
HST25X1.5-C6F-6M	25	1.5	115
HST25X2.0-C6F-6M	25	2	157
HST25X2.5-C6F-6M	25	2.5	232
HST25X3.0-C6F-6M	25	3	247
HST25X4.0-C6F-6M	25	4	347
HST28X1.5-C6F-6M	28	1.5	102
HST28X2.0-C6F-6M	28	2	139
HST28X2.5-C6F-6M	28	2.5	177
HST28X3.0-C6F-6M	28	3	217
HST30X2.5-C6F-6M	30	2.5	164
HST30X3.0-C6F-6M	30	3	201
HST30X4.0-C6F-6M	30	4	279
HST35X2.0-C6F-6M	35	2	109
HST35X2.5-C6F-6M	35	2.5	139
HST35X3.0-C6F-6M	35	3	169
HST35X5.0-C6F-6M	35	5	303
HST38X3.0-C6F-6M	38	3	155
HST38X4.0-C6F-6M	38	4	213
HST42X3.0-C6F-6M	42	3	139
HST42X4.0-C6F-6M	42	4	190
HST50X3.0-C6F-6M	50	3	115
HST50X5.0-C6F-6M	50	5	201
HST50X6.0-C6F-6M	50	6	247

Chrome 6 Free, 6 Metre Lengths, Bundles of 10


0201	OD mm	Wall Thickness mm	Pressure Kg/cm²
HST4X1.0-C6F-6M	4	1	624
HST6X1.0-C6F-6M	6	1	365
HST6X1.5-C6F-6M	6	1.5	624
HST6X2.0-C6F-6M	6	2	989
HST8X1.0-C6F-6M	8	1	259
HST8X1.5-C6F-6M	8	1.5	423
HST8X2.0-C6F-6M	8	2	624

Danfoss Waltech



Hydraulic Fittings
see pages **115-136**

RSB



Hydraulic Tube Clamps
see pages **184-200**

FAC Fluid-Air Components Ltd

IMPERIAL HYDRAULIC TUBING

Hydraulic Tubing


Maximum working pressure has been determined according to DIN 2413 scope of application 1, for primarily static load at temperatures up to 120°C.

3 metre lengths next day.

6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.

For full details please contact our Business Development Team.

Other gauges available on request.



Imperial - DIN 2391/C ST37.4, 3 Metre Lengths

0201	OD	SWG	Max Pressure Bar
HST1/4X16G-3M	1/4"	16	648
HST3/8X16G-3M	3/8"	16	377
HST1/2X16G-3M	1/2"	16	267
HST5/8X16G-3M	5/8"	16	207
HST3/4X16G-3M	3/4"	16	169
HST1X16G-3M	1"	16	124
HST1.1/4X16G-3M	1.1/4"	16	98
HST1.1/2X16G-3M	1.1/2"	16	81

Imperial - DIN 2391/C ST37.4, 6 Metre Lengths

0201	OD	SWG	Max Pressure Bar
HST1/4X16G-6M	1/4"	16	648
HST3/8X16G-6M	3/8"	16	377
HST1/2X16G-6M	1/2"	16	267
HST5/8X16G-6M	5/8"	16	207
HST3/4X16G-6M	3/4"	16	169
HST1X16G-6M	1"	16	124
HST1.1/4X16G-6M	1.1/4"	16	98
HST1.1/2X16G-6M	1.1/2"	16	81

IMPERIAL HYDRAULIC TUBING

Reinforcing Tube Inserts

Danfoss Waltech



For use with Thin Wall Hydraulic Steel Tube

0350	To Fit Tube Size mm	ID mm
EH4MS	6 x 1	4
EH5MS	6 x 0.5	5
EH6MS	8 x 1	6
EH7MS	10 x 1.5	7
EH8MS	10 x 1	8
EH9MS	12 x 1.5	9
EH10MS	12 x 1	10
EH12MS	14 x 1 & 15 x 1.5	12
EH13MS	15 x 1	13
EH15MS	18 x 1.5	15
EH16MS	18 x 1	16
EH18MS	20 x 1	18
EH19MS	22 x 1.5	19
EH20MS	22 x 1	20
EH24MS	28 x 2	24
EH25MS	28 x 1.5	25
	Tech Sheet 1715	

Manual Tube Benders

The tube bender is for use in manual vice.
The kit contains 3 bending dies.
Die 1: 6mm and 8mm tube
Die 2: 10mm tube
Die 3: 12mm tube

Tube Size Bend Radius
6mm 19.5mm
8mm 20.5mm
10mm 25.5mm
12mm 26.5mm
Tolerance +/-2mm



To suit Tube O.D. 6mm-12mm

0027
SBVO-612

The tube bender is for use in manual vice. The kit contains 6 bending dies with O.D. 6mm to 18mm, (1/8" to 3/8").
Die 1: 6mm and 8mm tube
Die 2: 10mm tube
Die 3: 12mm tube
Die 4: 14mm tube
Die 5: 16mm tube
Die 6: 18mm tube



To suit Tube O.D. 6mm-18mm

0027
SBVO-618

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBING

stainless steel

FTI PRO

316 Stainless Steel Tube

3 metre lengths next day.
6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.

For full details please contact our Business Development Team.
Minimum of 10 lengths is advised up to 8mm to prevent damage in transit.



Seamless ASTM A269, Metric, 6 Metre Lengths

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610-6M	6	1	428
765-6X1.5-6M	6	1.5	627
765-0810-6M	8	1	321
765-8X1.5-6M	8	1.5	472
765-1013-6M	10	1	257
765-10X1.5-6M	10	1.5	385
765-12X1.5-6M	12	1.5	321
765-1515-6M	15	1.5	257
765-16X1.5-6M	16	1.5	235
765-1602-6M	16	2	321
765-20X2-6M	20	2	257
765-25X2.5-6M	25	2.5	210
765-30X3-6M	30	3	257
Tech Sheet 831			

PANAM



You might also need...
Stainless Steel Fittings
see pages **165-178**

Seamless ASTM A269, Metric, 3 Metre Lengths, Random

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610	6	1	428
765-6X1.5	6	1.5	627
765-6X2	6	2	942
765-0813	8	1	321
765-8X1.5	8	1.5	472
765-8X2	8	2	706
765-1013	10	1	257
765-10X1.5	10	1.5	385
765-10X2	10	2	564
765-1213	12	1	210
765-12X1.5	12	1.5	321
765-12X2	12	2	420
765-1513	15	1	200
765-15X1.5	15	1.5	257
765-15X2	15	2	376
765-16X1.5	16	1.5	235
765-16X2	16	2	321
765-18X1.5	18	1.5	235
765-18X2	18	2	314
765-20X1.5	20	1.5	212
765-20X2	20	2	257
765-20X3	20	3	424
765-22X1.5	22	1.5	193
765-22X2	22	2	256
765-25X1.5	25	1.5	169
765-25X2	25	2	226
765-25X2.5	25	2.5	210
765-25X3	25	3	339
765-28X2	28	2	201
765-30X3	30	3	257
765-35X3	35	3	242
765-42X3	42	3	201
Tech Sheet 831			

Seamless ASTM A269, Imperial, 3 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372	1/8"	20	718
2020-1380	1/4"	20	360
2020-1406	3/8"	20	240
2020-1414	1/2"	20	180
2020-1422	3/4"	20	120
2020-1430	1"	20	90
Tech Sheet 831			

Seamless ASTM A269, Imperial, 6 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372-6M	1/8"	20	750
2020-1380-6M	1/4"	20	360
2020-1406-6M	3/8"	20	240
2020-1414-6M	1/2"	20	180
2020-1422-6M	3/4"	20	120
2020-1430-6M	1"	20	90
Tech Sheet 831			

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Hydraulic Tube Clamps

Our quality range of Hydraulic Tube Clamps have been manufactured to the highest specifications using quality materials and conforms to DIN 3015 and DIN 3570 Standards.

RSB clamps according to DIN 3015 are **DNV certified**

The vast range includes:

Light, heavy and double units in sizes ranging from 6mm to 168.3mm. Body materials of polypropylene, polyamide, rubber and aluminium, also with plates and bolts in steel (zinc plated) and stainless steel offering anti-corrosion and fire retardant options. U bolts, pipe saddles, steel clamps and O clamps are available.

The range is tried, tested and used extensively throughout the world's manufacturing facilities and in the mobile plant industry.

Applications:

- Hydraulics
- Construction
- Agriculture
- Mining
- OEM Machine Building
- Offshore
- Marine
- Automotive Technology
- Machine Tool
- Lubrication Systems

If you have any requirements for sizes or types of clamps not shown in the catalogue, please contact a member of our sales team.

For tubing
see pages **179-183**



Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c



FAC
Fluid-Air Components Ltd
ef nkl i roi r p
c
c c
a c c

HYDRAULIC TUBE CLAMPS

Series A Light-duty Complete Clamps



Group 0



Group 1-6

Single Polypropylene Clamps with Hex Head Bolts

0162	OD mm	Group
RAPR3-006	6	0
RAPR3-006.4	6.4	0
RAPR3-008	8	0
RAPR3-009.5	9.5	0
RAPR3-010	10	0
RAPR3-012	12	0
RAPR3-106	6	1
RAPR3-106.4	6.4	1
RAPR3-108	8	1
RAPR3-109.5	9.5	1
RAPR3-110	10	1
RAPR3-112	12	1
RAPR3-212.7	12.7	2
RAPR3-213.5	13.5	2
RAPR3-214	14	2
RAPR3-215	15	2
RAPR3-216	16	2
RAPR3-217.2	17.2	2
RAPR3-218	18	2
RAPR3-319	19	3
RAPR3-320	20	3
RAPR3-321.3	21.3	3
RAPR3-322	22	3
RAPR3-323	23	3
RAPR3-325	25	3
RAPR3-426.9	26.9	4
RAPR3-428	28	4
RAPR3-430	30	4
RAPR3-532	32	5
RAPR3-533.7	33.7	5
RAPR3-535	35	5
RAPR3-538	38	5
RAPR3-540	40	5
RAPR3-542	42	5
RAPR3-644.5	44.5	6
RAPR3-645	45	6
RAPR3-648	48	6
RAPR3-650	50	6
RAPR3-650.8	50.8	6
RAPR3-652	52	6
RAPR3-655	55	6
RAPR3-657	57	6

Series B Standard-duty Complete Clamps



Double Polypropylene Clamps with Hex Head Bolts

0162	OD mm	Group
RBPR1-106	6	1
RBPR1-106.4	6.4	1
RBPR1-108	8	1
RBPR1-109.5	9.5	1
RBPR1-110	10	1
RBPR1-112	12	1
RBPR1-212.7	12.7	2
RBPR1-213.5	13.5	2
RBPR1-214	14	2
RBPR1-215	15	2
RBPR1-216	16	2
RBPR1-217.2	17.2	2
RBPR1-218	18	2
RBPR1-319	19	3
RBPR1-320	20	3
RBPR1-321.3	21.3	3
RBPR1-322	22	3
RBPR1-325	25	3
RBPR1-426.9	26.9	4
RBPR1-428	28	4
RBPR1-430	30	4
RBPR1-532	32	5
RBPR1-533.7	33.7	5
RBPR1-535	35	5
RBPR1-538	38	5
RBPR1-540	40	5
RBPR1-542	42	5

Series C Heavy-duty Complete Clamps



Single Polypropylene Clamps with Hex Head Bolts

0162	OD mm	Group
RCPR3-106	6	1
RCPR3-108	8	1
RCPR3-110	10	1
RCPR3-112	12	1
RCPR3-112.7	12.7	1
RCPR3-113.5	13.5	1
RCPR3-114	14	1
RCPR3-115	15	1
RCPR3-116	16	1
RCPR3-117.2	17.2	1
RCPR3-118	18	1
RCPR3-219	19	2
RCPR3-220	20	2
RCPR3-221.3	21.3	2
RCPR3-222	22	2
RCPR3-223	23	2
RCPR3-225	25	2
RCPR3-226.9	26.9	2
RCPR3-228	28	2
RCPR3-230	30	2
RCPR3-330	30	3
RCPR3-332	32	3
RCPR3-333.7	33.7	3
RCPR3-335	35	3
RCPR3-338	38	3
RCPR3-340	40	3
RCPR3-342	42	3
RCPR3-438	38	4
RCPR3-440	40	4
RCPR3-442	42	4
RCPR3-445	45	4
RCPR3-448.3	48.3	4
RCPR3-450	50	4
RCPR3-451	51	4
RCPR3-452	52	4
RCPR3-455	55	4
RCPR3-457	57	4
RCPR3-460.3	60.3	4
RCPR3-463	63	4
RCPR3-465	65	4
RCPR3-470	70	4
RCPR3-570	70	5
RCPR3-573	73	5
RCPR3-575	75	5
RCPR3-576.1	76.1	5
RCPR3-580	80	5
RCPR3-582.5	82.5	5
RCPR3-588.9	88.9	5
RCPR3-590	90	5
RCPR3-6101.6	101.6	6
RCPR3-6114.3	114.3	6
RCPR3-6127	127	6
RCPR3-7130	130	7
RCPR3-7140	140	7
RCPR3-7168.3	168.3	7

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBE CLAMPS



The clamp system for vibration dampening and structure borne noise insulation. Select relevant insert for your tube size and appropriate sized body, for use with all regular plates bolts, etc.

Series A Light-duty Noise Protection Clamp Body

Supplied in pairs



Polypropylene

0162	OD mm	Group
RAPE-4	10	4
RAPE-5	10-12	5
RAPE-6	10-20	6
RAPAE-6	18-30	6
Tech Sheet 10133		

Series C Heavy-duty Noise Protection Clamp Body

Other sizes and materials available on request
Supplied in pairs



Polypropylene

0162	OD mm	Group
RCPE-2	10	2
RCPE-3	10-20	3
RCPE-4	22-35	4
RCPE-5	35-60.3	5
Tech Sheet 10133		

Noise Protection Insert

Other sizes and materials available on request



Group 2 Heavy, Group 4 Light

0162	OD mm	Group
EE-206/406	6	2/4
EE-208/408	8	2/4
EE-210/410	10	2/4
EE-212/412	12	2/4
EE-212.7/412.7	12.7	2/4
EE-214/414	14	2/4
EE-215/415	15	2/4
EE-216/416	16	2/4
EE-217.2/417.2	17.2	2/4
EE-218/418	18	2/4
EE-219/419	19	2/4
Tech Sheet 10133		

Group 3 Heavy, Group 6 Light

0162	OD mm	Group
EE-320/620	20	3/6
EE-321.3/621.3	21.3	3/6
EE-322/622	22	3/6
EE-323/623	23	3/6
EE-325/625	25	3/6
EE-326.9/626.9	26.9	3/6
EE-328/628	28	3/6
EE-330/630	30	3/6
EE-332/632	32	3/6
Tech Sheet 10133		

Group 4 Heavy

0162	OD mm	Group
EE-432	32	4
EE-433.7	33.7	4
EE-435	35	4
EE-438	38	4
EE-440	40	4
EE-442	42	4
EE-445	45	4
EE-448	48	4
EE-451	51	4
EE-453.4	53.4	4
EE-456.4	56.4	4
Tech Sheet 10133		

Noise Protection & Anti-vibration Inserts



Group 2 Heavy, Group 4 Light

0162	OD mm	Group
EFA-410/210	10	2/4
Tech Sheet 10133		

Group 3 Heavy, Group 6 Light

0162	OD mm	Group
EFA-610/310	10	3/6
EFA-612/312	12	3/6
EFA-615/315	15	3/6
EFA-618/318	18	3/6
EFA-620/320	20	3/6
Tech Sheet 10133		

Group 4 Heavy

0162	OD mm	Group
EFA-422	22	4
EFA-425	25	4
EFA-428	28	4
EFA-430	30	4
EFA-435	35	4
Tech Sheet 10133		

Group 5 Light

0162	OD mm	Group
EFA-510	10	5
EFA-512	12	5
EFA-515	15	5
Tech Sheet 10133		

Group 5 Heavy

0162	OD mm	Group
EFA-535	35	5
EFA-538	38	5
EFA-542	42	5
EFA-548.3	48.3	5
EFA-560.3	60.3	5
Tech Sheet 10133		

Group 6 Light

0162	OD mm	Group
EFA-618	18	6
EFA-620	20	6
EFA-622	22	6
EFA-625	25	6
EFA-628	28	6
EFA-630	30	6
Tech Sheet 10133		

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

We have simplified the selection of this clamp range by making it self selection.

Select in the following order.

1. Clamp body by material, series, group and tube size.
2. Weld plate by series and group.
3. Top plate by series and group (not required with slotted head and socket head bolts as they countersink into body).
4. Bolts by series and group.

As a regular feature of Series A and B clamps, screws, rail nuts and cover plates are zinc coated, welding plates phosphatized and support rails uncoated.

As a regular feature of Series C clamps, all steel parts are uncoated.


Please order the **same series** to make complete clamp, i.e. **Series A** clamp, **Series A** top plate and **Series A** bottom plate and **Series A** screws or bolts.



High Pressure Tube Couplings
see pages **138-140**

Series A Light-duty Clamp Halves

Supplied in pairs



Single Polypropylene

0162	OD mm	Group
RAPR-006	6	0
RAPR-006.4	6.4	0
RAPR-008	8	0
RAPR-009.5	9.5	0
RAPR-010	10	0
RAPR-012	12	0
RAPR-106	6	1
RAPR-106.4	6.4	1
RAPR-108	8	1
RAPR-109.5	9.5	1
RAPR-110	10	1
RAPR-112	12	1
RAPR-212.7	12.7	2
RAPR-213.5	13.5	2
RAPR-214	14	2
RAPR-215	15	2
RAPR-216	16	2
RAPR-217.2	17.2	2
RAPR-218	18	2
RAPR-319	19	3
RAPR-320	20	3
RAPR-321.3	21.3	3
RAPR-322	22	3
RAPR-323	23	3
RAPR-325	25	3
RAPR-426.9	26.9	4
RAPR-428	28	4
RAPR-430	30	4
RAPR-532	32	5
RAPR-533.7	33.7	5
RAPR-535	35	5
RAPR-538	38	5
RAPR-540	40	5
RAPR-542	42	5
RAPR-644.5	44.5	6
RAPR-645	45	6
RAPR-648	48	6
RAPR-650	50	6
RAPR-650.8	50.8	6
RAPR-652	52	6
RAPR-655	55	6
RAPR-657	57	6
Tech Sheet 811		

Supplied in pairs



Single Polypropylene Inside Smooth

0162	OD mm	Group
RAPG-106	6	1
RAPG-106.4	6.4	1
RAPG-108	8	1
RAPG-109.5	9.5	1
RAPG-110	10	1
RAPG-112	12	1
RAPG-212.7	12.7	2
RAPG-213.5	13.5	2
RAPG-214	14	2
RAPG-215	15	2
RAPG-216	16	2
RAPG-217.2	17.2	2
RAPG-218	18	2
RAPG-319	19	3
RAPG-320	20	3
RAPG-321.3	21.3	3
RAPG-322	22	3
RAPG-323	23	3
RAPG-325	25	3
RAPG-426.9	26.9	4
RAPG-428	28	4
RAPG-430	30	4
RAPG-532	32	5
RAPG-533.7	33.7	5
RAPG-535	35	5
RAPG-538	38	5
RAPG-540	40	5
RAPG-542	42	5
RAPG-644.5	44.5	6
RAPG-645	45	6
RAPG-648	48	6
RAPG-650	50	6
RAPG-650.8	50.8	6
RAPG-652	52	6
RAPG-655	55	6
RAPG-657	57	6
Tech Sheet 811		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBE CLAMPS

Series A Light-duty Clamp Halves

Supplied in pairs



Single Polyamide 6 Inside Smooth

0162	OD mm	Group
RANG-106	6	1
RANG-106.4	6.4	1
RANG-108	8	1
RANG-109.5	9.5	1
RANG-110	10	1
RANG-112	12	1
RANG-212.7	12.7	2
RANG-213.5	13.5	2
RANG-214	14	2
RANG-215	15	2
RANG-216	16	2
RANG-217.2	17.2	2
RANG-218	18	2
RANG-319	19	3
RANG-320	20	3
RANG-321.3	21.3	3
RANG-322	22	3
RANG-323	23	3
RANG-325	25	3
RANG-426.9	26.9	4
RANG-428	28	4
RANG-430	30	4
RANG-532	32	5
RANG-533.7	33.7	5
RANG-535	35	5
RANG-538	38	5
RANG-540	40	5
RANG-542	42	5
RANG-644.5	44.5	6
RANG-645	45	6
RANG-648	48	6
RANG-650	50	6
RANG-650.8	50.8	6
RANG-652	52	6
RANG-655	55	6
RANG-657	57	6
Tech Sheet 811		

Supplied in pairs



Single Rubber

0162	OD mm	Group
RAVG-106	6	1
RAVG-108	8	1
RAVG-109.5	9.5	1
RAVG-110	10	1
RAVG-112	12	1
RAVG-212.7	12.7	2
RAVG-213.5	13.5	2
RAVG-214	14	2
RAVG-215	15	2
RAVG-216	16	2
RAVG-217.2	17.2	2
RAVG-218	18	2
RAVG-319	19	3
RAVG-320	20	3
RAVG-321.3	21.3	3
RAVG-322	22	3
RAVG-323	23	3
RAVG-325	25	3
RAVG-426.9	26.9	4
RAVG-428	28	4
RAVG-430	30	4
RAVG-532	32	5
RAVG-533.7	33.7	5
RAVG-535	35	5
RAVG-538	38	5
RAVG-540	40	5
RAVG-542	42	5
RAVG-644.5	44.5	6
RAVG-645	45	6
RAVG-648	48	6
RAVG-650	50	6
RAVG-650.8	50.8	6
RAVG-652	52	6
RAVG-655	55	6
RAVG-657	57	6
Tech Sheet 811		

Supplied in pairs



Single Polyamide 6 (Fire Retardant)

0162	OD mm	Group
RANR-006	6	0
RANR-008	8	0
RANR-009.5	9.5	0
RANR-012	12	0
RANR-106	6	1
RANR-106.4	6.4	1
RANR-110	10	1
RANR-112	12	1
RANR-212.7	12.7	2
RANR-214	14	2
RANR-215	15	2
RANR-216	16	2
RANR-217.2	17.2	2
RANR-218	18	2
RANR-320	20	3
RANR-321.3	21.3	3
RANR-325	25	3
RANR-426.9	26.9	4
RANR-532	32	5
RANR-533.7	33.7	5
RANR-538	38	5
RANR-540	40	5
RANR-542	42	5
RANR-644.5	44.5	6
RANR-650.8	50.8	6
Tech Sheet 811		



Supplied in pairs

Single Aluminium

0162	OD mm	Group
RAAR-106	6	1
RAAR-106.4	6.4	1
RAAR-108	8	1
RAAR-109.5	9.5	1
RAAR-110	10	1
RAAR-112	12	1
RAAR-212.7	12.7	2
RAAR-213.5	13.5	2
RAAR-214	14	2
RAAR-215	15	2

0162	OD mm	Group
RAAR-216	16	2
RAAR-217.2	17.2	2
RAAR-218	18	2
RAAR-319	19	3
RAAR-320	20	3
RAAR-321.3	21.3	3
RAAR-322	22	3
RAAR-323	23	3
RAAR-325	25	3
RAAR-426.9	26.9	4

0162	OD mm	Group
RAAR-430	30	4
RAAR-532	32	5
RAAR-533.7	33.7	5
RAAR-535	35	5
RAAR-538	38	5
RAAR-540	40	5
RAAR-542	42	5
RAAR-648	48	6
RAAR-650	50	6
Tech Sheet 811		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBE CLAMPS

Tube Identification System

Tube labelling/identification system
Complete with plastic cover and galvanised steel strap.



Universal Holder

0162	To Suit
UNH	Up to 2.1/2" OD


Tube labelling/identification system
Complete with plastic cover and 100mm welding pin.



Welding Holder


0162	To Suit
SWH	100mm Welding Pin

Clamping Rails



Series A, B & C, Steel

0162	Series	Length Metres	Depth mm
TS11-A/B1	A & B	1	11
TS11-A/B2	A & B	2	11
TS14-A/B1	A & B	1	14
TS14-A/B2	A & B	2	14
TS-C1	C	1	22
TS-C2	C	2	22
Tech Sheet 1640			



Series A, B & C, Stainless Steel

stainless steel

0162	Series	Length Metres	Depth mm
TS11-A/B1-SS	A & B	1	11
TS11-A/B2-SS	A & B	2	11
TS14-A/B1-SS	A & B	1	14
TS14-A/B2-SS	A & B	2	14
TS-C1-SS	C	1	22
TS-C2-SS	C	2	22
Tech Sheet 1640			

Clamping Nuts



Series A, B & C, Chromium VI-Free

0162	Group	Series
TM-A	All A & B1	A & B1
TM-B2	2-5	B
TM-C1	1-3	C
TM-C4	4	C
Tech Sheet 1640		



Series A, B & C, Stainless Steel

stainless steel

0162	Group	Series
TM-A/B1	All A & B1	A & B1
TM-B2-SS	2-5	B
TM-C1-SS	1-3	B
TM-C4-SS	4	C
Tech Sheet 1640		

Special Clamps

Fixing Clamps for 40 x 40mm square cased sensors built to EN 50 025 and 50 037.
The sensors can be adjusted axially and laterally when mounted on support rails.
Accessory materials are Series A, Group 5.



Series A Sensor Clamps

0162	Material
RAPS-540	Polypropylene
RANS-540	Polyamide 6
Tech Sheet 814	

You might also need a
RIDGID® StrutSlayr
see page **1744**



Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Series A Weld Plates



Short Weld Plate, Stainless Steel

stainless steel

0162	Group
APK-A0-SS	0
APK-A1-SS	1
APK-A2-SS	2
APK-A3-SS	3
APK-A4-SS	4
APK-A5-SS	5
APK-A6-SS	6
APK-A7-SS	7
APK-A8-SS	8
Tech Sheet 811	



Short Weld Plate, Steel

0162	Group
APK-A0	0
APK-A1	1
APK-A2	2
APK-A3	3
APK-A4	4
APK-A5	5
APK-A6	6
Tech Sheet 811	



Multiple Weld Plate, Steel

0162	Group	Centres mm
APR-A0	0	-
APR-A1	1	20
APRL-A1	1	20
APR-A2	2	26
APRL-A2	2	26
APR-A3	3	33
APRL-A3	3	33
APR-A4	4	40
APR-A5	5	52
APR-A6	6	66
Tech Sheet 812		



Weld/Screw Plate, Steel

0162	Group
APL-A0	0
APL-A1	1
APL-A2	2
APL-A3	3
APL-A4	4
APL-A5	5
APL-A6	6
Tech Sheet 812	

Weld/Screw Plate, Stainless Steel

stainless steel

0162	Group
APL-A1-SS	1
APL-A2-SS	2
APL-A3-SS	3
APL-A4-SS	4
APL-A5-SS	5
APL-A6-SS	6
Tech Sheet 812	



Twin Weld Plate, Steel

0162	Group	Centres mm
APD-A0	0	-
APD-A1	1	20
APDL-A1	1	20
APD-A2	2	26
APDL-A2	2	26
APD-A3	3	33
APDL-A3	3	33
APD-A5	5	52
APD-A6	6	66
Tech Sheet 812		



You might also need
Hydraulic Tubing
see pages **179-183**

Series A Cover Plates



Single, Steel

0162	Group
DP-A0	0
DP-A1	1
DP-A2	2
DP-A3	3
DP-A4	4
DP-A5	5
DP-A6	6
Tech Sheet 813	

Single, Stainless Steel

stainless steel

0162	Group
DP-A0-SS	0
DP-A1-SS	1
DP-A2-SS	2
DP-A3-SS	3
DP-A4-SS	4
DP-A5-SS	5
DP-A6-SS	6
DP-A7-SS	7
DP-A8-SS	8
Tech Sheet 813	

Series A Locking Plates




Steel

0162	Group
SBR-A	0-6
Tech Sheet 1391	

Stainless Steel

stainless steel

0162	Group
SBR-A-SS	0-6
Tech Sheet 1391	



You might also need
Hydraulic Fittings
see pages **115-135**

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Series A Fixing Bolts



Slotted Head, Steel

0162	Group
SL-A0/A1	0 & 1
SL-A2	2
SL-A3	3
SL-A4	4
SL-A5	5
SL-A6	6
Tech Sheet 813	



Socket Head, Steel

0162	Group
IS-A0/A1	0 & 1
IS-A2	2
IS-A3	3
IS-A4	4
IS-A5	5
IS-A6	6
Tech Sheet 813	



Stacking Head, Steel

0162	Group
AS-A0/A1	0 & 1
AS-A2	2
AS-A3	3
AS-A4	4
AS-A5	5
AS-A6	6
Tech Sheet 1391	

Stacking Head, Stainless Steel

stainless steel

0162	Group
AS-A0/A1-SS	0 & 1
AS-A2-SS	2
AS-A3-SS	3
AS-A4-SS	4
AS-A5-SS	5
AS-A6-SS	6
Tech Sheet 1391	



Hexagon Head, Steel

0162	Group
SSL-A0/A1	0 & 1
SSL-A2	2
SSL-A3	3
SSL-A4	4
SSL-A5	5
SSL-A6	6
SSL-A7	7
Tech Sheet 813	

Hexagon Head, Stainless Steel

stainless steel

0162	Group
SSL-A0/A1-SS	0 & 1
SSL-A2-SS	2
SSL-A3-SS	3
SSL-A4-SS	4
SSL-A5-SS	5
SSL-A6-SS	6
Tech Sheet 813	

Visitec Clamping Nuts, Light Series

The rail nut with loss protection.

The larger flange area prevents the rail nut falling int the rail during installation which is a problem inherent to the traditional design. The new design has a vibration and sound installation function.

The rubber cap has an integrated screw locking device. Fast and easy to install, easy to adjust, especially for vertical installations.

Advantages:

- Vibration and sound insulating function
- Designed especially for vertical installations
- Fast and easy to install
- 40% time savings for installers



Series A, Chromium VI-Free

0162	Group	Series
TM-A/B1VISITEC	All A & B1	A & B1
Tech Sheet 1981		

Series A, Stainless Steel

stainless steel

0162	Group	Series
TM-A/B1SSVISITEC	All A & B1	A & B1
Tech Sheet 1981		

Locking Washers



Series A & B

0162	Group
US-A	1
US-B2	2-5
Tech Sheet 1391	


Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Please order the same series to make complete clamp, i.e. **Series B** clamp and **Series B** top plate and **Series B** bottom plate and **Series B** screws or bolts.

Series B Clamp Halves

Supplied in pairs



Double Polypropylene

0162	OD mm	Group
RBPR-106	6	1
RBPR-106.4	6.4	1
RBPR-108	8	1
RBPR-109.5	9.5	1
RBPR-110	10	1
RBPR-112	12	1
RBPR-212.7	12.7	2
RBPR-213.5	13.5	2
RBPR-214	14	2
RBPR-215	15	2
RBPR-216	16	2
RBPR-217.2	17.2	2
RBPR-218	18	2
RBPR-319	19	3
RBPR-320	20	3
RBPR-321.3	21.3	3
RBPR-322	22	3
RBPR-325	25	3
RBPR-426.9	26.9	4
RBPR-428	28	4
RBPR-430	30	4
RBPR-532	32	5
RBPR-533.7	33.7	5
RBPR-535	35	5
RBPR-538	38	5
RBPR-540	40	5
RBPR-542	42	5
Tech Sheet 1641		

Supplied in pairs



Double Polypropylene Inside Smooth

0162	OD mm	Group
RBPG-106	6	1
RBPG-106.4	6.4	1
RBPG-108	8	1
RBPG-109.5	9.5	1
RBPG-110	10	1
RBPG-112	12	1
RBPG-212.7	12.7	2
RBPG-213.5	13.5	2
RBPG-214	14	2
RBPG-215	15	2
RBPG-216	16	2
RBPG-217.2	17.2	2
RBPG-218	18	2
RBPG-319	19	3
RBPG-320	20	3
RBPG-321.3	21.3	3
RBPG-322	22	3
RBPG-325	25	3
RBPG-426.9	26.9	3
RBPG-428	28	4
RBPG-430	30	4
RBPG-532	32	4
RBPG-533.7	33.7	5
RBPG-535	35	5
RBPG-538	38	5
RBPG-540	40	5
RBPG-542	42	5
Tech Sheet 1641		

Supplied in pairs



Double Polyamide 6 (Fire Retardant)

0162	OD mm	Group
RBNR-106.4	6.4	1
RBNR-109.5	9.5	1
RBNR-212.7	12.7	2
RBNR-213.5	13.5	2
RBNR-214	14	2
RBNR-215	15	2
RBNR-218	18	2
RBNR-320	20	3
RBNR-322	22	3
RBNR-325	25	3
RBNR-428	28	4
RBNR-533.7	33.7	5
RBNR-535	35	5
Tech Sheet 1641		

Supplied in pairs




Double Polyamide 6 Inside Smooth

0162	OD mm	Group
RBNG-106	6	1
RBNG-106.4	6.4	1
RBNG-108	8	1
RBNG-109.5	9.5	1
RBNG-110	10	1
RBNG-112	12	1
RBNG-212.7	12.7	2
RBNG-213.5	13.5	2
RBNG-214	14	2
RBNG-215	15	2
RBNG-216	16	2
RBNG-217.2	17.2	2
RBNG-218	18	2
RBNG-319	19	3
RBNG-320	20	3
RBNG-321.3	21.3	3
RBNG-322	22	3
RBNG-325	25	3
RBNG-426.9	26.9	3
RBNG-428	28	4
RBNG-430	30	4
RBNG-532	32	4
RBNG-533.7	33.7	5
RBNG-535	35	5
RBNG-538	38	5
RBNG-542	42	5
Tech Sheet 1641		



You might also need
Hydraulic Tubing
see pages **179-183**



You might also need
Hydraulic Fittings
see pages **115-135**

FAC
Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Series B Clamp Halves

Supplied in pairs




Double Rubber

0162	OD mm	Group
RBVG-106	6	1
RBVG-106.4	6.4	1
RBVG-108	8	1
RBVG-109.5	9.5	1
RBVG-110	10	1
RBVG-112	12	1
RBVG-212.7	12.7	2
RBVG-213.5	13.5	2
RBVG-214	14	2
RBVG-215	15	2
RBVG-216	16	2
RBVG-217.2	17.2	2
RBVG-218	18	2
RBVG-319	19	3
RBVG-320	20	3
RBVG-321.3	21.3	3
RBVG-322	22	3
RBVG-325	25	3
RBVG-426.9	26.9	4
RBVG-428	28	4
RBVG-430	30	4
RBVG-532	32	5
RBVG-533.7	33.7	5
RBVG-535	35	5
RBVG-538	38	5
RBVG-542	42	5

Tech Sheet 1641

Series B Weld Plates



Short Weld Plate, Steel

0162	Group
AP-B1	1
AP-B2	2
AP-B3	3
AP-B4	4
AP-B5	5

Tech Sheet 1641

Short Weld Plate, Stainless Steel

stainless steel

0162	Group
AP-B1-SS	1
AP-B2-SS	2
AP-B3-SS	3
AP-B4-SS	4
AP-B5-SS	5

Tech Sheet 1641

For illustration purposes only




Multiple Weld Plate, Steel

0162	Group	Centres mm
APR-B1	1	40
APR-B2	2	58
APR-B3	3	72
APR-B4	4	90
APR-B5	5	112

Tech Sheet 1642

Series B Cover Plates



Double, Steel

0162	Group
DP-B1	1
DP-B2	2
DP-B3	3
DP-B4	4
DP-B5	5

Tech Sheet 1643


Double, Stainless Steel

stainless steel

0162	Group
DP-B1-SS	1
DP-B2-SS	2
DP-B3-SS	3
DP-B4-SS	4
DP-B5-SS	5

Tech Sheet 1643

Series B Locking Plates



Steel

0162	Group
SB-B1	1
SB-B2	2-5

Tech Sheet 1644

Series B Fixing Bolts



Socket Head, Steel

0162	Group
IS-B1	1
IS-B2	2
IS-B3	3
IS-B5	5

Tech Sheet 1644



Stacking Head, Steel

0162	Group
AS-B1	1
AS-B2	2
AS-B3	3
AS-B4	4
AS-B5	5

Tech Sheet 1644

Stacking Head, Stainless Steel

stainless steel

0162	Group
AS-B1-SS	1
AS-B2-SS	2
AS-B3-SS	3
AS-B4-SS	4
AS-B5-SS	5

Tech Sheet 1644



Hexagon Head, Steel

0162	Group
SS-B1	1
SS-B2	2
SS-B3	3
SS-B4	4
SS-B5	5

Tech Sheet 1643

Hexagon Head, Stainless Steel

stainless steel

0162	Group
SS-B1-SS	1
SS-B2-SS	2
SS-B3-SS	3


Tech Sheet 1643

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Series C Heavy-duty Clamp Halves

Supplied in pairs



Single Polypropylene

0162	OD mm	Group
RCPR-106	6	1
RCPR-108	8	1
RCPR-110	10	1
RCPR-112	12	1
RCPR-112.7	12.7	1
RCPR-113.5	13.5	1
RCPR-114	14	1
RCPR-115	15	1
RCPR-116	16	1
RCPR-117.2	17.2	1
RCPR-118	18	1
RCPR-219	19	2
RCPR-220	20	2
RCPR-221.3	21.3	2
RCPR-222	22	2
RCPR-223	23	2
RCPR-225	25	2
RCPR-226.9	26.9	2
RCPR-228	28	2
RCPR-230	30	2
RCPR-330	30	3
RCPR-332	32	3
RCPR-333.7	33.7	3
RCPR-335	35	3
RCPR-338	38	3
RCPR-340	40	3
RCPR-342	42	3
RCPR-438	38	4
RCPR-440	40	4
RCPR-442	42	4
RCPR-445	45	4
RCPR-448.3	48.3	4
RCPR-450	50	4
RCPR-451	51	4
RCPR-452	52	4
RCPR-455	55	4
RCPR-457	57	4
RCPR-460.3	60.3	4
RCPR-463	63	4
RCPR-465	65	4
RCPR-470	70	4
RCPR-570	70	5
RCPR-573	73	5
RCPR-575	75	5
RCPR-576.1	76.1	5
RCPR-580	80	5
RCPR-582.5	82.5	5
RCPR-588.9	88.9	5
RCPR-590	90	5
RCPR-6101.6	101.6	6
RCPR-6114.3	114.3	6
RCPR-6127	127	6
RCPR-7130	130	7
RCPR-7140	140	7
RCPR-7168.3	168.3	7
Tech Sheet 1645		

Supplied in pairs



Single Polyamide 6 (Fire Retardant)

0162	OD mm	Group
RCNR-106	6	1
RCNR-108	8	1
RCNR-110	10	1
RCNR-112	12	1
RCNR-112.7	12.7	1
RCNR-113.5	13.5	1
RCNR-114	14	1
RCNR-115	15	1
RCNR-116	16	1
RCNR-117.2	17.2	1
RCNR-118	18	1
RCNR-220	20	2
RCNR-221.3	21.3	2
RCNR-222	22	2
RCNR-223	23	2
RCNR-225	25	2
RCNR-226.9	26.9	2
RCNR-228	28	2
RCNR-230	30	2
RCNR-330	30	3
RCNR-332	32	3
RCNR-333.7	33.7	3
RCNR-335	35	3
RCNR-338	38	3
RCNR-340	40	3
RCNR-342	42	3
RCNR-438	38	4
RCNR-440	40	4
RCNR-442	42	4
RCNR-445	45	4
RCNR-448.3	48.3	4
RCNR-450	50	4
RCNR-451	51	4
RCNR-452	52	4
RCNR-455	55	4
RCNR-457	57	4
RCNR-460.3	60.3	4
RCNR-463	63	4
RCNR-465	65	4
RCNR-470	70	4
RCNR-570	70	5
RCNR-573	73	5
RCNR-575	75	5
RCNR-576.1	76.1	5
RCNR-580	80	5
RCNR-582.5	82.5	5
RCNR-588.9	88.9	5
RCNR-590	90	5
Tech Sheet 1645		

Supplied in pairs



Single Aluminium

0162	OD mm	Group
RCAR-110	10	1
RCAR-220	20	2
RCAR-221.3	21.3	2
RCAR-222	22	2
RCAR-226.9	26.9	2
RCAR-230	30	2
RCAR-330	30	3
RCAR-332	32	3
RCAR-333.7	33.7	3
RCAR-338	38	3
RCAR-340	40	3
RCAR-448.3	48.3	4
RCAR-450	50	4
RCAR-455	55	4
RCAR-460.3	60.3	4
RCAR-470	70	4
Tech Sheet 1645		


Please order the same series to make complete clamp, i.e. Series C Clamp & Series C Top Plate & Series C Bottom Plate & Series C Screws or Bolts.

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBE CLAMPS

Series C Heavy-duty Clamp Halves

Supplied in pairs



Single Polypropylene Inside Smooth

0162	OD mm	Group
RCPG-106	6	1
RCPG-108	8	1
RCPG-110	10	1
RCPG-112	12	1
RCPG-112.7	12.7	1
RCPG-114	14	1
RCPG-115	15	1
RCPG-116	16	1
RCPG-117.2	17.2	1
RCPG-118	18	1
RCPG-219	19	2
RCPG-220	20	2
RCPG-221.3	21.3	2
RCPG-222	22	2
RCPG-225	25	2
RCPG-226.9	26.9	2
RCPG-230	30	2
RCPG-330	30	3
RCPG-332	32	3
RCPG-333.7	33.7	3
RCPG-335	35	3
RCPG-338	38	3
RCPG-340	40	3
RCPG-342	42	3

0162	OD mm	Group
RCPG-438	38	4
RCPG-440	40	4
RCPG-442	42	4
RCPG-445	45	4
RCPG-448.3	48.3	4
RCPG-450	50	4
RCPG-452	52	4
RCPG-455	55	4
RCPG-457	57	4
RCPG-460.3	60.3	4
RCPG-465	65	4
RCPG-470	70	4
RCPG-560.3	60.3	5
RCPG-573	73	5
RCPG-576.1	76.1	5
RCPG-580	80	5
RCPG-588.9	88.9	5
RCPG-6100	100	6
RCPG-6101.6	101.6	6
RCPG-6114.3	114.3	6
RCPG-7108	108	7
RCPG-7168.3	168.3	7
RCPG-8168.3	168.3	8
	Tech Sheet 1645	

You might also need
Hydraulic Ball Valves
see pages **238-240**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC TUBE CLAMPS

Series C Weld Plates



Short Weld Plate, Steel

0162	Group
AP-C1	1
AP-C2	2
AP-C3	3
AP-C4	4
AP-C5	5
AP-C6	6
AP-C7	7
Tech Sheet 1646	

Short Weld Plate, Stainless Steel

stainless steel

0162	Group
AP-C1-SS	1
AP-C2-SS	2
AP-C3-SS	3
AP-C4-SS	4
AP-C5-SS	5
AP-C6-SS	6
AP-C7-SS	7
AP-C8-SS	8
Tech Sheet 1646	



Weld/Screw Plate, Steel

0162	Group
APL-C1	1
APL-C2	2
APL-C3	3
APL-C4	4
APL-C5	5
Tech Sheet 1646	



Short Double Weld Plate, Steel

0162	Group
APD-C1	1
APD-C2	2
APD-C3	3
APD-C5	5
Tech Sheet 1646	

Series C Cover Plates



Single, Steel

0162	Group
DP-C1	1
DP-C2	2
DP-C3	3
DP-C4	4
DP-C5	5
DP-C6	6
DP-C7	7
Tech Sheet 1647	

Single, Stainless Steel

stainless steel

0162	Group
DP-C1-SS	1
DP-C2-SS	2
DP-C3-SS	3
DP-C4-SS	4
DP-C5-SS	5
DP-C6-SS	6
DP-C7-SS	7
DP-C8-SS	8
Tech Sheet 1647	



Double, Steel

0162	Group
DPD-C1	1
DPD-C2	2
DPD-C3	3
DPD-C4	4
DPD-C5	5
Tech Sheet 1647	

Series C Locking Plates



Steel

0162	Group
SP-C1	1
SP-C2	2
SP-C3	3
SP-C4	4
SP-C5	5
Tech Sheet 1648	

Stainless Steel

stainless steel

0162	Group
SP-C1-SS	1
SP-C2-SS	2
SP-C3-SS	3
SP-C4-SS	4
SP-C5-SS	5
SP-C6-SS	6
SP-C7-SS	7
SP-C8-SS	8
Tech Sheet 1648	

Series C Fixing Bolts



Socket Head, Steel

0162	Group
IS-C1	1
IS-C2	2
IS-C3	3
IS-C4	4
IS-C5	5
Tech Sheet 1648	



Stacking Head, Steel

0162	Group
AS-C1	1
AS-C2	2
AS-C3	3
AS-C4	4
AS-C5	5
Tech Sheet 1648	

Stacking Head, Stainless Steel

stainless steel

0162	Group
AS-C1-SS	1
AS-C2-SS	2
AS-C3-SS	3
AS-C4-SS	4
Tech Sheet 1648	



Hexagon Head, Steel

0162	Group
SS-C1	1
SS-C2	2
SS-C3	3
SS-C4	4
SS-C5	5
SS-C6	6
SS-C7	7
Tech Sheet 1647	

Hexagon Head, Stainless Steel

stainless steel

0162	Group
SS-C1-SS	1
SS-C2-SS	2
SS-C3-SS	3
SS-C4-SS	4
SS-C5-SS	5
Tech Sheet 1647	

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

U-Bolt Clamps

DIN 3570



2 Nuts Steel Clamps

0162	Size mm
RUBS-15/24	15-24
RUBS-20/30	20-30
RUBS-25/38	25-38
RUBS-32/46	32-46
RUBS-40/52	40-52
RUBS-50/64	50-64
RUBS-65/82	65-82
RUBS-80/94	80-94
RUBS-100/120	100-120
RUBS-125/148	125-148
RUBS-150/176	150-176
Tech Sheet 1650	

DIN 3570 **Bolts:** Zinc Plated

2 Nuts Zinc Plated Steel Clamps

0162	Size mm
RUBZ-15/24	15-24
RUBZ-20/30	20-30
RUBZ-25/38	25-38
RUBZ-32/46	32-46
RUBZ-40/52	40-52
RUBZ-50/64	50-64
RUBZ-65/82	65-82
RUBZ-80/94	80-94
RUBZ-100/120	100-120
RUBZ-150/176	150-176
RUBZ-175/202	175-202
RUBZ-250/282	250-282
Tech Sheet 1650	



4 Nuts Steel Clamps

0162	Size mm
RUBLS-15/24	15-24
RUBLS-20/30	20-30
RUBLS-25/38	25-38
RUBLS-32/46	32-46
RUBLS-50/64	50-64
RUBLS-65/82	65-82
RUBLS-80/94	80-94
RUBLS-100/120	100-120
RUBLS-125/148	125-148
Tech Sheet 1650	

Bolts: Zinc Plated

4 Nuts Zinc Plated Steel Clamps

0162	Size mm
RUBLZ-20/30	20-30
RUBLZ-32/46	32-46
RUBLZ-50/64	50-64
RUBLZ-65/82	65-82
RUBLZ-80/94	80-94
RUBLZ-100/120	100-120
RUBLZ-125/148	125-148
Tech Sheet 1650	

Pipe Saddles



Long Polypropylene

0162	Size mm
KUPL-15/17.2	15-17.2
KUPL-15/21.3	15-21.3
KUPL-20/25	20-25
KUPL-20/26.9	20-26.9
KUPL-25/30	25-30
KUPL-25/33.7	25-33.7
KUPL-32/38	32-38
KUPL-32/42.4	32-42.4
KUPL-40/44.5	40-44.5
KUPL-40/48.3	40-48.3
KUPL-50/57	50-57
KUPL-50/60.3	50-60.3
KUPL-65/76.1	65-76.1
KUPL-80/88.9	80-88.9
KUPL-100/108	100-108
KUPL-100/114.3	100-114.3
Tech Sheet 1651	



Long Polyamide 6 (Fire Retardant)

0162	Size mm
KUNL-20/25	20-25
KUNL-20/26.9	20-26.9
KUNL-25/30	25-30
KUNL-25/33.7	25-33.7
KUNL-32/38	32-38
KUNL-40/44.5	40-44.5
KUNL-40/48.3	40-48.3
KUNL-50/57	50-57
KUNL-50/60.3	50-60.3
KUNL-65/76.1	65-76.1
KUNL-80/88.9	80-88.9
KUNL-100/108	100-108
KUNL-100/114.3	100-114.3
Tech Sheet 1651	

Cylinder Tube Fastenings






Supports

0162	Group
RLP-16	16
RLP-22	22
Tech Sheet 1649	

NOTE: To suit all cylinder tube fastenings.



Adaptor

0162
ADP
Tech Sheet 1649

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Hydraulic Steel Clamps

The support-block is welded to the machine body or another component either in upend or flat position
The tube clamp is screwed on.



HRS Series Clamps

0162	To Fit Tube Size mm
HSRS-25	25
HSRS-30	30
HSRS-35	35
HSRS-38	38
HSRS-42	42
Tech Sheet 1653	

Improved quality as regards noise and vibration reduction.
Safe fastening method even for very sensitive tube and hose lines.
Only one clamp for different diameters.



Elastomer Inlay

0162	To Fit Tube Size mm
EE25-12	25 x 12
EE25-15	25 x 15
EE30-20	30 x 20
EE35-25	35 x 25
EE42-30	42 x 30
Tech Sheet 1653	

Cover to suit Double Clamps



Galvanised Steel

0162	Group
DP-01	1
DP-02	2
DP-03	3
DP-04	4
Tech Sheet 1655	

Flat Tube Clamps

DIN 3570



Steel

0162	NB mm
FRDS-20A	20
FRDS-22A	22
FRDS-25A	25
FRDS-27A	27
FRDS-30A	30
FRDS-34A	34
FRDS-38A	38
FRDS-43A	43
FRDS-45A	45
FRDS-49A	49
FRDS-57A	57
FRDS-61A	61
FRDS-77A	77
FRDS-89A	89
FRDS-108A	108
FRDS-115A	115
FRDS-133A	133
FRDS-169A	169
Tech Sheet 1654	



Galvanised Steel

0162	NB mm
FRDZ-22A	22
FRDZ-25A	25
FRDZ-30A	30
FRDZ-34A	34
FRDZ-38A	38
FRDZ-43A	43
FRDZ-45A	45
FRDZ-49A	49
FRDZ-57A	57
FRDZ-61A	61
FRDZ-77A	77
FRDZ-89A	89
FRDZ-115A	115
FRDZ-159A	159
FRDZ-169A	169
FRDZ-194A	194
FRDZ-220A	220
Tech Sheet 1654	

Fluid-Air Components Ltd

HYDRAULIC TUBE CLAMPS

Series O Clamps

Areas of Application: Pneumatics, automotive technology, machine tool industry, lubrication and naval technology.



Single Polypropylene

0162	OD mm	Group
ROP-106	6	1
ROP-106.4	6.4	1
ROP-108	8	1
ROP-208	8	2
ROP-209.5	9.5	2
ROP-210	10	2
ROP-212	12	2
ROP-212.7	12.7	2
ROP-310	10	3
ROP-312	12	3
ROP-312.7	12.7	3
ROP-313.5	13.5	3
ROP-314	14	3
ROP-315	15	3
ROP-316	16	3
ROP-415	15	4
ROP-416	16	4
ROP-417.2	17.2	4
ROP-418	18	4
ROP-419	19	4
ROP-420	20	4
ROP-421.3	21.3	4
ROP-422	22	4
Tech Sheet 1655		



Single Polyamide 6 (Fire Retardant)

0162	OD mm	Group
RON-106	6	1
RON-106.4	6.4	1
RON-108	8	1
RON-208	8	2
RON-209.5	9.5	2
RON-210	10	2
RON-212	12	2
RON-212.7	12.7	2
RON-312	12	3
RON-312.7	12.7	3
RON-313.5	13.5	3
RON-314	14	3
RON-315	15	3
RON-316	16	3
RON-414	14	4
RON-415	15	4
RON-416	16	4
RON-417.2	17.2	4
RON-418	18	4
RON-419	19	4
RON-420	20	4
RON-421.3	21.3	4
RON-422	22	4
Tech Sheet 1655		



Double Polypropylene

0162	OD mm	Group
ROPD-106	6	1
ROPD-106.4	6.4	1
ROPD-108	8	1
ROPD-208	8	2
ROPD-209.5	9.5	2
ROPD-210	10	2
ROPD-212	12	2
ROPD-212.7	12.7	2
ROPD-310	10	3
ROPD-312	12	3
ROPD-312.7	12.7	3
ROPD-313.5	13.5	3
ROPD-314	14	3
ROPD-315	15	3
ROPD-316	16	3
ROPD-414	14	4
ROPD-415	15	4
ROPD-416	16	4
ROPD-417.2	17.2	4
ROPD-418	18	4
ROPD-419	19	4
ROPD-420	20	4
ROPD-421.3	21.3	4
ROPD-422	22	4
Tech Sheet 1655		



Double Polyamide 6 (Fire Retardant)

0162	OD mm	Group
ROND-106	6	1
ROND-106.4	6.4	1
ROND-108	8	1
ROND-208	8	2
ROND-209.5	9.5	2
ROND-210	10	2
ROND-212	12	2
ROND-212.7	12.7	2
ROND-310	10	3
ROND-312	12	3
ROND-312.7	12.7	3
ROND-313.5	13.5	3
ROND-314	14	3
ROND-315	15	3
ROND-316	16	3
ROND-414	14	4
ROND-415	15	4
ROND-416	16	4
ROND-417.2	17.2	4
ROND-418	18	4
ROND-419	19	4
ROND-420	20	4
ROND-421.3	21.3	4
ROND-422	22	4
Tech Sheet 1655		


Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

MULTICLAMP


Multiclamp is a system of components, each one engineered to a high standard, that together build to provide effective, all purpose pipe work clamping. Available in a single, double and multiple hole clamps across 3 sizes, each with a range of split bushes allowing the clamping of hose or pipe with diameters from 6mm up to 50mm.

Features

- High quality pipe clamping system in 3 ranges Series 10, 16, 32
- Covers a range from 6mm up to 50mm
- 26 different diameter, high quality split rubber bushes
- Plated steel construction with anti-corrosive, full passivate
- Stainless steel option available upon request



Series 10



Steel Clamp Body

0045	Type	Box Quantity
MC101	Single Clamp	10
MC102	Double Clamp	10
MC1016	16 Bay Clamp	1
Tech Sheet 10178		



Split Bushes


0045	OD mm	OD	Box Quantity
MCG105	8	5/16"	10
MCG106	10	3/8"	10
MCG108	12-14	1/2"	10
MCG1010	15-16	5/8"	10
MCG1012	18-20	3/4"	10
Tech Sheet 10178			



Clamp Components

0045	Type	Box Quantity
MCN10	Stacking Nut	50
MCS10	Stacking Stud	50
MCWP10	Weld Plate	10
MCSB10	Standard Bolt	50
Tech Sheet 10178		

Series 16



Steel Clamp Body

0045	Type	Box Quantity
MC161	Single Clamp	10
MC162	Double Clamp	10
MC1612	12 Bay Clamp	1
Tech Sheet 10178		



Split Bushes


0045	OD mm	OD	Box Quantity
MCG164	6	1/4"	10
MCG166	10	3/8"	10
MCG168	12-14	1/2"	10
MCG1610	15-16	5/8"	10
MCG1612	18-20	3/4"	10
MCG1614	22	7/8"	10
MCG1616	25	1"	10
MCG1618	28	-	10
Tech Sheet 10178			



Clamp Components

0045	Type	Box Quantity
MCN16	Stacking Nut	50
MCS10	Stacking Stud	50
MCWP10	Weld Plate	10
MCSB10	Standard Bolt	50
Tech Sheet 10178		

Series 32




Steel Clamp Body

0045	Type	Box Quantity
MC321	Single Clamp	10
MC322	Double Clamp	10
MC3216	16 Bay Clamp	1
Tech Sheet 10178		



Split Bushes

0045	OD mm	OD	Box Quantity
MCG326	10	3/8"	10
MCG328	12-14	1/2"	10
MCG3210	15-16	5/8"	10
MCG3212	18-20	3/4"	10
MCG3214	22	7/8"	10
MCG3218	28	-	10
MCG3220	32-34	1.1/4"	10
MCG3224	35-38	1.1/4"	10
MCG3226	42	-	10
MCG3232	50	2"	10
Tech Sheet 10178			




Clamp Components

0045	Type	Box Quantity
MCN32	Stacking Nut	50
MCS32	Stacking Stud	50
MCWP32	Weld Plate	10
MCSB32	Standard Bolt	50
Tech Sheet 10178		

FAC
Fluid-Air Components Ltd

CETOP Directional Control Valves

FT PRO®



FAC
Fluid-Air Components Ltd
efnkl iroirp c cc a cc

CETOP DIRECTIONAL CONTROL VALVES

CETOP 3, Single Solenoid

Max Flow Rate: 80 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 3
DIN 24340 Size 6
IP65

Working Temperature:
-20°C to +70°C


Maximum Working Pressure:
350 bar





2 Position, All Ports Closed, Spring Offset to Centre

0451	Model	Voltage
1010-1047	ADC 3 2EY/RX14/AC110N9K	110V AC
1010-1046	ADC 3 2EY/RX14/DC24N9K	24V DC
	Tech Sheet 10682	



2 Position, Spring Offset, Open Transient

0451	Model	Voltage
1010-1045	ADC 3 2CY/RX14/AC110N9K	110V AC
1010-1044	ADC 3 2CY/RX14/DC24N9K	24V DC
	Tech Sheet 10682	



2 Position, All Ports Open, Spring Offset to Centre

0451	Model	Voltage
1010-1000	ADC 3 2HY/RX14/AC110N9K	110V AC
1010-1001	ADC 3 2HY/RX14/DC24N9K	24V DC
1010-1059	ADC 3 2HY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	



2 Position, Spring Offset End to End

0451	Model	Voltage
1010-1002	ADC 3 2DY/RX14/AC110N9K	110V AC
1010-1003	ADC 3 2DY/RX14/DC24N9K	24V DC
1010-1058	ADC 3 2DY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	

You might also need
CETOP 3 Manifold
see page **208**



Fluid-Air Components Ltd

CETOP DIRECTIONAL CONTROL VALVES

CETOP 3, Double Solenoid

Max Flow Rate: 80 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 3
DIN 24340 Size 6
IP65

Working Temperature:
-20°C to +70°C


Maximum Working Pressure:
350 bar






3 Position, All Ports Open, Spring Centred

0451	Model	Voltage
1010-1004	ADC 3 3HY/RX14/AC110N9K	110V AC
1010-1006	ADC 3 3HY/RX14/DC24N9K	24V DC
1010-1005	ADC 3 3HY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	




3 Position, All Ports Closed, Spring Centred

0451	Model	Voltage
1010-1007	ADC 3 3EY/RX14/AC110N9K	110V AC
1010-1008	ADC 3 3EY/RX14/DC24N9K	24V DC
1010-1060	ADC 3 3EY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	



3 Position, A, B & T Connected, Spring Centred

0451	Model	Voltage
1010-1009	ADC 3 3JY/RX14/AC110N9K	110V AC
1010-1010	ADC 3 3JY/RX14/DC24N9K	24V DC
1010-1062	ADC 3 3JY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	



3 Position, P & T Connected A & B Blocked, Spring Centred

0451	Model	Voltage
1010-1011	ADC 3 3GY/RX14/AC110N9K	110V AC
1010-1012	ADC 3 3GY/RX14/DC24N9K	24V DC
1010-1061	ADC 3 3GY/RX14/DC12N9K	12V DC
	Tech Sheet 10682	



2 Position, Detent

0451	Model	Voltage
1010-1013	ADC 3 2DD/RX14/AC110N9K	110V AC
1010-1014	ADC 3 2DD/RX14/DC24N9K	24V DC
	Tech Sheet 10682	

Fluid-Air Components Ltd

CETOP DIRECTIONAL CONTROL VALVES


CETOP 5, Single Solenoid

Max Flow Rate: 120 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 5
DIN 24340 Size 10
IP65

Working Temperature:
-20°C to +70°C


Maximum Working Pressure:
315 bar





2 Position, Spring Offset End to End

0451	Model	Voltage
1010-1015	ADC 5 2DY/RX14/AC110N9K	110V AC
1010-1016	ADC 5 2DY/RX14/DC24N9K	24V DC
1010-1063	ADC 5 2DY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	



2 Position, All Ports Open, Spring Offset to Centre

0451	Model	Voltage
1010-1069	ADC 5 2HY/RX14/DC24N9K	24V DC
1010-1064	ADC 5 2HY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	



2 Position, A, B & T Connected, Spring Return

0451	Model	Voltage
1010-1071	ADC 5 2JY/RX14/DC12N9K	12V DC
1010-1072	ADC 5 2JY/RX14/DC24N9K	24V DC
	Tech Sheet 10683	

Replacement Coils



CETOP 3

0451	Voltage
1010-1036	110V AC
1010-1037	220V AC
1010-1038	12V DC
1010-1039	24V DC
	Tech Sheet 10683



CETOP 5

0451	Voltage
1010-1040	110V AC
1010-1041	220V AC
1010-1042	12V DC
1010-1043	24V DC
	Tech Sheet 10683

Fluid-Air Components Ltd


CETOP DIRECTIONAL CONTROL VALVES

CETOP 5, Double Solenoid

Max Flow Rate: 120 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 5
DIN 24340 Size 10
IP65

Working Temperature:
-20°C to +70°C


Maximum Working Pressure:
315 bar





3 Position, All Ports Open, Spring Centred

0451	Model	Voltage
1010-1070	ADC 5 3HY/RX14/DC24N9K	24V DC
1010-1067	ADC 5 3HY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	



3 Position, All Ports Closed, Spring Centred

0451	Model	Voltage
1010-1017	ADC 5 3EY/RX14/AC110N9K	110V AC
1010-1018	ADC 5 3EY/RX14/DC24N9K	24V DC
1010-1065	ADC 5 3EY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	




3 Position, A, B & T Connected, Spring Centred

0451	Model	Voltage
1010-1019	ADC 5 3JY/RX14/AC110N9K	110V AC
1010-1020	ADC 5 3JY/RX14/DC24N9K	24V DC
1010-1068	ADC 5 3JY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	



3 Position, P & T Connected A & B Blocked, Spring Centred

0451	Model	Voltage
1010-1056	ADC 5 3GY/RX14/AC110N9K	110V AC
1010-1021	ADC 5 3GY/RX14/DC24N9K	24V DC
1010-1066	ADC 5 3GY/RX14/DC12N9K	12V DC
	Tech Sheet 10683	



2 Position, Detented

0451	Model	Voltage
1010-1055	ADC 5 2DD/RX14/AC110N9K	110V AC
1010-1054	ADC 5 2DD/RX14/DC24N9K	24V DC
	Tech Sheet 10683	

Fluid-Air Components Ltd


CETOP DIRECTIONAL CONTROL VALVES

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 350 bar

Max Flow Rate: 80 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 3
DIN 24340 Size 6


CETOP 3 Sandwich Valves






Flow Restrictor

0451	Model	Type
1010-1022	AFR 3 X2/RX14/2Q	A & B Meter In
1010-1023	AFR 3 Y2/RX14/2Q	A & B Meter Out
1010-1053	AFR 3 Z P2/RX14/2Q	P Line
	Tech Sheet 10682	






Pilot Operated Check

0451	Model	Type
1010-1024	APOC 3 A1/RX14/N	Single
1010-1025	APOC 3 AB1/RX14/	Double
	Tech Sheet 10682	



Direct Operated Check


0451	Model	Cracking Pressure Bar
1010-1052	ADOC 3 PA/RX14/	0.5
	Tech Sheet 10682	





Pressure Reducing


0451	Model	Pressure Range Bar
1010-1026	ARD 3 PP 2/RX14/75	3.5 - 75
1010-1027	ARD 3 PP 2/RX14/150	10 - 150
1010-1028	ARD 3 PP 2/RX14/210	20 - 210
	Tech Sheet 10682	





Single Line Pressure Relief

0451	Model	Pressure Range Bar
1010-1050	ASPR 3 PT1/RX14/100	3 - 100
1010-1029	ASPR 3 PT1/RX14/200	10 - 200
1010-1030	ASPR 3 PT1/RX14/315	50 - 315
	Tech Sheet 10682	



Dual Line Pressure Relief


0451	Model	Pressure Range Bar
1010-1051	ADPR 3 AT1 BT1/RX14/200	10 - 200
	Tech Sheet 10682	

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 315 bar

Max Flow Rate; 80 L/min
Viscosity 2.8-100 mm²/s
ISO 4401 Size 5
DIN 24340 Size 10


CETOP 5 Sandwich Valves





Flow Restrictor


0451	Model	Type
1010-1031	AFR 5 Y2/RX14/2Q	A & B Meter Out
1010-1057	AFR 5 X2/RX14/2Q	A & B Meter In
	Tech Sheet 10683	





Pilot Operated Check


0451	Model	Type
1010-1032	APOC 5 AB1/RX14	Double
	Tech Sheet 10683	





Pressure Reducing

0451	Model	Pressure Range Bar
1010-1033	ARD 5 PP 2/RX14/200	8.5 - 200
1010-1034	ARD 5 PP 2/RX14/315	8.5 - 315
	Tech Sheet 10683	





Single Line Pressure Relief

0451	Model	Pressure Range Bar
1010-1035	ASPR 5 PT1/RX14/315	8.5 - 315
	Tech Sheet 10683	

Fluid-Air Components Ltd

CETOP MANIFOLD & AUXILIARY PLATES

FT PRO

CETOP 3, Steel Manifold

Maximum Working Pressure:
345 bar



Ports: P & T 1/2", A & B 3/8" BSPP

0345	No of Stations
CM3-1G	1
CM3-2G	2
CM3-3G	3
CM3-4G	4
CM3-5G	5
CM3-6G	6

Tech Sheet 10041

CETOP 3, Steel Manifold with Pressure Relief Valve

Maximum Working Pressure:
345 bar



Ports: P & T 1/2", A & B 3/8" BSPP, 60-250 bar

0345	No of Stations
CM3-1G-ADJ	1
CM3-2G-ADJ	2
CM3-3G-ADJ	3
CM3-4G-ADJ	4
CM3-5G-ADJ	5
CM3-6G-ADJ	6

Tech Sheet 10041

CETOP 3, Aluminium Manifold

Maximum Working Pressure:
207 bar



Ports: P & T 1/2", A & B 3/8" BSPP

0345	No of Stations
CM3-1G/ALU	1
CM3-2G/ALU	2
CM3-3G/ALU	3
CM3-4G/ALU	4
CM3-5G/ALU	5
CM3-6G/ALU	6

Tech Sheet 10041

CETOP 5, Steel Manifold

Maximum Working Pressure:
345 bar



Ports: P 3/4" & T 1", A & B 1/2" BSPP

0345	No of Stations
CM5-1G	1
CM5-2G	2
CM5-3G	3
CM5-4G	4
CM5-5G	5
CM5-6G	6

Tech Sheet 10130

CETOP 5, Steel Manifold with Pressure Relief Valve

Maximum Working Pressure:
345 bar



Ports: P 3/4" & T 1", A & B 1/2" BSPP, 60-250 bar

0345	No of Stations
CM5-1G-ADJ	1
CM5-2G-ADJ	2
CM5-3G-ADJ	3
CM5-4G-ADJ	4
CM5-5G-ADJ	5
CM5-6G-ADJ	6

Tech Sheet 10130

CETOP 3, Side Entry Subplate

Maximum Working Pressure:
345 bar



BSPP

0345	Thread
CSP-03	3/8"

Tech Sheet 10041

CETOP 5, Side Entry Subplate



BSPP

0345	Thread
CSP-05	1/2"

Tech Sheet 10130

Auxiliary Plates



CETOP 3

0345	Type
CBP-03	Blanking Plate
CCOP-PA-03	Cross Over Plate P-A
CCOP-PB-03	Cross Over Plate P-B
CTP-AB-03	Tapping Plate A & B
CTP-PT-03	Tapping Plate P & T

Tech Sheet 10041



CETOP 5

0345	Type
CBP-05	Blanking Plate
CCOP-PA-05	Cross Over Plate P-A
CCOP-PB-05	Cross Over Plate P-B
CTP-AB-05	Tapping Plate A & B
CTP-PT-05	Tapping Plate P & T

Tech Sheet 10130

FAC
Fluid-Air Components Ltd



Solenoid Operated Directional Valve

DG4V-3-60 Design

General Description

Solenoid operated directional control valves are for directing and stopping flow at any point in a hydraulic system.

- Efficient control of greater hydraulic powers without increasing solenoid power consumption.
- Installed cost and space savings from higher power/weight-and-size ratios.
- Installation flexibility resulting from choice of numerous combinations of solenoid connectors and locations.
- Viton seals as standard for multi-fluid capability. Nitrile seals available as a model code option.
- Higher sustained machine productivity and higher uptime because of proven fatigue life and endurance, tested over 20 million cycles.
- Solenoid coils can be changed quickly and easily without leakage from hydraulic system.
- Compact, cost effective system design when used with Vickers SystemStak™ valves and subplates.

DG4V-3 High Performance Valves

- Available with manual overrides for industrial or water-resistant overrides for mobile applications.
- Minimum pressure drop 2.5 Bar at 30 lpm.
- Range of coil voltages.
- Up to 80 lpm at 350 Bar.
- Offers designers the opportunity to select the optimum value package for each application.
- International standard interface. The valve mounting face conforms to ISO 4401, size 03 and is compatible with related international standards.
- Alternative coil voltages and connectors such as Deutsch, Amp and terminal box are available, contact sales office for a quotation.

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC DIRECTIONAL CONTROL VALVES

CETOP 3 Single Solenoid Directional Control Valves

Max flow rates up to 80 L/min.
Mounting interface.
ISO 4401 Size 3.
ANSI/B93.7M Size 3.
CETOP RP6SH Size 3.
DIN 24340 (NG6).

Temperature Limits:
Min -20°C (-4°F)
Max +70°C (+150°F)

Working Temperature:
-20°C (-4°F) to +70°C (+150°F)

Maximum Working Pressure:
350 bar (5075 psi)





2 Position, All Ports Open, Spring Offset End to Centre

3019	Voltage	Manufacturer's Code
859160	24V DC	DG4V 3 0B M U H7 60
859195	110V AC	DG4V 3 0B M U A6 60
	Tech Sheet 3111	




2 Position, All Ports Open, Spring Offset End to Centre, Water Resistant Override

3019	Voltage	Manufacturer's Code
869951	12V DC	DG4V 3 0B H M U G7 60
870804	24V DC	DG4V 3 0B H M U H7 60
	Tech Sheet 3111	



2 Position, Spring Offset End to End

3019	Voltage	Manufacturer's Code
529762	24V DC	DG4V 3 2A M U H7 60
529763	110V AC	DG4V 3 2A M U A6 60
	Tech Sheet 3111	



2 Position, Spring Offset End to End, Water Resistant Override

3019	Voltage	Manufacturer's Code
869959	12V DC	DG4V 3 2A H M U G7 60
870221	24V DC	DG4V 3 2A H M U H7 60
871358	110/120V 50/60Hz	DG4V 3 2A H M U B6 60
871505	220/240V 50/60Hz	DG4V 3 2A H M U D6 60
	Tech Sheet 3111	

For **CETOP Coils**
see page **219**



Other voltages are available. Please contact our Business Development Team for more details.

Fluid-Air Components Ltd

HYDRAULIC DIRECTIONAL CONTROL VALVES

CETOP 3 Double Solenoid Directional Control Valves


Max flow rates up to 80 L/min.
Mounting interface.
ISO 4401 Size 3.
ANSI/B93.7M Size 3.
CETOP RP6SH Size 3.
DIN 24340 (NG6).

Temperature Limits:
Min -20°C (-4°F)
Max +70°C (+150°F)

Working Temperature:
-20°C (-4°F) to +70°C (+150°F)


Maximum Working Pressure:
350 bar (5075 psi)






3 Position, All Ports Closed, Spring Centred

3019	Voltage	Manufacturer's Code
529761	110V AC	DG4V 3 2C M U A6 60
	Tech Sheet 3111	




3 Position, All Ports Closed, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
859172	220/240V 50/60Hz	DG4V 3 2C H M U D6 60
870177	24V DC	DG4V 3 2C H M U H7 60
870378	12V DC	DG4V 3 2C H M U G7 60
	Tech Sheet 3111	



3 Position, A, B & T Connected, Spring Centred

3019	Voltage	Manufacturer's Code
565465	24V DC	DG4V 3 6C M U H7 60
859177	110V AC	DG4V 3 6C M U A6 60
	Tech Sheet 3111	



3 Position, A, B & T Connected, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
869952	12V DC	DG4V 3 6C H M U G7 60
869953	24V DC	DG4V 3 6C H M U H7 60
02-146111	110/120V 50/60Hz	DG4V 3 6C H M U B6 60
	Tech Sheet 3111	

For **Hydraulic Quick Release Couplings** see pages **289-294**



Other voltages are available. Please contact our Business Development Team for more details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC DIRECTIONAL CONTROL VALVES

CETOP 3 Double Solenoid Directional Control Valves

Max flow rates up to 80 L/min.
Mounting interface.
ISO 4401 Size 3.
ANSI/B93.7M Size 3.
CETOP RP6SH Size 3.
DIN 24340 (NG6).

Temperature Limits:
Min -20°C (-4°F)
Max +70°C (+150°F)

Working Temperature:
-20°C (-4°F) to +70°C (+150°F)

Maximum Working Pressure:
350 bar (5075 psi)





3 Position, All Ports Open, Spring Centred

3019	Voltage	Manufacturer's Code
859197	110V AC	DG4V 3 0C M U A6 60
	Tech Sheet 3111	




3 Position, All Ports Open, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
869960	24V DC	DG4V 3 0C H M U H7 60
870518	12V DC	DG4V 3 0C H M U G7 60
	Tech Sheet 3111	



P & T Connected, A & B Blocked, Spring Centred

3019	Voltage	Manufacturer's Code
02-144961	110V AC	DG4V 3 8C VM U A6 61
02-145162	24V DC	DG4V 3 8C VM U H7 61
	Tech Sheet 3111	




P & T Connected, A & B Blocked, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
02-353298	110/120V 50/60Hz	DG4V 3 8C H VM U B6 61
	Tech Sheet 3111	



2 Position, Detented

3019	Voltage	Manufacturer's Code
529764	24V DC	DG4V 3 2N M U H7 60
529765	110V AC	DG4V 3 2N M U A6 60
	Tech Sheet 3111	



2 Position, Detented, Water Resistant Override


3019	Voltage	Manufacturer's Code
02-139074	24V DC	DG4V 3 2N H M U H7 60
	Tech Sheet 3111	


Other voltages are available. Please contact our Business Development Team for more details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SYSTEM STACK VALVES

CETOP 3 Modules






Single Line Relief Valves

3019	Pressure Range Bar	Manufacturer's Code
694419	10-200	DGMC 3 PT CW 41
869641	50-315	DGMC 3 PT GW 41
	Tech Sheet 71678	






Dual Line Relief Valve

3019	Pressure Range Bar	Manufacturer's Code
869628	10-200	DGMC2 3 AB CW BA CW 41
	Tech Sheet 71678	






Direct Operated Check Valve

3019	Manufacturer's Code
694415	DGMDC 3 Y PK 41
Tech Sheet 71678	







Flow Restrictors

3019	Description	Manufacturer's Code
694414	A & B Meter In	DGMFN 3 X A2W B2W 41
694412	A & B Meter Out	DGMFN 3 Y A2W B2W 41
870043	P Line	DGMFN 3 Z P2W 41
	Tech Sheet 71678	








Pilot Operated Check Valves

3019	Description	Manufacturer's Code
870024	Single	DGMPC 3 ABK 41
694400	Double	DGMPC 3 ABK BAK 41
	Tech Sheet 71678	





Pressure Reducing Valves

3019	Pressure Range Bar	Manufacturer's Code
870036	3.5-70	DGMX2 3 PP BW B 40
870038	20-250	DGMX2 3 PP FW B 40
	Tech Sheet 71678	

Fluid-Air Components Ltd


Cetop 5 Valves











Solenoid Operated Directional Valve

DG4V-5-20/22 Design

General Description

A range of four-port solenoid operated directional control valves with four-land spool design to facilitate provision of smooth, variable valve response speeds.

The range includes:

- AC and DC wet-armature solenoid options with ISO 4400 (DIN 43650) electrical connections and manual overrides and manual overrides for industrial or water-resistant overrides for mobile applications.
- Variable speed changeover potential in all DC models; see "Response Times" section.
- Many spool types; in spring-offset, spring centred and detented arrangements.
- Compact, cost effective system design when used with Vickers® SystemStak™ valves and subplates.

FAC
Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

HYDRAULIC DIRECTIONAL CONTROL VALVES

CETOP 5 Single Solenoid Directional Control Valves

Max flow rates up to 120 L/min.
Mounting interface.
ISO 4401 Size 5.
NFPA D02
DIN 24340 (NG10).

Temperature Limits:
Min -20°C (-4°F)
Max +70°C (+150°F)

Working Temperature:
-20°C (-4°F) to +70°C (+150°F)


Maximum Working Pressure:
350 bar (5075 psi)





2 Position, All Ports Open, Spring Offset End to Centre

3019	Voltage	Manufacturer's Code
459215	110V AC	DG4V 5 0B M U A6 20
	Tech Sheet 3112	



2 Position, Spring Offset End to End, Water Resistant Override

3019	Voltage	Manufacturer's Code
829AN00176A	24V DC	DG4V 5-2AJ H M U H7 22
	Tech Sheet 3112	



2 Position, Spring Offset End to End, Notched Spool

3019	Voltage	Manufacturer's Code
829AN00102A	24V DC	DG4V 5 2AJ M U H7 22
	Tech Sheet 3112	



2 Position, Spring Offset End to End


3019	Voltage	Manufacturer's Code
616769	110V AC	DG4V 5 2A M U A6 20
	Tech Sheet 3112	


Other voltages are available. Please contact our Business Development Team for more details.

Fluid-Air Components Ltd

HYDRAULIC DIRECTIONAL CONTROL VALVES


CETOP 5 Double Solenoid Directional Control Valves






All Ports Closed, Spring Centred

3019	Voltage	Manufacturer's Code
829AN00101A	24V DC	DG4V 5 2CJ M U H7 22
616777	110V AC	DG4V 5 2C M U A6 20
	Tech Sheet 3112	



A & B to T, P Blocked, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
829AN00158A	24V DC	DG4V 5 6CJ H M U H7 22
	Tech Sheet 3112	



A & B to T, P Blocked, Spring Centred

3019	Voltage	Manufacturer's Code
829AN00100A	24V DC	DG4V 5 6CJ M U H7 22
616781	110V AC	DG4V 5 6C M U A6 20
	Tech Sheet 3112	




All Ports Open, Spring Centred

3019	Voltage	Manufacturer's Code
829AN00132A	24V DC	DG4V 5 0CJ M H7 22
616789	110V DC	DG4V 5 0C M U A6 20
	Tech Sheet 3112	

Roquet making moves

For **Gear Pumps & Motors**
see pages **231-236**





FAC Fluid-Air Components Ltd

HYDRAULIC DIRECTIONAL CONTROL VALVES

CETOP 5 Double Solenoid Directional Control Valves








All Ports Open, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
829AN00165A	24V DC	DG4V 5 0CJ H M U H7 22
	Tech Sheet 3112	




P & T Connected, A & B Blocked, Spring Centred, Water Resistant Override

3019	Voltage	Manufacturer's Code
829AN00221A	24V DC	DG4V 5 8CJ H VM U H7 22
	Tech Sheet 3112	



P & T Connected, A & B Blocked, Spring Centred

3019	Voltage	Manufacturer's Code
829AN00103A	24V DC	DG4V 5 8CJ VM U H7 22
616785	110V AC	DG4V 5 8CJ VM U A6 20
	Tech Sheet 3112	



2 Position, Detented

3019	Voltage	Manufacturer's Code
829AN00105A	24V DC	DG4V 5 2NJ M U H7 22
616773	110V AC	DG4V 5 2N M U A6 20
	Tech Sheet 3112	


Other voltages are available. Please contact our Business Development Team for more details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c c a c c

SYSTEM STACK VALVES

CETOP 5 Modules






Flow Restrictors

3019	Description	Manufacturer's Code
867332	Meter Out	DGMFN 5 Y A2W B2W 30
867335	Meter In	DGMFN 5 X A2W B2W 30
	Tech Sheet 3112	







Pressure Reducing Valves

3019	Pressure Range Bar	Manufacturer's Code
868314	8.5-100	DGMX2 5 PP BW B 30
880553	8.5-200	DGMX2 5 PP FW B 30
879046	8.5-315	DGMX2 5 PP GH B 30
	Tech Sheet 3112	









Pilot Operated Check Valve, 1 bar Cracking Pressure

3019	Description	Manufacturer's Code
867339	Single A Port	DGMPC 5 ABK 30
867340	Single B Port	DGMPC 5 BAK 30
867364	Double A & B Port	DGMPC 5 ABK BAK 30
	Tech Sheet 3112	







Single Line Relief Valves

3019	Pressure Range Bar	Manufacturer's Code
868651	4-100	DGMC 5 AT BW B 30
879342	4-200	DGMC 5 PT FW B 30
868300	4-315	DGMC 5 PT GW B 30
	Tech Sheet 3112	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CETOP VALVE COILS

CETOP 3 Coils, 60 Design



DC Coils

3019	Voltage
507847	12V
507848	24V
507855	12V 18W
507852	24V 18W
865882	48V
865637	98V
865884	110V
865638	196V

AC Coils

3019	Voltage
507825	110V 50Hz
507826	220V 50Hz
507833	110V 50Hz / 120V 60Hz
507834	220V 50Hz / 240V 60Hz

CETOP 5 Coils, 20 Design



DC Coils

3019	Voltage
617470	12V
617471	24V
457942	48V
457977	98V
457911	110V
698523	196V

AC Coils

3019	Voltage
617475	110V 50Hz
617476	220V 50Hz
617477	240V 50Hz
617499	115V 60Hz
617500	230V 60Hz

ELECTRICAL CONNECTORS

EN175301-803, DIN43650

PG11

0347	Voltage	Description
GDM2011-G	250V AC/DC	No LED, Grey
GDML2011-GB1-B	250V AC/DC	Bridge-type Rectifier No LED
GDML2011LED-24-B	24V AC/DC	LED No Protection
GDML2011LED-120B	120V AC/DC	LED No Protection
GDML2011LED-230B	230V AC/DC	LED No Protection
GDML2011LED-24HH	24V DC	LED with Diode Protection
GDML2011LED-48HH	48V DC	LED with Diode Protection
Tech Sheet 10132		



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC VALVES PUMPS & MOTORS

Parker Cetop 3 & 5 Valves



Cetop 3 - 4 Port 3 & 2
Position Solenoid Directional Control Valve - 24-110V

0484	Coil Voltage	Control Spool	Description
D1VW001CNJNJW	24V DC	All Blocked	4 Port 3 Pos



Cetop 5 - 4 Port 3 & 2
Position Solenoid Directional Control Valve - 24-110V

0484	Coil Voltage	Control Spool	Description
D3W008CNJW	24V DC	PT Connected	4 Port 3 Pos



Cetop 3 Modular
Flow Control Valve

0484	Metering
FM2DDSV	A & B



Cetop 5 Modular
Flow Control Valve

0484	Metering
FM3DDSV	A & B



Cetop 3 Modular
Pilot Operated Check Valve, 1 bar Cracking Pressure

0484	Cracking Pressure Bar
CPOM2DDV	1.0



Cetop 5 Modular
Pilot Operated Check Valve, 1 bar Cracking Pressure

0484	Cracking Pressure Bar
CPOM3DDV	1.0


For **Hydraulic Oils**
see page **283**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c c a c c

Vane & Piston Pumps











Vickers Vane Pumps – V10 and V20

- V10 and V20 balanced vane type construction.
- High performance.
- Enhanced bearing life.
- Low cost.
- High flow, pressure and speed capabilities enable these pumps to meet the hydraulic circuit needs of many types of modern machinery.

Vickers Intravane pumps – 25V, 35V and 45V.

- High performance.
- Low noise characteristics.
- The cartridge design offers fast and efficient field serviceability.
- Eleven flow displacements and high operating pressure capabilities provide optimum selection and single source capabilities.

Vickers PVQ inline variable displacement pumps.

- Available in five displacements from 10.55cc/rev to 41.00cc/rev.
- Low noise characteristics.
- Choice of pump compensators, high and low-pressure compensator, remote compensator, and load sense compensator.
- Pump stroke adjustment kits available for all sizes.

Vickers PVM variable displacement axial piston pumps.

- Available in six displacements from 18cc/rev to 131cc/rev.
- 315 Bar continuous working pressure across all displacements.
- Low noise characteristics.
- Compact size envelope.
- Available as pressure compensated or load sensing.

Fluid-Air Components Ltd

INDUSTRIAL VANE PUMPS



V10 Series

SAE A 2 Bolt Mounting, Keyed Shaft, BSPP Ports

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
708371-C	6.60	172	V10 1B2B 1C 20
708784-C	9.80	172	V10 1B3B 1C 20
708785-C	13.10	172	V10 1B4B 1C 20
708219-C	16.40	172	V10 1B5B 1C 20
708786-C	19.50	152	V10 1B6B 1C 20
708787-C	22.80	138	V10 1B7B 1C 20
		Tech Sheet 10095	

V20 Series

SAE A 2 Bolt Mounting, Keyed Shaft, BSPP Ports

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
707277-C	19.5	172	V20 1B6B 1C 11 EN1000
708397-C	22.80	172	V20 1B7B 1C 11 EN1000
706996-C	26.5	172	V20 1B8B 1C 11 EN1000
707278-C	29.7	172	V20 1B9B 1C 11 EN1000
706997-C	36.40	172	V20 1B11B 1C 11 EN1000
708398-C	39.0	152	V20 1B12B 1C 11 EN1000
706998-C	42.4	152	V20 1B13B 1C 11 EN1000
		Tech Sheet 10095	

25V Series

SAE B 2 Bolt Mounting, Keyed Shaft, SAE Flanged Ports

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
02-137109-CR	39	172	25V 12A 1C 22R
02-137110-CR	45	172	25V 14A 1C 22R
02-137113-CR	55	172	25V 17A 1C 22R
02-137117-CR	67	172	25V 21A 1C 22R
		Tech Sheet 10097	

35V Series

SAE C 2 Bolt Mounting, Keyed Shaft, SAE Flanged Ports

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
02-137124-CR	81	172	35V 25A 1C 22R
02-137126-CR	97	172	35V 30A 1C 22R
02-137129-CR	112	172	35V 35A 1C 22R
02-137132-CR	121	172	35V 38A 1C 22R
		Tech Sheet 10097	

45V Series

SAE C 2 Bolt Mounting, Keyed Shaft, SAE Flanged Ports


3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
02-137140-CR	138	172	45V 42A 1C 22R
02-137144-CR	162	172	45V 50A 1C 22R
02-137146-CR	193	172	45V 60A 1C 22R
		Tech Sheet 10097	

Other options available, contact us with your requirements

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL VANE PUMPS

Replacement Parts



V10 Cartridge Kits

3017	Displacement cc/rev	To Suit
923471	3.3	V10 1G Cartridge Kit
923470	6.6	V10 2G Cartridge Kit
923496	9.8	V10 3G Cartridge Kit
923469	13.10	V10 4G Cartridge Kit
923468	16.40	V10 5G Cartridge Kit
923497	19.5	V10 6G Cartridge Kit
923498	22.80	V10 7G Cartridge Kit

V20 Cartridge Kits

3017	Displacement cc/rev	To Suit
02-137560	19.5	V20 6G Cartridge Kit
02-137561	22.80	V20 7G Cartridge Kit
02-137562	26.5	V20 8G Cartridge Kit
02-137563	29.7	V20 9G Cartridge Kit
02-137565	36.40	V20 11G Cartridge Kit
02-137566	39.0	V20 12G Cartridge Kit
02-137567	42.4	V20 13G Cartridge Kit

25V Cartridge Kits

3017	Displacement cc/rev	To Suit
02-102532	39	25V 12G Cartridge Kit
02-102533	45	25V 14G Cartridge Kit
02-102534	55	25V 17G Cartridge Kit
02-102535	67	25V 21G Cartridge Kit

35V Cartridge Kits

3017	Displacement cc/rev	To Suit
02-102552	81	35V 25G Cartridge Kit
02-102553	97	35V 30G Cartridge Kit
02-102554	112	35V 35G Cartridge Kit
02-102555	121	35V 38G Cartridge Kit

45V Cartridge Kits

3017	Displacement cc/rev	To Suit
02-102572	138	45V 42G Cartridge Kit
02-102574	162	45V 50G Cartridge Kit
02-102575	193	45V 60G Cartridge Kit



Shafts

3017	To Suit
238929	25V No. 11 Splined Shaft
242287	35V No. 11 Splined Shaft
242885	45V No. 11 Splined Shaft
392669	35V No. 86 HD Keyed Shaft
361760	45V No. 86 HD Keyed Shaft
393536	Key to suit 392669
239751	Key to suit 361760



Seal Kits

3017	To Suit
923548	V10 Standard Seal Kit
919772	V10 F3 Seal Kit
922733	V20 Standard Seal Kit
919805	V20 F3 Seal Kit
922850	25V Standard Seal Kit
919656	25V F3 Seal Kit
922851	35V Standard Seal Kit
919262	35V F3 Seal Kit
919850	45V Standard Seal Kit
919632	45V F3 Seal Kit

Other options available, contact us with your requirements

Fluid-Air Components Ltd

HYDRAULIC PISTON PUMPS



Q Series Piston Pump

210 bar, SAE A Flange, Keyed Shaft

3017	Displacement cc/rev	Manufacturer's Code
02-341576	10.5	PVQ10 A2R SE1S 20 C21 12
	Tech Sheet 10045	

140 bar, SAE A 2 Bolt Flange, Keyed Shaft

3017	Displacement cc/rev	Manufacturer's Code
02-341644	13.8	PVQ13 A2R SE1S 20 C14 12
	Tech Sheet 10045	

210 bar, SAE B 2 Bolt Flange, Keyed Shaft

3017	Displacement cc/rev	Manufacturer's Code
02-341552	21.1	PVQ20 B2R SE1S 21 C21 12
	Tech Sheet 10045	

140 bar, SAE B 2 Bolt Flange, Keyed Shaft

3017	Displacement cc/rev	Manufacturer's Code
02-341685	32.9	PVQ32 B2R SE1S 21 C14 12
	Tech Sheet 10045	

210 bar, SAE B 2 Bolt Flange, Keyed Shaft

3017	Displacement cc/rev	Manufacturer's Code
02-341949	41.0	PVQ40AR01AB01AB10G2100000100100CD0A
	Tech Sheet 10045	

Q Series Piston Pump Compensator

Standard Compensator

3017	To Suit
9900224-003	PVQ10, 13, 20, 32
02-348260	PVQ40
Tech Sheet 10045	

CM Low Pressure Compensator

3017	To Suit
9900224-002	PVQ10,13,20,32
02-348259	PVQ40
Tech Sheet 10045	

CG Hydraulic Remote Compensator

3017	To Suit
02-348243	PVQ10,13,20,32,40
Tech Sheet 10045	

C**V**B Load Sensing Compensator

3017	To Suit
02-466861	PVQ10,13,20,32
Tech Sheet 10045	

Q Series Piston Pump Stroke Adjustment Kit

Maximum Stop/Stroke Limiter

3017	To Suit
5986572-001	PVQ10,13
5986574-001	PVQ20,32
5986576-001	PVQ40
Tech Sheet 10045	

Q Series Piston Pump Seal Kits

Standard Buna Material

3017	To Suit
919191	PVQ10,13
919682	PVQ20,32
920227	PVQ40
Tech Sheet 10045	

Other options available, contact us with your requirements

Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

HYDRAULIC PISTON PUMPS

M Series Piston Pump



Pressure Compensate Pump

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
123AL02399A	18.0	320	PVM018ER02AS02AAA28000001A0A
123AL02398A	45.0	320	PVM045ER06CS02AAA28000001A0A
123AL02054A	57.0	320	PVM057ER09GS02AAA28000001A0A
123AL02062A	74.0	320	PVM074ER09GS02AAA28000001A0A
123AL02070A	98.0	320	PVM098ER09GS02AAA28000001A0A
123AL02090A	131.0	320	PVM131ER09GS02AAA28000001A0A
		Tech Sheet 71680	

Load Sense Pump

3017	Displacement cc/rev	Max Pressure Bar	Manufacturer's Code
123AL02012A	18.0	320	PVM018ER02AS02AAC28200001A0A
123AL02150A	45.0	320	PVM045ER06CS02AAC28110001A0A
123AL02056A	57.0	320	PVM057ER09GS02AAC28200001A0A
123AL02241A	74.0	320	PVM074ER09GS02AAC28200001A0A
123AL02074A	98.0	320	PVM098ER09GS02AAC28200001A0A
123AL02356A	131.0	320	PVM131ER09GS02AAC28200001A0A
		Tech Sheet 71680	

Roquet making moves



For **Roquet Gear Pumps**
see page **231**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



Partnership brands available



Hydraulic Accumulators & Accessories
See section 1 pages 227-228

Hydraulic Oil Coolers
See section 1 page 273



Ball & Check Valves
See section 5 page 628

Plastic Push-in Fittings
See section 6 pages 793-807

Metal Push-in Fittings
See section 6 pages 848-851

Ball Valves
See section 7 pages 933-935

Blow Guns
See section 15 page 1596



Pneumatic Quick Release Couplings
See section 3 pages 330-390



Filters & Drains Air, Water & Vacuum
See section 4 page 430



Aluminium Ring Main Systems
See section 8 pages 1063-1067



Plastic Push-in Fittings
See section 6 pages 800-803

ENGINEERING YOUR SUCCESS.

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

HYDRAULIC ACCUMULATORS & ACCESSORIES

Diaphragm Accumulators

- Low cost non-repairable accumulators
- High reliability gas sealing system, ensures no leakage
- Electron beam welded steel shell
- Parallel threads with bonded seal recess ensures easy connection with no leaks
- **Material:** steel shell electron beam welded. Non repairable
- Nitrile membrane for mineral oil or non aggressive fluid




BSPP

0197	Manufacturer's Code	Thread	Capacity Litres	Temp Range °C	Max Pressure Bar
E007-1515-013611	108492-01125	1/2"	0.075	-10/+80	250
E016-1515-013611	108493-01125	1/2"	0.16	-10/+80	250
E032-1515-013611	109866-01125	1/2"	0.32	-10/+80	210
E050-1515-023611	108495-01125	1/2"	0.50	-20/+80	210
E075-1515-093611	108497-01125	1/2"	0.75	-20/+80	210
E100-1515-123611	109847-01125	1/2"	1.0	-20/+80	210
E140-1515-113511	108502-01125	1/2"	1.4	-20/+80	140
E200-1515-063411	108504-01125	1/2"	2.0	-10/+80	100
E200-1515-063611	110134-01125	3/4"	2.0	-10/+80	250
E280-1515-032611	108879-01125	3/4"	2.8	-10/+80	250
E350-1515-092611	108505-01125	3/4"	3.5	-10/+80	250
Tech Sheet 10553					

Safety Blocks

- Carbon steel
- All blocks fully tested
- Nitrile seals as standard, Viton available on request
- Contact technical department
- Pressure relief valve for the protection of accumulator
- Manual dump to tank as standard

Maximum Working Pressure:
360 bar



Carbon Steel

0197	BSPP S	BSPP P	BSPP T	BSPP M	Max Pressure Bar
ECA12-01-L-N	1/2"	1/2"	1/4"	1/4"	360
Tech Sheet 2153					

Hydra-Cushions

Hydracushions are a robust non repairable accumulator. They have been specifically designed for high volume, low cost applications, where it is more economical to replace a unit than to refurbish it after a long service life.

- Steel construction
- Nitrile bladder
- 1/4" gas valve

Maximum Working Pressure:
172 bar



BSPP

0197	Thread	Litres
HC0100A-00-17	3/4"	1.0
HC0200A-00-17	1"	2.0
HC0400A-00-17	1.1/4"	4.0
Tech Sheet 10797		

Accumulator Bladder Kits

The kit comprises of a bladder assembly, protective cap, anti extrusion ring, O-Ring for the fluid port, back up ring and seal for the bleed plug.



Oil Service

0197	Litres	Description
0B00A-00	0.16	-
0F00A-00	0.6	-
01C00A-00	1.15	-
0300A-00	3	5/8" Stem
03C00A-00	3	7/8" Stem
0400A-00	4	-
1000A-00	10	-
2000A-00	20	-
2800A-00	28	-
3700A-00	37	-
5400A-00	54	-
Tech Sheet 10797		

Thermoswitches

For use with the LAC series of air blast coolers.



1/2" BSPP

0197	Temp°C
598262	40
598261	50
598263	60
598264	70
598265	80

Fluid-Air Components Ltd

HYDRAULIC ACCUMULATORS & ACCESSORIES

Accumulator Charging Kits

For safe pre-charging of accumulators, Fawcett Christie Hydraulics offer a comprehensive range of equipment.



Universal Pre-charged

0197	Description
10597-01	0-25 & 0-250 bar Gauge
10597-02	0-60 & 0-400 bar Gauge
10597-03	0-10 & 0-160 bar Gauge

Accumulator Accessories

Designed to allow quick, easy and safe installation of accumulators. They are fabricated from steel and come complete with rubber cushion mouldings and mounting bolts.



Saddle & Clamps

0197	Bore mm
10958	112-114
10959	165-168
10960	220-230



Support Brackets

0197	To Suit
10961	4-9 Litre FCH Accumulators
10962	10-54 Litre FCH Accumulators



Cushioning Rings

0197	To Suit
48473-A00	10-54 Litre Support Brackets



Gas Valves

0197	Thread
10031-S03	1/4" x 1/4" BSPP
43030	0.302 x 1/2" UNF

For **Hydraulic Filtration** see pages **247-251**



Fluid-Air Components Ltd

HYDRAULIC HAND PUMPS

Pumps

Specification
- Cast iron body
- White zinc-plated support lever
- Lever connection OD: 27mm
- White zinc-plated external parts

Maximum Working Pressure:
350 bar



Double Acting Pump with Release Knob, Side Mount

0462	Displacement cm³	Thread	Max Pressure Bar	Model	To Suit
HHP-01	20	1/2"	350	Wall Mount	Single Acting Cylinder
		Tech Sheet 60145			

Specification
- Cast iron body
- Piston treated with Niploy
- White zinc-plated support lever
- Lever connection OD: 27mm
- White zinc-plated external parts

Maximum Working Pressure:
280 bar



Double Acting Pump with Release Knob, Bottom Mount

0462	Displacement cm³	Thread	Max Pressure Bar	Model	To Suit
HHP-02	50	1/2"	280	Wall Mount	Single Acting Cylinder
		Tech Sheet 60146			

Double acting hand pump for single acting cylinder.

Specification
- Cast iron body
- Piston treated with Niploy
- White zinc-plated support lever
- Lever connection OD: 27mm
- White zinc-plated external parts
- Oil tank mounting kit included
- Pressure relief valve (standard setting): 100 bar

Maximum Working Pressure:
350 bar



Double Acting Pump with Release Knob & Pressure Relief Valve

0462	Displacement cm³	Thread	Max Pressure Bar	Model	To Suit
HHP-03	25	3/8"	350	Tank Mount	Single Acting Cylinder
		Tech Sheet 60147			

Double acting hand pump for double acting cylinder.

Specification
- Cast iron body
- Piston treated with Niploy
- White zinc-plated support lever
- Lever connection OD: 27mm
- White zinc-plated external parts

Maximum Working Pressure:
350 bar



Double Acting Pump with 4/3 Diverter Valve & Pressure Relief Valve

0462	Displacement cm³	Thread	Max Pressure Bar	Model	To Suit
HHP-04	25	3/8"	350	Tank Mount	Double Acting Cylinder
		Tech Sheet 60148			

FAC
Fluid-Air Components Ltd

HYDRAULIC HAND PUMPS

Pumps

Double acting pump for double acting cylinder.

Specification:

- Cast iron body
- Piston treated with Niploy
- White zinc-plated support lever
- Lever connection OD: 27mm
- White zinc-plated external parts
- Oil tank mounting kit included
- Hydraulic brake to operate under 50 bar
- Pressure relief valve (standard setting): 100 bar

Maximum Working Pressure:
350 bar



Double Acting Pump with 4/3 Diverter Valve, PRV & Dual PO Check Valve

0462	Displacement cm^3	Thread	Max Pressure Bar	Model	To Suit
HHP-05	25	3/8"	350	Tank Mount	Double Acting Cylinder
Tech Sheet 60149					

Single acting pump for single acting cylinder.

Specification:

- White zinc-plated steel body
- Piston treated with Niploy
- White zinc-plated external parts
- Release lever

Maximum Working Pressure:
220 bar



Single Acting Foot Pump with 1.5 Litre Reservoir

0462	Displacement cm^3	Thread	Max Pressure Bar	To Suit
HFP-01	15	1/4"	220	Single Acting Cylinder
Tech Sheet 60150				

Accessories

Specification:

- Black hand grip
- White zinc-plated steel lever



Operating Lever

0462	To Suit	Length mm
HHP-OL	HHP Series	900
Tech Sheet 60152		

Closed centre option available.



3 Way Flow Diverter Valves

0462	Thread	Description	Max Pressure Bar	LPM
HHPDV-06	3/8"	Open Centre	350	60
HHPDV-08	1/2"	Open Centre	350	90
HHPDV-12	3/4"	Open Centre	350	120
Tech Sheet 60153				

Normally open, two position with mechanical control for tipping trucks.

Specification:

- Cast iron body
- Piston treated with Niploy
- White zinc plated external parts

Maximum Working Pressure:
250 bar



End Stroke Valves

0462	Thread	LPM
HESV-06	3/8"	60
HESV-08	1/2"	80

Gear Pump Elbows, BSPP

0347	Group	Thread
GPE1-12	1	1/2"
GPE1-38	1	3/8"
GPE2-12	2	1/2"
GPE2-34	2	3/4"
Tech Sheet 10129		



Steel Tanks

Specification:

- Suction pipe included
- Breather Cap 1/4" BSPP
- Release Cap 1/4" BSPP
- Standard colour black



Steel Oil Tanks for Hand Pumps

0462	Volume Litres	Thread
HHPT-01	1	1/4"
HHPT-02	2	1/4"
HHPT-03	3	1/4"
HHPT-05	5	1/4"
HHPT-07	7	1/4"
Tech Sheet 60151		

Fluid-Air Components Ltd

Roquet making moves

new product

Gear Pumps

Roquet is a premium manufacturer of gear pumps and motors ranging from 0.33-150 cm³/rev. As standard, all Roquet gear pumps are manufactured with cast iron front and rear covers; reducing noise and increasing the product's life cycle. This design also enables the unit to accommodate in-built valves for speed control, etc.

Roquet pumps have an anechoic chamber, where engineers have designed the gear profile to reduce noise levels.



Gear Pumps

A gear pump is a positive displacement pump. It contains two identical interlocking gears, supported by separate shafts.

Generally, one gear is driven by a motor, and this in turn drives the other gear (idler gear).

Fixed volumes of fluid are enclosed between the outer gear teeth mechanically using a cyclic pumping action. This delivers a smooth and pulse-free flow, which is proportional to the rotational speed of the gears.

Close tolerances between the gears prevent fluid from transferring back through the centre. Also, close tolerances between the gears and the casing allow the pump to create suction at the inlet, and prevents fluid leaking back from the outlet. (Leakage is more likely with low viscosity liquids)

making moves

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

ALUMINIUM GEAR PUMPS

Roquet making moves

new product

Group 1

Series: L0
Body: Aluminium
Displacement: from 1cm³/rev to 6,63cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1L01.5DE10R	1	275	300
1L03DE10R	2	275	300
1L05DE10R	3.3	240	275
1L07.5DE10R	5	185	200
1L010DE10R	6.6	135	150
Tech Sheet 71710			

Group 2

Series: G
Body: Aluminium
Displacement: from 4cm³/rev to 26,67cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.
'G' series improvements over previous 'L' series:
• More drive shaft designs are available.
• Shorter multiple pumps.
• Higher torque admissible.
• Higher torque from rear pumps in multiple pumps.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1G4CDE10R	4	275	300
1G6CDE10R	6	275	300
1G8CDE10R	8	275	300
1G11CDE10R	10.7	275	300
1G12CDE10R	12	275	300
1G15CDE10R	14.7	250	275
1G16CDE10R	16	250	275
1G18CDE10R	18	225	250
1G23CDE10R	23.3	180	200
1G27CDE10R	26.6	170	190
Tech Sheet 71710			



9 Tooth Splined Shaft, 2 Bolt SAE-A Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1G4CDG09R	4	275	300
1G6CDG09R	6	275	300
1G8CDG09R	8	275	300
1G11CDG09R	10.7	275	300
1G12CDG09R	12	275	300
1G15CDG09R	14.7	250	275
1G16CDG09R	16	250	275
1G18CDG09R	18	225	250
1G23CDG09R	23.3	180	200
1G27CDG09R	26.6	170	190
Tech Sheet 71710			



1:5 Taper Shaft, 4 Bolt German Flange, Square Flanged Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1G4CDJ23F	4	275	300
1G6CDJ23F	6	275	300
1G8CDJ23F	8	275	300
1G11CDJ23F	10.7	275	300
1G12CDJ23F	12	275	300
1G15CDJ23F	14.7	250	275
1G16CDJ23F	16	250	275
1G18CDJ23F	18	225	250
1G23CDJ23F	23.3	180	200
1G27CDJ23F	26.6	170	190
Tech Sheet 71710			

Other shaft, flange, porting or rotation configurations available on request. Also available in cast iron material.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ALUMINIUM GEAR PUMPS

Group 3

Series: PLA
Body: Aluminium
Displacement: from 18cm³/rev to 56cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PLA27DE10R	250	275
1PLA36DE10R	250	275
1PLA45DE10R	250	275
1PLA54DE10R	225	250
1PLA66DE10R	200	225
1PLA84DE10R	175	200
Tech Sheet 71710		



1:5 Taper Shaft, 4 Bolt German Flange, Square Flanged Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PLA27DJ23F	18	250	275
1PLA36DJ23F	24	250	275
1PLA45DJ23F	30	250	275
1PLA54DJ23F	36	225	250
1PLA66DJ23F	44	200	225
1PLA84DJ23F	56	175	200
Tech Sheet 71710			



9 Tooth Splined Shaft, 2 Bolt SAE-A Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PLA27DG09R	18	250	275
1PLA36DG09R	24	250	275
1PLA45DG09R	30	250	275
1PLA54DG09R	36	225	250
1PLA66DG09R	44	200	225
1PLA84DG09R	56	175	200
Tech Sheet 71710			

Group 3.5

Series: PLC
Body: Aluminium
Displacement: from 53,33cm³/rev to 150cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



1:8 Taper Shaft, 4 Bolt European Flange, SAE Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PLC80DE10M	53.3	225	250
1PLC100DE10M	66.6	225	250
1PLC125DE10M	83.3	225	250
1PLC150DE10M	100	225	250
1PLC175DE10M	116.6	225	250
1PLC200DE10M	133.3	200	225
1PLC225DE10M	150	150	175
Tech Sheet 71710			

Group 4

Series: PLC
Body: Aluminium
Displacement: from 53,33cm³/rev to 150cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



1:8 Taper Shaft, 4 Bolt European Flange, SAE Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PLC80DJ23M	53.3	225	250
1PLC100DJ23M	66.6	225	250
1PLC125DJ23M	83.3	225	250
1PLC150DJ23M	100	225	250
1PLC175DJ23M	116.6	225	250
1PLC200DJ23M	133.3	200	225
1PLC225DJ23M	150	150	175
Tech Sheet 71710			

Other shaft, flange, porting or rotation configurations available on request. Also available in cast iron material.

Fluid-Air Components Ltd

Roquet making moves

new product

Gear Motors

Roquet is a premium manufacturer of gear pumps and motors ranging from 0.33-150 cm^3/rev. As standard, all Roquet gear motors are manufactured with cast iron front and rear covers; reducing noise and increasing the product's life cycle. This design also enables the unit to accommodate in-built valves for speed control, etc.

Roquet gear motors have an anechoic chamber where engineers have designed the gear profile to reduce noise levels.



Gear Motors

A gear motor is a mechanical actuator converting hydraulic pressure and flow into shaft rotation and torque. It is the rotary counterpart of the hydraulic cylinder.

Similarly to a gear pump, a gear motor consists of two identical interlocking gears, the driven gear and the idler gear. High-pressure oil enters the inlet side of the motor and flows around the outer periphery of the gear teeth - the gears mesh, which prevents the oil from coming back to the inlet from the outlet side.

For lubrication, a small amount of oil from the pressurised side bleeds through the bearings, and vents to the low pressure side, or through the drain port.

making moves

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

ALUMINIUM GEAR MOTORS

Roquet making moves

new product

Group 1

Series: L0
Body: Aluminium
Displacement: from 1cm³/rev to 6,63cm³/rev
• Motors with back cover in built valves available.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1ML01.5DE10R	1	275	300
1ML03DE10R	2	275	300
1ML05DE10R	3.3	240	275
1ML07.5DE10R	5	185	200
1ML010DE10R	6.6	135	150
Tech Sheet 71711			

Group 2

Series: G
Body: Aluminium
Displacement: from 4cm³/rev to 26,67cm³/rev
• Motors with back cover in built valves available.
'G' series improvements over previous 'L' series:
• More drive shaft designs are available.
• Shorter multiple pumps.
• Higher torque admissible.
• Higher torque from rear pumps in multiple pumps.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1MG4CDE10R	4	275	300
1MG6CDE10R	6	275	300
1MG8CDE10R	8	275	300
1MG11CDE10R	10.7	275	300
1MG12CDE10R	12	275	300
1MG15CDE10R	14.7	250	275
1MG16CDE10R	16	250	275
1MG18CDE10R	18	225	250
1MG23CDE10R	23.3	180	200
1MG27CDE10R	26.6	170	190
Tech Sheet 71711			

Other shaft, flange, porting or rotation configurations available on request. Also available in cast iron material.

Group 3

Series: PLA
Body: Aluminium
Displacement: from 18cm³/rev to 56cm³/rev
• Motors with back cover in built valves available.



1:8 Taper Shaft, 4 Bolt European Flange, BSPP Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1MPLA27DE10R	18	250	275
1MPLA36DE10R	24	250	275
1MPLA45DE10R	30	250	275
1MPLA54DE10R	36	225	250
1MPLA66DE10R	44	200	225
1MPLA84DE10R	56	175	200
Tech Sheet 71711			

Group 3.5

Series: PLC
Body: Aluminium
Displacement: from 53,33cm³/rev to 150cm³/rev
• Motors with back cover in built valves available.



1:8 Taper Shaft, 4 Bolt European Flange, SAE Ports, Clockwise Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1MPLC80DE10M	53.3	225	250
1MPLC100DE10M	66.6	225	250
1MPLC125DE10M	83.3	225	250
1MPLC150DE10M	100	225	250
1MPLC175DE10M	116.6	225	250
1MPLC200DE10M	133.3	200	225
1MPLC225DE10M	150	150	175
Tech Sheet 71711			

Group 4

Series: PLC
Body: Aluminium
Displacement: from 53,33cm³/rev to 150cm³/rev
• Motors with back cover in built valves available.



1:8 Taper Shaft, 4 Bolt European Flange, SAE Ports, Clockwise Rotation


3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1MPLC80DJ23M	53.3	225	250
1MPLC100DJ23M	66.6	225	250
1MPLC125DJ23M	83.3	225	250
1MPLC150DJ23M	100	225	250
1MPLC175DJ23M	116.6	225	250
1MPLC200DJ23M	133.3	200	225
1MPLC225DJ23M	150	150	175
Tech Sheet 71711			

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Roquet
making moves

new product

Cast Iron Gear Pumps



Group 3

Series: PNA
Material: Nodular cast iron
Displacement: from 53,33cm³/rev to 150cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



ISO Flange, Splined Shaft, 2 Bolt SAE B Flange, Bearing & Shaft Seal

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
13PNA36DG09R	24	270	300
13PNA45DG09R	30	270	300
13PNA54DG09R	36	260	285
13PNA66DG09R	44	260	285
13PNA84DG09R	56	210	250
13PNA96DG09R	64	180	225
13PNA110DG09R	73.3	160	200
Tech Sheet 71712			

Group 3.5

Series: PNC
Material: Nodular cast iron
Displacement: from 53,33cm³/rev to 150cm³/rev
• Pumps with back cover in built valves available.
• Multiple pumps available.



SAE Flange, Parallel Shaft, 4 Bolt Rotation

3014	Displacement (cc/rev)	Continuous Max Pressure (bar)	Intermittent Max Pressure (bar)
1PNC80DE10M	53.3	260	290
1PNC100DE10M	66.6	260	290
1PNC125DE10M	83.3	250	275
1PNC150DE10M	100	250	275
1PNC175DE10M	116.6	225	250
1PNC200DE10M	133.3	200	225
1PNC225DE10M	150	175	200
Tech Sheet 71712			

Other shaft, flange, porting or rotation configurations available on request.

making moves

FAC
Fluid-Air Components Ltd

HYDRAULIC CONTROL VALVES

Roquet making moves

new product

Monoblock Valves

Maximum Working Pressure:
350 bar

Port Sizes:
P, T, A, B: 3/8" BSPP
Nominal Flow: 40 L/min
Maximum Spool Quantity: 6
Main Relief Valve Pressure Ranges Available: 5-80 bar, 85-175 bar, 180-250 bar, 255-350 bar



3/8" BSPP, 102 Series, 3 Position, Single Section, Open Centre, 85-175 bar Relief Valve

3013	Spool Control Option	Spool Type
102N1PA12I	Spring Return	Motor
102N1PA12D	Spring Return	Cylinder
102N2PA12I	Detent	Motor
102N2PA12D	Detent	Cylinder
102N22PA12I	Pneumatic Pilot	Motor
102N22PA12D	Pneumatic Pilot	Cylinder
102N35RA12I	Rotative	Motor
102N35RA12D	Rotative	Cylinder
Tech Sheet 71709		

Maximum Working Pressure:
350 bar

Port Sizes:
P, T, A, B: 1/2" BSPP
Nominal Flow: 60 L/min
Maximum Spool Quantity: 2
Main Relief Valve Pressure Ranges Available: 5-80 bar, 85-175 bar, 180-250 bar, 255-350 bar



1/2" BSPP, 1102 Series, 3 Position, Single Section, Open Centre, 85-175 bar Relief Valve

3013	Spool Control Option	Spool Type
1102N1PA12I	Spring Return	Motor
1102N1PA12D	Spring Return	Cylinder
1102N2PA12I	Detent	Motor
1102N2PA12D	Detent	Cylinder
1102N22PA12I	Pneumatic Pilot	Motor
1102N22PA12D	Pneumatic Pilot	Cylinder
1102N35RA12I	Rotative	Motor
1102N35RA12D	Rotative	Cylinder
Tech Sheet 71709		

Sectional Valves

Maximum Working Pressure:
350 bar

Port Sizes:
P, T: 3/4" BSPP
A, B: 1/2" BSPP
Nominal Flow: 100 L/min
Maximum Spool Quantity: 10
Main Relief Valve Pressure Ranges Available: 5-80 bar, 85-175 bar, 180-250 bar, 255-350 bar



1/2" BSPP, 406 Series, 3 Position, Single Section, Open Centre, 85-175 bar Relief Valve

3013	Spool Control Option	Spool Type
406N1PA12I	Spring Return	Motor
406N1PA12D	Spring Return	Cylinder
406N2PA12I	Detent	Motor
406N2PA12D	Detent	Cylinder
406N22PA12I	Pneumatic Pilot	Motor
406N22PA12D	Pneumatic Pilot	Cylinder
406N35RA12I	Rotative	Motor
406N35RA12D	Rotative	Cylinder
Tech Sheet 71709		

Maximum Working Pressure:
350 bar

Port Sizes:
P, T, A, B: 3/4" BSPP
Nominal Flow: 100 L/min
Maximum Spool Quantity: 10
Main Relief Valve Pressure Ranges Available: 5-80 bar, 85-175 bar, 180-250 bar, 255-350 bar



3/4" BSPP, 1406 Series, 3 Position, Single Section, Open Centre, 85-175 bar Relief Valve

3013	Spool Control Option	Spool Type
1406N1PA12I	Spring Return	Motor
1406N1PA12D	Spring Return	Cylinder
1406N2PA12I	Detent	Motor
1406N2PA12D	Detent	Cylinder
1406N22PA12I	Pneumatic Pilot	Motor
1406N22PA12D	Pneumatic Pilot	Cylinder
1406N35RA12I	Rotative	Motor
1406N35RA12D	Rotative	Cylinder
Tech Sheet 71709		

Closed centre, HPCO, additional sections and bespoke configurations available on reques

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC BALL VALVES

Hydraulic Ball Valves

Working Temperature:
-20°C to +120°C

- Carbon steel body
- Excellent sealing properties
- Zinc-plated C6F
- High pressure
- Steel ball
- Full flow



2 Way, BSPP, NBR Seals

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHB-G1/4	1/4"	6	69	500
KHB-G3/8	3/8"	10	72	500
KHB-G1/2	1/2"	13	83	500
KHB-G3/4	3/4"	20	95	315
KHB-G1	1"	25	113	315
KHB-G11/4	1.1/4"	25	110	315
KHB-G11/2	1.1/2"	25	130	315
Tech Sheet 10171				



2 Way, Side Hole Fixing, BSPP, Nitrile Seals

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHBSM-G1/4	1/4"	6	69	500
KHBSM-G3/8	3/8"	10	72	500
KHBSM-G1/2	1/2"	13	83	500
KHBSM-G3/4	3/4"	20	95	315
KHBSM-G1	1"	25	113	315
KHBSM-G11/4	1.1/4"	25	110	315
KHBSM-G11/2	1.1/2"	25	130	315
Tech Sheet 10171				



2 Way, Top Mountable for Actuation, BSPP, Nitrile Seals

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHBTM-G1/4	1/4"	6	69	500
KHBTM-G3/8	3/8"	10	72	500
KHBTM-G1/2	1/2"	13	83	500
KHBTM-G3/4	3/4"	20	95	315
KHBTM-G1	1"	25	113	315
KHBTM-G11/4	1.1/4"	25	110	315
KHBTM-G11/2	1.1/2"	25	130	315
Tech Sheet 10171				



2 Way, 3000lb, Flanged

0177	ND	DN Size	Length mm	Max Pressure Bar
KHBF3-1/2	1/2"	13	151	210
KHBF3-3/4	3/4"	20	162	210
KHBF3-1	1"	25	178	210
KHBF3-1.1/4	1.1/4"	32	191	210
KHBF3-1.1/2	1.1/2"	40	231	210
KHBF3-2	2"	50	232	210
Tech Sheet 10044				



2 Way, 6000lb, Flanged

0177	ND	DN Size	Length mm	Max Pressure Bar
KHBF6-1/2	1/2"	13	151	420
KHBF6-3/4	3/4"	20	174	420
KHBF6-1	1"	25	198	420
KHBF6-1.1/4	1.1/4"	32	223	420
KHBF6-1.1/2	1.1/2"	40	281	420
Tech Sheet 10044				



2 Way, Light-duty, DIN 2353

0177	Thread	DN Size	Description	Length mm	Max Pressure Bar
KHB-8L	M14 x 1.5	6	8L	69	500
KHB-10L	M16 x 1.5	10	10L	77	500
KHB-12L	M18 x 1.5	10	12L	77	500
KHB-15L	M22 x 1.5	13	15L	83	500
KHB-22L	M30 x 2	20	22L	101	315
KHB-28L	M36 x 2	25	28L	108	315
Tech Sheet 10171					



2 Way, Heavy-duty, DIN 2353

0177	Thread	DN Size	Description	Length mm	Max Pressure Bar
KHB-10S	M18 x 1.5	6	10S	73	500
KHB-12S	M20 x 1.5	8	12S	77	500
KHB-16S	M24 x 1.5	13	16S	87	500
KHB-20S	M30 x 2	13	20S	91	500
KHB-25S	M36 x 2	20	25S	111	315
KHB-30S	M42 x 2	25	30S	120	315
Tech Sheet 10171					

Fluid-Air Components Ltd

HYDRAULIC BALL VALVES

Lockable Hydraulic Ball Valves

Working Temperature:
-20°C to +120°C

Lock not included



2 Way, BSPP

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHB-G1/4-LK	1/4"	6	69	500
KHB-G3/8-LK	3/8"	10	72	500
KHB-G1/2-LK	1/2"	13	83	500
KHB-G3/4-LK	3/4"	20	95	315
KHB-G1-LK	1"	25	113	315
KHB-G11/4-LK	1.1/4"	25	110	315
KHB-G11/2-LK	1.1/2"	25	130	315
Tech Sheet 10171				



2 Way, Side Hole Fixing, BSPP

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHBSM-G1/4-LK	1/4"	6	69	500
KHBSM-G3/8-LK	3/8"	10	72	500
KHBSM-G1/2-LK	1/2"	13	83	500
KHBSM-G3/4-LK	3/4"	20	95	315
KHBSM-G1-LK	1"	25	113	315
KHBSM-G11/4-LK	1.1/4"	25	110	315
KHBSM-G11/2-LK	1.1/2"	25	130	315
Tech Sheet 10171				




2 Way, Light-duty, DIN 2353

0177	Thread	DN Size	Description	Length mm	Max Pressure Bar
KHB-8L-LK	M14 x 1.5	6	8L	69	500
KHB-10L-LK	M16 x 1.5	8	10L	77	500
KHB-12L-LK	M18 x 1.5	13	12L	77	500
KHB-15L-LK	M22 x 1.5	13	15L	83	500
KHB-22L-LK	M30 x 2	20	22L	101	315
KHB-28L-LK	M36 x 2	25	28L	108	315
Tech Sheet 10171					



2 Way, Heavy-duty, DIN 2353

0177	Thread	DN Size	Description	Length mm	Max Pressure Bar
KHB-10S-LK	M18 x 1.5	8	10S	73	500
KHB-12S-LK	M20 x 1.5	13	12S	77	500
KHB-16S-LK	M24 x 1.5	13	16S	87	500
KHB-20S-LK	M30 x 2	20	20S	91	500
KHB-25S-LK	M36 x 2	25	25S	111	315
KHB-30S-LK	M42 x 2	25	30S	120	315
Tech Sheet 10171					



2 Way, 3000lb, Flanged

0177	ND	DN Size	Length mm	Max Pressure Bar
KHBF3-1/2-LK	1/2"	13	151	210
KHBF3-3/4-LK	3/4"	20	162	210
KHBF3-1-LK	1"	25	178	210
KHBF3-1.1/4-LK	1.1/4"	32	191	210
KHBF3-1.1/2-LK	1.1/2"	40	231	210
KHBF3-2-LK	2"	50	232	210
Tech Sheet 10171				



2 Way, 6000lb, Flanged

0177	ND	DN Size	Length mm	Max Pressure Bar
KHBF6-1/2-LK	1/2"	13	151	420
KHBF6-6/4-LK	3/4"	20	174	420
KHBF6-1-LK	1"	25	198	420
KHBF6-1.1/4-LK	1.1/4"	32	223	420
KHBF6-1.1/2-LK	1.1/2"	40	281	420
KHBF6-2-LK	2"	50	316	420
Tech Sheet 10171				

FAC
Fluid-Air Components Ltd

HYDRAULIC BALL VALVES

Hydraulic Ball Valves

Working Temperature:
-20°C to +120°C

- Carbon steel body
- Excellent sealing properties
- Zinc-plated C6F
- High pressure
- Steel ball
- Full flow



3 Way, L-Ported, BSPP, Nitrile Seals

0177	Thread	Length mm	Max Pressure Bar
KHB3K-G1/4	1/4"	69	500
KHB3K-G3/8	3/8"	72	500
KHB3K-G1/2	1/2"	83	500
KHB3K-G3/4	3/4"	95	315
KHB3K-G1	1"	113	315
KHB3K-G11/4	1.1/4"	110	315
KHB3K-G11/2	1.1/2"	130	315
Tech Sheet 2129			

Working Temperature:
-20°C to +120°C


- Carbon steel body
- Excellent sealing properties
- Zinc-plated C6F
- High pressure
- Steel ball
- Full flow



3 Way, T-Ported, BSPP, Nitrile Seals


0177	Thread	Length mm	Max Pressure Bar
KHB3T-G1/4	1/4"	69	500
KHB3T-G3/8	3/8"	72	500
KHB3T-G1/2	1/2"	83	500
KHB3T-G3/4	3/4"	95	315
KHB3T-G1	1"	113	315
KHB3T-G11/4	1.1/4"	110	315
KHB3T-G11/2	1.1/2"	130	315
Tech Sheet 2129			

Lockable Hydraulic Ball Valves



3 Way, L-Ported, BSPP, Nitrile Seals

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHB3K-G1/4-LK	1/4"	6	69	500
KHB3K-G3/8-LK	3/8"	10	72	500
KHB3K-G1/2-LK	1/2"	13	83	500
KHB3K-G3/4-LK	3/4"	20	95	315
KHB3K-G1-LK	1"	25	113	315
KHB3K-G11/4-LK	1.1/4"	25	110	315
KHB3K-G11/2-LK	1.1/2"	25	130	315
Tech Sheet 2129				



3 Way, T-Ported, BSPP, Nitrile Seals

0177	Thread	DN Size	Length mm	Max Pressure Bar
KHB3T-G1/4-LK	1/4"	6	69	500
KHB3T-G3/8-LK	3/8"	10	72	500
KHB3T-G1/2-LK	1/2"	13	83	500
KHB3T-G3/4-LK	3/4"	20	95	315
KHB3T-G1-LK	1"	25	113	315
KHB3T-G11/4-LK	1.1/4"	25	110	315
KHB3T-G11/2-LK	1.1/2"	25	130	315
Tech Sheet 2129				

Spare Handles



KHB Series Cranked Handles

0177	To Suit
KHBHANDLE-14-12	1/4" to 1/2"
KHBHANDLE-34-1	3/4" to 1"
KHBHANDLE-114-2	1.1/4" to 2"
Tech Sheet 2129	

Lock not included

Fluid-Air Components Ltd

Non-return Valves

Material: Carbon steel
Plating: Zinc-plated chrome free
Interchangeability: Stucchi VU, Holmbury ATR, VPC series
Cracking Pressure: 0.35 bar



High Pressure 0.35 to 0.5 bar Cracking Pressure, BSPP

0177	Thread	Length mm	Hex Size mm	Max Pressure Bar
EHRVG-14	1/4"	60	19	700
EHRVG-38	3/8"	70	24	700
EHRVG-12	1/2"	77	30	500
EHRVG-34	3/4"	90	36	500
EHRVG-1	1"	106	45	500
EHRVG-114	1.1/4"	125	55	400
EHRVG-112	1.1/2"	140	65	320
EHRVG-2	2"	160	75	320
Tech Sheet 10170				

Material: Carbon steel
Plating: Zinc-plated chrome free
Interchangeability: Stucchi VU, Holmbury ATR, VPC series
Cracking Pressure: 3 bar

3 bar Cracking Pressure, BSPP

0177	Thread	Length mm	Hex Size mm	Max Pressure Bar
EHRVG-14-3CP	1/4"	62	19	350
EHRVG-38-3CP	3/8"	68	24	350
EHRVG-12-3CP	1/2"	77	30	350
EHRVG-34-3CP	3/4"	88	36	350
EHRVG-1-3CP	1"	105	41	350
EHRVG-114-3CP	1.1/4"	135	55	300
EHRVG-112-3CP	1.1/2"	145	60	300
Tech Sheet 10170				

Material: Carbon steel
Plating: Zinc-plated chrome free
Interchangeability: Stucchi VU, Holmbury ATR, VPC series
Cracking Pressure: 5 bar

5 bar Cracking Pressure, BSPP

0177	Thread	Length mm	Hex Size mm	Max Pressure Bar
EHRVG-14-5CP	1/4"	62	19	350
EHRVG-38-5CP	3/8"	68	24	350
EHRVG-12-5CP	1/2"	77	30	350
EHRVG-34-5CP	3/4"	88	36	350
EHRVG-1-5CP	1"	105	41	350
EHRVG-114-5CP	1.1/4"	135	55	300
EHRVG-112-5CP	1.1/2"	145	60	300
Tech Sheet 10170				

Flow Control Valves

Body: Carbon steel
Handle: Aluminium
Spring: SS302 or C72
Standard O-Rings: Nitrile
Ring Stem: PTFE

Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
350 bar



Uni-directional (Controlled Flow One Direction, Free Flow Reverse), BSPP

0177	Thread	Mounting Thread
EHCVG1/4	1/4"	M20 x 1
EHCVG3/8	3/8"	M25 x 1
EHCVG1/2	1/2"	M30 x 1.5
EHCVG3/4	3/4"	M35 x 1.5
EHCVG1	1"	M35 x 1.5
Tech Sheet 2130		



Bi-directional (Controlled Flow Both Directions), BSPP

0177	Thread	Mounting Thread
EHTVG1/4	1/4"	M20 x 1
EHTVG3/8	3/8"	M25 x 1
EHTVG1/2	1/2"	M30 x 1.5
EHTVG3/4	3/4"	M35 x 1.5
EHTVG1	1"	M35 x 1.5
Tech Sheet 2131		

Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

STAINLESS STEEL HYDRAULIC VALVES

stainless steel

FTPRO

High Pressure Stainless Steel Ball Valves

Working Temperature:
-20°C to +120°C

- Nitrile seals



2 Way, BSPP

0098	Thread	Max Pressure Bar
HBVSS-14	1/4"	500
HBVSS-38	3/8"	500
HBVSS-12	1/2"	500
HBVSS-34	3/4"	315
HBVSS-1	1"	315
Tech Sheet 20888		

High Pressure Stainless Steel Block Style Ball Valves



2 Way, BSPP

0098	Thread	DN Size	Length mm	Max Pressure Bar
HBBVSS-14	1/4"	6	69	500
HBBVSS-38	3/8"	10	72	500
HBBVSS-12	1/2"	13	83	500
HBBVSS-34	3/4"	20	95	315
HBBVSS-1	1"	25	113	315
Tech Sheet 10224				

Due to the change of finishes used by our supplier, the product you receive may look slightly different to that illustrated.

Lockable High Pressure Stainless Steel Block Style Ball Valves

Lock not included



2 Way, BSPP

0098	Thread	DN Size	Length mm	Max Pressure Bar
HBBVSS-14-LK	1/4"	6	69	500
HBBVSS-38-LK	3/8"	10	72	500
HBBVSS-12-LK	1/2"	13	83	500
HBBVSS-34-LK	3/4"	20	95	315
HBBVSS-1-LK	1"	25	113	315
Tech Sheet 10224				

High Pressure Check Valves

Maximum Working Pressure:
350 bar



BSPP, 0.5 bar Cracking Pressure

0098	Thread
HCVSS-3/8	3/8"
HCVSS-1/2	1/2"
HCVSS-3/4	3/4"
HCVSS-1	1"
Tech Sheet 10043	

Locking Device



Stainless Steel

0177	To Suit
HPBVLD-1	DN6, DN8, DN10, DN13
HPBVLD-2	DN20, DN25
HPBVLD-3	DN32, DN38, DN50
Tech Sheet 10171	

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Needle Valves

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 210 bar

Body: Brass, nickel plated
Seal: Nitrile
Stem: 304 Stainless steel



In-line, Bi-directional (Controlled Flow Both Ways) Flow Control & Shut Off, BSPP


0274	Thread
1251-1010	1/8"
1251-1313	1/4"
1251-1717	3/8"
1251-2121	1/2"
Tech Sheet 10514	

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 210 bar

Body: Brass, nickel plated
Seal: Nitrile
Stem: 304 Stainless steel





Angled, In-line, Bi-directional (Controlled Flow Both Ways) Flow Control & Shut Off, BSPP


0274	Thread
1252-2010	1/8"
1252-2013	1/4"
1252-2017	3/8"
1252-2021	1/2"
Tech Sheet 10515	

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 210 bar

Body: Brass, nickel plated
Seal: Nitrile
Stem: 304 Stainless steel





In-line, Uni-directional (Controlled Flow One Way) with Free Reverse Flow, BSPP

0274	Thread
1253-3013	1/4"
1253-3017	3/8"
1253-3021	1/2"
Tech Sheet 10516	

Needle Valves - Speed Control

Working Temperature: -20°C to +100°C

Maximum Working Pressure:
400 bar: 1/4" to 3/4"
320 bar: 1"

Seal: Nitrile



Female x Female, BSPP

0274	Thread	Length mm	LPM	Return LPM
NCV-14	1/4"	55	50	70
NCV-38	3/8"	65	75	110
NCV-12	1/2"	73	140	150
NCV-34	3/4"	88	175	200
NCV-1	1"	127	350	275
Tech Sheet 10517				

Needle Valves - Flow Control

Working Temperature: -20°C to +100°C

Maximum Working Pressure:
400 bar: 1/4" to 3/4"
320 bar: 1

Seal: Nitrile



Female x Female, BSPP

0274	Thread	Length mm	LPM
INV-14	1/4"	48	50
INV-38	3/8"	58	75
INV-12	1/2"	68	140
INV-34	3/4"	78	175
INV-1	1"	108	350
Tech Sheet 10518			

Hydraulic Non-return Valves



High Pressure, Carbon Steel, BSPP

0268	Thread	Length mm	Max Pressure Bar	Cracking Pressure Bar
HNRV-14	1/4"	62	350	0.5
HNRV-38	3/8"	68	350	0.5
HNRV-12	1/2"	78	350	0.5
HNRV-34	3/4"	88	300	0.5
HNRV-1	1"	112	250	0.5
Tech Sheet 10519				

Panel Mounting Nuts



For Series INV & NCV


0274	To Suit
2570-13	1/4"
2570-17	3/8"
2570-21	1/2"
2570-26	3/4"

For Series 1251, 1252 & 1253

0274	To Suit
1203-1010	1/8"
1203-1313	1/4"
1203-1717	3/8"
1203-2121	1/2"

Diverter Valves


Manufactured from machined steel body with a hardened and ground spool, and a chemically blackened finish.



Three Port 2 Way, BSPP


0267	Thread	LPM	Max Pressure Bar
38-3DVL	3/8"	27	207
12-3DVL	1/2"	36	210
34-3DVL	3/4"	100	207
1-3DVL	1"	160	207

Four Port Open Centre, BSPP




0267	Thread	LPM	Max Pressure Bar
38-4DVOC	3/8"	27	207
12-4DVOC	1/2"	36	210

Three Port T, BSPP



0267	Thread	LPM	Max Pressure Bar
38-3DVT	3/8"	27	207
12-3DVT	1/2"	36	210

Four Port Closed Centre, BSPP



0267	Thread	LPM	Max Pressure Bar
38-DVCC	3/8"	27	207
12-DVCC	1/2"	36	210

Fluid-Air Components Ltd


THREADED HYDRAULIC VALVES

FT PRO

Direct Acting Sequence Valves

Pre-set and other spring ratings available on request.

Maximum Working Pressure:
350 bar






BSPP

0347	Thread	Pressure Range Bar
DASV06	3/8"	10-180
DASV08	1/2"	10-180
DASV12	3/4"	50-350
Tech Sheet 10098		

Pressure Relief Valves

Pre-set and other spring ratings available on request.

Maximum Working Pressure:
300 bar






BSPP

0347	Thread	Pressure Range Bar
RV06/180	3/8"	10-180
RV08/180	1/2"	10-180
RV12/180	3/4"	10-180
Tech Sheet 10101		

Dual Cross Relief Valve






BSPP

0347	Thread	Pressure Range Bar
DCRV04/180	1/4"	10-180
DCRV06/180	3/8"	10-180
DCRV08/180	1/2"	10-180
DCRV012/180	3/4"	10-180
Tech Sheet 10534		

Single Overcentre Valves

1:8 pilot ratio available on request.






BSPP

0347	Thread	Ratio
SOCV06	3/8"	1:3.1
SOCV08	1/2"	1:3.1
SOCV12	3/4"	1:5.5
Tech Sheet 10099		

Single Pilot Operated Check Valves

Other cracking pressures available on request.






BSPP

0347	Thread	Cracking Pressure Bar	Ratio
POCV04	1/4"	4	1:5.5
POCV06	3/8"	3	1:5.5
POCV08	1/2"	6	1:5
Tech Sheet 10102			

Pressure Reducing Valve, Direct Acting

15-55 bar range available on request.







BSPP

0347	Thread	Pressure Range Bar
PREDV06	3/8"	30-165
PREDV08	1/2"	30-165
Tech Sheet 10535		

Double Overcentre Valves






BSPP

0347	Thread	Ratio
DOCV06	3/8"	1:3.1
DOCV08	1/2"	1:3.1
DOCV12	3/4"	1:5.5
Tech Sheet 10100		

Double Pilot Operated Check Valves






BSPP

0347	Thread	Cracking Pressure Bar	Ratio
DPOCV04	1/4"	4.5	1:5.5
DPOCV06	3/8"	4.5	1:5.5
DPOCV08	1/2"	3	1:4.5
Tech Sheet 10103			

Fluid-Air Components Ltd

Shuttle Valves




BSPP

0347	Thread	Max Pressure Bar	LPM
SV04	1/4"	450	30
SV06	3/8"	450	45
SV08	1/2"	450	70
SV12	3/4"	350	110

Tech Sheet 10104

3 Way Diverter Valves

Closed centre configuration available on request.



Maximum Working Pressure: 250 bar




Open Centre, BSPP

0347	Thread	LPM
DV306	3/8"	35
DV308	1/2"	60
DV312	3/4"	100

Tech Sheet 10105

4 Way Diverter Valves

P to T, A and B closed, available on request.






All Ports Closed, BSPP

0347	Thread	LPM
DV406	3/8"	35
DV408	1/2"	60
DV412	3/4"	100

Tech Sheet 10106

Hose Burst Valves




Maximum Working Pressure: 350 bar



Female/Female, BSPP

0347	Thread	LPM
HBVF04	1/4"	25
HBVF06	3/8"	50
HBVF08	1/2"	80
HBVF12	3/4"	140
HBVF16	1"	180

Tech Sheet 10107




Maximum Working Pressure: 350 bar



Male/Female, BSPP

0347	Thread	LPM
HBVMF04	1/4"	25
HBVMF06	3/8"	50
HBVMF08	1/2"	80
HBVMF12	3/4"	140
HBVMF16	1"	180

Tech Sheet 10107



Maximum Working Pressure: 350 bar



Cartridge

0347	To Suit
HBVC04	1/4"
HBVC06	3/8"
HBVC08	1/2"
HBVC12	3/4"

Tech Sheet 10107

Hydraulic Swivel Joints


- Seal Nitrile
- Mounted between a hose assembly and rigid component in order to allow and compensate occasional rotations, preventing hose damage.



90° Swivel, BSPP

0507	Thread	Max Static Pressure Bar	Max Dynamic Pressure Bar
2019-3660	1/4"	400	200
2019-3678	3/8"	400	200
2019-3686	1/2"	300	150
2019-3694	3/4"	300	150
2019-3702	1"	300	100
2019-3703	1.1/4"	300	100
2019-3704	1.1/2"	300	80
2019-3705	2"	250	50

Tech Sheet 849



Straight Swivel, BSPP

0507	Thread	Max Rotating Pressure Bar	Max Dynamic Pressure Bar
2019-2639	1/4"	400	200
2019-3629	3/8"	400	200
2019-3637	1/2"	300	150
2019-3645	3/4"	300	150
2019-3652	1"	300	100
2019-3653	1.1/4"	300	100
2019-3654	1.1/2"	300	80
2019-3655	2"	250	50

Tech Sheet 848

Fluid-Air Components Ltd

THREADED HYDRAULIC VALVES

FT PRO

Barrel Flow Control Valve





BSPP

0347	Thread	LPM	Max Pressure Bar
BFCV04	1/4"	20	300
BFCV06	3/8"	45	300
BFCV08	1/2"	70	300
BFCV12	3/4"	110	250
BFCV16	1"	160	250

Tech Sheet 10536

Barrel Flow Control Valve, with Check




BSPP

0347	Thread	LPM	Max Pressure Bar
BFCVC04	1/4"	20	300
BFCVC06	3/8"	45	300
BFCVC08	1/2"	70	300
BFCVC12	3/4"	110	250
BFCVC16	1"	160	250

Tech Sheet 10537

Compensated Flow Control Valve

Maximum Working Pressure:
250 bar




BSPP

0347	Thread	LPM
CFVC04	1/4"	25
CFVC06	3/8"	30
CFVC08	1/2"	45

Tech Sheet 10538

3 Port Flow Control Valve, Ongoing to Pressure





BSPP

0347	Thread	LPM
3FCVP06	3/8"	60
3FCVP08	1/2"	80
3FCVP12	3/4"	120
3FCVP16	1"	200

Tech Sheet 10539

3 Port Flow Control Valve, Excess to Tank

Maximum Working Pressure:
350 bar





BSPP

0347	Thread	LPM
3FCVT06	3/8"	60
3FCVT08	1/2"	80
3FCVT12	3/4"	120

Tech Sheet 10540

2 Way Flow Divider, Cast Iron

Maximum Working Pressure:
250 bar





BSPP

0347	Inlet Thread	Outlet Thread	LPM
CFD063	3/8"	3/8"	3
CFD066	3/8"	3/8"	6
CFD0610	3/8"	3/8"	10
CFD0620	3/8"	3/8"	20
CFD0632	3/8"	3/8"	32
CFD0840	1/2"	3/8"	40
CFD0860	1/2"	3/8"	60
CFD0880	1/2"	3/8"	80

Tech Sheet 10541

2 Way Flow Divider, Steel

Maximum Working Pressure:
250 bar




BSPP

0347	Inlet Thread	Outlet Thread	LPM
SFD0610	3/8"	3/8"	10
SFD0620	3/8"	3/8"	20
SFD0840	1/2"	3/8"	40
SFD0860	1/2"	3/8"	60

Tech Sheet 10542

Male Check Valve




BSPP, 1 bar Cracking Pressure

0347	Thread	Max Pressure Bar
MVC04	1/4"	350
MVC06	3/8"	350
MVC08	1/2"	350
MVC12	3/4"	350
MVC16	1"	320
MVC20	1.1/4"	320
MVC24	1.1/2"	320
MVC32	2"	320

Tech Sheet 10543

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC FILTRATION

High Pressure In-line Filters

Features:
- Filter element remains in filter bow
- Environmentally-friendly design
- Bypass valve integral part of filter bow

Benefits
- Avoid use of non-genuine parts
- Less space needed to change/service filte
- Reduces environmental waste by over 50%
- No handling of loose reusable parts
- Easy to integrate in manifold systems
- Lower pressure lost across filte

Typical Applications:
- Mobile working hydraulics
- Mobile drive system
- Pilot line filtratio
- Servo controls
- Reverse flow valve application
- Industrial working hydraulics
- Control systems

iprotect® glass fibre element as standard

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
450 bar

Also available with various connections:
- SAE flanged
- SAE threaded
- ISO metric
- Manifold mounted



EPF Series, 7 bar Bypass

0045	Thread	LPM	Micron
EPF1105QIBPMG081	1/2"	40	5
EPF1110QIBPMG081	1/2"	40	10
EPF2205QIBPMG121	3/4"	140	5
EPF2210QIBPMG121	3/4"	140	10
EPF3205QIBPMG161	1"	250	5
EPF3210QIBPMG161	1"	250	10
EPF4205QIBPMG201	1.1/4"	450	5
EPF4210QIBPMG201	1.1/4"	450	10
EPF5105QIBPMG241	1.1/2"	500	5
EPF5110QIBPMG241	1.1/2"	500	10
Tech Sheet 67979			

High Pressure Replacement Elements



2 Micron Element

0045	Manufacturer's Code	To Suit
EPF1-12-2	944418Q	EPF1
EPF2-34-2	944430Q	EPF2
EPF3-1-2	944438Q	EPF3
Tech Sheet 67979		

5 Micron Element

0045	Manufacturer's Code	To Suit
EPF1-12-5	944419Q	EPF1
EPF2-34-5	944431Q	EPF2
EPF3-1-5	944439Q	EPF3
EPF4-114-5	944447Q	EPF4
Tech Sheet 67979		

10 Micron Element

0045	Manufacturer's Code	To Suit
EPF1-12-10	944420Q	EPF1
EPF2-34-10	944432Q	EPF2
EPF3-1-10	944440Q	EPF3
EPF4-114-10	944448Q	EPF4
Tech Sheet 67979		

20 Micron Element

0045	Manufacturer's Code	To Suit
EPF1-12-20	944421Q	EPF1
EPF2-34-20	944433Q	EPF2
EPF5-112-20	944453Q	EPF5
Tech Sheet 67979		

High Pressure In-line Filter Accessories



Visual Clogging Indicators

0045	Port Size
FMUM3MVMS08	S08 Cavity
Tech Sheet 67979	

- Enclosure class IP65
- Electrical connector DIN 43650
- Overvoltage category II (EN61010-1)



Electrical Clogging Indicators

0045	Port Size
FMUT1MVMS08	S08 Cavity
Tech Sheet 67979	

Fluoroelastomer also available



Nitrile Seal Kits

0045	To Suit
EPFSK001	EPF1
EPFSK002	EPF2
EPFSK003	EPF3
EPFSK004	EPF4 & 5
Tech Sheet 67979	

Fluid-Air Components Ltd

HYDRAULIC FILTRATION

Medium Pressure Filters

Features:
- More compact solutions are possible
- Filter element remains in filter bowl during filter servi
- Reduces waste over 50% thanks to reusable element core
- No risk of installation mistake due to a 'foolproof' design
- Easy to integrate into hydraulic manifold solutions

Benefits
- Avoid use of non-genuine parts
- Less space needed to change/service filte
- No handling of loose reusable parts
- Lower pressure lost across filte

Typical Applications:
- Compressor lube oil
- Off-line filter loops
- Machine tools (automotive standard)
- Hydrostatic drive charge pumps
- Mobile equipment
- Pilot lines for servo controls
- Oil patch drilling equipment




Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
70 bar

GMF Series

0045	Thread	LPM	Micron
GMF2110QIVPKG164	1"	55	10
GMF2210QIVPKG164	1"	90	10
GMF3110QIVPKG244	1.1/2"	120	10
GMF3210QIVPKG244	1.1/2"	230	10
GMF4110QIVPKG324	2"	350	10
GMF4210QIVPKG324	2"	530	10
Tech Sheet 67980			

Medium Pressure Replacement Elements



10 Micron Element

0045	Manufacturer's Code	To Suit
GMF321-112-10	938909Q	GMF321
GMF411-2-10	938913Q	GMF411
Tech Sheet 67980		

Medium Pressure In-line Filter Accessories




Visual Clogging Indicators

0045	Port Size
FMUM3KVMS08	S08 Cavity
Tech Sheet 67980	



Electrical Clogging Indicators

0045	Port Size
FMUT1KVMS08	S08 Cavity
Tech Sheet 67980	



Nitrile Seal Kits

0045	To Suit
930000140	GMF21 & 22
930000141	GMF31 & 32
930000142	GMF41 & 42
Tech Sheet 67980	

Viton Seal Kits

0045	To Suit
930000149	GMF21 & 22
930000150	GMF31 & 32
930000151	GMF41 & 42
Tech Sheet 67980	

Fluid-Air Components Ltd

HYDRAULIC FILTRATION

Gauge Isolator Valves

Designed to prevent pressure gauge damage and extend gauge life. The gauge isolator valve when installed between gauge and pressure line protects the pressure gauge from continuous hydraulic pressure, surges or shock loads.

Single Station:
Cast iron and steel. Knurled aluminium knob twist to lock or push to read type.
Maximum W/P:
350 bar
Port Size:
Single station = G1/4
Weight:
Single station = 0.90kg



Single Station

0045	Description	Port Size
GI1414	Push to Read	1/4"

For **Pneumatic Valves & Accessories** see page **564**



Modular Filler Breathers

Construction:
Moulded in non-corrodible glass-filled nylon combining strength with lightweight design.
Options:

- Single 63mm diameter hole filler breather installation that eliminates drilled and tapped holes using self-locking clamps
- 6 hole filler breather installation that uses 6 x No. 10 thread forming screws
- 3 hole filler breather installation that uses 3 x No. 10 thread forming screws

Filtration: Expanded polyurethane foam, 10 micron.
Seals: Nitrile.



Un-pressurised, 10 Micron

0045	Description
AB98210011UC	Single Hole
AB98810011UC	6 Hole
AB68118	3 Hole
Tech Sheet 636	

Screw-on Type Air Breather (IP65)

Manufactured from non-corrodible glass filled nylon



Un-pressurised 10 Micron, BSPP, 101mm Diameter

0045	Thread
AB98410101UC	3/4"
Tech Sheet 636	

Manufactured from in glass filled nylon and glass-coupled polypropylene.

Un-pressurised 10 Micron, BSPP, 70mm Diameter

0045	Thread
SAB6101	G1/2
SAB7101	G3/4

Suction Strainers

Construction:

- Stainless steel media 30% glass-filled nylon hea
- Zintec centre tube and end cap
- Epoxy adhesives

Filter Media: 125 micron.
Flow Range: 15-500 L/min.
Mounting Threads: G1/2 up to G3

Maximum Working Temperature:
+90°C



BSPP, Without Bypass

0045	Old Ref	Thread	LPM
SE1319	SS1A1S1AP	1/2"	15
SE1320	SS1B2A1AP	3/4"	25
SE1457	SS1B3A1AP	1"	50
SE1323	SS1C4A1AP	1.1/2"	95
SE1324	SS1C5A1AP	1.1/2"	130
SE1326	SS1C6A1AP	2"	180
SE1219	SS1D7A1AP	2"	225
SE1221	SS1D9A1AP	3"	500
Tech Sheet 60433			

BSPP, With Bypass

0045	Thread	LPM
SE5100	1/2"	15
SE5101	3/4"	25
SE5102	1"	50
SE5103	1.1/2"	95
SE5104	1.1/2"	130
SE5105	2"	180
SE5106	2"	225
SE5107	2.1/2"	350
SE5108	3"	500
Tech Sheet 60433		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC FILTRATION

Maxiflo

Seal: Nitrile
Filter Bowl Material: Steel
Fluids: Mineral oils
Filter Head Material: Aluminium LM24



Working Temperature:
-30°C to +90°C

Maximum Working Pressure:
7 bar

BSPP

0045	Thread	LPM	Material
MXA9551424	1.1/4"	160	Microglass
MXA9511424	1.1/4"	160	Paper



Replacement Elements

0045	Model	Quantity
MXR8550	MXA8551424	1
MX1518410X4	MXA8551223, MX8551023 & 12PS10CTV1R2B	4
MXR9560	MXA9561424	1
MXR9550	MXA9551424	1
MX1591.4.10X4	MXA9511424 & MXA9511223	4

Mini Pressure Filter

- Compact, robust and easy to install
- Manufactured in high quality brass
- 10µ, 25µ, and 125µ elements
- No indicator filter
- G1/4 ports
- For use in lubrication, high pressure water and oil burner systems
- Reliable protection of low flow pilot valve
- Suitable for use with mineral and petroleum based fluid
- Nitrile seal

Filtration Media:
10 micron (nominal) Nitrile phenolic resin impregnated cellulose.
25µ, 40µ and 125µ (nominal) stainless steel.
Please note: HPR1719 and HPR1819 elements are not stainless steel, they are paper with tin end caps.



Working Temperature:
-30°C to +90°C

Maximum Working Pressure:
280 bar

Filters

0045	Old Ref	Micron	LPM
HPA1619100	HP122910	10	6
HPA1719100	HP122925	25	17
HPA1819100	HP122940	40	18

Replacement Elements

0045	Old Ref	To Suit
HPR1619	R122910	HPA1619100
HPR1719	R122925	HPA1719100
HPR1819	R122940	HP1819100

In-line Spin-on Filters

- Paper and glass fibre element medi
- Spin-on disposable canisters
- Suitable for suction and return line applications
- Flow rates to 350 L/min.
- Bypass
- Visual indicator

Seals: Buna Nitrile.
Filter Head Material: Aluminium alloy.
Fluids: Compatible with hydraulic oils, coolant fluids and petroleum based fluids
Filter Bowl Material: Steel.
Element Media:
10CT = 10 micrometer nominal filtration (resin impregnated cellulose).
10BT = 10 micrometer absolute filtration (glass fibr composite material).
Indication:
42mm dia gauge: (0-12 bar. Return line). 0-76cm. Hg Suction line.



Working Temperature:
-30°C to +100°C

Maximum Working Pressure:
7 bar

10BT, BSPP

0045	Thread	LPM Suction & Return
12PS10BTV1R2B	3/4"	65

Replacement Elements

0045	To Suit
926501	12PS10BTV1R2B

Diffusers

Construction:
- Zintec body, 30% glass-filled nylon hea
- Zintec end cap
- Epoxy adhesives

Flow Range:
50 L/min up to 454 L/min.
Mounting Threads:
3/4" up to 2".
Designed to reduce fluid aeration, foaming and reservoir noise in fluid systems, extends pump life by reducing cavitation to pump inlet, ranging from 50-454 L/min and port sizes G3/4 up to G2. Suitable for all mineral base fluids



BSPP

0045	Thread	LPM
2210	3/4"	50
2201	1"	114
2202	1.1/2"	227
2203	2"	454

Fluid-Air Components Ltd

HYDRAULIC FILTRATION

Tank Top Filters

Working Temperature:
-30°C to +90°C

Maximum Working Pressure:
280 bar



1" BSPP

0045	LPM	Bypass PSIG	Micron
FTB1A10QV25G16X	120	25	10
Tech Sheet 1338			

1" BSPP, Replacement Element

0045	Description	Micron
FTBE2A20Q	Replacement Element	20

Tanktopper offers a total filtration solution with integrated air breathe .
Patented LEIF elements safeguard filtration qualit .

Working Temperature:
-40°C to +80°C

Maximum Working Pressure:
10 bar



Tanktopper Series

0045	Thread	LPM
TPR110QLBP2EG12E	3/4"	40
TPR510QLBP2E2G20	1.1/4"	120
TPR710QLBP2E2G24	1.1/2"	250
Tech Sheet 60430		

TTF features pre-filtration by means of a magnet column
Flow from inside to out.

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
10 bar



TTF Series

0045	Thread	LPM
TF310QLBP2EG121	3/4"	90
TF610QLBP2EG203	1.1/2"	170
TF810QLBP2EG243	1.1/2"	300
TF1010QLBP2HG24A	1.1/2"	500
Tech Sheet 60431		

Compact tank top mounted return line filte .
Filter element can be used for direct screw-in mounting with co-polymer reservoirs.
Inside to out flow avoids re-contamination of the system

Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
10 bar



PT Tank Top Mounted Filter Series

0045	Thread	LPM
PT2110QBPGG124	3/4"	25
PT2210QBPGG124	3/4"	50
PT4110QBPGG164	1"	110
PT4210QBPGG164	1"	175
Tech Sheet 60432		

Non-corrodible In-line Filter



Working Temperature:
-30°C to +80°C

Maximum Working Pressure:
7 bar

Oil, BSPP

0045	Thread
IL1151	1"
Tech Sheet 1340	

Water, BSPP

0045	Thread
IL1251	1"
Tech Sheet 1340	

Replacement Element for Oil

0045
R76115
Tech Sheet 1340

Replacement Element for Water

0045
R76125
Tech Sheet 1340

Fluid-Air Components Ltd

HYDRAULIC FLOW METERING

Easiflow Meter

Working Temperature:
+5°C to +80°C
+60°C with water

Maximum Working Pressure:
10 bar

- Oil and water calibrated
- Works in any plane
- Pressures up to 10 bar
- Switches – Fully adjustable flow rate signalling
- Plant and equipment protection
- Switches – Colour coded by application and AC/DC options

Construction:

Cone:	Acetal
Viewing Glass:	Borosilicate glass
Calibrated Spring:	Stainless steel
Seal:	Nitrile
Body:	Glass filled nylo
Flow Range:	1-150 L/min
Viscosity Range:	10-200 centistrokes
Accuracy:	±5% FSD
Repeatability:	±1% FSD
Connections:	1" BSPP
Weight:	0.4kg



Oil

0045	LPM
EFL0301	2-30
EFL0501	4-50
EFL1001	5-100
EFL1501	10-150



Water

0045	LPM
EFW0152	1-15
EFW0302	2-30
EFW0502	4-50
EFW1002	5-100
EFW1502	10-150

Fluid Level & Temperature Gauges

Working Temperature:
-30°C to +90°C


Maximum Working Pressure:
1 bar

Construction:
- Lens transparent polyamide
- Lens base nylon 66
- No aluminium content
- Shroud high impact polystyrene

Seals: Nitrile.

Fluid Compatibility:
Mineral and petroleum based fluids





Fluid Level

0045	Centres mm	Thread
FL111	76	M10
FL211	127	M10
FL311	254	M10
FL112	76	M12
FL212	127	M12
FL312	254	M12
Tech Sheet 10301		

Fluid Level Temperature

0045	Centres mm	Thread
FLT121	76	M10
FLT221	127	M10
FLT321	254	M10
FLT112	76	M12
FLT212	127	M12
FLT312	254	M12
Tech Sheet 10301		

Dataflow In-line Flow Indicatio

Working Temperature:
+5°C to +80°C Oil
+5°C to +60°C Water

Maximum Working Pressure:
10 bar Oil/water

- Indicator gives flow visibilit
- Works in any plane
- Accepts reverse flo
- Indicates flow from 2-150 L/mi



Indicator

0045	Description
DFI900	Dataflow Indicator
Tech Sheet 1341	

Hydraulic Test Unit



Hydraulic test units are designed specifically for the speedy diagnosis of hydraulic circuit faults in mobile, marine and industrial systems using normal range of mineral oils, their rugged construction based mainly on mild steel, manganese bronze and acrylic materials makes them ideally suited for arduous use in the field

Each unit is supplied in a convenient carrying case providing full protection and additional storage space for fittings. Because they need no power source such as batteries etc, they are always ready for instant use.

The scale on the flow meter can be rotated to ensure visibility in any situation and the installed attitude is not critical, though whenever possible the unit should be monitored with pressure gauge vertical and gauge case relief valve uppermost. **The unit is designed for flow to be in the direction of the arrow on the flow meter scale and must not be installed with the flow reversed**

Safety

An axial flow restrictor valve is fitted which can b adjusted under full load from open to fully closed, and to complete the specification, a safety blow out disc, set to operate at 455 bar is fitted to the manifold in a position facing away from the operator when reading the gauges normally. Two spare blow out discs are supplied which are easily replaced by removing the hexagonal plug on the gauge manifold.

- Speedy diagnosis of hydraulic circuit faults
- Flows ranging from 2-360 L/min
- Measuring flo , pressure and temperature
- Portable. No power source required
- Hydrotrac unit for flows from 2-110 L/min availabl

Working Temperature:
0°C to +100°C

Flow Range:
10-110 L/min

Maximum Working Pressure:
350 bar

BSPP

0045	Thread
4121	3/4"

Fluid-Air Components Ltd
efnkl iroirp c cc a cc

HYDRAULIC FLOW METERING

Dataflow 4-20mA & Pulse Output Flow Transmitters



- Pulse output available for totalising/batching
- Works in any plane
- Accepts reverse flo
- Maximum flow 150 L/mi
- Negligible pressure drop
- Pressures up to 10 bar
- Low cost. Simple to install
- For use with most liquids
- DIN connection

Construction:
Borosilicate glass tube, Nitrile seals.

Body:	Glass filled nylon
Rotor and Locator:	Acetal.
Washers and shaft:	Stainless steel.
Rotor Tips:	Stainless steel.

Minimum Flow:
2 L/min (Max 150 L/min). Accepts reverse flo .

Accuracy: ±2%.

Connection: 1" BSPP.

Weight: 0.7kg.

Calibration 4-20mA:
4-20mA = 0-100 L/min on water.
4mA = 0 L/min, 20mA = 100 L/min.

Pulse Output: K factors CE.
Oil: 51.14 pulses per litre.
Water: 44.25 pulses per litre.

Electrical Details:
4-20mA:
Supply = 24V DC. Output = 4-20mA.

Pulse Output:
Supply = 24V DC-pulse output.
(open collector transistor).

Working Temperature:
+5°C to +80°C Oil
+5°C to +60°C Water

Maximum Working Pressure:
10 bar oil/water

Dataflow ransmitters

0045	Description
DFT980	Dataflow Pulse Output Transmitter

Loflow Oil, ater & Air Flowmeters



- Flow measurement from 7.0 ml/min to 22 L/min
- Easy to read, permanent printed scales
- Large scale definition for precise measuremen
- Easy panel mounting assembly
- Negligible pressure drop characteristics
- 10 bar pressure rating

Construction:

Body:	Grillon TR55.
Back Body:	ABS7020.
Ball Retainer:	ABS7020.
Back Panel:	PVC.

Accuracy: ±2% FSD.

Repeatability: ±1%.

Connections:
Inlet 1/4" or 3/4" tapered threads.
Outlet 3/4" tapered threads.

Typical Applications:
- Monitoring inert gases for the welding industry
- Pollution monitoring
- Pharmaceutical industry
- Filtration systems
- Hospital equipment for water applications
- Water treatment
- Swimming pools

Water BSPT, Inlet

0045	Media	Thread	LPM	Float Material
LF2020	Water	3/4"	0.2-2.0	Acetal
LF2100	Water	3/4"	1.5-10.0	S/S
LF2220	Water	3/4"	2.0-22.0	S/S
Tech Sheet 10321				

Air BSPT, Inlet

0045	Media	Thread	LPM	Float Material
LF3007E	Air	1/4"	1-7.0	Acetal
LF3050E	Air	3/4"	10-50.0	Acetal
LF3135E	Air	3/4"	20-135.0	Acetal
LF3330E	Air	3/4"	1.5-5.5 l/sec	S/S
LF3720E	Air	3/4"	1-12.0 l/sec	S/S
Tech Sheet 10321				

Oil BSPT, Inlet

0045	Media	Thread	LPM	Float Material
LF1002	Oil	3/4"	0.010-0.20	S/S
LF1009	Oil	3/4"	0.1-0.9	Acetal
LF1090	Oil	3/4"	1.0-9.0	S/S
Tech Sheet 10321				

Flowline Oil & Water Calibrated Flowmeters, Stainless Steel

- For flow measurement of corrosive or chemical media
- Works in any position
- Pressure up to 350 bar (5000psi)
- Flows up to 360 L/min
- Direct reading



Construction:
Stainless steel to BS970 316S

Calibration:
Oil = Specific gravity 0.856 at 20°
Water = Specific gravity 1.0 at 20°

Viscosity Range: 10-200 centistokes

Accuracy: ±5% FSD

Repeatability: ±1% FSD

Minimum Scale: ±1% FSD 10% FSD.

Connections: BSPP

Seal: Viton

Wetted Parts:
Body, Thread, Adaptor, Piston etc:
Cone Locknut Stainless steel BS 970316S 16

Magnet Encapsulation:
Stainless steel BS970/1:1991:316S31

Spring: Stainless steel to BS2056 EN58J

Working Temperature:
-20°C to +105°C

Maximum Working Pressure:
350 bar

Stainless Steel, BSPP, Red - Oil

0045	Thread	LPM	Max Pressure Bar
FM26332112	3/4"	5-55	350
FM26332212	3/4"	10-110	350

Stainless Steel, BSPP, Yellow - Water

0045	Thread	LPM	Max Pressure Bar
FM26332122	3/4"	5-55	350
FM26332222	3/4"	10-110	350

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FLOW METERING

Compressed Air Flowmeters, Brass

Working Temperature: -20°C to +90°C

Maximum Working Pressure: 41 bar

- Calibrated for direct reading of compressed air at 7 bar
- Works in any plane
- Calibrated at 7 bar and 20°C
- Flow ranges from 2-600 SCFM
- Maximum working pressure 41 bar

Construction:
Brass Body to BS2874 CZ114

Calibration:
Oil = Specific gravity 0.856 at 20°C
Water = Specific gravity 1.0 at 20°C

Viscosity Range: 10-200 centistokes
Accuracy: ±5% FSD
Repeatability: ±1% FSD
Minimum Scale: 10% FSD
Connections: BSPP

- Works in any position
- Flows up to 1100 L/min
- Direct reading
- Relatively insensitive to viscosity changes
- Oil or water calibrated



Brass, Blue - Air, BSPP

0045	Thread	SCFM	LPS
FM26223132	1/2"	5-50	2-25
FM26223232	1/2"	10-110	5-50

Flowline Oil & Water Calibrated Flowmeters, Brass

Working Temperature: -20°C to +90°C

Maximum Working Pressure: 350 bar

Construction:
Brass body to BS2874 CZ114

Calibration:
Oil = Specific gravity 0.856 at 20°C

Viscosity Range: 10-200 centistokes
Accuracy: ±5% FSD
Repeatability: ±1% FSD
Minimum Scale: 10% FSD
Connections: BSPP

- Works in any position
- Pressure up to 350 bar (5000psi)
- Flows up to 360 L/min
- Direct reading
- Relatively insensitive to viscosity changes



Brass, Red - Oil, BSPP

0045	Thread	LPM	Max Pressure Bar
FM26122212	1/4"	0.5-4.5	350
FM26222112	1/2"	2-20	350
FM26322112	3/4"	5-55	350
FM26322212	3/4"	10-110	350

spradow
german engineering at your service

Customers who bought from this page also purchased **Hydraulic Test Points**
see pages **268-272**



FAC
Fluid-Air Components Ltd

Tank Top Return Filter



1 bar By-pass, 7 bar Working Pressure, BSPP

0347	Thread	Micron
TTF-08B-10	1/2"	10
TTF-08B-25	1/2"	25
TTF-12B-10	3/4"	10
TTF-12B-25	3/4"	25
TTF-16B-10	1"	10
TTF-16B-25	1"	25
TTF-20B-10	1.1/4"	10
TTF-20B-25	1.1/4"	25
Tech Sheet 10051		



Replacement Element to suit TTF Housing

0347	To Suit	Micron
TTE-08-10	1/2"	10
TTE-08-10-A	1/2"	10ABS
TTE-08-25	1/2"	25
TTE-12-10	3/4"	10
TTE-12-10-A	3/4"	10ABS
TTE-12-25	3/4"	25
TTE-16-10	1"	10
TTE-16-10-A	1"	10ABS
TTE-16-25	1"	25
TTE-20-10	1.1/4"	10
TTE-20-10-A	1.1/4"	10ABS
TTE-20-25	1.1/4"	25
Tech Sheet 10051		

Suction Strainers



149 Micron, Nylon, BSPP


0347	To Suit	LPM
SS020-08	1/2"	20
SS030-12	3/4"	30
SS040-16	1"	40
SS080-20	1.1/4"	80
SS120-24	1.1/2"	120
SS200-24	1.1/2"	200
SS200-32	2"	200
SS300-40	2.1/2"	300
SS400-48	3"	400
Tech Sheet 10052		



149 Micron, Aluminium, BSPP

0347	To Suit	LPM
SSA020-08	1/2"	20
SSA028-12	3/4"	28
SSA040-16	1"	40
SSA060-20	1.1/4"	60
SSA080-24	1.1/2"	80
SSA120-24	1.1/2"	120
SSA160-32	2"	160
SSA200-32	2"	200
SSA300-40	2.1/2"	300
SSA400-40	3"	400
Tech Sheet 20010		

TTF Seal Kit



Seal Kit to suit TTF Housing

0347	To Suit
TTF-SK-08	1/2"
TTF-SK-12	3/4"
TTF-SK-16	1"
TTF-SK-20	1.1/4"

Return Line Diffuser



BSPP

0347	Thread	LPM
RLD-12	3/4"	50
RLD-16	1"	100
RLD-20	1.1/4"	200
RLD-24	1.1/2"	300
RLD-32	2"	400
RLD-40	2.1/2"	500
RLD-48	3"	600
Tech Sheet 10053		

Aluminium In-line Heavy-duty Return Filter

Suction and no by-pass models available on request



Maximum Working Temperature:
+80°C

Maximum Working Pressure:
20 bar

1 bar By-pass, BSPP

0347	Thread	Micron
ILRF1-08-10	1/2"	10
ILRF1-08-25	1/2"	25
ILRF2-12-10	3/4"	10
ILRF2-12-25	3/4"	25
ILRF2-16-10	1"	10
ILRF2-16-25	1"	25
ILRF3-20-10	1.1/4"	10
ILRF3-20-25	1.1/4"	25
ILRF3-24-10	1.1/2"	10
ILRF3-24-25	1.1/2"	25
Tech Sheet 10215		

Absolute and stainless steel mesh elements available on request



Replacement Element to suit ILFR*

0347	To Suit	Micron
ILFE-1-10	ILFR1	10
ILFE-1-25	ILFR1	25
ILFE-2-10	ILFR2	10
ILFE-2-25	ILFR2	25
ILFE-3-10	ILFR3	10
ILFE-3-25	ILFR3	25
Tech Sheet 10215		

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HYDRAULIC ACCESSORIES

Spin-on Filter Assemblies

- Disposable spin-on element
- Die-cast aluminium head
- 5 sizes, flows to 200 L/min
- 2232 Bypass standard 1 bar (suction 0.2 bar)
- For use with mineral/petroleum based oils

Maximum Working Temperature:
+80°C

Maximum Working Pressure:
10 bar



In-line Return, BSPP

0347	Thread	Micron	LPM
SPR08-10-35	1/2"	10	35
SPR08-10-70	1/2"	10	70
SPR08-10-100	1/2"	10	100
SPR08-25-35	1/2"	25	35
SPR08-25-70	1/2"	25	70
SPR08-25-100	1/2"	25	100
SPR12-10-35	3/4"	10	35
SPR12-10-70	3/4"	10	70
SPR12-10-100	3/4"	10	100
SPR12-25-35	3/4"	25	35
SPR12-25-70	3/4"	25	70
SPR12-25-100	3/4"	25	100
SPR16-10-35	1"	10	35
SPR16-10-70	1"	10	70
SPR16-10-100	1"	10	100
SPR16-25-35	1"	25	35
SPR16-25-70	1"	25	70
SPR16-25-100	1"	25	100
SPR20-10-150	1.1/4"	10	150
SPR20-10-200	1.1/4"	10	200
SPR20-25-150	1.1/4"	25	150
SPR20-25-200	1.1/4"	25	200

Tech Sheet 10054

In-line Suction, BSPP

0347	Thread	Micron	LPM
SPS08-10-35	1/2"	10	35
SPS08-10-70	1/2"	10	70
SPS08-10-100	1/2"	10	100
SPS08-25-35	1/2"	25	35
SPS08-25-70	1/2"	25	70
SPS08-25-100	1/2"	25	100
SPS12-10-35	3/4"	10	35
SPS12-10-70	3/4"	10	70
SPS12-10-100	3/4"	10	100
SPS12-25-35	3/4"	25	35
SPS12-25-70	3/4"	25	70
SPS12-25-100	3/4"	25	100
SPS16-10-35	1"	10	35
SPS16-10-70	1"	10	70
SPS16-10-100	1"	10	100
SPS16-25-35	1"	25	35
SPS16-25-70	1"	25	70
SPS16-25-100	1"	25	100
SPS20-10-150	1.1/4"	10	150
SPS20-10-200	1.1/4"	10	200
SPS20-25-150	1.1/4"	25	150
SPS20-25-200	1.1/4"	25	200

Tech Sheet 10054

Visual Indicator



Return, NPT

0347	Thread
VRG	1/8"

Tech Sheet 10054



Suction, NPT

0347	Thread
VSG	1/8"

Tech Sheet 10054

Return/Suction In-line Spin-on Filter Heads



Working Pressure 10 bar, BSPP Post, BSPP Ports

0347	Thread	Description
SRFH-08	1/2"	Return
SSFH-08	1/2"	Suction
SRFH-12	3/4"	Return
SSFH-12	3/4"	Suction
SRFH-16	1"	Return
SSFH-16	1"	Suction
SRFH-20	1.1/4"	Return
SSFH-20	1.1/4"	Suction

Tech Sheet 10054

Spin-on Element to suit S*FH



BSPP

0347	To Suit	Micron	LPM
SE-035-10-12	1/2"	10	35
SE-035-10A-12	1/2"	10ABS	35
SE-035-25-12	1/2"	25	35
SE-070-10-12	3/4"	10	70
SE-070-10A-12	3/4"	10ABS	70
SE-070-25-12	3/4"	25	70
SE-100-10-12	1"	10	100
SE-100-10A-12	1"	10ABS	100
SE-100-25-12	1"	25	100
SE-150-10-20	1.1/4"	10	150
SE-150-25-20	1.1/4"	25	150
SE-200-10-20	1.1/4"	10	200
SE-200-25-20	1.1/4"	25	200

Tech Sheet 10054

Fluid-Air Components Ltd

HIGH PRESSURE HYDRAULIC FILTRATION

Pressure line filters are an essential part in most hydraulic systems. When the hydraulic components are sophisticated, with close tolerances and a regulation function (not simply that of control), the use of filters in the pressure lines is a must.

The UFI Hydraulic Division pressure filters are named 'COMPO CARE because they take care of system components, ensuring the recommended cleanliness levels.

Filter elements are manufactured from glass fibre and cellulose media

Materials:
- Cast iron head
- Steel bowl
- Steel bypass valve
- NBR nitrile seals (FKM fluoroelastomer on request
- Brass indicator housing

Pressures: (ISO 10771-1:2002)
- Maximum working: 42 MPa (420 bar)
- Test: 62 MPa (620 bar)
- Bursting: 126 MPa (1.260 bar)
- Collapse differential for the filter element (ISO 2941):
  - Series standard 2 MPa (20 bar)
  - Series H+ 21 MPa (210 bar)

PB Series Filters, 420 bar

Working Temperature: -25°C to +110°C

Maximum Working Pressure: 420 bar



BSPP Ported, No Indicator, Bypass 6 bar, 5 Micron

0526	Thread	Filter Element Size
FPB12B04CNFA03EX	1/2"	12
FPB13B06CNFA03EX	3/4"	13
FPB21B08CNFA03EX	1"	21
FPB31B10CNFA03EX	1.1/4"	31
FPB33B12CNFA03EX	1.1/2"	33
FPB34B12CNFA03EX	1.1/2"	34
Tech Sheet 68074		

BSPP Ported, No Indicator, Bypass 6 bar, 12 Micron

0526	Thread	Filter Element Size
FPB12B04CNFC03EX	1/2"	12
FPB13B06CNFC03EX	3/4"	13
FPB21B08CNFC03EX	1"	21
FPB31B10CNFC03EX	1.1/4"	31
FPB33B12CNFC03EX	1.1/2"	33
FPB34B12CNFC03EX	1.1/2"	34
Tech Sheet 68074		

BSPP Ported, No Indicator, Bypass 6 bar, 7 Micron

0526	Thread	Filter Element Size
FPB12B04CNFB03EX	1/2"	12
FPB13B06CNFB03EX	3/4"	13
FPB21B08CNFB03EX	1"	21
FPB31B10CNFB03EX	1.1/4"	31
FPB33B12CNFB03EX	1.1/2"	33
FPB34B12CNFB03EX	1.1/2"	34
Tech Sheet 68074		

BSPP Ported, No Indicator, Bypass 6 bar, 21 Micron

0526	Thread	Filter Element Size
FPB12B04CNFD03EX	1/2"	12
FPB13B06CNFD03EX	3/4"	13
FPB21B08CNFD03EX	1"	21
FPB31B10CNFD03EX	1.1/4"	31
FPB33B12CNFD03EX	1.1/2"	33
FPB34B12CNFD03EX	1.1/2"	34
Tech Sheet 68074		

The UFI Hydraulic Division clogging indicators give an exact indication of the proper time to replace the filter element



Clogging Indicators, Visual

0526	Cracking Pressure Bar
5E-PBIND	5
5F-PBIND	8
Tech Sheet 68074	



Clogging Indicators, Electrical

0526	Cracking Pressure Bar
6E-PBIND	5
6F-PBIND	8
Tech Sheet 68074	



Clogging Indicators, LED Electrical, 24V

0526	Cracking Pressure Bar
7E-PBIND	5
7F-PBIND	8
Tech Sheet 68074	



Replacement Fibre Elements

0526	Filter Element Size	Micron
EPB12NFA	12	5
EPB12NFB	12	7
EPB12NFC	12	12
EPB12NFD	12	21
EPB13NFA	13	5
EPB13NFB	13	7
EPB13NFC	13	12
EPB13NFD	13	21

0526	Filter Element Size	Micron
EPB21NFA	21	5
EPB21NFB	21	7
EPB21NFC	21	12
EPB21NFD	21	21
EPB31NFA	31	5
EPB31NFB	31	7
EPB31NFC	31	12
EPB31NFD	31	21

0526	Filter Element Size	Micron
EPB33NFA	33	5
EPB33NFB	33	7
EPB33NFC	33	12
EPB33NFD	33	21
EPB34NFA	34	5
EPB34NFB	34	7
EPB34NFC	34	12
EPB34NFD	34	21

Fluid-Air Components Ltd

HIGH PRESSURE HYDRAULIC FILTRATION

The UFI Hydraulic Division pressure filters are named 'COMPO CARE' because they take care of system components, ensuring the recommended cleanliness levels.

Filter elements are manufactured from glass fibre and cellulose media

Materials:
- Anodized aluminium alloy housing
- Steel bypass valve
- NBR nitrile seals (FKM fluoroelastomer on request
- Brass indicator housing

Pressures: (ISO 10771-1:2002)
- Maximum working: 21 MPa (210 bar)
- Test: 33 MPa (330 bar)
- Bursting: 66 MPa (660 bar)
- Collapse differential for the filter element (ISO 2941): 2,1 MPa (21 bar)

Compatibility: (ISO 2943:1999)
- Full with fluids: HH-HL-HM-H -HTG (according to ISO 6743/4)

PM Series Filters, 210 bar

Working Temperature: -25°C to +110°C

Maximum Working Pressure: 210 bar



BSPP Ported, No Indicator, Bypass 6 bar, 5 Micron

0526	Thread	Filter Element Size
FPM21B04CNFA03XX	1/2"	21
FPM22B06CNFA03XX	3/4"	22
FPM22B08CNFA03XX	1"	22
Tech Sheet 68075		

BSPP Ported, No Indicator, Bypass 6 bar, 7 Micron

0526	Thread	Filter Element Size
FPM21B04CNFB03XX	1/2"	21
FPM22B06CNFB03XX	3/4"	22
FPM22B08CNFB03XX	1"	22
Tech Sheet 68075		



Replacement Fibre Elements

0526	Filter Element Size	Micron
EPB22NFA	22	5
EPB22NFB	22	7
EPB22NFC	22	12
EPB22NFD	22	21
Tech Sheet 68075		

BSPP Ported, No Indicator, Bypass 6 bar, 12 Micron

0526	Thread	Filter Element Size
FPM21B04CNFC03XX	1/2"	21
FPM22B06CNFC03XX	3/4"	22
FPM22B08CNFC03XX	1"	22
Tech Sheet 68075		

BSPP Ported, No Indicator, Bypass 6 bar, 21 Micron

0526	Thread	Filter Element Size
FPM21B04CNFD03XX	1/2"	21
FPM22B06CNFD03XX	3/4"	22
FPM22B08CNFD03XX	1"	22
Tech Sheet 68075		



For **Clogging Indicators** see page **257**

Materials:
- Aluminium alloy head
- Steel bowl
- NBR nitrile bypass valve (FKM fluoroelastomer on request)
- NBR nitrile seals (FKM fluoroelastomer on request)
- Brass indicator housing

Pressures: (ISO 10771-1:2002)
- Maximum working: 5 MPa (50 bar)
- Fatigue test: 0-5 Mpa (0-50 bar) 1 million cycles
- Collapse differential for the filter element (ISO 2941): 1 MPa (10 bar)

Compatibility: (ISO 2943:1999)
- Full with fluids: HH-HL-HM-H -HTG (according to ISO 6743/4)

PG Series Filters, 50 bar

Working Temperature: -25°C to +110°C

Maximum Working Pressure: 50 bar



BSPP Ported, No Indicator, Bypass 3.5 bar, 12 Micron

0526	Thread	Filter Element Size
FPG20B06DNFC03CX	3/4"	20
FPG21B06DNFC03CX	3/4"	21
FPG22B08DNFC03CX	1"	22
FPG31B10DNFC03CX	1.1/4"	31
Tech Sheet 68076		

BSPP Ported, No Indicator, Bypass 6 bar, 21 Micron

0526	Thread	Filter Element Size
FPG20B06DNFD03CX	3/4"	20
FPG21B06DNFD03CX	3/4"	21
FPG22B08DNFD03CX	1"	22
FPG31B10DNFD03CX	1.1/4"	31
Tech Sheet 68076		



Replacement Fibre Elements

0526	Filter Element Size	Micron
EPG20NFA	20	5
EPG20NFB	20	7
EPG20NFC	20	12
EPG20NFD	20	21
EPG21NFA	21	5
EPG21NFB	21	7
EPG21NFC	21	12
EPG21NFD	21	21
EPG22NFA	22	5
EPG22NFB	22	7
EPG22NFC	22	12
EPG22NFD	22	21
EPG31NFA	31	5
EPG31NFB	31	7
EPG31NFC	31	12
EPG31NFD	31	21
Tech Sheet 68076		

Fluid-Air Components Ltd

HYDRAULIC FILTRATION

The UFI Hydraulic Division return filters are named ' ANK CARE' because they take care of the oil returning into the tank, ensuring the fluid cleanliness level to be within the required values. Nominal flow rates up to 2.400 L/mi (635 GPM). Degree of filtration is from 5µm(c) to 90µm. Filter elements are glass fibre, cellulose and metal wire mesh media.

Materials:
- Aluminium alloy head and cover
- Polyamide bowl for FRA21-31-32-33-41
- Zinc-plated steel bowl for FRA41-42-51-52-53-5D
- Polyamide bypass valve
- NBR nitrile seals (FKM fluoroelastomer on request
- Brass indicator housing

Compatibility: (ISO 2943:1999)
- Full with fluids: HH-HL-HM-H -HTG (according to ISO 6743/4)

RA Series Filters, Tank Return



Working Temperature: -25°C to +110°C

Maximum Working Pressure: 3 bar

BSPP Ported, Visual Indicator, Bypass 1.7 bar, 12 Micron

0526	Thread	Filter Element Size
FRA21B04BNFC32WX	1/2"	21
FRA31B06BNFC32WX	3/4"	31
FRA32B08BNFC32WX	1"	32
FRA41B10BNFC32WX	1.1/4"	41
FRA51B12BNFC32WX	1.1/2"	51
FRA53B16BNFC32WX	2"	53

Tech Sheet 68077

BSPP Ported, Visual Indicator, Bypass 1.7 bar, 21 Micron

0526	Thread	Filter Element Size
FRA21B04BNFD32WX	1/2"	21
FRA31B06BNFD32WX	3/4"	31
FRA32B08BNFD32WX	1"	32
FRA41B10BNFD32WX	1.1/4"	41
FRA51B12BNFD32WX	1.1/2"	51
FRA53B16BNFD32WX	2"	53

Replacement Fibre Elements



0526	Filter Element Size	Micron
ERA21NFC	21	12
ERA31NFC	31	12
ERA32NFC	32	12
ERA41NFC	41	12
ERA51NFC	51	12
ERA53NFC	53	12
ERA21NFD	21	21
ERA31NFD	31	21
ERA32NFD	32	21
ERA41NFD	41	21
ERA51NFD	51	21
ERA53NFD	53	21

Materials:
- Aluminium alloy head
- Steel spin-on cartridge
- Polyamide bypass valve
- NBR nitrile seals (FKM fluoroelastomer on request
- Brass indicator housing

Pressures: (ISO 10771-1:2002)
- Maximum working: 1,2 MPa (12 bar)
- Test: 1,5 MPa (15 bar)
- Bursting: 2,5 MPa (25 bar)
- Collapse differential for the filter element (ISO 2941): 400 kPa (4 bar)

Compatibility: (ISO 2943:1999)
- Full with fluids: HH-HL-HM-HR-HV-HG (according to ISO 6743/4)

PE Series Filters, Spin-on

Maximum Working Pressure: 12 bar



Single, BSPP Ported, Visual Indicator, Bypass 1.7 bar, 12 Micron

0526	Thread	Filter Element Size
FPE11B06BNFC31XX	3/4"	11
FPE12B06BNFC31XX	3/4"	12
FPE21B10BNFC31XX	1.1/4"	21
FPE22B10BNFC31XX	1.1/4"	22



Twin, BSPP Ported, Visual Indicator, Bypass 1.7 bar, 12 Micron

0526	Thread	Filter Element Size
FPE31B12BNFC31XX	1.1/2"	31
FPE32B12BNFC31XX	1.1/2"	32



Dual, BSPP Ported, Visual Indicator, Bypass 1.7 bar, 12 Micron

0526	Thread	Filter Element Size
FPE41B12BNFC31XX	1.1/2"	41
FPE42B12BNFC31XX	1.1/2"	42

Working Temperature: -25°C to +110°C



Replacement Fibre Elements

0526	Filter Element Size	Micron
ESE11NFA	11	5
ESE11NFB	11	7
ESE11NFC	11	12
ESE11NFD	11	21
ESE12NFA	12	5
ESE12NFB	12	7
ESE12NFC	12	12
ESE12NFD	12	21
ESE21NFA	21	5
ESE21NFB	21	7
ESE21NFC	21	12
ESE21NFD	21	21
ESE22NFA	22	5
ESE22NFB	22	7
ESE22NFC	22	12
ESE22NFD	22	21

Tech Sheet 68078

The UFI Hydraulic Division clogging indicator gives an exact indication of the proper time to replace the filter element



Clogging Indicators, Visual

0526	Thread
31-PEIND	1/8"

F.A.C
Fluid-Air Components Ltd

HYDRAULIC ACCESSORIES

Magnetic Tank Cleaner



M12 Thread, 57mm OD

0347	Length mm
MTC-300	300
MTC-450	450
MTC-525	525
MTC-600	600
Tech Sheet 10055	

Fluid Sight Glass



BSPP

0347	Thread
SG-12	3/4"
SG-16	1"
SG-20	1.1/4"
SG-24	1.1/2"
Tech Sheet 10060	

Weldable Flange to suit SG-**



BSPP

0347	Thread
WF-12	3/4"
WF-16	1"
WF-20	1.1/4"
WF-24	1.1/2"
Tech Sheet 10060	

Sight Glasses

- Housing and reflector in aluminium, sight glass in polyamide, transparent, high mechanical stability, non-ageing
- Fluid Compatibility: Mineral based oils and solvents

Maximum Working Temperature: +100°C

Maximum Working Pressure: 3 bar



Aluminium Oil Level Sight Glasses, BSPP

0027	Thread	Hex Size mm
K561020014	1/4"	18
K561024038	3/8"	22
K561029012	1/2"	27
Tech Sheet 10473		

- Housing in polyamide, transparent, high mechanical stability, non-ageing
- Fluid Compatibility: Mineral based oils and solvents

Maximum Working Temperature: +100°C

Maximum Working Pressure: 3 bar



Plastic Oil Sight Glasses, BSPP

0027	Thread	Hex Size mm
K5604120014	1/4"	17
K5604122038	3/8"	18
K5604128012	1/2"	24
K5604135034	3/4"	30
K5604143100	1"	35
K5604151114	1.1/4"	42
K5604158112	1.1/2"	50
K5604174200	2"	64
K56041201415	M14 x 1.5	17
K56041221615	M16 x 1.5	18
K56041251815	M18 x 1.5	21
K56041282015	M20 x 1.5	24
Tech Sheet 10472		

Plastic Oil Sight Glasses with Reflector, BSPP

0027	Thread	Hex Size mm
K5604222038	3/8"	18
K5604228012	1/2"	24
K5604235034	3/4"	30
K5604243100	1"	35
K5604251114	1.1/4"	42
K5604258112	1.1/2"	50
K5604274200	2"	64
K56042221615	M16 x 1.5	18
K56042251815	M18 x 1.5	21
K56042282015	M20 x 1.5	24
Tech Sheet 10472		

- Housing in polyamide, transparent, high mechanical stability, non-ageing
- Fluid Compatibility: Mineral based oils and solvents

NOTE: For use with a tank with a minimum wall thickness of 5mm. Not suitable for pressurised tanks

Maximum Working Temperature: +100°C



Push-in Plastic Oil Sight Glasses with Reflector

0027	OD mm
K56062420	20
K56063026	26
K56063632	32
K56064238	38
K56064440	40
Tech Sheet 10471	

- Shock resistant
- Transparent polyamid reflector
- Anodised aluminium reflector
- Buna-n seal
- For use with mineral, petroleum and water-based fluid
- Any contact with alcohol or solvents must be avoided

Maximum Working Temperature: +100°C

Maximum Working Pressure: 3 bar



Dome Oil Level Sight Glasses, BSPP

0027	Thread	Hex Size mm
K560822038	3/8"	19
K560828012	1/2"	24
K560835034	3/4"	30
K560842100	1"	36
Tech Sheet 10470		

Fluid-Air Components Ltd

Fluid Level Gauge



Without Thermometer

0347	Bolt Thread	Hole Centres mm
FLGS-76	12	76
FLGS-76-10	10	76
FLGS-127	12	127
FLGS-127-10	10	127
FLGS-254	12	254
FLGS-254-10	10	254
Tech Sheet 10060		



With Thermometer


0347	Bolt Thread	Hole Centres mm
FLTGS-76	12	76
FLTGS-76-10	10	76
FLTGS-127	12	127
FLTGS-127-10	10	127
FLTGS-254	12	254
FLTGS-254-10	10	254
Tech Sheet 10060		

Oil Level Indicators

- Housing in polyamide, transparent, high mechanical stability, non-ageing
- Fluid Compatibility:
  Mineral based oils and petroleum based fluids
- Plastic mount and frame allowing for side reading

Working Temperature:
-30°C to +100°C

Maximum Working Pressure:
1 bar



Without Thermometer

0027	Bolt Thread	Hole Centres mm	Length mm
K56001076	M10 x 1.5	76	103
K56001127	M12 x 1.75	127	154
Tech Sheet 10483			

With Thermometer

0027	Bolt Thread	Hole Centres mm	Length mm
K56002076	76	M10 x 1.5	103
K56002127	127	M12 x 1.75	154
Tech Sheet 10483			

Filler Breathers



Chrome Plated Steel, 40 Micron

0347	OD mm	Description
SFB-3-40	28	3 Bolt Mount
SFB-6-40	48	6 Bolt Mount
SFB-6-40-HN	48	6 Bolt Mount High Neck
SFB-6-40-SM	101.6	Side Mount
Tech Sheet 10056		

- Material Body: Thermoplastic polyamide 66
- Strainer: Thermoplastic polypropylene
- Filter: Polyurethane foam 50µm
- Fluid Compatibility: Mineral based oils and solvents

Maximum Working Temperature:
+90°C



Plastic, Push-in

0027	OD mm	Length mm
K5670706020	55	88
Tech Sheet 10484		

Desiccant Breather



10 Micron, 2" NPT

0347	LPM
DB-1000	1000
DB-1500	1500
DB-2400	2400
Tech Sheet 10059	

Breather



Chrome Plated Steel, 40 Micron, BSPP

0347	Thread
SB-04B	1/4"
SB-08B	1/2"
SB-12B	3/4"



ABS, 40 Micron, BSPP

0347	Thread
ABSB-06B	3/8"
ABSB-08B	1/2"
ABSB-12B	3/4"
ABSB-16B	1"
Tech Sheet 10057	



Giant Breather, BSPP

0347	Thread	Micron
GTB-12-10	3/4"	10
GTB-12-25	3/4"	25
GTB-20-10	1.1/4"	10
GTB-20-25	1.1/4"	25
Tech Sheet 10058		

5 PSI Pressurised Breather



Chrome Plated Steel, 40 Micron, BSPP

0347	Thread
SPB-08B	1/2"
SPB-12B	3/4"

Fluid-Air Components Ltd

HYDRAULIC ACCESSORIES

Plugs

- Material: Elastomer, soft polyurethane
- Ideal for keeping threads clean when spraying tanks

Maximum Working Temperature: +100°C

Working Pressure: 2 to 3 bar



Screw-in Protection Plugs, BSPP

0027	Thread
K5618018	1/8"
K5618014	1/4"
K5618038	3/8"
K5618012	1/2"
K5618034	3/4"
K5618100	1"
Tech Sheet 10474	

Press-in Plugs

- Material: Thermoplastic polyamide 66
- Air Filter: Polyurethane foam
- Filter Fineness 50µm

NOTE: Not suitable for pressurised tanks



With Ventilation with Rubber O-Ring

0027	OD mm	Band Width mm
K562223018	18	8
K562323020	20	8
K562423026	26	9.5
Tech Sheet 10475		

Without Ventilation with Rubber O-Ring

0027	OD mm	Band Width mm
K562213020	20	8
K562213030	30	9.5
Tech Sheet 10475		

Plugs with Magnets

- Material: Aluminium

NOTE: Mounted on the bottom of tanks to attract metal parts



Aluminium, BSPP

0027	OD mm	Hex Size mm
K562621014	1/4"	19
K562624038	3/8"	22
K562630012	1/2"	27
K562636034	3/4"	34
K562642100	1"	40
Tech Sheet 10476		

Vent Screws

- Material: Thermoplastic polyamide 66
- Air Filter: Polyurethane foam
- Fluid Compatibility: Mineral based oils and solvents

Maximum Working Temperature: +100°C



With Oil Fill Symbol

0027	Thread
K5634136038	3/8"
K5634141012	1/2"
K5634147034	3/4"
K5634152100	1"
K5634163114	1.1/4"
K5634163112	1.1/2"
K56341361615	M16 x 1.5
K56341411815	M18 x 1.5
K56341412015	M20 x 1.5
K56341412215	M22 x 1.5
Tech Sheet 10477	

With Oil Fill Symbol & Filter

0027	Thread
K5634236038	3/8"
K5634241012	1/2"
K5634247034	3/4"
K5634252100	1"
K5634263114	1.1/4"
K5634263112	1.1/2"
K56342361615	M16 x 1.5
K56342411815	M18 x 1.5
K56342412215	M22 x 1.5
Tech Sheet 10477	



With Splash Guard, Filter & Oil Symbol, BSPP

0027	Thread
K563630014	1/4"
K563630038	3/8"
K563630012	1/2"
Tech Sheet 10478	

Vent Screws with Dipstick

- Material: Black thermoplastic polyamide 66
- Filter: Polyurethane foam 50µm
- Dipstick: Galvanized steel
- Fluid Compatibility: Mineral based oils and solvents
- Dipstick Length: 200mm except non-return and splash back 195mm



With Vent, Filter & Fill Symbol

0027	Thread
K5654236038	3/8"
K5654241012	1/2"
K5654247034	3/4"
K5654252100	1"
K56542412015	M20 x 1.5
Tech Sheet 10479	



With Non-return Valve & Non-return Symbol, BSPP

0027	Thread
K563830014	1/4"
K563830038	3/8"
K563830012	1/2"
Tech Sheet 10480	

Thinking Sticks





Traffic Light Lollipops

0166	Qty
LOL1	150

Brass Vent Screws

- Material: Housing and cap in brass filter in galvanized steel wire 50-60µm



Filter & Vent, BSPP

0027	Thread
K564020014	1/4"
K564024038	3/8"
K564030012	1/2"
Tech Sheet 10481	



Non-return Valve & Vent, BSPP

0027	Thread
K564220014	1/4"
K564224038	3/8"
K564230012	1/2"
Tech Sheet 10482	

Fluid-Air Components Ltd

Hydraulic Pressure Gauges



This quality range of hydraulic glycerine-filled pressure gauges have been manufactured to the highest specification using quality materials.

The range includes stainless steel cased to complete stainless steel units with 40mm, 63mm and 100mm dials. Pressures range from 0-1 bar to 0-600 bar, with rear and bottom connections of 1/4" and 1/2" in BSPP and BSPT.

FT Pro gauges are tried, tested and used extensively throughout the world's manufacturing facilities and in the mobile plant industry.

For your peace of mind all gauges can be supplied with a calibration certificate at a nominal charge.

Applications:

- Hydraulics
- Construction
- Agriculture
- Mining
- OEM machine building
- Offshore
- Marine
- High pressure water applications
- Service kits

GLYCERINE GAUGES & ACCESSORIES

Stainless Steel Case, Bottom Connection

stainless steel



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001BG	1/4"	63	0-15	0-1
G63-002BG	1/4"	63	0-30	0-2
G63-004BG	1/4"	63	0-60	0-4
G63-006BG	1/4"	63	0-100	0-6
G63-012BG	1/4"	63	0-200	0-12
G63-020BG	1/4"	63	0-300	0-20
G63-025BG	1/4"	63	0-400	0-25
G63-040BG	1/4"	63	0-600	0-40
G63-060BG	1/4"	63	0-1000	0-60
G63-120BG	1/4"	63	0-2000	0-120
G63-200BG	1/4"	63	0-3000	0-200
G63-250BG	1/4"	63	0-4000	0-250
G63-400BG	1/4"	63	0-6000	0-400
G63-600BG	1/4"	63	0-9000	0-600
VG63-01BG	1/4"	63	-30" Hg	-1 bar

Tech Sheet 20593

stainless steel



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001BG	1/4"	63	0-15	0-1
PG63-002BG	1/4"	63	0-30	0-2
PG63-004BG	1/4"	63	0-60	0-4
PG63-006BG	1/4"	63	0-100	0-6
PG63-012BG	1/4"	63	0-200	0-12
PG63-014BG	1/4"	63	0-200	0-14
PG63-020BG	1/4"	63	0-300	0-20
PG63-025BG	1/4"	63	0-400	0-25
PG63-040BG	1/4"	63	0-600	0-40
PG63-060BG	1/4"	63	0-1000	0-60
PG63-120BG	1/4"	63	0-2000	0-120
PG63-200BG	1/4"	63	0-3000	0-200
PG63-250BG	1/4"	63	0-4000	0-250
PG63-400BG	1/4"	63	0-6000	0-400
PG63-600BG	1/4"	63	0-9000	0-600

Tech Sheet 20594

Stainless Steel Case, Centre Back Connection

See Panel Mount Bracket Options: G63-PM & G63-PM-RHOMB

stainless steel



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001RG	1/4"	63	0-15	0-1
G63-002RG	1/4"	63	0-30	0-2
G63-004RG	1/4"	63	0-60	0-4
G63-006RG	1/4"	63	0-100	0-6
G63-010RG	1/4"	63	0-160	0-10
G63-012RG	1/4"	63	0-200	0-12
G63-020RG	1/4"	63	0-300	0-20
G63-025RG	1/4"	63	0-400	0-25
G63-040RG	1/4"	63	0-600	0-40
G63-060RG	1/4"	63	0-1000	0-60
G63-120RG	1/4"	63	0-2000	0-120
G63-200RG	1/4"	63	0-3000	0-200
G63-250RG	1/4"	63	0-4000	0-250
G63-400RG	1/4"	63	0-6000	0-400
G63-600RG	1/4"	63	0-9000	0-600
VG63-01RG	1/4"	63	-30" Hg	-1 bar

Tech Sheet 20595

See Panel Mount Bracket Options: G63-PM & G63-PM-RHOMB

stainless steel



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001RG	1/4"	63	0-15	0-1
PG63-002RG	1/4"	63	0-30	0-2
PG63-004RG	1/4"	63	0-60	0-4
PG63-006RG	1/4"	63	0-100	0-6
PG63-012RG	1/4"	63	0-200	0-12
PG63-020RG	1/4"	63	0-300	0-20
PG63-025RG	1/4"	63	0-400	0-25
PG63-040RG	1/4"	63	0-600	0-40
PG63-060RG	1/4"	63	0-1000	0-60
PG63-120RG	1/4"	63	0-2000	0-120
PG63-200RG	1/4"	63	0-3000	0-200
PG63-250RG	1/4"	63	0-4000	0-250
PG63-400RG	1/4"	63	0-6000	0-400
PG63-600RG	1/4"	63	0-9000	0-600

Tech Sheet 20596

Panel Mounting Brackets

stainless steel



For G63 & PG63 Centre Back Connection below 100 bar

0021
G63-PM

stainless steel



For G63 & PG63 Centre Back Connection above 100 bar

0021
G63-PM-RHOMB

Gauge Snubbers

Working Pressure: 20 to 300 bar



High Pressure

0234	Male Thread	Female Thread
130.4	1/4"	1/4"
130.3	3/8"	3/8"
130.2	1/2"	1/2"

Tech Sheet 28

Gauge snubbers are a great way of protecting gauges from damage, with sudden impact pressure i.e. when full line pressure is introduced to the gauge damage can occur. With the use of the snubber the gauge will be protected.

Working Pressure: 0 to 20 bar



Low Pressure

0234	Male Thread	Female Thread
131.8	1/8"	1/8"
131.4	1/4"	1/4"
131.3	3/8"	3/8"
131.2	1/2"	1/2"

Tech Sheet 28

Back Rubber Gauge Protectors



Open Closed

0021	Description
G63-OB	Open
G63-CB	Closed

Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

TEMPERATURE GAUGES

WIKA

Bi-metallic Thermometers, Centre Back Connection

Pressure Rating of Thermowell:
6 bar max



63mm & 100mm Diameter, Aluminium Case, 1/2" BSPP

0056	Gauge Diameter mm	Temperature Range °C
WTG63-60	63	0-60
WTG63-120	63	0-120
WTG63-200	63	0-200
WTG100-60	100	0-60
WTG100-120	100	0-120
WTG100-200	100	0-200
	Tech Sheet 10526	

Refrigeration Gauges, Plastic Case, Bottom Connection



63mm Diameter, 7/16" UNF, 1/4" Flare

0056	Temperature Range °C
WG63-716B-1/9	-1/+9

**All pressure gauges can be supplied with a calibration certificate at a nominal charge.
Please call our Business Development Team for price and delivery.**

spradow
german engineering at your service

Customers who bought from this page also purchased
Hydraulic Test Points
see pages **268-272**



FAC
Fluid-Air Components Ltd

GLYCERINE GAUGES

Heavy-duty, Bottom Connection

Accuracy:
63mm diameter: +/- 1.6%
100mm diameter: +/- 1.0%



63mm & 100mm Diameter, BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar	Max Pressure PSI
WG63-14B-1G	1/4"	63	1	15
WG63-14B-1.6G	1/4"	63	1.6	25
WG63-14B-2.5G	1/4"	63	2.5	40
WG63-14B-4G	1/4"	63	4	60
WG63-14B-6G	1/4"	63	6	90
WG63-14B-10G	1/4"	63	10	160
WG63-14B-16G	1/4"	63	16	230
WG63-14B-25G	1/4"	63	25	400
WG63-14B-40G	1/4"	63	40	600
WG63-14B-60G	1/4"	63	60	900
WG63-14B-100G	1/4"	63	100	1600
WG63-14B-160G	1/4"	63	160	2300
WG63-14B-250G	1/4"	63	250	4000
WG63-14B-400G	1/4"	63	400	6000
WG63-14B-600G	1/4"	63	600	9000
WG100-38B-2.5G	3/8"	100	2.5	40
WG100-38B-4G	3/8"	100	4	60
WG100-38B-6G	3/8"	100	6	90
WG100-38B-10G	3/8"	100	10	160
WG100-38B-16G	3/8"	100	16	230
WG100-38B-40G	3/8"	100	40	600
WG100-12B-100G	1/2"	100	100	1600
WG100-12B-160G	1/2"	100	160	2300
WG100-12B-250G	1/2"	100	250	4000
WG100-12B-400G	1/2"	100	400	6000
WG100-12B-600G	1/2"	100	600	9000
Tech Sheet 10525				

Heavy-duty, Centre Back Connection



63mm & 100mm Diameter, BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar	Max Pressure PSI
WG63-14R-1G	1/4"	63	1	15
WG63-14R-1.6G	1/4"	63	1.6	25
WG63-14R-2.5G	1/4"	63	2.5	40
WG63-14R-4G	1/4"	63	4	60
WG63-14R-6G	1/4"	63	6	90
WG63-14R-10G	1/4"	63	10	160
WG63-14R-16G	1/4"	63	16	230
WG63-14R-25G	1/4"	63	25	400
WG63-14R-40G	1/4"	63	40	600
WG63-14R-60G	1/4"	63	60	900
WG63-14R-100G	1/4"	63	100	1600
WG63-14R-160G	1/4"	63	160	2300
WG63-14R-250G	1/4"	63	250	3600
WG63-14R-400G	1/4"	63	400	6000
WG63-14R-600G	1/4"	63	600	9000
WG100-38R-2.5G	3/8"	100	2.5	40
WG100-38R-4G	3/8"	100	4	60
WG100-38R-6G	3/8"	100	6	90
WG100-38R-10G	3/8"	100	10	160
WG100-38R-16G	3/8"	100	16	230
WG100-38R-40G	3/8"	100	40	600
WG100-12R-100G	1/2"	100	100	1600
WG100-12R-160G	1/2"	100	160	2300
WG100-12R-250G	1/2"	100	250	4000
WG100-12R-400G	1/2"	100	400	6000
WG100-12R-600G	1/2"	100	600	9000
Tech Sheet 10525				

Vacuum Gauges, Bottom Connection

Accuracy:
63mm diameter: +/- 1.6%



63mm Diameter, 1/4" BSPP

0056	Max Pressure Hg	Max Pressure Bar
WG63-14B/-30HG	-30	-1
Tech Sheet 10525		

Vacuum Gauges, Centre Back Connection



63mm Diameter, 1/4" BSPP

0056	Max Pressure Hg	Max Pressure Bar
WG63-14R/-30HG	-30	-1
Tech Sheet 10525		

Fluid-Air Components Ltd

GLYCERINE GAUGES

stainless steel FT PRO

All Stainless Steel Gauges, 1/4" Bottom Connection



1/4" BSPP

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SSG63-001BG	63	0-15	0-1
SSG63-004BG	63	0-60	0-4
SSG63-012BG	63	0-200	0-12
SSG63-025BG	63	0-400	0-25
SSG63-060BG	63	0-1000	0-60
SSG63-200BG	63	0-3000	0-200
SSG63-400BG	63	0-6000	0-400
Tech Sheet 20598			

All Stainless Steel Gauges, 1/4" Centre Back Connection



1/4" BSPP

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2020-0340	50	0-200	0-12
2020-0341	50	0-300	0-20
2020-0342	50	0-600	0-40
2020-0343	50	0-900	0-60
2020-0344	50	0-4000	0-250
2038-8534	63	0-200	0-12
2038-8567	63	0-900	0-60
2038-8575	63	0-4000	0-250
Tech Sheet 20600			

All Stainless Steel Gauges, 1/2" Bottom Connection



1/2" BSPP

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SHG100-002BG	100	0-30	0-2
SHG100-006BG	100	0-100	0-6
SHG100-016BG	100	0-250	0-16
SHG100-040BG	100	0-600	0-40
SHG100-100BG	100	0-1500	0-100
SHG100-250BG	100	0-4000	0-250
SHG100-600BG	100	0-9000	0-600
Tech Sheet 20599			

All Stainless Steel Gauges, 1/2" Centre Back Connection



1/2" BSPP

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2038-8435	100	0-200	0-12
2038-8443	100	0-300	0-20
2038-8450	100	0-600	0-40
2038-8476	100	0-4000	0-250
Tech Sheet 20601			

Stainless Steel Case, Heavy-duty, Bottom Connection



1/2" BSPP

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002G	100	0-36	0-2.5
HG100-004G	100	0-58	0-4
HG100-006G	100	0-87	0-6
HG100-010G	100	0-145	0-10
HG100-016G	100	0-232	0-16
HG100-040G	100	0-580	0-40
HG100-100G	100	0-1450	0-100
HG100-160G	100	0-2320	0-160
HG100-250G	100	0-3625	0-250
HG100-400G	100	0-5800	0-400



1/2" BSPT

0021	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002B	100	0-36	0-2.5
HG100-004B	100	0-58	0-4
HG100-006B	100	0-87	0-6
HG100-010B	100	0-145	0-10
HG100-016B	100	0-232	0-16
HG100-040B	100	0-580	0-40
HG100-100B	100	0-1450	0-100
HG100-160B	100	0-2320	0-160
HG100-250B	100	0-3625	0-250
HG100-400B	100	0-5800	0-400
Tech Sheet 20597			

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



HYDRAULICS you can count on!

spradow
german engineering at your service

TÜV
ISO 9001
Certified Company

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

TEST POINT COUPLINGS

spradow
german engineering at your service

Piston Valve Type, M16 x 2

Media Application:
Hydraulic and other oils on mineral oil basis.

Metal Cap -30°C to +100°C Sealings Buna N
Metal Cap -20°C to +200°C Sealings Viton



Test Coupling

0330	Thread	Max Pressure Bar
1-Z06-28-11-600	1/8" BSPP	400
1-Z06-29-11-600	1/4" BSPP	400
1-Z06-30-11-600	3/8" BSPP	400
1-Z06-22-11-600	M10 x 1.0	630
1-Z06-23-11-600	M12 x 1.5	630
1-Z06-24-11-600	M14 x 1.5	630
1-Z06-43-00-600	1/8" NPT	400
1-Z06-44-00-600	1/4" NPT	400
1-Z06-39-30-600	7/16" UNF	630
1-Z06-40-30-600	9/16" UNF	630
Tech Sheet 10292		



Bulkhead Coupling

0330	Max Pressure Bar
1-Z80-48-60-040	630
Tech Sheet 10292	



In-line Tee, BSPP

0330	Thread	Max Pressure Bar
1-Z10-68-00-600	1/4"	400
1-Z10-69-00-600	3/8"	400
1-Z10-70-00-600	1/2"	630
1-Z10-72-00-600	3/4"	630
1-Z10-73-00-600	1"	630
Tech Sheet 10292		

stainless steel



316 Stainless Steel, BSPP

0330	OD mm	Max Pressure Bar
1-912-28-12-660	1/8"	400
1-912-29-12-660	1/4"	630
Tech Sheet 10292		



DIN 2353 DKO Light-duty, Metric

0330	OD mm	Burst Pressure Bar
1-Z08-00-10-600	6L	1000
1-Z08-02-10-600	8L	1000
1-Z08-04-10-600	10L	1000
1-Z08-06-10-600	12L	1000
Tech Sheet 10292		

DIN 2353 DKO Heavy-duty, Metric

0330	OD mm	Burst Pressure Bar
1-Z08-03-10-600	8S	1890
1-Z08-05-10-600	10S	1890
1-Z08-07-10-600	12S	1890
Tech Sheet 10292		

Gauge Adaptors

stainless steel



316 Stainless Steel, BSPP

0330	Thread	Max Pressure Bar
1-940-31-22-080	1/2"	630
Tech Sheet 10292		



Direct, BSPP

0330	Thread	Max Pressure Bar
1-927-29-01-020	1/4"	630
1-927-31-01-020	1/2"	630
Tech Sheet 10292		



Hose/Gauge, BSPP

0330	Thread	Max Pressure Bar
1-918-29-01-240	1/4"	630
1-918-31-01-240	1/2"	630
Tech Sheet 10292		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TEST POINT COUPLINGS

spradow
german engineering at your service

Ball Valve Type, M16 x 2

Maximum Working Pressure:
630 bar



Test Coupling

0330	Thread	Max Pressure Bar
1-906-22-11-600	M10 x 1.0	630
1-906-23-11-600	M12 x 1.5	630
1-906-24-11-600	M14 x 1.5	630
1-906-28-11-600	G1/8" BSPP	630
1-906-29-11-600	G1/4" BSPP	630
1-906-30-11-600	G3/8" BSPP	630
1-906-43-00-600	1/8" NPT	630
1-906-44-00-600	1/4" NPT	630
1-906-39-30-600	7/16" UNF	630
1-906-40-30-600	9/16" UNF	630
Tech Sheet 10292		



Bulkhead Coupling

0330
1-980-48-60-040
Tech Sheet 10292

Maximum Working Pressure:
135 bar



DIN 2353 DKO Light-duty, Metric

0330	OD mm	Burst Pressure Bar
1-908-00-20-600	6L	630
1-908-02-20-600	8L	630
1-908-04-20-600	10L	630
1-908-06-20-600	12L	630
Tech Sheet 10292		



DIN 2353 DKO Heavy-duty, Metric

0330	OD mm	Burst Pressure Bar
1-908-03-20-600	8S	1890
1-908-05-20-600	10S	1890
1-908-07-20-600	12S	1890
Tech Sheet 10292		

316 Stainless Steel Test Points

Sealing by an elastomer captive profiled ring - Vito
Test connection: M16 x 2

Maximum Working Pressure:
630 bar

stainless steel



Form C, BSPP

0330	Thread
MAS-G1/8-WD	1/8"
MAS-G1/4-WD	1/4"
MAS-G3/8-WD	3/8"
MAS-G1/2-WD	1/2"

400 bar Microbore Test Point Hose Assemblies



M16 x 2

0330	Length mm
1-970-04-04-010	200
1-970-04-04-040	400
1-970-04-04-060	630
1-970-04-04-080	800
1-970-04-04-090	1000
1-970-04-04-100	1500
1-970-04-04-110	2000
1-970-04-04-120	2500
1-970-04-04-130	3200
1-970-04-04-140	4000
Tech Sheet 10292	



1/4" BSPP

0330	Length mm
1-970-02-04-010	200
1-970-02-04-030	300
1-970-02-04-050	500
1-970-02-04-060	630
1-970-02-04-080	800
1-970-02-04-090	1000
1-970-02-04-100	1500
1-970-02-04-110	2000
1-970-02-04-120	2500
1-970-02-04-140	4000
Tech Sheet 10292	



1/2" BSPP

0330	Length mm
1-970-04-25-090	1000
1-970-04-25-100	1500
1-970-04-25-110	2000
Tech Sheet 10292	

FAC
Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

TEST POINT COUPLINGS

End Fitting to suit DN2 and DN4 Hose

Bespoke assemblies available on request



Test Female Straight

0330	Thread	Type	DN
2-971-04-02-001	M16 x 2	Knurled	2
2-971-04-04-001	M16 x 2	Knurled	4
2-971-10-02-001	M16 x 1.5	Knurled	2
2-971-10-04-001	M16 x 1.5	Knurled	4
2-971-12-02-001	S12 x 1.5	Knurled	2
2-971-12-04-001	S12 x 1.5	Knurled	4
Tech Sheet 60388			



Test Female Straight

0330	Thread	Type	DN
2-971-03-02-001	M16 x 2	Hex	2
2-971-09-02-001	M16 x 1.5	Hex	2
Tech Sheet 60388			



Test 90° Elbow

0330	Thread	Type	DN
2-971-50-02-001	M16 x 2	Knurled	2
2-971-50-04-001	M16 x 2	Knurled	4
2-971-57-02-001	S12 x 1.5	Knurled	2
2-971-57-04-001	S12 x 1.5	Knurled	4
Tech Sheet 60388			



BSPP Female

0330	Thread	DN
2-971-02-02-004	1/4"	2
2-971-02-04-004	1/4"	4
2-971-25-02-001	1/2"	2
2-971-25-04-001	1/2"	4
Tech Sheet 60388		



BSPP 90° Elbow

0330	Thread	DN
2-971-58-02-001	1/4"	2
2-971-58-04-001	1/4"	4
2-971-54-02-001	1/2"	2
2-971-54-04-001	1/2"	4
Tech Sheet 60388		



NPT Female

0330	Thread	DN
2-971-26-00-001	1/4"	2
2-971-26-04-001	1/4"	4
2-971-27-00-001	1/2"	2
2-971-27-04-001	1/2"	4
Tech Sheet 60388		



Metric Female, DN2353

0330	Thread	Type	DN
2-971-19-02-001	M12 x 1.5	6L	2
2-971-19-04-001	M12 x 1.5	6L	4
2-971-20-02-001	M14 x 1.5	6S	2
2-971-20-04-001	M14 x 1.5	6S	4
2-971-21-02-001	M14 x 1.5	8L	2
2-971-21-04-001	M14 x 1.5	8L	4
2-971-22-02-001	M16 x 1.5	8S	2
2-971-22-04-001	M16 x 1.5	8S	4
2-971-23-02-001	M16 x 1.5	10L	2
2-971-23-04-001	M16 x 1.5	10L	4
2-971-24-02-001	M18 x 1.5	10S	2
2-971-24-04-001	M18 x 1.5	10S	4
Tech Sheet 60388			



Metric 90° Elbow, DN2353

0330	Thread	Type	DN
2-971-44-02-001	M12 x 1.5	6L	2
2-971-44-04-001	M12 x 1.5	6L	4
2-971-45-02-001	M14 x 1.5	6S	2
2-971-45-04-001	M14 x 1.5	6S	4
2-971-46-02-001	M14 x 1.5	8L	2
2-971-46-04-001	M14 x 1.5	8L	4
2-971-48-02-001	M16 x 1.5	10L	2
2-971-48-04-001	M16 x 1.5	10L	4
Tech Sheet 60388			



Metric Straight Standpipe

0330	OD mm	DN
2-971-13-00-001	6	2
2-971-13-04-001	6	4
2-971-15-00-001	8	2
2-971-15-04-001	8	4
Tech Sheet 60388		



BSPP Male, DN3852

0330	Thread	DN
2-971-33-00-001	1/8"	2
2-971-33-04-001	1/8"	4
Tech Sheet 60388		



JIC, SAE J541, Female

0330	Thread	DN
2-971-41-02-001	7/16"	2
2-971-41-04-001	7/16"	4
Tech Sheet 60388		



Banjo

0330	OD mm	DN
2-971-75-00-001	8	2
2-971-75-04-001	8	4
Tech Sheet 60388		

Anti-kink Spring



DN2

0330	To Suit
4-946-00-05-020	DN2 Hose

Ferrule



DN2 & DN4

0330	DN
4-999-03-01-160	2
6-999-03-01-010	4

Test Hose

Bespoke assemblies available on request.
Pin pricked



DN2 & DN4 Pin Pricked, Per Metre

0330	Max Pressure Bar	Type	DN
9-946-02-00-012	400	Pin Pricked	2
9-946-02-01-020	630	Pin Pricked	2
9-946-04-00-010	500	Pin Pricked	4
Tech Sheet 10487			



DN2 Per Metre

0330	Max Pressure Bar	DN
9-946-02-00-020	630	2
Tech Sheet 10487		

Fluid-Air Components Ltd

TEST POINT COUPLINGS

spradow
german engineering at your service

Spradow - Innovative Measuring Systems

The **Spradow** test coupling enables you to connect a pressure gauge or other measuring instruments in seconds - even if the system is still under pressure. The connection can be applied without any further tools.

The non-return valve inside the test coupling opens only after being connected with the measuring instrument to allow a secure and clean pressure measurement.

Pressure is an important parameter for a successful preventing service and maintenance or, if necessary, trouble-shooting.

With **Spradow** test couplings you can reduce your service and maintenance costs considerably.

The **Spradow** test box is the perfect tool for hydraulic systems offering service and maintenance engineers an easy mobile pressure test solution.

The complete **Spradow** test equipment is of course compatible with all other manufactures and fulfils all current important industrial standards.

Furthermore **Spradow** offers a comprehensive range of measuring systems for pneumatic braking systems.

Pressure Test Kits

Contents:
- 1 x Microbore Hose DN2-400 1620 Gauge Connection 1/4" BSPP 400 bar
- 1 x Pressure Gauge 0-40 bar 1/4" BSPP
- 1 x Pressure Gauge 0-400 bar 1/4" BSPP
- 1 x Gauge Connection 1620 1/4" BSPP
- 1 x Test Point 1620 1/4" BSPP Metal Cap
- 1 x Test Point 1620 M10 x 1
- 1 x Adaptor 1/4" Female x 3/8" Male
- 1 x Adaptor 1/4" Female x 1/2" Male
- 1 x Cleaning Cloth
- 1 x 1/4" Bonded Seal
- 1 x 3/8" Bonded Seal
- 1 x 1/2" Bonded Seal



400 bar, Pressure Test Kit

0330
HYD-KIT1
Tech Sheet 10292

Contents:
- 1 x SNA 1620 Adaptor 1/4" Male x Female
- 1 x SNA 1620 Adaptor 3/8" Male x Female
- 1 x SNA 1620 Adaptor 1/2" Male x Female
- 1 x Test Point 1620 1/4" BSPP Metal Cap
- 1 x Pressure Gauge 0-40 bar 1/4" BSPP
- 1 x Pressure Gauge 0-400 bar 1/4" BSPP
- 1 x Adaptor 1/4" Female x 1/2" Male
- 1 x Adaptor 1/4" Female x 3/8" Male
- 1 x Microbore Hose DN2-400 1620/Gauge Connection 1/4" BSPP 400 bar
- 1 x Cleaning Cloth
- 1 x 1/4" Bonded Seal
- 1 x 3/8" Bonded Seal
- 1 x 1/2" Bonded Seal



400 bar, Test Kit BSPP with In-line Tees

0330
HYD-KIT2
Tech Sheet 10292

You might also need
Glycerine Gauges
see pages **414-416**



Contents:
- 1 x SNA 1620 Adaptor 1/4" Male x Female
- 1 x SNA 1620 Adaptor 3/8" Male x Female
- 1 x SNA 1620 Adaptor 1/2" Male x Female
- 1 x Test Point 1620 1/4" BSPP Metal Cap
- 1 x Test Point 1620 1/8" BSPP Metal Cap
- 1 x Test Point 1620 M10 x 1
- 1 x Test Point 1620 M12 x 1.5 Metal Cap
- 1 x Adaptor 1/4" Female x 1/2" Male
- 1 x Adaptor 1/4" Female x 3/8" Male
- 1 x Pressure Gauge 0-400 bar 1/4" BSPP
- 1 x Pressure Gauge 0-40 bar 1/4" BSPP
- 1 x Microbore Hose DN2-400 1620/Gauge Connection 1/4"BSP 400 bar
- 1 x Cleaning Cloth
- 1 x 1/4" Bonded Seal
- 1 x 3/8" Bonded Seal
- 1 x 1/2" Bonded Seal



400 bar, Test Kit BSPP/Metric with In-line Tees

0330
HYD-KIT3
Tech Sheet 10292

Deluxe Pressure Test Kits



400 bar, Pressure Test Kit

0330
HYD-KIT4
Tech Sheet 10292

Same contents as HYD-KIT1 + Deluxe Spradow Box

400 bar, Test Kit BSPP with In-line Tees

0330
HYD-KIT5
Tech Sheet 10292

Same contents as HYD-KIT2 + Deluxe Spradow Box

400 bar, Test Kit BSPP/ Metric with In-line Tees

0330
HYD-KIT6
Tech Sheet 10292

Same contents as HYD-KIT3 + Deluxe Spradow Box

F.A.C
Fluid-Air Components Ltd

HYDRAULIC OIL COOLERS

AC Range Air Blast Oil Coolers

The LAC air oil cooler, with single-phase or three-phase AC motor, is optimised for use in the industrial sector. The maximum cooling capacity is 300kW at ETD +40°C.

See Tech Sheet for full specification on this model.

Maximum Working Temperature: +120°C

Maximum Static Working Pressure: 21 bar

Maximum Dynamic Working Pressure: 14 bar



BSPP

0488	Thread	Voltage	KW/°C
LAC-1	1/2"	230/1/50	0.05
LAC-3	1"	230/3/50-275/3/60	0.36
LAC-6	1.1/4"	230/3/50	1.75
LAC-7	1.1/4"	230/3/50	2.1
Tech Sheet 60442			

DC Range Air Blast Oil Coolers

The LDC air oil cooler with 24V DC motor is optimised for use in the mobile industry.

Together with a wide range of accessories, the LDC cooler is suitable for installation in most applications and environments.

Maximum Working Temperature: +120°C

Maximum Static Working Pressure: 21 bar

Maximum Dynamic Working Pressure: 14 bar

The maximum cooling capacity is 30kW at +ETD 40°C.

Also available with a 12V DC motor.

See Tech Sheet for full specification on this model.



BSPP

0488	Thread	Voltage	KW/°C
LDC-1	1"	24V	0.12
LDC-2	1"	24V	0.19
LDC-3	1"	24V	0.3
LDC-4	1"	24V	0.38
LDC-5	1"	24V	0.6
LDC-6	1.1/4"	24V	0.72
Tech Sheet 60443			

Offline Air Blast Oil Cooler

The LOC cooling system with three-phase AC motor is optimised for use in the industrial sector.

The system is supplied ready for installation. An integrated circulation pump makes it possible to cool and treat the oil in a separate circuit (offline cooling)

See Tech Sheet for full specification on this model.

Maximum Working Temperature: +100°C

Maximum Static Working Pressure: 21 bar

Maximum Dynamic Working Pressure: 14 bar



BSPP

0488	Thread	Voltage	KW/°C
LOC-1	1"	230/3/50-275/3/60	0.07
LOC-2	1"	230/3/50-275/3/60	0.2
LOC-3	1"	230/3/50-275/3/60	0.26
LOC-4	1"	230/3/50-275/3/60	0.45
LOC-5	1"	230/3/50-275/3/60	0.61
LOC-6	1.1/4"	230/3/50	1
Tech Sheet 60444			

Hydraulic Motor In-line Coolers

The LHC air oil cooler with hydraulic motor is optimised for use in the mobile and industrial sectors.

The maximum cooling capacity is 300kW at ETD +40°C.

See Tech Sheet for full specification on this model

Maximum Working Temperature: +120°C

Maximum Static Working Pressure: 21 bar

Maximum Dynamic Working Pressure: 14 bar



BSPP

0488	Thread	Motor Option	KW/°C
LHC-1	1"	8.4cc	0.22
LHC-2	1"	14.4cc	0.38
LHC-3	1"	10.8cc	0.58
LHC-4	1"	10.8cc	0.76
LHC-5	1.1/4"	10.8cc	1.1
LHC-6	1.1/4"	8.4cc	1.3
Tech Sheet 60445			

Compact Water/Oil Coolers

The Parker PWO is a compact and lightweight water/oil cooler with a high cooling capacity for its size.

Features:

- Light and compact
- Suitable for many applications
- Easy installation
- Cost-efficient and environmentally friendly

Material:

- Plates: EN 10028/7-1.4401 (AISI 316)
- Brazing: pure copper
- Connections: EN 10272-1.4401 (AISI 316)

For full specification on this item see ech Sheet.

Working Temperature: -196°C to +225°C

Maximum Working Pressure: 31 bar at 155°C



BSPP

0488	Thread	Thread	KW/°C	Type
PWO-1	3/4"	1/2"	1.5-5	B5TH
PWO-2	3/4"	1/2"	4-7	B8TH
PWO-3	3/4"	1/2"	5-17	B8TH
PWO-4	3/4"	1/2"	7-27	B8TH
PWO-5	1"	3/4"	5-27	B10TH
PWO-6	1"	3/4"	10-50	B10TH
PWO-7	1"	3/4"	10-65	B10TH
PWO-8	1.1/4"	1"	10-60	B25TH
PWO-9	1.1/4"	1"	10-80	B25TH
PWO-10	1.1/4"	1"	20-95	B25TH
PWO-11	1.1/4"	1"	20-105	B25TH
Tech Sheet 60460				

Fluid-Air Components Ltd

HYDRAULIC TOOLING & LIFTING EQUIPMENT

UK CA



Cylinders



Pumps



Cylinder Kits



Accessories



Bottle Jacks



Toe Jacks

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HYDRAULIC TOOLING & LIFTING EQUIPMENT

- Collar threads and base
- Hard chrome-plated piston plunger protects against corrosion and damage
- Polyurethane U cup seals provide a sure seal and long life
- Solid one-piece alloy steel body
- One-piece aluminium alloy bearing protects against cylinder wall damage
- Dust cap is standard on all cylinders

Maximum Working Pressure: 700 bar

Cylinders



5 Ton General Purpose, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
H0503	78	169	247
H0505	129	221	350
H0507	180	272	452
H0509	229	324	552
Tech Sheet 60403			



15 Ton General Purpose, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
H1501	25	124	149
H1502	51	149	200
H1504	101	200	301
H1506	152	270	422
H1508	203	321	524
H1510	245	372	626
H1512	305	423	728
H1514	356	474	830
Tech Sheet 60403			



55 Ton General Purpose, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
H5502	51	176	227
H5504	103	227	330
H5506	159	283	442
H5510	260	385	645
H5513	337	461	798
Tech Sheet 60403			



10 Ton General Purpose, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
H1001	25	92	117
H1002	51	123	174
H1004	102	174	276
H1006	151	250	401
H1008	202	301	503
H1010	253	352	605
H1012	304	403	707
H1014	356	450	806
Tech Sheet 60403			



25 Ton General Purpose, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
H2501	26	143	169
H2502	51	168	219
H2504	102	219	321
H2506	155	272	427
H2508	206	323	529
H2510	257	374	631
H2512	310	426	736
H2514	362	476	838
Tech Sheet 60403			

Fluid-Air Components Ltd

HYDRAULIC TOOLING & LIFTING EQUIPMENT

Maximum Working Pressure:
700 bar

Pumps

- Metal reservoirs resist cracking
- Built-in bypass device protects the hydraulic system from over-pumping damage (US Patent No. 5,946,912)
- Compact yet powerful air turbo motor (US Patent No. 5,341,723)
- Suggested air inlet range: 110-175 psi (7.6-12.1 bar)



Air Pump, Single Acting

0481	Thread	Oil Capacity Litres	Material
PA1500	3/8"	346.4	Aluminium
Tech Sheet 60403			

- Portable, lightweight and compact design
- Universal motor starts under full load
- 3m 24V AC pendant control for safety
- Weighs only 17kg with oil
- External pressure adjustment is available
- Designed for intermittent duty operation
- Gauge port on control valve



Universal Motor Pump

0481	Thread	LPM	HP	Voltage
PU20M4N01B	3/8"	0.46	1	110V AC
Tech Sheet 60406				

- Metal reservoirs resist cracking
- Internal pressure relief valve for overload protection
- Perfect for use with cylinders and hydraulic tools or OEM applications
- Two-speed pumps reduce user fatigue and increase productivity



Single Speed Hand Pump, Single Acting

0481	Thread	Oil Capacity cm³	Material
P601S	3/8"	600	Steel
Tech Sheet 60403			



Two-speed Hand Pumps, Single Acting

0481	Thread	Oil Capacity cm³	Material
P350	3/8"	350	Aluminium
P1000	3/8"	1000	Aluminium
Tech Sheet 60403			



Hand Pump, Double Acting

0481	Thread	Oil Capacity cm³	Material
P2301M	3/8"	2200	Steel
Tech Sheet 60403			

Fluid-Air Components Ltd

HYDRAULIC TOOLING & LIFTING EQUIPMENT

- Stackable magnetic adaptors, various heights
- Eliminates dangerous cribbing
- Convenient carrying case
- US Patent No. 7,237,762 B2

Maximum Working Pressure:
700 bar

Cylinder Kits

Adaptor sizes: 4, 11, 23 and 30mm.



5 Ton Flat Body Cylinder Kit, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
HF0503B	6	32	38
Tech Sheet 60405			

Adaptor sizes: 10, 20 and 40mm.



20 Ton Flat Body Cylinder Kit, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
HF2005B	11	51	62
Tech Sheet 60405			

Adaptor sizes: 10, 20 and 40mm.



50 Ton Flat Body Cylinder Kit, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
HF5006B	16	67	83
Tech Sheet 60405			

Adaptor sizes: 10, 20 and 40mm.



10 Ton Flat Body Cylinder Kit, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
HF1005B	11	43	54
Tech Sheet 60405			

Adaptor sizes: 10, 20 and 40mm.



30 Ton Flat Body Cylinder Kit, Single Acting

0481	Stroke mm	Min Height mm	Max Height mm
HF3005B	13	59	72
Tech Sheet 60405			

- Compact design for use in small spaces
- Ideal for pushing applications
- Plunger wiper helps seal out dirt and contamination
- Return spring ensures a quick retraction and extends the life of the spring
- Industrial hard chrome-plated plunger helps prevent scratching and corrosion
- Includes stackable 1", 2" and 3" aluminium adaptors that conveniently snap into the base of the plunger
- Includes high flow CH38F coupler and dust cap
- Convenient storage case
- Bolt-on tilt saddles available



10 Ton Low Profile Cylinder Kit

0481	Stroke mm	Min Height mm	Max Height mm
HL-1001-D	38	88	126
Tech Sheet 60404			

Fluid-Air Components Ltd

HYDRAULIC TOOLING & LIFTING EQUIPMENT

Accessories

- Rubber bend restrictors
- High working pressure
- Optimum flexibility
- Lightweight

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
700 bar



Hose Assembly, Male NPT

0481	Thread	Length Metres
CS3814-1	3/8"	1
CS3814-2	3/8"	2
CS3814-3	3/8"	3
CS3814-4	3/8"	4
CS3814-6	3/8"	6
Tech Sheet 60403		



High Flow Quick Release Coupling, NPT

0481	Thread
CH38	3/8"
Tech Sheet 60403	

Bottle Jacks

- Easily adjustable extension screw (2-20 tons)
- Removable rubber carry ring for easy storage of pump handle (2-20 tons)
- Safety valve against over-loading
- Supplied with a carry grip (8 tons and over)



Manual

0481	Stroke mm	Min Height mm	Max Height mm
1412000	228	241	469
1420000	226	249	475
1430000	212	268	480
10500	178	305	483
10990	156	305	461
Tech Sheet 60403			

Toe Jacks

- Low height
- Heat-treated and chrome-plated medium carbon steel cylinder
- Chrome-plated plunger improves seal life and optimises performance
- By-pass device protects hydraulic system from over-travel damage (US Patented)
- Hydraulic system is protected from internal damage by a patented by-pass mechanism (US Patent No. 5946912)

Maximum Working Pressure:
700 bar



Manual

0481	Stroke mm	Min Height mm	Max Height mm
J13060	130	15	147
J13120	130	23	152
J13200	130	28	160
J13300	130	28	168
Tech Sheet 68802			

Fluid-Air Components Ltd

Spill Absorbents

Perforated for High Absorbency



The unique perforated design of the dimple roll allows the material to be used in the most efficient way.

FT Pro spill absorbents are a superior range of spill solutions designed for ultimate versatility and economical usage.



Unfold for larger spills.




Fold to use as a boom for increased absorbency.



Tear off pieces to use only what you need.

Spill Kits available in reusable carry bags with barrier tape, gloves and safety goggles.





Large range of spill absorbents for many applications and spill types.

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SPILL ABSORBENTS & SPILL PREVENTION

FT PRO

Oil Only Heavy-duty Spill Pads

Oil only absorbents are best used outdoors to recover oil-based spills such as petroleum, diesel and solvents.



100 Pads Per Pack

0365	Size cm	Absorbency Per Pack
HDOP-100	40 x 50	108 Litres

Oil Only Spill Dimple Pads

Oil only absorbents are best used outdoors to recover oil-based spills such as petroleum, diesel and solvents.

200 Pads Per Pack

0365	Size cm	Absorbency Per Pack
SOP-200	40 x 50	128 Litres

Oil Spill Perforated Dimple Rolls

Oil only absorbents are best used outdoors to recover oil-based spills such as petroleum, diesel and solvents.



2 x 40 Metre Rolls Per Pack

0365	Size	Absorbency Per Pack
OR-2-40	40cm x 40m	113 Litres

Oil Only Folded Perforated Dimple Rolls

Oil only absorbents are best used outdoors to recover oil-based spills such as petroleum, diesel and solvents.



18 Metre Rolls Per Pack

0365	Size	Absorbency Per Pack	Contents
FOR-3-18	11cm x 18m	105 Litres	3
FOR-1-18	11cm x 18m	35 Litres	1

Oil Only Spill Socks

Oil only absorbents are best used outdoors to recover oil-based spills such as petroleum, diesel and solvents.




20 Socks Per Pack

0365	Size cm	Absorbency Per Pack
SOS-20	7.6 x 120	85 Litres

General Purpose Spill Dimple Pads

As a general rule of thumb, if the spill happens indoors use a general purpose product to absorb both oil and water-based substances.



20 Pads Per Pack

0365	Size cm	Absorbency Per Pack
SGP-20	40 x 50	128 Litres

General Purpose Spill Perforated Dimple Rolls

As a general rule of thumb, if the spill happens indoors use a general purpose product to absorb both oil and water-based substances.



2 x 40 Metre Rolls Per Pack

0365	Size	Absorbency Per Pack
SGR-2-40	40cm x 40m	153 Litres

General Purpose Spill Folded Perforated Dimple Rolls

As a general rule of thumb, if the spill happens indoors use a general purpose product to absorb both oil and water-based substances.



18 Metre Rolls Per Pack

0365	Size	Absorbency Per Pack	Contents
FGR-3-18	11cm x 18m	105 Litres	3
FGR-1-18	11cm x 18m	35 Litres	1

General Purpose Spill Socks


As a general rule of thumb, if the spill happens indoors use a general purpose product to absorb both oil and water-based substances.



20 Socks Per Pack

0365	Size cm	Absorbency Per Pack
SGS-20	7.6 x 120	70 Litres

Loose Absorbents



16kg Bag

0751
CG16

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SPILL ABSORBENTS & SPILL PREVENTION

Chemical Spill Pads

- Suitable for toxic, flammable, corrosive and aggressive liquids
- Fire retardant as per ASTM 726
- Low slip base layer, great for foot traffic



100 Pads Per Pack

0365	Size cm	Absorbency Per Pack
COP-100	40 x 50	78 Litres
	Tech Sheet 67960	

Chemical Spill Perforated Dimple Rolls

- Suitable for toxic, flammable, corrosive and aggressive liquids
- Fire retardant as per ASTM 726
- Low slip base layer, great for foot traffic



2 x 40 Metre Rolls Per Pack

0365	Size	Absorbency Per Pack
CSR-2-40	40cm x 40m	114 Litres

Chemical Spill Socks

- Suitable for small hazardous, toxic or unknown based spills
- Absorbs both oil and water based fluids
- Once saturated, will not become slippery



20 Socks Per Pack

0365	Size cm	Absorbency Per Pack
CSS-20	8 x 120	80 Litres
	Tech Sheet 67961	

Bags of Rags



0086	Weight Kg
BOR-10KG	10

Shoulder Bag Spill Kit

Kit includes:

- 1 x reusable carry bag.
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 55 x oil only dimple pads.
- 6 x 1.2 metre oil only socks.



Oil Only

0365	Absorbency Per Pack
SOK-50	50 Litres

Kit includes:

- 1 x reusable carry bag.
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 55 x general purpose dimple pads.
- 6 x 1.2 metre general purpose socks.



General Purpose

0365	Absorbency Per Pack
SGK-50	50 Litres

Fluid-Air Components Ltd

SPILL ABSORBENTS & SPILL PREVENTION

Carry Bag Spill Kit

Kit includes:
- 1 x reusable carry bag.
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 30 x oil only dimple pads.
- 4 x 1.2 metre oil only socks.



Oil Only

0365	Absorbency Per Pack
SOK-30	30 Litres

Kit includes:
- 1 x reusable carry bag.
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 30 x general purpose dimple pads.
- 4 x 1.2 metre general purpose socks.



General Purpose

0365	Absorbency Per Pack
SGK-30	30 Litres

Refill Kit

Kit includes:
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 55 x oil only dimple pads.
- 6 x 1.2 metre oil only socks.



Oil Only

0365	Absorbency Per Pack
SOK-50-REFILL	50 Litres

Kit includes:
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 30 x oil only dimple pads.
- 4 x 1.2 metre oil only socks.



Oil Only

0365	Absorbency Per Pack
SOK-30-REFILL	30 Litres

Kit Includes:
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 55 x general purpose dimple pads.
- 6 x 1.2 metre general purpose socks.



General Purpose

0365	Absorbency Per Pack
SGK-50-REFILL	50 Litres

Kit includes:
- 50 metres of barrier tape.
- 2 x cable ties.
- 2 x disposal sacks.
- 2 x pairs of disposable Dura-Touch gloves.
- 1 x vented safety goggles.
- 30 x general purpose dimple pads.
- 4 x 1.2 metre general purpose socks.



General Purpose

0365	Absorbency Per Pack
SGK-30-REFILL	30 Litres

Fluid-Air Components Ltd

HYDRAULIC OILS

ISO 32 Hydraulic Oil

Quality mineral hydraulic oil with good anti-wear performance, oxidation resistance, corrosion protection, low pour, air release and anti-foam properties.

Conforms to DIN 51524 11.



20 Litre Drum

0026	Volume Litres
2020-0333	20
Tech Sheet 544	

10W Hydraulic Oil

Hydraulic Oil 10W is a high performance hydraulic oil formulated from solvent refined paraffinic base oils and high performance additives designed to meet a wide range of heavy-duty hydraulic equipment requirements.

Benefits include: Good deposit control, good anti-sludge and varnish resistance, excellent anti-wear and corrosion protection.

Oxidation stability, dispersant/detergent properties and wide temperature range.

High viscosity index promotes high oil pressure.

Conforms to API: SF/CD and MIL-L-2104C.



20 Litre Drum

0026	Volume Litres
10W OIL	20
Tech Sheet 3147	

ISO 46 Hydraulic Oil

Hydraulic oil 46 is blended to ISO 46 viscosity grade requirements and is suitable for use in a wide range of mobile and static hydraulic equipment.

Benefits include: Excellent anti-wear, anti-corrosion, anti-rust performance, low air retention/air entrainment, low foaming and good thermal stability and resistance to oxidation.

Confirms to DIN 51524, Part 2 (HLP).



20 Litre Drum

0026	Volume Litres
ISO 46	20
Tech Sheet 10318	

ATF Dexron II

ATF Dexron II is a high performance multi-application fluid. The high viscosity index and low pour point makes this product ideal for use in hydraulic systems and power steering.

Conforms to GM Dexron II D and GM 6137-M.



20 Litre Drum

0026	Volume Litres
ATF II	20
Tech Sheet 3148	

For **Workshop Fluid Transfer** see pages **1655-1656**






Fluid-Air Components Ltd

SPILL ABSORBENTS & SPILL PREVENTION

Trays

Made from 100% polyethylene, these spill trays come with a removable grid and are ideal for ensuring drips and spills are contained correctly.
Applications: Truck and machinery leaks, machine part cleaning, ink solvent storage, battery storage and chemical dosing points.



Bunded Spill Trays

0480	Capacity Litres	Weight Kg	Height mm	Length mm	Width mm	Max Working Load Kg
ST20	22	3.5	175	595	395	55
ST30	31	4.5	170	805	405	55
ST40	43	7	170	800	605	105
ST60	63	10	200	1000	605	205
ST100	104	14	185	1195	795	205
Tech Sheet 67968						

Drain Cover

An integral part of any spill response plan, drain covers go hand in hand with spill response kits. They can also be used proactively, to seal off drains prior to deliveries or refuelling taking place, to ensure leaks and spills are kept out of the drainage system.



Magnetic Drain Cover

0480	Height mm	Length mm	Thickness mm
MDC03	600	600	0.9
Tech Sheet 67970			

Drum Spill Containment

Manufactured from medium density polyethylene, these pallets comply with the guidelines issued by environment agencies. They are robust, resistant to most chemicals and come with a removable grid.



Bunded Drum Pallets

0480	Capacity Litres	Weight Kg	Height mm	Length mm	Width mm	Max Working Load Kg
BP2-205	240	24	330	1220	820	650
BP4-205	410	40	370	1310	1310	1250
Tech Sheet 67969						

Absorbent Dispensing Stations

Ideal for day-to-day housekeeping or responding to minor spills, these polyethylene cabinets are specifically designed for dispensing absorbents. Accepts rolls up to 550mm diameter x 520mm wide.
Weight: 20kg.
Absorbents not included.



Open Front Absorbent Centre, Polyethylene

0480	Size
POLY-STATION	64cm x 58cm x 118cm


Floor standing with single roll holder and workstation cabinet. Welded together to provide a safe and secure fixing.
Weight: 29kg.
Absorbents not included.



Combined Absorbent Centre, Steel

0480	Size
WSHOP-STATION	66cm x 42cm x 150.5cm

Twin wall mounted absorbent roll holders.
Weight: 10.5kg.
Absorbents not included.



Wall Mountable Twin Roll Holder, Steel

0480	Size
WALL-STATION	66cm x 42cm x 89cm

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 **Hydraulic Quick Release Couplings** 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 2

Hydraulic Quick Release Couplings

2 Hydraulic Quick Release Couplings

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 2 Hydraulic QRCs

2.00 Hydraulic QRCs

- ISO A Interchange Couplings & Plugs
- ISO B Interchange Couplings & Plugs
- ISO 5676 Trailer Brake Couplings & Plugs
- ISO 16028 Flat Face Couplings
- T Series Hydraulic Quick Release Coupling
- Screw-on Couplings
- High Pressure Spin-on Couplings
- Stainless Steel Couplings & Plugs
- Push/Pull Breakaway Steel Couplings
- Coupling & Plug Colour Rings
- Screw to Connect Couplings & Plugs
- Ultra High Pressure Couplings
- ISO 14540 Screw Couplings
- Wing Nut Screw Couplings
- TDG Swivel Joints
- Brass Couplings & Plugs
- Thread to Connect Couplings



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PROFILE IDENTIFICATION

ISO A Interchange Plugs



HKPA16CS, FT Pro, ISO A Plugs Page 290



HKPA12CS, FT Pro, ISO A Plugs Page 290



HKPA08CS, FT Pro, ISO A Plugs Page 290




HKPA06CS, FT Pro, ISO A Plugs Page 290



HKPA06CS, FT Pro, ISO A Plugs Page 290

ISO B Interchange Plugs



HKP16B, FT Pro, ISO B Plugs Page 291



HKP12B, FT Pro, ISO B Plugs Page 291



HKP08B, FT Pro, ISO B Plugs Page 291



HKP06B, FT Pro, ISO B Plugs Page 291



HKP04B, FT Pro, ISO B Plugs Page 291



HKP02B, FT Pro, ISO B Plugs Page 291

PROFILE IDENTIFICATION

ISO 16028 Interchange, Flat Face



HKPFF16CS, FT Pro, ISO 16028 Flat Face Plug Page 292



HKPFF12CS, FT Pro, ISO 16028 Flat Face Plug Page 292



HKPFF08CS, FT Pro, ISO 16028 Flat Face Plug Page 292



HKPFF06CS, FT Pro, ISO 16028 Flat Face Plug Page 292



HKPFF04CS, FT Pro, ISO 16028 Flat Face Plug Page 292

Note: Due to the change in finished used by our suppliers. the product you receive may differ from that illustrated

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FT PRO has a quality range of **hydraulic quick release couplings** which have been manufactured to the highest specification using quality materials.



The range consists of interchange couplings designed to meet or exceed ISO A, ISO B, Flat Faced ISO 16028, Trailer Brake ISO 5676, Spin on High Pressure 88, 97 and 98 Series, in a variation of coated steel, stainless steel and brass.

FT Pro quick release couplings are tried, tested and used extensively throughout the world's manufacturing facilities and in the mobile plant industry.

Applications:

- Hydraulics
- Offshore
- Construction
- Marine
- Agriculture
- High pressure water applications
- Mining
- OEM machine building

NOW INCLUDES VITON SEALING OPTIONS FOR MORE AGGRESSIVE MEDIA

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

ISO A INTERCHANGE COUPLINGS & PLUGS

ISO A Interchange

Working Temperature:
-25°C to +120°C Nitrile
-25°C to +175°C Viton



Carbon Steel ISO A Coupling with Nitrile Seals, BSPP

8111	Thread	Max Pressure Bar
HKSA04CS	1/4"	350
HKSA06CS	3/8"	315
HKSA08CS	1/2"	250
HKSA12CS	3/4"	250
HKSA16CS	1"	230
HKSA20CS	1.1/4"	230
HKSA24CS	1.1/2"	180
HKSA32CS	2"	130
Tech Sheet 10002		

Carbon Steel ISO A Coupling with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKSA04CS-NPT	1/4"	350
HKSA06CS-NPT	3/8"	315
HKSA08CS-NPT	1/2"	250
HKSA12CS-NPT	3/4"	250
HKSA16CS-NPT	1"	230
HKSA24CS-NPT	1.1/2"	180
HKSA32CS-NPT	2"	130
Tech Sheet 10002		

Carbon Steel ISO A Coupling with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HKSA04CS-V	1/4"	350
HKSA06CS-V	3/8"	315
HKSA08CS-V	1/2"	250
HKSA12CS-V	3/4"	250
HKSA16CS-V	1"	230
HKSA20CS-V	1.1/4"	230
HKSA24CS-V	1.1/2"	180
HKSA32CS-V	2"	130
Tech Sheet 10002		



ISO A Coupling Dust Protection Cap

8111	To Suit
ISOADC-4	1/4"
ISOADC-6	3/8"
ISOADC-8	1/2"
ISOADC-12	3/4"
ISOADC-16	1"
Tech Sheet 10002	



Carbon Steel ISO A Plug with Nitrile Seals, BSPP

8111	Thread	Max Pressure Bar
HKPA04CS	1/4"	350
HKPA06CS	3/8"	315
HKPA08CS	1/2"	250
HKPA12CS	3/4"	250
HKPA16CS	1"	230
HKPA20CS	1.1/4"	230
HKPA24CS	1.1/2"	180
HKPA32CS	2"	130
Tech Sheet 10002		

Carbon Steel ISO A Plug with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKPA04CS-NPT	1/4"	350
HKPA06CS-NPT	3/8"	315
HKPA08CS-NPT	1/2"	250
HKPA12CS-NPT	3/4"	250
HKPA16CS-NPT	1"	230
HKPA20CS-NPT	1.1/4"	230
HKPA24CS-NPT	1.1/2"	180
HKPA32CS-NPT	2"	130
Tech Sheet 10002		

Carbon Steel ISO A Plug with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HKPA04CS-V	1/4"	350
HKPA06CS-V	3/8"	315
HKPA08CS-V	1/2"	250
HKPA12CS-V	3/4"	250
HKPA16CS-V	1"	230
HKPA20CS-V	1.1/4"	230
HKPA24CS-V	1.1/2"	180
HKPA32CS-V	2"	130
Tech Sheet 10002		



ISO A Plug Dust Protection Plug

8111	To Suit
ISOADP-4	1/4"
ISOADP-6	3/8"
ISOADP-8	1/2"
ISOADP-12	3/4"
ISOADP-16	1"
Tech Sheet 10002	

stainless steel



316 Stainless Steel ISO A Coupling with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HFSSFC7314-V	1/4"	250
HFSSFC7338-V	3/8"	200
HFSSFC7312-V	1/2"	200
HFSSFC7334-V	3/4"	160
HFSSFC7310-V	1"	125
Tech Sheet 10002		

316 Stainless Steel ISO A Coupling with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKSA04SS-NPT	1/4"	250
HKSA06SS-NPT	3/8"	200
HKSA08SS-NPT	1/2"	200
HKSA12SS-NPT	3/4"	160
HKSA16SS-NPT	1"	125
Tech Sheet 10002		

stainless steel



316 Stainless Steel ISO A Plug with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HFSSFP7314-V	1/4"	250
HFSSFP7338-V	3/8"	200
HFSSFP7312-V	1/2"	200
HFSSFP7334-V	3/4"	160
HFSSFP7310-V	1"	125
Tech Sheet 10002		

316 Stainless Steel ISO A Plug with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKPA04SS-NPT	1/4"	250
HKPA06SS-NPT	3/8"	200
HKPA08SS-NPT	1/2"	200
HKPA12SS-NPT	3/4"	160
HKPA16SS-NPT	1"	125
Tech Sheet 10002		

Fluid-Air Components Ltd

ISO B INTERCHANGE COUPLINGS & PLUGS

ISO B Interchange

Other seals available on request

Working Temperature:
-25°C to +120°C Nitrile
-25°C to +175°C Viton



Carbon Steel ISO B Coupling with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKS04CS	1/4"	350
HKS06CS	3/8"	315
HKS08CS	1/2"	250
HKS12CS	3/4"	230
HKS16CS	1"	200
Tech Sheet 10003		

Carbon Steel ISO B Coupling with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKS02CS-NPT	1/8"	350
HKS04CS-NPT	1/4"	350
HKS06CS-NPT	3/8"	315
HKS08CS-NPT	1/2"	250
HKS12CS-NPT	3/4"	250
HKS16CS-NPT	1"	230
Tech Sheet 10003		



Carbon Steel ISO B Plug with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKP04CS	1/4"	350
HKP06CS	3/8"	315
HKP08CS	1/2"	250
HKP12CS	3/4"	230
HKP16CS	1"	200
Tech Sheet 10003		

Carbon Steel ISO B Plug with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKP04CS-NPT	1/4"	350
HKP06CS-NPT	3/8"	315
HKP08CS-NPT	1/2"	250
HKP12CS-NPT	3/4"	250
HKP16CS-NPT	1"	230
Tech Sheet 10003		



ISO B Plug & Coupling Dust Protection Cap

8111	To Suit
ISOBDP-4	1/4"
ISOBDP-6	3/8"
ISOBDP-8	1/2"
ISOBDP-12	3/4"
ISOBDP-16	1"
Tech Sheet 10003	

stainless steel



316 Stainless Steel ISO B Coupling with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKS02SS	1/8"	250
HKS04SS	1/4"	250
HKS06SS	3/8"	200
HKS08SS	1/2"	200
HKS12SS	3/4"	160
HKS16SS	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Coupling with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKS04SS-NPT	1/4"	250
HKS06SS-NPT	3/8"	200
HKS08SS-NPT	1/2"	200
HKS12SS-NPT	3/4"	160
HKS16SS-NPT	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Coupling with Viton Seal, BSPP

0249	Thread	Max Pressure Bar
HKS02SS-V	1/8"	250
HKS04SS-V	1/4"	250
HKS06SS-V	3/8"	200
HKS08SS-V	1/2"	200
HKS12SS-V	3/4"	160
HKS16SS-V	1"	125
Tech Sheet 10003		



Brass ISO B Coupling with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKS02B	1/8"	200
HKS04B	1/4"	180
HKS06B	3/8"	180
HKS08B	1/2"	160
HKS12B	3/4"	120
HKS16B	1"	120
Tech Sheet 10003		

Brass ISO B Coupling with Viton Seals, BSPP

0249	Thread	Max Pressure Bar
HKS02B-V	1/8"	200
HKS04B-V	1/4"	180
HKS06B-V	3/8"	180
HKS08B-V	1/2"	160
HKS12B-V	3/4"	120
HKS16B-V	1"	120
Tech Sheet 10003		

stainless steel



316 Stainless Steel ISO B Plug with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKP02SS	1/8"	250
HKP04SS	1/4"	250
HKP06SS	3/8"	200
HKP08SS	1/2"	200
HKP12SS	3/4"	160
HKP16SS	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Plug with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKP04SS-NPT	1/4"	250
HKP06SS-NPT	3/8"	200
HKP08SS-NPT	1/2"	200
HKP12SS-NPT	3/4"	160
HKP16SS-NPT	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Plug with Viton Seal, BSPP

0249	Thread	Max Pressure Bar
HKP02SS-V	1/8"	250
HKP04SS-V	1/4"	250
HKP06SS-V	3/8"	200
HKP08SS-V	1/2"	200
HKP12SS-V	3/4"	160
HKP16SS-V	1"	125
Tech Sheet 10003		



Brass ISO B Plug with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKP02B	1/8"	200
HKP04B	1/4"	180
HKP06B	3/8"	180
HKP08B	1/2"	160
HKP12B	3/4"	120
HKP16B	1"	120
Tech Sheet 10003		

Brass ISO B Plug with Viton Seals, BSPP

0249	Thread	Max Pressure Bar
HKP02B-V	1/8"	200
HKP04B-V	1/4"	180
HKP06B-V	3/8"	180
HKP08B-V	1/2"	160
HKP12B-V	3/4"	120
HKP16B-V	1"	120
Tech Sheet 10003		

Fluid-Air Components Ltd

ISO 5676 TRAILER BRAKE, INTERCHANGE COUPLINGS & PLUGS

High Pressure Screw-on Coupling (Carbon Steel), 65 Series, ISO 5676

Working Temperature: -25°C to +120°C Nitrile

Maximum Working Pressure: 220 bar

Used to connect the hydraulic braking system of tractors to their trailers.

Socket with Nitrile Seals, BSPP & Metric

8111	Thread
HFSFC6538	3/8"
HFSFC6512	1/2"
HFSFC6518	M18 x 1.5
HFSFC6522	M22 x 1.5
Tech Sheet 2126	



Plug with Nitrile Seals, BSPP & Metric

8111	Thread
HFSFP6538	3/8"
HFSFP6512	1/2"
HFSFP6518	M18 x 1.5
HFSFP6522	M22 x 1.5
Tech Sheet 2126	



ISO 16028 INTERCHANGE, FLAT FACE COUPLINGS

ISO 16028 Interchange

Working Temperature: -25°C to +120°C Nitrile

Designed to meet or exceed the requirements of ISO 16028. Flush face and dry break design facilitates easy cleaning prior to connection. Manufactured from high strength steel construction.

Other seals available on request

Steel Flat Face Coupling with Nitrile Seals, BSPP

8111	Thread	Body	Max Pressure Bar
HKSFF04CS	1/4"	1/4"	315
HKSFF06CS	3/8"	3/8"	250
HKSFF0608CS	1/2"	3/8"	250
HKSFF08CS	1/2"	1/2"	250
HKSFF12CS	3/4"	1/2"	250
HKSFF1212CS	3/4"	3/4"	250
HKSFF16CS	1"	3/4"	250
HKSFF1616CS	1"	1"	200
HKSFF2016CS	1.1/4"	1"	200
Tech Sheet 10233			



Steel Flat Face Plug with Nitrile Seals, BSPP

8111	Thread	Body	Max Pressure Bar
HKPFF04CS	1/4"	1/4"	315
HKPFF06CS	3/8"	3/8"	250
HKPFF0608CS	1/2"	3/8"	250
HKPFF08CS	1/2"	1/2"	250
HKPFF12CS	3/4"	1/2"	250
HKPFF1212CS	3/4"	3/4"	250
HKPFF16CS	1"	3/4"	250
HKPFF1616CS	1"	1"	200
HKPFF2016CS	1.1/4"	1"	200
Tech Sheet 10233			





Dust Protection Cap, Plug

8111	To Suit
FFDP-04	1/4"
FFDP-06	3/8"
FFDP-08	1/2"
FFDP-12	3/4"
FFDP-16	1"
Tech Sheet 10233	



Dust Protection Cap, Coupling

8111	To Suit
FFDC-04	1/4"
FFDC-06	3/8"
FFDC-08	1/2"
FFDC-12	3/4"
FFDC-16	1"
Tech Sheet 10233	

Fluid-Air Components Ltd

ISO 16028 FLAT FACE COUPLINGS

ISO 16028, High Pressure Series

Working Temperature:
-25°C to +120°C Nitrile

HP Series offers higher pressure ratings, superior flow ratings and lower pressure drops compared to our standard series. The change in the design increases the male bearing points and decreases the brinelling effect. The couplings are ideal for applications involving high pressure impulses on agriculture, mobile construction and plant equipment.

Other seals available on request.

Steel Flat Face Couplings with Nitrile Seals, BSPP



8111	Thread	Body	Max Pressure Bar
HPSFF04CS	1/4"	1/4"	420
HPSFF06CS	3/8"	3/8"	350
HPSFF00608CS	1/2"	3/8"	350
HPSFF08CS	1/2"	1/2"	330
HPSFF12CS	3/4"	1/2"	330
HPSFF01212CS	3/4"	3/4"	330
HPSFF16CS	1"	3/4"	330
HPSFF1616CS	1"	1"	300
HPSFF2016CS	1.1/4"	1"	300
Tech Sheet 10277			

Steel Flat Face Plug with Nitrile Seals, BSPP



8111	Thread	Body	Max Pressure Bar
HPPFF04CS	1/4"	1/4"	420
HPPFF06CS	3/8"	3/8"	350
HPPFF00608CS	1/2"	3/8"	350
HPPFF08CS	1/2"	1/2"	330
HPPFF12CS	3/4"	1/2"	330
HPPFF01212CS	3/4"	3/4"	330
HPPFF16CS	1"	3/4"	330
HPPFF1616CS	1"	1"	300
HPPFF2016CS	1.1/4"	1"	300
Tech Sheet 10277			

T SERIES HYDRAULIC QUICK RELEASE COUPLING

Manual Locking Coupling with Pressure Eliminator

Working Temperature:
-25°C to +120°C Nitrile
-25°C to +175°C Viton

The T Series coupling is designed for high pressure systems. A manually operated locking ring provides extra security against unintentional disconnection.
All come complete with poppet valves and pressure eliminator.

Interchangeability: Parker Tema

Other seals available on request.

Steel Coupling, Nitrile Seals, BSPP



0385	Thread	Max Pressure Bar
TSC06CS	3/8"	350
TSC08CS	1/2"	300
TSC12CS	3/4"	280
TSC16CS	1"	250
Tech Sheet 10278		

Steel Plug, Nitrile Seals, BSPP



0385	Thread	Max Pressure Bar
TSP06CS	3/8"	350
TSP08CS	1/2"	300
TSP12CS	3/4"	280
TSP16CS	1"	250
Tech Sheet 10278		

Steel Coupling, Viton Seals, BSPP

0385	Thread	Max Pressure Bar
TSC06CS-V	3/8"	350
TSC08CS-V	1/2"	300
TSC12CS-V	3/4"	280
TSC16CS-V	1"	250
Tech Sheet 10278		

Steel Plug, Viton Seals, BSPP

0385	Thread	Max Pressure Bar
TSP06CS-V	3/8"	350
TSP08CS-V	1/2"	300
TSP12CS-V	3/4"	280
TSP16CS-V	1"	250
Tech Sheet 10278		

Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

Screw-on Couplings, 98 Series

Working Temperature: -25°C to +120°C

Ideal for hydraulic dump trucks, oil field equipment, spreading equipment and applications requiring the ability to connect or disconnect under pressure.
With Standard Seals: Nitrile

Only plug and socket with same thread fit together.



Brass Body/Zinc Plated Steel Wing Nut.



Coupling, NPTF

8111	Thread	Max Pressure Bar
HFBFP9834	3/4"	210
HFBFP9810	1"	210
HFBFP98114	1.1/4"	190
HFBFP98112	1.1/2"	175
Tech Sheet 2128		

Plug, NPTF

8111	Thread	Max Pressure Bar
HFBFC9834	3/4"	210
HFBFC9810	1"	210
HFBFC98114	1.1/4"	190
HFBFC98112	1.1/2"	175
Tech Sheet 2128		

HIGH PRESSURE SPIN-ON COUPLINGS (CARBON STEEL)

88 Series

Working Temperature: -25°C to +120°C

Maximum Working Pressure: 700 bar

This series of couplings with their threaded union locking system and precision ball-type check valves, are designed for extreme high pressure applications such as found on portable hydraulic rams.

Interchangeability:
Hansen HP3 Series
Parker 3000 Series
Faster PVVM Series
DNP PVS Series
Stucchi IVHP Series
Safeway S30 Series



Coupling with Nitrile Seals, NPTF

8111	Thread
HFSFC8814	1/4"
HFSFC8838	3/8"
Tech Sheet 10005	



88 Series Aluminium Dust Covers

8111	To Suit
HFSFC-14-DP	1/4"
HFSFC-38-DP	3/8"
HFSFP-14-DC	1/4"
HFSFP-38-DC	3/8"
Tech Sheet 10005	



Plug with Nitrile Seals, NPTF

8111	Thread
HFSFP8814	1/4"
HFSFP8838	3/8"
Tech Sheet 10005	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

The leader in coupling innovation

- DNP combine sophisticated complex technology, highly skilled and experienced operators, tight production and assembly controls, and systematic vigorous testing in order to produce a vast range of superior couplings.
- Quality assurance ISO 9002.
- Interchangeable couplings with other major manufacturers.
- The range consists of over 60 varieties of couplings, including ISO A, ISO B, flat face, screw/ISO 14541 and push-pull, with working pressures up to 1500 bar.
- The range also includes multi-coupling plates which allow simultaneous coupling and uncoupling of a certain number of hydraulic and or electrical lines.



- Selected ranges (flat face – PVT4 BOP, PVTX BOP, PST4 BOP and ISO B – PBV1 BOP) come with Lloyds registered approval. The range is specially designed for blow-out preventer accumulator systems in the oil and gas market.



Lloyd's Register TYPE APPROVAL

DNV·GL

FULL RANGE AVAILABLE

Tech Sheet **20574**


Inspection Certificate


MANAGEMENT SYSTEM CERTIFICATE

To see the latest certification consult Tech Sheet 71604

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HYDRAULIC QUICK RELEASE COUPLINGS

PAV1 Series, ISO A Steel Couplings

Standard: ISO 7241-1 A
Occlusion: Poppet
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III)

Available Threads: BSP, NPT, RC, SAE
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed

Working Temperature:
-25°C to +100°C Nitrile
-25°C to +200°C Viton

Maximum Working Pressure:
350 bar



Coupling with Nitrile Seal, BSPP

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.002	1/4"	6.3	350
PAV1.1010.002	3/8"	10	350
PAV1.1313.002	1/2"	12.5	250
PAV1.2019.002	3/4"	20	250
PAV1.2525.002	1"	25	200
PAV1.3031.002	1.1/4"	31.5	200
PAV1.3939.002	1.1/2"	40	190
PAV1.5051.002	2"	50	160
Tech Sheet 20473			

Coupling with Nitrile Seal, NPT

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.012	1/4"	6.3	350
PAV1.1010.012	3/8"	10	350
PAV1.1313.012	1/2"	12.5	250
PAV1.2019.012	3/4"	20	250
PAV1.2525.012	1"	25	200
PAV1.3031.012	1.1/4"	31.5	200
PAV1.3939.012	1.1/2"	40	190
PAV1.5051.012	2"	50	160
Tech Sheet 20473			

Coupling with Viton Seal, BSPP

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.002 V	1/4"	6.3	350
PAV1.1010.002 V	3/8"	10	350
PAV1.1313.002 V	1/2"	12.5	250
PAV1.2019.002 V	3/4"	20	250
PAV1.2525.002 V	1"	25	200
PAV1.3031.002 V	1.1/4"	31.5	200
PAV1.3939.002 V	1.1/2"	40	190
PAV1.5051.002 V	2"	50	160
Tech Sheet 20473			



Plug with Nitrile Seal, BSPP

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.003	1/4"	6.3	350
PAV1.1010.003	3/8"	10	350
PAV1.1313.003	1/2"	12.5	250
PAV1.2019.003	3/4"	20	250
PAV1.2525.003	1"	25	200
PAV1.3031.003	1.1/4"	31.5	200
PAV1.3939.003	1.1/2"	40	190
PAV1.5051.003	2"	50	160
Tech Sheet 20473			

Plug with Nitrile Seal, NPT

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.013	1/4"	6.3	350
PAV1.1010.013	3/8"	10	350
PAV1.1313.013	1/2"	12.5	250
PAV1.2019.013	3/4"	20	250
PAV1.2525.013	1"	25	200
PAV1.3031.013	1.1/4"	31.5	200
PAV1.3939.013	1.1/2"	40	190
PAV1.5051.013	2"	50	160
Tech Sheet 20473			

Plug with Viton Seal, BSPP

0457	Thread	ISO	Max Pressure Bar
PAV1.0606.003 V	1/4"	6.3	350
PAV1.1010.003 V	3/8"	10	350
PAV1.1313.003 V	1/2"	12.5	250
PAV1.2019.003 V	3/4"	20	250
PAV1.2525.003 V	1"	25	200
PAV1.3031.003 V	1.1/4"	31.5	200
PAV1.3939.003 V	1.1/2"	40	190
PAV1.5051.003 V	2"	50	160
Tech Sheet 20473			

ISO A Protection Caps & Plugs



Plug for Coupling

0457	To Suit	Material
SPAV.06002	ISO 6.3	Plastic
SPAV.10002	ISO 10	Plastic
SPAV.13002	ISO 12.5	Plastic
SPAV.20002	ISO 20	Plastic
SPAV.25002	ISO 25	Plastic
Tech Sheet 20475		



Cap for Plug

0457	To Suit	Material
SPAV.06003	ISO 6.3	Plastic
SPAV.10003	ISO 10	Plastic
SPAV.13003	ISO 12.5	Plastic
SPAV.20003	ISO 20	Plastic
SPAV.25003	ISO 25	Plastic
Tech Sheet 20475		

BURNETT & HILLMAN
HYDRAULIC ADAPTOR UK MANUFACTURER



For **Burnett & Hillman Hydraulic Adaptors**
see pages **52-81**

Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

stainless steel

PAVX Series, ISO A Stainless Steel Couplings

Working Temperature: -25°C to +200°C Viton

Maximum Working Pressure: 450 bar

Standard: ISO 7241-1 A
Occlusion: Poppet
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PAVX.0606.002	1/4"	6.3	450
PAVX.1010.002	3/8"	10	300
PAVX.1313.002	1/2"	12.5	300
PAVX.2019.002	3/4"	20	250
PAVX.2525.002	1"	25	200
PAVX.3031.002	1.1/4"	31.5	100
PAVX.3939.002	1.1/2"	40	80
PAVX.5051.002	2"	50	60
Tech Sheet 20474			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PAVX.0606.003	1/4"	6.3	450
PAVX.1010.003	3/8"	10	300
PAVX.1313.003	1/2"	12.5	300
PAVX.2019.003	3/4"	19	250
PAVX.2525.003	1"	25	200
PAVX.3031.003	1.1/4"	31.5	100
PAVX.3939.003	1.1/2"	40	80
PAVX.5051.003	2"	50	60
Tech Sheet 20474			



PBVX Series, ISO B Stainless Steel Couplings

Working Temperature: -25°C to +200°C

Maximum Working Pressure: 400 bar

Standard: ISO 7241-1 B
Occlusion: Poppet
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVX.0404.002	1/8"	5	400
PBVX.0606.002	1/4"	6.3	350
PBVX.1010.002	3/8"	10	300
PBVX.1313.002	1/2"	12.5	300
PBVX.2019.002	3/4"	20	220
PBVX.2525.002	1"	25	200
PBVX.3931.002	1.1/4"	40	80
PBVX.3939.002	1.1/2"	40	80
PBVX.5051.002	2"	50	60
Tech Sheet 20478			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVX.0404.003	1/8"	5	400
PBVX.0606.003	1/4"	6.3	350
PBVX.1010.003	3/8"	10	300
PBVX.1313.003	1/2"	12.5	300
PBVX.2019.003	3/4"	20	220
PBVX.2525.003	1"	25	200
PBVX.3931.003	1.1/4"	40	80
PBVX.3939.003	1.1/2"	40	80
PBVX.5051.003	2"	50	60
Tech Sheet 20478			



PTV1 Series, Nordic Interchange Steel Couplings

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 300 to 370 bar

Interchange: Tema T Series
Occlusion: Poppet
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III)

Available Threads: BSP, NPT
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed

Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PTV1.1010.002	3/8"	10	370
PTV1.1313.002	1/2"	12.5	350
PTV1.2019.002	3/4"	19	300
PTV1.2525.002	1"	25	300
Tech Sheet 68086			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PTV1.1010.003	3/8"	10	370
PTV1.1313.003	1/2"	12.5	350
PTV1.2019.003	3/4"	19	300
PTV1.2525.003	1"	25	300
Tech Sheet 68086			



Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

PPV3 Series, ISO A Push/Pull Breakaway Steel Couplings

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 350 bar

Push/pull design, ideal for mobile applications using hydraulic attachments, PPV series is designed to break away in case of accidental pulls, one hand to connect and disconnect.

Standard: ISO 7241-1 A
Sleeve: Double acting
Occlusion: Poppet
Locking: Radial balls

Material: steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT, SAE, metric
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed



Coupling, BSPP


0457	Thread	ISO	Max Pressure Bar
PPV3.0606.112	1/4"	6.3	350
PPV3.1010.112	3/8"	10	300
PPV3.1313.112	1/2"	12.5	250
PPV3.2019.112	3/4"	19	250
PPV3.2525.112	1"	25	225
Tech Sheet 20475			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PPV3.0606.113	1/4"	6.3	350
PPV3.1010.113	3/8"	10	300
PPV3.1313.113	1/2"	12.5	250
PPV3.2019.113	3/4"	19	250
PPV3.2525.113	1"	25	225
Tech Sheet 20475			

The DNP range also includes multi-coupling plates which allow simultaneous coupling and uncoupling of a certain number of hydraulic and/or electrical lines.





Coupling, DIN 2353, Male Thread

0457	Thread	Size	ISO	Max Pressure Bar
PPV3.1012.302	M12 x 1.5	6L	10	300
PPV3.1014.302	M14 x 1.5	8L	10	300
PPV3.1016.302	M16 x 1.5	10L	10	300
PPV3.1018.302	M18 x 1.5	12L	10	300
PPV3.1016.402	M16 x 1.5	8S	10	300
PPV3.1018.402	M18 x 1.5	10S	10	300
PPV3.1020.402	M20 x 1.5	12S	10	300
PPV3.1314.302	M14 x 1.5	8L	12.5	250
PPV3.1316.302	M16 x 1.5	10L	12.5	250
PPV3.1318.302	M18 x 1.5	12L	12.5	250
PPV3.1322.302	M22 x 1.5	15L	12.5	250
PPV3.1326.302	M26 x 1.5	18L	12.5	250
PPV3.1318.402	M18 x 1.5	10S	12.5	250
PPV3.1320.402	M20 x 1.5	12S	12.5	250
PPV3.1322.402	M22 x 1.5	14S	12.5	250
PPV3.1324.402	M24 x 1.5	16S	12.5	250
PPV3.1330.402	M30 x 2	20S	12.5	250
Tech Sheet 20475				



Plug, DIN 2353, Male Thread

0457	Thread	Size	ISO	Max Pressure Bar
PPV3.1012.303	M12 x 1.5	6L	10	300
PPV3.1014.303	M14 x 1.5	8L	10	300
PPV3.1016.303	M16 x 1.5	10L	10	300
PPV3.1018.303	M18 x 1.5	12L	10	300
PPV3.1016.403	M16 x 1.5	8S	10	300
PPV3.1018.403	M18 x 1.5	10S	10	300
PPV3.1020.403	M20 x 1.5	12S	10	300
PPV3.1314.303	M14 x 1.5	8L	12.5	250
PPV3.1316.303	M16 x 1.5	10L	12.5	250
PPV3.1318.303	M18 x 1.5	12L	12.5	250
PPV3.1322.303	M22 x 1.5	15L	12.5	250
PPV3.1326.303	M26 x 1.5	18L	12.5	250
PPV3.1318.403	M18 x 1.5	10S	12.5	250
PPV3.1320.403	M20 x 1.5	12S	12.5	250
PPV3.1322.403	M22 x 1.5	14S	12.5	250
PPV3.1324.403	M24 x 1.5	16S	12.5	250
PPV3.1330.403	M30 x 2	20S	12.5	250
Tech Sheet 20475				



Coupling, DIN 2353, Male Bulkhead Thread

0457	Thread	Size	ISO	Max Pressure Bar
PPV3.1012.502	M12 x 1.5	6L	10	300
PPV3.1014.502	M14 x 1.5	8L	10	300
PPV3.1016.502	M16 x 1.5	10L	10	300
PPV3.1018.502	M18 x 1.5	12L	10	300
Tech Sheet 20475				



Plug, DIN 2353, Male Bulkhead Thread

0457	Thread	Size	ISO	Max Pressure Bar
PPV3.1012.503	M12 x 1.5	6L	10	300
PPV3.1014.503	M14 x 1.5	8L	10	300
PPV3.1016.503	M16 x 1.5	10L	10	300
PPV3.1018.503	M18 x 1.5	12L	10	300
PPV3.1016.603	M16 x 1.5	8S	10	300
PPV3.1018.603	M18 x 1.5	10S	10	300
PPV3.1020.603	M20 x 1.5	12S	10	300
PPV3.1314.503	M14 x 1.5	8L	12.5	250
PPV3.1316.503	M16 x 1.5	10L	12.5	250
PPV3.1318.503	M18 x 1.5	12L	12.5	250
PPV3.1322.503	M22 x 1.5	15L	12.5	250
PPV3.1326.503	M26 x 1.5	18L	12.5	250
PPV3.1318.603	M18 x 1.5	10S	12.5	250
PPV3.1320.603	M20 x 1.5	12S	12.5	250
PPV3.1322.603	M22 x 1.5	14S	12.5	250
PPV3.1324.603	M24 x 1.5	16S	12.5	250
PPV3.1330.603	M30 x 2	20S	12.5	250
Tech Sheet 20475				

Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

stainless steel

PLTX Series, ISO 16028 Flat Face Couplings, Stainless Steel

Standard: ISO 16028
Occlusion: Flat face
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT, SAE
Standard Seals: Viton
Optional Seals: EPDM, FFKM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 350 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLTX.0606.112	1/4"	6.3	400
PLTX.1310.112	3/8"	10	250
PLTX.1313.112	1/2"	10	250
PLTX.2013.112	1/2"	12.5	250
PLTX.2019.112	3/4"	12.5	250
PLTX.2519.112	3/4"	19	250
PLTX.2525.112	1"	19	250
PLTX.3031.112	1.1/4"	25	250
PLTX.3939.112	1.1/2"	40	150
PLTX.5051.112	2"	50	100
Tech Sheet 20483			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLTX.0606.113	1/4"	6.3	400
PLTX.1310.113	3/8"	10	250
PLTX.1313.113	1/2"	10	250
PLTX.2013.113	1/2"	12.5	250
PLTX.2019.113	3/4"	12.5	250
PLTX.2519.113	3/4"	19	250
PLTX.2525.113	1"	19	250
PLTX.3031.113	1.1/4"	25	250
PLTX.3939.113	1.1/2"	40	150
PLTX.5051.113	2"	50	100
Tech Sheet 20483			

PLSX Series, Flat Face, Stainless Steel

Interchange: Snap-Tite 71
Occlusion: Flat face
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 350 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLSX.0606.112	1/4"	6.3	350
PLSX.1010.112	3/8"	10	350
PLSX.1013.112	1/2"	10	350
PLSX.1313.112	1/2"	12.5	350
PLSX.2019.112	3/4"	19	350
PLSX.2525.112	1"	25	350
PLSX.2531.112	1.1/4"	25	350
Tech Sheet 20485			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLSX.0606.113	1/4"	6.3	350
PLSX.1010.113	3/8"	10	350
PLSX.1013.113	1/2"	10	350
PLSX.1313.113	1/2"	12.5	350
PLSX.2019.113	3/4"	19	350
PLSX.2525.113	1"	25	350
PLSX.2531.113	1.1/4"	25	350
Tech Sheet 20485			

PLS1 Series, Flat Face

Material: Steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT, SAE

Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLS1.0606.112	1/4"	6.3	350
PLS1.1010.112	3/8"	10	350
PLS1.1013.112	1/2"	10	350
PLS1.1313.112	1/2"	12.5	350
PLS1.2019.112	3/4"	19	350
PLS1.2525.112	1"	25	350
PLS1.2531.112	1.1/4"	25	350
Tech Sheet 20484			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLS1.0606.113	1/4"	6.3	350
PLS1.1010.113	3/8"	10	350
PLS1.1013.113	1/2"	10	350
PLS1.1313.113	1/2"	12.5	350
PLS1.2019.113	3/4"	19	350
PLS1.2525.113	1"	25	350
PLS1.2531.113	1.1/4"	25	350
Tech Sheet 20484			

ISO 16028 Flat Face Protection Caps & Plugs

Plug for Coupling



Cap for Plug



Plug for Coupling

0457	To Suit	Material
SPLT.06002	ISO 6.3	Plastic
SPLT.13002	ISO 10	Plastic
SPLT.20002	ISO 12.5	Plastic
SPLT.25002	ISO 19	Plastic
Tech Sheet 20483		

Cap for Plug

0457	To Suit	Material
SPLT.06003	ISO 6.3	Plastic
SPLT.13003	ISO 10	Plastic
SPLT.20003	ISO 12.5	Plastic
SPLT.25003	ISO 19	Plastic
SPLT.30003	ISO 25	Plastic
Tech Sheet 20483		

ISO 16028 Automatic Caps



Cap for Coupling

0457	To Suit	Colour
SPLT.13302	ISO 10	Red
SPLT.13342	ISO 10	Black
SPPV.13302	ISO 12.5	Black
SPPV.13312	ISO 12.5	Black
SPPV.13322	ISO 12.5	Yellow
SPPV.13342	ISO 12.5	Red
Tech Sheet 20483		

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC QUICK RELEASE COUPLINGS

PBV1 Series, ISO B Steel Couplings

Standard: ISO 7241-1 B
Occlusion: Poppet
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 500 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PBV1.0404.002	1/8"	5	500
PBV1.0606.002	1/4"	6.3	250
PBV1.1010.002	3/8"	10	250
PBV1.1313.002	1/2"	12.5	250
PBV1.2019.002	3/4"	20	250
PBV1.2525.002	1"	25	250
PBV1.3931.002	1.1/4"	40	200
PBV1.3939.002	1.1/2"	40	200
PBV1.5051.002	2"	50	100
Tech Sheet 20476			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PBV1.0404.003	1/8"	5	500
PBV1.0606.003	1/4"	6.3	250
PBV1.1010.003	3/8"	10	250
PBV1.1313.003	1/2"	12.5	250
PBV1.2019.003	3/4"	20	250
PBV1.2525.003	1"	25	250
PBV1.3931.003	1.1/4"	40	200
PBV1.3939.003	1.1/2"	40	200
PBV1.5051.003	2"	50	100
Tech Sheet 20476			

PBVM Series, ISO B Brass Couplings

Standard: ISO 7241-1 B
Occlusion: Poppet
Locking: Radial balls
Material: Brass
Finishing: Nickel plating on request
Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +200°C

Maximum Working Pressure: 300 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVM.0404.002	1/8"	5	300
PBVM.0606.002	1/4"	6.3	200
PBVM.1010.002	3/8"	10	200
PBVM.1313.002	1/2"	12.5	180
PBVM.2019.002	3/4"	20	130
PBVM.2525.002	1"	25	130
PBVM.3931.002	1.1/4"	40	60
PBVM.3939.002	1.1/2"	40	60
PBVM.5051.002	2"	50	50
Tech Sheet 20477			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVM.0404.003	1/8"	5	300
PBVM.0606.003	1/4"	6.3	200
PBVM.1010.003	3/8"	10	200
PBVM.1313.003	1/2"	12.5	180
PBVM.2019.003	3/4"	20	130
PBVM.2525.003	1"	25	130
PBVM.3931.003	1.1/4"	40	60
PBVM.3939.003	1.1/2"	40	60
PBVM.5051.003	2"	50	50
Tech Sheet 20477			

ISO B Protection Caps & Plugs



Plug for Coupling

0457	To Suit	Material
SPBV.06002	ISO 6.3	Plastic
SPBV.10002	ISO 10	Plastic
SPBV.13002	ISO 12.5	Plastic
SPBV.20002	ISO 20	Plastic
SPBV.25002	ISO 25	Plastic
Tech Sheet 20477		

Cap for Plug

0457	To Suit	Material
SPBV.06003	ISO 6.3	Plastic
SPBV.10003	ISO 10	Plastic
SPBV.13003	ISO 12.5	Plastic
SPBV.20003	ISO 20	Plastic
SPBV.25003	ISO 25	Plastic
Tech Sheet 20477		

For **High Pressure Metric Tube Couplings** see pages **138-140**



Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

PLT1 Series, ISO 16028 Flat Face Couplings

Standard: ISO16028
Occlusion: Flat face
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT, SAE
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 300 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLT1.0606.002	1/4"	6.3	300
PLT1.1310.002	3/8"	10	250
PLT1.1313.002	1/2"	10	250
PLT1.2013.002	1/2"	12.5	250
PLT1.2019.002	3/4"	12.5	250
PLT1.2519.002	3/4"	19	250
PLT1.2525.002	1"	19	250
PLT1.3031.002	1.1/4"	25	250
PLT1.3939.002	1.1/2"	40	250
PLT1.5051.112	2"	50	250
Tech Sheet 20479			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLT1.0606.003	1/4"	6.3	300
PLT1.1310.003	3/8"	10	250
PLT1.1313.003	1/2"	10	250
PLT1.2013.003	1/2"	12.5	250
PLT1.2019.003	3/4"	12.5	250
PLT1.2519.003	3/4"	19	250
PLT1.2525.003	1"	19	250
PLT1.3031.003	1.1/4"	25	250
PLT1.3939.003	1.1/2"	40	250
Tech Sheet 20479			

PLT4 Series, ISO 16028 Flat Face Couplings

High working pressures to 7.350 psi/500 bar, sleeve lock device, locking radial balls. PLT 4 series is ideal for non-spill high pressure and high impulse applications.

Standard: ISO16028
Occlusion: Flat face
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III) and Zn-Ni
Available Threads: BSP, NPT, SAE, metric
Standard Seals: Nitrile and PU
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 500 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLT4.0606.112	1/4"	6.3	500
PLT4.1310.112	3/8"	10	400
PLT4.1313.112	1/2"	10	350
PLT4.2013.112	1/2"	12.5	350
PLT4.2019.112	3/4"	12.5	350
PLT4.2519.112	3/4"	19	350
PLT4.2525.112	1"	19	350
PLT4.3025.112	1"	25	350
PLT4.3031.112	1.1/4"	25	350
Tech Sheet 20480			

Coupling, SAE

0457	Thread	ISO	Max Pressure Bar
PLT4.1319.032	3/4"	10	350
PLT4.2027.032	1.1/16"	12.5	350
Tech Sheet 20480			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLT4.0606.113	1/4"	6.3	500
PLT4.1310.113	3/8"	10	400
PLT4.1313.113	1/2"	10	350
PLT4.2013.113	1/2"	12.5	350
PLT4.2019.113	3/4"	12.5	350
PLT4.2519.113	3/4"	19	350
PLT4.2525.113	1"	19	350
PLT4.3025.113	1"	25	350
PLT4.3031.113	1.1/4"	25	350
Tech Sheet 20480			

Plug, SAE

0457	Thread	ISO	Max Pressure Bar
PLT4.1319.033	3/4"	10	350
PLT4.2027.033	1.1/16"	12.5	350
Tech Sheet 20480			

PLK4 Series, ISO 16028 Flat Face Plug, Connect Under Pressure

Interchanges with any ISO16028 quick disconnect, connect under pressure to 3,675 psi/250 bar, high pressure up to 5,800 psi/400 bar, flat face, non-spill design, high resistance steel. PLK4 series is ideal for systems that need to be connected under residual pressure, high pressure applications, attachments that may have trapped pressure in the system.

Standard: ISO16028
Occlusion: Flat face
Locking: Radial balls
Material: High resistance steel
Finishing: Zn-Fe (Cr III) and Zn-Ni
Available Threads: BSP, NPT, SAE, metric
Standard Seals: Nitrile and PU
Optional Seals: Viton, EPDM
Connection Under Pressure: Allowed (male side only)
Maximum Residual Pressure: 250 bar

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 400 bar



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLK4.0606.113	1/4"	6.3	400
PLK4.1310.113	3/8"	10	350
PLK4.1313.113	1/2"	10	350
PLK4.2013.113	1/2"	12.5	350
PLK4.2019.113	3/4"	12.5	350
PLK4.2519.113	3/4"	19	300
PLK4.2525.113	1"	19	300
PLK4.3025.113	1"	25	300
PLK4.3031.113	1.1/4"	25	300
PLK4.3939.113	1.1/2"	40	250
PLK4.5051.113	2"	50	250
Tech Sheet 20482			

FAC
Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

PLT Colour Safe System

- For use with PLT1, PLT4, PLT5 and PLTX series couplings
- Helps keep workers safe
- Helps to prevent equipment damage
- Easy to use and implement



Coupling Colour Ring, ISO 6.3

0457	Colour
PLT.006.802	Red
PLT.006.812	Yellow
PLT.006.822	Green
PLT.006.832	Blue
PLT.006.852	White
PLT.006.862	Grey
PLT.006.882	Violet
PLT.006.892	Brown
Tech Sheet 68088	

Coupling Colour Ring, ISO 10

0457	Colour
PLT.013.802	Red
PLT.013.812	Yellow
PLT.013.822	Green
PLT.013.832	Blue
PLT.013.852	White
PLT.013.862	Grey
PLT.013.872	Orange
PLT.013.882	Violet
PLT.013.892	Brown
Tech Sheet 68088	

Coupling Colour Ring, ISO 12.5

0457	Colour
PLT.019.802	Red
PLT.019.812	Yellow
PLT.019.822	Green
PLT.019.832	Blue
PLT.019.852	White
PLT.019.862	Grey
PLT.019.872	Orange
PLT.019.882	Violet
PLT.019.892	Brown
Tech Sheet 68088	

Coupling Colour Ring, ISO 19


0457	Colour
PLT.025.802	Red
PLT.025.812	Yellow
PLT.025.822	Green
PLT.025.832	Blue
PLT.025.842	Black
PLT.025.872	Orange
Tech Sheet 68088	

Coupling Colour Ring, ISO 25

0457	Colour
PLT.030.802	Red
PLT.030.812	Yellow
PLT.030.822	Green
PLT.030.832	Blue
PLT.030.872	Orange
Tech Sheet 68088	

FT PRO®

For **Hydraulic Hose**
see pages **6-14**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c c a c c

HYDRAULIC QUICK RELEASE COUPLINGS

PLT Colour Safe System

- Helps keep workers safe
- Helps to prevent equipment damage
- Easy to use and implement



Plug Colour Ring, ISO 6.3 for use with PLT1, PLT4 & PLTX

0457	Colour
PLT.006.803	Red
PLT.006.813	Yellow
PLT.006.833	Blue
PLT.006.853	White
PLT.006.863	Grey
PLT.006.873	Orange
PLT.006.883	Violet
PLT.006.893	Brown
Tech Sheet 68088	

Plug Colour Ring, ISO 10 for use with PLT1

0457	Colour
PLT.613.803	Red
PLT.613.813	Yellow
PLT.613.823	Green
PLT.613.833	Blue
PLT.613.843	Black
PLT.613.853	White
PLT.613.873	Orange
PLT.613.893	Brown
Tech Sheet 68088	

Plug Colour Ring, ISO 12.5 for use with PLT1, PLT4 & PLTX

0457	Colour
PLT.019.803	Red
PLT.019.813	Yellow
PLT.019.823	Green
PLT.019.833	Blue
PLT.019.853	White
PLT.019.863	Grey
PLT.019.873	Orange
PLT.019.883	Violet
PLT.019.893	Brown
Tech Sheet 68088	

Plug Colour Ring, ISO 19 for use with PLT1, PLT4, PLT5 & PLTX

0457	Colour
PLT.025.803	Red
PLT.025.813	Yellow
PLT.025.823	Green
PLT.025.833	Blue
PLT.025.843	Black
PLT.025.873	Orange
Tech Sheet 68088	

Plug Colour Ring, ISO 25 for use with PLT4.3031.113, PLT4.3031.013 & PLT4.3041.033

0457	Colour
PLT.030.803	Red
PLT.030.813	Yellow
PLT.030.823	Green
PLT.030.833	Blue
PLT.030.843	Black
PLT.030.873	Orange
Tech Sheet 68088	

NORMA

For **Pipe Repair Couplings** see page **1557**



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC QUICK RELEASE COUPLINGS

PST4 Series, Screw to Connect Flat Face Couplings

Interchanges with Stucchi VEP, high-tech anti-corrosion plating salt spray tested for 700 hours before any appearance of surface red rust, high working pressures, connects and disconnects by hand up to 4,400 psi/300 bar, seal is blowout resistant to 4,400 psi/300 bar when connecting or disconnecting with residual pressure. Exceeds 1,000,000 impulse cycles, flat face design eliminates spillage upon disconnection, thread to connect style coupling eliminates brinelling issues, heavy-duty hex nut.

Interchangeability: Stucchi VEP
Occlusion: Flat face
Locking: Screw
Material: Steel
Finishing: Zn-Fe (Cr III) and Zn-Ni

Available Threads: BSP, NPT, SAE
Standard Seals: Nitrile and PU
Optional Seals: Viton, EPDM
Connection Under Pressure: Allowed (both male or female side)

Maximum Residual Pressure: 300 bar

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 450 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PST4.0606.112	1/4"	6.3	450
PST4.1310.112	3/8"	10	350
PST4.1313.112	1/2"	10	350
PST4.2013.112	1/2"	12.5	350
PST4.2019.112	3/4"	12.5	350
PST4.2519.112	3/4"	19	350
PST4.2525.112	1"	19	350
PST4.3025.112	1"	25	350
PST4.3031.112	1.1/4"	25	350
PST4.3939.112	1.1/2"	40	300

Tech Sheet 20486



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PST4.0606.113	1/4"	6.3	450
PST4.1310.113	3/8"	10	350
PST4.1313.113	1/2"	10	350
PST4.2013.113	1/2"	12.5	350
PST4.2019.113	3/4"	12.5	350
PST4.2519.113	3/4"	19	350
PST4.2525.113	1"	19	350
PST4.3025.113	1"	25	350
PST4.3031.113	1.1/4"	25	350
PST4.3939.113	1.1/2"	40	300

Tech Sheet 20486

PVV3 Series, ISO 14541 Screw Couplings

Standard: ISO 14541
Occlusion: Poppet
Locking: Screw
Material: Steel

Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT, SAE, metric
Standard Seals: Nitrile
Optional Seals: Viton, EPDM

Connection Under Pressure: Allowed (both male or female side)
Maximum Residual Pressure: working pressure

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 450 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PVV3.0606.112	1/4"	6.3	450
PVV3.1010.112	3/8"	10	400
PVV3.1313.112	1/2"	12.5	400
PVV3.2019.112	3/4"	19	300
PVV3.2525.112	1"	25	300
PVV3.3031.112	1.1/4"	31.5	300
PVV3.3039.112	1.1/2"	31.5	300

Tech Sheet 20487



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PVV3.0606.113	1/4"	6.3	450
PVV3.1010.113	3/8"	10	400
PVV3.1313.113	1/2"	12.5	400
PVV3.2019.113	3/4"	19	300
PVV3.2525.113 T	1"	25	300
PVV3.3031.113 T	1.1/4"	31.5	300
PVV3.3039.113 T	1.1/2"	31.5	300

Tech Sheet 20487

VVS High Pressure Screw Couplings & Plugs

Interchange: VVS faster
Occlusion: Poppet
Locking: Screw
Material: Steel

Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT
Standard Seals: Nitrile

Optional Seals: Viton, EPDM
Connection Under Pressure: Allowed (both male or female side)

Working Temperature: -25°C to +100°C
Working Pressure: 210 to 650 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
VVV1.1010.002	3/8"	10	650
VVV1.1313.002	1/2"	12.5	600
VVV1.2019.002	3/4"	19	500
VVV1.2525.002	1"	25	460
VVV1.3031.002	1.1/4"	31.5	360
VVV1.3939.002	1.1/2"	40	360
VVV1.5051.002	2"	50	210

Tech Sheet 68087



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
VVV1.1010.003	3/8"	10	650
VVV1.1313.003	1/2"	12.5	600
VVV1.2019.003	3/4"	19	500
VVV1.2525.003	1"	25	460
VVV1.3031.003	1.1/4"	31.5	360
VVV1.3939.003	1.1/2"	40	360
VVV1.5051.003	2"	50	210

Tech Sheet 68087

PST4 Series, Protection Caps & Plugs

Plug for Coupling



Cap for Plug



Plug for Coupling

0457	To Suit	Material
SPST.06202	ISO 6.3	Aluminium
SPST.13202	ISO 10	Aluminium
SPST.20202	ISO 12.5	Aluminium
SPST.25202	ISO 19	Aluminium
SPST.30202	ISO 25	Aluminium
SPST.39202	ISO 40	Aluminium

Tech Sheet 20486

Cap for Plug

0457	To Suit	Material
SPST.06203	ISO 6.3	Aluminium
SPST.13203	ISO 10	Aluminium
SPST.20203	ISO 12.5	Aluminium
SPST.25203	ISO 19	Aluminium
SPST.30203	ISO 25	Aluminium
SPST.39203	ISO 40	Aluminium

Tech Sheet 20486

ISO 14541 Protection Caps & Plugs

Cap for Plug



Plug for Coupling



Plug for Coupling

0457	To Suit	Material
SPVV.06002	ISO 6.3	Polypropylene
SPVV.10002	ISO 10	Polypropylene
SPVV.13002	ISO 12.5	Polypropylene
SPVV.20002	ISO 20	Polypropylene
SPVV.25002	ISO 25	Polypropylene
SPVV.30002	ISO 31.5	Polypropylene
SPVV.10202	ISO 10	Aluminium
SPVV.13202	ISO 12.5	Aluminium
SPVV.20202	ISO 20	Aluminium
SPVV.25202	ISO 25	Aluminium
SPVV.30202	ISO 31.5	Aluminium

Tech Sheet 20487

Cap for Plug

0457	To Suit	Material
SPVV.06003	ISO 6.3	Polypropylene
SPVV.10003	ISO 10	Polypropylene
SPVV.13003	ISO 12.5	Polypropylene
SPVV.20003	ISO 20	Polypropylene
SPVV.25003	ISO 25	Polypropylene
SPVV.30003	ISO 31.5	Polypropylene
SPVV.10203	ISO 10	Aluminium
SPVV.13203	ISO 12.5	Aluminium
SPVV.20203	ISO 20	Aluminium
SPVV.25203	ISO 25	Aluminium
SPVV.30203	ISO 31.5	Aluminium

Tech Sheet 20487

Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

PCJ5 Series, Ultra High Pressure Couplings

DNP standard, 15,000 psi/1,000 bar working pressure, high resistance steel, locking radial balls. Tested 100% with helium at low and high pressure. PCJ5 series is ideal for high pressure tools and torque equipment.

Occlusion: Poppet
Locking: Radial balls
Material: High resistance steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT

Standard Seals: Special compound
Safety Factor: 1:2,5
Test: with helium, 100% at low and high pressure
Connection Under Pressure: Not allowed

Working Temperature: -35°C to +130°C
Maximum Working Pressure: 1000 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PCJ5.0606.002	1/4"	6.3	1000
PCJ5.0610.002	3/8"	6.3	1000
Tech Sheet 20488			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PCJ5.0606.003	1/4"	6.3	1000
PCJ5.0610.003	3/8"	6.3	1000
Tech Sheet 20488			

Coupling, NPT

0457	Thread	ISO	Max Pressure Bar
PCJ5.0606.012	1/4"	6.3	1000
PCJ5.0610.012	3/8"	6.3	1000
Tech Sheet 20488			

Plug, NPT

0457	Thread	ISO	Max Pressure Bar
PCJ5.0606.013	1/4"	6.3	1000
PCJ5.0610.013	3/8"	6.3	1000
Tech Sheet 20488			

PCJ5 Protection Caps & Plugs



Plug for Coupling

0457	To Suit	Material
SPCJ.06002	ISO 6.3	PVC
Tech Sheet 20488		



Cap For Plug

0457	To Suit	Material
SPCJ.06003	ISO 6.3	PVC
Tech Sheet 20488		

PCJ6 Series, Ultra High Pressure Couplings

DNP standard, 21,780 psi/1,500 bar working pressure, high resistance steel, locking radial balls. Tested 100% with helium at low and high pressure. PCJ6 series is ideal for high pressure tools and torque equipment.

Occlusion: Poppet
Locking: Radial balls
Material: High resistance steel
Finishing: Zn-Fe (Cr III)

Available Threads: BSP, NPT
Standard Seals: Special compound
Safety Factor: 1:2,5
Test: with helium, 100% at low and high pressure
Connection Under Pressure: Not allowed

Working Temperature: -35°C to +130°C
Maximum Working Pressure: 1500 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PCJ6.0606.002	1/4"	6.3	1500
Tech Sheet 20489			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PCJ6.0606.003	1/4"	6.3	1500
Tech Sheet 20489			

Coupling, NPT

0457	Thread	ISO	Max Pressure Bar
PCJ6.0606.012	1/4"	6.3	1500
Tech Sheet 20489			

Plug, NPT

0457	Thread	ISO	Max Pressure Bar
PCJ6.0606.013	1/4"	6.3	1500
Tech Sheet 20489			

PCJ6 Protection Caps & Plugs



Plug for Coupling

0457	To Suit	Material
SPCJ.06042	ISO 6.3	PVC
Tech Sheet 20489		



Cap For Plug

0457	To Suit	Material
SPCJ.06043	ISO 6.3	PVC
Tech Sheet 20489		

Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

PVS Series, ISO 14540 Screw Couplings

Standard: ISO 14540
Occlusion: Ball
Locking: Screw
Material: Steel
Finishing: Zn-Fe (Cr III)
Threads: BSP, NPT
Standard Seals: Nitrile

Optional Seals: Viton, EPDM
Connection Under Pressure: Allowed (both male or female side)
Maximum Residual Pressure: 100 bar

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 700 bar



Coupling, NPT

0457	Thread	ISO	Max Pressure Bar
PVS3.0606.022	1/4"	6.3	700
PVS3.1006.022	1/4"	10	700
PVS3.1010.022	3/8"	10	700
Tech Sheet 20490			



Plug, NPT

0457	Thread	ISO	Max Pressure Bar
PVS1.0606.013	1/4"	6.3	700
PVS1.1006.013	1/4"	10	700
PVS1.1010.013	3/8"	10	700
Tech Sheet 20490			

ISO 14540 Protection Caps & Plugs

Cap for Plug



Plug for Coupling



Plug for Coupling

0457	To Suit	Material
SPVS.06100	ISO 6.3	Steel
SPVS.10100 C	ISO 10	Steel
Tech Sheet 20490		

Cap for Plug

0457	To Suit	Material
SPVS.06101	ISO 6.3	Steel
SPVS.10103 C	ISO 10	Steel
Tech Sheet 20490		

PFT1 Series, ISO 5676 Brake Couplings

Standard: ISO 5676
Occlusion: Flat face
Locking: Radial balls
Material: Steel
Finishing: Zn-Fe (Cr III)
Threads: BSP, SAE, metric

Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: not allowed

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 150 bar



Coupling, Female Thread

0457	Thread	ISO	Max Pressure Bar
PFT1.1310.002	3/8"	12.5	150
PFT1.1313.002	1/2"	12.5	150
PFT1.1318.102	M18 x 1.5	12.5	150
Tech Sheet 20491			



Plug, Male Thread

0457	Thread	ISO	Max Pressure Bar
PFT3.1313.213	1/2"	12.5	150
Tech Sheet 20491			

Plug, Male Thread Bulkhead

0457	Thread	ISO	Max Pressure Bar
PFT3.1318.503	M18 x 1.5	12.5	150
PFT3.1322.503	M22 x 1.5	12.5	150
Tech Sheet 20491			

For **RSB Hydraulic Tube Clamps** see pages **184-200**



Fluid-Air Components Ltd

HYDRAULIC QUICK RELEASE COUPLINGS

VFF1 Series, Wing Nut Screw Couplings

Interchangeability: Snap-Tite 78
Occlusion: Flat face
Locking: Screw
Material: Brass and steel
Steel Finishing: Zn-Fe (Cr III)
Threads: NPT
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not suggested

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 210 bar



Coupling, NPT

0457	Thread	ISO	Max Pressure Bar
VFF1.2013.012	1/2"	19	210
VFF1.2019.012	3/4"	19	210
VFF1.2525.012	1"	25	210
VFF1.3031.012	1.1/4"	31.5	190
VFF1.3939.012	1.1/2"	40	170
Tech Sheet 20492			



Plug, NPT

0457	Thread	ISO	Max Pressure Bar
VFF1.2013.013	1/2"	19	210
VFF1.2019.013	3/4"	19	210
VFF1.2525.013	1"	25	210
VFF1.3031.013	1.1/4"	31.5	190
VFF1.3939.013	1.1/2"	40	170
Tech Sheet 20492			

VFH1 Series, Wing Nut Screw Couplings

Wing style screw to connect, 5,000 psi/350 bar working pressure, heavy-duty design, high flow rate, heavy-duty acme threads. VFH1 series has a universal design that can be used in any industry, used frequently in oil field applications, applications needing high working pressures and high flow rates, oil field services such as coiled tubin units, snubbing units, power swivels and much more.

Interchangeability: Snap-Tite 75
Occlusion: Poppet
Locking: Screw
Material: Steel
Steel Finishing: Zn-Fe (Cr III)
Available Threads: NPT
Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Allowed (both male or female side)
Maximum Residual Pressure: 100 bar

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 350 bar



Coupling, NPT

0457	Thread	ISO	Max Pressure Bar
VFH1.2019.012	3/4"	19	350
VFH1.2525.012	1"	25	350
VFH1.3031.012	1.1/4"	31.5	350
VFH1.3939.012	1.1/2"	40	350
VFH1.5051.012	2"	50	350
Tech Sheet 20493			



Plug, NPT

0457	Thread	ISO	Max Pressure Bar
VFH1.2019.013	3/4"	19	350
VFH1.2525.013	1"	25	350
VFH1.3031.013	1.1/4"	31.5	350
VFH1.3939.013	1.1/2"	40	350
VFH1.5051.013	2"	50	350
Tech Sheet 20493			

PVE1 Series, Screw Couplings

Interchange: Faster CVE
Occlusion: Poppet
Locking: Screw
Material: Steel
Finishing: Zn-Fe (Cr III)
Threads: BSP
Standard Seals: Nitrile
Optional Seals: Viton, EPDM and more
Connection Under Pressure: Not suggested

Working Temperature: -25°C to +100°C

Maximum Working Pressure: 350 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PVE1.2019.002	3/4"	19	350
PVE1.2525.002	1"	25	350
Tech Sheet 68223			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PVE1.2019.003	3/4"	19	350
PVE1.2525.003	1"	25	350
Tech Sheet 68223			

ISO 19 Protection Caps & Plugs



Female Dust Plug

0457	To Suit	Material
SPVE.20202	ISO 19	Steel
SPVE.25202	ISO 25	Steel
Tech Sheet 68223		



Male Dust Cap

0457	To Suit	Material
SPVE.20203	ISO 19	Steel
SPVE.25203	ISO 25	Steel
Tech Sheet 68223		

Fluid-Air Components Ltd

Products available...

Solenoid Operated Directional Valves

See section 1, pages 209-219




Vane & Piston Pumps

See section 1, pages 221-225



Waltech Component Parts

See section 1, pages 115-137



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC COUPLINGS

6600 Series, ISO A Profil

Working Temperature:
-40°C to +110°C

- Nitrile Seals as Standard

Other seals available on request.



Female Coupling, BSPP

0398	Thread	Max Pressure Bar
6603-4-4	1/4"	350
6603-6-6	3/8"	280
6603-8-10	1/2"	280
6603-12-12	3/4"	280
6603-16-16	1"	280
Tech Sheet 10676		

Female Plug, BSPP

0398	Thread	Max Pressure Bar
6605-4-4	1/4"	350
6605-6-6	3/8"	280
6605-8-10	1/2"	280
6605-12-12	3/4"	280
6605-16-16	1"	280
Tech Sheet 10676		

Colour may vary



Plug for Coupling

0398	To Suit
6659-6PL	3/8"
6659-8PL	1/2"
6659-12PL	3/4"
6659-16PL	1"
Tech Sheet 10676	

Colour may vary



Cap for Plug

0398	To Suit
6657-6PL	3/8"
6657-8PL	1/2"
6657-12PL	3/4"
6657-16PL	1"
Tech Sheet 10676	

2000 Series, ISO A Profil

Working Temperature:
-25°C to +110°C


Colour may vary



Dust Protection

0398	Body	To Suit
5025-3PR	3/8"	Coupling
5029-3PR	3/8"	Plug
5205-4M	1/2"	Coupling
5209-4M	1/2"	Plug
Tech Sheet 10677		

For **Parker Hydraulic Filtration** see page **247**



Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

60 Series, ISO B Profil

Working Temperature:
-40°C to +110°C

- Nitrile Seals as Standard

Other seals available on request.



Female Coupling, Steel, BSPP

0398	Thread	Max Pressure Bar
H1-62-BSPP	1/8"	350
H2-62-BSPP	1/4"	350
H3-62-BSPP	3/8"	280
H4-62-BSPP	1/2"	280
H6-62-BSPP	3/4"	175
H8-62-BSPP	1"	140
Tech Sheet 10678		

Female Coupling, Brass, BSPP

0398	Thread	Max Pressure Bar
BH1-60-BSPP	1/8"	210
BH2-60-BSPP	1/4"	255
BH3-60-BSPP	3/8"	185
BH4-60-BSPP	1/2"	240
BH6-60-BSPP	3/4"	150
BH8-60-BSPP	1"	105
Tech Sheet 10678		

Female Coupling, 303 Stainless Steel, BSPP

0398	Thread	Max Pressure Bar
SH2-62-BSPP	1/4"	350
SH3-62-BSPP	3/8"	350
SH4-62-BSPP	1/2"	350
SH6-62-BSPP	3/4"	210
SH8-62-BSPP	1"	210
Tech Sheet 10678		

Female Coupling, Brass, NPT

0398	Thread	Max Pressure Bar
BH1-60	1/8"	210
BH2-60	1/4"	255
BH3-60	3/8"	185
BH4-60	1/2"	240
BH6-60	3/4"	150
BH8-60	1"	105
Tech Sheet 10678		

Female Coupling, 303 Stainless Steel, NPT

0398	Thread	Max Pressure Bar
SH2-62	1/4"	350
SH3-62	3/8"	350
SH4-62	1/2"	350
SH6-62	3/4"	210
SH8-62	1"	210
Tech Sheet 10678		

Female Plug, Steel, BSPP

0398	Thread	Max Pressure Bar
H1-63-BSPP	1/8"	350
H2-63-BSPP	1/4"	350
H3-63-BSPP	3/8"	280
H4-63-BSPP	1/2"	280
H6-63-BSPP	3/4"	175
H8-63-BSPP	1"	140
Tech Sheet 10678		

Female Plug, Brass, BSPP

0398	Thread	Max Pressure Bar
BH1-61-BSPP	1/8"	210
BH2-61-BSPP	1/4"	255
BH3-61-BSPP	3/8"	185
BH4-61-BSPP	1/2"	240
BH6-61-BSPP	3/4"	150
BH8-61-BSPP	1"	105
Tech Sheet 10678		

Female Plug, 303 Stainless Steel, BSPP

0398	Thread	Max Pressure Bar
SH2-63-BSPP	1/4"	350
SH3-63-BSPP	3/8"	350
SH4-63-BSPP	1/2"	350
SH6-63-BSPP	3/4"	210
SH8-63-BSPP	1"	210
Tech Sheet 10678		

Female Plug, Brass, NPT

0398	Thread	Max Pressure Bar
BH1-61	1/8"	210
BH2-61	1/4"	255
BH3-61	3/8"	185
BH4-61	1/2"	240
BH6-61	3/4"	150
BH8-61	1"	105
Tech Sheet 10678		

Female Plug, 303 Stainless Steel, NPT

0398	Thread	Max Pressure Bar
SH2-63	1/4"	350
SH3-63	3/8"	350
SH4-63	1/2"	350
SH6-63	3/4"	210
SH8-63	1"	210
Tech Sheet 10678		



Plug for Coupling

0398	To Suit	Material
H1-65	1/8"	Aluminium
H1-65M	1/8"	Rubber
H2-65	1/4"	Aluminium
H2-65M	1/4"	Rubber
H3-65	3/8"	Aluminium
H3-65M	3/8"	Rubber
H4-65	1/2"	Aluminium
H4-65M	1/2"	Rubber
H6-65	3/4"	Aluminium
H6-65M	3/4"	Rubber
H8-65	1"	Aluminium
H8-65M	1"	Rubber
Tech Sheet 10678		



Cap for Plug

0398	To Suit	Material
H1-66	1/8"	Aluminium
H1-66M	1/8"	Rubber
H2-66	1/4"	Aluminium
H2-66M	1/4"	Rubber
H3-66	3/8"	Aluminium
H3-66M	3/8"	Rubber
H4-66	1/2"	Aluminium
H4-66M	1/2"	Rubber
H6-66	3/4"	Aluminium
H6-66M	3/4"	Rubber
H8-66	1"	Aluminium
H8-66M	1"	Rubber
Tech Sheet 10678		

Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

QHPA Series

Working Temperature:
-25°C to +110°C

- Nitrile Seals as Standard

Other seals available on request.



Male Coupling, DIN 2353 Thread

0398	Thread	Size	Max Pressure Bar	Body
QHPA53-D6X2-C	M14 x 1.5	8L	450	3/8"
QHPA53-D6X3-C	M14 x 1.5	10L	450	3/8"
QHPA53-D7X3-C	M14 x 1.5	10S	450	3/8"
QHPA53-D7X4-C	M14 x 1.5	12S	450	3/8"
QHPA54-D6X4-C	M14 x 1.5	12L	400	1/2"
QHPA54-D6X5-C	M14 x 1.5	15L	400	1/2"
QHPA54-D7X5-C	M14 x 1.5	14S	400	1/2"
QHPA54-D7X6-C	M14 x 1.5	16S	400	1/2"
QHPA56-D6X6-C	M14 x 1.5	18L	370	3/4"
QHPA56-D6X7-C	M14 x 1.5	22L	370	3/4"
QHPA56-D7X7-C	M14 x 1.5	20S	370	3/4"
Tech Sheet 10679				

Male Coupling, DIN 3852, BSPP

0398	Thread	Max Pressure Bar	Body
QHPA53-F4B3-C	3/8"	450	3/8"
QHPA54-F4B4-C	1/2"	400	1/2"
Tech Sheet 10679			

Male Plug, DIN 2353 Thread

0398	Thread	Size	Max Pressure Bar	Body
QHPA13-D6X2-C	M14 x 1.5	8L	450	3/8"
QHPA13-D6X3-C	M14 x 1.5	10L	450	3/8"
QHPA13-D7X3-C	M14 x 1.5	10S	450	3/8"
QHPA13-D7X4-C	M14 x 1.5	12S	450	3/8"
QHPA14-D6X4-C	M14 x 1.5	12L	400	1/2"
QHPA14-D7X5-C	M14 x 1.5	14S	400	1/2"
QHPA14-D7X6-C	M14 x 1.5	16S	400	1/2"
QHPA16-D6X6-C	M14 x 1.5	18L	370	3/4"
QHPA16-D6X7-C	M14 x 1.5	22L	370	3/4"
QHPA16-D7X7-C	M14 x 1.5	20S	370	3/4"
Tech Sheet 10679				

Male Plug, DIN 3852, BSPP

0398	Thread	Max Pressure Bar	Body
QHPA13-F4B3-C	3/8"	450	3/8"
QHPA14-F4B4-C	1/2"	400	1/2"
Tech Sheet 10679			

3000 Series

Working Temperature:
-25°C to +110°C

Maximum Working Pressure:
700 bar



Male Coupling, NPT

0398	Thread
3050-2	1/4"
3050-3	3/8"
Tech Sheet 10680	

Female Plug, NPT

0398	Thread
3010-2	1/4"
3010-3	3/8"
Tech Sheet 10680	



Dust Protection

0398	Body	To Suit
3005-2	1/4"	Coupling
3009-2	1/4"	Plug
3005-3	3/8"	Coupling
3009-3	3/8"	Plug
Tech Sheet 10680		

FF2500 Series

Working Temperature:
-30°C to +100°C

Maximum Working Pressure:
800 bar



Female Coupling, BSPP

0398	Thread
FF2510	1/4"
Tech Sheet 10681	

Female Plug, BSPP

0398	Thread
FF2520	1/4"
Tech Sheet 10681	

Colour may vary



Dust Protection

0398	Body	To Suit
FF2516	1/4"	Coupling
FF2526	1/4"	Plug
Tech Sheet 10681		

For **Hydraulic Seals** see pages **109-112**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HYDRAULIC COUPLINGS

TDG Swivel Joints

Description: TDG swivel joints can be used in hydraulic systems where a rotating connection is required, for example in add-on units with rotational movements of up to 360°. TDG Swivel joints minimise the extreme wear occurring in the hoses of the hydraulic system.

A patented Pressure Relief Unit guarantees a long service life and smooth running even in the event of pressure hammers.

Standard Version: Body: Brass, Nitrile Seal.

Advantages: The housing is made of brass the rotating shaft is made so surface-treated steel or stainless steel. Sturdy construction with two needle roller bearings and an axis sliding bearing, adapted for combination with standardised hydraulic components. Has a maximum rotating speed 60 RPM.

Applications: Elevating mechanism, building machinery, materials handling technology and industrial plants.



DN6 Female Thread, BSPP

0071	Thread	Thread	Hex Size mm	Max Pressure Bar
TE-250	1/4"	3/8"	22	250
Tech Sheet 10009				



DN11 Female Thread, BSPP

0071	Thread	Thread	Hex Size mm	Max Pressure Bar
TE-500	1/2"	3/4"	32	250
Tech Sheet 10009				



DN11 Male/Female Thread, BSPP

0071	Thread	Thread	Hex Size mm	Max Pressure Bar
TE-500 B	1/2"	1/2"	32	250
Tech Sheet 10009				




DN17 Female Thread, BSPP

0071	Thread	Thread	Hex Size mm	Max Pressure Bar
TE-750	3/4"	1"	40	250
TE-750 RF	3/4"	1"	40	250
TE-1000	1"	1.1/4"	50	200
TE-1000 RF	1"	1.1/4"	50	200
Tech Sheet 10009				

TFF5000/TFF7500/TFF10000 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Static Working Pressure:
Safety Factor 4:1





TFF5000 Series Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-TFF5010	1/2"	400	Nitrile	With valve
Tech Sheet 2000				

TFF5000 Series Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-TFF5020	1/2"	400	Nitrile	With valve
Tech Sheet 2000				

TFF7500 Series Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-TFF7510	3/4"	400	Nitrile	With valve
Tech Sheet 2000				

TFF7500 Series Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-TFF7520	3/4"	400	Nitrile	With valve
Tech Sheet 2000				

TFF10000 Plugs with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-TFF10021	1"	300	Nitrile	With valve
Tech Sheet 2000				

Fluid-Air Components Ltd


HYDRAULIC COUPLINGS

TIF2500/TIF3800/TIF5000 Series

Working Temperature:
-40°C to +100°C (Nitrile)

Maximum Static Working Pressure:
Safety Factor 4:1





TIF2500 Series Couplings, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF2510	1/4"	1/4"	315	Nitrile
Tech Sheet 2001				

TIF2500 Series Plug, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF2520	1/4"	1/4"	315	Nitrile
Tech Sheet 2001				

TIF3800 Series Couplings, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF3810	3/8"	3/8"	250	Nitrile
TE-TIF3810-50	1/2"	3/8"	250	Nitrile
Tech Sheet 2001				

TIF3800 Series Couplings with Pressure Eliminator, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF3811	3/8"	3/8"	250	Nitrile
Tech Sheet 2001				

TIF3800 Series Plugs, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF3820	3/8"	3/8"	250	Nitrile
TE-TIF3820-50	1/2"	3/8"	250	Nitrile
Tech Sheet 2001				

TIF3800 Series Plugs with Pressure Eliminator, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF3821	3/8"	3/8"	250	Nitrile
Tech Sheet 2001				

TIF5000 Series Couplings, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF5010	1/2"	1/2"	250	Nitrile
TE-TIF5010 75	3/4"	1/2"	250	Nitrile
Tech Sheet 2001				

TIF5000 Series Couplings with Pressure Eliminator, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF5011	1/2"	1/2"	250	Nitrile
Tech Sheet 2001				

TIF5000 Series Plugs, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF5020	1/2"	1/2"	250	Nitrile
TE-TIF5020 75	3/4"	1/2"	250	Nitrile
Tech Sheet 2001				


TIF5000 Series Plugs with Pressure Eliminator, BSPP

0071	Thread	Body	Max Pressure Bar	Seal
TE-TIF5021	1/2"	1/2"	250	Nitrile
Tech Sheet 2001				

T2300 Series

Temperature Range:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)
Depending on the medium









Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-2310	1/8"	200	Nitrile	With valve
TE-2310 UV	1/8"	200	Nitrile	No valve
TE-2310 V	1/8"	200	Viton	With valve
Tech Sheet 2003				



Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-2320	1/8"	200	Nitrile	With valve
TE-2320 UV	1/8"	200	-	No valve
TE-2320 V	1/8"	200	Viton	With valve
Tech Sheet 2003				

T2500 Series

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1



Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-2510	1/4"	450	Nitrile	With valve
TE-2510 UV	1/4"	450	Nitrile	No valve
TE-2510 V	1/4"	450	Viton	With valve
TE-2510 RV	1/4"	250	Viton	With valve
Tech Sheet 2004				



Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-2520	1/4"	450	Nitrile	With valve
TE-2520 UV	1/4"	450	-	No valve
TE-2520 V	1/4"	450	Viton	With valve
TE-2520 RV	1/4"	250	Viton	With valve
Tech Sheet 2004				

Dust Protection



Plug for Coupling

0071	To Suit
TE-TIF3816	Series TIF3800
TE-TIF10016	Series TIF10000
Tech Sheet 71769	



Cap for Plug

0071	To Suit
TE-TIF3826	Series TIF3800
TE-TIF10026	Series TIF10000
Tech Sheet 71769	

Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

T3800 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1





Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-3810	3/8"	350	Nitrile	With valve
TE-3810 H	3/8"	350	Nitrile	No valve
TE-3810 UV	3/8"	350	Nitrile	No valve
TE-3810 HV	3/8"	350	Viton	No valve
TE-3810 V	3/8"	350	Viton	With valve
TE-3810 RV	3/8"	300	Viton	With valve
Tech Sheet 2005				

Couplings with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-3811	3/8"	350	Nitrile	With valve
TE-3811 V	3/8"	350	Viton	With valve
Tech Sheet 2005				

Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-3820	3/8"	350	Nitrile	With valve
TE-3820 UV	3/8"	350	-	No valve
TE-3820 V	3/8"	350	Viton	With valve
TE-3820 RV	3/8"	300	Viton	With valve
TE-3820 RUV	3/8"	300	-	No valve
Tech Sheet 2005				

Plugs with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-3821	3/8"	350	Nitrile	With valve
TE-3821 V	3/8"	350	Viton	With valve
TE-3821 RV	3/8"	300	Viton	With valve
Tech Sheet 2005				

T5000 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1





Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-5010	1/2"	300	Nitrile	With valve
TE-5010 UV	1/2"	300	Nitrile	No valve
TE-5010 V	1/2"	300	Viton	With valve
TE-5010 RV	1/2"	300	Viton	With valve
Tech Sheet 2005				

Couplings with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-5011	1/2"	300	Nitrile	With valve
TE-5011 V	1/2"	300	Viton	With valve
TE-5011 RV	1/2"	300	Viton	With valve
Tech Sheet 2005				

Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-5020	1/2"	320	Nitrile	With valve
TE-5020 UV	1/2"	320	-	No valve
TE-5020 V	1/2"	320	Viton	With valve
TE-5020 RV	1/2"	300	Viton	With valve
Tech Sheet 2005				

Plugs with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-5021	1/2"	320	Nitrile	With valve
TE-5021 V	1/2"	320	Viton	With valve
TE-5021 RV	1/2"	300	Viton	With valve
Tech Sheet 2005				

TEMA Coupling Letter Key

NO Letter	=	Standard, Nitrile seals with valve
H	=	No valve and no locking sleeve, Nitrile seals
UV	=	Standard Nitrile seals, unvalved
HV	=	No valve and no locking sleeve, viton seals
V	=	With valve and viton seals
RV	=	Stainless steel body with valve and viton seals
RUV	=	Stainless steel body, unvalved with viton seals
VUV	=	Unvalved with viton seals
S	=	Super nipple, special steel alloy construction, high durability

Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

T7500 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1





Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-7510	3/4"	280	Nitrile	With valve
TE-7510 UV	3/4"	280	Nitrile	No valve
TE-7510 V	3/4"	280	Viton	With valve
TE-7510 RV	3/4"	250	Viton	With valve
TE-7510 VUV	3/4"	280	Viton	No valve
Tech Sheet 2006				

Couplings with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-7511	3/4"	280	Nitrile	With valve
TE-7511 V	3/4"	280	Viton	With valve
Tech Sheet 2006				

Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-7520	3/4"	300	Nitrile	With valve
TE-7520 UV	3/4"	300	-	No valve
TE-7520 V	3/4"	300	Viton	With valve
Tech Sheet 2006				

Plugs with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-7521	3/4"	300	Nitrile	With valve
TE-7521 V	3/4"	300	Viton	With valve
Tech Sheet 2006				

Super Plug to be Used for Very High Loads, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-7520 S	3/4"	300	Nitrile	With valve
Tech Sheet 2006				

T10000 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1





Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-10010	1"	250	Nitrile	With valve
TE-10010 V	1"	250	Viton	With valve
Tech Sheet 2006				

Couplings with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-10011	1"	250	Nitrile	With valve
Tech Sheet 2006				

Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-10020	1"	280	Nitrile	With valve
TE-10020 UV	1"	280	-	No valve
TE-10020 V	1"	280	Viton	With valve
TE-10020 RV	1"	250	Viton	With valve
Tech Sheet 2006				

Plugs with Pressure Eliminator, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-10021	1"	280	Nitrile	With valve
Tech Sheet 2006				

FT PRO®

Customers who bought from this page also purchased
Glycerine Gauges
see page **264**



Fluid-Air Components Ltd

HYDRAULIC COUPLINGS

T15000 Series

Working Temperature:
-40°C up to +100°C (Nitrile)
-25°C up to +200°C (Viton)

Maximum Working Pressure:
Maximum static working pressure with safety factor 4:1





Couplings, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-15010	1.1/2"	200	Nitrile	With valve
TE-15010 UV	1.1/2"	200	Nitrile	No valve
TE-15010 V	1.1/2"	200	Viton	With valve
TE-15010 VUV	1.1/2"	200	Viton	No valve
Tech Sheet 2007				



Plugs, BSPP

0071	Thread	Max Pressure Bar	Seal	Operation
TE-15020	1.1/2"	200	Nitrile	With valve
TE-15020 UV	1.1/2"	200	-	No valve
TE-15020 V	1.1/2"	200	Viton	With valve
Tech Sheet 2007				

High Pressure Series

The TEMA High Pressure 1000 couplings were specially developed for use in industrial machinery, salvage devices and testing equipment. The Series is galvanised and produced in steel. They are provided with safety locking and dust caps inclusive.



THP1000 Series Couplings, BSPP

0071	Thread	Hex Size mm	Max Pressure Bar	Length mm
THP10104132	1/4"	24	1000	59
THP10104172	3/8"	24	1000	59
Tech Sheet 10010				



THP1000 Series Plugs, BSPP

0071	Thread	Hex Size mm	Max Pressure Bar	Length mm
THP1020413	1/4"	22	1000	37
THP1020417	3/8"	24	1000	37
Tech Sheet 10010				

The TEMA High Pressure 1500 couplings were specially developed for use in bolt tensioning equipment. This series is produced in steel with the coupling body QPQ treated and black galvanised. They are provided with safety locking and dust caps inclusive.



THP1500 Series Couplings, BSPP

0071	Thread	Hex Size mm	Max Pressure Bar	Length mm
THP15104132	1/4"	24	1500	59
Tech Sheet 10010				



THP1500 Series Plugs, BSPP

0071	Thread	Hex Size mm	Max Pressure Bar	Length mm
THP1520413	1/4"	22	1500	38
Tech Sheet 10010				

Dust Protection Plugs



Plug

0071	To Suit	Type
TE-2516	Series T2500	B
TE-3816	Series T3800	B
TE-5016	Series T5000	B
TE-7516	Series T7500	B
TE-10016	Series T10000	B
THP16	High Pressure Series	C
Tech Sheet 71770		

Dust Protection Caps



Cap

0071	To Suit	Type
TE-125	Series T2300	C
TE-2526	Series T2500	B
TE-3826	Series T3800	B
TE-5026	Series T5000	B
TE-7526	Series T7500	B
TE-10026	Series T10000	B
Tech Sheet 71770		

Seal Kits



Nitrile & Viton

0071	To Suit	Material
TE-2500-PSN	Series T2500	Nitrile
TE-3800-PSN	Series T3800	Nitrile
TE-3800-PSV	Series T3800	Viton
TE-5000-PSN	Series T5000	Nitrile
TE-5000-PSV	Series T5000	Viton
TE-7500-PSN	Series T7500	Nitrile
TE-7500-PSV	Series T7500	Viton
TE-10000-PSN	Series T10000	Nitrile
TE-10000-PSV	Series T10000	Viton
Tech Sheet 71771		

Fluid-Air Components Ltd

SERIES 70KB

ULTRA-FLO »»


Description: The quick-connect-couplings series 71-76 are robust and simple models having best proven their quality for many years in many applications. Only couplings and plugs with the same size internal threads will match. These couplings are designed for manual operation, i.e. to couple the sleeve must be first pushed back

Advantages: The simple and robust design guarantees a maximum of safety.

Ideal for Applications: With liquids and in laboratory and food areas.

Technical Data: Only couplings and plugs of the same series will match.

Interchangeability:
Industrial interchange ISO 7241-1 Series B, BS 7198. Hansen 'HK'.



	RectuPom		Brass
Working Temperature	-20°C to +90°C		-20°C to +200°C
Working Pressures:	50°C (bar)	90°C (bar)	-20°C to +200°C (bar)
Series 71 1/8"	15	7.5	250
Series 72 1/4"	15	7.5	250
Series 73 3/8"	15	7.5	200
Series 74 1/2"	10	5	150
Series 75 3/4"	10	5	100
Series 76 1"	10	5	100

Couplings



RectuPom, BSPP

4605	Thread	Length mm
71KBIW10DPX	1/8"	49
72KBIW13DPX	1/4"	58
73KBIW17DPX	3/8"	64
74KBIW21DPX	1/2"	74
75KBIW26DPX	3/4"	96
76KBIW33DPX	1"	106
Tech Sheet 10011		



Brass, Viton Seals, BSPP

4605	Thread	Length mm
71KBIW10MVX	1/8"	49
72KBIW13MVX	1/4"	58
73KBIW17MVX	3/8"	64
74KBIW21MVX	1/2"	74
75KBIW26MVX	3/4"	96
76KBIW33MVX	1"	106
Tech Sheet 10011		

Plugs



RectuPom, BSPP


4605	Thread	Length mm
71SBIW10DPX	1/8"	30
72SBIW13DPX	1/4"	35
73SBIW17DPX	3/8"	39
74SBIW21DPX	1/2"	46
75SBIW26DPX	3/4"	60
Tech Sheet 10011		



Brass, Viton Seals, BSPP

4605	Thread	Length mm
71SBIW10MVX	1/8"	30
72SBIW13MVX	1/4"	35
73SBIW17MVX	3/8"	39
74SBIW21MVX	1/2"	46
75SBIW26MVX	3/4"	60
76SBIW33MVX	1"	65
Tech Sheet 10011		

Grade 316 available upon request



For **Series 70, Stainless Steel 303, Viton Seals, BSPP**
see page **320**

Fluid-Air Components Ltd

H SERIES

Steel Plated Couplings



BSPP, Valved

0067	Thread	Max Pressure Bar
VHC4-4RP	1/4"	450
VHC6-6RP	3/8"	310
VHC8-8RP	1/2"	280
VHC12-12RP	3/4"	245
VHC16-16RP	1"	140
VHC20-20RP	1.1/4"	125
Tech Sheet 1336		

BSPP, Unvalved

0067	Thread	Max Pressure Bar
PHC4-4RP	1/4"	760
PHC6-6RP	3/8"	760
PHC8-8RP	1/2"	760
PHC12-12RP	3/4"	625
PHC16-16RP	1"	415
PHC20-20RP	1.1/4"	345
Tech Sheet 1336		

Steel Plated Plugs



BSPP, Valved

0067	Thread
VHN4-4RP	1/4"
VHN6-6RP	3/8"
VHN8-8RP	1/2"
VHN12-12RP	3/4"
VHN16-16RP	1"
VHN20-20RP	1.1/4"
VHN24-24RP	1.1/2"
Tech Sheet 1336	

BSPP, Unvalved

0067	Thread
PHN4-4RP	1/4"
PHN6-6RP	3/8"
PHN8-8RP	1/2"
PHN12-12RP	3/4"
PHN16-16RP	1"
Tech Sheet 1336	

Brass Couplings



BSPP, Valved

0067	Thread	Max Pressure Bar
BVHC4-4RP	1/4"	155
BVHC6-6RP	3/8"	155
BVHC8-8RP	1/2"	140
BVHC12-12RP	3/4"	140
BVHC16-16RP	1"	125
BVHC20-20RP	1.1/4"	25
BVHC24-24RP	1.1/2"	25
BVHC32-32RP	2"	30
Tech Sheet 1336		

BSPP, Unvalved

0067	Thread	Max Pressure Bar
BPHC4-4RP	1/4"	280
BPHC6-6RP	3/8"	280
BPHC8-8RP	1/2"	280
BPHC12-12RP	3/4"	245
BPHC16-16RP	1"	210
BPHC24-24RP	1.1/2"	70
Tech Sheet 1336		

Brass Plugs




BSPP, Valved

0067	Thread
BVHN4-4RP	1/4"
BVHN6-6RP	3/8"
BVHN8-8RP	1/2"
BVHN12-12RP	3/4"
BVHN16-16RP	1"
BVHN20-20RP	1.1/4"
BVHN24-24RP	1.1/2"
BVHN32-32RP	2"
Tech Sheet 1336	

BSPP, Unvalved

0067	Thread
BPHN4-4RP	1/4"
BPHN6-6RP	3/8"
BPHN8-8RP	1/2"
BPHN12-12RP	3/4"
BPHN16-16RP	1"
BPHN32-32RP	2"
Tech Sheet 1336	

H Series Aluminium Dust Protection



Dust Plug

0067	To Suit
AMPH-8	1/2"
AMPH-16	1"
AMPH-20	1.1/4"
AMPH-24	1.1/2"
AMPH-32	2"
Tech Sheet 1336	

Dust Cap

0067	To Suit
ADCH-4	1/4"
ADCH-6	3/8"
ADCH-16	1"
ADCH-20	1.1/4"
ADCH-32	2"
Tech Sheet 1336	

H Series Plastic Dust Protection



Cap & Plug

0067	To Suit
PDCP-4	1/4"
PDCP-6	3/8"
Tech Sheet 1336	



For **H Series, 316 Stainless Steel Couplings and Plugs** see page **320**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 71

The Series 71 has been designed to eliminate fluid loss and air inclusion. The dirt tolerant, heavy-duty construction withstand abusive treatment.

Couplings

Flush Face/Dry Break Steel Valved, BSPP



0067	Thread	Max Pressure Bar
71-3C4-4RP	1/4"	690
71-3C6-6RP	3/8"	690
71-3C8-8RP	1/2"	690
71-3C12-12RP	3/4"	520
71-3C16-16RP	1"	520
Tech Sheet 612		

Plugs

Flush Face/Dry Break Steel Valved, BSPP



0067	Thread
71-3N4-4RP	1/4"
71-3N6-6RP	3/8"
71-3N8-8RP	1/2"
71-3N12-12RP	3/4"
71-3N16-16RP	1"
Tech Sheet 612	

Parker

For **Pneumatic Valves & Accessories** see page **564**



SERIES 75

Series 75 is designed and constructed for high pressure hydraulic service. Although these couplings are used in a broad variety of heavy-duty applications.

A primary usage is in oil fields and offshore drilling, cranes, power tongs and swivels, diving etc.

Thread to Connect Couplings

Steel Valved, BSPP



0067	Thread	Max Pressure Bar
75C12-12RP	3/4"	345
75C16-16RP	1"	345
75C20-20RP	1.1/4"	345
75C24-24RP	1.1/2"	345
Tech Sheet 615		

Thread to Connect Plugs

Steel Valved, BSPP



0067	Thread
75N12-12RP	3/4"
75N16-16RP	1"
75N20-20RP	1.1/4"
75N24-24RP	1.1/2"
Tech Sheet 615	

Metal Dust Plug & Dust Cap

Dust Plug



0067	To Suit
75MDP-12	3/4"
75MDP-16	1"
75MDP-20	1.1/4"
75MDP-24	1.1/2"
75MDP-32	2"
Tech Sheet 615	

Dust Cap



0067	To Suit
75MDC-12	3/4"
75MDC-16	1"
75MDC-20	1.1/4"
75MDC-24	1.1/2"
75MDC-32	2"
Tech Sheet 615	

FAC
Fluid-Air Components Ltd

SERIES 70KB

stainless steel

Parker

ULTRA-FLO »»


Description: The quick-connect-couplings Series 71-76 are robust and simple models having best proven their quality for many years in many applications. Only couplings and plugs with the same size internal threads will match. These couplings are designed for manual operation, i.e. to couple the sleeve must be first pushed back

Advantages: The simple and robust design guarantees a maximum of safety.

Ideal for Applications: With liquids and in laboratory and food areas.

Technical Data: Only couplings and plugs of the same series will match.

Interchangeability:
Industrial interchange ISO 7241-1 Series B, BS 7198. Hansen 'HK'.



	Stainless Steel 303	
Working Temperature	-20°C to +200°C	
Working Pressures:	**50°C (bar)**	200°C (bar)
Series 71 1/8"	250	190
Series 72 1/4"	250	190
Series 73 3/8"	250	190
Series 74 1/2"	250	190
Series 75 3/4"	160	120
Series 76 1"	100	75

Stainless Steel 303, Viton Seals, BSPP

4605	Thread	Length mm
71KBIW10RVX	1/8"	49
72KBIW13RVX	1/4"	58
Tech Sheet 10011		



Stainless Steel 303, Viton Seals, BSPP

4605	Thread	Length mm
71SBIW10RVX	1/8"	30
72SBIW13RVX	1/4"	35
Tech Sheet 10011		



H SERIES

stainless steel

Snap-tite

316 Stainless Steel Couplings

BSPP, Valved

0067	Thread	Max Pressure Bar
SVHC4-4RP	1/4"	345
SVHC6-6RP	3/8"	280
SVHC8-8RP	1/2"	260
SVHC12-12RP	3/4"	140
SVHC16-16RP	1"	140
SVHC24-24RP	1.1/2"	105
SVHC32-32RP	2"	35
Tech Sheet 1336		



BSPP, Unvalved

0067	Thread	Max Pressure Bar
SPHC4-4RP	1/4"	690
SPHC6-6RP	3/8"	555
SPHC8-8RP	1/2"	555
SPHC12-12RP	3/4"	485
Tech Sheet 1336		

316 Stainless Steel Plugs

BSPP, Valved

0067	Thread
SVHN4-4RP	1/4"
SVHN6-6RP	3/8"
SVHN8-8RP	1/2"
SVHN12-12RP	3/4"
SVHN16-16RP	1"
SVHN20-20RP	1.1/4"
SVHN24-24RP	1.1/2"
SVHN32-32RP	2"
Tech Sheet 1336	



BSPP, Unvalved

0067	Thread
SPHN4-4RP	1/4"
SPHN6-6RP	3/8"
SPHN8-8RP	1/2"
SPHN12-12RP	3/4"
SPHN16-16RP	1"
SPHN24-24RP	1.1/2"
SPHN32-32RP	2"
Tech Sheet 1336	

SERIES 71

stainless steel

Snap-tite

The Series 71 has been designed to eliminate fluid loss and air inclusion. The dirt tolerant, heavy-duty construction withstand abusive treatment.

Flush Face/Dry Break 316 Valved, BSPP

0067	Thread	Max Pressure Bar
S71-3C4-4RP	1/4"	345
S71-3C6-6RP	3/8"	345
S71-3C8-8RP	1/2"	345
S71-3C12-12RP	3/4"	345
S71-3C16-16RP	1"	280
Tech Sheet 612		



Flush Face/Dry Break 316 Valved, BSPP

0067	Thread
S71-3N4-4RP	1/4"
S71-3N6-6RP	3/8"
S71-3N8-8RP	1/2"
S71-3N12-12RP	3/4"
S71-3N16-16RP	1"
Tech Sheet 612	



FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 **Pneumatic Quick Release Couplings** 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 3

Pneumatic Quick Release Couplings

3 Pneumatic Quick Release Couplings 324-406

Fluid-Air Components Ltd


ef nkl i r oi r p c c c a c c

SECTION 3 Pneumatic QRCs

3.00 Pneumatic Quick Release Couplings

324-406

- Mini Couplings & Plugs
- High Flow Couplings & Plugs
- Heavy-duty Couplings & Plugs
- Twist Air Couplings & Plugs
- Small Couplings & Plugs
- Japanese Profile Couplings & Plugs
- Aro Profile Couplings & Plugs
- Self Venting Couplings & Plugs
- English Profile Couplings Plugs
- ISO 6150 'C' Profile Couplings & Plugs
- English Industrial Profile Couplings & Plugs
- International Profile Couplings & Plugs
- Worldwide Profile Couplings & Plugs
- Safety Locking Couplings & Plugs
- Colour Coded Couplings & Plugs
- Thermoplastic Couplings & Plugs
- Industrial Interchange High Flow Couplings & Plugs
- ISO 6150 B Couplings & Plugs
- European Profile Couplings & Plugs
- Self Venting Couplings & Plugs
- Stainless Steel Couplings & Plugs
- Parker Profile Couplings & Plugs
- Atlas Copco Profile Couplings & Plugs
- Low Pressure Fluid & Pneumatic Couplings & Plugs
- German Industrial Profile Couplings & Plugs
- Breathing Air Couplings & Plugs
- Schrader Couplings & Plugs
- Scandinavian Profile Couplings & Plugs
- Moldtite Couplings & Plugs
- Plastic Injection Moulding Couplings
- Acetal Resin Couplings & Plugs
- Air Line Couplings & Plugs
- Instantair Couplings & Plugs
- Swing Couplings & Hose Tails
- Straight-Through Couplings & Plugs
- Air Brake Components



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



Your Partner for Air & Other Fluids
Low Pressure Solutions

legris



RECTUS



Manufactured in Europe


Parker

ENGINEERING YOUR SUCCESS.

ENGINEERING YOUR SUCCESS.

FAC
Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

PLUG PROFILE



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

BE RANGES

BE-17 Couplings



Male Thread, BSPT

0531	Thread
B1704M	1/4"
B1706M	3/8"
B1708M	1/2"



Female Thread, BSPP

0531	Thread
B1704F	1/4"
B1706F	3/8"
B1708F	1/2"



Hose Tail

0531	Thread
B1704H	1/4" (6mm)
B1705H	5/16" (8mm)
B1706H	3/8" (10mm)
B1708H	1/2" (12mm)

BE-17 Plugs



Male Thread, BSPT

0531	Thread
B1702MP	1/8"
B1704MP	1/4"
B1706MP	3/8"
B1708MP	1/2"



Female Thread, BSPP

0531	Thread
B1702FP	1/8"
B1704FP	1/4"
B1706FP	3/8"



BE-17 Plugs, Hose Tail

0531	To Suit Hose ID
B1704HP	1/4" (6mm)
B1705HP	5/16" (8mm)
B1706HP	3/8" (10mm)
B1708HP	1/2" (12mm)

BE-19 Couplings



Male Thread, BSPT

0532	Thread
B1904M	1/4"
B1906M	3/8"
B1908M	1/2"



Female Thread, BSPP

0532	Thread
B1904F	1/4"
B1906F	3/8"
B1908F	1/2"



Hose Tail

0532	To Suit Hose ID
B1904H	1/4" (6mm)
B1905H	5/16" (8mm)
B1906H	3/8" (10mm)
B1908H	1/2" (12mm)

BE-19 Plugs



Male Thread, BSPT

0532	Thread
B1902MP	1/8"
B1904MP	1/4"
B1906MP	3/8"
B1908MP	1/2"



Female Thread, BSPP

0532	Thread
B1904FP	1/4"
B1906FP	3/8"
B1908FP	1/2"



Hose Tail

0532	To Suit Hose ID
B1904HP	1/4"
B1905HP	5/16"
B1906HP	3/8"
B1908HP	1/2"

Fluid-Air Components Ltd

BE RANGES

BE-21 Mini Couplings



Male Thread, BSPT

0533	Thread
B2102M	1/8"
B2104M	1/4"



Panel Mounting, Male Thread, BSPP

0533	Thread
B2102BH	1/8"
B2104BH	1/4"



Female Thread, BSPP

0533	Thread
B2102F	1/8"
B2104F	1/4"



Quick Fit Tube

0533	To Suit Tube mm
B2106Q	6 x 4
B2108Q	8 x 6



Quick Fit Panel Mounting

0533	To Suit Tube mm
B2106QBH	6 x 4
B2108QBH	8 x 6



BE-21 Mini Couplings, Hose Tail

0533	To Suit Hose ID
B2104H	6mm
B2105H	9mm
B2106H	3/8" (10mm)

BE-21 Mini Plugs



Male Thread, BSPP

0533	Thread
B2102MP	1/8"
B2104MP	1/4"



Female Thread, BSPP

0533	Thread
B2102FP	1/8"
B2104FP	1/4"



Quick Fit

0533	To Suit Tube mm
B2106QP	6 x 4
B2108QP	8 x 6



Hose Tail

0533	To Suit Hose ID
B2103HP	3/16" (5mm)
B2104HP	6mm
B2105HP	9mm

BE-23 ISO Couplings



Male Thread, BSPT

0534	Thread
B2304M	1/4"
B2306M	3/8"
B2308M	1/2"



Female Thread, BSPP

0534	Thread
B2304F	1/4"
B2306F	3/8"
B2308F	1/2"



Hose Tail

0534	To Suit Hose ID
B2305H	5/16"
B2306H	3/8"

BE-23 ISO Plugs



Male Thread, BSPT

0534	Thread
B2304MP	1/4"



Female Thread, BSPP

0534	Thread
B2304FP	1/4"
B2306FP	3/8"



Hose Tail

0534	To Suit Hose ID
B2304HP	1/4"
B2306HP	3/8"
B2308HP	1/2"



Safety, Male Thread, BSPT

0534	Thread
B2304MPS	1/4"

Fluid-Air Components Ltd

BE RANGES

BE-25B Brass Couplings



Male Thread, BSPT

0535	Thread
B25B04M	1/4"
B25B06M	3/8"
B25B08M	1/2"



Female Thread, BSPP

0535	Thread
B25B04F	1/4"
B25B06F	3/8"
B25B08F	1/2"



Hose Tail

0535	To Suit Hose ID
B25B05H	5/16" (8mm)
B25B06H	3/8" (10mm)
B25B08H	1/2" (13mm)

BE-25B Brass Plugs



Male Thread, BSPT

0535	Thread
B25B04MP	1/4"
B25B06MP	3/8"
B25B08MP	1/2"



Hose Tail

0535	To Suit Hose ID
B25B04HP	1/4" (6mm)
B25B05HP	5/16" (8mm)
B25B06HP	3/8" (10mm)
B25B08HP	1/2" (12mm)

BE-25 Couplings



Male Thread, BSPT

0535	Thread
B2504M	1/4"
B2506M	3/8"
B2508M	1/2"



Female Thread, BSPP

0535	Thread
B2504F	1/4"
B2506F	3/8"
B2508F	1/2"



Hose Tail

0535	To Suit Hose ID
B2504H	1/4" (6mm)
B2505H	5/16" (8mm)
B2506H	3/8" (10mm)
B2508H	1/2" (12mm)

BE-25 Plugs



Male Thread, BSPT

0535	Thread
B2502MP	1/8"
B2504MP	1/4"
B2506MP	3/8"
B2508MP	1/2"



Female Thread, BSPP

0535	Thread
B2502FP	1/8"
B2504FP	1/4"
B2506FP	3/8"
B2508FP	1/2"



Hose Tail

0535	To Suit Hose ID
B2504HP	1/4" (6mm)
B2505HP	5/16" (8mm)
B2506HP	3/8" (10mm)
B2508HP	1/2" (12mm)



Safety, Male Thread, BSPT

0535	Thread
B2506MPS	3/8"

Fluid-Air Components Ltd

BE RANGES

BE-27 High Flow Couplings



Male Thread, BSPT

0536	Thread
B2708M	1/2"



Female Thread, BSPP

0536	Thread
B2706F	3/8"
B2708F	1/2"



Hose Tail

0536	To Suit Hose ID
B2706H	3/8"
B2708H	1/2"

BE-27 High Flow Plugs



Male Thread, BSPT

0536	Thread
B2704MP	1/4"
B2708MP	1/2"



Female Thread, BSPP

0536	Thread
B2708FP	1/2"



Hose Tail

0536	To Suit Hose ID
B2706HP	3/8"
B2710HP	5/8"

BE-68 Heavy-duty Couplings



Male Thread, BSPP

0538	Thread
B6808M	1/2"
B6812M	3/4"



Female Thread, BSPP

0538	Thread
B6804F	1/4"
B6808F	1/2"
B6812F	3/4"



Hose Tail

0538	To Suit Hose ID
B6806H	3/8" (10mm)
B6808H	1/2" (12mm)
B6812H	3/4" (19mm)

BE-68 Heavy-duty Plugs



Male Thread, BSPT

0538	Thread
B6804MP	1/4"
B6806MP	3/8"
B6808MP	1/2"
B6812MP	3/4"



Female Thread, BSPP

0538	Thread
B6804FP	1/4"
B6806FP	3/8"
B6808FP	1/2"



Hose Tail

0538	To Suit Hose ID
B6806HP	3/8" (10mm)
B6808HP	1/2" (12mm)

Fluid-Air Components Ltd

TWIST-AIR COUPLINGS

Working Temperature:
-15°C to +80°C
Standard seal NBR

Maximum Static Working Pressure
Static and random rotation:
PB 17 bar (250 psi)

Single Shut Off



Profile

Triple Outlet Connector



3 x Coupling Outlets, 1 x 1/4" BSPP Inlet

9000
M3-TA

Under continuous rotation:
PB 10 bar (145 psi)
Interchangeability:
Twist air PCL series
Flow rate: 900 L/min
Material: Mild steel zinc plated
Application:
General purpose pneumatic twist coupling.

Twist-Air Socket Halves



Male Thread, BSPP

9000	Old Ref	Thread	Length mm
TAC14M	PT8825	1/4"	58
TAC38M	PT8827	3/8"	54



Female Thread, BSPP

9000	Old Ref	Thread	Length mm
TAC14F	PT8823	1/4"	55
TAC38F	PT8800	3/8"	58



Hose Tail

9000	Old Ref.	To Suit Hose ID	Length mm
TAC14HT	PT8800/SU4	1/4"	91
TAC516HT	PT8800/SU5	5/16"	94
TAC38HT	PT8800/SU6	3/8"	96

Twist-Air Plug Halves - Swivel



Male Thread, BSPP

9000	Old Ref	Thread	Length mm
TAPS14M	PT8836	1/4"	46
TAPS38M	PT8838	3/8"	50



Female Thread, BSPP

9000	Old Ref	Thread	Length mm
TAPS14F	PT8834	1/4"	50
TAPS38F	PT8804	3/8"	51



Hose Tail

9000	Old Ref.	To Suit Hose ID	Length mm
TAPS14HT	PT8804/SU4	1/4"	85
TAPS516HT	PT8804/SU5	5/16"	88
TAPS38HT	PT8804/SU6	3/8"	90

Twist-Air Plug Halves - Non-swivel



Male Thread, BSPP

9000	Old Ref	Thread	Length mm
TAP14M	PT8808	1/4"	42
TAP38M	PT8817	3/8"	41



Female Thread, BSPP

9000	Old Ref	Thread	Length mm
TAP14F	PT8806	1/4"	41
TAP38F	PT8802	3/8"	44



Hose Tail

9000	Old Ref.	To Suit Hose ID	Length mm
TAP14HT	PT8802/SU4	1/4"	77
TAP516HT	PT8802/SU5	5/16"	81
TAP38HT	PT8802/SU6	3/8"	83

Fluid-Air Components Ltd

SERIES 02 SMALL QUICK COUPLINGS

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Material:
Brass and NBR seal (standard series) coupling and plug.

Application:
Medical and dental equipment, robotics instrumentation, air brush systems and pneumatic systems.



Profile

Couplings



Male Thread, Metric

2010	Thread	Hex Size mm	Length mm
02KAAM03MPX	M3	6	19
Tech Sheet 10276			



Hose Tail

2010	To Suit Hose ID mm	Hex Size mm	Length mm
02KATF02MPX	2	6	21
Tech Sheet 10276			

Plugs



Male Thread, Metric

2010	Thread	Hex Size mm	Length mm
02SFAM03MXX	M3	6	11
Tech Sheet 10276			



Hose Tail

2010	To Suit Hose ID mm	Length mm
02SFTF03MXX	3	13
Tech Sheet 10276		

Other materials, seals and finishes available on request, please contact our technical department for further details.

FT PRO®

You might also need
FT Pro Micro One Touch + Plastic Push-in Fittings
see pages **787-791**



Fluid-Air Components Ltd

SERIES 13 JAPANESE PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
Rectus 03,
Nitto Kohki 200 (Japan)

Material:
Brass and NBR seal (standard series) coupling.

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPT

1310	Thread	Hex Size mm	Length mm
13KAAK13MPX	1/4"	22	49
13KAAK17MPX	3/8"	22	49
13KAAK21MPX	1/2"	22	53
Tech Sheet 501			



Female Thread, BSPP

1310	Thread	Hex Size mm	Length mm
13KAIW13MPX	1/4"	22	45
13KAIW17MPX	3/8"	22	45
13KAIW21MPX	1/2"	24	48
Tech Sheet 501			



Hose Tail

1310	To Suit Hose ID	Hex Size mm	Length mm
13KATF06MPX	6mm (1/4")	21	62
13KATF08MPX	8mm (5/16")	21	62
13KATF10MPX	10mm (3/8")	21	62
13KATF13MPX	13mm (1/2")	21	62
Tech Sheet 501			

Plugs



Male Thread, BSPT

1310	Thread	Hex Size mm	Length mm
13SFAK13SXN	1/4"	14	37
13SFAK17SXN	3/8"	17	37
13SFAK21SXN	1/2"	22	44
Tech Sheet 501			



Female Thread, BSPP

1310	Thread	Hex Size mm	Length mm
13SFIW13SXN	1/4"	17	33
13SFIW17SXN	3/8"	19	33
13SFIW21SXN	1/2"	24	36
Tech Sheet 501			



Hose Tail

1310	To Suit Hose ID	Length mm
13SFTF06SXN	6mm (1/4")	48
13SFTF08SXN	8mm (5/16")	48
13SFTF10SXN	10mm (3/8")	48
13SFTF13SXN	13mm (1/2")	48
Tech Sheet 501		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 14 ARO PROFILE

Working Temperature:
-20°C to +100°C
Standard Seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
Rectus 22, ARO 210, Parker 50, JWL 522, JWL 532.

Material:
Brass and NBR seal (standard series) coupling.

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPP

2210	Thread	Hex Size mm	Length mm
14KAAW13MPX	1/4"	22	43
14KAAW17MPX	3/8"	22	43
14KAAW21MPX	1/2"	22	46
Tech Sheet 502			



Female Thread, BSPP

2210	Thread	Hex Size mm	Length mm
14KAIW13MPX	1/4"	22	43
14KAIW17MPX	3/8"	22	43
14KAIW21MPX	1/2"	24	46
Tech Sheet 502			



Hose Tail

2210	To Suit Hose ID mm	Hex Size mm	Length mm
14KATF06MPX	6	21	60
14KATF08MPX	8	21	60
14KATF09MPX	9	21	60
14KATF10MPX	10	21	60
14KATF13MPX	13	21	60
Tech Sheet 502			

Plugs



Male Thread, BSPT

2210	Thread	Hex Size mm	Length mm
22SFAK13SXN	1/4"	14	41
22SFAK17SXN	3/8"	17	41
22SFAK21SXN	1/2"	22	46
Tech Sheet 30001			



Female Thread, BSPP

2210	Thread	Hex Size mm	Length mm
22SFIW13SXN	1/4"	17	35
22SFIW17SXN	3/8"	19	35
22SFIW21SXN	1/2"	24	38
Tech Sheet 30001			



Hose Tail

2210	To Suit Hose ID	Length mm
22SFTF06SXN	6	49
22SFTF08SXN	8	49
22SFTF10SXN	10	49
22SFTF13SXN	13	49
Tech Sheet 30001		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 14 SELF VENTING LOW PRESSURE

Working Temperature:
-20°C to +60°C

Maximum Static Working Pressure:
PB 12 bar (174 PSI)

Single Shut Off

Material:
Brass nickel plated, thermoplastic sleeve, NBR seal.

Application:
General purpose pneumatic coupling, self-venting on disconnection as per ISO 4414.



Profile

Couplings



Male Thread, BSPT

0194	Thread	Hex Size mm	Length mm
14KEAK13MPN	1/4"	22	58
14KEAK21MPN	1/2"	24	63



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
14KEIW13MPN	1/4"	22	57
14KEIW17MPN	3/8"	22	57
14KEIW21MPN	1/2"	24	60



Hose Tail

0194	To Suit Hose ID mm	Hex Size mm	Length mm
14KETF06MPN	6	22	71
14KETF08MPN	8	22	71
14KETF09MPN	9	22	71
14KETF10MPN	10	22	71
14KETF13MPN	13	22	71

Plugs



Male Thread, BSPT

2210	Thread	Hex Size mm	Length mm
22SFAK13SXN	1/4"	14	41
22SFAK17SXN	3/8"	17	41
22SFAK21SXN	1/2"	22	46
Tech Sheet 30001			



Female Thread, BSPP

2210	Thread	Hex Size mm	Length mm
22SFIW13SXN	1/4"	17	35
22SFIW17SXN	3/8"	19	35
22SFIW21SXN	1/2"	24	38
Tech Sheet 30001			



Hose Tail

2210	To Suit Hose ID	Length mm
22SFTF06SXN	6	49
22SFTF08SXN	8	49
22SFTF10SXN	10	49
22SFTF13SXN	13	49
Tech Sheet 30001		

Fluid-Air Components Ltd

SERIES 17 QUICK COUPLING ENGLISH PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

ULTRA-FLO

Interchangeability:
Standard Schrader series NW5

Flow Rate: 865 L/min

Material:
Steel nickel plated, Steel zinc plated, Brass nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, garages, workshops.



Profile

Couplings

Male Thread, BSPT



1710	Thread	Hex Size mm	Length mm
17KAAK13SPN	1/4"	19	63
17KAAK17SPN	3/8"	19	62
17KAAK21SPN	1/2"	22	63
Tech Sheet 503			

Female Thread, BSPP



1710	Thread	Hex Size mm	Length mm
17KAIW13SPN	1/4"	19	58
17KAIW17SPN	3/8"	19	57
17KAIW21SPN	1/2"	24	60
Tech Sheet 503			

Hose Tail



1710	To Suit Hose ID	Hex Size mm	Length mm
17KATF06SPN	6mm (1/4")	19	76
17KATF08SPN	8mm (5/16")	19	76
17KATF10SPN	10mm (3/8")	19	76
17KATF13SPN	13mm (1/2")	19	76
Tech Sheet 503			

Plugs

Male Thread, BSPT



1710	Thread	Hex Size mm	Length mm
17SFAK10SXN	1/8"	11	37
17SFAK13SXN	1/4"	14	42
17SFAK17SXN	3/8"	17	42
17SFAK21SXN	1/2"	21	43
Tech Sheet 503			

Female Thread, BSPP



1710	Thread	Hex Size mm	Length mm
17SFIW10SXN	1/8"	14	33
17SFIW13SXN	1/4"	17	36
17SFIW17SXN	3/8"	19	39
17SFIW21SXN	1/2"	24	41
Tech Sheet 503			

Hose Tail



1710	To Suit Hose ID	Length mm
17SFTF06SXN	6mm (1/4")	58
17SFTF08SXN	8mm (5/16")	52
17SFTF10SXN	10mm (3/8")	52
17SFTF13SXN	13mm (1/2")	52
Tech Sheet 503		

Y Connector

2 x Coupling Outlets, 1 x Plug Inlet



1710	Length mm
17Y	114
Tech Sheet 503	

Triple Outlet Connectors

3 x Coupling Outlets, 1 x 3/8" BSPP Inlet



1710	Length mm
17W	111
Tech Sheet 503	

Leader Hoses

A 'Leader Hose' is a length of flexible hose which should be fitted betwee an air tool and the connecting coupling. By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.

3/8" Bore Rubber-Tech Hose, Series 17 Plug x Male Thread, BSPT

1710	Thread	Length mm
LH17/13K	1/4"	381
LH17/17K	3/8"	381
LH17/21K	1/2"	381
Tech Sheet 503		



WARNING – Leader Hoses

The Health and Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug and coupling from the tool vibration".

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 18 QUICK COUPLING ISO 6150 'C' PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
ISO 6150 C, Staubli RBE06

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
Industrial pneumatic coupling, robust design.



Profile

Couplings



Male Thread, BSPT

0194	Thread	Hex Size mm	Length mm
18KAAK13MPN	1/4"	19	63
18KAAK17MPN	3/8"	19	62
18KAAK21MPN	1/2"	22	63
Tech Sheet 2098			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
18KAIW13MPN	1/4"	19	58
18KAIW17MPN	3/8"	19	57
18KAIW21MPN	1/2"	24	60
Tech Sheet 2098			



Hose Tail

0194	To Suit Hose ID mm	Hex Size mm	Length mm
18KATF06MPN	6	19	76
18KATF08MPN	8	19	76
Tech Sheet 2098			

Plugs



Male Thread, BSPT

0194	Thread	Length mm
18SFAK13SXN	1/4"	41
Tech Sheet 2098		



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
18SFIW13SXN	1/4"	19	43
18SFIW17SXN	3/8"	19	44
Tech Sheet 2098			



Hose Tail

0194	To Suit Hose ID mm	Length mm
18SFTF06SXN	6	56
18SFTF08SXN	8	56
18SFTF10SXN	10	56
Tech Sheet 2098		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 18 QUICK COUPLING ISO 6150 'C' PROFILE SELF VENTING LOW PRESSURE

Working Temperature:
-20°C to +60°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, self-venting on disconnection.



Profile

Couplings



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
18KEIW21SPN	1/2"	24	65
Tech Sheet 504			

Plugs



Male Thread, BSPT

0194	Thread	Length mm
18SFAK13SXN	1/4"	41
Tech Sheet 504		



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
18SFIW13SXN	1/4"	19	43
18SFIW17SXN	3/8"	19	44
Tech Sheet 504			



Hose Tail

0194	To Suit Hose ID mm	Length mm
18SFTF06SXN	6	56
18SFTF08SXN	8	56
18SFTF10SXN	10	56
Tech Sheet 504		

FT PRO®

You might also need
FT Pro Pneumatic Tube
see page **898**



Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 19 QUICK COUPLING ENGLISH INDUSTRIAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
Standard PCL series.

Material:
Steel nickel plated, Brass nickel plated,
NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, original PCL.



Profile

Couplings



Male Thread, BSPT

1910	Thread	Hex Size mm	Length mm
19KAAK13MPX	1/4"	19	63
19KAAK17MPX	3/8"	19	63
19KAAK21MPX	1/2"	22	68
Tech Sheet 505			



Female Thread, BSPP

1910	Thread	Hex Size mm	Length mm
19KAIW13MPX	1/4"	19	58
19KAIW17MPX	3/8"	19	58
19KAIW21MPX	1/2"	24	60
Tech Sheet 505			



Hose Tail

1910	To Suit Hose ID	Hex Size mm	Length mm
19KATF06MPX	6mm (1/4")	19	76
19KATF08MPX	8mm (5/16")	19	76
19KATF10MPX	10mm (3/8")	19	76
19KATF13MPX	13mm (1/2")	19	76
Tech Sheet 505			

Plugs



Male Thread, BSPT

1910	Thread	Hex Size mm	Length mm
19SFAK13SXN	1/4"	14	50
19SFAK17SXN	3/8"	17	50
19SFAK21SXN	1/2"	21	57
Tech Sheet 505			



Female Thread, BSPP

1910	Thread	Hex Size mm	Length mm
19SFIW13SXN	1/4"	17	46
19SFIW17SXN	3/8"	17	47
19SFIW21SXN	1/2"	19	47
Tech Sheet 505			



Hose Tail

1910	To Suit Hose ID	Length mm
19SFTF05SXN	5mm	60
19SFTF06SXN	6mm (1/4")	60
19SFTF08SXN	8mm (5/16")	60
19SFTF10SXN	10mm (3/8")	60
19SFTF13SXN	13mm (1/2")	60
Tech Sheet 505		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 19

Y Connector



2 x Coupling Outlets, 1 x Plug Inlet

1910	Length mm
19Y	117

Triple Outlet Connectors



3 x Coupling Outlets, 1 x 3/8" BSPP Inlet

1910	Length mm
19W	111



3 x Coupling Outlets, 1 x 1/4" BSPP Inlet

1910
M3-19

Free Angle Rotating Joint



Male Thread, BSPT


1910	Thread
19FAAK13	1/4"
19FAAK17	3/8"
19FAAK21	1/2"



Female Thread, BSPP

1910	Thread
19FAIW13	1/4"

Leader Hoses



3/8" Bore Rubber-Tech Hose, Series 19 Plug x Male Thread, BSPT

1910	Thread	Length mm
LH19/13K	1/4"	381
LH19/17K	3/8"	381
LH19/21K	1/2"	381
Tech Sheet 1337		

A 'Leader Hose' is a length of flexible hose which should be fitted between an air tool and the connecting coupling By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.

WARNING – Leader Hoses

The Health and Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug and coupling from the tool vibration".

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 20 QUICK COUPLING INTERNATIONAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
Rectus 91, Walther 06-003

Flow Rate:
165 L/min

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, medical, dental, robotics, instrumentation.



Profile

Couplings



Male Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20KAAM05MPN	M5	9	26
20KAAW10MPN	1/8"	11	28
Tech Sheet 506			



Female Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20KAIM05MPN	M5	9	26
20KAIW10MPN	1/8"	12	28
Tech Sheet 506			



Hose Tail

2010	To Suit Hose ID mm	Length mm
20KATF03MPN	3	35
20KATF04MPN	4	35
20KATF05MPN	5	35
Tech Sheet 506		



Quick Fit Tube Connection

2010	To Suit Tube mm	Hex Size mm	Length mm
20KAKO04MPN	3 x 4	9	34
20KAKO06MPN	4 x 6	9	34
Tech Sheet 506			



Panel Mount, Quick Fit Tube Connection

2010	To Suit Tube mm	Hex Size mm	Length mm
20KAKS04MPN	3 x 4	12	45
20KAKS06MPN	4 x 6	12	45
Tech Sheet 506			



Panel Mount, Standard Hose Tail

2010	To Suit Hose ID mm	Hex Size mm	Length mm
20SFTS03MXN	3	12	45
Tech Sheet 506			

Plugs



Male Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20SFAM05MXN	M5	7	18
20SFAW10MXN	1/8"	11	20
Tech Sheet 506			



Female Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20SFIM05MXN	M5	7	17
20SFIW10MXN	1/8"	12	19
Tech Sheet 506			



Hose Tail

2010	To Suit Hose ID mm	Length mm
20SFTF03MXN	3	24
20SFTF04MXN	4	24
20SFTF05MXN	5	24
Tech Sheet 506		



Quick Fit Tube Connection

2010	To Suit Tube mm	Hex Size mm	Length mm
20SFKO04MXN	3 x 4	7	25
20SFKO05MXN	3 x 5	7	25
Tech Sheet 506			



Panel Mount, Quick Fit Tube Connection

2010	To Suit Tube mm	Hex Size mm	Length mm
20SFKS06MXN	3 x 6	12	38
Tech Sheet 506			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 20 QUICK COUPLING INTERNATIONAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Double Shut Off

Material:
Brass, NBR seal
(standard series coupling).

Application:
General purpose pneumatic coupling, medical, dental, robotics, instrumentation.



Profile

Couplings



Male Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20KBAM05MPX	M5	9	26
20KBAW10MPX	1/8"	11	28
Tech Sheet 507			



Female Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20KBIM05MPX	M5	9	26
20KBIW10MPX	1/8"	12	28
Tech Sheet 507			



Quick Fit Tube Connection

2010	Thread	Hex Size mm	Length mm
20KBKO06MPX	4 x 6	9	34
Tech Sheet 507			



Hose Tail

2010	To Suit Hose ID mm	Hex Size mm	Length mm
20KBTF03MPX	3	11	35
20KBTF04MPX	4	11	35
Tech Sheet 507			

Plugs



Male Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20SBAM05MPX	M5	9	28
20SBAW10MPX	1/8"	11	30
Tech Sheet 507			



Female Thread, Metric & BSPP

2010	Thread	Hex Size mm	Length mm
20SBIM05MPX	M5	9	26
20SBIW10MPX	1/8"	12	30
Tech Sheet 507			



Quick Fit Tube Connection

2010	To Suit Tube mm	Hex Size mm	Length mm
20SBKO06MPX	4 x 6	9	30.5
Tech Sheet 507			



Hose Tail

2010	To Suit Hose ID mm	Hex Size mm	Length mm
20SBTF04MPX	4	8	36
Tech Sheet 507			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 QUICK COUPLING WORLDWIDE PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Interchangeability:
Rectus 90, Camozzi, EWO.

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, medical, dental, robotics, instrumentation.



Profile

Couplings



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KAAW10MPN	1/8"	14	36
21KAAW13MPN	1/4"	17	38
21KAAW17MPN	3/8"	19	38
Tech Sheet 508			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KAIW10MPN	1/8"	14	36
21KAIW13MPN	1/4"	17	38
21KAIW17MPN	3/8"	19	38
Tech Sheet 508			



Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21KATF04MPN	4mm	14	46
21KATF06MPN	6mm (1/4")	14	46
21KATF08MPN	8mm (5/16")	14	46
21KATF09MPN	9mm	14	46
21KATF10MPN	10mm (3/8")	14	46
Tech Sheet 508			



Panel Mount, Standard Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21KATS04MPN	4mm	14	60
21KATS06MPN	6mm (1/4")	17	60
21KATS08MPN	8mm (5/16")	17	60
Tech Sheet 508			



Quick Fit Tube Connection

2110	To Suit Tube mm	Hex Size mm	Length mm
21KAKO06MPN	4 x 6	14	42
21KAKO08MPN	6 x 8	14	42
Tech Sheet 508			



Panel Mount, Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KAAS13MPN	1/4"	17	43
Tech Sheet 508			



Panel Mount, Quick Fit Tube Connection

2110	To Suit Tube mm	Hex Size mm	Length mm
21KAKS06MPN	4 x 6	14	54
21KAKS08MPN	6 x 8	17	54
Tech Sheet 508			



Quick Fit Tube Connection with Spring Guard

2110	To Suit Tube mm	Hex Size mm	Length mm
21KAKK06MPN	4 x 6	14	125
21KAKK08MPN	6 x 8	14	130
Tech Sheet 508			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 QUICK COUPLING WORLDWIDE PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Plugs



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SFAW10MXN	1/8"	14	25
21SFAW13MXN	1/4"	17	28
21SFAW17MXN	3/8"	17	28
Tech Sheet 508			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SFIW10MXN	1/8"	14	25
21SFIW13MXN	1/4"	17	25
21SFIW17MXN	3/8"	19	26
Tech Sheet 508			



Hose Tail

2110	To Suit Hose ID	Length mm
21SFTF04MXN	4mm	32
21SFTF05MXN	5mm	32
21SFTF06MXN	6mm (1/4")	32
21SFTF08MXN	8mm (5/16")	32
21SFTF09MXN	9mm	33
21SFTF10MXN	10mm (3/8")	33
Tech Sheet 508		



Panel Mount, Standard Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21SFTS04MXN	4mm	14	50
21SFTS06MXN	6mm (1/4")	14	50
21SFTS09MXN	9mm	14	50
Tech Sheet 508			



Quick Fit Tube Connection

2110	To Suit Tube mm	Length mm
21SFKO06MXN	4 x 6	32
21SFKO08MXN	6 x 8	32
Tech Sheet 508		



Panel Mount, Quick Fit Tube Connection

2110	To Suit Tube mm	Hex Size mm	Length mm
21SFKS06MXN	4 x 6	14	44
21SFKS08MXN	6 x 8	17	44
Tech Sheet 508			




Quick Fit Tube Connection with Spring Guard

2110	To Suit Tube mm	Hex Size mm	Length mm
21SFKK06MXN	4 x 6	12	115
21SFKK08MXN	6 x 8	14	120
Tech Sheet 508			

FTPRO®

You might also need
Brass Quick-Fit Push-on Fittings
see pages **1156-1159**



Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 QUICK COUPLING WORLDWIDE PROFILE PUSH-IN

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 psi)

Single Shut Off

Flow Rate:
560 L/min

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
Usable for air, oil and water. Ideally suited where tubing is often changed.



Profile

Couplings



Push-in

2010	OD mm	Hex Size mm	Length mm
21KARP06MPN	6	14	43.5
21KARP08MPN	8	17	48
Tech Sheet 508			


Plugs



Push-in

2010	OD mm	Hex Size mm	Length mm
21SFRP06MPN	6	17	30.5
21SFRP08MPN	8	17	37
Tech Sheet 508			

You might also need
Parker Legris Pneumatic Tube
see page **908**



Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 QUICK COUPLING WORLDWIDE PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Flow Rate:
310 L/min

Material:
Brass, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, medical, dental, robotics, instrumentation.



Profile

Couplings



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KBAW10MPX	1/8"	14	36
21KBAW13MPX	1/4"	17	38
Tech Sheet 509			



Quick Fit Tube Connection

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKO06MPX	6 x 4	14	42
21KBKO08MPX	8 x 6	14	42
Tech Sheet 509			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KBIW10MPX	1/8"	14	36
21KBIW13MPX	1/4"	17	38
Tech Sheet 509			



Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21KBTF04MPX	4mm (1/8")	14	46
21KBTF06MPX	6mm (1/4")	14	46
21KBTF08MPX	8mm (5/16")	14	46
Tech Sheet 509			

Plugs



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SBAW10MPX	1/8"	14	40
Tech Sheet 509			



Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21SBTF08MPX	8mm (5/16")	14	50
Tech Sheet 509			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SBIW10MPX	1/8"	14	40
Tech Sheet 509			



Quick Fit Tube Connection

2110	To Suit Tube mm	Hex Size mm	Length mm
21SBKO06MPX	6 x 4	14	46
21SBKO08MPX	8 x 6	14	46
Tech Sheet 509			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 SAFETY QUICK COUPLING WORLDWIDE PROFILE SAFETY LOCKING

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus design

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
Air breathing systems, medical, laboratories, diving suits etc.



Profile

Couplings



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KSAW10MPN	1/8"	14	36
21KSAW13MPN	1/4"	17	38
Tech Sheet 10279			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21KSIW10MPN	1/8"	14	36
21KSIW13MPN	1/4"	17	38
Tech Sheet 10279			



Hose Tail

2110	To Suit Hose ID	Hex Size mm	Length mm
21KSTF06MPN	6mm (1/4")	14	46
21KSTF08MPN	8mm (5/16")	14	46
21KSTF10MPN	10mm (3/8")	14	46
Tech Sheet 10279			

Plugs



Male Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SSAW10MXN	1/8"	14	25
21SSAW13MXN	1/4"	17	28
Tech Sheet 10279			



Female Thread, BSPP

2110	Thread	Hex Size mm	Length mm
21SSIW10MXN	1/8"	14	25
21SSIW13MXN	1/4"	17	26
Tech Sheet 10279			



Hose Tail

2110	To Suit Hose ID	Length mm
21SSTF06MXN	6mm (1/4")	32
21SSTF08MXN	8mm (5/16")	32
21SSTF10MXN	10mm (3/8")	33
Tech Sheet 10279		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 CODED QUICK COUPLINGS

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus design

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
Non-interchangeable, each coupling and plug has an individual shape so they can only be connected to each other, colour coded, one hand operation.



Profile

Couplings



Male Thread, BSPP

2110	Colour	Thread	Length mm
21KAAW10MPN0	Green	1/8"	47
21KAAW10MPN3	Brown	1/8"	47
21KAAW10MPN6	Blue	1/8"	47
21KAAW10MPN8	Red	1/8"	47
21KAAW13MPN0	Green	1/4"	47
21KAAW13MPN3	Brown	1/4"	47
21KAAW13MPN6	Blue	1/4"	47
21KAAW13MPN8	Red	1/4"	47
Tech Sheet 510			



Female Thread, BSPP

2110	Colour	Thread	Length mm
21KAIW10MPN0	Green	1/8"	47
21KAIW10MPN6	Blue	1/8"	47
21KAIW10MPN8	Red	1/8"	47
21KAIW13MPN0	Green	1/4"	47
21KAIW13MPN6	Blue	1/4"	47
21KAIW13MPN8	Red	1/4"	47
Tech Sheet 510			



Hose Tail

2110	Colour	To Suit Hose ID mm	Length mm
21KATF10MPN8	Red	10	69
Tech Sheet 510			

Plugs




Male Thread, BSPP

2110	Colour	Thread	Length mm
21SFAW10MXN0	Green	1/8"	39.5
21SFAW10MXN3	Brown	1/8"	39.5
21SFAW10MXN6	Blue	1/8"	39.5
21SFAW10MXN8	Red	1/8"	39.5
21SFAW13MXN0	Green	1/4"	41.5
21SFAW13MXN3	Brown	1/4"	41.5
21SFAW13MXN6	Blue	1/4"	41.5
21SFAW13MXN8	Red	1/4"	41.5
Tech Sheet 510			



Female Thread, BSPP

2110	Colour	Thread	Length mm
21SFIW10MXN0	Green	1/8"	38.5
21SFIW10MXN3	Brown	1/8"	38.5
21SFIW10MXN6	Blue	1/8"	38.5
21SFIW10MXN8	Red	1/8"	38.5
21SFIW13MXN0	Green	1/4"	39
21SFIW13MXN3	Brown	1/4"	39
21SFIW13MXN6	Blue	1/4"	39
21SFIW13MXN8	Red	1/4"	39
Tech Sheet 510			



Hose Tail

2110	Colour	To Suit Hose ID mm	Length mm
21SFTF04MXN0	Green	4	47
21SFTF04MXN6	Blue	4	47
21SFTF06MXN8	Red	6	47
Tech Sheet 510			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 QUICK COUPLING WORLDWIDE PROFILE THERMOPLASTIC

Working Temperature:
Rectupom -20°C to +80°C
Rectuchem -20°C to +120°C

Working Pressure:
Rectupom 10 bar @ 20°C
Rectuchem 8 bar @ 20°C

Double Shut Off

Interchangeability:
Rectus design

Material:
RectuPom – thermoplastic POM Black
RectuChem – thermoplastic PVDF White

Application:
Suitable for liquids, gases, drinking water, laboratories, medical technology and food areas.



Profile

Couplings



Male Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21KBAW10DPX	1/8"	17	50
21KBAW13DPX	1/4"	17	52
Tech Sheet 10280			



Female Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21KBIW10DPX	1/8"	17	53
21KBIW13DPX	1/4"	17	53
Tech Sheet 10280			



Hose Tail, RectuPom

2110	To Suit Hose ID mm	Hex Size mm	Length mm
21KBTF04DPX	4	17	60
21KBTF06DPX	6	17	60
Tech Sheet 10280			



Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKO06DPX	4 x 6	17	56
Tech Sheet 10280			



Female Thread, BSPP, RectuChem

2110	Thread	Hex Size mm	Length mm
21KBIW10FVX	1/8"	17	53
Tech Sheet 10280			



Quick Fit Tube Connection, RectuChem

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKO06FVX	4 x 6	17	56
Tech Sheet 10280			



Panel Mount, Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKS06DPX	4 x 6	17	68
Tech Sheet 10280			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 21 THERMOPLASTIC QUICK COUPLING WORLDWIDE PROFILE

Plugs



Male Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21SFAW10DXX	1/8"	14	25
21SFAW13DXX	1/4"	17	28
Tech Sheet 10280			



Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21SFKO06DXX	4 x 6	14	32
Tech Sheet 10280			



Quick Fit Tube Connection, RectuChem

2110	To Suit Tube mm	Hex Size mm	Length mm
21SFKO08FXX	6 x 8	17	32
Tech Sheet 10280			



Female Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21SFIW13DXX	1/4"	17	25
Tech Sheet 10280			



Female Thread, BSPP, RectuChem

2110	Thread	Hex Size mm	Length mm
21SFIW13FXX	1/4"	17	26
Tech Sheet 10280			



Hose Tail, RectuPom

2110	To Suit Hose ID mm	Length mm
21SFTF06DXX	6	32
Tech Sheet 10280		



Panel Mount, Standard Hose Tail, RectuChem

2110	To Suit Hose ID mm	Hex Size mm	Length mm
21SFTS04FXX	4	14	50
Tech Sheet 10280			

Other materials, seals and finishes available on request, please contact our technical department for further details.

You might also need
Translucent Silicone & FEP Tubing
see page **909**



Fluid-Air Components Ltd

SERIES 21 THERMOPLASTIC QUICK COUPLING WORLDWIDE PROFILE

Plugs (with Valve)



Male Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21SBAW10DPX	1/8"	17	36
21SBAW13DPX	1/4"	17	38
Tech Sheet 10280			



Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21SBKO06DPX	4 x 6	17	42
Tech Sheet 10280			



Quick Fit Tube Connection, RectuChem

2110	To Suit Tube mm	Hex Size mm	Length mm
21SBKO08FVX	6 x 8	17	42
Tech Sheet 10280			



Female Thread, BSPP, RectuPom

2110	Thread	Hex Size mm	Length mm
21SBIW10DPX	1/8"	17	39
21SBIW13DPX	1/4"	17	41
Tech Sheet 10280			



Panel Mount, Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21SBKS06DPX	4 x 6	17	54
Tech Sheet 10280			

Sleeve Mounting for Front Panel Installation



Panel Mount, Quick Fit Tube Connection, RectuPom

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKE06DPX	4 x 6	17	56
Tech Sheet 10280			



Panel Mount, Quick Fit Tube Connection, RectuChem

2110	To Suit Tube mm	Hex Size mm	Length mm
21KBKE06FVX	4 x 6	17	56
Tech Sheet 10280			



Panel Mount, Standard Hose Tail, RectuPom

2110	To Suit Hose ID mm	Hex Size mm	Length mm
21KBTE04DPX	4	17	60
Tech Sheet 10280			

Other materials, seals and finishes available on request, please contact our technical department for further details.

FT PRO®



For **FT Pro Polypropylene Hose Tails & Adaptors** see page **1149**

Fluid-Air Components Ltd

SERIES 22 QUICK COUPLING ARO PROFILE

Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
35 bar

Single Shut Off

Interchangeability:
Rectus 14, Aro 210, Parker 50, Orion 44510, JWL 522 & JWL 532

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. Specially suited to use with gaseous media in industry. The steel sleeve counters oscillating forces



Profile

Couplings



Male Thread, BSPP

2210	Thread	Hex Size mm	Length mm
22KAAK13MPN	1/4"	19	61
22KAAK17MPN	3/8"	19	60
Tech Sheet 30001			



Female Thread, BSPP

2210	Thread	Hex Size mm	Length mm
22KAIW13MPN	1/4"	19	56
22KAIW21MPN	1/2"	24	58
Tech Sheet 30001			



Hose Tail

2210	To Suit Hose ID mm	Hex Size mm	Length mm
22KATF06MPN	6	19	74
22KATF08MPN	8	19	74
22KATF13MPN	13	19	74
Tech Sheet 30001			

Plugs



Male Thread, BSPT

2210	Thread	Hex Size mm	Length mm
22SFAK13SXN	1/4"	14	41
22SFAK17SXN	3/8"	17	41
22SFAK21SXN	1/2"	22	46
Tech Sheet 30001			



Female Thread, BSPP

2210	Thread	Hex Size mm	Length mm
22SFIW13SXN	1/4"	17	35
22SFIW17SXN	3/8"	19	35
22SFIW21SXN	1/2"	24	38
Tech Sheet 30001			



Hose Tail

2210	To Suit Hose ID	Length mm
22SFTF06SXN	6	49
22SFTF08SXN	8	49
22SFTF10SXN	10	49
22SFTF13SXN	13	49
Tech Sheet 30001		

Fluid-Air Components Ltd

SERIES 23 INDUSTRIAL INTERCHANGE HIGH FLOW QUICK CONNECT AIR COUPLINGS

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Norgren Dynaquip DC3, Hanson 3000, Parker, US C4109 1/4", ISO 6150

Flow Rate:
900 L/min

Material:
Brass nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPT

2310	Thread	Hex Size mm	Length mm
23KAAK13MPN	1/4"	19	60
23KAAK17MPN	3/8"	19	60
23KAAK21MPN	1/2"	22	61
Tech Sheet 511			



Female Thread, BSPP

2310	Thread	Hex Size mm	Length mm
23KAIW13MPN	1/4"	19	56
23KAIW17MPN	3/8"	19	55
23KAIW21MPN	1/2"	24	58
Tech Sheet 511			



Hose Tail

2310	To Suit Hose ID	Hex Size mm	Length mm
23KATF06MPN	6mm (1/4")	19	74
23KATF08MPN	8mm (5/16")	19	74
23KATF09MPN	9mm	19	74
23KATF10MPN	10mm (3/8")	19	74
23KATF13MPN	13mm (1/2")	19	74
Tech Sheet 511			

Plugs



Male Thread, BSPT

2310	Thread	Hex Size mm	Length mm
23SFAK10SXN	1/8"	13	39
23SFAK13SXN	1/4"	14	42
23SFAK17SXN	3/8"	17	42
23SFAK21SXN	1/2"	22	48
Tech Sheet 511			



Female Thread, BSPP

2310	Thread	Hex Size mm	Length mm
23SFIW10SXN	1/8"	14	36
23SFIW13SXN	1/4"	17	36
23SFIW17SXN	3/8"	19	36
23SFIW21SXN	1/2"	24	39
Tech Sheet 511			



Hose Tail

2310	To Suit Hose ID	Length mm
23SFTF06SXN	6mm (1/4")	51
23SFTF08SXN	8mm (5/16")	51
23SFTF09SXN	9mm	51
23SFTF10SXN	10mm (3/8")	51
23SFTF13SXN	13mm (1/2")	51
Tech Sheet 511		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 24 QUICK COUPLING ISO 6150 B PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Series 23, Norgren DC3, Hanson 3000.

Material:
Brass

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
24KAAW13MPX	1/4"	22	43
24KAAW17MPX	3/8"	22	43
24KAAW21MPX	1/2"	22	46
Tech Sheet 513			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
24KAIW13MPX	1/4"	22	43
24KAIW17MPX	3/8"	22	43
24KAIW21MPX	1/2"	22	46
Tech Sheet 513			



Hose Tail

0194	To Suit Hose ID	Hex Size mm	Length mm
24KATF06MPX	6mm (1/4")	21	60
24KATF08MPX	8mm (5/16")	21	60
24KATF10MPX	10mm (3/8")	21	60
24KATF13MPX	13mm (1/2")	21	60
Tech Sheet 513			

Plugs



Male Thread, BSPT

2310	Thread	Hex Size mm	Length mm
23SFAK10SXN	1/8"	13	39
23SFAK13SXN	1/4"	14	42
23SFAK17SXN	3/8"	17	42
23SFAK21SXN	1/2"	22	48
Tech Sheet 513			



Female Thread, BSPP

2310	Thread	Hex Size mm	Length mm
23SFIW10SXN	1/8"	14	36
23SFIW13SXN	1/4"	17	36
23SFIW17SXN	3/8"	19	36
23SFIW21SXN	1/2"	24	39
Tech Sheet 513			



Hose Tail

2310	To Suit Hose ID	Length mm
23SFTF06SXN	6mm (1/4")	51
23SFTF08SXN	8mm (5/16")	51
23SFTF09SXN	9mm	51
23SFTF10SXN	10mm (3/8")	51
23SFTF13SXN	13mm (1/2")	51
Tech Sheet 513		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 25 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus 26, 1600, 1625, JWL 520, 530.

Flow Rate:
1800 L/min

Material:
Brass nickel plated

Application:
General purpose pneumatic coupling
Euro standard design.

ULTRA-FLO »



Profile

Couplings



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25KAAK13MPN	1/4"	19	60
25KAAK17MPN	3/8"	19	60
25KAAK21MPN	1/2"	22	61
Tech Sheet 514			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KAIW13MPN	1/4"	19	56
25KAIW17MPN	3/8"	19	55
25KAIW21MPN	1/2"	24	58
Tech Sheet 514			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KATF06MPN	6mm (1/4")	19	74
25KATF08MPN	8mm (5/16")	19	74
25KATF09MPN	9mm	19	74
25KATF10MPN	10mm (3/8")	19	74
25KATF13MPN	13mm (1/2")	19	74
Tech Sheet 514			



Quick Fit Tube Connection

2510	To Suit Tube mm	Hex Size mm	Length mm
25KAKO08MPN	6 x 8	19	60
Tech Sheet 514			



Panel Mount, Standard Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KATS08MPN	8mm (5/16")	19	80
25KATS10MPN	10mm (3/8")	19	87
Tech Sheet 514			



Quick Fit Tube Connection with Spring Guard

2510	To Suit Tube mm	Hex Size mm	Length mm
25KAKK08MPN	6 x 8	19	144
25KAKK10MPN	8 x 10	19	155
Tech Sheet 514			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Interchangeability:
Rectus design

Material:
Steel zinc plated

Application:
General purpose pneumatic coupling

Plugs



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25SFAK10SXN	1/8"	13	33
25SFAK13SXN	1/4"	14	37
25SFAK17SXN	3/8"	17	37
25SFAK21SXN	1/2"	22	43
Tech Sheet 514			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SFIW10SXN	1/8"	14	30
25SFIW13SXN	1/4"	17	38.5
25SFIW17SXN	3/8"	19	39.5
25SFIW21SXN	1/2"	24	44
Tech Sheet 514			



Hose Tail

2510	To Suit Hose ID	Length mm
25SFTF06SXN	6mm (1/4")	48
25SFTF08SXN	8mm (5/16")	48
25SFTF09SXN	9mm	48
25SFTF10SXN	10mm (3/8")	48
25SFTF13SXN	13mm (1/2")	48
Tech Sheet 514		

Y Connector



2 x Coupling Outlets, 1 x Plug Inlet

2510	Length mm
25Y	114
Tech Sheet 514	

Triple Outlet Connectors



3 x Coupling Outlets, 1 x 3/8" BSPP Inlet

2510	Length mm
25W	119
Tech Sheet 514	



3 x Coupling Outlets, 1 x 1/4" BSPP Inlet

2510
M3-25
Tech Sheet 514

NUAIR



For **Compressors**
see page **1699-1703**

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 QUICK COUPLING EUROPEAN PROFILE

Free Angle Rotating Joint



Male Thread, BSPT, Steel Nickel Plated

2510	Thread
25FAAK13SPN	1/4"



Male Thread x Female Thread, BSPP, Steel Nickel Plated

2510	Thread
FA13A13ISPN	1/4"
FA17A17ISPN	3/8"

Leader Hoses

A 'Leader Hose' is a length of flexible hose which should be fitted between a air tool and the connecting coupling.
By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.



3/8" Bore Rubber-Tech Hose, Series 25 Plug x Male Thread, BSPT

2510	Thread	Length mm
LH25/13K	1/4"	381
LH25/17K	3/8"	381

WARNING – Leader Hoses

The Health and Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug and coupling from the tool vibration".

Flexible Connectors

This rotating joint, when installed between the airline and hand tool, reduces operator wrist and elbow strain.
It also acts as a universal joint and prevents kinks appearing in the airline.



Male Thread, BSP x Female Thread, BSPP

0560	Male Thread	Female Thread
FC04	1/4"	1/4"



Male Thread, BSPT x Female Thread, BSPP

0560	Male Thread	Female Thread
FE101	1/4"	1/4"

Recoil Eliminator (Anti-Whip)



Hose Tail, Steel Nickel Plated

2510	To Suit Hose ID	Hex Size mm	Length mm
25SRTF10SXN	10mm (3/8")	21	60

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Interchangeability:
Rectus design

Material:
Brass, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling, double shut off, Rectus Ultra-Flo valve.



Profile

Couplings



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25KBAK13BPX	1/4"	19	60
25KBAK17BPX	3/8"	19	59
25KBAK21BPX	1/2"	22	57.5
Tech Sheet 515			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KBIW13BPX	1/4"	19	56
25KBIW17BPX	3/8"	19	55
25KBIW21BPX	1/2"	24	58
Tech Sheet 515			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KBTF06BPX	6mm (1/4")	19	74
25KBTF08BPX	8mm (5/16")	19	74
25KBTF10BPX	10mm (3/8")	19	74
25KBTF13BPX	13mm (1/2")	19	74
Tech Sheet 515			

Plugs



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SBAW13MPX	1/4"	22	43
25SBAW17MPX	3/8"	22	43
25SBAW21MPX	1/2"	22	46
Tech Sheet 515			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SBIW13MPX	1/4"	22	43
25SBIW17MPX	3/8"	22	43
25SBIW21MPX	1/2"	22	46
Tech Sheet 515			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25SBTF06MPX	6mm (1/4")	21	60
25SBTF08MPX	8mm (5/16")	21	60
25SBTF10MPX	10mm (3/8")	21	60
25SBTF13MPX	13mm (1/2")	21	60
Tech Sheet 515			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 1600 SAFETY QUICK COUPLING SELF VENTING

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 12 bar (174 PSI)

Single Shut Off

Interchangeability:
Rectus design

Material:
Steel nickel plated

Application:
General purpose pneumatic coupling self-venting safety feature EN 983, ISO 4414, ISO 6150.

New updated version of the 25KE self venting couplings. Still interchangeable with original 25 Series couplings.



Profile

Couplings



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
1600KEAK13SPN	1/4"	19	64.5
Tech Sheet 60256			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
1600KEIW13SPN	1/4"	19	59
1600KEIW17SPN	3/8"	19	59
1600KEIW21SPN	1/2"	24	61.5
Tech Sheet 60256			



Hose Tail

0194	To Suit Hose ID	Hex Size mm	Length mm
1600KETF09SPN	9mm	19	79.5
1600KETF10SPN	10mm (3/8")	19	79.5
1600KETF13SPN	13mm (1/2")	19	79.5
Tech Sheet 60256			

Plugs



Male Thread, BSPT, Steel Nickel Plated

2510	Thread	Hex Size mm	Length mm
25SFAK10SXN	1/8"	13	33
25SFAK13SXN	1/4"	14	37
25SFAK17SXN	3/8"	17	37
25SFAK21SXN	1/2"	22	43
Tech Sheet 514			



Female Thread, BSPP, Steel Nickel Plated

2510	Thread	Hex Size mm	Length mm
25SFIW10SXN	1/8"	14	30
25SFIW13SXN	1/4"	17	38.5
25SFIW17SXN	3/8"	19	39.5
25SFIW21SXN	1/2"	24	44
Tech Sheet 514			



Hose Tail, Steel Nickel Plated

2510	To Suit Hose ID	Length mm
25SFTF06SXN	6mm (1/4")	48
25SFTF08SXN	8mm (5/16")	48
25SFTF09SXN	9mm	48
25SFTF10SXN	10mm (3/8")	48
25SFTF13SXN	13mm (1/2")	48
Tech Sheet 514		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 25 PREMIUM CODED QUICK COUPLING

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus design

Application:
Non-interchangeable, each coupling and plug has an individual shape so they can only be connected to each other, colour coded, one hand operation.



Profile

Couplings



Male Thread, BSPP

2510	Colour	Thread	Length mm
25KAAW13BPX6	Blue	1/4"	60
25KAAW13BPX8	Red	1/4"	60
25KAAW17BPX6	Blue	3/8"	60
25KAAW17BPX8	Red	3/8"	60
25KAAW21BPX8	Red	1/2"	61
Tech Sheet 517			



Female Thread, BSPP

2510	Colour	Thread	Length mm
25KAIW13BPX0	Green	1/4"	55
25KAIW13BPX3	Brown	1/4"	55
25KAIW13BPX6	Blue	1/4"	55
25KAIW13BPX8	Red	1/4"	55
25KAIW17BPX6	Blue	3/8"	55
25KAIW17BPX8	Red	3/8"	55
25KAIW21BPX3	Brown	1/2"	58
25KAIW21BPX6	Blue	1/2"	58
25KAIW21BPX8	Red	1/2"	58
Tech Sheet 517			



Hose Tail

2510	Colour	To Suit Hose ID mm	Length mm
25KATF06BPX3	Brown	6	74
25KATF06BPX6	Blue	6	74
25KATF06BPX8	Red	6	74
25KATF09BPX6	Blue	9	74
25KATF09BPX8	Red	9	74
Tech Sheet 517			

Plugs




Male Thread, BSPP

2510	Colour	Thread	Length mm
25SFAW13MXX6	Blue	1/4"	37
25SFAW13MXX8	Red	1/4"	37
25SFAW17MXX6	Blue	3/8"	37
Tech Sheet 517			



Female Thread, BSPP

2510	Colour	Thread	Length mm
25SFIW13MXX0	Green	1/4"	33
25SFIW13MXX3	Brown	1/4"	33
25SFIW13MXX6	Blue	1/4"	33
25SFIW13MXX8	Red	1/4"	33
25SFIW17MXX0	Green	3/8"	33
25SFIW17MXX6	Blue	3/8"	33
25SFIW17MXX8	Red	3/8"	33
Tech Sheet 517			



Hose Tail

2510	Colour	To Suit Hose ID mm	Length mm
25SFTF09MXX6	Blue	9	50.5
25SFTF09MXX8	Red	9	50.5
Tech Sheet 517			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 SAFETY QUICK COUPLING PARKER PROFILE SAFETY LOCK

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus design

Material:
Coupling: Steel nickel plated. NBR seal (standard series coupling).
Plug: Steel zinc plated.

Application:
Two-handed disconnection prevents accidental disconnection.
The coupling and plug must firstly be pushed together before the sleeve is pulled back.



Profile

Couplings



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25KSAK13SPN	1/4"	19	60
Tech Sheet 519			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KSTF10SPN	10mm (3/8")	19	74
25KSTF13SPN	13mm (1/2")	19	74
Tech Sheet 519			

Plugs



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25SSAK13SXN	1/4"	14	37
25SSAK17SXN	3/8"	17	37
25SSAK21SXN	1/2"	22	43
Tech Sheet 519			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SSIW13SXN	1/4"	17	33
25SSIW17SXN	3/8"	19	33
Tech Sheet 519			



Hose Tail

2510	To Suit Hose ID	Length mm
25SSTF08SXN	8mm (5/16")	48
25SSTF10SXN	10mm (3/8")	48
25SSTF13SXN	13mm (1/2")	48
Tech Sheet 519		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 QUICK COUPLING EUROPEAN PROFILE STAINLESS STEEL

stainless steel

Parker RECTUS

Working Temperature:
-15°C to +200°C
Standard seal FKM

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus 26

Material:
Stainless steel coupling and plug

Application:
General purpose pneumatic coupling, stainless steel.



Profile

Couplings



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KAAW13RVX	1/4"	19	59
25KAAW17RVX	3/8"	19	57.5
Tech Sheet 518			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KAIW13RVX	1/4"	19	56
25KAIW17RVX	3/8"	19	55
25KAIW21RVX	1/2"	24	56
Tech Sheet 518			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KATF10RVX	10mm (3/8")	19	74
25KATF13RVX	13mm (1/2")	19	74
Tech Sheet 518			

Plugs



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SFAW13RXX	1/4"	17	33.5
25SFAW17RXX	3/8"	19	33
25SFAW21RXX	1/2"	24	38
Tech Sheet 518			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SFIW13RXX	1/4"	17	38.5
25SFIW17RXX	3/8"	19	39.5
25SFIW21RXX	1/2"	24	44
Tech Sheet 518			



Hose Tail

2510	To Suit Hose ID	Length mm
25SFTF06RXX	6mm (1/4")	48
25SFTF08RXX	8mm (5/16")	48
25SFTF10RXX	10mm (3/8")	48
25SFTF13RXX	13mm (1/2")	48
Tech Sheet 518		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 25 SAFETY QUICK COUPLING
PARKER PROFILE SAFETY LOCKING

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Interchangeability:
Rectus design

Flow Rate:
Double valved 710 L/min

Material:
Brass nickel plated

Application:
General purpose pneumatic coupling



Profile

ULTRA-FLO »»

Couplings (Steel sleeve)



Male Thread, BSPT

2510	Thread	Hex Size mm	Length mm
25KDAK13BPNS	1/4"	19	60



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KDIW13BPNS	1/4"	19	56
25KDIW21BPNS	1/2"	24	58



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KDTF08BPNS	8mm (5/16")	19	74

Plugs (Valved)



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SDAW13MPN	1/4"	22	43
25SDAW17MPN	3/8"	22	43
25SDAW21MPN	1/2"	22	46



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SDIW13MPN	1/4"	22	43
25SDIW17MPN	3/8"	22	43
25SDIW21MPN	1/2"	24	46



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25SDTF08MPN	8mm (5/16")	21	60
25SDTF10MPN	10mm (3/8")	21	60
25SDTF13MPN	13mm (1/2")	21	60

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 26 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Festo KD Series

Material:
Brass

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KAAW10MPX	1/8"	22	43
26KAAW13MPX	1/4"	22	39
26KAAW17MPX	3/8"	22	41
26KAAW21MPX	1/2"	22	44
Tech Sheet 520			



Female Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KAIW13MPX	1/4"	22	41
26KAIW17MPX	3/8"	22	41
26KAIW21MPX	1/2"	24	44
Tech Sheet 520			



Hose Tail

2610	To Suit Hose ID	Hex Size mm	Length mm
26KATF06MPX	6mm (1/4")	21	58
26KATF08MPX	8mm (5/16")	21	58
26KATF09MPX	9mm	21	58
26KATF10MPX	10mm (3/8")	21	58
26KATF13MPX	13mm (1/2")	21	58
Tech Sheet 520			

Plugs



Male Thread, BSPP

2610	Thread	Hex Size mm	Length mm
25SFAW10MXX	1/8"	14	31
25SFAW13MXX	1/4"	17	33
25SFAW17MXX	3/8"	19	33
25SFAW21MXX	1/2"	24	38
Tech Sheet 520			



Female Thread, BSPP

2610	Thread	Hex Size mm	Length mm
25SFIW10MXX	1/8"	14	30
25SFIW13MXX	1/4"	17	33
25SFIW17MXX	3/8"	19	33
25SFIW21MXX	1/2"	24	35
Tech Sheet 520			



Hose Tail

2610	To Suit Hose ID	Length mm
25SFTF06MXX	6mm (1/4")	48
25SFTF08MXX	8mm (5/16")	48
25SFTF09MXX	9mm	48
25SFTF10MXX	10mm (3/8")	48
25SFTF13MXX	13mm (1/2")	48
Tech Sheet 520		

Y Connector



2 x Coupling Outlets, 1 x Plug Inlet

2610	Length mm
26Y	90
Tech Sheet 520	

Triple Outlet Connector



3 x Coupling Outlets, 1 x 3/8" BSPP Inlet

2610	Length mm
26W	96
Tech Sheet 520	

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

SERIES 26 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Interchangeability:
Rectus design

Material:
Brass

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KBAW13MPX	1/4"	22	39
26KBAW17MPX	3/8"	22	41
26KBAW21MPX	1/2"	24	42
Tech Sheet 520			



Female Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KBIW13MPX	1/4"	22	41
26KBIW17MPX	3/8"	22	41
26KBIW21MPX	1/2"	24	44
Tech Sheet 520			



Hose Tail

2610	To Suit Hose ID	Hex Size mm	Length mm
26KBTF06MPX	6mm (1/4")	21	58
26KBTF08MPX	8mm (5/16")	21	58
26KBTF10MPX	10mm (3/8")	21	58
26KBTF13MPX	13mm (1/2")	21	58
Tech Sheet 520			

Plugs



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SBAW13MPX	1/4"	22	43
25SBAW17MPX	3/8"	22	43
25SBAW21MPX	1/2"	22	46
Tech Sheet 520			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SBIW13MPX	1/4"	22	43
25SBIW17MPX	3/8"	22	43
25SBIW21MPX	1/2"	22	46
Tech Sheet 520			




Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25SBTF06MPX	6mm (1/4")	21	60
25SBTF08MPX	8mm (5/16")	21	60
25SBTF10MPX	10mm (3/8")	21	60
25SBTF13MPX	13mm (1/2")	21	60
Tech Sheet 520			

Other materials, seals and finishes available on request, please contact our technical department for further details.

FT PRO®

For **Brass & Nickel Plated Brass Hose Tails**
see pages **1140-1146**



FAC
Fluid-Air Components Ltd

SERIES 26 SAFETY QUICK COUPLING EUROPEAN PROFILE SELF VENTING

Working Temperature:
-20°C to +60°C
Standard seal nitrile

Maximum Static Working Pressure:
PB 12 bar (174 PSI)

Single Shut Off

Interchangeability:
Rectus design

EN 983
ISO 4414
ISO 6150

Material:
Brass nickel plated, nitrile seal

Application:
General purpose pneumatic coupling self-venting safety feature.



Profile

Couplings



Male Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KEAW13MPN	1/4"	22	55
26KEAW17MPN	3/8"	22	55
26KEAW21MPN	1/2"	24	58
Tech Sheet 10281			



Female Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KEIW13MPN	1/4"	22	57
26KEIW17MPN	3/8"	22	57
26KEIW21MPN	1/2"	24	60
Tech Sheet 10281			



Hose Tail

2610	To Suit Hose ID	Hex Size mm	Length mm
26KETF06MPN	6mm (1/4")	22	71
26KETF08MPN	8mm (5/16")	22	71
26KETF09MPN	9mm	22	71
26KETF10MPN	10mm (3/8")	22	71
26KETF13MPN	13mm (1/2")	22	71
Tech Sheet 10281			

Plugs



Male Thread, BSPT, Steel Nickel Plated

2510	Thread	Hex Size mm	Length mm
25SFAK10SXN	1/8"	13	33
25SFAK13SXN	1/4"	14	37
25SFAK17SXN	3/8"	17	37
25SFAK21SXN	1/2"	22	43
Tech Sheet 514			



Female Thread, BSPP, Steel Nickel Plated

2510	Thread	Hex Size mm	Length mm
25SFIW10SXN	1/8"	14	30
25SFIW13SXN	1/4"	17	38.5
25SFIW17SXN	3/8"	19	39.5
25SFIW21SXN	1/2"	24	44
Tech Sheet 514			



Hose Tail, Steel Nickel Plated

2510	To Suit Hose ID	Length mm
25SFTF06SXN	6mm (1/4")	48
25SFTF08SXN	8mm (5/16")	48
25SFTF09SXN	9mm	48
25SFTF10SXN	10mm (3/8")	48
25SFTF13SXN	13mm (1/2")	48
Tech Sheet 514		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 26 SAFETY PUSH BUTTON QUICK COUPLING ISO 6150 B ISO 6150 C & EUROPEAN SELF VENTING

Working Temperature:
-20°C up to +100°C

Maximum Working Pressure:
12 bar

Double Shut Off

Profile:
Euro Profile

Interchangeability:
Rectus 25, 1600/1625, JWL 520 and 530.

Material:
Anodised aluminium, brass nickel plated.

Application:
Parker's Safety Quick Coupling Series KP is a safety coupling with pushing button integrating self-venting system according to ISO 6150 B, ISO 6150 and EURO. The self-venting takes place during disconnection in 2 steps - no risk of pressurised hoses being tossed around. When the pushing button is pressed one time, the plug is released yet remains locked in. The coupling valve closes and the air is vented from the air line at the same time. Only then, by pressing the button again, can uncoupling take place safely. The system fulfils the requirements of ISO 4414 - increased safety standards in the work place and make the use easy.

The right plug for self-venting series KP can be found as followings:

- ISO 6150 B; DN 5,5: Plug series 23
- ISO 6150 B; DN 8: Plug series 30
- ISO 6150 C; DN 5,5: Plug series 18
- ISO 6150 B; DN 8: Plug series 84
- EURO; DN 7,4: Plug series 25

Nominal Diameter:
7.4mm

Flow Rate:
1225 L/min (6 bar, dP 0.5 bar)



Profile

Couplings



Male Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KPAW13APX	1/4"	22	72
26KPAW17APX	3/8"	22	72
26KPAW21APX	1/2"	22	75
Tech Sheet 110818			



Female Thread, BSPP

2610	Thread	Hex Size mm	Length mm
26KPIW13APX	1/4"	22	70.5
26KPIW17APX	3/8"	22	72.5
26KPIW21APX	1/2"	22	74.5
Tech Sheet 110818			



Hose Tail

2610	Thread	Hex Size mm	Length mm
26KPTF06APX	6	22	85.5
26KPTF08APX	8	22	85.5
26KPTF10APX	10	22	85.5
26KPTF13APX	13	22	85.5
Tech Sheet 110818			

FTPRO



For **Rubber Alloy Hose Assemblies**
see page **1411**

Fluid-Air Components Ltd

SERIES 27 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
Couplings:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus 41, 100, 1727.

Material:
Brass, nickel plated, NBR seal (standard series) coupling.

Application:
General purpose high-flo pneumatic
Coupling self venting safety feature
Machinery construction, trade and automotive.



Profile

Couplings



Male Thread, BSPT

2710	Thread	Hex Size mm	Length mm
27KAAK13MPN	1/4"	24	63
27KAAK17MPN	3/8"	24	63
27KAAK21MPN	1/2"	24	65
27KAAK26MPN	3/4"	27	65
Tech Sheet 521			



Female Thread, BSPP

2710	Thread	Hex Size mm	Length mm
27KAIW13MPN	1/4"	24	56
27KAIW17MPN	3/8"	24	56
27KAIW21MPN	1/2"	24	56
27KAIW26MPN	3/4"	27	60
Tech Sheet 521			



Hose Tail

2710	To Suit Hose ID	Hex Size mm	Length mm
27KATF06MPN	6mm (1/4")	24	76
27KATF09MPN	9mm	24	76
27KATF10MPN	10mm (3/8")	24	76
27KATF13MPN	13mm (1/2")	24	76
27KATF16MPN	16mm (5/8")	24	76
27KATF19MPN	19mm (3/4")	24	76
Tech Sheet 521			

For **Parker LF3000® Push-In**
see page **793**



Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 27 QUICK COUPLING EUROPEAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Interchangeability:
Rectus design

Material:
Brass

Application:
General purpose high-flo pneumatic couplin



Profile

Couplings



Male Thread, BSPT

0194	Thread	Hex Size mm	Length mm
27KBAK21BPX	1/2"	24	65
Tech Sheet 522			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
27KBIW17BPX	3/8"	24	56
27KBIW21BPX	1/2"	24	56
27KBIW26BPX	3/4"	32	60
Tech Sheet 522			



Hose Tail

0194	To Suit Hose ID mm	Hex Size mm	Length mm
27KBTF10BPX	10mm (3/8")	24	76
27KBTF13BPX	13mm (1/2")	24	76
27KBTF19BPX	19mm (3/4")	24	76
Tech Sheet 522			

Plugs



Male Thread, BSPT

0194	Thread	Hex Size mm	Length mm
27SBAK21MPX	1/2"	24	62.5
27SBAK26MPX	3/4"	27	62.5
Tech Sheet 522			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
27SBIW21MPX	1/2"	24	54.5
Tech Sheet 522			



Hose Tail

0194	To Suit Hose ID	Hex Size mm	Length mm
27SBTF13MPX	13mm (1/2")	24	74
Tech Sheet 522			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 1700 SAFETY QUICK COUPLING SELF VENTING

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 12 bar (174 PSI)

Single Shut Off

Material:
Brass, nickel plated, NBR seal (standard series) coupling.

Application:
General purpose pneumatic coupling self venting safety feature.
Machinery construction, trade and automotive.

New updated version of the 27KE self venting couplings.
Still interchangeable with original 27 Series couplings.



Profile

Couplings



Male Thread, BSPT

0194	Thread	Hex Size mm	Length mm
1700KEAW17SPN	3/8"	24	67
1700KEAW21SPN	1/2"	24	70
1700KEAW26SPN	3/4"	30	74
Tech Sheet 60257			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
1700KEIW17SPN	3/8"	24	64.5
1700KEIW21SPN	1/2"	24	68
1700KEIW26SPN	3/4"	32	74
Tech Sheet 60257			

Plugs



Male Thread, BSPT

2710	Thread	Hex Size mm	Length mm
27SFAK13SXN	1/4"	17	40
27SFAK17SXN	3/8"	17	40
27SFAK21SXN	1/2"	22	45
27SFAK26SXN	3/4"	27	48
Tech Sheet 60257			



Female Thread, BSPP

2710	Thread	Hex Size mm	Length mm
27SFIW13SXN	1/4"	17	33
27SFIW17SXN	3/8"	19	33
27SFIW21SXN	1/2"	24	37
27SFIW26SXN	3/4"	32	42
Tech Sheet 60257			



Hose Tail

2710	To Suit Hose ID	Length mm
27SFTF06SXN	6mm (1/4")	48
27SFTF09SXN	9mm	48
27SFTF10SXN	10mm (3/8")	48
27SFTF13SXN	13mm (1/2")	48
27SFTF16SXN	16mm (5/8")	48
27SFTF19SXN	19mm (3/4")	48
Tech Sheet 60257		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 30 QUICK COUPLING ISO 6150 B PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
US-MIL-SPEC-C-4109
ISO 615oB, Gromelle 900 Aro,
Hansen 4000, Parker 30 3/8"

Material:
Brass, nickel plated, NBR seal (standard series) coupling.

Application:
General purpose pneumatic coupling, machinery construction, trade and automotive.



Profile

Couplings



Male Thread, BSPP

3710	Thread	Hex Size mm	Length mm
30KAAW13SPN	1/4"	22	49
30KAAW17SPN	3/8"	22	49
30KAAW21SPN	1/2"	22	52
Tech Sheet 800			



Female Thread, BSPP

3710	Thread	Hex Size mm	Length mm
30KAIW13SPN	1/4"	22	49
30KAIW17SPN	3/8"	22	49
30KAIW21SPN	1/2"	22	52
Tech Sheet 800			



Hose Tail

3710	To Suit Hose ID	Hex Size mm	Length mm
30KATF08SPN	8mm (5/16")	21	66
30KATF10SPN	10mm (3/8")	21	66
Tech Sheet 800			

Plugs



Male Thread, BSPP

3710	Thread	Hex Size mm	Length mm
30SFAW13SXN	1/4"	17	42
30SFAW17SXN	3/8"	19	42
30SFAW21SXN	1/2"	24	46
Tech Sheet 800			



Female Thread, BSPP

3710	Thread	Hex Size mm	Length mm
30SFIW13SXN	1/4"	17	40
30SFIW17SXN	3/8"	19	42
30SFIW21SXN	1/2"	24	43
Tech Sheet 800			



Hose Tail

3710	To Suit Hose ID	Length mm
30SFTF06SXN	6mm (1/4")	55
30SFTF08SXN	8mm (5/16")	55
30SFTF10SXN	10mm (3/8")	55
30SFTF13SXN	13mm (1/2")	55
Tech Sheet 800		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 33 QUICK COUPLING
ATLAS COPCO PROFILE

Working Temperature:
-20°C to +100°C
Standard seal nitrile

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Atlas QIC 10

Material:
Steel nickel plated, nitrile seal

Application:
General purpose high-flo pneumatic couplin



Profile

Couplings



Male Thread, BSPT

3310	Thread	Hex Size mm	Length mm
33KAAK13SPN	1/4"	19	60
33KAAK17SPN	3/8"	19	59
33KAAK21SPN	1/2"	22	60
Tech Sheet 523			



Female Thread, BSPP

3310	Thread	Hex Size mm	Length mm
33KAIW13SPN	1/4"	19	55
33KAIW17SPN	3/8"	19	54
33KAIW21SPN	1/2"	24	57
Tech Sheet 523			



Hose Tail

3310	To Suit Hose ID	Hex Size mm	Length mm
33KATF06SPN	6mm (1/4")	19	73
33KATF08SPN	8mm (5/16")	19	73
33KATF13SPN	13mm (1/2")	19	73
Tech Sheet 523			

Plugs



Male Thread, BSPT

3310	Thread	Hex Size mm	Length mm
33SFAK13SXN	1/4"	14	42
33SFAK17SXN	3/8"	17	42
33SFAK21SXN	1/2"	22	47
Tech Sheet 523			



Female Thread, BSPP

3310	Thread	Hex Size mm	Length mm
33SFIW13SXN	1/4"	17	37
33SFIW17SXN	3/8"	17	37
33SFIW21SXN	1/2"	24	42
Tech Sheet 523			



Hose Tail

3310	To Suit Hose ID	Length mm
33SFTF06SXN	6mm (1/4")	52
33SFTF08SXN	8mm (5/16")	52
33SFTF10SXN	10mm (3/8")	52
33SFTF13SXN	13mm (1/2")	52
Tech Sheet 523		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 34 QUICK COUPLING ATLAS COPCO PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Atlas Copco QIC 15

Material:
Steel nickel plated, nitrile seal

Application:
General purpose pneumatic coupling



Profile

ULTRA-FLO »

Couplings



Male Thread, BSPT

3310	Thread	Hex Size mm	Length mm
34KAAK17SPN	3/8"	24	70
34KAAK21SPN	1/2"	24	72
34KAAK26SPN	3/4"	27	72
Tech Sheet 524			



Female Thread, BSPP

3310	Thread	Hex Size mm	Length mm
34KAIW21SPN	1/2"	24	64
34KAIW26SPN	3/4"	32	68
Tech Sheet 524			



Hose Tail

3310	To Suit Hose ID	Hex Size mm	Length mm
34KATF10SPN	10mm (3/8")	24	84
34KATF13SPN	13mm (1/2")	24	84
Tech Sheet 524			

Plugs



Male Thread, BSPT

3310	Thread	Hex Size mm	Length mm
34SFAK13SXN	1/4"	17	46
34SFAK17SXN	3/8"	19	46
34SFAK21SXN	1/2"	22	52
Tech Sheet 524			



Female Thread, BSPP

3310	Thread	Hex Size mm	Length mm
34SFIW17SXN	3/8"	19	40
34SFIW21SXN	1/2"	24	44
Tech Sheet 524			



Hose Tail

3310	To Suit Hose ID	Length mm
34SFTF10SXN	10mm (3/8")	55
34SFTF13SXN	13mm (1/2")	55
34SFTF16SXN	16mm (5/8")	55
Tech Sheet 524		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 40 QUICK COUPLING PARKER PROFILE LOW PRESSURE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Material:
Brass, nitrile seal



Profile

Couplings



Female Thread, BSPP

4010	Thread	Hex Size mm	Length mm
40KAIW17MPX	3/8"	27	46
40KAIW21MPX	1/2"	27	46
Tech Sheet 30002			

Plugs



Male Thread, BSPT

4010	Thread	Hex Size mm	Length mm
40SFAK17SXN	3/8"	17	40
Tech Sheet 30002			



Female Thread, BSPP

4010	Thread	Hex Size mm	Length mm
40SFIW17SXN	3/8"	19	35
40SFIW21SXN	1/2"	24	39
Tech Sheet 30002			



Hose Tail

4010	To Suit Hose ID mm	Length mm
40SFTF08SXN	8	51
40SFTF10SXN	10	51
40SFTF13SXN	13	51
Tech Sheet 30002		

For **Valves & Actuation** see **Section 7** page **919**



Fluid-Air Components Ltd

SERIES 41 QUICK COUPLING PARKER PROFILE LOW PRESSURE FLUID & PNEUMATIC

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Straight Through

Interchangeability:
Rectus 27

Material:
Brass nickel plated

Application:
Straight through coupling designed for water.
High flow water applications



Profile

Couplings



Male Thread, BSPP

4110	Thread	Length mm
41KFAW21MPN	1/2"	31
Tech Sheet 525		



Female Thread, BSPP & Metric

4110	Thread	Hex Size mm	Length mm
41KFIW21MPN	1/2"	24	32
Tech Sheet 525			



Hose Tail

4110	To Suit Hose ID	Length mm
41KFTF13MPN	13mm (1/2")	48
41KFTF16MPN	16mm (5/8")	48
41KFTF19MPN	19mm (3/4")	48
Tech Sheet 525		

Plugs



Male Thread, BSPP

4110	Thread	Hex Size mm	Length mm
41SFAW21MXN	1/2"	24	40
41SFAW26MXN	3/4"	32	45
Tech Sheet 525			



Female Thread, BSPP

4110	Thread	Hex Size mm	Length mm
41SFIW21MXN	1/2"	24	37
41SFIW26MXN	3/4"	32	42
Tech Sheet 525			



Hose Tail

4110	To Suit Hose ID	Length mm
41SFTF10MXN	10mm (3/8")	48
41SFTF13MXN	13mm (1/2")	48
41SFTF16MXN	16mm (5/8")	48
41SFTF19MXN	19mm (3/4")	48
Tech Sheet 525		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 45 QUICK COUPLING PARKER PROFILE ISO BAR

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 15 bar

Straight Through

Interchangeability:
Hanson, Parker

Material:
Steel nickel plated

Application:
Straight through coupling, maximum flo , high pressure water and steam washers.



Profile

Couplings



Male Thread, BSPP, Viton Seals

4510	Thread	Hex Size mm	Length mm
45KFIW17MVX	3/8"	24	37
Tech Sheet 10282			

Plugs



Male Thread, BSPP, Steel Nickel Plated

4510	Thread	Hex Size mm	Length mm
45SFAW17SXN	3/8"	22	40
Tech Sheet 10282			



Female Thread, BSPP, Steel Nickel Plated

4510	Thread	Hex Size mm	Length mm
45SFIW17SXN	3/8"	22	42
Tech Sheet 10282			

For **Pneumatic Valves & Accessories** see page **565**




Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 48 QUICK COUPLING
PARKER PROFILE THERMOPLASTIC

Working Temperature:
RectuPom -20°C to +80°C NBR
RectuChem -20°C to +120°C NBR

Working Pressure @ +20°C:
RectuPom 0-10 bar
RectuChem 0-8 bar
RectuChem+ 1-8 bar



Interchangeability:
Rectus design

Material:
RectuPom – thermoplastic POM Black
RectuChem – thermoplastic PVDF White

Application:
Suitable for liquids, gases, drinking water, laboratories, medical technology and food areas.



Profile

Couplings



Male Thread, BSPP, RectuPom

0194	Thread	Hex Size mm	Length mm
48KBAW17DPX	3/8"	21	67
48KBAW21DPX	1/2"	21	74
Tech Sheet 10283			



Female Thread, BSPP, RectuPom

0194	Thread	Hex Size mm	Length mm
48KBIW13DPX	1/4"	21	64
48KBIW17DPX	3/8"	21	64
Tech Sheet 10283			



Hose Tail, RectuPom

0194	To Suit Hose ID mm	Hex Size mm	Length mm
48KBTF06DPX	6	21	81
48KBTF09DPX	9	21	81
48KBTF13DPX	13	21	84
Tech Sheet 10283			



Male Thread, BSPP, RectuChem

0194	Thread	Hex Size mm	Length mm
48KBAW13FVX	1/4"	21	71
48KBAW17FVX	3/8"	21	67
Tech Sheet 10283			



Female Thread, BSPP, RectuChem

0194	Thread	Hex Size mm	Length mm
48KBIW21FVX	1/2"	21	75
Tech Sheet 10283			



Hose Tail, RectuChem

0194	To Suit Hose ID mm	Hex Size mm	Length mm
48KBTF06FVX	6	21	81
48KBTF13FVX	13	21	84
Tech Sheet 10283			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 48 QUICK COUPLING
PARKER PROFILE THERMOPLASTIC

Plugs

Single Shut Off



Male Thread, BSPP, RectuPom

0194	Thread	Hex Size mm	Length mm
48SFAW13DXX	1/4"	17	39
Tech Sheet 10283			



Male Thread, BSPP, RectuChem

0194	Thread	Hex Size mm	Length mm
48SFAW13FXX	1/4"	17	39
48SFAW17FXX	3/8"	21	39
Tech Sheet 10283			



Female Thread, BSPP, RectuPom

0194	Thread	Hex Size mm	Length mm
48SFIW13DXX	1/4"	17	38.5
48SFIW17DXX	3/8"	21	35.5
Tech Sheet 10283			



Hose Tail, RectuPom

0194	To Suit Hose ID mm	Length mm
48SFTF13DXX	13	65.5
Tech Sheet 10283		



Hose Tail, RectuChem

0194	To Suit Hose ID mm	Length mm
48SFTF09FXX	9	65.5
Tech Sheet 10283		

Plugs (with Valve)

Double Shut Off



Female Thread, BSPP, RectuPom

0194	Thread	Hex Size mm	Length mm
48SBIW17DPX	3/8"	21	48
Tech Sheet 10283			



Female Thread, BSPP, RectuChem

0194	Thread	Hex Size mm	Length mm
48SBIW21FVX	1/2"	21	59
Tech Sheet 10283			



Hose Tail, RectuPom

0194	To Suit Hose ID mm	Hex Size mm	Length mm
48SBTF06DPX	6	21	65.5
48SBTF09DPX	9	21	65.5
Tech Sheet 10283			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 51 QUICK COUPLING GERMAN INDUSTRIAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 50 bar (725 PSI)

Single Shut Off Double Shut Off

Interchangeability:
Rectus design

Material:
Steel nickel plated

Application:
Robust steel coupling for compressed air.
Pneumatic fluid handling



Profile

Couplings



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
51KBIW13SPN	1/4"	22	61
51KBIW17SPN	3/8"	22	61
Tech Sheet 2099			

Plugs



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
51SFAW13SXN	1/4"	17	35
Tech Sheet 2099			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
51SFIW13SXN	1/4"	17	34
51SFIW17SXN	3/8"	19	34
Tech Sheet 2099			

stainless steel



For **Angle Seat Valves**
see page **1051**


Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 52 QUICK COUPLING GERMAN INDUSTRIAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 50 bar (725 PSI)



Interchangeability:
Rectus design

Material:
Steel nickel plated, NBR seal.

Application:
Robust steel coupling for compressed air.
Pneumatic fluid handling



Profile

Couplings



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
52KBAW13SPN	1/4"	22	62
52KBAW17SPN	3/8"	22	62
52KBAW21SPN	1/2"	22	65
Tech Sheet 2100			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
52KBIW13SPN	1/4"	22	62
52KBIW17SPN	3/8"	22	60
52KBIW21SPN	1/2"	22	65
Tech Sheet 2100			



Hose Tail

0194	To Suit Hose ID mm	Hex Size mm	Length mm
52KBTF11SPN	11	21	80
Tech Sheet 2100			

Plugs



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
52SFAW17SXN	3/8"	19	35
Tech Sheet 2100			



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
52SBAW13SPN	1/4"	22	48
52SBAW17SPN	3/8"	22	48
52SBAW21SPN	1/2"	22	48
Tech Sheet 2100			



Hose Tail

0194	To Suit Hose ID mm	Length mm
52SFTF06SXN	6	46
Tech Sheet 2100		

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 57 QUICK COUPLING GERMAN INDUSTRIAL PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Double Shut Off

Interchangeability:
Rectus design

Material:
Brass nickel plated, NBR seal.

Application:
Robust steel coupling for compressed air.
Pneumatic fluid handling



Profile

ULTRA-FLO »»

Couplings



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
57KBAW26SPN	3/4"	34	100
57KBAW33SPN	1"	41	100
Tech Sheet 2101			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
57KBIW21SPN	1/2"	34	100
57KBIW26SPN	3/4"	34	100
57KBIW33SPN	1"	41	101
Tech Sheet 2101			



Hose Tail

0194	To Suit Hose ID mm	Hex Size mm	Length mm
57KBTF19SPN	19	34	122
Tech Sheet 2101			

Plugs



Male Thread, BSPP

0194	Thread	Hex Size mm	Length mm
57SBAW21SPN	1/2"	27	83
57SBAW26SPN	3/4"	34	85
57SBAW33SPN	1"	41	85
Tech Sheet 2101			



Female Thread, BSPP

0194	Thread	Hex Size mm	Length mm
57SBIW21SPN	1/2"	27	85
57SBIW26SPN	3/4"	34	85
Tech Sheet 2101			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 68 SCHRADER

Working Temperature:
-10°C to +80°C
Standard seal NBR

Maximum Static Working Pressure:
PB 17 bar (246 PSI)

Single Shut Off

Interchangeability:
Schrader heavy-duty

Material:
Steel nickel plated, NBR seal (standard series coupling).

Application:
General purpose pneumatic coupling



Profile

Couplings



Male Thread, BSPP

1710	Thread	Hex Size mm	Length mm
68KAAW17SPN	3/8"	30	66
68KAAW21SPN	1/2"	30	68
68KAAW26SPN	3/4"	30	68



Female Thread, BSPP

1710	Thread	Hex Size mm	Length mm
68KAIW13SPN	1/4"	30	74
68KAIW17SPN	3/8"	30	74
68KAIW21SPN	1/2"	30	68
68KAIW26SPN	3/4"	32	68



Hose Tail

1710	To Suit Hose ID	Hex Size mm	Length mm
68KATF10SPN	10mm (3/8")	30	81
68KATF13SPN	13mm (1/2")	30	81
68KATF19SPN	19mm (3/4")	30	81

FT PRO®

For **Superior Rubber Alloy Air Hose & Assemblies**
see page **1410**





Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 86 QUICK COUPLINGS INTERNATIONAL PROFILE MOULD COUPLING (MOLD)

Working Temperature:
-15°C to +200°C
Standard seal FKM

Maximum Static Working Pressure:
PB 15 bar (217 PSI)



Interchangeability:
D-M-E, Foster FJT,
Parker Mold Mate.

Material:
Brass, seals FKM standard, silicone available.

Application:
Brass coupling for connection of coolant lines to moulds and dies.

Product Description:
Parker's Quick Coupling Series 86/87/88 were especially developed for connecting coolant lines and injection molds. The countersunk plugs can easily be connected and disconnected because of the extended sleeve. The angular connections prevent kinks from forming in the hose.

This coupling series is available in single shut-off, double shut-off, straight-through versions and is also available with SAFE-LOCK™ technology. The shut-off couplings (with valve) are equipped with nickel plated sleeves for quick and accurate visual differentiation.


Markets: Industrial

Features and Benefits:
- SAFE-LOCK™ technology reliably prevents accidental uncoupling of the system under pressure.
- Shut off couplings are equipped with nickel plated sleeve for quick and accurate visual differentiation.



Profile

Couplings



Male Thread, BSPP, Straight Through

4610	Thread	Hex Size mm	Length mm
86KFAW13MVX	1/4"	15	43
Tech Sheet 527			

Male Thread, BSPP, Double Shut Off

4610	Thread	Hex Size mm	Length mm
86KBAW13MVX	1/4"	15	43
Tech Sheet 527			



45° Hose Tail, Double Shut Off

4610	To Suit Hose ID	Hex Size mm	Length mm
86KBTH09MVX	9mm (3/8")	15	61
Tech Sheet 527			



Female Thread, BSPP, Straight Through

4610	Thread	Hex Size mm	Length mm
86KFIW10MVX	1/8"	15	39
86KFIW13MVX	1/4"	15	41
Tech Sheet 527			

Female Thread, BSPP, Double Shut Off

4610	Thread	Hex Size mm	Length mm
86KBIW13MVX	1/4"	15	41
Tech Sheet 527			



90° Hose Tail, Straight

4610	To Suit Hose ID	Hex Size mm	Length mm
86KFTR09MVX	9mm (3/8")	15	44
Tech Sheet 527			

90° Hose Tail, Double Shut Off

4610	To Suit Hose ID	Hex Size mm	Length mm
86KBTR09MVX	9mm (3/8")	15	44
Tech Sheet 527			



Straight Hose Tail, Straight

4610	To Suit Hose ID	Hex Size mm	Length mm
86KFTF06MVX	6mm (1/4")	15	56
86KFTF09MVX	9mm (3/8")	15	56
Tech Sheet 527			

Straight Hose Tail, Double Shut Off

4610	To Suit Hose ID	Hex Size mm	Length mm
86KBTF06MVX	6mm (1/4")	15	56
86KBTF09MVX	9mm (3/8")	15	56
Tech Sheet 527			

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 86 QUICK COUPLING INTERNATIONAL PROFILE

Straight Through Plugs



Male Thread, BSPT

4610	Thread	Hex Size mm	Length mm
86SFAK10MXX	1/8"	11	24
86SFAK13MXX	1/4"	14	28.5
86SFAK17MXX	3/8"	17	26.5
Tech Sheet 527			

Shut-off Plug



Male Thread, BSPT

4610	Thread	Hex Size mm	Length mm
86SBAK13MVX	1/4"	17	23.5
Tech Sheet 527			

Replacement Bodyseals



Viton & Silicone

4610
86-VITON
86-SILICONE
Tech Sheet 527

Snap-tite





Other materials, seals and finishes available on request, please contact our technical department for further details.

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 87 QUICK COUPLING INTERNATIONAL PROFILE MOULD COUPLINGS

Working Temperature:
-15°C to +200°C
Standard seal FKM

Maximum Static Working Pressure:
PB 15 bar (217 PSI)



Interchangeability:
D-M-E, Jiffy-Tite, Jiffy-Matic, Foster FJT, Parker Mould Mate

Material:
Brass, viton or silicone seals

Application:
Brass coupling for connection of coolant lines to moulds and dies



Profile

Couplings



Straight Hose Tail, Straight

4610	To Suit Hose ID	Hex Size mm	Length mm
87KFTF09MVX	9mm (3/8")	19	71
87KFTF13MVX	13mm (1/2")	19	71
Tech Sheet 526			

Straight Hose Tail, Double Shut Off

4610	To Suit Hose ID	Hex Size mm	Length mm
87KBTF09MVX	9mm (3/8")	19	71
87KBTF13MVX	13mm (1/2")	19	71
Tech Sheet 526			



45° Hose Tail, Straight

4610	To Suit Hose ID	Hex Size mm	Length mm
87KFTH09MVX	9mm (3/8")	19	79
87KFTH13MVX	13mm (1/2")	19	79
Tech Sheet 526			

45° Hose Tail, Double Shut Off

4610	To Suit Hose ID	Hex Size mm	Length mm
87KBTH09MVX	9mm (3/8")	19	79
87KBTH13MVX	13mm (1/2")	19	79
Tech Sheet 526			



90° Hose Tail, Straight

4610	To Suit Hose ID	Hex Size mm	Length mm
87KFTR09MVX	9mm (3/8")	19	65
87KFTR13MVX	13mm (1/2")	19	65
Tech Sheet 526			

Straight Through Plugs



Male Thread, Brass, BSPT

4610	Thread	Hex Size mm	Length mm
87SFAK13MXX	1/4"	14	32
87SFAK17MXX	3/8"	17	32
87SFAK21MXX	1/2"	22	39
Tech Sheet 526			



Female Thread, Steel, Nickel Plated, BSPP

4610	Thread	Hex Size mm	Length mm
87SFIW13SXN	1/4"	19	37
87SFIW17SXN	3/8"	19	37
Tech Sheet 526			

Shut-off Plug



Male Thread, Brass, BSPT

4610	Thread	Hex Size mm	Length mm
87SBAK17MVX	3/8"	17	34
87SBAK21MVX	1/2"	22	39
Tech Sheet 526			

Replacement Bodyseals



Viton & Silicone

4610
87-VITON
87-SILICONE
Tech Sheet 526

Fluid-Air Components Ltd

SERIES 95 BREATHING AIR QUICK COUPLINGS

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Flow Rate:
1700 L/min

Material:
Brass nickel plated, NBR seal (standard series coupling)

Application:
Single shut off quick connect coupling commonly used on portable breathing air kits and hose line trolley packs

ULTRA-FLO



Profile

Couplings



Male Thread, BSPT

9510	Thread	Hex Size mm	Length mm
95KSAK13BPN	1/4"	19	61
95KSAK17BPN	3/8"	19	61
95KSAK21BPN	1/2"	22	61
Tech Sheet 528			



Female Thread, BSPP

9510	Thread	Hex Size mm	Length mm
95KSIW13BPN	1/4"	19	56
95KSIW17BPN	3/8"	19	55
Tech Sheet 528			



Hose Tail

9510	To Suit Hose ID	Hex Size mm	Length mm
95KSTF08BPN	8mm (5/16")	19	74
95KSTF09BPN	9mm (3/8")	19	74
95KSTF13BPN	13mm (1/2")	19	74
Tech Sheet 528			

Plugs



Male Thread, BSPT

9510	Thread	Hex Size mm	Length mm
96SSAK13MXN	1/4"	14	38.5
96SSAK17MXN	3/8"	17	38.5
Tech Sheet 528			

Male Thread, BSPT, 316 Stainless Steel

stainless steel

9510	Thread	Hex Size mm	Length mm
96SSAK13EXX	1/4"	14	38.5
Tech Sheet 528			



Female Thread, BSPP

9510	Thread	Hex Size mm	Length mm
96SSIW13MXN	1/4"	17	33
96SSIW17MXN	3/8"	19	33
Tech Sheet 528			

Dust Protection



Caps & Plugs

9510	To Suit
SK23S	Coupling
SK12S	Plug
Tech Sheet 528	



Hose Tail

9510	To Suit Hose ID	Length mm
96SSTF06MXN	6mm (1/4")	48
96SSTF09MXN	9mm (3/8")	48
Tech Sheet 528		

Hose Tail, 316 Stainless Steel

stainless steel

9510	To Suit Hose ID	Length mm
96SSTF10EXX	10mm (3/8")	48
Tech Sheet 528		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SCHRADER COUPLINGS & PLUGS

Features:
- Twist-lock action
- Wide choice of adaptors
- Non-whip
- Rugged design

Application:
Twist-lock units are designed for single-handed connection and disconnection. A twist on the cap will release the adaptor and the air line will automatically reseal. When coupled, the check unit allows the adaptors to swivel, to eliminate kinking of the hose.

Working Temperature: -10°C to +80°C

Working Pressure: 0 to 17 bar

Standard Duty Couplings



Male Thread, BSPT

4801	Thread	Length mm
9793D-12	1/4"	55
9792D-12	3/8"	55
Tech Sheet 68771		



Female Thread, BSPP

4801	Thread	Length mm
8952DL-12	1/4"	45
Tech Sheet 68771		

Standard Duty Plugs



Male Thread, BSPT

4801	Thread	Length mm
8051B-11	1/8"	42
8050B-11	1/4"	44
Tech Sheet 68771		



Hose Tail

4801	To Suit Hose ID	Length mm
8787-11	6mm (1/4")	57
9750-11	8mm (5/16")	57
8788-11	10mm (3/8")	57
Tech Sheet 68771		



Female Thread, BSPP, Non-whip

4801	Thread	Length mm
9031	1/4"	55
Tech Sheet 68771		

Heavy-duty Couplings



Female Thread, BSPP

4801	Thread	Length mm
1054EL-12	1/4"	58
1095EL-12	3/8"	58
1461EL-12	1/2"	58
1462EL-12	3/4"	63
Tech Sheet 68771		

Heavy-duty Plugs



Male Thread, BSPT

4801	Thread	Length mm
8624B-11	1/4"	48
9739-11	3/8"	48
8807-11	1/2"	54
Tech Sheet 68771		



Male Thread, BSPP

4801	Thread	Length mm
1462B-11	3/4"	55
Tech Sheet 68771		



Female Thread, BSPP

4801	Thread	Length mm
1261L-11	1/4"	43
1096B-11	3/8"	47
Tech Sheet 68771		



Hose Tail

4801	To Suit Hose ID	Length mm
1097-11	10mm (3/8")	71
1098-11	12mm (1/2")	71
Tech Sheet 68771		



Female Thread, BSPP, Non-whip

4801	Thread	Length mm
9042	3/8"	57.5
Tech Sheet 68771		

Fluid-Air Components Ltd

SERIES 1100 SCANDINAVIAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
30 bar

Single Shut Off

Material:
Coupling: Brass nickel plated
Plug: Steel zinc plated
Seals: NBR
Interchangeability:
Tema design
Application:

Robust design with small dimensions. Series 1100 is used mainly for applications in the area of compressed air and liquids. Optimally suited to smaller pneumatic systems and to compressed air tools with a consumption of up to 900 litres per minute. Coupling systems with two hand operation i.e. both hands are required when connect/disconnect.



Profile

Couplings



BSPP, Nitrile Seals, Single Shut Off

0073	Thread	Length mm
TE-1100 A	1/4" Male	38
TE-1100	1/8" Female	37
	Tech Sheet 529	

Plugs



BSPP, Single Shut Off

0073	Thread	Length mm
TE-11410	1/8" Female	27
	Tech Sheet 529	



Hose Tail, Single Shut Off

0073	To Suit Hose ID mm	Length mm
TE-11006	6	33
	Tech Sheet 529	



For **Parker Rectus RectuChem Fittings**
see pages **347-349**

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SERIES 1300 SCANDINAVIAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
35 bar

Single Shut Off



Profile

Features:
- Single hand operation

Material:
Coupling: Brass nickel plated
Plug: Brass nickel plated
Seals: NBR

Interchangeability:
Rectus Series 31.

Application:
Series 1300 is used mainly for applications in the area of compressed air and liquids. Optimally suited to smaller to medium-sized pneumatic systems and to compressed air tools. The coupling series stands out for its compact design and high flow rates with the UltraFlo valve. Coupling body made of nitrocarburized steel.

Couplings



BSPP, Nitrile Seals NBR

0073	Thread	Length mm
TE-1300	1/4" Female	49
TE-1300 A	3/8" Male	49
TE-1300 B	3/8" Female	50
	Tech Sheet 530	

BSPP, Valved Viton Seals

0073	Thread	Length mm
TE-1300 V	1/4" Female	49
	Tech Sheet 530	

Dust Protection



Plug

0073	To Suit
TE-1325	Series 1300
	Tech Sheet 530

Plugs



BSPP

0073	Thread	Length mm
TE-13210	1/4" Male	38
TE-13410	1/4" Female	36
	Tech Sheet 530	



Hose Tail

0073	To Suit Hose ID mm	Length mm
TE-13010	10	44
	Tech Sheet 530	

AIR CONTROL JWL

new product



For **JWL Air Boy® Thrust Blow Gun**
see page **1601**

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

SERIES 1800 SCANDINAVIAN PROFILE

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
35 bar

Single Shut Off

Features:
- Single hand operation
- Particularly suited to medium-sized to large pneumatic systems and compressed air tools

Material:
Coupling: Brass nickel plated
Plug: Steel zinc plated
Seals: NBR

Interchangeability:
Rectus 32

Application:
Series 1800 is used mainly for applications in the area of compressed air and liquids. The coupling system stands out for its robust, compact design, high flow and high corrosion resistance due to the ultra high flow valve



Profile

Couplings



BSPP, Valved Nitrile Seal

0073	Thread	Length mm
TE-1800	3/8" Female	54
TE-1800 A	1/2" Male	54
TE-1800 B	1/2" Female	55
TE-1800 C	3/4" Female	57
	Tech Sheet 531	

Plugs



BSPP

0073	Thread	Length mm
TE-18110	1/4" Male	39
TE-18210	3/8" Male	38
TE-18220	1/2" Male	40
TE-18405	1/4" Female	36
TE-18410	3/8" Female	36
TE-18420	1/2" Female	39
	Tech Sheet 531	



Hose Tail

0073	To Suit Hose ID mm	Length mm
TE-18008	8	42
	Tech Sheet 531	

For **Parker Legris Universal Blow Gun**
see page **1602**



Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

C9000 ADVANCED QUICK ACTING COUPLERS – ISO 6150B PROFILE SAFETY

Couplings



Male, BSPP

1014	Thread
LE-9401U06 13	1/4"
LE-9401U06 17	3/8"
LE-9401U06 21	1/2"
Tech Sheet 1344	



Male, BSPT

1014	Thread
LE-9405U06 13	1/4"
LE-9405U06 17	3/8"
LE-9405U06 21	1/2"
Tech Sheet 1344	



Hose Tail

1014	To Suit Hose ID mm
LE-9421U06 06	6
LE-9421U06 08	8
LE-9421U06 10	10
Tech Sheet 1344	



Female, BSPP

1014	Thread
LE-9414U06 13	1/4"
LE-9414U06 17	3/8"
LE-9414U06 21	1/2"
Tech Sheet 1344	

Plugs



Male, BSPP

1014	Thread
LE-9087U06 13	1/4"
LE-9087U06 17	3/8"
LE-9087U06 21	1/2"
Tech Sheet 1344	



Hose Tail

1014	To Suit Hose ID mm
LE-9094U06 06	6
LE-9094U06 08	8
LE-9094U06 10	10
Tech Sheet 1344	



Female, BSPP

1014	Thread
LE-9086 23 13	1/4"
LE-9086 23 21	1/2"
Tech Sheet 1344	

C9000 ADVANCED QUICK ACTING COUPLERS - EURO PROFILE SAFETY

Couplings



Male, BSPP

1014	Thread
LE-9401E07 13	1/4"
LE-9401E07 17	3/8"
LE-9401E07 21	1/2"
Tech Sheet 1344	



Hose Tail

1014	Thread
LE-9421E07 10	10
LE-9421E07 13	13
Tech Sheet 1344	



Female, BSPP

1014	Thread
LE-9414E07 13	1/4"
LE-9414E07 17	3/8"
LE-9414E07 21	1/2"
Tech Sheet 1344	

Plugs



Male, BSPP

1014	Thread
LE-9087E07 17	3/8"
LE-9087E07 21	1/2"
Tech Sheet 1344	



Hose Tail

1014	To Suit Hose ID mm
LE-9094E07 08	8
LE-9094E07 10	10
LE-9094E07 13	13
Tech Sheet 1344	



Female, BSPP

1014	Thread
LE-9086 25 13	1/4"
LE-9086 25 17	3/8"
LE-9086 25 21	1/2"
Tech Sheet 1344	

Fluid-Air Components Ltd

SERIES 10/11 MOLDTITE

Working Temperature:
-15°C to +200°C
Standard seal FKM

Maximum Static Working Pressure:
PB 15 bar (217 PSI)
Safety factor of 4 to 1



Material:
Brass

Application:
Mold coupling



Profile

Couplings



Straight Hose Tail, 9mm Profile, with Valve

0194	To Suit Hose ID
2053-5613	9mm (3/8")

Straight Hose Tail, 13mm Profile, with Valve

0194	To Suit Hose ID
2053-5639	13mm (1/2")



Straight Hose Tail, 13mm Profile, Straight Through

0194	To Suit Hose ID
2053-5621	13mm (1/2")



45° Hose Tail, 13mm Profile, Non-valved

0194	To Suit Hose ID
2053-5662	13mm (1/2")



90° Hose Tail, 9mm Profile, Valved

0194	To Suit Hose ID
2053-5696	9mm (3/8")

90° Hose Tail, 13mm Profile, Valved

0194	To Suit Hose ID
2053-5712	13mm (1/2")

ambersil



For **Maintenance Sprays** see pages **1570-1577**

Non-valved, Straight Through Plugs



Male Thread, BSPT, 9mm Profile

0194	Thread
2053-5746	1/8"

Male Thread, BSPT, 13mm Profile

0194	Thread
2053-5761	1/4"

Valved Shut-off Plug



Male Thread, BSPT, 9mm Profile

0194	Thread
2053-5787	1/4"

Male Thread, BSPT, 13mm Profile

0194	Thread
2053-5795	3/8"

Other materials, seals and finishes available on request, please contact our technical department for further details.

Fluid-Air Components Ltd

QUICK COUPLINGS FOR PLASTIC INJECTION MOULDING

Working Temperature: -15°C to +110°C
(when using identification collets 513 and 523
Working Temperature: 0°C to +200°C (when using without identification collets 513 and 523

Maximum Working Pressure:
15 bar (1.5Mpa).

These Couplings are designed to be connected with cooling systems of plastic injection mouldings. They have a particular structure that assures reduced Size and allows coupling using a single hand.

Temperature and Pressures:
The working pressures and working temperatures depend on the type of tube used; therefore the values must be determined in accordance with the tubes features. The following values apply only to Aignep products.

- Parallel gas in conformity with ISO 228.
- Water, cooling water, oil.
- Flexible tubes in plastic and rubber.

410-510 DN8 Series



412 Straight Female Socket, BSPP

0220	Thread
412-1/4	1/4"
Tech Sheet 20602	



415 Straight Female Socket with Hose Tail

0220	To Suit Hose ID mm
415-08	8
415-10	10
415-12	12
Tech Sheet 20602	



416 135° Socket

0220	To Suit Hose ID mm
416-08	8
416-12	12
Tech Sheet 20602	



418 90º Female Socket

0220	To Suit Hose ID mm
418-10	10
418-12	12
Tech Sheet 20602	



511 Female Plug, BSPP

0220	Thread
511-18	1/8"
511-14	1/4"
511-38	3/8"
Tech Sheet 20602	



513 Collets to suit 511 Female Plugs

0220	Colour
513-RED	Red
513-BLUE	Blue
Tech Sheet 20602	

420-520 DN12 Series



422 Straight Female Socket, BSPP

0220	Thread
422-12	1/2"
Tech Sheet 20602	



425 Straight Female Socket with Hose Tail

0220	To Suit Hose ID mm
425-13	13
425-16	16
Tech Sheet 20602	



521 Female Plug, BSPP

0220	Thread
521-38	3/8"
521-12	1/2"
Tech Sheet 20602	



523 Collets, to suit 521 Female Plugs

0220	Colour
523-RED	Red
Tech Sheet 20602	

Fluid-Air Components Ltd

ACETAL RESIN QUICK RELEASE COUPLINGS

The special quick connector offers a fast and reliable push-to-connect mechanism. The outer sleeve locks the plug into the socket. When the plug is disconnected, the socket acts as a shut-off valve. Various plugs can be connected and used, suitable for hydraulic or pneumatic systems.

Temperature: 4 to 90°C

Working Pressure: Up to 14 bar (200 psi) at 20°C

Part	Material
Body	Nylon 6-6
Internal parts	Acetal
Spring & ball	Stainless steel

Couplings



Female Thread, BSPT

0497	Thread
81000	1/4"

Plugs



Male Thread, BSPT

0497	Thread
81400	1/4"



Female Thread, BSPT

0497	Thread
81500	1/4"



Hose Tail

0497	To Suit Hose ID mm
81606	6
81608	8
81610	10
81612	12

For **Tefen Nylon Hose Tails**
see page **1150**



Fluid-Air Components Ltd

AIR LINE COUPLINGS

Airflow Air Line Couplings (Fixed Application

- Suitable for fixed applications where the coupling is used over a workbench and a single action is preferred
- Compatible with the Standard Air Line plugs
- Steel Construction – robust and hard wearing, ideal for use in the engineering/workshop environment
- Benchmark in the UK for quality and reliability

Interchangeability: Rectus 19
Nominal Bore: 4.8mm

Working Temperature: -40°C to +100°C

Maximum Working Pressure: 14 bar



Male Thread, BSPT

7001	Thread
AC21CM02	1/4"
AC21EM02	3/8"
AC21JM02	1/2"
Tech Sheet 20603	



Female Thread, BSPP

7001	Thread
AC21CF02	1/4"
AC21EF02	3/8"
AC21JF02	1/2"
Tech Sheet 20603	



Hose Tail

7001	To Suit Hose ID
AC21R02	6mm (1/4")
AC21S02	8mm (5/16")
AC21T02	10mm (3/8")
Tech Sheet 20603	

Twin Coupling, Airflo

- Single action - designed for FIXED applications
- Compatible with Standard Adaptors
- Steel Construction - robust and hard-wearing, ideal for use in the engineering/workshop environment
- Positive locking mechanism
- British Standard Profil



'Y' 2 x Coupling, 1 x Plug

7001
AC6103
Tech Sheet 20606

Vertex Air Line Couplings (Trailing Hose Application)

- Double action mechanism
- Ideal where operators are using air tools or handheld inflators for trailing hose application
- Compatible with the Standard Air Line plugs
- Steel Construction – robust and hard wearing, ideal for use in the engineering/workshop environment

Interchangeability: Rectus 19
Nominal Bore: 4.8mm

Working Temperature: -40°C to +100°C

Maximum Working Pressure: 14 bar



Male Thread, BSPT

7001	Thread
AC91CM	1/4"
AC91EM	3/8"
AC91JM	1/2"
Tech Sheet 20603	



Female Thread, BSPP

7001	Thread
AC91CF	1/4"
AC91EF	3/8"
AC91JF	1/2"
Tech Sheet 20603	



Hose Tail

7001	Thread
AC91R	7mm (1/4")
AC91S	8mm (5/16")
AC91T	10mm (3/8")
Tech Sheet 20603	

Fluid-Air Components Ltd

AIR LINE COUPLINGS

Safeflow Safety Coupling

Compatible with the Standard Air Line plugs
Enhances workshop safety; prevents hose whip
Nominal Bore: 4.8mm

Maximum flow rate 43cfm at 100lbf/in²
Approvals: conforms to ISO 4414:1998 and EN 983:1996
Interchangeability: Rectus 19

Maximum Working Pressure: 200lbf/in² (14 bar)

5 YEARS EXTENDED WARRANTY



Male Thread, BSPT

7001	Thread
SC21CM	1/4"
SC21EM	3/8"
SC21JM	1/2"
Tech Sheet 20605	

5 YEARS EXTENDED WARRANTY



Female Thread, BSPP

7001	Thread
SC21CF	1/4"
SC21EF	3/8"
SC21JF	1/2"
Tech Sheet 20605	

Standard Air Line Plugs

- For use with all PCL Airflo , Vertex and Safeflow Coupling
- Steel Construction – robust and hard wearing, ideal for use in the engineering/workshop environment

Interchangeability: Rectus 19
Nominal Bore: 4.8mm


Working Temperature: -40°C to +100°C

Maximum Working Pressure: 14 bar



Male Thread, BSPT

7001	Thread
ACA2593	1/4"
ACA6909	3/8"
ACA6584	1/2"
Tech Sheet 20604	



Female Thread, BSPP

7001	Thread
ACA2746	1/4"
ACA6582	3/8"
ACA6583	1/2"
Tech Sheet 20604	



Hose Tail

7001	To Suit Hose ID
ACA1793	6mm (1/4")
ACA2487	8mm (5/16")
ACA2488	10mm (3/8")
Tech Sheet 20604	

Coupling Kit

Designed for the service engineer, or to keep in a workshop in case of a pneumatic air line failure, this small, compact kit contains all the parts you need to repair any standard air line failure.

Contents:

- 1 x AC91CM, AC91CF, HC6560, HC6892, HC6893, HC5656, HC1217, HC2479, HC6895, HC6896 and PTFE tape
- 2 x ACA2593, ACA2746, OOO and OO



Emergency Coupling Kit

7000
ACKIT01

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR LINE COUPLINGS

60 Series Air Line Couplings

- Hardened shoulder helps prevent accidental disconnection
- Swivel feature prevents kinking of the hose
- Ideal for fixed and trailing hose applications in garage, tyre shop and industrial environments

Working Temperature: -40°C to +100°C

Maximum Working Pressure: 14 bar

Nominal Bore: 7.1mm



Male Thread, BSPT

7000	Thread
AC4CM02	1/4"
AC4EM02	3/8"
AC4JM02	1/2"
Tech Sheet 20606	



Female Thread, BSPP

7000	Thread
AC4CF02	1/4"
AC4EF02	3/8"
AC4JF02	1/2"
Tech Sheet 20606	

60 Series Air Line Plugs



Male Thread, BSPT

7000	Thread
ACA2657	1/4"
ACA2661	3/8"
Tech Sheet 20606	



Female Thread, BSPP

7000	Thread
ACA2653	1/4"
ACA2660	3/8"
Tech Sheet 20606	



Hose Tail

7000	To Suit Hose ID
ACA2654	8mm (5/16")
ACA2658	10mm (3/8")
ACA2659	13mm (1/2")
Tech Sheet 20606	

100 Series Air Line Couplings

- Hardened shoulder helps prevent accidental disconnection
- Swivel feature prevents kinking of the hose
- Specially designed valves and large aperture adaptors provide increased airflow for heavy duty application

Ideal for larger air tool applications in garage and tyre shop environments

Nominal Bore: 10.3mm

Working Temperature: -40°C to +100°C

Maximum Working Pressure: 14 bar



Male Thread, BSPT

7000	Thread
AC5EM02	3/8"
AC5JM02	1/2"
Tech Sheet 20607	



Female Thread, BSPP

7000	Thread
AC5EF02	3/8"
AC5JF02	1/2"
Tech Sheet 20607	

100 Series Air Line Plugs



Male Thread, BSPT

7000	Thread
ACA2999	3/8"
ACA3035	1/2"
Tech Sheet 20607	



Female Thread, BSPP

7000	Thread
ACA2994	3/8"
Tech Sheet 20607	



Hose Tail

7000	To Suit Hose ID
ACA3037	10mm (3/8")
ACA3036	13mm (1/2")
Tech Sheet 20607	

Fluid-Air Components Ltd

AIR LINE COUPLINGS

Mini Couplings

- Small-bore couplings has proved popular in the robotics, medical, instrumentation and automation industries
- Lightweight and compact design
- Brass chrome plated

Nominal Bore: 5.0mm
Flow rate @ 6 bar (0.5 bar P.D.) 560 L/min

Interchangeability:
Camozzi Mini, Legris 21, Norgren 233, Rectus 21 and Schrader Mini

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
35 bar (508 psi)




Male Thread, BSPP

7000	Thread
AC11AM	1/8"
AC11CM	1/4"
Tech Sheet 10662	



Female Thread, BSPP


7000	Thread
AC11AF	1/8"
AC11CF	1/4"
Tech Sheet 10662	



Hose Tail

7000	To Suit Hose ID
AC1106	6mm (1/4")
AC1109	9mm
Tech Sheet 10662	

Mini Plugs



Male Thread, BSPP

7000	Thread
AA11AM	1/8"
AA11CM	1/4"
Tech Sheet 10662	



Female Thread, BSPP

7000	Thread
AA11AF	1/8"
AA11CF	1/4"
Tech Sheet 10662	



Hose Tail

7000	To Suit Hose ID
AA1106	6mm (1/4")
AA1109	9mm
Tech Sheet 10662	

For **PCL Ergo Extreme Blow Guns**
see page **1605**



Fluid-Air Components Ltd

AIR LINE COUPLINGS

XF-Euro Couplings

- High flow rate of 130 cfm @ 100 ps
- Hardened steel construction with corrosive resistant finis
- Steel shoulder helps prevent accidental disconnection
- Enhances tool efficienc
- Compatible with XF-Euro profile adaptor

Nominal Bore: 7.4 mm
Flow rate @ 6 bar (0.5 bar P.D.)
2200 L/min

Interchangeability:
Legris 25/26, Norgen 234/238, Rectus 25/26 and Schrader InterCheck 35

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
35 bar (508 psi)



Male Thread, BSPT

7000	Thread
AC71CM	1/4"
AC71EM	3/8"
AC71JM	1/2"
Tech Sheet 10663	



Female Thread, BSPP

7000	Thread
AC71CF	1/4"
AC71EF	3/8"
AC71JF	1/2"
Tech Sheet 10663	



Hose Tail

7000	To Suit Hose ID
AC7106	6mm (1/4")
AC7108	8mm (5/16")
AC7109	9mm
AC7110	10mm (3/8")
AC7113	13mm (1/2")
Tech Sheet 10663	

XF-Euro Safety Couplings

Maximum Working Pressure:
16 bar

Nominal Bore: 7.4mm
Flow Rate @ 6 bar (0.5 Bar P.D.) 1750 l/min

Designed to conform with compressed air Health and Safety Guide HS(G)39 and ISO 4414:2010



Male Thread, BSPT

7000	Thread
AS71CM	1/4"
AS71EM	3/8"
AS71JM	1/2"
Tech Sheet 10664	



Female Thread, BSPP

7000	Thread
AS71CF	1/4"
AS71EF	3/8"
AS71JF	1/2"
Tech Sheet 10664	

XF-Euro Plugs



Male Thread, BSPT

7000	Thread
AA7101	1/8"
AA7102	1/4"
AA7103	3/8"
AA7104	1/2"
Tech Sheet 10663	



Female Thread, BSPP

7000	Thread
AA7105	1/8"
AA7106	1/4"
AA7107	3/8"
AA7108	1/2"
Tech Sheet 10663	



Hose Tail

7000	To Suit Hose ID
AA7109	4mm
AA7110	6mm (1/4")
AA7111	8mm (5/16")
AA7114	9mm
AA7112	10mm (3/8")
AA7113	13mm (1/2")
Tech Sheet 10663	

Fluid-Air Components Ltd

AIR LINE COUPLINGS

PF Couplings

- Competitive alternative to Schrader Couplings and Adaptors
- Steel Construction with corrosive resistant finish for longer life
- Superior flow characteristics

Nominal Bore: 5.0mm
Flow rate @ 6 bar (0.5 bar P.D.) 2200 L/min

Interchangeability:
Rectus 17 and Schrader Standard

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
35 bar (508 psi)



Male Thread, BSPT

7000	Thread
AC77CM	1/4"
AC77EM	3/8"
AC77JM	1/2"
Tech Sheet 10665	



Female Thread, BSPP


7000	Thread
AC77CF	1/4"
AC77EF	3/8"
AC77JF	1/2"
Tech Sheet 10665	



Hose Tail


7000	To Suit Hose ID
AC7706	6mm (1/4")
AC7708	8mm (5/16")
AC7710	10mm (3/8")
AC7713	13mm (1/2")
Tech Sheet 10665	

PF Plugs



Male Thread, BSPT

7000	Thread
AA7702	1/4"
AA7703	3/8"
Tech Sheet 10665	



Female Thread, BSPP

7000	Thread
AA7706	1/4"
AA7707	3/8"
Tech Sheet 10665	



Hose Tail

7000	To Suit Hose ID
AA7710	6mm (1/4")
AA7711	8mm (5/16")
AA7712	10mm (3/8")
Tech Sheet 10665	



Fluid-Air Components Ltd

AIR LINE COUPLINGS

ISO B12 Couplings

- Commonly used in Scandinavian markets, where this adaptor profile is required
- Steel Construction with corrosive resistant finish for longer life
- Steel shoulder helps prevent accidental disconnection

Nominal Bore: 5.5mm
Flow rate @ 6 bar (0.5 bar P.D.) 1100 L/min

Interchangeability:
Rectus 23/24, Hanson 3000 and Legris 24

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
35 bar (508 psi)



Male Thread, BSPT

7000	Thread
AC75CM	1/4"
AC75EM	3/8"
AC75JM	1/2"
Tech Sheet 10667	



Female Thread, BSPP

7000	Thread
AC75CF	1/4"
AC75EF	3/8"
AC75JF	1/2"
Tech Sheet 10667	



Hose Tail


7000	To Suit Hose ID
AC7506	6mm (1/4")
AC7508	8mm (5/16")
AC7510	10mm (3/8")
AC7513	13mm (1/2")
Tech Sheet 10667	

ISO B12 Plugs



Male Thread, BSPT

7000	Thread
AA7502	1/4"
AA7503	3/8"
AA7504	1/2"
Tech Sheet 10667	



Female Thread, BSPP

7000	Thread
AA7506	1/4"
AA7507	3/8"
Tech Sheet 10667	



Hose Tail

7000	To Suit Hose ID
AA7510	6mm (1/4")
AA7512	10mm (3/8")
AA7513	13mm (1/2")
Tech Sheet 10667	

PORTWEST



Fluid-Air Components Ltd

AIR LINE COUPLINGS

"A"Style Couplings

- Commonly used in American and most African markets where this specific profile of adapto is required
- Steel Construction with corrosive resistant finish for longer lif

Nominal Bore: 5.5mm
Flow rate @ 6 bar (0.5 bar P.D.) 650 L/min

Interchangeability:
ARO 210, JWL 522/532, Rectus 14/22 and Schrader Euro

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
14 bar



Male Thread, BSPT

7000	Thread
AC61CM	1/4"
AC61EM	3/8"
AC61JM	1/2"
Tech Sheet 10668	



Female Thread, BSPP

7000	Thread
AC61CF	1/4"
AC61EF	3/8"
AC61JF	1/2"
Tech Sheet 10668	



Hose Tail

7000	To Suit Hose ID
AC61R	6mm (1/4")
AC61S	8mm (5/16")
AC61T	10mm (3/8")
Tech Sheet 10668	

"A" Style Plugs



Male Thread, BSPT

7000	Thread
ACA6923	1/4"
Tech Sheet 10668	



Female Thread, BSPP

7000	Thread
ACA6924	1/4"
Tech Sheet 10668	



Hose Tail

7000	To Suit Hose ID
ACA6912	6mm (1/4")
ACA6922	8mm (5/16")
ACA6930	10mm (3/8")
Tech Sheet 10668	

FT PRO



For **FT PRO Flow Regulators** see page **1160**

Fluid-Air Components Ltd

AIR LINE COUPLINGS

KF Couplings

- Ideal for portable air tool and industrial applications
- Excellent flow characteristic
- Commonly used in Asian and Oceania markets where this adaptor profile is required
- Steel Construction with corrosive resistant finish for longer life

Nominal Bore: 7.6mm
Flow rate @ 6 bar (0.5 bar P.D.)
2100 L/min

Interchangeability
Nitto Kohki 200 and Rectus 13

Working Temperature:
-40°C to +100°C

Maximum Working Pressure:
35 bar (508 psi)



Male Thread, BSPT

7000	Thread
AC78CM	1/4"
AC78EM	3/8"
AC78JM	1/2"
Tech Sheet 10669	



Female Thread, BSPP

7000	Thread
AC78CF	1/4"
AC78EF	3/8"
AC78JF	1/2"
Tech Sheet 10669	



Hose Tail


7000	To Suit Hose ID
AC7806	6mm (1/4")
AC7808	8mm (5/16")
AC7810	10mm (3/8")
AC7813	13mm (1/2")
Tech Sheet 10669	

KF Plugs



Male Thread, BSPT

7000	Thread
AA7802	1/4"
AA7803	3/8"
AA7804	1/2"
Tech Sheet 10669	



Female Thread, BSPP

7000	Thread
AA7806	1/4"
AA7807	3/8"
AA7808	1/2"
Tech Sheet 10669	



Hose Tail

7000	To Suit Hose ID
AA7810	6mm (1/4")
AA7811	8mm (5/16")
AA7812	10mm (3/8")
AA7813	13mm (1/2")
Tech Sheet 10669	

Multi-Fit Couplings

- Has the additional flexibility of accepting 3 key adaptor profiles; XF-Euro, "A" Style and ISO B12
- Steel Construction with corrosive resistant finish for longer lif
- Offers enhanced tool efficienc

Nominal Bore: 5.0mm
Flow rate @ 6 bar (0.5 bar P.D.)
1800 L/min
Coupling can be used in conjunction with any of the following plugs ISO B12, XF, and Euro

Interchangeability:
Rectus 23/25/26, Hanson 3000 and Dynaquip DC 3

Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
35 bar (508 psi)



Male Thread, BSPT

7000	Thread
AC73CM	1/4"
AC73EM	3/8"
AC73JM	1/2"
Tech Sheet 10666	



Female Thread, BSPP

7000	Thread
AC73CF	1/4"
AC73EF	3/8"
AC73JF	1/2"
Tech Sheet 10666	



Hose Tail

7000	To Suit Hose ID
AC7306	6mm (1/4")
AC7308	8mm (5/16")
AC7310	10mm (3/8")
AC7313	13mm (1/2")
Tech Sheet 10666	

Fluid-Air Components Ltd

INSTANTAIR COUPLINGS

- Bayonet type quick acting couplings to maximum efficiency and prevent accidental uncoupling
- Zinc plated steel / Brass chrome plated

Nominal Bore: 5.6mm

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 17 bar

Steel Zinc Plated Instantair Couplings



Male Thread, BSPT

7000	Broomwade Reference	Thread
AC51CM	PT8825	1/4"
AC51EM	PT8827	3/8"
AC51JM	PT9095	1/2"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thread
AC51CF	PT8823	1/4"
AC51EF	PT8800	3/8"
AC51JF	PT9096	1/2"
Tech Sheet 536		



Hose Tail

7000	Broomwade Reference	To Suit Hose ID
AC51R	PT8800/SU4	6mm (1/4")
AC51S	PT8800/SU5	8mm (5/16")
AC51T	PT8800/SU6	10mm (3/8")
Tech Sheet 536		

Steel Zinc Plated Instantair Adaptors



Male Thread, BSPP

7000	Broomwade Reference	Thread
AA5102	PT8808	1/4"
AA5103	PT8817	3/8"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thread
AA5106	PT8806	1/4"
AA5107	PT8802	3/8"
Tech Sheet 536		



Hose Tail

7000	Broomwade Reference	To Suit Hose ID
AA5110	PT8802/SU4	6mm (1/4")
AA5111	PT8802/SU5	8mm (5/16")
AA5112	PT8802/SU6	10mm (3/8")
Tech Sheet 536		

Steel Zinc Plated Instantair Swivel Adaptors



Male Thread, BSPP

7000	Broomwade Reference	Thread
AA5302	PT8836	1/4"
AA5303	PT8838	3/8"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thread
AA5306	PT8834	1/4"
AA5307	PT8804	3/8"
Tech Sheet 536		



Hose Tail

7000	Broomwade Reference	To Suit Hose ID
AA5310	PT8804/SU4	6mm (1/4")
AA5312	PT8804/SU6	10mm (3/8")
Tech Sheet 536		

Fluid-Air Components Ltd

INSTANTAIR COUPLINGS

Brass Chrome Plated Instantair Couplings



Male Thread, BSPP

7000	Broomwade Reference	Thread
AC52CM	PT8826	1/4"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thread
AC52CF	PT8824	1/4"
Tech Sheet 536		

INSTANTAIR COUPLINGS

- 1/2" Instantair Couplings and Adaptors are not interchangeable with the Standard Instantair range
- Offer higher flow characteristics, they are ideal for heavy duty industrial applications

Nominal Bore: 8mm

Maximum Working Pressure:
17 bar

Steel Zinc Plated Instantair 1/2" Couplings



Male Thread, BSPP

7000	Broomwade Reference	Thread
AC59JM	PT8811	1/2"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thread
AC59JF	PT8812	1/2"
Tech Sheet 536		



Hose Tail

7000	Broomwade Reference	To Suit Hose ID
AC59V	PT8813	13mm (1/2")
Tech Sheet 536		

Steel Zinc Plated Instantair 1/2" Swivel Adaptors



Male Thread, BSPP

7000	Broomwade Reference	Thred
AA5904	PT8820	1/2"
Tech Sheet 536		



Female Thread, BSPP

7000	Broomwade Reference	Thred
AA5908	PT8821	1/2"
Tech Sheet 536		



Hose Tail

7000	Broomwade Reference	To Suit Hose ID
AA5913	PT8819	13mm (1/2")
Tech Sheet 536		

Fluid-Air Components Ltd

OETIKER RANGES

19 Series SC Type P Couplings



Male Thread, BSPP

0550	Thread
20500434	1/4"
20500441	3/8"
20500442	1/2"



Female Thread, BSPP

0550	Thread
20500438	1/4"
20500439	3/8"
20500440	1/2"



Hose Tail

0550	To Suit Hose ID
20500443	1/4"
20500444	5/16"
20500445	3/8"

23 Series SC Type B1 Swing Couplings



Male Thread, BSPP

0551	Thread
20500314	1/4"
20500315	3/8"
20500316	1/2"



Female Thread, BSPP

0551	Thread
20500307	1/4"
20500308	3/8"
20500309	1/2"



Hose Tail

0551	To Suit Hose ID
20500320	1/4" (6mm)
20500321	5/16" (8mm)
20500322	3/8" (10mm)

25 & 26 Series SC Type C Swing Couplings



Male Thread, BSPP

0552	Thread
20500351	1/4"
20500352	3/8"
20500353	1/2"



Female Thread, BSPP


0552	Thread
20500345	1/4"
20500346	3/8"
20500347	1/2"



Hose Tail

0552	To Suit Hose ID
20500356	5/16"
20500357	3/8"
20500358	1/2"

FT PRO



For **Fueling Equipment & Accessories** see page **1620**

Fluid-Air Components Ltd

SERIES 'ST' STRAIGHT-THROUGH COUPLINGS

Working Temperature:
-40°C to +100°C

Working Pressure (PSI) Series 'ST'

Size	Steel Plug	Brass Plug	All Stainless
1/8"	2,600	2,500	4,200
1/4"	5,500	5,200	6,700
3/8"	3,500	2,700	5,500
1/2"	2,700	2,200	-
3/4"	1,700	1,700	-

Standard Seals: Nitrile
Only couplings and plugs of the same size, will interchange.
Interchangeability: Hansen ST

Couplings



Brass, Male Thread, NPTF

8110	Thread	Length mm
TB1S-10	1/8"	27
TB2S-15	1/4"	44
TB3S-20	3/8"	45
TB4S-25	1/2"	52
TB6S-30	3/4"	57
Tech Sheet 535		

stainless steel



Stainless Steel, Male Thread, NPTF

8110	Thread	Length mm
T2S-15-303	1/4"	44
T3S-20-303	3/8"	45
Tech Sheet 535		



Brass, Female Thread, NPTF

8110	Thread	Length mm
TB1S-11	1/8"	27
TB2S-16	1/4"	39
TB3S-21	3/8"	41
TB4S-26	1/2"	48
TB6S-31	3/4"	52
Tech Sheet 535		

stainless steel



Stainless Steel, Female Thread, NPTF

8110	Thread	Length mm
T1S-11-303	1/8"	27
T2S-16-303	1/4"	39
Tech Sheet 535		

Plugs



Brass, Male Thread, NPTF

8110	Thread
TB1T-10	1/8"
TB2T-15	1/4"
TB3T-20	3/8"
TB4T-25	1/2"
TB6T-30	3/4"
Tech Sheet 535	



Brass, Female Thread, NPTF

8110	Thread
TB1T-11	1/8"
TB2T-16	1/4"
TB3T-21	3/8"
TB4T-26	1/2"
TB6T-31	3/4"
Tech Sheet 535	



Steel, Male Thread, NPTF

8110	Thread
T1T-10	1/8"
T4T-25	1/2"
Tech Sheet 535	



Steel, Female Thread, NPTF

8110	Thread
T2T-16	1/4"
T3T-21	3/8"
T6T-31	3/4"
Tech Sheet 535	

stainless steel



Stainless Steel, Male Thread, NPTF

8110	Thread
T1T-10-303	1/8"
T2T-15-303	1/4"
Tech Sheet 535	

Fluid-Air Components Ltd

AIR BRAKE COMPONENTS

British Standard BS AU138B 2000, Air Line Couplings



Male, Emergency

0042	Thread
18-980/1	M22
Tech Sheet 20608	



Combined Male with Self Sealing Valve, Service

0042	Thread
18-978/1	M16
18-982/1	M22
Tech Sheet 20608	



Combined Female with Self Sealing Valve, Emergency


0042	Thread
18-979/1	M16
18-981/1	M22
Tech Sheet 20608	



Female with Lift Valve, Service

0042	Thread
18-983/1	M22
Tech Sheet 20608	

Quality Assured, Air Line Couplings



Self Sealing Valve


0042	Thread
18-868/1	M22 x 1.5
Tech Sheet 20610	



Operating Plug

0042	Thread
18-867/1	M22 x 1.5
Tech Sheet 20610	

Air Line Couplings



Self Sealing Valve


0042	Thread
18-868	M22 x 1.5
SSVC-12	1/2"
Tech Sheet 20609	



Operating Plug

0042	Thread
18-867	M22 x 1.5
OSC-12	1/2"
Tech Sheet 20609	

Emergency Couplings



Self Sealing Valve for C or CA Coupling

0042	Thread
SSV-12	1/2"
Tech Sheet 20611	

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 4

Monitor & Test

4

4.01 Pressure Gauges 409-418

4.02 Temperature & Pressure Switches 419-429

4.03 Industrial Filtration 430-435

4.04 Sight Glasses & Flow Switches 436-445

4.05 Thermometers for Industry 446

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 4 Monitor & Test

4.01 Pressure Gauges

409-418

- Dry Pressure Gauges & Accessories
- Glycerine Gauges & Accessories
- Temperature Gauges
- HVAC Gauges & Accessories



4.02 Temperature & Pressure Switches

419-429

- Digital Flow Pressure Sensors
- Temperature Switches
- Pressure Transducers
- Adjustable Pressure Switches
- Pressure Switches
- Vacuum Switches
- Flow Sensors
- Pressure Sensors



4.03 Industrial Filtration

430-435

- Filters & Drains (Air, Water & Vacuum)
- Condensate Management
- Air Receivers & Accessories
- Reservoir Tanks
- Compressor Oil



4.04 Sight Glasses & Flow Switches

436-445


- Sight Glasses & Indicators
- Flow Switches
- Flow Indicators
- Variable Area Flow Meters
- Flow Meters
- Float Level Switches
- Liquid Level Gauges
- Visual Indicators
- Cold Water Flow Meters



4.05 Thermometers for Industry

446

- K Type Handheld Thermometers
- K Type Probes
- Room Thermometers
- Bimetal Indicators
- Dial Pipe Thermometers
- Magnetic Dial Thermometers



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Dry Pressure Gauges

FT Pro dry gauges are a market leading range offering a reliable solution for pressure monitoring within pneumatic systems.

Used extensively throughout the world's manufacturing facilities, all units have been 100% pressure tested and inspected, so quality can be guaranteed.

Applications:

- Construction
- Chemical
- Agriculture
- Offshore
- Mining
- Automotive
- OEM machine
- Rail building
- Industrial



Fluid-Air Components Ltd

DRY GAUGES

Steel Case, Centre Back Connection

- Robust metal case
- Brass thread
- BSP taper



BSPT Brass Connection

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2018-1681	1/8"	40	0-15	0-1
2018-1699	1/8"	40	0-30	0-2
2018-1707	1/8"	40	0-60	0-4
2018-1723	1/8"	40	0-100	0-6
2018-1731	1/8"	40	0-160	0-10
2018-1749	1/8"	40	0-200	0-12
2018-1756	1/8"	40	0-300	0-20
2018-1764	1/8"	50	0-15	0-1
2018-1772	1/8"	50	0-30	0-2
2018-1780	1/8"	50	0-60	0-4
2018-1798	1/8"	50	0-100	0-6
2018-1806	1/8"	50	0-160	0-10
2018-1814	1/8"	50	0-200	0-12
2018-1822	1/8"	50	0-300	0-20
Tech Sheet 20581				

BSPT Brass Connection

0236	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PGR050114	1/4"	50	0-15	0-1
PGR050314	1/4"	50	0-30	0-2
PGR050414	1/4"	50	0-60	0-4
PGR050614	1/4"	50	0-100	0-6
PGR051014	1/4"	50	0-160	0-10
PGR051214	1/4"	50	0-200	0-12
PGR052014	1/4"	50	0-300	0-20
PGR060114	1/4"	63	0-15	0-1
PGR061014	1/4"	63	0-160	0-10
PGR061214	1/4"	63	0-200	0-12
PGR062014	1/4"	63	0-300	0-20
Tech Sheet 20581				



Panel Mount Brackets, to suit Steel Dry Gauges

0338	To Suit mm
KPMB40R	40
KPMB50R	50

ABS Case, Bottom Connection



BSPT Brass Connection

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G50-01B	1/8"	50	0-15	0-1
G50-02B	1/8"	50	0-30	0-2
G50-04B	1/8"	50	0-60	0-4
G50-06B	1/8"	50	0-100	0-6
G50-10B	1/8"	50	0-160	0-10
G50-12B	1/8"	50	0-200	0-12
G50-01C	1/4"	50	0-15	0-1
G50-02C	1/4"	50	0-30	0-2
G50-025C	1/4"	50	0-40	0-2.5
G50-04C	1/4"	50	0-60	0-4
G50-06C	1/4"	50	0-100	0-6
G50-10C	1/4"	50	0-160	0-10
G50-12C	1/4"	50	0-200	0-12
G50-16C	1/4"	50	0-250	0-16
G63-01D	1/4"	63	0-15	0-1
G63-04D	1/4"	63	0-60	0-4
G100-04B	3/8"	100	0-60	0-4
G100-06B	3/8"	100	0-100	0-6
G100-10B	3/8"	100	0-160	0-10
G100-14B	3/8"	100	0-200	0-14
Tech Sheet 20582				

ABS Case, Centre Back Connection



BSPT Brass Connection

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G40-01R	1/8"	40	0-15	0-1
G40-02R	1/8"	40	0-30	0-2
G40-04R	1/8"	40	0-60	0-4
G40-06R	1/8"	40	0-100	0-6
G40-07R	1/8"	40	0-100	0-7
G40-10R	1/8"	40	0-160	0-10
G40-12R	1/8"	40	0-200	0-12
G40-16R	1/8"	40	0-250	0-16
G40-20R	1/8"	40	0-300	0-20
G50-01R	1/8"	50	0-15	0-1
G50-02R	1/8"	50	0-30	0-2
G50-04R	1/8"	50	0-60	0-4
G50-06R	1/8"	50	0-100	0-6
G50-10R	1/8"	50	0-160	0-10
G50-12R	1/8"	50	0-200	0-12
G50-16R	1/8"	50	0-250	0-16
G50-20R	1/8"	50	0-300	0-20
G50-02T	1/4"	50	0-30	0-2
G50-04T	1/4"	50	0-60	0-4
G50-06T	1/4"	50	0-100	0-6
G50-10T	1/4"	50	0-160	0-10
G50-12T	1/4"	50	0-200	0-12
G50-16T	1/4"	50	0-250	0-16
G50-20T	1/4"	50	0-300	0-20
G63-10T	1/4"	63	0-160	0-10
G63-12T	1/4"	63	0-200	0-12
G63-16T	1/4"	63	0-250	0-16
Tech Sheet 20584				

All pressure gauges can be supplied with a calibration certificate at a nominal charge. Please call our Business Development Team for price and delivery.

DRY GAUGES

Pressure Gauge Bottom Entry, Steel Case



BSPT Brass Connection

0236	Thread	Gauge Diameter mm	Pressure Range Bar
PGB050118	1/8"	50	0-1
PGB050318	1/8"	50	0-2
PGB050418	1/8"	50	0-4
PGB050618	1/8"	50	0-6
PGB051018	1/8"	50	0-10
PGB051418	1/8"	50	0-14
PGB052018	1/8"	50	0-20
PGB050114	1/4"	50	0-1
PGB050314	1/4"	50	0-2
PGB050414	1/4"	50	0-4
PGB050614	1/4"	50	0-6
PGB051014	1/4"	50	0-10
PGB051214	1/4"	50	0-12
PGB051414	1/4"	50	0-14
PGB052014	1/4"	50	0-20
PGB060114	1/4"	63	0-1
PGB060314	1/4"	63	0-2
PGB060414	1/4"	63	0-4
PGB061014	1/4"	63	0-10
PGB061214	1/4"	63	0-12
PGB062014	1/4"	63	0-20
PGB100138	3/8"	100	0-1
PGB100338	3/8"	100	0-2
PGB100438	3/8"	100	0-4
PGB100638	3/8"	100	0-6
PGB101038	3/8"	100	0-10
PGB101238	3/8"	100	0-12
PGB102038	3/8"	100	0-20

Flange Type Pressure Gauges, Centre Back Connection



BSPT Brass Connection

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2018-1830	1/4"	50	0-160	0-10
2018-1848	1/4"	50	0-200	0-12
Tech Sheet 20587				

Panel Mount, Stainless Steel Case, Centre Back Connection



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G50-12PM	1/8"	50	0-200	0-12
Tech Sheet 20588				

Panel Mount Gauge, Centre Back Connection



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range Bar
56144010	1/8"	40	0-10
56145010	1/8"	50	0-10
Tech Sheet 20386			

Panel Mount, Centre Back Connection



BPST

0236	Thread	Gauge Diameter mm	Pressure Range Bar	Pressure Range PSI
GCPM402	1/8"	40	0-2	0-30
GCPM404	1/8"	40	0-4	0-60
GCPM407	1/8"	40	0-6	0-100
GCPM4010	1/8"	40	0-11	0-160
GCPM4014	1/8"	40	0-14	0-200
GCPM4020	1/8"	40	0-20	0-300
GCPM502	1/8"	50	0-2	0-30
GCPM504	1/8"	50	0-4	0-60
GCPM507	1/8"	50	0-6	0-100
GCPM5010	1/8"	50	0-11	0-160
GCPM5014	1/8"	50	0-14	0-200

Panel Mounted Gauge, U Clamp, Back Entry



BSPP

0237	Thread	Gauge Diameter mm	Pressure Range Bar
VGBU040118	1/8"	40	-1-0
PGBU040418	1/8"	40	0-4
VGBU060114	1/4"	63	-1-0
PGBU061014	1/4"	63	0-10

Panel Mounted Gauge, Back Entry



BSPP

0237	Thread	Gauge Diameter mm	Pressure Range Bar
VGBP040118	1/8"	40	-1-0
PGBP040418	1/8"	40	0-4
PGBP040618	1/8"	40	0-6
PGBP041018	1/8"	40	0-10
PGBP041218	1/8"	40	0-12
VGBP060114	1/4"	63	-1-0
PGBP060414	1/4"	63	0-4
PGBP060614	1/4"	63	0-6
PGBP061014	1/4"	63	0-10
PGBP061214	1/4"	63	0-12

Vacuum Gauges, Panel Mount, Back Connection



BSPT

0236	Male Thread	Gauge Diameter mm	Max Pressure ar
GCVPM40/02	1/8"	40	-1
GCVPM50/02	1/8"	50	-1

DRY GAUGES

Capsule Gauges, Bottom Connection

1 Millibar = 0.001 bar



Millibar Scale, BSPT

0021	Thread	Gauge Diameter mm	Pressure Range Millibar
CG63-100B	1/4"	63	0-100
CG63-250B	1/4"	63	0-250
CG63-400B	1/4"	63	0-400
CG63-600B	1/4"	63	0-600
Tech Sheet 20586			

Welding Gauges, Oxygen, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range Bar	Pressure Range PSI
OG50-050	1/4"	50	0-5	0-80
OG50-010	1/4"	50	0-10	0-160
Tech Sheet 20590				

Welding Gauges, Acetylene, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range Bar	Pressure Range PSI
AG50-0015	1/4"	50	0-1.5	0-30
Tech Sheet 20592				

All Stainless Steel Dry Gauges, Bottom Connection



63mm Diameter, 1/4" BSPP

0021	Pressure Range PSI	Pressure Range Bar
SSG63-001B	0-15	0-1
SSG63-004B	0-60	0-4
SSG63-012B	0-200	0-12
SSG63-025B	0-400	0-25
SSG63-060B	0-1000	0-60
SSG63-200B	0-3000	0-200
SSG63-400B	0-6000	0-400
Tech Sheet 20589		

All Stainless Steel Dry Gauges, Centre Back Connection



63mm Diameter, 1/4" BSPP

0021	Pressure Range PSI	Pressure Range Bar
2038-8484	0-200	0-12
2038-8492	0-300	0-20
2038-8526	0-4000	0-250
Tech Sheet 20591		

Vacuum Gauges, Centre Back Connection



BSPT, ABS Case

0021	Thread	Gauge Diameter mm	Max Pressure Hg	Max Pressure Bar
VG40-01R	1/8"	40	-30	-1
VG50-01R	1/8"	50	-30	-1
VG50-01T	1/4"	50	-30	-1
VG63-01T	1/4"	63	-30	-1
VG100-01T	3/8"	100	-30	-1
Tech Sheet 20583				

stainless steel

Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GCV63/04D	1/4" BSPT	63	-1
GCV100/06D	3/8" BSPT	100	-1

Vacuum Gauges, Bottom Connection



BSPT, ABS Case

0021	Thread	Gauge Diameter mm	Max Pressure Hg	Max Pressure Bar
VG40-01B	1/8"	40	-30	-1
VG50-01B	1/8"	50	-30	-1
VG50-01C	1/4"	50	-30	-1
VG63-01C	1/4"	63	-30	-1
VG100-01D	3/8"	100	-30	-1
Tech Sheet 20585				

stainless steel

Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GBV63/04D	1/4" BSPT	63	-1
GBV100/06D	3/8" BSPT	100	-1

DRY GAUGES

ABS Case, Centre Back Connection

Accuracy:
40mm and 50mm diameter: +/- 2.5%



BSPT

0056	Thread	Gauge Diameter mm	Max Pressure PSI	Max Pressure Bar
WG40-18R-1	1/8"	40	15	1
WG40-18R-2.5	1/8"	40	40	2.5
WG40-18R-4	1/8"	40	60	4
WG40-18R-6	1/8"	40	90	6
WG40-18R-10	1/8"	40	160	10
WG40-18R-16	1/8"	40	230	16
WG40-18R-25	1/8"	40	400	25
WG50-18R-1	1/8"	50	15	1
WG50-18R-2.5	1/8"	50	40	2.5
WG50-18R-4	1/8"	50	60	4
WG50-18R-6	1/8"	50	90	6
WG50-18R-10	1/8"	50	160	10
WG50-18R-16	1/8"	50	230	16
WG50-18R-25	1/8"	50	400	25
Tech Sheet 10524				

Flush Panel Mount, Centre Back Connection



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar
WG63-14FPM-1BAR	1/4"	63	1
WG63-14FPM-2BAR	1/4"	63	2
WG63-14FPM-4BAR	1/4"	63	4
WG63-14FPM-7BAR	1/4"	63	7
WG63-14FPM-11BAR	1/4"	63	11
WG63-14FPM-14BAR	1/4"	63	14
WG63-14FPM-20BAR	1/4"	63	20
WG63-14FPM-28BAR	1/4"	63	28
WG63-14FPM-40BAR	1/4"	63	40

Panel Mount Gauge Bracket



Bracket

0056	To Suit
WGB-63	63mm Rear
WGB-100	100mm Rear

ABS Case, Bottom Connection

Accuracy:
40mm and 50mm diameter: +/- 2.5%
63mm diameter: +/- 1.6%



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar
WG40-18B-1BAR	1/8"	40	1
WG40-18B-2BAR	1/8"	40	2
WG40-18B-14BAR	1/8"	40	14
WG50-18B-4BAR	1/8"	50	4
WG50-18B-7BAR	1/8"	50	7
WG50-18B-11BAR	1/8"	50	11
WG50-18B-14BAR	1/8"	50	14
WG50-18B-20BAR	1/8"	50	20
WG50-18B-40BAR	1/8"	50	40
WG50-18B-70BAR	1/8"	50	70
WG50-18B-200BAR	1/8"	50	200
WG63-14B-1BAR	1/4"	63	1
WG63-14B-2BAR	1/4"	63	2
WG63-14B-4BAR	1/4"	63	4
WG63-14B-7BAR	1/4"	63	7
WG63-14B-11BAR	1/4"	63	11
WG63-14B-14BAR	1/4"	63	14
WG63-14B-20BAR	1/4"	63	20
WG63-14B-28BAR	1/4"	63	28
WG63-14B-40BAR	1/4"	63	40
WG63-14B-70BAR	1/4"	63	70
WG63-14B-140BAR	1/4"	63	140
WG63-14B-400BAR	1/4"	63	400
Tech Sheet 10523			

Accuracy:
100mm diameter: +/- 1.0%



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar
WG100-38B-1BAR	3/8"	100	1
WG100-38B-2BAR	3/8"	100	2
WG100-38B-4BAR	3/8"	100	4
WG100-38B-7BAR	3/8"	100	7
WG100-38B-11BAR	3/8"	100	11
WG100-38B-14BAR	3/8"	100	14
WG100-38B-20BAR	3/8"	100	20
WG100-38B-28BAR	3/8"	100	28
WG100-38B-40BAR	3/8"	100	40
Tech Sheet 10523			

Fluid-Air Components Ltd

GLYCERINE GAUGES & ACCESSORIES

Stainless Steel Case, Bottom Connection

stainless steel



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001BG	1/4"	63	0-15	0-1
G63-002BG	1/4"	63	0-30	0-2
G63-004BG	1/4"	63	0-60	0-4
G63-006BG	1/4"	63	0-100	0-6
G63-012BG	1/4"	63	0-200	0-12
G63-020BG	1/4"	63	0-300	0-20
G63-025BG	1/4"	63	0-400	0-25
G63-040BG	1/4"	63	0-600	0-40
G63-060BG	1/4"	63	0-1000	0-60
G63-120BG	1/4"	63	0-2000	0-120
G63-200BG	1/4"	63	0-3000	0-200
G63-250BG	1/4"	63	0-4000	0-250
G63-400BG	1/4"	63	0-6000	0-400
G63-600BG	1/4"	63	0-9000	0-600
VG63-01BG	1/4"	63	-30" Hg	-1 bar
Tech Sheet 20593				

stainless steel



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001BG	1/4"	63	0-15	0-1
PG63-002BG	1/4"	63	0-30	0-2
PG63-004BG	1/4"	63	0-60	0-4
PG63-006BG	1/4"	63	0-100	0-6
PG63-012BG	1/4"	63	0-200	0-12
PG63-014BG	1/4"	63	0-200	0-14
PG63-020BG	1/4"	63	0-300	0-20
PG63-025BG	1/4"	63	0-400	0-25
PG63-040BG	1/4"	63	0-600	0-40
PG63-060BG	1/4"	63	0-1000	0-60
PG63-120BG	1/4"	63	0-2000	0-120
PG63-200BG	1/4"	63	0-3000	0-200
PG63-250BG	1/4"	63	0-4000	0-250
PG63-400BG	1/4"	63	0-6000	0-400
PG63-600BG	1/4"	63	0-9000	0-600
Tech Sheet 20594				

Stainless Steel Case, Centre Back Connection

See Panel Mount Bracket Options: G63-PM & G63-PM-RHOMB

stainless steel



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001RG	1/4"	63	0-15	0-1
G63-002RG	1/4"	63	0-30	0-2
G63-004RG	1/4"	63	0-60	0-4
G63-006RG	1/4"	63	0-100	0-6
G63-010RG	1/4"	63	0-160	0-10
G63-012RG	1/4"	63	0-200	0-12
G63-020RG	1/4"	63	0-300	0-20
G63-025RG	1/4"	63	0-400	0-25
G63-040RG	1/4"	63	0-600	0-40
G63-060RG	1/4"	63	0-1000	0-60
G63-120RG	1/4"	63	0-2000	0-120
G63-200RG	1/4"	63	0-3000	0-200
G63-250RG	1/4"	63	0-4000	0-250
G63-400RG	1/4"	63	0-6000	0-400
G63-600RG	1/4"	63	0-9000	0-600
VG63-01RG	1/4"	63	-30" Hg	-1 bar
Tech Sheet 20595				

See Panel Mount Bracket Options: G63-PM & G63-PM-RHOMB

stainless steel



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001RG	1/4"	63	0-15	0-1
PG63-002RG	1/4"	63	0-30	0-2
PG63-004RG	1/4"	63	0-60	0-4
PG63-006RG	1/4"	63	0-100	0-6
PG63-012RG	1/4"	63	0-200	0-12
PG63-020RG	1/4"	63	0-300	0-20
PG63-025RG	1/4"	63	0-400	0-25
PG63-040RG	1/4"	63	0-600	0-40
PG63-060RG	1/4"	63	0-1000	0-60
PG63-120RG	1/4"	63	0-2000	0-120
PG63-200RG	1/4"	63	0-3000	0-200
PG63-250RG	1/4"	63	0-4000	0-250
PG63-400RG	1/4"	63	0-6000	0-400
PG63-600RG	1/4"	63	0-9000	0-600
Tech Sheet 20596				

Panel Mounting Brackets

stainless steel



For G63 & PG63 Centre Back Connection below 100 bar

0021
G63-PM

stainless steel



For G63 & PG63 Centre Back Connection above 100 bar

0021
G63-PM-RHOMB

Gauge Snubbers

Working Pressure: 20 to 300 bar



High Pressure

0234	Male Thread	Female Thread
130.4	1/4"	1/4"
130.3	3/8"	3/8"
130.2	1/2"	1/2"
Tech Sheet 28		

Gauge snubbers are a great way of protecting gauges from damage, with sudden impact pressure i.e. when full line pressure is introduced to the gauge damage can occur. With the use of the snubber the gauge will be protected.

Working Pressure: 0 to 20 bar



Low Pressure

0234	Male Thread	Female Thread
131.8	1/8"	1/8"
131.4	1/4"	1/4"
131.3	3/8"	3/8"
131.2	1/2"	1/2"
Tech Sheet 28		

Back Rubber Gauge Protectors



Open Closed

0021	Description
G63-OB	Open
G63-CB	Closed

GLYCERINE GAUGES

stainless steel

FT PRO

All Stainless Steel Gauges, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SSG63-001BG	1/4"	63	0-15	0-1
SSG63-004BG	1/4"	63	0-60	0-4
SSG63-012BG	1/4"	63	0-200	0-12
SSG63-025BG	1/4"	63	0-400	0-25
SSG63-060BG	1/4"	63	0-1000	0-60
SSG63-200BG	1/4"	63	0-3000	0-200
SSG63-250BG	1/4"	63	0-4000	0-250
SSG63-400BG	1/4"	63	0-6000	0-400
Tech Sheet 20598				



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SHG100-002BG	1/2"	100	0-30	0-2
SHG100-006BG	1/2"	100	0-100	0-6
SHG100-016BG	1/2"	100	0-250	0-16
SHG100-040BG	1/2"	100	0-600	0-40
SHG100-100BG	1/2"	100	0-1500	0-100
SHG100-250BG	1/2"	100	0-4000	0-250
SHG100-600BG	1/2"	100	0-9000	0-600
Tech Sheet 20599				

All Stainless Steel Gauges, Centre Back Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2020-0340	1/4"	50	0-200	0-12
2020-0341	1/4"	50	0-300	0-20
2020-0342	1/4"	50	0-600	0-40
2020-0343	1/4"	50	0-900	0-60
2020-0344	1/4"	50	0-4000	0-250
2038-8534	1/4"	63	0-200	0-12
2038-8567	1/4"	63	0-900	0-60
2038-8575	1/4"	63	0-4000	0-250
Tech Sheet 20600				



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2038-8435	1/2"	100	0-200	0-12
2038-8443	1/2"	100	0-300	0-20
2038-8450	1/2"	100	0-600	0-40
2038-8476	1/2"	100	0-4000	0-250
Tech Sheet 20601				

Stainless Steel Case, Heavy-duty, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002G	1/2"	100	0-36	0-2.5
HG100-004G	1/2"	100	0-58	0-4
HG100-006G	1/2"	100	0-87	0-6
HG100-010G	1/2"	100	0-145	0-10
HG100-016G	1/2"	100	0-232	0-16
HG100-040G	1/2"	100	0-580	0-40
HG100-100G	1/2"	100	0-1450	0-100
HG100-160G	1/2"	100	0-2320	0-160
HG100-250G	1/2"	100	0-3625	0-250
HG100-400G	1/2"	100	0-5800	0-400



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002B	1/2"	100	0-36	0-2.5
HG100-004B	1/2"	100	0-58	0-4
HG100-006B	1/2"	100	0-87	0-6
HG100-010B	1/2"	100	0-145	0-10
HG100-016B	1/2"	100	0-232	0-16
HG100-040B	1/2"	100	0-580	0-40
HG100-100B	1/2"	100	0-1450	0-100
HG100-160B	1/2"	100	0-2320	0-160
HG100-250B	1/2"	100	0-3625	0-250
HG100-400B	1/2"	100	0-5800	0-400
Tech Sheet 20597				

Vacuum Gauges, Centre Back Connection

stainless steel



Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GCV63/04	1/4" BSPP	63	-1
GCV100/06	3/8" BSPP	100	-1

Vacuum Gauges, Bottom Connection

stainless steel



Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GBV63/04	1/4" BSPP	63	-1
GBV100/06	3/8" BSPP	100	-1

GLYCERINE GAUGES

WIKA

Heavy-duty, Bottom Connection

Accuracy:
63mm diameter: +/- 1.6%
100mm diameter: +/- 1.0%



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar	Max Pressure PSI
WG63-14B-1G	1/4"	63	1	15
WG63-14B-1.6G	1/4"	63	1.6	25
WG63-14B-2.5G	1/4"	63	2.5	40
WG63-14B-4G	1/4"	63	4	60
WG63-14B-6G	1/4"	63	6	90
WG63-14B-10G	1/4"	63	10	160
WG63-14B-16G	1/4"	63	16	230
WG63-14B-25G	1/4"	63	25	400
WG63-14B-40G	1/4"	63	40	600
WG63-14B-60G	1/4"	63	60	900
WG63-14B-100G	1/4"	63	100	1600
WG63-14B-160G	1/4"	63	160	2300
WG63-14B-250G	1/4"	63	250	4000
WG63-14B-400G	1/4"	63	400	6000
WG63-14B-600G	1/4"	63	600	9000
WG100-38B-2.5G	3/8"	100	2.5	40
WG100-38B-4G	3/8"	100	4	60
WG100-38B-6G	3/8"	100	6	90
WG100-38B-10G	3/8"	100	10	160
WG100-38B-16G	3/8"	100	16	230
WG100-38B-40G	3/8"	100	40	600
WG100-12B-100G	1/2"	100	100	1600
WG100-12B-160G	1/2"	100	160	2300
WG100-12B-250G	1/2"	100	250	4000
WG100-12B-400G	1/2"	100	400	6000
WG100-12B-600G	1/2"	100	600	9000
Tech Sheet 10525				

Heavy-duty, Centre Back Connection



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Bar	Max Pressure PSI
WG63-14R-1G	1/4"	63	1	15
WG63-14R-1.6G	1/4"	63	1.6	25
WG63-14R-2.5G	1/4"	63	2.5	40
WG63-14R-4G	1/4"	63	4	60
WG63-14R-6G	1/4"	63	6	90
WG63-14R-10G	1/4"	63	10	160
WG63-14R-16G	1/4"	63	16	230
WG63-14R-25G	1/4"	63	25	400
WG63-14R-40G	1/4"	63	40	600
WG63-14R-60G	1/4"	63	60	900
WG63-14R-100G	1/4"	63	100	1600
WG63-14R-160G	1/4"	63	160	2300
WG63-14R-250G	1/4"	63	250	3600
WG63-14R-400G	1/4"	63	400	6000
WG63-14R-600G	1/4"	63	600	9000
WG100-38R-2.5G	3/8"	100	2.5	40
WG100-38R-4G	3/8"	100	4	60
WG100-38R-6G	3/8"	100	6	90
WG100-38R-10G	3/8"	100	10	160
WG100-38R-16G	3/8"	100	16	230
WG100-38R-40G	3/8"	100	40	600
WG100-12R-100G	1/2"	100	100	1600
WG100-12R-160G	1/2"	100	160	2300
WG100-12R-250G	1/2"	100	250	4000
WG100-12R-400G	1/2"	100	400	6000
WG100-12R-600G	1/2"	100	600	9000
Tech Sheet 10525				

Vacuum Gauges, Bottom Connection

Accuracy:
63mm diameter: +/- 1.6%



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Hg	Max Pressure Bar
WG63-14B/-30HG	1/4"	63	-30	-1
Tech Sheet 10525				

Vacuum Gauges, Centre Back Connection



BSPP

0056	Thread	Gauge Diameter mm	Max Pressure Hg	Max Pressure Bar
WG63-14R/-30HG	1/4"	63	-30	-1
Tech Sheet 10525				

All pressure gauges can be supplied with a calibration certificate at a nominal charge.
Please call our Business Development Team for price and delivery.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TEMPERATURE GAUGES

WIKA

Bi-metallic Thermometers, Aluminiun Case, Centre Back Connection

Pressure Rating of Thermowell:
6 bar max



BSPP

0056	Thread	Gauge Diameter mm	Temperature Range °C
WTG63-60	1/2"	63	0-60
WTG63-120	1/2"	63	0-120
WTG63-200	1/2"	63	0-200
WTG100-60	1/2"	100	0-60
WTG100-120	1/2"	100	0-120
WTG100-200	1/2"	100	0-200
Tech Sheet 10526			

Bi-metallic Thermometers, Stainless Steel Case, Centre Back Connection

Pressure Rating of Thermowell:
25 bar max

stainless steel



BSPP

0056	Thread	Gauge Diameter mm	Temperature Range°C
WTG63160-60	1/2"	63	0-60
WTG63160-120	1/2"	63	0-120
WTG160-60	1/2"	100	0-60
WTG160-120	1/2"	100	0-120
Tech Sheet 10527			

Refrigeration Gauges, Plastic Case, Bottom Connection



1/4" Flare

0056	Thread	Gauge Diameter mm	Temperature Range °C	Temperature Range °C
WG63-716B-1/9	7/16" UNF	63	-1/+9	-1/+9

Bi-metallic Thermometers

Other temperatures are available.
Please call our Technical Department for details.

Pressure Rating of Thermowell:
35 bar max

stainless steel



Stainless Steel Case, BSPP

0056	Thread	Gauge Diameter mm	Temperature Range°C
WTG100-TE-60	1/2"	100	0-60
WTG100-TE-120	1/2"	100	0-120
Tech Sheet 10527			

GLYCERINE GAUGES

stainless steel

FT PRO®

Bi-metallic Thermometers

Stainless steel case and stainless steel stem, 100mm insertion.
Applications:
- Machine and plant engineering, piping, industrial heating
- BSPP Male



Stainless Steel Case, Back Entry, BSPP

0021	Thread	Gauge Diameter mm	Temperature Range°C
2052-8774	1/4"	63	0-60
2052-8782	1/4"	63	0-120
2052-8790	1/4"	63	0-200
2052-8808	1/4"	63	0-300
2052-8816	1/2"	100	0-60
2052-8824	1/2"	100	0-120
2052-8840	1/2"	100	0-200

Stainless steel case and stainless steel stem, 100mm insertion.
Applications:
- Machine and plant engineering, piping, industrial heating
- BSPP Male



Stainless Steel Case, Bottom Entry, BSPP

0021	Thread	Gauge Diameter mm	Temperature Range°C
2052-8873	1/4"	63	0-120
2052-8907	1/2"	100	0-60
2052-8915	1/2"	100	0-120
2052-8923	1/2"	100	0-200

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HVAC GAUGES & ACCESSORIES

Temperature Gauges, Bottom Connection



BSPP

1480	Thread	Gauge Diameter mm	Stem Length	Range
T401A215A	1/2"	100	5cm	-30 to +60°
T401A251A	1/2"	100	5cm	0 to +120°
T401A251C	1/2"	100	10cm	0 to +120°

Temperature Gauges, Back Connection



BSPP

1480	Thread	Gauge Diameter mm	Stem Length	Range
T401F215A	1/2"	100	5cm	-30 to +60°
T401F215C	1/2"	100	10cm	-30 to +60°
T401F251A	1/2"	100	5cm	0 to +120°
T401F251C	1/2"	100	10cm	0 to +120°

Mild Steel Syphons



BSPP

1480	Thread	Type
ACC01582	3/8"	U
ACC01583	1/2"	U
ACC02082	3/8"	Ring
ACC02083	1/2"	Ring

Brass Gauge Cocks



BSPP

1480	Thread	Type
ACC00005	1/4"	F/F
ACC00006	3/8"	F/F
ACC00007	1/2"	F/F
ACC00022	3/8"	M/F

AIR CONTROL JWL Air Boy®



new product

For **JWL Air Boy Car Tyre Inflators** see page **1723**

AIGNEP

Digital Flow & Pressure Sensor PR03



See section 4
page 420

316 Stainless Steel Push-in Fittings

stainless steel



See section 6
pages 878-879

Plastic Push-in Fittings 55000 & 56000 Series



See section 6
pages 817-820

Gas Mini Ball Valves, Brass

AIGNEP
British Gas Approved Valves



See section 7
page 942

Aluminium Ring Main System

AIGNEP INFINITY



See section 8
pages 1082-1084

Metal Push-in Fittings 50000, 55000 58000 & 89000



See section 6
pages 852-861

EXCELLENT SOLUTIONS IN FLUID TECHNOLOGY

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

DIGITAL FLOW & PRESSURE SENSOR PR03

AIGNEP new product


Pressure Switches

The PR03 sensor is available in different sizes, from ¼" to ¾", to suit the different flow rates required in the various industrial applications in which it can be used. The largest size allows measurements up to a maximum of 2000 l/min.

The new digital flowmeter offers the following advantage

- **Easily display** the status of the accumulated **flow rat** .
- **Monitor air flow** in real time.
- **Detect** momentary **changes** in **fluid statu** .






Series PR03


9025	Regulation Range	Thread	Output
PR030103P1	0-100 l/min	1/4"	PNP + Analog Output (1~5V)
PR030203P1	0-200 l/min	1/4"	PNP + Analog Output (1~5V)
PR030505P1	0-500 l/min	1/2"	PNP + Analog Output (1~5V)
PR032007P1	0-2000 l/min	3/4"	PNP + Analog Output (1~5V)
PR030103P2	0-100 l/min	1/4"	PNP + Analog Output (4~20mA)
PR030203P2	0-200 l/min	1/4"	PNP + Analog Output (4~20mA)
PR030505P2	0-500 l/min	1/2"	PNP + Analog Output (4~20mA)
PR032007P2	0-2000 l/min	3/4"	PNP + Analog Output (4~20mA)
Tech Sheet 71761			

Digital Flow & Pressure Sensor PR03



Mounting Bracket

9025	
PR03B01	For 100-200 l/min
Tech Sheet 71761	



Mounting Bracket

9025	
PR03B05	For 500 l/min
PR03B20	For 2000 l/min
Tech Sheet 71761	

Fluid-Air Components Ltd

TEMPERATURE SWITCHES

TBF Series, Push-on Terminal DIN 46248 Normally Closed

Maximum Working Temperature:
+125°C

Maximum Static Pressure:
200 bar

Economic range
Material: Brass



Fixed Set Point, 3/8" BSPP Male

9025	Set Temperature °C
TBF-EV025-C38	25
TBF-EV035-C38	35
TBF-EV045-C38	45
TBF-EV050-C38	50
TBF-EV055-C38	55
TBF-EV060-C38	60
TBF-EV065-C38	65
TBF-EV070-C38	70
TBF-EV075-C38	75
TBF-EV080-C38	80
TBF-EV085-C38	85
TBF-EV090-C38	90
TBF-EV095-C38	95
TBF-EV0100-C38	100
TBF-EV0105-C38	105
TBF-EV0110-C38	110
TBF-EV0125-C38	125
Tech Sheet 68798	

Fixed Set Point, 1/2" BSPP Male

9025	Set Temperature °C
TBF-EV025-C12	25
TBF-EV035-C12	35
TBF-EV045-C12	45
TBF-EV050-C12	50
TBF-EV055-C12	55
TBF-EV060-C12	60
TBF-EV065-C12	65
TBF-EV070-C12	70
TBF-EV075-C12	75
TBF-EV080-C12	80
TBF-EV085-C12	85
TBF-EV090-C12	90
TBF-EV095-C12	95
TBF-EV0100-C12	100
TBF-EV0105-C12	105
TBF-EV0110-C12	110
TBF-EV0125-C12	125
Tech Sheet 68798	

EBC Series, PG 09 DIN 43650 Connector SPDT IP65

Maximum Working Temperature:
+80°C

Maximum Static Pressure:
200 bar

Material: Brass



Fixed Set Point, 1/2" BSPP Male

9025	Set Temperature °C
EBC50C	50
EBC60C	60
EBC70C	70
Tech Sheet 110835	

Fixed Set Point, 3/8" BSPP Male

9025	Set Temperature °C
EBC50B	50
EBC60B	60
EBC70B	70
Tech Sheet 110835	

NTB Series, PG 09 DIN 43650 Connector Normally Open IP65

Maximum Working Temperature:
+120°C

Maximum Static Pressure:
200 bar

Material:
Anodised aluminium



Fixed Set Point with 360° Rotating Head, 1/2" BSPP Male

9025	Set Temperature °C
NTB25CA	25
NTB31CA	31
NTB38CA	38
NTB47CA	47
NTB60CA	60
NTB70CA	70
NTB80CA	80
NTB90CA	90
NTB100CA	100
NTB105CA	105
Tech Sheet 68797	

Fixed Set Point with 360° Rotating Head, 3/8" BSPP Male

9025	Set Temperature °C
NTB25BA	25
NTB31BA	31
NTB38BA	38
NTB47BA	47
NTB60BA	60
NTB70BA	70
NTB80BA	80
NTB90BA	90
NTB100BA	100
NTB105BA	105
Tech Sheet 68797	

PRESSURE TRANSDUCERS

stainless steel

ELETTROTEC

Material: AISI 316

Working Temperature:
-25°C to +100°C



PG 09 DIN 43650 Connector IP65

0-10V Output, 1/4" BSPP Male

9025	Pressure Range Bar	Max Pressure Bar
PTE1GA-VMDMR14	-1 to 4	4
PTE2GA-VMDMR14	0-2	4
PTE4GA-VMDMR14	-1 to 9	10
PTE5GA-VMDMR14	0-5	10
PTE10GA-VMDMR14	0-10	15
PTE20GA-VMDMR14	0-20	35
PTE50GA-VMDMR14	0-50	100
PTE100GA-VMDMR14	0-100	150
PTE200GA-VMDMR14	0-200	300
PTE400GA-VMDMR14	0-400	500
Tech Sheet 110836		

4-20mA Output, 1/4" BSPP Male

9025	Pressure Range Bar	Max Pressure Bar
PTE1GA-IMDMR14	-1 to 4	4
PTE2GA-IMDMR14	0-2	4
PTE4GA-IMDMR14	-1 to 9	10
PTE5GA-IMDMR14	0-5	10
PTE10GA-IMDMR14	0-10	15
PTE20GA-IMDMR14	0-20	35
PTE50GA-IMDMR14	0-50	100
PTE100GA-IMDMR14	0-100	150
PTE200GA-IMDMR14	0-200	300
PTE400GA-IMDMR14	0-400	500
Tech Sheet 110836		

M12 x 1.5 Pole Male Connector IP67

0-10V Output, 1/4" BSPP Male

9025	Pressure Range Bar	Max Pressure Bar
PTE1GA-VMR14	-1 to 4	4
PTE2GA-VMR14	0-2	4
PTE4GA-VMR14	-1 to 9	10
PTE5GA-VMR14	0-5	10
PTE10GA-VMR14	0-10	15
PTE20GA-VMR14	0-20	35
PTE50GA-VMR14	0-50	100
PTE100GA-VMR14	0-100	150
PTE200GA-VMR14	0-200	300
PTE400GA-VMR14	0-400	500
Tech Sheet 110836		

4-20mA Output, 1/4" BSPP Male

9025	Pressure Range Bar	Max Pressure Bar
PTE1GA-IMR14	-1 to 4	4
PTE2GA-IMR14	0-2	4
PTE4GA-IMR14	-1 to 9	10
PTE5GA-IMR14	0-5	10
PTE10GA-IMR14	0-10	15
PTE20GA-IMR14	0-20	35
PTE50GA-IMR14	0-50	100
PTE100GA-IMR14	0-100	150
PTE200GA-IMR14	0-200	300
PTE400GA-IMR14	0-400	500
Tech Sheet 110836		

FTI PRO



For **Wired Plugs**
see page **1043**

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

ADJUSTABLE PRESSURE SWITCHES

PMN Series, Normally Closed, DIN 462488

Seal: Nitrile

Working Temperature: -5°C to +60°C



Push-on 6.3 x 0.8, 1/4" BSPT Male, Brass

9025	Pressure Range Bar	Max Pressure Bar
PMN1C-BN14K	0.1-1	300
PMN2C-BN14K	0.15-2	300
PMN5C-BN14K	1-5	300
PMN10C-BN14K	2-10	300
PMN20C-BN14K	10-20	300
PMN50C-BN14K	20-50	300
PMN80C-BN14K	50-80	300
Tech Sheet 68789		

Push-on 6.3 x 0.8, 1/4" BSPT Male, Zinc Plated Steel

9025	Pressure Range Bar	Max Pressure Bar
PMN150C-FN14K	50-150	300
PMN250C-FN14K	100-250	600
PMN300C-FN14K	50-300	600
Tech Sheet 68789		

PMN Series, Normally Open

Seal: Nitrile

Working Temperature: -5°C to +60°C



Push-on 6.3 x 0.8, 1/4" BSPT Male, Brass

9025	Pressure Range Bar	Max Pressure Bar
PMN1A-BN14K	0.1-1	300
PMN5A-BN14K	1 - 5	600
PMN2A-BN14K	0.15-2	300
PMN10A-BN14K	2-10	300
PMN50A-BN14K	20-50	300
PMN80A-BN14K	50-80	300
Tech Sheet 68789		

Push-on 6.3 x 0.8, 1/4" BSPT Male, Zinc Plated Steel

9025	Pressure Range Bar	Max Pressure Bar
PMN150A-FN14K	50-150	300
PMN250A-FN14K	100-250	600
PMN300A-FN14K	50-300	600
Tech Sheet 68789		

PMC Series, PG 09 DIN 43650, SPDT Contacts

Seal: Nitrile

Working Temperature: -5°C to +90°C



1/8" BSPT Male, Anodised Aluminium

9025	Pressure Range Bar	Max Pressure Bar
PMC2	0.15-2	30
PMC5	0.2-5	60
PMC10	0.5-10	100
PMC25	10-25	100
PMC80	25-80	150
Tech Sheet 68791		

PPC Series, PG 90 DIN 43650, SPDT Contacts

Seal: Nitrile

Working Temperature: -5°C to +90°C

Maximum Static Pressure: 600 bar



1/4" BSPT Male, Anodised Aluminium

9025	Pressure Range Bar
PPC150	30-150
PPC300	150-300
Tech Sheet 68791	

PPCF Series, PG 09 DIN 43650, SPDT Contacts

Seal: Nitrile

Working Temperature: -5°C to +90°C

Maximum Static Pressure: 600 bar



1/4" BSPT Female, Anodised Aluminium

9025	Pressure Range Bar
PPCF150	30-150
PPCF300	150-300
Tech Sheet 68791	

PSK Series, PG 09 DIN 43650 with Graduated Knobs

Seal: Nitrile

Working Temperature: -5°C to +90°C



1/4" BSPP Female, Yellow Anodised Aluminium

9025	Pressure Range Bar	Max Pressure Bar
PSK10	1-10	30
PSK100	10-100	300
PSK360	100-300	600
Tech Sheet 38793		

Fluid-Air Components Ltd

PRESSURE SWITCHES

High Temperature MS Series, PG 09 DIN 43650, SPDT IP65

Material: Brass
Seal: High temperature nitrile

Working Temperature:
-25°C to +140°C

Maximun Static Pressure:
300 bar



Push-on 6.3 x 0.8, 1/4" BSPT Male

9025	Pressure Range Bar
MS2SC-BNT14K	0.2-2
MS10SC-BNT14K	1-10
MS50SC-BNT14K	10-50
MS100SC-BNT14K	10-100
Tech Sheet 110833	

Adjustable Hysteresis PSM Series, PG 09 DIN 43650, SPDT IP65

Material: Brass
Adjustable hysteresis 10% - 30% of set-point

Working Temperature:
-5°C to +90°C

Maximun Static Pressure:
300 bar



1/4" BSPT Male

9025	Pressure Range Bar
PSM2-BN14K	0.2-2
PSM5-BN14K	1-5
PSM10-BN14K	1-10
PSM50-BN14K	10-50
PSM100-BN14K	10-100
Tech Sheet 110834	

High Temperature PS Series, PG 09 DIN 43650, SPDT IP65

Material: Steel
Seal: High temperature nitrile

Working Temperature:
-25°C to +140°C

Maximum Static Pressure:
600 bar



Push-on 6.3 x 0.8, 1/4" BSPT Male

9025	Pressure Range Bar
PS150SC-FNT14K	30-150
PS300SC-FNT14K	50-300
Tech Sheet 110833	

Adjustable Hysteresis PSP Series, PG 09 DIN 43650, SPDT IP65

Material: Zinc plated steel
Adjustable hysteresis: 10% to 30% of set-point

Working Temperature:
-5°C to +90°C

Maximun Static Pressure:
600 bar



1/4" BSPT Male

9025	Pressure Range Bar
PSP150-FN14K	30-150
PSP300-FN14K	50-300
Tech Sheet 110834	

You may also be interested in...
Adjustable Pressure Switches
...see page **423**



Fluid-Air Components Ltd

VACUUM SWITCHES

VCN Series, Push-on Terminal DIN 46248, Normally Closed

Material: Brass
Seal: Nitrile

Working Temperature: -5°C to +60°C

Maximum Static Pressure: 20 bar



1/4" BSPT Male

9025	Pressure Range Bar
VCN2C-BN14K	-0.2 to -0.9
	Tech Sheet 38794

VCN Series, Push-on Terminal DIN 46248, Normally Open

1/4" BSPT Male, Brass

9025	Pressure Range Bar
VCN2A-BN14K	-0.2 to -0.9
	Tech Sheet 38794

VMC Series, PG 09 DIN 43650, SPDT IP65

Material: Anodised aluminium
Seal: Nitrile

Working Temperature: -5°C to +90°C

Maximum Static Pressure: 20 bar



Fixed Hysteresis, 1/8" BSPT Male, Anodised Aluminium

9025	Pressure Range Bar
VMC1N	-0.2 to -0.5
	Tech Sheet 38794

VSM Series, PG 09 DIN 43650, SPDT IP65

Material: Brass
Seal: Nitrile

Working Temperature: -5°C to +90°C

Maximum Static Pressure: 20 bar



Adjustable Hysteresis, 1/4" BSPP Male, Brass

9025	Pressure Range Bar
VSM1-BNR14	-0.1 to -0.5
VSM2-BNR14	-0.5 to -0.9
	Tech Sheet 38794

Switch Protection



IP54, Cap 1

9025	To Suit Series
CAP54-1	VCN, VCM, PMN, PMM, PM250



IP54, Cap 10

9025	To Suit Series
CAP54-10	VCN, VCM, PMN, PMM



IP54, Cap 12

9025	To Suit Series
CAP54-12	VSM, PSM, PSP



IP54, Cap 16

9025	To Suit Series
CAP54-16	VS, MS, PS



IP65, Cap 3

9025	To Suit Series
CAP65-3	VCM, PMN, PMM, PM250



IP65, Cap 13

9025	To Suit Series
CAP65-13	VS, MS, PS



IP67, Cap M12

9025	To Suit Series
CAP67-M12	VSM, NMC, MS, PS, PSM, PSP, PMC, PPC, PPCF, PMC, PPC, PPL, PSK, MPS

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



New:
cylinder sensor SDBT-SMX


The first self-learning sensor

FESTO

The cylinder sensor detects the piston and automatically learns the switching point during commissioning.







Programming the switching window
2 to 15 mm in increments of 1 mm

The benefits of SDBT-MSX:

Auto teach-in
The switching point is taught in automatically, so there no longer is a need for precision adjustment.

- Fit, connect - ready!
- Several cylinders at the same time

Touch button
Programming button for the switching functions NPN/PNP, NO/NC and the switching window.

- Just one type for all switching functions

Programmable switching window
Setting the switching signal between 2 and 15 mm, for example for early detection of high speeds.

- Flexible position detection

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SFAB SERIES, FLOW SENSORS

FESTO

Airflow Sensor

Ambient Temperature:
0°C to +50°C

Working Pressure:
0 to 10 bar

- Freely selectable pulse output for consumption measurement
- Analogue filter for setting the rise time
- Digital filter for smoothing the display values



4-20mA, H Rail Mounted Push-in with M12 x 1, 5 Pin Plug

0010	OD mm	Maximum LPM	Manufacturer's Code
565401	10	600	SFAB-600U-HQ10-2SA-M12
565405	10	1000	SFAB-1000U-HQ10-2SA-M12
Tech Sheet 71588			

0-10V, H Rail Mounted Push-in with M12 x 1, 5 Pin Plug

0010	OD mm	Maximum LPM	Manufacturer's Code
565402	10	600	SFAB-600U-HQ10-2SV-M12
565406	10	1000	SFAB-1000U-HQ10-2SV-M12
Tech Sheet 71589			

SFAM SERIES, FLOW SENSORS

FESTO

Airflow Sensor

Ambient Temperature:
0°C to +50°C

Working Pressure:
0 to 16 bar

- Freely selectable pulse output for consumption measurement
- Analogue filter for setting the rise time
- Digital filter for smoothing the display values



4-20mA, Manifold Assembly

0010	LPM	Manufacturer's Code
564930	1000	SFAM-62-1000L-M-2SA-M12
564934	3000	SFAM-62-3000L-M-2SA-M12
564938	5000	SFAM-62-5000L-M-2SA-M12
573346	5000	SFAM-90-5000L-M-2SA-M12
573348	10000	SFAM-90-10000L-M-2SA-M12
573350	15000	SFAM-90-15000L-M-2SA-M12
Tech Sheet 71590		

0-10V, Manifold Assembly

0010	LPM	Manufacturer's Code
564932	1000	SFAM-62-1000L-M-2SV-M12
564936	3000	SFAM-62-3000L-M-2SV-M12
564940	5000	SFAM-62-5000L-M-2SV-M12
573347	5000	SFAM-90-5000L-M-2SV-M12
573349	10000	SFAM-90-10000L-M-2SV-M12
573351	15000	SFAM-90-15000L-M-2SV-M12
Tech Sheet 71591		

Fluid-Air Components Ltd

PRESSURE SENSORS

FESTO

SPAN Series with Display

- For network monitoring, regulator monitoring, leak test and object detection
- For monitoring compressed air and non corrosive gases
- Relative measurement method based on a piezo-resistive measuring cell
- Serial communication integrated using IO-Link® 1.1
- Compact design
- High-contrast, blue backlit display

Ambient Temperature:
0°C to +50°C



Male Thread, BSPP with PNP or NPN Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035544	1/8"	0 to 10	SPAN-P10R-G18M-PN-PN-L1
		Tech Sheet 70713	

Male Thread, BSPT with PNP or NPN Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035547	1/8"	0 to 10	SPAN-P10R-R18M-PN-PN-L1
		Tech Sheet 70715	

Male Thread, BSPP with PNP, NPN or IO-Link Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035533	1/8"	0 to 10	SPAN-P10R-G18M-PNLK-PNVBA-L1
		Tech Sheet 70714	

Male Thread, BSPT with PNP, NPN or IO-Link Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035536	1/8"	0 to 10	SPAN-P10R-R18M-PNLK-PNVBA-L1
		Tech Sheet 70716	



Female Thread, Metric & BSPP with PNP, NPN or IO-Link Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035539	M5	0 to 10	SPAN-P10R-M5F-PNLK-PNVBA-L1
		Tech Sheet 70712	

Female Thread, Metric & BSPP with PNP or NPN Output

0009	Thread	Pressure Range Bar	Manufacturer's Code
8035550	M5	0 to 10	SPAN-P10R-M5F-PN-PN-L1
		Tech Sheet 70711	

4mm Push-in Connector with PNP, NPN or IO-Link Output

0009	Pressure Range Bar	Manufacturer's Code
8035541	0 to 10	SPAN-P10R-Q4-PNLK-PNVBA-L1
	Tech Sheet 70718	

4mm Push-in Connector with PNP or NPN Output

0009	Pressure Range Bar	Manufacturer's Code
8035552	0 to 10	SPAN-P10R-Q4-PN-PN-L1
	Tech Sheet 70717	

Accessories

Mounting Brackets, PU

0010	Manufacturer's Code
8003354	SAMH-PU-A
Tech Sheet 71593	

Accessory to: SPAN



Wall Mounting Brackets, PN

0009	Manufacturer's Code
8035563	SAMH-PN-W
Tech Sheet 71594	

Accessory to: SPAN, SCDN



NEBS Series, Connecting Cables For Sensors



4 Pin PCB Plug Connector x 4 Wire Open End with Label Holder

0009	Cable Length Metres	Connection Angle	Manufacturer's Code
572576	2.5	Straight	NEBS-L1G4-K-2.5-LE4
572577	5	Straight	NEBS-L1G4-K-5-LE4
	Tech Sheet 70286		

Accessories to: SPAN, SFAH, SCDN sensors

FAC
Fluid-Air Components Ltd

PRESSURE SWITCHES

NORGREN

Electro-Mechanical Pressure Switch

- Gold-plated contacts
- High cycle life
- Vibration resistant to 15g

Working Temperature:
-10°C to +85°C



18D Pneumatic

0036	Thread	Switching Pressure Difference
0880600000000000	1/4"	1,00 to 5,00 bar
0880160000000000	1/4"	0.15 to 0.18 bar
0880260000000000	1/4"	0.2 to 0.35 bar
0880460000000000	1/4"	0,40 to 1,20
Tech Sheet 71726		

Electronic Pressure Sensor Digital

- Compact, robust and light weight
- Pressure display colour change configurable
- High overpressure and vacuum resistance
- Housing: Stainless steel (1.4404 / 316L)

Working Temperature:
0°C to +70°C



54D Pneumatic

0036	Thread	Working Pressure
54D-V101G-DD0-AA	1/8"	- 1 to 1
54D-V110G-DD0-AA	1/8"	-1 to 10
54D-P016G-DD0-AA	1/8"	0 to 16
54D-V101G-DA1-AA	1/8"	- 1 to 1
54D-V110G-DA1-AA	1/8"	-1 to 10
54D-P016G-DA1-AA	1/8"	0 to 16
0523449000000000	1.5m Cable, 4-pin	-
0523447000000000	5m Cable, 4-pin	-
Tech Sheet 71728		

Electro-Mechanical Pressure Switch, Digital

- Multicolour 4-digit display
- Upper body can be rotated 345° relative to the process connection for easy alignment of the display
- Suitable for harsh industrial and process control environments
- Housing: Stainless steel (1.4404 / 316L)

Working Temperature:
-25°C to +80°C



34D Pneumatic/Hydraulic/Allflui

0036	Thread	Working Pressure
34D-V101G-DD1-AA	1/4	- 1 to 1
34D-V110G-DD1-AA	1/4	-1 to 10
34D-P016G-DD1-AA	1/4	0 to 16
34D-V101G-DA1-AA	1/4	- 1 to 1
34D-V110G-DA1-AA	1/4	-1 to 10
34D-P016G-DA1-AA	1/4	0 to 16
34D-BRKT-ANGLED	Wall mounting kit	-
0523058000000000	1.5m Cable, 4-pin	-
0523053000000000	5m Cable, 4-pin	-
Tech Sheet 71727		

Electronic Pressure Switch with IO-Link

- IO-Link output option
- Set points parameters set via software
- Robust pressure sensor
- Excellent long life
- Suitable for harsh industrial environments
- High over pressure resistance

Working Temperature:
-40°C to +90°C



60D Pneumatic/Hydraulic/Allflui

0036	Thread	Working Pressure
60D-V110G-DD1-AA	1/4	- 1 to 1
60D-P100G-DD1-AA	1/4	0 to 100
Tech Sheet 71729		

Electronic Pressure Sensor

- Robust pressure sensor
- Excellent long life
- Suitable for harsh industrial environments
- High over pressure resistance

Working Temperature:
-40°C to +90°C



60S Pneumatic/Hydraulic/Allflui

0036	Thread	Working Pressure
60S-V110G-A42-AA	1/4	- 1 to 1
60S-P010G-A42-AA	1/4	-1 to 10
60S-P016G-A42-AA	1/4	0 to 16
Tech Sheet 71730		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PARKER D.H FILTERS & DRAINS AIR, WATER, VACUUM

Parker D.H Filters & Drains



Electronic Zero Loss Condensate Drains

0050	Capacity Compressor 1 m³/h	Capacity Dryer 1 m³/h	Connection
ED3004-G230	2400	480	1 x G1/2"
ED3007-G230	4200	840	2 x G1/2"



Oil-X Combination Point of Use Filter

0050	Size	L/S	CFM
AC015CBFI	1/2"	13	27



Combination Replacement Element Kit

0050	Description
015AC	2nd Stage Element



Replacement Element Kit Oil-X Evolution AA Filters

0050	Range
015AA	015AA
020AA	020AA
025AA	025AA







Oil-X Evolution Filter Accessories, 1/4" to 3" Models

0050	Filter Model	Description
FXKE1	005-010	Filter Fixing Clamp Kit
FXKE3	025-030	Filter Fixing Clamp Kit
605009902	AC010-AC030	Oil Indicator
EF1	AO/AA GRADE	Replacement Drains



Oil-X Plus Replacement AO/AA Elements for Oil-X Filters (94-04)

0050	Housing Type	Description
K030AO	0030G	Pre Filter Element
K145AO	0080G	Pre Filter Element
K009AA	0009G	High Efficiency Element
K030AA	0030G	High Efficiency Element
K145AA	0080G	High Efficiency Element

Oil-X Plus Activated Carbon Elements (94-04)

0050	Housing Type	Description
K006AC	AC-0006G	Activated Carbon Element

Old Model Oil-X Plus Filter Spares (94-04)

0050	Housing Type	Description
605006520	0006G-0009G	Automatic Drain Kit
605006250	0017G-01045G	Automatic Drain Kit

Parker transair

For **Transair Ring Main System**
see page **1063**



Fluid-Air Components Ltd



Your Partner for Air & Other Fluids
Low Pressure Solutions

legris



RECTUS



Manufactured in Europe

Parker

ENGINEERING YOUR SUCCESS.

ENGINEERING YOUR SUCCESS.

431

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

CONDENSATE MANAGEMENT

Refrigerated Dryers & Filters 600 - 150000 L/min



Final Filters (0.01 Micron)

0640	CFM	G	DxH mm
HM10	30	3/8"	100x220
HM18	59	1/2"	100x250
HM30	88	3/4"	120x290
HM34	118	3/4"	120x360



Refrigerated Dryers

0640	Gas	CFM	Bar	G
RD6.A	R134a	21	16	1/2"
RD9.A	R134a	34	16	1/2"
RD12.A	R134a	42	16	1/2"
RD18.A	R134a	64	16	1/2"
RD25.A	R134a	88	14	1"
RD32.A	R134a	113	14	1.1/4"
RD43.A	R407c	152	14	1.1/4"
RD52.A	R407c	184	14	1.1/4"
RD63.A	R407c	222	14	1.1/2"
RD80.A	R407c	283	14	1.1/2"

Donaldson Membrane Dryers

Donaldson FILTRATION SOLUTIONS



Donaldson VarioDry Membrane Dryers

0640	m³/h-(CFM) Inlet	m³/h-(CFM) Outlet	Connection
SPN0006	6.0 (3.53)	5.5 (3.24)	G 1/4"
SPN0009	9.0 (5.30)	8.1 (4.80)	G 1/4"
SPN0012	12.0 (7.10)	10.8 (6.40)	G 1/4"
SPN0018	18.0 (10.62)	16.2 (9.50)	G 1/2"
SPN0024	24.0 (14.12)	21.6 (12.71)	G 1/2"
SPN0036	36.0 (21.19)	32.4 (19.07)	G 1/2"
SPN0048	48.0 (28.25)	43.2 (25.43)	G 1/2"
SPN0063	63.0 (37.08)	56.7 (33.37)	G 1/2"

PANAM



For **Stainless Steel Tube Fittings**
see pages **165-178**

AIR RECEIVERS & ACCESSORIES

Installation: always in combination with a full receiver kit, water drain and safety relief valve. Ensure the compressor never takes in air/solvent mix. This could cause the tank to explode.

The air receiver or tank allows the storage and control of compressed air. A device on most compressors maintains pressure at a predetermined pressure range, allowing the compressor to operate automatically as the air is used, switching on and off accordingly. The air receiver must also be fitted with a safety device to prevent over pressurisation, a means of draining condensate and various outlet sockets. The size of air receiver (usually measured in litres) will normally be proportional to the size or capacity of air compressor fitted.

Material: carbon steel
Finishing: external RAL 5015 blue paint
Fluid content: compressed air and nitrogen (group 2)

All air receivers for the European market are supplied with a declaration of conformity

In compliance with the applicable EU Directives or according to the major international standards:
SPVD 2014/29/UE Directive (ex 2009/105/EC)
PED 2014/68/UE Directive (ex 97/23/EC)
ABS American Bureau of Shipping
DNV Det Norske Veritas
B.V. Bureau Veritas
LRS Lloyd's Register of Naval Ship
GL Germanischer Lloyd

Available upon request:
- Internal and external hot dip galvanization
- 16 bar rated
- Alternative port sizes

Vessel options include:
- Stainless steel vessels
- Pressurised water vessels
- High pressure vessels
- Vacuum vessels
- Oxygen vessels
- Oversized vessels

Working Temperature:
11 bar versions: 10°C to +100°C
12 bar versions: 10°C to +50°C

Maximum Working Pressure:
11 bar SPVD 2014/29/UE
12 bar PED 2014/68/UE

Additional carriage charges will apply to this product and will vary dependant on location. This overrides any other carriage agreements. For further details please contact us.

Ensure the compressor never takes in air/solvent mix. This could cause the tank to explode.

Horizontal with Fixing Bracket



BSPP Ported, RAL 5015

0458	Litres	Max Pressure Bar	Kg
VEC01294	5	11	7
VEC01249	10	11	8
VEC01237	15	11	9
VEC01250	24	11	10
VEC01251	50	11	19
VEC01095	100	11	29
VEC02139	150	11	44
VEC01732	200	11	55
VEC01733	270	11	67
VEC00728	500	11	130
VEC00873*	720	11	178
VEC00707*	900	11	194
VEC00515*	1000	12	210
VEC00739*	1500	12	325
VEC00680*	2000	12	394
VEC00534*	3000	12	605

Tech Sheet 20570

Vertical with Fixing Bracket



BSPP Ported, RAL 5015

0458	Litres	Max Pressure Bar	Kg
VEC01295	24	11	10
VEC01296	50	11	19
VEC00644	100	11	29
VEC00709	150	11	44
VEC00645	200	11	55
VEC00478	270	11	67
VEC00493	500	11	115
VEC00511*	900	11	194
VEC00518*	1000	12	210
VEC00525*	1500	12	320
VEC00528*	2000	12	388
VEC00535*	3000	12	594

Tech Sheet 20570

Receiver Kits

For illustration purposes only, each kit contains different components based on the specific connections of each air receiver



Each kit to suit vertical air receivers contains a mechanical float condensate drain (50 litre onwards), safety relief valve, ball valve, gauge and connection materials

To suit Vertical Air Receivers, RAL 5015

0085	To Suit Type	To Suit Litres
AVK-24B	VEC01295	24
AVK-50B	VEC01296	50
AVK-100B	VEC00644	100
AVK-150B	VEC00709	50
AVK-200B	VEC00645	200
AVK-270B	VEC00478	270
AVK-500B	VEC00493	500
AVK-720B	VEC00507	720
AVK-900B	VEC00511	900
AVK-1000B	VEC00518	1000
AVK-1500B	VEC00525	1500
AVK-2000B	VEC00528	2000
AVK-3000B	VEC00535	3000

Each kit to suit horizontal air receivers contains a drain valve, safety relief valve, ball valve, gauge and connection materials

To suit Horizontal Air Receivers, RAL 5015

0085	To Suit Type	To Suit Litres
AHK-5B	VEC01294	5
AHK-10B	VEC01249	10
AHK-15B	VEC01237	15
AHK-24B	VEC01250	24
AHK-50B	VEC01251	50
AHK-100B	VEC00633	100
AHK-150B	VEC00634	150
AHK-200B	VEC00635	200
AHK-270B	VEC00474	270
AHK-500B	VEC00728	500
AHK-720B	VEC00873	720
AHK-900B	VEC00707	900
AHK-1000B	VEC00515	1000
AHK-1500B	VEC00739	1500
AHK-2000B	VEC00680	2000
AHK-3000B	VEC00534	3000

DIRECT DELIVERY

***Direct delivery, to Mainland UK only, on any air receiver above 500 litres. Please contact your Account Manager.**

Fluid-Air Components Ltd

AIR RECEIVERS & ACCESSORIES

Vertical with Fixing Bracket

Installation: always in combination with a full receiver kit, water drain and safety relief valve. Ensure the compressor never takes in air/solvent mix. This could cause the tank to explode.

Additional carriage charges will apply to this product and will vary dependant on location. This overrides any other carriage agreements. For further details please contact us.

Working Temperature:
11 bar versions: 10°C to +100°C
12 bar versions: 10°C to +50°C

Maximum Working Pressure:
11 bar SPVD 2014/29/UE
12 bar PED 2014/68/UE

Ensure the compressor never takes in air/ solvent mix. This could cause the tank to explode.



BSPP Ported, Galvanised

0458	Litres	Max Pressure Bar	Weight Kg
VEC00901	100	11	32
VEC00908	200	11	57
VEC00909	270	11	70
VEC00906	500	11	119
VEC00519	1000	12	214
VEC00529	2000	12	394
VEC00536	3000	12	600
Tech Sheet 60120			

Receiver Kits

For illustration purposes only, each kit contains different components based on the specific connections of each air receiver



Each kit to suit vertical air receivers contains a mechanical float condensate drain (50 litre onwards), safety relief valve, ball valve, gauge and connection materials

To suit Vertical Air Receivers, Galvanised

0085	To Suit Type	To Suit Litres
AVK-100G	VEC00901	100
AVK-200G	VEC00908	200
AVK-270G	VEC00909	270
AVK-500G	VEC00906	500
AVK-720G	VEC00907	720
AVK-900G	VEC00512	900
AVK-1000G	VEC00519	1000
AVK-2000G	VEC00529	2000
AVK-3000G	VEC00536	3000

Reservoir Tanks



1/2" Inlet/Outlet Reservoir Tanks

0088	Litres	Height mm	Ø mm
7710061	2.5	166	160
7710062	5	175	210
7710063	7	240	210
7710064	12	365	229
Tech Sheet 808			

Long Life Compressor Oil

ISO 46 low carbon formation characteristics. Suitable for screw, reciprocating, axial flow and rotary vane compressors.



0085	Litres
2020-6025	5
Tech Sheet 1382	

M-Press Fittings Ltd



For **M-Press Press Fit Piping System**
see pages **1116-1134**

DIRECT DELIVERY

***Direct delivery, to Mainland UK only, on any air receiver above 500 litres. Please contact your Account Manager.**

CONDENSATE MANAGEMENT

No Loss Pneumatic & Electric Drain



No Loss Pneumatic Condensate Drain 1/2"

0600	Inlet/Outlet BSPP	Pressure (bar)
TVR-20B	1/2" Male/Female	20



Zero Loss Electric Drain - 106 CFM Capacity

0600	Capacity (CFM)	Thread
TZLD100	106	G1/2"



Zero Loss Electric Drain - 350 CFM Capacity

0600	Capacity (CFM)	Thread
TZLD300	353 (Compressor)	G1/2"

Condensate Separators



Disposable Condensate Separator

0600	Capacity (CFM)
TCS60	60



Condensate Separator - 100 CFM Capacity

0600	Capacity (CFM)
TCS100	100



TCS100 Service Kit

0600	Description
TCS100-KIT	Service Kit TCS100

For **Automatic Drain Valves**
see pages **1024-1025**



Fluid-Air Components Ltd

SIGHT GLASSES & FLOW INDICATORS

200 Series - All Stainless Steel

A low cost, all stainless steel sight flow indicator straight through type.

Maximum Working Pressure:
10 bar at 200°C

stainless steel

RHODES



233 Model Through Type

0115	Thread	OD mm	Length mm
RHO-FIS-146410-1	1/2" BSPT	15	70
Tech Sheet 10037			

A low cost, all stainless steel sight flow indicator fitte with a flap and scale plate to give an indication of the flow rate

Maximum Working Pressure:
10 bar at 200°C

stainless steel

RHODES



234 Model with Flap & Plate

0115	Thread	OD mm	Length mm
RHO-FIS-146510-1	1/2" BSPT	15	70
RHO-FIS-146510-2	1/2" BSPP	15	70
RHO-FIS-146515-2	3/4" BSPP	20	70
Tech Sheet 10037			

400 Series - Straight Through Sight Flow Indicator with Spinner/Ball

Maximum Working Pressure:
16 bar at 100°C

stainless steel

RHODES



Stainless Steel with Spinner

0115	Thread	Min LPH	Max LPH
RHO-FIS-140300-1	1/4" BSPT	30	200
RHO-FIS-140305-1	3/8" BSPT	50	450
RHO-FIS-140305-2	3/8" BSPP	50	450
RHO-FIS-140310-1	1/2" BSPT	60	600
RHO-FIS-140310-2	1/2" BSPP	60	600
RHO-FIS-140315-1	3/4" BSPT	120	1600
RHO-FIS-140320-1	1" BSPT	300	1600
Tech Sheet 10038			

400 Series - Straight Through Sight Flow Indicator with Spinner/Ball

Maximum Working Pressure:
7 bar at 100°C

RHODES



With Spinner, Gun Metal

0115	Thread	LPH Min	LPH Max
RHO-FIG-170300-1	1/4" BSPT	30	200
RHO-FIG-170300-2	1/4" BSPP	30	200
RHO-FIG-170305-1	3/8" BSPT	50	450
RHO-FIG-170305-2	3/8" BSPP	50	450
RHO-FIG-170310-1	1/2" BSPT	60	600
RHO-FIG-170310-2	1/2" BSPP	60	600
RHO-FIG-170315-1	3/4" BSPT	120	1600
RHO-FIG-170315-2	3/4" BSPP	120	1600
RHO-FIG-170320-1	1" BSPT	300	1600
RHO-FIG-170320-2	1" BSPP	300	1600
Tech Sheet 10038			

Maximum Working Pressure:
7 bar at 100°C

RHODES



With Ball, Gun Metal

0115	Thread	LPH Min	LPH Max
RHO-FIG-176600-1	1/4" BSPT	30	200
RHO-FIG-176600-2	1/4" BSPP	30	200
RHO-FIG-176605-1	3/8" BSPT	50	450
RHO-FIG-176610-1	1/2" BSPT	60	600
RHO-FIG-176610-2	1/2" BSPP	60	600
RHO-FIG-176615-1	3/4" BSPT	120	1600
RHO-FIG-176615-2	3/4" BSPP	120	1600
RHO-FIG-176615-3	3/4" NPT	120	1600
RHO-FIG-176620-1	1" BSPT	300	1600
RHO-FIG-176620-2	1" BSPP	300	1600
Tech Sheet 10038			

Bronze Sight Glass/Indicator

Maximum Working Temperature:
150°C

Maximum Working Pressure:
16 bar

Specification
Hardened single glass inspection window.

FT PRO



BSPP

0118	Thread
2021-1330	1/2"
2021-1348	3/4"
2021-1355	1"
Tech Sheet 821	

Can't see the product you're looking for? Contact us. More often than not, we can acquire that product.



Are you looking for...
a stainless steel flanged PN16 sight glass?
...see page **963**

Fluid-Air Components Ltd

FLOW SWITCHES

ELETTROTEC

Adjustable IF-E Series, Normally Open, IP65



Working Temperature:
-10°C to +80°C

Maximum Working Pressure:
50 bar

Viscosity up to 1 cSt, PG 09 DIN 43650, BSPP Female

9025	Thread	LPM
IFE0.5R2.5	1/8"	0.1-2.5
IFE1R3	1/8"	0.3-3
IFE2R9	1/4"	2-9
IFE3R18	3/8"	3-18
IFE5R35	3/4"	6-35
IFE6R60	1"	15-60
IFE4R24	1/2"	3-24
Tech Sheet 110837		

Adjustable IF_VE Series, Visual, Normally Open, IP65





Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
15 bar

Viscosity up to 14.4 cSt, PG 09 DIN 43650, BSPP Female

9025	Thread	LPM
IF1VE1/A-M6	1/4"	0.1-1
IF2VE3/A-M6	1/4"	0.2-3
IF3VE6/A-M6	1/4"	1-6
IF4VE16/A-M6	1/2"	2-16
IF5VE60/A-M6	1"	5-60
Tech Sheet 110832		

Viscosity up to 39.8 cSt, PG 09 DIN 43650, BSPP Female

9025	Thread	LPM
IF1VE1/A-M7	1/4"	0.1-1
IF3VE6/A-M7	1/4"	1-6
IF4VE16/A-M7	1/2"	2-16
IF5VE60/A-M7	1"	5-60
Tech Sheet 110832		

Viscosity up to 70.4 cSt, PG09 DIN 43650, BSPP Female

9025	Thread	LPM
IF1VE1/A-M8	1/4"	0.1 - 1 LPM
IF2VE3/A-M8	1/4"	0.2 - 3 LPM
IF3VE6/A-M8	1/4"	1 - 6 LPM
IF4VE16/A-M8	1/2"	2 - 16 LPM
IF5VE60/A-M8	1"	5 - 60 LPM
Tech Sheet 110832		

FPL Series, Paddle SPDT IP65

Maximum Working Temperature:
+120°C




1" BSPP Male, Brass

9025	Nm³/h	Max Pressure Bar
FPL.1E	1-2.1	11
Tech Sheet 114		

1" BSPP Male, Stainless Steel

9025	Nm³/h	Max Pressure Bar
FPL.2E	46.5-94.2	30
Tech Sheet 114		



BSPP Female, Brass with T Fitting

9025	Thread	Nm³/h	Max Pressure Bar
FPL1E-12	1/2"	1-2.1	11
FPL1E-34	3/4"	1-2.1	11
FPL1E-1	1"	1-2.1	11
FPL1E-114	1.1/4"	1-2.1	11
FPL1E-112	1.1/2"	1-2.1	11
FPL1E-2	2"	1-2.1	11
Tech Sheet 20003			

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FLOW INDICATORS

CFV Series, Propeller

Maximum Working Temperature:
+90°C



Viscosity up to 250 cSt, BSPP Female

9025	Thread	LPM
CFV1B-N	1/4"	1-10
CFV2B-N	3/8"	2-20
CFV3B-N	1/2"	3-30
CFV4B-N	3/4"	4-40
CFV5B-N	1"	6-60
Tech Sheet 110829		

IF...V Series, Visual Indicator

Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
15 bar



Viscosity up to 14.4 cSt, Female

9025	Thread	LPM
IF1V1/A-M6	1/4"	0.1-1
IF2V3/A-M6	1/4"	0.2-3
IF3V6/A-M6	1/4"	1-6
IF4V16/A-M6	1/2"	2-16
IF5V60/A-M6	1"	5-60
Tech Sheet 110830		

Viscosity up to 39.8 cSt, BSPP Female

9025	Thread	LPM
IF1V1/A-M7	1/4"	0.1-1
IF2V3/A-M7	1/4"	0.2-3
IF3V6/A-M7	1/4"	1-6
IF4V16/A-M7	1/2"	2-16
IF5V60/A-M7	1"	5-60
Tech Sheet 110830		

Viscosity up to 70.4 cSt, BSPP Female

9025	Thread	LPM
IF1V1/A-M8	1/4"	0.1-1
IF2V3/A-M8	1/4"	0.2-3
IF3V6/A-M8	1/4"	1-6
IF4V16/A-M8	1/2"	2-16
IF5V60/A-M8	1"	5-60
Tech Sheet 110830		

You may also be interested in...
Flow Meters
...see page **440**



Fluid-Air Components Ltd

VARIABLE AREA FLOW METERS

TFM Series, Vertical Type

Working Temperature:
0°C to +60°C

Maximum Working Pressure:
10 bar



Gas/Air, BSPT Female, Silicone Gasket

9025	Thread	Nm3/h
TFM01VG10	1/2"	1-10
TFM02VG16	1/2"	1.6-16
TFM03VG40	1/2"	4-40
TFM04VG60	1"	6-60
TFM05VG160	1"	16-160
TFM06VG250	1"	25-250
TFM07VG350	1"	35-350
Tech Sheet 110831		

Gas/Air, BSPT Male, Silicone Gasket

9025	Thread	Nm 3/h
TFM08VG250	1.1/2"	25-250
TFM09VG350	1.1/2"	35-350
TFM10VG400	1.1/2"	80-400
TFM11VG500	2"	100-500
TFM12VG600	2"	120-600
TFM13VG850	2"	300-850
TFM14VG1200	2"	400-1200
TFM15VG1400	2"	550-1400
Tech Sheet 110831		

Liquid, BSPT Female, Silicone Gasket

9025	Thread	LPM
TFM01VL4	1/2"	0.5-4
TFM02VL7	1/2"	1-7
TFM03VL18	1/2"	8-18
TFM05VL70	1"	10-70
TFM07VL150	1"	20-150
TFM10VL220	1.1/2"	80-220
TFM11VL300	2"	80-300
TFM12VL360	2"	80-360
TFM13VL450	2"	150-450
TFM14VL550	2"	190-550
TFM15VL750	2"	220-750
Tech Sheet 110831		

FMP Series, Panel Type

Working Temperature:
0°C to +60°C

Maximum Working Pressure:
10 bar



Gas/Air, BSPT Male, Silicone Gasket

9025	Thread	Nm 3/h
FMP01VG1	1/2"	0.1-1
FMP02VG6	1/2"	0.6-6
FMP06VG10	1/2"	1-10
FMP07VG16	1/2"	1.6-16
FMP08VG25	1/2"	2.5-25
FMP09VG40	1/2"	4-40
FMP10VG100	1"	10-100
FMP11VG100	1"	20-100
FMP12VG160	1"	16-160
FMP13VG250	1"	25-250
FMP14VG300	1"	30-300
FMP15VG350	1"	35-350
Tech Sheet 110838		

Liquid, BSPT Male, Silicone Gasket

9025	Thread	LPM
FMP03VL100	1/2"	10-100 LPH
FMP04VL160	1/2"	16-160 LPH
FMP06VL4	1/2"	0.5-4
FMP07VL7	1/2"	1-7
FMP08VL11	1/2"	1-11
FMP09VL18	1/2"	2-18
FMP10VL35	1"	5-35
FMP11VL50	1"	10-50
FMP12VL70	1"	10-70
FMP15VL170	1"	10-170
Tech Sheet 110838		

Fluid-Air Components Ltd

FLOW METERS

Low Pressure Flow Meters



Water

0061	Thread	LPM
2018-2929	1/4" Male	0.04-0.4
2018-2937	1/2" Female	0.3-3.75
2018-2938	1/2" Female	1-19
	Tech Sheet 2008	

Air

0061	Thread	SCFM
2040-1626	1/2"	1-15
2040-1634	1/2"	2-20
	Tech Sheet 2008	

Flow Meters



Standard Water Meters, 3/4" BSPT

0061	Thread	LPM
2018-2838	3/4"	2-15
2018-2853	3/4"	4-35
2018-2887	3/4"	15-65
2018-2903	3/4"	20-100
	Tech Sheet 2009	



Water Meters & Flowalert Signal, 3/4" BSPT

0061	Thread	LPM
2018-2911	3/4"	20-100
	Tech Sheet 2009	

Water & Oil



Water, BSPP, fm

0061	Thread	LPM	Max Pressure Bar
2018-1947	1/4"	1-7.5	122
2018-1970	3/4"	10-115	183
2039-9432	1"	15-150	183
	Tech Sheet 2010		

Note: Other flow rate units available on request




Oil, BSPP, fm

0061	Thread	LPM	Max Pressure Bar
2039-9119	1/4"	0.2-1.9	122
2039-9184	3/4"	5-38	183
2018-1913	3/4"	10-115	183
2039-9200	1"	10-115	183
2039-9218	1"	19-150	183
	Tech Sheet 2010		

Fluid-Air Components Ltd

FLOAT LEVEL SWITCHES

Working Temperature:
-10°C to +80°C



Fixed Thermostat, Normally Closed IP65

Top Entry 100mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA100-T40	40
LM1FA100-T50	50
LM1FA100-T60	60
LM1FA100-T70	70
LM1FA100-T80	80
Tech Sheet 110840	

Top Entry 150mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA150-T40	40
LM1FA150-T50	50
LM1FA150-T60	60
LM1FA150-T70	70
LM1FA150-T80	80
Tech Sheet 110840	

Top Entry 200mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA200-T40	40
LM1FA200-T50	50
LM1FA200-T60	60
LM1FA200-T70	70
LM1FA200-T80	80
Tech Sheet 110840	

Top Entry 250mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA250-T40	40
LM1FA250-T50	50
LM1FA250-T60	60
LM1FA250-T70	70
LM1FA250-T80	80
Tech Sheet 110840	

Top Entry 300mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA300-T40	40
LM1FA300-T50	50
LM1FA300-T60	60
LM1FA300-T70	70
LM1FA300-T80	80
Tech Sheet 110840	

Top Entry 350mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA350-T40	40
LM1FA350-T50	50
LM1FA350-T60	60
LM1FA350-T70	70
LM1FA350-T80	80
Tech Sheet 110840	

Top Entry 400mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA400-T40	40
LM1FA400-T50	50
LM1FA400-T60	60
LM1FA400-T70	70
LM1FA400-T80	80
Tech Sheet 110840	

Top Entry 450mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA450-T40	40
LM1FA450-T50	50
LM1FA450-T60	60
LM1FA450-T70	70
LM1FA450-T80	80
Tech Sheet 110840	

Top Entry 500mm, PG 09 DIN 43650 Connection

9025	Actuation Temperature °C
LM1FA500-T40	40
LM1FA500-T50	50
LM1FA500-T60	60
LM1FA500-T70	70
LM1FA500-T80	80
Tech Sheet 110840	

ATEX Stop Ring SPDT IP65

Top Entry, PG 09 DIN 43650 Connection

9025	Length mm
LM2FA100	100
LM2FA150	150
LM2FA200	200
LM2FA250	250
LM2FA300	300
LM2FA350	350
LM2FA400	400
LM2FA450	450
LM2FA500	500
Tech Sheet 110839	

DIY Kit Normally Closed IP65, 1" BSPP Male

Top Entry, PG 09 DIN 43650 Connection

9025	Length mm
LM1TB-1000	1000
LM1TB-0500	500
Tech Sheet 110840	

Fluid-Air Components Ltd

FLOAT LEVEL SWITCHES

Polypropylene Normally Open or Normally Closed

Working Temperature:
-10°C to +80°C

- Fluid specific gravity: >0.8
- Cable length: 300mm



Side Entry, 1/2" NPT

9025
MFS10-N1-2
Tech Sheet 112

Working Temperature:
-40°C to +120°C

- Fluid specific gravity >0.8
- Cable length: 300mm



Top Entry, 1/8" BSPP

9025
MFS17-C-2
Tech Sheet 112

Stainless Steel Normally Closed IP65

- Normally open/normally closed contacts.
- Specific Gravity > 0.
- PG09 DIN 43650 connection

stainless steel



Side Entry, BSPT Male

9025	Thread
RFS-12P-2-SUS304	1/2"
Tech Sheet 111	

FLOAT LEVEL SWITCHES

stainless steel

Stainless Steel Normally Closed IP65

Working Temperature:
-10°C to +80°C

Maximum Working Pressure:
10 bar

- Fluid specific gravitiy:≥ 0.
- Maximum fluid viscosity 150 cS
- Cable length: 500mm



Side Entry, BSPP Male

9025	Thread
LEM7A	1/8"

Working Temperature:
-10°C to +80°C

Maximum Working Pressure:
10 bar

- Fluid specific gravitiy:≥ 0.
- Maximum fluid viscosity 150 cS
- Cable length: 500mm



Top Entry, BSPT Male

9025	Thread
LEM7NC	1/8"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

LIQUID LEVEL GAUGES

EcoFit Gauges

EcoFit liquid level gauges are available up to 1 metre, each gauge above 400mm is supplied with a upper tank bracket. Thread sizes available in G1/4", G3/8", G1/2" BSPP Male

- Suitable for many industrial and domestic usages, subject to pressure and material compatibility

Maximum Working Temperature: +60°C

Pressure: Atmospheric
Lower Body: Brass, nickel plated
Fixing Bolts: Brass, nickel plated
Seals: Viton
Sight Tube: Polycarbonate
Guard Tube: Polycarbonate
Top Cap: Brass
Adaptor: Brass
Tank Seals: Walkertite washer



BSPP

0171	Thread	Centres mm
SEE80100	1/4"	100
SEE80125	1/4"	125
SEE80150	1/4"	150
SEE80200	1/4"	200
SEE80250	1/4"	250
SEE80300	1/4"	300
SEE80350	1/4"	350
SEE80400	1/4"	400
SEE80450	1/4"	450
SEE80500	1/4"	500
SEE80600	1/4"	600
SEE80650	1/4"	650
SEE80700	1/4"	700
SEE80750	1/4"	750
SEE80800	1/4"	800
SEE80850	1/4"	850
SEE80900	1/4"	900
SEE80950	1/4"	950
SEE801000	1/4"	1000
SEE82100	3/8"	100
SEE82125	3/8"	125
SEE82150	3/8"	150
SEE82200	3/8"	200
SEE82250	3/8"	250
SEE82300	3/8"	300
SEE82350	3/8"	350
SEE82400	3/8"	400
SEE82450	3/8"	450
SEE82500	3/8"	500
SEE82600	3/8"	600
SEE82650	3/8"	650
SEE82700	3/8"	700
SEE82750	3/8"	750
SEE82800	3/8"	800
SEE82900	3/8"	900
SEE821000	3/8"	1000
SEE84100	1/2"	100
SEE84125	1/2"	125
SEE84150	1/2"	150
SEE84200	1/2"	200
SEE84250	1/2"	250
SEE84300	1/2"	300
SEE84350	1/2"	350
SEE84400	1/2"	400
SEE84450	1/2"	450
SEE84500	1/2"	500
SEE84600	1/2"	600
SEE84650	1/2"	650
SEE84700	1/2"	700
SEE84750	1/2"	750
SEE84800	1/2"	800
SEE84900	1/2"	900
SEE841000	1/2"	1000
Tech Sheet 20616		

EasyFit Gauges

EasyFit liquid level gauges are available up to 1 metre.

Suitable for many industrial and domestic usages, subject to pressure and material compatibility.

Maximum Working Temperature: +60°C

Maximum Working Pressure: 14 bar (subject to centre distance selected)

Lower Body: Brass
Fixing Bolts: Brass
Seals: Viton
Sight Tube: Polycarbonate
Guard Tube: Polycarbonate
Adaptor: Brass
Tank Seals: Dowty sealing washer



BSPP

0171	Thread	Centres mm
SEE27100	1/4"	100
SEE27150	1/4"	150
SEE27200	1/4"	200
SEE27250	1/4"	250
SEE27300	1/4"	300
SEE27350	1/4"	350
SEE27400	1/4"	400
SEE27450	1/4"	450
SEE27500	1/4"	500
SEE27600	1/4"	600
SEE27650	1/4"	650
SEE27700	1/4"	700
SEE27800	1/4"	800
SEE27850	1/4"	850
SEE27900	1/4"	900
SEE27950	1/4"	950
SEE271000	1/4"	1000
SEE29100	3/8"	100
SEE29150	3/8"	150
SEE29200	3/8"	200
SEE29250	3/8"	250
SEE29300	3/8"	300
SEE29350	3/8"	350
SEE29400	3/8"	400
SEE29450	3/8"	450
SEE29500	3/8"	500
SEE29600	3/8"	600
SEE29650	3/8"	650
SEE29700	3/8"	700
SEE29800	3/8"	800
SEE29850	3/8"	850
SEE29900	3/8"	900
SEE29950	3/8"	950
SEE291000	3/8"	1000
SEE31100	1/2"	100
SEE31150	1/2"	150
SEE31200	1/2"	200
SEE31250	1/2"	250
SEE31300	1/2"	300
SEE31350	1/2"	350
SEE31400	1/2"	400
SEE31450	1/2"	450
SEE31500	1/2"	500
SEE31600	1/2"	600
SEE31650	1/2"	650
SEE31700	1/2"	700
SEE31800	1/2"	800
SEE31850	1/2"	850
SEE31900	1/2"	900
SEE31950	1/2"	950
SEE311000	1/2"	1000
Tech Sheet 20617		

Fluid-Air Components Ltd

LIQUID LEVEL GAUGES

QuickFit Gauges

QuickFit liquid level gauges are available up to 1 metre.

- Suitable for many industrial and domestic usages, subject to pressure and material compatibility

Maximum Working Temperature: +65°C

Maximum Working Pressure: 3 bar

Lower Body: Brass, nickel plated
Fixing Bolts: Brass, nickel plated
Seals: Viton
Sight Tube: Polycarbonate
Adaptor: Brass
Tank Seals: Dowty sealing washer



BSPP

0171	Thread	Centres mm
SEE99100	1/4"	100
SEE99150	1/4"	150
SEE99200	1/4"	200
SEE99250	1/4"	250
SEE99300	1/4"	300
SEE99350	1/4"	350
SEE99400	1/4"	400
SEE99450	1/4"	450
SEE99500	1/4"	500
SEE99600	1/4"	600
SEE99650	1/4"	650
SEE99700	1/4"	700
SEE99800	1/4"	800
SEE99850	1/4"	850
SEE99000	1/4"	900
SEE99950	1/4"	950
SEE991000	1/4"	1000
SEE97100	3/8"	100
SEE97150	3/8"	150
SEE97200	3/8"	200
SEE97250	3/8"	250
SEE97300	3/8"	300
SEE97350	3/8"	350
SEE97400	3/8"	400
SEE97450	3/8"	450
SEE97500	3/8"	500
SEE97600	3/8"	600
SEE97650	3/8"	650
SEE97700	3/8"	700
SEE97800	3/8"	800
SEE97850	3/8"	850
SEE97900	3/8"	900
SEE97950	3/8"	950
SEE971000	3/8"	1000
SEE95100	1/2"	100
SEE95150	1/2"	150
SEE95200	1/2"	200
SEE95250	1/2"	250
SEE95300	1/2"	300
SEE95350	1/2"	350
SEE95400	1/2"	400
SEE95450	1/2"	450
SEE95500	1/2"	500
SEE95600	1/2"	600
SEE95650	1/2"	650
SEE95700	1/2"	700
SEE95800	1/2"	800
SEE95850	1/2"	850
SEE95900	1/2"	900
SEE95950	1/2"	950
SEE951000	1/2"	1000
Tech Sheet 20618		

QuickMount Gauges

Available in G1/2", G3/4" BSPP male.
G3/4" stainless steel model also.

Without Valve, BSPP

0171	Thread	Centres mm
SEE22500P12	1/2"	500
SEE22550P12	1/2"	550
SEE22600P12	1/2"	600
SEE22650P12	1/2"	650
SEE22700P12	1/2"	700
SEE22750P12	1/2"	750
SEE22800P12	1/2"	800
SEE22850P12	1/2"	850
SEE22900P12	1/2"	900
SEE22950P12	1/2"	950
SEE221000P12	1/2"	1000
SEE221125P12	1/2"	1125
SEE221250P12	1/2"	1250
SEE221500P12	1/2"	1500
SEE221600P12	1/2"	1600
SEE221700P12	1/2"	1700
Tech Sheet 10435		

With Valve, Brass Fittings, BSPP

0171	Thread	Centres mm
SEE22280P	3/4"	280
SEE22400P	3/4"	400
SEE22500P	3/4"	500
SEE22600P	3/4"	600
SEE22610P	3/4"	610
SEE22710P	3/4"	710
SEE22750P	3/4"	750
SEE22770P	3/4"	770
SEE22800P	3/4"	800
SEE22825P	3/4"	825
SEE22850P	3/4"	850
SEE22880P	3/4"	880
SEE22900P	3/4"	900
SEE22950P	3/4"	950
SEE221000P	3/4"	1000
SEE221300P	3/4"	1300
SEE221400P	3/4"	1400
Tech Sheet 10435		

With Valve, Stainless Steel Fittings, BSPP

0171	Thread	Centres mm
SEE22S500P	3/4"	500
SEE22S550P	3/4"	550
SEE22S600P	3/4"	600
SEE22S1000P	3/4"	1000
SEE22S2800P	3/4"	2800
SEE22S4200P	3/4"	4200
SEE22S500B	3/4"	500
SEE22S550B	3/4"	550
SEE22S600B	3/4"	600
SEE22S650B	3/4"	650
SEE22S700B	3/4"	700
SEE22S750B	3/4"	750
SEE22S800B	3/4"	800
SEE22S850B	3/4"	850
SEE22S900B	3/4"	900
SEE22S1000B	3/4"	1000
SEE22S2800B	3/4"	2800
Tech Sheet 10435		

The QuickMount valve assemblies are G3/4" BSPP which are manual screwdown with Auto Safety Shut-off (ASV) as the standard configuration, G1/2" BSPP does not come with the safety shut-off valve.

Valves Assemblies: Brass or stainless steel
Collar: Brass
Seals: Viton
Sight Tube: Polycarbonate
Guard Tube: 'C' section aluminium
Tank Seals: Walkertite washer

Maximum Working Temperature: +100°C

Maximum Pressure: 14 bar



Fluid-Air Components Ltd

VISUAL INDICATORS

NORGREN

High Pressure Visual Indicators

- Indicate the presence or absence of a pneumatic signal
- Wide angle of visibility
- Contrasting colours combinations for positive identificatio

Medium:
Compressed air, filtered dry or lubricate
Operation: Visual indicator, diaphragm operated

Materials:
Molded plastic body and internal components, brass connector, steel spring, synthetic rubber diaphragm

Operating Temperature:
+2°C to +66°C*
*Consult our technical service for use below +2°C

Operating Pressure:
0.7 to 8.6 bar full actuation
0-0.14 bar full de-actuation



BSPP

0036	Unactuated Colour	Actuated Colour	Connection
5VS-401-800	Black	Red	G1/8
5VS-402-800	Black	Green	G1/8
5VS-410-800	Red	Black	G1/8
5VS-412-800	Red	Green	G1/8
5VS-420-800	Green	Black	G1/8
5VS-421-800	Green	Red	G1/8
Tech Sheet 71749			

COLD WATER FLOW METER

Single-jet Water Meter

Compact design for most metering applications
Meter Type: Single-jet impeller design
Meter Body Material: Brass, epoxy coated
Drinking Water Approved: (75/33/EEC)
Accuracy: Class B
Installation: Horizontal or vertical
Connection: BSP (nuts, tails and washers supplied)

Maximum Working Temperature:
+30°C

Maximum Working Pressure:
16 bar

WRAS APPROVED MATERIAL



Super Dry Dial

0241	Thread	Length	Gauge Diameter mm	LPM
WATERC1.5D	1/2"	110	15	1.5
WATERC2.5D	3/4"	130	20	2.5
Tech Sheet 10364				

Fluid-Air Components Ltd

THERMOMETERS FOR INDUSTRY

Handheld Thermometers, Type K

- Free traceable Certificate of Calibration included
- Robust waterproof case offering IP66/67 protection
- Backlight, max/min and hold functions
- Integrated rubber seal for durability and complete watertightness
- Designed for reliability and ease of use
- Ideal for industry applications
- Excludes probe

Working Temperature:
-100°C to +1372°C



Therma Waterproof

0065	Colour	IP Rating
232-101	Black	66/67
	Tech Sheet 20016	

K Type Probes



To suit all Thermometers, K Type

0065	Probe Type
123-030	Ribbon Surface
123-046	Waterproof Surface
123-212	High Temperature
	Tech Sheet 20069

Please see tech sheet 20069 for all available K Type products

Room Thermometers

- Accuracy +/- 1°C

Working Temperature:
-30°C to +50°C



Spirit-filled

0065	Description
803-232	White 200mm
803-233	Factory Act 200mm
	Tech Sheet 10273

Bimetal Indicators

Working Temperature:
-30°C to +30°C



52mm Thermometer

0065
800-100
Tech Sheet 20615

Dial Pipe Thermometers

- Wrap-around stainless steel, spring mounting
- 50mm dial
- Stainless steel dial pipe thermometer, supplied with a wrap-around stainless steel spring kit (53mm long) that enables the user to mount each thermometer to a pipe
- For larger pipes it is possible to attach the thermometer to pipework using either tie wraps or wire (not supplied)



50mm Dial

0065	Temperature Range °C
800-951	0°C to +120°C
	Tech Sheet 10271

Magnetic Dial Thermometers

- 50mm dial
- Stainless steel dial thermometer incorporating a magnetic sensing pad for mounting on ferrous metals



50mm Dial

0065	Temperature Range °C
800-950	0°C to +120°C
	Tech Sheet 10272

FT PRO



For **Diesel Transfer Pumps Drain Valves** see page **1636**

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 **Pneumatic & Vacuum** 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 5

Pneumatic & Vacuum

5.01 ISO 6432 Cylinders & Accessories 450-477

5.02 ISO 15552 Cylinders & Accessories 478-515

5.03 Compact Cylinders & Accessories 516-536

5.04 Cartridge & Roundline Cylinders 537-541

5.05 Grippers & Drives 542-544

5.06 Manual & Mechanical Valves 545-574

5.07 Solenoid Valves 575-599

5.08 Pilot Valves 600-610

5.09 Logic, Specialist & ISO Mount Valves 611-636

5.10 Air Preparation 637-704

5.11 Air Boosters 705-706

5.12 Suction Cups 707-749

5.13 Suction Cup Fittings 750-754

5.14 Vacuum Pumps 755-757

5.15 Point of use complete Pump & Cup Units 758-760

5.16 Vacuum Filters 761-762

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 5

5.01 ISO 6432 Cylinders & Accessories — 450-477

- Pneumatic Mini Cylinders
- Stainless Steel Mini Cylinders
- Round Cylinders
- Mini Air Cylinders
- Mini-ISO Cylinders
- Mountings
- Attachments & Accessories



5.02 ISO 15552 Cylinders & Accessories — 478-515

- ISO 15552 Cylinders
- Reed Switches
- Mountings
- Attachments
- Accessories



5.03 Compact Cylinders & Accessories — 516-536

- Compact Cylinders
- Reed Switches
- Repair Kits
- ISO 21287 Compact Cylinders
- Proximity Sensors
- DFM Guided Drives
- ISO 21287 Cylinders
- ISO Compact Cylinders
- Mountings & Accessories



5.04 Cartridge & Roundline Cylinders — 537-541

- Pneumatic Cylinder & Transmitters
- Round RNDC Cylinders
- Round RNDC Cylinder Accessories
- Roundline Cylinders & Mountings



5.05 Grippers & Drives — 542-544

- Pneumatic Grippers
- Semi-Rotary Drives



5.06 Manual & Mechanical Valves — 545-574

- Panel Mount Valves
- Mechanical & Manual Valves
- VME Roller Valves
- Plunger Valves
- Top Lever Valves
- Aerial Valves
- Push/Pull Valves
- Lever Valves
- Mechanically & Manually Actuated Valves
- Directional Control Valves



5.07 Solenoid Valves — 575-599

- Solenoid Valves
- Solenoid Control Valves
- In-line Piston Spool Valves
- Electrically Actuated Directional Control Valves
- In-line Valves
- Solenoid Actuated Poppet Valves
- Pneumatic Valves
- Manifolds



5.08 Pilot Valves — 600-610

- Pilot Valves
- Pneumatically Operated Valves
- Directional Control Valves
- Solenoid Valves
- 3/2 Pneumatic Valves
- 5/2 Pneumatic Valves
- 5/3 Pneumatic Valves



Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

Pneumatics & Vacuum

5.09 Logic, Specialist & ISO Mount Valves

611-636

- Logic Valves
- Timers & Controls
- ISO Valves
- Non-return Valves
- Directional Control Valves
- Pressure & Vacuum Valves
- Industrial Vibrators
- Ball & Check Valves
- Mufflers
- Proportional Valves
- Exhaust Flow Regulators
- Automatic Valves
- Silencers
- Pneumatic Logic Valves



5.10 Air Preparation

637-704

- Filters, Regulators & Lubriactors
- Soft Start Valves
- Porting Blocks
- Pressure Regulators
- Filter Regulators
- Modular Valves
- Minature FRLs
- Pressure Switches
- Air Treatment Units
- Fixing Brackets
- Accessories



5.11 Air Boosters

705-706


- Pressure Booster
- Air Pressure Boosters



5.12 Suction Cups

707-749


- Single Bellows
- Direct Mount Bellows
- Double Bellows
- Bellows & Cross Groove
- Long Multi Bellows
- Dual Lip Suction Cups
- Oval Universal Cups
- Universal Cups
- Flat Cups
- Flat & Curve Cups
- Mark Free Cups
- Flat Structure
- Deep Cups
- Foam Rubber Cups



5.13 Suction Cup Fittings

750-754


- VU/VB/VF/VBL/VBU/ VBX/VFC Series
- BL5040 Series
- VOBL 35 x 90 Series
- FF Series
- BL5040 Series



5.14 Vacuum Pumps

755-757

- Green Pumps
- VSM Pumps
- VCS Pumps
- Magic Pumps
- Turtle Pumps



5.15 Point of use complete Pump & Cup Units

758-760


- Vacuum Grippers
- Suction Lips



5.16 Vacuum Filters

761-762


- In-line Vacuum Filters
- Replacement Elements
- Vacuum Pump Filters
- Blower Intake Filter
- High Volume Muffler



Fluid-Air Components Ltd

PNEUMATIC ISO 6432 MINI CYLINDERS

Accessories & Mounting Selector



Cylinders
Pages 452-454

Mountings
Pages 454-455

Reed Switches
Page 455

Cylinder Guides
Page 456

Single Acting or Double Acting ISO 6432 Mini Cylinders


FA	Front flange mounting
TC	Front trunnion mounting
SDB	Rear hinge mounting
LB	Foot mounting (pair)
Y	Piston rod clevis
I	Piston rod clevis
F	Piston rod floating joint
U	Piston rod universal joint
Reed Switches	Two wire N/O with LED

Fluid-Air Components Ltd

Technical Information

KA Series

CA type



Bore	A	A1	A2	A3	A4	A5	A6	B	C	C1	C2	D	E	F	G	G1	H	I
8	76	64	46	86	74	–	–	28	12	9.5	5	9.5	5	6	11.5	7	12	12
10	76	64	46	86	74	–	–	28	12	9.5	5	9.5	5	6	11.5	7	12	12
12	91	75	50	105	88	–	–	38	17	10.5	6	10.5	6	9	12.5	8	16	17
16	98	82	56	111	94	111	94	38	17	10.5	6	10.5	6	9	12.5	8	16	17
20	115	95	62	126	106	126	106	44	20	14.5	7.5	14.5	7.5	12	14.5	7.5	20	20
25	126	104	65	137	114.5	137	115	50	22	16	8	16	8	12	16	8	22	22
32	–	–	–	–	125	140	126	58	14	16.5	9	–	–	–	16.5	9	20	30
40	–	–	–	–	158	174	158	69	16	22	12	–	–	–	22	12	24	35

Bore	J	K	L	M	N	O	P	P1	Q	R	S	T	T1	X	V	W	Y
8	2.5	M4 x 0.7	M12 x 1.25	6	16	10	17	4	8	12	15	7	17	M5 x 0.8	4	–	–
10	2.5	M4 x 0.7	M12 x 1.25	6	16	10	17	4	8	12	15	7	17	M5 x 0.8	4	–	–
12	5	M6 x 1.0	M16 x 1.5	6	22	14	20	6	12	16	18	10	22	M5 x 0.8	6	–	5
16	5	M6 x 1.0	M16 x 1.5	6	22	13	22	6	12	16	20	10	22	M5 x 0.8	6	13.5	5
20	6	M8 x 1.25	M22 x 1.5	7	24	11	29	8	16	22	25	12	29	1/8"	8	16.5	6
25	6	M10 x 1.25	M22 x 1.5	7	28	11	33.5	8	16	22	30	17	29	1/8"	10	18.5	8
32	6	M10 x 1.25	M30 x 1.5	7	38	–	37.5	–	–	30	34.5	17	36	1/8"	12	10.5	10
40	7	M12 x 1.25	M38 x 1.5	8	45	–	46.5	–	–	38	42.5	17	46	1/4"	16	12.5	14

KB Series

Ø16 to Ø25

Bore	A	A1	A2	A3	A4	A5	B	C	D
16	98	82	56	111	94	111	38	17	12.1
20	115	95	62	126	106	126	44	20	14.5
25	126	104	65	137	113.5	137	50	22	16

Bore	D1	D2	D3	E	F	G	G1	G2
16	7	9	12.1	6	9	12.5	7.5	9.5
20	7.5	10.5	14.5	8	12	14.5	7.5	10.5
25	8	10.5	14.5	8	12	16	8	12

Bore	H	I	J	K	L	M	O	N
16	16	17	5	M6 x 1.0	M16 x 1.5	6	13	22
20	20	20	6	M8 x 1.25	M22 x 1.5	7	11	24
25	22	22	6	M10 x 1.25	M22 x 1.5	7	11	28

Bore	P	Q	R	S	T	T1	V	W	X
16	22	12	5	20	10	22	6	13.5	M5 x 0.8
20	29	16	6	25	12	29	8	16.5	1.8"
25	33.5	16	9	30	17	29	10	18.5	1/8"

Ø32 & Ø40


Bore	A2	A4	A5	B	C	D	D1	D2	D3	D4
32	68	124	140	58	14	16.5	9	11.5	14.5	7.5
40	89	157.5	174	69	16	22	12	12	21.5	11.5

Bore	D5	G	G1	G2	H	I	J	K
32	11	16.5	9	11.8	20	30	6	M10 x 1.25
40	14	22	12	12	24	35	7	M12 x 1.25


Bore	L	M	N	P	S	T	T1	V	W	X
32	M30 x 1.5	7	38	37.5	34.5	17	36	12	10.5	1/8"
40	M38 x 1.5	8	45	46.5	42.5	17	46	16	12.5	1/4"

KC Series

CA type




Inner Structure



No.	Item	Material
1	Rod	304
2	Rod nut	Carbon steel
3	Front cover packing	NBR
4	Front cover nut	Carbon steel
5	Bushing	Wear-resistant material
6	Front cover	Aluminium
7	Barrel	304
8	Bumper	TPU
9	Piston	303*
10	Piston O-ring	NBR
11	Wear ring	Wear-resistant material
12	Nut	Carbon steel
13	Back cover	Aluminium allow

*16-40 bore: aluminium alloy.

CM type



Bore	A			A1		
Stroke	0-50	51-100	101-150	0-50	51-100	101-150
8	101	–	–	89	–	–
10	101	–	–	89	–	–
12	116	–	–	100	–	–
16	123	148	–	107	132	–
20	140	165	190	120	145	170
25	151	176	201	129	154	179
32	–	–	–	–	–	–
40	–	–	–	–	–	–

Bore	A4			A5		
Stroke	0-50	51-100	101-150	0-50	51-100	101-150
8	99	–	–	–	–	–
10	99	–	–	–	–	–
12	113	–	–	–	–	–
16	119	144	–	136	161	–
20	131	156	181	151	176	201
25	139.5	164.5	189.5	162	187	212
32	150	175	200	165	190	215
40	183	208	233	199	224	249

Bore	A2			A3		
Stroke	0-50	51-100	101-150	0-50	51-100	101-150
8	71	–	–	111	–	–
10	71	–	–	111	–	–
12	75	–	–	130	–	–
16	81	106	–	136	161	–
20	87	112	137	151	176	201
25	90	115	140	162	187	212
32	–	–	–	–	–	–
40	–	–	–	–	–	–

Bore	A6					
Stroke	0-50	51-100	101-150	B	C	C1	C2
8	–	–	–	28	12	9.5	5
10	–	–	–	28	12	9.5	5
12	–	–	–	38	17	10.5	5
16	119	144	–	38	17	10.5	5
20	131	156	181	44	20	14.5	7.5
25	140	165	190	50	22	16	8
32	151	176	201	58	14	16.5	9
40	183	208	233	69	16	22	12

FAC
Fluid-Air Components Ltd

PNEUMATIC CYLINDERS

ISO 6432 Mini Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated cushioning-bumper.
Please note: Bore sizes 8mm-12mm and 32mm-40mm are available on a lead time. Please contact our sales office for details.

Working Temperature:
-20°C to +70°C

Working Pressure:
2 to 10 bar

2 Year Warranty



Stainless Steel Piston Rod and Barrel as Standard

Magnetic Single Acting

0334	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KC-8X10-S-CA	8	10	M5	M12 x 1.25	M4 x 0.7
KC-8X15-S-CA	8	15	M5	M12 x 1.25	M4 x 0.7
KC-8X20-S-CA	8	20	M5	M12 x 1.25	M4 x 0.7
KC-8X25-S-CA	8	25	M5	M12 x 1.25	M4 x 0.7
KC-8X30-S-CA	8	30	M5	M12 x 1.25	M4 x 0.7
KC-8X40-S-CA	8	40	M5	M12 x 1.25	M4 x 0.7
KC-8X50-S-CA	8	50	M5	M12 x 1.25	M4 x 0.7
KC-10X10-S-CA	10	10	M5	M12 x 1.25	M4 x 0.7
KC-10X15-S-CA	10	15	M5	M12 x 1.25	M4 x 0.7
KC-10X20-S-CA	10	20	M5	M12 x 1.25	M4 x 0.7
KC-10X25-S-CA	10	25	M5	M12 x 1.25	M4 x 0.7
KC-10X30-S-CA	10	30	M5	M12 x 1.25	M4 x 0.7
KC-10X40-S-CA	10	40	M5	M12 x 1.25	M4 x 0.7
KC-10X50-S-CA	10	50	M5	M12 x 1.25	M4 x 0.7
KC-12X10-S-CA	12	10	M5	M16 x 1.5	M6 x 1.0
KC-12X15-S-CA	12	15	M5	M16 x 1.5	M6 x 1.0
KC-12X20-S-CA	12	20	M5	M16 x 1.5	M6 x 1.0
KC-12X25-S-CA	12	25	M5	M16 x 1.5	M6 x 1.0
KC-12X30-S-CA	12	30	M5	M16 x 1.5	M6 x 1.0
KC-12X40-S-CA	12	40	M5	M16 x 1.5	M6 x 1.0
KC-12X50-S-CA	12	50	M5	M16 x 1.5	M6 x 1.0
KC-16X10-S-CA	16	10	M5	M16 x 1.5	M6 x 1.0
KC-16X15-S-CA	16	15	M5	M16 x 1.5	M6 x 1.0
KC-16X20-S-CA	16	20	M5	M16 x 1.5	M6 x 1.0
KC-16X25-S-CA	16	25	M5	M16 x 1.5	M6 x 1.0
KC-16X30-S-CA	16	30	M5	M16 x 1.5	M6 x 1.0
KC-16X40-S-CA	16	40	M5	M16 x 1.5	M6 x 1.0
KC-16X50-S-CA	16	50	M5	M16 x 1.5	M6 x 1.0
KC-16X60-S-CA	16	60	M5	M16 x 1.5	M6 x 1.0
KC-16X75-S-CA	16	75	M5	M16 x 1.5	M6 x 1.0
KC-16X80-S-CA	16	80	M5	M16 x 1.5	M6 x 1.0
KC-16X100-S-CA	16	100	M5	M16 x 1.5	M6 x 1.0
KC-20X10-S-CA	20	10	1/8"	M22 x 1.5	M8 x 1.25
KC-20X15-S-CA	20	15	1/8"	M22 x 1.5	M8 x 1.25
KC-20X20-S-CA	20	20	1/8"	M22 x 1.5	M8 x 1.25
KC-20X25-S-CA	20	25	1/8"	M22 x 1.5	M8 x 1.25
KC-20X30-S-CA	20	30	1/8"	M22 x 1.5	M8 x 1.25
KC-20X40-S-CA	20	40	1/8"	M22 x 1.5	M8 x 1.25
KC-20X50-S-CA	20	50	1/8"	M22 x 1.5	M8 x 1.25
KC-20X60-S-CA	20	60	1/8"	M22 x 1.5	M8 x 1.25
KC-20X75-S-CA	20	75	1/8"	M22 x 1.5	M8 x 1.25
KC-20X80-S-CA	20	80	1/8"	M22 x 1.5	M8 x 1.25

0334	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KC-20X100-S-CA	20	100	1/8"	M22 x 1.5	M8 x 1.25
KC-20X125-S-CA	20	125	1/8"	M22 x 1.5	M8 x 1.25
KC-20X150-S-CA	20	150	1/8"	M22 x 1.5	M8 x 1.25
KC-25X10-S-CA	25	10	1/8"	M22 x 1.5	M10 x 1.25
KC-25X20-S-CA	25	20	1/8"	M22 x 1.5	M10 x 1.25
KC-25X25-S-CA	25	25	1/8"	M22 x 1.5	M10 x 1.25
KC-25X30-S-CA	25	30	1/8"	M22 x 1.5	M10 x 1.25
KC-25X40-S-CA	25	40	1/8"	M22 x 1.5	M10 x 1.25
KC-25X50-S-CA	25	50	1/8"	M22 x 1.5	M10 x 1.25
KC-25X60-S-CA	25	60	1/8"	M22 x 1.5	M10 x 1.25
KC-25X75-S-CA	25	75	1/8"	M22 x 1.5	M10 x 1.25
KC-25X80-S-CA	25	80	1/8"	M22 x 1.5	M10 x 1.25
KC-25X100-S-CA	25	100	1/8"	M22 x 1.5	M10 x 1.25
KC-25X125-S-CA	25	125	1/8"	M22 x 1.5	M10 x 1.25
KC-25X150-S-CA	25	150	1/8"	M22 x 1.5	M10 x 1.25
KC-32X10-S-CM	32	10	1/8"	M30 x 1.5	M10 x 1.25
KC-32X15-S-CM	32	15	1/8"	M30 x 1.5	M10 x 1.25
KC-32X20-S-CM	32	20	1/8"	M30 x 1.5	M10 x 1.25
KC-32X25-S-CM	32	25	1/8"	M30 x 1.5	M10 x 1.25
KC-32X30-S-CM	32	30	1/8"	M30 x 1.5	M10 x 1.25
KC-32X40-S-CM	32	40	1/8"	M30 x 1.5	M10 x 1.25
KC-32X50-S-CM	32	50	1/8"	M30 x 1.5	M10 x 1.25
KC-32X60-S-CM	32	60	1/8"	M30 x 1.5	M10 x 1.25
KC-32X75-S-CM	32	75	1/8"	M30 x 1.5	M10 x 1.25
KC-32X80-S-CM	32	80	1/8"	M30 x 1.5	M10 x 1.25
KC-32X100-S-CM	32	100	1/8"	M30 x 1.5	M10 x 1.25
KC-32X125-S-CM	32	125	1/8"	M30 x 1.5	M10 x 1.25
KC-32X150-S-CM	32	150	1/8"	M30 x 1.5	M10 x 1.25
KC-40X10-S-CM	40	10	1/4"	M38 x 1.5	M12 x 1.25
KC-40X15-S-CM	40	15	1/4"	M38 x 1.5	M12 x 1.25
KC-40X20-S-CM	40	20	1/4"	M38 x 1.5	M12 x 1.25
KC-40X25-S-CM	40	25	1/4"	M38 x 1.5	M12 x 1.25
KC-40X30-S-CM	40	30	1/4"	M38 x 1.5	M12 x 1.25
KC-40X40-S-CM	40	40	1/4"	M38 x 1.5	M12 x 1.25
KC-40X50-S-CM	40	50	1/4"	M38 x 1.5	M12 x 1.25
KC-40X60-S-CM	40	60	1/4"	M38 x 1.5	M12 x 1.25
KC-40X75-S-CM	40	75	1/4"	M38 x 1.5	M12 x 1.25
KC-40X80-S-CM	40	80	1/4"	M38 x 1.5	M12 x 1.25
KC-40X100-S-CM	40	100	1/4"	M38 x 1.5	M12 x 1.25
KC-40X125-S-CM	40	125	1/4"	M38 x 1.5	M12 x 1.25
KC-40X150-S-CM	40	150	1/4"	M38 x 1.5	M12 x 1.25

Tech Sheet 3001

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


ISO 6432 Mini Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated cushioning KA-Bumper, KB-Adjustable.
Please note: Bore sizes 32mm-40mm are available on a lead time. Please contact our sales office for details.

2 Year Warranty

Working Temperature: -20°C to +70°C

Working Pressure: 1 to 10 bar



Stainless Steel Piston Rod and Barrel as Standard

Magnetic Double Acting

0334	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KA-8X15-S-CA	8	15	M5	M12 x 1.25	M4 x 0.7
KA-8X20-S-CA	8	20	M5	M12 x 1.25	M4 x 0.7
KA-8X25-S-CA	8	25	M5	M12 x 1.25	M4 x 0.7
KA-8X30-S-CA	8	30	M5	M12 x 1.25	M4 x 0.7
KA-8X40-S-CA	8	40	M5	M12 x 1.25	M4 x 0.7
KA-8X50-S-CA	8	50	M5	M12 x 1.25	M4 x 0.7
KA-8X60-S-CA	8	60	M5	M12 x 1.25	M4 x 0.7
KA-8X75-S-CA	8	75	M5	M12 x 1.25	M4 x 0.7
KA-8X80-S-CA	8	80	M5	M12 x 1.25	M4 x 0.7
KA-8X100-S-CA	8	100	M5	M12 x 1.25	M4 x 0.7
KA-8X125-S-CA	8	125	M5	M12 x 1.25	M4 x 0.7
KA-8X150-S-CA	8	150	M5	M12 x 1.25	M4 x 0.7
KA-10X10-S-CA	10	10	M5	M12 x 1.25	M4 x 0.7
KA-10X15-S-CA	10	15	M5	M12 x 1.25	M4 x 0.7
KA-10X20-S-CA	10	20	M5	M12 x 1.25	M4 x 0.7
KA-10X25-S-CA	10	25	M5	M12 x 1.25	M4 x 0.7
KA-10X30-S-CA	10	30	M5	M12 x 1.25	M4 x 0.7
KA-10X40-S-CA	10	40	M5	M12 x 1.25	M4 x 0.7
KA-10X50-S-CA	10	50	M5	M12 x 1.25	M4 x 0.7
KA-10X60-S-CA	10	60	M5	M12 x 1.25	M4 x 0.7
KA-10X75-S-CA	10	75	M5	M12 x 1.25	M4 x 0.7
KA-10X80-S-CA	10	80	M5	M12 x 1.25	M4 x 0.7
KA-10X100-S-CA	10	100	M5	M12 x 1.25	M4 x 0.7
KA-10X125-S-CA	10	125	M5	M12 x 1.25	M4 x 0.7
KA-10X150-S-CA	10	150	M5	M12 x 1.25	M4 x 0.7
KA-10X160-S-CA	10	160	M5	M12 x 1.25	M4 x 0.7
KA-10X175-S-CA	10	175	M5	M12 x 1.25	M4 x 0.7
KA-10X200-S-CA	10	200	M5	M12 x 1.25	M4 x 0.7
KA-12X10-S-CA	12	10	M5	M16 x 1.5	M6 x 1.0
KA-12X15-S-CA	12	15	M5	M16 x 1.5	M6 x 1.0
KA-12X20-S-CA	12	20	M5	M16 x 1.5	M6 x 1.0
KA-12X25-S-CA	12	25	M5	M16 x 1.5	M6 x 1.0
KA-12X30-S-CA	12	30	M5	M16 x 1.5	M6 x 1.0
KA-12X40-S-CA	12	40	M5	M16 x 1.5	M6 x 1.0
KA-12X50-S-CA	12	50	M5	M16 x 1.5	M6 x 1.0
KA-12X60-S-CA	12	60	M5	M16 x 1.5	M6 x 1.0
KA-12X75-S-CA	12	75	M5	M16 x 1.5	M6 x 1.0
KA-12X80-S-CA	12	80	M5	M16 x 1.5	M6 x 1.0
KA-12X100-S-CA	12	100	M5	M16 x 1.5	M6 x 1.0
KA-12X125-S-CA	12	125	M5	M16 x 1.5	M6 x 1.0
KA-12X150-S-CA	12	150	M5	M16 x 1.5	M6 x 1.0
KA-12X175-S-CA	12	175	M5	M16 x 1.5	M6 x 1.0
KA-12X200-S-CA	12	200	M5	M16 x 1.5	M6 x 1.0
KA-12X250-S-CA	12	250	M5	M16 x 1.5	M6 x 1.0
KB-16X10-S-CA	16	10	M5	M16 x 1.5	M6 x 1.0
KB-16X15-S-CA	16	15	M5	M16 x 1.5	M6 x 1.0
KB-16X20-S-CA	16	20	M5	M16 x 1.5	M6 x 1.0
KB-16X25-S-CA	16	25	M5	M16 x 1.5	M6 x 1.0
KB-16X30-S-CA	16	30	M5	M16 x 1.5	M6 x 1.0

0334	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KB-16X40-S-CA	16	40	M5	M16 x 1.5	M6 x 1.0
KB-16X50-S-CA	16	50	M5	M16 x 1.5	M6 x 1.0
KB-16X60-S-CA	16	60	M5	M16 x 1.5	M6 x 1.0
KB-16X75-S-CA	16	75	M5	M16 x 1.5	M6 x 1.0
KB-16X80-S-CA	16	80	M5	M16 x 1.5	M6 x 1.0
KB-16X100-S-CA	16	100	M5	M16 x 1.5	M6 x 1.0
KB-16X125-S-CA	16	125	M5	M16 x 1.5	M6 x 1.0
KB-16X150-S-CA	16	150	M5	M16 x 1.5	M6 x 1.0
KB-16X160-S-CA	16	160	M5	M16 x 1.5	M6 x 1.0
KB-16X175-S-CA	16	175	M5	M16 x 1.5	M6 x 1.0
KB-16X200-S-CA	16	200	M5	M16 x 1.5	M6 x 1.0
KB-16X250-S-CA	16	250	M5	M16 x 1.5	M6 x 1.0
KB-16X300-S-CA	16	300	M5	M16 x 1.5	M6 x 1.0
KB-20X10-S-CA	20	10	1/8"	M22 x 1.5	M8 x 1.25
KB-20X15-S-CA	20	15	1/8"	M22 x 1.5	M8 x 1.25
KB-20X20-S-CA	20	20	1/8"	M22 x 1.5	M8 x 1.25
KB-20X25-S-CA	20	25	1/8"	M22 x 1.5	M8 x 1.25
KB-20X30-S-CA	20	30	1/8"	M22 x 1.5	M8 x 1.25
KB-20X40-S-CA	20	40	1/8"	M22 x 1.5	M8 x 1.25
KB-20X50-S-CA	20	50	1/8"	M22 x 1.5	M8 x 1.25
KB-20X60-S-CA	20	60	1/8"	M22 x 1.5	M8 x 1.25
KB-20X75-S-CA	20	75	1/8"	M22 x 1.5	M8 x 1.25
KB-20X80-S-CA	20	80	1/8"	M22 x 1.5	M8 x 1.25
KB-20X100-S-CA	20	100	1/8"	M22 x 1.5	M8 x 1.25
KB-20X125-S-CA	20	125	1/8"	M22 x 1.5	M8 x 1.25
KB-20X150-S-CA	20	150	1/8"	M22 x 1.5	M8 x 1.25
KB-20X160-S-CA	20	160	1/8"	M22 x 1.5	M8 x 1.25
KB-20X175-S-CA	20	175	1/8"	M22 x 1.5	M8 x 1.25
KB-20X200-S-CA	20	200	1/8"	M22 x 1.5	M8 x 1.25
KB-20X250-S-CA	20	250	1/8"	M22 x 1.5	M8 x 1.25
KB-20X300-S-CA	20	300	1/8"	M22 x 1.5	M8 x 1.25
KB-20X350-S-CA	20	350	1/8"	M22 x 1.5	M8 x 1.25
KB-20X400-S-CA	20	400	1/8"	M22 x 1.5	M8 x 1.25
KB-20X450-S-CA	20	450	1/8"	M22 x 1.5	M8 x 1.25
KB-20X500-S-CA	20	500	1/8"	M22 x 1.5	M8 x 1.25
KB-25X10-S-CA	25	10	1/8"	M22 x 1.5	M10 x 1.25
KB-25X15-S-CA	25	15	1/8"	M22 x 1.5	M10 x 1.25
KB-25X20-S-CA	25	20	1/8"	M22 x 1.5	M10 x 1.25
KB-25X25-S-CA	25	25	1/8"	M22 x 1.5	M10 x 1.25
KB-25X30-S-CA	25	30	1/8"	M22 x 1.5	M10 x 1.25
KB-25X40-S-CA	25	40	1/8"	M22 x 1.5	M10 x 1.25
KB-25X50-S-CA	25	50	1/8"	M22 x 1.5	M10 x 1.25
KB-25X60-S-CA	25	60	1/8"	M22 x 1.5	M10 x 1.25
KB-25X75-S-CA	25	75	1/8"	M22 x 1.5	M10 x 1.25
KB-25X80-S-CA	25	80	1/8"	M22 x 1.5	M10 x 1.25
KB-25X100-S-CA	25	100	1/8"	M22 x 1.5	M10 x 1.25
KB-25X125-S-CA	25	125	1/8"	M22 x 1.5	M10 x 1.25
KB-25X150-S-CA	25	150	1/8"	M22 x 1.5	M10 x 1.25
			Tech Sheet 3001		

Further sizes in this range continued on next page

FAC Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

PNEUMATIC CYLINDERS


ISO 6432 Mini Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated cushioning KA-Bumper, KB-Adjustable.
Please note: Bore sizes 32mm-40mm are available on a lead time.
Please contact our sales office for details.

Working Temperature:
-20°C to +70°C

Working Pressure:
1 to 10 bar

2 Year Warranty



Stainless Steel Piston Rod and Barrel as Standard

Magnetic Double Acting

0334	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KB-25X160-S-CA	25	160	1/8"	M22 x 1.5	M10 x 1.25
KB-25X175-S-CA	25	175	1/8"	M22 x 1.5	M10 x 1.25
KB-25X200-S-CA	25	200	1/8"	M22 x 1.5	M10 x 1.25
KB-25X250-S-CA	25	250	1/8"	M22 x 1.5	M10 x 1.25
KB-25X300-S-CA	25	300	1/8"	M22 x 1.5	M10 x 1.25
KB-25X350-S-CA	25	350	1/8"	M22 x 1.5	M10 x 1.25
KB-25X400-S-CA	25	400	1/8"	M22 x 1.5	M10 x 1.25
KB-25X450-S-CA	25	450	1/8"	M22 x 1.5	M10 x 1.25
KB-25X500-S-CA	25	500	1/8"	M22 x 1.5	M10 x 1.25
KB-25X600-S-CA	25	600	1/8"	M22 x 1.5	M10 x 1.25
KB-32X10-S-CM	32	10	1/8"	M30 x 1.5	M10 x 1.25
KB-32X15-S-CM	32	15	1/8"	M30 x 1.5	M10 x 1.25
KB-32X20-S-CM	32	20	1/8"	M30 x 1.5	M10 x 1.25
KB-32X25-S-CM	32	25	1/8"	M30 x 1.5	M10 x 1.25
KB-32X30-S-CM	32	30	1/8"	M30 x 1.5	M10 x 1.25
KB-32X40-S-CM	32	40	1/8"	M30 x 1.5	M10 x 1.25
KB-32X50-S-CM	32	50	1/8"	M30 x 1.5	M10 x 1.25
KB-32X60-S-CM	32	60	1/8"	M30 x 1.5	M10 x 1.25
KB-32X75-S-CM	32	75	1/8"	M30 x 1.5	M10 x 1.25
KB-32X80-S-CM	32	80	1/8"	M30 x 1.5	M10 x 1.25
KB-32X100-S-CM	32	100	1/8"	M30 x 1.5	M10 x 1.25
KB-32X125-S-CM	32	125	1/8"	M30 x 1.5	M10 x 1.25
KB-32X150-S-CM	32	150	1/8"	M30 x 1.5	M10 x 1.25
KB-32X160-S-CM	32	160	1/8"	M30 x 1.5	M10 x 1.25
KB-32X175-S-CM	32	175	1/8"	M30 x 1.5	M10 x 1.25
KB-32X200-S-CM	32	200	1/8"	M30 x 1.5	M10 x 1.25
KB-32X250-S-CM	32	250	1/8"	M30 x 1.5	M10 x 1.25
KB-32X300-S-CM	32	300	1/8"	M30 x 1.5	M10 x 1.25
KB-32X350-S-CM	32	350	1/8"	M30 x 1.5	M10 x 1.25
KB-32X400-S-CM	32	400	1/8"	M30 x 1.5	M10 x 1.25
KB-32X450-S-CM	32	450	1/8"	M30 x 1.5	M10 x 1.25
KB-32X500-S-CM	32	500	1/8"	M30 x 1.5	M10 x 1.25
KB-32X600-S-CM	32	600	1/8"	M30 x 1.5	M10 x 1.25
KB-40X10-S-CM	40	10	1/4"	M38 x 1.5	M12 x 1.25
KB-40X15-S-CM	40	15	1/4"	M38 x 1.5	M12 x 1.25
KB-40X20-S-CM	40	20	1/4"	M38 x 1.5	M12 x 1.25
KB-40X25-S-CM	40	25	1/4"	M38 x 1.5	M12 x 1.25
KB-40X30-S-CM	40	30	1/4"	M38 x 1.5	M12 x 1.25
KB-40X40-S-CM	40	40	1/4"	M38 x 1.5	M12 x 1.25
KB-40X50-S-CM	40	50	1/4"	M38 x 1.5	M12 x 1.25
KB-40X60-S-CM	40	60	1/4"	M38 x 1.5	M12 x 1.25
KB-40X75-S-CM	40	75	1/4"	M38 x 1.5	M12 x 1.25
KB-40X80-S-CM	40	80	1/4"	M38 x 1.5	M12 x 1.25
KB-40X100-S-CM	40	100	1/4"	M38 x 1.5	M12 x 1.25
KB-40X125-S-CM	40	125	1/4"	M38 x 1.5	M12 x 1.25
KB-40X150-S-CM	40	150	1/4"	M38 x 1.5	M12 x 1.25
KB-40X160-S-CM	40	160	1/4"	M38 x 1.5	M12 x 1.25
KB-40X175-S-CM	40	175	1/4"	M38 x 1.5	M12 x 1.25
KB-40X200-S-CM	40	200	1/4"	M38 x 1.5	M12 x 1.25
KB-40X250-S-CM	40	250	1/4"	M38 x 1.5	M12 x 1.25
KB-40X300-S-CM	40	300	1/4"	M38 x 1.5	M12 x 1.25
KB-40X350-S-CM	40	350	1/4"	M38 x 1.5	M12 x 1.25
KB-40X400-S-CM	40	400	1/4"	M38 x 1.5	M12 x 1.25
KB-40X450-S-CM	40	450	1/4"	M38 x 1.5	M12 x 1.25
KB-40X500-S-CM	40	500	1/4"	M38 x 1.5	M12 x 1.25
KB-40X600-S-CM	40	600	1/4"	M38 x 1.5	M12 x 1.25

Tech Sheet 3001

ISO 6432 Mountings



Front Flange Mounting FA

0334	Bore mm
F-KA8FA	8/10
F-KA12FA	12/16
F-KA20FA	20/25

Tech Sheet 3002



Front Trunnion Mounting TC

0334	Bore mm
F-KA8TC	8/10
F-KA12TC	12/16
F-KA20TC	20/25
F-KA32TC	32
F-KA40TC	40

Tech Sheet 3003

Fluid-Air Components Ltd

ISO 6432 Mountings



Rear Hinge Mounting SDB

0334	Bore mm
F-KA8SDB	8/10
F-KA12SDB	12/16
F-KA20SDB	20/25
F-KA32SDB	32
F-KA40SDB	40
Tech Sheet 3004	



Foot Mounting LB, (Pair)

0334	Bore mm
F-KA8LB	8/10
F-KA12LB	12/16
F-KA20LB	20/25
F-KA32LB	32
F-KA40LB	40
Tech Sheet 3005	



Piston Rod Clevis Y

0334	Bore mm	Thread
F-M04070YE	8/10	M4 x 0.7
F-M06100YE	12/16	M6 x 1
F-M08125YE	20	M8 x 1.25
F-M1025YE	25/32	M10 x 1.25
Tech Sheet 3006		



Piston Rod Clevis I

0334	Bore mm	Thread
F-M06100II	12/16	M6 x 1
F-M08125II	20	M8 x 1.25
F-M10125II	25/32	M10 x 1.25
F-M12125II	40	M12 x 1.25
Tech Sheet 3007		



Piston Rod Floating Joint F

0334	Bore mm	Thread
F-M08125F	20	M8 x 1.25
F-M10125F	25/32	M10 x 1.25
F-M12125F	40	M12 x 1.25
Tech Sheet 3008		



Piston Rod Universal Joint U

0334	Bore mm	Thread
F-M04070U	8/10	M4 x 0.7
F-M06100U	12/16	M6 x 1
F-M08125U	20	M8 x 1.25
F-M10125U	25/32	M10 x 1.25
F-M12125U	40	M12 x 1.25
Tech Sheet 3009		

Reed Switches to suit ISO 6432



Two Wire, N/O with LED

0334	Bore mm	Voltage
CS1-M-8	8	5-240V AC/DC
CS1-M-10	10	5-240V AC/DC
CS1-M-12	12	5-240V AC/DC
CS1-M-16	16	5-240V AC/DC
CS1-M-20	20	5-240V AC/DC
CS1-M-25	25	5-240V AC/DC
CS1-M-32	32	5-240V AC/DC
CS1-M-40	40	5-240V AC/DC
Tech Sheet 3010		

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c


ISO 6432 Mini Cylinder Guides


The guide unit allows for standard ISO 6432 cylinder to move loads with high positioning accuracy.

Features and Benefits

- Protection against rotation at high torques.
- High guide precision for cylinder guiding.
- Supplied plain or recirculating ball bearing guides.

2 Year Warranty





With Slide Bearings

0334	Bore mm	Stroke mm
KRF-16X50-0	16	50
KRF-16X100-0	16	100
KRF-16X160-0	16	160
KRF-16X200-0	16	200
KRF-16X250-0	16	250
KRF-16X320-0	16	320
KRF-16X400-0	16	400
KRF-16X500-0	16	500
KRF-20X50-0	20	50
KRF-20X100-0	20	100
KRF-20X160-0	20	160
KRF-20X200-0	20	200
KRF-20X250-0	20	250
KRF-20X320-0	20	320
KRF-20X400-0	20	400
KRF-20X500-0	20	500
KRF-25X50-0	25	50
KRF-25X100-0	25	100
KRF-25X160-0	25	160
KRF-25X200-0	25	200
KRF-25X250-0	25	250
KRF-25X320-0	25	320
KRF-25X400-0	25	400
KRF-25X500-0	25	500
	Tech Sheet 20893	

With Ball Bearings

0334	Bore mm	Stroke mm
KRF-16X50-1	16	50
KRF-16X100-1	16	100
KRF-16X160-1	16	160
KRF-16X200-1	16	200
KRF-16X250-1	16	250
KRF-16X320-1	16	320
KRF-16X400-1	16	400
KRF-16X500-1	16	500
KRF-20X50-1	20	50
KRF-20X100-1	20	100
KRF-20X160-1	20	160
KRF-20X200-1	20	200
KRF-20X250-1	20	250
KRF-20X320-1	20	320
KRF-20X400-1	20	400
KRF-20X500-1	20	500
KRF-25X50-1	25	50
KRF-25X100-1	25	100
KRF-25X160-1	25	160
KRF-25X200-1	25	200
KRF-25X250-1	25	250
KRF-25X320-1	25	320
KRF-25X400-1	25	400
KRF-25X500-1	25	500
	Tech Sheet 20894	


Fluid-Air Components Ltd

PNEUMATIC STAINLESS STEEL ISO 6432 MINI CYLINDERS

Accessories & Mounting Selector

stainless steel

FT PRO



Double Acting ISO 6432 Stainless Steel Mini Cylinders

FA	Front flange mounting
SDB	Rear hinge mounting
LB	Foot mounting (pair)
Y	Piston rod clevis
Lock Nut	
Piston Rod Lock Nut	
Reed Switches	Two wire N/O with LED
Reed Switch Bracket	

Cylinders Pages 452-454

Mountings Pages 454-455

Reed Switches Page 455

Cylinder Guides Page 456

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PNEUMATIC STAINLESS STEEL ISO 6432 MINI CYLINDERS


Technical Information

stainless steel


FT PRO

Component Parts & Materials

No.	Item	Material
1	Nut	Steel AISI 304
2	Piston rod	Steel AISI 306
3	Rod seal	Polyurethane
4	Front cover	Steel AISI 304
5	Nut	Steel AISI 304
6	Bearing	Sintered bronze
7	O-ring seals	Nitrile
8	Bumper	Neoprene
9	Piston	Brass
10	Piston seal	Polyurethane
11	Magnet	Plastoferrite
12	Mini cylinder shape body	Steel AISI 304
13	Back cover	Steel AISI 304



Double Acting Magnetic



KASS...

Ø mm	A	A1	B	C	D	E	F	G	K	L	M	N	P	R	CH
16	M6	6	M16 x 1.5	12	19	6	18	M5	22	16	109	9	53	82	5
20	M8	8	M22 x 1.5	16	27	8	20	1/8G	24	20	131	12	67	95	7
25	M10 x 1.25	10	M22 x 1.5	16	30	8	22	1/8G	28	22	140	12	68	104	9

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Stainless Steel ISO 6432 Mini Cylinders

Full stainless steel double acting, magnetic, bumper cushioned cylinders.
Available in:
Bore sizes: 16, 20 and 25mm
Stroke lengths: 10, 25, 50, 80, 100, 125, 160, 200, 250 and 320mm
Intermediate strokes are available upon request, please contact our Business Development Team.
Suitable for all industrial fields, but particularly suitable for use in corrosive environments.

2 Year Warranty

Working Temperature:
0°C to +80°C

Operating Pressure:
2-10 bar



stainless steel

Magnetic Double Acting

0333	Bore mm	Stroke mm	Thread	Locknut Thread	Piston Rod Thread
KASS-16X10-S-CA	16	10	M5	M16 x 1.5	M6
KASS-16X25-S-CA	16	25	M5	M16 x 1.5	M6
KASS-16X50-S-CA	16	50	M5	M16 x 1.5	M6
KASS-16X80-S-CA	16	80	M5	M16 x 1.5	M6
KASS-16X100-S-CA	16	100	M5	M16 x 1.5	M6
KASS-16X125-S-CA	16	125	M5	M16 x 1.5	M6
KASS-16X160-S-CA	16	160	M5	M16 x 1.5	M6
KASS-16X200-S-CA	16	200	M5	M16 x 1.5	M6
KASS-16X250-S-CA	16	250	M5	M16 x 1.5	M6
KASS-16X320-S-CA	16	320	M5	M16 x 1.5	M6
KASS-20X10-S-CA	20	10	1/8"	M22 x 1.5	M8
KASS-20X25-S-CA	20	25	1/8"	M22 x 1.5	M8
KASS-20X50-S-CA	20	50	1/8"	M22 x 1.5	M8
KASS-20X80-S-CA	20	80	1/8"	M22 x 1.5	M8
KASS-20X100-S-CA	20	100	1/8"	M22 x 1.5	M8
KASS-20X125-S-CA	20	125	1/8"	M22 x 1.5	M8
KASS-20X160-S-CA	20	160	1/8"	M22 x 1.5	M8
KASS-20X200-S-CA	20	200	1/8"	M22 x 1.5	M8
KASS-20X250-S-CA	20	250	1/8"	M22 x 1.5	M8
KASS-20X320-S-CA	20	320	1/8"	M22 x 1.5	M8
KASS-25X10-S-CA	25	10	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X25-S-CA	25	25	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X50-S-CA	25	50	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X80-S-CA	25	80	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X100-S-CA	25	100	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X125-S-CA	25	125	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X160-S-CA	25	160	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X200-S-CA	25	200	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X250-S-CA	25	250	1/8"	M22 x 1.5	M10 x 1.25
KASS-25X320-S-CA	25	320	1/8"	M22 x 1.5	M10 x 1.25
		Tech Sheet 10287			











FAC
Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

Stainless Steel ISO 6432 Mountings



stainless steel

Front Flange Mounting FA

0333	Bore mm
F-KASS16FA	16
F-KASS20FA	20/25



stainless steel

Foot Mounting LB, (single)

0333	Bore mm
F-KASS16LB	16
F-KASS20LB	20/25



stainless steel

Rear Hinge Mounting SDB

0333	Bore mm
F-KASS16SDB	16
F-KASS20SDB	20/25



stainless steel

Piston Rod Clevis Y

0333	Bore mm	Thread
F-KASS16Y	16	M6 x 1
F-KASS20Y	20	M8 x 1.25
F-KASS25Y	25	M10 x 1.25



stainless steel

Lock Nut

0333	Bore mm	Thread
F-KASS16LN	16	M16 x 1.5
F-KASS20LN	20/25	M22 x 1.5



stainless steel

Piston Rod Lock Nut

0333	Bore mm	Thread
F-KASS16PLN	16	M6
F-KASS20PLN	20	M8
F-KASS25PLN	25	M10 x 1.25

Reed Switches



Two Wire, N/O with LED

0333	Voltage
KRS-2.5	5-240V AC/DC

Reed Switch Mounting Brackets



0333	Bore mm
RSMC16	16
RSMC20	20
RSMC25	25

Fluid-Air Components Ltd



FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CYLINDERS

For the full range and more information, please contact one of our sales team.

DSNU ROUND CYLINDER CETOP RP 52 P ISO 6432 ★

Features



Product Description

DSNU - 16 - 100 - PPS - A

- DSNU: Cylinder Type
- 16: Bore Size mm
- 100: Stroke Size mm
- PPS: Cushioning
  - PPS - Self adjusting
  - P - Polymer
  - PPV - Adjustable
- A: Magnetic

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DIN ISO 6432 ROUND CYLINDERS, DSNU

Double Acting, Elastic Polymer Cushioning Rings


- Diameter 12-25mm: ISO 6432
- For very high demands on running characteristics, service life and load capacity
- Stainless Steel piston rod
- Comprehensive range of accessories

See page 468 for sensor mounts and sensors

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1.5 to 10 bar (12mm Piston)
1 to 10 bar (Piston: 16, 20, 25)

Elastic Polymer Cushioning





Polymer, Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
19189	12	10	M6	DSNU-12-10-P-A
1908255	12	15	M6	DSNU-12-15-P-A
1908256	12	20	M6	DSNU-12-20-P-A
19190	12	25	M6	DSNU-12-25-P-A
1908257	12	30	M6	DSNU-12-30-P-A
19191	12	40	M6	DSNU-12-40-P-A
19192	12	50	M6	DSNU-12-50-P-A
1908258	12	60	M6	DSNU-12-60-P-A
19193	12	80	M6	DSNU-12-80-P-A
19194	12	100	M6	DSNU-12-100-P-A
19195	12	125	M6	DSNU-12-125-P-A
19196	12	160	M6	DSNU-12-160-P-A
19197	12	200	M6	DSNU-12-200-P-A
19198	16	10	M6	DSNU-16-10-P-A
1908259	16	15	M6	DSNU-16-15-P-A
1908260	16	20	M6	DSNU-16-20-P-A
19199	16	25	M6	DSNU-16-25-P-A
1908261	16	30	M6	DSNU-16-30-P-A
1908262	16	35	M6	DSNU-16-35-P-A
19200	16	40	M6	DSNU-16-40-P-A
19201	16	50	M6	DSNU-16-50-P-A
1908263	16	60	M6	DSNU-16-60-P-A
1908264	16	70	M6	DSNU-16-70-P-A
19202	16	80	M6	DSNU-16-80-P-A
19203	16	100	M6	DSNU-16-100-P-A
19204	16	125	M6	DSNU-16-125-P-A
1908265	16	150	M6	DSNU-16-150-P-A
19205	16	160	M6	DSNU-16-160-P-A
19206	16	200	M6	DSNU-16-200-P-A
Tech Sheet 70225				

Polymer, Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
19207	20	10	M8	DSNU-20-10-P-A
1908282	20	15	M8	DSNU-20-15-P-A
1908283	20	20	M8	DSNU-20-20-P-A
19208	20	25	M8	DSNU-20-25-P-A
1908284	20	30	M8	DSNU-20-30-P-A
1908285	20	35	M8	DSNU-20-35-P-A
19209	20	40	M8	DSNU-20-40-P-A
19210	20	50	M8	DSNU-20-50-P-A
1908286	20	60	M8	DSNU-20-60-P-A
1908287	20	70	M8	DSNU-20-70-P-A
19211	20	80	M8	DSNU-20-80-P-A
19212	20	100	M8	DSNU-20-100-P-A
19213	20	125	M8	DSNU-20-125-P-A
1908288	20	150	M8	DSNU-20-150-P-A
19214	20	160	M8	DSNU-20-160-P-A
19215	20	200	M8	DSNU-20-200-P-A
19216	20	250	M8	DSNU-20-250-P-A
19217	20	300	M8	DSNU-20-300-P-A
34718	20	320	M8	DSNU-20-320-P-A
19218	25	10	M10 x 1.25	DSNU-25-10-P-A
1908305	25	15	M10 x 1.25	DSNU-25-15-P-A
1908306	25	20	M10 x 1.25	DSNU-25-20-P-A
19219	25	25	M10 x 1.25	DSNU-25-25-P-A
1908307	25	30	M10 x 1.25	DSNU-25-30-P-A
1908308	25	35	M10 x 1.25	DSNU-25-35-P-A
19220	25	40	M10 x 1.25	DSNU-25-40-P-A
19221	25	50	M10 x 1.25	DSNU-25-50-P-A
1908309	25	60	M10 x 1.25	DSNU-25-60-P-A
1908310	25	70	M10 x 1.25	DSNU-25-70-P-A
19222	25	80	M10 x 1.25	DSNU-25-80-P-A
19223	25	100	M10 x 1.25	DSNU-25-100-P-A
19224	25	125	M10 x 1.25	DSNU-25-125-P-A
1908311	25	150	M10 x 1.25	DSNU-25-150-P-A
19225	25	160	M10 x 1.25	DSNU-25-160-P-A
19226	25	200	M10 x 1.25	DSNU-25-200-P-A
19227	25	250	M10 x 1.25	DSNU-25-250-P-A
19228	25	300	M10 x 1.25	DSNU-25-300-P-A
34719	25	320	M10 x 1.25	DSNU-25-320-P-A
Tech Sheet 70226				

Fluid-Air Components Ltd

DIN ISO 6432 ROUND CYLINDERS, DSNU

FESTO

Double Acting, Adjustable Pneumatic Cushioning


- Diameter 16-25mm: ISO 6432
- For very high demands on running characteristics, service life and load capacity
- Stainless Steel piston rod
- Comprehensive range of accessories

See page 468 for sensor mounts and sensors

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar

Adjustable Cushioning





Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
1908266	16	10	M6	DSNU-16-10-PPV-A
1908267	16	15	M6	DSNU-16-15-PPV-A
1908268	16	20	M6	DSNU-16-20-PPV-A
33973	16	25	M6	DSNU-16-25-PPV-A
1908269	16	30	M6	DSNU-16-30-PPV-A
1908270	16	35	M6	DSNU-16-35-PPV-A
19229	16	40	M6	DSNU-16-40-PPV-A
19230	16	50	M6	DSNU-16-50-PPV-A
1908271	16	60	M6	DSNU-16-60-PPV-A
1908272	16	70	M6	DSNU-16-70-PPV-A
19231	16	80	M6	DSNU-16-80-PPV-A
19232	16	100	M6	DSNU-16-100-PPV-A
19233	16	125	M6	DSNU-16-125-PPV-A
1908273	16	150	M6	DSNU-16-150-PPV-A
19234	16	160	M6	DSNU-16-160-PPV-A
19235	16	200	M6	DSNU-16-200-PPV-A
		Tech Sheet 70229		

FESTO



For **Festo Tube Regulators**
see page **814**

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
1908289	20	10	M8	DSNU-20-10-PPV-A
1908290	20	15	M8	DSNU-20-15-PPV-A
1908291	20	20	M8	DSNU-20-20-PPV-A
33974	20	25	M8	DSNU-20-25-PPV-A
1908292	20	30	M8	DSNU-20-30-PPV-A
1908293	20	35	M8	DSNU-20-35-PPV-A
19236	20	40	M8	DSNU-20-40-PPV-A
19237	20	50	M8	DSNU-20-50-PPV-A
1908294	20	60	M8	DSNU-20-60-PPV-A
1908295	20	70	M8	DSNU-20-70-PPV-A
19238	20	80	M8	DSNU-20-80-PPV-A
19239	20	100	M8	DSNU-20-100-PPV-A
19240	20	125	M8	DSNU-20-125-PPV-A
1908296	20	150	M8	DSNU-20-150-PPV-A
19241	20	160	M8	DSNU-20-160-PPV-A
19242	20	200	M8	DSNU-20-200-PPV-A
19243	20	250	M8	DSNU-20-250-PPV-A
19244	20	300	M8	DSNU-20-300-PPV-A
34720	20	320	M8	DSNU-20-320-PPV-A
1908312	25	10	M10 x 1.25	DSNU-25-10-PPV-A
1908313	25	15	M10 x 1.25	DSNU-25-15-PPV-A
1908314	25	20	M10 x 1.25	DSNU-25-20-PPV-A
33975	25	25	M10 x 1.25	DSNU-25-25-PPV-A
1908315	25	30	M10 x 1.25	DSNU-25-30-PPV-A
1908316	25	35	M10 x 1.25	DSNU-25-35-PPV-A
19245	25	40	M10 x 1.25	DSNU-25-40-PPV-A
19246	25	50	M10 x 1.25	DSNU-25-50-PPV-A
1908317	25	60	M10 x 1.25	DSNU-25-60-PPV-A
1908318	25	70	M10 x 1.25	DSNU-25-70-PPV-A
19247	25	80	M10 x 1.25	DSNU-25-80-PPV-A
19248	25	100	M10 x 1.25	DSNU-25-100-PPV-A
19249	25	125	M10 x 1.25	DSNU-25-125-PPV-A
1908319	25	150	M10 x 1.25	DSNU-25-150-PPV-A
19250	25	160	M10 x 1.25	DSNU-25-160-PPV-A
19251	25	200	M10 x 1.25	DSNU-25-200-PPV-A
19252	25	250	M10 x 1.25	DSNU-25-250-PPV-A
19253	25	300	M10 x 1.25	DSNU-25-300-PPV-A
34721	25	320	M10 x 1.25	DSNU-25-320-PPV-A
		Tech Sheet 70230		

Fluid-Air Components Ltd

DIN ISO 6432 ROUND CYLINDERS, DSNU

FESTO

Double Acting, Self-adjusting Pneumatic Cushioning


- Diameter 16-25mm: ISO 6432
- For very high demands on running characteristics, service life and load capacity
- Stainless Steel piston rod
- Comprehensive range of accessories

See page 468 for sensor mounts and sensors

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar

Self-adjusting Cushioning





Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
1908274	16	10	M6	DSNU-16-10-PPS-A
1908275	16	15	M6	DSNU-16-15-PPS-A
1908276	16	20	M6	DSNU-16-20-PPS-A
559263	16	25	M6	DSNU-16-25-PPS-A
1908277	16	30	M6	DSNU-16-30-PPS-A
1908278	16	35	M6	DSNU-16-35-PPS-A
559264	16	40	M6	DSNU-16-40-PPS-A
559265	16	50	M6	DSNU-16-50-PPS-A
1908279	16	60	M6	DSNU-16-60-PPS-A
1908280	16	70	M6	DSNU-16-70-PPS-A
559266	16	80	M6	DSNU-16-80-PPS-A
559267	16	100	M6	DSNU-16-100-PPS-A
559268	16	125	M6	DSNU-16-125-PPS-A
1908281	16	150	M6	DSNU-16-150-PPS-A
559269	16	160	M6	DSNU-16-160-PPS-A
559270	16	200	M6	DSNU-16-200-PPS-A
		Tech Sheet 70231		

FESTO



For **Festo Differential Pressure Regulators** see page **816**

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
1908297	20	10	M8	DSNU-20-10-PPS-A
1908298	20	15	M8	DSNU-20-15-PPS-A
1908299	20	20	M8	DSNU-20-20-PPS-A
559271	20	25	M8	DSNU-20-25-PPS-A
1908300	20	30	M8	DSNU-20-30-PPS-A
1908301	20	35	M8	DSNU-20-35-PPS-A
559272	20	40	M8	DSNU-20-40-PPS-A
559273	20	50	M8	DSNU-20-50-PPS-A
1908302	20	60	M8	DSNU-20-60-PPS-A
1908303	20	70	M8	DSNU-20-70-PPS-A
559274	20	80	M8	DSNU-20-80-PPS-A
559275	20	100	M8	DSNU-20-100-PPS-A
559276	20	125	M8	DSNU-20-125-PPS-A
1908304	20	150	M8	DSNU-20-150-PPS-A
559277	20	160	M8	DSNU-20-160-PPS-A
559278	20	200	M8	DSNU-20-200-PPS-A
559279	20	250	M8	DSNU-20-250-PPS-A
559280	20	300	M8	DSNU-20-300-PPS-A
559281	20	320	M8	DSNU-20-320-PPS-A
1908320	25	10	M10 x 1.25	DSNU-25-10-PPS-A
1908321	25	15	M10 x 1.25	DSNU-25-15-PPS-A
1908322	25	20	M10 x 1.25	DSNU-25-20-PPS-A
559282	25	25	M10 x 1.25	DSNU-25-25-PPS-A
1908323	25	30	M10 x 1.25	DSNU-25-30-PPS-A
1908324	25	35	M10 x 1.25	DSNU-25-35-PPS-A
559283	25	40	M10 x 1.25	DSNU-25-40-PPS-A
559284	25	50	M10 x 1.25	DSNU-25-50-PPS-A
1908325	25	60	M10 x 1.25	DSNU-25-60-PPS-A
1908326	25	70	M10 x 1.25	DSNU-25-70-PPS-A
559285	25	80	M10 x 1.25	DSNU-25-80-PPS-A
559286	25	100	M10 x 1.25	DSNU-25-100-PPS-A
559287	25	125	M10 x 1.25	DSNU-25-125-PPS-A
1908327	25	150	M10 x 1.25	DSNU-25-150-PPS-A
559288	25	160	M10 x 1.25	DSNU-25-160-PPS-A
559289	25	200	M10 x 1.25	DSNU-25-200-PPS-A
559290	25	250	M10 x 1.25	DSNU-25-250-PPS-A
559291	25	300	M10 x 1.25	DSNU-25-300-PPS-A
559292	25	320	M10 x 1.25	DSNU-25-320-PPS-A
		Tech Sheet 70232		

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ROUND CYLINDERS, DSNU-S

FESTO

Compact Double Acting, Elastic Polymer Cushioning Rings


- Compact variant of standards-based cylinder DSNU
- Diameter 12-25mm
- Space saving

See page 468 for sensor mounts and sensors

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar

Elastic Polymer Cushioning





Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
5211896	12	10	M6	DSNU-S-12-10-P-A
5211897	12	15	M6	DSNU-S-12-15-P-A
5211898	12	20	M6	DSNU-S-12-20-P-A
5211899	12	25	M6	DSNU-S-12-25-P-A
5211900	12	30	M6	DSNU-S-12-30-P-A
5211901	12	40	M6	DSNU-S-12-40-P-A
5211903	12	50	M6	DSNU-S-12-50-P-A
5211904	12	60	M6	DSNU-S-12-60-P-A
5211905	12	80	M6	DSNU-S-12-80-P-A
5211906	12	100	M6	DSNU-S-12-100-P-A
5211908	12	125	M6	DSNU-S-12-125-P-A
5211909	12	150	M6	DSNU-S-12-150-P-A
5216087	16	10	M6	DSNU-S-16-10-P-A
5216088	16	15	M6	DSNU-S-16-15-P-A
5216089	16	20	M6	DSNU-S-16-20-P-A
5216090	16	25	M6	DSNU-S-16-25-P-A
5216091	16	30	M6	DSNU-S-16-30-P-A
5216093	16	40	M6	DSNU-S-16-40-P-A
5216094	16	50	M6	DSNU-S-16-50-P-A
5216095	16	60	M6	DSNU-S-16-60-P-A
5216096	16	80	M6	DSNU-S-16-80-P-A
5216098	16	100	M6	DSNU-S-16-100-P-A
5216099	16	125	M6	DSNU-S-16-125-P-A
5216100	16	150	M6	DSNU-S-16-150-P-A
5216101	16	200	M6	DSNU-S-16-200-P-A
Tech Sheet 70227				

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
5224633	20	10	M8	DSNU-S-20-10-P-A
5224634	20	15	M8	DSNU-S-20-15-P-A
5224635	20	20	M8	DSNU-S-20-20-P-A
5224636	20	25	M8	DSNU-S-20-25-P-A
5224637	20	30	M8	DSNU-S-20-30-P-A
5224639	20	40	M8	DSNU-S-20-40-P-A
5224641	20	50	M8	DSNU-S-20-50-P-A
5224642	20	60	M8	DSNU-S-20-60-P-A
5224643	20	80	M8	DSNU-S-20-80-P-A
5224644	20	100	M8	DSNU-S-20-100-P-A
5224645	20	125	M8	DSNU-S-20-125-P-A
5224646	20	150	M8	DSNU-S-20-150-P-A
5224647	20	200	M8	DSNU-S-20-200-P-A
5228227	25	10	M8	DSNU-S-25-10-P-A
5228228	25	15	M8	DSNU-S-25-15-P-A
5228229	25	20	M8	DSNU-S-25-20-P-A
5228230	25	25	M8	DSNU-S-25-25-P-A
5228231	25	30	M8	DSNU-S-25-30-P-A
5228232	25	40	M8	DSNU-S-25-40-P-A
5228233	25	50	M8	DSNU-S-25-50-P-A
5228234	25	60	M8	DSNU-S-25-60-P-A
5228235	25	80	M8	DSNU-S-25-80-P-A
5228236	25	100	M8	DSNU-S-25-100-P-A
5228237	25	125	M8	DSNU-S-25-125-P-A
5228238	25	150	M8	DSNU-S-25-150-P-A
5228239	25	200	M8	DSNU-S-25-200-P-A
Tech Sheet 70228				

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

ROUND CYLINDERS, DSNU-S

FESTO

Compact Double Acting, Self-adjusting Pneumatic Cushioning


- Compact variant of standards-based cylinder DSNU
- Diameter 16-25mm
- Space saving

See page 468 for sensor mounts and sensors

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar

Self-adjusting Cushioning





Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
5217238	16	25	M6	DSNU-S-16-25-PPS-A
5217239	16	30	M6	DSNU-S-16-30-PPS-A
5217240	16	40	M6	DSNU-S-16-40-PPS-A
5217241	16	50	M6	DSNU-S-16-50-PPS-A
5217242	16	60	M6	DSNU-S-16-60-PPS-A
5217243	16	80	M6	DSNU-S-16-80-PPS-A
5217244	16	100	M6	DSNU-S-16-100-PPS-A
5217245	16	125	M6	DSNU-S-16-125-PPS-A
5217246	16	150	M6	DSNU-S-16-150-PPS-A
5217248	16	200	M6	DSNU-S-16-200-PPS-A
		Tech Sheet 70233		

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
5225836	20	25	M8	DSNU-S-20-25-PPS-A
5225837	20	30	M8	DSNU-S-20-30-PPS-A
5225838	20	40	M8	DSNU-S-20-40-PPS-A
5225839	20	50	M8	DSNU-S-20-50-PPS-A
5225840	20	60	M8	DSNU-S-20-60-PPS-A
5225841	20	80	M8	DSNU-S-20-80-PPS-A
5225842	20	100	M8	DSNU-S-20-100-PPS-A
5225843	20	125	M8	DSNU-S-20-125-PPS-A
5225844	20	150	M8	DSNU-S-20-150-PPS-A
5225846	20	200	M8	DSNU-S-20-200-PPS-A
5228452	25	25	M8	DSNU-S-25-25-PPS-A
5228453	25	30	M8	DSNU-S-25-30-PPS-A
5228454	25	40	M8	DSNU-S-25-40-PPS-A
5228455	25	50	M8	DSNU-S-25-50-PPS-A
5228456	25	60	M8	DSNU-S-25-60-PPS-A
5228457	25	80	M8	DSNU-S-25-80-PPS-A
5228458	25	100	M8	DSNU-S-25-100-PPS-A
5228459	25	125	M8	DSNU-S-25-125-PPS-A
5228460	25	150	M8	DSNU-S-25-150-PPS-A
5228461	25	200	M8	DSNU-S-25-200-PPS-A
		Tech Sheet 70234		

FESTO



For **Festo Air Prep MS Series**
see pages **657-662**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CYLINDER ATTACHMENTS & ACCESSORIES

FESTO

Mounting Components for Drive Units



Foot Mounting, ISO 6432, Version S1, For DSNU Standard Cylinder

0009	To Suit Bore mm	Quantity	Manufacturer's Code
5125	12/16	1	HBN-12/16X1
5126	12/16	2	HBN-12/16X2
5127	20/25	1	HBN-20/25X1
5128	20/25	2	HBN-20/25X2
Tech Sheet 70217			



Foot Mounting, ISO 6432, Version S3, For DSNU-S Space Saving Cylinder

0009	To Suit Bore mm	Quantity	Manufacturer's Code
5407772	12/16	1	HBN-S-12/16X1
5407787	20/25	1	HBN-S-20/25X1
5407847	20/25	2	HBN-S-20/25X2
Tech Sheet 70218			



Clevis Foot Swivel Mounting, ISO 6432

0009	To Suit Bore mm	Manufacturer's Code
6058	12/16	LBN-12/16
6059	20/25	LBN-20/25
Tech Sheet 70216		

Mounting Components for Sensors



SMBR, Clip Mounting Kits

0009	Type
175091	SMBR-8
175092	SMBR-8-10
175093	SMBR-8-12
175094	SMBR-8-16
175095	SMBR-8-20
175096	SMBR-8-25
175097	SMBR-8-32
175098	SMBR-8-40
175099	SMBR-8-50
175100	SMBR-8-63

T Slot



C Slot






Proximity Sensors For T-Slot, Non-contacting

0009	Type N/O Contact
574334	SMT-8M-A-PS-24V-E-0.3-M8D (PNP)
574339	SMT-8M-A-NS-24V-E-0.3-M8D (NPN)



Cable Type NEBU

0009	Designation
541334	Connecting cable



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 6432 MINI CYLINDERS

ISO 6432 Single Acting Cylinders

Technical Data for all ISO 6432 Cylinders

Temperature Range: 10°C to +80°C

Maximum Operating Pressure: 10 bar


- Fluid: lubricated or unlubricated air
- Inrush pressure: Ø10-12 = 0.8 bar, Ø16-25 = 0.6 bar
- Forces generated at 6 bar thrust/retraction: Ø16: 108N/95N, Ø20: 169N/148N, Ø25: 265N/228N

Dimensions

Ø	AM	BE	ØCD	ØD	ØD1	G	EE	EW	L	L1	L2	L3	L4	L5	KK	XC	WF	KW	KV	MR	NA	NB	SW	CH	K
10	12	M12 x 1.25	4	17	4	6	M5	8	6	86	10	12	10	46	M4	64	16	7	19	12	15	15	7	3	3
12	16	M16 x 1.5	6	19	6	6	M5	12	9	104	13	17	10	49	M6	75	22	8	24	16	17	17	10	5	3
16	16	M16 x 1.5	6	23	6	6	M5	12	9	111	13	17	10	56	M6	82	22	8	24	16	20	20	10	5	3.5
20	20	M22 x 1.5	8	34	8	8	G1/8	16	12	129	14	17	15	68	M8	95	24	10	32	18	28	28	13	7	4.6
25	22	M22 x 1.5	8	34	10	9	G1/8	16	12	143	17	20	18	73	M10 x 1.25	104	28	10	32	21	30	30	17	8	5

Non-magnetic


9146	Diameter mm	Stroke mm
1110100010XN	10	10
1110100025XN	10	25
1110100050XN	10	50
1110120010CN	12	10
1110120025CN	12	25
1110120050CN	12	50
1110160010CN	16	10
1110160025CN	16	25
1110160050CN	16	50
1110200010CN	20	10
1110200025CN	20	25
1110200050CN	20	50
1110250010CN	25	10
1110250025CN	25	25
1110250050CN	25	50



ISO 6432 Double Acting Cylinders

Magnetic


9146	Diameter mm	Stroke mm
1120160010CN	16	10
1120160025CN	16	25
1120160050CN	16	50
1120160080CN	16	80
1120160100CN	16	100
1120160125CN	16	125
1120160160CN	16	160
1120160200CN	16	200
1120200010CN	20	10
1120200025CN	20	25
1120200050CN	20	50
1120200080CN	20	80
1120200100CN	20	100
1120200125CN	20	125
1120200160CN	20	160
1120200200CN	20	200
1120200250CN	20	250
1120250010CN	25	10
1120250025CN	25	25
1120250050CN	25	50
1120250080CN	25	80
1120250100CN	25	100
1120250125CN	25	125
1120250160CN	25	160
1120250200CN	25	200
1120250250CN	25	250
1120250320CN	25	320



Fluid-Air Components Ltd

ISO 6432 MINI CYLINDERS ACCESSORIES

Foot Mounting



To suit ISO 6432 Cylinders

9146	To Suit Size mm
W0950080001	10
W0950120001	12-16
W0950200001	20-25

Flange Mounting



To suit ISO 6432 Cylinders

9146	To Suit Size mm
W0950080002	10
W0950120002	12-16
W0950200002	20-25


Counter Support



To suit ISO 6432 Cylinders

9146	To Suit Size mm
W0950080005	10
W0950120005	12-16
W0950200005	20-25


Cylinder Head Nut



To suit ISO 6432 Cylinders

9146	To Suit Size mm	Thread
W0950080010	10	M12 x 1.25
W0950120010	16	M16 x 1.5
W0950200010	25	M22 x 1.5

Piston Rod Nut



To suit ISO 6432 Cylinders

9146	To Suit Size mm	Thread
W0950080011	10	M4
W0950120011	16	M6
W0950200011	20	M8
W0950322010	25	M10 x 1.25

Fork Clevis



To suit ISO 6432 Cylinders

9146	To Suit Size mm	Thread
W0950080020	10	M4
W0950120020	12-16	M6
W0950200020	20	M8
W0950322020	25	M10 x 1.25

Spherical Rod Eye



To suit ISO 6432 Cylinders

9146	To Suit Size mm	Thread
W0950080025	10	M4
W0950120025	12-16	M6
W0950200025	20	M8
W0950322025	25	M10 x 1.25

Reed Switch & Bracket



To suit ISO 6432 Cylinders

9146	Description/To Suit
W0950000201	Reed Switch
W0950000510	10
W0950000512	12
W0950000516	16
W0950000520	20
W0950000525	25

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 6432 MINI AIR CYLINDERS, ALL STAINLESS STEEL

ISO 6432 Mini Cylinders, Double Acting

Technical Specification

- ISO 6432 stainless steel micro-cylinders are available in various versions with a wide range of accessories
- With or without magnet execution
- Double-acting, single or through-rod
- Gaskets: polyurethane or FKM/FPM (for high temperatures)
- Fixing accessories

Fluid


Lubricated or non-lubricated air

Temperature Range:
10°C to +80°C

Maximum Operating Pressure:
10 bar



1. Piston rod: AISI 316 steel
2. Head: AISI 304 steel
3. Piston rod gasket: polyurethane or FKM/FPM
4. Guide bushing: sintered bronze
5. Barrel: AISI 304 steel
6. Piston: brass
7. Piston gasket: polyurethane or FKM/FPM
8. Magnet: plastoferrite
9. Static O-rings: NBR or FKM/FPM



Magnetic

9146	Ø mm	Stroke mm
W1800160010	16	10
W1800160025	16	25
W1800160050	16	50
W1800160080	16	80
W1800160100	16	100
W1800160125	16	125
W1800160160	16	160
W1800160200	16	200
W1800160250	16	250
W1800160320	16	320
W1800200010	20	10
W1800200025	20	25
W1800200050	20	50
W1800200080	20	80
W1800200100	20	100
W1800200125	20	125
W1800200160	20	160

9146	Ø mm	Stroke mm
W1800200200	20	200
W1800200250	20	250
W1800200320	20	320
W1800200400	20	400
W1800250010	25	10
W1800250025	25	25
W1800250050	25	50
W1800250080	25	80
W1800250100	25	100
W1800250125	25	125
W1800250160	25	160
W1800250200	25	200
W1800250250	25	250
W1800250320	25	320
W1800250400	25	400
W1800250500	25	500

Fluid-Air Components Ltd

ISO 6432 MINI AIR CYLINDER ACCESSORIES, ALL STAINLESS STEEL

Foot Mountings



To suit ISO 6432 Mini Cylinders

9146	To Suit Size mm
W095X120001	16
W095X200001	20/25

Female Hinges



To suit ISO 6432 Mini Cylinders

9146	To Suit Size mm
W095X120005	16
W095X200005	20/25

Rod Nuts



To suit ISO 6432 Mini Cylinders

9146	To Suit Size mm	Thread
W095X120011	16	M6 x 1
W095X200011	20	M8 x 1
W095X322011	25/32	M10 x 1.25

Cylinder Head Nuts



To suit ISO 6432 Mini Cylinders

9146	To Suit Size mm	Thread
W095X120010	16	M16 x 1.25
W095X200010	20/25	M22 x 1.5

Flange



To suit ISO 6432 Mini Cylinders

9146	Size to Suit mm
W095X120002	16
W095X200002	20/25

Fork Clevis



To suit ISO 6432 Cylinders

9146	To Suit Size mm	Thread
W095X120020	16	M6 x 1
W095X200020	20	M8 x 1
W095X322020	25/32	M10 x 1.25


Reed Switch



To suit ISO 6432 Mini Cylinders

9146	Description
W0952028184	With M8 Connection

Mounting for Reed Switch



To suit ISO 6432 Mini Cylinders

9146	To Suit Size mm
W0950001103	8-63

Fluid-Air Components Ltd

We have access to over 10,000 product lines available via Norgren's European Distribution Centre. Contact our business development team with your Norgren requirements.

Norgren's extensive product range comprises of other leading brands including: Pneufit, Herion, Buschjost, Martonair, Lintra, Excelon Plus and Fleetfit.



VACUUM

Vacuum is most commonly used for picking and placing components in assembly automation systems. Generated from a compressed air supply, this can be controlled very simply in order to perform most common tasks. The range includes a range of pumps, cups, switches and accessories; easily selected and applied.



PRESSURE SWITCHES

Pressure switches can be used to automatically monitor pressure levels in a compressed air system. They can however also be used for more complex monitoring functions in air, water or hydraulic applications.



ACTUATORS

Pneumatic actuators (sometimes called cylinders) are the product used to provide motion and force to industrial automation applications. Linear and rotary output, they are available in all manner of sizes and styles to suit most requirements. Norgren has a long history of production of this kind of device – an early example of a pneumatic actuator was the original Martonair air hoist. They now include rodded, rodless, compact, roundline, guided and other ranges.



VALVES

In industrial automation, valves can be as simple or complex as required. Norgren has many brand names associated with its valve ranges – Herion, Buschjost, Walter, FAS, Webber, Watson Smith, Maxseal, Enots and Martonair.



AIR PREPARATION

Correct air preparation is essential for best performance. Norgren has a great reputation in this area, and its ranges have been at the forefront of industry for many years.

Fluid-Air Components Ltd

ISO 6432 CYLINDERS & MOUNTINGS

NORGREN

ISO 6432 Cylinders

- Magnetic piston as standard
- Generally conforms to ISO 6432
- High strength, double crimped end cap design
- Corrosion resistant
- Nose mounting nut and piston rod locknut as standard
- Optional port arrangement for compact installation

Medium:
Compressed air, filtered, lubricated or non-lubricated

Working Temperature:
-10°C to +80°C

Working Pressure:
2 to 10 bar

Standard:
ISO 6432

Buffer:
Polyurethane

Operation:
Single acting (sprung in), magnetic piston, buffer cushioning

Barrel:
Stainless steel (austenitic)


Piston Rod:
Stainless steel (austenitic)

Seals:
Nitrile rubber

End Covers:
Clear anodised aluminium alloy

Single Acting RM/28000/M

0036	Bore mm	Stroke mm	Thread
RM/28010/M/10	10	10	M5
RM/28010/M/25	10	25	M5
RM/28010/M/50	10	50	M5
RM/28020/M/10	20	10	G1/8
RM/28020/M/25	20	25	G1/8
RM/28020/M/50	20	50	G1/8
RM/28025/M/10	25	10	G1/8
RM/28025/M/25	25	25	G1/8
RM/28025/M/50	25	50	G1/8
Tech Sheet 10316			



Working Temperature:
-10°C to +80°C

Working Pressure:
1 to 10 bar

Medium:
Compressed air, filtered, lubricated or non-lubricated

Standard:
ISO 6432

Buffer:
Polyurethane

Operation:
Double acting, magnetic piston with buffer or adjustable cushioning

Barrel:
Stainless steel (austenitic)

Piston Rod:
Stainless steel (austenitic)


Wiper:
Polyurethane

Seals:
Nitrile rubber

End Covers:
Clear anodised aluminium alloy

Double Acting RM/8000/M

0036	Bore mm	Stroke mm	Thread
RM/8010/M/25	10	25	M5
RM/8010/M/50	10	50	M5
RM/8010/M/80	10	80	M5
RM/8010/M/100	10	100	M5
RM/8012/M/25	12	25	M5
RM/8012/M/50	12	50	M5
RM/8016/M/25	16	25	M5
RM/8016/M/50	16	50	M5
RM/8016/M/100	16	100	M5
RM/8020/M/25	20	25	G1/8
RM/8020/M/50	20	50	G1/8
RM/8020/M/80	20	80	G1/8
RM/8020/M/100	20	100	G1/8
RM/8025/M/25	25	25	G1/8
RM/8025/M/50	25	50	G1/8
RM/8025/M/80	25	80	G1/8
RM/8025/M/100	25	100	G1/8
Tech Sheet 10316			



ISO 6432 Mountings



Female Piston Rod Clevis

0036	Bore mm
QM/8010/25	10
QM/8012/25	12 & 16
QM/8020/25	20
QM/8025/25	25
Tech Sheet 10316	



Piston Rod Eye

0036	Bore mm
QM/8010/32	10
QM/8012/32	12 & 16
QM/8020/32	20
QM/8025/32	25
Tech Sheet 10316	



Clevis Foot Mounting

0036	Bore mm
QM/947	10
QM/8012/24	12 & 16
QM/8020/24	20 & 25
Tech Sheet 10316	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 6432 CYLINDERS

Proximity Switches to suit Series 24, 32, 60 & 61



T Slot

0158	Description	Voltage
CST 220	2 Wire	10-110V AC/DC
CST 232	3 Wire	5-30V AC/DC
CST 332	Hall Effect, 3 Wire, PNP	27V DC
Tech Sheet 20084		



T Slot, M8

0158	Description	Voltage
CST 250	2 Wire	10-110V AC/DC
CST 262	3 Wire	5-30V AC/DC
CST 362	Hall Effect, 3 Wire, PNP	27V DC
Tech Sheet 20084		

Extension Lead

0158	Length Metres
GG08B3C25050	5
Tech Sheet 20084	

Proximity Switch Brackets



Series 24

0158	OD mm
S-CST 02	16
S-CST 03	20
S-CST 04	25
Tech Sheet 20084	



Series 60

0158	OD mm
S-CST 25	32-63
S-CST 26	80-100
Tech Sheet 20084	

Series 24, Double Acting Cylinders

Single and double-acting
Standard CETOP RP52P DIN/ISO 6432
Stainless steel rod and tube
Anodized AL end-blocks
Type of construction: flanged
Operation: single-acting or double-acting
Materials: end-blocks = anodized AL, tube and rod = stainless steel, piston = AL, seals = NBR - PU, other parts = see coding
Brackets: screw, flange, feet, trunnion
Stroke min – max: Ø 16: 10 - 600 mm; Ø 20 - Ø 25: 10 - 1000 mm
Bores: Ø 16, 20, 25

Fluid: Filtered air, without lubrication. If lubricated air is used, it is recommended to use oil ISO VG32. Once applied the lubrication should never be interrupted.
Speed: 10 to 1000 mm/sec (without load)

Operating temperature:
0°C to 80°C (with dry air -20°C)

Operating pressure:
1 to 10 bar (double-acting);
2 to 10 bar (single-acting)



M5, Ø16mm

0158	Stroke mm
24N2A16A010	10
24N2A16A025	25
24N2A16A040	40
24N2A16A050	50
24N2A16A080	80
24N2A16A100	100
24N2A16A125	125
24N2A16A160	160
24N2A16A200	200
Tech Sheet 1844	

G1/8", Ø20mm

0158	Stroke mm
24N2A20A010	10
24N2A20A025	25
24N2A20A040	40
24N2A20A050	50
24N2A20A080	80
24N2A20A100	100
24N2A20A125	125
24N2A20A160	160
24N2A20A200	200
24N2A20A250	250
24N2A20A300	300
Tech Sheet 1844	

G1/8", Ø25mm

0158	Stroke mm
24N2A25A010	10
24N2A25A025	25
24N2A25A040	40
24N2A25A050	50
24N2A25A080	80
24N2A25A100	100
24N2A25A125	125
24N2A25A160	160
24N2A25A200	200
24N2A25A250	250
24N2A25A300	300
24N2A25A320	320
24N2A25A400	400
24N2A25A500	500
Tech Sheet 1844	



For **Super-Rapid Compact Fittings** see page **832**

Fluid-Air Components Ltd

ISO 6432 CYLINDERS

Mini-ISO Cylinders





Micro Cylinders Double Acting 8mm-16mm

0110	Bore mm	Stroke mm
1280.10.15.M	10	15
1280.10.100.M	10	100
1280.12.15.M	12	15
1280.12.50.M	12	50
1280.12.100.M	12	100
1280.12.250.M	12	250
1280.12.300.M	12	300
1280.16.50.M	16	50
1280.16.75.M	16	75
1280.16.80.M	16	80
1280.16.100.M	16	100
1280.16.150.M	16	150
1280.16.160.M	16	160
1280.16.200.M	16	200

Micro Cylinders Double Acting 20mm-32mm

0110	Bore mm	Stroke mm
1280.20.15.M	20	15
1280.20.25.M	20	25
1280.20.50.M	20	50
1280.20.75.M	20	75
1280.20.80.M	20	80
1280.20.150.M	20	150
1280.20.200.M	20	200
1280.20.250.M	20	250
1280.20.300.M	20	300
1280.20.350.M	20	350
1280.25.15.M	25	15
1280.25.25.M	25	25
1280.25.50.M	25	50
1280.25.75.M	25	75
1280.25.80.M	25	80
1280.25.100.M	25	100
1280.25.125.M	25	125
1280.25.200.M	25	200
1280.25.250.M	25	250
1280.25.300.M	25	300
1280.25.400.M	25	400
1280.32.50.M	32	50
1280.32.150.M	32	150
1280.32.250.M	32	250
1280.32.400.M	32	400

Micro Cylinders Double Acting No Rear Eye 8mm-16mm

0110	Bore mm	Stroke mm
1281.12.150.M	12	150
1281.16.80.M	16	80
1281.16.150.M	16	150

Micro Cylinders Double Acting No Rear Eye 20mm-32mm

0110	Bore mm	Stroke mm
1281.20.50.M	20	50
1281.20.200.M	20	200
1281.25.50.M	25	50
1281.25.75.M	25	75
1281.25.160.M	25	160
1281.32.50.M	32	50
1281.32.75.M	32	75
1281.32.200.M	32	200
1281.32.300.M	32	300



For **Pneumax Air Preparation**
see page **700**

Fluid-Air Components Ltd

ISO 6432 CYLINDER ACCESSORIES

Mini-ISO Cylinder Mountings



1580U Reed Switch c/w LED

0110	Description
1580U	LED Reed Switch N/O



1580.U Switch Clamps 8mm-32mm

0110	Bore mm
1280.8.FS	8



1500U Reed Switch c/w LED

0110	Description
1500.U	LED Reed Switch N/O



1500.U Switch Clamps 12mm-32mm

0110	Bore mm
1280.16.F	16



Foot Bracket 8mm-32mm

0110	Bore mm
1200.8.01	8



Flange Bracket 8mm-32mm

0110	Bore mm
1200.8.02	8



Rear Eye Bracket 8mm-32mm

0110	Bore mm
1200.32.03	32



Rod Clevis c/w Pin 8mm-32mm

0110	Bore mm
1200.12.04	12



Rod Clevis c/w Pin & Clip 8mm-32mm

0110	Bore mm
1200.25.04/1	25



Rod Nut & Locking Ring 8mm-32mm

0110	Bore mm
1200.8.05	8


Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PNEUMATIC GEN 1 & 2 ISO 15552 CYLINDERS

Accessories & Mounting Selector

stainless steel

FT PRO



ISO 15552 Cylinders

FA	Front and rear flange mounting	**CR**	Rear bracket mounting
FTC	Front trunnion mounting	**LB**	Foot mounting (pair)
TF	Front trunnion clevis mounting	**YI**	Piston rod clevis
TM	Trunnion support mounting	**I**	Piston rod clevis
CA	Rear eye mounting	**F**	Piston rod floating joint
CB	Rear clevis mounting	**U**	Piston rod universal joint
		Reed Switches	Two wire N/O with LED

Cylinders
Pages 480-483

Mountings
Pages 484-485

Reed Switches
Page 485

Cylinder Guides
Page 486


Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

Technical Information


Inner Structure & Material of Major Parts

No.	Item	Material
1	Rod nut	Stainless steel
2	Piston rod	Blank: medium carbon steel B: 304 stainless steel
3	Front cover packing	TPU
4	Front cover	Aluminium alloy
5	Bushing	Wear-resistant material
6	Cushioning O-ring	TPU
7	Barrel	Aluminium alloy
8	O-ring	Nitrile
9	Piston	Aluminium alloy
10	Piston seal	TPU
11	Wear ring	Wear-resistant material
12	Magnet	Plastic/rubber (Ø125)
13	Bolt	Carbon steel
14	Buffer gasket	TPU
15	Back cover	Aluminium alloy
16	Screw	Carbon steel/stainless steel





Dimensions



Bore Size/Item	A	B	C	D	E	F	G	H	I	J	K	L	N	P	Q	R	S	T	V	W	X	Z
32	142	48	94	30	29	19	27.5	22	17	6	M10 x 1.25	M6	13.5	5.8	6	6.3	46.5	32.5	12	10	3	30
40	159	54	105	35	33	21	32	24	17	7	M12 x 1.25	M6	17.5	6	5.5	9	54	38	16	13	3.5	35
50	175	69	106	40	42	27	31	32	23	8	M16 x 1.5	M8	14	8	5	10.5	64	46.5	20	17	3.5	40
63	190	69	121	45	42	27	33	32	23	8	M16 x 1.5	M8	17	8	6	10.5	75	56.5	20	17	4	45
80	214	86	128	45	53	33	33	40	26	10	M20 x 1.5	M10	16.5	8	8.5	12.5	93	72	25	22	4	45
100	229	91	138	55	55	36	37	40	26	10	M20 x 1.5	M10	19.5	10	7	12	110	89	25	22	4	55
125	279	119	160	60	74	45	46	54	41	13.5	M27 x 2	M12	23	11	12	11	135	110	32	27	4	60

PNEUMATIC CYLINDERS


Gen 1 ISO 15552 Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated adjustable cushioning.
Piston Rod Material: Chrome plated carbon steel.
Please note: Bore sizes 125mm are available on a lead time.
Please contact our sales office for details.

2 Year Warranty

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar



Chrome Plated Carbon Steel Piston Rod as Standard

Magnetic Double Acting, Adjustable Cushioning, BSPP

0414	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-32X25-S-G	32	25	1/8"	M10 x 1.25
KI-32X50-S-G	32	50	1/8"	M10 x 1.25
KI-32X75-S-G	32	75	1/8"	M10 x 1.25
KI-32X80-S-G	32	80	1/8"	M10 x 1.25
KI-32X100-S-G	32	100	1/8"	M10 x 1.25
KI-32X125-S-G	32	125	1/8"	M10 x 1.25
KI-32X150-S-G	32	150	1/8"	M10 x 1.25
KI-32X160-S-G	32	160	1/8"	M10 x 1.25
KI-32X175-S-G	32	175	1/8"	M10 x 1.25
KI-32X200-S-G	32	200	1/8"	M10 x 1.25
KI-32X250-S-G	32	250	1/8"	M10 x 1.25
KI-32X300-S-G	32	300	1/8"	M10 x 1.25
KI-32X350-S-G	32	350	1/8"	M10 x 1.25
KI-32X400-S-G	32	400	1/8"	M10 x 1.25
KI-32X450-S-G	32	450	1/8"	M10 x 1.25
KI-32X500-S-G	32	500	1/8"	M10 x 1.25
KI-40X25-S-G	40	25	1/4"	M12 x 1.25
KI-40X50-S-G	40	50	1/4"	M12 x 1.25
KI-40X75-S-G	40	75	1/4"	M12 x 1.25
KI-40X80-S-G	40	80	1/4"	M12 x 1.25
KI-40X100-S-G	40	100	1/4"	M12 x 1.25
KI-40X125-S-G	40	125	1/4"	M12 x 1.25
KI-40X150-S-G	40	150	1/4"	M12 x 1.25
KI-40X160-S-G	40	160	1/4"	M12 x 1.25
KI-40X175-S-G	40	175	1/4"	M12 x 1.25
KI-40X200-S-G	40	200	1/4"	M12 x 1.25
KI-40X250-S-G	40	250	1/4"	M12 x 1.25
KI-40X300-S-G	40	300	1/4"	M12 x 1.25
KI-40X350-S-G	40	350	1/4"	M12 x 1.25
KI-40X400-S-G	40	400	1/4"	M12 x 1.25
KI-40X450-S-G	40	450	1/4"	M12 x 1.25
KI-40X500-S-G	40	500	1/4"	M12 x 1.25
KI-40X600-S-G	40	600	1/4"	M12 x 1.25
KI-40X700-S-G	40	700	1/4"	M12 x 1.25
KI-40X800-S-G	40	800	1/4"	M12 x 1.25
KI-50X25-S-G	50	25	1/4"	M16 x 1.5
KI-50X50-S-G	50	50	1/4"	M16 x 1.5
KI-50X75-S-G	50	75	1/4"	M16 x 1.5
KI-50X80-S-G	50	80	1/4"	M16 x 1.5
KI-50X100-S-G	50	100	1/4"	M16 x 1.5
KI-50X125-S-G	50	125	1/4"	M16 x 1.5
KI-50X150-S-G	50	150	1/4"	M16 x 1.5
KI-50X160-S-G	50	160	1/4"	M16 x 1.5
KI-50X175-S-G	50	175	1/4"	M16 x 1.5
KI-50X200-S-G	50	200	1/4"	M16 x 1.5
KI-50X250-S-G	50	250	1/4"	M16 x 1.5
KI-50X300-S-G	50	300	1/4"	M16 x 1.5
KI-50X350-S-G	50	350	1/4"	M16 x 1.5
KI-50X400-S-G	50	400	1/4"	M16 x 1.5
KI-50X450-S-G	50	450	1/4"	M16 x 1.5
KI-50X500-S-G	50	500	1/4"	M16 x 1.5
KI-50X600-S-G	50	600	1/4"	M16 x 1.5
KI-50X700-S-G	50	700	1/4"	M16 x 1.5
KI-50X800-S-G	50	800	1/4"	M16 x 1.5
KI-50X900-S-G	50	900	1/4"	M16 x 1.5
KI-50X1000-S-G	50	1000	1/4"	M16 x 1.5
KI-63X25-S-G	63	25	3/8"	M16 x 1.5
KI-63X50-S-G	63	50	3/8"	M16 x 1.5
KI-63X75-S-G	63	75	3/8"	M16 x 1.5
KI-63X80-S-G	63	80	3/8"	M16 x 1.5
KI-63X100-S-G	63	100	3/8"	M16 x 1.5
KI-63X125-S-G	63	125	3/8"	M16 x 1.5
KI-63X150-S-G	63	150	3/8"	M16 x 1.5
KI-63X160-S-G	63	160	3/8"	M16 x 1.5
KI-63X175-S-G	63	175	3/8"	M16 x 1.5
KI-63X200-S-G	63	200	3/8"	M16 x 1.5
KI-63X250-S-G	63	250	3/8"	M16 x 1.5
KI-63X300-S-G	63	300	3/8"	M16 x 1.5
KI-63X350-S-G	63	350	3/8"	M16 x 1.5
KI-63X400-S-G	63	400	3/8"	M16 x 1.5
KI-63X450-S-G	63	450	3/8"	M16 x 1.5
KI-63X500-S-G	63	500	3/8"	M16 x 1.5
KI-63X600-S-G	63	600	3/8"	M16 x 1.5
KI-63X700-S-G	63	700	3/8"	M16 x 1.5
KI-63X800-S-G	63	800	3/8"	M16 x 1.5
KI-63X900-S-G	63	900	3/8"	M16 x 1.5
KI-63X1000-S-G	63	1000	3/8"	M16 x 1.5
KI-80X25-S-G	80	25	3/8"	M20 x 1.5
KI-80X50-S-G	80	50	3/8"	M20 x 1.5
KI-80X75-S-G	80	75	3/8"	M20 x 1.5
KI-80X80-S-G	80	80	3/8"	M20 x 1.5
KI-80X100-S-G	80	100	3/8"	M20 x 1.5
KI-80X125-S-G	80	125	3/8"	M20 x 1.5
KI-80X150-S-G	80	150	3/8"	M20 x 1.5
KI-80X160-S-G	80	160	3/8"	M20 x 1.5
KI-80X175-S-G	80	175	3/8"	M20 x 1.5
KI-80X200-S-G	80	200	3/8"	M20 x 1.5
KI-80X250-S-G	80	250	3/8"	M20 x 1.5
KI-80X300-S-G	80	300	3/8"	M20 x 1.5
KI-80X350-S-G	80	350	3/8"	M20 x 1.5
KI-80X400-S-G	80	400	3/8"	M20 x 1.5

Tech Sheet 10657

Further sizes in this range continued on next page

Fluid-Air Components Ltd

Gen 1 ISO 15552 Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated adjustable cushioning.
Piston Rod Material: Chrome plated carbon steel.
Please note: Bore sizes 125mm are available on a lead time.
Please contact our sales office for details.

2 Year Warranty

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar



Chrome Plated Carbon Steel Piston Rod as Standard

Magnetic Double Acting, Adjustable Cushioning, BSPP

0414	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-80X450-S-G	80	450	3/8"	M20 x 1.5
KI-80X500-S-G	80	500	3/8"	M20 x 1.5
KI-80X600-S-G	80	600	3/8"	M20 x 1.5
KI-80X700-S-G	80	700	3/8"	M20 x 1.5
KI-80X800-S-G	80	800	3/8"	M20 x 1.5
KI-80X900-S-G	80	900	3/8"	M20 x 1.5
KI-80X1000-S-G	80	1000	3/8"	M20 x 1.5
KI-100X25-S-G	100	25	1/2"	M20 x 1.5
KI-100X50-S-G	100	50	1/2"	M20 x 1.5
KI-100X75-S-G	100	75	1/2"	M20 x 1.5
KI-100X80-S-G	100	80	1/2"	M20 x 1.5
KI-100X100-S-G	100	100	1/2"	M20 x 1.5
KI-100X125-S-G	100	125	1/2"	M20 x 1.5
KI-100X150-S-G	100	150	1/2"	M20 x 1.5
KI-100X160-S-G	100	160	1/2"	M20 x 1.5
KI-100X175-S-G	100	175	1/2"	M20 x 1.5
KI-100X200-S-G	100	200	1/2"	M20 x 1.5
KI-100X250-S-G	100	250	1/2"	M20 x 1.5
KI-100X300-S-G	100	300	1/2"	M20 x 1.5
KI-100X350-S-G	100	350	1/2"	M20 x 1.5
KI-100X400-S-G	100	400	1/2"	M20 x 1.5
KI-100X450-S-G	100	450	1/2"	M20 x 1.5
KI-100X500-S-G	100	500	1/2"	M20 x 1.5
KI-100X600-S-G	100	600	1/2"	M20 x 1.5
KI-100X700-S-G	100	700	1/2"	M20 x 1.5

0414	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-100X800-S-G	100	800	1/2"	M20 x 1.5
KI-100X900-S-G	100	900	1/2"	M20 x 1.5
KI-100X1000-S-G	100	1000	1/2"	M20 x 1.5
KI-125X25-S-G	125	25	1/2"	M27 x 2
KI-125X50-S-G	125	50	1/2"	M27 x 2
KI-125X75-S-G	125	75	1/2"	M27 x 2
KI-125X80-S-G	125	80	1/2"	M27 x 2
KI-125X100-S-G	125	100	1/2"	M27 x 2
KI-125X125-S-G	125	125	1/2"	M27 x 2
KI-125X150-S-G	125	150	1/2"	M27 x 2
KI-125X160-S-G	125	160	1/2"	M27 x 2
KI-125X175-S-G	125	175	1/2"	M27 x 2
KI-125X200-S-G	125	200	1/2"	M27 x 2
KI-125X250-S-G	125	250	1/2"	M27 x 2
KI-125X300-S-G	125	300	1/2"	M27 x 2
KI-125X350-S-G	125	350	1/2"	M27 x 2
KI-125X400-S-G	125	400	1/2"	M27 x 2
KI-125X450-S-G	125	450	1/2"	M27 x 2
KI-125X500-S-G	125	500	1/2"	M27 x 2
KI-125X600-S-G	125	600	1/2"	M27 x 2
KI-125X700-S-G	125	700	1/2"	M27 x 2
KI-125X800-S-G	125	800	1/2"	M27 x 2
KI-125X900-S-G	125	900	1/2"	M27 x 2
KI-125X1000-S-G	125	1000	1/2"	M27 x 2

Tech Sheet 10657

For **FT Air Preparation**
see page **637**



For Reed Switches see page 455

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PNEUMATIC CYLINDERS


Gen 2 ISO 15552 Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated adjustable cushioning.
Piston Rod Material: Stainless steel 304.
Please note: Bore sizes 125mm are available on a lead time.
Please contact our sales office for details.

2 Year Warranty

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar



Stainless Steel Piston Rod as Standard

Magnetic Double Acting, Adjustable Cushioning, BSPP

0413	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-32BX25-S-G	32	25	1/8"	M10 x 1.25
KI-32BX50-S-G	32	50	1/8"	M10 x 1.25
KI-32BX75-S-G	32	75	1/8"	M10 x 1.25
KI-32BX80-S-G	32	80	1/8"	M10 x 1.25
KI-32BX100-S-G	32	100	1/8"	M10 x 1.25
KI-32BX125-S-G	32	125	1/8"	M10 x 1.25
KI-32BX150-S-G	32	150	1/8"	M10 x 1.25
KI-32BX160-S-G	32	160	1/8"	M10 x 1.25
KI-32BX175-S-G	32	175	1/8"	M10 x 1.25
KI-32BX200-S-G	32	200	1/8"	M10 x 1.25
KI-32BX250-S-G	32	250	1/8"	M10 x 1.25
KI-32BX300-S-G	32	300	1/8"	M10 x 1.25
KI-32BX350-S-G	32	350	1/8"	M10 x 1.25
KI-32BX400-S-G	32	400	1/8"	M10 x 1.25
KI-32BX450-S-G	32	450	1/8"	M10 x 1.25
KI-32BX500-S-G	32	500	1/8"	M10 x 1.25
KI-40BX25-S-G	40	25	1/4"	M12 x 1.25
KI-40BX50-S-G	40	50	1/4"	M12 x 1.25
KI-40BX75-S-G	40	75	1/4"	M12 x 1.25
KI-40BX80-S-G	40	80	1/4"	M12 x 1.25
KI-40BX100-S-G	40	100	1/4"	M12 x 1.25
KI-40BX125-S-G	40	125	1/4"	M12 x 1.25
KI-40BX150-S-G	40	150	1/4"	M12 x 1.25
KI-40BX160-S-G	40	160	1/4"	M12 x 1.25
KI-40BX175-S-G	40	175	1/4"	M12 x 1.25
KI-40BX200-S-G	40	200	1/4"	M12 x 1.25
KI-40BX250-S-G	40	250	1/4"	M12 x 1.25
KI-40BX300-S-G	40	300	1/4"	M12 x 1.25
KI-40BX350-S-G	40	350	1/4"	M12 x 1.25
KI-40BX400-S-G	40	400	1/4"	M12 x 1.25
KI-40BX450-S-G	40	450	1/4"	M12 x 1.25
KI-40BX500-S-G	40	500	1/4"	M12 x 1.25
KI-40BX600-S-G	40	600	1/4"	M12 x 1.25
KI-40BX700-S-G	40	700	1/4"	M12 x 1.25
KI-40BX800-S-G	40	800	1/4"	M12 x 1.25
KI-50BX25-S-G	50	25	1/4"	M16 x 1.5
KI-50BX50-S-G	50	50	1/4"	M16 x 1.5
KI-50BX75-S-G	50	75	1/4"	M16 x 1.5
KI-50BX80-S-G	50	80	1/4"	M16 x 1.5
KI-50BX100-S-G	50	100	1/4"	M16 x 1.5
KI-50BX125-S-G	50	125	1/4"	M16 x 1.5
KI-50BX150-S-G	50	150	1/4"	M16 x 1.5
KI-50BX160-S-G	50	160	1/4"	M16 x 1.5
KI-50BX175-S-G	50	175	1/4"	M16 x 1.5
KI-50BX200-S-G	50	200	1/4"	M16 x 1.5
KI-50BX250-S-G	50	250	1/4"	M16 x 1.5

0413	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-50BX300-S-G	50	300	1/4"	M16 x 1.5
KI-50BX350-S-G	50	350	1/4"	M16 x 1.5
KI-50BX400-S-G	50	400	1/4"	M16 x 1.5
KI-50BX450-S-G	50	450	1/4"	M16 x 1.5
KI-50BX500-S-G	50	500	1/4"	M16 x 1.5
KI-50BX600-S-G	50	600	1/4"	M16 x 1.5
KI-50BX700-S-G	50	700	1/4"	M16 x 1.5
KI-50BX800-S-G	50	800	1/4"	M16 x 1.5
KI-50BX900-S-G	50	900	1/4"	M16 x 1.5
KI-50BX1000-S-G	50	1000	1/4"	M16 x 1.5
KI-63BX25-S-G	63	25	3/8"	M16 x 1.5
KI-63BX50-S-G	63	50	3/8"	M16 x 1.5
KI-63BX75-S-G	63	75	3/8"	M16 x 1.5
KI-63BX80-S-G	63	80	3/8"	M16 x 1.5
KI-63BX100-S-G	63	100	3/8"	M16 x 1.5
KI-63BX125-S-G	63	125	3/8"	M16 x 1.5
KI-63BX150-S-G	63	150	3/8"	M16 x 1.5
KI-63BX160-S-G	63	160	3/8"	M16 x 1.5
KI-63BX175-S-G	63	175	3/8"	M16 x 1.5
KI-63BX200-S-G	63	200	3/8"	M16 x 1.5
KI-63BX250-S-G	63	250	3/8"	M16 x 1.5
KI-63BX300-S-G	63	300	3/8"	M16 x 1.5
KI-63BX350-S-G	63	350	3/8"	M16 x 1.5
KI-63BX400-S-G	63	400	3/8"	M16 x 1.5
KI-63BX450-S-G	63	450	3/8"	M16 x 1.5
KI-63BX500-S-G	63	500	3/8"	M16 x 1.5
KI-63BX600-S-G	63	600	3/8"	M16 x 1.5
KI-63BX700-S-G	63	700	3/8"	M16 x 1.5
KI-63BX800-S-G	63	800	3/8"	M16 x 1.5
KI-63BX900-S-G	63	900	3/8"	M16 x 1.5
KI-63BX1000-S-G	63	1000	3/8"	M16 x 1.5
KI-80BX25-S-G	80	25	3/8"	M20 x 1.5
KI-80BX50-S-G	80	50	3/8"	M20 x 1.5
KI-80BX75-S-G	80	75	3/8"	M20 x 1.5
KI-80BX80-S-G	80	80	3/8"	M20 x 1.5
KI-80BX100-S-G	80	100	3/8"	M20 x 1.5
KI-80BX125-S-G	80	125	3/8"	M20 x 1.5
KI-80BX150-S-G	80	150	3/8"	M20 x 1.5
KI-80BX160-S-G	80	160	3/8"	M20 x 1.5
KI-80BX175-S-G	80	175	3/8"	M20 x 1.5
KI-80BX200-S-G	80	200	3/8"	M20 x 1.5
KI-80BX250-S-G	80	250	3/8"	M20 x 1.5
KI-80BX300-S-G	80	300	3/8"	M20 x 1.5
KI-80BX350-S-G	80	350	3/8"	M20 x 1.5
KI-80BX400-S-G	80	400	3/8"	M20 x 1.5

Tech Sheet 10657

Further sizes in this range continued on next page

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Gen 2 ISO 15552 Cylinders


Medium:
Clean compressed air. Filtered (40µm) and lubricated adjustable cushioning.
Piston Rod Material: Stainless steel 304
Please note: Bore sizes 125mm are available on a lead time.
Please contact our sales office for details.

2 Year Warranty

Working Temperature: -20°C to +80°C

Working Pressure: 1 to 10 bar

Stainless Steel Piston Rod as Standard



Magnetic Double Acting, Adjustable Cushioning, BSPP

0413	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-80BX450-S-G	80	450	3/8"	M20 x 1.5
KI-80BX500-S-G	80	500	3/8"	M20 x 1.5
KI-80BX600-S-G	80	600	3/8"	M20 x 1.5
KI-80BX700-S-G	80	700	3/8"	M20 x 1.5
KI-80BX800-S-G	80	800	3/8"	M20 x 1.5
KI-80BX900-S-G	80	900	3/8"	M20 x 1.5
KI-80BX1000-S-G	80	1000	3/8"	M20 x 1.5
KI-100BX25-S-G	100	25	1/2"	M20 x 1.5
KI-100BX50-S-G	100	50	1/2"	M20 x 1.5
KI-100BX75-S-G	100	75	1/2"	M20 x 1.5
KI-100BX80-S-G	100	80	1/2"	M20 x 1.5
KI-100BX100-S-G	100	100	1/2"	M20 x 1.5
KI-100BX125-S-G	100	125	1/2"	M20 x 1.5
KI-100BX150-S-G	100	150	1/2"	M20 x 1.5
KI-100BX160-S-G	100	160	1/2"	M20 x 1.5
KI-100BX175-S-G	100	175	1/2"	M20 x 1.5
KI-100BX200-S-G	100	200	1/2"	M20 x 1.5
KI-100BX250-S-G	100	250	1/2"	M20 x 1.5
KI-100BX300-S-G	100	300	1/2"	M20 x 1.5
KI-100BX350-S-G	100	350	1/2"	M20 x 1.5
KI-100BX400-S-G	100	400	1/2"	M20 x 1.5
KI-100BX450-S-G	100	450	1/2"	M20 x 1.5
KI-100BX500-S-G	100	500	1/2"	M20 x 1.5
KI-100BX600-S-G	100	600	1/2"	M20 x 1.5
KI-100BX700-S-G	100	700	1/2"	M20 x 1.5

0413	Bore mm	Stroke mm	Thread	Piston Rod Thread
KI-100BX800-S-G	100	800	1/2"	M20 x 1.5
KI-100BX900-S-G	100	900	1/2"	M20 x 1.5
KI-100BX1000-S-G	100	1000	1/2"	M20 x 1.5
KI-125BX25-S-G	125	25	1/2"	M27 x 2
KI-125BX50-S-G	125	50	1/2"	M27 x 2
KI-125BX75-S-G	125	75	1/2"	M27 x 2
KI-125BX80-S-G	125	80	1/2"	M27 x 2
KI-125BX100-S-G	125	100	1/2"	M27 x 2
KI-125BX125-S-G	125	125	1/2"	M27 x 2
KI-125BX150-S-G	125	150	1/2"	M27 x 2
KI-125BX160-S-G	125	160	1/2"	M27 x 2
KI-125BX175-S-G	125	175	1/2"	M27 x 2
KI-125BX200-S-G	125	200	1/2"	M27 x 2
KI-125BX250-S-G	125	250	1/2"	M27 x 2
KI-125BX300-S-G	125	300	1/2"	M27 x 2
KI-125BX350-S-G	125	350	1/2"	M27 x 2
KI-125BX400-S-G	125	400	1/2"	M27 x 2
KI-125BX450-S-G	125	450	1/2"	M27 x 2
KI-125BX500-S-G	125	500	1/2"	M27 x 2
KI-125BX600-S-G	125	600	1/2"	M27 x 2
KI-125BX700-S-G	125	700	1/2"	M27 x 2
KI-125BX800-S-G	125	800	1/2"	M27 x 2
KI-125BX900-S-G	125	900	1/2"	M27 x 2
KI-125BX1000-S-G	125	1000	1/2"	M27 x 2

Tech Sheet 10657

FT PRO



For **Reed Switches** see page **485**

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PNEUMATIC CYLINDERS

ISO 15552 Mountings



Front/Rear Flange Mounting FA

0334	Bore mm
F-KF32FA	32
F-KF40FA	40
F-KF50FA	50
F-KF63FA	63
F-KF80FA	80
F-KF100FA	100
F-KF125FA	125
Tech Sheet 3012	



Front Trunnion Mounting FTC

0334	Bore mm
F-KF32FTC	32
F-KF40FTC	40
F-KF50FTC	50
F-KF63FTC	63
F-KF80FTC	80
F-KF100FTC	100
F-KF160FTC	160
Tech Sheet 3013	



Front Trunnion Clevis Mounting TF

0334	Bore mm
F-KF32TF	32
F-KF40TF	40/50
F-KF63TF	63/80
F-KF125TF	100/125
Tech Sheet 3014	



Trunnion Support Mounting TM

0334	Bore mm
F-KF32TM	32
F-KF40TM	40/50
F-KF63TM	63/80
F-KF125TM	100/125
F-KF160TM	160/200
Tech Sheet 3015	



Rear Eye Mounting CA

0334	Bore mm
F-KF32CA	32
F-KF40CA	40
F-KF50CA	50
F-KF63CA	63
F-KF80CA	80
F-KF100CA	100
F-KF125CA	125
F-KF160CA	160
F-KF200CA	200
Tech Sheet 3016	



Rear Clevis Mounting CB

0334	Bore mm
F-KF32CB	32
F-KF40CB	40
F-KF50CB	50
F-KF63CB	63
F-KF80CB	80
F-KF100CB	100
F-KF125CB	125
F-KF160CB	160
F-KF200CB	200
Tech Sheet 3017	



Rear Bracket Mounting CR

0334	Bore mm
F-KF32CR	32
F-KF40CR	40
F-KF50CR	50
F-KF63CR	63
F-KF80CR	80
F-KF100CR	100
F-KF125CR	125
F-KF160CR	160
F-KF200CR	200
Tech Sheet 3018	



Foot Mounting LB, (Pair)

0334	Bore mm
F-KF32LB	32
F-KF40LB	40
F-KF50LB	50
F-KF63LB	63
F-KF80LB	80
F-KF100LB	100
F-KF125LB	125
F-KF160LB	160
Tech Sheet 3019	



Piston Rod Clevis YI

0334	Bore mm	Thread
F-M10125YI	32	M10 x 1.25
F-M12125YI	40	M12 x 1.25
F-M16150YI	50/63	M16 x 1.5
F-M20150YI	80/100	M20 x 1.5
F-M27200YI	125	M27 x 2
F-M36200YI	160/200	M36 x 2
Tech Sheet 3020		

Fluid-Air Components Ltd

ISO 15552 Mountings



Piston Rod Clevis I

0334	Bore mm	Thread
F-M10125II	25/32	M10 x 1.25
F-M12125II	40	M12 x 1.25
F-M16150II	50/63	M16 x 1.5
F-M20150II	80/100	M20 x 1.5
F-M27200II	125	M27 x 2
Tech Sheet 3021		



Piston Rod Floating Joint F

0334	Bore mm	Thread
F-M10125F	25/32	M10 x 1.25
F-M12125F	40	M12 x 1.25
F-M16150F	50/63	M16 x 1.5
F-M20150F	80/100	M20 x 1.5
Tech Sheet 3022		



Piston Rod Universal Joint U

0334	Bore mm	Thread
F-M10125U	25/32	M10 x 1.25
F-M12125U	40	M12 x 1.25
F-M16150U	50/63	M16 x 1.5
F-M20150U	80/100	M20 x 1.5
F-M27200U	125	M27 x 2
F-M36200U	160/200	M36 x 2
Tech Sheet 3023		

Reed Switches to suit ISO 15552

Working Temperature:
-10°C to +70°C



Two Wire, N/O with LED

0413	Length mm	Voltage
CSM-E020	2	5-240V AC/DC
CSM-E050	5	5-240V AC/DC
Tech Sheet 20890		

Three Wire, NO Current Flows Out (PNP)

0413	Length mm	Voltage
DSM-EP020	2	5-30V DC
DSM-EP050	5	5-30V DC
Tech Sheet 20890		

Three Wire, NO Current Flows In (NPN)

0413	Length mm	Voltage
DSM-EN020	2	5-30V DC
DSM-EN050	5	5-30V DC
Tech Sheet 20890		



For **FT Pro One Touch+ Plastic Push-in Fittings Emergency Kits** see page **781**

Fluid-Air Components Ltd

PNEUMATIC CYLINDERS


ISO 15552 Standard Cylinder Guides


The guide unit allows for standard ISO 15552 cylinder to move loads with high positioning accuracy.

Features and Benefits

- Protection against rotation at high torques.
- High guide precision for cylinder guiding.
- Supplied plain or recirculating ball bearing guides.

2 Year Warranty





With Slide Bearings

0334	Bore mm	Stroke mm
KRF-32X50-0	32	50
KRF-32X100-0	32	100
KRF-32X160-0	32	160
KRF-32X200-0	32	200
KRF-32X250-0	32	250
KRF-32X320-0	32	320
KRF-32X400-0	32	400
KRF-32X500-0	32	500
KRF-40X50-0	40	50
KRF-40X100-0	40	100
KRF-40X160-0	40	160
KRF-40X200-0	40	200
KRF-40X250-0	40	250
KRF-40X320-0	40	320
KRF-40X400-0	40	400
KRF-40X500-0	40	500
KRF-50X50-0	50	50
KRF-50X100-0	50	100
KRF-50X160-0	50	160
KRF-50X200-0	50	200
KRF-50X250-0	50	250
KRF-50X320-0	50	320
KRF-50X400-0	50	400
KRF-50X500-0	50	500
KRF-63X50-0	63	50
KRF-63X100-0	63	100
KRF-63X160-0	63	160
KRF-63X200-0	63	200
KRF-63X250-0	63	250
KRF-63X320-0	63	320
KRF-63X400-0	63	400
KRF-63X500-0	63	500
KRF-80X50-0	80	50
KRF-80X100-0	80	100
KRF-80X160-0	80	160
KRF-80X200-0	80	200
KRF-80X250-0	80	250
KRF-80X320-0	80	320
KRF-80X400-0	80	400
KRF-80X500-0	80	500
KRF-100X50-0	100	50
KRF-100X100-0	100	100
KRF-100X160-0	100	160
KRF-100X200-0	100	200
KRF-100X250-0	100	250
KRF-100X320-0	100	320
KRF-100X400-0	100	400
KRF-100X500-0	100	500
Tech Sheet 20891		

With Ball Bearings

0334	Bore mm	Stroke mm
KRF-32X50-1	32	50
KRF-32X100-1	32	100
KRF-32X160-1	32	160
KRF-32X200-1	32	200
KRF-32X250-1	32	250
KRF-32X320-1	32	320
KRF-32X400-1	32	400
KRF-32X500-1	32	500
KRF-40X50-1	40	50
KRF-40X100-1	40	100
KRF-40X160-1	40	160
KRF-40X200-1	40	200
KRF-40X250-1	40	250
KRF-40X320-1	40	320
KRF-40X400-1	40	400
KRF-40X500-1	40	500
KRF-50X50-1	50	50
KRF-50X100-1	50	100
KRF-50X160-1	50	160
KRF-50X200-1	50	200
KRF-50X250-1	50	250
KRF-50X320-1	50	320
KRF-50X400-1	50	400
KRF-50X500-1	50	500
KRF-63X50-1	63	50
KRF-63X100-1	63	100
KRF-63X160-1	63	160
KRF-63X200-1	63	200
KRF-63X250-1	63	250
KRF-63X320-1	63	320
KRF-63X400-1	63	400
KRF-63X500-1	63	500
KRF-80X50-1	80	50
KRF-80X100-1	80	100
KRF-80X160-1	80	160
KRF-80X200-1	80	200
KRF-80X250-1	80	250
KRF-80X320-1	80	320
KRF-80X400-1	80	400
KRF-80X500-1	80	500
KRF-100X50-1	100	50
KRF-100X100-1	100	100
KRF-100X160-1	100	160
KRF-100X200-1	100	200
KRF-100X250-1	100	250
KRF-100X320-1	100	320
KRF-100X400-1	100	400
KRF-100X500-1	100	500
Tech Sheet 20892		


Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CYLINDERS

For the full range and more information, please contact one of our sales team.

DSBC STANDARD CYLINDER ★

Features



Product Description

DSBC - 40 - 200 - PPSA - A

- DSBC: Cylinder Type
- 40: Bore Size mm
- 200: Stroke Size mm
- PPSA: Cushioning
  - PPS - Automatic
  - P - Polymer Cushion
  - PPV - Adjustable Pneumatic Cushioning
- A: Magnetic

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 STANDARD CYLINDERS, DSBC

FESTO

Double Acting, Adjustable Pneumatic Cushioning

- Strokes of up to 2800mm
- Excellent flexibility thanks to wide range of variants
- Extensive range of accessories makes it possible to install the cylinder virtually anywhere
- T-Slot


Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2123069	32	20	M10 x 1.25	DSBC-32-20-PPVA-N3
1376422	32	25	M10 x 1.25	DSBC-32-25-PPVA-N3
2123070	32	30	M10 x 1.25	DSBC-32-30-PPVA-N3
1376423	32	40	M10 x 1.25	DSBC-32-40-PPVA-N3
1376424	32	50	M10 x 1.25	DSBC-32-50-PPVA-N3
2123071	32	60	M10 x 1.25	DSBC-32-60-PPVA-N3
2123072	32	70	M10 x 1.25	DSBC-32-70-PPVA-N3
1376425	32	80	M10 x 1.25	DSBC-32-80-PPVA-N3
1376426	32	100	M10 x 1.25	DSBC-32-100-PPVA-N3
1376427	32	125	M10 x 1.25	DSBC-32-125-PPVA-N3
2123073	32	150	M10 x 1.25	DSBC-32-150-PPVA-N3
1376428	32	160	M10 x 1.25	DSBC-32-160-PPVA-N3
1376429	32	200	M10 x 1.25	DSBC-32-200-PPVA-N3
1376430	32	250	M10 x 1.25	DSBC-32-250-PPVA-N3
2123074	32	300	M10 x 1.25	DSBC-32-300-PPVA-N3
1376431	32	320	M10 x 1.25	DSBC-32-320-PPVA-N3
1376432	32	400	M10 x 1.25	DSBC-32-400-PPVA-N3
1376433	32	500	M10 x 1.25	DSBC-32-500-PPVA-N3
Tech Sheet 70239				

Ambient Temperature:
-20°C to +80°C

Working Pressure:
0.6 to 12 bar (Piston: 32, 40mm)
0.4 to 12 bar (Piston 50, 63, 80, 100mm)

Adjustable Cushioning



Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2123166	40	20	M12 x 1.25	DSBC-40-20-PPVA-N3
1376656	40	25	M12 x 1.25	DSBC-50-250-PPVA-N3
2123167	40	30	M12 x 1.25	DSBC-40-30-PPVA-N3
1376657	40	40	M12 x 1.25	DSBC-40-40-PPVA-N3
1376658	40	50	M12 x 1.25	DSBC-40-50-PPVA-N3
2123224	40	60	M12 x 1.25	DSBC-40-60-PPVA-N3
2123225	40	70	M12 x 1.25	DSBC-40-70-PPVA-N3
1376659	40	80	M12 x 1.25	DSBC-40-80-PPVA-N3
1376660	40	100	M12 x 1.25	DSBC-40-100-PPVA-N3
1376661	40	125	M12 x 1.25	DSBC-40-125-PPVA-N3
2123226	40	150	M12 x 1.25	DSBC-40-150-PPVA-N3
1376662	40	160	M12 x 1.25	DSBC-40-160-PPVA-N3
1376663	40	200	M12 x 1.25	DSBC-40-200-PPVA-N3
1376664	40	250	M12 x 1.25	DSBC-40-250-PPVA-N3
2123227	40	300	M12 x 1.25	DSBC-40-300-PPVA-N3
1376665	40	320	M12 x 1.25	DSBC-40-320-PPVA-N3
1376666	40	400	M12 x 1.25	DSBC-40-400-PPVA-N3
1376667	40	500	M12 x 1.25	DSBC-40-500-PPVA-N3
2098969	50	20	M16 x 1.5	DSBC-50-20-PPVA-N3
1366948	50	25	M16 x 1.5	DSBC-50-25-PPVA-N3
2098970	50	30	M16 x 1.5	DSBC-50-30-PPVA-N3
1366949	50	40	M16 x 1.5	DSBC-50-40-PPVA-N3
1366950	50	50	M16 x 1.5	DSBC-50-50-PPVA-N3
2098972	50	60	M16 x 1.5	DSBC-50-60-PPVA-N3
2098973	50	70	M16 x 1.5	DSBC-50-70-PPVA-N3
1366951	50	80	M16 x 1.5	DSBC-50-80-PPVA-N3
1366952	50	100	M16 x 1.5	DSBC-50-100-PPVA-N3
1366953	50	125	M16 x 1.5	DSBC-50-125-PPVA-N3
2098974	50	150	M16 x 1.5	DSBC-50-150-PPVA-N3
1366954	50	160	M16 x 1.5	DSBC-50-160-PPVA-N3
1366955	50	200	M16 x 1.5	DSBC-50-200-PPVA-N3
1366956	50	250	M16 x 1.5	DSBC-40-25-PPVA-N3
2098975	50	300	M16 x 1.5	DSBC-50-300-PPVA-N3
1366957	50	320	M16 x 1.5	DSBC-50-320-PPVA-N3
1366958	50	400	M16 x 1.5	DSBC-50-400-PPVA-N3
1366959	50	500	M16 x 1.5	DSBC-50-500-PPVA-N3
Tech Sheet 70240				

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2125490	63	20	M16 x 1.5	DSBC-63-20-PPVA-N3
1383578	63	25	M16 x 1.5	DSBC-63-25-PPVA-N3
2125491	63	30	M16 x 1.5	DSBC-63-30-PPVA-N3
1383579	63	40	M16 x 1.5	DSBC-63-40-PPVA-N3
1383580	63	50	M16 x 1.5	DSBC-63-50-PPVA-N3
2125492	63	60	M16 x 1.5	DSBC-63-60-PPVA-N3
2125493	63	70	M16 x 1.5	DSBC-63-70-PPVA-N3
1383581	63	80	M16 x 1.5	DSBC-63-80-PPVA-N3
1383582	63	100	M16 x 1.5	DSBC-63-100-PPVA-N3
1383583	63	125	M16 x 1.5	DSBC-63-125-PPVA-N3
2125494	63	150	M16 x 1.5	DSBC-63-150-PPVA-N3
1383584	63	160	M16 x 1.5	DSBC-63-160-PPVA-N3
1383585	63	200	M16 x 1.5	DSBC-63-200-PPVA-N3
1383586	63	250	M16 x 1.5	DSBC-63-250-PPVA-N3
2125495	63	300	M16 x 1.5	DSBC-63-300-PPVA-N3
1383587	63	320	M16 x 1.5	DSBC-63-320-PPVA-N3
1383588	63	400	M16 x 1.5	DSBC-63-400-PPVA-N3
1383589	63	500	M16 x 1.5	DSBC-63-500-PPVA-N3
2126594	80	20	M20 x 1.5	DSBC-80-20-PPVA-N3
1383333	80	25	M20 x 1.5	DSBC-80-25-PPVA-N3
2126595	80	30	M20 x 1.5	DSBC-80-30-PPVA-N3
1383334	80	40	M20 x 1.5	DSBC-80-40-PPVA-N3
1383335	80	50	M20 x1.5	DSBC-80-50-PPVA-N3
2126597	80	60	M20 x 1.5	DSBC-80-60-PPVA-N3
2126598	80	70	M20 x 1.5	DSBC-80-70-PPVA-N3
1383336	80	80	M20 x 1.5	DSBC-80-80-PPVA-N3
1383337	80	100	M20 x 1.5	DSBC-80-100-PPVA-N3
1383338	80	125	M20 x 1.5	DSBC-80-125-PPVA-N3
2126599	80	150	M20 x 1.5	DSBC-80-150-PPVA-N3
1383339	80	160	M20 x 1.5	DSBC-80-160-PPVA-N3
1383340	80	200	M20 x 1.5	DSBC-80-200-PPVA-N3
1383341	80	250	M20 x 1.5	DSBC-80-250-PPVA-N3
2126600	80	300	M20 x 1.5	DSBC-80-300-PPVA-N3
1383342	80	320	M20 x 1.5	DSBC-80-320-PPVA-N3
1383343	80	400	M20 x 1.5	DSBC-80-400-PPVA-N3
1383344	80	500	M20 x 1.5	DSBC-80-500-PPVA-N3
Tech Sheet 70241				

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 STANDARD CYLINDERS, DSBC


Double Acting, Self-adjusting Pneumatic Cushioning

- Strokes of up to 2800mm
- Excellent flexibility thanks to wide range of variants
- Extensive range of accessories makes it possible to install the cylinder virtually anywhere
- T-Slot

Ambient Temperature:
-20°C to +80°C

Working Pressure:
0.6 to 12 bar (Piston: 32, 40mm)
0.4 to 12 bar (Piston 50, 63, 80, 100mm)

Self-adjusting Cushioning



Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2123085	32	20	M10 x 1.25	DSBC-32-20-PPSA-N3
1376467	32	25	M10 x 1.25	DSBC-32-25-PPSA-N3
2123086	32	30	M10 x 1.25	DSBC-32-30-PPSA-N3
1376468	32	40	M10 x 1.25	DSBC-32-40-PPSA-N3
1376469	32	50	M10 x 1.25	DSBC-32-50-PPSA-N3
2123087	32	60	M10 x 1.25	DSBC-32-60-PPSA-N3
2123088	32	70	M10 x 1.25	DSBC-32-70-PPSA-N3
1376470	32	80	M10 x 1.25	DSBC-32-80-PPSA-N3
1376471	32	100	M10 x 1.25	DSBC-32-100-PPSA-N3
1376472	32	125	M10 x 1.25	DSBC-32-125-PPSA-N3
2123089	32	150	M10 x 1.25	DSBC-32-150-PPSA-N3
1376473	32	160	M10 x 1.25	DSBC-32-160-PPSA-N3
1376474	32	200	M10 x 1.25	DSBC-32-200-PPSA-N3
1376475	32	250	M10 x 1.25	DSBC-32-250-PPSA-N3
2123090	32	300	M10 x 1.25	DSBC-32-300-PPSA-N3
1376476	32	320	M10 x 1.25	DSBC-32-320-PPSA-N3
1376477	32	400	M10 x 1.25	DSBC-32-400-PPSA-N3
1376478	32	500	M10 x 1.25	DSBC-32-500-PPSA-N3
Tech Sheet 70242				

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2123780	40	20	M12 x 1.25	DSBC-40-20-PPSA-N3
1376903	40	25	M12 x 1.25	DSBC-40-25-PPSA-N3
2123781	40	30	M12 x 1.25	DSBC-40-30-PPSA-N3
1376904	40	40	M12 x 1.25	DSBC-40-40-PPSA-N3
1376905	40	50	M12 x 1.25	DSBC-40-50-PPSA-N3
2123782	40	60	M12 x 1.25	DSBC-40-60-PPSA-N3
2123783	40	70	M12 x 1.25	DSBC-40-70-PPSA-N3
1376906	40	80	M12 x 1.25	DSBC-40-80-PPSA-N3
1376907	40	100	M12 x 1.25	DSBC-40-100-PPSA-N3
1376908	40	125	M12 x 1.25	DSBC-40-125-PPSA-N3
2123784	40	150	M12 x 1.25	DSBC-40-150-PPSA-N3
1376909	40	160	M12 x 1.25	DSBC-40-160-PPSA-N3
1376910	40	200	M12 x 1.25	DSBC-40-200-PPSA-N3
1376911	40	250	M12 x 1.25	DSBC-40-250-PPSA-N3
2123785	40	300	M12 x 1.25	DSBC-40-300-PPSA-N3
1376912	40	320	M12 x 1.25	DSBC-40-320-PPSA-N3
1376913	40	400	M12 x 1.25	DSBC-40-400-PPSA-N3
1376914	40	500	M12 x 1.25	DSBC-40-500-PPSA-N3
2102628	50	20	M16 x 1.5	DSBC-50-20-PPSA-N3
1376301	50	25	M16 x 1.5	DSBC-50-25-PPSA-N3
2102629	50	30	M16 x 1.5	DSBC-50-30-PPSA-N3
1376304	50	40	M16 x 1.5	DSBC-50-40-PPSA-N3
1376305	50	50	M16 x 1.5	DSBC-50-50-PPSA-N3
2102630	50	60	M16 x 1.5	DSBC-50-60-PPSA-N3
2102631	50	70	M16 x 1.5	DSBC-50-70-PPSA-N3
1376306	50	80	M16 x 1.5	DSBC-50-80-PPSA-N3
1376307	50	100	M16 x 1.5	DSBC-50-100-PPSA-N3
1376308	50	125	M16 x 1.5	DSBC-50-125-PPSA-N3
2102632	50	150	M16 x 1.5	DSBC-50-150-PPSA-N3
1376309	50	160	M16 x 1.5	DSBC-50-160-PPSA-N3
1376310	50	200	M16 x 1.5	DSBC-50-200-PPSA-N3
1376311	50	250	M16 x 1.5	DSBC-50-250-PPSA-N3
2102633	50	300	M16 x 1.5	DSBC-50-300-PPSA-N3
1376312	50	320	M16 x 1.5	DSBC-50-320-PPSA-N3
1376313	50	400	M16 x 1.5	DSBC-50-400-PPSA-N3
1376314	50	500	M16 x 1.5	DSBC-50-500-PPSA-N3
Tech Sheet 70243				

Magnetic

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
2126684	63	20	M16 x 1.5	DSBC-63-20-PPSA-N3
1383632	63	25	M16 x 1.5	DSBC-63-25-PPSA-N3
2126685	63	30	M16 x 1.5	DSBC-63-30-PPSA-N3
1383633	63	40	M16 x 1.5	DSBC-63-40-PPSA-N3
1383634	63	50	M16 x 1.5	DSBC-63-50-PPSA-N3
2126686	63	60	M16 x 1.5	DSBC-63-60-PPSA-N3
2126687	63	70	M16 x 1.5	DSBC-63-70-PPSA-N3
1383635	63	80	M16 x 1.5	DSBC-63-80-PPSA-N3
1383636	63	100	M16 x 1.5	DSBC-63-100-PPSA-N3
1383637	63	125	M16 x 1.5	DSBC-63-125-PPSA-N3
2126688	63	150	M16 x 1.5	DSBC-63-150-PPSA-N3
1383638	63	160	M16 x 1.5	DSBC-63-160-PPSA-N3
1383639	63	200	M16 x 1.5	DSBC-63-200-PPSA-N3
1383640	63	250	M16 x 1.5	DSBC-63-250-PPSA-N3
2126689	63	300	M16 x 1.5	DSBC-63-300-PPSA-N3
1383641	63	320	M16 x 1.5	DSBC-63-320-PPSA-N3
1383642	63	400	M16 x 1.5	DSBC-63-400-PPSA-N3
1383643	63	500	M16 x 1.5	DSBC-63-500-PPSA-N3
2126636	80	20	M20 x 1.5	DSBC-80-20-PPSA-N3
1383366	80	25	M20 x 1.5	DSBC-80-25-PPSA-N3
2126637	80	30	M20 x 1.5	DSBC-80-30-PPSA-N3
1383367	80	40	M20 x 1.5	DSBC-80-40-PPSA-N3
1383368	80	50	M20 x 1.5	DSBC-80-50-PPSA-N3
2126638	80	60	M20 x 1.5	DSBC-80-60-PPSA-N3
2126639	80	70	M20 x 1.5	DSBC-80-70-PPSA-N3
1383369	80	80	M20 x 1.5	DSBC-80-80-PPSA-N3
1383370	80	100	M20 x 1.5	DSBC-80-100-PPSA-N3
1383371	80	125	M20 x 1.5	DSBC-80-125-PPSA-N3
2126640	80	150	M20 x 1.5	DSBC-80-150-PPSA-N3
1383372	80	160	M20 x 1.5	DSBC-80-160-PPSA-N3
1383373	80	200	M20 x 1.5	DSBC-80-200-PPSA-N3
1383374	80	250	M20 x 1.5	DSBC-80-250-PPSA-N3
2126641	80	300	M20 x 1.5	DSBC-80-300-PPSA-N3
1383375	80	320	M20 x 1.5	DSBC-80-320-PPSA-N3
1383376	80	400	M20 x 1.5	DSBC-80-400-PPSA-N3
1383377	80	500	M20 x 1.5	DSBC-80-500-PPSA-N3
Tech Sheet 70244				

Fluid-Air Components Ltd

CYLINDER ATTACHMENTS & ACCESSORIES

FESTO

ISO 15552 Cylinders Mounting Components for Drive Units




Standard Swivel Flange with Spherical Rod Eye, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
174397	32	SNCS-32
174398	40	SNCS-40
174399	50	SNCS-50
174400	63	SNCS-63
174401	80	SNCS-80
Tech Sheet 70220		



Standard Swivel Flange, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
174383	32	SNC-32
174384	40	SNC-40
174385	50	SNC-50
174386	63	SNC-63
174387	80	SNC-80
Tech Sheet 70222		



Trunnion Mounting Kit, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
2213233	32	DAMT-V1-32-A
2214899	40	DAMT-V1-40-A
2214909	50	DAMT-V1-50-A
2214971	63	DAMT-V1-63-A
163529	80	DAMT-V1-80-A
Tech Sheet 70224		



Wide Swivel Flange, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
174404	32	SNCL-32
174405	40	SNCL-40
174406	50	SNCL-50
174407	63	SNCL-63
174408	80	SNCL-80
Tech Sheet 70221		



Wide Swivel Flange, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
174390	32	SNCB-32
174391	40	SNCB-40
174392	50	SNCB-50
174393	63	SNCB-63
174394	80	SNCB-80
Tech Sheet 70223		

Piston Rod Attachments



SGS, Rod Eyes

0009	Thread	Manufacturer's Code
9254	M6	SGS-M6
9255	M8	SGS-M8
9261	M10 x 1.25	SGS-M10X1.25
9262	M12 x 1.25	SGS-M12X1.25
9263	M16 x 1.5	SGS-M16X1.5
9264	M20 x 1.5	SGS-M20X1.5
Tech Sheet 71576		



Clevis Foot Mounting, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
33890	32	LNG-32
33891	40	LNG-40
33892	50	LNG-50
33893	63	LNG-63
33894	80	LNG-80
Tech Sheet 70215		



Foot Mountings, ISO 15552

0009	To Suit Bore mm	Manufacturer's Code
174369	32	HNC-32
174370	40	HNC-40
174371	50	HNC-50
174372	63	HNC-63
174373	80	HNC-80
Tech Sheet 70219		

For use with all cylinders.



Rod Clevis

0009	Thread	Manufacturer's Code
3110	M6	SG-M6
3111	M8	SG-M8
6144	M10 x 1.25	SG-M10X1.25
6145	M12 x 1.25	SG-M12X1.25
6146	M16 x 1.25	SG-M16X1.5
6147	M20 x 1.5	SG-M20X1.5
Tech Sheet 71577		

FAC Fluid-Air Components Ltd

ISO 15552 CYLINDERS

Double Acting Cylinders


Technical Data for ISO 15552 Cylinders
- Fluid: unlubricated air (lubrication, if used, must be continuous)
- Sensor magnet: all versions come complete with magnet
- Piston rod material: C40 chromed steel Ø32-63
- Piston seal: NBR

Temperature Range:
10°C to +70°C

Maximum Operating Pressure:
10 bar

Dimensions

Ø	A	A1	A2	B	C	C1	CH	CH1	D	D1	D2	E	E1	F	G	G1	H	Ø	L	L0	L1	L2	M	N	P	Q
32	10	7	10	30	26	16	10	6	M10 x 1.25	12	15	32.5	5	22	G1/8	M6	47	32	120	94	74	146	9	4.5	6	4
40	12	9	10	35	30	20	13	6	M12 x 1.25	16	19	38	5	24	G1/4	M6	53	40	135	105	81	165	9	4.5	6	4
50	14	14	10	40	37	25	17	8	M16 x 1.5	20	19	46.5	5	32	G1/4	M8	65	50	143	106	78	180	12	5.5	6	6
63	16	14	10	45	37	25	17	8	M16 x 1.5	20	23	56.5	5	32	G3/8	M8	75	63	158	121	89	195	12	5.5	6	6
80	18	12	12	45	46	33	22	10	M20 x 1.5	25	23	72	8	40	G3/8	M10	95	80	174	128	92	220	16	5.5	10	7
100	20	14	12	55	51	38	22	10	M20 x 1.5	25	27	89	8	40	G1/2	M10	115	100	189	138	98	240	16	5.5	10	7
125	25	21	10	60	65	45	27	12	M27 x 2	32	27	110	8	54	G1/2	M12	140	125	225	160	110	290	19	6.5	12	8



More Sizes Available
Up to 320mm diameter & 2600mm stroke



Magnetic & Cushioned


9195	Diameter (mm)	Stroke (mm)
1213320025CN	32	25
1213320050CN	32	50
1213320080CN	32	80
1213320100CN	32	100
1213320125CN	32	125
1213320160CN	32	160
1213320200CN	32	200
1213320250CN	32	250
1213320320CN	32	320
1213320400CN	32	400
1213320500CN	32	500
1213400025CN	40	25
1213400050CN	40	50
1213400080CN	40	80
1213400100CN	40	100
1213400125CN	40	125
1213400160CN	40	160

9195	Diameter (mm)	Stroke (mm)
1213400200CN	40	200
1213400250CN	40	250
1213400320CN	40	320
1213400400CN	40	400
1213400500CN	40	500
1213500025CN	50	25
1213500050CN	50	50
1213500080CN	50	80
1213500100CN	50	100
1213500125CN	50	125
1213500160CN	50	160
1213500200CN	50	200
1213500250CN	50	250
1213500320CN	50	320
1213500400CN	50	400
1213500500CN	50	500

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 CYLINDERS

Double Acting Cylinders





Magnetic & Cushioned

9195	Diameter (mm)	Stroke (mm)
1213630025CN	63	25
1213630050CN	63	50
1213630080CN	63	80
1213630100CN	63	100
1213630125CN	63	125
1213630160CN	63	160
1213630200CN	63	200
1213630250CN	63	250
1213630320CN	63	320
1213630400CN	63	400
1213630500CN	63	500
1213800025AN	80	25
1213800050AN	80	50
1213800080AN	80	80
1213800100AN	80	100
1213800125AN	80	125
1213800160AN	80	160
1213800200AN	80	200
1213800250AN	80	250
1213800320AN	80	320
1213800400AN	80	400

9195	Diameter (mm)	Stroke (mm)
1213800500AN	80	500
1213A10025AN	100	25
1213A10050AN	100	50
1213A10080AN	100	80
1213A10100AN	100	100
1213A10125AN	100	125
1213A10160AN	100	160
1213A10200AN	100	200
1213A10250AN	100	250
1213A10320AN	100	320
1213A10400AN	100	400
1213A10500AN	100	500
1213A20100AN	125	100
1213A20125AN	125	125
1213A20160AN	125	160
1213A20200AN	125	200
1213A20250AN	125	250
1213A20320AN	125	320
1213A20400AN	125	400
1213A20500AN	125	500

SYNTESI® METAL WORK PNEUMATIC



For **Metal Work Standard Series FRL's 'Syntesti'**
see pages **668-672**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 CYLINDERS


Double Acting Cylinders

Technical Data for ISO 15552 Cylinders Ø 160-320
- Design: round barrel with tie rods
- Sensor magnet: all versions come complete with magnet
- Piston rod material: C45 steel, chromed
- Piston seal: NBR
- Options: available with mounted intermediate hinge

Temperature Range:
10°C to +80°C

Maximum Operating Pressure:
10 bar

More Sizes Available
Up to 320mm diameter & 2600mm stroke



Magnetic & Cushioned

9195	Diameter mm	Stroke mm
W1211600025	160	25
W1211600050	160	50
W1211600080	160	80
W1211600100	160	100
W1211600125	160	125
W1211600160	160	160
W1211600200	160	200
W1211600250	160	250
W1211600320	160	320
W1211600400	160	400
W1211600500	160	500
W1212000025	200	25
W1212000050	200	50
W1212000080	200	80
W1212000100	200	100
W1212000125	200	125
W1212000160	200	160
W1212000200	200	200
W1212000250	200	250
W1212000320	200	320
W1212000400	200	400
W1212000500	200	500

9195	Diameter mm	Stroke mm
W1212500025	250	25
W1212500050	250	50
W1212500080	250	80
W1212500100	250	100
W1212500125	250	125
W1212500160	250	160
W1212500200	250	200
W1212500250	250	250
W1212500320	250	320
W1212500400	250	400
W1212500500	250	500
W1213200025	320	25
W1213200050	320	50
W1213200080	320	80
W1213200100	320	100
W1213200125	320	125
W1213200160	320	160
W1213200200	320	200
W1213200250	320	250
W1213200320	320	320
W1213200400	320	400
W1213200500	320	500


For dimensions and further technical information refer to sales team.

Fluid-Air Components Ltd

ISO 15552 CYLINDERS ACCESSORIES

Foot Mounting






To suit ISO 15552 Cylinders

9146	Ø	AB	AH	AO	AT	AU	TR	UH	H1	H2
W0950322001	32	7	32	35	4	24	32	45	144	142
W0950402001	40	9	36	43	4	28	36	52	163	161
W0950502001	50	9	45	47	4	32	45	65	175	170
W0950632001	63	9	50	47	6	32	50	75	190	185
W0950802001	80	12	63	61	6	41	63	95	215	210
W0951002001	100	14	71	66	6	41	75	115	230	220
W0951252001	125	16	90	60	7	45	90	140	270	250
W0951602001	160	18	115	80	10	60	115	180	319	300
W0952002001	200	22	135	100	10	70	135	220	345	320

Female Hinge






To suit ISO 15552 Cylinders

9146	Ø	B	D	E	ØG	H3	R	S
W0950322003	32	45	26	22	10	142	11	10
W0950402003	40	52	28	25	12	160	13	10
W0950502003	50	60	32	27	12	170	13	12
W0950632003	63	70	40	32	16	190	17	12
W0950802003	80	90	50	36	16	210	17	16
W0951002003	100	110	60	41	20	230	21	16
W0951252003	125	130	70	50	25	275	26	20
W0951602003	160	170	90	55	30	314	25	20
W0952002003	200	170	90	60	30	335	25	25

Male Hinge





To suit ISO 15552 Cylinders

9146	Ø	D	E	F	ØG	H	H2
W0950322004	32	26	22	11	10	10	142
W0950402004	40	28	25	13	12	10	160
W0950502004	50	32	27	13	12	12	170
W0950632004	63	40	32	17	16	12	190
W0950802004	80	50	36	17	16	16	210
W0951002004	100	60	41	21	20	16	230
W0951252004	125	70	50	26	25	20	1590
W0951602004	160	90	55	25	30	20	314
W0952002004	200	90	60	25	30	25	335

Fluid-Air Components Ltd


ISO 15552 CYLINDERS ACCESSORIES

Male 90° Hinge

To suit ISO 15552 Cylinders

9146	Ø	B	C	D	E	G	L	M	N
W0950322108	32	25.5	25	45	7	32	10	10	10
W0950402108	40	27.5	32	52	7	36	10	12	12
W0950502108	50	31.5	32	65	9	45	12	12	12
W0950632108	63	39.5	40	75	9	50	16	16	15
W0950802108	80	49.5	40	95	11	63	16	16	15
W0951002108	100	59.5	50	115	11	21	20	20	22
W0951252008	125	70	50	25	14	90	16	25	22







Flange Mounting

To suit ISO 15552 Cylinders

9146	Ø	B	B1	B2	B3	B4	ØD4	T
W0950322002	32	64	80	50	10	32	7	16
W0950402002	40	72	90	55	10	36	9	20
W0950502002	50	90	110	65	12	45	9	25
W0950632002	63	100	120	75	12	50	9	25
W0950802002	80	126	153	95	16	63	12	30
W0951002002	100	150	178	115	16	75	14	35
W0951252002	125	180	220	140	20	90	16	45
W0951602002	160	230	270	180	20	115	18	59
W0952002002	200	270	312	225	25	135	22	70







Piston Rod Nut

To suit ISO 15552 Cylinders

9146	Ø	D	H	SW
W0950322010	32	M10 x 1.25	6	17
W0950402010	40	M12 x 1.25	7	19
W0950502010	50-63	M16 x 1.5	8	24
W0950802010	80-100	M20 x 1.5	9	30
W0951252010	125	M27 x 2	12	74
W0951602010	160/200	M36 x 2	14	55






Fork Clevis

To suit ISO 15552 Cylinders

9146	Ø	M	A	B	C	L	F	D
W0950322020	32	10	20	10	20	52	40	M10 x 1.25
W0950402020	40	12	24	12	24	62	48	M12 x 1.25
W0950502020	50/63	16	32	16	32	83	64	M16 x 1.5
W0950802020	80/100	20	40	20	40	106	80	M20 x 1.5
W0951252020	125	30	55	30	55	148	110	M27 x 2
W0951602008	160/200	90	63	154	18	140	20	30
W0951602020	160/200	35	70	35	72	188	144	M36 x 2





Fluid-Air Components Ltd


ISO 15552 CYLINDERS ACCESSORIES

Spherical Rod Eye

To suit ISO 15552 Cylinders

9146	Ø	M	B1	B	A	L	F	D	CH	ØG
W0950322025	32	10	10.5	14	28	57	43	M10 x 1.25	17	15
W0950402025	40	12	12	16	32	66	50	M12 x 1.25	19	17.5
W0950502025	50/63	16	15	21	42	85	64	M16 x 1.5	22	22
W0950802025	80/100	20	18	25	50	102	77	M20 x 1.5	30	27.5
W0951252025	125	30	25	37	70	145	110	M27 x 2	41	40
W0952002025	160/200	35	28	43	80	165	125	M36 x 2	58	46






Reed Switch

Technical Data

Type		Contact
Maximum AC/DC voltage	V	Reed + varistor + LED 2 wires
		Reed + varistor + LED NO
		220 ISO cylinder
Maximum current at +25°C	mA	1,000
Power with inductive load	VA	15
Power with resistive load	Watt	50
Switch-on time	M sec	1.2
Switch-off time	M sec	0.1
Cable length		2.5m
Cable material		Soft PVC
Switch-on point	Gauss	110
Switch-off point	Gauss	95
Contact resistance		0.1



To suit ISO 15552 Cylinders

9146	Description
W0950000201	Reed Sensor ACC.DSM2-C525

Reed Switch Bracket



To suit ISO 15552 Cylinders

9146	Description	Cylinder Diameter
W0950000711	Bracket ACC. D.32 DST 80	32-40
W0950000712	Bracket ACC. D.50 DST 81	50-63
W0950000713	Bracket ACC. D.80-100-125 DST 82	80-125
0951602093	Bracket ACC. D.160-200	160-200

Seal Kits

Other variants available on request



To suit ISO 15552 Cylinders

9146	Ø	Material
0090320502	32	NBR
0090400502	40	NBR
0090500502	50	NBR
0090630502	63	NBR
0090800502	80	NBR
0091000502	100	NBR
0091250502	125	NBR

Sensor Tester with M8 & M12 Connections

This sensor tester features the following:

- A green light and acoustic signal indicating correct operation
- Sensors can be checked without having to be disassembled
- M8 and M12 connections and terminal board for direct connection to the wires
- PNP or NPN switching button

Technical Data

- Container material: PA 6.6 blue
- Degree of protection: IP00
- Connections: M8 and M12 plug-socket type with 40cm cable
- Additional connections: three terminals for wire connection
- Power supply: 9V DC (battery type 6LR61)
- Internal voltage: 15V DC
- Green light: tester switched on
- Yellow light: sensor in operation
- Red light: battery fla



Automatic Switch Off


9146	Dimensions (mm)
W0950060000	63 x 88 x 24

Fluid-Air Components Ltd

CYLINDER GUIDE UNITS FOR ISO15552 CYLINDER


Profile (GD4) & (GDM

More Sizes Available
Up to 100mm diameter & 1000mm stroke



With Self-lubricating Bushings

9147	Diameter mm	Stroke mm
HGU020-0100	20	100
HGU020-0200	20	200
HGU020-0250	20	250
HGU020-0320	20	320
HGU020-0400	20	400
HGU020-0500	20	500
HGU032-0100	32	100
HGU032-0200	32	200
HGU032-0250	32	250
HGU032-0320	32	320
HGU032-0400	32	400
HGU032-0500	32	500
HGU040-0100	40	100
HGU040-0200	40	200
HGU040-0250	40	250
HGU040-0320	40	320
HGU040-0400	40	400
HGU040-0500	40	500
HGU050-0100	50	100
HGU050-0200	50	200
HGU050-0250	50	250
HGU050-0320	50	320
HGU050-0400	50	400
HGU050-0500	50	500
HGU063-0100	63	100
HGU063-0200	63	200
HGU063-0250	63	250
HGU063-0320	63	320
HGU063-0400	63	400
HGU063-0500	63	500




Fluid-Air Components Ltd

CYLINDER GUIDE UNITS FOR ISO15552 CYLINDER


Profile (GD4) & (GDM

More Sizes Available
Up to 100mm diameter & 1000mm stroke




With Self-lubricating Bushings

9147	Diameter mm	Stroke mm
UGU020-0100	20	100
UGU020-0200	20	200
UGU020-0320	20	320
UGU020-0400	20	400
UGU020-0500	20	500
UGU032-0100	32	100
UGU032-0200	32	200
UGU032-0250	32	250
UGU032-0320	32	320
UGU032-0400	32	400
UGU032-0500	32	500
UGU040-0100	40	100
UGU040-0200	40	200
UGU040-0250	40	250
UGU040-0320	40	320
UGU040-0400	40	400
UGU040-0500	40	500
UGU050-0100	50	100
UGU050-0200	50	200
UGU050-0250	50	250
UGU050-0320	50	320
UGU050-0400	50	400
UGU050-0500	50	500
UGU063-0100	63	100
UGU063-0200	63	200
UGU063-0250	63	250
UGU063-0320	63	320
UGU063-0400	63	400
UGU063-0500	63	500




Rear End Plate



To suit Guide Units

9147	Description
KG3043.20	For 20/25mm Guide Units
KG3043.32	For 32mm Guide Units
KG3043.40	For 40mm Guide Units
KG3043.50	For 50mm Guide Units
KG3043.63	For 63mm Guide Units



Fluid-Air Components Ltd

ISO 15552 CYLINDERS, SERIES HCR (HIGH CORROSION RESISTANCE)

Uses stainless steel fixing

In some applications, cylinders are exposed to aggressive environments (e.g. the dairy, fruit and vegetable, and food industry) or to substances and washings with aggressive detergents (e.g. caustic soda, hydrochloric acid and lactic acid). Under these conditions, the HCR series cylinders ensure better corrosion resistance.

Cylinders made to ISO 15552, designed and built with materials and/or surface treatments that are highly resistant to corrosion


They come in various versions and with specific range of accessories


- with or without magnet
- with single or through piston rod

Also available with liner in the STD series or series 3



1.	Piston rod: AISI 316, thickness chromed
2.	Head: anodised pressure die-cast aluminium, epoxy-vinyl ester and epoxy-resin powder coating
3.	Piston rod gasket: special polyurethane
4.	Guide bushing: steel strip with bronze and PTFE insert
5.	Barrel: drawn anodised calibrated aluminium
6.	Semi-piston: made of self-lubricating technopolymer with built-in cushioning olives (aluminium with technopolymer shoe for Ø 80, 10 and 125)
7.	Piston gasket: NBR
8.	Magnet: plastoferrite
9.	Buffer + static O-rings: NBR
10.	Cushioning gasket: NBR
11.	Needle: AISI 316, screws: AISI 316
12.	Screws: AISI 316





Ø	PL	VD	A	B	B1	WH	C1	CH1	CH2	CH3	KK	D	TG	VA	F	EE	RT	E	E1 min	E1 max	L	LO	ZM	BG	N	P	Q
32	10	6.5	10	30	28	26	16	10	17	6	M10 x 1.25	12	32.5	4	22	G1/8	M6	46	5.5	8.4	120	94	146	14.5	4.5	6	4
40	12	8	10	35	33	30	20	13	19	6	M12 x 1.25	16	38	4	24	G1/4	M6	54	4.5	8.4	135	105	165	14.5	4.5	6	4
50	14	13	10	40	38	37	25	17	24	8	M16 x 1.5	20	46.5	4	32	G1/4	M8	64.5	4.5	8.9	143	106	180	17.5	5.5	6	6
63	16	14	10	45	40	37	25	17	24	8	M16 x 1.5	20	56.5	4	32	G3/8	M8	75.5	4.1	9.5	158	121	195	17.5	5.5	6	6
80	18	12	12	45	43	46	33	22	30	10	M20 x 1.5	25	72	4	40	G3/8	M10	94	6.2	12.2	174	128	220	21.5	5.5	10	7
100	20	14	12	55	49	51	38	22	30	10	M20 x 1.5	25	89	4	40	G1/2	M10	111	6.7	12.2	189	138	240	21.5	5.5	10	7
125	25	20	10	60	54	65	45	27	41	12	M27 x 2	32	110	6	54	G1/2	M12	135	5.7	12.7	225	160	290	25.5	6.5	12	8

Fluid-Air Components Ltd

ISO 15552 CYLINDERS, SERIES HCR (HIGH CORROSION RESISTANCE)

ISO 15552 HCR Double Acting Cylinders

Uses stainless steel accessories



Magnetic & Cushioned

9195	Diameter mm	Stroke mm
1213320025BL	32	25
1213320050BL	32	50
1213320080BL	32	80
1213320100BL	32	100
1213320125BL	32	125
1213320160BL	32	160
1213320200BL	32	200
1213320250BL	32	250
1213320320BL	32	320
1213320400BL	32	400
1213320500BL	32	500
1213400025BL	40	25
1213400050BL	40	50
1213400080BL	40	80
1213400100BL	40	100
1213400125BL	40	125
1213400160BL	40	160
1213400200BL	40	200
1213400250BL	40	250
1213400320BL	40	320
1213400400BL	40	400
1213400500BL	40	500
1213500025BL	50	25
1213500050BL	50	50
1213500080BL	50	80
1213500100BL	50	100
1213500125BL	50	125
1213500160BL	50	160
1213500200BL	50	200
1213500250BL	50	250
1213500320BL	50	320
1213500400BL	50	400
1213500500BL	50	500
1213630025BL	63	25
1213630050BL	63	50
1213630080BL	63	80
1213630100BL	63	100

9195	Diameter mm	Stroke mm
1213630125BL	63	125
1213630160BL	63	160
1213630200BL	63	200
1213630250BL	63	250
1213630320BL	63	320
1213630400BL	63	400
1213630500BL	63	500
1213800025WL	80	25
1213800050WL	80	50
1213800080WL	80	80
1213800100WL	80	100
1213800125WL	80	125
1213800160WL	80	160
1213800200WL	80	200
1213800250WL	80	250
1213800320WL	80	320
1213800400WL	80	400
1213800500WL	80	500
1213A10025WL	100	25
1213A10050WL	100	50
1213A10080WL	100	80
1213A10100WL	100	100
1213A10125WL	100	125
1213A10160WL	100	160
1213A10200WL	100	200
1213A10250WL	100	250
1213A10320WL	100	320
1213A10400WL	100	400
1213A10500WL	100	500
1213A20100WL	125	100
1213A20125WL	125	125
1213A20160WL	125	160
1213A20200WL	125	200
1213A20250WL	125	250
1213A20320WL	125	320
1213A20400WL	125	400
1213A20500WL	125	500

For **correct magnetic sensors & fitting**
contact sales department

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 AIR CYLINDERS, ALL STAINLESS STEEL


Technical Specifications
Fluid: lubricated or non-lubricated air


Temperature Range:
10°C to +80°C

Maximum Operating Pressure:
10 bar



1. Piston rod: AISI 316 steel
2. Head: AISI 304 steel
3. Piston rod gasket: polyurethane or FKM/FPM
4. Guide bushing: sintered bronze
5. Barrel: AISI 304 steel
6. Enbloc gasket: NBR or FKM/FPM
7. Magnet: plastoferrite
8. Static O-rings: NBR or FKM/FPM
9. Cushioning gasket: polyurethane or FKM/FPM
10. Cushioning needle: AISI 304 steel
11. Tie rod: AISI 316 steel
12. Needle-retaining ring: technopolymer





Ø	A	A_1	A_2	B	C	C_1	CH	CH_1	D	D_1	E	E_1	F	G	G_1	H	L	L_0	L_1	L_2	P
32	13	9	11.3	30	26	18	10	6	M10 x 1.25	12	32.5	4	22	G1/8	M6	50	120	94	68	146	6
40	14	9	13	35	30	22	13	6	M12 x 1.25	16	38	4	24	G1/4	M6	55	135	105	77	165	8
50	14	9	12.7	40	37	25.5	17	8	M16 x 1.5	20	46.5	4	32	G1/4	M8	65	143	106	78	180	11.8
63	16	9	15.8	45	37	25	17	8	M16 x 1.5	20	56.5	4	32	G3/8	M8	75	158	121	89	195	11.7
80	17	10	16.3	45	46	35	22	-	M20 x 1.5	25	72	4	40	G3/8	M10	95	174	128	94	220	15.5
100	18	10	15.5	55	51	38	22	-	M20 x 1.5	25	89	4	40	G1/2	M10	110	189	138	102	240	15.5
125	18	11	20	60	65	46	27	-	M27 x 2	32	110	6	54	G1/2	M12	140	225	160	124	290	15

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

ISO 15552 AIR CYLINDERS, ALL STAINLESS STEEL

ISO 15552 Cylinders, Double Acting

Technical Specifications
Fluid: lubricated or non-lubricated air

Temperature Range:
10°C to +80°C

Maximum Operating Pressure:
10 bar



Magnetic

9146	Diameter mm	Stroke mm
W1840320025	32	25
W1840320050	32	50
W1840320080	32	80
W1840320100	32	100
W1840320125	32	125
W1840320160	32	160
W1840320200	32	200
W1840320250	32	250
W1840320320	32	320
W1840320400	32	400
W1840320500	32	500
W1840400025	40	25
W1840400050	40	50
W1840400080	40	80
W1840400100	40	100
W1840400125	40	125
W1840400160	40	160
W1840400200	40	200
W1840400250	40	250
W1840400320	40	320
W1840400400	40	400
W1840400500	40	500
W1840500025	50	25
W1840500050	50	50
W1840500080	50	80
W1840500100	50	100
W1840500125	50	125
W1840500160	50	160
W1840500200	50	200
W1840500250	50	250
W1840500320	50	320
W1840500400	50	400
W1840500500	50	500

9146	Diameter mm	Stroke mm
W1840630025	63	25
W1840630050	63	50
W1840630080	63	80
W1840630100	63	100
W1840630125	63	125
W1840630160	63	160
W1840630200	63	200
W1840630250	63	250
W1840630320	63	320
W1840630400	63	400
W1840630500	63	500
W1840800025	80	25
W1840800050	80	50
W1840800080	80	80
W1840800100	80	100
W1840800125	80	125
W1840800160	80	160
W1840800200	80	200
W1840800250	80	250
W1840800320	80	320
W1840800400	80	400
W1840800500	80	500
W1841000025	100	25
W1841000050	100	50
W1841000080	100	80
W1841000100	100	100
W1841000125	100	125
W1841000160	100	160
W1841000200	100	200
W1841000250	100	250
W1841000320	100	320
W1841000400	100	400
W1841000500	100	500

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 AIR CYLINDER ACCESSORIES, ALL STAINLESS STEEL

Foot Mounting



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322001	32
W095X402001	40
W095X502001	50
W095X632001	63
W095X802001	80
W095XA12001	100

Male 90° Hinge



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322008	32
W095X402008	40
W095X502008	50
W095X632008	63
W095X802008	80
W095XA12008	100

Male Hinge



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322004	32
W095X402004	40
W095X502004	50
W095X632004	63
W095X802004	80
W095XA12004	100

Female Hinge



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322003	32
W095X402003	40
W095X502003	50
W095X632003	63
W095X802003	80
W095XA12003	100



For **Syntesi Metal Work Standard Series FRL's** see page **666**

Fluid-Air Components Ltd

ISO 15552 AIR CYLINDER ACCESSORIES, ALL STAINLESS STEEL

Hinge Pin



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322050	32
W095X402050	40
W095X502050	50
W095X632050	63
W095X802050	80
W095XA12050	100

Fork Clevis



To suit ISO 15552 Cylinders

9146	To Suit Size mm	Thread
W095X322020	25/32	M10 x 1.25
W095X402020	40	M12 x 1.25
W095X502020	50/63	M16 x 1.5
W095X802020	80/100	M20 x 1.5

Intermediate Hinge



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322007	32
W095X402007	40
W095X502007	50
W095X632007	63
W095X802007	80
W095XA12007	100

Flange



To suit ISO 15552 Cylinders

9146	To Suit Size mm
W095X322002	32
W095X402002	40
W095X502002	50
W095X632002	63
W095X802002	80
W095XA12002	100

Rod Nuts



To suit ISO 15552 Cylinders

9146	To Suit Size	Thread
W095X322011	25/32	M10 x 1.25
W095X402011	40	M12 x 1.25
W095X502011	50/63	M16 x 1.5
W095X802011	80/100	M20 x 1.5

Reed Switch



To suit ISO 15552 Cylinders

9146	Thread
W0952022180	With Moulded Cable
W0952028184	With M8 Connection

Mounting for Reed Switch



To suit ISO 15552 Cylinders

9146
W0950001100

Fluid-Air Components Ltd

ISO 15552 CYLINDERS & MOUNTINGS


ISO 15552 Cylinders

- Cylinder conforms to ISO 15552
- High performance adaptive cushioning system "ACS"
- Polyurethane seals ensure efficient low friction operation and long life
- Switches can be mounted flush with the profile barrel
- Comprehensive range of standard mountings

Medium: Compressed air, filtered, lubricated or non-lubricated
Operation: Double acting, adjustable cushioning.
Profile Anodised aluminium
Piston Rod: Stainless steel (martensitic)
Piston Rod Seals: Polyurethane
Piston Seals: Polyurethane
O-Rings: Nitrile Rubber
End Covers: Pressure diecast aluminium

Working Temperature: -20°C to +80°C

Working Pressure: 1 to 16 bar





PROFILE BARREL

Double Acting, 8020 Series

0036	Bore mm	Stroke mm	Thread
PRA/802032/M/25	32	25	1/8"
PRA/802032/M/50	32	50	1/8"
PRA/802032/M/80	32	80	1/8"
PRA/802032/M/100	32	100	1/8"
PRA/802032/M/125	32	125	1/8"
PRA/802032/M/160	32	160	1/8"
PRA/802032/M/200	32	200	1/8"
PRA/802032/M/250	32	250	1/8"
PRA/802032/M/320	32	320	1/8"
PRA/802040/M/50	40	50	1/4"
PRA/802040/M/80	40	80	1/4"
PRA/802040/M/100	40	100	1/4"
PRA/802040/M/160	40	160	1/4"
PRA/802040/M/200	40	200	1/4"
PRA/802050/M/25	50	25	1/4"
PRA/802050/M/50	50	50	1/4"
PRA/802050/M/80	50	80	1/4"
PRA/802050/M/100	50	100	1/4"
PRA/802050/M/125	50	125	1/4"
PRA/802050/M/160	50	160	1/4"
PRA/802050/M/200	50	200	1/4"
PRA/802050/M/250	50	250	1/4"
PRA/802050/M/320	50	320	1/4"
PRA/802063/M/25	63	25	3/8"
PRA/802063/M/50	63	50	3/8"
PRA/802063/M/80	63	80	3/8"
PRA/802063/M/100	63	100	3/8"
PRA/802063/M/125	63	125	3/8"
PRA/802063/M/160	63	160	3/8"
PRA/802063/M/200	63	200	3/8"
PRA/802063/M/250	63	250	3/8"
PRA/802063/M/320	63	320	3/8"
PRA/802080/M/25	80	25	3/8"
PRA/802080/M/50	80	50	3/8"
PRA/802080/M/80	80	80	3/8"
PRA/802080/M/160	80	160	3/8"
PRA/802080/M/200	80	200	3/8"
PRA/802080/M/250	80	250	3/8"
PRA/802100/M/50	100	50	1/2"
PRA/802100/M/100	100	100	1/2"
PRA/802100/M/125	100	125	1/2"
PRA/802100/M/160	100	160	1/2"
PRA/802100/M/250	100	250	1/2"
PRA/802100/M/320	100	320	1/2"

Tech Sheet 71373

Self adjusting cushioning feature



ROUND BARREL

Tie rod double acting cylinder, round barrel RA/802 Series

0036	Bore mm	Stroke mm	Thread
RA/802032/M/25	32	25	1/8"
RA/802032/M/50	32	50	1/8"
RA/802032/M/80	32	80	1/8"
RA/802032/M/100	32	100	1/8"
RA/802032/M/125	32	125	1/8"
RA/802032/M/160	32	160	1/8"
RA/802032/M/200	32	200	1/8"
RA/802032/M/250	32	250	1/8"
RA/802032/M/320	32	320	1/8"
RA/802040/M/25	40	25	1/4"
RA/802040/M/50	40	50	1/4"
RA/802040/M/80	40	80	1/4"
RA/802040/M/100	40	100	1/4"
RA/802040/M/125	40	125	1/4"
RA/802040/M/200	40	200	1/4"
RA/802040/M/250	40	250	1/4"
RA/802040/M/320	40	320	1/4"
RA/802050/M/25	50	25	1/4"
RA/802050/M/50	50	50	1/4"
RA/802050/M/80	50	80	1/4"
RA/802050/M/160	50	160	1/4"
RA/802050/M/200	50	200	1/4"
RA/802050/M/250	50	250	1/4"
RA/802063/M/25	63	25	3/8"
RA/802063/M/50	63	50	3/8"
RA/802063/M/100	63	100	3/8"
RA/802063/M/250	63	250	3/8"
RA/802063/M/320	63	320	3/8"
RA/802080/M/25	80	25	3/8"
RA/802080/M/50	80	50	3/8"
RA/802080/M/80	80	80	3/8"
RA/802080/M/100	80	100	3/8"
RA/802080/M/160	80	160	3/8"
RA/802080/M/200	80	200	3/8"

Tech Sheet 71751

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 15552 CYLINDERS & MOUNTINGS

NORGREN

ISO 15552 Mountings



Female Piston Rod Clevis

0036	Bore mm
QM/8025/25	25
QM/8050/25	50/63
QM/8080/25	80/100
Tech Sheet 10317	



Piston Rod Eye

0036	Bore mm
QM/8050/32	50/63
QM/8080/32	80/100
Tech Sheet 10317	



Foot Mounting

0036	Bore mm
QA/8032/21	32
QA/8050/21	50
QA/8063/21	63
QA/8080/21	80
QA/8100/21	100
Tech Sheet 10317	



Rear Swivel Flange

0036	Bore mm
QA/8032/23	32
QA/8040/23	40
QA/8050/23	50
QA/8063/23	63
QA/8080/23	80
QA/8100/23	100
Tech Sheet 10317	



Standard Service Kits

0036	Bore mm
QA/8032/00	32
QA/8040/00	40
QA/8050/00	50
QA/8063/00	63
QA/8100/00	100
Tech Sheet 10317	



Reed Switch

0036	Length Metre
M/50/LSU/2V	2
M/50/LSU/5V	5
M/50/LSU/10V	10
Tech Sheet 10317	

IMPERIAL CYLINDERS

NORGREN

Imperial Cylinders

- Large range of bore sizes – ideal for a wide variety of industrial applications
- Extensive choice of mountings
- Long established design – proven ruggedness and reliability
- Adjustable cushioning

Working Temperature: -5°C to +80°C

Working Pressure: 2 to 10 bar

Medium: Compressed air, filtered, lubricated or non-lubricated


Operation: Double acting, adjustable cushioning

Piston Rod and Tie Rods: Stainless steel (martensitic)

Barrel: Anodised aluminium

Piston and End Covers: Aluminium

Seals: Nitrile





Double Acting Imperial RM/900

0036	Bore Inch	Stroke mm	Thread
RM/925/75	2.1/2"	75	G3/8
RM/925/100	2.1/2"	100	G3/8
RM/925/150	2.1/2"	150	G3/8
RM/930/75	3"	75	G3/8
RM/930/100	3"	100	G3/8
RM/930/150	3"	150	G3/8
RM/930/300	3"	300	G3/8
RM/940/100	4"	100	G3/8
RM/940/150	4"	150	G3/8
RM/940/300	4"	300	G3/8
Tech Sheet 20131			

In-line Positioner Cylinders

Medium: Compressed air, filtered, non-lubricated.

Response time: 10 secs max. for 200mm stroke.

Working Temperature: -20°C to + 80°C

Working Pressure: 2 to 10 bar

Materials:

Piston Rod and Valve Spool: Stainless steel. Piston rod end and zero.

Adjuster: Zinc plated steel

Valve Bush: Brass cylinder barrel and piston.

Valve Body: Aluminium alloy



M/1525, M1540 - G1/4

0036	Bore Inch	Stroke mm
M/1525/75	2.1/2"	75
M/1525/125	2.1/2"	125
M/1525/200	2.1/2"	200
M/1540/75	4"	75
M/1540/125	4"	125
M/1540/200	4"	200
Tech Sheet 10360		

Fluid-Air Components Ltd

ISO 15552 CYLINDERS

Series 61, Double Acting Cylinders Aluminium Profile ISO 1555

- In compliance with ISO 15552 standards and with the previous DIN/ISO 6431 – VDMA 24562 standards.
- Rolled stainless steel rod
- Clean design with adjustable pneumatic cushioning
- Special designs available

Type of construction: with tie-rods (inside the profile)
Operation: double-acting, single-acting, tandem. Low friction version: double-acting only.
Materials: standard = aluminium end-blocks and piston, rolled stainless steel AISI 420B rod, anodised aluminium tube, zinc-plated steel tie-rods and tie-rod nuts, PU seals. Low friction = standard materials with NBR piston seal and NBR rod seal (FKM rod seal on request).
Type of mounting: with front rear flange, foot mounting, with front/rear/centre/ swivel trunnion.
Strokes, min – max: 10 to 2500mm.
Speed: 10 to 1000mm/sec, no load (standard versions). 5 to 1000mm/sec, no load (low friction version).

Fluid: filtered ai , without lubrication. For standard versions only: if lubricated air is used, it is recommended to use oil ISOVG32. Once applied the lubrication should never be interrupted.
Full range of ISO cylinders available including large bore (160, 200 and 250mm) and stainless steel options.
Non-stock strokes available on request.

Operating temperature:
0°C to +80°C (with dry air: +20°C).

Operating pressure:
1 to 10 bar (standard versions).
0.1 to 10 bar (low friction version).



G1/8", Ø32mm

0158	Stroke mm
61M2P032A0025	25
61M2P032A0050	50
61M2P032A0075	75
61M2P032A0080	80
61M2P032A0100	100
61M2P032A0125	125
61M2P032A0150	150
61M2P032A0160	160
61M2P032A0200	200
61M2P032A0250	250
61M2P032A0300	300
61M2P032A0320	320
61M2P032A0400	400
61M2P032A0500	500
61M2P032A0600	600
61M2P032A0700	700
61M2P032A0800	800
61M2P032A0900	900
61M2P032A1000	1000
Tech Sheet 1841	

G1/4", Ø40mm

0158	Stroke mm
61M2P040A0025	25
61M2P040A0050	50
61M2P040A0075	75
61M2P040A0080	80
61M2P040A0100	100
61M2P040A0125	125
61M2P040A0150	150
61M2P040A0160	160
61M2P040A0200	200
61M2P040A0250	250
61M2P040A0300	300
61M2P040A0320	320
61M2P040A0400	400
61M2P040A0500	500
61M2P040A0600	600
61M2P040A0700	700
61M2P040A0800	800
61M2P040A0900	900
61M2P040A1000	1000
Tech Sheet 1841	

G1/4", Ø50mm

0158	Stroke mm
61M2P050A0025	25
61M2P050A0050	50
61M2P050A0075	75
61M2P050A0080	80
61M2P050A0100	100
61M2P050A0125	125
61M2P050A0150	150
61M2P050A0160	160
61M2P050A0200	200
61M2P050A0250	250
61M2P050A0300	300
61M2P050A0320	320
61M2P050A0400	400
61M2P050A0500	500
61M2P050A0600	600
61M2P050A0800	800
61M2P050A0900	900
61M2P050A1000	1000
Tech Sheet 1841	

G3/8", Ø63mm

0158	Stroke mm
61M2P063A0025	25
61M2P063A0050	50
61M2P063A0075	75
61M2P063A0080	80
61M2P063A0100	100
61M2P063A0125	125
61M2P063A0150	150
61M2P063A0160	160
61M2P063A0200	200
61M2P063A0250	250
61M2P063A0300	300
61M2P063A0320	320
61M2P063A0400	400
61M2P063A0500	500
61M2P063A0600	600
61M2P063A0700	700
61M2P063A0800	800
61M2P063A0900	900
61M2P063A1000	1000
Tech Sheet 1841	

G3/8", Ø80mm

0158	Stroke mm
61M2P080A0025	25
61M2P080A0050	50
61M2P080A0075	75
61M2P080A0080	80
61M2P080A0100	100
61M2P080A0125	125
61M2P080A0150	150
61M2P080A0160	160
61M2P080A0200	200
61M2P080A0250	250
61M2P080A0300	300
61M2P080A0320	320
61M2P080A0500	500
61M2P080A0600	600
61M2P080A0700	700
61M2P080A0800	800
61M2P080A0900	900
61M2P080A1000	1000
Tech Sheet 1841	

G1/2", Ø100mm

0158	Stroke mm
61M2P100A0025	25
61M2P100A0050	50
61M2P100A0080	80
61M2P100A0100	100
61M2P100A0125	125
61M2P100A0150	150
61M2P100A0160	160
61M2P100A0200	200
61M2P100A0250	250
61M2P100A0300	300
61M2P100A0320	320
61M2P100A0400	400
61M2P100A0500	500
61M2P100A0600	600
61M2P100A0700	700
61M2P100A0800	800
61M2P100A0900	900
61M2P100A1000	1000
Tech Sheet 1841	

G1/2", Ø125mm

0158	Stroke mm
61M2P125A0025	25
61M2P125A0050	50
61M2P125A0075	75
61M2P125A0080	80
61M2P125A0100	100
61M2P125A0125	125
61M2P125A0150	150
61M2P125A0160	160
61M2P125A0200	200
61M2P125A0250	250
61M2P125A0300	300
61M2P125A0320	320
61M2P125A0400	400
61M2P125A0500	500
61M2P125A0600	600
61M2P125A0700	700
61M2P125A0800	800
61M2P125A0900	900
61M2P125A1000	1000
Tech Sheet 1841	

Fluid-Air Components Ltd

ISO 15552 CYLINDERS

Series 63, Double Acting Cylinders ISO 15552

Series 63 pneumatic cylinders comply with the ISO 1552 standard. They have been developed to guarantee high performance whilst also offering significant reduction in weight.

The new adjustable pneumatic and mechanical cushioning system ensures Series 63 also reduces the noise caused by the impact of the piston on the end block.

Type of construction: profile (with screws)

Operation: double-acting.

Materials: aluminium end blocks, technopolymer (nominal bore 32mm) or aluminium (nominal bore 40 to 125mm) piston, rolled stainless steel AISI 420B piston rod, zinc-plated steel piston rod nut, anodised aluminium tube, NBR-PU rod, piston and cushion seals.

Type of Mounting: with front/rear flange, foot mounting, with centre/front/rear/swivel trunnion.

Strokes, min – max: 10 to 2500mm.
Non-stock strokes available on request.

Speed: 10 to 500mm/sec, no load.

Fluid: filtered ai , in class 7.8.4, according to ISO 8573-1, without lubrication. If lubricated air is used, it is recommended to use oil ISOVG32. Once applied, the lubrication should never be interrupted.

Non-stock strokes available on request.

Operating temperature:
°C to +80°C (with dry air: -20°C).

Operating pressure:
1 to 10 bar.



G1/8", Ø32mm

0158	Stroke mm
63MP2C032A0025	25
63MP2C032A0050	50
63MP2C032A0075	75
63MP2C032A0080	80
63MP2C032A0100	100
63MP2C032A0125	125
63MP2C032A0150	150
63MP2C032A0160	160
63MP2C032A0200	200
63MP2C032A0250	250
63MP2C032A0300	300
63MP2C032A0320	320
63MP2C032A0400	400
63MP2C032A0500	500
63MP2C032A0600	600
63MP2C032A0700	700
63MP2C032A0800	800
63MP2C032A0900	900
Tech Sheet 68272	

G1/4", Ø40mm

0158	Stroke mm
63MP2C040A0025	25
63MP2C040A0050	50
63MP2C040A0075	75
63MP2C040A0080	80
63MP2C040A0100	100
63MP2C040A0125	125
63MP2C040A0150	150
63MP2C040A0160	160
63MP2C040A0200	200
63MP2C040A0250	250
63MP2C040A0300	300
63MP2C040A0320	320
63MP2C040A0400	400
63MP2C040A0500	500
63MP2C040A0600	600
63MP2C040A0700	700
63MP2C040A0800	800
63MP2C040A0900	900
Tech Sheet 68272	

G1/4", Ø50mm

0158	Stroke mm
63MP2C050A0025	25
63MP2C050A0050	50
63MP2C050A0075	75
63MP2C050A0080	80
63MP2C050A0100	100
63MP2C050A0125	125
63MP2C050A0150	150
63MP2C050A0160	160
63MP2C050A0200	200
63MP2C050A0250	250
63MP2C050A0300	300
63MP2C050A0320	320
63MP2C050A0400	400
63MP2C050A0500	500
63MP2C050A0600	600
63MP2C050A0700	700
63MP2C050A0800	800
63MP2C050A0900	900
Tech Sheet 68272	

G3/8", Ø63mm

0158	Stroke mm
63MP2C063A0025	25
63MP2C063A0050	50
63MP2C063A0075	75
63MP2C063A0080	80
63MP2C063A0100	100
63MP2C063A0125	125
63MP2C063A0150	150
63MP2C063A0160	160
63MP2C063A0200	200
63MP2C063A0250	250
63MP2C063A0300	300
63MP2C063A0320	320
63MP2C063A0400	400
63MP2C063A0500	500
63MP2C063A0600	600
63MP2C063A0700	700
63MP2C063A0800	800
63MP2C063A0900	900
Tech Sheet 68272	

G3/8", Ø80mm

0158	Stroke mm
63MP2C080A0025	25
63MP2C080A0050	50
63MP2C080A0075	75
63MP2C080A0080	80
63MP2C080A0100	100
63MP2C080A0125	125
63MP2C080A0150	150
63MP2C080A0160	160
63MP2C080A0200	200
63MP2C080A0250	250
63MP2C080A0300	300
63MP2C080A0320	320
63MP2C080A0400	400
63MP2C080A0500	500
63MP2C080A0600	600
63MP2C080A0700	700
63MP2C080A0800	800
63MP2C080A0900	900
63MP2C080A0985	985
Tech Sheet 68272	

G1/2", Ø100mm

0158	Stroke mm
63MP2C100A0025	25
63MP2C100A0050	50
63MP2C100A0075	75
63MP2C100A0080	80
63MP2C100A0100	100
63MP2C100A0125	125
63MP2C100A0150	150
63MP2C100A0160	160
63MP2C100A0200	200
63MP2C100A0250	250
63MP2C100A0300	300
63MP2C100A0320	320
63MP2C100A0400	400
63MP2C100A0500	500
63MP2C100A0600	600
63MP2C100A0700	700
63MP2C100A0800	800
63MP2C100A0900	900
Tech Sheet 68272	

G1/2", Ø125mm

0158	Stroke mm
63MP2C125A0025	25
63MP2C125A0050	50
63MP2C125A0075	75
63MP2C125A0080	80
63MP2C125A0100	100
63MP2C125A0125	125
63MP2C125A0150	150
63MP2C125A0160	160
63MP2C125A0200	200
63MP2C125A0250	250
63MP2C125A0300	300
63MP2C125A0320	320
63MP2C125A0400	400
63MP2C125A0500	500
63MP2C125A0600	600
63MP2C125A0700	700
63MP2C125A0800	800
63MP2C125A0900	900
Tech Sheet 68272	

Fluid-Air Components Ltd

ISO 15552 CYLINDERS

Series 40, Double Acting Cylinders ISO 15552

Series 40 cylinders have been designed in compliance with ISO 15552 standards and with previous DIN/ISO 6431-VDMA 24562 standards.

A permanent magnet on the piston of these cylinders is able to send, through proximity switches mounted on the cylinder sliding axis, electrical signals to indicate its position.

Type of construction: with tie-rods.

Operation: double-acting.

Materials: aluminium end blocks and piston, rolled stainless steel AISI 420B (nominal bore 160-200mm) piston rod, zinc-plated piston rod nut, anodised aluminium tube, zinc-plated steel tie-rods and tie-rod nuts, NBR-PU rod, piston and cushion seals, brass rod scraper.

Operating temperature:
0°C to +80°C (with dry air: -20°C).

Operating pressure:
1 to 10 bar.

Type of Mounting: with tie-rods, with front/rear flange, foot mounting, with centre/front rear/swivel trunnion.

Strokes, min – max: 10 to 2500mm.

Speed: 10 to 500mm/sec, no load.

Fluid: filtered air without lubrication. If lubricated air is used, it is recommended to use oil ISOVG32. Once applied, the lubrication should never be interrupted.

250 and 320mm bore cylinders are available upon request.



G3/4", Ø160mm

0158	Stroke mm
40M2L160A0050	50
40M2L160A0080	80
40M2L160A0100	100
40M2L160A0150	150
40M2L160A0200	200
40M2L160A0250	250
40M2L160A0300	300
40M2L160A0400	400
40M2L160A0500	500
40M2L160A0600	600
40M2L160A0700	700
40M2L160A0800	800
40M2L160A0900	900
40M2L160A1000	1000
40M2L160A1250	1250
40M2L160A1500	1500
40M2L160A1750	1750
40M2L160A2000	2000
Tech Sheet 68271	

G3/4", Ø200mm

0158	Stroke mm
40M2L200A0050	50
40M2L200A0080	80
40M2L200A0100	100
40M2L200A0150	150
40M2L200A0200	200
40M2L200A0250	250
40M2L200A0300	300
40M2L200A0400	400
40M2L200A0500	500
40M2L200A0600	600
40M2L200A0700	700
40M2L200A0800	800
40M2L200A0900	900
40M2L200A1000	1000
40M2L200A1250	1250
40M2L200A1500	1500
40M2L200A1750	1750
40M2L200A2000	2000
Tech Sheet 68271	

CAMOZZI
Automation



For **In-line Flow Control Valves**
see page **636**

Fluid-Air Components Ltd

ISO & VDMA CYLINDER MOUNTINGS

CAMOZZI Automation

Piston Rod Mountings



Piston Rod Swivel Ball Ends, Mod GA

0158	Bore mm	To Suit Unit
GA 8/10	8/10	24
GA 12/16	12/16	24
GA 20	20	24
GA 25/32	25/32	60,61,63
GA 40	40	60,61,63
GA 50/63	50/63	60,61,63
GA 80/100	80/100	60,61,63
GA 41 125	125	60,61,63
GA 160/200	160/200	40
Tech Sheet 1844		



Piston Rod Fork Ends, Mod G

0158	Bore mm	To Suit Unit
G 12/16	12/16	24
G 20	20	24
G 25/32	25/32	24,60,61,63
G 40	40	60,61,63
G 50/63	50/63	60,61,63
G 80/100	80/100	60,61,63
G 41 125	125	60,61,63
G 160/200	160/200	40
Tech Sheet 1844		



Self Aligning Rod, Mod GK

0158	Bore mm	To Suit Unit
GK 25 32	25/32	60,61,63
GK 40	40	60,61,63
GK 50 63	50/63	60,61,63
GK 80 100	80/100	60,61,63
GK 125	125	60,61,63
GK 160 200	160/200	40
Tech Sheet 1844		



Piston Rod Socket Joint, Mod GY

0158	Bore mm	To Suit Unit
GY 32	32	60,61,63
GY 40	40	60,61,63
GY 50 63	50/63	60,61,63
GY 80 100	80/100	60,61,63
Tech Sheet 1844		



Piston Rod Lock Nut, Mod U

0158	Bore mm	To Suit Unit
U 12/16	12/16	24
U 20	20	24
U 25/32	25/32	24,60,61,63
U 40	40	60,61,63
U 50/63	50/63	60,61,63
U 80/100	80/100	60,61,63
U 41 125	125	60,61,63
U 160/200	160/200	40
Tech Sheet 1844		

Foot Mountings



Foot Mountings (Pair), Mod B

0158	Bore mm	To Suit Unit
B 12/16	12/16	24
B 20/25	20/25	24
B 41 32	32	60,61,63
B 41 40	40	60,61,63
B 41 50	50	60,61,63
B 41 63	63	60,61,63
B 41 80	80	60,61,63
B 41 100	100	60,61,63
B 41 125	125	60,61,63
B 41 160	160	40
B 41 200	200	40
Tech Sheet 1844		

Flange Mountings



Front & Rear Flange Mounts, Mod E

0158	Bore mm	To Suit Unit
E 12/16	12/16	24
E 20/25	20/25	24
Tech Sheet 1844		

Front & Rear Flange Mounts, Mod D & E

0158	Bore mm	To Suit Unit
D E 41 32	32	60,61,63
D E 41 40	40	60,61,63
D E 41 50	50	60,61,63
D E 41 63	63	60,61,63
D E 41 80	80	60,61,63
D E 41 100	100	60,61,63
D E 41 125	125	60,61,63
D E 41 160	160	40
D E 41 200	200	40
Tech Sheet 1844		

Trunnion Mountings



Rear Male Trunnion Mounts, Mod L

0158	Bore mm	To Suit Unit
L 41 32	32	60,61,63
L 41 40	40	60,61,63
L 41 50	50	60,61,63
L 41 63	63	60,61,63
L 41 80	80	60,61,63
L 41 125	125	60,61,63
L 41 160	160	40
L 41 200	200	40
Tech Sheet 1844		



Rear Female Trunnion Mounts, Mod C & C H

0158	Bore mm	To Suit Unit
C 41 32	32	60,61,63
C 41 40	40	60,61,63
C 41 50	50	60,61,63
C 41 63	63	60,61,63
C H 41 80	80	60,61,63
C H 41 100	100	60,61,63
C H 41 125	125	60,61,63
C H 41 160	160	40
C H 41 200	200	40
Tech Sheet 1844		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO & VDMA CYLINDER MOUNTINGS

Trunnion Mountings

Rear Trunnion Ball Joint Mounts, Mod R



0158	Bore mm	To Suit Unit
R 41 32	32	60,61,63
R 41 40	40	60,61,63
R 41 50	50	60,61,63
R 41 63	63	60,61,63
R 41 80	80	60,61,63
R 41 100	100	60,61,63
R 41 125	125	60,61,63
Tech Sheet 1844		

Rear Trunnion Mounts, Mod I



0158	Bore mm	To Suit Unit
I 12/16	12/16	24
I 20/25	20/25	24
Tech Sheet 1844		

Rear 90° Male Trunnion Mounts, Mod ZC




0158	Bore mm	To Suit Unit
ZC 32	32	60,61,63
ZC 40	40	60,61,63
ZC 50	50	60,61,63
ZC 63	63	60,61,63
ZC 80	80	60,61,63
ZC 100	100	60,61,63
ZC 125	125	60,61,63
Tech Sheet 1844		

90° Swivel Combination Trunnion, Mod ZS



0158	Bore mm	To Suit Unit
ZS 160	160	40
ZS 200	200	40
Tech Sheet 1844		



Front Female Trunnion Mounts, Mod H & CH

0158	Bore mm	To Suit Unit
H 41 32	32	60,61,63
H 41 40	40	60,61,63
H 41 50	50	60,61,63
H 60 63	63	60,61,63
Tech Sheet 1844		



Centre Trunnion Mounts, Mod F

0158	Bore mm	To Suit Unit
F 32	32	60,61,63
F 40	40	60,61,63
F 50	50	60,61,63
F 63	63	60,61,63
F 80	80	60,61,63
F 100	100	60,61,63
F 125	125	60,61,63
F 160	160	40
F 200	200	40
Tech Sheet 1844		



61 Series Centre Trunnion Mounts, Mod F

0158	Bore mm
F 61 32	32
F 61 40	40
F 61 50	50
F 61 80	80
F 61 100	100
F 61 125	125
Tech Sheet 1844	



Centre Trunnion Counter Brackets, Mod BF

0158	Bore mm	To Suit Unit
BF 40 50	40/50	60,61,63
BF 63 80	63/80	60,61,63
BF 100 125	100/125	60,61,63
BF 160 200	160/200	40
Tech Sheet 1844		



Centre Trunnion for 63 Series Profile Cylinders, Mod F

0158	Bore mm	To Suit Unit
F 63 32	32	63
F 63 40	40	63
F 63 50	50	63
F 63 63	63	63
F 63 80	80	63
F 63 100	100	63
F 63 125	125	63
Tech Sheet 1844		



Clevis Pin, to suit C & CH Mountings

0158	Bore mm	To Suit Unit
S 32	32	60,61,63
S 40	40	60,61,63
S 50	50	60,61,63
S 63	63	60,61,63
S 80	80	60,61,63
S 100	100	60,61,63
S 125	125	60,61,63
S 160 200	160/200	40
Tech Sheet 1844		

Fluid-Air Components Ltd

ISO 15552 CYLINDERS

Double Action Pneumatic Profile Cylinders ISO 15552


The P1F, in bore sizes Ø32 to 125mm, is a smooth profile linear pneumatic cylinder conforming to the ISO 15552 standard. It utilises internal composite technology (piston) to save weight, while assuring the high performance and functionality expected of an ISO cylinder. With aluminium sandblasted front and rear end covers, multi-layer PTFE-coated steel bearing with stainless steel piston rod, pneumatic cushioning and magnetic piston with polyurethane (PUR) seals as standard, this is our industrial profile ISO cylinder.

Challenges encountered within rigorous environments require leading engineered solutions and products. Meeting these exacting needs, the P1F provides the answer for high and low temperature applications. It is engineered to provide superior performance in harsh conditions, using proven class-leading seal technology for reliable operation, and long service life in temperatures down to -40°C and up to +150°C. With robust corrosion-resistant body and optional metal scraper, the P1F leads the way in today's changing climate.

Applications:
- Factory automation
- Machine tools
- Packaging machinery
- Vehicle assembly facilities
- Material handling
- Outdoor
- Transport

Working Temperature:
-20 to +80 (Standard)

Maximum Working Pressure:
10 bar



ISO 15552

0678	Bore mm	Stroke mm	Thread	Piston Rod Thread Size
P1F-S032MS-0050	32	50	1/8"	M10 x 1.25
P1F-S032MS-0080	32	80	1/8"	M10 x 1.25
P1F-S032MS-0100	32	100	1/8"	M10 x 1.25
P1F-S032MS-0125	32	125	1/8"	M10 x 1.25
P1F-S032MS-0160	32	160	1/8"	M10 x 1.25
P1F-S040MS-0050	40	50	1/4"	M12 x 1.25
P1F-S040MS-0125	40	125	1/4"	M12 x 1.25
P1F-S050MS-0080	50	80	1/4"	M16 x 1.5
P1F-S050MS-0100	50	100	1/4"	M16 x 1.5
P1F-S063MS-0100	63	100	3/8"	M16 x 1.5
P1F-S063MS-0200	63	200	3/8"	M16 x 1.5
P1F-S063MS-0500	63	500	3/8"	M16 x 1.5
P1F-S080MS-0100	80	100	3/8"	M20 x 1.5
P1F-S080MS-0200	80	200	3/8"	M20 x 1.5
P1F-S100MS-0025	100	25	1/2"	M20 x 1.5
P1F-S100MS-0200	100	200	1/2"	M20 x 1.5
P1F-S125MS-0250	125	250	1/2"	M27 x 2
Tech Sheet 68754				



For **Parker LF 3000 Push-in Fittings**
see pages **793-799**

Fluid-Air Components Ltd

ISO VDMA CYLINDER ACCESSORIES

Parker VDMA Cylinders



ISO6431 VDMA Flange MF1/MF2

0678	Cylinder Dia mm
P1C-4KMB	32



ISO6431/VDMA Foot Bracket MS1

0678	Cylinder Dia mm
P1C-4LMF	40



ISO6431/VDMA Clevis Bracket GA

0678	Cylinder Dia mm
P1C-4KMCA	32



ISO6431/VDMA Clevis Bracket MP2

0678	Cylinder Dia mm
P1C-4LMT	40
P1C-4NMT	63



ISO6431 VDMA Rear Pivot Bracket with Rigid Bearing

0678	Cylinder Dia mm
P1C-4KMD	32



ISO6431/VDMA Clevis Bracket MP4

0678	Cylinder Dia mm
P1C-4KME	32
P1C-4LME	40
P1C-4NME	63



Reed Sensors & Mountings

0678	Description
P8S-GSFLX	Reed Switch c/w 3m PVC Cable
9126344341	3m Cable with 8mm Round Connector
9126344342	10m Cable with 8mm Round Connector



Solid State PNP Sensor & Cable

0678	Description
P8S-GPMHX	PNP Sensor c/w 0.27m Lead
P8S-GPFLX	PNP 3 Metre Flying Lead.



ISO6431 VDMA Cylinder Repair Kits

0678	Bore mm
P1D-6KRN	32
P1D-6LRN	40
P1D-6MRN	50
P1D-6NRN	63
P1D-6PRN	80
P1D-6RRN	125



ISO Cylinder Repair Kits

0678	Bore mm
32-2110AR	32
40-2110AR	40

Fluid-Air Components Ltd

ISO 15552 CYLINDERS

PNEUMAX

Cylinders series 1319 ISO5552 VDMA Ecolight

Working Temperature:
-5°C to +70°C
with standard seals

Maximum Pressure:
10 bar



Ecolight Cylinders ISO 15552 VDMA 32mm-50mm

0110	Bore mm	Stroke mm	Port Size
1391.32.50.01	32	50	1/8"
1391.32.100.01	32	100	1/8"
1391.32.125.01	32	125	1/8"
1391.32.150.01	32	150	1/8"
1391.32.200.01	32	200	1/8"
1391.32.250.01	32	250	1/8"
1391.32.300.01	32	300	1/8"
1391.32.350.01	32	350	1/8"
1391.32.450.01	32	450	1/8"
1391.32.500.01	32	500	1/8"
1391.40.50.01	40	50	1/4"
1391.40.100.01	40	100	1/4"
1391.40.150.01	40	150	1/4"
1391.40.200.01	40	200	1/4"
1391.40.250.01	40	250	1/4"
1391.40.300.01	40	300	1/4"
1391.40.350.01	40	350	1/4"
1391.40.400.01	40	400	1/4"
1391.40.500.01	40	500	1/4"
1391.40.600.01	40	600	1/4"
1391.50.25.01	50	25	1/4"
1391.50.50.01	50	50	1/4"
1391.50.75.01	50	75	1/4"
1391.50.100.01	50	100	1/4"
1391.50.125.01	50	125	1/4"
1391.50.150.01	50	150	1/4"
1391.50.200.01	50	200	1/4"
1391.50.250.01	50	250	1/4"
1391.50.300.01	50	300	1/4"
1391.50.350.01	50	350	1/4"
1391.50.400.01	50	400	1/4"
1391.50.500.01	50	500	1/4"
1391.50.1000.01	50	1000	1/4"

Ecolight Cylinders ISO 15552 VDMA 63mm-100mm

0110	Bore mm	Stroke mm	Port Size
1391.63.25.01	63	25	3/8"
1391.63.100.01	63	100	3/8"
1391.63.150.01	63	150	3/8"
1391.63.200.01	63	200	3/8"
1391.63.250.01	63	250	3/8"
1391.63.300.01	63	300	3/8"
1391.63.350.01	63	350	3/8"
1391.63.450.01	63	450	3/8"
1391.80.200.01	80	200	3/8"
1391.80.250.01	80	250	3/8"
1391.80.300.01	80	300	3/8"
1391.80.500.01	80	500	3/8"
1391.80.1000.01	80	1000	3/8"
1391.100.25.01	100	25	1/2"
1391.100.50.01	100	50	1/2"
1391.100.75.01	100	75	1/2"
1391.100.125.01	100	125	1/2"
1391.100.150.01	100	150	1/2"
1391.100.200.01	100	200	1/2"
1391.100.250.01	100	250	1/2"
1391.100.300.01	100	300	1/2"
1391.100.350.01	100	350	1/2"
1391.100.400.01	100	400	1/2"
1391.100.450.01	100	450	1/2"
1391.100.500.01	100	500	1/2"
1391.100.600.01	100	600	1/2"
1391.100.800.01	100	800	1/2"


Ecolight Cylinders ISO 15552 VDMA 125mm-200mm

0110	Bore mm	Stroke mm	Port Size
1391.125.300.01	125	300	1/2"
1391.160.700.01	160	700	3/4"

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO VDMA CYLINDER ACCESSORIES

VDMA Cylinder Mountings



Front & Rear Flanges - Aluminium

0110	Bore mm
1390.63.03F	63
1390.80.03F	80
1390.100.03F	100



Foot Brackets - Steel

0110	Bore mm
1320.40.05/1F	40



Front Cylinder Clevis - Aluminium

0110	Bore mm
1380.50.08F	50
1380.63.08F	63
1380.100.08F	100



Rear Clevis MP2 - Aluminium

0110	Bore mm
1380.32.09F	32
1380.40.09F	40
1380.50.09F	50
1380.63.09F	63
1380.80.09F	80
1380.100.09F	100



Rear Clevis MP4 - Aluminium

0110	Bore mm
1380.40.09/1F	40
1380.50.09/1F	50
1380.63.09/1F	63
1380.100.09/1F	100



Simple Rear Trunnion complete with Support (Not ISO) - Aluminium

0110	Bore mm
1380.40.11F	40
1380.50.11F	50
1380.63.11F	63
1380.100.11F	100



Square Angle Trunnion - Aluminium

0110	Bore mm
1380.32.35F	32
1380.63.35F	63
1380.80.35F	80
1380.100.35F	100



Standard Trunnion (not ISO) - Aluminium

0110	Bore mm
1380.32.10F	32



Rear Narrow Clevis - Aluminium

0110	Bore mm
1380.80.30F	80



Rear Male Clevis complete with Jointed Head - Aluminium

0110	Bore mm
1380.32.15F	32
1380.40.15F	40
1380.50.15F	50
1380.80.15F	80



Rod Clevis complete with Pin - Steel

0110	Bore mm
1320.40.13F	40
1320.50.13F	50
1320.80.13F	80
1320.100.13F	100



Rod Clevis complete with Clip - Steel

0110	Bore mm
1320.32.13/1F	32
1320.40.13/1F	40
1320.50.13/1F	50
1320.63.13/1F	63
1320.80.13/1F	80
1320.100.13/1F	100



Rod Lock Nuts

0110	Bore mm
1320.32.18F	32



Ball Joint

0110	Bore mm
1320.32.32F	32
1320.40.32F	40
1320.50.32F	50
1320.63.32F	63



Self Aligning Joint

0110	Bore mm
1320.32.33F	32
1320.40.33F	40



1580U Reed Switch complete with LED

0110	Description
1580U	LED Reed Switch N/O



1500U Reed Switch complete with LED

0110	Description
1500.U	LED Reed Switch N/O



1500U Sensor Clamp

0110	Bore mm
1390.A	32 & 40


Fluid-Air Components Ltd

PNEUMATIC COMPACT MAGNETIC CYLINDERS

Accessories & Mounting Selector

stainless steel

FT PRO



Cylinders	Mountings	Reed Switches
Pages 518-519	Pages 520	Page 520

Compact Cylinders

CB	Rear clevis mounting
FA/FB	Front and rear flange mounting
LB	Foot mounting (pair)
Reed Switches	Two wire N/O with LED


FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c


Technical Information

Dimensions

Ø12 and Ø16




Ø20 and Ø25




Model Item/ Bore	With Magnet A	C	B1	D	E	K1	M	N1 Without Magnet	N1 With Magnet	N2 Without Magnet	N2 With Magnet	O	P1	P3	P4	S	T1	T2	V	W
12	31.5	28	3.5	–	6	M3 x 0.5	3.5	7.5	9	5	7	M5 x 0.8	2 sides: Ø6.5 Thread: M4 x 0.7	11	3.5	25	15.5	22	6	5
16	34	30.5	3.5	–	8	M4 x 0.7	3	8	9.5	5.5			Through hole: Ø3.4	11	3.5	29	20	28	8	6
20	36	31.5	4.5	–	7	M5 x 0.8	4	9	9.5	5.5		M5 x 0.8	2 sides: Ø9 Thread: M6 x 1.0	17	7	36	25.5	36	10	8
25	37.5	32.5	5	25	12	M6 x 1.0	4.5	11		5.5			Through hole: Ø5.2	17	7	40	28	40	12	10

Dimensions

Ø32 and Ø100 (stroke ≤100)



Inner Structure



Model Item/Bore		With Magnet A	C	B1	D	E	K1	M	N1 Without Magnet	N1 With Magnet	N2 Without Magnet	N2 With Magnet
32	St.=5	40	33	7	49.5	13	M8 x 1.25	6	7.5	10.5	6.5	7.5
	St.>5								10.5		7.5	
40		46.5	39.5	7	57	13	M8 x 1.25	6	11		8	
50	St.=5	48.5	40.5	8	71	15	M10 x 1.5	6.5	9	10.5	9	10.5
	St.>5								10.5		10.5	
63	St.=5	54	46	8	84	15	M10 x 1.5	6.5	14	15	9.5	10.5
	St.>5								15		10.5	
80		63.5	53.5	10	104	20	M16 x 2.0	8.5	16		14	
100		75	63	12	123.5	26	M20 x 2.5	9.5	20		17.5	

Item/Bore	O	P1	P3	P4	S	T1	T2	V	W
32	1/8"	2 sides: Ø9 Thread: M6 x 1.0 Through hole: Ø5.2	17	7	45	34	–	16	14
40	1/8"	2 sides: Ø9 Thread: M6 x 1.0 Through hole: Ø5.2	17	7	53	40	–	16	14
50	1/4"	2 sides: Ø11 Thread: M8 x 1.25 Through hole: Ø6.5	22	8	64	50	–	20	17
63	1/4"	2 sides: Ø14 Thread: M10 x 1.5 Through hole: Ø8.7	28.5	10.5	77	60	–	20	17
80	3/8"	2 sides: Ø17.5 Thread: M12 x 1.75 Through hole: Ø10.7	35.5	13.5	98	77	–	25	22
100	3/8"	2 sides: Ø17.5 Thread: M12 x 1.75 Through hole: Ø10.7	35.5	13.5	117	94	–	32	27

No.	Bore/Item	Material 12 & 16	20	25	32	10-100
1	Back cover	–	Aluminium Alloy			
2	Bumper	TPU			NBR	
3	Piston	Brass	Aluminium Alloy			
4	Wear ring	–			Wear-resistant material	
5	Piston O-ring	NBR				
6	Piston Rod	Carbon steel with 20µm chrome plated				
7	Body	Aluminium alloy				
8	Bushing	–			Wear-resistant material	
9	Cover Gasket	NBR				
10	Front Cover	Brass		Aluminium alloy		
11	C clip	Spring steel				
12	Front cover packing	NBR				
13	Magnet	Sintered metal (neodymium-iron-boron)			Plastic	
14	Magnet holder	Brass	Aluminium Alloy			

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PNEUMATIC CYLINDERS


Compact Magnetic Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated cushioning-buffer.
Body: Aluminium
Seals: Nitrile

2 Year Warranty

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar



See page 520 for Compact Cylinder Standard and Viton Seal Kits

Double Acting

0334	Bore mm	Stroke mm	Thread	Piston Rod Thread
KKS-12X5	12	5	M5 x 0.8	M3 x 0.5
KKS-12X10	12	10	M5 x 0.8	M3 x 0.5
KKS-12X20	12	20	M5 x 0.8	M3 x 0.5
KKS-12X25	12	25	M5 x 0.8	M3 x 0.5
KKS-12X30	12	30	M5 x 0.8	M3 x 0.5
KKS-12X40	12	40	M5 x 0.8	M3 x 0.5
KKS-12X50	12	50	M5 x 0.8	M3 x 0.5
KKS-16X5	16	5	M5 x 0.8	M4 x 0.7
KKS-16X10	16	10	M5 x 0.8	M4 x 0.7
KKS-16X15	16	15	M5 x 0.8	M4 x 0.7
KKS-16X25	16	25	M5 x 0.8	M4 x 0.7
KKS-16X30	16	30	M5 x 0.8	M4 x 0.7
KKS-16X35	16	35	M5 x 0.8	M4 x 0.7
KKS-16X50	16	50	M5 x 0.8	M4 x 0.7
KKS-16X55	16	55	M5 x 0.8	M4 x 0.7
KKS-16X60	16	60	M5 x 0.8	M4 x 0.7
KKS-20X5	20	5	M5 x 0.8	M5 x 0.8
KKS-20X10	20	10	M5 x 0.8	M5 x 0.8
KKS-20X15	20	15	M5 x 0.8	M5 x 0.8
KKS-20X20	20	20	M5 x 0.8	M5 x 0.8
KKS-20X25	20	25	M5 x 0.8	M5 x 0.8
KKS-20X30	20	30	M5 x 0.8	M5 x 0.8
KKS-20X40	20	40	M5 x 0.8	M5 x 0.8
KKS-20X45	20	45	M5 x 0.8	M5 x 0.8
KKS-20X50	20	50	M5 x 0.8	M5 x 0.8
KKS-20X70	20	70	M5 x 0.8	M5 x 0.8
KKS-20X80	20	80	M5 x 0.8	M5 x 0.8
KKS-20X90	20	90	M5 x 0.8	M5 x 0.8
KKS-20X100	20	100	M5 x 0.8	M5 x 0.8
KKS-25X5	25	5	M5 x 0.8	M6 x 1
KKS-25X10	25	10	M5 x 0.8	M6 x 1
KKS-25X15	25	15	M5 x 0.8	M6 x 1
KKS-25X20	25	20	M5 x 0.8	M6 x 1
KKS-25X25	25	25	M5 x 0.8	M6 x 1
KKS-25X30	25	30	M5 x 0.8	M6 x 1
KKS-25X35	25	35	M5 x 0.8	M6 x 1
KKS-25X40	25	40	M5 x 0.8	M6 x 1
KKS-25X45	25	45	M5 x 0.8	M6 x 1
KKS-25X50	25	50	M5 x 0.8	M6 x 1
KKS-25X60	25	60	M5 x 0.8	M6 x 1
KKS-25X70	25	70	M5 x 0.8	M6 x 1
KKS-25X75	25	75	M5 x 0.8	M6 x 1
KKS-25X80	25	80	M5 x 0.8	M6 x 1
KKS-25X90	25	90	M5 x 0.8	M6 x 1
KKS-25X100	25	100	M5 x 0.8	M6 x 1

0334	Bore mm	Stroke mm	Thread	Piston Rod Thread
KKS-32X5	32	5	1/8"	M8 x 1.25
KKS-32X10	32	10	1/8"	M8 x 1.25
KKS-32X15	32	15	1/8"	M8 x 1.25
KKS-32X20	32	20	1/8"	M8 x 1.25
KKS-32X25	32	25	1/8"	M8 x 1.25
KKS-32X30	32	30	1/8"	M8 x 1.25
KKS-32X35	32	35	1/8"	M8 x 1.25
KKS-32X40	32	40	1/8"	M8 x 1.25
KKS-32X45	32	45	1/8"	M8 x 1.25
KKS-32X50	32	50	1/8"	M8 x 1.25
KKS-32X60	32	60	1/8"	M8 x 1.25
KKS-32X70	32	70	1/8"	M8 x 1.25
KKS-32X75	32	75	1/8"	M8 x 1.25
KKS-32X80	32	80	1/8"	M8 x 1.25
KKS-32X100	32	100	1/8"	M8 x 1.25
KKS-32X125	32	125	1/8"	M8 x 1.25
KKS-32X150	32	150	1/8"	M8 x 1.25
KKS-40X5	40	5	1/8"	M8 x 1.25
KKS-40X10	40	10	1/8"	M8 x 1.25
KKS-40X15	40	15	1/8"	M8 x 1.25
KKS-40X20	40	20	1/8"	M8 x 1.25
KKS-40X25	40	25	1/8"	M8 x 1.25
KKS-40X30	40	30	1/8"	M8 x 1.25
KKS-40X35	40	35	1/8"	M8 x 1.25
KKS-40X40	40	40	1/8"	M8 x 1.25
KKS-40X45	40	45	1/8"	M8 x 1.25
KKS-40X50	40	50	1/8"	M8 x 1.25
KKS-40X60	40	60	1/8"	M8 x 1.25
KKS-40X75	40	75	1/8"	M8 x 1.25
KKS-40X100	40	100	1/8"	M8 x 1.25
KKS-40X125	40	125	1/8"	M8 x 1.25
KKS-50X10	50	10	1/4"	M10 x 1.5
KKS-50X15	50	15	1/4"	M10 x 1.5
KKS-50X20	50	20	1/4"	M10 x 1.5
KKS-50X25	50	25	1/4"	M10 x 1.5
KKS-50X30	50	30	1/4"	M10 x 1.5
KKS-50X40	50	40	1/4"	M10 x 1.5
KKS-50X45	50	45	1/4"	M10 x 1.5
KKS-50X50	50	50	1/4"	M10 x 1.5
KKS-50X60	50	60	1/4"	M10 x 1.5
KKS-50X70	50	70	1/4"	M10 x 1.5
KKS-50X75	50	75	1/4"	M10 x 1.5
KKS-50X80	50	80	1/4"	M10 x 1.5
KKS-50X90	50	90	1/4"	M10 x 1.5
KKS-50X100	50	100	1/4"	M10 x 1.5

Tech Sheet 3027

Further sizes in this range continued on next page

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Compact Magnetic Cylinders

Medium:
Clean compressed air. Filtered (40µm) and lubricated cushioning-buffer.
Body: Aluminium
Seals: Nitrile


2 Year Warranty

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar



See page 520 for Compact Cylinder Standard and Viton Seal Kits



Double Acting

0334	Bore mm	Stroke mm	Thread	Piston Rod Thread
KKS-50X125	50	125	1/4"	M10 x 1.5
KKS-50X150	50	150	1/4"	M10 x 1.5
KKS-50X250	50	250	1/4"	M10 x 1.5
KKS-63X5	63	5	1/4"	M10 x 1.5
KKS-63X15	63	15	1/4"	M10 x 1.5
KKS-63X20	63	20	1/4"	M10 x 1.5
KKS-63X25	63	25	1/4"	M10 x 1.5
KKS-63X30	63	30	1/4"	M10 x 1.5
KKS-63X35	63	35	1/4"	M10 x 1.5
KKS-63X50	63	50	1/4"	M10 x 1.5
KKS-63X60	63	60	1/4"	M10 x 1.5
KKS-63X75	63	75	1/4"	M10 x 1.5
KKS-63X80	63	80	1/4"	M10 x 1.5
KKS-63X100	63	100	1/4"	M10 x 1.5
KKS-63X125	63	125	1/4"	M10 x 1.5
KKS-63X150	63	150	1/4"	M10 x 1.5
KKS-63X250	63	250	1/4"	M10 x 1.5
KKS-80X5	80	5	3/8"	M16 x 2
KKS-80X10	80	10	3/8"	M16 x 2
KKS-80X15	80	15	3/8"	M16 x 2
KKS-80X20	80	20	3/8"	M16 x 2
KKS-80X25	80	25	3/8"	M16 x 2
KKS-80X30	80	30	3/8"	M16 x 2
KKS-80X35	80	35	3/8"	M16 x 2
KKS-80X40	80	40	3/8"	M16 x 2
KKS-80X45	80	45	3/8"	M16 x 2
KKS-80X50	80	50	3/8"	M16 x 2
KKS-80X60	80	60	3/8"	M16 x 2
KKS-80X70	80	70	3/8"	M16 x 2
KKS-80X75	80	75	3/8"	M16 x 2

0334	Bore mm	Stroke mm	Thread	Piston Rod Thread
KKS-80X80	80	80	3/8"	M16 x 2
KKS-80X90	80	90	3/8"	M16 x 2
KKS-80X100	80	100	3/8"	M16 x 2
KKS-80X125	80	125	3/8"	M16 x 2
KKS-80X150	80	150	3/8"	M16 x 2
KKS-80X175	80	175	3/8"	M16 x 2
KKS-80X200	80	200	3/8"	M16 x 2
KKS-80X250	80	250	3/8"	M16 x 2
KKS-100X5	100	5	3/8"	M20 x 2.5
KKS-100X10	100	10	3/8"	M20 x 2.5
KKS-100X15	100	15	3/8"	M20 x 2.5
KKS-100X20	100	20	3/8"	M20 x 2.5
KKS-100X25	100	25	3/8"	M20 x 2.5
KKS-100X30	100	30	3/8"	M20 x 2.5
KKS-100X35	100	35	3/8"	M20 x 2.5
KKS-100X40	100	40	3/8"	M20 x 2.5
KKS-100X45	100	45	3/8"	M20 x 2.5
KKS-100X50	100	50	3/8"	M20 x 2.5
KKS-100X60	100	60	3/8"	M20 x 2.5
KKS-100X70	100	70	3/8"	M20 x 2.5
KKS-100X75	100	75	3/8"	M20 x 2.5
KKS-100X80	100	80	3/8"	M20 x 2.5
KKS-100X90	100	90	3/8"	M20 x 2.5
KKS-100X100	100	100	3/8"	M20 x 2.5
KKS-100X125	100	125	3/8"	M20 x 2.5
KKS-100X150	100	150	3/8"	M20 x 2.5
KKS-100X175	100	175	3/8"	M20 x 2.5
KKS-100X200	100	200	3/8"	M20 x 2.5
KKS-100X250	100	250	3/8"	M20 x 2.5
Tech Sheet 3027				

Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

Compact Cylinder Mountings



Rear Clevis Mounting CB

0334	Bore mm
KSS-20-CB	20
KSS-32-CB	32
KSS-40-CB	40
KSS-50-CB	50
KSS-63-CB	63
KSS-80-CB	80
Tech Sheet 3028	



Front/Rear Flange Mounting FA/FB

0334	Bore mm
KSS-12-FAFB	12
KSS-16-FAFB	16
KSS-20-FAFB	20
KSS-25-FAFB	25
KSS-32-FAFB	32
KSS-40-FAFB	40
KSS-50-FAFB	50
KSS-63-FAFB	63
KSS-80-FAFB	80
Tech Sheet 3029	



Foot Mountings LB (Pair)

0334	Bore mm	To Suit Stroke
KSS-12-LB	12	All
KSS-20-LB	20	>15
KSS-25-LB	25	>10
KSS-32-LB	32	>10
KSS-40-LB	40	All
KSS-50-LB	50	>15
KSS-63-LB	63	>10
KSS-100-LB	100	>15
Tech Sheet 3030		

Foot Mountings LBS (Pair) Short Stroke

0334	Bore mm	To Suit Stroke
KSS-20-LBS-P1	20	<10
KSS-25-LBS-P1	25	<5
KSS-50-LBS-P1	50	<10
Tech Sheet 3030		

Reed Switches to suit Compact Cylinders



Two Wire, N/O with LED 2 Metres

0334	Bore mm	Voltage
KSS1-G	32-100	5-240V AC/DC
Tech Sheet 3031		

Repair Kits to suit Compact Cylinders



Standard

0334	Bore mm
KKSRK-12	12
KKSRK-16	16
KKSRK-20	20
KKSRK-25	25
KKSRK-32	32
KKSRK-40	40
KKSRK-50	50
KKSRK-63	63
KKSRK-80	80
Tech Sheet 20388	

Viton

0334	Bore mm
KKSRK-12-V	12
KKSRK-20-V	20
KKSRK-50-V	50
Tech Sheet 20389	

Fluid-Air Components Ltd


Save space, increase productivity

FESTO

Pneumatic components are often the preferred option for machines since they have a high power density. Smaller components are ever more popular because they are easy to use, save energy and help to boost productivity too.

Benefits of compact products

- Lower energy consumption
- Less material used
  → smaller CO_2 footprint
- More space for other movements
  → increased productivity
- Less mass means higher speed
  → increased productivity
- Less expensive m² per machine



521


Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CYLINDERS

For the full range and more information, please contact one of our sales team.

ADN COMPACT CYLINDER ISO 21287
(Male & Female Piston Rod)

Features



Product Description

ADN - 25 - 25 - A - P - A

- ADN — Cylinder Type
- 25 — Bore Size mm
- 25 — Stroke Size mm
- A — A - Male Piston Rod, I - Female Piston Rod
- P — Polymer Cushioning
- A — Magnetic

Fluid-Air Components Ltd

ISO 21287 COMPACT CYLINDERS, ADN


FESTO

Double Acting, Elastic Cushioning Rings

- Compact cylinders with standard dimensions
- Comply with the standard ISO 21287
- Innovative technology for maximum speeds
- Flexible in use thanks to easy-to-configure variant
- T-Slot

Ambient Temperature:
-20°C to +80°C

Elastic Cushioning







Magnetic Male Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
536204	12	5	M5	ADN-12-5-A-P-A
536205	12	10	M5	ADN-12-10-A-P-A
536206	12	15	M5	ADN-12-15-A-P-A
536207	12	20	M5	ADN-12-20-A-P-A
536208	12	25	M5	ADN-12-25-A-P-A
536209	12	30	M5	ADN-12-30-A-P-A
536210	12	40	M5	ADN-12-40-A-P-A
536219	16	5	M5	ADN-16-5-A-P-A
536220	16	10	M5	ADN-16-10-A-P-A
536221	16	15	M5	ADN-16-15-A-P-A
536222	16	20	M5	ADN-16-20-A-P-A
536223	16	25	M5	ADN-16-25-A-P-A
536224	16	30	M5	ADN-16-30-A-P-A
536225	16	40	M5	ADN-16-40-A-P-A
536331	16	50	M5	ADN-16-50-A-P-A
536234	20	5	M8	ADN-20-5-A-P-A
536235	20	10	M8	ADN-20-10-A-P-A
536236	20	15	M8	ADN-20-15-A-P-A
536237	20	20	M8	ADN-20-20-A-P-A
536238	20	25	M8	ADN-20-25-A-P-A
536239	20	30	M8	ADN-20-30-A-P-A
536240	20	40	M8	ADN-20-40-A-P-A
536241	20	50	M8	ADN-20-50-A-P-A
536352	20	60	M8	ADN-20-60-A-P-A
536251	25	5	M8	ADN-25-5-A-P-A
536252	25	10	M8	ADN-25-10-A-P-A
536253	25	15	M8	ADN-25-15-A-P-A
536254	25	20	M8	ADN-25-20-A-P-A
536255	25	25	M8	ADN-25-25-A-P-A
536256	25	30	M8	ADN-25-30-A-P-A
536257	25	40	M8	ADN-25-40-A-P-A
536258	25	50	M8	ADN-25-50-A-P-A
536373	25	60	M8	ADN-25-60-A-P-A
Tech Sheet 20563				

Magnetic Female Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
536211	12	5	M3	ADN-12-5-I-P-A
536212	12	10	M3	ADN-12-10-I-P-A
536213	12	15	M3	ADN-12-15-I-P-A
536214	12	20	M3	ADN-12-20-I-P-A
536215	12	25	M3	ADN-12-25-I-P-A
536216	12	30	M3	ADN-12-30-I-P-A
536217	12	40	M3	ADN-12-40-I-P-A
536226	16	5	M4	ADN-16-5-I-P-A
536227	16	10	M4	ADN-16-10-I-P-A
536228	16	15	M4	ADN-16-15-I-P-A
536229	16	20	M4	ADN-16-20-I-P-A
536230	16	25	M4	ADN-16-25-I-P-A
536231	16	30	M4	ADN-16-30-I-P-A
536232	16	40	M4	ADN-16-40-I-P-A
536341	16	50	M4	ADN-16-50-I-P-A
536242	20	5	M6	ADN-20-5-I-P-A
536243	20	10	M6	ADN-20-10-I-P-A
536244	20	15	M6	ADN-20-15-I-P-A
536245	20	20	M6	ADN-20-20-I-P-A
536246	20	25	M6	ADN-20-25-I-P-A
536247	20	30	M6	ADN-20-30-I-P-A
536248	20	40	M6	ADN-20-40-I-P-A
536249	20	50	M6	ADN-20-50-I-P-A
536362	20	60	M6	ADN-20-60-I-P-A
536259	25	5	M6	ADN-25-5-I-P-A
536260	25	10	M6	ADN-25-10-I-P-A
536261	25	15	M6	ADN-25-15-I-P-A
536262	25	20	M6	ADN-25-20-I-P-A
536263	25	25	M6	ADN-25-25-I-P-A
536264	25	30	M6	ADN-25-30-I-P-A
536265	25	40	M6	ADN-25-40-I-P-A
536266	25	50	M6	ADN-25-50-I-P-A
536383	25	60	M6	ADN-25-60-I-P-A
Tech Sheet 20562				

FAC
Fluid-Air Components Ltd

ISO 21287 COMPACT CYLINDERS, ADN


FESTO

Double Acting, Elastic Cushioning Rings

- Compact cylinders with standard dimensions
- Comply with the standard ISO 21287
- Innovative technology for maximum speeds
- Flexible in use thanks to easy-to-configure variant
- T-Slot

Ambient Temperature:
-20°C to +80°C

Elastic Cushioning





Magnetic Male Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
536268	32	5	M10 x 1.25	ADN-32-5-A-P-A
536269	32	10	M10 x 1.25	ADN-32-10-A-P-A
536270	32	15	M10 x 1.25	ADN-32-15-A-P-A
536271	32	20	M10 x 1.25	ADN-32-20-A-P-A
536272	32	25	M10 x 1.25	ADN-32-25-A-P-A
536273	32	30	M10 x 1.25	ADN-32-30-A-P-A
536274	32	40	M10 x 1.25	ADN-32-40-A-P-A
536275	32	50	M10 x 1.25	ADN-32-50-A-P-A
536276	32	60	M10 x 1.25	ADN-32-60-A-P-A
536277	32	80	M10 x 1.25	ADN-32-80-A-P-A
536289	40	5	M10 x 1.25	ADN-40-5-A-P-A
536290	40	10	M10 x 1.25	ADN-40-10-A-P-A
536291	40	15	M10 x 1.25	ADN-40-15-A-P-A
536292	40	20	M10 x 1.25	ADN-40-20-A-P-A
536293	40	25	M10 x 1.25	ADN-40-25-A-P-A
536294	40	30	M10 x 1.25	ADN-40-30-A-P-A
536295	40	40	M10 x 1.25	ADN-40-40-A-P-A
536296	40	50	M10 x 1.25	ADN-40-50-A-P-A
536297	40	60	M10 x 1.25	ADN-40-60-A-P-A
536298	40	80	M10 x 1.25	ADN-40-80-A-P-A
536310	50	5	M12 x 1.25	ADN-50-5-A-P-A
536311	50	10	M12 x 1.25	ADN-50-10-A-P-A
536312	50	15	M12 x 1.25	ADN-50-15-A-P-A
536313	50	20	M12 x 1.25	ADN-50-20-A-P-A
536314	50	25	M12 x 1.25	ADN-50-25-A-P-A
536315	50	30	M12 x 1.25	ADN-50-30-A-P-A
536316	50	40	M12 x 1.25	ADN-50-40-A-P-A
536317	50	50	M12 x 1.25	ADN-50-50-A-P-A
536318	50	60	M12 x 1.25	ADN-50-60-A-P-A
536319	50	80	M12 x 1.25	ADN-50-80-A-P-A
536332	63	10	M12 x 1.25	ADN-63-10-A-P-A
536333	63	15	M12 x 1.25	ADN-63-15-A-P-A
536334	63	20	M12 x 1.25	ADN-63-20-A-P-A
536335	63	25	M12 x 1.25	ADN-63-25-A-P-A
536336	63	30	M12 x 1.25	ADN-63-30-A-P-A
536337	63	40	M12 x 1.25	ADN-63-40-A-P-A
536338	63	50	M12 x 1.25	ADN-63-50-A-P-A
536339	63	60	M12 x 1.25	ADN-63-60-A-P-A
536340	63	80	M12 x 1.25	ADN-63-80-A-P-A
536353	80	10	M16 x 1.5	ADN-80-10-A-P-A
536354	80	15	M16 x 1.5	ADN-80-15-A-P-A
536355	80	20	M16 x 1.5	ADN-80-20-A-P-A
536356	80	25	M16 x 1.5	ADN-80-25-A-P-A
536357	80	30	M16 x 1.5	ADN-80-30-A-P-A
536358	80	40	M16 x 1.5	ADN-80-40-A-P-A
536359	80	50	M16 x 1.5	ADN-80-50-A-P-A
536360	80	60	M16 x 1.5	ADN-80-60-A-P-A
536361	80	80	M16 x 1.5	ADN-80-80-A-P-A

Tech Sheet 71595

Magnetic Female Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
536278	32	5	M8	ADN-32-5-I-P-A
536279	32	10	M8	ADN-32-10-I-P-A
536280	32	15	M8	ADN-32-15-I-P-A
536281	32	20	M8	ADN-32-20-I-P-A
536282	32	25	M8	ADN-32-25-I-P-A
536283	32	30	M8	ADN-32-30-I-P-A
536284	32	40	M8	ADN-32-40-I-P-A
536285	32	50	M8	ADN-32-50-I-P-A
536286	32	60	M8	ADN-32-60-I-P-A
536287	32	80	M8	ADN-32-80-I-P-A
536299	40	5	M8	ADN-40-5-I-P-A
536300	40	10	M8	ADN-40-10-I-P-A
536301	40	15	M8	ADN-40-15-I-P-A
536302	40	20	M8	ADN-40-20-I-P-A
536303	40	25	M8	ADN-40-25-I-P-A
536304	40	30	M8	ADN-40-30-I-P-A
536305	40	40	M8	ADN-40-40-I-P-A
536306	40	50	M8	ADN-40-50-I-P-A
536307	40	60	M8	ADN-40-60-I-P-A
536308	40	80	M8	ADN-40-80-I-P-A
536320	50	5	M10	ADN-50-5-I-P-A
536321	50	10	M10	ADN-50-10-I-P-A
536322	50	15	M10	ADN-50-15-I-P-A
536323	50	20	M10	ADN-50-20-I-P-A
536324	50	25	M10	ADN-50-25-I-P-A
536325	50	30	M10	ADN-50-30-I-P-A
536326	50	40	M10	ADN-50-40-I-P-A
536327	50	50	M10	ADN-50-50-I-P-A
536328	50	60	M10	ADN-50-60-I-P-A
536329	50	80	M10	ADN-50-80-I-P-A
536342	63	10	M10	ADN-63-10-I-P-A
536343	63	15	M10	ADN-63-15-I-P-A
536344	63	20	M10	ADN-63-20-I-P-A
536345	63	25	M10	ADN-63-25-I-P-A
536346	63	30	M10	ADN-63-30-I-P-A
536347	63	40	M10	ADN-63-40-I-P-A
536348	63	50	M10	ADN-63-50-I-P-A
536349	63	60	M10	ADN-63-60-I-P-A
536350	63	80	M10	ADN-63-80-I-P-A
536363	80	10	M12	ADN-80-10-I-P-A
536364	80	15	M12	ADN-80-15-I-P-A
536365	80	20	M12	ADN-80-20-I-P-A
536366	80	25	M12	ADN-80-25-I-P-A
536367	80	30	M12	ADN-80-30-I-P-A
536368	80	40	M12	ADN-80-40-I-P-A
536369	80	50	M12	ADN-80-50-I-P-A
536370	80	60	M12	ADN-80-60-I-P-A
536371	80	80	M12	ADN-80-80-I-P-A

Tech Sheet 71596

FAC
Fluid-Air Components Ltd

ISO 21287 COMPACT CYLINDERS, ADN


Double Acting, Self-adjusting Pneumatic Cushioning


- Compact cylinders with standard dimensions
- Comply with the standard ISO 21287
- Innovative technology for maximum speeds
- Flexible in use thanks to easy-to-configure variant
- Profile slot for proximity senso
- T-Slot

Ambient Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar

Self-adjusting Cushioning





Magnetic Male Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
572655	32	10	M10 x 1.25	ADN-32-10-A-PPS-A
572656	32	15	M10 x 1.25	ADN-32-15-A-PPS-A
572657	32	20	M10 x 1.25	ADN-32-20-A-PPS-A
572658	32	25	M10 x 1.25	ADN-32-25-A-PPS-A
572659	32	30	M10 x 1.25	ADN-32-30-A-PPS-A
572660	32	40	M10 x 1.25	ADN-32-40-A-PPS-A
572661	32	50	M10 x 1.25	ADN-32-50-A-PPS-A
572662	32	60	M10 x 1.25	ADN-32-60-A-PPS-A
572663	32	80	M10 x 1.25	ADN-32-80-A-PPS-A
572673	40	10	M10 x 1.25	ADN-40-10-A-PPS-A
572674	40	15	M10 x 1.25	ADN-40-15-A-PPS-A
572675	40	20	M10 x 1.25	ADN-40-20-A-PPS-A
572676	40	25	M10 x 1.25	ADN-40-25-A-PPS-A
572677	40	30	M10 x 1.25	ADN-40-30-A-PPS-A
572678	40	40	M10 x 1.25	ADN-40-40-A-PPS-A
572679	40	50	M10 x 1.25	ADN-40-50-A-PPS-A
572680	40	60	M10 x 1.25	ADN-40-60-A-PPS-A
572681	40	80	M10 x 1.25	ADN-40-80-A-PPS-A
572691	50	10	M12 x 1.25	ADN-50-10-A-PPS-A
572692	50	15	M12 x 1.25	ADN-50-15-A-PPS-A
572693	50	20	M12 x 1.25	ADN-50-20-A-PPS-A
572694	50	25	M12 x 1.25	ADN-50-25-A-PPS-A
572695	50	30	M12 x 1.25	ADN-50-30-A-PPS-A
572696	50	40	M12 x 1.25	ADN-50-40-A-PPS-A
572697	50	50	M12 x 1.25	ADN-50-50-A-PPS-A
572698	50	60	M12 x 1.25	ADN-50-60-A-PPS-A
572699	50	80	M12 x 1.25	ADN-50-80-A-PPS-A
572709	63	10	M12 x 1.25	ADN-63-10-A-PPS-A
572710	63	15	M12 x 1.25	ADN-63-15-A-PPS-A
572711	63	20	M12 x 1.25	ADN-63-20-A-PPS-A
572712	63	25	M12 x 1.25	ADN-63-25-A-PPS-A
572713	63	30	M12 x 1.25	ADN-63-30-A-PPS-A
572714	63	40	M12 x 1.25	ADN-63-40-A-PPS-A
572715	63	50	M12 x 1.25	ADN-63-50-A-PPS-A
572716	63	60	M12 x 1.25	ADN-63-60-A-PPS-A
572717	63	80	M12 x 1.25	ADN-63-80-A-PPS-A
572727	80	10	M16 x 1.5	ADN-80-10-A-PPS-A
572728	80	15	M16 x 1.5	ADN-80-15-A-PPS-A
572729	80	20	M16 x 1.5	ADN-80-20-A-PPS-A
572730	80	25	M16 x 1.5	ADN-80-25-A-PPS-A
572731	80	30	M16 x 1.5	ADN-80-30-A-PPS-A
572732	80	40	M16 x 1.5	ADN-80-40-A-PPS-A
572733	80	50	M16 x 1.5	ADN-80-50-A-PPS-A
572734	80	60	M16 x 1.5	ADN-80-60-A-PPS-A
572735	80	80	M16 x 1.5	ADN-80-80-A-PPS-A

Tech Sheet 71597

Magnetic Female Piston Rod Thread

0009	Piston Diameter mm	Stroke mm	Piston Rod Thread	Manufacturer's Code
572646	32	10	M8	ADN-32-10-I-PPS-A
572647	32	15	M8	ADN-32-15-I-PPS-A
572648	32	20	M8	ADN-32-20-I-PPS-A
572649	32	25	M8	ADN-32-25-I-PPS-A
572650	32	30	M8	ADN-32-30-I-PPS-A
572651	32	40	M8	ADN-32-40-I-PPS-A
572652	32	50	M8	ADN-32-50-I-PPS-A
572653-FESTO	32	60	M8	ADN-32-60-I-PPS-A
572654	32	80	M8	ADN-32-80-I-PPS-A
572664	40	10	M8	ADN-40-10-I-PPS-A
572665	40	15	M8	ADN-40-15-I-PPS-A
572666	40	20	M8	ADN-40-20-I-PPS-A
572667	40	25	M8	ADN-40-25-I-PPS-A
572668	40	30	M8	ADN-40-30-I-PPS-A
572669	40	40	M8	ADN-40-40-I-PPS-A
572670	40	50	M8	ADN-40-50-I-PPS-A
572671	40	60	M8	ADN-40-60-I-PPS-A
572672	40	80	M8	ADN-40-80-I-PPS-A
572682	50	10	M10	ADN-50-10-I-PPS-A
572683	50	15	M10	ADN-50-15-I-PPS-A
572684	50	20	M10	ADN-50-20-I-PPS-A
572685	50	25	M10	ADN-50-25-I-PPS-A
572686	50	30	M10	ADN-50-30-I-PPS-A
572687	50	40	M10	ADN-50-40-I-PPS-A
572688	50	50	M10	ADN-50-50-I-PPS-A
572689	50	60	M10	ADN-50-60-I-PPS-A
572690	50	80	M10	ADN-50-80-I-PPS-A
572700	63	10	M10	ADN-63-10-I-PPS-A
572701	63	15	M10	ADN-63-15-I-PPS-A
572702	63	20	M10	ADN-63-20-I-PPS-A
572703	63	25	M10	ADN-63-25-I-PPS-A
572704	63	30	M10	ADN-63-30-I-PPS-A
572705	63	40	M10	ADN-63-40-I-PPS-A
572706	63	50	M10	ADN-63-50-I-PPS-A
572707	63	60	M10	ADN-63-60-I-PPS-A
572708	63	80	M10	ADN-63-80-I-PPS-A
572718	80	10	M12	ADN-80-10-I-PPS-A
572719	80	15	M12	ADN-80-15-I-PPS-A
572720	80	20	M12	ADN-80-20-I-PPS-A
572721	80	25	M12	ADN-80-25-I-PPS-A
572722	80	30	M12	ADN-80-30-I-PPS-A
572723	80	40	M12	ADN-80-40-I-PPS-A
572724	80	50	M12	ADN-80-50-I-PPS-A
572725	80	60	M12	ADN-80-60-I-PPS-A
572726	80	80	M12	ADN-80-80-I-PPS-A

Tech Sheet 71598

Fluid-Air Components Ltd

PROXIMITY SENSORS

FESTO

For T-Slot For DSBC/ADN/DSNU Cylinders

- Switching output via reed contact or non-contacting
- Insertable in the slot from above, does not protrude beyond the cylinder profil
- Variant suitable for use with energy chains and robots
- Cable clip and inscription labels included in the scope of delivery
- With switching status indication
- Selected types in accordance with ATEX directive for potentially explosive atmospheres

Ambient Temperature:
-40°C to +70°C





With Reed Contacts

0010	Function	Connection	Cable Length Metres	Manufacturer's Code
543872	N/O Contact, 2 Wire	Open End	2.5	SME-8M-ZS-24V-K-2,5-OE
543861	N/O Contact, 3 Wire	M8 Thread Rotatable	0.3	SME-8M-DS-24V-K-0,3-M8D
543862	N/O Contact, 3 Wire	Open End	2.5	SME-8M-DS-24V-K-2,5-OE
543863	N/O Contact, 3 Wire	Open End	5.0	SME-8M-DS-24V-K-5,0-OE
546799	N/C Contact, 3 Wire	Open End	7.5	SME-8M-DO-24V-K-7,5-OE
		Tech Sheet 70211		

Non-contacting

0009	Function	Connection	Cable Length Metres	Manufacturer's Code
574334	PNP N/O Contact, 3 Wire	M8 Thread Rotatable	0.3	SMT-8M-A-PS-24V-E-0,3-M8D
574337	PNP N/O Contact, 3 Wire	M12 Thread Rotatable	0.3	SMT-8M-A-PS-24V-E-0,3-M12
574339	NPN N/O Contact, 3 Wire	M8 Thread Rotatable	0.3	SMT-8M-A-NS-24V-E-0,3-M8D
574335	PNP N/O Contact, 3 Wire	Open End	2.5	SMT-8M-A-PS-24V-E-2,5-OE
574338	NPN N/O Contact, 3 Wire	Open End	2.5	SMT-8M-A-NS-24V-E-2,5-OE
574341	PNP N/O Contact, 2 Wire	Open End	5.0	SMT-8M-A-ZS-24V-E-5,0-OE-EX2
574336	PNP N/O Contact, 3 Wire	Open End	5.0	SMT-8M-A-PS-24V-E-5,0-OE
574340	PNP N/C Contact, 3 Wire	Open End	7.5	SMT-8M-A-PO-24V-E-7,5-OE
		Tech Sheet 70212		

For C-Slot For ADN/ADVC/DFM

- Switching output via reed contact or non-contacting
- Insertable in the slot from above, does not protrude beyond the cylinder profil
- Suitable for use with energy chains and robots
- Cable clip and inscription labels included in the scope of delivery
- With switching status indication


Ambient Temperature:
-40°C to +70°C






With Reed Contacts

0010	Function	Connection	Cable Length Metres	Manufacturer's Code
551367	N/O Contact, 3 Wire	M8 Thread Rotatable	0.3	SME-10M-DS-24V-E-0,3-L-M8D
551369	N/O Contact, 2 Wire	Open End	2.5	SME-10M-ZS-24V-E-2,5-L-OE
551365	N/O Contact, 3 Wire	Open End	2.5	SME-10M-DS-24V-E-2,5-L-OE
		Tech Sheet 70213		





For C-Slot For ADN/ADVC/DFM

- Magneto-resistive cylinder sensor for round slot, can be inserted from above.
- Measuring principle: magneto-resistive
- For universal use
- Individually configurable or pre-assemble
- Inserted in the slot from above, flush with the cylinder profil
- LED switching status indication
- Cable length 0.3, 2.5m



Proximity Sensors SMT-10M, for C-Slot

0009	N/O Contact	Cable Length (m)	Type
551373	PNP	2.5	SMT-10M-PS-24V-E-2,5-L-OE
551375	PNP	0.3	SMT-10M-PS-24V-E-0,3-L-M8D
551377	NPN	2.5	SMT-10M-NS-24V-E-2,5-L-OE
551379	NPN	0.3	SMT-10M-NS-24V-E-0,3-L-M8D
551382	Non-contacting, 2-wire	2.5	SMT-10M-ZS-24V-E-2,5-L-OE
		Tech Sheet 70212	

- Modular cable system with unlimited combination options for sockets, cable lengths and cable qualities. Matches all devices with M8 and M12 plugs such as proximity switches, pressure switches, sensors, transmitters, flow sensors and others
- For thread M8 x 1 A-coded according to EN 61076-2-104
- For thread M12 x 1 A-coded according to EN 61076-2-101
- Pre-assembled at one or both ends
- Designs for static, standard, energy chain and robot applications
- Cable length 0.1 - 30m
- With PVC or PUR cable
- Ambient temperature -25 to +80 °C



Connecting Cable NEBU

0009	Number of wires	Cable Length (m)	Type
541333	3	2.5	NEBU-M8G3-K-2.5-LE3
541334	3	5	NEBU-M8G3-K-5-LE3
541338	3	2.5	NEBU-M8W3-K-2.5-LE3
541341	3	5	NEBU-M8W3-K-5-LE3
		Tech Sheet 70212	


Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

CYLINDERS

For the full range and more information, please contact one of our sales team.

DFM GUIDED DRIVES

Features



Product Description

DFM - 32 - 80 - P - A - GF

- DFM — Cylinder Type
- 32 — Bore Size mm
- 80 — Stroke Size mm
- P — Polymer Cushioning
- A — Magnetic
- GF — GF Plain bearing guide, KF Ball bearing guide


FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DFM GUIDED DRIVES

FESTO


Sliding Guided Drives with Plain Bearing, Double Acting

- Drive and guide unit in a single housing
- Sturdy and precise
- Plain bearing guide
- High resistance to torques and lateral forces
- Wide range of applications
- Selected types in accordance with ATEX directive for potentially explosive atmospheres
- Sensor C Slot SMT 10G
- C Slot 6 to 10 bore
- T Slot 12 to 63 bore



Ambient Temperature:
-20°C to +80°C

Working Pressure:
2 to 8 bar (Piston: 6mm)
1.5 to 8 bar (Piston: 10mm)
2 to 10 bar (Piston: 12, 16, 20mm)
1.5 to 10 bar (Piston: 25, 32, 40mm)
1 to 10 bar (Piston: 50, 63mm)



M3 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
4149944	6	5	DFM-6-5-P-A-GF
4149945	6	10	DFM-6-10-P-A-GF
4149946	6	15	DFM-6-15-P-A-GF
4149947	6	20	DFM-6-20-P-A-GF
4154768	10	5	DFM-10-5-P-A-GF
4154769	10	10	DFM-10-10-P-A-GF
4154770	10	15	DFM-10-15-P-A-GF
4154799	10	20	DFM-10-20-P-A-GF
		Tech Sheet 70196	

M5 Connection, Magnetic Sensors T Slot SMT-8M

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170824	12	10	DFM-12-10-P-A-GF
170825	12	20	DFM-12-20-P-A-GF
170826	12	25	DFM-12-25-P-A-GF
170827	12	30	DFM-12-30-P-A-GF
170828	12	40	DFM-12-40-P-A-GF
170829	12	50	DFM-12-50-P-A-GF
170830	12	80	DFM-12-80-P-A-GF
170831	12	100	DFM-12-100-P-A-GF
170832	16	10	DFM-16-10-P-A-GF
170833	16	20	DFM-16-20-P-A-GF
170834	16	25	DFM-16-25-P-A-GF
170835	16	30	DFM-16-30-P-A-GF
170836	16	40	DFM-16-40-P-A-GF
170837	16	50	DFM-16-50-P-A-GF
170838	16	80	DFM-16-80-P-A-GF
170839	16	100	DFM-16-100-P-A-GF
170840	20	20	DFM-20-20-P-A-GF
170841	20	25	DFM-20-25-P-A-GF
170842	20	30	DFM-20-30-P-A-GF
170843	20	40	DFM-20-40-P-A-GF
170844	20	50	DFM-20-50-P-A-GF
170845	20	80	DFM-20-80-P-A-GF
170846	20	100	DFM-20-100-P-A-GF
		Tech Sheet 70197	

T Slot



C Slot



G1/8 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170847	25	20	DFM-25-20-P-A-GF
170848	25	25	DFM-25-25-P-A-GF
170849	25	30	DFM-25-30-P-A-GF
170850	25	40	DFM-25-40-P-A-GF
170851	25	50	DFM-25-50-P-A-GF
170852	25	80	DFM-25-80-P-A-GF
170853	25	100	DFM-25-100-P-A-GF
170854	32	20	DFM-32-20-P-A-GF
170855	32	25	DFM-32-25-P-A-GF
170856	32	30	DFM-32-30-P-A-GF
170857	32	40	DFM-32-40-P-A-GF
170858	32	50	DFM-32-50-P-A-GF
170859	32	80	DFM-32-80-P-A-GF
170860	32	100	DFM-32-100-P-A-GF
170861	32	125	DFM-32-125-P-A-GF
170862	32	160	DFM-32-160-P-A-GF
170863	32	200	DFM-32-200-P-A-GF
170864	40	25	DFM-40-25-P-A-GF
170865	40	50	DFM-40-50-P-A-GF
170866	40	80	DFM-40-80-P-A-GF
170867	40	100	DFM-40-100-P-A-GF
170868	40	125	DFM-40-125-P-A-GF
170869	40	160	DFM-40-160-P-A-GF
170870	40	200	DFM-40-200-P-A-GF
		Tech Sheet 70198	

G1/4 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170871	50	25	DFM-50-25-P-A-GF
170872	50	50	DFM-50-50-P-A-GF
170873	50	80	DFM-50-80-P-A-GF
170874	50	100	DFM-50-100-P-A-GF
170875	50	125	DFM-50-125-P-A-GF
170876	50	160	DFM-50-160-P-A-GF
170877	50	200	DFM-50-200-P-A-GF
170878	63	25	DFM-63-25-P-A-GF
170879	63	50	DFM-63-50-P-A-GF
170880	63	80	DFM-63-80-P-A-GF
170881	63	100	DFM-63-100-P-A-GF
170882	63	125	DFM-63-125-P-A-GF
170883	63	160	DFM-63-160-P-A-GF
170884	63	200	DFM-63-200-P-A-GF
		Tech Sheet 70199	


FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

DFM GUIDED DRIVES

FESTO


Recirculating Ball Bearing Guided Drives, Double Acting

- Drive and guide unit in a single housing
- Sturdy and precise
- Plain or Recirculating ball bearing guide
- High resistance to torques and lateral forces
- Wide range of applications
- Selected types in accordance with ATEX directive for potentially explosive atmospheres
- C Slot 6 to 10 bore
- T Slot 12 to 63 bore



Ambient Temperature:
-20°C to +80°C

Working Pressure:
2 to 10 bar (Piston: 12, 16, 20mm)
1.5 to 10 bar (Piston: 25, 32, 40mm)
1 to 10 bar (Piston: 50, 63mm)



M5 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170899	12	10	DFM-12-10-P-A-KF
170900	12	20	DFM-12-20-P-A-KF
170901	12	25	DFM-12-25-P-A-KF
170902	12	30	DFM-12-30-P-A-KF
170903	12	40	DFM-12-40-P-A-KF
170904	12	50	DFM-12-50-P-A-KF
170905	12	80	DFM-12-80-P-A-KF
170906	12	100	DFM-12-100-P-A-KF
170907	16	10	DFM-16-10-P-A-KF
170908	16	20	DFM-16-20-P-A-KF
170909	16	25	DFM-16-25-P-A-KF
170910	16	30	DFM-16-30-P-A-KF
170911	16	40	DFM-16-40-P-A-KF
170912	16	50	DFM-16-50-P-A-KF
170913	16	80	DFM-16-80-P-A-KF
170914	16	100	DFM-16-100-P-A-KF
170915	20	20	DFM-20-20-P-A-KF
170916	20	25	DFM-20-25-P-A-KF
170917	20	30	DFM-20-30-P-A-KF
170918	20	40	DFM-20-40-P-A-KF
170919	20	50	DFM-20-50-P-A-KF
170920	20	80	DFM-20-80-P-A-KF
170921	20	100	DFM-20-100-P-A-KF
		Tech Sheet 70200	

T Slot



C Slot



G1/8 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170922	25	20	DFM-25-20-P-A-KF
170923	25	25	DFM-25-25-P-A-KF
170924	25	30	DFM-25-30-P-A-KF
170925	25	40	DFM-25-40-P-A-KF
170926	25	50	DFM-25-50-P-A-KF
170927	25	80	DFM-25-80-P-A-KF
170928	25	100	DFM-25-100-P-A-KF
170929	32	20	DFM-32-20-P-A-KF
170930	32	25	DFM-32-25-P-A-KF
170931	32	30	DFM-32-30-P-A-KF
170932	32	40	DFM-32-40-P-A-KF
170933	32	50	DFM-32-50-P-A-KF
170934	32	80	DFM-32-80-P-A-KF
170935	32	100	DFM-32-100-P-A-KF
170936	32	125	DFM-32-125-P-A-KF
170937	32	160	DFM-32-160-P-A-KF
170938	32	200	DFM-32-200-P-A-KF
170939	40	25	DFM-40-25-P-A-KF
170940	40	50	DFM-40-50-P-A-KF
170941	40	80	DFM-40-80-P-A-KF
170942	40	100	DFM-40-100-P-A-KF
170943	40	125	DFM-40-125-P-A-KF
170944	40	160	DFM-40-160-P-A-KF
170945	40	200	DFM-40-200-P-A-KF
		Tech Sheet 70201	

G1/4 Connection, Magnetic

0009	Cylinder Bore mm	Cylinder Stroke Length mm	Manufacturer's Code
170946	50	25	DFM-50-25-P-A-KF
170947	50	50	DFM-50-50-P-A-KF
170948	50	80	DFM-50-80-P-A-KF
170949	50	100	DFM-50-100-P-A-KF
170950	50	125	DFM-50-125-P-A-KF
170951	50	160	DFM-50-160-P-A-KF
170952	50	200	DFM-50-200-P-A-KF
170953	63	25	DFM-63-25-P-A-KF
170954	63	50	DFM-63-50-P-A-KF
170955	63	80	DFM-63-80-P-A-KF
170956	63	100	DFM-63-100-P-A-KF
170957	63	125	DFM-63-125-P-A-KF
170958	63	160	DFM-63-160-P-A-KF
170959	63	200	DFM-63-200-P-A-KF
		Tech Sheet 70202	


FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CYLINDERS

For the full range and more information, please contact one of our sales team.

DRRD SEMI-ROTARY DRIVE

Features



Product Description

DRRD - 12 - 180 - FH - PA

- DRRD — Cylinder Type
- 12 — Bore Size mm
- 180 — Rotation Angle
- FH — Flanged Shaft
- PA — PA - Polymer Cushion Magnetic; Y9A - Shock Absorber Magnetic

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TWIN PISTONS SEMI-ROTARY DRIVES, DRRD


FESTO

Rack & Pinion

- Modern and compact design
- Lighter than other semi-rotary drives
- Housing protected against splash water and dust
- Selected types in accordance with ATEX directive for potentially explosive atmospheres
- T-Slot 8M

Ambient Temperature:
-10°C to +60°C

Working Pressure:
3 to 8 bar





Elastic Cushioning Rings, M5 Connection

0009	Size mm	Manufacturer's Code
1577238	16	DRRD-16-180-FH-PA
1395606	20	DRRD-20-180-FH-PA
1359980	25	DRRD-25-180-FH-PA
	Tech Sheet 70205	

Elastic Cushioning Rings, G1/8 Connection

0009	Size mm	Manufacturer's Code
1578512	32	DRRD-32-180-FH-PA
1526825	35	DRRD-35-180-FH-PA
1503269	40	DRRD-40-180-FH-PA
	Tech Sheet 70206	

Self-adjusting Linear Shock Absorber, M5 Connection

0009	Size mm	Manufacturer's Code
1644389	16	DRRD-16-180-FH-Y9A
1427379	20	DRRD-20-180-FH-Y9A
1360248	25	DRRD-25-180-FH-Y9A
	Tech Sheet 70207	

Self-adjusting Linear Shock Absorber, G1/8 Connection

0009	Size mm	Manufacturer's Code
1578518	32	DRRD-32-180-FH-Y9A
1547102	35	DRRD-35-180-FH-Y9A
1526986	40	DRRD-40-180-FH-Y9A
	Tech Sheet 70208	

FESTO



For **FESTO pneumatic tubing**
see pages **911-912**

FAC
Fluid-Air Components Ltd

ISO 21287 CYLINDERS

Compact Series Liner

Compact cylinder to ISO 21287, LINER series, available in different versions to meet all possible requirements. Below sizes listed are most popular, if you require an alternative size please contact the sales office

The heads have been eliminated for ease of installation, improved sturdiness and precision. The metal lining is designed to withstand heavy-duty work, tensile stress and impact. Technopolymer parts can withstand dynamic and pneumatic thrust. The lining virtually acts as a "bearing" to which most of user accessories are attached. The wide range of anchors provide numerous fixing points. Retractable magnetic limit switches can be mounted to identify the position in the cylinder grooves.



Double Acting, Male Piston Rod

9146	Bore mm	Stroke mm
2800200005XP	20	5
2800200010XP	20	10
2800200015XP	20	15
2800200020XP	20	20
2800200025XP	20	25
2800200040XP	20	40
2800200050XP	20	50
2800250005XP	25	5
2800250010XP	25	10
2800250015XP	25	15
2800250020XP	25	20
2800250025XP	25	25
2800250040XP	25	40
2800250050XP	25	50
2800320005CP	32	5
2800320010CP	32	10
2800320015CP	32	15
2800320020CP	32	20
2800320025CP	32	25
2800320040CP	32	40
2800320050CP	32	50
2800400005CP	40	5
2800400010CP	40	10
2800400015CP	40	15
2800400020CP	40	20
2800400025CP	40	25
2800400040CP	40	40
2800400050CP	40	50

9146	Bore mm	Stroke mm
2800500005CP	50	5
2800500010CP	50	10
2800500015CP	50	15
2800500020CP	50	20
2800500025CP	50	25
2800500040CP	50	40
2800500050CP	50	50
2800630005CP	63	5
2800630010CP	63	10
2800630015CP	63	15
2800630020CP	63	20
2800630025CP	63	25
2800630040CP	63	40
2800630050CP	63	50
2800800005AP	80	5
2800800010AP	80	10
2800800015AP	80	15
2800800020AP	80	20
2800800025AP	80	25
2800800040AP	80	40
2800800050AP	80	50
2800100005AP	100	5
2800100010AP	100	10
2800100015AP	100	15
2800100020AP	100	20
2800100025AP	100	25
2800100040AP	100	40
2800100050AP	100	50

Please contact our Sales Department for full range of accessories

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO 21287 CYLINDERS

Compact Series Liner

Compact cylinder to ISO 21287, LINER series, available in different versions to meet all possible requirements. Below sizes listed are most popular, if you require an alternative size please contact the sales office

The heads have been eliminated for ease of installation, improved sturdiness and precision. The metal lining is designed to withstand heavy-duty work, tensile stress and impact. Technopolymer parts can withstand dynamic and pneumatic thrust. The lining virtually acts as a "bearing" to which most of user accessories are attached. The wide range of anchors provide numerous fixing points. Retractable magnetic limit switches can be mounted to identify the position in the cylinder grooves.



Double Acting, Female Piston Rod

9146	Bore mm	Stroke mm
2900200005XP	20	5
2900200010XP	20	10
2900200015XP	20	15
2900200020XP	20	20
2900200025XP	20	25
2900200040XP	20	40
2900200050XP	20	50
2900250005XP	25	5
2900250010XP	25	10
2900250015XP	25	15
2900250020XP	25	20
2900250025XP	25	25
2900250040XP	25	40
2900250050XP	25	50
2900320005CP	32	5
2900320010CP	32	10
2900320015CP	32	15
2900320020CP	32	20
2900320025CP	32	25
2900320040CP	32	40
2900320050CP	32	50
2900400005CP	40	5
2900400010CP	40	10
2900400015CP	40	15
2900400020CP	40	20
2900400025CP	40	25
2900400040CP	40	40
2900400050CP	40	50

9146	Bore mm	Stroke mm
2900500005CP	50	5
2900500010CP	50	10
2900500015CP	50	15
2900500020CP	50	20
2900500025CP	50	25
2900500040CP	50	40
2900500050CP	50	50
2900630005CP	63	5
2900630010CP	63	10
2900630015CP	63	15
2900630020CP	63	20
2900630025CP	63	25
2900630040CP	63	40
2900630050CP	63	50
2900800005AP	80	5
2900800010AP	80	10
2900800015AP	80	15
2900800020AP	80	20
2900800025AP	80	25
2900800040AP	80	40
2900800050AP	80	50
2900100005AP	100	5
2900100010AP	100	10
2900100015AP	100	15
2900100020AP	100	20
2900100025AP	100	25
2900100040AP	100	40
2900100050AP	100	50

Please contact our Sales Department for full range of accessories

Fluid-Air Components Ltd

COMPACT CYLINDERS & MOUNTINGS

NORGREN

Compact Cylinders

- One third the basic length of a corresponding VDMA/ISO model
- Low friction, long life seal design
- Fully non-corrodible specificatio
- Non-lube operation
- Optional non-rotating piston rod (non-rotating or guided piston rod on RM/92000/M)
- Standard magnetic piston for full control system versatility

Medium:
Compressed air, filtered, lubricated or non-lubricated


Operation:
RM/91000/M Single acting, non-cushioned, magnetic sprung in RM/92000/M
Double acting, buffer cushioning

Barrel and End Caps:
Anodised aluminium alloy

Piston Rod:
RM/91000/M Stainless steel (Ø 12 to 40mm austenitic)
RM/92000/M Stainless steel (Ø 12 to 40mm austenitic, Ø 50 to 100mm martensitic)

Seals:
PUR and/or NBR






Working Temperature:
-5°C to +80°C

Working Pressure:
2 to 10 bar

Single Acting RM/91000/M

0036	Bore mm	Stroke mm	Thread
RM/91032/M/25	32	25	G1/8
RM/91040/M/25	40	25	G1/8
Tech Sheet 10362			



Working Temperature:
-5°C to +80°C

Working Pressure:
1 to 10 bar

Double Acting RM/92000/M

0036	Bore mm	Stroke mm	Thread
RM/92012/M/10	12	10	M5
RM/92016/M/10	16	10	M5
RM/92016/M/15	16	15	M5
RM/92016/M/20	16	20	M5
RM/92020/M/10	20	10	M5
RM/92020/M/15	20	15	M5
RM/92020/M/25	20	25	M5
RM/92020/M/30	20	30	M5
RM/92020/M/40	20	40	M5
RM/92020/M/50	20	50	M5
RM/92025/M/10	25	10	M5
RM/92025/M/20	25	20	M5
RM/92025/M/25	25	25	M5
RM/92025/M/30	25	30	M5
RM/92025/M/40	25	40	M5
RM/92025/M/50	25	50	M5
RM/92032/M/10	32	10	G1/8
RM/92032/M/15	32	15	G1/8
RM/92032/M/20	32	20	G1/8
RM/92032/M/25	32	25	G1/8
RM/92032/M/30	32	30	G1/8
RM/92032/M/40	32	40	G1/8
RM/92032/M/50	32	50	G1/8
RM/92032/M/60	32	60	G1/8
RM/92032/M/80	32	80	G1/8
RM/92040/M/5	40	5	G1/8
RM/92040/M/10	40	10	G1/8
RM/92040/M/20	40	20	G1/8
RM/92040/M/25	40	25	G1/8
RM/92040/M/30	40	30	G1/8
RM/92040/M/50	40	50	G1/8
RM/92050/M/10	50	10	G1/8
RM/92050/M/20	50	20	G1/8
RM/92050/M/25	50	25	G1/8
RM/92050/M/30	50	30	G1/8
RM/92050/M/40	50	40	G1/8
RM/92050/M/50	50	50	G1/8
RM/92050/M/100	50	100	G1/8
RM/92063/M/15	63	15	G1/4
RM/92063/M/25	63	25	G1/4
RM/92063/M/40	63	40	G1/4
RM/92080/M/25	80	25	G1/4
RM/92080/M/40	80	40	G1/4
RM/92080/M/50	80	50	G1/4
RM/92080/M/60	80	60	G1/4
RM/92080/M/80	80	80	G1/4
RM/92100/M/30	100	30	G1/4
RM/92100/M/50	100	50	G1/4
Tech Sheet 10361			

Compact Mountings



Female Piston Rod Clevis

0036	Bore mm
QM/57063/25	80 & 100
Tech Sheet 10361	



Flange Mounting

0036	Bore mm
QM/90016/22	16
QM/90025/22	25
QM/90040/22	40
QM/90050/22	50
QM/90063/22	63
QM/90080/22	80
QM/90100/22	100
Tech Sheet 10361	

NORGREN



For **Norgren Excelon Plus** see page **686**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO COMPACT CYLINDERS & MOUNTINGS

NORGREN

ISO Compact Cylinders & Mountings

- Conforms to ISO 21287
- Up to 30% shorter than full
- ISO/VDMA actuators
- Uses standard ISO/VDMA mountings

Working Temperature:
-5°C to +80°C

Working Pressure:
0 to 10 bar

Medium:
Compressed air, filtered, lubricated or non-lubricated

Operation: RA/192000/MX, Double acting, magnetic piston, female piston rod thread, buffer cushioning

Materials:
Profile barrel Anodized aluminium
End covers: Pressure diecast aluminium
Piston rod: Stainless steel
Piston rod seals: PUR
Piston seals: NBR
O-rings: NBR



RA/192000 Series

0036	Bore mm	Stroke mm	Thread
RA/192020/MX/10	20	10	M5
RA/192020/MX/15	20	15	M5
RA/192020/MX/20	20	20	M5
RA/192020/MX/25	20	25	M5
RA/192020/MX/30	20	30	M5
RA/192020/MX/40	20	40	M5
RA/192020/MX/50	20	50	M5
RA/192025/MX/10	25	10	M5
RA/192025/MX/15	25	15	M5
RA/192025/MX/20	25	20	M5
RA/192025/MX/25	25	25	M5
RA/192025/MX/30	25	30	M5
RA/192025/MX/40	25	40	M5
RA/192025/MX/50	25	50	M5
RA/192032/MX/10	32	10	1/8"
RA/192032/MX/15	32	15	1/8"
RA/192032/MX/20	32	20	1/8"
RA/192032/MX/25	32	25	1/8"
RA/192032/MX/30	32	30	1/8"
RA/192032/MX/40	32	40	1/8"
RA/192032/MX/50	32	50	1/8"
RA/192032/MX/60	32	60	1/8"
RA/192032/MX/80	32	80	1/8"
RA/192040/MX/10	40	10	1/8"
RA/192040/MX/15	40	15	1/8"
RA/192040/MX/20	40	20	1/8"
RA/192040/MX/25	40	25	1/8"
RA/192040/MX/30	40	30	1/8"

0036	Bore mm	Stroke mm	Thread
RA/192040/MX/40	40	40	1/8"
RA/192040/MX/50	40	50	1/8"
RA/192050/MX/10	50	10	1/8"
RA/192050/MX/15	50	15	1/8"
RA/192050/MX/20	50	20	1/8"
RA/192050/MX/25	50	25	1/8"
RA/192050/MX/30	50	30	1/8"
RA/192050/MX/40	50	40	1/8"
RA/192050/MX/50	50	50	1/8"
RA/192050/MX/60	50	60	1/8"
RA/192063/M/15	63	15	1/8"
RA/192063/M/25	63	25	1/8"
RA/192063/M/40	63	40	1/8"
RA/192063/M/50	63	50	1/8"
RA/192063/M/60	63	60	1/8"
RA/192063/M/80	63	80	1/8"
RA/192080/M/15	80	15	1/8"
RA/192080/M/25	80	25	1/8"
RA/192080/M/40	80	40	1/8"
RA/192080/M/50	80	50	1/8"
RA/192080/M/60	80	60	1/8"
RA/192080/M/80	80	80	1/8"
RA/192100/M/15	100	15	1/8"
RA/192100/M/25	100	25	1/8"
RA/192100/M/40	100	40	1/8"
RA/192100/M/50	100	50	1/8"
RA/192100/M/60	100	60	1/8"
RA/192100/M/80	100	80	1/8"
Tech Sheet 71752			

Mountings



Front Flange

0036	Bore mm
QA/192020/22	20
QA/192025/22	25
QA/8032/22	32
QA/8040/22	40
QA/8050/22	50
QA/8063/22	63
QA/8080/22	80
QA/8100/22	100
Tech Sheet 71752	



Piston Rod Clevis

0036	Bore mm
QM/8020/25	20
QM/8025/25	25
QM/8032/35	32
QM/8040/25	40
QM/8050/25	50
QM/8080/25	80
Tech Sheet 71752	



Foot C

0036	Bore mm
QM/192020/21	20
QM/192025/21	25
QA/192032/21	32
QA/192040/21	40
QA/192050/21	50
QA/192063/21	63
QA/192080/21	80
QA/192100/21	100
Tech Sheet 71752	



Rear Clevis

0036	Bore mm
QA/8032/23	32
QA/8040/23	40
QA/8050/23	50
QA/8063/23	63
QA/8080/23	80
QA/8100/23	100
Tech Sheet 71752	

Fluid-Air Components Ltd


PNEUMATIC ACTUATION

Compact Cylinders & Accessories

Compact Cylinders ISO 21287 Double Acting 20mm-100mm



0110	Bore mm	Stroke mm
1540.20.15.01.1	20	15
1540.20.50.01.1	20	50
1540.25.50.01.1	25	50
1540.25.60.01.1	25	60
1540.32.15.01.1	32	15
1540.32.20.01.1	32	20
1540.32.30.01.1	32	30
1540.32.60.01.1	32	60
1540.32.200.01.1	32	200
1540.40.75.01.1	40	75
1540.50.30.01.1	50	30
1540.50.35.01.1	50	35
1540.50.50.01.1	50	50
1540.50.100.01.1	50	100
1540.63.25.01.1	63	25
1540.63.50.01.1	63	50
1540.63.100.01.1	63	100
1540.100.80.01.1	100	80



Front & Rear Flanges - Steel

0110	Bore mm
1540.20.03F	20



Foot Brackets MS1 - Steel

0110	Bore mm
1540.20.05/1F	20



Rear Clevis MP2 - Aluminium

0110	Bore mm
1380.32.09F	32
1380.40.09F	40
1380.50.09F	50
1380.63.09F	63
1380.80.09F	80
1380.100.09F	100



Rear Narrow Clevis - Aluminium

0110	Bore mm
1380.80.30F	80



Rear Clevis MP4 - Aluminium

0110	Bore mm
1380.40.09/1F	40
1380.50.09/1F	50
1380.63.09/1F	63
1380.100.09/1F	100



Rear Male Clevis complete with Jointed Head - Aluminium

0110	Bore mm
1380.32.15F	32
1380.40.15F	40
1380.50.15F	50
1380.80.15F	80



Square Angle Trunnion - Aluminium

0110	Bore mm
1380.32.35F	32
1380.63.35F	63
1380.80.35F	80
1380.100.35F	100



1580U Reed Switch complete with LED

0110	Description
1580U	LED Reed Switch N/O

Please contact our Sales Department for full range of accessories

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PNEUMATIC CYLINDER & TRANSMITTERS

Pencil Cylinder

The miniature cylinder with a piston diameter of 3mm is for general-purpose use in testing and other operations in very restricted spaces. Even with its small dimensions the cylinder offers the technical features of the proven series of larger miniature cylinders.



Single Acting

0047	Bore mm	Stroke mm
KU-40.100	3	6
	Tech Sheet 10289	

Position Transmitter & Clamp

This unit acts as a 3/2 valve, it can be actuated either by a magnetic cylinder piston or by iron (FE). Use the clamp 33.006 to mount the transmitter onto the cylinder.

Transmitter not included


Working Temperature:
10° to + 60°C

Working Pressure:
2 to 6 bar

Suitable for sizes 8mm to 100mm. For other applications, the 4mm thread on the other side of the housing can be used.

Medium: Compressed air oil free





Transmitter not included

Transmitter, Pneumatic

0047	ID mm
KU-33.21.326	3
Tech Sheet 10290	

Clamp

0047	To Suit
KU-33.006	8mm to 100mm Cylinders
Tech Sheet 10290	

FT PRO

For **FT Pro hose reels** see pages **1449-1453**



FAC Fluid-Air Components Ltd

ROUND RNDC CYLINDERS


Double Acting Cylinders

Clean profile cylinders available in different versions
- Configuration with or without magnet
- Single and double acting
- Single or through-rod
- Pneumatic cushioning on request
- Range of gaskets available in NBR, polyurethane and FKM/FPM (for high temperatures)

Technical Specification
- Fluid: unlubricated air (lubrication, if used, must be continuous)
- Sensor magnet: all versions come complete with magnet
- Piston rod material: C45 chrome rod, technolopolymer piston rod
- Piston seal: NBR

Temperature Range:
10°C to +80°C

Maximum Operating Pressure:
10 bar




Dimensions

Ø	D	E	F	ØG	CH1	I	L	M	N	O	Ø P	R	ØS	SW	T	CH2	V	W	L1
32	M30x1.5	M8x1	22	30	10	96	172	M10x1.25	14	G1/8	38	78	12	17	49	36	30	40	220
40	M38x1.5	M10x1	24	38	13	113	198	M12x1.25	16	G1/4	46	89	16	19	57	43	35	45	251
50	M45x1.5	M12x1.5	32	45	17	120	220	M16x1.5	18	G1/4	57	96	20	24	62	54	38	50	284

Components

1.	Piston rod: C45 steel or stainless steel, thick chromed
2.	Piston rod gasket: polyurethane, NBR or FKM/FPM
3.	Guide bushing: steel strip with bronze and PTFE insert
4.	Barrel: drawn anodised aluminium alloy
5.	Half-piston: self-lubricating technopolymer with integrated cushioning olives
6.	Magnet: plastoferrite
7.	Piston gasket: polyurethane, NBR or FKM/FPM
8.	Head: anodised aluminium alloy



Other variants available on request



Magnetic & Cushioned

9195	Diameter mm	Stroke mm
1120320025CN	32	25
1120320050CN	32	50
1120320080CN	32	80
1120320100CN	32	100
1120320125CN	32	125
1120320160CN	32	160
1120320200CN	32	200
1120320250CN	32	250
1120400025CN	40	25
1120400050CN	40	50
1120400080CN	40	80
1120400100CN	40	100

9195	Diameter mm	Stroke mm
1120400125CN	40	125
1120400160CN	40	160
1120400200CN	40	200
1120400250CN	40	250
1120500025CN	50	25
1120500050CN	50	50
1120500080CN	50	80
1120500100CN	50	100
1120500125CN	50	125
1120500160CN	50	160
1120500200CN	50	200
1120500250CN	50	250


Fluid-Air Components Ltd

ROUND RNDC CYLINDER ACCESSORIES

Foot Mounting

To suit RNDC Cylinders


9146	Ø	A	B	C	D	E	F	G	H	I	L	M	N	O
W0950320002	32	124	50	7	4	14	52	7	14	28	150	66	49	28
W0950400002	40	153	60	10	5	20	60	9	18	30	178	80	58	33
W0950500002	50	160	64	10	6	20	70	9	20	40	190	90	70	40



Counter Support

To suit RNDC Cylinders


9146	Ø	A	B	C	D	E	F	G	H	I	L	M	R	SW
W0950320005	32	40	35	24	4	7	8	12	46.1	20	127	60	12	13
W0950400005	40	50	40	30	5	9	10	13	57.5	28	146	74	13	17
W0950500005	50	54	45	34	6	9	10	14	69.1	36	158	89	14	19



Head Lock Ring

To suit RNDC Cylinders


9146	Ø	A	B	C
W0950320010	32	M30 x 1.5	45	7
W0950400010	40	M38 x 1.5	50	8
W0950500010	50	M45 x 1.5	58	9



Fork Clevis

To suit RNDC Cylinders


9146	Ø	ØM	A	B	C	L	F	D	N
W0950322020	32	10	20	10	20	52	40	M10 x 1.25	26
W0950402020	40	12	24	12	24	62	48	M12 x 1.25	32
W0950502020	50/63	16	32	16	32	83	64	M16 x 1.5	40



Spherical Rod Eye

To suit RNDC Cylinders


9146	Ø	ØM	C	B1	B	A	L	F	D	ØG	CH
W0950322025	32	10	15	10.5	14	28	57	43	M10 x 1.25	15	17
W0950402025	40	12	17	12	16	32	66	50	M12 x 1.25	17.5	19
W0950502025	50	16	22	15	21	42	85	64	M16 x 1.5	22	22



Fluid-Air Components Ltd

ROUND RNDC CYLINDER ACCESSORIES


Articulated Joint



To suit RNDC Cylinders

9146	Ø	A	B	C	D	ØE	ØF	SW1	SW2	SW3	SW4	SW5
W0950322030	32	M10 x 1.25	20	20	71	4	22	12	30	30	19	17
W0950402030	40	M12 x 1.25	24	20	75	4	22	12	30	30	19	19
W0950502030	50	M16 x 1.5	32	32	103	4	32	20	41	41	30	24

Flexible Collar




To suit RNDC Cylinders

9146	Ø	A	B	C	CH	ØD	ØD1	F	ØG	ØG1	P	S	S1
W0950326021	32	49	36	30	13	11	6.5	M10 x 1.25	39.5	17	6.5	12	10
W0950406021	40	59	42	36	15	14	8.5	M12 x 1.25	44	19	8.5	15	13.5
W0950506021	50	79	58	44	22	17	10.5	M16 x 1.5	59	26	10.5	20	15

Reed Switch & Bracket

Technical Data

Type		Contact
Maximum AC/DC voltage	V	Reed + varistor + LED 2 wires
		Reed + varistor + LED NO
		220 ISO cylinder
Maximum current at +25°C	mA	1,000
Power with inductive load	VA	15
Power with resistive load	Watt	50
Switch-on time	M sec	1.2






To suit ISO 6432 Cylinders

9146	Description
W0950000201	Reed Switch

Reed Switch & Bracket

Technical Data

Type		Contact
Switch-off time	M sec	0.1
Cable length		2.5m
Cable material		Soft PVC
Switch-on point	Gauss	110
Switch-off point	Gauss	95
Contact resistance		0.1



To suit RNDC Cylinders

9146	Description
W0950000132	Bracket for RNDC Ø32 Cylinder
W0950000140	Bracket for RNDC Ø40 Cylinder
W0950000150	Bracket for RNDC Ø50 Cylinder

Fluid-Air Components Ltd
ef nkl i r oi r p c c c c a c c

ROUNDLINE CYLINDERS & MOUNTINGS

NORGREN

Roundline Cylinders

- One fifth shorter than the basic length of a corresponding VDMA/ISO cylinder
- Low friction, long life seals
- High strength, double crimped end cap design
- Standard magnetic piston for full control system versatility
- Non-lube operation
- Choice of porting option for compact installation

Medium:
Compressed air, filtered, lubricated or non-lubricated

Operation (Double Acting):
Double acting, buffer cushioning

Piston Rod (Single Acting):
Stainless steel (16 mm bore martensitic, 20 to 40mm bore austenitic)

Piston Rod (Double Acting):
Stainless steel (16mm bore martensitic, 20 to 63mm bore austenitic)

Barrel: Stainless steel (austenitic)

Seals and O-Rings: Nitrile

Wiper: Polyurethane

End Covers: Aluminium




Single Acting:



Working Temperature:
-5°C to +80°C

Working Pressure:
2 to 10 bar

Double Acting:



Working Temperature:
-5°C to +80°C

Working Pressure:
1 to 10 bar

Single Acting RT/57100/M, Side Port - Sprung In

0036	Bore mm	Stroke mm	Thread
RT/57116/M/25	16	25	M5
RT/57120/M/25	20	25	Rc 1/8
RT/57125/M/25	25	25	Rc 1/8
RT/57125/M/50	25	50	Rc 1/8
RT/57132/M/50	32	50	Rc 1/8
RT/57140/M/50	40	50	Rc 1/8
Tech Sheet 10315			

Single Acting RT/57100/M, Axial Port - Sprung In

0036	Bore mm	Stroke mm	Thread
RT/57116/MC/25	16	25	M5
Tech Sheet 10315			

Double Acting RT/57200/M, Side Port - Rear Eye

0036	Bore mm	Stroke mm	Thread
RT/57216/M/25	16	25	M5
RT/57216/M/80	16	80	M5
RT/57220/M/10	20	10	Rc 1/8
RT/57220/M/25	20	25	Rc 1/8
RT/57220/M/100	20	100	Rc 1/8
RT/57225/M/25	25	25	Rc 1/8
RT/57225/M/50	25	50	Rc 1/8
RT/57225/M/80	25	80	Rc 1/8
RT/57225/M/100	25	100	Rc 1/8
RT/57225/M/160	25	160	Rc 1/8
RT/57232/M/25	32	25	Rc 1/8
RT/57232/M/50	32	50	Rc 1/8
RT/57232/M/80	32	80	Rc 1/8
RT/57232/M/100	32	100	Rc 1/8
RT/57232/M/160	32	160	Rc 1/8
RT/57240/M/50	40	50	Rc 1/8
RT/57240/M/80	40	80	Rc 1/8
RT/57240/M/100	40	100	Rc 1/8
Tech Sheet 10315			

Double Acting RT/57200/M, Side Port - Flat End

0036	Bore mm	Stroke mm	Thread
RT/57216/MF/10	16	10	M5
RT/57220/MF/50	20	50	Rc 1/8
RT/57225/MF/25	25	25	Rc 1/8
RT/57225/MF/50	25	50	Rc 1/8
RT/57240/MF/80	40	80	Rc 1/8
Tech Sheet 10315			

Roundline Mountings



Clevis Foot Mounting

0036	Bore mm
QM/946	16
QM/57025/24	25
QM/57040/24	40
Tech Sheet 10315	



Piston Rod Locknut

0036	Bore mm
M/P1501/60	20
M/P1501/89	25 & 32
M/P1501/90	40
Tech Sheet 10315	



Female Piston Rod Clevis

0036	Bore mm
QM/57016/25	16
QM/57020/25	20
QM/57025/25	25
QM/57032/25	32
Tech Sheet 10315	



Piston Rod Eye

0036	Bore mm
QM/8040/32	40
Tech Sheet 10315	




Switch Mounting Bracket (QM33)

0036	Bore mm
QM/33/032/22	32
QM/33/040/22	40
Tech Sheet 10315	


FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Pneumatic Grippers

- Uses a single piston structure to generate a large gripping force
- Integrated variable flow valve to conveniently adjust the speed of opening and closing of the fingers
- Precise positioning accuracy when gripping components
- Body profile adapted with grooves for mounting sensor switches
- Integrated magnet for added control
- Gripping jaw opening and closing angle 30° to -10°
- Single acting N/O available on request
- Interchangeability: SMC



KHFY: Double Acting




Double Acting, Angular Style

0415	Thread	Bore mm	Optimum Gripping Points Length mm
KHFY6	M3 x 0.5	6	30
KHFY10	M3 x 0.5	10	30
KHFY16	M5 x 0.8	16	40
KHFY20	M5 x 0.8	20	60
KHFY25	M5 x 0.8	25	70
KHFY32	M5 x 0.8	32	85
Tech Sheet 20470			

- Integrated linear guide rail for high precision and rigidity
- Positioning pin at the base of the unit to prevent deviation of the rail and body
- Deeper hole on the body to improve precision and consistency when dismounting and positioning
- Variable positioning jaws
- Body profile adapted with grooves for mounting sensor switches
- Other finger types available on request
- Single acting N/O and N/C available on request
- Interchangeability: SMC



KHFZ: Double Acting



Double Acting, Parallel Style

0415	Thread	Bore mm	Optimum Gripping Points Length mm	Open Diameter mm	Closed Diameter mm
KHFZ10	M3 x 0.5	6	5-50	15.5	11.5
KHFZ16	M5 x 0.8	16	5-55	21.0	15.0
KHFZ20	M5 x 0.8	20	5-80	26.5	16.5
KHFZ25	M5 x 0.8	25	5-100	33.5	19.5
Tech Sheet 20471					

How to select product:


Please select pneumatic finger according to the following steps:

The selection of the effective gripping force ⟶ the confirmation of the gripping point ⟶ the confirmation of the external force put on the gripping jaw.

The selection of the gripping force:

The gripping work-pieces shown, on the impact condition of ordinary handling state, taking safety coefficient a=4, have a gripping force that is more than 10-20 times of the mass of the gripped objects

μ = 0.2	μ = 0.1
$F = \frac{mg}{2 \times 0.2} \times 4$ = 10 x mg	$F = \frac{mg}{2 \times 0.1} \times 4$ = 20 x mg
10 times of the mass of the gripped objects	**20 times of the mass of the gripped objects**



F: gripping force (N)

μ: friction coefficient between fittings and work-pieces

m: mass of work-pieces

g: acceleration of gravity (=9.8m/s²)

The condition that the work-pieces won't drop is 2 x μ F>mg, so:

$$F > \frac{mg}{2 \times \mu}$$

Safety coefficient is a, so F is:

$$F = \frac{mg}{2 \times \mu} \times a$$

Note: if the friction coefficient μ>D.2, for safety, please also select clamping force according to the principle of 10-20 times of the mass of the clamped objects. As for large acceleration and shock, it requires for greater safety coefficient.



Slim profile for discreet safe mounting to grippers.

Sensor Switch, Two-line, N/O

0415	Connection	Connecting Cable	Length Metres
KDS1-H-C08	Straight	M8 Quick Joint	0.15
KDS1-H-020	Straight	-	2
KDS1-H-030	Straight	-	3
KDS1-H-050	Straight	-	5
KDS1-HL-C08	90°	M8 Quick Joint	0.15
KDS1-HL-020	90°	-	2
KDS1-HL-030	90°	-	3
KDS1-HL-050	90° Connection	-	5
Tech Sheet 20472			

Sensor Switch, Three-line NPN with No Contact (Current Flows In), N/O

0415	Connection	Connecting Cable	Length Metres
KDS1-H-N-C08	Straight	M8 Quick Joint	0.15
KDS1-H-N-020	Straight	-	2
KDS1-H-N-030	Straight	-	3
KDS1-H-N-050	Straight	-	5
KDS1-HL-N-C08	90°	M8 Quick Joint	0.15
KDS1-HL-N-020	90°	-	2
KDS1-HL-N-030	90°	-	3
KDS1-HL-N-050	90°	-	5
Tech Sheet 20472			

Sensor Switch, Three-line PNP with No Contact (Current Flows Out), N/O

0415	Connection	Connecting Cable	Length Metres
KDS1-H-P-C08	Straight	M8 Quick Joint	0.15
KDS1-H-P-020	Straight	-	2
KDS1-H-P-030	Straight	-	3
KDS1-H-P-050	Straight	-	5
KDS1-HL-P-C08	90°	M8 Quick Joint	0.15
KDS1-HL-P-020	90°	-	2
KDS1-HL-P-030	90°	-	3
KDS1-HL-P-050	90°	-	5
Tech Sheet 20472			


Fluid-Air Components Ltd

CYLINDERS

For the full range and more information, please contact one of our sales team.

DRVS SEMI-ROTARY VANE DRIVE ★

Features



Product Description

DRVS - 12 - 180 - P

- DRVS: Cylinder Type
- 12: Bore Size mm
- 180: Rotation Angle
- P: Elastic polymer buffer

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

SEMI-ROTARY DRIVES, DRVS

Rotary Vane, Double Acting

- Modern and compact design
- Lighter than other semi-rotary drives
- Housing protected against splash water and dust
- Selected types in accordance with ATEX directive for potentially explosive atmospheres

Ambient Temperature:
-10°C to +60°C

Working Pressure:
3.5 to 8 bar (Size: 6, 8mm)
2.5 to 8 bar (Size: 12, 16mm)
2 to 8 bar (Size: 25, 32, 40mm)



Elastic Cushioning Rings, M3 Connection

0009	Size	Nominal Swivel Angle	Manufacturer's Code
1845706	6	90°	DRVS-6-90-P
1845707	6	180°	DRVS-6-180-P
1845708	8	90°	DRVS-8-90-P
1845709	8	180°	DRVS-8-180-P
Tech Sheet 20564			

Elastic Cushioning Rings, M5 Connection

0009	Size	Nominal Swivel Angle	Manufacturer's Code
1845710	12	90°	DRVS-12-90-P
1845711	12	180°	DRVS-12-180-P
1845712	12	270°	DRVS-12-270-P
1845713	16	90°	DRVS-16-90-P
1845714	16	180°	DRVS-16-180-P
1845715	16	270°	DRVS-16-270-P
1845716	25	90°	DRVS-25-90-P
1845717	25	180°	DRVS-25-180-P
1845718	25	270°	DRVS-25-270-P
Tech Sheet 71599			



Position Sensor

0009	Weight	For Drives	Type
2619969	25g	DSM 6, DRVS 6	SRBS-Q12-6-E270-EP-1-S-M8

Elastic Cushioning Rings, G1/8 Connection

0009	Size	Nominal Swivel Angle	Manufacturer's Code
1845719	32	90°	DRVS-32-90-P
1845720	32	180°	DRVS-32-180-P
1845721	32	270°	DRVS-32-270-P
1845722	40	90°	DRVS-40-90-P
1845723	40	180°	DRVS-40-180-P
1845724	40	270°	DRVS-40-270-P
Tech Sheet 71600			



For **Festo MS Series**
see page **658**

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c


Panel Mount Valves, Manual & Mechanical 3/2 Way Valves

Medium: Clean compressed air. Filtered (40µm)
Material: Valve body aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 10 bar


2 Year Warranty





Basic Valve, Metric & BSPP


0335	Thread
K3M3B-05	M5
K3M3B-06	1/8"
K3M3B-08	1/4"
Tech Sheet 3097	





One Way Roller Lever Valve, Metric & BSPP

0335	Thread
K3M3L-05	M5
K3M3L-06	1/8"
K3M3L-08	1/4"
Tech Sheet 3097	





Roller Lever Valve, Metric & BSPP


0335	Thread
K3M3R-05	M5
K3M3R-06	1/8"
K3M3R-08	1/4"
Tech Sheet 3097	





Lever/Lever, Metric & BSPP

0335	Thread
K3M3Y-05	M5
K3M3Y-06	1/8"
K3M3Y-08	1/4"
Tech Sheet 3097	





Roller Valve, Metric & BSPP

0335	Thread
K3M3V-05	M5
K3M3V-06	1/8"
K3M3V-08	1/4"
Tech Sheet 3097	

Fluid-Air Components Ltd

MANUAL & MECHANICAL VALVES


Panel Mount Valves, Manual & Mechanical 3/2 Way Valves

Medium: Clean compressed air. Filtered (40µm)
Material: Valve body aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 10 bar


2 Year Warranty





Push Button (Shrouded), Metric & BSPP

0335	Thread	Colour
K3M3PF-05-B	M5	Black
K3M3PF-05-G	M5	Green
K3M3PF-05-R	M5	Red
K3M3PF-06-B	1/8"	Black
K3M3PF-06-G	1/8"	Green
K3M3PF-06-R	1/8"	Red
K3M3PF-08-B	1/4"	Black
K3M3PF-08-G	1/4"	Green
K3M3PF-08-R	1/4"	Red
Tech Sheet 3097		





Palm Button, Metric & BSPP


0335	Thread	Colour
K3M3PM-05-B	M5	Black
K3M3PM-05-G	M5	Green
K3M3PM-05-R	M5	Red
K3M3PM-06-B	1/8"	Black
K3M3PM-06-G	1/8"	Green
K3M3PM-06-R	1/8"	Red
K3M3PM-08-B	1/4"	Black
K3M3PM-08-G	1/4"	Green
K3M3PM-08-R	1/4"	Red
Tech Sheet 3097		





Push Button (External), Metric & BSPP


0335	Thread	Colour
K3M3PP-05-B	M5	Black
K3M3PP-05-G	M5	Green
K3M3PP-05-R	M5	Red
K3M3PP-06-B	1/8"	Black
K3M3PP-06-G	1/8"	Green
K3M3PP-06-R	1/8"	Red
K3M3PP-08-B	1/4"	Black
K3M3PP-08-G	1/4"	Green
K3M3PP-08-R	1/4"	Red
Tech Sheet 3097		





Palm Button, Latching, Metric & BSPP

0335	Thread	Colour
K3M3PL-05-R	M5	Red
K3M3PL-06-R	1/8"	Red
K3M3PL-08-R	1/4"	Red
Tech Sheet 3097		





2 Position Selector Switch, Metric & BSPP

0335	Thread
K3M3HS05	M5
K3M3HS06	1/8"
K3M3HS08	1/4"
Tech Sheet 3097	

Fluid-Air Components Ltd

Manual 3/2 Way Valves

Medium: Clean compressed air. Filtered (40µm) and lubricated
Material: Aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 8 bar

2 Year Warranty





Push/Pull, BSPP


0335	Thread
CKL110-06	1/8"
CKL210-08	1/4"
CKL310-10	3/8"
Tech Sheet 3032	





Push Button (Shrouded), 1/8" BSPP


0335	Colour
KSCPF-06-B	Black
KSCPF-06-G	Green
KSCPF-06-R	Red
Tech Sheet 3038	





Push Button (External), 1/8" BSPP


0335	Colour
KSCPP-06-B	Black
KSCPP-06-G	Green
KSCPP-06-R	Red
Tech Sheet 3038	





Palm Button, 1/8" BSPP

0335	Colour
KSCPM-06-B	Black
KSCPM-06-G	Green
KSCPM-06-R	Red
Tech Sheet 3038	





Palm Button, Latching, 1/8" BSPP


0335	Colour
KSCPL-06-R	Red
Tech Sheet 3038	





Lever/Lever, 1/8" BSPP

0335
KSY-06
Tech Sheet 3038





Switch, 1/8" BSPP

0335	Colour
KSCHS-06-B	Black
KSCHS-06-G	Green
KSCHS-06-R	Red
Tech Sheet 3038	

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MANUAL & MECHANICAL VALVES

Working Temperature:
-20°C to +70°C


2 Year Warranty

Mechanical 3/2 Way Valves

Maximum Working Pressure:
8 bar

One Way Roller Lever, 1/8" BSPP






0335
KSCL-06
Tech Sheet 3038

Maximum Working Pressure:
8 bar

Roller, 1/8" BSPP






0335
KSCV-06
Tech Sheet 3038

Maximum Working Pressure:
8 bar

Roller Lever, 1/8" BSPP






0335
KSCR-06
Tech Sheet 3038

Maximum Working Pressure:
8 bar

Plunger, 1/8" BSPP






0335
KCB-06
Tech Sheet 3038

Maximum Working Pressure:
10 bar

Roller/Spring, 1/8" BSPP






0335
ZMCR-06-W
Tech Sheet 10061

Maximum Working Pressure:
10 bar


Adjustable Roller/Spring, 1/8" BSPP





0335
ZMCJ-06-W
Tech Sheet 10061

Maximum Working Pressure:
10 bar



Antenna/Spring, 1/8" BSPP




0335
ZMCP-06-W
Tech Sheet 10061

Manual 4/2 Way Valves

Maximum Working Pressure:
10 bar



Lever/Lever, BSPP




0335	Thread
DKHV210-06-S	1/8"
DKHV310-08-S	1/4"
DKHV310-10-S	3/8"
DKHV410-15-S	1/2"
DKHV410-20-S	3/4"
Tech Sheet 3033	

Manual 4/3 Way Valves

Maximum Working Pressure:
10 bar



Lever/Lever/Lever (Fully Sealed Mid Position), BSPP



0335	Thread
DKHV230-C-06-S	1/8"
DKHV330-C-08-S	1/4"
DKHV330-C-10-S	3/8"
DKHV430-C-15-S	1/2"
DKHV430-C-20-S	3/4"
Tech Sheet 3033	

Fluid-Air Components Ltd

MANUAL & MECHANICAL VALVES

Working Temperature:
-20°C to +70°C

2 Year Warranty

Manual 5/2 Way Valves

Maximum Working Pressure:
8 bar





Push/Pull, BSPP

0335	Thread
DKL110-06	1/8"
DKL210-08	1/4"
DKL310-10	3/8"
Tech Sheet 3034	

Maximum Working Pressure:
8 bar






Lever/Lever, BSPP

0335	Thread
DKH210-06	1/8"
DKH310-08	1/4"
DKH310-10	3/8"
Tech Sheet 3041	

Manual 5/3 Way Valves

Maximum Working Pressure:
8 bar






Lever/Lever/Lever, Fully Sealed Mid Position, BSPP

0335	Thread
DKH230-C-06	1/8"
DKH230-C-08	1/4"
DKH330-C-10	3/8"
Tech Sheet 3045	

Maximum Working Pressure:
8 bar






Lever/Spring/Lever, Fully Sealed Mid Position, BSPP

0335	Thread
DKHA230-C-06	1/8"
DKHA230-C-08	1/4"
DKHA330-C-10	3/8"
Tech Sheet 3046	

Manual 5/2 Way Foot Valves

Maximum Working Pressure:
8 bar






Foot/Spring, 1/4" BSPP

0335	Description
DKF210-08	-
DKF210-08G	Guarded
Tech Sheet 3055	

Maximum Working Pressure:
8 bar






Foot/Foot, 1/4" BSPP

0335	Description
DKF210-08L	-
DKF210-08LG	Guarded
Tech Sheet 3055	

Flow Control Valves

Maximum Working Pressure:
0.5 to 10 bar





Uni-directional, BSPP

0335	Thread
K100-06	1/8"
K200-08	1/4"
K300-10	3/8"
K300-15	1/2"
Tech Sheet 3056	

3/2 Hand Slide Valves

Maximum Working Pressure:
10 bar





Hand Slide Valves, BSPP

0335	Thread
KSV-06	1/8"
KSV-08	1/4"
KSV-10	3/8"
KSV-15	1/2"
KSV-20	3/4"
KSV-25	1"
Tech Sheet 3035	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MECHANICAL VALVES, MINIATURE


Technical Data


- Valve fitting port: push-in fitting for pip diameter, 4mm tube or M5 thread
- Fluid: filtered air without lubrication. Lubrication, if used, must be continuous
- Type: with poppet
- Nominal diameter: 2.5mm
- Conductance C: 16.5 Nl/min – bar
- Critical ratio b: 0.003 bar/bar
- Flow rate at 6 bar P 0.5 bar: 35 Nl/min
- Flow rate at 6 bar P 1 bar: 60 Nl/min
- Actuation force, plunger at 6 bar: 8N
- Recommended lubricant: ISO and UNI FD22
- Installation: in any position

Operating Temperature Range: 10°C to +60°C

Operating Pressure: 0.5-10 bar

'VME' Roller Valve








4mm Push-in Fittings

9149	Description	Figure
W3501000200	3/2 Way, Normally Closed, Bottom Ported	A
W3501001201	3/2 Way, Normally Closed, Side Ported	B
W3501000201	3/2 Way, Normally Open, Bottom Ported	C
W3501001200	3/2 Way, Normally Open, Side Ported	D

M5 Thread

9149	Description	Figure
W3501000211	3/2 Way, Normally Closed, Bottom Ported	A
W3501001211	3/2 Way, Normally Closed, Side Ported	B
W3501000210	3/2 Way, Normally Open, Bottom Ported	C
W3501001210	3/2 Way, Normally Open, Side Ported	D

'VME' One Way Roller Valve






4mm Push-in Fittings


9149	Description	Figure
W3501000300	3/2 Way, Normally Closed, Bottom Ported	E
W3501001301	3/2 Way, Normally Closed, Side Ported	F

M5 Thread

9149	Description	Figure
W3501000311	3/2 Way, Normally Closed, Bottom Ported	E
W3501001311	3/2 Way, Normally Closed, Side Ported	F

'VME' Plunger Valve








4mm Push-in Fittings

9149	Description	Figure
W3501000101	3/2 Way, Normally Open, Bottom Ported	G
W3501001100	3/2 Way, Normally Open, Side Ported	H
W3501000100	3/2 Way, Normally Closed, Bottom Ported	I
W3501001101	3/2 Way, Normally Closed, Side Ported	J

M5 Thread

9149	Description	Figure
W3501000110	3/2 Way, Normally Open, Bottom Ported	G
W3501001110	3/2 Way, Normally Open, Side Ported	H
W3501000111	3/2 Way, Normally Closed, Bottom Ported	I
W3501001111	3/2 Way, Normally Closed, Side Ported	J

'VME' Panel Mounted Plunger Valve






4mm Push-in Fittings

9149	Description	Figure
W3501000400	3/2 Way, Normally Closed, Bottom Ported	K
W3501001401	3/2 Way, Normally Closed, Side Ported	L

M5 Thread

9149	Description	Figure
W3501000411	3/2 Way, Normally Closed, Bottom Ported	K
W3501001411	3/2 Way, Normally Closed, Side Ported	L

Adaptor Plate





For 'VME' Push Button

9149	Description
0351000050	For Plunger Valves

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


MECHANICAL VALVES

Technical Specification
- Nominal diameter: 5mm
- Flow rate at 6 bar P1Δ bar: 550 Nl/min

Operating Temperature Range:
10°C to +60°C

Operating Pressure:
Direct control version: vacuum to 10 bar
Servo piloted version: 2.5 to 10 bar


3/2 Plunger Valve



G1/8 Ports

9149	Description
7001000100	3/2 G1/8" Normally Closed


5/2 Plunger Valve



G1/8 Ports

9149	Description
7001000110	5/2 G1/8"


3/2 Roller Valve



G1/8 Ports

9149	Description
7001000500	3/2 G1/8" Normally Closed


5/2 Roller Valve



G1/8 Ports

9149	Description
7001000510	5/2 G1/8"


3/2 Unidirectional Lever Valve



G1/8 Ports

9149	Description
7001000600	3/2 G1/8" Normally Closed

5/2 Unidirectional Lever Valve




G1/8 Ports

9149	Description
7001000610	5/2 G1/8"

Fluid-Air Components Ltd

MECHANICAL VALVES

3/2 Sensitive Plunger Valve






G1/8 Ports

9149	Description
7001000200	3/2 G1/8" Normally Closed

5/2 Sensitive Plunger Valve






G1/8 Ports

9149	Description
7001000210	5/2 G1/8"

3/2 Sensitive Roller Lever Valve






G1/8 Ports

9149	Description
7001000400	3/2 G1/8" Normally Closed

5/2 Sensitive Roller Lever Valve






G1/8 Ports

9149	Description
7001000410	5/2 G1/8"

3/2 Sensitive Aerial Valve






G1/8 Ports

9149	Description
7001000700	3/2 G1/8" Normally Closed

5/2 Sensitive Aerial Valve






G1/8 Ports

9149	Description
7001000710	5/2 G1/8"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MECHANICAL VALVES

3/2 Plunger Valve for Manual Actuator






G1/8 Ports

9149	Description
7010001800	3/2 G1/8" Normally Closed

3/2 Roller Lever Valve






Swing Type G1/8 Ports

9149	Description
7001000900	3/2 G1/8" Ports Spring Return

5/2 Plunger Valve for Manual Actuator






G1/8 Ports

9149	Description
7010001900	5/2 G1/8"

5/2 Roller Lever Valve






Swing Type G1/8 Ports

9149	Description
7001000910	5/2 G1/8" Ports Spring Return

Adaptor Plate




For VME Push Button


9149	Description
0351000050	For Plunger Valves

Fluid-Air Components Ltd

HAND VALVES

3/2 Push/Pull Valve







G1/8 Ports

9149	Description
7010001200	3/2 NC Spring Return, G1/8"
7010001300	3/2 NC Bistable, G1/8"

5/2 Push/Pull Valve







G1/8 Ports

9149	Description
7010001500	5/2 Spring Return, G1/8"
7010001600	5/2 Bistable, G1/8"

3/2 Top Lever Valve







G1/8 Ports

9149	Description
7010001400	3/2 Bistable, G1/8"

3/2 Top Lever Valve






G1/8 Ports

9149	Description
7020001400	3/2 Bistable, G1/4"

5/2 Top Lever Valve






G1/8 Ports

9149	Description
7010001700	5/2 Bistable, G1/8"

5/2 Top Lever Valve






G1/8 Ports

9149	Description
7020001700	5/2 Bistable, G1/4"

Fluid-Air Components Ltd

HAND VALVES


3/2 Lever Valve, 90º



G1/8 Ports

9149	Description
7010000100	3/2 NC Spring Return, G1/8"
7010000200	3/2 Bistable, G1/8"


3/2 Lever Valve, 90º



G1/4 Ports

9149	Description
7020000100	3/2 NC Spring Return, G1/4"
7020000200	3/2 Bistable, G1/4"


3/2 Lever Valve, 90º



G1/2 Ports

9149	Description
7030000100	3/2 NC Spring Return, G1/2"
7030000200	3/2 Bistable, G1/2"


5/2 Lever Valve, 90º



G1/8 Ports

9149	Description
7010000300	5/2 Spring Return, G1/8"
7010000400	5/2 Bistable, G1/8"


5/2 Lever Valve, 90º



G1/4 Ports

9149	Description
7020000300	5/2 Spring Return, G1/4"
7020000400	5/2 Bistable, G1/4"

5/2 Lever Valve, 90º




G1/2 Ports

9149	Description
7030000300	5/2 Spring Return, G1/2"
7030000400	5/2 Bistable, G1/2"

Fluid-Air Components Ltd

HAND VALVES


5/3 Lever Valve, Closed Centres



G1/4 Ports

9149	Description
7020001000	5/3 CC Monostable, G1/4"
7020000500	5/3 CC Bistable, G1/4"


5/3 Lever Valve, Closed Centres



G1/2 Ports

9149	Description
7030001000	5/3 CC Monostable, G1/2"
7030000500	5/3 CC Bistable, G1/2"


5/3 Lever Valve, Open Centres



G1/4 Ports

9149	Description
7020000900	5/3 OC Monostable, G1/4"
7020000600	5/3 OC Bistable, G1/4"


5/3 Lever Valve, Open Centres



G1/2 Ports

9149	Description
7030000900	5/3 CC Monostable, G1/2"
7030000600	5/3 CC Bistable, G1/2"


5/3 Lever Valve, Pressurised Centres



G1/4 Ports

9149	Description
7020001100	5/3 PC Monostable, G1/4"
7020000700	5/3 PC Bistable, G1/4"

5/3 Lever Valve, Pressurised Centres



G1/2 Ports

9149	Description
7030001100	5/3 PC Monostable, G1/2"
7030000700	5/3 PC Bistable, G1/2"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MECHANICALLY & MANUALLY ACTUATED

M/1553 In-line

- Extremely compact
- Extensive range of electrical style operating heads
- Very light operating forces
- Particularly suitable for control panels

Working Temperature:
-20°C to +80°C

Working Pressure:
-0,9 to 10 bar

Medium:
Compressed air, filtered, lubricated and non-lubricate

Panel Mounting:
Hole size Ø 22 mm thickness 5 mm

Flow: 59 L/min


Body: Plastic

Roller Operator: Plastic

Plunger: Brass

Seals: Nitrile





Mechanical

0036	Thread	Function	Actuation
M/1553/14	M5	3/2	Plunger/Spring
M/1553/8	M5	3/2	Roller/Spring
Tech Sheet 10530			

T-Lockouts

- Fully isolates supply pressure
- Lockable
- Rapid exhaust
- Ideal for isolating supply lines during maintenance and servicing
- High flo



CR14, BSPP

0036	BSPP Thread
CR143B	3/8"
CR143C	1/2"
CR144A	3/4" (1" body)
Tech Sheet 20742	

Two-Hand Control Unit

Working Temperature:
+5°C to +40°C

Working Pressure:
3 to 8 bar



XSHC04

0036
XSHC04
Tech Sheet 1346

S/666, S/667 In-line

- Poppet design – high flow with compact size
- Extensive range of mechanical and manual operators
- Long established design – proven reliability
- Normally open and normally closed models

Working Temperature:
-20°C to +80°C

Working Pressure:
2-10 bar

Medium:
Compressed air, filtered lubricated and non-lubricated


Panel Mounting:
Hole size Ø 29 mm
(Ø 16 mm lever valves)
Thickness 9,5 mm
(4 mm lever valves)

Flow:
N/C: 197 L/min
N/O: 177 L/min

Body:
Die-cast zinc alloy

Piston: Plastic

Seals: Nitrile





Mechanical

0036	Thread	Function	Actuation
S/666/14	G1/8	3/2 N/C	Plunger/Spring
S/667/14	G1/8	3/2 N/O	Plunger/Spring
S/666/8	G1/8	3/2 N/C	Roller/Spring
S/667/8	G1/8	3/2 N/O	Roller/Spring
S/666/108	G1/8	3/2 N/C	Variable Roller/Spring
Tech Sheet 10531			

Manual

0036	Thread	Function	Actuation	Colour
S/666/1	G1/8	3/2 N/C	Button/Spring	-
PS/666/1/R	G1/8	3/2 N/C	Button (Panel Mounting)/Spring	Red
PS/666/1/G	G1/8	3/2 N/C	Button (Panel Mounting)/Spring	Green
PS/666/1/N	G1/8	3/2 N/C	Button (Panel Mounting)/Spring	Black
S/666/6	G1/8	3/2 N/C	Lever/Spring (Panel Mounting)	-
S/666/7	G1/8	3/2 N/C	Lever/Lever (Panel Mounting)	-
S/666/117	G1/8	3/2 N/C	Lever (Long)/Lever (Panel Mounting)	-
Tech Sheet 10531				

Fluid-Air Components Ltd

SUPER X ACTUATED IN-LINE

NORGREN

Mechanically & Manually

- Wide range of operators
- Suitable for multi-directional flow and dual supply applications
- High flow capacit
- Lightweight corrosion resistant materials

Working Temperature:
0°C to +70°C

Maximum Working Pressure:
10 bar

Medium:
Compressed air, filtered, lubricated and non-lubricated

Flow:


Size	L/min
G1/8	335
G1/4	965

Body:
Die-cast aluminium alloy

End Cover:
Aluminium or glass filled nylo

Seals:
Nitrile rubber





Mechanical

0036	Thread	Function	Actuation
03040002	G1/8	3/2	Plunger/Spring
03040202	G1/8	3/2	Roller/Spring
03029302	G1/8	3/2	Roller Lever (Heavy-duty)/Spring
03029402	G1/8	3/2	One Way Trip (Heavy-duty)/Spring
03043202	G1/8	3/2	Antenna Valve
X3044002	G1/8	5/2	Plunger/Spring
X3045102	G1/8	5/2	Roller Lever/Spring
X3039302	G1/8	5/2	Roller Lever (Heavy-duty)/Spring
X3046302	G1/8	5/2	Sensitive Roller Lever/Spring
X3047202	G1/8	5/2	Antenna/Spring
03060002	G1/4	3/2	Plunger/Spring
03060202	G1/4	3/2	Roller/Spring
03061102	G1/4	3/2	Roller Lever/Spring
X3064002	G1/4	5/2	Plunger/Spring
X3064202	G1/4	5/2	Roller/Spring
X3065102	G1/4	5/2	Roller Lever/Spring
Tech Sheet 10582			


Manual

0036	Thread	Function	Actuation	Colour
03040402	G1/8	3/2	Button/Spring	Black
03040502	G1/8	3/2	Button/Spring	Green
03040602	G1/8	3/2	Button/Spring	Red
03036602	G1/8	3/2	Button Palm/Spring	Red
03036702	G1/8	3/2	Button Palm/Spring	Green
03036802	G1/8	3/2	Button Palm/Spring	Black
03041402	G1/8	3/2	Button (Shrouded)/Spring	Black
03041502	G1/8	3/2	Button (Shrouded)/Spring	Green
03041602	G1/8	3/2	Button (Shrouded)/Spring	Red
03040802	G1/8	3/2	Button/Pilot	Black
03043802	G1/8	3/2	Lever/Spring	Black
03042602	G1/8	3/2	Lever Knob/Spring	Black
03043702	G1/8	3/2	Lever/Lever	Black
03040302	G1/8	3/2	Toggle/Toggle	Black
03042502	G1/8	3/2	Knob/Knob	Black
X3045502	G1/8	5/2	Button (Shrouded)/Spring	Green
X3044802	G1/8	5/2	Button/Pilot	Black
X3046502	G1/8	5/2	Knob, Push/Knob, Pull	Black
X3047802	G1/8	5/2	Lever/Spring	Black
X3044302	G1/8	5/2	Toggle/Toggle	Black
X3047702	G1/8	5/2	Lever/Lever	Black
X3046402	G1/8	5/2	Knob/Knob or Pilot	Black
X3048202	G1/8	5/2	Pedal/Spring	Black
X3048402	G1/8	5/2	Pedal/Pedal	Black
X3343802	G1/8	5/3	Lever/Spring/Lever	Black
X3347802	G1/8	5/3	Level/Spring/Lever	Black
X3343702	G1/8	5/3	Lever/Lever/Lever	Black
03060402	G1/4	3/2	Button/Spring	Black
03063802	G1/4	3/2	Lever/Spring	Black
03063702	G1/4	3/2	Lever/Lever	Black
03062502	G1/4	3/2	Knob/Knob	Black
X3064402	G1/4	5/2	Button/Spring	Black
X3067802	G1/4	5/2	Lever/Spring	Black
X3067702	G1/4	5/2	Lever/Lever	Black
X3066502	G1/4	5/2	Knob/Knob	Black
X3068202	G1/4	5/2	Pedal/Spring	Black
X3068402	G1/4	5/2	Pedal/Pedal	Black
X3363802	G1/4	5/3	Lever/Spring/Lever	Black
X3367802	G1/4	5/3	Lever/Spring/Lever	Black
X3363702	G1/4	5/3	Lever/Lever/Lever	Black
Tech Sheet 10582				

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


DIRECTIONAL CONTROL VALVES

Series 2, Mechanically Operated Mini-Valves




3/2 Plunger Type Valves

0158	Thread
235 945	M5
234 945	Ø4mm
Tech Sheet 1850	




3/2 Panel Mounted Plunger Type Valves

0158	Thread
235 985	M5
234 985	Ø4mm
Tech Sheet 1850	



3/2 Roller Lever Type Valves

0158	Thread
235 955	M5
234 955	Ø4mm
Tech Sheet 1850	



3/2 One Way Trip Type Valves

0158	Thread
235 965	M5
234 965	Ø4mm
Tech Sheet 1850	

Series 3, Mechanically Operated Valves




G1/8", 3/2 Plunger Type Valve

0158	Thread
338 945	G1/8"
Tech Sheet 1851	




G1/8", 5/2 Roller Lever Type Valve

0158	Thread
358 955	G1/8"
Tech Sheet 1851	



G1/8", 5/2 Plunger Type Valve

0158	Thread
358 945	G1/8"
Tech Sheet 1851	



G1/8", 3/2 Roller Lever One Way Trip Type Valve

0158	Thread
338 965	G1/8"
Tech Sheet 1851	



G1/8", 3/2 Roller Lever Type Valve

0158	Thread
338 955	G1/8"
Tech Sheet 1851	



G1/8", 5/2 Roller Lever One Way Trip Type Valve

0158	Thread
358 965	G1/8"
Tech Sheet 1851	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 2, Manually Operated Console Mini-Valves




3/2 Push Button Spring Return Valves

0158	Thread
235 895	M5
234 895	Ø4mm
Tech Sheet 1852	



3/2 Stable Palm Switch

0158	Thread
235 970	M5
234 970	Ø4mm
Tech Sheet 1852	




5/3 3 Position Selector Switch

0158	Thread
285 870	M5
284 870	Ø4mm
Tech Sheet 1852	




3/2 Palm Switch Spring Return Valves

0158	Thread
235 975	M5
234 975	Ø4mm
Tech Sheet 1852	




3/2 Joystick Valve

0158	Thread
235 905	M5
234 905	Ø4mm
Tech Sheet 1852	



3/2 3 Key Switch

0158	Thread
235 904	M5
234 904	Ø4mm
Tech Sheet 1852	




3/2 Twist Lock Palm Switch

0158	Thread
235 972	M5
234 972	Ø4mm
Tech Sheet 1852	



3/2 2 Position Selector Switch

0158	Thread
235 990	M5
234 990	Ø4mm
Tech Sheet 1852	




3/2 Foot Operated Valves

0158	Thread
235 925	M5
234 925	Ø4mm
Tech Sheet 1852	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES


Series 3, 4 & VMS Manually Operated Valves





G1/8", 3/2 NC Switch


0158	Thread
338 990	G1/8"
Tech Sheet 10309	





G1/8", 5/2 Switch


0158	Thread
358 990	G1/8"
Tech Sheet 10309	





G1/8", 3/2 Push Button


0158	Thread	Colour
338 895	G1/8"	Black
338 896	G1/8"	Green
338 897	G1/8"	Red
Tech Sheet 10309		





G1/8", 5/2 Push Button


0158	Thread	Colour
358 895	G1/8"	Black
358 896	G1/8"	Green
358 897	G1/8"	Red
Tech Sheet 10309		





G1/8", 3/2 Palm Switch


0158	Thread	Colour
338 975	G1/8"	Black
338 976	G1/8"	Green
338 977	G1/8"	Red
Tech Sheet 10309		





G1/8", 5/2 Palm Switch


0158	Thread	Colour
358 975	G1/8"	Black
358 976	G1/8"	Green
358 977	G1/8"	Red
Tech Sheet 10309		






G1/8", 3/2 Push/Pull Knob Bistable

0158	Thread
338 910	G1/8"
Tech Sheet 10309	



G1/8", 3/2 Push Knob Monostable


0158	Thread
338 915	G1/8"
Tech Sheet 10309	






G1/8", 5/2 Push/Pull Knob Bistable

0158	Thread
358 910	G1/8"
Tech Sheet 10309	



G1/8", 5/2 Push Knob Monostable


0158	Thread
358 915	G1/8"
Tech Sheet 10309	





G1/8", 3/2 Lever Valve Bistable

0158	Thread
338 900	G1/8"
Tech Sheet 10309	




G1/8", 3/2 Lever Valve Monostable

0158	Thread
338 905	G1/8"
Tech Sheet 10309	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 3, 4 & VMS Manually Operated Valves



G1/8", 5/2 Lever Valve Bistable

0158	Thread
358 900	G1/8"
Tech Sheet 10309	




G1/8", 5/2 Lever Valve Monostable

0158	Thread
358 905	G1/8"
Tech Sheet 10309	



G1/8", 5/3 CC Lever Valve Bistable

0158	Thread
368 900	G1/8"
Tech Sheet 10309	




G1/8", 5/3 CC Lever Valve Monostable

0158	Thread
368 905	G1/8"
Tech Sheet 10309	




G1/8", 5/3 CO Lever Valve Bistable

0158	Thread
378 900	G1/8"
Tech Sheet 10309	




G1/8", 5/3 CO Lever Valve Monostable

0158	Thread
378 905	G1/8"
Tech Sheet 10309	




G1/4", 3/2 Push/Pull Knob Bistable

0158	Thread
434 910	G1/4"
Tech Sheet 10309	




G1/4", 3/2 Push Knob Monostable

0158	Thread
434 915	G1/4"
Tech Sheet 10309	



G1/4", 5/2 Push/Pull Knob Bistable

0158	Thread
454 910	G1/4"
Tech Sheet 10309	




G1/4", 5/2 Push Knob Monostable

0158	Thread
454 915	G1/4"
Tech Sheet 10309	



G1/4", 3/2 Lever Bistable

0158	Thread
434 900	G1/4"
Tech Sheet 10309	




G1/4", 3/2 Lever Monostable

0158	Thread
434 905	G1/4"
Tech Sheet 10309	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 3, 4 & VMS Manually Operated Valves




G1/4", 5/2 Lever Valve Bistable

0158	Thread
454 900	G1/4"
Tech Sheet 10309	




G1/4", 5/2 Lever Valve Monostable

0158	Thread
454 905	G1/4"
Tech Sheet 10309	



G1/4", 5/3 CC Lever Valve Bistable

0158	Thread
464 900	G1/4"
Tech Sheet 10309	




G1/4", 5/3 CC Lever Valve Monostable

0158	Thread
464 905	G1/4"
Tech Sheet 10309	




G1/4", 5/3 CO Lever Valve Bistable

0158	Thread
474 900	G1/4"
Tech Sheet 10309	




G1/4", 5/3 CO Lever Valve Monostable

0158	Thread
474 905	G1/4"
Tech Sheet 10309	



G1/8", 3/2 Joystick Lever Valve

0158	Thread
234 9054	G1/8"
Tech Sheet 10309	



Slide Valves

0158	Thread
VMS 105 M5	M5
VMS 118 1/8	1/8"
VMS 114 1/4	1/4"
VMS 138 3/8	3/8"
VMS 112 1/2	1/2"
VMS 134 3/4	3/4"
Tech Sheet 10309	

Fluid-Air Components Ltd


PNEUMATIC VALVES & ACCESSORIES

Parker Mechanical Valves




Push Button & Valve Spring Return 4mm Push-in

0678	Flow l/min	Description
PXB-B4131BA2	240	Black with 1 NC Valve




Mushroom Head Push Button 4mm Push-in

0678	Flow l/min	Description
PXB-B4131BC2	240	Black - Spring Return - with 1 NC Valve



Selector Switch & Valve 4mm Push-in

0678	Flow l/min	Description
PXB-B4131BD2	240	Black - 2 Positions - with 1 NC Valve



Latching Push Button 4mm Push-in

0678	Flow l/min	Description
PXB-B4131BT4	240	Red - Latching - with 1 NC Valve

stainless steel



For **Parker Angle Seat Valves**
see page **1051**

Fluid-Air Components Ltd


PNEUMATIC VALVES & ACCESSORIES

Mechanical Valves



Push Buttons & Valves (Separate Components)

0681	Description
PXB-B4931	Switch Valve - Flow 240 l/min NO/NC



Micro Plunger & Roller Limit Valves 4mm

0681	Actuator	Return
PXC-M601A110	Steel Plunger	Spring Return
PXC-M121	Plastic Roller	Spring Return
PXC-M521	Plastic Roller	Spring Return



B43 / B53 Lever Valves G1/8" - G1/4"

0681	Type	Actuator	Return	Thread BSPP
B43003ES	3-2	Palm Lever	Spring Return	1/8"
B43003LS	3-2	Lock Down Lever	Spring Return	1/8"
B43004LS	5-2	Lock Down Lever	Spring Return	1/8"
B53003LT	3-2	Lever	Lever	1/4"
B53004LT	5-2	Lever	Lever	1/4"



B43 / B53 Valves 3/2 & 5/2 Button Operated G1/8" - G1/4"

0681	Type	Actuator	Return	Thread BSPP
B43003BXS	3-2	Button	Spring	1/8"
B43003HXS	3-2	Button	Button	1/8"
B53003HX	3-2	Button	Button	1/4"
B53004HXS	5-2	Button	Spring	1/4"
B43004HXS	5-2	Button	Button	1/8"



B43/B53 3/2 Trip Valves G1/8" - G1/4"

0681	Type	Actuator	Return	Thread BSPP
B43003CS	3-2	Plunger	Spring Return	1/8"
B43003RS	3-2	Roller Lever	Spring Return	1/8"
B43003RTS	3-2	One Way Roller Trip	Spring Return	1/8"



B53 Spool Valve Panel Mounting Kit

0681	Description
M53004L-10A	B53 Series Panel Mounting Kit



B43 / B53 Foot Pedal 3/2 & 5/2 Valves G1/8" - G1/4"

0681	Type	Actuator	Return	Thread BSPP
B43003FS	3-2	Foot Pedal	Spring Return	1/8"
B53003FS	3-2	Foot Pedal	Spring Return	1/4"
B53004FS	3-2	Foot Pedal	Spring Return	1/4"



Heavy-duty Lever 3/2 Poppet Valve G1/2"

0681	Actuator	Return	Thread BSPP
B203L	Lever	Lever	1/2"

Fluid-Air Components Ltd

PNEUMATIC VALVES & ACCESSORIES

Mechanical Valves



Viking Xtreme 3/2 & 5/2 Lever Operated G1/8" G1/4" & G1/2"

0681	Type	Actuator	Return	Thread BSPP
P2LAX511VV	5-2	Lever	Lever	1/8"
P2LAX511VS	5-2	Lever	Spring	1/8"
P2LDX514VS	5-2	Lever	Spring	1/2"



Viking Xtreme Valve 5/3 Lever Operated G1/4" & G1/2"

0681	Actuator	Mid Position	Return	Thread BSPP
P2LBX61222	Lever	Closed	Lever	1/4"
P2LBX61211	Lever	Closed	Spring	1/4"
P2LBX81211	Lever	Vented	Spring	1/4"

Pilot & Solenoid Valves



B3 Series 1/8" Valves Pilot & Solenoid

0681	Type	Actuator	Return	Voltage (if applicable)
B345000XXH	5-2	Air	Air	N/A

For **Parker Solenoid Valves**
see pages **1036-1038**



Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

Series 104 Miniature Manual & Mechanical, 4mm Push-in Connectors



Handle complete with Integrated Valve, Metric 3/2 - 4mm

0110	Function
105.32.6.40C	Normally Closed



Tappet/Spring Return, Metric

0110	Function
104.32.0.1.LC	Normally Closed
104.32.0.1.PA	Normally Open



Lever Plastic Roller/Spring Return, Metric

0110	Function
104.32.2.1.LA	Normally Open
104.32.2.1.LC	Normally Closed
104.32.2.1.PA	Normally Open



Lever Unidirectional - Spring Return, Metric

0110	Function
104.32.3.1.PC	Normally Closed



Lever Metal Roller Bearing - Spring Return, Metric

0110	Function
104.32.2.1/1.LA	Normally Closed



Raised Push Button/Spring Return Side Connection, Metric

0110	Colour	Function
104.32.6.23/1.LC	Red	Normally Closed
104.32.6.23/3.LC	Green	Normally Closed



Raised Push Button/Spring Return Rear Connection, Metric

0110	Colour	Function
104.32.6.23/3.PC	Green	Normally Closed
104.32.6.23/4.PC	Yellow	Normally Closed



Palm Push Button Locking, Metric

0110	Colour	Function
104.32.6.25.PA	Red	Normally Open



Flush Push Button/Spring Return Side Connection, Metric

0110	Colour	Function
104.32.6.22/3.LC	Green	Normally Closed

Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

Series 104 Miniature Manual & Mechanical, 4mm Push-in Connectors



Flush Push Button/Spring Return Rear Connection, Metric

0110	Colour	Function
104.32.6.22/2.PC	Black	Normally Open



Raised Push Button/Step/Step, Side Connection, Metric

0110	Thread	Colour	Function
104.32.6.31.LA	Clear	Clear	Normally Open



Key Switch, Rear Connection

0110	Function
104.32.6.28.PC	Normally Closed



2/2 Switch Short Lever, Rear Connection

0110	Function
104.22.6.30.PC	Normally Closed



Switch Long Lever, Side Connection

0110	Function
104.32.6.27.LC	Normally Closed



Switch Short Lever, Side Connection

0110	Function
104.32.6.30.LC	Normally Closed
104.32.6.30.PC	Normally Closed

PNEUMAX

For **Air Preparation**
see pages **700-702**



FAC
Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

Series Techno Manual & Mechanical



Tappet/Spring Return, BSPP

0110	Thread	Function
T228.32.0.1	1/8"	Normally Closed



Push Button/Spring Return, BSPP

0110	Thread	Function
T224.32.8.1	1/4"	Normally Closed



2 Position Switch Short Lever

0110	Thread	Function
T228.32.6.27	1/8"	Normally Closed



Lever Plastic Roller/Spring Return, BSPP

0110	Thread	Function
T228.32.2.1	1/8"	Normally Closed



Palm Push Button Locking, BSPP

0110	Thread	Function
T228.32.6.25	1/8"	Normally Closed



Lateral Lever

0110	Thread	Colour	Actuation
T228.32.9/2	1/8"	Black	Lever/Lever



Lever Metal Roller/Spring Return, BSPP

0110	Thread	Function
T228.32.2.1/2	1/8"	Normally Closed



Flush 30mm Push Button/ Spring Return, BSPP

0110	Thread	Colour
T228.32.6.1/2	1/8"	Black
T228.32.6.1/3	1/8"	Green



Lateral Lever

0110	Thread	Colour	Actuation
T224.32.9.1/2	1/4"	Black	Lever/Spring
T224.32.9/2	1/4"	Black	Lever/Lever
T224.32.9/3	1/4"	Green	Lever/Lever



Lever Metal Roller Bearing/ Spring Return, BSPP

0110	Thread	Function
T228.32.2.1/1	1/8"	Normally Closed



2 Position Key Switch, BSPP

0110	Thread
T228.32.6.28	1/8"

Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

PNEUMAX

Series 200 Manual & Mechanical

Tappet/Spring Return, BSPP



0110	Thread	Description	Function
228.32.0.1	1/8"	-	Normally Closed
228.32.1.1	1/8"	Panel Mount	Normally Closed

Lever Plastic Roller/Spring Return, BSPP



0110	Thread	Function
228.32.2.1	1/8"	Normally Closed

Lever Metal Roller/Spring Return, BSPP



0110	Thread	Function
228.32.2.1/2	1/8"	Normally Closed

Lever Metal Roller Bearing/ Spring Return, BSPP



0110	Thread	Function
228.32.2.1/1	1/8"	Normally Closed

Lever Roller Bidirectional/ Spring Return, BSPP



0110	Thread	Function
228.32.4.1	1/8"	Normally Closed

Push Button/Spring Return, BSPP



0110	Thread	Function
224.32.8.1	1/8"	Normally Closed

Palm Push Button Locking, BSPP



0110	Thread	Function
228.32.6.25	1/8"	Normally Closed

Flush 30mm Push Button/ Spring Return, BSPP



0110	Thread	Function
228.32.6.1/2	1/8"	Normally Closed
228.32.6.1/1	1/8"	Normally Closed
228.32.6.1/3	1/8"	Normally Closed

Sensitive 30mm Push Button/ Differential, BSPP



0110	Thread	Colour	Function
228.32.6.13/1	1/8"	Red	Normally Closed
228.32.6.13/3	1/8"	Green	Normally Closed

2 Position Key Switch, BSPP



0110	Thread	Function
228.32.6.28	1/8"	Normally Closed

Switch Short Lever, BSPP



0110	Thread	Function
228.32.6.27	1/8"	

Lever



0110	Thread	Colour	Actuation	Function
228.32.9.1/2	1/8"	Black	Spring Return	Normally Closed
228.32.9/2	1/8"	Black	Stable 2 Position	Normally Closed

Lever, BSPP



0110	Thread	Colour	Actuation	Function
224.32.9.1/2	1/4"	Black	Spring Return	Normally Closed
224.32.9.1/1	1/4"	Red	Spring Return	Normally Closed
224.32.9.2	1/4"	Black	Stable 2 Position	Normally Closed
224.32.9.3	1/4"	Green	Stable 2 Position	Normally Closed

Lever, BSPP



0110	Thread	Actuation
212.32.9.1	1/2"	Spring Return

Guarded Foot Valve



0110	Thread	Actuation	Function
228.32.10.2/1	1/8"	Foot/Spring	Normally Closed
228.32.10/1	1/8"	Foot/Foot	Normally Closed

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

5/2 PNEUMATIC VALVES

PNEUMAX

Series 104 Minature Manual & Mechanical, 4mm Push-in Connectors



Raised Push Button Step/Step, Metric

0110	Colour
104.52.6.31.L	Clear



Palm Push Button Locking, Metric

0110	Colour
104.52.6.25.L	Red



Flush Push Button/Spring Return/ Side Connection, Metric

0110	Colour
104.52.6.22/1.L	Red



Flush Push Button/Spring Return/ Rear Connection, Metric

0110	Colour
104.52.6.22/2.P	Black



Key Switch/Side Connection, Metric

0110
104.52.6.28.L



Switch Short Lever/ Side Connection, Metric

0110
104.52.6.30.L

Switch Short Lever/ Rear Connection, Metric


0110
104.52.6.30.P



Switch Long Lever/Rear Connection, Metric

0110
104.52.6.27.P

FT PRO



For **Nylon Tube**
see pages **913-917**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

5/2 PNEUMATIC VALVES

Series Techno Manual & Mechanical



Tappet /Spring Return/Panel Mount, BSPP

0110	Thread
T228.52.1.1	1/8"



Key Switch, BSPP

0110	Thread
T228.52.6.28	1/8"



Lateral Lever, BSPP

0110	Thread	Colour	Function
T228.52.9.1/3	1/8"	Green	Lever/Spring
T228.52.9/2	1/8"	Black	Lever/Lever
T228.52.9/1	1/8"	Red	Lever/Lever



Lever Metal Roller/Spring Return, BSPP

0110	Thread
T228.52.2.1/2	1/8"



Switch Short Lever, BSPP

0110	Thread
T228.52.6.27	1/8"



Lateral Lever, BSPP

0110	Thread	Colour	Description
T224.52.9.1/2	1/4"	Black	Lever/Spring
T224.52.9/2	1/4"	Black	Lever/Lever
T224.52.9/1	1/4"	Red	Lever/Lever
T224.52.9/3	1/4"	Green	Lever/Lever



Palm Push Button Locking, BSPP

0110	Thread
T228.52.6.25	1/8"



Front Facing Lever, BSPP

0110	Thread	Colour
T228.52.55/2	1/8"	Black



For **Pneumax Compact Cylinders**
see page **536**

Fluid-Air Components Ltd

5/2 PNEUMATIC VALVES

Series 200 Manual & Mechanical

Tappet/Spring Return/Panel Mount, BSPP



0110	Thread
228.52.1.1	1/8"

Lever Plastic Roller/Spring Return, BSPP



0110	Thread
228.52.2.1	1/8"

Lever Metal Roller/Spring Return, BSPP



0110	Thread
228.52.2.1/2	1/8"

Lever Metal Roller Bearing/ Spring Return, BSPP



0110	Thread
228.52.2.1/1	1/8"

Lever Roller Bidirectional/ Spring Return, BSPP



0110	Thread
228.52.4.1	1/8"

Push Button/Spring Return, BSPP



0110	Thread
224.52.8.1	1/4"

Palm Push Button Locking, BSPP



0110	Thread	Colour
228.52.6.25	1/8"	Red

2 Position Switch, Short Lever, BSPP



0110	Thread
228.52.6.27	1/8"

2 Position Key Switch, BSPP



0110	Thread
228.52.6.28	1/8"

2 Position Front Facing Lever, BSPP



0110	Thread	Colour
228.52.55/2	1/8"	Black
228.52.55/1	1/8"	Red
228.52.55/3	1/8"	Green

2 Position Lever, BSPP



0110	Thread	Colour
228.52.9/2	1/8"	Black

Lever/Spring Return, BSPP



0110	Thread	Colour
224.52.9.1/2	1/4"	Black
224.52.9.1/1	1/4"	Red
224.52.9.1/3	1/4"	Green

2 Position Locking Lever, BSPP



0110	Thread
224.52.9.2	1/4"

2 Position Stable Lever, BSPP



0110	Thread
212.52.9	1/2"

Guarded Foot Valve/ Spring Return, BSPP



0110	Thread
228.52.10.1/1	1/8"
214.52.10.1/1	1/4"

Miniaturised Foot Valve/Spring, BSPP



0110	Thread
228.52.10.1P	1/8"

Foot Valve/Spring Return, BSPP



0110	Thread
228.52.10.1	1/8"

Fluid-Air Components Ltd

5/3 PNEUMATIC VALVES

PNEUMAX

Eco 22 Solenoid Valves



Lever/Stable 3 Position, BSPP

0110	Thread	Colour	Function
T228.53.31.9/2	1/8"	Black	Closed Centre
T228.53.32.9/2	1/8"	Black	Open Centre



Lever/Spring To Centre, BSPP

0110	Thread	Colour	Description
T228.53.32.9.1/2	1/8"	Black	Open Centre
T228.53.32.9.1/1	1/8"	Red	Open Centre



Lever/Spring To Centre, BSPP

0110	Thread	Colour	Function
T224.53.31.9.1/2	1/8"	Black	Closed Centre
T224.53.32.9.1/2	1/8"	Black	Open Centre
T224.53.31.9.1/3	1/8"	Green	Closed Centre



Lever/Stable 3 Position, BSPP

0110	Thread	Colour	Function
T224.53.31.9/2	1/8"	Black	Closed Centre
T224.53.32.9/2	1/8"	Black	Open Centre
T224.53.31.9/3	1/8"	Green	Closed Centre

Series 200 Manual & Mechanical



Lever/Spring To Centre, BSPP

0110	Thread	Colour	Function
228.53.31.9.1/2	1/8"	Black	Closed Centre
228.53.32.9.1/2	1/8"	Black	Open Centre
228.53.31.9.1/1	1/8"	Red	Closed Centre



Lever/Stable 3 Position, BPP

0110	Thread	Colour	Function
228.53.31.9/2	1/8"	Black	Closed Centre
228.53.31.9/1	1/8"	Red	Closed Centre



Lever/Spring To Centre, BSPP

0110	Thread	Colour	Function
224.53.31.9.1/2	1/4"	Black	Closed Centre
224.53.31.9.1/3	1/4"	Green	Closed Centre



Lever/3 Position Locking, BSPP

0110	Thread	Function
224.53.31.9.2	1/4"	Closed Centre



Lever, BSPP

0110	Description	Thread	Function
212.53.31.9.1	Spring/Lever	1/2"	Closed Centre
212.53.31.9	Lever/ Lever	1/2"	Closed Centre



Foot Valve/Spring To Centre, BSPP

0110	Thread	Function
228.53.32.10.1	1/8"	Open Centre

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SOLENOID VALVES

Medium: Clean compressed air. Filtered (40µm) and lubricated
Body Material: Aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Working Pressure: 1.5 to 8 bar

2 Year Warranty

Solenoid 3/2 Way Valves





Direct Acting, Normally Closed, M5

0335	Voltage
KCV1-M5-B	24V DC
KCV1-M5-C	110V 50/60Hz
KCV1-M5-A	220V 50/60Hz
Tech Sheet 3107	





Direct Acting, Normally Closed, 1/8" BSPP

0335	Voltage
KCV1-06-B	24V DC
KCV1-06-C	110V 50/60Hz
KCV1-06-A	220V 50/60Hz
Tech Sheet 3107	





Solenoid/Spring, Normally Open, BSPP

0335	Thread
CKV210-06-NO	1/8"
CKV210-08-NO	1/4"
CKV310-10-NO	3/8"
Tech Sheet 3039	





Solenoid/Spring, Normally Closed, BSPP

0335	Thread
CKV210-06-NC	1/8"
CKV210-08-NC	1/4"
CKV310-10-NC	3/8"
Tech Sheet 3039	





Solenoid/Solenoid, BSPP

0335	Thread
CKV220-06	1/8"
CKV220-08	1/4"
CKV320-10	3/8"
Tech Sheet 3039	

FTPRO

For **Pre wired moulded DIN Plugs** see page **1043**



Gang Mount Components, to suit KCV Series



Coupling Screws & O-Ring

0335
KCV1-P31
Tech Sheet 3107



Coupling Screws & End Fixing Nuts

0335
KCV1-P30
Tech Sheet 3107



Base Plate

0335
KCV1-P32
Tech Sheet 3107

SOLENOID VALVES

Medium: Clean compressed air. Filtered (40µm) and lubricated
Body Material: Aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Working Pressure: 1.5 to 8 bar

2 Year Warranty

Solenoid 5/2 Way Valves





Solenoid/Spring, BSPP

0335	Thread
DKV210-06	1/8"
DKV210-08	1/4"
DKV310-10	3/8"
DKV410-15	1/2"
Tech Sheet 3040	





Solenoid/Solenoid, BSPP

0335	Thread
DKV220-06	1/8"
DKV220-08	1/4"
DKV320-10	3/8"
DKV420-15	1/2"
Tech Sheet 3040	

Solenoid 5/3 Way Valves





Solenoid/Solenoid, Fully Sealed Mid Position, BSPP


0335	Thread
DKV230C-06	1/8"
DKV230C-08	1/4"
DKV330C-10	3/8"
DKV430C-15	1/2"
Tech Sheet 3040	





Solenoid/Solenoid, Centre Open Pressurised, BSPP

0335	Thread
DKV230P-06	1/8"
DKV230P-08	1/4"
DKV330P-10	3/8"
DKV430P-15	1/2"
Tech Sheet 3040	





Solenoid/Solenoid, Supply Sealed Mid Position, BSPP


0335	Thread
DKV230E-06	1/8"
DKV230E-08	1/4"
DKV330E-10	3/8"
DKV430E-15	1/2"
Tech Sheet 3040	

For **Silencers** see page **631**



Fluid-Air Components Ltd

Valve Manifolds



Suitable for use with 5/2 and 5/3 Valves only

Please contact our Technical Department if larger manifolds are required up to 16 stations.

B Series, to suit 1/8" & 1/4" BSPP Valves, 1/4" BSPP Inlet

0335	No. of Stations
B00KM-1F	1
B00KM-2F	2
B00KM-3F	3
B00KM-4F	4
B00KM-5F	5
B00KM-6F	6
B00KM-8F	8
B00KM-10F	10
Tech Sheet 3042	

Please contact our Technical Department if larger manifolds are required up to 12 stations.

C Series, to suit 3/8" BSPP Valves, 3/8" BSPP Inlet

0335	No. of Stations
C00KM-1F	1
C00KM-2F	2
C00KM-3F	3
C00KM-4F	4
C00KM-5F	5
C00KM-6F	6
C00KM-8F	8
C00KM-10F	10
Tech Sheet 3042	

Maximum number of stations available is 8.

D Series, to suit 1/2" BSPP Valves, 1/2" BSPP Inlet

0335	No. of Stations
D00KM-1F	1
D00KM-2F	2
D00KM-3F	3
D00KM-4F	4
D00KM-5F	5
D00KM-6F	6
D00KM-8F	8
Tech Sheet 3042	

Blanking Plates




Single

0335	To Suit
B00KM-B	B Series
C00KM-B	C Series
D00KM-B	D Series
Tech Sheet 3042	

5/2 Namur Solenoid Valves





Solenoid/Spring, BSPP

0335	Thread
DKM310-08	1/4"
DKM310-10	3/8"
Tech Sheet 3043	





Solenoid/Solenoid, BSPP

0335	Thread
DKM320-08	1/4"
DKM320-10	3/8"
Tech Sheet 3043	

Solenoid Coils & Plugs



Coil & LED Connector

0335	Voltage
K-12DC	12V DC
K-24DC	24V DC
K-24AC	24V 50/60Hz
K-110AC	110V 50/60Hz
K-220AC	220V 50/60Hz
Tech Sheet 3044	

FAC Fluid-Air Components Ltd


ef nkl i r oi r p c c c a c c

VALVES

For the full range and more information, please contact one of our sales team.

VUVS UNIVERSAL DIRECTIONAL CONTROL VALVES ★

Features



Product Description

VUVS - L - K - 20 - M32C - A - D - G18 - 1 - C1 - S

- VUVS: Solenoid valve
- L: In-line valve
- K: Piston spool with sealing ring
- 20: Size 20 (21 mm) / 700 l/min / Gx
- M32C: 3/2-way valve, normally open
- A: Pneumatic spring for valve functions M52 and M32
- D: Non-detenting, detenting without accessories
- G18: Thread Gx
- 1: 24 V DC
- C1: Connection pattern type C, to EN 175301
- S: Variants with focused features

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c c a c c


IN-LINE PISTON SPOOL VALVES WITH SEALING RING, VUVS

Ambient Temperature:
-5°C to +50°C

- Flow rate up to 2300 l/min
- In-line valves can be used as individual valves or manifold valves
- Variable pressure zones
- Universal valve, sturdy and durable
- Low-cost, no limitations with regard to performance
- Can be used as individual valves or manifold valves VTUS

In-line Electrical Connection Pattern Type B

Working Pressure:
1.5 to 8 bar






3/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply, Normally Closed

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043217	G1/4"	25	24V DC	VUVS-LK25-M32C-AD-G14-1B2-S
8049880	G3/8"	30	24V DC	VUVS-LK30-M32C-AD-G38-1B2-S
		Tech Sheet 70803		

Working Pressure:
1.5 to 8 bar






5/2 Way Solenoid/Solenoid with Internal Pilot Supply

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043219	G1/4"	25	24V DC	VUVS-LK25-B52-D-G14-1B2-S
8049882	G3/8"	30	24V DC	VUVS-LK30-B52-D-G38-1B2-S
		Tech Sheet 70804		

Working Pressure:
1.5 to 8 bar






5/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043218	G1/4"	25	24V DC	VUVS-LK25-M52-AD-G14-1B2-S
8049881	G3/8"	30	24V DC	VUVS-LK30-M52-AD-G38-1B2-S
		Tech Sheet 70805		

In-line Electrical Connection Pattern Type C

Working Pressure:
1.5 to 8 bar






3/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply, Normally Closed

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043213	G1/8"	20	24V DC	VUVS-LK20-M32C-AD-G18-1C1-S
		Tech Sheet 70806		

Working Pressure:
1.5 to 8 bar






5/2 Way Solenoid/Solenoid with Internal Pilot Supply

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043215	G1/8""	20	24V DC	VUVS-LK20-B52-D-G18-1C1-S
		Tech Sheet 70808		

Working Pressure:
1.5 to 8 bar





5/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply

0009	Thread	Size mm	Voltage	Manufacturer's Code
8043214	G1/8"	20	24V DC	VUVS-LK20-M52-AD-G18-1C1-S
		Tech Sheet 70807		

Fluid-Air Components Ltd

IN-LINE PISTON SPOOL VALVES, VUVS

FESTO

Ambient Temperature:
-5°C to +50°C


- Flow rate up to 2300 l/min
- In-line valves can be used as individual valves or manifold valves
- Variable pressure zones
- Universal valve, sturdy and durable
- Low-cost, no limitations with regard to performance
- Can be used as individual valves or manifold valves VTUS

In-line Electrical Connection Pattern Type C

Working Pressure:
2.5 to 10 bar



3/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply, Normally Closed




0009	Thread	Size mm	Voltage	Manufacturer's Code
575475	G1/4"	25	24V DC	VUVS-L25-M32C-AD-G14-F8-1C1
575568	G3/8"	30	24V DC	VUVS-L30-M32C-AD-G38-F8-1C1
		Tech Sheet 70809		

Working Pressure:
1.5 to 10 bar




5/2 Way Solenoid/Solenoid with Internal Pilot Supply



0009	Thread	Size mm	Voltage	Manufacturer's Code
575265	G1/8"	20	24V DC	VUVS-L20-B52-D-G18-F7-1C1
575518	G1/4"	25	24V DC	VUVS-L25-B52-D-G14-F8-1C1
575611	G3/8"	30	24V DC	VUVS-L30-B52-D-G38-F8-1C1
		Tech Sheet 70813		

Working Pressure:
2.5 to 10 bar

5/3 Way Solenoid/Solenoid, Fully Closed Mid Position with Internal Pilot Supply




0009	Thread	Size mm	Voltage	Manufacturer's Code
575268	G1/8"	20	24V DC	VUVS-L20-P53C-MD-G18-F7-1C1
575525	G1/4"	25	24V DC	VUVS-L25-P53C-MD-G14-F8-1C1
575618	G3/8"	30	24V DC	VUVS-L30-P53C-MD-G38-F8-1C1
		Tech Sheet 70814		

Working Pressure:
2.5 to 10 bar



3/2 Way Solenoid/Mechanical Spring with Internal Pilot Supply, Normally Closed




0009	Thread	Size mm	Voltage	Manufacturer's Code
575274	G1/8"	20	24V DC	VUVS-L20-M32C-MD-G18-F7-1C1
575477	G1/4"	25	24V DC	VUVS-L25-M32C-MD-G14-F8-1C1
575570	G3/8"	30	24V DC	VUVS-L30-M32C-MD-G38-F8-1C1
		Tech Sheet 70810		

Working Pressure:
2.5 to 10 bar




5/2 Solenoid/Mechanical Spring Valves with Internal Pilot Supply



0009	Thread	Size mm	Voltage	Manufacturer's Code
575264	G1/8"	20	24V DC	VUVS-L20-M52-MD-G18-F7-1C1
575511	G1/4"	25	24V DC	VUVS-L25-M52-MD-G14-F8-1C1
575604	G3/8"	30	24V DC	VUVS-L30-M52-MD-G38-F8-1C1
		Tech Sheet 70811		

5/2 Way Solenoid/Pneumatic Spring with Internal Pilot Supply




0009	Thread	Size mm	Voltage	Manufacturer's Code
575263	G1/8"	20	24V DC	VUVS-L20-M52-AD-G18-F7-1C1
575503	G1/4"	25	24V DC	VUVS-L25-M52-AD-G14-F8-1C1
575596	G3/8"	30	24V DC	VUVS-L30-M52-AD-G38-F8-1C1
		Tech Sheet 70812		

Fluid-Air Components Ltd

ACCESSORIES FOR VALVES

FESTO

Manifold Blocks includes Seals & Screws for Mounting Valves




Common Supply Manifold for Mounting Both Sides, Size 20

0009	Thread	No. of Stations	Manufacturer's Code
576363	G3/8	2	VABM-B10-20-G38-2-P53
576365	G3/8	4	VABM-B10-20-G38-4-P53
576367	G3/8	6	VABM-B10-20-G38-6-P53
576369	G3/8	8	VABM-B10-20-G38-8-P53
576371	G3/8	10	VABM-B10-20-G38-10-P53
Tech Sheet 70145			

Common Supply Manifold for Mounting Both Sides, Size 25

0009	Thread	No. of Stations	Manufacturer's Code
8026219	G1/2	2	VABM-B10-25-G12-2-P53
8026221	G1/2	4	VABM-B10-25-G12-4-P53
8026223	G1/2	6	VABM-B10-25-G12-6-P53
8026225	G1/2	8	VABM-B10-25-G12-8-P53
8026227	G1/2	10	VABM-B10-25-G12-10-P53
Tech Sheet 71601			




Compact Manifold Blocks for 5/2 & 5/3 Valves, Size 20

0009	Thread	No. of Stations	Manufacturer's Code
576417	G1/4	2	VABM-B10-20S-G14-2
576419	G1/4	4	VABM-B10-20S-G14-4
576421	G1/4	6	VABM-B10-20S-G14-6
576423	G1/4	8	VABM-B10-20S-G14-8
576425	G1/4	10	VABM-B10-20S-G14-10
Tech Sheet 70143			

Compact Manifold Blocks for 5/2 & 5/3 Valves, Size 25

0009	Thread	No. of Stations	Manufacturer's Code
8026261	G3/8	2	VABM-B10-25S-G38-2
8026263	G3/8	4	VABM-B10-25S-G38-4
8026265	G3/8	6	VABM-B10-25S-G38-6
8026267	G3/8	8	VABM-B10-25S-G38-8
8026269	G3/8	10	VABM-B10-25S-G38-10
Tech Sheet 71602			



Compact Manifold Blocks for 3/2 Valves, Size 20

0009	Thread	No. of Stations	Manufacturer's Code
576465	G1/4	2	VABM-B10-20S-G14-2-P3
576467	G1/4	4	VABM-B10-20S-G14-4-P3
576469	G1/4	6	VABM-B10-20S-G14-6-P3
576471	G1/4	8	VABM-B10-20S-G14-8-P3
576473	G1/4	10	VABM-B10-20S-G14-10-P3
Tech Sheet 70159			

Compact Manifold Blocks for 3/2 Valves, Size 25

0009	Thread	No. of Stations	Manufacturer's Code
8026297	G3/8	2	VABM-B10-25S-G38-2-P3
8026299	G3/8	4	VABM-B10-25S-G38-4-P3
8026301	G3/8	6	VABM-B10-25S-G38-6-P3
8026303	G3/8	8	VABM-B10-25S-G38-8-P3
576473	G1/4	10	VABM-B10-20S-G14-10-P3
Tech Sheet 70144			

Solenoid Coils VACS





Solenoid Coil Without Plug Socket, Connection Pattern To EN 175301-803, Type C

0009	Voltage	Manufacturer's Code
8025331	12V DC	VACS-C-C1-5
8025330	24V DC	VACS-C-C1-1
8025336	48V DC	VACS-C-C1-7
8025335	24V AC	VACS-C-C1-1A
8025337	48V AC	VACS-C-C1-7A
Tech Sheet 71578		

Plug Sockets MSSD



To suit Type C to EN 175301-803


0009	Manufacturer's Code
151687	MSSD-EB
Tech Sheet 70184	

Blanking Plates



Cover Plates for VUVS, Common Supply

0009	To Suit	Manufacturer's Code
576409	G3/8	VABB-B10-20-A
8026208	G1/2	VABB-B10-25-A
8026334	G3/4	VABB-B10-30-A
Tech Sheet 70159		



Cover Plates for VUVS, 3/2 Way Valves

0009	To Suit	Manufacturer's Code
576411	G3/8	VABB-B10-20-E-P3
8026210	G1/2	VABB-B10-25-E-P3
8026336	G3/4	VABB-B10-30-E-P3
Tech Sheet 70161		



Cover Plates for VUVS, 5/2 & 5/3 Way Valves

0009	To Suit	Manufacturer's Code
576410	G3/8	VABB-B10-20-E
8026209	G1/2	VABB-B10-25-E
8026335	G3/4	VABB-B10-30-E
Tech Sheet 70160		

ELECTRICALLY ACTUATED DIRECTIONAL CONTROL VALVES

FESTO

VUVS-L Series, Solenoid Valves, Type B, with 24V DC Soleniod Coil



3/2 Way, Normally Closed, Single Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575481	G1/4	25	Mechanical Spring	1000	VUVS-L25-M32C-MD-G14-F8-1B2
575574	G3/8	30	Mechanical Spring	2300	VUVS-L30-M32C-MD-G38-F8-1B2
			Tech Sheet 71579		



5/2 Way, Single Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575513	G1/4	25	Mechanical Spring	1300	VUVS-L25-M52-MD-G14-F8-1B2
575606	G3/8	30	Mechanical Spring	2300	VUVS-L30-M52-MD-G38-F8-1B2
			Tech Sheet 71580		



5/2 Way, Double Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575520	G1/4	25	Mechanical Spring	1300	VUVS-L25-B52-D-G14-F8-1B2
575613	G3/8	30	Mechanical Spring	2300	VUVS-L30-B52-D-G38-F8-1B2
			Tech Sheet 71581		

5/3 Way, Closed Mid Position, Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575527	G1/4	25	Mechanical Spring	1200	VUVS-L25-P53C-MD-G14-F8-1B2
575620	G3/8	30	Mechanical Spring	2300	VUVS-L30-P53C-MD-G38-F8-1B2
			Tech Sheet 71582		

5/3 Way, Exhausted Mid Position, Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575541	G1/4	25	Mechanical Spring	1000	VUVS-L25-P53E-MD-G14-F8-1B2
			Tech Sheet 71583		

VUVS-L Series, Solenoid Valves, Type C, with 24V DC Solenoid Coil



5/3 Way, Closed Mid Position, Solenoid Valve with Internal Pilot Supply

0009	Thread	Size mm	Function	LPM	Manufacturer's Code
575266	G1/8	20	Mechanical Spring	600	VUVS-L20-P53E-MD-G18-F7-1C1
			Tech Sheet 71584		

Fluid-Air Components Ltd

SOLENOID CONTROL VALVES

Solenoid Valves

Technical Data	1/8"	1/4"	3/8"	1/2"	Namur
Operating pressure:					
monostable bar	2.5 to 10				
bistable bar	1 to 10				
external pilot assisted bar	Vacuum to 10				
Minimum pilot pressure bar	2.5				
Operating temperature range	-10°C to +60°C				
Nominal diameter mm	5	7.5	13.3	15	7.5
Conductance C Nl/min - bar	121.43	264.26	505.52	971.43	264.26
Critical ratio b bar/bar	0.32	0.27	0.32	0.43	0.27
Flow rate at 6 bar ΔP 0.5 bar Nl/min	400	750	1560	3200	750
Flow rate at 6 bar ΔP 1 bar Nl/min	550	1100	2150	4600	1100
TRA / TRR monostable at 6 bar ms	15/35	19/45	21/72	36/60	7/15
TRA / TRR bistable at 6 bar ms	20/20	21/21	18/18	30/30	7/7
Coil voltage values	12; 24 VDC – 24; 110; 220 V AC 50/60Hz				
Power	2 W (DC) 3.5VA (AC)				
Voltage tolerance %	-10 to +15				
Insulation class	F 155				

Namur Interface Solenoid/Spring Valve



G1/4 Ports


9149	Description
7021020100	Single Solenoid 5/2 G1/4"


Namur Interface Solenoid/Solenoid Valve

G1/4 Ports

9149	Description
7021020200	Double Solenoid 5/2 G1/4"

3/2 Solenoid/Spring Valve, Normally Open









G1/8 Ports

9149	Description
7010020400	3/2 G1/8" NO

3/2 Solenoid/Spring Valve, Normally Open









G1/4 Ports

9149	Description
7020020400	3/2 G1/4" NO

3/2 Solenoid/Spring Valve, Normally Open







G3/8 Ports

9149	Description
7040020400	3/2 G3/8" NO

3/2 Solenoid/Spring Valve, Normally Open







G1/2 Ports

9149	Description
7030020400	3/2 G1/2" NO Spring

FT PRO


For **Pre wired moulded DIN Plugs** see page **1043**



Fluid-Air Components Ltd

SOLENOID CONTROL VALVES


3/2 Solenoid/Spring Valve, Normally Closed



G1/8 Ports

9149	Description
7010020200	3/2 G1/8" NC


3/2 Solenoid/Spring Valve, Normally Closed



G1/4 Ports

9149	Description
7020020200	3/2 G1/4" NC


3/2 Solenoid/Spring Valve, Normally Closed



G3/8 Ports

9149	Description
7040020200	3/2 G3/8" NC


3/2 Solenoid/Spring Valve, Normally Closed



G1/2 Ports

9149	Description
7030020200	3/2 G1/2 NC Spring


3/2 Solenoid/Spring Valve, Normally Open Assisted



G3/8 Ports

9149	Description
7040020600	3/2 G3/8" NO ASS


3/2 Solenoid/Spring Valve, Normally Closed Assisted



G3/8 Ports

9149	Description
7040020500	3/2 G3/8" NC ASS


3/2 Solenoid/Solenoid Valve, Normally Closed



G3/8 Ports

9149	Description
7040020100	3/2 G3/8" NC

3/2 Solenoid/ Solenoid Valve, Normally Closed Assisted



G3/8 Ports


9149	Description
7040020300	3/2 G3/8" ASS

Fluid-Air Components Ltd

SOLENOID CONTROL VALVES

5/2 Solenoid/Spring Valve


Note: solenoid coils must be ordered separately.



G1/8 Ports

9149	Description
7010021100	5/2 G1/8"


5/2 Solenoid/Spring Valve



G1/2 Ports

9149	Description
7030021100	5/2 G1/2" Sol/Spring


5/2 Solenoid/Spring Valve



G1/4 Ports

9149	Description
7020021100	5/2 G1/4"


5/2 Solenoid/Spring Valve, Assisted



G3/8 Ports

9149	Description
7040021500	5/2 G3/8" ASS

5/2 Solenoid/Spring Valve



G3/8 Ports


9149	Description
7040021100	5/2 G3/8"

5

SOLENOID CONTROL VALVES

5/2 Solenoid/Solenoid Valve

Note: solenoid coils must be ordered separately.



G1/8 Ports

9149	Description
7010021200	5/2 G1/8"


5/2 Solenoid/Solenoid Valve



Sol/Spring



Sol/Sol




G1/2 Ports

9149	Description
7030021200	5/2 G1/2" Sol/Sol

5/2 Solenoid/Solenoid Valve









G1/4 Ports

9149	Description
7020021200	5/2 G1/4"

5/2 Solenoid/Solenoid Valve, Differential






G3/8 Ports

9149	Description
7040021300	5/2 G3/8"

5/2 Solenoid/Solenoid Valve







G3/8 Ports

9149	Description
7040021200	5/2 G3/8"

5/2 Solenoid/Solenoid Valve, Assisted





G3/8 Ports

9149	Description
7040021600	5/2 G3/8" ASS


Fluid-Air Components Ltd

SOLENOID CONTROL VALVES

5/3 Solenoid/Spring/Solenoid Valve, Pressure Centres

Technical Data
- Nominal diameter: 7.5mm
- Flow rate at 6 bar Δ P 0.5 bar: 750 Nl/min
- Flow rate at 6 bar Δ P 1 bar: 1100 Nl/min
- **Note: solenoid coils must be ordered separately.**

Operating Temperature Range:
10ºC to +60ºC






G1/8 Ports

9149	Description
7010022300	5/3 G1/8" PC

5/3 Solenoid/Spring/Solenoid Valve, Pressure Centres




PC


G1/4 Ports

9149	Description
7020022300	5/3 G1/4" PC

5/3 Solenoid/Spring/Solenoid Valve, Pressure Centres




PC

Body only

G3/8 Ports

9149	Description
7040022300	5/3 G3/8" PC

5/3 Solenoid/Spring/Solenoid Valve, Closed Centres


CC

G3/8 Ports

9149	Description
7040022100	5/3 G3/8" CC

5/3 Solenoid/Spring/Solenoid Valve, Pressure Centres

Technical Data
- Monostable solenoid/spring: 2.5 bar to 10 bar
- Bistable solenoid/solenoid: 1 to 10 bar
- Nominal diameter: 15mm
- Flow rate at 6 bar ΔP 1 bar: 4600Nl/min
- Absorbed power: 2W (DC) 3VA (AC)
- Voltages tolerances: -10ºC to +15ºC
- Degree of protection: IP65 - DIN 40050
- Solenoid rating: 100% ED

Operating Temperature Range:
-10ºC to +60ºC

Maximum Temperature at 100% Solenoid rating:
+70ºC at +20ºC ambient

Minimum Actuation Pressure:
2.5 bar


PC

CC


G1/2 Ports

9149	Description
7030022300	G1/2" PC Solenoid


5/3 Solenoid/Spring/ Solenoid Valve, Closed Centres



G1/2 Ports

9149	Description
7030022100	G1/2" CC Solenoid


5/3 Solenoid/Spring/Solenoid Valve, Closed Centres




G1/8 Ports

9149	Description
7010022100	5/3 G1/8" CC

5/3 Solenoid/Spring/Solenoid Valve, Closed Centres





G1/4 Ports

9149	Description
7020022100	5/3 G1/4" CC


5


SOLENOID CONTROL VALVES

5/3 Solenoid/Spring/Solenoid Valve, Open Centres

Technical Data
- Nominal diameter: 7.5mm
- Flow rate at 6 bar Δ P 0.5 bar: 750 Nl/min
- Flow rate at 6 bar Δ P 1 bar: 1100 Nl/min
- **Note: solenoid coils must be ordered separately.**

Operating Temperature range: -10°C to +60°C





G1/8 Ports

9149	Description
7010022200	5/3 G1/8" OC


5/3 Solenoid/Spring/Solenoid Valve,Open Centres

Technical Data
- Monostable solenoid/spring: 2.5 bar to 10 bar
- Bistable solenoid/solenoid: 1 to 10 bar
- Nominal diameter: 15mm
- Flow rate at 6 bar ΔP 1 bar: 4600Nl/min
- Absorbed power: 2W (DC) 3VA (AC)
- Voltages tolerances: -10°C to +15°C
- Degree of protection: IP65 - DIN 40050
- Solenoid rating: 100% ED

Operating Temperature Range: -10°C to +60°C

Maximum Temperature at 100% Solenoid rating: +70°C at +20°C ambient

Minimum Actuation Pressure: 2.5 bar









G1/2 Ports

9149	Description
7030022200	G1/2" OC Solenoid

5/3 Solenoid/Spring/Solenoid Valve, Open Centres







G1/4 Ports

9149	Description
7020022200	5/3 G1/4" OC

5/3 Solenoid/Spring/Solenoid Valve, Pressure Centres Assisted







G3/8 Ports

9149	Description
7040022600	5/3 G3/8" PC ASS

5/3 Solenoid/Spring/Solenoid Valve, Open Centres





G3/8 Ports

9149	Description
7040022200	5/3 G3/8" OC

5/3 Solenoid/Spring/Solenoid Valve, Closed Centres Assisted

G3/8 Ports

9149	Description
7040022400	5/3 G3/8" CC ASS

5/3 Solenoid/Spring/Solenoid Valve, Open Centres Assisted

G3/8 Ports

9149	Description
7040022500	5/3 G3/8" OC ASS

Fluid-Air Components Ltd


SOLENOID CONTROL VALVES

Solenoid Coils for ISO 5599 Valves, Size 1

Technical Data
- Voltage tolerances: -10% to +15%
- Insulation class: F155
- Degree of protection: IP65 -DIN 40050
- Solenoid rating: 100%
- Electric contact: AMP DIN 43650 2 contacts + 1 earth

Operating Temperature Range:
-20°C to +120°C

Maximum Temperature at 100% Solenoid Rating:
+70°C at +20°C ambient temperature





22mm

9149	Nominal Voltage	Power Inrush	Input Holding	Type
W0215000101	24V DC	2W	2W	22 Ø8 BA 2W-24V DC
W0215000111	24V 50/60Hz	4VA	3VA	22 Ø8 BA 3V-24V AC
W0215000121	110V 50/60Hz	4VA	2W	22 Ø8 BA 3VA-110V AC
W0215000131	220V 50/60Hz	4VA	2W	22 Ø8 3VA-220V AC

Solenoid Coils, 5W

Technical Data
- Monostable solenoid/spring: 2.5 bar to 10 bar
- Bistable solenoid/solenoid: 1 to 10 bar
- Nominal diameter: 15mm
- Flow rate at 6 bar ΔP 1 bar: 4600NI/min
- Absorbed power: 2W (DC) 3VA (AC)
- Voltages tolerances: -10°C to +15°C
- Degree of protection: IP65 - DIN 40050
- Solenoid rating: 100% ED
- **Note: solenoid coils must be ordered separately.**

Operating Temperature Range:
-10°C to +60°C

Maximum Temperature at 100% Solenoid Rating:
+70°C at +20°C ambient temperature


Minimum Actuation Pressure:
2.5 bar



22mm

9182	Nominal Voltage	Power Inrush	Input Holding	Type
W0215000001	24V DC	5W	5W	22 Ø8 5W-24V DC
W0215000011	24V 50/60Hz	8VA	5VA	22 Ø8 5VA-24V AC
W0215000021	110V 50/60Hz	8VA	5VA	22 Ø8 5VA-110V AC
W0215000031	220V 50/60Hz	8VA	5VA	22 Ø8 5W-220V AC

Manifolds




G1/8" Ports



In-line, 1/8" Ports

9149	Description
0223000201	2 Position
0223000301	3 Position
0223000401	4 Position
0223000501	5 Position
0223000601	6 Position
0223000701	7 Position
0226004500	Blanking Plate Size 1/8"

Manifolds



G1/4" Ports



In-line, 1/4" Ports

9149	Description
0224000201	2 Position
0224000401	4 Position
0224000501	5 Position
0224000601	6 Position
0224000701	7 Position
0226004500	Blanking Plate Size 1/8"
0226005500	Blanking Plate Size 1/4"

FT PRO

For **Pre wired moulded DIN Plugs** see page **1043**



Fluid-Air Components Ltd

EXCEL 32 V03, V04 & V05 SERIES

NORGREN

- Extensive range of power and orifice size option
- G1/8, G1/4 and 7mm interface
- Compact installation
- Removable coil
- Standard exhaust diffuser
- Choice of manual override

Medium:
Compressed air, filtered, lubricated and non-lubricate

Materials:
Coil: Glass reinforced nylon
Armature: Stainless steel
Base:
Zinc alloy (G1/8), brass (G1/4), polyester (interface)
Seals: Nitrile (viton top seat)

Working Temperature:
-20°C to +50°C

Note: the below valves are only available in 24V DC.

V03 Series

V03 2/2 NC 24V DC 0-10 bar 1mm Orific

0036	Thread
V03A286J-B613A	G1/8
Tech Sheet 10363	

V03 3/2 NC 24V DC 0-10 bar 1mm Orific

0036	Thread
V03X486J-B613A	Interface
V03A486J-B613A	G1/8
Tech Sheet 10363	

V04 Series

V04 2/2 SOL NC 0-10 bar 2.5mm Orific


0036	Thread	Voltage
V04X286M-B623A	Interface	24V DC
V04A286M-B623A	G1/8	24V DC
V04A286M-B628A	G1/8	110/50-60
V04A286M-B629A	G1/8	220/50-60
V04B286M-B423A	G1/4	24V DC
V04B286M-B428A	G1/4	220/50-60
V04B286M-B429A	G1/4	220/50-60
Tech Sheet 10363		

V04 3/2 SOL NC 0-10 bar 2mm Orific

0036	Thread	Voltage
V04X486L-B623A	Interface	24V DC
V04X486L-B628A	Interface	110/50-60
V04X486L-B629A	Interface	220/50-60
V04A486L-B623A	G1/8	24V DC
V04A486L-B628A	G1/8	110/50-60
V04A486L-B629A	G1/8	220/50-60
Tech Sheet 10363		

V04 3/2 SOL NO 0-10 bar 2mm Orific

0036	Thread	Voltage
V04X386L-B623A	Interface	24V DC
V04X386L-B628A	Interface	110/50-60
V04X386L-B629A	Interface	220/50-60
V04A386L-B623A	G1/8	24V DC
V04A386L-B628A	G1/8	110/50-60
V04A386L-B629A	G1/8	220/50-60
Tech Sheet 10363		



V05 Series

V05 2/2 SOL NC 0-16 bar 2.5mm Orific

0036	Thread	Voltage
V05X286M-B633A	Interface	24V DC
V05X286M-B638A	Flange	110/120V
V05B286M-B433A	G1/4	24V DC
Tech Sheet 10363		

V05 3/2 SOL NC 0-10 bar 2.5mm Orific

0036	Thread	Voltage
V05X486M-B633A	Interface	24V DC
V05X486M-B638A	Interface	110/50-60
V05X486M-B639A	Interface	220/50-60
V05A486M-B633A	G1/8	24V DC
V05A486M-B638A	G1/8	110/50-60
V05A486M-B639A	G1/8	220/50-60
Tech Sheet 10363		

Accessories for Excel 32

Manifolds to suit Interface Valves G1/8

0036	No. of Stations
M/P35598/1	1
M/P35598/2	2
M/P35598/3	3
M/P35598/4	4
M/P35598/5	5
M/P35598/6	6
M/P35598/8	8
M/P35598/9	9
M/P35598/10	10
Tech Sheet 10363	

V03, V04 & V05 Spare Solenoid Coils

0036	To Suit	Voltage
V03X286A-Q1213	V03	24V DC
V04X286A-Q1228	V04	110/50-60
V04X286A-Q1229	V04	220/50-60
V05X286A-Q1233	V05	24V DC
V05X286A-Q1238	V05	110/50-60
V05X286A-Q1239	V05	220/50-60
Tech Sheet 10363		


Fluid-Air Components Ltd

V60

In-line Valves Solenoid/Pilot Operated

High Flow Rates:
G1/8 - 750 L/min, G1/4 - 1,300 L/min,
G3/8 - 2,600 L/min, G1/2 - 4,200 L/min available
Multifunctional: 3/2, 2x 3/2, 5/2, 5/3
Medium: Compressed air, filtered to 50micron, lubricated or non-lubricated

- Maintenance free
- Proven sealing system
- Small volumetric size
- Multiple solenoid/manual override variations





Solenoid Actuated, BSPP

0036	Thread	Function	Actuation
V60A413A-A2000	1/8"	3/2 NC	Sol/Spring
V60A513A-A2000	1/8"	5/2	Sol/Spring
V60A511A-A3000	1/8"	5/2	Sol/Sol
V61B413A-A2000	1/4"	3/2 NC	Sol/Spring
V61B513A-A2000	1/4"	5/2	Sol/Spring
V61B511A-A3000	1/4"	5/2	Sol/Sol
V62C413A-A2000	3/8"	3/2 NC	Sol/Spring
V62C513A-A2000	3/8"	5/2	Sol/Spring
V62C511A-A3000	3/8"	5/2	Sol/Sol
Tech Sheet 20152			



Pilot Actuated, BSPP

0036	Thread	Function	Actuation
V60A4D7A-XA090	1/8"	3/2 NC	Pilot/Spring
V60A5D7A-XA090	1/8"	5/2	Pilot/Spring
V60A5DDA-XA020	1/8"	5/2	Pilot/Pilot
V61B4D7A-XA090	1/4"	3/2 NC	Pilot/Spring
V61B5D7A-XA090	1/4"	5/2	Pilot/Spring
V61B5DDA-XA020	1/4"	5/2	Pilot/Pilot
V62C4D7A-XA090	3/8"	3/2 NC	Pilot/Spring
V62C5D7A-XA090	3/8"	5/2	Pilot/Spring
V62C5DDA-XA020	3/8"	5/2	Pilot/Pilot
Tech Sheet 20152			

V60 Accessories



Solenoid Coils 22mm DIN EN 175 301-803 (DIN 43650 B)

0036	Voltage
V10626-A13L	24V DC-2W
V10626-A18L	110V AC-4/2.5W
V10626-A19L	240V AC-6/5VA
Tech Sheet 20152	

EXCEL 22 M/48 & M/49 SERIES

Solenoid Actuated 22mm Poppet Valves



M5 3/2 Sol/Spring Sub-base

0036	Voltage
M/48/MAZ13J	24V DC
M/48/MAZ19J	220V AC
Tech Sheet 20154	



G1/8 3/2 Sol/Spring Sub-base

0036	Voltage
M/49/MAZ14J	24V AC
M/49/MAZ13J	24V DC
M/49/MAZ18J	110V AC
M/49/MAZ19J	220V AC
Tech Sheet 20154	



Spare Coils

0036	Voltage
QM/48/13J/21	24V DC
QM/48/14J/21	24V AC
QM/48/18J/21	110V AC
QM/48/19J/21	220V AC
Tech Sheet 20154	



Spare DIN 22mm Plug


0036
M/P19063
Tech Sheet 20154

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

DIRECTIONAL CONTROL VALVES


Series A, Directly Operated Solenoid Valves






M5, 2/2 NC Solenoid Valves (A32)

0158	Orifice mm	Voltage
A321 0C2	1.5	Valve Only
A321 0C2 U72	1.5	12V DC 5W
A321 0C2 U73	1.5	24V DC 5W
A321 0C2 U74	1.5	48V DC 5.3W
A321 0C2 U76	1.5	110V DC 4.2W
A321 0C2 U7H	1.5	24V AC 3.5VA
A321 0C2 U7K	1.5	110V AC 4.3VA
A321 0C2 U7J	1.5	240V AC 4VA
Tech Sheet 1845		




G1/8", 2/2 NC Solenoid Valves (A32)

0158	Orifice mm	Voltage
A321 1C2	1.5	Valve Only
A321 1C2 U72	1.5	12V DC 5W
A321 1C2 U73	1.5	24V DC 5W
A321 1C2 U74	1.5	48V DC 5.3W
A321 1C2 U76	1.5	110V DC 4.2W
A321 1C2 U7H	1.5	24V AC 3.5VA
A321 1C2 U7K	1.5	110V AC 4.3VA
A321 1C2 U7J	1.5	240V AC 4VA
A321 1D2	2	Valve Only
A321 1D2 U72	2	12V DC 5W
A321 1D2 U73	2	24V DC 5W
A321 1D2 U74	2	48V DC 5.3W
A321 1D2 U76	2	110V DC 4.2W
A321 1D2 U7H	2	24V AC 3.5VA
A321 1D2 U7K	2	110V AC 4.3VA
A321 1D2 U7J	2	240V AC 4VA
A321 1E2	2.5	Valve Only
A321 1E2 U72	2.5	12V DC 5W
A321 1E2 U73	2.5	24V DC 5W
A321 1E2 U74	2.5	48V DC 5.3W
A321 1E2 U76	2.5	110V DC 4.2W
A321 1E2 U7H	2.5	24V AC 3.5VA
A321 1E2 U7K	2.5	110V AC 4.3VA
A321 1E2 U7J	2.5	240V AC 4VA
Tech Sheet 1845		




M5, 2/2 NO Solenoid Valves (A32)

0158	Orifice mm	Voltage
A322 0C2	1.8	Valve Only
A322 0C2 U72	1.8	12V DC 5W
A322 0C2 U73	1.8	24V DC 5W
A322 0C2 U74	1.8	48V DC 5.3W
A322 0C2 U76	1.8	110V DC 4.2W
A322 0C2 U7H	1.8	24V AC 3.5VA
A322 0C2 U7K	1.8	110V AC 4.3VA
A322 0C2 U7J	1.8	240V AC 4VA
Tech Sheet 1845		




G1/8", 2/2 NO Solenoid Valves (A32)

0158	Orifice mm	Voltage
A322 1C2	1.8	Valve Only
A322 1C2 U72	1.8	12V DC 5W
A322 1C2 U73	1.8	24V DC 5W
A322 1C2 U74	1.8	48V DC 5.3W
A322 1C2 U76	1.8	110V DC 4.2W
A322 1C2 U7H	1.8	24V AC 3.5VA
A322 1C2 U7K	1.8	110V AC 4.3VA
A322 1C2 U7J	1.8	240V AC 4VA
Tech Sheet 1845		




M5, 3/2 NC Solenoid Valves (A33)

0158	Orifice mm	Voltage
A331 0C2	1.5	Valve Only
A331 0C2 U72	1.5	12V DC 5W
A331 0C2 U73	1.5	24V DC 5W
A331 0C2 U74	1.5	48V DC 5.3W
A331 0C2 U76	1.5	110V DC 4.2W
A331 0C2 U7H	1.5	24V AC 3.5VA
A331 0C2 U7K	1.5	110V AC 4.3VA
A331 0C2 U7J	1.5	240V AC 4VA
Tech Sheet 1845		



G1/8", 3/2 NC Solenoid Valves (A33)

0158	Orifice mm	Voltage
A331 1C2	1.5	Valve Only
A331 1C2 U72	1.5	12V DC 5W
A331 1C2 U73	1.5	24V DC 5W
A331 1C2 U74	1.5	48V DC 5.3W
A331 1C2 U76	1.5	110V DC 4.2W
A331 1C2 U7H	1.5	24V AC 3.5VA
A331 1C2 U7K	1.5	110V AC 4.3VA
A331 1C2 U7J	1.5	240V AC 4VA
Tech Sheet 1845		



M5, 3/2 NO Solenoid Valves (A33)

0158	Orifice mm	Voltage
A332 0C2	1.5	Valve Only
A332 0C2 U72	1.5	12V DC 5W
A332 0C2 U73	1.5	24V DC 5W
A332 0C2 U74	1.5	48V DC 5.3W
A332 0C2 U76	1.5	110V DC 4.2W
A332 0C2 U7H	1.5	24V AC 3.5VA
A332 0C2 U7K	1.5	110V AC 4.3VA
A332 0C2 U7J	1.5	240V AC 4VA
Tech Sheet 1845		

G1/8", 3/2 NO Solenoid Valves (A33)

0158	Orifice mm	Voltage
A332 1C2	1.5	Valve Only
A332 1C2 U72	1.5	12V DC 5W
A332 1C2 U73	1.5	24V DC 5W
A332 1C2 U74	1.5	48V DC 5.3W
A332 1C2 U76	1.5	110V DC 4.2W
A332 1C2 U7H	1.5	24V AC 3.5VA
A332 1C2 U7K	1.5	110V AC 4.3VA
A332 1C2 U7J	1.5	240V AC 4VA
Tech Sheet 1845		


Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 3, Electro Pneumatically Operated Solenoid Valves


Actuation:
Solenoid/Spring





G1/8", 3/2 NC Single Solenoid Valves (338)

0158	Voltage
338 015 02	Valve Only
338 015 02 U7H	24V 50/60Hz 3.5VA
338 015 02 U7K	110V 50/60Hz 3.5VA
338 015 02 U7J	240V 50/60Hz 4VA
338 015 02 U72	12V DC 5W
338 015 02 U73	24V DC 5W
338 015 02 U74	48V DC 5W
338 015 02 U76	110V DC 5W
338 015 02 U77	24V DC 3W
Tech Sheet 1847	




G1/8", 3/2 NO Single Solenoid Valves (348)

0158	Voltage
348 015 02	Valve Only
348 015 02 U7H	24V 50/60Hz 3.5VA
348 015 02 U7K	110V 50/60Hz 3.5VA
348 015 02 U7J	240V 50/60Hz 4VA
348 015 02 U72	12V DC 5W
348 015 02 U73	24V DC 5W
348 015 02 U74	48V DC 5W
348 015 02 U76	110V DC 5W
348 015 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation:
Solenoid/Solenoid






G1/8", 3/2 Manual Override Double Solenoid Valves (338)

0158	Voltage
338 011 02 U7H	24V 50/60Hz 3.5VA
338 011 02 U7K	110V 50/60HZ 3.5VA
338 011 02 U7J	240V 50/60Hz 4VA
338 011 02 U72	12V DC 5W
338 011 02 U73	24V DC 5W
338 011 02 U74	48V DC 5W
338 011 02 U76	110V DC 5W
338 011 02 U77	24V DC 3W
Tech Sheet 1847	


Actuation:
Solenoid/Spring





G1/8", 3/2 x 3/2 NC Double Valves S.R. Solenoid Valves (338)

0158	Voltage
338D 015 02	Valve Only
338D 015 02 U7H	24V 50/60Hz 3.5VA
338D 015 02 U7K	110V 50/60Hz 3.5VA
338D 015 02 U7J	240V 50/60Hz 4VA
338D 015 02 U72	12V DC 5W
338D 015 02 U73	24V DC 5W
338D 015 02 U74	48V DC 5W
338D 015 02 U76	110V DC 5W
338D 015 02 U77	24V DC 3W
Tech Sheet 1847	



G1/8", 3/2 x 3/2 NO Double Valves S.R. Solenoid Valves (348)

0158	Voltage
348D 015 02	Valve Only
348D 015 02 U7H	24V 50/60Hz 3.5VA
348D 015 02 U7K	110V 50/60Hz 3.5VA
348D 015 02 U7J	240V 50/60Hz 4VA
348D 015 02 U72	12V DC 5W
348D 015 02 U73	24V DC 5W
348D 015 02 U74	48V DC 5W
348D 015 02 U76	110V DC 5W
348D 015 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation:
Solenoid/Spring






G1/8", 5/2 Manual Override Single Solenoid Valves (358)

0158	Voltage
358 015 02	Valve Only
358 015 02 U7H	24V 50/60Hz 3.5VA
358 015 02 U7K	110V 50/60Hz 3.5VA
358 015 02 U7J	240V 50/60Hz 4VA
358 015 02 U72	12V DC 5W
358 015 02 U73	24V DC 5W
358 015 02 U74	48V DC 5W
358 015 02 U76	110V DC 5W
358 015 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation:
Solenoid/Solenoid





G1/8", 5/2 Manual Override Double Solenoid Valves (358)

0158	Voltage
358 011 02	Valve Only
358 011 02 U7H	24V 50/60Hz 3.5VA
358 011 02 U7K	110V 50/60Hz 3.5VA
358 011 02 U7J	240V 50/60Hz 4VA
358 011 02 U72	12V DC 5W
358 011 02 U73	24V DC 5W
358 011 02 U74	48V DC 5W
358 011 02 U76	110V DC 5W
358 011 02 U77	24V DC 3W
Tech Sheet 1847	

Fluid-Air Components Ltd


DIRECTIONAL CONTROL VALVES

CAMOZZI Automation

Series 3, Electro Pneumatically Operated Solenoid Valves

Actuation: Solenoid/Solenoid






G1/8", 5/3 C/C Double Solenoid Valves (368)

0158	Voltage
368 011 02	Valve Only
368 011 02 U7H	24V 50/60Hz 3.5VA
368 011 02 U7K	110V 50/60Hz 3.5VA
368 011 02 U7J	240V 50/60Hz 4VA
368 011 02 U72	12V DC 5W
368 011 02 U73	24V DC 5W
368 011 02 U74	48V DC 5W
368 011 02 U76	110V DC 5W
368 011 02 U77	24V DC 3W
Tech Sheet 1847	



G1/8", 5/3 C/O Double Solenoid Valves (378)

0158	Voltage
378 011 02	Valve Only
378 011 02 U7H	24V 50/60Hz 3.5VA
378 011 02 U7K	110V 50/60Hz 3.5VA
378 011 02 U7J	240V 50/60Hz 4VA
378 011 02 U72	12V DC 5W
378 011 02 U73	24V DC 5W
378 011 02 U74	48V DC 5W
378 011 02 U76	110V DC 5W
378 011 02 U77	24V DC 3W
Tech Sheet 1847	




G1/8", 5/3 NC & NO Double Valve P/C Double Solenoid Valves (388)

0158	Voltage
388 011 02	Valve Only
388 011 02 U7H	24V 50/60Hz 3.5VA
388 011 02 U7K	110V 50/60Hz 3.5VA
388 011 02 U7J	240V 50/60Hz 4VA
388 011 02 U72	12V DC 5W
388 011 02 U73	24V DC 5W
388 011 02 U74	48V DC 5W
388 011 02 U76	110V DC 5W
388 011 02 U77	24V DC 3W
Tech Sheet 1847	

Series 3, Electro Pneumatically Operated High Flow Solenoid Valves

Actuation: Solenoid/Spring






G1/4", 3/2 NC Single Solenoid Valves (334)

0158	Voltage
334 015 02	Valve Only
334 015 02 U7H	24V 50/60Hz 3.5VA
334 015 02 U7K	110V 50/60Hz 3.5VA
334 015 02 U7J	230V 50/60Hz 4VA
334 015 02 U72	12V DC 5W
334 015 02 U73	24V DC 5W
334 015 02 U74	48V DC 5W
334 015 02 U76	110V DC 5W
334 015 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation: Solenoid/Spring




G1/4", 3/2 NC External Servo Single Solenoid Valves (334)

0158	Voltage
334 E15 02	Valve Only
334 E15 02 U7H	24V 50/60Hz 3.5VA
334 E15 02 U7K	110V 50/60Hz 3.5VA
334 E15 02 U7J	230V 50/60Hz 4VA
334 E15 02 U72	12V DC 5W
334 E15 02 U73	24V DC 5W
334 E15 02 U74	48V DC 5W
334 E15 02 U76	110V DC 5W
334 E15 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation: Solenoid/Solenoid






G1/4", 3/2 NC Double Solenoid Valves (334)

0158	Voltage
334 011 02	Valve Only
334 011 02 U7H	24V 50/60Hz 3.5VA
334 011 02 U7K	110V 50/60Hz 3.5VA
334 011 02 U7J	230V 50/60Hz 4VA
334 011 02 U72	12V DC 5W
334 011 02 U73	24V DC 5W
334 011 02 U74	48V DC 5W
334 011 02 U76	110V DC 5W
334 011 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation: Solenoid/Solenoid



G1/4", 3/2 External Servo Double Solenoid Valves (334)

0158	Voltage
334 E11 02	Valve Only
334 E11 02 U7H	24V 50/60Hz 3.5VA
334 E11 02 U7K	110V 50/60Hz 3.5VA
334 E11 02 U7J	230V 50/60Hz 4VA
334 E11 02 U72	12V DC 5W
334 E11 02 U73	24V DC 5W
334 E11 02 U74	48V DC 5W
334 E11 02 U76	110V DC 5W
334 E11 02 U77	24V DC 3W
Tech Sheet 1847	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 3, Electro Pneumatically Operated High Flow Solenoid Valves

Actuation: Solenoid/Spring






G1/4", 5/2 Single Solenoid Valves (354)

0158	Voltage
354 015 02	Valve Only
354 015 02 U7H	24V 50/60Hz 3.5VA
354 015 02 U7K	110V 50/60Hz 3.5VA
354 015 02 U7J	230V 50/60Hz 4VA
354 015 02 U72	12V DC 5W
354 015 02 U73	24V DC 5W
354 015 02 U74	48V DC 5W
354 015 02 U76	110V DC 5W
354 015 02 U77	24V DC 3W
Tech Sheet 1847	


Actuation: Solenoid/Spring



G1/4", 5/2 External Servo Single Solenoid Valves (354)

0158	Voltage
354 E15 02	Valve Only
354 E15 02 U7H	24V 50/60Hz 3.5VA
354 E15 02 U7K	110V 50/60Hz 3.5VA
354 E15 02 U7J	230V 50/60Hz 4VA
354 E15 02 U72	12V DC 5W
354 E15 02 U73	24V DC 5W
354 E15 02 U74	48V DC 5W
354 E15 02 U76	110V DC 5W
354 E15 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation: Solenoid/Solenoid



G1/4", 5/2 Double Solenoid Valves (354)

0158	Voltage
354 011 02	Valve Only
354 011 02 U7H	24V 50/60Hz 3.5VA
354 011 02 U7K	110V 50/60Hz 3.5VA
354 011 02 U7J	230V 50/60Hz 4VA
354 011 02 U72	12V DC 5W
354 011 02 U73	24V DC 5W
354 011 02 U74	48V DC 5W
354 011 02 U76	110V DC 5W
354 011 02 U77	24V DC 3W
Tech Sheet 1847	



G1/4", 5/2 External Servo Double Solenoid Valves (354)


0158	Voltage
354 E11 02	Valve Only
354 E11 02 U7H	24V 50/60Hz 3.5VA
354 E11 02 U7K	110V 50/60Hz 3.5VA
354 E11 02 U7J	230V 50/60Hz 4VA
354 E11 02 U72	12V DC 5W
354 E11 02 U73	24V DC 5W
354 E11 02 U74	48V DC 5W
354 E11 02 U76	110V DC 5W
354 E11 02 U77	24V DC 3W
Tech Sheet 1847	

Actuation: Solenoid/Solenoid



G1/4", 5/3 C/C Manual Override Double Solenoid Valves(364)

0158	Voltage
364 011 02	Valve Only
364 011 02 U7H	24V 50/60Hz 3.5VA
364 011 02 U7K	110V 50/60Hz 4.3VA
364 011 02 U7J	240V 50/60Hz 4VA
364 011 02 U72	12V DC 5W
364 011 02 U73	24V DC 5W
364 011 02 U74	48V DC 5W
364 011 02 U76	110V DC 4.2W
364 011 02 U77	24V DC 3W
Tech Sheet 1847	



G1/4", 5/3 C/C Manual Override Double Solenoid Valves External Pilot (364)


0158	Voltage
364 E11 02	Valve Only
364 E11 02 U7H	24V 50/60Hz 3.5VA
364 E11 02 U7K	110V 50/60Hz 4.3VA
364 E11 02 U7J	240V 50/60Hz 4VA
364 E11 02 U72	12V DC 5W
364 E11 02 U73	24V DC 5W
364 E11 02 U74	48V DC 5W
364 E11 02 U76	110V DC 4.2W
364 E11 02 U77	24V DC 3W
Tech Sheet 1847	





G1/4", 5/3 C/O Manual Override Double Solenoid Valves (374)

0158	Voltage
374 011 02	Valve Only
374 011 02 U7H	24V 50/60Hz 3.5VA
374 011 02 U7K	110V 50/60Hz 4.3VA
374 011 02 U7J	240V 50/60Hz 4VA
374 011 02 U72	12V DC 5W
374 011 02 U73	24V DC 5W
374 011 02 U74	48V DC 5W
374 011 02 U76	110V DC 4.2W
374 011 02 U77	24V DC 3W
Tech Sheet 1847	



G1/4", 5/3 C/O Manual Override Double Solenoid Valves External Pilot (374)

0158	Voltage
374 E11 02	Valve Only
374 E11 02 U7H	24V 50/60Hz 3.5VA
374 E11 02 U7K	110V 50/60Hz 4.3VA
374 E11 02 U7J	240V 50/60Hz 4VA
374 E11 02 U72	12V DC 5W
374 E11 02 U73	24V DC 5W
374 E11 02 U74	48V DC 5W
374 E11 02 U76	110V DC 4.2W
374 E11 02 U77	24V DC 3W
Tech Sheet 1847	

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Solenoid Coils for Electro Pneumatically Operated Valves

- Solenoid DIN connector use Form B.



U70 Solenoid Coils

0158	Voltage
U7H	24V 50/60Hz 3.5VA
U7K	110V 50/60Hz 3.5VA
U7J	240V 50/60Hz 4VA
U77	24V DC 3W
U71	6V DC 5W
U72	12V DC 5W
U73	24V DC 5W
U74	48V DC 5W
U76	110V DC 5W
Tech Sheet 10313	

- Solenoid DIN connector use Form B.



G70 Solenoid Coils

0158	Voltage
G7H	24V 50/60Hz 3.5VA
G7K	110V 50/60Hz 3.5VA
G7J	240V 50/60Hz 4VA
G79	48V DC 3W
G77	24V DC 3W
G72	12V DC 5W
G73	24V DC 5W
G76	110V DC 4W
Tech Sheet 10313	

- Solenoid DIN connector use Form A.



A80 Solenoid Coils

0158	Voltage
A8B	24V 50/60Hz 5VA
A8D	110V 50/60Hz 5VA
A8E	220V 50/60Hz 5VA
A83	24V DC 4W
A84	48V DC 4W
A86	110V DC 4W
Tech Sheet 10313	

- Solenoid DIN connector use Form B.



G80 Solenoid Coils

0158	Voltage
G93	24V Coil
Tech Sheet 10313	

Solenoid DIN Connectors



Black Connectors

0158	Type
KA132000B9	Form A 18mm Pin Spacing
KB132000B9	Form B 11mm Pin Spacing
Tech Sheet 10313	



Grey Connectors

0158	Type
KA132000A9	Form A 18mm Pin Spacing
Tech Sheet 10313	



Transparent Connectors, with LED

0158	Type
KA132V54T9	Form A 18mm Pin Spacing, 24V
KA132V55T9	Form A 18mm Pin Spacing, 115V
KA132V56T9	Form A 18mm Pin Spacing, 230V
KB132V54T9	Form B 11mm Pin Spacing, 24V
KB132V55T9	Form B 11mm Pin Spacing, 115V
KB132V56T9	Form B 11mm Pin Spacing, 230V
Tech Sheet 10313	

For **Banding & Tie Wraps** see page **1553**





Fluid-Air Components Ltd

PNEUMATIC VALVES & ACCESSORIES

Solenoid 5/2 Way Valve


The **Viking Lite** valve range is robust, versatile and combines high performance with compact installation dimensions. The choice of G1/8, G1/4 or G3/8 port sizes provide large flow capacity and short change-over times. Low change-over pressure is also an important characteristic of this valve range.

Under pressure, radial expansion of the seal occurs to maintain sealing contact with the valve bore.

This sealing method reduces friction and gives lower pilot pressures, providing fast response and less wear. Valves do not require lubrication in operation but they can also be installed in systems that are lubricated.

Working Temperature:
-10°C to +50°C

Maximum Working Pressure:
10 bar



Spring Return, Single Solenoid, BSPP

0681	Thread
P2LAZ511ESNDCN	1/8"
P2LBZ512ESNDCN	1/4"
Tech Sheet 68763	

Solenoid Coils & Plugs

Solenoid Coils, 22mm



0681	Voltage
P2FCB449	24V DC
P2FCB453	110V AC
P2FCB457	230V AC
Tech Sheet 68763	

Connector Plug, IP65



0681
3EV10V10
Tech Sheet 68763

Plug with LED & Protection



0681	To Suit
3EV10V20-110	110V AC
Tech Sheet 68763	

Pilot & Solenoid Valves



B3 & B4 Series Coils 15mm

0681	Voltage
P2E-KV32B2	12V DC
P2E-KV32C2	24V DC



B3 & B4 Series Solenoid Connectors / Cable Plugs

0681	Description
P8C-D	Standard IP65 without Flying Lead



Viking Lite Valve 3/2 & 5/2 Solenoid Operated G1/8" - G1/4"

0681	Type	Actuator	Return	Thread BSPP
P2LBZ312ESNDCN	3-2	Electric	Spring	1/4"
P2LBZ512EENDCN	5-2	Electric	Electric	1/4"
P2LAZ511ESNDCN	5-2	Electric	Spring	1/8"

Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

ECO 22 Solenoid Valves



Solenoid/Spring, BSPP

0110	Thread	Function
8880.32.C.39.F00	1/8"	Normally Closed

ECO 22 Solenoid Valves - 1/4"



Solenoid/Spring, BSPP

0110	Thread	Function
8884.32.C.39.F00	1/4"	Normally Closed
8884.32.A.39.F00	1/4"	Normally Open

5/2 PNEUMATIC VALVES

Eco 22 Solenoid Valves



Solenoid/Spring Valves, BSPP

0110	Thread
8880520039F00	1/8"
8884520039F00	1/4"



Solenoid/Solenoid, BSPP

0110	Thread
8880520035F00	1/8"
8884520035F00	1/4"

400 Series Valves



Solenoid/Spring, BSPP

0110	Thread
412/2.52.0.1.M2	1/2"



Solenoid/Solenoid, BSPP

0110	Thread
412/2.52.0.0.M2	1/2"

T400 Series Tecno Eco Valves



Solenoid/Spring (Ext Pilot), BSPP

0110	Thread
T424.52.0.1.E.M2	1/4"

T488 Series Tecno Valves



Solenoid/Differential Pilot (Ext Feed), BSPP

0110	Thread
T488.52.0.12E.M2	1/8"



Solenoid/Spring (Int Feed), BSPP

0110	Thread
T488.52.0.1.M2	1/8"

Solenoid/Spring (Ext Feed), BSPP

0110	Thread
T488.52.0.1E.M2	1/8"



Solenoid/Solenoid, BSPP

0110	Thread
T488.52.0.0.M2	1/8"

Fluid-Air Components Ltd

PNEUMATIC VALVES & ACCESSORIES

Eco 22 Series




Complete Manifolds 5/2 - 5/3

0110	Stations
888.02	2
888.03	3
888.04	4
888.05	5
888.06	6
888.07	7
888.08	8
888.09	9
888.10	10



Modular 3/2 Solenoid/Spring Valves

0110	Thread	NO/NC
345.M1	4mm	N/C
305.M1	1/8"	N/C
305.M1/1	1/8"	N/O



Manifold Closing Plate

0110	Description
888	Blanking Plate



MF Type Coils

0110	Voltage
MF4	12V DC
MF5	24V DC
MF56	2V AC
MF57	110V AC
MF58	220V AC



888 Type Coil Caps

0110	Voltage
888.11.01	24V DC - 24V AC LED
888.11.02	110V AC LED
888.11.03	220V AC LED

T400 Series



Manifold Bases

0110	Description
T424.01	Single Complete Base



Manifold Closing Plate

0110	Description
T424.00	Blanking Plate



MB Type 22mm Coils

0110	Voltage
MB4	12V DC
MB5	24V DC
MB9	24V DC (2 watt)
MB56	24V AC
MB57	110V AC
MB58	22V DC



305 22mm Coil Caps

0110	Voltage
305.11.00	No LED
305.11.01L	24V DC LED
305.11.02L	110V AC LED
305.11.03L	240V AC LED

T488 Series



Manifold Bases

0110	Description
T488.01	Single Complete Base

Fluid-Air Components Ltd

PILOT VALVES

Medium: Clean compressed air. Filtered (40µm) and lubricated
Body Material: Aluminium alloy
Seals: Nitrile

Working Temperature: -20°C to +70°C

Working Pressure: 1.5 to 8 bar

2 Year Warranty

Pilot 3/2 Way Valves





Pilot/Spring, Normally Open, BSPP

0335	Thread
CKA210-06-NO	1/8"
CKA210-08-NO	1/4"
CKA310-10-NO	3/8"
Tech Sheet 3036	





Pilot/Spring, Normally Closed, BSPP

0335	Thread
CKA210-06-NC	1/8"
CKA210-08-NC	1/4"
CKA310-10-NC	3/8"
Tech Sheet 3036	





Pilot/Pilot, BSPP

0335	Thread
CKA220-06	1/8"
CKA220-08	1/4"
CKA320-10	3/8"
Tech Sheet 3036	

Pilot 5/2 Way Valves





Pilot/Spring, BSPP

0335	Thread
DKA210-06	1/8"
DKA210-08	1/4"
DKA310-10	3/8"
DKA410-15	1/2"
Tech Sheet 3037	





Pilot/Pilot, BSPP

0335	Thread
DKA220-06	1/8"
DKA220-08	1/4"
DKA320-10	3/8"
DKA420-15	1/2"
Tech Sheet 3037	

Fluid-Air Components Ltd

PILOT VALVES

Medium: Clean compressed air. Filtered (40µm) and lubricated
Body Material: Aluminium alloy
Seals: Nitrile


Working Temperature: -20°C to +70°C

Working Pressure: 1.5 to 8 bar

2 Year Warranty

Pilot 5/3 Way Valves





Pilot/Pilot, Fully Sealed Mid Position, BSPP

0335	Thread
DKA230C-06	1/8"
DKA230C-08	1/4"
DKA330C-10	3/8"
DKA430C-15	1/2"
Tech Sheet 3037	






Pilot/Pilot, Centre Open Pressurised, BSPP

0335	Thread
DKA230P-06	1/8"
DKA230P-08	1/4"
DKA330P-10	3/8"
DKA430P-15	1/2"
Tech Sheet 3037	





Pilot/Pilot, Supply Sealed Mid Position, BSPP


0335	Thread
DKA230E-06	1/8"
DKA230E-08	1/4"
DKA330E-10	3/8"
DKA430E-15	1/2"
Tech Sheet 3037	



For **Stainless Steel Silencers**
see page **630**

Driven by Customers Designed by Metal Work

EB80 VALVES



Why cut costs on components, putting quality and performance in jeopardy? Make your systems ultra efficient with Metal Work Pneumatics.



METAL WORK PNEUMATIC

ISO 9001 QUALITY MANAGEMENT SYSTEM

ISO 14001 ENVIRONMENTAL MANAGEMENT SYSTEM

OHSAS 18001 HEALTH AND SAFETY MANAGEMENT SYSTEM

SYNTESI MONITORED DUMP VALVE


Fluid-Air Components Ltd

PNEUMATICALLY OPERATED VALVES

Pilot Valves

Technical Data	1/8"	1/4"	3/8"	1/2"
Operating Pressure Bar	Vacuum to 10			
Minimum pilot pressure:				
monostable bar	2.5 to 10			
bistable bar	1 to 10			
Operating temperature range	-10°C to +60°C			
Nominal diameter mm	5	7.5	13.3	15
Conductance C Nl/min - bar	121.43	264.26	505.52	971.43
Critical ratio b bar/bar	0.32	0.27	0.32	0.43
Flow rate at 6 bar ΔP 0.5 bar Nl/min	400	750	1560	3200
Flow rate at 6 bar ΔP 1 bar Nl/min	550	1100	2150	4600
TRA / TRR monostable at 6 bar ms	6/15	7/15	5/28	16/46
TRA / TRR bistable at 6 bar ms	7/7	7/7	13/13	16/16


3/2 Pilot/Spring Valve



G1/8 Ports

9149	Description
7010010200	3/2 G1/8"

3/2 Pilot/Spring Valve



G1/4 Ports

9149	Description
7020010200	3/2 G1/4"


3/2 Pilot/Spring Valve



G3/8 Ports

9149	Description
7040010400	3/2 G3/8" NO


3/2 Pilot/Spring Valve, NC



G3/8 Ports

9149	Description
7040010200	3/2 G3/8"


3/2 Pilot/Pilot Valve



G1/8 Ports

9149	Description
7010010100	3/2 G1/8"


3/2 Pilot/Pilot Valve



G1/4 Ports

9149	Description
7020010100	3/2 G1/4"

3/2 Pilot/Pilot Valve, NC




G3/8 Ports

9149	Description
7040010100	3/2 G3/8" NC

5

PNEUMATICALLY OPERATED VALVES


5/2 Pilot/Spring Valve



G1/8 Ports

9149	Description
7010011100	5/2 G1/8"


5/2 Pilot/Spring Valve



G1/4 Ports

9149	Description
7020011100	5/2 G1/4"


5/2 Pilot/Spring Valve



G3/8 Ports

9149	Description
7040011100	5/2 G3/8"


5/2 Pilot/Spring Valve



G1/2 Ports

9149	Description
7030011100	5/2 G1/2"


5/2 Pilot/Pilot Valve



G1/8 Ports

9149	Description
7010011200	5/2 G1/8


5/2 Pilot/Pilot Valve



G1/4 Ports

9149	Description
7020011200	5/2 G1/4


5/2 Pilot/Pilot Valve



G3/8 Ports

9149	Description
7040011200	5/2 G3/8"


5/2 Pilot/Pilot Valve



G1/2 Ports

9149	Description
7030011200	5/2 G1/2"

5/2 Pilot/Pilot Valve (Differential)




G3/8 Ports

9149	Description
7040011300	5/2 G3/8"

Fluid-Air Components Ltd

PNEUMATICALLY OPERATED VALVES


5/3 Pilot/Spring/Pilot Valve, CC



G1/8 Ports

9149	Description
7010012100	5/3 G1/8" CC


5/3 Pilot/Spring/Pilot Valve, OC



G1/8 Ports

9149	Description
7010012200	5/3 G1/8" OC


5/3 Pilot/Spring/Pilot Valve, CC



G1/4 Ports

9149	Description
7020012100	5/3 G1/4" CC


5/3 Pilot/Spring/Pilot Valve, OC



G1/4 Ports

9149	Description
7020012200	5/3 G1/4" OC


5/3 Pilot/Spring/Pilot Valve, CC



G3/8 Ports

9149	Description
7040012100	5/3 G3/8" CC


5/3 Pilot/Spring/Pilot Valve, OC



G3/8 Ports

9149	Description
7040012200	5/3 G3/8" OC


5/3 Pilot/Spring/Pilot Valve, CC



G1/2 Ports

9149	Description
7030012100	5/3 G1/2" CC

5/3 Pilot/Spring/Pilot Valve, OC




G1/2 Ports

9149	Description
7030012200	5/3 G1/2" OC

PNEUMATICALLY OPERATED VALVES


5/3 Pilot/Spring/Pilot Valve, PC



G1/8 Ports

9149	Description
7010012300	5/3 G1/8" PC


5/3 Pilot/Spring/Pilot Valve, PC



G3/8 Ports

9149	Description
7040012300	5/3 G3/8" PC


5/3 Pilot Valve, PC



G1/4 Ports

9149	Description
7020012300	5/3 G1/4" PC

5/3 Pilot/Spring/Pilot Valve, PC



G1/2 Ports

9149	Description
7030012300	5/3 G1/2" PC

FT PRO




For **Silencers**
see page **631**

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES

Series 3, In-line Pneumatically Operated Valves








5/2 Pneumatic/Pneumatic Bistable


0158	Thread
358 033	G1/8"
354 033	G1/4"
Tech Sheet 1847	

5/3 Pneumatic Open Centres

0158	Thread
378 033	G1/8"
374 033	G1/4"
Tech Sheet 1847	










5/3 Pneumatic Closed Centres

0158	Thread
368 033	G1/8"
364 033	G1/4"
Tech Sheet 1847	

5/3 Pneumatic Pressure Centres

0158	Thread
388 033	G1/8"
384 033	G1/4"
Tech Sheet 1847	


Series 3, In-line Pneumatically Operated Valves





3/2 Pneumatic/Spring N/C


0158	Thread
338 035	G1/8"
338L 035	G1/8"
334 035	G1/4"
Tech Sheet 1847	





3/2 Pneumatic/Pneumatic Bistable

0158	Thread
338 033	G1/8"
338L 033	G1/8"
334 033	G1/4"
Tech Sheet 1847	





Series 3, 5/2 Pneumatic/Spring Monostable

0158	Thread
358 035	G1/8"
354 035	G1/4"
Tech Sheet 1847	

Fluid-Air Components Ltd

Pilot & Solenoid Valves



Viking Xtreme Valve 3/2 Pilot Operated G1/2"

0681	Actuator	Return	Thread BSPP
P2LDX314PS	Pilot	Spring	1/2"



Viking Xtreme G1/2" Valves Pilot & Solenoid 5/2

0681	Actuator	Return	Voltage (if applicable)
P2LDX514ESNXXX	Electric	Spring Return	Less Solenoid



ISOMAX Solenoid Operated Valves ISO 1 & 2

0681	ISO Size	Actuator	Return	Voltage (if applicable)
DX1-621-BN	1 - 43mm	Electric	Spring Return	Less Solenoid
DX2-621-BN	2 - 56mm	Electric	Spring Return	Less Solenoid
DX1-606-BN	1 - 43mm	Electric	Electric	Less Solenoid
DX2-606-BN	2 - 56mm	Electric	Electric	Less Solenoid



Side Ported Manifold & End Plates ISO 1 & 2

0681	Description	Ported	Port Size	ISO Size
P2N-EM512MD	Manifold	Side	1/4" BSPP	1 - 43mm



Heavy-duty Pilot 3/2 Poppet Valve G1/2"

0681	Actuator	Return
B203P	Pilot	Spring

Fluid-Air Components Ltd

3/2 PNEUMATIC VALVES

PNEUMAX

Series 224 Pilot



Pilot/Spring Return, BSPP

0110	Thread	Function
224.32.11.1	1/4"	Normally Closed



Pilot/Pilot, BSPP

0110	Thread	Function
224.32.11.11	1/4"	Normally Closed

Series T200 Pilot



Pilot/Spring Return, BSPP

0110	Thread	Function
T228.32.11.1	1/8"	Normally Closed



Pilot/Pilot, BSPP

0110	Thread	Function
T228.32.11.11	1/8"	Normally Closed

Series T224 Tecno Eco



Pilot/Spring Return

0110	Thread	Function
T224.32.11.1	1/4"	Normally Closed



Pilot/Pilot

0110	Thread	Function
T224.32.11.11	1/4"	Normally Closed

Series T400 Tecno Eco Pilot



Pilot/Spring Return, BSPP

0110	Thread	Function
T488.32.11.1	1/8"	Normally Closed



Pilot/Pilot, BSPP

0110	Thread	Function
T488.32.11.11	G1/8"	Normally Closed

Series 212 Pilot



Pilot/Spring Return, BSPP

0110	Thread	Function
212/2.32.11.1	1/2"	Normally Closed



Pilot/Pilot, BSPP

0110	Thread	Function
212/2.32.11.11	1/2"	Normally Closed

200 Series Pilot Valves - 1/8"



200 Series Pilot/Spring Return 3/2 - G1/8"

0110	Description	Port Size
228.32.11.1	Pilot-Spring	G1/8"



200 Series Amplified Pilot/Spring Return 3/2 - G1/8"

0110	Description	Port Size
228.32.13.1	Amplified Pilot-Spring	G1/8"



200 Series Pilot/Pilot 3/2 - G1/8"

0110	Description	Port Size
228.32.11.11	Pilot-Pilot	G1/8"
228.32.11.12	Pilot-Ext Differential	G1/8"

FAC Fluid-Air Components Ltd

5/2 PNEUMATIC VALVES

PNEUMAX

Series 200 Pilot



Pilot/Spring Return, BSPP

0110	Thread
228.52.11.1	1/8"



Amplified Pilot/Spring Return, BSPP

0110	Thread
228.52.13.1	1/8"



Pilot/Pilot

0110	Thread
228.52.11.11	1/8"

Pilot/Pilot Differential External

0110	Thread
228.52.11.12	1/8"

Series 224 Pilot



Pilot/Spring Return, BSPP

0110	Thread
224.52.11.1	1/4"



Pilot/Pilot, BSPP

0110	Thread
224.52.11.11	1/4"

Series 212 Pilot



Pilot/Spring Return, BSPP

0110	Thread
212/2.52.11.1	1/2"



Pilot/Pilot, BSPP

0110	Thread
212/2.52.11.12	1/2"

Series T200 Tecno Pilot



Pilot/Spring Return, BSPP

0110	Thread
T228.52.11.1	1/8"



Pilot/Pilot, BSPP

0110	Thread
T228.52.11.11	1/8"

Series T224 Tecno Eco



Pilot/Spring Return, BSPP

0110	Thread
T224.52.11.1	1/4"



Pilot/Pilot, BSPP

0110	Thread
T224.52.11.11	1/4"

Series T400 Tecno Pilot



Pilot/Spring Return, BSPP

0110	Thread
T488.52.11.1	1/8"



Pilot/Pilot, BSPP

0110	Thread
T488.52.11.11	1/8"

5/3 PNEUMATIC VALVES

PNEUMAX

Series 224 Pilot



Pilot/Pilot, BSPP

0110	Thread	Function
224.53.31.11.11	1/4"	Closed Centre

Series 224 Tecno Eco



Pilot/Pilot, BSPP

0110	Thread	Function
T224.53.31.11.11	1/4"	Closed Centre
T224.53.32.11.11	1/4"	Open Centre

Series T400 Tecno Eco



Pilot/Pilot, BSPP

0110	Thread	Function
T488.53.31.11.11	1/8"	Closed Centre

Fluid-Air Components Ltd

LOGIC VALVES

Medium: Clean compressed air. Filtered (40µm) and lubricated
Body Material: Aluminium alloy
Seals: Nitrile

Working Temperature: 0°C to +60°C

Working Pressure: 2 to 10 bar

2 Year Warranty

NOT Valve



4mm Push-in Connection

9149
KP080394
Tech Sheet 3098

AND Valve



4mm Push-in Connection

9149
KP080254
Tech Sheet 3098

YES Valve



4mm Push-in Connection

9149
KP080494
Tech Sheet 3098

Mono-stable Valve



4mm Push-in Connection

9149
KP040034
Tech Sheet 3098

OR Valve



4mm Push-in Connection

9149
KP080214
Tech Sheet 3098

FT PRO



For **Pneumatic Tube** see pages **895-904**

FAC Fluid-Air Components Ltd

PNEUMATIC LOGIC VALVES

Introduction

Logic elements are available with five different functions:
OR, AND, NOT, YES, MEMORY.

Main features common to all elements:

Adaptor for DIN rail bar (DIN EN 50022) integral with the body

Built-in pressure indicator

Pipe locking system using Ø 4 built-in fitting

Technical Specification

- Nominal diameter: 2.7mm
- Flow rate at 6 bar P 1 bar: 100 Nl/min
- Reset:
  AND, OR via compressed air
  YES, NOT via mechanical spring

Operating Temperature Range:
-10°C to 60°C

Pressure Range:
YES, MEMORY, OR, AND from 0 to 8 bar pilot pressure from 1.5 to 8 bar
NOT from 0.4 to 6 bar

Logic Elements



OR

9149	Description
W3604000001	Function 4mm Fittings



AND

9149	Description
W3604000002	Function 4mm Fittings



NOT

9149	Description
W3604000003	Function 4mm Fittings



YES

9149	Description
W3604000004	Function 4mm Fittings



MEMORY

9149	Description
W3604000005	Function 4mm Fittings

Technical Specification

Delay setting range: from 0 to 30, at 6 bar

Signal shut off time: <0.1s



Timer

9149	Description
W3604000006	Timer with 4mm Fittings

Fluid-Air Components Ltd

PNEUMATIC CONTROL

Pneumatic Visual Indicators



Maximum Working Pressure:
8 bar

22mm Diameter

0113	Colour	To Fit Tube Size mm
CZT-84 150 201	Red	4
CZT-84 150 202	Green	4
CZT-84 150 203	Yellow	4
Tech Sheet 1508		

DIN Rail Mountable Pressure & Vacuum Switches



IP20

0113	Function	To Fit Tube Size mm	Manual Override Detail	Switching Adjustment
CZT-81 513 501	Pressure Switch	4	Yes	2 to 8 bar
CZT-81 513 502	Pressure Switch	4	No	2 to 8 bar
CZT-81 513 552	Vacuum Switch	4	No	-0.3 to -0.8 bar
Tech Sheet 1509				

Sub-base Mountable Pressure & Vacuum Switches



IP54

0113	Manual Override Detail	Switching Adjustment
CZT-81 513 510	Yes	2 to 8 bar
Tech Sheet 1510		

Sub-bases



Push-in

0113	Type	To Fit Tube Size mm
CZT-81 532 001	Single/End Sub-base, DIN Rail Mount	4
CZT-81 532 102	Associable Sub-base, DIN Rail Mount	4
CZT-81 532 104	Single Sub-base, 2 x M4 Screw Mount	4
Tech Sheet 20085		

Timers



- 2.7mm Orifice, 170 L/min
- Accuracy +/- 5%.
- Positive output gives a time delay then an output.
- Greater than 107 operations.
- Minimum Reset <0.1 sec.
- Negative output gives an immediate output that switches off after a delay.

Working Temperature:
-5 to +50°C

Sub-base Mounted

0113	Timer Range	Switching Output
CZT-81 503 710	0.1 to 15 Adjustable	Positive
CZT-81 506 710	0.1 to 15 Adjustable	Negative
CZT-81 503 720	0.1 to 30 Adjustable	Positive
CZT-81 506 720	0.1 to 30 Adjustable	Negative
CZT-81 503 725	0.1 to 60 Adjustable	Positive
CZT-81 507 540	0.4 Fixed Single Impulse Gen.	-
CZT-81 507 720	0.02 to 8 Hz Adj. Freq. Gen.	-
Tech Sheet 1513		

Logic Elements



Flow rate based on 6 bar pressure rating.

Working Pressure:
2 to 8 bar

Plug-in

0113	Type	To Fit Tube Size mm	Litres per min
CZT-81 540 001	OR Gate	4	170
CZT-81 540 005	OR Gate	6	200
CZT-81 541 001	AND Gate	4	150
CZT-81 541 005	AND Gate	6	200
CZT-81 545 001	Vacuum	4	-
Tech Sheet 1511			

2.7mm orifice, 170 L/min. Greater than 107 operations

Function:


OR Element:
The output signal "S" is present when a signal at "a" OR "b" is present. S = a OR b.

AND Element:
The output signal "S" is present only when signals "a" AND "b" are present simultaneously. S = a AND b.

YES Element:
The output signal "S" is only present when the pilot is present. S = a YES b.

NOT Element:
The output signal "S" is present only if the input signal "a" is NOT present. The output signal is therefore the inverse of the pilot signal. S = NOT a. If the supply port is connected to a 2nd input "b" the function obtained is called Inhibition. S=NOT a AND b.

Note: Switching time = <4ms exception OR and AND.



Working Temperature:
-5 to +50°C

Working Pressure:
2 to 8 bar

Sub-base Mounted


0113	Type	Colour
CZT-81 521 501	OR Gate	Blue
CZT-81 522 501	AND Gate	Green
CZT-81 501 025	YES Gate	Yellow
CZT-81 503 025	Yes Gate (Threshold)	Orange
CZT-81 504 025	NO Gate (Simple & Inhibition)	Light Grey
CZT-81 506 025	NO Gate (Threshold)	Dark Grey
Tech Sheet 1512		

Interface Modular Valve Range

Ideal for DIN rail mounting applications.
Mechanical life 5 x 107.
Switching time 5 to 15ms.
IP rating when used with Sub-base IP20.
IP rating when used with DIN connector IP65.

Working Pressure:
1 to 8 bar

Note: Flow rate based on 6 bar.
Coil Consumption: 1W
Voltage: 24V DC
LPM: 25 L/min



Miniature Solenoid Valves & Sub-bases

0113	Function	Coil Consumption	Voltage	LPM
CZT-81 519 032	3 /2 NC without Manual Override	1W	24VDC	25
CZT-81 519 632	3/2 NC with Maintained Manual Override	1W	24VDC	25
Tech Sheet 1515				

Accessories



LED Indicator

0113	Type	Voltage
CZT-81 513 052	Visual LED Indicator	24V AC/DC 50-60Hz
Tech Sheet 20741		

Fluid-Air Components Ltd

COUNTERS

Ratchet Counters

Rugged 4 and 5 figure hand-operated reset counters with push button actuator for easy operation. It can be used for unlimited counting chores. Traffic analysis, attendance, sporting events, farming and ranching operations, inventory control, surveys, laboratory studies, production counting and a variety of merchandises.



4 Figure Ratchet Tally Counter with Reset

0065
2089-3731
Tech Sheet 20088



5 Figure Ratchet Counter with Reset

0065
2089-3764
Tech Sheet 20088

PNEUMATIC TIMERS & COUNTERS

Timers 5/2

Working Temperature:
-10 to +60°C

Pressure Range:
1.2 to 10 bar



M5 Thread

0047	Timer Range
KU-54.022	3-100 sec, Normally Open or Normally Closed
KU-54.023	0.3-10 min, Normally Open or Normally Closed
KU-54.024	3-100 min, Normally Open or Normally Closed
Tech Sheet 175	

Timers 3/2

Working Pressure:
2 to 6 bar



M5 Thread, NC

0047	Timer Range
KU-51.020.03.00	2-30 sec, Normally Closed
KU-51.020.30.00	20-300 sec, Normally Closed
Tech Sheet 176	

Pneumatic Preset Counters

Working Temperature:
0 to +60°C

Pressure Range:
2 to 8 bar



5 Digit

0047	Thread
KU-50.680	M5
Tech Sheet 177	



6 Digit

0047	Thread
KU-50.670	M5
Tech Sheet 178	

Fluid-Air Components Ltd

SPECIALIST VALVES

Working Temperature:
0°C to +60°C

2 Year Warranty

Impulse Valves

Working Pressure:
2 to 10 bar



Normally Open, 1/8" BSPP

9149
KP100014
Tech Sheet 3099

Working Pressure:
2 to 10 bar



Normally Closed, 1/8" BSPP

9149
KP100094
Tech Sheet 3099

Oscillating Valves

Working Pressure:
2 to 10 bar



Continuous Cycle, 1/4" BSPP

9149
KP010444
Tech Sheet 3100

Working Pressure:
2 to 10 bar



Pneumatically Piloted, 1/4" BSPP

9149
KP010464
Tech Sheet 3100

Flip Flop Valve

Working Pressure:
3 to 10 bar



Pneumatically Piloted, 1/4" BSPP

9149
KP100354
Tech Sheet 3103

SPECIALIST VALVES

FT PRO

Working Temperature:
0°C to +60°C

2 Year Warranty

High Flow Pneumatic Timer for Automatic Return

Working Pressure:
2 to 10 bar



1/8" BSPP

9149
KP000744
Tech Sheet 3101

Vacuum Driven Liquid Sprayer

Working Pressure:
3 to 8 bar



M5 Thread

9149
KP2005
Tech Sheet 3102

Two Hand Safety Unit

Working Temperature:
0°C to +60°C

Working Pressure:
3 to 8 bar

The pre-assembled unit is specially designed with the operator's safety in mind. The unit requires both hands of the operator to function; if both 3/2 button valves are not activated within 0.5 seconds of each other the unit will not operate.



4mm Push-in

0341
KP081564
Tech Sheet 3099



Two Hand Safety Base Unit, 1/8" BSPP

9149
KPBU081564
Tech Sheet 3099


FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO VALVES

Technical Data

ISO Size	Operating Pressure	Operating Temperature Range	Nominal Diameter	Flow Rate at 6 bar ΔP 0.5 bar	Flow Rate at 6 bar ΔP 1 bar
1	Vacuum ÷≥10 bar	-10ºC to 60ºC≥	7.5mm	700 Nl/min	1100 Nl/min
2			12mm	1800 Nl/min	2700 Nl/min

Pneumatic ISO 5599 Valves





ISO size 1.





5/2 Pilot/Spring

9149	ISO Size
7051011100	1
7052011100	2


Pneumatic ISO 5599 Valves




5/2 Pilot/Pilot


9149	ISO Size
7051011200	1
7052011200	2

Pneumatic ISO 5599 Valves





ISO size 2.






5/3 Pilot/Pilot Closed Centres

9149	ISO Size
7051012100	1
7052012100	2


Pneumatic ISO 5599 Valves



5/3 Pilot/Pilot Open Centres

9149	ISO Size
7051012200	1
7052012200	2

Pneumatic ISO 5599 Valves



5/3 Pilot/Pilot Pressurised Centres


9149	ISO Size
7051012300	1
7052012300	2

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ISO VALVES

Solenoid ISO 5599 Valves

ISO size 1.







5/2 Solenoid/Spring

9149	ISO Size
7051021100	1
7052021100	2

Solenoid ISO 5599 Valves



5/2 Solenoid/Solenoid

9149	ISO Size
7051021200	1
7052021200	2


FT PRO

For **Pre wired moulded DIN Plugs** see page **1043**



Solenoid ISO 5599 Valves

ISO size 2.







5/2 Solenoid/Solenoid Closed Centres

9149	ISO Size
7051022100	1
7052022100	2

Solenoid ISO 5599 Valves



5/2 Solenoid/Solenoid Open Centres

9149	ISO Size
7051022200	1
7052022200	2

Solenoid ISO 5599 Valves



5/3 Solenoid/Solenoid Pressurised Centres

9149	ISO Size
7051022300	1
7052022300	2

Fluid-Air Components Ltd


ISO VALVES

Safe Air Series Solenoid Spring Valves ISO 5599/1

- Nominal Diameter 7.5
- Flow Rate at 6 bar Δp 0.5 bar 700 Nl/min
- Flow rate at 6 bar Δp 1bar 1100 Nl/min

Operating Temperature Range:
-10°C to 60°C

Operating Pressure:
2.5 to 10 bar





ISO 1, 2.5 Metre, 3 Wires


9149	Description
7057021100	Solenoid/Spring
7057021400	Solenoid/Spring Pilot

Safe Air Series Solenoid Spring Valves ISO 5599/1

- Nominal Diameter 12
- Flow Rate at 6 bar Δp 0.5 bar 1800 Nl/min
- Flow Rate at 6 bar Δp 1bar 2700 Nl/min

Operating Temperature Range:
-10°C to 60°C

Operating Pressure:
2.5 to 10 bar



ISO 2, 2.5 ISO 1, 2.5 Metre, 3 Wires


9149	Description
7058021100	Solenoid/Spring
7058021400	Solenoid/Spring Pilot

Safe Air Series Solenoid Spring Valves ISO 5599/1

- Nominal Diameter 15
- Flow Rate at 6 bar Δp 0.5 bar 3200 Nl/min
- Flow Rate at 6 bar Δp 1bar 4600 Nl/min

Operating Temperature Range:
-10°C to 60°C

Operating Pressure:
2.5 to 10 bar



ISO 3, 2.5 Metre, 3 Wires

9149	Description
7059021100	Solenoid/Spring
7059021400	Solenoid/Spring Pilot

ACCESSORIES FOR ISO VALVES

Solenoid Coils for ISO 5599 Valves, Size 1

Technical Data

- Voltage tolerance: -10% to +15%
- Insulation class: F155
- Degree of protection: IP65 EN60529 with connector
- Avoid prolonged exposure to atmospheric agents
- Coil temperature range, 100% ED: +20°C to +70°C (ambient temperature)



22mm

9149	Description
W0215000101	24V DC
W0215000111	24V AC
W0215000121	110V AC
W0215000131	220V AC

9072	Description
M1NS2000	Form B Socket Connector

Solenoid Coils for ISO 5599 Valves, Size 2




30mm

9182	Description
W0210010100	24V DC
W0210011100	24V AC
W0210012100	110V AC
W0210013100	220V AC



9072	Description
G1NU2000	Form A Socket Connector

Sub-bases



For ISO 5599 Valves, Size 1

9258	Description
0228000150	1) Manifold Base, Side Ports
0228000155	2) Manifold Base, Bottom Ports
0228000200	3) Input End Plate
0228000210	5) Blind End Plate
0228000300	6) Intermediate Plate, Top Ports
0228000301	7) Intermediate Plate, Back Ports
0228000500	8) Blanking Plate
0228000400	9) Intermediate Diaphragm
0228000100	11) Individual Base, Side Ports
0228000700	13) Assembly Kit

Sub-bases

For ISO 5599 Valves, Size 2

9258	Description
0228001150	1) Manifold Base, Side Ports
0228001155	2) Manifold Base, Bottom Ports
0228001200	3) Input End Plate
0228001210	5) Blind End Plate
0228001300	6) Intermediate Plate, Top Ports
0228001301	7) Intermediate Plate, Back Ports
0228001500	8) Blanking Plate
0228001400	9) Intermediate Diaphragm
0228001100	11) Individual Base, Side Ports
0228001700	13) Assembly Kit


Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DIRECTIONAL CONTROL VALVES

CAMOZZI Automation

Series 9, Electro Pneumatically & Pneumatically Operated Valves*

Actuation:
Solenoid/Spring
- Coils also available separately





Size 1, 5/2 Manual Override Spring Return Single Solenoid Valves (951)

0158	Voltage
951 000 P15 23	Valve Body
2085-9179	24V 50/60Hz 3.5VA
2085-9195	110V 50/60Hz 3.5VA
2085-9203	240V 50/60Hz 4VA
2085-9211	48V DC 3W
2085-9229	110V DC 3W
2085-9245	24V DC 3W
2085-9252	6V DC 5W
2085-9260	12V DC 5W
2085-9278	24V DC 5W
2085-9286	48V DC 5W
2085-9294	110V DC 5W
Tech Sheet 1849	


Size 2, 5/2 Manual Override Spring Return Single Solenoid Valves (952)

0158	Voltage
952 000 P15 23	Valve Only
2085-9310	24V 50/60Hz 3.5VA
2085-9328	110V 50/60Hz 3.5VA
2085-9336	240V 50/60Hz 4VA
2085-9344	48V DC 3W
2085-9351	110V DC 3W
2085-9369	24V DC 3W
2085-9377	6V DC 5W
2085-9385	12V DC 5W
2085-9393	24V DC 5W
2085-9401	48V DC 5W
2085-9419	110V DC 5W
Tech Sheet 1849	

Size 3, 5/2 Manual Override Spring Return Single Solenoid Valves (953)

0158	Voltage
953 000 P15 23	Valve Only
2085-9435	24V 50/60Hz 3.5VA
2085-9443	110V 50/60Hz 3.5VA
2085-9450	240V 50/60Hz 4VA
2085-9468	48V DC 3W
2085-9476	110V DC 3W
2085-9484	24V DC 3W
2085-9492	6V DC 5W
2085-9500	12V DC 5W
2085-9518	24V DC 5W
2085-9526	48V DC 5W
2085-9534	110V DC 5W
Tech Sheet 1849	


***According to ISO 5599/1**






Size 1, 5/2 Manual Override Double Solenoid Valve (951)

0158	Voltage
951 000 P11 23	Valve Only
951 P11 23 U7H	24V 50/60Hz 3.5VA
951 P11 23 U7K	110V 50/60Hz 3.5VA
951 P11 23 U7J	240V 50/60Hz 4VA
951 P11 23 U72	12V DC 5W
951 P11 23 U73	24V DC 5W
951 P11 23 U74	48V DC 5W
951 P11 23 U76	110V DC 5W
951 P11 23 U77	24V DC 3W
Tech Sheet 1849	



Size 2, 5/2 Manual Override Double Solenoid Valve (952)

0158	Voltage
952 000 P11 23	Valve Only
952 P11 23 U7H	24V 50/60Hz 3.5VA
952 P11 23 U7K	110V 50/60Hz 3.5VA
952 P11 23 U7J	240V 50/60Hz 4VA
952 P11 23 U72	12V DC 5W
952 P11 23 U73	12V DC 5W
952 P11 23 U74	48V DC 5W
952 P11 23 U76	110V DC 5W
952 P11 23 U77	24V DC 3W
Tech Sheet 1849	



Size 3, 5/2 Manual Override Double Solenoid Valve (953)

0158	Voltage
953-000-P11-23	Valve Only
953 P11 23 U7H	24V 50/60Hz 3.5VA
953 P11 23 U7K	110V 50/60Hz 3.5VA
953 P11 23 U7J	240V 50/60Hz 4VA
953 P11 23 U72	12V DC 5W
953 P11 23 U73	12V DC 5W
953 P11 23 U74	48V DC 5W
953 P11 23 U76	110V DC 5W
953 P11 23 U77	24V DC 3W
Tech Sheet 1849	


Pneumatic spring return and 5/3 CO, CC options also available

Fluid-Air Components Ltd

DIRECTIONAL CONTROL VALVES


Series 9, Electro Pneumatically & Pneumatically Operated Valves*

*According to ISO 5599/1



5/2 Pneumatic/Pneumatic Return Valves (951, 952 & 953)

0158	Port Size
951 000 33	Size 1
952 000 33	Size 2
953 000 33	Size 3
Tech Sheet 1849	




5/3 Pneumatic Closed Centres (961, 962 & 963)

0158	Port Size
961 000 33	Size 1
962 000 33	Size 2
963 000 33	Size 3
Tech Sheet 1849	




Single Sub-base with Rear Outlets

0158	To Suit
901 G1A	ISO 1
902 G2A	ISO 2
903 G3A	ISO 3
Tech Sheet 1849	



5/2 Pneumatic Differential Return Valves (951, 952 & 953)

0158	Port Size
951 000 34	Size 1
952 000 34	Size 2
953 000 34	Size 3
Tech Sheet 1849	




5/3 Pneumatic Open Centres (971, 972 & 973)

0158	Port Size
971 000 33	Size 1
972 000 33	Size 2
973 000 33	Size 3
Tech Sheet 1849	



Manifold Sub-base with Common Exhaust & Inlets

0158	To Suit
901 C1A	ISO 1
902 C2A	ISO 2
903 C3A	ISO 3
Tech Sheet 1849	



5/2 Pneumatic Mechanical Spring Return Valves (951, 952 & 953)

0158	Port Size
951 000 35	Size 1
952 000 35	Size 2
953 000 35	Size 3
Tech Sheet 1849	



Single Sub-base with Side Outlets

0158	To Suit
901 F1A	ISO 1
902 F2A	ISO 2
903 F3A	ISO 3
Tech Sheet 1849	



End Block for Manifold Sub-base

0158	To Suit
901 H1	ISO 1
902 H2	ISO 2
903 H3	ISO 3
Tech Sheet 1849	

Fluid-Air Components Ltd

SPECIAL PURPOSE VALVES

In-line Progressive Starter

The in-line progressive starter is a valve that regulates the flow of air until the outlet pressure reaches a certain value, at which the valve opens and allows air to flow at full rate.

This valve can be used to control a group of valves or a single valve, it can also be mounted between another valve and an actuator.

The air that enters inlet 1 passes through a choke that has a knob adjustment to control the flo . The valve opens completely when the outlet pressure reaches about 60% of the inlet pressure. If the air supply is switched off, the valve discharges air from outlet 2 to inlet 1.

Working Temperature:
-10°C to 70°C

Maximum Working Pressure:
10 bar



1/4" & 1/2"


9149	Thread
W3606000002	G1/4"
W3606000004	G1/2"

PRESSURE REGULATOR ASSEMBLY

Line-on Line, RMV

Valves
Flow-rate at 6.3 bar DP 1 bar (Nl/min): 140
Functional denomination: Regulator
Thread Type: Cylindrical gas
Threaded Port: 1/8"

Temperature:
-10°C to 50°C





RMV, 1/8"

9149	Description
9061601	Line on Line RMV 1/8" Pressure Regulator Assembly

Fluid-Air Components Ltd

PRESSURE & VACUUM SWITCHES

Adjustable Pressure Switch

This type of pressure switch features a high degree of miniaturisation and a modern attractive design.

It can be installed in any position and also mounted onto a wall by means of two transversal holes.

In order to reduce wiring times, it is supplied ready assembled with a 2-metre electric cable or an M8 connector with a 300-mm cable.

The contact is the switching type, which means it can be normally open or normally closed

A knurled push-lock handle is provided for regulation



Working Temperature:
+50°C

Maximum Working Pressure:
15 bar

With 2 Metre Cable

9149	Thread
9000401	1/8"


Adjustable Pressure Switch

With M8 Connector & 300mm Cable

9149	Thread
9000402	1/8"

Digital Pressure Switch

The digital pressure switch can be used to transmit electric pressure signals and also display the pressure instantly. The signal is transmitted for two settable pressure values and with an analogue voltage signal. The values are clearly displayed on a LED video and different parameters can be entered from the keypad. Hysteresis can be adjusted and the unit of measurement for pressure can be modified. Two compressed air ports are provided, one at the back and one on the bottom. The pressure switch comes with a threaded plug in the bottom port. If you wish to connect to this port, merely unscrew the plug and screw it into the back port. A kit of accessories is provided for fixing to the top or wall, or to a panel.



Maximum Working Pressure:
10 bar

With Digital Display Showing Pressure Reading

9149
9000600

Security Knob

NOTE: Pull outwards to remove the knob from the pressure switch on the unit. Insert the security knob and regulate the pressure switch. Then press the handle firmly to lock it in position. If the pressure switch needs to be reset, remove the security knob by forcing it laterally with a screwdriver.



To suit 9000401 & 9000402

9149
9200703

SPECIAL PURPOSE VALVES

Two Hand Safety Valve

Technical Specifications


- Compressed air couplings: push-in fittings for Ø4mm pipe
- Fluid: filtered, non-lubricated compressed air
- Standard: EN574 type IIIA, TUV approved, certified M6020244919001
- Synchronisation, maximum time between two signals: 0.4 sec
- De-activation time, with 1000mm maximum pipe length: <0.05 sec
- Actuation: pneumatic
- Reset: spring operated
- Nominal diameter: 2.7mm
- Mounting position: any direction


Materials

- Body: anodised aluminium
- Internal parts: brass and technopolymer
- Gaskets: NBR
- Spring: alloy steel

Working Temperature:
-10°C to +60°C

Working Pressure:
2.5 to 8 bar





4mm Push-in Fittings

9149
W3605000001

Complete Two Handed Push Button Assembly



4mm Push-in Connections

9149	Description
0227700000	4mm OD Push-in Inlets & Outlets

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PNEUMATIC VIBRATORS

CORN • CEMENT • CHEMICAL • POWDERS • SAND • GRAVEL



Pneumatic Ball Vibrators

BSPP

0314	Thread	Min Pressure Bar	Max Pressure Bar	Air Consumption in Litres at 6 Bar
JM8	1/4"	2	6	195
JM10	1/4"	2	6	200
JM13	1/4"	2	6	225
JM16	1/4"	2	6	280
JM20	1/4"	2	6	340
JM25	1/4"	2	6	425
JM30	3/8"	2	6	570
JM36	3/8"	2	6	675
Tech Sheet 1012				

- The JM range of ball vibrators produces a rotative vibration with infinitely variable amplitude and frequency. The frequency is controlled by air pressure. The vibrator is designed to perform the following activities: moving, feeding, compacting and/or separating of all kinds of materials such as chemical powders, corn, sand, gravel and cement, etc.
- It is designed for indoor and outdoor applications but not to be submerged in any kind of liquid.

Maximum Working Temperature: +100°C (220°F)

Maximum Working Pressure: 6 bar

Pneumatic Turbine Vibrators

BSPP

0314	Thread	Min Pressure Bar	Max Pressure Bar	Air Consumption in Litres at 6 Bar
JMT8	1/8"	2	6	120
JMT10	1/8"	2	6	120
JMT13	1/4"	2	6	290
JMT16	1/4"	2	6	290
JMT20	1/4"	2	6	455
JMT25	1/4"	2	6	455
JMT30	3/8"	2	6	745
JMT36	3/8"	2	6	745
Tech Sheet 1013				

- The JMT range of turbine vibrators produces a rotative vibration with infinitely variable amplitude and frequency. The frequency is controlled by air pressure. The vibrator is designed to perform the following activities: moving, feeding, compacting and/or separating of all kinds of materials such as chemical powders, corn, sand, gravel and cement, etc.

Maximum Working Temperature: +100°C (220°F)

Maximum Working Pressure: 6 bar

Piston Vibrators

Aluminium, BSPP

0314	Thread	Min Pressure Bar	Min Pressure Bar	Air Consumption in Litres at 6 Bar
KFP-12-M	1/8"	2	6	20
KFP-18-M	1/8"	2	6	55
KFP-25-M	1/4"	2	6	88
KFP-35-M	1/4"	2	6	145
Tech Sheet 10158				

Fluid-Air Components Ltd

INDUSTRIAL VIBRATORS

VIBTEC
Vibration Solutions

Model K Pneumatic Ball Vibrators



0024	VPM/N	BSP
K8	35000/360N	1/4"
K10	34000/710N	1/4"
K13	22500/870N	1/4"
K16	19500/1100N	1/4"
K20	16000/1720N	1/4"
K25	14000/2050N	1/4"
K30	12500/3210N	3/8"
K36	10000/4050N	3/8"

Model GT Pneumatic Turbine Vibrators



0024	VPM/N	BSP
GT4	15000/200N	1/8"
GT6	12500/210N	1/8"
GT8	46000/2910N	1/8"
GT10	37500/2400N	1/8"
GT13	33000/3730N	1/4"
GT16	24000/3160N	1/4"
GT20	23000/5520N	1/4"
GT25	17000/5070N	1/4"
GT30	16000/7540N	3/8"

Model DAR Pneumatic Roller Vibrators



0024	VPM/N	BSP
DAR4	25000/6690N	1/4"

Model FP Pneumatic Linear Vibrators



0024	VPM/N	BSP
FP12M	6700/74N	1/8"
FP25M	4200/504N	1/4"
FP35M	4600/1080N	1/4"

VMECA™



For **Suction Cups Range and Magic Grips**
see pages **707-760**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Compact Non-return Valves



Working Temperature:
-20°C to +150°C

Maximum Working Pressure: 145 psi
Cracking Pressure: 0.5 psi

Brass, Viton Seals, BSPP

0444	Thread
VFU8.V	1/8"
VFU4.V	1/4"
VFU3.V	3/8"
VFU2.V	1/2"

Tech Sheet 20354

Working Temperature: -10°C to +85°C
Maximum Working Pressure: 145 psi
Cracking Pressure: 0.5 psi

Brass, EPDM Seals

0444	Thread
VFU8.E	1/8"
VFU4.E	1/4"
VFU3.E	3/8"
VFU2.E	1/2"

Tech Sheet 20354

Ported Non-return Valves



Working Temperature:
-10°C to +85°C

Maximum Working Pressure: 145 psi
Cracking Pressure: 0.5 psi

Brass, Nitrile Seals, BSPP

0444	Thread
VUP8.M	1/8"
VUP4.M	1/4"

Tech Sheet 20355

Working Temperature: -20°C to +150°C
Maximum Working Pressure: 145 psi
Cracking Pressure: 0.5 psi

Brass, Viton Seals, BSPP

0444	Thread
VUP8.VM	1/8"
VUP4.VM	1/4"

Tech Sheet 20355

Working Temperature: -10°C to +85°C
Maximum Working Pressure: 145 psi
Cracking Pressure: 0.5 psi

Brass, EPDM Seals, BSPP

0444	Thread
VUP8.EM	1/8"
VUP4.EM	1/4"


Tech Sheet 20355

Air Pinch Valves

Control Pressure:
20 to 40 psi greater than material pressure

N.B: Air pinch valve sleeves can be easily and economically replaced when they wear out. Other body and sleeve material options are available on request.

Maximum Actuation Pressure: 90 psi



With Polypropylene Body & Buna Sleeve, BSPP

0253	Thread A	Thread B
PINCH-AP6372	1/4"	1/8"
PINCH-AP6304	3/8"	1/8"
PINCH-AP6252	5/8"	1/4"

Tech Sheet 10324

VALVES

Compact Non-return Valves, Brass



Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
8 bar (115 psi)
Cracking Pressure:
0.2 bar
Seal: Nitrile

Type 6062, Metric & BSPP

0090	Thread
6062-M5	M5
6062-18	1/8"
6062-14	1/4"
6062-38	3/8"
6062-12	1/2"

Tech Sheet 1607



Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
8 bar (115 psi)
Cracking Pressure: 0.2 bar

Type 6063, Male x Female, BSPP

0090	Thread
6063-18	1/8"
6063-14	1/4"
6063-38	3/8"
6063-12	1/2"

Tech Sheet 1607

Quick Exhaust Valves, Brass



Working Temperature:
-20°C to +80°C

Type 6050, Metric & BSPP

0090	Thread
6050-M5	M5
6050-18	1/8"
6050-14	1/4"
6050-38	3/8"
6050-12	1/2"
6050-34	3/4"
6050-1	1"

Tech Sheet 552

Push-in Non-return Valves



Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
8 bar

1020	OD mm
6064-4	4
6064-6	6
6064-8	8

Tech Sheet 1608

Fluid-Air Components Ltd

BALL & CHECK VALVES

stainless steel

Flow Control Regulators

Stainless steel flow control regulators control the speed of a pneumatic cylinder (models LE-7820 7822) or the speed of a chemical of food fluid carried (model 7822: for fluids compatible with FKM and PTFE seals) in aggressive environments or submitted to high mechanical or chemical constraints.

Designed without retention zones, these models are perfectly suitable for food applications or requiring frequent washing of installations.

Working Temperature: -15°C to +120°C

Working Pressure: 1 to 16 bar



In-line, 1 Way Adjustment, BSPP

1012	Thread
LE-7820 00 10	1/8"
LE-7820 00 13	1/4"
LE-7820 00 17	3/8"
LE-7820 00 21	1/2"
Tech Sheet 10320	

In-line, Bi-directional, BSPP

1012	Thread
LE-7822 00 10	1/8"
LE-7822 00 13	1/4"
LE-7822 00 17	3/8"
LE-7822 00 21	1/2"
Tech Sheet 10320	

Non-return Valves

Legris stainless steel non-return valves allow fluids to pass in one direction whilst blocking flow in the other direction. Robust and extremely compact, they are suitable for use as a safety item in all fluids circuits.

They are ideal for use in severe conditions and in aggressive environments.

Operation: A stainless steel valve blocks the fluid passage, when the pressure differential is lower than 0.25 bar.

Working Temperature: -20°C to +180°C

Working Pressure: 0.5 to 40 bar



Uni-directional, Female x Female, BSPP

1012	Thread	OD mm
LE-4890 10 10	1/8"	22
LE-4890 13 13	1/4"	22
LE-4890 17 17	3/8"	30
LE-4890 21 21	1/2"	30
LE-4890 27 27	3/4"	35
LE-4890 34 34	1"	42
Tech Sheet 10320		



Uni-directional, Female x Male, BSPP

1012	Thread	OD mm
LE-4892 10 10	1/8"	22
LE-4892 13 13	1/4"	22
LE-4892 17 17	3/8"	30
LE-4892 21 21	1/2"	30
LE-4892 27 27	3/4"	35
LE-4892 34 34	1"	42
Tech Sheet 10320		



Uni-directional, Male x Female, BSPP

1012	Thread	OD mm
LE-4891 10 10	1/8"	22
LE-4891 13 13	1/4"	22
LE-4891 17 17	3/8"	30
LE-4891 21 21	1/2"	30
LE-4891 27 27	3/4"	35
LE-4891 34 34	1"	42
Tech Sheet 10320		



Uni-directional, Female x Female, NPT

1012	Thread	OD mm
LE-4895 11 11	1/8"	22
LE-4895 14 14	1/4"	22
LE-4895 18 18	3/8"	30
LE-4895 22 22	1/2"	30
Tech Sheet 10320		

Adjustable Check Valves



Brass nickel plated

Female, BSPP

1012	Thread	Cracking Pressure Bar
LE-7930 10 10	1/8"	1 to 0.10
LE-7930 13 13	1/4"	1 to 0.10
LE-7930 17 17	3/8"	1 to 0.15
Tech Sheet 10660		

Adjustable Check Valves, Supply Version



Brass nickel plated

Male x Female, BSPP

1012	Thread	Cracking Pressure Bar
LE-7931 10 10	1/8"	1 to 0.10
LE-7931 13 13	1/4"	1 to 0.10
LE-7931 17 17	3/8"	1 to 0.15
Tech Sheet 10660		

Fluid-Air Components Ltd

VALVES

Auxiliary Valves

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar



Straight Union Check Valve, Tube x Tube

0018	OD mm
331.05.04	4
331.05.06	6
331.05.08	8
331.05.10	10
331.05.12	12
Tech Sheet 10329	



Conical Check Out Valve, Tube x BSPT

0018	OD mm	Thread
331.01.04.18	4	1/8"
331.01.06.18	6	1/8"
331.01.06.14	6	1/4"
331.01.08.18	8	1/8"
331.01.08.14	8	1/4"
331.01.10.38	10	3/8"
331.01.12.38	12	3/8"
331.01.12.12	12	1/2"
Tech Sheet 10329		



Conical Check In Valve, Tube x BSPT

0018	OD mm	Thread
331.02.04.18	4	1/8"
331.02.06.18	6	1/8"
331.02.06.14	6	1/4"
331.02.08.18	8	1/8"
331.02.08.14	8	1/4"
331.02.10.38	10	3/8"
331.02.12.38	12	3/8"
331.02.12.12	12	1/2"
Tech Sheet 10329		

Ball Valves

• Vaccum - 750mm 1.1Hg



Union Ball Valve, Tube x Tube

0018	OD mm
351.01.06.06	6
351.01.08.08	8
351.01.10.10	10
351.01.12.12	12
Tech Sheet 10330	



Straight Ball Valves, Tube x BSPP

0018	OD mm	Thread
351.03.06.18	6	1/8"
351.03.06.14	6	1/4"
351.03.08.18	8	1/8"
351.03.08.14	8	1/4"
351.03.08.38	8	3/8"
351.03.10.14	10	1/4"
351.03.10.38	10	3/8"
351.03.10.12	10	1/2"
351.03.12.38	12	3/8"
351.03.12.12	12	1/2"
Tech Sheet 10330		



90° Elbow Union Ball Valves, Tube x Tube

0018	OD mm
351.04.06.06	6
351.04.08.08	8
351.04.12.12	12
Tech Sheet 10330	



90° Elbow Union Ball Valves, Tube x BSPP

0018	OD mm	Thread
351.06.06.18	6	1/8"
351.06.06.14	6	1/4"
351.06.08.18	8	1/8"
351.06.08.14	8	1/4"
351.06.08.38	8	3/8"
351.06.10.14	10	1/4"
351.06.10.38	10	3/8"
351.06.10.12	10	1/2"
351.06.12.38	12	3/8"
351.06.12.12	12	1/2"
Tech Sheet 10330		

Fluid-Air Components Ltd

SILENCERS

Plastic Silencers

Working Temperature: 0°C to +75°C

Maximum Working Pressure: 10 bar



Granular Filling (Dynamic), POM Body, Male Thread, BSPP

0423	Thread
YPS-18	1/8"
YPS-14	1/4"
YPS-38	3/8"
YPS-12	1/2"
YPS-34	3/4"
YPS-1	1"
Tech Sheet 823	



PE Body, Male Thread, BSPP

0423	Thread
PS-M5	M5
PS-18	1/8"
PS-14	1/4"
PS-38	3/8"
PS-12	1/2"
PS-34	3/4"
Tech Sheet 823	



PE Body with Restrictor, Male Thread, BSPP

0423	Thread
RS-18	1/8"
RS-14	1/4"
RS-38	3/8"
RS-12	1/2"
Tech Sheet 823	



PE Body, Metric Push-in

0423	Stem OD mm
S03STPI-6	6
S03WBPI-8	8
S04STPI-10	10
S05STPI-12	12
Tech Sheet 823	



Granular Filling (Dynamic), Acetalic Resin Body, Male Thread, BSPP

0448	Thread
7070-1/8	1/8"
7070-1/4	1/4"
7070-3/8	3/8"
7070-1/2	1/2"
7070-3/4	3/4"
7070-1	1"
Tech Sheet 823	



Felt Filling (Static), Nylon Body, Male Thread, BSPPP

0448	Thread
7080-1/8	1/8"
7080-1/4	1/4"
7080-3/8	3/8"
7080-1/2	1/2"
7080-3/4	3/4"
7080-1	1"
Tech Sheet 823	

Steel Silencers



Single Ported, Male Thread, BSPP

0449	Thread
SLS050	1/2"
SLS075	3/4"
SLS100	1"
SLS125	1.1/4"
SLS150	1.1/2"
SLS200	2"
SLS250	2.1/2"
Tech Sheet 20351	



Double Ported, Male Thread, BSPP

0449	Thread
SLD050	1/2"
SLD075	3/4"
SLD150	1.1/2"
SLD200	2"
Tech Sheet 20351	

Stainless Steel Silencers

stainless steel



BSPP

0423	Thread
S70-18	1/8"
S70-14	1/4"
S70-38	3/8"
S70-12	1/2"
S70-34	3/4"
S70-1	1"

Stainless Steel Pad Silencers

Body: 304 stainless steel
Pad: 316 stainless steel

stainless steel



Metric & BSPP

0423	Thread
12020507	M5
12021007	1/8"
12021307	1/4"
12021707	3/8"
12022107	1/2"
12022707	3/4"
12023207	1"
Tech Sheet 20455	

Fluid-Air Components Ltd

Coned Brass & Sintered Bronze Silencers



7000, Male Thread, BSPP

0423	Thread
7000-1/8	1/8"
7000-1/4	1/4"
7000-3/8	3/8"
7000-1/2	1/2"
7000-3/4	3/4"
7000-1	1"

Tech Sheet 195



7030, Male Thread, NPT

0423	Thread
7030-1/8NPT	1/8"
7030-1/4NPT	1/4"
7030-3/8NPT	3/8"
7030-1/2NPT	1/2"
7030-3/4NPT	3/4"
7030-1NPT	1"

Tech Sheet 195



7030, Male Thread, Metric & BSPP

0423	Thread
7030-M5	M5
7030-1/8	1/8"
7030-1/4	1/4"
7030-3/8	3/8"
7030-1/2	1/2"
7030-3/4	3/4"
7030-1	1"

Tech Sheet 195



7040, Male Thread, Long, BSPP

0423	Thread
7040-1/8	1/8"
7040-1/4	1/4"
7040-3/8	3/8"
7040-1/2	1/2"
7040-3/4	3/4"

Tech Sheet 195



Square Head Silencer, BSPP

0423	Thread
12041000	1/8"
12041300	1/4"
12041700	3/8"
12042100	1/2"
12042700	3/4"
12043200	1"

Tech Sheet 195

Flat Brass & Sintered Bronze Silencers



7010, Male Thread, BSPP

0423	Thread
7010-M5	M5
7010-1/8	1/8"
7010-1/4	1/4"
7010-3/8	3/8"
7010-1/2	1/2"
7010-3/4	3/4"
7010-1	1"

Tech Sheet 195



7020, Male Thread, Metric & BSPP

0423	Thread
7020-M5	M5
7020-1/8	1/8"
7020-1/4	1/4"
7020-3/8	3/8"
7020-1/2	1/2"
7020-3/4	3/4"

Tech Sheet 195



7050, Male Thread, BSPP

0423	Thread
7050-1/8	1/8"
7050-1/4	1/4"
7050-3/8	3/8"
7050-1/2	1/2"

Tech Sheet 195

Round Brass Silencers



Metric & BSPP

0423	Thread
12100500	M5
12101000	1/8"
12101300	1/4"

Flush Brass Silencers



BSPP

0423	Thread
12001000	1/8"
12001300	1/4"
12001700	3/8"
12002100	1/2"
12002700	3/4"
12003200	1"

Miniature Silencers



Nickel Plated Brass, BSPP

1012	Thread
LE-0677 00 10	1/8"
LE-0677 00 13	1/4"
LE-0677 00 17	3/8"
LE-0677 00 21	1/2"
LE-0677 00 34	1"

Adjustable Brass Restricting Silencers



Metric & BSPP

0423	Thread
12090500	M5
12091000	1/8"
12091300	1/4"
12091700	3/8"
12092100	1/2"
12092700	3/4"
12093200	1"

Exhaust Silencer Restrictor



BSP

0423	Thread BSPP
ESR18	G1/8"
ESR14	G1/4"
ESR38	G3/8"
ESR12	G1/2"

ALWITCO MUFFLERS

Air Exhaust Muffle

- "The Original"... provides up to 85% noise reduction and 94% flow facto .
- Thoroughly proven on thousands of installations, the world-class Atomuffer® Air Exhaust Muffler expertly reduces Exponentially Perceived Noise (EPNdB) without impeding equipment performance. Its design takes explosive air exhaust noise discharged from valve exhaust ports and muffles it with optimized Constant elocity (CV) flow facto . Exhaust air flows softly to atmosphere free of noise, oil fog, and contaminates, providing a clean, comfortable and productive work environment.
- The Air Exhaust Muffler features a unique obstruction-free expansion chamber. Standard Air Exhaust Muffler construction includes aluminium end covers, zinc-plated steel components and a cellulose fibre element
- This design is recommended for general purpose air exhaust application for pressures up to 125 psi.

*Multi-chamber muffle



BSPT

9234	Thread BSPT	Model	Diameter Inches	Item Weight lbs	Flow SCFM
0121001	R1/8"	B01	1.84"	0.19	44
0121005	R1/2"	B05	3.15"	0.79	256
0121007	R3/4"	B07	3.40"	1.04	544
0121010	R1"	B10	3.90"	1.02	800
0121015	R1.1/2"	B15	5.25"	3.27	2080
0121030*	R3"	B30	7.00"	13.43	7200

Air Ejector Mufflers

- Featuring collimator inserts for concentrated air flo .
- Quickly and easily connected to any compressed air source. Concentrates the air stream in a narrow beam over a longer distance, delivering maximum force at a required point.
- Supplied as a complete unit with a cylindrical housing which can be directly attached to compressed air lines properly positioned for parts ejection or packaging requirements. Can be supplied with a standard plastic collimator insert or a special heat-resistant metal collimator insert (for use in locations with extremely high ambient temperatures)
- Separate collimator inserts also are available as a low-cost solution for applications where it is necessary to bore holes directly into a die and insert the collimator to provide exact air thrust.

Working Temperature:
+10°C to +48°C

Maximum Working Pressure:
8.6 bar



NPT

9234	Thread NPT	Model	Dimensions		Item Weight lbs	Flow SCFM
			Hex	Length		
0152018	1/8"	A18	0.43	1.37	0.02	22
0152038	3/8"	A38	0.69	2.20	0.06	45
0152048	1/2"	A48	0.87	2.75	0.11	68
0152068	3/4"	A68	1.06	3.15	0.21	75

End Flow Mufflers

- Directional flow in a compact design.
- Specifically designed for directing the flow of exhaust air in a single directio
- Discharges exhaust air axially through a unique honey-combed end cap that disperses the air blast and dampens exhaust noise.
- Lightweight and small, standard model is constructed of zinc-plated steel. All stainless steel construction available for very corrosive or sensitive situations. Ideal for use in most locations facing any direction.

Working Temperature:
+10°C to +48°C

Maximum Working Pressure:
8.6 bar



NPT

9234	Thread NPT	Model	Dimensions		Item Weight lbs	Flow SCFM
			Hex	Length		
0153028	1/4"	D28	0.56	1.75	0.04	72
0153038	3/8"	D38	0.69	2.20	0.07	136
0153068	3/4"	D68	1.06	3.15	0.22	400
0153108	1.1/4"	D108	1.68	4.50	0.62	800
0153128	1.1/2"	D128	2.00	5.00	0.78	880
0153168	2"	D168	2.37	5.50	1.29	1760

Bantam™ Muffle

- Ideal for use where space is limited.
- Tough and compact, the Bantam™ Muffler is durably constructed of corrosion-resistant metals to withstand shock and continuous heavy duty use under all types of conditions.
- The Bantam™ Muffler is designed with a precise distribution of peripheral openings in a zinc-plated steel and brass acoustical element, which softly disperses exhaust air uniformly over a 360° pattern. All stainless steel construction is also available for very corrosive or sensitive situations.
- Supplied with a standard pipe thread fitting, the Bantam™ Muffler can be attache directly to the exhaust ports of air-operated equipment.

Working Temperature:
+10°C to +48°C

Maximum Working Pressure:
12 bar



Steel

9234	Thread BSPT	Model	Dimensions		Item Weight lbs	Flow SCFM
			Hex	Length		
0554018	R1/8"	B18	0.43"	1.37"	0.02	44
0554048	R1/2"	B48	0.87"	2.75"	0.15	304
0554068	R3/4"	B68	1.06"	3.15"	0.27	560

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

EXHAUST FLOW REGULATOR/ SILENCERS & AIR FUSES

NORGREN

Exhaust Flow Regulator/ Silencers

- Compact, integral flow regulator and silencer units
- Captive regulating needle will not blow out when unscrewed
- Reduced dimensions

Medium:
Compressed air, filtered, lubricated or non-lubricated, inert gases

(T20)
Body and Washer: Nylon
Adjusting Screw: High tensile zinc electroplated steel
Silencer: Porous polyethylene

Mounting:
Directly in the exhaust port. hexagon key adjustment for flow regulation (T20

(0405)
Body and Nut: Brass
Needle: Plastic
Silencer: Sintered bronze

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
10 bar



Brass, BSPT

0036	Thread
04057100	1/8"
04057200	1/4"
04057300	3/8"
04057400	1/2"
Tech Sheet 10259	

Nylon, BSPT & Metric

0036	Thread
T20M0500	M5
T20C1800	1/8"
T20C2800	1/4"
T20C3800	3/8"
T20C4800	1/2"
Tech Sheet 10259	

Air Fuses

- Assists in complying with safety regulations
- Tamper proof
- Compact and safe design
- Low pressure drop
- Automatically resets after failure correction
- High corrosion resistance
- High air pressure rating

Medium:
Compressed air, filtered, lubricated and non-lubricated, inert gases


Mounting:
In-line two way valve. To be inserted between fixed air supply and flexible hose air line. See guidelines for typical installation

Type: Fixed uni-directional excess flow automatic shut off valve
Body: Aluminium
Spring: Stainless steel
Internal Parts: Brass

Working Temperature:
-20°C to +80°C
At low temperature ensure fuse is not subjected to icy conditions which may prevent function

Working Pressure:
Maximum 16 bar, minimum according to hose length
Drop pressure at shut-off flow
0,14 or 0,3 bar

PRODUCTS FOR SAFE SYSTEMS





BSPP

0036	Thread	Shut Off Flow Rate at 7 bar dm^3/s ±10%
T60C2890	1/4"	8.3
T60C3890	3/8"	19.14
T60C4890	1/2"	32.2
T60C6890	3/4"	48.3
T60C8890	1"	92
Tech Sheet 10510		

Shuttle Valves

- Allow two independent signal sources to be connected to a common pilot line
- Can be used to perform an 'OR' logic function
- Can be combined to operate from three or more sources
- Valves can be ganged together



BSPP

0036	Thread
T65C1800	G1/8
T65C2800	G1/4
Tech Sheet 20750	

PORTWEST



For **Portwest PPE** see page **1752-1760**

FAC Fluid-Air Components Ltd

BLOCK FORM FLOW REGULATORS & QUICK EXHAUST VALVES

NORGREN

Block Form Flow Regulators

- Compact size/low weight/ in-line units
- High flow performance
- Suitable for panel and wall mounting
- Adjustment can be locked
- Captive regulator needle will not blow out when unscrewed
- Adjusting knob position line

Medium: compressed air, filtered, lubricated or non-lubricated, inert gases
(M5) Body: Aluminium
Seals: Nitrile
Needle: Brass (1/8", 1/4", 3/8", 1/2")
Body: Aluminium alloy
Needle and Internal Parts: Brass
External Parts: Aluminium alloy

Working Temperature:
-20°C to +80°C

Working Pressure:
1 to 10 bar (0.3 to 10 bar for M5)



T1000 Series, BSPP & Metric

0036	Thread	Function
T1000M0500	M5	Uni-directional
T1000C1800	1/8"	Uni-directional
T1000C2800	1/4"	Uni-directional
T1000C3800	3/8"	Uni-directional
T1000C4800	1/2"	Uni-directional
	Tech Sheet 10248	

T1100 Series, BSPP

0036	Thread	Function
T1100C1800	1/8"	Bi-directional
T1100C2800	1/4"	Bi-directional
	Tech Sheet 10249	

Quick Exhaust Valves

Medium: Compressed air, filtered, lubricated or non-lubricated
Body and Cover: Zinc (1/8"-1/4") or Aluminium alloy (3/8"-1/2")

Seals: Nitrile
- Allows higher cylinder speeds to be achieved

Working Temperature:
-20°C to +80°C


Working Pressure:
0.5 to 10 bar



T70 Series, BSPP

0036	Thread
T70C1800	1/8"
T70C2800	1/4"
T70C3800	3/8"
T70C4800	1/2"
	Tech Sheet 10250

FT PRO



Customers who bought from this page also purchased
Brass & Nickel Plated Brass Hose Tails
see pages **1140-1147**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PROPORTIONAL VALVES

NORGREN

Valves

- Closed loop air pilot operated proportional pressure control valve
- Adjustable for a wide range of applications
- Fast response
- Low power consumption
- High flo
- **Medium:** Compressed air filtered to 50µm, non-lubricated
- **Flow:** Up to 1200 L/min at 11 bar supply pressure

Working Temperature:
-20°C to +50°C

Supply Pressure:
14 bar max.



VP50 Series Proportional Valves

0036	Control Signal	Output Bar
VP5010BJ111H00	0...10 V	0...10
VP5010BJ411H00	4...20 mA	0...10
VP5008BJ411H00	4...20 mA	0...8
VP5006BJ111H00	0...10 V	0...6
VP5006BJ411H00	4...20 mA	0...6
VP5002BJ111H00	0...10 V	0...2
VP5002BJ411H00	4...20 mA	0...2
Tech Sheet 10357		

- Proven low power technology
- Reliable, rugged, open-loop device
- Compact and flexible desig
- Excellent performance characteristics
- Output pressures up to 8 bar
- **Medium:** Oil free, dry air, filtered to 5µ

Working Temperature:
0°C to +60°C

Output Pressure:
0 to 1 bar (0 to 15 psi), 0 to 2 bar (0 to 30 psi),
0 to 4 bar (0 to 60 psi), 0 to 6 bar (0 to 90 psi),
0 to 8 bar (0 to 120 psi)

Supply Pressure:
Minimum 1.5 bar (22 psi) above maximum output pressure 10 bar (150 psi) maximum



VP12 Series Miniature Proportional Valves

0036	Control Signal	Output Bar
VP1204BG401Q00	4...20 mA	0...4
VP1204BG101Q00	0...10 V	0...4
VP1208BG401Q00	4...20 mA	0...8
VP1208BG101Q00	0...10 V	0...8
Tech Sheet 10358		

ADDITIONAL RANGES

NORGREN

Heavy-duty Flow Regulators Uni-directional

- Heavy-duty general-purpose flow regulator, suitable for in line and wall mount
- Additional port sizes available



BSPP

0036	Thread
M837	1/4"
Tech Sheet 20159	

Exhaust Port Filters

- Prevent the ingress of dirt with minimal flow restriction. Robust and compact. Screw directly into the exhaust port



BSPP

0036	Thread
M/1511	1/8"
M/1512	1/4"
M/1514	1/2"
M/1516	3/4"
M/1518	1"
Tech Sheet 20158	

Plastic Silencers



BSPP

0036	Thread
M/S1	1/8"
M/S2	1/4"
M/S3	3/8"
M/S4	1/2"
S/S6	3/4"
Tech Sheet 1356	

Quietaire Heavy-duty Silencers

- Brass mesh screen and aluminium construction provide improved flo , longer life and cleanable elements



Male Thread, BSPT

0036	Thread
MB001B	1/8"
MB002B	1/4"
MB003B	3/8"
MB004B	1/2"
MB006B	3/4"
MB008B	1"
Tech Sheet 2058	

Female Thread, BSPT

0036	Thread
MA001B	1/8"
MA002B	1/4"
MA003B	3/8"
MA004B	1/2"
MA006B	3/4"
Tech Sheet 2058	

Female Thread, BSPP

0036	Thread
MA010C	1.1/4"
MA012C	1.1/2"
MA016C	2"
Tech Sheet 2058	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AUTOMATIC VALVES

Shuttle Valve



SCS

0158	Thread
SCS 668	G1/8"
Tech Sheet 1854	


Non-return Valves



VNR

0158	Thread
VNR M5	M5
VNR 1/8	G1/8"
VNR 843 07	G1/4"
Tech Sheet 1854	

Quick Exhaust Valves




VSO

0158	OD mm
VSO 426 04	4
Tech Sheet 1854	



VSC, BSPP

0158	Thread
VSC 588	G1/8"
VSC 544	G1/4"
VSC 522	G1/2"
Tech Sheet 1854	



VSO, Standpipe Style

0158	Thread
VSO 425 M5	5
Tech Sheet 1854	

In-line Flow Control Valves



Uni-directional

0158	Thread
RFU 452	M5
RFU 482	G1/8"
RFU 483	G1/8"
RFU 444	G1/4"
RFU 446	G1/4"
RFU 429	G1/2"
Tech Sheet 10307	

Bi-directional

0158	Thread
RFO 352	M5
RFO 382	G1/8"
RFO 383	G1/8"
RFO 344	G1/4"
RFO 346	G1/4"
Tech Sheet 10307	

CAMOZZI Automation



For **Air Brake Accessories C-Truck 9000 Series**
see pages **890-894**

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar


40 Micron fitted as standard
Auto or semi-auto drain fitted as standard
Guarded bowl protection on Series 300, 400 and 600

All FT Pro Regulators can now be adapted to use either a 40mm or 50mm round face gauge with the new FT Pro Gauge Adaptor. See page 646

2 Year Warranty

200 Series Filter + Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar






Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KCS200-06-F-3	1/8"	3000
KCS200-08-F-3	1/4"	3000
Tech Sheet 3060		

300 Series Filter + Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar





Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP


0338	Thread	LPM
KCS300-08-A-F-3	1/4"	4000
KCS300-10-A-F-3	3/8"	4000
KCS300-15-A-F-3	1/2"	4000
Tech Sheet 3060		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KCS300-08-F-3	1/4"	4000
KCS300-10-F-3	3/8"	4000
KCS300-15-F-3	1/2"	4000
Tech Sheet 3060		

400 Series Filter + Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar





Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP


0338	Thread	LPM
KCS400-10-A-F-3	3/8"	6000
KCS400-15-A-F-3	1/2"	6000
Tech Sheet 3060		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KCS400-10-F-3	3/8"	6000
KCS400-15-F-3	1/2"	6000
Tech Sheet 3060		

600 Series Filter + Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar





Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KCS600-20-A-F-3	3/4"	9000
KCS600-25-A-F-3	1"	9000
Tech Sheet 3060		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KCS600-20-F-3	3/4"	9000
KCS600-25-F-3	1"	9000
Tech Sheet 3060		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

Working Temperature: -5°C to +60°C


Maximum Working Pressure: 10 bar

40 Micron fitted as standard
Auto or semi-auto drain fitted as standard
Guarded bowl protection on Series 300, 400 and 600

2 Year Warranty

200 Series Filter/Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar






Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS200-06-F-3	1/8"	3000
KFCS200-08-F-3	1/4"	3000
Tech Sheet 3061		

300 Series Filter/Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar





Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS300-08-A-F-3	1/4"	4000
KFCS300-10-A-F-3	3/8"	4000
KFCS300-15-A-F-3	1/2"	4000
Tech Sheet 3061		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS300-08-F-3	1/4"	4000
KFCS300-10-F-3	3/8"	4000
KFCS300-15-F-3	1/2"	4000
Tech Sheet 3061		

400 Series Filter/Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar



Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS400-10-A-F-3	3/8"	6000
KFCS400-15-A-F-3	1/2"	6000
Tech Sheet 3061		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS400-10-F-3	3/8"	6000
KFCS400-15-F-3	1/2"	6000
Tech Sheet 3061		

600 Series Filter/Regulator + Lubricator Combination Units

Operating Pressure
1.5 to 9.0 bar



Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS600-20-A-F-3	3/4"	9000
KFCS600-25-A-F-3	1"	9000
Tech Sheet 3061		

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFCS600-20-F-3	3/4"	9000
KFCS600-25-F-3	1"	9000
Tech Sheet 3061		

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -5°C to +60°C


Maximum Working Pressure: 10 bar

40 Micron fitted as standard
Auto or semi-auto drain fitted as standard
Guarded bowl protection on Series 300, 400 and 600

2 Year Warranty

200 Series Filter/Regulators

Operating Pressure
1.5 to 9.0 bar






Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS200-06-F-3	1/8"	3000
KFRS200-08-F-3	1/4"	3000

Tech Sheet 3062

300 Series Filter/Regulators

Operating Pressure
1.5 to 9.0 bar





Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS300-08-A-F-3	1/4"	4000
KFRS300-10-A-F-3	3/8"	4000
KFRS300-15-A-F-3	1/2"	4000

Tech Sheet 3062

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS300-08-F-3	1/4"	4000
KFRS300-10-F-3	3/8"	4000
KFRS300-15-F-3	1/2"	4000

Tech Sheet 3062

400 Series Filter/Regulators

Operating Pressure
1.5 to 9.0 bar



Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS400-10-A-F-3	3/8"	6000
KFRS400-15-A-F-3	1/2"	6000

Tech Sheet 3062

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS400-10-F-3	3/8"	6000
KFRS400-15-F-3	1/2"	6000

Tech Sheet 3062

600 Series Filter/Regulators

Operating Pressure
1.5 to 9.0 bar



Auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS600-20-A-F-3	3/4"	9000
KFRS600-25-A-F-3	1"	9000

Tech Sheet 3062

Semi-auto Drain, supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KFRS600-20-F-3	3/4"	9000
KFRS600-25-F-3	1"	9000

Tech Sheet 3062

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar


40 Micron fitted as standard
Auto or semi-auto drain fitted as standard
Guarded bowl protection on Series 300, 400 and 600

All FT Pro Regulators can now be adapted to use either a 40mm or 50mm round face gauge with the new FT Pro Gauge Adaptor. See page 646

2 Year Warranty

Mini Regulators

Max inlet pressure 10 bar
Operating pressure 0.5 to 9.0 bar






Supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread
KRS200-06	1/8"
KRS200-08	1/4"
Tech Sheet 3066	

200 Series Regulators

Operating pressure 1.5 to 9.0 bar






Supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KRS200-06-F-3	1/8"	3000
KRS200-08-F-3	1/4"	3000
Tech Sheet 3064		

300 Series Regulators

Operating pressure 1.5 to 9.0 bar






Supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KRS300-08-F-3	1/4"	5000
KRS300-10-F-3	3/8"	5000
KRS300-15-F-3	1/2"	5000
Tech Sheet 3064		

400 Series Regulators

Operating pressure 1.5 to 9.0 bar






Supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KRS400-10-F-3	3/8"	7500
KRS400-15-F-3	1/2"	7500
Tech Sheet 3064		

600 Series Regulators

Operating pressure 1.5 to 9.0 bar





Supplied with Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread	LPM
KRS600-20-F-3	3/4"	9500
KRS600-25-F-3	1"	9500
Tech Sheet 3064		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar

Guarded bowl protection on Series 300, 400 and 600

2 Year Warranty

200 Series Lubricators



Supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KLS200-06	1/8"	3000
KLS200-08	1/4"	3000
Tech Sheet 3065		

400 Series Lubricators



Supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KLS400-10	3/8"	7500
KLS400-15	1/2"	7500
Tech Sheet 3065		

300 Series Lubricators



Supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KLS300-08	1/4"	5000
KLS300-10	3/8"	5000
KLS300-15	1/2"	5000
Tech Sheet 3065		

600 Series Lubricators



Supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KLS600-20	3/4"	9000
KLS600-25	1"	9000
Tech Sheet 3065		

Fluid-Air Components Ltd

AIR PREPARATION


Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar

40 Micron fitted as standard
Auto or semi-auto drain fitted as standard
Guarded bowl protection on Series 300, 400 and 600

2 Year Warranty

200 Series Filters






Semi-auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS200-06	1/8"	3000
KFS200-08	1/4"	3000
Tech Sheet 3063		

300 Series Filters






Auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS300-08-A	1/4"	5000
KFS300-10-A	3/8"	5000
KFS300-15-A	1/2"	5000
Tech Sheet 3063		

Semi-auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS300-08	1/4"	5000
KFS300-10	3/8"	5000
KFS300-15	1/2"	5000
Tech Sheet 3063		

400 Series Filters






Auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS400-10-A	3/8"	7500
KFS400-15-A	1/2"	7500
Tech Sheet 3063		

Semi-auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS400-10	3/8"	7500
KFS400-15	1/2"	7500
Tech Sheet 3063		

600 Series Filters





Auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS600-20-A	3/4"	10000
KFS600-25-A	1"	10000
Tech Sheet 3063		

Semi-auto Drain, supplied with Mounting Bracket, BSPP

0338	Thread	LPM
KFS600-20	3/4"	10000
KFS600-25	1"	10000
Tech Sheet 3063		

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar


FT Pro Air Service Units come complete with: Filter/regulator, lubricator, 3/2 shut-off valve, mounting bracket and 10 bar pressure gauge.

Available in both auto drain and semi-auto drain.
The units are also available on a floor stand for use with mobile compressors for use on site.
All FT Pro Regulators can now be adapted to use either a 40mm or 50mm round face gauge with the new FT Pro Gauge Adaptor. See page 646

2 Year Warranty

300 Series Air Service Unit, Wall Mount

Operating Pressure
1.5 to 9.0 bar






Auto Drain, supplied with Shut Off Valve & 10 bar Gauge, BSPP

0338	Thread	LPM
KCAS300-15-A-F-3	1/2"	4000
	Tech Sheet 10286	

Operating Pressure
1.5 to 9.0 bar






Semi-auto Drain, supplied with Shut Off Valve & 10 bar Gauge, BSPP

0338	Thread	LPM
KCAS300-15-F-3	1/2"	4000
	Tech Sheet 10286	

400 Series Air Service Unit, Wall Mount

Operating Pressure
1.5 to 9.0 bar






Auto Drain, supplied with Shut Off Valve & 10 bar Gauge, BSPP

0338	Thread	LPM
KCAS400-15-A-F-3	1/2"	6000
	Tech Sheet 10286	

Operating Pressure
1.5 to 9.0 bar





Semi-auto Drain, supplied with Shut Off Valve & 10 bar Gauge, BSPP

0338	Thread	LPM
KCAS400-15-F-3	1/2"	6000
	Tech Sheet 10286	

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 9 bar

Soft Start Valves are increasingly being used where safety is key in the start up of systems and machines in helping protect the operators and the equipment.

The valves allow the pressure to gradually increase to the full flow required on start up of the system.


OSHA approved.

These units can be used in conjunction with FT Pro Air Preparation with the addition of brackets style 'U' or 'L', or as a stand alone in-line unit.

All FT Pro Regulators can now be adapted to use either a 40mm or 50mm round face gauge with the new FT Pro Gauge Adaptor. See page 646

2 Year Warranty

200 Series Soft Start Valves, Solenoid




24V DC, supplied with Coil, DIN Plug, Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread
KC200-06	1/8"
KC200-08	1/4"

Tech Sheet 3067

300 Series Soft Start Valves, Solenoid




24V DC, supplied with Coil, DIN Plug, Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread
KC300-08	1/4"
KC300-10	3/8"
KC300-15	1/2"

Tech Sheet 3067

400 Series Soft Start Valves, Solenoid



24V DC, supplied with Coil, DIN Plug, Mounting Bracket & 10 bar Gauge, BSPP

0338	Thread
KC400-10	3/8"
KC400-15	1/2"

Tech Sheet 3067

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 9 bar


Lockable shut off valves prevent accidental start ups when maintenance or service work is being carried out on the machines.

Padlock supplied.

These units can be used in conjunction with FT Pro Air Preparation with the addition of brackets style 'U' or 'L', or as a stand alone 3/2 exhausting ball valve.

2 Year Warranty

200 Series 3/2 Shut Off Valves, Lockable




Supplied with Padlock & Mounting Bracket, BSPP

0338	Thread
KZ200-06	1/8"
KZ200-08	1/4"

Tech Sheet 3068


300 Series 3/2 Shut Off Valves, Lockable



Supplied with Padlock & Mounting Bracket, BSPP

0338	Thread
KZ300-08	1/4"
KZ300-10	3/8"
KZ300-15	1/2"

Tech Sheet 3068



Supplied with Padlock & Mounting Bracket, BSPP

0338	Thread
KZ400-10	3/8"
KZ400-15	1/2"

Tech Sheet 3068

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar

Can be fitted to any combination units, fitted before the lubricator it can be used to port off a non-lubricated air supply that might be required for your system.

These units are to be used in conjunction with FT Pro Air Preparation, or as a stand alone BSPP manifold block. When using with existing FT Pro Air Preparation, you will also require additional fixing brackets.

2 Year Warranty

200 Series Porting Blocks



BSPP

0338	Thread
KA200-06	1/8"
KA200-08	1/4"
Tech Sheet 3069	

400 Series Porting Blocks



BSPP

0338	Thread
KA400-10	3/8"
KA400-15	1/2"
Tech Sheet 3069	

300 Series Porting Blocks



BSPP

0338	Thread
KA300-08	1/4"
KA300-10	3/8"
Tech Sheet 3069	

600 Series Porting Blocks



BSPP

0338	Thread
KA600-20	3/4"
KA600-25	1"
Tech Sheet 3069	

Fixing Brackets



U Style Brackets

0338	To Suit Series
KA200U-P1	200
KA300U-P1	300
KA400U-P1	400
KA600U-P1	600
Tech Sheet 3069	



L Style Brackets

0338	To Suit Series
KA201-P1	200
KA301-P1	300
KA401-P1	400
KA601-P1	600
Tech Sheet 3069	

AIR PREPARATION

All FT Pro Regulators can now be adapted to use either a 40mm or 50mm round face gauge with the new FT Pro Gauge Adaptor. See below

Accessories



Drain Bowl & Auto Drain

0338	To Suit Series
KF300-P6	300
KF400-P10	400
KF600-P1	600
Tech Sheet 20382	



Filter Elements 40 Micron

0338	To Suit Series
KF200-004-1	200
KF300-004-1	300
KF400-004-1	400
KF600-004-1	600
Tech Sheet 20379	

Filter Elements 5 Micron

0338	To Suit Series
KF200-004-2	200
KF300-004-2	300
KF400-004-2	400
KF600-004-2	600
Tech Sheet 20379	



Drain Bowl & Semi-auto Drain

0338	To Suit Series
KF200-P3	200
KF300-P5	300
KF400-P9	400
KF600-P2	600
Tech Sheet 20896	





Micro Gauge

0338
K-PR010B-P1
Tech Sheet 20381

All FT Pro regulators can be fitted with a 40mm or 50mm round faced gauge, by using the FT Pro gauge adaptor

Complete with
2 x screws.



Gauge Adaptor

0338	Thread	To Suit Series
KGA-1/8	1/8"	200 & 300
KGA-1/4	1/4"	400 & 600
Tech Sheet 20381		



Drain Bowl & Manual Drain

0338	To Suit Series
KF200-P6	200
KF300-P4	300
KF400-P11	400
KF600-P3	600
Tech Sheet 20380	



1/8" BSPT, Steel Case Centre Back Connection

0338	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
KG40-10R	40	0-160	0-10
KG50-10R	50	0-160	0-10



Panel Mount Brackets, to suit Steel Dry Gauges

0338	To Suit mm
KPMB40R	40
KPMB50R	50

AIR PREPARATION

FT PRO

The manufacturers strive to maintain quality and are continually improving products to suit the industry.

Due to the success of the Professional FRL's, The Professional Range has been revamped with improved structure and sensitivity.

200 and 300 series now come with larger, stronger drip cups, extending the products in use life cycle.

Advancements to the construction of the regulators mechanism, has given extra sensitivity on the control this helps to ensure the system is working to the optimum pressure.

- Heavy-duty
- 20 micron filtration as standard
- Metal construction
- Modular compact design
- Semi-auto drain as standard
- Guard bowl protection only on FM3000, FM4000 and FM5000 units
- Micro gauge also available

Working Temperature: -10°C to +60°C

Maximum Working Pressure: 10 bar

Filter + Regulator + Lubricator

Operating Pressure: 1.5 bar to 8.5 bar



Supplied with Mounting Bracket & Gauge, BSPP

0132	Thread	LPM
FM2-20-01-C	1/8"	500
FM2-30-02-C	1/4"	2000
FM2-40-03-C	3/8"	4000
FM2-40-04-C	1/2"	4000
FM2-50-06-C	3/4"	5000
FM2-50-10-C	1"	5000

Tech Sheet 60527

Filter Regulator + Lubricator

Operating Pressure: 1.5 bar to 8.5 bar



Supplied with Mounting Bracket & Gauge, BSPP

0132	Thread	LPM
FM2-21-01-C	1/8"	500
FM2-31-02-C	1/4"	2000
FM2-41-03-C	3/8"	4000
FM2-41-04-C	1/2"	4000
FM2-51-06-C	3/4"	5000
FM2-51-10-C	1"	5000

Tech Sheet 60528

Filter Regulator

Operating Pressure: 1.5 bar to 8.5 bar



Supplied with Mounting Bracket & Gauge, BSPP

0132	Thread	LPM
FM2-20-01-W	1/8"	500
FM2-30-02-W	1/4"	1700
FM2-40-03-W	3/8"	3000
FM2-40-04-W	1/2"	3000
FM2-50-06-W	3/4"	5000
FM2-50-10-W	1"	5000

Tech Sheet 60529

Filter



BSPP

0132	Thread	LPM
FM2-20-01-F	1/8"	500
FM2-30-02-F	1/4"	1700
FM2-40-03-F	3/8"	3000
FM2-40-04-F	1/2"	3000
FM2-50-06-F	3/4"	5000
FM2-50-10-F	1"	5000

Tech Sheet 60530

Regulator

Operating Pressure: 1.5 bar to 8.5 bar



Supplied with Mounting Bracket & Gauge, BSPP

0132	Thread	LPM
FM2-20-01-R	1/8"	500
FM2-30-02-R	1/4"	1700
FM2-40-03-R	3/8"	3000
FM2-40-04-R	1/2"	3000
FM2-50-06-R	3/4"	5000
FM2-50-10-R	1"	5000

Tech Sheet 60531

Lubricator



BSPP

0132	Thread	LPM
FM2-20-01-L	1/8"	500
FM2-30-02-L	1/4"	1700
FM2-40-03-L	3/8"	3000
FM2-40-04-L	1/2"	3000
FM2-50-06-L	3/4"	5000
FM2-50-10-L	1"	5000

Tech Sheet 60532

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

As with the original Professional Range, the MKII air preparation range comes fully assembled.
We offer users the ability to assemble their own bespoke units with the use of connectors and wall mounting kits.

Applications:

- Construction
- Agriculture
- Mining
- OEM machine building
- Automotive
- Rail
- Industrial

Professional Range MKII Accessories



Neck Brackets

0132	To Suit
FM2-20-N	1/8"
FM2-30-N	1/4"
FM2-40-N	3/8"-1"
Tech Sheet 60537	



Filter Elements

0132	To Suit
FM2-20-20UM	200 Filter Series
FM2-30-20UM	300 Filter Series
FM2-40-20UM	400 Filter Series
FM2-50-20UM	500 Filter Series



Connector & Wall Brackets

0132	To Suit
FM2-20-MB	1/8"
FM2-30-MB	1/4"
FM2-40-MB	3/8"-1/2"
FM2-50-MB	3/4"-1"
Tech Sheet 60537	



Micro Gauge

0132	To Suit
GM-27	All Series



Steel Case Centre Back Connection

0132	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
GS-40	1/8"	40	0-145	0-10
GS-50	1/8"	50	0-145	0-10

Drip Leg Drain



BSPP

0132	To Suit
FM-402-04-S	1/2"
Tech Sheet 1998	

Fluid-Air Components Ltd

A SERIES AIR PREPARATION

A Series Regulators



AR2 Series Regulator 1/8"G - 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
AR2000-01	1/8"	1/8"	550



AR3 Series Regulator 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
AR3000-02	1/4"	1/8"	2500



AR4 Series Regulator 1/2"G - 3/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
AR4000-04	1/2"	1/4"	6000
AR4000-06	3/4"	1/4"	6000



AR5 Series Regulators 3/4"G - 1"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
AR5000-06	3/4"	1/4"	8000
AR5000-10	1"	1/4"	8000

A Series Filter Regulators



AW2 Series Filter Regulator 1/8"G - 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AW2000-01	1/8"	1/8"	550	Manual
AW2000-02	1/4"	1/8"	550	Manual
AW2000-02D	1/4"	1/8"	550	Auto Drain



AW3 Series Filter Regulator 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AW3000-02	1/4"	1/8"	2000	Manual
AW3000-02D	1/4"	1/8"	2000	Auto Drain



AW4 Series Filter Regulator 1/2"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AW4000-04	1/2"	1/4"	4000-4500	Manual
AW4000-04D	1/2"	1/4"	4000-4500	Auto Drain



AW5 Series Filter Regulators 3/4"G - 1"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AW5000-06D	3/4"	1/4"	5500	Auto Drain
AW5000-10D	1"	1/4"	5500	Auto Drain

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

A SERIES AIR PREPARATION

A Series Combi Sets



AC2 Series Filter Regulator & Lube Combi Sets 1/8"G - 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AC2010-01	1/8"	1/8"	500	Manual
AC2010-02	1/4"	1/8"	500	Manual
AC2010-02D	1/4"	1/8"	500	Auto Drain



AC3 Series Filter Regulator & Lube Combi Sets 1/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AC3010-02	1/4"	1/4"	1700	Manual
AC3010-02D	1/4"	1/4"	1700	Auto Drain



AC4 Series Filter Regulator & Lube Combi Sets 1/2"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AC4010-04	1/2"	1/4"	3000	Manual
AC4010-04D	1/2"	1/4"	3000	Auto Drain



AC5 Series Filter Regulator & Lube Combi Sets 3/4"G - 1"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AC5010-06D	3/4"	1/4"	4000	Auto Drain
AC5010-10D	1"	1/4"	4000	Auto Drain

A Series Filters



AF2 Series Filter 1/8"G - 1/4"G

0600	Port Size G	Max Flow L/min	Drain
AF2000-01	1/8"	750	Manual
AF2000-02	1/4"	750	Manual



AF3 Series Filter 1/4"G

0600	Port Size G	Max Flow L/min	Drain
AF3000-02	1/4"	1500	Manual
AF3000-02D	1/4"	1500	Auto Drain



AF4 Series Filter 1/2"G - 3/4"G

0600	Port Size G	Max Flow L/min	Drain
AF4000-04	1/2"	4000-6000	Manual
AF4000-04D	1/2"	4000-6000	Auto Drain
AF4000-06D	3/4"	4000-6000	Auto Drain



AF5 Series Filter 3/4"G - 1"G

0600	Port Size G	Max Flow L/min	Drain
AF5000-06D	3/4"	7000	Auto Drain
AF5000-10D	1"	7000	Auto Drain

A SERIES AIR PREPARATION

A Series Lubricators



AL2 Series Lubricator 1/8"G - 1/4"G

0600	Port Size G	Max Flow L/min
AL2000-02	1/4"	800



AL3 Series Lubricator 1/4"G

0600	Port Size G	Max Flow L/min
AL3000-02	1/4"	1700



AL4 Series Lubricator 1/2"G

0600	Port Size G	Max Flow L/min
AL4000-04	1/2"	5000-6300

A Series Mounting Brackets



A2 Series Mounting Bracket

0600	Description
A2000-BRKT	Mounting Bracket



A3 Series Mounting Bracket

0600	Description
A3000-BRKT	Mounting Bracket



A4 Series Mounting Bracket

0600	Description
A4000-BRKT	Mounting Bracket



A5 Series Mounting Bracket

0600	Description
A5000-BRKT	Mounting Bracket



A4 Series Mounting Bracket

0600	Description
A400T	Mounting Bracket

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

D SERIES AIR PREPARATION

D Series Regulators



DR2 Series Regulator 1/8"G - 3/8"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
DR200-01	1/8"	1/8"	1700
DR200-02	1/4"	1/8"	1700
DR200-03	3/8"	1/8"	1700



DR4 Series Regulator 3/8"G - 1/2"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
DR400-03	3/8"	1/4"	3500
DR400-04	1/2"	1/4"	3500



DR6 Series Regulator 3/4"G - 1"G

0600	Port Size G	Gauge Thread G	Max Flow L/min
DR600-06	3/4"	1/4"	11500
DR600-08	1"	1/4"	11500

D Series Filter Regulators



DC2 Series Filter Regulator 1/8"G - 3/8"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DFR200-01	1/8"	1/8"	1700	Manual
DFR200-02	1/4"	1/8"	1700	Manual
DFR200-02D	1/4"	1/8"	1700	Auto Drain
DFR200-03D	3/8"	1/8"	1700	Auto Drain



DC4 Series Filter Regulator 3/8"G - 3/4"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DFR400-03D	3/8"	1/4"	3500	Auto Drain
DFR400-04	1/2"	1/4"	3500	Manual
DFR400-04D	1/2"	1/4"	3500	Auto Drain
DFR400-06	3/4"	1/4"	3500	Manual
DFR400-06D	3/4"	1/4"	3500	Auto Drain



DC6 Series Filter Regulator 3/4"G - 1"G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DFR600-06	3/4"	1/4"	11500	Manual
DFR600-08D	1"	1/4"	11500	Auto Drain

Fluid-Air Components Ltd

D SERIES AIR PREPARATION

D Series Combi Sets



DC2 Series Filter Regulator & Lube Combi Sets 1/8″G - 3/8″G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DC201-01	1/8″	1/8″	1700	Manual
DC201-02	1/4″	1/8″	1700	Manual
DC201-02D	1/4″	1/8″	1700	Auto Drain
DC201-03D	3/8″	1/8″	1700	Auto Drain



DC4 Series Filter Regulator & Lube Combi Sets 3/8″G - 3/4″G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DC401-01	3/8″	1/4″	3500	Manual
DC401-02	1/2″	1/4″	3500	Manual
DC401-02D	1/2″	1/4″	3500	Auto Drain
DC401-03D	3/4″	1/4″	3500	Auto Drain



DC6 Series Filter Regulator & Lube Combi Sets 3/4″G - 1″G

0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
DC601-06	3/4″	1/4″	11500	Manual
DC601-08D	1″	1/4″	11500	Auto Drain

D Series Filters



DF2 Series Filter 1/8″G - 3/8″G

0600	Port Size G	Max Flow L/min	Drain
DF200-02	1/4″	2000	Manual
DF200-02D	1/4″	2000	Auto Drain
DF200-03D	1/4″	2000	Auto Drain



DF4 Series Filter 3/8″G - 3/4″G

0600	Port Size G	Max Flow L/min	Drain
DF400-03D	3/8″	4000	Auto Drain
DF400-04	1/2″	4000	Manual
DF400-04D	1/2″	4000	Auto Drain
DF400-06	3/4″	4000	Manual



DF6 Series Filter 3/4″G - 1″G

0600	Port Size G	Max Flow L/min	Drain
DF600-06	3/4″	11500	Manual
DF600-08	1″	11500	Manual
DF600-08D	1″	11500	Auto Drain

Fluid-Air Components Ltd

D SERIES AIR PREPARATION

D Series Lubricators



DL1 Series Lubricator M5 - 1/8"G

0600	Port Size G	Max Flow L/min
DL100-M5	M5	500



DL2 Series Lubricator 1/8"G - 3/8"G

0600	Port Size G	Max Flow L/min
DL200-01	1/8"	2000
DL200-02	1/4"	2000
DL200-03	3/8"	2000



DL4 Series Lubricator 3/8"G - 1/2"G

0600	Port Size G	Max Flow L/min
DL400-03	3/8"	4000
DL400-04	1/2"	4000

D Series Accessories



Port Block Sets

0600	Series	Size
D400LB-04	400	1/2"



Filter to Regulator to Lube Joiner Kits

0600	Series
DC400JK	400



Wall Mounting Brackets

0600	Series
MB-D200	200
MB-D400	400
MB-D600	600

A9 SERIES AIR PREPARATION

A9 Series Air Preparation

AC9 Series Filter Regulator & Lube Combi Sets 1.1/2" - 2"



0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AC901-15D	1.1/2"	1/4"	17500	Auto Drain
AC901-20D	2"	1/4"	17500	Auto Drain

AFR9 Series Filter Regulators 1.1/2" - 2"



0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AFR900-15D	1.1/2"	1/4"	17500	Auto Drain
AFR900-20D	2"	1/4"	17500	Auto Drain

AR9 Series Regulators 1.1/2" - 2"



0600	Port Size G	Gauge Thread G	Max Flow L/min	Drain
AR900-15	1.1/2"	1/4"	17500	Auto Drain
AR900-20	2"	1/4"	17500	Auto Drain

AF9 Series Filters 1.1/2" - 2"



0600	Port Size G	Max Flow L/min	Drain
AF900-15D	1.1/2"	17500	Auto Drain
AF900-20D	2"	17500	Auto Drain

AF9 Series Lubricators 1.1/2" - 2"



0600	Port Size G	Max Flow L/min
AL900-15	1.1/2"	17500
AL900-20	2"	17500

PR SERIES AIR PREPARATION

PR Series Air Preparation

PR100 Series 1/8" Precision Regulators



0600	Range MPA	Max Flow L/min
PR101-01	0.01-0.4	4.4 (ANR)
PR102-01	0.01-0.8	4.4 (ANR)

PR200 Series 1/4" Precision Regulators



0600	Range MPA	Max Flow L/min
PR200-02	0.005-0.2	4.4 (ANR)
PR201-02	0.01-0.4	4.4 (ANR)

PR300 Series 1/2" Precision Regulator



0600	Range MPA	Max Flow L/min
PR302-04	0.01-0.8	11.5 (ANR)

WORKFORCE RANGE

FT PRO

In-line Filter Aluminium

Prevents dirt entering the air line

Working Temperature:
0°C to +70°C

Maxium Working Pressure:
10 bar



Male x Female Thread, BSPP

0043	Thread
ILF-14	1/4"
ILF-38	3/8"
Tech Sheet 824	

Flow: 400 L/min

Working Temperature:
0°C to +45°C

Maximum Working Pressure:
9 bar



Male x Female Thread, BSPP

0043	Thread
IF-14	1/4"
Tech Sheet 20383	

In-line Brass Flow Regulator

Working Temperature:
0°C to +70°C

Maximum Working Pressure:
10 bar



Male x Female Thread, BSPP

0043	Thread
ILR-14	1/4"
Tech Sheet 20384	

Mini In-line Oiler

Working Temperature:
0°C to +45°C

Maximum Working Pressure:
9 bar



Male x Female Thread, BSPP

0043	Thread
MO-14	1/4"
Tech Sheet 20385	

FESTO

new product



For **FESTO Flow Regulators**
see pages **814-815**

AIR PREPARATION

For the full range and more information, please contact one of our sales team.

AIR PREPARATION MS SERIES

Features



Robust design, perfect for harsh environments

Good regulation characteristics with minimal pressure

High flow rate and highly efficient in removing contaminants

Available in both manual and auto-drain options

Product Description

MS	4	-	LFR	-	1/4	-	D6	-	C	-	R	-	M	-	AS
Type	Size		Service Function		Pneumatic Connection		Pressure Regulation Range		Grade of Filtration		Bowl Guard		Condensate Drain		Security

AIR PREPARATION MS SERIES

FESTO

Filter Regulator, Manual Shut-off Valve & Pressure Gauge

Ambient Temperature:
-10°C to +60°C

- For filtered and unlubricated compressed ai
- Supply pressure can be opened and closed
- Output pressure is indefinitely adjustable within the pressure regulation rang
- Manual rotary condensate drain

Working Pressure:
0.8 to 14 bar



Manual Drain Filter Regulator with Manual Shut-Off Valve

0009	Thread	LPM	Micron	Pressure Regulation Range Bar	Manufacturer's Code
8025354	1/4"	1700	40	0.5 to 12	MSB4-1/4:C3:J1-WP
8025355	1/2"	5100	40	0.5 to 12	MSB6-1/2:C3:J1-WP
Tech Sheet 71003					

Working Pressure:
0.8 to 10 bar



Manual Drain Filter Regulator with Manual Shut-Off Valve, Solenoid Valve & Pressure Sensor

0009	Thread	LPM	Micron	Pressure Regulation Range Bar	Manufacturer's Code
8025358	1/4"	1400	40	0.5 to 10	MSB4-1/4:C3:J1:D14-WP
8025359	1/2"	4000	40	0.5 to 10	MSB6-1/2:C3:J1:D14-WP
Tech Sheet 71011					

Working Pressure:
0.8 to 14 bar



Manual Drain Filter Regulator with Manual Shut-Off & Pressure Sensor

0009	Thread	LPM	Micron	Pressure Regulation Range Bar	Manufacturer's Code
8025356	1/4"	1600	40	0.5 to 10	MSB4-1/4:C3:J1:F12-WP
8025357	1/2"	4500	40	0.5 to 10	MSB6-1/2:C3:J1:F12-WP
Tech Sheet 71007					

Working Pressure:
1.5 to 20 bar



Manual Rotary Filter Regulator with Pressure Gauge, Rotary Knob with Detent & Lubricator

0009	Thread	LPM	Micron	Bowl Type	Pressure Regulation Range Bar	Manufacturer's Code
530244	1/4"	850	40	Plastic	+0.5 to +12	MSB6-1/2-FRC5:J1M1
531117	1/2"	3700	40	Plastic	+0.5 to +12	MSB4-1/4-FRC5:J1M1
Tech Sheet 71014						

Fluid-Air Components Ltd

AIR PREPARATION MS SERIES

FESTO

Pressure Regulators

- Maintains a constant working pressure independent of pressure fluctuations and air consumption
- High flow rate with minimal pressure drop
- Connection G1/4, G1/2
- Selected types in accordance with ATEX directive for potentially explosive atmospheres
- Lockable via accessories



Ambient Temperature:
-10°C to +60°C

Working Pressure:
1/4 BSPP 0.8 to 14 bar
1/2 BSPP 0.8 to 20 bar

Integrated Pressure Gauge, BSPP

0009	Thread	LPM	Pressure Regulation Range Bar	Manufacturer's Code
529415	1/4"	2100	0.3 to 4	MS4-LR-1/4-D5-AS
529417	1/4"	1800	0.3 to 7	MS4-LR-1/4-D6-AS
529419	1/4"	1700	0.5 to 12	MS4-LR-1/4-D7-AS
529989	1/2"	7500	0.3 to 4	MS6-LR-1/2-D5-AS
529991	1/2"	6500	0.3 to 7	MS6-LR-1/2-D6-AS
529993	1/2"	5500	0.5 to 12	MS6-LR-1/2-D7-AS
Tech Sheet 71440				

Air Preparation Units MS-LFR-B Series

- Grid dimension 25, 40, 62mm
- Competitively priced basic component focused on the most important technical functions
- Lightweight and sturdy thanks to modern polymer materials
- Compatible with the MS series for the ideal combination of low-cost basic functionality and high-end functional requirements
- Stabile control response
- With or without pressure gauge
- Rotary knob with latch
- MS2: Directly operated diaphragm regulator
- MS4, MS6: directly actuated piston regulator
- With integrated secondary exhausting and primary exhausting with return flow function



Integrated Pressure Gauge, BSPP

0009	Thread	LPM	Micron	Bowl Type	Pressure Regulation Range Bar	Type
8098257	1/4"	1500	5	Polymer	1 bar to 10 bar	MS4-LFR-1/4-D6-C-P-M-AG-BAR-B
8098265	1/4"	1500	5	Polymer	1 bar to 10 bar	MS4-LFR-1/4-D6-C-P-M-AG-MPA-B
8098259	1/4"	1500	5	Polymer	2 bar to 10 bar	MS4-LFR-1/4-D6-C-P-VC-AG-BAR-B
8098266	1/4"	1500	5	Polymer	2 bar to 10 bar	MS4-LFR-1/4-D6-C-P-VC-AG-MPA-B
8098258	1/4"	1700	40	Polymer	1 bar to 10 bar	MS4-LFR-1/4-D6-E-P-M-AG-BAR-B
8098254	1/4"	1700	40	Polymer	1 bar to 10 bar	MS4-LFR-1/4-D6-E-P-M-AG-MPA-B
8098264	1/4"	1700	40	Polymer	2 bar to 10 bar	MS4-LFR-1/4-D6-E-P-VC-AG-BAR-B
8098256	1/4"	1700	40	Polymer	2 bar to 10 bar	MS4-LFR-1/4-D6-E-P-VC-AG-MPA-B
8098300	1/2"	4750	5	Polymer	1 bar to 10 bar	MS6-LFR-1/2-D6-C-P-M-AG-BAR-B
8098310	1/2"	4750	5	Polymer	1 bar to 10 bar	MS6-LFR-1/2-D6-C-P-M-AG-MPA-B
8098309	1/2"	4750	5	Polymer	2 bar to 10 bar	MS6-LFR-1/2-D6-C-P-VC-AG-BAR-B
8098302	1/2"	4750	5	Polymer	2 bar to 10 bar	MS6-LFR-1/2-D6-C-P-VC-AG-MPA-B
8098304	1/2"	5300	40	Polymer	1 bar to 10 bar	MS6-LFR-1/2-D6-E-P-M-AG-BAR-B
8098307	1/2"	5300	40	Polymer	1 bar to 10 bar	MS6-LFR-1/2-D6-E-P-M-AG-MPA-B
8098312	1/2"	5300	40	Polymer	2 bar to 10 bar	MS6-LFR-1/2-D6-E-P-VC-AG-BAR-B
8098305	1/2"	5300	40	Polymer	2 bar to 10 bar	MS6-LFR-1/2-D6-E-P-VC-AG-MPA-B
More variants available online						

Filter Regulators

- Filter and pressure regulator in a single unit
- Good regulation characteristics with minimal hysteresis and primary pressure compensation
- Good particle and condensate separation



Ambient Temperature:
-10°C to +60°C

Working Pressure:
1/4 BSPP 0.8 to 14 bar
1/2 BSPP 0.8 to 20 bar

Manual Drain, BSPP

0009	Thread	LPM	Micron	Bowl Type	Pressure Regulation Range Bar	Manufacturer's Code
529144	1/4"	1500	5	Plastic	0.3 to 7	MS4-LFR-1/4-D6-CRM-AS
529148	1/4"	1700	40	Plastic	0.3 to 7	MS4-LFR-1/4-D6-ERM-AS
529152	1/4"	1700	5	Plastic	0.5 to 12	MS4-LFR-1/4-D7-CRM-AS
529156	1/4"	1500	40	Plastic	0.5 to 12	MS4-LFR-1/4-D7-ERM-AS
535724	1/4"	1500	40	Metal	0.5 to 12	MS4-LFR-1/4-D7-EUM-AS
529176	1/2"	5600	5	Plastic	0.3 to 7	MS6-LFR-1/2-D6-CRM-AS
529180	1/2"	5600	40	Plastic	0.3 to 7	MS6-LFR-1/2-D6-ERM-AS
529184	1/2"	4000	5	Plastic	0.5 to 12	MS6-LFR-1/2-D7-CRM-AS
529188	1/2"	4500	40	Plastic	0.5 to 12	MS6-LFR-1/2-D7-ERM-AS
530338	1/2"	4000	5	Metal	0.5 to 12	MS6-LFR-1/2-D7-CUM-AS
529192	1/2"	4500	40	Metal	0.5 to 12	MS6-LFR-1/2-D7-EUM-AS
Tech Sheet 71120						

Working Pressure:
2 to 12 bar

Automatic Drain, BSPP

0009	Thread	LPM	Micron	Bowl Type	Pressure Regulation Range Bar	Manufacturer's Code
529146	1/4"	1500	5	Plastic	0.3 to 7	MS4-LFR-1/4-D6-CRV-AS
529150	1/4"	1700	40	Plastic	0.3 to 7	MS4-LFR-1/4-D6-ERV-AS
529158	1/4"	1200	40	Plastic	0.5 to 12	MS4-LFR-1/4-D7-ERV-AS
535720	1/4"	1200	5	Metal	0.5 to 12	MS4-LFR-1/4-D7-CUV-AS
535722	1/4"	1200	40	Metal	0.5 to 12	MS4-LFR-1/4-D7-EUV-AS
529178	1/2"	5600	5	Plastic	0.3 to 7	MS6-LFR-1/2-D6-CRV-AS
529182	1/2"	6200	40	Plastic	0.3 to 7	MS6-LFR-1/2-D6-ERV-AS
529190	1/2"	4500	40	Plastic	0.5 to 12	MS6-LFR-1/2-D7-ERV-AS
530340	1/2"	4000	5	Metal	0.5 to 12	MS6-LFR-1/2-D7-CUV-AS
529194	1/2"	4500	40	Metal	0.5 to 12	MS6-LFR-1/2-D7-EUV-AS
Tech Sheet 71122						

FESTO



For **FESTO Actuation**
see page **1020**

AIR PREPARATION MS SERIES

FESTO

Energy Efficiency Module MSE6-E2M

- MSE6-E2M constantly monitors the compressed air consumption, blocks the compressed air after waiting a specific period once production has stopped and reduces the system pressure to 0 bar. It can be integrated directly into PROFIBUS, PROFINET, EtherCAT or Ethernet/IP via fieldbus.
- Grid dimension 62mm
- Intelligent service unit component for optimising the use of compressed air as an energy medium in industrial automation technology
- Combination of stop valve, flow sensor, pressure sensor and fieldbus node
- Identification of production downtime and leakages
- User-controlled shut-off and pressurisation
- Equipped with measurement, control and diagnostic functions
- Fieldbus connection (PROFIBUS DP, PROFINET IO, EtherNet/IP or EtherCAT®) via integrated fieldbus nodes enables connection to a higher-level controller
- Sustainable operation with active air shut-off and pressure reduction



Service Unit Combination MSE6-E2M

0009	Thread	Electrical Actuation	Type
2465321	1/2"	Fieldbus node for PROFIBUS DP	MSE6-E2M-5000-FB13-AGD
3990296	1/2"	Fieldbus node for Ethernet/IP	MSE6-E2M-5000-FB36-AGD
3992150	1/2"	Fieldbus node for EtherCAT®	MSE6-E2M-5000-FB37-AGD
8157910	1/2"	Bus node for PROFINET IO with M12 connection	MSE6-E2M-5000-FB43-AGD
8157911	1/2"	Bus node for PROFINET IO with RJ45 connection	MSE6-E2M-5000-FB44-AGD
More variants available online			

Air Preparation Units MS-LFR-B Series

Filter MS2-LF-B

- Very compact and extremely lightweight series for use close to the process directly in the machine
- Lightweight and sturdy thanks to modern polymer materials
- Compatible with the MS series for the ideal combination of low-cost basic functionality and high-end functional requirements
- With manual condensate drain, rotating
- Grid dimension 25mm
- Variants recommended for production systems for manufacturing lithium-ion batteries



Filter Regulator MS-LFR-B

0009	Thread	LPM	Micron	Bowl Type	Pressure Regulation Range Bar	Type
8086643	M5	140	5	Polymer	0.5 bar to 7 bar	MS2-LFR-M5-D6-A8-C-M-B
8086641	M5	140	5	Polymer	0.5 bar to 7 bar	MS2-LFR-M5-D6-AR-BAR-C-M-B
8086642	M5	140	5	Polymer	0.5 bar to 7 bar	MS2-LFR-M5-D6-AR-MPA-C-M-B
8086646	QS-6	310	5	Polymer	0.5 bar to 7 bar	MS2-LFR-QS6-D6-A8-C-M-B
8086644	QS-6	310	5	Polymer	0.5 bar to 7 bar	MS2-LFR-QS6-D6-AR-BAR-C-M-B
8086645	QS-6	310	5	Polymer	0.5 bar to 7 bar	MS2-LFR-QS6-D6-AR-MPA-C-M-B
More variants available online						

FESTO



For **FESTO QS Standard Push-in Fittings**
see pages **808-811**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION MS SERIES

FESTO

Standard Modular Valves

Ambient Temperature:
-10°C to +60°C

- For pressurising and exhausting pneumatic systems

Working Pressure:
0 to 14 bar



Manual On/Off Valve, BSPP

0009	Thread	Manufacturer's Code
541258	1/4"	MS4-EM1-1/4
541267	1/2"	MS6-EM1-1/2
	Tech Sheet 71132	

Working Pressure:
0 to 18 bar



Manual On/Off Valve with Silencer, BSPP

0009	Thread	Manufacturer's Code
541259	1/4"	MS4-EM1-1/4-S
541272	1/4"	MS6-EM1-1/4-S
541268	1/2"	MS6-EM1-1/2-S
	Tech Sheet 71133	

Working Pressure:
3 to 10 bar



Soft-start & Quick Exhaust Valves

0009	Thread	Manufacturer's Code
8001469	1/2"	MS6-SV-1/2-C-10V24-S
	Tech Sheet 71587	

Working Pressure:
4 to 18 bar



Solenoid Actuated On/Off Valve with Silencer, BSPP

0009	Thread	Voltage	Manufacturer's Code
542598	1/4"	24V DC	MS4-EE-1/4-10V24-S
542602	1/2"	24V DC	MS6-EE-3/8-10V24-S
	Tech Sheet 71137		

Working Pressure:
4 to 18 bar



Solenoid Actuated On/Off Valve, BSPP

0009	Thread	Voltage	Manufacturer's Code
542578	1/4"	24V DC	MS4-EE-1/4-10V24
542582	1/2"	24V DC	MS6-EE-1/2-10V24
	Tech Sheet 71136		

- For slowly pressurising and exhausting pneumatic installations (for use with on/off valves EM1 and EE)

Working Pressure:
4 to 18 bar



Pneumatically Operated Soft-Start Valve, BSPP


0009	Thread	Manufacturer's Code
529531	1/4"	MS4-DL-1/4
529817	1/2"	MS6-DL-1/2
	Tech Sheet 71145	

FAC
Fluid-Air Components Ltd

AIR PREPARATION MS SERIES

FESTO

Brackets & Connection Accessories



Connector for MS module

0009	To Suit Series	Manufacturer's Code
8119201	MS4	MS4-MV1
8119204	MS6	MS6-MV1
552950	MS9	MS9-MV
Tech Sheet 71257		



Module Connector for Installation of Modules with Regulating Knob Pointing Downwards

0009	To Suit Series	Manufacturer's Code
532800	MS4	MS4-MVM
532801	MS6	MS6-MVM
Tech Sheet 71261		



Mouting Bracket with Distancing Piece

0009	To Suit Series	Manufacturer's Code
526073	M6	MS6-WPM-D
Tech Sheet 71268		



Wall Mounting Bracket


0009	To Suit Series	Manufacturer's Code
526064	MS4	MS4-WR
526075	MS6	MS6-WR
Tech Sheet 71270		

- Can be used as an intermediate distributor for varying air qualities
- Outlet at top and bottom



Branching Module

0009	To Suit Series	Thread	Manufacturer's Code
529853	MS6	G1/2"	MS6-FRM-1/2
Tech Sheet 71267			




Wall Bracket

0009	To Suit Series	Manufacturer's Code
526063	MS4	MS4-WPB
526074	MS6	MS6-WPB
Tech Sheet 71266		



Wall Bracket, WPM with Distancing Piece

0009	To Suit Series	Manufacturer's Code
526060	MS4	MS4-WPM-D
532186	MS6	MS6-WPM-2D
Tech Sheet 71586		



Mounting Bracket

0009	To Suit Series	Manufacturer's Code
532184	MS4	MS4-WP
532195	MS6	MS6-WP
Tech Sheet 71269		



Wall Mounting Bracket

0009	To Suit Series	Manufacturer's Code
532185	MS4	MS4-WB
532196	MS6	MS6-WB
Tech Sheet 71585		

- Adaptor for pneumatic connection



Connecting Plate Set

0009	To Suit Series	Thread	Manufacturer's Code
526069	MS4	G1/4"	MS4-AGB
526082	MS6	G1/2"	MS6-AGD
526083	MS6	G3/4"	MS6-AGE
Tech Sheet 71271			

FAC
Fluid-Air Components Ltd


MINIATURE FRLS, 'BIT'

Miniature Filter

- Flow rate at 6 bar ΔP 0.5 bar: 860 Nl/min
- Fluid: compressed air
- Weight: 40g
- Mounting position: vertical
- Condensate drain: manual/semi-auto
- Bowl capacity: 16cm³

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 13 bar






BSPP

9154	Thread BSPP	Micron µm
5101002	1/8"	20
5101001	1/8"	5
5201002	1/4"	20
5201001	1/4"	5

Miniature Lubricator

- Type of lubrication: oil mist
- Bowl capacity: 26.5cm³
- Flow rate at 6 bar ΔP 0.5 bar: 400 Nl/min
- Fluid: compressed air
- Weight: 40g

Maximum Temperature at 1MPa, 10 bar (145 psi): +50°C





BSPP


9154	Thread BSPP
5103001	1/8"
5203001	1/4"

Miniature Pressure Regulator

- Flow rate at 6 bar ΔP 0.5 bar: 340 Nl/min
- Fluid: filtered, lubricated or non-lubricated compressed ai
- Weight: 80g
- Mounting position: any
- Gauge port: G1/8"

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 13 bar





BSPP

9154	Thread BSPP	Pressure Range bar
5107003	1/8"	0 to 8
5107004	1/8"	0 to 12
5207003	1/4"	0 to 8
5207004	1/4"	0 to 12

Miniature Pressure Regulator, Padlockable



BSPP


9154	Thread BSPP	Pressure Range bar
5110003	1/8"	0 to 8
5110004	1/8"	0 to 12
5210003	1/4"	0 to 8
5210004	1/4"	0 to 12

Miniature Filter Regulator

- Flow rate at 6 bar ΔP 0.5 bar: 290 Nl/min
- Fluid: compressed air
- Weight: 110g
- Mounting position: vertical
- Gauge port: G1/8"
- Bowl capacity: 16cm³
- Condensate drain: manual/semi-auto

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 13 bar





BSPP


9154	Thread BSPP	Micron µm	Pressure Range bar
5105008	1/8"	20	0 to 8
5105011	1/8"	20	0 to 12
5205008	1/4"	20	0 to 8
5205011	1/4"	20	0 to 12

Miniature Filter + Regulator + Lubricator Set

- Flow rate at 6 bar ΔP 0.5 bar: 150 Nl/min
- Fluid: compressed air
- Weight: 160g
- Mounting position: any
- Gauge port: G1/8"

Maximum Temperature at 1MPa, 10 bar (145 psi): +50°C

Maximum Inlet Pressure: 13 bar





BSPP

9154	Thread BSPP	Micron µm	Pressure Range bar
5104008	1/8"	20	0 to 8
5104011	1/8"	20	0 to 12
5204008	1/4"	20	0 to 8

MINIATURE FRLS, 'BIT'


Miniature Oil Removal Filter

- Degree of filtration: 99.97% 0.01µm
- Flow rate at 6 bar ΔP 0.5 bar: 700 Nl/min
- Fluid: compressed air
- Weight: 65g
- Mounting position: vertical
- Condensate drain: manual/semi-auto
- Bowl capacity: 16cm³

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 13 bar

NB: it is advisable to mount a 5µm filter upstream acting as a rough filter.






BSPP

9154	Thread BSPP
5212001	1/4"

Miniature Filter Regulator + Lubricator Set

- Flow rate at 6 bar ΔP 0.5 bar: 140 Nl/min
- Flow rate at 6 bar ΔP 1 bar: 260 Nl/min
- Fluid: compressed air
- Weight: 170g
- Mounting: vertical
- Gauge port: G1/8"

Maximum Inlet Pressure: 13 bar






BSPP

9154	Thread BSPP	Micron µm	Pressure Range bar
5106008	1/8"	20	0 to 8
5106011	1/8"	20	0 to 12
5206008	1/4"	20	0 to 8
5206011	1/4"	20	0 to 12

Mounting Hardware





Bit Regulator Bracket

9154	Description
9200701	Mounting Bracket
9170301	Wall Mounting Kit

Automatic Drain



To suit Miniature Filters

9154	Description
9000803	For Miniature Filters

Filter Elements



Spare

9154	Micron µm
9251708	5
9251709	20
9251712	For Coalescing Filter, 0.001

FT PRO



For **Gauges** see page **409**

Fluid-Air Components Ltd

FILTER REGULATOR FOR WATER, 'BIT' SERIES F

- Filtering and/or water pressure regulation units, characterised by the use of materials certified to specific standards on products for use in contact with foodstuff or drinking water.
- Declarations of conformity and release test reports are available on request for those who need them to certify our product incorporated in their own systems.
- The white colour surface finish of the body was chosen to enhance the highly hygienic properties of the product.
- If the pressure regulator works with incompressible fluids (water) and there is a valve leak, the downstream pressure could rise up to reach the inlet pressure and then it re-stabilises with water consumption.
- If necessary, consider the possibility of installing a safety valve that relieves any excess pressure.
- Fluid: water, air and fluids compatible with materials used

- Flow rate at 6.3 bar ΔP 1 bar: 6 up to 14.5 l/min dependant on model (refer to sales department)
- Gauge port: regulator, filter regulator, 1/8" BSPP
- Mounting: fixing plates 9170301, regulator bracket 9200701


Certifications

- European Regulation (EU) 10/2011, KTW, W270, WRAS, ACS, NSF61
- Approved for compliance with the UBA list, NSF/ANSI 372
- European Regulation (EU) 10/2011, KTW, W270, WRAS, NSF61, DM174/04, KTW, W270, WRAS, ACS, NSF61
- Approved for compliance with the UBA list, DM174/04, KTW, W270, WRAS, ACS, NSF61

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 13 bar

Filter for Water



BSPP

9154	Thread BSPP	Micron µm
5101002F	1/8"	20
5201002F	1/4"	20


Regulator for Water



Brass Ports, BSPP

9154	Thread BSPP	Pressure Range bar
5108001F	1/8"	0 to 2
5108002F	1/8"	0 to 4
5108003F	1/8"	0 to 8
5108004F	1/8"	0 to 12
5208001F	1/4"	0 to 2
5208002F	1/4"	0 to 4
5208003F	1/4"	0 to 8
5208004F	1/4"	0 to 12


Regulator for Water



Technopolymer Ports (No Gauge Port), BSPP

9154	Thread BSPP	Pressure Range bar
5228001F	1/4"	0 to 2
5228002F	1/4"	0 to 4
5228003F	1/4"	0 to 8
5228004F	1/4"	0 to 12

Filter Regulator for Water



BSPP

9154	Thread BSPP	Micron µm	Pressure Range bar
5105111F	1/8"	20	0 to 12
5205102F	1/4"	20	0 to 2
5205105F	1/4"	20	0 to 4
5205111F	1/4"	20	0 to 12

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STANDARD SERIES FRLS, 'SYNTESI'

Syntesi® is an important milestone achieved by Metal Work, the result of thirty years' experience producing air treatment units. Syntesi® obtains the best possible performance in a reduced space and with limited weight. The capacity is much higher than that of other units of the same size. These modular units feature a very simple yet effective system that requires no brackets, stay bolts or yoke for assembling the elements.

The basic version of Syntesi® incorporates numerous functions that are not provided or are only optional with traditional units:

- Padlockable knobs
- Additional pneumatic ports on the front and back
- Flow options from left to right or vice versa
- Regulators with compensation system which are accurate even when the upstream pressure changes, with rapid downstream pressure relief
- Full indelible marking
- Automatic condensate drain even in size 1
- 360° visual inspection of oil and condensate levels

The basic materials – technopolymer and nickel-plated brass – have excellent corrosion resistance. An anti-corrosion version is available with stainless steel components (screws and plates) or Geomet® related ones (regulator springs).



Technical Specifications

- Padlockable knob: the knobs of the regulators, filter regulators and standard sectioning valves can all be padlocked
- Fluid: compressed air or other inert gases

Body Size	Threaded Port BSP	Maximum Input Pressure bar	Temperature Range at 1 MPa, 10 bar (145 psi)
1	1/8"	15	-10°C to +50°C
	1/4"		
	3/8"		
2	3/8"	13	-10°C to +50°C
	1/2"		
	3/4"		
	1"		



Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 1 bar (0.1 MPa, 14 psi)	1300	1650	1750	4500	5200	5200	
Weight g	178	173	164	488	461	457	445
Condensate Bowl Capacity cm3	30			70			
Mounting Position	Vertical			Vertical			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			

Standard Filter, Body Size 1

Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5611F201	1/8"	20
5612F202	1/4"	20
5613F203	3/8"	20

Standard Filter, Body Size 1

Auto Drain, BSPP

9154	Thread BSPP	Micron µm
5611F501	1/8"	20
5612F502	1/4"	20
5613F503	3/8"	20

Standard Filter, Body Size 2

Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5623F203	3/8"	20
5624F204	1/2"	20
5625F205	3/4"	20
5626F206	1"	20

Standard Filter, Body Size 2

Auto Drain, BSPP

9154	Thread BSPP	Micron µm
5623F503	3/8"	20
5624F504	1/2"	20
5625F505	3/4"	20
5626F506	1"	20

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'SYNTESI'

Oil Removal Filter, Body Size 1

Technical Data	Body Size 1		
Maximum Input Pressure bar	15		
Suggested Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi)	460		
Weight g	194	189	180
Bowl Capacity cm3	15		
Mounting Position	Vertical		
Wall Fixing Screws	No. 2 M4 Screws		

Oil Removal Filter, Body Size 2

Technical Data	Body Size 2			
Maximum Input Pressure bar	13			
Suggested Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi)	620			
Weight g	483	456	452	440
Bowl Capacity cm3	40			
Mounting Position	Vertical			
Wall Fixing Screws	No. 2 M5 Screws			



Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5611D101	1/8"	0.01
5612D102	1/4"	0.01
5613D103	3/8"	0.01

Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5623D103	3/8"	0.01
5624D104	1/2"	0.01
5625D105	3/4"	0.01
5626D106	1"	0.01

Active Carbon Filter, Body Size 1

Technical Data	Body Size 1		
Maximum Input Pressure bar	15		
Suggested Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi)	350		
Weight g	195	190	181
Inlet Fluid	0.01 mm filtred and depurated air		
Mounting Position	Any		
Wall Fixing Screws	No. 2 M4 Screws		

Active Carbon Filter, Body Size 2

Technical Data	Body Size 2			
Maximum Input Pressure bar	13			
Suggested Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi)	800			
Weight g	483	456	452	440
Inlet Fluid	0.01 mm filtred and depurated air			
Mounting Position	Any			
Wall Fixing Screws	No. 2 M5 Screws			



Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5611C101	1/8"	0.003
5612C102	1/4"	0.003
5613C103	3/8"	0.003

Manual Drain, BSPP

9154	Thread BSPP	Micron µm
5623C103	3/8"	0.003
5624C104	1/2"	0.003
5625C105	3/4"	0.003

aircom PIPINGSYSTEM

For **Piping Systems**
see pages **1068-1080**



Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'SYNTESI'

Pressure Regulator

Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 1 bar (0.1 MPa, 14 psi)	570	1650	2900	3000	4300	4700	
Weight g	193	188	179	546	519	515	503
Mounting Position	Any			Any			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			
Gauge Port	1/8" BSP			1/4" BSP			



Body Size 1, Relieving, BSPP

9185	Thread BSPP	Pressure Range bar
5611R141	1/8"	0 to 8
5611R161	1/8"	0 to 12
5612R142	1/4"	0 to 8
5612R162	1/4"	0 to 12
5613R143	3/8"	0 to 8
5613R163	3/8"	0 to 12

Body Size 2, Relieving, BSPP

9185	Thread BSPP	Pressure Range bar
5623R143	3/8"	0 to 8
5623R163	3/8"	0 to 12
5624R144	1/2"	0 to 8
5624R164	1/2"	0 to 12
5625R145	3/4"	0 to 8
5625R165	3/4"	0 to 12
5626R146	1"	0 to 8
5626R166	1"	0 to 12

In-series Regulator


The in-series regulator is used to take air at a set pressure from the ports on the front and back of the body, while the pneumatic inlet and outlet ports are connected directly.

It is possible to assemble several regulators side by side, all supplied at the same pressure, and obtain different regulated pressures, regardless of the pressure of the previous module.

The in-series regulator uses the same construction principles as the standard regulator, so the advantages are the same, such as compensation for upstream pressure changes, relief valve, rapid relief of the downstream pressure and a padlockable push-lock knob.



Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 1 bar (0.1 MPa, 14 psi)	500			1000			
Weight g	193	188	179	546	519	515	503
Mounting Position	Any			Any			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			
Gauge Port	1/8" BSP			1/4" BSP			



1. Technopolymer adjusting knob
2. Technopolymer bell
3. Steel adjusting spring (with Geomet. treatment for anti-corrosion version)
4. Technopolymer flang
5. Rolling diaphragm
6. IN/OUT bushing made of OT58 nickel-plated brass or passivated aluminium for 3/4" - 1"
7. Technopolymer body
8. OT58 brass valve, with NBR vulcanized gasket
9. Stainless steel valve spring
10. Galvanised steel plate for knob locking (stainless steel for anti-corrosion version)
11. OT58 brass adjusting screw
12. Technopolymer ring nut
13. Technopolymer plate
14. Technopolymer rod
15. NBR o-ring gaskets
16. Technopolymer plug

Body Size 1, Relieving, BSPP

9185	Thread BSPP	Pressure Range bar
5611R241	1/8"	0 to 8
5611R261	1/8"	0 to 12
5612R242	1/4"	0 to 8
5612R262	1/4"	0 to 12
5613R243	3/8"	0 to 8
5613R263	3/8"	0 to 12

Body Size 2, Relieving, BSPP

9185	Thread BSPP	Pressure Range bar
5623R243	3/8"	0 to 8
5623R263	3/8"	0 to 12
5624R244	1/2"	0 to 8
5624R264	1/2"	0 to 12
5625R245	3/4"	0 to 8
5625R265	3/4"	0 to 12
5626R246	1"	0 to 8
5626R266	1"	0 to 12

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'SYNTESI'

Standard Filter Regulator

Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 1 bar (0.1 MPa, 14 psi)	500	800	2200	3200	4300		5200
Weight g	244	239	230	623	596	592	580
Bowl Capacity cm3	30			70			
Mounting Position	Vertical			Vertical			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			
Gauge Port	1/8" BSP			1/4" BSP			



Standard Filter Regulator, Body Size 1, Relieving Manual Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5611B241	1/8"	20	0 to 8
5611B261	1/8"	20	0 to 12
5612B242	1/4"	20	0 to 8
5612B262	1/4"	20	0 to 12
5613B243	3/8"	20	0 to 8
5613B263	3/8"	20	0 to 12

Standard Filter Regulator, Body Size 1, Relieving Auto Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5611B541	1/8"	20	0 to 8
5611B561	1/8"	20	0 to 12
5612B542	1/4"	20	0 to 8
5612B562	1/4"	20	0 to 12
5613B543	3/8"	20	0 to 8
5613B563	3/8"	20	0 to 12

Standard Filter Regulator, Body Size 2, Relieving Manual Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5623B243	3/8"	20	0 to 8
5623B263	3/8"	20	0 to 12
5624B244	1/2"	20	0 to 8
5624B264	1/2"	20	0 to 12
5625B245	3/4"	20	0 to 8
5625B265	3/4"	20	0 to 12
5626B246	1"	20	0 to 8
5626B266	1"	20	0 to 12

Standard Filter Regulator, Body Size 2, Relieving Auto Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5623B543	3/8"	20	0 to 8
5623B563	3/8"	20	0 to 12
5624B544	1/2"	20	0 to 8
5624B564	1/2"	20	0 to 12
5625B545	3/4"	20	0 to 8
5625B565	3/4"	20	0 to 12
5626B546	1"	20	0 to 8
5626B566	1"	20	0 to 12

Standard Lubricator

Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 1 bar (0.1 MPa, 14 psi)	1300	1700	2200	2300	3900		3900
Weight g	185	180	171	480	453	449	437
Quantity of Fitted Oil cm3	60			130			
Mounting Position	Vertical			Vertical			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			



Body Size 1, BSPP

9154	Thread BSPP
5611L101	1/8"
5612L102	1/4"
5613L103	3/8"

Body Size 2, BSPP

9185	Thread BSPP
5623L103	3/8"
5624L104	1/2"
5625L105	3/4"
5626L106	1"

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'SYNTESI'

Shut Off Valve

Technical Data	Body Size 1			Body Size 2			
Maximum Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 0.5 bar (0.05 MPa, 7 psi)	800	1000	1100	2800	3000		3000
Weight g	197	192	183	476	449	445	433
Mounting Position	Any			Any			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			



Body Size 1, Manual, BSPP

9185	Thread BSPP
5611V101	1/8"
5612V102	1/4"
5613V103	3/8"

Body Size 2, Manual, BSPP

9185	Thread BSPP
5623V103	3/8"
5624V104	1/2"
5625V105	3/4"
5626V106	1"

Body Size 1, Pneumatic, BSPP

9185	Thread BSPP
5611V201	1/8"
5612V202	1/4"
5613V203	3/8"

Body Size 2, Pneumatic, BSPP

9185	Thread BSPP
5623V203	3/8"
5624V204	1/2"
5625V205	3/4"
5626V206	1"

S Body Size 1, Solenoid, BSPP

9185	Thread BSPP
5611V701	1/8"
5612V702	1/4"
5613V703	3/8"

Body Size 2, Solenoid, BSPP

9185	Thread BSPP
5623V703	3/8"
5624V704	1/2"
5625V705	3/4"
5626V706	1"

FT PRO



For **FT Pro One Touch All Metal Push-in Fittings**
see pages **843-847**

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'SYNTESI'

Progressive Starter

Technical Data	Body Size 1			Body Size 2			
Input Pressure Range bar	3 to 10			3 to 10			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 0.5 bar (0.05 MPa, 7 psi)	900	1000	1100	2800	3600		3600
Weight g	203	198	189	503	476	472	460
Mounting Position	Any			Any			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			



Body Size 1, BSPP

9185	Thread BSPP
5611A701	G1/8"
5612A702	G1/4"
5613A703	G3/8"

Body Size 2, BSPP

9185	Thread BSPP
5623A703	G3/8"
5624A704	G1/2"
5625A705	G3/4"
5626A706	G1"

Pressure Switch

Technical Data	Body Size 1	Body Size 2
Maximum Pressure bar	15	13
Maximum Current A	2	2
Maximum Voltage V	250	250
Cable OD mm	4.9	4.9
Fluid	Filtered lubricated or non-lubricated compressed air. Lubrication, if used, must be continuous	
Mounting Position	Any	Any
Wall Fixing Screws	No. 2 M4 Screws	No. 2 M5 Screws



Body Size 1, M8 Connector, BSPP

9185	Thread BSPP
5611S201	G1/8"
5612S202	G1/4"
5613S203	G3/8"

Body Size 2, M8 Connector, BSPP

9185	Thread BSPP
5623S203	G3/8"
5624S204	G1/2"
5625S205	G3/4"
5626S206	G1"

Filter Regulator + Lubricator Set

Technical Data	Body Size 1			Body Size 2			
Input Pressure bar	15			13			
Flow Rate Nl/min at 6.3 bar (0.63 MPa, 91 psi) ΔP 0.5 bar (0.05 MPa, 7 psi)	350			1200			
Weight g	414	409	400	1074	1074	1043	1031
Mounting Position	Vertical			Vertical			
Wall Fixing Screws	No. 2 M4 Screws			No. 2 M5 Screws			
Gauge Port	1/8" BSP			1/4" BSP			



Body Size 1, Manual Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5611B24L101	G1/8"	20	0 to 8
5612B24L102	G1/4"	20	0 to 8
5613B24L103	G3/8"	20	0 to 8

Body Size 2, Manual Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5623B24L103	G3/8"	20	0 to 8
5624B24L104	G1/2"	20	0 to 8
5625B24L105	G3/4"	20	0 to 8
5626B24L106	G1"	20	0 to 8

Body Size 1, Auto Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5611B54L101	G1/8"	20	0 to 8
5612B54L102	G1/4"	20	0 to 8
5613B54L103	G3/8"	20	0 to 8

Body Size 2, Auto Drain, BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
5623B54L103	G3/8"	20	0 to 8
5624B54L104	G1/2"	20	0 to 8
5625B54L105	G3/4"	20	0 to 8
5626B54L106	G1"	20	0 to 8

Fluid-Air Components Ltd

ACCESSORIES, 'SYNTESI'

Connecting Nipple Kit



Body Size 1

9185
9210000

Connecting Nipple Kit

Body Size 2

9185
9210010

Threaded Port Kit



Body Size 1

9185	Thread BSPP
9210001	G1/8"
9210002	G1/4"
9210003	G3/8"

Threaded Port Kit

Body Size 2

9185	Thread BSPP
9210011	G3/8"
9210012	G1/2"
9210013	G3/4"
9210014	G1"

Automatic Drain



Maximum Inlet Pressure: 10 bar

To suit Body Sizes 1 & 2

9185
9000802

Replacement Elements



Spare, Body Size 1

9185	Micron µm
9210150	5
9210151	20

Replacement Elements

Spare, Body Size 2

9185	Micron µm
9210155	5
9210156	20

Replacement Elements



Oil Removal, Body Size 1

9185
9210160

Replacement Elements

Oil Removal, Body Size 2

9185
9210165

Replacement Elements



Active Carbon, Body Size 1


9185
9210161

Replacement Elements

Active Carbon, Body Size 2

9185
9210166

Mountings





Bracket for Regulators

9154	To Sizes
9200701	Body size 1
9400701	Body size 2

Square Dial Pressure Gauge

- A compact pressure gauge with a square dial suitable for air treatment units.
- Suitable for use with Metal Work Bit, Syntesi, New Deal and Skillair ranges.
- A PTFE ring seal mounted on the 1/8" thread of the fiting ensures a perfect pneumatic seal.
- To mount it, screw the gauge in as far as it will go, then loosen enough to align the dial. A sealant is not required.
- The pressure gauge has a neck to dampen pressure vibration and absorb water hammer. This improves overall reliability and guarantees longer life.





G1/8" Thread

9154	Pressure Range (bar)
9700109	0 to 4
9700110	0 to 12

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'NEW DEAL'

Standard Filter


Technical Specification
- Fluid: compressed air
- Mounting position: vertical
- Condensate drain: manual/semi-auto

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Dimensions

Thread BSP	A	B	C	D	E	G	H	L (Hole)	M	kg
G1/4"	42	142	42	42	32	10	21	M4	185	0.4
G3/8"	60	180	60	60	46	14	30	M4	230	0.9
G1/2"	60	180	60	60	46	14	30	M4	230	0.9
G3/4"	80	235	80	80	66	22	40	M6	325	1.9
G1"	80	235	80	80	66	22	40	M6	325	1.9





Manual/Semi-auto, BSPP

9154	Thread BSPP	Micron µm
1221006	G1/4"	20
1321006	G3/8"	20
1421006	G1/2"	20
1521006	G3/4"	20
1621006	G1"	20

Technical Specification
- Fluid: filtered, lubricated or non-lubricated compressed air

*Lubrication, if used, must be continuous.

Oil Removal Filter

Technical Specification
- Degree of filtration: 99.97% 0.01µ
- Flow rate at 6 bar ΔP 1 bar: 1600 Nl/min
- Fluid: filtered 4µm compressed ai
- Weight: 0.9kg
- Mounting position: vertical
- Bowl capacity: 45cm³


NB: It is advisable to mount a 4µ filter upstream acting as a rough filt .

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Dimensions

Thread BSP	A	B	C	D	E	G	H	L (Hole)	M
G1/2"	60	180	60	60	46	14	30	M4	230





BSPP

9154	Thread BSPP
1422002	G1/2"

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Dimensions

Thread BSP	A	B	C	D	E	F	G	H	I	L (Hole)	M	N	kg
G1/4"	42	142	42	42	32	30 x 1.5	10	21	25	M4	185	G1/8"	0.3
G3/8"	60	180	60	60	46	38 x 2	14	30	35	M4	230	G1/8"	0.8
G1/2"	60	180	60	60	46	38 x 2	14	30	35	M4	230	G1/8"	0.8
G3/4"	80	235	80	80	66	55 x 2	22	40	47	M6	325	G1/4"	2.2
G1"	80	235	80	80	66	55 x 2	22	40	47	M6	325	G1/4"	2.2

Security Knob

NOTE: pull outwards to remove the knob from the pressure switch on the unit. Insert the security knob and regulate the pressure switch. Then press the handle firmly to lock it in position. If the pressure switch needs to be reset, remove the security knob by forcing it laterally with a screwdriver.




To suit 9000401 & 9000402

9149
9200703

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'NEW DEAL'

Pressure Regulator





BSPP

9154	Thread BSPP	Pressure Range bar
1202002	G1/4"	0 to 8
1202003	G1/4"	0 to 12
1302002	G3/8"	0 to 8
1302003	G3/8"	0 to 12
1402002	G1/2"	0 to 8
1402003	G1/2"	0 to 12
1502003	G3/4"	0 to 12
1602003	G1"	0 to 12

Pressure Regulator, Padlockable



BSPP

9154	Thread BSPP	Pressure Range bar
1210013	G1/4"	0 to 8
1210014	G1/4"	0 to 12
1310013	G3/8"	0 to 8
1310014	G3/8"	0 to 12
1410013	G1/2"	0 to 8
1410014	G1/2"	0 to 12

Filter Regulator

Technical Specification
- Mounting position: vertical


NB: the regulator pressure must always be set upwards.


Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Dimensions

Thread BSP	A	B	C	D	E	F	G	I	L (Hole)	M	N	P	kg
G1/4"	42	190	42	42	36	30 x 1.5	10	121	M4	145	G1/8"	233	0.5
G3/8"	60	245	60	60	52	30 x 1.5	14	150	M4	185	G1/8"	295	1
G1/2"	60	245	60	60	52	30 x 1.5	14	150	M4	185	G1/8"	295	1







BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
1225030	G1/4"	20	0 to 8
1225054	G1/4"	20	0 to 12
1325030	G3/8"	20	0 to 8
1325054	G3/8"	20	0 to 12
1425030	G1/2"	20	0 to 8
1425054	G1/2"	20	0 to 12

Lubricator

Technical Specification
- Fluid: filtered compressed air
- Mounting position: vertical


Maximum Temperature at 10 bar: +50°C


Maximum Inlet Pressure: 18 bar

Notes
- Use the screw provided to set the drip rate to drop every 300-600ml.
- Fit the lubricator as close as possible to the point of use
- Fill the bowl with oil before pressurising the system
- Do not use cleaning oil, brake fluid or solvents in general
- Recommended lubricants: ISO and UNI FD22, e.g. Energol HLP 22(BP), Spinesso 22 (Esso), Mobil, Tellus Oil 22 (Shell)
- Automatic filling lubricato and minimum level lubricator

Dimensions

Thread BSP	A	B	C	D	E	G	I	L (Hole)	M	kg
G1/4"	42	156	42	42	32	10	121	M4	176	0.4
G3/8"	60	195	60	60	46	14	136	M4	220	0.9
G1/2"	80	195	80	80	66	22	182	M4	290	0.9
G3/4"	80	260	80	80	66	22	182	M6	290	1.8
G1"	80	260	80	80	66	22	182	M6	290	1.8







BSPP

9154	Thread BSPP
1223001	G1/4"
1323001	G3/8"
1423001	G1/2"
1523001	G3/4"
1623001	G1"

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'NEW DEAL'

Filter + Regulator + Lubricator Set

Technical Specification
- Fluid: compressed air


Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Notes
- Highly reliable, heavy duty, piston operated
- FRL unit
- Stability of the set pressure as the upstream pressure varies
- Metal bowl with external sight glass
- Semi-automatic and automatic condensate drain
- Lubrication proportional to flow rat
- Micrometric lubrication regulation
- Activation guaranteed with low flow rate

Dimensions

Thread BSPP	A	B	D	E	G	L (Hole)	kg
G1/4"	42	190	126	116	20	M4	1
G3/8"	60	245	180	166	28	M4	2.5
G1/2"	60	245	180	166	28	M4	2.5
G3/4"	80	332	240	226	44	M6	5.8
G1"	80	332	240	226	44	M6	5.8



BSPP

9185	Thread BSPP	Micron µm	Pressure Range bar
1224030	G1/4"	20	0 to 8
1224054	G1/4"	20	0 to 12
1324030	G3/8"	20	0 to 8
1324054	G3/8"	20	0 to 12
1424030	G1/2"	20	0 to 8
1424054	G1/2"	20	0 to 12
1524030	G3/4"	20	0 to 12
1624030	G1"	20	0 to 12

Filter Regulator + Lubricator Sets


Technical Specification
- Fluid: compressed air

Maximum Temperature at 10 bar: +50°C

Maximum Inlet Pressure: 18 bar

Dimensions

Thread BSPP	A	B	D	E	G	L (Hole)	kg
G1/4"	42	190	84	76	10	M4	0.9
G3/8"	60	240	120	109	14	M4	2
G1/2"	60	240	120	109	14	M6	2



BSPP

9185	Thread BSPP	Micro µm	Pressure Range bar
1226030	G1/4"	20	0 to 8
1226054	G1/4"	20	0 to 12
1326030	G3/8"	20	0 to 8
1326054	G3/8"	20	0 to 12
1426030	G1/2"	20	0 to 8
1426054	G1/2"	20	0 to 12

Shut Off Valve

Technical Specification
- Fluid: filtered, lubricated or non lubricated compressed air*


Maximum Temperature at 10 bar: +50°C

Inlet Pressure: 18 bar

* Lubrication, if used, must be continuous.

Dimensions

Thread BSPP	A	B	C	D	E	F	G	I	L (Hole)	kg
G1/4"	42	105	42	42	32	10	42	32	M4	0.35
G3/8"	60	126	60	60	46	14	60	43	M4	0.8
G1/2"	60	126	60	60	46	14	60	43	M4	0.8



Lockable

9154	Thread BSPP
1270001	G1/4"
1370001	G3/8"
1470001	G1/2"


Distribution Block

Maximum Working Temperature at 10 bar: +50°C

Maximum admissible Pressure: 18 bar

Dimensions

Thread BSPP	A	B	C	D	E	F	G	H (No2 pos)	L (Hole)
G1/4"	42	42	15	34	34	8.5	8.5	21	M4
G3/8"	60	60	20	49	49	14	14	30	M4
G1/2"	60	60	20	49	49	14	14	30	M4
G3/4"	80	80	30	64	64	16	16	40	M6
G1"	80	80	30	64	64	16	16	40	M6



BSPP

9154	To Suit
9200401	G1/8" for G1/4
9400401	G1/4" for G3/8 to G1/2
9600401	G1/2" for G3/4 to G1

STANDARD SERIES FRLS, 'NEW DEAL' ACCESSORIES

Drip Leg Drain

Technical Specifications
- Threaded port: G1/2"
- Wall fixing screws: M6 x 75

System supply condensate drain:
- All-round condensate level viewing
- Automatic drain from inside the bowl
- Axial coupling

Maximum Working Temperature at 10 bar: +50°C


Maximum admissible Pressure: 18 bar



BSPP

9154	Thread BSPP
4589003	G1/2"

Mountings






Bracket for Regulators

9154	To Suit Sizes
9200701	G1/4"
9400701	G3/8" to G1/2"

Mountings





Spacers for Wall Mount FRLs

9154	To Suit Sizes
9200601	G1/4"
9400601	G3/8" to G1/2"
9600601	G3/4"

Filter Element



Spare

9154	To Suit Sizes	Micron µm
9250103	G1/4"	4
9250102	G1/4"	20
9450103	G3/8" to G1/2"	4
9450102	G3/8" to G1/2"	20
9650103	G3/4" to G1"	4
9650102	G3/4" to G1"	20
9450105	G3/8" to G1/2"	0.01

Shut Off Valve Adaptor



Brass

9154	To Suit Sizes
9201001	G1/4"
9401001	G3/8"
9401002	G1/2"

Automatic Drains



Maximum Inlet Pressure: 10 bar

Fully Automatic

9185	To Suit Sizes
9000802	G3/8" to G1"

Automatic Drains



Semi-automatic

9154	To Suit Sizes
9000803	G1/4" to G1/2"

Automatic Drains




Metal Bowl for use with Semi-auto & Auto Drains

9154	To Suit Sizes
9255201	G1/4"
9455201	G3/8" to G1/2"

Square Dial Pressure Gauge

- A compact pressure gauge with a square dial suitable for air treatment units.
- Suitable for use with Metal Work Bit, Syntesi, New Deal and Skillair ranges.
- A PTFE ring seal mounted on the 1/8" thread of the fitting ensures a perfect pneumatic seal.
- To mount it, screw the gauge in as far as it will go, the loosen enough to align the dial. A sealant is not required.
- The pressure gauge has a neck to dampen pressure vibration and absorb water hammer. This improves overall reliability and guarantees longer life.





G1/8" Thread

9154	Pressure Range (bar)
9700109	0 to 4
9700110	0 to 12

Fluid-Air Components Ltd

STANDARD SERIES FRLS, 'NEW DEAL' BREATHE AIR SET


Breathe Air Set

Breathe provides high quality, clean air, essential for paint spraying and breathing air applications. Designed for self-contained operations, it will filter compressed air directly from most types of compressor and ring main systems.

Breathe will supply sufficient breathable air for up to two men on constant demand and will provide breathing quality air to a higher standard than specified in BS4275: 1974

Technical Specification

- Element grade: XA and AC
- Threaded port: 1/2" BSP
- Particle removal: 0.01 microns
- Maximum oil carry over @ +20°C: 0.005 mg/cu m
- Pressure loss, clean and dry: 150 mbar
- Pressure loss, saturated: 350 mbar
- Pressure loss, change element: 400 mbar



Dimensions

A	60mm	E	121mm
B	180mm	G	14mm
D	135mm	L	4mm Hole



Maximum Recommended Temperature: +25°C

Maximum Working Pressure: 16 bar

BSP

9154	Element Grade	Thread Size BSP	Micron µm	Pressure Range Bar
Z29100BREATHE	XA & SC	1/2"	0.01	0 to 16

FT PRO



For **FT Pro Pneumatic Hose** see pages **895-904**

FRLS, 'SKILLAIR'

Filter, 200 Series

Technical Specification
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 2400 Nl/min
- Fluid: compressed air
- Weight: 0.7kg

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
3480002	1/4"
3580002	3/8"
3680002	1/2"

Regulator, 200 Series

Technical Specification
- Setting range: 0 to 8 bar
- Flow rate at 6.3 bar: 25000 Nl/min
- Weight: 0.7kg
- Mounting: any position
- Pressure gauge port: G1/8"

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
3402003	1/4"
3502003	3/8"
3602003	1/2"

Filter, 300 Series

Technical Specification
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 3800 Nl/min
- ΔP 0.5 bar (0.005 MPa, 7 psi): 135 scfm
- Fluid: compressed air
- Weight: 1.4 kg

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
4480002	1/2"
4580002	3/4"
4680002	1"

Regulator, 300 Series

Technical Specification
- Setting range: 0 to 8 bar
- Flow rate at 6.3 bar: 35000 Nl/min
- Weight: 1.4kg

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
4402002	1/2"
4502002	3/4"
4602002	1"

Filter, 400 Series

Technical Specification
- Degree of filtration: 20µ
- Flow rate at 6.3 bar:
  - 16500 (G11/2") Nl/min, 20000 (G2") Nl/min
- Fluid: compressed air
- Weight: 1.4kg

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP


9193	Thread BSPP
6380002	1.1/2"
6480002	2"

Regulator, 400 Series

Technical Specification
- Setting range: dependent on pilot operating regulator
- Flow rate at 6.3 bar:
  18000 (G1.1/2") Nl/min, 20000 (G2") Nl/min
- Weight: 4.8kg (G1.1/2"), 5.6kg (G2")
- Mounting: any position
- Pressure gauge port: G1/4"
- Requires pilot regulator

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
6302001	1.1/2'
6402001	2"

FRLS, 'SKILLAIR'

Pilot Regulator, 400 Series

Technical Specification
- Flow rate at 6.3 bar ΔP 0.5 bar: 120 Nl/min
- Weight: 0.6kg
- Pressure gauge port: G1/8"

Maximum Temperature at 10 bar: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP	Pressure Range bar
3206001	1/4"	2
3206002	1/4"	4
3206003	1/4"	8
3206004	1/4"	12

Filter Regulator, 200 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar ΔP 0.5 bar: 1600 Nl/min
- Weight: 1kg
- Pressure gauge port: G1/8"

Maximum Temperature: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
3483008	1/4"
3583008	3/8"
3683008	1/2"

Filter Regulator, 300 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 3500 Nl/min
- ΔP 0.5 bar: 57 scfm
- Weight: 1.8kg
- Pressure gauge port: G1/8"

Maximum Temperature: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
4483005	1/2"
4583005	3/4"
4683005	1"

Lubricator, 200 Series

Technical Specification
- Bowl capacity: 95
- Flow rate at 6.3 bar: 2200 Nl/min
- Weight: 0.7kg

Maximum Temperature: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
3481001	1/4"
3581001	3/8"
3681001	1/2"

Lubricator, 300 Series

Technical Specification
- Bowl capacity: 160
- Flow rate at 6.3 bar: 3500 Nl/min
- Weight: 1.4kg

Maximum Temperature: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
4481001	1/2"
4581001	3/4"
4681001	1"

Lubricator, 400 Series

Technical Specification
- Type of lubrication: mist
- Bowl capacity: 800
- Flow rate at 6.3 bar: 18.000 (G1.1/2") Nl/min, 21.000 (G2") Nl/min
- Weight: 4.9kg (G1.1/2"), 5.7kg (G2")

Maximum Temperature: +50°C

Maximum Input Pressure: 13 bar



BSPP

9193	Thread BSPP
6381001	1.1/2"
6481001	2"

Fluid-Air Components Ltd

FRLS, 'SKILLAIR'

Manual Shut Off Valve, 200 Series

Technical Specification
- Flow rate at 6.3 bar: 24000 Nl/min
- Weight: 0.8kg

Maximum Temperature at 1 MPa, 10 bar (145 psi):
+50°C

Maximum Inlet Pressure (solenoid version:
3 bar
Maximum Inlet Pressure:
13 bar



BSPP

9193	Thread BSPP
3470001	1/4"
3570001	3/8"
3670001	1/2"

Filter + Regulator + Lubricator, 200 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 1300 Nl/min
- Weight: 1.5kg

Maximum Temperature:
+50°C

Maximum Inlet Pressure:
13 bar



BSPP

9193	Thread BSPP
3482008	1/4"
3582008	3/8"
3682008	1/2"

Manual Shut Off Valve, 300 Series

Technical Specification
- Flow rate at 6.3 bar: 32000 Nl/min
- Weight: 1.2kg

Maximum Temperature at 1 MPa, 10 bar (145 psi):
+50°C

Maximum Inlet Pressure (solenoid version:
2 bar
Maximum Inlet Pressure:
13 bar



BSPP

9193	Thread BSPP
4470001	1/2"
4570001	3/4"
4670001	1"

Filter + Regulator + Lubricator, 300 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 2500 Nl/min
- Weight: 2.9kg

Maximum Temperature:
+50°C

Maximum Inlet Pressure:
13 bar



BSPP

9193	Thread BSPP
4482005	1/2"
4582005	3/4"
4682005	1"

Fluid-Air Components Ltd

FRLS, 'SKILLAIR'

Filter Regulator + Lubricator, 200 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 1200 Nl/min
- Weight: 1.35kg

Maximum Temperature: +50°C

Maximum Inlet Pressure: 13 bar



BSPP

9193	Thread BSPP
3484008	1/4"
3584008	3/8"
3684008	1/2"

Filter Regulator + Lubricator, 300 Series

Technical Specification
- Setting range: 0 to 8 bar
- Degree of filtration: 20µ
- Flow rate at 6.3 bar: 2300 Nl/min
- Weight: 2.7kg

Maximum Temperature: +50°C

Maximum Inlet Pressure: 13 bar



BSPP

9193	Thread BSPP
4484005	1/2"
4584005	3/4"
4684005	1"

Solenoid Coil, 200 Series



Form B/Industrial, 22mm Coil

9149	Voltage
W0215000101	24V DC 2W
W0215000111	24V AC
W0215000121	110V AC
W0215000131	230V AC

M1NS2000: Socket Connector, Form B.

Solenoid Coil, 300 Series



Form B/Industrial, 30mm Coil

9182	Voltage
W0210010100	24V DC 2W
W0210011100	24V AC
W0210012100	110V AC
W0210013100	230V AC

G1NU2000: Socket Connector, Form A.

Mounting Bracket



To suit 200 & 300 Series

9154	To Suit Series
9400701	200
9400702	300

Fluid-Air Components Ltd

FRLS, 'ONE' AIR TREATMENT UNIT

'ONE' Integrated Compressed Air Treatment Unit

In the world of pneumatics, which is considered mature, it is rare to encounter completely new and different products.

ONE is a compressed air treatment unit with a high degree of integration, that encompassed numerous pneumatic functions.
In fact, it contains so many innovations that a single patent is not enough to safeguard it against imitation – three separate patent applications have been registered with a total of 39 claims.
This unit is so innovative that it won the international novelty award at Fluidtrons Compomac.


ONE has a single high-performance valve on the main row that handles all the functions from regulation to relief. It is controlled by a high-precision pilot regulator with controlled relief, in series with the manual on-off valve, the electric valve and the progressive actuator. Unification of the valve has led to a significant reduction in overall dimensions, enhanced capacity, precision and response speed.

The **ONE** single unit houses the threaded ports, filter, condensate drain, pressure regulator, shut-off valve, soft start valve, pressure switch and three supplementary air intakes.

The single unit houses the threaded ports, filter, condensate drain, pressure regulator, shut-off valve, soft start valve, pressure switch and three supplementary air intakes.



Other versions and further technical information available on request





1. Air intake, with swivel threaded port
2. Fixing hole
3. Access to filter cartridge
4. Pressure regulation
5. Shut-off Valve (manual)
6. Manual override (shut-off valve, electrical)
7. Soft start valve regulation
8. Switching pressure regulation
9. Air outlet with swivel threaded port
10. LED signalling unit, ON
11. LED signalling pressure below the value set on pressure switch
12. LED signalling pressure over the value set on pressure switch
13. 5-pin M12x1 electrical connector
14. Pressure gauge
15. 1/4" air intake; another regulated air intake and a filtered non-regulated air intake are situated on the top
16. Air exhaust with a G1/4" silencer
17. Condensate tank
18. Condensate drain
19. Clogged filter signal

BSPP

9193	Version	Air Inlet/Outlet BSPP	Micron µm	Clogged Filter Signal	Condensate Drain	Pressure Range Bar	Valves	Pressure Switch
543211881300	Electric*	1/2"	20	Yes	Automatic	0.5 to 8	Padlock and APR	Yes


Fluid-Air Components Ltd

OLYMPIAN PLUS PLUG-IN SYSTEM

NORGREN

Olympian Plus is the new generation FRL system from Norgren, world leaders in air line equipment. The unique Olympian plug-in design has been updated to set new standards for ease of use and system flexibilit .

1. **QUICK CONNECT YOKE SYSTEM**
   Simple, speedy assembly of accessories and combination units.
2. **PLUG IN UNITS**
   Rapid installation and maintenance. Quarter turn clamp ring graphite impregnated for easy operation. Detent action prevents removal under pressure.
3. **BAYONET BOWLS**
   Easy removal for routine maintenance. Detent action to prevent removal under pressure.
4. **UNIQUE PRISMATIC SIGHT GLASS**
   High visibility of liquid level. Colour change service indication on filters and filter regulators
   - Complete air processing units pre-assembled, ready to install
   - Filter-regulator and micro-fog lubricator combinations
5. **CAPTIVE O-RINGS**
   Easy to assemble with no loose parts.
6. **TAMPER RESISTANT COVER**
   Simple accessory to prevent unauthorised adjustment of regulated pressure.
7. **PORTING BLOCK MOUNTED PRESSURE SWITCH**
   Adjustable pressure switch for feedback to monitoring systems.
8. **SOFT START/DUMP VALVE**
   Provides controlled increase in pressure on system start-up. High exhaust flow capacity.
9. **3/2 SHUT OFF VALVE**
   Slide valve with lockable blade. Threaded exhaust port.
   - Filter and micro-fog lubricator combinations



Working Temperature: -20°C to +66°C

Inlet Pressure: 0-17 bar

Medium: Compressed air only
Body and Yoke: Zinc alloy
Bowl: Aluminium

Element: Sintered plastic
Elastomers: Synthetic rubber units assembled for left to right flo

Boxed Sets



BSPP

0037	Thread	Micron	Bowl	Pressure Range Bar	Operation	Drain Type
BL64-401	1/2"	40	Metal	0.3-10	Relieving	Auto
BL64-421	1/2"	40	Metal	0.3-10	Relieving	Manual
Tech Sheet 20160						

Filter & Lubricator Combinations



BSPP

0037	Thread	Micron	Bowl	Drain Type
FL64-608	3/4"	40	Metal	Auto
FL64-628	3/4"	40	Metal	Manual
Tech Sheet 20160				

Filter/Regulator & Lubricator Combinations



BSPP

0037	Thread	Micron	Bowl	Pressure Range Bar	Operation	Drain Type
BL64-408	1/2"	40	Metal	0.3-10	Relieving	Auto
BL64-428	1/2"	40	Metal	0.3-10	Relieving	Manual
BL64-608	3/4"	40	Metal	0.3-10	Relieving	Manual
Tech Sheet 20160						

Gauge



50mm, Centre Back Connection

0037	Thread	Pressure Range Bar
18-013-013	1/8"	0-10
Tech Sheet 20160		

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

OLYMPIAN PLUS PLUG-IN SYSTEM

NORGREN

General Purpose Filters


- Effective liquid removal and positive solid filtratio
- Large filter element area for minimum pressure dro
- Standard options include element service indicator, manual drain and alternative filter element

F64G Series:
Body: Zinc alloy
Bowl: Aluminium
Yoke: Zinc alloy
Filter Element: Sintered plastic
Elastomers: Synthetic rubber

F15 Series:
Body: Aluminium
Bowl: Aluminium
Yoke: Zinc alloy
Filter Element: Sintered bronze
Elastomers: Synthetic rubber
Medium: Compressed air only

Medium: Compressed air only

Working Pressure:
0-17 bar (Metal Bowl)





F64G & F68G

0037	Flow dm³/s	Micron	Bowl	Drain Type
F64G-NNN-AD3	75	40	Metal	Auto
F64G-NNN-MD3	75	40	Metal	Manual
F68G-NNN-AR3	160	40	Metal	Auto
F68G-NNN-MR3	160	40	Metal	Manual

This unit is to be used in conjunction with a Ported Yoke

Pressure Regulators

- Diaphragm and balanced valve design ensure good regulation characteristics
- Non-rising adjusting knob has snap-action lock
- Standard options include non-relieving models and alternative pressure ranges


R64G Series:
Body: Zinc alloy
Bonnet: Aluminium
Yoke: Zinc alloy
Elastomers: Synthetic rubber

R15 Series:
Body, Bonnet and Yoke: Aluminium
Adjusting Knob: Acetal resin
Optional T-bar Adjusting Screw: Steel
Elastomers: Synthetic rubber

Medium: Compressed air only
Gauge Ports: G1/8

Working Temperature:
-20°C to +80°C

Working Pressure:
0-17 bar (R64G)
0-20 bar (R68G)





R64G & R68G

0037	Thread	Flow dm³/s	Pressure Range Bar	Operation
R64G-NNK-RMN	-	120	0.3-10	Relieving
R64G-4GK-RMN	1/2"	120	0.3-10	Relieving
R68G-NNK-RLN	-	150	0.4-8	Relieving
Tech Sheet 20161				

This unit is to be used in conjunction with a ported yoke

Filter Regulators


- High efficiency water remova
- Good regulation characteristics
- Non-rising adjusting knob has snap-action lock
- Standard options include non-relieving models, manual drain and alternative pressure ranges

B64G Series:
Body: Zinc alloy
Bonnet and Bowl: Aluminium
Yoke: Zinc alloy
Filter Element: Sintered plastic
Elastomers: Synthetic rubber

B15 Series:
Body: Aluminium
Bonnet and Bowl: Aluminium
Yoke: Aluminium
Filter Element: Sintered bronze
Elastomers: Synthetic rubber
Adjusting Knob: Acetal resin

Medium: Compressed air only
Gauge Ports: G1/8
Operation: Relieving

Ambient Temperature:
-20°C to +80°C (Metal bowl)





B64G & B68G

0037	Flow dm³/s	Micron	Bowl	Pressure Range Bar	Drain Type
B64G-NNK-AD3-RMN	106	40	Metal	0.3-10	Auto
B64G-NNK-MD3-RMN	106	40	Metal	0.3-10	Manual
B68G-NNK-AR3-RLN	230	40	Metal	0.4-8	Auto
Tech Sheet 20162					

This unit is to be used in conjunction with a ported yoke

High Efficiency Oil Removal Filter



F64H & F68H

0037	Thread	Flow dm³/s	Bowl	Drain Type
F64H-3GD-MD0	3/8"	28	Metal	Auto
F64H-4GD-MD0	1/2"	28	Metal	Auto
F68H-8GD-MU0	1"	60	Metal	Auto
Tech Sheet 20163				

This unit is to be used in conjunction with a ported yoke

Lubricators



L64M & L68M

0037	Thread	Bowl
L64M-2GP-EDN	1/4"	Metal
L64M-3GP-EDN	3/8"	Metal
L64M-4GP-EDN	1/2"	Metal
L64M-6GP-EDN	3/4"	Metal
L68M-NNP-ERN	-	Metal
Tech Sheet 20164		

This unit is to be used in conjunction with a ported yoke

OLYMPIAN PLUS PLUG-IN SYSTEM

Relief & Soft Start Valves

Olympian relief valves protect compressed air systems from over-pressurisation.
High relief capacity, sensitive and accurate.
Yoke must be ordered separately.
Medium: Compressed air only
Gauge port: G1/8
Relief Port:
V64 Series - G1/2
V68 Series - G1

Materials 64 Series:
Body, bonnet: zinc alloy
Bottom Plug: Aluminium
Adjusting Screw: Steel
Elastomers: Synthetic rubber
Materials 68 Series:
Intermediate body, bonnet and bottom plug: aluminium
Adjusting Screw: Steel
Elastomers: Synthetic rubber

Working Temperature:
-20°C to +80°C



V64H, V68H Pressure Relief Valves

0037	Port Size
V64H-NND-RMN	1/4"-3/4"
V68H-NND-RMN	3/4"-1.1/2"
Tech Sheet 20165	

This unit is to be used in conjunction with a ported yoke

Assists machine designers in complying with the European Machineries Directive.
Can help existing machinery to comply with PUWER (Provision and Use of Work Equipment Regulations).
Controlled increase of downstream pressure on start up.
Solenoid, air pilot or manual operator.
High forward flow capacit .
High flow dump facilit .

Medium: Compressed air
Material:
Body and yoke:
Zinc alloy (yoke sold separately)
Intermediate Body and Top Plate:
Aluminium
Elastomers: Synthetic materials
Filter Discs: Sintered plastic
Internal Components:
Brass and steel

Working Temperature:
+5°C to +50°C



P64F Soft Start/Dump Valve

0037	Port Size	Flow dm³/s	Pressure Range Bar
P64F-NNC-PZN	1/4"-3/4"	57	3-10
Tech Sheet 20165			

This unit is to be used in conjunction with a ported yoke

Yokes

- When installed, enables Olympian basic units to be 'plugged in' or removed without disturbing connecting pipework



Single Unit

0037	Thread
Y64A-4GA-N1N	1/2"
Y68A-6GN-N1N	3/4"
Y68A-8GN-N1N	1"
Y68A-BGN-N1N	1.1/2"
Tech Sheet 20166	



Double Unit

0037	Thread
Y64A-4GA-N2N	1/2"
Y68A-6GN-N2N	3/4"
Y68A-BGN-N2N	1.1/2"
Tech Sheet 20166	

Shut Off Valves

- 3 port/2 position
- Easy to operate
- Lockable in the 'closed' position

PRODUCTS FOR SAFE SYSTEMS



BSPP

0037	Thread
T64T-4GB-P1N	1/2"
T68C-6GB-B2N	3/4"
Tech Sheet 20166	

Coalescing Exhaust Silencers



BSPP

0037	Thread
CS13-364-10GG	1/4"
CS13-664-10GG	1/2"
Tech Sheet 20166	

FAC Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

EXCELON® PLUS MODULAR AIR PREPARATION

Filters/Regulators & Lubricators - Box Sets

- Unique Quikclamp connection system offers full modularity
- 40µm particle and high efficiency water removal
- Double safety lock on bowl
- Integrated gauge
- Shut off valve, regulator and filter regulator with tamper resistance feature
- Light weight polycarbonate bowl
- Easy to read flush mounted integrated pressure gauge as standard
- All round (360°) visibility of sightdome for ease of drip rate setting
- High corrosion resistance: Body and metal bowl with electrophoretic paint finis

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar

Materials:
Body: Die cast aluminum
Body covers: ABS
Transparent Bowl: Polycarbonate with polypropylene guard
Filter element: Sintered PP
Bowl 'O'- ring: Chloroprene
Elastomers: NBR
Port: BSPP
Element: (µm) 40
Lubricator: Micro-fog®
Bowl: Guarded/Polycarbonate

Medium: Compressed air only
Operation: Relieving



Boxed sets including shut-off valve, gauge and mounting bracket

0037	Thread	Drain Model
BL82-201G	1/4"	Auto
BL82-221G	1/4"	Manual
BL84-301G	3/8"	Auto
BL84-321G	3/8"	Manual
BL84-401G	1/2"	Auto
BL84-421G	1/2"	Manual
Tech Sheet 71736		

Micro-Fog Lubricators

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- Flow sensor provides a nearly constant oil/air ratio over a wide range of flow
- Double safety lock bowl
- Light weight polycarbonate bowl
- All round (360°) visibility of sightdome for ease of drip rate setting
- Choice of two oil delivery systems
- High Corrosion resistance: Body and metal bowl with electrophoretic paint finis

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar

Materials:
Transparent Bowl: Polycarbonate with Polypropylene Guard
Body: Die cast zinc
Body cover: ABS
Sightdome: Transparent PA
Bowl 'O'- ring: Chloroprene
Elastomers: NBR

Medium: Compressed air only
Operation: Relieving



L82C, L82M & L84C, L84M series

0037	Thread	Flow (dm³/s)
L82M-2GP-EPN	1/4"	22
L84M-3GP-EPN	3/8"	73
L84M-4GP-EPN	1/2"	73
Tech Sheet 71743		

Filters/Regulators

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- 5 or 40µm particle and high efficiency water removal
- Double safety lock bowl
- Push to lock adjusting knob with built in tamper resistant feature
- Light weight polycarbonate bowl with guard
- Easy to read flush mounted integrated pressure gauge
- Air purity classes in accordance to ISO8573-1:2010: 7:8:4 (40µm), 6:8:4 (5µm)
- High Corrosion resistance: Body and metal bowl with electrophoretic paint finish
- DoC in accordance with 2014/34/EU/ATEX

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar

Materials:
Body covers: ABS
Transparent Bowl: Polycarbonate with Polypropylene Guard
Filter Element: Synthetic fibre & PE foam
Bowl 'O'- ring: Chloroprene
Elastomers: NBR
Port: BSPP
Element: (µm) 40
Flow: (dm3/s) 100

Medium: Compressed air only
Operation: Relieving



B82G & B84G series

0037	Thread	Bar
B82G-2GK-AP3-RMG	1/4"	03 to 10
B82G-2GK-QP3-RMG	1/4"	03 to 10
B84G-3GK-AP3-RMG	3/8"	03 to 10
B84G-3GK-QP3-RMG	3/8"	03 to 10
B84G-4GK-AP3-RMG	1/2"	03 to 10
B84G-4GK-QP3-RMG	1/2"	03 to 10
Tech Sheet 71734		



For **Norgren Non-return Valves** see page **864**

Fluid-Air Components Ltd

EXCELON® PLUS MODULAR SYSTEM

General Purpose Filters

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- 5 or 40µm particle and high efficiency water removal (> 98%)
- Double safety lock bowl
- Light weight polycarbonate bowl
- Air purity classes in accordance to ISO8573-1:2010: 7:8:4 (40µm), 6:8:4 (5µm)
- High Corrosion resistance: Body and metal bowl with electrophoretic paint finish
- DoC in accordance with 2014/34/EU/ATEX

Materials:
Body: Die cast aluminum
Body covers: ABS
Bonnet: Acetal Valve: PP
Transparent Bowl: Polycarbonate with polypropylene guard
Filter element: Sintered PP
Bowl 'O'- ring: Chloroprene
Elastomers: NBR

Port: BSPP
Element: (µm) 40
Bowl: Guarded/Polycarbonate

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar

Medium: Compressed air only
Operation: Relieving



F82G & F84G series

0037	Thread	Flow (dm³ /s)
F82G-2GN-AP3	1/4"	23
F82G-2GN-QP3	1/4"	23
F84G-3GN-AP3	3/8"	78
F84G-3GN-QP3	3/8"	78
F84G-4GN-AP3	1/2"	78
F84G-4GN-QP3	1/2"	78
Tech Sheet 71741		

'Puraire'® High Efficiency Oil Removal Filter

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- High efficiency oil and particle removal
- Double safety lock bowl
- Light weight polycarbonate bowl
- Service indicator standard
- Air purity class in accordance with ISO8573-1:2010: 1:7:1* *Tested in accordance with the methods laid out in ISO 12500-1 using an inlet oil aerosol concentration of 4mg/m³
- High Corrosion resistance: Body and metal bowl with electrophoretic paint finish
- DoC in accordance with 2014/34/EU/ATEX

Materials:
Body: Die cast aluminum
Body covers: ABS
Bonnet: Acetal Valve: PP
Transparent Bowl: Polycarbonate with polypropylene guard
Filter element: Synthetic fibre & PE foam
Bowl 'O'- ring: Chloroprene
Elastomers: NBR

Port: BSPP
Element: (µm) 40
Bowl: Guarded/Polycarbonate

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar

Medium: Compressed air only
Operation: Relieving



F82C & F84C series

0037	Thread	Flow (dm³ /s)
F82C-2GD-AP0	1/4"	5.5
F82C-2GD-QP0	1/4"	5.5
F84C-3GD-AP0	3/8"	25
F84C-3GD-QP0	3/8"	25
F84C-4GD-AP0	1/2"	25
F84C-4GD-QP0	1/2"	25
Tech Sheet 71739		

Pressure Regulators

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- Push to lock adjusting knob with built in tamper resistant feature
- Easy to read flush mounted integrated pressure gauge as standard
- High Corrosion resistance: Body bowl with electrophoretic paint finish
- EX DoC in accordance with 2014/34/EU/ATEX

Materials:
Body: Die cast aluminium
Body covers: ABS
Bonnet: POM/Aluminium
Valve: PP
Elastomers: NBR

Port: BSPP
Bar: 03 - 10

Medium: Compressed air only
Operation: Relieving

Working Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar



R82G & R84G Series

0037	Thread	Flow (dm3 /s)
R82G-2GK-RMG	1/4"	125
R84G-3GK-RMG	3/8"	125
R84G-4GK-RMG	1/2"	125
Tech Sheet 71745		

3/2 Shut Off Valves

- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- 3/2 way function
- Threaded exhaust port
- Lockable in closed position with padlock



T82T & T84T Series

0037	Port Size	Exhaust Port
T82T-2GA-B1N	1/4"	1/4"
T84T-3GA-B1N	3/8"	1/4"
T84T-4GA-B1N	1/2"	1/4"
Tech Sheet 71747		

EXCELON® PLUS MODULAR AIR PREPARATION

Wall Mounting Bracket

- Provides secure wall mounting for individual Excelon® Plus products



0037	Series
820024-50KIT	82
840024-50KIT	84
Tech Sheet 71736	

Quickclamp

- Allows easy connection of one Excelon® Plus unit to another
- Uniquely, connected products can be rotated in 90° increments



0037	Series
820014-51KIT	82
840014-51KIT	84
Tech Sheet 71736	



For **Norgren Pneufi ® Push-In Fittings** see page **862**

Neck Mounting Bracket and Panel Nut

- Provides secure wall mounting for individual pressure regulators, filte -regulators and pressure relief valves
- Includes panel nut



0037	Series
820068-51KIT	82
840068-51KIT	84
Tech Sheet 71736	

Quickclamps and Wall Brackets

- Allows easy connection of one Excelon® Plus unit to another
- Uniquely, connected products can be rotated in 90° increments
- Secure mounting to a wall, panel or machine surface



0037	Series
820014-52KIT	82
840014-52KIT	84
Tech Sheet 71736	

Panel Mounting Ring

- Allows bonnets with panel mounting thread to be directly mounted



0037	Series
820048-89KIT	82
840048-01KIT	84
Tech Sheet 71736	

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PORTED FILTERS & REGULATORS

NORGREN


Filter Regulator & Lubricator Box Set

- Miniature boxed sets offer rapid set up and installation.
- Boxed sets are pre-assembled and ready to install.
- Set consists of a filter/regulato , lubricator, shut-off valve, mounting bracket and pressure gauge.

Medium: Compressed air only
Body: Zinc alloy
Bowls: Polycarbonate
Filter Element: Polypropylene
Elastomers: Nitrile

Working Temperature:
-20°C to +50°C
Consult our Technical Service for use below +2°C

Inlet Pressure:
0 to 10 bar





Box Set 07, BSPP

0037	Thread
BL07-201	1/4"
Tech Sheet 20746	

Ported Pureaire Oil Removal Filters


- High efficiency coalescing oil-removal filter
- Air quality to ISO 8573-1: Class 1.7.2.
- Maximum remaining oil content 0,01 ppm, particle removal to 0,01 µm
- Automatic drain fitted as standar

Medium: Compressed air only
Remaining Oil content at +21°C:
0,01 ppm maximum
0,5 ppm maximum (high flow units
Particle Removal: 0,01 µm, 1 µm (high flow units
Bowl: Polycarbonate to BS 6005, Zinc alloy (optional)

Body: Zinc alloy
Filter Element:
Synthetic fibre and polypropylene foa
Elastomers: Neoprene and nitrile

Working Temperature:
-20°C to +50°C
(Transparent Bowl)

Inlet Pressure:
0 to 10 bar (Transparent bowl)






F39, BSPP

0037	Thread	Flow dm³/s	Drain Type	Bowl
F39-100-A0TG	1/8"	2.8	Auto	Transparent
F39-200-M0MG	1/4"	3	Manual	Metal
F39-200-M0TG	1/4"	3	Manual	Transparent
Tech Sheet 20747				

Ported Pressure Regulators






R07, BSPP

0037	Thread	Flow dm³/s	Pressure Range Bar	Operation
R07-100-RNKG	1/8"	7.5	0.3-7	Relieving
R07-200-RNKG	1/4"	7	0.3-7	Relieving
Tech Sheet 10637				



R18, Pilot Operated, BSPP

0037	Thread	Flow dm³/s	Pressure Range Bar
R18-B00-RNXD	1.1/2"	1000	0.16-17
R18-C00-RNXD	2"	1000	0.16-17
Tech Sheet 10636			





11-808 & 11-204, Pilot Operated, BSPP

0037	Thread	Flow dm³/s	Pressure Range Bar	Operation
11-808-960	3/4"	180	0.16-17	Relieving
11-204-004	1/4"	N/A	0.16-17	Relieving
11-204-006	1/4"	N/A	4-17	Relieving
Tech Sheet 10636				



General Use, BSPP

0037	Thread	Flow dm³/s	Pressure Range Bar
20AG-X4G-PH100	1/2"	60	0.2-8
20AG-X4G-PJ100	1/2"	60	7-16
Tech Sheet 10637			

Fluid-Air Components Ltd

PORTED FILTERS & REGULATORS

NORGREN

Drip Leg Drain




17-816, BSPP

0037	Thread	Bowl
17-816-999	G1/2"	Transparent
17-816-998	G1/2"	Metal
Tech Sheet 10635		

Ported Lubricator

- Transparent bowl
- Bowl capacity 31ml






L07, BSPP

0037	Thread	Flow dm^3/s	Start Point dm^3/s
L07-100-MPQG	G1/8"	5	0.24
Tech Sheet 10634			

Ported Pressure Relief Valve





V07, Diaphragm Type, BSPP

0037	Thread	Pressure Range Bar
V07-200-NNLG	G1/4"	0.3-9
Tech Sheet 10633		

Ported Precision Pressure Regulators

- 11-818† compact, high precision regulators for air gauging, laboratory use and precise pilot control.

† Not recommended for dead end use, consult our technical service for details.

Working Temperature:
-20°C to +80°C
Consult our Technical Service for use below +2°C

Inlet Pressure:
0 to 14 bar (11-818-110)
0 to 8 bar (11-818-999)



11-818, BSPP

0037	Thread	Accuracy Bar	Pressure Range Bar	Operation
11-818-999	G1/4"	0.01	0.02-0.5	Relieving
11-818-100	G1/4"	0.03	0.07-4	Relieving
11-818-110	G1/4"	0.05	0.4-10	Relieving
Tech Sheet 1362				

General Purpose Filter

- High flow miniature uni
- Direct ported filters with high water removal efficien
- Automatic drains supplied as standard

Medium: Compressed air only
Filter element: 40µm

Materials:
Body: Zinc alloy
Bowls: Plastic or zinc alloy
Filter Element: Polypropylene
Elastomers: Nitrile

Working Temperature:
-34°C to +50°C


Inlet Pressure:
0 to 10 bar



F07 Series

0037	Manual Drain	Thread
F07-100-A3TG	F07-100-M3TG	G1/8"
F07-200-A3TG	F07-200-M3TG	G1/4"
Tech Sheet 71738		

Pressure Gauges





18-013, BSPT

0037	Thread	Pressure Range Bar	Gauge Diameter mm	Type
18-013-990	R1/8"	0-4	40	Centre Back
18-013-989	R1/8"	0-10	40	Centre Back

Pre-Set Regulator

- Factory pre-set and sealed to give a regulated pressure of 2 bar
- Tamper resistant
- Compact

Medium: Compressed air only
Filter element: 40µm

Materials:
Body: Zinc alloy
Bonnet: Aluminium alloy
Valve: Brass
Seals: NBR

Working Temperature:
-20°C to +80°C

Inlet Pressure:
0 to 28 bar



R16 Series

0037	Thread
R16-200-R30G	G1/4"
Tech Sheet 71750	

AIR PREPARATION

MX is the new series of air treatment components, characterised by a modern, linear and compact design. The perfect integration between metal alloys and technopolymers allows a reliable product that is light and strong at the same time.

Series MX offers a multi-sector solution that guarantees saving in terms of installation time, space and cost.

Other options available, please contact our Business Development Team.



Series MX, Filter Regulator Lubricator Kits

Complete filter regulator set with bracket and integrated gauge.

- Fully modular and compact
- Lightweight
- Durable
- Improved flow rate performance
- Locking cap



Filter Regulator Kit MX2, Semi-auto Drain, 25 Micron, 0.5-10 bar

0158	Thread
FR-MX2-3/8-KIT	G3/8"
FR-MX2-1/2-KIT	G1/2"
FR-MX2-3/4-KIT	G3/4"
Tech Sheet 20120	

Filter Regulator Kit MX3, Semi-auto Drain, 25 Micron, 0.5-10 bar

0158	Thread
FR-MX3-3/4-KIT	G3/4"
FR-MX3-1-KIT	G1"
Tech Sheet 20120	

Filter Regulator Lubricator Kit MX2, Semi-auto Drain, 25 Micron, 0.5-10 bar

0158	Thread
FRL-MX2-3/8-KIT	G3/8"
FRL-MX2-1/2-KIT	G1/2"
FRL-MX2-3/4-KIT	G3/4"
Tech Sheet 20120	

Filter Regulator Lubricator Kit MX3, Semi-auto Drain, 25 Micron, 0.5-10 bar

0158	Thread
FRL-MX3-3/4-KIT	G3/4"
FRL-MX3-1-KIT	G1"
Tech Sheet 20120	

Series MX, Modular Pressure Regulators

Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar



Series MX2, Pressure Regulators, Self-relieving with Gauge

0158	Thread	Pressure Range Bar
MX2-3/8-R004	G3/8"	0.5-10
MX2-1/2-R004	G1/2"	0.5-10
MX2-3/4-R004	G3/4"	0.5-10
Tech Sheet 68728		

Series MX3, Pressure Regulators, Self-relieving with Gauge

0158	Thread	Pressure Range Bar
MX3-3/4-R004	G3/4"	0.5-10
MX3-1-R004	G1"	0.5-10
Tech Sheet 68728		

Series MX2, Pressure Regulators, Non-relieving with Gauge

0158	Thread	Pressure Range Bar
MX2-3/8-R014	G3/8"	0.5-10
MX2-1/2-R014	G1/2"	0.5-10
MX2-3/4-R014	G1"	0.5-10
Tech Sheet 68728		

Series MX3, Pressure Regulators, Non-relieving with Gauge

0158	Thread	Pressure Range Bar
MX3-3/4-R014	G3/4"	0.5-10
MX3-1-R014	G1"	0.5-10
Tech Sheet 68728		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

MX is the new series of air treatment components, characterised by a modern, linear and compact design. The perfect integration between metal alloys and technopolymers allows a reliable product that is light and strong at the same time.

Series MX offers a multi-sector solution that guarantees saving in terms of installation time, space and cost.

Other options available, please contact our Business Development Team.



Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MX, Modular Filters





Series MX2, Semi-auto Drain Filters, No Indicator

0158	Thread	Micron
MX2-3/8-F00	G3/8"	25
MX2-1/2-F00	G1/2"	25
MX2-3/4-F00	G3/4"	25
Tech Sheet 68728		

Series MX2, Semi-auto Drain Coalescing Filters

0158	Thread	Micron
MX2-3/8-FC00	G3/8"	0.01
MX2-1/2-FC00	G1/2"	0.01
MX2-3/4-FC00	G3/4"	0.01
Tech Sheet 68728		

Series MX3, Semi-auto Drain Filters, No Indicator

0158	Thread	Micron
MX3-3/4-F00	G3/4"	25
MX3-1-F00	G1"	25
Tech Sheet 68728		

Series MX3, Semi-auto Drain Coalescing Filters

0158	Thread	Micron
MX3-3/4-FC00	G3/4"	0.01
MX3-1-FC00	G1"	0.01
Tech Sheet 68728		

Series MX2, Auto Drain Filters, No Indicator

0158	Thread	Micron
MX2-3/8-F03	G3/8"	25
MX2-1/2-F03	G1/2"	25
MX2-3/4-F03	G3/4"	25
Tech Sheet 68728		

Series MX2, Auto Drain Coalescing Filters

0158	Thread	Micron
MX2-3/8-FC03	G3/8"	0.01
MX2-1/2-FC03	G1/2"	0.01
MX2-3/4-FC03	G3/4"	0.01
Tech Sheet 68728		

Series MX3, Auto Drain Filters, No Indicator

0158	Thread	Micron
MX3-3/4-F03	G3/4"	25
MX3-1-F03	G1"	25
Tech Sheet 68728		

Series MX3, Auto Drain Coalescing Filters

0158	Thread	Micron
MX3-3/4-FC03	G3/4"	0.01
MX3-1-FC03	G1"	0.01
Tech Sheet 68728		

Fluid-Air Components Ltd

AIR PREPARATION

MX is the new series of air treatment components, characterised by a modern, linear and compact design. The perfect integration between metal alloys and technopolymers allows a reliable product that is light and strong at the same time.

Series MX offers a multi-sector solution that guarantees saving in terms of installation time, space and cost.

Other options available, please contact our Business Development Team.



Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MX, Modular Filters



Series MX2, Activated Carbon Filters, No Indicator

0158	Thread
MX2-3/8-FCA	G3/8"
MX2-1/2-FCA	G1/2"
MX2-3/4-FCA	G3/4"
Tech Sheet 68728	

Series MX3, Activated Carbon Filters, No Indicator

0158	Thread
MX3-3/4-FCA	G3/4"
MX3-1-FCA	G1"
Tech Sheet 68728	

Series MX, Modular Lubricators



Series MX2, Lockable Manual Valves

0158	Thread
MX2-3/8-V01	G3/8"
MX2-1/2-V01	G1/2"
MX2-3/4-V01	G1"
Tech Sheet 68728	

Series MX3, Lockable Manual Valves

0158	Thread
MX3-3/4-V01	G3/4"
MX3-1-V01	G1"
Tech Sheet 68728	

Series MX, Modular Valves



Series MX2, Lubricators

0158	Thread
MX2-3/8-L00	G3/8"
MX2-1/2-L00	G1/2"
MX2-3/4-L00	G3/4"
Tech Sheet 68728	

Series MX3, Lubricators

0158	Thread
MX3-3/4-L00	G3/4"
MX3-1-L00	G1"
Tech Sheet 68728	



Series MX2, 3/2 Lockable Electro-pneumatic Isolation Valves

0158	Thread
MX2-3/8-V16	G3/8"
MX2-1/2-V16	G1/2"
MX2-3/4-V16	G3/4"
Tech Sheet 68728	

Series MX3, 3/2 Lockable Electro-pneumatic Isolation Valves

0158	Thread
MX3-3/4-V16	G3/4"
MX3-1-V16	G1"
Tech Sheet 68728	

Fluid-Air Components Ltd

AIR PREPARATION

MX is the new series of air treatment components, characterised by a modern, linear and compact design. The perfect integration between metal alloys and technopolymers allows a reliable product that is light and strong at the same time.

Series MX offers a multi-sector solution that guarantees saving in terms of installation time, space and cost.

Other options available, please contact our Business Development Team.



Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MX, Modular Valves

Series MX2, 3/2 Lockable Pneumatic Isolation Valves

0158	Thread
MX2-3/8-V36	G3/8"
MX2-1/2-V36	G1/2"
MX2-3/4-V36	G3/4"
Tech Sheet 68728	

Series MX3, 3/2 Lockable Pneumatic Isolation Valves

0158	Thread
MX3-3/4-V36	G3/4"
MX3-1-V36	G1"
Tech Sheet 68728	



Series MX2, Soft Start Valves

0158	Thread
MX2-3/8-AV	G3/8"
MX2-1/2-AV	G1/2"
MX2-3/4-AV	G3/4"
Tech Sheet 68728	

Series MX3, Soft Start Valves

0158	Thread
MX3-3/4-AV	G3/4"
MX3-1-AV	G1"
Tech Sheet 68728	



Series MX, Modular Take-off Blocks




Series MX2, Block, 4 Outlets, BSPP

0158	Outlet
MX2-1/2-B00	G1/2"
Tech Sheet 68728	

Series MX3, Block, 4 Outlets, BSPP

0158	Outlet
MX3-1-B00	G1"
Tech Sheet 68728	

Series MX, Accessories



Series MX2, Terminal Flanges

0158	Thread
MX2-3/8-FL	G3/8"
MX2-1/2-FL	G1/2"
MX2-3/4-FL	G3/4"
Tech Sheet 68728	

Series MX3, Terminal Flanges

0158	Thread
MX3-3/4-FL	G3/4"
MX3-1-FL	G1"
Tech Sheet 68728	



Series MX2, Fixing Bracket for Regulators

0158
MX2-S
Tech Sheet 68728

Series MX3, Fixing Bracket for Regulators

0158
MX3-S
Tech Sheet 68728

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

MX is the new series of air treatment components, characterised by a modern, linear and compact design. The perfect integration between metal alloys and technopolymers allows a reliable product that is light and strong at the same time.

Series MX offers a multi-sector solution that guarantees saving in terms of installation time, space and cost.

Other options available, please contact our Business Development Team.



Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MX, Accessories

Series MX2, Rapid Clamp

0158
MX2-X
Tech Sheet 68728

Series MX3, Rapid Clamp

0158
MX3-X
Tech Sheet 68728



Series MX2, Rapid Clamp with Wall Bracket

0158
MX2-Y
Tech Sheet 68728

Series MX3, Rapid Clamp with Wall Bracket

0158
MX3-Y
Tech Sheet 68728



Precision Regulators

Series PR precision pressure regulators work on a three diaphragm force-balance principle which allows them to react even to the smallest changes in pressure that can occur during operation.

- High precision
- Triple diaphragm construction
- Compact dimensions
- Adjustable lock
- Removable adjustment knob
- Three ranges of pressure

Working Temperature:
0°C to +50°C



Series PR, Manual Override

0158	Thread	Pressure Range Bar
PR104-M02	G1/4"	0.05 to 2
PR104-M04	G1/4"	0.05 to 4
PR104-M07	G1/4"	0.05 to 7
Tech Sheet 20464		

Digital Gauges

Series PG digital pressure gauges meet the needs of an even more precise pressure adjustment, above all in proportional control.

Thanks to the IP65 protection class these pressure gauges are particularly suitable for applications where the highest environmental protection is required.



Pressure, BSPP

0158	Thread	Pressure Range Bar
PG010-PB-1/8	G1/8"	0 to 10
PG010-PB-1/4	G1/4"	0 to 10
Tech Sheet 20465		

Vacuum, BSPP

0158	Thread	Pressure Range Bar
PG001-VB-1/8	G1/8"	0.01 to -1
PG001-VB-1/4	G1/4"	0.01 to -1
Tech Sheet 20465		

Fluid-Air Components Ltd

AIR PREPARATION

Series MD air preparation product line has been designed to meet the numerous demands of a market requiring light and compact modular products which are characterised by high performance, flexible connection and orientation.

The different functions are connected to each other by means of intermediate joining cartridges.

Thanks to the solution adopted for the pneumatic connection, it is possible to equip the same element with interchangeable cartridges that are available in different sizes and can either be threaded or integrated with a super rapid push-in fitting.



Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MD, Modular Filter + Regulator + Lubricator Combination Units



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, BSPP

0158	Thread
MD1-000014-1/8	G1/8"
MD1-000014-1/4	G1/4"
MD1-000014-3/8	G3/8"
Tech Sheet 60158	



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, Tube

0158	OD mm
MD1-000014-6	6
MD1-000014-8	8
MD1-000014-10	10
Tech Sheet 60159	

Series MD, Modular Filter/ Regulator + Lubricator Combination Units



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, BSPP

0158	Thread
MD1-000015-1/8	G1/8"
MD1-000015-1/4	G1/4"
MD1-000015-3/8	G3/8"
Tech Sheet 60160	



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, Tube

0158	OD mm
MD1-000015-6	6
MD1-000015-8	8
MD1-000015-10	10
Tech Sheet 60161	

Series MD, Modular Lockable Isolation Filter/Regulator + Lubricator Combination Units



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, BSPP

0158	Thread
MD1-000016-1/8	G1/8"
MD1-000016-1/4	G1/4"
MD1-000016-3/8	G3/8"
Tech Sheet 60162	



Semi-auto Drain, 25 Micron, supplied with Mounting Bracket & Gauge, Tube

0158	OD mm
MD1-000016-6	6
MD1-000016-8	8
MD1-000016-10	10
Tech Sheet 60163	

Fluid-Air Components Ltd

AIR PREPARATION

Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar

Series MD, Modular Pressure Regulators



Pressure Regulators, Self-relieving

0158	Pressure Range Bar
MD1-R000	0.5-10
MD1-R200	0-2
MD1-R400	0-4
MD1-R700	0.5-7
Tech Sheet 60168	



Pressure Regulators, Non-relieving

0158	Pressure Range Bar
MD1-R010	0.5-10
MD1-R210	0-2
MD1-R410	0-4
MD1-R710	0.5-7
Tech Sheet 60168	

Series MD, Modular Filter Regulators



0.5-10 bar, 25 Micron

0158	Description
MD1-FR0000	Semi-auto Drain
MD1-FR0500	Auto Drain
MD1-FR0800	Without Drain
Tech Sheet 60170	

Series MD modular products are listed with blank ports. This enables versatility with the product and can be fitted with either threaded or tube fitting cartridges.



Series MD, Modular Filters



Semi-auto Drain

0158	Description	Micron
MD1-F000	No Indicator	25
MD1-F100	No Indicator	5
MD1-F001	With Indicator	25
MD1-F101	With Indicator	5
Tech Sheet 60164		



Auto Drain Filters

0158	Description	Micron
MD1-F050	No Indicator	25
MD1-F150	No Indicator	5
MD1-F051	With Indicator	25
MD1-F151	With Indicator	5
Tech Sheet 60165		



Activated Carbon Filters

0158	Description
MD1-FCA0	No Indicator
MD1-FCA1	With Indicator
Tech Sheet 60166	



Semi-auto Drain Coalescing Filters

0158	Description	Micron
MD1-FC000	No Indicator	0.01
MD1-FC100	No Indicator	1
MD1-FC001	With Indicator	0.01
MD1-FC101	With Indicator	1
Tech Sheet 60167		



Auto Drain Coalescing Filters

0158	Description	Micron
MD1-FC050	No Indicator	0.01
MD1-FC150	No Indicator	1
MD1-FC051	With Indicator	0.01
MD1-FC151	With Indicator	1
Tech Sheet 60167		

Fluid-Air Components Ltd

AIR PREPARATION

Series MD, Modular Lubricator

Working Temperature:
-5°C to +50°C

Maximum Working Pressure:
16 bar



Lubricator

0158
MD1-L00
Tech Sheet 60169

Series MD, Modular Valves



3/2 Lockable Isolation Valves

0158	Description
MD1-V36	Pneumatic Control
MD1-V01	Lockable Manual Control
Tech Sheet 60171	



Soft Start Valve

0158
MD1-AV
Tech Sheet 60172

Series MD modular products are listed with blank ports. This enables versatility with the product and can be fitted with either threaded or tube fitting cartridges.



Series MD, Modular Take-off Blocks



Block, 4 Outlets, BSPP

0158	Outlet
MD1-B00	1/8"
Tech Sheet 60173	



Cartridge, 2 Outlets, BSPP

0158	Outlet
MD1-B	1/8"
Tech Sheet 60174	

Series MD, Porting Cartridges

Porting cartridges can be used on all Series MD module equipment, offering versatility.



Joining Cartridge

0158
MD1-C
Tech Sheet 60175



Threaded, BSPP

0158	Thread
MD1-A-1/8	1/8"
MD1-A-1/4	1/4"
MD1-A-3/8	3/8"
Tech Sheet 60175	



Push Fit

0158	OD mm
MD1-A-6	6
MD1-A-8	8
MD1-A-10	10
Tech Sheet 60175	

Series MD, Mounting Bracket

Other mounting types available.



Rear Mounting Bracket

0158
MD1-ST/1
Tech Sheet 60176

Fluid-Air Components Ltd

AIR PREPARATION EQUIPMENT

Filter Regulator + Lubricator

Parker's P3L Lite combination kit is a configure two-piece unit consisting of a filter regulator and mist-style lubricator.
The P3L combination kit provides accurate pressure regulation, high moisture removal efficienc , and proportional oil delivery over a wide range of air flows



Working Temperature: 0°C to +50°C

Maximum Working Pressure: 10 bar

P3L Lite FRL Combination Kit

0677	Thread	Drain Type
P3LCA12PESNGLNW	1/4"	Semi-auto
Tech Sheet 68749		

Filter Regulator



P3L Lite Particulate Filter Regulator

0677	Thread	Drain Type
P3LEA12EPSBNNP	1/4"	Semi-auto
Tech Sheet 68749		

Regulator

Parker's P3LR is a lightweight pressure regulator with an unbalanced poppet design, offering good response and accurate pressure regulation. For low flow an space-restricted applications, this product can provide a solution that does not sacrifice performance. The P3LR can also be mounted using a modular connector, limited to two other P3L air preparation product units. The various options available, such as pressure gauge, relieving and non-relieving, pressure range, preset pressures and tamper-proof options, make this series easy to design to your application.
Flow rates up to 12.8dm³/s.



P3L Lite Regulator

0677	Thread	Material
P3LRA12BNNP	1/4"	Polymer
P3LRX12BNNP	1/4"	Brass
Tech Sheet 68748		

Filter

Parker's P3LF is a lightweight particulate filter tha delivers high moisture removal in a compact package. The P3LF is used for the removal of solid particle contaminants down to 5 micron and the separation of bulk liquids.
This type of filter is generally used in industrial applications where liquid water, oil, and harmful dirt particles must be removed from the compressed air system.
For specific flow and space restricte applications, this product can provide a solution that does not sacrifice performance



Maximum Working Pressure: 150 bar

P3L Lite Particulate Filter

0677	Thread	Drain Type
P3LFA12EPSN	1/4"	Pulse
Tech Sheet 68750		

Coalescing Filter

Parker's P3LF, a lightweight coalescing filte , is designed to remove liquid aerosols, water, oil and sub-micron particulate matter from your pneumatic system. These filters will provide oil-free air for severa demanding applications.
The P3LF is specifically designed fo the removal of solid particles, water and oil aerosols down to 0.01 micron.



P3L Lite Coalescing Filter

0677	Thread	Drain Type
P3LFA12CPPN	1/4"	Manual
Tech Sheet 68751		

Adsorber Filter



P3L Lite Adsorber Filter

0677	Thread	Drain Type
P3LFA12APPN	1/4"	Manual
Tech Sheet 68752		

Lubricator

The P3LL is a lightweight lubricator that injects a mist of oil into the flowing air stream to automatically provide the correct amount of internal lubrication for air tools and other pneumatic devices.
This type of lubricator can be precisely adjusted to avery low oil flow rate because only a portion of the oil drops seen in the sight dome travels downstream. Proportional oil is delivered over a wide range of air flows and a precision needle valve assures repeatable oil delivery. A slight adjustment can provide a desired mist rate.
This unit is ideal for low and high flow applications that demand uniform lubrication in a robust package. ISO/ASTM VG32 oil is suggested for lubrication and will allow the product to perform at peak performance. Do not use oils with additives, compounded oils containing solvents, graphite, detergents or synthetic oils.



P3L Lite Lubricator

0677	Thread
P3LLA12LPNN	1/4"
Tech Sheet 68753	

Accessories

P3L Lite Accessories

0677	Description
P3LKA00MR	Neck Mounting Bracket
P3LKA00MW	Mounting Bracket for P3LFA or P3LLA
P3LKA00MP	Plastic Panel Mount Nut
P3LKA00MM	Aluminium Panel Mount Nut
P3LMA12020C	Manifold Block
P3LKA00CB1	Connector Kit, FR or R to F or L
P3LKA00CB2	Connector Kit, FR or R to M to F or L
P3LKA00CB3	Connector Kit, FR or R to F to F
P3LKA00CB4	Connector Kit, F to F or L

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

PNEUMAX

Airplus Service Units



Size 1 FRL Air Service Units, BSPP

0110	Thread	Range
GT171BHH	1/4"	0-12



Size 3 FRL Air Service Units, BSPP

0110	Thread	Drain
GT173BHH	1/2"	Semi
GT173BHHS	1/2"	Auto



Size 2 FRL Air Service Units, BSPP

0110	Thread	Drain
GN172AHHS	1/4"	Semi
GT172BHH	3/8"	Semi
GT172BHHS	3/8"	Auto



Size 4 FRL Air Service Units, BSPP

0110	Thread	Drain
GN174BHHS	1"	Auto

Airplus Filter/Regulators



Size 1 Filter/Regulator, BSPP

0110	Thread	Pressure Range Bar
N171AEBD	1/8"	0-12
T171BEBD	1/4"	0-12

Size 2 Filter/Regulator

0110	Thread	Pressure Range Bar
T172BEBD	3/8"	0-12

Size 3 Filter/Regulator

0110	Thread	Pressure Range Bar
T173BEBD	1/2"	0-12



Size 4 Filter/Regulator

0110	Thread	Pressure Range Bar
N174BEBD	1"	0-12

Airplus Filter/Regulators Complete with Pressure Gauge



Size 1 Filter/Regulator

0110	Thread	Pressure Range Bar
N171AEMBD	1/8"	0-12
T171BEMBD	1/4"	0-12

Size 2 Filter/Regulator

0110	Thread	Pressure Range Bar
T172BEMBB	3/8"	0-4
T172BEMBD	3/8"	0-12

Size 3 Filter/Regulator

0110	Thread	Pressure Range Bar
T173BEMBD	1/2"	0-12



Size 4 Filter Regulator

0110	Thread	Pressure Range Bar
N174BEMBD	1"	0-12

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR PREPARATION

PNEUMAX

Airplus Filter/Regulators Complete with Pressure Switch



Size 1 Filter/Regulator

0110	Thread	Pressure Range Bar
N171AEPBDA	1/8"	0-12

Size 2 Filter/Regulator

0110	Thread	Pressure Range Bar
T172BEPBDA	3/8"	0-12

Size 3 Filter/Regulator

0110	Thread	Pressure Range Bar
T173BEPBDA	1/2"	0-12



Size 4 Filter/Regulator

0110	Thread	Pressure Range Bar
N174BEPBDA	1"	0-12

Accessories



Pressure Switch Connecting Cables

0110	Description
MCH1	M8 Cable 3 Wires, 2.5 Metres

Airplus Regulators Complete with Pressure Gauge



Size 1 Regulator, BSPP

0110	Thread	Pressure Range Bar
T171BRMA	1/4"	0-2
T171BRMB	1/4"	0-4
T171BRMC	1/4"	0-8
T171BRMD	1/4"	0-12

Size 2 Regulator, BSPP

0110	Thread	Pressure Range Bar
T172BRMA	3/8"	0-2
T172BRMB	3/8"	0-4
T172BRMC	3/8"	0-8
T172BRMD	3/8"	0-12

Size 3 Regulator, BSPP

0110	Thread	Pressure Range Bar
T173BRMA	1/2"	0-2
T173BRMC	1/2"	0-8
T173BRMD	1/2"	0-12



Size 4 Regulator, BSPP

0110	Thread	Pressure Range Bar
N174BRMA	1"	0-2
N174BRMD	1"	0-12

Airplus Lubricators



Size 1 Lubricator, BSPP

0110	Thread
T171BL	1/4"



Size 2 Lubricator, BSPP

0110	Thread
T172BL	3/8"



Size 3 Lubricator, BSPP

0110	Thread
T173BL	1/2"



Size 4 Lubricator, BSPP

0110	Thread
N174BL	1"

AIR PREPARATION

PNEUMAX

Airplus Filters



Size 1 Filter, BSPP

0110	Thread
T171BFB	1/4"



Size 2 Filter, BSPP

0110	Thread
T172BFB	3/8"

Size 3 Filter, BSPP

0110	Thread
T173BFB	1/2"

Airplus Valves



Manual Shut-off Valves, BSPP

0110	Thread	Size
T171BVL	1/4"	1
T172BVL	3/8"	2
T173BVL	1/2"	3

High/Low Pressure Devices



High/Low Solenoid Pressure Device - 1/8"

0110	Description
900.18.8E	Solenoid Hi-Lo Pressure Device

Airplus Valves



Electric Sol Shut Off Valves, BSPP

0110	Thread	Size
T171BVEB2	1/4"	1
T172BVEB2	3/8"	2
T173BVEB2	1/2"	3



Soft Start Valves, BSPP

0110	Thread	Size
T172BAP	3/8"	2



Manifolds, BSPP

0110	Thread	Size
T171BPA	1/4"	1



Pressure Switches, BSPP

0110	Thread	Size
T171BPP	1/4"	1

Airplus Accessories



Airplus X Coupling Flange Size 1-4

0110	Size
T171X	1
T172X	2



Airplus Y Coupling Flange Range Size 1-4

0110	Size
T171Y	1
T173Y	3



Airplus Fixing Bracket Size 1-3

0110	Size
T17150	1
T17250	2 & 3



MB Type 22mm Coils

0110	Voltage
MB4	12V DC
MB5	24V DC
MB9	24V DC (2 watt)
MB56	24V AC
MB57	110V AC
MB58	220V DC



305 22mm Coil Caps

0110	Voltage
305.11.00	No LED
305.11.01L	24V DC LED
305.11.02L	110V AC LED
305.11.03L	240V AC LED

Fluid-Air Components Ltd

AIR SERVICE UNITS

Filter/Regulator + Lubricator

PCL's FRL range includes combination units with 1/4" and 1/2" inlet ports. Adding a PCL Air Treatment unit into an air line efficiently filters to 10 microns. Products featur polycarbonate bowls, allowing the user to easily monitor the element's condition and the collected liquid's level. The bowl is surrounded with protective metal as a safety measure to protect the user in case of excessive pressures, temperatures, or aggressive chemicals.

Features

- Selectable manual/semi-automatic drain
- Polycarbonate bowl
- Locking device
- 10 micron filte
- Complete with wall bracket and pressure gauge



Regulators

7000	Port Thread (BSPP)	Regulating Pressure	Max Inlet (bar)	Flow @ 6 (bar)
ATR6	1/4"	0-10	12	1,700 l/min
ATR12	1/2"	0-12	16	6,000 l/min



Filters

7000	Drain	Port Thread (BSPP)	Filtration Micron	Max Inlet (bar)	Flow@ 6 (bar)
ATF6	Manual/Semi-automatic	1/4"	10	12	2,100 l/min
ATF12	Manual/Semi-automatic	1/2"	10	16	6,000 l/min



Lubricators

7000	Port Thread (BSPP)	Max Inlet (bar)	Flow @ 6 (bar)
ATL6	1/4"	12	2,200 l/min
ATL12	1/2"	16	6,000 l/min



Filter/Regulator, BSPP

7000	Thread (BSPP)	Max Inlet (bar)	Flow @ 6 (bar)
ATC6	1/4"	12	1,800 l/min
ATC12	1/2"	16	5,000 l/min
	Tech Sheet 60545		



Filter/Regulator + Lubricator, BSPP

7000	Thread (BSPP)	Max Inlet (bar)	Flow @ 6 (bar)
ATCFRL6	1/4"	12	1,800 l/min
ATCFRL12	1/2"	16	5,000 l/min
	Tech Sheet 60545		

Fluid-Air Components Ltd

MINIATURE, HIGH PRECISION REGULATORS

Universal Pressure Control Valves



Relieving, BSPP

0113	Thread	Pressure Range Bar
48.250.00.10.00	1/8"	0-1
48.250.00.50.00	1/8"	0-5
Tech Sheet 172		

Non Relieving, BSPP

0113	Thread	Pressure Range Bar
48.250.00.10.10	1/8"	0-1
48.250.00.50.10	1/8"	0-5
Tech Sheet 172		

Panel Mount Pressure Regulators



Relieving, BSPP

0113	Thread	Pressure Range Bar
50.780.00.10.00	1/8"	0-1
50.780.00.25.00	1/8"	0-2.5
50.780.00.80.00	1/8"	0-8
Tech Sheet 173		

Non Relieving, BSPP

0113	Thread	Pressure Range Bar
50.780.00.10.10	1/8"	0-1
Tech Sheet 173		

Miniature Pressure Regulators

- Panel mountable



Relieving, Metric

0113	Thread	Pressure Range Bar
50.880.00.40.00	M5	0-4
Tech Sheet 174		

REGULATORS

SaveAir Regulator



1/4" BSPP

0093	Set Pressure Bar
231A0210	1
231A0220	2
231A0230	3
231A0240	4
231A0250	5
231A0260	6
231A0270	7
231A0280	8
Tech Sheet 1347	

ToolReg

Male/Female





Female/Female

1/4" BSPP

0093	Inlet	Outlet	Set Pressure Bar
232A0220	Female	Female	2
232F0220	Male	Female	2
232A0230	Female	Female	3
232F0230	Male	Female	3
232A0240	Female	Female	4
232F0240	Male	Female	4
232A0260	Female	Female	6
232F0260	Male	Female	6
232A0270	Female	Female	7
232A0280	Female	Female	8
232F0280	Male	Female	8
Tech Sheet 1349			

3/8" BSPP

0093	Inlet	Outlet	Set Pressure Bar
232A0340	Female	Female	4
232A0360	Female	Female	6
232A0380	Female	Female	8
Tech Sheet 1349			

PRESSURE BOOSTERS


Air Pressure Booster


The air-to-air pressure multiplier, or booster, is an automatic device that compresses air to give an outlet pressure that is double the inlet pressure. It is normally used to locally intensify the input pressure of one or more actuators. As it is entirely pneumatic it can be used when electric devices are not recommended. The booster can be supplied with or without a pressure regulator.

It is fitted with check valves that maintain the outlet pressure even when the supply of compressed air is switched off. This means it is necessary to interrupt the supply and relieve the circuit before intervening on the device in any way. It is advisable to install a tank after the booster to prevent fluctuations in outlet pressure.

Technical Data

		Booster Ø40	Booster Ø40 with regulator	Booster Ø63	Booster Ø63 with regulator
Bore		Ø 40		Ø 63	
Fluid		Filtered unlubricated compressed air. Lubrication, if used, must be continuous.			
Threaded port		G1/8		G3/8	
Inlet pressure	**MPa**	0.2-1			
	bar	2-10			
	psi	29-145			
Outlet pressure	**MPa**	Maximum 2	Maximum 1.6 (regulated)	Maximum 2	Maximum 1.6 (regulated)
	bar	Maximum 20	Maximum 16 (regulated)	Maximum 20	Maximum 16 (regulated)
	psi	Maximum 290	Maximum 232 (regulated)	Maximum 290	Maximum 232 (regulated)
Operating temperature	**ºC**	-10º to +60º	-10º to +50º	-10º to +60º	
	ºF	+14º to +140º	+14º to +122º	+14º to +140º	
Weight	**gr**	1.380	1.600	4.240	5.350
Mounting		Wall or panel			
Installation		In any position			






Without Regulator

9146	Description
9002100	40mm Diameter Booster, 1:2 Ratio
9002300	63mm Diameter Booster, 1:2 Ratio

Air Regulators



To suit Air Pressure Multiplier (Booster)

9193	Description
9002180	40mm Regulator Unit
9002380	63mm Regulator Unit

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PRESSURE BOOSTERS

Pressure Boosters



40mm complete with Regulator, BSPP

0110	Thread
1740.50.NR	1/8"



63mm complete with Regulator, BSPP

0110	Thread
1763.80.NR	3/8"



100mm complete with Regulator, BSPP

0110	Thread
17100.125.NR	1/2"



P+ Pressure Booster 40mm 0-20 bar complete with Gauges

0110	Thread
MDPT40.2R.A	1/4"



P+ Pressure Booster Mounting Bracket

0110	Description
T1740.01	Mounting for P+ 40mm Booster



Mounting Bracket 40/63/100mm

0110	To Suit
1740.02	40mm
1763.03	63mm
17100.04	100mm

VACUUM TECHNOLOGY - SUCTION CUPS

Index

VB Series - Single Bellows Page 708



- Single-bellow suction cup
- Diameter range: Ø5 to 150
- Material selection: NBR, silicone, conductive silicone, urethane, polyurethane

VOBL Series - Oval Bellow Page 728



- Long multi bellows and oval suction cup
- Diameter range: Ø35 x 90
- Material selection: NBR, silicone, conductive silicone

VB-M Series (Direct Fitting Bellows) Page 715



- Single-bellow suction cup for direct fittin
- Diameter range: Ø20 to 50
- Material selection: NBR, silicone, conductive silicone, urethane

VU Series - Universal Page 731



- Universal suction cup
- Diameter range: Ø1.5 to 80
- Material selection: NBR, silicone, conductive silicone, urethane

VBU Series - Double Bellow Page 718



- Bellows and universal suction cup
- Diameter range: Ø35 to 55
- Material selection: NBR, silicone, polyurethane

VF & LF Series - Flat Page 736



- Flat suction cup
- Diameter range: Ø15 to 300
- Material selection: NBR, silicone, conductive silicone, urethane, polyurethane

VBX Series - Double Bellow Page 719



- Bellows and cross groove suction cup
- Diameter range: Ø35 to 55
- Material selection: polyurethane

VFC Series - Deep Page 737



- Flat curved suction cup
- Diameter range: Ø50 to 100
- Material selection: NBR, silicone, conductive silicone, urethane, polyurethane

VBL Series - Long Multi Bellow Page 723



- Long multi-bellow suction cup
- Diameter range: Ø15 to 50
- Material selection: NBR, silicone, conductive silicone, urethane

FF Series - Flat, Mark Free Page 740



- Mark free and flat suction cu
- Diameter range: Ø10 to 30
- Material selection: NBR, silicone, conductive silicone, urethane

BL5040 - Long Multi Bellow Page 724



- Dual lip structure suction cup
- Diameter range: Ø50
- Material selection: NBR, silicone

VD Series - Deep Page 742w




- Deep suction cup
- Diameter range: Ø30 to 90
- Material selection: NBR, silicone, conductive silicone, urethane, polyurethane

VOU Series - Oval Universal Page 727



- Oval universal suction cup
- Diameter range: Ø4 x 10 to Ø20 x 60
- Material selection: NBR, silicone, conductive silicone, urethane

Specials Available on request



- Bellow flat suction cu
- Diameter range: Ø25 to 100
- Material selection: NBR, silicone, polyurethane
- Suction cups, foam rubber
- Suction cups, special flat bellow

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series




5mm, Cup Only

9205	Material	Colour	Temperature	Hardness
VB5-N	Nitrile	Black	-20°C-110°C	60
VB5-S	Silicone	Red	-70°C-200°C	55
VB5-WS	White Silicone	Translucent White	-70°C-200°C	55
VB5-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB5-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB5-U	Urethane	Dark Green	0°C-100°C	60
VB5-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions



With M5M fitting




Cup only



6mm, Cup Only

9205	Material	Colour	Temperature	Hardness
VB6X-N	Nitrile	Black	-20°C-110°C	60
VB6X-S	Silicone	Red	-70°C-200°C	55
VB6X-WS	White Silicone	Translucent White	-70°C-200°C	55
VB6X-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB6X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB6X-U	Urethane	Dark Green	0°C-100°C	60
VB6X-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions




Cup only




8mm, Cup Only

9205	Material	Colour	Temperature	Hardness
VB8X-N	Nitrile	Black	-20°C-110°C	60
VB8X-S	Silicone	Red	-70°C-200°C	55
VB8X-WS	White Silicone	Translucent White	-70°C-200°C	55
VB8X-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB8X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB8X-U	Urethane	Dark Green	0°C-100°C	60
VB8X-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions



With M5M fitting



Cup only

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series



10mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB10-N	Nitrile	Black	-20°C-110°C	60
VB10-S	Silicone	Red	-70°C-200°C	55
VB10-WS	White Silicone	Translucent White	-70°C-200°C	55
VB10-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB10-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB10-U	Urethane	Dark Green	0°C-100°C	60
VB10-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions




With M5M fitting | Cup only



12mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB12-N	Nitrile	Black	-20°C-110°C	60
VB12-S	Silicone	Red	-70°C-200°C	55
VB12-WS	White Silicone	Translucent White	-70°C-200°C	55
VB12-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB12-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB12-U	Urethane	Dark Green	0°C-100°C	60
VB12-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions




With M5M fitting | Cup only



15mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB15-N	Nitrile	Black	-20°C-110°C	60
VB15-S	Silicone	Red	-70°C-200°C	55
VB15-WS	White Silicone	Translucent White	-70°C-200°C	55
VB15-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB15-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB15-U	Urethane	Dark Green	0°C-100°C	60
VB15-A	Mark Free	Black	-10°C-100°C	75
VB15-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		

Dimensions



With M5M fitting | Cup only

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications


Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series



Dimensions




With M518MF fitting



With 18F fitting

17mm, Cup Only


9205	Material	Colour	Temperature	Hardness
VB17-N	Nitrile	Black	-20°C-110°C	60
VB17-S	Silicone	Red	-70°C-200°C	55
VB17-WS	White Silicone	Translucent White	-70°C-200°C	55
VB17-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB17-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB17-U	Urethane	Dark Green	0°C-100°C	60
VB17-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		




Cup only



Dimensions




With M518MF fitting




With M518MFB fitting

20mm, Cup Only

9205	Material	Colour	Temperature	Hardness
VB20-N	Nitrile	Black	-20°C-110°C	60
VB20-S	Silicone	Red	-70°C-200°C	55
VB20-WS	White Silicone	Translucent White	-70°C-200°C	55
VB20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB20-U	Urethane	Dark Green	0°C-100°C	60
VB20-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		



With 18F fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series




30mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB30-N	Nitrile	Black	-20°C-110°C	60
VB30-S	Silicone	Red	-70°C-200°C	55
VB30-WS	White Silicone	Translucent White	-70°C-200°C	55
VB30-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB30-U	Urethane	Dark Green	0°C-100°C	60
VB30-A	Mark Free	Black	-10°C-100°C	75
VB30-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		


Dimensions




With 18F fitting




With M518MF fitting



With 14M fitting



With 18M fitting




Cup only




40mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB40-N	Nitrile	Black	-20°C-110°C	60
VB40-S	Silicone	Red	-70°C-200°C	55
VB40-WS	White Silicone	Translucent White	-70°C-200°C	55
VB40-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VB40-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB40-U	Urethane	Dark Green	0°C-100°C	60
VB40-A	Mark Free	Black	-10°C-100°C	75
VB40-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		


Dimensions




With 18F fitting




With 18M fitting



With 14M fitting



With 18M fitting



Cup only

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series




50mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB50-N	Nitrile	Black	-20°C-110°C	60
VB50-S	Silicone	Red	-70°C-200°C	55
VB50-WS	White Silicone	Translucent White	-70°C-200°C	55
VB50-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB50-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB50-U	Urethane	Dark Green	0°C-100°C	60
VB50-A	Mark Free	Black	-10°C-100°C	75
VB50-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		


Dimensions




With 18F fitting




With 14M fitting



With 38M fitting



With 18x5F fitting




Cup only




75mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB75-N	Nitrile	Black	-20°C-110°C	60
VB75-S	Silicone	Red	-70°C-200°C	55
VB75-WS	White Silicone	Translucent White	-70°C-200°C	55
VB75-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB75-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB75-U	Urethane	Dark Green	0°C-100°C	60
VB75-A	Mark Free	Black	-10°C-100°C	75
VB75-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71773		


Dimensions




With 14F fitting




With 18F fitting



With 12F fitting



With 38F fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series




75mm with Large Cleats, Cup Only

9204	Material	Colour	Temperature	Hardness
VB75B-N	Nitrile	Black	-20°C-110°C	60
VB75B-S	Silicone	Red	-70°C-200°C	55
VB75B-WS	White Silicone	Translucent White	-70°C-200°C	55
VB75B-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB75B-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB75B-U	Urethane	Dark Green	0°C-100°C	60
VB75B-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		


Dimensions




With 14F fitting




With 18F fitting



With 12F fitting



With 38F fitting




Cup only




110mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB110-N	Nitrile	Black	-20°C-110°C	60
VB110-S	Silicone	Red	-70°C-200°C	55
VB110-WS	White Silicone	Translucent White	-70°C-200°C	55
VB110-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB110-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB110-U	Urethane	Dark Green	0°C-100°C	60
VB110-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71773		

Dimensions



With 12F fitting



Cup only

SUCTION CUPS – SINGLE BELLOWS

Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets


VB Series




110mm with Large Cleats, Cup Only

9204	Material	Colour	Temperature	Hardness
VB110B-N	Nitrile	Black	-20°C-110°C	60
VB110B-S	Silicone	Red	-70°C-200°C	55
VB110B-WS	White Silicone	Translucent White	-70°C-200°C	55
VB110B-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB110B-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB110B-U	Urethane	Dark Green	0°C-100°C	60
VB110B-A	Mark Free	Black	-10°C-100°C	75
Tech Sheet 71773				

Dimensions



With 12F fitting




Cup only




150mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VB150-N	Nitrile	Black	-20°C-110°C	60
VB150-S	Silicone	Red	-70°C-200°C	55
VB150-WS	White Silicone	Translucent White	-70°C-200°C	55
VB150-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB150-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB150-U	Urethane	Dark Green	0°C-100°C	60
VB150-A	Mark Free	Black	-10°C-100°C	75
Tech Sheet 71773				

Dimensions



With 12F fitting



Cup only

Disc Filters

To suit VB Series Cups

9204	Material	To Suit
VTFE-B30	Polyethylene	VB30/30M
VTFE-B40	Polyethylene	VB40
VTFE-B50	Polyethylene	VB50/50M
VTFE-B75	Polyethylene	VB75
VTFE-B110	Polyethylene	VB110
Tech Sheet 71773		

Fluid-Air Components Ltd

SUCTION CUPS – DIRECT MOUNT BELLOWS


Features & Strengths
- Compensating for a difference in level
- Various materials for a wide range of applications

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks.
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece.
- Fitted directly onto a piece of pipe, making installation very simple and reducing cup cost

Examples of Use
- Cardboards
- Packaging materials
- Thin film sheets
- Veneer sheets
- Plastic sheets

VB-M Series






Cup only

30mm with Long Neck, Cup Only

9204	Material	Colour	Temperature	Hardness
VB30M-N	Nitrile	Black	-20°C-110°C	60
VB30M-S	Silicone	Red	-70°C-200°C	55
VB30M-WS	White Silicone	Translucent White	-70°C-200°C	55
VB30M-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB30M-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB30M-U	Urethane	Dark Green	0°C-100°C	60
VB30M-A	Mark Free	Black	-10°C-100°C	75
VB30M-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71774		





Cup only

50mm with Long Neck, Cup Only

9204	Material	Colour	Temperature	Hardness
VB50M-N	Nitrile	Black	-20°C-110°C	60
VB50M-S	Silicone	Red	-70°C-200°C	55
VB50M-WS	White Silicone	Translucent White	-70°C-200°C	55
VB50M-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VB50M-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VB50M-U	Urethane	Dark Green	0°C-100°C	60
VB50M-A	Mark Free	Black	-10°C-100°C	75
VB50M-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71774		

Disc Filters

To suit VB-M Series Cups

9204	Material	To Suit
VTFE-B30	Polyethylene	VB30/30M
VTFE-B50	Polyethylene	VB50/50M
	Tech Sheet 71774	

SUCTION CUPS – DOUBLE BELLOWS


Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for curved products and separating thin sheets in stocks

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of materials in stacks with long bellows
- Can cope with an increased degree of height compensation and is particularly good for handling fragile objects

Examples of Use
- Convex surface
- Plastic bag
- Metal sheets
- Plywood
- Carton box
- Cement sack

VBU Series

Dimensions




With 14M fitting | With 18M fitting | With 18F fitting | With 38M fitting | Cup only



35mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBU35-N	Nitrile	Black	-20°C-110°C	60
VBU35-S	Silicone	Red	-70°C-200°C	55
VBU35-WS	White Silicone	Translucent White	-70°C-200°C	55
VBU35-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VBU35-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71775		

Dimensions



With 14M fitting | With 18M fitting | With 18F fitting | With 38M fitting | Cup only



45mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBU45-N	Nitrile	Black	-20°C-110°C	60
VBU45-S	Silicone	Red	-70°C-200°C	55
VBU45-WS	White Silicone	Translucent White	-70°C-200°C	55
VBU45-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VBU45-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71775		

Fluid-Air Components Ltd

SUCTION CUPS – DOUBLE BELLOWS


Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for curved products and separating thin sheets in stocks

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of materials in stacks with long bellows
- Can cope with an increased degree of height compensation and is particularly good for handling fragile objects

Examples of Use
- Convex surface
- Plastic bag
- Metal sheets
- Plywood
- Carton box
- Cement sack

VBU Series

Dimensions



With 14M fitting | With 18F fitting | With 38M fitting | With 38F fitting | Cup only



55mm, Cup Only


9205	Material	Colour	Temperature	Hardness
VBU55-N	Nitrile	Black	-20°C-110°C	60
VBU55-S	Silicone	Red	-70°C-200°C	55
VBU55-WS	White Silicone	Translucent White	-70°C-200°C	55
VBU55-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VBU55-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71775		

Disc Filters

To suit VBU Series Cups

9204	Material	To Suit
VTFE-BU35	Polyethylene	VBU35
VTFE-BU45	Polyethylene	VBU45
VTFE-BU55	Polyethylene	VBU55
	Tech Sheet 71775	

FT PRO




For **FT Pro Vacuum Gauges**
see page **412**

SUCTION CUPS – BELLOWS & CROSS GROOVE

VBX Series

Dimensions




With 14M fitting | With 18M fitting | With 18F fitting | With 38M fitting | Cup only



35mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBX35-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71776		

Dimensions




With 14M fitting | With 18M fitting | With 18F fitting | With 38M fitting | Cup only



45mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBX45-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71776		

Dimensions



With 14M fitting | With 18F fitting | With 38M fitting | With 38F fitting | Cup only



55mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBX55-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71776		

Disc Filters

To suit VBX Series

9204	Material	To Suit
VTFE-BX35	Polyethylene	VBX35-PU
VTFE-BX45	Polyethylene	VBX45-PU
VTFE-BX55	Polyethylene	VBX55-PU
	Tech Sheet 71776	

Fluid-Air Components Ltd

SUCTION CUPS – LONG MULTI BELLOWS

Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for fragile products

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks with long bellows
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece

Examples of Use
- Fragile objects
- Glass
- Bread
- General food products
- Eggs

VBL Series



10mm, Cup Only


9204	Material	Colour	Temperature	Hardness
VBL10-N	Nitrile	Black	-20°C-110°C	60
VBL10-S	Silicone	Red	-70°C-200°C	55
VBL10-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL10-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL10-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL10-U	Urethane	Dark Green	0°C-100°C	60
VBL10-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		



15mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL15-N	Nitrile	Black	-20°C-110°C	60
VBL15-S	Silicone	Red	-70°C-200°C	55
VBL15-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL15-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL15-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL15-U	Urethane	Dark Green	0°C-100°C	60
VBL15-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		

Dimensions



With M5M fitting

Cup only

Fluid-Air Components Ltd

SUCTION CUPS – LONG MULTI BELLOWS

Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for fragile products

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks with long bellows
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece

Examples of Use
- Fragile objects
- Glass
- Bread
- General food products
- Eggs


VBL Series




20mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL20-N	Nitrile	Black	-20°C-110°C	60
VBL20-S	Silicone	Red	-70°C-200°C	55
VBL20-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL20-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL20-U	Urethane	Dark Green	0°C-100°C	60
VBL20-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		


Dimensions




With 18F fitting



With M518MB fitting



With M518MF fitting




Cup only




30mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL30-N	Nitrile	Black	-20°C-110°C	60
VBL30-S	Silicone	Red	-70°C-200°C	55
VBL30-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL30-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL30-U	Urethane	Dark Green	0°C-100°C	60
VBL30-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		


Dimensions




With 18M fitting




With 14M fitting



With 18F fitting



With 18FB fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS – LONG MULTI BELLOWS

Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for fragile products

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks with long bellows
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece

Examples of Use
- Fragile objects
- Glass
- Bread
- General food products
- Eggs


VBL Series



35mm, with Pipe Mount Neck, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL35M-N	Nitrile	Black	-20°C-110°C	60
VBL35M-S	Silicone	Red	-70°C-200°C	55
VBL35M-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL35M-FDA-30	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL35M-FDA-55	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL35M-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL35M-U	Urethane	Dark Green	0°C-100°C	60
VBL35M-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		

Dimensions




Cup only




40mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL40-N	Nitrile	Black	-20°C-110°C	60
VBL40-S	Silicone	Red	-70°C-200°C	55
VBL40-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL40-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL40-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL40-U	Urethane	Dark Green	0°C-100°C	60
VBL40-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		


Dimensions




With 14M fitting




With 18M fitting



With 18F fitting



With 18FB fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS – LONG MULTI BELLOWS

Features & Strengths
- Wide cover for increased degree of height compensation
- Excellent for fragile products

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of material in stacks with long bellows
- The bellows cup is very good at compensating for a degree of difference in level and curvature of the work piece

Examples of Use
- Fragile objects
- Glass
- Bread
- General food products
- Eggs


VBL Series



40mm, Alternate Design, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL40B-N	Nitrile	Black	-20°C-110°C	60
VBL40B-S	Silicone	Red	-70°C-200°C	55
VBL40B-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL40B-FDA-30	White Silicone FDA	Translucent White	-70°C-200°C	30
VBL40B-FDA-55	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL40B-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL40B-U	Urethane	Dark Green	0°C-100°C	60
VBL40B-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		

Dimensions




Cup only




50mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VBL50-N	Nitrile	Black	-20°C-110°C	60
VBL50-S	Silicone	Red	-70°C-200°C	55
VBL50-WS	White Silicone	Translucent White	-70°C-200°C	55
VBL50-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VBL50-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VBL50-U	Urethane	Dark Green	0°C-100°C	60
VBL50-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71777		


Dimensions




With 18F fitting



With 14M fitting



With 38M fitting



Cup only

Disc Filters

To suit VBL Series

9204	Material	To Suit
VTFE-BL20	Polyethylene	VBL20
VTFE-BL30	Polyethylene	VBL30
VTFE-BL40B	Polyethylene	VBL40B
VTFE-BL40	Polyethylene	VBL40
VTFE-BL50	Polyethylene	VBL50
	Tech Sheet 71777	

Fluid-Air Components Ltd

SUCTION CUPS – DUAL LIP STRUCTURE

BL5040 Series


Features & Strengths
- Excellent for irregular curved surfaces and rough surfaces and has a dual lip structure to increase safety

Advantages
- Particularly good for use on curved surfaces and for separating thin sheets of materials in stacks with long bellows
- Can cope with an increased degree of heights compensation and is particularly good for handling fragile objects


Examples of Use
- Round food types (such as apples & oranges)
- Convex surface




Dimensions




With 14M fitting



With 18F fitting



With 38M fitting



Cup Only

40mm Inner x 50mm Outer, Cup Only

9205	Material	Colour	Temperature	Hardness
BL5040-N	Nitrile	Black	-20°C-110°C	60
BL5040-S3	Silicone - S3	Translucent Blue	-70°C-200°C	30
BL5040-S5	Silicone - S5	Red	-70°C-200°C	55
BL5040-WS3	White Silicone - WS3	Translucent White	-70°C-200°C	30
BL5040-WS5	White Silicone - WS5	Translucent White	-70°C-200°C	55
BL5040-WS3-FDA	White Silicone - WS3 (FDA)	Translucent White	-70°C-200°C	30
BL5040-WS5-FDA	White Silicone - WS5 (FDA)	Translucent White	-70°C-200°C	55
Tech Sheet 71778				

FT PRO



For **All Metal Push-in Fittings Emergency Kit**
see page **844**

SUCTION CUPS - OVAL UNIVERSAL

Features & Strengths
- Great performance for handling long objects with flat and curved surfaces

Advantages
- Good lifting forces can be achieved with even the small sizes
- Conductive silicone material provides excellent handling of PCB boards or electronic components
- Easily mountable without having to detach a fitting from the machine (saving in maintenance time)

Examples of Use
- Semiconductor chips
- PCB boards
- Electronic components
- Solar cells
- Small glass cases


VOU Series



4 x 10mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOU4X10-N	Nitrile	Black	-20°C-110°C	60
VOU4X10-S	Silicone	Red	-70°C-200°C	55
VOU4X10-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU4X10-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU4X10-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU4X10-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions




With M5M Fitting | With M5F Fitting



6 x 10mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOU6X10-N	Nitrile	Black	-20°C-110°C	60
VOU6X10-S	Silicone	Red	-70°C-200°C	55
VOU6X10-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU6X10-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU6X10-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU6X10-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions




Cup only



4 x 20mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOU4X20-N	Nitrile	Black	-20°C-110°C	60
VOU4X20-S	Silicone	Red	-70°C-200°C	55
VOU4X20-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU4X20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU4X20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU4X20-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions



With M5M Fitting | With M5F Fitting

SUCTION CUPS - OVAL UNIVERSAL

Features & Strengths
- Great performance for handling long objects with flat and curved surfaces

Advantages
- Good lifting forces can be achieved with even the small sizes
- Conductive silicone material provides excellent handling of PCB boards or electronic components
- Easily mountable without having to detach a fitting from the machine (saving in maintenance time)

Examples of Use
- Semiconductor chips
- PCB boards
- Electronic components
- Solar cells
- Small glass cases


VOU Series

6 x 20mm, Cup Only



9204	Material	Colour	Temperature	Hardness
VOU6X20-N	Nitrile	Black	-20°C-110°C	60
VOU6X20-S	Silicone	Red	-70°C-200°C	55
VOU6X20-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU6X20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU6X20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU6X20-U	Urethane	Dark Green	0-100°C	60
		Tech Sheet 71779		

Dimensions




8 x 20mm, Cup Only



9204	Material	Colour	Temperature	Hardness
VOU8X20-N	Nitrile	Black	-20°C-110°C	60
VOU8X20-S	Silicone	Red	-70°C-200°C	55
VOU8X20-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU8X20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU8X20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU8X20-U	Urethane	Dark Green	0-100°C	60
		Tech Sheet 71779		

Dimensions




8 x 30mm, Cup Only



9204	Material	Colour	Temperature	Hardness
VOU8X30-N	Nitrile	Black	-20°C-110°C	60
VOU8X30-S	Silicone	Red	-70°C-200°C	55
VOU8X30-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU8X30-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU8X30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU8X30-U	Urethane	Dark Green	0-100°C	60
		Tech Sheet 71779		

Dimensions



Fluid-Air Components Ltd

SUCTION CUPS - OVAL UNIVERSAL

Features & Strengths
- Great performance for handling long objects with flat and curved surfaces

Advantages
- Good lifting forces can be achieved with even the small sizes
- Conductive silicone material provides excellent handling of PCB boards or electronic components
- Easily mountable without having to detach a fitting from the machine (saving in maintenance time)

Examples of Use
- Semiconductor chips
- PCB boards
- Electronic components
- Solar cells
- Small glass cases


VOU Series



10 x 30mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOU10X30-N	Nitrile	Black	-20°C-110°C	60
VOU10X30-S	Silicone	Red	-70°C-200°C	55
VOU10X30-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU10X30-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU10X30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU10X30-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions






15 x 45mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOU15X45-N	Nitrile	Black	-20°C-110°C	60
VOU15X45-S	Silicone	Red	-70°C-200°C	55
VOU15X45-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU15X45-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU15X45-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU15X45-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions






20 x 60mm Cup Only

9204	Material	Colour	Temperature	Hardness
VOU20X60-N	Nitrile	Black	-20°C-110°C	60
VOU20X60-S	Silicone	Red	-70°C-200°C	55
VOU20X60-WS	White Silicone	Translucent White	-70°C-200°C	55
VOU20X60-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOU20X60-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOU20X60-U	Urethane	Dark Green	0-100°C	60
Tech Sheet 71779				

Dimensions




Fluid-Air Components Ltd

SUCTION CUPS – LONG MULTI BELLOWS & OVAL TYPE

VOBL Series

Dimensions



With 12F fitting

Cup only



35 x 90mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VOBL35X90-N	Nitrile	Black	-20°C-110°C	60
VOBL35X90-S	Silicone	Red	-70°C-200°C	55
VOBL35X90-WS	White Silicone	Translucent White	-70°C-200°C	55
VOBL35X90-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VOBL35X90-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VOBL35X90-U	Urethane	Dark Green	0-100°C	60
VOBL35X90-A	Mark Free	Black	-10°C-100°C	75
Tech Sheet 71780				

Disc Filters

To suit VOBL Series

9204	Material
VTFE-OBL35X90	Polyethylene
Tech Sheet 71780	

For **Solenoid Valves** see pages **1031-1034**



SUCTION CUPS - UNIVERSAL

Features & Strengths

- Excellent performance for flat stable and slightly curved surfaces with direct fitting
- Suitable for concave surface

Examples of Use

- Good lifting forces can be achieved with this cup; is best suited to flat stable surfaces, but can cope with a small degree of curvature
- Very small cups are available down to just 1.5mm diameter


VU Series



1.5mm to suit Level Compensator, Cup Only

9204	Material	Colour	Temperature	Hardness
VU1.5X-N	Nitrile	Black	-20°C-110°C	60
VU1.5X-S	Silicone	Red	-70°C-200°C	55
VU1.5X-WS	White Silicone	Translucent White	-70°C-200°C	55
VU1.5X-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU1.5X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU1.5X-U	Urethane	Dark Green	0-100°C	60
VU1.5X-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions




Cup only




2mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VU2-N	Nitrile	Black	-20°C-110°C	60
VU2-S	Silicone	Red	-70°C-200°C	55
VU2-WS	White Silicone	Translucent White	-70°C-200°C	55
VU2-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU2-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU2-U	Urethane	Dark Green	0°C-100°C	60
VU2-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		


Dimensions



With M2.5M fitting



With M5M fitting




Cup only



2mm to suit Level Compensator, Cup Only

9204	Material	Colour	Temperature	Hardness
VU2X-N	Nitrile	Black	-20°C-110°C	60
VU2X-S	Silicone	Red	-70°C-200°C	55
VU2X-WS	White Silicone	Translucent White	-70°C-200°C	55
VU2X-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU2X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU2X-U	Urethane	Dark Green	0-100°C	60
VU2X-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



Cup only

Fluid-Air Components Ltd

SUCTION CUPS - UNIVERSAL

Features & Strengths
- Excellent performance for flat stable and slightly curved surfaces with direct fitting
- Suitable for concave surface

Examples of Use
- Good lifting forces can be achieved with this cup; is best suited to flat stable surfaces, but can cope with a small degree of curvature
- Very small cups are available down to just 1.5mm diameter


VU Series

3mm, Cup Only




9204	Material	Colour	Temperature	Hardness
VU3-N	Nitrile	Black	-20°C-110°C	60
VU3-S	Silicone	Red	-70°C-200°C	55
VU3-WS	White Silicone	Translucent White	-70°C-200°C	55
VU3-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU3-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU3-U	Urethane	Dark Green	0-100°C	60
VU3-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		


Dimensions



With M2.5M fitting



With M5M fitting




Cup only

4mm, Cup Only




9204	Material	Colour	Temperature	Hardness
VU4-N	Nitrile	Black	-20°C-110°C	60
VU4-S	Silicone	Red	-70°C-200°C	55
VU4-WS	White Silicone	Translucent White	-70°C-200°C	55
VU4-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU4-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU4-U	Urethane	Dark Green	0-100°C	60
VU4-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



With M5M fitting




Cup only

4mm to suit Level Compensators, Cup Only



9204	Material	Colour	Temperature	Hardness
VU4X-N	Nitrile	Black	-20°C-110°C	60
VU4X-S	Silicone	Red	-70°C-200°C	55
VU4X-WS	White Silicone	Translucent White	-70°C-200°C	55
VU4X-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU4X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU4X-U	Urethane	Dark Green	0-100°C	60
VU4X-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



Cup only

Specifications subject to change without notice

Fluid-Air Components Ltd

SUCTION CUPS - UNIVERSAL

Features & Strengths

- Excellent performance for flat stable and slightly curved surfaces with direct fitting
- Suitable for concave surface

Examples of Use

- Good lifting forces can be achieved with this cup; is best suited to flat stable surfaces, but can cope with a small degree of curvature
- Very small cups are available down to just 1.5mm diameter


VU Series




6mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VU6-N	Nitrile	Black	-20°C-110°C	60
VU6-S	Silicone	Red	-70°C-200°C	55
VU6-WS	White Silicone	Translucent White	-70°C-200°C	55
VU6-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU6-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU6-U	Urethane	Dark Green	0-100°C	60
VU6-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



With M5M fitting




Cup only




8mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VU8-N	Nitrile	Black	-20°C-110°C	60
VU8-S	Silicone	Red	-70°C-200°C	55
VU8-WS	White Silicone	Translucent White	-70°C-200°C	55
VU8-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU8-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU8-U	Urethane	Dark Green	0-100°C	60
VU8-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



With M5M fitting




Cup only




10mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VU10-N	Nitrile	Black	-20°C-110°C	60
VU10-S	Silicone	Red	-70°C-200°C	55
VU10-WS	White Silicone	Translucent White	-70°C-200°C	55
VU10-WS(FDA)	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VU10-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VU10-U	Urethane	Dark Green	0-100°C	60
VU10-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71781		

Dimensions



With M5M fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS - FLAT

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Metal sheet, veneer sheets, glass, electronic components


VF Series




15mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF15-N	Nitrile	Black	-20°C-110°C	60
VF15-S	Silicone	Red	-70°C-200°C	55
VF15-WS	White Silicone	Translucent White	-70°C-200°C	55
VF15-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF15-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF15-U	Urethane	Dark Green	0°C-100°C	60
VF15-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		

Dimensions



With M5M fitting




Cup only




20mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF20-N	Nitrile	Black	-20°C-110°C	60
VF20-S	Silicone	Red	-70°C-200°C	55
VF20-WS	White Silicone	Translucent White	-70°C-200°C	55
VF20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF20-U	Urethane	Dark Green	0°C-100°C	60
VF20-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		


Dimensions




With 18F fitting




With M518MF fitting



With M518MFO fitting



With M518MFX fitting



Cup only

Fluid-Air Components Ltd

SUCTION CUPS - FLAT


Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Metal sheet, veneer sheets, glass, electronic components


VF Series




Dimensions



Cup only




With 18F fitting




With M518MF fitting

25mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF25-N	Nitrile	Black	-20°C-110°C	60
VF25-S	Silicone	Red	-70°C-20°C	55
VF25-WS	White Silicone	Translucent White	-70°C-200°C	55
VF25-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF25-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF25-U	Urethane	Dark Green	0°C-100°C	60
VF25-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		




With M518MFO fitting




With M518MFX fitting




Dimensions



Cup only




With 18F fitting




With M518MF fitting

30mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF30-N	Nitrile	Black	-20°C-110°C	60
VF30-S	Silicone	Red	-70°C-200°C	55
VF30-WS	White Silicone	Translucent White	-70°C-200°C	55
VF30-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF30-U	Urethane	Dark Green	0°C-100°C	60
VF30-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		




With M518MFO fitting




With M518MFX fitting




Dimensions



Cup only




With 18F fitting




With 18FX fitting

40mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF40-N	Nitrile	Black	-20°C-110°C	60
VF40-S	Silicone	Red	-70°C-200°C	55
VF40-WS	White Silicone	Translucent White	-70°C-200°C	55
VF40-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF40-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF40-U	Urethane	Dark Green	0°C-100°C	60
VF40-A	Mark Free	Black	-10°C-100°C	75
VF40-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71782		



With 18M fitting



With M518MFX fitting

Fluid-Air Components Ltd

SUCTION CUPS - FLAT

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Metal sheet, veneer sheets, glass, electronic components


VF Series




50mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF50-N	Nitrile	Black	-20°C-110°C	60
VF50-S	Silicone	Red	-70°C-200°C	55
VF50-WS	White Silicone	Translucent White	-70°C-200°C	55
VF50-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF50-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF50-U	Urethane	Dark Green	0°C-100°C	60
VF50-A	Mark Free	Black	-10°C-100°C	75
VF50-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71782		


Dimensions




With 18F fitting



With 14M fitting



With 38M fitting




Cup only



50mm with M16M Fitting

9204	Material	Colour	Temperature	Hardness
VF50X2-N	Nitrile	Black	-20°C-110°C	60
VF50X2-S	Silicone	Red	-70°C-200°C	55
VF50X2-WS	White Silicone	Translucent White	-70°C-200°C	55
VF50X2-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF50X2-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF50X2-U	Urethane	Dark Green	0°C-100°C	60
VF50X2-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		

Dimensions




With M16M fitting




75mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF75-N	Nitrile	Black	-20°C-110°C	60
VF75-S	Silicone	Red	-70°C-200°C	55
VF75-WS	White Silicone	Translucent White	-70°C-200°C	55
VF75-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF75-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF75-U	Urethane	Dark Green	0°C-100°C	60
VF75-A	Mark Free	Black	-10°C-100°C	75
VF75-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71782		


Dimensions




With 18F fitting




With 14F fitting



With 38F fitting



With 12F fitting



Cup only

Fluid-Air Components Ltd


SUCTION CUPS - FLAT

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Metal sheet, veneer sheets, glass, electronic components

VF Series

Dimensions



With 12F fitting | With 14F fitting | With 38F fitting | With 18F fitting | Cup only



90mm, Cup Only


9204	Material	Colour	Temperature	Hardness
VF90-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71782		



110mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF110-N	Nitrile	Black	-20°C-110°C	60
VF110-S	Silicone	Red	-70°C-200°C	55
VF110-WS	White Silicone	Translucent White	-70°C-200°C	55
VF110-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF110-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF110-U	Urethane	Dark Green	0°C-100°C	60
VF110-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		

Dimensions



With 12F fitting


Cup only



150mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF150-N	Nitrile	Black	-20°C-110°C	60
VF150-S	Silicone	Red	-70°C-200°C	55
VF150-WS	White Silicone	Translucent White	-70°C-200°C	55
VF150-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF150-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF150-U	Urethane	Dark Green	0°C-100°C	60
VF150-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		

Dimensions



With 12F fitting

Cup only

Fluid-Air Components Ltd

SUCTION CUPS - FLAT

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Metal sheet, veneer sheets, glass, electronic components


VF Series




200mm, Cup Only

9204	Material	Colour	Temperature	Hardness
VF200-N	Nitrile	Black	-20°C-110°C	60
VF200-S	Silicone	Red	-70°C-200°C	55
VF200-WS	White Silicone	Translucent White	-70°C-200°C	55
VF200-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
VF200-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VF200-U	Urethane	Dark Green	0°C-100°C	60
VF200-A	Mark Free	Black	-10°C-100°C	75
		Tech Sheet 71782		

Dimensions



With 12F fitting




Cup only



300mm Cups with Female Fitting

9204	Material	Female Thread	Colour	Temperature	Hardness
VF300-N-34F	Nitrile	G3/4"	Black	-20°C-110°C	60
VF300-S-34F	Silicone	G3/4"	Red	-70°C-200°C	55
VF300-WS-34F	White Silicone	G3/4"	Translucent White	-70°C-200°C	55
VF300-WS-FDA-34F	White Silicone (FDA)	G3/4"	Translucent White	-70°C-200°C	55
VF300-CS-34F	Conductive Silicone	G3/4"	Smoky Black	-45°C-90°C	70
VF300-U-34F	Urethane	G3/4"	Dark Green	0°C-100°C	60
VF300-A-34F	Mark Free	G3/4"	Black	-10°C-100°C	75
		Tech Sheet 71782			

Dimensions



With 34F fitting

PORTWEST



For **Portwest PPE & Safeguarding Equipment**
see pages **1750-1760**

Fluid-Air Components Ltd

SUCTION CUPS - FLAT, DUAL LIP STRUCTURE


LF Series



150mm, Cup Only

9204	Material	Female Thread	Colour	Temperature	Hardness
LF150-N-12F	Nitrile	G1/2"	Black	-20°C-110°C	60
LF150-S-12F	Silicone	G1/2"	Red	-70°C-200°C	55
LF150-WS-12F	White Silicone	G1/2"	Translucent White	-70°C-200°C	55
LF150-WS-12FDA	White Silicone FDA	G1/2"	Translucent White	-70°C-200°C	55
		Tech Sheet 71783			

Dimensions




With 12F fitting



200mm, Cup Only

9204	Material	Female Thread	Colour	Temperature	Hardness
LF200-N-12F	Nitrile	G1/2"	Black	-20°C-110°C	60
LF200-S-12F	Silicone	G1/2"	Red	-70°C-200°C	55
LF200-WS-12F	White Silicone	G1/2"	Translucent White	-70°C-200°C	55
LF200-WS-12FDA	White Silicone FDA	G1/2"	Translucent White	-70°C-200°C	55
		Tech Sheet 71783			

Dimensions




With 12F fitting



250mm, Cup Only

9204	Material	Female Thread	Colour	Temperature	Hardness
LF250-N-12F	Nitrile	G1/2"	Black	-20°C-110°C	60
LF250-S-12F	Silicone	G1/2"	Red	-70°C-200°C	55
LF250-WS-12F	White Silicone	G1/2"	Translucent White	-70°C-200°C	55
LF250-WS-12FDA	White Silicone FDA	G1/2"	Translucent White	-70°C-200°C	55
		Tech Sheet 71783			

Dimensions




With 12F fitting



300mm, Cup Only

9204	Material	Female Thread	Colour	Temperature	Hardness
LF300-N-12F	Nitrile	G1/2"	Black	-20°C-110°C	60
LF300-S-12F	Silicone	G1/2"	Red	-70°C-200°C	55
LF300-WS-12F	White Silicone	G1/2"	Translucent White	-70°C-200°C	55
LF300-WS-12FDA	White Silicone FDA	G1/2"	Translucent White	-70°C-200°C	55
		Tech Sheet 71783			

Dimensions



With 12F fitting

SUCTION CUPS - FLAT & CURVE

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Automobile windscreens, roof and door, metal sheet, shaped metal panel, TV cathode ray tube


VFC Series



50mm Cup with Fitting

9204	Material	Connection		Colour	Temperature	Hardness
		Male	Female			
VFC50-N-1838MF	Nitrile	3/8"	1/8"	Black	-20°C-110°C	60
VFC50-S-1838MF	Silicone	3/8"	1/8"	Red	-70°C-200°C	55
VFC50-WS-1838MF	White Silicone	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC50-WS-FDA	White Silicone FDA	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC50-CS-1838MF	Conductive Silicone	3/8"	1/8"	Smoky Black	-45°C-90°C	70
VFC50-U-1838MF	Urethane	3/8"	1/8"	Dark Green	0°C-100°C	60
VFC50-A-1838MF	Mark Free	3/8"	1/8"	Black	-10°C-100°C	75
VFC50-PU-1838MF	Polyurethane	3/8"	1/8"	Translucent Orange	0°C-60°C	60
Tech Sheet 71784						

Dimensions




With 1838MF fitting



60mm Cup with Fitting

9204	Material	Connection		Colour	Temperature	Hardness
		Male	Female			
VFC60-N-1838MF	Nitrile	3/8"	1/8"	Black	-20°C-110°C	60
VFC60-S-1838MF	Silicone	3/8"	1/8"	Red	-70°C-200°C	55
VFC60-WS-1838MF	White Silicone	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC60-WS-FDA	White Silicone FDA	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC60-CS-1838MF	Conductive Silicone	3/8"	1/8"	Smoky Black	-45°C-90°C	70
VFC60-U-1838MF	Urethane	3/8"	1/8"	Dark Green	0°C-100°C	60
VFC60-A-1838MF	Mark Free	3/8"	1/8"	Black	-10°C-100°C	75
VFC60-PU-1838MF	Polyurethane	3/8"	1/8"	Translucent Orange	0°C-60°C	60
VFC60X1-N-M10M	Nitrile	M10	-	Black	-20°C-110°C	60
VFC60X1-S-M10M	Silicone	M10	-	Red	-70°C-200°C	55
VFC60X1-WS-M10M	White Silicone	M10	-	Translucent White	-70°C-200°C	55
VFC60X1-WSA-FDA	White Silicone FDA	M10	-	Translucent White	-70°C-200°C	55
VFC60X1-CS-M10M	Conductive Silicone	M10	-	Smoky Black	-45°C-90°C	70
VFC60X1-U-M10M	Urethane	M10	-	Dark Green	0°C-100°C	60
VFC60X1-A-M10M	Mark Free	M10	-	Black	-10°C-100°C	75
VFC60X1-PU-M10M	Polyurethane	M10	-	Translucent Orange	0°C-60°C	60
Tech Sheet 71784						

Dimensions



With 1838MF fitting

Fluid-Air Components Ltd

SUCTION CUPS - FLAT & CURVE


Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Automobile windscreens, roof and door, metal sheet, shaped metal panel, TV cathode ray tube

VFC Series



Dimensions



With 1838MF fitting

75mm Cup with Fitting

9204	Material	Connection		Colour	Temperature	Hardness
		Male	Female			
VFC75-N-1838MF	Nitrile	3/8"	1/8"	Black	-20°C-110°C	60
VFC75-S-1838MF	Silicone	3/8"	1/8"	Red	-70°C-200°C	55
VFC75-WS-1838MF	White Silicone	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC75-WS-FDA	White Silicone FDA	3/8"	1/8"	Translucent White	-70°C-200°C	55
VFC75-CS-1838MF	Conductive Silicone	3/8"	1/8"	Smoky Black	-45°C-90°C	70
VFC75-U-1838MF	Urethane	3/8"	1/8"	Dark Green	0°C-100°C	60
VFC75-A-1838MF	Mark Free	3/8"	1/8"	Black	-10°C-100°C	75
VFC75-PU-1838MF	Polyurethane	3/8"	1/8"	Translucent Orange	0°C-60°C	60
VFC75X1-N-M10M	Nitrile	M10	–	Black	-20°C-110°C	60
VFC75X1-S-M10M	Silicone	M10	–	Red	-70°C-200°C	55
VFC75X1-WS-M10M	White Silicone	M10	–	Translucent White	-70°C-200°C	55
VFC75X1-WS-FDA	White Silicone FDA	M10	–	Translucent White	-70°C-200°C	55
VFC75X1-CS-M10M	Conductive Silicone	M10	–	Smoky Black	-45°C-90°C	70
VFC75X1-U-M10M	Urethane	M10	–	Dark Green	0°C-100°C	60
VFC75X1-A-M10M	Mark Free	M10	–	Black	-10°C-100°C	75
VFC75X2-N-M16M	Nitrile	M16	–	Black	-20°C-110°C	60
VFC75X2-S-M16M	Silicone	M16	–	Red	-70°C-200°C	55
VFC75X2-WS-M16M	White Silicone	M16	–	Translucent White	-70°C-200°C	55
VFC75X2-WS-FDA	White Silicone FDA	M16	–	Translucent White	-70°C-200°C	55
VFC75X2-CS-M16M	Conductive Silicone	M16	–	Smoky Black	-45°C-90°C	70
VFC75X2-U-M16M	Urethane	M16	–	Dark Green	0°C-100°C	60
VFC75X2-A-M16M	Mark Free	M16	–	Black	-10°C-100°C	75
Tech Sheet 71784						

aircom PIPINGSYSTEM



For **Aircom Ring Main System**
see pages **1068-1080**

Fluid-Air Components Ltd


SUCTION CUPS - FLAT & CURVE

Features & Strengths
- Specifically designed for flat and curved surface
- Available to handle multiple objects with the same suction cup

Examples of Use
- Automobile windscreens, roof and door, metal sheet, shaped metal panel, TV cathode ray tube

VFC Series

Dimensions




With 18F fitting | With 14F fitting | With 38F fitting | With 12F fitting | Cup only



90mm Cups, Cup Only

9204	Material	Colour	Temperature	Hardness
VFC90-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71784		

Dimensions



With 18F fitting | With 14F fitting | With 38F fitting | With 12F fitting | Cup only



100mm Cups, Cup Only

9204	Material	Colour	Temperature	Hardness
VFC100-N	Nitrile	Black	-20°C-110°C	60
VFC100-S	Silicone	Red	-70°C-200°C	55
VFC100-WS	White Silicone	Translucent White	-70°C-200°C	55
VFC100-WS-FDA	White Silicone FDA	Translucent White	-70°C-200°C	55
VFC100-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
VFC100-U	Urethane	Dark Green	0°C-100°C	60
VFC100-A	Mark Free	Black	-10°C-100°C	75
VFC100-PU	Polyurethane	Translucent Orange	0°C-60°C	60
		Tech Sheet 71784		

Fluid-Air Components Ltd

SUCTION CUPS - MARK FREE, FLAT STRUCTURE

Features & Strengths
- Excellent performance for very thin and light weight products
- Mark free

Examples of Use
- Semiconductor, display, thin film


FF Series



10mm Cups with M5 Male Fitting

9204	Material	Colour	Temperature	Hardness
FF10-N-M5M	Nitrile	Black	-20°C-110°C	60
FF10-S-M5M	Silicone	Red	-70°C-200°C	55
FF10-WS-M5M	White Silicone	Translucent White	-70°C-200°C	55
FF10-WS-M5M-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF10-CS-M5M	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions




With M5M fitting



15mm, Cup Only

9204	Material	Colour	Temperature	Hardness
FF15-N	Nitrile	Black	-20°C-110°C	60
FF15-S	Silicone	Red	-70°C-200°C	55
FF15-WS	White Silicone	Translucent White	-70°C-200°C	55
FF15-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF15-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions




With M5M fitting | Cup only



15mm with 7mm Neck, Cup Only

9204	Material	Colour	Temperature	Hardness
FF15X-N	Nitrile	Black	-20°C-110°C	60
FF15X-S	Silicone	Red	-70°C-200°C	55
FF15X-WS	White Silicone	Translucent White	-70°C-200°C	55
FF15X-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF15X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions



With M5M fitting | Cup only

Fluid-Air Components Ltd

SUCTION CUPS - MARK FREE, FLAT STRUCTURE

Features & Strengths
- Excellent performance for very thin and light weight products
- Mark free

Examples of Use
- Semiconductor, display, thin film


FF Series



20mm, Cup Only

9204	Material	Colour	Temperature	Hardness
FF20-N	Nitrile	Black	-20°C-110°C	60
FF20-S	Silicone	Red	-70°C-200°C	55
FF20-WS	White Silicone	Translucent White	-70°C-200°C	55
FF20-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF20-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions




With M5M fitting | Cup only



20mm with 7mm Neck, Cup Only

9204	Material	Colour	Temperature	Hardness
FF20X-N	Nitrile	Black	-20°C-110°C	60
FF20X-S	Silicone	Red	-70°C-200°C	55
FF20X-WS	White Silicone	Translucent White	-70°C-200°C	55
FF20X-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF20X-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions




With M5M fitting | Cup only



25mm, Cup Only

9204	Material	Colour	Temperature	Hardness
FF25-N	Nitrile	Black	-20°C-110°C	60
FF25-S	Silicone	Red	-70°C-200°C	55
FF25-WS	White Silicone	Translucent White	-70°C-200°C	55
FF25-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF25-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions




With M5M fitting | Cup only



30mm, Cup Only

9204	Material	Colour	Temperature	Hardness
FF30-N	Nitrile	Black	-20°C-110°C	60
FF30-S	Silicone	Red	-70°C-200°C	55
FF30-WS	White Silicone	Translucent White	-70°C-200°C	55
FF30-WS-FDA	White Silicone (FDA)	Translucent White	-70°C-200°C	55
FF30-CS	Conductive Silicone	Smoky Black	-45°C-90°C	70
		Tech Sheet 71785		

Dimensions



With M5M fitting | Cup only

Fluid-Air Components Ltd

SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge

Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting


VD Series




30mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD30-N-M8M	Nitrile	M8	Black	-20°C-110°C	60	Male
VD30-S-M8M	Silicone	M8	Red	-70°C-200°C	55	Male
VD30-WS-M8M	White Silicone	M8	Translucent White	-70°C-200°C	55	Male
VD30-WS-FDA-M8M	White Silicone (FDA)	M8	Translucent White	-70°C-200°C	55	Male
VD30-CS-M8M	Conductive Silicone	M8	Smoky Black	-45°C-90°C	70	Male
VD30-U-M8M	Urethane	M8	Dark Green	0°C-100°C	60	Male
VD30-A-M8M	Mark Free	M8	Black	-10°C-100°C	75	Male
VD30-PU-M8M	Polyurethane	M8	Translucent Orange	0°C-60°C	60	Male
VD30-N-M10M	Nitrile	M10	Black	-20°C-110°C	60	Male
VD30-S-M10M	Silicone	M10	Red	-70°C-200°C	55	Male
VD30-WS-M10M	White Silicone	M10	Translucent White	-70°C-200°C	55	Male
VD30-WS-FDA-M10M	White Silicone (FDA)	M10	Translucent White	-70°C-200°C	55	Male
VD30-CS-M10M	Conductive Silicone	M10	Smoky Black	-45°C-90°C	70	Male
VD30-U-M10M	Urethane	M10	Dark Green	0°C-100°C	60	Male
VD30-A-M10M	Mark Free	M10	Black	-10°C-100°C	75	Male
VD30-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD30-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD30-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD30-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD30-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD30-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD30-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD30-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
VD30-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female
Tech Sheet 71786						


Dimensions



With M8M fitting



With M10M fitting



With 18F fitting

RIDGID



For **Ridgid Tools**
see pages **1742-1746**

SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge

Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting

VD Series




40mm Cups with Fitting


9204	Material	Connection	Colour	Temperature	Hardness	Type
VD40-N-M8M	Nitrile	M8	Black	-20°C-110°C	60	Male
VD40-S-M8M	Silicone	M8	Red	-70°C-200°C	55	Male
VD40-WS-M8M	White Silicone	M8	Translucent White	-70°C-200°C	55	Male
VD40-WS-FDA-M8M	White Silicone (FDA)	M8	Translucent White	-70°C-200°C	55	Male
VD40-CS-M8M	Conductive Silicone	M8	Smoky Black	-45°C-90°C	70	Male
VD40-U-M8M	Urethane	M8	Dark Green	0°C-100°C	60	Male
VD40-A-M8M	Mark Free	M8	Black	-10°C-100°C	75	Male
VD40-PU-M8M	Polyurethane	M8	Translucent Orange	0°C-60°C	60	Male
VD40-N-M10M	Nitrile	M10	Black	-20°C-110°C	60	Male
VD40-S-M10M	Silicone	M10	Red	-70°C-200°C	55	Male
VD40-WS-M10M	White Silicone	M10	Translucent White	-70°C-200°C	55	Male
VD40-WS-FDA-M10M	White Silicone (FDA)	M10	Translucent White	-70°C-200°C	55	Male
VD40-CS-M10M	Conductive Silicone	M10	Smoky Black	-45°C-90°C	70	Male
VD40-U-M10M	Urethane	M10	Dark Green	0°C-100°C	60	Male
VD40-A-M10M	Mark Free	M10	Black	-10°C-100°C	75	Male
VD40-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD40-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD40-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD40-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD40-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD40-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD40-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD40-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
VD40-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female

Tech Sheet 71786


Dimensions



With M8M fitting




With M10M fitting



With 18F fitting

FT PRO®



For **Storage Range**
see page **1747**

Fluid-Air Components Ltd

SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge

Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting


VD Series




50mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD50-N-M8M	Nitrile	M8	Black	-20°C-110°C	60	Male
VD50-S-M8M	Silicone	M8	Red	-70°C-200°C	55	Male
VD50-WS-M8M	White Silicone	M8	Translucent White	-70°C-200°C	55	Male
VD50-WS-FDA-M8M	White Silicone (FDA)	M8	Translucent White	-70°C-200°C	55	Male
VD50-CS-M8M	Conductive Silicone	M8	Smoky Black	-45°C-90°C	70	Male
VD50-U-M8M	Urethane	M8	Dark Green	0°C-100°C	60	Male
VD50-A-M8M	Mark Free	M8	Black	-10°C-100°C	75	Male
VD50-PU-M8M	Polyurethane	M8	Translucent Orange	0°C-60°C	60	Male
VD50-N-M10M	Nitrile	M10	Black	-20°C-110°C	60	Male
VD50-S-M10M	Silicone	M10	Red	-70°C-200°C	55	Male
VD50-WS-M10M	White Silicone	M10	Translucent White	-70°C-200°C	55	Male
VD50-WS-FDA-M10M	White Silicone (FDA)	M10	Translucent White	-70°C-200°C	55	Male
VD50-CS-M10M	Conductive Silicone	M10	Smoky Black	-45°C-90°C	70	Male
VD50-U-M10M	Urethane	M10	Dark Green	0°C-100°C	60	Male
VD50-A-M10M	Mark Free	M10	Black	-10°C-100°C	75	Male
VD50-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD50-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD50-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD50-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD50-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD50-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD50-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD50-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
VD50-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female
Tech Sheet 71786						


Dimensions



With M8M fitting



With M10M fitting



With 18F fitting



For **Ring Main Parker Transair Tools**
see pages **1064-1067**

Fluid-Air Components Ltd

SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge

Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting


VD Series




60mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD60-N-M8M	Nitrile	M8	Black	-20°C-110°C	60	Male
VD60-S-M8M	Silicone	M8	Red	-70°C-200°C	55	Male
VD60-WS-M8M	White Silicone	M8	Translucent White	-70°C-200°C	55	Male
VD60-WS-FDA-M8M	White Silicone (FDA)	M8	Translucent White	-70°C-200°C	55	Male
VD60-CS-M8M	Conductive Silicone	M8	Smoky Black	-45°C-90°C	70	Male
VD60-U-M8M	Urethane	M8	Dark Green	0°C-100°C	60	Male
VD60-A-M8M	Mark Free	M8	Black	-10°C-100°C	75	Male
VD60-PU-M8M	Polyurethane	M8	Translucent Orange	0°C-60°C	60	Male
VD60-N-M10M	Nitrile	M10	Black	-20°C-110°C	60	Male
VD60-S-M10M	Silicone	M10	Red	-70°C-200°C	55	Male
VD60-WS-M10M	White Silicone	M10	Translucent White	-70°C-200°C	55	Male
VD60-WS-FDA-M10M	White Silicone (FDA)	M10	Translucent White	-70°C-200°C	55	Male
VD60-CS-M10M	Conductive Silicone	M10	Smoky Black	-45°C-90°C	70	Male
VD60-U-M10M	Urethane	M10	Dark Green	0°C-100°C	60	Male
VD60-A-M10M	Mark Free	M10	Black	-10°C-100°C	75	Male
VD60-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD60-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD60-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD60-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD60-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD60-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD60-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD60-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
VD60-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female
Tech Sheet 71786						


Dimensions



With M8M fitting



With M10M fitting




With 18F fitting




70mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD70-PU-M8M	Polyurethane	M8	Translucent Orange	0°C-60°C	60	Male
VD70-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD70-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female
Tech Sheet 71786						


Dimensions



With M8M fitting



With M10M fitting



With 18F fitting

Fluid-Air Components Ltd


SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge


Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting

VD Series


Dimensions



With M8M fitting



With M10M fitting



With 18F fitting





85mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD85-N-M8M	Nitrile	M8	Black	-20°C-110°C	60	Male
VD85-S-M8M	Silicone	M8	Red	-70°C-200°C	55	Male
VD85-WS-M8M	White Silicone	M8	Translucent White	-70°C-200°C	55	Male
VD85-WS-FDA-M8M	White Silicone (FDA)	M8	Translucent White	-70°C-200°C	55	Male
VD85-CS-M8M	Conductive Silicone	M8	Smoky Black	-45°C-90°C	70	Male
VD85-U-M8M	Urethane	M8	Dark Green	0°C-100°C	60	Male
VD85-A-M8M	Mark Free	M8	Black	-10°C-100°C	75	Male
VD85-N-M10M	Nitrile	M10	Black	-20°C-110°C	60	Male
VD85-S-M10M	Silicone	M10	Red	-70°C-200°C	55	Male
VD85-WS-M10M	White Silicone	M10	Translucent White	-70°C-200°C	55	Male
VD85-WS-FDA-M10M	White Silicone (FDA)	M10	Translucent White	-70°C-200°C	55	Male
VD85-CS-M10M	Conductive Silicone	M10	Smoky Black	-45°C-90°C	70	Male
VD85-U-M10M	Urethane	M10	Dark Green	0°C-100°C	60	Male
VD85-A-M10M	Mark Free	M10	Black	-10°C-100°C	75	Male
VD85-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD85-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD85-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD85-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD85-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD85-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD85-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
VD85-N-12F	Nitrile	G1/2"	Black	-20°C-110°C	60	Female
VD85-S-12F	Silicone	G1/2"	Red	-70°C-200°C	55	Female
VD85-WS-12F	White Silicone	G1/2"	Translucent White	-70°C-200°C	55	Female
VD85-WS-FDA-12F	White Silicone (FDA)	G1/2"	Translucent White	-70°C-200°C	55	Female
VD85-CS-12F	Conductive Silicone	G1/2"	Smoky Black	-45°C-90°C	70	Female
VD85-U-12F	Urethane	G1/2"	Dark Green	0°C-100°C	60	Female
VD85-A-12F	Mark Free	G1/2"	Black	-10°C-100°C	75	Female
Tech Sheet 71786						

Fluid-Air Components Ltd


SUCTION CUPS - DEEP

Features & Strengths
- This cup is best suited to curved or irregular surfaces
- Excellent performance for round corners and edge


Suitable for Handling
- Automotive roof and doors
- Shaped sheet metal
- Sheet metals, plastics and veneers
- Pre-mounted fitting

VD Series

Dimensions



With 18F fitting




With 12F fitting




85mm Cups with Fitting (inc. 4 x M6)

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD85X-N-18F	Nitrile	G1/8"	Black	-20°C-110°C	60	Female
VD85X-S-18F	Silicone	G1/8"	Red	-70°C-200°C	55	Female
VD85X-WS-18F	White Silicone	G1/8"	Translucent White	-70°C-200°C	55	Female
VD85X-WS-FDA-18F	White Silicone (FDA)	G1/8"	Translucent White	-70°C-200°C	55	Female
VD85X-CS-18F	Conductive Silicone	G1/8"	Smoky Black	-45°C-90°C	70	Female
VD85X-U-18F	Urethane	G1/8"	Dark Green	0°C-100°C	60	Female
VD85X-A-18F	Mark Free	G1/8"	Black	-10°C-100°C	75	Female
Tech Sheet 71786						


Dimensions




19Ø Hole




With 18F fitting



With 14F fitting



With 38F fitting



With 12F fitting



90mm Cups with Fitting

9204	Material	Connection	Colour	Temperature	Hardness	Type
VD90F-PU-M10M	Polyurethane	M10	Translucent Orange	0°C-60°C	60	Male
VD90F-PU-18F	Polyurethane	G1/8"	Translucent Orange	0°C-60°C	60	Female
VD90F-PU-14F	Polyurethane	G1/4"	Translucent Orange	0°C-60°C	60	Female
VD90F-PU-38F	Polyurethane	G3/8"	Translucent Orange	0°C-60°C	60	Female
VD90F-PU-12F	Polyurethane	G1/2"	Translucent Orange	0°C-60°C	60	Female
VD90F-PU-H19	Polyurethane	19Ø Hole	Translucent Orange	0°C-60°C	60	N/A
Tech Sheet 71786						

SUCTION CUPS, SPECIAL FLAT/BELLOWS

1900 Series


Long bellows suction cup

Specially designed for opening plastic bags. Suitable for handling thin and delicate objects, such as plastic films or paper. The thin and adaptable lip together with the internal plugs avoid damages to the film during the suction phase.

Material: Silicone

Working Temperature:
-40°C to +200°C





VTF Flat Cups with Fittings

0256	Colour	Drawing	Hardness °Shore A	Lifting Force In Vertical Direction (N) -60kPa	Lifting Force In Parallel Direction (N) -60kPa	Stroke mm	Weight g
19VTF.S.05.02000	Blue	A	40	10	6	1.5	4.6
19VTF.S.05.02500	Blue	B	40	25	21	1.5	5.0
19VTF.S.14.03500	Blue	C	40	38	32.5	1.5	10.0
19VTF.S.14.05000	Blue	D	40	92	76	2	25.0

FOOD PACKAGING — PLASTIC BAG

Vacuum technology
Catalogue
Suction cups
Series 1900


Round bellows suction cup made of polyurethane

Round bellows suction cup made of polyurethane, suitable for movement of pieces of various size and shape and where level compensation is necessary, such as when withdrawing from loaders. The big advantage of this suction cup, is that the material it's made of, polyurethane, lasts longer than other materials, has optimum wear resistance, good flexibility and optimum tensile strength. Suitable for moving porous objects or ones with an irregular surface, such as cardboard. Polyurethane suction cups are mark resistant.

Material: PU

Working Temperature:
+10°C to +50°C





VTS Round Bellows with Fittings

0256	Colour	Drawing	D	H	G	h	L_G	Y	S	Hardness °Shore A	Lifting Force In Vertical Direction (N) -20kPa	-60kPa	-90kPa	Weight g
19VTS.P.18.03025	Green	A	30	21.3	G1/8	7.8	6	13		55	10	19	25	6.9
19VTS.P.14.04025	Green	A	40	28.4	G1/4	12	6	17		55	15	50		18.2
19VTS.P.38.05025	Green	A	50	36.5	G3/8	18	10	13.4	24	55	35	50	70	32.6
19VTS.P.38.07025	Green	B	70	58.5	G3/8	18	10	18.6	*	55	72	128	150	60.5

PACKAGING — LONG LIFETIME


Long bellows suction cup for bags

The long bellows suction cup is especially suited for the movement of bags, thanks to its very thin lip and internal notchings, which allow it to ensure secure gripping even with heavy bags that are difficult to lift.

Material: Silicone

Working Temperature:
-40°C to +200°C






VTS Extended Round Bellows with Fittings

0256	Colour	Drawing	D	H	h	L_G	G	S	Hardness °Shore A	Lifting Force In Vertical Direction (N) -60kPa	Weight g
19VTS.S.14.03035	Red	A	30	36.5	6	10	G1/4	19	40	9	17.6
19VTS.S.38.04035	Red	A	40	40	6	10	G3/8	22	40	15	23.6
19VTS.S.12.05035	Red	A	50	55	6	10	G1/2	28	40	25	44.2

FOOD PACKAGING — PLASTIC BAG

Fluid-Air Components Ltd

Foam rubber round suction cup




Suction cups
Series 1900
Vacuum technology
Catalogue

Foam rubber round suction cup


Foam rubber round suction cup is made from a special mixture called "NR", which has a density that allows for gripping even on very rough and irregular surfaces, and allows its elasticity to be maintained even after several working cycles. Especially suited for moving loads with coarse or very rough surfaces such as: sawn, bush-hammered or flamed marble, textured, non-slip or ribbed/corrugated sheets, brick, items made of rough concrete, garden walkway tiles, etc., and in general in all cases where traditional suction cups cannot be used. Recommended for handling loads with lifting force parallel to the surface and for the movement of loads with oiled surfaces.

Material: Foam Rubber (NR)

Working Temperature:
-20°C to +80°C



A



VTN Foam Rubber Round Suction Cup


0256	Colour	Drawing	D	D1	H	H1	G1	L	M	d	G	Hardness °Shore A	Lifting Force In Vertical Direction (N)-60kPa	Weight g
19VTN.G.04000	Orange	A	40	20	25	15	-	-	-	-	G1/4	30	7.8	33.4
19VTN.G.06400	Orange	A	64	40	25	15	-	-	-	40	G1/4	30	35	82.4

Foam rubber rectangular suction cup


Foam rubber rectangular suction cup is made from a special mixture called "NR", which has a density that allows for gripping even on very rough and irregular surfaces, and allows its elasticity to be maintained even after several working cycles. Especially suited for movement of loads with coarse or very rough surfaces such as: sawn, bush-hammered or flamed marble, textured, non-slip or ribbed/corrugated sheets, brick, items made of rough concrete, garden walkway tiles, etc. and in general in all cases where traditional suction cups cannot be used. Not recommended for handling loads with lifting force parallel to the surface or for the movement of loads with oiled surfaces.


Material: Foam Rubber (NR)

Working Temperature:
-20°C to +80°C




A







B




Foam rubber rectangular suction cup

19VRN.G.14.FXR00	Orange	A	135	60	80	40	15	26	G1/4	4-M5	-	30	80	231.7
19VRN.G.14.HXN00	Orange	A	107	75	60	40	15	26	G1/4	4-M5	-	30	90	236.7
19VRN.G.12.RXS00	Orange	B	290	140	80	100	15	26	G1/2	8-M5	2-M12	30	706	1175.1







SUCCTION CUPS

Overall dimensions and technical information are provided solely for informative purposes and may be modified without notice

Suction Cups

SAME AS ABOVE

- Choice of cup designs and material type
- Flat cups ideal where minimal movement is required for pliable materials
- Bellows cups ideal where level compensation is required
- Wide variety of cup sizes

Medium: Vacuum
Cups: Nitrile
Connection Fittings: Aluminium

Working Temperature:
-10°C to +70°C for Aluminium nitrile rubber cups





Flat, M/58000

0036	OD mm	Thread
M/58301/01	6	M5
M/58303/01	10	M5
M/58304/01	15	M5
M/58305/01	20	G1/8
M/58306/01	25	G1/8
M/58307/01	30	G1/8
Tech Sheet 10356		

Bellows, M/58000












0036	OD mm	Thread
M/58403/01	10	M5
M/58405/01	20	G1/8
M/58408/01	40	G1/8
M/58410/01	75	G1/8
Tech Sheet 10356		

Overall dimensions and technical information are provided solely for informative purposes and may be modified without notice

Fluid-Air Components Ltd

FITTINGS













VU/VB/VF/VBL/VBU/VBX/VFC Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 000 3000	M2.5M	Standard		VU2, VU3	0.47
350 000 3100	M5M	Standard		VU2, VU3	0.54
350 000 3101	M5M	Standard		VU4, VU6, VU8, VB5, VB8	1.84
350 000 3102	M5M	Standard		VU10, VU15, VF15, VB10, VB12, VB15, VBL15	2.52
350 010 3102		Built in efficiency valve			2.63
350 000 3321	18FX (For silicone material)	Standard		VU40, VF40	8.46
350 000 3209	M518MF	Standard		VU20, VU25, VU30, VF20, VF25, VF30, VB17, VB20, VBL20	1.82
350 000 5209		Built in mesh-filter			1.92
350 010 4209		Built in efficiency valve			1.94
350 020 4209		Built in button valve			2.21
350 000 1209	M518MFO	Standard		VU20, VU25, VU30, VF20, VF25, VF30, VB17, VB20, VBL20	2.88
350 000 1109		Built in mesh-filter			2.94
350 010 1209		Built in efficiency valve			2.87
350 000 3239	M518MFB (For silicone material)	Standard		VB17, VB20, VBL20	3.56
350 000 3310	18F	Standard		VU20, VU25, VU30, VF20, VF25, VF30, VB17, VB20, VBL20	3.23
350 000 4310		Built in mesh-filter			3.3
350 010 3310		Built in efficiency valve			3.43
350 020 3310		Built in button valve			
350 000 3229	M518MFX (For silicone material)	Standard		VU20, VU25, VU30, VF20, VF25, VF30	3.71
350 000 3311	18F	Standard		VU40, VF40, VB30, VB40, VBL30, VBL40, VBU35, VBU45, VBX35, VBX45	5.62
350 000 4311		Built in mesh-filter			5.72
350 010 3311		Built in efficiency valve			5.86
350 020 3311		Built in button valve			8.97
350 000 2311	18FO	Standard		VU40, VF40, VB30, VB40, VBL30, VBL40, VBU35,VBU45, VBX35, VBX45	8.24
350 000 4811		Built in mesh-filter			8.41

Fluid-Air Components Ltd

FITTINGS











VU/VB/VF/VBL/VBU/VBX/VFC Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 000 3331	18FB (For silicone material)	Standard		VB30, VB40, VBL30, VBL40, VBU35, VBU45	9.78
350 000 2304	18M	Standard		VU40, VF40, VB30, VB40, VBL30, VBL40, VBU35, VBU45, VBX35, VBX45	5.68
350 000 4304		Built in mesh-filter			5.73
350 010 2304		Built in efficiency valve			5.63
350 000 3404	14M	Standard		VU40, VF40, VB30, VB40, VBL30, VBL40, VBU35, VBU45, VBX35, VBX45	5.88
350 000 3804		Built in mesh-filter			5.92
350 010 3404		Built in efficiency valve			6.03
350 000 3504	38M	Standard		VBU35, VBU45, VBX35, VBX45	9.16
350 000 3904		Built in mesh-filter			9.56
350 010 3504		Built in efficiency valve			9.72
350 000 3312	18F	Standard		VU50, VF50 VB50, VBL50 VBU55, VBX55	14.47
350 000 4312		Built in mesh-filter			14.58
350 010 3312		Built in efficiency valve			15.81
350 000 1312	18FO	Standard		VU50, VF50, VB50, VBL50, VBU55, VBX55	10.12
350 000 4912		Built in mesh-filter			10.2
350 010 1312		Built in efficiency valve			10.22
350 000 3405	14M	Standard		VU50, VF50, VB50, VBL50, VBU55, VBX55	14.18
350 000 3805		Built in mesh-filter			14.42
350 010 3405		Built in efficiency valve			14.38
350 000 3505	38M	Standard		VU50, VF50, VB50, VBL50, VBU55, VBX55	18.14
350 000 3905		Built in mesh-filter			17.75
350 010 3505		Built in efficiency valve			17.53
350 000 3342	18FB2 (For silicone material)	Standard		VBU35, VBU45	5.4
350 000 3442		Built in mesh-filter			5.5
350 010 3342		Built in efficiency valve			5.64
350 000 3341	18MB2 (For silicone material)	Standard		VBU35, VBU45	5.44
350 000 4341		Built in mesh-filter			5.33
350 010 3341		Built in efficiency valve			5.47
350 010 3342	18FB2 (For silicone material)	Built in efficiency valve		VBU55, VBX55	15.95
350 000 3441	14MB2 (For silicone material)	Standard		VBU35, VBU45	5.88
350 000 3841		Built in mesh-filter			6
350 010 3441		Built in efficiency valve			6.14

Fluid-Air Components Ltd

FITTINGS




VU/VB/VF/VBL/VBU/VBX/VFC Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 000 3443	14MB2 (For silicone material)	Standard		VBU55	16.69
350 000 3843		Built in mesh-filter			17.22
350 010 3441		Built in efficiency valve			17.26
350 000 3543	38MB2 (For silicone material)	Standard		VBU55	16.69
350 000 3943		Built in mesh-filter			17.05
350 010 3543		Built in efficiency valve			17.11
350 000 3323	18F	Standard		VB75, VB75B, VF75, VF90, VFC90, VFC100	59.36
350 000 4323		Built in mesh-filter			59.76
350 020 3323		Built in button valve		VF75, VF90	83.56
350 000 3423	14F	Standard		VB75, VB75B, VF75, VF90, VFC90, VFC100	56.92
350 000 3823		Built in mesh-filter			57.32
350 000 3523	38F	Standard		VB75, VB75B, VF75, VF90, VFC90, VFC100	55.08
350 000 3923		Built in mesh-filter			55.48
350 000 3623	12F	Standard		VB75, VB75B, VF75, VF90, VFC90, VFC100	51.50
350 000 4023		Built in mesh-filter			51.90
350 000 3614	12F	Standard		VB110, VB110B, VF110	103.70
350 000 4014		Built in mesh-filter			10.50
350 020 3614		Built in button valve		VF110	115.54
350 000 3615	12F	Standard		VB150, VF150	198.93
350 000 4015		Built in mesh-filter			199.73
350 020 3615		Built in button valve		VF150	314.47
350 000 1405	M16M	Standard		VF50X2	52.23
350 000 3616	12F	Standard		VF200	555
350 000 4016		Built in mesh-filter			555.3


Fluid-Air Components Ltd

FITTINGS

BL5040 Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 005 0101	18F	Standard		BL5040	11.24
350 005 0103		Built in mesh-filter			11.27
350 005 0202	14M	Standard		BL5040	7.92
350 005 0204		Built in mesh-filter			8.96
350 005 0302	38M	Standard		BL5040	11.47
350 005 0304		Built in mesh-filter			11.51

VOBL35x90 Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 000 3660	12F	Standard		VOBL35x90	18.7

VOU Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 002 1012	M5M	Standard		VOU4x20, VOU6X20, VOU8X20, VOU8X30, VOU10X30	1.78
350 002 1112	M5F	Standard		VOU4x20, VOU6X20, VOU8X20, VOU8X30, VOU10X30	2.82
350 002 3021	18M	Standard		VOU15x45, VOU20X60	13.74
350 002 3022		Built in mesh-filter			13.84
350 002 3121	18F	Standard		VOU15x45, VOU20X60	10.32
350 002 3122		Built in mesh-filter			10.46

FF Series

9205	Type	Description	Dimension	Available suction cups	Weight (g)
350 007 0101	M5M	Standard		FF15	1.41
350 007 0102	M5M	Standard		FF20, FF25, FF30	2.59
350 007 0103	M5M	Standard		FF15X, FF20X	2.41


Fluid-Air Components Ltd

SUCTION CUPS - FITTINGS

BL5040 Series

9205
350 005 0101
350 005 0103
350 005 0202
350 005 0204
350 005 0302
350 005 0304


Dimensions



VOBL 35 x 90 Series

9205
350 000 3660


Dimensions



VOU Series

9205
350 002 1012
350 002 1112
350 002 3021
350 002 3022
350 002 3121
350 002 3122


Dimensions



FF Series

9205
350 007 0101
350 007 0102
350 007 0103

Dimensions



Fluid-Air Components Ltd

VACUUM PUMPS - TECHNICAL INFORMATION

Green Pumps

- VMECA vacuum cartridge technology integrated
- High polished clean surface (= for food, pharma industry)
- Vacuum filter self-cleaning system

Features & Strengths

- Highly operational reliability despite fluctuating or low compressed-air pressure
- Integrated vacuum filter with high dirt capacity and auto-cleaning system
- High polished clean surface for food, pharma and chemical industry
- Easy to install in limited space due to compact size
- Quick response time



GS Range

9205	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
						Air supply	Vacuum	Exhaust
GS203	90	3 - 4	85.8	21 - 32	52 - 58	4 - 6	6	8
GS252	94	5 - 6	113	70.5 - 83.5	60 - 68	6 - 8	6	10
GS253	94	5 - 6	146	70.5 - 83.5		6 - 8	8	10
GS302	93	3 - 4	171	97 - 152		6 - 8	8	10
GSL302	75	4 - 6	200	70 - 104		6 - 8	8	10

- VMECA vacuum cartridge technology integrated
- High polished clean surface (= for food, pharma industry)
- Vacuum filter self-cleaning system

Features & Strengths

- Dual vacuum cartridge structure
- Highly operational reliability despite fluctuating or low compressed-air pressure
- Integrated vacuum filter with high dirt capacity and auto-cleaning system
- High polished clean surface for food, pharma and chemical industry
- Easy to install in limited space due to compact size
- Quick response time



GH Range

9205	Max. Vacuum level (-kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
						Air supply	Vacuum	Exhaust
GH203	90	3 - 4	172	40 - 64	52 - 58	6 - 8	8	10
GH252	94	5 - 6	222	141 - 167	60 - 68	6 - 8	8	10
GH253	94	5 - 6	292	141 - 167		6 - 8	8	10
GH302	93	3 - 4	343	194 - 304		6 - 8	8	10
GHL302	75	4 - 6	400	140 - 208		6 - 8	8	10

VSM Pumps

- VMECA vacuum cartridge technology integrated
- Various mounting options for easy installation
- Extremely low noise level

Features & Strengths

- Efficient individual and independent point-of-use vacuum
- Highly operational reliability despite fluctuating or low compressed-air pressure
- Extremely quick response
- Available for multiple connection ports
- Extremely low noise level with VMECA twofold silencer



VSM Range

9205	Vacuum Connection	Type	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
								Air supply	Vacuum	Exhaust
VSM202	3/8" (x1), 1/8" (x3)	Holding Plug	90	3 - 4	44	22 - 40.5	55 - 65	8	8	8
VSM203	3/8" (x1), 1/8" (x3)	Silencer	90	3 - 4	84.5	21 - 40		8	8	10
VSM303	1/2" (x1), 1/4" (x3)	Silencer	92	4	341	82 - 152		8	12	14

Please contact our sales office for full technical information

VACUUM PUMPS

VCS Pumps

- VMECA vacuum cartridge technology integrated
- Level compensator and vacuum ejector in one body

Features & Strengths

- Built in level compensator in one body
- Highly operational reliability despite fluctuating or low compressed air pressure
- Quick response time
- Compact size and light weight



VCS Range

9205	Male Thread	Female Thread	Check Valve	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
									Air supply	Vacuum	Exhaust
VCS102	M5	N/A	No	85	1.2 - 2.6	16.5	6.8 - 10.6	55 - 65	4 - 6	8	6
VCS102C	N/A	G1/8"	Yes	85	1.2 - 2.6	16.5	6.8 - 10.6	55 - 65	4 - 6	8	6

Premium Pumps

- VMECA vacuum cartridge technology integrated
- High vacuum flow with durable aluminium body

Features & Strengths

- Highly operational reliability despite fluctuating or low compressed air pressure
- Top and side vacuum connection ports available
- Optional air-saving kit available to minimise energy consumption
- Quick response time
- Strong aluminium body



PM Range with Side Vacuum Port

9205	No. of Cartridges	Thread	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
								Air supply	Vacuum	Exhaust
PM303X1	1	G1"	92	3 - 4	341	97 - 158	60 - 65	8	12	12
PM303X2	2	G1"	92	3 - 4	682	194 - 340		8	15	15
PM303X3	3	G1"	92	3 - 4	1023	291 - 456		10	19	22
PM303X4	4	G1"	92	3 - 4	1364	388 - 608		10	22	32

- VMECA vacuum cartridge technology integrated
- Large vacuum flow with up to 16 VMECA vacuum cartridge

Features & Strengths

- Highly operational reliability despite fluctuating or low compressed-air pressure
- High vacuum flow with low energy consumption
- Available to replace 4kw(5Hp) electric motor pump
- Very low noise level
- Durable and light aluminium body



MPM Range without Vacuum Filter

9205	No. of Cartridges	Thread	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
								Air supply	Vacuum	Exhaust
MPM303X6	6	G2"	93	3 - 4	2048	804	55 - 62	11	35	40
MPM303X8	8	G2"	93	3 - 4	2728	1072	55 - 62	11	40	40
MPM303X10	10	G2"	93	3 - 4	3410	1340	55 - 62	11	40	45
MPM303X12	12	G2"	93	3 - 4	4092	1608	55 - 62	12	40	50
MPM303X14	14	G2"	93	3 - 4	4774	1876	55 - 62	13	45	50
MPM303X16	16	G2"	93	3 - 4	5456	2144	55 - 62	14	35	60

Please contact our sales office for full technical information

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

VACUUM PUMPS

Magic Pumps

- VMECA vacuum cartridge technology integrated
- Flexibly rotatable vacuum pump
- Easy to distribute vacuum connections with integrated distribution body module

Features & Strengths

- Highly operational reliability despite fluctuating or low compressed-air pressure
- Integrated pleated filter with high dirt capacity and auto-cleaning system
- Flexible structure available to select various port options and port position/direction
- Easy to assemble and disassemble without any tools
- Quick response time
- Patented design



M3000 Range

9205	No. of Cartridges	Thread	Stage	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
									Air supply	Vacuum	Exhaust
M3122	2	G3/4"	2	92	3 - 4	342	194 - 304	50 - 60	8	15	15
M3123	3	G3/4"	2	92	3 - 4	513	291 - 456		10	19	22
M3124	4	G3/4"	2	92	3 - 4	684	388 - 608		10	22	32
M3132	2	G3/4"	3	92	3 - 4	682	194 - 304		8	15	15
M3133	3	G3/4"	3	92	3 - 4	1023	291 - 456	50 - 60	10	19	22
M3134	4	G3/4"	3	92	3 - 4	1364	388 - 608		10	22	32

Turtle Pumps

- VMECA vacuum cartridge technology integrated
- Vacuum filter in one body with auto filter cleaning system

Features & Strengths

- Highly operational reliability despite fluctuating or low compressed-air pressure
- Integrated pleated filter with high dirt capacity and auto-cleaning system
- Optional air-saving kit available to minimise energy consumption
- Quick response time
- Patented design



VTC Range

9205	No. of Cartridges	Thread	Silencer	Stage	Max. Vacuum level (- kPa)	Supply Air Pressure (bar)	Max. Vacuum Flow(Nl/m)	Air Consumption (Nl/m)	Noise level (dBA)	Min. hose inner Ø (within 2m)		
										Air supply	Vacuum	Exhaust
VTC3021-2	1	G3/4"	-	2	92	3 - 4	171	97 - 152	50 - 60	6	8	10
VTC3031-2	1	G3/4"	Two Fold	3	92	3 - 4	341	97 - 152		6	8	10
VTC3122-2	2	G3/4"	Standard	2	92	3 - 4	342	194 - 304	60 - 65	8	15	15
VTC3032-2	2	G3/4"	Two Fold	3	92	3 - 4	682	194 - 304		8	12	18
VTC3022-2	2	G3/4"	-	3	92	3 - 4	342	194 - 304		8	12	18
VTC3132-2	2	G3/4"	Standard	3	92	3 - 4	682	194 - 304		8	15	15
VTC3123-2	3	G3/4"	Standard	2	92	3 - 4	513	291 - 456		10	19	22
VTC3133-2	3	G3/4"	Standard	3	92	3 - 4	1023	291 - 456		10	19	22
VTC3124-2	4	G3/4"	Standard	2	92	3 - 4	684	388 - 608		10	22	32
VTC3134-2	4	G3/4"	Standard	3	92	3 - 4	1364	388 - 608		10	22	32

Please contact our sales office for full technical information

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

VACUUM GRIPPERS - MAGIC GRIPPERS

Features & Strengths

- Reliable performance despite inconsistent compressed air pressure
- Extremely compact and light weight
- Low air consumption
- Various mounting options
- Excellent gripping power
- Various suction lips for different applications

A-Type - Single Cartridge



Micro Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC10A1-20	20	Nitrile
MC10A2-20	20	Nitrile
MC10A1-40	40	Nitrile
MC10A2-40	40	Nitrile

Mini Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC20A1-40	40	Nitrile
MC20A2-40	40	Nitrile
MC20A1-60	60	Nitrile
MC20A2-60	60	Nitrile

Mini Cartridge, 3-Stage

9205	Bellow Size mm	Material
MC23A1-40	40	Nitrile
MC23A2-40	40	Nitrile
MC23A1-60	60	Nitrile
MC23A2-60	60	Nitrile

Mini Premium Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC25A1-40	40	Nitrile
MC25A2-40	40	Nitrile
MC25A1-60	60	Nitrile
MC25A2-60	60	Nitrile

B Type - Single Cartridge/Auto Vac Release



Micro Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC10B1-20	20	Nitrile
MC10B2-20	20	Nitrile
MC10B1-40	40	Nitrile
MC10B2-40	40	Nitrile

Mini Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC20B1-40	40	Nitrile
MC20B2-40	40	Nitrile
MC20B1-60	60	Nitrile
MC20B2-60	60	Nitrile

Mini Cartridge, 3-Stage

9205	Bellow Size mm	Material
MC23B1-40	40	Nitrile
MC23B2-40	40	Nitrile
MC23B1-60	60	Nitrile
MC23B2-60	60	Nitrile

Mini Premium Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC25B1-40	40	Nitrile
MC25B2-40	40	Nitrile
MC25B1-60	60	Nitrile
MC25B2-60	60	Nitrile

Fluid-Air Components Ltd

VACUUM GRIPPERS - MAGIC GRIPPERS

Features & Strengths

- Reliable performance despite inconsistent compressed air pressure
- Extremely compact and light weight
- Low air consumption
- Various mounting options
- Excellent gripping power
- Various suction lips for different applications

C Type – Single Cartridge/Check Valve



Micro Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC10C1-20	20	Nitrile
MC10C2-20	20	Nitrile
MC10C1-40	40	Nitrile
MC10C2-40	40	Nitrile

Mini Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC20C1-40	40	Nitrile
MC20C2-40	40	Nitrile
MC20C1-60	60	Nitrile
MC20C2-60	60	Nitrile

Mini Cartridge, 3-Stage

9205	Bellow Size mm	Material
MC23C1-40	40	Nitrile
MC23C2-40	40	Nitrile
MC23C1-60	60	Nitrile
MC23C2-60	60	Nitrile

Mini Premium Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC25C1-40	40	Nitrile
MC25C2-40	40	Nitrile
MC25C1-60	60	Nitrile
MC25C2-60	60	Nitrile

D-Type - Dual Cartridge



Micro Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC10D1-20	20	Nitrile
MC10D2-20	20	Nitrile
MC10D1-40	40	Nitrile
MC10D2-40	40	Nitrile

Mini Cartridge, 2-Stage

9205	Bellow Size mm	Material
MC20D1-40	40	Nitrile
MC20D2-40	40	Nitrile
MC20D1-60	60	Nitrile
MC20D2-60	60	Nitrile

Mini Cartridge, 3-Stage

9205	Bellow Size mm	Material
MC23D1-40	40	Nitrile
MC23D2-40	40	Nitrile
MC23D1-60	60	Nitrile
MC23D2-60	60	Nitrile

Parker legris LIQUIfit™



For **Parker Leak Free Liquifit Push-in Fitting** see pages **800-803**

Fluid-Air Components Ltd

VACUUM GRIPPERS - MAGIC GRIPPERS

Suction Lips

- X type suction lips are excellent in handling thin and light plastic bag applications such as ice cream bags and aluminium foil.



X Type

9205	Ø mm	Material
X25-N6	25	Nitrile
X30-N6	30	Nitrile
X45-N6	45	Nitrile
X55-N6	55	Nitrile
X65-N6	65	Nitrile
X75-N6	75	Nitrile
X25-S3	25	Silicone
X30-S3	30	Silicone
X45-S3	45	Silicone
X55-S3	55	Silicone
X65-S3	65	Silicone
X75-S3	75	Silicone
X25-W3	25	White Silicone
X30-W3	30	White Silicone
X45-W3	45	White Silicone
X55-W3	55	White Silicone
X65-W3	65	White Silicone
X75-W3	75	White Silicone

- P type suction lips are excellent in handling heavy or thick plastic bags containing liquid and powder substances.
- Various stopper and lip material options to cover a wide range of vacuum applications.



P Type

9205	Ø mm	Material
P15-N6	15	Nitrile
P17-N6	17	Nitrile
P20-N6	20	Nitrile
P27-N6	27	Nitrile
P32-N6	32	Nitrile
P48-N6	48	Nitrile
P60-N6	60	Nitrile
P15-S3	15	Silicone
P17-S3	17	Silicone
P20-S3	20	Silicone
P27-S3	27	Silicone
P32-S3	32	Silicone
P48-S3	48	Silicone
P60-S3	60	Silicone
P85-S3	85	Silicone
P15-W3	15	White Silicone
P17-W3	17	White Silicone
P20-W3	20	White Silicone
P27-W3	27	White Silicone
P32-W3	32	White Silicone
P48-W3	48	White Silicone
P60-W3	60	White Silicone

- U type suction lips are excellent in handling flat an slightly curved objects such as carton boxes and tubes.



U Type

9205	Ø mm	Material
U25-N6	25	Nitrile
U30-N6	30	Nitrile
U45-N6	45	Nitrile
U55-N6	55	Nitrile
U65-N6	65	Nitrile
U75-N6	75	Nitrile
U25-S3	25	Silicone
U30-S3	30	Silicone
U45-S3	45	Silicone
U55-S3	55	Silicone
U65-S3	65	Silicone
U75-S3	75	Silicone
U25-W3	25	White Silicone
U30-W3	30	White Silicone
U45-W3	45	White Silicone
U55-W3	55	White Silicone
U65-W3	65	White Silicone
U75-W3	75	White Silicone

Stoppers - A-Type



To Suit X Type Lips

9205	Stopper Size mm
MS20-A	20
MS40-A	40
MS60-A	60

Stoppers - A-Type



To Suit U & X Type Lips

9205	Stopper Size mm
MS20-B	20
MS40-B	40
MS60-B	60

Stoppers - C-Type



To Suit U & X Type Lips

9205	Stopper Size mm
MS20-C	20
MS40-C	40
MS60-C	60

Stoppers - C-Type



To Suit P, U & X Type Lips

9205	Stopper Size mm
MS20-D	20
MS40-D	40
MS60-D	60

NB: Other materials available on request

Fluid-Air Components Ltd

IN-LINE VACUUM FILTER

These filters provide a cost effective in-line vacuum filtration method.
The 6mm push fit version is useful for individual lines particularly with the Oneline pump and multiple stack pumps. The 3/8" version can be screwed directly into the mini type vacuum pump as well as any other port using a 3/8" BSP connection. When used with the mini pumps and midi multiple pumps, it provides a very compact set up.

Features & Strengths

- Simply pushing the tube into the LV-filter
- No other operation is required
- Excellent filtering - minimum particle : 20 micron
- Easy to check and replace filter element

Body Material: Polycarbonate (PC)



Specification


Model	Tube size (mm) (Outer diameter)	Removal efficiency (μ)	Filter area (mm²)	Temperature (°C)	Weight (g)
VTF-0706	6	10	7.5	0 to +60	25.0
VTF-1208	8	10	12.5	0 to +60	39.5

Dimensions

Model	L	D1	D2	F1	F2
VTF-0706	55.5	Ø6	Ø18.5	10	20
VTF-1208	65.2	Ø8	Ø22.5	14	44

Unit: mm

Dimensions



Square Parts - Filter Element

Model	Description	Weight (g)
VTFE0706	Filter Element for VTF-0706	0.74
VTFE1208	Filter Element for VTF-1208	1.2

VTF Filters

9205	OD (mm)
VTF-0706	6
VTF-1208	8

VTFB Filters

9205	Flow Rate (l/m)	Vacuum Connection
VTF38-96	660	G3/8"
VTF38-141	780	G3/8"
VTF12-96	900	G1/2"
VTF12-141	1080	G1/2"
VTF34-96	900	G3/4"
VTF34-141	1320	G3/4"
VTF01-118	2520	G1"
VTF01-154	3480	G1"
VTF02-118	2880	G1.1/2"
VTF02-154	5100	G1.1/2"

VTF Replacement Elements - Polyester

9205	To Suit
VTFE27.5-39096	VTF38-96, 12-96, 34-96
VTFE27.5-39141	VTF38-141,12-141, 34-141
VTFE47.4-62118	VTF01-118, 02-118
VTFE47.4-62154	VTF01-154, 02-154

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INTERCHANGE FILTER ELEMENTS

Vacuum Pump Filters

BSP

9156	d1	Male/ Female	d2 mm	h1 mm	h2 mm	Dh3 mm	h4 mm	Flow Rate m³/h	Element ref
SA6654	G3/8"	F	80	66	12	39	45	24	SA6715
SA6058	G3/4"	F	110	76	14	53	54	42	SA6091
SA6647	G1/2"	F	110	76	14	53	54	42	SA6091
SA6952	G1"	F	133	85	17	53	78	85	SA6120
SA6059	G1.1/4"	F	133	85	17	53	78	96	SA6120
SA6061	G1.1/4"	F	170	141	17	93	96	108	SA6122
SA6648	G1.1/2"	F	170	170	18	124	100	192	SA6651
SA6649	G2"	F	200	240	18	124	114	310	SA6096
SA6060	G2.1/2"	F	200	240	18	124	114	360	SA6096
SA6650	G3"	F	270	180	50	145	165	550	SA6095
SA6652	G4"	F	270	180	50	145	165	720	SA6095
SA6749	G3"	F	280	395	50	330	190	1080	SA6005
SA6750	G4"	F	360	590	50	400	230	1260	SA6005



Please request a technical data sheet.

Vacuum Pump Spare Filter Elements

BSP

9156	To Suit
SA6715	Element for SA6654
SA6091	Element for SA6647 & SA6058
SA6120	Element for SA6952 & SA6059
SA6122	Element for SA6061
SA6651	Element for SA6648
SA6096	Element for SA6649 & SA6060
SA6095	Element for SA6650 & SA6652
SA6005	Element for SA6749
SA6025	Element for SA6750




In-line Vacuum Filter

(1) Flow rates measured with 10 mbar pressure loss

(2) C = paper
R = stainless steel net

(3) Metallic frame



BSP

9032	Flow Rate m³/h	A inches	B mm	C mm	Element (2)	Weight kg
9001003	12	G1/4"	82	62	C	0.16
9001004	12	G1/4"	76	62	R	0.13
9001069	12	G1/4"	74	62	C	0.13
9001004/0	12	G3/8"	76	62	R	0.13
9001009	24	G3/8"	138	85	C	0.37
9001070	24	G3/8"	117	80	C	0.37
9001008	30	G1/2"	88	85	R	0.25
9001010	30	G1/2"	88	80	C	0.25
9001030	90	G1"	240	145	C	1.16
9001016	90	G1"	175	120	R	0.85

In-line Vacuum Spare Filter Elements

(2) C = paper
R = stainless steel net

Spare Filter Elements

9032	Element to Suit Nl/min(1)	µm	Element (2)	Temperature Maximum °C
1801001	9001069, 9001003	30	C	80
1803002	9001004, 9001004/0	100	R	50
1802003	9001008	44	R	50
1801006	9001009, 9001010	30	C	50
1802011	9001016	60	R	50
1801047	9001070	15	C	80
1801021	9001030	25	C	50



Blower Intake Filter

Female

9033	Female Thread	A	D	H	S	L	M	Capacity m³/h
FL1	1/2"	75	21	62	23	100	15	25
FL2	3/4"	150	27	105	23	130	15	85
FL3	1"	150	33	105	23	130	15	85
FL4	1.1/4"	150	42	105	23	200	15	85
FL5	1.1/2"	180	48	155	23	200	15	250
FL6	2"	230	60	155	23	200	15	400
FL8	3"	280	89	180	35	200	15	700
FL9	4"	410	114	330	35	200	15	1400




Blower Intake Spare Filter Elements

Spare Filter Elements

9033	Element For	A	D	H
CF1	FL1	55	25	50
CF4	FL2, FL3, FL4	110	55	83
CF5	FL5	150	80	135
CF6	FL6	180	80	135
CF8	FL8	225	100	150
CF9	FL9, FL10	300	215	300



High Volume Muffler




Type SS



Pump Mounted, Male

9033	D	A	B	C	E
SS4	G1.1/4"	190	138	69	52
SS5	G1.1/2"	200	168	80	32
SS6	G2"	230	198	89	32
SS8	G3"	390	350	152	40



Type SI



In-line, Male x Male

9033	D	A	B	C	E
SI4	G1.1/4"	242	138	69	52
SI5	G1.1/2"	232	168	80	32
SI6	G2"	262	198	89	32
SI8	G3"	430	350	152	40

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 **Push-in Fittings & Tubing** 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 6

Push-in Fittings & Tubing

6.01 Plastic Push-in Fittings 763-842

6.02 Metal Push-in Fittings 843-874

6.03 Stainless Steel Push-in Fittings 875-879

6.04 Plumbing Push-in Fittings 880-886

6.05 Air Brake Push-in Fittings 887-894

6.06 Polyurethane & Nylon Tubing 895-918

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 6

6.01 Plastic Push-in Fittings

763-842

- One Touch Emergency Fittings Kits
- One Touch Plastic (Metric)
- One Touch NPT Plastic (Imperial)
- One Touch+ Emergency Fittings Kits (16 bar rated)
- Micro One Touch (Metric)
- Mirco One Touch (Imperial) NPT & UNI
- Check & Stop Valves
- LF 3000®
- Leak Free
- NPT Threads x Imperial Tube
- BSP Threads x Metric Tube
- Flow Control Regulators Polymer Version
- Flow Control Regulators & Function Fittings
- QS Standard Series
- QS Miniature Series
- Function Fittings
- 55000 Series (20 bar Rated)
- 55000 Series Metal Body
- 55000 Series Miniature
- Metric Push-in Fittings
- Technopolymer
- Push-in Fittings Kits
- Flow Micro Regulators
- Block Fittings
- Flow Control Valves
- Functional Fittings Series 7000 Super Rapid
- Compact Fittings
- Push-in Fittings (Metric)
- Push-in Fittings (Imperial)



6.02 Metal Push-in Fittings

843-874

- One Touch Emergency Fittings Kits
- One Touch All Metal, LF 3600®
- Centralised Lubrication System Fittings
- 50000 Series - Brass
- 89000 Series Imperial Tube Fittings
- 50000 Series Metal Body
- 50000 Series Brass
- 58000 Series High Pressure Lubrication Fittings
- Food Grade
- Pneufi ® Push-in Fittings (Metric/Imperial)
- Non Return Valves & Fittings
- Food Grade Fittings
- Nickel Plated Brass & Technoplymer
- Metric Push-in Fittings
- Nickel Plated Brass
- Super-Rapid
- Push-in Fittings
- Series 8000 Super-Rapid Fittings
- Series H8000 Dual Seal Super-Rapid Fittings



6.03 Stainless Steel Push-in Fittings

875-879

All seals have FDA Certification

stainless steel

- One Touch All Stainless Steel Push-in Fittings
- 316 Stainless Steel Push-in Fittings



Fluid-Air Components Ltd

6.04 Plumbing Push-in Fittings

Speedfit · John Guest · Hep2O

880-886

- Plastic Push-in Fittings
- Plastic Push-in Fittings Pipes & Cutters
- Fitting Valves Piping & Accessories Range
- Brass Push-in Plumbing Tube Fittings



6.05 Air Brake Push-in Fittings

SIRIT AIR BRAKE FITTINGS · CAMOZZI Automation

887-894

- Air Brake Fittings
- Air Brake Swivel Fittings
- Air Brake Threaded Fittings C Truck 9000 Series
- Air Brake Accessories C Truck 9000 Series



6.06 Polyurethane & Nylon Tubing

FT PRO · Parker · legris · LIQUIfit™ · John Guest · Parker · legris · Synflex by Danfoss

895-918

- Polyurethane Tube
- Polyurethane Recoil Hoses, Polyurethane Tube & Assemblies
- Polyurethane Anti-Spatter Tube & Hose
- Tube & Hose Cutters
- Tubing
- Specialist Tubing
- Automotive Tubing & Hose
- Festo Polyurethane Tubing
- Nylon Tubing & Tube Cutters
- Nylon Tubing
- LLDPE & Synflex ube



PLASTIC PUSH-IN FITTINGS

BSP & Metric Threads x Metric Tube



Features:

- Convenient One Touch fittings provide instant connections
- Elliptical release ring facilitates pneumatic installation in confined spaces
- Light manual pressure on the elliptical release ring is all that is required to instantly disconnect each tube; no special tools required
- Nickel-plated brass threaded body ensures anti-corrosion and anti-contamination
- All taper threaded fittings are pre-coated with PTFE sealant and require no additional sealing

Working Temperature:
0°C to +60°C

Maximum Working Pressure
10 bar (150 psi)

Construction:

Resin Body:	PBT
Metal Body:	Nickel-plated brass
Packing:	Nitrile
Back Ring:	POM
O-Ring:	Nitrile
Collar:	Nickel-plated zinc
Sleeve:	POM
Locking Claw:	Stainless steel
Media:	Air and vacuum
Threads:	BSPP, BSPT, metric
OD:	Metric

Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

PLASTIC PUSH-IN FITTINGS

One Touch Emergency Fittings Kits

FT PRO®

Convenient, compact boxes containing a selection of popular FT Pro One Touch plastic push-in fittings along with handy tube cutter.

Available in three sizes: 6mm, 8mm and 10mm. Can be used with nylon 6, 11, 12, and polyurethane (ester and ether).

Working Temperature:
Brass & Acetal:
0°C to +60°C*

Maximum Working Pressure:
10 bar (150 psi)*
Negative Pressure:
-750mm Hg (10 Torr)*



Media:
Air and vacuum only.

Plastic Push-in

1060	OD mm
FTP-06MMBOX-P	6
FTP-08MMBOX-P	8
FTP-10MMBOX-P	10
Tech Sheet 1964	

*Dependent upon tubing specification.

Contents:

6mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	10 x Equal Tees 2019-8404	10 x Equal Connectors 2019-8305	2 x Equal Bulkheads 2019-8503
8 x Equal Elbows 2019-8354	8 x 1/8" BSPP Male Stud Elbows 2028-8247	5 x 1/4" BSPP Male Stud Elbows 2028-8254	
2 x 1/8" BSPT Flow Controllers 2022-9852	2 x 1/4" BSPT Flow Controllers 2022-9878	2 x Flow Controllers (Unidirectional) 2022-9746	
10 x 1/8" BSPT Male Studs 2019-4965	10 x 1/4" BSPT Male Studs 2019-4973	2 x Shut Off Valves (Tube x Tube) HVFF06-06	
5 x M5 BSPT Male Studs 2019-4957	10 x 1/8" BSPP Male Studs 2028-7819	10 x 1/4" BSPP Male Studs 2028-7843	

8mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	8 x Equal Tees 2019-8412	10 x Equal Connectors 2019-8313	2 x Equal Bulkheads 2019-8511
6 x Equal Elbows 2019-8362	6 x 1/8" BSPP Male Stud Elbows 2028-8270	5 x 1/4" BSPP Male Stud Elbows 2028-8288	
2 x 1/8" BSPT Flow Controllers 2022-9886	2 x 1/4" BSPT Flow Controllers 2022-9894	2 x Flow Controllers (Unidirectional) 2022-9753	
10 x 1/8" BSPT Male Studs 2019-4999	10 x 1/4" BSPT Male Studs 2019-5004	2 x Shut Off Valves (Tube x Tube) HVFF08-08	
5 x 3/8" BSPT Male Studs 2019-5012	10 x 1/8" BSPP Male Studs 2028-7876	10 x 1/4" BSPP Male Studs 2028-7884	

10mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	2 x Flow Controllers (Unidirectional) 2022-9761	8 x Equal Connectors 2019-8321
3 x Equal Elbows 2019-8370	3 x 1/8" BSPP Male Stud Elbows 2028-8312	3 x 1/4" BSPP Male Stud Elbows 2028-8320
2 x 1/4" BSPT Flow Controllers 2022-9928	1 x 3/8" BSPT Flow Controller 2022-9936	2 x Equal Tees 2019-8420
7 x 1/8" BSPT Male Studs 2019-5038	7 x 1/4" BSPT Male Studs 2019-5046	2 x Equal Bulkheads 2019-8529
5 x 3/8" BSPT Male Studs 2019-5053	8 x 1/8" BSPP Male Studs 2028-7926	6 x 1/4" BSPP Male Studs 2028-7934

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10 Torr)

Male Studs



Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-4890	4	M5
2019-4932	4	1/8"
2046-7163	4	M6
2019-4940	4	1/4"
2046-7164	4	3/8"
2019-4957	6	M5
2019-4965	6	1/8"
2046-7165	6	M6
2019-4973	6	1/4"
2019-4981	6	3/8"
2046-7166	6	1/2"
2019-4999	8	1/8"
2019-5004	8	1/4"
2019-5012	8	3/8"
2019-5020	8	1/2"
2019-5038	10	1/8"
2019-5046	10	1/4"
2019-5053	10	3/8"
2019-5061	10	1/2"
2019-5076	12	1/4"
2019-5087	12	3/8"
2019-5095	12	1/2"
2019-5096	16	3/8"
2019-5097	16	1/2"
Tech Sheet 1964		



Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-0010	4	M5
2019-0011	4	M6
2019-0012	4	1/8"
2019-0013	4	1/4"
2019-0014	6	M5
2019-0015	6	M6
2019-0016	6	1/8"
2019-0017	6	1/4"
2019-0018	6	3/8"
2019-0019	6	1/2"
2019-0020	8	1/8"
2019-0021	8	1/4"
2019-0022	8	3/8"
2019-0023	8	1/2"
2019-0024	10	1/8"
2019-0025	10	1/4"
2019-0026	10	3/8"
2019-0027	10	1/2"
2019-0028	12	1/4"
2019-0029	12	3/8"
2019-0030	12	1/2"
2019-0031	16	3/8"
2019-0032	16	1/2"



Male Thread, BSPP

1060	OD mm	Thread
2028-7736	4	1/8"
2028-7793	4	1/4"
2028-7819	6	1/8"
2028-7843	6	1/4"
2028-7868	6	3/8"
2028-7876	8	1/8"
2028-7884	8	1/4"
2028-7900	8	3/8"
2028-7918	8	1/2"
2028-7926	10	1/8"
2028-7934	10	1/4"
2028-7942	10	3/8"
2028-7959	10	1/2"
2028-7967	12	1/4"
2028-7975	12	3/8"
2028-7983	12	1/2"
2028-7986	16	3/8"
2028-7987	16	1/2"
Tech Sheet 1964		

Female Studs



Female Thread, BSPP

1060	OD mm	Thread
2019-6325	4	1/8"
2046-7167	4	1/4"
2019-6366	6	1/8"
2019-6416	6	1/4"
2019-6432	6	3/8"
2019-6440	8	1/8"
2019-6465	8	1/4"
2019-6721	8	3/8"
2046-7168	8	1/2"
2019-6739	10	1/8"
2019-6754	10	1/4"
2019-6911	10	3/8"
2046-7169	10	1/2"
2019-6929	12	1/4"
2019-7018	12	3/8"
2019-7059	12	1/2"
Tech Sheet 1964		

Female Bulkhead Connectors



Female Thread, Metric & BSPP

1060	OD mm	Thread	Bulkhead
2046-7194	4	M5	M12 x 1
2019-7083	4	1/8"	M12 x 1
2046-7196	4	1/4"	M12 x 1
2046-7197	6	M5	M14 x 1
2019-7125	6	1/8"	M14 x 1
2046-7198	6	M6	M14 x 1
2019-7133	6	1/4"	M14 x 1
2046-7199	6	3/8"	M14 x 1
2046-7200	6	1/2"	M14 x 1
2046-7201	8	1/8"	M16 x 1
2019-7166	8	1/4"	M16 x 1
2019-7182	8	3/8"	M16 x 1
2046-7202	8	1/2"	M16 x 1
2046-7203	10	1/8"	M20 x 1
2019-7299	10	1/4"	M20 x 1
2019-7307	10	3/8"	M20 x 1
2046-7204	10	1/2"	M20 x 1
2019-7315	12	1/4"	M22 x 1
2019-7497	12	3/8"	M22 x 1
2046-7205	12	1/2"	M22 x 1
Tech Sheet 1964			



For **Brass Nickel Plated Hose Tails** see pages **1140-1146**

Fluid-Air Components Ltd

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Male Stud Swivel Elbows



Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-5103	4	M5
2019-5111	4	1/8"
2046-7170	4	M6
2019-5129	4	1/4"
2019-5822	6	M5
2019-5145	6	1/8"
2046-7171	6	M6
2019-5152	6	1/4"
2019-5160	6	3/8"
2046-7172	6	1/2"
2019-5178	8	1/8"
2019-5186	8	1/4"
2019-5194	8	3/8"
2019-5202	8	1/2"
2019-5210	10	1/8"
2019-5228	10	1/4"
2019-5236	10	3/8"
2019-5244	10	1/2"
2019-5251	12	1/4"
2019-5269	12	3/8"
2019-5277	12	1/2"
2019-5278	16	3/8"
2019-5279	16	1/2"
Tech Sheet 1964		



Male Thread, BSPP

1060	OD mm	Thread
2028-8221	4	1/8"
2028-8239	4	1/4"
2028-8247	6	1/8"
2028-8254	6	1/4"
2028-8262	6	3/8"
2028-8270	8	1/8"
2028-8288	8	1/4"
2028-8296	8	3/8"
2028-8304	8	1/2"
2028-8312	10	1/8"
2028-8320	10	1/4"
2028-8338	10	3/8"
2028-8379	10	1/2"
2028-8403	12	1/4"
2028-8411	12	3/8"
2028-8429	12	1/2"
Tech Sheet 1964		

Male Stud Swivel Elbows



Extended Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-5905	4	M5
2019-5913	4	1/8"
2019-5939	6	M5
2019-5947	6	1/8"
2046-7191	6	M6
2019-5954	6	1/4"
2019-5970	8	1/8"
2019-5988	8	1/4"
2019-6135	10	1/8"
2019-6150	10	1/4"
2019-6192	12	1/4"
2019-6200	12	3/8"
Tech Sheet 1964		



Extended Male Thread, BSPP

1060	OD mm	Thread
2033-8729	4	1/8"
2033-8737	4	1/4"
2033-8745	6	1/8"
2033-8752	6	1/4"
2033-8778	6	3/8"
2033-8786	8	1/8"
2033-9107	8	1/4"
2033-9115	8	3/8"
2033-9131	10	1/8"
2033-9149	10	1/4"
2033-9156	10	3/8"
2033-9180	12	3/8"
Tech Sheet 1964		

45° Male Stud Elbows



Male Thread, BSPT

1060	OD mm	Thread
2019-0210	6	1/8"
2019-0211	6	1/4"



For **Silencers** see page **631**

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Male Stud Swivel Tees



Branch Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-5293	4	M5
2019-5301	4	1/8"
2019-5335	4	1/4"
2019-5541	6	M5
2019-5749	6	1/8"
2019-5764	6	1/4"
2019-5772	6	3/8"
2046-7175	6	1/2"
2019-5780	8	1/8"
2019-5798	8	1/4"
2019-5806	8	3/8"
2019-5814	8	1/2"
2019-5830	10	1/8"
2019-5848	10	1/4"
2019-5855	10	3/8"
2019-5863	10	1/2"
2019-5871	12	1/4"
2019-5889	12	3/8"
2019-5897	12	1/2"
Tech Sheet 1964		



Branch Male Thread, BSPP

1060	OD mm	Thread
2028-8007	4	1/8"
2028-8023	4	1/4"
2028-8031	6	1/8"
2028-8049	6	1/4"
2028-8056	6	3/8"
2028-8064	8	1/8"
2028-8072	8	1/4"
2028-8122	8	3/8"
2028-8130	8	1/2"
2028-8148	10	1/8"
2028-8155	10	1/4"
2028-8163	10	3/8"
2028-8189	12	1/4"
2028-8205	12	3/8"
2028-8213	12	1/2"
Tech Sheet 1964		



Run Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-7992	4	M5
2019-8008	4	1/8"
2019-8010	4	1/4"
2019-8012	6	M5
2019-8032	6	1/8"
2019-8040	6	1/4"
2019-8057	6	3/8"
2019-8065	8	1/8"
2019-8073	8	1/4"
2019-8081	8	3/8"
2019-8089	8	1/2"
2019-8107	10	1/8"
2019-8115	10	1/4"
2019-8123	10	3/8"
2019-8156	12	3/8"
2019-8164	12	1/2"
Tech Sheet 1964		



Run Male Thread, BSPP

1060	OD mm	Thread
2033-8570	6	1/8"
2033-8588	6	1/4"
2033-8612	8	1/4"
Tech Sheet 1964		

Male Stud Swivel Ys



Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-7513	4	1/8"
2019-7547	6	1/8"
2019-7554	6	1/4"
2019-7570	6	3/8"
2019-7596	8	1/8"
2019-7604	8	1/4"
2019-7612	8	3/8"
2019-7620	8	1/2"
2019-7638	10	1/8"
2019-7646	10	1/4"
2019-7653	10	3/8"
2019-7950	10	1/2"
2019-7968	12	1/4"
2019-7976	12	3/8"
2019-7984	12	1/2"
Tech Sheet 1964		



For **Combination Nipples** see page **1497**

Fluid-Air Components Ltd

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Tube x Tube Connectors



Equal Straights

1060	OD mm
2019-8297	4
2019-8305	6
2019-8313	8
2019-8321	10
2019-8339	12
2019-8340	16
Tech Sheet 1964	



Equal Tees

1060	OD mm
2019-8396	4
2019-8404	6
2019-8412	8
2019-8420	10
2019-8438	12
2019-8439	16
Tech Sheet 1964	



Equal Crosses

1060	OD mm
2019-8974	4
2019-8982	6
2019-8990	8
2019-9006	10
2019-9014	12
Tech Sheet 1964	



Unequal Straights

1060	OD mm	OD mm
2019-8545	4	6
2019-8552	6	8
2019-8560	8	10
2019-8578	10	12
2019-8579	12	16
Tech Sheet 1964		



Equal Ys

1060	OD mm
2019-8446	4
2019-8453	6
2019-8461	8
2019-8479	10
2019-8487	12
Tech Sheet 1964	



Equal Bulkheads

1060	OD mm	Bulkhead
2019-8495	4	M12 x 1
2019-8503	6	M14 x 1
2019-8511	8	M16 x 1
2019-8529	10	M20 x 1
2019-8537	12	M22 x 1
Tech Sheet 1964		



Equal Elbows

1060	OD mm
2019-8347	4
2019-8354	6
2019-8362	8
2019-8370	10
2019-8388	12
2019-8392	16
Tech Sheet 1964	



Unequal Ys

1060	OD mm	OD mm
2019-9139	6	4
2019-9162	8	6
2019-9170	10	8
2019-9188	12	10
Tech Sheet 1964		



For **Manual & Mechanical Valves** see pages **545-549**

Fluid-Air Components Ltd

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Tube x Stem Connectors



Straights, Tube x Stem

1060	OD mm	Stem OD mm
2028-8437	4	6
2028-8445	4	8
2028-8452	6	8
2028-8460	6	10
2028-8478	8	10
2028-8486	8	12
2028-8494	10	12
Tech Sheet 1964		



BSPP & Metric

1060	OD mm	Thread
2019-0220	4	M5
2019-0226	8	1/8"



Elbows, Tube x Stem

1060	OD mm	Stem OD mm
2024-2566	4	4
2024-2574	6	6
2024-2582	8	8
2024-2590	10	10
2024-2608	12	12
Tech Sheet 1964		



Ys, Tube x Stem

1060	OD mm	Stem OD mm
2024-2616	4	4
2024-2624	6	6
2024-2632	8	8
2024-2640	10	10
2024-2657	12	12
Tech Sheet 1964		



Reducing Ys, Tube x Stem

1060	OD mm	Stem OD mm
2024-2673	4	6
2024-2699	6	8
2024-2731	8	10
Tech Sheet 1964		

Plugs



Tube

1060	OD mm
2028-8627	4
2028-8635	6
2028-8643	8
2028-8668	10
2028-8684	12
Tech Sheet 1964	

Equal Double Joint Adaptors



Tube x Tube

1060	OD mm
2028-8502	4
2028-8510	6
2028-8528	8
2028-8536	10
2028-8544	12
Tech Sheet 1964	

Reducers



Tube x Tube

1060	OD mm	Stem OD mm
2028-8551	6	4
2028-8569	8	4
2028-8577	8	6
2028-8585	10	6
2028-8593	10	8
2028-8601	12	8
2028-8619	12	10
Tech Sheet 1964		

Tube Plugs



Tube

1060	OD mm
2033-8505	4
2033-8513	6
2033-8521	8
2033-8539	10
2033-8547	12
Tech Sheet 1964	

Single Banjos



Male Thread, Metric & BSPT

1060	OD mm	Thread
2019-8172	4	M5
2019-8180	4	1/8"
2046-7183	4	M6
2019-8198	6	M5
2019-8206	6	1/8"
2046-7185	6	M6
2019-8214	6	1/4"
2046-7186	6	3/8"
2019-8222	8	1/8"
2019-8230	8	1/4"
2019-8248	8	3/8"
2046-7188	10	1/4"
2019-8255	10	3/8"
2019-8263	10	1/2"
2046-7189	12	1/4"
2019-8271	12	3/8"
2019-8289	12	1/2"
Tech Sheet 1964		

ONE TOUCH PLASTIC PUSH-IN FITTINGS, METRIC

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Reducing Manifolds



Male Thread, BSPT

1060	Inlet OD mm	Outlet OD mm	Thread
2019-9022	6	4	1/8"
2019-9035	8	4	1/4"
2019-9048	8	6	1/4"
2019-9055	10	8	3/8"
Tech Sheet 1964			



Tube x Tube

1060	Inlet OD mm	Outlet OD mm
2019-9063	6	4
2019-9071	8	4
2019-9089	8	6
2019-9097	10	6
2023-0637	10	8
Tech Sheet 1964		

FTPRO

For **Metric Polyurethane Tubing** see pages **897-900**

Speed Control Valves



In-line, Tube x Tube

1060	OD mm
2022-9720	4
2022-9746	6
2022-9753	8
2022-9761	10
2022-9779	12
Tech Sheet 1964	



Elbow, Male Thread, Metric & BSPT

1060	OD mm	Thread
2022-9829	4	M5
2022-9845	4	1/8"
2022-9860	4	1/4"
2022-9837	6	M5
2022-9852	6	1/8"
2046-7181	6	M6
2022-9878	6	1/4"
2022-9902	6	3/8"
2022-9886	8	1/8"
2022-9894	8	1/4"
2022-9910	8	3/8"
2046-7182	8	1/2"
2022-9928	10	1/4"
2022-9936	10	3/8"
2022-9969	10	1/2"
2022-9944	12	1/4"
2022-9951	12	3/8"
2022-9977	12	1/2"
Tech Sheet 1964		

Manual Shut Off Valves

Maximum Working Pressure:
7 bar (100 psi)



BSPT x BSPT

1060	Thread	Thread
HVSS-01-01	1/8"	1/8"
HVSS-02-01	1/4"	1/8"
HVSS-02-02	1/4"	1/4"
HVSS-02-03	1/4"	3/8"
HVSS-03-03	3/8"	3/8"
HVSS-04-03	1/2"	3/8"
HVSS-04-04	1/2"	1/2"
Tech Sheet 1964		



Tube x BSPT

1060	OD mm	Thread
HVFS6-01	6	1/8"
HVFS6-02	6	1/4"
HVFS6-03	6	3/8"
HVFS8-01	8	1/8"
HVFS8-02	8	1/4"
HVFS8-03	8	3/8"
Tech Sheet 1964		

Maximum Working Pressure:
7 bar (100 psi)



Tube x Tube, Venting

1060	OD mm	OD mm
HVFF06-06	6	6
HVFF08-06	8	6
HVFF08-08	8	8
HVFF10-10	10	10
HVFF12-10	12	10
HVFF12-12	12	12
Tech Sheet 1964		

PLASTIC PUSH-IN FITTINGS

NPT & UNF Threads x Metric & Imperial Tube



Features:

- Convenient One Touch fittings provide instant connections
- Elliptical release ring facilitates pneumatic installation in confined spaces
- Light manual pressure on the elliptical release ring is all that is required to instantly disconnect each tube; no special tools required
- Nickel-plated brass threaded body ensures anti-corrosion and anti-contamination
- All taper threaded fittings are pre-coated with PTFE sealant and require no additional sealing

Working Temperature:
-10°C to +60°C

Maximum Working Pressure
10 bar (150 psi)

Construction:

Resin Body:	PBT
Metal Body:	Nickel-plated brass
Packing:	Nitrile
Back Ring:	POM
O-Ring:	Nitrile
Collar:	Nickel-plated zinc
Sleeve:	POM
Locking Claw:	Stainless steel
Media:	Air and vacuum
Threads:	NPT, UNF
OD:	Metric and imperial tube sizes

Fluid-Air Components Ltd

ONE TOUCH NPT PLASTIC PUSH-IN FITTINGS, IMPERIAL

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10 Torr)

Male Studs



Male Thread (Hex Body), NPT

1101	OD	Thread
2110-7800	1/8"	1/8"
2110-7826	1/8"	1/4"
2110-7842	5/32"	1/8"
2110-7859	5/32"	1/4"
2110-7875	3/16"	1/8"
2110-7909	3/16"	1/4"
2110-7925	3/16"	3/8"
2110-7941	1/4"	1/8"
2110-7958	1/4"	1/4"
2110-7966	1/4"	3/8"
2110-7974	5/16"	1/8"
2110-7982	5/16"	1/4"
2110-7990	5/16"	3/8"
2110-8006	3/8"	1/8"
2110-8014	3/8"	1/4"
2110-8022	3/8"	1/2"
2110-8063	1/2"	1/4"
2110-8071	1/2"	3/8"
2110-8089	1/2"	1/2"
Tech Sheet 1964		

Male Thread (Hex Body), UNF

1101	OD	Thread
2110-7776	1/8"	10-32
2110-7834	5/32"	10-32
2110-7933	1/4"	10-32
Tech Sheet 1964		



Male Thread (Round), NPT

1101	OD	Thread
2110-8105	1/8"	1/8"
2110-8113	1/8"	1/4"
2110-8139	5/32"	1/8"
2110-8147	5/32"	1/4"
2110-8188	3/16"	1/8"
2110-8204	3/16"	1/4"
2110-8220	3/16"	3/8"
2110-8246	1/4"	1/8"
2110-8253	1/4"	1/4"
2110-8279	1/4"	3/8"
2110-8287	1/4"	1/8"
2110-8295	1/4"	1/4"
2110-8303	1/4"	3/8"
2110-8311	3/8"	1/8"
2110-8329	3/8"	1/4"
2110-8337	3/8"	3/8"
2110-8345	3/8"	1/2"
2110-8352	1/2"	1/4"
2110-8360	1/2"	3/8"
2110-8378	1/2"	1/2"
Tech Sheet 1964		

Male Thread (Round), UNF


1101	OD	Thread
2110-8097	1/8"	10-32
2110-8121	5/32"	10-32
2110-8154	3/16"	10-32
2110-8238	1/4"	10-32
Tech Sheet 1964		

Female Studs



Female Thread, NPT

1101	OD	Thread
2110-8386	1/8"	1/8"
2110-8394	1/8"	1/4"
2110-8402	5/32"	1/8"
2110-8410	5/32"	1/4"
2110-8428	3/16"	1/8"
2110-8436	3/16"	1/4"
2110-8444	1/4"	1/8"
2110-8451	1/4"	1/4"
2110-8469	1/4"	3/8"
2110-8477	5/16"	1/8"
2110-8485	5/16"	1/4"
2110-8493	5/16"	3/8"
2110-8519	3/8"	1/8"
2110-8527	3/8"	1/4"
2110-8535	3/8"	3/8"
2110-8543	3/8"	1/2"
2110-8550	1/2"	1/4"
2110-8568	1/2"	3/8"
2110-8576	1/2"	1/2"
Tech Sheet 1964		



You might also need
Nylon Tubing
see page **913**

Fluid-Air Components Ltd

ONE TOUCH NPT PLASTIC PUSH-IN FITTINGS, IMPERIAL

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Male Stud Swivel Elbows



Male Thread, NPT

1101	OD	Thread
2110-8592	1/8"	1/8"
2110-8600	1/8"	1/4"
2110-8626	5/32"	1/8"
2110-8634	5/32"	1/4"
2110-8659	3/16"	1/8"
2110-8667	3/16"	1/4"
2110-8691	3/16"	3/8"
2110-8717	1/4"	1/8"
2110-8725	1/4"	1/4"
2110-8733	1/4"	3/8"
2110-8741	5/16"	1/8"
2110-8758	5/16"	1/4"
2110-8766	5/16"	3/8"
2110-8774	3/8"	1/8"
2110-8782	3/8"	1/4"
2110-8790	3/8"	3/8"
2110-8808	3/8"	1/2"
2110-8816	1/2"	1/4"
2110-8824	1/2"	3/8"
2110-8832	1/2"	1/2"
Tech Sheet 1964		

Male Thread, UNF

1101	OD	Thread
2110-8584	1/8"	10-32
2110-8618	5/32"	10-32
2110-8709	1/4"	10-32
Tech Sheet 1964		



Extended Male Thread, NPT

1101	OD	Thread
2110-8857	1/8"	1/8"
2110-8865	1/8"	1/4"
2110-8907	5/32"	1/4"
2110-8923	3/16"	1/8"
2110-8931	3/16"	1/4"
2110-8949	3/16"	3/8"
2110-8964	1/4"	1/8"
2110-8972	1/4"	1/4"
2110-8980	1/4"	3/8"
2110-8998	5/16"	1/8"
2110-9004	5/16"	1/4"
2110-9020	3/8"	1/8"
2110-9038	3/8"	1/4"
2110-9046	3/8"	3/8"
2110-9053	3/8"	1/2"
2110-9061	1/2"	1/4"
2110-9087	1/2"	1/2"
Tech Sheet 1964		

Extended Male Thread, UNF

1101	OD	Thread
2110-8840	1/8"	10-32
2110-8881	5/32"	10-32
2110-8915	3/16"	10-32
2110-8956	1/4"	10-32
Tech Sheet 1964		

Female Swivel Elbows



Female Thread, NPT

1101	OD	Thread
2110-9095	1/8"	1/8"
2110-9111	5/32"	1/8"
2110-9129	5/32"	1/4"
2110-9137	3/16"	1/8"
2110-9145	3/16"	1/4"
2110-9178	1/4"	1/8"
2110-9186	1/4"	1/4"
2110-9194	1/4"	3/8"
2110-9202	5/16"	1/8"
2110-9228	5/16"	1/4"
2110-9236	5/16"	3/8"
2110-9251	5/16"	1/2"
2110-9277	3/8"	1/8"
2110-9269	3/8"	1/4"
2110-9285	3/8"	3/8"
2110-9293	3/8"	1/2"
2111-0093	1/2"	1/4"
2111-0101	1/2"	3/8"
2111-0119	1/2"	1/2"
Tech Sheet 1964		

You might also need **Solenoid Valves**
see pages **1031-1034**



Fluid-Air Components Ltd

ONE TOUCH NPT PLASTIC PUSH-IN FITTINGS, IMPERIAL

Male Stud Elbow



Male Thread, BSPT

1060	OD	Thread
PL1/4-01	1/4"	1/8"
PL1/4-02	1/4"	1/4"
PL3/8-01	3/8"	1/8"
PL3/8-02	3/8"	1/4"
PL1/2-03	1/2"	3/8"
PL1/2-04	1/2"	1/2"

Male Stud Tees



Male Thread, BSPT

1060	OD	Thread
PB1/4-01	1/4"	1/8"
PB1/4-02	1/4"	1/4"
PB3/8-02	3/8"	1/4"
PB1/2-02	1/2"	1/4"



Male Thread, NPT

1060	OD	Thread
PB1/8-N01	1/8"	1/8"
PB1/4-N02	1/4"	1/4"

Male Studs



Male Thread, BSPT

1060	OD	Thread
PC1/4-01	1/4"	1/8"
PC1/4-02	1/4"	1/4"
PC3/8-01	3/8"	1/8"
PC3/8-02	3/8"	1/4"
PC3/8-04	3/8"	1/2"
PC1/2-03	1/2"	3/8"
PC1/2-04	1/2"	1/2"

Plugs



Tube

1060	OD
PP1/8	1/8"
PP1/4	1/4"
PP3/8	3/8"
PP1/2	1/2"

Female Studs



Female Thread, BSPP

1060	OD	Thread
PCF1/4-01	1/4"	1/8"
PCF1/4-02	1/4"	1/4"
PCF3/8-02	3/8"	1/4"
PCF3/8-04	3/8"	1/2"
PCF1/2-03	1/2"	3/8"
PCF1/2-04	1/2"	1/2"

Tube Cap



Tube

1060	OD
PPF1/2	1/2"

Tube x Tube Connectors



Equal Straights

1060	OD
PU1/8	1/8"
PU1/4	1/4"
PU3/8	3/8"
PU1/2	1/2"



Unequal Straights

1060	OD	OD
PG1/2-3/8	1/2"	3/8"



Equal Elbows

1060	OD
PV1/8	1/8"
PV1/4	1/4"
PV3/8	3/8"
PV1/2	1/2"



Equal Tees

1060	OD
PE1/8	1/8"
PE1/4	1/4"
PE3/8	3/8"
PE1/2	1/2"



Equal Bulkheads

1060	OD
PM3/8	3/8"

ONE TOUCH NPT PLASTIC PUSH-IN FITTINGS, IMPERIAL

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Male Studs



Male Thread, NPT

1101	OD mm	Thread
2111-2420	4	1/8"
2111-2446	4	1/4"
2111-2453	4	3/8"
2111-2461	6	1/8"
2111-2479	6	1/4"
2111-2487	6	3/8"
2111-2495	8	1/8"
2111-2503	8	1/4"
2111-2511	8	3/8"
2111-2529	8	1/2"
2111-2537	10	1/8"
2111-2545	10	1/4"
2111-2552	10	3/8"
2111-2560	10	1/2"
2111-2578	12	1/4"
2111-2586	12	3/8"
2111-2594	12	1/2"

Tech Sheet 1964

Male Stud Swivel Elbows



Male Thread, NPT

1101	OD mm	Thread
2111-2768	4	1/8"
2111-2776	4	1/4"
2111-2784	6	1/8"
2111-2792	6	1/4"
2111-2800	6	3/8"
2111-2818	6	1/2"
2111-2826	8	1/8"
2111-2834	8	1/4"
2111-2842	8	3/8"
2111-2859	8	1/2"
2111-2867	10	1/8"
2111-2875	10	1/4"
2111-2883	10	3/8"
2111-2891	10	1/2"
2111-2909	12	1/4"
2111-2917	12	3/8"
2111-2925	12	1/2"

Tech Sheet 1964

Female Swivel Elbows



Female Thread, NPT

1101	OD mm	Thread
2111-3113	4	1/8"
2111-3121	4	1/4"
2111-3139	6	1/8"
2111-3147	6	1/4"
2111-3154	6	3/8"
2111-3162	8	1/8"
2111-3170	8	1/4"
2111-3196	8	3/8"
2111-3204	8	1/2"
2111-3212	10	1/8"
2111-3220	10	1/4"
2111-3238	10	3/8"
2111-3246	10	1/2"
2111-3253	12	1/4"
2111-3261	12	3/8"
2111-3279	12	1/2"

Tech Sheet 1964

Female Studs



Female Thread, NPT

1101	OD mm	Thread
2111-2602	4	1/8"
2111-2610	4	1/4"
2111-2628	6	1/8"
2111-2636	6	1/4"
2111-2644	6	3/8"
2111-2651	8	1/8"
2111-2669	8	1/4"
2111-2677	8	3/8"
2111-2685	8	1/2"
2111-2693	10	1/8"
2111-2701	10	1/4"
2111-2719	10	3/8"
2111-2727	10	1/2"
2111-2735	12	1/4"
2111-2743	12	3/8"
2111-2750	12	1/2"

Tech Sheet 1964



Extended Male Thread, NPT

1101	OD mm	Thread
2111-2933	4	1/8"
2111-2941	4	1/4"
2111-2958	6	1/8"
2111-2966	6	1/4"
2111-2974	6	3/8"
2111-2982	8	1/8"
2111-3006	8	1/4"
2111-3014	8	3/8"
2111-3030	8	1/2"
2111-3048	10	1/8"
2111-3055	10	1/4"
2111-3063	10	3/8"
2111-3071	10	1/2"
2111-3089	12	1/4"
2111-3097	12	3/8"
2111-3105	12	1/2"

Tech Sheet 1964

Male Stud Swivel Tees



Branch Male Thread, NPT

1101	OD mm	Thread
2111-3287	4	1/8"
2111-3295	4	1/4"
2111-3303	6	1/8"
2111-3311	6	1/4"
2111-3329	6	3/8"
2111-3337	8	1/8"
2111-3345	8	1/4"
2111-3352	8	3/8"
2111-3360	8	1/2"
2111-3378	10	1/8"
2111-3386	10	1/4"
2111-3394	10	3/8"
2111-3402	10	1/2"
2111-3410	12	1/4"
2111-3428	12	3/8"
2111-3436	12	1/2"

Tech Sheet 1964

Fluid-Air Components Ltd

ONE TOUCH NPT PLASTIC PUSH-IN FITTINGS, IMPERIAL

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10 Torr)

Male Stud Swivel Tees



Run Male Thread, NPT

1101	OD mm	Thread
2111-3485	4	1/8"
2111-3519	4	1/4"
2111-3527	6	1/8"
2111-3535	6	1/4"
2111-3568	8	1/8"
2111-3576	8	1/4"
2111-3584	8	3/8"
2111-3592	8	1/2"
2111-3600	10	1/4"
2111-3618	10	3/8"
2111-3626	10	1/2"
2111-3634	12	1/4"
2111-3642	12	3/8"
2111-3659	12	1/2"
Tech Sheet 1964		

Male Stud Swivel Ys



Male Thread, NPT

1101	OD mm	Thread
2111-3667	4	1/8"
2111-3675	6	1/8"
2111-3683	6	1/4"
2111-3691	6	3/8"
2111-3709	8	1/8"
2111-3717	8	1/4"
2111-3725	8	3/8"
2111-3733	8	1/2"
2111-3758	10	1/4"
2111-3766	10	3/8"
2111-3774	10	1/2"
2111-3782	12	1/4"
2111-3790	12	3/8"
2111-3808	12	1/2"
Tech Sheet 1964		

Female Bulkhead Connectors



Female Thread, NPT

1101	OD mm	Thread
2111-3816	4	1/8"
2111-3832	4	1/4"
2111-3840	6	1/8"
2111-3857	6	1/4"
2111-3865	6	3/8"
2111-3873	6	1/2"
2111-3881	8	1/8"
2111-3899	8	1/4"
2111-3907	8	3/8"
2111-3915	8	1/2"
2111-3923	10	1/4"
2111-3931	10	3/8"
2111-3949	10	1/2"
2111-3956	12	1/4"
2111-3964	12	3/8"
2111-3972	12	1/2"
Tech Sheet 1964		

Single Banjos



Male Thread, NPT

1101	OD mm	Thread
2111-4020	4	1/8"
2111-4038	6	1/8"
2111-4053	6	1/4"
2111-4061	8	1/8"
2111-4079	8	1/4"
2111-4087	8	3/8"
2111-4095	10	3/8"
2111-4111	12	1/4"
2111-4137	12	1/2"
Tech Sheet 1964		



Male x Female Thread (Stacking), NPT

1101	OD mm	Thread
2111-4145	4	1/8"
2111-4152	4	1/4"
2111-4160	6	1/8"
2111-4178	6	1/4"
2111-4186	6	3/8"
2111-4202	8	1/4"
2111-4210	8	3/8"
2111-4228	8	1/2"
2111-4236	10	1/4"
2111-4244	10	3/8"
2111-4251	10	1/2"
2111-4277	12	3/8"
2111-4285	12	1/2"
Tech Sheet 1964		

Reducing Manifolds



Male Thread, NPT

1101	Inlet OD mm	Outlet OD mm	Thread
2111-3980	6	4	1/8"
2111-3998	8	4	1/4"
2111-4004	8	6	1/4"
2111-4012	10	8	3/8"
Tech Sheet 1964			

Speed Control Valves



Male Thread, NPT

1101	OD mm	Thread
2111-4293	4	1/8"
2111-4301	4	1/4"
2111-4319	6	1/8"
2111-4327	6	1/4"
2111-4335	6	3/8"
2111-4343	8	1/8"
2111-4350	8	1/4"
2111-4368	8	3/8"
2111-4376	8	1/2"
2111-4384	10	1/4"
2111-4392	10	3/8"
2111-4400	10	1/2"
2111-4418	12	1/4"
2111-4426	12	3/8"
2111-4434	12	1/2"
Tech Sheet 1964		



Male Thread, NPT x Tube

1101	OD mm	Thread
2111-4442	6	1/8"
2111-4459	6	1/4"
2111-4467	6	3/8"
2111-4475	8	1/8"
2111-4483	8	1/4"
2111-4491	8	3/8"
Tech Sheet 1964		

Fluid-Air Components Ltd

PLASTIC PUSH-IN FITTINGS

One Touch+
16 Bar Rated



Features:

- One of the highest pressure rated polymer push-in fittings available on the market
- Convenient One Touch+ fittings provide instant connections
- Elliptical release ring facilitates pneumatic installation in confined spaces
- Light manual pressure on the elliptical release ring is all that is required to instantly disconnect each tube; no special tools required
- Nickel-plated brass ensures anti-corrosion and anti-contamination
- All taper threaded fittings are pre-coated with PTFE sealant and require no additional sealing

Working Temperature:
-10°C to +60°C

Working Pressure
-0.8 bar 16 bar

*Dependent upon tubing specification.

Construction:

Resin Body:	Technopolymer resin
Metal Body:	Nickel-plated brass
Packing:	Nitrile
Back O-Ring:	POM
O-Ring:	Nitrile
Collar:	Nickel-plated zinc
Collet:	Technopolymer resin
Collet Ring:	Nickel-plated brass
Sleeve:	POM

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PLASTIC PUSH-IN FITTINGS

One Touch+ Emergency Fittings Kits, 16 Bar Rated

FT PRO®

Convenient, compact boxes containing a selection of popular FT Pro One Touch+ plastic push-in fittings along with handy tube cutter.

Available in three sizes: 6mm, 8mm and 10mm. Can be used with nylon 6, 11, 12, and polyurethane (ester and ether).

Working Temperature:
0°C to +60°C

Maximum Working Pressure:
16 bar (220 psi)

Negative Pressure:
-750mm Hg (10 Torr)



Media:
Air and vacuum only.

Plastic, 16 bar Rated Push-in

1103	OD mm
FTP-06MMBOX-OTP	6
FTP-08MMBOX-OTP	8
FTP-10MMBOX-OTP	10

Tech Sheet 10019

*Dependent upon tubing specification.

Contents:

6mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	10 x Equal Tees 2175-1038	10 x Equal Connectors 2175-1024	2 x Equal Bulkheads 2175-1057
8 x Equal Elbows 2175-1033	8 x 1/8" BSPT Male Stud Elbows 2175-0909	5 x 1/4" BSPT Male Stud Elbows 2175-0910	
5 x 1/4" BSPP Female Bulkheads 2175-1009	4 x 6mm Equal Ys 2175-1043	2 x Shut Off Valves 2175-1127	
10 x 1/8" BSPP Male Studs 2175-0873	10 x 1/4" BSPP Male Studs 2175-0874	2 x 1/8" BSPT Single Banjos 2175-1085	
5 x M5 Male Studs 2175-0854	10 x 1/8" BSPT Male Studs 2175-0856	10 x 1/4" BSPT Male Studs 2175-0857	

8mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	8 x Equal Tees 2175-1039	10 x Equal Connectors 2175-1025	2 x Equal Bulkheads 2175-1058
5 x Equal Elbows 2175-1034	6 x 1/8" BSPT Male Stud Elbows 2175-0913	5 x 1/4" BSPT Male Stud Elbows 2175-0914	
2 x 1/4" BSPP Female Bulkheads 2175-1013	4 x Equal Ys 2175-1044	2 x Shut Off Valves 2175-1129	
10 x 1/8" BSPT Male Studs 2175-0860	10 x 1/4" BSPT Male Studs 2175-0861	4 x 1/8" BSPT Single Banjos 2175-1088	
10 x 1/8" BSPP Male Studs 2175-0876	10 x 1/4" BSPP Male Studs 2175-0877	6 x 3/8" BSPP Male Studs 2175-0878	

10mm
Plastic Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	5 x Equal Tees 2175-1040	6 x Equal Connectors 2175-1026	2 x Equal Bulkheads 2175-1059
3 x Equal Elbows 2175-1035	2 x 1/8" BSPT Male Stud Elbows 2175-0917	2 x 1/4" BSPT Male Stud Elbows 2175-0918	
3 x 1/4" BSPP Female Bulkheads 2175-1017	2 x Equal Ys 2175-1045	1 x Speed Control Valve 2175-1154	
8 x 1/8" BSPP Male Studs 2175-0880	6 x 1/4" BSPP Male Studs 2175-0881	2 x 3/8" BSPT Single Banjos 2175-1092	
7 x 3/8" BSPT Male Studs 2175-0864	7 x 1/4" BSPT Male Studs 2175-0865	2 x 3/8" BSPT Male Studs 2175-0866	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ONE TOUCH+ PLASTIC PUSH-IN FITTINGS (16 BAR RATED)

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 16 bar (220 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10 Torr)

Male Studs

Male Thread, Metric & BSPT



1103	OD mm	Thread
2175-0849	4	M5
2175-0850	4	M6
2175-0851	4	1/8"
2175-0852	4	1/4"
2175-0853	4	3/8"
2175-0854	6	M5
2175-0855	6	M6
2175-0856	6	1/8"
2175-0857	6	1/4"
2175-0858	6	3/8"
2175-0859	6	1/2"
2175-0860	8	1/8"
2175-0861	8	1/4"
2175-0862	8	3/8"
2175-0863	8	1/2"
2175-0864	10	1/8"
2175-0865	10	1/4"
2175-0866	10	3/8"
2175-0867	10	1/2"
2175-0868	12	1/4"
2175-0869	12	3/8"
2175-0870	12	1/2"
2207-0684	14	3/8"
2207-0685	14	1/2"
2207-0686	16	3/8"
2207-0687	16	1/2"
Tech Sheet 10019		

Male Thread, BSPP



1103	OD mm	Thread
2175-0871	4	1/8"
2175-0872	4	1/4"
2175-0873	6	1/8"
2175-0874	6	1/4"
2175-0875	6	3/8"
2175-0876	8	1/8"
2175-0877	8	1/4"
2175-0878	8	3/8"
2175-0879	8	1/2"
2175-0880	10	1/8"
2175-0881	10	1/4"
2175-0882	10	3/8"
2175-0883	10	1/2"
2175-0884	12	1/4"
2175-0885	12	3/8"
2175-0886	12	1/2"
2207-0688	14	3/8"
2207-0689	14	1/2"
2207-0690	16	3/8"
2207-0691	16	1/2"
Tech Sheet 10019		

Female Studs

Female Thread, BSPP



1103	OD mm	Thread
2175-0887	4	1/8"
2175-0888	4	1/4"
2175-0889	6	1/8"
2175-0890	6	1/4"
2175-0891	6	3/8"
2175-0892	8	1/8"
2175-0893	8	1/4"
2175-0894	8	3/8"
2175-0895	8	1/2"
2175-0896	10	1/8"
2175-0897	10	1/4"
2175-0898	10	3/8"
2175-0899	10	1/2"
2175-0900	12	1/4"
2175-0901	12	3/8"
2175-0902	12	1/2"
2207-0692	14	3/8"
2207-0693	14	1/2"
2207-0694	16	3/8"
2207-0695	16	1/2"
Tech Sheet 10019		

Female Elbow

BSPP x Tube



1103	OD mm	Thread
2207-0800	4	1/8"
2207-0801	4	1/4"
2207-0802	6	1/8"
2207-0803	6	1/4"
2207-0804	6	3/8"
2207-0806	8	1/8"
2207-0807	8	1/4"
2207-0808	8	3/8"
2207-0809	8	1/2"
2207-0810	10	1/8"
2207-0811	10	1/4"
2207-0812	10	3/8"
2207-0813	10	1/2"
2207-0814	12	1/4"
2207-0815	12	3/8"
2207-0816	12	1/2"

Male Stud Swivel Elbows

Male Thread, Metric & BSPT



1103	OD mm	Thread
2175-0903	4	M5
2175-0904	4	M6
2175-0905	4	1/8"
2175-0906	4	1/4"
2175-0907	6	M5
2175-0908	6	M6
2175-0909	6	1/8"
2175-0910	6	1/4"
2175-0911	6	3/8"
2175-0912	6	1/2"
2175-0913	8	1/8"
2175-0914	8	1/4"
2175-0915	8	3/8"
2175-0916	8	1/2"
2175-0917	10	1/8"
2175-0918	10	1/4"
2175-0919	10	3/8"
2175-0920	10	1/2"
2175-0921	12	1/4"
2175-0922	12	3/8"
2175-0923	12	1/2"
2207-0696	14	3/8"
2207-0697	14	1/2"
2207-0698	16	3/8"
2207-0699	16	1/2"
Tech Sheet 10019		

Male Thread, BSPP



1103	OD mm	Thread
2175-0924	4	1/8"
2175-0925	4	1/4"
2175-0926	6	1/8"
2175-0927	6	1/4"
2175-0928	6	3/8"
2207-0714	6	1/2"
2175-0929	8	1/8"
2175-0930	8	1/4"
2175-0931	8	3/8"
2175-0932	8	1/2"
2175-0933	10	1/8"
2175-0934	10	1/4"
2175-0935	10	3/8"
2175-0936	10	1/2"
2175-0937	12	1/4"
2175-0938	12	3/8"
2175-0939	12	1/2"
2207-0700	14	3/8"
2207-0701	14	1/2"
2207-0702	16	3/8"
2207-0703	16	1/2"
Tech Sheet 10019		

Fluid-Air Components Ltd

ONE TOUCH+ PLASTIC PUSH-IN FITTINGS (16 BAR RATED)

FT PRO

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 16 bar (220 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10 Torr)

Male Stud Swivel Elbows



Extended Male Thread, Metric & BSPT

1103	OD mm	Thread
2175-0940	4	M5
2175-0941	4	1/8"
2175-0942	4	1/4"
2175-0943	6	M5
2175-0944	6	1/8"
2175-0945	6	1/4"
2175-0946	6	3/8"
2175-0947	8	1/8"
2175-0948	8	1/4"
2175-0949	8	3/8"
2175-0950	10	1/8"
2175-0951	10	1/4"
2175-0952	10	3/8"
2175-0953	10	1/2"
2175-0954	12	1/4"
2175-0956	12	1/2"
Tech Sheet 10019		

Extended Male Thread, BSPP

1103	OD mm	Thread
2175-0957	4	1/8"
2175-0958	4	1/4"
2175-0959	6	1/8"
2175-0960	6	1/4"
2175-0961	6	3/8"
2175-0962	8	1/8"
2175-0963	8	1/4"
2175-0964	10	1/8"
2175-0965	10	1/4"
2175-0966	10	3/8"
2175-0967	12	3/8"
Tech Sheet 10019		

Male Stud Swivel Tees



Run Male Thread, BSPP

1103	OD mm	Thread
2175-0968	4	1/8"
2175-0969	4	1/4"
2175-0970	6	1/8"
2175-0971	6	1/4"
2175-0972	8	1/4"
2175-0973	10	1/4"
Tech Sheet 10019		



Branch Male Thread, BSPP

1103	OD mm	Thread
2175-0974	4	1/8"
2175-0975	4	1/4"
2175-0976	6	1/8"
2175-0977	6	1/4"
2175-0978	6	3/8"
2175-0979	8	1/8"
2175-0980	8	1/4"
2175-0981	8	3/8"
2175-0982	8	1/2"
2175-0983	10	1/8"
2175-0984	10	1/4"
2175-0985	10	3/8"
2175-1160	10	1/2"
2175-0986	12	1/4"
2175-0987	12	3/8"
2175-0988	12	1/2"
Tech Sheet 10019		



BSPT x Tube

1103	OD mm	Thread
2175-1170	4	M5
2175-1171	4	1/8"
2175-1172	4	1/4"
2175-1173	6	M5
2175-1174	6	1/8"
2175-1175	6	1/4"
2175-1176	6	3/8"
2175-1177	6	1/2"
2175-1178	8	1/8"
2175-1179	8	1/4"
2175-1180	8	3/8"
2175-1181	8	1/2"
2175-1182	10	1/8"
2175-1183	10	1/4"
2175-1184	10	3/8"
2175-1185	10	1/2"
2175-1186	12	1/4"



BSPT & Metric

1103	OD mm	Thread
2176-0001	4	M5
2176-0002	4	1/8"
2176-0003	4	1/4"
2176-0004	4	3/8"
2176-0005	6	M5
2176-0006	6	1/8"
2176-0007	6	1/4"
2176-0009	8	1/8"
2176-0011	8	3/8"
2176-0012	8	1/2"
2176-0015	10	3/8"
2176-0016	10	1/2"
2176-0018	12	3/8"
2176-0019	12	1/2"
2176-0020	16	3/8"
2176-0021	16	1/2"

ONE TOUCH+ PLASTIC PUSH-IN FITTINGS (16 BAR RATED)

FT PRO

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 16 bar (220 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10Torr)

Female Bulkhead Connectors



Female Thread, BSPP

1103	OD mm	Thread
2175-1006	4	1/8"
2175-1007	4	1/4"
2175-1008	6	1/8"
2175-1009	6	1/4"
2175-1010	6	3/8"
2175-1011	6	1/2"
2175-1012	8	1/8"
2175-1013	8	1/4"
2175-1014	8	3/8"
2175-1015	8	1/2"
2175-1016	10	1/8"
2175-1017	10	1/4"
2175-1018	10	3/8"
2175-1019	10	1/2"
2175-1020	12	1/4"
2175-1021	12	3/8"
2175-1022	12	1/2"
Tech Sheet 10019		

Male Stud Swivel Ys



Male Thread, Metric & BSPT

1103	OD mm	Thread
2175-0989	4	M5
2175-0990	4	1/8"
2174-1001	4	1/4"
2175-0991	6	M5
2175-0992	6	1/8"
2175-0993	6	1/4"
2175-0994	6	3/8"
2174-1002	6	1/2"
2175-0995	8	1/8"
2175-0996	8	1/4"
2175-0997	8	3/8"
2175-0998	8	1/2"
2175-0999	10	1/8"
2175-1000	10	1/4"
2175-1001	10	3/8"
2175-1002	10	1/2"
2175-1003	12	1/4"
2175-1004	12	3/8"
2175-1005	12	1/2"
Tech Sheet 10019		

Tube x Tube Connectors



Equal Straights

1103	OD mm
2175-1023	4
2175-1024	6
2175-1025	8
2175-1026	10
2175-1027	12
2207-0704	14
2207-0705	16
Tech Sheet 10019	



Unequal Straights

1103	OD mm	OD mm
2175-1028	6	4
2174-1005	8	4
2175-1029	8	6
2175-1030	10	8
2174-1010	12	6
2174-1015	12	8
2175-1031	12	10
2174-1020	16	12
Tech Sheet 10019		



Equal Elbows

1103	OD mm
2175-1032	4
2175-1033	6
2175-1034	8
2175-1035	10
2175-1036	12
2207-0706	14
2207-0707	16
Tech Sheet 10019	



Equal Tees

1103	OD mm
2175-1037	4
2175-1038	6
2175-1039	8
2175-1040	10
2175-1041	12
2207-0708	14
2207-0709	16
Tech Sheet 10019	

Reducing on Branch Tees



Tube x Tube

1103	OD A mm	OD B mm	OD C mm
2174-1030	6	4	6
2174-1031	8	6	8
2174-1032	10	8	10
2174-1033	12	10	12

Tube x Tube Connectors



Equal Ys

1103	OD mm
2175-1042	4
2175-1043	6
2175-1044	8
2175-1045	10
2175-1046	12
2207-0710	14
2207-0711	16
Tech Sheet 10019	



Unequal Ys

1103	OD mm	OD mm
2175-1047	4	6
2175-1048	6	8
2175-1049	8	10
2175-1050	10	12
Tech Sheet 10019		

Fluid-Air Components Ltd

ONE TOUCH+ PLASTIC PUSH-IN FITTINGS (16 BAR RATED)

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 16 bar (220 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10Torr)

Tube x Tube Connectors



Equal Crosses

1103	OD mm
2175-1051	4
2175-1052	6
2175-1053	8
2175-1054	10
2175-1055	12
Tech Sheet 10019	



Equal Bulkheads

1103	OD mm
2175-1056	4
2175-1057	6
2175-1058	8
2175-1059	10
2175-1060	12
2174-1040	16
Tech Sheet 10019	



For **Control Valves** see page **1056**

Tube x Stem Connectors



Straights, Tube x Stem

1103	OD mm	Stem OD mm
2175-1061	4	6
2175-1062	4	8
2175-1063	6	8
2175-1064	6	10
2175-1065	8	10
2174-1070	8	12
2175-1066	10	12
Tech Sheet 10019		



Elbows, Tube x Stem

1103	OD mm	Stem OD mm
2175-1067	4	4
2175-1068	6	6
2175-1069	8	8
2175-1070	10	10
2175-1071	12	12
Tech Sheet 10019		



Ys, Tube x Stem

1103	OD mm	Stem OD mm
2175-1072	6	6
2175-1073	8	8
2175-1074	10	10
2174-1081	12	12
Tech Sheet 10019		

Plugs



Tube

1103	OD mm
2175-1075	4
2175-1076	6
2175-1077	8
2175-1078	10
2175-1079	12
Tech Sheet 10019	

Blanking Cap



1103	OD mm
2174-2000	4
2174-2001	6
2174-2002	8
2174-2003	10
2174-2004	12

Single Banjos



Male Thread, Metric & BSPT

1103	OD mm	Thread
2175-1080	4	M5
2175-1081	4	M6
2175-1082	4	1/8"
2174-2006	4	1/4"
2175-1083	6	M5
2175-1084	6	M6
2175-1085	6	1/8"
2175-1086	6	1/4"
2175-1087	6	3/8"
2175-1088	8	1/8"
2175-1089	8	1/4"
2175-1090	8	3/8"
2174-2008	10	1/8"
2175-1091	10	1/4"
2175-1092	10	3/8"
2175-1093	10	1/2"
2175-1094	12	1/4"
2175-1095	12	3/8"
2175-1096	12	1/2"
Tech Sheet 10019		

Fluid-Air Components Ltd

ONE TOUCH+ PLASTIC PUSH-IN FITTINGS (16 BAR RATED)

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 16 bar (220 psi)

Media: Air and vacuum only.

Negative Pressure: -750mm Hg (10Torr)

Reducing Manifolds



Tube x Male Thread, BSPP

1103	Inlet OD mm	Outlet OD mm	Thread
2174-3000	4	4	1/8"
2174-3001	4	4	1/4"
2174-3002	6	6	1/8"
2174-3003	6	6	1/4"
2174-3004	6	6	3/8"
2175-1097	6	4	1/8"
2174-3005	8	8	1/8"
2175-1098	8	4	1/4"
2175-1099	8	6	1/4"
2174-3006	8	8	1/4"
2174-3007	8	8	3/8"
2175-1100	10	8	3/8"
Tech Sheet 10019			



Tube x Tube

1103	Inlet OD mm	Outlet OD mm
2175-1101	6	4
2175-1102	8	4
2175-1103	8	6
2175-1104	10	6
2175-1105	10	8
Tech Sheet 10019		

Manual Shut Off Valves



BSPT x BSPT

1103	Thread	Thread
2175-1106	1/8"	1/8"
2175-1107	1/4"	1/8"
2175-1108	1/4"	1/4"
2175-1109	1/4"	3/8"
2175-1110	3/8"	3/8"
2175-1111	1/2"	3/8"
2175-1112	1/2"	1/2"
Tech Sheet 10019		



Tube x BSPT

1103	OD mm	Thread
2175-1113	6	1/8"
2175-1114	6	1/4"
2175-1115	6	3/8"
2175-1116	8	1/8"
2175-1117	8	1/4"
2175-1118	8	3/8"
2175-1119	10	1/4"
2175-1120	10	3/8"
2175-1121	10	1/2"
2175-1122	12	1/4"
2175-1123	12	3/8"
2175-1124	12	1/2"
Tech Sheet 10019		



Tube x Tube

1103	OD mm	OD mm
2175-1125	4	4
2175-1126	6	4
2175-1127	6	6
2175-1128	8	6
2175-1129	8	8
2175-1130	10	10
2175-1131	12	10
2175-1132	12	12
Tech Sheet 10019		

Speed Control Valves



Tube x Metric & BSPT

1103	OD mm	Thread
2175-1133	4	M5
2175-1134	4	1/8"
2175-1135	4	1/4"
2175-1136	6	M5
2175-1137	6	M6
2175-1138	6	1/8"
2175-1139	6	1/4"
2175-1140	6	3/8"
2175-1141	8	1/8"
2175-1142	8	1/4"
2175-1143	8	3/8"
2175-1144	8	1/2"
2175-1145	10	1/4"
2175-1146	10	3/8"
2175-1147	10	1/2"
2175-1148	12	1/4"
2175-1149	12	3/8"
2175-1150	12	1/2"
Tech Sheet 10019		



Tube x Tube

1103	OD mm
2175-1151	4
2175-1152	6
2175-1153	8
2175-1154	10
2175-1155	12
Tech Sheet 10019	

Fluid-Air Components Ltd

MICRO PUSH-IN FITTINGS
One Touch



Features:

- Convenient One Touch micro fittings provide instant connections
- Elliptical release ring
- 40% less volume and 20% smaller OD compared with standard One Touch fittings, making them ideal for use in confined spaces
- Light manual pressure on the elliptical release ring is all that is required to instantly disconnect each tube; no special tools required
- Nickel plated brass ensures anti-corrosion and anti-contamination
- Available in metric, parallel and taper BSP threads, imperial NPT and UNF threads
- All taper threaded fittings are pre-coated with PTFE sealant and require no additional sealing

Working Temperature:
-10°C to +60°C

Maximum Working Pressure
-0.8 bar to 10 bar

*Dependent upon tubing specification.

Construction:

Resin Body:	PBT
Metal Body:	Nickel-plated brass
Packing:	Nitrile
Back Ring:	POM
O-Ring:	Nitrile
Collar:	Nickel-plated zinc
Collet:	PBT
Collet Ring:	Nickel plated brass
Sleeve:	POM

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MICRO ONE TOUCH METRIC PLASTIC PUSH-IN FITTINGS

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

40% less volume and a 20% smaller OD than the standard One Touch design..

Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time and money on installations.

Male Studs

Male Thread (Hex Body), Metric



0315	OD mm	Thread
PC03-M3C	3	M3
PC04-M3C	4	M3
PC03-M5C	3	M5
PC04-M5C	4	M5
PC06-M5C	6	M5
PC03-M6C	3	M6
PC04-M6C	4	M6
PC06-M6C	6	M6

Tech Sheet 10000

Male Thread (Hex Body), BSPT

0315	OD mm	Thread
PC04-01C	4	1/8"
PC06-01C	6	1/8"

Tech Sheet 10000

Male Thread (Hex Body), BSPP

0315	OD mm	Thread
PC04-G01C	4	1/8"
PC06-G01C	6	1/8"

Tech Sheet 10000

Male Thread (Round Body), Metric



0315	OD mm	Thread
POC03-M3C	3	M3
POC04-M3C	4	M3
POC03-M5C	3	M5
POC04-M5C	4	M5
POC06-M5C	6	M5
POC03-M6C	3	M6
POC04-M6C	4	M6
POC06-M6C	6	M6

Tech Sheet 10000

Male Thread (Round Body), BSPT

0315	OD mm	Thread
POC04-01C	4	1/8"
POC06-01C	6	1/8"

Tech Sheet 10000

Male Thread (Round Body), BSPP

0315	OD mm	Thread
POC04-G01C	4	1/8"
POC06-G01C	6	1/8"

Tech Sheet 10000

Female Studs

Female Thread (Hex Body), Metric



0315	OD mm	Thread
PCF03-M3C	3	M3
PCF04-M3C	4	M3
PCF03-M5C	3	M5
PCF04-M5C	4	M5
PCF06-M5C	6	M5
PCF03-M6C	3	M6
PCF04-M6C	4	M6
PCF06-M6C	6	M6

Tech Sheet 10000

Female Thread (Hex Body), BSPT

0315	OD mm	Thread
PCF04-01C	4	1/8"
PCF06-01C	6	1/8"

Tech Sheet 10000

Female Thread (Hex Body), BSPP

0315	OD mm	Thread
PCF04-G01C	4	1/8"
PCF06-G01C	6	1/8"

Tech Sheet 10000

Male Stud Elbows

Male Thread, Metric



0315	OD mm	Thread
PL03-M3C	3	M3
PL04-M3C	4	M3
PL03-M5C	3	M5
PL04-M5C	4	M5
PL06-M5C	6	M5
PL03-M6C	3	M6
PL04-M6C	4	M6
PL06-M6C	6	M6

Tech Sheet 10000

Male Thread, BSPT

0315	OD mm	Thread
PL04-01C	4	1/8"
PL06-01C	6	1/8"

Tech Sheet 10000

Male Thread, BSPP

0315	OD mm	Thread
PL04-G01C	4	1/8"
PL06-G01C	6	1/8"

Tech Sheet 10000

Extended Male Thread, Metric



0315	OD mm	Thread
PLL03-M3C	3	M3
PLL04-M3C	4	M3
PLL03-M5C	3	M5
PLL04-M5C	4	M5
PLL06-M5C	6	M5
PLL03-M6C	3	M6
PLL04-M6C	4	M6
PLL06-M6C	6	M6

Tech Sheet 10000

Extended Male Thread, BSPT

0315	OD mm	Thread
PLL04-01C	4	1/8"
PLL06-01C	6	1/8"

Tech Sheet 10000

Extended Male Thread, BSPP

0315	OD mm	Thread
PLL06-G01C	6	1/8"

Tech Sheet 10000

Male Stud Tees

Branch Male Thread, Metric



0315	OD mm	Thread
PT03-M3C	3	M3
PT04-M3C	4	M3
PT03-M5C	3	M5
PT04-M5C	4	M5
PT06-M5C	6	M5
PT03-M6C	3	M6
PT04-M6C	4	M6
PT06-M6C	6	M6

Tech Sheet 10000

Branch Male Thread, BSPT

0315	OD mm	Thread
PT04-01C	4	1/8"
PT06-01C	6	1/8"

Tech Sheet 10000

Branch Male Thread, BSPP

0315	OD mm	Thread
PT04-G01C	4	1/8"
PT06-G01C	6	1/8"

Tech Sheet 10000

Fluid-Air Components Ltd

MICRO ONE TOUCH METRIC PLASTIC PUSH-IN FITTINGS

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

40% less volume and a 20% smaller OD than the standard One Touch design.Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time and money on installations.

Male Stud Tees



Run Male Thread, Metric

0315	OD mm	Thread
PST03-M3C	3	M3
PST04-M3C	4	M3
PST03-M5C	3	M5
PST04-M5C	4	M5
PST06-M5C	6	M5
PST03-M6C	3	M6
PST04-M6C	4	M6
PST06-M6C	6	M6
Tech Sheet 10000		

Run Male Thread, BSPT

0315	OD mm	Thread
PST04-01C	4	1/8"
PST06-01C	6	1/8"
Tech Sheet 10000		

Run Male Thread, BSPP

0315	OD mm	Thread
PST04-G01C	4	1/8"
PST06-G01C	6	1/8"
Tech Sheet 10000		



You might also need **Polyurethane Coil Assemblies** see page **900**

Equal Connectors



Straights

0315	OD mm
PUC03C	3
PUC04C	4
PUC06C	6
Tech Sheet 10000	



Elbows

0315	OD mm
PUL03C	3
PUL04C	4
PUL06C	6
Tech Sheet 10000	



Tees

0315	OD mm
PUT03C	3
PUT04C	4
PUT06C	6
Tech Sheet 10000	



Ys

0315	OD mm
PY04C	4
PY06C	6
Tech Sheet 10000	

Bulkheads



Equal Elbows

0315	OD mm
PLM04C	4
PLM06C	6
Tech Sheet 10000	



Customers who bought from this page also purchased **Metric Nylon Tubing** see page **913**

MICRO ONE TOUCH IMPERIAL NPT & UNF PLASTIC PUSH-IN FITTINGS

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

40% less volume and a 20% smaller OD than the standard One Touch design.

Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time and money on installations.

Male Studs



Male Thread (Hex Body), NPT

0315	OD	Thread
PC1/8-N00C	1/8"	1/16"
PC5/32-N00C	5/32"	1/16"
PC1/4-N00C	1/4"	1/16"
PC1/8-N01C	1/8"	1/8"
PC5/32-N01C	5/32"	1/8"
PC1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Male Thread (Hex Body), UNF

0315	OD	Thread mm
PC1/8-U10C	1/8"	10-32
PC5/32-U10C	5/32"	10-32
PC1/4-U10C	1/4"	10-32
Tech Sheet 10001		



Male Thread (Round Body), NPT

0315	OD	Thread
POC1/8-N00C	1/8"	1/16"
POC5/32-N00C	5/32"	1/16"
POC1/4-N00C	1/4"	1/16"
POC1/8-N01C	1/8"	1/8"
POC5/32-N01C	5/32"	1/8"
POC1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Male Thread (Round Body), UNF

0315	OD	Thread mm
POC1/8-U10C	1/8"	10-32
POC5/32-U10C	5/32"	10-32
POC1/4-U10C	1/4"	10-32
Tech Sheet 10001		

Female Studs



Female Thread, NPT

0315	OD	Thread
PCF5/32-N00C	5/32"	1/16"
PCF1/4-N00C	1/4"	1/16"
PCF1/8-N01C	1/8"	1/8"
PCF5/32-N01C	5/32"	1/8"
PCF1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Female Thread, UNF

0315	OD	Thread mm
PCF1/8-U10C	1/8"	10-32
PCF5/32-U10C	5/32"	10-32
PCF1/4-U10C	1/4"	10-32
Tech Sheet 10001		



You might also need
Hose & Tube Cutters
see page **905**

Male Stud Elbows



Male Thread, NPT

0315	OD	Thread
PL1/8-N00C	1/8"	1/16"
PL5/32-N00C	5/32"	1/16"
PL1/4-N00C	1/4"	1/16"
PL1/8-N01C	1/8"	1/8"
PL5/32-N01C	5/32"	1/8"
PL1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Male Thread, UNF

0315	OD	Thread mm
PL1/8-U10C	1/8"	10-32
PL5/32-U10C	5/32"	10-32
PL1/4-U10C	1/4"	10-32
Tech Sheet 10001		



Extended Male Thread, NPT

0315	OD	Thread
PLL1/8-N00C	1/8"	1/16"
PLL5/32-N00C	5/32"	1/16"
PLL1/4-N00C	1/4"	1/16"
PLL1/8-N01C	1/8"	1/8"
PLL5/32-N01C	5/32"	1/8"
PLL1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Extended Male Thread, UNF

0315	OD	Thread mm
PLL1/8-U10C	1/8"	10-32
PLL5/32-U10C	5/32"	10-32
PLL1/4-U10C	1/4"	10-32
Tech Sheet 10001		

Fluid-Air Components Ltd

MICRO ONE TOUCH IMPERIAL NPT & UNF PLASTIC PUSH-IN FITTINGS

Working Temperature: 0°C to +60°C

Maximum Working Pressure: 10 bar (150 psi)

40% less volume and a 20% smaller OD than the standard One Touch design.

Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time and money on installations.

Male Stud Tees



Branch Male Thread, NPT

0315	OD	Thread
PT1/8-N00C	1/8"	1/16"
PT5/32-N00C	5/32"	1/16"
PT1/4-N00C	1/4"	1/16"
PT1/8-N01C	1/8"	1/8"
PT5/32-N01C	5/32"	1/8"
PT1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Branch Male Thread, UNF

0315	OD	Thread mm
PT1/8-U10C	1/8"	10-32
PT5/32-U10C	5/32"	10-32
PT1/4-U10C	1/4"	10-32
Tech Sheet 10001		



Run Male Thread, NPT

0315	OD	Thread
PST1/8-N00C	1/8"	1/16"
PST5/32-N00C	5/32"	1/16"
PST1/4-N00C	1/4"	1/16"
PST1/8-N01C	1/8"	1/8"
PST1/4-N01C	1/4"	1/8"
Tech Sheet 10001		

Run Male Thread, UNF

0315	OD	Thread mm
PST1/8-U10C	1/8"	10-32
PST5/32-U10C	5/32"	10-32
PST1/4-U10C	1/4"	10-32
Tech Sheet 10001		

Equal Connectors



Straights

0315	OD
PUC1/8C	1/8"
PUC5/32C	5/32"
PUC1/4C	1/4"
Tech Sheet 10001	



Elbows

0315	OD
PUL1/8C	1/8"
PUL5/32C	5/32"
PUL1/4C	1/4"
Tech Sheet 10001	



Tees

0315	OD
PUT1/8C	1/8"
PUT5/32C	5/32"
PUT1/4C	1/4"
Tech Sheet 10001	



Ys

0315	OD
PY5/32C	5/32"
PY1/4C	1/4"
Tech Sheet 10001	

Bulkheads



Equal Straights

0315	OD
PMM1/8C	1/8"
PMM5/32C	5/32"
PMM1/4C	1/4"
Tech Sheet 10001	



Equal Elbows

0315	OD
PLM1/8C	1/8"
PLM5/32C	5/32"
PLM1/4C	1/4"
Tech Sheet 10001	

Speed Control Valves



Male Thread, UNF

0315	OD	Thread mm
NSE1/8-U10C	1/8"	10-32
NSE5/32-U10C	5/32"	10-32
NSE1/4-U10C	1/4"	10-32
Tech Sheet 10001		

Fluid-Air Components Ltd

CHECK & STOP VALVES

Working Temperature:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

Media:
Air and vacuum only.

Negative Pressure:
-750mm Hg (10Torr)

Cracking Pressure:
0.3 bar to 0.5 bar (5 psi to 7.5 psi)

Check Valves

Free flow thread to tube



Tube x BSPT

1060	OD mm	Thread
PCVC04-01	4	1/8"
PCVC04-02	4	1/4"
PCVC06-01	6	1/8"
PCVC06-02	6	1/4"
PCVC08-01	8	1/8"
PCVC08-02	8	1/4"
PCVC10-02	10	1/4"
PCVC10-03	10	3/8"
PCVC12-02	12	1/4"
PCVC12-03	12	3/8"
Tech Sheet 10134		



Tube x Tube

1060	OD mm
PCVU04	4
PCVU06	6
PCVU08	8
PCVU10	10
Tech Sheet 10134	



Female x Female, BSPT

1060	Thread
PCFF01-01	1/8"
PCFF02-02	1/4"
PCFF03-03	3/8"
PCFF04-04	1/2"
Tech Sheet 10134	

Free flow female to male



Male x Female, BSPP

1060	Thread
PCVF01-01	1/8"
PCVF02-02	1/4"
PCVF03-03	3/8"
PCVF04-04	1/2"
Tech Sheet 10134	

Stop Valves, Self-sealing



Tube x BSPT

1060	OD mm	Thread
SPC06-02	6	1/4"
SPC08-02	8	1/4"
SPC08-03	8	3/8"
SPC10-02	10	1/4"
SPC10-03	10	3/8"
SPC10-04	10	1/2"
SPC12-03	12	3/8"
SPC12-04	12	1/2"
Tech Sheet 10134		



Tube x Tube

1060	OD mm
SPU06	6
SPU08	8
SPU10	10
SPU12	12
Tech Sheet 10134	

For **Air Receivers & Accessories**
see pages **433-434**





Fluid-Air Components Ltd

LF 3000® PUSH-IN FITTINGS




Pre-coated Threads:
All taper threaded LF 3000 male fittings are supplied with a pre-coated thread for immediate installation.



Identification:
The part numbers have been chosen by a method of mnemonics. Each LF 3000 fitting is identified b

- Its series
- The diameter of passage through the fittin
- The thread code or second tube diameter



Seals:
All LF 3000 fittings with BSPP and M5 threads are supplied complete with an integral O-ring seal or a pre-assembled nylon sealing washer. This permits instant assembly of the fitting without preparation of the thread, and provides a fixed assembled height to the fitting



Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar

Vacuum Capability:
Vacuum of 755mm Hg (99% vacuum).

Suitable Fluids:
Compressed air, LF 3000 can also be used for conveying various types of liquids (water, cutting oil, etc) for industrial applications. The working pressure, from 0.6-10 bar and temperatures from 0-60°C, are dependent upon the fluid conveyed and the type of O-ring used. Silicone free.

Male Stud Fittings, Hexagonal



BSPT

1014	OD mm	Thread
LE-3175 04 10	4	1/8"
LE-3175 04 13	4	1/4"
LE-3175 06 10	6	1/8"
LE-3175 06 13	6	1/4"
LE-3175 06 17	6	3/8"
LE-3175 06 21	6	1/2"
LE-3175 08 10	8	1/8"
LE-3175 08 13	8	1/4"
LE-3175 08 17	8	3/8"
LE-3175 08 21	8	1/2"
LE-3175 10 13	10	1/4"
LE-3175 10 17	10	3/8"
LE-3175 10 21	10	1/2"
LE-3175 12 13	12	1/4"
LE-3175 12 17	12	3/8"
LE-3175 12 21	12	1/2"
LE-3175 14 17	14	3/8"
LE-3175 14 21	14	1/2"
LE-3175 16 17	16	3/8"
LE-3175 16 21	16	1/2"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3101 03 09	3	M3 x 0.5
LE-3101 03 19	3	M5 x 0.8
LE-3101 04 09	4	M3 x 0.5
LE-3101 04 19	4	M5 x 0.8
LE-3101 04 55	4	M7 x 1
LE-3101 04 13	4	1/4"
LE-3101 06 19	6	M5 x 0.8
LE-3101 06 55	6	M7 x 1
LE-3101 06 10	6	1/8"
LE-3101 06 13	6	1/4"
LE-3101 06 17	6	3/8"
LE-3101 06 21	6	1/2"
LE-3101 08 10	8	1/8"
LE-3101 08 13	8	1/4"
LE-3101 08 17	8	3/8"
LE-3101 10 13	10	1/4"
LE-3101 10 17	10	3/8"
LE-3101 10 21	10	1/2"
LE-3101 12 13	12	1/4"
LE-3101 12 17	12	3/8"
LE-3101 12 21	12	1/2"
LE-3101 14 21	14	1/2"
LE-3101 16 17	16	3/8"
LE-3101 16 21	16	1/2"
Tech Sheet 10626		

Female Stud Fittings



Metric & BSPP

1014	OD mm	Thread
LE-3114 04 19	4	M5 x 0.8
LE-3114 04 10	4	1/8"
LE-3114 04 13	4	1/4"
LE-3114 06 10	6	1/8"
LE-3114 06 13	6	1/4"
LE-3114 08 10	8	1/8"
LE-3114 08 13	8	1/4"
LE-3114 08 17	8	3/8"
LE-3114 10 13	10	1/4"
LE-3114 10 17	10	3/8"
LE-3114 10 21	10	1/2"
LE-3114 12 17	12	3/8"
LE-3114 12 21	12	1/2"
Tech Sheet 10626		

Fluid-Air Components Ltd



Parker Partnership brands available



Parker OLAER

Hydraulic Accumulators & Accessories
See section 1 pages 227-228

Hydraulic Oil Coolers
See section 1 page 273









Parker legris

Ball & Check Valves
See section 5 pages 628

Plastic Push-in Fittings
See section 6 pages 793-807

Metal Push-in Fittings
See section 6 pages 848-851

Ball Valves
See section 7 pages 933-935



Blow Guns
See section 15 page 1596



Parker RECTUS

Pneumatic Quick Release Couplings
See section 3 pages 330-390



Parker dh domnick hunter

Filters & Drains Air, Water & Vacuum
See section 4 page 430



Parker transair

Aluminium Ring Main Systems
See section 8 pages 1063-1067



Parker legris LIQUIfit™

Plastic Push-in Fittings
See section 6 pages 800-803

ENGINEERING YOUR SUCCESS.

FAC Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

LF 3000® PUSH-IN FITTINGS

Male Stud Elbows



BSPT

1014	OD mm	Thread
LE-3109 04 10	4	1/8"
LE-3109 04 13	4	1/4"
LE-3109 06 10	6	1/8"
LE-3109 06 13	6	1/4"
LE-3109 06 17	6	3/8"
LE-3109 06 21	6	1/2"
LE-3109 08 10	8	1/8"
LE-3109 08 13	8	1/4"
LE-3109 08 17	8	3/8"
LE-3109 08 21	8	1/2"
LE-3109 10 13	10	1/4"
LE-3109 10 17	10	3/8"
LE-3109 10 21	10	1/2"
LE-3109 12 13	12	1/4"
LE-3109 12 17	12	3/8"
LE-3109 12 21	12	1/2"
LE-3109 14 17	14	3/8"
LE-3109 14 21	14	1/2"
LE-3109 16 17	16	3/8"
LE-3109 16 21	16	1/2"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3199 03 19	3	M5 x 0.8
LE-3199 04 09	4	M3 x 0.5
LE-3199 04 19	4	M5 x 0.8
LE-3199 04 55	4	M7 x 1
LE-3199 04 10	4	1/8"
LE-3199 04 13	4	1/4"
LE-3199 06 19	6	M5 x 0.8
LE-3199 06 55	6	M7 x 1
LE-3199 06 10	6	1/8"
LE-3199 06 13	6	1/4"
LE-3199 06 17	6	3/8"
LE-3199 06 21	6	1/2"
LE-3199 08 10	8	1/8"
LE-3199 08 13	8	1/4"
LE-3199 08 17	8	3/8"
LE-3199 08 21	8	1/2"
LE-3199 10 13	10	1/4"
LE-3199 10 17	10	3/8"
LE-3199 10 21	10	1/2"
LE-3199 12 13	12	1/4"
LE-3199 12 21	12	1/2"
LE-3199 14 17	14	3/8"
LE-3199 14 21	14	1/2"
LE-3199 16 17	16	3/8"
LE-3199 16 21	16	1/2"
Tech Sheet 10626		

Extended Male Stud Elbows



BSPT

1014	OD mm	Thread
LE-3129 04 13	4	1/4"
LE-3129 06 10	6	1/8"
LE-3129 06 13	6	1/4"
LE-3129 08 10	8	1/8"
LE-3129 08 13	8	1/4"
LE-3129 08 17	8	3/8"
LE-3129 10 17	10	3/8"
LE-3129 12 13	12	1/4"
LE-3129 12 17	12	3/8"
LE-3129 12 21	12	1/2"
LE-3129 14 21	14	1/2"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3169 04 19	4	M5 x 0.8
LE-3169 04 13	4	1/4"
LE-3169 06 19	6	M5 x 0.8
LE-3169 06 10	6	1/8"
LE-3169 06 13	6	1/4"
Tech Sheet 10626		



You might also need
Leak-free LIQUIfit Fittings
see pages **800-803**

45º Male Elbows



BSPT

1014	OD mm	Thread
LE-3113 04 10	4	1/8"
LE-3113 06 10	6	1/8"
LE-3113 06 13	6	1/4"
LE-3113 08 13	8	1/4"
LE-3113 08 17	8	3/8"
LE-3113 10 13	10	1/4"
LE-3113 10 17	10	3/8"
LE-3113 12 17	12	3/8"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3133 04 19	4	M5 x 0.8
LE-3133 06 19	6	M5 x 0.8
LE-3133 06 10	6	1/8"
Tech Sheet 10626		

Female Stud Elbows



BSPP

1014	OD mm	Thread
LE-3192 04 10	4	1/8"
LE-3192 04 13	4	1/4"
LE-3192 06 10	6	1/8"
LE-3192 06 13	6	1/4"
LE-3192 08 10	8	1/8"
LE-3192 08 13	8	1/4"
LE-3192 08 17	8	3/8"
LE-3192 10 13	10	1/4"
LE-3192 10 17	10	3/8"
LE-3192 12 13	12	1/4"
LE-3192 12 17	12	3/8"
LE-3192 12 21	12	1/2"
Tech Sheet 10626		

Fluid-Air Components Ltd

LF 3000® PUSH-IN FITTINGS

Male Stud Branch Tees



BSPT

1014	OD mm	Thread
LE-3108 04 10	4	1/8"
LE-3108 04 13	4	1/4"
LE-3108 06 10	6	1/8"
LE-3108 06 13	6	1/4"
LE-3108 08 10	8	1/8"
LE-3108 08 13	8	1/4"
LE-3108 10 13	10	1/4"
LE-3108 10 17	10	3/8"
LE-3108 10 21	10	1/2"
LE-3108 12 13	12	1/4"
LE-3108 12 17	12	3/8"
LE-3108 12 21	12	1/2"
LE-3108 14 21	14	1/2"
LE-3108 16 17	16	3/8"
LE-3108 16 21	16	1/2"
Tech Sheet 10626		

Male Stud Run Tees



BSPT

1014	OD mm	Thread
LE-3103 04 13	4	1/4"
LE-3103 06 10	6	1/8"
LE-3103 08 10	8	1/8"
LE-3103 08 13	8	1/4"
LE-3103 10 13	10	1/4"
LE-3103 10 21	10	1/2"
LE-3103 12 13	12	1/4"
LE-3103 12 17	12	3/8"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3193 04 19	4	M5 x 0.8
LE-3193 04 10	4	1/8"
LE-3193 06 19	6	M5 x 0.8
LE-3193 06 10	6	1/8"
LE-3193 08 10	8	1/8"
LE-3193 08 17	8	3/8"
LE-3193 10 13	10	1/4"
LE-3193 12 17	12	3/8"
LE-3193 14 21	14	1/2"
Tech Sheet 10626		

Threaded Standpipes



Stem x BSPT

1014	Stem OD mm	Thread
LE-3121 04 13	4	1/4"
LE-3121 06 13	6	1/4"
LE-3121 10 17	10	3/8"
Tech Sheet 10626		



Stem x BSPP

1014	Stem OD mm	Thread
LE-3131 08 13	8	1/4"
LE-3131 12 21	12	1/2"
LE-3131 14 17	14	3/8"
Tech Sheet 10626		

Double Y Pieces



BSPT

1014	OD mm	Thread
LE-3112 06 13	6	1/4"
Tech Sheet 10626		



BSPP

1014	OD mm	Thread
LE-3132 06 13	6	1/4"
Tech Sheet 10626		

Twin Banjos



BSPP

1014	OD mm	Thread
LE-3149 04 10	4	1/8"
LE-3149 06 10	6	1/8"
LE-3149 06 13	6	1/4"
LE-3149 08 13	8	1/4"
LE-3149 08 17	8	3/8"
Tech Sheet 10626		

Stacking Banjo Bolts



2 Body High Modules BSPP

1014	Thread
LE-3528 00 13	1/4"
Tech Sheet 10626	



3 Body High Modules BSPP

1014	Thread
LE-3529 00 10	1/8"
LE-3529 00 13	1/4"
Tech Sheet 10626	

Double Banjos



Metric & BSPP

1014	OD mm	Thread
LE-3119 04 19	4	M5 x 0.8
LE-3119 08 13	8	1/4"
Tech Sheet 10626		

Single Banjo Bolts



BSPP

1014	Thread
LE-3527 00 10	1/8"
LE-3527 00 13	1/4"
LE-3527 00 17	3/8"
Tech Sheet 10626	

Female Threaded Banjo Bolts



BSPP

1014	Thread	Thread
LE-3524 00 10	1/8"	1/8"
LE-3524 00 13	1/4"	1/4"
Tech Sheet 10626		

Single Banjo Bodies



BSPP

1014	OD mm	Thread
LE-3538 06 10	6	1/8"
LE-3538 06 13	6	1/4"
LE-3538 08 13	8	1/4"
Tech Sheet 10626		

Fluid-Air Components Ltd

LF 3000® PUSH-IN FITTINGS

Tube/Tube Connectors - Equal & Unequal



Equal

1014	OD mm
LE-3106 03 00	3
LE-3106 04 00	4
LE-3106 06 00	6
LE-3106 08 00	8
LE-3106 10 00	10
LE-3106 12 00	12
LE-3106 14 00	14
LE-3106 16 00	16
Tech Sheet 10626	

Unequal

1014	OD mm	OD mm
LE-3106 03 04	3	4
LE-3106 04 06	4	6
LE-3106 04 08	4	8
LE-3106 06 08	6	8
LE-3106 06 10	6	10
LE-3106 08 10	8	10
LE-3106 10 12	10	12
LE-3106 12 14	12	14
LE-3106 12 16	16	12
Tech Sheet 10626		

Bulkhead Connectors

All bulkhead fixing nuts ar complete with an integral sealing ring for improved performance.



Equal

1014	OD mm
LE-3116 04 00	4
LE-3116 06 00	6
LE-3116 08 00	8
LE-3116 10 00	10
LE-3116 12 00	12
LE-3116 14 00	14
Tech Sheet 10626	

Bulkhead Elbows

All bulkhead fixing nuts are complete with an integral sealing ring for improved performance.



Equal

1014	OD mm
LE-3139 04 00	4
LE-3139 06 00	6
LE-3139 08 00	8
LE-3139 10 00	10
LE-3139 12 00	12
Tech Sheet 10626	

Single Y Pieces



Equal

1014	OD mm
LE-3140 04 00	4
LE-3140 06 00	6
LE-3140 08 00	8
LE-3140 10 00	10
LE-3140 12 00	12
Tech Sheet 10626	

Unequal

1014	OD mm	OD mm
LE-3140 04 06	4	6
LE-3140 06 08	6	8
LE-3140 08 10	8	10
LE-3140 10 12	10	12
Tech Sheet 10626		

Elbows



Equal

1014	OD mm
LE-3102 04 00	4
LE-3102 06 00	6
LE-3102 08 00	8
LE-3102 10 00	10
LE-3102 12 00	12
LE-3102 14 00	14
LE-3102 16 00	16
Tech Sheet 10626	

Unequal

1014	OD mm	OD mm
LE-3102 04 06	4	6
LE-3102 06 08	6	8
LE-3102 08 10	8	10
LE-3102 10 12	10	12
Tech Sheet 10626		

Female Bulkhead Connectors

All bulkhead fixing nuts are complete with an integral sealing ring for improved performance.



BSPP

1014	OD mm	Thread
LE-3136 04 10	4	1/8"
LE-3136 06 10	6	1/8"
LE-3136 06 13	6	1/4"
LE-3136 08 10	8	1/8"
LE-3136 08 13	8	1/4"
LE-3136 10 17	10	3/8"
LE-3136 12 17	12	3/8"
Tech Sheet 10626		

Multiple Y Pieces



Equal

1014	OD mm
LE-3144 04 04	4
LE-3144 06 06	6
Tech Sheet 10626	

Unequal

1014	OD mm	OD mm
LE-3144 04 06	4	6
LE-3144 06 08	6	8
Tech Sheet 10626		

Tees



Equal

1014	OD mm
LE-3104 03 00	3
LE-3104 04 00	4
LE-3104 06 00	6
LE-3104 08 00	8
LE-3104 10 00	10
LE-3104 12 00	12
LE-3104 14 00	14
LE-3104 16 00	16
Tech Sheet 10626	

Unequal, Branch

1014	OD mm	OD mm
LE-3104 04 06	4	6
LE-3104 06 04	6	4
LE-3104 06 08	6	8
LE-3104 08 06	8	6
LE-3104 08 10	8	10
LE-3104 10 08	10	8
LE-3104 10 12	10	12
LE-3104 12 10	12	10
LE-3104 16 12	16	12
Tech Sheet 10626		

Mixed Bulkhead Connectors

All bulkhead fixing nuts are complete with an integral sealing ring for improved performance.



Push-in x Compression

1014	OD mm
LE-3146 04 00	4
LE-3146 06 00	6
Tech Sheet 10626	

Fluid-Air Components Ltd

LF 3000® PUSH-IN FITTINGS

Unequal Multiple Elbow with Fixing Holes



Reducing Tube x Tube

1014	OD mm	OD mm
LE-3306 06 04	6	4
LE-3306 08 04	8	4
LE-3306 08 06	8	6
LE-3306 10 06	10	6
LE-3306 10 08	10	8
Tech Sheet 10626		

Manifold with LF 3000 Push-in Connection



BSPP x Tube

1014	OD mm	Thread
LE-3310 04 13	4	1/4"
LE-3310 06 13	6	1/4"
LE-3310 08 17	8	3/8"
Tech Sheet 10626		

Blanking Plugs



Tube

1014	OD mm
LE-3126 04 00	4
LE-3126 06 00	6
LE-3126 08 00	8
LE-3126 10 00	10
LE-3126 12 00	12
LE-3126 14 00	14
LE-3126 16 00	16
Tech Sheet 10626	

Plug-in Equal & Unequal Compact Elbow with Plastic Tailpiece



Equal

1014	OD mm
LE-3182 04 00	4
LE-3182 06 00	6
LE-3182 08 00	8
LE-3182 10 00	10
LE-3182 12 00	12
Tech Sheet 10626	

Unequal

1014	OD mm	Stem OD mm
LE-3182 04 06	4	6
LE-3182 06 04	6	4
LE-3182 06 08	6	8
LE-3182 08 10	8	10
LE-3182 10 12	10	12
Tech Sheet 10626		

Extended Equal & Unequal Elbow with Plastic Tailpiece



Equal

1014	OD mm
LE-3184 12 00	12
Tech Sheet 10626	

Unequal

1014	OD mm	Stem OD mm
LE-3184 08 10	8	10
Tech Sheet 10626		

45º Equal Elbow with Plastic Tailpiece



Tube x Stem

1014	OD mm
LE-3180 04 00	4
LE-3180 08 00	8
Tech Sheet 10626	

Cross Equal



Tube x Tube

1014	OD mm
LE-3107 06 00	6
Tech Sheet 10626	

Plug-in Equal Compact Tee with Plastic Tailpiece



Tube x Stem

1014	OD mm
LE-3188 06 00	6
LE-3188 08 00	8
Tech Sheet 10626	

Plug-in Equal & Unequal Single Y Piece



Reducing Tube x Stem

1014	OD mm	Stem OD mm
LE-3142 04 06	4	6
LE-3142 06 08	6	8
LE-3142 08 10	8	10
Tech Sheet 10626		

Plug-in Equal Tee with Plastic Tailpiece



Tube x Stem

1014	OD mm	Stem OD mm
LE-3183 06 00	6	6
LE-3183 08 00	8	8
Tech Sheet 10626		

Plug-in Multiple Y Piece



Tube x Stem

1014	OD mm	Stem OD mm
LE-3143 04 06	4	6
Tech Sheet 10626		

Barbed Connector for Unequal Tube



Stem x Hose Tail

1014	Stem OD mm	To Suit Hose OD mm
LE-3122 04 53	4	5
LE-3122 06 05	6	7
LE-3122 08 56	8	6.3
LE-3122 10 08	10	10
LE-3122 12 10	12	12
LE-3122 12 62	12	14.5
Tech Sheet 10626		

Double Male Stem Connector - Plastic



Tube x Tube

1014	OD mm
LE-3120 04 00	4
LE-3120 06 00	6
LE-3120 08 00	8
LE-3120 10 00	10
Tech Sheet 10626	

Increaser



Tube x Stem

1014	OD mm	Stem OD mm
LE-3168 06 04	6	4
LE-3168 08 06	8	6
LE-3168 10 08	10	8
LE-3168 12 10	12	10
Tech Sheet 10626		

LF 3000® PUSH-IN FITTINGS

Reducer



Tube x Stem

1014	OD mm	Stem OD mm
LE-3166 03 04	3	4
LE-3166 04 06	4	6
LE-3166 04 08	4	8
LE-3166 04 10	4	10
LE-3166 06 08	6	8
LE-3166 06 10	6	10
LE-3166 06 12	6	12
LE-3166 06 14	6	14
LE-3166 08 10	8	10
LE-3166 08 12	8	12
LE-3166 08 14	8	14
LE-3166 10 12	10	12
LE-3166 10 14	10	14
LE-3166 12 14	12	14
Tech Sheet 10626		

LF 3000 Multi Connectors

The Legris multi connector is designed for simultaneous connection and disconnection of 2, 4, 7 and 12 tubes. Its LF 3000 technology and performance makes it easy to use:- instant connection and disconnection, without tools, - full flo , without restriction. In order to facilitate the installation, each tube outlet is numbered. A location pin avoids assembly errors and a cap helps to guide the tubes and to protect connections. To cover all users needs, this range can also be used for bulkhead connections.



Male Screw Body

1014	OD mm	No of Tubes
LE-3320 04 00 04	4	4
LE-3320 04 00 07	4	7
LE-3320 04 00 12	4	12
LE-3320 06 00 04	6	4
LE-3320 06 00 07	6	7
Tech Sheet 10626		



Female Screw Body

1014	OD mm	No of Tubes
LE-3321 04 00 04	4	4
LE-3321 04 00 07	4	7
LE-3321 04 00 12	4	12
LE-3321 06 00 04	6	4
LE-3321 06 00 07	6	7
Tech Sheet 10626		



Screw Cap

1014	No of Tubes
LE-3329 00 02	4 and 7
Tech Sheet 10626	

DIN Rail Connections




These components are similar in principle to the electrical connectors found in control panels and are used to rationalise cabling and to assist trouble shooting. Used alongside electrical connectors, Legris DIN rail connectors provide similar facilities for pneumatics circuits, and are mounted on the same rail profile which allows electrics and pneumatics to run side by side. All tube connections are Legris push-in fittings for plastic tubing

Connector for 2 Tubes In-line

1014	To Suit Hose OD mm
LE-3379 08 00	8
Tech Sheet 10626	

Self-Sealing Male Stud Fittings



BSPP


1014	OD mm	Thread
LE-3391 04 10	4	1/8"
LE-3391 06 10	6	1/8"
LE-3391 08 13	8	1/4"
LE-3391 10 17	10	3/8"
Tech Sheet 10626		

Clip Strips for Tubes



1014	To Suit Hose OD mm
LE-CLIP 04 00	4
LE-CLIP 06 00	6
LE-CLIP 08 00	8
LE-CLIP 10 00	10
LE-CLIP 12 00	12
LE-CLIP 14 00	14
Tech Sheet 10626	

Oscillating Compact Elbows





BSPT

1014	OD mm	Thread
LE-3159 04 10	4	1/8"
LE-3159 06 10	6	1/8"
LE-3159 06 13	6	1/4"
LE-3159 08 10	8	1/8"
LE-3159 08 13	8	1/4"
Tech Sheet 10626		



Metric & BSPP

1014	OD mm	Thread
LE-3189 04 19	4	M5 x 0.8
LE-3189 06 19	6	M5 x 0.8
LE-3189 06 10	6	1/8"
LE-3189 06 13	6	1/4"
LE-3189 08 10	8	1/8"
LE-3189 08 17	8	3/8"
LE-3189 10 13	10	1/4"
LE-3189 10 17	10	3/8"
Tech Sheet 10626		

Coloured Release Button Covers for LF 3000 3rd Generation



1014	OD mm	Colour
LE-3110 14 00	14	White
LE-3110 14 02	14	Green
LE-3110 06 03	6	Red
LE-3110 14 03	14	Red
LE-3110 04 04	4	Blue
LE-3110 06 04	6	Blue
LE-3110 12 04	12	Blue
LE-3110 14 04	14	Blue
LE-3110 14 05	14	Yellow
Tech Sheet 10626		

Fluid-Air Components Ltd

LEAK-FREE, PUSH-IN FITTINGS NPT THREADS X IMPERIAL TUBE

Introducing LIQUIfi ™ a range of leak-free, push-in fittings in a bio-based compact body.

LIQUIfi ™ offers:

- The most compact profile on the marke
- EPDM patented sealing technology
- Full flo
- No pumping effect
- No need for locking clip or tube insert
- Optimum performance suitable for food and water contact
- 100% bio-based body and base

	Working Temperature:	Maximum Working Pressure:
1/4"	+2°C to +38°C	16 bar
	+65°C	10 bar
	+93°C	6 bar
3/8"	+2°C to +38°C	13 bar
	+65°C	7 bar
	+93°C	4 bar
1/2"	+2°C to +38°C	11 bar
	+65°C	7 bar
	+93°C	4 bar

Suitable for use with chemicals and other potentially aggressive liquids.
Please contact our technical department for full details.

Male Stud Fittings



Hexagonal, NPT

1014	OD	Thread
LE-6305 56 14W	1/4"	1/4"

Tech Sheet 10625

Female Stud Fittings



NPT

1014	OD	Thread
LE-6315 56 14W	1/4"	1/4"
LE-6315 60 18W	3/8"	3/8"

Tech Sheet 10625

Tees



Equal

1014	OD
LE-6304 56 00W	1/4"
LE-6304 60 00W	3/8"
LE-6304 62 00W	1/2"

Tech Sheet 10625

Equal Elbows



Tube x Tube

1014	OD
LE-6302 56 00W	1/4"
LE-6302 60 00W	3/8"
LE-6302 62 00W	1/2"

Tech Sheet 10625

Straight Connectors



Equal, Tube x Tube

1014	OD
LE-6306 56 00W	1/4"
LE-6306 60 00W	3/8"
LE-6306 62 00W	3/8"

Tech Sheet 10625

Tube/Tube Connectors



Unequal, Tube x Tube

1014	OD	OD
LE-6306 56 60W	1/4"	3/8"
LE-6306 60 62W	3/8"	1/2"

Tech Sheet 10625

Bulkhead Connectors



Tube x Tube

1014	OD
LE-6316 56 00W	1/4"
LE-6316 60 00W	3/8"
LE-6316 62 00W	1/2"

Tech Sheet 10625

Single Y Pieces



Tube x Tube

1014	OD
LE-6340 56 00W	1/4"
LE-6340 60 00W	3/8"
LE-6340 62 00W	1/2"

Tech Sheet 10625

Tube Blanking Caps



Tube

1014	OD
LE-6351 56 00W	1/4"
LE-6351 60 00W	3/8"

Tech Sheet 10625

Fluid-Air Components Ltd

LEAK-FREE, PUSH-IN FITTINGS NPT THREADS X IMPERIAL TUBE

Parker legris LIQUIfit™

Connectors



Tube x Hose Tail

1014	Stem OD	To Suit Hose ID
LE-6322 56 56W	1/4"	0.28
LE-6322 60 56W	3/8"	0.28
LE-6322 60 08W	3/8"	0.33
LE-6322 60 60W	3/8"	0.4
LE-6322 62 60W	1/2"	0.4
Tech Sheet 10625		

Plugs



Tube

1014	OD
LE-6326 56 00W	1/4"
Tech Sheet 10625	

Acetal Check Valves



Tube x Tube

1014	OD
LE-7992 56 00W	1/4"
LE-7992 60 00W	3/8"
Tech Sheet 10625	

Tank Ball Valves



Tube x Female, NPT

1014	OD	Thread
LE-4022 56 14W	1/4"	1/4"
LE-4022 60 18W	3/8"	3/8"
Tech Sheet 10625		

In-line Ball Valves



Tube x Tube

1014	OD
LE-4020 56 00W	1/4"
LE-4020 60 00W	3/8"
Tech Sheet 10625	



Tube x Male, NPT

1014	OD	Thread
LE-4021 56 14W	1/4"	1/4"
LE-4021 60 18W	3/8"	3/8"
Tech Sheet 10625		

Reducers



Tube x Stem

1014	OD	Stem OD
LE-6366 56 08W	1/4"	5/16"
LE-6366 56 60W	1/4"	3/8"
LE-6366 60 62W	3/8"	1/2"
Tech Sheet 10625		

Plug-in Equal Compact Elbows



Tube x Stem

1014	OD
LE-6382 56 00W	1/4"
LE-6382 60 00W	3/8"
LE-6382 62 00W	1/2"
Tech Sheet 10625	

Plug-in Equal Branch Tees



Tube x Stem

1014	OD
LE-6388 56 00W	1/4"
LE-6388 60 00W	3/8"
Tech Sheet 10625	

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

LEAK-FREE, PUSH-IN FITTINGS BSP THREADS X METRIC TUBE

Parker legris LIQUIfit™

Male Stud Fittings



BSPT

1014	OD mm	Thread
LE-6505 04 10W	4	1/8"
LE-6505 04 13W	4	1/4"
LE-6505 06 10W	6	1/8"
LE-6505 06 13W	6	1/4"
LE-6505 08 10W	8	1/8"
LE-6505 08 13W	8	1/4"
LE-6505 08 17W	8	3/8"
LE-6505 10 13W	10	1/4"
LE-6505 10 17W	10	3/8"
LE-6505 10 21W	10	1/2"
LE-6505 12 17W	12	3/8"
LE-6505 12 21W	12	1/2"
Tech Sheet 10625		

Female Stud Fittings



BSPT

1014	OD mm	Thread
LE-6315 06 10W	6	1/8"
LE-6315 06 13W	6	1/4"
LE-6315 08 13W	8	1/4"
LE-6315 08 17W	8	3/8"
Tech Sheet 10625		

Fixed Male Stud Elbows



BSPT

1014	OD mm	Thread
LE-6579 06 10W	6	1/8"
LE-6579 06 13W	6	1/4"
LE-6579 06 17W	6	3/8"
Tech Sheet 10625		

Swivel Male Stud Fittings



BSPT

1014	OD mm	Thread
LE-6509 06 10W	6	1/8"
LE-6509 06 13W	6	1/4"
LE-6509 06 17W	6	3/8"
LE-6509 08 10W	8	1/8"
LE-6509 08 13W	8	1/4"
LE-6509 08 17W	8	3/8"
LE-6509 10 13W	10	1/4"
LE-6509 10 17W	10	3/8"
LE-6509 10 21W	10	1/2"
LE-6509 12 17W	12	3/8"
LE-6509 12 21W	12	1/2"
Tech Sheet 10625		

Tees



Equal

1014	OD mm
LE-6304 04 00W	4
LE-6304 06 00W	6
LE-6304 08 00W	8
LE-6304 10 00W	10
LE-6304 12 00W	12
Tech Sheet 10625	

Swivel Branch Tees



BSPT

1014	OD mm	Thread
LE-6508 06 10W	6	1/8"
LE-6508 06 13W	6	1/4"
LE-6508 06 17W	6	3/8"
LE-6508 08 13W	8	1/4"
LE-6508 08 17W	8	3/8"
LE-6508 10 13W	10	1/4"
LE-6508 10 17W	10	3/8"
LE-6508 10 21W	10	1/2"
LE-6508 12 17W	12	3/8"
LE-6508 12 21W	12	1/2"
Tech Sheet 10625		

Swivel Male Run Tees



BSPT

1014	OD mm	Thread
LE-6503 06 13W	6	1/4"
LE-6503 08 10W	8	1/8"
LE-6503 08 13W	8	1/4"
LE-6503 08 17W	8	3/8"
LE-6503 12 17W	12	3/8"
LE-6503 12 21W	12	1/2"
Tech Sheet 10625		

Stem Adaptors



BSPT

1014	OD mm	Thread
LE-6521 06 10W	6	1/8"
LE-6521 06 13W	6	1/4"
LE-6521 06 17W	6	3/8"
LE-6521 08 10W	8	1/8"
LE-6521 08 13W	8	1/4"
LE-6521 08 17W	8	3/8"
LE-6521 10 13W	10	1/4"
LE-6521 10 17W	10	3/8"
LE-6521 10 21W	10	1/2"
LE-6521 12 17W	12	3/8"
LE-6521 12 21W	12	1/2"
Tech Sheet 10625		

Fluid-Air Components Ltd

LEAK-FREE, PUSH-IN FITTINGS

Parker legris LIQUIfit™

Equal Elbows



Tube x Tube

1014	OD mm
LE-6302 04 00W	4
LE-6302 06 00W	6
LE-6302 08 00W	8
LE-6302 10 00W	10
LE-6302 12 00W	12
Tech Sheet 10625	

Single Y Pieces



Tube x Tube

1014	OD mm
LE-6340 04 00W	4
LE-6340 06 00W	6
LE-6340 08 00W	8
LE-6340 10 00W	10
LE-6340 12 00W	12
Tech Sheet 10625	

Plug-in Equal Compact Elbows



Tube x Stem

1014	OD mm
LE-6382 04 00W	4
LE-6382 06 00W	6
LE-6382 08 00W	8
LE-6382 10 00W	10
LE-6382 12 00W	12
Tech Sheet 10625	

Straight Connectors



Equal, Tube x Tube

1014	OD mm
LE-6306 04 00W	4
LE-6306 06 00W	6
LE-6306 08 00W	8
LE-6306 10 00W	10
LE-6306 12 00W	12
Tech Sheet 10625	

Tube Blanking Caps



Tube

1014	OD mm
LE-6351 04 00W	4
LE-6351 06 00W	6
LE-6351 08 00W	8
LE-6351 10 00W	10
LE-6351 12 00W	12
Tech Sheet 10625	

Plug-in Equal Branch Tees



Tube x Stem

1014	OD mm
LE-6388 04 00W	4
LE-6388 06 00W	6
LE-6388 08 00W	8
LE-6388 10 00W	10
Tech Sheet 10625	

Bulkhead Connectors



Tube x Tube

1014	OD mm
LE-6316 04 00W	4
LE-6316 06 00W	6
LE-6316 08 00W	8
LE-6316 10 00W	10
LE-6316 12 00W	12
Tech Sheet 10625	

Reducers



Tube x Stem

1014	OD mm	Stem OD mm
LE-6366 04 06W	4	6
LE-6366 06 08W	6	8
LE-6366 08 10W	8	10
Tech Sheet 10625		

Plugs




Tube


1014	OD mm
LE-6326 04 00W	4
LE-6326 06 00W	6
LE-6326 08 00W	8
LE-6326 10 00W	10
LE-6326 12 00W	12
Tech Sheet 10625	

FLOW CONTROL REGULATORS POLYMER VERSION

Miniature



Compact



Identification:

The part numbers have been chosen by a method of mnemonics. Each item is identified by

- Its series
- The diameter of passage through the fittin
- The thread code or second tube diameter

LE-7060 04 10

Type of fittin | OD of tube | Thread code or second OD

Working Temperature: 0°C to +70°C

Working Pressure: 1 to 10 bar

Working Fluids: Compressed air

Compact



Exhaust Version (A), BSPP

1012	OD mm	Thread
LE-7060 06 10	6	1/8"
LE-7060 06 13	6	1/4"
LE-7060 08 10	8	1/8"
LE-7060 08 13	8	1/4"
LE-7060 08 17	8	3/8"
LE-7060 10 13	10	1/4"
LE-7060 10 17	10	3/8"
LE-7060 12 17	12	3/8"
LE-7060 12 21	12	1/2"
Tech Sheet 10627		



Supply Version (B), BSPP

1012	OD mm	Thread
LE-7061 04 10	4	1/8"
LE-7061 06 10	6	1/8"
LE-7061 06 13	6	1/4"
LE-7061 08 13	8	1/4"
LE-7061 08 17	8	3/8"
LE-7061 10 17	10	3/8"
LE-7061 12 21	12	1/2"
Tech Sheet 10627		



Bi-directional Version (C), BSPP

1012	OD mm	Thread
LE-7062 04 10	4	1/8"
LE-7062 06 10	6	1/8"
LE-7062 06 13	6	1/4"
LE-7062 08 10	8	1/8"
LE-7062 08 13	8	1/4"
Tech Sheet 10627		

Miniature



Exhaust Version (A), Metric & BSPP

1012	OD mm	Thread
LE-7660 03 19	3	M5 x 0.8
LE-7660 04 19	4	M5 x 0.8
LE-7660 04 10	4	1/8"
LE-7660 06 19	6	M5 x 0.8
LE-7660 06 10	6	1/8"
LE-7660 06 13	6	1/4"
LE-7660 08 10	8	1/8"
LE-7660 08 13	8	1/4"
LE-7660 08 17	8	3/8"
Tech Sheet 10627		



Supply Version (B), Metric & BSPP

1012	OD mm	Thread
LE-7669 03 09	3	M3 x 0.5
LE-7669 04 19	4	M5 x 0.8
LE-7669 04 10	4	1/8"
LE-7669 06 19	6	M5 x 0.8
LE-7669 06 10	6	1/8"
LE-7669 08 13	8	1/4"
Tech Sheet 10627		

Plug-in Compact



Exhaust Version (A)

1012	OD mm
LE-7030 08 00	8
Tech Sheet 10627	

Supply Version (B)

1012	OD mm
LE-7031 06 00	6
LE-7031 08 00	8
Tech Sheet 10627	

Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

FLOW CONTROL REGULATORS POLYMER VERSION

In-line Panel Mountable with LF 3000 Push-in Connections



One Way Adjustment (A), for Nylon PU Tubing

1012	OD mm
LE-7776 04 00	4
LE-7776 06 00	6
LE-7776 08 00	8
LE-7776 10 00	10
LE-7776 12 00	12

In-line with LF 3000 Push-in Connections



One Way Adjustment (A), for Nylon and PU Tubing

1012	OD mm
LE-7770 04 00	4
LE-7770 06 00	6
LE-7770 08 00	8
LE-7770 10 00	10
LE-7770 12 00	12

Bi-directional (C)

1012	OD mm
LE-7772 04 00	4
LE-7772 06 00	6
LE-7772 08 00	8

Compact Swivel Outlet



Exhaust Version (A), BSPP

1012	OD mm	Thread
LE-7740 06 10	6	1/8"
LE-7040 08 10	8	1/8"
Tech Sheet 10627		

Exhaust Version (A), BSPT

1012	OD mm	Thread
LE-7045 08 17	8	3/8"

In-line with Threaded Connections



One Way Adjustment (C), Panel Mountable, BSPP

1012	Thread
LE-7771 10 10	1/8"
LE-7771 13 13	1/4"
LE-7771 17 17	3/8"
LE-7771 21 21	1/2"

Miniature Swivel Outlet



Supply Version (B), Metric & BSPP

1012	OD mm	Thread
LE-7649 04 19	4	M5 x 0.8
LE-7649 06 19	6	M5 x 0.8
LE-7649 06 10	6	1/8"

Compact, with Recessed Adjustment Screw



Exhaust Version (A), Metric & BSPP

1012	OD mm	Thread
LE-7010 04 19	4	M5 x 0.8
LE-7010 04 10	4	1/4"
LE-7010 06 19	6	M5 x 0.8
LE-7010 06 10	6	1/8"
LE-7010 06 13	6	1/4"
LE-7010 08 10	8	1/8"
LE-7010 08 13	8	1/4"
LE-7010 10 13	10	1/4"
LE-7010 10 17	10	3/8"

Supply Version (B), Metric & BSPP

1012	OD mm	Thread
LE-7011 06 19	6	M5 x 0.8
LE-7011 06 10	6	1/8"
LE-7011 06 13	6	1/4"
LE-7011 08 13	8	1/4"
LE-7011 10 13	10	1/4"



Bi-directional (C), Metric

1012	OD mm	Thread
LE-7012 04 19	4	M5 x 0.8

Metal Body with LF 3000 Instant Fittings

Flow Control Regulators Metal Version Working Temperature:
0°C to +70°C



Exhaust Flow Control, BSPP

1012	OD mm	Thread
LE-7100 06 13	6	1/4"
LE-7100 08 10	8	1/8"
LE-7100 08 13	8	1/4"
LE-7100 12 21	12	1/2"
LE-7100 14 21	14	1/2"

Supply Flow Control, BSPP

1012	OD mm	Thread
LE-7101 06 13	6	1/4"

FLOW CONTROL REGULATORS & FUNCTION FITTINGS

Metal Body with Threaded Fittings



Exhaust Flow Control, BSPP

1012	Thread
LE-7110 13 13	1/4"
LE-7110 17 17	3/8"
LE-7110 21 21	1/2"

Supply Flow Control, BSPP

1012	Thread
LE-7111 13 13	1/4"

Blocking Fittings: Which are mounted in pairs in a cylinder-lock the piston by simultaneously cutting off the supply and exhaust. Functional locks are more precise and rapid when blocking fittings are locate on the cylinder: the volume of air in the supply line no longer needs to be taken into consideration.

Male Thread BSPP

Working Temperature: -20°C to +70°C

Working Pressure: 1 to 10 bar

No. of Cycles: 10 million at 20°C and 1 Hz

Body: Treated brass



With LF 3000 Instant Fittings, BSPP

1012	Thread A mm	Thread B mm	Thread
LE-7880 06 10	6	4	1/8"
LE-7880 06 13	6	4	1/4"
LE-7880 08 13	8	4	1/4"
LE-7880 08 17	8	4	3/8"
LE-7880 10 17	10	4	3/8"
LE-7880 12 21	12	4	1/2"

With Threaded Connection

1012	OD A mm	OD B mm	Thread
LE-7881 13 10	1/8"	M5	1/4"
LE-7881 13 13	1/4"	M5	1/4"
LE-7881 17 17	3/8"	M5	3/8"
LE-7881 21 21	1/2"	M5	1/2"

Blocker/Flow Regulator

Working Temperature: -15°C to +60°C

Body: Polymer HR/brass body with captive seal. This fitting combines the functions of blocking and flow regulation, saving space and installing time



With LF 3000 Instant Fittings, BSPP

1012	OD A mm	OD B mm	Thread
LE-7883 06 10	6	4	1/8"
LE-7883 06 13	6	4	1/4"
LE-7883 08 13	8	4	1/4"

Push-in Connectors



Supply Version, BSPP

1012	OD mm	Thread
LE-7984 06 10	6	1/8"
LE-7984 06 13	6	1/4"
LE-7984 08 10	8	1/8"
LE-7984 08 13	8	1/4"



Supply Version, BSPT

1012	OD mm	Thread
LE-7985 06 13	6	1/4"
LE-7985 08 13	8	1/4"

Miniature with Push-in Connection



Exhaust Version, Metric & BSPP

1012	OD mm	Thread
LE-7180 04 19	4	M5 x 0.8
LE-7180 04 10	4	1/8"
LE-7180 06 10	6	1/8"
LE-7180 08 10	8	1/8"

Miniature with Threaded Fitting



Exhaust Version, Metric & BSPP

1012	Thread
LE-7190 19 19	M5 x 0.8
LE-7190 10 10	1/8"

Recessed Adjustment Screw



Push-in, Exhaust Version, Metric & BSPP

1012	OD mm	Thread
LE-7130 04 19	4	M5 x 0.8
LE-7130 04 10	4	1/8"
LE-7130 06 19	6	M5 x 0.8
LE-7130 06 10	6	1/8"
LE-7130 06 13	6	1/4"
LE-7130 08 10	8	1/8"
LE-7130 08 13	8	1/4"
LE-7130 08 17	8	3/8"
LE-7130 10 13	10	1/4"
LE-7130 10 17	10	3/8"
LE-7130 12 17	12	3/8"
LE-7130 12 21	12	1/2"



Threaded Fitting, Exhaust Version, Metric & BSPP

1012	Thread
LE-7140 19 19	M5 x 0.8
LE-7140 10 10	1/8"
LE-7140 13 13	1/4"
LE-7140 17 17	3/8"
LE-7140 21 21	1/2"



Threaded Fitting, Exhaust Version, BSPP

1012	Thread
LE-7810 13 13	1/4"
LE-7810 17 17	3/8"




Threaded Fitting, Bi-directional, BSPP

1012	Thread
LE-7812 10 10	1/8"
LE-7812 13 13	1/4"

Fluid-Air Components Ltd

FLOW CONTROL REGULATORS & FUNCTION FITTINGS

Pilot Operated Vent Fittings





Male Thread, with Push-in Connection, BSPP

1012	OD mm	Thread
LE-7800 04 10	4	1/8"
LE-7800 06 10	6	1/8"
LE-7800 06 13	6	1/4"
LE-7800 08 13	8	1/4"
Tech Sheet 10628		



2/2 Manual Switch Operated Valve, BSPP

1012	OD mm	Thread
LE-7802 06 10	6	1/8"
LE-7802 06 13	6	1/4"
LE-7802 08 10	8	1/8"
LE-7802 08 13	8	1/4"
Tech Sheet 10628		

Pneumatic Sensor Fittings

Working Temperature: -15°C to +60°C

Working Pressure: 3 to 8 bar

Breaking Pressure: 0.6 bar

Response Time: 3ms



With LF 3000 Push-in Fittings for Nylon and PU Tubing, Metric & BSPP

1012	OD mm	Thread
LE-7818 04 19	4	M5 x 0.8
LE-7818 04 10	4	1/8"
LE-7818 04 13	4	1/4"
LE-7818 04 17	4	3/8"
LE-7818 04 21	4	1/2"
Tech Sheet 10632		



Threaded Fittings, Metric & BSPP

1012	Thread	Thread
LE-7818 19 10	1/8"	M5
LE-7818 19 13	1/4"	M5
Tech Sheet 10632		

In-line Non-return Valve



With LF 3000 Push-in Connector

1012	OD mm
LE-7996 04 00	4
LE-7996 06 00	6
LE-7996 08 00	8
LE-7996 10 00	10
LE-7996 12 00	12

Piloted Non-return Valves



BSPP

1012	OD mm	Thread
LE-7892 06 10	6	1/8"
LE-7892 08 10	8	1/8"
LE-7892 06 13	6	1/4"
LE-7892 08 13	8	1/4"
LE-7892 08 17	8	3/8"
Tech Sheet 10661		

Piloted Non-return, Regulator & Exhaust



BSPP

1012	OD mm	Thread
LE-7894 06 10	6	1/8"
LE-7894 08 10	8	1/8"
LE-7894 06 13	6	1/4"
LE-7894 08 13	8	1/4"
LE-7894 08 17	8	3/8"
Tech Sheet 10661		

SNAP CONNECTORS

Body with LF 3000 Connection



1012	OD A mm	OD B mm
LE-7926 05 06	6	5
LE-7926 05 08	8	5
LE-7926 07 10	10	7,3
Tech Sheet 10629		

Probe with LF 3000 Connection



1012	OD A mm	OD B mm
LE-7960 05 06	6	5
LE-7960 05 08	8	5
LE-7960 07 10	10	7,3
Tech Sheet 10629		

Fluid-Air Components Ltd

QS, STANDARD SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Wide range of variants: large selection for maximum flexibility in standard applications
- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum, (water as per manufacturer's declaration)

Male Studs



Male Thread, BSPP

0009	OD mm	Thread	Quantity	Manufacturer's Code
186106	4	G1/8"	10	QS-G1/8-4-I
186107	6	G1/8"	10	QS-G1/8-6-I
186109	8	G1/8"	10	QS-G1/8-10-I
186108	6	G1/4"	10	QS-G1/4-6-I
186110	8	G1/4"	10	QS-G1/4-8-I
186111	8	G3/8"	10	QS-G3/8-8-I
132999	10	G1/8"	10	QS-G3/8-10-I
186112	10	G1/4"	10	QS-G3/8-12-I
186113	10	G3/8"	10	QS-G1/2-12-I
186114	12	G3/8"	10	QS-G1/8-8-I
186115	12	G1/2"	1	QS-G1/4-10-I
Tech Sheet 70377				



Male Thread, BSPP (Hex Body)

0009	OD mm	Thread	Quantity	Manufacturer's Code
186095	4	G1/8"	10	QS-G1/8-4
186096	6	G1/8"	10	QS-G1/8-6
186097	6	G1/4"	10	QS-G1/4-6
186098	8	G1/8"	10	QS-G1/8-8
186099	8	G1/4"	10	QS-G1/4-8
186100	8	G3/8"	10	QS-G3/8-8
186101	10	G1/4"	10	QS-G1/4-10
186102	10	G3/8"	10	QS-G3/8-10
186350	12	G1/4"	10	QS-G1/4-12
186103	12	G3/8"	10	QS-G3/8-12
186104	12	G1/2"	1	QS-G1/2-12
Tech Sheet 70379				



Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153012	4	R1/8"	10	QS-1/8-4-I
153013	6	R1/8"	10	QS-1/8-6-I
153014	6	R1/4"	10	QS-1/4-6-I
153015	8	R1/8"	10	QS-1/8-8-I
153016	8	R1/4"	10	QS-1/4-8-I
153017	8	R3/8"	10	QS-3/8-8-I
190647	10	R1/8"	10	QS-1/8-10-I
153018	10	R1/4"	10	QS-1/4-10-I
153019	10	R3/8"	10	QS-3/8-10-I
190648	10	R1/2"	1	QS-1/2-10-I
190649	12	R1/4"	10	QS-1/4-12-I
153020	12	R3/8"	10	QS-3/8-12-I
153021	12	R1/2"	1	QS-1/2-12-I
Tech Sheet 70380				



Male Thread, BSPT (Hex Body)

0009	OD mm	Thread	Quantity	Manufacturer's Code
153001	4	R1/8"	10	QS-1/8-4
190644	4	R1/4"	10	QS-1/4-4
153002	6	R1/8"	10	QS-1/8-6
153003	6	R1/4"	10	QS-1/4-6
190645	6	R3/8"	10	QS-3/8-6
153004	8	R1/8"	10	QS-1/8-8
153005	8	R1/4"	10	QS-1/4-8
153006	8	R3/8"	10	QS-3/8-8
190643	10	R1/8"	10	QS-1/8-10
153007	10	R1/4"	10	QS-1/4-10
153008	10	R3/8"	10	QS-3/8-10
190646	10	R1/2"	1	QS-1/2-10
164980	12	R1/4"	10	QS-1/4-12
153009	12	R3/8"	10	QS-3/8-12
153010	12	R1/2"	1	QS-1/2-12
Tech Sheet 70378				


Female Studs



Female Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153022	4	R1/8"	10	QSF-1/8-4-B
130709	4	R1/8"	100	QSF-1/8-4-B-100
190650	4	R1/4"	10	QSF-1/4-4-B
153023	6	R1/8"	10	QSF-1/8-6-B
130712	6	R1/4"	100	QSF-1/4-6-B-100
130710	6	R1/8"	100	QSF-1/8-6-B-100
153024	6	R1/4"	10	QSF-1/4-6-B
190652	6	R3/8"	10	QSF-3/8-6-B
153025	8	R1/8"	10	QSF-1/8-8-B
130711	8	R1/8"	50	QSF-1/8-8-B-50
153026	8	R1/4"	10	QSF-1/4-8-B
130713	8	R1/4"	50	QSF-1/4-8-B-50
153027	8	R3/8"	10	QSF-3/8-8-B
130715	8	R3/8"	50	QSF-3/8-8-B-50
153028	10	R1/4"	10	QSF-1/4-10-B
130714	10	R1/4"	50	QSF-1/4-10-B-50
153029	10	R3/8"	10	QSF-3/8-10-B
130716	10	R3/8"	50	QSF-3/8-10-B-50
190651	12	R1/4"	10	QSF-1/4-12-B
153030	12	R3/8"	10	QSF-3/8-12-B
130717	12	R3/8"	20	QSF-3/8-12-B-20
190653	12	R1/2"	1	QSF-1/2-12-B
190654	16	R1/2"	1	QSF-1/2-16-B
Tech Sheet 70384				

FESTO



You might also need
Polyurethane Tubing
see pages **911-912**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

QS, STANDARD SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Wide range of variants: large selection for maximum flexibility in standard applications
- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum, (water as per manufacturer's declaration)

Male Stud 90° Elbows



Male Thread, BSPP

0009	OD mm	Thread	Quantity	Manufacturer's Code
186116	4	G1/8"	10	QSL-G1/8-4
186117	6	G1/8"	10	QSL-G1/8-6
186118	6	G1/4"	10	QSL-G1/4-6
186119	8	G1/8"	10	QSL-G1/8-8
186120	8	G1/4"	10	QSL-G1/4-8
186121	8	G3/8"	10	QSL-G3/8-8
186122	10	G1/4"	10	QSL-G1/4-10
186123	10	G3/8"	10	QSL-G3/8-10
186351	12	G1/4"	10	QSL-G1/4-12
186124	12	G3/8"	10	QSL-G3/8-12
186125	12	G1/2"	1	QSL-G1/2-12
Tech Sheet 70385				



Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153045	4	R1/8"	10	QSL-1/8-4
190659	4	R1/4"	10	QSL-1/4-4
153046	6	R1/8"	10	QSL-1/8-6
153047	6	R1/4"	10	QSL-1/4-6
190660	6	R3/8"	10	QSL-3/8-6
153048	8	R1/8"	10	QSL-1/8-8
153049	8	R1/4"	10	QSL-1/4-8
153050	8	R3/8"	10	QSL-3/8-8
190658	10	R1/8"	10	QSL-1/8-10
153051	10	R1/4"	10	QSL-1/4-10
153052	10	R3/8"	10	QSL-3/8-10
190661	10	R1/2"	1	QSL-1/2-10
164981	12	R1/4"	10	QSL-1/4-12
153053	12	R3/8"	10	QSL-3/8-12
153054	12	R1/2"	1	QSL-1/2-12
Tech Sheet 70386				

Male Stud 90° Extended Elbows



Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153076	4	R1/8"	10	QSLL-1/8-4
190662	4	R1/4"	10	QSLL-1/4-4
153077	6	R1/8"	10	QSLL-1/8-6
153078	6	R1/4"	10	QSLL-1/4-6
190663	6	R3/8"	10	QSLL-3/8-6
153079	8	R1/8"	10	QSLL-1/8-8
153080	8	R1/4"	10	QSLL-1/4-8
153081	8	R3/8"	10	QSLL-3/8-8
153082	10	R1/4"	10	QSLL-1/4-10
153083	10	R3/8"	10	QSLL-3/8-10
190664	10	R1/2"	1	QSLL-1/2-10
153084	12	R3/8"	10	QSLL-3/8-12
153085	12	R1/2"	1	QSLL-1/2-12
Tech Sheet 70393				

Female Stud 90° Elbows



Female Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153273	4	R1/8"	10	QSLF-1/8-4-B
153274	6	R1/8"	10	QSLF-1/8-6-B
153275	6	R1/4"	10	QSLF-1/4-6-B
153276	8	R1/8"	10	QSLF-1/8-8-B
153277	8	R1/4"	10	QSLF-1/4-8-B
153278	8	R3/8"	10	QSLF-3/8-8-B
153279	10	R1/4"	10	QSLF-1/4-10-B
153280	10	R3/8"	10	QSLF-3/8-10-B
Tech Sheet 70387				

Male Stud Tees



Branch Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153106	4	R1/8"	10	QST-1/8-4
190668	4	R1/4"	10	QST-1/4-4
153107	6	R1/8"	10	QST-1/8-6
153108	6	R1/4"	10	QST-1/4-6
190670	6	R3/8"	10	QST-3/8-6
153109	8	R1/8"	10	QST-1/8-8
153110	8	R1/4"	10	QST-1/4-8
153111	8	R3/8"	10	QST-3/8-8
190667	10	R1/8"	10	QST-1/8-10
153112	10	R1/4"	10	QST-1/4-10
153113	10	R3/8"	10	QST-3/8-10
190672	10	R1/2"	1	QST-1/2-10
190669	12	R1/4"	10	QST-1/4-12
153114	12	R3/8"	10	QST-3/8-12
153115	12	R1/2"	1	QST-1/2-12
Tech Sheet 70395				



Run Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153117	4	R1/8"	10	QSTL-1/8-4
153118	6	R1/8"	10	QSTL-1/8-6
153119	6	R1/4"	10	QSTL-1/4-6
153120	8	R1/8"	10	QSTL-1/8-8
153121	8	R1/4"	10	QSTL-1/4-8
153122	8	R3/8"	10	QSTL-3/8-8
153123	10	R1/4"	10	QSTL-1/4-10
153124	10	R3/8"	10	QSTL-3/8-10
153125	12	R3/8"	10	QSTL-3/8-12
153126	12	R1/2"	1	QSTL-1/2-12
Tech Sheet 70399				

FAC
Fluid-Air Components Ltd

QS, STANDARD SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Wide range of variants: large selection for maximum flexibility in standard applications
- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum, (water as per manufacturer's declaration)

Male Stud Ys



Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153138	4	R1/8"	10	QSY-1/8-4
190675	4	R1/4"	10	QSY-1/4-4
153139	6	R1/8"	10	QSY-1/8-6
153140	6	R1/4"	10	QSY-1/4-6
153141	8	R1/8"	10	QSY-1/8-8
153142	8	R1/4"	10	QSY-1/4-8
153143	8	R3/8"	10	QSY-3/8-8
153145	10	R3/8"	10	QSY-3/8-10
153144	10	R1/4"	10	QSY-1/4-10
153146	12	R3/8"	10	QSY-3/8-12
153147	12	R1/2"	1	QSY-1/2-12
Tech Sheet 70404				



Male Thread, Metric

0009	OD mm	Thread	Quantity	Manufacturer's Code
190673	4	M5	10	QSY-M5-4
190674	6	M5	10	QSY-M5-6
Tech Sheet 70405				

Male Stud 90° Ys



Male Thread, BSPT

0009	OD mm	Thread	Quantity	Manufacturer's Code
153172	4	R1/8"	1	QSYL-1/8-4
153173	6	R1/8"	1	QSYL-1/8-6
153174	6	R1/4"	1	QSYL-1/4-6
153175	8	R1/8"	1	QSYL-1/8-8
153176	8	R1/4"	1	QSYL-1/4-8
153177	8	R3/8"	1	QSYL-3/8-8
153178	10	R1/4"	1	QSYL-1/4-10
153179	10	R3/8"	1	QSYL-3/8-10
153180	12	R3/8"	1	QSYL-3/8-12
153181	12	R1/2"	1	QSYL-1/2-12
Tech Sheet 70401				

Single Banjos



Male Thread, BSPT (Hex Body)

0009	OD mm	Thread	Quantity	Manufacturer's Code
153086	4	R1/8"	10	QSLV-1/8-4
153087	6	R1/8"	10	QSLV-1/8-6
153088	6	R1/4"	10	QSLV-1/4-6
153089	8	R1/8"	10	QSLV-1/8-8
153090	8	R1/4"	10	QSLV-1/4-8
153091	8	R3/8"	10	QSLV-3/8-8
153092	10	R1/4"	10	QSLV-1/4-10
153093	10	R3/8"	10	QSLV-3/8-10
153094	12	R3/8"	10	QSLV-3/8-12
153095	12	R1/2"	1	QSLV-1/2-12
Tech Sheet 70392				



Male Thread, BSPP (Hex Body)

0009	OD mm	Thread	Quantity	Manufacturer's Code
186137	4	G1/8"	10	QSLV-G1/8-4
190666	6	M5	10	QSLV-M5-6
186138	6	G1/8"	10	QSLV-G1/8-6
186139	6	G1/4"	10	QSLV-G1/4-6
186140	8	G1/8"	10	QSLV-G1/8-8
186141	8	G1/4"	10	QSLV-G1/4-8
186142	8	G3/8"	10	QSLV-G3/8-8
186143	10	G1/4"	10	QSLV-G1/4-10
186144	10	G3/8"	10	QSLV-G3/8-10
186145	12	G3/8"	10	QSLV-G3/8-12
186146	12	G1/2"	1	QSLV-G1/2-12
Tech Sheet 70390				

Tube x Tube Connectors



Equal Straights

0009	OD mm	Quantity	Manufacturers Code
153031	4	10	QS-4
153032	6	10	QS-6
153033	8	10	QS-8
153034	10	10	QS-10
153035	12	10	QS-12
Tech Sheet 70417			



Unequal Straights

0009	OD mm	OD mm	Quantity	Manufacturers Code
153037	6	4	10	QS-6-4
130606	8	4	10	QS-8-4
153038	8	6	10	QS-8-6
130607	10	6	10	QS-10-6
153039	10	8	10	QS-10-8
130608	12	8	10	QS-12-8
153040	12	10	10	QS-12-10
Tech Sheet 70418				



Equal Bulkheads with Fixed Collar

0009	OD mm	Quantity	Manufacturers Code
130642	8	10	QSS-8-F
130643	10	10	QSS-10-F
130644	12	10	QSS-12-F
Tech Sheet 70421			



Equal Bulkheads

0009	OD mm	Quantity	Manufacturers Code
153157	4	10	QSS-4
153158	6	10	QSS-6
153159	8	10	QSS-8
153160	10	10	QSS-10
153161	12	10	QSS-12
Tech Sheet 70422			

Fluid-Air Components Ltd

QS, STANDARD SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Wide range of variants: large selection for maximum flexibility in standard applications
- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum, (water as per manufacturer's declaration)

Tube x Tube Connectors



Equal Elbows

0009	OD mm	Quantity	Manufacturers Code
153070	4	10	QSL-4
153071	6	10	QSL-6
153072	8	10	QSL-8
153073	10	10	QSL-10
153074	12	10	QSL-12
Tech Sheet 70424			



Equal Tees

0009	OD mm	Quantity	Manufacturers Code
153128	4	10	QST-4
153129	6	10	QST-6
153130	8	10	QST-8
153131	10	10	QST-10
153132	12	10	QST-12
Tech Sheet 70426			



Unequal Tees

0009	OD mm	OD mm	Quantity	Manufacturers Code
153134	6	4	10	QST-6-4
130613	8	4	10	QST-8-4
153135	8	6	10	QST-8-6
130614	10	6	10	QST-10-6
153136	10	8	10	QST-10-8
130615	12	8	10	QST-12-8
153137	12	10	10	QST-12-10
130616	16	12	1	QST-16-12
Tech Sheet 70427				



Equal Ys

0009	OD mm	Quantity	Code
153148	4	10	QSY-4
153149	6	10	QSY-6
153150	8	10	QSY-8
153151	10	10	QSY-10
153152	12	10	QSY-12
Tech Sheet 70429			



Unequal Ys

0009	OD mm	OD mm	Quantity	Manufacturer's Code
153153	6	4	10	QSY-6-4
130610	8	4	10	QSY-8-4
153154	8	6	10	QSY-8-6
130611	10	6	10	QSY-10-6
153155	10	8	10	QSY-10-8
130612	12	8	10	QSY-12-8
153156	12	10	10	QSY-12-10
190708	16	12	1	QSY-16-12
Tech Sheet 70430				



Tube x Stem Connectors

Straights, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Code
153041	6	4	10	QS-6H-4
130622	8	4	10	QS-8H-4
153042	8	6	10	QS-8H-6
130623	10	6	10	QS-10H-6
153043	10	8	10	QS-10H-8
132981	12	6	10	QS-12H-6
130624	12	8	10	QS-12H-8
153044	12	10	10	QS-12H-10
130698	12	10	20	QS-12H-10-20
Tech Sheet 70431				



Elbows, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Manufacturers Code
153056	4	4	10	QSL-4H
153057	6	6	10	QSL-6H
153058	8	8	10	QSL-8H
153059	10	10	10	QSL-10H
153060	12	12	10	QSL-12H
Tech Sheet 70432				



Reducing Elbows, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Code
153061	6	4	10	QSL-6H-4
153062	8	6	10	QSL-8H-6
153063	10	8	10	QSL-10H-8
Tech Sheet 70433				

Tube x Tube Plugs



Tube

0009	OD mm	Quantity	Code
153262	4	10	QSC-4
153263	6	10	QSC-6
153264	8	10	QSC-8
153265	10	10	QSC-10
153266	12	10	QSC-12
Tech Sheet 70440			

Tube x Stem Extended Connectors



Elbows, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Code
153065	4	4	10	QSL-4HL
153066	6	6	10	QSL-6HL
153067	8	8	10	QSL-8HL
153068	10	10	10	QSL-10HL
153069	12	12	10	QSL-12HL
Tech Sheet 70434				

Tube x Stem Plugs



Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Manufacturers Code
153267	4	4	10	QSC-4H
153268	6	6	10	QSC-6H
153269	8	8	10	QSC-8H
153270	10	10	10	QSC-10H
153271	12	12	10	QSC-12H
Tech Sheet 70441				

Fluid-Air Components Ltd

QS, MINIATURE SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Compact for maximum component density in confined installation space
- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum

Male Studs



Male Thread, BSPP

0009	OD mm	Thread	Quantity	Code
186266	4	G1/8"	10	QSM-G1/8-4-I
186267	6	G1/8"	10	QSM-G1/8-6-I
Tech Sheet 70481				



Male Thread, Metric & BSPT

0009	OD mm	Thread	Quantity	Code
153314	4	M3	10	QSM-M3-4-I
153315	4	M5	10	QSM-M5-4-I
153319	4	M7	10	QSM-M7-4-I
153316	4	R1/8"	10	QSM-1/8-4-I
153321	6	M7	10	QSM-M7-6-I
153317	6	M5	10	QSM-M5-6-I
153318	6	R1/8"	10	QSM-1/8-6-I
Tech Sheet 70479				



Male Thread, BSPP (Hex Body)

0009	OD mm	Thread	Quantity	Code
186264	4	R1/8"	10	QSM-G1/8-4
186265	6	R1/8"	10	QSM-G1/8-6
Tech Sheet 70480				



Male Thread, Metric & BSPT (Hex Body)

0009	OD mm	Thread	Quantity	Code
153303	4	M3	10	QSM-M3-4
153304	4	M5	10	QSM-M5-4
153305	4	R1/8"	10	QSM-1/8-4
153306	6	M5	10	QSM-M5-6
132600	6	M6	10	QSM-M6-6
153307	6	R1/8"	10	QSM-1/8-6
Tech Sheet 70478				

Male Stud 90° Elbows



Male Thread, BSPP

0009	OD mm	Thread	Quantity	Code
186268	4	G1/8"	10	QSML-G1/8-4
186269	6	G1/8"	10	QSML-G1/8-6
Tech Sheet 70484				



Male Thread, Metric & BSPT

0009	OD mm	Thread	Quantity	Code
153332	4	M3	10	QSML-M3-4
153333	4	M5	10	QSML-M5-4
186352	4	M7	10	QSML-M7-4
153334	4	R1/8"	10	QSML-1/8-4
153335	6	M5	10	QSML-M5-6
186353	6	M7	10	QSML-M7-6
153336	6	R1/8"	10	QSML-1/8-6
Tech Sheet 70483				

FESTO

You might also need
SPAN Series Pressure Sensors
see page **428**



FAC
Fluid-Air Components Ltd

QS, MINIATURE SERIES PUSH-IN FITTINGS

FESTO

Ambient Temperature:
-10°C to +80°C

Temperature Dependant Operating Pressure:
- 0.95 to 6 bar at 80°C
- 0.95 to 14 bar at 20°C

- Simple and reliable connection and release
- Compact for maximum component density in confined installation space

- PBT housing, POM release ring, NBR tube seal
- Operating media: compressed air, vacuum

Tube x Tube Connectors



Equal Straights

0009	OD mm	Quantity	Code
153324	4	10	QSM-4
153325	6	10	QSM-6
Tech Sheet 70491			



Equal Tees

0009	OD mm	Quantity	Code
153366	4	10	QSMT-4
153367	6	10	QSMT-6
Tech Sheet 70494			



Unequal Straights

0009	OD mm	OD mm	Quantity	Code
153326	4	3	10	QSM-4-3
153327	6	4	10	QSM-6-4
Tech Sheet 70492				



Unequal Tees

0009	OD mm	OD mm	Quantity	Code
153368	4	3	10	QSMT-4-3
153369	6	4	10	QSMT-6-4
Tech Sheet 70495				



Equal Bulkheads

0009	OD mm	Quantity	Code
153376	4	10	QSMS-4
153377	6	10	QSMS-6
Tech Sheet 70498			



Equal Ys

0009	OD mm	Quantity	Code
153371	4	10	QSMY-4
153372	6	10	QSMY-6
Tech Sheet 70496			



Equal Elbows

0009	OD mm	Quantity	Code
153344	4	10	QSML-4
153345	6	10	QSML-6
Tech Sheet 70493			



Unequal Ys

0009	OD mm	OD mm	Quantity	Code
153373	4	3	10	QSMY-4-3
153374	6	4	10	QSMY-6-4
Tech Sheet 70497				

Tube x Stem Connectors



Unequal Straights, Tube x Stem

0009	ODmm	Stem OD mm	Quantity	Code
153328	4	3	10	QSM-4H-3
153329	6	4	10	QSM-6H-4
Tech Sheet 70499				



Equal Elbows, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Code
153347	4	4	10	QSML-4H
153348	6	6	10	QSML-6H
Tech Sheet 70500				



Unequal Elbows, Tube x Stem

0009	OD mm	Stem OD mm	Quantity	Code
153349	4	3	10	QSML-4H-3
153350	6	4	10	QSML-6H-4
Tech Sheet 70501				


Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FLOW REGULATORS & FUNCTION FITTINGS

For the full range and more information, please contact one of our sales team.

FLOW REGULATORS

Features



Product Description

VFOE	-	L	-	E/S	-	T	-	M/G/R	-	Q	-	F1A/NONE
Series		Design		Function		Adjusting component		Pneumatic connection 2		Pneumatic connection 1		Special material properties

Fluid-Air Components Ltd

One-way Flow Control Valves, Elbow Outlet

Ambient Temperature:
-10°C to +60°C

Working Pressure:
0.2 to 10 bar

- Sturdy metal design
- Can be swivelled around the screw-in axis after mounting
- Push-in connector

- Polymer design
- Can be rotated 360° around the screw-in axis after mounting/not permitted for continuous rotation
- Push-in connector

- Polymer design



Exhaust Control, Rotary Knob Detented, Metric & BSPP

0009	OD mm	Thread	Manufacturer's Code
8068723	4	M5	VFOE-LE-T-M5-Q4
8068724	6	M5	VFOE-LE-T-M5-Q6
8068725	4	1/8"	VFOE-LE-T-G18-Q4
8068726	6	1/8"	VFOE-LE-T-G18-Q6
8068727	8	1/8"	VFOE-LE-T-G18-Q8
8068728	6	1/4"	VFOE-LE-T-G14-Q6
8068729	8	1/4"	VFOE-LE-T-G14-Q8
8068732	10	3/8"	VFOE-LE-T-G38-Q10
Tech Sheet 71679			

Exhaust Control, Rotary Knob Detented, BSPT

0009	OD mm	Thread	Manufacturer's Code
8068734	4	1/8"	VFOE-LE-T-R18-Q4
8068735	6	1/8"	VFOE-LE-T-R18-Q6
8068736	8	1/8"	VFOE-LE-T-R18-Q8
Tech Sheet 71679			

- Polymer design



Supply Air One-way Detented Flow Control Function, BSPP

0009	OD mm	Thread	Manufacturer's Code
8068747	4	1/8"	VFOE-LS-T-G18-Q4
8068748	6	1/8"	VFOE-LS-T-G18-Q6
8068749	8	1/8"	VFOE-LS-T-G18-Q8

Supply Air One-way Detented, Flow Control Function, BSPT

0009	OD mm	Thread	Manufacturer's Code
8068750	4	1/8"	VFOE-LS-T-R18-Q4
8068751	6	1/8"	VFOE-LS-T-R18-Q6
8068752	8	1/8"	VFOE-LS-T-R18-Q8

- Sturdy metal design



Supply Control, Slotted Head Screw, Male Thread, Metric & BSPP x Push-in

0009	OD mm	Thread	Manufacturer's Code
193153	3	M5	GRLZ-M5-QS-3-D
193156	3	G1/8"	GRLZ-1/8-QS-3-D
193154	4	M5	GRLZ-M5-QS-4-D
193157	4	G1/8"	GRLZ-1/8-QS-4-D
193155	6	M5	GRLZ-M5-QS-6-D
193158	6	G1/8"	GRLZ-1/8-QS-6-D
193159	8	G1/8"	GRLZ-1/8-QS-8-D
Tech Sheet 71232			

- Sturdy metal design



Exhaust Control, Slotted Head Screw, Male Thread, Metric & BSPP x Push-in

0009	OD mm	Thread	Manufacturer's Code
193137	3	M5	GRLA-M5-QS-3-D
193142	3	G1/8"	GRLA-1/8-QS-3-D
193138	4	M5	GRLA-M5-QS-4-D
193143	4	G1/8"	GRLA-1/8-QS-4-D
193139	6	M5	GRLA-M5-QS-6-D
193144-FESTO	6	G1/8"	GRLA-1/8-QS-6-D
193146	6	G1/4"	GRLA-1/4-QS-6-D
193149	6	G3/8"	GRLA-3/8-QS-6-D
193145	8	G1/8"	GRLA-1/8-QS-8-D
193147	8	G1/4"	GRLA-1/4-QS-8-D
193150	8	G3/8"	GRLA-3/8-QS-8-D
193148	10	G1/4"	GRLA-1/4-QS-10-D
193151	10	G3/8"	GRLA-3/8-QS-10-D
193152	12	G1/2"	GRLA-1/2-QS-12-D
Tech Sheet 71233			

- Sturdy metal design



Exhaust Control, Knurled Screw, Male Thread, Metric & BSPP x Push-in

0009	OD mm	Thread	Manufacturer's Code
197576	3	M5	GRLA-M5-QS-3-RS-D
197579	3	G1/8"	GRLA-1/8-QS-3-RS-D
197577	4	M5	GRLA-M5-QS-4-RS-D
197580	4	G1/8"	GRLA-1/8-QS-4-RS-D
197578	6	M5	GRLA-M5-QS-6-RS-D
197581	6	G1/8"	GRLA-1/8-QS-6-RS-D
534338	6	G1/4"	GRLA-1/4-QS-6-RS-D
534341	6	G3/8"	GRLA-3/8-QS-6-RS-D
534337	8	G1/8"	GRLA-1/8-QS-8-RS-D
534339	8	G1/4"	GRLA-1/4-QS-8-RS-D
534342	8	G3/8"	GRLA-3/8-QS-8-RS-D
534340	10	G1/4"	GRLA-1/4-QS-10-RS-D
534343	10	G3/8"	GRLA-3/8-QS-10-RS-D
534344	12	G1/2"	GRLA-1/2-QS-12-RS-D
Tech Sheet 71237			

- Sturdy metal design



Medium Flow, Exhaust Control, Slotted Head Screw, Male Thread, Metric & BSPP x Push-in

0009	OD mm	Thread	Manufacturer's Code
537075	6	G1/8"	GRLA-1/8-QS-6-MF-D
537076	8	G1/8"	GRLA-1/8-QS-8-MF-D
Tech Sheet 71236			

FAC
Fluid-Air Components Ltd

FUNCTION FITTINGS

FESTO

Piloted Non-return Valves

- Controlled, piloted non-return function
- Manual exhausting
- Rotatable when installed
- Push-in fittin

Working Pressure:
0.5 to 10 bar
Pilot Pressure:
2 to 10 bar (M5,1/8.1/4)
1 to 10 bar (3/8, 1/2)

Ambient Temperature:
-10°C to +60°C



Male Thread, BSPP

0009	Thread	Manufacturer's Code
530029	M5	HGL-M5-B
530030	G1/8"	HGL-1/8-B
530031	G1/4"	HGL-1/4-B
530032	G3/8"	HGL-3/8-B
530033	G1/2"	HGL-1/2-B
Tech Sheet 71243		



Male Thread BSPP x Push-in

0009	OD mm	Thread	Manufacturer's Code
530038	4	M5	HGL-M5-QS-4
530039	4	G1/8"	HGL-1/8-QS-4
530040	6	G1/8"	HGL-1/8-QS-6
530041	8	G1/4"	HGL-1/4-QS-8
530043	8	G3/8"	HGL-3/8-QS-8
530042	10	G1/4"	HGL-1/4-QS-10
530044	10	G3/8"	HGL-3/8-QS-10
530045	12	G1/2"	HGL-1/2-QS-12
Tech Sheet 71242			

Differential Pressure Regulator

- Constant differential pressure between input and output
- Cuts energy usage on cylinder return stroke approx 20%
- Connecting thread M5, R1/8, R1/4, R3/8, R1/2
- Push-in connector for tubing OD 4, 6, 8, 10, 12mm
- Rotatable 360 degrees

new product



Energy Saving Regulator LRL, LRLL

0010	Thread	Outlet Port	Type
153510	M5	Top	LRL-M5-QS-4
153512	M5	Top	LRL-M5-QS-6
153511	1/8"	Top	LRL-1/8-QS-4
153513	1/8"	Top	LRL-1/8-QS-6
153515	1/8"	Top	LRL-1/8-QS-8
153514	1/4"	Top	LRL-1/4-QS-6
153516	1/4"	Top	LRL-1/4-QS-8
153518	1/4"	Top	LRL-1/4-QS-10
153517	3/8"	Top	LRL-3/8-QS-8
153519	3/8"	Top	LRL-3/8-QS-10
153520	3/8"	Top	LRL-3/8-QS-12
153521	1/2"	Top	LRL-1/2-QS-12
153498	M5	Side	LRLL-M5-QS-4
153500	M5	Side	LRLL-M5-QS-6
153499	1/8"	Side	LRLL-1/8-QS-4
153501	1/8"	Side	LRLL-1/8-QS-6
153503	1/8"	Side	LRLL-1/8-QS-8
153502	1/4"	Side	LRLL-1/4-QS-6
153504	1/4"	Side	LRLL-1/4-QS-8
153506	1/4"	Side	LRLL-1/4-QS-10
153505	3/8"	Side	LRLL-3/8-QS-8
153507	3/8"	Side	LRLL-3/8-QS-10
153508	3/8"	Side	LRLL-3/8-QS-12
153509	1/2"	Side	LRLL-1/2-QS-12
More variants available online			

FESTO

You might also need
SFAB Series Flow Sensors
see page **427**



FAC
Fluid-Air Components Ltd

55000 SERIES, 20 BAR RATED

AIGNEP

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar

BSPT in conformity with ISO 7.1, BS 21, DIN 2999.
BSPP in conformity with ISO 228 Class A.
Metric in conformity with ISO R/262.
Fittings with "Short" tapered thread allow assembly with tapered as well as parallel threads (BSPT, NPT and BSPP) and have reduced overall height.2

Straight Male Adaptors

This is a Taper Thread designed so that it's suitable for BSPT, BSPP, NPTF and Metric.



Universal Short Thread Type

1020	OD mm	Thread
5500000001	4	1/8"
5500000013	4	1/4"
5500000002	5	1/8"
5500000003	5	1/4"
5500000004	6	1/8"
5500000005	6	1/4"
5500000014	6	3/8"
5500000015	6	1/2"
5500000006	8	1/8"
5500000007	8	1/4"
5500000008	8	3/8"
5500000016	8	1/2"
5500000009	10	1/4"
5500000010	10	3/8"
5500000017	10	1/2"
5500000011	12	1/4"
5500000012	12	3/8"
5500000018	12	1/2"
5500000019	14	3/8"
5500000020	14	1/2"
Tech Sheet 10709		



(Round Body) BSPT

1020	OD mm	Thread
5501000001	4	1/8"
5501000002	6	1/8"
5501000003	6	1/4"
5501000004	8	1/8"
5501000005	8	1/4"
Tech Sheet 10709		



(Hex Body) Metric & BSPP

1020	OD mm	Thread
5002000N01	4	M5
5002000N02	4	1/8"
5002000N22	4	1/4"
5002000N18	5	M5
5002000N19	5	1/8"
5002000N20	6	M5
5002000N12	6	M12 x 1
5002000N13	6	M12 x 1.25
5002000N14	6	M12 x 1.5
5002000N03	6	1/8"
5002000N04	6	1/4"
5002000N27	6	3/8"
5002000N28	6	1/2"
5002000N17	8	M12 x 1.5
5002000N05	8	1/8"
5002000N06	8	1/4"
5002000N07	8	3/8"
5002000N29	8	1/2"
5002000N08	10	1/4"
5002000N09	10	3/8"
5002000N31	10	1/2"
5002000N32	12	1/4"
5002000N11	12	3/8"
5002000N23	12	1/2"
5002000N24	14	3/8"
5002000N25	14	1/2"
Tech Sheet 10709		

Straight Female Adaptors



(Hex Body) Metric & BSPT

1020	OD mm	Thread
5003000N08	4	M5
5003000N01	4	1/8"
5003000N09	4	1/4"
5003000N06	5	1/8"
5003000N02	6	1/8"
5003000N03	6	1/4"
5003000N04	8	1/8"
5003000N05	8	1/4"
5003000N10	8	3/8"
5003000N11	10	1/4"
5003000N12	10	3/8"
5003000N13	10	1/2"
5003000N14	12	3/8"
5003000N15	12	1/2"
Tech Sheet 10709		

Bulkhead Connectors



Tube x Tube

1020	OD mm
5005000N01	4
5005000N06	5
5005000N02	6
5005000N03	8
5005000N04	10
5005000N05	12
Tech Sheet 10709	

55000 SERIES METAL BODY PUSH-IN FITTINGS

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar

Parallel gas in conformity with ISO 228 Class A
Metric in conformity with ISO R/262

Straight Connectors



Equal Straight Connectors

1020	OD mm
55040-4	4
55040-5	5
55040-6	6
55040-8	8
55040-10	10
55040-12	12
55040-14	14
Tech Sheet 10709	

Unequal Straight Connectors

1020	OD mm	OD mm
55040-6-4	6	4
55040-8-6	8	6
55040-10-8	10	8
55040-12-10	12	10
55040-10-6	10	6
Tech Sheet 10709		

AIGNEP



For **PRO3**
see page **420**

Male Swivel Elbows

This is a taper thread designed so that its suitable for BSPT, BSPP, NPTF and metric.



Universal Short Thread Type

1020	OD mm	Thread
55111-4-1/8	4	1/8"
55111-4-1/4	4	1/4"
55111-5-1/8	5	1/8"
55111-6-1/2	6	1/2"
55111-6-1/8	6	1/8"
55111-6-1/4	6	1/4"
55111-6-3/8	6	3/8"
55111-8-1/8	8	1/8"
55111-8-1/4	8	1/4"
55111-8-3/8	8	3/8"
55111-8-1/2	8	1/2"
55111-10-1/4	10	1/4"
55111-10-3/8	10	3/8"
55111-10-1/2	10	1/2"
55111-12-1/4	12	1/4"
55111-12-3/8	12	3/8"
55111-12-1/2	12	1/2"
55111-14-3/8	14	3/8"
55111-14-1/2	14	1/2"
Tech Sheet 10709		



Metric & BSPP

1020	OD mm	Thread
55116-4-M3X0.5	4	M3 x 0.5
55116-4-M5	4	M5
55116-4-M7X1	4	M7 x 1
55116-4-1/8	4	1/8"
55116-4-1/4	4	1/4"
55116-5-M5	5	M5
55116-5-1/8	5	1/8"
55116-6-M5	6	M5
55116-6-1/8	6	1/8"
55116-6-1/4	6	1/4"
55116-6-3/8	6	3/8"
55116-6-1/2	6	1/2"
55116-8-1/8	8	1/8"
55116-8-1/4	8	1/4"
55116-8-3/8	8	3/8"
55116-8-1/2	8	1/2"
55116-10-1/4	10	1/4"
55116-10-3/8	10	3/8"
55116-10-1/2	10	1/2"
55116-12-1/4	12	1/4"
55116-12-3/8	12	3/8"
55116-12-1/2	12	1/2"
55116-14-3/8	14	3/8"
55116-14-1/2	14	1/2"
Tech Sheet 10709		

Elbow Connectors



Equal Elbow Connectors

1020	OD mm
55130-4	4
55130-5	5
55130-6	6
55130-8	8
55130-10	10
55130-12	12
55130-14	14
Tech Sheet 10709	



Equal Stem Elbows

1020	OD mm
55140-4	4
55140-6	6
55140-8	8
55140-10	10
55140-12	12
Tech Sheet 10709	

Reducing Stem Elbows

1020	OD mm	Stem OD mm
55140-4-6	4	6
55140-6-4	6	4
55140-8-10	8	10
55140-10-12	10	12
Tech Sheet 10709		

Fluid-Air Components Ltd

55000 SERIES, 20 BAR RATED

AIGNEP

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar

Vacuum: -0.99 bar

Parallel gas in conformity with ISO 228 Class A
Metric in conformity with ISO R/262

Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT

Tee Connectors



Equal Tees

1020	OD mm
55230-4	4
55230-5	5
55230-6	6
55230-8	8
55230-10	10
55230-12	12
55230-14	14
Tech Sheet 10709	



Equal Stem Tees

1020	OD mm
55240-4	4
55240-6	6
55240-8	8
55240-10	10
55240-12	12
Tech Sheet 10709	



Reducing Stem Tees

1020	OD mm	Stem OD mm
55240-4-6	4	6
55240-6-4	6	4
55240-8-10	8	10
55240-10-12	10	12
Tech Sheet 10709		

Y Connectors



Equal Y Connectors

1020	OD mm
55310-4	4
55310-6	6
55310-8	8
55310-10	10
55310-12	12
Tech Sheet 10709	

In-line Manifolds



Reducing, Tube x Tube

1020	OD mm	OD mm
55350-6-4	6	4
55350-8-4	8	4
55350-8-6	8	6
55350-10-6	10	6
55350-10-8	10	8
Tech Sheet 10709		

Double Y Connectors



Tube x Tube, Reducing

1020	OD mm	OD mm
55330-4-4	4	4
55330-4-6	6	4
55330-6-6	6	6
55330-6-8	8	6
Tech Sheet 10709		



Tube x Male Thread, Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
55340-4-1/8	4	1/8"
55340-4-1/4	4	1/4"
55340-6-1/8	6	1/8"
55340-6-1/4	6	1/4"
Tech Sheet 10709		



Tube x Male Thread, BSPP

1020	OD mm	Thread
55345-4-1/8	4	1/8"
55345-4-1/4	4	1/4"
55345-6-1/8	6	1/8"
55345-6-1/4	6	1/4"
Tech Sheet 10709		

Banjos



Single Body, Metric & BSPP

1020	OD mm	Thread
55500-4-M5	4	M5
55500-4-M6	4	M6
55500-4-1/8	4	1/8"
55500-5-M5	5	M5
55500-5-M6	5	M6
55500-5-1/8	5	1/8"
55500-5-1/4	5	1/4"
55500-6-M5	6	M5
55500-6-M6	6	M6
55500-6-1/8	6	1/8"
55500-6-1/4	6	1/4"
55500-8-1/8	8	1/8"
55500-8-1/4	8	1/4"
55500-8-3/8	8	3/8"
55500-10-3/8	10	3/8"
55500-12-3/8	12	3/8"
55500-12-1/2	12	1/2"
Tech Sheet 10709		



Double Banjo Body, Metric & BSPP

1020	OD mm	Thread
55510-4-M5	4	M5
55510-5-1/8	5	1/8"
55510-5-1/4	5	1/4"
55510-6-1/8	6	1/8"
55510-6-1/4	6	1/4"
55510-8-1/8	8	1/8"
55510-8-1/4	8	1/4"
Tech Sheet 10709		

55000 SERIES, 20 BAR RATED

Banjo Bolts



Single, Metric & BSPP

1020	Thread
55410-M5	M5
55410-M6	M6
55410-1/8	1/8"
55410-1/4	1/4"
55410-3/8	3/8"
55410-1/2	1/2"
55410-M12X1.5	M12 x 1.5
Tech Sheet 10709	



Double, BSPP

1020	Thread
55420-1/8	1/8"
55420-1/4	1/4"
55420-3/8	3/8"
55420-1/2	1/2"
Tech Sheet 10709	



Triple, BSPP

1020	Thread
55430-1/8	1/8"
55430-1/4	1/4"
55430-3/8	3/8"
55430-1/2	1/2"
Tech Sheet 10709	

56000 SERIES - MINIATURE PUSH-IN FITTINGS

Working Temperature: -20 to 80

Maximum Working Pressure: 20 bar (290 psi)

Vacuum: -0.99 bar

Male Studs



Male Thread, Metric

1020	OD mm	Thread
MP1-2-M3	2	M3
MP1-2-M5	2	M5
MP1-3-M3	3	M3
MP1-3-M5	3	M5
Tech Sheet 984		

Swivel Male Stud Elbow



Male Thread, Metric

1020	OD mm	Thread
MP7-2-M3	2	M3
MP7-2-M5	2	M5
MP7-3-M3	3	M3
MP7-3-M5	3	M5
Tech Sheet 984		

Swivel Tee Male Centre Leg



Male Thread, Metric

1020	OD mm	Thread
MP12-3-M5	3	M5
Tech Sheet 984		

For **Quick Couplings for Plastic Injection Moulding** see page **391**



Fluid-Air Components Ltd

METRIC PUSH-IN FITTINGS, TECHNOPOLYMER

Straight Connector



Tube x Tube

9151	Tube OD mm
2019001	4
2019002	5
2019003	6
2019004	8
2019005	10
2019006	12

Equal Elbow



Tube x Tube

9151	Tube OD mm
2L21001	4
2021002	5
2L21003	6
2L21004	8
2021005	10
2021006	12

Equal Tee



Tube x Tube

9151	Tube OD mm
2L22001	4
2022002	5
2L22003	6
2L22004	8
2022005	10
2022006	12

Male Stud Swivel Elbow



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L34001	M5	4
2L34002	G1/8"	4
2L34003	G1/4"	4
2L34006	M5	6
2L34007	G1/8"	6
2L34008	G1/4"	6
2L34009	G1/8"	8
2L34010	G1/4"	8
2L34011	G3/8"	8
2L34013	G1/4"	10
2L34014	G3/8"	10
2L34016	G3/8"	12
2L34017	G1/2"	12

Female Stud Swivel Elbow



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L34F01	M5	4
2L34F06	M5	6
2L34F05	G1/8"	4
2L34F07	G1/8"	6
2L34F08	G1/4"	6
2L34F09	G1/8"	8
2L34F10	G1/4"	8

Plug



Stem

9151	Tube OD mm
2L10001	4
2010002	5
2L10003	6
2L10004	8
2L10005	10
2L10006	12
2010007	14

Male Stud Swivel Tee



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L35001	M5	4
2L35002	G1/8"	4
2L35003	G1/4"	4
2L35006	M5	6
2L35007	G1/8"	6
2L35008	G1/4"	6
2L35009	G1/8"	8
2L35010	G1/4"	8
2L35011	G3/8"	8
2L35013	G1/4"	10
2L35014	G3/8"	10
2L35016	G3/8"	12
2L35017	G1/2"	12

Equal Y



Tube x Tube

9151	Tube OD mm
2023001	4
2023002	5
2023003	6
2023004	8
2L23005	10
2L23006	12

Male Stud Y



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L23402	G1/8"	4
2L23403	G1/4"	4
2L23406	G1/8"	6
2L23407	G1/4"	6
2L23409	G1/8"	8
2L23410	G1/4"	8
2L23412	G3/8"	8

Fluid-Air Components Ltd

METRIC PUSH-IN FITTINGS, TECHNOPOLYMER

Y Stem



Stem x Tube

9151	OD mm Stem	OD mm Tube
2024001	4	4
2024003	6	6
2L24004	8	8
2L24005	10	10
2L24006	12	12

Y Elbow



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L25003	G1/8"	4
2L25004	G1/8"	6
2L25005	G1/4"	6
2L25008	G1/4"	8
2L25009	G3/8"	8

Plug-in Elbow



Stem x Tube

9151	Stem OD mm	Tube OD mm
2L46001	4	4
2L46002	6	6
2L46003	8	8
2L46004	10	10

Distribution Fitting



Tube x Tube

9151	Tube OD mm A	Tube OD mm B
2L42001	4	4
2L42002	6	4
2L42004	6	6
2L42005	8	6

Distribution Fitting



BSP Parallel x Tube

9151	Thread BSPP	Tube OD mm
2L43001	M5	4
2L43002	G1/8"	4
2L43003	G1/4"	4
2L43008	G1/8"	6
2L43009	G1/4"	6

Tube Removal Tool



For use with Push-in Fittings

9150	To Suit Tube mm
2017001	4-14

Aluminium Distribution Manifold



BSP Parallel x Tube Inlet Ports

9185	BSPP Inlet Thread	Tube OD mm	Outlets
7304106	G1/8"	4	6
7304112	G1/8"	4	12
7306206	G1/4"	6	6
7306212	G1/4"	6	12
7308306	G3/8"	8	6
7308312	G3/8"	8	12

For **Round RNDC Cylinders** see page **538**




Fluid-Air Components Ltd

PUSH-IN FITTINGS KITS

A convenient range of Metal Work push-in fittings in a kit. Comprising of seventeen removable compartments. These are contained in a hand carry case measuring 57mm deep x 340mm long x 265mm wide, made from tough polypropylene, with a clear view plastic hinged lid, sliding locks and carry handle. There are four pneumatic push-in fittings kits available: 4mm, 6mm 8mm and a 6/8mm combination.






Push-in Fittings Kit

4mm Outside Diameter


9153	Description
HANDYFIT-4	Assorted



Push-in Fittings Kit

8mm Outside Diameter


9153	Description
HANDYFIT-8	Assorted



Push-in Fittings Kit

6mm Outside Diameter

9153	Description
HANDYFIT-6	Assorted



Push-in Fittings Kit

6mm & 8mm Outside Diameter

9153	Description
HANDYFIT-6/8	Assorted

FLOW MICRO-REGULATORS

MFR Compact 'O' Threaded Brass Ring

Technical Features

- The job of flow micro-regulators is to regulate speed in the pneumatic cylinders. The configuration of both type C (to be mounted on the cylinder inlet) and type V (to be mounted on the valve port) is such as to ensure full flow on feed and regulated flow on charge. ype B (bidirectional) can be used to regulate the flow both on feed and discharge. Flow micro-regulators are divided into 4 series:
- MRF Compact 'O': Can be adjusted using a screwdriver; the regulation pin is lubricated with a particular anti-vibration grease; it has reduced dimensions and fine adjustment in the first turns; adjustment can b prevented by assembling a disposable cap (supplied separately) that can be removed using a tool.
- MRF Compact 'N': Can be adjusted using the knob and/or screwdriver; adjustment can be prevented by tightening the ring nut; it has the same regulation curve as those in series 'O'.

Main Features

- Reduced dimensions
- Excellent regulation
- Regulation with a screwdriver and disposable anti-tampering cap (Compact 'O')
- Regulation with either a screwdriver and/or a knob, can be fixed with a ring nut (Compact 'N')
- Available in all sizes (from M5 to 1/2") with a brass or a technopolymer ring
- Can be mounted with an automatic screwdriver
- Comes with a ring that can rotate even with the MRF mounted in position

Working Temperature Range:
-10°C to +70°C (Brass Ring)
-10°C to +50°C (Technopolymer Ring)

Maximum Working Pressure:
10 bar



Type C to Suit Cylinder

9148	Thread BSPT	Tube OD mm
9001001C	M5	4
9001002C	M5	5
9001007C	M5	6
9001011C	R1/8"	4
9001012C	R1/8"	5

Type V to Suit Values

9148	Thread BSPT	Tube OD mm
9001101V	R1/8"	6
9001103V	R1/8"	8
9001102V	R1/4"	6
9001104V	R1/4"	8
9001115V	R3/8"	8

Type B Bidirectional to Suit Cylinder & Valves

9148	Thread BSPT	Tube OD mm
9001609B	R1/4"	10
9001623B	R1/4"	12
9001610B	R3/8"	10
9001624B	R3/8"	12
9001625B	R1/2"	12

MRF Compact 'O' Threaded Brass Ring, Imperial



Type C to suit Cylinder

9148	Thread BSPT	Tube OD
9001020C	R1/8"	1/8"
9001021C	R1/4"	1/4"
9001022C	R3/8"	3/8"

Type B Bidirectional to suit Cylinders & Valves

9148	Thread BSPT	Tube OD
9001620B	R1/8"	1/8"
9001621B	R1/4"	1/4"
9001622B	R3/8"	3/8"

Type V to suit Valves

9148	Thread BSPT	Tube OD
9001120V	R1/8"	1/8"
9001121V	R1/4"	1/4"
9001122V	R3/8"	3/8"

Accessories for MRF Compact 'O'



Anti-tampering Cap

9148	To Fit Thread BSPT
9090001	M5
9090002	R1/8" - R1/4"
9090003	R3/8" - R1/2"

MRF Compact 'O' Technopolymer Ring



Type C to suit Cylinder

9148	Thread BSPT	Tube OD mm
9011001C	M5	4
9011007C	M5	6
9011011C	R1/8"	4
9011003C	R1/8"	6
9011005C	R1/8"	8
9011004C	R1/4"	6
9011006C	R1/4"	8
9011008C	R1/4"	10
9011014C	R1/4"	12
9011009C	R3/8"	10
9011015C	R3/8"	12
9011016C	R1/2"	12

Type V to suit Valves

9148	Thread BSPT	Tube OD mm
9011110V	M5	4
9011105V	M5	6
9011111V	R1/8"	4
9011101V	R1/8"	6
9011103V	R1/8"	8
9011102V	R1/4"	6
9011104V	R1/4"	8
9011106V	R1/4"	10
9011123V	R1/4"	12
9011114V	R3/8"	10
9011124V	R3/8"	12
9011125V	R1/2"	12

Type B Bidirectional to suit Cylinders & Valves

9148	Thread BSPT	Tube OD mm
9011601B	M5	4
9011612B	M5	6
9011602B	R1/8"	4
9011605B	R1/8"	6
9011607B	R1/8"	8
9011606B	R1/4"	6
9011608B	R1/4"	8
9011609B	R1/4"	10
9011623B	R1/4"	12
9011610B	R3/8"	10
9011624B	R3/8"	12
9011625B	R1/2"	12

Fluid-Air Components Ltd

FLOW MICRO-REGULATORS

MRF Compact 'N' Brass Ring



Type C to suit Cylinder

9148	Thread BSPT	Tube OD mm
9031001C	M5	4
9031003C	M5	5
9031005C	M5	6
9031002C	R1/8"	4
9031004C	R1/8"	5
9031006C	R1/8"	6
9031008C	R1/8"	8
9031007C	R1/4"	6
9031009C	R1/4"	8
9031010C	R3/8"	8
9031011C	R1/4"	10
9031014C	R1/4"	12
9031012C	R3/8"	10
9031015C	R3/8"	12
9031016C	1/2"	12

Type V to suit Valves

9148	Thread BSPT	Tube OD mm
9031101V	M5	4
9031103V	M5	5
9031105V	M5	6
9031102V	R1/8"	4
9031104V	R1/8"	5
9031106V	R1/8"	6
9031108V	R1/8"	8
9031107V	R1/4"	6
9031109V	R1/4"	8
9031110V	R3/8"	8
9031111V	R1/4"	10
9031114V	R1/4"	12
9031112V	R3/8"	10
9031115V	R3/8"	12
9031116V	1/2"	12

Type B Bidirectional to suit Cylinders & Valves

9148	Thread BSPT	Tube OD mm
9031201B	M5	4
9031203B	M5	5
9031205B	M5	6
9031202B	R1/8"	4
9031204B	R1/8"	5
9031206B	R1/8"	6
9031208B	R1/8"	8
9031207B	R1/4"	6
9031209B	R1/4"	8
9031210B	R3/8"	8
9031211B	R1/4"	10
9031214B	R1/4"	12
9031212B	R3/8"	10
9031215B	R3/8"	12
9031216B	1/2"	12

MRF Compact 'N' Technopolymer Ring



Type C to suit Cylinder

9148	Thread BSPT	Tube OD mm
9021001C	M5	4
9021005C	M5	6
9021002C	R1/8"	4
9021006C	R1/8"	6
9021008C	R1/8"	8
9021007C	R1/4"	6
9021009C	R1/4"	8
9021011C	R1/4"	10
9021014C	R1/4"	12
9021012C	R3/8"	10
9021212C	R3/8"	10
9021015C	R3/8"	12
9021016C	R1/2"	12

Type V to suit Valves

9148	Thread BSPT	Tube OD mm
9021101V	M5	4
9021105V	M5	6
9021102V	R1/8"	4
9021106V	R1/8"	6
9021108V	R1/8"	8
9011107V	R1/4"	6
9021109V	R1/4"	8
9021111V	R1/4"	10
9021114V	R1/4"	12
9021112V	R3/8"	10
9021115V	R3/8"	12
9021116V	R1/2"	12

Type B Bidirectional to suit Cylinders & Valves

9148	Thread BSPT	Tube OD mm
9021201B	M5	4
9021205B	M5	6
9021202B	R1/8"	4
9021206B	R1/8"	6
9021208B	R1/8"	8
9021207B	R1/4"	6
9021209B	R1/4"	8
9021211B	R1/4"	10
9021214B	R1/4"	12
9021215B	R3/8"	12
9021216B	R1/2"	12

MRF Compact 'N' Threaded Brass Ring



Type C to suit Cylinder

9148	Thread BSPT	Tube OD
9031301C	R1/8"	1/8"
9031302C	R1/4"	1/4"
9031303C	R3/8"	3/8"

Type V to suit Valves

9148	Thread BSPT	Tube OD
9031401V	R1/8"	1/8"
9031402V	R1/4"	1/4"
9031403V	R3/8"	3/8"

Type B Bidirectional to suit Cylinders & Valves

9148	Thread BSPT	Tube OD
9031501B	R1/8"	1/8"
9031502B	R1/4"	1/4"
9031503B	R3/8"	3/8"

BLOCK FITTINGS

Blocking Fitting


Stop valves mounted on the cylinder inlets allow a flow of air only in the presence of a pneumatic pilot. This item is mainly used as a safety valve. When pressure drops in the pneumatic pilot, all cylinder movement is halted.




Technical Data

	Bidirectional			
	1/8"	1/4"	3/8"	1/2"
Operating Pressure bar	0.5-10			
Operating temperature °C	-10° to +60°			
Flow rate (6 bar)	320	700	1060	1700









Fully Threaded

9148	F	F1	F2
W6001101001	G1/8"	G1/8"	G1/8"
W6001111011	G1/4"	G1/4"	G1/8"
W6001121021	G3/8"	G3/8"	G1/8"

Tube Fittings

9148	F	Ø1 mm	Ø2 mm
W6001101106	G1/8"	6	4
W6001111106	G1/4"	6	4
W6001111108	G1/4"	8	4
W6001121108	G3/8"	8	4
W6001121110	G3/8"	10	4
W6001131112	G1/2"	12	4

For **FRL's, 'SKILLAIR'**
see pages **678-681**



Fluid-Air Components Ltd

FLOW CONTROL VALVES

Unidirectional In-line Flow Control



To suit Cylinders

9148	Thread BSP	Mounting Thread
9041001	M5	M10 x 0.75
9041002	G1/8"	M12 x 1
9041003	G1/4"	M12 x 1
9041004	G3/8"	M15 x 1
9041005	G1/2"	M15 x 1

Bidirectional In-line Flow Control



To suit Cylinders

9148	Thread BSP	Mounting Thread
9041201	M5	M10 x 0.75
9041202	G1/8"	M12 x 1
9041203	G1/4"	M12 x 1
9041204	G3/8"	M15 x 1
9041205	G1/2"	M15 x 1

Unidirectional Flow Control



With Push-in Fittings

9148	Tube Ø mm	Mounting Thread
9041301	4	M9 x 0.75
9041316	6	M12 x 0.7
9041324	8	M15 x 1

Unidirectional Flow Control Fittings

➤ Flow Direction



Flow Direction Thread to Tube

9148	Thread BSP	Tube Ø mm
9041401	M5	4
9041402	G1/8"	4
9041408	G1/8"	6
9041409	G1/4"	6
9041410	G1/8"	8
9041411	G1/4"	8
9041412	G3/8"	8

Unidirectional Flow Control Fittings

➤ Flow Direction



Flow Direction Tube to Thread

9148	Thread BSP	Tube Ø mm
9041501	M5	4
9041502	G1/8"	4
9041508	G1/8"	6
9041509	G1/4"	6
9041510	G1/8"	8
9041511	G1/4"	8
9041512	G3/8"	8

Quick Exhaust Valves



BSP

9149	Thread BSP
9101201	1/8"
9201201	1/4"
9401201	1/2"

For **Standard Series FRL's, 'NEW DEAL'**
see page **673**



Fluid-Air Components Ltd

FUNCTIONAL FITTINGS

METAL WORK PNEUMATIC

lineonline


LINE OF PRODUCTS ON LINE

Line on Line is an exclusive range of products for mounting on pneumatic circuits. With these small, highly efficient components it is possible to perform all pneumatic functions at any point of the circuit.


Line on Line is ultra-modular; the components can be connected in parallel, in series or combined parallel/series.

All Line on Line products are available for pipe-pipe connection with integral push-in fittings, or for thread-pipe connection with a brass nickel-plated male thread and an integral push-in fitting.


The body is made of technopolymer, giving a product that is extremely lightweight and compact. One side of the body is marked with an indelible pneumatic symbol to facilitate identification and indicate the direction of flow.




Parallel Lines



Serial Line Parallel Fittings



Serial Line In-line Fittings



Wall Fixing






Plate Fixing




Panel Fixing



Under Wall Fixing

Technical Specifications

- Maximum operating pressure: 10 bar
- Temperature range: -20°C to +60°C
- Maximum flow rate on regulation at 6.3 bar: 155 Nl/min (4mm), 450 Nl/min (6mm), 850 Nl/min (8mm)
- Adjustment: manual or using a screwdriver
- Internal system: tapered needle
- Recommended pipe: Rilson PA 11, nylon 6, polyamide 12, polypropylene
- Fluid: lubricated or non-lubricated filtered air




FAC Fluid-Air Components Ltd

FUNCTIONAL FITTINGS

Line Mounted Pressure Regulator





lineonline

Tube to Tube

9148	Ø	A	B	C	D	E
9061316	6	47	46-52	14.7	6.4	11.4
9061324	8	55.5	52-58	18.7	9.1	13.8

In-line Quick Exhaust Valve

Fig. A.





Fig. B.






lineonline

Tube to Tube

9148	Ø	Figure	A	B	C	D	E	E1	I	I1
9063016	6	A	47	29	14.7	6.4	11.4	13	14.6	20
9063024	8	A	55.5	35	18.7	9.1	13.8	15	18.7	24
9063116	6	B	47	25.5	14.7	6.4	11.4	14	14.6	20
9063124	8	B	55.5	31.5	18.7	9.1	13.8	18	18.7	24

In-line Quick Exhaust Valve






lineonline

Tube to Thread

9148	Ø	Figure	P	A	A1	B	C	D	E	E1	E2	I	I1	I2
9063308	6	1/8	6	57.3	27.8	25.5	14.7	6.4	14	11.4	14	14.6	20	12
9063309	6	1/4	8	60.3	28.8	25.5	14.7	6.4	18	11.4	14	14.6	20	14
9063310	8	1/8	6	65.5	31.8	31.5	18.7	9.1	15	13.8	18	18.7	24	13
9063311	8	1/4	8	69.7	34.2	31.5	18.7	9.1	18	13.8	18	18.7	24	14

In-line Check Valve





Tube to Tube

9148	Ø	A	B	C	D	E	I	I1
9064016	6	47	20	14.7	6.4	11.4	14.6	20
9064024	8	55.5	25.5	18.7	9.1	13.8	18.7	24


Fluid-Air Components Ltd

FUNCTIONAL FITTINGS

In-line Shut-off Valve

Technical Data
- Inlet Flow rate at 6.3 bar ΔP 1 bar: 280 Nl/min (6mm), 470 Nl/min (8mm)
- V2V L: on/off function
- V3V L: on/off function with vent







Tube to Tube

9148	Function	Ø	A	B	C	D	E	G	H	I	I1	Ch	Nmax
9065016	V2V L	6	47	41	14.7	6.4	11.4	21	M15 x 1	14.6	20	17	5.5
9066016	V3V L	6	47	41	14.7	6.4	11.4	21	M15 x 1	14.6	20	17	5.5
9065024	V2V L	8	55.5	46	18.7	9.1	13.8	26	M15 x 1	18.7	24	17	5.5
9066024	V3V L	8	55.5	46	18.7	9.1	13.8	26	M15 x 1	18.7	24	17	5.5

In-line Shut-off Valve, Lockable

Technical Data
- V2V L: on/off function
- V3V L: on/off function with vent






Tube to Tube

9148	Function	Ø	A	B	C	D	E	G	H	I	I1	Ch	Nmax
9065116	V2V L	6	47	41	14.7	6.4	11.4	21	M15 x 1	14.6	20	17	5.5
9066116	V3V L	6	47	41	14.7	6.4	11.4	21	M15 x 1	14.6	20	17	5.5
9065124	V2V L	8	55.5	46	18.7	9.1	13.8	26	M15 x 1	18.7	24	17	5.5
9066124	V3V L	8	55.5	46	18.7	9.1	13.8	26	M15 x 1	18.7	24	17	5.5

In-line Pressure Gauge

Technical Data
- Operating pressure: 12 bar
- Precision: +4% full scale






Tube to Tube

9148	Ø	A	B	C	D	E	E1	I	I1
9067016	6	47	35	14.7	6.4	11.4	23	14.6	20
9067024	8	55.5	41	18.7	9.1	13.8	23	18.7	24

Technical Data
- Operating pressure: 12 bar
- Precision: +4% full scale






Thread to Tube

9148	Function	Ø	P	A	A1	B	C	D	E	E1	E2	I	I1	Ch
9067108	1/8	6	6	57.3	27.5	35	14.7	6.4	14	11.4	23	14.6	20	12
9067109	1/4	6	8	60.3	28.8	35	14.7	6.4	18	11.4	23	14.6	20	14
9067110	1/8	8	6	65.3	31.8	41	18.7	9.1	15	13.8	23	18.7	24	14
9067111	1/4	8	8	69.7	34.2	41	18.7	9.1	18	13.8	23	18.7	24	14

In-line Pressure Indicator

Technical Data
- Operating pressure: 2-12 bar
- A = Orange, V = Green





Tube to Tube

9148	Type	Ø	A	B	C	D	E	E1	G	H	I	I1	Ch	NmAX
9068016	A	6	47	37	14.7	6.4	11.4	10.6	21	M15 x 1	14.6	20	17	4.5
9068216	V	6	47	37	14.7	6.4	11.4	10.6	21	M15 x 1	14.6	20	17	4.5
9068024	A	8	55.5	41	18.7	9.1	13.8	10.6	26	M15 x 1	18.7	24	17	4.5
9068224	V	8	55.5	41	18.7	9.1	13.8	10.6	26	M15 x 1	18.7	24	17	4.5


Fluid-Air Components Ltd

FUNCTIONAL FITTINGS

In-line 3 Port Solenoid Valve, Silenced Exhaust

Technical Data
- Operating pressure: 2.5-7 bar
- Flow rate at 6.3 bar ΔP 0.5 bar: 270 Nl/min (6mm), 500 Nl/min (8mm)
- Voltage: 24V DC
- Power: 1.2W







Tube to Tube

9148	Ø	A	B	C	D	E	I	I1
9069016	6	47	55.5	14.7	6.4	11.4	14.6	20
9069024	8	55.5	63.5	18.7	9.1	13.8	18.7	24

Technical Data
- Operating pressure: 2.5-7 bar
- Flow rate at 6.3 bar ΔP 0.5 bar: 270 Nl/min, 500 Nl/min
- Voltage: 24V DC
- Power: 1.2W






Thread to Tube

9148	Ø	F	P	A	A1	B	C	I	I1	Ch1
9069408	6	1/8	6	57.3	27.8	55.5	14.7	14.6	20	12
9069409	6	1/4	8	60.3	28.8	55.5	14.7	14.6	20	14
9069410	8	1/8	6	65.3	31.3	63.5	18.7	18.7	24	14
9069411	8	1/4	8	69.7	34.2	63.5	18.7	18.7	24	14

In-line 3 Port Solenoid Valve, Threaded Exhaust

Technical Data
- Operating pressure: 2.5 to 7 bar
- Flow rate at 6.3 bar ΔP 0.5 bar: 500 Nl/min
- Voltage: 24V DC
- Power: 1.2W







Tube to Tube

9148	Ø	A	B	C	D	E	E1	I	I1	L
9069224	8	55.5	63.5	18.7	9.1	13.8	1/8	18.7	24	21.5

In-line 3 Port Solenoid Valve, Silenced Exhaust

Technical Data
- Operating pressure: 2.5 to 7 bar
- Flow rate at 6.3 bar ΔP 0.5 bar: 270 Nl/min, 500 Nl/min
- Voltage: 24V DC
- Power: 1.2W





Tube to Thread

9148	Ø	F	P	A	A1	B	C	D	E	E1	F1	I	I1	L	Ch1
9069610	8	1/8	6	65.3	31.8	63.5	18.7	9.1	15	13.8	1/8	18.7	24	25.1	1
9069611	8	1/4	8	69.7	34.2	63.5	18.7	9.1	18	13.8	1/8	18.7	24	21.5	1

Electrical Connector




Plug-in

9148	Description
W0970512000	Plug-in Connector, 300mm Leads

Fixing Bracket





To suit All Line on Line Products

9148	A	B	C	F	I	I1	I2	I3	I4	I5	S
9062110	30	22	14.5	4.2	6.8	4.8	5.9	9.1	2	6.5	1.2

U Tube



Tube

9148	OD mm
9062216	6
9062224	8

Fluid-Air Components Ltd

SERIES 7000 SUPER-RAPID COMPACT FITTINGS

CAMOZZI Automation

Material: Technopolymer

Working Pressure: -0.9 to 16 bar

Swivel Male Stud Elbows



Metric & BSPP

0158	OD mm	Thread
7522 4-M5	4	M5
7522 4-M7	4	M7
7522 4-1/8	4	1/8"
7522 4-1/4	4	1/4"
7522 6-M5	6	M5
7522 6-M7	6	M7
7522 6-1/8	6	1/8"
7522 6-1/4	6	1/4"
7522 8-1/8	8	1/8"
7522 8-1/4	8	1/4"
7522 8-3/8	8	3/8"
7522 10-1/4	10	1/4"
7522 10-3/8	10	3/8"
7522 10-1/2	10	1/2"
7522 12-1/4	12	1/4"
7522 12-3/8	12	3/8"
7522 12-1/2	12	1/2"
7522 16-1/2	16	1/2"
7522 16-3/4	16	3/4"
Tech Sheet 68274		

Swivel Male Stud Extended Elbows



BSPP, Extended

0158	OD mm	Thread
7526 4-1/8	4	1/8"
7526 6-1/8	6	1/8"
7526 6-1/4	6	1/4"
7526 8-1/8	8	1/8"
7526 8-1/4	8	1/4"
Tech Sheet 68274		

Swivel Male Stud Branch Tees



Metric & BSPP

0158	OD mm	Thread
7432 4-M5	4	M5
7432 4-1/8	4	1/8"
7432 6-M5	6	M5
7432 6-1/8	6	1/8"
7432 6-1/4	6	1/4"
7432 8-1/8	8	1/8"
7432 8-1/4	8	1/4"
7432 8-3/8	8	3/8"
7432 10-1/4	10	1/4"
7432 10-3/8	10	3/8"
7432 10-1/2	10	1/2"
7432 12-1/4	12	1/4"
7432 12-3/8	12	3/8"
7432 12-1/2	12	1/2"
7432 16-1/2	16	1/2"
7432 16-3/4	16	3/4"
Tech Sheet 68274		

Swivel Male Stud Run Tees



BSPP

0158	OD mm	Thread
7442 4-1/8	4	1/8"
7442 6-1/8	6	1/8"
7442 6-1/4	6	1/4"
7442 8-1/8	8	1/8"
7442 8-1/4	8	1/4"
7442 8-3/8	8	3/8"
7442 10-1/4	10	1/4"
7442 10-3/8	10	3/8"
7442 12-3/8	12	3/8"
7442 12-1/2	12	1/2"
7442 16-1/2	16	1/2"
7442 16-3/4	16	3/4"
Tech Sheet 68274		

Swivel Male Stud Ys



BSPP

0158	OD mm	Thread
7562 4-1/8	4	1/8"
7562 6-1/8	6	1/8"
7562 6-1/4	6	1/4"
7562 8-1/8	8	1/8"
7562 8-1/4	8	1/4"
7562 10-1/4	10	1/4"
7562 10-3/8	10	3/8"
Tech Sheet 68274		

Swivel Male Stud Double Ys



BSPP

0158	OD mm	Thread
7572 4-1/8	4	1/8"
7572 4-1/4	4	1/4"
7572 6-1/8	6	1/8"
7572 6-1/4	6	1/4"
Tech Sheet 68274		

Fluid-Air Components Ltd

SERIES 7000 SUPER-RAPID COMPACT FITTINGS

CAMOZZI Automation

Material: Technopolymer

Working Pressure: -0.9 to 16 bar

Tube x Tube Connectors



Equal Straights

0158	OD mm
7580 4	4
7580 6	6
7580 8	8
7580 10	10
7580 12	12
Tech Sheet 68274	



Equal Elbows

0158	OD mm
7550 4	4
7550 6	6
7550 8	8
7550 10	10
7550 12	12
7550 16	16
Tech Sheet 68274	



Equal Tees

0158	OD mm
7540 4	4
7540 6	6
7540 8	8
7540 10	10
7540 12	12
7540 16	16
Tech Sheet 68274	



Equal Ys

0158	OD mm
7560 4	4
7560 6	6
7560 8	8
7560 10	10
Tech Sheet 68274	



Unequal Ys

0158	OD mm	OD mm
7560 6-4	6	4
7560 8-6	8	6
7560 10-8	10	8
Tech Sheet 68274		



Unequal Double Ys

0158	OD mm	OD mm
7575 6-4	6	4
7575 8-6	8	6
Tech Sheet 68274		

Tube x Stem Connectors



Unequal Straights

0158	OD mm	Stem OD mm
7800 4-6	4	6
7800 4-8	4	8
7800 6-8	6	8
7800 6-10	6	10
7800 6-12	6	12
7800 8-10	8	10
7800 8-12	8	12
7800 10-12	10	12
Tech Sheet 68274		



Elbows

0158	OD mm	Stem OD mm
7555 4-4	4	4
7555 6-6	6	6
7555 8-8	8	8
7555 10-10	10	10
7555 12-12	12	12
Tech Sheet 68274		

Stem Connectors



Stem x Stem

0158	Stem OD mm
7950 4	4
7950 6	6
7950 8	8
7950 10	10
7950 12	12
Tech Sheet 68274	

Reducing Manifolds



Tube x Tube

0158	Inlet OD mm	Outlet OD mm
7545 6-4	6	4
7545 8-6	8	6
7545 10-8	10	10
Tech Sheet 68274		



Swivel Male, BSPP

0158	Inlet OD mm	Outlet OD mm	Thread
7542 6-4-1/8	6	4	1/8"
7542 6-4-1/4	6	4	1/4"
7542 8-6-1/8	8	6	1/8"
7542 8-6-1/4	8	6	1/4"
7542 10-8-1/4	10	8	1/4"
7542 10-8-3/8	10	8	3/8"
Tech Sheet 68274			

FAC Fluid-Air Components Ltd

SERIES 7000 SUPER-RAPID COMPACT FITTINGS

CAMOZZI Automation

Material: Technopolymer

Working Pressure: -0.9 to 16 bar

Single Banjo Bodies



BSPP

0158	OD mm	Thread
7610 4-1/8	4	1/8"
7610 6-1/8	6	1/8"
7610 6-1/4	6	1/4"
7610 8-1/8	8	1/8"
7610 8-1/4	8	1/4"
7610 10-1/4	10	1/4"
7610 10-3/8	10	3/8"
7610 12-3/8	12	3/8"
Tech Sheet 68274		

Twin Banjo Bodies



BSPP

0158	OD mm	Thread
7640 4-1/8	4	1/8"
7640 6-1/8	6	1/8"
7640 6-1/4	6	1/4"
7640 8-1/8	8	1/8"
7640 8-1/4	8	1/4"
7640 10-1/4	10	1/4"
Tech Sheet 68274		

Swivel Banjos, 1 Outlet



BSPP

0158	OD mm	Thread
7622 4-1/8	4	1/8"
7622 6-1/8	6	1/8"
7622 6-1/4	6	1/4"
7622 8-1/8	8	1/8"
7622 8-1/4	8	1/4"
7622 10-1/4	10	1/4"
7622 10-3/8	10	3/8"
7622 12-3/8	12	3/8"
Tech Sheet 68274		

Swivel Twin Banjos, 2 Outlets



BSPP

0158	OD mm	Thread
7652 4-1/8	4	1/8"
7652 6-1/8	6	1/8"
7652 6-1/4	6	1/4"
7652 8-1/8	8	1/8"
7652 8-1/4	8	1/4"
7652 10-1/4	10	1/4"
7652 10-3/8	10	3/8"
Tech Sheet 68274		

Double Adjustable Banjos, 2 Outlets



BSPP

0158	OD mm	Thread
7612 02-4-1/8	4	1/8"
7612 02-6-1/8	6	1/8"
7612 02-6-1/4	6	1/4"
7612 02-8-1/8	8	1/8"
7612 02-8-1/4	8	1/4"
7612 02-10-1/4	10	1/4"
7612 02-10-3/8	10	3/8"
7612 02-12-3/8	12	3/8"
Tech Sheet 68274		

Double Adjustable Twin Banjos, 4 Outlets



BSPP

0158	OD mm	Thread
7642 02-4-1/8	4	1/8"
7642 02-6-1/8	6	1/8"
7642 02-6-1/4	6	1/4"
7642 02-8-1/8	8	1/8"
7642 02-8-1/4	8	1/4"
7642 02-10-1/4	10	1/4"
Tech Sheet 68274		

Triple Adjustable Banjos, 3 Outlets



BSPP

0158	OD mm	Thread
7612 03-4-1/8	4	1/8"
7612 03-6-1/8	6	1/8"
7612 03-6-1/4	6	1/4"
7612 03-8-1/8	8	1/8"
7612 03-8-1/4	8	1/4"
7612 03-10-1/4	10	1/4"
Tech Sheet 68274		

Triple Adjustable Twin Banjos, 6 Outlets



BSPP

0158	OD mm	Thread
7642 03-4-1/8	4	1/8"
7642 03-6-1/8	6	1/8"
7642 03-6-1/4	6	1/4"
7642 03-8-1/8	8	1/8"
7642 03-8-1/4	8	1/4"
7642 03-10-1/4	10	1/4"
Tech Sheet 68274		

Banjo Bolts



Double Stem, BSPP

0158	Thread
7632 02-1/8	1/8"
7632 02-1/4	1/4"
7632 02-3/8	3/8"
Tech Sheet 68274	



Triple Stem, BSPP

0158	Thread
7632 03-1/8	1/8"
7632 03-1/4	1/4"
Tech Sheet 68274	

Fluid-Air Components Ltd



Push-in Fittings & Ring Main Systems

For Ring Main Systems see section 8 page 1061





For Push-in Fittings see section 6 page 763

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PUSH-IN FITTINGS, METRIC

Media: Compressed air. Suitable for vacuum.

Temperature at:	Pressure 5/32" – 5/16" 4mm – 8mm	Pressure 3/8" - 1/2": 10mm – 22mm
Air		
-20°C	16 bar	10 bar

Potable Liquids and Air		
+1°C	16 bar	10 bar
+20°C	16 bar	10 bar
+65°C	10 bar	7 bar

Straight Adaptors



Male Thread, Super Thread

1400	OD mm	Thread
LM0104M5	4	M5
RM010411	4	1/8"
RM010511	5	1/8"
RM010512	5	1/4"
RM010611	6	1/8"
RM010612	6	1/4"
RM010811	8	1/8"
RM010812	8	1/4"
RM010813	8	3/8"
RM011012	10	1/4"
RM011013	10	3/8"
RM011014	10	1/2"
RM011213	12	3/8"
RM011214	12	1/2"



Male Thread, Metric

1400	OD mm	Thread
RM0104M5	4	M5
RM0106M5	6	M5



Male Thread, BSPP

1400	OD mm	Thread
PM010411E	4	1/8"
PM010412E	4	1/4"
PM010511E	5	1/8"
PM010512E	5	1/4"
PM010611E	6	1/8"
PM010612E	6	1/4"
PM010811E	8	1/8"
PM010812E	8	1/4"
PM010813E	8	3/8"
PM011012E	10	1/4"
PM011013E	10	3/8"
PM011014E	10	1/2"
PM011213E	12	3/8"
PM011514E	15	1/2"



Male Thread, BSPT

1400	OD mm	Thread
PM010401E	4	1/8"
PM010402E	4	1/4"
PM010501E	5	1/8"
PM010502E	5	1/4"
PM010601E	6	1/8"
PM010602E	6	1/4"
PM010801E	8	1/8"
PM010802E	8	1/4"
PM010803E	8	3/8"
PM011002E	10	1/4"
PM011003E	10	3/8"
PM011004E	10	1/2"
PM011203E	12	3/8"
PM011204E	12	1/2"

Brass Straight Adaptors



Male Thread, BSPP

1400	OD mm	Thread
MM010411	4	1/8"
MM010611	6	1/8"



Male Super Thread

1400	OD mm	Thread
LM010411	4	1/8"

Equal Tees



Tube x Tube

1400	OD mm
LM0203E	3
PM0204E	4
PM0205E	5
PM0206E	6
PM0208E	8
PM0210E	10
PM0212E	12
PM0215E	15

Equal Elbows



Tube x Tube

1400	OD mm
LM0303E	3
PM0304E	4
PM0305E	5
PM0306E	6
PM0308E	8
PM0310E	10
PM0312E	12
PM0315E	15

Reducing Elbow Connectors



Tube x Tube

1400	OD mm	OD mm
PM210604E	6	4
PM210804E	8	4
PM210806E	8	6
PM211004E	10	4
PM211006E	10	6
PM211008E	10	8
PM211208E	12	8
PM211210E	12	10

Fluid-Air Components Ltd

PUSH-IN FITTINGS, METRIC

John Guest

Female Adaptors



BSPP

1400	OD mm	Thread
PM450411E	4	1/8"
PM450611E	6	1/8"
PM450612E	6	1/4"
PM450812E	8	1/4"
PM451015FE	10	5/8"

Stem Elbows



Tube x Stem

1400	OD mm	Stem OD mm
PM220404E	4	4
PM220505E	5	5
PM220606E	6	6
PM220808E	8	8
PM221010E	10	10
PM221212E	12	12
PM221515E	15	15

Equal Straight Connectors



Tube x Tube

1400	OD mm
PM0404E	4
PM0405E	5
PM0406E	6
PM0408E	8
PM0410E	10

Reducing Straight Connectors



Tube x Tube

1400	OD mm	OD mm
PM200604E	6	4
PM200804E	8	4
PM200806E	8	6
PM201004E	10	4
PM201006E	10	6
PM201008E	10	8
PM201208E	12	8
PM201210E	12	10

Stem Adaptors



Super Thread, BSPP

1400	Stem OD mm	Thread
RM050411	4	1/8"
RM050412	4	1/4"
RM050512	5	1/4"
RM050611	6	1/8"
RM050612	6	1/4"
RM051013	10	3/8"
RM051014	10	1/2"
RM051213	12	3/8"



Metric

1400	Stem OD mm	Thread
RM0504M5	4	M5
RM0506M5	6	M5



BSPT

1400	Stem OD mm	Thread
PM050401E	4	1/8"
PM050402E	4	1/4"
PM050501E	5	1/8"
PM050502E	5	1/4"
PM050601E	6	1/8"
PM050602E	6	1/4"
PM050801E	8	1/8"
PM050802E	8	1/4"
PM050803E	8	3/8"
PM051002E	10	1/4"
PM051003E	10	3/8"
PM051004E	10	1/2"
PM051203E	12	3/8"
PM051204E	12	1/2"



BSPP

1400	Stem OD mm	Thread
PM050411E	4	1/8"
PM050412E	4	1/4"
PM050511E	5	1/8"
PM050512E	5	1/4"
PM050611E	6	1/8"
PM050612E	6	1/4"
PM050811E	8	1/8"
PM050812E	8	1/4"
PM050813E	8	3/8"
PM051012E	10	1/4"
PM051013E	10	3/8"
PM051014E	10	1/2"
PM051213E	12	3/8"
PM051214E	12	1/2"

Dividers



Tube x Tube

1400	OD mm
PM2304E	4
PM2306E	6
RM2308E	8
PM2310E	10

Bulkhead Adaptors

Media:
Compressed air. Suitable for vacuum.
Maximum bulkhead mounting torque 27Nm.



BSPP

1400	OD mm	Thread	Bulkhead
RM070612	6	1/4"	3/8"

Swivel Tees Offset Leg

Media:
Compressed Air. Suitable for vacuum.



BSPT

1400	OD mm	Thread
PM110601E	6	1/8"
PM110802E	8	1/4"
PM111003E	10	3/8"
PM111203E	12	3/8"
PM111204E	12	1/2"



BSPP Thread

1400	OD mm	Thread
PM110411E	4	1/8"
PM110511E	5	1/8"
PM110512E	5	1/4"
PM110611E	6	1/8"
PM110612E	6	1/4"
PM110811E	8	1/8"
PM110812E	8	1/4"
PM110813E	8	3/8"
PM111012E	10	1/4"
PM111013E	10	3/8"
PM111014E	10	1/2"
PM111213E	12	3/8"
PM111214E	12	1/2"

PUSH-IN FITTINGS, METRIC

Bulkhead Connectors



BSPP Thread

1400	OD mm	Thread
PM1204E	4	3/8"
PM1206E	6	3/8"
PM1208E	8	1/2"
PM1210E	10	1/2"
PM1212E	12	3/4"

Reducers



Tube x Stem

1400	Stem OD mm	Thread
PM060504E	5	4
PM060604E	6	4
PM060605E	6	5
PM060804E	8	4
PM060805E	8	5
PM060806E	8	6
PM061006E	10	6
PM061008E	10	8
PM061208E	12	8
PM061210E	12	10
PM061510E	15	10

Single Banjo Body



BSPP Thread

1400	OD mm	Thread
RM150411E	4	1/8"
RM150511E	5	1/8"
RM150811E	8	1/4"
RM151013E	10	3/8"
RM151214E	12	1/2"

Banjo Bolts



Single, BSPP Thread

1400	Thread
RM1611	1/8"
RM1614	1/2"

Media:
Compressed air. Suitable for vacuum.



Double, BSPP Thread

1400	Thread
RM1711	1/8"
RM1712	1/4"
RM1713	3/8"
RM1714	1/2"

Swivel Elbows



Super Thread, BSPP

1400	OD mm	Thread
RM090412	4	1/4"
RM090611	6	1/8"
RM090612	6	1/4"
RM090811	8	1/8"
RM090812	8	1/4"
RM091013	10	3/8"
RM091213	12	3/8"
RM091214	12	1/2"



Metric Thread

1400	OD mm	Thread
LM0904M5	4	M5
RM0904M5	4	M5
RM0905M5	5	M5
RM0906M5	6	M5

Plugs

Media:
Compressed Air. Suitable for vacuum.



Tube

1400	Stem OD mm	Colour
PM0804R	4	Red
PM0805R	5	Red
PM0806R	6	Red
PM0808R	8	Red
PM0810R	10	Red
PM0812R	12	Red
PM0815R	15	Black



BSPP Thread

1400	OD mm	Thread
PM090411E	4	1/8"
PM090412E	4	1/4"
PM090511E	5	1/8"
PM090512E	5	1/4"
PM090611E	6	1/8"
PM090612E	6	1/4"
PM090811E	8	1/8"
PM090812E	8	1/4"
PM090813E	8	3/8"
PM091012E	10	1/4"
PM091013E	10	3/8"
PM091014E	10	1/2"
PM091213E	12	3/8"
PM091214E	12	1/2"



BSPT Thread

1400	OD mm	Thread
PM090401E	4	1/8"
PM090402E	4	1/4"
PM090501E	5	1/8"
PM090502E	5	1/4"
PM090601E	6	1/8"
PM090602E	6	1/4"
PM090801E	8	1/8"
PM090802E	8	1/4"
PM090803E	8	3/8"
PM091002E	10	1/4"
PM091003E	10	3/8"
PM091004E	10	1/2"
PM091203E	12	3/8"
PM091204E	12	1/2"

Fluid-Air Components Ltd

PUSH-IN FITTINGS, METRIC

Swivel Tees Centre Leg



Super Thread, BSPP

1400	OD mm	Thread
RM100611	6	1/8"
RM100612	6	1/4"



BSPT Thread

1400	OD mm	Thread
PM100401E	4	1/8"
PM100402E	4	1/4"
PM100502E	5	1/4"
PM100601E	6	1/8"
PM100602E	6	1/4"
PM100801E	8	1/8"
PM100802E	8	1/4"
PM100803E	8	3/8"
PM101002E	10	1/4"
PM101003E	10	3/8"
PM101004E	10	1/2"
PM101203E	12	3/8"
PM101204E	12	1/2"



BSPP Thread

1400	OD mm	Thread
PM100411E	4	1/8"
PM100412E	4	1/4"
PM100511E	5	1/8"
PM100512E	5	1/4"
PM100611E	6	1/8"
PM100612E	6	1/4"
PM100811E	8	1/8"
PM100812E	8	1/4"
PM100813E	8	3/8"
PM101012E	10	1/4"
PM101013E	10	3/8"
PM101014E	10	1/2"
PM101213E	12	3/8"
PM101214E	12	1/2"

Tube to Hose Stem



Stem x Hose Tail

1400	Stem OD mm	To Suit Hose ID mm
PM250604E	6	4
PM250806E	8	6
PM251008E	10	8

Collet Covers



Colour Coding and Additional Security

The slip-on collet covers shown in this photograph prevent accidental removal or tampering with tubing. Tubing can be inserted with the collet cover already attached to the fittings or the cover can be slid into position afterwards. The cover is easily removed as and when required and comes in a variety of colours for colour-coding.

Colours available - suffix indicates colour

i.e. E = Black S = Grey
R = Red B = Blue
Y = Yellow G = Green

Please indicate, by suffix the colour required or black will be supplied.

Metric


1400	OD mm
PM1904E	4
PM1905E	5
PM1910E	10
PM1912E	12
PM1915E	15
PM1922E	22


Locking Clip



1400	OD mm
PMC1815R	15

John Guest





For **John Guest Ring Main System** see pages **1088-1092**

FT PRO



You might also need **Nylon Tubing** see pages **913-917**

Fluid-Air Components Ltd

PUSH-IN FITTINGS, IMPERIAL

Media: Compressed air. Suitable for vacuum.
- Drink dispensers and pure water fittings

Temperature at:	Working Pressure 5/32"-5/16"	Working Pressure 3/8"-1/2"
+20°C	16 bar	10 bar
+23°C	16 bar	10 bar
+70°C	10 bar	7 bar

Straight Adaptors



Male Thread, BSPT

1400	OD	Thread
PM010401S	5/32"	1/8"
PM010402S	5/32"	1/4"
PI010601S	3/16"	1/8"
PI010801S	1/4"	1/8"
PI010802S	1/4"	1/4"
PM010801S	5/16"	1/8"
PM010802S	5/16"	1/4"
PM010803S	5/16"	3/8"
PI011202S	3/8"	1/4"
PI011203S	3/8"	3/8"
PI011603S	1/2"	3/8"
PI011604S	1/2"	1/2"

Male Thread, BSPP

1400	OD	Thread
PI010812S	1/4"	1/4"
PI011212S	3/8"	1/4"

Male Thread, NPT

1400	OD	Thread
PM010421S	5/32"	1/8"
PM010422S	5/32"	1/4"
PI010621S	3/16"	1/8"
PI010821S	1/4"	1/8"
PI010822S	1/4"	1/4"
PI010823S	1/4"	3/8"
PM010821S	5/16"	1/8"
PM010822S	5/16"	1/4"
PM010823S	5/16"	3/8"
PI011221S	3/8"	1/8"
PI011222S	3/8"	1/4"
PI011223S	3/8"	3/8"
PI011224S	3/8"	1/2"
PI011623S	1/2"	3/8"
PI011624S	1/2"	1/2"
PI012026S	5/8"	3/4"

Equal Straight Connectors



Tube x Tube

1400	OD
PM0404S	5/32"
PI0406S	3/16"
PI0408S	1/4"
PM0408S	5/16"
PI0412S	3/8"
PI0416S	1/2"

Equal Tees



Tube x Tube

1400	OD
PM0204S	5/32"
PI0206S	3/16"
PI0208S	1/4"
PM0208S	5/16"
PI0212S	3/8"
PI0216S	1/2"

Branch Reducing Tees



Tube x Tube

1400	OD	OD
PI301208S	3/8"	1/4"
PI301612S	1/2"	3/8"

Bulkhead Connectors



Tube x Tube

1400	OD
PI1206S	3/16"
PI1208S	1/4"
PM1208S	5/16"
PI1212S	3/8"
PI1216S	1/2"

Swivel Branch Tee, Leg



BSPT

1400	OD	Thread
PI100802S	1/4"	1/4"

Swivel Branch Tee, Run



BSPT

1400	OD	Thread
PM110801S	5/16"	1/8"

Reducing Bulkhead Connectors



Tube x Tube

1400	OD	OD
PI121208S	3/8"	1/4"

Stem Adaptors



Male Thread, BSPT

1400	Stem OD	Thread
PI050801S	1/4"	1/8"
PI050802S	1/4"	1/4"
PM050801S	5/16"	1/8"
PM050802S	5/16"	1/4"
PI051202S	3/8"	1/4"
PI051203S	3/8"	3/8"
PI051603S	1/2"	3/8"
PI051604S	1/2"	1/2"

Male Thread, BSPP

1400	Stem OD	Thread
PI051212S	3/8"	1/4"
PI051213S	3/8"	3/8"

Male Thread, NPT

1400	Stem OD	Thread
PM050421S	5/32"	1/8"
PM050422S	5/32"	1/4"
PI050621S	3/16"	1/8"
PI050821S	1/4"	1/8"
PI050822S	1/4"	1/4"
PI050823S	1/4"	3/8"
PM050821S	5/16"	1/8"
PM050822S	5/16"	1/4"
PM050823S	5/16"	3/8"
PI051222S	3/8"	1/4"
PI051223S	3/8"	3/8"
PI051623S	1/2"	3/8"
PI051624S	1/2"	1/2"

Fluid-Air Components Ltd

PUSH-IN FITTINGS, IMPERIAL

Equal Elbows



Tube x Tube

1400	OD
PM0304S	5/32"
PI0306S	3/16"
PI0308S	1/4"
PM0308S	5/16"
PI0312S	3/8"
PI0316S	1/2"

Reducing Elbows



Tube x Tube

1400	OD	OD
PM210804S	5/16"	5/32"
PI211006S	5/16"	3/16"
PI211008S	5/16"	1/4"
PI211206S	3/8"	3/16"
PI211208S	3/8"	1/4"
PI211210S	3/8"	5/16"
PI211610S	1/2"	5/16"
PI211612S	1/2"	3/8"

Stem Elbows



Tube x Stem

1400	Stem OD	Thread
PM220404S	5/32"	5/32"
PI220606S	3/16"	3/16"
PI220808S	1/4"	1/4"
PM220808S	5/16"	5/16"
PI221206S	3/8"	3/16"
PI221208S	3/8"	1/4"
PI221210S	3/8"	5/16"
PI221212S	3/8"	3/8"
PI221616S	1/2"	1/2"

Rigid Elbows



Male Thread, NPT

1400	OD	Thread
PI480821S	1/4"	1/8"
PI480822S	1/4"	1/4"
PI480823S	1/4"	3/8"
PI481022S	5/16"	1/4"
PI481023S	5/16"	3/8"
PI481222S	3/8"	1/4"
PI481223S	3/8"	3/8"
PI482024S	5/8"	1/2"

Swivel Elbows



Male Thread, BSPT

1400	OD	Thread
PI090801S	1/4"	1/8"
PI090802S	1/4"	1/4"
PM090801S	5/16"	1/8"
PM090803S	5/16"	3/8"
PI091202S	3/8"	1/4"
PI091203S	3/8"	3/8"
PI091603S	1/2"	3/8"
PI091604S	1/2"	1/2"

Male Thread, NPT

1400	OD	Thread
PM090421S	5/32"	1/8"
PI090621S	3/16"	1/8"
PI090822S	1/4"	1/4"
PI091623S	1/2"	3/8"
PI091624S	1/2"	1/2"

Plugs



Tube

1400	Stem OD
PM0804S	5/32"
PI0806S	3/16"
PI0808S	1/4"
PM0808S	5/16"
PI0812S	3/8"
PI0816S	1/2"

Female Adaptors



BSPP

1400	OD	Thread
PI451014FS	5/16"	1/2"
PI451213S	3/8"	3/8"
PI451214FS	3/8"	1/2"
PI451613S	1/2"	3/8"



NPT

1400	OD	Thread
PI450822S	1/4"	1/4"
PI451222S	3/8"	1/4"

Reducers



Tube x Stem

1400	Stem OD	OD
PI060605S	3/16"	5/32"
PI061006S	5/16"	3/16"
PI061008S	5/16"	1/4"
PI061206S	3/8"	3/16"
PI061208S	3/8"	1/4"
PI061210S	3/8"	5/16"
PI061610S	1/2"	5/16"
PI061612S	1/2"	3/8"

Fluid-Air Components Ltd

PUSH-IN FITTINGS, IMPERIAL

Dividers



2 Way, Tube x Tube

1400	OD
PI2308S	1/4"
PI2312S	3/8"
PI2316S	1/2"



Reducing 2 Way, Tube x Tube

1400	OD A	OD B
PI241210S	3/8"	5/16"



Reducing 3 Way, Tube x Tube

1400	OD A	OD B
PI491612S	1/2"	3/8"

Enlargers



Tube x Stem

1400	OD	Stem OD
PI131012S	3/8"	5/16"
PI131216S	1/2"	3/8"

Cross



Tube x Tube

1400	OD
PI4712S	3/8"

U-Bends



Tube x Tube

1400	OD
PIUB16S	1/2"

End Stops



1400	OD
PI4608S	1/4"
PI4612S	3/8"

Tube to Hose Stems



Stem x Hose Tail

1400	Stem OD	To Suit Hose ID
PI250806S	1/4"	3/16"
PI250808S	1/4"	1/4"
PI250810S	1/4"	5/16"
PI251006S	5/16"	3/16"
PI251008S	5/16"	1/4"
PM250808S	5/16"	5/16"
PI251012S	5/16"	3/8"
PI251208S	3/8"	1/4"
PI251210S	3/8"	5/16"
PI251212S	3/8"	3/8"
PI251216S	3/8"	1/2"
PI251612S	1/2"	3/8"
PI251616S	1/2"	1/2"

Tube Hose to Elbows



Stem x Hose Tail

1400	Stem OD	To Suit Hose ID
PI290808S	1/4"	1/4"
PI290810S	1/4"	5/16"
PI291008S	5/16"	1/4"
PM290808S	5/16"	5/16"
PI291208S	3/8"	1/4"
PI291210S	3/8"	5/16"

Reducing Straight Connectors



Tube x Tube

1400	OD A	OD B
PI200806S	1/4"	3/16"
PM200804S	5/16"	5/32"
PI201006S	5/16"	3/16"
PI201008S	5/16"	1/4"
PI201206S	3/8"	3/16"
PI201208S	3/8"	1/4"
PI201210S	3/8"	5/16"
PI201610S	1/2"	5/16"
PI201612S	1/2"	3/8"

Flow Bend Tube Clips



90°

1400	OD mm	OD
PM2608S	8	5/16"
PM2610S	10	3/8"

Tube Supports



Tube

1400	To Suit Hose ID
TSI250S	1/4"
TSI312S	5/16"
TSI375S	3/8"

Locking Clip



1400	OD
PIC1808R	1/4"
PIC1812R	3/8"

Collet Covers



Imperial

1400	OD
PM1904S	5/32"
PI1908S	1/4"
PM1908S	5/16"
PI1916S	1/2"

Fluid-Air Components Ltd

ALL METAL PUSH-IN FITTINGS

One Touch



Features:

- Convenient One Touch fittings provide instant connections
- Light manual pressure on the collet ring is all that is required to instantly disconnect each tube; no special tool is required
- Nickel-plated brass ensures anti-corrosion and anti-contamination

Working Temperature:
-10°C to +60°C

Working Pressure
-0.8 bar to 8 bar*

*Dependent upon tubing specification.

Construction:

Resin Body:	Nickel-plated brass
Packing:	Nitrile
Back O-Ring:	POM
O-Ring:	Nitrile
Collet Ring:	Nickel-plated brass

Fluid-Air Components Ltd

ALL METAL PUSH-IN FITTINGS

One Touch Emergency Fittings Kits

FT PRO®

Convenient, compact boxes containing a selection of popular FT Pro One Touch metal push-in fittings along with handy tube cutter.

Available in three sizes: 6mm, 8mm and 10mm. Can be used with nylon 6, 11, 12, and polyurethane (ester and ether).



Working Temperature:
-10°C to +60°C*

Working Pressure:
0.8 to 8 bar*

Media:
Air and vacuum only.

Metal Push-in

0315	OD mm
FTP-06MMBOX-M	6
FTP-08MMBOX-M	8
FTP-10MMBOX-M	10
Tech Sheet 3130	

*Dependent upon tubing specification.

Contents:

6mm
Metal Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	2 x Shut Off Valves MNSF06	10 x Equal Tees MPUT-6	
8 x Equal Elbows MPUL-6	8 x 1/8" BSPP Male Stud Elbows MPL6-G01	5 x 1/4" BSPP Male Stud Elbows MPL6-G02	
2 x 1/8" BSPT Speed Controllers MNSE6-G01	2 x 1/4" BSPT Speed Controllers MNSE6-G02	10 x Equal Connectors MPUC-6	2 x Equal Bulkheads MPM-6
10 x 1/8" BSPT Male Studs MPC6-01	10 x 1/4" BSPT Male Studs MPC6-02	5 x M5 BSPT Male Studs MPC6-M5	
10 x 1/8" BSPP Male Studs MPC6-G01	10 x 1/4" BSPP Male Studs MPC6-G02	4 x 1/8" Manifolds KMDS-1/8	

8mm
Metal Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	2 x Shut Off Valves MNSF08	6 x Equal Tees MPUT-8	2 x Equal Bulkheads MPM-8
6 x Equal Elbows MPUL-8	6 x 1/8" BSPP Male Stud Elbows MPL8-G01	5 x 1/4" BSPP Male Stud Elbows MPL8-G02	
2 x 1/8" BSPT Speed Controllers MNSE8-G01	2 x 1/4" BSPT Speed Controllers MNSE8-G02	10 x Equal Connectors MPUC-8	
10 x 1/8" BSPT Male Studs MPC8-01	10 x 1/4" BSPT Male Studs MPC8-02	8 x 3/8" BSPT Male Studs MPC8-03	
8 x 1/8" BSPP Male Studs MPC8-G01	8 x 1/4" BSPP Male Studs MPC8-G02	4 x 1/8" Manifolds KMDS-1/8	

10mm
Metal Push-in Fittings & Tube Cutter

1 x Tube Cutter KTC-1	1 x Shut Off Valve MNSF10	4 x Equal Tees MPUT-10	
2 x Equal Elbows MPUL-10	2 x 1/4" BSPP Male Stud Elbows MPL10-G01	2 x 3/8" BSPP Male Stud Elbows MPL10-G03	
2 x 1/4" BSPT Speed Controllers MNSE10-G02	1 x 3/8" BSPT Speed Controller MNSE10-G03	6 x Equal Connectors MPUC-10	
8 x 1/4" BSPT Male Studs MPC10-02	10 x 3/8" BSPT Male Studs MPC10-03	2 x Equal Bulkheads MPM-10	
8 x 1/4" BSPP Male Studs MPC10-G02	5 x 3/8" BSPP Male Studs MPC10-G03	1 x 1/4" Manifolds KMDS-1/4	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ONE TOUCH ALL METAL PUSH-IN FITTINGS

Working Temperature: -10°C to + 60°C (dependent upon tubing specification)

Working Pressure: 0.8 to 8 bar (dependent upon tubing specification)

Tube connection and disconnection can be repeated several times and is performed with one hand, without the use of tools. Nickel plated brass bodies ensures anti-corrosion and anti-contamination.

Material: **Body and Collet:** Nickel plated brass
O-Ring: Nitrile
Threads: BSPT, BSPP and metric
Tube to Connect: PU, PE, nylon 6-11-12
Fluid: Compressed air

Male Studs



Male Thread, Metric & BSPT

0315	OD mm	Thread
MPC4-M5	4	M5
MPC4-01	4	1/8"
MPC4-M6	4	M6
MPC4-02	4	1/4"
MPC6-M5	6	M5
MPC6-01	6	1/8"
MPC6-M6	6	M6
MPC6-02	6	1/4"
MPC8-01	8	1/8"
MPC8-02	8	1/4"
MPC8-03	8	3/8"
MPC10-02	10	1/4"
MPC10-03	10	3/8"
MPC10-04	10	1/2"
MPC12-02	12	1/4"
MPC12-03	12	3/8"
MPC12-04	12	1/2"
Tech Sheet 3130		



Male Thread, BSPP

0315	OD mm	Thread
MPC4-G01	4	1/8"
MPC4-G02	4	1/4"
MPC6-G01	6	1/8"
MPC6-G02	6	1/4"
MPC6-G03	6	3/8"
MPC6-G04	6	1/2"
MPC8-G01	8	1/8"
MPC8-G02	8	1/4"
MPC8-G03	8	3/8"
MPC8-G04	8	1/2"
MPC10-G02	10	1/4"
MPC10-G03	10	3/8"
MPC10-G04	10	1/2"
MPC12-G02	12	1/4"
MPC12-G03	12	3/8"
MPC12-G04	12	1/2"
MPC14-G03	14	3/8"
MPC14-G04	14	1/2"
Tech Sheet 3130		

Male Hex Studs



Male Super Thread

0315	OD mm	Thread
MPCS4-G01	4	1/8"
MPCS4-G02	4	1/4"
MPCS6-G01	6	1/8"
MPCS6-G02	6	1/4"
MPCS6-G03	6	3/8"
MPCS6-G04	6	1/2"
MPCS8-G01	8	1/8"
MPCS8-G02	8	1/4"
MPCS8-G03	8	3/8"
MPCS8-G04	8	1/2"
MPCS10-G02	10	1/4"
MPCS10-G03	10	3/8"
MPCS10-G04	10	1/2"
MPCS12-G02	12	1/4"
MPCS12-G03	12	3/8"
MPCS12-G04	12	1/2"
MPCS14-G03	14	3/8"
MPCS14-G04	14	1/2"

Male Round Studs



Male Super Thread

0315	OD mm	Thread
MPCS4-M5	4	M5
MPCS4-01	4	1/8"
MPCS6-M5	6	M5
MPCS6-01	6	1/8"
MPCS6-02	6	1/4"
MPCS8-01	8	1/8"
MPCS8-02	8	1/4"

Female Studs



Female Thread, BSPP

0315	OD mm	Thread
MPCF4-G01	4	1/8"
MPCF4-G02	4	1/4"
MPCF6-G01	6	1/8"
MPCF6-G02	6	1/4"
MPCF8-G01	8	1/8"
MPCF8-G02	8	1/4"
MPCF8-G03	8	3/8"
MPCF10-G02	10	1/4"
MPCF10-G03	10	3/8"
MPCF10-G04	10	1/2"
MPCF12-G02	12	1/4"
MPCF12-G03	12	3/8"
MPCF12-G04	12	1/2"
Tech Sheet 3130		

Female Bulkhead Connectors



Female Thread, BSPP

0315	OD mm	Thread
MPMF6-G01	6	1/8"
MPMF6-G02	6	1/4"
Tech Sheet 3130		

Female Swivel Elbows



Female Thread, BSPP

0315	OD mm	Thread
MPLF4-G01	4	1/8"
MPLF6-G01	6	1/8"
MPLF6-G02	6	1/4"
MPLF8-G02	8	1/4"
MPLF8-G04	8	1/2"
MPLF10-G02	10	1/4"
Tech Sheet 3130		

Fluid-Air Components Ltd

ONE TOUCH ALL METAL PUSH-IN FITTINGS

Working Temperature: -10°C to + 60°C (dependent upon tubing specification)

Working Pressure: 0.8 to 8 bar (dependent upon tubing specification)

Tube connection and disconnection can be repeated several times and is performed with one hand, without the use of tools. Nickel plated brass bodies ensures anti-corrosion and anti-contamination.

Material: **Body and Collet:** Nickel plated brass
O-Ring: Nitrile
Threads: BSPT, BSPP and metric
Tube to Connect: PU, PE, nylon 6-11-12
Fluid: Compressed air

Male Stud Swivel Elbows



Male Thread, Metric & BSPT

0315	OD mm	Thread
MPL4-01	4	1/8"
MPL6-01	6	1/8"
MPL6-02	6	1/4"
MPL8-01	8	1/8"
MPL8-02	8	1/4"
MPL8-03	8	3/8"
MPL8-04	8	1/2"
MPL10-02	10	1/4"
MPL10-03	10	3/8"
MPL10-04	10	1/2"
MPL12-02	12	1/4"
MPL12-03	12	3/8"
MPL12-04	12	1/2"
5711114-3/8	14	3/8"
5711114-1/2	14	1/2"
Tech Sheet 3130		



Male Thread, BSPP

0315	OD mm	Thread
MPL4-M5	4	M5
MPL4-G01	4	1/8"
MPL4-G02	4	1/4"
MPL6-M5	6	M5
MPL6-G01	6	1/8"
MPL6-G02	6	1/4"
MPL8-G01	8	1/8"
MPL8-G02	8	1/4"
MPL8-G03	8	3/8"
MPL8-G04	8	1/2"
MPL10-G02	10	1/4"
MPL10-G03	10	3/8"
MPL10-G04	10	1/2"
MPL12-G02	12	1/4"
MPL12-G03	12	3/8"
MPL12-G04	12	1/2"
MPL14-G03	14	3/8"
MPL14-G04	14	1/2"
Tech Sheet 3130		



Extended Male Thread, BSPP

0315	OD mm	Thread
MPLL4-G01	4	1/8"
MPLL6-G01	6	1/8"
MPLL6-G02	6	1/4"
MPLL8-G01	8	1/8"
MPLL8-G02	8	1/4"
MPLL8-G03	8	3/8"
MPLL10-G02	10	1/4"
MPLL10-G03	10	3/8"
MPLL10-G04	10	1/2"
MPLL12-G02	12	1/4"
MPLL12-G03	12	3/8"
MPLL12-G04	12	1/2"
Tech Sheet 3130		

Male Stud Swivel Tees



Branch Male Thread, BSPP

0315	OD mm	Thread
MPB4-M5	4	M5
MPB4-G01	4	1/8"
MPB4-G02	4	1/4"
MPB6-M5	6	M5
MPB6-G01	6	1/8"
MPB6-G02	6	1/4"
MPB8-G01	8	1/8"
MPB8-G02	8	1/4"
MPB8-G03	8	3/8"
MPB8-G04	8	1/2"
MPB10-G02	10	1/4"
MPB10-G03	10	3/8"
MPB10-G04	10	1/2"
MPB12-G03	12	3/8"
MPB12-G04	12	1/2"
MPB14-G03	14	3/8"
MPB14-G04	14	1/2"
Tech Sheet 3130		

Single Banjos



Male Thread, Metric & BSPP

0315	OD mm	Thread
MPH4-M5	4	M5
MPH4-G01	4	1/8"
MPH6-G01	6	1/8"
MPH8-G01	8	1/8"
MPH8-G02	8	1/4"
Tech Sheet 3130		

Speed Control Valves



Tube x Metric & BSPP

0315	OD mm	Thread
MNSE4-M5	4	M5
MNSE4-G01	4	1/8"
MNSE4-G02	4	1/4"
MNSE6-G01	6	1/8"
MNSE6-G02	6	1/4"
MNSE8-G01	8	1/8"
MNSE8-G02	8	1/4"
MNSE8-G03	8	3/8"
MNSE10-G02	10	1/4"
MNSE10-G03	10	3/8"
MNSE10-G04	10	1/2"
MNSE12-G02	12	1/4"
MNSE12-G03	12	3/8"
MNSE12-G04	12	1/2"
Tech Sheet 3130		

Fluid-Air Components Ltd

ONE TOUCH ALL METAL PUSH-IN FITTINGS

Working Temperature: -10°C to + 60°C (dependent upon tubing specification)

Working Pressure: 0.8 to 8 bar (dependent upon tubing specification)

Tube connection and disconnection can be repeated several times and is performed with one hand, without the use of tools. Nickel plated brass bodies ensures anti-corrosion and anti-contamination.

Material: **Body and Collet:** Nickel plated brass
O-Ring: Nitrile
Threads: BSPT, BSPP and metric
Tube to Connect: PU, PE, nylon 6-11-12
Fluid: Compressed air

Tube x Tube Connectors



Equal Straights

0315	OD mm
MPUC-4	4
MPUC-6	6
MPUC-8	8
MPUC-10	10
MPUC-12	12
MPUC-14	14
Tech Sheet 3130	



Unequal Straights

0315	OD mm	OD mm
MPG6-4	6	4
MPG8-6	8	6
MPG10-8	10	8
MPG12-10	12	10
Tech Sheet 3130		



Equal Elbows

0315	OD mm
MPUL-4	4
MPUL-6	6
MPUL-8	8
MPUL-10	10
MPUL-12	12
MPUL-14	14
Tech Sheet 3130	



Equal Tees

0315	OD mm
MPUT-4	4
MPUT-6	6
MPUT-8	8
MPUT-10	10
MPUT-12	12
MPUT-14	14
Tech Sheet 3130	



Equal Ys

0315	OD mm
MPY-6	6
MPY-8	8
Tech Sheet 3130	



Equal Bulkheads

0315	OD mm
MPM-4	4
MPM-6	6
MPM-8	8
MPM-10	10
MPM-12	12
Tech Sheet 3130	

Tube x Stem Connectors



Straight, Tube x Stem

0315	Stem OD mm	OD mm
MPJG6-4	6	4
MPJG8-4	8	4
MPJG8-6	8	6
MPJG10-4	10	4
MPJG10-6	10	6
MPJG10-8	10	8
MPJG12-8	12	8
MPJG12-10	12	10
Tech Sheet 3130		

Standpipes



Male Thread, BSPP

0315	Stem OD mm	Thread
MPCJ4-G01	4	1/8"
MPCJ4-G02	4	1/4"
MPCJ6-G01	6	1/8"
MPCJ6-G02	6	1/4"
MPCJ8-G02	8	1/4"
MPCJ8-G03	8	3/8"
MPCJ8-G04	8	1/2"
MPCJ10-G02	10	1/4"
MPCJ10-G03	10	3/8"
MPCJ10-G04	10	1/2"
MPCJ12-G02	12	1/4"
MPCJ12-G03	12	3/8"
MPCJ12-G04	12	1/2"
Tech Sheet 3130		



Female Thread, BSPP

0315	Stem OD mm	Thread
MPCFJ4-G01	4	1/8"
MPCFJ4-G02	4	1/4"
MPCFJ6-G01	6	1/8"
MPCFJ6-G02	6	1/4"
MPCFJ8-G02	8	1/4"
MPCFJ8-G03	8	3/8"
MPCFJ8-G04	8	1/2"
MPCFJ10-G02	10	1/4"
MPCFJ10-G03	10	3/8"
MPCFJ10-G04	10	1/2"
MPCFJ12-G02	12	1/4"
MPCFJ12-G03	12	3/8"
MPCFJ12-G04	12	1/2"
Tech Sheet 3130		

Shut Off Valves



Tube x Tube

0315	OD mm
MNSF04	4
MNSF06	6
MNSF08	8
MNSF10	10
MNSF12	12
Tech Sheet 3130	

LF 3600® PUSH-IN FITTINGS

All metal new LF 3600 (except sealing components) is compatible with many liquids and gases of average aggressiveness and is ideal for environments that require mechanical strength-incorporating high phosphorus chemical nickel plating that conforms to FDA standard (FOOD AND DRUG ADMINISTRATION).

Working Temperature:
-20°C to + 120°C

Maximum Working Pressure for Compressed Air:
20 bar

NOTE: Ideal for food applications.
These fittings represents only part of this new range, for full details please speak to our technical department.

Male Stud Fittings



BSPT

1014	OD mm	Thread
LE-3675 04 10	4	1/8"
LE-3675 04 13	4	1/4"
LE-3675 06 10	6	1/8"
LE-3675 06 13	6	1/4"
LE-3675 08 10	8	1/8"
LE-3675 08 13	8	1/4"
LE-3675 08 17	8	3/8"
LE-3675 10 13	10	1/4"
LE-3675 10 17	10	3/8"
LE-3675 10 21	10	1/2"
LE-3675 12 13	12	1/4"
LE-3675 12 17	12	3/8"
LE-3675 12 21	12	1/2"
LE-3675 14 17	14	3/8"
LE-3675 14 21	14	1/2"
Tech Sheet 1528		



Standpipe, BSPT

1014	Stem OD mm	Thread
LE-3621 04 10	4	1/8"
LE-3621 06 10	6	1/8"
LE-3621 06 13	6	1/4"
LE-3621 08 10	8	1/8"
LE-3621 08 13	8	1/4"
LE-3621 10 13	10	1/4"
LE-3621 10 17	10	3/8"
LE-3621 12 17	12	3/8"
LE-3621 12 21	12	1/2"
Tech Sheet 1528		



Elbow, BSPT

1014	OD mm	Thread
LE-3609 04 10	4	1/8"
LE-3609 04 13	4	1/4"
LE-3609 06 10	6	1/8"
LE-3609 06 13	6	1/4"
LE-3609 08 10	8	1/8"
LE-3609 08 13	8	1/4"
LE-3609 08 17	8	3/8"
LE-3609 10 13	10	1/4"
LE-3609 10 17	10	3/8"
LE-3609 12 13	12	1/4"
LE-3609 12 17	12	3/8"
LE-3609 12 21	12	1/2"
LE-3609 14 21	14	1/2"
Tech Sheet 1528		



Hexagon, Metric & BSPP

1014	OD mm	Thread
LE-3601 04 10	4	1/8"
LE-3601 04 52	4	M6 x 1
LE-3601 04 13	4	1/4"
LE-3601 04 56	4	M8 x 1
LE-3601 06 19	6	M5 x 0.8
LE-3601 06 10	6	1/8"
LE-3601 06 60	6	M10 x 1
LE-3601 06 13	6	1/4"
LE-3601 08 10	8	1/8"
LE-3601 08 13	8	1/4"
LE-3601 08 17	8	3/8"
LE-3601 10 13	10	1/4"
LE-3601 10 17	10	3/8"
LE-3601 10 21	10	1/2"
LE-3601 12 13	12	1/4"
LE-3601 12 17	12	3/8"
LE-3601 12 21	12	1/2"
LE-3601 14 17	14	3/8"
LE-3601 14 21	14	1/2"
Tech Sheet 1528		



Metric

1014	OD mm	Thread
LE-3681 04 19	4	M5 x 0.8
Tech Sheet 1528		



Extended Male Stud Elbow, Metric & BSPP

1014	OD mm	Thread
LE-3669 04 19	4	M5 x 0.8
LE-3669 04 10	4	1/8"
LE-3669 06 10	6	1/8"
LE-3669 06 13	6	1/4"
LE-3669 08 10	8	1/8"
LE-3669 08 13	8	1/4"
LE-3669 10 13	10	1/4"
LE-3669 10 17	10	3/8"
LE-3669 12 17	12	3/8"
LE-3669 14 21	14	1/2"
Tech Sheet 1528		



Standpipe, Metric & BSPP

1014	Stem OD mm	Thread
LE-3631 04 19	4	M5 x 0.8
LE-3631 04 10	4	1/8"
LE-3631 06 10	6	1/8"
LE-3631 06 13	6	1/4"
LE-3631 08 13	8	1/4"
LE-3631 10 13	10	1/4"
LE-3631 10 17	10	3/8"
LE-3631 10 21	10	1/2"
LE-3631 12 17	12	3/8"
LE-3631 12 21	12	1/2"
LE-3631 14 21	14	1/2"
Tech Sheet 1528		

Fluid-Air Components Ltd

LF 3600® PUSH-IN FITTINGS

Male Stud Fittings



Elbow, Metric & BSPP

1014	OD mm	Thread
LE-3699 04 19	4	M5 x 0.8
LE-3699 04 52	4	M6 x 1
LE-3699 04 13	4	1/4"
LE-3699 04 56	4	M8 x 1
LE-3699 06 10	6	1/8"
LE-3699 06 60	6	M10 x 1
LE-3699 06 13	6	1/4"
LE-3699 08 10	8	1/8"
LE-3699 08 13	8	1/4"
LE-3699 08 17	8	3/8"
LE-3699 10 13	10	1/4"
LE-3699 10 17	10	3/8"
LE-3699 12 13	12	1/4"
LE-3699 12 17	12	3/8"
LE-3699 12 21	12	1/2"
LE-3699 14 17	14	3/8"
Tech Sheet 1528		



Branch Tee, BSPT

1014	OD mm	Thread
LE-3608 06 10	6	1/8"
LE-3608 06 13	6	1/4"
LE-3608 08 13	8	1/4"
LE-3608 10 13	10	1/4"
LE-3608 12 17	12	3/8"
LE-3608 14 21	14	1/2"
Tech Sheet 1528		



Run Tee, BSPT

1014	OD mm	Thread
LE-3603 06 10	6	1/8"
LE-3603 06 13	6	1/4"
LE-3603 08 13	8	1/4"
LE-3603 10 13	10	1/4"
Tech Sheet 1528		



Branch Tee, BSPP

1014	OD mm	Thread
LE-3698 04 10	4	1/8"
LE-3698 06 13	6	1/4"
LE-3698 08 13	8	1/4"
LE-3698 14 21	14	1/2"
Tech Sheet 1528		



Run Tee, BSPP

1014	OD mm	Thread
LE-3693 06 10	6	1/8"
LE-3693 08 13	8	1/4"
Tech Sheet 1528		



Extended Stud Elbow, BSPT

1014	OD mm	Thread
LE-3629 04 10	4	1/8"
LE-3629 06 10	6	1/8"
LE-3629 06 13	6	1/4"
LE-3629 08 10	8	1/8"
LE-3629 08 13	8	1/4"
Tech Sheet 1528		

Female Stud Fittings



Female Stud Hexagon, Metric & BSPP

1014	OD mm	Thread
LE-3614 04 10	4	1/8"
LE-3614 04 13	4	1/4"
LE-3614 06 10	6	1/8"
LE-3614 06 13	6	1/4"
LE-3614 08 10	8	1/8"
LE-3614 08 13	8	1/4"
LE-3614 10 17	10	3/8"
LE-3614 12 17	12	3/8"
LE-3614 12 21	12	1/2"
Tech Sheet 1528		

Single Banjo c/w Bolt



Metric & BSPP

1014	OD mm	Thread
LE-3618 04 19	4	M5 x 0.8
LE-3618 04 10	4	1/8"
LE-3618 06 19	6	M5 x 0.8
LE-3618 06 10	6	1/8"
LE-3618 06 13	6	1/4"
LE-3618 08 10	8	1/8"
LE-3618 08 13	8	1/4"
LE-3618 10 17	10	3/8"
Tech Sheet 1528		

Equal Connectors



Tube x Tube

1014	OD mm
LE-3606 04 00	4
LE-3606 06 00	6
LE-3606 08 00	8
LE-3606 10 00	10
LE-3606 12 00	12
LE-3606 14 00	14
Tech Sheet 1528	

LF 3600® PUSH-IN FITTINGS

Equal Elbows



Tube x Tube

1014	OD mm
LE-3602 04 00	4
LE-3602 06 00	6
LE-3602 08 00	8
LE-3602 10 00	10
LE-3602 12 00	12
LE-3602 14 00	14
Tech Sheet 1528	

Equal Tees



Tube x Tube

1014	OD mm
LE-3604 04 00	4
LE-3604 06 00	6
LE-3604 08 00	8
LE-3604 10 00	10
LE-3604 12 00	12
LE-3604 14 00	14
Tech Sheet 1528	

Double Male Stem Connectors



Stem x Stem

1014	Stem OD mm
LE-3620 04 00	4
LE-3620 06 00	6
LE-3620 08 00	8
LE-3620 10 00	10
LE-3620 12 00	12
Tech Sheet 1528	

Equal Bulkhead Elbows



Tube x Tube

1014	OD mm
LE-3639 04 00	4
LE-3639 06 00	6
LE-3639 08 00	8
LE-3639 10 00	10
LE-3639 12 00	12
Tech Sheet 1528	

Bulkhead Connectors



Tube x Tube

1014	OD mm
LE-3616 04 00	4
LE-3616 06 00	6
LE-3616 08 00	8
LE-3616 10 00	10
LE-3616 12 00	12
LE-3616 14 00	14
Tech Sheet 1528	



Female, BSPP

1014	OD mm	Thread
LE-3636 06 10	6	1/8"
LE-3636 06 13	6	1/4"
LE-3636 08 10	8	1/8"
LE-3636 08 13	8	1/4"
LE-3636 10 17	10	3/8"
LE-3636 12 21	12	1/2"
Tech Sheet 1528		

Blanking Plugs



Tube

1014	Stem OD mm
LE-3626 04 00	4
LE-3626 06 00	6
LE-3626 08 00	8
LE-3626 10 00	10
LE-3626 12 00	12
Tech Sheet 1528	

Plug-in Fittings



Reducer, Tube x Stem

1014	OD mm	Stem OD mm
LE-3666 04 06	4	6
LE-3666 04 08	4	8
LE-3666 06 08	6	8
LE-3666 06 10	6	10
LE-3666 08 10	8	10
LE-3666 08 12	8	12
LE-3666 10 12	10	12
LE-3666 12 14	12	14
Tech Sheet 1528		



Increaser

1014	OD mm	Stem OD mm
LE-3668 06 04	6	4
Tech Sheet 1528		



Metric/Imperial Adaptor, Tube x Stem

1014	OD	Stem OD mm
LE-3667 06 56	1/4"	6
Tech Sheet 1528		



Stem x Hose Tail

1014	Stem OD	To Suit Hose ID mm
LE-3622 04 53	4	3.2
LE-3622 04 05	4	5
LE-3622 06 05	6	5
LE-3622 08 56	8	6.3
LE-3622 08 08	8	8
LE-3622 10 56	10	6.3
LE-3622 10 08	10	8
LE-3622 12 08	12	8
LE-3622 12 10	12	10
LE-3622 12 62	12	12.5
Tech Sheet 1528		

Fluid-Air Components Ltd

CENTRALISED LUBRICATION SYSTEM FITTINGS

This range of fittings has been designed for uses involving both rotation or linear movements which require lubrication.
Designed using Legris push-in technology, this range is produced with specific applications in mind, hence its:

- Emphasis on safety – the tube cannot be disconnected without using a spanner
- Nitrile seals on nut assemblies
- Sealing of tube by 2 O-rings in addition to the gripping teeth

Working Temperature: -40°C to +120°C

Working Pressure: Up to 60 bar

The characteristics provide a perfect component for such applications as:

- Lubrication circuits on industrial machinery: Wood industry, textile, paper, cement industry
- Lubrication on industrial equipment and vehicles (trucks)
- Lubrication on public works vehicles (mobile cranes) and agricultural equipment

Suitable Fluids: Lubricating oils, liquid or viscous greases, oil sprays

Material:
Body: Brass
Seals: Nitrile rubber

Equal Connectors



Equal Straights

1012	OD mm
LE-6106 04 00	4
LE-6106 06 00	6
LE-6106 08 00	8



Equal Tees

1012	OD mm
LE-6104 04 00	4

Copper Washers



1012	OD mm
LE-0138 08 00	8
LE-0138 10 00	10
LE-0138 12 00	12

Close Tolerance Rigid Nylon



25 Metre Coils, Black

6001	OD mm	ID mm	Bend Radius mm
1025L04 01 25	4	2.5	35
1025L06 01	6	4	45
1025L08 01 05	8	5	70
1025L08 01	8	6	65

Stud Couplings



Male Studs, BSPT

1012	OD mm	Thread
LE-6105 04 10	4	1/8"
LE-6105 06 10	6	1/8"
LE-6105 04 13	4	1/4"
LE-6105 06 13	6	1/4"



Male Studs, Metric Taper

1012	OD mm	Thread
LE-6105 04 52	4	M6 x 1
LE-6105 04 56	4	M8 x 1
LE-6105 04 57	4	M8 x 1.25
LE-6105 04 60	4	M10 x 1
LE-6105 06 60	6	M10 x 1



Male Studs, Metric Parallel

1012	OD mm	Thread
LE-6101 06 60	6	M10 x 1
LE-6101 06 65	6	M12 x 1



Female Studs, Metric Parallel

1012	OD mm	Thread
LE-6114 04 56	4	M8 x 1
LE-6114 06 56	6	M8 x 1



Male Stud Elbows, BSPT

1012	OD mm	Thread
LE-6179 04 10	4	1/8"
LE-6179 06 10	6	1/8"
LE-6179 04 13	4	1/4"
LE-6179 06 13	6	1/4"



Male Stud Elbows, Metric

1012	OD mm	Thread
LE-6179 04 52	4	M6 x 1
LE-6179 04 56	4	M8 x 1
LE-6179 04 57	4	M8 x 1.25
LE-6179 04 60	4	M10 x 1
LE-6179 06 65	6	M12 x 1
LE-6179 08 65	8	M12 x 1

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

50000 SERIES - BRASS PUSH-IN FITTINGS

Working Temperature: -20°C to +80°C

Maximum Working Pressure: -0.99 to 20 bar (290 psi)

Media: Suitable for compressed air and vacuum

Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT

Male Studs



Male Thread, Metric & BSPP

1020	OD mm	Thread
P2-3-M5	3	M5
P2-4-M5	4	M5
P2-4-1/8	4	1/8"
P2-4-1/4	4	1/4"
P2-5-M5	5	M5
P2-5-1/8	5	1/8"
P2-6-M5	6	M5
P2-6-1/8	6	1/8"
P2-6-1/4	6	1/4"
P2-6-3/8	6	3/8"
P2-6-1/2	6	1/2"
P2-8-1/8	8	1/8"
P2-8-1/4	8	1/4"
P2-8-3/8	8	3/8"
P2-8-1/2	8	1/2"
P2-10-1/4	10	1/4"
P2-10-3/8	10	3/8"
P2-10-1/2	10	1/2"
P2-12-1/4	12	1/4"
P2-12-3/8	12	3/8"
P2-12-1/2	12	1/2"
P2-14-3/8	14	3/8"
P2-14-1/2	14	1/2"
Tech Sheet 30106		



Male Thread, BSPT (Universal Short)

1020	OD mm	Thread
P1-4-1/8	4	1/8"
P1-4-1/4	4	1/4"
P1-5-1/8	5	1/8"
P1-5-1/4	5	1/4"
P1-6-1/8	6	1/8"
P1-6-1/4	6	1/4"
P1-6-3/8	6	3/8"
P1-6-1/2	6	1/2"
P1-8-1/8	8	1/8"
P1-8-1/4	8	1/4"
P1-8-3/8	8	3/8"
P1-8-1/2	8	1/2"
P1-10-1/4	10	1/4"
P1-10-3/8	10	3/8"
P1-10-1/2	10	1/2"
P1-12-1/4	12	1/4"
P1-12-3/8	12	3/8"
P1-12-1/2	12	1/2"
P1-14-3/8	14	3/8"
P1-14-1/2	14	1/2"
Tech Sheet 30106		



Universal, BSPT, BSPP & NPT (Round Body, Internal Hex)

1020	OD mm	Thread
P20-3-M5	3	M5
P20-4-M5	4	M5
P20-4-1/8	4	1/8"
P20-6-M5	6	M5
P20-6-1/8	6	1/8"
P20-6-1/4	6	1/4"
P20-8-1/8	8	1/8"
P20-8-1/4	8	1/4"
Tech Sheet 30106		

Female Studs



Female Thread, Metric & BSPP

1020	OD mm	Thread
P3-3-M5	3	M5
P3-4-M5	4	M5
P3-4-1/8	4	1/8"
P3-4-1/4	4	1/4"
P3-5-1/8	5	1/8"
P3-6-1/8	6	1/8"
P3-6-1/4	6	1/4"
P3-8-1/8	8	1/8"
P3-8-1/4	8	1/4"
P3-8-3/8	8	3/8"
P3-10-1/4	10	1/4"
P3-10-3/8	10	3/8"
P3-10-1/2	10	1/2"
P3-12-3/8	12	3/8"
P3-12-1/2	12	1/2"
Tech Sheet 30106		

Male Stud Elbows



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
P6-4-M5	4	M5
P6-4-1/8	4	1/8"
P6-5-1/8	5	1/8"
P6-6-1/8	6	1/8"
P6-6-1/4	6	1/4"
P6-8-1/8	8	1/8"
P6-8-1/4	8	1/4"
P6-10-1/4	10	1/4"
P6-10-3/8	10	3/8"
P6-12-1/4	12	1/4"
P6-12-3/8	12	3/8"
Tech Sheet 30106		

Male Stud Swivel Elbows



Extended Male Thread, BSPP

1020	OD mm	Thread
P51-6-18	6	1/8"
P51-6-14	6	1/4"
P51-8-14	8	1/4"
P51-8-38	8	3/8"
Tech Sheet 30106		



Extended Male, Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
P50-4-18	4	1/8"
P50-6-18	6	1/8"
P50-6-14	6	1/4"
P50-8-18	8	1/8"
P50-8-14	8	1/4"
P50-10-38	10	3/8"
Tech Sheet 30106		

Fluid-Air Components Ltd

50000 SERIES - BRASS PUSH-IN FITTINGS

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 20 bar (220 psi)

Media: Suitable for compressed air and vacuum

Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT

Male Stud Swivel Elbows



Male Thread, Metric & BSPP

1020	OD	Thread
P8-3-M5	3	M5
P8-4-M5	4	M5
P8-4-1/8	4	1/8"
P8-4-1/4	4	1/4"
P8-5-M5	5	M5
P8-5-1/8	5	1/8"
P8-6-M5	6	M5
P8-6-1/8	6	1/8"
P8-6-1/4	6	1/4"
P8-6-3/8	6	3/8"
P8-8-1/8	8	1/8"
P8-8-1/4	8	1/4"
P8-8-3/8	8	3/8"
P8-8-1/2	8	1/2"
P8-10-1/4	10	1/4"
P8-10-3/8	10	3/8"
P8-10-1/2	10	1/2"
P8-12-1/4	12	1/4"
P8-12-3/8	12	3/8"
P8-12-1/2	12	1/2"
P8-14-3/8	14	3/8"
P8-14-1/2	14	1/2"
Tech Sheet 30106		



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
P7-4-1/8	4	1/8"
P7-4-1/4	4	1/4"
P7-5-1/8	5	1/8"
P7-6-1/8	6	1/8"
P7-6-1/4	6	1/4"
P7-8-1/8	8	1/8"
P7-8-1/4	8	1/4"
P7-8-3/8	8	3/8"
P7-8-1/2	8	1/2"
P7-10-1/4	10	1/4"
P7-10-3/8	10	3/8"
P7-10-1/2	10	1/2"
P7-12-3/8	12	3/8"
P7-12-1/2	12	1/2"
P7-14-3/8	14	3/8"
P7-14-1/2	14	1/2"
Tech Sheet 30106		

Female Stud Elbows



Female Thread, BSPP

1020	OD mm	Thread
P14-4-18	4	1/8"
P14-4-14	4	1/4"
P14-6-18	6	1/8"
P14-6-14	6	1/4"
P14-8-18	8	1/8"
P14-8-14	8	1/4"
P14-8-38	8	3/8"
Tech Sheet 30106		

Male Stud Tees



Branch Male Thread, BSPT

1020	OD mm	Thread
P10-4-1/8	4	1/8"
P10-5-1/8	5	1/8"
P10-6-1/8	6	1/8"
P10-8-1/8	8	1/8"
P10-8-1/4	8	1/4"
P10-10-1/4	10	1/4"
P10-12-1/4	12	1/4"
P10-12-3/8	12	3/8"
Tech Sheet 30106		

Male Stud Swivel Tees



Branch Male Thread, Metric & BSPP

1020	OD mm	Thread
P12-4-M5	4	M5
P12-4-1/8	4	1/8"
P12-5-M5	5	M5
P12-5-1/8	5	1/8"
P12-6-M5	6	M5
P12-6-1/8	6	1/8"
P12-6-1/4	6	1/4"
P12-8-1/8	8	1/8"
P12-8-1/4	8	1/4"
P12-8-3/8	8	3/8"
P12-8-1/2	8	1/2"
P12-10-1/4	10	1/4"
P12-10-3/8	10	3/8"
P12-10-1/2	10	1/2"
P12-12-3/8	12	3/8"
P12-12-1/2	12	1/2"
P12-14-3/8	14	3/8"
P12-14-1/2	14	1/2"
Tech Sheet 30106		



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
P11-5-1/8	5	1/8"
P11-6-1/8	6	1/8"
P11-6-1/4	6	1/4"
P11-8-1/8	8	1/8"
P11-8-1/4	8	1/4"
P11-8-3/8	8	3/8"
P11-8-1/2	8	1/2"
P11-10-1/4	10	1/4"
P11-10-3/8	10	3/8"
P11-10-1/2	10	1/2"
P11-12-3/8	12	3/8"
P11-12-1/2	12	1/2"
P11-14-3/8	14	3/8"
P11-14-1/2	14	1/2"
Tech Sheet 30106		

50000 SERIES - BRASS PUSH-IN FITTINGS

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 20 bar (220 psi)

Media: Suitable for compressed air and vacuum

Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT

Male Stud Swivel Tees



Run Male Thread, Metric & BSPP

1020	OD mm	Thread
P45-4-M5	4	M5
P45-5-1/8	5	1/8"
P45-6-M5	6	M5
P45-6-1/8	6	1/8"
P45-6-1/4	6	1/4"
P45-8-1/8	8	1/8"
P45-8-1/4	8	1/4"
Tech Sheet 30106		



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
P44-4-1/8	4	1/8"
P44-6-1/8	6	1/8"
P44-6-1/4	6	1/4"
P44-8-1/8	8	1/8"
P44-8-1/4	8	1/4"
P44-10-3/8	10	3/8"
P44-12-3/8	12	3/8"
Tech Sheet 30106		

Straight Connectors



Equal Tube x Tube

1020	OD mm
P4-3	3
P4-4	4
P4-5	5
P4-6	6
P4-8	8
P4-10	10
P4-12	12
P4-14	14
Tech Sheet 30106	

Unequal Tube x Tube

1020	OD mm
P4-6-4	6-4
P4-8-6	8-6
Tech Sheet 30106	

Equal Elbows



Tube x Tube

1020	OD mm
P9-3	3
P9-4	4
P9-5	5
P9-6	6
P9-8	8
P9-10	10
P9-12	12
P9-14	14
Tech Sheet 30106	

Equal Bulkhead Connectors



Tube x Tube

1020	OD mm	Thread
P5-3	3	M10 x 1
P5-4	4	M12 x 1
P5-5	5	M14 x 1
P5-6	6	M14 x 1
P5-8	8	M16 x 1
P5-10	10	M20 x 1
P5-12	12	M22 x 1
Tech Sheet 30106		

Equal Tees



Tube x Tube

1020	OD mm
P16-3	3
P16-4	4
P16-5	5
P16-6	6
P16-8	8
P16-10	10
P16-12	12
P16-14	14
Tech Sheet 30106	

Equal Ys



Tube x Tube

1020	OD mm
P21-3	3
P21-4	4
P21-5	5
P21-6	6
P21-8	8
P21-10	10
Tech Sheet 30106	

Stem Adaptor



Metric & BSPP

1020	Stem OD mm	Thread
P30-4-M5	4	M5
P30-4-1/8	4	1/8"
P30-5-M5	5	M5
P30-5-1/8	5	1/8"
P30-5-1/4	5	1/4"
P30-6-M5	6	M5
P30-6-1/8	6	1/8"
P30-6-1/4	6	1/4"
P30-8-1/8	8	1/8"
P30-8-1/4	8	1/4"
P30-8-3/8	8	3/8"
P30-10-1/4	10	1/4"
P30-10-3/8	10	3/8"
P30-12-1/4	12	1/4"
P30-12-3/8	12	3/8"
Tech Sheet 30106		

Reducers



Tube x Stem

1020	OD mm	Stem OD mm
P32-4-3	3	4
P32-5-4	4	5
P32-6-4	4	6
P32-6-5	5	6
P32-8-6	6	8
P32-10-8	8	10
P32-12-8	8	12
P32-12-10	10	12
Tech Sheet 30106		

Fluid-Air Components Ltd

50000 SERIES, BRASS PUSH-IN FITTINGS

AIGNEP

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 20 bar (220 psi)

Media: Suitable for compressed air and vacuum

Single Banjo Body, 1 Outlet



Bolt Thread, Metric & BSPP

1020	OD mm	Thread
P17-4-M5	4	M5
P17-4-1/8	4	1/8"
P17-6-M5	6	M5
P17-6-1/8	6	1/8"
P17-6-1/4	6	1/4"
P17-8-1/8	8	1/8"
P17-8-1/4	8	1/4"
P17-8-3/8	8	3/8"
P17-10-1/4	10	1/4"
P17-12-3/8	12	3/8"
Tech Sheet 30106		

5 Way Manifolds



BSPP

1020	OD mm	Thread
P39-4-1/8	4	1/8"
P39-6-1/8	6	1/8"
P39-6-1/4	6	1/4"
P39-8-1/4	8	1/4"
Tech Sheet 30106		

Disassembling Tool



1020
P43
Tech Sheet 30106

Single Banjo Assembly, 1 Outlet



Bolt Thread, Metric & BSPP

1020	OD mm	Thread
P22-4-M5	4	M5
P22-4-1/8	4	1/8"
P22-5-M5	5	M5
P22-5-1/8	5	1/8"
P22-6-M5	6	M5
P22-6-1/8	6	1/8"
P22-6-1/4	6	1/4"
P22-8-1/8	8	1/8"
P22-8-1/4	8	1/4"
P22-8-3/8	8	3/8"
P22-10-1/4	10	1/4"
P22-10-3/8	10	3/8"
P22-12-3/8	12	3/8"
Tech Sheet 30106		

Double Banjo Assembly, 2 Outlets



Bolt Thread, BSPP

1020	OD mm	Thread
P23-4-1/8	4	1/8"
P23-6-1/8	6	1/8"
P23-6-1/4	6	1/4"
P23-8-1/8	8	1/8"
P23-8-1/4	8	1/4"
P23-8-3/8	8	3/8"
P23-10-1/4	10	1/4"
P23-12-3/8	12	3/8"
Tech Sheet 30106		

Triple Banjo Assembly, 3 Outlets



Bolt Thread, BSPP

1020	OD mm	Thread
P24-6-1/8	6	1/8"
P24-6-1/4	6	1/4"
P24-8-1/4	8	1/4"
Tech Sheet 30106		

Double Banjo Tee Assembly, 4 Outlets



Bolt Thread, BSPP

1020	OD mm	Thread
P26-6-1/4	6	1/4"
P26-8-1/4	8	1/4"
Tech Sheet 30106		

Double Banjo Tee Assembly, 6 Outlets



Bolt Thread, BSPP

1020	OD mm	Thread
P27-8-1/4	8	1/4"
Tech Sheet 30106		

Swivel Single Banjo Assembly, 1 Outlet



Bolt Thread, Metric & BSPP

1020	OD mm	Thread
P28-4-M5	4	M5
P28-4-1/8	4	1/8"
P28-5-M5	5	M5
P28-5-1/8	5	1/8"
P28-5-1/4	5	1/4"
P28-6-M5	6	M5
P28-6-1/8	6	1/8"
P28-6-1/4	6	1/4"
P28-8-1/8	8	1/8"
P28-8-1/4	8	1/4"
P28-10-1/4	10	1/4"
Tech Sheet 30106		

Swivel Double Banjo Tee Assembly, 2 Outlets



Bolt Thread, BSPP

1020	OD mm	Thread
P29-4-1/8	4	1/8"
P29-6-1/8	6	1/8"
Tech Sheet 30106		

FAC Fluid-Air Components Ltd

50000 SERIES BRASS PUSH-IN FITTINGS

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar
Vacuum: -0.99 bar

Material:
Body and Collet: Robust nickel plated brass body and Acetalic resin collet

O-Ring: Nitrile
Media: Compressed air

Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT

Elbows



Equal

1025	OD mm
50130N4	4
50130N6	6
50130N8	8
50130N10	10
50130N12	12
50130N14	14

Male Swivel Elbows



Universal, BSPT, BSPP & NPT

1025	OD mm	Thread
50111N4-1/8	4	1/8"
50111N4-1/4	4	1/4"
50111N6-1/8	6	1/8"
50111N6-1/4	6	1/4"
50111N8-1/8	8	1/8"
50111N8-1/4	8	1/4"
50111N8-3/8	8	3/8"
50111N8-1/2	8	1/2"
50111N10-1/4	10	1/4"
50111N10-3/8	10	3/8"
50111N10-1/2	10	1/2"
50111N12-3/8	12	3/8"
50111N12-1/2	12	1/2"
50111N14-3/8	14	3/8"
50111N14-1/2	14	1/2"

Female Swivel Elbows



BSPP

1025	OD mm	Thread
50106N4-1/8	4	1/8"
50106N4-1/4	4	1/4"
50106N6-1/8	6	1/8"
50106N6-1/4	6	1/4"
50106N8-1/8	8	1/8"
50106N8-1/4	8	1/4"
50106N8-3/8	8	3/8"

Tees



Equal

1025	OD mm
50230N4	4
50230N6	6
50230N8	8
50230N10	10
50230N12	12
50230N14	14

Male Swivel Tees



Universal, BSPT, BSPP & NPT

1025	OD mm	Thread
50211N4-1/8	4	1/8"
50211N4-1/4	4	1/4"
50211N6-1/8	6	1/8"
50211N6-1/4	6	1/4"
50211N8-1/8	8	1/8"
50211N8-1/4	8	1/4"
50211N8-3/8	8	3/8"
50211N8-1/2	8	1/2"
50211N10-1/4	10	1/4"
50211N10-3/8	10	3/8"
50211N10-1/2	10	1/2"
50211N12-3/8	12	3/8"
50211N12-1/2	12	1/2"
50211N14-3/8	14	3/8"
50211N14-1/2	14	1/2"

Male Swivel Offset Tees



Universal, BSPT, BSPP & NPT

1025	OD mm	Thread
50223N4-1/8	4	1/8"
50223N4-1/4	4	1/4"
50223N6-1/8	6	1/8"
50223N6-1/4	6	1/4"
50223N8-1/8	8	1/8"
50223N8-1/4	8	1/4"
50223N8-3/8	8	3/8"
50223N8-1/2	8	1/2"
50223N10-1/4	10	1/4"
50223N10-3/8	10	3/8"
50223N10-1/2	10	1/2"
50223N12-3/8	12	3/8"
50223N12-1/2	12	1/2"

Male Swivel Banjo



BSPP & Metric

1025	OD mm	Thread
50550N4-M5	4	M5
50550N4-1/8	4	1/8"
50550N6-M5	6	M5
50550N6-1/8	6	1/8"
50550N6-1/4	6	1/4"
50550N8-1/8	8	1/8"
50550N8-1/4	8	1/4"
50550N8-3/8	8	3/8"
50550N10-1/4	10	1/4"
50550N10-3/8	10	3/8"
50550N12-3/8	12	3/8"

Y Connectors



Equal

1025	OD mm
50310N4	4
50310N6	6
50310N8	8
50310N10	10

Straight Connector



Equal

1025	OD mm
50040N4	4
50040N6	6
50040N8	8
50040N10	10
50040N12	12

Unequal

1025	OD mm	OD mm
50040N6-4	4	6
50040N8-6	6	8
50040N10-8	8	10
50040N12-10	10	12

Reducer



Tube x Stem Reducers

1025	OD mm	OD mm
50700N6-4	6	4
50700N8-4	8	4
50700N8-6	8	6
50700N10-4	10	4
50700N10-6	10	6
50700N10-8	10	8
50700N12-8	12	8
50700N12-10	12	10

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

55000 SERIES METAL BODY PUSH-IN FITTINGS

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar

Vacuum: -0.99 bar

BSPT in conformity with ISO 7.1, BS 21, DIN 2999.
BSPP in conformity with ISO 228 Class A.
Metric in conformity with ISO R/262.
Fittings with "Universal Short" thread are suitable for both taper as well as parallel threads like NPT, NPTF, BSPP and BSPT.

Straight Male Adaptors

This is a Taper Thread designed so that its suitable for BSPT, BSPP, NPTF and Metric.



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
5500000001	4	1/8"
5500000013	4	1/4"
5500000002	5	1/8"
5500000003	5	1/4"
5500000004	6	1/8"
5500000005	6	1/4"
5500000014	6	3/8"
5500000015	6	1/2"
5500000006	8	1/8"
5500000007	8	1/4"
5500000008	8	3/8"
5500000016	8	1/2"
5500000009	10	1/4"
5500000010	10	3/8"
5500000017	10	1/2"
5500000011	12	1/4"
5500000012	12	3/8"
5500000018	12	1/2"
5500000019	14	3/8"
5500000020	14	1/2"
Tech Sheet 10709		



Universal, BSPT, BSPP & NPT

1020	OD mm	Thread
5501000001	4	1/8"
5501000002	6	1/8"
5501000003	6	1/4"
5501000004	8	1/8"
5501000005	8	1/4"
Tech Sheet 10709		



(Hex Body) Metric & BSPP

1020	OD mm	Thread
5002000N01	4	M5
5002000N02	4	1/8"
5002000N22	4	1/4"
5002000N18	5	M5
5002000N19	5	1/8"
5002000N20	6	M5
5002000N12	6	M12 x 1
5002000N13	6	M12 x 1.25
5002000N14	6	M12 x 1.5
5002000N03	6	1/8"
5002000N04	6	1/4"
5002000N27	6	3/8"
5002000N28	6	1/2"
5002000N17	8	M12 x 1.5
5002000N05	8	1/8"
5002000N06	8	1/4"
5002000N07	8	3/8"
5002000N29	8	1/2"
5002000N08	10	1/4"
5002000N09	10	3/8"
5002000N31	10	1/2"
5002000N32	12	1/4"
5002000N11	12	3/8"
5002000N23	12	1/2"
5002000N24	14	3/8"
5002000N25	14	1/2"
Tech Sheet 10709		

Straight Female Adaptors



(Hex Body) Metric & BSPT

1020	OD mm	Thread
5003000N08	4	M5
5003000N01	4	1/8"
5003000N09	4	1/4"
5003000N06	5	1/8"
5003000N02	6	1/8"
5003000N03	6	1/4"
5003000N04	8	1/8"
5003000N05	8	1/4"
5003000N10	8	3/8"
5003000N11	10	1/4"
5003000N12	10	3/8"
5003000N13	10	1/2"
5003000N14	12	3/8"
5003000N15	12	1/2"
Tech Sheet 10709		

Bulkhead Connectors



Tube x Tube

1020	OD mm	Thread Size:
5005000N01	4	M12X1
5005000N06	5	M14X1
5005000N02	6	M14X1
5005000N03	8	M16X1
5005000N04	10	M20X1
5005000N05	12	M22X1
Tech Sheet 10709		

58000 SERIES HIGH PRESSURE LUBRICATION FITTINGS

Working Temperature:
-30°C to +150°C

Maximum Working Pressure:
150 bar

Maximum Working Pressure for compressed air:
30 bar

Maximum Working Pressure for fluids
150 bar

- Nickel plated brass collet and body
- Compressed air, oil and grease
- PA6, PA11, PA12 polyethylene, polyurethane (polyurethane hoses require a minimum hardness of 98 shore)

Male Adaptors



Metric & BSPT

1020	OD mm	Thread
58000-4-M6	4	M6 x 1
58000-4-M8	4	M8 x 1
58000-4-M10	4	M10 x 1
58000-4-1/8	4	1/8"
58000-6-M6	6	M6 x 1
58000-6-M8	6	M8 x 1
58000-6-M10	6	M10 x 1
58000-6-1/8	6	1/8"

Swivel Elbow Adaptors



Metric & BSPT

1020	OD mm	Thread
58110-4-M6	4	M6 x 1
58110-4-M8	4	M8 x 1
58110-4-M10	4	M10 x 1
58110-4-1/8	4	1/8"
58110-6-M6	6	M6 x 1
58110-6-M8	6	M8 x 1
58110-6-M10	6	M10 x 1
58110-6-1/8	6	1/8"

Elbow Adaptors



Metric & BSPP

1020	OD mm	Thread
58100-4-M6	4	M6 x 1
58100-4-M8	4	M8 x 1
58100-4-M10	4	M10 x 1
58100-4-1/8	4	1/8"
58100-6-M6X1	6	M6 x 1
58100-6-M8X1	6	M8 x 1
58100-6-M10X1	6	M10 x 1
58100-6-1/8	6	1/8"

Straight Connectors



Tube x Tube

1020	OD mm	OD mm
58040-4	4	4
58040-6	6	6

Fluid-Air Components Ltd

89000 SERIES IMPERIAL TUBE FITTINGS

Working Temperature:
-20°c to +80°C

Working Pressure:
-0.99 bar to 20 bar

Fittings with "Short" tapered thread allow assembly with tapered as well as parallel threads (BSPT, NPT and BSPP) and have a reduced overall height.

The clamping washer made in stainless steel ensures the perfect grip on the tube with all kinds of material without damage to the surface.

The connection between the tube and the fitting ensure a tight seal even in severe conditions such as impact and vibration.

The design of the geometric seal ensures the perfect fit for vacuum applications

Suitable to be used with PA6, PA11, PA12, Polyethylene, Polyurethane (minimum hardness of 98 shore).

Material:
Body: Brass nickel plated
Collet: Brass nickel plated
Capsule: Brass nickel plated
Clamping Washer: Stainless steel 301
Media: Compressed air, vacuum, water

Straight Male Adaptors

This is a taper thread designed so that its suitable for BSPT, BSPP, NPTF and metric.



Universal Short Thread Type

1020	OD	Thread
8900000001	1/8"	1/8"
8900000002	1/8"	1/4"
8900000003	5/32"	1/8"
8900000004	5/32"	1/4"
8900000005	1/4"	1/8"
8900000006	1/4"	1/4"
8900000007	1/4"	3/8"
8900000008	5/16"	1/8"
8900000009	5/16"	1/4"
8900000010	5/16"	3/8"
8900000011	3/8"	1/8"
8900000012	3/8"	1/4"
8900000013	3/8"	3/8"
8900000014	3/8"	1/2"
8900000015	1/2"	1/8"
8900000016	1/2"	1/4"
8900000017	1/2"	3/8"
8900000018	1/2"	1/2"
Tech Sheet 10707		

Straight Female Adaptors



NPT

1020	OD	Thread
8903000001	1/8"	1/8"
8903000002	1/8"	1/4"
8903000003	5/32"	1/8"
8903000004	5/32"	1/4"
8903000005	1/4"	1/8"
8903000006	1/4"	1/4"
8903000007	3/8"	1/4"
8903000008	3/8"	3/8"
Tech Sheet 10707		

Swivel Male Elbows

This is a taper thread designed so that its suitable for BSPT, BSPP, NPTF and metric.



Universal Short Thread Type

1020	OD	Thread
8911100001	1/8"	1/8"
8911100002	1/8"	1/4"
8911100003	5/32"	1/8"
8911100004	5/32"	1/4"
8911100005	1/4"	1/8"
8911100006	1/4"	1/4"
8911100007	1/4"	3/8"
8911100008	5/16"	1/8"
8911100009	5/16"	1/4"
8911100011	3/8"	1/8"
8911100012	3/8"	1/4"
8911100013	3/8"	3/8"
8911100014	3/8"	1/2"
8911100015	1/2"	1/4"
8911100016	1/2"	3/8"
8911100017	1/2"	1/2"
Tech Sheet 10707		

Swivel Female Elbows



NPT

1020	OD	Thread
8910600001	5/32"	1/8"
8910600002	1/4"	1/4"
8910600003	5/32"	1/8"
8910600004	1/4"	1/4"
8910600005	3/8"	1/8"
8910600006	3/8"	1/4"
Tech Sheet 10707		

Swivel Tee Male Centre Leg

This is a taper thread designed so that its suitable for BSPT, BSPP, NPTF and metric.



Universal Short Thread Type

1020	OD	Thread
8921100001	1/8"	1/8"
8921100005	1/4"	1/8"
8921100006	1/4"	1/4"
8921100007	1/4"	3/8"
8921100014	3/8"	1/8"
8921100008	3/8"	1/4"
8921100009	3/8"	3/8"
8921100010	3/8"	1/2"
8921100011	1/2"	1/4"
8921100012	1/2"	3/8"
8921100013	1/2"	1/2"
Tech Sheet 10707		

AIGNEP



For **PRO3**
see page **420**

Fluid-Air Components Ltd

89000 SERIES IMPERIAL TUBE FITTINGS

Working Temperature:
-20°c to +80°C

Working Pressure:
-0.99 bar to 20 bar

The clamping washer made in stainless steel ensures the perfect grip on the tube with all kinds of material without damage to the surface.

The connection between the tube and the fitting ensure a tight seal even in severe conditions such as impact and vibration.

The design of the geometric seal ensures the perfect fit for vacuum applications.

Suitable to be used with PA6, PA11, PA12, polyethylene, polyurethane (minimum hardness of 98 shore).

Material:
Body: Brass nickel plated
Collet: Brass nickel plated
Capsule: Brass nickel plated
Clamping Washer: Stainless steel 301
Media: Compressed air, vacuum, water

Straight Male Adaptors



Tube x Tube

1020	OD
8904000001	1/8"
8904000002	5/32"
8904000004	1/4"
8904000005	5/16"
8904000007	3/8"
8904000008	1/2"

Tech Sheet 10707

Unequal Straight Male Adaptors



Tube x Tube

1020	OD	OD
8904000003	1/4"	5/32"
8904000006	3/8"	1/4"
8904000009	3/8"	1/2"

Tech Sheet 10707

Equal Elbows



Tube x Tube

1020	OD
8913000001	1/8"
8913000002	5/32"
8913000003	1/4"
8913000004	5/16"
8913000005	3/8"
8913000006	1/2"

Tech Sheet 10707

Equal Tees



Tube x Tube

1020	OD
8923000001	1/8"
8923000003	1/4"
8923000004	5/16"
8923000005	3/8"
8923000006	1/2"

Tech Sheet 10707

Equal Bulkheads



Tube x Tube

1020	OD
8905000001	1/8"
8905000003	1/4"
8905000004	5/16"
8905000005	3/8"
8905000006	1/2"

Tech Sheet 10707

Stem Reducers



Tube x Tube

1020	Stem OD	OD
8970000001	1/4"	1/8"
8970000002	1/4"	5/32"
8970000003	3/8"	1/4"
8970000004	1/2"	1/4"
8970000005	1/2"	3/8"

Tech Sheet 10707

FT PRO



For **Stainless Steel Mini Cylinders** see page **457**

Fluid-Air Components Ltd

FOOD GRADE PUSH-IN FITTINGS

AIGNEP

Working Temperature: -15°C to +190°C

Working Pressure: -0.99 to 20 bar

Brass nickel plated fittings designed for the food industr .
Suitable for compressed air, vacuum and water.

Straight Adaptors



Male Thread, Metric & BSPP

1020	OD mm	Thread
70020-4-M5	4	M5
70020-4-1/8	4	1/8"
70020-6-1/8	6	1/8"
70020-6-1/4	6	1/4"
70020-8-1/8	8	1/8"
70020-8-1/4	8	1/4"
70020-10-1/4	10	1/4"
70020-10-3/8	10	3/8"
70020-12-3/8	12	3/8"
Tech Sheet 1905		

Swivel Elbows



Male Thread, Metric & BSPP

1020	OD mm	Thread
70116-4-M5	4	M5
70116-4-1/8	4	1/8"
70116-6-1/8	6	1/8"
70116-6-1/4	6	1/4"
70116-8-1/8	8	1/8"
70116-8-1/4	8	1/4"
70116-10-1/4	10	1/4"
70116-10-3/8	10	3/8"
70116-12-3/8	12	3/8"
Tech Sheet 1905		

Tee Connectors



Tube x Tube

1020	OD mm
70230-4	4
70230-6	6
70230-8	8
70230-10	10
70230-12	12
Tech Sheet 1905	

Straight Connectors



Tube x Tube

1020	OD mm
70040-4	4
70040-6	6
70040-8	8
70040-10	10
70040-12	12
Tech Sheet 1905	

Swivel Tees



Male Thread, BSPT

1020	OD mm	Thread
70216-4-1/8	4	1/8"
70216-6-1/8	6	1/8"
70216-6-1/4	6	1/4"
70216-8-1/8	8	1/8"
70216-8-1/4	8	1/4"
Tech Sheet 1905		

FTPRO

For **ISO 15552 Cylinders**
see pages **478-486**



FAC
Fluid-Air Components Ltd

PNEUFIT® PUSH-IN FITTINGS, METRIC

NORGREN

- Very compact units featuring retained collets and positive tube anchorage
- Silicone free O-ring seals
- Non-PTFE based thread sealant on all BSP taper threads
- Easy tube insertion for rapid assembly
- Positive tube anchorage
- For simple and quick assembly of pneumatic circuits
- Wide range of types available
- Reliable and corrosion resistant

Fluid: Compressed air

Body: Nickel plated brass **Washer (Banjo):** PA

Collet: Nickel plated brass **Thread Sealant:** Non-PTFE

O-Ring: VMQ free NBR **Tube Sizes:**


Warning: The push-in tube fittings in this section must not be used in vehicle air braking and ancillary systems

Tube Types: Positive tube anchorage

Warning: PA 11 or 12, PUR and other plasticised or unplasticised tubing which conforms to the tolerances specified in BS 5409, Part 1, 1976, light and normal dut , DIN 73378, DIN 74234, NFE 49-100

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
Vacuum – 18 bar unless otherwise stated
(dependant upon tubing specification



Straight Adaptors



BSPP & Metric

0038	OD mm	Thread
102250405	4	M5
102250418	4	1/8"
102250428	4	1/4"
102250605	6	M5
102250618	6	1/8"
102250628	6	1/4"
102250818	8	1/8"
102250828	8	1/4"
102250838	8	3/8"
102251018	10	1/8"
102251028	10	1/4"
102251038	10	3/8"
102251228	12	1/4"
102251238	12	3/8"



BSPT

0038	OD mm	Thread
101250418	4	1/8"
101250428	4	1/4"
101250618	6	1/8"
101250628	6	1/4"
101250818	8	1/8"
101250828	8	1/4"
101250838	8	3/8"
101251018	10	1/8"
101251028	10	1/4"
101251038	10	3/8"
101251228	12	1/4"
101251238	12	3/8"

Straight Stem Adaptors



BSPP

0038	OD mm	Thread
102150418	4	1/8"
102150618	6	1/8"
102150838	8	3/8"
102151028	10	1/4"
102151038	10	3/8"
102151248	12	3/8"



BSPT

0038	OD mm	Thread
101150418	4	1/8"
101150618	6	1/8"
101150628	6	1/4"
101150818	8	1/8"
101150828	8	1/4"
101151028	10	1/4"
101151038	10	3/8"
101151238	12	3/8"

Swivel Elbows



BSPT

0038	OD mm	Thread
101470418	4	1/8"
101470428	4	1/4"
101470618	6	1/8"
101470628	6	1/4"
101470638	6	3/8"
101470818	8	1/8"
101470828	8	1/4"
101470838	8	3/8"
101471018	10	1/8"
101471028	10	1/4"
101471038	10	3/8"
101471228	12	1/4"
101471238	12	3/8"

Elbow Connectors



Tube x Tube

0038	OD mm
100400400	4
100400600	6
100400800	8
100401000	10
100401200	12

Straight Connectors



Tube x Tube

0038	OD mm
100200400	4
100200600	6
100200800	8
100201000	10
100201200	12

Bulkhead Connectors



Tube x Tube

0038	OD mm
100290400	4
100290600	6
100290800	8
100291000	10
100291200	12

Tee Connectors



Tube x Tube

0038	OD mm
100600400	4
100600600	6
100600800	8
100601000	10
100601200	12

Fluid-Air Components Ltd

PNEUFIT® PUSH-IN FITTINGS, IMPERIAL

NORGREN

- For simple and quick assembly of pneumatic circuits
- Positive tube anchorage
- Wide range of types available
- Reliable and corrosion resistant

Medium: Compressed air

Collet and Body Manufactured from Bar:
Nickel plated brass to BS 2874: 1986 (CZ121)

Body Manufactured from Stamping:
Nickel plated brass to BS 2872: 1969 (CZ122)

Seal: Nitrile rubber

Tube Sizes: 1/8", 1/4", 3/8", 1/2" O/D

Warning:
The push-in tube fittings in this section must not be used in vehicle air braking and ancillary systems

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
Vacuum – 18 bar unless otherwise stated (dependant upon tubing specification

Straight Adaptors



BSPT

0038	OD	Thread
121250118	1/8"	1/8"
121250418	1/4"	1/8"
121250428	1/4"	1/4"
121250628	3/8"	1/4"
121250638	3/8"	3/8"

Straight Connectors



Tube x Tube

0038	OD
120200400	1/4"
120200600	3/8"

Bulkhead Connectors



Tube x Tube

0038	OD	Thread
120290400	1/4"	M12 x 1.0
120290600	3/8"	M20 x 1.5

Elbow Connectors



Tube x Tube

0038	OD
120400400	1/4"
120400600	3/8"

90º Swivel Elbow Adaptors



BSPT

0038	OD	Thread
121470418	1/4"	1/8"
121470428	1/4"	1/4"
121470628	3/8"	1/4"
121470638	3/8"	3/8"

Swivel Tee Adaptor



BSPT

0038	OD	Thread
121670418	1/4"	1/8"

Tee Connectors



Tube x Tube

0038	OD
120600300	3/16"
120600400	1/4"
120600600	3/8"

NORGREN

For **Olympian Plus Boxed Sets** see page **683**



FAC
Fluid-Air Components Ltd

NON-RETURN VALVES & FITTINGS

NORGREN

Non-return Valves

- Allow free flow in one direction only
- Simple reliable design
- Low weight
- Low cracking pressure
- High operating pressure

Medium:
Compressed air, filtered, lubricated and non-lubricated, vacuum
Body:
Anodised aluminium
Collet:
Nickel plated brass
Spring:
Stainless steel
Seals:
Nitrile rubber
Valve and Insert:
Aluminium

Working Temperature:
-20°C to +80°C

Mounting:
Line mounted, push-In connection
Tubing Types:
Nylon 11 or 12. Polyurethane, and other plasticised or unplasticised tubing which conforms to the tolerances specified in BS 5409, part 1, 1976, light and normal duty, DIN 73378, DIN 74234, NFE 49100

Working Pressure:
-0.9 to 16 bar (dependent upon operating specification of tubing



T50 Series, In-line Push-in

0038	OD mm	Cracking Pressure Bar
T50P0004	4	0.03
T50P0006	6	0.03
T50P0008	8	0.03
T50P0010	10	0.03
T50P0012	12	0.03
Tech Sheet 20749		

Blocking, Pressure Reducing & Pneumatic Sensor Fittings

- Very compact units
- Safer pneumatic systems
- Easy tube insertion for rapid assembly of pneumatic circuits
- BSP threads

Working Temperature:
0°C to +70°C

Operating Pressures:
Blocking Fitting:
Supply pressure: 1-10 bar

Pressure Reducing Fitting:
Primary pressure: 1-16 bar max.
Secondary pressure: 1-8 bar max.

Pressure Sensor Fitting:
Cylinder pressure (Pc): 10 bar max.
Sensor supply pressure: 3-10 bar

Tubing Types:
Nylon 11 or 12, polyurethane and other plasticised or unplasticised tubing which conforms to the tolerances specified in BS 5409, Part 1, 1976, light and normal duty, DIN 73378, DIN 74234, NFE 49-100

Cover (pilot thread): Brass
Lock rings: SUS
Main body: Brass
Case (female thread):
Zinc die-casting
Valve: SUS and NBR
Springs: SUS
Sealing: NBR

new product



Blocking Fitting, BSPP

0038	OD	Thread
102GA1818	1/8"	1/8"
102GA2828	1/4"	1/4"
102GA3838	3/8"	3/8"
102GA4848	1/2"	1/2"
Tech Sheet 71731		

Banjo body: Aluminium
Retaining ring: PA
Banjo bolt and valve:
Brass - zinc plated
Washer: NBR

new product



Pressure Reducing Fitting, BSPP

0038	OD	Thread
102GB1818	1/8"	1/8"
102GB2828	1/4"	1/4"
102GB3838	3/8"	3/8"
102GB4848	1/2"	1/2"
Tech Sheet 71732		

NORGREN



For **Norgren Excelon Plus** see pages **686-688**

Body: PA
Banjo bolt: nickel plated brass
Washer: NBR and PU



Pneumatic Sensor Fitting, BSPP

0038	OD	Thread
102GD0418	4	1/8"
102GD0428	4	1/4"
Tech Sheet 71733		

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


FOOD GRADE FITTINGS

Series F Push-in Fittings, Safe for Use in the Food Industry

Brass parts are chemically treated with phosphorus nickel-plating according to the NSF®/ ANSI 51 standard of the food programme. The seals are made of FDA-approved FKM/FPM. Fittings contain no technopolymer, solving the problem of incompatibility with detergents and other chemicals.

The fittings can be used up to +150°C, making them suitable for high temperature applications other industries. The threads are cylindrical and under-head o-rings provide a pneumatic seal. This avoids the need for sealants (e.g. Teflon®) which could release solid fragments during screwing and unscrewing that would contaminate the environment or the fluid. Our fittings can be screwed and unscrewed any number of times and still remain clean and pneumatically sealed.

This choice of materials and treatments make these fittings suitable for use in the chemical, pharmaceutical, medical and electronics industry.



1. Body: chemically nickel plated brass to NSF®/ ANSI 51 standards
2. Gripper: chemically nickel plated brass to NSF®/ ANSI 51 standards
3. Fitting seal: FKM/FPM
4. Port seal: FKM/FPM

Temperature Range:
-20°C to +150°C (-4°F to 302°F)

Pressure:
-0.99 to 16 bar (-0.099 to 1.6 MPa)



Technical Features

- Threaded ports: M5, G1/8", G1/4", G3/8", G1/2"
- Pipe diameter: 4, 6, 8 and 10mm
- Recommended pipe: Rilsan PA 11, nylon 6, polyamide 12, polypropylene
- Under-head O-ring can be screwed and unscrewed any number of times; no fragments of Teflon® or sealant will contaminate the fluid
- Corrosion proof: chemical nickel-plating + FKM/FPM, compatible with numerous substances
- No plastic parts, so no risk of incompatibility

Male Stud



BSP Parallel x Tube

9186	Tube OD mm	Thread BSPP
2F01001	4	M5
2F01002	4	G1/8"
2F01003	4	G1/4"
2F01000	6	M5
2F01007	6	G1/8"
2F01008	6	G1/4"
2F01009	8	G1/8"
2F01010	8	G1/4"
2F01011	8	G3/8"
2F01012	10	G1/4"
2F01013	10	G3/8"
2F01022	10	G1/2"

Male Stud



BSP Tapered x Tube

9186	Tube OD mm	Thread BSPT
2F01C02	4	R1/8"
2F01C07	6	R1/8"
2F01C08	6	R1/4"
2F01C09	8	R1/8"
2F01C10	8	R1/4"
2F01C11	8	R3/8"
2F01C13	10	R1/4"
2F01C14	10	R3/8"

Straight Connector



Tube x Tube

9186	Tube OD mm	Bulkhead Thread
2F03001	4	M13 x 1
2F03003	6	M15 x 1
2F03004	8	M17 x 1
2F03005	10	M20 x 1

Equal Tee



Tube x Tube

9186	Tube OD mm
2F05001	4
2F05003	6
2F05004	8
2F05005	10

Fluid-Air Components Ltd

FOOD GRADE FITTINGS

Male Stud Swivel Elbow



BSP Parallel x Tube

9186	Thread BSPP	Tube OD mm
2F31001	M5	4
2F31002	G1/8"	4
2F31003	G1/4"	4
2F31007	M5	6
2F31008	G1/8"	6
2F31009	G1/4"	6
2F31010	G1/8"	8
2F31011	G1/4"	8
2F31012	G3/8"	8
2F31013	G1/4"	10
2F31014	G3/8"	10
2F31015	G1/2"	10

Bulkhead Connector



Tube x Tube

9186	Tube OD mm	Bulkhead Thread
2F11001	4	M13 x 1
2F11003	6	M15 x 1
2F11004	8	M17 x 1
2F11005	10	M20 x 1

Equal Elbow



Tube x Tube

9186	Tube OD mm
2F04001	4
2F04003	6
2F04004	8
2F04005	10

Male Stud Swivel Elbow



BSP Parallel x Tube

9186	Thread BSPT	Tube OD mm
2F31C02	R1/8"	4
2F31C03	R1/4"	4
2F31C08	R1/8"	6
2F31C09	R1/4"	6
2F31C10	R1/8"	8
2F31C11	R1/4"	8
2F31C12	R3/8"	8
2F31C13	R1/4"	10
2F31C14	R3/8"	10

Male Stem Adaptor



BSP Parallel x Tube

9186	Thread BSPP	Tube OD mm
2F06001	M5	4
2F06002	G1/8"	4
2F06003	G1/4"	4
2F06000	M5	6
2F06007	G1/8"	6
2F06008	G1/4"	6
2F06009	G1/8"	8
2F06010	G1/4"	8
2F06011	G3/8"	8
2F06012	G1/4"	10
2F06013	G1/4"	10

Male Stud Elbow



BSP Parallel x Tube

9186	Thread BSPT	Tube OD mm
2F39C02	R1/8"	4
2F39C08	R1/8"	6
2F39C09	R1/4"	6
2F39C10	R1/8"	8
2F39C11	R1/4"	8
2F39C12	R3/8"	8
2F39C13	R1/4"	10

Male Swivel Branch Tee



BSP Parallel x Tube

9186	Thread BSPP	Tube OD mm
2F32002	G1/8"	4
2F32008	G1/8"	6
2F32009	G1/4"	6
2F32010	G1/8"	8
2F32011	G1/4"	8
2F32012	G3/8"	8
2F32013	G1/4"	10
2F32014	G3/8"	10

Female Stud



BSP Parallel x Tube

9186	Thread BSPP	Tube OD mm
2F02001	G1/8"	4
2F02005	G1/8"	6
2F02006	G1/4"	6
2F02007	G1/8"	8
2F02008	G1/4"	8
2F02011	G1/4"	10


Fluid-Air Components Ltd

NICKEL PLATED BRASS & TECHNOPOLYMER

Push-in fittings by Metal Work are the best elements for connecting pipes and actuators.

Quick and easy to use, the Metal Work push-in fitting can be re-used thousands of times without affecting the pneumatic and mechanical seal in any way. It comes in various configurations and guarantees a virtually unlimited, highly flexible use. The clamping spring with its special shape grips the pipe without scratching or deforming it, which facilitates release.

In the fittings, the release bushing has patented screwdriver slots to facilitate release in applications not accessible to the fingers.




Technical Data

Threaded coupling	M3 - M5 - M7 - 1/8'' - 1/4'' - 3/8'' - 1/2''
Diameter	Ø 3mm - Ø 3.17mm - Ø 4mm - Ø 5mm - Ø 6mm - Ø 8mm - Ø 10mm - Ø 12mm - Ø 14mm
Temperature range for brass fittings	– 20 °C to + 80 °C
	– 4 °F to 176 °F
Temperature range for technopolymer fittings	– 20 °C to + 60 °C
	– 4 °F to 140 °F
Pressure range for brass fittings	– 0.99 bar ... 16 bar / – 0.099 MPa ... 1.6 MPa
Pressure range for technopolymer fittings	– 0.99 bar ... 12 bar / – 0.099 MPa ... 1.2 MPa
Recommended pipe	Rilsan PA 11 - Nylon 6 - Polyamide 12 - Polypropylene
Fluid	Vacuum - Compressed air

Components

1. Ring or release bushing: technopolymer
2. Locking bushing: brass or technopolymer
3. Body: brass or technopolymer
4. Clamping spring: stainless steel (for pipes Ø 3 and Ø 3.17 and R31 Ø 5 and R32 Ø 5: brass gripper)
5. Spring supporting ring: technopolymer
6. Seal: NBR



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

METRIC PUSH-IN FITTINGS, NICKEL PLATED BRASS

Male Stud



BSP Parallel x Tube

9150	Thread BSPP	Tube OD mm
2L01001	M5	4
2L01002	G1/8"	4
2L01003	G1/4"	4
2001005	G1/8"	5
2001006	G1/4"	5
2L01000	M5	6
2L01007	G1/8"	6
2L01008	G1/4"	6
2L01009	G1/8"	8
2L01010	G1/4"	8
2L01011	G3/8"	8
2L01012	G1/4"	10
2L01013	G3/8"	10
2001019	G1/4"	12
2001014	G3/8"	12
2001015	G1/2"	12
2001016	G3/8"	14
2001017	G1/2"	14
2L01018	G1/2"	10

Female Stud



BSP Parallel x Tube

9150	Thread BSPP	Tube OD mm
2L02001	G1/8"	4
2L02002	G1/4"	4
2002003	G1/8"	5
2002004	G1/4"	5
2L02005	G1/8"	6
2L02006	G1/4"	6
2L02007	G1/8"	8
2L02008	G1/4"	8
2L02009	G1/4"	10
2L02010	G3/8"	10
2L02011	G3/8"	12
2L02012	G1/2"	12

Male Stud



BSP Tapered x Tube

9150	Thread BSPT	Tube OD mm
2L01C02	R1/8"	4
2L01C07	R1/8"	6
2L01C08	R1/4"	6
2L01C09	R1/8"	8
2L01C10	R1/4"	8
2L01C11	R3/8"	8

Straight Connector



Tube x Tube

9150	Tube OD mm
2L03001	4
2003002	5
2L03003	6
2L03004	8
2L03005	10
2003006	12
2003007	14

Straight Connector, Reducing



Tube x Tube

9150	Tube OD mm	
2L03301	4	6
2L03302	4	8
2L03303	6	8
2L03304	6	10
2L03305	8	10
2L03306	6	12
2L03307	8	12
2L03308	10	12

Bulkhead Connector



Tube x Tube

9150	Bulkhead Thread	Tube OD mm
2L11001	M11	4
2011002	M14	5
2L11003	M13	6
2L11004	M15	8
2L11005	M17	10
2011006	M20	12
2011007	M24	14

Unequal Bulkhead Connector



Tube x Tube

9150	Tube OD mm	
2L11301	4	6
2L11302	4	8
2L11303	6	8
2L11304	6	10
2L11305	8	10
2L11306	6	12
2L11307	8	12
2L11308	10	12

Equal Elbow



Tube x Tube

9150	Tube OD mm
2L04001	4
2004002	5
2L04003	6
2L04004	8
2L04005	10
2004006	12
2004007	14

Equal Tee



Tube x Tube

9150	Tube OD mm
2L05001	4
2005002	5
2L05003	6
2L05004	8
2L05005	10
2005006	12
2005007	14

Equal Cross



Tube x Tube

9150	Tube OD mm
2L40003	6
2L40004	8

Fluid-Air Components Ltd

METRIC PUSH-IN FITTINGS, NICKEL PLATED BRASS

Male Stud Swivel Elbow



BSP Parallel x Tube

9150	Thread BSPP	Tube OD mm
2L31001	M5	4
2L31002	G1/8"	4
2L31003	G1/4"	4
2031004	M5	5
2031005	G1/8"	5
2031006	G1/4"	5
2L31007	M5	6
2L31008	G1/8"	6
2L31009	G1/4"	6
2L31010	G1/8"	8
2L31011	G1/4"	8
2L31012	G3/8"	8
2L31013	G1/4"	10
2L31014	G3/8"	10
2031016	G1/4"	12
2031017	G3/8"	12
2031018	G1/2"	12
2031019	G1/2"	14

Male Rotary Elbow



BSP Tapered x Tube

9150	Thread BSPT	Tube OD mm
2L31C02	R1/8"	4
2L31C03	R1/4"	4
2L31C08	R1/8"	6
2L31C09	R1/4"	6
2L31C10	R1/8"	8
2L31C11	R1/4"	8
2L31C12	R3/8"	8
2L31C13	R1/4"	10
2L31C14	R3/8"	10
2031C15	R3/8"	12
2031C16	R1/2"	12

Male Stud Elbow



BSP Tapered x Tube

9150	Thread BSPT	Tube OD mm
2L39C02	R1/8"	4
2L39C08	R1/8"	6
2L39C09	R1/4"	6
2L39C10	R1/8"	8
2L39C11	R1/4"	8
2L39C13	R1/4"	10

Male Stud Swivel Tee



BSP Parallel & Tube

9150	Thread BSPP	Tube OD mm
2L32002	G1/8"	4
2L32003	G1/4"	4
2032005	G1/8"	5
2L32008	G1/8"	6
2L32009	G1/4"	6
2L32010	G1/8"	8
2L32011	G1/4"	8
2L32012	G3/8"	8
2L32013	G1/4"	10
2L32014	G3/8"	10
2032017	G3/8"	12
2032018	G1/2"	12
2032019	G1/2"	14

Extension Stem



Stem x Stem

9150	Stem OD mm
2007001	4
2007002	5
2007003	6
2L07004	8
2007005	10
2007006	12
2007007	14

Stem Reducer



Stem x Tube

9150	Stem OD mm	Tube OD mm
2008001	5	4
2L08002	6	4
2008003	6	5
2L08004	8	4
2008005	8	5
2L08006	8	6
2L08007	10	6
2L08008	10	8
2008009	12	4
2008010	12	6
2008011	12	8
2008015	12	10
2008014	14	8
2008017	14	10
2008018	14	12

Male Stem Adaptor



BSP Parallel x Tube

9150	Thread BSPP	Stem OD mm
2006001	M5	4
2006002	G1/8"	4
2006003	G1/4"	4
2006004	M5	5
2006005	G1/8"	5
2006006	G1/4"	5
2006000	M5	6
2006007	G1/8"	6
2006008	G1/4"	6
2006009	G1/8"	8
2006010	G1/4"	8
2006011	G3/8"	8
2006012	G1/4"	10
2006013	G3/8"	10
2006019	G1/4"	12
2006014	G3/8"	12
2006015	G1/2"	12
2006016	G3/8"	14
2006017	G1/2"	14

Fluid-Air Components Ltd

SUPER-RAPID PUSH-IN FITTINGS

CAMOZZI Automation

Material:
Body nickel plated brass. O-ring NBR seals PTFE/NBR/PA

Working Pressure:
0.8 to 16 bar

Male Stud Couplings



Sprint Parallel Male Stud, BSPP

0158	OD mm	Thread
S6510 4 1/8	4	1/8"
S6510 4 1/4	4	1/4"
S6510 5 1/8	5	1/8"
S6510 5 1/4	5	1/4"
S6510 6 1/8	6	1/8"
S6510 6 1/4	6	1/4"
S6510 8 1/8	8	1/8"
S6510 8 1/4	8	1/4"
S6510 8 3/8	8	3/8"
S6510 10 1/4	10	1/4"
S6510 10 3/8	10	3/8"
S6510 10 1/2	10	1/2"
S6510 12 1/4	12	1/4"
S6510 12 3/8	12	3/8"
S6510 12 1/2	12	1/2"
S6510 14 3/8	14	3/8"
S6510 14 1/2	14	1/2"
Tech Sheet 1861		



Parallel Male Stud, BSPP & Metric with O-Ring

0158	OD mm	Thread
6512 4 M5	4	M5
6512 4 M6	4	M6
6512 4 1/8	4	1/8"
6512 4 1/4	4	1/4"
6512 5 M5	5	M5
6512 6 M5	6	M5
6512 6 1/8	6	1/8"
6512 6 1/4	6	1/4"
6512 8 1/8	8	1/8"
6512 8 1/4	8	1/4"
6512 8 3/8	8	3/8"
6512 10 1/4	10	1/4"
6512 10 3/8	10	3/8"
6512 12 1/4	12	1/4"
6512 12 3/8	12	3/8"
Tech Sheet 1861		

Female Stud Couplings



Female Stud, BSPP & Metric

0158	OD mm	Thread
6463 4 M5	4	M5
6463 4 1/8	4	1/8"
6463 5 1/8	5	1/8"
6463 6 1/8	6	1/8"
6463 6 1/4	6	1/4"
6463 8 1/8	8	1/8"
6463 8 1/4	8	1/4"
6463 10 1/4	10	1/4"
Tech Sheet 1862		

Elbows



Sprint Taper Male Elbow, BSPT

0158	OD mm	Thread
S6500 4 1/8	4	1/8"
S6500 4 1/4	4	1/4"
S6500 5 1/8	5	1/8"
S6500 5 1/4	5	1/4"
S6500 6 1/8	6	1/8"
S6500 6 1/4	6	1/4"
S6500 8 1/8	8	1/8"
S6500 8 1/4	8	1/4"
S6500 8 3/8	8	3/8"
S6500 10 1/4	10	1/4"
S6500 10 3/8	10	3/8"
S6500 12 1/4	12	1/4"
S6500 12 3/8	12	3/8"
Tech Sheet 1863		



Sprint Swivel Parallel Male Stud, BSPP

0158	OD mm	Thread
S6520 4 1/8	4	1/8"
S6520 4 1/4	4	1/4"
S6520 5 1/8	5	1/8"
S6520 5 1/4	5	1/4"
S6520 6 1/8	6	1/8"
S6520 6 1/4	6	1/4"
S6520 8 1/8	8	1/8"
S6520 8 1/4	8	1/4"
S6520 8 3/8	8	3/8"
S6520 10 1/4	10	1/4"
S6520 10 3/8	10	3/8"
S6520 10 1/2	10	1/2"
S6520 12 1/4	12	1/4"
S6520 12 3/8	12	3/8"
S6520 12 1/2	12	1/2"
S6520 14 3/8	14	3/8"
S6520 14 1/2	14	1/2"
Tech Sheet 1863		



Swivel Parallel Male Elbow, BSPP & Metric with O-Ring

0158	OD mm	Thread
6522 4 M5	4	M5
6522 4 1/8	4	1/8"
6522 4 1/4	4	1/4"
6522 5 M5	5	M5
6522 6 M5	6	M5
6522 6 1/8	6	1/8"
6522 6 1/4	6	1/4"
6522 8 1/8	8	1/8"
6522 8 1/4	8	1/4"
6522 8 3/8	8	3/8"
6522 10 1/4	10	1/4"
6522 10 3/8	10	3/8"
6522 12 1/4	12	1/4"
6522 12 3/8	12	3/8"
Tech Sheet 1863		

Fluid-Air Components Ltd

SUPER-RAPID PUSH-IN FITTINGS

CAMOZZI Automation

Material:
Body nickel plated brass. O-ring NBR seals PTFE/NBR/PA

Working Pressure:
0.8 to 16 bar

Tees



Sprint Swivel Branch Tee Parallel, BSPP

0158	OD mm	Thread
S6430 4 1/8	4	1/8"
S6430 5 1/8	5	1/8"
S6430 5 1/4	5	1/4"
S6430 6 1/8	6	1/8"
S6430 6 1/4	6	1/4"
S6430 8 1/8	8	1/8"
S6430 8 1/4	8	1/4"
S6430 8 3/8	8	3/8"
S6430 10 1/4	10	1/4"
S6430 10 3/8	10	3/8"
S6430 12 1/4	12	1/4"
S6430 12 3/8	12	3/8"
S6430 12 1/2	12	1/2"
S6430 14 1/2	14	1/2"
Tech Sheet 1864		



Swivel Branch Tee Parallel, BSPP & Metric with O-Ring

0158	OD mm	Thread
6432 4 M5	4	M5
6432 4 1/8	4	1/8"
6432 5 M5	5	M5
6432 6 1/8	6	1/8"
6432 6 1/4	6	1/4"
6432 8 1/8	8	1/8"
6432 8 1/4	8	1/4"
6432 8 3/8	8	3/8"
6432 10 1/4	10	1/4"
6432 10 3/8	10	3/8"
6432 12 1/4	12	1/4"
6432 12 3/8	12	3/8"
Tech Sheet 1864		



Sprint Swivel Run Tee Parallel, BSPP

0158	OD mm	Thread
S6440 4 1/8	4	1/8"
S6440 5 1/8	5	1/8"
S6440 6 1/8	6	1/8"
S6440 6 1/4	6	1/4"
S6440 8 1/8	8	1/8"
S6440 8 1/4	8	1/4"
S6440 8 3/8	8	3/8"
S6440 10 1/4	10	1/4"
S6440 10 3/8	10	3/8"
S6440 12 3/8	12	3/8"
S6440 14 1/2	14	1/2"
Tech Sheet 1864		



Swivel Run Tee Parallel, BSPP & Metric with O-Ring

0158	OD mm	Thread
6442 4 M5	4	M5
6442 4 1/8	4	1/8"
6442 5 M5	5	M5
6442 6 1/8	6	1/8"
6442 6 1/4	6	1/4"
6442 8 1/8	8	1/8"
6442 8 1/4	8	1/4"
6442 8 3/8	8	3/8"
6442 10 1/4	10	1/4"
6442 10 3/8	10	3/8"
6442 12 1/4	12	1/4"
6442 12 3/8	12	3/8"
Tech Sheet 1864		

Banjo Bolts



Single Banjo, BSPP & Metric with O-Ring

0158	OD mm	Thread
6622 4 M5	4	M5
6622 4 1/8	4	1/8"
6622 6 1/8	6	1/8"
6622 6 1/4	6	1/4"
6622 8 1/8	8	1/8"
6622 8 1/4	8	1/4"
6622 10 1/4	10	1/4"
Tech Sheet 20121		



Double Banjo, BSPP with O-Ring

0158	OD mm	Thread
6632 4 1/8	4	1/8"
6632 6 1/8	6	1/8"
6632 8 1/8	8	1/8"
6632 8 1/4	8	1/4"
6632 10 1/4	10	1/4"
Tech Sheet 1866		

Stem Adaptors



Parallel Stem Adaptor, BSPP x Metric

0158	Stem OD mm	Thread
6811 4 M5	4	M5
6811 4 1/8	4	1/8"
6811 5 1/8	5	1/8"
6811 5 1/4	5	1/4"
6811 6 1/8	6	1/8"
6811 6 1/4	6	1/4"
6811 8 1/8	8	1/8"
6811 8 1/4	8	1/4"
6811 10 1/4	10	1/4"
6811 10 3/8	10	3/8"
6811 12 3/8	12	3/8"
6811 14 1/2	14	1/2"
Tech Sheet 20122		

FAC Fluid-Air Components Ltd

SUPER-RAPID PUSH-IN FITTINGS

Material:
Body nickel plated brass. O-ring NBR seals PTFE/NBR/PA

Working Pressure:
0.8 to 16 bar

Tube Connectors



Swivel Y Connector, BSPP & Metric

0158	OD mm	Thread
6451 4 M5	4	M5
S6450 4 1/8	4	1/8"
S6450 6 1/8	6	1/8"
S6450 8 1/8	8	1/8"
S6450 8 1/4	8	1/4"



Equal Y Tube Connector

0158	OD mm
6560 4	4
6560 6	6
6560 8	8
6560 10	10
Tech Sheet 1869	



Straight Tube Connector

0158	OD mm
6580 4	4
6580 5	5
6580 6	6
6580 8	8
6580 10	10
6580 12	12
6580 14	14
Tech Sheet 1867	



Equal Bulkhead Tube Connector

0158	OD mm	Thread
6590 4	4	M10 x 1
6590 5	5	M12 x 1
6590 6	6	M14 x 1
6590 8	8	M16 x 1
6590 10	10	M18 x 1
6590 12	12	M20 x 1
6590 14	14	M22 x 1
Tech Sheet 20123		



Equal Elbow Tube Connector

0158	OD mm
6550 4	4
6550 5	5
6550 6	6
6550 8	8
6550 10	10
6550 12	12
6550 14	14
Tech Sheet 20124	



Equal Tee Tube Connector

0158	OD mm
6540 4	4
6540 5	5
6540 6	6
6540 8	8
6540 10	10
6540 12	12
6540 14	14
Tech Sheet 20125	



Equal Cross Tube Connector

0158	OD mm
6600 4	4
6600 5	5
6600 6	6
6600 8	8
6600 10	10
6600 12	12
Tech Sheet 20126	



Tube/Stem Reducer

0158	Tube OD mm	Stem OD mm
6800 4 5	4	5
6800 4 6	4	6
6800 4 8	4	8
6800 5 6	5	6
6800 5 8	5	8
6800 6 8	6	8
6800 6 10	6	10
6800 6 12	6	12
6800 8 10	8	10
6800 8 12	8	12
6800 10 12	10	12
6800 10 14	10	14
6800 12 14	12	14
Tech Sheet 1870		



Tube to Stem Elbow

0158	OD mm	Stem OD mm
6555 4 4	4	4
6555 6 6	6	6
6555 8 8	8	8
6555 10 10	10	10
Tech Sheet 20127		

Press Fit Cartridges



Tube

0158	OD mm
6700 4	4
6700 5	5
6700 6	6
Tech Sheet 20128	

Blanking Caps & Plugs



Tube Blanking Cap

0158	OD mm
6750 4	4
6750 6	6
6750 8	8
6750 12	12
Tech Sheet 20129	



Plastic Blanking Plug

0158	OD mm
6900 4MM	4
6900 5MM	5
6900 6MM	6
6900 8MM	8
6900 10MM	10
6900 12MM	12
6900 14MM	14

Fluid-Air Components Ltd

SERIES 8000 SUPER-RAPID PUSH-IN FITTINGS

CAMOZZI Automation

Series 8000 has a patented additional seal that provides a double tight seal on the tube, ensuring a highly reliable connection and avoiding any possible leakage. Connection and disconnection of the tube can be repeated several times without the use of proper tools and without compromising the performance of the fitting or the sealing on the tube

Material:
Body and Gripper: Nickel plated brass
Seals: Nitrile

Working Pressure:
-0.9 to 16 bar

Male Studs



BSPP

0158	OD mm	Thread
8512 4-1/8	4	1/8"
8512 6-1/8	6	1/8"
8512 6-1/4	6	1/4"
8512 8-1/8	8	1/8"
8512 8-1/4	8	1/4"
8512 10-1/4	10	1/4"
8512 10-3/8	10	3/8"
8512 12-3/8	12	3/8"
8512 12-1/2	12	1/2"
Tech Sheet 68276		

Male Stud Swivel Elbows



BSPP

0158	OD mm	Thread
8522 4-1/8	4	1/8"
8522 6-1/8	6	1/8"
8522 6-1/4	6	1/4"
8522 8-1/8	8	1/8"
8522 8-1/4	8	1/4"
8522 10-1/4	10	1/4"
8522 10-3/8	10	3/8"
8522 12-3/8	12	3/8"
8522 12-1/2	12	1/2"
Tech Sheet 68276		

Male Stud Swivel Tees



BSPP

0158	OD mm	Thread
8432 4-1/8	4	1/8"
8432 6-1/8	6	1/8"
8432 8-1/8	8	1/8"
8432 8-1/4	8	1/4"
Tech Sheet 68276		

Tube x Tube Connectors



Equal Straights

0158	OD mm
8580 4	4
8580 6	6
8580 8	8
Tech Sheet 68276	



Equal Tees

0158	OD mm
8540 4	4
8540 6	6
8540 8	8
Tech Sheet 68276	



Equal Elbows

0158	OD mm
8550 4	4
8550 6	6
8550 8	8
Tech Sheet 68276	

Fluid-Air Components Ltd

CAMOZZI
Automation

Series H8000 fittings are designed to be used in particularly dirty and dusty environments.
The patented system, with double tightening on the tube, guarantees a highly reliable connection and avoids any risk of leakage.

Features:
- Protection against dust and debris
- Silicone free
- Suitable for vacuum and metal tubes

Material:
Body and Gripper: Nickel plated brass
Seals: Viton

Working Pressure:
-0.9 to +60 bar



BSPP

0158	OD mm	Thread
H8512 4-1/8-V	4	1/8"
H8512 6-1/4-V	6	1/4"
H8512 6-1/8-V	6	1/8"
H8512 8-1/4-V	8	1/4"
H8512 8-1/8-V	8	1/8"
H8512 8-3/8-V	8	3/8"
H8512 10-1/2-V	10	1/2"
H8512 10-1/4-V	10	1/4"
H8512 10-1/8-V	10	1/8"
H8512 10-3/8-V	10	3/8"
H8512 12-1/2-V	12	1/2"
H8512 12-1/4-V	12	1/4"
H8512 12-3/8-V	12	3/8"
H8512 14-1/2-V	14	1/2"
H8512 14-3/8-V	14	3/8"
H8512 16-1/2-V	16	1/2"
H8512 16-3/8-V	16	3/8"

Tech Sheet 68275

Male Stud Swivel Elbows



BSPP

0158	OD mm	Thread
H8522 4-1/8-V	4	1/8"
H8522 6-1/4 -V	6	1/4"
H8522 6-1/8-V	6	1/8"
H8522 8-1/8-V	8	1/8"
H8522 8-1/4-V	8	1/4"
H8522 8-3/8-V	8	3/8"
H8522 10-1/2-V	10	1/2"
H8522 10-1/4-V	10	1/4"
H8522 10-1/8-V	10	1/8"
H8522 10-3/8-V	10	3/8"
H8522 12-1/2-V	12	1/2"
H8522 12-1/4-V	12	1/4"
H8522 12-3/8-V	12	3/8"
H8522 14-1/2-V	14	1/2"
H8522 14-3/8-V	14	3/8"

Tech Sheet 68275

Tube x Tube Connectors



Equal Tees

0158	OD mm
H8540 4-V	4
H8540 6-V	6
H8540 8-V	8
H8540 10-V	10
H8540 12-V	12
H8540 14-V	14

Tech Sheet 68275



Equal Elbows

0158	OD mm
H8550 4-V	4
H8550 6-V	6
H8550 8-V	8
H8550 10-V	10
H8550 12-V	12
H8550 14-V	14

Tech Sheet 68275



Equal Straights

0158	OD mm
H8580 4-V	10
H8580 6-V	6
H8580 8-V	8
H8580 10-V	10
H8580 12-V	12
H8580 14-V	14

Tech Sheet 68275

APPLICATION FIELDS

- WELDING
- CUTTING
- CEMENT PLANT
- ROADS AND MOTORWAYS
- PAINTING







APPLICATION FIELDS
› WELDING
› CUTTING
› CEMENT PLANT
› OFF HIGHWAY
› PAINTING

› CUTTING
› CEMENT PLANT
› OFF HIGHWAY

FAC
Fluid-Air Components Ltd

FT PRO

stainless steel

All seals have FDA Certification

STAINLESS STEEL PUSH-IN FITTINGS

One Touch



Features:

- Convenient One Touch fittings provide instant connections
- Light manual pressure on the collet ring is all that is required to instantly disconnect each tube, no special tool is required
- Full stainless steel construction prevents corrosion and increases compatibility with more aggressive medias and environments

Temperature Range: -20°C to +200°C

Working Pressure 10 bar*

*Dependent upon tubing specification.

Construction:

Body & Collet:	316 stainless steel
O-Ring:	Viton (FDA certified)
Tube to Connect:	PU, nylon, PTFE
Media:	Compressed air, steam, water, other compatible liquids

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

ONE TOUCH ALL STAINLESS STEEL PUSH-IN FITTINGS

stainless steel FT PRO

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 10 bar
Negative Pressure: 750mm Hg (10Torr)

Material:
Body and Collet: 316 stainless steel
O-Ring: Viton

Tube to Connect: PU, Nylon and PTFE
Media: Compressed air, steam water and other compatible liquids

Male Studs



Male Thread, BSPP

0386	OD mm	Thread
SSPC4-01	4	1/8"
SSPC6-01	6	1/8"
SSPC6-02	6	1/4"
SSPC8-01	8	1/8"
SSPC8-02	8	1/4"
SSPC10-02	10	1/4"
SSPC10-03	10	3/8"
SSPC12-04	12	1/2"
Tech Sheet 10257		



Male Thread, BSPP

0386	OD mm	Thread
SSPC4-G01	4	1/8"
SSPC6-G01	6	1/8"
SSPC6-G02	6	1/4"
SSPC8-G01	8	1/8"
SSPC8-G02	8	1/4"
SSPC10-G02	10	1/4"
SSPC10-G03	10	3/8"
SSPC12-G04	12	1/2"
Tech Sheet 10257		

Female Studs



Female Thread, BSPP

0386	OD mm	Thread
SSPCF4-G01	4	1/8"
SSPCF6-G01	6	1/8"
SSPCF6-G02	6	1/4"
SSPCF8-G01	8	1/8"
SSPCF8-G02	8	1/4"
SSPCF10-G02	10	1/4"
SSPCF10-G03	10	3/8"
SSPCF12-G03	12	3/8"
SSPCF12-G04	12	1/2"
Tech Sheet 10257		

Male Stud Swivel Elbows



Male Thread, BSPP

0386	OD mm	Thread
SSPL4-01	4	1/8"
SSPL6-01	6	1/8"
SSPL6-02	6	1/4"
SSPL8-01	8	1/8"
SSPL8-02	8	1/4"
SSPL10-02	10	1/4"
SSPL10-03	10	3/8"
SSPL12-04	12	1/2"
Tech Sheet 10257		



Male Thread, BSPP

0386	OD mm	Thread
SSPL4-G01	4	1/8"
SSPL6-G01	6	1/8"
SSPL6-G02	6	1/4"
SSPL8-G01	8	1/8"
SSPL8-G02	8	1/4"
SSPL10-G02	10	1/4"
SSPL10-G03	10	3/8"
SSPL12-G04	12	1/2"
Tech Sheet 10257		

Female Stud Elbows



Female Thread, BSPP

0386	OD mm	Thread
SSPLF4-G01	4	1/8"
SSPLF6-G01	6	1/8"
SSPLF6-G02	6	1/4"
SSPLF8-G01	8	1/8"
SSPLF8-G02	8	1/4"
SSPLF10-G02	10	1/4"
SSPLF10-G03	10	3/8"
SSPLF12-G03	12	3/8"
SSPLF12-G04	12	1/2"
Tech Sheet 10257		

Male Stud Swivel Tees



Branch Male Thread, BSPP

0386	OD mm	Thread
SSPB4-G01	4	1/8"
SSPB6-G01	6	1/8"
SSPB6-G02	6	1/4"
SSPB8-G01	8	1/8"
SSPB8-G02	8	1/4"
SSPB10-G02	10	1/4"
SSPB10-G03	10	3/8"
SSPB12-G03	12	3/8"
SSPB12-G04	12	1/2"
Tech Sheet 10257		

Speed Control Valves



Male Thread, BSPP

0386	OD mm	Thread
SSNSE4-G01	4	1/8"
SSNSE6-G01	6	1/8"
SSNSE6-G02	6	1/4"
SSNSE8-G01	8	1/8"
SSNSE8-G02	8	1/4"
SSNSE8-G03	8	3/8"
SSNSE10-G02	10	1/4"
SSNSE10-G03	10	3/8"
SSNSE10-G04	10	1/2"
SSNSE12-G04	12	1/2"
Tech Sheet 10257		



All seals have FDA Certification

ONE TOUCH ALL STAINLESS STEEL PUSH-IN FITTINGS

stainless steel FTPRO

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 10 bar
Negative Pressure: 750mm Hg (10Torr)

Material:
Body and Collet: 316 stainless steel
O-Ring: Viton

Tube to Connect: PU, Nylon and PTFE
Media: Compressed air, steam water and other compatible liquids

Tube x Tube Connectors



Equal Straights

0386	OD mm
SSPUC-4	4
SSPUC-6	6
SSPUC-8	8
SSPUC-10	10
SSPUC-12	12
Tech Sheet 10257	



Unequal Straights

0386	OD mm	OD mm
SSPG6-4	6	4
SSPG8-4	8	4
SSPG8-6	8	6
SSPG10-6	10	6
SSPG10-8	10	8
SSPG12-8	12	8
SSPG12-10	12	10
Tech Sheet 10257		



Equal Elbows

0386	OD mm
SSPUL-4	4
SSPUL-6	6
SSPUL-8	8
SSPUL-10	10
SSPUL-12	12
Tech Sheet 10257	



Equal Tees

0386	OD mm
SSPUT-4	4
SSPUT-6	6
SSPUT-8	8
SSPUT-10	10
SSPUT-12	12
Tech Sheet 10257	



Equal Bulkheads

0386	OD mm
SSPM-4	4
SSPM-6	6
SSPM-8	8
SSPM-10	10
SSPM-12	12
Tech Sheet 10257	



Equal Ys

0386	OD mm
SSPY-4	4
SSPY-6	6
SSPY-8	8
SSPY-10	10
SSPY-12	12
Tech Sheet 10257	

Stem Connectors



Tube x Stem Reducers

0386	OD mm	OD mm
SSPGJ6-4	6	4
SSPGJ8-4	8	4
SSPGJ8-6	8	6
SSPGJ10-6	10	6
SSPGJ10-8	10	8
SSPGJ12-8	12	8
SSPGJ12-10	12	10
Tech Sheet 10257		

Plugs



Tube

0386	OD mm
SSPP-4	4
SSPP-6	6
SSPP-8	8
SSPP-10	10
SSPP-12	12
Tech Sheet 10257	

All seals have FDA Certification

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL PUSH-IN FITTINGS

stainless steel

AIGNEP

Working Temperature: -15°C to +190°C

Maximum Working Pressure: -0.99 bar to 20 bar

This series is fully made of stainless steel AISI 316L and developed to be used with aggressive fluids and food applications. Also ideal for use in salty environments and in machines that need frequent washing with aggressive detergents. Certified NSF 169 and conformed to NSF 61 & NSF 372 standards. All parallel threads have a Food FKM seal as standard.

Male Studs



Male Thread, BSPT

0006	OD mm	Thread
60000-4-1/8	4	1/8"
60000-4-1/4	4	1/4"
60000-6-1/8	6	1/8"
60000-6-1/4	6	1/4"
60000-8-1/8	8	1/8"
60000-8-1/4	8	1/4"
60000-10-1/4	10	1/4"
60000-10-3/8	10	3/8"
60000-12-3/8	12	3/8"
60000-12-1/2	12	1/2"
Tech Sheet 1378		



Male Thread, Metric & BSPP

0006	OD mm	Thread
60020-4-M5	4	M5
60020-4-1/8	4	1/8"
60020-4-1/4	4	1/4"
60020-6-M5	6	M5
60020-6-1/8	6	1/8"
60020-6-1/4	6	1/4"
60020-8-1/8	8	1/8"
60020-8-1/4	8	1/4"
60020-10-1/4	10	1/4"
60020-10-3/8	10	3/8"
60020-10-1/2	10	1/2"
60020-12-3/8	12	3/8"
60020-12-1/2	12	1/2"
60020-14-1/2	14	1/2"
Tech Sheet 1378		

Male Stud Swivel Elbows



Male Thread, BSPT

0006	OD mm	Thread
60110X-4-18	4	1/8"
60110X-4-14	4	1/4"
60110X-6-18	6	1/8"
60110X-6-14	6	1/4"
60110X-8-18	8	1/8"
60110X-8-14	8	1/4"
60110X-10-14	10	1/4"
60110X-10-38	10	3/8"
60110X-10-12	10	1/2"
60110X-12-38	12	3/8"
60110X-12-12	12	1/2"
Tech Sheet 1378		



Male Thread, Metric & BSPP

0006	OD mm	Thread
60115X-4-M5	4	M5
60115X-4-18	4	1/8"
60115X-4-14	4	1/4"
60115X-6-M5	6	M5
60115X-6-18	6	1/8"
60115X-6-14	6	1/4"
60115X-6-38	6	3/8"
60115X-8-18	8	1/8"
60115X-8-14	8	1/4"
60115X-8-38	8	3/8"
60115X-10-14	10	1/4"
60115X-10-38	10	3/8"
60115X-10-12	10	1/2"
60115X-12-38	12	3/8"
60115X-12-12	12	1/2"
60115X-14-12	14	1/2"
Tech Sheet 1378		

Male Stud Swivel Tees



Branch Male Thread, BSPT

0006	OD mm	Thread
60210X-4-18	4	1/8"
60210X-4-14	4	1/4"
60210X-6-18	6	1/8"
60210X-6-14	6	1/4"
60210X-8-18	8	1/8"
60210X-8-14	8	1/4"
60210X-10-14	10	1/4"
60210X-10-38	10	3/8"
60210X-10-12	10	1/2"
60210X-12-38	12	3/8"
60210X-12-12	12	1/2"
Tech Sheet 1378		



Branch Male Thread, BSPP

0006	OD mm	Thread
60215X-4-M5	4	M5
60215X-4-14	4	1/4"
60215X-6-M5	6	M5
60215X-6-18	6	1/8"
60215X-6-14	6	1/4"
60215X-8-18	8	1/8"
60215X-8-14	8	1/4"
60215X-10-14	10	1/4"
60215X-10-38	10	3/8"
60215X-10-12	10	1/2"
60215X-12-38	12	3/8"
60215X-12-12	12	1/2"
60215X-14-12	14	1/2"
Tech Sheet 1378		

Fluid-Air Components Ltd

316 STAINLESS STEEL PUSH-IN FITTINGS

stainless steel

AIGNEP

Working Temperature: -15°C to +190°C

Maximum Working Pressure: -0.99 bar to 20 bar

This series is fully made of stainless steel AISI 316L and developed to be used with aggressive fluids and food applications. Also ideal for use in salty environments and in machines that need frequent washing with aggressive detergents. Certified NSF 169 and conformed to NSF 61 & NSF 372 standards. All parallel threads have a Food FKM seal as standard.

Tube x Tube Connectors



Equal Straights

0006	OD mm
60040-4	4
60040-6	6
60040-8	8
60040-10	10
60040-12	12
60040-14	14
Tech Sheet 1378	



Unequal Straights

0006	OD mm	OD mm
60040-4-6	4	6
60040-6-8	6	8
60040-8-10	8	10
60040-10-12	10	12
Tech Sheet 1378		



Equal Bulkheads

0006	OD mm	Thread
60050-4	4	M12 x 1
60050-6	6	M14 x 1
60050-8	8	M16 x 1
60050-10	10	M20 x 1
60050-12	12	M22 x 1
Tech Sheet 1378		



Equal Ys

0006	OD mm
60310X-4	4
60310X-6	6
60310X-8	8
Tech Sheet 1378	



Equal Elbows

0006	OD mm
60130X-4	4
60130X-6	6
60130X-8	8
60130X-10	10
60130X-12	12
60130X-14	14
Tech Sheet 1378	



Equal Tees

0006	OD mm
60230X-4	4
60230X-6	6
60230X-8	8
60230X-10	10
60230X-12	12
60230X-14	14
Tech Sheet 1378	

Stem Adaptors



Male Thread, BSPP

0006	OD mm	Thread
60600-6-18	6	1/8"
60600-8-14	8	1/4"
60600-10-14	10	1/4"
60600-10-38	10	3/8"
60600-12-38	12	3/8"
60600-12-12	12	1/2"
Tech Sheet 1378		

Fluid-Air Components Ltd

PLASTIC PLUMBING PUSH-IN FITTINGS

Couplings



Straight

1400	OD mm
PEM0410W	10
PKM0415W	15
PKM0422W	22
PEM0428W	28
Tech Sheet 20630	



Reducing

1400	OD mm	OD mm
PKM201510W	15	10
PKM202215W	22	15
Tech Sheet 20630		



BSPP Female to Tap Connector

1400	OD mm	Thread
PEM3210W	10	1/2"
PEM3201W	15	1/2"
PEM3203W	15	3/4"
PEM3202W	22	3/4"
Tech Sheet 20630		

Pipe Inserts

To be used on installation when using plastic pipe.



1400	To Suit ID mm
TSM10N	10
TSM15N	15
TSM22N	22
TSM28N	28
Tech Sheet 20630	

Elbows



Equal

1400	OD mm
PEM0310W	10
PKM0315W	15
PKM0322W	22
PEM03228W	28
Tech Sheet 20630	

- Provides a swivel type connection.



Stem

1400	OD mm	Stem OD mm
PEM221010W	10	10
PKM221515W	15	15
PKM222222W	22	22
Tech Sheet 20630		



Brass Wing Back, BSPP Female

1400	OD mm	Thread
15WB	15	1/2"
22WB	22	3/4"
Tech Sheet 20630		

End Stops



1400	OD mm
PSE4610W	10
PKM4615W	15
PKM4622W	22
Tech Sheet 20630	

Tees



Equal

1400	OD mm
PEM0210W	10
PKM0215W	15
PKM0222W	22
PEM0228W	28
Tech Sheet 20630	



Increasing on Branch

1400	OD A mm	OD B mm
PKM3022CW	15	22
Tech Sheet 20630		



Reducing on Branch

1400	OD A mm	OD B mm
PEM3015BW	15	10
PEM3015AW	15	10
PEM302210AW	22	10
PKM3022AW	22	15
PEM3028AW	28	22



Increasing on Run

1400	OD A mm	OD B mm
PEM3022BW	22	15
Tech Sheet 20630		



Reducing on Run

1400	OD A mm	OD B mm
PKM3022DW	22	15
PEM3028DW	28	22

PLASTIC PLUMBING PUSH-IN FITTINGS

Reducers



1400	OD mm	Stem OD mm
PEM061510W	10	15
PEM062215W	15	22
PEM062815W	15	28
PEM062822W	22	28
Tech Sheet 20630		

Connectors



Tap, BSPP Female

1400	OD mm	Thread
PKMSTC1514	15	1/2" Straight
PKMSTC1516	15	3/4" Straight
PKMSTC2216	22	3/4" Straight
Tech Sheet 20630		

Maximum wall thickness of tank = 4mm.
Note: Requires hand tightening only.



Tank

1400	OD mm
CM0715S	15
CM0722S	22
CM0728S	28
Tech Sheet 20630	

Brass Drain Cock

Speedfit Drain Cocks cannot be used where collet covers are fitted. They can be used with a standard fitting fitte with a collet clip.



1400	OD mm
15BDC	15
Tech Sheet 20630	

Service Valves

N.B: Hot and cold water only 65°C max.
Not suitable for central heating systems.



Plastic

1400	OD mm
15ISV	15
Tech Sheet 20630	



Brass Chrome Plated

1400	OD mm
10HSV	10
15HSV	15
22HSV	22
Tech Sheet 20630	



Brass Chrome Plated with Tap Connector BSPP Female

1400	OD mm	Thread
15PTSV	15	1/2"
Tech Sheet 20630		

Brass Chrome Plated Ball Valves

Suitable for central heating systems, each valve has a red and blue indice.



1400	OD mm
10BV	10
15BV	15
22BV	22
Tech Sheet 20630	

Valves

N.B. Hot and cold water only 65°C max.



Stop

1400	OD mm
15STV	15
22STV	22
Tech Sheet 20630	



Brass Stop

1400	OD mm
15BSC	15
Tech Sheet 20630	

N.B. Hot and cold water only 65°C max.
Not suitable for central heating systems.



Double Check

1400	OD mm
15DCV	15
Tech Sheet 20630	

Taps



Emergency Shut Off

1400	OD mm
15ESOT	15
Tech Sheet 20630	

N.B. Hot and cold water only 65°C max.



Washing Machine, BSPP

1400	OD mm	Thread
15APT-B	15	3/4"
Tech Sheet 20630		

Fluid-Air Components Ltd

PLASTIC PLUMBING PUSH-IN FITTINGS, PIPES & CUTTERS

Barrier Pipes

British Gas accepted for water pipe in vented and sealed central heating systems.
The pipe has an inner barrier to stop the ingress of atmosphere.



Pex Coils

1400	OD mm	Length Metres
10BPEX-25C	10	25
10BPEX-50C	10	50
15BPEX-25C	15	25
15BPEX-50C	15	50
15BPEX-100C	15	100
22BPEX-25C	22	25
22BPEX-50C	22	50
Tech Sheet 20363		


This pipe is made from a soft material with little memory ensuring a flexible system. It has an inner barrier to stop the ingress of atmosphere. British Gas accepted for water pipe in vented and sealed central heating systems.

- Easy to handle
- Ultra flexibl



Layflat Polybutylen

1400	OD mm	Length Metres
15BPB-25C	15	25
15BPB-50C	15	50
15BPB-100C	15	100
22BPB-25C	22	25
22BPB-50C	22	50
Tech Sheet 20363		





Straight Lengths

1400	OD mm	Length Metres	Quantity
15BPEX-20X2L	15	2	20
15BPEX-20X3L	15	3	20
22BPEX-20X2L	22	2	20
22BPEX-20X3L	22	3	20
28BPEX-10X3L	28	3	10
Tech Sheet 20363			

Flexi Hoses



Push-in to BSPP Female

1400	OD mm	Thread	Length mm
FLX15	15	1/2"	300
FLX18	15	1/2"	500
FLX16	15	3/4"	300
FLX20	15	3/4"	500
FLX22	22	3/4"	300
FLX19	22	3/4"	500
Tech Sheet 20630			



Push-in to Push-in

1400	OD mm	OD mm	Length mm
FLX33	15	10	300
FLX17	15	15	300
FLX21	15	15	500
FLX26	22	22	300
FLX27	22	22	500
Tech Sheet 20630			



Push-in to BSPP Female with Service Valve

1400	OD mm	Thread	Length mm
FLX37	15	1/2"	300 Full Bore
FLX24	15	1/2"	300
Tech Sheet 20630			

N.B. Hot & cold water only, 65°C maximum



Elbow

1400	OD mm	Thread	Length mm
FLX36	15	1/2"	300
Tech Sheet 20630			

Adaptors



Brass Male Cylinder, BSPP

1400	OD mm	Thread
22CMA	22	1"
Tech Sheet 20630		



Brass Female Cylinder, BSPP

1400	OD mm	Thread
22CFA	22	1"
Tech Sheet 20630		

Cutters



Heavy-duty Pipe Cutter

1400	Pipe Size
JG-HDC	Up to 28 mm



Aluminium Pipe Cutter

1400	OD mm
ALU-CUTTER15	15
ALU-CUTTER22	22
ALU-CUTTER28	28
Tech Sheet 20629	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FITTINGS VALVES PIPING & ACCESSORIES RANGE

John Guest

John Guest Plumbing Range



Radiator Key

1400	Description
RK1C	Brass Key



Male Coupler - Brass

1400	Size mm	Thread
10MC	10	1/2" BSPP
15MC	15	1/2" BSPP
MW011504N	15	1/2" BSPT
22MC	22	3/4" BSPP
MW012206N	22	3/4" BSPT
MW012818N	28	1" BSPP
MW012808N	28	1" BSPT



Hose Connector

1400	Size mm	Hose ID
NC448	15	1/2"
NC473	22	3/4"



Conversion Connector

1400	Size mm	OD
NC471	15	5/8"



Slip Connector

1400	Size mm
CM-SC-15S	15



PE Copper Coupler

1400	Size mm
JG603B	25 x 15



45° Stem Elbow

1400	Pipe mm	Stem mm
PEM571515W	15	15
PEM572222W	22	22



Bend Tap Connector, Female Thread, BSPP

1400	Size mm	Thread
PEMBTC1514	15	1/2"



Stem Tee

1400	Size mm
PEM532210W	22 x 22 x 10
PEM532215W	22 x 22 x 15



4 Port Rail Manifold

1400	Size mm
SFM522210S	22 x 10
SFM522215S	22 x 15



4 Way Manifold

1400	Size mm
SFM512210S	22 x 10



Male Stem Adaptor, Brass, BSPT

1400	Size mm	Thread
MW052206N	22	3/4"
MW052818N	28	1"



Female Stem Adaptor, Brass, BSPP

1400	Size mm	Thread
MW502216N	22	3/4"



Pipe Adaptor, Brass

1400	Thread	Size mm
NC2239	3/4"	22

FITTINGS VALVES PIPING & ACCESSORIES RANGE


John Guest

John Guest Plumbing Range



Collet Locking Clip

1400	Size mm	Colour
CM1815B	15	Blue
CM1815R	15	Red



Collet Cover

1400	Colour	Size mm
AM1915W	White	15
PM1915B	Blue	15



Collets

1400	Size mm
PXC10	10



EPDM O Ring

1400	Size mm
10EPR	10



Thread Washer

1400	Size
1/2EPW	1/2"



Shut Off Valve, Imperial & Metric

1400	Tube OD 1	Tube OD 2
PPMSV040606W	6mm	6mm
PPMSV041010W	10mm	10mm
PPSV040808W	1/4"	1/4"
PPSV041212W	3/8"	3/8"



Shut Off Valve, Long Handle

1400	Tube OD
PISV0412S	3/8"
PISV0416S	1/2"



Shut Off Valve, Male Thread, NPT

1400	Tube OD	Thread
PPSV010822W	1/4"	1/4"
PPSV011223W	3/8"	3/8"



Shut Off Valve, Female Thread, NPT

1400	Tube OD	Thread
PPSV500822W	1/4"	1/4"



Mounting Clip

1400	Size
SVMC-10	3/8" Shut Off Valve Clip



Single Check Valve

1400	Tube OD mm
6SCV	6
10SCV	10
5/16SCV	5/16"



Conduit Pipe

1400	Size mm	Length Metres
22BLKCON-25C	22	25



Bending Spring

1400	Size mm
JG-BS15	15



Superseal Pipe Insert

1400	Size mm
STS15	15
STS22	22
STS28	28



Pipe Clips & Spacers

1400	Size mm	Colour
PC15W	15	White
PC22W	22	White
PC28W	28	White
PCSW	Spacer	White



Nail Clip

1400	Size mm	Colour
NPC15	15	White

BRASS PUSH-IN PLUMBING TUBE FITTINGS

ITAP-FIT® Fitting

Suitable for:
Copper, PEX and Polybutylene pipe.

Working Temperature:
-20°C to +120°C

Maximum Working Pressure:
Copper Pipe: 20 bar @ 25°C, 10 bar @ 90°C
PEX and Polybutylene Pipe: 12 bar @ 25°C, 5 bar @ 90°C



Female Stud Coupling

0089	OD mm	Thread
610B038012	12	3/8"
610B012012	12	1/2"
610B012014	14	1/2"
610B012015	15	1/2"
610B012016	16	1/2"
610B012018	18	1/2"
610B012020	20	1/2"
610B034018	18	3/4"
610B034022	22	3/4"
610B034025	25	3/4"
610B100028	28	1"
Tech Sheet 10533		



Male Stud Coupling

0089	OD mm	Thread
615B038012	12	3/8"
615B038014	14	3/8"
615B012012	12	1/2"
615B012014	14	1/2"
615B012015	15	1/2"
615B012016	16	1/2"
615B012018	18	1/2"
615B012020	20	1/2"
615B034018	18	3/4"
615B034022	22	3/4"
615B034025	25	3/4"
615B100028	28	1"
Tech Sheet 10533		



Female Stud 90° Elbow, BSPT

0089	OD mm	Thread
645B038012	12	3/8"
645B012012	12	1/2"
645B012014	14	1/2"
645B012015	15	1/2"
645B012016	16	1/2"
645B012018	18	1/2"
645B012020	20	1/2"
645B034018	18	3/4"
645B034022	22	3/4"
645B034025	25	3/4"
645B100028	28	1"
Tech Sheet 10533		



Female Stud 90° Elbow (Wall Mount), BSPT

0089	OD mm	Thread
648B038012	12	3/8"
648B012012	12	1/2"
648B012014	14	1/2"
648B012015	15	1/2"
648B012016	16	1/2"
648B012018	18	1/2"
648B012020	20	1/2"
648B034018	18	3/4"
648B034022	22	3/4"
Tech Sheet 10533		



Male Stud 90° Elbow, BSPT

0089	OD mm	Thread
640B038012	12	3/8"
640B012012	12	1/2"
640B012014	14	1/2"
640B012015	15	1/2"
640B012016	16	1/2"
640B012018	18	1/2"
640B012020	20	1/2"
640B034018	18	3/4"
640B034022	22	3/4"
640B034025	25	3/4"
640B100028	28	1"
Tech Sheet 10533		



Female Branch Tee, BSPT

0089	OD mm	Thread
635B012014	14	1/2"
635B012015	15	1/2"
635B012016	16	1/2"
635B012018	18	1/2"
635B012020	20	1/2"
635B034018	18	3/4"
635B034022	22	3/4"
635B034025	25	3/4"
635B100028	28	1"
Tech Sheet 10533		



Disconnecting Clip

0089	OD mm
671012	12
671014	14
671015	15
671016	16
671018	18
671020	20
671022	22
671025	25
671028	28
Tech Sheet 10533	



Depth Gauge

0089
685012028
Tech Sheet 10533

Fluid-Air Components Ltd

BRASS PUSH-IN PLUMBING TUBE FITTINGS

ITAP-FIT® Fitting

Suitable for:
Copper, PEX and Polybutylene pipe

Working Temperature:
-20°C to +120°C

Maximum Working Pressure:
Copper Pipe: 20 bar @ 25°C, 10 bar @ 90°C
PEX and Polybutylene Pipe: 12 bar @ 25°C, 5 bar @ 90°C



Straight

0089	OD mm
620C000012	12
620C000014	14
620C000015	15
620C000016	16
620C000018	18
620C000020	20
620C000022	22
620C000025	25
620C000028	28
Tech Sheet 10533	



Equal 90° Elbow

0089	OD mm
650C000012	12
650C000014	14
650C000015	15
650C000016	16
650C000018	18
650C000020	20
650C000022	22
650C000025	25
650C000028	28
Tech Sheet 10533	



Equal Tee

0089	OD mm
630C000012	12
630C000014	14
630C000015	15
630C000016	16
630C000018	18
630C000020	20
630C000022	22
630C000025	25
630C000028	28
Tech Sheet 10533	



End Stop

0089	OD mm
625C000012	12
625C000014	14
625C000015	15
625C000016	16
625C000018	18
625C000020	20
625C000022	22
Tech Sheet 10533	



Tube Liner

0089	To Suit
655BU012110	12 x 1.1
655BU012180	12 x 1.8
655BU012200	12 x 2.0
655BU015180	15 x 1.8
655BU015250	15 x 2.5
655BU016150	16 x 1.5
655BU016180	16 x 1.8
655BU016200	16 x 2.0
655BU018200	18 x 2.0
655BU020190	20 x 1.9
655BU020280	20 x 2.8
655BU022200	22 x 2.0
655BU025230	25 x 2.3
655BU025250	25 x 2.5
655BU028280	28 x 2.8
655BU028300	28 x 3.0
Tech Sheet 10533	



O-Ring

0089	OD mm
656EP012	12
656EP014	14
656EP015	15
656EP016	16
656EP018	18
656EP020	20
656EP022	22
656EP025	25
656EP028	28
Tech Sheet 10533	



Spacer

0089	OD mm
657DI012	12
657DI014	14
657DI015	15
657DI016	16
657DI018	18
657DI020	20
657DI022	22
657DI025	25
657DI028	28
Tech Sheet 10533	



Ring

0089	OD mm
658AG012	12
658AG014	14
658AG015	15
658AG016	16
658AG018	18
658AG020	20
658AG022	22
658AG025	25
658AG028	28
Tech Sheet 10533	

Fluid-Air Components Ltd

AIR BRAKE FITTINGS

Male Stud Couplings Mix Box

Contains:
2 x M12 x 8, 2 x M16 x 12, 2 x M16 x 8,
2 x M22 x 12, 2 x M16 x 10, 1 x M22 x 15,
2 x M22 x 10, 1 x M22 x 18



14 Piece

1360
008ABK

Straight Connectors Mix Box

Contains:
2 x 6 mm, 2 x 12 mm, 2 x 8 mm,
2 x 15 mm, 2 x 10 mm, 2 x 16 mm,
1 x 18 mm



15 Piece

1360
085ABK

Male Stud Elbow Mix Box

Contains:
2 x M12 x 8, 1 x M22 x 10, 2 x M16 x 8,
1 x M16 x 12, 2 x M22 x 8, 1 x M22 x 12,
2 x M12 x 10, 1 x M22 x 15, 2 x M16 x 10,
1 x M22 x 18



15 Piece

1360
081ABK

Workshop & Mobile Full Repair/Service Kit



120 Piece

1360
086ABK

Male Studs



Metric

1360	OD mm	Thread
800212ABF	6	M12
800216ABF	6	M16
800312ABF	8	M12
800316ABF	8	M16
800322ABF	8	M22
800412ABF	10	M12
800416ABF	10	M16
800422ABF	10	M22
800516ABF	12	M16
800522ABF	12	M22
800622ABF	15	M22
800722ABF	16	M22
800822ABF	18	M22
800826ABF	18	M26

Male Stud Elbows



Metric

1360	OD mm	Thread
810212ABF	6	M12
810216ABF	6	M16
810312ABF	8	M12
810316ABF	8	M16
810322ABF	8	M22
810412ABF	10	M12
810416ABF	10	M16
810422ABF	10	M22
810516ABF	12	M16
810522ABF	12	M22
810622ABF	15	M22
810722ABF	16	M22
810822ABF	18	M22

Bulkheads



Metric

1360	Thread
703222ABF	M22 x M16 x F10 mm
703322ABF	M22 x M18 x F12 mm
703522ABF	M22 x M22 x F16 mm

Hex Straight



Metric

1360	Thread
750300ABF	M12
750500ABF	M16
750700ABF	M22

Fluid-Air Components Ltd

AIR BRAKE FITTINGS

Straight Joiners



Tube

1360	OD mm
850200ABF	6
850300ABF	8
850400ABF	10
850500ABF	12
850600ABF	15
850700ABF	16
850800ABF	18

Elbow Joiners



Tube

1360	OD mm
860200ABF	6
860300ABF	8
860900ABF	9
860400ABF	10
860110ABF	11
860500ABF	12
860600ABF	15
860700ABF	16
860800ABF	18

Tee Joiners



Tube

1360	OD mm
870200ABF	6
870300ABF	8
870400ABF	10
870500ABF	12
870600ABF	15

Elbows



Female Thread, Metric

1360	Thread
760300ABF	M12
760500ABF	M16
760700ABF	M22



Male Thread x Female Thread, Metric

1360	Male Thread	Female Thread
710312ABF	M12	M12
710316ABF	M16	M12
710322ABF	M22	M12
710516ABF	M16	M16
710522ABF	M22	M16
710722ABF	M22	M22



F Elbow, Male Thread x Female Thread, Metric

1360	Male Thread	Female Thread
743516ABF	M16	M16



45° Elbow, Male Thread x Female Thread, Metric

1360	Male Thread	Female Thread
740516ABF	M16	M16
740722ABF	M22	M22

Tees



Female Thread, Metric

1360	Thread
770300ABF	M12
770500ABF	M16
770700ABF	M22



Male Thread x Female Thread, Metric

1360	Male Thread	Female Thread
730312ABF	M12	M12
730316ABF	M16	M12
730322ABF	M22	M12
730516ABF	M16	M16
730522ABF	M22	M16
730722ABF	M22	M22

Stud Run Tee



Male Thread x Female Thread, Metric

1360	Male Thread	Female Thread
720312ABF	M12	M12
720316ABF	M16	M12
720322ABF	M22	M12
720516ABF	M16	M16
720522ABF	M22	M16
720722ABF	M22	M22

AIR BRAKE FITTINGS

Test Points



Male Thread, Metric

1360	Thread
TPM12T	M12
TPM16T	M16
TPM22T	M22

Drain Taps



Male Thread, Metric

1360	Thread
TT3T	M22

Blanking Plugs



Male Thread, Metric

1360	Thread
BP12B	M12
BP16B	M16
BP22B	M22

AIR BRAKE SWIVEL FITTINGS

Male Studs



Male Thread, Metric

1360	Thread
660502ABF	1/8"
660504ABF	1/4"
660510ABF	M10
660512ABF	M12
660514ABF	M14
660516ABF	M16
660522ABF	M22
660526ABF	M26

Elbow Joiners



Tube

1360	Tube OD mm
815200ABF	6
815300ABF	8
815400ABF	10
815500ABF	12

Elbow



Female Thread, Metric

1360	Thread
615500ABF	M16

45º Elbow



Female Thread, Metric

1360	Thread
645500ABF	M16

Tee



Female Thread, Metric

1360	Thread
635500ABF	2 x M16

Side Tee



Female Thread, Metric

1360	Thread
625500ABF	2 x M16

Cross



Female Thread, Metric


1360	Tube OD mm
646500ABF	3 x M16

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Series 9000 C-Truck

Brass fittings

CAMOZZI
Automation



The safe and practical solution for pneumatic braking systems

Series 9000 C-Truck fittings have been designed to connect tubes in the pneumatic braking systems on industrial and commercial vehicles ensuring reliability and ease of assembling. The use of a proper disconnection tool enables disconnection of the tube without having to remove the fitting. All fittings have a protective cap that keeps humidity an dirt away from the collet. A reinforced insert enables the dimensions of the tube to remain constant, thus ensuring a tight and safe connection even with high changes in temperature. Indeed, Series 9000 C-Truck fittings can be used at extreme temperatures (from -50°C to +100°C). They are assembled according to a precise angle and supplied with locking nut and a self sealing O-ring. The O-ring on the thread is set in a special groove of the threaded part, ensuring there is no damage during assembly. The brass body guarantees a high resistance to corrosion, whilst the O-ring and protective cap are made from oil resistant rubber. All fittings are supplied
pre-assembled and ready to use.



General Data

Materials: see table of materials
Thread: Metric NPT
Media: Compressed air
Max working pressure: 16 bar
Note: pressure depends on tube characteristics
Temperature: -50°C ÷ +100°C
Tube: Material Polyamide
Tube diameters (D/d): 4/2, 6/4, 8/6, 10/7, 10/8, 12/9, 15/11, 15/12, 16/12, 16/13 and 18/14

Certification


Camozzi
Air that moves the world

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR BRAKE PUSH-IN FITTINGS C-TRUCK 9000 SERIES

CAMOZZI Automation

Table of Materials



Parts	Materials
1 = Body	Brass
2 = Insert	Technopolymer (Brass only for Ø10/7, 15/11, 16/12, 16/13 and 18/14)
3 = S-rapid	O-Ring NBR
4 = Collet	Brass
5 = Protective seal	NBR
6 = O-Ring for thread	NBR
7 = Locking ring	Steel

Fittings Assembly in the System

To guarantee the tightening of the fitting in the system, make sure that the thread chamfer conforms to the standard ISO 965 or GOST 10549-80.

The fittings which have an O-Ring seal on the thread, but no locking nut, have to be screwed into the system with the torque forces as shown in the table below.

For the assembly of fittings with locking nut, it is necessary to do the following:

1. Loosen the locking nut
2. Screw the fitting into the system until the O-Ring comes into contact with the system surface
3. Position the fitting according to the suitable angle, moving the body up to 360°
4. Keep the body still
5. Screw the locking nut with torque forces as shown in the table

Thread	Torque force (Nm)
M10 x 1	11 - 15
M12 x 1.5	15 - 19
M14 x 1.5	19 - 23
M16 x 1.5	24 - 30
M18 x 1.5	27 - 33
M22 x 1.5	36 - 44

Straight Adaptors



Male, Metric

0322	Thread	OD mm
9512-6-M10	M10 x 1	6
9512-6-M12	M12 x 1.5	6
9512-6-M14	M14 x 1.5	6
9512-6-M16	M16 x 1.5	6
9512-8-M10	M10 x 1	8
9512-8-M12	M12 x 1.5	8
9512-8-M14	M14 x 1.5	8
9512-8-M16	M16 x 1.5	8
9512-8-M22	M22 x 1.5	8
9512-10-M12	M12 x 1.5	10
9512-10-M16	M16 x 1.5	10
9512-10-M18	M18 x 1.5	10
9512-10-M22	M22 x 1.5	10
9512-10/7-M12	M12 x 1.5	10/7
9512-10/7-M16	M16 x 1.5	10/7
9512-10/7-M22	M22 x 1.5	10/7
9512-12-M12	M12 x 1.5	12
9512-12-M14	M14 x 1.5	12
9512-12-M16	M16 x 1.5	12
9512-12-M22	M22 x 1.5	12
9512-15-M16	M16 x 1.5	15
9512-15-M22	M22 x 1.5	15
9512-15/11-M16	M16 x 1.5	15/11
9512-16-M22	M22 x 1.5	16
9512-16/12-M16	M16 x 1.5	16/12
9512-16/12-M22	M22 x 1.5	16/12
9512-18-M22	M22 x 1.5	18
Tech Sheet 20453		



Male, NPT

0322	Thread	OD mm
9510-6-02	1/8"	6
9510-05-02	1/8"	8



Female, Metric

0322	Thread	OD mm
9463-6-M10	M10 x 1	6
9463-6-M16	M16 x 1.5	6
9463-8-M10	M10 x 1	8

Elbow Adaptors



Male, Metric

0322	Thread	OD mm
9502-6-M10	M10 x 1	6
9502-6-M12	M12 x 1.5	6
9502-6-M16	M16 x 1.5	6
9502-6-M22	M22 x 1.5	6
9502-8-M10	M10 x 1	8
9502-8-M12	M12 x 1.5	8
9502-8-M14	M14 x 1.5	8
9502-8-M16	M16 x 1.5	8
9502-8-M22	M22 x 1.5	8
9502-10-M12	M12 x 1.5	10
9502-10-M16	M16 x 1.5	10
9502-10-M22	M22 x 1.5	10
9502-10/7-M12	M12 x 1.5	10/7
9502-10/7-M16	M16 x 1.5	10/7
9502-10/7-M22	M22 x 1.5	10/7
9502-12-M12	M12 x 1.5	12
9502-12-M16	M16 x 1.5	12
9502-12-M22	M22 x 1.5	12
9502-15-M16	M16 x 1.5	15
9502-15-M22	M22 x 1.5	15
9502-16-M22	M22 x 1.5	16
9502-16/12-M16	M16 x 1.5	16/12
9502-16/12-M22	M22 x 1.5	16/12
9502-18-M22	M22 x 1.5	18
Tech Sheet 20453		



Double Push-in, Male, Metric

0322	Thread	OD mm
9402-12-M16	M16 x 1.5	12
9402-12-M22	M22 x 1.5	12
Tech Sheet 20453		



Male, NPT

0322	Thread	OD mm
9500-6-02	1/8"	6
9500-05-02	1/8"	8
Tech Sheet 20453		

FAC Fluid-Air Components Ltd

AIR BRAKE THREADED FITTINGS C-TRUCK 9000 SERIES

CAMOZZI Automation

Tee Adaptors



Male Branch, Metric

0322	Thread	OD mm
9412-6-M10	M10 x 1	6
9412-6-M12	M12 x 1.5	6
9412-6-M16	M16 x 1.5	6
9412-8-M12	M12 x 1.5	8
9412-8-M16	M16 x 1.5	8
9412-8-M22	M22 x 1.5	8
9412-10-M12	M12 x 1.5	10
9412-10-M16	M16 x 1.5	10
9412-10-M22	M22 x 1.5	10
9412-10/7-M12	M12 x 1.5	10/7
9412-10/7-M16	M16 x 1.5	10/7
9412-10/7-M22	M22 x 1.5	10/7
9412-12-M12	M12 x 1.5	12
9412-12-M16	M16 x 1.5	12
9412-12-M22	M22 x 1.5	12
9412-15-M16	M16 x 1.5	15
9412-15-M22	M22 x 1.5	15
9412-15/11-M16	M16 x 1.5	15/11
9412-15/11-M22	M22 x 1.5	15/11
Tech Sheet 20453		



Male Branch, NPT

0322	Thread	OD mm
9410-6-02	1/8"	6
9410-05-02	1/8"	8
Tech Sheet 20453		



Male Run, Metric

0322	Thread	OD mm
9422-6-M10	M10 x 1	6
9422-6-M12	M12 x 1.5	6
9422-6-M16	M16 x 1.5	6
9422-8-M12	M12 x 1.5	8
9422-8-M16	M16 x 1.5	8
9422-8-M22	M22 x 1.5	8
9422-10-M16	M16 x 1.5	10
9422-10-M22	M22 x 1.5	10
9422-12-M12	M12 x 1.5	12
9422-12-M16	M16 x 1.5	12
9422-12-M22	M22 x 1.5	12
9422-15-M16	M16 x 1.5	15
9422-15-M22	M22 x 1.5	15
Tech Sheet 20453		



Male Run, NPT

0322	Thread	OD mm
9420-6-02	1/8"	6
9420-05-02	1/8"	8
Tech Sheet 20453		

Y Piece Adaptors



Male, Metric

0322	Thread	OD mm
9450-8-M16	M16 x 1.5	8
9450-12-M16	M16 x 1.5	12
9450-12-M22	M22 x 1.5	12
Tech Sheet 20453		

Straight Couplings



Tube x Tube

0322	OD mm
9580-6	6
9580-8	8
9580-10	10
9580-12	12
9580-15/11	15/11
9580-16/12	16/12
9580-18/14	18/14
Tech Sheet 20453	

Elbows



Tube x Tube

0322	OD mm
9550-6	6
9550-8	8
9550-10	10
9550-12	12
Tech Sheet 20453	

Tees



Equal, Tube x Tube

0322	OD mm
9540-6	6
9540-8	8
9540-10	10
9540-12	12
9540-15/11	15/11
Tech Sheet 20453	



Branch Unequal, Tube x Tube

0322	OD mm	OD mm
9540-8-8-6	8	6
9540-12-12-8	12	8
Tech Sheet 20453		

Bulkhead Couplings



Male, Metric

0322	Thread	OD mm
9590-8-M18	M18 x 1.5	8
9590-8-M18-S01	M18 x 1.5	8
9590-12-M18	M18 x 1.5	12
9590-12-M18-S01	M18 x 1.5	12
Tech Sheet 20453		

Bulkhead Couplings



Female, Metric


0322	Thread	OD mm
9592-8-8-M18	M18 x 1.5	8
9592-12-8-M18	M18 x 1.5	12
Tech Sheet 20453		

Fluid-Air Components Ltd

AIR BRAKE THREADED FITTINGS C-TRUCK 9000 SERIES


CAMOZZI Automation

Tees



Male x Female Branch, Metric

0322	Thread A	Thread B
D2062-M16XM12	M16 x 1.5	M12 x 1.5
D2062-M16XM16	M16 x 1.5	M16 x 1.5
D2062-M16XM22	M22 x 1.5	M16 x 1.5
D2062-M22XM22	M22 x 1.5	M22 x 1.5
Tech Sheet 20453		



Male x Female Run, Metric

0322	Thread A	Thread B
D2072-M16XM12	M16 x 1.5	M12 x 1.5
D2072-M16XM16	M16 x 1.5	M16 x 1.5
D2072-M16XM22	M22 x 1.5	M16 x 1.5
D2072-M22XM22	M22 x 1.5	M22 x 1.5
Tech Sheet 20453		



Equal Female, Metric

0322	Thread
D2003-M16	M16 x 1.5
D2003-M22	M22 x 1.5
Tech Sheet 20453	



Equal Female, Metric (Mountable)


0322	Thread
D2003-M16-S01	M16 x 1.5
Tech Sheet 20453	



Double Female, Metric

0322	Thread
D3043-M16-2D-S01	M16 x 1.5
Tech Sheet 20453	

Bulkheads





Female, Metric

0322	Thread A	Thread B	Thread C	Bulkhead
D2512-M22XM16	M16	M16	M10	M22
D2502-M22XM22	M22	M16	M16	M22
Tech Sheet 20453				

Elbows



Male x Female, Metric

0322	Thread A	Thread B
D2022-M16XM16	M16 x 1.5	M16 x 1.5
D2022-M16XM22	M22 x 1.5	M16 x 1.5
D2022-M22XM22	M22 x 1.5	M22 x 1.5
Tech Sheet 20453		



Male x Female, 2 Way Elbow, Metric

0322	Thread A	Thread B
D2077-M16-S01	M16 x 1.5	M16 x 1.5
D2077-M16M22S01	M16 x 1.5	M22 x 1.5
Tech Sheet 20453		

Cross



Male x Female, Metric

0322	Thread
D2032-M16	M16 x 1.5
Tech Sheet 20453	

For **Air Brake Tubing** see page **910**




Fluid-Air Components Ltd

AIR BRAKE ACCESSORIES C-TRUCK 9000 SERIES

CAMOZZI Automation

Hosetail Adaptors



Male, Metric

0322	Thread	OD mm	Length A mm
D2602-10-M16-L30	M16 x 1.5	11	30
D2602-12-M16X1.5	M16 x 1.5	12.5	20
D2602-11.5M16L35	M16 x 1.5	12.5	35
Tech Sheet 20453			

Release Tools



Metric

0322	To Suit mm
DRK 6	6
DRK 8	8
DRK 10	10
DRK 12	12
DRK 15	15
DRK 16	16
DRK 18	18
Tech Sheet 20453	

Plugs



Male, Metric

0322	Thread
D2612-M12X1.5	M12 x 1.5
D2612-M16X1.5	M16 x 1.5
D2612-M22X1.5	M22 x 1.5
Tech Sheet 20453	

Test Point Valve



Male, Metric

0322	Thread	Thread
VPC-M16-M16	M16 x 1.5	M16 x 1.5
VPC-M22-M16	M22 x 1.5	M16 x 1.5
Tech Sheet 20453		

PORTWEST



For **PPE**
see pages **1750-1760**

Inflation alve



Male x Female, Metric

0322	Thread
V604-M22-S01	M22 x 1.5
Tech Sheet 20453	

Drain Valve



Male, Metric

0322	Thread
VDC-M22-S01	M22 x 1.5
Tech Sheet 20453	

Push-in Connector



Male Metric Fittings Mod D6512

0322	Thread	OD mm
D6512-4-M10	M10 x 1	4
Tech Sheet 20453		

Fluid-Air Components Ltd

FT PRO®

Hose & Tubing

Thermoplastic tubing, hoses and assemblies for industrial and mobile applications.

- Polyurethane Tube
- Polyurethane Recoil Hoses
- Polyurethane Assemblies
- Nylon Tubing
- Nylon Recoil Hoses
- Tube Cutters



FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

FT PRO®

new product

Crystal Blue

FT Pro tubing is the engineered solution for pneumatic applications requiring excellence as standard.



896

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

Metric Polyurethane Ester Tube

Ester-based polyurethane tubing has outstanding characteristics compared with other pneumatic tubing. This tube is extremely flexible and offers excellent bend capabilities, making it ideal for pneumatic control or robotic systems. It is also resistant to many chemicals, gases and oils, as well as having excellent abrasion resistance.

✔ **Ideal for use with push-in fittings, compression fittings, quick-fit fittings and hose tail fittings.**

✘ **Not suitable for use with water or in high humidity environments.**



Specifications

Medium
Compressed air and industrial fluids

Working Pressure
Vacuum to 12 bar

Working Temperature
-20°C to +70°C

Component Materials
Polyurethane ester

Regulations

Industrial

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

FT PRO Polyurethane Tube

REACh ✓ RoHS


Metric Polyurethane Ester Tube



Part Number Colour Codes

N	Black	G	Green
B	Blue		Transparent
R	Red	CB	Crystal Blue
Y	Yellow		

new product



Metric, 25 Metre Coils

5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PU03/020B	3	2		150	10
PU03/020CB	3	2		150	10
PU04/025N	4	2.5		190	13
PU04/025B	4	2.5		190	13
PU04/025CB	4	2.5		190	13
PU04/025R	4	2.5		190	13
PU04/025Y	4	2.5		190	13
PU04/025G	4	2.5		190	13
PU04/025	4	2.5		190	13
PU05/030N	5	3		160	11
PU05/030B	5	3		160	11
PU05/030CB	5	3		160	11
PU06/040N	6	4		155	11
PU06/040B	6	4		155	11
PU06/040CB	6	4		155	11
PU06/040R	6	4		155	11
PU06/040Y	6	4		155	11
PU06/040G	6	4		155	11
PU06/040	6	4		155	11
PU08/055N	8	5.5		150	10
PU08/055B	8	5.5		150	10
PU08/055CB	8	5.5		150	10
PU08/055R	8	5.5		150	10
PU08/055Y	8	5.5		150	10
PU08/055G	8	5.5		150	10
PU08/055	8	5.5		150	10
PU08/060N	8	6		120	8

5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PU08/060B	8	6		120	8
PU08/060CB	8	6		120	8
PU08/060R	8	6		120	8
PU08/060Y	8	6		120	8
PU08/060G	8	6		120	8
PU08/060	8	6		120	8
PU10/065N	10	6.5		125	9
PU10/065B	10	6.5		125	9
PU10/065CB	10	6.5		125	9
PU10/065R	10	6.5		125	9
PU10/065Y	10	6.5		125	9
PU10/065G	10	6.5		125	9
PU10/065	10	6.5		125	9
PU10/080N	10	8		120	8
PU10/080B	10	8		120	8
PU10/080CB	10	8		120	8
PU10/080	10	8		120	8
PU12/080N	12	8		120	8
PU12/080B	12	8		120	8
PU12/080CB	12	8		120	8
PU12/080R	12	8		120	8
PU12/080Y	12	8		120	8
PU12/080G	12	8		120	8
PU12/080	12	8		120	8
PU16/110B	16	11		100	7
PU16/110CB	16	11		100	7

Tech Sheet 3131

Metric Polyurethane Ester Tube

Ester based polyurethane tubing has outstanding characteristics compared with other pneumatic tubing.

Part Number Colour Codes

N Black | B Blue | R Red | Y Yellow | G Green | Transparent | CB Crystal Blue





Metric, 100 Metre Coils


5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PU04/025N-100	4	2.5		190	13
PU04/025B-100	4	2.5		190	13
PU04/025CB-100	4	2.5		190	13
PU04/025R-100	4	2.5		190	13
PU04/025Y-100	4	2.5		190	13
PU04/025G-100	4	2.5		190	13
PU04/025-100	4	2.5		190	13
PU06/040N-100	6	4		155	11
PU06/040B-100	6	4		155	11
PU06/040CB-100	6	4		155	11
PU06/040R-100	6	4		155	11
PU06/040Y-100	6	4		155	11
PU06/040G-100	6	4		155	11
PU06/040-100	6	4		155	11
PU08/055N-100	8	5.5		150	10
PU08/055B-100	8	5.5		150	10
PU08/055CB-100	8	5.5		150	10
PU08/055R-100	8	5.5		150	10
PU08/055Y-100	8	5.5		150	10
PU08/055G-100	8	5.5		150	10
PU08/055-100	8	5.5		150	10
PU08/060N-100	8	6		120	8
PU08/060B-100	8	6		120	8

5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PU08/060CB-100	8	6		120	8
PU08/060R-100	8	6		120	8
PU08/060Y-100	8	6		120	8
PU08/060G-100	8	6		120	8
PU08/060-100	8	6		120	8
PU10/065N-100	10	6.5		125	9
PU10/065B-100	10	6.5		125	9
PU10/065CB-100	10	6.5		125	9
PU10/065R-100	10	6.5		125	9
PU10/065Y-100	10	6.5		125	9
PU10/065G-100	10	6.5		125	9
PU10/065-100	10	6.5		125	9
PU10/080N-100	10	8		120	8
PU10/080B-100	10	8		120	8
PU10/080CB-100	10	8		120	8
PU10/080-100	10	8		120	8
PU12/080N-100	12	8		120	8
PU12/080B-100	12	8		120	8
PU12/080CB-100	12	8		120	8
PU12/080R-100	12	8		120	8
PU12/080G-100	12	8		120	8
PU12/080-100	12	8		120	8
Tech Sheet 3131					

Polyurethane Recoil Twin Hose

Working Temperature
-20°C to +70°C





Red/Yellow

0306	OD mm	ID mm	Working Length Metres
TWIN80505RY	8	5	2.5
TWIN10656RY	10	6.5	3
TWIN12806RY	12	8	3
Tech Sheet 3133			

FT PRO Polyurethane Tube

REACh ✓ RoHS


Metric Polyurethane Ether Tube

Working Temperature
-40°C to +70°C

Ether based tube has a greater durability to water and high humidity environments.

PUET air line tubing is made from 95A shore durometer, ether-based polyurethane and is an excellent choice for compressed air systems.

- **Kink and abrasion resistant.**
- **Resistant to chemicals, water, fuel and oil.**
- **Outstanding flexibility and memory.**
- **Safety factor of 3 to 1**
- **Vacuum rating 28" Hg.**



Metric, 25 Metre Coils

5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PUET04/025N-25	4	2.5	■	156	11
PUET04/025B-25	4	2.5	■	156	11
PUET04/025CB-25	4	2.5	■	156	11
PUET04/025-25	4	2.5	□	156	11
PUET05/030N-25	5	3	■	171	12
PUET05/030B-25	5	3	■	171	12
PUET05/030CB-25	5	3	■	171	12
PUET05/030-25	5	3	□	171	12
PUET06/040N-25	6	4	■	142	10
PUET06/040B-25	6	4	■	142	10
PUET06/040CB-25	6	4	■	142	10
PUET06/040-25	6	4	□	142	10
PUET08/055N-25	8	5.5	■	114	8
PUET08/055B-25	8	5.5	■	114	8
PUET08/055CB-25	8	5.5	■	114	8
PUET08/055-25	8	5.5	□	114	8
PUET10/070N-25	10	7	■	114	8
PUET10/070B-25	10	7	■	114	8
PUET10/070CB-25	10	7	■	114	8
PUET10/070-25	10	7	□	114	8
PUET12/080N-25	12	8	■	128	9
PUET12/080B-25	12	8	■	128	9
PUET12/080CB-25	12	8	■	128	9
PUET12/080-25	12	8	□	128	9
Tech Sheet 3132					


Metric, 100 Metre Coils

5030	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
PUET04/025N-100	4	2.5	■	156	11
PUET04/025B-100	4	2.5	■	156	11
PUET04/025CB-100	4	2.5	■	156	11
PUET04/025-100	4	2.5	□	156	11
PUET06/040N-100	6	4	■	142	10
PUET06/040B-100	6	4	■	142	10
PUET06/040CB-100	6	4	■	142	10
PUET06/040-100	6	4	□	142	10
PUET08/055N-100	8	5.5	■	114	8
PUET08/055B-100	8	5.5	■	114	8
PUET08/055CB-100	8	5.5	■	114	8
PUET08/055-100	8	5.5	□	114	8
PUET10/070N-100	10	7	■	114	8
PUET10/070B-100	10	7	■	114	8
PUET10/070CB-100	10	7	■	114	8
PUET10/070-100	10	7	□	114	8
PUET12/080N-100	12	8	■	128	9
PUET12/080B-100	12	8	■	128	9
PUET12/080CB-100	12	8	■	128	9
PUET12/080-100	12	8	□	128	9
Tech Sheet 3132					

Blow Guns & Polyurethane Coil Assemblies, Red

1/4" BSPT

5030	OD mm	ID mm	Working Length Metres	Blow Gun Type
2027-3967	6	4	2	ASG-1
2027-3975	6	4	4	ASG-1
2027-4007	6	4	2	BG5
2027-4015	6	4	4	BG5
2027-4023	10	6.5	2	ASG-1
2025-2763	10	6.5	4	ASG-1
2027-4049	10	6.5	6	ASG-1
2027-4056	10	6.5	2	BG5
2027-4064	10	6.5	4	BG5
2027-4072	10	6.5	6	BG5
Tech Sheet 3133				



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Metric Polyurethane Coil Assemblies

Also available in

B Blue R Red Y Yellow





CB Crystal Blue

Brass Nickel Plated Swivel, BSPT with Spring Guards

5030	OD mm	ID mm	Working Length Metres	Thread	Colour
2196-4229	6	4	2	1/4"	
2196-4230	6	4	4	1/4"	
2196-4231	6	4	6	1/4"	
2196-4232	6	4	8	1/4"	
2196-4233	6	4	10	1/4"	
2196-4234	8	5	2	1/4"	
2196-4235	8	5	4	1/4"	
2196-4236	8	5	6	1/4"	
2196-4237	8	5	8	1/4"	
2196-4238	8	5	10	1/4"	
2196-4239	8	5	12	1/4"	
2196-4240	10	6.5	2	1/4"	
2196-4241	10	6.5	4	1/4"	
2196-4242	10	6.5	6	1/4"	
2196-4243	10	6.5	8	1/4"	
2196-4244	10	6.5	10	1/4"	
2196-4245	10	6.5	12	1/4"	
2196-4246	12	8	2	3/8"	
2196-4247	12	8	4	3/8"	
2196-4248	12	8	6	3/8"	
2196-4249	12	8	8	3/8"	
2196-4250	12	8	10	3/8"	
2196-4251	12	8	12	3/8"	
2196-4252	6	4	2	1/4"	
2196-4253	6	4	4	1/4"	
2196-4254	6	4	6	1/4"	
2196-4255	6	4	8	1/4"	
2196-4256	6	4	10	1/4"	
2196-4257	8	5	2	1/4"	
2196-4258	8	5	4	1/4"	
2196-4259	8	5	6	1/4"	
2196-4260	8	5	8	1/4"	
2196-4261	8	5	10	1/4"	
2196-4262	8	5	12	1/4"	
2196-4263	10	6.5	2	1/4"	
2196-4264	10	6.5	4	1/4"	
2196-4265	10	6.5	6	1/4"	
2196-4266	10	6.5	8	1/4"	
2196-4267	10	6.5	10	1/4"	
2196-4268	10	6.5	12	1/4"	
2196-4269	12	8	2	3/8"	
2196-4270	12	8	4	3/8"	
2196-4271	12	8	6	3/8"	
2196-4272	12	8	8	3/8"	
2196-4273	12	8	10	3/8"	

5030	OD mm	ID mm	Working Length Metres	Thread	Colour
2196-4275	6	4	2	1/4"	
2196-4276	6	4	4	1/4"	
2196-4277	6	4	6	1/4"	
2196-4278	6	4	8	1/4"	
2196-4279	6	4	10	1/4"	
2196-4280	8	5	2	1/4"	
2196-4281	8	5	4	1/4"	
2196-4282	8	5	6	1/4"	
2196-4283	8	5	8	1/4"	
2196-4284	8	5	10	1/4"	
2196-4285	8	5	12	1/4"	
2196-4286	10	6.5	2	1/4"	
2196-4287	10	6.5	4	1/4"	
2196-4288	10	6.5	6	1/4"	
2196-4289	10	6.5	8	1/4"	
2196-4290	10	6.5	10	1/4"	
2196-4291	10	6.5	12	1/4"	
2196-4292	12	8	2	3/8"	
2196-4293	12	8	4	3/8"	
2196-4294	12	8	6	3/8"	
2196-4295	12	8	8	3/8"	
2196-4296	12	8	10	3/8"	
2196-4297	12	8	12	3/8"	
2196-4298	6	4	2	1/4"	
2196-4299	6	4	4	1/4"	
2196-4300	6	4	6	1/4"	
2196-4301	6	4	8	1/4"	
2196-4302	6	4	10	1/4"	
2196-4303	8	5	2	1/4"	
2196-4304	8	5	4	1/4"	
2196-4305	8	5	6	1/4"	
2196-4306	8	5	8	1/4"	
2196-4307	8	5	10	1/4"	
2196-4308	8	5	12	1/4"	
2196-4309	10	6.5	2	1/4"	
2196-4310	10	6.5	4	1/4"	
2196-4311	10	6.5	6	1/4"	
2196-4312	10	6.5	8	1/4"	
2196-4313	10	6.5	10	1/4"	
2196-4314	10	6.5	12	1/4"	
2196-4315	12	8	2	3/8"	
2196-4316	12	8	4	3/8"	
2196-4317	12	8	6	3/8"	
2196-4318	12	8	8	3/8"	
2196-4319	12	8	10	3/8"	
2196-4320	12	8	12	3/8"	

FT PRO® Polyurethane Recoil Hoses

REACh ✓ RoHS

Swivel Fitting for Polyurethane Tube & Flexi-Braid Polyurethane Braided Hose

Other fittings can be used with "Flexi-Braid" Hose, such as brass hose-tails (see page 1141) stainless steel hose tails (see page 1311) or nylon hose tails (see page 1150).



Brass Fitting BSPT


5030	To Suit Tube Size mm	Thread
PF0406-14	4 x 6	1/4"
PF0508-14	5 x 8	1/4"
PF0610-14	6.5 x 10	1/4"
PF0812-14	8 x 12	1/4"
PF0812-38	8 x 12	3/8"
Tech Sheet 20350		

Brass Fitting BSPT, Nickel Plated with Spring Guards



5030	To Suit Tube Size mm	Thread
PF0406-14-NG	4 x 6	1/4"
PF0508-14-NG	5 x 8	1/4"
PF0610-14-NG	6.5 x 10	1/4"
PF0812-14-NG	8 x 12	1/4"
PF0812-38-NG	8 x 12	3/8"
Tech Sheet 20350		

Metric Poly Coil Assemblies




BSPT

5030	OD mm	Working Length Mtrs	Thread
PUC4/1-18	4	1	1/8"
PUC4/1-14	4	1	1/4"
PUC4/2-18	4	2	1/8"
PUC4/2-14	4	2	1/4"
PUC6/1-18	6	1	1/8"
PUC6/1-14	6	1	1/4"
PUC6/2-18	6	2	1/8"
PUC6/2-14	6	2	1/4"
PUC6/3-18	6	3	1/8"
PUC6/3-14	6	3	1/4"
PUC8/2-14	8	2	1/4"
PUC8/2-38	8	2	3/8"
PUC8/3-14	8	3	1/4"
PUC8/5-14	8	5	1/4"
Tech Sheet 3135			

Polyurethane Coil Type PUC

Coil hose polyurethane self-storing hose was developed to eliminate the two most common limitations of nylon self storing hoses; kinking and abrasion resistance. Lightweight yet extremely durable, polyurethane coil hose is ideal for use in tough work areas or highly mobile applications. This extremely flexible material which resists kinking and is impervious to abrasions and oils, is ideally suited for production line air tools; instrumentation; robotics; and many more industrial applications. The superior elasticity characteristics and very small bend radius make it ideal for use in confined spaces. Supplied without fittings, but ideal for use with push-in, hose tail or quick-fit fittings.

Working Temperature
-20°C to +60°C





5030	OD mm	ID mm	Length A mm	Length B mm	Length C mm	Working Length Mtrs	Colour
PUC4/1	4	2.5	80	26	60	1	
PUC4/2	4	2.5	80	26	120	2	
PUC6/1	6	4	120	37	51	1	
PUC6/2	6	4	120	37	120	2	
PUC6/3	6	4	120	37	185	3	
PUC8/2	8	5	150	47	140	2	
PUC8/3	8	5	150	47	210	3	
PUC8/5	8	5	150	47	345	5	
PUC4/1B	4	2.5	80	26	60	1	
PUC4/2B	4	2.5	80	26	120	2	
PUC6/1B	6	4	120	37	51	1	
PUC6/2B	6	4	120	37	120	2	
PUC6/3B	6	4	120	37	185	3	
PUC8/2B	8	5	150	47	140	2	
PUC8/3B	8	5	150	47	210	3	
PUC8/5B	8	5	150	47	345	5	
PUC4/1CB	4	2.5	80	26	60	1	
PUC4/2CB	4	2.5	80	26	120	2	
PUC6/1CB	6	4	120	37	51	1	
PUC6/2CB	6	4	120	37	120	2	
PUC6/3CB	6	4	120	37	186	3	
PUC8/2CB	8	5	150	47	140	2	
PUC8/3CB	8	5	150	47	210	3	
PUC8/5CB	8	5	150	47	345	5	
Tech Sheet 3134							

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Imperial Polyurethane Tube



25 Metre Coils, Black

5030	OD	ID	ID mm
2021-5265	1/8"	1/6"	2
2021-5273	1/4"	1/8"	4
2021-5281	5/16"	3/16"	5
2021-5299	3/8"	1/4"	6.5



100 Metre Coils, Black

5030	OD	ID	ID mm
2021-5224	1/8"	1/6"	2
2021-5232	1/4"	1/8"	4
2021-5240	5/16"	3/16"	5
2021-5257	3/8"	1/4"	6.5

'Flexi-Braid' Tubing


"Flexi-Braid" inner-braided polyurethane hose offers an excellent alternative too much bulkier rubber and plastic hoses. Extremely lightweight and tough, it is ideal for either outdoor contractor use or indoor industrial use. **"Flexi-Braid"** retains its flexibility even in cold environments. Unlike other hoses that are made up of a separate core, braiding and cover, **"Flexi-Braid"** is extracted complete as a braided hose.

This integral piece construction eliminates the possibility of having the various layers separate due to constant expansion and contraction during pulsating operations, such as with staple or nail guns.

Flexi-Braid Advantages:

- Extremely flexible with a lively rubber like feel making it easier to rewind and handle.
- Broad temperature range (-20°C to + 80°C) and retains its flexibility even in sub-zero temperatures.
- Highly resistant to lubricating oils and greases that can damage PVC.
- UV stabilised for larger out door service.
- Extremely tough, it is the most abrasion resistant tube available.
- High flexural strength, it withstands the rigors of repeated flexing and tight bends..

Flexi-Braid Polyurethane Recoils




1/4" BSPT Swivel

5030	OD mm	ID mm	Working Length Metres
IBR10-50	10	6.5	5
IBR10-75	10	6.5	7.5
IBR12-50	12	8	5
IBR12-75	12	8	7.5
Tech Sheet 20345			

Flexi-Braid Polyurethane Braided Hose

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 15 bar (200 psi)



Blue, 25 Metre Coils

5030	OD mm	ID mm
BPU065/100B	10	6.5
BPU080/120B	12	8
BPU100/145B	14.5	10
Tech Sheet 20346		

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

POLYURETHANE ANTI-SPATTER TUBE & HOSE


Polyurethane Anti-spatter Tube

This PVC/Polyurethane, alloy tubing has been developed by taking 98A durometer polyurethane as the inner tube and jacketing it with a specially formulated flame retardant cover.
The jacket protects the tubing from incidental contact with weld spatter.

Features:
- UL-94 (V-0) Fire Resistance.
- High abrasion resistance.
- Non-Marking Cover.
- Good flexibility over a wide temperature range.
- Excellent fitting retention at elevated temperatures.

Applications:
- Transfer of Air & Water.
- Induction welding tubing lines.
- Transfer of deionised water.
- Robotic & Pneumatic Air Lines.
- Automotive assembly lines.

Temperature Range:
-40°C to +70°C



Anti-spatter Tube, 50 Metre Coils

0306	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar	Bend Radius mm
S604050MBU	6	4	Blue	159	11	20
S604050MGY	6	4	Grey	159	11	20
S604050MY	6	4	Yellow	159	11	20
S805050MBU	8	5	Blue	188	13	30
S805050MGY	8	5	Grey	188	13	30
S805050MY	8	5	Yellow	188	13	30
S128050MBU	12	8	Blue	145	10	45
S128050MGY	12	8	Grey	145	10	45
S128050MY	12	8	Yellow	145	10	45
Tech Sheet 20343						

Polyurethane Anti-spatter Recoil Hose

Temperature Range:
-40°C to +70°C

Safety factor of 3 to 1.



Blue, Anti-spatter Recoil Hose, 4 Metre Coils, 1/4" BSPT

0306	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar	Bend Radius mm
SC60404MBU	6	4	159	11	15
SC80504MBU	8	5	188	13	20
SC10654MBU	10	6.5	159	10	30
Tech Sheet 20344					

ambersil



For **Welding Sprays** see page **1577**

Fluid-Air Components Ltd

TUBE & HOSE CUTTERS

FT PRO

Tube & Hose Cutters



Nylon & Polyurethane Tube Cutter, 3mm-16mm

5010	Colour
KTC-1	Blue
Tech Sheet 3136	



LBS-25



LBS-120



LBS-63N

5100	To Suit Tube OD mm
LBS-25	3 - 25
LBS-120	6 - 42
LBS-63N	6 - 63



Metal

5100	To Suit Tube OD mm
27000216	2 - 12
27000825	4 - 28

Spare Blades (Per Piece)

5100	To Suit
27010216	27000216
27010825	27000825



Replacement Blade



Heavy-duty

9057	Description
TCUT0001	Up to 20mm Tube
TCUT0101	Replacement Blade up to 20mm



John Guest

Heavy-duty

1400	Description
JG-TSP	To Suit up to 22mm Pipe

Copper Tube Cutters



Standard Cutter

5100	To Suit OD mm
CTC1	3-28



Mini Cutter

5100	To Suit OD mm
CTC2	3-16

Automatic Tube Cutters

- Single action automatic tube cutting in tight locations.



5100	To Suit OD mm
88801	15
88802	22

Copper Tube Reamer



Internal/External Reamer for Tube

5070	To Suit OD mm
CTR1	3-36

TUBING

Crystal Clear Colour Tinted Polyether Polyurethane Tubing



25 Metre Rolls, Tinted Close Tolerance Flexible


1014	OD mm	ID mm	Colour
LE-1025U04R12	4	2.5	Green
LE-1025U04R13	4	2.5	Red
LE-1025U04R14	4	2.5	Blue
LE-1025U04R17	4	2.5	Orange
LE-1025U06R12	6	4	Green
LE-1025U06R13	6	4	Red
LE-1025U06R14	6	4	Blue
LE-1025U06R17	6	4	Orange
LE-1025U08R12	8	5.5	Green
LE-1025U08R13	8	5.5	Red
LE-1025U08R14	8	5.5	Blue
LE-1025U08R17	8	5.5	Orange
LE-1025U10R14	10	7	Blue
LE-1025U12R14	12	8	Blue
Tech Sheet 60547			

100 Metre Rolls, Tinted Close Tolerance Flexible

1014	OD mm	ID mm	Colour
LE-1100U04R12	4	2.5	Green
LE-1100U04R13	4	2.5	Red
LE-1100U04R14	4	2.5	Blue
LE-1100U04R17	4	2.5	Orange
LE-1100U06R12	6	4	Green
LE-1100U06R13	6	4	Red
LE-1100U06R14	6	4	Blue
LE-1100U06R17	6	4	Orange
LE-1100U08R12	8	5.5	Green
LE-1100U08R13	8	5.5	Red
LE-1100U08R14	8	5.5	Blue
LE-1100U08R17	8	5.5	Orange
LE-1100U10R14	10	7	Blue
LE-1100U12R14	12	8	Blue
Tech Sheet 60547			

Polyamide Fireproof High Resistance Tubing

Working Temperature:
-40°C to +100°C



100 Metre Coils

1014	OD mm	ID mm	Colour
LE-1100P04R00	4	2	Natural
LE-1100P04R01	4	2	Black
LE-1100P04R04	4	2	Blue
LE-1100P06R00	6	4	Natural
LE-1100P06R01	6	4	Black
LE-1100P06R04	6	4	Blue
LE-1100P08R00	8	6	Natural
LE-1100P08R01	8	6	Black
LE-1100P08R04	8	6	Blue
LE-1100P10R00	10	8	Natural
LE-1100P10R01	10	8	Black
LE-1100P10R04	10	8	Blue
LE-1100P12R00	12	9	Natural
LE-1100P12R01	12	9	Black
Tech Sheet 10658			

FT PRO®



For **Tube & Hose Cutters** see page **905**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TUBING

Advanced Polyethylene Tubing

- Suitable for a wide variety of uses in point of use water purification systems, industrial water treatment and drink dispense systems.
- Made from a high grade of polyethylene, the advanced PE tubing ensures the best balance between flexibility and pressure/temperature resistance.
- Resistant to a wide range of aggressive chemical agents.
- Available in nine colours.
- Black tubing is UV stabilized, making it resistant to direct ultraviolet sunlight and ideal for outdoor applications.
- Silicone free.

Working Temperature:
+34°F (1°C) to +203°F (95°C)



150 Metre Coils

1014	OD	ID	Colour
LE-1098Y56F00	1/4"	0.170"	Natural
LE-1098Y56F01	1/4"	0.170"	Black
LE-1098Y56F03	1/4"	0.170"	Red
LE-1098Y56F04	1/4"	0.170"	Blue
LE-1098Y60F00	3/8"	0.250"	Natural
LE-1098Y60F01	3/8"	0.250"	Black
LE-1098Y60F04	3/8"	0.250"	Blue

75 Metre Coils

1014	OD	ID	Colour
LE-1096Y62F00	1/2"	0.375"	Natural
LE-1096Y62F01	1/2"	0.375"	Black
LE-1096Y62F04	1/2"	0.375"	Blue

150 Metre Coils

1014	OD mm	ID mm	Colour
LE-1015Y06F00	6	4	Natural
LE-1015Y06F01	6	4	Black
LE-1015Y06F04	6	4	Blue
LE-1015Y08F00	8	5.75	Natural
LE-1015Y08F01	8	5.75	Black
LE-1015Y08F04	8	5.75	Blue
LE-1015Y10F00	10	7	Natural
LE-1015Y10F01	10	7	Black
LE-1015Y10F04	10	7	Blue

75 Metre Coils

1014	OD mm	ID mm	Colour
LE-1075Y12F00	4	2.5	Natural
LE-1075Y12F01	4	2.5	Black
LE-1075Y12F04	4	2.5	Blue



For **Parker Legris Fittings**
see pages **800-803**

Fluid-Air Components Ltd

TUBING


Polyether Polyurethane Tubing

The high flexibility of Legris flexible polyurethane tubing allows compact cabling where a small bend radius is required.

Legris flexible polyurethane tubing has a shore hardness 52°C and conforms to NFE 49.101 standard.

Polyether polyurethane tubing, for excellent resistanceto humidity and bacteriological aggressions.

Polyester polyurethane available on request.




25 Metre Rolls, Close Tolerance Flexible

1014	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
LE-1025U04R01	4	2.5	Black	145	10
LE-1025U04R04	4	2.5	Blue	145	10
LE-1025U04R08	4	2.5	Clear	145	10
LE-1025U05R08	5	3	Clear	160	11
LE-1025U06R01	6	4	Black	130	9
LE-1025U06R04	6	4	Blue	130	9
LE-1025U06R08	6	4	Clear	130	9
LE-1025U08R01	8	5.5	Black	116	8
LE-1025U08R04	8	5.5	Blue	116	8
LE-1025U08R08	8	5.5	Clear	116	8
LE-1025U10R01	10	7	Black	116	8
LE-1025U10R04	10	7	Blue	116	8
LE-1025U10R08	10	7	Clear	116	8
LE-1025U12R01	12	8	Black	130	9
LE-1025U12R04	12	8	Blue	130	9
LE-1025U12R08	12	8	Clear	130	9
LE-1025U14R0495	14	9.5	Blue	130	9
LE-1025U14R0895	14	9.5	Clear	130	9

Polyurethane Twin Tubing

- Twin tubing maintains the smooth surface of both tubes when separated and keeps the characteristics of their dimensions.
- Swift and easy assembly.
- Compactness of circuitry.
- Differentiation of circuits, via two colours.



25 Metre Coils

1012	OD mm	ID mm	Colour
LE-1420U04 11	4	2.5	Black/Black
LE-1420U04 44	4	2.5	Blue/Blue
LE-1420U04 41	4	2.5	Black/Blue
LE-1420U06 11	6	4	Black/Black
LE-1420U06 44	6	4	Blue/Blue
LE-1420U06 41	6	4	Black/Blue
LE-1420U08 41	8	5.5	Black/Blue

Anti-spark Tubing

- Anti-spark tubing is suitable for installations submitted to aggressive environments and provides resistance to spark projections. It is designed with a PVC sheath and semi-rigid nylon tubing and conforms to UL94V-0 standard.
- A special mark on the tube indicates the length to be stripped back to reach the shoulder of the fitting.



25 Metre Coils

1012	OD mm	ID mm	Bend Radius mm	Colour
LE-1025P06V01	6	4	20	Black
LE-1025P06V04	6	4	20	Blue
LE-1025P08V01	8	6	25	Black
LE-1025P08V04	8	6	25	Blue
LE-1025P10V01	10	8	32	Black
LE-1025P10V04	10	8	32	Blue
LE-1025P12V01	12	10	35	Black

100 Metre Coils

1012	OD mm	ID mm	Bend Radius mm	Colour
LE-1100P06V01	6	4	20	Black
LE-1100P08V01	8	6	25	Black
LE-1100P08V04	8	6	25	Blue

Anti-static Tubing

- Anti-static polyurethane tubing has a low surface resistance (103 ohms) and is designed to prevent accumulation of electrostatic charges.



100 Metre Coils

1012	OD mm	ID mm	Bend Radius mm
LE-1100U03A01	3	1.5	8
LE-1100U06A01	6	4	15
LE-1100U08A01	8	5.5	25
LE-1100U10A01	10	7	35

Stripping Tool

- For use on anti-spark tube.



1012
LE-60007100

Fluid-Air Components Ltd

Translucent Silicone Tubing

Translucent silicone tube is non-toxic and biologically inert. it is FDA, BGA, WRC and NWC approved for drug and medical use, and meets European Pharmacopoeia class VI. Outstanding temperature resistance from -60°C to +200°C, it can withstand repeated autoclaving.

Excellent chemical resistance (contact technical department for advice).

Not suitable for high pressure applications.

Working Temperature:
-60°C to +200°C



10 Metre Coils

5012	OD mm	ID mm	Wall Thickness mm
TST-04/020	2	4	1
TST-06/040	4	6	1
TST-08/050	5	8	1.5
TST-10/080	8	10	1
TST-12/080	8	12	2

FEP Tubing



10 Metre Coils

5012	OD mm
4500400100	6
4500600100	8
Tech Sheet 20216	

PFA Tubing



10 Metre Coils

5012	OD mm	OD
4601000100	12	-
4600952159	-	1/2"
Tech Sheet 60553		

PTFE Tubing (Polytetrafluoroethylene)

The unique properties of PTFE are excellent. Enjoying a non-stick/low friction release property and a very wide temperature range, it is virtually inert to all known chemicals and solvents. It exhibits extremely good electrical insulation properties and good weatherability. All these characteristics combined make PTFE the ideal material for innumerable applications.

Please note: no recommended burst pressures/working pressures due to hose being unreinforced.



10 Metre Coils

5012	ID mm	OD mm	Wall Thickness mm
TPTFE-04/025-10M	2.5	4	0.75
TPTFE-06/040-10M	4	6	1
TPTFE-08/060-10M	6	8	1
TPTFE-10/080-10M	8	10	1
TPTFE-12/010-10M	10	12	1
Tech Sheet 1379			

30 Metre Coils

5012	ID mm	OD mm	Wall Thickness mm
TPTFE-04/025-30M	2.5	4	0.75
TPTFE-06/040-30M	4	6	1
TPTFE-08/060-30M	6	8	1
TPTFE-10/080-30M	8	10	1
TPTFE-12/010-30M	10	12	1
Tech Sheet 1379			

LDP Low Density Polyethylene Tube



30 Metre Coils

5040	ID mm	OD mm	Max Pressure PSI	Max Pressure Bar
LDP04/025	4	2.5	200	13.5
LDP05/030	5	3	200	13.5
LDP06/040	6	4	185	12.5
LDP08/060	8	6	165	11
LDP10/080	10	8	150	10
LDP12/100	12	10	90	6

Customers who bought from this page also purchased...

Parker RECTUS

Pneumatic Quick Release Series 21 Worldwide Profile Thermoplastic Couplings



...see pages **347-349**

FAC Fluid-Air Components Ltd

Air Brake Tubing DIN 74324

Working Temperature:
-20°C to +70°C



- Manufactured from heat and light stabilised polyamide. This tube has excellent low density, low water absorption, physical properties and dimensions relatively constant even during humidity changes.
- Other colours available on request, minimum order of 20 x 30 metre coils.

30 Metre Coils


5040	OD mm	ID mm	Colour	Max Pressure Bar
AB4230	4	2	Black	45
AB6430	6	4	Black	27
AB10730	10	7	Black	19
AB12930	12	9	Black	19
AB161230	16	12	Black	19
AB181430	18	14	Black	17

SIRIT AIR BRAKE FITTINGS



For **Air Brake Fittings**
see pages **887-889**

Nylon 12 Air Brake Coils, DIN 73378, SAE J 844 Type B



- Low moisture absorption.
- Excellent resistance to a wide range of chemicals.

Working Temperature:
-40°C to +80°C

Red, Emergency Line, 1/2" BSPT

0306	ID mm	OD mm	Working Length Metres	Rotation
AB129035R	12	9	3.5	16
AB129050R	12	9	5	22
Tech Sheet 20391				

Blue, Auxiliary Line, 1/2" BSPT

0306	ID mm	OD mm	Working Length Metres	Rotation
AB129035B	12	9	3.5	16
AB129050B	12	9	5	22
Tech Sheet 20391				

Yellow, Service Line, 1/2" BSPT

0306	ID mm	OD mm	Working Length Metres	Rotation
AB129035Y	12	9	3.5	16
AB129050Y	12	9	5	22
Tech Sheet 20391				

Fluid-Air Components Ltd

TUBING


For the full range and more information, please contact one of our sales team.

POLYURETHANE TUBING

FESTO

Features

- Extremely flexible polyurethane tubing
- High resistance to stress cracks
- Suitable for use with energy chains
- Food safe - FDA Compliant
- Plastic tubing PUN-H-F
- Polyurethane
- High resistance to microbes and hydrolysis
- Clean room-compatible combination with fitting NPKA
- Operating medium: compressed air, vacuum and water



For food safety certificates, see www.festo.com/certificates/PUN_H_F

Product Description

PUN - **H** - **6X1** - **TSW**

- PUN: Standard Tubing
- H: Hydrolysis Resistant Material
- 6X1: OD x Wall Thickness mm
- TSW: Colour

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

POLYURETHANE TUBING


FESTO

Hydrolysis-resistant

- Extremely flexible polyurethane tubing
- Suitable for use with energy chains
- Operating media: compressed air, vacuum and water

Working Temperature:
-35°C to +60°C

Maximum Working Pressure: 10 bar



50 Metres

0011	OD mm	ID mm	Colour	Manufacturer's Code
197390	4	2.6	Black	PUN-H-4X0,75-SW
8048673	4	2.6	Translucent Black	PUN-H-4X0,75-TSW
8048675	4	2.6	Translucent Red	PUN-H-4X0,75-TRT
197383	4	2.6	Blue	PUN-H-4X0,75-BL
197376	4	2.6	Natural	PUN-H-4X0,75-NT
558278	4	2.6	Silver	PUN-H-4X0,75-SI
8048677	4	2.6	Translucent Green	PUN-H-4X0,75-TGN
8048679	4	2.6	Translucent Yellow	PUN-H-4X0,75-TGE
8048671	4	2.6	Translucent Blue	PUN-H-4X0,75-TBL
8048683	6	4	Translucent Black	PUN-H-6X1-TSW
197384	6	4	Blue	PUN-H-6X1-BL
8048681	6	4	Translucent Blue	PUN-H-6X1-TBL
197377	6	4	Natural	PUN-H-6X1-NT
558279	6	4	Silver	PUN-H-6X1-SI
197391	6	4	Black	PUN-H-6X1-SW
8048685	6	4	Translucent Red	PUN-H-6X1-TRT
8048687	6	4	Translucent Green	PUN-H-6X1-TGN

0011	OD mm	ID mm	Colour	Manufacturer's Code
8048689	6	4	Translucent Yellow	PUN-H-6X1-TGE
8048693	8	5.7	Translucent Black	PUN-H-8X1,25-TSW
8048691	8	5.7	Translucent Blue	PUN-H-8X1,25-TBL
8048695	8	5.7	Translucent Red	PUN-H-8X1,25-TRT
8048697	8	5.7	Translucent Green	PUN-H-8X1,25-TGN
8048699	8	5.7	Translucent Yellow	PUN-H-8X1,25-TGE
8048705	10	7	Translucent Red	PUN-H-10X1,5-TRT
8048707	10	7	Translucent Green	PUN-H-10X1,5-TGN
8048709	10	7	Translucent Yellow	PUN-H-10X1,5-TGE
8048703	10	7	Translucent Black	PUN-H-10X1,5-TSW
8048701	10	7	Translucent Blue	PUN-H-10X1,5-TBL
8048715	12	8	Translucent Red	PUN-H-12X2-TRT
8048717	12	8	Translucent Green	PUN-H-12X2-TGN
8048719	12	8	Translucent Yellow	PUN-H-12X2-TGE
8048713	12	8	Translucent Black	PUN-H-12X2-TSW
8048711	12	8	Translucent Blue	PUN-H-12X2-TBL
Tech Sheet 70006				


FAC
Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

Metric Flexible Nylon Tubing, Type NT (to BS5409)

Working Temperature
-10°C to +80°C

Tube is not suitable for use with water or in high humidity environments.

- ✔ **U.V. stable.**
- ✔ **Silicone free.**
- ✔ **Abrasion resistant.**
- ✔ **Manufactured from quality grade nylon granules.**



Other colours and lengths available on request
The properties of this tube make it ideal for use in pneumatic control systems. (Ideally suited for use with push-in fittings).

30 Metre Coils

5010	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
NTM04/030	4	3		300	21
NTM04/025	4	2.5		400	28
NTM04/025N	4	2.5		400	28
NTM04/025B	4	2.5		400	28
NTM04/025G	4	2.5		400	28
NTM04/025R	4	2.5		400	28
NTM04/025Y	4	2.5		400	28
NTM05/030	5	3		400	28
NTM05/030N	5	3		400	28
NTM05/030B	5	3		400	28
NTM05/030G	5	3		400	28
NTM05/030R	5	3		400	28
NTM05/030Y	5	3		400	28
NTM06/040	6	4		350	24
NTM06/040N	6	4		350	24
NTM06/040B	6	4		350	24
NTM06/040G	6	4		350	24
NTM06/040R	6	4		350	24
NTM06/040Y	6	4		350	24
NTM08/060	8	6		350	24
NTM08/060N	8	6		350	24
NTM08/060B	8	6		350	24
NTM08/060G	8	6		350	24
NTM08/060R	8	6		350	24
NTM08/060Y	8	6		350	24
NTM08/055	8	5.5		350	24

30 Metre Coils

5010	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
NTM08/055N	8	5.5		350	24
NTM10/070	10	7		300	21
NTM10/070N	10	7		300	21
NTM10/070B	10	7		300	21
NTM10/070G	10	7		300	21
NTM10/070R	10	7		300	21
NTM10/070Y	10	7		300	21
NTM10/080	10	8		220	15
NTM10/080N	10	8		220	15
NTM10/080B	10	8		220	15
NTM10/080G	10	8		220	15
NTM10/080R	10	8		220	15
NTM10/080Y	10	8		220	15
NTM12/090	12	9		250	17
NTM12/090N	12	9		250	17
NTM12/090B	12	9		250	17
NTM12/090G	12	9		250	17
NTM12/090R	12	9		250	17
NTM12/090Y	12	9		250	17
NTM12/100	12	10		200	14
NTM12/100N	12	10		200	14
NTM12/100R	12	10		200	14
NTM14/110	14	11		250	17
NTM14/110N	14	11		250	17
NTM15/120	15	12		200	14
NTM16/130	16	13		200	14
NTM18/140	18	14		200	14
NTM22/170	22	17		180	17


Tech Sheet 3136

100 Metre Coils

5010	OD mm	ID mm	Colour	PSI	Max Pressure Bar
NTM06/040-100	6	4		350	24
NTM06/040N-100	6	4		350	24
NTM06/040B-100	6	4		350	24
NTM06/040G-100	6	4		350	24
NTM06/040R-100	6	4		350	24
NTM06/040Y-100	6	4		350	24
NTM08/060-100	8	6		350	24
NTM08/060N-100	8	6		350	24
NTM08/060B-100	8	6		350	24
NTM10/080-100	10	8		220	15
NTM10/080N-100	10	8		220	15
NTM10/080B-100	10	8		220	15

Tech Sheet 3136

Nylon & Polyurethane Tube Cutter



3mm-16mm

5010	Colour
KTC-1	

Tech Sheet 3136

FTPRO

For **Push-in Fittings** see pages **767-791**



FAC Fluid-Air Components Ltd

FT PRO® Nylon Tubing

REACh ✓ RoHS

Imperial Flexible Nylon Tubing, (to BS5409)

Working Temperature
-10°C to +80°C

Tube is not suitable for use with water or in high humidity environments.


Specifications

Standard Coil Length:
30 Metres

(other colours and lengths available on request).

Manufactured from top quality crystal clear "virgin" nylon compound. This hose is ideal for factory airlines, fluid systems and many industrial applications.
The hose is resistant to a wide range of chemicals (please consult our Business Development Team for further details).

✔ **U.V. stable.** ✔ **Silicone free.** ✔ **Abrasion resistant.**



30 Metre Coils

5010	OD	ID	Colour	Max Pressure PSI	Max Pressure Bar
NTI18/075	1/8"	0.075		300	21
NTI532/096	5/32"	0.096		250	17
NTI316/117	3/16"	0.117		300	21
NTI316/117N	3/16"	0.117		300	21
NTI14/170	1/4"	0.17		300	21
NTI14/170B	1/4"	0.17		300	21
NTI14/170G	1/4"	0.17		300	21
NTI14/170R	1/4"	0.17		300	21
NTI14/170Y	1/4"	0.17		300	21
NTI14/170N	1/4"	0.17		300	21
NTI516/212	5/16"	0.212		250	17
NTI516/212B	5/16"	0.212		250	17
NTI516/212R	5/16"	0.212		250	17
NTI516/212N	5/16"	0.212		250	17
NTI38/250	3/8"	0.25		250	17

5010	OD	ID	Colour	Max Pressure PSI	Max Pressure Bar
NTI38/250B	3/8"	0.25		250	17
NTI38/250G	3/8"	0.25		250	17
NTI38/250R	3/8"	0.25		250	17
NTI38/250Y	3/8"	0.25		250	17
NTI38/250N	3/8"	0.25		250	17
NTI12/375	1/2"	0.375		250	17
NTI12/375B	1/2"	0.375		250	17
NTI12/375G	1/2"	0.375		250	17
NTI12/375R	1/2"	0.375		250	17
NTI12/375Y	1/2"	0.375		250	17
NTI12/375N	1/2"	0.375		250	17
NTI34/594	3/4"	0.594		200	14
NTI58/500	5/8"	0.5		200	14
NTI1/813	1"	0.813		180	12


Tech Sheet 20895

Fluid-Air Components Ltd

Metric Flexible Nylon Tubing, (to BS5409, DIN 73378 & ISO 7628)

Working Temperature
-40°C to +80°C

Manufactured from extremely high grade nylon granules, this hose gives almost total resistance to abrasion and many more chemicals including dilute acid and alkaline.
The properties of this tube make it ideal for use in pneumatic control systems, fuel lines, lubrication and also within the food, beverage and brewing industry (ideally suited for use with push-in fittings).
Working pressure will differ at higher temperatures.



30 Metre Coils

0306	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
BNTM03/015	3	1.5		200	13
BNTM04/2	4	2		350	24
BNTM04/025	4	2.5		400	27
BNTM04/025N	4	2.5		400	27
BNTM04/025B	4	2.5		400	27
BNTM04/025G	4	2.5		400	27
BNTM04/025R	4	2.5		400	27
BNTM05/030	5	3		400	27
BNTM05/030N	5	3		400	27
BNTM05/030B	5	3		400	27
BNTM060/030	6	3		350	24
BNTM06/040	6	4		350	24
BNTM06/040N	6	4		350	24
BNTM06/040B	6	4		350	24
BNTM06/040G	6	4		350	24
BNTM06/040R	6	4		350	24
BNTM06/040Y	6	4		350	24
BNTM08/060	8	6		350	24
BNTM08/060N	8	6		350	24
BNTM08/060B	8	6		350	24
BNTM08/060G	8	6		350	24
BNTM08/060R	8	6		350	24
BNTM08/060Y	8	6		350	24
BNTM10/070	10	7		300	20
BNTM10/070N	10	7		300	20
BNTM10/070B	10	7		300	20
BNTM10/070R	10	7		300	20
BNTM10/080	10	8		220	15
BNTM10/080N	10	8		220	15
BNTM10/080B	10	8		220	15
BNTM10/080R	10	8		220	15
BNTM12/090	12	9		250	17
BNTM12/090N	12	9		250	17
BNTM12/090B	12	9		250	17
BNTM12/090R	12	9		250	17
BNTM12/100	12	10		200	13
BNTM12/100N	12	10		200	13
BNTM14/110	14	11		250	17
BNTM14/110N	14	11		250	17

Tech Sheet 1386

100 Metre Coils

0306	OD mm	ID mm	Colour	Max Pressure PSI	Max Pressure Bar
BNTM04/025-100	4	2.5		400	27
BNTM05/030-100	5	3		400	27
BNTM06/040-100	6	4		350	24
BNTM06/040N-100	6	4		350	24
BNTM06/040B-100	6	4		350	24
BNTM06/040G-100	6	4		350	24
BNTM06/040R-100	6	4		350	24
BNTM06/040Y-100	6	4		350	24
BNTM08/060-100	8	6		350	24
BNTM08/060N-100	8	6		350	24
BNTM08/060B-100	8	6		350	24
BNTM08/060G-100	8	6		350	24
BNTM08/060R-100	8	6		350	24
BNTM08/060Y-100	8	6		350	24
BNTM10/080-100	10	8		220	15
BNTM10/080N-100	10	8		220	15
BNTM10/080B-100	10	8		220	15
BNTM10/080R-100	10	8		220	15

Tech Sheet 1386

- **High resistance to moisture absorption.**
- **Suitable for use in air brake systems.**
- **Suitable for fuel and lubrication systems. 4 to 1 safety factor.**
- **Very stable in moisture type atmospheres.**

FT PRO® Nylon Recoil Hoses

REACh ✓ RoHS

Nylon 12 Coil Hose with Tails

Working Temperature
-40°C to +80°C


Applications:

- Fuel lines.
- Oil lines.
- Petrol tank breather lines.
- Pneumatic lines.
- Bleed lines.
- Brake controls.

✔ **Low moisture absorption.**

✔ **Excellent resistance to a wide range of chemicals.**

✔ **Safety factor of 3 to 1.**





BSPT

0306	ID mm	OD mm	Working Length Metres	Thread	Colour
N12C60402.5MB	4	6	2.5	1/4"	
N12C60405MB	4	6	5	1/4"	
N12C604010MB	4	6	10	1/4"	
N12C604015MB	4	6	15	1/4"	
N12C60402.5MR	4	6	2.5	1/4"	
N12C60405MR	4	6	5	1/4"	
N12C604010MR	4	6	10	1/4"	
N12C604015MR	4	6	15	1/4"	
N12C80602.5MB	6	8	2.5	1/4"	
N12C80605MB	6	8	5	1/4"	
N12C806010MB	6	8	10	1/4"	
N12C806015MB	6	8	15	1/4"	
N12C80602.5MR	6	8	2.5	1/4"	
N12C80605MR	6	8	5	1/4"	
N12C806010MR	6	8	10	1/4"	
N12C806015MR	6	8	15	1/4"	
N12C100802.5MB	8	10	2.5	1/4"	
N12C100805MB	8	10	5	1/4"	
N12C1008010MB	8	10	10	1/4"	
N12C1008015MB	8	10	15	1/4"	

0306	ID mm	OD mm	Working Length Metres	Thread	Colour
N12C100802.5MR	8	10	2.5	1/4"	
N12C100805MR	8	10	5	1/4"	
N12C1008010MR	8	10	10	1/4"	
N12C1008015MR	8	10	15	1/4"	
N12C120902.5MB	9	12	2.5	3/8"	
N12C120905MB	9	12	5	3/8"	
N12C1209010MB	9	12	10	3/8"	
N12C1209015MB	9	12	15	3/8"	
N12C120902.5MR	9	12	2.5	3/8"	
N12C120905MR	9	12	5	3/8"	
N12C1209010MR	9	12	10	3/8"	
N12C1209015MR	9	12	15	3/8"	
N12C120902.5MB12	9	12	2.5	1/2"	
N12C120905MB12	9	12	5	1/2"	
N12C1209010MB12	9	12	10	1/2"	
N12C1209015MB12	9	12	15	1/2"	
N12C120902.5MR12	9	12	2.5	1/2"	
N12C120905MR12	9	12	5	1/2"	
N12C1209010MR12	9	12	10	1/2"	
N12C1209015MR12	9	12	15	1/2"	

Tech Sheet 3138

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

Food Grade Semi-rigid Nylon Tubing



Working Temperature
-40°C to +110°C continuous
(+140°C intermittent)

30 Metre Coils, Imperial

5015	ID	OD	Max Pressure PSI	Max Pressure Bar
SRN18	0.075"	1/8"	967	67
SRN316	0.117"	3/16"	868	60
SRN14	0.170"	1/4"	683	47
SRN516	0.212"	5/16"	684	47
SRN38	0.250"	3/8"	725	50
SRN12	0.375"	1/2"	483	33
SRN58	0.500"	5/8"	363	25
Tech Sheet 67981				

30 Metre Coils, Metric

5015	ID mm	OD mm	Max Pressure PSI	Max Pressure Bar
SRN4	2.5	4	870	60
SRN5	3	5	967	67
SRN6	4	6	725	50
SRN8	6	8	483	34
SRN10	8	10	363	25
SRN1012	10	12	290	20
SRN15	12	15	363	25
Tech Sheet 67981				


NYLON TUBING

Parker legris

Semi-rigid Nylon Multitube Close Tolerance

Legris semi-rigid nylon multitube is suited to pneumatic circuits submitted to external aggression.
Its PVC sheath is resistant to abrasion, fire, caustic fluids, oils, alcohol etc.
The special design sheath and spiral assembly ensure a small bend radius for compact and flexible cabling.
For fast identification of circuits, tubes are numbered from 1 to 12 and 6 colours are available.

Note: Also available in 25 metre and 50 metre coils.



10 Metre Coils

1012	Tube Quantity	ID mm	OD mm
LE-1010P04 00M04	4	2.7	4
LE-1010P04 00M07	7	2.7	4
LE-1010P06 00M04	4	4	6
LE-1010P06 00M07	7	4	6
LE-1010P08 00M02	2	6	8

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

LLDPE & SYNFLEX TUBE

Tubing LLDPE



Maximum Working Temperature:
180°F / 80°C (temperature and pressure variations apply*)

Strong but flexible, LLDPE tubing is suitable for use with super Speedfit push in fittings and virtually all standard tubing connectors.
The John Guest PE range of plastic tubing is produced in linear low density polyethylene for cold and intermittent hot water applications.

NOTE:
LLDPE IS NOT RECOMMENDED FOR HIGH PRESSURE COMPRESSED AIR SYSTEMS 10 bar+, MINERAL OILS, GASES AND FUELS.

- Other colours available white, green, yellow, orange and violet.

Minimum order 500m. POA.

100 Metre Coils

1400	OD mm	ID mm	Colour
PE-04025-0100M-N	4	2.5	Natural
PE-04025-0100M-B	4	2.5	Blue
PE-04025-0100M-E	4	2.5	Black
PE-0604-0100M-N	6	4	Natural
PE-0604-0100M-B	6	4	Blue
PE-0604-0100M-R	6	4	Red
PE-0604-0100M-E	6	4	Black
PE-0806-100M-N	8	6	Natural
PE-0806-100M-B	8	6	Blue
PE-0806-100M-E	8	6	Black
PE-1007-100M-N	10	7	Natural
PE-1007-100M-B	10	7	Blue
PE-1007-100M-R	10	7	Red
PE-1007-100M-E	10	7	Black
PE-1209-100M-B	12	9	Blue
PE-1209-100M-R	12	9	Red
PE-1209-100M-E	12	9	Black
Tech Sheet 2057			

Tubing



Application: Synflex 1300 is a unique composite-wall tubing designed for pneumatic instrument control systems. Its fully bonded polyethylene/aluminium construction combines the advantages of both metal and plastic tubing.
Chemical Resistance: The outer, high density polyethylene layer is impervious to most chemical-containing atmospheres and enables Synflex 1300 to out perform practically all types of unprotected metal tubing.

Metric, 25 Metre Coils

5074	OD mm
MAL6-25	6
MAL8-25	8
MAL10-25	10
MAL12-25	12
Tech Sheet 593	

Imperial, 25 Metre Coils

5074	OD
MAL1/4-25-IMP	1/4"
Tech Sheet 593	

Imperial, 75 Metre Coils

5074	OD
MAL1/4-75-IMP	1/4"
MAL3/8-75-IMP	3/8"
MAL1/2-75-IMP	1/2"
Tech Sheet 593	

Customers who bought from this page also purchased...



Pneumatic Quick Release
Series 25 Couplings see pages **359-361**

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 7

Valves & Actuation

7.01 Industrial Ball Valves 919-937

7.02 WRAS & Gas Ball Valves 938-945

7.03 Stainless Steel & Carbon Steel Ball Valves 946-956

7.04 Gate Valves 957-959

7.05 Check Valves 960-966

7.06 Hygienic, Wafer & Lugged Butterfly alves 967-971

7.07 Y Strainers 972-974

7.08 Globe Valves 975-977

7.09 Balancing Valves, Air Vents & Steam Traps 978-979

7.10 Pressure Reducing Valves 980

7.11 Instrumentation Manifolds 981

7.12 Needle Valves 982-983

7.13 Pressure Relief Valves 984-992

7.14 Actuation 993-1014

7.15 Actuators & Accessories 1015-1023

7.16 General Purpose Solenoid Valves 1024-1047

7.17 Angle Seat Valves 1048-1055

7.18 Valves Accessories 1056-1060

SECTION 7

7.01 Industrial Ball Valves — 922-937

- Lever Handle
- Wing Handle
- Full Bore
- Mini
- High Pressure
- Drain
- Bibcock
- Standard In-line
- Direct Mount



7.02 WRAS & Gas Ball Valves — 938-945

- Lever Handle
- Wing Handle
- Full Bore
- Mini
- Compression Ended
- Super Filter
- Dual Sealing
- Lockable
- Direct Mount



7.03 Stainless Steel & Carbon Steel Ball Valves — 946-956

- Lever Handle
- Wing Handle
- Full Bore
- Mini
- ISO Pad Mount
- Fire Safe
- Hygenic
- Flanged
- Direct Mount



7.04 Gate Valves — 957-959

- Heavy-duty
- Flanged
- PN10, PN16, PN20
- ANSI150
- Metal Seat
- Resilient Seat
- EPDM Seat
- Class 800
- Socket Weld



7.05 Check Valves — 960-966

- Spring
- Swing
- PN16, PN20
- ANSI150
- Metal Seat
- Rubber Seat
- Flanged
- Double Union
- Strainers



7.06 Hygienic, Wafer & Lugged Butterfly alves — 967-971

- Hygenic
- Wafer Pattern
- Lugged Pattern
- Weld End
- Clamp End
- RJT



7.07 Y Strainers — 972-974

- Brass
- Stainless Steel
- Cast Iron
- Flanged PN16
- Flanged ANSI150



7.08 Globe Valves — 975-977

- Bronze
- Stainless Steel
- Cast Iron
- Carbon
- Ductile Iron
- Carbon Steel
- Flanged PN16
- Flanged PN40
- Flanged ANSI150



7.09 Balancing Valves, Air Vents & Steam Traps — 978-979

- Fixed/Variable Orific
- Flanged PN16
- Test Points
- Auto Air Vent
- Air Eliminators
- 3 Way Boiler Vent Valves



Fluid-Air Components Ltd

7.10 Pressure Reducing Valves — 980

- Brass Pressure Reducing Valves
- Type 143
- Type 243



7.11 Instrumentation Manifolds — 981

- Manifold Valves
- 2/3 Valve
- Pipe to Pipe
- Remote Mount



7.12 Needle Valves — 982-983

- Brass
- Stainless Steel
- 3,000/6,000/ 10,000 psi Rated
- Mini



7.13 Pressure Relief Valves — 984-992

- Series 6000
- Compact Relief Valves
- Type 1776
- Safety Relief Valves
- Combined Pressure & Temperature



7.14 Actuation — 993-1014

- Ball Valves/Wafer Pattern/ Lugged & Tapped Butterfly Valves fitted with a Pneumatic Actuator or a Electric Actuator
- Full Bore
- Flanged
- 3 Way
- Fire Safe
- Hygienic
- Actuated Knife Gate Valves



7.15 Actuators & Accessories — 1015-1023

- Pneumatic/Electric Actuators
- Position Indicator
- Electric Actuator Kits
- Mounting Brackets
- Pilot Accessories



7.16 General Purpose Solenoid Valves — 1024-1047

- Automatic Drain Valves
- Coils
- Plugs
- Timers
- Pre-wired Moulded Solenoid LED DIN Plug Connectors
- ZS Series
- Electrical Socket Connectors



7.17 Angle Seat Valves — 1048-1055

- Angle Seat Valves
- Pinch Valves
- Piston Valves
- Banjo Solenoid Valves
- Pressure Switches
- V.I.P. Axial Flow Valves



7.18 Valves Accessories — 1056-1060

- Control Valves
- Filters
- Water Valves
- Drain Cock & Bleeder Valves
- Drain Ball Valves & Pump Connectors
- Float Valves
- Spring Auto
- Self Close Pour Tap Valves



BALL VALVES

- Full bore
- Long thread
- Flat steel handle
- Seal material PTFE

Working Temperature
-15°C to +120°C

Maximum Working Pressure:
25 bar

Red Steel Long Handle



Female x Female, BSPP

0109	Thread
2023-0439	1/4"
2023-0447	3/8"
2023-0454	1/2"
2023-0462	3/4"
2023-0470	1"
2023-0488	1.1/4"
2023-0496	1.1/2"
2023-0504	2"
2023-0512	2.1/2"
2023-0520	3"
2023-0538	4"
Tech Sheet 837	



Male x Female, BSPP

0109	Thread
2024-1808	1/4"
2024-1816	3/8"
2024-1824	1/2"
2024-1832	3/4"
2024-1840	1"
2024-1857	1.1/4"
2024-1865	1.1/2"
2024-1873	2"
Tech Sheet 790	

Blue Steel Long Handle



Female x Female, BSPP

0109	Thread
2042-5336	1/4"
2042-5337	3/8"
2042-5338	1/2"
2042-5339	3/4"
2042-5340	1"
2042-5341	1.1/4"
2042-5342	1.1/2"
2042-5343	2"
2042-5344	2.1/2"
2042-5345	3"
2042-5346	4"
Tech Sheet 837	



Male x Female, BSPP

0109	Thread
2064-7889	1/4"
2064-7897	3/8"
2064-7905	1/2"
2064-7913	3/4"
2064-7921	1"
2064-7939	1.1/4"
2064-7947	1.1/2"
2064-7954	2"
Tech Sheet 790	

Green Steel Long Handle



Female x Female, BSPP

0109	Thread
2046-1695	1/4"
2046-1703	3/8"
2046-1711	1/2"
2046-1729	3/4"
2046-1737	1"
2046-1745	1.1/4"
2046-1752	1.1/2"
2046-1760	2"
Tech Sheet 837	



Male x Female, BSPP

0109	Thread
2064-7962	1/4"
2064-7970	3/8"
2064-7988	1/2"
2064-7996	3/4"
2064-8002	1"
Tech Sheet 790	

Fluid-Air Components Ltd

Brass Ball Valves, Full Bore

- Long thread
- Seal material PTFE

Working Temperature: -10°C to +60°C

Maximum Working Pressure: 25 bar



Female x Female, BSPP

0109	Thread
2024-1915	1/4"
2024-1923	3/8"
2024-1949	1/2"
2024-1964	3/4"
2024-1980	1"
Tech Sheet 1763	

Working Temperature: -10°C to +60°C


Maximum Working Pressure: 25 bar



Male x Female, BSPP

0109	Thread
2024-2079	1/4"
2024-2087	3/8"
2024-2095	1/2"
2024-2103	3/4"
2024-2111	1"
Tech Sheet 1763	

Working Temperature: -15°C to +120°C



Female x Female, BSPP, Lever Handle

0906	Thread	Max Pressure bar
BV90-14	1/4"	40
BV90-38	3/8"	40
BV90-12	1/2"	25
BV90-34	3/4"	25
BV90-1	1"	25
BV90-114	1.1/4"	25
BV90-112	1.1/2"	25
BV90-2	2"	25
Tech Sheet 10023		

Light Model Brass Ball Valves

- Lightweight, low pressure brass ball valve
- Suitable for domestic water services, heating, air conditioning and compressed air systems

Working Temperature: -15°C to +120°C

Maximum Working Pressure: 25 bar



Female x Female, BSPP, Lever Handle

0109	Thread
LMBV-12	1/2"
LMBV-34	3/4"
LMBV-1	1"
LMBV-114	1.1/4"
LMBV-112	1.1/2"
LMBV-2	2"
Tech Sheet 10157	

HAITIMA




stainless steel

For **Stainless Steel 2 Piece Ball Valves** see page **1289**

Heavy Model Brass Ball Valves, Full Bore

Working Temperature: 0°C to +90°C

Maximum Working Pressure: 40 bar




Female x Female, BSPP, Lever Handle

0906	Thread
HMBV-14	1/4"
HMBV-38	3/8"
HMBV-12	1/2"
HMBV-34	3/4"
HMBV-1	1"
HMBV-114	1.1/4"
HMBV-112	1.1/2"
HMBV-2	2"
HMBV-212	2.1/2"
HMBV-3	3"
HMBV-4	4"
Tech Sheet 60402	

Working Temperature: 0°C to +90°C

Maximum Working Pressure: 40 bar




Male x Female, BSPP, Long Female Thread, Lever Handle

0109	Thread
BV13-14	1/4"
BV13-38	3/8"
BV13-12	1/2"
BV13-34	3/4"
BV13-1	1"
Tech Sheet 68239	

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 40 bar



Male x Male, BSPP, High Pressure PN40, Lever Handle

0109	Thread
BV538-38	3/8"
BV538-12	1/2"
BV538-34	3/4"
BV538-1	1"
Tech Sheet 68240	

FAC Fluid-Air Components Ltd

BALL VALVES

Heavy Model Brass Ball Valves, Full Bore

Working Temperature: 0°C to +90°C

Maximum Working Pressure: 40 bar



Female x Female, BSPP, Long Thread, Wing Handle

0109	Thread
BV12-14W	1/4"
BV12-38W	3/8"
BV12-12W	1/2"
BV12-34W	3/4"
BV12-1W	1"
Tech Sheet 68238	



Male x Female, BSPP, Long Female Thread, Wing Handle

0109	Thread
BV13-14W	1/4"
BV13-38W	3/8"
BV13-12W	1/2"
BV13-34W	3/4"
BV13-1W	1"
Tech Sheet 68239	



Male x Male, BSPP, High Pressure Version, Wing Handle

0109	Thread
BV548-38	3/8"
BV548-12	1/2"
BV548-34	3/4"
BV548-1	1"
Tech Sheet 68240	

Right Angled, Brass Ball Valves, Full Bore

Working Temperature: -20°C to +150°C



Type BV07, Female x Female, BSPP

0090	Thread	Max Pressure Bar
BV07-12	1/2"	40
BV07-34	3/4"	30
BV07-1	1"	30
Tech Sheet 10035		

Ball Valve with Strainer, Full Bore

Working Temperature: -20°C to +150°C




Type BV620, Female x Female, BSPP

0090	Thread	Max Pressure Bar
BV620-12	1/2"	50
BV620-34	3/4"	40
Tech Sheet 10294		

3 Way Diverter, Ball Valves

Working Temperature: -20°C to +150°C

Maximum Working Pressure: 25 bar



3 Way BSPP, Female x Female x Female, T Port

0090	Thread
BV23-12	1/2"
BV23-34	3/4"
BV23-1	1"
Tech Sheet 10293	

Brass Ball Valves

Working Temperature: -10°C to +100°C

Maximum Working Pressure: 25 bar



3 Way BSPP, Bottom Entry Ball Valve, L Port


0906	Thread
534-14	1/4"
534-38	3/8"
534-12	1/2"
534-34	3/4"
534-1	1"
534-114	1.1/4"
534-112	1.1/2"
534-2	2"
534-3	3"
Tech Sheet 68242	

Looking for bespoke Flow Path Configuration?
Contact our technical team.

Fluid-Air Components Ltd

Full Bore, Ball Valves, Brass, Unplated

Working Temperature:
-20°C to +150°C



Type BV50, Female x Female, Lever Handle, NPT

0090	Thread	Max Pressure Bar
BV50-12NPT	1/2"	50
BV50-34NPT	3/4"	40
Tech Sheet 10030		

High Pressure 2 Way Valves, Brass

Working Temperature:
-10°C to +80°C

Maximum Working Pressure:
210 bar



Type BV210, Female x Female, BSPP

0090	Thread
BV210-38	3/8"
BV210-12	1/2"
BV210-34	3/4"
BV210-1	1"
Tech Sheet 10032	

Venting, Ball Valves

Working Temperature:
0°C to +60°C

Maximum Working Pressure:
12 bar



Female x Female, BSPP

0090	Thread
VBV-14	1/4"
VBV-38	3/8"
VBV-12	1/2"
VBV-34	3/4"
VBV-1	1"
Tech Sheet 10319	

Full Bore, Ball Valves, Extended Handle

Working Temperature:
-20°C to +130°C

Maximum Working Pressure:
100 bar



Type BV581, Female x Female, BSPP

0090	Thread
BV581-38	3/8"
BV581-12	1/2"
BV581-34	3/4"
BV581-1	1"
Tech Sheet 10298	

For **Aluminium Hose Tails** see page **1147**



For **Brass Compression Fittings** see pages **1197-1202**



Fluid-Air Components Ltd

BALL VALVES

Mini Ball Valves, Brass

- Polished chrome finish
- Seal material PTFE

Working Temperature: -10°C to +110°C

Maximum Working Pressure: 8 bar (120 psi)



Type MBV, Female x Female, Black Lever Handle, BSPP

0443	Thread
MBV18S	1/8"
MBV14S	1/4"
MBV38S	3/8"
MBV12S	1/2"
MBV34S	3/4"
Tech Sheet 834	



Type MBVM, Male x Female, Black Lever Handle, BSPP

0443	Thread
MBVM18S	1/8"
MBVM14S	1/4"
MBVM38S	3/8"
MBVM12S	1/2"
MBVM34S	3/4"
Tech Sheet 834	



Type MBV, Female x Female, Red Lever Handle, BSPP

0443	Thread
MBV18	1/8"
MBV14	1/4"
MBV38	3/8"
MBV12	1/2"
MBV34	3/4"
Tech Sheet 834	



Type MBVM, Male x Female, Red Lever Handle, BSPP

0443	Thread
MBVM18	1/8"
MBVM14	1/4"
MBVM38	3/8"
MBVM12	1/2"
MBVM34	3/4"
Tech Sheet 834	

Mini Ball Valves, Brass

Working Temperature: -20°C to +150°C

Maximum Working Pressure: 15 bar (220 psi)



Type MVS, Female x Female, Screwdriver Slot, BSPP

0090	Thread
MVS-14	1/4"
MVS-38	3/8"
MVS-12	1/2"
Tech Sheet 10033	



Type MVSM, Male x Female, Screwdriver Slot, BSPP

0090	Thread
MVSM-18	1/8"
MVSM-14	1/4"
MVSM-38	3/8"
MVSM-12	1/2"
Tech Sheet 10034	

BALL VALVES

High Pressure Mini Ball Valves

- Nickel plated brass
- Conforms to EN 12164

Working Temperature: -20°C to +90°C

Maximum Working Pressure: 30 bar



Female x Female, BSPP

0358	Thread
BV35-18	1/8"
BV35-14	1/4"
BV35-38	3/8"
BV35-12	1/2"
Tech Sheet 60394	



Male x Female, BSPP

0358	Thread
BV35-18M	1/8"
BV35-14M	1/4"
BV35-38M	3/8"
BV35-12M	1/2"
Tech Sheet 60394	

Fluid-Air Components Ltd

BALL VALVES

Mini Ball Valves, Brass Chrome Plated

Working Temperature: 0°C to +90°C

Maximum Working Pressure: 10 bar

Suitable for domestic water services, heating and air-conditioning plants and compressed air systems.



Type 125, Female x Female, BSPP, Red Nylon Lever Handle

0089	Thread
IT125-14	1/4"
IT125-38	3/8"
IT125-12	1/2"
IT125-34	3/4"
Tech Sheet 1828	



Type 126, Male x Female, BSPP, Red Nylon Lever Handle

0089	Thread
IT126-14	1/4"
IT126-38	3/8"
IT126-12	1/2"
IT126-34	3/4"
Tech Sheet 1828	



Type 125, Female x Female, BSPP, Black Nylon Lever Handle

0089	Thread
IT125-14N	1/4"
IT125-38N	3/8"
IT125-12N	1/2"
IT125-34N	3/4"
Tech Sheet 1828	



Type 126, Male x Female, BSPP, Black Nylon Lever Handle

0089	Thread
IT126-14N	1/4"
IT126-38N	3/8"
IT126-12N	1/2"
IT126-34N	3/4"
Tech Sheet 1828	

BALL VALVES

Mini Ball Valves

- **Body:** Brass
- **End Connection:** Brass
- **Ball:** Brass, chrome plated
- **Stem:** Brass
- **Seal:** PTFE
- **O-Ring:** Nitrile
- **Handle:** Plastic (ABS)

Working Temperature: -10°C to +90°C

Maximum Working Pressure: 20 bar



Female x Female, BSPP

0468	Thread
TEMBVFF-1/4	1/4"
TEMBVFF-3/8	3/8"
TEMBVFF-1/2	1/2"
Tech Sheet 67953	

- **Body:** Brass
- **Sleeve:** Brass
- **Ball:** Brass, chrome plated
- **Stem:** Brass
- **Seal:** PTFE
- **O-Ring:** Nitrile
- **Handle:** Plastic (ABS)

Working Temperature: -10°C to +90°C

Maximum Working Pressure: 20 bar



Male x Female, BSPP


0468	Thread
TEMBVMF-1/4	1/4"
TEMBVMF-3/8	3/8"
TEMBVMF-1/2	1/2"
Tech Sheet 67954	

Fluid-Air Components Ltd

BALL VALVES

Mini Ball Valve Handles

Please Note: Handles do not come with coloured inserts, please order separately



Type 6910, Long Handle

0090	Length mm
6910-A	35
6910-B	50
Tech Sheet 1606	

Colour Coded Handle Inserts - Type 6920



For 1/8", 1/4", 3/8" Valves

0090	Colour
6920-A-B	Blue
6920-A-G	Green
6920-A-R	Red
6920-A-W	White
6920-A-Y	Yellow
Tech Sheet 1605	

For 1/2", 3/4" Valves

0090	Colour
6920-B-B	Blue
6920-B-G	Green
6920-B-R	Red
6920-B-W	White
6920-B-Y	Yellow
Tech Sheet 1605	

Mini Ball Valves, Brass

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar



Type 6560, Push-in x Push-in

0090	OD mm
6560-4	4
6560-6	6
6560-8	8
Tech Sheet 1604	



Type 6570, Push-in x BSPT Male

0090	OD mm	Thread
6570-18-4	4	1/8"
6570-18-6	6	1/8"
6570-18-8	8	1/8"
6570-14-6	6	1/4"
6570-14-8	8	1/4"
Tech Sheet 1605		



Type 6700, L Port, BSPP

0090	Thread
6700-18	1/8"
6700-14	1/4"
6700-38	3/8"
Tech Sheet 1605	



Type 6710, T Port, BSPP

0090	Thread
6710-18	1/8"
6710-14	1/4"
6710-38	3/8"
Tech Sheet 1605	



Type 6720, Angle Port, BSPP

0090	Thread
6720-18	1/8"
6720-14	1/4"
6720-38	3/8"
Tech Sheet 1605	

AIGNEP



For **Metric Brass Compression Fittings** see pages **1076-1079**

FAC Fluid-Air Components Ltd

BALL VALVES

Full Bore Ball Valves, Brass Nickel Plated

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.


Working Temperature:
-20°C to +150°C
in absence of steam



IDEAL 090, Female x Female, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT090-14	1/4"	50
IT090-38	3/8"	50
IT090-12	1/2"	50
IT090-34	3/4"	40
IT090-1	1"	40
IT090-114	1.1/4"	30
IT090-112	1.1/2"	30
IT090-2	2"	25
IT090-212	2.1/2"	18
IT090-3	3"	16
IT090-4	4"	14
Tech Sheet 1826		


Working Temperature:
-20°C to +150°C
in absence of steam



IDEAL 091, Male x Female, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT091-14	1/4"	50
IT091-38	3/8"	50
IT091-12	1/2"	50
IT091-34	3/4"	40
IT091-1	1"	40
IT091-114	1.1/4"	30
IT091-112	1.1/2"	30
IT091-2	2"	25
Tech Sheet 6042		

Working Temperature:
-10°C to +95°C
in absence of steam




Type 099, Male x Male, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT099-12	1/2"	40
IT099-34	3/4"	40
IT099-1	1"	40
IT099-114	1.1/4"	30
IT099-112	1.1/2"	30
IT099-2	2"	30
Tech Sheet 6044		

Standard Bore Ball Valves, Brass Nickel Plated

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Working Temperature:
-20°C to +110°C in
the absence of steam



Type 115 with Drain Valve, Female x Female, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT115-12	1/2"	25
IT115-34	3/4"	25
IT115-1	1"	25
IT115-114	1.1/4"	20
IT115-112	1.1/2"	20
IT115-2	2"	20
Tech Sheet 6045		


Working Temperature:
-20°C to +150°C in
the absence of steam



VIENNA 216, Female x Female, BSPP, Flat Lever Handle

0089	Thread	Max Pressure Bar
IT216-14	1/4"	50
IT216-38	3/8"	50
IT216-12	1/2"	30
IT216-34	3/4"	30
IT216-1	1"	30
IT216-114	1.1/4"	25
IT216-112	1.1/2"	25
IT216-2	2"	25
Tech Sheet 1830		

Working Temperature:
-20°C to +150°C in
the absence of steam



VIENNA 217, Male x Female, BSPP, Flat Lever Handle

0089	Thread	Max Pressure Bar
IT217-14	1/4"	50
IT217-38	3/8"	50
IT217-12	1/2"	30
IT217-34	3/4"	30
IT217-1	1"	30
IT217-114	1.1/4"	25
IT217-112	1.1/2"	25
IT217-2	2"	25
Tech Sheet 1830		

Fluid-Air Components Ltd

BALL VALVES

Full Bore Ball Valves, Brass Nickel Plated

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Working Temperature:
-20°C to +150°C
in absence of steam



IDEAL 092, Female x Female, BSPP, Wing Handle

0089	Thread	Max Pressure Bar
IT092-14	1/4"	50
IT092-38	3/8"	50
IT092-12	1/2"	50
IT092-34	3/4"	40
IT092-1	1"	40
Tech Sheet 1826		


Working Temperature:
-20°C to +150°C
in absence of steam



IDEAL 093, Male x Female, BSPP, Wing Handle

0089	Thread	Max Pressure Bar
IT093-14	1/4"	50
IT093-38	3/8"	50
IT093-12	1/2"	50
IT093-34	3/4"	40
IT093-1	1"	40
Tech Sheet 6042		

Working Temperature:
-20°C to +150°C
in absence of steam



IDEAL 098, Male Union x Female, BSPP, Wing Handle

0089	Thread	Max Pressure Bar
IT098-12	1/2"	50
IT098-34	3/4"	40
IT098-1	1"	40
IT098-114	1.1/4"	30
IT098-112	1.1/2"	30
IT098-2	2"	25
Tech Sheet 6043		

Working Temperature:
-20°C to +150°C
in absence of steam




IDEAL 298, Elbow, Male Union x Female, BSPP, Wing Handle

0089	Thread	Max Pressure Bar
IT298-12	1/2'	50
IT298-34	3/4"	40
IT298-1	1"	40
Tech Sheet 1827		

3 Way Ball Valves, Brass Nickel Plated

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Working Temperature:
-10°C to +120°C



Type 128, L Port, Female, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT128-14L	1/4"	55
IT128-38L	3/8"	55
IT128-12L	1/2"	50
IT128-34L	3/4"	50
IT128-1L	1"	45
IT128-114L	1.1/4"	35
IT128-112L	1.1/2"	35
IT128-2L	2"	35
Tech Sheet 1829		

Type 128, T Port, Female, BSPP, Lever Handle

0089	Thread	Max Pressure Bar
IT128-14T	1/4"	55
IT128-38T	3/8"	55
IT128-12T	1/2"	50
IT128-34T	3/4"	50
IT128-1T	1"	45
IT128-114T	1.1/4"	35
IT128-112T	1.1/2"	35
IT128-2T	2"	35
Tech Sheet 1829		

Fluid-Air Components Ltd

BALL VALVES

Bibcock Ball Valves, Brass Nickel Plated

Working Temperature:
-20°C to +80°C

Maximum Working Pressure: 15 bar



Type 174, Plastic Hose Tail x Male, BSPP, Lever Handle

0089	Thread	To Suit Hose ID mm
IT174-12	1/2"	13
IT174-34	3/4"	19
Tech Sheet 68270		

Working Temperature:
-20°C to +80°C



Type 134 Heavy-duty, Hose Tail x Male, BSPP, Wing Handle

0089	Thread	To Suit Hose ID mm	Max Pressure Bar
IT134-38	3/8"	19	15
IT134-12	1/2"	19	15
IT134-34	3/4"	25	15
IT134-1	1"	32	12
Tech Sheet 68270			

Working Temperature:
-20°C to +80°C




Type 132 Heavy-duty, Hose Tail x Male, BSPP, Lever Handle

0089	Thread	To Suit Hose ID mm	Max Pressure Bar
IT132-38	3/8"	19	15
IT132-12	1/2"	19	15
IT132-34	3/4"	25	15
IT132-1	1"	32	12
Tech Sheet 68270			

Working Temperature:
0°C to +80°C

Maximum Working Pressure: 15 bar



Type 144, Hose Tail x Male, BSPP, Handle with Lockpad Eye (7mm ID)

0089	Thread	To Suit Hose ID mm
IT144-12	1/2"	13
IT144-34	3/4"	19
Tech Sheet 1834		

FT PRO

For **Hose Reels**
see pages **1449-1453**



BALL VALVES

Antifrost Bibcocks

- **Body, Sleeve and Hose Connection:** Brass
- **Ball:** Brass, chrome plated
- **Stem and Nut:** Brass
- **Seals:** PTFE
- **O-Ring:** Nitrile
- **Flat Seal:** EPDM
- **Handle:** Aluminium

Working Temperature:
-20°C to +100°C

Maximum Working Pressure:
Without nipple for hose: 30 bar
With nipple for hose: 3 bar



BSPP


0468	Thread	OD mm
AFBV-12	1/2"	14
AFBV-34	3/4"	20

Tech Sheet 67955

Oxygen Ball Valves

- **Body and Sleeve:** Brass
- **Stem:** Brass
- **Ball:** Brass, chrome plated
- **O-Rings:** Viton
- **Seals/O-Ring:** Pure PTFE
- **Handle:** Zinc-plated steel, plastic cover

Working Temperature:
-10°C to +120°C



Female x Female, BSPP

0468	Thread	Max Pressure Bar
OXYBV-14	1/4"	63
OXYBV-38	3/8"	63
OXYBV-12	1/2"	50
OXYBV-34	3/4"	50
OXYBV-1	1"	45
OXYBV-114	1.1/4"	30
OXYBV-112	1.1/2"	25
OXYBV-2	2"	20

Tech Sheet 67959

Full Bore Venting Ball Valves, Brass

Conforms to Directive 97/23/EC.

Working Temperature:
-10°C to +120°C

Maximum Working Pressure @ +20°C
45 bar (1/2" to 3/4")
40 bar (1")
30 bar (1.1/4" to 2")



Female x Female, BSPP

0468	Thread
BV215-12	1/2"
BV215-34	3/4"
BV215-1	1"
BV215-114	1.1/4"
BV215-112	1.1/2"
BV215-2	2"

Tech Sheet 60156

BALL VALVES

Vented Lockable Ball Valves

Material: nickel plated brass.
- Full bore
- Locking lever in the closed position only
- Vents downstream pressure when closed
- Suitable for compressed air systems

Working Temperature:
-10°C to +100°C

Maximum Working Pressure: 14 bar

Female x Female, BSPP

0358	Thread
BV93-14L	1/4"
BV93-38L	3/8"
BV93-12L	1/2"
BV93-34L	3/4"
BV93-1L	1"
BV93-114L	1.1/4"
BV93-112L	1.1/2"
BV93-2L	2"

Tech Sheet 6041



FESTO

For **Filter Regulators**
see pages **658-661**



Fluid-Air Components Ltd

BALL VALVES

Standard In-line Vented Ball Valves

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
40 bar



Double Female BSPP with Threaded Exhaust

1012	Thread	DN Size
LE-0489 07 13	1/4"	7
LE-0489 10 17	3/8"	10
LE-0489 13 21	1/2"	13
LE-0489 18 27	3/4"	18
LE-0489 23 34	1"	23
Tech Sheet 10455		

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar



Double Female Panel Mountable with Threaded Exhaust, BSPP

1012	Thread	DN Size
LE-0449 07 13	1/4"	7
LE-0449 10 17	3/8"	10
LE-0449 13 21	1/2"	13
Tech Sheet 10451		

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
40 bar



Double Female Vented, BSPP

1012	Thread	DN Size
LE-0469 04 10	1/8"	4
LE-0469 07 13	1/4"	7
LE-0469 10 17	3/8"	10
LE-0469 13 21	1/2"	13
LE-0469 18 27	3/4"	18
LE-0469 23 34	1"	23
Tech Sheet 10453		

Standard In-line Ball Valves

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar



Double Female Panel Mount, BSPP

1012	Thread	DN Size
LE-0446 04 10	1/8"	4
LE-0446 07 13	1/4"	7
LE-0446 10 17	3/8"	10
LE-0446 13 21	1/2"	13
Tech Sheet 10448		

Standard Ball Valves for Screw Fixing

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
40 bar



Double Female, BSPP

1012	Thread	DN Size
LE-6402 04 10	1/8"	4
LE-6402 07 13	1/4"	7
LE-6402 10 17	3/8"	10
LE-6402 13 21	1/2"	13
LE-6402 20 27	3/4"	20
LE-6402 23 34	1"	23
Tech Sheet 10449		



For **Panel Mountable Flow Control Regulators** see pages **804-807**

Fluid-Air Components Ltd

BALL VALVES

Standard 3 Way Ball Valves

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar

- L Ported closed centre



Female Right Angled Porting, BSPP

1012	Thread	DN Size
LE-0482 06 13	1/4"	6
LE-0482 09 17	3/8"	9
LE-0482 12 21	1/2"	12
LE-0482 23 34	1"	23
Tech Sheet 10461		

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar

- L Ported closed centre



Female Right Angled Porting - Panel Mountable, BSPP

1012	Thread	DN Size
LE-0448 06 13	1/4"	6
LE-0448 09 17	3/8"	9
LE-0448 12 21	1/2"	12
Tech Sheet 10464		

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar

- L Ported



Female Equal Plane Porting - Panel Mountable, BSPP

1012	Thread	DN Size
LE-0452 04 10	1/8"	4
LE-0452 06 13	1/4"	6
Tech Sheet 10459		

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar

- L Ported closed centre



Female Right Angled Porting without Closed Position, BSPP

1012	Thread	DN Size
LE-0483 04 10	1/8"	4
LE-0483 06 13	1/4"	6
LE-0483 09 17	3/8"	9
LE-0483 12 21	1/2"	12
Tech Sheet 10463		

Lockable Ball Valves

- Legris lockable ball valves have been developed in order to prevent potentially dangerous consequences by unintended operation. Lockable in different positions, this range meets international safety requirements, such as ISO 4414. Lockable ball valves feature a plate fixed to the valve body and a plate attached to the valve stem. When the plates are pad-locked together, the valve handle cannot be moved.

The valves are lockable:

- In both open and closed position, by one padlock: models 0437 and 0439.
- Only in the closed position by up to three padlocks: models 0437 and 0438.

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
40 bar



In-line Double Female, BSPP

1012	Thread	DN Size
LE-0432 10 17	3/8"	10
LE-0432 13 21	1/2"	13
LE-0432 20 27	3/4"	20
LE-0432 23 34	1"	23
Tech Sheet 10457		

Maximum Working Pressure:
40 bar



Double Female with Vent, BSPP

1012	Thread	DN Size
LE-0439 07 13	1/4"	7
LE-0439 10 17	3/8"	10
LE-0439 13 21	1/2"	13
LE-0439 18 27	3/4"	18
LE-0439 23 34	1"	23
Tech Sheet 10462		

Maximum Working Pressure:
40 bar



In-line Double Female with Vent, BSPP

1012	Thread	DN Size
LE-0437 10 17	3/8"	10
LE-0437 13 21	1/2"	13
LE-0437 18 27	3/4"	18
LE-0437 23 34	1"	23
Tech Sheet 10458		

Maximum Working Pressure:
20 bar



3 Way, BSPP

1012	Thread	DN Size
LE-0438 12 21	1/2"	12
Tech Sheet 10460		

FTPRO®



For **Nickel Plated Brass Adaptors** see page **1171-1176**

Fluid-Air Components Ltd

BALL VALVES

Mini Ball Valves

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
10 bar



3/2 with Vent, Push-in

1012	OD mm
LE-7913 04 00	4
LE-7913 06 00	6
LE-7913 08 00	8
LE-7913 10 00	10
LE-7913 12 00	12
Tech Sheet 10456	



2/2, Push-in

1012	OD mm
LE-7910 04 00	4
LE-7910 06 00	6
LE-7910 08 00	8
LE-7910 10 00	10
LE-7910 12 00	12
Tech Sheet 10452	



3/2 with Vent, Push-in x Male, BSPP

1012	Thread	OD mm
LE-7914 06 10	1/8"	6
LE-7914 08 13	1/4"	8
LE-7914 12 21	1/2"	12
Tech Sheet 10450		



2/2, Push-in x Male, BSPP

1012	Thread	OD mm
LE-7911 06 10	1/8"	6
LE-7911 10 17	3/8"	10
LE-7911 12 21	1/2"	12
Tech Sheet 10454		

BALL VALVES

Direct Mount Brass Ball Valves

Suitable for domestic water services, heating and air conditioning plants, and compressed air systems.

- Full bore
- Direct mount ISO 5211

Working Temperature:
-20°C to +130°C

Maximum Working Pressure:
40 bar



Female x Female, BSPP

0986	Thread
BV1021-14	1/4"
BV1021-38	3/8"
Tech Sheet 68247	



3 Way T Port, Female, BSPP

0986	Thread	Max Pressure Bar
BV1070-14	1/4"	40
BV1070-38	3/8"	40
BV1070-12	1/2"	40
BV1070-34	3/4"	40
BV1070-1	1"	40
BV1070-114	1.1/4"	40
BV1070-112	1.1/2"	25
BV1070-2	2"	25
Tech Sheet 68248		



3 Way L Port, Female, BSPP

0986	Thread	Max Pressure Bar
BV1071-14	1/4"	40
BV1071-38	3/8"	40
BV1071-12	1/2"	40
BV1071-34	3/4"	40
BV1071-1	1"	40
BV1071-114	1.1/4"	40
BV1071-112	1.1/2"	25
BV1071-2	2"	25
Tech Sheet 68248		

Fluid-Air Components Ltd

CAST IRON BALL VALVES

Cast Iron Ball Valves

Features:
- ISO 5211 Mounting Pad
- ATEX approved
- Blowout proof stem
- Locking device available on request

Working Temperature: -10°C to +200°C

Maximum Working Pressure: 16 bar



2 Piece, Flanged PN16, Full Bore

0905	Flange Size
150HIT 04	1/2"
150HIT 05	3/4"
150HIT 06	1"
150HIT 07	1.1/4"
150HIT 08	1.1/2"
150HIT 09	2"
150HIT 10	2.1/2"
150HIT 11	3"
150HIT 12	4"
150HIT 13	5"
150HIT 14	6"
150HIT 16	8"
Tech Sheet 6036	

Mounting Kits



Mounting Kit for 150HIT Cast Iron Flanged PN16 Ball Valve

3100	Size
MK150HIT-1	1/2"
MK150HIT-2	3/4" to 1.1/4"
MK150HIT-3	1.1/2" to 2"
MK150HIT-4	2.1/2" to 3"
MK150HIT-5	4" to 5"
MK150HIT-6	6" to 8"
Tech Sheet 71760	

HAITIMA



For **Haitima Actuated Cast Iron Flanged PN16 Ball Valves** see page **1000**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

BALL VALVES

Plastic Ball Valves

Maximum Working Pressure: 3.5 bar

Body: Polypropylene
Seal: Nitrile



Hose Tail x Hose Tail

0270	To Suit Hose ID mm
18530-1	12
18530-2	16
18530-3	20



Male BSPP x Male BSPP

0270	Thread
18570-1	1/2"
18570-2	1/2" x 3/4"
18570-3	3/4"



Hose Tail x Female BSPP

0270	To Suit Hose ID mm	Thread
18563-1	16	1/2"
18563-2	16	3/4"
18563-3	20	1/2"
18563-4	20	3/4"



Hose Tail x Male BSPP

0270	To Suit Hose ID mm	Thread
18560-1	12	1/2"
18560-2	12	3/4"
18560-3	16	1/2"
18560-4	16	3/4"
18560-5	20	1/2"
18560-6	20	3/4"

Working Temperature:
0°C to +60°C
0°C to +20°C (at 16 bar)

Maximum Working Pressure:
16 bar



UPVC, Double Union Ball Valve, EPDM Seals

0118	Thread
2020-0424	1/2"
2020-0432	3/4"
2020-0440	1"
2020-0457	1.1/4"
2020-0465	1.1/2"
2020-0473	2"
Tech Sheet 10322	

BALL VALVES

Plastic Ball Valves

Working Temperature:
0°C to +60°C

Maximum Working Pressure: 15 bar



UPVC, Economy Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVD13-12-PVC	1/2"
BVD13-34-PVC	3/4"
BVD13-1-PVC	1"
BVD13-114-PVC	1.1/4"
BVD13-112-PVC	1.1/2"
BVD13-2-PVC	2"
BVD13-212-PVC	2.1/2"
BVD13-3-PVC	3"
BVD13-4-PVC	4"
Tech Sheet 10254	



Industrial 3 Way Ball Valve, T Port, EPDM Seals

0118	Nominal Bore ID
BVT13-12-PVC	1/2"
BVT13-34-PVC	3/4"
BVT13-1-PVC	1"
BVT13-114-PVC	1.1/4"
BVT13-112-PVC	1.1/2"
BVT13-2-PVC	2"
Tech Sheet 10254	



Industrial 3 Way Ball Valve, L Port, EPDM Seals

0118	Nominal Bore ID
BVL13-12-PVC	1/2"
BVL13-34-PVC	3/4"
BVL13-1-PVC	1"
BVL13-114-PVC	1.1/4"
BVL13-112-PVC	1.1/2"
BVL13-2-PVC	2"
Tech Sheet 10254	

Fluid-Air Components Ltd

FT PRO

WRAS APPROVED MATERIAL | CE | Gas Approved EN331 | RoHS 3 COMPLIANT | 3 YEAR WARRANTY

LEVER HANDLE BALL VALVES

FULL FLOW VALVES

WRAS
Brass ball valves fully approved by WRAS for clean water solutions.

The quality of the full flow brass ball valves is approved in the UK under the Water Regulations Advisory Scheme (WRAS) for water fittings. Suitable for domestic water services, heating, air-conditioning plants and compressed air systems for isolation shut-off. Blue wing handle valves are stocked as standard with green, red and black available on request.

EN 331 GAS
Brass ball valves conforming to EN 331 for gas applications.

Certified by Deutsche Akkreditierungsstelle (Dakks) in Germany to conform to EN 331 and EU 305, the yellow handle full flow brass ball valve has been specifically developed for gas installations including town gas, natural gas and liquid gas isolation shut-off.

WRAS, Lever Handles, Brass Nickel Plated

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 25 bar



Red and green levers are available on request

Female x Female, BSPP

0682	Thread
1063-14	1/4"
1063-38	3/8"
1063-12	1/2"
1063-34	3/4"
1063-1	1"
1063-114	1.1/4"
1063-112	1.1/2"
1063-2	2"
1063-212	2.1/2"
1063-3	3"
1063-4	4"
Tech Sheet 68778	

EN 331 Gas, Lever Handles, Brass Nickel Plated

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 5 bar



Female x Female, BSPP

0682	Thread
1071-14	1/4"
1071-38	3/8"
1071-12	1/2"
1071-34	3/4"
1071-1	1"
1071-114	1.1/4"
1071-112	1.1/2"
1071-2	2"
1071-212	2.1/2"
1071-3	3"
1071-4	4"
Tech Sheet 68780	

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 5 bar



Male x Female, BSPP

0682	Thread
1073-14	1/4"
1073-38	3/8"
1073-12	1/2"
1073-34	3/4"
1073-1	1"
1073-114	1.1/4"
1073-112	1.1/2"
1073-2	2"
Tech Sheet 68781	

Customised Ball Valve Handles available for this range

EN 331 Gas/WRAS Approved Brass Ball Valve Compression Ended

- Brass Nickel Plated Body
- Full bore
- Compression ends to EN1254-2

Working Temperature: -5°C to +150°C (oil and water) -5°C to +60°C (gas)

Maximum Working Pressure: 20 bar (oil and water) 5 bar (gas)

WRAS APPROVED MATERIAL



Red Lever Operated

0682	Size mm
EPS-102200	15
EPS-102205	22
EPS-102210	28
EPS-102215	35
EPS-102220	42
EPS-102225	54
Tech Sheet 717	

WRAS APPROVED MATERIAL



Blue Lever Operated

0682	Size mm
EPS-102150	15
EPS-102155	22
EPS-102160	28
EPS-102165	35
EPS-102170	42
EPS-102175	54
Tech Sheet 717	

Gas Approved EN331



Yellow Lever Operated

0682	Size mm
EPS-102100	15
EPS-102105	22
EPS-102110	28
EPS-102115	35
EPS-102120	42
EPS-102125	54
Tech Sheet 717	

Fluid-Air Components Ltd

WING HANDLE BALL VALVES

FULL FLOW VALVES

- WRAS approved
- EN 331 and EU 305 conformity
- RoHS 3 compliant
- Blowout proof
- Double seal
- No metal-to-metal moving parts
- Maintenance-free
- 3 year warranty

WRAS, Wing Handles, Brass Nickel Plated

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 25 bar



Female x Female, BSPP

0682	Thread
1193-14	1/4"
1193-38	3/8"
1193-12	1/2"
1193-34	3/4"
1193-1	1"

Tech Sheet 68779

EN 331 Gas, Wing Handles, Brass Nickel Plated

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 5 bar



Female x Female, BSPP

0682	Thread
1072-14	1/4"
1072-38	3/8"
1072-12	1/2"
1072-34	3/4"
1072-1	1"

Tech Sheet 68783

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 5 bar



Male x Female, BSPP

0682	Thread
1074-14	1/4"
1074-38	3/8"
1074-12	1/2"
1074-34	3/4"
1074-1	1"

Tech Sheet 68782

EN 331 Gas/WRAS Approved Brass Ball Valve Compression Ended

- Brass Nickel Plated Body
- Full bore
- Compression ends to EN1254-2

Working Temperature: -5°C to +150°C (oil and water) -5°C to +60°C (gas)

Maximum Working Pressure: 20 bar (oil and water) 5 bar (gas)



Red Wing Handle

0682	Size mm
EPS-102450	15
EPS-102455	22
EPS-102460	28

Tech Sheet 717



Blue Wing Handle

0682	Size mm
EPS-102470	15
EPS-102475	22
EPS-102480	28

Tech Sheet 717

Gas Approved EN331



Yellow Wing Handle

0682	Size mm
EPS-102420	15
EPS-102425	22
EPS-102430	28

Tech Sheet 717

Fluid-Air Components Ltd

BALL VALVES

Full Bore Gas Ball Valves, Brass Nickel Plated

Working Temperature: -20°C to +60°C

Maximum Working Pressure: 5 bar

EN 331 approved



LONDON 066 Compact, Female x Female, BSPP, Lever Handle

0089	Thread
IT066-14	1/4"
IT066-38	3/8"
IT066-12	1/2"
IT066-34	3/4"
IT066-1	1"
IT066-114	1.1/4"
IT066-112	1.1/2"
IT066-2	2"
Tech Sheet 68253	



LONDON 067 Compact, Male, BSPT x Female, BSPP, Lever Handle

0089	Thread
IT067-14	1/4"
IT067-38	3/8"
IT067-12	1/2"
IT067-34	3/4"
IT067-1	1"
IT067-114	1.1/4"
IT067-112	1.1/2"
IT067-2	2"
Tech Sheet 68254	



BERLIN 070, Female x Female, BSPP, Lever Handle

0089	Thread
IT070-12	1/2"
IT070-34	3/4"
IT070-1	1"
IT070-114	1.1/4"
IT070-112	1.1/2"
IT070-2	2"
Tech Sheet 1831	



BERLIN 071, Male, BSPT x Female, BSPP, Lever Handle

0089	Thread
IT071-12	1/2"
IT071-34	3/4"
IT071-1	1"
IT071-114	1.1/4"
IT071-112	1.1/2"
IT071-2	2"
Tech Sheet 1831	



LONDON 266 Compact, Female x Female, BSPP, Flat Lever Handle

0089	Thread
IT266-14	1/4"
IT266-38	3/8"
IT266-12	1/2"
IT266-34	3/4"
IT266-1	1"
IT266-114	1.1/4"
IT266-112	1.1/2"
IT266-2	2"
Tech Sheet 68257	



LONDON 267 Compact, Male, BSPT x Female, BSPP, Flat Lever Handle

0089	Thread
IT267-14	1/4"
IT267-38	3/8"
IT267-12	1/2"
IT267-34	3/4"
IT267-1	1"
IT267-114	1.1/4"
IT267-112	1.1/2"
IT267-2	2"
Tech Sheet 68258	



LONDON 068 Compact, Female x Female, BSPP, Wing Handle

0089	Thread
IT068-14	1/4"
IT068-38	3/8"
IT068-12	1/2"
IT068-34	3/4"
IT068-1	1"
Tech Sheet 68255	



LONDON 069 Compact, Male, BSPT x Female, BSPP, Wing Handle

0089	Thread
IT069-14	1/4"
IT069-38	3/8"
IT069-12	1/2"
IT069-34	3/4"
IT069-1	1"
Tech Sheet 68256	



BERLIN 072, Female x Female, BSPP, Wing Handle

0089	Thread
IT072-12	1/2"
IT072-34	3/4"
IT072-1	1"
Tech Sheet 1831	



BERLIN 073, Male, BSPT x Female, BSPP, Wing Handle

0089	Thread
IT073-12	1/2"
IT073-34	3/4"
IT073-1	1"
Tech Sheet 1832	



Type 060, Male x Male, BSPT, Wing Handle

0089	Thread
IT060-12	1/2"
Tech Sheet 10340	

Fluid-Air Components Ltd


BALL VALVES

Super Filter Ball Valves, Brass

Advantages:
- Large flo
- Low head loss
- Eliminates need for separate in-line filte
- Reduces installation time
- Easy access for filter cleanin
- Can be installed in any position

500 micron filter (35 mesh)
Conforms to Directive 97/23/EC.

Working Temperature: -20°C to +100°C



Built-in Filter, BSPP

0468	Thread	Max Pressure Bar
SFBV-12	1/2"	30
SFBV-34	3/4"	30
SFBV-1	1"	30
SFBV-114	1.1/4"	20
SFBV-112	1.1/2"	20
SFBV-2	2"	20
Tech Sheet 60155		

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 30 bar

- Can be installed in any position



T Handle, Built-in Filter, BSPP

0468	Thread
SFBVT-12	1/2"
SFBVT-34	3/4"
SFBVT-1	1"
Tech Sheet 60155	

90° Gas Ball Valves

- **Body:** Brass
- **Ball:** Brass, chrome plated
- **Sleeve, Stem and Nut:** Brass
- **Seal:** PTFE
- **O-Rings:** Nitrile + FKM
- **Handle:** Aluminium
- EN 331 approved

Working Temperature: -20°C to +60°C

Maximum Working Pressure: 5 bar



Male x Female, BSPP

0468	Thread	Thread
GBVMF-3434	3/4"	3/4"
Tech Sheet 67956		

For **Combination Spanner Sets** see page **1739**



Fluid-Air Components Ltd

BALL VALVES

Gas Mini Ball Valves, Brass

- **Seal:** Material PTFE

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
20 bar



Type 6300, Female x Female, BSPP

0090	Thread	Thread
6300-18	1/8"	1/8"
6300-14	1/4"	1/4"
6300-38	3/8"	3/8"
6300-12	1/2"	1/2"
Tech Sheet 1602		



Type 6310, BSPT Male x BSPP Female

0090	Male Thread	Female Thread
6310-18-18	1/8"	1/8"
6310-14-18	1/4"	1/8"
6310-14-14	1/4"	1/4"
6310-38-38	3/8"	3/8"
6310-12-12	1/2"	1/2"
6310-34-34	3/4"	3/4"
Tech Sheet 1602		



Type 6320, Male x Female, BSPP

0090	Male Thread	Female Thread
6320-18-18	1/8"	1/8"
6320-14-18	1/4"	1/8"
6320-14-14	1/4"	1/4"
6320-38-38	3/8"	3/8"
6320-12-12	1/2"	1/2"
Tech Sheet 1602		



Type 6330, Male x Male, BSPP

0090	Thread	Thread
6330-18-18	1/8"	1/8"
6330-18-14	1/8"	1/4"
6330-14-14	1/4"	1/4"
6330-12-12	1/2"	1/2"
Tech Sheet 1602		



Type 6340, Tube x Female, BSPP

0090	OD mm	Thread
6340-6-18	6	1/8"
6340-8-18	8	1/8"
6340-8-14	8	1/4"
6340-10-38	10	3/8"
6340-15-12	15	1/2"
Tech Sheet 1603		



Type 6350, Male, BSPT x Tube

0090	OD mm	Thread
6350-18-6	6	1/8"
6350-18-8	8	1/8"
6350-14-6	6	1/4"
6350-14-8	8	1/4"
6350-38-10	10	3/8"
6350-38-12	12	3/8"
6350-12-15	15	1/2"
Tech Sheet 1603		



Type 6420, Male x Male, BSPP

0090	Thread	Thread
6420-18-18	1/8"	1/8"
6420-18-14	1/8"	1/4"
6420-14-14	1/4"	1/4"
6420-38-14	3/8"	1/4"
6420-38-38	3/8"	3/8"
6420-12-12	1/2"	1/2"
Tech Sheet 1603		



Type 6440, Male BSPP x Tube

0090	OD mm	Thread
6440-18-6	6	1/8"
6440-18-8	8	1/8"
6440-14-6	6	1/4"
6440-14-8	8	1/4"
6440-14-10	10	1/4"
6440-38-8	8	3/8"
6440-38-10	10	3/8"
6440-38-15	15	3/8"
6440-12-12	12	1/2"
6440-12-15	15	1/2"
6440-34-15	15	3/4"
Tech Sheet 1604		



Type 6500, Tube x Tube

0090	OD mm
6500-8	8
Tech Sheet 1604	

Fluid-Air Components Ltd

BALL VALVES

Dual Sealing Gas Approved Ball Valves

- Manufactured in accordance to BSI
- ISO 228 parallel female threads to EN10226-1
- Full port to DIN 3357 for maximum flo
- PED 2014/68/EU
- Spring return handle available on request

Working Temperature:
-40°C to +170°C

AS4617 Limitations for Gas:
0°C to +60°C

Maximum Working Pressure:
Up to 2": 40 bar
Over 2": 30 bar

AS4617 Limitations for Gas:
Up to 2": 21 bar
2.1/2" to 4": 15 bar



Female x Female, BSPP

0358	Thread
BV84-14	1/4"
BV84-38	3/8"
BV84-12	1/2"
BV84-34	3/4"
BV84-1	1"
BV84-114	1.1/4"
BV84-112	1.1/2"
BV84-2	2"
BV84-212	2.1/2"
BV84-3	3"
BV84-4	4"
Tech Sheet 20558	

Dual Sealing WRAS Ball Valves

The BV84W potable ball valve range is approved for use with drinking water. The ball design avoids water stagnation and the spread of bacteria in the system.

- PED 2014/68/EU

Working Temperature:
-40°C to +170°C

Maximum Working Pressure:
40 bar



Female x Female, BSPP

0358	Thread
BV84-14W	1/4"
BV84-38W	3/8"
BV84-12W	1/2"
BV84-34W	3/4"
BV84-1W	1"
BV84-114W	1.1/4"
BV84-112W	1.1/2"
BV84-2W	2"
Tech Sheet 20558	

Dual Sealing Gas Lockable Ball Valves

- Manufactured in accordance to BSI
- ISO 228 parallel female threads to EN10226-1
- Full port to DIN 3357 for maximum flo
- PED 2014/68/EU
- Spring return handle available on request

Working Temperature:
-40°C to +170°C

AS4617 Limitations for Gas:
0°C to +60°C

Maximum Working Pressure:
Up to 2": 40 bar
Over 2": 30 bar

AS4617 Limitations for Gas:
Up to 2": 21 bar
2.1/2" to 4": 15 bar



Female x Female, BSPP

0358	Thread
BV84-14L	1/4"
BV84-38L	3/8"
BV84-12L	1/2"
BV84-34L	3/4"
BV84-1L	1"
BV84-114L	1.1/4"
BV84-112L	1.1/2"
BV84-2L	2"
BV84-212L	2.1/2"
BV84-3L	3"
BV84-4L	4"
Tech Sheet 60397	

Dual Sealing WRAS Lockable Ball Valves

The BV84WL potable ball valve range is approved for use with drinking water. The specific ball design avoids water stagnation and the spread of bacteria in the system.

- PED 2014/68/EU

Working Temperature:
-40°C to +170°C

Maximum Working Pressure:
40 bar



Female x Female, BSPP

0358	Thread
BV84-14WL	1/4"
BV84-38WL	3/8"
BV84-12WL	1/2"
BV84-34WL	3/4"
BV84-1WL	1"
BV84-114WL	1.1/4"
BV84-112WL	1.1/2"
BV84-2WL	2"
Tech Sheet 60397	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

BALL VALVES

Direct Mount WRAS Approved Brass Ball Valve

- Full bore
- Direct mount ISO 5211

Working Temperature: -20°C to +170°C

Maximum Working Pressure: 40 bar



Female x Female, BSPP

0358	Thread
BV64-12	1/2"
BV64-34	3/4"
BV64-1	1"
BV64-114	1.1/4"
BV64-112	1.1/2"
BV64-2	2"
Tech Sheet 6040	

Compression Ended WRAS Ball Valves

Body material: DZR brass.

- Suitable for domestic water services, heating and air conditioning plants and compressed air systems.

Working Temperature: -20°C to +120°C

Maximum Working Pressure: 16 bar



Male x Male

0358	OD mm
BV28-15	15
BV28-22	22
BV28-28	28
BV28-35	35
BV28-42	42
BV28-54	54
Tech Sheet 68241	

Stem Extension

- Can be used when insulating the pipework.



To suit RuB Ball Valves

0358	To Suit
PPR003	1/4"-1/2"
PPR006	3/4"-1"
PPR009	1.1/4"-2"
Tech Sheet 68243	

Ball Valve Lockable Handles



Yellow

0358	To Suit
PBFG13	1/4"-1/2"
PBFG16	3/4"-1"
PBFG19	1.1/4"-2"
PBFG20	2.1/2"-4"
Tech Sheet 68244	

Blue

0358	To Suit
PBFA13	1/4"-1/2"
PBFA16	3/4"-1"
PBFA19	1.1/4"-2"
PBFA20	2.1/2"-4"
Tech Sheet 68244	

J+J



For **J+J Electric Actuators Fitted With RuB Ball Valves** see page **1007**

Fluid-Air Components Ltd

BALL VALVES

Plastic Ball Valves

Working Temperature:
0°C to +60°C

Maximum Working Pressure:
15 bar



UPVC, Industrial Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVI13-38-PVC	3/8"
BVI13-12-PVC	1/2"
BVI13-34-PVC	3/4"
BVI13-1-PVC	1"
BVI13-114-PVC	1.1/4"
BVI13-112-PVC	1.1/2"
BVI13-2-PVC	2"
BVI13-212-PVC	2.1/2"
BVI13-3-PVC	3"
BVI13-4-PVC	4"
Tech Sheet 10254	



ABS, Industrial Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVI13-12-ABS	1/2"
BVI13-34-ABS	3/4"
BVI13-1-ABS	1"
BVI13-114-ABS	1.1/4"
BVI13-112-ABS	1.1/2"
BVI13-2-ABS	2"
BVI13-212-ABS	2.1/2"
BVI13-3-ABS	3"
BVI13-4-ABS	4"
Tech Sheet 10255	



For **Tubing Accessories**
see page **1097**

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

316 Stainless Steel Mini Ball Valves

Features:

- Reduced bore
- Suitable for domestic water services, heating and air-conditioning plants and compressed air systems

Working Temperature: -25°C to +180°C

Maximum Working Pressure: 63 bar



Hexagon Body, Female, BSPP

0902	Thread
HEXSMBV14	1/4"
HEXSMBV38	3/8"
HEXSMBV12	1/2"
HEXSMBV34	3/4"
HEXSMBV1	1"
Tech Sheet 6018	



Hexagon Body, Male BSPT x Female BSPP

0902	Thread
HEXSMBV14M	1/4"
HEXSMBV38M	3/8"
HEXSMBV12M	1/2"
HEXSMBV34M	3/4"
HEXSMBV1M	1"
Tech Sheet 6018	

Stainless Steel Lockable Ball Valves

Suitable for domestic water services, heating and air-conditioning plants, and compressed air systems.

- Full bore
- PTFE seals
- PTFE O-rings

Working Temperature: -20°C to +180°C

Maximum Working Pressure:
63 bar: up to 3/4"
50 bar: 1" and 1.1/4"
40 bar: 1.1/2" upwards



2 Piece, Full Bore, Male x Female, BSPP

0901	Thread
789-14	1/4"
789-38	3/8"
789-12	1/2"
789-34	3/4"
789-1	1"
789-114	1.1/4"
789-112	1.1/2"
789-2	2"
Tech Sheet 6019	

HAITIMA stainless steel



You might also need...
Stainless Steel 150LB Fittings
...see pages **1181-1273**

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel HAITIMA

316 Stainless Steel Ball Valves

Features:
- ATEX approved
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



2 Piece, Full Bore, BSPP

0099	Thread
2006S-14	1/4"
2006S-38	3/8"
2006S-12	1/2"
2006S-34	3/4"
2006S-1	1"
2006S-114	1.1/4"
2006S-112	1.1/2"
2006S-2	2"
Tech Sheet 1966	

2 Piece, Full Bore, NPT

0099	Thread
2006S-14N	1/4"
2006S-38N	3/8"
2006S-12N	1/2"
2006S-34N	3/4"
2006S-1N	1"
2006S-114N	1.1/4"
2006S-112N	1.1/2"
2006S-2N	2"
Tech Sheet 1966	

Features:
- ATEX approved
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 138 bar



2 Piece, Full Bore, BSPP

0099	Thread
2006-14	1/4"
2006-38	3/8"
2006-12	1/2"
2006-34	3/4"
2006-1	1"
Tech Sheet 6003	

Features:
- Investment casting
- Blowout proof stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar




2 Piece, Full Bore, BSPP, Wing Handle

0924	Size
2006FW-14W	1/4"
2006FW-38W	3/8"
2006FW-12W	1/2"
Tech Sheet 6001	

You might also need...
Valve Lockouts & Padlocks
...see page **1763**



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c



Stainless Steel Valves

A quality range of stainless steel ball valves with a reliable reputation across the manufacturing industry. A wide selection of valves are available from the manufacturer including API 607 fire safe and specialised material options of Titanium, Monel, Hastelloy, Inconel 625, SMO 254 and Duplex.

Approvals:

- ISO 9001 approved manufacturer
- 3A approved
- Pressure equipment directive/module H certification
- TA-Luft certification
- EN10204 3:1 material certification
- DNV certification

Applications:

- Hydraulic
- Pneumatic
- Steam
- Oxygen (if degreased)
- Vacuum
- Thermal fluids
- Chemical
- Oil/gas
- Food processing
- Dry/liquid chlorine
- Testing

For full compatibility for your application, please contact our Technical department.

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

STAINLESS STEEL VALVES

stainless steel HAITIMA

316 Stainless Steel Ball Valves

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar

Features:
- Investment casting
- Blowout proof stem
- Locking lever



1 Piece, Reduced Bore, BSPP

0924	Thread
2017FW-14	1/4"
2017FW-38	3/8"
2017FW-12	1/2"
2017FW-34	3/4"
2017FW-1	1"
2017FW-114	1.1/4"
2017FW-112	1.1/2"
2017FW-2	2"
Tech Sheet 6000	



2 Piece, Full Bore, BSPP

0924	Thread
2006FW-14	1/4"
2006FW-38	3/8"
2006FW-12	1/2"
2006FW-34	3/4"
2006FW-1	1"
2006FW-114	1.1/4"
2006FW-112	1.1/2"
2006FW-2	2"
2006FW-212	2.1/2"
2006FW-3	3"
Tech Sheet 6001	



3 Piece, Full Bore, BSPP

0924	Thread
2013FW-14	1/4"
2013FW-38	3/8"
2013FW-12	1/2"
2013FW-34	3/4"
2013FW-1	1"
2013FW-114	1.1/4"
2013FW-112	1.1/2"
2013FW-2	2"
2013FW-212	2.1/2"
2013FW-3	3"
2013FW-4	4"
Tech Sheet 6005	



3 Piece, Full Bore, NPT

0924	Thread
2013FW-14N	1/4"
2013FW-38N	3/8"
2013FW-12N	1/2"
2013FW-34N	3/4"
2013FW-1N	1"
2013FW-114N	1.1/4"
2013FW-112N	1.1/2"
2013FW-2N	2"
2013FW-212N	2.1/2"
2013FW-3N	3"
2013FW-4N	4"
Tech Sheet 6005	



3 Piece, Full Bore, Butt Weld

0924	Size
2012FW-14	1/4"
2012FW-38	3/8"
2012FW-12	1/2"
2012FW-34	3/4"
2012FW-1	1"
2012FW-114	1.1/4"
2012FW-112	1.1/2"
2012FW-2	2"
2012FW-212	2.1/2"
2012FW-3	3"
2012FW-4	4"
Tech Sheet 6005	



3 Piece, Full Bore, Socket Weld

0924	Thread
2011FW-14	1/4"
2011FW-38	3/8"
2011FW-12	1/2"
2011FW-34	3/4"
2011FW-1	1"
2011FW-114	1.1/4"
2011FW-112	1.1/2"
2011FW-2	2"
2011FW-212	2.1/2"
2011FW-3	3"
2011FW-4	4"
Tech Sheet 6005	

FAC Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel

HAITIMA

316 Stainless Steel Ball Valves ISO Pad Mount

Features:
- Direct mount ISO 5211
- ATEX approved
- TA Luft
- ISO 15848-1:2006 fugitive emissions
- Anti-static device
- Investment casting
- Blowout proof stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



2 Piece, Full Bore, BSPP

0924	Thread
2006SD-14	1/4"
2006SD-38	3/8"
2006SD-12	1/2"
2006SD-34	3/4"
2006SD-1	1"
2006SD-114	1.1/4"
2006SD-112	1.1/2"
2006SD-2	2"
Tech Sheet 6004	

HAITIMA



You might also need a...
Haitima Pneumatic Actuator
...see page **1015**

Features:
- Direct mount ISO 5211
- ATEX approved
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 6 bar

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



3 Piece, Full Bore, BSPP

0924	Thread
2013ND-14	1/4"
2013ND-38	3/8"
2013ND-12	1/2"
2013ND-34	3/4"
2013ND-1	1"
2013ND-114	1.1/4"
2013ND-112	1.1/2"
2013ND-2	2"
2013ND-212	2.1/2"
2013ND-3	3"
2013ND-4	4"
Tech Sheet 6006	

3 Piece, Full Bore, NPT

0924	Thread
2013ND-12N	1/2"
2013ND-34N	3/4"
2013ND-1N	1"
2013ND-114N	1.1/4"
2013ND-112N	1.1/2"
2013ND-2N	2"
Tech Sheet 6006	

3 Piece, Full Bore, Butt Weld

0924	Thread
2012ND-12	1/2"
2012ND-34	3/4"
2012ND-1	1"
2012ND-114	1.1/4"
2012ND-112	1.1/2"
2012ND-2	2"
2012ND-212	2.1/2"
2012ND-3	3"
2012ND-4	4"
Tech Sheet 6006	

3 Piece, Full Bore, Socket Weld

0924	Thread
2011ND-12	1/2"
2011ND-34	3/4"
2011ND-1	1"
2011ND-114	1.1/4"
2011ND-112	1.1/2"
2011ND-2	2"
2011ND-212	2.1/2"
2011ND-3	3"
2011ND-4	4"
Tech Sheet 6006	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL VALVES

stainless steel GENEBRE

316 Stainless Steel Ball Valves ISO Pad Mount

Features:
- Reduced bore
- Direct mount ISO 5211
- Anti-static device
- Blowout proof stem
- Locking lever

Working Temperature: -25°C to +180°C

Maximum Working Pressure: 63 bar





3 Way, L Port, BSPP

0902	Thread
2040-14	1/4"
2040-38	3/8"
2040-12	1/2"
2040-34	3/4"
2040-1	1"
2040-114	1.1/4"
2040-112	1.1/2"
2040-2	2"
2040-212	2.1/2"
Tech Sheet 6025	

3 Way, T Port, BSPP

0902	Thread
2041-14	1/4"
2041-38	3/8"
2041-12	1/2"
2041-34	3/4"
2041-1	1"
2041-114	1.1/4"
2041-112	1.1/2"
2041-2	2"
2041-212	2.1/2"
Tech Sheet 6025	

Looking for bespoke Flow Path Configuration?
Contact our technical team.

LOCTITE



You might also need...
577 Thread Sealant
...see page **1584**

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel

HAITIMA


Hygenic 316 Stainless Steel Ball Valves ISO Pad Mount

Features:

- Cavity filled seat
- Direct mount ISO 5211
- ATEX approved
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Piece, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2012CD-12	1/2"	15	12.70	90.70	F03/F04
2012CD-34	3/4"	20	19.10	103	F03/F04
2012CD-1	1"	25	25.40	115	F04/F05
2012CD-112	1.1/2"	40	38.10	139	F05/F07
2012CD-2	2"	50	50.80	158	F05/F07
2012CD-212	2.1/2"	65	63.50	197	F07/F10
2012CD-3	3"	80	76.20	228	F07/F10
2012CD-4	4"	100	101.60	241.80	F10/F12
Tech Sheet 6009					

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Piece, Clamp End

0924	Size	DN	Length	ISO 5211
2013CD-12	1/2"	15	90.70	F03/F04
2013CD-34	3/4"	20	103	F03/F04
2013CD-1	1"	25	115	F04/F05
2013CD-112	1.1/2"	40	139	F05/F07
2013CD-2	2"	50	158	F05/F07
2013CD-212	2.1/2"	65	197	F07/F10
2013CD-3	3"	80	228	F07/F10
2013CD-4	4"	100	241.80	F10/F12
Tech Sheet 6009				

Features:

- Direct mount ISO 5211
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Way, L Port, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2057CBL-12	1/2"	15	12.70	118	F03/F04
2057CBL-1	1"	25	25.40	152.40	F04/F05
2057CBL-112	1.1/2"	40	38.10	175	F05/F07
2057CBL-2	2"	50	50.80	190	F05/F07
2057CBL-212	2.1/2"	65	63.50	228	F07/F10
2057CBL-3	3"	80	76.20	260	F07/F10
2057CBL-4	4"	100	102	289	F10/F12
Tech Sheet 6009					

3 Way, T Port, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2057CBT-12	1/2"	15	12.70	118	F03/F04
2057CBT-1	1"	25	25.40	152.40	F04/F05
2057CBT-112	1.1/2"	40	38.10	175	F05/F07
2057CBT-2	2"	50	50.80	190	F05/F07
2057CBT-212	2.1/2"	65	63.50	228	F07/F10
2057CBT-3	3"	80	76.20	260	F07/F10
2057CBT-4	4"	100	102	289	F10/F12
Tech Sheet 6009					

Hygenic 316 Stainless Steel Ball Valves


FT PRO

Working Temperature:
-20°C to +160°C

Maximum Working Pressure:
8 bar

Features:

- Cavity filled seat
- Locking lever



3 Piece, Weld End

0708	OD	OD mm	Length mm
HSBVWE-12	1/2"	12.7	89
HSBVWE-112	1.1/2"	38.1	140
HSBVWE-2	2"	50.8	156
Tech Sheet 68171			

FT PRO

Working Temperature:
-20°C to +160°C

Maximum Working Pressure:
8 bar

Features:

- Cavity filled seat
- Locking lever



3 Piece, Clamp End

0708	Clamp Size	Length mm
HSBVCE-1	1"	114
HSBVCE-2	2"	156
Tech Sheet 68171		

Fluid-Air Components Ltd

STAINLESS STEEL VALVES


stainless steel HAITIMA

Fire Safe Direct Mount Ball Valves

Features:

- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th Edition
- NACE MR0175
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +220°C



3 Piece, BSPP, Full Bore

0924	Thread	Max Pressure bar
2013KMD-12	1/2"	138
2013KMD-34	3/4"	138
2013KMD-1	1"	138
2013KMD-114	1.1/4"	103
2013KMD-112	1.1/2"	103
2013KMD-2	2"	103
2013KMD-212	2.1/2"	63
2013KMD-3	3"	63
Tech Sheet 6007		

3 Piece, NPT, Full Bore

0924	Thread	Max Pressure bar
2013KMD-12N	1/2"	138
2013KMD-34N	3/4"	138
2013KMD-1N	1"	138
2013KMD-114N	1.1/4"	103
2013KMD-112N	1.1/2"	103
2013KMD-2N	2"	103
2013KMD-3N	3"	63
Tech Sheet 6007		

3 Piece, Butt Weld, Full Bore

0924	Size	Max Pressure bar
2012KMD-12	1/2"	138
2012KMD-34	3/4"	138
2012KMD-1	1"	138
2012KMD-112	1.1/2"	103
2012KMD-2	2"	103
Tech Sheet 6007		

3 Piece, Socket Weld, Full Bore

0924	Size	Max Pressure bar
2011KMD-12	1/2"	138
2011KMD-34	3/4"	138
2011KMD-1	1"	138
2011KMD-114	1.1/4"	103
2011KMD-112	1.1/2"	103
2011KMD-2	2"	103
Tech Sheet 6007		

AIR TORQUE



You might also need a...
Air Torque Pneumatic Actuator
...see page **1015**

316 Stainless Steel Ball Valves

Features:

- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 16 bar



2 Piece, Flanged PN16, Full Bore

0924	Flange Size	Bore mm
2019S 04	1/2"	15
2019S 05	3/4"	20
2019S 06	1"	25
2019S 07	1.1/4"	32
2019S 08	1.1/2"	40
2019S 09	2"	50
2019S 10	2.1/2"	65
2019S 11	3"	80
2019S 12	4"	100
2019S 14	6"	150
Tech Sheet 6011		

Features:

- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 19.6 bar



2 Piece, Flanged ANSI150, Full Bore

0924	Flange Size	Bore mm
2020S 04	1/2"	15
2020S 05	3/4"	20
2020S 06	1"	25
2020S 08	1.1/2"	40
2020S 09	2"	50
2020S 10	2.1/2"	65
2020S 11	3"	80
2020S 12	4"	100
2020S 14	6"	150
Tech Sheet 6013		

FAC Fluid-Air Components Ltd


STAINLESS STEEL VALVES

stainless steel HAITIMA

Fire Safe Direct Mount Ball Valves

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- DNV certifie
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +200°C



2 Piece, Flanged PN16, Full Bore

0924	Flange Size	Flange	Max Pressure bar
2019D 04	1/2"	PN16/40	40
2019D 05	3/4"	PN16/40	40
2019D 06	1"	PN16/40	40
2019D 07	1.1/4"	PN16/40	40
2019D 08	1.1/2"	PN16/40	40
2019D 09	2"	PN16/40	40
2019D 10	2.1/2"	PN16	16
2019D4 10	2.1/2"	PN40	40
2019D 11	3"	PN16	16
2019D4 11	3"	PN40	40
2019D 12	4"	PN16	16
2019D4 12	4"	PN40	40
2019D 13	5"	PN16	16
2019D 14	6"	PN16	16
2019D 16	8"	PN16	16
Tech Sheet 10336			

316 Stainless Steel Ball Valve Accessories

Features:
- ISO mounting pad to ISO 5211

Working Temperature:
-20°C to +200°C



Stem Extension

0924	Valve ISO	Stem Size
TSM 1	F04	9
TSM 2	F05	11
TSM 3	F07	14
TSM 4	F10	17
TSM 5	F12	22
Tech Sheet 6016		

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +230°C

Maximum Working Pressure:
19.6 bar



2 Piece, Flanged ANSI150, Full Bore


0924	Flange Size
2020D 04	1/2"
2020D 05	3/4"
2020D 06	1"
2020D 07	1.1/4"
2020D 08	1.1/2"
2020D 09	2"
2020D 10	2.1/2"
2020D 11	3"
2020D 12	4"
2020D 14	6"
Tech Sheet 10331	

Other Flanged End connections are available on request

316 Stainless Steel Direct Mount Ball Valves

Features:
- Direct mount ISO 5211
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature:
-20°C to +200°C



3 Way, L Port, Flanged PN16, Full Bore

0924	Flange Size	Max Pressure bar
2059DL16 04	1/2"	16
2059DL16 06	1"	16
2059DL16 08	1.1/2"	16
2059DL16 09	2"	16
2059DL16 10	2.1/2"	16
2059DL16 11	3"	16
2059DL16 12	4"	16
2059DL16 14	6"	16
Tech Sheet 6015		

3 Way, L Port, Flanged ANSI150, Full Bore

0924	Flange Size	Max Pressure bar
2059DL150 04	1/2"	19.6
2059DL150 06	1"	19.6
2059DL150 08	1.1/2"	19.6
2059DL150 09	2"	19.6
2059DL150 11	3"	19.6
2059DL150 12	4"	19.6
2059DL150 14	6"	19.6
Tech Sheet 6015		

3 Way, T Port, Flanged PN16, Full Bore

0924	Flange Size	Max Pressure bar
2059DT16 04	1/2"	16
2059DT16 06	1"	16
2059DT16 08	1.1/2"	16
2059DT16 09	2"	16
2059DT16 10	2.1/2"	16
2059DT16 11	3"	16
2059DT16 12	4"	16
2059DT16 14	6"	16
Tech Sheet 6015		

3 Way, T Port, Flanged ANSI150, Full Bore

0924	Flange Size	Max Pressure bar
2059DT150 04	1/2"	19.6
2059DT150 06	1"	19.6
2059DT150 08	1.1/2"	19.6
2059DT150 09	2"	19.6
2059DT150 11	3"	19.6
2059DT150 12	4"	19.6
2059DT150 14	6"	19.6
Tech Sheet 6015		

FAC Fluid-Air Components Ltd

CARBON STEEL BALL VALVES

HAITIMA

Fire Safe Direct Mount Ball Valves

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- NACE MR0175
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature:
-20°C to +220°C



3 Piece, BSPP, Full Bore

0924	Thread	Max Pressure bar
2013KMD-12C	1/2"	138
2013KMD-34C	3/4"	138
2013KMD-1C	1"	138
2013KMD-114C	1.1/4"	103
2013KMD-112C	1.1/2"	103
2013KMD-2C	2"	103
2013KMD-212C	2.1/2"	63
2013KMD-3C	3"	63
Tech Sheet 6007		

3 Piece, NPT, Full Bore

0924	Thread	Max Pressure bar
2013KMD-12CN	1/2"	138
2013KMD-34CN	3/4"	138
2013KMD-1CN	1"	138
2013KMD-114CN	1.1/4"	103
2013KMD-112CN	1.1/2"	103
2013KMD-2CN	2"	103
2013KMD-3CN	3"	63
Tech Sheet 6007		

3 Piece, Butt Weld, Full Bore

0924	Size	Max Pressure bar
2012KMD-12C	1/2"	138
2012KMD-34C	3/4"	138
2012KMD-1C	1"	138
2012KMD-112C	1.1/2"	103
2012KMD-2C	2"	103
Tech Sheet 6007		

3 Piece, Socket Weld, Full Bore

0924	Size	Max Pressure bar
2011KMD-12C	1/2"	138
2011KMD-34C	3/4"	138
2011KMD-1C	1"	138
2011KMD-114C	1.1/4"	103
2011KMD-112C	1.1/2"	103
2011KMD-2C	2"	103
Tech Sheet 6007		

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- DNV certified
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +200°C



2 Piece, Flanged PN16, Full Bore

0924	Flange Size	Flange	Max Pressure bar
2019D 04C	1/2"	PN16/40	40
2019D 05C	3/4"	PN16/40	40
2019D 06C	1"	PN16/40	40
2019D 08C	1.1/2"	PN16/40	40
2019D 09C	2"	PN16/40	40
2019D 10C	2.1/2"	PN16	16
2019D 11C	3"	PN16	16
2019D 12C	4"	PN16	16
2019D 14C	6"	PN16	16
Tech Sheet 10336			

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +230°C

Maximum Working Pressure:
19.6 bar



2 Piece, Flanged ANSI150, Full Bore

0924	Flange Size
2020D 04C	1/2"
2020D 05C	3/4"
2020D 06C	1"
2020D 08C	1.1/2"
2020D 09C	2"
2020D 10C	2.1/2"
2020D 11C	3"
2020D 12C	4"
2020D 14C	6"
Tech Sheet 10331	

Other Flanged End connections are available on request

FESTO



You might also need a...
Festo Pneumatic Actuator
...see page **1017**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL VALVES

stainless steel

FT PRO

316 Stainless Steel Ball Valves ISO Pad Mount

Features:

- Direct mount ISO 5211
- Blowout proof stem
- Locking lever for 1" to 4"
- Suitable for applications such as chemical, petrochemical, hydraulic and compressed air

Working Temperature:
-20°C to +180°C

Maximum Working Pressure:
16 bar



Wafer Pattern, Flanged PN16, Full Bore

0901	Flange Size
771 04	1/2"
771 05	3/4"
771 06	1"
771 07	1.1/4"
771 08	1.1/2"
771 09	2"
771 10	2.1/2"
771 11	3"
771 12	4"
771 13	5"
771 14	6"
Tech Sheet 6030	

STAINLESS STEEL VALVES

stainless steel

PANAM

6,000 psi Rated Ball Valves

Working Temperature:
-18°C to +93°C

Maximum Working Pressure:
413 bar



Female, NPT

0292	Thread
PBV-2-S-02-FF	1/8"
PBV-2-S-04-FF	1/4"
PBV-2-S-06-FF	3/8"
PBV-2-S-08-FF	1/2"
PBV-2-S-12-FF	3/4"
PBV-2-S-16-FF	1"
Tech Sheet 10508	

Ball Valves

Working Temperature:
-18°C to +93°C

Maximum Working Pressure:
413 bar



Compression, 2 Way

0292	OD
BV6000-18	1/8"
BV6000-12	1/2"
Tech Sheet 20847	

PANAM

stainless steel



For **Panam Fittings**
see pages **1256-1273**

Fluid-Air Components Ltd

GATE VALVES

Brass Gate Valves, Heavy-duty

Features:
- BSPT threads. BSPP for 2.1/2" upwards
- Suitable for isolation of fluids and general purpose applications such as domestic water services and heating plants



Working Temperature: -10°C to +80°C

Maximum Working Pressure: 20 bar
16 bar (2.1/2" upwards)

Type GV12

0910	Size
GV12-38	3/8"
GV12-12	1/2"
GV12-34	3/4"
GV12-1	1"
GV12-114	1.1/4"
GV12-112	1.1/2"
GV12-2	2"
GV12-212	2.1/2"
GV12-3	3"
GV12-4	4"

Tech Sheet 6081

new product



Bronze Square Plugs

1094	Size	DN
BSP-34-BR	3/4"	20
BSP-1-BR	1"	25
BSP-114-BR	1.1/4"	32
BSP-112-BR	1.1/2"	40
BSP-2-BR	2"	50

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 16 bar



Type GV157, BSPP

0442	Thread
GV157-38	3/8"
GV157-12	1/2"
GV157-34	3/4"
GV157-1	1"
GV157-114	1.1/4"
GV157-112	1.1/2"
GV157-2	2"
GV157-212	2.1/2"
GV157-3	3"

Tech Sheet 10143

Stainless Steel Gate Valves

Features:
- Investment casting
- Non-rising stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 200 psi (13.8 bar)

BSPP

0900	Size
2029-14	1/4"
2029-38	3/8"
2029-12	1/2"
2029-34	3/4"
2029-1	1"
2029-114	1.1/4"
2029-112	1.1/2"
2029-2	2"

Tech Sheet 6074



Cast Iron & Ductile Iron Gate Valves

Features:
- Cast Iron Body
- Face to face DIN 3202-F4
- Non-rising stem

Working Temperature: -10°C to +120°C at 16 bar
-10°C to +200°C at 12.8 bar

Maximum Working Pressure: 16 bar



Flanged PN16, Metal Seat

0927	Flange Size
D02 09	2"
D02 10	2.1/2"
D02 11	3"
D02 12	4"
D02 13	5"
D02 14	6"
D02 16	8"

Tech Sheet 6079

Features:
- Cast Iron Body
- Face to face BS 5150
- Non-rising stem

Working Temperature: -10°C to +120°C at 16 bar
-10°C to +200°C at 12.8 bar

Maximum Working Pressure: 16 bar



Flanged PN16, Metal Seat

0927	Flange Size
E02 09	2"
E02 10	2.1/2"
E02 11	3"
E02 12	4"
E02 13	5"
E02 14	6"
E02 16	8"

Tech Sheet 6080

Features:
- Ductile Iron Body
- WRAS approved
- UL listed
- Non-rising stem
- Conforms to BS 5163 Pt. 1 & 2:2004
- Position indicator for open/close

Working Temperature: 0°C to +80°C

Maximum Working Pressure: 16 bar



Flanged PN16, Resilient Seat

0909	Flange Size
HUK5163 09	2"
HUK5163 10	2.1/2"
HUK5163 11	3"
HUK5163 12	4"
HUK5163 14	6"
HUK5163 16	8"
HUK5163 18	10"
HUK5163 20	12"

Tech Sheet 6078

Features:
- Used to allow key operation



Cap Top to suit HUK5163 Valves

0909	Size
HUK5163CT 12	2"-4"
HUK5163CT 14	5"-8"

Fluid-Air Components Ltd

GATE VALVES

Brass Gate Valves

Suitable for domestic water services, heating, air-conditioning plants

Working Temperature:
0°C to +150°C
in absence of steam

Maximum Working Pressure: 16 bar



Type 156, PN16, BSPP

0089	Thread
IT156-12	1/2"
IT156-34	3/4"
IT156-1	1"
IT156-114	1.1/4"
IT156-112	1.1/2"
IT156-2	2"
IT156-212	2.1/2"
IT156-3	3"
IT156-4	4"

Tech Sheet 20009

Bronze Gate Valves

Working Temperature:
-10°C to +232°C

Maximum Working Pressure: 20 bar



PN20, Lockshield, BSPT

0205	Thread
GVBZ375LS-12	1/2"
GVBZ375LS-34	3/4"
GVBZ375LS-1	1"
GVBZ375LS-114	1.1/4"
GVBZ375LS-112	1.1/2"
GVBZ375LS-2	2"

Tech Sheet 1820

GATE VALVES

stainless steel

Stainless Steel Gate Valves

Features:
- Investment casting
- Rising stem

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
16 bar



Flanged PN16

0982	Size	DN
2054SL16 04	1/2"	15
2054SL16 05	3/4"	20
2054SL16 06	1"	25
2054SL16 07	1.1/4"	32
2054SL16 08	1.1/2"	40
2054SL16 09	2"	50
2054SL16 11	3"	80
2054SL16 12	4"	100
2054SL16 14	6"	150

Tech Sheet 1876

Features:
- Investment casting
- Rising stem

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
19.6 bar



Flanged ANSI150

0982	Size	DN
2054SL150 04	1/2"	15
2054SL150 05	3/4"	20
2054SL150 06	1"	25
2054SL150 08	1.1/2"	40
2054SL150 09	2"	50
2054SL150 10	2.1/2"	65
2054SL150 11	3"	80
2054SL150 12	4"	100
2054SL150 14	6"	150

Tech Sheet 1873

Fluid-Air Components Ltd

GATE VALVES

Stainless Steel Gate Valves



Features:
- ATEX approved
- NACE MR0175
- Conforms to API 602

Working Temperature:
-50°C to +450°C

Maximum Working Pressure:
110 bar

Class 800, NPT

0905	Thread
GA800S-12	1/2"
GA800S-34	3/4"
GA800S-1	1"
GA800S-114	1.1/4"
GA800S-112	1.1/2"
GA800S-2	2"
Tech Sheet 6075	

Class 800, Socket Weld

0905	Thread
GA800S-12S	1/2"
GA800S-34S	3/4"
GA800S-1S	1"
GA800S-114S	1.1/4"
GA800S-112S	1.1/2"
GA800S-2S	2"
Tech Sheet 6075	

Carbon Steel Gate Valves



Features:
- ATEX approved
- NACE MR0175
- Conforms to API 602

Working Temperature:
-29°C to +425°C

Maximum Working Pressure:
138 bar

Class 800, NPT

0905	Thread
GA800C-12	1/2"
GA800C-34	3/4"
GA800C-1	1"
GA800C-114	1.1/4"
GA800C-112	1.1/2"
GA800C-2	2"
Tech Sheet 6075	

Class 800, Socket Weld

0905	Thread
GA800C-12S	1/2"
GA800C-34S	3/4"
GA800C-1S	1"
GA800C-114S	1.1/4"
GA800C-112S	1.1/2"
GA800C-2S	2"
Tech Sheet 6075	

KNIFE GATE VALVES

Unidirectional Knife Gate Valves



Features:
- Wafer design knife gate valve
- 304 stainless steel blade
- Handwheel operated with a rising stem.
  A non-rising stem option is also available on request
- One-piece cast body
- Provides high flow rates with low pressure drop

Working Temperature:
0°C to +90°C

Cast Iron Body, EPDM Seat, PN10

0944	Flange Size	Max Pressure bar
A1V2H2 09	2"	10
A1V2H2 10	2.1/2"	10
A1V2H2 11	3"	10
A1V2H2 12	4"	10
A1V2H2 13	5"	10
A1V2H2 14	6"	10
A1V2H2 16	8"	10
A1V2H2 18	10"	10
A1V2H2 20	12"	6
Tech Sheet 10246		

Bidirectional Knife Gate Valves



Features:
- Wafer design knife gate valve
- 304 stainless steel blade
- Handwheel operated with a rising stem.
  A non-rising stem option is also available on request
- One-piece cast body
- Provides high flow rates with low pressure drop

Working Temperature:
0°C to +90°C

Cast Iron Body, EPDM Seat, PN10

0944	Flange Size	Max Pressure bar
AB1V2H2 09	2"	10
AB1V2H2 10	2.1/2"	10
AB1V2H2 11	3"	10
AB1V2H2 12	4"	10
AB1V2H2 13	5"	10
AB1V2H2 14	6"	10
AB1V2H2 16	8"	8
AB1V2H2 18	10"	6
AB1V2H2 20	12"	6
Tech Sheet 6085		

Fluid-Air Components Ltd

CHECK VALVES

Brass Spring Check Valves

- Can be installed in any position
- Minimum opening pressure 0.5 psi

Working Temperature: -20°C to +100°C

Maximum Working Pressure: 16 bar




Type CV100, BSPP

0442	Thread
CV100-38	3/8"
CV100-12	1/2"
CV100-34	3/4"
CV100-1	1"
CV100-114	1.1/4"
CV100-112	1.1/2"
CV100-2	2"
Tech Sheet 10025	

Strainer Basket for Check Valves

Working Temperature: -20°C to +100°C



Type CV105, Stainless Steel Filters, BSPP

0445	Thread	Length mm	Height mm	Max Pressure Bar
CV105-38	3/8"	44	22	25
CV105-12	1/2"	47	28	25
CV105-34	3/4"	57	33	25
CV105-1	1"	69	42	25
CV105-114	1.1/4"	75	50	18
CV105-112	1.1/2"	84	55	18
Tech Sheet 10039				



For more sizes **Strainer Basket for Check Valves** see page **962**

Brass Swing Check Valves

Features:

- Installation in a horizontal position only
- Suitable for domestic water services, heating and air-conditioning plants and compressed air systems

Working Temperature: -20°C to +90°C

Maximum Working Pressure: 20 bar



Rubber Seat, BSPP

0910	Thread
CV12R-12	1/2"
CV12R-34	3/4"
CV12R-1	1"
CV12R-114	1.1/4"
CV12R-112	1.1/2"
CV12R-2	2"
Tech Sheet 6126	

Metal Seat, BSPP

0910	Thread
CV12M-12	1/2"
CV12M-34	3/4"
CV12M-1	1"
CV12M-114	1.1/4"
CV12M-112	1.1/2"
CV12M-2	2"
Tech Sheet 6126	

Bronze Swing Check Valves

Working Temperature: -10°C to +232°C

Maximum Working Pressure: 20 bar



PN20 Swing Check Valve, BSPT

0205	Thread
CVBZ384-12	1/2"
CVBZ384-34	3/4"
CVBZ384-1	1"
CVBZ384-114	1.1/4"
CVBZ384-112	1.1/2"
CVBZ384-2	2"
Tech Sheet 1822	

Brass Double Check Valves

Features:

- Conforms to BS EN 13959:2004
- Can be installed in any position
- Suitable for potable water applications, heating and air-conditioning plants

Working Temperature: 0°C to +85°C

Maximum Working Pressure: 16 bar



Metal Seat, BSPP

0913	Thread
HUKDCV-12	1/2"
HUKDCV-34	3/4"
HUKDCV-1	1"
HUKDCV-114	1.1/4"
HUKDCV-112	1.1/2"
HUKDCV-2	2"
Tech Sheet 6127	

PVC Check Valves

Working Temperature: 0°C to +60°C
0°C to +20°C (at 16 bar)

Maximum Working Pressure: 16 bar



Double Union, Spring Assisted, BSPP

0118	Thread
2020-0481	1/2"
2020-0499	3/4"
2020-0507	1"
2020-0515	1.1/4"
2020-0523	1.1/2"
2020-0531	2"
Tech Sheet 10323	

Fluid-Air Components Ltd

CHECK VALVES

stainless steel

FT PRO

Stainless Steel Spring Check Valves

Features:
- Installation in a horizontal position only

Working Temperature: -25°C to +180°C

Maximum Working Pressure: 200 psi (13.8 bar)



Swing, BSPP

0900	Thread
2030-12	1/2"
2030-34	3/4"
2030-1	1"
2030-114	1.1/4"
2030-112	1.1/2"
2030-2	2"
2030-212	2.1/2"
2030-3	3"
Tech Sheet 6098	

Features:
- Can be installed in any position

Working Temperature: -25°C to +180°C



Spring Assisted, BSPP

0900	Thread	Max Pressure bar
2413-14	1/4"	83
2413-38	3/8"	83
2413-12	1/2"	83
2413-34	3/4"	83
2413-1	1"	83
2413-114	1.1/4"	69
2413-112	1.1/2"	69
2413-2	2"	63
Tech Sheet 6093		

Features:
- Can be mounted between PN16/25/40 and ANSI150 flanges
- Can be installed in any position
- Suitable for saturated steam up to 10 bar

Working Temperature: -20°C to +180°C

Maximum Working Pressure: 40 bar




Spring Assisted Wafer Pattern

0933	Flange Size
2026 04	1/2"
2026 05	3/4"
2026 06	1"
2026 07	1.1/4"
2026 08	1.1/2"
2026 09	2"
2026 10	2.1/2"
2026 11	3"
2026 12	4"
Tech Sheet 6095	

Features:
- Can be installed in any position
- Suitable for saturated steam up to 10 bar

Working Temperature: -20°C to +180°C

Maximum Working Pressure: 40 bar



3 Piece, Spring Assisted, BSPP

0933	Thread
2026C-12	1/2"
2026C-34	3/4"
2026C-1	1"
2026C-114	1.1/4"
2026C-112	1.1/2"
2026C-2	2"
2026C-212	2.1/2"
2026C-3	3"
2026C-4	4"
Tech Sheet 6097	

HAITIMA

stainless steel



You might also need...
Stainless Steel 150LB Fittings
...see pages **1181-1273**

Fluid-Air Components Ltd

CHECK VALVES

Brass Check Valves

- Suitable for domestic water services, heating and air-conditioning plants, compressed air systems. Suited for installation in any position: vertical, horizontal or diagonal.

Working Temperature:
-20°C to +100°C



Type 100 EUROPA, Female, BSPP

0089	Thread	Max Pressure bar
IT100-38	3/8"	25
IT100-12	1/2"	25
IT100-34	3/4"	25
IT100-1	1"	25
IT100-114	1.1/4"	18
IT100-112	1.1/2"	18
IT100-2	2"	18
IT100-212	2.1/2"	12
IT100-3	3"	12
IT100-4	4"	12
Tech Sheet 6124		

Working Temperature:
-20°C to +100°C



Type 103 YORK, Female, BSPP

0089	Thread	Max Pressure Bar
IT103-38	3/8"	12
IT103-12	1/2"	12
IT103-34	3/4"	12
IT103-1	1"	12
IT103-114	1.1/4"	10
IT103-112	1.1/2"	10
IT103-2	2"	10
IT103-212	2.1/2"	8
IT103-3	3"	8
IT103-4	4"	8
Tech Sheet 1837		

Working Temperature:
-20°C to +100°C



Type 101 BLOCK, Female, BSPP

0089	Thread	Max Pressure Bar
IT101-12	1/2"	12
IT101-34	3/4"	12
IT101-1	1"	12
IT101-114	1.1/4"	10
IT101-112	1.1/2"	10
IT101-2	2"	10
Tech Sheet 1982		

Working Temperature:
-20°C to +150°C (air & fluid hydrocarbons);
-20°C to +100°C (water)

- Also suitable for use with gasoline and fuels in general.



Type 104 ROMA, Female, BSPP

0089	Thread	Max Pressure bar
IT104-38	3/8"	25
IT104-12	1/2"	25
IT104-34	3/4"	25
IT104-1	1"	25
IT104-114	1.1/4"	18
IT104-112	1.1/2"	18
IT104-2	2"	18
Tech Sheet 1840		

Working Temperature:
-20°C to +100°C

- To suit Type 100, 101, 103 and 104



Strainer, Stainless Steel with Polymer Thread, BSPP

0089	Thread
IT102-38	3/8"
IT102-12	1/2"
IT102-34	3/4"
IT102-1	1"
IT102-114	1.1/4"
IT102-112	1.1/2"
IT102-2	2"
IT102-212	2.1/2"
IT102-3	3"
IT102-4	4"
Tech Sheet 6125	

Working Temperature:
-20°C to +100°C

- To suit Type 100, 101, 103 and 104



Strainer, Polymer, BSPP

0089	Thread
IT107-12	1/2"
IT107-34	3/4"
IT107-1	1"
IT107-2	2"
Tech Sheet 1983	

Working Temperature:
0°C to +90°C

- Installation in a horizontal position only



Type 130, Swing Check, Soft Seat, BSPP

0089	Thread	Max. Pressure bar
CV130-38	3/8"	16
CV130-12	1/2"	16
CV130-34	3/4"	16
CV130-1	1"	12
CV130-114	1.1/4"	10
CV130-112	1.1/2"	10
CV130-2	2"	10
Tech Sheet 10026		

Type 130, Swing Check, Metal Seat, BSPP

0089	Thread	Max. Pressure bar
IT1300-12M	1/2"	16
IT1300-34M	3/4"	16
IT1300-1M	1"	12
IT1300-114M	1.1/4"	10
IT1300-112M	1.1/2"	10
IT1300-2M	2"	10
CV130-212	2.1/2"	8
CV130-3	3"	8
CV130-4	4"	8
Tech Sheet 10026		

Foot Valves, Brass

- Suitable for domestic water services, heating and air-conditioning plants, compressed air systems. Suited for installation in any position: vertical, horizontal or diagonal. Stainless steel strainer with polymer thread. Filtration up to 2": 1200µm, 2.1/2" onwards: 1700µm

Working Temperature:
-20°C to +100°C



Type 108 YORK, Female, BSPP

0089	Thread	Max Pressure Bar
IT108-38	3/8"	12
IT108-12	1/2"	12
IT108-34	3/4"	12
IT108-1	1"	12
IT108-114	1.1/4"	10
IT108-112	1.1/2"	10
IT108-2	2"	10
IT108-212	2.1/2"	6
IT108-3	3"	6
IT108-4	4"	6
Tech Sheet 10197		

Fluid-Air Components Ltd

CHECK VALVES

stainless steel

PANAM

Stainless Steel Check Valves

Working Temperature:
-26°C to +190°C

Cracking Pressure:
0.35 psi

Maximum Working Pressure:
414 bar

Seal: Viton



6,000 psi, Female, NPT

0292	Thread
PCV-02-SS-FF	1/8"
PCV-04-SS-FF	1/4"
PCV-06-SS-FF	3/8"
PCV-08-SS-FF	1/2"
PCV-12-SS-FF	3/4"
PCV-16-SS-FF	1"
Tech Sheet 10507	

CHECK VALVES


stainless steel

HAITIMA

Stainless Steel Check Valves

Features:
- Installation in a horizontal position only
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C



Flanged PN16

0982	Flange Size	Max Pressure bar
2024SL16 06	1"	16
2024SL16 08	1.1/2"	16
2024SL16 09	2"	16
2024SL16 10	2.1/2"	16
2024SL16 11	3"	16
2024SL16 12	4"	16
2024SL16 14	6"	16
Tech Sheet 1875		

Flanged ANSI150

0982	Flange Size	Max Pressure bar
2024SL150 06	1"	19.6
2024SL150 08	1.1/2"	19.6
2024SL150 09	2"	19.6
2024SL150 11	3"	19.6
2024SL150 12	4"	19.6
2024SL150 14	6"	19.6
Tech Sheet 1875		

Other sizes on request.

Cannot see the product you're looking for? Contact us. More often than not, we can acquire that product.

Fluid-Air Components Ltd

CHECK VALVES

stainless steel GENEBRE

Cromax Spring Check Valves

Body: 304SS or 316SS
Seal: Viton
Other sizes on request.

Working Temperature:
-20°C to +150°C

Maximum Working Pressure: 16 bar



304 Stainless Steel, BSPP

0902	Thread
2440-14	1/4"
2440-38	3/8"
2440-12	1/2"
2440-34	3/4"
2440-1	1"
2440-114	1.1/4"
2440-112	1.1/2"
2440-2	2"
Tech Sheet 1871	

316 Stainless Steel, BSPP

0902	Thread
2445-14	1/4"
2445-38	3/8"
2445-12	1/2"
2445-34	3/4"
2445-1	1"
2445-114	1.1/4"
2445-112	1.1/2"
2445-2	2"
Tech Sheet 1871	

Basket for Check Valves

Features:
- BSPP threads
- Mesh size 1mm up to 2". 1.9mm for 2.1/2" upwards

Working Temperature:
-20°C to +150°C

Maximum Working Pressure:
16 bar



Strainer Basket for Cromax Spring Check Valve

0902	Thread	DN
2447-12	1/2"	15
2447-34	3/4"	20
2447-1	1"	25
2447-114	1.1/4"	32
2447-112	1.1/2"	40
2447-2	2"	50
2447-212	2.1/2"	65
2447-3	3"	80
2447-4	4"	100
Tech Sheet 6094		

Wafer Check Valves

Seal: Viton
- Can be mounted between PN10/16 and ANSI150 flange

Working Temperature:
-20°C to +180°C

Maximum Working Pressure:
16 bar



Swing Check

0902	Flange Size
2406 08	1.1/2"
2406 09	2"
2406 10	2.1/2"
2406 11	3"
2406 12	4"
2406 13	5"
2406 14	6"
2406 16	8"
2406 18	10"
2406 20	12"
Tech Sheet 1878	

Features:
- Can be mounted between PN25 and ANSI150 flange
- Can be installed in any position

Working Temperature:
-20°C to +180°C

Maximum Working Pressure:
25 bar



Dual Plate, Spring Assisted, Swing Check

0902	Flange Size
2402 09	2"
2402 10	2.1/2"
2402 11	3"
2402 12	4"
2402 13	5"
2402 14	6"
2402 16	8"
Tech Sheet 6096	

Fluid-Air Components Ltd

CHECK VALVES

Stainless Steel Check Valves

Features:
- Reduced bore
- ATEX approved
- NACE MR0175
- Conforms to BS 5352

Working Temperature: -50°C to +450°C

Maximum Working Pressure: 110 bar



Class 800, NPT

0905	Thread
C800S-12	1/2"
C800S-34	3/4"
C800S-1	1"
C800S-114	1.1/4"
C800S-112	1.1/2
C800S-2	2"
Tech Sheet 6099	

Class 800, Socket Weld

0905	Thread
C800S-12S	1/2"
C800S-34S	3/4"
C800S-1S	1"
C800S-114S	1.1/4"
C800S-112S	1.1/2
C800S-2S	2"
Tech Sheet 6099	

Carbon Steel Check Valves

Features:
- Reduced bore
- ATEX approved
- NACE MR0175
- Conforms to BS 5352

Working Temperature: -29°C to +425°C

Maximum Working Pressure: 138 bar



Class 800, NPT

0905	Thread
C800C-12	1/2"
C800C-34	3/4"
C800C-1	1"
C800C-114	1.1/4"
C800C-112	1.1/2
C800C-2	2"
Tech Sheet 6099	

Class 800, Socket Weld

0905	Thread
C800C-12S	1/2"
C800C-34S	3/4"
C800C-1S	1"
C800C-114S	1.1/4"
C800C-112S	1.1/2
C800C-2S	2"
Tech Sheet 6099	

CHECK VALVES

Cast Iron Check Valves

Features:
- Can be mounted between PN16 and ANSI150 flanges
- WRAS approved
- Can be installed in any position

Working Temperature: 0°C to +85°C

Maximum Working Pressure: 16 bar



Dual Plate

0909	Flange Size
HUKDPC 09W	2"
HUKDPC 10W	2.1/2"
HUKDPC 11W	3"
HUKDPC 12W	4"
HUKDPC 13W	5"
HUKDPC 14W	6"
HUKDPC 16W	8"
HUKDPC 18W	10"
HUKDPC 20W	12"
Tech Sheet 6116	

Features:
- Face to face BS 5153, EN 558-1
- Conforms to BS EN 12334
- Can be installed with vertical upwards flow or horizontal flow

Working Temperature: -10°C to +120°C at 16 bar
-10°C to +230°C at 11.8 bar

Maximum Working Pressure: 16 bar



Flanged PN16, Metal Seat, Swing Check

0927	Flange Size	DN
E03 09	2"	50
E03 10	2.1/2"	65
E03 11	3"	80
E03 12	4"	100
E03 14	6"	150
E03 16	8"	200
Tech Sheet 6123		

Ductile Iron Check Valves

Features:
- Face to face conforms to BS EN 558-1 (series 10)
- Manufactured to the BS EN 16767:2016 standard for industrial check valves, previously BS 5153
- Can be installed with vertical upwards flow or horizontal flow

Working Temperature: 0°C to +80°C

Maximum Working Pressure: 16 bar



Flanged PN16, Soft Seat, Swing Check

0909	Flange Size	DN
HUK5153W 09	2"	50
HUK5153W 10	2.1/2"	65
HUK5153W 11	3"	80
HUK5153W 12	4"	100
HUK5153W 14	6"	150
HUK5153W 16	8"	200
HUK5153W 18	10"	250
HUK5153W 20	12"	300
Tech Sheet 6122		

Fluid-Air Components Ltd

CHECK VALVES

GENEBRE

Cast Iron Check Valves

Features:
- Can be installed in any position

Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
16 bar



Flanged PN16, Spring Disc

0918	Flange Size	DN
2450 09	2"	50
2450 10	2.1/2"	65
2450 11	3"	80
2450 12	4"	100
2450 13	5"	125
2450 14	6"	150
2450 16	8"	200
Tech Sheet 6119		

Features:
- Can be mounted between PN10/16 and ANSI150 flange
- Can be installed in any position

Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
16 bar



Dual Plate

0918	Flange Size	DN
2401 09	2"	50
2401 10	2.1/2"	65
2401 11	3"	80
2401 12	4"	100
2401 13	5"	125
2401 14	6"	150
2401 16	8"	200
2401 18	10"	250
2401 20	12"	300
Tech Sheet 6117		

Features:
- Can be installed with vertical upwards flow or horizontal fl

Working Temperature:
-10°C to +80°C

Maximum Working Pressure:
16 bar



Flanged PN16, Ball Check

0918	Flange Size	DN
2453 09	2"	50
2453 10	2.1/2"	65
2453 11	3"	80
2453 12	4"	100
2453 13	5"	125
2453 14	6"	150
2453 16	8"	200
2453 18	10"	250
Tech Sheet 6121		

Basket for Check Valves

Features:
- To suit PN16 flanged end
- Zinc-Plated Steel

Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
16 bar



Basket for 2450 Check Valve

0918	Size	DN
2451 09	2"	50
2451 10	2.1/2"	65
2451 11	3"	80
2451 12	4"	100
2451 13	5"	125
2451 14	6"	150
2451 16	8"	200
Tech Sheet 6120		

Fluid-Air Components Ltd

HYGIENIC STAINLESS STEEL VALVES

stainless steel FT PRO

Hygienic Stainless Steel Butterfly Valves



Weld End

0708	OD	OD mm	Length mm
BUTVWE-1	1"	25.4	68
BUTVWE-112	1.1/2"	38.1	76
BUTVWE-2	2"	50.8	80
BUTVWE-212	2.1/2"	63.5	80
BUTVWE-3	3"	76.2	82
BUTVWE-4	4"	101.6	88
Tech Sheet 68172			



RJT Male x Male

0708	Size	Thread	Length mm
BUTVRJT-1	1"	45.72 x 8T WHIT	68
BUTVRJT-112	1.1/2"	58.42 x 8T WHIT	76
BUTVRJT-2	2"	72.72 x 6T WHIT	80
BUTVRJT-212	2.5"	85.42 x 6T WHIT	80
BUTVRJT-3	3"	98.12 x 6T WHIT	82
BUTVRJT-4	4"	123.52 x 6T WHIT	100
Tech Sheet 68172			



Clamp End

0708	Size	Length mm
BUTVCE-1	1"	66
BUTVCE-112	1.1/2"	70
BUTVCE-2	2"	70
Tech Sheet 68172		

Stainless Steel Lever Type and Pull Type Handles are available on request

stainless steel

You might also need...
Hygienic Stainless Steel Tube & Pipe Fittings
...see pages **1320-1321**



BUTTERFLY VALVES

Wafer Pattern Butterfly Valves

Features:
- To suit BS 10 Table D/E, PN6/10/16 and ANSI150 flanges

Working Temperature:
-20°C to +120°C (WC, WS and WW)
0°C to +80°C (WB, WD and WT)
-30°C to +180°C (WG, WH and WU)
-20°C to +200°C (WI)

Maximum Working Pressure: 16 bar


WRAS



2014WW



2014WW-G



2014WS

Ductile Iron Body, Stainless Steel Disc

EPDM Liner, Lever Operated, (WRAS Approved Valve)	
0999	Flange Size
2014WW 08	1.1/2"
2014WW 09	2"
2014WW 10	2.1/2"
2014WW 11	3"
2014WW 12	4"
2014WW 13	5"
2014WW 14	6"
2014WW 16	8"
2014WW 18	10"
Tech Sheet 6060	

EPDM Liner, Gearbox Operated, (WRAS Approved Valve)	
0999	Flange Size
2014WW 18G	10"
2014WW 20G	12"
2014WW 22G	14"
2014WW 24G	16"
2014WW 26G	18"
2014WW 28G	20"
2014WW 30G	24"
Tech Sheet 6060	

Cast Iron Body, Stainless Steel Disc

NBR Liner, Lever Operated	
0999	Flange Size
2014WB 08	1.1/2"
2014WB 09	2"
2014WB 10	2.1/2"
2014WB 11	3"
2014WB 12	4"
2014WB 13	5"
2014WB 14	6"
2014WB 16	8"
2014WB 18	10"
Tech Sheet 14	


NBR Liner, Gearbox Operated	
0999	Flange Size
2014WB 20G	12"
2014WB 22G	14"
2014WB 24G	16"
2014WB 26G	18"
2014WB 28G	20"
2014WB 30G	24"
Tech Sheet 14	

Silicone Liner, Lever Operated	
0999	Flange Size
2014WG 09	2"
2014WG 10	2.1/2"
2014WG 11	3"
2014WG 12	4"
2014WG 13	5"
2014WG 14	6"
2014WG 16	8"
2014WG 18	10"
Tech Sheet 14	

PTFE on Silicone, Lever Operated	
0999	Flange Size
2014WH 08	1.1/2"
2014WH 09	2"
2014WH 10	2.1/2"
2014WH 11	3"
2014WH 12	4"
2014WH 13	5"
Tech Sheet 14	

PTFE on Silicone, Gearbox Operated	
0999	Flange Size
2014WH 14G	6"
2014WH 16G	8"
2014WH 18G	10"
2014WH 20G	12"
Tech Sheet 14	

You may also need
PN16 Flanges & Flange Gaskets
see page **1099**



Fluid-Air Components Ltd

Wafer Pattern Butterfly Valves

Cast Iron Body, Ductile Iron ENP Disc

EPDM Liner, Lever Operated	
0999	Flange Size
2014WC 09	2"
2014WC 10	2.1/2"
2014WC 11	3"
2014WC 12	4"
2014WC 13	5"
2014WC 14	6"
2014WC 16	8"
2014WC 18	10"
Tech Sheet 14	

NBR Liner, Lever Operated	
0999	Flange Size
2014WD 09	2"
2014WD 10	2.1/2"
2014WD 11	3"
2014WD 12	4"
2014WD 13	5"
2014WD 14	6"
2014WD 16	8"
2014WD 18	10"
Tech Sheet 14	

Carbon Steel Body, Stainless Steel Disc

FPM Liner, Lever Operated	
0999	Flange Size
2014WI 08	1.1/2"
2014WI 09	2"
2014WI 10	2.1/2"
2014WI 11	3"
2014WI 12	4"
2014WI 13	5"
2014WI 14	6"
2014WI 16	8"
Tech Sheet 14	

FPM Liner, Gearbox Operated	
0999	Flange Size
2014WI 18G	10"
2014WI 20G	12"
Tech Sheet 14	

Stainless Steel Body, Stainless Steel Disc

EPDM Liner, Lever Operated	
0999	Flange Size
2014WS 08	1.1/2"
2014WS 09	2"
2014WS 10	2.1/2"
2014WS 11	3"
2014WS 12	4"
2014WS 13	5"
2014WS 14	6"
2014WS 16	8"
2014WS 18	10"
Tech Sheet 14	

NBR Liner, Lever Operated	
0999	Flange Size
2014WT 08	1.1/2"
2014WT 09	2"
2014WT 10	2.1/2"
2014WT 11	3"
2014WT 12	4"
2014WT 13	5"
2014WT 14	6"
2014WT 16	8"
2014WT 18	10"
Tech Sheet 14	

EPDM Liner, Gearbox Operated*	
0999	Flange Size
2014WS 20G	12"
Tech Sheet 14	

Stainless Steel Body, Stainless Steel Disc

PTFE on Silicone Liner, Lever Operated	
0999	Flange Size
2014WU 09	2"
2014WU 10	2.1/2"
2014WU 11	3"
2014WU 12	4"
2014WU 13	5"
Tech Sheet 14	

PTFE on Silicone Liner, Gearbox Operated*	
0999	Flange Size
2014WU 14G	6"
2014WU 16G	8"
2014WU 18G	10"
2014WU 20G	12"
Tech Sheet 14	

*Gearbox is in cast iron material. Stainless steel options are available on request

Wafer Pattern Butterfly Valves

Features:

- To suit BS 10 Table D/E, PN6/10/16 and ANSI150 flanges
- 316 stainless steel coated with PTFE disc
- Suitable for highly corrosive applications

Working Temperature:
-40°C to +200°C



2014WP



2014WP-G

Ductile Iron Body, Fully Lined PTFE

0999	Flange Size	Max Pressure bar
2014WP 09	2"	16
2014WP 10	2.1/2"	16
2014WP 11	3"	16
2014WP 12	4"	16
2014WP 13	5"	16
Tech Sheet 6061		

0999	Flange Size	Max Pressure bar
2014WP 14G	6"	16
2014WP 16G	8"	16
2014WP 18G	10"	16
2014WP 20G	12"	10
Tech Sheet 6061		

Fluid-Air Components Ltd


BUTTERFLY VALVES

Lugged Pattern Butterfly Valves

Features:
- To suit PN16 flanges
- Lugged and tapped pattern valve design

Working Temperature:
-20°C to +120°C (2014LW)
0°C to +80°C (2014LB and 2014LD)
-30°C to +180°C (2014LH)
-20°C to +200°C (2014LI and 2014LV)

Maximum Working Pressure:
16 bar



Ductile Iron Body, Stainless Steel Disc

PN16, EPDM Liner, Lever Operated, (WRAS Approved Valve)	
0999	Flange Size
2014LW 08	1.1/2"
2014LW 09	2"
2014LW 10	2.1/2"
2014LW 11	3"
2014LW 12	4"
2014LW 13	5"
2014LW 14	6"
2014LW 16	8"
2014LW 18	10"
Tech Sheet 6063	

PN16, EPDM Liner, Gearbox Operated, (WRAS Approved Valve)	
0999	Flange Size
2014LW 16G	8"
2014LW 18G	10"
2014LW 20G	12"
2014LW 22G	14"
2014LW 24G	16"
2014LW 26G	18"
2014LW 28G	20"
2014LW 30G	24"
Tech Sheet 6063	

PN16, NBR Liner, Lever Operated	
0999	Flange Size
2014LB 08Y	1.1/2"
2014LB 09Y	2"
2014LB 10Y	2.1/2"
2014LB 11Y	3"
2014LB 12Y	4"
2014LB 13Y	5"
2014LB 14Y	6"
2014LB 16Y	8"
2014LB 18Y	10"
Tech Sheet 6064	

PN16, NBR Liner, Gearbox Operated	
0999	Flange Size
2014LB 20G	12"
2014LB 22G	14"
2014LB 24G	16"
2014LB 26G	18"
2014LB 28G	20"
2014LB 30G	24"
Tech Sheet 6064	

All 2014LB lever operated valves will come with a yellow coloured lever

PN16, PTFE on Silicone Liner, Lever Operated	
0999	Flange Size
2014LH 08	1.1/2"
2014LH 09	2"
2014LH 10	2.1/2"
2014LH 11	3"
2014LH 12	4"
2014LH 13	5"
Tech Sheet 6064	

Carbon Steel Body, Stainless Steel Disc

PN16, FPM Liner, Lever Operated	
0999	Flange Size
2014LI 08	1.1/2"
2014LI 09	2"
2014LI 10	2.1/2"
2014LI 11	3"
2014LI 12	4"
2014LI 13	5"
2014LI 14	6"
2014LI 16	8"
Tech Sheet 6064	

Stainless Steel Body, Stainless Steel Disc

PN16, FPM Liner, Lever Operated	
0999	Flange Size
2014LV 08	1.1/2"
2014LV 09	2"
2014LV 10	2.1/2"
2014LV 11	3"
2014LV 12	4"
2014LV 13	5"
2014LV 14	6"
2014LV 16	8"
Tech Sheet 6064	

Ductile Iron Body, Ductile Iron ENP Disc

PN16, NBR Liner, Lever Operated	
0999	Flange Size
2014LD 09	2"
2014LD 10	2.1/2"
2014LD 11	3"
2014LD 12	4"
2014LD 13	5"
2014LD 14	6"
2014LD 16	8"
2014LD 18	10"
Tech Sheet 6064	

RUST-OLEUM®

You might also need...
Maintenance Paint
...see pages **1561-1567**



Butterfly Valve Accessories

Features:

- Cast iron housing
- Stainless steel spindle
- Lockable
- To suit FT Pro 2014W and 2014L butterfly valves



Gearbox for Butterfly Valves

0999	Size	DN
2014GB 09	2"	50
2014GB 10	2.1/2"	65
2014GB 11	3"	80
2014GB 12	4"	100
2014GB 13	5"	125
2014GB 14	6"	150
2014GB 16	8"	200
2014GB 18	10"	250
2014GB 20	12"	300
2014GB 22	14"	350
Tech Sheet 6067		

Features:

- Add-on price for kit and switch box
- Aluminium IP67 enclosure
- Beacon indicator
- 2 x SPDT 250V DC/AC V3 micro switches
- 2 x M20 cable entries
- Stainless steel bracket

Can be used with any ISO top valve. The valve stem will require some machining at an additional cost. Contact sales for more information.



Switch Box Kit for Lever Operated Butterfly Valve

0921	Size	DN
2014LSB 08	1.1/2"	40
2014LSB 09	2"	50
2014LSB 10	2.1/2"	65
2014LSB 11	3"	80
2014LSB 12	4"	100
2014LSB 13	5"	125
2014LSB 14	6"	150
2014LSB 16	8"	200
2014LSB 18	10"	250
Tech Sheet 6068		

Chain Wheel option available on request. Contact Sales for more information

You might also need...
Flange Bolt Kits
...see page **1384**



Fluid-Air Components Ltd

Y STRAINERS

Brass Y Strainers

- Mesh Size =1.5mm up to 2" valve

Working Temperature:
-20°C to +110°C


Maximum Working Pressure:
20 bar



BSPP

0442	Thread
YS-12	1/2"
YS-34	3/4"
YS-1	1"
YS-114	1.1/4"
YS-112	1.1/2"
YS-2	2"
YS-212	2.1/2"
YS-3	3"
YS-4	4"
Tech Sheet 10302	

Strainers for YS Series



Stainless Steel AISI 304

0446	To Suit
192-12-STRAINER	YS-12
192-34-STRAINER	YS-34
192-1-STRAINER	YS-1
192-114-STRAINER	YS-114
192-112-STRAINER	YS-112
192-2-STRAINER	YS-2
192-212-STRAINER	YS-212
192-3-STRAINER	YS-3
192-4-STRAINER	YS-4
Tech Sheet 2032	

Stainless Steel Y Strainers

- 0.4mm perforations
- Suitable for saturated steam up to 10 bar

Working Temperature:
-25°C to +180°C

Maximum Working Pressure:
800 psi (55.16 bar)

stainless steel



BSPP

0900	Thread
2049-38	3/8"
2049-12	1/2"
2049-34	3/4"
2049-1	1"
2049-114	1.1/4"
2049-112	1.1/2"
2049-2	2"
Tech Sheet 2049	

NPT

0900	Thread
2049-12N	1/2"
2049-34N	3/4"
2049-1N	1"
2049-114N	1.1/4"
2049-112N	1.1/2"
2049-2N	2"
Tech Sheet 2049	

Bespoke Strainer Baskets are also available on request. Contact Sales for more information

Fluid-Air Components Ltd

Y STRAINERS

Brass Y Strainers

Features:
- 0.5mm perforations for 1/4" to 2" and 0.8mm perforations for 2.1/2" upwards

Working Temperature:
-20°C to +110°C



BSPP

0089	Thread	Max Pressure bar
IT192-14	1/4"	20
IT192-38	3/8"	20
IT192-12	1/2"	20
IT192-34	3/4"	20
IT192-1	1"	20
IT192-114	1.1/4"	20
IT192-112	1.1/2"	20
IT192-2	2"	20
IT192-212	2.1/2"	16
IT192-3	3"	16
IT192-4	4"	16
Tech Sheet 6134		

Features:
- Nickel plated body
- 0.5mm perforations

Working Temperature:
-20°C to +110°C

Maximum Working Pressure:
20 bar



BSPP

0089	Thread
IT193-14	1/4"
IT193-38	3/8"
IT193-12	1/2"
IT193-34	3/4"
IT193-1	1"
IT193-114	1.1/4"
IT193-112	1.1/2"
IT193-2	2"
Tech Sheet 6499	

Y STRAINERS

stainless steel

HAITIMA

Stainless Steel Y Strainers

Features:
- 0.4mm perforations

Working Temperature:
-20°C to +200°C



Flanged PN16

0982	Flange Size	Max Pressure bar
2049SL16 04	1/2"	16
2049SL16 05	3/4"	16
2049SL16 06	1"	16
2049SL16 07	1.1/4"	16
2049SL16 08	1.1/2"	16
2049SL16 09	2"	16
2049SL16 10	2.1/2"	16
2049SL16 11	3"	16
2049SL16 12	4"	16
2049SL16 13	5"	16
2049SL16 14	6"	16
Tech Sheet 1877		

Flanged ANSI150

0982	Flange Size	Max Pressure bar
2049SL150 04	1/2"	19.6
2049SL150 05	3/4"	19.6
2049SL150 06	1"	19.6
2049SL150 08	1.1/2"	19.6
2049SL150 09	2"	19.6
2049SL150 10	2.1/2"	19.6
2049SL150 11	3"	19.6
2049SL150 12	4"	19.6
2049SL150 13	5"	19.6
2049SL150 14	6"	19.6
Tech Sheet 1874		

Fluid-Air Components Ltd

Y STRAINERS

Cast Iron Y Strainers

Features:
- 1.5mm perforations
- Suitable for saturated steam up to 10 bar

Working Temperature:
-10°C to +120°C at 16 bar
-10°C to +230°C at 12.8 bar

Maximum Working Pressure:
16 bar



Flanged PN16

0927	Flange Size
E21 09	2"
E21 10	2.1/2"
E21 11	3"
E21 12	4"
E21 13	5"
E21 14	6"
E21 16	8"
Tech Sheet 6138	

Ductile Iron Y Strainers

Features:
- 1.5mm perforations for 2" to 6". 2mm perforations for 8" upwards

Working Temperature:
0°C to +80°C

Maximum Working Pressure:
16 bar



Flanged PN16

0909	Flange Size
HUKYS 09W	2"
HUKYS 10W	2.1/2"
HUKYS 11W	3"
HUKYS 12W	4"
HUKYS 13W	5"
HUKYS 14W	6"
HUKYS 16W	8"
HUKYS 18W	10"
HUKYS 20W	12"
Tech Sheet 6137	



You might also need a...
Lugged & Tapped Butterfly Valve
...see page **970**

Fluid-Air Components Ltd

GLOBE VALVES

FT PRO

Bronze Globe Valves

- BS 5154 Series B

Working Temperature:
-10°C to +100°C

Maximum Working Pressure:
20 bar



Type 6062, BSPP

0090	Thread
GBV-12	1/2"
GBV-34	3/4"
GBV-1	1"
GBV-114	1.1/4"
GBV-112	1.1/2"
GBV-2	2"
Tech Sheet 2031	

Bronze Self-Closing Lever Globe Valve

- PTFE Disk
- Stainless steel spring

Working Temperature:
-10°C to +180°C

Maximum Working Pressure:
16 bar



BSPP

0238	Thread
SC/LV/G1003-12	1/2"
SC/LV/G1003-34	3/4"
SC/LV/G1003-1	1"
Tech Sheet 10325	

Stainless Steel Globe Valves

Features:
- Investment casting
- Non-rising stem

Working Temperature:
-25°C to +180°C

Maximum Working Pressure:
200 psi (13.8 bar)



BSPP

0900	Thread
2028-12	1/2"
2028-34	3/4"
2028-1	1"
2028-114	1.1/4"
2028-112	1.1/2"
2028-2	2"
Tech Sheet 6002	

Cast Iron Globe Valves

Features:
- Rising stem
- RAL 7011
- Suitable for saturated steam up to 10 bar

Working Temperature:
-10°C to +300°C

Maximum Working Pressure:
16 bar



Flanged PN16 RF

0912	Flange Size
479 04	1/2"
479 05	3/4"
479 06	1"
479 07	1.1/4"
479 08	1.1/2"
479 09	2"
479 10	2.1/2"
479 11	3"
479 12	4"
479 13	5"
479 14	6"
479 16	8"
Tech Sheet 6090	

brownall®



You might also need...
Boiler Vent Valves
...see page **979**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

GLOBE VALVES

Stainless Steel Globe Valves

Features:
- Reduced bore
- ATEX approved
- NACE MR0175
- Conforms to BS 5352

Working Temperature:
-50°C to +450°C

Maximum Working Pressure:
110 bar



Class 800, NPT

0905	Thread
GL800S-12	1/2"
GL800S-34	3/4"
GL800S-1	1"
GL800S-114	1.1/4"
GL800S-112	1.1/2"
GL800S-2	2"
Tech Sheet 6014	

Class 800, Socket Weld

0905	Thread
GL800S-12S	1/2"
GL800S-34S	3/4"
GL800S-1S	1"
GL800S-114S	1.1/4"
GL800S-112S	1.1/2"
GL800S-2S	2"
Tech Sheet 6014	

Carbon Steel Globe Valves

Features:
- Reduced bore
- ATEX approved
- NACE MR0175
- Conforms to BS 5352

Working Temperature:
-29°C to +425°C

Maximum Working Pressure:
138 bar



Class 800, NPT

0905	Thread
GL800C-12	1/2"
GL800C-34	3/4"
GL800C-1	1"
GL800C-114	1.1/4"
GL800C-112	1.1/2"
GL800C-2	2"
Tech Sheet 6014	

Class 800, Socket Weld

0905	Thread
GL800C-12S	1/2"
GL800C-34S	3/4"
GL800C-1S	1"
GL800C-114S	1.1/4"
GL800C-112S	1.1/2"
GL800C-2S	2"
Tech Sheet 6014	



You might also need...
Class 800 Check Valves
...see page **965**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

GLOBE VALVES

Ductile Iron Globe Valves

Features:
- PN16/25 RF flanged ends up to 2
- ATEX approved
- Non-rising stem
- Bolted bonnet
- RAL 9006
- Suitable for saturated steam up to 10 bar

Working Temperature:
-10°C to +350°C



Flanged PN16 RF, Bellows Sealed

0905	Flange Size	Max Pressure bar
476 04	1/2"	25
476 05	3/4"	25
476 06	1"	25
476 07	1.1/4"	25
476 08	1.1/2"	25
476 09	2"	25
476 10	2.1/2"	16
476 11	3"	16
476 12	4"	16
476 13	5"	16
476 14	6"	16
476 16	8"	16
	Tech Sheet 6091	

Carbon Steel Globe Valves

Features:
- ATEX approved
- Non-rising stem
- Bolted bonnet
- RAL 5002
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +400°C

Maximum Working Pressure:
40 bar



Flanged PN40 RF, Bellows Sealed

0905	Flange Size
475 04	1/2"
475 05	3/4"
475 06	1"
475 07	1.1/4"
475 08	1.1/2"
475 09	2"
475 10	2.1/2"
475 11	3"
475 12	4"
475 13	5"
475 14	6"
475 16	8"
	Tech Sheet 6092

GLOBE VALVES

stainless steel

HAITIMA

Stainless Steel Globe Valves

Features:
- Investment casting
- Non-rising stem

Working Temperature:
-20°C to +200°C



Flanged PN16

0982	Flange Size	Max Pressure bar
2053SL16 06	1"	16
2053SL16 08	1.1/2"	16
2053SL16 09	2"	16
2053SL16 10	2.1/2"	16
2053SL16 11	3"	16
2053SL16 12	4"	16
2053SL16 14	6"	16
	Tech Sheet 6086	

Flanged ANSI150

0982	Flange Size	Max Pressure bar
2053SL150 06	1"	19.6
2053SL150 08	1.1/2"	19.6
2053SL150 09	2"	19.6
2053SL150 10	2.1/2"	19.6
2053SL150 11	3"	19.6
2053SL150 12	4"	19.6
	Tech Sheet 6087	

BALANCING VALVES

Screwed Balancing Valves

Features:
- BSPP threads up to 3/4" and BSPT threads for 1" upwards
- Comes complete with test points
- For use in heating and cooling systems and other water systems

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 25 bar



Bronze, Fixed Orifice

0974	Thread
T3010-12	1/2"
T3010-34	3/4"
T3010-1	1"
T3010-114	1.1/4"
T3010-112	1.1/2"
T3010-2	2"

Tech Sheet 6153

Features:
- Design in accordance to BS 7350:1990
- Comes complete with test points
- For use in heating and cooling systems and other water systems

Working Temperature: -10°C to +110°C

Maximum Working Pressure: 25 bar

WRAS



Bronze, Variable Orifice, BSPP

0915	Thread
9505-12	1/2"
9505-34	3/4"
9505-1	1"
9505-114	1.1/4"
9505-112	1.1/2"
9505-2	2"

Tech Sheet 6156

Features:
- Design in accordance to BS 7350:1990
- Comes complete with test points
- For use in heating and cooling systems and other water systems

Working Temperature: -10°C to +110°C

Maximum Working Pressure: 25 bar



DZR Brass, Fixed Orifice, BSPP

0915	Thread
9515-12	1/2"
9515-34	3/4"
9515-1	1"
9515-114	1.1/4"
9515-112	1.1/2"
9515-2	2"

Tech Sheet 6154

Flanged Balancing Valves

Features:
- To suit PN16 flanged ends
- The accuracy of flow measurement at normal velocities is ±3%
- Can be used as a single unit or close-coupled to other regulating or isolating valves

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 16 bar



Stainless Steel, Orifice Plate

0974	Flange Size
9200 10	2.1/2"
9200 11	3"
9200 12	4"
9200 13	5"
9200 14	6"
9200 16	8"

Tech Sheet 6160

Features:
- Design in accordance to BS 7350:1990
- Comes complete with test points
- For use in heating and cooling systems and other water systems

*Will be painted black and is from a different manufacturer

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 16 bar



Ductile Iron, Flanged PN16, Fixed Orifice

0909	Flange Size
T3020 09	2"*
9201 10	2.1/2"
9201 11	3"
9201 12	4"
9201 13	5"
9201 14	6"
9201 16	8"
9201 18	10"

Tech Sheet 6157

Test Points

Features:
- EPDM seal

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 25 bar



DZR Brass, Test Points, BSPT

0915	Thread
HUKTP-14R	1/4" Red
HUKTP-14B	1/4" Blue
HUKTP-12	1/2"

Air Vents

Features:

- Must be installed in the vertical position only

Working Temperature:
0°C to +110°C

Maximum Working Pressure:
10 bar



Brass, Auto Air Vent, BSPP Male

0928	Size
AAV-38	3/8"
AAV-12	1/2"
Tech Sheet 6164	

AUTOMATIC AIR ELIMINATION

brownall®

Air Eliminators

Maximum Working Temperature:
+93°C

Maximum Working Pressure:
10 bar



BSPP

0115	Description	Inlet	Outlet
AE-A	Type A Vertical	1/2"	3/8"
AE-B	Type B Vertical Lockshield Isolator	1/2"	3/8"
AE-C	Type C Vertical Lockshield & Check Valve	1/2"	3/8"
Tech Sheet 547			

Service Kits

0115	Description
AE-SP-ABD	Float Assembly for Type A, B and D Valve
AE-SP-C	Float Assembly for Type C Valve
Tech Sheet 547	

Boiler Vent Valves

Maximum Working Temperature:
+93°C

Maximum Working Pressure:
7 bar



Univent Boiler Vent Valves, Fig 1688, BSPP

0115	Thread
UV-1688-025D	1"
UV-1688-032D	1.1/4"
UV-1688-050D	2"
Tech Sheet 546	

Maximum Working Temperature:
+93°C

Maximum Working Pressure:
7 bar



3 Way Boiler Vent Valves, Fig 1988, BSPP

0115	Thread
VCN-1988-025	1"
VCN-1988-040	1.1/2"
VCN-1988-050	2"
Tech Sheet 548	

Cannot see the product you're looking for? Contact us. More often than not, we can acquire that product.

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PRESSURE REDUCING VALVES

Brass Pressure Reducing Valves

Body in nickel plated brass. Adjustable outlet pressure: between 1 to 5.5 bar (up to 1") or 1 to 6 bar (1.1/4" onwards). Factory setting 3 bar.

Working Temperature: -0°C to +80°C

Maximum Inlet Pressure: 25 bar



Type 143, Female, BSPP, 1/4" Gauge Ports

0089	Thread
143-12	1/2"
143-34	3/4"
143-1	1"
143-114	1.1/4"
143-112	1.1/2"
143-2	2"
143-212	2.1/2"
143-3	3"
143-4	4"
Tech Sheet 10522	

Body in dezincification resistant brass. Adjustable outlet pressure: between 1 to 5.5 bar (up to 1") or 1 to 6 bar (1.1/4" onwards). Factory setting 4 bar.

Working Temperature: 0°C to +80°C

Maximum Inlet Pressure: 25 bar

WRAS approval for 1/2", 3/4" and 1" models only.



Type 243, Female, BSPP, 1/4" Gauge Ports

0089	Thread
IT243-12	1/2"
IT243-34	3/4"
IT243-1	1"
IT243-114	1.1/4"
IT243-112	1.1/2"
IT243-2	2"
Tech Sheet 60357	

FT PRO

You might also need...
Gauges
...see page **410**



Fluid-Air Components Ltd

INSTRUMENTATION MANIFOLDS

stainless steel

PANAM

Manifold Valves

Working Temperature: -29°C to +121°C

Maximum Working Pressure: 414 bar

2 Valve manifold pipe to pipe design for separate mounting, connection system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Pipe to Pipe, NPT

0380	Thread
P2VM-SS-8-R	1/2"
Tech Sheet 10216	

3 Valve manifold pipe to pipe design for connecting system impulse lines and transmitters. This valve consists of 1/2" NPT female connectors on 54mm centres and 1 equalizer valve and 2 block valves.

Other mounting options are available on request.




3 Valve Manifold, Pipe to Pipe, NPT

0380	Thread
P3VM-SS-8-R	1/2"
Tech Sheet 10216	

2 Valve manifold remote mount flange to flange design for separate mounting, connecting system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Remote Mount, NPT

0380	Thread
P2VM-SS-8-RM	1/2"
Tech Sheet 10216	

PANAM

You might also need...
Stainless Steel Tube Fittings
...see pages **166-178**



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

NEEDLE VALVES

FT PRO

Brass Needle Valves

Working Temperature:
0°C to +100°C

Maximum Working Pressure:
100 bar





Female x Female, BSPP

0441	Thread
EV-18	1/8"
EV-14	1/4"
EV-38	3/8"
EV-12	1/2"
Tech Sheet 10028	

Male x Male, BSPT

0441	Thread
EVMM-18	1/8"
EVMM-14	1/4"
EVMM-38	3/8"
EVMM-12	1/2"
Tech Sheet 10029	

NEEDLE VALVES

stainless steel

GENEBRE

Stainless Steel Needle Valves

Features:

- Safety bonnet lock prevents accidental loosening
- Flow can be controlled in both directions

Working Temperature:
-54°C to +232°C

Maximum Working Pressure:
413 bar at +38°C



Female x Female, BSPP

0902	Thread
2225-14	1/4"
2225-38	3/8"
2225-12	1/2"
2225-34	3/4"
2225-1	1"
Tech Sheet 6161	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

NEEDLE VALVES

stainless steel

PANAM

3,000 psi Rated Mini Needle Valve

Working Temperature:
-50°C to +121°C

Maximum Working Pressure:
205 bar

Seal: Viton



NPT

0292	Thread	Description
PMV-H-S-4-FF-V	1/4"	Female x Female
PMV-H-S-4-MF-V	1/4"	Male x Female
Tech Sheet 10506		



You might also need...
Hydraulic Tubing
...see page **181**

6,000 psi Rated Imperial Needle Valves

The 'IB' series of needle valves are specially designed and manufactured for use in corrosive and hazardous environments.

These valves are for use in process control, instrumentation and flow control applications.

Feature Benefits

One piece body construction for strength and safety.

Non rotating Vee tip design, which forms a bearing joint with the stem eliminating any rotation between the plug and seat on closure ensuring long life.

Testing: All valves are 100% factory tested and complete traceability is available upon request.

Material: Body, panel nut, washer and gland nut A479-316

Stem: A479-316 / 17-4PH

Packing: PTFE

Grub Screw: Steel plated

Handle: Stainless steel

Vee Tip: A 564-630

Working Temperature:
-29°C to +121°C

Maximum Working Pressure:
413 bar (6,000 psi)

Female x Female, NPTF

0292	Thread
PNV-IB-S-2-FF	1/8"
PNV-IB-S-4-FF	1/4"
PNV-IB-S-6-FF	3/8"
PNV-IB-S-8-FF	1/2"
PNV-IB-S-12-FF	3/4"
PNV-IB-S-16-FF	1"
Tech Sheet 2156	



Female x Female, BSPP

0292	Thread
2018-6938	1/4"
2018-6946	3/8"
2018-6953	1/2"
Tech Sheet 10036	

Male x Female, NPTF

0292	Thread
PNV-IB-S-2-MF	1/8"
PNV-IB-S-4-MF	1/4"
PNV-IB-S-6-MF	3/8"
PNV-IB-S-8-MF	1/2"
PNV-IB-S-12-MF	3/4"
PNV-IB-S-16-MF	1"
Tech Sheet 2156	



OD Compression

0292	OD
NV6000-18	1/8"
NV6000-14	1/4"
NV6000-38	3/8"
NV6000-12	1/2"
NV6000-34	3/4"
NV6000-1	1"
Tech Sheet 2156	



10,000 psi Rated Imperial Needle Valves

The 'HP' series of needle valves are specially designed and manufactured for use in corrosive and hazardous environments.

These valves are for use in process control, instrumentation and flow control applications.

Feature Benefits

One piece body construction for strength and safety.

Non rotating Vee tip design, which forms a bearing joint with the stem eliminating any rotation between the plug and seat on closure ensuring long life.

Testing: Each valve is hydrostatically tested in accordance with MSS-SP-99. This procedure includes testing of the body cavity. A Hydrostatic test is performed with pure water or other liquids of similar or lower viscosity at 1.5 times and seat leakage test at 1.1 times of the maximum working pressure.

Each valve is also tested with nitrogen gas at 1000psi for seat, seal and shell leakage. Other tests like vibration, temperature and helium are available upon request.

Material: Body, stem, packing washer, lock nut and gland retainer A479-316/A-105

Gland Packing: Glass Filled PTFE

Packing: PTFE

Handle: Stainless steel

Dust Cap: Plastic

Vee Tip: A 564-630

Working Temperature:
-50°C to +93°C

Maximum Working Pressure:
700 bar (10,000 psi)

Female x Female, NPTF

0292	Thread
PNV-HP-S-2-FF	1/8"
PNV-HP-S-4-FF	1/4"
PNV-HP-S-6-FF	3/8"
PNV-HP-S-8-FF	1/2"
PNV-HP-S-16-FF	1"
Tech Sheet 2157	



Male x Female, NPTF

0292	Thread
PNV-HP-S-2-MF	1/8"
PNV-HP-S-4-MF	1/4"
PNV-HP-S-6-MF	3/8"
PNV-HP-S-8-MF	1/2"
PNV-HP-S-12-MF	3/4"
PNV-HP-S-16-MF	1"
Tech Sheet 2157	



FAC
Fluid-Air Components Ltd

The Engineers Choice



FT Pro products have been meticulously selected based on their superior quality, dependability, and durability. Our products are engineered by engineers for engineers and produced by leading fluid power manufacturers, ensuring they meet even the most rigorous application demands.

We understand that all application requirements are unique, and that's why we only offer products that we know will provide the most effective solution.

At FT Pro, we work closely with our customers to ensure that we provide tailored solutions that meet their exact requirements. Whether you need products for hydraulic systems, pneumatic systems, or any other fluid power application, FT Pro has the product to support you and help you find the right outcome.

Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

Pressure Relief Valves

With the introduction of the European Pressure Equipment Directive, which recommend relevant testing and quality assurance with appropriate certification.


This range of pressure relief valves are manufactured and tested in accordance to the regulations (DIN 3320.AD SHEET A2/A4) which meets applicable specifications both nationally and internationally. Compliance with the component test report, by the identification the manufacture provides a guarantee for the specified setting values.

Test certificates come as standard.

Note: This product is CE marked, to comply with legislation.

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
15 bar



Nominal Diameter 8mm, 1/4" BSPP

0093	Set Pressure Bar
2035-0773	1
2042-2887	1.5
2042-2895	2
2020-8860	2.5
2042-2903	3
2042-2911	3.5
2020-8864	4
2042-2929	4.5
2020-8872	5
2042-2937	5.5
2042-2945	6
2042-2952	6.5
2042-2960	7
2020-8880	7.5
2020-8898	8
2042-2978	8.5
2031-7020	9
2020-8906	10
2042-2986	10.5
2020-8914	11
2020-8922	11.5
2020-8930	12
2020-8948	15
Tech Sheet 1762	

Nominal Diameter 10mm, 1/2" BSPP

0093	Set Pressure Bar
2042-2994	0.5
2042-3000	1.5
2042-3018	2.5
2042-3026	3.5
2020-9052	4
2020-9060	5
2042-3034	5.5
2020-9086	6
2042-3042	6.5
2020-9094	7
2020-9102	7.5
2020-9110	8
2042-3059	8.5
2042-3067	9
2020-9128	10
2042-3075	10.5
2020-9136	11
2020-9144	11.5
2020-9151	12
2042-3083	12.5
2020-9169	15
2042-3091	16
2042-3109	30
Tech Sheet 1762	

Nominal Diameter 10mm, 3/8" BSPP

0093	Set Pressure Bar
2020-8955	5
2020-8971	6
2020-8989	7
2020-8997	8
2020-9003	10
2020-9011	11
2020-9029	12
2020-9045	15
Tech Sheet 1762	

Nominal Diameter 10mm, 3/4" BSPP

0093	Set Pressure Bar
2020-9177	6
2020-9193	8
2020-9201	10
2020-9219	11
Tech Sheet 1762	

Individual test certificates come as standard

Other relief settings available on special request

Pressure Relief Valves - Series 6000

Working Temperature:
-15°C to +180°C

Maximum Set Pressure:
20.1 bar



High Lift Pressure Relief Valve, Male BSPT

0095	Thread	Set Pressure Bar
6000/06/G/5.5	1/4"	5.5
6000/06/H/9.0	1/4"	9
6000/06/J/11.0	1/4"	11
Tech Sheet 10341		

Individual test certificates to be requested at the time of order

FAC
Fluid-Air Components Ltd

PRESSURE RELIEF VALVES

Compact Relief Valve DN6

Relief valves to blow out non-poisonous and non-flammable gases into the atmosphere in order to protect pressure tanks against overpressure.
Please note: Only relief valves that have been set and sealed with lead (plumbed) by us can be delivered with the component symbols, it is thus absolutely necessary to indicate the setting pressure in bar. As functional test, relief valves may be aerated by the way of pulling the haul-off bolt. Repairs may only be carried out by the manufacturer.


Technical Data

- Connection thread: G1/4, G3/8
- Setting range: 4,5 to 24 bar (5 steps)
- Opening pressure difference: <10%
- Closing pressure difference: <10%
- Material: Brass
- Seal: Viton

Important: The supply connection to the relief valve should not be <DN6, the pressure drop in the supply connection not >3%.

Working Temperature:
-10°C to +150°C

Maximum Working Pressure:
24 bar (PN24)



Male, Thread, BSPP

9168	Thread	Set At Bar	Dimensions mm	
			L	Hex
469.23-5.0BAR	1/4"	5.0	65	17
469.24-7.0BAR	1/4"	7.0	65	17
469.24-9.0BAR	1/4"	9.0	65	17
469.25-11.0BAR	1/4"	11.0	65	17
469.26-16.0BAR	1/4"	16.0	65	17
469.27-20.0BAR	1/4"	20.0	65	17
469.33-5.0BAR	3/8"	5.0	65	19
469.34-7.0BAR	3/8"	7.0	65	19
469.34-9.0BAR	3/8"	9.0	65	19
469.35-11.0BAR	3/8"	11.0	65	19
469.36-16.0BAR	3/8"	16.0	65	19
469.37-20.0BAR	3/8"	20.0	65	19

Exhaust Capacity Air
The exhaust capacities indicated in the table are the minimum values reached when air pressure is raised by 10% above the set pressure.

Set Pressure Bar	Exhaust Flow Capacity (normal condition)	
	m^3/h	l/m
6	60	1000
10	110	1833
11	125	2083
14	155	2583

Intermediate values can be interpolated.

More variations available. Special set pressures, body materials & large threads.

Type 1776

All type 1776 valves are pre-set and sealed to prevent tampering.

Pre-set pressure relief valves are precision manufactured to open at the pre-set pressure and discharge fluid until pressure drops to acceptable levels to protect against equipment damage or personal injury.

- Dual certification* of ASME BPVC Section XIII and UKCA/CE for PE(S)R 2016 and PED 2014/68/EU
- Automatically vents at selected pressure
- Automatically resets when pressure returns to 'normal'
- Brass body with stainless steel internal components

Please note:
Removal of the pull ring will invalidate ASME certification but will still conform to UKCA/CE

Male, 1/4" NPT

0090	Set Pressure PSI	SCFM
1776K-0-05	5	9
1776K-0-10	10	11
1776K-0-15	15	13
1776K-0-20	20	15
1776K-0-30	30	19
1776K-0-40	40	24
1776K-0-50	50	28
1776K-0-60	60	33
1776K-0-75	75	39
Tech Sheet 835		



Working Temperature:
-18°C to +200°C

*Dual certification applies from 30 PSI upwards. Pressure ranges from 5 to 20 PSI will offer no accreditations that meet UK/European standards

**More variations available. Special set pressures, Body materials, valve serialisation & larger threads.
Test certificates are available on request at an additional cost.**

Fluid-Air Components Ltd

PRESSURE RELIEF VALVES

Atmospheric Pressure Relief Valves, 6mm-15mm

Seetru Atmospheric Discharge Pressure Relief valves are compact, highly efficient and incorporate the exclusive 'Tutchtite' seal technology to give repeatable bubble tight sealing performance.

Suitable for air and gases including refrigerant.

Type approved and/or manufactured in conformance with national and international standards which include BS6759 Part 2 and 3, ISO 4126 and TUV (Germany) in accordance with AD Merkblatt A2. Compliant with the requirements of the European Equipment Directive 97/23/EC and CE marked flow rates calculated

Std Ltrs/Sec of Air @ 15°C

Seals: Viton

Sealing: Elastomer

Working Temperature:
-15°C to +200°C



Nominal Bore 6mm, 1/4" BSPT Male

0171	Flow	Set Pressure Bar
SEE010EA1B	25	5.5
SEE0107A1B	38	9
SEE0106A1B	46	11
Tech Sheet 10342		

Nominal Bore 8mm, 1/4" BSPP Male

0171	Flow	Set Pressure Bar
SEE9111A1B	12	1
SEE9112A1B	16	1.5
SEE9113A1B	19	2
SEE9114A1B	22	2.5
SEE9115A1B	26	3
SEE911AA1B	30	3.5
SEE911BA1B	34	4
SEE911CA1B	37	4.5
SEE911EA1B	44	5.5
SEE911FA1m	47	6
SEE911GA1B	51	6.5
SEE911HA1B	54	7
SEE9119A1B	57	7.5
SEE9118A1B	61	8
SEE911JA1B	64	8.5
SEE9117A1B	68	9
SEE911LA1B	74	10
SEE911MA1B	78	10.5
SEE9116A1B	81	11
SEE911NA1B	85	11.5
SEE911PA1B	88	12
SEE911XA1B	109	15
Tech Sheet 10345		

Nominal Bore 8mm, 1/4" BSPT Male

0171	Flow	Set Pressure Bar
SEE011EA1B	44	5.5
SEE0117A1B	68	9
SEE0116A1B	81	11
Tech Sheet 10345		

Nominal Bore 8mm, 3/8" BSPT Male

0171	Flow	Set Pressure Bar
SEE021DA1B	40	5
SEE0216A1B	81	11
SEE021PA1B	88	12
Tech Sheet 10345		

Nominal Bore 8mm, 3/8" BSPP Male

0171	Flow	Set Pressure Bar
SEE921FA1B	47	6
SEE921HA1B	54	7
SEE9218A1B	61	8
SEE921LA1B	74	10
SEE9216A1B	81	11
SEE921PA1B	88	12
SEE921XA1B	109	15
Tech Sheet 10345		

Nominal Bore 10mm, 1/2" BSPT Male

0171	Flow	Set Pressure Bar
SEE032EA1B	170	5.5
SEE0327A1B	106	9
SEE0326A1B	127	11
Tech Sheet 10343		

Nominal Bore 10mm, 1/2" BSPP Male

0171	Flow	Set Pressure Bar
SEE9320A1B	12	0.5
SEE9322A1B	24	1.5
SEE9324A1B	36	2.5
SEE932AA1B	47	3.5
SEE932BA1B	52	4
SEE932DA1B	63	5
SEE932EA1B	68	5.5
SEE932FA1B	74	6
SEE932GA1B	79	6.5
SEE932HA1B	84	7
SEE9329A1B	90	7.5
SEE9328A1B	95	8
SEE932JA1B	100	8.5
SEE9327A1B	106	9
SEE932LA1B	116	10
SEE932MA1B	122	10.5
SEE9326A1B	127	11
SEE932NA1B	132	11.5
SEE932PA1B	138	12
SEE932RA1B	143	12.5
SEE932XA1B	170	15
SEE932YA1B	180	16
Tech Sheet 10343		

Nominal Bore 10mm, 3/4" BSPP Male

0171	Flow	Set Pressure Bar
SEE942FA1B	74	6
SEE942HA1B	84	7
SEE9428A1B	95	8
SEE9427A1B	106	9
SEE9426A1B	127	11
Tech Sheet 10343		

Nominal Bore 15mm, 3/4" BSPT Male

0171	Flow	Set Pressure Bar
SEE0447A1B	263	9
SEE0436A1B	315	11
Tech Sheet 10344		

Nominal Bore 15mm, 1" BSPT Male

0171	Flow	Set Pressure Bar
SEE0546A1B	315	11
Tech Sheet 10344		

Individual test certificates come as standard with abov

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAFETY VALVES

NABIC®

High Lift Safety Valves (Fig 500)

Applications: the Fig 500 high lift safety valve has been designed primarily for use on unvented hot water heating systems, where a high capacity, emergency steam relief capability is required. High capacity and resilient PTFE seating also make the Fig 500 ideal for steam, air and inert gas applications. A PTFE to Viton seating design is also available where greater seal tightness is required.

Construction: the Fig 500 is constructed in gunmetal with diaphragm protected working parts and PTFE to metal seating. All wetted parts are manufactured from dezincification resistant materials, approved by the ater Research Centre for use on potable water. Standard inlet and outlet connections have female threads to BS 21, with the outlet connection one size larger than the inlet. Sizes from DN20 upwards are available with flanged inlet connections; other thread forms are also available.



Please Note: due to pressure setting and certification of this product, normal delivery wil be up to 3 working days (manufacturers stock permitting), although a quicker service may be available if required. **Please contact our sales team.**

Features:

- Resilient PTFE seating designs
- High degree of seating tightness
- Suitable for hot water, steam and air
- High discharge capacity
- Diaphragm protected working parts
- Safe manual testing
- Easy inspection and cleaning
- Pressure setting locked and sealed
- Designed and tested to BS 6759
- Capacities certified by TOC

Working Temperature:
-20°C to +195°C

Maximum Working Pressure:
12.5 bar

WRAS

BSPP Inlet x BSPP Outlet

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500-15-1	1/2"	3/4"	1
500-15-3	1/2"	3/4"	3
500-15-4	1/2"	3/4"	4
500-15-5	1/2"	3/4"	5
500-15-5.5	1/2"	3/4"	5.5
500-15-6	1/2"	3/4"	6
500-15-6.5	1/2"	3/4"	6.5
500-15-7	1/2"	3/4"	7
500-15-7.5	1/2"	3/4"	7.5
500-15-8.5	1/2"	3/4"	8.5
500-15-10	1/2"	3/4"	10
500-15-10.5	1/2"	3/4"	10.5
500-15-11	1/2"	3/4"	11
500-15-11.5	1/2"	3/4"	11.5
500-20-1.5	3/4"	1"	1.5
500-20-2.5	3/4"	1"	2.5
500-20-3	3/4"	1"	3
500-20-3.5	3/4"	1"	3.5
500-20-4	3/4"	1"	4
500-20-5	3/4"	1"	5
500-20-5.5	3/4"	1"	5.5

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500-20-6	3/4"	1"	6
500-20-6.5	3/4"	1"	6.5
500-20-7	3/4"	1"	7
500-20-7.5	3/4"	1"	7.5
500-20-8	3/4"	1"	8
500-20-8.5	3/4"	1"	8.5
500-20-9	3/4"	1"	9
500-20-10	3/4"	1"	10
500-20-11	3/4"	1"	11
500-20-11.5	3/4"	1"	11.5
500-20-12	3/4"	1"	12
500-20-12.5	3/4"	1"	12.5
500-25-1.5	1"	1.1/4"	1.5
500-25-2	1"	1.1/4"	2
500-25-2.5	1"	1.1/4"	2.5
500-25-3	1"	1.1/4"	3
500-25-3.5	1"	1.1/4"	3.5
500-25-4	1"	1.1/4"	4
500-25-5.5	1"	1.1/4"	5.5
500-25-7	1"	1.1/4"	7
500-25-7.5	1"	1.1/4"	7.5

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500-25-8	1"	1.1/4"	8
500-25-8.5	1"	1.1/4"	8.5
500-25-11	1"	1.1/4"	11
500-25-12.5	1"	1.1/4"	12.5
500-32-3	1.1/4"	1.1/2"	3
500-32-3.5	1.1/4"	1.1/2"	3.5
500-32-5	1.1/4"	1.1/2"	5
500-32-7.5	1.1/4"	1.1/2"	7.5
500-32-8.5	1.1/4"	1.1/2"	8.5
500-32-10	1.1/4"	1.1/2"	10
500-32-11	1.1/4"	1.1/2"	11
500-40-1.5	1.1/2"	2"	1.5
500-40-3	1.1/2"	2"	3
500-40-3.5	1.1/2"	2"	3.5
500-40-4	1.1/2"	2"	4
500-40-7	1.1/2"	2"	7
500-40-7.5	1.1/2"	2"	7.5
500-40-12	1.1/2"	2"	12
500-50-3.5	2"	2.1/2"	3.5
500-50-7	2"	2.1/2"	7
500-50-12.5	2"	2.1/2"	12.5

Tech Sheet 1398

We have listed all the popular sizes and pressure ratings, however other variations are available.

Individual test certificates to be requested at the time of orde

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SAFETY VALVES

NABIC®

Safety Relief Valves (Fig 542)

Applications: the Fig 542 safety valve is an extremely versatile valve, suitable for use on hot water, steam or air. Although designed primarily for the protection of hot water boilers, its wide range of applications make it ideal as a general purpose safety valve.

Construction: the Fig 542 is of gunmetal construction with diaphragm protected working parts and PTFE to metal seating. All wetted parts manufactured from dezincification resistant materials, approved by the ater Research Centre for use on potable water. Inlet and outlet connections are of equal size, with female threads to BS 21. Sizes from DN32 upwards are also available with flanged inle connections.



Please Note: due to pressure setting and certification of this product, normal delivery wil be up to 3 working days (manufacturers stock permitting), although a quicker service may be available if required. **Please contact our sales team.**

Features:

- Resilient PTFE seating designs
- High degree of seat tightness
- Suitable for hot water, steam or air
- Diaphragm protected working parts
- Safe manual testing
- Easy inspection and cleaning
- Pressure setting locked and sealed
- Designed and tested to BS 6759
- Capacities certified by TOC

Working Temperature:
-20°C to +195°C

Maximum Working Pressure:
10.5 bar

WRAS

BSPP Inlet x BSPP Outlet

0115	Thread	Set Pressure Bar
542-15-1	1/2"	1
542-15-1.5	1/2"	1.5
542-15-2	1/2"	2
542-15-2.5	1/2"	2.5
542-15-3	1/2"	3
542-15-3.5	1/2"	3.5
542-15-4	1/2"	4
542-15-4.5	1/2"	4.5
542-15-5	1/2"	5
542-15-5.5	1/2"	5.5
542-15-6	1/2"	6
542-15-7	1/2"	7
542-15-7.5	1/2"	7.5
542-15-8	1/2"	8
542-15-8.5	1/2"	8.5
542-15-9	1/2"	9
542-15-9.5	1/2"	9.5
542-15-10	1/2"	10
542-15-10.5	1/2"	10.5
542-20-1	3/4"	1
542-20-1.5	3/4"	1.5
542-20-2	3/4"	2
542-20-2.5	3/4"	2.5
542-20-3	3/4"	3
542-20-3.5	3/4"	3.5
542-20-4	3/4"	4
542-20-4.5	3/4"	4.5
542-20-5	3/4"	5
542-20-5.5	3/4"	5.5
542-20-6	3/4"	6
542-20-7	3/4"	7

0115	Thread	Set Pressure Bar
542-20-7.5	3/4"	7.5
542-20-8	3/4"	8
542-20-8.5	3/4"	8.5
542-20-9	3/4"	9
542-20-10	3/4"	10
542-20-10.5	3/4"	10.5
542-25-1	1"	1
542-25-1.5	1"	1.5
542-25-2	1"	2
542-25-2.5	1"	2.5
542-25-3	1"	3
542-25-3.5	1"	3.5
542-25-4	1"	4
542-25-4.5	1"	4.5
542-25-5	1"	5
542-25-6	1"	6
542-25-7	1"	7
542-25-7.5	1"	7.5
542-25-8	1"	8
542-25-8.5	1"	8.5
542-25-9	1"	9
542-25-9.5	1"	9.5
542-25-10	1"	10
542-25-10.5	1"	10.5
542-32-1	1.1/4"	1
542-32-2.5	1.1/4"	2.5
542-32-3	1.1/4"	3
542-32-3.5	1.1/4"	3.5
542-32-4	1.1/4"	4
542-32-4.5	1.1/4"	4.5
542-32-5	1.1/4"	5

0115	Thread	Set Pressure Bar
542-32-6.5	1.1/4"	6.5
542-32-7	1.1/4"	7
542-32-8	1.1/4"	8
542-32-8.5	1.1/4"	8.5
542-32-9	1.1/4"	9
542-32-9.5	1.1/4"	9.5
542-32-10	1.1/4"	10
542-40-1	1.1/2"	1
542-40-1.5	1.1/2"	1.5
542-40-2	1.1/2"	2
542-40-3.5	1.1/2"	3.5
542-40-4	1.1/2"	4
542-40-5	1.1/2"	5
542-40-6	1.1/2"	6
542-40-7	1.1/2"	7
542-40-7.5	1.1/2"	7.5
542-40-8	1.1/2"	8
542-40-10	1.1/2"	10
542-40-10.5	1.1/2"	10.5
542-50-2	2"	2
542-50-3.5	2"	3.5
542-50-6	2"	6
542-50-7	2"	7
542-50-7.5	2"	7.5
542-50-8	2"	8
542-50-10	2"	10
542-50-10.5	2"	10.5
542-65-3	2.1/2"	3
542-65-4	2.1/2"	4
542-65-7.5	2.1/2"	7.5
	Tech Sheet 1399	

We have listed all the popular sizes and pressure ratings, however other variations are available.

Individual test certificates to be requested at the time of orde

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PRESSURE RELIEF VALVES

NABIC®

Pressure Relief Valves (Fig 500L)

Applications: Nabic pressure relief valves are intended for use where pressure tightness is required on the discharge side of the valve. They are ideal for pump relief, bypass relief, outside installations, and inflammable fluid

Construction: the valves are of gunmetal construction with top-guided copper alloy parts, chrome vanadium spring and PTFE to metal seating. O-Ring seals ensure pressure tightness at cover and cap joints. Available options are stainless steel springs, high pressure versions and Viton seat design.



Please Note: due to pressure setting and certification of this product, normal delivery wil be up to 3 working days (manufacturers stock permitting), although a quicker service may be available if required. **Please contact our sales team.**

Features:

- Resilient PTFE seating design
- High degree of seating tightness
- Suitable for liquids and gases
- Top-guided working parts
- Pressure tight on discharge side
- Designed and tested to BS 6759
- Flange inlets available

Working Temperature:
-20°C to +195°C

Maximum Working Pressure:
12.5 bar

WRAS

BSPP Inlet x BSPP Outlet

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500L-10-1	3/8"	1/2"	1
500L-10-1.5	3/8"	1/2"	1.5
500L-10-2	3/8"	1/2"	2
500L-10-2.5	3/8"	1/2"	2.5
500L-10-3	3/8"	1/2"	3
500L-10-3.5	3/8"	1/2"	3.5
500L-10-4	3/8"	1/2"	4
500L-10-5	3/8"	1/2"	5
500L-10-5.5	3/8"	1/2"	5.5
500L-10-6	3/8"	1/2"	6
500L-10-6.5	3/8"	1/2"	6.5
500L-10-8	3/8"	1/2"	8
500L-10-9.5	3/8"	1/2"	9.5
500L-10-10	3/8"	1/2"	10
500L-10-11	3/8"	1/2"	11
500L-10-12	3/8"	1/2"	12
500L-10-12.5	3/8"	1/2"	12.5
500L-15-1	1/2"	3/4"	1
500L-15-3	1/2"	3/4"	3
500L-15-4	1/2"	3/4"	4
500L-15-5	1/2"	3/4"	5
500L-15-5.5	1/2"	3/4"	5.5
500L-15-6	1/2"	3/4"	6
500L-15-6.5	1/2"	3/4"	6.5
500L-15-7	1/2"	3/4"	7
500L-15-7.5	1/2"	3/4"	7.5
500L-15-8.5	1/2"	3/4"	8.5

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500L-15-10	1/2"	3/4"	10
500L-15-10.5	1/2"	3/4"	10.5
500L-15-11	1/2"	3/4"	11
500L-15-11.5	1/2"	3/4"	11.5
500L-20-1.5	3/4"	1"	1.5
500L-20-2.5	3/4"	1"	2.5
500L-20-3	3/4"	1"	3
500L-20-3.5	3/4"	1"	3.5
500L-20-4	3/4"	1"	4
500L-20-5	3/4"	1"	5
500L-20-5.5	3/4"	1"	5.5
500L-20-6	3/4"	1"	6
500L-20-6.5	3/4"	1"	6.5
500L-20-7	3/4"	1"	7
500L-20-7.5	3/4"	1"	7.5
500L-20-8	3/4"	1"	8
500L-20-8.5	3/4"	1"	8.5
500L-20-9	3/4"	1"	9
500L-20-10	3/4"	1"	10
500L-20-11	3/4"	1"	11
500L-20-11.5	3/4"	1"	11.5
500L-20-12	3/4"	1"	12
500L-20-12.5	3/4"	1"	12.5
500L-25-1.5	1"	1.1/4"	1.5
500L-25-2	1"	1.1/4"	2
500L-25-2.5	1"	1.1/4"	2.5
500L-25-3	1"	1.1/4"	3

0115	Inlet Thread	Outlet Thread	Set Pressure Bar
500L-25-3.5	1"	1.1/4"	3.5
500L-25-4	1"	1.1/4"	4
500L-25-5.5	1"	1.1/4"	5.5
500L-25-7	1"	1.1/4"	7
500L-25-7.5	1"	1.1/4"	7.5
500L-25-8	1"	1.1/4"	8
500L-25-8.5	1"	1.1/4"	8.5
500L-25-11	1"	1.1/4"	11
500L-25-12.5	1"	1.1/4"	12.5
500L-32-3	1.1/4"	1.1/2"	3
500L-32-3.5	1.1/4"	1.1/2"	3.5
500L-32-5	1.1/4"	1.1/2"	5
500L-32-7.5	1.1/4"	1.1/2"	7.5
500L-32-8.5	1.1/4"	1.1/2"	8.5
500L-32-10	1.1/4"	1.1/2"	10
500L-32-11	1.1/4"	1.1/2"	11
500L-40-1.5	1.1/2"	2"	1.5
500L-40-3	1.1/2"	2"	3
500L-40-3.5	1.1/2"	2"	3.5
500L-40-4	1.1/2"	2"	4
500L-40-7	1.1/2"	2"	7
500L-40-7.5	1.1/2"	2"	7.5
500L-40-12	1.1/2"	2"	12
500L-50-3.5	2"	2.1/2"	3.5
500L-50-7	2"	2.1/2"	7
500L-50-12.5	2"	2.1/2"	12.5

Tech Sheet 20438

We have listed all the popular sizes and pressure ratings, however other variations are available.

Individual test certificates to be requested at the time of orde

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PRESSURE RELIEF VALVES

NABIC®

Pressure Relief Valves (Fig 542L)

Applications: NABIC liquid relief valves are intended for use where pressure tightness is required on the discharge side of the valve. They are ideal for use on pump relief and bypass relief applications, also on outside installations and where tamper-proof units are required.

Available options: stainless steel springs, high pressure versions and Viton seat design.

Construction: the valves are of gunmetal construction with top-guided copper alloy parts. Fitted with chrome vanadium spring as standard, they also incorporate the proven NABIC PTFE to metal seating design. O-Ring seals ensure pressure tightness at cover and cap joints.



Please Note: due to pressure setting and certification of this product, normal delivery wil be up to 3 working days (manufacturers stock permitting), although a quicker service may be available if required. **Please contact our sales team.**

Features:

- High degree of seat tightness
- Designed and tested to BS 6759
- Certified discharge table

Working Temperature:
-20°C to +195°C

Maximum Working Pressure:
12.5 bar

WRAS

BSPP Inlet x BSPP Outlet

0115	Thread	Set Pressure Bar
542L-15-1	1/2"	1
542L-15-1.5	1/2"	1.5
542L-15-2	1/2"	2
542L-15-2.5	1/2"	2.5
542L-15-3	1/2"	3
542L-15-3.5	1/2"	3.5
542L-15-4	1/2"	4
542L-15-4.5	1/2"	4.5
542L-15-5	1/2"	5
542L-15-6	1/2"	6
542L-15-7	1/2"	7
542L-15-8.5	1/2"	8.5
542L-15-10	1/2"	10
542L-15-10.5	1/2"	10.5
542L-20-1	3/4"	1
542L-20-1.5	3/4"	1.5
542L-20-2	3/4"	2
542L-20-2.5	3/4"	2.5
542L-20-3	3/4"	3
542L-20-3.5	3/4"	3.5
542L-20-5	3/4"	5
542L-20-6	3/4"	6

0115	Thread	Set Pressure Bar
542L-20-6.5	3/4"	6.5
542L-20-7	3/4"	7
542L-20-8	3/4"	8
542L-20-9	3/4"	9
542L-20-10	3/4"	10
542L-25-1	1"	1
542L-25-1.5	1"	1.5
542L-25-2	1"	2
542L-25-2.5	1"	2.5
542L-25-3	1"	3
542L-25-3.5	1"	3.5
542L-25-4	1"	4
542L-25-5	1"	5
542L-25-6	1"	6
542L-25-7	1"	7
542L-25-8	1"	8
542L-25-10	1"	10
542L-25-10.5	1"	10.5
542L-32-3	1.1/4"	3
542L-32-4	1.1/4"	4
542L-32-8	1.1/4"	8
542L-32-10	1.1/4"	10

0115	Thread	Set Pressure Bar
542L-32-10.5	1.1/4"	10.5
542L-40-1.5	1.1/2"	1.5
542L-40-2.5	1.1/2"	2.5
542L-40-5	1.1/2"	5
542L-40-6	1.1/2"	6
542L-40-7	1.1/2"	7
542L-40-10	1.1/2"	10
542L-50-1.5	2"	1.5
542L-50-2	2"	2
542L-50-4	2"	4
542L-50-7.5	2"	7.5
542L-50-8.5	2"	8.5
542L-50-9.5	2"	9.5
542L-50-10	2"	10
542L-50-10.5	2"	10.5
542L-65-2	2.1/2"	2
542L-65-3	2.1/2"	3
542L-65-3.5	2.1/2"	3.5
542L-65-5	2.1/2"	5
542L-80-4.5	3"	4.5
542L-80-7	3"	7
	Tech Sheet 1400	

We have listed all the popular sizes and pressure ratings, however other variations are available.

Individual test certificates to be requested at the time of orde

Fluid-Air Components Ltd

PRESSURE RELIEF VALVES

NABIC®

Combined Pressure & Temperature Relief Valves (Fig 500T)

Features:

- Dome top
- Relief pressure can be set between 1 and 12.5 bar for 3/4" to 1" and between 0.4 and 12.5 bar for 1.1/4" upwards
- Suitable for hot water and potable water
- A viton seat option is also available on request

Working Temperature:
-20°C to +95°C

Maximum Working Pressure:
12.5 bar

WRAS



BSPT Male Inlet x BSPP Female Outlet

0115	Thread	DN	Set Pressure Bar
500T-15-1	3/4"	15	1
500T-15-2	3/4"	15	2
500T-15-3	3/4"	15	3
500T-15-4	3/4"	15	4
500T-15-5	3/4"	15	5
500T-15-6	3/4"	15	6
500T-20-1	1"	20	1
500T-20-2	1"	20	2
500T-20-3	1"	20	3
500T-20-4	1"	20	4
500T-20-5	1"	20	5
500T-20-6	1"	20	6
500T-25-1	1.1/4"	25	1
500T-25-2	1.1/4"	25	2
500T-25-3	1.1/4"	25	3
500T-25-4	1.1/4"	25	4
500T-25-5	1.1/4"	25	5
500T-25-6	1.1/4"	25	6
500T-32-1	1.1/2"	32	1
500T-32-2	1.1/2"	32	2
500T-32-3	1.1/2"	32	3
500T-32-4	1.1/2"	32	4
500T-32-5	1.1/2"	32	5
500T-32-6	1.1/2"	32	6
400T-40-1	2"	40	1
400T-40-2	2"	40	2
400T-40-3	2"	40	3
400T-40-4	2"	40	4
400T-40-5	2"	40	5
400T-40-6	2"	40	6
500T-50-1	2.1/2"	50	1
500T-50-2	2.1/2"	50	2
500T-50-3	2.1/2"	50	3
500T-50-4	2.1/2"	50	4
500T-50-5	2.1/2"	50	5
500T-50-6	2.1/2"	50	6

Tech Sheet 20441

Safety Relief Valves (Fig 542F)

Features:

- Easing lever
- Relief pressure can be set between 0.3 and 10.5 bar
- Suitable for hot water, saturated steam, compressed air and inert gasses, CO2 (to +20°C), ethylene glycol and potable water
- A viton seat option is also available on request

Working Temperature:
-20°C to +195°C

Maximum Working Pressure:
10.5 bar

WRAS



Flanged PN16 Inlet x BSPP Female Outlet

0115	Flange Size	Thread	Set Pressure Bar
542F-32-1	1.1/4"	1.1/4"	1
542F-32-2	1.1/4"	1.1/4"	2
542F-32-3	1.1/4"	1.1/4"	3
542F-32-4	1.1/4"	1.1/4"	4
542F-32-6	1.1/4"	1.1/4"	6
542F-40-1	1.1/2"	1.1/2"	1
542F-40-2	1.1/2"	1.1/2"	2
542F-40-3	1.1/2"	1.1/2"	3
542F-40-4	1.1/2"	1.1/2"	4
542F-40-6	1.1/2"	1.1/2"	6
542F-50-1	2"	2"	1
542F-50-2	2"	2"	2
542F-50-3	2"	2"	3
542F-50-4	2"	2"	4
542F-50-6	2"	2"	6
542F-63-1	2.1/2"	2.1/2"	1
542F-63-2	2.1/2"	2.1/2"	2
542F-63-3	2.1/2"	2.1/2"	3
542F-63-4	2.1/2"	2.1/2"	4
542F-63-6	2.1/2"	2.1/2"	6
542F-80-1	3"	3"	1
542F-80-2	3"	3"	2
542F-80-3	3"	3"	3
542F-80-4	3"	3"	4
542F-80-6	3"	3"	6

Tech Sheet 20442

Please Note: due to pressure setting and certification of this product, normal delivery will be up to 3 working days (manufacturers stock permitting), although a quicker service may be available if required.
Please contact our sales team.

We have listed all the popular sizes and pressure ratings, however other variations are available.

Individual test certificates to be requested at the time of orde

Fluid-Air Components Ltd

HAITIMA ACTUATION

Brass Nickel Plated Ball Valves Fitted with a Pneumatic Actuator

Features:
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +170°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
40 bar



Single Acting, BSPP

0929	Thread
HSA 6400-12	1/2"
HSA 6400-34	3/4"
HSA 6400-1	1"
HSA 6400-114	1.1/4"
HSA 6400-112	1.1/2"
HSA 6400-2	2"
Tech Sheet 6184	

Double Acting, BSPP

0929	Thread
HDA 6400-12	1/2"
HDA 6400-34	3/4"
HDA 6400-1	1"
HDA 6400-114	1.1/4"
HDA 6400-112	1.1/2"
HDA 6400-2	2"
Tech Sheet 6184	

HAITIMA ACTUATION

Brass Nickel Plated Ball Valves Fitted with a Pneumatic Actuator

Features:
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +130°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
40 bar



Single Acting, BSPP

0929	Thread
HSA 1021-14	1/4"
HSA 1021-38	3/8"
Tech Sheet 6185	

Double Acting, BSPP

0929	Thread
HDA 1021-14	1/4"
HDA 1021-38	3/8"
Tech Sheet 6185	



You might also need...
NAMUR Solenoid Valves and Mechanical Switch Boxes
...see pages **1020-1022**

HAITIMA ACTUATION

HAITIMA ENOLGAS

Brass Nickel Plated 3 Way Ball Valves Fitted with a Pneumatic Actuator

Features:
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +130°C (valve)
-20°C to +90°C (actuator)



Single Acting, L Port, BSPP

0929	Thread	Max Pressure bar
HSA 1071-14	1/4"	40
HSA 1071-38	3/8"	40
HSA 1071-12	1/2"	40
HSA 1071-34	3/4"	40
HSA 1071-1	1"	40
HSA 1071-114	1.1/4"	40
HSA 1071-112	1.1/2"	25
HSA 1071-2	2"	25
Tech Sheet 6186		

Double Acting, L Port, BSPP

0929	Thread	Max Pressure bar
HDA 1071-14	1/4"	40
HDA 1071-38	3/8"	40
HDA 1071-12	1/2"	40
HDA 1071-34	3/4"	40
HDA 1071-1	1"	40
HDA 1071-114	1.1/4"	40
HDA 1071-112	1.1/2"	25
HDA 1071-2	2"	25
Tech Sheet 6186		

Single Acting, T Port, BSPP

0929	Thread	Max Pressure bar
HSA 1070-14	1/4"	40
HSA 1070-38	3/8"	40
HSA 1070-12	1/2"	40
HSA 1070-34	3/4"	40
HSA 1070-1	1"	40
HSA 1070-114	1.1/4"	40
HSA 1070-112	1.1/2"	25
HSA 1070-2	2"	25
Tech Sheet 6186		

Double Acting, T Port, BSPP

0929	Thread	Max Pressure bar
HDA 1070-14	1/4"	40
HDA 1070-38	3/8"	40
HDA 1070-12	1/2"	40
HDA 1070-34	3/4"	40
HDA 1070-1	1"	40
HDA 1070-114	1.1/4"	40
HDA 1070-112	1.1/2"	25
HDA 1070-2	2"	25
Tech Sheet 6186		

HAITIMA ACTUATION

HAITIMA

Stainless Steel Full Bore Ball Valves Fitted with a Pneumatic Actuator

Features:
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
63 bar



Single Acting

0929	Thread
HSA 2006SD-14	1/4"
HSA 2006SD-38	3/8"
HSA 2006SD-12	1/2"
HSA 2006SD-34	3/4"
HSA 2006SD-1	1"
HSA 2006SD-114	1.1/4"
HSA 2006SD-112	1.1/2"
HSA 2006SD-2	2"
Tech Sheet 6187	

Double Acting

0929	Thread
HDA 2006SD-14	1/4"
HDA 2006SD-38	3/8"
HDA 2006SD-12	1/2"
HDA 2006SD-34	3/4"
HDA 2006SD-1	1"
HDA 2006SD-114	1.1/4"
HDA 2006SD-112	1.1/2"
HDA 2006SD-2	2"
Tech Sheet 6187	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HAITIMA ACTUATION

HAITIMA

Stainless Steel Full Bore Ball Valves Fitted with a Pneumatic Actuator

Features:
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
63 bar



Single Acting, BSPP

0929	Thread
HSA 2013ND-14	1/4"
HSA 2013ND-38	3/8"
HSA 2013ND-12	1/2"
HSA 2013ND-34	3/4"
HSA 2013ND-1	1"
HSA 2013ND-114	1.1/4"
HSA 2013ND-112	1.1/2"
HSA 2013ND-2	2"
HSA 2013ND-212	2.1/2"
HSA 2013ND-3	3"
HSA 2013ND-4	4"
Tech Sheet 6188	

Single Acting, Butt Weld

0929	Size
HSA 2012ND-12	1/2"
HSA 2012ND-34	3/4"
HSA 2012ND-1	1"
HSA 2012ND-114	1.1/4"
HSA 2012ND-112	1.1/2"
HSA 2012ND-2	2"
HSA 2012ND-212	2.1/2"
HSA 2012ND-3	3"
HSA 2012ND-4	4"
Tech Sheet 6188	

Single Acting, Socket Weld

0929	Size
HSA 2011ND-38	3/8"
HSA 2011ND-12	1/2"
HSA 2011ND-34	3/4"
HSA 2011ND-1	1"
HSA 2011ND-114	1.1/4"
HSA 2011ND-112	1.1/2"
HSA 2011ND-2	2"
HSA 2011ND-212	2.1/2"
HSA 2011ND-3	3"
HSA 2011ND-4	4"
Tech Sheet 6188	

Double Acting, BSPP

0929	Thread
HDA 2013ND-14	1/4"
HDA 2013ND-38	3/8"
HDA 2013ND-12	1/2"
HDA 2013ND-34	3/4"
HDA 2013ND-1	1"
HDA 2013ND-114	1.1/4"
HDA 2013ND-112	1.1/2"
HDA 2013ND-2	2"
HDA 2013ND-212	2.1/2"
HDA 2013ND-3	3"
HDA 2013ND-4	4"
Tech Sheet 6188	

Double Acting, Butt Weld

0929	Size
HDA 2012ND-12	1/2"
HDA 2012ND-34	3/4"
HDA 2012ND-1	1"
HDA 2012ND-114	1.1/4"
HDA 2012ND-112	1.1/2"
HDA 2012ND-2	2"
HDA 2012ND-212	2.1/2"
HDA 2012ND-3	3"
HDA 2012ND-4	4"
Tech Sheet 6188	

Double Acting, Socket Weld

0929	Size
HDA 2011ND-12	1/2"
HDA 2011ND-34	3/4"
HDA 2011ND-1	1"
HDA 2011ND-114	1.1/4"
HDA 2011ND-112	1.1/2"
HDA 2011ND-2	2"
HDA 2011ND-212	2.1/2"
HDA 2011ND-3	3"
HDA 2011ND-4	4"
Tech Sheet 6188	

HAITIMA ACTUATION

HAITIMA

Features:

- Fire Safe approved and anti-static device (valve only)
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +220°C (valve)
-20°C to +90°C (actuator)

For saturated steam up to 12 bar - use an actuated valve with a TSM

Fire Safe Stainless Steel Ball Valves Fitted with a Pneumatic Actuator

Single Acting, BSPP

0929	Thread	Max Pressure bar
HSA 2013KMD-12	1/2"	138
HSA 2013KMD-34	3/4"	138
HSA 2013KMD-1	1"	138
HSA 2013KMD-114	1.1/4"	103
HSA 2013KMD-112	1.1/2"	103
HSA 2013KMD-2	2"	103
HSA 2013KMD-212	2.1/2"	63
HSA 2013KMD-3	3"	63
Tech Sheet 6189		

Double Acting, BSPP

0929	Thread	Max Pressure bar
HDA 2013KMD-12	1/2"	138
HDA 2013KMD-34	3/4"	138
HDA 2013KMD-1	1"	138
HDA 2013KMD-114	1.1/4"	103
HDA 2013KMD-112	1.1/2"	103
HDA 2013KMD-2	2"	103
HDA 2013KMD-212	2.1/2"	63
HDA 2013KMD-3	3"	63
Tech Sheet 6189		

Single Acting, Butt Weld

0929	Size	Max Pressure bar
HSA 2012KMD-12	1/2"	138
HSA 2012KMD-34	3/4"	138
HSA 2012KMD-1	1"	138
HSA 2012KMD-112	1.1/2"	103
HSA 2012KMD-2	2"	103
Tech Sheet 6189		

Double Acting, Butt Weld

0929	Size	Max Pressure bar
HDA 2012KMD-12	1/2"	138
HDA 2012KMD-34	3/4"	138
HDA 2012KMD-1	1"	138
HDA 2012KMD-112	1.1/2"	103
HDA 2012KMD-2	2"	103
Tech Sheet 6189		

Single Acting, Socket Weld

0929	Thread	Max Pressure bar
HSA 2011KMD-12	1/2"	138
HSA 2011KMD-34	3/4"	138
HSA 2011KMD-1	1"	138
HSA 2011KMD-114	1.1/4"	103
HSA 2011KMD-112	1.1/2"	103
HSA 2011KMD-2	2"	103
Tech Sheet 6189		

Double Acting, Socket Weld

0929	Thread	Max Pressure bar
HDA 2011KMD-12	1/2"	138
HDA 2011KMD-34	3/4"	138
HDA 2011KMD-1	1"	138
HDA 2011KMD-114	1.1/4"	103
HDA 2011KMD-112	1.1/2"	103
HDA 2011KMD-2	2"	103
Tech Sheet 6189		





Fire Safe Carbon Steel Ball Valves Fitted with a Pneumatic Actuator

Single Acting, BSPP

0929	Thread	Max Pressure bar
HSA 2013KMD-12C	1/2"	138
HSA 2013KMD-34C	3/4"	138
HSA 2013KMD-1C	1"	138
HSA 2013KMD-114C	1.1/4"	103
HSA 2013KMD-112C	1.1/2"	103
HSA 2013KMD-2C	2"	103
HSA 2013KMD-212C	2.1/2"	63
HSA 2013KMD-3C	3"	63
Tech Sheet 6189		

Double Acting, BSPP

0929	Thread	Max Pressure bar
HDA 2013KMD-12C	1/2"	138
HDA 2013KMD-34C	3/4"	138
HDA 2013KMD-1C	1"	138
HDA 2013KMD-114C	1.1/4"	103
HDA 2013KMD-112C	1.1/2"	103
HDA 2013KMD-2C	2"	103
HDA 2013KMD-212C	2.1/2"	63
HDA 2013KMD-3C	3"	63
Tech Sheet 6189		



Fluid-Air Components Ltd

HAITIMA ACTUATION

HAITIMA GENEBRE

Stainless Steel 3 Way Ball Valves Fitted with a Pneumatic Actuator

Features:
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-25°C to +180°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
63 bar



Single Acting, L Port, BSPP

0929	Thread
HSA 2040-14	1/4"
HSA 2040-38	3/8"
HSA 2040-12	1/2"
HSA 2040-34	3/4"
HSA 2040-1	1"
HSA 2040-114	1.1/4"
HSA 2040-112	1.1/2"
HSA 2040-2	2"
HSA 2040-212	2.1/2"
Tech Sheet 6190	

Double Acting, L Port, BSPP

0929	Thread
HDA 2040-14	1/4"
HDA 2040-38	3/8"
HDA 2040-12	1/2"
HDA 2040-34	3/4"
HDA 2040-1	1"
HDA 2040-114	1.1/4"
HDA 2040-112	1.1/2"
HDA 2040-2	2"
HDA 2040-212	2.1/2"
Tech Sheet 6190	

Single Acting, T Port, BSPP

0929	Thread
HSA 2041-14	1/4"
HSA 2041-38	3/8"
HSA 2041-12	1/2"
HSA 2041-34	3/4"
HSA 2041-1	1"
HSA 2041-114	1.1/4"
HSA 2041-112	1.1/2"
HSA 2041-2	2"
HSA 2041-212	2.1/2"
Tech Sheet 6190	

Double Acting, T Port, BSPP

0929	Thread
HDA 2041-14	1/4"
HDA 2041-38	3/8"
HDA 2041-12	1/2"
HDA 2041-34	3/4"
HDA 2041-1	1"
HDA 2041-114	1.1/4"
HDA 2041-112	1.1/2"
HDA 2041-2	2"
HDA 2041-212	2.1/2"
Tech Sheet 6190	

Looking for bespoke Flow Path Configuration?
Contact our technical team.

FT PRO

Customers who bought from this page also purchased
Flat Brass & Sintered Bronze Silencers
see page **631**



Fluid-Air Components Ltd

HAITIMA ACTUATION

HAITIMA

Stainless Steel Hygienic Ball Valves Fitted with a Pneumatic Actuator

Features:
- Cavity filled seat
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
10 bar
Suitable for up to 10 bar saturated steam with a TSM





Single Acting, Butt Weld

0929	Size
HSA 2012CD-12	1/2"
HSA 2012CD-34	3/4"
HSA 2012CD-1	1"
HSA 2012CD-112	1.1/2"
HSA 2012CD-2	2"
HSA 2012CD-212	2.1/2"
HSA 2012CD-3	3"
HSA 2012CD-4	4"
Tech Sheet 6191	

Double Acting, Butt Weld

0929	Size
HDA 2012CD-12	1/2"
HDA 2012CD-34	3/4"
HDA 2012CD-1	1"
HDA 2012CD-112	1.1/2"
HDA 2012CD-2	2"
HDA 2012CD-212	2.1/2"
HDA 2012CD-3	3"
HDA 2012CD-4	4"
Tech Sheet 6191	

Single Acting, Clamp

0929	Size
HSA 2013CD-12	1/2"
HSA 2013CD-34	3/4"
HSA 2013CD-1	1"
HSA 2013CD-112	1.1/2"
HSA 2013CD-2	2"
HSA 2013CD-212	2.1/2"
HSA 2013CD-3	3"
HSA 2013CD-4	4"
Tech Sheet 6191	

Double Acting, Clamp

0929	Size
HDA 2013CD-12	1/2"
HDA 2013CD-34	3/4"
HDA 2013CD-1	1"
HDA 2013CD-112	1.1/2"
HDA 2013CD-2	2"
HDA 2013CD-212	2.1/2"
HDA 2013CD-3	3"
HDA 2013CD-4	4"
Tech Sheet 6191	

Stainless Steel Hygienic 3 Way Ball Valves Fitted with a Pneumatic Actuator

Features:
- Cavity filled seat
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
10 bar
Suitable for up to 10 bar saturated steam with a TSM



Single Acting, L Port, Butt Weld

0929	Size
HSA 2057CBL-12	1/2"
HSA 2057CBL-1	1"
HSA 2057CBL-112	1.1/2"
HSA 2057CBL-2	2"
HSA 2057CBL-212	2.1/2"
HSA 2057CBL-3	3"
HSA 2057CBL-4	4"
Tech Sheet 6192	

Double Acting, L Port, Butt Weld

0929	Size
HDA 2057CBL-12	1/2"
HDA 2057CBL-1	1"
HDA 2057CBL-112	1.1/2"
HDA 2057CBL-2	2"
HDA 2057CBL-212	2.1/2"
HDA 2057CBL-3	3"
HDA 2057CBL-4	4"
Tech Sheet 6192	

Single Acting, T Port, Butt Weld

0929	Size
HSA 2057CBT-12	1/2"
HSA 2057CBT-1	1"
HSA 2057CBT-112	1.1/2"
HSA 2057CBT-2	2"
HSA 2057CBT-212	2.1/2"
HSA 2057CBT-3	3"
HSA 2057CBT-4	4"
Tech Sheet 6192	

Double Acting, T Port, Butt Weld

0929	Size
HDA 2057CBT-12	1/2"
HDA 2057CBT-1	1"
HDA 2057CBT-112	1.1/2"
HDA 2057CBT-2	2"
HDA 2057CBT-212	2.1/2"
HDA 2057CBT-3	3"
HDA 2057CBT-4	4"
Tech Sheet 6192	

Fluid-Air Components Ltd

HAITIMA ACTUATION

HAITIMA

Fire Safe Stainless Steel Ball Valves Fitted with a Pneumatic Actuator

Features:
- Fire Safe approved and anti-static device (valve only)
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Suitable for up to 12 bar saturated steam with a TSM



Single Acting, Flanged PN16

0929	Size	Max Pressure bar
HSA 2019D 04	1/2"	40
HSA 2019D 05	3/4"	40
HSA 2019D 06	1"	40
HSA 2019D 07	1.1/4"	40
HSA 2019D 08	1.1/2"	40
HSA 2019D 09	2"	40
HSA 2019D 10	2.1/2"	16
HSA 2019D 11	3"	16
HSA 2019D 12	4"	16
HSA 2019D 13	5"	16
HSA 2019D 14	6"	16
HSA 2019D 16	8"	16
Tech Sheet 6193		

Double Acting, Flanged PN16

0929	Size	Max Pressure bar
HDA 2019D 04	1/2"	40
HDA 2019D 05	3/4"	40
HDA 2019D 06	1"	40
HDA 2019D 07	1.1/4"	40
HDA 2019D 08	1.1/2"	40
HDA 2019D 09	2"	40
HDA 2019D 10	2.1/2"	16
HDA 2019D 11	3"	16
HDA 2019D 12	4"	16
HDA 2019D 13	5"	16
HDA 2019D 14	6"	16
HDA 2019D 16	8"	16
Tech Sheet 6193		

Single Acting, Flanged PN40

0929	Size	Max Pressure bar
HSA 2019D4 10	2.1/2"	40
HSA 2019D4 11	3"	40
HSA 2019D4 12	4"	40
Tech Sheet 6193		

Double Acting, Flanged PN40

0929	Size	Max Pressure bar
HDA 2019D4 10	2.1/2"	40
HDA 2019D4 11	3"	40
HDA 2019D4 12	4"	40
Tech Sheet 6193		

FT PRO

You might also need...
Stainless Steel Flanges
...see page **1195**



FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HAITIMA ACTUATION

Stainless Steel Flanged Ball Valves Fitted with a Pneumatic Actuator

Features:
- Fire Safe approved and anti-static device (valve only)
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +230°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
19.6 bar
Suitable for up to 12 bar saturated steam with a TSM



Single Acting, ANSI150

0929	Size
HSA 2020D 04	1/2"
HSA 2020D 05	3/4"
HSA 2020D 06	1"
HSA 2020D 07	1.1/4"
HSA 2020D 08	1.1/2"
HSA 2020D 09	2"
HSA 2020D 10	2.1/2"
HSA 2020D 11	3"
HSA 2020D 12	4"
HSA 2020D 14	6"
Tech Sheet 6194	

Double Acting, ANSI150

0929	Size
HDA 2020D 04	1/2"
HDA 2020D 05	3/4"
HDA 2020D 06	1"
HDA 2020D 07	1.1/4"
HDA 2020D 08	1.1/2"
HDA 2020D 09	2"
HDA 2020D 10	2.1/2"
HDA 2020D 11	3"
HDA 2020D 12	4"
HDA 2020D 14	6"
Tech Sheet 6194	

HAITIMA ACTUATION

Cast Iron Flanged Ball Valves Fitted with a Pneumatic Actuator

Features:
- 304 stainless steel ball and stem
- ATEX II 2GD c T5 certificatio
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-10°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
16 bar



Single Acting, PN16

0929	Size
HSA 150HIT 04	1/2"
HSA 150HIT 05	3/4"
HSA 150HIT 06	1"
HSA 150HIT 07	1.1/4"
HSA 150HIT 08	1.1/2"
HSA 150HIT 09	2"
HSA 150HIT 10	2.1/2"
HSA 150HIT 11	3"
HSA 150HIT 12	4"
HSA 150HIT 13	5"
HSA 150HIT 14	6"
HSA 150HIT 16	8"
Tech Sheet 6200	

Double Acting, PN16

0929	Size
HDA 150HIT 04	1/2"
HDA 150HIT 05	3/4"
HDA 150HIT 06	1"
HDA 150HIT 07	1.1/4"
HDA 150HIT 08	1.1/2"
HDA 150HIT 09	2"
HDA 150HIT 10	2.1/2"
HDA 150HIT 11	3"
HDA 150HIT 12	4"
HDA 150HIT 13	5"
HDA 150HIT 14	6"
HDA 150HIT 16	8"
Tech Sheet 6200	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HAITIMA ACTUATION

HAITIMA

Stainless Steel Flanged 3 Way Ball Valves Fitted with a Pneumatic Actuator

Features:
- Sized based on 10 bar pilot air and wet non-abrasive duty at +90°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +90°C (actuator)

Maximum Working Pressure:
16 bar: PN16
19.6 bar: ANSI150



Single Acting, L Port, PN16

0929	Size
HSA 2059DL16 04	1/2"
HSA 2059DL16 06	1"
HSA 2059DL16 08	1.1/2"
HSA 2059DL16 09	2"
HSA 2059DL16 10	2.1/2"
HSA 2059DL16 11	3"
HSA 2059DL16 12	4"
HSA 2059DL16 14	6"
Tech Sheet 6195	

Double Acting, L Port PN16

0929	Size
HDA 2059DL16 04	1/2"
HDA 2059DL16 06	1"
HDA 2059DL16 08	1.1/2"
HDA 2059DL16 09	2"
HDA 2059DL16 10	2.1/2"
HDA 2059DL16 11	3"
HDA 2059DL16 12	4"
HDA 2059DL16 14	6"
Tech Sheet 6195	

Single Acting, L Port, ANSI150

0929	Size
HSA 2059DL150 04	1/2"
HSA 2059DL150 06	1"
HSA 2059DL150 08	1.1/2"
HSA 2059DL150 09	2"
HSA 2059DL150 11	3"
HSA 2059DL150 12	4"
HSA 2059DL150 14	6"
Tech Sheet 6195	

Double Acting, L Port ANSI150

0929	Size
HDA 2059DL150 04	1/2"
HDA 2059DL150 06	1"
HDA 2059DL150 08	1.1/2"
HDA 2059DL150 09	2"
HDA 2059DL150 11	3"
HDA 2059DL150 12	4"
HDA 2059DL150 14	6"
Tech Sheet 6195	

Single Acting, T Port, PN16

0929	Size
HSA 2059DT16 04	1/2"
HSA 2059DT16 06	1"
HSA 2059DT16 08	1.1/2"
HSA 2059DT16 09	2"
HSA 2059DT16 10	2.1/2"
HSA 2059DT16 11	3"
HSA 2059DT16 12	4"
HSA 2059DT16 14	6"
Tech Sheet 6195	

Double Acting, T Port PN16

0929	Size
HDA 2059DT16 04	1/2"
HDA 2059DT16 06	1"
HDA 2059DT16 08	1.1/2"
HDA 2059DT16 09	2"
HDA 2059DT16 10	2.1/2"
HDA 2059DT16 11	3"
HDA 2059DT16 12	4"
HDA 2059DT16 14	6"
Tech Sheet 6195	

Single Acting, T Port, ANSI150

0929	Size
HSA 2059DT150 04	1/2"
HSA 2059DT150 06	1"
HSA 2059DT150 08	1.1/2"
HSA 2059DT150 09	2"
HSA 2059DT150 11	3"
HSA 2059DT150 12	4"
HSA 2059DT150 14	6"
Tech Sheet 6195	

Double Acting, T Port ANSI150

0929	Size
HDA 2059DT150 04	1/2"
HDA 2059DT150 06	1"
HDA 2059DT150 08	1.1/2"
HDA 2059DT150 09	2"
HDA 2059DT150 11	3"
HDA 2059DT150 12	4"
HDA 2059DT150 14	6"
Tech Sheet 6195	

HAITIMA ACTUATION

Wafer Pattern Butterfly alves Fitted with a Pneumatic Actuator

Features:
- To suit flanges PN6/10/16, ANSI150 and BS 10 able D/E
- Sized based on 10 bar pilot air and wet non-abrasive duty at +80°C

Working Temperature:
-20°C to +120°C (WA and WC)
0°C to +80°C (WB and WD)
-20°C to 90°C (actuator)
Excluding ice and steam

Maximum Working Pressure:
16 bar



Single Acting, Ductile Iron Body, EPDM Liner, Stainless Steel Disc (WRAS Approved Valve)

0929	Size
HSA 2014WA 08	1.1/2"
HSA 2014WA 09	2"
HSA 2014WA 10	2.1/2"
HSA 2014WA 11	3"
HSA 2014WA 12	4"
HSA 2014WA 13	5"
HSA 2014WA 14	6"
HSA 2014WA 16	8"
HSA 2014WA 18	10"
HSA 2014WA 20	12"
Tech Sheet 6204	

Double Acting, Ductile Iron Body, EPDM Liner, Stainless Steel Disc (WRAS Approved Valve)

0929	Size
HDA 2014WA 08	1.1/2"
HDA 2014WA 09	2"
HDA 2014WA 10	2.1/2"
HDA 2014WA 11	3"
HDA 2014WA 12	4"
HDA 2014WA 13	5"
HDA 2014WA 14	6"
HDA 2014WA 16	8"
HDA 2014WA 18	10"
HDA 2014WA 20	12"
Tech Sheet 6204	

Single Acting, Cast Iron Body, NBR Liner, Stainless Steel Disc

0929	Size
HSA 2014WB 08	1.1/2"
HSA 2014WB 09	2"
HSA 2014WB 10	2.1/2"
HSA 2014WB 11	3"
HSA 2014WB 12	4"
HSA 2014WB 13	5"
HSA 2014WB 14	6"
HSA 2014WB 16	8"
HSA 2014WB 18	10"
HSA 2014WB 20	12"
Tech Sheet 6204	

Double Acting, Cast Iron Body, NBR Liner, Stainless Steel Disc

0929	Size
HDA 2014WB 08	1.1/2"
HDA 2014WB 09	2"
HDA 2014WB 10	2.1/2"
HDA 2014WB 11	3"
HDA 2014WB 12	4"
HDA 2014WB 13	5"
HDA 2014WB 14	6"
HDA 2014WB 16	8"
HDA 2014WB 18	10"
HDA 2014WB 20	12"
Tech Sheet 6204	

Single Acting, Cast Iron Body, EPDM Liner, Ductile Iron Nickel Plated Disc

0929	Size
HSA 2014WC 09	2"
HSA 2014WC 10	2.1/2"
HSA 2014WC 11	3"
HSA 2014WC 12	4"
HSA 2014WC 13	5"
HSA 2014WC 14	6"
HSA 2014WC 16	8"
HSA 2014WC 18	10"
HSA 2014WC 20	12"
Tech Sheet 6204	

Double Acting, Cast Iron Body, EPDM Liner, Ductile Iron Nickel Plated Disc

0929	Size
HDA 2014WC 09	2"
HDA 2014WC 10	2.1/2"
HDA 2014WC 11	3"
HDA 2014WC 12	4"
HDA 2014WC 13	5"
HDA 2014WC 14	6"
HDA 2014WC 16	8"
HDA 2014WC 18	10"
HDA 2014WC 20	12"
Tech Sheet 6204	

Single Acting, Cast Iron Body, NBR Liner, Ductile Iron Nickel Plated Disc

0929	Size
HSA 2014WD 09	2"
HSA 2014WD 10	2.1/2"
HSA 2014WD 11	3"
HSA 2014WD 12	4"
HSA 2014WD 13	5"
HSA 2014WD 14	6"
HSA 2014WD 16	8"
HSA 2014WD 18	10"
HSA 2014WD 20	12"
Tech Sheet 6204	

Double Acting, Cast Iron Body, NBR Liner, Ductile Iron Nickel Plated Disc

0929	Size
HDA 2014WD 09	2"
HDA 2014WD 10	2.1/2"
HDA 2014WD 11	3"
HDA 2014WD 12	4"
HDA 2014WD 13	5"
HDA 2014WD 14	6"
HDA 2014WD 16	8"
HDA 2014WD 18	10"
HDA 2014WD 20	12"
Tech Sheet 6204	

You might also need...
NAMUR 5/2 Solenoid Valve
...see page **1020**



Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

HAITIMA ACTUATION

Wafer Pattern Butterfly alves Fitted with a Pneumatic Actuator

Features:
- To suit flanges PN6/10/16, ANSI150 and BS 10 able D/E
- Sized based on 10 bar pilot air and wet non-abrasive duty at +80°C

Working Temperature:
-40°C to +200°C (valve)
-20°C to +90°C (actuator)



Single Acting, Ductile Iron Body, Fully Lined PTFE

0929	Size	Max Pressure bar
HSA 2014WP 09	2"	16
HSA 2014WP 10	2.1/2"	16
HSA 2014WP 11	3"	16
HSA 2014WP 12	4"	16
HSA 2014WP 13	5"	16
HSA 2014WP 14	6"	16
HSA 2014WP 16	8"	16
HSA 2014WP 18	10"	16
HSA 2014WP 20	12"	10
Tech Sheet 6205		

Double Acting, Ductile Iron Body, Fully Lined PTFE

0929	Size	Max Pressure bar
HDA 2014WP 09	2"	16
HDA 2014WP 10	2.1/2"	16
HDA 2014WP 11	3"	16
HDA 2014WP 12	4"	16
HDA 2014WP 13	5"	16
HDA 2014WP 14	6"	16
HDA 2014WP 16	8"	16
HDA 2014WP 18	10"	16
HDA 2014WP 20	12"	10
Tech Sheet 6205		

Lugged & Tapped Butterfly alves Fitted with a Pneumatic Actuator

Features:
- To suit PN16 flanges
- Sized based on 10 bar pilot air and wet non-abrasive duty at +80°C

Working Temperature:
-20°C to +120°C (2014LA)
0°C to +80°C (2014LB)
-20°C to +90°C (actuator)
Excluding ice and steam

Maximum Working Pressure:
16 bar



Single Acting, Ductile Iron Body, EPDM Liner, Stainless Steel Disc (WRAS Approved Valve)

0929	Size
HSA 2014LA 08	1.1/2"
HSA 2014LA 09	2"
HSA 2014LA 10	2.1/2"
HSA 2014LA 11	3"
HSA 2014LA 12	4"
HSA 2014LA 13	5"
HSA 2014LA 14	6"
HSA 2014LA 16	8"
HSA 2014LA 18	10"
HSA 2014LA 20	12"
Tech Sheet 6206	

Double Acting, Ductile Iron Body, EPDM Liner, Stainless Steel Disc (WRAS Approved Valve)

0929	Size
HDA 2014LA 08	1.1/2"
HDA 2014LA 09	2"
HDA 2014LA 10	2.1/2"
HDA 2014LA 11	3"
HDA 2014LA 12	4"
HDA 2014LA 13	5"
HDA 2014LA 14	6"
HDA 2014LA 16	8"
HDA 2014LA 18	10"
HDA 2014LA 20	12"
Tech Sheet 6206	

Single Acting, Ductile Iron Body, NBR Liner, Stainless Steel Disc

0929	Size
HDA 2014LB 08	1.1/2"
HDA 2014LB 09	2"
HDA 2014LB 10	2.1/2"
HDA 2014LB 11	3"
HDA 2014LB 12	4"
HDA 2014LB 13	5"
HDA 2014LB 14	6"
HDA 2014LB 16	8"
HDA 2014LB 18	10"
HDA 2014LB 20	12"
Tech Sheet 6206	

Double Acting, Ductile Iron Body, NBR Liner, Stainless Steel Disc

0929	Size
HSA 2014LB 08	1.1/2"
HSA 2014LB 09	2"
HSA 2014LB 10	2.1/2"
HSA 2014LB 11	3"
HSA 2014LB 12	4"
HSA 2014LB 13	5"
HSA 2014LB 14	6"
HSA 2014LB 16	8"
HSA 2014LB 18	10"
HSA 2014LB 20	12"
Tech Sheet 6206	

ACTUATED KNIFE GATE VALVES

Features:
- ATEX II 3GD T3 certification
- Provides high flow rates with low pressure drop
- Other sizes or flange dimensions are available on request

Type A Unidirectional Knife Gate Valves Fitted with a Pneumatic Cylinder

- Suitable for liquids that contain a maximum of 5% suspended solids

Pressure Equipment Directive:
DIR 97/23/EC (PED) Art. 4.3, Cat. 1

Working Temperature:
0°C to +90°C



Double Acting, Cast Iron Body, 304SS Blade, EPDM Seat

0944	Size	DN	Flange	Max Pressure bar
A1N2H2 09	2"	50	PN10/16	10
A1N2H2 10	2.1/2"	65	PN10/16	10
A1N2H2 11	3"	80	PN10/16	10
A1N2H2 12	4"	100	PN10/16	10
A1N2H2 13	5"	125	PN10/16	10
A1N2H2 14	6"	150	PN10/16	10
A1N2H2 16	8"	200	PN10	10
A1N2H2 18	10"	250	PN10	10
A1N2H2 20	12"	300	PN10	6
A3N2H2 16	8"	200	PN16	10
A3N2H2 18	10"	250	PN16	10
A3N2H2 20	12"	300	PN16	6
Tech Sheet 10246				

Type AB Bidirectional Knife Gate Valves Fitted with a Pneumatic Cylinder

- Suitable for liquids that contain a maximum of 4% suspended solids

Pressure Equipment Directive:
DIR 97/23/EC (PED) Art. 4.3, Cat. 1

Working Temperature:
0°C to +90°C



Double Acting, Cast Iron Body, 304SS Blade, EPDM Seat

0944	Size	DN	Flange	Max Pressure bar
AB1N2H2 09	2"	50	PN10/16	10
AB1N2H2 10	2.1/2"	65	PN10/16	10
AB1N2H2 11	3"	80	PN10/16	10
AB1N2H2 12	4"	100	PN10/16	10
AB1N2H2 13	5"	125	PN10/16	10
AB1N2H2 14	6"	150	PN10/16	10
AB1N2H2 16	8"	200	PN10	8
AB1N2H2 18	10"	250	PN10	6
AB1N2H2 20	12"	300	PN10	6
Tech Sheet 6242				

Limit Switches are also available on request
Please contact our sales team.

Fluid-Air Components Ltd

J+J ACTUATION

Brass Nickel Plated Ball Valves Fitted with a J2-10 Electric Actuator

Features:

- L10: 24V DC/V AC 50/60Hz
  H10: 110-240V DC/V AC 50/60Hz
- Failsafe and/or modulating configurations cannot be used with the J2-10 electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +170°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
40 bar



BSPP, Low Voltage

0956	Thread
L10 6400-12	1/2"
L10 6400-34	3/4"
L10 6400-1	1"
L10 6400-114	1.1/4"
Tech Sheet 6259	

BSPP, High Voltage

0956	Thread
H10 6400-12	1/2"
H10 6400-34	3/4"
H10 6400-1	1"
H10 6400-114	1.1/4"
Tech Sheet 6259	

J+J ACTUATION


Brass Nickel Plated Ball Valves Fitted with a J2-10 Electric Actuator

Features:

- L10: 24V DC/V AC 50/60Hz
  H10: 110-240V DC/V AC 50/60Hz
- Failsafe and/or modulating configurations cannot be used with the J2-10 electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +130°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
40 bar



BSPP, Low Voltage

0956	Thread
L10 1021-14	1/4"
L10 1021-38	3/8"
Tech Sheet 6260	

BSPP, High Voltage

0956	Thread
H10 1021-14	1/4"
H10 1021-38	3/8"
Tech Sheet 6260	

Do you require the WRAS certificate?
Contact our sales team and they will send this to you by email.

J+J ACTUATION

Brass Nickel Plated 3 Way Ball Valves Fitted with a J2-10 Electric Actuator

Features:

- L10: 24V DC/V AC 50/60Hz
  H10: 110-240V DC/V AC 50/60Hz
- Failsafe and/or modulating configurations cannot be used with the J2-10 electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +130°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
40 bar



BSPP, Low Voltage, L Port

0956	Thread
L10 1071-14	1/4"
L10 1071-38	3/8"
L10 1071-12	1/2"
L10 1071-34	3/4"
Tech Sheet 6261	

BSPP, Low Voltage, T Port

0956	Thread
L10 1070-14	1/2"
L10 1070-38	3/4"
L10 1070-12	1"
L10 1070-34	1.1/4"
Tech Sheet 6259	

BSPP, High Voltage, L Port

0956	Thread
H10 1071-14	1/4"
H10 1071-38	3/8"
H10 1071-12	1/2"
H10 1071-34	3/4"
Tech Sheet 6261	

BSPP, High Voltage, T Port

0956	Thread
H10 1070-14	1/2"
H10 1070-38	3/4"
H10 1070-12	1"
H10 1070-34	1.1/4"
Tech Sheet 6259	

Brass Nickel Plated Ball Valves Fitted with a J4CS Electric Actuator

Features:

- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C


Working Temperature:
-20°C to +130°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
40 bar



BSPP, Multi Voltage

0956	Thread
S20 1021-14	1/4"
S20 1021-38	3/8"
Tech Sheet 6491	



Do you require...
failsafe and/or modulating configurations?
...see page **1019**

Fluid-Air Components Ltd

J+J ACTUATION

Brass Nickel Plated Ball Valves Fitted with a J4CS Electric Actuator

Features:
- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be use with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +170°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
40 bar



BSPP, Multi Voltage

0956	Thread
S20 6400-12	1/2"
S20 6400-34	3/4"
S20 6400-1	1"
S20 6400-114	1.1/4"
S20 6400-112	1.1/2"
S20 6400-2	2"
Tech Sheet 6497	

Features:
- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +130°C (valve)
-20°C to +70°C (actuator)



BSPP, L Port, Multi Voltage

0956	Thread	Max Pressure bar
S20 1071-14	1/4"	40
S20 1071-38	3/8"	40
S20 1071-12	1/2"	40
S20 1071-34	3/4"	40
S20 1071-1	1"	40
S20 1071-114	1.1/4"	40
S35 1071-112	1.1/2"	25
S55 1071-2	2"	25
Tech Sheet 6495		

BSPP, T Port, Multi Voltage

0956	Thread	Max Pressure bar
S20 1070-14	1/4"	40
S20 1070-38	3/8"	40
S20 1070-12	1/2"	40
S20 1070-34	3/4"	40
S20 1070-1	1"	40
S20 1070-114	1.1/4"	40
S35 1070-112	1.1/2"	25
S55 1070-2	2"	25
Tech Sheet 6495		

Do you require the WRAS certificate?
Contact our sales team and they will send this to you by email.

J+J ACTUATION

Stainless Steel Ball Valves Fitted with a J4CS Electric Actuator

Features:

- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
63 bar



BSPP, Multi Voltage

0956	Thread
S20 2006SD-14	1/4"
S20 2006SD-38	3/8"
S20 2006SD-12	1/2"
S20 2006SD-34	3/4"
S20 2006SD-1	1"
S20 2006SD-114	1.1/4"
S20 2006SD-112	1.1/2"
S55 2006SD-2	2"
Tech Sheet 6496	

J+J ACTUATION

Stainless Steel Full Bore Ball Valves Fitted with a J4CS Electric Actuator

Features:

- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
63 bar



BSPP, Multi Voltage

0956	Thread
S20 2013ND-14	1/4"
S20 2013ND-38	3/8"
S20 2013ND-12	1/2"
S20 2013ND-34	3/4"
S20 2013ND-1	1"
S20 2013ND-114	1.1/4"
S35 2013ND-112	1.1/2"
S55 2013ND-2	2"
S55 2013ND-212	2.1/2"
S85 2013ND-3	3"
S140 2013ND-4	4"
Tech Sheet 6262	

Butt Weld, Multi Voltage

0956	Size
S20 2012ND-12	1/2"
S20 2012ND-34	3/4"
S20 2012ND-1	1"
S20 2012ND-114	1.1/4"
S35 2012ND-112	1.1/2"
S55 2012ND-2	2"
S55 2012ND-212	2.1/2"
S85 2012ND-3	3"
S140 2012ND-4	4"
Tech Sheet 6262	

Socket Weld, Multi Voltage

0956	Thread
S20 2011ND-12	1/2"
S20 2011ND-34	3/4"
S20 2011ND-1	1"
S20 2011ND-114	1.1/4"
S35 2011ND-112	1.1/2"
S55 2011ND-2	2"
S55 2011ND-212	2.1/2"
S85 2011ND-3	3"
S140 2011ND-4	4"
Tech Sheet 6262	

Fluid-Air Components Ltd

J+J ACTUATION

Fire Safe Ball Valves Fitted with a J4CS Electric Actuator

Features:
- Fire Safe approved and anti-static device (valve only)
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +220°C (valve)
-20°C to +70°C (actuator)

Suitable for up to 12 bar saturated steam with a TSM

FIRE SAFE APPROVED



Stainless Steel, BSPP, Multi Voltage

0956	Thread	Max Pressure bar
S20 2013KMD-12	1/2"	138
S20 2013KMD-34	3/4"	138
S20 2013KMD-1	1"	138
S20 2013KMD-114	1.1/4"	103
S35 2013KMD-112	1.1/2"	103
S55 2013KMD-2	2"	103
S85 2013KMD-212	2.1/2"	63
S140 2013KMD-3	3"	63
Tech Sheet 6490		

Stainless Steel, Butt Weld, Multi Voltage

0956	Thread	Max Pressure bar
S20 2012KMD-12	1/2"	138
S20 2012KMD-34	3/4"	138
S20 2012KMD-1	1"	138
S35 2012KMD-112	1.1/2"	103
S55 2012KMD-2	2"	103
Tech Sheet 6490		

Stainless Steel, Socket Weld, Multi Voltage

0956	Thread	Max Pressure bar
S20 2011KMD-12	1/2"	138
S20 2011KMD-34	3/4"	138
S20 2011KMD-1	1"	138
S20 2011KMD-114	1.1/4"	103
S35 2011KMD-112	1.1/2"	103
S55 2011KMD-2	2"	103
Tech Sheet 6490		

Carbon Steel, BSPP, Multi Voltage

0956	Thread	Max Pressure bar
S20 2013KMD-12C	1/2"	138
S20 2013KMD-34C	3/4"	138
S20 2013KMD-1C	1"	138
S20 2013KMD-114C	1.1/4"	103
S35 2013KMD-112C	1.1/2"	103
S55 2013KMD-2C	2"	103
S85 2013KMD-212C	2.1/2"	63
S140 2013KMD-3C	3"	63
Tech Sheet 6490		

J+J ACTUATION

Stainless Steel 3 Way Ball Valves Fitted with a J4CS Electric Actuator

Features:
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-25°C to +180°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
63 bar



BSPP, L Port, Multi Voltage

0956	Thread
S20 2040-14	1/4"
S20 2040-38	3/8"
S20 2040-12	1/2"
S20 2040-34	3/4"
S20 2040-1	1"
S35 2040-114	1.1/4"
S55 2040-112	1.1/2"
S85 2040-2	2"
S85 2040-212	2.1/2"
Tech Sheet 6489	

BSPP, T Port, Multi Voltage

0956	Thread
S20 2041-14	1/4"
S20 2041-38	3/8"
S20 2041-12	1/2"
S20 2041-34	3/4"
S20 2041-1	1"
S35 2041-114	1.1/4"
S55 2041-112	1.1/2"
S85 2041-2	2"
S85 2041-212	2.1/2"
Tech Sheet 6489	

Fluid-Air Components Ltd

J+J ACTUATION

Stainless Steel Hygienic Ball Valves Fitted with a J4CS Electric Actuator

Features:
- Cavity filled seats
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
10 bar
(Suitable for up to 10 bar saturated steam with a TSM)



Butt Weld, Multi Voltage

0956	Size
S20 2012CD-12	1/2"
S20 2012CD-34	3/4"
S20 2012CD-1	1"
S20 2012CD-112	1.1/2"
S35 2012CD-2	2"
S55 2012CD-212	2.1/2"
S55 2012CD-3	3"
S85 2012CD-4	4"
Tech Sheet 6488	

Clamp, Multi Voltage

0956	Size
S20 2013CD-12	1/2"
S20 2013CD-34	3/4"
S20 2013CD-1	1"
S20 2013CD-112	1.1/2"
S35 2013CD-2	2"
S55 2013CD-212	2.1/2"
S55 2013CD-3	3"
S85 2013CD-4	4"
Tech Sheet 6488	

Stainless Steel Hygienic 3 Way Ball Valves Fitted with a J4CS Electric Actuator

Features:
- Cavity filled seats
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
10 bar
(Suitable for up to 10 bar saturated steam with a TSM)



Butt Weld, L Port, Multi Voltage

0956	Size
S20 2057CBL-12	1/2"
S20 2057CBL-1	1"
S20 2057CBL-112	1.1/2"
S35 2057CBL-2	2"
S85 2057CBL-212	2.1/2"
S140 2057CBL-3	3"
S140 2057CBL-4	4"
Tech Sheet 6487	

Butt Weld, T Port, Multi Voltage

0956	Size
S20 2057CBT-12	1/2"
S20 2057CBT-1	1"
S20 2057CBT-112	1.1/2"
S35 2057CBT-2	2"
S85 2057CBT-212	2.1/2"
S140 2057CBT-3	3"
S140 2057CBT-4	4"
Tech Sheet 6487	

Fluid-Air Components Ltd

J+J ACTUATION

J+J HAITIMA

Fire Safe Ball Valves Fitted with a J4CS Electric Actuator


Features:

FIRE SAFE APPROVED

- Fire Safe approved and anti-static device (valve only)
- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Suitable for up to 12 bar saturated steam with a TSM



Stainless Steel, Flanged PN16, Multi Voltage

0956	Flange Size	Max Pressure bar
S20 2019D 04	1/2"	40
S20 2019D 05	3/4"	40
S20 2019D 06	1"	40
S20 2019D 07	1.1/4"	40
S35 2019D 08	1.1/2"	40
S35 2019D 09	2"	40
S55 2019D 10	2.1/2"	16
S55 2019D 11	3"	16
S85 2019D 12	4"	16
S300 2019D 13	5"	16
Tech Sheet 6492		

Stainless Steel, Flanged PN40, Multi Voltage

0956	Flange Size	Max Pressure bar
S55 2019D4 10	2.1/2"	40
S55 2019D4 11	3"	40
S140 2019D4 12	4"	40
Tech Sheet 6492		

Carbon Steel, Flanged PN16, Multi Voltage

0956	Flange Size	Max Pressure bar
S20 2019D 04C	1/2"	40
S20 2019D 05C	3/4"	40
S20 2019D 06C	1"	40
S20 2019D 07C	1.1/4"	40
S35 2019D 08C	1.1/2"	40
S35 2019D 09C	2"	40
S55 2019D 10C	2.1/2"	16
S55 2019D 11C	3"	16
S85 2019D 12C	4"	16
Tech Sheet 6492		

Fire Safe Ball Valves Fitted with a J4CS Electric Actuator

Features:

FIRE SAFE APPROVED

- Fire Safe approved and anti-static device (valve only)
- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +230°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
19.6 bar



Flanged ANSI150, Stainless Steel, Multi Voltage

0956	Flange Size
S20 2020D 04	1/2"
S20 2020D 05	3/4"
S20 2020D 06	1"
S20 2020D 07	1.1/4"
S35 2020D 08	1.1/2"
S35 2020D 09	2"
S55 2020D 10	2.1/2"
S55 2020D 11	3"
S85 2020D 12	4"
Tech Sheet 6498	

Flanged ANSI150, Carbon Steel, Multi Voltage

0956	Flange Size
S20 2020D 04C	1/2"
S20 2020D 05C	3/4"
S20 2020D 06C	1"
S20 2020D 07C	1.1/4"
S35 2020D 08C	1.1/2"
S35 2020D 09C	2"
S55 2020D 10C	2.1/2"
S55 2020D 11C	3"
S85 2020D 12C	4"
Tech Sheet 6498	

J+J ACTUATION

Stainless Steel Flanged 3 Way Ball Valve Fitted with a J4CS Electric Actuator

Features:

- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
16 bar: PN16
19.6 bar: ANSI150



Flanged PN16, L Port, Multi Voltage

0956	Flange Size
S20 2059DL16 04	1/2"
S35 2059DL16 06	1"
S55 2059DL16 08	1.1/2"
S85 2059DL16 09	2"
S140 2059DL16 10	2.1/2"
S300 2059DL16 11	3"
S300 2059DL16 12	4"
Tech Sheet 6486	

Flanged PN16, T Port, Multi Voltage

0956	Flange Size
S20 2059DT16 04	1/2"
S35 2059DT16 06	1"
S55 2059DT16 08	1.1/2"
S85 2059DT16 09	2"
S140 2059DT16 10	2.1/2"
S300 2059DT16 11	3"
S300 2059DT16 12	4"
Tech Sheet 6486	

Flanged ANSI150, L Port, Multi Voltage

0956	Flange Size
S20 2059DL150 04	1/2"
S35 2059DL150 06	1"
S55 2059DL150 08	1.1/2"
S85 2059DL150 09	2"
Tech Sheet 6486	

Flanged ANSI150, T Port, Multi Voltage

0956	Flange Size
S20 2059DT150 04	1/2"
S35 2059DT150 06	1"
S55 2059DT150 08	1.1/2"
S85 2059DT150 09	2"
Tech Sheet 6486	

J+J ACTUATION

Cast Iron Flanged PN16 Ball Valves Fitted with a J4CS Electric Actuator

Features:

- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-10°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
16 bar



Flanged PN16, Multi Voltage

0956	Flange Size
S20 150HIT 04	1/2"
S20 150HIT 05	3/4"
S20 150HIT 06	1"
S20 150HIT 07	1.1/4"
S35 150HIT 08	1.1/2"
S55 150HIT 09	2"
S55 150HIT 10	2.1/2"
S85 150HIT 11	3"
S140 150HIT 12	4"
S300 150HIT 13	5"
S300 150HIT 14	6"
Tech Sheet 6483	

Fluid-Air Components Ltd

J+J ACTUATION

Wafer Pattern Butterfly alves Fitted with a J4CS Electric Actuator

Features:
- To suit flanges PN6/10/16, ANSI150 and BS 10 able D/E
- Multi voltage 24-240 VDC/VAC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with th J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +120°C (WA and WC)
0°C to +80°C (WB)
-20°C to +70°C (actuator)
Excluding ice and steam

Maximum Working Pressure:
16 bar



WRAS

Ductile Iron Body, EPDM Liner, Stainless Steel Disc, (WRAS Approved Valve), Multi Voltage

0956	Size
S20 2014WA 08	1.1/2"
S20 2014WA 09	2"
S20 2014WA 10	2.1/2"
S35 2014WA 11	3"
S55 2014WA 12	4"
S85 2014WA 13	5"
S140 2014WA 14	6"
S300 2014WA 16	8"
Tech Sheet 6494	

Cast Iron Body, NBR Liner, Stainless Steel Disc, Multi Voltage

0956	Size
S20 2014WB 08	1.1/2"
S20 2014WB 09	2"
S20 2014WB 10	2.1/2"
S35 2014WB 11	3"
S55 2014WB 12	4"
S85 2014WB 13	5"
S140 2014WB 14	6"
S300 2014WB 16	8"
Tech Sheet 6494	

Cast Iron Body, EPDM Liner, Ductile Iron Nickel Plated Disc, Multi Voltage

0956	Size
S20 2014WC 09	2"
S20 2014WC 10	2.1/2"
S35 2014WC 11	3"
S55 2014WC 12	4"
S85 2014WC 13	5"
S140 2014WC 14	6"
S300 2014WC 16	8"
Tech Sheet 6494	

Wafer Pattern Butterfly alves Fitted with a J4CS Electric Actuator

Features:
- To suit flanges PN6/10/16, ANSI150 and BS 10 able D/E
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuato
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-40°C to +200°C (valve)
-20°C to +70°C (actuator)

Maximum Working Pressure:
16 bar



Ductile Iron Body, Fully Lined PTFE, Multi Voltage

0956	Size
S20 2014WP 09	2"
S35 2014WP 10	2.1/2"
S55 2014WP 11	3"
S85 2014WP 12	4"
S140 2014WP 13	5"
S140 2014WP 14	6"
Tech Sheet 6479	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

J+J ACTUATION


Lugged and Tapped Butterfly alves Fitted with a J4CS Electric Actuator

Features:

- To suit PN16 flange
- Multi voltage 24-240V DC/V AC 50/60Hz
- Multicoloured LED light for continuous status feedback for the user
- Electronic torque limiter with auto gearbox relaxing
- Failsafe and/or modulating configurations can be used with the J4CS electric actuator
- Sized based on 10 bar wet non-abrasive duty at +70°C

Working Temperature:
-20°C to +120°C (2014LA)
0°C to +80°C (2014LB)
-20°C to +70°C (actuator)
Excluding ice and steam

Maximum Working Pressure:
16 bar



Ductile Iron Body, EPDM Liner, Stainless Steel Disc, (WRAS Approved Valve), Multi Voltage

0956	Size
S20 2014LA 08	1.1/2"
S20 2014LA 09	2"
S20 2014LA 10	2.1/2"
S35 2014LA 11	3"
S55 2014LA 12	4"
S85 2014LA 13	5"
S140 2014LA 14	6"
S300 2014LA 16	8"
Tech Sheet 6493	

Ductile Iron Body, NBR Liner, Stainless Steel Disc, Multi Voltage

0956	Size
S20 2014LB 08	1.1/2"
S20 2014LB 09	2"
S20 2014LB 10	2.1/2"
S35 2014LB 11	3"
S55 2014LB 12	4"
S85 2014LB 13	5"
S140 2014LB 14	6"
S300 2014LB 16	8"
Tech Sheet 6493	

Do you require...
failsafe and/or modulating configurations?
...see page **1019**



Fluid-Air Components Ltd

HAITIMA ACTUATION

HAITIMA

Pneumatic Actuators

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Hard anodized aluminium body
- ATEX II 2GD c T5 certificatio
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- Epoxy coated end caps
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-20°C to +90°C

Maximum Working Pressure:
8 bar



Single Acting

0929	Torque (Nm) - Single Acting - 12 Springs	
	Initial Air at 6 bar	End of Spring
HTS-040-2	9.93	4.13
HTS-052-12	15.46	9.50
HTS-063-12	27	16.90
HTS-075-12	42.10	28.40
HTS-083-12	56.20	34.78
HTS-092-12	82.40	54
HTS-105-12	123.90	79.70
HTS-125-12	207.30	142.50
HTS-140-12	314	212.40
HTS-160-12	474.60	327.60
HTS-190-12	771.10	521.80
HTS-210-12	1059.60	717
HTS-240-12	1660.70	1124.30
Tech Sheet 6183		

Double Acting

0929	Torque (Nm) - Double Acting
	at 6 bar
HTD-032	9
HTD-052	24.96
HTD-063	43.92
HTD-075	70.50
HTD-083	89.10
HTD-092	136.40
HTD-105	203.64
HTD-125	349.80
HTD-140	526.44
HTD-160	802.20
HTD-190	1292.90
HTD-210	1776.70
HTD-240	2444.60
Tech Sheet 6183	

AIR TORQUE ACTUATION

AIR TORQUE

new product

Pneumatic Actuators

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Alodur hard anaodied aluminium body
- ATEX 2014/34/EU certificatio
- SIL3 rated
- DNV certificatio
- IP67 rating with IP68 at manufacturers request
- Universal and anti-blowout patented drive shaft
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-40°C to +80°C

Maximum Working Pressure:
8 bar



Single Acting

0957	Torque (Nm) - End of Spring
AT051S10	6.70
AT101S12	13.30
AT201S10	22.10
AT251S09	33
AT301S10	50.70
AT351S09	73.80
AT401S12	126
AT451S11	181
AT501S09	202
Tech Sheet 6293	

Double Acting

0957	Torque (Nm) - Double Acting at 5.5 bar
AT051	18.30
AT101	32.20
AT201	64
AT251	101
AT301	146
AT351	236
AT401	305
Tech Sheet 6293	

Larger sizes available on request

PRISMA ACTUATION

Pneumatic Actuators

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Rilsan and epoxy coated aluminium body
- ATEX II 2G Ex h IIB T6 Gb / II 2D Ex h IIIC T80°C Db certificatio
- Suitable for use in a SIL safety loop
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-32°C to +90°C

Maximum Working Pressure:
8 bar



Single Acting

0946	Torque (Nm) - Single Acting - 6+6 Spring	
	Initial Air at 6 bar	End of Spring
PAWS-F04	10.30	6.70
PA00S	15.80	12.70
PA05S	28.80	20.90
PA10S	40.20	30.80
PA15S	67.50	49
PA20S	99.70	65.80
PA25S	170.60	119.40
PA30S	273.50	195.70
P40S	688.30	491.60
PA50S	1248	819.50
PA60S	2074	1383
PA70S	3273	1769
Tech Sheet 6209		

Double Acting

0946	Torque (Nm) - Double Acting at 6 bar
PAW	17
PA00	28.50
PA05	49.70
PA10	71
PA15	116.50
PA20	165.50
PA25	290
PA30	269.20
P40	1180
PA50	2067
PA60	3458
PA70	5043
Tech Sheet 6209	

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Polyamide body
- ATEX II 2G Ex h IIC T6 Gb / II 2D Ex h IIIC T80°C Db certificatio
- SIL3 rated
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-32°C to +80°C

Maximum Working Pressure:
8 bar



Single Acting

0946	Torque (Nm) - Single Acting - 6+6 Spring	
	Initial Air at 6 bar	End of Spring
PPWS	10.30	6.70
PP00S	15.80	12.70
PP10S	40.20	30.80
PP20S	99.70	65.80
Tech Sheet 6210		

Double Acting

0946	Torque (Nm) - Double Acting at 6 bar
PPW	17
PP00	28.50
PP10	71
PP20	165.50
Tech Sheet 6210	

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Stainless steel body
- ATEX II 2G Ex h IIC T6 Gb / II 2D Ex h IIIC T80°C Db certificatio
- Suitable for use in a SIL safety loop
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-32°C to +90°C

Maximum Working Pressure:
8 bar



Single Acting

0946	Torque (Nm) - Single Acting		
	Initial Air at 6 bar	End of Spring	Spring
PI00S	13.70	11.30	4+4
PI10S	38.70	32.30	4+4
PI20S	99.70	65.80	3+3
PI30S	289.30	179.90	4+4
PI40S	688.30	491.60	4+4
Tech Sheet 6211			

Double Acting

0946	Torque (Nm) - Double Acting at 6 bar
PI00	25
PI10	71
PI20	165.50
PI30	469.20
PI40	1180
Tech Sheet 6211	

Fluid-Air Components Ltd

FESTO ACTUATION

Pneumatic Actuators

Features:
- 0-90° rotation angle to pilot ball, butterfly and plug valve
- Aluminium body or epoxy coated aluminium body options available
- ATEX II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T105°C Db certificatio
- DNV certifie
- SIL2 rated
- Conforms to ISO 5211, DIN 3337 and VDI/VDE 3845
- NAMUR pneumatic connection for solenoid valve installation

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
8 bar



DFPD Single Acting Pneumatic Actuator - Aluminium Body

0990	Size	Manufacturer's Code
8047622	20	DFPD-20-RP-90-RS60-F04
8047624	40	DFPD-40-RP-90-RS60-F0507
8047626	80	DFPD-80-RP-90-RS60-F0507
8048134	120	DFPD-120-RP-90-RS60-F0507
8048136	160	DFPD-160-RP-90-RS60-F0710
8048138	240	DFPD-240-RP-90-RS60-F0710
8048140	300	DFPD-300-RP-90-RS60-F0710
8048142	480	DFPD-480-RP-90-RS60-F1012
8065262	700	DFPD-700-RP-90-RS60-F1012
8065266	900	DFPD-900-RP-90-RS60-F14
8065270	1200	DFPD-1200-RP-90-RS60-F14
8065274	2300	DFPD-2300-RP-90-RS60-F1216
	Tech Sheet 6270	

DFPD Single Acting Pneumatic Actuator - Epoxy Coated Aluminium Body

0990	Size	Manufacturer's Code
8047646	20	DFPD-20-RP-90-RS30-F03-R3-EP
8047642	40	DFPD-40-RP-90-RS30-F04-R3-EP
8047631	80	DFPD-80-RP-90-RS30-F0507-R3-EP
8048143	120	DFPD-120-RP-90-RS30-F0507-R3-EP
8048145	160	DFPD-160-RP-90-RS30-F0710-R3-EP
8048147	240	DFPD-240-RP-90-RS30-F0710-R3-EP
8048149	300	DFPD-300-RP-90-RS30-F0710-R3-EP
8048151	480	DFPD-480-RP-90-RS30-F1012-R3-EP
8065264	700	DFPD-700-RP-90-RS60-F1012-R3-EP
8065268	900	DFPD-900-RP-90-RS60-F14-R3-EP
8065272	1200	DFPD-1200-RP-90-RS60-F14-R3-EP
8065276	2300	DFPD-2300-RP-90-RS60-F1216-R3-EP
	Tech Sheet 6270	

DFPD Double Acting Pneumatic Actuator - Aluminium Body

0990	Size	Manufacturer's Code
8047613	10	DFPD-10-RP-90-RD-F03
8047614	20	DFPD-20-RP-90-RD-F04
8047615	40	DFPD-40-RP-90-RD-F0507
8047616	80	DFPD-80-RP-90-RD-F0507
8048123	120	DFPD-120-RP-90-RD-F0507
8048124	160	DFPD-160-RP-90-RD-F0710
8048125	240	DFPD-240-RP-90-RD-F0710
8048126	300	DFPD-300-RP-90-RD-F0710
8048127	480	DFPD-480-RP-90-RD-F1012
8065261	700	DFPD-700-RP-90-RD-F1012
8065265	900	DFPD-900-RP-90-RD-F14
8065269	1200	DFPD-1200-RP-90-RD-F14
8065273	2300	DFPD-2300-RP-90-RD-F1216
	Tech Sheet 6270	

DFPD Double Acting Pneumatic Actuator - Epoxy Coated Aluminium Body

0990	Size	Manufacturer's Code
8047617	10	DFPD-10-RP-90-RD-F03-R3-EP
8047618	20	DFPD-20-RP-90-RD-F04-R3-EP
8047619	40	DFPD-40-RP-90-RD-F0507-R3-EP
8047620	80	DFPD-80-RP-90-RD-F0507-R3-EP
8048128	120	DFPD-120-RP-90-RD-F0507-R3-EP
8048129	160	DFPD-160-RP-90-RD-F0710-R3-EP
8048130	240	DFPD-240-RP-90-RD-F0710-R3-EP
8048131	300	DFPD-300-RP-90-RD-F0710-R3-EP
8048132	480	DFPD-480-RP-90-RD-F1012-R3-EP
8065263	700	DFPD-700-RP-90-RD-F1012-R3-EP
8065267	900	DFPD-900-RP-90-RD-F14-R3-EP
8065271	1200	DFPD-1200-RP-90-RD-F14-R3-EP
8065275	2300	DFPD-2300-RP-90-RD-F1216-R3-EP
	Tech Sheet 6270	

Position Indicator

Features:
- PA plastic material
- 2 position indicators suitable for all quarter turn actuator sizes
- Suitable for use in ATEX zones



SASF Position Indicator

0990	Manufacturer's Code
4046082	SASF-S2-B-F-A34
Tech Sheet 6271	

Fluid-Air Components Ltd

J+J ACTUATION

Electric Actuators

Features:

- IP67 fully weatherproof polyamide PA6 housing
- Multicoloured LED light for continuous status feedback for the user
- Auto voltage sensing 24-240 VDC/VAC 50/60Hz. A 12 VDC/VAC 50/60Hz option is also available on request (J4CB)
- The J4CS series has brushless motor technology with each unit now having a 3 year warranty from shipment date or up to 60,000 working cycles, whichever comes firs
- Electronic torque limiter with auto gearbox relaxing
- Thermostatic 3.5W anti-condensation heater
- Local dome style visual position indicator
- Handwheel operated selectable manual override
- Two volt free end of travel position confirmation switche
- All external electrical connections via DIN plugs.
  Large Plug EN175301-803 Form A, small plug DIN 43650/C
- External wiring diagram showing 2 and 3 wire
- Multi-flange mounting to ISO 5211 and DIN 333
- Duty rating 75%

Options:

- Failsafe battery 'spring' return backup kit
- DPS modulating digital positioner system kit
- Interface system kit allowing communication with the actuator, read parameters and change the actuator configuration
- Bluetooth technology
- Modbus technology

Working Temperature:
-20°C to +70°C



J4CS Smart True Multi Voltage Electric Actuator

0956	Maximum Run Torque Nm	Maximum Break Torque Nm	Operating Speed	ISO Plate 5211	DIN 3337 Female Output Drive
J4CS20	20	25	9 sec	F03/F04/F05	14mm
J4CS35	35	38	9 sec	F03/F04/F05	14mm
J4CS55	55	60	13 sec	F05/F07	17mm
J4CS85	85	90	29 sec	F05/F07	17mm
J4CS140	140	170	34 sec	F07/F10	22mm
J4CS300	300	350	58 sec	F07/F10	22mm
		Tech Sheet 6255			

Option of a F07 x 17mm with a kit for the J4CS20 and J4CS35

Electric Actuators

Features:

- IP65 polyamide PA6 housing
- Main shaft made from stainless steel
- Polyamide gears
- Available in high voltage 110-240V DC/V AC 50/60Hz
  or low voltage 24V DC/V AC 50/60Hz
- Thermostatic 3.5W anti-condensation heater
- Local visual position indicator
- Selectable manual override
- Two volt free end of travel position confirmation switche
- All external electrical connections via DIN plugs large plug
  EN175301-803 form A, small plug DIN 43650/C
- External wiring diagram showing 2 and 3 wire
- Mounting to ISO 5211 and DIN 3337 female star drive
- Duty rating 75%

Working Temperature:
-20°C to +70°C



J2 10Nm Electric Actuator

0956	Maximum Run Torque Nm	Maximum Break Torque Nm	Operating Speed	ISO Plate 5211	Consumption	DIN 3337 Female Output Drive
J2H10	10	12	16 sec	F03/F05	110V 0.272A 30W 220V 0.272A 60W	14mm
J2L10	10	12	19 sec	F03/F05	24V 0.39A 9.36W	14mm
			Tech Sheet 6256			

Please note: **Failsafe and/or modulating configurations cannot be used with the J2-10 electric actuator.**

Fluid-Air Components Ltd

J+J ACTUATION

Electric Actuator Kits

Features:

- Battery 'spring' return kit for the J4CS electric actuators
- Can be set to fail open or closed (please specify)
- Can be retro-fitted to existing J4CS actuators.
  Also comes complete with installation instructions
- Rechargeable NiCd battery
- Both the BSR and DPS kit can be installed together to provide failsafe and modulating functionality




Supplied in display box.

BSR Battery Backup Plug-in

0956	To Suit Models
J4CSBSR1	20 to 85
J4CSBSR2	140 to 300
Tech Sheet 6257	

Features:

- Digital positioning system for the J4CS electric actuators
- 0-20mA, 4-20mA, 0-10V or 1-10V input/output options available
- Can be retro-fitted to existing J4CS actuators. Also comes complete with installation instructions
- Can be set to fail open or fail close on loss of control signal.
  A fail freeze option is also available but it requires the interface system kit fitted to the J4CS electric actuato
- Both the DPS and BSR kit can be installed together to provide failsafe and modulating functionality



Supplied in display box.

DPS Digital Positioning System

0956	To Suit Models
J4CSDPS1	20 to 85
J4CSDPS2	140 to 300
Tech Sheet 6258	

Mounting Brackets

- Designed for use with the FIP TKD and VKD ball valve series
- Standard holes drilled according to ISO 5211 specificatio
- Drive adapter to suit DIN 3337

new product



FIP EasyFit Kit

0956	Size	ISO Plate 5211	Square Size mm
ACTMKEASYFIP-12	D20/DN15/1/2"	F03/F04/F05	9
ACTMKEASYFIP-34	D25/DN20/3/4"	F03/F04/F05	9
ACTMKEASYFIP-1	D32/DN25/1"	F03/F04/F05	9
ACTMKEASYFIP-114	D40/DN32/1.1/4"	F05/F07	11
ACTMKEASYFIP-112	D50/DN40/1.1/2"	F05/F07	11
ACTMKEASYFIP-2	D65/DN50/2"	F05/F07	11

- Designed for use with the Georg Fischer 546 ball valve series
- Standard holes drilled according to ISO 5211 specificatio
- Drive adapter to suit DIN 3337

new product



GF 546 Kit

0956	Size	ISO Plate 5211	Square Size mm
ACTMKEASYGF-12	D20/DN15/1/2"	F03/F05	11
ACTMKEASYGF-1	D32-D25/DN25-DN20/3/4"-1"	F03/F05	11
ACTMKEASYGF-112	D50-D40/DN40-DN32/1.1/4"-1.1/2"	F03/F05	11
ACTMKEASYGF-2	D63/DN50/2"	F03/F05	11

Fluid-Air Components Ltd

PNEUMATIC ACTUATOR ACCESSORIES

Pilot Accessories

Features:
- For use with compressed air
- Internally piloted
- Anodised aluminium alloy body
- Suitable for single and double acting pneumatic actuators
- 5 port 2 position
- Manual override
- NAMUR and VDI/VDE 3845 standard interface for direct mounting to pneumatic actuators
- 1/4" BSPP inlet and exhaust ports
- Insulation class F
- LED DIN plug
- For safe area use only
- Flow rate 30kg/mm² (Cv=1.68)
- Voltage tolerance ± 10%
- Response time 0.05 seconds
- Terminal DIN 43650B
- IP65 rated
- Maximum frequency is 5 cycles per second

Working Temperature:
-5°C to +60°C

Maximum Working Pressure:
8 bar





NAMUR 5/2 Solenoid Valve Single Coil

0929	Voltage
HUKNAM24VDC	24V DC
HUKNAM24VAC	24V AC
HUKNAM110VAC	110V AC
HUKNAM230VAC	230V AC
Tech Sheet 6244	

FESTO ACTUATION

Pilot Accessories

Features:
- 5 port 2 position
- Can be changed between 3/2 and 5/2 by exchanging the sealing plate
- NAMUR and VDI/VDE 3845 standard interface for direct mounting to pneumatic actuators
- Non-detenting/detenting manual override
- IP65 rating with a DIN connector fitted
- Solenoid coil and DIN plug to be ordered separately
- For the flameproof option the interface and flameproof solenoid coil need to be ordered

Working Temperature:
-20°C to +60°C

Maximum Working Pressure:
10 bar



VSNC NAMUR 5/2 Solenoid Valve Single Coil

0990	Manufacturer's Code	Size
577257	VSNC-FC-M52-MD-G14-F8	1/4"
Tech Sheet 6271		

Features:
- Electrical connection according to DIN EN 175301-803 Form A
- Any mounting position
- IP65 rating
- 100% duty rating



Solenoid Coil

0990	Manufacturer's Code	Voltage
8029144	VACN-N-A1-1	24V DC
8029134	VACN-N-A1-16B	110V AC
8029135	VACN-N-A1-3A	230V AC
Tech Sheet 6272		

Features:
- ATEX II 3G Ex nA IIC T4 Gc / II 3D Ex tc IIIC T105°C Dc certification

ATEX Solenoid Coil with DIN Plug

0990	Manufacturer's Code	Voltage
8029136	VACN-N-A1-1-EX2-N	24V DC
8029137	VACN-N-A1-16B-EX2-N	110V AC
8029138	VACN-N-A1-3A-EX2-N	230V AC
Tech Sheet 6273		

Features:
- Electricial connection according to DIN EN 175301-803 Form A
- Reinforced PA housing
- IP65 rating



DIN Plug

0990	Manufacturer's Code
34583	MSSD-C
Tech Sheet 6275	

Features:
- ATEX II 2G Ex ia IIC T4 Ga / II 2D Ex tb IIIC T130°C Db certification

ATEX Solenoid Coil with DIN Plug

0990	Manufacturer's Code	Voltage
8029139	VACN-N-A1-1-EX4-A	24V DC
Tech Sheet 6274		



Solenoid Interface for Flameproof Coil Option

0990	Manufacturer's Code	Voltage
571061	VSCS-B-M32-MD-WA-1C1	24V DC
Tech Sheet 71760		

Features:
- ATEX II 2G Ex db IIC T5 Gb / II 2D Ex tb IIIC T100°C Db certification



Flameproof Solenoid Coil

0990	Manufacturer's Code	Voltage
535615	MGXDH-3/2-1.2-24DC-EX	24V DC
Tech Sheet 6277		

Fluid-Air Components Ltd

PNEUMATIC ACTUATOR ACCESSORIES

Pilot Accessories


The interface design is conform to the NAMUR standard and to the VDI/VDE 3845 recommendations of the actuator industry. It allows a compact design of the actuator/valve unit.
In case of a 3/2 function, the air of the actuator spring chamber also flows through the pilot valve (re-breather function). This prevents corrosion of the actuator springs.

Working Temperature:
-10°C to +50°C

Maximum Working Pressure:
10 bar

Normally Closed, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
341N35-4818653D	1/4"	230V AC	341N35-2995-4818653D
341N35-481865C2	1/4"	24V DC	341N35-2995-481865C2
		Tech Sheet 60419	




Normally Closed, suitable for Atex Zone 1/22, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
341N35-4958703D	1/4"	230V AC	341N35-2995-4958703D
341N35-495870C2	1/4"	24V DC	341N35-2995-495870C2
		Tech Sheet 60419	

Normally Closed, suitable for Atex Zone 1/21, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
341N35-495905C2	1/4"	230V AC	341N35-495905C2
		Tech Sheet 60419	

FT PRO



Customers who bought from this page also purchased
Pneumatic Quick Release Couplings
see page **631**

Fluid-Air Components Ltd

PNEUMATIC ACTUATOR ACCESSORIES

FT PRO

Pilot Accessories

Features:
- Aluminium IP67 enclosure
- Beacon indicator
- Stainless steel shaft
- Universal NAMUR and VDI/VDE 3845 mounting bracket
- 2 x SPDT 250V DC/AC V3 micro switches
- 2 x M20 cable entries
- Terminal strip connection
- For safe area use only

Working Temperature:
-20°C to +80°C



Safe Area Mechanical Switch Box

0364
KLS-820M
Tech Sheet 10142

PNEUMATIC ACTUATOR ACCESSORIES

HAITIMA

Pilot Accessories

Features:
- Aluminium IP67 enclosure
- Beacon indicator
- Stainless steel shaft
- Universal NAMUR and VDI/VDE 3845 mounting bracket
- 2 x SPDT 250V DC/AC V3 micro switches
- 2 x M20 cable entries
- Terminal strip connection
- For safe area use only

Working Temperature:
-20°C to +80°C



Safe Area Mechanical Switch Box

0929
HUKSBOX
Tech Sheet 6246

PNEUMATIC ACTUATOR ACCESSORIES

Prisma

Pilot Accessories

Features:
- Aluminium IP67 enclosure
- Beacon indicator
- Stainless steel shaft
- Stainless steel NAMUR mounting bracket
- Stainless steel bolting
- Polycarbonate indicator cover
- For safe area use only
- 2 x SPDT 250V DC/AC V3 micro switches
- 2 x M20 cable entries

Working Temperature:
-20°C to +80°C



Safe Area Mechanical Switch Box

0946	NAMUR Size
EFC5601W	80 x 30 x 20 or 80 x 30 x 30
EFC56014	130 x 30 x 50
Tech Sheet 6247	

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FESTO ACTUATION

Pilot Accessories

Features:
- Aluminium IP67 enclosure
- Beacon indicator
- NAMUR and VDI/VDE 3845 mounting bracket
- SIL2 rated
- Stainless steel shaft
- 2 x SPDT 30V DC 250V AC micro switches
- 2 x M20 cable entries

Working Temperature:
-20°C to +80°C



SRBC Mechanical Switch Box

0990	Manufacturer's Code
3482805	SRBC-CA3-YR90-MW-22A-1W-C2P20
	Tech Sheet 6263

Features:
- ATEX II 1G Ex ia IIC T5 Ga / II 1D Ex ia IIIC Txx°C Da certificatio

SRBC Hazardous Area Mechanical Switch Box

0990	Manufacturer's Code
3482807	SRBC-CA3-YR90-N-20N-ZC-C2P20-EX6
	Tech Sheet 6263

Pilot Accessories

Features:
- Aluminium IP67 enclosure
- ATEX II 2G Ex db IIC T6 Gb / II 2D Ex tb IIIC Txx°C Db certificatio
- Beacon indicator
- NAMUR and VDI/VDE 3845 mounting bracket
- SIL2 rated
- Stainless steel shaft
- 2 x SPDT 30V DC 250V AC micro switches
- Changeover switch, floating contac
- 2 x M20 cable entries

Working Temperature:
-20°C to +60°C

new product



SRBC Flameproof Enclosure Mechanical Switch Box

0990	Manufacturer's Code
3471009	SRBE-CA3-YR90-MW-22A-1W-C2M20-EX
	Tech Sheet 6290

PNEUMATIC ACTUATOR ACCESSORIES

Pilot Accessories

- Aluminum housing
- NAMUR and VDI/VDE 3845 standard interface for direct mounting to pneumatic actuators

Working Temperature:
-20°C to +60°C



Features:
- ATEX II 2G Ex dmb IIB T5 certificatio
- 1/2" BSPP conduit and 1/4" NPT air connection

YT-1000 Rotary Electro-Pneumatic Single Acting Positioner

0920
YT-1000RDM534S00
Tech Sheet 6248

Features:
- Non-explosive
- 4-20mA internal feedback
- M20 conduit and 1/4" NPT air connection

YT-1000 Rotary Electro-Pneumatic Double Acting Positioner with 4-20mA Feedback

0920
YT-1000RDN534S01
Tech Sheet 6248

Automatic Drain Valves



RoHS 3 COMPLIANT

FT PRO

Easy Timer

Valve Body: Brass
Orifice Size: 4.5 mm
IP65 Protection

Easy Timer
Timer On 0.5 to 10s
Timer Off 0.5 to 45 min
Test switch



Brass Valve

0016	Thread	Voltage
720-01AC220	1/8"	220V AC
720-02AC220	1/4"	220V AC
720-03AC220	3/8"	220V AC
720-04AC220	1/2"	220V AC
720-01AC110	1/8"	110V AC
720-02AC110	1/4"	110V AC
720-03AC110	3/8"	110V AC
720-04AC110	1/2"	110V AC
720-02DC24	1/4"	24V DC
720-03DC24	3/8"	24V DC
720-04DC24	1/2"	24V DC
720-02AC24	1/4"	24V AC
720-03AC24	3/8"	24V AC
720-04AC24	1/2"	24V AC

Tech Sheet 70001



Brass Valve with Vertical Strainer

0016	Thread	Voltage
720-01AC220-VIS	1/8"	220V AC
720-02AC220-VIS	1/4"	220V AC
720-03AC220-VIS	3/8"	220V AC
720-04AC220-VIS	1/2"	220V AC
720-01AC110-VIS	1/8"	110V AC
720-02AC110-VIS	1/4"	110V AC
720-03AC110-VIS	3/8"	110V AC
720-04AC110-VIS	1/2"	110V AC
720-02DC24-VIS	1/4"	24V DC
720-03DC24-VIS	3/8"	24V DC
720-04DC24-VIS	1/2"	24V DC
720-02AC24-VIS	1/4"	24V AC
720-03AC24-VIS	3/8"	24V AC
720-04AC24-VIS	1/2"	24V AC

Tech Sheet 71676

Valve Body: Brass
Orifice Size: 3.5 mm
Mesh Size: 29 micron
Manual isolation shut-off
IP65 Protection

Easy Timer
Timer On 0.5 to 10s
Timer Off 0.5 to 45 min
Test switch



Brass Valve with Strainer

0016	Thread	Voltage
728A-04AC220	1/2"	220V AC
728A-04AC110	1/2"	110V AC
728A-04AC24	1/2"	24V AC

Tech Sheet 70002

AUTOMATIC DRAIN VALVES

Digital Timer

Valve Body: Brass
Orifice Size: 4.5 mm
IP65 Protection
Digital Timer
Timer On 0.1 to 99s
Timer Off 0.5 to 99 min
Test switch



Brass Valve

0016	Thread	Voltage
790-01AC220	1/8"	220V AC
790-02AC220	1/4"	220V AC
790-03AC220	3/8"	220V AC
790-04AC220	1/2"	220V AC
790-01AC110	1/8"	110V AC
790-02AC110	1/4"	110V AC
790-03AC110	3/8"	110V AC
790-04AC110	1/2"	110V AC
790-01DC24	1/8"	24V DC
790-02DC24	1/4"	24V DC
790-03DC24	3/8"	24V DC
790-04DC24	1/2"	24V DC
790-02AC24	1/4"	24V AC
790-03AC24	3/8"	24V AC
790-04AC24	1/2"	24V AC

Tech Sheet 70003



Brass Valve with Vertical Strainer

0016	Thread	Voltage
790-01AC220-VIS	1/8"	220V AC
790-02AC220-VIS	1/4"	220V AC
790-03AC220-VIS	3/8"	220V AC
790-04AC220-VIS	1/2"	220V AC
790-01AC110-VIS	1/8"	110V AC
790-02AC110-VIS	1/4"	110V AC
790-03AC110-VIS	3/8"	110V AC
790-04AC110-VIS	1/2"	110V AC
790-01DC24-VIS	1/8"	24V DC
790-02DC24-VIS	1/4"	24V DC
790-03DC24-VIS	3/8"	24V DC
790-04DC24-VIS	1/2"	24V DC
790-02AC24-VIS	1/4"	24V AC
790-03AC24-VIS	3/8"	24V AC
790-04AC24-VIS	1/2"	24V AC

Tech Sheet 71677

Valve Body: Brass
Orifice Size: 3.5 mm
Mesh Size: 29 micron
Manual isolation shut-off
IP65 Protection

Digital Timer
Timer On 0.1 to 99s
Timer Off 0.5 to 99 min
Test switch



Brass Valve with Strainer

0016	Thread	Voltage
728A790-04AC220	1/2"	220V AC
728A790-04DC24	1/2"	24V DC

Tech Sheet 70004

Spare Parts

Valve Body: Brass
Orifice Size: 4.5 mm

Working Temperature: -10°C to +70°C

Maximum Working Pressure: 16 bar



Brass Valve

0016	Thread
CS-720W-01	1/8"
CS-720W-02	1/4"
CS-720W-03	3/8"
CS-720W-04	1/2"

Valve Body: Brass
Orifice Size: 3.5 mm

Working Temperature: -10°C to +70°C

High pressure 80 bar option available on request.

Mesh Size: 29 micron
Manual isolation shut-off

Maximum Working Pressure: 16 bar



Brass Strainer

0016	Thread
CS-S95-01	1/8"
CS-S95-03	3/8"
CS-S95-04	1/2"
CS-S95-02	1/4"

Easy Timer
Timer On 0.5 to 10s
Timer Off 0.5 to 45 min
Test switch



Easy

Digital Timer
Timer On 0.1 to 99s
Timer Off 0.5 to 99 min
Test switch



Digital

Timer

0016	Voltage	Operation
XY-720	24-220V AC/DC	Easy
XY-790H	110-220V AC/DC	Digital
XY-790L	24V AC/DC	Digital

Speak to Technical for most recent UL certification guidance for high voltage applications (110V and 220V AC).



Coil

0016	Voltage
SB256-0543AC110	110V AC
SB256-0543AC220	220V AC
SB256-0543AC24	24V AC
SB257-0545DC24	24V DC



Connector

0016
SB201-1

Fluid-Air Components Ltd

Solenoid Valves


The general purpose brass 2/2 solenoid valves again shows FT Pro's commitment to providing innovative and added value solutions to their customers.



Valve Timer



Pilot Operated 2/2 Solenoid Valve



Direct Acting 2/2 Solenoid Valve

Pilot Operated 2/2:

- Normally open
- Normally closed
- DIN connectors
- Valve timers
- DC and AC coils
- Available in sizes 3/8" to 2" BSPP
- Media: oil, air and water

Direct Acting 2/2:

- Normally closed
- DIN connectors
- DC and AC coils
- Available in sizes 1/8" to 3/8" BSPP
- Available in 0-10 bar and 0 to 35 bar
- High pressure option
- Media: oil, air and water

Fluid-Air Components Ltd

General Purpose 2/2 N/C, Pilot Operated

Working Pressure:
0.5 to 10 bar



Flow Rate 55 L/min
Orifice 13mm

3/8" BSPP

0366	Voltage
K225-03-230AC-NC	230/50V AC
K225-03-110AC-NC	110/50V AC
K225-03-24AC-NC	24/50V AC
K225-03-24DC-NC	24V DC
K225-03-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 63 L/min
Orifice 13mm

1/2" BSPP

0366	Voltage
K225-04-230AC-NC	230/50V AC
K225-04-110AC-NC	110/50V AC
K225-04-24AC-NC	24/50V AC
K225-04-24DC-NC	24V DC
K225-04-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 100 L/min
Orifice 25mm

3/4" BSPP

0366	Voltage
K225-06-230AC-NC	230/50V AC
K225-06-110AC-NC	110/50V AC
K225-06-24AC-NC	24/50V AC
K225-06-24DC-NC	24V DC
K225-06-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 160 L/min
Orifice 25mm

1" BSPP

0366	Voltage
K225-08-230AC-NC	230/50V AC
K225-08-110AC-NC	110/50V AC
K225-08-24AC-NC	24/50V AC
K225-08-24DC-NC	24V DC
K225-08-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 370 L/min
Orifice 38mm

1.1/4" BSPP

0366	Voltage
K225-12-230AC-NC	230/50V AC
K225-12-110AC-NC	110/50V AC
K225-12-24AC-NC	24/50V AC
K225-12-24DC-NC	24V DC
K225-12-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 400 L/min
Orifice 38mm

1.1/2" BSPP

0366	Voltage
K225-14-230AC-NC	230/50V AC
K225-14-110AC-NC	110/50V AC
K225-14-24AC-NC	24/50V AC
K225-14-24DC-NC	24V DC
K225-14-12DC-NC	12V DC
Tech Sheet 10162	

Flow Rate 540 L/min
Orifice 50mm

2" BSPP

0366	Voltage
K225-20-230AC-NC	230/50V AC
K225-20-110AC-NC	110/50V AC
K225-20-24AC-NC	24/50V AC
K225-20-24DC-NC	24V DC
K225-20-12DC-NC	12V DC
Tech Sheet 10162	

Coils to suit K225, Normally Closed Valves



Coil & Plug

0366	Voltage
K225-230/50AC-NC	230/50V AC
K225-110/50AC-NC	110/50V AC
K225-24/50AC-NC	24/50V AC
K225-24DC-NC	24V DC
K225-12DC-NC	12V DC
Tech Sheet 10162	

FT PRO



For **Pre wired moulded DIN Plugs** see page **1042**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SOLENOID VALVES

General Purpose 2/2 N/O, Pilot Operated

Working Pressure:
0.5 to 10 bar



Flow Rate 55 L/min
Orifice 13mm

3/8" BSPP

0366	Voltage
K225-03-230AC-NO	230/50V AC
K225-03-110AC-NO	110/50V AC
K225-03-24AC-NO	24/50V AC
K225-03-24DC-NO	24V DC
K225-03-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 63 L/min
Orifice 13mm

1/2" BSPP

0366	Voltage
K225-04-230AC-NO	230/50V AC
K225-04-110AC-NO	110/50V AC
K225-04-24AC-NO	24/50V AC
K225-04-24DC-NO	24V DC
K225-04-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 100 L/min
Orifice 25mm

3/4" BSPP

0366	Voltage
K225-06-230AC-NO	230/50V AC
K225-06-110AC-NO	110/50V AC
K225-06-24AC-NO	24/50V AC
K225-06-24DC-NO	24V DC
K225-06-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 160 L/min
Orifice 25mm

1" BSPP

0366	Voltage
K225-08-230AC-NO	230/50V AC
K225-08-110AC-NO	110/50V AC
K225-08-24AC-NO	24/50V AC
K225-08-24DC-NO	24V DC
K225-08-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 370 L/min
Orifice 38mm

1.1/4" BSPP

0366	Voltage
K225-12-230AC-NO	230/50V AC
K225-12-110AC-NO	110/50V AC
K225-12-24AC-NO	24/50V AC
K225-12-24DC-NO	24V DC
K225-12-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 400 L/min
Orifice 38mm

1.1/2" BSPP

0366	Voltage
K225-14-230AC-NO	230/50V AC
K225-14-110AC-NO	110/50V AC
K225-14-24AC-NO	24/50V AC
K225-14-24DC-NO	24V DC
K225-14-12DC-NO	12V DC
Tech Sheet 10162	

Flow Rate 540 L/min
Orifice 50mm

2" BSPP

0366	Voltage
K225-20-230AC-NO	230/50V AC
K225-20-110AC-NO	110/50V AC
K225-20-24AC-NO	24/50V AC
K225-20-24DC-NO	24V DC
K225-20-12DC-NO	12V DC
Tech Sheet 10162	

Coils to suit K225, Normally Open Valves



Coil & Plug

0366	Voltage
K225-230/50AC-NO	230/50V AC
K225-110/50AC-NO	110/50V AC
K225-24/50AC-NO	24/50V AC
K225-24DC-NO	24V DC
K225-12DC-NO	12V DC
Tech Sheet 10162	

Valve Timer



0366
KVT
Tech Sheet 10162

Fluid-Air Components Ltd

General Purpose 2/2 N/C, Direct Acting

Working Pressure:
7 bar
Maximum Working Pressure:
10 bar



Flow Rate 3.4 L/min
Orifice 2.5mm

1/8" BSPP

0366	Voltage
K2W025-06-230AC	230/50V AC
K2W025-06-110AC	110/50V AC
K2W025-06-24AC	24/50V AC
K2W025-06-24DC	24V DC
K2W025-06-12DC	12V DC
Tech Sheet 10163	

Flow Rate 3.4 L/min
Orifice 2.5mm

1/4" BSPP

0366	Voltage
K2W025-08-230AC	230/50V AC
K2W025-08-110AC	110/50V AC
K2W025-08-24AC	24/50V AC
K2W025-08-24DC	24V DC
K2W025-08-12DC	12V DC
Tech Sheet 10163	

Flow Rate 6 L/min
Orifice 4mm

3/8" BSPP

0366	Voltage
K2W040-10-230AC	230/50V AC
K2W040-10-110AC	110/50V AC
K2W040-10-24AC	24/50V AC
K2W040-10-24DC	24V DC
K2W040-10-12DC	12V DC
Tech Sheet 10163	

High Pressure 2/2 N/C, Direct Acting

Working Pressure:
20 bar
Maximum Working Pressure:
35 bar



Flow Rate 0.7 L/min
Orifice 1.2mm

1/8" BSPP

0366	Voltage
K2WH012-06-230AC	230/50V AC
K2WH012-06-110AC	110/50V AC
K2WH012-06-24AC	24/50V AC
K2WH012-06-24DC	24V DC
K2WH012-06-12DC	12V DC
Tech Sheet 10163	

Flow Rate 0.7 L/min
Orifice 1.2mm

1/4" BSPP

0366	Voltage
K2WH012-08-230AC	230/50V AC
K2WH012-08-110AC	110/50V AC
K2WH012-08-24AC	24/50V AC
K2WH012-08-24DC	24V DC
K2WH012-08-12DC	12V DC
Tech Sheet 10163	

Flow Rate 1.7 L/min
Orifice 2mm

3/8" BSPP

0366	Voltage
K2WH020-10-230AC	230/50V AC
K2WH020-10-110AC	110/50V AC
K2WH020-10-24AC	24/50V AC
K2WH020-10-24DC	24V DC
K2WH020-10-12DC	12V DC
Tech Sheet 10163	

Coils to suit K2W Direct Acting Valves



Coil & Plug, Normally Closed to suit 1/8", 1/4" BSPP

0366	Voltage
K2W-08-230/50AC	230/50V AC
K2W-08-110/50AC	110/50V AC
K2W-08-24/50AC	24/50V AC
K2W-08-24DC	24V DC
K2W-08-12DC	12V DC
Tech Sheet 10163	

Coil & Plug, Normally Closed to suit 3/8" BSPP

0366	Voltage
K2W-040-230/50AC	230/50V AC
K2W-040-110/50AC	110/50V AC
K2W-040-24/50AC	24/50V AC
K2W-040-24DC	24V DC
K2W-040-12DC	12V DC
Tech Sheet 10163	

Fluid-Air Components Ltd

SOLENOID VALVES, 25 SERIES

ZS Series 2/2 Solenoid Valve

- Suitable for use on air, gas, hot water and oil applications
- Normally closed
- Comes complete with solenoid coil and plug
- Direct acting - no minimum pressure
- Rated IP 65



Brass Body NBR Seals, BSPP

0366	Thread	Orifice mm	CV Value	Min pressure	Max Working Pressure Air,	Gas	Water, Hot Water, Liquid		Light Oil		Max Temp C	Power VA AC 220	W DC 24V	Voltage
					AC	DC	AC	DC	AC	DC				
ZS15E2-10L	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	220V AC
ZS15E1-10L	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	110V AC
ZS15E4-10L	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	24V DC
ZS15E7-10L	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	24V AC
ZS20E2	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	220V AC
ZS20E1	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	110V AC
ZS20E4	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	24V DC
ZS20E7	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	24V AC
ZS25E2	G1"	25	12	0	10	6	10	6	7	4	80	33	20	220V AC
ZS25E1-25L	G1"	25	12	0	10	6	10	6	7	4	80	33	20	110V AC
ZS25E4	G1"	25	12	0	10	6	10	6	7	4	80	33	20	24V DC
ZS25E7	G1"	25	12	0	10	6	10	6	7	4	80	33	20	24V AC

ZS Series 2/2 Solenoid Valve

- Suitable for use on air, gas, hot water and oil applications
- Normally closed
- Comes complete with solenoid coil and plug
- Direct acting - no minimum pressure
- Rated IP 65



Stainless Steel Body Viton Seals, BSPP

0366	Thread	Orifice mm	CV Value	Min pressure	Max Working Pressure Air,	Gas	Water, Hot Water, Liquid		Light Oil		Max Temp C	Power VA AC 220	W DC 24V	Voltage
					AC	DC	AC	DC	AC	DC				
ZS15VE2-10LS2	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	220V AC
ZS15VE1-10LS2	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	110V AC
ZS15VE4-10LS2	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	24V DC
ZS15VE7-10LS2	G1/2"	10	1.9	0	20	16	20	16	20	16	80	22	13	24V AC
ZS20VE2S2	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	220V AC
ZS20VE1S2	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	110V AC
ZS20VE4S2	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	24V DC
ZS20VE7S2	G3/4"	20	7.6	0	10	6	10	6	7	4	80	33	20	24V AC
ZS25VE2S2	G1"	25	12	0	10	6	10	6	7	4	80	33	20	220V AC
ZS25VE1S2	G1"	25	12	0	10	6	10	6	7	4	80	33	20	110V AC
ZS25VE4S2	G1"	25	12	0	10	6	10	6	7	4	80	33	20	24V DC
ZS25VE7S2	G1"	25	12	0	10	6	10	6	7	4	80	33	20	24V AC

Fluid-Air Components Ltd

SOLENOID VALVES

stainless steel

Stainless Steel 2/2 N/C, Direct Operated/ Pilot Operated Solenoid Valves

Materials in contact with fluids
Body: Stainless steel AISI 316
Sealing: FPM
Internal Components: Stainless steel
Seat: Stainless steel AISI 316
Core Tube: Stainless steel
Shading Coil: Copper

Supplied with DIN plugs



1/8"-1/4"



3/8"-1"

BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M3/ HR	Max Pressure Bar	Replacement Coil
G256C145S-23050	1/8"	230/50	4.5 VA	1.6	0.08	0-30	533534-003
G256C145S-11050	1/8"	110/50	4.5 VA	1.6	0.08	0-30	533534-024
G256C145S-2450	1/8"	24/50	4.5 VA	1.6	0.08	0-30	533534-011
G256C145S-24VDC	1/8"	24V DC	3.5 W	1.6	0.08	0-12	533534-001
G256C129S-23050	1/4"	230/50	14 VA	2.4	0.18	0-20	533593-003
G256C129S-11050	1/4"	110/50	14 VA	2.4	0.18	0-20	533593-020
G256C129S-2450	1/4"	24/50	14 VA	2.4	0.18	0-20	533593-011
G256C113S-24VDC	1/4"	24V DC	9 W	2.4	0.18	0-20	533593-002
L182V09-38-23050	3/8"	230/50	12VA	13.5	2.5	0.35 - 16	B12AA
L182V09-38-11050	3/8"	110/50	12VA	13.5	2.5	0.35 - 16	B12AC
L182V09-38-2450	3/8"	24/50	12VA	13.5	2.5	0.35 - 16	B12AE
L182V09-38-24	3/8"	24V DC	5.5W	13.5	2.5	0.35 - 16	B12AL
L182V09-12-23050	1/2"	230/50	12VA	13.5	3.8	0.35 - 16	B12AA
L182V09-12-11050	1/2"	110/50	12VA	13.5	3.8	0.35 - 16	B12AC
L182V09-12-2450	1/2"	24/50	12VA	13.5	3.8	0.35 - 16	B12AE
L182V09-12-24	1/2"	24V DC	5.5W	13.5	3.8	0.35 - 16	B12AL
L182V09-34-23050	3/4"	230/50	12VA	18	5	0.3 - 12	B12AA
L182V09-34-11050	3/4"	110/50	12VA	18	5	0.3 - 12	B12AC
L182V09-34-2450	3/4"	24/50	12VA	18	5	0.3 - 12	B12AE
L182V09-34-24	3/4"	24V DC	5.5W	18	5	0.3 - 12	B12AL
L182V09-1-23050	1"	230/50	12VA	24	12	0.3 - 12	B12AA
L182V09-1-11050	1"	110/50	12VA	24	12	0.3 - 12	B12AC
L182V09-1-2450	1"	24/50	12VA	24	12	0.3 - 12	B12AE
L182V09-1-24	1"	24V DC	5.5W	24	12	0.3 - 12	B12AL
Tech Sheets 2121, 2122 & 2123							

Stainless Steel 2/2 N/O, Pilot Operated Solenoid Valves

Materials in contact with fluids
Body: Stainless steel AISI 316
Sealing: FPM
Internal Components: Stainless steel
Seat: Stainless steel AISI 316
Core Tube: Stainless steel
Shading Coil: Copper

Supplied with DIN plugs



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M3/ HR	Max Pressure Bar	Replacement Coil
L282V09-38-23050	3/8"	230/50	12VA	13.5	2.5	0.3 - 12	B12AA
L282V09-38-11050	3/8"	110/50	12VA	13.5	2.5	0.3 - 12	B12AC
L282V09-38-2450	3/8"	24/50	12VA	13.5	2.5	0.3 - 12	B12AE
L282V09-38-24	3/8"	24V DC	5.5W	13.5	2.5	0.3 - 12	B12AL
L282V09-12-23050	1/2"	230/50	12VA	13.5	3.8	0.3 - 12	B12AA
L282V09-12-11050	1/2"	110/50	12VA	13.5	3.8	0.3 - 12	B12AC
L282V09-12-2450	1/2"	24/50	12VA	13.5	3.8	0.3 - 12	B12AE
L282V09-12-24	1/2"	24V DC	5.5W	13.5	3.8	0.3 - 12	B12AL
L282V09-34-23050	3/4"	230/50	12VA	18	5	0.3 - 10	B12AA
L282V09-34-11050	3/4"	110/50	12VA	18	5	0.3 - 10	B12AC
L282V09-34-2450	3/4"	24/50	12VA	18	5	0.3 - 10	B12AE
L282V09-34-24	3/4"	24V DC	5.5W	18	5	0.3 - 10	B12AL
L282V09-1-23050	1"	230/50	12VA	24	12	0.3 - 10	B12AA
L282V09-1-11050	1"	110/50	12VA	24	12	0.3 - 10	B12AC
L282V09-1-2450	1"	24/50	12VA	24	12	0.3 - 10	B12AE
L282V09-1-24	1"	24V DC	5.5W	24	12	0.3 - 10	B12AL
Tech Sheet 2154							

Coil reference for G256 series



BSPP

0030	Voltage
533534-003	230/50
533534-024	110/50
533534-011	24/50
533534-001	24V DC
533593-003	230/50
533593-020	110/50
533593-011	24/50
553534-002	24V DC
Tech Sheet 2154	

Fluid-Air Components Ltd

SOLENOID VALVES

General Purpose 2/2 N/C, Pilot Operated Solenoid Valves



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/ HR	Max Pressure Bar	Replacement Coil
L182D01-38-230	3/8"	230/50	6 VA	13.5	2.5	0.35 - 16	B10AA
L182D01-38-110	3/8"	110/50	6 VA	13.5	2.5	0.35 - 16	B10AC
L182D01-38-2450	3/8"	24/50	6 VA	13.5	2.5	0.35 - 16	B10AE
L182D01-38-24	3/8"	24V DC	5.5 W	13.5	2.5	0.35 - 16	B10AL
L182D01-12-230	1/2"	230/50	6 VA	13.5	3.8	0.35 - 16	B10AA
L182D01-12-110	1/2"	110/50	6 VA	13.5	3.8	0.35 - 16	B10AC
L182D01-12-2450	1/2"	24/50	6 VA	13.5	3.8	0.35 - 16	B10AE
L182D01-12-24	1/2"	24V DC	5.5 W	13.5	3.8	0.35 - 16	B10AL
L182D01-34-230	3/4"	230/50	6 VA	18	5	0.35 - 12	B10AA
L182D01-34-110	3/4"	110/50	6 VA	18	5	0.35 - 12	B10AC
L182D01-34-2450	3/4"	24/50	6 VA	18	5	0.35 - 12	B10AE
L182D01-34-24	3/4"	24V DC	5.5 W	18	5	0.35 - 12	B10AL
L182D01-1-230	1"	230/50	6 VA	24	12	0.35 - 12	B10AA
L182D01-1-110	1"	110/50	6 VA	24	12	0.35 - 12	B10AC
L182D01-1-2450	1"	24/50	6 VA	24	12	0.35 - 12	B10AE
L182D01-1-24	1"	24V DC	5.5 W	24	12	0.35 - 12	B10AL
L182D48-114-230	1.1/4"	230/50	14 VA	30	15	0.5-10	A10AA
L182D48-114-110	1.1/4"	110/50	14 VA	30	15	0.5-10	A10AC
L182D48-114-2450	1.1/4"	24/50	14 VA	30	15	0.5-10	A10AE
L182D48-114-24	1.1/4"	24V DC	9 W	30	15	0.5-10	A10AL
L182D48-112-230	1.1/2"	230/50	14 VA	45	27	0.5-10	A10AA
L182D48-112-110	1.1/2"	110/50	14 VA	45	27	0.5-10	A10AC
L182D48-112-2450	1.1/2"	24/50	14 VA	45	27	0.5-10	A10AE
L182D48-112-24	1.1/2"	24V DC	9 W	45	27	0.5-10	A10AL
L182D48-2-230	2"	230/50	14 VA	45	34	0.5-10	A10AA
L182D48-2-110	2"	110/50	15 VA	45	34	0.5-10	A10AC
L182D48-2-2450	2"	24/50	16 VA	45	34	0.5-10	A10AE
L182D48-2-24	2"	24V DC	9 W	45	34	0.5-10	A10AL

Tech Sheet 1977

General Purpose 2/2 N/O, Pilot Operated Solenoid Valves

3/8"-2" WRAS Approved. EPDM Seal



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/ HR	Max Pressure Bar	Replacement Coil
L282D01-38-230	3/8"	230/50	6 VA	13.5	2.5	0.35-12	B10AA
L282D01-38-110	3/8"	110/50	6 VA	13.5	2.5	0.35-12	B10AC
L282D01-38-2450	3/8"	24/50	6 VA	13.5	2.5	0.35-12	B10AE
L282D01-38-24	3/8"	24V DC	5.5 W	13.5	2.5	0.35-12	C10AL
L282D01-12-230	1/2"	230/50	6 VA	13.5	3.8	0.35-12	B10AA
L282D01-12-110	1/2"	110/50	6 VA	13.5	3.8	0.35-12	B10AC
L282D01-12-2450	1/2"	24/50	6 VA	13.5	3.8	0.35-12	B10AE
L282D01-12-24	1/2"	24V DC	5.5 W	13.5	3.8	0.35-12	C10AL
L282D01-34-230	3/4"	230/50	6 VA	18	5	0.35-10	B10AA
L282D01-34-110	3/4"	110/50	6 VA	18	5	0.35-10	B10AC
L282D01-34-2450	3/4"	24/50	6 VA	18	5	0.35-10	B10AE
L282D01-34-24	3/4"	24V DC	5.5 W	18	5	0.35-10	C10AL
L282D01-1-230	1"	230/50	6 VA	24	12	0.35-10	B10AA
L282D01-1-110	1"	110/50	6 VA	24	12	0.35-10	B10AC
L282D01-1-2450	1"	24/50	6 VA	24	12	0.35-10	B10AE
L282D01-1-24	1"	24V DC	5.5 W	24	12	0.35-10	C10AL
L282D48-114-230	1.1/4"	230/50	14 VA	30	15	0.5-10	A10AA
L282D48-114-110	1.1/4"	110/50	14 VA	30	15	0.5-10	A10AC
L282D48-114-2450	1.1/4"	24/50	14 VA	30	15	0.5-10	A10AE
L282D48-114-24	1.1/4"	24V DC	9 W	30	15	0.5-10	A10AL
L282D01-112-230	1.1/2"	230/50	14 VA	45	27	0.5-10	A10AA
L282D01-112-110	1.1/2"	110/50	14 VA	45	27	0.5-10	A10AC
L282D01-112-2450	1.1/2"	24/50	14 VA	45	27	0.5-10	A10AE
L282D01-112-24	1.1/2"	24V DC	9 W	45	27	0.5-10	A10AL
L282D01-2-230	2"	230/50	14 VA	45	34	0.5-10	A10AA
L282D01-2-110	2"	110/50	14 VA	45	34	0.5-10	A10AC
L282D01-2-2450	2"	24/50	14 VA	45	34	0.5-10	A10AE
L282D01-2-24	2"	24V DC	9 W	45	34	0.5-10	A10AL

Tech Sheet 1978

FT PRO

For **Reinforced PVC Braided Hose Type RPVC (to BS6066)**
see pages **1402-1406**



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SOLENOID VALVES

Direct Operated & Pilot Operated (zero rated) Solenoid Valves

1/8"-1/4"



3/8"-1"





BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/HR	Max Pressure Bar	Replacement Coil
G256C136S-23050	1/8"	230/50	4.5 VA	2	0.12	0-15	533534-003
G256C136S-11050	1/8"	110/50	4.5 VA	2	0.12	0-15	533534-024
G256C136S-2450	1/8"	24/50	4.5 VA	2	0.12	0-15	533534-011
G256C136S-24	1/8"	24V DC	3.5 W	2	0.12	0-6	533534-001
G256121S-23050	1/4"	230/50	14 VA	2.4	0.18	0-20	533593-003
G256C121S-11050	1/4"	110/50	14 VA	2.4	0.18	0-20	533593-020
G256C121S-2450	1/4"	24/50	14 VA	2.4	0.18	0-20	533593-011
G256C121S-24	1/4"	24V DC	9W	2.4	0.18	0-20	533593-002
L133B16-38-230	3/8"	230/50	14 VA	12.5	2	0-10	530AA
L133B16-38-110	3/8"	110/50	14 VA	12.5	2	0-10	530AC
L133B16-38-2450	3/8"	24/50	14 VA	12.5	2	0-10	530AE
L133B16-38-24	3/8"	24V DC	9W	12.5	2	0-3	530AL
L133B16-12-230	1/2"	230/50	24 VA	12.5	2.2	0-10	130AA
L133B16-12-110	1/2"	110/50	24 VA	12.5	2.2	0-10	130AC
L133B16-12-2450	1/2"	24/50	24 VA	12.5	2.2	0-10	130AE
L133B16-12-24	1/2"	24V DC	13W	12.5	2.2	0-3	130AL
L133B07-34-230	3/4"	230/50	24VA	17	4.5	0-10	130AA
L133B07-34-110	3/4"	110/50	24VA	17	4.5	0-10	130AC
L133B07-34-2450	3/4"	24/50	24VA	17	4.5	0-10	130AE
L133B07-34-24	3/4"	24V DC	13W	17	4.5	0-3	130AL
L133B06-1-230	1"	230/50	33VA	24	9	0-10	923EA
L133B06-1-110	1"	110/50	33VA	24	9	0-10	923EC
L133B06-1-2450	1"	24/50	33VA	24	9	0-10	923EE
L133B06-1-24	1"	24V DC	17W	24	9	0-3	923AL
Tech Sheets 870, 871 & 863							

Steam & Hot Water 2/2 N/C, Pilot Operated Solenoid Valves



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/HR	Max Pressure Bar	Replacement Coil
L145R2-12-230	1/2"	230/50	10VA	10	2.5	0.4-8	614AA
L145R2-12-110	1/2"	110/50	10VA	10	2.5	0.4-8	614AC
L145R2-12-24	1/2"	24V AC	10VA	10	2.5	0.4-8	614AE
L145R4-34-230	3/4"	230/50	14VA	16	4.5	0.4-6	534AA
L145R4-34-110	3/4"	110/50	14VA	16	4.5	0.4-6	534AC
L145R2-1-230	1"	230/50	14VA	18.5	18.5	0.4-6	534AA
L145R2-1-110	1"	110/50	14VA	18.5	18.5	0.4-6	534AC
Tech Sheet 864							

General Purpose 3/2 N/C, Direct Acting Solenoid Valves



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/HR	Max Pressure Bar	Replacement Coil
G356C136S-23050	1/8"	230/50	4.5 VA	1.6	0.08	0-10	533534-003
G356C136S-11050	1/8"	110/50	4.5 VA	1.6	0.08	0-10	533534-024
G356C136S-2450	1/8"	24/50	4.5 VA	1.6	0.08	0-10	533534-011
G356C136S-24	1/8"	24V DC	5W	1.6	0.08	0-10	533534-002
L321B02C-14-230	1/4"	230/50	14VA	2.3	0.14	0-8	230
L321B02C-14-110	1/4"	110/50	14VA	2.3	0.14	0-8	110
L321B02C-14-2450	1/4"	24/50	14VA	2.3	0.14	0-8	2450
L321B02C-14-24	1/4"	24V DC	9W	2.3	0.14	0-8	24DC
Tech Sheets 868 & 869							

FAC Fluid-Air Components Ltd

SOLENOID VALVES

Pilot Operated (zero rated) Solenoid Valves



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M³/ HR	Max Pressure Bar	Replacement Coil
L153D07-12-230*	1/2"	230/50	12VA	11.5	2.1	0-8	134AA
L153D07-12-110*	1/2"	110/50	12VA	11.5	2.1	0-8	134AC
L153D07-12-24*	1/2"	24V AC	12VA	11.5	2.1	0-8	134AE
L153D07-34-230	3/4"	230/50	12VA	17	5	0-8	134AA
L153D07-34-110	3/4"	110/50	12VA	17	5	0-8	134AC
L153D07-34-24	3/4"	24V AC	12VA	17	5	0-8	134AE
L153D5-1-230	1"	230/50	27VA	22	8.5	0-8	923EA
L153D5-1-110	1"	110/50	27VA	22	8.5	0-8	923EC
L153D5-1-24	1"	24V AC	27VA	22	8.5	0-8	923AL
Tech Sheet 865							

** Please Note 0-6 Bar Hot Water.*

DIN Plug



To suit Sirai Valves

0030	To Suit
122	122 Coil
182	182 Coil

Replacement Coils



To suit Sirai Valves

0030	Voltage	Plug
823AA	230/50	122
823AC	110/50	122
823AL	24V DC	122
830AE	24/50	122
A10AA	230/50	182
A10AC	110/50	182
A10AE	24/50	182
A10AL	24V DC	182
B10AA	230/50	122
B10AC	110/50	122
B10AE	24/50	122
B10AL	24V DC	122
530AA	230/50	182
530AC	110/50	182
530AL	24V DC	182
130AA	230/50	182
130AC	110/50	182
130AE	24/50	182
130AL	24V DC	182
923EA	230/50	182
923EC	110/50	182
923EE	24/50	182
923AL	24V DC	182
614AA	230/50	122
614AC	110/50	122
614AE	24V AC	122
534AA	230/50	182
534AC	110/50	182
534AE	24V AC	182
134AA	230/50	182
134AC	110/50	182
134AE	24V AC	182
934AA	230/50	182
934AC	110/50	182
934AE	24V AC	182
610AA	230/50	122
610AC	110/50	122
610AE	24/50	122
610AL	24V DC	122

Fluid-Air Components Ltd

SOLENOID VALVES

FESTO


VZWF 2/2 Way Normally Closed Solenoid Valves

Features:
- Available in brass or stainless steel body
- BSPP threads
- NBR seals
- Stainless steel tube and internals
- Suitable for applications such as water, inert gases, compressed air systems and neutral liquids.
  Also suitable for vacuum with Pabs > 100 mbar
- 22 centistokes maximum viscosity
- IP65 rating

Working Temperature:
-10°C to +80°C

Ambient Temperature:
-10°C to +35°C

Maximum Working Pressure:
10 bar: 1/4" to 1/2"
6 bar: 3/4" upwards



Brass

0990	Size	Festo Type Code	Voltage
1492110	1/4"	VZWF-B-L-M22C-G14-135-1P4-10	24V DC
1492206	1/4"	VZWF-B-L-M22C-G14-135-2AP4-10	110V AC
1492302	1/4"	VZWF-B-L-M22C-G14-135-3AP4-10	230V AC
1492111	3/8"	VZWF-B-L-M22C-G38-135-1P4-10	24V DC
1492207	3/8"	VZWF-B-L-M22C-G38-135-2AP4-10	110V AC
1492303	3/8"	VZWF-B-L-M22C-G38-135-3AP4-10	230V AC
1492112	1/2"	VZWF-B-L-M22C-G12-135-1P4-10	24V DC
1492208	1/2"	VZWF-B-L-M22C-G12-135-2AP4-10	110V AC
1492304	1/2"	VZWF-B-L-M22C-G12-135-3AP4-10	230V AC
1492113	3/4"	VZWF-B-L-M22C-G34-275-1P4-6	24V DC
1492209	3/4"	VZWF-B-L-M22C-G34-275-2AP4-6	110V AC
1492305	3/4"	VZWF-B-L-M22C-G34-275-3AP4-6	230V AC
1492114	1"	VZWF-B-L-M22C-G1-275-1P4-6	24V DC
1492210	1"	VZWF-B-L-M22C-G1-275-2AP4-6	110V AC
1492306	1"	VZWF-B-L-M22C-G1-275-3AP4-6	230V AC
Tech Sheet 6264			

Stainless Steel

0990	Size	Festo Type Code	Voltage
1492118	1/4"	VZWF-B-L-M22C-G14-135-1P4-10-R1	24V DC
1492214	1/4"	VZWF-B-L-M22C-G14-135-2AP4-10-R1	110V AC
1492310	1/4"	VZWF-B-L-M22C-G14-135-3AP4-10-R1	230V AC
1492119	3/8"	VZWF-B-L-M22C-G38-135-1P4-10-R1	24V DC
1492215	3/8"	VZWF-B-L-M22C-G38-135-2AP4-10-R1	110V AC
1492311	3/8"	VZWF-B-L-M22C-G38-135-3AP4-10-R1	230V AC
1492120	1/2"	VZWF-B-L-M22C-G12-135-1P4-10-R1	24V DC
1492216	1/2"	VZWF-B-L-M22C-G12-135-2AP4-10-R1	110V AC
1492312	1/2"	VZWF-B-L-M22C-G12-135-3AP4-10-R1	230V AC
1492121	3/4"	VZWF-B-L-M22C-G34-275-1P4-6-R1	24V DC
1492217	3/4"	VZWF-B-L-M22C-G34-275-2AP4-6-R1	110V AC
1492313	3/4"	VZWF-B-L-M22C-G34-275-3AP4-6-R1	230V AC
1492122	1"	VZWF-B-L-M22C-G1-275-1P4-6-R1	24V DC
1492218	1"	VZWF-B-L-M22C-G1-275-2AP4-6-R1	110V AC
1492314	1"	VZWF-B-L-M22C-G1-275-3AP4-6-R1	230V AC
Tech Sheet 6264			


VZWM 2/2 Way Normally Closed Solenoid Valves

Features:
- Available in brass or stainless steel body
- BSPP threads
- NBR seals
- Steel tube and internals
- Suitable for applications such as water, inert gases, compressed air systems and neutral liquids
- 22 centistokes maximum viscosity
- IP65 rating with a DIN connector fitte
- For a complete diaphragm opening, a minimum pressure of 0.5 bar is required for sizes 1/4" to 1" and 0.7 bar for sizes 1.1/4" upwards

Working Temperature:
-10°C to +60°C

Ambient Temperature:
-10°C to +60°C

Maximum Working Pressure:
10 bar (gases)
6 bar (liquids)



Brass

0990	Size	Festo Type Code	Solenoid Coil Size
546146	1/4"	VZWM-L-M22C-G14-F4	F4
546147	3/8"	VZWM-L-M22C-G38-F4	F4
546148	1/2"	VZWM-L-M22C-G12-F4	F4
546149	3/4"	VZWM-L-M22C-G34-F4	F4
546150	1"	VZWM-L-M22C-G1-F4	F4
546151	1.1/4"	VZWM-L-M22C-G114-F5	F5
546152	1.1/2"	VZWM-L-M22C-G112-F5	F5
546153	2"	VZWM-L-M22C-G2-F5	F5
Tech Sheet 6265			

Stainless Steel

0990	Size	Festo Type Code	Solenoid Coil Size
546162	1/4"	VZWM-L-M22C-G14-F5-R1	F5
546163	3/8"	VZWM-L-M22C-G38-F5-R1	F5
546164	1/2"	VZWM-L-M22C-G12-F5-R1	F5
546165	3/4"	VZWM-L-M22C-G34-F5-R1	F5
546166	1"	VZWM-L-M22C-G1-F5-R1	F5
546167	1.1/4"	VZWM-L-M22C-G114-F5-R1	F5
546168	1.1/2"	VZWM-L-M22C-G112-F5-R1	F5
546169	2"	VZWM-L-M22C-G2-F5-R1	F5
Tech Sheet 6265			

Fluid-Air Components Ltd

SOLENOID VALVES

FESTO

Solenoid Valves

Features:
- Electricial connection according to DIN EN 175301-803 Form A
- Any mounting position
- IP65 rating
- 100% duty rating



Features:
- Electricial connection according to DIN EN 175301-803 Form A
- Reinforced PA housing
- IP65 rating




Solenoid Coil

0990	Size	Festo Type Code	Voltage
549903	F4	MD-2-24VDC-PA	24V DC
549904	F4	MD-2-110VAC-PA	110V AC
549905	F4	MD-2-230VAC-PA	230V AC
549906	F5	MH-2-24VDC-PA	24V DC
549907	F5	MH-2-110VAC-PA	110V AC
549908	F5	MH-2-230VAC-PA	230V AC
Tech Sheet 6266			

DIN Plug

0990	Size	Festo Type Code
550067	1/4" to 2"	MSSD-N
Tech Sheet 6267		

FESTO



You might also need...
Festo Male Studs
...see page **808**

Require technical support with Festo products?...
Contact our technical sales team and they will be happy to assist you.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SOLENOID VALVES

stainless steel

Parker's 2 way and 3 way, normally closed and normally open, solenoid valves are used in a wide variety of applications, with or without pressure differential. Ideal for air, liquids and gases, these valves are available with a brass or stainless steel body with a range of sealing materials offering vast chemical compatibilities.

Applications:

- Compressors
- Water dispensing and purificatio
- Cooling systems
- Sterilisers
- Analysers and diagnostic equipment
- Medical and dental devices
- Welding equipment
- Lubrication equipment
- Beverage dispensing and vending machines
- Oil burners
- Humidification and misting equipment
- Mobile equipment
- Textile and dry cleaning machines
- Irrigation

Solenoid Valves, Stainless Steel 316L

Working Temperature:
-10°C to +140°C

Please see technical data sheet for working pressures



2/2 Way, Normally Closed, Viton Seal, BSPP

0484	Thread	Orifice mm	Voltage	Manufacturer's Code
550000DIS	1/8"	1.5	24V DC	550000DIS
550001DIS	1/8"	1.5	230V AC	550001DIS
550002DIS	1/4"	1.5	24V DC	550002DIS
550003DIS	1/4"	1.5	230V AC	550003DIS
550004DIS	1/4"	2.5	24V DC	550004DIS
550005DIS	1/4"	2.5	230V AC	550005DIS
550009DIS	3/8"	5	230V AC	550009DIS
550010DIS	1/2"	5	24V DC	550010DIS
550011DIS	1/2"	5	230V AC	550011DIS
		Tech Sheet 60420		

Maximum Working Pressure
6 bar

2/2 Way, Normally Open, Viton Seal, BSPP

0484	Thread	Orifice mm	Voltage	Manufacturer's Code
550013DIS	1/4"	3	230V AC	550013DIS
		Tech Sheet 60421		

Maximum Working Pressure
8 bar

3/2 Way, Normally Closed, Viton Seal, BSPP

0484	Thread	Orifice mm	Voltage	Manufacturer's Code
550014DIS	1/8"	1.5	24V DC	550014DIS
550015DIS	1/8"	1.5	230V AC	550015DIS
550016DIS	1/4"	1.5	24V DC	550016DIS
550017DIS	1/4"	1.5	230V AC	550017DIS
		Tech Sheet 60421		

2/2 Way Solenoid Valves, Direct Lift, Stainless Steel

Maximum Working Temperature:
+100°C

Maximum Working Pressure
16 bar = AC
6 bar = DC



Normally Closed, Viton Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
221G6306-230AC	3/8"	230V AC	221G6306-2995-4818653D
221G6506-230AC	1/2"	230V AC	221G6506-2995-4818653D
221G6536-24DC	1/2"	24V DC	221G6536-2995-492425C2
221G6606-230AC	3/4"	230V AC	221G6606-2995-4818653D
221G6106-230AC	1"	230V AC	221G6106-2995-4818653D
221G6136-24DC	1"	24V DC	221G6136-2995-492425C2
		Tech Sheet 60440	

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SOLENOID VALVES

Parker's 2 way and 3 way, normally closed and normally open, solenoid valves are used in a wide variety of applications, with or without pressure differential. Ideal for air, liquids and gases, these valves are available with a brass or stainless steel body with a range of sealing materials offering vast chemical compatibilities.

Applications:

- Compressors
- Water dispensing and purificatio
- Cooling systems
- Sterilisers
- Analysers and diagnostic equipment
- Medical and dental devices
- Welding equipment
- Lubrication equipment
- Beverage dispensing and vending machines
- Oil burners
- Humidification and misting equipment
- Mobile equipment
- Textile and dry cleaning machines
- Irrigation

2/2 Way Solenoid Valves, Brass, Compact Design

Working Temperature: -10°C to +140°C

Maximum Working Pressure: 10 bar = AC, 7 bar = DC



Normally Closed, Viton Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
321K3106-230AC	1/4"	230V AC	321K3106-8993-4889803D
321K3106-24DC	1/4"	24V DC	321K3106-8993-488980C2
321K3306-230AC	3/8"	230V AC	321K3306-8993-4889803D
321K3306-24DC	3/8"	24V DC	321K3306-8993-488980C2
321K3506-230AC	1/2"	230V AC	321K3506-8993-4889803D
321K3506-24DC	1/2"	24V DC	321K3506-8993-488980C2
321K3606-230AC	3/4"	230V AC	321K3606-8993-4889803D
321K3606-24DC	3/4"	24V DC	321K3606-8993-488980C2
321K3706-230AC	1"	230V AC	321K3706-8993-4889803D
321K3706-24DC	1"	24V DC	321K3706-8993-488980C2
Tech Sheet 60417			

Working Temperature: -10°C to +100°C

Maximum Working Pressure: 12 bar



Normally Open, Viton Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
322K4106-24DC	1/4"	24V DC	322K4106-2995-481865C2
322K4506-230AC	1/2"	230V AC	322K4506-2995-4818653D
322K4506-24DC	1/2"	24V DC	322K4506-2995-481865C2
322K4606-230AC	3/4"	230V AC	322K4606-2995-4818653D
322K4606-24DC	3/4"	24V DC	322K4606-2995-481865C2
Tech Sheet 60418			

2/2 Way Solenoid Valves, Brass, Direct Lift

Working Temperature: -10°C to +100°C

Maximum Working Pressure 16 bar = AC, 10 bar = DC



Normally Closed, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
221G13-230AC	3/8"	230V AC	221G13-2995-4818653D
221G13-24DC	3/8"	24V DC	221G13-2995-492425C2
221G1530-24DC	1/2"	24V DC	221G1530-2995-481865C2
221G16-230AC	3/4"	230V AC	221G16-2995-4818653D
221G16-24DC	3/4"	24V DC	221G16-2995-492425C2
221G17-24DC	1"	24V DC	221G17-2995-492425C2
Tech Sheet 60416			

Normally Closed, Large Flow, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
221G21-230AC	1"	230V AC	221G21-2995-4818653D
221G2130-24DC	1"	24V DC	221G2130-2995-481865C2
Tech Sheet 60416			

3/2 Way Solenoid Valve, Aluminium Banjo Design

Working Temperature: -10°C to +50°C

Maximum Working Pressure 10 bar



Normally Closed, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
131B14-24DC	1/8"	24V DC	131B14-496131C2
131B14-230AC	1/8"	230V AC	131B14-496131P9
131B04-24DC	1/4"	24V DC	131B04-496131C2
131B04-230AC	1/4"	230V AC	131B04-496131P9
Tech Sheet 60415			

Fluid-Air Components Ltd

SOLENOID VALVES

Parker's 2 way, normally closed and normally open, solenoid valves are used in a wide variety of applications, with or without pressure differential. Ideal for air, liquids and gases, these valves are available with a brass or stainless steel body with a range of sealing materials offering vast chemical compatibilities.

Applications:

- Compressors
- Water dispensing and purificatio
- Cooling systems
- Sterilisers
- Analysers and diagnostic equipment
- Medical and dental devices
- Welding equipment
- Lubrication equipment
- Beverage dispensing and vending machines
- Oil burners
- Humidification and misting equipmen
- Mobile equipment
- Textile and dry cleaning machines
- Irrigation



2/2 Way Solenoid Valves, Brass, Hot Water & Liquids

Working Temperature:
-10°C to +140°C (3/8" to 1")
-10°C to +50°C (1.1/4" to 2")

Maximum Working Pressure:
10 bar

Normally Closed, EPDM Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
550036DIS	3/8"	24V DC	550036DIS
550037DIS	3/8"	230V AC	550037DIS
550026DIS	3/4"	24V DC	550026DIS
550029DIS	1"	230V AC	550029DIS
550218DIS	2"	230V AC	550218DIS
Tech Sheet 60423			

2/2 Way Solenoid Valves, Brass, Hot Water & Liquids

Working Temperature:
-10°C to +90°C

Maximum Working Pressure:
20 bar (3/8" to 1/2")
10 bar (3/4" to 3")

Normally Closed, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
550039DIS	3/8"	230V AC	550039DIS
550198DIS	3/4"	230V AC	550198DIS
550030DIS	1"	24V DC	550030DIS
550031DIS	1"	230V AC	550031DIS
550033DIS	1.1/4"	230V AC	550033DIS
550034DIS	1.1/2"	24V DC	550034DIS
550035DIS	1.1/2"	230V AC	550035DIS
Tech Sheet 60424			

2/2 Way Solenoid Valves, Brass, Hot Water & Liquids

Working Temperature:
-10°C to +90°C

Maximum Working Pressure:
20 bar (3/8" to 1")
10 bar (1.1/2" to 2")

Normally Open, Nitrile Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
550057DIS	3/8"	230V AC	550057DIS
550046DIS	1/2"	24V DC	550046DIS
550047DIS	1/2"	230V AC	550047DIS
550049DIS	3/4"	230V AC	550049DIS
550050DIS	1"	24V DC	550050DIS
550051DIS	1"	230V AC	550051DIS
550052DIS	1.1/2"	24V DC	550052DIS
Tech Sheet 60425			

2/2 Way Solenoid Valves, Brass, Steam & Hot Water

Working Temperature:
-30°C to +180°C

Maximum Working Pressure:
10 bar

Normally Closed, PTFE Seal, BSPP

0484	Thread	Voltage	Manufacturer's Code
550072DIS	1/2"	230V AC	550072DIS
550076DIS	1"	230V AC	550076DIS
Tech Sheet 60426			

Fluid-Air Components Ltd

SOLENOID VALVES

General Purpose 2/2 N/C Pilot Operated Solenoid Valves



Media: Water, oil and air
Seal: Nitrile
Speed Control Screw: Standard on 1.1/2" and 2"
Body: Brass
Protection Class: IP65 (with connector fitted)

Working Temperature:
-10°C to +90°C

BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
F180-38-230	3/8"	230/50	10VA	13	55	0.3-16	2700
F180-38-110	3/8"	110/50	10VA	13	55	0.3-16	2400
F180-38-24	3/8"	24DC	7W	13	55	0.3-16	2250
F180-12-230	1/2"	230/50	10VA	13	63	0.3-16	2700
F180-12-110	1/2"	110/50	10VA	13	63	0.3-16	2400
F180-12-24	1/2"	24DC	7W	13	63	0.3-16	2250
F180-34-230	3/4"	230/50	10VA	21	90	0.3-16	2700
F180-34-110	3/4"	110/50	10VA	21	90	0.3-16	2400
F180-34-24	3/4"	24DC	7W	21	90	0.3-16	2250
F180-1-230	1"	230/50	10VA	25	216	0.3-16	2700
F180-1-110	1"	110/50	10VA	25	216	0.3-16	2400
F180-1-24	1"	24DC	7W	25	216	0.3-16	2250
F180-112-230	1.1/2"	230/50	18VA	40	400	0.5-16	7700
F180-112-110	1.1/2"	110/50	18VA	40	400	0.5-16	7400
F180-112-24	1.1/2"	24DC	14W	40	400	0.5-16	7250
F180-2-230	2"	230/50	18VA	50	540	0.5-16	7700
F180-2-110	2"	110/50	18VA	50	540	0.5-16	7400
F180-2-24	2"	24DC	14W	50	540	0.5-16	7250
Tech Sheet 10376							

General Purpose 2/2 N/C Direct Acting Solenoid Valves



Media: Water, oil and air
Seal: FKM
Body: Brass
Protection Class: IP65 (with connector fitted)

Working Temperature:
-10°C to +120°C

BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
F133-18-230	1/8"	230/50	10VA	2	1.9	0-12	2700
F133-18-110	1/8"	110/50	10VA	2	1.9	0-12	2400
F133-18-24	1/8"	24DC	7W	2	1.9	0-9	2250
F133-14-230	1/4"	230/50	18VA	3	4.5	0-15	7700
F133-14-110	1/4"	110/50	18VA	3	4.5	0-15	7400
F133-14-24	1/4"	24DC	14W	3	4.5	0-8	7250
F133-38-230	3/8"	230/50	18VA	4	6	0-8	7700
F133-38-110	3/8"	110/50	18VA	4	6	0-8	7400
F133-38-24	3/8"	24DC	14W	4	6	0-5	7250
Tech Sheet 10374							

General Purpose 2/2 N/O Pilot Operated Solenoid Valves



Media: Water, oil and air
Seal: Nitrile
Speed Control Screw: Standard on 1.1/2" and 2"
Body: Brass
Protection Class: IP65 (with connector fitted)

Working Temperature:
-10°C to +90°C

BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
F280-38-230	3/8"	230/50	10VA	13	55	0.3-16	2700
F280-38-110	3/8"	110/50	10VA	13	55	0.3-16	2400
F280-38-24	3/8"	24DC	7W	13	55	0.3-16	2250
F280-12-230	1/2"	230/50	10VA	13	63	0.3-16	2700
F280-12-110	1/2"	110/50	10VA	13	63	0.3-16	2400
F280-12-24	1/2"	24DC	7W	13	63	0.3-16	2250
F280-34-230	3/4"	230/50	10VA	21	100	0.3-16	2700
F280-34-110	3/4"	110/50	10VA	21	100	0.3-16	2400
F280-34-24	3/4"	24DC	7W	21	100	0.3-16	2250
F280-1-230	1"	230/50	10VA	21	160	0.3-16	2700
F280-1-110	1"	110/50	10VA	21	160	0.3-16	2400
F280-1-24	1"	24DC	7W	21	160	0.3-16	2250
F280-112-230	1.1/2"	230/50	18VA	40	480	0.5-16	7700
F280-112-24	1.1/2"	24DC	14W	40	480	0.5-16	7250
F280-2-230	2"	230/50	18VA	50	600	0.5-16	7700
F280-2-110	2"	110/50	18VA	50	600	0.5-16	7400
F280-2-24	2"	24DC	14W	50	600	0.5-16	7250
Tech Sheet 10377							

Fluid-Air Components Ltd

SOLENOID VALVES

Stainless Steel 2/2 N/C Direct Acting Solenoid Valves

Media: Aggressive media
Seal: FKM
Body: Stainless steel
Protection Class: IP65
(with connector fitted

Working Temperature:
-10°C to +130°C

stainless steel



BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
FSS-18-24	1/8"	24DC	14W	3	4.5	0-8	7250
FSS-14-230	1/4"	230/50	18VA	3	4.5	0-15	7700
FSS-14-110	1/4"	110/50	18VA	3	4.5	0-15	7400
FSS-14-24	1/4"	24DC	14W	3	4.5	0-8	7250
Tech Sheet 10380							

General Purpose 3/2 N/C Direct Acting Solenoid Valves

Media: Water, oil and air
Seal: FKM
Body: Brass
Protection Class: IP65
(with connector fitted

Working Temperature:
-10°C to +130°C



BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
F333-18-230	1/8"	230/50	18VA	2	2.2	0-10	7700
F333-18-110	1/8"	110/50	18VA	2	2.2	0-10	7400
F333-18-24	1/8"	24DC	14W	2	2.2	0-10	7250
F333-14-230	1/4"	230/50	18VA	2	2.2	0-10	7700
F333-14-110	1/4"	110/50	18VA	2	2.2	0-10	7400
F333-14-24	1/4"	24DC	14W	2	2.2	0-10	7250
Tech Sheet 10251							

2/2 Way Pilot Operated Valve with Assisted Lift

Media: Water, oil and air
Note:
Other voltages available on request

Working Temperature:
-10°C to +130°C



Compact Version, BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
D884DVU-230/50	1/4"	230/50	18VA	10.5	21	0-16	7700
D884DVU-110/50	1/4"	110/50	18VA	10.5	21	0-16	7400
D885DVU-230/50	3/8"	230/50	18VA	10.5	24	0-16	7700
D885DVU-24	3/8"	24DC	14W	10.5	24	0-4.5	7250
D886DVU-230/50	1/2"	230/50	18VA	10.5	25	0-16	7700
D886DVU-110/50	1/2"	110/50	18VA	10.5	25	0-16	7400
D886DVU-24	1/2"	24DC	14W	10.5	25	0-4.5	7250
Tech Sheet 10379							

Now available with WRAS approval, FKM seals, EPDM seals, stainless steel body and normally open configurations on request



High Flow Version, BSPP

0263	Thread	Voltage	Coil Consumption	DN Size	KV LPM	Max Pressure Bar	Replacement Coil
D288DBW-230/50	3/8"	230/50	18VA	15	60	0-16	7700
D288DBW-110/50	3/8"	110/50	18VA	15	60	0-16	7400
D288DBW-24	3/8"	24DC	14W	15	60	0-6	7250
D289BW-230/50	1/2"	230/50	18VA	15	65	0-16	7700
D289BW-110/50	1/2"	110/50	18VA	15	65	0-16	7400
D289BW-24	1/2"	24DC	14W	15	65	0-6	7250
D290DBW-230/50	3/4"	230/50	18VA	15	80	0-16	7700
D290DBW-110/50	3/4"	110/50	18VA	15	80	0-16	7400
D290DBW-24	3/4"	24DC	14W	15	80	0-6	7250
D293DBY-230/50	1"	230/50	18VA	25	170	0-16	7700
D293DBY-110/50	1"	110/50	18VA	25	170	0-16	7400
D293DBY-24	1"	24DC	14W	25	170	0-6	7250
Tech Sheet 10378							

Fluid-Air Components Ltd

SOLENOID VALVES

Steam 2/2 Way N/C Pilot Operated Solenoid Valves

Ambient Temperature:
-10°C to +70°C
Working Temperature:
-10°C to +180°C



2/2 Way N/C, BSPP

0263	Thread	LPM	Min Pressure Bar	Max Pressure Bar
D634DTT24VAC	1/4"	21	0.3	10
D634DTT110VAC	1/4"	21	0.3	10
D634DTT240VAC	1/4"	21	0.3	10
D635DTT24VAC	3/8"	24	0.3	10
D635DTT110VAC	3/8"	24	0.3	10
D635DTT240VAC	3/8"	24	0.3	10
D636DTT24VAC	1/2"	25	0.3	10
D636DTT110VAC	1/2"	25	0.3	10
D636DTT240VAC	1/2"	25	0.3	10
D606DTY24VAC	3/4"	120	1	10
D606DTY110VAC	3/4"	120	1	10
D606DTY240VAC	3/4"	120	1	10
D622DTY24VAC	1"	120	1	10
D622DTY110VAC	1"	120	1	10
D622DTY240VAC	1"	120	1	10
Tech Sheet 974				

DIN Connectors



Plug to suit F133/F180/F280 (1/8"-1")

0263
2021-7303
Tech Sheet 974

Plug to suit FSS/F153/F180/F280/F333 (1/8"-2")

0263
2021-7329
Tech Sheet 974

DIN Connectors with RED indicating LED



LED Plug to suit F133/F180/F280 (1/8"-1")

0263	Voltage
2027-5384	10V - 50V
2027-5392	70V - 250V
Tech Sheet 974	

LED Plug to suit FSS/F153/F180/ F280/F333 (1/8"-2")

0263	Voltage
2027-5400	10V - 50V
2027-5418	70V - 250V
Tech Sheet 974	

Valve Coils




0263	Voltage
2700	230/50
2400	110/50
2250	24DC
7700	230/50
7400	110/50
7250	24DC
7701	230/50
7401	110/50
7251	24DC
Tech Sheet 974	

Fluid-Air Components Ltd

PRE-WIRED MOULDED SOLENOID LED DIN PLUG CONNECTORS

FT PRO new product

Many experts in the fluid power industry frequently utilise pre-wired DIN connectors to meet their hydraulic, pneumatic, and process valve needs. These connectors were once referred to as DIN 43650 but are now industry standard EN175301-803.



- Thoroughly tested and ready for installation.
- Eliminates assembly errors.
- No manual cutting or wiring is required
- Reduction in labour costs
- Improved product efficiency and reliability.
- Improved IP ratings.
- Protection against ingress and environmental elements.

By opting for pre-assembled connectors, engineers can be assured of time and cost savings. Equipment and machinery can be safeguarded from contamination and environmental hazards. Additionally, the application will benefit from a noticeable improvement in IP ratings, which can elevate your rating from IP65 to IP67. Pre-moulded connectors provide a smart and efficient solution to any application.

The moulded insulated cable is crafted with premium-grade PVC to guarantee optimal performance and safety for all your connectors. Our utmost priority is to offer an unparalleled product that meets and exceeds your expectations.

Incorporating pre-assembled DIN connectors is a proven method for engineers to significantly increase efficiency and reduce costs.

MA6 Series



FORM A – Industrial (18mm Pin Spacing) Moulded Cable

0330	Voltage	Size mm Square	LED+VDR	Cable Length Metres
MA634V54PA05100	24V AC/DC	30	LED + VDR	1
MA634V54PA05300	24V AC/DC	30	LED + VDR	3
MA634V54PA05500	24V AC/DC	30	LED + VDR	5
MA634V55PA05100	115V AC	30	LED + VDR	1
MA634V55PA05300	115V AC	30	LED + VDR	3
MA634V55PA05500	115V AC	30	LED + VDR	5
MA634V56PA05100	230V AC	30	LED + VDR	1
MA634V56PA05300	230V AC	30	LED + VDR	3
MA634V56PA05500	230V AC	30	LED + VDR	5
Tech Sheet 10163				

MB6 Series



FORM B – Industrial (11mm Pin Spacing) Moulded Cable


0330	Voltage	Size mm Rectangle	LED+VDR	Cable Length Metres
MB635V54PA05100	24V AC/DC	22	LED + VDR	1
MB635V54PA05300	24V AC/DC	22	LED + VDR	3
MB635V54PA05500	24V AC/DC	22	LED + VDR	5
MB635V55PA05100	115V AC	22	LED + VDR	1
MB635V55PA05300	115V AC	22	LED + VDR	3
MB635V55PA05500	115V AC	22	LED + VDR	5
MB635V56PA05100	230V AC	22	LED + VDR	1
MB635V56PA05300	230V AC	22	LED + VDR	3
MB635V56PA05500	230V AC	22	LED + VDR	5
Tech Sheet 10163				

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

ELECTRICAL SOCKET CONNECTORS

Connector DIN43650/A

- Housing colour: Black, grey
- Type of contact: Screw with conductor protection
- Contact spacing: 18mm
- Number of poles: 2 poles + ⏚/3 + ⏚
- Cable diameter 6-8mm for PG9, 8-10mm for PG11.
- Max conductor section: 1.5mm²
- Fixing screw: M3 x 30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)
- Packing unit: *100 pieces with fixing screw and standard gasket






Standard

9072	Description
G1NU2000	PG9 / PG11 Black 2 Poles + Earth

Connector DIN43650/A

- Housing colour: Transparent
- Type of contact: Screw with conductor protection
- Contact spacing: 18mm
- Number of poles: 2 poles + ⏚
- Cable diameter 6-8mm for PG9, 8-10mm for PG11.
- Max conductor section: 1.5mm²
- Fixing screw: M3 x 30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)
- Working voltages available : 12V, 24V, 48V, 110V and 250V






LED & Protection Circuit

9072	Description
G1TU2VL1	PG9 / PG11 24V 2 Poles + Earth
G1TU2VL2	PG9 / PG11 115V 2 Poles + Earth
G1TU2VL3	PG9 / PG11 230V 2 Poles + Earth

Connector DIN43650/A with cable

- Housing colour: Black
- Type of contact: Soldered
- Contact spacing: 18mm
- Number of poles: 2 poles + 2⏚
- Earth position: h6/h12 (ground connection)
- Item available also with 3P+G
- Type of cable: Section 0,50mm and 0,75mm
- Cable length: 1 or 2 metres (other length upon request)
- Max conductor section: IP 65 with moulded cable
- Fixing screw: M3 x 25
- Profile gasket: NBR (other types upon request)
- Cable diameter 6-8mm for PG9, 8-10mm for PG11.

The gasket is integrated on the head of the connector and made of Sipolprene TPC-ET





Moulded Cable

9072	Description
CG1N02000C022	2 Metres 2 Poles + Double Earth

Fluid-Air Components Ltd


ELECTRICAL SOCKET CONNECTORS

Connector DIN43650/A

- Housing colour: Black
- Type of contact: Soldered, 18mm
- Number of poles: 2 poles + 2⏚
- Earth position: h6/h12 (ground connection)
- Type of cable: Section 0,50mm and 0,75mm
- Item available also with 3P+G
- Cable length: 1 or 2 metres (other length upon request)
- Max conductor section: 1.5 mm²
- Protection class: IP 65 with moulded cable
- Fixing screw: M3 x 25
- Profile gasket: NBR (other types upon request)

The gasket is integrated on the head of the connector and made of Sipolprene TPC-ET

In case of connectors with LED+VDR, working voltages available are 12V, 24V, 48V, 110V and 250V
In case od connectors with LED+diode, working voltages available 10/50V and 70/250V




Moulded Cable, LED & Protection Circuit

9072	Description
CG1N02VL1C022	2 Metre 24V 2 Poles + Double Earth
CG1N02VL2C022	2 Metre 115V 2 Poles + Double Earth
CG1N02VL3C022	2 Metre 230V 2 Poles + Double Earth

Connector DIN43650/B-Industrial

- Housing colour: Black, grey
- Type of contact: Screw with conductor protection
- Contact spacing: 11mm
- Number of poles: 2 poles + ⏚
- Cable diameter 6-8mm (PG9)
- Max conductor section: 1.5mm²
- Fixing screw: M3 x 30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class: IP 65 assembled
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)




Standard

9072	Description
M1NS2000	PG9 Black 2 Poles + Earth

Connector DIN43650/B-Industrial

- Housing colour: Transparent
- Type of contact: Screw with conductor protection
- Contact spacing: 11mm
- Number of poles: 2 poles + ⏚
- Cable entry: PG9
- Max conductor section: 1.5mm²
- Fixing screw: M3x30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)




LED & Protection Circuit

9072	Description
M1TS2VL1	PG9 24V 2 Poles + Earth
M1TS2VL2	PG9 115V 2 Poles + Earth
M1TS2VL3	PG9 230V 2 Poles + Earth

Connector DIN43650/B-Industrial Moulded Cabled

- Housing colour: Black
- Type of contact: Soldered
- Contact spacing: 11mm
- Number of poles: 2 poles + ⏚
- Item supplied with 2P+2G (double ground H6/H12)
- Type of cable: Section 0,50mm and 0,75mm
- Cable length: 1 or 2 metres (other length upon request)
- Max conductor section: 1.5mm²
- Protection class: IP 65 with moulded cables
- Fixing screw: M3 x 25
- Profile gasket: The gasket is integrated on the head of the connector and made of Sipolprene TPC-ET



Connector DIN43650/B-Industrial Moulded Cabled

9072	Description
CM1N02000A022	2 Metre 2 Poles + Earth at Cable End
CM1N02000B022	2 Metre 2 Poles + Earth Opposite Cable End

Fluid-Air Components Ltd


ELECTRICAL SOCKET CONNECTORS

Connector DIN43650/B-Industrial

- Housing colour: Black
- Type of contact: Soldered
- Contact spacing: 11mm
- Number of poles: 2 poles + ⏚
- Item supplied with 2P+2G (double ground H6/H12)
- Type of cable: Section 0,50mm and 0,75mm
- Cable length: 1 or 2 metres (other length upon request)
- Max conductor section: 1.5mm²
- Protection class: IP 65 with moulded cables
- Fixing screw: M3 x 25
- Profile gasket: The gasket is integrated on the head of the connector and made of Sipolprene TPC-ET
- In case of connectors with LED+VDR, working voltages available are 12V, 24V, 48V, 110V and 250V
- In case of connectors with LED+diode, working voltages available 10/50V and 70/250V

Moulded Cabled, LED & Protection Circuit

9072	Description
CM1N02VL1A022	2 Metre 24V Poles + Earth at Cable End
CM1N02VL2A022	2 Metre 115V Poles + Earth at Cable End
CM1N02VL3A022	2 Metre 230V Poles + Earth at Cable End
CM1N02VL1B022	2 Metre 24V Poles + Earth Opposite End
CM1N02VL2B022	2 Metre 115V Poles + Earth Opposite End
CM1N02VL3B022	2 Metre 230V Poles + Earth Opposite End




Connector DIN43650/B-ISO6952

Item available also with cable

- Housing colour: Black, grey
- Type of contact: Screw with conductor protection
- Contact spacing: 10mm
- Number of poles: 2 poles + ⏚
- Cable diameter 6-8mm (PG9)
- Max conductor section: 1.5mm²
- Fixing screw: M3 x 30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class: IP 65 assembled
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)

Standard

9072	Description
M2NS2000	PG9 Black 2 Poles + Earth




Connector DIN43650/B-ISO6952

Item available also with cable

- Housing colour: Transparent
- Type of contact: Screw with conductor protection
- Contact spacing: 10mm
- Number of poles: 2 poles + ⏚
- Cable entry: PG9
- Max conductor section: 1.5mm²
- Fixing screw: M3 x 30
- The gasket (profiled or flat) is made of thermoplastic rubber in black.
- Protection class: IP 65 assembled
- Protection class IP67 is also available (external thread as gland size, cable dia. 4,5-8mm)

LED & Protection Circuit

9072	Description
M2TS2VL1	PG9 24V 2 Poles + Earth
M2TS2VL2	PG9 115V 2 Poles + Earth
M2TS2VL3	PG9 230V 2 Poles + Earth






Connector DIN43650/C

Item available also with cable

- Housing colour: Black, grey
- Type of contact: Screw with conductor protection
- Contact spacing: 9.4mm ⏚
- Number of poles: 3 poles +
- Cable entry: PG7 2P+G
- Cable diameter 4-6mm (PG7).
- Max conductor section: 0.75mm²
- Fixing screw: M3 x 27
- Profile gasket: (profiled or flat) is made of thermoplastic rubber in black.
- Protection class: IP 65 assembled
- Protection class IP67 is also available (external thread as gland size, cable dia. 3,5-6mm)
- Item available also with spacing 8mm
- Item available also with circuitry

Standard

9072	Description
P1NZ3000	PG7 Black 3 Poles + Earth





Fluid-Air Components Ltd



Partnership brands available



Hydraulic Accumulators & Accessories
See section 1 pages 227-228

Hydraulic Oil Coolers
See section 1 page 273



Ball & Check Valves
See section 5 pages 628

Plastic Push-in Fittings
See section 6 pages 793-807

Metal Push-in Fittings
See section 6 pages 848-851

Ball Valves
See section 7 pages 933-935

Blow Guns
See section 15 page 1596



Pneumatic Quick Release Couplings
See section 3 pages 330-390



Filters & Drains Air, Water & Vacuum
See section 4 page 430



Aluminium Ring Main Systems
See section 8 pages 1063-1067



Plastic Push-in Fittings
See section 6 pages 800-803

ENGINEERING YOUR SUCCESS.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Angle Seat Valves with Stainless Steel Body



Pilot Operated 2/2 Solenoid Valve



Direct Acting 2/2 Solenoid Valve



Valve Timer

Features:

- Maintenance free actuator
- Long life piston rings
- Easy installation
- 360º positional actuator head
- Leak free after five million cycles
- Compact design
- Fast response
- Water hammer-free
- Cost effective against other materials

Applications:

- Food and beverage plants
- Textile factories
- Pharmaceuticals manufacture
- Laundries
- Water and sewage plants
- Petrochemical plants
- Automotive sites

Operation:

- Normally open
- Normally closed

Working Temperature:

Medium:
-10°C to +180°C

Environmental:

PA nylon	-10°C to +60°C
Stainless steel	-10°C to +80°C

Working Pressure
3 to 16 bar*

Construction:

Body:	316 stainless Steel
Actuator:	PA nylon or 316 stainless Steel

1048

ANGLE SEAT VALVES

Working Temperature:
Media: -10°C to +180°C
Environmental Temperature
PA Nylon -10°C to +60°C
Stainless steel -10°C to +80°C

Working Pressure:
3 to 16 bar

- Compact design, available in both normally open and normally closed options.
- Normally Closed - Closes with the flow.
- Normally Open - Closes against the flow.
- Pilot operated.
- High flow.
- 360° Actuator housing rotation.
- Single acting spring return.
- Suitable for use with water, oil, air, aggressive media and steam.

316 Stainless Steel Valve, PA Nylon Actuator

Material:
Body: 316L Stainless steel
Actuator: PA
Seals: PTFE



2 Way 63mm Actuator Normally Closed, BSPP

0381	Thread
KASV-SSP-38-NC	3/8"
KASV-SSP-12-NC	1/2"
KASV-SSP-34-NC	3/4"
KASV-SSP-1-NC	1"
KASV-SSP-114-NC	1.1/4"
KASV-SSP-112-NC	1.1/2"
KASV-SSP-2-NC	2"
KASV-SSP-212-NC	2.1/2"

Tech Sheet 10204



2 Way 63mm Actuator Normally Open, BSPP

0381	Thread
KASV-SSP-38-NO	3/8"
KASV-SSP-12-NO	1/2"
KASV-SSP-34-NO	3/4"
KASV-SSP-1-NO	1"
KASV-SSP-114-NO	1.1/4"
KASV-SSP-112-NO	1.1/2"
KASV-SSP-2-NO	2"
KASV-SSP-212-NO	2.1/2"

Tech Sheet 10204

316 Stainless Steel Valve, Stainless Steel Actuator

Material:
Body: 316L Stainless steel
Actuator: 316L Stainless steel
Seals: PTFE



2 Way 63mm Actuator Normally Closed, BSPP

0381	Thread
KASV-SSSS-38-NC	3/8"
KASV-SSSS-12-NC	1/2"
KASV-SSSS-34-NC	3/4"
KASV-SSSS-1-NC	1"
KASV-SSSS-114-NC	1.1/4"
KASV-SSSS-112-NC	1.1/2"
KASV-SSSS-2-NC	2"
KASV-SSSS-212-NC	2.1/2"

Tech Sheet 10204



2 Way 63mm Actuator Normally Open, BSPP

0381	Thread
KASV-SSSS-38-NO	3/8"
KASV-SSSS-12-NO	1/2"
KASV-SSSS-34-NO	3/4"
KASV-SSSS-1-NO	1"
KASV-SSSS-2-NO	2"

Tech Sheet 10204

You might also need...
Polyurethane & Nylon Tube
see pages **897-917**



Fluid-Air Components Ltd

FESTO ACTUATION

stainless steel

FESTO

new product

Pinch Valves

Features:

- 316 stainless steel body
- Normally open
- Pneumatically actuated
- BSPP or clamp end connections
- EPDM or silicone shut-off element material available
- Quick to install and easy to maintain
- Suitable for use with granulates, liquids containing solid particles, highly viscous, contaminated and abrasive media

Working Temperature:
-5°C to +60°C

Maximum Working Pressure:
6 bar



VZQA 2/2 Way Normally Open Pinch Valve, BSPP

0009	Size	Shut-Off Element Material	Manufacturer's Code
2931678	1/4"	EPDM	VZQA-C-M22U-6-GG-V4V4E-4
2931683	1/4"	Silicone	VZQA-C-M22U-6-GG-V4V4S1-4
3022829	1/2"	EPDM	VZQA-C-M22U-15-GG-V4V4E-4
3022835	1/2"	Silicone	VZQA-C-M22U-15-GG-V4V4S1-4
3968922	1"	EPDM	VZQA-C-M22U-25-GG-V4V4E-4
3968926	1"	Silicone	VZQA-C-M22U-25-GG-V4V4S1-4
		Tech Sheet 6292	

VZQA 2/2 Way Normally Open Pinch Valve, Clamp Style

0009	Size	Shut-Off Element Material	Manufacturer's Code
2931681	1/4"	EPDM	VZQA-C-M22U-6-S5S5-V4V4E-4
2931682	1/4"	Silicone	VZQA-C-M22U-6-S5S5-V4V4S1-4
3022833	1/2"	EPDM	VZQA-C-M22U-15-S5S5-V4V4E-4
3022834	1/2"	Silicone	VZQA-C-M22U-15-S5S5-V4V4S1-4
3968924	1"	EPDM	ZQA-C-M22U-25-S5S5-V4V4E-4
		Tech Sheet 6292	

ANGLE SEAT VALVES


FESTO

VZXF Normally Closed Angle Seat Valves

Features:

- Available in gunmetal or 316 stainless steel valve and actuator
- BSPP threads
- Normally closed
- PTFE seat
- Water hammer free flow under seat
- Suitable for domestic water services, inert gases, oil, hydraulic fluid, neutral liquids and compressed air systems dependent on the valve body

Working Temperature:
Media: -10°C to +80°C (gunmetal)
Media: -40°C to +200°C (stainless steel)
Environment: -10°C to +60°C



Gunmetal Angle Seat Valve and Actuator

0990	Thread	DN	Manufacturer's Code	Flow Rate (m³/h)
1002501	1/2"	15	VZXF-L-M22C-M-B-G12-120-H3B1-50-16	3.70
1002503	3/4"	20	VZXF-L-M22C-M-B-G34-160-H3B1-50-16	5.20
1002505	1"	25	VZXF-L-M22C-M-B-G1-230-H3B1-50-10	9.60
1002507	1.1/4"	32	VZXF-L-M22C-M-B-G114-290-H3B1-50-7	6
1002509	1.1/2"	40	VZXF-L-M22C-M-B-G112-350-H3B1-50-6	16.50
1002511	2"	50	VZXF-L-M22C-M-B-G2-430-H3B1-50-3	23
		Tech Sheet 6269		

Stainless Steel Angle Seat Valve and Actuator

0990	Thread	DN	Manufacturer's Code	Flow Rate (m³/h)
1002513	1/2"	15	VZXF-L-M22C-M-B-G12-130-M1-V4V4T-50-40	3.30
1002515	3/4"	20	VZXF-L-M22C-M-B-G34-180-M1-V4V4T-50-20	6.50
1002517	1"	25	VZXF-L-M22C-M-B-G1-240-M1-V4V4T-50-10	11
1002519	1.1/4"	32	VZXF-L-M22C-M-B-G114-310-M1-V4V4T-50-7	10.70
1002521	1.1/2"	40	VZXF-L-M22C-M-B-G112-350-M1-V4V4T-50-6	17.50
1002523	2"	50	VZXF-L-M22C-M-B-G2-450-M1-V4V4T-50-3	19.50
		Tech Sheet 6269		

VZXA Normally Closed Angle Seat Valves

Features:

- BSPP threads
- Normally closed
- PTFE seat
- ATEX II 2G Ex h IIC T3 Gb / II 2D Ex h IIIC T200°C Db certification
- SIL2 rated
- IP67 rated
- Water hammer free flow under seat
- Suitable for domestic water services, inert gases, oil, hydraulic fluid, neutral liquids, compressed air systems and hazardous areas

- Accessories such as a stroke reducing kit and a position indicator with or without sensors are also available on request

Working Temperature:
Media: -10°C to +180°C
Environment: 0°C to +60°C



Stainless Steel Angle Seat Valve and Actuator

0990	Thread	DN	Manufacturer's Code	Flow Rate (m³/h)
8060527	1/2"	15	VZXA-B-TS6-13-M2-V13T-30-K-46-17-V4	6
8060528	3/4"	20	VZXA-B-TS6-20-M2-V13T-12.8-K-46-17-V4	13.30
8060530	1"	25	VZXA-B-TS6-25-M2-V13T-8.3-K-46-17-V4	20.30
8060533	1.1/4"	32	VZXA-B-TS6-32-M2-V13T-4.4-K-46-17-V4	27.90
8060536	1.1/2"	40	VZXA-B-TS6-40-M2-V13T-9.3-K-75-20-V4	41.40
8060538	2"	50	VZXA-B-TS6-50-M2-V13T-5.6-K-75-20-V4	50.10
		Tech Sheet 6268		

Fluid-Air Components Ltd

ANGLE SEAT VALVES

stainless steel

Stainless Steel

Construction:
- Stainless steel actuator housing for exceptional durability in steam and aggressive applications
- 304 stainless steel actuator and 316L stainless steel body

Benefits
- Compact design, high flow rate
- Visual position indicator
- Dampened closing anti-water hammer design (fluid under seat
- Mountable in any position
- Tight shut-off and long service life
- Valves meet Pressure Equipment Directive 97/23/EC
- Conforms to 94/9/CE directive specific to non-electrical equipment for use within potentially explosive environments, zones 1/21 and 2/22

Working Temperature:
-10°C to +180°C

Applications:
- Food and beverage processing
- Water technology and treatment
- Textile industry
- Cooling systems on injection moulding machines
- Pharmaceutical/cosmetics industry
- Chemical process technology
- Refrigeration and cooling/heat exchangers
- Sterilisers and steam supply
- Water applications including mining, cement/concrete systems, pulp and paper
- General industrial applications of aggressive fluid
- Industrial laundry equipment
- Industrial air dryers



High Temperature, Flow Over Seat, 304 Stainless Steel Actuator, 316L Stainless Steel Body, Normally Closed

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA10C1G3R032S	3/8"	13	16	PA10C1G3R032S
PA15C1G4R032S	1/2"	13	16	PA15C1G4R032S
PA20C1G5R032S	3/4"	15	14	PA20C1G5R032S
Tech Sheet 60414				

High Temperature, Flow Under Seat, 304 Stainless Steel Actuator, 316L Stainless Steel Body, Normally Closed, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA10C2G3R032S	3/8"	13	16	PA10C2G3R032S
PA15C2G4R032S	1/2"	13	16	PA15C2G4R032S
PA20C2G5R032S	3/4"	15	14	PA20C2G5R032S
Tech Sheet 60414				

Flow Over Seat, 304 Stainless Steel Actuator, 316L Stainless Steel Body, Normally Closed, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA10S1G3R050S	3/8"	13	16	PA10S1G3R050S
PA15S1G4R040S	1/2"	13	16	PA15S1G4R040S
PA15S1G4R050S	1/2"	13	16	PA15S1G4R050S
PA20S1G5R050S	3/4"	18	16	PA20S1G5R050S
PA25S1G6R050S	1"	24	16	PA25S1G6R050S
PA25S1G6R063S	1"	24	16	PA25S1G6R063S
PA32S1G7R063S	1.1/4"	31	16	PA32S1G7R063S
Tech Sheet 60414				

Flow Over Seat, 304 Stainless Steel Actuator, 316L Stainless Steel Body, Normally Open, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA10S2G3R050S	3/8"	13	16	PA10S2G3R050S
PA15S2G4R050S	1/2"	13	16	PA15S2G4R050S
PA20S2G5R050S	3/4"	18	16	PA20S2G5R050S
PA25S2G6R063S	1"	24	16	PA25S2G6R063S
PA32S2G7R063S	1.1/4"	31	14	PA32S2G7R063S
Tech Sheet 60414				

Anti-water Hammer Construction, Flow Under Seat, 304 Stainless Steel Actuator, 316L Stainless Steel Body, Normally Closed, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA10SAG3R050S	3/8"	13	16	PA10SAG3R050S
PA15SAG4R050S	1/2"	13	16	PA15SAG4R050S
PA20SAG5R050S	3/4"	18	10	PA20SAG5R050S
PA25SAG6R063S	1"	24	8	PA25SAG6R063S
PA32SAG7R080S	1.1/4"	31	11	PA32SAG7R080S
Tech Sheet 60414				

Anti-water Hammer Construction Flow Under Seat Aluminium Actuator 316L Stainless Steel Body, Normally Closed, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA15SAG4R050A	1/2"	13	16	PA15SAG4R050A
PA20SAG5R050A	3/4"	18	10	PA20SAG5R050A
PA25SAG6R063A	1"	24	8	PA25SAG6R063A
Tech Sheet 60414				

Flow Over Seat, Aluminium Actuator, 316L Stainless Steel Body, Normally Closed, BSPP

0484	Thread	Orifice mm	Max Pressure Bar	Manufacturer's Code
PA15S1G4R050A	1/2"	13	16	PA15S1G4R050A
PA20S1G5R050A	3/4"	18	16	PA20S1G5R050A
Tech Sheet 60414				

Fluid-Air Components Ltd

ANGLE SEAT VALVES

stainless steel

Stainless Steel Angle Seat Piston Valves

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



Compact 45mm Actuator, 2 Way N/C, BSPP

0263	Thread	LPM	Max Pressure Bar
PG205CTW00	1/2"	98	16
PG206CTX00	3/4"	164	16
Tech Sheet 968			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



Compact 45mm Actuator, 2 Way N/O, BSPP

0263	Thread	LPM	Max Pressure Bar
RPG205CTW00	1/2"	98	16
RPG206CTX00	3/4"	164	16
Tech Sheet 969			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



63mm Actuator, 2 Way N/C, BSPP

0263	Thread	LPM	Max Pressure Bar
PG205STW00	1/2"	98	20
PG206STX00	3/4"	164	20
PG207STY00	1"	260	20
PG208STZ00	1.1/4"	410	16
PG209STK00	1.1/2"	700	16
PG210STJ00	2"	950	11
Tech Sheet 968			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



63mm Actuator, 2 Way N/O, BSPP

0263	Thread	LPM	Max Pressure Bar
RPG205STW00	1/2"	98	20
RPG206STX00	3/4"	164	20
RPG207STY00	1"	260	20
RPG208STZ00	1.1/4"	410	16
RPG209STK00	1.1/2"	700	16
RPG210STJ00	2"	950	11
Tech Sheet 969			

FTPRO stainless steel



For **Stainless Steel Push-in Fittings**
see pages **875-879**

Fluid-Air Components Ltd

ANGLE SEAT VALVES

Bronze Angle Seat Piston Valves

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



Compact 45mm Actuator, 2 Way N/C, BSPP

0263	Thread	LPM	Max Pressure Bar
CG205CTW00	1/2"	98	16
CG206CTX00	3/4"	164	16
CG207CTY00	1"	260	16
Tech Sheet 970			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



63mm Actuator, 2 Way N/C, BSPP

0263	Thread	LPM	Max Pressure Bar
CG205STW00	1/2"	98	20
CG206STX00	3/4"	164	20
CG207STY00	1"	260	20
CG208STZ00	1.1/4"	410	16
CG209STK00	1.1/2"	700	16
CG210STJ00	2"	950	11
Tech Sheet 970			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



Compact 45mm Actuator, 2 Way N/O, BSPP

0263	Thread	LPM	Max Pressure Bar
RCG205CTW00	1/2"	98	16
RCG206CTX00	3/4"	164	16
RCG207CTY00	1"	260	16
Tech Sheet 971			

Ambient Temperature:
-10°C to +60°C
Working Temperature:
-10°C to +180°C



63mm Actuator, 2 Way N/O, BSPP

0263	Thread	LPM	Max Pressure Bar
RCG205STW00	1/2"	98	16
RCG206STX00	3/4"	164	16
RCG207STY00	1"	260	16
RCG208STZ00	1.1/4"	410	16
RCG209STK00	1.1/2"	700	16
RCG210STJ00	2"	950	12
Tech Sheet 971			

Banjo Solenoid Valves

Ambient Temperature:
-10°C to +50°C
Working Temperature:
-10°C to +130°C

- Suitable for use with M&M, CG, PG and BLG piston valves.



Direct Mount

0263	To Suit Actuator Size	Voltage
B356CVCMK24VDC	45	24V DC
B356CVCMK24VAC	45	24V AC
B356CVCMK110VAC	45	110V AC
B356CVCMK240VAC	45	240V AC
B326CVCMK24VDC	63	24V DC
B326CVCMK24VAC	63	24V AC
B326CVCMK110VAC	63	110V AC
B326CVCMK240VAC	63	240V AC
Tech Sheet 972		

PRESSURE SWITCHES

Direct Mount Pressure Switches

- **Electrical Connection:** Terminal 6.3 x 0.8
- **Electrical Data:** 10amp x 250V



Ambient Temperature:
-10°C to +50°C
Working Temperature:
-10°C to +125°C

- Suitable for Hot Water, Steam, Neutral Liquids, Light Oils, Air and Inert Gases

Brass Body, Silicone Membrane, BSPP

0061	Thread	Pressure Range Bar	Fixed Differential Bar	Repeatability Bar
XP73AE61.000	1/8"	0.2-1.2	0.30±0.15	±0.15
XP73CE61.000	1/8"	1.0-2.5	0.30±0.15	±0.2
XP73DE61.000	1/8"	1.5-4.0	0.30±0.15	±0.2
XP73EE61.000	1/8"	2.0-6.0	0.30±0.15	±0.2
Tech Sheet 975				

Ambient Temperature:
-10°C to +50°C
Working Temperature:
-10°C to +80°C

- Suitable for water, neutral liquids, light oils, air and inert gases

Brass Body, Nitrile Membrane, BSPP

0061	Thread	Pressure Range Bar	Fixed Differential Bar	Repeatability Bar
GP73ME31.000	1/8"	0.2-3.0	0.3±0.1	±0.2
GP73PE31.000	1/8"	1.0-5.0	0.5±0.15	±0.2
Tech Sheet 10440				

Ambient Temperature:
-10°C to +50°C
Working Temperature:
-10°C to +125°C

- Suitable for hot water, steam and aggressive media

Stainless Steel Body, BSPP

0061	Thread	Pressure Range Bar	Fixed Differential Bar
XP83FE61000	1/8"	4.0-9.0	0.50±0.20
XP83GE61000	1/8"	9.0-15.0	0.70±0.30
Tech Sheet 976			

You might also need...
Galvanised Fittings
...see pages **1338-1381**



Fluid-Air Components Ltd

OMAL ACTUATION

Applications:
Nitrile:
Compatible with air, gas, oils, water etc.
Viton:
High compatibility with the majority of fluids, not advised for steam.

Working Temperature:
Nitrile:
-20°C to +80°C
Viton:
-20°C to +150°C

Note:
The compact design of a VIP valve with its reduced size and weight allows it to be used in applications where traditional actuated valve packages cannot be utilised. The VIP valve has no external moving parts, which ensures their operation is quick and efficient, with out the safety issues of the traditional actuated valve packages.
The VIP valve with the approved gas threaded connections (UN1-ISO 7/1-DIN 2999) coupled with a NAMUR mounting plate makes this valve suitable for every possible plant application.
The valve can be mounted in any position. Full technical specifications available on request

V.I.P. Axial Flow Valves with Nitrile Seals



Double Acting, BSPP

0129	Thread
VDA10003	3/8"
VDA10004	1/2"
VDA10005	3/4"
VDA10006	1"
VDA10007	1.1/4"
VDA10008	1.1/2"
VDA10009	2"
Tech Sheet 862	

Single Acting Spring Return Normally Closed, BSPP

0129	Thread
VNC10003	3/8"
VNC10004	1/2"
VNC10005	3/4"
VNC10006	1"
VNC10007	1.1/4"
VNC10008	1.1/2"
VNC10009	2"
Tech Sheet 862	

V.I.P. Axial Flow Valves with Viton Seals



Double Acting, BSPP

0129	Thread
VDA20003	3/8"
VDA20004	1/2"
VDA20005	3/4"
VDA20006	1"
VDA20007	1.1/4"
VDA20008	1.1/2"
VDA20009	2"
Tech Sheet 862	

Single Acting Spring Return Normally Closed, BSPP

0129	Thread
VNC20003	3/8"
VNC20004	1/2"
VNC20005	3/4"
VNC20006	1"
VNC20007	1.1/4"
VNC20008	1.1/2"
VNC20009	2"
Tech Sheet 862	

Stainless Steel Angle Seat Valve with NAMUR Interface

Working Temperature:
-10°C to 180°C

Working Pressure:
0-16 bar
(0-10 bar for steam)

Available up to 2" - alternative terminations available.



BSPP

0129	Thread
J4CPG1604	1/2"
J4CPG1605	3/4"
J4CPG1806	1"
Tech Sheet 121	

Bronze Angle Seat Valve with NAMUR Interface

Working Temperature:
-10°C to 180°C

Working Pressure:
0-16 bar
(0-10 bar for steam)

Available up to 2" - alternative terminations available.



BSPP

0129	Thread
J9CPG1603	3/8"
J9CPG1604	1/2"
J9CPG1605	3/4"
J9CPG1806	1"
Tech Sheet 121	

FAC
Fluid-Air Components Ltd

CONTROL VALVES

Slide Valves - On/Off Type, Brass

Working Temperature:
-20°C to +80°C



Type 6060, BSPP

0090	Thread
6060-18	1/8"
6060-14	1/4"
6060-38	3/8"
6060-12	1/2"
Tech Sheet 10803	

For **Push-Fittings**
...see page **768**



Fluid-Air Components Ltd

WATER VALVES & ACCESSORIES

Globe Valves



BSPP

0356	Thread	Voltage
KA-32-40-24-AC	1.1/2"	24V AC

Adjustable Pressure Regulators



3/4" Specifications, BSP

0356	Thread	Pressure Range Bar
KA-35-20-10-MF	3/4"	0.8-2.5



1" Specifications, BSP

0356	Thread	Pressure Range Bar
KA-35-25-05	1"	0.5-1.2
KA-35-25-12	1"	1.5-3.5



1.1/2" Specifications, BSP

0356	Thread	Pressure Range Bar
KA-35-40-10	1.1/2"	0.5-1.2
KA-35-40-18	1.1/2"	1.5-3.5

Air & Vacuum Release Valves



1" Automatic Air Release Valve, BSPP

0356	Thread
KA-35-75-20	1"

Standard Cold Water Meters



0356	Description
KA-36-00-25	1" Cold Water Meter 5m³ Nominal Flow Rate
KA-36-00-40	1.1/2" Cold Water Meter 10m³ Nominal Flow Rate
	Tech Sheet 663

Filters

Maximum Working Pressure: 8 bar



3/4" Plastic In-line Filter - 10gpm

0356	Description
KA-39-00-10	3/4" Plastic In-line Filter 100 Micron Mesh Element



1" Plastic In-line Filter - 25gpm

0356	Description
KA-39-10-10	1" Plastic In-line Filter 100 Micron Mesh Element

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DRAIN COCK & BLEEDER VALVES

Drain Cock Valves

Features:
- Type A drain-off cock
- BSPT male connection

Working Temperature: 0°C to +120°C

Maximum Working Pressure: 15 bar



Brass, BSPT

0908	Thread
DC-12	1/2"
Tech Sheet 6059	

Bleeder Valve

Working Temperature: -20°C to +85°C

Maximum Working Pressure: 10 bar



BSPP

0234	Thread
124.8	1/8"
124.4	1/4"
124.3	3/8"

DRAIN BALL VALVES & PUMP CONNECTORS

Drain Ball Valves, Brass

Working Temperature: -15°C to +110°C (Air)
0°C to +90°C (Water)

Maximum Working Pressure: 12 bar



Type 139, Male x Hose Tail, BSPP

0089	Thread	To Suit Hose ID mm
IT139-38	3/8"	10
IT139-12	1/2"	13
IT139-34	3/4"	19
Tech Sheet 10339		

5 Way Connector for Pumps & Tanks, Brass

Working Temperature: -20°C to +120°C

Nominal Pressure: 25 bar



Type 110, Male, BSPT x Female, BSPP

0089	Thread
IT110-1	1"
Tech Sheet 10335	

Fluid-Air Components Ltd

FLOAT VALVES

Cistern Valves & Accessories

Features:
- Brass float operated ball valve supplied with removable seat and back nuts
- Order floats separately

Working Temperature:
0°C to +90°C

Maximum Working Pressure:
14 bar



Brass BS 1212 Part 1 Float Valve

0908	Size	BSW	Lever	Float	Kg
DBL101A	1/2"	5/16"	220	4.1/2"	0.39
DBL305	3/4"	5/16"	325	6"	0.90
DBL141	1"	7/16"	400	8"	1.93
DBL161	1.1/4"	9/16"	565	10"	4.33
DBL171	1.1/2"	9/16"	565	10"	4.40
DBL181	2"	5/8"	725	12"	7.99
Tech Sheet 6059					

Features:
- Soldered copper floats for use with cold water only

Working Temperature:
0°C to +30°C



Copper Float

0908	Size	BSW	Kg
D1045	4.1/2"	5/16"	0.24
D1060	6"	5/16"	0.30
D1080	8"	7/16"	0.75
D1100	10"	9/16"	1.59
D1120	12"	5/8"	2.78
Tech Sheet 6059			

Features:
- Plastic floats with brass threaded inserts

Working Temperature:
0°C to +80°C



Plastic Float

0908	Size	BSW	Kg
D45BTOR	4.1/2"	5/16"	0.24
D60BTOR	6"	5/16"	0.30
D80BTOR	8"	7/16"	0.75
D910BTOR	10"	9/16"	1.59
D912BTOR	12"	5/8"	2.78
Tech Sheet 6059			

STAINLESS STEEL VALVES


stainless steel GENEBRE

Stainless Steel Float Valves

Body: 316 stainless steel
Seal: Silicone

Working Temperature:
0°C to +150°C

Maximum Working Pressure:
10 bar



Male, BSPP

0902	Thread
H2856-12	1/2"
H2856-34	3/4"
H2856-1	1"
H2856-114	1.1/4"
H2856-112	1.1/2"
H2856-2	2"
H2856-212	2.1/2"
Tech Sheet 68251	

Stainless Steel Floats

Working Temperature:
0°C to +150°C



Metric Female

0902	Thread	OD mm	To Suit
H2852 110	M6	110	1/2" Float Valve
H2852 160	M8	160	3/4"-1.1/4" Float Valve
H2852 200	M12	200	1.1/2"-2.1/2" Float Valve
Tech Sheet 68251			

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FT PRO VALVES

Spring Auto, Self Close Pour Tap

Polypropylene

- Maximum counteracting pressure is 4.5 bar from 0 bar operating range
- Black polypropylene with EPDM seals as standard
- Stainless steel 302 spring is in separate chamber to flow
- TPE thread gasket included
- Push button end to open flow, take hand away to allow self-closure
- Guide markings on tap
- Suitable for use with static or portable tanks to prevent unattended liquid loss
- Can be used with appropriate chemicals to prevent dangerous spills

Applications

Adopted by many local water authorities to use on emergency supply tankers, avoiding unnecessary waste.



3/4" BSPP Male x 20mm OD Outlet

0680	Thread	OD mm
11PP07	3/4"	20
	Tech Sheet 68761	

Nylon

- Maximum counteracting pressure is 4.5 bar from 0 bar operating range
- Beige nylon with FPM seals for use with paraffin or very rugged duty
- Stainless steel 302 spring is in separate chamber to flow
- TPE thread gasket included
- Push button end to open flow, take hand away to allow self-closure
- Guide markings on tap
- Suitable for use with static or portable tanks to prevent unattended liquid loss
- Can be used with appropriate chemicals to prevent dangerous spills

Applications

Adopted by many local water authorities to use on emergency supply tankers, avoiding unnecessary waste.



3/4" BSPP Male x 20mm OD Outlet

0680	Thread	OD mm
11PN07	3/4"	20
	Tech Sheet 68761	



Fluid-Air Components Ltd

1	Hydraulics	3-284
2	Hydraulic Quick Release Couplings	285-320
3	Pneumatic Quick Release Couplings	321-406
4	Monitor & Test	407-446
5	Pneumatic & Vacuum	447-762
6	Push-in Fittings & Tubing	763-918
7	Valves & Actuation	919-1060
8	**Ring Main**	1061-1136
9	Hose Tails, Adaptors, Fittings & Manifolds	1137-1224
10	Stainless Steel	1225-1332
11	Malleable Iron	1333-1398
12	Hose, Couplings, Ducting & Hose Reels	1399-1510
13	Clips & Clamps	1511-1558
14	Paint, Sprays & Adhesives	1559-1590
15	Blow Guns, Vacuum & Nozzles	1591-1616
16	Fuelling, Lubrication, Wash Down & Misting	1617-1696
17	Compressors & Air Tools	1697-1726
18	Hand Tools & PPE	1727-1765

SECTION 8

Ring Main

8.01	Aluminium & Plastic Systems	1061-1096
8.02	ABS Systems	1097-1100
8.03	UPVC Systems	1101-1115
8.04	Stainless Steel & Copper Systems	1116-1136

Fluid-Air Components Ltd

SECTION 8

8.01 Aluminium & Plastic Systems

1061-1096

- Transair Ring Main System Air & Vacuum Range
- Ring Main System
- Technopolymer System Fittings
- Valves
- Fittings, Aluminium System
- 6" (168.3mm) Tubing & Fittings System
- Ring Main Pipe Kits (CARM)
- Fast-Track Ring Main System
- Polyethylene Compression System
- Polyethylene Pipe Universal Transition fittings
- Polyethylene Pipe Universal Transition Fittings & Valves



8.02 ABS Systems

1097-1100

- ABS Imperial Pipe System



8.03 UPVC Systems

1101-1115


- UPVC Metric Pipe System
- UPVC Imperial Pipe System
- UPVC Threaded Fittings



8.04 Stainless Steel & Copper Systems

1116-1136


- Stainless Steel 316 Press Fit Piping System
- Copper Press Fit Piping System
- Brass Ball Valves
- Nirosan® Stainless Steel Press Fit Piping System



Fluid-Air Components Ltd

TRANSAIR RING MAIN SYSTEM AIR & VACUUM RANGE

Transair Aluminium Pipe



3 Metres, Single Lengths

1100	Tube OD mm	Tube ID mm
1003A.17.04.00	16.5	13
1003A.25.04.00	25	22
1003A.40.04.00	40	37
1003A.50.04	50	47
1003A.63.04	63	59

6 Metres, Per Pack

1100	Tube OD mm	Tube ID mm	Pack Size
1006A.25.04.00	25	22	6
1006A.40.04.00	40	37	6
1006A.50.04	50	47	5
1006A.63.04	63	59	4



2 Port 45° Threaded Wall Bracket, BSPP

1100	Female Thread
6690.21.21	1/2"

Transair Range



1 Port 45° Tube Wall Bracket, BSPP

1100	Tube OD mm	Female Thread
6639.17.21	16.5	1/2"
6639.25.21	25	1/2"



2 Port 45° Tube Wall Bracket, BSPP

1100	Tube OD mm	Female Thread
6682.17.21	16.5	1/2"
6682.25.21	25	1/2"



3 Port 45° Tube Wall Bracket, BSPP

1100	Tube OD mm	Female Thread
6695.25.21	25	1/2"



2 Port Horizontal Tube Wall Bracket, BSPP

1100	Tube OD mm	Female Thread
6681.17.21	16.5	1/2"
6681.25.21	25	1/2"



1 Port 45° Wall Bracket with Ball Valve

1100	Tube OD mm	Female Thread
6678.17.21	16.5	1/2"
6678.25.21	25	1/2"



2 Port 45° Wall Bracket with Ball Valve

1100	Tube OD mm	Female Thread
6693.17.21	16.5	1/2"
6693.25.21	25	1/2"



3 Port 45° Wall Bracket with Ball Valve


1100	Tube OD mm	Female Thread
6637.25.21	25	1/2"



Mini Bracket

1100	Tube OD mm	Female Thread
6661.25.21	25	1/2"
6661.40.21	40	1/2"
6661.40.27	40	3/4"
6661.50.21	50	1/2"
6661.50.27	50	3/4"
6662.63.21	63	1/2"

Fluid-Air Components Ltd



Transair: Modular Pipe Systems

- Lower pressure drop
- Air quality class 1-1-1
- Safest connection technologies
- Labour and installation time reduced
- Services to support your project



Parker

ENGINEERING YOUR SUCCESS.

1064

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

TRANSAIR RING MAIN SYSTEM AIR & VACUUM RANGE

Transair Range



Reducing Bracket

1100	Tube OD A mm	Tube OD B mm
6662.25.17	25	16.5
6662.25.00	25	25
6662.40.17	40	16.5
6662.40.25	40	25
6662.50.25	50	25
6662.63.25	63	25



Quick Assembly Bracket with Ball Valve, BSPP

1100	Tube OD mm	Female Thread
6669.25.21	25	1/2"
6669.40.21	40	1/2"
6669.40.27	40	3/4"
6669.50.21	50	1/2"
6669.50.27	50	3/4"
6669.63.21	63	1/2"
6669.63.27	63	3/4"



Quick Assembly Direct Feed Bracket

1100	Tube OD A mm	Tube OD B mm
RA69.50.25	50	25



Quick Assembly Direct Feed Bracket, BSPP

1100	Tube OD mm	Female Thread
RA65.50.04	50	1/2"
RA65.50.08	50	1"



Pressurised System Outlet with Ball Valve

1100	Tube OD mm	Female Thread
EA98.50.04	50	1/2"



Male Stud, BSPT

1100	Tube OD mm	Male Thread
6605.17.13	16.5	1/4"
6605.17.21	16.5	1/2"
6605.25.21	25	1/2"
6605.25.27	25	3/4"
6605.25.34	25	1"
6605.40.34	40	1"
6605.40.42	40	1.1/4"
6605.40.49	40	1.1/2"
6605.50.49	50	1.1/2"
6605.50.48	50	2"
6605.63.48	63	2"



Male Stud BSPT with Fixing Plate

1100	Tube OD mm	Male Thread
6615.50.49	50	1.1/2"
6615.50.48	50	2"



Pipe to Pipe Connector

1100	Tube OD mm
6606.17.00	16.5
6606.25.00	25
6606.40.00	40
6606.50.00	50
6606.63.00	63



Plug-in Reducer

1100	Description
6666.17.25	25mm Pipe to 16.5mm Pipe
6666.25.40	40mm Pipe to 25mm Pipe



Plug-in Reducer

1100	Description
6666.40.50	50mm Pipe to 40mm Pipe
6666.50.63	63mm Pipe to 50mm Pipe



For **Parker Blow Guns** see page **1596**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

TRANSAIR RING MAIN SYSTEM AIR & VACUUM RANGE

Transair Range



Vented End Cap

1100	Tube OD mm
6625.17.00	16.5
6625.25.00	25
6625.40.00	40
6625.50.00	50
6625.63.00	63



90° Elbow Male Stud, BSPT

1100	Tube OD mm	Male Thread
6609.17.13	16.5	1/4"
6609.17.21	16.5	1/2"
6609.25.21	25	1/2"
6609.25.27	25	3/4"
6609.25.34	25	1"
6609.40.34	40	1"
6609.40.42	40	1.1/4"
6609.50.49	50	1.1/2"
6609.50.48	50	2"
6609.63.48	63	2"



90° Elbow

1100	Tube OD mm
6602.17.00	16.5
6602.25.00	25
6602.40.00	40
6602.50.00	50
6602.63.00	63



45° Elbow

1100	Tube OD mm
6612.25.00	25
6612.40.00	40
6612.63.00	63



Equal Tee

1100	Tube OD mm
6604.17.00	16.5
6604.25.00	25
6604.40.00	40
6604.50.00	50
6604.63.00	63



Reducing Tee

1100	Tube OD A mm	Tube OD B mm
6604.50.25	50	25
6604.50.40	50	40



Lockable Aluminium Valve

1100	Tube OD mm
4092.17.00	16.5
4092.25.00	25
4092.40.00	40
4092.50.00	50
4092.63.00	63



Flexible Hose

1100	Tube OD mm	Length Metres
1001E.250001	25	0.57
1001E.250004	25	2



For **Parker Legris Tubing**
see pages **906-908**

Fluid-Air Components Ltd

TRANSAIR RING MAIN SYSTEM AIR & VACUUM RANGE

Clips, Clamps, Spacers & Tools



Fixing Clip For Rigid Pipe

1100	Tube OD mm
6697.17.00	16.5
6697.25.00	25
6697.40.00	40
6697.50.00	50
6697.63.00	63



Transair Clips & Spacers

1100	Description
6697.00.03	Spacer Block for Fixing Clip
6697.00.02	Clip Adaptor for Rod M8 x 1 Male x M10 x 1.5 Female



Transair Beam Clamps

1100	Description
6699.03.01	Screw Type Beam Clamp 16.5mm to 40mm
ER99.06.02	Screw Type Beam Clamp 63mm to 100mm for M8 Screw
ER99.06.03	Screw Type Beam Clamp 63mm to 100mm for M10 Screw



Transair Tube Cutter

1100	Description
6698.03.01	Tube Cutter for 16.5mm to 63mm Pipe



Transair Tools

1100	Description
6698.04.02	Deburring Tool for Rigid Aluminium Pipe 16.5mm to 100mm
6698.04.01	Chamfer Tool for Rigid Aluminium Pipe 16.5mm to 40mm
6698.04.03	Marking Tool for Rigid Aluminium Pipe 16.5mm to 40mm
6698.05.03	Tightening Spanners for 63mm Nuts



Transair Drilling Jig

1100	Description
6698.01.03	Drilling Jig 25 to 63mm



Transair Drilling Tool


1100	Description
6698.02.02	Drilling Tool for 25mm Pipe
6698.02.01	Drilling Tool for 40mm & 63mm Pipe



Tool Case

1100	Description
6698.00.05	Complete Kit 16.5mm to 63mm

For **Parker Rectus QRC's** see pages **330-390**




Fluid-Air Components Ltd

aircom PIPINGSYSTEM

WHY CHOOSE AIRCOM?





EXPANDABILITY ACCORDING TO REQUIREMENTS

The system grows with the plant.

ELIMINATE WASTED AIR AND LEAKS

Our components in aluminium, technopolymer and HIP guarantee superior, above-average performance.

EASY, RAPID INSTALLATION

Reduction in labor costs and ease of intervention.

MODULAR DESIGN

Flexibility of use and greater adaptability to the specific usage requirements.

OPTIMUM, CONSTANT PERFORMANCE

Constant energy savings over time.

OUR SERVICES

AIRCOM services support our Partners throughout the plant's entire life cycle: from the initial consultancy to support during design.

TECHNICAL TRAINING

We offer advanced training and periodic update courses for our Partners' technical personnel (designers, installers, dealers).

SUPPORT FOR DESIGNERS

We support our Partners at every step, from the more basic plants to the highly complex systems, assisting in totally new designs as well as in revamping and additions to existing structures.

RATIONALISING ENERGY CONSUMPTION

Thanks to the wide choice of components and the flexibilit of the systems, as well as to computer simulations, our piping systems help reduce energy costs to the lowest levels possible, in a consistent manner over time: the system pays for itself.

ADVANCED SOFTWARE

We have developed proprietary software to provide support in plant sizing and on site design. Thanks to this software, our Partners can offer the end user a complete, efficient and personalized service.

RINA TÜV ASME ISO CE

1068

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

RING MAIN SYSTEM

Coated Aluminium Pipe



Compressed Air, 5.8 Metres, Blue

9191	Ø mm
QLTUAL020S	20
QLTUAL025S	25
QLTUAL032S	32
QLTUAL040S	40
QLTUAL050S	50
QLTUAL063S	63
QLTUAL080S	80
QLTUAL110S	110
Tech Sheet 110821	

Compressed Air, 4 Metres, Blue

9191	Ø mm
QLTUAL4016S	16
QLTUAL4020S	20
QLTUAL4025S	25
QLTUAL4032S	32
QLTUAL4040S	40
QLTUAL4050S	50
QLTUAL4063S	63
Tech Sheet 110821	




Vacuum, 5.8 Metres, Grey

9191	Ø mm
QLTUALGY020S	20
QLTUALGY025S	25
QLTUALGY032S	32
QLTUALGY040S	40
QLTUALGY050S	50
QLTUALGY063S	63
QLTUALGY080S	80
Tech Sheet 110821	



Nitrogen, 5.8 Metres, Green

9191	Ø mm
QLTUALG020S	20
QLTUALG025S	25
QLTUALG040S	40
QLTUALG063S	63
Tech Sheet 110821	



Double Bend

9191	Ø mm
QLSCI016	16
QLSCI020	20
QLSCI025	25
Tech Sheet 110821	

Multilayer Bendable Pipe



Compressed Air, 50 Metres

9191	Ø mm
QLTUMLST016	16
QLTUMLST020	20
QLTUMLST025	25
Tech Sheet 110841	

Technopolymer Pipe



Compressed Air, 4 Metres

9191	Ø mm
AIRTU020S	20
AIRTU025S	25
AIRTU032S	32
AIRTU040S	40
Tech Sheet 110842	

RIDGID

You might also need
Pipe & Tube Cutters
see pages **1743-1746**



Free design services available for reducing energy costs

Fluid-Air Components Ltd

TECHNOPOLYMER SYSTEM



LIGHTWEIGHT, BUT POWERFUL

The Quick Line technopolymer product range comes in the following diameters:

16, 20, 25, 32, 40, 50 and 63 mm

A careful study and design of dimensions and materials enable us to achieve a light and functional, all-technopolymer product in a wide range of sizes, allowing you to create your aluminium tubing systems without any problems.

ENERGY SAVING

SHORT INSTALLATION TIME

The quick and easy assembly of our piping systems is the result of an innovative technology, with an instant connection of the fitting components to the aluminium pipe.

AIR QUALITY AND MAINTENANCE


Owing to full technopolymer construction, air quality keeps constant features from compressor outlet up to all end user points. Minimum roughness of internal pipe surfaces allows optimal air flo .The high quality and high resistance features of our fittings will significantly reduce maintenance costs

MODULARITY AND RESISTANCE

Our modular and lightweight technopolymer systems are an optimal solution to reduce installation time.

Owing to careful study of components and of materials, our fittings feature noticeable resistance to corrosion, mechanical shocks and thermal variations.

Quick Line technopolymer is the most advanced evolution in the field o systems for compressed air and pressurised fluids distribution



1070

TECHNOPOLYMER SYSTEM FITTINGS

Technopolymer fittings are specifically designed for use with Aluminium ube up to Ø 63mm.
For specific application guidance please speak to our echnical team.

Working Temperature:
-15°C to +65°C

Straight Couplings



Equal, Tube x Tube

9183	Ø mm
QLMAPA016	16
QLMAPA020	20
QLMAPA025	25
QLMAPA032	32
QLMAPA040	40
QLMAPA050	50
QLMAPA063	63
Tech Sheet 110822	



Reducer, Tube x Tube

9183	Ø mm	Ø mm
QLRIDPA025020	25	20
QLRIDPA032025	32	25
QLRIDPA040025	40	25
QLRIDPA040032	40	32
QLRIDPA050040	50	40
Tech Sheet 110822		



Sliding Coupling Tube x Tube (No Internal Stopper)

9183	Ø mm
QLMASPA032	32
QLMASPA040	40
QLMASPA050	50
QLMASPA063	63
Tech Sheet 110822	



Male Stud, BSPT Thread x Tube

9183	Ø mm	Thread
QLMNPA016048	16	1/2"
QLMNPA020048	20	1/2"
QLMNPA020068	20	3/4"
QLMNPA025048	25	1/2"
QLMNPA025068	25	3/4"
QLMNPA025088	25	1"
QLMNPA032088	32	1"
QLMNPA032108	32	1.1/4"
QLMNPA040088	40	1"
QLMNPA040108	40	1 .1/4"
QLMNPA040128	40	1.1/2"
QLMNPA050128	50	1.1/2"
QLMNPA050168	50	2"
QLMNPA063168	63	2"
Tech Sheet 110822		

FT PRO

For **Air Receivers**
see pages **433-434**



Elbows



90° Equal, Tube x Tube

9183	Ø mm
QLGO90PA016	16
QLGO90PA020	20
QLGO90PA025	25
QLGO90PA032	32
QLGO90PA040	40
QLGO90PA050	50
QLGO90PA063	63
Tech Sheet 110822	



45° Equal, Tube x Tube

9183	Ø mm
QLGO45PA020	20
QLGO45PA025	25
QLGO45PA032	32
QLGO45PA040	40
QLGO45PA050	50
QLGO45PA063	63
Tech Sheet 110822	



90° Male Stud, BSPT x Tube

9183	Ø mm	Thread
QLGO90PM020048	20	1/2"
QLGO90PM025048	25	1/2"
QLGO90PM025068	25	3/4"
Tech Sheet 110822		

Free design services available for reducing energy costs

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TECHNOPOLYMER SYSTEM FITTINGS

Technopolymer fittings are specifically designed for use with Aluminium ube up to Ø 63mm.
For specific application guidance please speak to our echnical team.

Working Temperature:
-15°C to +65°C

Tees



Equal Tube x Tube

9183	Ø mm
QLTEPA016	16
QLTEPA020	20
QLTEPA025	25
QLTEPA032	32
QLTEPA040	40
QLTEPA050	50
QLTEPA063	63
Tech Sheet 110822	



Unequal, Reducing on Branch, Tube x Tube

9183	Ø mm	Ø mm
QLTRPA020016	20	16
QLTRPA025016	25	16
QLTRPA025020	25	20
QLTRPA032020	32	20
QLTRPA032025	32	25
QLTRPA040020	40	20
QLTRPA040025	40	25
QLTRPA040032	40	32
QLTRPA050020	50	20
QLTRPA050025	50	25
QLTRPA050032	50	32
QLTRPA050040	50	40
QLTRPA063020	63	20
QLTRPA063025	63	25
QLTRPA063040	63	40
QLTRPA063050	63	50
Tech Sheet 110822		



Female Stud BSPP, 3.06 mm, Branch x Tube

9183	Ø mm	Thread
QLTPPA020048	20	1/2"
QLTPPA025048	25	1/2"
Tech Sheet 110822		

Quick Branch, Saddle Clamp



Tube x Tube

9183	Ø mm	Ø mm
QLDERPA025016	25	16
QLDERPA025020	25	20
QLDERPA032016	32	16
QLDERPA032020	32	20
QLDERPA040016	40	16
QLDERPA040020	40	20
QLDERPA040025	40	25
QLDERPA050016	50	16
QLDERPA050020	50	20
QLDERPA050025	50	25
QLDERPA063020	63	20
QLDERPA063025	63	25
QLDERPA063032	63	32
QLDERPA080020	80	20
QLDERPA080025	80	25
QLDERPA080032	80	32
QLDERPA110025	110	25
QLDERPA110032	110	32
Tech Sheet 110822		



Female BSPP x Tube

9183	Ø mm	Thread
DIRDERFF025048	25	1/2"
DIRDERFF032048	32	1/2"
DIRDERFF040048	40	1/2"
DIRDERFF040068	40	3/4"
DIRDERFF050048	50	1/2"
DIRDERFF050068	50	3/4"
DIRDERFF063048	63	1/2"
DIRDERFF063068	63	3/4"
DIRDERFF063088	63	1"
DIRDERFF080048	80	1/2"
DIRDERFF080068	80	3/4"
DIRDERFF080088	80	1"
DIRDERFF110068	110	3/4"
DIRDERFF110088	110	1"
Tech Sheet 110822		

End Caps



Tube

9183	Ø mm
QLCAPA016	16
QLCAPA020	20
QLCAPA025	25
QLCAPA032	32
QLCAPA040	40
QLCAPA050	50
QLCAPA063	63
Tech Sheet 110822	

Assembly Tools



QL Nut Wrench

9183	Ø mm	Ø mm
QLCLE16020	16	20
QLCLE25032	25	32
QLCLE40050	40	50
QLCLE63	63	63
Tech Sheet 110822		



Pipe Fitting Insertion Meter

9183	Ø mm	Ø mm
QLMIS016080	16	80
Tech Sheet 110822		

Free design services available for reducing energy costs

Fluid-Air Components Ltd

VALVES

Ball Valve Stainless Steel



Tube x Tube

9183	Ø mm
QLVAINOX025	25
QLVAINOX032	32
QLVAINOX040	40
QLVAINOX050	50
QLVAINOX063	63
QLVAINOX080	80
Tech Sheet 110823	



Female BSPP x Tube

9183	Ø mm	Thread
QLVAINOXMF025088	25	1"
QLVAINOXMF032128	32	1.1/2"
QLVAINOXMF040128	40	1.1/2"
QLVAINOXMF050168	50	2"
QLVAINOXMF063168	63	2"
QLVAINOXMF080248	80	2"
Tech Sheet 110823		

Ball Valve Nickel Plated Brass



Female BSPP x Tube

9183	Ø mm	Thread
QLVAF016048	16	1/2"
QLVAF020048AL	20	1/2"
QLVAF025068AL	25	3/4"
Tech Sheet 110823		



Male BSPT x Tube

9183	Ø mm	Thread
QLVAM016048	16	1/2"
QLVAM020048AL	20	1/2"
QLVAM025068AL	25	3/4"
Tech Sheet 110823		

Butterfly alve Stainless Steel



Tube x Tube

9183	Ø mm
QLVALFAR110	110
Tech Sheet 110823	



For **Ball Valves**
see pages **922-955**

Free design services available for reducing energy costs

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

aircom PIPINGSYSTEM

ALUMINIUM SYSTEM



LIGHTWEIGHT, BUT POWERFUL

The Quick Line aluminium product range comes in the following diameters:

20, 25, 32, 40, 50, 63, 80, and 110 mm

A careful study and design of dimensions and materials enable us to achieve a lightweight but powerful, all-aluminium product in a wide range of sizes. With the Ø 110 mm size you will have a powerful flow rate potential, allowing you to create compressor rooms without any problems.

ENERGY SAVING

SHORT INSTALLATION TIME

The quick and easy assembly of our piping systems is the result of an innovative technology, with an instant connection of the fitting components to the aluminium pipe.

AIR QUALITY AND MAINTENANCE


Owing to full aluminium construction,air quality keeps constant features from compressor outlet up to all end user points. Minimum roughness of internal pipe surfaces allows optimal air flo .The high quality and high resistance features of our fittings will significantly reduce maintenance costs

MODULARITY AND RESISTANCE

Our modular and lightweight aluminium systems are an optimal solution to reduce installation time.

Owing to careful study of components and of materials, our fittings feature noticeable resistance to corrosion, mechanical shocks and thermal variations.

Quick Line aluminium is the most advanced evolution in the field o systems for compressed air and pressurised fluids distribution



1074

FITTINGS, ALUMINIUM SYSTEM

Swap your Aluminium fittings for echnopolymer fittings for sizes up to Ø 63mm to reduce installation costs. For specific application guidance please speak to our echnical team.

Working Temperature:
-30°C to +80°C

Straight Couplings



Equal, Tube x Tube

9183	Ø mm
QLMAAL020	20
QLMAAL025	25
QLMAAL032	32
QLMAAL040	40
QLMAAL050	50
QLMAAL063	63
QLMAAL080	80
QLMAAL110	110
Tech Sheet 110824	



Sliding Coupling, Tube x Tube (No Internal Stopper)

9183	Ø mm
QLMASAL032	32
QLMASAL040	40
QLMASAL050	50
QLMASAL063	63
QLMASAL080	80
Tech Sheet 110824	



Female Stud, BSPP Thread x Tube

9183	Ø mm	Thread
QLMPMAL020048	20	1/2"
QLMPMAL020068	20	3/4"
QLMPMAL025068	25	3/4"
QLMPMAL025088	25	1"
QLMPMAL032108	32	1.1/4"
QLMPMAL040128	40	1.1/2"
QLMPMAL050168	50	2"
QLMPMAL063208	63	2.1/2"
Tech Sheet 110824		



Male Stud, BSPT Thread x Tube

9183	Ø mm	Thread
QLMNMAL020048	20	1/2"
QLMNMAL020068	20	3/4"
QLMNMAL025068	25	3/4"
QLMNMAL025088	25	1"
QLMNMAL032108	32	1.1/4"
QLMNMAL040128	40	1.1/2"
QLMNMAL050168	50	2"
QLMNMAL063168	63	2"
QLMNMAL063208	63	2.1/2"
QLMNMAL080208	80	2.1/2"
QLMNMAL080248	80	3"
Tech Sheet 110824		

Elbows



90° Equal, Tube x Tube

9183	Ø mm
QLGO90AL020	20
QLGO90AL025	25
QLGO90AL032	32
QLGO90AL040	40
QLGO90AL050	50
QLGO90AL063	63
QLGO90AL080	80
QLGO90AL110	110
Tech Sheet 110824	



45° Equal, Tube x Tube

9183	Ø mm
QLGO45AL020	20
QLGO45AL025	25
QLGO45AL032	32
QLGO45AL040	40
Tech Sheet 110824	



45° Female Stud, BSPP x Tube

9183	Ø mm	Thread
QLGO45FAL020048	20	1/2"
QLGO45FAL025048	25	1/2"
QLGO45FAL025068	25	3/4"
Tech Sheet 110824		



90° Male Stud, BSPT x Tube

9183	Ø mm	Thread
QLGO90MAL020048	20	1/2"
QLGO90MAL025048	25	1/2"
QLGO90MAL025068	25	3/4"
Tech Sheet 110824		

Free design services available for reducing energy costs

FITTINGS, ALUMINIUM SYSTEM

Tees



Equal, Tube x Tube

9183	Ø mm
QLTEAL020	20
QLTEAL025	25
QLTEAL032	32
QLTEAL040	40
QLTEAL050	50
QLTEAL063	63
QLTEAL080	80
QLTEAL110	110
Tech Sheet 110824	



Unequal, Reducing on Branch, Tube x Tube

9183	Ø mm	Ø mm
QLTRAL025020	25	20
QLTRAL032020	32	20
QLTRAL040020	40	20
QLTRAL040025	40	25
Tech Sheet 110824		



Female Stud BSPP, Branch x Tube

9183	Ø mm	Thread
QLTPAL020048	20	1/2"
QLTPAL025068	25	3/4"
QLTPAL032088	32	1"
QLTPAL040108	40	1.1/4"
QLTPAL050128	50	1.1/2"
QLTPAL063168	63	2"
QLTPAL080208	80	2.1/2"
QLTPAL110248	110	3"
Tech Sheet 110824		

End Caps



Equal, Tube x Tube

9183	Ø mm
QLCAAL020	20
QLCAAL025	25
QLCAAL032	32
QLCAAL040	40
QLCAAL050	50
QLCAAL063	63
QLCAAL080	80
Tech Sheet 110824	

Blind Flange



Tube

9183	Ø mm
DIRFC110DIN	110
Tech Sheet 110824	

Quick Branch (Saddle Clamp)



Tube x Tube

9183	Ø mm	Ø mm
QLDERAL025020	25	20
QLDERAL032020	32	20
QLDERAL040020	40	20
QLDERAL040025	40	25
QLDERAL050020	50	20
QLDERAL050025	50	25
QLDERAL063020	63	20
QLDERAL063025	63	25
QLDERAL063032	63	32
QLDERAL080020	80	20
QLDERAL080025	80	25
QLDERAL080032	80	32
QLDERAL110020	110	20
QLDERAL110025	110	25
QLDERAL110032	110	32
Tech Sheet 110824		

Flanged Couplings



Flange x Tube

9183	Ø mm	DIN Flange
QLMFLAL080248DIN	80	3"
QLMFLAL110328DIN	110	4"
Tech Sheet 110824		



Flange x Stem

9183	Ø mm	DIN Flange
QLTFLAL80248DIN	80	3"
QLTFLAL110328DIN	110	4"
Tech Sheet 110824		

Assembly Tools



QL Nut Wrench for Aluminium

9183	Ø mm	Ø mm
QLCLEAL020025	20	25
QLCLEAL032040	32	40
QLCLEAL050	50	50
QLCLEAL063	63	63
QLCLEAL080	80	80
Tech Sheet 110824		



Pipe Fitting Insertion Meter

9183	Ø mm	Ø mm
QLMISAL020110	20	110
Tech Sheet 110824		

Free design services available for reducing energy costs

Fluid-Air Components Ltd

6" (168.3MM) TUBING & FITTINGS SYSTEM

A full range of ready-to-use, pre-grooved 168.3 mm - 6" aluminium products.

In large industrial sites, main compressed air distribution networks need a flow rate of 3,000 ^{3} per hour.

Compatibility and Specification
Deliverable Fluids:
- Compressed air
- Inert gases
- Vacuum
- Other (please contact sales office for more information

Vacuum Level:
99% (about 10 mbar) approximately

Working Temperature:
-30°C to +80°C

Maximum Working Pressure:
12 bar

Coated Aluminium Pipe with Grooved Ends



Compressed Air, 5.8 Metres, Blue

9260	Ø mm
QLTUAL168S	168.3
Tech Sheet 110825	

Elbow with Grooved Ends



90° Equal, Tube x Tube

9260	Ø mm
QLGO90AL168	168.3
Tech Sheet 110825	



45° Equal, Tube x Tube

9260	Ø mm
QLGO45AL168	168.3
Tech Sheet 110825	

Tee with Grooved Ends



Equal, Tube x Tube

9260	Ø mm
QLTEAL168	168.3
Tech Sheet 110825	

Straight Rigid Coupling with Grooved Ends



Equal, Tube x Tube

9260	Ø mm
QLMAAL168	168.3
Tech Sheet 110825	

End Caps with Grooved Ends



Tube

9260	Ø mm
QLCAAL168	168.3
Tech Sheet 110825	

Expansion Joint



Flanged DIN

9260	Ø mm
DIRDIL168DIN	168.3
Tech Sheet 110825	

DIRDIL168DIN requires 1x QLFLA168480DIN on each side.

Flanged Adaptor



Tube x Flange DIN

9260	Ø mm	DIN Flange
QLFLA168480DIN	168.3	4"
Tech Sheet 110825		

Butterfly alve



Flange DIN Coupling

9260	Ø mm
QLVALFAR168	168.3
Tech Sheet 110825	

Pipe Bracket



M10 Insert Pieces

9260	Ø mm	Insert
DIRFEM10168CF	168.3	M10
Tech Sheet 110825		

Portable Manual Grooving Tool for 6" (168.3 mm) Tube



Manual Operation with Ratchet Handle

9260	Ø mm
DIRRULLUNI	168.3
Tech Sheet 110825	

MANIFOLDS, ALUMINIUM TUBING SYSTEM

Single Port



1/2" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
DIRAPMAL048048	1	1
Tech Sheet 110826		



With Fitting Holder Safety Block

9183	Inlet mm	Outlet
DAPGO45FAL020048	20	1/2"
DAPGO45FAL025048	25	1/2"
DAPGO45FAL025068	25	3/4"
Tech Sheet 110826		

Double Port



1/2" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
APLALL048	1	2
Tech Sheet 110826		

3/4" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
APLALL068	1	2
Tech Sheet 110826		

3 Port



1/2" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
DIRAPFRLAL048048	1	3
Tech Sheet 110826		

4 Port



1/2" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
DIRAPLAL048048	1	4
Tech Sheet 110826		

3/4" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
DIRAPLAL068068	1	4
Tech Sheet 110826		

5 Port



3/4" BSPP Inlet x 3/4" & 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets A (side)	No. of Outlet B (front)
DIRPMUAL120	1	2	3
Tech Sheet 110826			

6 Port



3/4" BSPP Inlet x 3/8" BSPP Outlet, No Drain

9183	No. of Inlets	No. of Outlets
APLALLMUL068038	1	6
Tech Sheet 110826		

1/2" BSPP Inlet x 3/4" BSPP Outlet, No Drain

9183	No. of Inlets	No. of Outlets
APLALLMUL068048	1	6
Tech Sheet 110826		

7 Port



3/4" BSPP Inlet x 1/2" BSPP Outlet, with Drain Option, 1/4" (Blind)

9183	No. of Inlets	No. of Outlets
DIRPMUAL200	1	7
Tech Sheet 110826		

Drain Valve



1/4" BSPP Male

9183	Thread
DIRVSP028	1/4"
Tech Sheet 110826	

Free design services available for reducing energy costs

Fluid-Air Components Ltd


SYSTEM ACCESSORIES

Pipe Brackets



M8 Insert Pieces

9183	Ø mm	Insert
DIRFEM8016CF	16	M8
DIRFEM8020CF	20	M8
DIRFEM8025CF	25	M8
DIRFEM8032CF	32	M8
DIRFEM8040CF	40	M8
DIRFEM8050CF	50	M8
DIRFEM8063CF	63	M8
DIRFEM8080CF	80	M8
DIRFEM8110CF	110	M8
Tech Sheet 110827		



Pipe Bracket Spacers

9183	Ø mm	Ø mm
DIRSPE020032	20	32
DIRSPE040063	40	63
Tech Sheet 110827		

Assembly Lubrication



Lubrication Fluid (Oil Free)

9183	Size ml
DIRLUB0750	750
Tech Sheet 110844	



Lubrication Gel (Oil Free)

9183	Size ml
DIRLUBGEL0950	950
Tech Sheet 110827	

Aluminium Spigots



Male BSPP x Stem

9183	Ø mm	Thread
QLPUNM016038	16	3/8"
QLPUNM020048	20	1/2"
QLPUNM020068	20	3/4"
QLPUNM025088	25	1"
QLPUNM032108	32	1.1/4"
QLPUNM040128	40	1.1/2"
QLPUNM050168	50	2"
QLPUNM063168	63	2"
QLPUNM080248	80	3"
Tech Sheet 110827		

Reduction Pipe



Stem x Stem

9183	Ø mm	Ø mm
QLRIDTU025020	25	20
QLRIDTU032020	32	20
QLRIDTU032025	32	25
QLRIDTU040025	40	25
QLRIDTU040032	40	32
QLRIDTU050032	50	32
QLRIDTU050040	50	40
QLRIDTU063040	63	40
QLRIDTU063050	63	50
QLRIDTU080050	80	50
QLRIDTU080063	80	63
QLRIDTU110050	110	50
QLRIDTU110063	110	63
QLRIDTU110080	110	80
Tech Sheet 110827		

Deburrers



To suit Tube Sizes 16mm - 110mm

9183	Ø mm	Ø mm
DIRSM016050	16	50
DIRSM063110	63	110
Tech Sheet 110827		



To suit Tube Sizes 16mm - 168.3mm

9183	Ø mm	Nominal Bore mm
DIRSBVUNI	16	168.3
Tech Sheet 110827		

Multilayer Pipe Bending Tools



Bending Gun

9260	Ø mm	Ø mm
DIRPIEGTMLS1625	16	25
Tech Sheet		



Calibrator & Chamfering Tool

9260	Ø mm	Ø mm
DIRCALML016025	16	25
Tech Sheet 110827		



Outer Bending Spring

9260	Ø mm
DIRMOLMLEST016	16
DIRMOLMLEST020	20
DIRMOLMLEST025	25
Tech Sheet 110827	



Inner Bending Spring

9260	Ø mm
DIRMOLMLINT016	16
DIRMOLMLINT020	20
DIRMOLMLINT025	25
Tech Sheet 110827	

Flexible Hoses




Stem x Stem

9183	Ø mm
QLFLEX020	20
QLFLEX025	25
QLFLEX032	32
QLFLEX040	40
QLFLEX063	63
Tech Sheet 110827	

Free design services available for reducing energy costs

Fluid-Air Components Ltd



MULTILAYER BENDABLE PIPE

Bendable, resistant & specific for compressed air

Due to its unique structure, Aircom's multilayer pipe for compressed air delivers excellent physical and chemical features, typical of PE-RT.


The structure of the multilayer pipe incorporates an aluminium layer, providing resistance to high pressures and high operating temperatures.

The lightness of the material enables easy shaping of piping sections, making installation trouble-free even in problem areas.

AIRCOM'S MULTILAYER PIPE ADVANTAGES

- ✔ Specifically for compressed air piping.
- ✔ Easy creation of shaped piping sections.
- ✔ Easy to fit around obstacles, corners, pillars, etc.
- ✔ Easy installation owing to its bendability.
- ✔ Linear thermal expansion factor similar to aluminium pipe.
- ✔ Corrosion resistant.
- ✔ Outstanding durability.

LAYERS AND MATERIALS



- **A** PE-RT (inner layer, colourless)
- **B** Adhesive layer
- **C** Aluminium layer, overlapped and ultrasonic welded
- **D** Adhesive layer
- **E** PE-RT (outer layer, blue)

Fluid-Air Components Ltd



AIR PIPE LINE “INFINITY“ SERIES

Complete selection of fittings and aluminum pipes fo air networks.

Patented drop fitting solution and more special features

Fastest assembly operations with ready-to-use and reusable fittings for all sizes

10 year warranty.

MADE IN ITALY

AIGNEP

EXCELLENT SOLUTIONS IN FLUIDTECHNOLOGY

1081

ALUMINIUM RING MAIN SYSTEM

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 16 bar


Material: Adaptors: Brass, Nickel Plated (Ø 50-63 Aluminium),Nitrile Seals Silicone free

Application: Compressed air, Vacuum, Inert gas (NITROGEN-ARGON)

Compliance: 2014/68/EU(PED), REACH EC N°1907/2006, ROHS 2011/65/EU, ASME B31.1, B31.3

Aluminium Tubing

Tubing may take up to 3 working days to be delivered, dependant on weight and delivery address location. Addition carriage charges may apply. For full details please contact sales.



4 Metre Lengths

0255	OD mm
900000011Y9B5	20
900000011J4B5	25
900000011J9B5	32
900000011K4B5	40
900000011W0B5	50
900000011W3B5	63
Tech Sheet 1609	

6 Metre Lengths

0255	OD mm
900006020BL	20
900006025BL	25
900006032BL	32
900006040BL	40
900006050BL	50
900006063BL	63
Tech Sheet 1609	

Straight Adaptors



Male Thread, BSPT

0255	OD mm	Thread
9001000001	20	1/2"
9001000009	20	3/4"
9001000011	25	1/2"
9001000002	25	3/4"
9001000003	32	1"
9001000013	40	1"
9001000004	40	1.1/4"
9001000007	40	1.1/2"
9001000014	50	1"
9001000005	50	1.1/2"
9001000012	50	2"
9001000006	63	2"
9001000008A	63	2.1/2"
Tech Sheet 1610		



Female Thread, BSPP

0255	OD mm	Thread
9003000001	20	1/2"
9003000002	25	3/4"
9003000003	32	1"
9003000004	40	1.1/4"
Tech Sheet 1610		

Elbow Adaptors



Male Thread, BSPT

0255	OD mm	Thread
9015000001	20	1/2"
9015000002	25	3/4"
9015000003	32	1"
Tech Sheet 1611		



Female Thread, BSPP

0255	OD mm	Thread
9016000001	20	1/2"
9016000002	25	3/4"
9016000003	32	1"
9016000004	40	1.1/4"
Tech Sheet 1611		



Bracketed, Female Thread, BSPP

0255	OD mm	Thread
9060000001	20	1/2"
9060000002	25	3/4"
9060000003	32	1"
Tech Sheet 1611		

Tee Adaptors



Female Thread, BSPP

0255	OD mm	Thread
9023600006	20	3/8"
9023600007	20	1/2"
9023600001	25	3/8"
9023600008	25	1/2"
9023600002	32	1/2"
9023600003	40	1/2"
9023600017A	63	1/2"
9023600005	63	3/4"
9023600018A	63	1"
Tech Sheet 10557		

Tee Adaptors with Condense Exhaust



Female Thread, BSPP

0255	OD mm	Thread
9025000017A	63	1/2"
Tech Sheet 10557		

Straight Connectors



Equal

0255	OD mm
9004000001	20
9004000002	25
9004000003	32
9004000004	40
9004000006	63
Tech Sheet 1614	

Fluid-Air Components Ltd

ALUMINIUM RING MAIN SYSTEM

Elbow Connectors



Equal 90°

0255	OD mm
9013000001	20
9013000002	25
9013000003	32
9013000004	40
9013000005	50
9013000006	63
Tech Sheet 1611	



Equal 135°

0255	OD mm
9014000001	20
9014000002	25
9014000003	32
9014000004	40
9014000005	50
Tech Sheet 1611	

Tee Connectors



Equal

0255	OD mm
9023000001	20
9023000002	25
9023000003	32
9023000004	40
9023000005	50
9023000006	63
Tech Sheet 10559	



Equal and Reducing Branch

0255	OD mm	OD mm
9023500013	20	20
9023500001	25	20
9023500002	32	20
9023500003	32	25
9023500004	40	20
9023500005	40	25
9023500008	50	25
Tech Sheet 10564		

Tee Connectors with Condense Exhaust



Equal and Reducing Branch

0255	OD mm
9025900001	20-20-20
9025900002	25-20-25
9025900003	32-20-32
9025900004	40-20-40
9025900005	50-20-50
Tech Sheet 10559	

End Caps



0255	OD mm
9061000001	20
9061000002	25
9061000003	32
9061000004	40
9061000006	63
Tech Sheet 1612	

Reducers



0255	OD mm	OD mm
9062000001	25	20
9062000002	32	20
9062000003	32	25
9062000005	40	25
9062000006	40	32
9062000011	50	25
9062000007	50	32
9062000008	50	40
9062000009A	63	40
9062000010A	63	50
Tech Sheet 1613		

Deburring Tool



For Aluminium Tubing 20-40mm

0255
9088000001

Support Collars



Technopolymer, M6 Thread

0255	OD mm
9081500001	20
9081500002	25
9081500003	32
9081500004	40
9081500005	50
9081500006	63
Tech Sheet 10567	



Spacer

0255
9081700001
Tech Sheet 60110

Wall Mount Female Manifolds, Aluminium



BSPP

0255	OD mm	Thread
9060200001	20	1/2"
9060200002	25	1/2"
Tech Sheet 10560		



2 Way, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
9064200001	1/2"	1/2"	2
9064200002	3/4"	1/2"	2
Tech Sheet 10576			



4 Way, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
9064400001	1/2"	1/2"	4
9064400002	3/4"	1/2"	4
Tech Sheet 10577			

Fluid-Air Components Ltd

ALUMINIUM RING MAIN SYSTEM

Wall Mount Female Manifolds, Plastic

Working Temperature: -20°C to +50°C

Maximum Working Pressure: 15 bar



Type VDK 10, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK10	1/2"	1/2"	1



Type VDK 138, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK138	1/2"	3/8"	1



Type VDK 20, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK20	1/2"	1/2"	2



Type VDK 21, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK21	2 x 1/2"	1/2"	2



Type VDK 30, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK30	3/4"	1/2"	3



Type VDK 31, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK31	2 x 3/4"	1/2"	3



Type VDK 34, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK34	1/2"	1/2"	3



Type VDK 35, BSPP

0255	Inlet Size	Outlet Size	No of Outlets
VDK35	2 x 1/2"	1/2"	3

Saddle Clamp Connectors



0255	OD A mm	OD B mm
9024000004	32	25
9024000006	40	25
9024000007	50	20
9024000010	63	20
9024000011	63	25
Tech Sheet 10565		

Tube Drilling Jigs & Drill Bits



Tube Drilling Jigs

0255	OD mm
9024200001	32
9024200002	40
9024200004	63
Tech Sheet 10567	



Drill Bits for Drilling Jig

0255	To Suit
9024100001	32 & 40
9024100002	50 & 63
Tech Sheet 10566	

Ball Valves



Tube x Tube

0255	OD mm
9070000001	20
9070000002	25
9070000003	32
9070000004	40
9070000005	50
9070000006	63
Tech Sheet 10570	



Tube x Male Thread, BSPT

0255	OD mm	Thread
9072000001	20	1/2"
9072000002	25	3/4"
Tech Sheet 10572		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIRNET PIPEWORK SYSTEM

Airnet Aluminium Air Pipe



Blue Compressed Air Pipe, 5.70m Lengths

1450	Size mm	Length Metres	Quantity
2811-4000-05	40	5.70	5



Blue S Bends

1450	Size mm
2811-1067-05	20 x 440
2811-2067-05	25 x 460

Airnet Connectors



Equal Straight Connector

1450	Size mm
2811-1002-80	20
2811-2002-80	25
2811-4002-80	40
2811-5002-80	50



Reducing Straight Connector

1450	Size mm
2811-2121-80	25 to 20
2811-4221-80	40 to 25



Male Stud Connector

1450	Size
2811-1017-80	20mm x R1/2"
2811-2117-80	25mm x R3/4"
2811-2217-80	25mm x R1"
2811-4417-80	40mm x R1.1/2"
2811-5417-80	50mm x R1.1/2"
2811-5517-80	50mm x R2"
2811-6517-80	63mm x R2"
2811-6617-80	63mm x R2.1/2"
2811-7717-80	80mm x R3"



Wall Mounting Connector ISO228

1450	Inlet mm	Outlet BSPP
2811-1023-80	20	1/2" x 3
2811-2023-80	25	1/2" x 3



Wall Mounting Connector Threaded

1450	Inlet	Outlet
2811-0025-80	1/2"	1/2" x 1
2811-1025-80	3/4"	1/2" x 1



End Cap

1450	Size mm
2811-1006-80	20
2811-2006-80	25
2811-4006-80	40
2811-5006-80	50

FT PRO

For **Condensate Management** see page **435**



Fluid-Air Components Ltd

AIRNET PIPEWORK SYSTEM

Airnet Elbows & Tees



Equal 90° Elbow

1450	Size mm
2811-1003-80	20
2811-2003-80	25
2811-4003-80	40
2811-5003-80	50
2811-6003-80	63



Equal 45° Elbow

1450	Size mm
2811-2004-80	25
2811-4004-80	40



Equal Tee

1450	Size mm
2811-1005-80	20
2811-2005-80	25
2811-4005-80	40



Reducing Tee

1450	Size A mm	Size B mm
2811-4107-80	40	20
2811-4207-80	40	25



Reducing Tee, Threaded Branch

1450	Inlet/Outlet mm	Reduced Branch
2811-1008-80	20	G1/2"
2811-2008-80	25	G1/2"
2811-2108-80	25	G3/4"
2811-4208-80	40	G1"
2811-5208-80	50	G1"



For **Air Receivers & Accessories**
see pages **433-435**

Airnet Quickdrops & Ball Valves



Quickdrop

1450	Inlet mm	Outlet mm
2811-2110-80	25	20
2811-4110-80	40	20



Quickdrop, Threaded Outlet

1450	Inlet mm	Outlet
2811-2011-80	25	G1/2"



Ball Valve

1450	Size mm
2811-1051-81	20
2811-2051-81	25
2811-4051-81	40



Ball Valve Airnet to ISO228 Female

1450	Size
2811-1152-81	20mm x G3/4"
2811-2252-81	25mm x G1"
2811-4452-81	40mm x G1.1/2"

Fluid-Air Components Ltd

AIRNET PIPEWORK SYSTEM

Airnet Piping Accessories



Pipe Clips

1450	Size mm	Connection
2811-1022-20	20	M6
2811-2022-20	25	M6
2811-4022-20	40	M6



Screw Beam Clamp

1450	Size	Range mm
2810-0036-10	M8	1.5 - 11



Hang Clamp H Profil

1450	Size	Range mm
2810-0038-10	M8	1.5 - 4



Sealing Gel

1450	Volume Litres
2810-0148-00	1

Airnet Installation Tool Kits



PF Series Installation Spanner

1450	Size mm
2811-1028-00	20 - 50



Black Series Installation Spanner

1450	Size mm
2811-6028-00	63 - 80



Belt Spanner

1450	Description
2810-8028-00	Covers 40 - 80 mm



Pipe Deburrer

1450	Size mm
2810-0141-00	20 - 50



Hole Deburrer Pen

1450	Type
2810-0641-00	Heavy-duty



PF Series Tool Kit

1450	Size mm
2811-0045-00	Install Kit to suit 20-50mm Airnet Range



Electrical Pipe Cutter

1450	Voltage
2810-0540-80	220 - 230

Fluid-Air Components Ltd

RINGMAIN PIPE KITS (CARM)

John Guest

new product

Simple, easy to install, basic air pipe systems at competitive pricing


Introducing **John Guest Compressed Air Ring Main (CARM) Kits** - the ultimate solution for compressed air piping systems installation. These kits come in three configurations, catering to 15 and 22 mm, and contain all the essential components for hassle-free assembly. No specialized knowledge or expensive equipment is needed, making it the go-to option for small ring-main installations.

Versatile kits for any project;

- Workshops
- Garages
- Domestic applications
- Extension onto existing pipe systems

2 Bay Kit, 15mm Pipe & Fittings

- 2 x bay kit of John Guest 15mm OD pipe and fittings
- 6 x 3 metre lengths nylon pipe.
- 12 x clips.
- 4 x elbows.
- 1 x flex 15 with 1/2" bsp male stem adaptor.
- 2 x brass wingback wall brackets.
- 1 x straight connector.
- 1 x tee and 2 PCL 19 series couplings.



1400
CARMKIT-2

1 Bay Kit, 15mm Pipe & Fittings


- 1 x bay kit of John Guest 15mm O.D pipe and fittings
- 4 x 3m lengths of 15mm nylon pipe.
- 8 x pipe clips.
- 2 x elbows.
- 1 x flex with 1/2" bsp male stem adaptor.
- 1 x straight connector.
- 1 brass wingback wall bracket with 1 x PCL 19 series coupling



1400
CARMKIT-1

3 Bay Kit, 22mm Pipe & Fittings

- 3 x bay kit of John Guest 22mm OD pipe and fittings
- 7 x 3 metre lengths nylon pipe.
- 14 x pipe clips.
- 4 x elbows.
- 1 x flex 22 with 1/2" bsp, male stem adaptor.
- 3 x brass wingback wall brackets.
- 2 x straight connector.
- 2 x tee.
- 3 x PCL 19 series couplings and 3 x 3/4 x 1/2 reducing bush.
- 1 x PTFE Tape



1400
CARMKIT-3

Fluid-Air Components Ltd

FAST-TRACK RING MAIN SYSTEM

Easy to use Push-fit connectors for air line ring mains

The John Guest range of push-fit fittings and pipe provide the ideal connection from compressor receiver to air line service components through to complete ring main and take off points.

Using the John Guest push-fit system, a compressed air ring main can be installed quickly and easily, with potential time savings of at least 50% when compared to other installation methods.

No need to prepare threaded pipe or solvent, all the connections can be made with a simple push-fit action. The system is then immediately ready for use.

Complex assembly can be performed much more rapidly than with traditional methods and because fittings are easy to disconnect, systems can be altered or extended with much reduced production down time.

To make a connection, the tube is simply pushed in by hand, with the unique collet locking system then holding the tube firmly in place withou deforming it or restricting flo .

**The fittings are produced in either tough engineering plastics material or in brass with Sizes 12mm to 28mm. They are intended for use with John Guest's nylon pipe, but can also be used with copper or aluminum alternatives.*

Working Temperature:
-20°C to +70°C

Working Pressure:
10 bar @ 23°C





Making a connection

Standard Fittings



Cut the pipe square
We recommend using the JG Pipe Cutter.



Push up to pipe stop




Pull to check secure
Test the system before use.



To disconnect
Ensure the system is depressurised. Push the collet towards the fitting and remove the pipe. The fitting can be reused

28mm Fittings



28mm fittings also have a collet with stainless steel teeth and an 'O' ring.



After inserting the pipe, a screw cap is turned approx 1/4 turn. This locks the collet in place and reduces lateral and sideways movement of the pipe.



To disconnect
Turn the screw cap 1/4 turn, push in the collet and remove the pipe. The fitting and pipe can be reused.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FAST-TRACK RING MAIN SYSTEM

John Guest

Fast-Track Tubing

John Guest Part No. Cross Reference

400-3012	PA-RM1209-3M-20B
400-3015	PA-RM1512-3M-20B
400-3018	PA-RM1814-3M-20B
400-3022	PA-RM2218-3M-20B
400-3028	PA-RM2823-3M-10B

Working Temperature: -20°C to +70°C

Maximum Working Pressure: +23°C: 10 bar, +70°C: 7 bar




Nylon 12, 3 Metre Lengths

1400	OD mm	ID mm
400-3012	12	9
400-3015	15	12
400-3018	18	14
400-3022	22	18
400-3028	28	23
Tech Sheet 20629		

N.B. Delivery may take up to 48 hours.

Working Temperature: -20°C to +70°C

Maximum Working Pressure: +23°C: 10 bar, +70°C: 7 bar



Blue Coated Aluminium, 3 Metre Lengths

1400	OD mm	ID mm
AL-RM1210-3M-20B	12	10
AL-RM1513-3M-20B	15	13
AL-RM1816-3M-20B	18	16
AL-RM2220-3M-20B	22	20
AL-RM2826-3M-10B	28	26
Tech Sheet 20629		

N.B. Delivery may take up to 48 hours.

Fast-Track Tube Clips



360° Pipe Retention, Tested to over 100lbs

1400	OD mm
405-1015	15
405-1022	22
405-1028	28
410-1522	Stand-off Spacer
Tech Sheet 20629	

U-Bend



1400	OD mm
PMUB15E	15
Tech Sheet 20629	

Straight Adaptor

* No thread seal.



BSPP Male

1400	OD mm	Thread
PM011213E	12	3/8"
PM011214E	12	1/2"
PM011514E	15	1/2"
PM011516E	15	3/4"
PM011814E	18	1/2"
PM012216E	22	3/4"
Tech Sheet 20629		

Stem Adaptor



BSPP Male

1400	OD mm	Thread
PM051213E	12	3/8"
PM051214E	12	1/2"
PM051513E	15	3/8"
PM051514E	15	1/2"
PM051814E	18	1/2"
PM052214E	22	1/2"
PM052216E	22	3/4"
Tech Sheet 20629		

Equal Elbow



1400	OD mm
PM0312E	12
PM0315E	15
PM0318E	18
PM0322E	22
PM0328E	28
Tech Sheet 20629	

Stem Elbow



1400	OD mm	Stem OD mm
PM221212E	12	12
PM221515E	15	15
PM221818E	18	18
PM222222E	22	22
Tech Sheet 20629		

Equal Tee



1400	OD mm
PM0212E	12
PM0215E	15
PM0218E	18
PM0222E	22
Tech Sheet 20629	

Reducing Tee



1400	Ends OD mm	Branch OD mm
PM03018AE	18	15
PM3022AE	22	15
Tech Sheet 20629		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FAST-TRACK RING MAIN SYSTEM

John Guest

Straight Connector



1400	OD mm
PM0412E	12
PM0415E	15
PM0418E	18
PM0422E	22
PM0428E	28
Tech Sheet 20629	

Reducer



1400	Stem OD mm	OD mm
PM061512E	15	12
PM061815E	18	15
PM062215E	22	15
PM062218E	22	18
PM062815E	28	15
Tech Sheet 20629		

Flexi-joint

When long runs of nylon tube are used, it is recommended a flexi-joint is installed. With temperature change, the tube can expand and contract along the length. This will lead to an unsightly distortion to the run of tube.



1400	OD mm	Max Pressure PSI
FLEX-15	15	145
FLEX-22	22	145
Tech Sheet 20629		

Plug



Black

1400	OD mm
PM0812R	12
PM0815E	15
PM0818E	18
PM0822E	22
PM0828E	28
Tech Sheet 20629	

Release Aid



1400	OD mm
15RA	15
22RA	22
Tech Sheet 20629	

Brass Straight Adaptors



BSPT Male

1400	OD mm	Thread
MM011504N	15	1/2"
MM012206N	22	3/4"
MM012808N	28	1"
Tech Sheet 20629		

Brass Wingback Elbow



BSPP Female

1400	OD mm	Thread
PM15WB	15	1/2"
PM22WB	22	3/4"
Tech Sheet 20629		

Brass Stem Adaptors



Male Thread

1400	OD mm	Thread
MM051504N	15	1/2" BSPT
MM052206N	22	3/4" BSPT
MM052818N	28	1" BSPT
MM052228N	22	1" NPT
MM052828N	28	1" NPT
Tech Sheet 20629		



BSPP Female

1400	OD mm	Thread
MM501514N	15	1/2"
MM502216N	22	3/4"
Tech Sheet 20629		

FTPRO

You might also need...
Polyurethane & Nylon Tube
...see pages **895-917**




FAST-TRACK RING MAIN SYSTEM

Water Trap Tee

The Fast-Track Water Trap Tee solves the on-going problem of moisture in a Ring Main system and provides the easy alternative to the need to install "Swan Necks".

The ingenious inside arrangement of the fitting allows air to flo , with minimum head loss, from the main to take-off point without allowing water to follow. The moisture is retained in the line to be drawn off at some suitable location.



Water Trap Tee Installation:

It is of vital importance for the correct function of the Water Trap Tee that the air ring main within which the Tee is installed is near horizontal and that the outlet port faces vertically downwards. Markings to indicate correct orientation have been moulded onto the body to assist installation.



1400	OD mm
PMTT22E	22
Tech Sheet 20629	

Water Trap Tee Convertor



Converts a 28mm Tee to a Water Trap Tee

1400	Size mm
WTC28	28
Tech Sheet 20629	

Collet Covers

Collet Covers prevent accidental removal or tampering with piping. The pipe can be inserted with the Collet Cover already attached to the fitting or the cover can slide into position afterwards.

We recommend covers be fitted when pipework is hidden inside walls, ceilings etc.

Collet Covers can be removed to allow the pipe to be disconnected as and when required.



Black

1400	OD mm
PM1915E	15
PM1922E	22
Tech Sheet 20629	

Pipe Clips & Spacers



Black

1400	Description	OD mm
PC15E	Clip	15
PC22E	Clip	22
PC28E	Clip	28
PCSE	Spacer	-
Tech Sheet 20629		

Pipe Cutters


Please Note: No spare blades available for this cutter.

The blade can be resharpened.



1400	Max Reach mm
JG-TSP	22
Tech Sheet 20629	

Aluminium Pipe Cutter



1400	OD mm
ALU-CUTTER15	15
ALU-CUTTER22	22
ALU-CUTTER28	28
Tech Sheet 20629	

End Stop



1400	OD mm
PM4612E	12
PM4615E	15
PM4622E	22
Tech Sheet 20629	

Porting Block



1/2" BSPP Female

1400	Outlets
JG-L-WSK	5 x 1/2" BSPP
Tech Sheet 20629	

Aluminium Wall Box



BSPP

1400	Inlet Size	Outlet Size	No. of Outlets
JGWALLBOX 1/2	1/2"	1/2"	3
JGWALLBOX 3/4	3/4"	1/2"	3
Tech Sheet 20629			

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

POLYETHYLENE COMPRESSION SYSTEM

FT PRO

Applications:
- Drinkable water systems
- Irrigation systems
- Fertilizing irrigation systems
- Wine, beer, beverages and other alimentary fluids
- Industrial equipment for acid bases and salts
- Swimming pools with fresh or sea water
- Ship Installations

Materials:
- Body and nut: polypropylene
- O-ring: nitrile
- Clenching ring: polyacetal resin
- Metal reinforcements: stainless steel

Maximum Working Temperature: +80°C

Maximum Working Pressure: 16 bar, atmospheric at 20°C up to 63mm bore
10 bar, atmospheric at 20°C from 75mm bore

NOTE: Materials fully conform with the international specification relating to Hygiene and Sanitary Requirements for the Transport of Potable Water and Alimentary Fluids.

Straight Connector



Tube x Tube

0116	OD mm
PE-701.016	16
PE-701.020	20
PE-701.025	25
PE-701.032	32
PE-701.040	40
PE-701.050	50
PE-701.063	63
PE-701.075	75
PE-701.110	110

Reducing Coupling



Tube x Tube

0116	OD mm	OD mm
PE-702.020	20	16
PE-702.025	25	20
PE-702.031	32	20
PE-702.032	32	25
PE-702.040	40	32
PE-702.049	50	32
PE-702.063	63	50

End Plug



Tube

0116	OD mm
PE-705.020	20
PE-705.025	25
PE-705.032	32
PE-705.050	50
PE-705.063	63

Female Adaptor



BSPT

0116	OD mm	Thread
PE-703.016	16	1/2"
PE-703.020	20	1/2"
PE-703.022	20	3/4"
PE-703.024	25	1/2"
PE-703.025	25	3/4"
PE-703.027	25	1"
PE-703.031	32	3/4"
PE-703.032	32	1"
PE-703.039	40	1"
PE-703.040	40	1.1/4"
PE-703.050	50	1.1/2"
PE-703.063	63	2"
PE-703.075	75	2.1/2"
PE-703.090	90	3"
PE-703.110	110	4"

Male Adaptor



BSPT

0116	OD mm	Thread
PE-704.016	16	1/2"
PE-704.020	20	1/2"
PE-704.021	20	3/4"
PE-704.024	25	1/2"
PE-704.025	25	3/4"
PE-704.026	25	1"
PE-704.031	32	3/4"
PE-704.032	32	1"
PE-704.033	32	1.1/4"
PE-704.039	40	1"
PE-704.040	40	1.1/4"
PE-704.041	40	1.1/2"
PE-704.049	50	1.1/4"
PE-704.050	50	1.1/2"
PE-704.051	50	2"
PE-704.063	63	2"
PE-704.074	75	2"
PE-704.075	75	2.1/2"
PE-704.090	90	3"

90º Equal Elbows



Tube x Tube

0116	OD mm
PE-706.016	16
PE-706.020	20
PE-706.025	25
PE-706.032	32
PE-706.040	40
PE-706.050	50
PE-706.063	63
PE-706.090	90



Male, BSPT

0116	OD mm	Thread
PE-707.020	20	1/2"
PE-707.024	25	1/2"
PE-707.025	25	3/4"
PE-707.031	32	3/4"
PE-707.032	32	1"
PE-707.050	50	1.1/2"
PE-707.063	63	2"



Female, BSPT

0116	OD mm	Thread
PE-708.020	20	1/2"
PE-708.024	25	1/2"
PE-708.025	25	3/4"
PE-708.031	32	3/4"
PE-708.032	32	1"
PE-708.050	50	1.1/2"
PE-708.063	63	2"

Fluid-Air Components Ltd

POLYETHYLENE COMPRESSION SYSTEM

FT PRO

90º Equal Tee



Tube x Tube

0116	OD mm
PE-709.020	20
PE-709.025	25
PE-709.032	32
PE-709.040	40
PE-709.050	50
PE-709.063	63
PE-709.075	75



Male, BSPT

0116	OD mm	Thread
PE-711.020	20	1/2"
PE-711.025	25	3/4"
PE-711.032	32	1"
PE-711.050	50	1.1/2"
PE-711.063	63	2"



Female, BSPP

0116	OD mm	Thread
PE-710.020	20	1/2"
PE-710.024	25	1/2"
PE-710.025	25	3/4"
PE-710.031	32	3/4"
PE-710.032	32	1"
PE-710.040	40	1.1/4"
PE-710.050	50	1.1/2"
PE-710.090	90	3"

Wall Support Bracket



BSPP

0116	OD mm	Thread
PE-712.020	20	1/2"
PE-712.025	25	3/4"

90º Reducing Tee



Branch

0116	OD mm	OD mm
PE-713.025	25	20
PE-713.032	32	25
PE-713.063	63	50

Compression Flange

Conforms to the following standards:

UNE EN-712, UNE EN-713, UNE EN-715, UNE EN-714, ISO 351, ISO 3503, ISO 3458, ISO 3459, DIN 8076, ISO 7, ISO 228, DIN 2999, DIN 259



Tube

0116	OD mm
PE-714.050	50
PE-714.063	63
PE-714.075	75
PE-714.090	90

Pipe Liner



0116	To Suit Hose OD mm
PE-780020	20
PE-780025	25
PE-780032	32

Repair Coupling



Tube x Tube

0116	OD mm
PE-725020	20
PE-725025	25
PE-725032	32
PE-725050	50
PE-725075	75

Spanner



0116	To Suit
PE-776001	20mm to 32mm
PE-776002	40mm to 63mm
PE-776003	20mm to 63mm
PE-776004	75mm to 110mm

MDPE Pipes



Blue

0116	OD mm	Length Metres
PE-MDPE20BLU	20	100
PE-MDPE25BLU	25	100
PE-MDPE32BLU	32	100
PE-MDPE63BLU	63	100



Black

0116	OD mm	Length Metres
PE-MDPE20BLK	20	100
PE-MDPE25BLK	25	100
PE-MDPE32BLK	32	100
PE-MDPE63BLK	63	100

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

POLYETHYLENE PIPE UNIVERSAL TRANSITION FITTINGS

Universal Fittings

This Universal STP Kit is compatible with any fitting, allowing the transition between pipes of any material with diameters from 15mm to 35mm (1/2" to 1" and polyethylene pipes between 16mm to 63mm.



Universal Fittings

0116	Inlet mm	Outlet
PE-715.020	15-22	To suit 25mm Body
PE-715.025	21-27	To suit 32mm Body
PE-715.032	27-35	To suit 40mm Body
	Tech Sheet 20360	

Rubber adaptor suitable for all STP fittings that allow the transition from copper (15-16 mm) to galvanised or UPVC (1/2").



For Copper Tubing

0116
PE-000.715

Couplings



Tube x Tube

0116	OD A mm	OD A	OD B mm
PE-716016	15-22	1/2"	16
PE-716020	15-22	1/2"	20
PE-716025	15-22	1/2"	25
PE-716032	15-22	1/2"	32
PE-716040	15-22	1/2"	40
PE-717020	21-27	3/4"	20
PE-717025	21-27	3/4"	25
PE-717032	21-27	3/4"	32
PE-717040	21-27	3/4"	40
PE-717050	21-27	3/4"	50
PE-718025	27-35	1"	25
PE-718032	27-35	1"	32
PE-718040	27-35	1"	40
PE-718050	27-35	1"	50
PE-718063	27-35	1"	63
PE-719032	35-50	1.1/2"	32
PE-719040	35-50	1.1/2"	40
PE-719050	35-50	1.1/2"	50
PE-719063	35-50	1.1/2"	63

Adaptors



Male, BSPT

0116	OD mm	OD	Thread
PE-721020	15-22	1/2"	1/2"
PE-721021	15-22	1/2"	3/4"
PE-721022	15-22	1/2"	1"
PE-721025	21-27	3/4"	3/4"
PE-721026	21-27	3/4"	1"
PE-721027	21-27	3/4"	1.1/4"
PE-721032	27-35	1"	1"
PE-721033	27-35	1"	1.1/4"
PE-721034	27-35	1"	1.1/2"
PE-721040	35-50	1.1/2"	1.1/4"
PE-721041	35-50	1.1/2"	1.1/2"
PE-721042	35-50	1.1/2"	2"



Female, BSPP

0116	OD mm	OD	Thread
PE-720020	15-22	1/2"	1/2"
PE-720021	15-22	1/2"	3/4"
PE-720022	15-22	1/2"	1"
PE-720026	21-27	3/4"	1"
PE-720032	27-35	1"	1"
PE-720033	27-35	1"	1.1/4"
PE-720041	35-50	1.1/2"	1.1/2"

End Caps



Tube

0116	OD mm	OD
PE-722020	15-22	1/2"
PE-722025	21-27	3/4"
PE-722032	27-35	1"
PE-722040	35-50	1.1/2"

Elbows



Tube x Tube

0116	OD A mm	OD A	OD B mm
PE-723020	15-22	1/2"	20
PE-723021	15-22	1/2"	25
PE-723025	21-27	3/4"	25
PE-723026	21-27	3/4"	32
PE-723033	27-35	1"	40



Male, BSPT

0116	OD mm	OD	Thread
PE-723121	15-22	1/2"	3/4"
PE-723132	27-35	1"	1"



Female, BSPP

0116	OD mm	OD	Thread
PE-723221	15-22	1/2"	3/4"
PE-723226	21-27	3/4"	1"
PE-723232	27-35	1"	1"
PE-723233	27-35	1"	1.1/4"

POLYETHYLENE PIPE UNIVERSAL TRANSITION FITTINGS & VALVES

FT PRO

Tees



Tube x Tube, Universal x PP x PP

0116	OD A mm	OD A	OD B mm	OD C mm
PE-724001	15-22	1/2"	25	25
PE-724003	15-22	1/2"	25	20
PE-724005	21-27	3/4"	32	32
PE-724007	21-27	3/4"	32	25
PE-724011	27-35	21"	40	40
PE-724013	27-35	1"	40	32



Tube x Tube, Universal x PP x Universal

0116	OD A mm	OD A	OD B mm
PE-724002	15-22	1/2"	25
PE-724004	15-22	1/2"	20
PE-724010	15-22	1/2"	32
PE-724008	21-27	3/4"	25
PE-724006	21-27	3/4"	32
PE-724016	21-27	3/4"	40
PE-724014	27-35	1"	32
PE-724012	27-35	1"	40



Female x BSPP

0116	OD A mm	OD A	OD B mm	Thread
PE-724120	15-22	1/2"	25	1/2"
PE-724121	15-22	1/2"	25	3/4"
PE-724125	21-27	3/4"	32	3/4"
PE-724126	21-27	3/4"	32	1"
PE-724132	27-35	1"	40	1"
PE-724133	27-35	1"	40	1.1/4"



Male x BSPT

0116	OD A mm	OD A	OD B mm	Thread
PE-724221	15-22	1/2"	25	3/4"
PE-724226	21-27	3/4"	32	1"
PE-724233	27-35	1"	40	1.1/4"

Compression Valves



Tube x Tube

0116	OD mm
PE-141020C	20
PE-141025C	25
PE-141032C	32
PE-141040C	40
PE-141050C	50
PE-141063C	63



Tube x BSPT Male

0116	OD mm	Thread
PE-142020C	20	1/2"
PE-142025C	25	3/4"
PE-142032C	32	1"
PE-142040C	40	1.1/4"
PE-142050C	50	1.1/2"
PE-142063C	63	2"



Tube x BSPP Female

0116	OD mm	Thread
PE-140020CX	20	1/2"
PE-140025CX	25	3/4"
PE-140032CX	32	1"
PE-140040CX	40	1.1/4"
PE-140050CX	50	1.1/2"
PE-140063CX	63	2"

Universal Compression Valves



Tube x Tube, Universal x PP

0116	OD mm	OD mm
PE-141024CU	15-22	25
PE-141031CU	15-22	32
PE-141040CU	27-35	40



Universal x Universal

0116	OD mm	OD mm
PE-140025U	15-22	15-22
PE-140031U	21-27	15-22
PE-140040U	27-35	27-35



Tube x BSPP Female

0116	OD mm	Thread
PE-141030UM	15-22	1"
PE-141031UM	21-27	3/4"
PE-141032UM	21-27	1"
PE-141041UM	27-35	1.1/2"



Tube x BSPT Male

0116	OD mm	Thread
PE-142024UM	15-22	1/2"
PE-142025UM	15-22	3/4"
PE-142030UM	15-22	1"
PE-142031UM	21-27	3/4"
PE-142032UM	21-27	1"
PE-142040UM	27-35	1.1/4"
PE-142041UM	27-35	1.1/2"

Fluid-Air Components Ltd

ABS IMPERIAL PIPE SYSTEM

Working Temperature: -40°C to 70°C

Maximum Working Pressure: 15 bar (8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Sockets & Reducing Bushes



Equal Socket

1050	Nominal Bore ID
SO13-12-ABS	1/2"
SO13-34-ABS	3/4"
SO13-1-ABS	1"
SO13-114-ABS	1.1/4"
SO13-112-ABS	1.1/2"
SO13-2-ABS	2"
SO13-212-ABS	2.1/2"
SO13-3-ABS	3"
SO13-4-ABS	4"
Tech Sheet 10255	



Plain x Threaded Male, BSPT

1050	Nominal Bore ID	Nominal Bore ID
RS13-3412-ABS	3/4"	1/2"
RS13-134-ABS	1"	3/4"
RS13-1141-ABS	1.1/4"	1"
RS13-112114-ABS	1.1/2"	1.1/4"
RS13-2112-ABS	2"	1.1/2"
RS13-3212-ABS	3"	2.1/2"
RS13-43-ABS	4"	3"
Tech Sheet 10255		



Reducing Bush

1050	Nominal Bore ID	Nominal Bore ID
RB93-3412-ABS	3/4"	1/2"
RB93-112-ABS	1"	1/2"
RB93-134-ABS	1"	3/4"
RB93-11412-ABS	1.1/4"	1/2"
RB93-11434-ABS	1.1/4"	3/4"
RB93-1141-ABS	1.1/4"	1"
RB93-11234-ABS	1.1/2"	3/4"
RB93-1121-ABS	1.1/2"	1"
RB93-112114-ABS	1.1/2"	1.1/4"
RB93-21-ABS	2"	1"
RB93-2114-ABS	2"	1.1/4"
RB93-2112-ABS	2"	1.1/2"
RB93-2122-ABS	2.1/2"	2"
RB93-3112-ABS	3"	1.1/2"
RB93-32-ABS	3"	2"
RB93-3212-ABS	3"	2.1/2"
RB93-42-ABS	4"	2"
RB93-4212-ABS	4"	2.1/2"
RB93-43-ABS	4"	3"
RB93-54-ABS	5"	4"
Tech Sheet 10255		

Elbows & Bends



Equal 90° Elbow

1050	Nominal Bore ID
EL53-12-ABS	1/2"
EL53-34-ABS	3/4"
EL53-1-ABS	1"
EL53-114-ABS	1.1/4"
EL53-112-ABS	1.1/2"
EL53-2-ABS	2"
EL53-212-ABS	2.1/2"
EL53-3-ABS	3"
EL53-4-ABS	4"
EL53-5-ABS	5"
EL53-6-ABS	6"
Tech Sheet 10255	



Equal 90° Bend, Short Radius

1050	Nominal Bore ID
BE33-12-ABS	1/2"
BE33-34-ABS	3/4"
BE33-1-ABS	1"
BE33-114-ABS	1.1/4"
BE33-112-ABS	1.1/2"
BE33-2-ABS	2"
BE33-212-ABS	2.1/2"
BE33-3-ABS	3"
BE33-4-ABS	4"
Tech Sheet 10255	



Equal 45° Elbow

1050	Nominal Bore ID
EY53-12-ABS	1/2"
EY53-34-ABS	3/4"
EY53-1-ABS	1"
EY53-114-ABS	1.1/4"
EY53-112-ABS	1.1/2"
EY53-2-ABS	2"
EY53-212-ABS	2.1/2"
EY53-3-ABS	3"
EY53-4-ABS	4"
EY53-6-ABS	6"
Tech Sheet 10255	

Equal Barrel Nipples



Male, BSPT

1050	Thread
BN11-12-ABS	1/2"
BN11-34-ABS	3/4"
BN11-1-ABS	1"
BN11-114-ABS	1.1/4"
BN11-112-ABS	1.1/2"
BN11-2-ABS	2"
BN11-212-ABS	2.1/2"
BN11-3-ABS	3"
BN11-4-ABS	4"
Tech Sheet 10255	



Stem Nipple, BSPT

1050	Thread	Nominal Bore ID	Length mm
BN12-12-ABS	1/2"	1/2"	50
BN12-34-ABS	3/4"	3/4"	56
BN12-1-ABS	1"	1"	63
BN12-114-ABS	1.1/4"	1.1/4"	75
BN12-112-ABS	1.1/2"	1.1/2"	88
BN12-2-ABS	2"	2"	88
BN12-212-ABS	2.1/2"	2.1/2"	106
BN12-3-ABS	3"	3"	128
BN12-4-ABS	4"	4"	153
Tech Sheet 10255			

Tees



45° Tee

1050	Nominal Bore ID
TY43-12-ABS	1/2"
TY43-34-ABS	3/4"
TY43-1-ABS	1"
TY43-114-ABS	1.1/4"
TY43-2-ABS	2"
Tech Sheet 10255	



Equal Tee

1050	Nominal Bore ID
TE43-12-ABS	1/2"
TE43-34-ABS	3/4"
TE43-1-ABS	1"
TE43-112-ABS	1.1/2"
TE43-114-ABS	1.1/4"
TE43-2-ABS	2"
TE43-212-ABS	2.1/2"
TE43-3-ABS	3"
TE43-4-ABS	4"
TE43-5-ABS	5"
TE43-6-ABS	6"
Tech Sheet 10255	

ABS IMPERIAL PIPE SYSTEM

Working Temperature: 0°C to 60°C

Maximum Working Pressure: 15 bar (8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Crosses



Equal Cross

1050	Nominal Bore ID
CR33-12-ABS	1/2"
CR33-34-ABS	3/4"
CR33-1-ABS	1"
CR33-2-ABS	2"
Tech Sheet 10255	

Caps



Plain

1050	Nominal Bore ID
CA73-12-ABS	1/2"
CA73-34-ABS	3/4"
CA73-1-ABS	1"
CA73-114-ABS	1.1/4"
CA73-112-ABS	1.1/2"
CA73-2-ABS	2"
CA73-212-ABS	2.1/2"
CA73-3-ABS	3"
CA73-4-ABS	4"
Tech Sheet 10255	

Unions



Equal Union

1050	Nominal Bore ID
UN83-12-ABS	1/2"
UN83-34-ABS	3/4"
UN83-1-ABS	1"
UN83-114-ABS	1.1/4"
UN83-112-ABS	1.1/2"
UN83-2-ABS	2"
UN83-212-ABS	2.1/2"
UN83-3-ABS	3"
UN83-4-ABS	4"
Tech Sheet 10255	

Tank Connectors



Plain x Female, BSPP

1050	Nominal Bore ID	Thread
TC93-12-ABS	1/2"	1/2"
TC93-34-ABS	3/4"	3/4"
TC93-1-ABS	1"	1"
TC93-114-ABS	1.1/4"	1.1/4"
TC93-112-ABS	1.1/2"	1.1/2"
TC93-2-ABS	2"	2"
TC93-212-ABS	2.1/2"	2.1/2"
TC93-3-ABS	3"	3"
TC93-4-ABS	4"	4"
Tech Sheet 10255		

Threaded Sockets & Adaptors



Plain x Threaded Female Socket, BSPP

1050	Nominal Bore ID	Thread
PTS-12-ABS	1/2"	1/2"
PTS-1-ABS	1"	1"
PTS-112-ABS	1.1/2"	1.1/2"
PTS-2-ABS	2"	2"
PTS-212-ABS	2.1/2"	2.1/2"
PTS-3-ABS	3"	3"
PTS-4-ABS	4"	4"



Plain x Threaded Male Adaptor, BSPP

1050	Nominal Bore ID	Spigot	BSPP Male
MFA1-34-ABS	3/4"	1"	3/4"
MFA1-1-ABS	1"	1.1/4"	1"
MFA1-112-ABS	1.1/2"	2"	1.1/2"
MFA1-2-ABS	2"	2.1/2"	2"



Plain x Threaded Female Adaptor, BSPP

1050	Nominal Bore ID	Thread
MFA2-12-ABS	1/2"	1/2"
MFA2-34-ABS	3/4"	3/4"
MFA2-1-ABS	1"	1"
MFA2-2-ABS	2"	2"
MFA2-3-ABS	3"	3"

Hose Connections



Male, BSPP x Hose Tail

1050	Thread	Hose ID mm
MHA-34-ABS	3/4"	25



Female, BSPP x Hose Tail

1050	Thread	Hose ID mm
FHA-1-ABS	1"	20

Reducing Bushes



Plain x Threaded Female, BSPP

1050	Nominal Bore ID	Female BSPP
FRB-12-ABS	1/2"	3/8"
FRB-34-ABS	3/4"	1/2"

Unions



Plain x Brass Composite Male Threaded Union, BSPP

1050	Nominal Bore ID	Thread
MBU-1-ABS	1"	1"
MBU-112-ABS	1.1/2"	1.1/2"



Plain x Brass Composite Female Threaded Union, BSPP

1050	Nominal Bore ID	Thread
FBU-12-ABS	1/2"	1/2"
FBU-34-ABS	3/4"	3/4"
FBU-1-ABS	1"	1"
FBU-114-ABS	1.1/4"	1.1/4"
FBU-112-ABS	1.1/2"	1.1/2"
FBU-2-ABS	2"	2"

Fluid-Air Components Ltd

ABS IMPERIAL PIPE SYSTEM

Working Temperature:
0°C to 60°C

Maximum Working Pressure:
15 bar
(8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Flanges



Stub Flange, Serrated Face

1050	Nominal Bore
ST23-34-ABS	3/4"
ST23-1-ABS	1"
ST23-112-ABS	1.1/2"
ST23-2-ABS	2"
ST23-212-ABS	2.1/2"
ST23-3-ABS	3"
ST23-4-ABS	4"
ST23-5-ABS	5"
ST23-6-ABS	6"

Tech Sheet 10255



Full Face Table E

1050	Nominal Bore
FF30-12-ABS	1/2"
FF30-34-ABS	3/4"
FF30-1-ABS	1"
FF30-114-ABS	1.1/4"
FF30-112-ABS	1.1/2"
FF30-2-ABS	2"
FF30-3-ABS	3"
FF30-4-ABS	4"

Tech Sheet 10255



ABS Plain Full Face Flange NP10/16

1050	Tube NB
FF31-2-ABS	2"



BS4504, PN16 Flange Gasket

1050	Size
SF16-12	1/2"
SF16-34	3/4"
SF16-1	1"
SF16-114	1.1/4"
SF16-112	1.1/2"
SF16-2	2"
SF16-3	3"
SF16-4	4"
SF16-6	6"

Tech Sheet 10255



BS10, Table E Flange Gasket

1050	Size
SF10-12	1/2"
SF10-34	3/4"
SF10-1	1"
SF10-114	1.1/4"
SF10-112	1.1/2"
SF10-2	2"
SF10-212	2.1/2"
SF10-3	3"
SF10-4	4"
SF10-6	6"

Tech Sheet 10255



ABS Blank Flange NP10/16

1050	Tube NB
BF10-212-ABS	2.1/2"



PN16 Galvanised Backing Ring

1050	Size
GB16-12	1/2"
GB16-34	3/4"
GB16-1	1"
GB16-114	1.1/4"
GB16-112	1.1/2"
GB16-2	2"
GB16-212	2.1/2"
GB16-3	3"
GB16-4	4"
GB16-5	5"
GB16-6	6"

Tech Sheet 10255



Stub Flange Gasket, EPDM

1050	Size
SG50-1-ABS	1"
SG50-114-ABS	1.1/4"
SG50-112-ABS	1.1/2"
SG50-2-ABS	2"
SG50-212-ABS	2.1/2"
SG50-3-ABS	3"
SG50-4-ABS	4"
SG50-5-ABS	5"

Tech Sheet 10255

Tube O.D. - Size Conversion Table

Nominal Bore	Outside Diameter
3/8"	17.1mm
1/2"	21.3mm
3/4"	26.7mm
1"	33.4mm
1.1/4"	42.2mm
1.1/2"	48.3mm
2"	60.3mm
2.1/2"	75mm
3"	88.9mm
4"	114.3mm
5"	140mm
6"	168.3mm
8"	219.1mm

ABS IMPERIAL PIPE SYSTEM

Working Temperature:
0°C to 60°C

Maximum Working Pressure:
15 bar
(8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Valves



Industrial Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVI13-12-ABS	1/2"
BVI13-34-ABS	3/4"
BVI13-1-ABS	1"
BVI13-114-ABS	1.1/4"
BVI13-112-ABS	1.1/2"
BVI13-2-ABS	2"
BVI13-212-ABS	2.1/2"
BVI13-3-ABS	3"
BVI13-4-ABS	4"
Tech Sheet 10255	



Standard Double Union Ball Valve, EPDM Seals

1050	Tube NB
BVDUS-12	1/2"
BVDUS-1	1"
BVDUS-112	1.1/2"
BVDUS-2	2"
BVDUS-212	2.1/2"



Industrial Check Valve, EPDM Seals

0118	Nominal Bore ID
CVD13-12-ABS	1/2"
CVD13-34-ABS	3/4"
CVD13-1-ABS	1"
CVD13-114-ABS	1.1/4"
CVD13-112-ABS	1.1/2"
CVD13-2-ABS	2"
Tech Sheet 10255	

Solvent Cement



ABS

1050	Millilitres
ABS	500
Tech Sheet 875	

Cleaning Fluid



500ml

1050	Millilitres
MEK-TIN	500
Tech Sheet 877	

Flamco
Flow of Innovation



For **Pipe Clips & Fixing Systems** ...see pages **1549-1557**

ABS Tubing

Note: 6 metre length tube is available on a 3 to 5 working day delivery service. Specified delivery dates and times can not be guaranteed. Carriage is charged as an extra based on weight and delivery service required. Please speak to our sales department for further details. Delivery of 2.9 metre lengths may take up to 48 hours.



Class C, 9 bar, 2.9 Metre Lengths

0118	Nominal Bore
ABS/CTUBE-3-1	1"
ABS/CTUBE-3-114	1.1/4"
ABS/CTUBE-3-112	1.1/2"
ABS/CTUBE-3-2	2"
ABS/CTUBE-3-212	2.1/2"
ABS/CTUBE-3-3	3"
ABS/CTUBE-3-4	4"
ABS/CTUBE-3-6	6"
ABS/CTUBE-3-8	8"
Tech Sheet 10255	

Class C, 9 bar, 5.8 Metre Lengths

0118	Nominal Bore
ABS/CTUBE-6-1	1"
ABS/CTUBE-6-114	1.1/4"
ABS/CTUBE-6-112	1.1/2"
ABS/CTUBE-6-2	2"
ABS/CTUBE-6-212	2.1/2"
ABS/CTUBE-6-3	3"
ABS/CTUBE-6-4	4"
Tech Sheet 10255	

Class E, 15 bar, 2.9 Metre Lengths

0118	Nominal Bore
ABS/ETUBE-3-12	1/2"
ABS/ETUBE-3-34	3/4"
ABS/ETUBE-3-1	1"
ABS/ETUBE-3-114	1.1/4"
ABS/ETUBE-3-112	1.1/2"
ABS/ETUBE-3-2	2"
ABS/ETUBE-3-3	3"
ABS/ETUBE-3-4	4"
Tech Sheet 10255	

Class E, 15 bar, 5.8 Metre Lengths

0118	Nominal Bore
ABS/ETUBE-6-12	1/2"
ABS/ETUBE-6-34	3/4"
ABS/ETUBE-6-1	1"
ABS/ETUBE-6-114	1.1/4"
ABS/ETUBE-6-112	1.1/2"
ABS/ETUBE-6-2	2"
ABS/ETUBE-6-3	3"
Tech Sheet 10255	

Fluid-Air Components Ltd

UPVC METRIC PIPE SYSTEM

UPVC (Unplasticised Polyvinyl Chloride) is a **low maintenance material** selected for use across various industries due to its **high tensile strength** and durability. The outstanding feature of this product is its **excellent chemical resistance** which makes it suitable for a wide range of acids, alkalis and chemicals.

Working Temperature:
All pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain Fittings
12 bar Threaded Fittings
(Sizes 200mm/225mm with reduced safety factor)

20°C	30°C	40°C	50°C	60°C
16.0 bar	12.8 bar	9.2 bar	6.2 bar	3.5 bar

Sockets & Reducing Bushes



Equal Socket

1050	ID mm
SO-16-UPVC	16
SO-20-UPVC	20
SO-25-UPVC	25
SO-32-UPVC	32
SO-40-UPVC	40
SO-50-UPVC	50
SO-63-UPVC	63
SO-75-UPVC	75
SO-90-UPVC	90
SO-110-UPVC	110
SO-125-UPVC	125
SO-160-UPVC	160
SO-200-UPVC	200
SO-225-UPVC	225
Tech Sheet 10256	



Plain x Threaded Socket, BSPP

1050	ID mm	Thread
TSO-16-38-UPVC	16	3/8"
TSO-20-12-UPVC	20	1/2"
TSO-25-34-UPVC	25	3/4"
TSO-32-1-UPVC	32	1"
TSO-40-114-UPVC	40	1.1/4"
TSO-50-112-UPVC	50	1.1/2"
TSO-63-2-UPVC	63	2"
TSO-75-212-UPVC	75	2.1/2"
TSO-90-3-UPVC	90	3"
TSO-110-4-UPVC	110	4"
TSO-125-5-UPVC	125	5"
Tech Sheet 10256		



Reducing Socket

1050	ID mm	ID mm
RSO-2016-UPVC	20	16
RSO-2516-UPVC	25	16
RSO-2520-UPVC	25	20
RSO-3220-UPVC	32	20
RSO-3225-UPVC	32	25
RSO-4020-UPVC	40	20
RSO-4025-UPVC	40	25
RSO-4032-UPVC	40	32
RSO-5025-UPVC	50	25
RSO-5032-UPVC	50	32
RSO-5040-UPVC	50	40
RSO-6340-UPVC	63	40
RSO-6350-UPVC	63	50
RSO-7540-UPVC	75	40
RSO-7550-UPVC	75	50
RSO-7563-UPVC	75	63
RSO-9040-UPVC	90	40
RSO-9050-UPVC	90	50
RSO-9063-UPVC	90	63
RSO-9075-UPVC	90	75
RSO-11050-UPVC	110	50
RSO-11063-UPVC	110	63
RSO-11075-UPVC	110	75
RSO-11090-UPVC	110	90
RSO-12590-UPVC	125	90
RSO-125110-UPVC	125	110
RSO-14090-UPVC	140	90
RSO-140110-UPVC	140	110
RSO-140125-UPVC	140	125
RSO-160110-UPVC	160	110
RSO-160140-UPVC	160	140
Tech Sheet 10256		



Reducing Bush

1050	OD mm	ID mm
RB-2016-UPVC	20	16
RB-2516-UPVC	25	16
RB-2520-UPVC	25	20
RB-3216-UPVC	32	16
RB-3220-UPVC	32	20
RB-3225-UPVC	32	25
RB-4020-UPVC	40	20
RB-4025-UPVC	40	25
RB-4032-UPVC	40	32
RB-5025-UPVC	50	25
RB-5032-UPVC	50	32
RB-5040-UPVC	50	40
RB-6325-UPVC	63	25
RB-6332-UPVC	63	32
RB-6340-UPVC	63	40
RB-6350-UPVC	63	50
RB-7532-UPVC	75	32
RB-7540-UPVC	75	40
RB-7550-UPVC	75	50
RB-7563-UPVC	75	63
RB-9050-UPVC	90	50
RB-9063-UPVC	90	63
RB-9075-UPVC	90	75
RB-11063-UPVC	110	63
RB-11075-UPVC	110	75
RB-11090-UPVC	110	90
RB-12575-UPVC	125	75
RB-12590-UPVC	125	90
RB-125110-UPVC	125	110
RB-14090-UPVC	140	90
RB-140110-UPVC	140	110
RB-140125-UPVC	140	125
RB-160110-UPVC	160	110
RB-160125-UPVC	160	125
RB-160140-UPVC	160	140
RB-180125-UPVC	180	125
RB-180140-UPVC	180	140
RB-180160-UPVC	180	160
RB-200160-UPVC	200	160
RB-200180-UPVC	200	180
RB-225160-UPVC	225	160
RB-225200-UPVC	225	200
Tech Sheet 10256		

UPVC METRIC PIPE SYSTEM

Working Temperature:
All pressures quoted are based on a working temperature of 20°C

PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain Fittings
12 bar Threaded Fittings
(Sizes 200mm/225mm with reduced safety factor)

20°C	30°C	40°C	50°C	60°C
16.0 bar	12.8 bar	9.2 bar	6.2 bar	3.5 bar

Elbows & Bends



Equal 90° Elbow

1050	ID mm
EE-90-16-UPVC	16
EE-90-20-UPVC	20
EE-90-25-UPVC	25
EE-90-32-UPVC	32
EE-90-40-UPVC	40
EE-90-50-UPVC	50
EE-90-63-UPVC	63
EE-90-75-UPVC	75
EE-90-90-UPVC	90
EE-90-110-UPVC	110
EE-90-125-UPVC	125
EE-90-140-UPVC	140
EE-90-160-UPVC	160
EE-90-200-UPVC	200
EE-90-225-UPVC	225
Tech Sheet 10256	



Equal 45° Elbow

1050	ID mm
EE-45-16-UPVC	16
EE-45-25-UPVC	25
EE-45-32-UPVC	32
EE-45-40-UPVC	40
EE-45-50-UPVC	50
EE-45-63-UPVC	63
EE-45-75-UPVC	75
EE-45-90-UPVC	90
EE-45-110-UPVC	110
EE-45-125-UPVC	125
EE-45-140-UPVC	140
EE-45-200-UPVC	200
EE-45-225-UPVC	225
Tech Sheet 10256	



Equal 90° Bend, Short Radius

1050	ID mm
EB-90-20-UPVC	20
EB-90-25-UPVC	25
EB-90-32-UPVC	32
EB-90-40-UPVC	40
EB-90-50-UPVC	50
EB-90-63-UPVC	63
EB-90-75-UPVC	75
EB-90-110-UPVC	110
Tech Sheet 10256	



Equal 45° Bend, Short Radius

1050	ID mm
EB-45-32-UPVC	32
EB-45-40-UPVC	40
EB-45-63-UPVC	63
EB-45-75-UPVC	75
EB-45-90-UPVC	90
Tech Sheet 10256	



Plain x Threaded 90° Elbow, BSPP

1050	ID mm	Thread
TE-90-16-UPVC	16	3/8"
TE-90-20-UPVC	20	1/2"
TE-90-25-UPVC	25	3/4"
TE-90-32-UPVC	32	1"
TE-90-40-UPVC	40	1.1/4"
TE-90-50-UPVC	50	1.1/2"
TE-90-63-UPVC	63	2"
TE-90-75-UPVC	75	2.1/2"
Tech Sheet 10256		



Plain x Threaded 45° Elbow, BSPP

1050	ID mm	Thread
TE-45-16-UPVC	16	3/8"
TE-45-20-UPVC	20	1/2"
TE-45-25-UPVC	25	3/4"
TE-45-32-UPVC	32	1"
TE-45-40-UPVC	40	1.1/4"
TE-45-50-UPVC	50	1.1/2"
TE-45-63-UPVC	63	2"
TE-45-75-UPVC	75	2.1/2"
TE-45-110-UPVC	110	4"
Tech Sheet 10256		

Fluid-Air Components Ltd

UPVC METRIC PIPE SYSTEM

Working Temperature:
All pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain Fittings
12 bar Threaded Fittings
(Sizes 200mm/225mm with reduced safety factor)

20°C	30°C	40°C	50°C	60°C
16.0 bar	12.8 bar	9.2 bar	6.2 bar	3.5 bar

Tees



Equal Tee

1050	ID mm
T-16-UPVC	16
T-20-UPVC	20
T-25-UPVC	25
T-32-UPVC	32
T-40-UPVC	40
T-50-UPVC	50
T-63-UPVC	63
T-75-UPVC	75
T-90-UPVC	90
T-110-UPVC	110
T-125-UPVC	125
T-140-UPVC	140
T-160-UPVC	160
T-200-UPVC	200
T-225-UPVC	225
Tech Sheet 10256	



Equal 45° Tee

1050	ID mm
TY-16-UPVC	16
TY-20-UPVC	20
TY-25-UPVC	25
TY-32-UPVC	32
TY-40-UPVC	40
TY-50-UPVC	50
TY-63-UPVC	63
Tech Sheet 10256	



Reducing Branch Tee

1050	ID mm	ID mm
TR-2016-UPVC	20	16
TR-2516-UPVC	25	16
TR-2520-UPVC	25	20
TR-3216-UPVC	32	16
TR-3220-UPVC	32	20
TR-3225-UPVC	32	25
TR-4016-UPVC	40	16
TR-4025-UPVC	40	25
TR-5020-UPVC	50	20
TR-5025-UPVC	50	25
TR-5032-UPVC	50	32
TR-5040-UPVC	50	40
TR-6325-UPVC	63	25
TR-6332-UPVC	63	32
TR-6340-UPVC	63	40
TR-6350-UPVC	63	50
TR-7532-UPVC	75	32
TR-7540-UPVC	75	40
TR-7550-UPVC	75	50
TR-7563-UPVC	75	63
TR-9040-UPVC	90	40
TR-9050-UPVC	90	50
TR-9063-UPVC	90	63
TR-9075-UPVC	90	75
TR-11050-UPVC	110	50
TR-11075-UPVC	110	75
TR-11090-UPVC	110	90
TR-12563-UPVC	125	63
TR-12575-UPVC	125	75
TR-12590-UPVC	125	90
TR-125110-UPVC	125	110
TR-14075-UPVC	140	75
TR-14090-UPVC	140	90
TR-140110-UPVC	140	110
TR-140125-UPVC	140	125
TR-16090-UPVC	160	90
TR-160110-UPVC	160	110
TR-160125-UPVC	160	125
TR-160140-UPVC	160	140
Tech Sheet 10256		

Crosses



Equal Cross

1050	ID mm
X-16-UPVC	16
X-20-UPVC	20
X-25-UPVC	25
X-32-UPVC	32
X-40-UPVC	40
X-50-UPVC	50
X-75-UPVC	75
X-90-UPVC	90
X-110-UPVC	110
Tech Sheet 10256	

Caps



Plain

1050	ID mm
BC-16-UPVC	16
BC-20-UPVC	20
BC-25-UPVC	25
BC-32-UPVC	32
BC-40-UPVC	40
BC-50-UPVC	50
BC-63-UPVC	63
BC-75-UPVC	75
BC-90-UPVC	90
BC-110-UPVC	110
BC-125-UPVC	125
BC-140-UPVC	140
BC-160-UPVC	160
BC-200-UPVC	200
BC-225-UPVC	225
Tech Sheet 10256	

UPVC METRIC PIPE SYSTEM

Working Temperature:
All Pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain Fittings
12 bar Threaded Fittings
(excluding 75mm-110mm Unions, which are 10 bar rated)

20°C	30°C	40°C	50°C	60°C
16.0 bar	12.8 bar	9.2 bar	6.2 bar	3.5 bar

Unions



Equal Union

1050	ID mm
U-16-UPVC	16
U-20-UPVC	20
U-25-UPVC	25
U-32-UPVC	32
U-40-UPVC	40
U-50-UPVC	50
U-63-UPVC	63
U-75-UPVC	75
U-90-UPVC	90
U-110-UPVC	110
Tech Sheet 10256	



Plain x Threaded Union, BSPP

1050	ID mm	Thread
UT-16-UPVC	16	3/8"
UT-20-UPVC	20	1/2"
UT-25-UPVC	25	3/4"
UT-32-UPVC	32	1"
UT-40-UPVC	40	1.1/4"
UT-50-UPVC	50	1.1/2"
UT-63-UPVC	63	2"
UT-75-UPVC	75	2.1/2"
UT-90-UPVC	90	3"
UT-110-UPVC	110	4"
Tech Sheet 10256		

Threaded Adaptors



Plain x Male Threaded Adaptor, BSPP

1050	ID mm	OD mm	Thread
MTA-12-38-UPVC	12	16	3/8"
MTA-16-12-UPVC	16	20	1/2"
MTA-16-38-UPVC	16	20	3/8"
MTA-20-12-UPVC	20	25	1/2"
MTA-20-34-UPVC	20	25	3/4"
MTA-20-38-UPVC	20	25	3/8"
MTA-25-1-UPVC	25	32	1"
MTA-25-12-UPVC	25	32	1/2"
MTA-25-34-UPVC	25	32	3/4"
MTA-32-1-UPVC	32	40	1"
MTA-32-114-UPVC	32	40	1.1/4"
MTA-32-34UPVC	32	40	3/4"
MTA-40-1-UPVC	40	50	1"
MTA-40-112-UPVC	40	50	1.1/2"
MTA-40-114-UPVC	40	50	1.1/4"
MTA-50-112-UPVC	50	63	1.1/2"
MTA-50-114-UPVC	50	63	1.1/4"
MTA-50-2-UPVC	50	63	2"
MTA-63-112-UPVC	63	75	1.1/2"
MTA-63-2-UPVC	63	75	2"
MTA-63-212-UPVC	63	75	2.1/2"
MTA-75-2-UPVC	75	90	2"
MTA-75-212-UPVC	75	90	2.1/2"
MTA-75-3-UPVC	75	90	3"
MTA-90-212-UPVC	90	110	2.1/2"
MTA-90-3-UPVC	90	110	3"
MTA-90-4-UPVC	90	110	4"
MTA-110-3-UPVC	110	125	3"
MTA-110-4-UPVC	110	125	4"
MTA-110-5-UPVC	110	125	5"
Tech Sheet 10256			



Plain x Female Threaded Adaptor, BSPP

1050	OD mm	Thread
FTA-16-38-UPVC	16	3/8"
FTA-16-12-UPVC	16	1/2"
FTA-20-12-UPVC	20	1/2"
FTA-20-34-UPVC	20	3/4"
FTA-25-1-UPVC	25	1"
FTA-25-12-UPVC	25	1/2"
FTA-25-34-UPVC	25	3/4"
FTA-32-1-UPVC	32	1"
FTA-32-34-UPVC	32	3/4"
FTA-40-1-UPVC	40	1"
FTA-40-114-UPVC	40	1.1/4"
FTA-50-112-UPVC	50	1.1/2"
FTA-50-114-UPVC	50	1.1/4"
FTA-50-2-UPVC	50	2"
FTA-63-112-UPVC	63	1.1/2"
FTA-63-2-UPVC	63	2"
FTA-75-2-UPVC	75	2"
FTA-75-212-UPVC	75	2.1/2"
FTA-90-212-UPVC	90	2.1/2"
FTA-90-3-UPVC	90	3"
FTA-90-4-UPVC	90	4"
FTA-110-3-UPVC	110	3"
FTA-110-4-UPVC	110	4"
Tech Sheet 10256		

JAYMAC Industrial Hose & Accessories

Customers who bought from this page also purchased **Suction Hose**
see pages **1427-1431**



Fluid-Air Components Ltd

UPVC METRIC PIPE SYSTEM

Working Temperature:
All pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain fitting
12 bar Threaded fitting

Flanges



Stub Flange, Serrated Face

1050	ID mm
SF-20-UPVC	20
SF-25-UPVC	25
SF-32-UPVC	32
SF-40-UPVC	40
SF-50-UPVC	50
SF-63-UPVC	63
SF-75-UPVC	75
SF-90-UPVC	90
SF-110-UPVC	110
Tech Sheet 10256	



PN16 Full Face Flange

1050	ID mm	Flange Size
FPN16-20-UPVC	20	1/2"
FPN16-25-UPVC	25	3/4"
FPN16-32-UPVC	32	1"
FPN16-40-UPVC	40	1.1/4"
FPN16-50-UPVC	50	1.1/2"
FPN16-63-UPVC	63	2"
FPN16-75-UPVC	75	2.1/2"
FPN16-90-UPVC	90	3"
FPN16-110-UPVC	110	4"
Tech Sheet 10256		

ASA150 Full Face Flange

1050	ID mm	Flange Size
FASA150-25-UPVC	25	3/4"
FASA150-32-UPVC	32	1"
FASA150-40-UPVC	40	1.1/4"
FASA150-50-UPVC	50	1.1/2"
FASA150-63-UPVC	63	2"
FASA150-90-UPVC	90	3"
FASA150-110-UPVC	110	4"
Tech Sheet 10256		



PN16 Blanking Flange

1050	To Suit mm	Flange Size
BPN16-20-UPVC	20	1/2"
BPN16-25-UPVC	25	3/4"
BPN16-32-UPVC	32	1"
BPN16-40-UPVC	40	1.1/4"
BPN16-50-UPVC	50	1.1/2"
BPN16-63-UPVC	63	2"
BPN16-75-UPVC	75	2.1/2"
BPN16-110-UPVC	110	4"
Tech Sheet 10256		

ASA150 Blanking Flange

1050	To Suit mm	Flange Size
BASA150-32-UPVC	32	1"
BASA150-40-UPVC	40	1.1/4"
BASA150-50-UPVC	50	1.1/2"
BASA150-63-UPVC	63	2"
BASA150-75-UPVC	75	2.1/2"
BASA150-90-UPVC	90	3"
BASA150-110-UPVC	110	4"
Tech Sheet 10256		



PN16 Flange Gasket, EPDM

1050	To Suit mm
PNFG-20	20
PNFG-25	25
PNFG-32	32
PNFG-40	40
PNFG-50	50
PNFG-63	63
PNFG-75	75
PNFG-90	90
PNFG-110	110
Tech Sheet 10256	

ASA150 Flange Gasket, EPDM

1050	To Suit mm
ASAFG-20	20
ASAFG-25	25
ASAFG-32	32
ASAFG-50	50
ASAFG-63	63
ASAFG-75	75
ASAFG-90	90
Tech Sheet 10256	



PN16 Galvanised Backing Ring

1050	To Suit mm
GBR-25	25
GBR-32	32
GBR-40	40
GBR-50	50
GBR-63	63
GBR-75	75
GBR-90	90
GBR-110	110
Tech Sheet 10256	



PN16 UPVC Backing Ring

1050	To Suit mm
UPVCBR-20	20
UPVCBR-25	25
UPVCBR-32	32
UPVCBR-40	40
UPVCBR-50	50
UPVCBR-63	63
UPVCBR-110	110
Tech Sheet 10256	



Stub Flange Gasket, EPDM

1050	To Suit mm
SFG-20	20
SFG-32	32
SFG-40	40
SFG-50	50
SFG-63	63
SFG-75	75
SFG-90	90
SFG-110	110
Tech Sheet 10256	

UPVC METRIC PIPE SYSTEM

Industrial Valves

Working Temperature:
All pressures quoted are based on a working temperature of 20°C

PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain ends
12 bar Threaded ends up to 63mm.
10 bar 75mm-110mm

Double Union Ball Valve, EPDM Seals



1050	ID mm
DUBV-16-UPVC	16
DUBV-20-UPVC	20
DUBV-25-UPVC	25
DUBV-32-UPVC	32
DUBV-40-UPVC	40
DUBV-50-UPVC	50
DUBV-63-UPVC	63
DUBV-75-UPVC	75
DUBV-90-UPVC	90
DUBV-110-UPVC	110
Tech Sheet 10256	

Double Union Spring Check Valve, EPDM Seals



1050	ID mm
DUCV-20-UPVC	20
DUCV-25-UPVC	25
DUCV-32-UPVC	32
DUCV-40-UPVC	40
DUCV-50-UPVC	50
DUCV-63-UPVC	63
DUCV-75-UPVC	75
DUCV-90-UPVC	90
DUCV-110-UPVC	110
Tech Sheet 10256	

Double Union Foot Valve, EPDM Seals



1050	ID mm
DUFV-20-UPVC	20
DUFV-25-UPVC	25
DUFV-40-UPVC	40
DUFV-50-UPVC	50
DUFV-63-UPVC	63
DUFV-75-UPVC	75
DUFV-90-UPVC	90
DUFV-110-UPVC	110
Tech Sheet 10256	

UPVC Tubing

Working Temperature:
All pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar

4 Metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply. For full details please contact sales.



PN16, 6 Metre Lengths

0118	OD mm
UPVC/TUBE-6-16	16
UPVC/TUBE-6-20	20
UPVC/TUBE-6-25	25
UPVC/TUBE-6-32	32
UPVC/TUBE-6-40	40
UPVC/TUBE-6-50	50
UPVC/TUBE-6-63	63
UPVC/TUBE-6-75	75
UPVC/TUBE-6-90	90
UPVC/TUBE-6-110	110
UPVC/TUBE-6-140	140
UPVC/TUBE-6-160	160
UPVC/TUBE-6-225	225
Tech Sheet 10256	

PN16, 3 Metre Lengths

0118	OD mm
UPVC/TUBE-3-16	16
UPVC/TUBE-3-20	20
UPVC/TUBE-3-25	25
UPVC/TUBE-3-32	32
UPVC/TUBE-3-40	40
UPVC/TUBE-3-50	50
UPVC/TUBE-3-63	63
UPVC/TUBE-3-75	75
UPVC/TUBE-3-90	90
UPVC/TUBE-3-110	110
UPVC/TUBE-3-140	140
UPVC/TUBE-3-160	160
UPVC/TUBE-3-225	225
Tech Sheet 10256	

Clear UPVC Tubing

Please Note: Clear PVC pipe is not suitable for outdoor use without adequate UV protection.

4 Metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply. For full details please contact sales.



With Blue Tint, 5 Metre Lengths

0118	OD mm	Wall Thickness mm
CUPVC/TUBE2015	20	1.5
CUPVC/TUBE2515	25	1.5
CUPVC/TUBE3218	32	1.8
CUPVC/TUBE3224	32	2.4
CUPVC/TUBE4020	40	2
CUPVC/TUBE4030	40	3
CUPVC/TUBE5018	50	1.8
CUPVC/TUBE6318	63	1.8
CUPVC/TUBE6330	63	3
CUPVC/TUBE6347	63	4.7
CUPVC/TUBE-7518	75	1.8
CUPVC/TUBE-7536	75	3.6
CUPVC/TUBE-9018	90	1.8
CUPVC/TUBE-11022	110	2.2
CUPVC/TUBE-11053	110	5.3
CUPVC/TUBE-12525	125	2.5
CUPVC/TUBE-14028	140	2.8
CUPVC/TUBE-16032	160	3.2
CUPVC/TUBE-16047	160	4.7
Tech Sheet 10256		

Pipe Clips

Type 1 Type 2 Type 3



Black PP Clips

1050	ID mm	Type
PPCLIP-16	16	1
PPCLIP-20	20	1
PPCLIP-25	25	1
PPCLIP-32	32	1
PPCLIP-40	40	2
PPCLIP-50	50	2
PPCLIP-63	63	2
PPCLIP-75	75	2
PPCLIP-90	90	2
PPCLIP-110	110	2
PPCLIP-160	160	2
PPCLIP-225	225	3
Tech Sheet 10256		

Fluid-Air Components Ltd

UPVC METRIC PIPE SYSTEM

Working Temperature:
All pressures quoted are based on a working temperature of 20°C
PVC-U Systems should never be used for temperatures in excess of 60°C

Maximum Working Pressure:
16 bar Plain fitting
12 bar Threaded fitting

Hose Connections



Male Spigot, Metric x Hose Tail, Metric

1050	Tube OD mm	Hosetail mm
HN50-1212-UPVC	12	12
HN50-1616-UPVC	16	16
HN50-2020-UPVC	20	20
HN50-2525-UPVC	25	25
HN50-3232-UPVC	32	32
HN50-5050-UPVC	50	50
HN50-6060-UPVC	63	63

Tank Connectors



Plain x Female, BSPP

1050	Tube OD mm	Thread
TC-32-1-UPVC	32	1"
TC-10-114-UPVC	40	1.1/4"

Threaded Adaptors



Plain x Threaded Female Stainless Steel Reinforced, BSPP

1050	Tube OD mm	Thread
FFTA-50-112-UPVC	50	1.1/2"



Plain Male x Threaded Female Stainless Steel Reinforced, BSPP

1050	Tube OD mm	Thread
MFTA-50-112-UPVC	50	1.1/2"

Valves



Standard Plain Single Union Ball Valve, EPDM Seals

1050	Tube OD mm
SUBV-32-UPVC	32

Valve End



UPVC Plain Valve End

1050	Tube OD mm
VE-32-UPVC	32

Tubing Accessories



Emery Tape 38mm x 5 Metres

1050	Size
ET-38-5	38mm x 5 Metres



1" Glue Brush

1050	Description
GB-1	1" Glue Brush



Griffon UNI100 UPVC Cement

1050	Size ml
PVC250	250
PVC	500

Tech Sheet 876



Griffon WDF-05 Quick Set Cement

1050	Size ml
QSC-250	250
WDF-05	500



Griffon HCR-36 Chemical Cement

1050	Size ml
CHEMC-1000	1000



Griffon UNI100 GT Slow Setting UPVC Cement

1050	Size
SSC-5000-UPVC	5 Litre



Griffon Aqua-Max Pool Sealant

1050	Size grms
AQM-SEALANT	425



Griffon Chamfering Tool 1/2" - 2"

1050	Description
CT-12-2	Chamfering Tool 1/2" - 2"

UPVC IMPERIAL PIPE SYSTEM

Recommended Working Temperature:
0°C to 60°C

Pressure Ratings for Fittings:
15 bar (8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Sockets & Reducing Bushes



Equal Socket

1050	Nominal Bore ID
SO13-12-UPVC	1/2"
SO13-34-UPVC	3/4"
SO13-1-UPVC	1"
SO13-114-UPVC	1.1/4"
SO13-112-UPVC	1.1/2"
SO13-2-UPVC	2"
SO13-212-UPVC	2.1/2"
SO13-3-UPVC	3"
SO13-4-UPVC	4"
SO13-5-UPVC	5"
SO13-6-UPVC	6"
SO13-8-UPVC	8"
Tech Sheet 10254	



Reducing Socket

1050	Nominal Bore ID	Nominal Bore ID
RS13-3412-UPVC	3/4"	1/2"
RS13-134-UPVC	1"	3/4"
RS13-1141-UPVC	1.1/4"	1"
RS13-112112-UPVC	1.1/2"	1.1/4"
RS13-2112-UPVC	2"	1.1/2"
RS13-2122-UPVC	2.1/2"	2"
RS13-3212-UPVC	3"	2.1/2"
RS13-43-UPVC	4"	3"
Tech Sheet 10254		

Equal Barrel Nipples



Male, BSPT

1050	Thread
BN11-14-UPVC	1/4"
BN11-38-UPVC	3/8"
BN11-12-UPVC	1/2"
BN11-34-UPVC	3/4"
BN11-1-UPVC	1"
BN11-114-UPVC	1.1/4"
BN11-112-UPVC	1.1/2"
BN11-2-UPVC	2"
BN11-212-UPVC	2.1/2"
BN11-3-UPVC	3"
BN11-4-UPVC	4"
Tech Sheet 10254	



Socket, Imperial x Metric

1050	Nominal Bore ID	ID mm
SO14-3534-UPVC	3/4"	25
SO14-321-UPVC	1"	32
SO14-40114-UPVC	1.1/4"	40
SO14-50112-UPVC	1.1/2"	50
SO14-632-UPVC	2"	63
SO14-903-UPVC	3"	90
SO14-1104-UPVC	4"	110
Tech Sheet 10254		



Plain x Threaded Reducing Bush, BSPP

1050	Nominal Bore ID	Thread
RB30-3814-UPVC	3/8"	1/4"
RB30-1214-UPVC	1/2"	1/4"
RB30-1238-UPVC	1/2"	3/8"
RB30-3438-UPVC	3/4"	1/2"
RB30-112-UPVC	1"	3/4"
RB30-11434-UPVC	1.1/4"	1"
RB30-1121-UPVC	1.1/2"	1.1/4"
RB30-2114-UPVC	2"	1.1/2"
RB30-212112-UPVC	2.1/2"	2"
RB30-3212-UPVC	3"	2.1/2"
RB30-43-UPVC	4"	3"
Tech Sheet 10254		



Plain x Male, BSPT

1050	Thread	Nominal Bore ID	Length mm
BN12-38-UPVC	3/8"	3/8"	43
BN12-12-UPVC	1/2"	1/2"	50
BN12-34-UPVC	3/4"	3/4"	56
BN12-1-UPVC	1"	1"	63
BN12-114-UPVC	1.1/4"	1.1/4"	75
BN12-112-UPVC	1.1/2"	1.1/2"	88
BN12-2-UPVC	2"	2"	88
BN12-212-UPVC	2.1/2"	2.1/2"	106
BN12-3-UPVC	3"	3"	128
BN12-4-UPVC	4"	4"	153
Tech Sheet 10254			



Reducing Bush

1050	Nominal Bore ID	Nominal Bore ID
RB93-3412-UPVC	3/4"	1/2"
RB93-112-UPVC	1"	1/2"
RB93-134-UPVC	1"	3/4"
RB93-11412-UPVC	1.1/4"	1/2"
RB93-11434-UPVC	1.1/4"	3/4"
RB93-1141-UPVC	1.1/4"	1"
RB93-11234-UPVC	1.1/2"	3/4"
RB93-1121-UPVC	1.1/2"	1"
RB93-112114-UPVC	1.1/2"	1.1/4"
RB93-21-UPVC	2"	1"
RB93-2114-UPVC	2"	1.1/4"
RB93-2112-UPVC	2"	1.1/2"
RB93-212112-UPVC	2.1/2"	1.1/2"
RB93-2122-UPVC	2.1/2"	2"
RB93-3112-UPVC	3"	1.1/2"
RB93-32-UPVC	3"	2"
RB93-3212-UPVC	3"	2.1/2"
RB93-42-UPVC	4"	2"
RB93-4212-UPVC	4"	2.1/2"
RB93-43-UPVC	4"	3"
RB93-53-UPVC	5"	3"
RB93-54-UPVC	5"	4"
RB93-64-UPVC	6"	4"
RB93-86-UPVC	8"	6"
Tech Sheet 10254		

Tube O.D. - Size Conversion Table

Nominal Bore	Outside Diameter
3/8"	17.1mm
1/2"	21.3mm
3/4"	26.7mm
1"	33.4mm
1.1/4"	42.2mm
1.1/2"	48.3mm
2"	60.3mm
2.1/2"	75mm
3"	88.9mm
4"	114.3mm
5"	140mm
6"	168.3mm
8"	219.1mm

Fluid-Air Components Ltd

UPVC IMPERIAL PIPE SYSTEM

Recommended Working Temperature:
0°C to 60°C

Pressure Ratings for Fittings:
15 bar (8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Elbows & Bends



Equal 90° Elbow

1050	Nominal Bore ID
EL53-12-UPVC	1/2"
EL53-34-UPVC	3/4"
EL53-1-UPVC	1"
EL53-114-UPVC	1.1/4"
EL53-112-UPVC	1.1/2"
EL53-2-UPVC	2"
EL53-212-UPVC	2.1/2"
EL53-3-UPVC	3"
EL53-4-UPVC	4"
EL53-5-UPVC	5"
EL53-6-UPVC	6"
EL53-8-UPVC	8"
Tech Sheet 10254	



Equal 45° Elbow

1050	Nominal Bore ID
EY53-12-UPVC	1/2"
EY53-34-UPVC	3/4"
EY53-1-UPVC	1"
EY53-114-UPVC	1.1/4"
EY53-112-UPVC	1.1/2"
EY53-2-UPVC	2"
EY53-212-UPVC	2.1/2"
EY53-3-UPVC	3"
EY53-4-UPVC	4"
EY53-5-UPVC	5"
EY53-6-UPVC	6"
EY53-8-UPVC	8"
Tech Sheet 10254	



Plain x Threaded 90° Elbow, BSPP

1050	Nominal Bore ID	Thread
PVEP12	1/2"	1/2"
PVEP34	3/4"	3/4"
PVEP1	1"	1"
PVEP114	1.1/4"	1.1/4"
PVEP112	1.1/2"	1.1/2"
PVEP2	2"	2"
PVEP212	2.1/2"	2.1/2"
PVEP3	3"	3"
PVEP4	4"	4"
Tech Sheet 10254		



Plain x Threaded 45° Elbow, BSPP

1050	Nominal Bore ID	Thread
PVEP45-12	1/2"	1/2"
PVEP45-34	3/4"	3/4"
PVEP45-1	1"	1"
PVEP45-114	1.1/4"	1.1/4"
PVEP45-112	1.1/2"	1.1/2"
PVEP45-2	2"	2"
PVEP45-212	2.1/2"	2.1/2"
PVEP45-3	3"	3"
PVEP45-4	4"	4"
Tech Sheet 10254		



Equal 90° Bend Short Radius

1050	Nominal Bore ID
BE33-12-UPVC	1/2"
BE33-34-UPVC	3/4"
BE33-1-UPVC	1"
BE33-114-UPVC	1.1/4"
BE33-112-UPVC	1.1/2"
BE33-2-UPVC	2"
BE33-212-UPVC	2.1/2"
BE33-3-UPVC	3"
BE33-4-UPVC	4"
Tech Sheet 10254	

Tees



Equal 45° Tee

1050	Nominal Bore ID
TY43-12-UPVC	1/2"
TY43-34-UPVC	3/4"
TY43-1-UPVC	1"
TY43-114-UPVC	1.1/4"
TY43-112-UPVC	1.1/2"
TY43-2-UPVC	2"
Tech Sheet 10254	



Plain x Threaded Branch Tee, BSPP

1050	Nominal Bore ID	Thread
PVTP12	1/2"	1/2"
PVTP34	3/4"	3/4"
PVTP1	1"	1"
PVTP114	1.1/4"	1.1/4"
PVTP112	1.1/2"	1.1/2"
PVTP2	2"	2"
PVTP212	2.1/2"	2.1/2"
PVTP3	3"	3"
PVTP4	4"	4"
Tech Sheet 10254		



Equal Tee

1050	Nominal Bore ID
TE43-12-UPVC	1/2"
TE43-34-UPVC	3/4"
TE43-1-UPVC	1"
TE43-114-UPVC	1.1/4"
TE43-112-UPVC	1.1/2"
TE43-2-UPVC	2"
TE43-212-UPVC	2.1/2"
TE43-3-UPVC	3"
TE43-4-UPVC	4"
TE43-5-UPVC	5"
TE43-6-UPVC	6"
TE43-8-UPVC	8"
Tech Sheet 10254	

UPVC IMPERIAL PIPE SYSTEM

Working Temperature: 0°C to 60°C

Maximum Working Pressure: 15 bar (8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Crosses



Equal Cross

1050	Nominal Bore ID
CR33-12-UPVC	1/2"
CR33-34-UPVC	3/4"
CR33-1-UPVC	1"
CR33-114-UPVC	1.1/4"
CR33-112-UPVC	1.1/2"
CR33-2-UPVC	2"
CR33-212-UPVC	2.1/2"
Tech Sheet 10254	

Caps



Plain

1050	Nominal Bore ID
CA73-12-UPVC	1/2"
CA73-34-UPVC	3/4"
CA73-1-UPVC	1"
CA73-114-UPVC	1.1/4"
CA73-112-UPVC	1.1/2"
CA73-2-UPVC	2"
CA73-212-UPVC	2.1/2"
CA73-3-UPVC	3"
CA73-4-UPVC	4"
CA73-5-UPVC	5"
CA73-6-UPVC	6"
CA73-8-UPVC	8"
Tech Sheet 10254	

Unions



Equal Union

1050	Nominal Bore ID
UN83-12-UPVC	1/2"
UN83-34-UPVC	3/4"
UN83-1-UPVC	1"
UN83-114-UPVC	1.1/4"
UN83-112-UPVC	1.1/2"
UN83-2-UPVC	2"
UN83-212-UPVC	2.1/2"
UN83-3-UPVC	3"
UN83-4-UPVC	4"
Tech Sheet 10254	



Plain x Male Threaded Union, BSPP

1050	Nominal Bore ID	Thread
PVUPM112	1.1/2"	1.1/2"
PVUPM2-112	2"	1.1/2"
PVUPM2	2"	2"
Tech Sheet 10254		



Plain x Female Threaded Union, BSPP

1050	Nominal Bore ID	Thread
PVUPF12	1/2"	1/2"
PVUPF34	3/4"	3/4"
PVUPF1	1"	1"
PVUPF114	1.1/4"	1.1/4"
PVUPF112	1.1/2"	1.1/2"
PVUPF2	2"	2"
PVUPF212	2.1/2"	2.1/2"
PVUPF3	3"	3"
PVUPF4	4"	4"
Tech Sheet 10254		

Threaded Adaptors



Male, BSPP

1050	Nominal Bore ID	Thread
AD32-3-UPVC	1/2"	1/2"
AD32-4-UPVC	3/4"	1/2"
AD32-5-UPVC	3/4"	3/4"
AD32-6-UPVC	3/4"	1"
AD32-7-UPVC	1"	1"
AD32-8-UPVC	1"	1.1/4"
AD32-9-UPVC	1.1/4"	1.1/4"
AD32-10-UPVC	1.1/4"	1.1/2"
AD32-11-UPVC	1.1/2"	1.1/2"
AD32-12-UPVC	1.1/2"	2"
AD32-13-UPVC	2"	2"
AD32-15-UPVC	2.1/2"	2.1/2"
AD32-17-UPVC	3"	3"
AD32-19-UPVC	4"	4"
Tech Sheet 10254		



Plain x Female Threaded Adaptor, BSPP

1050	Nominal Bore ID	Thread
AD42-1212-UPVC	1/2"	1/2"
AD42-3412-UPVC	1/2"	3/4"
AD42-1234-UPVC	3/4"	1/2"
AD42-3434-UPVC	3/4"	3/4"
AD42-341-UPVC	3/4"	1"
AD42-134-UPVC	1"	3/4"
AD42-11-UPVC	1"	1"
AD42-1141-UPVC	1"	1.1/4"
AD42-114114-UPVC	1.1/4"	1.1/4"
AD42-112114-UPVC	1.1/4"	1.1/2"
AD42-112112-UPVC	1.1/2"	1.1/2"
AD42-2112-UPVC	1.1/2"	2"
AD42-1122-UPVC	2"	1.1/2"
AD42-22-UPVC	2"	2"
AD42-2122-UPVC	2"	2.1/2"
AD42-212212-UPVC	2.1/2"	2.1/2"
AD42-3212-UPVC	2.1/2"	3"
AD42-2123-UPVC	3"	2.1/2"
AD42-33-UPVC	3"	3"
AD42-43-UPVC	3"	4"
AD42-34-UPVC	4"	3"
AD42-44-UPVC	4"	4"
Tech Sheet 10254		

Fluid-Air Components Ltd

UPVC IMPERIAL PIPE SYSTEM

Working Temperature:
0°C to 60°C

Maximum Working Pressure:
15 bar
(8" with reduced safety factor)

For Air Ring Mains use ABS. UPVC is not suitable for use with compressed air.

UPVC = Unplasticized Poly Vinyl Chloride
ABS = Acrylonitrile-Butadiene-Styrene Copolymers

Hose Connections



Plain x Hose Tail

1050	Nominal Bore ID	To Suit Hose ID mm
HN63-12-UPVC	1/2"	20
HN63-34-UPVC	3/4"	25
HN63-1-UPVC	1"	32
HN63-114-UPVC	1.1/4"	40
HN63-112-UPVC	1.1/2"	50
HN63-2-UPVC	2"	60
Tech Sheet 10254		



Male, BSPP x Hose Tail

1050	Thread	To Suit Hose ID
PVHTM14-12	1/4"	12mm
PVHTM38-58	3/8"	16mm
PVHTM12	1/2"	1/2"
PVHTM12-34	1/2"	20mm
PVHTM34	3/4"	3/4"
PVHTM34-1	3/4"	25mm
PVHTM1	1"	1"
PVHTM1-114	1"	32mm
PVHTM114-112	1.1/4"	40mm
PVHTM112-2	1.1/2"	50mm
PVHTM2-212	2"	60mm
Tech Sheet 10254		



Female, BSPP x Hose Tail

1050	Thread	To Suit Hose ID mm
HN64-3416-UPVC	3/4"	16
HN64-120-UPVC	1"	20
HN64-11425-UPVC	1.1/4"	25
HN64-11230-UPVC	1.1/2"	30
HN64-240-UPVC	2"	40
HN64-21450-UPVC	2.1/4"	50
HN64-23460-UPVC	2.3/4"	60
Tech Sheet 10254		

Tank Connectors



Plain x Female, BSPP

1050	Nominal Bore ID	Thread
TC93-12-UPVC	1/2"	1/2"
TC93-34-UPVC	3/4"	3/4"
TC93-1-UPVC	1"	1"
TC93-114-UPVC	1.1/4"	1.1/4"
TC93-112-UPVC	1.1/2"	1.1/2"
TC93-2-UPVC	2"	2"
TC93-212-UPVC	2.1/2"	2.1/2"
TC93-3-UPVC	3"	3"
TC93-4-UPVC	4"	4"
Tech Sheet 10254		

Flanges



Stub Flange, Serrated Face

1050	Nominal Bore ID
ST23-12-UPVC	1/2"
ST23-34-UPVC	3/4"
ST23-1-UPVC	1"
ST23-114-UPVC	1.1/4"
ST23-112-UPVC	1.1/2"
ST23-2-UPVC	2"
ST23-212-UPVC	2.1/2"
ST23-3-UPVC	3"
ST23-4-UPVC	4"
ST23-5-UPVC	5"
ST23-6-UPVC	6"
ST23-8-UPVC	8"
Tech Sheet 10254	



Full Face Table E

1050	Nominal Bore ID
FF30-12-UPVC	1/2"
FF30-34-UPVC	3/4"
FF30-1-UPVC	1"
FF30-114-UPVC	1.1/4"
FF30-112-UPVC	1.1/2"
FF30-2-UPVC	2"
FF30-3-UPVC	3"
FF30-4-UPVC	4"
Tech Sheet 10254	



PN16 Blanking Flange

1050	Size
BF00-1-UPVC	1"
BF00-112-UPVC	1.1/2"
BF00-2-UPVC	2"
BF00-3-UPVC	3"
BF00-4-UPVC	4"
BF00-5-UPVC	5"
Tech Sheet 10254	

Tube O.D. - Size Conversion Table

Nominal Bore	Outside Diameter	Nominal Bore	Outside Diameter
3/8"	17.1mm	2.1/2"	75mm
1/2"	21.3mm	3"	88.9mm
3/4"	26.7mm	4"	114.3mm
1"	33.4mm	5"	140mm
1.1/4"	42.2mm	6"	168.3mm
1.1/2"	48.3mm	8"	219.1mm
2"	60.3mm		



BS4504, PN16 Flange Gasket

1050	Size
SF16-12	1/2"
SF16-34	3/4"
SF16-1	1"
SF16-114	1.1/4"
SF16-112	1.1/2"
SF16-2	2"
SF16-3	3"
SF16-4	4"
SF16-6	6"
Tech Sheet 10254	



BS10, Table E Flange Gasket

1050	Size
SF10-12	1/2"
SF10-34	3/4"
SF10-1	1"
SF10-114	1.1/4"
SF10-112	1.1/2"
SF10-2	2"
SF10-212	2.1/2"
SF10-3	3"
SF10-4	4"
SF10-6	6"
Tech Sheet 10254	



PN16 Galvanised Backing Ring

1050	Size
GB16-12	1/2"
GB16-34	3/4"
GB16-1	1"
GB16-114	1.1/4"
GB16-112	1.1/2"
GB16-2	2"
GB16-212	2.1/2"
GB16-3	3"
GB16-4	4"
GB16-5	5"
GB16-6	6"
GB16-8	8"
Tech Sheet 10254	

UPVC IMPERIAL PIPE SYSTEM

Valves



Economy Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVD13-12-PVC	1/2"
BVD13-34-PVC	3/4"
BVD13-1-PVC	1"
BVD13-114-PVC	1.1/4"
BVD13-112-PVC	1.1/2"
BVD13-2-PVC	2"
BVD13-212-PVC	2.1/2"
BVD13-3-PVC	3"
BVD13-4-PVC	4"

Tech Sheet 10254



Industrial Double Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVI13-38-PVC	3/8"
BVI13-12-PVC	1/2"
BVI13-34-PVC	3/4"
BVI13-1-PVC	1"
BVI13-114-PVC	1.1/4"
BVI13-112-PVC	1.1/2"
BVI13-2-PVC	2"
BVI13-212-PVC	2.1/2"
BVI13-3-PVC	3"
BVI13-4-PVC	4"

Tech Sheet 10254



Industrial 3 Way Ball Valve, L Port, EPDM Seals

0118	Nominal Bore ID
BVL13-12-PVC	1/2"
BVL13-34-PVC	3/4"
BVL13-1-PVC	1"
BVL13-114-PVC	1.1/4"
BVL13-112-PVC	1.1/2"
BVL13-2-PVC	2"

Tech Sheet 10254



Industrial 3 Way Ball Valve, T Port, EPDM Seals

0118	Nominal Bore ID
BVT13-12-PVC	1/2"
BVT13-34-PVC	3/4"
BVT13-1-PVC	1"
BVT13-112-PVC	1.1/2"
BVT13-2-PVC	2"

Tech Sheet 10254



Industrial Check Valve, EPDM Seals

0118	Nominal Bore ID
CVD13-12-PVC	1/2"
CVD13-34-PVC	3/4"
CVD13-1-PVC	1"
CVD13-114-PVC	1.1/4"
CVD13-112-PVC	1.1/2"
CVD13-2-PVC	2"

Tech Sheet 10254

FT PRO



For **Air Blow Guns**
...see pages **1549-1557**

UPVC Tubing

NOTE: 6 metre length tube is available on a 3 to 5 working day delivery service. Specified delivery dates and times can not be guaranteed. Carriage is charged as an extra based on weight and delivery service required. Please speak to our sales department for further details.

Delivery of 3 metre lengths may take up to 48 hours.



Class C, 9 bar, 3 Metre Lengths

0118	Nominal Bore
UPVC/CTUBE-3-2	2"
UPVC/CTUBE-3-212	2.1/2"
UPVC/CTUBE-3-3	3"
UPVC/CTUBE-3-4	4"
UPVC/CTUBE-3-6	6"
UPVC/CTUBE-3-8	8"

Tech Sheet 10254

Class C, 9 bar, 6 Metre Lengths

0118	Nominal Bore
UPVC/CTUBE-6-2	2"
UPVC/CTUBE-6-212	2.1/2"
UPVC/CTUBE-6-3	3"
UPVC/CTUBE-6-4	4"
UPVC/CTUBE-6-5	5"
UPVC/CTUBE-6-6	6"

Tech Sheet 10254

Class E, 15 bar, 3 Metre Lengths

0118	Nominal Bore
UPVC/ETUBE-3-12	1/2"
UPVC/ETUBE-3-34	3/4"
UPVC/ETUBE-3-1	1"
UPVC/ETUBE-3-114	1.1/4"
UPVC/ETUBE-3-112	1.1/2"
UPVC/ETUBE-3-2	2"
UPVC/ETUBE-3-3	3"
UPVC/ETUBE-3-4	4"

Tech Sheet 10254

Class E, 15 bar, 6 Metre Lengths

0118	Nominal Bore
UPVC/ETUBE-6-12	1/2"
UPVC/ETUBE-6-34	3/4"
UPVC/ETUBE-6-1	1"
UPVC/ETUBE-6-114	1.1/4"
UPVC/ETUBE-6-112	1.1/2"
UPVC/ETUBE-6-2	2"
UPVC/ETUBE-6-3	3"
UPVC/ETUBE-6-4	4"

Tech Sheet 10254

Fluid-Air Components Ltd

UPVC IMPERIAL PIPE SYSTEM

UPVC Tubing



Class 7, Plain End, 3 Metre Lengths

0118	Size	Pipe OD mm	Pipe ID mm
UPVC/7TUBE-3-12	1/2"	21.4	13.4
UPVC/7TUBE-3-1	1"	33.6	24
UPVC/7TUBE-3-112	1 1/2"	48.3	37.3
UPVC/7TUBE-3-2	2"	60.3	48.3

Class 7, Plain End, 6 Metre Lengths

0118	Size	Pipe OD mm	Pipe ID mm
UPVC/7TUBE-6-112	1.1/2"	48.3	37.3

Threaded Adaptors



Equal, Plain x Threaded Female Stainless Steel Reinforced, BSPP

1050	Nominal Bore ID	Thread
ESRI-12	1/2"	1/2"
ESRI-34	3/4"	3/4"
ESRI-1	1"	1"
ESRI-2	2"	2"



Equal, Plain x Threaded Female

1050	Tube NB	Thread
ESI-12	1/2"	1/2"
ESI-34	3/4"	3/4"
ESI-1	1"	1"
ESI-114	1.1/4"	1.1/4"
ESI-112	1.1/2"	1.1/2"
ESI-2	2"	2"

Unions



Plain x Brass Composite Male Threaded Union, BSPP


1050	Nominal Bore ID	Male BSPP
MBU-1	1"	1"



Plain x Brass Composite Female Threaded Union, BSPP

1050	Nominal Bore ID	Female BSPP
FBU-112	1.1/2"	1.1/2"

Reducing Bushes




Plain x Threaded Female, BSPP

1050	Nominal Bore ID	Thread
RB30-1238-UPVC	3/4"	1/2"



Threaded Male x Female, BSPP (Long Pattern)

1050	Male Thread	Female Thread
PVR112-1	1.1/2"	1"
PVR2-1	2"	1"
PVR212-112	2.1/2"	1.1/2"



Threaded Male x Female, BSPP (Short Pattern)

1050	Male Thread	Female Thread
PVRB34-12	3/4"	1/2"
PVRB1-34	1"	3/4"
PVRB114-1	1.1/4"	1"
PVRB112-114	1.1/2"	1.1/4"
PVRB2-112	2"	1.1/2"

Equal Hex Nipples



Equal, Male, BSPP

1050	Thread
PVN1	1"
PVN2	2"

Unequal Hex Nipples



Unequal, Male, BSPP

1050	Thread	Thread
PVRN1-34	1"	3/4"
PVRN112-114	1.1/2"	1.1/4"

Backnuts



Female, BSPP

1050	Thread
PVLN12	1/2"
PVLN1	1"
PVLN114	1.1/4"

Valve End



Female, BSPP

1050	Thread
TVI-2	2"

Valves



Standard Plain Single Union Ball Valve, EPDM Seals

0118	Nominal Bore ID
BVSU-34	3/4"
BVSU-1	1"
BVSU-114	1.1/4"
BVSU-112	1.1/2"



Standard Lever Operated Butterfly alve, EPDM Liner

0118	Nominal Bore ID
BVBS-6	6"

Pipe Clips



Black PP Pipe Clips

1050	Nominal Bore ID	Type
IPPCLIP-12	1/2"	1
IPPCLIP-34	3/4"	1
IPPCLIP-1	1"	1
IPPCLIP-114	1.1/4"	2
IPPCLIP-112	1.1/2"	2
IPPCLIP-2	2"	2
IPPCLIP-212	2.1/2"	2
IPPCLIP-3	3"	2
IPPCLIP-4	4"	2
IPPCLIP-5	5"	3

Spacing Blocks



Black PP Spacing Block

1050	Nominal Bore ID
IPPSB-1	1" - 32mm
IPPSB-2	2" - 63mm

UPVC THREADED FITTINGS

Double Socket



Female, BSPP

1050	Thread
PVS12	1/2"
PVS34	3/4"
PVS1	1"
PVS114	1.1/4"
PVS112	1.1/2"
PVS2	2"

Reducing Socket



Female, BSPP

1050	Thread	Thread
PVRS12-38	1/2"	3/8"
PVRS34-12	3/4"	1/2"
PVRS1-34	1"	3/4"
PVRS114-1	1.1/4"	1"
PVRS112-114	1.1/2"	1.1/4"
PVRS2-112	2"	1.1/2"
PVRS3-212	3"	2.1/2"
PVRS4-3	4"	3"

Enlarging Piece



Male x Female, BSPP

1050	Male Thread	Female Thread
PVEN38-12	3/8"	1/2"
PVEN12-34	1/2"	3/4"
PVEN34-1	3/4"	1"
PVEN1-114	1"	1.1/4"
PVEN114-112	1.1/4"	1.1/2"
PVEN112-2	1.1/2"	2"
PVEN2-212	2"	2.1/2"
PVEN212-3	2.1/2"	3"
PVEN3-4	3"	4"

Reducing Male x Female



Male x Female, BSPP

1050	Male Thread	Female Thread
PVR12-38	1/2"	3/8"
PVR34-38	3/4"	3/8"
PVR34-12	3/4"	1/2"
PVR1-38	1"	3/8"
PVR1-12	1"	1/2"
PVR1-34	1"	3/4"
PVR114-12	1.1/4"	1/2"
PVR114-34	1.1/4"	3/4"
PVR114-1	1.1/4"	1"
PVR112-34	1.1/2"	3/4"
PVR112-1	1.1/2"	1"
PVR2-1	2"	1"
PVR2-114	2"	1.1/4"
PVR2-112	2"	1.1/2"
PVR212-112	2.1/2"	1.1/2"
PVR212-2	2.1/2"	2"
PVR3-112	3"	1.1/2"
PVR3-2	3"	2"
PVR3-212	3"	2.1/2"
PVR4-2	4"	2"
PVR4-212	4"	2.1/2"
PVR4-3	4"	3"

Reducing Bush Male x Female



Male x Female, BSPP

1050	Male Thread	Female Thread
PVRB34-12	3/4"	1/2"
PVRB1-34	1"	3/4"
PVRB114-1	1.1/4"	1"
PVRB112-114	1.1/2"	1.1/4"
PVRB2-112	2"	1.1/2"
PVRB212-2	2.1/2"	2"
PVRB3-212	3"	2.1/2"
PVRB4-3	4"	3"

Nipple



Male, BSPP

1050	Thread
PVN38	3/8"
PVN12	1/2"
PVN34	3/4"
PVN1	1"
PVN114	1.1/4"
PVN112	1.1/2"
PVN2	2"
PVN212	2.1/2"
PVN4	4"

Reducing Nipple



Male, BSPP

1050	Thread	Thread
PVRN34-12	3/4"	1/2"
PVRN1-34	1"	3/4"
PVRN114-1	1.1/4"	1"
PVRN112-114	1.1/2"	1.1/4"
PVRN212-2	2.1/2"	2"
PVRN3-212	3"	2.1/2"
PVRN4-3	4"	3"

RUST-OLEUM



For **Leak Seal**
...see pages **1564**

Fluid-Air Components Ltd

UPVC THREADED FITTINGS

Elbow 90º



Female, BSPP

1050	Thread
PVE12	1/2"
PVE34	3/4"
PVE1	1"
PVE114	1.1/4"
PVE112	1.1/2"
PVE2	2"
PVE212	2.1/2"
PVE3	3"

Elbow 45°



Female, BSPP

1050	Thread
PVE45-38	3/8"
PVE45-12	1/2"
PVE45-34	3/4"
PVE45-1	1"
PVE45-114	1.1/4"
PVE45-112	1.1/2"
PVE45-2	2"
PVE45-212	2.1/2"
PVE45-3	3"
PVE45-4	4"

Tee 90º



Female, BSPP

1050	Thread
PVT38	3/8"
PVT12	1/2"
PVT34	3/4"
PVT1	1"
PVT114	1.1/4"
PVT112	1.1/2"
PVT2	2"
PVT3	3"
PVT4	4"

Union



Female, BSPP

1050	Thread
PVU38	3/8"
PVU12	1/2"
PVU34	3/4"
PVU1	1"
PVU114	1.1/4"
PVU112	1.1/2"
PVU2	2"
PVU212	2.1/2"
PVU3	3"
PVU4	4"

Cap



Female, BSPP

1050	Thread
PVC38	3/8"
PVC12-CAP	1/2"
PVC34	3/4"
PVC1	1"
PVC114	1.1/4"
PVC112	1.1/2"
PVC2	2"
PVC212	2.1/2"
PVC3	3"
PVC4	4"

Plug



Male, BSPP

1050	Thread
PVP38	3/8"
PVP12	1/2"
PVP34	3/4"
PVP1	1"
PVP112	1.1/2"
PVP2	2"
PVP212	2.1/2"
PVP3	3"
PVP4	4"

Locknuts



Female, BSPP

1050	Thread
PVLN38	3/8"
PVLN12	1/2"
PVLN34	3/4"
PVLN1	1"
PVLN114	1.1/4"
PVLN112	1.1/2"
PVLN2	2"
PVLN212	2.1/2"
PVLN3	3"
PVLN4	4"

FT PRO



For **Air Prep**
...see pages **637-656**

M-Press Fittings Ltd



Stainless Steel 316L & Copper Press Fit Piping System

M-Press provides solutions to meet the demands of various industry applications, with capabilities of up to 168mm

1116


Fluid-Air Components Ltd

efnkl iroirp c cc a cc

stainless steel

50 Year Warranty

new product



Choose M-Press for industry-leading Press Fit solutions

1117

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

M-Press's stainless steel ring main system is the perfect solution for all ring main installation requirements.

The M-Press Press Fit system is an all-inclusive and quality-assured system designed to streamline on-site compliances for installers. It removes the need for traditional site hot-work permits, making the installation process hassle-free and efficient. The M-Profile system is equipped with advanced pressing technology that ensures a confident installation process, saving installers considerable time and effort, which ultimately leads to increased productivity and cost savings.



M-Press's Stainless Steel system has been engineered for use in a diverse range of industry applications, providing installers with a versatile solution. This and all other system features ensure that the installation process is always of the highest quality, making the installer's work hassle-free and efficient.

Features:

- WRAS certified
- Gas EN331 certified
- High molybdenum content offering excellent corrosion resistance
- Universally compatible with all M-Profile systems
- Reliable and durable press system
- Leak-free performance
- Excellent hygienic characteristics

Advantages:

- Removes the need for traditional site hot-work permits
- Ease of installation
- Increased productivity
- Wide choice of products and seal types
- Clean and hassle-free handling
- Lightweight system

The M-Press system is manufactured to meet the highest standards and materials:

- ✔ **M-Press fittings material no:** 1.4404 according to EN 10088 /316L
- ✔ **Threaded fittings material no:** 1.4408 according to EN 10283 /316L
- ✔ **Pipes material no:** 1.4404 according to EN 10312 (ECO 316L).

M-Press can offer solutions for all industry application demands up to 168mm

1118

Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

EPDM Seals



WRAS APPROVED PRODUCT

Material	Stainless Steel 316L
Formed Fittings:	1.4404 according to EN 10088 /316L
Threaded Fittings:	1.4408 according to EN 10283 /316L
Pipe:	1.4404 according to EN 10312 (ECO 316L)
Seal Type:	EPDM
Description:	Ethylene Propylene Diene Mnomer

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

Applications

- Potable water services
- Hydronic heating
- Compressed air
- BCWS (Boosted cold water services)
- Chilled water applications
- Purified water
- Fire suppression systems
- Inert gases

Application Services

- Drinking water
- HWS and commercial/domestic heating
- Compressed air (<25mg/M³ compressor oil concentration)
- Risers and plant rooms
- Cooling water (chilled water) with glycol <50% concentration
- Grey water
- Low pressure steam condensate
- Kitchen fire sprinkler/suppression systems
- Helium, Neon, Argon

HNBR Gas Approved Seals



DVGW DVGW G260 & G262

Material	Stainless Steel 316L
Formed Fittings:	1.4404 according to EN 10088 /316L
Threaded Fittings:	1.4408 according to EN 10283 /316L
Pipe:	1.4404 according to EN 10312 (ECO 316L)
Seal Type:	HNBR
Description:	Hydrogenated Nitrile Butadiene Rubber

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

Applications

- Industrial offshore applications
- Low pressure hydraulic systems
- Hot water supply
- Flammable gases (DVGW G260, 262)
- Inert gases

Application Services

- Commercial / industrial methane gas
- Low pressure hydraulic oil
- Commercial / industrial LPG and natural gases
- Helium, Argon, Neon

FKM Seals



Material	Stainless Steel 316L
Formed Fittings:	1.4404 according to EN 10088 /316L
Threaded Fittings:	1.4408 according to EN 10283 /316L
Pipe:	1.4404 according to EN 10312 (ECO 316L)
Seal Type:	FKM
Description:	Viton Fluroelastomer

Temperature: -30°C to +180°C (+230°C for short periods)


Pressure: PN16 16 bar

Applications

- Domestic and commercial solar thermal heating
- Domestic and commercial heating
- Commercial steam condensate
- Industrial compressed air
- Acidic transportation
- Hydraulic applications
- Oil and fuels

Application Services

- High temperature heating and hot water systems
- Commercial warehouse/large area heating systems
- Low pressure steam condensate
- Industrial compressed air systems (>25mg/M³ compressor oil concentration)
- Some acid solutions
- Hydraulic oils
- Heavy oil and fuel transportation (Kerosene, Paraffin, Diesel)
- Please enquire for exact suitability



stainless steel

50 Year Warranty

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

Adaptors



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1202015012	15	3/8"
1202015012	15	1/2"
1202015034	15	3/4"
1202022012	22	1/2"
1202022034	22	3/4"
1202022100	22	1"
1202028034	28	3/4"
1202028100	28	1"
1202035100	35	1"
1202035114	35	1.1/4"
1202042112	42	1.1/2"
1202054200	54	2"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1702015038	15	3/8"
1702015012	15	1/2"
1702015034	15	3/4"
1702022012	22	1/2"
1702022034	22	3/4"
1702022100	22	1"
1702028034	28	3/4"
1702028100	28	1"
1702035100	35	1"
1702035114	35	1.1/4"
1702042112	42	1.1/2"
1702054200	54	2"



Female x Female Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1402015038	15	3/8"
1402015012	15	1/2"
1402015034	15	3/4"
1402022012	22	1/2"
1402022034	22	3/4"
1402022100	22	1"
1402028034	28	3/4"
1402028100	28	1"
1402035100	35	1"
1402035114	35	1.1/4"
1402042112	42	1.1/2"
1402054200	54	2"



WRAS



Female x Male Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1201015012	15	1/2"
1201015034	15	3/4"
1201015038	15	3/8"
1201022012	22	1/2"
1201022034	22	3/4"
1201022100	22	1"
1201028034	28	3/4"
1201028100	28	1"
1201035100	35	1"
1201035114	35	1.1/4"
1201042112	42	1.1/2"
1201054200	54	2"

DVGW



Female x Male Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1701015012	15	1/2"
1701015034	15	3/4"
1701015038	15	3/8"
1701022012	22	1/2"
1701022034	22	3/4"
1701022100	22	1"
1701028034	28	3/4"
1701028100	28	1"
1701035100	35	1"
1701035114	35	1.1/4"
1701042112	42	1.1/2"
1701054200	54	2"



Female x Male Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1401015012	15	1/2"
1401015034	15	3/4"
1401015038	15	3/8"
1401022012	22	1/2"
1401022034	22	3/4"
1401022100	22	1"
1401028034	28	3/4"
1401028100	28	1"
1401035100	35	1"
1401035114	35	1.1/4"
1401042112	42	1.1/2"
1401054200	54	2"

Union Adaptors with Flat Seal



WRAS



Female x Male Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1208015012	15	1/2"
1208022034	22	3/4"
1208028100	28	1"
1208035114	35	1.1/4"
1208042112	42	1.1/2"
1208054200	54	2"

DVGW



Female x Male Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1708015012	15	1/2"
1708022034	22	3/4"
1708028100	28	1"
1708035114	35	1.1/4"
1708042112	42	1.1/2"
1708054200	54	2"



Female x Male Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1408015012	15	1/2"
1408022034	22	3/4"
1408028100	28	1"
1408035114	35	1.1/4"
1408042112	42	1.1/2"
1408054200	54	2"

Fluid-Air Components Ltd

Straight Couplings



WRAS



Female x Female, EPDM Seal

3102	Size mm
120001515	15
120002222	22
120002828	28
120003535	35
120004242	42
120005454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3102	Size mm
170001515	15
170002222	22
170002828	28
170003535	35
170004242	42
170005454	54



Female x Female, FKM Seal

3102	Size mm
140001515	15
140002222	22
140002828	28
140003535	35
140004242	42
140005454	54

Slip Couplers



WRAS



Female x Female, EPDM Seal

3102	Size mm
120401515	15
120402222	22
120402828	28
120403535	35
120404242	42
120405454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3102	Size mm
170401515	15
170402222	22
170402828	28
170403535	35
170404242	42
170405454	54



Female x Female, FKM Seal

3102	Size mm
140401515	15
140402222	22
140402828	28
140403535	35
140404242	42
140405454	54

Socket Reducers



WRAS



Female x Male Plain End, EPDM Seal

3102	Size mm	Size mm
124302215	22	15
124302815	28	15
124302822	28	22
124303522	35	22
124303528	35	28
124304222	42	22
124304228	42	28
124304235	42	35
124305422	54	22
124305428	54	28
124305435	54	35
124305442	54	42

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3102	Size mm	Size mm
174302215	22	15
174302815	28	15
174302822	28	22
174303522	35	22
174303528	35	28
174304222	42	22
174304228	42	28
174304235	42	35
174305422	54	22
174305428	54	28
174305435	54	35
174305442	54	42



Female x Male Plain End, FKM Seal

3102	Size mm	Size mm
144302215	22	15
144302815	28	15
144302822	28	22
144303522	35	22
144303528	35	28
144304222	42	22
144304228	42	28
144304235	42	35
144305422	54	22
144305428	54	28
144305435	54	35
144305442	54	42

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

End Caps



WRAS



Female x End Cap, EPDM Seal

3102	Size mm
1241015	15
1241022	22
1241028	28
1241035	35
1241042	42
1241054	54

DVGW



Female x End Cap, HNBR Gas Approved Seal

3102	Size mm
1741015	15
1741022	22
1741028	28
1741035	35
1741042	42
1741054	54



Female x End Cap, FKM Seal

3102	Size mm
1441015	15
1441022	22
1441028	28
1441035	35
1441042	42
1441054	54

45° Elbows



WRAS



Female x Female, EPDM Seal

3102	Size mm
122301515	15
122302222	22
122302828	28
122303535	35
122304242	42
122305454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3102	Size mm
172301515	15
172302222	22
172302828	28
172303535	35
172304242	42
172305454	54



Female x Female, FKM Seal

3102	Size mm
142301515	15
142302222	22
142302828	28
142303535	35
142304242	42
142305454	54

45° Street Elbows



WRAS



Female x Male Plain End, EPDM Seal

3102	Size mm
122401515	15
122402222	22
122402828	28
122403535	35
122404242	42
122405454	54

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3102	Size mm
172401515	15
172402222	22
172402828	28
172403535	35
172404242	42
172405454	54



Female x Male Plain End, FKM Seal

3102	Size mm
142401515	22
142402222	28
142402828	35
142403535	42
142404242	54
142405454	54

EPDM Seals

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

WRAS



Description:	Ethylene Propylene Diene Mnomer

HNBR Gas Approved Seals

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

DVGW

DVGW G260 & G262



Description:	Hydrogenated Nitrile Butadiene Rubber

FKM Seals

Temperature: -30°C to +180°C (+230°C for short periods)

Pressure: PN16 16 bar



Description:	Viton Fluroelastomer

Fluid-Air Components Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

Equal Tees



WRAS



Female x Female x Female, EPDM Seal

3102	Size mm
12100151515	15
12100222222	22
12100282828	28
12100353535	35
12100424242	42
12100545454	54

DVGW



Female x Female x Female, HNBR Gas Approved Seal

3102	Size mm
17100151515	15
17100222222	22
17100282828	28
17100353535	35
17100424242	42
17100545454	54



Female x Female x Female, FKM Seal

3102	Size mm
14100151515	15
14100222222	22
14100282828	28
14100353535	35
14100424242	42
14100545454	54

RIDGID



You might also need...

RIDGID RP 351 Press Tool

...see page **1744**

Reducing Tees



WRAS



Female x Female x Female, EPDM Seal

3102	Size mm	Size mm	Size mm
12110221522	22	15	22
12110281528	28	25	28
12110282228	28	22	28
12110352235	35	22	35
12110352835	35	28	35
12110422242	42	22	42
12110422842	42	28	42
12110423542	42	35	42
12110542254	54	22	54
12110542854	54	28	54
12110543554	54	35	54
12110544254	54	42	54

DVGW



Female x Female x Female, HNBR Gas Approved Seal

3102	Size mm	Size mm	Size mm
17110221522	22	15	22
17110281528	28	25	28
17110282228	28	22	28
17110352235	35	22	35
17110352835	35	28	35
17110422242	42	22	42
17110422842	42	28	42
17110423542	42	35	42
17110542254	54	22	54
17110542854	54	28	54
17110543554	54	35	54
17110544254	54	42	54



Female x Female x Female, FKM Seal

3102	Size mm	Size mm	Size mm
14110221522	22	15	22
14110281528	28	25	28
14110282228	28	22	28
14110352235	35	22	35
14110352835	35	28	35
14110422242	42	22	42
14110422842	42	28	42
14110423542	42	35	42
14110542254	54	22	54
14110542854	54	28	54
14110543554	54	35	54
14110544254	54	42	54



WRAS



Female x Female Threaded, BSPP x Female, EPDM Seal

3102	Size mm	Thread	Size mm
12120151215	15	1/2"	15
12120153815	15	3/8"	15
12120221222	22	1/2"	22
12120223422	22	3/4"	22
12120281228	28	1/2"	28
12120283428	28	3/4"	28
12120351235	35	1/2"	35
12120353435	35	3/4"	35
12120421242	42	1/2"	42
12120423442	42	3/4"	42
12120543454	54	1/2"	54
12120541254	54	3/4"	54

DVGW



Female x Female Threaded, BSPP x Female, HNBR Gas Approved Seal

3102	Size mm	Thread	Size mm
17120151215	15	1/2"	15
17120153815	15	3/8"	15
17120221222	22	1/2"	22
17120223422	22	3/4"	22
17120281228	28	1/2"	28
17120283428	28	3/4"	28
17120351235	35	1/2"	35
17120353435	35	3/4"	35
17120421242	42	1/2"	42
17120423442	42	3/4"	42
17120541254	54	1/2"	54
17120543454	54	3/4"	54



Female x Female Threaded, BSPP x Female, FKM Seal

3102	Size mm	Thread	Size mm
14120151215	15	1/2"	15
14120153815	15	3/8"	15
14120221222	22	1/2"	22
14120223422	22	3/4"	22
14120281218	28	1/2"	28
14120283428	28	3/4"	28
14120351235	35	1/2"	35
14120353435	35	3/4"	35
14120421242	42	1/2"	42
14120423442	42	3/4"	42
14120541254	54	1/2"	54
14120543454	54	3/4"	54

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

90° Elbows



WRAS



Female x Female, EPDM Seal

3102	Size mm
122001515	15
122002222	22
122002828	28
122003535	35
122004242	42
122005454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3102	Size mm
172001515	15
172002222	22
172002828	28
172003535	35
172004242	42
172005454	54



Female x Female, FKM Seal

3102	Size mm
142001515	15
142002222	22
142002828	28
142003535	35
142004242	42
142005454	54

90° Bends



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1232015012	15	1/2"
1232012038	15	3/8"
1232022034	22	3/4"
1232022012	22	1/2"
1232028012	28	1/2"
1232028100	28	1"
1232035012	35	1/2"
1232035114	34	1.1/4"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1732015012	15	1/2"
1732015038	15	3/8"
1732015034	22	3/4"
1732015012	22	1/2"
1732028012	28	1/2"
1732028100	28	1"
1732035012	35	1/2"
1732035114	34	1.1/4"



Female x Female Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1432015012	15	1/2"
1432015038	15	3/8"
1432022034	22	3/4"
1432022012	22	1/2"
1432028012	28	1/2"
1432028100	28	1"
1432035012	35	1/2"
1432035114	34	1.1/4"



WRAS



Female x Male Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1231015012	15	1/2"
1231015038	15	3/8"
1231022034	22	34"
1231028100	28	1"
1231035114	35	1.1/4"
1231042112	42	1.1/2"
1231054200	54	2"

DVGW



Female x Male Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1731015012	15	1/2"
1731015038	15	3/8"
1731022034	22	34"
1731028100	28	1"
1731035114	35	1.1/4"
1731042112	42	1.1/2"
1731054200	54	2"



Female x Male Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1431015012	15	1/2"
1431015038	15	3/8"
1431022034	22	34"
1431028100	28	1"
1431035114	35	1.1/4"
1431042112	42	1.1/2"
1431054200	54	2"

EPDM Seals

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

WRAS



Description:	Ethylene Propylene Diene Mnomer

HNBR Gas Approved Seals

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

DVGW



DVGW G260 & G262

Description:	Hydrogenated Nitrile Butadiene Rubber

FKM Seals

Temperature: -30°C to +180°C (+230°C for short periods)

Pressure: PN16 16 bar



Description:	Viton Fluroelastomer

Fluid-Air Components Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

90° Street Elbows



WRAS



Female x Male Plain End, EPDM Seal

3102	Size mm
122101515	15
122102222	22
122102828	28
122103535	35
122104242	42
122105454	54

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3102	Size mm
172101515	15
172102222	22
172102828	28
172103535	35
172104242	42
172105454	54



Female x Male Plain End, FKM Seal

3102	Size mm
142101515	15
142102222	22
142102828	28
142103535	35
142104242	42
142105454	54

Wallplates



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3102	Size mm	Thread
1234015012	15	1/2"
1234022034	22	3/4"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3102	Size mm	Thread
1734015012	15	1/2"
1734022034	22	3/4"



Female x Female Threaded, BSPP, FKM Seal

3102	Size mm	Thread
1434015012	15	1/2"
1434022034	22	3/4"

Flange Adaptors



WRAS



Female PN16, EPDM Seal

3102	Size mm
1240022	22
1240028	28
1240035	35
1240042	42
1240054	54

DVGW



Female PN16, HNBR Gas Approved Seal

3102	Size mm
1740022	22
1740028	28
1740035	35
1740042	42
1740054	54



Female PN16, FKM Seal

3102	Size mm
1440022	22
1440028	28
1440035	35
1440042	42
1440054	54

RIDGID



You might also need...
RIDGID Press Tool
...see page **1744**

M-Press Fittings Ltd

Stainless Steel 316L Press Fit Piping System

stainless steel

50 Year Warranty

new product

Partial Crossovers



Male Plain End x Male Plain End, Formed Pipe

3102	Size mm
123601515	15
123602222	22
123602828	28
123603535	35
123604242	42
123605454	54

90° Bends



Plain Male x Plain Male, Formed Pipe

3102	Size mm
123501515	15
123502222	22
123502828	28
123503535	35
123504242	42
123505454	54

45° Bends



Plain Male x Plain Male, Formed Pipe

3102	Size mm
123801515	15
123802222	22
123802828	28
123803535	35
123804242	42
123805454	54

Pipe



Series 1, 3 Metre Lengths

3102	Size mm	Wall Thickness
129501506-3MTR	15	0.6
129502207-3MTR	22	0.7
129502808-3MTR	28	0.8
129503510-3MTR	35	1.0
2023-9901-3MTR	42	1.1
129505412-3MTR	54	1.2



Series 2, 3 Metre Lengths

3102	Size mm	Wall Thickness
129001510-3MTR	15	1.0
129002212-3MTR	22	1.2
129002812-3MTR	28	1.2
129003515-3MTR	35	1.5
129004215-3MTR	42	1.5
129005415-3MTR	54	1.5

DIRECT DELIVERY

Series 1, 6 Metre Lengths

3102	Size mm	Wall Thickness
129501506	15	0.6
129502207	22	0.7
129502808	28	0.8
129503510	35	1.0
129504211	42	1.1
129505412	54	1.2

DIRECT DELIVERY

Series 2, 6 Metre Lengths

3102	Size mm	Wall Thickness
129001510	15	1.0
129002212	22	1.2
129002812	28	1.2
129003515	35	1.5
129004215	42	1.5
129005415	54	1.5

316L Stainless Steel Press Fit Ball Valves

Working Temperature: -10°C to +120°C

Maximum Working Pressure: 16 bar



WRAS, Female x Female, EPDM Seal

3105	Size mm
SS60015BH	15
SS60022BH	22
SS60028BH	28
SS60035BH	35
SS60042BH	42
SS60054BH	54

Working Temperature: -20°C to +70°C

Maximum Working Pressure: 5 bar



GAS, Female x Female, HNBR Gas Approved Seal

3105	Size mm
SS60015YH	15
SS60022YH	22
SS60028YH	28
SS60035YH	35
SS60042YH	42
SS60054YH	54

Fluid-Air Components Ltd

M-Press Fittings Ltd

Copper Press Fit Piping System

The M-Press copper ring main system is the leading solution for all copper installation requirements.

Its innovative design and superior quality guarantee a hassle-free installation process and long-lasting performance.



M-Press's copper system is a versatile and reliable solution for a wide range of industrial and domestic applications.

Its innovative design and high-quality construction guarantee a seamless installation process with minimal downtime and complications for the installer.

The system features a range of advanced components and features, including durable copper piping, precision-engineered fittings, and advanced sealing technologies, to ensure maximum performance and reliability in even the most demanding environments.

Whether working on a large industrial project or installing a domestic heating system, M-Press's Copper Press Fit system is the preferred solution for your needs.

Features:

- WRAS certified
- Gas EN331 certified
- Universally compatible with all M-Profile systems
- Reliable and durable press system
- Leak-free performance

Advantages:

- Ease of installation
- Increased productivity
- Removes the need for traditional site hot-work permits
- Wide choice of products and seal types
- Clean and hassle-free handling
- Lightweight system

The M-Press system is manufactured to meet the highest standards and materials:

- ✔ **Fittings:** CW024A according to EN 1254
- ✔ **Threaded fittings:** CC499K according to EN 1282

Trust M-Press to provide a reliable and efficient solution for your ring main installation

1127

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

M-Press Fittings Ltd

Copper Press Fit Piping System

50 Year Warranty

EPDM Seals



WRAS APPROVED PRODUCT

Material	Copper
Formed Fittings:	CW024A according to EN1254
Threaded Fittings:	CC499K according to EN1282
Pipe:	EN1057
Seal Type:	EPDM
Description:	Ethylene Propylene Diene Mnomer

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

Applications

- Potable water services
- Hydronic heating
- Compressed air
- BCWS (Boosted cold water services)
- Chilled water applications
- Purified water
- Inert gases

Application Services

- Drinking water
- HWS and commercial/domestic heating
- Compressed air (<25mg/M³ compressor oil concentration)
- Risers and plant rooms
- Cooling water (chilled water) with glycol <50% concentration
- Grey water
- Low pressure steam condensate
- Helium, Neon, Argon

HNBR Gas Approved Seals



DVGW DVGW G260 & G262

Material	Copper
Formed Fittings:	CW024A according to EN1254
Threaded Fittings:	CC499K according to EN1282
Pipe:	EN1057
Seal Type:	HNBR
Description:	Hydrogenated Nitrile Butadiene Rubber

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

Applications

- Offshore applications
- Low pressure hydraulic systems
- Hot water supply
- Flammable gases (DVGW G260, 262)
- Inert gases

Application Services

- Methane gas transportation
- Low pressure hydraulic system
- Domestic and commercial heating systems
- Natural gas and LPG
- Helium, Neon, Argon

FKM Seals



Material	Copper
Formed Fittings:	CW024A according to EN1254
Threaded Fittings:	CC499K according to EN1282
Pipe:	EN1057
Seal Type:	FKM
Description:	Viton Fluroelastomer

Temperature: -30°C to +180°C (+230°C for short periods)


Pressure: PN16 16 bar

Applications

- Domestic and commercial solar thermal heating
- Domestic and commercial heating
- Commercial steam condensate
- Industrial compressed air
- Acidic transportation
- Hydraulic applications
- Oil and fuels

Application Services

- High temperature heating and hot water systems
- Commercial warehouse/ Large area heating systems
- Low pressure steam condensate
- Industrial compressed air systems (>25mg/M³ compressor oil concentration)
- Some acid solutions
- Hydraulic oils
- Heavy oil and fuel transportation (Kerosene, Parafin, Diesel)
- Please enquire for exact suitability



50 Year Warranty

Fluid-Air Components Ltd

Adaptors



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3104	Size mm	Thread
6802015012	15	1/2"
6802015034	15	3/4"
6802022012	22	1/2"
6802022034	22	3/4"
6802022100	22	1"
6802028034	28	3/4"
6802028100	28	1"
6802035114	35	1.1/4"
6802042112	42	1.1/2"
6802054200	54	2"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3104	Size mm	Thread
7902015012	15	1/2"
7902015034	15	3/4"
7902022012	22	1/2"
7902022034	22	3/4"
7902022100	22	1"
7902028034	28	3/4"
7902028100	28	1"
7902035114	35	1.1/4"
7902042112	42	1.1/2"
7902054200	54	2"



Female x Female Threaded, BSPP, FKM Seal

3104	Size mm	Thread
8802015012	15	1/2"
8802015034	15	3/4"
8802022012	22	1/2"
8802022034	22	3/4"
8802022100	22	1"
8802028034	28	3/4"
8802028100	28	1"
8802035114	35	1.1/4"
8802042112	42	1.1/2"
8802054200	54	2"



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3104	Size mm	Thread
6801015012	15	1/2"
6801015034	15	3/4"
6801022012	22	1/2"
6801022034	22	3/4"
6801022100	22	1"
6801028034	28	3/4"
6801028100	28	1"
6801035114	35	1.1/4"
6801042112	42	1.1/2"
6801054200	54	2"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3104	Size mm	Thread
7901015012	15	1/2"
7901015034	15	3/4"
7901022012	22	1/2"
7901022034	22	3/4"
7901028100	22	1"
7901035100	28	3/4"
7901035114	28	1"
7901042112	35	1.1/4"
7901054200	42	1.1/2"
7901066212	54	2"



Female x Female Threaded, BSPP, FKM Seal

3104	Size mm	Thread
8801015012	15	1/2"
8801015034	15	3/4"
8801022012	22	1/2"
8801022034	22	3/4"
8801028100	22	1"
8801035100	28	3/4"
8801035114	28	1"
8801042112	35	1.1/4"
8801054200	42	1.1/2"
8801066212	54	2"

Union Adaptors with Flat Seal



WRAS



Female x Male Threaded, BSPP, EPDM Seal

3104	Size mm	Thread
6808015012	15	1/2"
6808022034	22	3/4"
6808028100	28	1"
6808035114	35	1.1/4"
6808042112	42	1.1/2"
6808054200	54	2"

DVGW



Female x Male Threaded, BSPP, HNBR Gas Approved Seal

3104	Size mm	Thread
7908015012	15	1/2"
7908022034	22	3/4"
7908028100	28	1"
7908035114	35	1.1/4"
7908042112	42	1.1/2"
7908054200	54	2"



Female x Male Threaded, BSPP, FKM Seal

3104	Size mm	Thread
8808015012	15	1/2"
8808022034	22	3/4"
8808028100	28	1"
8808035114	35	1.1/4"
8808042112	42	1.1/2"
8808054200	54	2"

M-Press Fittings Ltd

Copper Press Fit Piping System

50 Year Warranty

new product

Straight Couplings



WRAS

Female x Female, EPDM Seal

3104	Size mm
680001515	15
680002222	22
680002828	28
680003535	35
680004242	42
680005454	54

DVGW



Female x Female, HNBR Gas Approved Seal


3104	Size mm
790001515	15
790002222	22
790002828	28
790003535	35
790004242	42
790005454	54



Female x Male Plain End, FKM Seal

3104	Size mm
880001515	15
880002222	22
880002828	28
880003535	35
880004242	42
880005454	54

Slip Couplers



WRAS

Female x Female, EPDM Seal

3104	Size mm
680401515	15
680402222	22
680402828	28
680403535	35
680404242	42
680405454	54

DVGW



Female x Female, HNBR Gas Approved Seal


3104	Size mm
790001515	15
790002222	22
790002828	28
790003535	35
790004242	42
790005454	54



Female x Male Plain End, FKM Seal

3104	Size mm
880401515	15
880402222	22
880402828	28
880403535	35
880404242	42
880405454	54

Socket Reducers



WRAS

Female x Male Plain End, EPDM Seal

3104	Size mm	Size mm
684302215	22	15
684302815	28	15
684302822	28	22
684303522	35	22
684303528	35	28
684304222	42	22
684304228	42	28
684304235	42	35
684305435	54	35
684305442	54	42

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3104	Size mm	Size mm
794302215	22	15
794302815	28	15
794302822	28	22
794303522	35	22
794303528	35	28
794304222	42	22
794304228	42	28
794304235	42	35
794305435	54	35
794305442	54	42



Female x Male Plain End, FKM Seal

3104	Size mm	Size mm
884302215	22	15
884302815	28	15
884302822	28	22
884303522	35	22
884303528	35	28
884304222	42	22
884304228	42	28
884304235	42	35
884305435	54	35
884305442	54	42

Fluid-Air Components Ltd

End Caps



WRAS



Female x End Cap, EPDM Seal

3104	Size mm
6841015	15
6841022	22
6841028	28
6841035	35
6841042	42
6841054	54

DVGW



Female x End Cap, HNBR Gas Approved Seal

3104	Size mm
7941015	15
7941022	22
7941028	28
7941035	35
7941042	42
7941054	54



Female x End Cap, FKM Seal

3104	Size mm
8841015	15
8841022	22
8841028	28
8841035	35
8841042	42
8841054	54

45° Elbows



WRAS



Female x Female, EPDM Seal

3104	Size mm
682301515	15
682302222	22
682302828	28
682303535	35
682304242	42
682305454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3104	Size mm
792301515	15
792302222	22
792302828	28
792303535	35
792304242	42
792305454	54



Female x Female, FKM Seal

3104	Size mm
882301515	15
882302222	22
882302828	28
882303535	35
882304242	42
882305454	54

45° Street Elbows



WRAS



Female x Male Plain End, EPDM Seal

3104	Size mm
682401515	15
682402222	22
682402828	28
682403535	35
682404242	42
682405454	54

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3104	Size mm
792401515	15
792402222	22
792402828	28
792403535	35
792404242	42
792405454	54



Female x Male Plain End, FKM Seal

3104	Size mm
882001515	15
882002222	22
882002828	28
882003535	35
882004242	42
882005454	54

EPDM Seals

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

WRAS



Description:	Ethylene Propylene Diene Mnomer

HNBR Gas Approved Seals

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

DVGW



DVGW G260 & G262

Description:	Hydrogenated Nitrile Butadiene Rubber

FKM Seals

Temperature: -30°C to +180°C (+230°C for short periods)

Pressure: PN16 16 bar



Description:	Viton Fluroelastomer

Fluid-Air Components Ltd

M-Press Fittings Ltd

Copper Press Fit Piping System

50 Year Warranty

new product

Equal Tees





Female x Female x Female, EPDM Seal

3104	Size mm
68100151515	15
68100222222	22
68100282828	28
68100353535	35
68100424242	42
68100545454	54



Female x Female x Female, HNBR Gas Approved Seal

3104	Size mm
79100151515	15
79100222222	22
79100282828	28
79100353535	35
79100424242	42
79100545454	54



Female x Female x Female, FKM Seal

3104	Size mm
88100151515	15
88100222222	22
88100282828	28
88100353535	35
88100424242	42
88100545454	54

Reducing Tees





Female x Female x Female, EPDM Seal

3104	Size mm	Size mm	Size mm
68110221522	22	15	22
68110282228	28	22	28
68110352235	35	22	35
68110352835	35	28	35
68110422242	42	22	42
68110422842	42	28	42
68110423542	42	35	42
68110542254	54	22	54
68110542854	54	28	54
68110543554	54	35	54
68110544254	54	42	54



Female x Female x Female, HNBR Gas Approved Seal

3104	Size mm	Size mm	Size mm
79110221522	22	15	22
79110282228	28	22	28
79110352235	35	22	35
79110352835	35	28	35
79110422842	42	22	42
79110422842	42	28	42
79110423542	42	35	42
79110542254	54	22	54
79110542854	54	28	54
79110543554	54	35	54
79110544254	54	42	54



Female x Female x Female, FKM Seal

3104	Size mm	Size mm	Size mm
88110221522	22	15	22
88110282228	28	22	28
88110352235	35	22	35
88110352835	35	28	35
88110422242	42	22	42
88110422842	42	28	42
88110423542	42	35	42
88110542254	54	22	54
88110542854	54	28	54
88110543554	54	35	54
88110544254	54	42	54





Female x Female Threaded, BSPP x Female, EPDM Seal

3104	Size mm	Thread	Size mm
68120151215	15	1/2"	15
68120221222	22	1/2"	22
68120223422	22	3/4"	22
68120281228	28	1/2"	28
68120283428	28	3/4"	28
68120351235	35	1/2"	35
68120421242	42	1/2"	42
68120541254	54	1/2"	54



Female x Female Threaded, BSPP x Female, HNBR Gas Approved Seal

3104	Size mm	Thread	Size mm
79120151215	15	1/2"	15
79120221222	22	1/2"	22
79120223422	22	3/4"	22
79120281228	28	1/2"	28
79120283428	28	3/4"	28
79120351235	35	1/2"	35
79120421242	42	1/2"	42
79120541254	54	1/2"	54



Female x Female Threaded, BSPP x Female, FKM Seal

3104	Size mm	Thread	Size mm
88120151215	15	1/2"	15
88120221222	22	1/2"	22
88120223422	22	3/4"	22
88120281228	28	1/2"	28
88120283428	28	3/4"	28
88120351235	35	1/2"	35
88120421242	42	1/2"	42
88120541254	54	1/2"	54

Fluid-Air Components Ltd

90° Elbows



WRAS



Female x Female, EPDM Seal

3104	Size mm
682001515	15
682002222	22
682002828	28
682003535	35
682004242	42
682005454	54

DVGW



Female x Female, HNBR Gas Approved Seal

3104	Size mm
882001515	15
882002222	22
882002828	28
882003535	35
882004242	42
882005454	54



Female x Female, FKM Seal

3104	Size mm
882301515	15
882302222	22
882302828	28
882303535	35
882304242	42
882305454	54

90° Bends



WRAS



Female x Female Threaded, BSPP, EPDM Seal

3104	Size mm	Thread
6832015012	15	1/2"
6832022034	15	3/8"
6832028100	22	3/4"

DVGW



Female x Female Threaded, BSPP, HNBR Gas Approved Seal

3104	Size mm	Thread
7932015012	15	1/2"
7932022034	15	3/8"
7932028100	22	3/4"



Female x Female Threaded, BSPP, FKM Seal

3104	Size mm	Thread
8832015012	15	1/2"
8832022034	15	3/8"
8832028100	22	3/4"



WRAS



Female x Male Threaded, BSPP, EPDM Seal

3104	Size mm	Thread
6831015012	15	1/2"
6831022034	22	34
6831028100	28	1

DVGW



Female x Male Threaded, BSPP, HNBR Gas Approved Seal

3104	Size mm	Thread
7931015012	15	1/2"
7931022034	22	34
7931028100	28	1



Female x Male Threaded, BSPP, FKM Seal

3104	Size mm	Thread
8831015012	15	1/2"
8831022034	22	34
8831028100	28	1

EPDM Seals

Temperature: -30°C to +120°C

Pressure: PN16 16 bar

WRAS



Description:	Ethylene Propylene Diene Mnomer

HNBR Gas Approved Seals

Temperature: -20°C to +70°C

Pressure: PN5 5 bar

DVGW

DVGW G260 & G262



Description:	Hydrogenated Nitrile Butadiene Rubber

FKM Seals

Temperature: -30°C to +180°C (+230°C for short periods)

Pressure: PN16 16 bar



Description:	Viton Fluroelastomer

Fluid-Air Components Ltd

M-Press Fittings Ltd

Copper Press Fit Piping System

50 Year Warranty

new product

90° Street Elbows



WRAS APPROVED PRODUCT



Female x Male Plain End, EPDM Seal

3104	Size mm
682101515	15
682102222	22
682102828	28
682103535	35
682104242	42
682105454	54

DVGW



Female x Male Plain End, HNBR Gas Approved Seal

3104	Size mm
792101515	15
792102222	22
792102828	28
792103535	35
792104242	42
792105454	54



Female x Male Plain End, FKM Seal

3104	Size mm
882001515	15
882002222	22
882002828	28
882003535	35
882004242	42
882005454	54

Brass Press Fit Ball Valves

WRAS APPROVED PRODUCT

Working Temperature:
-10°C to +120°C


Maximum Working Pressure:
16 bar



Female x Female, EPDM Seal

3105	Size mm
GP60015PP	15
GP60022PP	22
GP60028PP	28
GP60035PP	35
GP60042PP	42
GP60054PP	54

Plumbing Copper Tube



- 6 metre lengths available upon request.

BS EN1057 R250, 3 Metre Lengths

5072	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
PCU15	15	13.6	843	59
PCU22	22	20.2	752	51
PCU28	28	26.2	582	40
PCU35	35	32.6	618	43
PCU42	42	39.6	512	35
PCU54	54	51.6	396	27
PCU67	67	64.6	317	22

RIDGID

You might also need...
RIDGID PC 116 Powered Tubing Cutter
...see page **1743**



Fluid-Air Components Ltd

NIROSAN® STAINLESS STEEL PRESS FIT PIPING SYSTEM

stainless steel

SANHA®

WRAS APPROVED PRODUCT

NiroSan® press system fittings and NiroSa ® system pipes in stainless steel with tool compatibility, leak path feature and 'push and stay' function.

Stainless steel systems from SANHA® can be used universally. The various NiroSan® pipes and NiroSan® press system fittings can be combined with each othe , making them particularly user friendly.

Features

- Pressable with V, M and SA profile
- Suitable for a very broad range of applications
- Long service life of fittings and EPDM sealing ring
- Inseparable, pressure-formed connection
- WRAS tested and certifie
- All fittings and tube are manufactured from 316 L grade stainless steel

Working Temperature:
-30°C to +120°C

Maximum Working Pressures:
Water: 22mm: 40 bar, 28-35mm: 25 bar, 42-54mm: 16 bar
Flammable Gases: 5 bar
Non-flammable/ oxic Gases: 16 bar

Press fittings suitable for both gas and industrial oil applications are available on request

Series 9000, Straights

Female x Male Plain End, Reducer



0473	ID mm	OD mm
692432215	22	15
692432815	28	15
692432822	28	22
692433522	35	22
692433528	35	28
692434228	42	28
692434235	42	35
692435428	54	28
692435435	54	35
692435442	54	42
Tech Sheet 60369		

Female x Male Threaded, BSPT



0473	ID mm	Thread
69243G1512	15	1/2"
69243G1534	15	3/4"
69243G221	22	1"
69243G2212	22	1/2"
69243G2234	22	3/4"
69243G281	28	1"
69243G2834	28	3/4"
69243G351	35	1"
69243G35114	35	1.1/4"
69243G42112	42	1.1/2"
69243G542	54	2"
Tech Sheet 60369		

Male Plain End x Female Threaded, BSPT



0473	ID mm	Thread
69246G1512	15	1/2"
69246G2212	22	1/2"
69246G2234	22	3/4"
69246G2834	28	3/4"
Tech Sheet 60369		

Male Plain End x Male Threaded, BSPT



0473	OD mm	Thread
69280G1512	15	1/2"
69280G2212	22	1/2"
69280G2234	22	3/4"
69280G281	28	1"
Tech Sheet 60369		

Coupling



0473	ID mm
6927015	15
6927022	22
6927028	28
6927035	35
6927042	42
6927054	54
Tech Sheet 60369	

Slip Coupling



0473	ID mm
69270S15	15
69270S22	22
69270S28	28
69270S35	35
69270S42	42
69270S54	54
Tech Sheet 60369	

Female End x Female Threaded, BSPT



0473	ID mm	Thread
69270G1512	15	1/2"
69270G2212	22	1/2"
69270G2234	22	3/4"
69270G281	28	1"
69270G2834	28	3/4"
69270G35114	35	1.1/4"
69270G42112	42	1.1/2"
69270G542	54	2"
Tech Sheet 60369		

Female End x Female Threaded, with Flat Centellen Seal, BSPP



0473	ID mm	Thread
69359M1512	15	1/2"
69359M1534	25	3/4"
69359M221	22	1"
69359M28114	28	1.1/4"
69359M35112	35	1.1/2"
69359M42134	42	1.3/4"
Tech Sheet 60369		

Series 9000, End Caps

Female



0473	ID mm
6930115	15
6930122	22
6930128	28
6930135	35
Tech Sheet 60369	

Series 9000, Tube



6 Metre Lengths

0473	ID mm
6960015	15
6960022	22
6960028	28
6960035	35
6960042	42
6960054	54
Tech Sheet 60369	

Fluid-Air Components Ltd

NIROSAN® STAINLESS STEEL PRESS FIT PIPING SYSTEM

stainless steel

SANHA

WRAS APPROVED PRODUCT

Series 9000, Tees



Equal

0473	ID mm
6913015	15
6913022	22
6913028	28
6913035	35
6913042	42
6913054	54
Tech Sheet 60369	



Reducing

0473	ID mm	ID mm
69130221522	22	15
69130281528	28	15
69130352235	35	22
69130352835	35	28
69130422242	42	22
69130422842	42	28
69130423542	42	35
69130542254	54	22
69130542854	54	28
69130543554	54	35
69130544254	54	42
Tech Sheet 60369		



Female Threaded Centre Leg, BSPT

0473	ID mm	Thread
69130G151215	15	1/2"
69130G221222	22	1/2"
69130G223422	22	3/4"
69130G281228	28	1/2"
69130G283428	28	3/4"
69130G351235	35	1/2"
69130G353435	35	3/4"
69130G421242	42	1/2"
69130G541254	54	1/2"
Tech Sheet 60369		

Press fittings suitable for both gas and industrial oil applications are available on request.

Series 9000, 90º Elbows



Female x Male Plain End

0473	ID mm	OD mm
69001A15	15	15
69001A22	22	22
69001A28	28	28
69001A35	35	35
69001A42	42	42
69001A54	54	54
Tech Sheet 60369		



Female x Male Plain End, Long

0473	ID mm	OD mm
69001L15	15	15
69001L22	22	22
69001L28	28	28
69001L35	35	35
69001L42	42	42
69001L54	54	54
Tech Sheet 60369		



Equal Female

0473	ID mm
69002A15	15
69002A22	22
69002A28	28
69002A35	35
69002A42	42
69002A54	54
Tech Sheet 60369	



Female x Male Thread, BSPT

0473	ID mm	Thread
69002AG1512	15	1/2"
69002AG2234	22	3/4"
Tech Sheet 60369		



Female x Female Thread, BSPT

0473	ID mm	Thread
69002G1512	15	1/2"
69002G2234	22	3/4"
Tech Sheet 60369		



Compact, Female x Female Thread, BSPT

0473	ID mm	Thread
69090IG1512	15	1/2"
69090IG2234	22	3/4"
Tech Sheet 60369		



Compact, Female x Male Thread, BSPT

0473	ID mm	Thread
69092AG1512	15	1/2"
69092AG2234	22	3/4"
69092AG281	28	1"
Tech Sheet 60369		

Series 9000, 45º Elbows



Female x Male Plain End

0473	ID mm	OD mm
6904015	15	15
6904022	22	22
6904028	28	28
6904035	35	35
6904042	42	42
6904054	54	54
Tech Sheet 60369		



Female x Female

0473	ID mm
6904115	15
6904122	22
6904128	28
6904135	35
6904142	42
6904154	54
Tech Sheet 60369	

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 **Hose Tails, Adaptors, Fittings & Manifolds** 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 9

Hose Tails, Adaptors, Fittings & Manifolds

9.01 Hose Tails 1137-1154

9.02 Quick Fit Fittings 1155-1164

9.03 Adaptors 1165-1194

9.04 Flanges & Gaskets 1195

9.05 Compression Fittings & Copper Tube 1196-1215

9.06 Plumbing Compression Fittings 1216-1219

9.07 Manifolds 1220-1224

Fluid-Air Components Ltd

SECTION 9

9.01 Hose Tails

1137-1154

- Nickel Plated Brass & Brass Hose Tails
- Push-on Hose Adaptors
- Polypropylene Hose Tails Adaptors
- Nylon Hose Tails
- PVDF Hose Tails
- Plastic Hose Tails
- Emergency Hose Connector Set
- Oxy-acetylene Fittings



9.02 Quick Fit Fittings

1155-1164


- Miniature Fittings M3-M6
- Brass Quick-fit Fitting
- Flow Regulators
- Finger-tight Fittings
- Polypropylene Quick-Fit Fittings
- PVDF Quick-Fit Fittings



9.03 Adaptors

1165-1194

- Brass Adaptors
- Nickel Plated Brass Adaptors
- Polypropylene Hose Adaptors
- Nylon Adaptors
- PVDF Adaptors
- 3000lb Forged Pipe Fittings, ANSI B16.11
- 150lb 316 Stainless Steel Pipe Fittings
- 3000lb 316 Stainless Steel Pipe Fittings
- Tubing
- BS TYPE, 316L Hygienic Pipe Fittings
- Hygienic Clamp Fittings
- RJT Couplings



9.04 Flanges & Gaskets

1195

- 3000lb 316 Stainless Steel Pipe Fittings



Hose Tails, Adaptors, Fittings & Manifolds

9.05 Compression Fittings & Copper Tube

1196-1215

- Brass Compression Fittings
- Enots Compression Fittings
- Nickel Plated Compression Fittings
- Copper Tubing
- Bundy Tubing
- PVC Covered Copper Tube
- Polyethylene Pipe Insulation



9.06 Plumbing Compression Fittings

1216-1219

- Brass Plumbing Compression Fittings
- Solder Ring
- End Feed Fittings



9.07 Manifolds

1220-1224

- Distribution Manifolds
- Aluminium Manifolds
- Brass Manifolds
- Minifolds



NICKEL PLATED BRASS & BRASS HOSE TAILS


FT PRO®


This technical data is applicable to the full range of hose tail fittings and airline fittings including tees, elbows, reducers and silencers etc.

Threads:
Tapered in conformity with ISO 7.1, BS 21, DIN 2999. Parallel in conformity with ISO 228 class A. Metric in conformity with ISO R/262.

Media:
Compressed air, water, oils and fluids for hydraulics and pneumatic fields.

N.B. Safe pressures and temperatures depend entirely on the tubes being used, for this reason the values must be determined in accordance with the tube features.





Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

Straight Hose Tails, Brass



Male Thread, BSPT

1010	Thread	To Suit Hose ID	To Suit Hose ID mm
GT10/04K	1/8"	1/8"	4
GT10/05K	1/8"	3/16"	5
GT10/06K	1/8"	1/4"	6
GT10/08K	1/8"	5/16"	8
GT10/09K	1/8"	3/8"	9
GT10/13K	1/8"	1/2"	13
GT13/04K	1/4"	1/8"	4
GT13/05K	1/4"	3/16"	5
GT13/06K	1/4"	1/4"	6
GT13/08K	1/4"	5/16"	8
GT13/09K	1/4"	3/8"	9
GT13/13K	1/4"	1/2"	13
GT13/16K	1/4"	5/8"	16
GT13/19K	1/4"	3/4"	19
GT17/05K	3/8"	3/16"	5
GT17/06K	3/8"	1/4"	6
GT17/08K	3/8"	5/16"	8
GT17/09K	3/8"	3/8"	9
GT17/13K	3/8"	1/2"	13
GT17/16K	3/8"	5/8"	16
GT17/19K	3/8"	3/4"	19
GT21/05K	1/2"	3/16"	5
GT21/06K	1/2"	1/4"	6
GT21/08K	1/2"	5/16"	8
GT21/09K	1/2"	3/8"	9
GT21/13K	1/2"	1/2"	13
GT21/16K	1/2"	5/8"	16
GT21/19K	1/2"	3/4"	19
GT21/25K	1/2"	1"	25
GT23/16K	5/8"	5/8"	16
GT26/06K	3/4"	1/4"	6
GT26/08K	3/4"	5/16"	8
GT26/09K	3/4"	3/8"	9
GT26/13K	3/4"	1/2"	13
GT26/16K	3/4"	5/8"	16
GT26/19K	3/4"	3/4"	19
GT26/25K	3/4"	1"	25
GT26/31K	3/4"	1.1/4"	31
GT33/13K	1"	1/2"	13
GT33/16K	1"	5/8"	16
GT33/19K	1"	3/4"	19
GT33/25K	1"	1"	25
GT33/31K	1"	1.1/4"	31
GT33/38K	1"	1.1/2"	38
GT42/19K	1.1/4"	3/4"	19
GT42/25K	1.1/4"	1"	25
GT42/31K	1.1/4"	1.1/4"	31
GT48/31K	1.1/2"	1.1/4"	31
GT48/38K	1.1/2"	1.1/2"	38
GT48/50K	1.1/2"	2"	50
GT52/38K	2"	1.1/2"	38
GT52/50K	2"	2"	50
GT56/53K	2.1/2"	2.1/2"	53
GT60/58K	3"	3"	58
Tech Sheet 20089			

Straight Hose Tails, Nickel Plated Brass



Male Thread, BSPT

1010	Thread	To Suit Hose ID	To Suit Hose ID mm
GT10/04KNP	1/8"	1/8"	4
GT10/05KNP	1/8"	3/16"	5
GT10/06KNP	1/8"	1/4"	6
GT10/08KNP	1/8"	5/16"	8
GT10/09KNP	1/8"	3/8"	9
GT13/04KNP	1/4"	1/8"	4
GT13/05KNP	1/4"	3/16"	5
GT13/06KNP	1/4"	1/4"	6
GT13/08KNP	1/4"	5/16"	8
GT13/09KNP	1/4"	3/8"	9
GT13/13KNP	1/4"	1/2"	13
GT13/16KNP	1/4"	5/8"	16
GT17/05KNP	3/8"	3/16"	5
GT17/06KNP	3/8"	1/4"	6
GT17/08KNP	3/8"	5/16"	8
GT17/09KNP	3/8"	3/8"	9
GT17/13KNP	3/8"	1/2"	13
GT17/16KNP	3/8"	5/8"	16
GT17/19KNP	3/8"	3/4"	19
GT21/06KNP	1/2"	1/4"	6
GT21/08KNP	1/2"	5/16"	8
GT21/09KNP	1/2"	3/8"	9
GT21/13KNP	1/2"	1/2"	13
GT21/16KNP	1/2"	5/8"	16
GT21/19KNP	1/2"	3/4"	19
GT21/25KNP	1/2"	1"	25
GT26/09KNP	3/4"	3/8"	9
GT26/13KNP	3/4"	1/2"	13
GT26/16KNP	3/4"	5/8"	16
GT26/19KNP	3/4"	3/4"	19
GT26/25KNP	3/4"	1"	25
GT33/13KNP	1"	1/2"	13
GT33/19KNP	1"	3/4"	19
GT33/25KNP	1"	1"	25
GT33/38KNP	1"	1.1/2"	38
GT33/31KNP	1"	1.1/4"	31
GT42/25KNP	1.1/4"	1"	25
GT42/31KNP	1.1/4"	1.1/4"	31
GT48/38KNP	1.1/2"	1.1/2"	38
GT48/50KNP	1.1/2"	2"	50
GT52/38KNP	2"	1.1/2"	38
GT52/50KNP	2"	2"	50
Tech Sheet 20089			

HOSE TAILS

Straight Hose Tails, Brass



Male Thread, BSPP

1010	Thread	To Suit Hose ID mm
GBP-34	3/4"	20
GBP-1	1"	25
GBP-114	1.1/4"	32
GBP-2	2"	50




Male Thread, Metric

1010	Thread	To Suit Hose ID mm
MHM5/03	M5 x 0.8	3
MHM5/04	M5 x 0.8	4
MHM6/04	M6 x 1.0	4
MHM8/04	M8 x 1.0	6
MHM10/04	M10 x 1.0	6
MHM10/05	M10 x 1.0	8
MHM10/06	M10 x 1.0	10
MHM12/04	M12 x 1.5	6
MHM12/05	M12 x 1.5	8
MHM12/06	M12 x 1.5	10
MHM14/06	M14 x 1.5	10
MHM16/06	M16 x 1.5	10
MHM16/08	M16 x 1.5	12
MHM18/06	M18 x 1.5	10
MHM18/08	M18 x 1.5	12
MHM22/08	M22 x 1.5	12
MHM22/12	M22 x 1.5	19



Male Thread, 60˚ Coned Seat, BSPP

1010	Thread	To Suit Hose ID
GT05/03	M5	3mm
GT05/04	M5	4mm
GT06/04	M6	4mm
GT10/04	1/8"	1/8"
GT10/05	1/8"	3/16"
GT10/06	1/8"	1/4"
GT10/08	1/8"	5/16"
GT10/09	1/8"	3/8"
GT13/05	1/4"	3/16"
GT13/04	1/4"	1/8"
GT13/06	1/4"	1/4"
GT13/08	1/4"	5/16"
GT13/09	1/4"	3/8"
GT13/13	1/4"	1/2"
GT17/06	3/8"	1/4"
GT17/08	3/8"	5/16"
GT17/09	3/8"	3/8"
GT17/13	3/8"	1/2"
GT17/16	3/8"	5/8"
GT17/19	3/8"	3/4"
GT21/06	1/2"	1/4"
GT21/08	1/2"	5/16"
GT21/09	1/2"	3/8"
GT21/13	1/2"	1/2"
GT21/16	1/2"	5/8"
GT21/19	1/2"	3/4"
GT21/25	1/2"	1"
GT26/06	3/4"	1/4"
GT26/08	3/4"	5/16"
GT26/10	3/4"	3/8"
GT26/13	3/4"	1/2"
GT26/16	3/4"	5/8"
GT26/19	3/4"	3/4"
GT26/25	3/4"	1"
GT33/13	1"	1/2"
GT33/19	1"	3/4"
GT33/25	1"	1"
GT33/32	1"	1.1/4"
GT42/25	1.1/4"	1"
GT42/32	1.1/4"	1.1/4"
GT42/38	1.1/4"	1.1/2"
GT48/38	1.1/2"	1.1/2"
GT52/50	2"	2"



Male Thread, NPT

1010	Thread	To Suit Hose ID mm
650-1003	1/8"	3
650-1004	1/8"	4
650-1005	1/8"	5
650-1006	1/8"	6
650-1008	1/8"	8
650-1010	1/8"	10
650-1305	1/4"	5
650-1306	1/4"	6
650-1308	1/4"	8
650-1310	1/4"	10
650-1312	1/4"	12
650-1706	3/8"	6
650-1708	3/8"	8
650-1710	3/8"	10
650-1713	3/8"	13
650-1716	3/8"	16
650-1719	3/8"	19
650-2106	1/2"	6
650-2108	1/2"	8
650-2110	1/2"	10
650-2113	1/2"	13
650-2116	1/2"	16
650-2119	1/2"	19
650-2125	1/2"	25
650-2612	3/4"	12
650-2616	3/4"	16
650-2625	3/4"	25
650-2632	3/4"	32
650-3312	1"	12
650-3316	1"	16
650-3319	1"	19
650-3325	1"	25
650-3332	1"	32
650-4219	1.1/4"	19
650-4225	1.1/4"	25
650-4232	1.1/4"	32
650-4238	1.1/4"	38
650-4838	1.1/2"	38

Fluid-Air Components Ltd

Straight Hose Tails, Brass



Male Thread, NPT, Ball Swivel Joints

1010	Thread	To Suit Hose ID
BSJ-IW13	1/4" x 1/4"	-
BSJ-TF06	1/4"	1/4"
BSJ-TF08	1/4"	5/16"
BSJ-TF10	1/4"	3/8"



Female Thread, BSPP

1010	Thread	To Suit Hose ID
FFH02/03	1/8"	3/16"
FFH02/04	1/8"	1/4"
FFH02/05	1/8"	5/16"
FFH02/06	1/8"	3/8"
FFH04/03	1/4"	3/16"
FFH04/04	1/4"	1/4"
FFH04/05	1/4"	5/16"
FFH04/06	1/4"	3/8"
FFH06/04	3/8"	1/4"
FFH06/05	3/8"	5/16"
FFH06/06	3/8"	3/8"
FFH06/08	3/8"	1/2"
FFH08/04	1/2"	1/4"
FFH08/05	1/2"	5/16"
FFH08/06	1/2"	3/8"
FFH08/08	1/2"	1/2"
FFH08/10	1/2"	5/8"
FFH08/12	1/2"	3/4"
FFH08/16	1/2"	1"

Straight Swivel Hose Tails, Brass



Swivel Female Thread, 60° Coned Seat, BSPP

1010	Thread	To Suit Hose ID
FH10/18	1/8"	1/8"
FH10/316	1/8"	3/16"
FH13/18	1/4"	1/8"
FH13/316	1/4"	3/16"
FH13/14	1/4"	1/4"
FH13/516	1/4"	5/16"
FH13/38	1/4"	3/8"
FH17/14	3/8"	1/4"
FH17/516	3/8"	5/16"
FH17/38	3/8"	3/8"
FH17/12	3/8"	1/2"
FH21/14	1/2"	1/4"
FH21/516	1/2"	5/16"
FH21/38	1/2"	3/8"
FH21/12	1/2"	1/2"
FH26/12	3/4"	1/2"
FH26/34	3/4"	3/4"
FH33/12	1"	1/2"
FH33/58	1"	5/8"
FH33/34	1"	3/4"
FH33/1	1"	1"
FH42/114	1.1/4"	1.1/4"
FH48/114	1.1/2"	1.1/4"
FH48/112	1.1/2"	1.1/2"
FH52/2	2"	2"



Swivel Female Thread, Flat Faced Seat with Washer, BSPP

1010	Thread	To Suit Hose ID
FH10/18FF	1/8"	1/8"
FH10/316FF	1/8"	3/16"
FH10/14FF	1/8"	1/4"
FH13/316FF	1/4"	3/16"
FH13/14FF	1/4"	1/4"
FH13/516FF	1/4"	5/16"
FH13/38FF	1/4"	3/8"
FH17/14FF	3/8"	1/4"
FH17/516FF	3/8"	5/16"
FH17/38FF	3/8"	3/8"
FH17/12FF	3/8"	1/2"
FH21/14FF	1/2"	1/4" (6)
FH21/516FF	1/2"	5/16"
FH21/38FF	1/2"	3/8"
FH21/12FF	1/2"	1/2"
FH21/58FF	1/2"	5/8"
FH26/12FF	3/4"	3/8" (10)
FH26/12FF	3/4"	1/2"
FH26/58FF	3/4"	5/8"
FH26/34FF	3/4"	3/4"
FH33/12FF	1"	1/2" (12)
FH33/34FF	1"	3/4" (19)
FH33/1FF	1"	1"
FH42/114FF	1.1/4"	1.1/4"
FH48/112FF	1.1/2"	1.1/2"
FH52/2FF	2"	2"

For **Brass Adaptors**
...see pages **1165-1176**



Fluid-Air Components Ltd

HOSE TAILS

Elbow Hose Tails, Brass



Male Thread, BSPT

1010	Thread	To Suit Hose ID mm
600-1008	1/8"	8
600-1306	1/4"	6
600-1308	1/4"	8
600-1310	1/4"	10
600-1708	3/8"	8
600-1710	3/8"	10



Swivel Female Thread, Coned Seat, BSPP

1010	Thread	To Suit Hose ID mm
628-1006	1/8"	6
628-1305	1/4"	5
628-1306	1/4"	6
628-1308	1/4"	8
628-1310	1/4"	10
628-1706	3/8"	6
628-1708	3/8"	8
628-1710	3/8"	10
628-2110	1/2"	10
628-2112	1/2"	12



Female Thread, BSPP

1010	Thread	To Suit Hose ID	To Suit Hose ID mm
FET14-516	1/4"	5/16"	8
FET14-38	1/4"	3/8"	10
FET38-38	3/8"	3/8"	10
FET38-12	3/8"	1/2"	13
Tech Sheet 20182			



Male Thread, BSPT

1010	Thread	To Suit Hose ID	To Suit Hose ID mm
EHT-18-6	1/8"	1/4"	6
EHT-18-8	1/8"	5/16"	8
EHT-18-10	1/8"	3/8"	10
EHT-14-6	1/4"	1/4"	6
EHT-14-8	1/4"	5/16"	8
EHT-14-10	1/4"	3/8"	10
EHT-14-13	1/4"	1/2"	13
EHT-38-6	3/8"	1/4"	6
EHT-38-8	3/8"	5/16"	8
EHT-38-10	3/8"	3/8"	10
EHT-38-13	3/8"	1/2"	13
EHT-12-8	1/2"	5/16"	8
EHT-12-10	1/2"	3/8"	10
EHT-12-13	1/2"	1/2"	13
Tech Sheet 20349			

Y Hose Tails, Brass



1010	To Suit Hose ID	To Suit Hose ID mm
2020-1940	3/16"	5
2020-1943	1/4"	6
2020-1950	5/16"	8
2020-1968	3/8"	10
2020-1976	1/2"	12

Cross Hose Tails, Brass



1010	To Suit Hose ID	To Suit Hose ID mm
2020-1901	1/4"	6
2020-1919	5/16"	8
2020-1927	3/8"	10
2020-1935	1/2"	12
Tech Sheet 20349		

Tee Hose Tails, Brass



Single Barbed

1010	To Suit Hose ID	To Suit Hose ID mm
620-2108	5/16"	8
620-2110	3/8"	10
620-2112	1/2"	12



Multi Barbed

1010	To Suit Hose ID	To Suit Hose ID mm
THT-5	3/16"	5
THT-6	1/4"	6
THT-8	5/16"	8
THT-10	3/8"	10
THT-13	1/2"	13
HRCT12	3/4"	19
Tech Sheet 20348		

Hose Joiners, Brass



Equal

0422	To Suit Hose ID
DS04/04	1/8"
DS05/05	3/16"
DS06/06	1/4"
DS08/08	5/16"
DS09/09	3/8"
DS13/13	1/2"
DS16/16	5/8"
DS19/19	3/4"
DS25/25	1"
DS31/31	1.1/4"
DS38/38	1.1/2"
DS50/50	2"

Unequal

0422	To Suit Hose ID	To Suit Hose ID
DS09/06	3/8"	1/4"
DS13/06	1/2"	1/4"
DS13/08	1/2"	5/16"
DS13/09	1/2"	3/8"
DS16/09	5/8"	3/8"
DS16/13	5/8"	1/2"
DS19/09	3/4"	3/8"
DS19/13	3/4"	1/2"
DS19/16	3/4"	5/8"
DS25/19	1"	3/4"

Metric Stand Pipe



0422	Stand Pipe mm	To Suit Hose ID mm
CL15-10	15	10

Soldering Nut & Nipple



Female Thread, BSPP

0447	Thread	To Suit Hose ID
SN02/03	1/8"	3/16"
SN04/04	1/4"	1/4"
SN04/05	1/4"	5/16"
SN06/06	3/8"	3/8"
SN08/08	1/2"	1/2"
SN12/12	3/4"	3/4"

Fluid-Air Components Ltd

Straight Hose Tails, Nickel Plated Brass



Male Thread, BSPT

0422	Thread	To Suit Hose ID mm
3040-4-1/8	1/8"	4
3040-6-1/8	1/8"	6
3040-7-1/8	1/8"	7
3040-8-1/8	1/8"	8
3040-9-1/8	1/8"	9
3040-10-1/8	1/8"	10
3040-6-1/4	1/4"	6
3040-7-1/4	1/4"	7
3040-8-1/4	1/4"	8
3040-9-1/4	1/4"	9
3040-10-1/4	1/4"	10
3040-12-1/4	1/4"	12
3040-8-3/8	3/8"	8
3040-9-3/8	3/8"	9
3040-10-3/8	3/8"	10
3040-12-3/8	3/8"	12
3040-14-3/8	3/8"	14
3040-16-3/8	3/8"	16
3040-17-3/8	3/8"	17
3040-18-3/8	3/8"	18
3040-20-3/8	3/8"	20
3040-9-1/2	1/2"	9
3040-10-1/2	1/2"	10
3040-12-1/2	1/2"	12
3040-14-1/2	1/2"	14
3040-15-1/2	1/2"	15
3040-16-1/2	1/2"	16
3040-17-1/2	1/2"	17
3040-18-1/2	1/2"	18
3040-20-1/2	1/2"	20
3040-16-3/4	3/4"	16
3040-18-3/4	3/4"	18
3040-20-3/4	3/4"	20
3040-25-3/4	3/4"	25
3040-25-1	1"	25
Tech Sheet 10700		




Male Thread, BSPP

0422	Thread	To Suit Hose ID mm
3045-4.5-M5	M5	4.5
3045-4-1/8	1/8"	4
3045-6-1/8	1/8"	6
3045-7-1/8	1/8"	7
3045-8-1/8	1/8"	8
3045-9-1/8	1/8"	9
3045-6-1/4	1/4"	6
3045-7-1/4	1/4"	7
3045-8-1/4	1/4"	8
3045-9-1/4	1/4"	9
3045-12-1/4	1/4"	12
3045-9-3/8	3/8"	9
3045-12-3/8	3/8"	12
3045-17-3/8	3/8"	17
3045-9-1/2	1/2"	9
3045-12-1/2	1/2"	12
3045-15-1/2	1/2"	15
3045-17-1/2	1/2"	17
Tech Sheet 10701		



Male Thread, BSPT

5003	Thread	To Suit Hose ID mm
MC3/4-19	3/4"	19
MC1-25	1"	25



Female Thread, BSPP

0422	Thread	To Suit Hose ID mm
FHT6/10	1/8"	6
FHT6/13	1/4"	6
FHT7/10	1/8"	7
FHT7/13	1/4"	7
FHT8/13	1/4"	8
FHT9/13	1/4"	9
FHT9/17	3/8"	9
FHT10/13	1/4"	10
FHT10/17	3/8"	10
FHT12/17	3/8"	12
FHT12/21	1/2"	12
Tech Sheet 10702		

Elbow Hose Tails, Nickel Plated Brass



Male Thread, BSPT

1020	Thread	To Suit Hose ID	To Suit Hose ID mm
3055-6-1/8	1/8"	1/4"	6
3055-6-1/4	1/4"	1/4"	6
3055-9-1/4	1/4"	3/8"	9
Tech Sheet 10702			

For **Hydraulic Hose Range**
...see pages **6-14**




HOSE TAILS

Straight Hose Tails, Steel Zinc Plated



Male Thread, BSPP

1011	Thread	To Suit Hose ID
2049-1460	3/8"	3/8"
2049-1478	1/2"	1/2"
2049-1502	3/4"	3/4"
2049-1528	1"	1"




Male Thread, BSPT, Safety Locking Collar

1011	Thread	To Suit Hose ID
SMH18-14	1/8"	1/4"
SMH14-38	1/4"	3/8"
SMH14-12	1/4"	1/2"
SMH38-14	3/8"	1/4"
SMH12-38	1/2"	3/8"
SMH12-12	1/2"	1/2"
SMH12-34	1/2"	3/4"
SMH34-12	3/4"	1/2"
SMH34-34	3/4"	3/4"
SMH01-01	1"	1"




Male Thread, BSPT

1011	Thread	To Suit Hose ID
2049-1536	1/4"	1/4"
2049-1537	1/4"	5/16"
2052-8998	1/4"	3/8"
2049-1538	1/4"	1/2"
2049-1539	3/8"	1/4"
2049-1540	3/8"	5/16"
2049-1544	3/8"	3/8"
2052-9020	3/8"	1/2"
2052-9038	1/2"	3/8"
2049-1551	1/2"	1/2"
2052-9046	3/4"	1/2"
2052-9053	3/4"	1"
2049-1577	1"	1"



Swivel Female Thread, Flat Faced Seat with Washer, BSPP

1011	Thread	To Suit Hose ID
2049-1585	1/2"	1/2"
2049-1593	3/4"	3/4"
2049-1601	1"	1"
2049-1619	1.1/4"	1.1/4"



Swivel Female Thread, Coned Seat, BSPP

1011	Thread	To Suit Hose ID
2049-1630	1/4"	1/4"
2049-1633	1/4"	5/16"
2049-1638	1/4"	3/8"
2049-1640	3/8"	3/8"
2049-1643	1/2"	1/2"
2049-1668	3/4"	3/4"
2049-1684	1"	1"

Straight Hose Tail, Steel Plated



Swivel Male Thread, BSPT

1011	Thread	To Suit Hose ID
MH04/04S	1/4"	1/4"

Hose Joiners, Steel



Equal

1011	To Suit Hose ID
SHRC04/04	1/4"
SHRC05/05	5/16"

FT PRO




For **Combination Nipples**
...see page **1497**

Fluid-Air Components Ltd

FT PRO®

HOSE TAILS

Straight Hose Tails, Aluminium



- These lightweight hose tails are manufactured to a high strength specification with a lower cost in comparison to its brass alternative.
- Tapered in conformity with ISO 7.1, BS 21, DIN 2999.
- Has the appearance of brass.
- Lightweight.
- General use for compressed air, pneumatics, oils and fluids.

Male Thread, BSPT

0383	Thread	To Suit Hose ID
AGT13/06K	1/4"	1/4"
AGT13/08K	1/4"	5/16"
AGT13/09K	1/4"	3/8"
AGT13/13K	1/4"	1/2"
AGT17/09K	3/8"	3/8"
AGT17/13K	3/8"	1/2"
AGT21/13K	1/2"	1/2"
AGT21/19K	1/2"	3/4"
AGT26/19K	3/4"	3/4"
AGT33/25K	1"	1"

N.B. Safe pressures and temperatures depend entirely on the hose being used, for this reason the values must be determined in accordance with the hose features.

Working Temperature:
0°C to +80°C

Maximum Working Pressure
10 bar

Fluid-Air Components Ltd

PUSH-ON HOSE ADAPTORS

Threads: Metric conforming to ISO R/262
Application: Flexible plastic tubes
Materials: Technopolymer body, Brass hose adaptor
Medium: Compressed air

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 10 bar
Vacuum: -0.99 bar

Elbow Hose Adaptor



Tube x Tube

1020	To Suit Hose ID mm
1513-2	2
1513-3	3
1513-4	4
1513-6	6
Tech Sheet 983	

Tee Hose Adaptor



Tube x Tube

1020	To Suit Hose ID mm
1523-2	2
1523-3	3
1523-4	4
1523-6	6
Tech Sheet 983	

Straight Male Hose Adaptor



Tube x Metric

1020	To Suit Hose ID mm	Thread
1500-2	2	M5
1500-3	3	M5
1500-4	4	M5
1500-6	6	M5
Tech Sheet 983		

Straight Hose Adaptor



Tube x Tube

1020	Hose ID mm A	To Suit Hose ID mm B:
1504-22	2	2
1504-32	3	2
1504-33	3	3
1504-43	4	3
1504-44	4	4
1504-64	6	4
1504-66	6	6
Tech Sheet 983		

For **Compression Fittings**
...see pages **1209-1211**



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

POLYPROPYLENE HOSE TAILS ADAPTORS

Maximum Working Temperature: +80°C

Maximum Working Pressure: 8 bar

Threaded Studs

Male BSPP x Barb OD



0679	OD mm	Thread
28PHA01	6	1/4"
28PHA04	10	3/8"
28PHA05	12	3/8"
28PHA06	16	3/8"
28PHA08	13	1/2"
28PHA09	16	1/2"
28PHA10	20	1/2"
28PHA11	10	3/4"
28PHA12	13	3/4"
28PHA13	16	3/4"
28PHA14	20	3/4"
28PHA15	25	3/4"
28PHA16	20	1"
28PHA17	25	1"
28PHA18	32	1"
28PHA18A	20	1.1/4"
28PHA19	25	1.1/4"
28PHA20	32	1.1/4"
28PHA21	40	1.1/4"
28PHA22	38	1.1/2"
28PHA22A	40	1.1/2"
28PHA23	50	1.1/2"
28PHA24	50	2"
Tech Sheet 68762		

Fixed Female BSPP x Barb OD



0679	OD mm	Thread
28PHA50	16	3/4"
28PHA51	20	3/4"
Tech Sheet 68762		

Female BSPP, Nut Liner & Seal x Barb OD



0679	OD mm	Thread
28PHA38	10	3/8"
28PHA39	13	1/2"
28PHA40	10	3/4"
28PHA40A	13	3/4"
28PHA40B	16	3/4"
28PHA40C	20	3/4"
28PHA41A	20	1"
28PHA41B	25	1"
28PHA42	20	1.1/4"
28PHA42A	25	1.1/4"
28PHA42B	32	1.1/4"
28PHA43	40	1.1/2"
28PHA43A	38	1.1/2"
28PHA44	50	2"
Tech Sheet 68762		

Stepped Male BSPP x Barb OD



0679	OD mm	Thread
28PHA25B1	10/13/20	1/2"
28PHA25C	13/20/25	3/4"
28PHA25D	20/25/32	1"
28PHA25E	25/32/38	1.1/4"
28PHA25F	13/20/25/32/38	1.1/2"
Tech Sheet 68762		

90° Male BSPP Elbow x Barb OD



0679	OD mm	Thread
29PHA27	13	1/2"
29PHA28	16	1/2"
29PHA29	20	1/2"
29PHA30	12	3/4"
29PHA31	20	3/4"
29PHA32A	25	3/4"
29PHA33	25	1"
29PHA34	32	1"
29PHA35	32	1.1/4"
29PHA36	40	1.1/2"
29PHA37	51	2"
Tech Sheet 68762		

Male BSPP Y Piece, Twin Barb OD



0679	OD mm	Thread
28PHA52	10	3/4"
28PHA53	13	3/4"
28PHA53B	20	3/4"
28PHA53C	25	1"
Tech Sheet 68762		

Male BSPP Y Piece, Triple Barb OD



0679	OD mm	Thread
28PHA54	10	3/4"
28PHA55	13	3/4"
Tech Sheet 68762		

90° Female BSPP Elbow, Nut Liner & Seal x Barb OD



0679	OD mm	Thread
28PHA45A	12	1/2"
28PHA45B	12	3/4"
28PHA45C	16	3/4"
28PHA46	20	3/4"
28PHA47A	25	1"
28PHA47BC	25	1.1/4"
28PHA47B	32	1.1/4"
28PHA47C	40	1.1/2"
28PHA47D	50	2"
Tech Sheet 68762		

OD Barb x OD Barb Adaptors

Equal Hose Menders



0679	OD mm
28PHM01A	6
28PHM03	13
28PHM04B	16
28PHM05	20
28PHM06	25
28PHM07	32
28PHM08	40
28PHM09A	50
Tech Sheet 68762	

Unequal Hose Menders



0679	OD A mm	OD B mm
28PHMR04B	13	20
28PHMR04C	13	26
28PHMR05	20	25
28PHMR06	26	32
28PHMR09	25	38
28PHMR08	32	38
28PHMR10	38.5	50
Tech Sheet 68762		

90° Equal Elbow Hose Menders



0679	OD mm
28PHLA01	6
28PHLA02	10
28PHLB03	13
28PHLB05	20
28PHLB06	25
28PHLB07	32
28PHLB08	40
28PHLB09A	50
Tech Sheet 68762	

Fluid-Air Components Ltd

NYLON HOSE TAILS

Tefen hose fittings are the perfect choice to connect all types of flexible rubbe and plastic tubes in domestic, industrial and all other general applications.

Nylon 6-6

Temperature: -20 to 110°C

Working Pressure: Up to 14 bar (200 psi) at 20°C

Fittings Dimensions: refer to tube ID or OD, with respect to the common application

Main advantages:
- Strong and durable
- High impact resistant
- Food Certifie

Female Swivel Nut x Hose Tail



BSPT

0497	To Suit Hose ID	To Suit Hose ID mm	Thread
PN14-4-18	1/8"	4	1/8"
PN14-5-18	3/16"	5	1/8"
PN14-4-14	1/8"	4	1/4"
PN14-5-14	3/16"	5	1/4"
PN14-6-14	1/4"	6	1/4"
PN14-8-14	5/16"	8	1/4"
PN14-5-38	3/16"	5	3/8"
PN14-6-38	1/4"	6	3/8"
PN14-8-38	5/16"	8	3/8"
PN14-10-38	3/8"	10	3/8"
PN14-6-12	1/4"	6	1/2"
PN14-8-12	5/16"	8	1/2"
PN14-10-12	3/8"	10	1/2"
PN14-12-12	1/2"	12	1/2"
PN14-14-12	-	14	1/2"
PN14-10-34	3/8"	10	3/4"
PN14-12-34	1/2"	12	3/4"
PN14-14-34	-	14	3/4"
PN14-16-34	5/8"	16	3/4"
PN14-19-34	3/4"	19	3/4"

Female x Hose Tail



BSPT

0497	To Suit Hose ID	To Suit Hose ID mm	Thread
PN25-5-18	3/16"	5	1/8"
PN25-6-18	1/4"	6	1/8"
PN25-8-12	5/16"	8	1/2"
PN25-10-12	3/8"	10	1/2"
PN25-12-12	1/2"	12	1/2"
PN25-14-12	-	14	1/2"
PN25-19-12	3/4"	19	1/2"

Male x Hose Tail



BSPT

0497	To Suit Hose ID	To Suit Hose ID mm	Thread
PN15-4-18	1/8"	4	1/8"
PN15-4-14	1/8"	4	1/4"
PN15-5-18	3/16"	5	1/8"
PN15-5-14	3/16"	5	1/4"
PN15-6-18	1/4"	6	1/8"
PN15-6-14	1/4"	6	1/4"
PN15-6-38	1/4"	6	3/8"
PN15-6-12	1/4"	6	1/2"
PN15-6-34	1/4"	6	3/4"
PN15-8-18	5/16"	8	1/8"
PN15-8-14	5/16"	8	1/4"
PN15-8-38	5/16"	8	3/8"
PN15-8-12	5/16"	8	1/2"
PN15-10-14	3/8"	10	1/4"
PN15-10-38	3/8"	10	3/8"
PN15-10-12	3/8"	10	1/2"
PN15-10-34	3/8"	10	3/4"
PN15-12-14	1/2"	12	1/4"
PN15-12-38	1/2"	12	3/8"
PN15-12-12	1/2"	12	1/2"
PN15-12-34	1/2"	12	3/4"
PN15-14-38	-	14	3/8"
PN15-14-12	-	14	1/2"
PN15-14-34	-	14	3/4"
PN15-16-12	5/8"	16	1/2"
PN15-16-34	5/8"	16	3/4"
PN15-19-12	3/4"	19	1/2"
PN15-19-34	3/4"	19	3/4"
PN15-19-1	3/4"	19	1"
PN15-25-34	1"	25	3/4"

Hose Repairer



Tube x Tube

0497	To Suit Hose ID	To Suit,Hose ID mm
PN20-4	1/8"	4
PN20-5	3/16"	5
PN20-6	1/4"	6
PN20-8	5/16"	8
PN20-10	3/8"	10
PN20-12	1/2"	12
PN20-14	-	14
PN20-16	5/8"	16
PN20-19	3/4"	19

Reducing Hose Repairer



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID mm	To Suit Hose ID	To Suit Hose ID mm
PN19-5-4	3/16"	5	1/8"	4
PN19-6-4	1/4"	6	1/8"	4
PN19-6-5	1/4"	6	3/16"	5
PN19-8-5	5/16"	8	3/16"	5
PN19-8-6	5/16"	8	1/4"	6
PN19-10-6	3/8"	10	1/4"	6
PN19-10-8	3/8"	10	5/16"	8
PN19-12-8	1/2"	12	5/16"	8
PN19-12-10	1/2"	12	3/8"	10
PN19-14-10	3/8"	10	3/8"	10
PN19-14-12	-	14	1/2"	12
PN19-16-12	5/8"	16	1/2"	12
PN19-16-14	5/8"	16	-	14
PN19-19-14	3/4"	19	-	14
PN19-19-16	3/4"	19	5/8"	16

Blanking Plug



BSPT

0497	Thread
PN12-18	1/8"
PN12-14	1/4"
PN12-38	3/8"
PN12-12	1/2"
PN12-34	3/4"

Blanking Cap



BSPT

0497	Thread
PN13-18	1/8"
PN13-14	1/4"
PN13-38	3/8"
PN13-12	1/2"
PN13-34	3/4"

Fluid-Air Components Ltd

NYLON HOSE TAILS

Food Contact FDA 21 CFR | Food Contact (EU) 1935/2004

tefen

Nylon 6-6

Temperature: -20 to 110°C

Working Pressure: Up to 14 bar (200 psi) at 20°C

Fittings Dimensions: refer to tube ID or OD, with respect to the common application

Male Elbow Hose Connector



BSPT

0497	To Suit Hose ID	To Suit Hose ID mm	Thread
PN16-4-18	1/8"	4	1/8"
PN16-4-14	1/8"	4	1/4"
PN16-5-18	3/16"	5	1/8"
PN16-5-14	3/16"	5	1/4"
PN16-5-12	3/16"	5	1/2"
PN16-6-18	1/4"	6	1/8"
PN16-6-14	1/4"	6	1/4"
PN16-6-38	1/4"	6	3/8"
PN16-6-12	1/4"	6	1/2"
PN16-8-18	5/16"	8	1/8"
PN16-8-14	5/16"	8	1/4"
PN16-8-38	5/16"	8	3/8"
PN16-8-12	5/16"	8	1/2"
PN16-10-14	3/8"	10	1/4"
PN16-10-38	3/8"	10	3/8"
PN16-10-12	3/8"	10	1/2"
PN16-10-34	3/8"	10	3/4"
PN16-12-14	1/2"	12	1/4"
PN16-12-38	1/2"	12	3/8"
PN16-12-12	1/2"	12	1/2"
PN16-12-34	1/2"	12	3/4"
PN16-14-38	14mm	14	3/8"
PN16-14-12	14mm	14	1/2"
PN16-14-34	14mm	14	3/4"
PN16-16-12	5/8"	16	1/2"
PN16-16-34	5/8"	16	3/4"
PN16-19-12	3/4"	19	1/2"
PN16-19-34	3/4"	19	3/4"

Male Branch Tee Hose Connector



BSPT

0497	To Suit Hose ID	To Suit Hose ID mm	Thread
PN22-4-18	1/8"	4	1/8"
PN22-4-14	1/8"	4	1/4"
PN22-5-18	3/16"	5	1/8"
PN22-5-14	3/16"	5	1/4"
PN22-6-18	1/4"	6	1/8"
PN22-6-14	1/4"	6	1/4"
PN22-6-38	1/4"	6	3/8"
PN22-6-12	1/4"	6	1/2"
PN22-8-18	5/16"	8	1/8"
PN22-8-14	5/16"	8	1/4"
PN22-8-38	5/16"	8	3/8"
PN22-10-14	3/8"	10	1/4"
PN22-10-38	3/8"	10	3/8"
PN22-10-12	3/8"	10	1/2"
PN22-12-14	1/2"	12	1/4"
PN22-12-38	1/2"	12	3/8"
PN22-12-12	1/2"	12	1/2"
PN22-12-34	1/2"	12	3/4"
PN22-14-38	-	14	3/8"
PN22-16-12	5/8"	16	1/2"
PN22-16-34	5/8"	16	3/4"
PN22-19-12	3/4"	19	1/2"
PN22-19-34	3/4"	19	3/4"

Tee Hose Connector



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID mm
PN23-4	1/8"	4
PN23-5	3/16"	5
PN23-6	1/4"	6
PN23-8	5/16"	8
PN23-10	3/8"	10
PN23-12	1/2"	12
PN23-14	14mm	14
PN23-16	5/8"	16
PN23-19	3/4"	19

Reducing Tee Hose Connector



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID	To Suit Hose ID mm
PN24-5-4	3/16"	1/8"	4
PN24-6-5	1/4"	3/16"	5
PN24-8-6	5/16"	1/4"	6
PN24-10-8	3/8"	5/16"	8
PN24-12-10	1/2"	3/8"	10
PN24-16-14	5/8"	14mm	14
PN24-19-16	3/4"	5/8"	16

Elbow Hose Connector



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID mm
PN18-4	1/8"	4
PN18-5	3/16"	5
PN18-6	1/4"	6
PN18-8	5/16"	8
PN18-10	3/8"	10
PN18-12	1/2"	12
PN18-14	14mm	14
PN18-16	5/8"	16
PN18-19	3/4"	19

Reducing Elbow Hose Connector



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID	To Suit Hose ID mm
PN17-5-4	3/16"	1/8"	4
PN17-6-5	1/4"	3/16"	5
PN17-8-6	5/16"	1/4"	6
PN17-10-6	3/8"	1/4"	6
PN17-10-8	3/8"	5/16"	8
PN17-12-10	1/2"	3/8"	10
PN17-16-14	5/8"	14mm	14
PN17-19-16	3/4"	5/8"	16

Hose Connector



Tube x Tube

0497	To Suit Hose ID	To Suit Hose ID mm
PN21-4	1/8"	4
PN21-6	1/4"	6
PN21-8	5/16"	8
PN21-10	3/8"	10

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PVDF HOSE TAILS

Fittings made of PVDF function better than nylon when exposed to a wide range of temperatures and high corrosive chemicals.

This enables them to be used in industries such as chemical processing due to their excellent chemical resistance properties.

Working Temperature: -20°C to +120°C

Maximum Working Pressure: 14 bar at 20°C

Male x Hose Connector



BSPT

0472	To Suit Hose ID	Thread
PPV15-4-18	1/8"	1/8"
PPV15-5-14	3/16"	1/4"
PPV15-6-18	1/4"	1/8"
PPV15-6-14	1/4"	1/4"
PPV15-6-38	1/4"	3/8"
PPV15-6-12	1/4"	1/2"
PPV15-8-14	5/16"	1/4"
PPV15-8-38	5/16"	3/8"
PPV15-8-12	5/16"	1/2"
PPV15-10-14	3/8"	1/4"
PPV15-10-38	3/8"	3/8"
PPV15-10-12	3/8"	1/2"
PPV15-10-34	3/8"	3/4"
PPV15-12-38	1/2"	3/8"
PPV15-12-12	1/2"	1/2"
PPV15-12-34	1/2"	3/4"
PPV15-16-12	5/8"	1/2"
PPV15-19-12	3/4"	1/2"
PPV15-19-34	3/4"	3/4"

Tech Sheet 60237

Female x Hose Connector



BSPT

0472	To Suit Hose ID	Thread
PPV14-5-18	3/16"	1/8"
PPV14-5-14	3/16"	1/4"
PPV14-5-38	3/16"	3/8"
PPV14-6-14	1/4"	1/4"
PPV14-6-38	1/4"	3/8"
PPV14-6-12	1/4"	1/2"
PPV14-8-14	5/16"	1/4"
PPV14-8-38	5/16"	3/8"
PPV14-10-12	3/8"	1/2"
PPV14-12-12	1/2"	1/2"

Tech Sheet 60237

Straight Hose Connector



Tube x Tube

0472	To Suit Hose ID
PV20-5	3/16"
PV20-6	1/4"
PV20-10	3/8"
PV20-12	1/2"

Tech Sheet 60237

Male Elbow Hose Connector



BSPT

0472	To Suit Hose ID	Thread
PPV16-4-18	1/8"	1/8"
PPV16-4-14	1/8"	1/4"
PPV16-5-18	3/16"	1/8"
PPV16-5-14	3/16"	1/4"
PPV16-6-18	1/4"	1/8"
PPV16-6-14	1/4"	1/4"
PPV16-6-38	1/4"	3/8"
PPV16-6-12	1/4"	1/2"
PPV16-8-18	5/16"	1/8"
PPV16-8-14	5/16"	1/4"
PPV16-8-38	5/16"	3/8"
PPV16-8-12	5/16"	1/2"
PPV16-10-14	3/8"	1/4"
PPV16-10-38	3/8"	3/8"
PPV16-10-12	3/8"	1/2"
PPV16-10-34	3/8"	3/4"
PPV16-12-14	1/2"	1/4"
PPV16-12-38	1/2"	3/8"
PPV16-12-12	1/2"	1/2"
PPV16-12-34	1/2"	3/4"
PPV16-16-12	5/8"	1/2"
PPV16-16-34	5/8"	3/4"
PPV16-19-12	3/4"	1/2"
PPV16-19-34	3/4"	3/4"

Tech Sheet 60237

Elbow Hose Connector



Tube x Tube

0472	To Suit Hose ID
PV18-5	3/16"
PV18-8	5/16"
PV18-10	3/8"
PV18-12	1/2"

Tech Sheet 60237

Reducing Elbow Hose Connector



Tube x Tube

0472	To Suit Hose ID	To Suit Hose ID
PV17-6-5	1/4"	3/16"
PV17-8-6	5/16"	1/4"
PV17-10-8	3/8"	5/16"
PV17-12-10	1/2"	3/8"

Tech Sheet 60237

Tee Hose Connector



Tube x Tube

0472	To Suit Hose ID
PV23-5	3/16"
PV23-6	1/4"
PV23-8	5/16"
PV23-10	3/8"
PV23-12	1/2"

Tech Sheet 60237

Male Branch Tee Hose Connector



BSPT

0472	To Suit Hose ID	Thread
PPV22-6-18	1/4"	1/8"
PPV22-6-14	1/4"	1/4"
PPV22-8-14	5/16"	1/4"
PPV22-10-14	3/8"	1/4"
PPV22-12-14	1/2"	1/4"
PPV22-12-12	1/2"	1/2"
PPV22-12-38	1/2"	3/8"
PPV22-16-34	5/8"	3/4"
PPV22-19-34	3/4"	3/4"

Tech Sheet 60237

Fluid-Air Components Ltd

PLASTIC HOSE TAILS

OUR SUPERIOR DESIGN AND MANUFACTURING PROCESS ENSURES HIGHLY ACCURATE CONNECTOR DIMENSIONS FOR A PERFECT SEAL.

NORMA® Plastic Hose Connectors

- High performance products specified by the world s leading manufacturers for all their hose, tube and pipe applications
- Quality assured engineering and manufacture to ISO 9002, QS 9000 and ISO 14001
- Nylon polyamide 6 material
- Acetal POM material



Reducing Straight

7777	To Suit Hose ID mm	To Suit Hose ID mm
NOR-GRS4-3	4	3
NOR-GRS5-4	5	4
NOR-GRS6-4	6	4
NOR-GRS8-4	8	4
NOR-GRS8-6	8	6
NOR-GRS10-6	10	6
NOR-GRS10-8	10	8
NOR-GRS12-8	12	8
NOR-GRS12-10	12	10

- Acetal POM material



Elbow

7777	To Suit Hose ID mm
NOR-WS3	3
NOR-WS4	4
NOR-WS5	5
NOR-WS6	6
NOR-WS8	8
NOR-WS10	10
NOR-WS12	12
NOR-WS13	13
NOR-WS16	16
NOR-WS19	19
NOR-WS25	25

- Acetal POM material



Equal Tee

7777	To Suit Hose ID mm
NOR-TS3	3
NOR-TS4	4
NOR-TS5	5
NOR-TS6	6
NOR-TS7	7
NOR-TS8	8
NOR-TS10	10
NOR-TS12	12
NOR-TS13	13
NOR-TS14	14
NOR-TS15	15
NOR-TS16	16
NOR-TS19	19
NOR-TS25	25

- Acetal POM material



Equal Y

7777	To Suit Hose ID mm
NOR-YS3	3
NOR-YS4	4
NOR-YS5	5
NOR-YS6	6
NOR-YS8	8
NOR-YS10	10
NOR-YS12	12
NOR-YS13	13
NOR-YS14	14
NOR-YS16	16
NOR-YS19	19

- Acetal POM material



Reducing Tee, on Branch

7777	To Suit Hose ID mm	To Suit Hose ID mm
NOR-TRS4-6-4	4	6
NOR-TRS6-4-6	4	6
NOR-TRS8-4-8	4	8
NOR-TRS8-6-8	6	8
NOR-TRS10-6-10	6	10
NOR-TRS10-8-10	8	10
NOR-TRS10-13-10	10	13
NOR-TRS12-6-12	6	12
NOR-TRS12-8-12	8	12
NOR-TRS12-10-12	10	12
NOR-TRS15-6-15	6	15
NOR-TRS15-8-15	8	15
NOR-TRS18-10-18	10	18

- Acetal POM material



Reducing Y, on Split

7777	To Suit Hose ID mm	To Suit Hose ID mm
NOR-YRS4-6-4	6	4
NOR-YRS6-8-6	8	6

- Acetal POM material



Cross

7777	To Suit Hose ID mm
NOR-KS4	4
NOR-KS5	5
NOR-KS6	6
NOR-KS12	12

- Nylon polyamide 6 material



Straight Taper Thread, BSPT Male

7777	To Suit Hose ID mm	Thread
NOR-GES4R18	4	1/8"
NOR-GES4R14	4	1/4"
NOR-GES5R14	5	1/4"
NOR-GES6R18	6	1/8"
NOR-GES6R14	6	1/4"
NOR-GES6R38	6	3/8"
NOR-GES8R14	8	1/4"
NOR-GES8R38	8	3/8"
NOR-GES8R12	8	1/2"
NOR-GES10R14	10	1/4"
NOR-GES10R38	10	3/8"
NOR-GES12R38	12	3/8"
NOR-GES12R12	12	1/2"
NOR-GES14R12	14	1/2"
NOR-GES16R12	16	1/2"
NOR-GES16R34	16	3/4"
NOR-GES19R34	19	3/4"
NOR-GES25R1	25	1"

- Nylon polyamide 6 material



Elbow Taper Thread, BSPT Male

7777	To Suit Hose ID mm	Thread
NOR-WES4R18	4	1/8"
NOR-WES4R14	4	1/4"
NOR-WES6R18	6	1/8"
NOR-WES6R14	6	1/4"
NOR-WES6R38	6	3/8"
NOR-WES8R14	8	1/4"
NOR-WES8R12	8	1/2"
NOR-WES10R14	10	1/4"
NOR-WES10R38	10	3/8"
NOR-WES12R38	12	3/8"
NOR-WES12R12	12	1/2"
NOR-WES19R34	19	3/4"
NOR-WES25R1	25	1"

- Nylon polyamide 6 material



T Taper Thread, BSPT Male

7777	To Suit Hose ID mm	Thread
NOR-TES6R18	6	1/8"
NOR-TES8R14	8	1/4"
NOR-TES10R38	10	3/8"

- Acetal POM material



Straight Push-on

7777	To Suit Hose ID mm
NOR-GS3	3
NOR-GS4	4
NOR-GS5	5
NOR-GS6	6
NOR-GS8	8
NOR-GS10	10
NOR-GS12	12
NOR-GS13	13
NOR-GS14	14
NOR-GS16	16
NOR-GS19	19
NOR-GS25	25

Fluid-Air Components Ltd

HOSE TAILS

Emergency Hose Connector Set

Ideal for service engineers, or for workshops in case of a hose failure, this handy kit includes genuine PCL Hose Tails, Union Nuts, Coned Tailpieces and Reducing Bushes - all stored in a solid compact pocket case.



Kit contents:
4 x HC5194
3 x HC5656, HC1206, HC1217
2 x HC2479, HC5276, HC5275, HC1226, HC6897, HC1225
1 x HC6560, HC6895, HC6896

7000
HCKIT01

OXY-ACETYLENE FITTINGS

Hose Tails

Acetylene Hose Tail
LH Thread, BSPP

0121	Thread	Hosetail
GA04/04	1/4"	1/4"
GA06/04	3/8"	1/4"
GA06/05	3/8"	5/16"
GA06/06	3/8"	3/8"



Oxygen Hose Tail
RH Thread, BSPP

0121	Thread	Hosetail
GO04/04	1/4"	1/4"
GO06/04	3/8"	1/4"
GO06/05	3/8"	5/16"
GO06/06	3/8"	3/8"



Customers who bought from this page also purchased…

Stainless Steel Hose Clamps
…see page **1513**

stainless steel



Fluid-Air Components Ltd

MINIATURE FITTINGS M3-M6

Miniature fittings are for use with air connections in confined areas. The hose nipple and hose elbow styles accept nylon, soft nylon and polyurethane tubing.

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar

Male Studs



Male Thread, Metric

0425	ID mm	OD mm	Thread
MIPC4-M3	2.5	4	M3
MIPC3-M5	2	3	M5
MIPC4-M5	2.5	4	M5
MIPC5-M5	4	6	M5
MIPC4-M6	2.5	4	M6
MIPC6-M6	4	6	M6
Tech Sheet 60240			

Male Elbows



Male Thread, Metric

0425	ID mm	OD mm	Thread
MIPL4-M3	2.5	4	M3
MIPL4-M5	2.5	4	M5
MIPL5-M6	4	6	M6
Tech Sheet 60240			

Male Stud Tee Centre Leg



Male x Female, Metric

0425	Male Thread	Female Thread
MIUT-M5	M5	M5
Tech Sheet 60240		

Female Tee



Female Thread, Metric

0425	Thread
MIFT-M5	M5
Tech Sheet 60240	

Barb Male Hose Tails



Male Thread, Metric

0425	To Suit Hose ID mm	Thread
MIMHT2-M3	2	M3
MIMHT4-M3	4	M3
MIMHT3-M5	3	M5
MIMHT4-M5	4	M5
MIMHT6-M5	6	M5
Tech Sheet 60240		

Barb Male Elbow Hose Tails



Male Thread, Metric

0425	To Suit Hose ID mm	Thread
MIEHT3-M3	3	M3
MIEHT4-M3	4	M3
MIEHT3-M5	3	M5
MIEHT4-M5	4	M5
MIEHT6-M5	6	M5
Tech Sheet 60240		

Barb Male Stud Tees



Centre Leg Male, Metric

0425	To Suit Hose ID mm	Thread
MIBPB4-M5	4	M5
Tech Sheet 60240		

Nipple



Male Thread, Metric

0425	Thread
MIMM-M5	M5
Tech Sheet 60240	

Plugs



Male Thread, Metric

0425	Thread
MIPP-M5	M5
Tech Sheet 60240	

Female Adaptor



Female Thread, Metric

0425	Thread
MIFF-M5	M5
Tech Sheet 60240	

Male x Female Reducer



Male x Female, Metric

0425	Male Thread	Female Thread
MIMF-M5	M5	M5
Tech Sheet 60240		

Extended Male x Female Adaptor



Male x Female, Metric

0425	Male Thread	Female Thread
MIRB18-M5	1/8"	M5
Tech Sheet 60240		

BRASS QUICK-FIT FITTINGS

The working pressures and working temperatures depend on which type of tube is used; for this reason, the values must be determined in accordance with the tubes features. For the "swivel" fittings, the values are:

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 15 bar (220 psi)

Male Studs



BSPT

1030	ID mm	OD mm	Thread
C1-4/2.7-1/8	2.7	4	1/8"
C1-5/3-1/8	3	5	1/8"
C1-6/4-1/8	4	6	1/8"
C1-6/4-1/4	4	6	1/4"
C1-6/4-3/8	4	6	3/8"
C1-8/6-1/8	6	8	1/8"
C1-8/6-1/4	6	8	1/4"
C1-8/6-3/8	6	8	3/8"
C1-10/8-1/8	8	10	1/8"
C1-10/8-1/4	8	10	1/4"
C1-10/8-3/8	8	10	3/8"
C1-10/8-1/2	8	10	1/2"
C1-12/10-3/8	10	12	3/8"
C1-12/10-1/2	10	12	1/2"
C1-15/12.5-1/2	12.5	15	1/2"
Tech Sheet 10705			



BSPP & Metric

1030	ID mm	OD mm	Thread
C1Z-4/2.7-5M	2.7	4	M5
C1Z-4/2.7-6M	2.7	4	M6
C1Z-4/2.7-1/8	2.7	4	1/8"
C1Z-5/3-5M	3	5	M5
C1Z-5/3-6M	3	5	M6
C1Z-5/3-1/8	3	5	1/8"
C1Z-6/4-5M	4	6	M5
C1Z-6/4-6M	4	6	M6
C1Z-6/4-1/8	4	6	1/8"
C1Z-6/4-1/4	4	6	1/4"
C1Z-6/4-3/8	4	6	3/8"
C1Z-6/4-1/2	4	6	1/2"
C1Z-8/6-1/8	6	8	1/8"
C1Z-8/6-1/4	6	8	1/4"
C1Z-8/6-3/8	6	8	3/8"
C1Z-10/8-1/8	8	10	1/8"
C1Z-10/8-1/4	8	10	1/4"
C1Z-10/8-3/8	8	10	3/8"
C1Z-10/8-1/2	8	10	1/2"
C1Z-12/10-3/8	10	12	3/8"
C1Z-12/10-1/2	10	12	1/2"
Tech Sheet 10705			

Swivel Male Studs



BSPT

1030	ID mm	OD mm	Thread
C1X-6/4-1/4	4	6	1/4"
C1X-8/6-1/8	6	8	1/8"
C1X-8/6-1/4	6	8	1/4"
C1X-12/10-3/8	10	12	3/8"
Tech Sheet 10705			



BSPP

1030	ID mm	OD mm	Thread
C1Y-6/4-1/8	4	6	1/8"
C1Y-6/4-1/4	4	6	1/4"
C1Y-8/6-1/8	6	8	1/8"
C1Y-8/6-1/4	6	8	1/4"
C1Y-10/6.5-1/4	6.5	10	1/4"
C1Y-10/8-1/4	8	10	1/4"
C1Y-12/10-3/8	10	12	3/8"
Tech Sheet 10705			

Female Studs



BSPP

1030	ID mm	OD mm	Thread
C2-6/4-1/8	4	6	1/8"
C2-6/4-1/4	4	6	1/4"
C2-6/4-3/8	4	6	3/8"
C2-8/6-1/8	6	8	1/8"
C2-8/6-1/4	6	8	1/4"
C2-8/6-3/8	6	8	3/8"
C2-8/6-1/2	6	8	1/2"
C2-10/8-1/4	8	10	1/4"
C2-12/10-3/8	10	12	3/8"
Tech Sheet 10705			

Straight Connectors



Equal Tube x Tube

1030	ID mm	OD mm
C3-4/2.7	2.7	4
C3-5/3	3	5
C3-6/4	4	6
C3-8/6	6	8
C3-10/8	8	10
C3-12/10	10	12
C3-15/12.5	12.5	15
Tech Sheet 10705		

Unequal Tube x Tube

1030	ID A mm	OD A mm	ID B mm	OD B mm
C3-6/4-5/3	4	6	3	5
C3-8/6-6/4	6	8	4	6
C3-10/8-8/6	8	10	6	8
Tech Sheet 10705				

Bulkhead Connectors



Equal Tube x Tube

1030	ID mm	OD mm
C4-4/2.7	2.7	4
C4-6/4	4	6
C4-8/6	6	8
C4-10/8	8	10
C4-12/10	10	12
Tech Sheet 10705		

Unequal Tube x Tube

1030	ID A mm	OD A mm	ID B mm	OD B mm
C4-6/4-5/3	4	6	3	5
C4-8/6-6/4	6	8	4	6
Tech Sheet 10705				

Fluid-Air Components Ltd

BRASS QUICK-FIT FITTINGS

The working pressures and working temperatures depend on which type of tube is used; for this reason, the values must be determined in accordance with the tubes features. For the "swivel" fittings, the values are:

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 15 bar (220 psi)

Male Studs, Spring Guard



BSPT

1030	ID mm	OD mm	Thread
E1-6/4-1/8	4	6	1/8"
E1-6/4-1/4	4	6	1/4"
E1-8/6-1/4	6	8	1/4"
E1-8/6-3/8	6	8	3/8"
E1-10/8-1/8	8	10	1/8"
E1-10/8-1/4	8	10	1/4"
E1-10/8-3/8	8	10	3/8"
E1-10/8-1/2	8	10	1/2"
Tech Sheet 10705			



BSPP

1030	ID mm	OD mm	Thread
E1Z-6/4-1/8	4	6	1/8"
E1Z-6/4-1/4	4	6	1/4"
E1Z-8/6-1/4	6	8	1/4"
E1Z-10/8-3/8	8	10	3/8"
E1Z-12/10-3/8	10	12	3/8"
Tech Sheet 10705			

Swivel Male Studs, Spring Guard



BSPT

1030	ID mm	OD mm	Thread
E1X-6/4-1/8	4	6	1/8"
E1X-6/4-1/4	4	6	1/4"
E1X-8/6-1/4	6	8	1/4"
E1X-10/6.5-1/4	6.5	10	1/4"
E1X-10/8-1/4	8	10	1/4"
E1X-12/8-3/8	8	12	3/8"
Tech Sheet 10705			



BSPP

1030	ID mm	OD mm	Thread
E1Y-6/4-1/8	4	6	1/8"
E1Y-6/4-1/4	4	6	1/4"
E1Y-8/6-1/4	6	8	1/4"
E1Y-10/6.5-1/4	6.5	10	1/4"
Tech Sheet 10705			

Female Studs, Spring Guard



BSPP

1030	ID mm	OD mm	Thread
C2X-6/4-1/4	4	6	1/4"
C2X-8/6-1/4	6	8	1/4"
C2X-8/6-3/8	6	8	3/8"
C2X-10/8-1/4	8	10	1/4"
Tech Sheet 10705			

Locking Nuts



Metric

1030	ID mm	OD mm	Thread
C10-4/2.7-M6	2.7	4	M6 x 0.5
C10-5/3-M7	3	5	M7 x 0.75
C10-6/4-M8	4	6	M8 x 0.75
C10-6/4-M10	4	6	M10 x 1
C10-8/6-M12	6	8	M12 x 1
C10-10/8-M14	8	10	M14 x 1
C10-15/12.5-M20	12.5	15	M20 x 1
Tech Sheet 10705			

Locking Nuts, Spring Guard



Metric

1030	ID mm	OD mm	Thread
C10X-6/4	4	6	M10 x 1
C10X-8/6	6	8	M12 x 1
C10X-10/8	8	10	M14 x 1
C10X-12/10	10	12	M16 x 1
Tech Sheet 10705			

FT PRO



For **Hydraulic QRC's**
...see pages **290-294**

Fluid-Air Components Ltd

BRASS QUICK-FIT FITTINGS

The working pressures and working temperatures depend on which type of tube is used; for this reason, the values must be determined in accordance with the tubes features. For the "swivel" fittings, the values are:

Working Temperature: -18°C to +70°C

Maximum Working Pressure: 15 bar (220 psi)

Male Stud Elbows



BSPT

1030	ID mm	OD mm	Thread
C5-4/2.7-1/8	2.7	4	1/8"
C5-5/3-1/8	3	5	1/8"
C5-6/4-1/8	4	6	1/8"
C5-6/4-1/4	4	6	1/4"
C5-8/6-1/8	6	8	1/8"
C5-8/6-1/4	6	8	1/4"
C5-8/6-3/8	6	8	3/8"
C5-8/6-1/2	6	8	1/2"
C5-10/8-1/8	8	10	1/8"
C5-10/8-1/4	8	10	1/4"
C5-10/8-3/8	8	10	3/8"
C5-10/8-1/2	8	10	1/2"
C5-12/10-3/8	10	12	3/8"
C5-12/10-1/2	10	12	1/2"
C5-15/12.5-1/2	12.5	15	1/2"
Tech Sheet 10705			

Swivel Male Stud Elbows



BSPT

1030	ID mm	OD mm	Thread
C5X-4/2.7-1/8	2.7	4	1/8"
C5X-6/4-1/8	4	6	1/8"
C5X-6/4-1/4	4	6	1/4"
C5X-8/6-1/8	6	8	1/8"
C5X-8/6-1/4	6	8	1/4"
C5X-10/8-1/4	8	10	1/4"
Tech Sheet 10705			



BSPP

1030	ID mm	OD mm	Thread
C5Y-4/2.7-1/8	2.7	4	1/8"
C5Y-6/4-M5	4	6	M5
C5Y-6/4-1/8	4	6	1/8"
C5Y-6/4-1/4	4	6	1/4"
C5Y-8/6-1/8	6	8	1/8"
C5Y-8/6-1/4	6	8	1/4"
C5Y-10/8-1/4	8	10	1/4"
Tech Sheet 10705			

Female Stud Elbows



BSPP

1030	ID mm	OD mm	Thread
C5F-5/3-1/8	3	5	1/8"
C5F-6/4-1/8	4	6	1/8"
C5F-6/4-1/4	4	6	1/4"
C5F-8/6-1/8	6	8	1/8"
C5F-8/6-1/4	6	8	1/4"
C5F-10/8-1/4	8	10	1/4"
C5F-10/8-3/8	8	10	3/8"
Tech Sheet 10705			

Elbow Connectors



Equal Tube x Tube

1030	ID mm	OD mm
C6-4/2.7	2.7	4
C6-5/3	3	5
C6-6/4	4	6
C6-8/6	6	8
C6-10/8	8	10
C6-12/10	10	12
Tech Sheet 10705		

Tee Connectors



Equal Tube x Tube

1030	ID mm	OD mm
C9-4/2.7	2.7	4
C9-5/3	3	5
C9-6/4	4	6
C9-8/6	6	8
C9-10/8	8	10
C9-12/10	10	12
Tech Sheet 10705		

Unequal Tube x Tube

1030	ID A mm	OD A mm	ID B mm	OD B mm
C9-10/8-8/6	8	10	6	8
Tech Sheet 10705				

Male Stud Tees



BSPT, Branch

1030	ID mm	OD mm	Thread
C7-4/2.7-1/8	2.7	4	1/8"
C7-6/4-1/8	4	6	1/8"
C7-6/4-1/4	4	6	1/4"
C7-8/6-1/8	6	8	1/8"
C7-8/6-1/4	6	8	1/4"
C7-10/8-1/4	8	10	1/4"
C7-12/10-3/8	10	12	3/8"
C7-15/12.5-1/2	12.5	15	1/2"
Tech Sheet 10705			



BSPT, Run

1030	ID mm	OD mm	Thread
C8-6/4-1/8	4	6	1/8"
C8-6/4-1/4	4	6	1/4"
C8-8/6-1/8	6	8	1/8"
C8-8/6-1/4	6	8	1/4"
C8-10/8-1/4	8	10	1/4"
Tech Sheet 10705			

Male Stud Swivel Tees



BSPT, Branch

1030	ID mm	OD mm	Thread
C7X-6/4-1/8	4	6	1/8"
C7X-6/4-1/4	4	6	1/4"
C7X-8/6-1/8	6	8	1/8"
C7X-8/6-1/4	6	8	1/4"
C7X-10/8-1/4	8	10	1/4"
Tech Sheet 10705			



BSPP, Branch

1030	ID mm	OD mm	Thread
C7Y-6/4-1/8	4	6	1/8"
C7Y-8/6-1/8	6	8	1/8"
C7Y-8/6-1/4	6	8	1/4"
Tech Sheet 10705			

Fluid-Air Components Ltd

BRASS QUICK-FIT FITTINGS

Cross Connectors



Tube x Tube

1030	ID mm	OD mm
C11-6/4	4	6
C11-8/6	6	8
C11-12/10	10	12
C11-15/12.5	12.5	15
Tech Sheet 10705		

Female Single Banjo Body



Female Thread, BSPP

1030	Thread
6090-1/8	1/8"
6090-1/4	1/4"
Tech Sheet 10705	

Single Banjo Body - Quick-Fit



BSPP & Metric

1030	ID mm	OD mm	Thread
D5-4/2.7-5M	2.7	4	M5
D5-5/3-5M	3	5	M5
D5-6/4-5M	4	6	M5
D5-6/4-1/8	4	6	1/8"
D5-6/4-1/4	4	6	1/4"
D5-8/6-1/8	6	8	1/8"
D5-8/6-1/4	6	8	1/4"
D5-8/6-3/8	6	8	3/8"
D5-10/8-1/4	8	10	1/4"
D5-10/8-3/8	8	10	3/8"
D5-10/8-1/2	8	10	1/2"
D5-12/10-3/8	10	12	3/8"
Tech Sheet 10705			

Double Banjo Body - Quick-Fit



BSPP & Metric

1030	ID mm	OD mm	Thread
D6-4/2.7-1/8	2.7	4	1/8"
D6-8/6-1/8	6	8	1/8"
D6-8/6-1/4	6	8	1/4"
D6-8/6-1/2	6	8	1/2"
D6-10/8-1/8	8	10	1/8"
D6-10/8-1/2	8	10	1/2"
Tech Sheet 10705			

Washers



Nylon, Notched

1030	Thread
D11X-5M	M5
D11X-1/8	1/8"
D11X-1/4	1/4"
D11X-3/8	3/8"
D11X-1/2	1/2"
D11X-3/4	3/4"
Tech Sheet 10705	



Aluminium

1030	Thread
D11-5M	M5
D11-1/8	1/8"
D11-1/4	1/4"
D11-3/8	3/8"
D11-1/2	1/2"
D11-3/4	3/4"
D11-1	1"
D11-11/2	1.1/2"
D11-2	2"
Tech Sheet 10705	

Short Banjo Bolts



Single Stem, BSPP & Metric

1030	Thread
D7-5M-L	M5
D7-6M	M6
D7-1/8	1/8"
D7-1/4	1/4"
D7-3/8	3/8"
D7-1/2	1/2"
D7-M12X1.5	M12 x 1.5
Tech Sheet 10705	



Double Stem, BSPP

1030	Thread
D8-1/8	1/8"
D8-1/4	1/4"
D8-3/8	3/8"
D8-1/2	1/2"
Tech Sheet 10705	



Triple Stem, BSPP

1030	Thread
D13-1/4	1/4"
D13-1/2	1/2"
Tech Sheet 10705	




Washer 10mm

1030	Thread
D11Z-1/4	1/4"
Tech Sheet 10705	

FLOW REGULATORS


Screwdriver Quick-Fit Flow Regulators






For Cylinders, Metric & BSPP

1000	ID mm	OD mm	Thread
8950-4/2.7-1/8	2.7	4	1/8"
8950-6/4-M5	4	6	M5
8950-6/4-1/4	4	6	1/4"
8950-8/6-1/8	6	8	1/8"
8950-8/6-1/4	6	8	1/4"



For Valves, BSPP

1000	ID mm	OD mm	Thread
8960-6/4-1/8	6/4	6	1/8"
8960-8/6-1/8	8/6	8	1/8"



For Bi-directional, BSPP

1000	ID mm	OD mm	Thread
8970-6/4-M5	4	6	M5
8970-6/4-1/4	4	6	1/4"
8970-8/6-1/4	6	8	1/4"

Manual Quick-Fit Female BSPP



For Cylinders, BSPP

1000	Thread
8957-1/8	1/8"
8957-1/4	1/4"


For Valves, BSPP

1000	Thread
8967-1/8	1/8"
8967-1/4	1/4"

For Bi-directional, BSPP

1000	Thread
8977-1/8	1/8"
8977-1/4	1/4"


Manual Quick-Fit Flow Regulators






For Cylinders, BSPP

1000	ID mm	OD mm	Thread
8955-6/4-1/8	4	6	1/8"
8955-6/4-1/4	4	6	1/4"
8955-8/6-1/8	6	8	1/8"
8955-10/8-1/4	8	10	1/4"



For Valves, Metric & BSPP

1000	ID mm	OD mm	Thread
8965-4/2.7-M5	2.7	4	M5
8965-6/4-M5	4	6	M5
8965-8/6-1/8	6	8	1/8"
8965-10/8-1/4	8	10	1/4"



For Bi-directional, BSPP

1000	ID mm	OD mm	Thread
8975-4/2.7-1/8	2.7	4	1/8"
8975-6/4-1/8	4	6	1/8"

Screwdriver Flow Regulator Valves



For Cylinders, Male Thread, BSPP

1000	Thread
8900-1/4	1/4"

For Valves, Male Thread, Metric

1000	Thread
8910-M5	M5

For Bi-directional Male Thread, BSPP

1000	Thread
8920-1/8	1/8"
8920-1/4	1/4"

Screwdriver Quick-Fit Female BSPP



For Cylinders, BSPP

1000	Thread
8952-1/8	1/8"
8952-1/4	1/4"

For Valves, BSPP

1000	Thread
8962-1/8	1/8"

For Bi-directional, BSPP

1000	Thread
8972-1/8	1/8"
8972-1/4	1/4"

Manual Flow Regulator Valves



For Valves, Male Thread, Metric

1000	Thread
8915-M5	M5


For Bi-directional Male Thread, Metric & BSPP

1000	Thread
8925-M5	M5
8925-1/4	1/4"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Driven by Customers Designed by Metal Work

EB80 VALVES



...y cut costs on components, putting quality and performance in jeopardy? Make your systems ultra efficient with Metal Work Pneumatics.



ISO 9001 QUALITY MANAGEMENT SYSTEM

ISO 14001 ENVIRONMENTAL MANAGEMENT SYSTEM

OHSAS 18001 HEALTH AND SAFETY MANAGEMENT SYSTEM

SYNTEC MONITORED DUMP VALVE

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

FINGER-TIGHT FITTINGS

Body:
OT 58 brass

Temperature Range:
-45°C to +80°C

Maximum Pressure:
18 bar

Male Stud



BSP Tapered x Tube

9152	Thread BSPT	Tube mm	
		OD	ID
2301001	R1/8"	6	4
2301002	R1/4"	6	4
2301003	R1/8"	8	6
2301004	R1/4"	8	6
2301005	R3/8"	8	6
2301006	R1/4"	10	8
2301007	R3/8"	10	8
2301008	R1/2"	10	8
2301009	R3/8"	12	10
2301010	R1/2"	12	10

Male Stud



BSP Tapered x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2351001	M5	4	2
2356001	M5	5	3
2351002	M5	6	4
2351003	G1/8"	6	4
2351004	G1/4"	6	4
2351005	G1/8"	8	6
2351006	G1/4"	8	6
2351007	G3/8"	8	6
2351008	G1/4"	10	8
2351009	G3/8"	10	8
2351010	G1/2"	10	8
2351011	G3/8"	12	10
2351012	G1/2"	12	10

Female Stud



BSP Parallel x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2302002	G1/4"	6	4
2302004	G1/4"	8	6
2302005	G3/8"	8	6
2302006	G1/4"	10	8
2302007	G3/8"	10	8
2302008	G1/2"	10	8

Equal Elbow



Tube x Tube

9152	Tube mm	
	OD	ID
2306001	6	4
2306003	10	8
2306004	12	10

Male Stud Elbow



BSP Tapered x Tube

9152	Thread BSPT	Tube mm	
		OD	ID
2305001	G1/8"	6	4
2305002	G1/4"	6	4
2305003	G1/8"	8	6
2305004	G1/4"	8	6
2305005	G3/8"	8	6
2305006	G1/4"	10	8
2305007	G3/8"	10	8
2305008	G1/2"	10	8
2305009	G3/8"	12	10
2305010	G1/2"	12	10

Straight Connector



Tube x Tube

9152	Tube mm	
	OD	ID
2303001	6	4
2303002	8	6
2303003	10	8
2303004	12	10

Equal Tee



Tube x Tube

9152	Tube mm	
	OD	ID
2309001	6	4
2309002	8	6
2309004	12	10

Female Stud Elbow



BSP Parallel x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2352002	G1/4"	8	6

Bulkhead Connector



Tube x Tube

9152	Tube mm	
	OD	ID
2304001	6	4
2304002	8	6

Male Stud Branch Tee



BSP Parallel x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2307001	G1/8"	6	4
2307002	G1/4"	6	4
2307003	G1/8"	8	6
2307004	G1/4"	8	6
2307005	G3/8"	8	6
2307008	G1/2"	10	8
2307009	G3/8"	12	10
2307010	G1/2"	12	10

Male Stud Run Tee



BSP Parallel x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2308012	G1/8"	5	3
2308001	G1/8"	6	4
2308002	G1/4"	6	4
2308004	G1/4"	8	6
2308005	G3/8"	8	6
2308006	G1/4"	10	8
2308007	G3/8"	10	8
2308008	G1/2"	10	8
2308009	G3/8"	12	10
2308010	G1/2"	12	10

Swivel Tube Fitting with Spring Guard



BSP Parallel x Tube

9152	Thread BSPP	Tube mm	
		OD	ID
2501010	G1/4"	6	4
2501011	G1/4"	8	6
2501012	G3/8"	10	8

Equal Cross



Tube x Tube

9152	Tube mm	
	OD	ID
2311001	6	4
2311002	8	6
2311003	10	8

Fluid-Air Components Ltd

POLYPROPYLENE QUICK-FIT FITTINGS

Food Contact FDA 21 CFR

Food Contact (EU) 1935/2004

tefen

3 Way Valve

EPDM O-rings

Working Temperature: -5°C to +60°C

Maximum Working Pressure: 10 bar



1/4" BSPT Inlet

0497	Outlet
3WAY-18	1/8" BSPT
3WAY-14	1/4" BSPT
3WAY-8MM	8mm Barb

Tech Sheet 10488

Female Connector



BSPT

0497	ID mm	OD mm	Thread
PP2-6-18	4	6	1/8"
PP2-6-14	4	6	1/4"
PP2-8-14	6	8	1/4"

Male Run Tee



BSPT

0497	ID mm	OD mm	Thread
PP8-6-14	4	6	1/4"
PP8-12-14	10	12	1/4"
PP8-12-12	10	12	1/2"

Male Branch Tee



BSPT

0497	ID mm	OD mm	Thread
PP7-6-14	4	6	1/4"
PP7-8-14	6	8	1/4"
PP7-12-14	10	12	1/4"
PP7-12-38	10	12	3/8"
PP7-12-12	10	12	1/2"

Equal Tee



Tube x Tube

0497	ID mm	OD mm
PP9-6	4	6
PP9-8	6	8
PP9-12	10	12

Reducing Connector



Tube x Tube

0497	ID A mm	OD A mm	ID B mm	OD B mm
PP4-8-6	6	8	4	6

Equal Connector



Tube x Tube

0497	ID mm	OD mm
PP3-6	4	6
PP3-8	6	8
PP3-12	10	12

Equal Elbow



Tube x Tube

0497	ID mm	OD mm
PP5-6	4	6
PP5-8	6	8
PP5-12	10	12

Male Elbow



BSPT

0497	ID mm	OD mm	Thread
PP6-6-18	4	6	1/8"
PP6-6-14	4	6	1/4"
PP6-8-18	6	8	1/8"
PP6-8-14	6	8	1/4"
PP6-8-38	6	8	3/8"
PP6-12-14	10	12	1/4"
PP6-12-38	10	12	3/8"
PP6-12-12	10	12	1/2"

1 Body Type Banjo Bolt



Type PP13, BSPP

0497	Thread
PP13-14	1/4"

Double Banjo Body



BSPP

0497	ID mm	OD mm
PP10-8-8-18	6	8

Male Connector



BSPT

0497	ID mm	OD mm	Thread
PP1-6-18	4	6	1/8"
PP1-6-14	4	6	1/4"
PP1-8-18	6	8	1/8"
PP1-8-14	6	8	1/4"
PP1-12-14	10	12	1/4"
PP1-12-38	10	12	3/8"
PP1-12-12	10	12	1/2"

PVDF QUICK-FIT FITTINGS

Fittings made of PVDF function better than nylon when exposed to a wide range of temperatures and high corrosive chemicals.

This enables them to be used in industries such as chemical processing due to their excellent chemical resistance properties.

Working Temperature: -20°C to +120°C

Maximum Working Pressure: 14 bar at 20°C

Male Connector



BSPT

0472	ID mm	OD mm	Thread
PPV1-6-18	4	6	1/8"
PPV1-8-14	6	8	1/4"
PPV1-12-38	10	12	3/8"
Tech Sheet 60237			

Equal Connector



Tube x Tube

0472	ID mm	OD mm
PPV3-6	4	6
PPV3-8	6	8
PPV3-12	10	12
Tech Sheet 60237		

Equal Tee



Tube x Tube

0472	ID mm	OD mm
PPV9-6	4	6
PPV9-8	6	8
PPV9-12	10	12
Tech Sheet 60237		

Female Connector



BSPT

0472	ID mm	OD mm	Thread
PPV2-6-18	4	6	1/8"
PPV2-6-14	4	6	1/4"
PPV2-8-14	6	8	1/4"
Tech Sheet 60237			

Equal Elbow



Tube x Tube

0472	ID mm	OD mm
PPV5-6	4	6
PPV5-8	6	8
PPV5-12	10	12
Tech Sheet 60237		


Male Elbow



BSPT

0472	ID mm	OD mm	Thread
PPV6-6-18	4	6	1/8"
PPV6-8-14	6	8	1/4"
PPV6-12-38	10	12	3/8"
Tech Sheet 60237			

For **Nylon Hose Tails**
...see pages **1150-1151**



Fluid-Air Components Ltd

BRASS ADAPTORS

Male Adaptors - Equal



Male Thread, BSPT

0447	Thread
UP1-18	1/8"
UP1-14	1/4"
UP1-38	3/8"
UP1-12	1/2"
UP1-34	3/4"
UP1-1	1"
UP1-114	1.1/4"
UP1-112	1.1/2"
UP1-2	2"

Male Thread, NPT x BSPT

0447	Thread
660-1010	1/8"
660-1313	1/4"
660-1717	3/8"
660-2121	1/2"
660-2626	3/4"
660-3333	1"

Male Thread, Metric

0447	Thread
2018-MM05	M5 x 0.8
2018-MM08	M8 x 1.0
2018-MM10	M10 x 1.0
2018-MM12	M12 x 1.5
2018-MM14	M14 x 1.5
2018-MM16	M16 x 1.5
2018-MM18	M18 x 1.5
2018-MM20	M20 x 1.5
2018-MM22	M22 x 1.5



Flat Faced, Male Thread, BSPP

0447	Thread
PM18-18FF	1/8"
PM14-14FF	1/4"
PM38-38FF	3/8"
PM12-12FF	1/2"
PM34-34FF	3/4"
PM1-1FF	1"

Male Adaptors - Unequal



Male Thread, BSPT x BSPT

0447	Thread	Thread
UP2-18-14	1/8"	1/4"
UP2-18-38	1/8"	3/8"
UP2-18-12	1/8"	1/2"
UP2-14-38	1/4"	3/8"
UP2-14-12	1/4"	1/2"
UP2-38-12	3/8"	1/2"
UP2-14-34	1/4"	3/4"
UP2-38-34	3/8"	3/4"
UP2-12-34	1/2"	3/4"
UP2-12-1	1/2"	1"
UP2-34-1	3/4"	1"



Male Thread, BSPP x BSPT

0447	BSPP Thread	BSPT Thread
UP2-14-18P	1/4"	1/8"
UP2-18-14P	1/8"	1/4"
UP2-38-14P	3/8"	1/4"
UP2-12-14P	1/2"	1/4"
UP2-14-38P	1/4"	3/8"
UP2-12-38P	1/2"	3/8"
UP2-14-12P	1/4"	1/2"
UP2-38-12P	3/8"	1/2"
UP2-34-12P	3/4"	1/2"
UP2-12-34P	1/2"	3/4"
UP2-34-1P	3/4"	1"



Male Thread, NPT x NPT

0447	Thread	Thread
2018-2473	1/8"	1/8"
2018-2481	1/8"	1/4"
2018-2499	1/4"	1/4"
2018-2515	3/8"	1/4"
2018-2523	3/8"	3/8"
2018-2531	1/4"	1/2"
2018-2549	1/2"	3/8"
2018-2556	1/2"	1/2"
2018-2564	1/4"	3/4"
2018-2572	3/8"	3/4"
2018-2580	1/2"	3/4"
2018-2598	3/4"	3/4"
2018-2606	1/2"	1"
2018-2614	3/4"	1"
2018-2622	1"	1"

60º Male Adaptors



Coned, Male Thread, BSPP

0447	Thread	Thread
PM18-18	1/8"	1/8"
PM14-18	1/4"	1/8"
PM14-14	1/4"	1/4"
PM38-18	3/8"	1/8"
PM38-14	3/8"	1/4"
PM12-38	1/2"	3/8"
PM12-12	1/2"	1/2"
PM34-38	3/4"	3/8"
PM34-12	3/4"	1/2"
PM34-34	3/4"	3/4"
PM1-38	1"	3/8"
PM1-12	1"	1/2"
PM1-34	1"	3/4"
PM114-1	1.1/4"	1"
PM112-114	1.1/2"	1.1/4"



Male Thread, BSPP x BSPT

0447	Thread
PT18	1/8"
PT14	1/4"
PT38	3/8"
PT12	1/2"
PT1	1"
PT114	1.1/4"
PT112	1.1/2"
PT2	2"

BRASS ADAPTORS

Reducing Bush



Male Thread, BSPT x Female Thread, BSPP

0447	Female Thread	Male Thread
UP3-18-14	1/8"	1/4"
UP3-18-38	1/8"	3/8"
UP3-18-12	1/8"	1/2"
UP3-14-38	1/4"	3/8"
UP3-14-12	1/4"	1/2"
UP3-38-12	3/8"	1/2"
UP3-14-34	3/4"	1/4"
UP3-38-34	3/4"	3/8"
UP3-12-34	3/4"	1/2"
UP3-14-1	1/4"	1"
UP3-38-1	1"	3/8"
UP3-12-1	1"	1/2"
UP3-34-1	1"	3/4"
UP3-34-114	1.1/4"	3/4"
UP3-1-114	1.1/4"	1"
UP3-114-112	1.1/2"	1.1/4"
UP3-114-2	2"	1.1/4"
UP3-112-2	2"	1.1/2"



Male Thread x Female Thread, BSPP

0447	Male Thread	Female Thread
UP3-18-14P	1/4"	1/8"
UP3-18-38P	3/8"	1/8"
UP3-14-38P	3/8"	1/4"
UP3-18-12P	1/2"	1/8"
UP3-14-12P	1/2"	1/4"
UP3-38-12P	1/2"	3/8"
UP3-14-34P	3/4"	1/4"
UP3-38-34P	3/4"	3/8"
UP3-12-34P	3/4"	1/2"
UP3-14-1P	1"	1/4"
UP3-38-1P	1"	3/8"
UP3-12-1P	1"	1/2"
UP3-34-1P	1"	3/4"



Male Thread, BSPT x Female Thread, Metric

0447	Male Thread	Female Thread
UP3-M5-18	1/8"	M5 x 0.8



Male Thread, NPT x Female Thread, NPS

0447	Male Thread	Female Thread
UP3-18-14N	1/4"	1/8"
UP3-18-38N	3/8"	1/8"
UP3-14-38N	3/8"	1/4"
UP3-18-12N	1/2"	1/8"
UP3-14-12N	1/2"	1/4"
UP3-38-12N	1/2"	3/8"
UP3-38-34N	3/4"	3/8"
UP3-12-34N	3/4"	1/2"
UP3-14-34N	3/4"	1/4"
UP3-14-1N	1"	1/4"
UP3-12-1N	1"	1/2"
UP3-34-1N	1"	3/4"

Bushes



Male Thread, Metric x Female Thread, Metric & BSPP

0447	Male Thread	Female Thread
UP3-14-M16	M16 x 1.5	1/4"
UP3-14-M18	M18 x 1.5	1/4"
UP3-14-M20	M20 x 1.5	1/4"
UP3-M16-M20	M20 x 1.5	M16 x 1.5
UP3-M16-M22	M22 x 1.5	M16 x 1.5
UP3-14-M22	M22 x 1.5	1/4"
UP3-38-M22	M22 x 1.5	3/8"

Female Equal Socket



Female Thread, BSPP

0447	Thread
UP4-18P	1/8"
UP4-12P	1/2"

Female Thread, Metric

0447	Thread
UP4-MM05	M5 x 0.8
UP4-MM06	M6 x 1.0
UP4-MM08	M8 x 1.0
UP4-MM10	M10 x 1.0
UP4-MM12	M12 x 1.5
UP4-MM14	M14 x 1.5
UP4-MM16	M16 x 1.5
UP4-MM18	M18 x 1.5
UP4-MM20	M20 x 1.5
UP4-MM22	M22 x 1.5
UP4-MM26	M26 x 1.5
UP4-MM30	M30 x 1.5

Female Thread, NPS

0447	Thread
UP4-18N	1/8"
UP4-14N	1/4"
UP4-38N	3/8"
UP4-12N	1/2"
UP4-1N	1"

Female Unequal Socket



Female Thread, BSPP

0447	Thread	Thread
UP4-18-14P	1/8"	1/4"
UP4-38-18P	3/8"	1/8"
UP4-38-14P	3/8"	1/4"
UP4-12-14P	1/2"	1/4"
UP4-12-38P	1/2"	3/8"
UP4-34-14P	3/4"	1/4"
UP4-34-38P	3/4"	3/8"
UP4-12-34P	1/2"	3/4"
UP4-1-34P	1"	3/4"
UP4-1-38P	1"	3/8"
UP4-1-12P	1"	1/2"

Fluid-Air Components Ltd

Male x Female Unequal Socket



Male Thread, BSPT x Female Thread, BSPP

0447	Male Thread	Female Thread
UP13-18-14P	1/8"	1/4"
UP13-18-38P	1/8"	3/8"
UP13-14-38P	1/4"	3/8"
UP13-14-12P	1/4"	1/2"
UP13-38-12P	3/8"	1/2"
UP13-12-34P	1/2"	3/4"
UP13-34-1P	3/4"	1"

Bulkhead Connector



Male Thread, BSPP

0447	Thread
MB18	1/8"
MB14	1/4"
MB38	3/8"
MB12	1/2"
MB34	3/4"
MB1	1"
MB114	1.1/4"
MB112	1.1/2"
MB2	2"



Male Thread, Metric x Female Thread, BSPP

0447	Thread	Thread
MBM18	M16 x 1.5	1/8"
MBM14	M20 x 1.5	1/4"
MBM38	M26 x 1.5	3/8"
MBM12	M28 x 1.5	1/2"
MBM34	M34 x 1.5	3/4"
MBM1	M42 x 1.5	1"

Connectors



Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP13-18	1/8"
UP13-14	1/4"
UP13-38	3/8"
UP13-12	1/2"
UP13-34	3/4"
UP13-1	1"

Male Thread, Metric x Female Thread, BSPP

0447	Thread	Thread
UP13-M5-18	M5 x 0.8	1/8"
UP13-M5-14	M5 x 0.8	1/4"
UP13-M6-18	M6 x 1.0	1/8"
UP13-M6-14	M6 x 1.0	1/4"

Male x Female Thread, Metric

0447	Thread	Thread
UP13-M5-M5	M5 x 0.8	M5 x 0.8

Male Thread, NPT x Female Thread, NPS

0447	Thread
UP13-18N	1/8"
UP13-14N	1/4"
UP13-38N	3/8"
UP13-12N	1/2"
UP13-34N	3/4"
UP13-1N	1"

Reducing Connector



Male, NPT x Female Thread, NPS

0447	Thread	Thread
UP13-18-14N	1/8"	1/4"
UP13-18-38N	1/8"	3/8"
UP13-14-38N	1/4"	3/8"
UP13-14-12N	1/4"	1/2"
UP13-38-12N	3/8"	1/2"



Male Thread, UNF x Female Thread, BSPP

0447	Male Thread	Female Thread
UP13-18-14U	1/4"	1/8"

Equal Elbows



Male Thread, BSPT

0447	Thread
UP5-18	1/8"
UP5-14	1/4"
UP5-38	3/8"
UP5-12	1/2"
MML16	1"
Tech Sheet 20183	



Male Thread x Female Thread, NPT

0447	Thread
UP5-18N	1/8"
UP5-14N	1/4"
UP5-12N	1/2"
UP5-34N	3/4"
UP5-1N	1"



Female Thread, BSPT

0447	Thread
UP6-18	1/8"
UP6-14	1/4"
UP6-38	3/8"
UP6-12	1/2"
UP6-34	3/4"
UP6-1	1"
UP6-114	1.1/4"
Tech Sheet 20183	



Female Thread, NPT

0447	Thread
UP6-14N	1/4"
UP6-34N	3/4"



Female Thread, Metric

0447	Thread
UP6-M5	M5 x 0.8

BRASS ADAPTORS

Equal Elbows



Male Thread x Female Thread, BSPT

0447	Thread
UP7-18	1/8"
UP7-14	1/4"
UP7-38	3/8"
UP7-12	1/2"
UP7-1	1"
UP7-114	1.1/4"
UP7-112	1.1/2"
Tech Sheet 20183	



Male Thread x Female Thread, Metric

0447	Thread
UP7-MM05	M5 x 0.8



Male Thread, BSPT x Female Thread, BSPP

0447	Thread
MFL02	1/8"
MFL04	1/4"
MFL06	3/8"
MFL08	1/2"
MFL12	3/4"
MFL16	1"
MFL20	1.1/4"
MFL24	1.1/2"
MFL32	2"

Compact 90° Elbows



Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP7-18C	1/8"
UP7-14C	1/4"
UP7-38C	3/8"
UP7-12C	1/2"

45° Elbows



Female Thread, BSPP

0447	Thread
UP11-12F	1/2"
UP11-34F	3/4"
UP11-114F	1.1/4"
UP11-112F	1.1/2"
UP11-2F	2"

Equal Tees



Female Thread, BSPP x Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP22-18	1/8"
UP22-14	1/4"
UP22-38	3/8"
UP22-12	1/2"
UP22-34	3/4"



Male Thread, BSPT x Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP14-18	1/8"
UP14-38	3/8"
UP14-12	1/2"



Male Thread, BSPT x Female Thread, BSPP x Male Thread, BSPT

0447	Thread
UP15-18	1/8"
UP15-14	1/4"
UP15-38	3/8"
UP15-12	1/2"



Female Thread, BSPP x Female Thread, BSPP x Male Thread, BSPT

0447	Thread
UP16-18	1/8"
UP16-14	1/4"
UP16-38	3/8"
UP16-12	1/2"
UP16-34	3/4"
UP16-1	1"



Female Thread, BSPP

0447	Thread
UP8-18	1/8"
UP8-14	1/4"
UP8-38	3/8"
UP8-12	1/2"
UP8-34	3/4"
UP8-1	1"
UP8-114	1.1/4"
UP8-112	1.1/2"
Tech Sheet 20184	



Female Thread, NPT

0447	Thread
UP8-18N	1/8"
UP8-14N	1/4"
UP8-12N	1/2"



Male Thread, BSPT

0447	Thread
UP9-18	1/8"
UP9-14	1/4"
UP9-38	3/8"
UP9-12	1/2"
Tech Sheet 20184	

Female Block Equal Tee



Female Thread, BSPT

0447	Thread
UP10-18	1/8"
UP10-14	1/4"
UP10-38	3/8"
Tech Sheet 20185	

Fluid-Air Components Ltd

BRASS ADAPTORS

Male x Female 45º Equal Elbow



Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP11-18	1/8"
UP11-14	1/4"
Tech Sheet 20186	

Cross Adaptors



Male Thread, BSPT

0447	Thread
UP19-14	1/4"
UP19-38	3/8"



Male Thread, BSPT x Female Thread, BSPP

0447	Thread
UP20-14	1/4"
UP20-38	3/8"
UP20-12	1/2"
UP20-34	3/4"
UP20-1	1"



Female Thread, BSPP

0447	Thread
UP21-14	1/4"
UP21-38	3/8"
UP21-12	1/2"

Barrel Nipple



Male Thread, BSPT

0447	Thread
TT18	1/8"
TT14	1/4"
TT38	3/8"
TT12	1/2"
TT34	3/4"
TT1	1"

Swivel Union



Male Thread, BSPT

1000	Thread	Thread
LD10/10K	1/8"	1/8"
LD13/13K	1/4"	1/4"
LD17/17K	3/8"	3/8"
LD21/21K	1/2"	1/2"
LD26/26K	3/4"	3/4"
LD33/33K	1"	1"
Tech Sheet 20775		



Female Thread, BSPP

1000	Thread
LDF21/21K	1/2"
LDF26/26K	3/4"
LDF33/33K	1"
LDF42/42K	1.1/4"
LDF48/48K	1.1/2"
LDF52/52K	2"

Equal Y Branch Outlet



Female Thread, BSPP

1000	Thread
UP17-18	1/8"
UP17-14	1/4"
UP17-38	3/8"
UP17-12	1/2"



Female Thread, BSPP x Female Thread, BSPP x Male Thread, BSPT

1000	Thread
UP18-18	1/8"
UP18-14	1/4"
UP18-38	3/8"
UP18-12	1/2"

Triple Outlet



Female Thread, BSPP

1000	Thread
DO-17	3/8"
DO-21	1/2"
Tech Sheet 20776	

Locknuts



Female Thread, BSPP

0447	Thread
UP12-18	1/8"
UP12-14	1/4"
UP12-38	3/8"
UP12-12	1/2"
UP12-58	5/8"
UP12-34	3/4"
UP12-78	7/8"
UP12-1	1"
UP12-114	1.1/4"
UP12-112	1.1/2"

Flanged Locknuts



Female Thread, BSPP

0447	Thread
UP12-38F	3/8"
UP12-12F	1/2"
UP12-34F	3/4"
UP12-1F	1"
UP12-114F	1.1/4"
UP12-112F	1.1/2"



Female Thread, Metric

0447	Thread
UP12-MM10	M10 x 1.0
UP12-MM12	M12 x 1.0
UP12-MM14.1	M14 x 1.0
UP12-MM14	M14 x 1.5
UP12-MM15	M15 x 1.0
UP12-MM16	M16 x 1.5
UP12-MM18	M18 x 1.5
UP12-MM20	M20 x 1.5
UP12-MM22	M22 x 1.5
UP12-MM24	M24 x 1.5
UP12-MM26	M26 x 1.5
UP12-MM28	M28 x 1.5
UP12-MM30	M30 x 1.5
UP12-MM34	M34 x 1.5
UP12-MM38	M38 x 1.5

BRASS ADAPTORS

Flanged Plugs



Male Thread, BSPP

1000	Thread
VFP10	1/8"
VFP13	1/4"
VFP17	3/8"
VFP21	1/2"
VFP26	3/4"
VFP33	1"
VFP42	1.1/4"
VFP48	1.1/2"
VFP52	2"

Hollow Plugs



Male Thread, BSPT

0447	Thread
VHP18	1/8"
VHP14	1/4"
VHP38	3/8"
VHP12	1/2"
VHP58	5/8"
VHP34	3/4"
VHP1	1"
VHP114	1.1/4"

Male Thread, BSPP

0447	Thread
VHP18P	1/8"
VHP14P	1/4"
VHP38P	3/8"
VHP12P	1/2"
VHP58P	5/8"
VHP34P	3/4"
VHP1P	1"
VHP114P	1/4"
VHP112P	1/2"
VHP2P	2"

Male Thread, NPT

0447	Thread
VHP18N	1/8"
VHP14N	1/4"
VHP38N	3/8"
VHP12N	1/2"
VHP34N	3/4"
VHP2N	2"

Solid Plugs

Male Thread, Metric



0447	Thread
VHPM05	M5 x 0.8
VHPM06	M6 x 1.0
VHPM08	M8 x 1.0
VHPM14	M14 x 1.5
VHPM16	M16 x 1.5
VHPM18	M18 x 1.5
VHPM20	M20 x 1.5
VHPM22	M22 x 1.5
VHPM24	M24 x 1.5
VHPM26	M26 x 1.5
VHPM28	M28 x 1.5

Male Thread, BSPT

0447	Thread
VPS18	1/8"
VPS14	1/4"
VPS38	3/8"
VPS12	1/2"
VPS58	5/8"
VPS34	3/4"
VPS78	7/8"
VPS1	1"
VPS114	1.1/4"
VPS112	1.1/2"
VPS2	2"

Male Thread, BSPP

0447	Thread
VPS18P	1/8"
VPS14P	1/4"
VPS38P	3/8"
VPS12P	1/2"
VPS58P	5/8"
VPS34P	3/4"
VPS1P	1"
VPS112P	1.1/2"
VPS2P	2"

Male Thread, NPT



0447	Thread
VPS18N	1/8"
VPS14N	1/4"
VPS38N	3/8"
VPS12N	1/2"
VPS34N	3/4"
VPS1N	1"
VPS114N	1.1/4"
VPS112N	1.1/2"
VPS2N	2"

Square Head Plugs

Male Thread, BSPP



1000	Thread
VPQ14	1/4"
VPQ38	3/8"
VPQ12	1/2"
VPQ34	3/4"
VPQ1	1"
VPQ114	1.1/4"
VPQ112	1.1/2"
VPQ2	2"

Allen Key Plugs



Male Thread, BSPT

0447	Thread
AK-TT18	1/8"
AK-TT14	1/4"
AK-TT38	3/8"
AK-TT12	1/2"
AK-TT34	3/4"
AK-TT1	1"

Male Thread, BSPP

0447	Thread
AK-PP18	1/8"
AK-PP14	1/4"
AK-PP38	3/8"
AK-PP12	1/2"

Male Thread, Metric

0447	Thread
AK-MM08	M8 x 1.0
AK-MM10	M10 x 1.0
AK-MM12	M12 x 1.5
AK-MM14	M14 x 1.5
AK-MM16	M16 x 1.5
AK-MM18	M18 x 1.5
AK-MM20	M20 x 1.5
AK-MM22	M22 x 1.5
AK-MM24	M24 x 1.5

Male Thread, NPT

0447	Thread
AK-NN18	1/8"
AK-NN14	1/4"
AK-NN38	3/8"
AK-NN12	1/2"

Caps



Female Thread, BSPP

0447	Thread
VCAP10	1/8"
VCAP13	1/4"
VCAP17	3/8"
VCAP21	1/2"
VCAP26	3/4"
VCAP33	1"
VCAP42	1/4"
VCAP48	1/2"

Air Vents



Male Thread, BSPP

1000	Thread
AK-VV18	1/8"
AK-VV14	1/4"
AK-VV12	1/2"

Fluid-Air Components Ltd

NICKEL PLATED BRASS ADAPTORS

Temperature: +300 °C

Maximum Working Pressure
1/8" - 150 bar 1/4" - 100 bar 3/8" - 75 bar 1/2" - 50 bar 3/4" - 85 bar 1" - 80 bar

Equal Male Adaptors



Male Thread, BSPT

0422	Thread
DN10/10K	1/8"
DN13/13K	1/4"
DN17/17K	3/8"
DN21/21K	1/2"
DN26/26K	3/4"
DN33/33K	1"
DN42/42K	1.1/4"
DN50/50K	1.1/2"

Tech Sheet 1620



Male Thread, Metric & BSPP

0422	Thread
DN05/05	M5
DN10/10	1/8"
DN13/13	1/4"
DN17/17	3/8"
DN21/21	1/2"
DN26/26	3/4"
DN33/33	1"
DN42/42	1.1/4"
DN50/50	1.1/2"
DN55/55	2"

Tech Sheet 1620

Unequal Male Adaptors



Male Thread, BSPT

0422	Thread	Thread
DN10/13K	1/8"	1/4"
DN10/17K	1/8"	3/8"
DN10/21K	1/8"	1/2"
DN13/17K	1/4"	3/8"
DN13/21K	1/4"	1/2"
DN17/21K	3/8"	1/2"
DN21/26K	1/2"	3/4"
DN26/33K	3/4"	1"
DN33/42K	1"	1.1/4"
DN42/50K	1.1/4"	1.1/2"
DN50/55K	1.1/2"	2"

Tech Sheet 1622



Male Thread, Metric & BSPP

0422	Thread	Thread
DN05/10	M5	1/8"
DN10/13	1/8"	1/4"
DN10/17	1/8"	3/8"
DN13/17	1/4"	3/8"
DN13/21	1/4"	1/2"
DN17/21	3/8"	1/2"
DN21/26	1/2"	3/4"
DN26/33	3/4"	1"
DN33/42	1"	1.1/4"
DN42/50	1.1/4"	1.1/2"
DN50/55	1.1/2"	2"

Tech Sheet 1622

Male x Female Adaptors



Male Thread, BSPT x Female Thread, BSPP

0422	Male Thread	Female Thread
RL10/10K	1/8"	1/8"
RL10/13K	1/8"	1/4"
RL10/17K	1/8"	3/8"
RL13/13K	1/4"	1/4"
RL13/17K	1/4"	3/8"
RL13/21K	1/4"	1/2"
RL17/17K	3/8"	3/8"
RL17/21K	3/8"	1/2"
RL17/26K	3/8"	3/4"
RL21/21K	1/2"	1/2"
RL21/26K	1/2"	3/4"
RL21/33K	1/2"	1"
RL26/26K	3/4"	3/4"
RL26/33K	3/4"	1"
RL33/33K	1"	1"

Tech Sheet 10704

Male Thread, NPTF x Female Thread, BSPP

0422	Thread
RL10/10KN	1/8"
RL13/13KN	1/4"
RL17/17KN	3/8"

Tech Sheet 10704



Male Thread, BSPP x Female Thread, Metric & BSPP

0422	Male Thread	Female Thread
RL05/05	M5	M5
RL05/10	M5	1/8"
RL10/10	1/8"	1/8"
RL10/13	1/8"	1/4"
RL10/17	1/8"	3/8"
RL13/13	1/4"	1/4"
RL13/17	1/4"	3/8"
RL13/21	1/4"	1/2"
RL17/17	3/8"	3/8"
RL17/21	3/8"	1/2"
RL17/26	3/8"	3/4"
RL21/21	1/2"	1/2"
RL21/26	1/2"	3/4"
RL21/33	1/2"	1"
RL26/26	3/4"	3/4"
RL26/33	3/4"	1"
RL33/33	1"	1"

Tech Sheet 10704

Male Thread, BSPP x Female Thread, NPTF

0422	Thread
RL10/10N	1/8"
RL13/13N	1/4"
RL17/17N	3/8"
RL21/21N	1/2"

Tech Sheet 10704



Extension, Male Thread, BSPP x Female Thread, BSPP

0422	Thread	Length mm
RL05/05X	M5	18.5
RL10/10X	1/8"	22
RL10/10Y	1/8"	42
RL13/13X	1/4"	35
RL13/13Y	1/4"	51
RL17/17X	3/8"	41
RL21/21X	1/2"	35
RL26/26X	3/4"	50
RL33/33X	1"	50

Tech Sheet 10704

X = Standard Length (as photo), Y = Extended Length



You might also need
Hose & Tubing
see **Section 12**

Fluid-Air Components Ltd

NICKEL PLATED BRASS ADAPTORS

Equal Swivel Connectors



Male Thread, BSPT x Female Thread, BSPP

0422	Thread
2110-18	1/8"
2110-14	1/4"
2110-38	3/8"
Tech Sheet 10704	



Male Thread, BSPP x Female Thread, BSPP

0422	Thread
2115-18	1/8"
2115-14	1/4"
2115-38	3/8"
Tech Sheet 10704	

Note:
Un-plated only.



Male Thread, BSPT x Female Thread, BSPP

0422	Thread
SF10	1/8"
SF13	1/4"
SF17	3/8"
SF21	1/2"
Tech Sheet 10704	

Equal Bulkhead Connectors



Female Thread, Metric & BSPP x Male Thread, Metric

0422	Female Thread	Male Thread
3060-M5	M5	M10 x 1
3060-1/8	1/8"	M16 x 1.5
3060-1/4	1/4"	M20 x 1.5
3060-3/8	3/8"	M26 x 1.5
3060-1/2	1/2"	M28 x 1.5
3060-3/4	3/4"	M33 x 1.5
3060-1	1"	M42 x 1.5
Tech Sheet 10702		

Equal Sockets



Female Thread, Metric & BSPP

0422	Thread
MU05	M5
MU10	1/8"
MU13	1/4"
MU17	3/8"
MU21	1/2"
MU26	3/4"
MU33	1"
Tech Sheet 1621	

Unequal Sockets



Female Thread, Metric & BSPP

0422	Thread	Thread
MU05/10	M5	1/8"
MU10/13	1/8"	1/4"
MU10/17	1/8"	3/8"
MU10/21	1/8"	1/2"
MU13/17	1/4"	3/8"
MU13/21	1/4"	1/2"
MU17/21	3/8"	1/2"
MU17/26	3/8"	3/4"
MU21/26	1/2"	3/4"
MU21/33	1/2"	1"
MU26/33	3/4"	1"
Tech Sheet 1621		

Reducing Bushes



Male Thread, BSPP x Female Thread, Metric & BSPP

0422	Male Thread	Female Thread
RK05/10	1/8"	M5
RK05/13	1/4"	M5
RK10/13	1/4"	1/8"
RK10/17	3/8"	1/8"
RK10/21	1/2"	1/8"
RK13/17	3/8"	1/4"
RK13/21	1/2"	1/4"
RK13/26	3/4"	1/4"
RK17/21	1/2"	3/8"
RK17/26	3/4"	3/8"
RK17/33	1"	3/8"
RK21/26	3/4"	1/2"
RK21/33	1"	1/2"
RK26/33	1"	3/4"
RK33/42	1.1/4"	1"
RK42/50	1.1/2"	1.1/4"
RK42/55	2"	1.1/4"
RK50/55	2"	1.1/2"
Tech Sheet 1623		



Male Thread, BSPT x Female Thread, BSPP

0422	Male Thread	Female Thread
RK05/10K	1/8"	M5x0.8
RK10/13K	1/4"	1/8"
RK10/17K	3/8"	1/8"
RK13/17K	3/8"	1/4"
RK10/21K	1/2"	1/8"
RK13/21K	1/2"	1/4"
RK17/21K	1/2"	3/8"
RK13/26K	3/4"	1/4"
RK17/26K	3/4"	3/8"
RK21/26K	3/4"	1/2"
RK13/33K	1"	1/4"
RK17/33K	1"	3/8"
RK21/33K	1"	1/2"
RK26/33K	1"	3/4"
RK21/42K	1.1/4"	1/2"
RK26/42K	1.1/4"	3/4"
RK33/42K	1.1/4"	1"
RK33/50K	1.1/2"	1"
RK33/55K	2"	1"
RK42/55K	2"	1.1/4"
RK50/55K	2"	1.1/2"
Tech Sheet 1623		

Note:
*Un-plated only.



Male Thread, BSPP x Female Thread, Metric & BSPP

0422	Male Thread	Female Thread
2095-13/10	1/4"	1/8"
2095-17/10	3/8"	1/8"
2095-17/13	3/8"	1/4"
2095-21/13	1/2"	1/4"
2095-21/17	1/2"	3/8"
2095-26/21	3/4"	1/2"
2095-33/21	1"	1/2"
2095-33/26	1"	3/4"
Tech Sheet 1623		

Fluid-Air Components Ltd

NICKEL PLATED BRASS ADAPTORS

Equal Elbows



Female Thread, Metric & BSPP

0422	Thread
WIM5	M5
WI10	1/8"
WI13	1/4"
WI17	3/8"
WI21	1/2"
WI26	3/4"
WI33	1"
Tech Sheet 1093	



Male Thread, Metric & BSPT x Female Thread, Metric & BSPP

0422	Thread
WSLM5	M5
WSL10	1/8"
WSL13	1/4"
WSL17	3/8"
WSL21	1/2"
WSL26	3/4"
WSL33	1"
Tech Sheet 1093	



Male Thread, Metric & BSPT

0422	Thread
WAM5	M5
WA10	1/8"
WA13	1/4"
WA17	3/8"
WA21	1/2"
WA26	3/4"
WA33	1"
Tech Sheet 1093	

Equal Tees



Offset Male Thread, BSPT x Female Thread, BSPP

0422	Thread
TD10	1/8"
TD13	1/4"
TD17	3/8"
TD21	1/2"
TD26	3/4"
TD33	1"
Tech Sheet 1094	



Branch Female Thread, Metric & BSPP x Male Thread, Metric & BSPT

0422	Thread
TCM5	M5
TC10	1/8"
TC13	1/4"
TC17	3/8"
TC21	1/2"
TC26	3/4"
TC33	1"
Tech Sheet 1094	



Male Thread, BSPT

0422	Thread
TA10	1/8"
TA13	1/4"
TA17	3/8"
TA21	1/2"
TA26	3/4"
TA33	1"
Tech Sheet 1094	



Female Thread, Metric & BSPP

0422	Thread
TIM5	M5
TI10	1/8"
TI13	1/4"
TI17	3/8"
TI21	1/2"
TI26	3/4"
TI33	1"
Tech Sheet 1094	



Branch Male Thread, Metric & BSPT x Female Thread, Metric & BSPP

0422	Thread
TKL05	M5
TKL10	1/8"
TKL13	1/4"
TKL17	3/8"
TKL21	1/2"
TKL26	3/4"
TKL33	1"
Tech Sheet 1094	



Offset Female Thread, Metric & BSPP x Male Thread, Metric & BSPT

0422	Thread
TB05	M5
TB10	1/8"
TB13	1/4"
TB17	3/8"
TB21	1/2"
TB26	3/4"
TB33	1"
Tech Sheet 1094	

NICKEL PLATED BRASS ADAPTORS

Equal Block Elbows



Male Thread,
BSPP x Female Thread, BSPP

0422	Thread
6070-1/8	1/8"
6070-1/4	1/4"

Equal Block Tees



Male Thread,
BSPP x Female Thread, BSPP

0422	Thread
6080-1/8	1/8"
6080-1/4	1/4"

90º Wall Bracket Fitting



Female Thread, BSPP

0422	Thread
5050-1/2	1/2"
Tech Sheet 10703	

Equal Crosses



Male Thread
BSPT x Female Thread, BSPP

0422	Thread
FD10	1/8"
FD13	1/4"
FD17	3/8"
FD21	1/2"
Tech Sheet 1095	



Male Thread, BSPT

0422	Thread
FE10	1/8"
FE13	1/4"
FE17	3/8"
FE21	1/2"
Tech Sheet 1095	



Female Thread, BSPP

0422	Thread
FC10	1/8"
FC13	1/4"
FC17	3/8"
FC21	1/2"
Tech Sheet 1095	

Equal Y Connectors



Female Thread, BSPP

0422	Thread
ZO-10	1/8"
ZO-13	1/4"
ZO-17	3/8"
ZO-21	1/2"
Tech Sheet 1096	



Male Thread,
BSPT x Female Thread, BSPP

0422	Male Thread
XO-10	1/8"
XO-13	1/4"
XO-17	3/8"
XO-21	1/2"
Tech Sheet 1096	

Triple Outlet



Female Thread, BSPP

0422	Thread
TO06NP	3/8"



For **Malleable Iron Fittings**
...see pages **1178-1380**



For **Malleable Iron Accessories**
...see pages **1184-1385**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

NICKEL PLATED BRASS ADAPTORS

Blanking Plugs



Male Thread, BSPT

0422	Thread
VZ10K	1/8"
VZ13K	1/4"
VZ17K	3/8"
VZ21K	1/2"
VZ26K	3/4"
VZ33K	1"



Male Thread, Metric & BSPP

0422	Thread
VZ05	M5
VZ10	1/8"
VZ13	1/4"
VZ17	3/8"
VZ21	1/2"
VZ26	3/4"
VZ33	1"
Tech Sheet 10704	



Nitrile O-Ring Seal & Hexagon Recess, Male Thread, Metric & BSPP

0422	Thread
ZV-05	M5
ZV-10	1/8"
ZV-13	1/4"
ZV-17	3/8"
ZV-21	1/2"
ZV-26	3/4"
ZV-33	1"
Tech Sheet 10704	



FKM O-Ring Seal & Hexagon Recess, Male Thread, Metric & BSPP

0422	Thread
ZV-05FKM	M5
ZV-10FKM	1/8"
ZV-13FKM	1/4"
ZV-17FKM	3/8"
ZV-21FKM	1/2"

Allen Key Plugs



Male Thread, BSPT

0422	Thread
3025-1/8	1/8"
3025-1/4	1/4"
3025-3/8	3/8"
3025-1/2	1/2"
3025-3/4	3/4"
3025-1	1"
Tech Sheet 10700	



Male Thread, BSPP

0422	Thread
3026-1/8	1/8"
3026-1/4	1/4"
3026-3/8	3/8"
3026-1/2	1/2"
3026-3/4	3/4"
Tech Sheet 10700	

Blanking Caps



Female Thread, BSPP

0422	Thread
VK10	1/8"
VK13	1/4"
VK17	3/8"
VK21	1/2"
VK26	3/4"
VK33	1"
Tech Sheet 10700	

Lock Nuts



Female Thread, BSPP

0422	Thread
KM10WN	1/8"
KM13WN	1/4"
KM17WN	3/8"
KM21WN	1/2"
KM26WN	3/4"
Tech Sheet 10702	

Equal Socket



Female Thread, BSPP

0447	Thread
FFA02/02NP	1/8"
FFA04/04NP	1/4"
FFA06/06NP	3/8"
FFA08/08NP	1/2"
FFA12/12NP	3/4"
FFA16/16NP	1"

Fluid-Air Components Ltd

NICKEL PLATED BRASS ADAPTORS

Unequal Reducing Sockets



Female Thread, BSPP

0447	Thread	Thread
FFR04/02NP	1/4"	1/8"
FFR06/04NP	3/8"	1/4"
FFR08/04NP	1/2"	1/4"
FFR08/06NP	1/2"	3/8"
FFR12/04NP	3/4"	1/4"
FFR12/06NP	3/4"	3/8"
FFR12/08NP	3/4"	1/2"
FFR16/08NP	1"	1/2"
FFR16/12NP	1"	3/4"

Caps



Female Thread, Metric

0447	Thread
CAP04NP	1/4"
CAP06NP	3/8"
CAP08NP	1/2"
CAP16NP	1"



For **Reusable Hydraulic Fittings** ...see page **41**

Hexagonal Plugs



Male Thread, BSPT

0447	Thread
PBT02SNP	1/8"
PBT04SNP	1/4"
PBT06SNP	3/8"



Male Thread, BSPP

0447	Thread
PBP02SNP	1/8"
PBP06SNP	3/8"
PBP08SNP	1/2"

Allen Key Plugs



Male Thread, NPT

0447	Thread
AKN02NP	1/8"
AKN04NP	1/4"
AKN06NP	3/8"
AKN08NP	1/2"



Steel, Male Thread, BSPT

0447	Thread
SAK02	1/8"
SAK04	1/4"
SAK06	3/8"
SAK08	1/2"

Lock Nuts



Female Thread, Metric

0447	Thread
LNM15NP	M15 x 1.0
LNM20NP	M20 x 1.5
LNM24NP	M24 x 1.5
LNM26NP	M26 x 1.5
LNM28NP	M28 x 1.5



Female Thread, BSPP

0447	Thread
LN02NP	1/8"
LN04NP	1/4"
LN06NP	3/8"
LN08NP	1/2"
LN12NP	3/4"
LN16NP	1"

Fluid-Air Components Ltd

POLYPROPYLENE HOSE ADAPTORS

Reducing Bush



Male x Female, BSPP

1050	Male Thread	Female Thread
PRB34-12	3/4"	1/2"
PRB1-12	1"	1/2"
PRB1-34	1"	3/4"
PRB114-12	1.1/4"	1/2"
PRB114-34	1.1/4"	3/4"
PRB114-1	1.1/4"	1"
PRB112-34	1.1/2"	3/4"
PRB112-1	1.1/2"	1"
PRB112-114	1.1/2"	1.1/4"
PRB2-34	2"	3/4"
PRB2-1	2"	1"
PRB2-114	2"	1.1/4"
PRB2-112	2"	1.1/2"
PRB212-2	2.1/2"	2"
PRB3-2	3"	2"
PRB3-212	3"	2.1/2"
Tech Sheet 10640		

Male x Female Reducer



Male x Female, BSPP

1050	Male Thread	Female Thread
PRE12-38	1/2"	3/8"
PRE34-12	3/4"	1/2"
PRE1-12	1"	1/2"
PRE1-34	1"	3/4"
PRE114-1	1.1/4"	1"
PRE112-114	1.1/2"	1.1/4"
PRE2-112	2"	1.1/2"
Tech Sheet 10640		

Reducing Nipple



Male, BSPP

1050	Thread	Thread
PRN34-12	3/4"	1/2"
PRN1-34	1"	3/4"
PRN114-1	1.1/4"	1"
PRN112-114	1.1/2"	1.1/4"
PRN2-112	2"	1.1/2"
PRN212-2	2.1/2"	2"
Tech Sheet 10640		

Nipple



Male, BSPP

1050	Thread
PEN12-12	1/2"
PEN34-34	3/4"
PEN1-1	1"
PEN114-114	1.1/4"
PEN112-112	1.1/2"
PEN2-2	2"
PEN3-3	3"
Tech Sheet 10640	

Plug



Male, BSPP

1050	Thread
PTP12	1/2"
PTP34	3/4"
PTP1	1"
PTP114	1.1/4"
PTP112	1.1/2"
PTP2	2"
PTP212	2.1/2"
Tech Sheet 10640	

Reducing Socket



Female, BSPP

1050	Thread	Thread
PRS34-12	3/4"	1/2"
PRS1-34	1"	3/4"
PRS114-1	1.1/4"	1"
PRS112-114	1.1/2"	1.1/4"
PRS2-112	2"	1.1/2"
Tech Sheet 10640		

Socket



Female, BSPP

1050	Thread
PES12-12	1/2"
PES34-34	3/4"
PES1-1	1"
PES114-114	1.1/4"
PES112-112	1.1/2"
PES2-2	2"
PES3-3	3"
Tech Sheet 10640	

Cap



Female, BSPP

1050	Thread
PTC12	1/2"
PTC34	3/4"
PTC1	1"
PTC114	1.1/4"
PTC112	1.1/2"
PTC2	2"
Tech Sheet 10640	

NYLON ADAPTORS

Food Contact FDA 21 CFR | Food Contact (EU) 1935/2004

tefen

Nylon 6-6

Temperature: -20 to 110°C

Working Pressure: Up to 14 bar (200 psi) at 20°C

Fittings Dimensions: refer to tube ID or OD, with respect to the common application

Unequal Nipple



BSPT

0497	Thread	Thread
PN1-14-18	1/4"	1/8"
PN1-38-14	3/8"	1/4"
PN1-12-14	1/2"	1/4"
PN1-12-38	1/2"	3/8"

Equal Nipple



BSPT

0497	Thread
PN2-18	1/8"
PN2-14	1/4"
PN2-38	3/8"
PN2-12	1/2"

Reducing Socket



BSPT

0497	Thread A	Thread B
PN6-14-18	1/8"	1/4"
PN6-38-18	1/8"	3/8"
PN6-38-14	1/4"	3/8"
PN6-12-14	1/4"	1/2"
PN6-34-14	1/4"	3/4"
PN6-12-38	3/8"	1/2"

Female Socket



BSPT

0497	Thread
PN5-18	1/8"
PN5-14	1/4"
PN5-38	3/8"
PN5-12	1/2"

Bush



BSPT

0497	Male Thread	Female Thread
PN3-18-14	1/4"	1/8"
PN3-18-12	1/2"	1/8"
PN3-14-18	1/8"	1/4"
PN3-14-14	1/4"	1/4"
PN3-14-38	3/8"	1/4"
PN3-38-18	1/8"	3/8"
PN3-38-14	1/4"	3/8"
PN3-38-38	3/8"	3/8"
PN3-38-12	1/2"	3/8"
PN3-12-14	1/4"	1/2"
PN3-12-38	3/8"	1/2"
PN3-12-12	1/2"	1/2"

Reducing Bush



BSPT

0497	Male Thread	Female Thread
PN4-14-18	1/4"	1/8"
PN4-38-18	3/8"	1/8"
PN4-38-14	3/8"	1/4"
PN4-12-14	1/2"	1/4"
PN4-12-38	1/2"	3/8"
PN4-34-14	3/4"	1/4"
PN4-34-38	3/4"	3/8"
PN4-34-12	3/4"	1/2"

Equal Elbow



BSPT

0497	Thread
PN10-18	1/8"
PN10-14	1/4"
PN10-38	3/8"
PN10-12	1/2"

Reducing Elbow



BSPT

0497	Thread	Thread
PN11-14-18	1/4"	1/8"
PN11-38-14	3/8"	1/4"

Equal Tee



BSPT

0497	Thread
PN7-14	1/4"
PN7-38	3/8"
PN7-12	1/2"

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PVDF ADAPTORS

Fittings made of PVDF function better then nylon when exposed to a wide range of temperatures and high corrosive chemicals.

This enables them to be used in industries such as chemical processing due to their excellent chemical resistance properties.

Working Temperature: -20°C to +120°C

Maximum Working Pressure: 14 bar at 20°C

Equal Nipple



BSPT

0472	Thread
PV2-18	1/8"
PV2-14	1/4"
PV2-38	3/8"
PV2-12	1/2"
Tech Sheet 60237	

Unequal Nipple



BSPT

0472	Thread	Thread
PV1-14-18	1/4"	1/8"
PV1-38-14	3/8"	1/4"
PV1-12-14	1/2"	1/4"
PV1-12-38	1/2"	3/8
Tech Sheet 60237		

Female Socket



BSPT

0472	Thread
PV5-18	1/8"
PV5-14	1/4"
PV5-38	3/8"
PV5-12	1/2"
Tech Sheet 60237	

Reducing Socket



BSPT

0472	Thread	Thread
PV6-14-18	1/4"	1/8"
PV6-38-14	3/8"	1/4"
PV6-12-14	1/2"	1/4"
Tech Sheet 60237		

Reducing Bush



BSPT

0472	Male Thread	Female Thread
PV4-14-18	1/4"	1/8"
PV4-38-18	3/8"	1/8"
PV4-38-14	3/8"	1/4"
PV4-12-18	1/2"	1/8"
PV4-12-14	1/2"	1/4"
PV4-12-38	1/2"	3/8"
Tech Sheet 60237		

Bush



BSPT

0472	Male Thread	Female Thread
PV3-18-38	1/8"	3/8"
PV3-14-18	1/4"	1/8"
PV3-14-14	1/4"	1/4"
PV3-14-38	1/4"	3/8"
PV3-38-18	3/8"	1/8"
PV3-38-14	3/8"	1/4"
PV3-38-12	3/8"	1/2"
PV3-12-14	1/2"	1/4"
Tech Sheet 60237		

Equal Elbow



BSPT

0472	Thread
PV10-38	3/8"
PV10-12	1/2"
Tech Sheet 60237	

Equal Tee



BSPT

0472	Thread
PV7-18	1/8"
PV7-14	1/4"
Tech Sheet 60237	

Blanking Plug



BSPT

0472	Thread
PV12-18	1/8"
PV12-14	1/4"
PV12-38	3/8"
PV12-12	1/2"
Tech Sheet 60237	

Blanking Cap



BSPT

0472	Thread
PV13-14	1/4"
PV13-38	3/8"
PV13-12	1/2"
Tech Sheet 60237	

3000lb FORGED PIPE FITTINGS, ANSI B16.11

Working Temperature: 0°C to +180°C

Maximum Working Pressure: 206 bar

Pressure and temperature ratings according to ASME B16.11

Available up to 4"

90° Equal Elbow



Female Thread, NPT

0506	Thread
1013-0003	1/2"
1013-0005	1"
1013-0008	2"
Tech Sheet 68800	

Equal Tee



Female Thread, NPT

0506	Thread
1013-0009	1/4"
1013-0011	1/2"
1013-0013	1"
1013-0016	2"
Tech Sheet 68800	

Equal Hexagon Nipple



Male Thread, NPT

0506	Thread
1013-0025	1/4"
1013-0027	1/2"
1013-0028	3/4"
1013-0029	1"
1013-0030	1.1/4"
1013-0032	2"
Tech Sheet 68800	

Equal Union



Female Thread, NPT

0506	Thread
1013-0034	3/8"
1013-0035	1/2"
1013-0038	1.1/4"
1013-0039	1.1/2"
1013-0040	2"
Tech Sheet 68800	

Hexagon Plug



Male Thread, NPT

0506	Thread
1013-0041	1/4"
1013-0042	3/8"
1013-0043	1/2"
1013-0044	3/4"
1013-0048	2"
Tech Sheet 68800	

Equal Coupling



Female Thread, NPT

0506	Thread
1013-0050	3/8"
1013-0051	1/2"
1013-0052	3/4"
1013-0053	1"
1013-0054	1.1/4"
1013-0056	2"
Tech Sheet 68800	





For **Flanges & Gaskets** see pages **1386-1390**

Fluid-Air Components Ltd

150lb 316 STAINLESS STEEL PIPE FITTINGS

RoHS 3 COMPLIANT | ISO 9001:2015 | stainless steel | HAITIMA

This technical data is applicable to the full range of 316 Stainless Steel Adaptors only.
Threads: Tapered in conformity with ISO 7.1, BS 21, DIN 2999. Parallel in conformity with BS 2779, ISO 228.
Dimensions: All components are manufactured to the requirements of ASTM A-351.
The dimensions are in accordance with ANSI B16.3.

Working Temperature: -20°C to +260°C

Working Pressure: 20 bar

Equal Cross



Female Thread, BSPP

1111	Thread
EC-18	1/8"
EC-14	1/4"
EC-38	3/8"
EC-12	1/2"
EC-34	3/4"
EC-1	1"
EC-114	1.1/4"
EC-112	1.1/2"
EC-2	2"
Tech Sheet 1800	

Equal Tee



Female Thread, BSPP

1111	Thread
ET-18	1/8"
ET-14	1/4"
ET-38	3/8"
ET-12	1/2"
ET-34	3/4"
ET-1	1"
ET-114	1.1/4"
ET-112	1.1/2"
ET-2	2"
ET-212	2.1/2"
ET-3	3"
ET-4	4"
Tech Sheet 1799	

Straight Hose Tails



Male Thread, BSPT

1111	Thread	To Suit Hose ID
HT-18-06	1/8"	1/4" (6mm)
HT-14	1/4"	1/4" (6mm)
HT-14-08	1/4"	5/16" (8mm)
HT-14-10	1/4"	3/8" (10mm)
HT-14-13	1/4"	1/2" (13mm)
HT-38-08	3/8"	5/16" (8mm)
HT-38	3/8"	3/8" (10mm)
HT-38-13	3/8"	1/2" (13mm)
HT-12-06	1/2"	1/4" (6mm)
HT-12-10	1/2"	3/8" (10mm)
HT-12	1/2"	1/2" (13mm)
HT-12-19	1/2"	3/4" (19mm)
HT-12-25	1/2"	1" (25mm)
HT-12-16	1/2"	5/8"
HT-34-13	3/4"	1/2" (13mm)
HT-34	3/4"	3/4" (19mm)
HT-1-19	1"	3/4" (19mm)
HT-1	1"	1" (25mm)
HT-1-31	1"	1.1/4" (31mm)
HT-114	1.1/4"	1.1/4" (31mm)
HT-112	1.1/2"	1.1/2" (38mm)
HT-2	2"	2" (50mm)
HT-212	2.1/2"	2.1/2" (63mm)
HT-3	3"	3" (75mm)
HT-4	4"	4" (100mm)
Tech Sheet 1795		



Female Fixed Thread, BSPP

1111	Thread	To Suit Hose ID
SFHT10/06	1/8"	6mm (1/4")
SFHT13/06	1/4"	6mm (1/4")
SFHT13/09	1/4"	9mm (3/8")
SFHT17/10	3/8"	10mm (3/8")
SFHT21/13	1/2"	13mm (1/2")
SFHT26/19	3/4"	19mm (3/4")
SFHT33/25	1"	25mm (1")
SFHT42/32	1.1/4"	32mm (1.1/4")
SFHT48/38	1.1/2"	38mm (1.1/2")
SFHT52/51	2"	51mm (2")
Tech Sheet 20777		



Equal Hose Joiner

1111	To Suit Hose ID
DS06-SS	1/4" (6mm)
DS08-SS	5/16" (8mm)
DS10-SS	3/8" (10mm)
DS13-SS	1/2" (13mm)
Tech Sheet 20778	



Swivel Female Thread, 60° Coned Seat, BSPP

1111	Thread	To Suit Hose ID
FH13/14SS	1/4"	1/4" (6mm)
FH17/38SS	3/8"	3/8" (10mm)
FH21/12SS	1/2"	1/2" (13mm)
FH26/34SS	3/4"	3/4" (19mm)
FH33/19SS	1"	3/4"
FH48/38SS	1.1/2"	1.1/2"
FH52/50SS	2"	2"
Tech Sheet 20779		

Barrel Nipple



Male Thread, BSPT


1111	Thread	Length mm
BN-18X30	1/8"	30
BN-18	1/8"	40
BN-14	1/4"	40
BN-14X80	1/4"	80
BN-38	3/8"	40
BN-38X80	3/8"	80
BN-12	1/2"	60
BN-12X80	1/2"	80
BN-34	3/4"	60
BN-34X80	3/4"	80
BN-1	1"	60
BN-1X100	1"	100
BN-1X150	1"	150
BN-114	1.1/4"	80
BN-112	1.1/2"	80
BN-2	2"	100
BN-212	2.1/2"	100
BN-3	3"	120
BN-4	4"	120
Tech Sheet 1803		



For Stainless Steel 304 & 316

see section **10** page **1225**

Many of our products are produced in stainless steel (304 or 316) so if that is your focus and to simplify product selection, we have all our products regardless of type or application grouped in section 10 (coded yellow) of our catalogue.



Food safety starts with rigorous hygiene and nickel-containing stainless steels are the superior, reliable standard at every link of the food and industry supply chain. Though it may not be inherently antimicrobial, stainless steel, particularly 304 or 316 stainless steels, are one of the best materials to use in a food and beverage processing environment.

Industries

- Food
- Brewing
- Transport
- Pharmaceuticals
- Chemicals

Stainless steel is commonly used in the food industry because of its non-toxicity and ease of cleaning. This material does not react chemically with other substances and can be cleaned with high temperatures. In the process of disinfection, we can also use most of the available detergents. Stainless steel is not absorbent and after rinsing its surface with water, you can freely use it for food processing. This material is extremely durable and does not require regular and expensive maintenance. Although stainless steel can be slightly more expensive than other raw materials, it is an excellent compromise between the interests of the consumer and manufacturer.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

150lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

HAITIMA

Close Nipple



Male Thread, BSPP

1111	Thread
CPN-14	1/4"
CPN-38	3/8"
CPN-12	1/2"
CPN-34	3/4"
CPN-1	1"
CPN-114	1.1/4"
CPN-112	1.1/2"
CPN-2	2"
CPN-212	2.1/2"

Tech Sheet 1801

Female Reducing Socket



Female Thread, BSPP

1111	Thread	Thread
FRS-14-18	1/4"	1/8"
FRS-38-14	3/8"	1/4"
FRS-38-18	3/8"	1/8"
FRS-12-38	1/2"	3/8"
FRS-12-14	1/2"	1/4"
FRS-12-18	1/2"	1/8"
FRS-34-14	3/4"	1/4"
FRS-34-12	3/4"	1/2"
FRS-34-38	3/4"	3/8"
FRS-1-34	1"	3/4"
FRS-1-14	1"	1/4"
FRS-1-38	1"	3/8"
FRS-1-12	1"	1/2"
FRS-114-1	1.1/4"	1"
FRS-114-12	1.1/4"	1/2"
FRS-114-34	1.1/4"	3/4"
FRS-112-1	1.1/2"	1"
FRS-112-34	1.1/2"	3/4"
FRS-112-114	1.1/2"	1.1/4"
FRS-2-34	2"	3/4"
FRS-2-1	2"	1"
FRS-2-112	2"	1.1/2"
FRS-2-114	2"	1.1/4"
FRS-212-114	2.1/2"	1.1/4"
FRS-212-2	2.1/2"	2"
FRS-3-114	3"	1.1/4"
FRS-3-2	3"	2"
FRS-3-212	3"	2.1/2"
FRS-4-2	4"	2"
FRS-4-3	4"	3"

Tech Sheet 1802

45º Equal Elbow



Female Thread, BSPP

1111	Thread
OE-18	1/8"
OE-14	1/4"
OE-38	3/8"
OE-12	1/2"
OE-34	3/4"
OE-1	1"
OE-114	1.1/4"
OE-112	1.1/2"
OE-2	2"
OE-212	2.1/2"
OE-3	3"
OE-4	4"

Tech Sheet 1796

45° Equal Bracket Elbow



Female Thread, BSPP

1111	Thread
WEP-12	1/2"

Tech Sheet 1797

90º Equal Elbow



Female Thread, BSPP

1111	Thread
EE-18	1/8"
EE-14	1/4"
EE-38	3/8"
EE-12	1/2"
EE-34	3/4"
EE-1	1"
EE-114	1.1/4"
EE-112	1.1/2"
EE-2	2"
EE-212	2.1/2"
EE-3	3"
EE-4	4"

Tech Sheet 1797

90º Street Elbow



Male Thread, BSPT x Female Thread, BSPP

1111	Male Thread	Female Thread
SE-18	1/8"	1/8"
SE-14	1/4"	1/4"
SE-38	3/8"	3/8"
SE-12	1/2"	1/2"
SE-34	3/4"	3/4"
SE-1	1"	1"
SE-114	1.1/4"	1.1/4"
SE-112	1.1/2"	1.1/2"
SE-2	2"	2"
SE-212	2.1/2"	2.1/2"
SE-3	3"	3"
SE-4	4"	4"

Tech Sheet 1798

Equal Nipple



Male Thread, BSPT

1111	Thread
HN-18	1/8"
HN-14	1/4"
HN-38	3/8"
HN-12	1/2"
HN-34	3/4"
HN-1	1"
HN-114	1.1/4"
HN-112	1.1/2"
HN-2	2"
HN-212	2.1/2"
HN-3	3"
HN-4	4"

Tech Sheet 1804

Male Thread, NPT

1111	Thread
NPT62001010	1/8"
NPT62001313	1/4"
NPT62001717	3/8"
NPT62002121	1/2"
NPT62002727	3/4"
NPT62003232	1"
NPT62004242	1.1/4"
NPT62004848	1.1/2"
NPT62006060	2"
NPT62007676	2.1/2"
NPT62008989	3"
NPT62000114	4"

Tech Sheet 1804

ABS DNV·GL Lloyd's Register RoHS

150lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

HAITIMA

Hexagon Blanking Cap



Female Thread, BSPP

1111	Thread
HBC-18	1/8"
HBC-14	1/4"
HBC-38	3/8"
HBC-12	1/2"
HBC-34	3/4"
HBC-1	1"
HBC-114	1.1/4"
HBC-112	1.1/2"
HBC-2	2"
HBC-212	2.1/2"
HBC-3	3"
HBC-4	4"

Tech Sheet 1805

Blanking Plug



Male Thread, BSPT

1111	Thread
HP-18	1/8"
HP-14	1/4"
HP-38	3/8"
HP-12	1/2"
HP-34	3/4"
HP-1	1"
HP-114	1.1/4"
HP-112	1.1/2"
HP-2	2"
HP-212	2.1/2"
HP-3	3"

Tech Sheet 1806

Male Thread, NPT

1111	Thread
NPT62181000	1/8"
NPT62181300	1/4"
NPT62181700	3/8"
NPT62182100	1/2"
NPT62182700	3/4"
NPT62183200	1"
NPT62184200	1.1/4"
NPT62184800	1.1/2"
NPT62186000	2"
NPT62187600	2.1/2"
NPT62188900	3"

Tech Sheet 1808

Female Union



Female Thread, BSPP (2 Piece)

1111	Thread
HU-18	1/8"
HU-14	1/4"
HU-38	3/8"
HU-12	1/2"
HU-34	3/4"
HU-1	1"
HU-114	1.1/4"
HU-112	1.1/2"
HU-2	2"
HU-212	2.1/2"
HU-3	3"
HU-4	4"

Tech Sheet 1807

Male/Female Union



Male Thread, BSPT x Female Thread, BSPP (2 Piece)

1111	Thread
MFU-14	1/4"
MFU-38	3/8"
MFU-12	1/2"
MFU-34	3/4"
MFU-1	1"
MFU-114	1.1/4"
MFU-112	1.1/2"
MFU-2	2"
MFU-4	4"

Tech Sheet 1808

Lock Nut



Female Thread, BSPP

1111	Thread
LN-18	1/8"
LN-14	1/4"
LN-38	3/8"
LN-12	1/2"
LN-34	3/4"
LN-1	1"
LN-114	1.1/4"
LN-112	1.1/2"
LN-2	2"
LN-212	2.1/2"
LN-3	3"
LN-4	4"

Tech Sheet 1809

Reducing Bush



Male Thread, BSPT x Female Thread, BSPP

1111	Male Thread	Female Thread
RB-14-18	1/4"	1/8"
RB-38-14	3/8"	1/4"
RB-38-18	3/8"	1/8"
RB-12-14	1/2"	1/4"
RB-12-18	1/2"	1/8"
RB-12-38	1/2"	3/8"
RB-34-12	3/4"	1/2"
RB-34-14	3/4"	1/4"
RB-34-18	3/4"	1/8"
RB-34-38	3/4"	3/8"
RB-1-12	1"	1/2"
RB-1-14	1"	1/4"
RB-1-34	1"	3/4"
RB-1-38	1"	3/8"
RB-114-1	1.1/4"	1"
RB-114-12	1.1/4"	1/2"
RB-114-34	1.1/4"	3/4"
RB-112-1	1.1/2"	1"
RB-112-12	1.1/2"	1/2"
RB-112-34	1.1/2"	3/4"
RB-112-114	1.1/2"	1.1/4"
RB-2-1	2"	1"
RB-2-34	2"	3/4"
RB-2-112	2"	1.1/2"
RB-2-114	2"	1.1/4"
RB-212-1	2.1/2"	1"
RB-212-2	2.1/2"	2"
RB-212-112	2.1/2"	1.1/2"
RB-212-114	2.1/2"	1.1/4"
RB-3-1	3"	1"
RB-3-112	3"	1.1/2"
RB-3-2	3"	2"
RB-3-212	3"	2.1/2"
RB-4-3	4"	3"

Tech Sheet 1810

Male Thread, NPTF x Female Thread, NPTF

1111	Male Thread	Female Thread
NPT62041310	1/4"	1/8"
NPT62041713	3/8"	1/4"
NPT62042117	1/2"	3/8"
NPT62042721	3/4"	1/2"
NPT62043227	1"	3/4"
NPT62044232	1.1/4"	1"
NPT62044842	1.1/2"	1.1/4"
NPT62046048	2"	1.1/2"
NPT62047660	2.1/2"	2"
NPT62048976	3"	2.1/2"

ABS DNV·GL Lloyd's Register RoHS

Fluid-Air Components Ltd

150lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

HAITIMA

Reducing Nipple



Male Thread, BSPT

1111	Thread	Thread
RHN-14-18	1/4"	1/8"
RHN-12-14	1/2"	1/4"
RHN-12-18	1/2"	1/8"
RHN-12-38	1/2"	3/8"
RHN-38-14	3/8"	1/4"
RHN-38-18	3/8"	1/8"
RHN-34-12	3/4"	1/2"
RHN-34-14	3/4"	1/4"
RHN-34-18	3/4"	1/8"
RHN-34-38	3/4"	3/8"
RHN-1-12	1"	1/2"
RHN-1-14	1"	1/4"
RHN-1-34	1"	3/4"
RHN-1-38	1"	3/8"
RHN-114-1	1.1/4"	1"
RHN-114-12	1.1/4"	1/2"
RHN-114-34	1.1/4"	3/4"
RHN-112-1	1.1/2"	1"
RHN-112-12	1.1/2"	1/2"
RHN-112-34	1.1/2"	3/4"
RHN-112-114	1.1/2"	1.1/4"
RHN-2-1	2"	1"
RHN-2-12	2"	1/2"
RHN-2-34	2"	3/4"
RHN-2-112	2"	1.1/2"
RHN-2-114	2"	1.1/4"
RHN-3-2	3"	2"

Tech Sheet 1811

Welding Nipple




Male Thread, BSPT

1111	Thread	Length mm
WN-18	1/8"	30
WN-14	1/4"	30
WN-38	3/8"	30
WN-12	1/2"	35
WN-34	3/4"	40
WN-1	1"	40
WN-114	1.1/4"	50
WN-112	1.1/2"	50
WN-2	2"	50
WN-212	2.1/2"	60
WN-3	3"	70
WN-4	4"	80

Tech Sheet 1813

Square Head Plug



Male Thread, BSPT

1111	Thread
SP-18	1/8"
SP-14	1/4"
SP-38	3/8"
SP-12	1/2"
SP-34	3/4"
SP-1	1"
SP-114	1.1/4"
SP-112	1.1/2"
SP-2	2"
SP-212	2.1/2"
SP-3	3"

Tech Sheet 1814

Round Blanking Cap



Female Thread, BSPP

1111	Thread
RC-18	1/8"
RC-14	1/4"
RC-38	3/8"
RC-12	1/2"
RC-34	3/4"
RC-1	1"
RC-114	1.1/4"
RC-112	1.1/2"
RC-2	2"
RC-212	2.1/2"
RC-3	3"

Tech Sheet 1812

Threaded Half Socket



Female Thread, BSPP

1111	Thread
HS-18	1/8"
HS-14	1/4"
HS-38	3/8"
HS-12	1/2"
HS-34	3/4"
HS-1	1"
HS-114	1.1/4"
HS-112	1.1/2"
HS-2	2"
HS-212	2.1/2"
HS-3	3"
HS-4	4"

Tech Sheet 1816

Threaded Full Socket



Female Thread, BSPP

1111	Thread
FS-18	1/8"
FS-14	1/4"
FS-38	3/8"
FS-12	1/2"
FS-34	3/4"
FS-1	1"
FS-114	1.1/4"
FS-112	1.1/2"
FS-2	2"
FS-212	2.1/2"
FS-3	3"
FS-4	4"

Tech Sheet 1815

Female Thread, NPT

1111	Thread
NPT62061010	1/8"
NPT62061313	1/4"
NPT62061717	3/8"
NPT62062121	1/2"
NPT62062727	3/4"
NPT62063232	1"
NPT62064242	1.1/4"
NPT62064848	1.1/2"
NPT62066060	2"
NPT62067676	2.1/2"
NPT62068989	3"
NPT62060114	4"

316 Stainless Steel Tube

Seamless schedule 40 ASTM A312/AMSE SA312-A530.
Conforms to NACE standard MR-01-75, Din50049-3.1.B.

N.B. Delivery may take up to 48 hours.



3 Metre Lengths, Random

0214	NB	Wall Thickness mm
2028-5839	1/8"	1.73
2028-5854	1/4"	2.24
2028-5862	3/8"	2.31
2028-5870	1/2"	2.77
2028-5953	3/4"	2.87
2028-5961	1"	3.38
2028-5979	1.1/4"	3.56
2028-5987	1.1/2"	3.68
2028-5995	2"	3.91

Tech Sheet 831

ABS DNV·GL Lloyd's Register RoHS

Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

90° Equal Female Elbow



NPT

0434	Thread
1012-0001	1/4"
1012-0002	3/8"
1012-0003	1/2"
1012-0004	3/4"
1012-0005	1"
1012-0006	1.1/4"
1012-0007	1.1/2"
1012-0008	2"

Tech Sheet 20506

BSPT

0434	Thread
1012-0009	1/4"
1012-0010	3/8"
1012-0011	1/2"
1012-0012	3/4"
1012-0013	1"
1012-0014	1.1/4"
1012-0016	2"

Tech Sheet 20494



Socket Weld

0434	NB
1012-0017	1/4"
1012-0018	3/8"
1012-0019	1/2"
1012-0021	1"
1012-0022	1.1/4"
1012-0023	1.1/2"
1012-0024	2"

Tech Sheet 20521

90° Equal Male/ Female Street Elbow



NPT

0434	Thread
1012-0041	1/4"
1012-0042	3/8"
1012-0043	1/2"
1012-0044	3/4"
1012-0045	1"
1012-0046	1.1/4"
1012-0047	1.1/2"
1012-0048	2"

Tech Sheet 20515

45° Equal Female Elbow



NPT

0434	Thread
1012-0025	1/4"
1012-0027	1/2"
1012-0028	3/4"
1012-0029	1"
1012-0030	1.1/4"
1012-0031	1.1/2"
1012-0032	2"

Tech Sheet 20505

Socket Weld

0434	NB
1012-0033	1/4"
1012-0034	3/8"
1012-0035	1/2"
1012-0036	3/4"
1012-0037	1"
1012-0038	1.1/4"
1012-0039	1.1/2"

Tech Sheet 20520

Equal Tee



NPT

0434	Thread
1012-0049	1/4"
1012-0050	3/8"
1012-0051	1/2"
1012-0052	3/4"
1012-0053	1"
1012-0054	1.1/4"
1012-0055	1.1/2"
1012-0056	2"

Tech Sheet 20516

BSPT

0434	Thread
1012-0057	1/4"
1012-0058	3/8"
1012-0059	1/2"
1012-0060	3/4"
1012-0061	1"
1012-0062	1.1/4"
1012-0063	1.1/2"
1012-0064	2"

Tech Sheet 20495



Socket Weld

0434	NB
1012-0065	1/4"
1012-0066	3/8"
1012-0067	1/2"
1012-0068	3/4"
1012-0069	1"
1012-0070	1.1/4"
1012-0071	1.1/2"
1012-0072	2"

Tech Sheet 20526

Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Equal Cross



NPT

0434	Thread
1012-0073	1/4"
1012-0074	3/8"
1012-0075	1/2"
1012-0076	3/4"
1012-0077	1"
1012-0078	1.1/4"
1012-0079	1.1/2"
1012-0080	2"
Tech Sheet 20504	



Socket Weld

0434	NB
1012-0082	3/8"
1012-0083	1/2"
1012-0084	3/4"
1012-0085	1"
1012-0086	1.1/4"
1012-0087	1.1/2"
1012-0088	2"
Tech Sheet 20519	

Male / Female Union



NPT

0434	Thread
1012-0089	1/4"
1012-0090	3/8"
1012-0091	1/2"
1012-0092	3/4"
1012-0093	1"
1012-0094	1.1/4"
1012-0095	1.1/2"
1012-0096	2"
Tech Sheet 20518	

Female Union



NPT

0434	Thread
1012-0097	1/4"
1012-0098	3/8"
1012-0099	1/2"
1012-0100	3/4"
1012-0101	1"
1012-0102	1.1/4"
1012-0103	1.1/2"
1012-0104	2"
Tech Sheet 20517	

BSPT

0434	Thread
1012-0106	3/8"
1012-0107	1/2"
1012-0108	3/4"
1012-0109	1"
1012-0110	1.1/4"
1012-0111	1.1/2"
1012-0112	2"
Tech Sheet 20500	



Socket Weld

0434	NB
1012-0113	1/4"
1012-0114	3/8"
1012-0115	1/2"
1012-0116	3/4"
1012-0117	1"
1012-0118	1.1/4"
1012-0119	1.1/2"
1012-0120	2"
Tech Sheet 20527	

Male Hex Nipple



NPT

0434	Thread
1012-0121	1/4"
1012-0122	3/8"
1012-0123	1/2"
1012-0124	3/4"
1012-0125	1"
1012-0126	1.1/4"
1012-0127	1.1/2"
1012-0128	2"
Tech Sheet 20509	

BSPT

0434	Thread
1012-0129	1/4"
1012-0130	3/8"
1012-0131	1/2"
1012-0132	3/4"
1012-0133	1"
1012-0134	1.1/4"
1012-0135	1.1/2"
1012-0136	2"
Tech Sheet 20498	

Male Barrel Nipple



NPT

0434	Thread	Length mm
1012-0137	1/4"	30
1012-0138	3/8"	40
1012-0139	1/2"	60
1012-0140	3/4"	60
1012-0141	1"	60
1012-0142	1.1/4"	80
1012-0143	1.1/2"	80
1012-0144	2"	100
Tech Sheet 20503		

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Male Hex Reducing Nipple



BSPT

0434	Thread	Thread
1012-0166	1/4"	1/8"
1012-0167	3/8"	1/8"
1012-0168	1/2"	1/4"
1012-0169	1/2"	3/8"
1012-0170	3/4"	3/8"
1012-0171	3/4"	1/2"
1012-0172	1"	1/2"
1012-0173	1"	3/4"
1012-0174	1.1/4"	3/4"
1012-0175	1.1/4"	1"
1012-0176	1.1/2"	1"
1012-0177	1.1/2"	1.1/4"
1012-0178	2"	1"
1012-0179	2"	1.1/4"
1012-0180	2"	1.1/2"
Tech Sheet 20499		

NPT

0434	Thread	Thread
1012-0145	1/4"	1/8"
1012-0146	3/8"	1/8"
1012-0147	3/8"	1/4"
1012-0148	1/2"	1/8"
1012-0149	1/2"	1/4"
1012-0150	1/2"	3/8"
1012-0151	3/4"	1/4"
1012-0152	3/4"	3/8"
1012-0153	3/4"	1/2"
1012-0154	1"	3/8"
1012-0155	1"	1/2"
1012-0156	1"	3/4"
1012-0157	1.1/4"	1/2"
1012-0158	1.1/4"	3/4"
1012-0159	1.1/4"	1"
1012-0160	1.1/2"	3/4"
1012-0161	1.1/2"	1"
1012-0162	1.1/2"	1.1/4"
1012-0163	2"	1"
1012-0164	2"	1.1/4"
1012-0165	2"	1.1/2"
Tech Sheet 20513		

Full Coupling



NPT

0434	Thread
1012-0181	1/4"
1012-0182	3/8"
1012-0183	1/2"
1012-0184	3/4"
1012-0185	1"
1012-0186	1.1/4"
1012-0187	1.1/2"
1012-0188	2"
Tech Sheet 20507	

BSPT

0434	Thread
1012-0189	1/4"
1012-0190	3/8"
1012-0191	1/2"
1012-0192	3/4"
1012-0193	1"
1012-0194	1.1/4"
1012-0195	1.1/2"
1012-0196	2"
Tech Sheet 20496	



Socket Weld

0434	NB
1012-0197	1/4"
1012-0198	3/8"
1012-0199	1/2"
1012-0200	3/4"
1012-0201	1"
1012-0202	1.1/4"
1012-0203	1.1/2"
1012-0204	2"
Tech Sheet 20522	

Half Coupling



NPT

0434	Thread
1012-0205	1/4"
1012-0206	3/8"
1012-0208	3/4"
1012-0209	1"
1012-0210	1.1/4"
1012-0211	1.1/2"
1012-0212	2"
Tech Sheet 20508	

BSPT

0434	Thread
1012-0213	1/4"
1012-0214	3/8"
1012-0215	1/2"
1012-0216	3/4"
1012-0217	1"
1012-0218	1.1/4"
1012-0219	1.1/2"
1012-0220	2"
Tech Sheet 20497	



Socket Weld

0434	NB
1012-0221	1/4"
1012-0222	3/8"
1012-0223	1/2"
1012-0224	3/4"
1012-0225	1"
1012-0226	1.1/4"
1012-0228	2"
Tech Sheet 20523	

FAC Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Reducing Coupling



NPT

0434	Thread	Thread
1012-0229	1/4"	1/8"
1012-0231	1/2"	1/4"
1012-0232	1/2"	3/8"
1012-0233	3/4"	3/8"
1012-0234	3/4"	1/2"
1012-0235	1"	1/2"
1012-0236	1"	3/4"
1012-0237	1.1/4"	3/4"
1012-0238	1.1/4"	1"
1012-0239	1.1/2"	1"
1012-0240	1.1/2"	1.1/4"
1012-0241	2"	1"
1012-0242	2"	1.1/4"
1012-0243	2"	1.1/2"
Tech Sheet 20512		



Socket Weld

0434	NB	NB
1012-0244	1/4"	1/8"
1012-0245	3/8"	1/4"
1012-0246	1/2"	1/4"
1012-0247	1/2"	3/8"
1012-0248	3/4"	3/8"
1012-0249	3/4"	1/2"
1012-0250	1"	1/2"
1012-0252	1.1/4"	1"
1012-0253	1.1/2"	1"
1012-0254	1.1/2"	1.1/4"
1012-0255	2"	1"
1012-0256	2"	1.1/4"
1012-0257	2"	1.1/2"
Tech Sheet 20524		

Reducing Bush



NPT

0434	Thread	Thread
1012-0258	1/4"	1/8"
1012-0259	3/8"	1/8"
1012-0260	3/8"	1/4"
1012-0261	1/2"	1/8"
1012-0262	1/2"	1/4"
1012-0263	1/2"	3/8"
1012-0264	3/4"	1/4"
1012-0265	3/4"	3/8"
1012-0266	3/4"	1/2"
1012-0267	1"	1/4"
1012-0268	1"	3/8"
1012-0269	1"	1/2"
1012-0270	1"	3/4"
1012-0271	1.1/4"	1/2"
1012-0272	1.1/4"	3/4"
1012-0273	1.1/4"	1"
1012-0274	1.1/2"	3/4"
1012-0275	1.1/2"	1"
1012-0276	1.1/2"	1.1/4"
1012-0277	2"	1"
1012-0278	2"	1.1/4"
1012-0279	2"	1.1/2"
Tech Sheet 20511		

BSPT

0434	Thread	Thread
1012-0280	1/4"	1/8"
1012-0281	3/8"	1/8"
1012-0282	3/8"	1/4"
1012-0283	1/2"	1/8"
1012-0284	1/2"	1/4"
1012-0285	1/2"	3/8"
1012-0286	3/4"	1/4"
1012-0287	3/4"	3/8"
1012-0288	3/4"	1/2"
1012-0289	1"	1/4"
1012-0290	1"	3/8"
1012-0291	1"	1/2"
1012-0292	1"	3/4"
1012-0293	1.1/4"	1/2"
1012-0294	1.1/4"	3/4"
1012-0295	1.1/4"	1"
1012-0296	1.1/2"	3/4"
1012-0297	1.1/2"	1"
1012-0298	1.1/2"	1.1/4"
1012-0299	2"	1"
1012-0300	2"	1.1/4"
1012-0301	2"	1.1/2"
Tech Sheet 20502		

Hex Head Plug



NPT

0434	Thread
1012-0302	1/4"
1012-0303	3/8"
1012-0304	1/2"
1012-0305	3/4"
1012-0306	1"
1012-0307	1.1/4"
1012-0308	1.1/2"
1012-0309	2"
Tech Sheet 20510	

BSPT

0434	Thread
1012-0310	1/4"
1012-0311	3/8"
1012-0312	1/2"
1012-0313	3/4"
1012-0314	1"
1012-0315	1.1/4"
1012-0316	1.1/2"
1012-0317	2"
Tech Sheet 20501	

Round Cap



NPT

0434	Thread
1012-0318	1/4"
1012-0319	3/8"
1012-0320	1/2"
1012-0321	3/4"
1012-0322	1"
1012-0323	1.1/4"
1012-0324	1.1/2"
1012-0325	2"
Tech Sheet 20514	



Socket Weld

0434	NB
1012-0326	1/4"
1012-0327	3/8"
1012-0328	1/2"
1012-0329	3/4"
1012-0330	1"
1012-0331	1.1/4"
1012-0332	1.1/2"
1012-0333	2"
Tech Sheet 20525	

TUBING

stainless steel

316 Stainless Steel Tube

3 metre lengths next day.
6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.

For full details please contact our Business Development Team.
Minimum of 10 lengths is advised up to 8mm to prevent damage in transit.



Seamless ASTM A269, Metric, 6 Metre Lengths

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610-6M	6	1	428
765-6X1.5-6M	6	1.5	627
765-0810-6M	8	1	321
765-8X1.5-6M	8	1.5	472
765-1013-6M	10	1	257
765-10X1.5-6M	10	1.5	385
765-12X1.5-6M	12	1.5	321
765-1515-6M	15	1.5	257
765-16X1.5-6M	16	1.5	235
765-1602-6M	16	2	321
765-20X2-6M	20	2	257
765-25X2.5-6M	25	2.5	210
765-30X3-6M	30	3	257
Tech Sheet 831			

PANAM



You might also need...
Stainless Steel Fittings
see pages **166-178**

Seamless ASTM A269, Metric, 3 Metre Lengths, Random

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610	6	1	428
765-6X1.5	6	1.5	627
765-6X2	6	2	942
765-0813	8	1	321
765-8X1.5	8	1.5	472
765-8X2	8	2	706
765-1013	10	1	257
765-10X1.5	10	1.5	385
765-10X2	10	2	564
765-1213	12	1	210
765-12X1.5	12	1.5	321
765-12X2	12	2	420
765-1513	15	1	200
765-15X1.5	15	1.5	257
765-15X2	15	2	376
765-16X1.5	16	1.5	235
765-16X2	16	2	321
765-18X1.5	18	1.5	235
765-18X2	18	2	314
765-20X1.5	20	1.5	212
765-20X2	20	2	257
765-20X3	20	3	424
765-22X1.5	22	1.5	193
765-22X2	22	2	256
765-25X1.5	25	1.5	169
765-25X2	25	2	226
765-25X2.5	25	2.5	210
765-25X3	25	3	339
765-28X2	28	2	201
765-30X3	30	3	257
765-35X3	35	3	242
765-42X3	42	3	201
Tech Sheet 831			

Seamless ASTM A269, Imperial, 3 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372	1/8"	20	718
2020-1380	1/4"	20	360
2020-1406	3/8"	20	240
2020-1414	1/2"	20	180
2020-1422	3/4"	20	120
2020-1430	1"	20	90
Tech Sheet 831			

Seamless ASTM A269, Imperial, 6 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372-6M	1/8"	20	750
2020-1380-6M	1/4"	20	360
2020-1406-6M	3/8"	20	240
2020-1414-6M	1/2"	20	180
2020-1422-6M	3/4"	20	120
2020-1430-6M	1"	20	90
Tech Sheet 831			

Fluid-Air Components Ltd

BS TYPE, 316L HYGIENIC PIPE FITTINGS

stainless steel FT PRO

Elbows



90° Bends, Long

0706	OD
BSL2S-316-1	1"
BSL2S-316-1.5	1.1/2"
BSL2S-316-2	2"
BSL2S-316-2.5	2.1/2"
BSL2S-316-3	3"
BSL2S-316-4	4"
Tech Sheet 68082	



90° Bends, Short

0706	OD
BS2WCL-316-1	1"
BS2WCL-316-1.5	1.1/2"
BS2WCL-316-2	2"
BS2WCL-316-2.5	2.1/2"
BS2WCL-316-3	3"
BS2WCL-316-4	4"
Tech Sheet 68082	



45° Bends, Long

0706	OD
BSL2KS-316-1	1"
BSL2KS-316-1.5	1.1/2"
BSL2KS-316-2	2"
BSL2KS-316-2.5	2.1/2"
BSL2KS-316-3	3"
BSL2KS-316-4	4"
Tech Sheet 68082	

Tees



Short Tees

0706	OD
BS7WWW-316-34	3/4"
BS7WWW-316-1	1"
BS7WWW-316-1.5	1.1/2"
BS7WWW-316-2	2"
BS7WWW-316-2.5	2.1/2"
BS7WWW-316-3	3"
Tech Sheet 68082	



Pulled Tees

0706	OD
BS7WWO-316-1	1"
BS7WWO-316-1.5	1.1/2"
BS7WWO-316-2	2"
BS7WWO-316-2.5	2.1/2"
BS7WWO-316-3	3"
BS7WWO-316-4	4"
Tech Sheet 68082	

Reducers



Concentric Reducing Cones

0706	OD A	OD B
BSL31-316-1X0.5	1"	1/2"
BSL31-316-1.5X1	1.1/2"	1"
BSL31-316-2X1	2"	1"
BSL31-316-2X1.5	2"	1.1/2"
BSL31-316-2.5X1	2.1/2"	1"
BSL31-316-2.5X15	2.1/2"	1.1/2"
BSL31-316-2.5X2	2.1/2"	2"
BSL31-316-3X2	3"	2"
BSL31-316-3X2.5	3"	2.1/2"
BSL31-316-4X1.5	4"	1.1/2"
BSL31-316-4X2	4"	2"
BSL31-316-4X2.5	4"	2.1/2"
BSL31-316-4X3	4"	3"
Tech Sheet 68082		



Eccentric Reducing Cones

0706	OD A	OD B
BSL32-316075X0.5	3/4"	1/2"
BSL32-316-2X1	2"	1"
BSL32-316-2X1.5	2"	1.1/2"
BSL32-316-2.5X2	2.1/2"	2"
BSL32-316-3X2	3"	2"
BSL32-316-3X2.5	3"	2.1/2"
BSL32-316-4X1.5	4"	1.1/2"
BSL32-316-4X2	4"	2"
BSL32-316-4X3	4"	3"
Tech Sheet 68082		

Fluid-Air Components Ltd

BS TYPE, 316L HYGIENIC PIPE FITTINGS

stainless steel

FT PRO

IDF Weld Fittings



Hex Nut

0706	Size
BSIDF-13H-1	1"
BSIDF-13H-1.5	1.1/2"
BSIDF-13H-2	2"
BSIDF-13H-2.5	2.1/2"
BSIDF-13H-3	3"
Tech Sheet 68081	



Welding Male

0706	Size
BSIDF-15-1	1"
BSIDF-15-1.5	1.1/2"
BSIDF-15-2	2"
BSIDF-15-2.5	2.1/2"
BSIDF-15-3	3"
BSIDF-15-4	4"
Tech Sheet 68081	



Welding Liner

0706	Size
BSIDF-14-1	1"
BSIDF-14-1.5	1.1/2"
BSIDF-14-2	2"
BSIDF-14-2.5	2.1/2"
BSIDF-14-3	3"
BSIDF-14-4	4"
Tech Sheet 68081	



EPDM Seal

0706	Size
BSIDF-SEAL-1	1"
BSIDF-SEAL-1.5	1.1/2"
BSIDF-SEAL-2	2"
BSIDF-SEAL-2.5	2.1/2"
BSIDF-SEAL-3	3"
BSIDF-SEAL-4	4"
Tech Sheet 68081	

RJT Weld Fittings



Hex Nut

0706	Size
BSRJT-13H-1	1"
BSRJT-13H-1.5	1.1/2"
BSRJT-13H-2	2"
BSRJT-13H-2.5	2.1/2"
BSRJT-13H-3	3"
BSRJT-13H-4	4"
Tech Sheet 68081	



Welding Male

0706	Size
BSRJT-15-1	1"
BSRJT-15-1.5	1.1/2"
BSRJT-15-2	2"
BSRJT-15-2.5	2.1/2"
BSRJT-15-3	3"
BSRJT-15-4	4"
Tech Sheet 68081	



Welding Liner

0706	Size
BSRJT-14-1	1"
BSRJT-14-1.5	1.1/2"
BSRJT-14-2	2"
BSRJT-14-2.5	2.1/2"
BSRJT-14-3	3"
BSRJT-14-4	4"
Tech Sheet 68081	



Blanking Nut

0706	Size
BSRJT-13HBN-1	1"
BSRJT-13HBN-1.5	1.1/2"
BSRJT-13HBN-2	2"
BSRJT-13HBN-2.5	2.1/2"
BSRJT-13HBN-3	3"
BSRJT-13HBN-4	4"
Tech Sheet 68081	



EPDM Seal

0706	Size
BSRJT-SEAL-1	1"
BSRJT-SEAL-1.5	1.1/2"
BSRJT-SEAL-2	2"
BSRJT-SEAL-2.5	2.1/2"
BSRJT-SEAL-3	3"
BSRJT-SEAL-4	4"
Tech Sheet 68081	

RJT Fittings

Most process lines have to be frequently dismantled for cleaning and all ranges of our hygienic fittings are suitable for this purpose.

Clamp unions provide a crevice free connection with a rapid break down and assembly, with no tools required.

RJT unions are probably the most widely used for frequent break down and cleaning.

IDF unions provide an alternative security and limit unauthorised access.

Sizes to suit OD tube.



RJT Spanner

0147	Size
RJT-SPANNER-1.0	1"
RJT-SPANNER-1.5	1.1/2"
RJT-SPANNER-2	2"
RJT-SPANNER-2.5	2.1/2"
RJT-SPANNER-3	3"
RJT-SPANNER-4	4"
Tech Sheet 68081	

Hygienic Tube

N.B. Delivery may take up to 48 hours.



3 Metre Lengths

0214	Size
ODT316L-W-H-1.0	1"
ODT316L-W-H-1.5	1.1/2"
ODT316L-W-H-2	2"
ODT316L-W-H-2.5	2.1/2"
ODT316L-W-H-3	3"
ODT316L-W-H-4	4"
Tech Sheet 68081	

Fluid-Air Components Ltd

HYGIENIC CLAMP FITTINGS

stainless steel

FT PRO

Clamp Fittings



Weld Ferrule

0707	Clamp Size
14MMP-0.5	1/2″
14MMP-0.75	3/4″
14MMP-1	1″
14MMP-1.5	1.1/2″
14MMP-2	2″
14MMP-2.5	2.1/2″
14MMP-3	3″
14MMP-4	4″
Tech Sheet 68084	



Heavy-duty Single Pin Clamp

0707	Clamp Size
13MHH-2.5	2.1/2″
13MHH-0.5	1/2″ - 3/4″
13MHH-1	1″ - 1.1/2″
13MHH-2	2″
13MHH-3	3″
13MHH-4	4″
Tech Sheet 68084	



Heavy-duty Double Pin Clamp

0707	Clamp Size
13MHHM-1	1″ - 1.1/2″
13MHHM-2	2″
13MHHM-2.5	2.1/2″
13MHHM-3	3″
13MHHM-4	4″
Tech Sheet 68084	



End Cap

0707	Clamp Size
16AMP-0.5	1/2″ - 3/4″
16AMP-1	1″ - 1.1/2″
16AMP-2	2″
16AMP-2.5	2.1/2″
16AMP-3	3″
16AMP-4	4″
Tech Sheet 68084	



Clamp Joint Seal, EPDM

0707	Clamp Size
HFE03-050	1/2″
HFE03-075	3/4″
HFE03-1	1″
HFE03-1.5	1.1/2″
HFE03-2	2″
HFE03-2.5	2.1/2″
HFE03-3	3″
HFE03-4	4″
Tech Sheet 68084	

FT PRO

stainless steel

You might also need...
Hygienic Stainless Steel Butterfly Valves
see page **967**



Fluid-Air Components Ltd

RJT COUPLINGS

stainless steel

FT PRO

Weld Liner



Stainless Steel

0354	Size
RJTWL1	1"
RJTWL112	1.1/2"
RJTWL2	2"
RJTWL212	2.1/2"
RJTWL3	3"

Tech Sheet 60554

Hose Liner



Stainless Steel

0354	Size
RJTHL1	1"
RJTHL112	1.1/2"
RJTHL2	2"
RJTHL212	2.1/2"
RJTHL3	3"

Tech Sheet 60554

BSPP Adaptor



Stainless Steel

0354	Size	Thread
RJTA1	1"	1"
RJTA112	1.1/2"	1.1/2"
RJTD2	2"	2"
RJTA3	3"	3"

Tech Sheet 60554

Reducing Weld Liner



Stainless Steel

0354	Size
RJTRWL2112	2" to 1.1/2"

Tech Sheet 60554

Hex Nut



Stainless Steel

0354	Size
RJTN1	1"
RJTN112	1.1/2"
RJTN2	2"
RJTN3	3"

Tech Sheet 60554

Seal



0354	Size
RJTS1	1"
RJTS112	1.1/2"
RJTS2	2"
RJTS3	3"

Tech Sheet 60554

Blank Liner



Stainless Steel

0354	Size
RJTBL1	1"
RJTBL112	1.1/2"
RJTBL2	2"
RJTBL212	2.1/2"
RJTBL3	3"

Tech Sheet 60554

Weld Male



Stainless Steel

0354	Size
RJTWM1	1"
RJTWM112	1.1/2"
RJTWM2	2"
RJTWM3	3"

Tech Sheet 60554

Fluid-Air Components Ltd

STAINLESS STEEL FLANGES

stainless steel FTPRO

Slip-on PN16/3



BS4504: Sect 3.1:1989

1113	Size
SSFSB-12	1/2"
SSFSB-34	3/4"
SSFSB-1	1"
SSFSB-114	1.1/4"
SSFSB-112	1.1/2"
SSFSB-2	2"
SSFSB-3	3"
Tech Sheet 1500	

Slip-on 150lb



ANSI B16.5

1113	Size
SSFSA-12	1/2"
SSFSA-1	1"
SSFSA-112	1.1/2"
SSFSA-2	2"
Tech Sheet 1500	

Table D




1113	Size
TABLE-D-112	1.1/2"
TABLE-D-4	4"
Tech Sheet 1500	

Table E



1113	Size
TABLE-E-1	1"
TABLE-E-112	1.1/2"
TABLE-E-2	2"
TABLE-E-3	3"
Tech Sheet 1500	

Blind PN16/8



BS4504: Sect 3.1:1989

1113	Size
SSFBB-12	1/2"
SSFBSB-34	3/4"
SSFBSB-1	1"
SSFBSB-114	1.1/4"
SSFBSB-112	1.1/2"
SSFBB-2	2"
SSFBB-3	3"
Tech Sheet 1500	

Blind 150lb



BS4504: Sect 3.1:1989

1113	Size
SSFBA-12	1/2"
SSFBA-34	3/4"
SSFBA-1	1"
SSFBA-2	2"
SSFBA-3	3"
Tech Sheet 1500	

Weld Neck 150lb



ANSI B16.5

1113	Size
SSFWA-34	3/4"
SSFWA-2	2"
SSFWA-3	3"
Tech Sheet 1500	

Customers who bought from this page also purchased...

FTPRO

Flange Gaskets



...see page **1389**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

FT PRO®


LEAK FREE

Compression Fittings


- To be used in conjunction with Nylon, Polyurethane & Metallic tube
- Superior to a Push-in Fitting where there are extremes of Temperature & Pressure

Brand	Fitting Variations	Nut Type	Tube Range	Thread Type	Finish
FT Pro	32	Internal	4-28mm	1/8" - 3/4"	Brass
FT Pro	34	Internal	1/8" - 3/4"	1/8" - 3/4"	Brass
Norgren Enots	26	Internal	4-12mm	1/8" - 3/4"	Brass
Norgren Enots	13	Internal	3/16" - 3/4"	1/8" - 1/2"	Brass
FT Pro	36	External	1/8" - 3/4"	1/8" - 3/4"	Brass
Aignep	18	External	4-22mm	1/8" - 3/4"	Brass
Aignep	12	External	4-18mm	1/8" - 1/2"	Nickel Plated Brass
Metal Work	11	External	4-15mm	1/8" - 1/2"	Nickel Plated Brass

Internal Nut



External Nut



1196

BRASS COMPRESSION FITTINGS, METRIC

Tubing Nuts



Tubing Nut, Metric

1315	Tube OD mm	Equivalent
TNM04	4	36050002
TNM05	5	36050003
TNM06	6	36050004
TNM08	8	36050005
TNM10	10	36050006
TNM12	12	36050007
TNM15	15	36050015
TNM16	16	36050008
TNM22	22	36050010
TNM28	28	-

Tubing Sleeves



Tubing Sleeve, Metric

1315	Tube OD mm	Equivalent
OMB04	4	36050202
OMB05	5	36050203
OMB06	6	36050204
OMB08	8	36050205
OMB10	10	3650206
OMB12	12	36050207
OMB15	15	36050215
OMB16	16	36050208



Universal Tubing Sleeve, Metric

1315	Tube OD mm	Equivalent
OM04	4	36050102
OM06	6	36050104
OM08	8	36050105
OM10	10	36050106
OM12	12	36050107
OM15	15	36050115
OM16	16	36050108
OM18	18	36050118
OM22	22	36050110
OM28	28	-

Tubing Plugs



Tubing Plug, Metric

1315	Tube OD mm	Equivalent
CMP04	4	36050902
CMP05	5	36050903
CMP06	6	36050904
CMP08	8	36050905
CMP10	10	36050906
CMP12	12	36050907
CMP22	22	36050910

Male Adaptors



Straight Male Adaptor, Metric, BSPT

1315	Tube OD mm	Thread	Equivalent
CM04/02	4	1/8"	36053002
CM04/04	4	1/4"	36053008
CM05/02	5	1/8"	36053003
CM05/04	5	1/4"	36053009
CM06/02	6	1/8"	36053004
CM06/04	6	1/4"	36053010
CM06/06	6	3/8"	36053018
CM08/02	8	1/8"	36053005
CM08/04	8	1/4"	36053011
CM08/06	8	3/8"	36053019
CM08/08	8	1/2"	36053028
CM10/02	10	1/8"	36053006
CM10/04	10	1/4"	36053012
CM10/06	10	3/8"	36053020
CM10/08	10	1/2"	36053029
CM12/04	12	1/4"	36053013
CM12/06	12	3/8"	36053021
CM12/08	12	1/2"	36053030
CM12/12	12	3/4"	36053044
CM15/08	15	1/2"	36053057
CM16/06	16	3/8"	36053022
CM16/08	16	1/2"	36053031
CM16/12	16	3/4"	36053045
CM22/08	22	1/2"	-
CM22/12	22	3/4"	-



Straight Male Adaptor, Metric, BSPP

1315	Tube OD mm	Thread	Equivalent
CMP04/02	4	1/8"	36050402
CMP04/04	4	1/4"	36050408
CMP05/02	5	1/8"	36050403
CMP05/04	5	1/4"	36050409
CMP06/02	6	1/8"	36050404
CMP06/04	6	1/4"	36050410
CMP08/02	8	1/8"	36050405
CMP08/04	8	1/4"	36050411
CMP08/06	8	3/8"	36050419
CMP08/08	8	1/2"	36050428
CMP10/04	10	1/4"	36050412
CMP10/06	10	3/8"	36050420
CMP10/08	10	1/2"	36050429
CMP12/06	12	3/8"	36050421
CMP12/08	12	1/2"	36050430
CMP16/08	16	1/2"	36050431

Female Adaptors



Straight Female Adaptor, Metric, BSPP

1315	Tube OD mm	Thread	Equivalent
CMF04/02	4	1/8"	36050502
CMF05/02	5	1/8"	36050503
CMF05/04	5	1/4"	36050509
CMF06/02	6	1/8"	36050504
CMF06/04	6	1/4"	36050510
CMF08/02	8	1/8"	36050505
CMF08/04	8	1/4"	36050511
CMF08/06	8	3/8"	36050519
CMF10/04	10	1/4"	36050512
CMF10/06	10	3/8"	36050520
CMF12/06	12	3/8"	36050521
CMF12/08	12	1/2"	36050530
CMF16/08	16	1/2"	36050531

Nipple Adaptors



Nipple Adaptor Tube Male, BSPT x Male, Metric

1315	Tube OD mm	Thread	Equivalent
CMA05/02	5	1/8"	36055603
CMA06/02	6	1/8"	36055604
CMA06/04	6	1/4"	36055610
CMA08/04	8	1/4"	36055611
CMA08/06	8	3/8"	36055619
CMA12/08	12	1/2"	36055630



Nipple Adaptor Tube Male, BSP x Female, Metric

1315	Tube OD mm	Female Thread	Equivalent
CMNF04/02	4	1/8"	36055702
CMNF05/02	5	1/8"	36055703
CMNF06/02	6	1/8"	36055704
CMNF06/04	6	1/4"	36055710
CMNF08/04	8	1/4"	36055711
CMNF10/04	10	1/4"	36055712
CMNF12/06	12	3/8"	36055721
CMNF12/08	12	1/2"	36055730

BRASS COMPRESSION FITTINGS, METRIC

Nipple Connectors



Nipple Connector, Metric

1315	Tube OD mm	Equivalent
CMNC05	5	36063203
CMNC06	6	36063204
CMNC08	8	36063205

Reducing Connectors



Reducing Connector, Metric

1315	Tube OD mm Male	Tube OD mm Female	Equivalent
CMMFB05/04	5	4	36051726
CMMFB08/06	8	6	36051747
CMMFB10/06	10	6	36051748
CMMFB10/08	10	8	36051756
CMMFB12/06	12	6	36051749
CMMFB12/08	12	8	36051757
CMMFB12/10	12	10	36051764
CMMFB16/08	16	8	36051758
CMMFB16/12	16	12	36051771

Straight Connectors



Straight Connector, Metric

1315	Tube OD mm	Equivalent
CMS04	4	36050302
CMS05	5	36050303
CMS06	6	36050304
CMS08	8	36050305
CMS10	10	36050306
CMS12	12	36050307
CMS16	16	36050308
CMS22	22	36050310

Bulkhead Connectors



Bulkhead Connector, Metric

1315	Tube OD mm	Male Thread	Equivalent
CMBH04	4	M12 x 1	36050802
CMBH05	5	M15 x 1	36050803
CMBH06	6	M15 x 1	36050804
CMBH08	8	M18 x 1.5	36050805
CMBH10	10	M20 x 1.5	36050806
CMBH12	12	M24 x 1.5	36050807
CMBH16	16	M30 x 1.5	36050808

Locknuts



Locknut NP, Metric

1315	Thread
LNM15NP	M15 x 1.0
LNM20NP	M20 x 1.5
LNM24NP	M24 x 1.5
LNM26NP	M26 x 1.5
LNM28NP	M28 x 1.5

Elbows



Male Elbow Adaptor, Metric, BSPT

1315	Tube OD mm	Male Thread	Equivalent
CMLM04/02	4	1/8"	36000502
CMLM04/04	4	1/4"	36000508
CMLM05/02	5	1/8"	36000503
CMLM05/04	5	1/4"	36000509
CMLM06/02	6	1/8"	36000504
CMLM06/04	6	1/4"	36000510
CMLM06/06	6	3/8"	36000518
CMLM08/02	8	1/8"	36000505
CMLM08/04	8	1/4"	36000511
CMLM08/06	8	3/8"	36000519
CMLM08/08	8	1/2"	36000528
CMLM10/04	10	1/4"	36000512
CMLM10/06	10	3/8"	36000520
CMLM12/06	12	3/8"	36000521
CMLM12/08	12	1/2"	36000530
CMLM16/08	16	1/2"	36000531
CMLM16/12	16	3/4"	36000545



Female Elbow Adaptor, Metric, BSPP

1315	Tube OD mm	Male Thread	Equivalent
CMLF06/04	6	1/4"	36055510
CMLF08/04	8	1/4"	36055511
CMLF10/04	10	1/4"	36055512
CMLF10/06	10	3/8"	36055520



Bracketed Elbow, Metric

1315	Tube OD mm	Equivalent
CMBL10	10	36054806



Elbow Connector, Metric

1315	Tube OD mm	Equivalent
CML04	4	36051102
CML05	5	36051103
CML06	6	36051104
CML08	8	36051105
CML10	10	36051106
CML12	12	36051107
CML16	16	36051108

Fluid-Air Components Ltd

BRASS COMPRESSION FITTINGS, METRIC

Elbow Connectors



Stem Elbow Connector, Metric

1315	Tube OD mm	Stem OD mm	Equivalent
CMLS06	6	6	36055104
CMLS08	8	8	36055105
CMLS10	10	10	36055106
CMLS12	12	12	36055107
CMLS16	16	16	36055108

Tees



Male Tee Adaptor, Metric, BSPT

1315	Tube OD mm	Male Thread	Equivalent
CMTM04/02	4	1/8"	36062702
CMTM06/02	6	1/8"	36062704
CMTM08/04	8	1/4"	36062711
CMTM10/04	10	1/4"	36062712



Tee Connector, Metric

1315	Tube OD mm	Equivalent
CMT04	4	36051402
CMT05	5	36051403
CMT06	6	36051404
CMT08	8	36051405
CMT10	10	36051406
CMT12	12	36051407
CMT16	16	36051408



Male Tee Adaptor, Metric, BSPT

1315	Tube OD mm	Male Thread	Equivalent
CMTR06/02	6	1/8"	36062804



Bracketed Tee, Metric

1315	Tube OD mm	Equivalent
CMBT06	6	36054904
CMBT08	8	36054905
CMBT10	10	36054906

Tee Connectors



Stem Tee Connector, Metric

1315	Tube OD mm	Stem OD mm	Equivalent
CMTS08	8	8	36055005
CMTS10	10	10	36055006
CMTS12	12	12	36055007
CMTS16	16	16	36055008



Stem Run Tee Connector, Metric

1315	Tube OD mm	Stem OD mm	Equivalent
CMTRS06	6	6	36062604
CMTRS10	10	10	36062606
CMTRS12	12	12	36062607

Crosses



Four Way Connector, Metric

1315	Tube OD mm	Equivalent
CMX06	6	36051604

Stem Adaptors



Nippled Stem Connector, Metric

1315	Tube OD mm	Stem OD mm	Equivalent
CMSPN12/12	12	12	36062507



Stem (Stand Pipe) x Hosetail Adaptor, Metric

1315	Standpipe mm	Hosetail	Equivalent
CMSPH04/03	4	3/16"	36052415
CMSPH06/04	6	1/4"	36052424
CMSPH08/04	8	1/4"	36052425
CMSPH12/06	12	3/8"	36052443



Straight Stem Adaptor, Metric

1315	Thread	Standpipe mm	Equivalent
CMSP02/08	1/8"	8	36053105
CMSP04/06	1/4"	6	36053110
CMSP04/08	1/4"	8	36053111
CMSP06/10	3/8"	10	36053120
CMSP06/12	3/8"	12	36053121
CMSP08/12	1/2"	12	-

Manifolds



Single Side 4 Output Manifold, Metric

1315	Inlet Tube OD mm	Outlet Tube OD mm	No. of Outlets	Equivalent
CMMB12/08	12	8	4	36030457
CMMB16/10	16	10	4	36030465

Fluid-Air Components Ltd

BRASS COMPRESSION FITTINGS, IMPERIAL

Tubing Nuts



Tubing Nut, Imperial

1315	Tube OD	Equivalent
TNI02	1/8"	34027902
TNI03	3/16"	34027903
TNI04	1/4"	34027904
TNI05	5/16"	34027905
TNI06	3/8"	34027906
TNI08	1/2"	34027907
TNI10	5/8"	34027908
TNI12	3/4"	34027909

Tubing Sleeves



Tubing Sleeve, Imperial

1315	Tube OD	Equivalent
OIB02	1/8"	34000302
OIB03	3/16"	34000303
OIB04	1/4"	34000304
OIB05	5/16"	34000305
OIB06	3/8"	34000306
OIB08	1/2"	34000307



Universal Tubing Sleeve, Imperial

1315	Tube OD	Equivalent
OI02	1/8"	34027802
OI04	1/4"	34027804
OI05	5/16"	34027805
OI06	3/8"	34027806
OI08	1/2"	34027807
OI10	5/8"	34027808
OI12	3/4"	34027809

Tubing Plugs



Tubing Plug, Imperial

1315	Tube OD	Equivalent
CIP04	1/4"	34003604
CIP05	5/16"	34003605
CIP06	3/8"	34003606
CIP08	1/2"	34003607

Male Adaptors



Straight Male Adaptor, Imperial, BSPT

1315	Tube OD	Thread	Equivalent
CI02/02	1/8"	1/8"	34034607
CI03/02	3/16"	1/8"	34034608
CI03/04	3/16"	1/4"	34034615
CI04/02	1/4"	1/8"	34034609
CI04/04	1/4"	1/4"	34034616
CI05/02	5/16"	1/8"	34034610
CI05/04	5/16"	1/4"	34034617
CI05/06	5/16"	3/8"	34034625
CI05/08	5/16"	1/2"	34034634
CI06/02	3/8"	1/8"	34034611
CI06/04	3/8"	1/4"	34034618
CI06/06	3/8"	3/8"	34034626
CI06/08	3/8"	1/2"	34034635
CI08/04	1/2"	1/4"	34034619
CI08/06	1/2"	3/8"	34034627
CI08/08	1/2"	1/2"	34034636
CI08/12	1/2"	3/4"	34034653
CI10/08	5/8"	1/2"	34034637
CI12/08	3/4"	1/2"	34034638
CI12/12	3/4"	3/4"	34034655



Straight Male Adaptor, Imperial, BSPP

1315	Tube OD	Thread	Equivalent
CIP03/02	3/16"	1/8"	34034808
CIP04/02	1/4"	1/8"	34034809
CIP04/04	1/4"	1/4"	34034816
CIP06/06	3/8"	3/8"	34034826
CIP08/06	1/2"	3/8"	34034827

Female Adaptors



Straight Female Adaptor, Imperial, BSPP

1315	Tube OD	Thread	Equivalent
CIF03/02	3/16"	1/8"	34034408
CIF03/04	3/16"	1/4"	34034415
CIF04/02	1/4"	1/8"	34034409
CIF04/04	1/4"	1/4"	34034416
CIF05/04	5/16"	1/4"	34034417
CIF06/04	3/8"	1/4"	34034418
CIF06/06	3/8"	3/8"	34034426
CIF08/08	1/2"	1/2"	34034436
CIF10/08	5/8"	1/2"	34034437

Nipple Adaptors



Nipple Adaptor Tube Male, BSPT x Male, Imperial

1315	Tube OD	Thread	Equivalent
CIA04/02	1/4"	1/8"	34035009
CIA05/04	5/16"	1/4"	34035017
CIA06/04	3/8"	1/4"	34035018
CIA06/06	3/8"	3/8"	34035026
CIA08/08	1/2"	1/2"	34035036



Nipple Adaptor Tube Male, BSP x Female, Imperial

1315	Tube OD	Female Thread	Equivalent
CINF03/02	3/16"	1/8"	34035108
CINF05/04	5/16"	1/4"	34035117
CINF06/06	3/8"	3/8"	34035126
CINF08/06	1/2"	3/8"	34035127
CINF08/08	1/2"	1/2"	34035136

Fluid-Air Components Ltd

BRASS COMPRESSION FITTINGS, IMPERIAL

Reducing Connectors



Reducing Connector, Imperial

1315	Tube OD Male	Tube OD Female	Equivalent
CIMFB04/03	1/4"	3/16"	34035231
CIMFB05/04	5/16"	1/4"	34035239
CIMFB06/04	3/8"	1/4"	34035240
CIMFB06/05	3/8"	5/16"	34035246
CIMFB08/05	1/2"	5/16"	34035247
CIMFB08/06	1/2"	3/8"	34035252

Nipple Connectors



Nipple Connector, Imperial

1315	Tube OD	Equivalent
CINC08	1/2"	34029107

Straight Connectors



Straight Connector, Imperial

1315	Tube OD	Equivalent
CIS03	3/16"	34000703
CIS04	1/4"	34000704
CIS05	5/16"	34000705
CIS06	3/8"	34000706
CIS08	1/2"	34000707
CIS12	3/4"	34000709

Bulkhead Connectors



Bulkhead Connector, Imperial

1315	Tube OD	Male Thread	Equivalent
CIBH03	3/16"	1/4"	34002103
CIBH04	1/4"	3/8"	34002104
CIBH05	5/16"	3/8"	34002105
CIBH06	3/8"	1/2"	34002106
CIBH08	1/2"	3/4"	34002107

Locknuts



Locknut, BSPP

1315	Thread	Equivalent
LN12	3/4"	34022306
LN16	1"	34022308



Locknut NP, BSPP

1315	Thread
LN02NP	1/8"
LN04NP	1/4"
LN06NP	3/8"
LN08NP	1/2"
LN12NP	3/4"
LN16NP	1"

Elbow Connectors



Stem Elbow Connector, Imperial

1315	Tube OD	Stem OD	Equivalent
CILS03	3/16"	3/16"	34005703
CILS04	1/4"	1/4"	34005704
CILS05	5/16"	5/16"	34005705
CILS06	3/8"	3/8"	34005706
CILS08	1/2"	1/2"	34005707



Universal Stem Elbow, Imperial

1315	Stem OD	Equivalent
CIUSL05	5/16"	34029205
CIUSL06	3/8"	34029206

Elbows



Female Elbow Adaptor, Imperial, BSPP

1315	Tube OD	Male Thread	Equivalent
CILF06/06	3/8"	3/8"	34032826
CILF08/06	1/2"	3/8"	34032827
CILF08/08	1/2"	1/2"	34032836



Elbow Connector, Imperial

1315	Tube OD	Equivalent
CIL04	1/4"	34006004
CIL05	5/16"	34006005
CIL06	3/8"	34006006
CIL08	1/2"	34006007



Male Elbow Adaptor, Imperial, BSPT

1315	Tube OD	Male Thread	Equivalent
CILM03/02	3/16"	1/8"	34033008
CILM03/04	3/16"	1/4"	34033015
CILM04/02	1/4"	1/8"	34033009
CILM04/04	1/4"	1/4"	34033016
CILM05/02	5/16"	1/8"	34033010
CILM05/04	5/16"	1/4"	34033017
CILM05/06	5/16"	3/8"	34033025
CILM06/04	3/8"	1/4"	34033018
CILM06/06	3/8"	3/8"	34033026

BRASS COMPRESSION FITTINGS, IMPERIAL

Tees



Male Tee Adaptor, Imperial, BSPT

1315	Tube OD	Male Thread	Equivalent
CITM04/02	1/4"	1/8"	34033409
CITM06/04	3/8"	1/4"	34033418



Tee Connector, Imperial

1315	Tube OD	Equivalent
CIT03	3/16"	34029003
CIT04	1/4"	34029004
CIT05	5/16"	34029005
CIT06	3/8"	34029006
CIT08	1/2"	34029007
CIT12	3/4"	34029009



Male Tee Adaptor, Imperial, BSPT

1315	Tube OD	Male Thread	Equivalent
CITR06/04	3/8"	1/4"	34033618



Bracketed Tee, Imperial

1315	Tube OD	Equivalent
CIBT03	3/16"	34029303

Tee Connectors




Stem Tee Connector, Imperial

1315	Tube OD	Stem OD	Equivalent
CITS04	1/4"	1/4"	34033904
CITS06	3/8"	3/8"	34033906



Stem Run Tee Connector, Imperial

1315	Tube OD	Stem OD	Equivalent
CITRS04	1/4"	1/4"	34034104



Universal Stem Tee, Imperial

1315	Stem OD	Equivalent
CIUST04	1/4"	34034204
CIUST06	3/8"	34034206

Y Connectors



Y Connector, Imperial

1315	Tube OD	Equivalent
CIY06	3/8"	34012706
CIY08	1/2"	34012707

Crosses



Four Way Connector, Imperial

1315	Tube OD	Equivalent
CIX06	3/8"	34013106

Stem Adaptors



Nippled Stem Connector, Imperial

1315	Tube OD	Stem OD	Equivalent
CISPN03/03	3/16"	3/16"	34001303
CISPN04/04	1/4"	1/4"	34001304
CISPN05/05	5/16"	5/16"	34001305
CISPN06/06	3/8"	3/8"	34001306



Stem (Stand Pipe) x Hosetail Adaptor, Imperial

1315	Standpipe	Hosetail	Equivalent
CISPH03/03	3/16"	3/16"	34005603
CISPH04/04	1/4"	1/4"	34005604
CISPH05/05	5/16"	5/16"	34005605
CISPH06/06	3/8"	3/8"	34005606
CISPH08/08	1/2"	1/2"	34005607



Straight Stem Adaptor, Imperial, BSPT

1315	Thread	Standpipe	Equivalent
CISP04/04	1/4"	1/4"	-
CISP04/05	1/4"	5/16"	34034317

Manifolds



Single Side 4 Output Manifold, Imperial

1315	Inlet Tube OD	Outlet Tube OD	No. of Outlets	Equivalent
CIMB08/04	1/2"	1/4"	4	34030441

Fluid-Air Components Ltd

ENOTS COMPRESSION FITTINGS, METRIC

- Wide range of types and sizes
- Suitable for use under extreme conditions of temperature and pressure
- Rugged and durable
- Ideal for most general industrial applications

Tubing Nut, Sleeve and Body Manufactured from Bar:
Brass to BS 2874: 1986 (CZ 121)
Body Manufactured from Stamping:
Brass to BS 2872: 1969 (CZ 122)
Banjo bolts have a bright nickel plated finis

Tube Types:
Nylon 11 or 12 and other plasticised or unplasticised tubing which conforms to the tolerances specified in **BS5409:** Part 1 1976. Copper, annealed and half-hard to BS2871: Part 2. Double wall brazed steel.

Stem Adaptors



Tailpiece

0038	Stem OD mm	To Suit Hose ID mm
36052424	6	6.3
36052425	8	6.3
36052442	10	10



Nippled

0038	Stem OD mm	OD mm
36062507	12	12



Straight, BSPP

0038	Stem OD mm	Thread
36052105	8	1/8"
36052111	8	1/4"



Straight, BSPT

0038	Stem OD mm	Thread
36053104	6	1/8"
36053110	6	1/4"
36053111	8	1/4"
36053112	10	1/4"

Tubing Plugs



Tube

0038	OD mm
36050902	4
36050905	8
36050906	10
36050907	12

Bulkhead Locknuts



Metric

0038	Thread
36052001	M12 x 1.0
36052003	M15 x 1.0
36052005	M18 x 1.5
36052006	M20 x 1.5
36052007	M24 x 1.5

Bulkhead Connectors



Metric

0038	OD mm	Thread
36050804	6	M15 x 1.0
36050805	8	M18 x 1.5
36050806	10	M20 x 1.5
36050807	12	M24 x 1.5

Reducing Connectors



Tube x Tube

0038	OD A mm	OD B mm
36051727	4	6
36051728	4	8
36051747	6	8
36051749	6	12
36051757	8	12

Fast Rotating Joints



BSPT

0038	Thread
04016100	1/4"

Straight Connectors



Equal

0038	OD mm
36050302	4
36050304	6
36050305	8
36050306	10
36050307	12



Bracketed

0038	OD mm
36055205	8

Nippled Adaptors



BSPT

0038	OD mm	Thread
36055605	8	1/8"
36055611	8	1/4"



BSPP

0038	OD mm	Thread
36055711	8	1/4"
36055712	10	1/4"
36055721	12	3/8"

ENOTS COMPRESSION FITTINGS, METRIC

NORGREN

Straight Adaptors



Male, BSPT

0038	OD mm	Thread
36053002	4	1/8"
36053008	4	1/4"
36053004	6	1/8"
36053010	6	1/4"
36053005	8	1/8"
36053011	8	1/4"
36053019	8	3/8"
36053028	8	1/2"
36053006	10	1/8"
36053012	10	1/4"
36053020	10	3/8"
36053029	10	1/2"
36053013	12	1/4"
36053030	12	1/2"
36053044	12	3/4"



Male, BSPP

0038	OD mm	Thread
36050402	4	1/8"
36050404	6	1/8"
36050405	8	1/8"
36050411	8	1/4"
36050428	8	1/2"
36050412	10	1/4"
36050420	10	3/8"
36050429	10	1/2"
36050413	12	1/4"
36050421	12	3/8"
36050430	12	1/2"



Female, BSPP

0038	OD mm	Thread
36050502	4	1/8"
36050510	6	1/4"
36050511	8	1/4"
36050512	10	1/4"
36050521	12	3/8"
36050530	12	1/2"

Elbow Connectors



Equal

0038	OD mm
36051104	6
36051107	12



Stem

0038	OD mm	Stem OD mm
36055104	6	6
36055105	8	8
36055106	10	10
36055107	12	12



Bracketed

0038	OD mm
36054804	6
36054805	8

Tee Connectors



Equal

0038	OD mm
36051404	6
36051405	8
36051406	10
36051407	12



Bracketed

0038	OD mm
36054905	8

Tubing Nuts



Tube

0038	OD mm
36050002	4
36050003	5
36050004	6
36050005	8
36050006	10
36050007	12
36050008	16

Elbow Adaptors



Female, BSPP

0038	OD mm	Thread
36055502	4	1/8"
36055510	6	1/4"
36055512	10	1/4"
36055520	10	3/8"



Male, BSPT

0038	OD mm	Thread
36000502	4	1/8"
36000508	4	1/4"
36000504	6	1/8"
36000510	6	1/4"
36000505	8	1/8"
36000511	8	1/4"
36000512	10	1/4"
36000520	10	3/8"
36000529	10	1/2"
36000513	12	1/4"
36000521	12	3/8"
36000530	12	1/2"

Universal Tubing Sleeves



To suit Metal & Nylon Tube

0038	OD mm
36050102	4
36050103	5
36050105	8
36050106	10
36050107	12
36050108	16

Elbow Banjo Assemblies



Non-regulating, BSPP

0038	OD mm	Thread
18A511028	10	1/4"
18A511048	10	1/2"
18A511238	12	3/8"

Fluid-Air Components Ltd

ENOTS COMPRESSION FITTINGS, IMPERIAL


NORGREN

- Wide range of types and sizes
- Rugged and durable
- Suitable for use under extreme conditions of temperature and pressure
- Ideal for most general industrial applications

Tubing Nut, Sleeve and Body Manufactured from Bar:
Brass to BS 2874: 1986 (CZ 121)
Body Manufactured from Stamping:
Brass to BS 2872: 1969 (CZ 122)
Banjo bolts have a bright nickel plated finis

Tube Types:
Nylon 11 or 12 and other plasticised or unplasticised tubing which conforms to the tolerances specified in **BS5409:** Part 1 1976. Copper, annealed and half-hard to BS2871: Part 2. Double wall brazed steel.

Stem Adaptors



Tailpiece

0038	Stem OD	To Suit Hose ID
34005607	1/2"	1/2"

Tubing Plugs



Tube

0038	OD
34003604	1/4"

Bulkhead Locknuts



BSPP

0038	Thread
34022302	1/4"
34022303	3/8"

Bulkhead Connectors



BSPP

0038	OD	Thread
34002104	1/4"	3/8"

Straight Connectors



Equal

0038	OD
34000704	1/4"
34000705	5/16"
34000706	3/8"
34000707	1/2"

Straight Adaptors



Male, BSPT

0038	OD	Thread
34034610	5/16"	1/8"
34034616	1/4"	1/4"
34034617	5/16"	1/4"
34034618	3/8"	1/4"
34034626	3/8"	3/8"
34034635	3/8"	1/2"
34034619	1/2"	1/4"
34034636	1/2"	1/2"



Male, BSPP

0038	OD	Thread
34034809	1/4"	1/8"



Female, BSPP

0038	OD	Thread
34034416	1/4"	1/4"

Elbow Connectors



Stem

0038	OD	Stem OD
34005704	1/4"	1/4"
34005706	3/8"	3/8"
34005707	1/2"	1/2"

Elbow Adaptors



Male, BSPT

0038	OD	Thread
34033009	1/4"	1/8"
34033016	1/4"	1/4"
34033018	3/8"	1/4"
34033026	3/8"	3/8"
34033019	1/2"	1/4"
34033027	1/2"	3/8"

Tubing Nuts



Tube

0038	OD
34027903	3/16"
34027904	1/4"
34027905	5/16"
34027906	3/8"
34027907	1/2"
34027909	3/4"

Tubing Sleeves



To suit Metal Tube Only

0038	OD
34000303	3/16"
34000304	1/4"



Universal, To suit Metal & Nylon Tube

0038	OD
34027803	3/16"
34027804	1/4"
34027805	5/16"
34027806	3/8"

IMPERIAL BRASS COMPRESSION FITTINGS

Please note: Safe pressures and temperatures depend entirely on the tubes being used, for this reason the values must be determined in accordance with the tube features.

Media: Water, oils, compressed air

Use universal barrel olive for copper and nylon tube.

Male Studs



BSPT

0062	OD	Thread
APMS-14-18	1/4"	1/8"
APMS-14-14	1/4"	1/4"
APMS-14-38	1/4"	3/8"
APMS-14-12	1/4"	1/2"
APMS-516-18	5/16"	1/8"
APMS-516-14	5/16"	1/4"
APMS-516-38	5/16"	3/8"
APMS-516-12	5/16"	1/2"
APMS-38-18	3/8"	1/8"
APMS-38-14	3/8"	1/4"
APMS-38-38	3/8"	3/8"
APMS-38-12	3/8"	1/2"
APMS-12-14	1/2"	1/4"
APMS-12-38	1/2"	3/8"
APMS-12-12	1/2"	1/2"

Tech Sheet 20193

Male Stud Elbows



BSPT

0062	OD	Thread
APSE-14-18	1/4"	1/8"
APSE-14-14	1/4"	1/4"
APSE-14-38	1/4"	3/8"
APSE-14-12	1/4"	1/2"
APSE-516-18	5/16"	1/8"
APSE-516-14	5/16"	1/4"
APSE-516-38	5/16"	3/8"
APSE-38-18	3/8"	1/8"
APSE-38-14	3/8"	1/4"
APSE-38-38	3/8"	3/8"
APSE-38-12	3/8"	1/2"
APSE-12-14	1/2"	1/4"
APSE-12-38	1/2"	3/8"
APSE-12-12	1/2"	1/2"

Tech Sheet 20194

Female Studs



BSPP

0062	OD	Thread
APFS-14-18	1/4"	1/8"
APFS-14-14	1/4"	1/4"
APFS-14-38	1/4"	3/8"
APFS-14-12	1/4"	1/2"
APFS-516-14	5/16"	1/4"
APFS-516-38	5/16"	3/8"
APFS-516-12	5/16"	1/2"
APFS-38-14	3/8"	1/4"
APFS-38-38	3/8"	3/8"
APFS-38-12	3/8"	1/2"
APFS-12-14	1/2"	1/4"
APFS-12-38	1/2"	3/8"
APFS-12-12	1/2"	1/2"

Tech Sheet 20192

Brass Barrel Olives



0062	OD
APBO-14	1/4"
APBO-516	5/16"
APBO-38	3/8"
APBO-12	1/2"

Female Stud Elbows



BSPP

0062	OD	Thread
APFE-14-14	1/4"	1/4"
APFE-516-14	5/16"	1/4"
APFE-38-38	3/8"	3/8"

Tech Sheet 20191

Brass Nuts



0062	OD
APBN-14	1/4"
APBN-38	3/8"
APBN-12	1/2"

Tech Sheet 20189

Tees, Male Stud Branch



BSPT

0062	OD	Thread
APST-14-18	1/4"	1/8"
APST-14-14	1/4"	1/4"
APST-516-14	5/16"	1/4"
APST-38-14	3/8"	1/4"
APST-12-14	1/2"	1/4"

Tech Sheet 20195

Equal Connectors



Tube x Tube

0062	OD
APEC-14	1/4"
APEC-516	5/16"
APEC-38	3/8"
APEC-12	1/2"

Tech Sheet 20187

Equal Tees



Tube x Tube

0062	OD
APET-14	1/4"
APET-516	5/16"
APET-38	3/8"
APET-12	1/2"

Tech Sheet 20190

Equal Elbows



Tube x Tube

0062	OD
APEE-14	1/4"
APEE-516	5/16"
APEE-38	3/8"
APEE-12	1/2"

Tech Sheet 20188

Fluid-Air Components Ltd

IMPERIAL BRASS COMPRESSION FITTINGS


Please note: Safe pressures and temperatures depend entirely on the tubes being used, for this reason the values must be determined in accordance with the tube features.
Media: Water, oils, compressed air

Male Studs



BSPT

1300	OD	Thread
MST18-18	1/8"	1/8"
MST18-14	1/8"	1/4"
MST316-18	3/16"	1/8"
MST316-14	3/16"	1/4"
MST14-18	1/4"	1/8"
MST14-14	1/4"	1/4"
MST14-38	1/4"	3/8"
MST14-12	1/4"	1/2"
MST516-18	5/16"	1/8"
MST516-14	5/16"	1/4"
MST516-38	5/16"	3/8"
MST38-18	3/8"	1/8"
MST38-14	3/8"	1/4"
MST38-38	3/8"	3/8"
MST38-12	3/8"	1/2"
MST12-14	1/2"	1/4"
MST12-38	1/2"	3/8"
MST12-12	1/2"	1/2"
MST34-12	3/4"	1/2"
MST34-34	3/4"	3/4"



BSPP

1300	OD	Thread
MSP18-18	1/8"	1/8"
MSP18-14	1/8"	1/4"
MSP316-18	3/16"	1/8"
MSP316-14	3/16"	1/4"
MSP316-38	3/16"	3/8"
MSP14-18	1/4"	1/8"
MSP14-14	1/4"	1/4"
MSP14-38	1/4"	3/8"
MSP516-18	5/16"	1/8"
MSP516-14	5/16"	1/4"
MSP516-38	5/16"	3/8"
MSP516-12	5/16"	1/2"
MSP38-18	3/8"	1/8"
MSP38-14	3/8"	1/4"
MSP38-38	3/8"	3/8"
MSP38-12	3/8"	1/2"
MSP12-38	1/2"	3/8"
MSP12-12	1/2"	1/2"
MSP12-34	1/2"	3/4"
MSP34-12	3/4"	1/2"
MSP34-34	3/4"	3/4"
MSP1-1	1"	1"

Female Studs



BSPP

1300	OD	Thread
FSC18-18	1/8"	1/8"
FSC18-14	1/8"	1/4"
FSC316-18	3/16"	1/8"
FSC316-14	3/16"	1/4"
FSC316-38	3/16"	3/8"
FSC14-18	1/4"	1/8"
FSC14-14	1/4"	1/4"
FSC14-38	1/4"	3/8"
FSC14-12	1/4"	1/2"
FSC516-18	5/16"	1/8"
FSC516-14	5/16"	1/4"
FSC516-38	5/16"	3/8"
FSC516-12	5/16"	1/2"
FSC38-18	3/8"	1/8"
FSC38-14	3/8"	1/4"
FSC38-38	3/8"	3/8"
FSC38-12	3/8"	1/2"
FSC12-14	1/2"	1/4"
FSC12-12	1/2"	1/2"
FSC34-12	3/4"	1/2"
FSC34-34	3/4"	3/4"
FSC1-1	1"	1"

Equal Ended



Tube x Tube

1300	Thread
EEC18	1/8"
EEC316	3/16"
EEC14	1/4"
EEC516	5/16"
EEC38	3/8"
EEC12	1/2"
EEC34	3/4"
EEC1	1"

Imperial to Metric Couplings



Tube x Tube

1300	OD	ODmm
IMC38-10	3/8"	10

Equal Ended Bulkheads



Tube x Tube

1300	OD	Thread
EB18	1/8"	1/8"
EB316	3/16"	1/8"
EB14	1/4"	1/4"
EB14/2	1/4"	3/8"
EB516	5/16"	1/8"
EB38	3/8"	3/8"
EB12	1/2"	1/2"

Reducing Couplings



Tube x Tube

1300	OD	OD
RDC316-18	3/16"	1/8"
RDC14-18	1/4"	1/8"
RDC14-316	1/4"	3/16"
RDC516-316	5/16"	3/16"
RDC516-14	5/16"	1/4"
RDC38-14	3/8"	1/4"
RDC38-516	3/8"	5/16"
RDC12-14	1/2"	1/4"
RDC12-516	1/2"	5/16"
RDC12-38	1/2"	3/8"

Tees, Male Stud Branch



BSPT

1300	OD	Thread
MSB14-18	1/4"	1/8"
MSB14-14	1/4"	1/4"
MSB38-14	3/8"	1/4"
MSB38-38	3/8"	3/8"
MSB12-12	1/2"	1/2"

Equal Tees



Tube x Tube

1300	OD
TE18	1/8"
TE316	3/16"
TE14	1/4"
TE516	5/16"
TE38	3/8"
TE12	1/2"
TE34	3/4"

IMPERIAL BRASS COMPRESSION FITTINGS

Tees, Male Stud Run



BSPT

1300	OD	Thread
MSR14-18	1/4"	1/8"
MSR14-14	1/4"	1/4"
MSR516-14	5/16"	1/4"
MSR38-38	3/8"	3/8"

Reducing Branch Tees



Tube x Tube

1300	OD	Branch OD
RT14-316	1/4"	3/16"
RT516-14	5/16"	1/4"
RT38-14	3/8"	1/4"
RT38-516	3/8"	5/16"
RT12-14	1/2"	1/4"
RT12-38	1/2"	3/8"

Equal Ended Crosses



Tube x Tube

1300	OD
EX14	1/4"
EX516	5/16"
EX12	1/2"

Flanged Blanking Plugs



BSPP

1300	Thread
FBP18	1/8"
FBP14	1/4"
FBP38	3/8"
FBP12	1/2"
FBP34	3/4"
FBP1	1"

End Stops



Tube

1300	OD
ES316	3/16"
ES14	1/4"
ES516	5/16"
ES38	3/8"
ES12	1/2"
ES34	3/4"

Standpipe Elbows



Tube x Stem

1300	Stem OD	OD
SPE516	5/16"	5/16"
SPE38	3/8"	3/8"
SPE12	1/2"	1/2"

Female Stud Elbows



BSPP

1300	OD	Thread
FSE316-18	3/16"	1/8"
FSE14-18	1/4"	1/8"
FSE14-14	1/4"	1/4"
FSE516-14	5/16"	1/4"
FSE38-14	3/8"	1/4"
FSE38-38	3/8"	3/8"
FSE38-12	3/8"	1/2"
FSE12-12	1/2"	1/2"

Equal Elbows



Tube x Tube

1300	OD
EL18	1/8"
EL316	3/16"
EL14	1/4"
EL516	5/16"
EL38	3/8"
EL12	1/2"
EL34	3/4"

Male Stud Elbows



BSPT

1300	OD	Thread
MSE18-18	1/8"	1/8"
MSE316-18	3/16"	1/8"
MSE316-14	3/16"	1/4"
MSE14-18	1/4"	1/8"
MSE14-14	1/4"	1/4"
MSE14-38	1/4"	3/8"
MSE516-18	5/16"	1/8"
MSE516-14	5/16"	1/4"
MSE38-18	3/8"	1/8"
MSE38-14	3/8"	1/4"
MSE38-38	3/8"	3/8"
MSE12-14	1/2"	1/4"
MSE12-38	1/2"	3/8"
MSE12-12	1/2"	1/2"
MSE34-34	3/4"	3/4"

Brass Compression Rings



1300	OD
CR18	1/8"
CR316	3/16"
CR14	1/4"
CR516	5/16"
CR38	3/8"
CR12	1/2"
CR34	3/4"
CR1	1"

Fulham Nozzles



Female Thread, BSPP

1300	To Suit Hose ID	Thread
FNF18	3/8"	1/8"
FNF14	3/8"	1/4"
FNF38	3/8"	3/8"



Male Thread, BSPT

1300	To Suit Hose ID	Thread
FN18	3/8"	1/8"
FN14	3/8"	1/4"
FN38	3/8"	3/8"



Male Thread, BSPP

1300	To Suit Hose ID	Thread
FNP18	3/8"	1/8"
FNP14	3/8"	1/4"



Tube x Hose Tail

1300	To Suit Hose ID	OD
FNT14	3/8"	1/4"
FNT516	3/8"	5/16"

Compression Nuts



BSPP

1300	OD	Thread
UN18	1/8"	1/8"
UN316	3/16"	1/8"
UN14	1/4"	1/4"
UN516	5/16"	1/4"
UN38	3/8"	3/8"
UN12	1/2"	1/2"
UN34	3/4"	3/4"

Copper Washers for BSPP Stud Ends



To suit BSPP

1300	Male Thread	Female Thread
CW18	1/8"	3/8"
CW14	1/4"	1/2"
CW38	3/8"	3/4"
CW12	1/2"	7/8"
CW34	3/4"	-
CW1	1"	-
CW114	1.1/4"	-
CW112	1.1/2"	-
CW2	2"	-

Tech Sheet 20358

Fluid-Air Components Ltd

METRIC BRASS COMPRESSION FITTINGS

Please note: Safe pressures and temperatures depend entirely on the tubes being used, for this reason the values must be determined in accordance with the tube features.
Media: Water, oils, compressed air

Male Studs



BSPT

1040	OD mm	Thread
13480-4-18	4	1/8"
13480-4-14	4	1/4"
13480-6-18	6	1/8"
13480-6-14	6	1/4"
13480-6-38	6	3/8"
13480-8-18	8	1/8"
13480-8-14	8	1/4"
13480-8-38	8	3/8"
13480-10-14	10	1/4"
13480-10-38	10	3/8"
13480-10-12	10	1/2"
13480-12-14	12	1/4"
13480-12-38	12	3/8"
13480-12-12	12	1/2"
13480-14-12	14	1/2"
13480-15-12	15	1/2"
13480-22-12	22	1/2"
13480-22-34	22	3/4"
Tech Sheet 68743		



BSPP

1040	OD mm	Thread
13485-4-18	4	1/8"
13485-6-18	6	1/8"
13485-6-14	6	1/4"
13485-8-18	8	1/8"
13485-8-14	8	1/4"
13485-8-38	8	3/8"
13485-10-14	10	1/4"
13485-10-38	10	3/8"
13485-22-34	22	3/4"
13485-22-1	22	1"
Tech Sheet 68743		

Standpipe Adaptors



BSPP

1040	OD mm	Thread
13530-6-18	6	1/8"
13530-6-14	6	1/4"
13530-8-14	8	1/4"
13530-8-38	8	3/8"
13530-10-14	10	1/4"
13530-10-38	10	3/8"
Tech Sheet 68743		

Female Studs



BSPP

1040	OD mm	Thread
13500-4-18	4	1/8"
13500-4-14	4	1/4"
13500-6-18	6	1/8"
13500-6-14	6	1/4"
13500-8-18	8	1/8"
13500-8-14	8	1/4"
13500-8-38	8	3/8"
13500-10-14	10	1/4"
13500-10-38	10	3/8"
13500-10-12	10	1/2"
13500-12-14	12	1/4"
13500-12-38	12	3/8"
13500-12-12	12	1/2"
13500-14-12	14	1/2"
13500-15-12	15	1/2"
13500-22-34	22	3/4"
Tech Sheet 68743		

Male Stud Elbows



BSPT

1040	OD mm	Thread
13280-4-18	4	1/8"
13280-6-18	6	1/8"
13280-6-14	6	1/4"
13280-8-18	8	1/8"
13280-8-14	8	1/4"
13280-8-38	8	3/8"
13280-10-14	10	1/4"
13280-10-38	10	3/8"
13280-10-12	10	1/2"
13280-12-14	12	1/4"
13280-12-38	12	3/8"
13280-12-12	12	1/2"
13280-14-12	14	1/2"
13280-15-12	15	1/2"
13280-22-34	22	3/4"
Tech Sheet 68743		

Equal Elbows



Tube x Tube

1040	OD mm
13260-4	4
13260-6	6
13260-8	8
13260-10	10
13260-12	12
13260-15	15
13260-22	22
Tech Sheet 68743	

Bulkhead Connectors



Tube x Tube

1040	OD mm
13465-4	4
13465-6	6
13465-8	8
13465-10	10
13465-12	12
13465-14	14
Tech Sheet 68743	

Straight Connectors



Tube x Tube

1040	OD mm
13460-4	4
13460-6	6
13460-8	8
13460-10	10
13460-12	12
13460-15	15
13460-22	22
Tech Sheet 68743	

Internal Tube Supports

- **This internal tube support, will prevent the tube from crushing caused by over tightening of compression type fittings or clamps**



Tube

1000	To Suit Hose ID mm
877-0027	2.7
877-0004	4
877-0006	6
877-0008	8
877-0009	9
877-0010	10
877-0012	12
877-0125	12.5
877-0013	13
877-0015	15
877-0016	16
877-0018	18

METRIC BRASS COMPRESSION FITTINGS

AIGNEP


Equal Crosses



Tube x Tube

1040	OD mm
13510-6	6
13510-8	8
13510-10	10
13510-12	12
Tech Sheet 68743	

Reducers



Tube

1040	ID mm	OD mm
13600-4-6	4	6
13600-6-8	6	8
13600-8-10	8	10
13600-10-12	10	12
Tech Sheet 68743		

Male Stud Tees



BSPT

1040	OD mm	Thread
13220-4-18	4	1/8"
13220-6-18	6	1/8"
13220-6-14	6	1/4"
13220-8-18	8	1/8"
13220-8-14	8	1/4"
13220-8-38	8	3/8"
13220-10-14	10	1/4"
13220-10-38	10	3/8"
13220-10-12	10	1/2"
13220-12-38	12	3/8"
13220-14-12	14	1/2"
13220-15-12	15	1/2"
13220-22-34	22	3/4"
Tech Sheet 68743		

Equal Tees



Tube x Tube

1040	OD mm
13200-4	4
13200-6	6
13200-8	8
13200-10	10
13200-12	12
13200-14	14
13200-22	22
Tech Sheet 68743	

Hose Tail Stem Adaptors



Stem x Hose Tail

1040	Stem OD mm	To Suit Hose ID mm
13540-6-7	6	7
13540-8-7	8	7
13540-8-10	8	10
13540-10-10	10	10
13540-12-10	12	10
13540-12-13	12	13
Tech Sheet 68743		

Nuts



Tube

1040	OD mm	Thread
13680-4	4	M8 x 1
13680-6	6	M10 x 1
13680-8	8	M12 x 1
13680-10	10	M16 x 1.5
13680-12	12	M18 x 1.5
13680-14	14	M20 x 1.5
13680-15	15	M20 x 1.5
Tech Sheet 68743		

Brass Olives



Tube

1040	OD mm
13740-4	4
13740-6	6
13740-8	8
13740-10	10
13740-12	12
13740-14	14
13740-15	15
13740-22	22
Tech Sheet 68743	

Single Banjo Body with Stem



BSPP

1040	OD mm	Thread
13550-4-18	4	1/8"
13550-6-18	6	1/8"
13550-6-14	6	1/4"
13550-8-18	8	1/8"
13550-8-14	8	1/4"
13550-8-38	8	3/8"
13550-10-14	10	1/4"
13550-10-38	10	3/8"
Tech Sheet 68743		

Blanking Plugs



Tube

1040	OD mm
13780-4	4
13780-6	6
13780-8	8
13780-10	10
13780-12	12
13780-14	14
13780-15	15
13780-22	22
Tech Sheet 68743	

METRIC NICKEL PLATED COMPRESSION FITTINGS

AIGNEP

Please note: Safe pressures and temperatures depend entirely on the tubes being used. For this reason, the values must be determined in accordance with the tube features.
Media: Water, oils and compressed air.

Male Studs



BSPT

1040	OD mm	Thread
2018-5336	4	1/8"
2018-5344	6	1/8"
2018-5351	6	1/4"
2018-5369	8	1/8"
2018-5377	8	1/4"
2018-5385	8	3/8"
2018-5393	10	1/4"
2018-5401	10	3/8"
2018-5419	12	3/8"
2018-5435	12	1/2"
2018-5436	14	1/2"
2018-5914	15	1/2"
2018-5915	16	1/2"
2018-5916	18	1/2"
Tech Sheet 68742		

Female Studs



BSPP

1040	OD mm	Thread
2018-5468	4	1/8"
2018-5476	6	1/8"
2018-5484	6	1/4"
2018-5492	8	1/8"
2018-5500	8	1/4"
2018-5518	8	3/8"
2018-5526	10	1/4"
2018-5534	10	3/8"
2018-5542	12	3/8"
2018-5559	12	1/2"
2018-5567	15	1/2"
Tech Sheet 68742		

Straight Connectors



Tube x Tube

1040	OD mm
2018-5773	4
2018-5880	6
2018-5922	8
2018-5930	10
2018-5948	12
2018-5951	16
Tech Sheet 68742	

Male Stud Elbows



BSPT

1040	OD mm	Thread
2018-5666	4	1/8"
2018-5674	6	1/8"
2018-5682	6	1/4"
2018-5690	8	1/8"
2018-5708	8	1/4"
2018-5716	8	3/8"
2018-5724	10	1/4"
2018-5732	10	3/8"
2018-5740	12	3/8"
2018-5757	12	1/2"
2018-5766	14	1/2"
2018-5765	15	1/2"
2018-5767	16	1/2"
Tech Sheet 68742		

Equal Elbows



Tube x Tube

1040	OD mm
2018-5575	4
2018-5583	6
2018-5591	8
2018-5609	10
2018-5617	12
2018-5626	14
2018-5625	15
Tech Sheet 68742	

Equal Tees



Tube x Tube

1040	OD mm
2018-5971	6
2018-5989	8
2018-5997	10
2018-6003	12
Tech Sheet 68742	

Male Stud Branch Tees



BSPT

1040	OD mm	Thread
2018-6045	6	1/4"
2018-6060	8	1/8"
2018-6094	8	1/4"
2018-6128	10	1/4"
2018-6151	12	3/8"
2018-6169	12	1/2"
2018-6177	15	1/2"
Tech Sheet 68742		

Olives

Brass



1040	OD mm
2018-6243	4
2018-6250	6
2018-6268	8
2018-6276	10
2018-6284	12
2018-6292	15
2018-6296	18
Tech Sheet 68742	

Nuts

BSPP



1040	OD mm	Thread
2018-6185	4	M8 x 1
2018-6193	6	M10 x 1
2018-6201	8	M12 x 1
Tech Sheet 68742		

Brass, Universal



1040	OD mm
2018-3001	4
2018-3002	6
2018-3003	8
2018-3004	10
2018-3005	12
2018-3009	18
Tech Sheet 68742	

PTFE



1040	OD mm
2018-3022	4
2018-3023	6
2018-3024	8
2018-3025	10
2018-3026	12
2018-3029	16
2018-3031	22
Tech Sheet 30104	

Single Banjos



BSPP

1040	OD mm	Thread
2018-3041	6	1/8"
2018-3042	6	1/4"
2018-3044	8	1/4"
Tech Sheet 68742		

METRIC NICKEL PLATED COMPRESSION FITTINGS

Body:
OT 58 brass

Temperature Range:
-45°C to +80°C

Maximum Pressure:
60 bar (dependant upon tubing specification

For use with copper tube

Male Stud



BSP Tapered x Tube, Nickel Plated Brass

9152	Thread	Tube mm	
		OD	ID
2201001	1/8"	4	2
2201002	1/8"	6	4
2201003	1/4"	6	4
2201004	1/8"	8	6
2201005	1/4"	8	6

Male Stud Elbow



BSP Tapered x Tube, Nickel Plated Brass

9152	Thread BSPT	Tube mm	
		OD	ID
2205001	1/8"	4	2
2205002	1/8"	6	4
2205003	1/4"	6	4
2205004	1/8"	8	6
2205005	1/4"	8	6
2205007	1/4"	10	8
2205008	3/8"	10	8
2205009	1/2"	10	8
2205010	3/8"	12	10
2205011	1/2"	12	10
2205012	1/2"	15	12

Female Stud



BSP Parallel x Tube, Nickel Plated Brass

9152	Thread BSPP	Tube mm	
		OD	ID
2202001	1/8"	6	4
2202002	1/4"	6	4
2202004	1/4"	8	6
2202005	3/8"	8	6
2202006	1/4"	10	8
2202007	3/8"	10	8

Equal Elbow



Tube x Tube, Nickel Plated Brass

9152	Tube mm	
	OD	ID
2206001	4	2
2206002	6	4
2206003	8	6
2206004	10	8
2206005	12	10
2206006	15	12

Equal Tee



Tube x Tube, Nickel Plated Brass

9152	Tube mm	
	OD	ID
2209001	4	2
2209002	6	4
2209003	8	6
2209004	10	8
2209005	12	10
2209006	15	12

Male Stud Branch Tee



BSP Tapered x Tube

9152	Thread	Tube mm	
		OD	ID
2207001	1/8"	4	2
2207002	1/8"	6	4
2207003	1/4"	6	4
2207004	1/8"	8	6
2207005	1/4"	8	6
2207006	3/8"	8	6
2207008	3/8"	10	8
2207011	1/2"	12	10

Male Run Tee



BSP Tapered x Tube

9152	Thread	Tube mm	
		OD	ID
2208002	1/4"	6	4
2208003	1/8"	8	6
2208005	3/8"	8	6
2208006	1/4"	10	8
2208007	3/8"	10	8
2208009	3/8"	12	10
2208010	1/2"	12	10
2208011	1/2"	15	12

Straight Connector



Tube x Tube

9152	Tube mm	
	OD	ID
2203001	4	2
2203002	6	4
2203003	8	6
2203004	10	8
2203005	12	10
2203006	15	12

Bulkhead Connector



Tube x Tube

9152	Tube mm	
	OD	ID
2204001	6	4
2204002	8	6
2204003	10	8
2204004	12	10

Spare Compression Olive



Brass

9152	Tube mm	
	OD	ID
2211001	4	2
2211002	6	4
2211003	8	6
2211004	10	8
2211005	12	10

Tube Inserts



Brass

9152	To Suit Tube mm	
	OD	ID
2212001	6	4
2212002	8	6
2212003	10	8
2212004	12	10
2212005	15	12

Fluid-Air Components Ltd

COPPER TUBING

Copper Tubing - Annealed to BS EN12449/C106 (Soft)



Metric, 10 Metre Lengths

5070	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
MCT-4	4	2.8	1,993	137
MCT-5	5	3.4	2,124	146
MCT-6	6	4.4	1,760	121
MCT-8	8	6.4	1,324	91
MCT-10	10	8.4	1,047	72
MCT-12	12	10.4	1,000	69
Tech Sheet 820				

Metric, 30 Metre Lengths

5070	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
MCT-4/30	4	2.8	1,993	137
MCT-6/30	6	4.4	1,760	121
MCT-6-4/30	6	4	2,669	184
MCT-8/30	8	6.4	1,324	91
MCT-10/30	10	8.4	1,047	72
MCT-12/30	12	10.4	1,000	69
MCT-15/30	15	13	1,091	75
Tech Sheet 820				

Imperial, 10 Metre Lengths

5070	OD	ID	SWG	Max Pressure PSI	Max Pressure Bar
ICT-18	1/8"	0.069"	22	3,026	209
ICT-316	3/16"	0.131"	22	1,978	136
ICT-14	1/4"	0.194"	22	1,484	102
ICT-516	5/16"	0.256"	22	1,178	81
ICT-38	3/8"	0.319"	22	974	67
ICT-12	1/2"	0.428"	20	945	65
ICT-58	5/8"	0.553"	20	742	51
Tech Sheet 820					

Imperial, 30 Metre Lengths

5070	OD	ID	SWG	Max Pressure PSI	Max Pressure Bar
ICT-18/30	1/8"	0.069"	22	3,026	209
ICT-316/30	3/16"	0.131"	22	1,978	136
ICT-14/30	1/4"	0.194"	22	1,484	102
ICT-14/30-20SWG	1/4"	0.178"	20	2,244	155
ICT-516/30	5/16"	0.256"	22	1,178	81
ICT-38/30	3/8"	0.319"	22	974	67
ICT-38/30-18SWG	3/8"	0.279"	18	1,958	135
ICT-12/30	1/2"	0.428"	20	945	65
ICT-12/30-18SWG	1/2"	0.404"	18	1,417	98
ICT-58/30	5/8"	0.553"	18	742	51
Tech Sheet 820					

Plumbing Copper Tube



Type: BS EN1057 R250, 3 Metre Lengths

5072	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
PCU15	15	13.6	843	59
PCU22	22	20.2	752	51
PCU28	28	26.2	582	40
PCU35	35	32.6	618	43
PCU42	42	39.6	512	35
PCU54	54	51.6	396	27
PCU67	67	64.6	317	22

Copper Tubing - Half Hard



Metric, 3 Metre Lengths

5070	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
MTS-4	4	2.8	2,604	180
MTS-6	6	4	2,885	199
MTS-8	8	6	2,167	149
MTS-10	10	8	1,731	119
MTS-12	12	10	1,440	99
MTS-15	15	13	1,149	79
MTS-16	16	13.6	1,280	88
MTS-18	18	15.6	1,193	82
MTS-22	22	20	931	64
MTS-28	28	25	902	62

Imperial, 3 Metre Lengths

5070	OD	ID	SWG	Max Pressure PSI	Max Pressure Bar
ITS-18	1/8"	0.069"	22	3,928	271
ITS-316	3/16"	0.131"	22	2,589	179
ITS-14	1/4"	0.178"	20	2,488	172
ITS-516	5/16"	0.241"	20	1,978	136
ITS-38	3/8"	0.303"	20	1,644	113
ITS-12	1/2"	0.428"	20	1,236	85
ITS-12-18SWG	1/2"	0.404"	18	1,848	127
ITS-12-16SWG	1/2"	0.372"	16	2,556	176
ITS-12-10SWG	1/2"	0.244"	10	5,988	413
ITS-58	5/8"	0.529"	18	974	67
ITS-34-18SWG	3/4"	0.654"	18	1,190	82
ITS-34	3/4"	0.622"	16	1,484	102
ITS-78-16SWG	7/8"	0.747"	16	1,374	95
ITS-1-18SWG	1"	0.904"	18	877	60
ITS-1-16SWG	1"	0.872"	16	1,190	82
ITS-118-18SWG	1.1/8"	1.029"	18	776	54
ITS-118-16SWG	1.1/8"	0.997"	16	1,050	72

Please note: Delivery may take up to 48 hours.



BALL VALVES



CHECK & FOOT VALVES



STRAINERS



FITTINGS



BIBCOCKS



PRESSURE REDUCING VALVES




CONVERTIBLE VALVES &
THERMOSTATIC HEAD




MANUAL VALVES &
LOCKSHIELDS



ZONE BALL VALVES



MANIFOLDS IN BRASS &
STAINLESS STEEL



1214

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

COPPER & BUNDY TUBING

Bundy Tube



Metric, 3.2 Metre Lengths

5071	OD mm	Wall Thickness	Burst Pressure PSI
BTM06	6	0.075"	13500
BTM08	8	0.075"	10875
BTM10	10	0.075"	7500

Imperial, 3.2 Metre Lengths

5071	OD	Wall Thickness	Burst Pressure PSI
BTI03	3/16"	0.028"	16500
BTI04	1/4"	0.028"	12000
BTI05	5/16"	0.028"	10875
BTI06	3/8"	0.028"	8200
BTI08	1/2"	0.028"	5000

PVC Covered Copper Tube

Annealed, soft copper tube to BS2871/2/C106 with a black PVC outer cover.

Please note: OD measurement is for copper tube, excluding cover.



Metric, 30 Metre Coils

5070	OD mm	ID mm	Max Pressure PSI	Max Pressure Bar
MSCT-6	6	4	2,053	142
MSCT-8	8	6	1,906	131
MSCT-10	10	8	1,483	102
MSCT-12	12	10	1,091	75

Annealed, soft copper tube to BS2871/2/C106 with a 1/16" black PVC outer cover.

Imperial, 30 Metre Coils

5070	OD	ID	SWG	Max Pressure PSI	Max Pressure Bar
ISCT-14	1/4"	0.194"	22	1,682	116
ISCT-38	3/8"	0.303"	20	1,416	98
ISCT-12	1/2"	0.444"	20	945	65

ACCESSORIES

Polyethylene Pipe Insulation

Thermal Conductivity DIN 52613:
0.035W(m.K) at 0°C.

Working Temperature:
-50°C to +100°C

Fire Rating BS479 Part 5:1979:
Class P (not easily ignitable).

High quality CFC easy-fit closed cell pipe insulation. Particularly effective for the thermal insulation of domestic heating and plumbing pipe work for energy conservation and frost protection. Easy to install, none fibrous and creates no dust during installation and is resistant to oils and greases



9mm Wall Insulation (Semi Split), 2 Metre Lengths

5073	ID mm
POLY15X9	15
POLY22X9	22
POLY28X9	28

13mm Wall Insulation (Semi Split), 2 Metre Lengths

5073	ID mm
POLY15X13	15
POLY22X13	22
POLY28X13	28

19mm Wall Insulation (Split through 1 Wall Thickness), 2 Metre Lengths

5073	ID mm
POLY15X19	15
POLY22X19	22
POLY28X19	28

25mm Wall Insulation (Split through 1 Wall Thickness), 2 Metre Lengths

5073	ID mm
POLY15X25	15
POLY22X25	22
POLY28X25	28



For **Tube Cutters and accessories** see page **905**

BRASS PLUMBING COMPRESSION FITTINGS, METRIC

Couplings



Straight

0242	OD mm
EPS-CFS-6	6
EPS-CFS-8	8
EPS-CFS-10	10
EPS-CFS-12	12
EPS-CFS-15	15
EPS-CFS-22	22
EPS-CFS-28	28
EPS-CFS-35	35
EPS-CFS-42	42
EPS-CFS-54	54



Reducing Straight

0242	OD mm	OD mm
EPS-CFR-10-8	10	8
EPS-CFR-12-10	12	10
EPS-CFR-15-8	15	8
EPS-CFR-15-10	15	10
EPS-CFR-15-12	15	12
EPS-CFR-22-15	22	15
EPS-CFR-28-15	28	15
EPS-CFR-28-22	28	22



BSPT Male x Metric Straight

0242	OD mm	Thread
EPS-CFM-6-14	6	1/4"
EPS-CFM-8-14	8	1/4"
EPS-CFM-8-12	8	1/2"
EPS-CFM-10-14	10	1/4"
EPS-CFM-10-38	10	3/8"
EPS-CFM-12-14	12	1/4"
EPS-CFM-12-38	12	3/8"
EPS-CFM-15-14	15	1/4"
EPS-CFM-15-38	15	3/8"

BSPP Male x Metric Straight

0242	OD mm	Thread
EPS-CFM-8-38	8	3/8"
EPS-CFM-10-12	10	1/2"
EPS-CFM-15-12	15	1/2"
EPS-CFM-15-34	15	3/4"
EPS-CFM-22-12	22	1/2"
EPS-CFM-22-34	22	3/4"
EPS-CFM-22-1	22	1"
EPS-CFM-28-34	28	3/4"
EPS-CFM-28-1	28	1"
EPS-CFM-35-114	35	1.1/4"
EPS-CFM-42-112	42	1.1/2"
EPS-CFM-54-2	54	2"



BSPP Female x Metric Straight

0242	OD mm	Thread
EPS-CFF-6-14	6	1/4"
EPS-CFF-8-14	8	1/4"
EPS-CFF-8-38	8	3/8"
EPS-CFF-10-14	10	1/4"
EPS-CFF-10-38	10	3/8"
EPS-CFF-10-12	10	1/2"
EPS-CFF-15-14	15	1/4"
EPS-CFF-15-38	15	3/8"
EPS-CFF-15-12	15	1/2"
EPS-CFF-15-34	15	3/4"
EPS-CFF-22-12	22	1/2"
EPS-CFF-22-34	22	3/4"
EPS-CFF-22-1	22	1"
EPS-CFF-28-34	28	3/4"
EPS-CFF-28-1	28	1"
EPS-CFF-35-114	35	1.1/4"
EPS-CFF-42-112	42	1.1/2"
EPS-CFF-54-2	54	2"

Elbows



BSPT Male x Metric

0242	OD mm	Thread
EPS-CFME-8-14	8	1/4"
EPS-CFME-8-38	8	3/8"
EPS-CFME-10-14	10	1/4"
EPS-CFME-10-38	10	3/8"
EPS-CFME-10-12	10	1/2"
EPS-CFME-15-14	15	1/4"

BSPP Male x Metric

0242	OD mm	Thread
EPS-CFME-15-12	15	1/2"
EPS-CFME-15-34	15	3/4"
EPS-CFME-22-34	22	3/4"
EPS-CFME-22-1	22	1"
EPS-CFME-28-1	28	1"
EPS-CFME-35-114	35	1.1/4"
EPS-CFME-42-112	42	1.1/2"
EPS-CFME-54-2	54	2"



90°

0242	OD mm
EPS-CFE-6	6
EPS-CFE-8	8
EPS-CFE-10	10
EPS-CFE-12	12
EPS-CFE-15	15
EPS-CFE-22	22
EPS-CFE-28	28
EPS-CFE-35	35
EPS-CFE-42	42
EPS-CFE-54	54



Wall Plate, BSPP

0242	OD mm	Thread
EPS-CFWE-15-12	15	1/2"
EPS-CFWE-22-12	22	1/2"
EPS-CFWE-22-34	22	3/4"



Reducing 90°

0242	OD mm	OD mm
EPS-CFE-22-15	22	15



BSPP Female x Metric

0242	OD mm	Thread
EPS-CFFE-8-14	8	1/4"
EPS-CFFE-10-14	10	1/4"
EPS-CFFE-10-38	10	3/8"
EPS-CFFE-10-12	10	1/2"
EPS-CFFE-15-14	15	1/4"
EPS-CFFE-15-12	15	1/2"
EPS-CFFE-15-34	15	3/4"
EPS-CFFE-22-12	22	1/2"
EPS-CFFE-22-34	22	3/4"
EPS-CFFE-22-1	22	1"
EPS-CFFE-28-1	28	1"
EPS-CFFE-35-114	35	1.1/4"
EPS-CFFE-54-2	54	2"

Fluid-Air Components Ltd

BRASS PLUMBING COMPRESSION FITTINGS, METRIC

Tees



Equal

0242	OD mm
EPS-CFET-6	6
EPS-CFET-8	8
EPS-CFET-10	10
EPS-CFET-12	12
EPS-CFET-15	15
EPS-CFET-22	22
EPS-CFET-28	28
EPS-CFET-35	35
EPS-CFET-42	42
EPS-CFET-54	54



Reducing

0242	OD A mm	OD B mm	OD C mm
CFRT-15-15-22	15	15	22
CFRT-22-22-15	22	22	15
CFRT-22-15-15	22	15	15
CFRT-22-15-22	22	15	22
CFRT-28-28-22	28	28	22
CFRT-35-35-15	35	35	15



Reducing Female

0242	OD mm	Thread
CFFRT-15-15-12	15	1/2"
CFFRT-22-22-12	22	1/2"
CFFRT-22-22-34	22	3/4"

Tank Connectors



Tank Connectors & Washers

0242	OD mm
EPS-CFTC-15	15
EPS-CFTC-22	22
EPS-CFTC-28	28
EPS-CFTC-35	35
EPS-CFTC-42	42
EPS-CFTC-54	54

Tap Connectors



Straight, BSPP

0242	OD mm	Thread
EPS-CFSTC-15-12	15	1/2"
EPS-CFSTC-15-34	15	3/4"
EPS-CFSTC-22-34	22	3/4"



90º, BSPP

0242	OD mm	Thread
EPS-CFBTC-15-12	15	1/2"

Internal Reducing Sets



3 Piece

0242	Reducing From-To mm
EPS-CFR3-10-6	10-6
EPS-CFR3-10-8	10-8
EPS-CFR3-15-8	15-8
EPS-CFR3-15-10	15-10
EPS-CFR3-15-12	15-12
EPS-CFR3-28-15	28-15
EPS-CFR3-28-22	28-22
EPS-CFR3-35-15	35-15
EPS-CFR3-35-22	35-22
EPS-CFR3-42-15	42-15
EPS-CFR3-42-28	42-28
EPS-CFR3-54-28	54-28
EPS-CFR3-54-42	54-42

Olives



Brass

0242	OD mm
EPS-CFBO-8	8
EPS-CFBO-10	10
EPS-CFBO-12	12
EPS-CFBO-15	15
EPS-CFBO-20	20
EPS-CFBO-22	22
EPS-CFBO-25	25
EPS-CFBO-28	28
EPS-CFBO-35	35
EPS-CFBO-42	42
EPS-CFBO-54	54
EPS-CFBO-3/4	3/4"

Copper

0242	OD mm
EPS-CFCO-8	8
EPS-CFCO-10	10
EPS-CFCO-12	12
EPS-CFCO-15	15
EPS-CFCO-20	20
EPS-CFCO-22	22
EPS-CFCO-25	25
EPS-CFCO-28	28
EPS-CFCO-35	35
EPS-CFCO-42	42
EPS-CFCO-54	54
EPS-CFCO-3/4	3/4"

Compression Nuts



0242	OD mm
EPS-CFN-8	8
EPS-CFN-10	10
EPS-CFN-15	15
EPS-CFN-22	22
EPS-CFN-28	28

Stop Ends



0242	OD mm
EPS-CFSE-8	8
EPS-CFSE-10	10
EPS-CFSE-12	12
EPS-CFSE-15	15
EPS-CFSE-22	22
EPS-CFSE-28	28
EPS-CFSE-35	35
EPS-CFSE-42	42
EPS-CFSE-54	54

SOLDER RING

Manufactured from copper and copper alloy. Designed for jointing copper tubes to BS EN 1057 in hot and cold water services, in small bore and mini bore central heating, low pressure steam heating, and in-vented/un-vented closed circuit heating systems.

- WRAS approved
- Manufactured to BS EN 1254 Part 1

Working Temperature:
-40°C to +110°C

Maximum Working Pressure:
16 bar (-40°C to +30°C)
10 bar (+30°C to +65°C)
6 bar (+65°C to +110°C)

Couplings



Straight

0474	OD mm
M-SRSC10	10
M-SRSC-22	22
M-SRSC-28	28
M-SRSC-35	35
M-SRSC-42	42
M-SRSC-54	54
Tech Sheet 60249	



Reducing Coupling

0474	OD mm	OD mm
M-SRRC-10-8	10	8
M-SRRC-15-10	15	10
M-SRRC-22-15	22	15
M-SRRC-28-22	28	22
Tech Sheet 60249		



Reducing Fitting

0474	OD mm	OD mm
M-SRRF-22-15	22	15
M-SRRF-28-15	28	15
M-SRRF-28-22	28	22
M-SRRF-35-22	35	22
M-SRRF-35-28	35	28
M-SRRF-42-15	42	15
M-SRRF-42-28	42	28
M-SRRF-42-35	42	35
M-SRRF-54-22	54	22
M-SRRF-54-35	54	35
M-SRRF-54-42	54	42
Tech Sheet 60249		

Elbows



90° Elbows

0474	OD mm
M-SR90-8	8
M-SR90-10	10
M-SR90-15	15
M-SR90-22	22
M-SR90-28	28
M-SR90-35	35
M-SR90-42	42
M-SR90-54	54
Tech Sheet 60249	



45° Elbows

0474	OD mm
M-SR45EL-15	15
M-SR45EL-22	22
M-SR45EL-35	35
M-SR45EL-45	42
Tech Sheet 60249	



Street Elbows

0474	OD mm
M-SRST90-15	15
M-SRST90-22	22
M-SRST90-28	28
Tech Sheet 60249	

End Caps



End Caps

0474	OD mm
M-SREC-15	15
M-SREC-22	22
Tech Sheet 60249	

Tees



Equal

0474	OD mm
M-SRET-10	10
M-SRET-15	15
M-SRET-22	22
M-SRET-28	28
M-SRET-42	42
Tech Sheet 60249	



Reducing Branch

0474	OD mm	OD mm
M-SRRB-22-15	22	15
M-SRRB-28-15	28	15
M-SRRB-28-22	28	22
M-SRRB-42-15	42	15
M-SRRB-42-22	42	22
M-SRRB-42-28	42	28
M-SRRB-42-35	42	35
M-SRRB-54-15	54	15
M-SRRB-54-22	54	22
M-SRRB-54-28	54	28
M-SRRB-54-35	54	35
M-SRRB-54-42	54	42
Tech Sheet 60249		

Tap Connectors



Straight

0474	OD mm	Thread
M-SRTC-15-12	15	1/2"
M-SRTC-15-34	15	3/4"
M-SRTC-22-34	22	3/4"
Tech Sheet 60249		



Bent

0474	OD mm	Thread
M-SRBTC-15-12	15	1/2"
Tech Sheet 60249		

Fluid-Air Components Ltd

END FEED FITTINGS

Designed for end-feeding with soft solder or hard solder (brazing alloy). Ideal for use in hot and cold water services, central heating, fuel services and general engineering applications.

- WRAS approved
- Manufactured to BS EN 1354 Part 1

Working Temperature:
-40°C to +110°C

Maximum Working Pressure:
Up to 28mm
25 bar (-40°C to +65°C), 16 bar (+110°C)
35mm to 54mm
25 bar (-40°C to +30°C), 16 bar (+65°C)
10 bar (+110°C)

Couplings



Straight

0474	OD mm
M-EFSC-28	28
M-EFSC-35	35
M-EFSC-42	42
M-EFSC-54	54
Tech Sheet 60249	

Tap Connectors



Straight

0474	OD mm	Thread
M-EFTCS-15-12	15	1/2"
M-EFTCS-22-34	22	3/4"
Tech Sheet 60249		



Bent

0474	OD mm	Thread
M-EFTCB-15-12	15	1/2"
M-EFTCB-15-34	15	3/4"
M-EFTCB-22-34	22	3/4"
Tech Sheet 60249		

Crossovers



Part

0474	OD mm
M-EFCOP-15	15
Tech Sheet 60249	

End Caps



End Caps

0474	OD mm
M-EFTC-8	8
M-EFTC-22	22
M-EFTC-28	28
Tech Sheet 60249	

Elbows



90° Elbows

0474	OD mm
M-EF90E-10	10
M-EF90E-15	15
M-EF90E-22	22
Tech Sheet 60249	



45° Elbows

0474	OD mm
M-EF45E-22	22
M-EF45E-42	42
Tech Sheet 60249	

Tees



Equal

0474	OD mm
M-EFET-8	8
M-EFET-10	10
M-EFET-15	15
M-EFET-35	35
M-EFET-42	42
M-EFET-54	54
Tech Sheet 60249	




Reducing Branch

0474	OD mm	OD mm
M-EFRBT-22-15	22	15
M-EFRBT-28-22	28	22
M-EFRBT-35-15	35	15
M-EFRBT-35-22	35	22
M-EFRBT-35-28	35	28
M-EFRBT-42-15	42	15
M-EFRBT-42-22	42	22
M-EFRBT-42-28	42	28
M-EFRBT-42-35	42	35
M-EFRBT-54-28	54	28
M-EFRBT-54-35	54	35
M-EFRBT-54-42	54	42
Tech Sheet 60249		

DISTRIBUTION MANIFOLDS

Equal Cross Manifolds



Female, BSPP

0315	Thread
KMDS-1/8	1/8"
KMDS-1/4	1/4"
KMDS-3/8	3/8"
KMDS-1/2	1/2"
Tech Sheet 3108	

ALUMINIUM MANIFOLDS

Single Distribution Manifold

Working Temperature:
0°C to +80°C

Maximum Working Pressure:
12 bar




1/4" BSPT Inlet x 1/4" BSPT Outlet

1000	No. of Inlets	No. of Outlets
MD-2	2	2
MD-3	2	3
MD-4	2	4
MD-5	2	5

Single Distribution Manifold

AIGNEP



1/4" BSPP Inlet x 1/8" BSPP Outlet

1000	No. of Inlets	No. of Outlets
DM13/3	2	3
DM13/4	2	4
DM13/5	2	5
DM13/6	2	6

Round Manifolds

Working Temperature:
0°C to +80°C

Maximum Working Pressure:
10 bar



1/4" BSPT Inlet x 1/4" BSPT Outlet

1000	No. of Inlets	No. of Outlets
M2-14	1	2

Round Manifolds

Working Temperature:
0°C to +80°C

Maximum Working Pressure:
10 bar



1/4" BSPT Inlet x 1/4" BSPT Outlet

1000	No. of Inlets	No. of Outlets
M3-14	1	3

Fluid-Air Components Ltd

ALUMINIUM MANIFOLDS

Single Distribution Manifolds



1/8" BSPP Inlet x M5 Outlet

0012	No. of Inlets	No. of Outlets
MAN-155.02	2	2
MAN-155.06	2	6
Tech Sheet 12		

1/4" BSPP Inlet x 1/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-151.02	2	2
MAN-151.03	2	3
MAN-151.04	2	4
MAN-151.05	2	5
MAN-151.06	2	6
Tech Sheet 12		

3/8" BSPP Inlet x 1/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-153.03	2	3
MAN-153.04	2	4
MAN-153.05	2	5
MAN-153.06	2	6
Tech Sheet 12		

3/8" BSPP Inlet x 1/4" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-152.02	2	2
MAN-152.03	2	3
MAN-152.04	2	4
MAN-152.05	2	5
MAN-152.06	2	6
Tech Sheet 12		

1/2" BSPP Inlet x 1/4" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-154.02	2	2
MAN-154.03	2	3
MAN-154.04	2	4
MAN-154.05	2	5
MAN-154.06	2	6
Tech Sheet 12		

1/2" BSPP Inlet x 3/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-156.02	2	2
MAN-156.03	2	3
MAN-156.04	2	4
MAN-156.05	2	5
MAN-156.06	2	6
Tech Sheet 12		

1/2" BSPP Inlet x 1/2" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-157.02	2	2
MAN-157.03	2	3
MAN-157.04	2	4
MAN-157.05	2	5
Tech Sheet 12		

Double Distribution Manifolds



1/8" BSPP Inlet x M5 Outlet

0012	No. of Inlets	No. of Outlets
MAN-155.22	2	5mm x 2 + 2
Tech Sheet 12		

1/4" BSPP Inlet x 1/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-151.22	2	2 + 2
MAN-151.33	2	3 + 3
MAN-151.44	2	4 + 4
MAN-151.55	2	5 + 5
Tech Sheet 12		

3/8" BSPP Inlet x 1/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-153.33	2	3 + 3
MAN-153.44	2	4 + 4
MAN-153.55	2	5 + 5
Tech Sheet 12		

3/8" BSPP Inlet x 1/4" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-152.22	2	2 + 2
MAN-152.33	2	3 + 3
MAN-152.44	2	4 + 4
MAN-152.55	2	5 + 5
Tech Sheet 12		

1/2" BSPP Inlet x 1/4" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-154.22	2	2 + 2
MAN-154.33	2	3 + 3
MAN-154.44	2	4 + 4
MAN-154.55	2	5 + 5
Tech Sheet 12		

1/2" BSPP Inlet x 3/8" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-156.44	2	4 + 4
MAN-156.55	2	5 + 5
Tech Sheet 12		

1/2" BSPP Inlet x 1/2" BSPP Outlet

0012	No. of Inlets	No. of Outlets
MAN-157.22	2	2 + 2
MAN-157.33	2	3 + 3
MAN-157.44	2	4 + 4
MAN-157.55	2	5 + 5
Tech Sheet 12		

Equal Cross Manifolds



Female, BSPP

0012	Thread
MAN-145.8	1/8"
MAN-145.4	1/4"
MAN-145.3	3/8"
MAN-145.2	1/2"
Tech Sheet 12	

A wide range of aluminium manifolds, ideal for multi-feeds and supplies in systems and for grouping valves.

BRASS MANIFOLDS

Single Sided Manifold Block, Brass



1/8" BSPP Inlet x 1/8" BSPP Outlet

1420	No. of Outlets
MB02/04	4
MB02/06	6
MB02/08	8

1/4" BSPP Inlet x 1/4" BSPP Outlet

1420	No. of Outlets
MB04/02	2
MB04/04	4
MB04/06	6
MB04/08	8
MB04/10	10

3/8" BSPP Inlet x 3/8" BSPP Outlet

1420	No. of Outlets
MB06/04	4
MB06/06	6
MB06/08	8

1/2" BSPP Inlet x 1/2" BSPP Outlet

1420	No. of Outlets
MB08/04	4
MB08/06	6
MB08/08	8

3/4" BSPP Inlet x 3/4" BSPP Outlet

1420	No. of Outlets
MB12/04	4
MB12/06	6

Unequal Manifold Block, Brass



3/4" BSPP Inlet x 1/2" BSPP Outlet

1420	No. of Outlets
MB12/08/04	4

3/8" BSPP Inlet x 1/4" BSPP Outlet

1420	No. of Outlets
MB06/04/04	4
MB06/04/06	6
MB06/04/08	8




For **Hydraulic Ball Valves**
...see pages **238-240**

Fluid-Air Components Ltd

MINIFOLDS

Aluminium 5 & 10 Way Manifolds

Replace complex assemblies of valves and fittings with anodised aluminium Minifolds
Each Minifold comprises of a number of valved outlets on a common header.
Minifold blocks have tapped inlet connections at both ends – connect to one and plug the other or connect Minifolds in series.



Working Temperature:
-20°C to +90°C

Maximum Working Pressure:
Vacuum to 10 bar

Specifications

Series 971: Nominal Bore 18mm
1/2" BSP Female or
1/2" NPT Female inlets
1/4" BSP Female or
1/4" NPT Female or 6mm push-in outlets

Series 975: Nominal Bore 25mm
3/4" BSP Female or
3/4" NPT Female inlets
3/8" BSP Female or
3/8" NPT Female outlets

Materials:

Blocks:	Anodised aluminium
Valve Spindles:	Thermoplastic (red for BSP, grey for NPT)
Seals:	Nitrile
Push-in Fittings:	Plated brass



1/2" BSPP Inlet x 1/4" BSPP Outlet

0202	No. of Inlets	No. of Outlets
971-05-251	2	5
971-10-251	2	10
Tech Sheet 10556		

1/2" BSPP Inlet x 6mm Outlet

0202	No. of Inlets	No. of Outlets
971-05-256	2	5
971-10-256	2	10
Tech Sheet 10556		

3/4" BSPP Inlet x 3/8" BSPP Outlet

0202	No. of Inlets	No. of Outlets
975-05-272	2	5
975-10-272	2	10
Tech Sheet 10556		

1/2" NPT Inlet x 1/4" NPT Outlet

0202	No. of Inlets	No. of Outlets
971-10-263	2	10
Tech Sheet 10556		

1/2" NPT Inlet x 6mm Outlet

0202	No. of Inlets	No. of Outlets
971-10-266	2	10
Tech Sheet 10556		

Stainless Steel 4, 6 & 10 Way Manifolds

Working Temperature:
60 bar @ 40°C
40 bar @ 100°C
25 bar @ 150°C

Replace complex assemblies of valves and fitting with stainless steel manifolds.
Each Minifold comprises of a number of ball valves on a common header.

Minifold blocks have tapped inlet connections at both ends – connect to one and plug the other or connect Minifold in series.

Specifications

Series 910: Nominal Bore 18mm
1/2" or 3/4" BSP Taper or NPT inlets
1/4" or 1/2" BSP Taper or NPT outlet

Supplied with two mounting brackets

Materials:

Blocks:	316 Stainless steel
Valve Body/Ball:	316 Stainless steel
Valve Handle:	304 Stainless steel (Red for BSP, black for NPT)
Valve Seals:	PTFE

stainless steel



1/2" BSPT Inlet x 1/4" BSPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP011414	2	4
910.06.SDP011414	2	6
910.10.SDP011414	2	10



3/4" BSPT Inlet x 1/4" BSPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP012828	2	4
910.10.SDP012828	2	10



3/4" BSPT Inlet x 1/2" BSPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP142828	2	4
910.06.SDP142828	2	6



1/2" NPT Inlet x 1/4" NPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP030606	2	4
910.06.SDP030606	2	6



3/4" NPT Inlet x 1/4" NPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP032727	2	4



3/4" NPT Inlet x 1/2" NPT Outlet

0202	No. of Inlets	No. of Outlets
910.04.SDP062727	2	4
910.06.SDP062727	2	6

ROTATING & SWIVEL JOINTS

Rotating Joints

- Viton seals as standard
- Suitable for fluids and air
- Units suitable for vacuum and non standard pressures available on request

Working Temperature:
-10°C to +85°C

Maximum Working Pressure:
12 bar



1 Inlet x 6 Outlets

0064	No. of Inlets	No. of Outlets	Rotation	RPM
300/V	1 x 3/8"	6 x 1/8"	Right/Left	300
Tech Sheet 29				

Working Temperature:
-10°C to +85°C

Maximum Working Pressure:
12 bar



1 Inlet x 3 Outlets

0064	No. of Inlets	No. of Outlets	Rotation	RPM
302/V	1 x 3/8"	3 x 1/4"	Right/Left	300
Tech Sheet 29				

Working Temperature:
-10°C to +85°C

Maximum Working Pressure:
12 bar




1 Inlet x 1 Outlet

0064	No. of Inlets	No. of Outlets	Rotation	RPM
303/V	1 x 1/8"	1 x 1/8"	Right/Left	550
304/V	1 x 1/4"	1 x 1/4"	Right/Left	550
305/V	1 x 3/8"	1 x 3/8"	Right/Left	300
307/V	1 x 3/4"	1 x 3/4"	Right/Left	160
Tech Sheet 30				

Working Temperature:
-10°C to +85°C

Maximum Working Pressure:
12 bar



2 Independent Inlets & Outlets

0064	No. of Inlets	No. of Outlets	Rotation	RPM
312/V	2 x 1/4"	2 x 1/4"	Right/Left	200
Tech Sheet 31				

Swivel Joints - Aluminium

Working Temperature:
0°C to +70°C

Maximum Working Pressure:
12 bar



Male x Female Thread, without Regulator

1000	Thread
RJ-14	1/4"

For **Globe Valves**
...see page **975**



Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 10

Stainless Steel

10.01 Stainless Steel Hydraulics **1225-1287**

10.02 Stainless Steel Valves **1288-1303**

10.03 Stainless Steel Couplings **1304-1310**

10.04 Stainless Steel Pipe Fittings **1311-1322**

10.05 Stainless Steel Pneumatic Push-in Fittings **1323-1326**

10.06 Stainless Steel Pneumatic QRC **1327**

10.07 Stainless Steel Solenoid Valves **1328**

10.08 Stainless Steel Pressure Gauges **1329-1332**


Fluid-Air Components Ltd

SECTION 10

10.01 Stainless Steel Hydraulics

1225-1287

- Hydraulic Stainless Steel Ferrules
- Hydraulic Stainless Steel Inserts
- 316 Stainless Steel DIN EN ISO 8434-1 Tube Fittings



10.02 Stainless Steel Valves

1288-1303

- Stainless Steel Hydraulic Valves
- Stainless Steel Valves
- Gate Valves
- Check Valves
- Y Strainers
- Stainless Steel Compression Ball Valves



10.03 Stainless Steel Couplings

1304-1310

- ISO A Interchange Couplings & Plugs
- ISO B Interchange Couplings & Plugs
- Hydraulic Quick Release Couplings
- Cam & Groove Quick Couplings
- Claw Couplings
- RJT Couplings
- Stainless Steel Lever Lock Water Pump Couplings



10.04 Stainless Steel Pipe Fittings

1311-1322

- 150lb 316 Stainless Steel Pipe Fittings
- 3000lb 316 Stainless Steel Pipe Fittings
- BS TYPE, 316L Hygienic Pipe Fittings
- Hygienic Clamp Fittings



Fluid-Air Components Ltd

10.05 Stainless Steel Pneumatic Push-in Fittings

1323-1326

- One Touch All Stainless Steel Push-In Fittings
- 316 Stainless Steel Push-In Fittings



10.06 Stainless Steel Pneumatic QRC

1327

- Series 25 Quick Coupling
  European Profile Stainless Stee



10.07 Stainless Steel Solenoid Valves

1328

- Solenoid Valves



10.08 Stainless Steel Pressure Gauges

1329-1332

- Glycerine Gauges & Accessories
- Test Point Couplings
- Silencers
- Float Level Switches



HYDRAULIC STAINLESS STEEL FERRULES

stainless steel

Ferrules

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)



R1AT Non-skive

0044	To Suit Hose ID
SFR1-05	3/16"
SFR1-06	1/4"
SFR1-08	5/16"
SFR1-10	3/8"
SFR1-12	1/2"
SFR1-16	5/8"
SFR1-20	3/4"
SFR1-25	1"
SFR1-31	1.1/4"
SFR1-38	1.1/2"
SFR1-51	2"

Tech Sheet 60587



R2AT Non-skive

0044	To Suit Hose ID
SFR2-05	3/16"
SFR2-06	1/4"
SFR2-08	5/16"
SFR2-10	3/8"
SFR2-12	1/2"
SFR2-16	5/8"
SFR2-20	3/4"
SFR2-25	1"
SFR2-31	1.1/4"
SFR2-38	1.1/2"
SFR2-51	2"

Tech Sheet 60588



R1AT & R2AT Dual, Non-skive

0044	To Suit Hose ID
SFR3-06	1/4"
SFR3-08	5/16"
SFR3-10	3/8"
SFR3-12	1/2"
SFR3-16	5/8"
SFR3-20	3/4"
SFR3-25	1"

Tech Sheet 60587

EN857-1SC Non-skive

0044	To Suit Hose ID
SFR1-06SC	1/4"
SFR1-08SC	5/16"
SFR1-10SC	3/8"
SFR1-12SC	1/2"

Tech Sheet 60587

EN857-2SC Non-skive

0044	To Suit Hose ID
SFR2-06SC	1/4"
SFR2-08SC	5/16"
SFR2-10SC	3/8"
SFR2-12SC	1/2"
SFR2-16SC	5/8"
SFR2-20SC	3/4"
SFR2-25SC	1"

Tech Sheet 60587



PTFE, Smooth Bore

0044	To Suit Hose ID
SFPTFE-05	3/16"
SFPTFE-06	1/4"
SFPTFE-08	5/16"
SFPTFE-10	3/8"
SFPTFE-12	1/2"
SFPTFE-16	5/8"
SFPTFE-20	3/4"
SFPTFE-25	1"

Tech Sheet 60586



PTFE, Convoluted Bore

0044	To Suit Hose ID
SCFPTFE-06	1/4"
SCFPTFE-08	5/16"
SCFPTFE-10	3/8"
SCFPTFE-12	1/2"
SCFPTFE-16	5/8"
SCFPTFE-20	3/4"
SCFPTFE-25	1"

Tech Sheet 60585

FT PRO



For **Full range of Hydraulic Hose** see pages **6-14**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

BSP

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Male Inserts, BSPP



0044	Thread	To Suit Hose ID
SMI05-14	1/4"	3/16"
SMI06-18	1/8"	1/4"
SMI06-14	1/4"	1/4"
SMI06-38	3/8"	1/4"
SMI06-12	1/2"	1/4"
SMI08-14	1/4"	5/16"
SMI08-38	3/8"	5/16"
SMI08-12	1/2"	5/16"
SMI10-14	1/4"	3/8"
SMI10-38	3/8"	3/8"
SMI10-12	1/2"	3/8"
SMI12-38	3/8"	1/2"
SMI12-12	1/2"	1/2"
SMI12-34	3/4"	1/2"
SMI16-12	1/2"	5/8"
SMI16-58	5/8"	5/8"
SMI16-34	3/4"	5/8"
SMI20-34	3/4"	3/4"
SMI20-1	1"	3/4"
SMI25-1	1"	1"
SMI25-34	3/4"	1"
SMI25-114	1.1/4"	1"
SMI31-114	1.1/4"	1.1/4"
SMI31-112	1.1/2"	1.1/4"
SMI38-112	1.1/2"	1.1/2"
SMI51-2	2"	2"

Tech Sheet 60593

Male Inserts, BSPT



0044	Thread	To Suit Hose ID
AGRK-1/8-DN05	1/8"	3/16"
AGRK-1/8-DN06	1/8"	1/4"
AGRK-1/4-DN05	1/4"	3/16"
AGRK-1/4-DN06	1/4"	1/4"
AGRK-1/4-DN10	1/4"	3/8"
AGRK-1/4-DN08	1/4"	5/16"
AGRK-3/8-DN06	3/8"	1/4"
AGRK-3/8-DN08	3/8"	5/16"
AGRK-3/8-DN10	3/8"	3/8"
AGRK-3/8-DN12	3/8"	1/2"
AGRK-1/2-DN10	1/2"	3/8"
AGRK-1/2-DN12	1/2"	1/2"
AGRK-1/2-DN19	1/2"	3/4"
AGRK-3/4-DN12	3/4"	1/2"
AGRK-3/4-DN16	3/4"	5/8"
AGRK-3/4-DN19	3/4"	3/4"
AGRK-3/4-DN25	3/4"	1"
AGRK-1-DN19	1"	3/4"
AGRK-1-DN25	1"	1"
AGRK-11/4-DN31	1.1/4"	1.1/4"
AGRK-11/2-DN38	1.1/2"	1.1/2"
AGRK-2-DN51	2"	2"

Tech Sheet 60589

Swivel Female Inserts, BSPP



0044	Thread	To Suit Hose ID
SFI05-18	1/8"	3/16"
SFI05-14	1/4"	3/16"
SFI06-18	1/8"	1/4"
SFI06-14	1/4"	1/4"
SFI06-38	3/8"	1/4"
SFI06-12	1/2"	1/4"
SFI08-14	1/4"	5/16"
SFI08-38	3/8"	5/16"
SFI08-12	1/2"	5/16"
SFI10-14	1/4"	3/8"
SFI10-38	3/8"	3/8"
SFI10-12	1/2"	3/8"
SFI12-38	3/8"	1/2"
SFI12-12	1/2"	1/2"
SFI12-58	5/8"	1/2"
SFI16-12	1/2"	5/8"
SFI16-58	5/8"	5/8"
SFI16-34	3/4"	5/8"
SFI20-12	1/2"	3/4"
SFI20-34	3/4"	3/4"
SFI20-1	1"	3/4"
SFI20-114	1.1/4"	3/4"
SFI25-1	1"	1"
SFI25-34	3/4"	1"
SFI25-114	1.1/4"	1"
SFI31-1	1"	1.1/4"
SFI31-114	1.1/4"	1.1/4"
SFI31-112	1.1/2"	1.1/4"
SFI38-112	1.1/2"	1.1/2"
SFI38-2	2"	1.1/2"
SFI51-2	2"	2"

Tech Sheet 60592

Female Swept 90° Inserts, BSPP



0044	Thread	To Suit Hose ID
SEI05-14	1/4"	3/16"
SEI05-18	1/8"	3/16"
SEI06-18	1/8"	1/4"
SEI06-14	1/4"	1/4"
SEI06-38	3/8"	1/4"
SEI08-14	1/4"	5/16"
SEI08-38	3/8"	5/16"
SEI10-14	1/4"	3/8"
SEI10-38	3/8"	3/8"
SEI10-12	1/2"	3/8"
SEI12-38	3/8"	1/2"
SEI12-12	1/2"	1/2"
SEI12-58	5/8"	1/2"
SEI16-12	1/2"	5/8"
SEI16-58	5/8"	5/8"
SEI16-34	3/4"	5/8"
SEI20-34	3/4"	3/4"
SEI20-1	1"	3/4"
SEI25-1	1"	1"
SEI25-114	1.1/4"	1"
SEI31-114	1.1/4"	1.1/4"
SEI31-112	1.1/2"	1.1/4"
SEI38-112	1.1/2"	1.1/2"
SEI38-2	2"	1.1/2"
SEI51-2	2"	2"

Tech Sheet 60591

Female Swept 45° Inserts, BSPP



0044	Thread	To Suit Hose ID
DKR-1/8-45-DN05	1/8"	3/16"
DKR-1/8-45-DN06	1/8"	1/4"
DKR-1/4-45-DN05	1/4"	3/16"
DKR-1/4-45-DN06	1/4"	1/4"
DKR-1/4-45-DN08	1/4"	5/16"
DKR-1/4-45-DN10	1/4"	3/8"
DKR-3/8-45-DN06	3/8"	1/4"
DKR-3/8-45-DN08	3/8"	5/16"
DKR-3/8-45-DN10	3/8"	3/8"
DKR-3/8-45-DN12	3/8"	1/2"
DKR-1/2-45-DN10	1/2"	3/8"
DKR-1/2-45-DN12	1/2"	1/2"
DKR-1/2-45-DN16	1/2"	5/8"
DKR-5/8-45-DN12	5/8"	1/2"
DKR-5/8-45-DN16	5/8"	5/8"
DKR-3/4-45-DN12	3/4"	1/2"
DKR-3/4-45-DN16	3/4"	5/8"
DKR-3/4-45-DN19	3/4"	3/4"
DKR-1-45-DN19	1"	3/4"
DKR-1-45-DN25	1"	1"
DKR-11/4-45-DN25	1.1/4"	1"
DKR-11/4-45-DN31	1.1/4"	1.1/4"
DKR-11/2-45-DN31	1.1/2"	1.1/4"
DKR-11/2-45-DN38	1.1/2"	1.1/2"
DKR-2-45-DN38	2"	1.1/2"
DKR-2-45-DN51	2"	2"

Tech Sheet 60590

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

JIC 37°

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Male Inserts

0044	Thread	To Suit Hose ID
AGJ-7/16-DN05	7/16"	3/16"
AGJ-7/16-DN06	7/16"	1/4"
AGJ-1/2-DN05	1/2"	3/16"
AGJ-1/2-DN06	1/2"	1/4"
AGJ-1/2-DN08	1/2"	5/16"
AGJ-9/16-DN05	9/16"	3/16"
AGJ-9/16-DN06	9/16"	1/4"
AGJ-9/16-DN08	9/16"	5/16"
AGJ-9/16-DN10	9/16"	3/8"
AGJ-3/4-DN10	3/4"	3/8"
AGJ-3/4-DN12	3/4"	1/2"
AGJ-7/8-DN10	7/8"	3/8"
AGJ-7/8-DN12	7/8"	1/2"
AGJ-7/8-DN16	7/8"	5/8"
AGJ-11/16-DN12	1.1/16"	1/2"
AGJ-11/16-DN16	1.1/16"	5/8"
AGJ-11/16-DN19	1.1/16"	3/4"
AGJ-15/16-DN19	1.5/16"	3/4"
AGJ-15/16-DN25	1.5/16"	1"
AGJ-15/8-DN25	1.5/8"	1"
AGJ-15/8-DN31	1.5/8"	1.1/4"
AGJ-17/8-DN31	1.7/8"	1.1/4"
AGJ-17/8-DN38	1.7/8"	1.1/2"
AGJ-2 1/2-DN38	2.1/2"	1.1/2"
AGJ-2 1/2-DN51	2.1/2"	2"

Tech Sheet 60594



Female Swivel Inserts

0044	Thread	To Suit Hose ID
DKJ7/16-DN05	7/16"	3/16"
DKJ7/16-DN06	7/16"	1/4"
DKJ1/2-DN05	1/2"	3/16"
DKJ1/2-DN06	1/2"	1/4"
DKJ1/2-DN08	1/2"	5/16"
DKJ9/16-DN05	9/16"	3/16"
DKJ9/16-DN06	9/16"	1/4"
DKJ9/16-DN08	9/16"	5/16"
DKJ9/16-DN10	9/16"	3/8"
DKJ9/16-DN12	9/16"	1/2"
DKJ3/4-DN06	3/4"	1/4"
DKJ3/4-DN08	3/4"	5/16"
DKJ3/4-DN10	3/4"	3/8"
DKJ3/4-DN12	3/4"	1/2"
DKJ3/4-DN16	3/4"	5/8"
DKJ3/4-DN19	3/4"	3/4"
DKJ7/8-DN10	7/8"	3/8"
DKJ7/8-DN12	7/8"	1/2"
DKJ7/8-DN16	7/8"	5/8"
DKJ7/8-DN19	7/8"	3/4"
DKJ11/16-DN12	1.1/16"	1/2"
DKJ11/16-DN16	1.1/16"	5/8"
DKJ11/16-DN19	1.1/16"	3/4"
DKJ11/16-DN25	1.1/16"	1"
DKJ15/16-DN16	1.5/16"	5/8"
DKJ15/16-DN25	1.5/16"	1"
DKJ15/8-DN25	1.5/8"	1"
DKJ15/8-DN31	1.5/8"	1.1/4"
DKJ17/8-DN31	1.7/8"	1.1/4"
DKJ17/8-DN38	1.7/8"	1.1/2"
DKJ21/2-DN38	2.1/2"	1.1/2"
DKJ21/2-DN51	2.1/2"	2"


Tech Sheet 60597



Female Swept 90° Inserts

0044	Thread	To Suit Hose ID
DKJ7/16-90-DN05	7/16"	3/16"
DKJ7/16-90-DN06	7/16"	1/4"
DKJ1/2-90-DN05	1/2"	3/16"
DKJ1/2-90-DN06	1/2"	1/4"
DKJ1/2-90-DN08	1/2"	5/16"
DKJ9/16-90-DN05	9/16"	3/16"
DKJ9/16-90-DN06	9/16"	1/4"
DKJ9/16-90-DN08	9/16"	5/16"
DKJ9/16-90-DN10	9/16"	3/8"
DKJ3/4-90-DN10	3/4"	3/8"
DKJ3/4-90-DN12	3/4"	1/2"
DKJ7/8-90-DN10	7/8"	3/8"
DKJ7/8-90-DN12	7/8"	1/2"
DKJ7/8-90-DN16	7/8"	5/8"
DKJ11/16-90-DN12	1.1/16"	1/2"
DKJ11/16-90-DN16	1.1/16"	5/8"
DKJ11/16-90-DN19	1.1/16"	3/4"
DKJ15/16-90-DN19	1.5/16"	3/4"
DKJ15/16-90-DN25	1.5/16"	1"
DKJ1.5/8-90-DN25	1.5/8"	1"
DKJ15/8-90-DN31	1.5/8"	1.1/4"
DKJ17/8-90-DN31	1.7/8"	1.1/4"
DKJ17/8-90-DN38	1.7/8"	1.1/2"
DKJ21/2-90-DN38	2.1/2"	1.1/2"
DKJ21/2-90-DN51	2.1/2"	2"

Tech Sheet 60596



Female Swept 45° Inserts

0044	Thread	To Suit Hose ID
DKJ-7/16-45-DN06	7/16"	1/4"
DKJ-1/2-45-DN06	1/2"	1/4"
DKJ-1/2-45-DN08	1/2"	5/16"
DKJ-9/16-45-DN06	9/16"	1/4"
DKJ-9/16-45-DN08	9/16"	5/16"
DKJ-9/16-45-DN10	9/16"	3/8"
DKJ-3/4-45-DN10	3/4"	3/8"
DKJ-3/4-45-DN12	3/4"	1/2"
DKJ-7/8-45-DN10	7/8"	3/8"
DKJ-7/8-45-DN12	7/8"	1/2"
DKJ-7/8-45-DN16	7/8"	5/8"
DKJ-1116-45-DN12	1.1/16	1/2"
DKJ-1116-45-DN16	1.1/16	5/8"
DKJ-1116-45-DN19	1.1/16	3/4"
DKJ-1516-45-DN19	1.5/16"	3/4"
DKJ-1516-45-DN25	1.5/16"	1"
DKJ-15/8-45-DN25	1.5/8"	1"
DKJ-15/8-45-DN31	1.5/8"	1.1/4"
DKJ-17/8-45-DN31	1.7/8"	1.1/4"
DKJ-17/8-45-DN38	1.7/8"	1.1/2"
DKJ-21/2-45-DN38	2.1/2"	1.1/2"
DKJ-21/2-45-DN51	2.1/2"	2"

Tech Sheet 60595

FT PRO



For **Hose & Pipe Cleaning** see page **49**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

Metric Light Series

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Metric Male 24° Cone Seat, L Series DIN 2353

0044	Thread	To Suit Hose ID
CEL-06-DN05	M12 x 1.5	3/16"
CEL-06-DN06	M12 x 1.5	1/4"
CEL-08-DN05	M14 x 1.5	3/16"
CEL-08-DN06	M14 x 1.5	1/4"
CEL-10-DN06	M16 x 1.5	1/4"
CEL-10-DN08	M16 x 1.5	5/16"
CEL-10-DN10	M16 x 1.5	3/8"
CEL-12-DN06	M18 x 1.5	1/4"
CEL-12-DN08	M18 x 1.5	5/16"
CEL-12-DN10	M18 x 1.5	3/8"
CEL-12-DN12	M18 x 1.5	1/2"
CEL-15-DN10	M22 x 1.5	3/8"
CEL-15-DN12	M22 x 1.5	1/2"
CEL-18-DN12	M26 x 1.5	1/2"
CEL-18-DN16	M26 x 1.5	5/8"
CEL-18-DN19	M26 x 1.5	3/4"
CEL-22-DN16	M30 x 2	5/8"
CEL-22-DN19	M30 x 2	3/4"
CEL-28-DN19	M36 x 2	3/4"
CEL-28-DN25	M36 x 2	1"
CEL-35-DN31	M45 x 2	1.1/4"
CEL-42-DN38	M52 x 2	1.1/2"

Tech Sheet 60598



Metric Female 24° Cone Seat, L Series with O-Ring, DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-DN05	M12 x 1.5	3/16"
DKOL-06-DN06	M12 x 1.5	1/4"
DKOL-08-DN05	M14 x 1.5	3/16"
DKOL-08-DN06	M14 x 1.5	1/4"
DKOL-08-DN08	M14 x 1.5	5/16"
DKOL-08-DN10	M14 x 1.5	3/8"
DKOL-10-DN06	M16 x 1.5	1/4"
DKOL-10-DN08	M16 x 1.5	5/16"
DKOL-10-DN10	M16 x 1.5	3/8"
DKOL-12-DN06	M18 x 1.5	1/4"
DKOL-12-DN08	M18 x 1.5	5/16"
DKOL-12-DN10	M18 x 1.5	3/8"
DKOL-12-DN12	M18 x 1.5	1/2"
DKOL-15-DN06	M22 x 1.5	1/4"
DKOL-15-DN08	M22 x 1.5	5/16"
DKOL-15-DN10	M22 x 1.5	3/8"
DKOL-15-DN12	M22 x 1.5	1/2"
DKOL-15-DN16	M22 x 1.5	5/8"
DKOL-18-DN10	M26 x 1.5	3/8"
DKOL-18-DN12	M26 x 1.5	1/2"
DKOL-18-DN16	M26 x 1.5	5/8"
DKOL-18-DN19	M26 x 1.5	3/4"
DKOL-22-DN12	M30 x 2	1/2"
DKOL-22-DN16	M30 x 2	5/8"
DKOL-22-DN19	M30 x 2	3/4"
DKOL-22-DN25	M30 x 2	1"
DKOL-28-DN16	M36 x 2	5/8"
DKOL-28-DN19	M36 x 2	3/4"
DKOL-28-DN25	M36 x 2	1"
DKOL-35-DN25	M45 x 2	1"
DKOL-35-DN31	M45 x 2	1.1/4"
DKOL-42-DN31	M52 x 2	1.1/4"
DKOL-42-DN38	M52 x 2	1.1/2"

Tech Sheet 60601



90° Metric Female 24° Cone Seat, L Series with O-Ring DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-90-DN05	M12 X 1.5	3/16"
DKOL-06-90-DN06	M12 x 1.5	1/4"
DKOL-08-90-DN06	M14 x 1.5	1/4"
DKOL-08-90-DN08	M14 x 1.5	5/16"
DKOL-10-90-DN06	M16 x 1.5	1/4"
DKOL-10-90-DN08	M16 x 1.5	5/16"
DKOL-10-90-DN10	M16 x 1.5	3/8"
DKOL-12-90-DN06	M18 x 1.5	1/4"
DKOL-12-90-DN08	M18 x 1.5	5/16"
DKOL-12-90-DN10	M18 x 1.5	3/8"
DKOL-12-90-DN12	M18 x 1.5	1/2"
DKOL-15-90-DN10	M22 x 1.5	3/8"
DKOL-15-90-DN12	M22 x 1.5	1/2"
DKOL-18-90-DN12	M26 x 1.5	1/2"
DKOL-18-90-DN16	M26 x 1.5	5/8"
DKOL-22-90-DN16	M30 x 2	5/8"
DKOL-22-90-DN19	M30 x 2	3/4"
DKOL-28-90-DN19	M36 x 2	3/4"
DKOL-28-90-DN25	M36 x 2	1"
DKOL-35-90-DN31	M45 x 2	1.1/4"
DKOL-42-90-DN38	M52 x 2	1.1/2"

Tech Sheet 60600



45° Metric Female 24° Cone Seat, L Series with O-Ring DIN 2353

0044	Thread	To Suit Hose ID
DKOL-06-45-DN05	M12 x 1.5	3/16"
DKOL-06-45-DN06	M12 x 1.5	1/4"
DKOL-08-45-DN05	M14 x 1.5	3/16"
DKOL-08-45-DN06	M14 x 1.5	1/4"
DKOL-08-45-DN08	M14 x 1.5	5/16"
DKOL-10-45-DN06	M16 x 1.5	1/4"
DKOL-10-45-DN08	M16 x 1.5	5/16"
DKOL-10-45-DN10	M16 x 1.5	3/8"
DKOL-12-45-DN06	M18 x 1.5	1/4"
DKOL-12-45-DN08	M18 x 1.5	5/16"
DKOL-12-45-DN10	M18 x 1.5	3/8"
DKOL-12-45-DN12	M18 x 1.5	1/2"
DKOL-15-45-DN10	M22 x 1.5	3/8"
DKOL-15-45-DN12	M22 x 1.5	1/2"
DKOL-18-45-DN12	M26 x 1.5	1/2"
DKOL-18-45-DN16	M26 x 1.5	5/8"
DKOL-22-45-DN16	M30 x 2	5/8"
DKOL-22-45-DN19	M30 x 2	3/4"
DKOL-28-45-DN19	M36 x 2	3/4"
DKOL-28-45-DN25	M36 x 2	1"
DKOL-35-45-DN31	M45 x 2	1.1/4"
DKOL-42-45-DN38	M52 x 2	1.1/2"

Tech Sheet 60599

FT PRO



For **Polypropylene Protective Hose Sleeves** see pages **47-48**

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

Metric Heavy Series

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Metric Male 24° Cone Seat, S Series DIN 2353

0044	Thread	To Suit Hose ID
CES-06-DN06	M14 x 1.5	1/4"
CES-08-DN06	M16 x 1.5	1/4"
CES-10-DN06	M18 x 1.5	1/4"
CES-10-DN08	M18 x 1.5	5/16"
CES-10-DN10	M18 x 1.5	3/8"
CES-12-DN08	M20 x 1.5	5/16"
CES-12-DN10	M20 x 1.5	3/8"
CES-14-DN08	M22 x 1.5	5/16"
CES-14-DN10	M22 x 1.5	3/8"
CES-16-DN10	M24 x 1.5	3/8"
CES-16-DN12	M24 x 1.5	1/2"
CES-20-DN12	M30 x 2	1/2"
CES-20-DN16	M30 x 2	5/8"
CES-20-DN19	M30 x 2	3/4"
CES-25-DN19	M36 x 2	3/4"
CES-25-DN25	M36 x 2	1"
CES-38-DN31	M52 x 2	1.1/4"
CES-30-DN25	M42 x 2	1"

Tech Sheet 60602



Metric Female 24° Cone Seat, S Series, DIN 2353

0044	Thread	To Suit Hose ID
DKOS-06-DN05	M14 x 1.5	3/16"
DKOS-06-DN06	M14 x 1.5	1/4"
DKOS-08-DN05	M16 x 1.5	3/16"
DKOS-08-DN06	M16 x 1.5	1/4"
DKOS-08-DN08	M16 x 1.5	5/16"
DKOS-08-DN10	M16 x 1.5	3/8"
DKOS-10-DN06	M18 x 1.5	1/4"
DKOS-10-DN08	M18 x 1.5	5/16"
DKOS-10-DN10	M18 x 1.5	3/8"
DKOS-12-DN06	M20 x 1.5	1/4"
DKOS-12-DN08	M20 x 1.5	5/16"
DKOS-12-DN10	M20 x 1.5	3/8"
DKOS-12-DN12	M20 x 1.5	1/2"
DKOS-14-DN08	M22 x 1.5	5/16"
DKOS-14-DN10	M22 x 1.5	3/8"
DKOS-16-DN06	M24 x 1.5	1/4"
DKOS-16-DN08	M24 x 1.5	5/16"
DKOS-16-DN10	M24 x 1.5	3/8"
DKOS-16-DN12	M24 x 1.5	1/2"
DKOS-16-DN16	M24 x 1.5	5/8"
DKOS-20-DN10	M30 x 2	3/8"
DKOS-20-DN12	M30 x 2	1/2"
DKOS-20-DN16	M30 x 2	5/8"
DKOS-20-DN19	M30 x 2	3/4"
DKOS-25-DN12	M36 x 2	1/2"
DKOS-25-DN16	M36 x 2	5/8"
DKOS-25-DN19	M36 x 2	3/4"
DKOS-25-DN25	M36 x 2	1"
DKOS-30-DN19	M42 x 2	3/4"
DKOS-30-DN25	M42 x 2	1"
DKOS-38-DN25	M52 x 2	1"
DKOS-38-DN31	M52 x 2	1.1/4"
DKOS-50-DN38	M68 x 2	1.1/2"

Tech Sheet 60605



90° Metric Female 24° Cone Seat, S Series with O-Ring, DIN 2353

0044	Thread	To Suit Hose ID
DKOS-06-90-DN06	M14 x 1.5	1/4"
DKOS-08-90-DN06	M16 x 1.5	1/4"
DKOS-08-90-DN08	M16 x 1.5	5/16"
DKOS-10-90-DN06	M18 x 1.5	1/4"
DKOS-10-90-DN08	M18 x 1.5	5/16"
DKOS-10-90-DN10	M18 x 1.5	3/8"
DKOS-12-90-DN06	M20 x 1.5	1/4"
DKOS-12-90-DN08	M20 x 1.5	5/16"
DKOS-12-90-DN10	M20 x 1.5	3/8"
DKOS-12-90-DN12	M20 x 1.5	1/2"
DKOS-14-90-DN10	M22 x 1.5	3/8"
DKOS-16-90-DN10	M24 x 1.5	3/8"
DKOS-16-90-DN12	M24 x 1.5	1/2"
DKOS-20-90-DN12	M30 x 2	1/2"
DKOS-20-90-DN16	M30 x 2	5/8"
DKOS-20-90-DN19	M30 x 2	3/4"
DKOS-25-90-DN19	M36 x 2	3/4"
DKOS-25-90-DN25	M36 x 2	1"
DKOS-30-90-DN19	M42 x 2	3/4"
DKOS-30-90-DN25	M42 x 2	1"
DKOS-38-90-DN25	M52 x 2	1"
DKOS-38-90-DN31	M52 x 2	1.1/4"

Tech Sheet 60604




45° Metric Female 24° Cone Seat, S Series with O-Ring, DIN 2353

0044	Thread	To Suit Hose ID
DKOS-06-45-DN06	M14 x 1.5	1/4"
DKOS-08-45-DN06	M16 x 1.5	1/4"
DKOS-08-45-DN08	M16 x 1.5	5/16"
DKOS-10-45-DN06	M18 x 1.5	1/4"
DKOS-10-45-DN08	M18 x 1.5	5/16"
DKOS-10-45-DN10	M18 x 1.5	3/8"
DKOS-12-45-DN06	M20 x 1.5	1/4"
DKOS-12-45-DN08	M20 x 1.5	5/16"
DKOS-12-45-DN10	M20 x 1.5	3/8"
DKOS-12-45-DN12	M20 x 1.5	1/2"
DKOS-14-45-DN10	M22 x 1.5	3/8"
DKOS-16-45-DN10	M24 x 1.5	3/8"
DKOS-16-45-DN12	M24 x 1.5	1/2"
DKOS-20-45-DN12	M30 x 2	1/2"
DKOS-20-45-DN16	M30 x 2	5/8"
DKOS-20-45-DN19	M30 x 2	3/4"
DKOS-25-45-DN19	M36 x 2	3/4"
DKOS-25-45-DN25	M36 x 2	1"
DKOS-30-45-DN19	M42 x 2	3/4"
DKOS-30-45-DN25	M42 x 2	1"
DKOS-38-45-DN25	M52 x 2	1"
DKOS-38-45-DN31	M52 x 2	1.1/4"

Tech Sheet 60603

STOPflex FOR PRESSURE HOSES



For **Hose Retention System** see pages **42-43**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel


ORFS

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)



Male (O-Ring Face) Inserts

0044	Thread	To Suit Hose ID
ORFSM0404SS	9/16"	1/4"
ORFSM0606SS	11/16"	3/8"
ORFSM0808SS	13/16"	1/2"
ORFSM1010SS	1"	5/8"
ORFSM1212SS	1.3/16"	3/4"
ORFSM1616SS	1.7/16"	1"
ORFSM2020SS	1.11/16"	1.1/4"
ORFSM2424SS	2"	1.1/2"
Tech Sheet 60610		



Female Inserts

0044	Thread	To Suit Hose ID
ORFSF0404SS	9/16"	1/4"
ORFSF0604SS	11/16"	1/4"
ORFSF0605SS	11/16"	5/16"
ORFSF0606SS	11/16"	3/8"
ORFSF0806SS	13/16"	3/8"
ORFSF0808SS	13/16"	1/2"
ORFSF1008SS	1"	1/2"
ORFSF1010SS	1"	5/8"
ORFSF1012SS	1"	3/4"
ORFSF1208SS	1.3/16"	1/2"
ORFSF1210SS	1.3/16"	5/8"
ORFSF1212SS	1.7/16"	3/4"
ORFSF1612SS	1.7/16"	3/4"
ORFSF1616SS	1.7/16"	1"
ORFSF2020SS	1.11/16"	1.1/4"
ORFSF2424SS	2"	1.1/2"
Tech Sheet 60607		



Female Swept 90° Elbow Inserts

0044	Thread	To Suit Hose ID
ORFSF049004SS	9/16"	1/4"
ORFSF069004SS	11/16"	1/4"
ORFSF069005SS	11/16"	5/16"
ORFSF069006SS	11/16"	3/8"
ORFSF089006SS	13/16"	3/8"
ORFSF089008SS	13/16"	1/2"
ORFSF109010SS	1"	5/8"
ORFSF109012SS	1"	3/4"
ORFSF129012SS	1.7/16"	3/4"
ORFSF169012SS	1.7/16"	3/4"
ORFSF169016SS	1.7/16"	1"
ORFSF209020SS	1.11/16"	1.1/4"
ORFSF209024SS	2"	1.1/2"
Tech Sheet 60609		



Female Swept 45° Elbow Inserts

0044	Thread	To Suit Hose ID
ORFSF044504SS	9/16"	1/4"
ORFSF064504SS	11/16"	1/4"
ORFSF064505SS	11/16"	5/16"
ORFSF064506SS	11/16"	3/8"
ORFSF084506SS	13/16"	3/8"
ORFSF084508SS	13/16"	1/2"
ORFSF104510SS	1"	5/8"
ORFSF104512SS	1"	3/4"
ORFSF124512SS	1.7/16"	3/4"
ORFSF164516SS	1.7/16"	1"
ORFSF204520SS	1.11/16"	1.1/4"
ORFSF204524SS	2"	1.1/2"
Tech Sheet 60608		

Jet Wash Female



M22 x 1.5

0044	To Suit Hose ID
DKO-KA-DN06	1/4"
DKO-KA-DN08	5/16"
DKO-KA-DN10	3/8"
DKO-KA-DN12	1/2"
Tech Sheet 60627	

Banjos



Bolt, Metric

0044	Thread
HS-M10X1	M10 x 1
HS-M12X1.5	M12 x 1.5
HS-M14X1.5	M14 x 1.5
HS-M16X1.5	M16 x 1.5
HS-M18X1.5	M18 x 1.5
HS-M22X1.5	M22 x 1.5
HS-M26X1.5	M26 x 1.5
Tech Sheet 60606	

Bolt, Imperial

0044	Thread
HS-G1/8	1/8"
HS-G1/4	1/4"
HS-G3/8	3/8"
HS-G1/2	1/2"
HS-G3/4	3/4"
Tech Sheet 60606	



Inserts, Metric/Imperial

0044	Thread	Thread	To Suit Hose ID
RGN-10-DN06	M10 x 1	1/8"	1/4"
RGN-10-DN08	M10 x 1	1/8"	5/16"
RGN-12-DN06	M12 x 1.5	-	1/4"
RGN-12-DN08	M12 x 1.5	-	5/16"
RGN-14-DN06	M14 x 1.5	-	1/4"
RGN-1/4-DN06	-	1/4"	1/4"
RGN-14-DN08	M14 x 1.5	-	5/16"
RGN-14-DN10	M14 x 1.5	-	3/8"
RGN-16-DN08	M16 x 1.5	3/8"	5/16"
RGN-16-DN10	M16 x 1.5	3/8"	3/8"
RGN-16-DN12	M16 x 1.5	3/8"	1/2"
RGN-18-DN10	M18 x 1.5	-	3/8"
RGN-1/2-DN10	-	1/2"	3/8"
RGN-1/2-DN12	-	1/2"	1/2"
RGN-18-DN12	M18 x 1.5	-	1/2"
RGN-22-DN12	M22 x 1.5	-	1/2"
RGN-22-DN16	M22 x 1.5	-	5/8"
RGN-26-DN19	M26 x 1.5	3/4"	3/4"
Tech Sheet 60611			

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

Standpipes

Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)



Straight, L Series

0044	OD mm	To Suit Hose ID
BEL-06-DN05	6	3/16"
BEL-06-DN06	6	1/4"
BEL-08-DN05	8	3/16"
BEL-08-DN06	8	1/4"
BEL-08-DN08	8	5/16"
BEL-10-DN08	10	5/16"
BEL-10-DN10	10	3/8"
BEL-12-DN10	12	3/8"
BEL-12-DN12	12	1/2"
BEL-15-DN10	15	3/8"
BEL-15-DN12	15	1/2"
BEL-18-DN12	18	1/2"
BEL-18-DN16	18	5/8"
BEL-22-DN16	22	5/8"
BEL-22-DN19	22	3/4"
BEL-28-DN25	28	1"
BEL-35-DN31	35	1.1/4"
BEL-42-DN38	42	1.1/2"
Tech Sheet 60615		

Straight, S Series

0044	OD mm	To Suit Hose ID
BES-06-DN05	6	3/16"
BES-06-DN06	6	1/4"
BES-08-DN06	8	1/4"
BES-08-DN08	8	5/16"
BES-10-DN06	10	1/4"
BES-10-DN08	10	5/16"
BES-10-DN10	10	3/8"
BES-12-DN06	12	1/4"
BES-12-DN08	12	5/16"
BES-12-DN10	12	3/8"
BES-12-DN12	12	1/2"
BES-14-DN10	14	3/8"
BES-16-DN12	16	1/2"
BES-20-DN12	20	1/2"
BES-20-DN16	20	5/8"
BES-20-DN19	20	3/4"
BES-25-DN19	25	3/4"
BES-25-DN25	25	1"
BES-30-DN25	30	1"
BES-38-DN31	38	1.1/4"
Tech Sheet 60616		

Straight, Imperial

0044	OD	To Suit Hose ID
BE-14-DN06	1/4"	1/4"
BE-516-DN08	5/16"	5/16"
BE-38-DN10	3/8"	3/8"
BE-12-DN12	1/2"	1/2"
BE-58-DN16	5/8"	5/8"
BE-34-DN19	3/4"	3/4"
BE-1-DN25	1"	1"
BE-114-DN31	1.1/4"	1.1/4"
BE-112-DN38	1.1/2"	1.1/2"
Tech Sheet 60612		



Swept 90°, L Series

0044	OD mm	To Suit Hose ID
BEL-06-90-DN05	6	3/16"
BEL-06-90-DN06	6	1/4"
BEL-08-90-DN06	8	1/4"
BEL-10-90-DN06	10	1/4"
BEL-10-90-DN08	10	5/16"
BEL-10-90-DN10	10	3/8"
BEL-12-90-DN08	12	5/16"
BEL-12-90-DN10	12	3/8"
BEL-12-90-DN12	12	1/2"
BEL-15-90-DN12	15	1/2"
BEL-18-90-DN16	18	5/8"
BEL-22-90-DN19	22	3/4"
BEL-28-90-DN25	28	1"
BEL-35-90-DN31	35	1.1/4"
BEL-42-90-DN38	42	1.1/2"
Tech Sheet 60614		

Swept 90°, S Series

0044	OD mm	To Suit Hose ID
BES-06-90-DN05	6	3/16"
BES-06-90-DN06	6	1/4"
BES-08-90-DN06	8	1/4"
BES-10-90-DN06	10	1/4"
BES-10-90-DN08	10	5/16"
BES-10-90-DN10	10	3/8"
BES-12-90-DN08	12	5/16"
BES-12-90-DN10	12	3/8"
BES-14-90-DN10	14	3/8"
BES-16-90-DN12	16	1/2"
BES-20-90-DN16	20	5/8"
BES-25-90-DN19	25	3/4"
BES-30-90-DN25	30	1"
BES-38-90-DN31	38	1.1/4"
Tech Sheet 60614		



Swept 45°, L Series

0044	OD mm	To Suit Hose ID
BEL-06-45-DN05	6	3/16"
BEL-06-45-DN06	6	1/4"
BEL-08-45-DN06	8	1/4"
BEL-10-45-DN06	10	1/4"
BEL-10-45-DN08	10	5/16"
BEL-10-45-DN10	10	3/8"
BEL-12-45-DN08	12	5/16"
BEL-12-45-DN10	12	3/8"
BEL-15-45-DN12	15	1/2"
BEL-18-45-DN16	18	5/8"
BEL-22-45-DN19	22	3/4"
BEL-28-45-DN25	28	1"
BEL-35-45-DN31	35	1.1/4"
BEL-42-45-DN38	42	1.1/2"
Tech Sheet 60613		

Swept 45°, S Series

0044	OD mm	To Suit Hose ID
BES-06-45-DN05	6	3/16"
BES-06-45-DN06	6	1/4"
BES-08-45-DN06	8	1/4"
BES-10-45-DN06	10	1/4"
BES-10-45-DN08	10	5/16"
BES-10-45-DN10	10	3/8"
BES-12-45-DN08	12	5/16"
BES-14-45-DN10	14	3/8"
BES-16-45-DN12	16	1/2"
BES-20-45-DN16	20	5/8"
BES-25-45-DN19	25	3/4"
BES-30-45-DN25	30	1"
BES-38-45-DN31	38	1.1/4"
Tech Sheet 60613		

FT PRO



For **Hose & Assemblies**
see page **15**

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL INSERTS

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

SAE 3000 psi (3k)



Straight Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-DN12	1/2"	1/2"
SFL3-1/2-DN16	1/2"	5/8"
SFL3-3/4-DN12	3/4"	1/2"
SFL3-3/4-DN16	3/4"	5/8"
SFL3-3/4-DN19	3/4"	3/4"
SFL3-1-DN19	1"	3/4"
SFL3-1-DN25	1"	1"
SFL3-11/4-DN25	1.1/4"	1"
SFL3-11/4-DN31	1.1/4"	1.1/4"
SFL3-11/2-DN31	1.1/2"	1.1/4"
SFL3-11/2-DN38	1.1/2"	1.1/2"
SFL3-2-DN38	2"	1.1/2"
SFL3-2-DN51	2"	2"
Tech Sheet 60618		



90° Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-90-DN12	1/2"	1/2"
SFL3-1/2-90-DN16	1/2"	5/8"
SFL3-3/4-90-DN12	3/4"	1/2"
SFL3-3/4-90-DN16	3/4"	5/8"
SFL3-3/4-90-DN19	3/4"	3/4"
SFL3-1-90-DN19	1"	3/4"
SFL3-1-90-DN25	1"	1"
SFL3-114-90-DN25	1.1/4"	1"
SFL3-114-90-DN31	1.1/4"	1.1/4"
SFL3-112-90-DN31	1.1/2"	1.1/4"
SFL3-112-90-DN38	1.1/2"	1.1/2"
SFL3-2-90-DN38	2"	1.1/2"
SFL3-2-90-DN51	2"	2"
Tech Sheet 60620		



45° Flanges

0044	Flange ND	To Suit Hose ID
SFL3-1/2-45-DN12	1/2"	1/2"
SFL3-1/2-45-DN16	1/2"	5/8"
SFL3-3/4-45-DN12	3/4"	1/2"
SFL3-3/4-45-DN16	3/4"	5/8"
SFL3-3/4-45-DN19	3/4"	3/4"
SFL3-1-45-DN19	1"	3/4"
SFL3-1-45-DN25	1"	1"
SFL3-114-45-DN25	1.1/4"	1"
SFL3-114-45-DN31	1.1/4"	1.1/4"
SFL3-112-45-DN31	1.1/2"	1.1/4"
SFL3-112-45-DN38	1.1/2"	1.1/2"
SFL3-2-45-DN38	2"	1.1/2"
SFL3-2-45-DN51	2"	2"
Tech Sheet 60619		

SAE 6000 psi (6k)



Straight Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-DN12	1/2"	1/2"
SFS6-1/2-DN16	1/2"	5/8"
SFS6-3/4-DN12	3/4"	1/2"
SFS6-3/4-DN16	3/4"	5/8"
SFS6-3/4-DN19	3/4"	3/4"
SFS6-1-DN19	1"	3/4"
SFS6-1-DN25	1"	1"
SFS6-11/4-DN25	1.1/4"	1"
SFS6-11/4-DN31	1.1/4"	1.1/4"
SFS6-11/2-DN31	1.1/2"	1.1/4"
SFS6-11/2-DN38	1.1/2"	1.1/2"
SFS6-2-DN38	2"	1.1/2"
SFS6-2-DN51	2"	2"
Tech Sheet 60618		



90° Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-90-DN12	1/2"	1/2"
SFS6-1/2-90-DN16	1/2"	5/8"
SFS6-3/4-90-DN12	3/4"	1/2"
SFS6-3/4-90-DN16	3/4"	5/8"
SFS6-3/4-90-DN19	3/4"	3/4"
SFS6-1-90-DN19	1"	3/4"
SFS6-1-90-DN25	1"	1"
SFS6-114-90-DN25	1.1/4"	1"
SFS6-114-90-DN31	1.1/4"	1.1/4"
SFS6-112-90-DN31	1.1/2"	1.1/4"
SFS6-112-90-DN38	1.1/2"	1.1/2"
SFS6-2-90-DN38	2"	1.1/2"
SFS6-2-90-DN51	2"	2"
Tech Sheet 60620		



45° Flanges

0044	Flange ND	To Suit Hose ID
SFS6-1/2-45-DN12	1/2"	1/2"
SFS6-1/2-45-DN16	1/2"	5/8"
SFS6-3/4-45-DN12	3/4"	1/2"
SFS6-3/4-45-DN16	3/4"	5/8"
SFS6-3/4-45-DN19	3/4"	3/4"
SFS6-1-45-DN19	1"	3/4"
SFS6-1-45-DN25	1"	1"
SFS6-114-45-DN25	1.1/4"	1"
SFS6-114-45-DN31	1.1/4"	1.1/4"
SFS6-112-45-DN31	1.1/2"	1.1/4"
SFS6-112-45-DN38	1.1/2"	1.1/2"
SFS6-2-45-DN38	2"	1.1/2"
SFS6-2-45-DN51	2"	2"
Tech Sheet 60619		



Split Flanges

0044	Flange Size	Bolt Type Metric	Bolt Type UNC
FLH-3-1/2	1/2"	M8 x 25	5/16" x 1.1/4"
FLH-3-3/4	3/4"	M10 x 30	3/8" x 1.1/4"
FLH-3-1	1"	M10 x 30	3/8" x 1.1/4"
FLH-3-1.1/4	1.1/4"	M10 x 30	7/16" x 1.1/2"
FLH-3-1.1/2	1.1/2"	M12 x 35	1/2" x 1.1/2"
FLH-3-2	2"	M12 x 35	1/2" x 1.1/2"
Tech Sheet 60617			

Sold as a half, two halves required for each flange insert.

0044	Flange Size	Bolt Type Metric	Bolt Type UNC
FLH-6-1/2	1/2"	M8 x 30	5/16" x 1.1/4"
FLH-6-3/4	3/4"	M10 x 35	3/8" x 1.1/4"
FLH-6-1	1"	M12 x 45	-
FLH-6-1.1/4	1.1/4"	M14 x 50	-
FLH-6-1.1/2	1.1/2"	M16 x 55	5/8" x 2"
FLH-6-2	2"	M20 x 65	3/4" x 2.1/2"
Tech Sheet 60617			

Sold as a half, two halves required for each flange insert.

Bolts, washers and O-rings are not included and must be purchased separately

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series, BSPP (Captive Seal)

0291	OD mm	Thread
GE-6L-2EO	6	1/8"
GE-6L-4EO	6	1/4"
GE-6L-6EO	6	3/8"
GE-6L-8EO	6	1/2"
GE-8L-2EO	8	1/8"
GE-8L-4EO	8	1/4"
GE-8L-6EO	8	3/8"
GE-8L-8EO	8	1/2"
GE-10L-2EO	10	1/8"
GE-10L-4EO	10	1/4"
GE-10L-6EO	10	3/8"
GE-10L-8EO	10	1/2"
GE-10L-12EO	10	3/4"
GE-12L-2EO	12	1/8"
GE-12L-4EO	12	1/4"
GE-12L-6EO	12	3/8"
GE-12L-8EO	12	1/2"
GE-12L-12EO	12	3/4"
GE-15L-4EO	15	1/4"
GE-15L-6EO	15	3/8"
GE-15L-8EO	15	1/2"
GE-15L-12EO	15	3/4"
GE-15L-16EO	15	1"
GE-18L-6EO	18	3/8"
GE-18L-8EO	18	1/2"
GE-18L-12EO	18	3/4"
GE-18L-16EO	18	1"
GE-22L-6EO	22	3/8"
GE-22L-8EO	22	1/2"
GE-22L-12EO	22	3/4"
GE-22L-16EO	22	1"
GE-22L-20EO	22	1.1/4"
GE-28L-8EO	28	1/2"
GE-28L-12EO	28	3/4"
GE-28L-16EO	28	1"
GE-28L-20EO	28	1.1/4"
GE-28L-24EO	28	1.1/2"
GE-35L-12EO	35	3/4"
GE-35L-16EO	35	1"
GE-35L-20EO	35	1.1/4"
GE-35L-24EO	35	1.1/2"
GE-42L-16EO	42	1"
GE-42L-20EO	42	1.1/4"
GE-42L-24EO	42	1.1/2"
GE-42L-32EO	42	2"

Tech Sheet 10585

S Series, BSPP (Captive Seal)

0291	OD mm	Thread
GE-6S-2EO	6	1/8"
GE-6S-4EO	6	1/4"
GE-6S-6EO	6	3/8"
GE-6S-8EO	6	1/2"
GE-8S-2EO	8	1/8"
GE-8S-4EO	8	1/4"
GE-8S-6EO	8	3/8"
GE-8S-8EO	8	1/2"
GE-10S-2EO	10	1/8"
GE-10S-4EO	10	1/4"
GE-10S-6EO	10	3/8"
GE-10S-8EO	10	1/2"
GE-10S-12EO	10	3/4"
GE-12S-4EO	12	1/4"
GE-12S-6EO	12	3/8"
GE-12S-8EO	12	1/2"
GE-12S-12EO	12	3/4"
GE-14S-6EO	14	3/8"
GE-14S-8EO	14	1/2"
GE-14S-12EO	14	3/4"
GE-16S-4EO	16	1/4"
GE-16S-6EO	16	3/8"
GE-16S-8EO	16	1/2"
GE-16S-12EO	16	3/4"
GE-16S-16EO	16	1"
GE-20S-6EO	20	3/8"
GE-20S-8EO	20	1/2"
GE-20S-12EO	20	3/4"
GE-20S-16EO	20	1"
GE-20S-20EO	20	1.1/4"
GE-25S-8EO	25	1/2"
GE-25S-12EO	25	3/4"
GE-25S-16EO	25	1"
GE-25S-20EO	25	1.1/4"
GE-30S-12EO	30	3/4"
GE-30S-16EO	30	1"
GE-30S-20EO	30	1.1/4"
GE-30S-24EO	30	1.1/2"
GE-38S-16EO	38	1"
GE-38S-20EO	38	1.1/4"
GE-38S-24EO	38	1.1/2"

Tech Sheet 10585

L Series, Metric (Captive Seal)

0291	OD mm	Thread
GE-6L-10MEO	6	M10 x 1
GE-6L-12MEO	6	M12 x 1.5
GE-6L-14MEO	6	M14 x 1.5
GE-8L-10MEO	8	M10 x 1.0
GE-8L-12MEO	8	M12 x 1.5
GE-8L-14MEO	8	M14 x 1.5
GE-8L-16MEO	8	M16 x 1.5
GE-8L-18MEO	8	M18 x 1.5
GE-10L-10MEO	10	M10 x 1.0
GE-10L-12MEO	10	M12 x 1.5
GE-10L-14MEO	10	M14 x 1.5
GE-10L-16MEO	10	M16 x 1.5
GE-10L-18MEO	10	M18 x 1.5
GE-10L-22MEO	10	M22 x 1.5
GE-12L-12MEO	12	M12 x 1.5
GE-12L-14MEO	12	M14 x 1.5
GE-12L-16MEO	12	M16 x 1.5
GE-12L-18MEO	12	M18 x 1.5
GE-12L-22MEO	12	M22 x 1.5
GE-15L-16MEO	15	M16 x 1.5
GE-15L-18MEO	15	M18 x 1.5
GE-15L-22MEO	15	M22 x 1.5
GE-18L-18MEO	18	M18 x 1.5
GE-18L-22MEO	18	M22 x 1.5
GE-18L-26MEO	18	M26 x 1.5
GE-22L-22MEO	22	M22 x 1.5
GE-22L-26MEO	22	M26 x 1.5
GE-28L-33MEO	28	M33 x 2
GE-35L-42MEO	35	M42 x 2.0
GE-42L-48MEO	42	M48 x 2.0

Tech Sheet 10586

S Series, Metric (Captive Seal)

0291	OD mm	Thread
GE-6S-12MEO	6	M12 x 1.5
GE-6S-14MEO	6	M14 x 1.5
GE-8S-12MEO	8	M12 x 1.5
GE-8S-14MEO	8	M14 x 1.5
GE-8S-16MEO	8	M16 x 1.5
GE-10S-14MEO	10	M14 x 1.5
GE-10S-16MEO	10	M16 x 1.5
GE-10S-18MEO	10	M18 x 1.5
GE-12S-14MEO	12	M14 x 1.5
GE-12S-16MEO	12	M16 x 1.5
GE-12S-18MEO	12	M18 x 1.5
GE-12S-20MEO	12	M20 x 1.5
GE-12S-22MEO	12	M22 x 1.5
GE-14S-20MEO	14	M20 x 1.5
GE-14S-22MEO	14	M22 x 1.5
GE-16S-18MEO	16	M18 x 1.5
GE-16S-22MEO	16	M22 x 1.5
GE-20S-27MEO	20	M27 x 2
GE-25S-33MEO	25	M33 x 2
GE-30S-42MEO	30	M42 x 2
GE-38S-48MEO	38	M48 x 2

Tech Sheet 10586

For **Stainless Steel Bonded Seals** see pages **109-112**



Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series, BSPP, Form B Sealing

0291	OD mm	Thread
GE-6L-2RP	6	1/8"
GE-6L-4RP	6	1/4"
GE-6L-6RP	6	3/8"
GE-6L-8RP	6	1/2"
GE-8L-2RP	8	1/8"
GE-8L-4RP	8	1/4"
GE-8L-6RP	8	3/8"
GE-8L-8RP	8	1/2"
GE-10L-2RP	10	1/8"
GE-10L-4RP	10	1/4"
GE-10L-6RP	10	3/8"
GE-10L-8RP	10	1/2"
GE-10L-12RP	10	3/4"
GE-12L-2RP	12	1/8"
GE-12L-4RP	12	1/4"
GE-12L-6RP	12	3/8"
GE-12L-8RP	12	1/2"
GE-12L-12RP	12	3/4"
GE-15L-4RP	15	1/4"
GE-15L-6RP	15	3/8"
GE-15L-8RP	15	1/2"
GE-15L-12RP	15	3/4"
GE-18L-6RP	18	3/8"
GE-18L-8RP	18	1/2"
GE-18L-12RP	18	3/4"
GE-18L-16RP	18	1"
GE-22L-6RP	22	3/8"
GE-22L-8RP	22	1/2"
GE-22L-12RP	22	3/4"
GE-22L-16RP	22	1"
GE-22L-20RP	22	1.1/4"
GE-28L-8RP	28	1/2"
GE-28L-12RP	28	3/4"
GE-28L-16RP	28	1"
GE-28L-20RP	28	1.1/4"
GE-28L-24RP	28	1.1/2"
GE-35L-12RP	35	3/4"
GE-35L-16RP	35	1"
GE-35L-20RP	35	1.1/4"
GE-35L-24RP	35	1.1/2"
GE-42L-16RP	42	1"
GE-42L-20RP	42	1.1/4"
GE-42L-24RP	42	1.1/2"
Tech Sheet 20796		

S Series, BSPP, Form B Sealing

0291	OD mm	Thread
GE-6S-2RP	6	1/8"
GE-6S-4RP	6	1/4"
GE-6S-6RP	6	3/8"
GE-6S-8RP	6	1/2"
GE-8S-2RP	8	1/8"
GE-8S-4RP	8	1/4"
GE-8S-6RP	8	3/8"
GE-8S-8RP	8	1/2"
GE-10S-2RP	10	1/8"
GE-10S-4RP	10	1/4"
GE-10S-6RP	10	3/8"
GE-10S-8RP	10	1/2"
GE-10S-12RP	10	3/4"
GE-12S-4RP	12	1/4"
GE-12S-6RP	12	3/8"
GE-12S-8RP	12	1/2"
GE-12S-12RP	12	3/4"
GE-14S-4RP	14	1/4"
GE-14S-6RP	14	3/8"
GE-14S-8RP	14	1/2"
GE-14S-12RP	14	3/4"
GE-16S-4RP	16	1/4"
GE-16S-6RP	16	3/8"
GE-16S-8RP	16	1/2"
GE-16S-12RP	16	3/4"
GE-16S-16RP	16	1"
GE-20S-6RP	20	3/8"
GE-20S-8RP	20	1/2"
GE-20S-12RP	20	3/4"
GE-20S-16RP	20	1"
GE-20S-20RP	20	1.1/4"
GE-25S-8RP	25	1/2"
GE-25S-12RP	25	3/4"
GE-25S-16RP	25	1"
GE-25S-20RP	25	1.1/4"
GE-30S-12RP	30	3/4"
GE-30S-16RP	30	1"
GE-30S-20RP	30	1.1/4"
GE-30S-24RP	30	1.1/2"
GE-38S-16RP	38	1"
GE-38S-20RP	38	1.1/4"
GE-38S-24RP	38	1.1/2"
Tech Sheet 20796		

L Series, Metric Parallel, Form B Sealing

0291	OD mm	Thread
GE-6L-10MPB	6	M10 x 1
GE-6L-12MPB	6	M12 x 1.5
GE-6L-14MPB	6	M14 x 1.5
GE-8L-10MPB	8	M10 x 1.0
GE-8L-12MPB	8	M12 x 1.5
GE-8L-14MPB	8	M14 x 1.5
GE-8L-18MPB	8	M18 x 1.5
GE-8L-16MPB	8	M16 x 1.5
GE-10L-10MPB	10	M16 x 1.5
GE-10L-14MPB	10	M14 x 1.5
GE-10L-12MPB	10	M12 x 1.5
GE-10L-16MPB	10	M16 x 1.5
GE-10L-18MPB	10	M18 x 1.5
GE-10L-22MPB	10	M22 x 1.5
GE-12L-14MPB	12	M14 x 1.5
GE-12L-12MPB	12	M12 x 1.5
GE-12L-16MPB	12	M16 x 1.5
GE-12L-18MPB	12	M18 x 1.5
GE-12L-22MPB	12	M22 x 1.5
GE-15L-16MPB	15	M16 x 1.5
GE-15L-18MPB	15	M18 x 1.5
GE-15L-22MPB	15	M22 x 1.5
GE-18L-18MPB	18	M18 x 1.5
GE-18L-22MPB	18	M22 x 1.5
GE-18L-26MPB	18	M26 x 1.5
GE-22L-22MPB	22	M22 x 1.5
GE-22L-26MPB	22	M26 x 1.5
GE-28L-33MPB	28	M33 x 1.5
GE-35L-42MPB	35	M42 x 2
GE-42L-48MPB	42	M48 x 2
Tech Sheet 10587		

S Series, Metric Parallel, Form B Sealing

0291	OD mm	Thread
GE-6S-12MPB	6	M12 x 1.5
GE-6S-14MPB	6	M14 x 1.5
GE-8S-14MPB	8	M14 x 1.5
GE-10S-16MPB	10	M16 x 1.5
GE-10S-18MPB	10	M18 x 1.5
GE-12S-14MPB	12	M14 x 1.5
GE-12S-16MPB	12	M16 x 1.5
GE-12S-18MPB	12	M18 x 1.5
GE-12S-22MPB	12	M22 x 1.5
GE-14S-20MPB	14	M20 x 1.5
GE-16S-18MPB	16	M18 x 1.5
GE-16S-22MPB	16	M22 x 1.5
GE-20S-27MPB	20	M27 x 2
GE-25S-33MPB	25	M33 x 2
GE-30S-42MPB	30	M42 x 2
GE-38S-48MPB	38	M48 x 2
Tech Sheet 10587		

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Male Stud Couplings

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

L Series, BSPT

0291	OD mm	Thread
GE-6L-2RT	6	1/8"
GE-6L-4RT	6	1/4"
GE-6L-6RT	6	3/8"
GE-6L-8RT	6	1/2"
GE-8L-2RT	8	1/8"
GE-8L-4RT	8	1/4"
GE-8L-6RT	8	3/8"
GE-8L-8RT	8	1/2"
GE-10L-2RT	10	1/8"
GE-10L-4RT	10	1/4"
GE-10L-6RT	10	3/8"
GE-10L-8RT	10	1/2"
GE-12L-2RT	12	1/8"
GE-12L-4RT	12	1/4"
GE-12L-6RT	12	3/8"
GE-12L-8RT	12	1/2"
GE-12L-12RT	12	3/4"
GE-15L-4RT	15	1/4"
GE-15L-6RT	15	3/8"
GE-15L-8RT	15	1/2"
GE-15L-12RT	15	3/4"
GE-18L-6RT	18	3/8"
GE-18L-8RT	18	1/2"
GE-18L-12RT	18	3/4"
GE-22L-6RT	22	3/8"
GE-22L-8RT	22	1/2"
GE-22L-12RT	22	3/4"
GE-22L-16RT	22	1"
GE-28L-8RT	28	1/2"
GE-28L-12RT	28	3/4"
GE-28L-16RT	28	1"
GE-28L-20RT	28	1.1/4"
GE-35L-16RT	35	1"
GE-35L-20RT	35	1.1/4"
GE-35L-24RT	35	1.1/2"
GE-42L-20RT	42	1.1/4"
GE-42L-24RT	42	1.1/2"
Tech Sheet 10588		

S Series, BSPT

0291	OD mm	Thread
GE-6S-2RT	6	1/8"
GE-6S-4RT	6	1/4"
GE-6S-6RT	6	3/8"
GE-8S-2RT	8	1/8"
GE-8S-4RT	8	1/4"
GE-8S-6RT	8	3/8"
GE-10S-4RT	10	1/4"
GE-10S-6RT	10	3/8"
GE-12S-4RT	12	1/4"
GE-12S-6RT	12	3/8"
GE-12S-8RT	12	1/2"
GE-14S-6RT	14	3/8"
GE-14S-8RT	14	1/2"
GE-16S-6RT	16	3/8"
GE-16S-8RT	16	1/2"
GE-16S-12RT	16	3/4"
GE-20S-8RT	20	1/2"
GE-20S-12RT	20	3/4"
GE-25S-12RT	25	3/4"
GE-25S-16RT	25	1"
GE-30S-20RT	30	1.1/4"
GE-38S-24RT	38	1.1/2"
Tech Sheet 10588		



L Series, NPT

0291	OD mm	Thread
GE-6L-2N	6	1/8"
GE-6L-4N	6	1/4"
GE-6L-6N	6	3/8"
GE-6L-8N	6	1/2"
GE-8L-2N	8	1/8"
GE-8L-4N	8	1/4"
GE-8L-6N	8	3/8"
GE-8L-8N	8	1/2"
GE-10L-2N	10	1/8"
GE-10L-4N	10	1/4"
GE-10L-6N	10	3/8"
GE-10L-8N	10	1/2"
GE-10L-12N	10	3/4"
GE-12L-2N	12	1/8"
GE-12L-4N	12	1/4"
GE-12L-6N	12	3/8"
GE-12L-8N	12	1/2"
GE-12L-12N	12	3/4"
GE-15L-4N	15	1/4"
GE-15L-6N	15	3/8"
GE-15L-8N	15	1/2"
GE-15L-12N	15	3/4"
GE-18L-6N	18	3/8"
GE-18L-8N	18	1/2"
GE-18L-12N	18	3/4"
GE-18L-16N	18	1"
GE-22L-6N	22	3/8"
GE-22L-8N	22	1/2"
GE-22L-12N	22	3/4"
GE-22L-16N	22	1"
GE-22L-20N	22	1.1/4"
GE-28L-8N	28	1/2"
GE-28L-12N	28	3/4"
GE-28L-16N	28	1"
GE-28L-20N	28	1.1/4"
GE-35L-16N	35	1"
GE-35L-20N	35	1.1/4"
GE-35L-24N	35	1.1/2"
GE-42L-16N	42	1"
GE-42L-20N	42	1.1/4"
GE-42L-24N	42	1.1/2"
Tech Sheet 10589		

S Series, NPT

0291	OD mm	Thread
GE-6S-2N	6	1/8"
GE-6S-4N	6	1/4"
GE-6S-6N	6	3/8"
GE-6S-8N	6	1/2"
GE-8S-2N	8	1/8"
GE-8S-4N	8	1/4"
GE-8S-6N	8	3/8"
GE-8S-8N	8	1/2"
GE-10S-2N	10	1/8"
GE-10S-4N	10	1/4"
GE-10S-6N	10	3/8"
GE-10S-8N	10	1/2"
GE-10S-12N	10	3/4"
GE-12S-4N	12	1/4"
GE-12S-6N	12	3/8"
GE-12S-8N	12	1/2"
GE-12S-12N	12	3/4"
GE-14S-6N	14	3/8"
GE-14S-8N	14	1/2"
GE-14S-12N	14	3/4"
GE-16S-6N	16	3/8"
GE-16S-8N	16	1/2"
GE-16S-12N	16	3/4"
GE-16S-16N	16	1"
GE-20S-6N	20	3/8"
GE-20S-12N	20	3/4"
GE-20S-16N	20	1"
GE-20S-20N	20	1.1/4"
GE-25S-8N	25	1/2"
GE-25S-12N	25	3/4"
GE-25S-16N	25	1"
GE-25S-20N	25	1.1/4"
GE-30S-12N	30	3/4"
GE-30S-16N	30	1"
GE-30S-20N	30	1.1/4"
GE-30S-24N	30	1.1/2"
GE-38S-16N	38	1"
GE-38S-20N	38	1.1/4"
GE-38S-24N	38	1.1/2"
Tech Sheet 10589		

stainless steel



For **Stainless Steel Component parts** see page **1255**

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Male Stud Couplings



L Series, UNF, O-Ring Sealing

0291	OD mm	Thread
GE-6L-7/16UNF	6	7/16"
GE-6L-1/2UNF	6	1/2"
GE-6L-9/16UNF	6	9/16"
GE-8L-7/16UNF	8	7/16"
GE-8L-1/2UNF	8	1/2"
GE-8L-9/16UNF	8	9/16"
GE-10L-7/16UNF	10	7/16"
GE-10L-1/2UNF	10	1/2"
GE-10L-9/16UNF	10	9/16"
GE-10L-3/4UNF	10	3/4"
GE-12L-9/16UNF	12	9/16"
GE-12L-3/4UNF	12	3/4"
GE-12L-7/8UNF	12	7/8"
GE-15L-9/16UNF	15	9/16"
GE-15L-3/4UNF	15	3/4"
GE-15L-7/8UNF	15	7/8"
GE-18L-3/4UNF	18	3/4"
GE-18L-7/8UNF	18	7/8"
GE-18L-11/16UNF	18	1.1/16"
GE-22L-3/4UNF	22	3/4"
GE-22L-7/8UNF	22	7/8"
GE-22L-11/16UNF	22	1.1/16"
GE-22L-15/16UNF	22	1.5/16"
GE-28L-11/16UNF	28	1.1/16"
GE-28L-15/16UNF	28	1.5/16"
GE-28L-15/8UNF	28	1.5/8"
GE-35L-15/16UNF	35	1.5/16"
GE-35L-15/8UNF	35	1.5/8"
GE-42L-15/8UNF	42	1.5/8"
GE-42L-17/8UNF	42	1.7/8"
Tech Sheet 20797		

S Series, UNF, O-Ring Sealing

0291	OD mm	Thread
GE-6S-7/16UNF	6	7/16"
GE-8S-1/2UNF	8	1/2"
GE-8S-7/16UNF	8	7/16"
GE-8S-9/16UNF	8	9/16"
GE-10S-3/4UNF	10	3/4"
GE-12S-9/16UNF	12	9/16"
GE-12S-3/4UNF	12	3/4"
GE-12S-7/8UNF	12	7/8"
GE-14S-3/4UNF	14	3/4"
GE-16S-3/4UNF	16	3/4"
GE-16S-7/8UNF	16	7/8"
GE-16S-11/16UNF	16	1.1/16"
GE-20S-3/4UNF	20	3/4"
GE-20S-7/8UNF	20	7/8"
GE-20S-11/16UNF	20	1.1/16
GE-20S-15/16UNF	20	1.5/16"
GE-25S-11/16UNF	25	1.1/16
GE-25S-15/16UNF	25	1.5/16"
GE-30S-11/16UNF	30	1.1/16"
GE-30S-15/16UNF	30	1.5/16"
GE-30S-15/8UNF	30	1.5/8"
GE-38S-15/8UNF	38	1.5/8"
GE-38S-17/8UNF	38	1.7/8"

Female Stud Couplings



L Series, BSPP

0291	OD mm	Thread
GAI-6L-2RG	6	1/8"
GAI-6L-4RG	6	1/4"
GAI-6L-6RG	6	3/8"
GAI-6L-8RG	6	1/2"
GAI-8L-2RG	8	1/8"
GAI-8L-4RG	8	1/4"
GAI-8L-6RG	8	3/8"
GAI-8L-8RG	8	1/2"
GAI-10L-2RG	10	1/8"
GAI-10L-4RG	10	1/4"
GAI-10L-6RG	10	3/8"
GAI-10L-8RG	10	1/2"
GAI-12L-4RG	12	1/4"
GAI-12L-6RG	12	3/8"
GAI-12L-8RG	12	1/2"
GAI-15L-6RG	15	3/8"
GAI-15L-8RG	15	1/2"
GAI-15L-12RG	15	3/4"
GAI-18L-6RG	18	3/8"
GAI-18L-8RG	18	1/2"
GAI-18L-12RG	18	3/4"
GAI-22L-8RG	22	1/2"
GAI-22L-12RG	22	3/4"
GAI-28L-16RG	28	1"
GAI-35L-20RG	35	1.1/4"
GAI-42L-24RG	42	1.1/2"
Tech Sheet 10590		

S Series, BSPP

0291	OD mm	Thread
GAI-6S-4RG	6	1/4"
GAI-8S-4RG	8	1/4"
GAI-8S-6RG	8	3/8"
GAI-8S-8RG	8	1/2"
GAI-10S-6RG	10	3/8"
GAI-10S-8RG	10	1/2"
GAI-12S-4RG	12	1/4"
GAI-12S-6RG	12	3/8"
GAI-12S-8RG	12	1/2"
GAI-14S-6RG	14	3/8"
GAI-14S-8RG	14	1/2"
GAI-16S-6RG	16	3/8"
GAI-16S-8RG	16	1/2"
GAI-20S-8RG	20	1/2"
GAI-20S-12RG	20	3/4"
GAI-25S-12RG	25	3/4"
GAI-25S-16RG	25	1"
GAI-30S-20RG	30	1.1/4"
GAI-38S-24RG	38	1.1/2"

L Series, NPT

0291	OD mm	Thread
GAI-6L-2N	6	1/8"
GAI-6L-4N	6	1/4"
GAI-8L-4N	8	1/4"
GAI-10L-4N	10	1/4"
GAI-10L-6N	10	3/8"
GAI-10L-8N	10	1/2"
GAI-12L-4N	12	1/4"
GAI-12L-6N	12	3/8"
GAI-12L-8N	12	1/2"
GAI-15L-8N	15	1/2"
GAI-18L-8N	18	1/2"
GAI-22L-12N	22	3/4"
GAI-28L-16N	28	1"
GAI-35L-20N	35	1.1/4"
GAI-42L-24N	42	1.1/2"

S Series, NPT

0291	OD mm	Thread
GAI-6S-4N	6	1/4"
GAI-8S-4N	8	1/4"
GAI-10S-6N	10	3/8"
GAI-12S-6N	12	3/8"
GAI-12S-8N	12	1/2"
GAI-14S-8N	14	1/2"
GAI-16S-6N	16	3/8"
GAI-16S-8N	16	1/2"
GAI-20S-12N	20	3/4"
GAI-25S-16N	25	1"
GAI-30S-20N	30	1.1/4"
GAI-38S-24N	38	1.1/2"

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Straight Stud Standpipes

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series, BSPP (Captive Seal)

0291	OD mm	Thread
EVGE-6L-2EO	6	1/8"
EVGE-8L-4EO	8	1/4"
EVGE-8L-6EO	8	3/8"
EVGE-10L-4EO	10	1/4"
EVGE-10L-6EO	10	3/8"
EVGE-10L-8EO	10	1/2"
EVGE-12L-4EO	12	1/4"
EVGE-12L-6EO	12	3/8"
EVGE-12L-8EO	12	1/2"
EVGE-15L-6EO	15	3/8"
EVGE-15L-8EO	15	1/2"
EVGE-18L-6EO	18	3/8"
EVGE-18L-8EO	18	1/2"
EVGE-18L-12EO	18	3/4"
EVGE-22L-6EO	22	3/8"
EVGE-22L-8EO	22	1/2"
EVGE-22L-12EO	22	3/4"
EVGE-28L-12EO	28	3/4"
EVGE-28L-16EO	28	1"
EVGE-35L-20EO	35	1.1/4"
EVGE-42L-24EO	42	1.1/2"
Tech Sheet 10591		

S Series, BSPP (Captive Seal)

0291	OD mm	Thread
EVGE-6S-2EO	6	1/8"
EVGE-6S-4EO	6	1/4"
EVGE-8S-4EO	8	1/4"
EVGE-8S-6EO	8	3/8"
EVGE-10S-4EO	10	1/4"
EVGE-10S-6EO	10	3/8"
EVGE-10S-8EO	10	1/2"
EVGE-12S-4EO	12	1/4"
EVGE-12S-6EO	12	3/8"
EVGE-12S-8EO	12	1/2"
EVGE-14S-8EO	14	1/2"
EVGE-16S-6EO	16	3/8"
EVGE-16S-8EO	16	1/2"
EVGE-16S-12EO	16	3/4"
EVGE-20S-8EO	20	1/2"
EVGE-20S-12EO	20	3/4"
EVGE-25S-12EO	25	3/4"
EVGE-25S-16EO	25	1"
EVGE-30S-20EO	30	1.1/4"
EVGE-38S-24EO	38	1.1/2"
Tech Sheet 10591		

L Series, Metric Parallel (Captive Seal)

0291	OD mm	Thread
EVGE-6L-10MEO	6	M10 x 1
EVGE-8L-12MEO	8	M12 x 1.5
EVGE-10L-14MEO	10	M14 x 1.5
EVGE-15L-18MEO	15	M18 x 1.5
EVGE-18L-22MEO	18	M22 x 1.5
EVGE-22L-26MEO	22	M26 x 1.5
EVGE-28L-33MEO	28	M33 x 2
EVGE-35L-42MEO	35	M42 x 2
EVGE-42L-48MEO	42	M48 x 2
Tech Sheet 10592		

S Series, Metric Parallel (Captive Seal)

0291	OD mm	Thread
EVGE-6S-12MEO	6	M12 x 1.5
EVGE-8S-14MEO	8	M14 x 1.5
EVGE-10S-16MEO	10	M16 x 1.5
EVGE-12S-18MEO	12	M18 x 1.5
EVGE-14S-20MEO	14	M20 x 1.5
EVGE-16S-22MEO	16	M22 x 1.5
EVGE-20S-27MEO	20	M27 x 2
EVGE-30S-42MEO	30	M42 x 2
EVGE-38S-48MEO	38	M48 x 2
Tech Sheet 10592		

Reducing Adaptors



Male x Female, BSPP

0291	OD mm	Thread
GRI-2-4RG	1/8"	1/4"
GRI-2-6RG	1/8"	3/8"
GRI-4-2RG	1/4"	1/8"
GRI-4-6RG	1/4"	3/8"
GRI-4-8RG	1/4"	1/2"
GRI-4-12RG	1/4"	3/4"
GRI-6-4RG	3/8"	1/4"
GRI-6-8RG	3/8"	1/2"
GRI-6-12RG	3/8"	3/4"
GRI-6-16RG	3/8"	1"
GRI-8-6RG	1/2"	3/8"
GRI-8-12RG	1/2"	3/4"
GRI-8-16RG	1/2"	1"
GRI-8-20RG	1/2"	1.1/4"
GRI-12-8RG	3/4"	1/2"
GRI-12-16RG	3/4"	1"
GRI-12-20RG	3/4"	1.1/4"
GRI-12-24RG	3/4"	1.1/2"
GRI-16-12RG	1"	3/4"
GRI-16-20RG	1"	1.1/4"
GRI-16-24RG	1"	1.1/2"
GRI-20-16RG	1.1/4"	1"
GRI-24-20RG	1.1/2"	1.1/4"
GRI-20-24RG	1.1/4"	1.1/2"
Tech Sheet 10593		

Reducing Bush



Male x Female, BSPP

0291	OD mm	Thread
GRI-6-2RG	3/8"	1/8"
GRI-8-2RG	1/2"	1/8"
GRI-8-4RG	1/2"	1/4"
GRI-12-2RG	3/4"	1/8"
GRI-12-4RG	3/4"	1/4"
GRI-12-6RG	3/4"	3/8"
GRI-16-4RG	1"	1/4"
GRI-16-6RG	1"	3/8"
GRI-16-8RG	1"	1/2"
GRI-20-6RG	1.1/4"	3/8"
GRI-20-8RG	1.1/4"	1/2"
GRI-20-12RG	1.1/4"	3/4"
GRI-24-8RG	1.1/2"	1/2"
GRI-24-12RG	1.1/2"	3/4"
GRI-24-16RG	1.1/2"	1"
GRI-32-8RG	2"	1/2"
GRI-32-12RG	2"	3/4"
GRI-32-16RG	2"	1"
GRI-32-20RG	2"	1.1/4"
GRI-32-24RG	2"	1.1/2"
Tech Sheet 10593		

Adjustable Branch Tees



L Series, Metric, Female Thread

0291	OD mm	Thread
EVT-6L	6	M12 x 1.5
EVT-8L	8	M14 x 1.5
EVT-10L	10	M16 x 1.5
EVT-12L	12	M18 x 1.5
EVT-15L	15	M22 x 1.5
EVT-18L	18	M26 x 1.5
EVT-22L	22	M30 x 2
EVT-28L	28	M36 x 2
EVT-35L	35	M45 x 2
EVT-42L	42	M52 x 2
Tech Sheet 10594		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVT-6S	6	M14 x 1.5
EVT-8S	8	M16 x 1.5
EVT-10S	10	M18 x 1.5
EVT-12S	12	M20 x 1.5
EVT-14S	14	M22 x 1.5
EVT-16S	16	M24 x 1.5
EVT-20S	20	M30 x 2
EVT-25S	25	M36 x 2
EVT-30S	30	M42 x 2
EVT-38S	38	M52 x 2
Tech Sheet 10594		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Adjustable Run Tees



L Series, Metric, Female Thread

0291	OD mm	Thread
EVL-6L	6	M12 x 1.5
EVL-8L	8	M14 x 1.5
EVL-10L	10	M16 x 1.5
EVL-12L	12	M18 x 1.5
EVL-15L	15	M22 x 1.5
EVL-18L	18	M26 x 1.5
EVL-22L	22	M30 x 2
EVL-28L	28	M36 x 2
EVL-35L	35	M45 x 2
EVL-42L	42	M52 x 2
Tech Sheet 10597		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVL-6S	6	M14 x 1.5
EVL-8S	8	M16 x 1.5
EVL-10S	10	M18 x 1.5
EVL-12S	12	M20 x 1.5
EVL-14S	14	M22 x 1.5
EVL-16S	16	M24 x 1.5
EVL-20S	20	M30 x 2
EVL-25S	25	M36 x 2
EVL-30S	30	M42 x 2
EVL-38S	38	M52 x 2
Tech Sheet 10597		

stainless steel



For **Stainless Steel Tubing** see page **1287**

Male Stud Elbows



L Series, BSPT

0291	OD mm	Thread
WE6L-2RT	6	1/8"
WE6L-4RT	6	1/4"
WE6L-6RT	6	3/8"
WE6L-8RT	6	1/2"
WE8L-2RT	8	1/8"
WE8L-4RT	8	1/4"
WE8L-6RT	8	3/8"
WE8L-8RT	8	1/2"
WE10L-2RT	10	1/8"
WE10L-4RT	10	1/4"
WE10L-6RT	10	3/8"
WE10L-8RT	10	1/2"
WE12L-2RT	12	1/8"
WE12L-4RT	12	1/4"
WE12L-6RT	12	3/8"
WE12L-8RT	12	1/2"
WE15L-4RT	15	1/4"
WE15L-6RT	15	3/8"
WE15L-8RT	15	1/2"
WE15L-12RT	15	3/4"
WE18L-6RT	18	3/8"
WE18L-8RT	18	1/2"
WE18L-12RT	18	3/4"
WE22L-8RT	22	1/2"
WE22L-12RT	22	3/4"
WE28L-16RT	28	1"
WE35L-20RT	35	1.1/4"
Tech Sheet 10600		

S Series, BSPT

0291	OD mm	Thread
WE6S-2RT	6	1/8"
WE6S-4RT	6	1/4"
WE6S-6RT	6	3/8"
WE6S-8RT	6	1/2"
WE8S-4RT	8	1/4"
WE8S-6RT	8	3/8"
WE8S-8RT	8	1/2"
WE10S-4RT	10	1/4"
WE10S-6RT	10	3/8"
WE10S-8RT	10	1/2"
WE12S-4RT	12	1/4"
WE12S-6RT	12	3/8"
WE12S-8RT	12	1/2"
WE14S-6RT	14	3/8"
WE14S-8RT	14	1/2"
WE16S-6RT	16	3/8"
WE16S-8RT	16	1/2"
WE16S-12RT	16	3/4"
WE20S-8RT	20	1/2"
WE20S-12RT	20	3/4"
Tech Sheet 10600		

L Series, NPT

0291	OD mm	Thread
WE6L-2N	6	1/8"
WE6L-4N	6	1/4"
WE6L-6N	6	3/8"
WE6L-8N	6	1/2"
WE8L-2N	8	1/8"
WE8L-4N	8	1/4"
WE8L-6N	8	3/8"
WE8L-8N	8	1/2"
WE10L-2N	10	1/8"
WE10L-4N	10	1/4"
WE10L-8N	10	1/2"
WE12L-4N	12	1/4"
WE12L-6N	12	3/8"
WE12L-8N	12	1/2"
WE15L-6N	15	3/8"
WE15L-8N	15	1/2"
WE15L-12N	15	3/4"
WE18L-6N	18	3/8"
WE18L-8N	18	1/2"
WE18L-12N	18	3/4"
WE22L-8N	22	1/2"
WE22L-12N	22	3/4"
WE28L-12N	28	3/4"
WE28L-16N	28	1"
WE35L-20N	35	1.1/4"
WE42L-24N	42	1.1/2"
Tech Sheet 10601		

S Series, NPT

0291	OD mm	Thread
WE6S-4N	6	1/4"
WE6S-6N	6	3/8"
WE6S-8N	6	1/2"
WE8S-4N	8	1/4"
WE8S-6N	8	3/8"
WE8S-8N	8	1/2"
WE10S-4N	8	1/4"
WE10S-6N	10	3/8"
WE10S-8N	10	1/2"
WE12S-4N	12	1/4"
WE12S-6N	12	3/8"
WE12S-8N	12	1/2"
WE14S-6N	14	3/8"
WE14S-8N	14	1/2"
WE16S-6N	16	3/8"
WE16S-8N	16	1/2"
WE16S-12N	16	3/4"
WE20S-8N	20	1/2"
WE20S-12N	20	3/4"
WE25S-16N	25	1"
WE30S-20N	30	1.1/4"
WE38S-24N	38	1.1/2"
Tech Sheet 10601		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Adjustable Elbows



L Series, Metric, Female Thread

0291	OD mm	Thread
EVW-6L	6	M12 x 1.5
EVW-8L	8	M14 x 1.5
EVW-10L	10	M16 x 1.5
EVW-12L	12	M18 x 1.5
EVW-15L	15	M22 x 1.5
EVW-18L	18	M26 x 1.5
EVW-22L	22	M30 x 2
EVW-28L	28	M36 x 2
EVW-35L	35	M45 x 2
EVW-42L	42	M52 x 2
Tech Sheet 10602		

S Series, Metric, Female Thread

0291	OD mm	Thread
EVW-6S	6	M14 x 1.5
EVW-8S	8	M16 x 1.5
EVW-10S	10	M18 x 1.5
EVW-12S	12	M20 x 1.5
EVW-14S	14	M22 x 1.5
EVW-16S	16	M24 x 1.5
EVW-20S	20	M30 x 2
EVW-25S	25	M36 x 2
EVW-30S	30	M42 x 2
EVW-38S	38	M52 x 2
Tech Sheet 10602		

Straights



L Series

0291	OD mm
G6-UL	6
G8-UL	8
G10-UL	10
G12-UL	12
G15-UL	15
G18-UL	18
G22-UL	22
G28-UL	28
G35-UL	35
G42-UL	42
Tech Sheet 10605	

S Series

0291	OD mm
G6-US	6
G8-US	8
G10-US	10
G12-US	12
G14-US	14
G16-US	16
G20-US	20
G25-US	25
G30-US	30
G38-US	38
Tech Sheet 10605	

Straight Reducers



L Series

0291	OD mm	OD mm
GR-8L-6L	8	6
GR-10L-6L	10	6
GR-10L-8L	10	8
GR-12L-6L	12	6
GR-12L-8L	12	8
GR-12L-10L	12	10
GR-15L-6L	15	6
GR-15L-8L	15	8
GR-15L-10L	15	10
GR-15L-12L	15	12
GR-18L-8L	18	8
GR-18L-10L	18	10
GR-18L-12L	18	12
GR-18L-15L	18	15
GR-22L-8L	22	8
GR-22L-10L	22	10
GR-22L-12L	22	12
GR-22L-15L	22	15
GR-22L-18L	22	18
GR-28L-10L	28	10
GR-28L-12L	28	12
GR-28L-15L	28	15
GR-28L-18L	28	18
GR-28L-22L	28	22
GR-35L-15L	35	15
GR-35L-18L	35	18
GR-35L-22L	35	22
GR-35L-28L	35	28
GR-42L-15L	42	15
GR-42L-18L	42	18
GR-42L-22L	42	22
GR-42L-28L	42	28
GR-42L-35L	42	35
Tech Sheet 10606		

S Series

0291	OD mm	OD mm
GR-8S-6S	8	6
GR-10S-6S	10	6
GR-10S-8S	10	8
GR-12S-6S	12	6
GR-12S-8S	12	8
GR-12S-10S	12	10
GR-14S-6S	14	6
GR-14S-8S	14	8
GR-14S-10S	14	10
GR-14S-12S	14	12
GR-16S-6S	16	6
GR-16S-8S	16	8
GR-16S-10S	16	10
GR-16S-12S	16	12
GR-16S-14S	16	14
GR-20S-6S	20	6
GR-20S-8S	20	8
GR-20S-10S	20	10
GR-20S-12S	20	12
GR-20S-14S	20	14
GR-20S-16S	20	16
GR-25S-8S	25	8
GR-25S-10S	25	10
GR-25S-12S	25	12
GR-25S-14S	25	14
GR-25S-16S	25	16
GR-25S-20S	25	20
GR-30S-10S	30	10
GR-30S-12S	30	12
GR-30S-14S	30	14
GR-30S-16S	30	16
GR-30S-20S	30	20
GR-30S-25S	30	25
GR-38S-10S	38	10
GR-38S-12S	38	12
GR-38S-14S	38	14
GR-38S-16S	38	16
GR-38S-20S	38	20
GR-38S-25S	38	25
GR-38S-30S	38	30
Tech Sheet 10606		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Equal Elbows



L Series

0291	OD mm
W6-UEL	6
W8-UEL	8
W10-UEL	10
W12-UEL	12
W15-UEL	15
W18-UEL	18
W22-UEL	22
W28-UEL	28
W35-UEL	35
W42-UEL	42
Tech Sheet 10607	

S Series

0291	OD mm
W6-UES	6
W8-UES	8
W10-UES	10
W12-UES	12
W14-UES	14
W16-UES	16
W20-UES	20
W25-UES	25
W30-UES	30
W38-UES	38
Tech Sheet 10607	

Equal Tees



L Series

0291	OD mm
T6-UTL	6
T8-UTL	8
T10-UTL	10
T12-UTL	12
T15-UTL	15
T18-UTL	18
T22-UTL	22
T28-UTL	28
T35-UTL	35
T42-UTL	42
Tech Sheet 10608	

S Series

0291	OD mm
T6-UTS	6
T8-UTS	8
T10-UTS	10
T12-UTS	12
T14-UTS	14
T16-UTS	16
T20-UTS	20
T25-UTS	25
T30-UTS	30
T38-UTS	38
Tech Sheet 10608	

Equal Crosses



L Series

0291	OD mm
K6-UCL	6
K8-UCL	8
K10-UCL	10
K12-UCL	12
K15-UCL	15
K18-UCL	18
K22-UCL	22
K28-UCL	28
K35-UCL	35
K42-UCL	42
Tech Sheet 10609	

S Series

0291	OD mm
K6-UCS	6
K8-UCS	8
K10-UCS	10
K12-UCS	12
K14-UCS	14
K16-UCS	16
K20-UCS	20
K25-UCS	25
K30-UCS	30
K38-UCS	38
Tech Sheet 10609	

stainless steel

For **Stainless Steel Gauges** see page **1330**



316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Reducing Standpipes

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series

0291	OD mm	OD mm
KOR-8L-6L	8	6
KOR-10L-6L	10	6
KOR-10L-8L	10	8
KOR-12L-6L	12	6
KOR-12L-8L	12	8
KOR-12L-10L	12	10
KOR-15L-6L	15	6
KOR-15L-8L	15	8
KOR-15L-10L	15	10
KOR-15L-12L	15	12
KOR-18L-6L	18	6
KOR-18L-8L	18	8
KOR-18L-10L	18	10
KOR-18L-12L	18	12
KOR-18L-15L	18	15
KOR-22L-6L	22	6
KOR-22L-8L	22	8
KOR-22L-10L	22	10
KOR-22L-12L	22	12
KOR-22L-15L	22	15
KOR-22L-18L	22	18
KOR-28L-6L	28	6
KOR-28L-8L	28	8
KOR-28L-10L	28	10
KOR-28L-12L	28	12
KOR-28L-15L	28	15
KOR-28L-18L	28	18
KOR-28L-22L	28	22
KOR-35L-6L	35	6
KOR-35L-8L	35	8
KOR-35L-10L	35	10
KOR-35L-12L	35	12
KOR-35L-15L	35	15
KOR-35L-18L	35	18
KOR-35L-22L	35	22
KOR-35L-28L	35	28
KOR-42L-10L	42	10
KOR-42L-12L	42	12
KOR-42L-15L	42	15
KOR-42L-18L	42	18
KOR-42L-22L	42	22
KOR-42L-28L	42	28
KOR-42L-35L	42	35

Tech Sheet 10610

S Series

0291	OD mm	OD mm
KOR-8S-6S	8	6
KOR-10S-6S	10	6
KOR-10S-8S	10	8
KOR-12S-6S	12	6
KOR-12S-8S	12	8
KOR-12S-10S	12	10
KOR-14S-6S	14	6
KOR-14S-8S	14	8
KOR-14S-10S	14	10
KOR-14S-12S	14	12
KOR-16S-6S	16	6
KOR-16S-8S	16	8
KOR-16S-10S	16	10
KOR-16S-12S	16	12
KOR-16S-14S	16	14
KOR-20S-6S	20	6
KOR-20S-8S	20	8
KOR-20S-10S	20	10
KOR-20S-12S	20	12
KOR-20S-14S	20	14
KOR-20S-16S	20	16
KOR-25S-6S	25	6
KOR-25S-8S	25	8
KOR-25S-10S	25	10
KOR-25S-12S	25	12
KOR-25S-14S	25	14
KOR-25S-16S	25	16
KOR-25S-20S	25	20
KOR-30S-6S	30	6
KOR-30S-8S	30	8
KOR-30S-10S	30	10
KOR-30S-12S	30	12
KOR-30S-14S	30	14
KOR-30S-16S	30	16
KOR-30S-20S	30	20
KOR-30S-25S	30	25
KOR-38S-6S	38	6
KOR-38S-8S	38	8
KOR-38S-10S	38	10
KOR-38S-12S	38	12
KOR-38S-14S	38	14
KOR-38S-16S	38	16
KOR-38S-20S	38	20
KOR-38S-25S	38	25
KOR-38S-30S	38	30

Tech Sheet 10610



For **Stainless Steel Seals & Bonded washers** see page **110**

stainless steel



For **Stainless Steel Tube** see page **1287**

Fluid-Air Components Ltd


316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Tee Reducers

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series

0291	OD A mm	OD B mm	OD C mm
TR-6-8-6L	6	8	6
TR-6-10-6L	6	10	6
TR-8-6-8L	8	6	8
TR-8-10-8L	8	10	8
TR-8-12-8L	8	12	8
TR-10-6-10L	10	6	10
TR-10-8-10L	10	8	10
TR-10-10-6L	10	10	6
TR-10-12-10L	10	12	10
TR-10-15-10L	10	15	10
TR-12-6-12L	12	6	12
TR-12-8-8L	12	8	8
TR-12-8-12L	12	8	12
TR-12-10-10L	12	10	10
TR-12-10-12L	12	10	12
TR-12-12-10L	12	12	10
TR-12-15-12L	12	15	12
TR-12-18-12L	12	18	12
TR-15-6-15L	15	6	15
TR-15-10-15L	15	10	15
TR-15-12-12L	15	12	12
TR-15-12-15L	15	12	15
TR-15-15-12L	15	15	12
TR-18-10-10L	18	10	10
TR-18-10-18L	18	10	18
TR-18-12-18L	18	12	18
TR-18-15-18L	18	15	18
TR-18-18-10L	18	18	10
TR-22-10-22L	22	10	22
TR-22-12-22L	22	12	22
TR-22-15-15L	22	15	15
TR-22-15-22L	22	15	22
TR-22-18-18L	22	18	18
TR-22-18-22L	22	18	22
TR-22-22-18L	22	22	18
TR-28-10-28L	28	10	28
TR-28-12-28L	28	12	28
TR-28-15-28L	28	15	28
TR-28-18-28L	28	18	28
TR-28-22-22L	28	22	22
TR-28-22-28L	28	22	28
TR-28-35-28L	28	35	28
TR-35-12-35L	35	12	35
TR-35-15-35L	35	15	35
TR-35-18-35L	35	18	35
TR-35-22-35L	35	22	35
TR-35-28-35L	35	28	35
TR-35-42-35L	35	42	35
TR-42-15-42L	42	15	42
TR-42-18-42L	42	18	42
TR-42-22-42L	42	22	42
TR-42-28-42L	42	28	42
TR-42-35-42L	42	35	42

Tech Sheet 10611

S Series

0291	OD A mm	OD B mm	OD C mm
TR-8-6-8S	8	6	8
TR-10-6-10S	10	6	10
TR-10-8-10S	10	8	10
TR-12-6-12S	12	6	12
TR-12-8-8S	12	8	8
TR-12-8-12S	12	8	12
TR-12-10-12S	12	10	12
TR-12-16-12S	12	16	12
TR-14-8-14S	14	8	14
TR-14-10-14S	14	10	14
TR-16-6-16S	16	6	16
TR-16-8-16S	16	8	16
TR-16-10-16S	16	10	16
TR-16-12-16S	16	12	16
TR-16-14-16S	16	14	16
TR-16-20-16S	16	20	16
TR-20-8-20S	20	08	20
TR-20-10-20S	20	10	20
TR-20-12-20S	20	12	20
TR-20-14-20S	20	14	20
TR-20-16-20S	20	16	20
TR-20-25-20S	20	25	20
TR-25-10-25S	25	10	25
TR-25-12-25S	25	12	25
TR-25-14-25S	25	14	25
TR-25-16-25S	25	16	25
TR-25-20-25S	25	20	25
TR-25-30-25S	25	30	25
TR-30-12-30S	30	12	30
TR-30-16-30S	30	16	30
TR-30-20-30S	30	20	30
TR-30-25-30S	30	25	30
TR-30-38-30S	30	38	30
TR-38-16-38S	38	16	38
TR-38-20-38S	38	20	38
TR-38-25-38S	38	25	38
TR-38-30-38S	38	30	38

Tech Sheet 10611

Straight Bulkheads



L Series

0291	OD mm
SV-6L	6
SV-8L	8
SV-10L	10
SV-12L	12
SV-15L	15
SV-18L	18
SV-22L	22
SV-28L	28
SV-35L	35
SV-42L	42

Tech Sheet 10612

S Series

0291	OD mm
SV-6S	6
SV-8S	8
SV-10S	10
SV-12S	12
SV-14S	14
SV-16S	16
SV-20S	20
SV-25S	25
SV-30S	30
SV-38S	38

Tech Sheet 10612

Weld Bulkheads



L Series

0291	OD mm
ESV-6L-FT	6
ESV-8L-FT	8
ESV-10L-FT	10
ESV-12L-FT	12
ESV-15L-FT	15
ESV-18L-FT	18
ESV-20L-FT	20
ESV-28L-FT	28

Tech Sheet 10613

S Series

0291	OD mm
ESV-6S-FT	6
ESV-8S-FT	8
ESV-10S-FT	10
ESV-12S-FT	12
ESV-14S-FT	14
ESV-16S-FT	16
ESV-20S-FT	20
ESV-25S-FT	25

Tech Sheet 10613

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Bulkhead Elbows



L Series

0291	OD mm
WSV-6L-FT	6
WSV-8L-FT	8
WSV-10L-FT	10
WSV-12L-FT	12
WSV-15L-FT	15
WSV-18L-FT	18
WSV-22L-FT	22
WSV-28L-FT	28
WSV-35L-FT	35
WSV-42L-FT	42
Tech Sheet 10614	

S Series

0291	OD mm
WSV-6S-FT	6
WSV-8S-FT	8
WSV-10S-FT	10
WSV-12S-FT	12
WSV-14S-FT	14
WSV-16S-FT	16
WSV-20S-FT	20
WSV-25S-FT	25
WSV-30S-FT	30
WSV-38S-FT	38
Tech Sheet 10614	

Weld Nipples



O-Ring Sealing, Nitrile

0291	OD mm	Diameter mm
SKA-108	10	8
SKA-107	10	7
SKA-106	10	6
SKA-129	12	9
SKA-128	12	8
SKA-127	12	7
SKA-1613	16	13
SKA-1612	16	12
SKA-1611	16	11
SKA-1610	16	10
SKA-2016	20	16
SKA-2015	20	15
SKA-2014	20	14
SKA-2012	20	12
SKA-2519	25	19
SKA-2517	25	17
SKA-2515	25	15
Tech Sheet 10615		

Butt Weld Fittings



L Series

0291	OD mm
AS-6L	6
AS-8L	8
AS-10L	10
AS-12L	12
AS-15L	15
AS-18L	18
AS-22L	22
AS-28L	28
Tech Sheet 10616	

S Series

0291	OD mm
AS-6S	6
AS-8S	8
AS-10S	10
AS-12S	12
AS-14S	14
AS-16S	16
AS-20S	20
AS-25S	25
Tech Sheet 10616	



Weld Standpipe

0291	OD mm	Diameter mm
ASK-108	10	8
ASK-107	10	7
ASK-106	10	6
ASK-129	12	9
ASK-128	12	8
ASK-127	12	7
ASK-1612	16	12
ASK-1611	16	11
ASK-1610	16	10
ASK-2016	20	16
ASK-2015	20	15
ASK-2014	20	14
ASK-2012	20	12
ASK-2519	25	19
ASK-2517	25	17
ASK-2515	25	15
Tech Sheet 10617		

Special Weld Nipples (Reducers)



O-Ring Sealing, Nitrile

0291	OD mm	Diameter mm
SKAR-10-6	10	6
SKAR-10-8	10	8
SKAR-12-8	12	8
SKAR-12-10	12	10
SKAR-16-12	16	12
SKAR-20-12	20	12
SKAR-20-16	20	16
SKAR-25-16	25	16
SKAR-25-20	25	20
SKAR-25-15	25	15
Tech Sheet 10618		

Metric Standpipe Adaptors, BSPP



L Series

0291	Thread	OD mm
2101-8247	1/8"	6
2101-8254	1/4"	8
2101-8262	1/4"	10
2101-8270	3/8"	12
2101-8288	1/2"	15
2101-8296	1/2"	18
2101-8304	3/4"	22
2101-8312	1"	28
2101-8445	1.1/4"	35
2101-8338	1.1/2"	42
Tech Sheet 20799		

S Series

0291	Thread	OD mm
2101-8346	1/4"	6
2101-8353	1/4"	8
2101-8361	3/8"	10
2101-8379	3/8"	12
2101-8387	1/2"	14
2101-8395	1/2"	16
2101-8403	3/4"	20
2101-8411	1"	25
2101-8429	1.1/4"	30
2101-8437	1.1/2"	38
Tech Sheet 20799		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Gauge Couplings



L Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
MV-6L-4RG	6	1/4"
MV-6L-8RG	6	1/2"
MV-8L-4RG	8	1/4"
MV-8L-8RG	8	1/2"
MV-10L-4RG	10	1/4"
MV-10L-8RG	10	1/2"
MV-12L-4RG	12	1/4"
MV-12L-8RG	12	1/2"
Tech Sheet 20737		



L Series, NPT

0291	OD mm	Thread
MV-6L-4N	6	1/4"
MV-6L-8N	6	1/2"
MV-8L-4N	8	1/4"
MV-8L-8N	8	1/2"
MV-10L-4N	10	1/4"
MV-10L-8N	10	1/2"
MV-12L-4N	12	1/4"
MV-12L-8N	12	1/2"
Tech Sheet 20901		



S Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
MV-6S-8RG	6	1/2"
MV-8S-4RG	8	1/4"
MV-8S-8RG	8	1/2"
MV-10S-4RG	10	1/4"
MV-10S-8RG	10	1/2"
MV-12S-4RG	12	1/4"
MV-12S-8RG	12	1/2"
Tech Sheet 20737		



S Series, NPT

0291	OD mm	Thread
MV-6S-8N	6	1/2"
MV-8S-8N	8	1/2"
MV-10S-8N	10	1/2"
MV-12S-8N	12	1/2"
Tech Sheet 20901		


90° Compact Adjustable Elbows



L Series, Metric, BSPP Male Thread with Viton O-Ring

0291	OD mm	Thread
WEEV-06L-1/8	6	1/8"
WEEV-08L-1/4	8	1/4"
WEEV-10L-1/4	10	1/4"
WEEV-12L-3/8	12	3/8"
WEEV-15L-1/2	15	1/2"
WEEV-18L-1/2	18	1/2"
WEEV-22L-3/4	22	3/4"
WEEV-28L-1	28	1"
WEEV-35L-114	35	1.1/4"
Tech Sheet 67962		

stainless steel



For **Stainless Steel Clamps** see page **186**

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Non-return Valves

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

All valves supplied with 1 bar cracking pressure unless stated, other pressures available on request are 0.2, 0.5, 2.0 and 3.0

L Series, BSPP, Flow Towards Thread



0291	OD mm	Thread
RZ-6L-2RG	6	1/8"
RZ-8L-4RG	8	1/4"
RZ-10L-4RG	10	1/4"
RZ-12L-6RG	12	3/8"
RZ-15L-8RG	15	1/2"
RZ-18L-8RG	18	1/2"
RZ-22L-12RG	22	3/4"
RZ-28L-16RG	28	1"
RZ-35L-20RG	35	1.1/4"
RZ-42L-24RG	42	1.1/2"

Tech Sheet 20352

L Series, BSPP, Flow Away From Thread



0291	OD mm	Thread
RV-6L-2RG	6	1/8"
RV-8L-4RG	8	1/4"
RV-10L-4RG	10	1/4"
RV-12L-6RG	12	3/8"
RV-15L-8RG	15	1/2"
RV-18L-8RG	18	1/2"
RV-22L-12RG	22	3/4"
RV-28L-16RG	28	1"
RV-35L-20RG	35	1.1/4"
RV-42L-24RG	42	1.1/2"

Tech Sheet 20352

L Series, Tube x Tube



0291	OD mm	Cracking Pressure Bar
770-0606	6	0.5
770-0808	8	0.5
770-1010	10	0.5
770-1212	12	0.5
770-1515	15	0.5
770-1818	18	0.5
770-2222	22	0.5
770-2828	28	0.5
770-3535	35	0.5
770-4242	42	0.5

Tech Sheet 10619

S Series, BSPP, Flow Towards Thread

0291	OD mm	Thread
RZ-6S-2RG	6	1/8"
RZ-8S-4RG	8	1/4"
RZ-10S-4RG	10	1/4"
RZ-12S-6RG	12	3/8"
RZ-14S-8RG	14	1/2"
RZ-16S-8RG	16	1/2"
RZ-20S-12RG	20	3/4"
RZ-25S-16RG	25	1"
RZ-30S-20RG	30	1.1/4"
RZ-38S-24RG	38	1.1/2"

S Series, BSPP, Flow Away From Thread

0291	OD mm	Thread
RV-6S-2RG	6	1/8"
RV-8S-4RG	8	1/4"
RV-10S-4RG	10	1/4"
RV-12S-6RG	12	3/8"
RV-14S-8RG	14	1/2"
RV-16S-8RG	16	1/2"
RV-20S-12RG	20	3/4"
RV-25S-16RG	25	1"
RV-30S-20RG	30	1.1/4"
RV-38S-24RG	38	1.1/2"

S Series, Tube x Tube

0291	OD mm
RD-6S	6
RD-8S	8
RD-10S	10
RD-12S	12
RD-14S	14
RD-16S	16
RD-20S	20
RD-25S	25
RD-30S	30
RD-38S	38

Tech Sheet 10619

Blanking Plugs, Threaded



BSPP

0291	Thread
VSTI-2EO	1/8"
VSTI-4EO	1/4"
VSTI-6EO	3/8"
VSTI-8EO	1/2"
VSTI-12EO	3/4"
VSTI-16EO	1"
VSTI-20EO	1.1/4"
VSTI-24EO	1.1/2"

Tech Sheet 10620

Metric

0291	Thread
VSTI-10M	M10 x 1
VSTI-12M	M12 x 1.5
VSTI-14M	M14 x 1.5
VSTI-16M	M16 x 1.5
VSTI-18M	M18 x 1.5
VSTI-20M	M20 x 1.5
VSTI-22M	M22 x 1.5
VSTI-26M	M26 x 1.5
VSTI-27M	M27 x 2
VSTI-33M	M33 x 2
VSTI-42M	M42 x 2
VSTI-48M	M48 x 2

Tech Sheet 10620

Blanking Plugs



L Series

0291	OD mm
VKA-6L	6
VKA-8L	8
VKA-10L	10
VKA-12L	12
VKA-15L	15
VKA-18L	18
VKA-22L	22
VKA-28L	28
VKA-35L	35
VKA-42L	42

Tech Sheet 10621

S Series

0291	OD mm
VKA-6S	6
VKA-8S	8
VKA-10S	10
VKA-12S	12
VKA-14S	14
VKA-16S	16
VKA-20S	20
VKA-25S	25
VKA-30S	30
VKA-38S	38

Tech Sheet 10621

Blanking Ends



L Series

0291	OD mm
ROV-6L	6
ROV-8L	8
ROV-10L	10
ROV-12L	12
ROV-15L	15
ROV-18L	18
ROV-22L	22
ROV-28L	28
ROV-35L	35
ROV-42L	42

Tech Sheet 10622

S Series

0291	OD mm
ROV-6S	6
ROV-8S	8
ROV-10S	10
ROV-12S	12
ROV-14S	14
ROV-16S	16
ROV-20S	20
ROV-25S	25
ROV-30S	30
ROV-38S	38

Tech Sheet 10622

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Nut



L Series

0291	OD mm
M-6L-FT	6
M-8L-FT	8
M-10L-FT	10
M-12L-FT	12
M-15L-FT	15
M-18L-FT	18
M-22L-FT	22
M-28L-FT	28
M-35L-FT	35
M-42L-FT	42
Tech Sheet 10623	

S Series

0291	OD mm
M-6S-FT	6
M-8S-FT	8
M-10S-FT	10
M-12S-FT	12
M-14S-FT	14
M-16S-FT	16
M-20S-FT	20
M-25S-FT	25
M-30S-FT	30
M-38S-FT	38
Tech Sheet 10623	

Compression Ring

- Hardened, nickel plated.



L Series

0291	OD mm
DPR-6L	6
DPR-8L	8
DPR-10L	10
DPR-12L	12
DPR-15L	15
DPR-18L	18
DPR-22L	22
DPR-28L	28
DPR-35L	35
DPR-42L	42
Tech Sheet 10624	

S Series

0291	OD mm
DPR-6S	6
DPR-8S	8
DPR-10S	10
DPR-12S	12
DPR-14S	14
DPR-16S	16
DPR-20S	20
DPR-25S	25
DPR-30S	30
DPR-38S	38
Tech Sheet 10624	

stainless steel



For **Stainless Steel Tubing** see page **1287**

Fluid-Air Components Ltd

METRIC STAINLESS STEEL COMPRESSION FITTINGS

stainless steel

FTPRO

Stainless steel AISI 316L compression fittings.

The perfect solution for multiple applications and connections. Can be connected to several rigid metallic tubes in complete safety (stainless steel, brass, aluminium and copper) and can also be connected to plastic tubes (polyurethane, polyamide and Teflon).

Main Advantages:

- Complete range of fittings, suitable for all corrosive fluids and environments
- Made completely of AISI 316L stainless steel
- Good mechanical strength
- Sealing is guaranteed on different types of tube
- No sealing elements (elastomeric)
- 4-12mm diameters

Applications:

- Farming
- Chemical, petrochemical and pharmaceutical
- Medical and science
- Inkjet and printing
- Pneumatic and fluid automation
- Food and beverages
- Inert gases
- Heavy-duty pneumatic automation and tools
- Automotive

Male Studs



BSPT

0676	OD mm	Thread
69480-4-1/8	4	1/8"
69480-6-1/8	6	1/8"
69480-6-1/4	6	1/4"
69480-8-1/8	8	1/8"
69480-8-1/4	8	1/4"
69480-8-3/8	8	3/8"
69480-10-1/4	10	1/4"
69480-10-3/8	10	3/8"
69480-12-3/8	12	3/8"
69480-12-1/2	12	1/2"
Tech Sheet 68741		



BSPP

0676	OD mm	Thread
69485-4-1/8	4	1/8"
69485-6-1/8	6	1/8"
69485-6-1/4	6	1/4"
69485-8-1/8	8	1/8"
69485-8-1/4	8	1/4"
69485-8-3/8	8	3/8"
69485-10-1/4	10	1/4"
69485-10-3/8	10	3/8"
69485-12-3/8	12	3/8"
69485-12-1/2	12	1/2"
Tech Sheet 68741		

Male Stud Elbows



BSPT

0676	OD mm	Thread
69280-4-1/8	4	1/8"
69280-6-1/8	6	1/8"
69280-6-1/4	6	1/4"
69280-8-1/8	8	1/8"
69280-8-1/4	8	1/4"
69280-8-3/8	8	3/8"
69280-10-1/4	10	1/4"
69280-10-3/8	10	3/8"
69280-12-3/8	12	3/8"
69280-12-1/2	12	1/2"
Tech Sheet 68741		

Equal Elbows



Tube x Tube

0676	OD mm
69260-4	4
69260-6	6
69260-8	8
69260-10	10
69260-12	12
Tech Sheet 68741	

Equal Tees



Tube x Tube

0676	OD mm
69200-4	4
69200-6	6
69200-8	8
69200-10	10
69200-12	12
Tech Sheet 68741	

Male Stud Branch Tees



BSPT

0676	OD mm	Thread
69220-4-1/8	4	1/8"
69220-6-1/8	6	1/8"
69220-6-1/4	6	1/4"
69220-8-1/8	8	1/8"
69220-8-1/4	8	1/4"
69220-8-3/8	8	3/8"
69220-10-1/4	10	1/4"
69220-10-3/8	10	3/8"
69220-12-3/8	12	3/8"
69220-12-1/2	12	1/2"
Tech Sheet 68741		

Straight Connectors



Tube x Tube

0676	OD mm
69460-4	4
69460-6	6
69460-8	8
69460-10	10
69460-12	12
Tech Sheet 68741	

Nuts



Tube

0676	OD mm	Thread
69680-4	4	M8 x 1
69680-6	6	M10 x 1
69680-8	8	M12 x 1
69680-10	10	M16 x 1.5
69680-12	12	M18 x 1.5
Tech Sheet 68741		

Olives



Tube

0676	OD mm
69740-4	4
69740-6	6
69740-8	8
69740-10	10
69740-12	12
Tech Sheet 68741	

NB: safe pressures and temperatures depend entirely on the tubes being used.
For this reason, the values must be determined in accordance with the tube features.

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Technical details of ISO 8434-1 24° Fittings
Cone sealing couplings with 24° Cone and O-ring - FPM

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

There are several advantages to using DKO couplings:
- They are simple to assemble with low torque requirements.
- There is a wide variety of couplings to choose from.
- They are also easy to combine with each other.
- Additionally, DKO couplings have a super low leakage rate thanks to the O-ring sealing.

Straight Swivel Unions - DKO



L Series

0291	OD mm	Thread
GV-DKOL-06	6	M12 x 1.5
GV-DKOL-08	8	M 4 x 1.5
GV-DKOL-10	10	M16 x 1.5
GV-DKOL-12	12	M18 x 1.5
GV-DKOL-15	15	M22 x 1.5
GV-DKOL-18	18	M26 x 1.5
GV-DKOL-22	22	M30 x 2
GV-DKOL-28	28	M36 x 2
GV-DKOL-35	35	M45 x 2
GV-DKOL-42	42	M52 x 2
Tech Sheet 71713		

S Series

0291	OD mm	Thread
GV-DKOS-06	6	M14 x 1.5
GV-DKOS-08	8	M16 x 1.5
GV-DKOS-10	10	M18 x 1.5
GV-DKOS-12	12	M20 x 1.5
GV-DKOS-14	14	M22 x 1.5
GV-DKOS-16	16	M24 x 1.5
GV-DKOS-20	20	M30 x 2
GV-DKOS-25	25	M36 x 2
GV-DKOS-30	30	M42 x 2
GV-DKOS-38	38	M52 x 2
Tech Sheet 71713		

Straight Swivel Reducers - DKO



L/L Series

0291	OD mm	OD mm
GVR-DKO-08L/06L	8	6
GVR-DKO-10L/06L	10	6
GVR-DKO-10L/08L	10	8
GVR-DKO-12L/06L	12	6
GVR-DKO-12L/08L	12	8
GVR-DKO-12L/10L	12	10
GVR-DKO-15L/08L	15	8
GVR-DKO-15L/10L	15	10
GVR-DKO-15L/12L	15	12
GVR-DKO-18L/10L	18	10
GVR-DKO-18L/12L	18	12
GVR-DKO-18L/15L	18	15
GVR-DKO-22L/12L	22	12
GVR-DKO-22L/15L	22	15
GVR-DKO-22L/18L	22	18
GVR-DKO-28L/15L	28	15
GVR-DKO-28L/18L	28	18
GVR-DKO-28L/22L	28	22
GVR-DKO-35L/18L	35	18
GVR-DKO-35L/22L	35	22
GVR-DKO-35L/28L	35	28
GVR-DKO-42L/22L	42	22
GVR-DKO-42L/28L	42	28
GVR-DKO-42L/35L	42	35
Tech Sheet 71714		

S/S Series

0291	OD mm	OD mm
GVR-DKO-08S/06S	8	6
GVR-DKO-10S/06S	10	6
GVR-DKO-10S/08S	10	8
GVR-DKO-12S/06S	12	6
GVR-DKO-12S/08S	12	8
GVR-DKO-12S/10S	12	10
GVR-DKO-16S/10S	16	10
GVR-DKO-16S/12S	16	12
GVR-DKO-16S/14S	16	14
GVR-DKO-20S/12S	20	12
GVR-DKO-20S/14S	20	14
GVR-DKO-20S/16S	20	16
GVR-DKO-25S/16S	25	16
GVR-DKO-25S/20S	25	20
GVR-DKO-30S/16S	30	16
GVR-DKO-30S/20S	30	20
GVR-DKO-30S/25S	30	25
GVR-DKO-38S/20S	38	20
GVR-DKO-38S/25S	38	25
GVR-DKO-38S/30S	38	30
Tech Sheet 71714		

L/S Series

0291	OD mm	OD mm
GVR-DKO-06L/06S	6	6
GVR-DKO-08L/06S	8	6
GVR-DKO-08L/08S	8	8
GVR-DKO-10L/10S	10	10
GVR-DKO-12L/10S	12	10
GVR-DKO-12L/12S	12	12
GVR-DKO-15L/12S	15	12
GVR-DKO-15L/14S	15	14
GVR-DKO-18L/16S	18	16
GVR-DKO-22L/20S	22	20
GVR-DKO-28L/25S	28	25
GVR-DKO-35L/30S	35	30
GVR-DKO-42L/38S	42	38
Tech Sheet 71715		

S/L Series

0291	OD mm	OD mm
GVR-DKO-10S/08L	10	8
GVR-DKO-12S/08L	12	8
GVR-DKO-12S/10L	12	10
GVR-DKO-16S/10L	16	10
GVR-DKO-16S/12L	16	12
GVR-DKO-16S/15L	16	15
GVR-DKO-20S/18L	20	18
GVR-DKO-25S/18L	25	18
GVR-DKO-25S/22L	25	22
GVR-DKO-30S/28L	30	28
GVR-DKO-38S/35L	38	35
Tech Sheet 71715		

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Adjustable Elbows - DKO



L Series, Metric, Female Thread

0291	OD mm	Thread
EW-DKOL-06	6	M12 x 1,5
EW-DKOL-08	8	M14 x 1,5
EW-DKOL-10	10	M16 x 1,5
EW-DKOL-12	12	M18 x 1,5
EW-DKOL-15	15	M22 x 1,5
EW-DKOL-18	18	M26 x 1,5
EW-DKOL-22	22	M30 x 2
EW-DKOL-28	28	M36 x 2
EW-DKOL-35	35	M45 x 2
EW-DKOL-42	42	M52 x 2
Tech Sheet 71716		

S Series, Metric, Female Thread

0291	OD mm	Thread
EW-DKOS-06	6	M14 x 1,5
EW-DKOS-08	8	M16 x 1,5
EW-DKOS-10	10	M18 x 1,5
EW-DKOS-12	12	M20 x 1,5
EW-DKOS-14	14	M22 x 1,5
EW-DKOS-16	16	M24 x 1,5
EW-DKOS-20	20	M30 x 2
EW-DKOS-25	25	M36 x 2
EW-DKOS-30	30	M42 x 2
EW-DKOS-38	38	M52 x 2
Tech Sheet 71716		

45° Adjustable Elbows



L Series, Metric, BSPP Female Thread with Viton O-Ring

0291	OD mm	Thread
EV-DKOL-06	6	M12 x 1.5
EV-DKOL-08	8	M14 x 1.5
EV-DKOL-10	10	M16 x 1.5
EV-DKOL-12	12	M18 x 1.5
EV-DKOL-15	15	M22 x 1.5
EV-DKOL-18	18	M26 x 1.5
EV-DKOL-22	22	M30 x 2
EV-DKOL-28	28	M36 x 2
EV-DKOL-35	35	M45 x 2
EV-DKOL-42	42	M52 x 2
Tech Sheet 67963		

Adjustable Branch Tees - DKO



L Series, Metric, Female Thread

0291	OD mm	Thread
ET-DKOL-06	6	M12 x 1,5
ET-DKOL-08	8	M14 x 1,5
ET-DKOL-10	10	M16 x 1,5
ET-DKOL-12	12	M18 x 1,5
ET-DKOL-15	15	M22 x 1,5
ET-DKOL-18	18	M26 x 1,5
ET-DKOL-22	22	M30 x 2
ET-DKOL-28	28	M36 x 2
ET-DKOL-35	35	M45 x 2
ET-DKOL-42	42	M52 x 2
Tech Sheet 71717		

S Series, Metric, Female Thread

0291	OD mm	OD mm
ET-DKOS-06	6	M14 x 1,5
ET-DKOS-08	8	M16 x 1,5
ET-DKOS-10	10	M18 x 1,5
ET-DKOS-12	12	M20 x 1,5
ET-DKOS-14	14	M22 x 1,5
ET-DKOS-16	16	M24 x 1,5
ET-DKOS-20	20	M30 x 2
ET-DKOS-25	25	M36 x 2
ET-DKOS-30	30	M42 x 2
ET-DKOS-38	38	M52 x 2
Tech Sheet 71717		

Adjustable Run Tees - DKO



L Series, Metric, Female Thread

0291	OD mm	Thread
EL-DKOL-06	6	M12 x 1,5
EL-DKOL-08	8	M14 x 1,5
EL-DKOL-10	10	M16 x 1,5
EL-DKOL-12	12	M18 x 1,5
EL-DKOL-15	15	M22 x 1,5
EL-DKOL-18	18	M26 x 1,5
EL-DKOL-22	22	M30 x 2
EL-DKOL-28	28	M36 x 2
EL-DKOL-35	35	M45 x 2
EL-DKOL-42	42	M52 x 2
Tech Sheet 71718		

S Series, Metric, Female Thread

0291	OD mm	Thread
EL-DKOS-06	6	M14 x 1,5
EL-DKOS-08	8	M16 x 1,5
EL-DKOS-10	10	M18 x 1,5
EL-DKOS-12	12	M20 x 1,5
EL-DKOS-14	14	M22 x 1,5
EL-DKOS-16	16	M24 x 1,5
EL-DKOS-20	20	M30 x 2
EL-DKOS-25	25	M36 x 2
EL-DKOS-30	30	M42 x 2
EL-DKOS-38	38	M52 x 2
Tech Sheet 71718		

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Reducing Couplings - DKO

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature: -20°C to +200°C (FPM/Viton)



L Series

0291	OD mm	OD mm
RED-DKOL-08/06	8	6
RED-DKOL-10/06	10	6
RED-DKOL-10/08	10	8
RED-DKOL-12/06	12	6
RED-DKOL-12/08	12	8
RED-DKOL-12/10	12	10
RED-DKOL-15/06	15	6
RED-DKOL-15/08	15	8
RED-DKOL-15/10	15	10
RED-DKOL-15/12	15	12
RED-DKOL-18/06	18	6
RED-DKOL-18/08	18	8
RED-DKOL-18/10	18	10
RED-DKOL-18/12	18	12
RED-DKOL-18/15	18	15
RED-DKOL-22/06	22	6
RED-DKOL-22/08	22	8
RED-DKOL-22/10	22	10
RED-DKOL-22/12	22	12
RED-DKOL-22/15	22	15
RED-DKOL-22/18	22	18
RED-DKOL-28/06	28	6
RED-DKOL-28/08	28	8
RED-DKOL-28/10	28	10
RED-DKOL-28/12	28	12
RED-DKOL-28/15	28	15
RED-DKOL-28/18	28	18
RED-DKOL-28/22	28	22
RED-DKOL-35/06	35	6
RED-DKOL-35/08	35	8
RED-DKOL-35/10	35	10
RED-DKOL-35/12	35	12
RED-DKOL-35/15	35	15
RED-DKOL-35/18	35	18
RED-DKOL-35/22	35	22
RED-DKOL-35/28	35	28
RED-DKOL-42/06	42	6
RED-DKOL-42/08	42	8
RED-DKOL-42/10	42	10
RED-DKOL-42/12	42	12
RED-DKOL-42/15	42	15
RED-DKOL-42/18	42	18
RED-DKOL-42/22	42	22
RED-DKOL-42/28	42	28
RED-DKOL-42/35	42	35

Tech Sheet 71719

S Series

0291	OD mm	OD mm
RED-DKOS-08/06	8	6
RED-DKOS-10/06	10	6
RED-DKOS-10/08	10	8
RED-DKOS-12/06	12	6
RED-DKOS-12/08	12	8
RED-DKOS-12/10	12	10
RED-DKOS-14/06	14	6
RED-DKOS-14/08	14	8
RED-DKOS-14/10	14	10
RED-DKOS-14/12	14	12
RED-DKOS-16/06	16	6
RED-DKOS-16/08	16	8
RED-DKOS-16/10	16	10
RED-DKOS-16/12	16	12
RED-DKOS-16/14	16	14
RED-DKOS-20/06	20	6
RED-DKOS-20/08	20	8
RED-DKOS-20/10	20	10
RED-DKOS-20/12	20	12
RED-DKOS-20/14	20	14
RED-DKOS-20/16	20	16
RED-DKOS-25/06	25	6
RED-DKOS-25/08	25	8
RED-DKOS-25/10	25	10
RED-DKOS-25/12	25	12
RED-DKOS-25/14	25	14
RED-DKOS-25/16	25	16
RED-DKOS-25/20	25	20
RED-DKOS-30/06	30	6
RED-DKOS-30/08	30	8
RED-DKOS-30/10	30	10
RED-DKOS-30/12	30	12
RED-DKOS-30/14	30	14
RED-DKOS-30/16	30	16
RED-DKOS-30/20	30	20
RED-DKOS-30/25	30	25
RED-DKOS-38/06	38	6
RED-DKOS-38/08	38	8
RED-DKOS-38/10	38	10
RED-DKOS-38/12	38	12
RED-DKOS-38/14	38	14
RED-DKOS-38/16	38	16
RED-DKOS-38/20	38	20
RED-DKOS-38/25	38	25
RED-DKOS-38/30	38	30

Tech Sheet 71720

Swivel Female - Male, Connectors - DKO



L Series

0291	OD mm	Thread BSPP
EGE-DKO-06L-2EO	6	1/8"
EGE-DKO-06L-4EO	6	1/4"
EGE-DKO-06L-6EO	6	3/8"
EGE-DKO-08L-2EO	8	1/8"
EGE-DKO-08L-4EO	8	1/4"
EGE-DKO-08L-6EO	8	3/8"
EGE-DKO-08L-8EO	8	1/2"
EGE-DKO-10L-2EO	10	1/8"
EGE-DKO-10L-4EO	10	1/4"
EGE-DKO-10L-6EO	10	3/8"
EGE-DKO-10L-8EO	10	1/2"
EGE-DKO-12L-2EO	12	1/8"
EGE-DKO-12L-4EO	12	1/4"
EGE-DKO-12L-6EO	12	3/8"
EGE-DKO-12L-8EO	12	1/2"
EGE-DKO-15L-6EO	15	3/8"
EGE-DKO-15L-8EO	15	1/2"
EGE-DKO-15L-12EO	15	3/4"
EGE-DKO-18L-6EO	18	3/8"
EGE-DKO-18L-8EO	18	1/2"
EGE-DKO-18L-12EO	18	3/4"
EGE-DKO-22L-8EO	22	1/2"
EGE-DKO-22L-12EO	22	3/4"
EGE-DKO-22L-16EO	22	1"
EGE-DKO-28L-12EO	28	3/4"
EGE-DKO-28L-16EO	28	1"
EGE-DKO-35L-20EO	35	1.1/4"
EGE-DKO-42L-20EO	42	1.1/4"
EGE-DKO-42L-24EO	42	1.1/2"

Tech Sheet 71721

S Series

0291	OD mm	Thread BSPP
EGE-DKO-06S-4EO	6	1/4"
EGE-DKO-08S-4EO	8	1/4"
EGE-DKO-08S-6EO	8	3/8"
EGE-DKO-10S-4EO	10	1/4"
EGE-DKO-10S-6EO	10	3/8"
EGE-DKO-10S-8EO	10	1/2"
EGE-DKO-12S-4EO	12	1/4"
EGE-DKO-12S-6EO	12	3/8"
EGE-DKO-12S-8EO	12	1/2"
EGE-DKO-14S-8EO	14	1/2"
EGE-DKO-16S-6EO	16	3/8"
EGE-DKO-16S-8EO	16	1/2"
EGE-DKO-16S-12EO	16	3/4"
EGE-DKO-20S-8EO	20	1/2"
EGE-DKO-20S-12EO	20	3/4"
EGE-DKO-20S-16EO	20	1"
EGE-DKO-25S-12EO	25	3/4"
EGE-DKO-25S-16EO	25	1"
EGE-DKO-30S-16EO	30	1"
EGE-DKO-30S-20EO	30	1.1/4"
EGE-DKO-38S-24EO	38	1.1/2"

Tech Sheet 71721

Fluid-Air Components Ltd

316 STAINLESS STEEL DIN EN ISO 8434-1 TUBE FITTINGS (FORMERLY DIN 2353)

stainless steel

Stainless Steel 1.4571 Working Temperature: -60°C to +400°C (DIN 17 440, AD W 10)
Seal Working Temperature: -20°C to +200°C (FPM/Viton)

Banjo Elbows



LL Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-4LL-2EO-WDS	4	1/8"
WHV-6LL-2EO-WDS	6	1/8"
WHV-8LL-2EO-WDS	8	1/8"
Tech Sheet 71722		

L Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-06L-2EO-WDS	6	1/8"
WHV-08L-4EO-WDS	8	1/4"
WHV-10L-4EO-WDS	10	1/4"
WHV-10L-6EO-WDS	10	3/8"
WHV-12L-4EO-WDS	12	1/4"
WHV-12L-6EO-WDS	12	3/8"
WHV-12L-8EO-WDS	12	1/2"
WHV-15L-8EO-WDS	15	1/2"
WHV-18L-8EO-WDS	18	1/2"
WHV-22L-12EO-WDS	22	3/4"
WHV-28L-16EO-WDS	28	1"
WHV-35L-20EO-WDS	35	1.1/4"
WHV-42L-24EO-WDS	42	1.1/2"
Tech Sheet 71722		

S Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
WHV-06S-4EO-WDS	6	1/4"
WHV-08S-4EO-WDS	8	1/4"
WHV-10S-4EO-WDS	10	1/4"
WHV-10S-6EO-WDS	10	3/8"
WHV-12S-6EO-WDS	12	3/8"
WHV-14S-8EO-WDS	14	1/2"
WHV-16S-8EO-WDS	16	1/2"
WHV-20S-12EO-WDS	20	3/4"
WHV-25S-16EO-WDS	25	1"
WHV-30S-20EO-WDS	30	1.1/4"
WHV-38S-24EO-WDS	38	1.1/2"
Tech Sheet 71722		

Banjo Elbows



L Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
WHV-6L-2RG	6	1/8"
WHV-8L-4RG	8	1/4"
WHV-10L-4RG	10	1/4"
WHV-10L-6G	10	3/8"
WHV-12L-4RG	12	1/4"
WHV-12L-6RG	12	3/8"
WHV-12L-8RG	12	1/2"
WHV-15L-8RG	15	1/2"
WHV-18L-8RG	18	1/2"
WHV-22L-12RG	22	3/4"
WHV-28L-16RG	28	1"
WHV-35L-20RG	35	1.1/4"
WHV-42L-24RG	42	1.1/2"
Tech Sheet 20736		

S Series, BSPP, Metal Sealing Ring

0291	OD mm	Thread
WHV-6S-4RG	6	1/4"
WHV-8S-4RG	8	1/4"
WHV-10S-4RG	10	1/4"
WHV-10S-6G	10	3/8"
WHV-12S-6RG	12	3/8"
WHV-14S-8RG	14	1/2"
WHV-16S-8RG	16	1/2"
WHV-20S-12RG	20	3/4"
WHV-25S-16RG	25	1"
WHV-30S-20RG	30	1.1/4"
WHV-38S-24RG	38	1.1/2"
Tech Sheet 20736		

Banjo Tees



LL Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-4LL-2EO-WDS	4	1/8"
THV-6LL-2EO-WDS	6	1/8"
THV-8LL-2EO-WDS	8	1/8"
Tech Sheet 71723		

L Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-06L-2EO-WDS	6	1/8"
THV-08L-4EO-WDS	8	1/4"
THV-10L-4EO-WDS	10	1/4"
THV-12L-4EO-WDS	12	1/4"
THV-12L-6EO-WDS	12	3/8"
THV-15L-8EO-WDS	15	1/2"
THV-18L-8EO-WDS	18	1/2"
THV-22L-12EO-WDS	22	3/4"
THV-28L-16EO-WDS	28	1"
THV-35L-20EO-WDS	35	1.1/4"
THV-42L-24EO-WDS	42	1.1/2"
Tech Sheet 71723		

S Series, BSPP, WDS, Standard

0291	OD mm	Thread BSPP
THV-06S-4EO-WDS	6	1/4"
THV-08S-4EO-WDS	8	1/4"
THV-10S-4EO-WDS	10	1/4"
THV-10S-6EO-WDS	10	3/8"
THV-12S-6EO-WDS	12	3/8"
THV-14S-8EO-WDS	14	1/2"
THV-16S-8EO-WDS	16	1/2"
THV-20S-12EO-WDS	20	3/4"
THV-25S-16EO-WDS	25	1"
THV-30S-20EO-WDS	30	1.1/4"
THV-38S-24EO-WDS	38	1.1/2"
Tech Sheet 71723		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL COMPONENT PARTS

stainless steel

Seals



Banjo Couplings

0291	Thread
DKR-2RG	1/8"
DKR-4RG	1/4"
DKR-6RG	3/8"
DKR-8RG	1/2"
DKR-12RG	3/4"
DKR-16RG	1"
DKR-20RG	1.1/4"
DKR-24RG	1.1/2"



Gauge Couplings

0291	Thread
DKRI-4RG	1/4"
DKRI-8RG	1/2"



Viton

0291	Thread
WD-10X1	M10 x 1 (1/8")
WD-12X1.5	M12 x 1.5
WD-14X1.5	M14 x 1.5 (1/4")
WD-16X1.5	M16 x 1.5
WD-3/8	3/8"
WD-18X1.5	M18 x 1.5
WD-20X1.5	M20 x 1.5
WD-1/2	1/2"
WD-26X1.5	M26 x 1.5 (3/4")
WD-22X1.5	M22 x 1.5
WD-27X2	M27 x 2 (3/4")
WD-33X2	M33 x 2 (1")
WD-42X2	M42 x 2 (1.1/4")
WD-48X2	M48 x 2 (1.1/2")

One-Bite Cutting Rings - SPH Finish



LL Series Sealing Ring with SPH Finish

0291	OD mm
SR-LL-04/1 K-SPH	4
SR-LL-06/1 K-SPH	6
SR-LL-08/1 K-SPH	8
Tech Sheet 71724	

Double-Bite Cutting Rings - SPH Finish



L Series Sealing Ring with SPH Finish

0291	OD mm
SR-L-06/2 K-SPH	6
SR-L-08/2 K-SPH	8
SR-L-10/2 K-SPH	10
SR-L-12/2 K-SPH	12
SR-L-15/2 K-SPH	15
SR-L-18/2 K-SPH	18
SR-L-22/2 K-SPH	22
SR-L-28/2 K-SPH	28
SR-L-35/2 K-SPH	35
SR-L-42/2 K-SPH	42
Tech Sheet 71724	

S Series Sealing Ring with SPH Finish

0291	OD mm
SR-S-06/2 K-SPH	6
SR-S-08/2 K-SPH	8
SR-S-10/2 K-SPH	10
SR-S-12/2 K-SPH	12
SR-S-16/2 K-SPH	16
SR-S-20/2 K-SPH	20
SR-S-25/2 K-SPH	25
SR-S-30/2 K-SPH	30
SR-S-38/2 K-SPH	38
Tech Sheet 71724	

Soft Sealed Cutting Ring



L Series Sealing Ring with Viton Seal

0291	OD mm
ES4-L-06-WD	6
ES4-L-08-WD	8
ES4-L-10-WD	10
ES4-L-12-WD	12
ES4-L-15-WD	15
ES4-L-18-WD	18
ES4-L-22-WD	22
ES4-L-28-WD	28
ES4-L-35-WD	35
ES4-L-42-WD	42
Tech Sheet 67964	

S Series Sealing Ring with Viton Seal

0291	OD mm
ES4-S-06-WD	6
ES4-S-08-WD	8
ES4-S-10-WD	10
ES4-S-12-WD	12
ES4-S-14-WD	14
ES4-S-16-WD	16
ES4-S-20-WD	20
ES4-S-25-WD	25
ES4-S-30-WD	30
ES4-S-38-WD	38
Tech Sheet 67964	

Silver Plated Stainless Steel Nuts (AGP)

There is a high risk for cold welding (gripping) at the threads without silver-coating.

Together with ABF-grease easy assembly due to reduction in tightening torque by up to 70%.

Reduced torsion load to the coupling body.

Applications: Marine industry.



Light-duty

0294	Thread	OD mm
M18L-1.4571AGP	M26 x 1.5	18
M22L-1.4571AGP	M30 x 2	22
M28L-1.4571AGP	M36 x 2	28
M35L-1.4571AGP	M45 x 2	35

Heavy-duty

0294	Thread	OD mm
M20S-1.4571AGP	M30 x 2	20
M25S-1.4571AGP	M36 x 2	25
M30S-1.4571AGP	M42 x 2	30
M38S-1.4571AGP	M52 x 2	38

ABF Anti Bloc Grease

Special grease for the installation of stainless couplings, material 1.4571.

Applications: Marine industry.

To avoid gripping and reduce the coefficient of friction



1000g Can

0294	Grams
ANTI-BLOC 1KG	1000



100g Tube

0294	Grams
ANTI-BLOC 100G	100

Fluid-Air Components Ltd

INTRODUCING TWIN FERRULE TUBE COMPRESSION FITTINGS

stainless steel

PANAM


Panam Instrumentation tube fittings provide a zero leak proof seal which will withstand high pressure, impulse, vibration and temperature. These features offer high safety and maintenance free smooth working. Each component is precision machined to the most accurate tolerance; maintain TQM practices throughout manufacturing process.

The fittings are manufactured in accordance with ISO9001 quality standards and CE marking requirements with complete traceability records available upon request.

Available in 316 SS, Brass, CS, Monel materials in a variety of end connections. Straight fittings are machined from bar stock and shaped bodies are machined from forgings.

The fittings are used on instrumentation process control systems, analysers and environmental equipment in oil and gas, Petro-chemical, Power generation, Pulp and Paper industry and many more.

Functions



Compression nut Threads are silver plated which prevents galling.

Back Ferrule locks together the fittings and tube forms a primary Seal which absorbs the pressure pulses and vibration.

Front Ferrule Forms a secondary seal which connects tube and fitting and guarantees a bubble tight Zero Leak Sealing.

Rugged body construction, high precision machined surface and standardised tolerances provides maximum trouble free service life in severe working conditions.

The above illustrates sealing action of a Tube Fitting assembly which takes place after the assembly is fully tightened

Assembly Instructions

SIZE M6 thru M25 (6mm-25mm)



1-1/4 Turns from Finger Tight

SIZE M3 thru M4 (3mm-4mm)




Only 3/4 Turn from Finger Tight is necessary to seal and will result in additional remakes of the fitting

1 Insert the tubing in to the Tube Fitting until it comes up to the tube stop.

2 Ensure that the nut is finger tight and tighten the nut 1-1/4 turns as shown in figure.

3 For 1/8" and 3/16 Fittings only 3/4 turns as shown in Fig-3.

Identification of Twin Ferrule Fittings



Metric Tube End with Stepped Shoulder on Nut and Fitting

Imperial Tube End

The Metric size of the Fittings have extra stepped shoulder on the body and nut to distinguish them from imperial size.

All Dimensions are in mm unless otherwise stated. Dimensions are for reference only, subject to change.

Material Standards

Material	Bar Stock a	Forging b	Tubing
316 Stainless Steel	ASTM A276 ASME SA479	ASTM A182 ASME SA182	ASME-SA-213 / ASTM-A-213/ ASTM-A-249 / ASTM-A-269 / MIL T-88504 / MIL T-8506
Brass	ASTRM B16	ASTM B283	ASTM-B75 / ASME-SB75 (TEMPER "O")
Alloy 400	ASTM B164 ASMESB164	ASTM B564 ASME SB564	
Alloy 600	ASTM B166 ASME SB166	ASTM B564 ASME SB564	ASTM-B-163
Alloy C-276	ASTM B574	ASTM SB564	ASTM-B-622 / ASTM-B-626
Carbon Steel	ASTM A108		SAE J524b / SAE J525b / ASTM-A-179
PTFE	ASTM D1710	ASTM D3293	

A includes straight configuration **B** includes all elbows, crosses and tees

Stress Values based on ASME B31.3 Code for Process Piping

Material	Allowable Stress Value Psig	Allowable Stress Value bar	Design Factor	Ultimate Tensile Strength Psig	Ultimate Tensile Strength bar
316SS	20000	1378	3.75:1	75000	5170
Brass	10000	689	4:1	40000	2760
Steel	20000	1378	3:1	60000	4140

Pipe End Pressure Ratings

Calculations based on ASME B31.3 code for Process Piping

NPT/ISO Pipe Size Inches	316 SS and Carbon Steel Male Psig	316 SS and Carbon Steel Male bar	316 SS and Carbon Steel Female Psig	316 SS and Carbon Steel Female bar	Brass Male Psig	Brass Male bar	Brass Female Psig	Brass Female bar
1/16	11000	760	6700	460	5500	380	3300	230
1/8	10000	690	6500	440	5000	340	3200	220
1/4	8000	550	6600	450	4000	270	3300	220
S3/8	7800	540	5300	360	3900	270	2600	180
1/2	7700	530	4900	330	3800	260	2400	160
3/4	7300	500	4600	320	3600	250	2300	160
1	5300	370	4400	300	2600	180	2200	150
1.1/4	6000	410	5000	350	3000	200	2500	170
1.1/2	5000	340	4600	310	2500	170	2300	150
2	3900	270	3900	270	1900	130	1900	130

To determine working pressure ratings in accordance with ASME B31.1 Power Piping For 316 stainless steel, multiply psig by 0.94; for carbon steel multiply psig by 0.75; Brass ratings remain the same. To determine working pressure kPa multiply psig by 6.89

SAE Pressure Ratings

Pressure Ratings are from SAE J1926/3

SAE/MS Thread Size	316 SS and Carbon Steel (Nonpositionable) Psig	316 SS and Carbon Steel (Nonpositionable) bar	316 SS and Carbon Steel (Positionable) Psig	316 SS and Carbon Steel (Positionable) bar
5/16-24	4568	315	4568	315
7/16-20				
1/2-20				
9/16-18			3626	250
3/4-16				
7/8-14	3626	250	2900	200
1.1/16-12				
1.3/16-12	2900	200	2320	160
1.5/16-12				
1.5/8-12	2320	160	1813	125
1.7/8-12				
1.1/2-12	1813	125	1450	100

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Connectors



Male Thread, NPT

0292	OD	Thread
MC-125-125N	1/8"	1/8"
MC-125-250N	1/8"	1/4"
MC-125-375N	1/8"	3/8"
MC-125-500N	1/8"	1/2"
MC-187-125N	3/16"	1/8"
MC-187-250N	3/16"	1/4"
MC-250-125N	1/4"	1/8"
MC-250-250N	1/4"	1/4"
MC-250-375N	1/4"	3/8"
MC-250-500N	1/4"	1/2"
MC-250-750N	1/4"	3/4"
MC-312-125N	5/16"	1/8"
MC-312-250N	5/16"	1/4"
MC-312-375N	5/16"	3/8"
MC-312-500N	5/16"	1/2"
MC-375-125N	5/16"	1/8"
MC-375-250N	3/8"	1/4"
MC-375-375N	3/8"	3/8"
MC-375-500N	3/8"	1/2"
MC-375-750N	3/8"	3/4"
MC-500-125N	1/2"	1/8"
MC-500-250N	1/2"	1/4"
MC-500-375N	1/2"	3/8"
MC-500-500N	1/2"	1/2"
MC-500-750N	1/2"	3/4"
MC-500-1000N	1/2"	1"
MC-625-375N	5/8"	3/8"
MC-625-500N	5/8"	1/2"
MC-625-750N	5/8"	3/4"
MC-750-500N	3/4"	1/2"
MC-750-750N	3/4"	3/4"
MC-750-1000N	3/4"	1"
MC-875-750N	7/8"	3/4"
MC-875-1000N	7/8"	1"
MC-1000-500N	1"	1/2"
MC-1000-750N	1"	3/4"
MC-1000-1000N	1"	1"
Tech Sheet 20234		



Male Thread, BSPT

0292	OD	Thread
MC-125-125RT	1/8"	1/8"
MC-125-250RT	1/8"	1/4"
MC-250-125RT	1/4"	1/8"
MC-250-250RT	1/4"	1/4"
MC-250-375RT	1/4"	3/8"
MC-250-500RT	1/4"	1/2"
MC-312-125RT	5/16"	1/8"
MC-312-250RT	5/16"	1/4"
MC-375-125RT	3/8"	1/8"
MC-375-250RT	3/8"	1/4"
MC-375-375RT	3/8"	3/8"
MC-375-500RT	3/8"	1/2"
MC-500-250RT	1/2"	1/4"
MC-500-375RT	1/2"	3/8"
MC-500-500RT	1/2"	1/2"
MC-500-750RT	1/2"	3/4"
MC-750-750RT	3/4"	3/4"
MC-1000-1000RT	1"	1"
Tech Sheet 20233		



Male Thread, SAE/MS

0292	OD	Thread
MC-125-312SE	1/8"	5/16"-24
MC-125-562SE	1/8"	9/16"-18
MC-250-437SE	1/4"	7/16"-20
MC-250-750SE	1/4"	3/4"-16
MC-250-875SE	1/4"	7/8"-14
MC-312-500SE	5/16"	1/2"-20
MC-375-437SE	3/8"	7/16"-20
MC-375-562SE	3/8"	9/16"-18
MC-375-750SE	3/8"	3/4"-16
MC-375-875SE	3/8"	7/8"-14
MC-500-562SE	1/2"	9/16"-18
MC-500-750SE	1/2"	3/4"-16
MC-500-875SE	1/2"	7/8"-14
MC-500-1062SE	1/2"	1.1/16"-12
MC-625-750SE	5/8"	3/4"-16
MC-625-875SE	5/8"	7/8"-14
MC-750-750SE	3/4"	3/4"-16
MC-750-1062SE	3/4"	1.1/16"-12
MC-875-1187SE	7/8"	1.3/16"-12
MC-1000-1062SE	1"	1.1/16"-12
MC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20807		



Male Thread, SAE/MS (Long)

0292	OD	Thread
LMC-250-437SE	1/4"	7/16"-20
LMC-312-500SE	5/16"	1/2"-20
LMC-375-562SE	3/8"	9/16"-18
LMC-500-750SE	1/2"	3/4"-16
LMC-625-875SE	5/8"	7/8"-14
LMC-750-1062SE	3/4"	1.1/16"-12
LMC-875-1187SE	7/8"	1.3/16"-12
LMC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20808		



Male Thread, SAE/MS (Captive Seal)

0292	OD	Thread
OMC-125-312SE	1/8"	5/16"-24
OMC-187-375SE	3/16"	3/8"-24
OMC-250-437SE	1/4"	7/16"-20
OMC-312-500SE	5/16"	1/2"-20
OMC-375-562SE	3/8"	9/16"-18
OMC-500-750SE	1/2"	3/4"-16
OMC-750-1062SE	3/4"	1.1/16"-12
OMC-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20809		

Male Thread, BSPP (Captive Seal)

0292	OD	Thread
OMC-250-250EO	1/4"	1/4"
OMC-250-500EO	1/4"	1/2"
OMC-375-375EO	3/8"	3/8"
OMC-500-250EO	1/2"	1/4"
OMC-500-375EO	1/2"	3/8"
OMC-500-500EO	1/2"	1/2"
OMC-750-750EO	3/4"	3/4"
Tech Sheet 20809		

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Connectors

Stainless steel washer with a Viton inner ring.



Male Thread-RS, BSPP

0292	OD	Thread
MC-125-125RS	1/8"	1/8"
MC-125-250RS	1/8"	1/4"
MC-125-375RS	1/8"	3/8"
MC-250-125RS	1/4"	1/8"
MC-250-250RS	1/4"	1/4"
MC-250-375RS	1/4"	3/8"
MC-250-500RS	1/4"	1/2"
MC-375-250RS	3/8"	1/4"
MC-375-375RS	3/8"	3/8"
MC-375-500RS	3/8"	1/2"
MC-500-250RS	1/2"	1/4"
MC-500-375RS	1/2"	3/8"
MC-500-500RS	1/2"	1/2"
MC-750-500RS	3/4"	1/2"
MC-750-750RS	3/4"	3/4"
MC-1000-500RS	1"	1/2"
MC-1000-1000RS	1"	1"
Tech Sheet 20810		

Female Connectors



Female Thread, NPT

0292	OD	Thread
FC-125-125N	1/8"	1/8"
FC-125-250N	1/8"	1/4"
FC-187-125N	3/16"	1/8"
FC-250-125N	1/4"	1/8"
FC-250-250N	1/4"	1/4"
FC-250-375N	1/4"	3/8"
FC-250-500N	1/4"	1/2"
FC-312-125N	5/16"	1/8"
FC-312-250N	5/16"	1/4"
FC-312-375N	5/16"	3/8"
FC-375-125N	3/8"	1/8"
FC-375-250N	3/8"	1/4"
FC-375-375N	3/8"	3/8"
FC-375-500N	3/8"	1/2"
FC-375-750N	3/8"	3/4"
FC-500-250N	1/2"	1/4"
FC-500-375N	1/2"	3/8"
FC-500-500N	1/2"	1/2"
FC-500-750N	1/2"	3/4"
FC-625-375N	5/8"	3/8"
FC-625-500N	5/8"	1/2"
FC-625-750N	5/8"	3/4"
FC-750-500N	3/4"	1/2"
FC-750-750N	3/4"	3/4"
FC-875-750N	7/8"	3/4"
FC-1000-750N	1"	3/4"
FC-1000-1000N	1"	1"
Tech Sheet 20235		

Female Thread, BSPT

0292	OD	Thread
FC-250-125RT	1/4"	1/8"
FC-250-250RT	1/4"	1/4"
FC-250-375RT	1/4"	3/8"
FC-250-500RT	1/4"	1/2"
FC-375-250RT	3/8"	1/4"
FC-375-375RT	3/8"	3/8"
FC-375-500RT	3/8"	1/2"
FC-500-250RT	1/2"	1/4"
FC-500-375RT	1/2"	3/8"
FC-500-500RT	1/2"	1/2"
Tech Sheet 20237		

Female Thread, BSPP

0292	OD	Thread
FC-250-250RG	1/4"	1/4"
FC-250-375RG	1/4"	3/8"
FC-250-500RG	1/4"	1/2"
FC-312-250RG	5/16"	1/4"
FC-312-500RG	5/16"	1/2"
FC-375-250RG	3/8"	1/4"
FC-375-375RG	3/8"	3/8"
FC-375-500RG	3/8"	1/2"
FC-500-375RG	1/2"	3/8"
FC-500-500RG	1/2"	1/2"
Tech Sheet 20236		


Bulkhead Male Connectors



Male Thread, NPT

0292	OD	Thread
BMC-125-125N	1/8"	1/8"
BMC-187-125N	3/16"	1/8"
BMC-250-125N	1/4"	1/8"
BMC-250-250N	1/4"	1/4"
BMC-250-375N	1/4"	3/8"
BMC-250-500N	1/4"	1/2"
BMC-312-125N	5/16"	1/8"
BMC-312-250N	5/16"	1/4"
BMC-375-125N	3/8"	1/8"
BMC-375-250N	3/8"	1/4"
BMC-375-375N	3/8"	3/8"
BMC-500-250N	1/2"	1/4"
BMC-500-375N	1/2"	3/8"
BMC-500-500N	1/2"	1/2"
BMC-500-750N	1/2"	3/4"
BMC-625-375N	5/8"	3/8"
BMC-625-500N	5/8"	1/2"
BMC-750-500N	3/4"	1/2"
BMC-750-750N	3/4"	3/4"
BMC-875-750N	7/8"	3/4"
BMC-1000-750N	1"	3/4"
Tech Sheet 20814		

Bulkhead Female Connectors



Female Thread, NPT

0292	OD	Thread
BFC-125-125N	1/8"	1/8"
BFC-187-125N	3/16"	1/8"
BFC-250-125N	1/4"	1/8"
BFC-250-250N	1/4"	1/4"
BFC-312-125N	5/16"	1/8"
BFC-375-250N	3/8"	1/4"
BFC-500-375N	1/2"	3/8"
BFC-500-500N	1/2"	1/2"
BFC-625-500N	5/8"	1/2"
BFC-750-750N	3/4"	3/4"
BFC-875-750N	7/8"	3/4"
BFC-1000-1000N	1"	1"
Tech Sheet 20815		

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Unions



Tube x Tube

0292	OD
U-125	1/8"
U-187	3/16"
U-250	1/4"
U-312	5/16"
U-375	3/8"
U-500	1/2"
U-625	5/8"
U-750	3/4"
U-875	7/8"
U-1000	1"

Tech Sheet 20297



Metric Tube x Imperial Tube

0292	OD mm	OD
U-3-125	3	1/8"
U-4-125	4	1/8"
U-4-250	4	1/4"
U-6-125	6	1/8"
U-6-250	6	1/4"
U-6-312	6	5/16"
U-8-250	8	1/4"
U-8-375	8	3/8"
U-10-125	10	1/8"
U-10-250	10	1/4"
U-10-312	10	5/16"
U-10-375	10	3/8"
U-12-312	12	5/16"
U-12-375	12	3/8"
U-12-500	12	1/2"
U-15-500	15	1/2"
U-18-750	18	3/4"
U-20-500	20	1/2"
U-20-1000	20	1"
U-25-1000	25	1"

Tech Sheet 20817

Reducing Unions




Tube x Tube

0292	OD	OD
RU-187-125	3/16"	1/8"
RU-250-125	1/4"	1/8"
RU-250-187	1/4"	3/16"
RU-312-125	5/16"	1/8"
RU-312-250	5/16"	1/4"
RU-375-125	3/8"	1/8"
RU-375-250	3/8"	1/4"
RU-375-312	3/8"	5/16"
RU-500-125	1/2"	1/8"
RU-500-250	1/2"	1/4"
RU-500-375	1/2"	3/8"
RU-625-375	5/8"	3/8"
RU-625-500	5/8"	1/2"
RU-750-250	3/4"	1/4"
RU-750-375	3/4"	3/8"
RU-750-500	3/4"	1/2"
RU-750-625	3/4"	5/8"
RU-1000-500	1"	1/2"
RU-1000-750	1"	3/4"

Tech Sheet 20298

Bulkhead Unions



Tube x Tube

0292	OD
BU-125	1/8"
BU-187	3/16"
BU-250	1/4"
BU-312	5/16"
BU-375	3/8"
BU-500	1/2"
BU-625	5/8"
BU-750	3/4"
BU-1000	1"

Tech Sheet 20238

Male Branch Tees



Male Thread, NPT

0292	OD	Thread
MBT-125-125N	1/8"	1/8"
MBT-125-250N	1/8"	1/4"
MBT-187-125N	3/16"	1/8"
MBT-250-125N	1/4"	1/8"
MBT-250-250N	1/4"	1/4"
MBT-312-125N	5/16"	1/8"
MBT-375-250N	3/8"	1/4"
MBT-375-375N	3/8"	3/8"
MBT-500-375N	1/2"	3/8"
MBT-500-500N	1/2"	1/2"
MBT-625-500N	5/8"	1/2"
MBT-750-750N	3/4"	3/4"

Tech Sheet 20240

Male Positionable Branch Tees



Male Thread, SAE/MS

0292	OD	Thread
MBTP-250-437SE	1/4"	7/16"-20
MBTP-375-562SE	3/8"	9/16"-18
MBTP-500-750SE	1/2"	3/4"-16
MBTP-750-1062SE	3/4"	1.1/16"-12
MBTP-1000-1312SE	1"	1.5/16"-12

Tech Sheet 20821

Male Thread, BSPP

0292	OD	Thread
MBTP-250-125PR	1/4"	1/8"
MBTP-250-250PR	1/4"	1/4"
MBTP-375-250PR	3/8"	1/4"
MBTP-500-375PR	1/2"	3/8"
MBTP-500-500PR	1/2"	1/2"
MBTP-625-500PR	5/8"	1/2"
MBTP-750-500PR	3/4"	1/2"
MBTP-750-750PR	3/4"	3/4"
MBTP-1000-1000PR	1"	1"

Tech Sheet 20822

Male Run Tees



Male Thread, NPT

0292	OD	Thread
MRT-125-125N	1/8"	1/8"
MRT-125-250N	1/8"	1/4"
MRT-187-125N	3/16"	1/8"
MRT-250-125N	1/4"	1/8"
MRT-250-250N	1/4"	1/4"
MRT-312-125N	5/16"	1/8"
MRT-375-250N	3/8"	1/4"
MRT-375-375N	3/8"	3/8"
MRT-500-375N	1/2"	3/8"
MRT-500-500N	1/2"	1/2"
MRT-625-500N	5/8"	1/2"
MRT-750-750N	3/4"	3/4"

Tech Sheet 20299

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Male Positionable Run Tees



Male Thread, SAE/MS

0292	OD	Thread
MRTP-250-437SE	1/4"	7/16"-20
MRTP-375-562SE	3/8"	9/16"-18
MRTP-500-750SE	1/2"	3/4"-16
MRTP-750-1062SE	3/4"	1.1/16"-12
MRTP-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20824		

Male Thread, BSPP

0292	OD	Thread
MRTP-250-125PR	1/4"	1/8"
MRTP-250-250PR	1/4"	1/4"
MRTP-375-250PR	3/8"	1/4"
MRTP-500-375PR	1/2"	3/8"
MRTP-500-500PR	1/2"	1/2"
MRTP-625-500PR	5/8"	1/2"
MRTP-750-500PR	3/4"	1/2"
MRTP-750-750PR	3/4"	3/4"
MRTP-1000-1000PR	1"	1"
Tech Sheet 20825		

Female Branch Tees



Female Thread, NPT

0292	OD	Thread
FBT-125-125N	1/8"	1/8"
FBT-250-125N	1/4"	1/8"
FBT-250-250N	1/4"	1/4"
FBT-375-250N	3/8"	1/4"
FBT-375-375N	3/8"	3/8"
FBT-375-500N	3/8"	1/2"
FBT-500-250N	1/2"	1/4"
FBT-500-375N	1/2"	3/8"
FBT-500-500N	1/2"	1/2"
FBT-625-500N	5/8"	1/2"
FBT-750-750N	3/4"	3/4"
FBT-1000-750N	1"	3/4"
FBT-1000-1000N	1"	1"
Tech Sheet 20826		

Female Run Tees



Female Thread, NPT

0292	OD	Thread
FRT-125-125N	1/8"	1/8"
FRT-250-125N	1/4"	1/8"
FRT-250-250N	1/4"	1/4"
FRT-375-250N	3/8"	1/4"
FRT-500-375N	1/2"	3/8"
FRT-500-500N	1/2"	1/2"
FRT-750-750N	3/4"	3/4"
FRT-1000-750N	1"	3/4"
FRT-1000-1000N	1"	1"
Tech Sheet 20239		

Male Elbows



Male Thread, NPT

0292	OD	Thread
ME-125-125N	1/8"	1/8"
ME-125-250N	1/8"	1/4"
ME-187-125N	3/16"	1/8"
ME-187-250N	3/16"	1/4"
ME-250-125N	1/4"	1/8"
ME-250-250N	1/4"	1/4"
ME-250-375N	1/4"	3/8"
ME-250-500N	1/4"	1/2"
ME-312-125N	5/16"	1/8"
ME-312-250N	5/16"	1/4"
ME-312-375N	5/16"	3/8"
ME-375-125N	3/8"	1/8"
ME-375-250N	3/8"	1/4"
ME-375-375N	3/8"	3/8"
ME-375-500N	3/8"	1/2"
ME-375-750N	3/8"	3/4"
ME-500-250N	1/2"	1/4"
ME-500-375N	1/2"	3/8"
ME-500-500N	1/2"	1/2"
ME-500-750N	1/2"	3/4"
ME-625-375N	5/8"	3/8"
ME-625-500N	5/8"	1/2"
ME-625-750N	5/8"	3/4"
ME-750-500N	3/4"	1/2"
ME-750-750N	3/4"	3/4"
ME-875-750N	7/8"	3/4"
ME-1000-750N	1"	3/4"
ME-1000-1000N	1"	1"
Tech Sheet 20295		

Male Thread, BSPT

0292	OD	Thread
ME-250-125RT	1/4"	1/8"
ME-250-250RT	1/4"	1/4"
ME-250-375RT	1/4"	3/8"
ME-250-500RT	1/4"	1/2"
ME-312-250RT	5/16"	1/4"
ME-375-250RT	3/8"	1/4"
ME-375-375RT	3/8"	3/8"
Tech Sheet 20294		

Female Elbows



Female Thread, NPT

0292	OD	Thread
FE-125-125N	1/8"	1/8"
FE-125-250N	1/8"	1/4"
FE-187-125N	3/16"	1/8"
FE-250-125N	1/4"	1/8"
FE-250-250N	1/4"	1/4"
FE-250-375N	1/4"	3/8"
FE-250-500N	1/4"	1/2"
FE-312-125N	5/16"	1/8"
FE-312-250N	5/16"	1/4"
FE-375-125N	3/8"	1/8"
FE-375-250N	3/8"	1/4"
FE-375-375N	3/8"	3/8"
FE-375-500N	3/8"	1/2"
FE-500-250N	1/2"	1/4"
FE-500-375N	1/2"	3/8"
FE-500-500N	1/2"	1/2"
FE-625-375N	5/8"	3/8"
FE-625-500N	5/8"	1/2"
FE-750-500N	3/4"	1/2"
FE-750-750N	3/4"	3/4"
FE-875-750N	7/8"	3/4"
FE-1000-750N	1"	3/4"
FE-1000-1000N	1"	1"
Tech Sheet 20296		

Positionable Elbows



Male Thread, SAE/MS

0292	OD	Thread
MEP-250-437SE	1/4"	7/16"-20
MEP-250-562SE	1/4"	9/16"-18
MEP-312-500SE	5/16"	1/2"-20
MEP-375-562SE	3/8"	9/16"-18
MEP-375-750SE	3/8"	3/4"-16
MEP-500-750SE	1/2"	3/4"-16
MEP-625-875SE	5/8"	7/8"-14
MEP-750-1062SE	3/4"	1.1/16"-12
MEP-875-1187SE	7/8"	1.3/16"-12
MEP-1000-1312SE	1"	1.5/16"-12
Tech Sheet 20831		

Male Thread, BSPP

0292	OD	Thread
MEP-250-125PR	1/4"	1/8"
MEP-250-250PR	1/4"	1/4"
MEP-375-250PR	3/8"	1/4"
MEP-375-375PR	3/8"	3/8"
MEP-500-250PR	1/2"	1/4"
MEP-500-375PR	1/2"	3/8"
MEP-500-500PR	1/2"	1/2"
MEP-625-500PR	5/8"	1/2"
MEP-750-500PR	3/4"	1/2"
MEP-750-750PR	3/4"	3/4"
MEP-1000-750PR	1"	3/4"
MEP-1000-1000PR	1"	1"
Tech Sheet 20832		

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Bulkhead Reducing Unions



Tube x Tube

0292	OD	OD
RBU-250-125	1/4"	1/8"
RBU-375-250	3/8"	1/4"
RBU-500-250	1/2"	1/4"

Tech Sheet 20833

Union Elbows



Tube x Tube

0292	OD
UE-125	1/8"
UE-187	3/16"
UE-250	1/4"
UE-312	5/16"
UE-375	3/8"
UE-500	1/2"
UE-625	5/8"
UE-750	3/4"
UE-875	7/8"
UE-1000	1"

Tech Sheet 20289

Reducing Union Elbows



Tube x Tube

0292	OD	OD
RUE-187-125	3/16"	1/8"
RUE-250-125	1/4"	1/8"
RUE-312-125	5/16"	1/8"
RUE-312-250	5/16"	1/4"
RUE-375-125	3/8"	1/8"
RUE-375-250	3/8"	1/4"
RUE-375-312	3/8"	5/16"
RUE-500-250	1/2"	1/4"
RUE-500-312	1/2"	5/16"
RUE-500-375	1/2"	3/8"
RUE-625-375	5/8"	3/8"
RUE-625-500	5/8"	1/2"
RUE-750-250	3/4"	1/4"
RUE-750-375	3/4"	3/8"
RUE-750-500	3/4"	1/2"
RUE-875-250	7/8"	1/4"
RUE-1000-500	1"	1/2"
RUE-1000-750	1"	3/4"

Tech Sheet 20835

Union Tees



Tube x Tube

0292	OD
UT-125	1/8"
UT-187	3/16"
UT-250	1/4"
UT-312	5/16"
UT-375	3/8"
UT-500	1/2"
UT-625	5/8"
UT-750	3/4"
UT-875	7/8"
UT-1000	1"

Tech Sheet 20288

Reducing Branch, Union Tees



Tube x Tube

0292	OD	OD
RUT-375-250	3/8"	1/4"
RUT-500-250	1/2"	1/4"
RUT-500-375	1/2"	3/8"
RUT-625-375	5/8"	3/8"
RUT-750-375	3/4"	3/8"
RUT-750-500	3/4"	1/2"
RUT-1000-375	1"	3/8"
RUT-1000-500	1"	1/2"
RUT-1000-750	1"	3/4"

Tech Sheet 20837

Union Crosses



Tube x Tube

0292	OD
UC-125	1/8"
UC-250	1/4"
UC-312	5/16"
UC-375	3/8"
UC-500	1/2"
UC-750	3/4"
UC-1000	1"

Tech Sheet 20290

AN Unions



Male Thread, AN

0292	OD	Thread
NU-125-125AN	1/8"	5/16"
NU-125-250AN	1/8"	7/16"
NU-250-250AN	1/4"	7/16"
NU-312-312AN	5/16"	1/2"
NU-375-250AN	3/8"	7/16"
NU-375-375AN	3/8"	9/16"
NU-500-500AN	1/2"	3/4"
NU-750-750AN	3/4"	1.1/16"
NU-1000-1000AN	1"	1.5/16"

Tech Sheet 20839

AN Bulkhead Unions



Male Thread, AN

0292	OD	Thread
ABU-250-250AN	1/4"	7/16"
ABU-375-375AN	3/8"	9/16"
ABU-500-500AN	1/2"	3/4"
ABU-750-750AN	3/4"	1.1/16"
ABU-1000-1000AN	1"	1.5/16"

Tech Sheet 20840

Weld Union, Sockets



Tube x Tube

0292	OD
SWU-125	1/8"
SWU-250	1/4"
SWU-375	3/8"
SWU-500	1/2"
SWU-750	3/4"
SWU-1000	1"

Tech Sheet 20841

Weld Elbow, Sockets



Tube x Tube

0292	OD
SWE-250	1/4"
SWE-375	3/8"
SWE-500	1/2"
SWE-750	3/4"
SWE-1000	1"

Tech Sheet 20842

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Weld Union, Connectors



Tube x Tube

0292	OD	Stem OD
MWC-125-125	1/8"	1/8"
MWC-187-125	3/16"	1/8"
MWC-250-125	1/4"	1/8"
MWC-250-250	1/4"	1/4"
MWC-312-125	5/16"	1/8"
MWC-312-250	5/16"	1/4"
MWC-375-250	3/8"	1/4"
MWC-375-375	3/8"	3/8"
MWC-375-500	3/8"	1/2"
MWC-375-750	3/8"	3/4"
MWC-500-375	1/2"	3/8"
MWC-500-500	1/2"	1/2"
MWC-500-750	1/2"	3/4"
MWC-625-500	5/8"	1/2"
MWC-750-750	3/4"	3/4"
MWC-1000-1000	1"	1"

Tech Sheet 20843

Weld Elbow, Connectors



Tube x Tube

0292	OD	Stem OD
MWE-250-125	1/4"	1/8"
MWE-250-250	1/4"	1/4"
MWE-375-250	3/8"	1/4"
MWE-500-500	1/2"	1/2"
MWE-750-750	3/4"	3/4"

Tech Sheet 20844

Bulkhead Reducers



Tube x Tube

0292	OD
BR-125	1/8"
BR-250	1/4"
BR-375	3/8"
BR-500	1/2"
BR-625	5/8"
BR-1000	1"

Tech Sheet 20287

Reducers



Tube x Tube

0292	OD	Stem OD
R-125-125	1/8"	1/8"
R-125-187	1/8"	3/16"
R-125-250	1/8"	1/4"
R-125-375	1/8"	3/8"
R-125-500	1/8"	1/2"
R-187-125	3/16"	1/8"
R-187-250	3/16"	1/4"
R-250-125	1/4"	1/8"
R-250-187	1/4"	3/16"
R-250-250	1/4"	1/4"
R-250-312	1/4"	5/16"
R-250-375	1/4"	3/8"
R-250-500	1/4"	1/2"
R-250-625	1/4"	5/8"
R-250-750	1/4"	3/4"
R-312-375	5/16"	3/8"
R-312-500	5/16"	1/2"
R-375-250	3/8"	1/4"
R-375-375	3/8"	3/8"
R-375-500	3/8"	1/2"
R-375-625	3/8"	5/8"
R-375-750	3/8"	3/4"
R-500-250	1/2"	1/4"
R-500-375	1/2"	3/8"
R-500-500	1/2"	1/2"
R-500-625	1/2"	5/8"
R-500-750	1/2"	3/4"
R-500-1000	1/2"	1"
R-625-750	5/8"	3/4"
R-625-875	5/8"	7/8"
R-625-1000	5/8"	1"
R-750-500	3/4"	1/2"
R-750-1000	3/4"	1"

Tech Sheet 20286

Port Connectors



Tube x Tube

0292	OD
PC-125	1/8"
PC-250	1/4"
PC-312	5/16"
PC-375	3/8"
PC-500	1/2"
PC-750	3/4"
PC-1000	1"

Tech Sheet 20378

Reducing Port Connectors



Tube x Tube

0292	OD	Stem OD
RPC-250-125	1/4"	1/8"
RPC-375-125	3/8"	1/8"
RPC-375-250	3/8"	1/4"
RPC-500-250	1/2"	1/4"
RPC-750-500	3/4"	1/2"
RPC-1000-500	1"	1/2"
RPC-1000-750	1"	3/4"

Tech Sheet 20849

FAC Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE IMPERIAL TUBE FITTINGS

stainless steel

PANAM

Caps



Tube

0292	OD
C-125-FT	1/8"
C-187	3/16"
C-250	1/4"
C-312	5/16"
C-375	3/8"
C-500	1/2"
C-625	5/8"
C-750	3/4"
C-875	7/8"
C-1000	1"

Tech Sheet 20284

Nuts



Tube

0292	OD
N-125-FT	1/8"
N-187	3/16"
N-250	1/4"
N-312	5/16"
N-375	3/8"
N-500	1/2"
N-625	5/8"
N-750	3/4"
N-875	7/8"
N-1000	1"

Tech Sheet 20283

Front Ferrules



Tube

0292	OD
FF-125	1/8"
FF-187	3/16"
FF-250	1/4"
FF-312	5/16"
FF-375	3/8"
FF-500	1/2"
FF-625	5/8"
FF-750	3/4"
FF-875	7/8"
FF-1000	1"

Tech Sheet 20854

Plugs



Tube

0292	OD
P-125	1/8"
P-187	3/16"
P-250	1/4"
P-312	5/16"
P-375	3/8"
P-500	1/2"
P-625	5/8"
P-750	3/4"
P-875	7/8"
P-1000	1"

Tech Sheet 20282

Back Ferrules



Tube

0292	OD
BF-125	1/8"
BF-187	3/16"
BF-250	1/4"
BF-312	5/16"
BF-375	3/8"
BF-500	1/2"
BF-625	5/8"
BF-750	3/4"
BF-875	7/8"
BF-1000	1"

Tech Sheet 20285

Lock Nuts



To suit Bulkheads

0292	OD
BLN-125	1/8"
BLN-187	3/16"
BLN-250	1/4"
BLN-312	5/16"
BLN-375	3/8"
BLN-500	1/2"
BLN-625	5/8"
BLN-750	3/4"
BLN-875	7/8"
BLN-1000	1"

Tech Sheet 20855

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Male Connectors



Male Thread, NPT

0292	OD mm	Thread
MC-3-125N	3	1/8"
MC-3-250N	3	1/4"
MC-4-125N	4	1/8"
MC-4-250N	4	1/4"
MC-6-125N	6	1/8"
MC-6-250N	6	1/4"
MC-6-375N	6	3/8"
MC-6-500N	6	1/2"
MC-8-125N	8	1/8"
MC-8-250N	8	1/4"
MC-8-375N	8	3/8"
MC-8-500N	8	1/2"
MC-10-125N	10	1/8"
MC-10-250N	10	1/4"
MC-10-375N	10	3/8"
MC-10-500N	10	1/2"
MC-10-750N	10	3/4"
MC-12-125N	12	1/8"
MC-12-250N	12	1/4"
MC-12-375N	12	3/8"
MC-12-500N	12	1/2"
MC-12-750N	12	3/4"
MC-14-250N	14	1/4"
MC-14-375N	14	3/8"
MC-14-500N	14	1/2"
MC-15-500N	15	1/2"
MC-16-375N	16	3/8"
MC-16-500N	16	1/2"
MC-16-750N	16	3/4"
MC-18-500N	18	1/2"
MC-18-750N	18	3/4"
MC-20-500N	20	1/2"
MC-20-750N	20	3/4"
MC-22-750N	22	3/4"
MC-22-1000N	22	1"
MC-25-500N	25	1/2"
MC-25-750N	25	3/4"
MC-25-1000N	25	1"
Tech Sheet 20281		



Male Thread, BSPT

0292	OD mm	Thread
MC-3-125RT	3	1/8"
MC-3-250RT	3	1/4"
MC-4-125RT	4	1/8"
MC-4-250RT	4	1/4"
MC-6-125RT	6	1/8"
MC-6-250RT	6	1/4"
MC-6-375RT	6	3/8"
MC-6-500RT	6	1/2"
MC-8-125RT	8	1/8"
MC-8-250RT	8	1/4"
MC-8-375RT	8	3/8"
MC-8-500RT	8	1/2"
MC-10-125RT	10	1/8"
MC-10-250RT	10	1/4"
MC-10-375RT	10	3/8"
MC-10-500RT	10	1/2"
MC-12-125RT	12	1/8"
MC-12-250RT	12	1/4"
MC-12-375RT	12	3/8"
MC-12-500RT	12	1/2"
MC-12-750RT	12	3/4"
MC-15-500RT	15	1/2"
MC-16-250RT	16	1/4"
MC-16-375RT	16	3/8"
MC-16-500RT	16	1/2"
MC-16-750RT	16	3/4"
MC-18-500RT	18	1/2"
MC-18-750RT	18	3/4"
MC-20-500RT	20	1/2"
MC-20-750RT	20	3/4"
MC-22-750RT	22	3/4"
MC-22-1000RT	22	1"
MC-25-750RT	25	3/4"
MC-25-1000RT	25	1"
Tech Sheet 20278		



Male Thread, BSPP (Captive Seal)

0292	OD mm	Thread
OMC-6-125EO	6	1/8"
OMC-6-250EO	6	1/4"
OMC-6-375EO	6	3/8"
OMC-6-500EO	6	1/2"
OMC-10-250EO	10	1/4"
OMC-10-375EO	10	3/8"
OMC-10-500EO	10	1/2"
OMC-12-250EO	12	1/4"
OMC-12-375EO	12	3/8"
OMC-12-500EO	12	1/2"
Tech Sheet 20856		



Male Thread-RS, BSPP

0292	OD mm	Thread
MC-3-125RS	3	1/8"
MC-3-250RS	3	1/4"
MC-4-125RS	4	1/8"
MC-6-125RS	6	1/8"
MC-6-250RS	6	1/4"
MC-6-375RS	6	3/8"
MC-6-500RS	6	1/2"
MC-8-125RS	8	1/8"
MC-8-250RS	8	1/4"
MC-8-375RS	8	3/8"
MC-8-500RS	8	1/2"
MC-10-250RS	10	1/4"
MC-10-375RS	10	3/8"
MC-10-500RS	10	1/2"
MC-12-250RS	12	1/4"
MC-12-375RS	12	3/8"
MC-12-500RS	12	1/2"
MC-12-750RS	12	3/4"
MC-16-375RS	16	3/8"
MC-16-500RS	16	1/2"
MC-18-500RS	18	1/2"
MC-18-750RS	18	3/4"
MC-20-500RS	20	1/2"
MC-20-750RS	20	3/4"
MC-22-750RS	22	3/4"
MC-22-1000RS	22	1"
MC-25-750RS	25	3/4"
MC-25-1000RS	25	1"
Tech Sheet 20279		

stainless steel



You might also need
Stainless Steel Tubing
see page **1287**

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Female Connectors



Female Thread, NPT

0292	OD mm	Thread
FC-3-125N	3	1/8"
FC-3-250N	3	1/4"
FC-4-125N	4	1/8"
FC-6-125N	6	1/8"
FC-6-250N	6	1/4"
FC-6-375N	6	3/8"
FC-6-500N	6	1/2"
FC-8-125N	8	1/8"
FC-8-250N	8	1/4"
FC-8-375N	8	3/8"
FC-8-500N	8	1/2"
FC-10-250N	10	1/4"
FC-10-375N	10	3/8"
FC-10-500N	10	1/2"
FC-12-250N	12	1/4"
FC-12-375N	12	3/8"
FC-12-500N	12	1/2"
FC-15-500N	15	1/2"
FC-16-500N	16	1/2"
FC-20-500N	20	1/2"
FC-20-750N	20	3/4"
FC-22-750N	22	3/4"
FC-22-1000N	22	1"
FC-25-750N	25	3/4"
FC-25-1000N	25	1"
Tech Sheet 20275		

Female Thread, BSPT

0292	OD mm	Thread
FC-3-125RT	3	1/8"
FC-6-125RT	6	1/8"
FC-6-250RT	6	1/4"
FC-6-375RT	6	3/8"
FC-6-500RT	6	1/2"
FC-8-125RT	8	1/8"
FC-8-250RT	8	1/4"
FC-8-375RT	8	3/8"
FC-8-500RT	8	1/2"
FC-10-125RT	10	1/8"
FC-10-250RT	10	1/4"
FC-10-375RT	10	3/8"
FC-10-500RT	10	1/2"
FC-12-125RT	12	1/8"
FC-12-250RT	12	1/4"
FC-12-375RT	12	3/8"
FC-12-500RT	12	1/2"
FC-12-750RT	12	3/4"
FC-15-375RT	15	3/8"
FC-15-500RT	15	1/2"
FC-20-500RT	20	1/2"
FC-20-750RT	20	3/4"
FC-22-750RT	22	3/4"
FC-22-1000RT	22	1"
FC-25-750RT	25	3/4"
FC-25-1000RT	25	1"
Tech Sheet 20274		



Female Thread, BSPP

0292	OD mm	Thread
FC-3-250RG	3	1/4"
FC-6-250RG	6	1/4"
FC-6-375RG	6	3/8"
FC-6-500RG	6	1/2"
FC-8-250RG	8	1/4"
FC-8-375RG	8	3/8"
FC-8-500RG	8	1/2"
FC-10-250RG	10	1/4"
FC-10-375RG	10	3/8"
FC-10-500RG	10	1/2"
FC-12-250RG	12	1/4"
FC-12-375RG	12	3/8"
FC-12-500RG	12	1/2"
FC-20-500RG	20	1/2"
FC-22-500RG	22	1/2"
Tech Sheet 20273		

Bulkhead Male Connectors



Male Thread, NPT

0292	OD mm	Thread
BMC-6-125N	6	1/8"
BMC-6-250N	6	1/4"
BMC-8-125N	8	1/8"
BMC-8-250N	8	1/4"
BMC-10-250N	10	1/4"
BMC-10-375N	10	3/8"
BMC-10-500N	10	1/2"
BMC-12-250N	12	1/4"
BMC-12-375N	12	3/8"
BMC-12-500N	12	1/2"
Tech Sheet 20276		

Bulkhead Female Connectors



Female Thread, NPT

0292	OD mm	Thread
BFC-6-125N	6	1/8"
BFC-6-250N	6	1/4"
BFC-8-125N	8	1/8"
BFC-10-250N	10	1/4"
BFC-12-375N	12	3/8"
BFC-12-500N	12	1/2"
Tech Sheet 20277		

FAC Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Unions



Tube x Tube

0292	OD mm
U-3	3
U-4	4
U-6	6
U-8	8
U-10	10
U-12	12
U-15	15
U-16	16
U-18	18
U-20-FT	20
U-22	22
U-25	25

Tech Sheet 20266

Reducing Unions



Tube x Tube

0292	OD mm	OD mm
RU-6-3	6	3
RU-6-4	6	4
RU-8-6	8	6
RU-10-6	10	6
RU-10-8	10	8
RU-12-6	12	6
RU-12-8	12	8
RU-12-10	12	10
RU-16-10	16	10
RU-16-12	16	12
RU-18-12	18	12
RU-25-18	25	18
RU-25-20	25	20

Tech Sheet 20267

Bulkhead Unions



Tube x Tube

0292	OD mm
BU-3-FT	3
BU-4	4
BU-6	6
BU-8	8
BU-10	10
BU-12-FT	12
BU-14	14
BU-15	15
BU-16	16
BU-18	18
BU-20	20

Tech Sheet 20272

Male Branch Tees



Male Thread, NPT

0292	OD mm	Thread
MBT-6-125N	6	1/8"
MBT-6-250N	6	1/4"
MBT-8-125N	8	1/8"
MBT-8-250N	8	1/4"
MBT-10-250N	10	1/4"
MBT-12-250N	12	1/4"
MBT-12-375N	12	3/8"
MBT-12-500N	12	1/2"
MBT-16-500N	16	1/2"

Tech Sheet 20269

Male Positionable Branch Tees



Male Thread, BSPP

0292	OD mm	Thread
MBTP-6-125PR	6	1/8"
MBTP-6-250PR	6	1/4"
MBTP-8-125PR	8	1/8"
MBTP-8-250PR	8	1/4"
MBTP-10-250PR	10	1/4"
MBTP-12-375PR	12	3/8"
MBTP-12-500PR	12	1/2"

Tech Sheet 20861

Male Run Tees



Male Thread, NPT

0292	OD mm	Thread
MRT-6-125N	6	1/8"
MRT-6-250N	6	1/4"
MRT-8-250N	8	1/4"
MRT-12-250N	12	1/4"
MRT-12-375N	12	3/8"
MRT-12-500N	12	1/2"
MRT-16-500N	16	1/2"

Tech Sheet 20268

Male Positionable Run Tees



Male Thread, BSPP

0292	OD mm	Thread
MRTP-6-125PR	6	1/8"
MRTP-6-250PR	6	1/4"
MRTP-8-125PR	8	1/8"
MRTP-8-250PR	8	1/4"
MRTP-10-250PR	10	1/4"
MRTP-12-375PR	12	3/8"
MRTP-12-500PR	12	1/2"

Tech Sheet 20863

Female Branch Tees



Female Thread, NPT

0292	OD mm	Thread
FBT-6-125N	6	1/8"
FBT-6-250N	6	1/4"
FBT-8-125N	8	1/8"
FBT-8-250N	8	1/4"
FBT-10-250N	10	1/4"
FBT-12-250N	12	1/4"
FBT-12-375N	12	3/8"
FBT-16-500N	16	1/2"

Tech Sheet 20271

Female Run Tees



Female Thread, NPT

0292	OD mm	Thread
FRT-6-125N	6	1/8"
FRT-6-250N	6	1/4"
FRT-8-125N	8	1/8"
FRT-8-250N	8	1/4"
FRT-10-250N	10	1/4"
FRT-12-250N	12	1/4"
FRT-12-375N	12	3/8"
FRT-16-500N	16	1/2"

Tech Sheet 20270

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Male Elbows



Male Thread, NPT

0292	OD mm	Thread
ME-3-250N	3	1/4"
ME-4-125N	4	1/8"
ME-4-250N	4	1/4"
ME-6-125N	6	1/8"
ME-6-250N	6	1/4"
ME-6-375N	6	3/8"
ME-6-500N	6	1/2"
ME-8-125N	8	1/8"
ME-8-250N	8	1/4"
ME-8-375N	8	3/8"
ME-8-500N	8	1/2"
ME-10-250N	10	1/4"
ME-10-375N	10	3/8"
ME-10-500N	10	1/2"
ME-12-250N	12	1/4"
ME-12-375N	12	3/8"
ME-12-500N	12	1/2"
ME-12-750N	12	3/4"
ME-15-500N	15	1/2"
ME-16-375N	16	3/8"
ME-16-500N	16	1/2"
ME-16-750N	16	3/4"
ME-18-500N	18	1/2"
ME-18-750N	18	3/4"
ME-20-500N	20	1/2"
ME-22-750N	22	3/4"
ME-22-1000N	22	1"
ME-25-750N	25	3/4"
ME-25-1000N	25	1"

Tech Sheet 20264



Male Thread, BSPT

0292	OD mm	Thread
ME-3-125RT	3	1/8"
ME-3-250RT	3	1/4"
ME-4-125RT	4	1/8"
ME-4-250RT	4	1/4"
ME-6-125RT	6	1/8"
ME-6-250RT	6	1/4"
ME-6-375RT	6	3/8"
ME-6-500RT	6	1/2"
ME-8-125RT	8	1/8"
ME-8-250RT	8	1/4"
ME-8-375RT	8	3/8"
ME-8-500RT	8	1/2"
ME-10-250RT	10	1/4"
ME-10-375RT	10	3/8"
ME-10-500RT	10	1/2"
ME-12-250RT	12	1/4"
ME-12-375RT	12	3/8"
ME-12-500RT	12	1/2"
ME-12-750RT	12	3/4"
ME-16-375RT	16	3/8"
ME-16-500RT	16	1/2"
ME-18-500RT	18	1/2"
ME-18-750RT	18	3/4"
ME-20-500RT	20	1/2"
ME-20-750RT	20	3/4"
ME-22-750RT	22	3/4"
ME-22-1000RT	22	1"
ME-25-750RT	25	3/4"
ME-25-1000RT	25	1"

Tech Sheet 20263

Female Elbows



Female Thread, NPT

0292	OD mm	Thread
FE-6-125N	6	1/8"
FE-6-250N	6	1/4"
FE-6-500N	6	1/2"
FE-8-250N	8	1/4"
FE-10-125N	10	1/8"
FE-10-250N	10	1/4"
FE-12-250N	12	1/4"
FE-12-375N	12	3/8"
FE-12-500N	12	1/2"
FE-16-500N	16	1/2"

Tech Sheet 20265

Positionable Elbows



Male Thread, BSPP

0292	OD mm	Thread
MEP-6-125PR	6	1/8"
MEP-6-250PR	6	1/4"
MEP-8-125PR	8	1/8"
MEP-8-250PR	8	1/4"
MEP-10-250PR	10	1/4"
MEP-10-375PR	10	3/8"
MEP-12-250PR	12	1/4"
MEP-12-375PR	12	3/8"
MEP-12-500PR	12	1/2"
MEP-12-750PR	12	3/4"

Tech Sheet 20265

Union Elbows



Tube x Tube

0292	OD mm
UE-3	3
UE-4	4
UE-6	6
UE-8	8
UE-10	10
UE-12	12
UE-14	14
UE-15	15
UE-16	16
UE-18	18
UE-20	20
UE-22	22
UE-25	25

Tech Sheet 20261

Union Tees



Tube x Tube

0292	OD mm
UT-3	3
UT-4	4
UT-6	6
UT-8	8
UT-10	10
UT-12	12
UT-14	14
UT-15	15
UT-16	16
UT-18	18
UT-20	20
UT-22	22
UT-25	25

Tech Sheet 20260

Union Crosses



Tube x Tube

0292	OD mm
UC-3	3
UC-6	6
UC-8	8
UC-10	10
UC-12	12
UC-16	16
UC-18	18
UC-20	20
UC-25	25

Tech Sheet 20262

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Weld Union, Connectors



Tube x Tube

0292	OD mm	Stem OD
MWC-3-125	3	1/8"
MWC-4-125	4	1/8"
MWC-6-125	6	1/8"
MWC-6-250	6	1/4"
MWC-8-125	8	1/8"
MWC-8-250	8	1/4"
MWC-8-500	8	1/2"
MWC-10-250	10	1/4"
MWC-10-500	10	1/2"
MWC-12-250	12	1/4"
MWC-12-375	12	3/8"
MWC-12-500	12	1/2"
MWC-14-375	14	3/8"
MWC-15-500	15	1/2"
MWC-16-500	16	1/2"
MWC-18-500	18	1/2"

Tech Sheet 20873

Port Connectors



Tube x Tube

0292	OD mm
PC-3	3
PC-6	6
PC-8	8
PC-10	10
PC-12-FT	12
PC-15-FT	15
PC-16	16
PC-18-FT	18
PC-20	20
PC-25	25

Tech Sheet 20874

Reducing Port Connectors



Tube x Tube

0292	OD mm	Stem OD mm
RPC-6-3	6	3
RPC-8-6	8	6
RPC-10-6	10	6
RPC-10-8	10	8
RPC-12-6	12	6
RPC-12-8	12	8
RPC-12-10	12	10
RPC-16-12	16	12

Tech Sheet 20875

Reducers



Tube x Tube

0292	OD mm	Stem OD mm
R-3-4	3	4
R-3-6	3	6
R-3-10	3	10
R-4-6	4	6
R-6-3	6	3
R-6-8	6	8
R-6-10	6	10
R-6-12	6	12
R-6-18	6	18
R-8-6	8	6
R-8-10	8	10
R-8-12	8	12
R-10-6	10	6
R-10-12	10	12
R-10-15	10	15
R-10-18	10	18
R-12-6	12	6
R-12-8	12	8
R-12-10	12	10
R-12-16	12	16
R-12-18	12	18
R-12-20	12	20
R-12-22	12	22
R-12-25	12	25
R-16-12	16	12
R-18-12	18	12
R-18-16	18	16
R-18-20	18	20
R-18-22	18	22
R-18-25	18	25
R-20-16	20	16
R-20-22	20	22
R-20-25	20	25
R-22-18	22	18
R-22-20	22	20
R-22-25	22	25
R-25-18	25	18
R-25-20	25	20

Tech Sheet 20258



Metric Tube x Imperial Tube

0292	OD mm	Stem OD
R-3-125	3	1/8"
R-3-250	3	1/4"
R-4-250	4	1/4"
R-6-125	6	1/8"
R-6-250	6	1/4"
R-6-312	6	5/16"
R-6-375	6	3/8"
R-6-500	6	1/2"
R-8-375	8	3/8"
R-8-500	8	1/2"
R-10-375	10	3/8"
R-10-500	10	1/2"
R-12-500	12	1/2"
R-12-750	12	3/4"
R-18-750	18	3/4"
R-25-1000	25	1"

Tech Sheet 20877

Caps



Tube

0292	OD mm
C-3	3
C-4	4
C-6	6
C-8	8
C-10	10
C-12	12
C-14	14
C-15	15
C-16	16
C-18	18
C-20	20
C-22	22
C-25	25

Tech Sheet 20259

Fluid-Air Components Ltd

316 STAINLESS STEEL TWIN FERRULE METRIC TUBE FITTINGS

stainless steel

PANAM

Plugs



Tube

0292	OD mm
P-3-FT	3
P-4	4
P-6-FT	6
P-8	8
P-10	10
P-12	12
P-15	15
P-16	16
P-18	18
P-20	20
P-22	22
P-25	25

Tech Sheet 20254

Nuts



Tube

0292	OD mm
N-3	3
N-4	4
N-6	6
N-8	8
N-10	10
N-12	12
N-15	15
N-16	16
N-18	18
N-20	20
N-25	25

Tech Sheet 20255

Back Ferrules



Tube

0292	OD mm
BF-3	3
BF-4	4
BF-6	6
BF-8	8
BF-10	10
BF-12	12
BF-14	14
BF-15	15
BF-16	16
BF-18	18
BF-20	20
BF-22	22
BF-25	25

Tech Sheet 20257

Front Ferrules



Tube

0292	OD mm
FF-3	3
FF-4	4
FF-6	6
FF-8	8
FF-10	10
FF-12	12
FF-14	14
FF-15	15
FF-16	16
FF-18	18
FF-20	20
FF-22	22
FF-25	25

Tech Sheet 20256

Lock Nuts



To suit Bulkheads

0292	OD mm
BLN-3	3
BLN-4	4
BLN-6	6
BLN-8	8
BLN-10-FT	10
BLN-12-FT	12
BLN-14	14
BLN-16-FT	16
BLN-18	18
BLN-20-FT	20

Tech Sheet 20883

stainless steel



For **Stainless Steel Tubing** see page **1287**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HYDRAULIC STAINLESS STEEL ADAPTORS

stainless steel

PANAM

Male x Male Straight Adaptors



BSPP x BSPP

0044	Thread	Thread
2025-1401	1/8"	1/8"
2025-1419	1/4"	1/8"
2025-1427	1/4"	1/4"
2025-1435	3/8"	1/8"
2025-1443	3/8"	1/4"
2025-1450	3/8"	3/8"
2025-1468	1/2"	1/4"
2025-1476	1/2"	3/8"
2025-1484	1/2"	1/2"
2025-1495	5/8"	1/2"
2025-1505	5/8"	5/8"
2025-1520	3/4"	1/4"
2025-1526	3/4"	3/8"
2025-1534	3/4"	1/2"
2025-1538	3/4"	5/8"
2025-1559	3/4"	3/4"
2025-1567	1"	1/2"
2025-1572	1"	5/8"
2025-1583	1"	3/4"
2025-1591	1"	1"
2025-1595	1.1/4"	3/4"
2025-1600	1.1/4"	1"
2025-1609	1.1/4"	1.1/4"
2025-1611	1.1/2"	1"
2025-1615	1.1/2"	1.1/4"
2025-1617	1.1/2"	1.1/2"
2025-1620	2"	1.1/2"
2025-1625	2"	2"
Tech Sheet 20884		



BSPP x BSPT

0044	Thread
2033-9693	1/4"
2033-9761	3/8"
2033-9719	1/2"
2033-9727	3/4"
2033-9735	1"
Tech Sheet 20884	



BSPP x NPT

0044	BSPP Thread	NPT Thread
2025-1633	1/8"	1/8"
2025-1636	1/8"	1/4"
2025-1639	1/4"	1/8"
2025-1641	1/4"	1/4"
2025-1643	1/4"	3/8"
2025-1656	3/8"	1/4"
2025-1658	3/8"	3/8"
2025-1661	3/8"	1/2"
2025-1671	1/2"	3/8"
2025-1674	1/2"	1/2"
2025-1677	5/8"	1/2"
2025-1679	5/8"	3/4"
2025-1681	3/4"	1/2"
2025-1682	3/4"	3/4"
2025-1684	3/4"	1"
2025-1687	1"	3/4"
2025-1690	1"	1"
2025-1700	1.1/4"	1.1/4"
2025-1710	1.1/2"	1.1/2"
2025-1720	2"	2"
Tech Sheet 20884		



BSPT x BSPT

0044	Thread	Thread
2025-1708	1/8"	1/8"
2025-1715	1/4"	1/8"
2025-1724	1/4"	1/4"
2025-1727	3/8"	1/8"
2025-1732	3/8"	1/4"
2025-1740	3/8"	3/8"
2025-1845	1/2"	1/8"
2025-1852	1/2"	1/4"
2025-1856	1/2"	3/8"
2025-1865	1/2"	1/2"
2025-1881	3/4"	1/8"
2025-1885	3/4"	1/4"
2025-1889	3/4"	3/8"
2025-1894	3/4"	1/2"
2025-1898	3/4"	3/4"
2025-1905	1"	1/8"
2025-1910	1"	1/4"
2025-1915	1"	3/8"
2025-1920	1"	1/2"
2025-1925	1"	3/4"
2025-1931	1"	1"
2025-1935	1.1/4"	1"
2025-1940	1.1/4"	1.1/4"
2025-1945	1.1/2"	1"
2025-1950	1.1/2"	1.1/2"
2025-1956	2"	1"
2025-1960	2"	1.1/2"
2025-1965	2"	2"
Tech Sheet 20884		

Male x Female Straight Adaptors



Male x Female Swivel, BSPP

0044	Male Thread	Female Thread
2025-1930	1/8"	1/8"
2025-1948	1/4"	1/4"
2025-1955	1/4"	3/8"
2025-1961	1/4"	1/2"
2025-1963	3/8"	1/4"
2025-1971	3/8"	3/8"
2025-1989	3/8"	1/2"
2025-1997	1/2"	3/8"
2025-2003	1/2"	1/2"
2025-2020	1/2"	3/4"
2025-2029	3/4"	1/2"
2025-2037	3/4"	3/4"
2025-2043	3/4"	1"
2025-2060	1"	1"
Tech Sheet 20884		

Female Swivel, BSPP x BSPT Male

0044	Thread
2033-9862	1/8"
2033-9867	1/4"
2033-9875	3/8"
2033-9883	1/2"
2033-9891	3/4"
2033-9896	1"
Tech Sheet 20884	



Male x Female Fixed, BSPP

0044	Male Thread	Female Thread
2025-8121	1/8"	1/8"
2025-8131	1/4"	1/8"
2025-8142	1/4"	1/4"
2025-8151	3/8"	1/8"
2025-8161	3/8"	1/4"
2025-8171	3/8"	3/8"
2025-8181	1/2"	1/4"
2025-8201	1/2"	3/8"
2025-8211	1/2"	1/2"
2025-8191	3/4"	1/4"
2025-8221	3/4"	3/8"
2025-8231	3/4"	1/2"
2025-8241	3/4"	3/4"
2025-8251	1"	1/2"
2025-8261	1"	1"
2025-8271	1"	3/4"
2025-8281	1.1/4"	1/2"
2025-8291	1.1/4"	3/4"
2025-8301	1.1/4"	1"
2025-8311	1.1/4"	1.1/4"
2025-8321	1.1/2"	3/4"
2025-8331	1.1/2"	1"
2025-8341	1.1/2"	1.1/2"
2025-8351	1.1/2"	1.1/4"
2025-8361	2"	2"
Tech Sheet 20884		

Fluid-Air Components Ltd

HYDRAULIC STAINLESS STEEL ADAPTORS

stainless steel

PANAM

Female x Female Straight Adaptors



Swivel, BSPP

0044	Thread	Thread
2025-2078	1/4"	1/4"
2025-2082	3/8"	1/4"
2025-2086	3/8"	3/8"
2025-2089	1/2"	1/4"
2025-2093	1/2"	3/8"
2025-2094	1/2"	1/2"
2025-2100	5/8"	5/8"
2025-2122	3/4"	1/2"
2025-2132	3/4"	3/4"
2025-2110	1"	1"

Tech Sheet 20884

Fixed Female Hexagon Socket, BSPP



0044	Thread
2025-2466	1/8"
2025-2474	1/4"
2025-2482	3/8"
2025-2490	1/2"
2025-2508	3/4"
2025-2516	1"

Tech Sheet 20884

Elbows



Equal Elbow, BSPP

0044	Thread
2033-9922	1/8"
2033-9933	1/4"
2033-9941	3/8"
2033-9958	1/2"
2033-9962	5/8"
2033-9963	3/4"
2033-9974	1"
2033-9982	1.1/4"
2033-9992	1.1/2"

Tech Sheet 20884

Male x Female Swivel, BSPP



0044	Thread
2025-2185	1/8"
2025-2193	1/4"
2025-2201	3/8"
2025-2219	1/2"
2025-2223	5/8"
2025-2227	3/4"
2025-2232	1"
2025-2240	1.1/4"
2025-2245	1.1/2"

Tech Sheet 20884

Female Swivel, BSPP



0044	Thread
2025-2128	1/8"
2025-2136	1/4"
2025-2151	1/2"
2025-2169	3/4"

Tech Sheet 20884

Tees



Male, BSPP

0044	Thread
2025-2321	1/8"
2025-2326	1/4"
2025-2334	3/8"
2025-2342	1/2"
2025-2449	3/4"
2025-2354	1"

Tech Sheet 20884



Female Swivel, BSPP

0044	Thread
2025-2250	1/4"
2025-2258	3/8"
2025-2263	1/2"
2025-2273	5/8"
2025-2283	3/4"
2025-2293	1"

Tech Sheet 20884



Female Swivel Branch, BSPP

0044	Thread
2025-4001	1/8"
2025-4011	1/4"
2025-4021	3/8"
2025-4031	1/2"
2025-4041	3/4"
2025-4051	1"

Tech Sheet 20884



Female Swivel Run, BSPP

0044	Thread
2025-4501	1/8"
2025-4511	1/4"
2025-4521	3/8"
2025-4531	1/2"
2025-4541	3/4"
2025-4551	1"

Tech Sheet 20884

Bulkhead complete with Locknut



BSPP

0044	Thread
2025-2391	1/4"
2025-2409	3/8"
2025-2417	1/2"
2025-2425	5/8"
2025-2433	3/4"
2025-2441	1"
2025-2445	1.1/4"
2025-2450	1.1/2"

Tech Sheet 20884

Plugs



BSPP

0044	Thread
2033-4002	1/8"
2033-4012	1/4"
2033-4022	3/8"
2033-4032	1/2"
2033-4042	5/8"
2033-4052	3/4"
2033-4062	1"
2033-4072	1.1/4"
2033-4082	1.1/2"
2033-4092	2"

Tech Sheet 20884



BSPT

0044	Thread
2025-2524	1/8"
2025-2532	1/4"
2025-2540	3/8"
2025-2557	1/2"
2025-2565	3/4"
2025-2573	1"
2025-2582	1.1/4"
2025-2592	1.1/2"
2025-2602	2"

Tech Sheet 20884

Caps



BSPP

0044	Thread
2033-8301	1/8"
2033-8311	1/4"
2033-8321	3/8"
2033-8331	1/2"
2033-8341	3/4"
2033-8351	1"

Tech Sheet 20884

316 PRECISION INSTRUMENTATION PIPE FITTINGS

stainless steel

PANAM

Hexagon Nipples



Male x Male, NPT

0342	Thread
PHN-01	1/16"
PHN-02	1/8"
PHN-04	1/4"
PHN-06	3/8"
PHN-08	1/2"
PHN-12	3/4"
PHN-16	1"
Tech Sheet 20885	

Hexagon Nipples, Long



Male x Male, NPT

0342	Thread	Length
PHNL-02-L1.5	1/8"	1.5"
PHNL-02-L2	1/8"	2"
PHNL-02-L3	1/8"	3"
PHNL-02-L4	1/8"	4"
PHNL-02-L6	1/8"	6"
PHNL-04-L1.5	1/4"	1.5"
PHNL-04-L2	1/4"	2"
PHNL-04-L3	1/4"	3"
PHNL-04-L4	1/4"	4"
PHNL-04-L6	1/4"	6"
PHNL-06-L1.5	3/8"	1.5"
PHNL-06-L2	3/8"	2"
PHNL-06-L3	3/8"	3"
PHNL-06-L4	3/8"	4"
PHNL-06-L6	3/8"	6"
PHNL-08-L1.5	1/2"	1.5"
PHNL-08-L2	1/2"	2"
PHNL-08-L3	1/2"	3"
PHNL-08-L4	1/2"	4"
PHNL-08-L6	1/2"	6"
PHNL-12-L2	3/4"	2"
PHNL-12-L3	3/4"	3"
PHNL-12-L4	3/4"	4"
PHNL-12-L6	3/4"	6"
PHNL-16-L1.5	1"	1.5"
PHNL-16-L2	1"	2"
PHNL-16-L3	1"	3"
PHNL-16-L4	1"	4"
PHNL-16-L6	1"	6"
Tech Sheet 20885		

Reducing Hexagon Nipples



Male x Male, NPT

0342	Thread	Thread
PRHN-02-01	1/8"	1/16"
PRHN-04-02	1/4"	1/8"
PRHN-06-02	3/8"	1/8"
PRHN-06-04	3/8"	1/4"
PRHN-08-02	1/2"	1/8"
PRHN-08-04	1/2"	1/4"
PRHN-08-06	1/2"	3/8"
PRHN-12-06	3/4"	1/4"
PRHN-12-08	3/4"	1/2"
PRHN-16-08	1"	1/2"
PRHN-16-12	1"	3/4"
Tech Sheet 20885		

Hexagon Coupling



Female x Female, NPT

0342	Thread
PHC-02	1/8"
PHC-04	1/4"
PHC-06	3/8"
PHC-08	1/2"
PHC-12	3/4"
PHC-16	1"
Tech Sheet 20885	

Reducing Hexagon Couplings



Female x Female, NPT

0342	Thread	Thread
PRC-04-02	1/4"	1/8"
PRC-06-04	3/8"	1/4"
PRC-08-02	1/2"	1/8"
PRC-08-04	1/2"	1/4"
PRC-08-06	1/2"	3/8"
PRC-12-04	3/4"	1/4"
PRC-12-08	3/4"	1/2"
PRC-16-08	1"	1/2"
Tech Sheet 20885		

Equal Male x Female Adaptors



Male x Female, NPT

0342	Thread
PPA-02	1/8"
PPA-04	1/4"
PPA-06	3/8"
PPA-08	1/2"
PPA-12	3/4"
PPA-16	1"
Tech Sheet 20885	

Reducing Male x Female Adaptors



Male x Female, NPT

0342	Male Thread	Female Thread
PRA-02-01	1/16"	1/8"
PRA-04-02	1/8"	1/4"
PRA-06-02	1/8"	3/8"
PRA-06-04	1/4"	3/8"
PRA-08-02	1/8"	1/2"
PRA-08-04	1/4"	1/2"
PRA-08-06	3/8"	1/2"
PRA-12-04	1/4"	3/4"
PRA-12-06	3/8"	3/4"
PRA-12-08	1/2"	3/4"
PRA-16-04	1/4"	1"
PRA-16-08	1/2"	1"
PRA-16-12	3/4"	1"
Tech Sheet 20885		

Gauge Adaptor



Male NPT x Female, BSPP

0342	Male Thread	Female Thread
PGA-04-04	1/4"	1/4"
PGA-06-06	3/8"	3/8"
PGA-08-08	1/2"	1/2"
Tech Sheet 20885		

Fluid-Air Components Ltd

316 PRECISION INSTRUMENTATION PIPE FITTINGS

stainless steel

PANAM

Reducing Bushes



Male x Female, NPT

0342	Male Thread	Female Thread
PRB-02-01	1/8"	1/16"
PRB-04-02	1/4"	1/8"
PRB-06-02	3/8"	1/8"
PRB-06-04	3/8"	1/4"
PRB-08-02	1/2"	1/8"
PRB-08-04	1/2"	1/4"
PRB-08-06	1/2"	3/8"
PRB-12-04	3/4"	1/4"
PRB-12-06	3/4"	3/8"
PRB-12-08	3/4"	1/2"
PRB-16-04	1"	1/4"
PRB-16-06	1"	3/8"
PRB-16-08	1"	1/2"
PRB-16-12	1"	3/4"

Tech Sheet 20885

Pipe Caps



NPT

0342	Thread
PCP-02	1/8"
PCP-04	1/4"
PCP-06	3/8"
PCP-08	1/2"
PCP-12	3/4"
PCP-16	1"

Tech Sheet 20885

Pipe Plugs



NPT

0342	Thread
PP-01	1/16"
PP-02	1/8"
PP-04	1/4"
PP-06	3/8"
PP-08	1/2"
PP-12	3/4"
PP-16	1"

Tech Sheet 20885

Equal Elbows



Female, NPT

0342	Thread
PPFE-02	1/8"
PPFE-04	1/4"
PPFE-06	3/8"
PPFE-08	1/2"
PPFE-12	3/4"
PPFE-16	1"

Tech Sheet 20885



Male, NPT

0342	Thread
PPME-02	1/8"
PPME-04	1/4"
PPME-06	3/8"
PPME-08	1/2"

Tech Sheet 20885



Male x Female, NPT

0342	Thread
PSE-01	1/16"
PSE-02	1/8"
PSE-04	1/4"
PSE-06	3/8"
PSE-08	1/2"
PSE-12	3/4"
PSE-16	1"

Tech Sheet 20885

Equal Tees



Female, NPT

0342	Thread
PFT-02	1/8"
PFT-04	1/4"
PFT-06	3/8"
PFT-08	1/2"
PFT-12	3/4"
PFT-16	1"

Tech Sheet 20885



Male, NPT

0342	Thread
PMT-02	1/8"
PMT-04	1/4"
PMT-06	3/8"
PMT-08	1/2"

Tech Sheet 20885

Branch Tees



Female x Male, NPT

0342	Thread
PBT-02	1/8"
PBT-04	1/4"
PBT-06	3/8"
PBT-08	1/2"

Tech Sheet 20885

Equal Crosses



Female, NPT

0342	Thread
PPC-02	1/8"
PPC-04	1/4"
PPC-06	3/8"
PPC-08	1/2"
PPC-12	3/4"
PPC-16	1"

Tech Sheet 20885

Fluid-Air Components Ltd

316 STAINLESS STEEL ADAPTORS

stainless steel

AIGNEP

Threads:
Tapered gas in conformity with ISO 7.1, BS 21, DIN 2999.
Parallel gas in conformity with ISO 228 Class A.
Metric in conformity with ISO R/262.

Working Temperature:
-110°C to +300°C

Maximum Working Pressure:
-0.99 - 140 bar

Adaptors



Equal Male Thread, BSPT

0188	Thread
62000-1/8	1/8"
62000-1/4	1/4"
62000-3/8	3/8"
62000-1/2	1/2"
62000-3/4	3/4"
Tech Sheet 10708	



Unequal Male Thread, BSPT

0188	Thread	Thread
62020-1/8-1/4	1/8"	1/4"
62020-1/8-3/8	1/8"	3/8"
62020-1/4-3/8	1/4"	3/8"
62020-1/4-1/2	1/4"	1/2"
62020-3/8-1/2	3/8"	1/2"
62020-1/2-3/4	1/2"	3/4"
Tech Sheet 10708		



Male Thread, BSPT x Female Thread, BSPP

0188	Male Thread	Female Thread
62040-1/8-1/4	1/8"	1/4"
62040-1/4-3/8	1/4"	3/8"
62040-1/4-1/2	1/4"	1/2"
62040-3/8-1/2	3/8"	1/2"
62040-1/2-3/4	1/2"	3/4"
Tech Sheet 10708		

Reducing Bush



Male Thread, BSPT x Female Thread, BSPP

0188	Male Thread	Female Thread
62080-1/4-1/8	1/4"	1/8"
62080-3/8-1/8	3/8"	1/8"
62080-3/8-1/4	3/8"	1/4"
62080-1/2-1/4	1/2"	1/4"
62080-1/2-3/8	1/2"	3/8"
62080-3/4-1/2	3/4"	1/2"
Tech Sheet 10708		

Sockets



Equal Female Thread, BSPP

0188	Thread
62300-1/8	1/8"
62300-1/4	1/4"
62300-3/8	3/8"
62300-1/2	1/2"
62300-3/4	3/4"
Tech Sheet 10708	



Unequal Female Thread, BSPP

0188	Thread	Thread
62310-1/8-1/4	1/8"	1/4"
62310-1/4-3/8	1/4"	3/8"
62310-3/8-1/2	3/8"	1/2"
62310-1/2-3/4	1/2"	3/4"
Tech Sheet 10708		

Blanking Plugs



FKM O-Ring & Hexagon Recess, Male Thread, BSPP

0188	Thread
62315-M5	M5
62315-1/8	1/8"
62315-1/4	1/4"
62315-3/8	3/8"
62315-1/2	1/2"
Tech Sheet 10708	



Male Thread, BSPP

0188	Thread
62320-1/8	1/8"
62320-1/4	1/4"
62320-3/8	3/8"
62320-1/2	1/2"
62320-3/4	3/4"
Tech Sheet 10708	

Male Plugs



Male Thread, BSPT

0188	Thread
62325-1/8	1/8"
62325-1/4	1/4"
62325-3/8	3/8"
62325-1/2	1/2"
Tech Sheet 10708	

Fluid-Air Components Ltd

316 STAINLESS STEEL ADAPTORS

stainless steel

AIGNEP

Threads:
Tapered gas in conformity with ISO 7.1, BS 21, DIN 2999.
Parallel gas in conformity with ISO 228 Class A.
Metric in conformity with ISO R/262.

Working Temperature:
-110°C to +300°C

Maximum Working Pressure:
-0.99 - 140 bar

Equal Tees



Female Thread, BSPP

0188	Thread
62400-1/8	1/8"
62400-1/4	1/4"
62400-3/8	3/8"
62400-1/2	1/2"

Tech Sheet 10708



Female BSPP Run Tee x Male BSPT Branch

0188	Thread
62440-1/8	1/8"
62440-1/4	1/4"
62440-3/8	3/8"
62440-1/2	1/2"

Tech Sheet 10708



Male BSPT x Female BSPP Run Tee x Female BSPP Branch

0188	Thread
62450-1/8	1/8"
62450-1/4	1/4"
62450-3/8	3/8"
62450-1/2	1/2"

Tech Sheet 10708

Equal Elbows



Female Thread, BSPP

0188	Thread
62510-1/8	1/8"
62510-1/4	1/4"
62510-3/8	3/8"
62510-1/2	1/2"

Tech Sheet 10708



Male Thread, BSPT x Female Thread, BSPP

0188	Thread
62520-1/8	1/8"
62520-1/4	1/4"
62520-3/8	3/8"
62520-1/2	1/2"

Tech Sheet 10708

Bulkhead with Locknut



Female Thread, BSPP

0188	Thread
62360-1/8	1/8"
62360-1/4	1/4"
62360-3/8	3/8"
62360-1/2	1/2"
62360-3/4	3/4"

Tech Sheet 10708

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Male Stud Couplings



UNF

0215	Thread
205BM6	7/16"-20
205BM8	1/2"-20
205BM10	9/16"-18
205BM12	3/4"-16
205BM16	7/8"-14
205BM20	1.1/16"-12
205BM22	1.3/16"-12
205BM25	1.5/16"-12
205BM32	1.5/8"-12
Tech Sheet 20886	



UNF x BSPT

0215	Thread	Thread
210BM6R18	7/16"-20	1/8"
210BM6R14	7/16"-20	1/4"
210BM6R12	7/16"-20	1/2"
210BM8R18	1/2"-20	1/8"
210BM8R14	1/2"-20	1/4"
210BM10R14	9/16"-18	1/4"
210BM10R18	9/16"-18	1/8"
210BM10R38	9/16"-18	3/8"
210BM10R12	9/16"-18	1/2"
210BM12R14	3/4"-16	1/4"
210BM12R38	3/4"-16	3/8"
210BM12R12	3/4"-16	1/2"
210BM16R12	7/8"-14	1/2"
210BM16R34	7/8"-14	3/4"
210BM20R12	1.1/16"-12	1/2"
210BM20R34	1.1/16"-12	3/4"
210BM20R1	1.1/16"-12	1"
210BM22R34	1.3/16"-12	3/4"
210BM25R34	1.5/16"-12	3/4"
210BM25R1	1.5/16"-12	1"
210BM32R1	1.5/8"-12	1"
210BM32R114	1.5/8"-12	1.1/4"
210BM38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		



UNF x BSPP

0215	Thread	Thread
210SM6G18	7/16"-20	1/8"
210SM6G14	7/16"-20	1/4"
210SM6G38	7/16"-20	3/8"
210SM6G12	7/16"-20	1/2"
210SM8G18	1/2"-20	1/8"
210SM8G14	1/2"-20	1/4"
210SM8G38	1/2"-20	3/8"
210SM10G18	9/16"-18	1/8"
210SM10G14	9/16"-18	1/4"
210SM10G38	9/16"-18	3/8"
210SM10G12	9/16"-18	1/2"
210SM12G14	3/4"-16	1/4"
210SM12G38	3/4"-16	3/8"
210SM12G12	3/4"-16	1/2"
210SM12G34	3/4"-16	3/4"
210SM16G38	7/8"-14	3/8"
210SM16G12	7/8"-14	1/2"
210SM16G34	7/8"-14	3/4"
210SM20G12	1.1/16"-12	1/2"
210SM20G34	1.1/16"-12	3/4"
210SM20G1	1.1/16"-12	1"
210SM22G34	1.3/16"-12	3/4"
210SM25G34	1.5/16"-12	3/4"
210SM25G1	1.5/16"-12	1"
210SM25G114	1.5/16"-12	1.1/4"
210SM32G1	1.5/8"-12	1"
210SM32G114	1.5/8"-12	1.1/4"
210SM38G114	1.7/8"-12	1.1/4"
210SM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		



UNF x NPT

0215	Thread	Thread
214BM6N18	7/16"-20	1/8"
214BM6N14	7/16"-20	1/4"
214BM8N18	1/2"-20	1/8"
214BM8N14	1/2"-20	1/4"
214BM10N18	9/16"-18	1/8"
214BM10N14	9/16"-18	1/4"
214BM10N38	9/16"-18	3/8"
214BM10N12	9/16"-18	1/2"
214BM12N14	3/4"-16	1/4"
214BM12N38	3/4"-16	3/8"
214BM12N12	3/4"-16	1/2"
214BM12N34	3/4"-16	3/4"
214BM16N12	7/8"-14	1/2"
214BM20N12	1.1/16"-12	1/2"
214BM20N34	1.1/16"-12	3/4"
214BM20N1	1.1/16"-12	1"
214BM25N34	1.5/16"-12	3/4"
214BM25N1	1.5/16"-12	1"
214BM32N1	1.5/8"-12	1"
214BM32N114	1.5/8"-12	1.1/4"
214BM38N114	1.7/8"-12	1.1/4"
214BM38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

stainless steel



For **316 Stainless Steel Tubing** see page **1287**

For Flaretite Seals see page 111

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Female Stud Couplings



Male UNF x Female BSPP

0215	Male Thread	Female Thread
230BM6G18	7/16"-20	1/8"
230BM6G14	7/16"-20	1/4"
230BM6G12	7/16"-20	1/2"
230BM8G14	1/2"-20	1/4"
230BM10G18	9/16"-18	1/8"
230BM10G14	9/16"-18	1/4"
230BM10G38	9/16"-18	3/8"
230BM10G12	9/16"-18	1/2"
230BM12G14	3/4"-16	1/4"
230BM12G38	3/4"-16	3/8"
230BM12G12	3/4"-16	1/2"
230BM12G34	3/4"-16	3/4"
230BM16G38	7/8"-14	3/8"
230BM16G12	7/8"-14	1/2"
230BM16G34	7/8"-14	3/4"
230BM18G1	1.1/16"-12	1"
230BM22G34	1.3/16"-12	3/4"
230BM25G34	1.5/16"-12	3/4"
230BM25G1	1.5/16"-12	1"
230BM32G1	1.5/8"-12	1"
230BM32G114	1.5/8"-12	1.1/4"
230BM38G114	1.7/8"-12	1.1/2"
230BM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Male UNF x Female NPT

0215	Male Thread	Female Thread
232BM6N18	7/16"-20	1/8"
232BM6N14	7/16"-20	1/4"
232BM8N14	1/2"-20	1/4"
232BM10N14	9/16"-18	1/4"
232BM10N38	9/16"-18	3/8"
232BM12N12	3/4"-16	1/2"
232BM20N12	1.1/16"-12	1/2"
232BM20N34	1.1/16"-12	3/4"
232BM25N1	1.5/16"-12	1"
232BM32N114	1.5/8"-12	1.1/4"
232BM38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Male UNF x Female BSPT

0215	Male Thread	Female Thread
231M6R18	7/16"-20	1/8"
231M6R14	7/16"-20	1/4"
231M6R12	7/16"-20	1/2"
231M8R18	1/2"-20	1/8"
231M8R14	1/2"-20	1/4"
231M10R18	9/16"-18	1/8"
231M10R14	9/16"-18	1/4"
231M10R38	9/16"-18	3/8"
231M10R12	9/16"-18	1/2"
231M12R14	3/4"-16	1/4"
231M12R38	3/4"-16	3/8"
231M12R12	3/4"-16	1/2"
231M12R34	3/4"-16	3/4"
231M16R38	7/8"-14	3/8"
231M16R12	7/8"-14	1/2"
231M16R34	7/8"-14	3/4"
231M18R34	1.1/16"-12	3/4"
231M18R1	1.1/16"-12	1"
231M22R34	1.3/16"-12	3/4"
231M25R34	1.5/16"-12	3/4"
231M25R1	1.5/16"-12	1"
231M32R1	1.5/8"-12	1"
231M32R114	1.5/8"-12	1.1/4"
231M38R114	1.7/8"-12	1.1/4"
231M38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Female Swivel Connectors



Male UNF x Female UNF

0215	Male Thread	Female Thread
273M6U716	7/16"-20	7/16"-20
273M8U716	1/2"-20	7/16"-20
273M8U12	1/2"-20	1/2"-20
273M10U716	9/16"-18	7/16"-20
273M10U916	9/16"-18	9/16"-18
273M12U916	3/4"-16	9/16"-18
273M16U34	7/8"-14	3/4"-16
273M18U34	1.1/16"-12	3/4"-16
273M18U1116	1.1/16"-12	1.1/16"-12
273M22U1116	1.3/16"-12	1.1/16"-12
273M25U1116	1.5/16"-12	1.1/16"-12
273M25U1516	1.5/16"-12	1.5/16"-12
Tech Sheet 20886		



Male BSPP x Female UNF

0215	Male Thread	Female Thread
273M6G18	1/8"	7/16"-20
273M8G18	1/8"	1/2"-20
273M8G14	1/4"	1/2"-20
273M10G14	1/4"	9/16"-18
273M10G38	3/8"	9/16"-18
273M12G38	3/8"	3/4"-16
273M16G12	1/2"	7/8"-14
273M20G34	3/4"	1.1/16"-12
273M22G34	3/4"	1.3/16"-12
273M25G1	1"	1.5/16"-12
273M32G114	1.1/4"	1.5/8"-12
273M38G112	1.1/2"	1.7/8"-12
Tech Sheet 20886		



Male NPT x Female UNF

0215	Male Thread	Female Thread
276M6N18	1/8"	7/16"-20
276M8N18	1/8"	1/2"-20
276M6N14	1/4"	7/16"-20
276M8N14	1/4"	1/2"-20
276M10N14	1/4"	9/16"-18
276M10N38	3/8"	9/16"-18
276M12N38	3/8"	3/4"-16
276M16N12	1/2"	7/8"-14
276M20N12	1/2"	1.1/16"-12
276M20N34	3/4"	1.1/16"-12
276M22N34	3/4"	1.3/16"-12
276M25N34	3/4"	1.5/16"-12
276M25N1	1"	1.5/16"-12
276M32N114	1.1/4"	1.5/8"-12
276M38N112	1.1/2"	1.7/8"-12
Tech Sheet 20886		



Male BSPT x Female UNF

0215	Male Thread	Female Thread
273M6R18	1/8"	7/16"-20
273M8R14	1/4"	1/2"-20
273M10R14	1/4"	9/16"-18
273M12R14	1/4"	3/4"-16
273M12R38	3/8"	3/4"-16
273M16R12	1/2"	7/8"-14
273M20R12	1/2"	1.1/16"-12
273M20R34	3/4"	1.1/16"-12
273M22R34	3/4"	1.3/16"-12
273M25R34	3/4"	1.5/16"-12
273M25R1	1"	1.5/16"-12
273M32R114	1.1/4"	1.5/8"-12
273M38R112	1.1/2"	1.7/8"-12
Tech Sheet 20886		

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Bulkhead Unions



Bulkhead complete with Locknut, UNF

0215	Thread
204M6U716	7/16"-20
204M8U12	1/2"-20
204M10U916	9/16"-18
204M12U34	3/4"-16
204M16U78	7/8"-14
204M18U1116	1.1/16"-12
204M22U1316	1.3/16"-12
204M25U1516	1.5/16"-12
204M32U158	1.5/8"-12
204M38U178	1.7/8"-12
Tech Sheet 20886	

Bulkhead Locknuts

0215	Thread
199M6U716	7/16"-20
199M8U12	1/2"-20
199M10U916	9/16"-18
199M12U34	3/4"-16
199M16U78	7/8"-14
199M18U1116	1.1/16"-12
199M22U1316	1.3/16"-12
199M25U1516	1.5/16"-12
199M32U158	1.5/8"-12
199M38U178	1.7/8"-12
Tech Sheet 20886	

Fixed Elbows



UNF

0215	Thread
206BM6	7/16"-20
206BM8	1/2"-20
206BM12	3/4"-16
206BM20	1.1/16"-12
206BM22	1.3/16"-12
206BM25	1.5/16"-12
206BM32	1.5/8"-12
206BM38	1.7/8"-12
Tech Sheet 20886	

UNF Male x BSPT Male

0215	Thread	Thread
206M6R18	7/16"-20	1/8"
206M6R14	7/16"-20	1/4"
206M6R12	7/16"-20	1/2"
206M8R18	1/2"-20	1/8"
206M8R14	1/2"-20	1/4"
206M10R18	9/16"-18	1/8"
206M10R14	9/16"-18	1/4"
206M10R38	9/16"-18	3/8"
206M10R12	9/16"-18	1/2"
206M12R14	3/4"-16	1/4"
206M12R38	3/4"-16	3/8"
206M12R12	3/4"-16	1/2"
206M12R34	3/4"-16	3/4"
206M16R38	7/8"-14	3/8"
206M16R12	7/8"-14	1/2"
206M16R34	7/8"-14	3/4"
206M18R34	1.1/16"-12	3/4"
206M18R1	1.1/16"-12	1"
206M22R34	1.3/16"-12	3/4"
206M25R34	1.5/16"-12	3/4"
206M25R1	1.5/16"-12	1"
206M32R1	1.5/8"-12	1"
206M32R114	1.5/8"-12	1.1/4"
206M38R114	1.7/8"-12	1.1/4"
206M38R112	1.7/8"-12	1.1/2"
Tech Sheet 20886		



UNF Male x 45° NPT Male

0215	Thread	Thread
285M6N18	7/16"-20	1/8"
285M8N14	1/2"-20	1/8"
285M10N12	9/16"-18	1/4"
285M12N18	3/4"-16	3/8"
285M16N14	7/8"-14	1/2"
285M18N18	1.1/16"-12	3/4"
285M22N14	1.3/16"-12	3/4"
285M25N38	1.5/16"-12	1"
285M32N12	1.5/8"-12	1.1/4"
285M38N14	1.7/8"-12	1.1/2"
Tech Sheet 20886		



For **Hydraulic Oil** see page **283**

For Flaretite Seals see page 111

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Swivel Elbows



Male x Female, UNF

0215	Thread
275M6U716	7/16"-20
275M8U12	1/2"-20
275M10U916	9/16"-18
275M12U34	3/4"-16
275M16U78	7/8"-14
275M18U1116	1.1/16"-12
275M22U1316	1.3/16"-12
275M25U1516	1.5/16"-12
275M32U158	1.5/8"-12
275M38U178	1.7/8"-12
Tech Sheet 20886	



NPT Male x UNF Female

0215	Thread	Thread
275M6N18	7/16"-20	1/8"
275M6N14	7/16"-20	1/4"
275M6N12	7/16"-20	1/2"
275M8N18	1/2"-20	1/8"
275M8N14	1/2"-20	1/4"
275M10N18	9/16"-18	1/8"
275M10N14	9/16"-18	1/4"
275M10N38	9/16"-18	3/8"
275M10N12	9/16"-18	1/2"
275M12N14	3/4"-16	1/4"
275M12N38	3/4"-16	3/8"
275M12N12	3/4"-16	1/2"
275M12N34	3/4"-16	3/4"
275M16N38	7/8"-14	3/8"
275M16N12	7/8"-14	1/2"
275M16N34	7/8"-14	3/4"
275M18N34	1.1/16"-12	3/4"
275M18N1	1.1/16"-12	1"
275M22N34	1.3/16"-12	3/4"
275M25N34	1.5/16"-12	3/4"
275M25N1	1.5/16"-12	1"
275M32N1	1.5/8"-12	1"
275M32N114	1.5/8"-12	1.1/4"
275M38N114	1.7/8"-12	1.1/4"
275M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		



Equal Female, UNF

0215	Thread
265M6U716	7/16"-20
265M8U12	1/2"-20
265M10U916	9/16"-18
265M12U34	3/4"-16
265M16U78	7/8"-14
265M18U1116	1.1/16"-12
265M22U1316	1.3/16"-12
265M25U1516	1.5/16"-12
265M32U158	1.5/8"-12
265M38U178	1.7/8"-12
Tech Sheet 20886	

90º Position Elbows



UNF x BSPP

0215	Thread	Thread
216SM6G18	7/16"-20	1/8"
216SM6G14	7/16"-20	1/4"
216SM8G18	1/2"-20	1/8"
216SM10G38	9/16"-18	3/8"
216SM12G14	3/4"-16	1/4"
216SM12G38	3/4"-16	3/8"
216SM12G12	3/4"-16	1/2"
216SM12G34	3/4"-16	3/4"
216SM16G14	7/8"-14	1/4"
216SM16G38	7/8"-14	3/8"
216SM16G12	7/8"-14	1/2"
216SM16G34	7/8"-14	3/4"
216SM20G12	1.1/16"-12	1/2"
216SM20G34	1.1/16"-12	3/4"
216SM22G12	1.3/16"-12	1/2"
216SM22G34	1.3/16"-12	3/4"
216SM22G1	1.3/16"-12	1/2"
216SM25G12	1.5/16"-12	1/2"
216SM25G1	1.5/16"-12	1"
216SM32G1	1.5/8"-12	1"
216SM38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Fixed Tees



UNF

0215	Thread
207BM6	7/16"-20
207BM8	1/2"-20
207BM10	9/16"-18
207BM12	3/4"-16
207BM16	7/8"-14
207BM20	1.1/16"-12
207BM22	1.3/16"-12
207BM25	1.5/16"-12
207BM32	1.5/8"-12
Tech Sheet 20886	



UNF Male x NPT Male Branch

0215	Thread	Thread
307M6N18	7/16"-20	1/8"
307M6N14	7/16"-20	1/4"
307M6N12	7/16"-20	1/2"
307M8N18	1/2"-20	1/8"
307M8N14	1/2"-20	1/4"
307M10N18	9/16"-18	1/8"
307M10N14	9/16"-18	1/4"
307M10N38	9/16"-18	3/8"
307M10N12	9/16"-18	1/2"
307M12N14	3/4"-16	1/4"
307M12N38	3/4"-16	3/8"
307M12N12	3/4"-16	1/2"
307M12N34	3/4"-16	3/4"
307M16N38	7/8"-14	3/8"
307M16N12	7/8"-14	1/2"
307M16N34	7/8"-14	3/4"
307M18N34	1.1/16"-12	3/4"
307M18N1	1.1/16"-12	1"
307M22N34	1.3/16"-12	3/4"
307M25N34	1.5/16"-12	3/4"
307M25N1	1.5/16"-12	1"
307M32N1	1.5/8"-12	1"
307M32N114	1.5/8"-12	1.1/4"
307M38N114	1.7/8"-12	1.1/4"
307M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

For Flaretite Seals see page 111

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Fixed Tees



UNF Male x NPT Male Run

0215	Thread	Thread
309M6N18	7/16"-20	1/8"
309M6N14	7/16"-20	1/4"
309M6N12	7/16"-20	1/2"
309M8N18	1/2"-20	1/8"
309M8N14	1/2"-20	1/4"
309M10N18	9/16"-18	1/8"
309M10N14	9/16"-18	1/4"
309M10N38	9/16"-18	3/8"
309M10N12	9/16"-18	1/2"
309M12N14	3/4"-16	1/4"
309M12N38	3/4"-16	3/8"
309M12N12	3/4"-16	1/2"
309M12N34	3/4"-16	3/4"
309M16N38	7/8"-14	3/8"
309M16N12	7/8"-14	1/2"
309M16N34	7/8"-14	3/4"
309M18N34	1.1/16"-12	3/4"
309M18N1	1.1/16"-12	1"
309M22N34	1.3/16"-12	3/4"
309M25N34	1.5/16"-12	3/4"
309M25N1	1.5/16"-12	1"
309M32N1	1.5/8"-12	1"
309M32N114	1.5/8"-12	1.1/4"
309M38N114	1.7/8"-12	1.1/4"
309M38N112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Swivel Tees



Female Swivel, UNF

0215	Thread
310M6U716	7/16"-20
310M8U12	1/2"-20
310M10U916	9/16"-18
310M12U34	3/4"-16
310M16U78	7/8"-14
310M18U1116	1.1/16"-12
310M22U1316	1.3/16"-12
310M25U1516	1.5/16"-12
310M32U158	1.5/8"-12
310M38U178	1.7/8"-12
Tech Sheet 20886	



Female Swivel Branch, UNF

0215	Thread
314M6U716	7/16"-20
314M8U12	1/2"-20
314M10U916	9/16"-18
314M12U34	3/4"-16
314M16U78	7/8"-14
314M18U1116	1.1/16"-12
314M22U1316	1.3/16"-12
314M25U1516	1.5/16"-12
314M32U158	1.5/8"-12
314M38U178	1.7/8"-12
Tech Sheet 20886	



Female Swivel Run, UNF

0215	Thread
312M6U716	7/16"-20
312M8U12	1/2"-20
312M10U916	9/16"-18
312M12U34	3/4"-16
312M16U78	7/8"-14
312M18U1116	1.1/16"-12
312M22U1316	1.3/16"-12
312M25U1516	1.5/16"-12
312M32U158	1.5/8"-12
312M38U178	1.7/8"-12
Tech Sheet 20886	

Position Tees



UNF Male x BSPP Male

0215	Thread	Thread
308M6G18	7/16"-20	1/8"
308M6G14	7/16"-20	1/4"
308M8G18	1/2"-20	1/8"
308M8G14	1/2"-20	1/4"
308M10G14	9/16"-18	1/4"
308M10G38	9/16"-18	3/8"
308M12G14	3/4"-16	1/4"
308M12G38	3/4"-16	3/8"
308M12G12	3/4"-16	1/2"
308M12G34	3/4"-16	3/4"
308M16G14	7/8"-14	1/4"
308M16G38	7/8"-14	3/8"
308M16G12	7/8"-14	1/2"
308M16G34	7/8"-14	3/4"
308M20G12	1.1/16"-12	1/2"
308M20G34	1.1/16"-12	3/4"
308M22G34	1.3/16"-12	1/2"
308M22G1	1.3/16"-12	3/4"
308M22G12	1.3/16"-12	1"
308M25G34	1.5/16"-12	1/2"
308M25G1	1.5/16"-12	3/4"
308M32G1	1.5/8"-12	1"
308M32G114	1.5/8"-12	1"
308M38G114	1.7/8"-12	1.1/4"
308M38G112	1.7/8"-12	1.1/2"
Tech Sheet 20886		

Cross



Male, UNF

0215	Thread
320M6U716	7/16"-20
320M8U12	1/2"-20
320M10U916	9/16"-18
320M12U34	3/4"-16
320M16U78	7/8"-14
320M18U1116	1.1/16"-12
320M22U1316	1.3/16"-12
320M25U1516	1.5/16"-12
320M32U158	1.5/8"-12
320M38U178	1.7/8"-12
Tech Sheet 20886	

For Flaretite Seals see page 111

Fluid-Air Components Ltd

37° JIC STAINLESS STEEL FLARE FITTINGS

stainless steel

PANAM

Swivel Caps



UNF

0215	Thread
289M6U716	7/16"-20
289M8U12	1/2"-20
289M10U916	9/16"-18
289M12U34	3/4"-16
289M16U78	7/8"-14
289M22U1316	1.3/16"-12
289M25U1516	1.5/16"-12
289M32U158	1.5/8"-12
289M38U178	1.7/8"-12

Tech Sheet 20886

Blanking Plugs



UNF

0215	Thread
299M6	7/16"-20
299M8	1/2"-20
299M10	9/16"-18
299M12	3/4"-16
299M16	7/8"-14
299M20	1.1/16"-12
299M22	1.3/16"-12
299M25	1.5/16"-12
299M32	1.5/8"-12
299M38	1.7/8"-12

Tech Sheet 20886

Reducing Adaptors



UNF Tube x UNF Male

0215	OD mm	OD mm	Male Thread
303M6U716	10	6	7/16"-20
303M6U34	12	6	3/4"-16
303M10U34	12	10	3/4"-16
303M6U78	16	6	7/8"-14
303M10U78	16	10	7/8"-14
303M6U1116	18	6	1.1/16"-12
303M10U1116	18	10	1.1/16"-12
303M12U1116	18	12	1.1/16"-12
303M10U1316	22	10	1.3/16"-12
303M16U1316	22	16	1.3/16"-12
303M6U1516	25	6	1.5/16"-12
303M10U1516	25	10	1.5/16"-12
303M12U1516	25	12	1.5/16"-12
303M16U1516	25	16	1.5/16"-12
303M18U1516	25	18	1.5/16"-12
303M18U158	32	18	1.5/8"-12
303M25U158	32	25	1.5/8"-12
303M12U178	38	12	1.7/8"-12
303M18U178	38	18	1.7/8"-12
303M25U178	38	25	1.7/8"-12

Tech Sheet 20886

Tube Nuts



UNF

0215	Thread
201M6U716	7/16"-20
201M8U12	1/2"-20
201M10U916	9/16"-18
201M12U34	3/4"-16
201M16U78	7/8"-14
201M20U1116	1.1/16"-12
201M22U1316	1.3/16"-12
201M25U1516	1.5/16"-12
201M32U158	1.5/8"-12
201M38U178	1.7/8"-12

Tech Sheet 20886

Flare Sleeves



Metric

0215	OD mm
203M6	6
203M8	8
203M10	10
203M12	12
203M14	14
203M15	15
203M16Z58	16
203M18	18
203M20	20
203M25	25
203M30	30
203M32	32
203M38Z112	38

Tech Sheet 20886

Imperial

0215	OD
203Z14	1/4"
203Z516	5/16"
203Z38	3/8"
203Z12	1/2"
203M15Z58	5/8"
203Z34	3/4"
203Z1	1"

Tech Sheet 20886

For Flaretite Seals see page 111

Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60º coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Male Straight Adaptors



BSPP x BSPP

0339	Thread	Thread
2G-2G-MM-10K	1/8"	1/8"
2G-4G-MM-10K	1/8"	1/4"
2G-6G-MM-10K	1/8"	3/8"
2G-8G-MM-10K	1/8"	1/2"
2G-12G-MM-10K	1/8"	3/4"
2G-16G-MM-10K	1/8"	1"
4G-4G-MM-10K	1/4"	1/4"
4G-6G-MM-10K	1/4"	3/8"
4G-8G-MM-10K	1/4"	1/2"
4G-12G-MM-10K	1/4"	3/4"
4G-16G-MM-10K	1/4"	1"
6G-6G-MM-10K	3/8"	3/8"
6G-8G-MM-10K	3/8"	1/2"
6G-12G-MM-10K	3/8"	3/4"
6G-16G-MM-10K	3/8"	1"
8G-8G-MM-10K	1/2"	1/2"
8G-12G-MM-10K	1/2"	3/4"
8G-16G-MM-10K	1/2"	1"
12G-12G-MM-10K	3/4"	3/4"
12G-16G-MM-10K	3/4"	1"
16G-16G-MM-10K	1"	1"
Tech Sheet 20887		



BSPP x NPT

0339	Thread	Thread
2G-2N-MM-10K	1/8"	1/8"
2G-4N-MM-10K	1/8"	1/4"
2G-6N-MM-10K	1/8"	3/8"
2G-8N-MM-10K	1/8"	1/2"
2G-12N-MM-10K	1/8"	3/4"
2G-16N-MM-10K	1/8"	1"
4G-2N-MM-10K	1/4"	1/8"
4G-4N-MM-10K	1/4"	1/4"
4G-6N-MM-10K	1/4"	3/8"
4G-8N-MM-10K	1/4"	1/2"
4G-12N-MM-10K	1/4"	3/4"
4G-16N-MM-10K	1/4"	1"
6G-4N-MM-10K	3/8"	1/4"
6G-6N-MM-10K	3/8"	3/8"
6G-8N-MM-10K	3/8"	1/2"
6G-12N-MM-10K	3/8"	3/4"
6G-16N-MM-10K	3/8"	1"
8G-4N-MM-10K	1/2"	1/4"
8G-6N-MM-10K	1/2"	3/8"
8G-8N-MM-10K	1/2"	1/2"
8G-12N-MM-10K	1/2"	3/4"
8G-16N-MM-10K	1/2"	1"
12G-12N-MM-10K	3/4"	3/4"
12G-16N-MM-10K	3/4"	1"
16G-16N-MM-10K	1"	1"
Tech Sheet 20887		



BSPP x JIC

0339	Thread	Thread
2G-4J-MM-10K	1/8"	7/16"
2G-6J-MM-10K	1/8"	9/16"
4G-4J-MM-10K	1/4"	7/16"
4G-6J-MM-10K	1/4"	9/16"
4G-8J-MM-10K	1/4"	3/4"
6G-4J-MM-10K	3/8"	7/16"
6G-6J-MM-10K	3/8"	9/16"
6G-8J-MM-10K	3/8"	3/4"
6G-10J-MM-10K	3/8"	7/8"
6G-12J-MM-10K	3/8"	1.1/16"
8G-4J-MM-10K	1/2"	7/16"
8G-8J-MM-10K	1/2"	3/4"
8G-10J-MM-10K	1/2"	7/8"
8G-12J-MM-10K	1/2"	1.1/16"
8G-16J-MM-10K	1/2"	1.5/16"
12G-8J-MM-10K	3/4"	3/4"
12G-10J-MM-10K	3/4"	7/8"
12G-12J-MM-10K	3/4"	1.1/16"
12G-16J-MM-10K	3/4"	1.5/16"
16G-10J-MM-10K	1"	7/8"
16G-12J-MM-10K	1"	1.1/16"
16G-16J-MM-10K	1"	1.5/16"
Tech Sheet 20887		



NPT x NPT

0339	Thread	Thread
2N-2N-MM-10K	1/8"	1/8"
2N-4N-MM-10K	1/8"	1/4"
4N-4N-MM-10K	1/4"	1/4"
4N-6N-MM-10K	1/4"	3/8"
4N-8N-MM-10K	1/4"	1/2"
6N-2N-MM-10K	3/8"	1/8"
6N-6N-MM-10K	3/8"	3/8"
6N-8N-MM-10K	3/8"	1/2"
8N-2N-MM-10K	1/2"	1/8"
8N-8N-MM-10K	1/2"	1/2"
12N-2N-MM-10K	3/4"	1/8"
12N-4N-MM-10K	3/4"	1/4"
12N-6N-MM-10K	3/4"	3/8"
12N-8N-MM-10K	3/4"	1/2"
12N-12N-MM-10K	3/4"	3/4"
16N-2N-MM-10K	1"	1/8"
16N-4N-MM-10K	1"	1/4"
16N-6N-MM-10K	1"	3/8"
16N-8N-MM-10K	1"	1/2"
16N-12N-MM-10K	1"	3/4"
16N-16N-MM-10K	1"	1"
Tech Sheet 20887		



NPT x JIC

0339	Thread	Thread
2N-2J-MM-10K	1/8"	5/16"
2N-4J-MM-10K	1/8"	7/16"
4N-4J-MM-10K	1/4"	7/16"
4N-6J-MM-10K	1/4"	9/16"
4N-8J-MM-10K	1/4"	3/4"
6N-4J-MM-10K	3/8"	7/16"
6N-6J-MM-10K	3/8"	9/16"
6N-8J-MM-10K	3/8"	3/4"
6N-12J-MM-10K	3/8"	1.1/16"
8N-4J-MM-10K	1/2"	7/16"
8N-6J-MM-10K	1/2"	9/16"
8N-8J-MM-10K	1/2"	3/4"
8N-12J-MM-10K	1/2"	1.1/16"
12N-8J-MM-10K	3/4"	3/4"
12N-12J-MM-10K	3/4"	1.1/16"
12N-16J-MM-10K	3/4"	1.5/16"
16N-12J-MM-10K	1"	1.1/16"
16N-16J-MM-10K	1"	1.5/16"
Tech Sheet 20887		



JIC x JIC

0339	Thread	Thread
4J-4J-MM-10K	7/16"	7/16"
4J-6J-MM-10K	7/16"	9/16"
4J-8J-MM-10K	7/16"	3/4"
6J-6J-MM-10K	9/16"	9/16"
6J-8J-MM-10K	9/16"	3/4"
6J-10J-MM-10K	9/16"	7/8"
8J-8J-MM-10K	3/4"	3/4"
8J-10J-MM-10K	3/4"	7/8"
8J-12J-MM-10K	3/4"	1.1/16"
10J-10J-MM-10K	7/8"	7/8"
10J-12J-MM-10K	7/8"	1.1/16"
10J-16J-MM-10K	7/8"	1.5/16"
12J-16J-MM-10K	1.1/16"	1.5/16"
16J-16J-MM-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Straight Adaptors



BSPP x BSPP

0339	Male Thread	Female Thread
2G-2G-MF-A-10K	1/8"	1/8"
2G-4G-MF-A-10K	1/8"	1/4"
2G-6G-MF-A-10K	1/8"	3/8"
2G-8G-MF-A-10K	1/8"	1/2"
2G-12G-MF-A-10K	1/8"	3/4"
4G-4G-MF-A-10K	1/4"	1/4"
4G-6G-MF-A-10K	1/4"	3/8"
4G-8G-MF-A-10K	1/4"	1/2"
4G-12G-MF-A-10K	1/4"	3/4"
4G-16G-MF-A-10K	1/4"	1"
6G-6G-MF-A-10K	3/8"	3/8"
6G-8G-MF-A-10K	3/8"	1/2"
6G-12G-MF-A-10K	3/8"	3/4"
6G-16G-MF-A-10K	3/8"	1"
8G-8G-MF-A-10K	1/2"	1/2"
8G-12G-MF-A-10K	1/2"	3/4"
8G-16G-MF-A-10K	1/2"	1"
12G-12G-MF-A-10K	3/4"	3/4"
12G-16G-MF-A-10K	3/4"	1"
16G-16G-MF-A-10K	1"	1"
Tech Sheet 20887		



NPT x NPT

0339	Male Thread	Female Thread
2N-2N-MF-A-10K	1/8"	1/8"
2N-4N-MF-A-10K	1/8"	1/4"
2N-6N-MF-A-10K	1/8"	3/8"
2N-8N-MF-A-10K	1/8"	1/2"
2N-12N-MF-A-10K	1/8"	3/4"
4N-4N-MF-A-10K	1/4"	1/4"
4N-6N-MF-A-10K	1/4"	3/8"
4N-8N-MF-A-10K	1/4"	1/2"
4N-12N-MF-A-10K	1/4"	3/4"
4N-16N-MF-A-10K	1/4"	1"
6N-6N-MF-A-10K	3/8"	3/8"
6N-8N-MF-A-10K	3/8"	1/2"
6N-12N-MF-A-10K	3/8"	3/4"
6N-16N-MF-A-10K	3/8"	1"
8N-8N-MF-A-10K	1/2"	1/2"
8N-12N-MF-A-10K	1/2"	3/4"
8N-16N-MF-A-10K	1/2"	1"
12N-12N-MF-A-10K	3/4"	3/4"
12N-16N-MF-A-10K	3/4"	1"
16N-16N-MF-A-10K	1"	1"
Tech Sheet 20887		



JIC x NPT

0339	Male Thread	Female Thread
4J-2N-MF-A-10K	7/16"-20	1/8"
4J-4N-MF-A-10K	7/16"-20	1/4"
6J-4N-MF-A-10K	9/16"-18	1/4"
4J-6N-MF-A-10K	7/16"-20	3/8"
6J-6N-MF-A-10K	9/16"-18	3/8"
8J-6N-MF-A-10K	3/4"-16	3/8"
8J-8N-MF-A-10K	9/16"-18	1/2"
10J-8N-MF-A-10K	3/4"-16	1/2"
12J-8N-MF-A-10K	7/8"-14	1/2"
12J-12N-MF-A-10K	3/4"-16	1/2"
16J-16N-MF-A-10K	7/8"-14	1/2"
Tech Sheet 20887		

BSPP x JIC, Swivel

0339	Male Thread	Female Thread
4G-4J-MF-10K	1/4"	7/16"
4G-5J-MF-10K	1/4"	1/2"
4G-6J-MF-10K	1/4"	9/16"
6G-6J-MF-10K	3/8"	9/16"
8G-6J-MF-10K	1/2"	9/16"
6G-8J-MF-10K	3/8"	3/4"
8G-8J-MF-10K	1/2"	3/4"
6G-10J-MF-10K	3/8"	7/8"
8G-10J-MF-10K	1/2"	7/8"
12G-10J-MF-10K	3/4"	7/8"
8G-12J-MF-10K	1/2"	1.1/16"
12G-12J-MF-10K	3/4"	1.1/16"
16G-12J-MF-10K	1"	1.1/16"
12G-16J-MF-10K	3/4"	1.5/16"
16G-16J-MF-10K	1"	1.5/16"
Tech Sheet 20887		



NPT x JIC, Swivel


0339	Male Thread	Female Thread
4N-4J-MF-10K	1/4"	7/16"
6N-6J-MF-10K	3/8"	9/16"
6N-8J-MF-10K	3/8"	3/4"
8N-10J-MF-10K	1/2"	7/8"
8N-12J-MF-10K	1/2"	1.1/16"
12N-12J-MF-10K	3/4"	1.1/16"
12N-14J-MF-10K	3/4"	1.3/16"
12N-16J-MF-10K	3/4"	1.5/16"
16N-16J-MF-10K	1"	1.5/16"
Tech Sheet 20887		



JIC x JIC, Swivel

0339	Male Thread	Female Thread
4J-4J-MF-10K	7/16"	7/16"
4J-6J-MF-10K	7/16"	9/16"
4J-8J-MF-10K	7/16"	3/4"
6J-4J-MF-10K	9/16"	7/16"
6J-6J-MF-10K	9/16"	9/16"
6J-8J-MF-10K	9/16"	3/4"
8J-4J-MF-10K	3/4"	7/16"
8J-6J-MF-10K	3/4"	9/16"
10J-8J-MF-10K	7/8"	3/4"
12J-8J-MF-10K	1.1/16"	3/4"
12J-12J-MF-10K	1.1/16"	1.1/16"
14J-12J-MF-10K	1.3/16"	1.1/16"
16J-12J-MF-10K	1.5/16"	1.1/16"
16J-16J-MF-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

KR 500



For **Hydraulic Adaptors** see pages **82-84**

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Straight Reducers



BSPP

0339	Male Thread	Female Thread
4G-2G-MF-B-10K	1/4"	1/8"
6G-2G-MF-B-10K	3/8"	1/8"
6G-4G-MF-B-10K	3/8"	1/4"
8G-2G-MF-B-10K	1/2"	1/8"
8G-4G-MF-B-10K	1/2"	1/4"
8G-6G-MF-B-10K	1/2"	3/8"
12G-2G-MF-B-10K	3/4"	1/8"
12G-4G-MF-B-10K	3/4"	1/4"
12G-6G-MF-B-10K	3/4"	3/8"
12G-8G-MF-B-10K	3/4"	1/2"
16G-2G-MF-B-10K	1"	1/8"
16G-4G-MF-B-10K	1"	1/4"
16G-6G-MF-B-10K	1"	3/8"
16G-8G-MF-B-10K	1"	1/2"
16G-12G-MF-B-10K	1"	3/4"
Tech Sheet 20887		



NPT

0339	Male Thread	Female Thread
4N-2N-MF-B-10K	1/4"	1/8"
6N-2N-MF-B-10K	3/8"	1/8"
6N-4N-MF-B-10K	3/8"	1/4"
8N-2N-MF-B-10K	1/2"	1/8"
8N-4N-MF-B-10K	1/2"	1/4"
8N-6N-MF-B-10K	1/2"	3/8"
12N-2N-MF-B-10K	3/4"	1/8"
12N-4N-MF-B-10K	3/4"	1/4"
12N-6N-MF-B-10K	3/4"	3/8"
12N-8N-MF-B-10K	3/4"	1/2"
16N-2N-MF-B-10K	1"	1/8"
16N-4N-MF-B-10K	1"	1/4"
16N-6N-MF-B-10K	1"	3/8"
16N-8N-MF-B-10K	1"	1/2"
16N-12N-MF-B-10K	1"	3/4"
Tech Sheet 20887		

Female x Female Straight Adaptors



Swivel, BSPP

0339	Thread	Thread
4G-4G-FF-10K	1/4"	1/4"
4G-6G-FF-10K	1/4"	3/8"
4G-8G-FF-10K	1/4"	1/2"
6G-6G-FF-10K	3/8"	3/8"
6G-8G-FF-10K	3/8"	1/2"
8G-8G-FF-10K	1/2"	1/2"
12G-12G-FF-10K	3/4"	3/4"
16G-16G-FF-10K	1"	1"
Tech Sheet 20887		



Fixed, NPT

0339	Thread	Thread
2N-2N-FF-10K	1/8"	1/8"
2N-4N-FF-10K	1/8"	1/4"
2N-6N-FF-10K	1/8"	3/8"
2N-8N-FF-10K	1/8"	1/2"
2N-12N-FF-10K	1/8"	3/4"
2N-16N-FF-10K	1/8"	1"
4N-4N-FF-10K	1/4"	1/4"
4N-6N-FF-10K	1/4"	3/8"
4N-8N-FF-10K	1/4"	1/2"
4N-12N-FF-10K	1/4"	3/4"
4N-16N-FF-10K	1/4"	1"
6N-6N-FF-10K	3/8"	3/8"
6N-8N-FF-10K	3/8"	1/2"
6N-12N-FF-10K	3/8"	3/4"
6N-16N-FF-10K	3/8"	1"
8N-8N-FF-10K	1/2"	1/2"
8N-12N-FF-10K	1/2"	3/4"
8N-16N-FF-10K	1/2"	1"
12N-12N-FF-10K	3/4"	3/4"
12N-16N-FF-10K	3/4"	1"
16N-16N-FF-10K	1"	1"
Tech Sheet 20887		



Swivel, JIC

0339	Thread	Thread
4J-4J-FF-10K	7/16"	7/16"
4J-6J-FF-10K	7/16"	9/16"
4J-8J-FF-10K	9/16"	3/4"
6J-6J-FF-10K	9/16"	9/16"
6J-8J-FF-10K	9/16"	3/4"
8J-8J-FF-10K	3/4"	3/4"
12J-12J-FF-10K	1.1/16"	1.1/16"
16J-16J-FF-10K	1.5/16"	1.5/16"
Tech Sheet 20887		

Male x Male Elbows



BSPP

0339	Thread
2G-E-MM-10K	1/8"
4G-E-MM-10K	1/4"
6G-E-MM-10K	3/8"
8G-E-MM-10K	1/2"
12G-E-MM-10K	3/4"
16G-E-MM-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-E-MM-10K	1/8"
4N-E-MM-10K	1/4"
6N-E-MM-10K	3/8"
8N-E-MM-10K	1/2"
12N-E-MM-10K	3/4"
16N-E-MM-10K	1"
Tech Sheet 20887	

Fluid-Air Components Ltd

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Male x Female Elbows



Swivel, BSPP

0339	Thread
2G-E-MF-10K	1/8"
4G-E-MF-10K	1/4"
6G-E-MF-10K	3/8"
8G-E-MF-10K	1/2"
12G-E-MF-10K	3/4"
16G-E-MF-10K	1"
Tech Sheet 20887	



Fixed, NPT

0339	Thread
2N-E-MF-10K	1/8"
4N-E-MF-10K	1/4"
6N-E-MF-10K	3/8"
8N-E-MF-10K	1/2"
12N-E-MF-10K	3/4"
16N-E-MF-10K	1"
Tech Sheet 20887	



Swivel, JIC

0339	Thread
4J-E-MF-10K	7/16"
6J-E-MF-10K	9/16"
8J-E-MF-10K	3/4"
10J-E-MF-10K	7/8"
12J-E-MF-10K	1.1/16"
16J-E-MF-10K	1.5/16"
Tech Sheet 20887	



NPT x JIC

0339	Male Thread	Female Thread
4N-4J-E-MF-10K	1/4"	7/16"
6N-6J-E-MF-10K	3/8"	9/16"
8N-8J-E-MF-10K	1/2"	3/4"
12N-12J-E-MF-10K	3/4"	1.1/16"
Tech Sheet 20887		

Female x Female Elbows



BSPP

0339	Thread
2G-E-FF-10K	1/8"
4G-E-FF-10K	1/4"
6G-E-FF-10K	3/8"
8G-E-FF-10K	1/2"
12G-E-FF-10K	3/4"
16G-E-FF-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-E-10K	1/8"
4N-E-10K	1/4"
6N-E-10K	3/8"
8N-E-10K	1/2"
12N-E-10K	3/4"
16N-E-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
2J-E-FF-10K	7/16"
4J-E-FF-10K	9/16"
6J-E-FF-10K	3/4"
8J-E-FF-10K	7/8"
12J-E-FF-10K	1.1/16"
16J-E-FF-10K	1.5/16"
Tech Sheet 20887	

Male x Male Tees



BSPP

0339	Thread
2G-T-MM-10K	1/8"
4G-T-MM-10K	1/4"
6G-T-MM-10K	3/8"
8G-T-MM-10K	1/2"
12G-T-MM-10K	3/4"
16G-T-MM-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-T-MM-10K	1/8"
4N-T-MM-10K	1/4"
6N-T-MM-10K	3/8"
8N-T-MM-10K	1/2"
12N-T-MM-10K	3/4"
16N-T-MM-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
4J-T-MM-10K	7/16"
5J-T-MM-10K	1/2"
6J-T-MM-10K	9/16"
8J-T-MM-10K	3/4"
10J-T-MM-10K	7/8"
12J-T-MM-10K	1.1/16"
14J-T-MM-10K	1.3/16"
16J-T-MM-10K	1.5/16"
Tech Sheet 20887	

10,000 PSI RATED, 316 STAINLESS STEEL ADAPTORS

stainless steel

PANAM

These fittings within the industry are known as 10K fittings which have a 10,000 psi working pressure rating.
All BSPP fittings are 60° coned for connection to hoses.

Maximum Working Pressure:
10,000 psi (690 bar)

Female x Female Tees



BSPP

0339	Thread
2G-T-FF-10K	1/8"
4G-T-FF-10K	1/4"
6G-T-FF-10K	3/8"
8G-T-FF-10K	1/2"
12G-T-FF-10K	3/4"
16G-T-FF-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-T-10K	1/8"
4N-T-10K	1/4"
6N-T-10K	3/8"
8N-T-10K	1/2"
12N-T-10K	3/4"
Tech Sheet 20887	



JIC

0339	Thread
2J-T-FF-10K	7/16"
4J-T-FF-10K	9/16"
6J-T-FF-10K	3/4"
8J-T-FF-10K	7/8"
12J-T-FF-10K	1.1/16"
16J-T-FF-10K	1.5/16"
Tech Sheet 20887	

Female Equal Cross



NPT

0339	Thread
2N-X-10K	1/8"
4N-X-10K	1/4"
6N-X-10K	3/8"
8N-X-10K	1/2"
12N-X-10K	3/4"
16N-X-10K	1"
Tech Sheet 20887	

Plugs



BSPP

0339	Thread
2G-P-10K	1/8"
4G-P-10K	1/4"
6G-P-10K	3/8"
8G-P-10K	1/2"
12G-P-10K	3/4"
16G-P-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-P-10K	1/8"
4N-P-10K	1/4"
6N-P-10K	3/8"
8N-P-10K	1/2"
12N-P-10K	3/4"
16N-P-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
4J-P-10K	7/16"
6J-P-10K	9/16"
8J-P-10K	3/4"
10J-P-10K	7/8"
12J-P-10K	1.1/16"
16J-P-10K	1.5/16"
Tech Sheet 20887	

Caps



BSPP

0339	Thread
2G-C-10K	1/8"
4G-C-10K	1/4"
6G-C-10K	3/8"
8G-C-10K	1/2"
12G-C-10K	3/4"
16G-C-10K	1"
Tech Sheet 20887	



NPT

0339	Thread
2N-C-10K	1/8"
4N-C-10K	1/4"
6N-C-10K	3/8"
8N-C-10K	1/2"
12N-C-10K	3/4"
16N-C-10K	1"
Tech Sheet 20887	



JIC

0339	Thread
4J-C-10K	7/16"
6J-C-10K	9/16"
8J-C-10K	3/4"
10J-C-10K	7/8"
12J-C-10K	1.1/16"
16J-C-10K	1.5/16"
Tech Sheet 20887	

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HYDRAULIC TUBING

stainless steel

316 Stainless Steel Tube

3 metre lengths next day.
6 metre lengths may take up to 3 working days to be delivered, dependant on weight and delivery address location. Additional carriage charges may apply.


For full details please contact our Business Development Team.
Minimum of 10 lengths is advised up to 8mm to prevent damage in transit.



Seamless ASTM A269, Metric, 6 Metre Lengths

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610-6M	6	1	428
765-6X1.5-6M	6	1.5	627
765-0810-6M	8	1	321
765-8X1.5-6M	8	1.5	472
765-1013-6M	10	1	257
765-10X1.5-6M	10	1.5	385
765-12X1.5-6M	12	1.5	321
765-1515-6M	15	1.5	257
765-16X1.5-6M	16	1.5	235
765-1602-6M	16	2	321
765-20X2-6M	20	2	257
765-25X2.5-6M	25	2.5	210
765-30X3-6M	30	3	257
Tech Sheet 831			

RSB



For **Tube Clamps Stainless Steel** see pages **186-189**

Seamless ASTM A269, Metric, 3 Metre Lengths, Random

0214	OD mm	Wall Thickness mm	Max Pressure Bar
765-0610	6	1	428
765-6X1.5	6	1.5	627
765-6X2	6	2	942
765-0813	8	1	321
765-8X1.5	8	1.5	472
765-8X2	8	2	706
765-1013	10	1	257
765-10X1.5	10	1.5	385
765-10X2	10	2	564
765-1213	12	1	210
765-12X1.5	12	1.5	321
765-12X2	12	2	420
765-1513	15	1	200
765-15X1.5	15	1.5	257
765-15X2	15	2	376
765-16X1.5	16	1.5	235
765-16X2	16	2	321
765-18X1.5	18	1.5	235
765-18X2	18	2	314
765-20X1.5	20	1.5	212
765-20X2	20	2	257
765-20X3	20	3	424
765-22X1.5	22	1.5	193
765-22X2	22	2	256
765-25X1.5	25	1.5	169
765-25X2	25	2	226
765-25X2.5	25	2.5	210
765-25X3	25	3	339
765-28X2	28	2	201
765-30X3	30	3	257
765-35X3	35	3	242
765-42X3	42	3	201
Tech Sheet 831			

Seamless ASTM A269, Imperial, 3 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372	1/8"	20	718
2020-1380	1/4"	20	360
2020-1406	3/8"	20	240
2020-1414	1/2"	20	180
2020-1422	3/4"	20	120
2020-1430	1"	20	90
Tech Sheet 831			

Seamless ASTM A269, Imperial, 6 Metre Lengths, Random

0214	OD	SWG	Max Pressure Bar
2020-1372-6M	1/8"	20	750
2020-1380-6M	1/4"	20	360
2020-1406-6M	3/8"	20	240
2020-1414-6M	1/2"	20	180
2020-1422-6M	3/4"	20	120
2020-1430-6M	1"	20	90
Tech Sheet 831			

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL HYDRAULIC VALVES

stainless steel

FT PRO

High Pressure Stainless Steel Ball Valves

Working Temperature:
-20°C to +120°C

- Nitrile seals



2 Way, BSPP

0098	Thread	Max Pressure Bar
HBVSS-14	1/4"	500
HBVSS-38	3/8"	500
HBVSS-12	1/2"	500
HBVSS-34	3/4"	315
HBVSS-1	1"	315
Tech Sheet 20888		

High Pressure Stainless Steel Block Style Ball Valves



2 Way, BSPP

0098	Thread	DN Size	Length mm	Max Pressure Bar
HBBVSS-14	1/4"	6	69	500
HBBVSS-38	3/8"	10	72	500
HBBVSS-12	1/2"	13	83	500
HBBVSS-34	3/4"	20	95	315
HBBVSS-1	1"	25	113	315
Tech Sheet 10224				

Due to the change of finishes used by our supplier, the product you receive may look slightly different to that illustrated.

Lockable High Pressure Stainless Steel Block Style Ball Valves

Lock not included



2 Way, BSPP

0098	Thread	DN Size	Length mm	Max Pressure Bar
HBBVSS-14-LK	1/4"	6	69	500
HBBVSS-38-LK	3/8"	10	72	500
HBBVSS-12-LK	1/2"	13	83	500
HBBVSS-34-LK	3/4"	20	95	315
HBBVSS-1-LK	1"	25	113	315
Tech Sheet 10224				

Locking Device



Stainless Steel

0177	To Suit
HPBVLD-1	DN6, DN8, DN10, DN13
HPBVLD-2	DN20, DN25
HPBVLD-3	DN32, DN38, DN50
Tech Sheet 10171	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel

FTPRO

Stainless Steel Lockable Ball Valves

Suitable for domestic water services, heating and air-conditioning plants, and compressed air systems.

- Full bore
- PTFE seals
- PTFE O-rings

Working Temperature:
-20°C to +180°C

Maximum Working Pressure:
63 bar: up to 3/4"
50 bar: 1" and 1.1/4"
40 bar: 1.1/2" upwards



2 Piece, Full Bore, Male x Female, BSPP

0901	Thread
789-14	1/4"
789-38	3/8"
789-12	1/2"
789-34	3/4"
789-1	1"
789-114	1.1/4"
789-112	1.1/2"
789-2	2"
Tech Sheet 6019	

316 Stainless Steel Ball Valves ISO Pad Mount

Features:

- Full bore
- PN16 flanged ends
- Direct mount ISO 5211
- Bureau Veritas certification
- Blowout proof stem
- Locking lever for 1" to 4"
- Suitable for applications such as chemical, petrochemical, hydraulic and compressed air

Working Temperature:
-20°C to +180°C

Maximum Working Pressure:
16 bar



Flanged PN16 Wafer Pattern Direct Mount Ball Valve

0901	Size
771 04	1/2"
771 05	3/4"
771 06	1"
771 07	1.1/4"
771 08	1.1/2"
771 09	2"
771 10	2.1/2"
771 11	3"
771 12	4"
771 13	5"
771 14	6"
Tech Sheet 6030	

316 Stainless Steel Mini Ball Valves

Features:

- Suitable for domestic water services, heating and air-conditioning plants and compressed air systems

Working Temperature:
-29°C to +160°C

Maximum Working Pressure: 63 bar



Hexagon Body, Female, BSPP

0902	Thread
HEXSMBV14	1/4"
HEXSMBV38	3/8"
HEXSMBV12	1/2"
HEXSMBV34	3/4"
HEXSMBV1	1"
Tech Sheet 6018	



Hexagon Body, Male x Female, BSPP

0902	Thread
HEXSMBV14M	1/4"
HEXSMBV38M	3/8"
HEXSMBV12M	1/2"
HEXSMBV34M	3/4"
HEXSMBV1M	1"
Tech Sheet 6018	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel FT PRO

Hygienic Stainless Steel Butterfly Valves



Weld End

0708	OD	OD mm	Length mm
BUTVWE-1	1"	12.7	68
BUTVWE-112	1.1/2"	19.05	76
BUTVWE-2	2"	25.4	80
BUTVWE-212	2.1/2"	38.1	80
BUTVWE-3	3"	50.8	82
BUTVWE-4	4"	63.5	88
Tech Sheet 68172			



RJT Male x Male

0708	Size	Thread	Length mm
BUTVRJT-1	1"	45.72 x 8T WHIT	68
BUTVRJT-112	1.1/2"	58.42 x 8T WHIT	76
BUTVRJT-2	2"	72.72 x 6T WHIT	80
BUTVRJT-212	2.5"	85.42 x 6T WHIT	80
BUTVRJT-3	3"	98.12 x 6T WHIT	82
BUTVRJT-4	4"	123.52 x 6T WHIT	100
Tech Sheet 68172			



Clamp End

0708	Size	Length mm
BUTVCE-1	1"	66
BUTVCE-112	1.1/2"	70
BUTVCE-2	2"	70
Tech Sheet 68172		

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel HAITIMA

316 Stainless Steel Ball Valves

Features:
- ATEX approved
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



2 Piece, Full Bore, BSPP

0099	Thread
2006S-14	1/4"
2006S-38	3/8"
2006S-12	1/2"
2006S-34	3/4"
2006S-1	1"
2006S-114	1.1/4"
2006S-112	1.1/2"
2006S-2	2"
Tech Sheet 1966	

2 Piece, Full Bore, NPT

0099	Thread
2006S-14N	1/4"
2006S-38N	3/8"
2006S-12N	1/2"
2006S-34N	3/4"
2006S-1N	1"
2006S-114N	1.1/4"
2006S-112N	1.1/2"
2006S-2N	2"
Tech Sheet 1966	

Features:
- ATEX approved
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 138 bar



2 Piece, Full Bore, BSPP

0099	Thread
2006-14	1/4"
2006-38	3/8"
2006-12	1/2"
2006-34	3/4"
2006-1	1"
Tech Sheet 6003	

Features:
- Full bore
- Investment casting
- Blowout proof stem
- Locking lever or wing handle

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



Wing Handle, BSPP

0099	Size
2006FW-14W	1/4"
2006FW-38W	3/8"
2006FW-12W	1/2"
Tech Sheet 6001	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel HAITIMA

316 Stainless Steel Ball Valves

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar

Features:
- Investment casting
- Blowout proof stem
- Locking lever



1 Piece, Reduced Bore, BSPP

0924	Thread
2017FW-14	1/4"
2017FW-38	3/8"
2017FW-12	1/2"
2017FW-34	3/4"
2017FW-1	1"
2017FW-114	1.1/4"
2017FW-112	1.1/2"
2017FW-2	2"
Tech Sheet 6000	



2 Piece, Full Bore, BSPP

0924	Thread
2006FW-14	1/4"
2006FW-38	3/8"
2006FW-12	1/2"
2006FW-34	3/4"
2006FW-1	1"
2006FW-114	1.1/4"
2006FW-112	1.1/2"
2006FW-2	2"
2006FW-212	2.1/2"
2006FW-3	3"
Tech Sheet 6001	



3 Piece, Full Bore, BSPP

0924	Thread
2013FW-14	1/4"
2013FW-38	3/8"
2013FW-12	1/2"
2013FW-34	3/4"
2013FW-1	1"
2013FW-114	1.1/4"
2013FW-112	1.1/2"
2013FW-2	2"
2013FW-212	2.1/2"
2013FW-3	3"
2013FW-4	4"
Tech Sheet 6005	



3 Piece, Full Bore, NPT

0924	Thread
2013FW-14N	1/4"
2013FW-38N	3/8"
2013FW-12N	1/2"
2013FW-34N	3/4"
2013FW-1N	1"
2013FW-114N	1.1/4"
2013FW-112N	1.1/2"
2013FW-2N	2"
2013FW-212N	2.1/2"
2013FW-3N	3"
2013FW-4N	4"
Tech Sheet 6005	



3 Piece, Full Bore, Butt Weld

0924	Size
2012FW-14	1/4"
2012FW-38	3/8"
2012FW-12	1/2"
2012FW-34	3/4"
2012FW-1	1"
2012FW-114	1.1/4"
2012FW-112	1.1/2"
2012FW-2	2"
2012FW-212	2.1/2"
2012FW-3	3"
2012FW-4	4"
Tech Sheet 6005	



3 Piece, Full Bore, Socket Weld

0924	Thread
2011FW-14	1/4"
2011FW-38	3/8"
2011FW-12	1/2"
2011FW-34	3/4"
2011FW-1	1"
2011FW-114	1.1/4"
2011FW-112	1.1/2"
2011FW-2	2"
2011FW-212	2.1/2"
2011FW-3	3"
2011FW-4	4"
Tech Sheet 6005	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel HAITIMA

316 Stainless Steel Ball Valves ISO Pad Mount

Features:
- Direct mount ISO 5211
- ATEX approved
- TA Luft
- ISO 15848-1:2006 fugitive emissions
- Anti-static device
- Investment casting
- Blowout proof stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



2 Piece, Full Bore, BSPP

0924	Thread
2006SD-14	1/4"
2006SD-38	3/8"
2006SD-12	1/2"
2006SD-34	3/4"
2006SD-1	1"
2006SD-114	1.1/4"
2006SD-112	1.1/2"
2006SD-2	2"
Tech Sheet 6004	

Features:
- Direct mount ISO 5211
- ATEX approved
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 6 bar

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 63 bar



3 Piece, Full Bore, BSPP

0924	Thread
2013ND-14	1/4"
2013ND-38	3/8"
2013ND-12	1/2"
2013ND-34	3/4"
2013ND-1	1"
2013ND-114	1.1/4"
2013ND-112	1.1/2"
2013ND-2	2"
2013ND-212	2.1/2"
2013ND-3	3"
2013ND-4	4"
Tech Sheet 6006	

3 Piece, Full Bore, NPT

0924	Thread
2013ND-12N	1/2"
2013ND-34N	3/4"
2013ND-1N	1"
2013ND-114N	1.1/4"
2013ND-112N	1.1/2"
2013ND-2N	2"
Tech Sheet 6006	

3 Piece, Full Bore, Butt Weld

0924	Thread
2012ND-12	1/2"
2012ND-34	3/4"
2012ND-1	1"
2012ND-114	1.1/4"
2012ND-112	1.1/2"
2012ND-2	2"
2012ND-212	2.1/2"
2012ND-3	3"
2012ND-4	4"
Tech Sheet 6006	

3 Piece, Full Bore, Socket Weld

0924	Thread
2011ND-12	1/2"
2011ND-34	3/4"
2011ND-1	1"
2011ND-114	1.1/4"
2011ND-112	1.1/2"
2011ND-2	2"
2011ND-212	2.1/2"
2011ND-3	3"
2011ND-4	4"
Tech Sheet 6006	

HAITIMA



You might also need a...
Haitima Pneumatic Actuator
...see page **1015**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL VALVES

stainless steel

HAITIMA

316 Stainless Steel Ball Valves

Features:
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 16 bar



PN16 Full Bore

0924	Flange Size	Bore mm
2019S 04	1/2"	15
2019S 05	3/4"	20
2019S 06	1"	25
2019S 07	1.1/4"	32
2019S 08	1.1/2"	40
2019S 09	2"	50
2019S 10	2.1/2"	65
2019S 11	3"	80
2019S 12	4"	100
2019S 14	6"	150
Tech Sheet 6011		

Features:
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 19.6 bar



ANSI150 Full Bore

0099	Flange Size	Bore mm
2020S 04	1/2"	15
2020S 05	3/4"	20
2020S 06	1"	25
2020S 08	1.1/2"	40
2020S 09	2"	50
2020S 10	2.1/2"	65
2020S 11	3"	80
2020S 12	4"	100
2020S 14	6"	150
Tech Sheet 6013		

3 Piece Full Bore Fire Safe Direct Mount Ball Valve

Features:
- Full bore
- Direct mount ISO 5211
- ATEX approved
- DNV certifie
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature: -20°C to +220°C

Maximum Working Pressure:
138 bar: 1/2" to 1"
103 bar: 1.1/4" to 2"
63 bar: 2.1/2" upwards



BSPP

0924	Thread
2013KMD-12	1/2"
2013KMD-34	3/4"
2013KMD-1	1"
2013KMD-114	1.1/4"
2013KMD-112	1.1/2"
2013KMD-2	2"
2013KMD-212	2.1/2"
2013KMD-3	3"
Tech Sheet 6007	

NPT

0924	Thread
2013KMD-12N	1/2"
2013KMD-34N	3/4"
2013KMD-1N	1"
2013KMD-114N	1.1/4"
2013KMD-112N	1.1/2"
2013KMD-2N	2"
2013KMD-3N	3"
Tech Sheet 6007	

Butt Weld

0924	Size
2012KMD-12	1/2"
2012KMD-34	3/4"
2012KMD-1	1"
2012KMD-112	1.1/2"
2012KMD-2	2"
Tech Sheet 6007	

Socket Weld

0924	Size
2011KMD-12	1/2"
2011KMD-34	3/4"
2011KMD-1	1"
2011KMD-114	1.1/4"
2011KMD-112	1.1/2"
2011KMD-2	2"
Tech Sheet 6007	

Fluid-Air Components Ltd


STAINLESS STEEL VALVES

stainless steel HAITIMA

Fire Safe Direct Mount Ball Valves

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- DNV certifie
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +200°C



2 Piece, Flanged PN16, Full Bore

0924	Flange Size	Flange	Max Pressure bar
2019D 04	1/2"	PN16/40	40
2019D 05	3/4"	PN16/40	40
2019D 06	1"	PN16/40	40
2019D 07	1.1/4"	PN16/40	40
2019D 08	1.1/2"	PN16/40	40
2019D 09	2"	PN16/40	40
2019D 10	2.1/2"	PN16	16
2019D4 10	2.1/2"	PN40	40
2019D 11	3"	PN16	16
2019D4 11	3"	PN40	40
2019D 12	4"	PN16	16
2019D4 12	4"	PN40	40
2019D 13	5"	PN16	16
2019D 14	6"	PN16	16
2019D 16	8"	PN16	16
Tech Sheet 10336			

316 Stainless Steel Ball Valve Accessories

Features:
- ISO mounting pad to ISO 5211

Working Temperature:
-20°C to +200°C




Stem Extension

0924	Valve ISO	Stem Size
TSM 1	F04	9
TSM 2	F05	11
TSM 3	F07	14
TSM 4	F10	17
TSM 5	F12	22
Tech Sheet 6016		

Features:
- Direct mount ISO 5211
- ATEX approved
- Fire Safe API 607 4th edition
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- NACE MR0175

Working Temperature:
-20°C to +230°C

Maximum Working Pressure:
19.6 bar



2 Piece, Flanged ANSI150, Full Bore


0924	Flange Size
2020D 04	1/2"
2020D 05	3/4"
2020D 06	1"
2020D 07	1.1/4"
2020D 08	1.1/2"
2020D 09	2"
2020D 10	2.1/2"
2020D 11	3"
2020D 12	4"
2020D 14	6"
Tech Sheet 10331	

Other Flanged End connections are available on request

316 Stainless Steel Direct Mount Ball Valves

Features:
- Direct mount ISO 5211
- Investment casting
- Blowout proof stem
- Locking lever

Working Temperature:
-20°C to +200°C



3 Way, L Port, Flanged PN16, Full Bore

0924	Flange Size	Max Pressure bar
2059DL16 04	1/2"	16
2059DL16 06	1"	16
2059DL16 08	1.1/2"	16
2059DL16 09	2"	16
2059DL16 10	2.1/2"	16
2059DL16 11	3"	16
2059DL16 12	4"	16
2059DL16 14	6"	16
Tech Sheet 6015		

3 Way, L Port, Flanged ANSI150, Full Bore

0924	Flange Size	Max Pressure bar
2059DL150 04	1/2"	19.6
2059DL150 06	1"	19.6
2059DL150 08	1.1/2"	19.6
2059DL150 09	2"	19.6
2059DL150 11	3"	19.6
2059DL150 12	4"	19.6
2059DL150 14	6"	19.6
Tech Sheet 6015		

3 Way, T Port, Flanged PN16, Full Bore

0924	Flange Size	Max Pressure bar
2059DT16 04	1/2"	16
2059DT16 06	1"	16
2059DT16 08	1.1/2"	16
2059DT16 09	2"	16
2059DT16 10	2.1/2"	16
2059DT16 11	3"	16
2059DT16 12	4"	16
2059DT16 14	6"	16
Tech Sheet 6015		

3 Way, T Port, Flanged ANSI150, Full Bore

0924	Flange Size	Max Pressure bar
2059DT150 04	1/2"	19.6
2059DT150 06	1"	19.6
2059DT150 08	1.1/2"	19.6
2059DT150 09	2"	19.6
2059DT150 11	3"	19.6
2059DT150 12	4"	19.6
2059DT150 14	6"	19.6
Tech Sheet 6015		

STAINLESS STEEL VALVES

stainless steel GENEBRE

316 Stainless Steel Ball Valves ISO Pad Mount

Features:
- Reduced bore
- Direct mount ISO 5211
- Anti-static device
- Blowout proof stem
- Locking lever

Working Temperature: -25°C to +180°C

Maximum Working Pressure: 63 bar



3 Way, L Port, BSPP

0902	Thread
2040-14	1/4"
2040-38	3/8"
2040-12	1/2"
2040-34	3/4"
2040-1	1"
2040-114	1.1/4"
2040-112	1.1/2"
2040-2	2"
2040-212	2.1/2"
Tech Sheet 6025	



3 Way, T Port, BSPP

0902	Thread
2041-14	1/4"
2041-38	3/8"
2041-12	1/2"
2041-34	3/4"
2041-1	1"
2041-114	1.1/4"
2041-112	1.1/2"
2041-2	2"
2041-212	2.1/2"
Tech Sheet 6025	

10

GATE VALVES

stainless steel HAITIMA

Stainless Steel Flanged Gate Valves

Features:
- Investment casting
- Rising stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: PN16: 16 bar



PN16

0982	Flange Size
2054SL16 04	1/2"
2054SL16 06	1"
2054SL16 07	1.1/4"
2054SL16 08	1.1/2"
2054SL16 09	2"
2054SL16 11	3"
2054SL16 12	4"
2054SL16 14	6"
Tech Sheet 1876	

Features:
- Investment casting
- Rising stem

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 196 bar



ANSI150

0982	Flange Size
2054SL150 04	1/2"
2054SL150 06	1"
2054SL150 08	1.1/2"
2054SL150 09	2"
2054SL150 10	2.1/2"
2054SL150 11	3"
2054SL150 12	4"
2054SL150 14	6"
Tech Sheet 1873	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

STAINLESS STEEL VALVES

stainless steel

HAITIMA


Hygenic 316 Stainless Steel Ball Valves ISO Pad Mount

Features:

- Cavity filled seats
- Direct mount ISO 5211
- ATEX approved
- Anti-static device
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Piece, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2012CD-12	1/2"	15	12.70	90.70	F03/F04
2012CD-34	3/4"	20	19.10	103	F03/F04
2012CD-1	1"	25	25.40	115	F04/F05
2012CD-112	1.1/2"	40	38.10	139	F05/F07
2012CD-2	2"	50	50.80	158	F05/F07
2012CD-212	2.1/2"	65	63.50	197	F07/F10
2012CD-3	3"	80	76.20	228	F07/F10
2012CD-4	4"	100	101.60	241.80	F10/F12
Tech Sheet 6009					

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Piece, Clamp End

0924	Size	DN	Length	ISO 5211
2013CD-12	1/2"	15	90.70	F03/F04
2013CD-34	3/4"	20	103	F03/F04
2013CD-1	1"	25	115	F04/F05
2013CD-112	1.1/2"	40	139	F05/F07
2013CD-2	2"	50	158	F05/F07
2013CD-212	2.1/2"	65	197	F07/F10
2013CD-3	3"	80	228	F07/F10
2013CD-4	4"	100	241.80	F10/F12
Tech Sheet 6009				

Features:

- Direct mount ISO 5211
- Investment casting
- Blowout proof stem
- Locking lever
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar



3 Way, L Port, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2057CBL-12	1/2"	15	12.70	118	F03/F04
2057CBL-1	1"	25	25.40	152.40	F04/F05
2057CBL-112	1.1/2"	40	38.10	175	F05/F07
2057CBL-2	2"	50	50.80	190	F05/F07
2057CBL-212	2.1/2"	65	63.50	228	F07/F10
2057CBL-3	3"	80	76.20	260	F07/F10
2057CBL-4	4"	100	102	289	F10/F12
Tech Sheet 6009					

3 Way, T Port, Butt Weld

0924	Size	DN	OD mm	Length	ISO 5211
2057CBT-12	1/2"	15	12.70	118	F03/F04
2057CBT-1	1"	25	25.40	152.40	F04/F05
2057CBT-112	1.1/2"	40	38.10	175	F05/F07
2057CBT-2	2"	50	50.80	190	F05/F07
2057CBT-212	2.1/2"	65	63.50	228	F07/F10
2057CBT-3	3"	80	76.20	260	F07/F10
2057CBT-4	4"	100	102	289	F10/F12
Tech Sheet 6009					

Hygenic 316 Stainless Steel Ball Valves

FT PRO

Working Temperature:
-20°C to +160°C

Maximum Working Pressure:
8 bar

Features:

- Cavity filled seats
- Locking lever



3 Piece, Weld End

0708	OD	OD mm	Length mm
HSBVWE-12	1/2"	12.7	89
HSBVWE-34	3/4"	19.05	101
HSBVWE-1	1"	25.4	114
HSBVWE-112	1.1/2"	38.1	140
HSBVWE-2	2"	50.8	156
HSBVWE-212	2.1/2"	63.5	197
HSBVWE-3	3"	76.2	229
HSBVWE-4	4"	101.6	242.7
Tech Sheet 68171			

FT PRO

Working Temperature:
-20°C to +160°C

Maximum Working Pressure:
8 bar

Features:

- Cavity filled seats
- Locking lever



3 Piece, Clamp End

0708	Clamp Size	Length mm
HSBVCE-12	1/2"	89
HSBVCE-34	3/4"	101
HSBVCE-1	1"	114
HSBVCE-112	1.1/2"	140
HSBVCE-2	2"	156
HSBVCE-212	2.1/2"	197
HSBVCE-3	3"	229
HSBVCE-4	4"	242.7
Tech Sheet 68171		

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

CHECK VALVES

stainless steel

HAITIMA


Stainless Steel Flanged Check Valves

Features:

- Installation in a horizontal position only
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
19.6 bar: ANSI150
16 bar: PN16



ANSI150

0982	Flange Size
2024SL150 06	1"
2024SL150 08	1.1/2"
2024SL150 09	2"
2024SL150 11	3"
2024SL150 12	4"
2024SL150 14	6"
Tech Sheet 1875	

Other sizes on request.

PN16

0982	Flange Size
2024SL16 06	1"
2024SL16 08	1.1/2"
2024SL16 09	2"
2024SL16 10	2.1/2"
2024SL16 11	3"
2024SL16 12	4"
2024SL16 14	6"
Tech Sheet 1875	

Cannot see the product you're looking for? Contact us. More often than not, we can acquire that product.

HAITIMA stainless steel

You may also need...
Stainless Steel 150lb Fittings
...see pages **1181-1185**



Fluid-Air Components Ltd

CHECK VALVES

stainless steel GENEBRE

Cromax Spring Check Valves

Body: 304SS or 316SS
Seal: Viton
Other sizes on request.

Working Temperature: -20°C - +150°C

Maximum Working Pressure: 16 bar



304 Stainless Steel, BSPP

0902	Thread
2440-14	1/4"
2440-38	3/8"
2440-12	1/2"
2440-34	3/4"
2440-1	1"
2440-114	1.1/4"
2440-112	1.1/2"
2440-2	2"
Tech Sheet 1871	

316 Stainless Steel, BSPP

0902	Thread
2445-14	1/4"
2445-38	3/8"
2445-12	1/2"
2445-34	3/4"
2445-1	1"
2445-114	1.1/4"
2445-112	1.1/2"
2445-2	2"
Tech Sheet 1871	

Check Valves Basket

Features:
- BSPP threads
- Mesh size 1mm up to 2". 1.9mm for 2.1/2" upwards

Working Temperature: -20°C to +150°C

Maximum Working Pressure: 16 bar



Strainer Basket for CROMAX Spring Check Valve

0902	Size	DN
2447-12	1/2"	15
2447-34	3/4"	20
2447-1	1"	25
2447-114	1.1/4"	32
2447-112	1.1/2"	40
2447-2	2"	50
2447-212	2.1/2"	65
2447-3	3"	80
2447-4	4"	100
Tech Sheet 6094		

Wafer Check Valves

Seal: Viton
- Can be mounted between PN10/16 and ANSI150 flange

Working Temperature: -20°C to +180°C

Maximum Working Pressure: 16 bar



Wafer Pattern, Swing

0902	Flange Size
2406 08	1.1/2"
2406 09	2"
2406 10	2.1/2"
2406 11	3"
2406 12	4"
2406 13	5"
2406 14	6"
2406 16	8"
2406 18	10"
2406 20	12"
Tech Sheet 1878	

Features:
- Can be mounted between PN25 and ANSI150 flange
- Can be installed in any position

Working Temperature: -20°C to +180°C

Maximum Working Pressure: 25 bar



Dual Plate Spring Assisted Swing

0902	Flange Size
2402 09	2"
2402 10	2.1/2"
2402 11	3"
2402 12	4"
2402 13	5"
2402 14	6"
2402 16	8"
Tech Sheet 6096	

CHECK VALVES

Stainless Steel Spring Check Valves

Features:
- Installation in a horizontal position only

Working Temperature:
-25°C to +180°C

Maximum Working Pressure:
200 psi (13.8 bar)



Swing, BSPP

0900	Thread
2030-12	1/2"
2030-34	3/4"
2030-1	1"
2030-114	1.1/4"
2030-112	1.1/2"
2030-2	2"
2030-212	2.1/2"
2030-3	3"
Tech Sheet 6098	

Features:
- Can be installed in any position

Working Temperature:
-25°C to +180°C



Spring Assisted, BSPP

0900	Thread	Max Pressure bar
2413-14	1/4"	83
2413-38	3/8"	83
2413-12	1/2"	83
2413-34	3/4"	83
2413-1	1"	83
2413-114	1.1/4"	69
2413-112	1.1/2"	69
2413-2	2"	63
Tech Sheet 6093		

Features:
- Can be mounted between PN16/25/40 and ANSI150 flanges
- Can be installed in any position
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +180°C

Maximum Working Pressure: 40 bar




Spring Assisted Wafer Pattern

0933	Flange Size
2026 04	1/2"
2026 05	3/4"
2026 06	1"
2026 07	1.1/4"
2026 08	1.1/2"
2026 09	2"
2026 10	2.1/2"
2026 11	3"
2026 12	4"
Tech Sheet 6095	

Features:
- Can be installed in any position
- Suitable for saturated steam up to 10 bar

Working Temperature:
-20°C to +180°C

Maximum Working Pressure: 40 bar



3 Piece, Spring Assisted, BSPP

0933	Thread
2026C-12	1/2"
2026C-34	3/4"
2026C-1	1"
2026C-114	1.1/4"
2026C-112	1.1/2"
2026C-2	2"
2026C-212	2.1/2"
2026C-3	3"
2026C-4	4"
Tech Sheet 6097	

High Pressure Check Valves

Maximum Working Pressure: 350 bar



BSPP, 0.5 bar Cracking Pressure

0098	Thread
HCVSS-3/8	3/8"
HCVSS-1/2	1/2"
HCVSS-3/4	3/4"
HCVSS-1	1"
Tech Sheet 10043	

Fluid-Air Components Ltd

Y STRAINERS

Strainers for YS Series



Stainless Steel AISI 304

0090	To Suit
192-12-STRAINER	YS-12
192-34-STRAINER	YS-34
192-1-STRAINER	YS-1
192-114-STRAINER	YS-114
192-112-STRAINER	YS-112
192-2-STRAINER	YS-2
192-212-STRAINER	YS-212
192-3-STRAINER	YS-3
192-4-STRAINER	YS-4
Tech Sheet 2032	

Stainless Steel Y Strainers

Features:
- 0.4mm perforations
- Suitable for saturated steam up to 10 bar

Working Temperature:
-25°C to +180°C

Maximum Working Pressure:
800 psi (55.16 bar)

stainless steel



BSP

0900	Size
2049-38	3/8"
2049-12	1/2"
2049-34	3/4"
2049-1	1"
2049-114	1.1/4"
2049-112	1.1/2"
2049-2	2"
Tech Sheet 2049	

NPT

0900	Size
2049-12N	1/2"
2049-34N	3/4"
2049-1N	1"
2049-114N	1.1/4"
2049-112N	1.1/2"
2049-2N	2"
Tech Sheet 2049	

Y STRAINERS

stainless steel

HAITIMA

Flanged Y Strainers

Features:
- 0.4mm perforations

Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
16 bar: PN16
19.6 bar: ANSI150



PN16

0982	Size
2049SL16 04	1/2"
2049SL16 05	3/4"
2049SL16 06	1"
2049SL16 07	1.1/4"
2049SL16 08	1.1/2"
2049SL16 09	2"
2049SL16 10	2.1/2"
2049SL16 11	3"
2049SL16 12	4"
2049SL16 13	5"
2049SL16 14	6"
Tech Sheet 1877	

ANSI150

0982	Size
2049SL150 04	1/2"
2049SL150 05	3/4"
2049SL150 06	1"
2049SL150 08	1.1/2"
2049SL150 09	2"
2049SL150 10	2.1/2"
2049SL150 11	3"
2049SL150 12	4"
2049SL150 13	5"
2049SL150 14	6"
Tech Sheet 1874	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel

PANAM

3,000 psi Rated Mini Needle Valve

Working Temperature:
-50°C to +121°C

Maximum Working Pressure:
205 bar

Seal: Viton



NPT

0292	Thread	Description
PMV-H-S-4-FF-V	1/4"	Female x Female
PMV-H-S-4-MF-V	1/4"	Male x Female
Tech Sheet 10506		

6,000 psi Rated Imperial Needle Valves

The 'IB' series of needle valves are specially designed and manufactured for use in corrosive and hazardous environments.

These valves are for use in process control, instrumentation and flow control applications.

Feature Benefits

One piece body construction for strength and safety.

Non rotating Vee tip design, which forms a bearing joint with the stem eliminating any rotation between the plug and seat on closure ensuring long life.

Testing: All valves are 100% factory tested and complete traceability is available upon request.

Material: Body, panel nut, washer and gland nut A479-316

Stem: A479-316 / 17-4PH

Packing: PTFE

Grub Screw: Steel plated

Handle: Stainless steel

Vee Tip: A 564-630

Working Temperature:
-29°C to +121°C

Maximum Working Pressure:
413 bar (6,000 psi)

Female x Female, NPTF



0292	Thread
PNV-IB-S-2-FF	1/8"
PNV-IB-S-4-FF	1/4"
PNV-IB-S-6-FF	3/8"
PNV-IB-S-8-FF	1/2"
PNV-IB-S-12-FF	3/4"
PNV-IB-S-16-FF	1"
Tech Sheet 2156	

Female x Female, BSPP

0099	Thread
2018-6938	1/4"
2018-6946	3/8"
2018-6953	1/2"
Tech Sheet 10036	

Male x Female, NPTF



0292	Thread
PNV-IB-S-2-MF	1/8"
PNV-IB-S-4-MF	1/4"
PNV-IB-S-6-MF	3/8"
PNV-IB-S-8-MF	1/2"
PNV-IB-S-12-MF	3/4"
PNV-IB-S-16-MF	1"
Tech Sheet 2156	

OD Compression



0292	OD
NV6000-18	1/8"
NV6000-14	1/4"
NV6000-38	3/8"
NV6000-12	1/2"
NV6000-34	3/4"
NV6000-1	1"
Tech Sheet 2156	

10,000 psi Rated Imperial Needle Valves

The 'HP' series of needle valves are specially designed and manufactured for use in corrosive and hazardous environments.

These valves are for use in process control, instrumentation and flow control applications.

Feature Benefits

One piece body construction for strength and safety.

Non rotating Vee tip design, which forms a bearing joint with the stem eliminating any rotation between the plug and seat on closure ensuring long life.

Testing: Each valve is hydrostatically tested in accordance with MSS-SP-99. This procedure includes testing of the body cavity. A Hydrostatic test is performed with pure water or other liquids of similar or lower viscosity at 1.5 times and seat leakage test at 1.1 times of the maximum working pressure.

Each valve is also tested with nitrogen gas at 1000psi for seat, seal and shell leakage. Other tests like vibration, temperature and helium are available upon request.

Material: Body, stem, packing washer, lock nut and gland retainer A479-316/A-105

Gland Packing: Glass Filled PTFE

Packing: PTFE

Handle: Stainless steel

Dust Cap: Plastic

Vee Tip: A 564-630

Working Temperature:
-50°C to +93°C

Maximum Working Pressure:
700 bar (10,000 psi)

Female x Female, NPTF



0292	Thread
PNV-HP-S-2-FF	1/8"
PNV-HP-S-4-FF	1/4"
PNV-HP-S-6-FF	3/8"
PNV-HP-S-8-FF	1/2"
PNV-HP-S-16-FF	1"
Tech Sheet 2157	

Male x Female, NPTF



0292	Thread
PNV-HP-S-2-MF	1/8"
PNV-HP-S-4-MF	1/4"
PNV-HP-S-6-MF	3/8"
PNV-HP-S-8-MF	1/2"
PNV-HP-S-12-MF	3/4"
PNV-HP-S-16-MF	1"
Tech Sheet 2157	

Fluid-Air Components Ltd

STAINLESS STEEL VALVES

stainless steel

PANAM


Manifold Valves

Working Temperature: -29°C to +121°C

Maximum Working Pressure: 414 bar

2 Valve manifold pipe to pipe design for separate mounting, connection system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Pipe to Pipe, NPT

0380	Thread
P2VM-SS-8-R	1/2"
Tech Sheet 10216	

3 Valve manifold pipe to pipe design for connecting system impulse lines and transmitters. This valve consists of 1/2" NPT female connectors on 54mm centres and 1 equalizer valve and 2 block valves.

Other mounting options are available on request.




3 Valve Manifold, Pipe to Pipe, NPT

0380	Thread
P3VM-SS-8-R	1/2"
Tech Sheet 10216	

2 Valve manifold remote mount flange to flange desig for separate mounting, connecting system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Remote Mount, NPT

0380	Thread
P2VM-SS-8-RM	1/2"
Tech Sheet 10216	

STAINLESS STEEL COMPRESSION BALL VALVES

stainless steel

PANAM

Stainless Steel 6,000 psi, Check Valves

Working Temperature: -26°C to +190°C

Cracking Pressure: 0.35 psi

Maximum Working Pressure: 414 bar

Seal: Viton



Female, NPT

0292	Thread
PCV-02-SS-FF	1/8"
PCV-04-SS-FF	1/4"
PCV-06-SS-FF	3/8"
PCV-08-SS-FF	1/2"
PCV-12-SS-FF	3/4"
PCV-16-SS-FF	1"
Tech Sheet 10507	

6,000 psi Rated Ball Valves

Working Temperature: 0°C to +40°C

Maximum Working Pressure: 400 bar



Female, NPT

0292	Thread
PBV-2-S-02-FF	1/8"
PBV-2-S-04-FF	1/4"
PBV-2-S-06-FF	3/8"
PBV-2-S-08-FF	1/2"
PBV-2-S-12-FF	3/4"
PBV-2-S-16-FF	1"
Tech Sheet 10508	

Ball Valves

Working Pressure: 6000 psi



Compression, 2 Way

0292	OD
BV6000-18	1/8"
BV6000-12	1/2"
Tech Sheet 20847	

FAC Fluid-Air Components Ltd

ISO A INTERCHANGE COUPLINGS & PLUGS

stainless steel

FTPRO

ISO A Interchange

Working Temperature:
-25°C to +120°C Nitrile
-25°C to +175°C Viton



316 Stainless Steel ISO A Coupling with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HFSSFC7314-V	1/4"	250
HFSSFC7338-V	3/8"	200
HFSSFC7312-V	1/2"	200
HFSSFC7334-V	3/4"	160
HFSSFC7310-V	1"	125
Tech Sheet 10002		



316 Stainless Steel ISO A Plug with Viton Seals, BSPP

8111	Thread	Max Pressure Bar
HFSSFP7314-V	1/4"	250
HFSSFP7338-V	3/8"	200
HFSSFP7312-V	1/2"	200
HFSSFP7334-V	3/4"	160
HFSSFP7310-V	1"	125
Tech Sheet 10002		

316 Stainless Steel ISO A Coupling with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKSA04SS-NPT	1/4"	250
HKSA06SS-NPT	3/8"	200
HKSA08SS-NPT	1/2"	200
HKSA12SS-NPT	3/4"	160
HKSA16SS-NPT	1"	125
Tech Sheet 10002		

316 Stainless Steel ISO A Plug with Nitrile Seals, NPT

8111	Thread	Max Pressure Bar
HKPA04SS-NPT	1/4"	250
HKPA06SS-NPT	3/8"	200
HKPA08SS-NPT	1/2"	200
HKPA12SS-NPT	3/4"	160
HKPA16SS-NPT	1"	125
Tech Sheet 10002		

ISO B INTERCHANGE COUPLINGS & PLUGS

stainless steel

FTPRO

ISO B Interchange

Other seals available on request

Working Temperature:
-25°C to +120°C Nitrile
-25°C to +175°C Viton



316 Stainless Steel ISO B Coupling with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKS02SS	1/8"	250
HKS04SS	1/4"	250
HKS06SS	3/8"	200
HKS08SS	1/2"	200
HKS12SS	3/4"	160
HKS16SS	1"	125
Tech Sheet 10003		



316 Stainless Steel ISO B Plug with Nitrile Seal, BSPP

0249	Thread	Max Pressure Bar
HKP02SS	1/8"	250
HKP04SS	1/4"	250
HKP06SS	3/8"	200
HKP08SS	1/2"	200
HKP12SS	3/4"	160
HKP16SS	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Coupling with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKS04SS-NPT	1/4"	250
HKS06SS-NPT	3/8"	200
HKS08SS-NPT	1/2"	200
HKS12SS-NPT	3/4"	160
HKS16SS-NPT	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Plug with Nitrile Seal, NPT

8111	Thread	Max Pressure Bar
HKP04SS-NPT	1/4"	250
HKP06SS-NPT	3/8"	200
HKP08SS-NPT	1/2"	200
HKP12SS-NPT	3/4"	160
HKP16SS-NPT	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Coupling with Viton Seal, BSPP

0249	Thread	Max Pressure Bar
HKS02SS-V	1/8"	250
HKS04SS-V	1/4"	250
HKS06SS-V	3/8"	200
HKS08SS-V	1/2"	200
HKS12SS-V	3/4"	160
HKS16SS-V	1"	125
Tech Sheet 10003		

316 Stainless Steel ISO B Plug with Viton Seal, BSPP

0249	Thread	Max Pressure Bar
HKP02SS-V	1/8"	250
HKP04SS-V	1/4"	250
HKP06SS-V	3/8"	200
HKP08SS-V	1/2"	200
HKP12SS-V	3/4"	160
HKP16SS-V	1"	125
Tech Sheet 10003		

Fluid-Air Components Ltd
ef nkl i r o i r p c c c a c c

HYDRAULIC QUICK RELEASE COUPLINGS

stainless steel

PAVX Series, ISO A Stainless Steel Couplings

Working Temperature: -25°C to +200°C Viton

Maximum Working Pressure: 450 bar

Standard: ISO 7241-1 A
Occlusion: Poppet
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PAVX.0606.002	1/4"	6.3	450
PAVX.1010.002	3/8"	10	300
PAVX.1313.002	1/2"	12.5	300
PAVX.2019.002	3/4"	20	250
PAVX.2525.002	1"	25	200
PAVX.3031.002	1.1/4"	31.5	100
PAVX.3939.002	1.1/2"	40	80
PAVX.5051.002	2"	50	60
Tech Sheet 20474			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PAVX.0606.003	1/4"	6.3	450
PAVX.1010.003	3/8"	10	300
PAVX.1313.003	1/2"	12.5	300
PAVX.2019.003	3/4"	19	250
PAVX.2525.003	1"	25	200
PAVX.3031.003	1.1/4"	31.5	100
PAVX.3939.003	1.1/2"	40	80
PAVX.5051.003	2"	50	60
Tech Sheet 20474			



PBVX Series, ISO B Stainless Steel Couplings

Working Temperature: -25°C to +200°C

Maximum Working Pressure: 400 bar

Standard: ISO 7241-1 B
Occlusion: Poppet
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVX.0404.002	1/8"	5	400
PBVX.0606.002	1/4"	6.3	350
PBVX.1010.002	3/8"	10	300
PBVX.1313.002	1/2"	12.5	300
PBVX.2019.002	3/4"	20	220
PBVX.2525.002	1"	25	200
PBVX.3931.002	1.1/4"	40	80
PBVX.3939.002	1.1/2"	40	80
PBVX.5051.002	2"	50	60
Tech Sheet 20478			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PBVX.0404.003	1/8"	5	400
PBVX.0606.003	1/4"	6.3	350
PBVX.1010.003	3/8"	10	300
PBVX.1313.003	1/2"	12.5	300
PBVX.2019.003	3/4"	20	220
PBVX.2525.003	1"	25	200
PBVX.3931.003	1.1/4"	40	80
PBVX.3939.003	1.1/2"	40	80
PBVX.5051.003	2"	50	60
Tech Sheet 20478			



HYDRAULIC QUICK RELEASE COUPLINGS

stainless steel

PLTX Series, ISO 16028 Flat Face Couplings, Stainless Steel

Standard: ISO 16028
Occlusion: Flat face
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT, SAE
Standard Seals: Viton
Optional Seals: EPDM, FFKM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 350 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLTX.0606.112	1/4"	6.3	400
PLTX.1310.112	3/8"	10	250
PLTX.1313.112	1/2"	10	250
PLTX.2013.112	1/2"	12.5	250
PLTX.2019.112	3/4"	12.5	250
PLTX.2519.112	3/4"	19	250
PLTX.2525.112	1"	19	250
PLTX.3031.112	1.1/4"	25	250
PLTX.3939.112	1.1/2"	40	150
PLTX.5051.112	2"	50	100
Tech Sheet 20483			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLTX.0606.113	1/4"	6.3	400
PLTX.1310.113	3/8"	10	250
PLTX.1313.113	1/2"	10	250
PLTX.2013.113	1/2"	12.5	250
PLTX.2019.113	3/4"	12.5	250
PLTX.2519.113	3/4"	19	250
PLTX.2525.113	1"	19	250
PLTX.3031.113	1.1/4"	25	250
PLTX.3939.113	1.1/2"	40	150
PLTX.5051.113	2"	50	100
Tech Sheet 20483			

PLSX Series, Flat Face, Stainless Steel

Interchange: Snap-Tite 71
Occlusion: Flat face
Locking: Radial balls
Material: Stainless steel AISI 316

Available Threads: BSP, NPT
Standard Seals: Viton
Optional Seals: FFKM, EPDM
Connection Under Pressure: Not allowed

Working Temperature: -25°C to +100°C
Maximum Working Pressure: 350 bar



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLSX.0606.112	1/4"	6.3	350
PLSX.1010.112	3/8"	10	350
PLSX.1013.112	1/2"	10	350
PLSX.1313.112	1/2"	12.5	350
PLSX.2019.112	3/4"	19	350
PLSX.2525.112	1"	25	350
PLSX.2531.112	1.1/4"	25	350
Tech Sheet 20485			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLSX.0606.113	1/4"	6.3	350
PLSX.1010.113	3/8"	10	350
PLSX.1013.113	1/2"	10	350
PLSX.1313.113	1/2"	12.5	350
PLSX.2019.113	3/4"	19	350
PLSX.2525.113	1"	25	350
PLSX.2531.113	1.1/4"	25	350
Tech Sheet 20485			

PLS1 Series, Flat Face

Material: Steel
Finishing: Zn-Fe (Cr III)
Available Threads: BSP, NPT, SAE

Standard Seals: Nitrile
Optional Seals: Viton, EPDM
Connection Under Pressure: Not allowed



Coupling, BSPP

0457	Thread	ISO	Max Pressure Bar
PLS1.0606.112	1/4"	6.3	350
PLS1.1010.112	3/8"	10	350
PLS1.1013.112	1/2"	10	350
PLS1.1313.112	1/2"	12.5	350
PLS1.2019.112	3/4"	19	350
PLS1.2525.112	1"	25	350
PLS1.2531.112	1.1/4"	25	350
Tech Sheet 20484			



Plug, BSPP

0457	Thread	ISO	Max Pressure Bar
PLS1.0606.113	1/4"	6.3	350
PLS1.1010.113	3/8"	10	350
PLS1.1013.113	1/2"	10	350
PLS1.1313.113	1/2"	12.5	350
PLS1.2019.113	3/4"	19	350
PLS1.2525.113	1"	25	350
PLS1.2531.113	1.1/4"	25	350
Tech Sheet 20484			

ISO 16028 Flat Face Protection Caps & Plugs

Plug for Coupling **Cap for Plug**



Plug for Coupling

0457	To Suit	Material
SPLT.06002	ISO 6.3	Plastic
SPLT.13002	ISO 10	Plastic
SPLT.20002	ISO 12.5	Plastic
SPLT.25002	ISO 19	Plastic
Tech Sheet 20483		

Cap for Plug

0457	To Suit	Material
SPLT.06003	ISO 6.3	Plastic
SPLT.13003	ISO 10	Plastic
SPLT.20003	ISO 12.5	Plastic
SPLT.25003	ISO 19	Plastic
SPLT.30003	ISO 25	Plastic
Tech Sheet 20483		

ISO 16028 Automatic Caps



Cap for Coupling

0457	To Suit	Colour
SPLT.13302	ISO 10	Red
SPLT.13342	ISO 10	Black
SPPV.13302	ISO 12.5	Black
SPPV.13312	ISO 12.5	Black
SPPV.13322	ISO 12.5	Yellow
SPPV.13342	ISO 12.5	Red
Tech Sheet 20483		

Fluid-Air Components Ltd

CAM & GROOVE QUICK COUPLINGS

stainless steel FT PRO

316 Stainless Steel Couplings

See page 1472 for spare seals.



A

Female Threaded Plug, BSPP

0060	Thread
A12-SS	1/2"
A34-SS	3/4"
A1-SS	1"
A114-SS	1.1/4"
A112-SS	1.1/2"
A2-SS	2"
A212-SS	2.1/2"
A3-SS	3"
A4-SS	4"
A6-SS	6"
Tech Sheet 532	

Female Threaded Plug, NPT

0060	Thread
A12-SS-NPT	1/2"
A34-SS-NPT	3/4"
A1-SS-NPT	1"
A114-SS-NPT	1.1/4"
A112-SS-NPT	1.1/2"
A2-SS-NPT	2"
A212-SS-NPT	2.1/2"
A3-SS-NPT	3"
A4-SS-NPT	4"
Tech Sheet 532	



B

Male Threaded Lever Coupling, BSPT

0060	Thread
B12-SS	1/2"
B34-SS	3/4"
B1-SS	1"
B114-SS	1.1/4"
B112-SS	1.1/2"
B2-SS	2"
B212-SS	2.1/2"
B3-SS	3"
B4-SS	4"
Tech Sheet 532	

Male Threaded Lever Coupling, NPT

0060	Thread
B12-SS-NPT	1/2"
B34-SS-NPT	3/4"
B1-SS-NPT	1"
B114-SS-NPT	1.1/4"
B112-SS-NPT	1.1/2"
B2-SS-NPT	2"
B3-SS-NPT	3"
B4-SS-NPT	4"
Tech Sheet 532	



C

Hose Tail Lever Coupling

0060	Body
C12-SS	1/2"
C34-SS	3/4"
C1-SS	1"
C114-SS	1.1/4"
C112-SS	1.1/2"
C2-SS	2"
C212-SS	2.1/2"
C3-SS	3"
C4-SS	4"
Tech Sheet 532	



D

Female Lever Coupling, BSPP

0060	Thread
D12-SS	1/2"
D34-SS	3/4"
D1-SS	1"
D114-SS	1.1/4"
D112-SS	1.1/2"
D2-SS	2"
D212-SS	2.1/2"
D3-SS	3"
D4-SS	4"
Tech Sheet 532	

Female Lever Coupling, NPT

0060	Thread
D12-SS-NPT	1/2"
D34-SS-NPT	3/4"
D1-SS-NPT	1"
D114-SS-NPT	1.1/4"
D112-SS-NPT	1.1/2"
D2-SS-NPT	2"
D212-SS-NPT	2.1/2"
D3-SS-NPT	3"
D4-SS-NPT	4"
Tech Sheet 532	



Dust Plug

0060	Body
DP12-SS	1/2"
DP34-SS	3/4"
DP1-SS	1"
DP112-SS	1.1/2"
DP2-SS	2"
DP212-SS	2.1/2"
DP3-SS	3"
Tech Sheet 532	



Lever Stop

0060	Body
DC34-SS	3/4"
DC1-SS	1"
DC114-SS	1.1/4"
DC112-SS	1.1/2"
DC2-SS	2"
DC3-SS	3"
DC4-SS	4"
Tech Sheet 532	



E

Hose Tail

0060	Thread
E12-SS	1/2"
E34-SS	3/4"
E1-SS	1"
E114-SS	1.1/4"
E112-SS	1.1/2"
E2-SS	2"
E212-SS	2.1/2"
E3-SS	3"
E4-SS	4"
Tech Sheet 532	



F

Male Threaded Plug, BSPT

0060	Thread
F12-SS	1/2"
F34-SS	3/4"
F1-SS	1"
F114-SS	1.1/4"
F112-SS	1.1/2"
F2-SS	2"
F212-SS	2.1/2"
F3-SS	3"
F4-SS	4"
Tech Sheet 532	

Male Threaded Plug, NPT

0060	Body
F12-SS-NPT	1/2"
F34-SS-NPT	3/4"
F1-SS-NPT	1"
F114-SS-NPT	1.1/4"
F112-SS-NPT	1.1/2"
F2-SS-NPT	2"
F212-SS-NPT	2.1/2"
F3-SS-NPT	3"
F4-SS-NPT	4"
Tech Sheet 532	

Please note: 1/2" sizes are only supplied with one locking arm.

CLAW COUPLINGS

LÜDECKE

Claw Couplings DIN 3489, Stainless Steel

Working Temperature: -30°C to +200°C

Maximum Working Pressure: 16 bar

Universal system for aggressive fluids in chemical or petrochemical industry, as well as food or drinking water applications.

Use original DIN 3489 Seal GPOR (EPDM) food or drinking water applications.

Material: Stainless steel 1.4401/1.4404
Seal: FKM
Media: Chemical substances
Claw Distance: 42 mm

stainless steel



Hose Tail

6295	To Suit Hose ID mm
EKT10V	10
EKT13V	13
EKT19V	19
EKT25V	25

stainless steel



Female Thread, BSPP

6295	Thread
EKI38V	3/8'
EKI12V	1/2"
EKI34V	3/4"
EKI10V	1"

stainless steel



Male Thread, BSPP

6295	Thread
EKA12V	1/2'
EKA34V	3/4"
EKA10V	1"

stainless steel



Blank End

6295	Description
EKOV	Blank End
EKMV	Blank End with Chain
EKMV-K	Spare Chain 200mm

Fluid-Air Components Ltd

RJT COUPLINGS

stainless steel

FTPRO

Weld Liner



Stainless Steel

0108	Size
RJTWL1	1″
RJTWL112	1.1/2″
RJTWL2	2″
RJTWL212	2.1/2″
RJTWL3	3″
Tech Sheet 60554	

Reducing Weld Liner



Stainless Steel

0108	Size
RJTRWL2112	2″ to 1.1/2″
Tech Sheet 60554	

Blank Liner



Stainless Steel

0108	Size
RJTBL1	1″
RJTBL112	1.1/2″
RJTBL2	2″
RJTBL212	2.1/2″
RJTBL3	3″
Tech Sheet 60554	

Hose Liner



Stainless Steel

0108	Size
RJTHL1	1″
RJTHL112	1.1/2″
RJTHL2	2″
RJTHL212	2.1/2″
RJTHL3	3″
Tech Sheet 60554	

Hex Nut



Stainless Steel

0108	Size
RJTN1	1″
RJTN112	1.1/2″
RJTN2	2″
RJTN3	3″
Tech Sheet 60554	

Weld Male



Stainless Steel

0108	Size
RJTWM1	1″
RJTWM112	1.1/2″
RJTWM2	2″
RJTWM3	3″
Tech Sheet 60554	

BSPP Adaptor



Stainless Steel

0108	Size	Thread
RJTA1	1″	1″
RJTA112	1.1/2″	1.1/2″
RJTD2	2″	2″
RJTA3	3″	3″
Tech Sheet 60554		

Seal



0108	Size
RJTS1	1″
RJTS112	1.1/2″
RJTS2	2″
RJTS3	3″
Tech Sheet 60554	

FAC Fluid-Air Components Ltd

STAINLESS STEEL LEVER LOCK WATER PUMP COUPLINGS

stainless steel

Male x Hose Connector



0120	Coupling Size	To Suit Hose ID
LLSSMT2	50	2"
LLSSMT33	76	3"
LLSSMT3312	89	3" Tail x 3.1/2"
LLSSMT4	108	4"
LLSSMT6	159	6"
LLSSMT8	194	8"

Female x Hose Connector



0120	Coupling Size	To Suit Hose ID
LLSSFT2	50	2"
LLSSFT3312	89	3" Tail x 3.1/2"
LLSSFT4	108	4"
LLSSFT6	159	6"
LLSSFT8	194	8"

Male Weld End

Other sizes available on request.
Minimum quantity order may apply.



0120	Coupling Size
LLSSMWE2	50
LLSSMWE3312	89
LLSSMWE4	108
LLSSMWE6	159

Female Weld End



0120	Coupling Size
LLSSFWE2	50
LLSSFWE33	76
LLSSFWE3312	89
LLSSFWE4	108
LLSSFWE6	159

Male x Male BSPP Pipe Thread

Other sizes available on request.
Minimum quantity order may apply.



With Lever Closure Ring, BSPP

0120	Coupling Size	To Suit Hose ID
LLSSMBSP2	50	2"
LLSSMBSP33	76	3"
LLSSMBSP3312	89	3" BSPP x 3.1/2"
LLSSMBSP4	108	4"

Female complete with BSPP Male Pipe Thread

Other sizes available on request.
Minimum quantity order may apply.



0120	Coupling Size	Thread
LLSSFBSP2	50	2"
LLSSFBSP33	76	3"
LLSSFBSP3312	89	3" BSPP x 3.1/2"
LLSSFBSP4	108	4"
LLSSFBSP5	133	5"
LLSSFBSP6	159	6"

Male End Cap



0120	Coupling Size
LLSSMEC2	50
LLSSMEC33	76
LLSSMEC3312	89
LLSSMEC4	108
LLSSMEC5	133
LLSSMEC6	159

Female End Cap

Other sizes available on request.
Minimum quantity order may apply.



0120	Coupling Size
LLSSFEC3312	89
LLSSFEC4	108
LLSSFEC6	159

Fluid-Air Components Ltd

150lb 316 STAINLESS STEEL PIPE FITTINGS

RoHS 3 COMPLIANT | ISO 9001:2015 | stainless steel | HAITIMA

This technical data is applicable to the full range of 316 Stainless Steel Adaptors only.
Threads: Tapered in conformity with ISO 7.1, BS 21, DIN 2999. Parallel in conformity with BS 2779, ISO 228.
Dimensions: All components are manufactured to the requirements of ASTM A-351.
The dimensions are in accordance with ANSI B16.3.

Working Temperature: -20°C to +260°C

Working Pressure: 20 bar

Equal Cross



Female Thread, BSPP

1111	Thread
EC-18	1/8"
EC-14	1/4"
EC-38	3/8"
EC-12	1/2"
EC-34	3/4"
EC-1	1"
EC-114	1.1/4"
EC-112	1.1/2"
EC-2	2"
Tech Sheet 1800	

Equal Tee



Female Thread, BSPP

1111	Thread
ET-18	1/8"
ET-14	1/4"
ET-38	3/8"
ET-12	1/2"
ET-34	3/4"
ET-1	1"
ET-114	1.1/4"
ET-112	1.1/2"
ET-2	2"
ET-212	2.1/2"
ET-3	3"
ET-4	4"
Tech Sheet 1799	

Straight Hose Tails



Male Thread, BSPT

1111	Thread	To Suit Hose ID
HT-18-06	1/8"	1/4" (6mm)
HT-14	1/4"	1/4" (6mm)
HT-14-08	1/4"	5/16" (8mm)
HT-14-10	1/4"	3/8" (10mm)
HT-14-13	1/4"	1/2" (13mm)
HT-38-08	3/8"	5/16" (8mm)
HT-38	3/8"	3/8" (10mm)
HT-38-13	3/8"	1/2" (13mm)
HT-12-06	1/2"	1/4" (6mm)
HT-12-10	1/2"	3/8" (10mm)
HT-12	1/2"	1/2" (13mm)
HT-12-19	1/2"	3/4" (19mm)
HT-12-25	1/2"	1" (25mm)
HT-12-16	1/2"	5/8"
HT-34-13	3/4"	1/2" (13mm)
HT-34	3/4"	3/4" (19mm)
HT-1-19	1"	3/4" (19mm)
HT-1	1"	1" (25mm)
HT-1-31	1"	1.1/4" (31mm)
HT-114	1.1/4"	1.1/4" (31mm)
HT-112	1.1/2"	1.1/2" (38mm)
HT-2	2"	2" (50mm)
HT-212	2.1/2"	2.1/2" (63mm)
HT-3	3"	3" (75mm)
HT-4	4"	4" (100mm)
Tech Sheet 1795		



Female Fixed Thread, BSPP

1111	Thread	To Suit Hose ID
SFHT10/06	1/8"	6mm (1/4")
SFHT13/06	1/4"	6mm (1/4")
SFHT13/09	1/4"	9mm (3/8")
SFHT17/10	3/8"	10mm (3/8")
SFHT21/13	1/2"	13mm (1/2")
SFHT26/19	3/4"	19mm (3/4")
SFHT33/25	1"	25mm (1")
SFHT42/32	1.1/4"	32mm (1.1/4")
SFHT48/38	1.1/2"	38mm (1.1/2")
SFHT52/51	2"	51mm (2")
Tech Sheet 20777		



Equal Hose Joiner

1111	To Suit Hose ID
DS06-SS	1/4" (6mm)
DS08-SS	5/16" (8mm)
DS10-SS	3/8" (10mm)
DS13-SS	1/2" (13mm)
Tech Sheet 20778	



Swivel Female Thread, 60° Coned Seat, BSPP

1111	Thread	To Suit Hose ID
FH13/14SS	1/4"	1/4" (6mm)
FH17/38SS	3/8"	3/8" (10mm)
FH21/12SS	1/2"	1/2" (13mm)
FH26/12SS	3/4"	1/2" (13mm)
FH26/34SS	3/4"	3/4" (19mm)
FH33/19SS	1"	3/4"
FH33/25SS	1"	1"
FH48/38SS	1.1/2"	1.1/2"
FH52/50SS	2"	2"
Tech Sheet 20779		

Barrel Nipple



Male Thread, BSPT

1111	Thread	Length mm
BN-18X30	1/8"	30
BN-18	1/8"	40
BN-14	1/4"	40
BN-14X80	1/4"	80
BN-38	3/8"	40
BN-38X80	3/8"	80
BN-12	1/2"	60
BN-12X80	1/2"	80
BN-34	3/4"	60
BN-34X80	3/4"	80
BN-1	1"	60
BN-1X100	1"	100
BN-1X150	1"	150
BN-114	1.1/4"	80
BN-112	1.1/2"	80
BN-2	2"	100
BN-212	2.1/2"	100
BN-3	3"	120
BN-4	4"	120
Tech Sheet 1803		

150lb 316 STAINLESS STEEL PIPE FITTINGS

RoHS 3 COMPLIANT | ISO 9001:2015 | stainless steel | HAITIMA

Close Nipple



Male Thread, BSPP

1111	Thread
CPN-14	1/4"
CPN-38	3/8"
CPN-12	1/2"
CPN-34	3/4"
CPN-1	1"
CPN-114	1.1/4"
CPN-112	1.1/2"
CPN-2	2"
CPN-212	2.1/2"
Tech Sheet 1801	

Female Reducing Socket



Female Thread, BSPP

1111	Thread	Thread
FRS-14-18	1/4"	1/8"
FRS-38-14	3/8"	1/4"
FRS-38-18	3/8"	1/8"
FRS-12-38	1/2"	3/8"
FRS-12-14	1/2"	1/4"
FRS-12-18	1/2"	1/8"
FRS-34-14	3/4"	1/4"
FRS-34-12	3/4"	1/2"
FRS-34-38	3/4"	3/8"
FRS-1-34	1"	3/4"
FRS-1-14	1"	1/4"
FRS-1-38	1"	3/8"
FRS-1-12	1"	1/2"
FRS-114-1	1.1/4"	1"
FRS-114-12	1.1/4"	1/2"
FRS-114-34	1.1/4"	3/4"
FRS-112-1	1.1/2"	1"
FRS-112-34	1.1/2"	3/4"
FRS-112-114	1.1/2"	1.1/4"
FRS-2-34	2"	3/4"
FRS-2-1	2"	1"
FRS-2-112	2"	1.1/2"
FRS-2-114	2"	1.1/4"
FRS-212-114	2.1/2"	1.1/4"
FRS-212-2	2.1/2"	2"
FRS-3-114	3"	1.1/4"
FRS-3-2	3"	2"
FRS-3-212	3"	2.1/2"
FRS-4-2	4"	2"
FRS-4-3	4"	3"
Tech Sheet 1802		

45º Equal Elbow



Female Thread, BSPP

1111	Thread
OE-18	1/8"
OE-14	1/4"
OE-38	3/8"
OE-12	1/2"
OE-34	3/4"
OE-1	1"
OE-114	1.1/4"
OE-112	1.1/2"
OE-2	2"
OE-212	2.1/2"
OE-3	3"
OE-4	4"
Tech Sheet 1796	

45° Equal Bracket Elbow



Female Thread, BSPP

1111	Thread
WEP-12	1/2"
Tech Sheet 1797	

90º Equal Elbow



Female Thread, BSPP

1111	Thread
EE-18	1/8"
EE-14	1/4"
EE-38	3/8"
EE-12	1/2"
EE-34	3/4"
EE-1	1"
EE-114	1.1/4"
EE-112	1.1/2"
EE-2	2"
EE-212	2.1/2"
EE-3	3"
EE-4	4"
Tech Sheet 1797	

90º Street Elbow



Male Thread, BSPT x Female Thread, BSPP

1111	Male Thread	Female Thread
SE-18	1/8"	1/8"
SE-14	1/4"	1/4"
SE-38	3/8"	3/8"
SE-12	1/2"	1/2"
SE-34	3/4"	3/4"
SE-1	1"	1"
SE-114	1.1/4"	1.1/4"
SE-112	1.1/2"	1.1/2"
SE-2	2"	2"
SE-212	2.1/2"	2.1/2"
SE-3	3"	3"
SE-4	4"	4"
Tech Sheet 1798		

Equal Nipple



Male Thread, BSPT

1111	Thread
HN-18	1/8"
HN-14	1/4"
HN-38	3/8"
HN-12	1/2"
HN-34	3/4"
HN-1	1"
HN-114	1.1/4"
HN-112	1.1/2"
HN-2	2"
HN-212	2.1/2"
HN-3	3"
HN-4	4"
Tech Sheet 1804	

Male Thread, NPT

1111	Thread
NPT62001010	1/8"
NPT62001313	1/4"
NPT62001717	3/8"
NPT62002121	1/2"
NPT62002727	3/4"
NPT62003232	1"
NPT62004242	1.1/4"
NPT62004848	1.1/2"
NPT62006060	2"
NPT62007676	2.1/2"
NPT62008989	3"
NPT62000114	4"
Tech Sheet 1804	

ABS | DNV·GL | Bureau Veritas | Lloyd's Register | RoHS

Fluid-Air Components Ltd

150lb 316 STAINLESS STEEL PIPE FITTINGS

RoHS 3 COMPLIANT | ISO 9001:2015 | stainless steel | HAITIMA

Hexagon Blanking Cap



Female Thread, BSPP

1111	Thread
HBC-18	1/8"
HBC-14	1/4"
HBC-38	3/8"
HBC-12	1/2"
HBC-34	3/4"
HBC-1	1"
HBC-114	1.1/4"
HBC-112	1.1/2"
HBC-2	2"
HBC-212	2.1/2"
HBC-3	3"
HBC-4	4"

Tech Sheet 1805

Blanking Plug



Male Thread, BSPT

1111	Thread
HP-18	1/8"
HP-14	1/4"
HP-38	3/8"
HP-12	1/2"
HP-34	3/4"
HP-1	1"
HP-114	1.1/4"
HP-112	1.1/2"
HP-2	2"
HP-212	2.1/2"
HP-3	3"

Tech Sheet 1806

Male Thread, NPT

1111	Thread
NPT62181000	1/8"
NPT62181300	1/4"
NPT62181700	3/8"
NPT62182100	1/2"
NPT62182700	3/4"
NPT62183200	1"
NPT62184200	1.1/4"
NPT62184800	1.1/2"
NPT62186000	2"
NPT62187600	2.1/2"
NPT62188900	3"

Tech Sheet 1808

Female Union



Female Thread, BSPP (2 Piece)

1111	Thread
HU-18	1/8"
HU-14	1/4"
HU-38	3/8"
HU-12	1/2"
HU-34	3/4"
HU-1	1"
HU-114	1.1/4"
HU-112	1.1/2"
HU-2	2"
HU-212	2.1/2"
HU-3	3"
HU-4	4"

Tech Sheet 1807

Male/Female Union



Male Thread, BSPT x Female Thread, BSPP (2 Piece)

1111	Thread
MFU-14	1/4"
MFU-38	3/8"
MFU-12	1/2"
MFU-34	3/4"
MFU-1	1"
MFU-114	1.1/4"
MFU-112	1.1/2"
MFU-2	2"
MFU-4	4"

Tech Sheet 1808

Lock Nut



Female Thread, BSPP

1111	Thread
LN-18	1/8"
LN-14	1/4"
LN-38	3/8"
LN-12	1/2"
LN-34	3/4"
LN-1	1"
LN-114	1.1/4"
LN-112	1.1/2"
LN-2	2"
LN-212	2.1/2"
LN-3	3"
LN-4	4"

Tech Sheet 1809

Reducing Bush



Male Thread, BSPT x Female Thread, BSPP

1111	Male Thread	Female Thread
RB-14-18	1/4"	1/8"
RB-38-14	3/8"	1/4"
RB-38-18	3/8"	1/8"
RB-12-14	1/2"	1/4"
RB-12-18	1/2"	1/8"
RB-12-38	1/2"	3/8"
RB-34-12	3/4"	1/2"
RB-34-14	3/4"	1/4"
RB-34-18	3/4"	1/8"
RB-34-38	3/4"	3/8"
RB-1-12	1"	1/2"
RB-1-14	1"	1/4"
RB-1-34	1"	3/4"
RB-1-38	1"	3/8"
RB-114-1	1.1/4"	1"
RB-114-12	1.1/4"	1/2"
RB-114-34	1.1/4"	3/4"
RB-112-1	1.1/2"	1"
RB-112-12	1.1/2"	1/2"
RB-112-34	1.1/2"	3/4"
RB-112-114	1.1/2"	1.1/4"
RB-2-1	2"	1"
RB-2-34	2"	3/4"
RB-2-112	2"	1.1/2"
RB-2-114	2"	1.1/4"
RB-212-1	2.1/2"	1"
RB-212-2	2.1/2"	2"
RB-212-112	2.1/2"	1.1/2"
RB-212-114	2.1/2"	1.1/4"
RB-3-1	3"	1"
RB-3-112	3"	1.1/2"
RB-3-2	3"	2"
RB-3-212	3"	2.1/2"
RB-4-3	4"	3"

Tech Sheet 1810

Male Thread, NPTF x Female Thread, NPTF

1111	Male Thread	Female Thread
NPT62041310	1/4"	1/8"
NPT62041713	3/8"	1/4"
NPT62042117	1/2"	3/8"
NPT62042721	3/4"	1/2"
NPT62043227	1"	3/4"
NPT62044232	1.1/4"	1"
NPT62044842	1.1/2"	1.1/4"
NPT62046048	2"	1.1/2"
NPT62047660	2.1/2"	2"
NPT62048976	3"	2.1/2"

ABS | DNV·GL | Marine Division Recognition Bureau Veritas Certification | Lloyd's Register | RoHS

150lb 316 STAINLESS STEEL PIPE FITTINGS

RoHS 3 COMPLIANT | ISO 9001:2015 | stainless steel | HAITIMA

Reducing Nipple



Male Thread, BSPT

1111	Thread	Thread
RHN-14-18	1/4"	1/8"
RHN-12-14	1/2"	1/4"
RHN-12-18	1/2"	1/8"
RHN-12-38	1/2"	3/8"
RHN-38-14	3/8"	1/4"
RHN-38-18	3/8"	1/8"
RHN-34-12	3/4"	1/2"
RHN-34-14	3/4"	1/4"
RHN-34-18	3/4"	1/8"
RHN-34-38	3/4"	3/8"
RHN-1-12	1"	1/2"
RHN-1-14	1"	1/4"
RHN-1-34	1"	3/4"
RHN-1-38	1"	3/8"
RHN-114-1	1.1/4"	1"
RHN-114-12	1.1/4"	1/2"
RHN-114-34	1.1/4"	3/4"
RHN-112-1	1.1/2"	1"
RHN-112-12	1.1/2"	1/2"
RHN-112-34	1.1/2"	3/4"
RHN-112-114	1.1/2"	1.1/4"
RHN-2-1	2"	1"
RHN-2-12	2"	1/2"
RHN-2-34	2"	3/4"
RHN-2-112	2"	1.1/2"
RHN-2-114	2"	1.1/4"
RHN-3-2	3"	2"
Tech Sheet 1811		

Welding Nipple



Male Thread, BSPT

1111	Thread	Length mm
WN-18	1/8"	30
WN-14	1/4"	30
WN-38	3/8"	30
WN-12	1/2"	35
WN-34	3/4"	40
WN-1	1"	40
WN-114	1.1/4"	50
WN-112	1.1/2"	50
WN-2	2"	50
WN-212	2.1/2"	60
WN-3	3"	70
WN-4	4"	80
Tech Sheet 1813		

Square Head Plug



Male Thread, BSPT

1111	Thread
SP-18	1/8"
SP-14	1/4"
SP-38	3/8"
SP-12	1/2"
SP-34	3/4"
SP-1	1"
SP-114	1.1/4"
SP-112	1.1/2"
SP-2	2"
SP-212	2.1/2"
SP-3	3"
Tech Sheet 1814	

Round Blanking Cap



Female Thread, BSPP

1111	Thread
RC-18	1/8"
RC-14	1/4"
RC-38	3/8"
RC-12	1/2"
RC-34	3/4"
RC-1	1"
RC-114	1.1/4"
RC-112	1.1/2"
RC-2	2"
RC-212	2.1/2"
RC-3	3"
Tech Sheet 1812	

Threaded Half Socket



Female Thread, BSPP

1111	Thread
HS-18	1/8"
HS-14	1/4"
HS-38	3/8"
HS-12	1/2"
HS-34	3/4"
HS-1	1"
HS-114	1.1/4"
HS-112	1.1/2"
HS-2	2"
HS-212	2.1/2"
HS-3	3"
HS-4	4"
Tech Sheet 1816	

Threaded Full Socket



Female Thread, BSPP

1111	Thread
FS-18	1/8"
FS-14	1/4"
FS-38	3/8"
FS-12	1/2"
FS-34	3/4"
FS-1	1"
FS-114	1.1/4"
FS-112	1.1/2"
FS-2	2"
FS-212	2.1/2"
FS-3	3"
FS-4	4"
Tech Sheet 1815	

Female Thread, NPT

1111	Thread
NPT62061010	1/8"
NPT62061313	1/4"
NPT62061717	3/8"
NPT62062121	1/2"
NPT62062727	3/4"
NPT62063232	1"
NPT62064242	1.1/4"
NPT62064848	1.1/2"
NPT62066060	2"
NPT62067676	2.1/2"
NPT62068989	3"
NPT62060114	4"

316 Stainless Steel Tube

Seamless schedule 40 ASTM A312/AMSE SA312-A530.
Conforms to NACE standard MR-01-75, Din50049-3.1.B.

N.B. Delivery may take up to 48 hours.



3 Metre Lengths, Random

0214	NB	Wall Thickness mm
2028-5839	1/8"	1.73
2028-5854	1/4"	2.24
2028-5862	3/8"	2.31
2028-5870	1/2"	2.77
2028-5953	3/4"	2.87
2028-5961	1"	3.38
2028-5979	1.1/4"	3.56
2028-5987	1.1/2"	3.68
2028-5995	2"	3.91
Tech Sheet 831		

ABS | DNV·GL | Bureau Veritas | Lloyd's Register | RoHS

Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

90° Equal Female Elbow



NPT

0434	Thread
1012-0001	1/4"
1012-0002	3/8"
1012-0003	1/2"
1012-0004	3/4"
1012-0005	1"
1012-0006	1.1/4"
1012-0007	1.1/2"
1012-0008	2"
Tech Sheet 20506	

BSPT

0434	Thread
1012-0009	1/4"
1012-0010	3/8"
1012-0011	1/2"
1012-0012	3/4"
1012-0013	1"
1012-0014	1.1/4"
1012-0016	2"
Tech Sheet 20494	



Socket Weld

0434	NB
1012-0017	1/4"
1012-0018	3/8"
1012-0019	1/2"
1012-0021	1"
1012-0022	1.1/4"
1012-0023	1.1/2"
1012-0024	2"
Tech Sheet 20521	

90° Equal Male/ Female Street Elbow



NPT

0434	Thread
1012-0041	1/4"
1012-0042	3/8"
1012-0043	1/2"
1012-0044	3/4"
1012-0045	1"
1012-0046	1.1/4"
1012-0047	1.1/2"
1012-0048	2"
Tech Sheet 20515	

45° Equal Female Elbow



NPT

0434	Thread
1012-0025	1/4"
1012-0027	1/2"
1012-0028	3/4"
1012-0029	1"
1012-0030	1.1/4"
1012-0031	1.1/2"
1012-0032	2"
Tech Sheet 20505	

Socket Weld

0434	NB
1012-0033	1/4"
1012-0034	3/8"
1012-0035	1/2"
1012-0036	3/4"
1012-0037	1"
1012-0038	1.1/4"
1012-0039	1.1/2"
Tech Sheet 20520	

Equal Tee



NPT

0434	Thread
1012-0049	1/4"
1012-0050	3/8"
1012-0051	1/2"
1012-0052	3/4"
1012-0053	1"
1012-0054	1.1/4"
1012-0055	1.1/2"
1012-0056	2"
Tech Sheet 20516	

BSPT

0434	Thread
1012-0057	1/4"
1012-0058	3/8"
1012-0059	1/2"
1012-0060	3/4"
1012-0061	1"
1012-0062	1.1/4"
1012-0063	1.1/2"
1012-0064	2"
Tech Sheet 20495	



Socket Weld

0434	NB
1012-0065	1/4"
1012-0066	3/8"
1012-0067	1/2"
1012-0068	3/4"
1012-0069	1"
1012-0070	1.1/4"
1012-0071	1.1/2"
1012-0072	2"
Tech Sheet 20526	

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FT PRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Equal Cross



NPT

0434	Thread
1012-0073	1/4"
1012-0074	3/8"
1012-0075	1/2"
1012-0076	3/4"
1012-0077	1"
1012-0078	1.1/4"
1012-0079	1.1/2"
1012-0080	2"
Tech Sheet 20504	



Socket Weld

0434	NB
1012-0082	3/8"
1012-0083	1/2"
1012-0084	3/4"
1012-0085	1"
1012-0086	1.1/4"
1012-0087	1.1/2"
1012-0088	2"
Tech Sheet 20519	

Male / Female Union



NPT

0434	Thread
1012-0089	1/4"
1012-0090	3/8"
1012-0091	1/2"
1012-0092	3/4"
1012-0093	1"
1012-0094	1.1/4"
1012-0095	1.1/2"
1012-0096	2"
Tech Sheet 20518	

Female Union



NPT

0434	Thread
1012-0097	1/4"
1012-0098	3/8"
1012-0099	1/2"
1012-0100	3/4"
1012-0101	1"
1012-0102	1.1/4"
1012-0103	1.1/2"
1012-0104	2"
Tech Sheet 20517	

BSPT

0434	Thread
1012-0106	3/8"
1012-0107	1/2"
1012-0108	3/4"
1012-0109	1"
1012-0110	1.1/4"
1012-0111	1.1/2"
1012-0112	2"
Tech Sheet 20500	



Socket Weld

0434	NB
1012-0113	1/4"
1012-0114	3/8"
1012-0115	1/2"
1012-0116	3/4"
1012-0117	1"
1012-0118	1.1/4"
1012-0119	1.1/2"
1012-0120	2"
Tech Sheet 20527	

Male Hex Nipple



NPT

0434	Thread
1012-0121	1/4"
1012-0122	3/8"
1012-0123	1/2"
1012-0124	3/4"
1012-0125	1"
1012-0126	1.1/4"
1012-0127	1.1/2"
1012-0128	2"
Tech Sheet 20509	

BSPT

0434	Thread
1012-0129	1/4"
1012-0130	3/8"
1012-0131	1/2"
1012-0132	3/4"
1012-0133	1"
1012-0134	1.1/4"
1012-0135	1.1/2"
1012-0136	2"
Tech Sheet 20498	

Male Barrel Nipple



NPT

0434	Thread	Length mm
1012-0137	1/4"	30
1012-0138	3/8"	40
1012-0139	1/2"	60
1012-0140	3/4"	60
1012-0141	1"	60
1012-0142	1.1/4"	80
1012-0143	1.1/2"	80
1012-0144	2"	100
Tech Sheet 20503		

FAC Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Male Hex Reducing Nipple



BSPT

0434	Thread	Thread
1012-0166	1/4"	1/8"
1012-0167	3/8"	1/8"
1012-0168	1/2"	1/4"
1012-0169	1/2"	3/8"
1012-0170	3/4"	3/8"
1012-0171	3/4"	1/2"
1012-0172	1"	1/2"
1012-0173	1"	3/4"
1012-0174	1.1/4"	3/4"
1012-0175	1.1/4"	1"
1012-0176	1.1/2"	1"
1012-0177	1.1/2"	1.1/4"
1012-0178	2"	1"
1012-0179	2"	1.1/4"
1012-0180	2"	1.1/2"
Tech Sheet 20499		

NPT

0434	Thread	Thread
1012-0145	1/4"	1/8"
1012-0146	3/8"	1/8"
1012-0147	3/8"	1/4"
1012-0148	1/2"	1/8"
1012-0149	1/2"	1/4"
1012-0150	1/2"	3/8"
1012-0151	3/4"	1/4"
1012-0152	3/4"	3/8"
1012-0153	3/4"	1/2"
1012-0154	1"	3/8"
1012-0155	1"	1/2"
1012-0156	1"	3/4"
1012-0157	1.1/4"	1/2"
1012-0158	1.1/4"	3/4"
1012-0159	1.1/4"	1"
1012-0160	1.1/2"	3/4"
1012-0161	1.1/2"	1"
1012-0162	1.1/2"	1.1/4"
1012-0163	2"	1"
1012-0164	2"	1.1/4"
1012-0165	2"	1.1/2"
Tech Sheet 20513		

Full Coupling



NPT

0434	Thread
1012-0181	1/4"
1012-0182	3/8"
1012-0183	1/2"
1012-0184	3/4"
1012-0185	1"
1012-0186	1.1/4"
1012-0187	1.1/2"
1012-0188	2"
Tech Sheet 20507	

BSPT

0434	Thread
1012-0189	1/4"
1012-0190	3/8"
1012-0191	1/2"
1012-0192	3/4"
1012-0193	1"
1012-0194	1.1/4"
1012-0195	1.1/2"
1012-0196	2"
Tech Sheet 20496	



Socket Weld

0434	NB
1012-0197	1/4"
1012-0198	3/8"
1012-0199	1/2"
1012-0200	3/4"
1012-0201	1"
1012-0202	1.1/4"
1012-0203	1.1/2"
1012-0204	2"
Tech Sheet 20522	

Half Coupling



NPT

0434	Thread
1012-0205	1/4"
1012-0206	3/8"
1012-0208	3/4"
1012-0209	1"
1012-0210	1.1/4"
1012-0211	1.1/2"
1012-0212	2"
Tech Sheet 20508	

BSPT

0434	Thread
1012-0213	1/4"
1012-0214	3/8"
1012-0215	1/2"
1012-0216	3/4"
1012-0217	1"
1012-0218	1.1/4"
1012-0219	1.1/2"
1012-0220	2"
Tech Sheet 20497	



Socket Weld

0434	NB
1012-0221	1/4"
1012-0222	3/8"
1012-0223	1/2"
1012-0224	3/4"
1012-0225	1"
1012-0226	1.1/4"
1012-0228	2"
Tech Sheet 20523	

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel FTPRO

- ASTM A182 316/L stainless steel
- Dimensions to ANSI B16.11/BS3799
- Sizes 1/4" to 2"
- NPT threaded to ANSI B2.1
- BSPT threaded to ISO 7/1
- Pressure/temperature ratings according to BS 3799
- Pressure rating performance will vary depending on temperature.

Working Temperature: -100°C to +525°C

Maximum Working Pressure: 207 bar

Reducing Coupling



NPT

0434	Thread	Thread
1012-0229	1/4"	1/8"
1012-0231	1/2"	1/4"
1012-0232	1/2"	3/8"
1012-0233	3/4"	3/8"
1012-0234	3/4"	1/2"
1012-0235	1"	1/2"
1012-0236	1"	3/4"
1012-0237	1.1/4"	3/4"
1012-0238	1.1/4"	1"
1012-0239	1.1/2"	1"
1012-0240	1.1/2"	1.1/4"
1012-0241	2"	1"
1012-0242	2"	1.1/4"
1012-0243	2"	1.1/2"
Tech Sheet 20512		



Socket Weld

0434	NB	NB
1012-0244	1/4"	1/8"
1012-0245	3/8"	1/4"
1012-0246	1/2"	1/4"
1012-0247	1/2"	3/8"
1012-0248	3/4"	3/8"
1012-0249	3/4"	1/2"
1012-0250	1"	1/2"
1012-0252	1.1/4"	1"
1012-0253	1.1/2"	1"
1012-0254	1.1/2"	1.1/4"
1012-0255	2"	1"
1012-0256	2"	1.1/4"
1012-0257	2"	1.1/2"
Tech Sheet 20524		

Reducing Bush



NPT

0434	Thread	Thread
1012-0258	1/4"	1/8"
1012-0259	3/8"	1/8"
1012-0260	3/8"	1/4"
1012-0261	1/2"	1/8"
1012-0262	1/2"	1/4"
1012-0263	1/2"	3/8"
1012-0264	3/4"	1/4"
1012-0265	3/4"	3/8"
1012-0266	3/4"	1/2"
1012-0267	1"	1/4"
1012-0268	1"	3/8"
1012-0269	1"	1/2"
1012-0270	1"	3/4"
1012-0271	1.1/4"	1/2"
1012-0272	1.1/4"	3/4"
1012-0273	1.1/4"	1"
1012-0274	1.1/2"	3/4"
1012-0275	1.1/2"	1"
1012-0276	1.1/2"	1.1/4"
1012-0277	2"	1"
1012-0278	2"	1.1/4"
1012-0279	2"	1.1/2"
Tech Sheet 20511		

BSPT

0434	Thread	Thread
1012-0280	1/4"	1/8"
1012-0281	3/8"	1/8"
1012-0282	3/8"	1/4"
1012-0283	1/2"	1/8"
1012-0284	1/2"	1/4"
1012-0285	1/2"	3/8"
1012-0286	3/4"	1/4"
1012-0287	3/4"	3/8"
1012-0288	3/4"	1/2"
1012-0289	1"	1/4"
1012-0290	1"	3/8"
1012-0291	1"	1/2"
1012-0292	1"	3/4"
1012-0293	1.1/4"	1/2"
1012-0294	1.1/4"	3/4"
1012-0295	1.1/4"	1"
1012-0296	1.1/2"	3/4"
1012-0297	1.1/2"	1"
1012-0298	1.1/2"	1.1/4"
1012-0299	2"	1"
1012-0300	2"	1.1/4"
1012-0301	2"	1.1/2"
Tech Sheet 20502		

Hex Head Plug



NPT

0434	Thread
1012-0302	1/4"
1012-0303	3/8"
1012-0304	1/2"
1012-0305	3/4"
1012-0306	1"
1012-0307	1.1/4"
1012-0308	1.1/2"
1012-0309	2"
Tech Sheet 20510	

BSPT

0434	Thread
1012-0310	1/4"
1012-0311	3/8"
1012-0312	1/2"
1012-0313	3/4"
1012-0314	1"
1012-0315	1.1/4"
1012-0316	1.1/2"
1012-0317	2"
Tech Sheet 20501	

Round Cap



NPT

0434	Thread
1012-0318	1/4"
1012-0319	3/8"
1012-0320	1/2"
1012-0321	3/4"
1012-0322	1"
1012-0323	1.1/4"
1012-0324	1.1/2"
1012-0325	2"
Tech Sheet 20514	



Socket Weld

0434	NB
1012-0326	1/4"
1012-0327	3/8"
1012-0328	1/2"
1012-0329	3/4"
1012-0330	1"
1012-0331	1.1/4"
1012-0332	1.1/2"
1012-0333	2"
Tech Sheet 20525	

Fluid-Air Components Ltd

3000lb 316 STAINLESS STEEL PIPE FITTINGS

stainless steel

FT PRO

Slip-on PN16/3



BS4504: Sect 3.1:1989

1113	Size
SSFSB-12	1/2"
SSFSB-34	3/4"
SSFSB-1	1"
SSFSB-114	1.1/4"
SSFSB-112	1.1/2"
SSFSB-2	2"
SSFSB-3	3"
Tech Sheet 1500	

Slip-on 150lb



ANSI B16.5

1113	Size
SSFSA-12	1/2"
SSFSA-1	1"
SSFSA-112	1.1/2"
SSFSA-2	2"
Tech Sheet 1500	

Table D




1113	Size
TABLE-D-112	1.1/2"
TABLE-D-4	4"
Tech Sheet 1500	

Table E



1113	Size
TABLE-E-1	1"
TABLE-E-112	1.1/2"
TABLE-E-2	2"
TABLE-E-3	3"
Tech Sheet 1500	

Blind PN16/8



BS4504: Sect 3.1:1989

1113	Size
SSFBB-12	1/2"
SSFBSB-34	3/4"
SSFBSB-1	1"
SSFBSB-114	1.1/4"
SSFBSB-112	1.1/2"
SSFBB-2	2"
SSFBB-3	3"
Tech Sheet 1500	

Blind 150lb



BS4504: Sect 3.1:1989

1113	Size
SSFBA-12	1/2"
SSFBA-34	3/4"
SSFBA-1	1"
SSFBA-2	2"
SSFBA-3	3"
Tech Sheet 1500	

Weld Neck 150lb



ANSI B16.5

1113	Size
SSFWA-34	3/4"
SSFWA-2	2"
SSFWA-3	3"
Tech Sheet 1500	

Customers who bought from this page also purchased...



FT PRO

Flange Gaskets

...see page **1389**

Fluid-Air Components Ltd

BS TYPE, 316L HYGIENIC PIPE FITTINGS

stainless steel FT PRO

Elbows



90° Bends, Long

0706	OD
BSL2S-316-1	1"
BSL2S-316-1.5	1.1/2"
BSL2S-316-2	2"
BSL2S-316-2.5	2.1/2"
BSL2S-316-3	3"
BSL2S-316-4	4"
Tech Sheet 68082	



90° Bends, Short

0706	OD
BS2WCL-316-1	1"
BS2WCL-316-1.5	1.1/2"
BS2WCL-316-2	2"
BS2WCL-316-2.5	2.1/2"
BS2WCL-316-3	3"
BS2WCL-316-4	4"
Tech Sheet 68082	



45° Bends, Long

0706	OD
BSL2KS-316-1	1"
BSL2KS-316-1.5	1.1/2"
BSL2KS-316-2	2"
BSL2KS-316-2.5	2.1/2"
BSL2KS-316-3	3"
BSL2KS-316-4	4"
Tech Sheet 68082	

Tees



Short Tees

0706	OD
BS7WWW-316-34	3/4"
BS7WWW-316-1	1"
BS7WWW-316-1.5	1.1/2"
BS7WWW-316-2	2"
BS7WWW-316-2.5	2.1/2"
BS7WWW-316-3	3"
Tech Sheet 68082	



Pulled Tees

0706	OD
BS7WWO-316-1	1"
BS7WWO-316-1.5	1.1/2"
BS7WWO-316-2	2"
BS7WWO-316-2.5	2.1/2"
BS7WWO-316-3	3"
BS7WWO-316-4	4"
Tech Sheet 68082	

Reducers



Concentric Reducing Cones

0706	OD A	OD B
BSL31-316-1X0.5	1"	1/2"
BSL31-316-1.5X1	1.1/2"	1"
BSL31-316-2X1	2"	1"
BSL31-316-2X1.5	2"	1.1/2"
BSL31-316-2.5X1	2.1/2"	1"
BSL31-316-2.5X15	2.1/2"	1.1/2"
BSL31-316-2.5X2	2.1/2"	2"
BSL31-316-3X2	3"	2"
BSL31-316-3X2.5	3"	2.1/2"
BSL31-316-4X1.5	4"	1.1/2"
BSL31-316-4X2	4"	2"
BSL31-316-4X2.5	4"	2.1/2"
BSL31-316-4X3	4"	3"
Tech Sheet 68082		



Eccentric Reducing Cones

0706	OD A	OD B
BSL32-316075X0.5	3/4"	1/2"
BSL32-316-2X1	2"	1"
BSL32-316-2X1.5	2"	1.1/2"
BSL32-316-2.5X2	2.1/2"	2"
BSL32-316-3X2	3"	2"
BSL32-316-3X2.5	3"	2.1/2"
BSL32-316-4X1.5	4"	1.1/2"
BSL32-316-4X2	4"	2"
BSL32-316-4X3	4"	3"
Tech Sheet 68082		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

BS TYPE, 316L HYGIENIC PIPE FITTINGS

stainless steel

FTPRO

IDF Weld Fittings



Hex Nut

0706	Size
BSIDF-13H-1	1"
BSIDF-13H-1.5	1.1/2"
BSIDF-13H-2	2"
BSIDF-13H-2.5	2.1/2"
BSIDF-13H-3	3"
Tech Sheet 68081	



Welding Male

0706	Size
BSIDF-15-1	1"
BSIDF-15-1.5	1.1/2"
BSIDF-15-2	2"
BSIDF-15-2.5	2.1/2"
BSIDF-15-3	3"
BSIDF-15-4	4"
Tech Sheet 68081	



Welding Liner

0706	Size
BSIDF-14-1	1"
BSIDF-14-1.5	1.1/2"
BSIDF-14-2	2"
BSIDF-14-2.5	2.1/2"
BSIDF-14-3	3"
BSIDF-14-4	4"
Tech Sheet 68081	



EPDM Seal

0706	Size
BSIDF-SEAL-1	1"
BSIDF-SEAL-1.5	1.1/2"
BSIDF-SEAL-2	2"
BSIDF-SEAL-2.5	2.1/2"
BSIDF-SEAL-3	3"
BSIDF-SEAL-4	4"
Tech Sheet 68081	

RJT Weld Fittings



Hex Nut

0706	Size
BSRJT-13H-1	1"
BSRJT-13H-1.5	1.1/2"
BSRJT-13H-2	2"
BSRJT-13H-2.5	2.1/2"
BSRJT-13H-3	3"
BSRJT-13H-4	4"
Tech Sheet 68081	



Welding Male

0706	Size
BSRJT-15-1	1"
BSRJT-15-1.5	1.1/2"
BSRJT-15-2	2"
BSRJT-15-2.5	2.1/2"
BSRJT-15-3	3"
BSRJT-15-4	4"
Tech Sheet 68081	



Welding Liner

0706	Size
BSRJT-14-1	1"
BSRJT-14-1.5	1.1/2"
BSRJT-14-2	2"
BSRJT-14-2.5	2.1/2"
BSRJT-14-3	3"
BSRJT-14-4	4"
Tech Sheet 68081	



Blanking Nut

0706	Size
BSRJT-13HBN-1	1"
BSRJT-13HBN-1.5	1.1/2"
BSRJT-13HBN-2	2"
BSRJT-13HBN-2.5	2.1/2"
BSRJT-13HBN-3	3"
BSRJT-13HBN-4	4"
Tech Sheet 68081	



EPDM Seal

0706	Size
BSRJT-SEAL-1	1"
BSRJT-SEAL-1.5	1.1/2"
BSRJT-SEAL-2	2"
BSRJT-SEAL-2.5	2.1/2"
BSRJT-SEAL-3	3"
BSRJT-SEAL-4	4"
Tech Sheet 68081	

RJT Fittings

Most process lines have to be frequently dismantled for cleaning and all ranges of our hygienic fittings are suitable for this purpose.

Clamp unions provide a crevice free connection with a rapid break down and assembly, with no tools required.

RJT unions are probably the most widely used for frequent break down and cleaning.

IDF unions provide an alternative security and limit unauthorised access.

Sizes to suit OD tube.



RJT Spanner

0147	Size
RJT-SPANNER-1.0	1"
RJT-SPANNER-1.5	1.1/2"
RJT-SPANNER-2	2"
RJT-SPANNER-2.5	2.1/2"
RJT-SPANNER-3	3"
RJT-SPANNER-4	4"
Tech Sheet 68081	

Hygienic Tube

N.B. Delivery may take up to 48 hours.



3 Metre Lengths

0214	Size
ODT316L-W-H-1.0	1"
ODT316L-W-H-1.5	1.1/2"
ODT316L-W-H-2	2"
ODT316L-W-H-2.5	2.1/2"
ODT316L-W-H-3	3"
ODT316L-W-H-4	4"
Tech Sheet 68081	

HYGIENIC CLAMP FITTINGS

stainless steel

FT PRO

Clamp Fittings



Weld Ferrule

0707	Clamp Size
14MMP-0.5	1/2"
14MMP-0.75	3/4"
14MMP-1	1"
14MMP-1.5	1.1/2"
14MMP-2	2"
14MMP-2.5	2.1/2"
14MMP-3	3"
14MMP-4	4"
Tech Sheet 68084	



Heavy-duty Single Pin Clamp

0707	Clamp Size
13MHH-2.5	2.1/2"
13MHH-0.5	1/2" - 3/4"
13MHH-1	1" - 1.1/2"
13MHH-2	2"
13MHH-3	3"
13MHH-4	4"
Tech Sheet 68084	



Heavy-duty Double Pin Clamp

0707	Clamp Size
13MHHM-1	1" - 1.1/2"
13MHHM-2	2"
13MHHM-2.5	2.1/2"
13MHHM-3	3"
13MHHM-4	4"
Tech Sheet 68084	



End Cap

0707	Clamp Size
16AMP-0.5	1/2" - 3/4"
16AMP-1	1" - 1.1/2"
16AMP-2	2"
16AMP-2.5	2.1/2"
16AMP-3	3"
16AMP-4	4"
Tech Sheet 68084	



Clamp Joint Seal, EPDM

0707	Clamp Size
13PG-0.5	1/2"
13PG-0.75	3/4"
13PG-1	1"
13PG-1.5	1.1/2"
13PG-2	2"
13PG-2.5	2.1/2"
13PG-3	3"
13PG-4	4"
Tech Sheet 68084	

M-Press Fittings Ltd



For **M-Press Stainless Steel Fittings**
see pages **1120-1125**

Fluid-Air Components Ltd

ONE TOUCH ALL STAINLESS STEEL PUSH-IN FITTINGS

stainless steel FTPRO

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 10 bar
Negative Pressure: 750mm Hg (10Torr)

Material:
Body and Collet: 316 stainless steel
O-Ring: Viton

Tube to Connect: PU, Nylon and PTFE
Media: Compressed air, steam water and other compatible liquids

Male Studs



Male Thread, BSPP

0386	OD mm	Thread
SSPC4-01	4	1/8"
SSPC6-01	6	1/8"
SSPC6-02	6	1/4"
SSPC8-01	8	1/8"
SSPC8-02	8	1/4"
SSPC10-02	10	1/4"
SSPC10-03	10	3/8"
SSPC12-04	12	1/2"
Tech Sheet 10257		



Male Thread, BSPP

0386	OD mm	Thread
SSPC4-G01	4	1/8"
SSPC6-G01	6	1/8"
SSPC6-G02	6	1/4"
SSPC8-G01	8	1/8"
SSPC8-G02	8	1/4"
SSPC10-G02	10	1/4"
SSPC10-G03	10	3/8"
SSPC12-G04	12	1/2"
Tech Sheet 10257		

Female Studs



Female Thread, BSPP

0386	OD mm	Thread
SSPCF4-G01	4	1/8"
SSPCF6-G01	6	1/8"
SSPCF6-G02	6	1/4"
SSPCF8-G01	8	1/8"
SSPCF8-G02	8	1/4"
SSPCF10-G02	10	1/4"
SSPCF10-G03	10	3/8"
SSPCF12-G03	12	3/8"
SSPCF12-G04	12	1/2"
Tech Sheet 10257		

Male Stud Swivel Elbows



Male Thread, BSPP

0386	OD mm	Thread
SSPL4-01	4	1/8"
SSPL6-01	6	1/8"
SSPL6-02	6	1/4"
SSPL8-01	8	1/8"
SSPL8-02	8	1/4"
SSPL10-02	10	1/4"
SSPL10-03	10	3/8"
SSPL12-04	12	1/2"
Tech Sheet 10257		



Male Thread, BSPP

0386	OD mm	Thread
SSPL4-G01	4	1/8"
SSPL6-G01	6	1/8"
SSPL6-G02	6	1/4"
SSPL8-G01	8	1/8"
SSPL8-G02	8	1/4"
SSPL10-G02	10	1/4"
SSPL10-G03	10	3/8"
SSPL12-G04	12	1/2"
Tech Sheet 10257		

Female Stud Elbows



Female Thread, BSPP

0386	OD mm	Thread
SSPLF4-G01	4	1/8"
SSPLF6-G01	6	1/8"
SSPLF6-G02	6	1/4"
SSPLF8-G01	8	1/8"
SSPLF8-G02	8	1/4"
SSPLF10-G02	10	1/4"
SSPLF10-G03	10	3/8"
SSPLF12-G03	12	3/8"
SSPLF12-G04	12	1/2"
Tech Sheet 10257		

Male Stud Swivel Tees



Branch Male Thread, BSPP

0386	OD mm	Thread
SSPB4-G01	4	1/8"
SSPB6-G01	6	1/8"
SSPB6-G02	6	1/4"
SSPB8-G01	8	1/8"
SSPB8-G02	8	1/4"
SSPB10-G02	10	1/4"
SSPB10-G03	10	3/8"
SSPB12-G03	12	3/8"
SSPB12-G04	12	1/2"
Tech Sheet 10257		

Speed Control Valves



Male Thread, BSPP

0386	OD mm	Thread
SSNSE4-G01	4	1/8"
SSNSE6-G01	6	1/8"
SSNSE6-G02	6	1/4"
SSNSE8-G01	8	1/8"
SSNSE8-G02	8	1/4"
SSNSE8-G03	8	3/8"
SSNSE10-G02	10	1/4"
SSNSE10-G03	10	3/8"
SSNSE10-G04	10	1/2"
SSNSE12-G04	12	1/2"
Tech Sheet 10257		



All seals have FDA Certification

ONE TOUCH ALL STAINLESS STEEL PUSH-IN FITTINGS

stainless steel

FT PRO

Working Temperature: -20°C to +200°C

Maximum Working Pressure: 10 bar
Negative Pressure: 750mm Hg (10Torr)

Material:
Body and Collet: 316 stainless steel
O-Ring: Viton

Tube to Connect: PU, Nylon and PTFE
Media: Compressed air, steam water and other compatible liquids

Tube x Tube Connectors



Equal Straights

0386	OD mm
SSPUC-4	4
SSPUC-6	6
SSPUC-8	8
SSPUC-10	10
SSPUC-12	12
Tech Sheet 10257	



Unequal Straights

0386	OD mm	OD mm
SSPG6-4	6	4
SSPG8-4	8	4
SSPG8-6	8	6
SSPG10-6	10	6
SSPG10-8	10	8
SSPG12-8	12	8
SSPG12-10	12	10
Tech Sheet 10257		



Equal Elbows

0386	OD mm
SSPUL-4	4
SSPUL-6	6
SSPUL-8	8
SSPUL-10	10
SSPUL-12	12
Tech Sheet 10257	



Equal Tees

0386	OD mm
SSPUT-4	4
SSPUT-6	6
SSPUT-8	8
SSPUT-10	10
SSPUT-12	12
Tech Sheet 10257	



Equal Bulkheads

0386	OD mm
SSPM-4	4
SSPM-6	6
SSPM-8	8
SSPM-10	10
SSPM-12	12
Tech Sheet 10257	



Equal Ys

0386	OD mm
SSPY-4	4
SSPY-6	6
SSPY-8	8
SSPY-10	10
SSPY-12	12
Tech Sheet 10257	

Stem Connectors



Tube x Stem Reducers

0386	OD mm	OD mm
SSPGJ6-4	6	4
SSPGJ8-4	8	4
SSPGJ8-6	8	6
SSPGJ10-6	10	6
SSPGJ10-8	10	8
SSPGJ12-8	12	8
SSPGJ12-10	12	10
Tech Sheet 10257		

Plugs



Tube

0386	OD mm
SSPP-4	4
SSPP-6	6
SSPP-8	8
SSPP-10	10
SSPP-12	12
Tech Sheet 10257	

All seals have FDA Certification

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

316 STAINLESS STEEL PUSH-IN FITTINGS

stainless steel

AIGNEP

Working Temperature: -15°C to +190°C

Maximum Working Pressure: -0.99 bar to 20 bar

This series is fully made of stainless steel AISI 316L and developed to be used with aggressive fluids and food applications
Also ideal for use in salty environments and in machines that need frequent washing with aggressive detergents.
Certified NSF 169 and conformed to NSF 61 & NSF 372 standards. All parallel threads have a Food FKM seal as standard

Male Studs



Male Thread, BSPT

0006	OD mm	Thread
60000-4-1/8	4	1/8"
60000-4-1/4	4	1/4"
60000-6-1/8	6	1/8"
60000-6-1/4	6	1/4"
60000-8-1/8	8	1/8"
60000-8-1/4	8	1/4"
60000-10-1/4	10	1/4"
60000-10-3/8	10	3/8"
60000-12-3/8	12	3/8"
60000-12-1/2	12	1/2"
Tech Sheet 1378		



Male Thread, Metric & BSPP

0006	OD mm	Thread
60020-4-M5	4	M5
60020-4-1/8	4	1/8"
60020-4-1/4	4	1/4"
60020-6-M5	6	M5
60020-6-1/8	6	1/8"
60020-6-1/4	6	1/4"
60020-8-1/8	8	1/8"
60020-8-1/4	8	1/4"
60020-10-1/4	10	1/4"
60020-10-3/8	10	3/8"
60020-10-1/2	10	1/2"
60020-12-3/8	12	3/8"
60020-12-1/2	12	1/2"
60020-14-1/2	14	1/2"
Tech Sheet 1378		

Male Stud Swivel Elbows



Male Thread, BSPT

0006	OD mm	Thread
60110X-4-18	4	1/8"
60110X-4-14	4	1/4"
60110X-6-18	6	1/8"
60110X-6-14	6	1/4"
60110X-8-18	8	1/8"
60110X-8-14	8	1/4"
60110X-10-14	10	1/4"
60110X-10-38	10	3/8"
60110X-10-12	10	1/2"
60110X-12-38	12	3/8"
60110X-12-12	12	1/2"
Tech Sheet 1378		



Male Thread, Metric & BSPP

0006	OD mm	Thread
60115X-4-M5	4	M5
60115X-4-18	4	1/8"
60115X-4-14	4	1/4"
60115X-6-M5	6	M5
60115X-6-18	6	1/8"
60115X-6-14	6	1/4"
60115X-6-38	6	3/8"
60115X-8-18	8	1/8"
60115X-8-14	8	1/4"
60115X-8-38	8	3/8"
60115X-10-14	10	1/4"
60115X-10-38	10	3/8"
60115X-10-12	10	1/2"
60115X-12-38	12	3/8"
60115X-12-12	12	1/2"
60115X-14-12	14	1/2"
Tech Sheet 1378		

Male Stud Swivel Tees



Branch Male Thread, BSPT

0006	OD mm	Thread
60210X-4-18	4	1/8"
60210X-4-14	4	1/4"
60210X-6-18	6	1/8"
60210X-6-14	6	1/4"
60210X-8-18	8	1/8"
60210X-8-14	8	1/4"
60210X-10-14	10	1/4"
60210X-10-38	10	3/8"
60210X-10-12	10	1/2"
60210X-12-38	12	3/8"
60210X-12-12	12	1/2"
Tech Sheet 1378		



Branch Male Thread, BSPP

0006	OD mm	Thread
60215X-4-M5	4	M5
60215X-4-18	4	1/8"
60215X-4-14	4	1/4"
60215X-6-M5	6	M5
60215X-6-18	6	1/8"
60215X-6-14	6	1/4"
60215X-8-18	8	1/8"
60215X-8-14	8	1/4"
60215X-10-14	10	1/4"
60215X-10-38	10	3/8"
60215X-10-12	10	1/2"
60215X-12-38	12	3/8"
60215X-12-12	12	1/2"
60215X-14-12	14	1/2"
Tech Sheet 1378		

316 STAINLESS STEEL PUSH-IN FITTINGS

stainless steel

AIGNEP

Working Temperature: -15°C to +190°C

Maximum Working Pressure: -0.99 bar to 20 bar

This series is fully made of stainless steel AISI 316L and developed to be used with aggressive fluids and food applications. Also ideal for use in salty environments and in machines that need frequent washing with aggressive detergents. Certified NSF 169 and conformed to NSF 61 & NSF 372 standards. All parallel threads have a Food FKM seal as standard.

Tube x Tube Connectors



Equal Straights

0006	OD mm
60040-4	4
60040-6	6
60040-8	8
60040-10	10
60040-12	12
60040-14	14
Tech Sheet 1378	



Unequal Straights

0006	OD mm	OD mm
60040-4-6	4	6
60040-6-8	6	8
60040-8-10	8	10
60040-10-12	10	12
Tech Sheet 1378		



Equal Bulkheads

0006	OD mm	Thread
60050-4	4	M12 x 1
60050-6	6	M14 x 1
60050-8	8	M16 x 1
60050-10	10	M20 x 1
60050-12	12	M22 x 1
Tech Sheet 1378		



Equal Ys

0006	OD mm
60310X-4	4
60310X-6	6
60310X-8	8
Tech Sheet 1378	



Equal Elbows

0006	OD mm
60130X-4	4
60130X-6	6
60130X-8	8
60130X-10	10
60130X-12	12
60130X-14	14
Tech Sheet 1378	



Equal Tees

0006	OD mm
60230X-4	4
60230X-6	6
60230X-8	8
60230X-10	10
60230X-12	12
60230X-14	14
Tech Sheet 1378	

Stem Adaptors



Male Thread, BSPP

0006	OD mm	Thread
60600-6-18	6	1/8"
60600-8-14	8	1/4"
60600-10-14	10	1/4"
60600-10-38	10	3/8"
60600-12-38	12	3/8"
60600-12-12	12	1/2"
Tech Sheet 1378		

Fluid-Air Components Ltd

SERIES 25 QUICK COUPLING EUROPEAN PROFILE STAINLESS STEEL

stainless steel

Working Temperature:
-15°C to +200°C
Standard seal FKM

Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Single Shut Off

Interchangeability:
Rectus 26

Material:
Stainless steel coupling and plug

Application:
General purpose pneumatic coupling, stainless steel.



Profil

Couplings



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KAAW13RVX	1/4"	19	59
25KAAW17RVX	3/8"	19	57.5
Tech Sheet 518			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25KAIW13RVX	1/4"	19	56
25KAIW17RVX	3/8"	19	55
25KAIW21RVX	1/2"	24	56
Tech Sheet 518			



Hose Tail

2510	To Suit Hose ID	Hex Size mm	Length mm
25KATF10RVX	10mm (3/8")	19	74
25KATF13RVX	13mm (1/2")	19	74
Tech Sheet 518			

Plugs



Male Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SFAW13RXX	1/4"	17	33.5
25SFAW17RXX	3/8"	19	33
25SFAW21RXX	1/2"	24	38
Tech Sheet 518			



Female Thread, BSPP

2510	Thread	Hex Size mm	Length mm
25SFIW13RXX	1/4"	17	38.5
25SFIW17RXX	3/8"	19	39.5
25SFIW21RXX	1/2"	24	44
Tech Sheet 518			



Hose Tail

2510	To Suit Hose ID	Length mm
25SFTF06RXX	6mm (1/4")	48
25SFTF08RXX	8mm (5/16")	48
25SFTF10RXX	10mm (3/8")	48
25SFTF13RXX	13mm (1/2")	48
Tech Sheet 518		

Other materials, seals and finishes available on request, please contact our technical department for further details

SOLENOID VALVES

stainless steel

Stainless Steel 2/2 N/C, Direct Operated/ Pilot Operated Solenoid Valves

Materials in contact with fluids
Body: Stainless steel AISI 316
Sealing: FPM
Internal Components: Stainless steel
Seat: Stainless steel AISI 316
Core Tube: Stainless steel
Shading Coil: Copper

Supplied with DIN plugs



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M3/ HR	Max Pressure Bar	Replacement Coil
G256C145S-23050	1/8"	230/50	4.5 VA	1.6	0.08	0-30	533534-003
G256C145S-11050	1/8"	110/50	4.5 VA	1.6	0.08	0-30	533534-024
G256C145S-2450	1/8"	24/50	4.5 VA	1.6	0.08	0-30	533534-011
G256C145S-24VDC	1/8"	24V DC	3.5 W	1.6	0.08	0-12	533534-001
G256C129S-23050	1/4"	230/50	14 VA	2.4	0.18	0-20	533593-003
G256C129S-11050	1/4"	110/50	14 VA	2.4	0.18	0-20	533593-020
G256C129S-2450	1/4"	24/50	14 VA	2.4	0.18	0-20	533593-011
G256C113S-24VDC	1/4"	24V DC	9 W	2.4	0.18	0-20	533593-002
L182V09-38-23050	3/8"	230/50	12VA	13.5	2.5	0.35 - 16	B12AA
L182V09-38-11050	3/8"	110/50	12VA	13.5	2.5	0.35 - 16	B12AC
L182V09-38-2450	3/8"	24/50	12VA	13.5	2.5	0.35 - 16	B12AE
L182V09-38-24	3/8"	24V DC	5.5W	13.5	2.5	0.35 - 16	B12AL
L182V09-12-23050	1/2"	230/50	12VA	13.5	3.8	0.35 - 16	B12AA
L182V09-12-11050	1/2"	110/50	12VA	13.5	3.8	0.35 - 16	B12AC
L182V09-12-2450	1/2"	24/50	12VA	13.5	3.8	0.35 - 16	B12AE
L182V09-12-24	1/2"	24V DC	5.5W	13.5	3.8	0.35 - 16	B12AL
L182V09-34-23050	3/4"	230/50	12VA	18	5	0.3 - 12	B12AA
L182V09-34-11050	3/4"	110/50	12VA	18	5	0.3 - 12	B12AC
L182V09-34-2450	3/4"	24/50	12VA	18	5	0.3 - 12	B12AE
L182V09-34-24	3/4"	24V DC	5.5W	18	5	0.3 - 12	B12AL
L182V09-1-23050	1"	230/50	12VA	24	12	0.3 - 12	B12AA
L182V09-1-11050	1"	110/50	12VA	24	12	0.3 - 12	B12AC
L182V09-1-2450	1"	24/50	12VA	24	12	0.3 - 12	B12AE
L182V09-1-24	1"	24V DC	5.5W	24	12	0.3 - 12	B12AL
Tech Sheets 2121, 2122 & 2123							

Stainless Steel 2/2 N/O, Pilot Operated Solenoid Valves

Materials in contact with fluids
Body: Stainless steel AISI 316
Sealing: FPM
Internal Components: Stainless steel
Seat: Stainless steel AISI 316
Core Tube: Stainless steel
Shading Coil: Copper

Supplied with DIN plugs



BSPP

0030	Thread	Voltage	Coil Consumption	DN Size	KV M3/ HR	Max Pressure Bar	Replacement Coil
L282V09-38-23050	3/8"	230/50	12VA	13.5	2.5	0.3 - 12	B12AA
L282V09-38-11050	3/8"	110/50	12VA	13.5	2.5	0.3 - 12	B12AC
L282V09-38-2450	3/8"	24/50	12VA	13.5	2.5	0.3 - 12	B12AE
L282V09-38-24	3/8"	24V DC	5.5W	13.5	2.5	0.3 - 12	B12AL
L282V09-12-23050	1/2"	230/50	12VA	13.5	3.8	0.3 - 12	B12AA
L282V09-12-11050	1/2"	110/50	12VA	13.5	3.8	0.3 - 12	B12AC
L282V09-12-2450	1/2"	24/50	12VA	13.5	3.8	0.3 - 12	B12AE
L282V09-12-24	1/2"	24V DC	5.5W	13.5	3.8	0.3 - 12	B12AL
L282V09-34-23050	3/4"	230/50	12VA	18	5	0.3 - 10	B12AA
L282V09-34-11050	3/4"	110/50	12VA	18	5	0.3 - 10	B12AC
L282V09-34-2450	3/4"	24/50	12VA	18	5	0.3 - 10	B12AE
L282V09-34-24	3/4"	24V DC	5.5W	18	5	0.3 - 10	B12AL
L282V09-1-23050	1"	230/50	12VA	24	12	0.3 - 10	B12AA
L282V09-1-11050	1"	110/50	12VA	24	12	0.3 - 10	B12AC
L282V09-1-2450	1"	24/50	12VA	24	12	0.3 - 10	B12AE
L282V09-1-24	1"	24V DC	5.5W	24	12	0.3 - 10	B12AL
Tech Sheet 2154							

Coil reference for G256 series



BSPP

0030	Voltage
533534-003	230/50
533534-024	110/50
533534-011	24/50
533534-001	24V DC
533593-003	230/50
533593-020	110/50
533593-011	24/50
553534-002	24V DC
Tech Sheet 2154	

Fluid-Air Components Ltd

GLYCERINE GAUGES & ACCESSORIES

stainless steel FT PRO

Stainless Steel Case, Bottom Connection



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001BG	1/4"	63	0-15	0-1
G63-002BG	1/4"	63	0-30	0-2
G63-004BG	1/4"	63	0-60	0-4
G63-006BG	1/4"	63	0-100	0-6
G63-012BG	1/4"	63	0-200	0-12
G63-020BG	1/4"	63	0-300	0-20
G63-025BG	1/4"	63	0-400	0-25
G63-040BG	1/4"	63	0-600	0-40
G63-060BG	1/4"	63	0-1000	0-60
G63-120BG	1/4"	63	0-2000	0-120
G63-200BG	1/4"	63	0-3000	0-200
G63-250BG	1/4"	63	0-4000	0-250
G63-400BG	1/4"	63	0-6000	0-400
G63-600BG	1/4"	63	0-9000	0-600
VG63-01BG	1/4"	63	-30" Hg	-1 bar
Tech Sheet 20593				



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001BG	1/4"	63	0-15	0-1
PG63-002BG	1/4"	63	0-30	0-2
PG63-004BG	1/4"	63	0-60	0-4
PG63-006BG	1/4"	63	0-100	0-6
PG63-012BG	1/4"	63	0-200	0-12
PG63-014BG	1/4"	63	0-200	0-14
PG63-020BG	1/4"	63	0-300	0-20
PG63-025BG	1/4"	63	0-400	0-25
PG63-040BG	1/4"	63	0-600	0-40
PG63-060BG	1/4"	63	0-1000	0-60
PG63-120BG	1/4"	63	0-2000	0-120
PG63-200BG	1/4"	63	0-3000	0-200
PG63-250BG	1/4"	63	0-4000	0-250
PG63-400BG	1/4"	63	0-6000	0-400
PG63-600BG	1/4"	63	0-9000	0-600
Tech Sheet 20594				

Stainless Steel Case, Centre Back Connection

See Panel Mount Bracket Options:
G63-PM & G63-PM-RHOMB



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
G63-001RG	1/4"	63	0-15	0-1
G63-002RG	1/4"	63	0-30	0-2
G63-004RG	1/4"	63	0-60	0-4
G63-006RG	1/4"	63	0-100	0-6
G63-010RG	1/4"	63	0-160	0-10
G63-012RG	1/4"	63	0-200	0-12
G63-020RG	1/4"	63	0-300	0-20
G63-025RG	1/4"	63	0-400	0-25
G63-040RG	1/4"	63	0-600	0-40
G63-060RG	1/4"	63	0-1000	0-60
G63-120RG	1/4"	63	0-2000	0-120
G63-200RG	1/4"	63	0-3000	0-200
G63-250RG	1/4"	63	0-4000	0-250
G63-400RG	1/4"	63	0-6000	0-400
G63-600RG	1/4"	63	0-9000	0-600
VG63-01RG	1/4"	63	-30" Hg	-1 bar
Tech Sheet 20595				

See Panel Mount Bracket Options:
G63-PM & G63-PM-RHOMB



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
PG63-001RG	1/4"	63	0-15	0-1
PG63-002RG	1/4"	63	0-30	0-2
PG63-004RG	1/4"	63	0-60	0-4
PG63-006RG	1/4"	63	0-100	0-6
PG63-012RG	1/4"	63	0-200	0-12
PG63-020RG	1/4"	63	0-300	0-20
PG63-025RG	1/4"	63	0-400	0-25
PG63-040RG	1/4"	63	0-600	0-40
PG63-060RG	1/4"	63	0-1000	0-60
PG63-120RG	1/4"	63	0-2000	0-120
PG63-200RG	1/4"	63	0-3000	0-200
PG63-250RG	1/4"	63	0-4000	0-250
PG63-400RG	1/4"	63	0-6000	0-400
PG63-600RG	1/4"	63	0-9000	0-600
Tech Sheet 20596				

Panel Mounting Brackets



For G63 & PG63 Centre Back Connection below 100 bar

0021
G63-PM



For G63 & PG63 Centre Back Connection above 100 bar

0021
G63-PM-RHOMB

GLYCERINE GAUGES

stainless steel

FT PRO

All Stainless Steel Gauges, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SSG63-001BG	1/4"	63	0-15	0-1
SSG63-004BG	1/4"	63	0-60	0-4
SSG63-012BG	1/4"	63	0-200	0-12
SSG63-025BG	1/4"	63	0-400	0-25
SSG63-060BG	1/4"	63	0-1000	0-60
SSG63-200BG	1/4"	63	0-3000	0-200
SSG63-250BG	1/4"	63	0-4000	0-250
SSG63-400BG	1/4"	63	0-6000	0-400
Tech Sheet 20598				



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
SHG100-002BG	1/2"	100	0-30	0-2
SHG100-006BG	1/2"	100	0-100	0-6
SHG100-016BG	1/2"	100	0-250	0-16
SHG100-040BG	1/2"	100	0-600	0-40
SHG100-100BG	1/2"	100	0-1500	0-100
SHG100-250BG	1/2"	100	0-4000	0-250
SHG100-600BG	1/2"	100	0-9000	0-600
Tech Sheet 20599				

All Stainless Steel Gauges, Centre Back Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2020-0340	1/4"	50	0-200	0-12
2020-0341	1/4"	50	0-300	0-20
2020-0342	1/4"	50	0-600	0-40
2020-0343	1/4"	50	0-900	0-60
2020-0344	1/4"	50	0-4000	0-250
2038-8534	1/4"	63	0-200	0-12
2038-8567	1/4"	63	0-900	0-60
2038-8575	1/4"	63	0-4000	0-250
Tech Sheet 20600				



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
2038-8435	1/2"	100	0-200	0-12
2038-8443	1/2"	100	0-300	0-20
2038-8450	1/2"	100	0-600	0-40
2038-8476	1/2"	100	0-4000	0-250
Tech Sheet 20601				

Stainless Steel Case, Heavy-duty, Bottom Connection



BSPP

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002G	1/2"	100	0-36	0-2.5
HG100-004G	1/2"	100	0-58	0-4
HG100-006G	1/2"	100	0-87	0-6
HG100-010G	1/2"	100	0-145	0-10
HG100-016G	1/2"	100	0-232	0-16
HG100-040G	1/2"	100	0-580	0-40
HG100-100G	1/2"	100	0-1450	0-100
HG100-160G	1/2"	100	0-2320	0-160
HG100-250G	1/2"	100	0-3625	0-250
HG100-400G	1/2"	100	0-5800	0-400



BSPT

0021	Thread	Gauge Diameter mm	Pressure Range PSI	Pressure Range Bar
HG100-002B	1/2"	100	0-36	0-2.5
HG100-004B	1/2"	100	0-58	0-4
HG100-006B	1/2"	100	0-87	0-6
HG100-010B	1/2"	100	0-145	0-10
HG100-016B	1/2"	100	0-232	0-16
HG100-040B	1/2"	100	0-580	0-40
HG100-100B	1/2"	100	0-1450	0-100
HG100-160B	1/2"	100	0-2320	0-160
HG100-250B	1/2"	100	0-3625	0-250
HG100-400B	1/2"	100	0-5800	0-400
Tech Sheet 20597				

Vacuum Gauges, Centre Back Connection



Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GCV63/04	1/4" BSPP	63	-1
GCV100/06	3/8" BSPP	100	-1

Vacuum Gauges, Bottom Connection



Stainless Steel

0236	Thread	Gauge Diameter mm	Max Pressure Bar
GBV63/04	1/4" BSPP	63	-1
GBV100/06	3/8" BSPP	100	-1

Fluid-Air Components Ltd

TEST POINT COUPLINGS

stainless steel

spradow
german engineering at your service

Piston Valve Type, M16 x 2

Media Application:
Hydraulic and other oils on mineral oil basis.
Metal Cap -30°C to +100°C Sealings Buna N
Metal Cap -20°C to +200°C Sealings Viton

stainless steel



316 Stainless Steel, BSPP

0330	OD mm	Max Pressure Bar
1-912-28-12-660	1/8"	400
1-912-29-12-660	1/4"	630
Tech Sheet 10292		

Gauge Adaptors

stainless steel



316 Stainless Steel, BSPP

0330	Thread	Max Pressure Bar
1-940-31-22-080	1/2"	630
Tech Sheet 10292		

316 Stainless Steel Test Points

Sealing by an elastomer captive profiled ring - Viton
Test connection: M16 x 2

Maximum Working Pressure: 630 bar

stainless steel



Form C, BSPP

0330	Thread
MAS-G1/8-WD	1/8"
MAS-G1/4-WD	1/4"
MAS-G3/8-WD	3/8"
MAS-G1/2-WD	1/2"

SILENCERS

stainless steel

FT PRO

Stainless Steel Silencers



BSPP

0423	Thread
S70-18	1/8"
S70-14	1/4"
S70-38	3/8"
S70-12	1/2"
S70-34	3/4"
S70-1	1"

Stainless Steel Pad Silencers



Body: 304 stainless steel
Pad: 316 stainless steel

Metric & BSPP

0423	Thread
12020507	M5
12021007	1/8"
12021307	1/4"
12021707	3/8"
12022107	1/2"
12022707	3/4"
12023207	1"
Tech Sheet 20455	

FLOAT LEVEL SWITCHES

stainless steel

Stainless Steel Normally Closed IP65

Working Temperature: -10°C to +80°C
Maximum Working Pressure: 10 bar

- Fluid specific gravitiy:° 0.7
- Maximum fluid viscosity 150 cSt
- Cable length: 500mm



ELETTROTEC

Side Entry, BSPP Male

9025	Thread
LEM7A	1/8"

Working Temperature: -10°C to +80°C
Maximum Working Pressure: 10 bar

- Fluid specific gravitiy:° 0.7
- Maximum fluid viscosity 150 cSt
- Cable length: 500mm



ELETTROTEC

Top Entry, BSPT Male

9025	Thread
LEM7NC	1/8"

Stainless Steel Normally Closed IP65

- Normally open/normally closed contacts.
- Specific Gravity > 0.8
- PG09 DIN 43650 connection

PVL
Engineers Supplying Engineers



Side Entry, BSPT Male

9025	Thread
RFS-12P-2-SUS304	1/2"
Tech Sheet 111	

KR 500

High Pressure Hydraulic Adaptors

Over 25 years of proven high performance with a comprehensive history of product approvals and 3rd party accreditations.

- Superior quality range of Hydraulic Adaptors
- High grade materials manufactured to extremely high tolerance
- 1/8"-3/4" up to 680 bar
- 1"-2" up to 500 bar

High quality Hydraulic Adaptors for high pressure applications completing the integrity of any hose assembly.



1332

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 11

Malleable Iron

11.01 Malleable Iron Fittings 1333-1376

11.02 Barrel Nipples, Tube & Accessories 1377-1391

11.03 Forged & Butt Weld Fittings 1392

11.04 Handrail System 1393-1398

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 11 Malleable Iron


11.01 Malleable Iron Fittings — 1333-1376

- Malleable Iron Fittings



11.02 Barrel Nipples, Tube & Accessories — 1377-1391

- Malleable Iron Fittings
- EN10255, EN10217-1 & BS1387 Steel Tube
- Flange Bolt Kits
- Malleable Iron Accessories
- Forged Steel Flanges
- Carbon Steel Flanges
- Flexible Rubber Bellows
- Flange Gaskets
- None Asbestos Flange Gaskets
- Jointing Compounds & Sealants



11.03 Forged & Butt Weld Fittings — 1392

- Butt Weld Fittings BS1640/ASTM A234WPB




11.04 Handrail System — 1393-1398

- Pipeclamps Handrail Systems
- The Swivel Range
- Disability Access



Fluid-Air Components Ltd

FT PRO For the Engineers



FT Pro products are designed using advanced engineering techniques and the latest manufacturing technology to ensure that your applications benefit from the highest level of quality and performance.

Our products are engineered to be reliable and long-lasting, ensuring that your equipment operates smoothly and reliably throughout its lifespan. With FT Pro products, you can be confident that your applications will run efficiently and productive, no matter how demanding the conditions.

Trust FT Pro Product for the engineers from the engineers.

1335

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c



MASTERS OF MALLEABLE IRON

Malleable iron fittings are the most commonly used pipe fittings in the world, renowned for its durability and mechanical strength.

The fittings are used in a variety of systems including compressed air, water supply, central heating, sprinkler systems and air conditioning, as well as gas and steam systems. They are also used to convey non-aggressive liquids and gases.

Malleable iron fittings provide ring main solutions across various industries including construction, agriculture, mining, automotive and industrial.

All fittings are specially coated to provide an anti-corrosive property as standard.

EE ODLEWNIA

Pages 1338-1348



+GF+

Pages 1356-1369



K-LINE CONNECT

Pages 1349-1355



CRANE

Pages 1370-1376



Available in a black finish (usually for oil and gas fluid applications) and a galvanised finish (usually for water, air and steam installations).

All galvanised fittings are hot-dip zinc coated prior to machining to provide an electrochemical protection and increases resistance to corrosion.

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

The most extensive choice of MALLEABLE IRON to suit any application & any budget

The choice of fittings is very much dependent on the application, the engineer's preference and budget. With a choice of five brands, large stocks and speedy delivery, there's no need to look any further.


Brand	Duty	Fitting Variations*	Beaded	Banded	Thread	BSI Kitemarked®	Up to 4"	Up to 5"	Up to 6"	WRAS approved	Max Temp	Max Working Pressure	Casting: ISO5922	Threads: ISO 7-1	Manufactured: according to EN 10142 and ISO 49	Design: ISO49, BS EN 10242w	Testing: BS 143 & 1256	Materials: ASTM A-197, ASTM A47
K-Line Connect	Heavy	19		Y	Male Taper, Female Taper	Y	Y			Y	300**	25**	Y	Y	Y	Y	Y	Y
Crane	Heavy	36		Y	Male Taper, Female Taper	Y	Y			Y	300**	25**	Y	Y	Y	Y	Y	Y
EE	Heavy	26	Y		Male Taper, Female Parallel		Y				300**	25**	Y	Y	Y	Y		
GF	Heavy	42	Y		Male Taper, Female Parallel		Y	Y	Y		300**	25**	Y	Y	Y	Y	Y	

For full technical specification, please contact the manufacturer.

* Excludes brackets, nuts, flanges, plates and rings.
** Maximum temperature +120°C at maximum working pressure of 20 bar.

Banded Range

- BSPT Male, BSPT Female – EN10226-2
- British Kitemark
- Available in black or galvanised finish
- Choice of two heavy-duty brands: Crane or K-Line Connect



Tapered Pipe Thread to EN10226-2 Standard


• 55° thread angle • Taper angle 1° 47'

Medium & Heavy-duty Barrel Nipples from FT Pro

- From 1/8" to 4" thread
- Lengths up to 300mm

Beaded Range

- Male Taper, Female Parallel – EN10226-1
- Available in black or galvanised finish
- Choice of two heavy-duty brands: GF and EE
- Heavy-duty ranges manufactured in accordance with EN 10142



Parallel Pipe Thread to EN10226-1 Standard

• 55° thread angle


BS EN 10241 from K-Line Connect

- From 1/8" to 4" thread
- Lengths up to 300mm

1337

MALLEABLE IRON FITTINGS

Maximum Working Pressure:
25 bar @ -20°C to +120°C
20 bar @ +300°C



Threads: Threads are in accordance to IS07-1. All male threads are BSPT and female threads are BSPP.

Materials: Whiteheart malleable EN-GJMW-400-5 cast iron, grade W40-05 according to ISO5922/DIN-1692, and tested in accordance to EN 10242

Media: Suitable for the flow of wate , steam, gas or other non aggressive media.

Surface Finishing:

Black: With an anti-corrosive varnish to protect against rust after installation prior to plant conditioning.

Galvanised: According to EN 10242, zinc coating weight relative to surface exceeds 500 g/m² (average layer thickness 70 micron).

Male Equal Hexagon Nipple (280)



Black, BSPT

1095	Thread
EE-MI280-14N	1/4"
EE-MI280-38N	3/8"
EE-MI280-12N	1/2"
EE-MI280-34N	3/4"
EE-MI280-1N	1"
EE-MI280-114N	1.1/4"
EE-MI280-112N	1.1/2"
EE-MI280-2N	2"
EE-MI280-212N	2.1/2"
EE-MI280-3N	3"
EE-MI280-4N	4"
Tech Sheet 20535	

Galvanised, BSPT

1095	Thread
EE-MI280-14	1/4"
EE-MI280-38	3/8"
EE-MI280-12	1/2"
EE-MI280-34	3/4"
EE-MI280-1	1"
EE-MI280-114	1.1/4"
EE-MI280-112	1.1/2"
EE-MI280-2	2"
EE-MI280-212	2.1/2"
EE-MI280-3	3"
EE-MI280-4	4"
Tech Sheet 20535	

Male Reducing Hexagon Nipple (245)



Black, BSPT

1095	Thread	Thread
EE-MI245-38-14N	3/8"	1/4"
EE-MI245-12-14N	1/2"	1/4"
EE-MI245-12-38N	1/2"	3/8"
EE-MI245-34-38N	3/4"	3/8"
EE-MI245-34-12N	3/4"	1/2"
EE-MI245-1-12N	1"	1/2"
EE-MI245-1-34N	1"	3/4"
EE-MI245-114-12N	1.1/4"	1/2"
EE-MI245-114-34N	1.1/4"	3/4"
EE-MI245-114-1N	1.1/4"	1"
EE-MI245-112-12N	1.1/2"	1/2"
EE-MI245-112-34N	1.1/2"	3/4"
EE-MI245-112-1N	1.1/2"	1"
EE-MI245-112114N	1.1/2"	1.1/4"
EE-MI245-2-1N	2"	1"
EE-MI245-2-114N	2"	1.1/4"
EE-MI245-2-112N	2"	1.1/2"
EE-MI245-212114N	2.1/2"	1.1/4"
EE-MI245-212112N	2.1/2"	1.1/2"
EE-MI245-212-2N	2.1/2"	2"
EE-MI245-3-2N	3"	2"
EE-MI245-3-212N	3"	2.1/2"
Tech Sheet 20535		

Galvanised, BSPT

1095	Thread	Thread
EE-MI245-14-18	1/4"	1/8"
EE-MI245-38-14	3/8"	1/4"
EE-MI245-12-14	1/2"	1/4"
EE-MI245-12-38	1/2"	3/8"
EE-MI245-34-38	3/4"	3/8"
EE-MI245-34-12	3/4"	1/2"
EE-MI245-1-12	1"	1/2"
EE-MI245-1-34	1"	3/4"
EE-MI245-114-12	1.1/4"	1/2"
EE-MI245-114-34	1.1/4"	3/4"
EE-MI245-114-1	1.1/4"	1"
EE-MI245-112-34	1.1/2"	3/4"
EE-MI245-112-1	1.1/2"	1"
EE-MI245-112-114	1.1/2"	1.1/4"
EE-MI245-2-1	2"	1"
EE-MI245-2-114	2"	1.1/4"
EE-MI245-2-112	2"	1.1/2"
EE-MI245-212-112	2.1/2"	1.1/2"
EE-MI245-212-2	2.1/2"	2"
EE-MI245-3-2	3"	2"
EE-MI245-3-212	3"	2.1/2"
Tech Sheet 20535		

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Male x Female Equal Union, Taper Seat (341)



Black, BSPP Female x BSPT Male

1095	Thread
EE-MI341-38N	3/8"
EE-MI341-12N	1/2"
EE-MI341-34N	3/4"
EE-MI341-1N	1"
EE-MI341-114N	1.1/4"
EE-MI341-112N	1.1/2"
EE-MI341-2N	2"
EE-MI341-212N	2.1/2"
EE-MI341-3N	3"
Tech Sheet 20539	

Galvanised, BSPP Female x BSPT Male

1095	Thread
EE-MI341-38	3/8"
EE-MI341-12	1/2"
EE-MI341-34	3/4"
EE-MI341-1	1"
EE-MI341-114	1.1/4"
EE-MI341-112	1.1/2"
EE-MI341-2	2"
EE-MI341-212	2.1/2"
EE-MI341-3	3"
EE-MI341-4	4"
Tech Sheet 20539	

Male x Female Reducing Bush (241)



Black, BSPP Female x BSPT Male

1095	Male Thread	Female Thread
EE-MI241-38-14N	3/8"	1/4"
EE-MI241-12-14N	1/2"	1/4"
EE-MI241-12-38N	1/2"	3/8"
EE-MI241-34-14N	3/4"	1/4"
EE-MI241-34-38N	3/4"	3/8"
EE-MI241-34-12N	3/4"	1/2"
EE-MI241-1-38N	1"	3/8"
EE-MI241-1-12N	1"	1/2"
EE-MI241-1-34N	1"	3/4"
EE-MI241-114-12N	1.1/4"	1/2"
EE-MI241-114-34N	1.1/4"	3/4"
EE-MI241-114-1N	1.1/4"	1"
EE-MI241-112-12N	1.1/2"	1/2"
EE-MI241-112-34N	1.1/2"	3/4"
EE-MI241-112-1N	1.1/2"	1"
EE-MI241-112114N	1.1/2"	1.1/4"
EE-MI241-2-12N	2"	1/2"
EE-MI241-2-34N	2"	3/4"
EE-MI241-2-1N	2"	1"
EE-MI241-2-114N	2"	1.1/4"
EE-MI241-2-112N	2"	1.1/2"
EE-MI241-212-1N	2.1/2"	1"
EE-MI241-212112N	2.1/2"	1.1/2"
EE-MI241-212-2N	2.1/2"	2"
EE-MI241-3-114N	3"	1.1/4"
EE-MI241-3-112N	3"	1.1/2"
EE-MI241-3-2N	3"	2"
EE-MI241-3-212N	3"	2.1/2"
EE-MI241-4-2N	4"	2"
Tech Sheet 20534		

Galvanised, BSPP Female x BSPT Male

1095	Male Thread	Female Thread
EE-MI241-38-14	3/8"	1/4"
EE-MI241-12-14	1/2"	1/4"
EE-MI241-12-38	1/2"	3/8"
EE-MI241-34-14	3/4"	1/4"
EE-MI241-34-38	3/4"	3/8"
EE-MI241-34-12	3/4"	1/2"
EE-MI241-1-38	1"	3/8"
EE-MI241-1-12	1"	1/2"
EE-MI241-1-34	1"	3/4"
EE-MI241-114-38	1.1/4"	3/8"
EE-MI241-114-12	1.1/4"	1/2"
EE-MI241-114-34	1.1/4"	3/4"
EE-MI241-114-1	1.1/4"	1"
EE-MI241-112-12	1.1/2"	1/2"
EE-MI241-112-34	1.1/2"	3/4"
EE-MI241-112-1	1.1/2"	1"
EE-MI241-112-114	1.1/2"	1.1/4"
EE-MI241-2-12	2"	1/2"
EE-MI241-2-34	2"	3/4"
EE-MI241-2-1	2"	1"
EE-MI241-2-114	2"	1.1/4"
EE-MI241-2-112	2"	1.1/2"
EE-MI241-212-1	2.1/2"	1"
EE-MI241-212-114	2.1/2"	1.1/4"
EE-MI241-212-112	2.1/2"	1.1/2"
EE-MI241-212-2	2.1/2"	2"
EE-MI241-3-1	3"	1"
EE-MI241-3-112	3"	1.1/2"
EE-MI241-3-2	3"	2"
EE-MI241-3-212	3"	2.1/2"
EE-MI241-4-2	4"	2"
EE-MI241-4-212	4"	2.1/2"
EE-MI241-4-3	4"	3"
Tech Sheet 20534		

Male x Female Reducing Socket (246)



Black, BSPP Female x BSPT Male

1095	Female Thread	Male Thread
EE-MI246-38-14N	3/8"	1/4"
EE-MI246-12-14N	1/2"	1/4"
EE-MI246-12-38N	1/2"	3/8"
EE-MI246-34-38N	3/4"	3/8"
EE-MI246-34-12N	3/4"	1/2"
EE-MI246-1-12N	1"	1/2"
EE-MI246-1-34N	1"	3/4"
EE-MI246-114-34N	1.1/4"	3/4"
EE-MI246-114-1N	1.1/4"	1"
EE-MI246-112-1N	1.1/2	1"
EE-MI246-112114N	1.1/2"	1.1/4"
EE-MI246-2-114N	2"	1.1/4"
EE-MI246-2-112N	2"	1.1/2"
Tech Sheet 20536		

Galvanised, BSPP Female x BSPT Male

1095	Female Thread	Male Thread
EE-MI246-38-14	3/8"	1/4"
EE-MI246-12-14	1/2"	1/4"
EE-MI246-12-38	1/2"	3/8"
EE-MI246-34-38	3/4"	3/8"
EE-MI246-34-12	3/4"	1/2"
EE-MI246-1-12	1"	1/2"
EE-MI246-1-34	1"	3/4"
EE-MI246-114-34	1.1/4"	3/4"
EE-MI246-114-1	1.1/4"	1"
EE-MI246-112-1	1.1/2"	1"
EE-MI246-112-114	1.1/2"	1.1/4"
EE-MI246-2-114	2"	1.1/4"
EE-MI246-2-112	2"	1.1/2"
Tech Sheet 20536		

Male x Female Socket (529A)



Galvanised, BSPT Male x BSPP Female

1095	Thread
EE-MI529A-12	1/2"
EE-MI529A-34	3/4"
EE-MI529A-1	1"

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Equal Socket (270)



Black, BSPP

1095	Thread
EE-MI270-14N	1/4"
EE-MI270-38N	3/8"
EE-MI270-12N	1/2"
EE-MI270-34N	3/4"
EE-MI270-1N	1"
EE-MI270-114N	1.1/4"
EE-MI270-112N	1.1/2"
EE-MI270-2N	2"
EE-MI270-212N	2.1/2"
EE-MI270-3N	3"
EE-MI270-4N	4"

Tech Sheet 20537

Galvanised, BSPP

1095	Thread
EE-MI270-14	1/4"
EE-MI270-38	3/8"
EE-MI270-12	1/2"
EE-MI270-34	3/4"
EE-MI270-1	1"
EE-MI270-114	1.1/4"
EE-MI270-112	1.1/2"
EE-MI270-2	2"
EE-MI270-212	2.1/2"
EE-MI270-3	3"
EE-MI270-4	4"

Tech Sheet 20537

Female Reducing Socket (240)



Black, BSPP

1095	Thread	Thread
EE-MI240-38-14N	3/8"	1/4"
EE-MI240-12-14N	1/2"	1/4"
EE-MI240-12-38N	1/2"	3/8"
EE-MI240-34-38N	3/4"	3/8"
EE-MI240-34-12N	3/4"	1/2"
EE-MI240-1-38N	1"	3/8"
EE-MI240-1-12N	1"	1/2"
EE-MI240-1-34N	1"	3/4"
EE-MI240-114-38N	1.1/4"	3/8"
EE-MI240-114-12N	1.1/4"	1/2"
EE-MI240-114-34N	1.1/4"	3/4"
EE-MI240-114-1N	1.1/4"	1"
EE-MI240-112-12N	1.1/2"	1/2"
EE-MI240-112-34N	1.1/2"	3/4"
EE-MI240-112-1N	1.1/2"	1"
EE-MI240-112114N	1.1/2"	1.1/4"
EE-MI240-2-12N	2"	1/2"
EE-MI240-2-34N	2"	3/4"
EE-MI240-2-1N	2"	1"
EE-MI240-2-114N	2"	1.1/4"
EE-MI240-2-112N	2"	1.1/2"
EE-MI240-212114N	2.1/2"	1.1/4"
EE-MI240-212112N	2.1/2"	1.1/2"
EE-MI240-212-2N	2.1/2"	2"
EE-MI240-3-112N	3"	1.1/2"
EE-MI240-3-2N	3"	2"
EE-MI240-3-212N	3"	2.1/2"

Tech Sheet 20533

Galvanised, BSPP

1095	Thread	Thread
EE-MI240-38-14	3/8"	1/4"
EE-MI240-12-14	1/2"	1/4"
EE-MI240-12-38	1/2"	3/8"
EE-MI240-34-38	3/4"	3/8"
EE-MI240-34-12	3/4"	1/2"
EE-MI240-1-38	1"	3/8"
EE-MI240-1-12	1"	1/2"
EE-MI240-1-34	1"	3/4"
EE-MI240-114-38	1.1/4"	3/8"
EE-MI240-114-12	1.1/4"	1/2"
EE-MI240-114-34	1.1/4"	3/4"
EE-MI240-114-1	1.1/4"	1"
EE-MI240-112-12	1.1/2"	1/2"
EE-MI240-112-34	1.1/2"	3/4"
EE-MI240-112-1	1.1/2"	1"
EE-MI240-112-114	1.1/2"	1.1/4"
EE-MI240-2-12	2"	1/2"
EE-MI240-2-34	2"	3/4"
EE-MI240-2-1	2"	1"
EE-MI240-2-114	2"	1.1/4"
EE-MI240-2-112	2"	1.1/2"
EE-MI240-212-1	2.1/2"	1"
EE-MI240-212-2	2.1/2"	2"
EE-MI240-3-2	3"	2"
EE-MI240-3-212	3"	2.1/2"
EE-MI240-4-2	4"	2"
EE-MI240-4-3	4"	3"

Tech Sheet 20533

FT PRO



For **Screwed & Socketed Steel Tubing**
see page **1383**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Equal Union, Taper Seat (340)



Black, BSPP

1095	Thread
EE-MI340-38N	3/8"
EE-MI340-12N	1/2"
EE-MI340-34N	3/4"
EE-MI340-1N	1"
EE-MI340-114N	1.1/4"
EE-MI340-112N	1.1/2"
EE-MI340-2N	2"
EE-MI340-212N	2.1/2"
EE-MI340-3N	3"
Tech Sheet 20538	

Galvanised, BSPP

1095	Thread
EE-MI340-38	3/8"
EE-MI340-12	1/2"
EE-MI340-34	3/4"
EE-MI340-1	1"
EE-MI340-114	1.1/4"
EE-MI340-112	1.1/2"
EE-MI340-2	2"
EE-MI340-212	2.1/2"
EE-MI340-3	3"
EE-MI340-4	4"
Tech Sheet 20538	

Plug, Hollow Beaded (290)



Black, BSPT

1095	Thread
EE-MI290-14N	1/4"
EE-MI290-38N	3/8"
EE-MI290-12N	1/2"
EE-MI290-34N	3/4"
EE-MI290-1N	1"
EE-MI290-114N	1.1/4"
EE-MI290-112N	1.1/2"
EE-MI290-2N	2"
EE-MI290-212N	2.1/2"
EE-MI290-3N	3"
EE-MI290-4N	4"
Tech Sheet 20538	

Galvanised, BSPT

1095	Thread
EE-MI290-14	1/4"
EE-MI290-38	3/8"
EE-MI290-12	1/2"
EE-MI290-34	3/4"
EE-MI290-1	1"
EE-MI290-114	1.1/4"
EE-MI290-112	1.1/2"
EE-MI290-2	2"
EE-MI290-212	2.1/2"
EE-MI290-3	3"
EE-MI290-4	4"
Tech Sheet 20538	

Cap, Hexagonal (300)



Black, BSPP

1095	Thread
EE-MI300-14N	1/4"
EE-MI300-38N	3/8"
EE-MI300-12N	1/2"
EE-MI300-34N	3/4"
EE-MI300-1N	1"
EE-MI300-114N	1.1/4"
EE-MI300-112N	1.1/2"
EE-MI300-2N	2"
EE-MI300-212N	2.1/2"
EE-MI300-3N	3"
EE-MI300-4N	4"
Tech Sheet 20538	

Galvanised, BSPP

1095	Thread
EE-MI300-14	1/4"
EE-MI300-38	3/8"
EE-MI300-12	1/2"
EE-MI300-34	3/4"
EE-MI300-1	1"
EE-MI300-114	1.1/4"
EE-MI300-112	1.1/2"
EE-MI300-2	2"
EE-MI300-212	2.1/2"
EE-MI300-3	3"
EE-MI300-4	4"
Tech Sheet 20538	

Cap, Rounded (301)




Black, BSPP

1095	Thread
EE-MI301-38N	3/8"
EE-MI301-12N	1/2"
EE-MI301-34N	3/4"
EE-MI301-1N	1"
EE-MI301-112N	1.1/2"
EE-MI301-2N	2"
Tech Sheet 20538	

Galvanised, BSPP

1095	Thread
EE-MI301-38	3/8"
EE-MI301-12	1/2"
EE-MI301-34	3/4"
EE-MI301-1	1"
EE-MI301-112	1.1/2"
EE-MI301-2	2"
Tech Sheet 20538	



For **PTFE Sealing Tape** see page **1391**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Backnut (310)



Black, BSPP

1095	Thread
EE-MI310-14N	1/4"
EE-MI310-38N	3/8"
EE-MI310-12N	1/2"
EE-MI310-34N	3/4"
EE-MI310-1N	1"
EE-MI310-114N	1.1/4"
EE-MI310-112N	1.1/2"
EE-MI310-2N	2"
EE-MI310-212N	2.1/2"
EE-MI310-3N	3"
Tech Sheet 20539	

Galvanised, BSPP

1095	Thread
EE-MI310-14	1/4"
EE-MI310-38	3/8"
EE-MI310-12	1/2"
EE-MI310-34	3/4"
EE-MI310-1	1"
EE-MI310-114	1.1/4"
EE-MI310-112	1.1/2"
EE-MI310-2	2"
EE-MI310-212	2.1/2"
EE-MI310-3	3"
Tech Sheet 20539	

Male x Female Equal Elbow 90° (92)



Black, BSPP Female x BSPT Male

1095	Thread
EE-MI92-14N	1/4"
EE-MI92-38N	3/8"
EE-MI92-12N	1/2"
EE-MI92-34N	3/4"
EE-MI92-1N	1"
EE-MI92-114N	1.1/4"
EE-MI92-112N	1.1/2"
EE-MI92-2N	2"
EE-MI92-212N	2.1/2"
EE-MI92-3N	3"
EE-MI92-4N	4"
Tech Sheet 20529	

Galvanised, BSPP Female x BSPT Male

1095	Thread
EE-MI92-14	1/4"
EE-MI92-38	3/8"
EE-MI92-12	1/2"
EE-MI92-34	3/4"
EE-MI92-1	1"
EE-MI92-114	1.1/4"
EE-MI92-112	1.1/2"
EE-MI92-2	2"
EE-MI92-212	2.1/2"
EE-MI92-3	3"
EE-MI92-4	4"
Tech Sheet 20529	

Female Equal Elbow 90° (90)



Black, BSPP

1095	Thread
EE-MI90-14N	1/4"
EE-MI90-38N	3/8"
EE-MI90-12N	1/2"
EE-MI90-34N	3/4"
EE-MI90-1N	1"
EE-MI90-114N	1.1/4"
EE-MI90-112N	1.1/2"
EE-MI90-2N	2"
EE-MI90-212N	2.1/2"
EE-MI90-3N	3"
EE-MI90-4N	4"
Tech Sheet 20529	

Galvanised, BSPP

1095	Thread
EE-MI90-14	1/4"
EE-MI90-38	3/8"
EE-MI90-12	1/2"
EE-MI90-34	3/4"
EE-MI90-1	1"
EE-MI90-114	1.1/4"
EE-MI90-112	1.1/2"
EE-MI90-2	2"
EE-MI90-212	2.1/2"
EE-MI90-3	3"
EE-MI90-4	4"
Tech Sheet 20529	

Male Equal Elbow 90°



Black, BSPT

1095	Thread
EE-MI94-12N	1/2"
EE-MI94-34N	3/4"
EE-MI94-1N	1"

Galvanised, BSPT

1095	Thread
EE-MI94-12	1/2"
EE-MI94-34	3/4"
EE-MI94-1	1"

Male x Female Union Elbow 90°, Taper Seat (98)



Black, BSPP Female x BSPT Male

1095	Thread
EE-MI98-38N	3/8"
EE-MI98-12N	1/2"
EE-MI98-34N	3/4"
EE-MI98-1N	1"
EE-MI98-114N	1.1/4"
EE-MI98-112N	1.1/2"
EE-MI98-2N	2"
Tech Sheet 20529	

Galvanised, BSPP Female x BSPT Male

1095	Thread
EE-MI98-38	3/8"
EE-MI98-12	1/2"
EE-MI98-34	3/4"
EE-MI98-1	1"
EE-MI98-114	1.1/4"
EE-MI98-112	1.1/2"
EE-MI98-2	2"
Tech Sheet 20529	

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Equal Union Elbow 90°, Taper Seat (96)



Black, BSPP

1095	Thread
EE-MI96-38N	3/8"
EE-MI96-12N	1/2"
EE-MI96-34N	3/4"
EE-MI96-1N	1"
EE-MI96-114N	1.1/4"
EE-MI96-112N	1.1/2"
EE-MI96-2N	2"
Tech Sheet 20529	

Galvanised, BSPP

1095	Thread
EE-MI96-38	3/8"
EE-MI96-12	1/2"
EE-MI96-34	3/4"
EE-MI96-1	1"
EE-MI96-114	1.1/4"
EE-MI96-112	1.1/2"
EE-MI96-2	2"
Tech Sheet 20529	

Female Equal Elbow 45° (120)



Black, BSPP

1095	Thread
EE-MI120-12N	1/2"
EE-MI120-34N	3/4"
EE-MI120-1N	1"

Galvanised, BSPP

1095	Thread
EE-MI120-12	1/2"
EE-MI120-34	3/4"
EE-MI120-1	1"

Female Reducing Elbow 90° (90R)



Black, BSPP

1095	Thread	Thread
EE-MI90-12-38N	1/2"	3/8"
EE-MI90-34-12N	3/4"	1/2"
EE-MI90-1-12N	1"	1/2"
EE-MI90-1-34N	1"	3/4"
EE-MI90-114-1N	1.1/4"	1"
EE-MI90-112-1N	1.1/2"	1"
EE-MI90-112-114N	1.1/2"	1.1/4"
EE-MI90-2-114N	2"	1.1/4"
EE-MI90-2-112N	2"	1.1/2"
Tech Sheet 20529		

Galvanised, BSPP

1095	Thread	Thread
EE-MI90-12-38	1/2"	3/8"
EE-MI90-34-38	3/4"	3/8"
EE-MI90-34-12	3/4"	1/2"
EE-MI90-1-12	1"	1/2"
EE-MI90-1-34	1"	3/4"
EE-MI90-114-1	1.1/4"	1"
EE-MI90-112-34	1.1/2"	3/4"
EE-MI90-112-1	1.1/2"	1"
EE-MI90-112-114	1.1/2"	1.1/4"
EE-MI90-2-1	2"	1"
EE-MI90-2-114	2"	1.1/4"
EE-MI90-2-112	2"	1.1/2"
Tech Sheet 20529		

Male x Female Reducing Elbow 90º (92R)



Galvanised, BSPP Female x BSPT Male

1095	Female Thread	Male Thread
EE-MI92-12-38	1/2"	3/8"
EE-MI92-34-12	3/4"	1/2"
EE-MI92-1-34	1"	3/4"

Black, BSPP Female x BSPT Male

1095	Female Thread	Male Thread
EE-MI92-12-38N	1/2"	3/8"
EE-MI92-34-12N	3/4"	1/2"
EE-MI92-1-34N	1"	3/4"

Female Equal Side Outlet Elbow (221)



Black, BSPP

1095	Thread
EE-MI221-38N	3/8"
EE-MI221-12N	1/2"
EE-MI221-34N	3/4"
EE-MI221-1N	1"
EE-MI221-114N	1.1/4"
EE-MI221-112N	1.1/2"
EE-MI221-2N	2"
Tech Sheet 20532	

Galvanised, BSPP

1095	Thread
EE-MI221-38	3/8"
EE-MI221-12	1/2"
EE-MI221-34	3/4"
EE-MI221-1	1"
EE-MI221-114	1.1/4"
EE-MI221-112	1.1/2"
EE-MI221-2	2"
Tech Sheet 20532	

Female Equal Bracket Elbow (471)



Galvanised, BSPP

1095	Thread
EE-MI471-12	1/2"
EE-MI471-34	3/4"

Black, BSPP

1095	Thread
EE-MI471-12N	1/2"
EE-MI471-34N	3/4"

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Male Equal Bend 90° (3)



Black, BSPT

1095	Thread
EE-MI3-12N	1/2"
EE-MI3-34N	3/4"
EE-MI3-1N	1"
Tech Sheet 20528	

Galvanised, BSPT

1095	Thread
EE-MI3-12	1/2"
EE-MI3-34	3/4"
EE-MI3-1	1"
Tech Sheet 20528	

Male x Female Equal Bend 90° (1)



Black, BSPP Female x BSPT Male

1095	Thread
EE-MI1-14N	1/4"
EE-MI1-38N	3/8"
EE-MI1-12N	1/2"
EE-MI1-34N	3/4"
EE-MI1-1N	1"
EE-MI1-114N	1.1/4"
EE-MI1-112N	1.1/2"
EE-MI1-2N	2"
EE-MI1-212N	2.1/2"
EE-MI1-3N	3"
Tech Sheet 20528	

Galvanised, BSPP Female x BSPT Male

1095	Thread
EE-MI1-14	1/4"
EE-MI1-38	3/8"
EE-MI1-12	1/2"
EE-MI1-34	3/4"
EE-MI1-1	1"
EE-MI1-114	1.1/4"
EE-MI1-112	1.1/2"
EE-MI1-2	2"
EE-MI1-212	2.1/2"
EE-MI1-3	3"
EE-MI1-4	4"
Tech Sheet 20528	

Female Equal Bend 90° (2)



Black, BSPP

1095	Thread
EE-MI2-14N	1/4"
EE-MI2-38N	3/8"
EE-MI2-12N	1/2"
EE-MI2-34N	3/4"
EE-MI2-1N	1"
EE-MI2-114N	1.1/4"
EE-MI2-112N	1.1/2"
EE-MI2-2N	2"
EE-MI2-3N	3"
Tech Sheet 20528	

Galvanised, BSPP

1095	Thread
EE-MI2-14	1/4"
EE-MI2-38	3/8"
EE-MI2-12	1/2"
EE-MI2-34	3/4"
EE-MI2-1	1"
EE-MI2-114	1.1/4"
EE-MI2-112	1.1/2"
EE-MI2-2	2"
EE-MI2-212	2.1/2"
EE-MI2-3	3"
EE-MI2-4	4"
Tech Sheet 20528	

Female Equal Short Bend 90° (2A)



Black, BSPP

1095	Thread
EE-MI2A-38N	3/8"
EE-MI2A-12N	1/2"
EE-MI2A-34N	3/4"
EE-MI2A-1N	1"
EE-MI2A-114N	1.1/4"
EE-MI2A-112N	1.1/2"
EE-MI2A-2N	2"

Galvanised, BSPP

1095	Thread
EE-MI2A-12	1/2"
EE-MI2A-34	3/4"
EE-MI2A-1	1"
EE-MI2A-114	1.1/4"
EE-MI2A-112	1.1/2"
EE-MI2A-2	2"

Male x Female Equal Short Bend 90° (1A)



Black, BSPT Male x BSPP Female

1095	Thread
EE-MI1A-38N	3/8"
EE-MI1A-12N	1/2"
EE-MI1A-34N	3/4"
EE-MI1A-1N	1"
EE-MI1A-114N	1.1/4"
EE-MI1A-112N	1.1/2"
EE-MI1A-2N	2"

Galvanised, BSPT Male x BSPP Female

1095	Thread
EE-MI1A-38	3/8"
EE-MI1A-12	1/2"
EE-MI1A-34	3/4"
EE-MI1A-1	1"
EE-MI1A-114	1.1/4"
EE-MI1A-112	1.1/2"
EE-MI1A-2	2"

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Male x Female Equal Bend 45° (40)



Black, BSPP Female x BSPT Male

1095	Thread
EE-MI40-14N	1/4"
EE-MI40-38N	3/8"
EE-MI40-12N	1/2"
EE-MI40-34N	3/4"
EE-MI40-1N	1"
EE-MI40-114N	1.1/4"
EE-MI40-112N	1.1/2"
EE-MI40-2N	2"
Tech Sheet 20528	

Galvanised, BSPP Female x BSPT Male

1095	Thread
EE-MI40-14	1/4"
EE-MI40-38	3/8"
EE-MI40-12	1/2"
EE-MI40-34	3/4"
EE-MI40-1	1"
EE-MI40-114	1.1/4"
EE-MI40-112	1.1/2"
EE-MI40-2	2"
EE-MI40-212	2.1/2"
EE-MI40-3	3"
EE-MI40-4	4"
Tech Sheet 20528	

Female Equal Bend 45° (41)



Black, BSPP

1095	Thread
EE-MI41-38N	3/8"
EE-MI41-12N	1/2"
EE-MI41-34N	3/4"
EE-MI41-1N	1"
EE-MI41-114N	1.1/4"
EE-MI41-112N	1.1/2"
EE-MI41-2N	2"
EE-MI41-212N	2.1/2"
Tech Sheet 20528	

Galvanised, BSPP

1095	Thread
EE-MI41-38	3/8"
EE-MI41-12	1/2"
EE-MI41-34	3/4"
EE-MI41-1	1"
EE-MI41-114	1.1/4"
EE-MI41-112	1.1/2"
EE-MI41-2	2"
EE-MI41-212	2.1/2"
EE-MI41-3	3"
Tech Sheet 20528	

Female Equal Tee (130)



Black, BSPP

1095	Thread
EE-MI130-14N	1/4"
EE-MI130-38N	3/8"
EE-MI130-12N	1/2"
EE-MI130-34N	3/4"
EE-MI130-1N	1"
EE-MI130-114N	1.1/4"
EE-MI130-112N	1.1/2"
EE-MI130-2N	2"
EE-MI130-3N	3"
EE-MI130-4N	4"
Tech Sheet 20530	

Galvanised, BSPP

1095	Thread
EE-MI130-14	1/4"
EE-MI130-38	3/8"
EE-MI130-12	1/2"
EE-MI130-34	3/4"
EE-MI130-1	1"
EE-MI130-114	1.1/4"
EE-MI130-112	1.1/2"
EE-MI130-2	2"
EE-MI130-212	2.1/2"
EE-MI130-3	3"
EE-MI130-4	4"
Tech Sheet 20530	

Female Equal Pitcher Tee (131)



Black, BSPP

1095	Thread
EE-MI131-12N	1/2"
EE-MI131-34N	3/4"
EE-MI131-1N	1"
EE-MI131-114N	1.1/4"
EE-MI131-112N	1.1/2"
EE-MI131-2N	2"
Tech Sheet 20530	


Galvanised, BSPP

1095	Thread
EE-MI131-12	1/2"
EE-MI131-34	3/4"
EE-MI131-1	1"
EE-MI131-114	1.1/4"
EE-MI131-112	1.1/2"
EE-MI131-2	2"
Tech Sheet 20530	

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Unequal Reducing Branch Tee (130)



Black, BSPP

1095	Thread A	Thread B
EE-MI130-38-14N	3/8"	1/4"
EE-MI130-12-14N	1/2"	1/4"
EE-MI130-12-38N	1/2"	3/8"
EE-MI130-34-14N	3/4"	1/4"
EE-MI130-34-38N	3/4"	3/8"
EE-MI130-34-12N	3/4"	1/2"
EE-MI130-1-38N	1"	3/8"
EE-MI130-1-12N	1"	1/2"
EE-MI130-1-34N	1"	3/4"
EE-MI130-114-12N	1.1/4"	1/2"
EE-MI130-114-34N	1.1/4"	3/4"
EE-MI130-114-1N	1.1/4"	1"
EE-MI130-112-12N	1.1/2"	1/2"
EE-MI130-112-34N	1.1/2"	3/4"
EE-MI130-112-1N	1.1/2"	1"
EE-MI130-112114N	1.1/2"	1.1/4"
EE-MI130-2-12N	2"	1/2"
EE-MI130-2-34N	2"	3/4"
EE-MI130-2-1N	2"	1"
EE-MI130-2-114N	2"	1.1/4"
EE-MI130-2-112N	2"	1.1/2"
EE-MI130-212-1N	2.1/2"	1"
EE-MI130-212114N	2.1/2"	1.1/4"
EE-MI130-212112N	2.1/2"	1.1/2"
EE-MI130-212-2N	2.1/2"	2"
EE-MI130-3-112N	3"	1.1/2"
EE-MI130-3-2N	3"	2"
EE-MI130-3-212N	3"	2.1/2"
EE-MI130-4-2N	4"	2"
EE-MI130-4-3N	4"	3"
Tech Sheet 20530		

Galvanised, BSPP

1095	Thread A	Thread B
EE-MI130-38-14	3/8"	1/4"
EE-MI130-12-14	1/2"	1/4"
EE-MI130-12-38	1/2"	3/8"
EE-MI130-34-14	3/4"	1/4"
EE-MI130-34-38	3/4"	3/8"
EE-MI130-34-12	3/4"	1/2"
EE-MI130-1-38	1"	3/8"
EE-MI130-1-12	1"	1/2"
EE-MI130-1-34	1"	3/4"
EE-MI130-114-12	1.1/4"	1/2"
EE-MI130-114-34	1.1/4"	3/4"
EE-MI130-114-1	1.1/4"	1"
EE-MI130-112-12	1.1/2"	1/2"
EE-MI130-112-34	1.1/2"	3/4"
EE-MI130-112-1	1.1/2"	1"
EE-MI130-112-114	1.1/2"	1.1/4"
EE-MI130-2-12	2"	1/2"
EE-MI130-2-34	2"	3/4"
EE-MI130-2-1	2"	1"
EE-MI130-2-114	2"	1.1/4"
EE-MI130-2-112	2"	1.1/2"
EE-MI130-212-34	2.1/2"	3/4"
EE-MI130-212-1	2.1/2"	1"
EE-MI130-212-112	2.1/2"	1.1/2"
EE-MI130-212-2	2.1/2"	2"
EE-MI130-3-112	3"	1.1/2"
EE-MI130-3-2	3"	2"
EE-MI130-3-212	3"	2.1/2"
EE-MI130-4-2	4"	2"
EE-MI130-4-3	4"	3"
Tech Sheet 20530		

Female Unequal Reducing Run Tee (130B)




Black, BSPP

1095	Thread A	Thread B
EEMI30-12-38-12N	1/2"	3/8"
EEMI30-34-12-34N	3/4"	1/2"
EEMI30-1-12-1N	1"	1/2"
EEMI30-1-34-1N	1"	3/4"
EEMI3011434114N	1.1/4"	3/4"
EEMI301141114N	1.1/4"	1"
EEMI30112114112N	1.1/2"	1.1/4"

Galvanised, BSPP

1095	Thread A	Thread B
EEMI30-12-38-12	1/2"	3/8"
EEMI30-34-12-34	3/4"	1/2"
EEMI30-1-12-1	1"	1/2"
EEMI30-1-34-1	1"	3/4"
EEMI3011434114	1.1/4"	3/4"
EEMI301141114	1.1/4"	1"
EEMI30112114112	1.1/2"	1.1/4"

Female Unequal Increasing Branch Tee (130)



Black, BSPP

1095	Thread A	Thread B
EE-MI130-38-12N	3/8"	1/2"
EE-MI130-12-34N	1/2"	3/4"
EE-MI130-12-1N	1/2"	1"
EE-MI130-34-1N	3/4"	1"
EE-MI130-1-114N	1"	1.1/4"
EE-MI130-1-112N	1"	1.1/2"
EE-MI130-114112N	1.1/4"	1.1/2"
EE-MI130-114-2N	1.1/4"	2"
EE-MI130-112-2N	1.1/2"	2"
EE-MI130-2-212N	2"	2.1/2"
EE-MI130-2-3N	2"	3"
Tech Sheet 20530		

Galvanised, BSPP


1095	Thread A	Thread B
EE-MI130-38-12	3/8"	1/2"
EE-MI130-12-34	1/2"	3/4"
EE-MI130-12-1	1/2"	1"
EE-MI130-34-1	3/4"	1"
EE-MI130-1-114	1"	1.1/4"
EE-MI130-1-112	1"	1.1/2"
EE-MI130-114-112	1.1/4"	1.1/2"
EE-MI130-114-2	1.1/4"	2"
EE-MI130-112-2	1.1/2"	2"
EE-MI130-2-212	2"	2.1/2"
EE-MI130-2-3	2"	3"
Tech Sheet 20530		

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Unequal Reducing Run & Branch Tee



Black, BSPP

1095	Thread A	Thread B	Thread C
EEMI30C123838N	1/2"	3/8"	3/8"
EEMI30C343812N	3/4"	3/8"	1/2"
EEMI30C341212N	3/4"	1/2"	1/2"
EEMI30C11212N	1"	1/2"	1/2"
EEMI30C11234N	1"	1/2"	3/4"
EEMI30C13434N	1"	3/4"	3/4"
EEMI30C114121N	1.1/4"	1/2"	1"
EEMI30C1143434N	1.1/4"	3/4"	3/4"
EEMI30C114341N	1.1/4"	3/4"	1"
EEMI30C11411N	1.1/4"	1"	1"
EEMI30C1121234N	1.1/2"	1/2"	3/4"
EEMI30C112134N	1.1/2"	1"	3/4"
EEMI30C11211N	1.1/2"	1"	1"
EEMI30C1121114N	1.1/2"	1"	1.1/4"
EEMI3C112114114N	1.1/2"	1.1/4"	1.1/4"
EEMI30C2112112N	2"	1.1/2"	1.1/2"

Galvanised, BSPP

1095	Thread A	Thread B	Thread C
EEMI30C123838	1/2"	3/8"	3/8"
EEMI30C343812	3/4"	3/8"	1/2"
EEMI30C341212	3/4"	1/2"	1/2"
EEMI30C11212	1"	1/2"	1/2"
EEMI30C11234	1"	1/2"	3/4"
EEMI30C13412	1"	3/4"	1/2"
EEMI30C13434	1"	3/4"	3/4"
EEMI30C114121	1.1/4"	1/2"	1"
EEMI30C1143434	1.1/4"	3/4"	3/4"
EEMI30C114341	1.1/4"	3/4"	1"
EEMI30C11411	1.1/4"	1"	1"
EEMI30C112134	1.1/2"	1"	3/4"
EEMI30C11211	1.1/2"	1"	1"
EEMI30C1121114	1.1/2"	1"	1.1/4"
EEMI30C112114114	1.1/2"	1.1/4"	1.1/4"
EEMI30C2112112	2"	1.1/2"	1.1/2"

Male Equal Tee



Black, BSPT

1095	Thread
EEMI135-1N	1"

Galvanised, BSPT

1095	Thread
EEMI135-1	1"

Female Equal Tee 45° (165)



Black, BSPP

1095	Thread
EE-MI165-12N	1/2"
EE-MI165-34N	3/4"
EE-MI165-1N	1"
EE-MI165-114N	1.1/4"
EE-MI165-112N	1.1/2"
EE-MI165-2N	2"
Tech Sheet 20530	

Galvanised, BSPP

1095	Thread
EE-MI165-12	1/2"
EE-MI165-34	3/4"
EE-MI165-1	1"
EE-MI165-114	1.1/4"
EE-MI165-112	1.1/2"
Tech Sheet 20530	

Equal Ys



Black, BSPP

1095	Thread
EE-MI220-12N	1/2"
EE-MI220-34N	3/4"
EE-MI220-1N	1"

Galvanised, BSPP

1095	Thread
EE-MI220-12	1/2"
EE-MI220-34	3/4"
EE-MI220-1	1"

MALLEABLE IRON FITTINGS

EE ODLEWNIA

Female Equal Cross (180)




Black, BSPP

1095	Thread
EE-MI180-38N	3/8"
EE-MI180-12N	1/2"
EE-MI180-34N	3/4"
EE-MI180-1N	1"
EE-MI180-114N	1.1/4"
EE-MI180-112N	1.1/2"
EE-MI180-2N	2"
Tech Sheet 20531	

Galvanised, BSPP

1095	Thread
EE-MI180-38	3/8"
EE-MI180-12	1/2"
EE-MI180-34	3/4"
EE-MI180-1	1"
EE-MI180-114	1.1/4"
EE-MI180-112	1.1/2"
EE-MI180-2	2"
EE-MI180-3	3"
Tech Sheet 20531	

Female Unequal Cross (180)



Black, BSPP

1095	Thread A	Thread B
EE-MI180-12-38N	1/2"	3/8"
EE-MI180-34-38N	3/4"	3/8"
EE-MI180-34-12N	3/4"	1/2"
EE-MI180-1-12N	1"	1/2"
EE-MI180-1-34N	1"	3/4"
EE-MI180-114-12N	1.1/4"	1/2"
EE-MI180-2-34N	2"	3/4"

Galvanised, BSPP

1095	Thread A	Thread B
EE-MI180-12-38	1/2"	3/8"
EE-MI180-34-38	3/4"	3/8"
EE-MI180-34-12	3/4"	1/2"
EE-MI180-1-12	1"	1/2"
EE-MI180-1-34	1"	3/4"
EE-MI180-114-12	1.1/4"	1/2"
EE-MI180-2-34	2"	3/4"

Female Crossover



Black, BSPP

1095	Thread
EE-MI85-12N	1/2"
EE-MI85-34N	3/4"

Galvanised, BSPP

1095	Thread
EE-MI85-12	1/2"
EE-MI85-34	3/4"

Screwed Flange




Black, BSPP

1095	Thread
EE-MI326-34-N	3/4"
EE-MI326-1-N	1"
EE-MI326-114-N	1.1/4"
EE-MI326-112-N	1.1/2"

Galvanised, BSPP

1095	Thread
EE-MI326-34	3/4"
EE-MI326-1	1"
EE-MI326-114	1.1/4"
EE-MI326-112	1.1/2"

Flange



Black, BSPP

1095	Thread
EE-MI321-38-N	3/8"
EE-MI321-12-N	1/2"
EE-MI321-34-N	3/4"
EE-MI321-1-N	1"
EE-MI321-114-N	1.1/4"
EE-MI321-112-N	1.1/2"
EE-MI321-2-N	2"
EE-MI321-212-N	2.1/2"
EE-MI321-3-N	3"
EE-MI321-4-N	4"

Galvanised, BSPP

1095	Thread
EE-MI321-38	3/8"
EE-MI321-12	1/2"
EE-MI321-34	3/4"
EE-MI321-1	1"
EE-MI321-114	1.1/4"
EE-MI321-112	1.1/2"
EE-MI321-2	2"
EE-MI321-212	2.1/2"
EE-MI321-3	3"
EE-MI321-4	4"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Hexagon Reducing Nipple (145)



Black, BSPT

1094	Thread	Thread
K-MI245-38-14N	3/8"	1/4"
K-MI245-12-14N	1/2"	1/4"
K-MI245-12-38N	1/2"	3/8"
K-MI245-34-14N	3/4"	1/4"
K-MI245-34-38N	3/4"	3/8"
K-MI245-34-12N	3/4"	1/2"
K-MI245-1-12N	1"	1/2"
K-MI245-1-34N	1"	3/4"
K-MI245-114-12N	1.1/4"	1/2"
K-MI245-114-34N	1.1/4"	3/4"
K-MI245-114-1N	1.1/4"	1"
K-MI245-112-12N	1.1/2"	1/2"
K-MI245-112-34N	1.1/2"	3/4"
K-MI245-112-1N	1.1/2"	1"
K-MI245-112-114N	1.1/2"	1.1/4"
K-MI245-2-12N	2"	1/2"
K-MI245-2-34N	2"	3/4"
K-MI245-2-1N	2"	1"
K-MI245-2-114N	2"	1.1/4"
K-MI245-2-112N	2"	1.1/2"
K-MI245-212-112N	2.1/2"	1.1/2"
K-MI245-212-2N	2.1/2"	2"
K-MI245-3-2N	3"	2"
K-MI245-3-212N	3"	2.1/2"
K-MI245-4-3N	4"	3"
Tech Sheet 20449		



Galvanised, BSPT

1094	Thread	Thread
K-MI245-38-14	3/8"	1/4"
K-MI245-12-14	1/2"	1/4"
K-MI245-12-38	1/2"	3/8"
K-MI245-34-14	3/4"	1/4"
K-MI245-34-38	3/4"	3/8"
K-MI245-34-12	3/4"	1/2"
K-MI245-1-38	1"	3/8"
K-MI245-1-12	1"	1/2"
K-MI245-1-34	1"	3/4"
K-MI245-114-12	1.1/4"	1/2"
K-MI245-114-34	1.1/4"	3/4"
K-MI245-114-1	1.1/4"	1"
K-MI245-112-12	1.1/2"	1/2"
K-MI245-112-34	1.1/2"	3/4"
K-MI245-112-1	1.1/2"	1"
K-MI245-112-114	1.1/2"	1.1/4"
K-MI245-2-12	2"	1/2"
K-MI245-2-34	2"	3/4"
K-MI245-2-1	2"	1"
K-MI245-2-114	2"	1.1/4"
K-MI245-2-112	2"	1.1/2"
K-MI245-212-112	2.1/2"	1.1/2"
K-MI245-212-2	2.1/2"	2"
K-MI245-3-2	3"	2"
K-MI245-3-212	3"	2.1/2"
K-MI245-4-3	4"	3"
Tech Sheet 20449		

Equal Hexagon Nipple (144)



Black, BSPT

1094	Thread
K-MI280-14N	1/4"
K-MI280-38N	3/8"
K-MI280-12N	1/2"
K-MI280-34N	3/4"
K-MI280-1N	1"
K-MI280-114N	1.1/4"
K-MI280-112N	1.1/2"
K-MI280-2N	2"
K-MI280-212N	2.1/2"
K-MI280-3N	3"
K-MI280-4N	4"
Tech Sheet 20449	

Galvanised, BSPT

1094	Thread
K-MI280-14	1/4"
K-MI280-38	3/8"
K-MI280-12	1/2"
K-MI280-34	3/4"
K-MI280-1	1"
K-MI280-114	1.1/4"
K-MI280-112	1.1/2"
K-MI280-2	2"
K-MI280-212	2.1/2"
K-MI280-3	3"
K-MI280-4	4"
Tech Sheet 20449	

RIDGID




For **Ridgid Wrenches** see page **1742**

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Maximum Working Pressure:
25 bar @ -20°C to +120°C
20 bar @ +300°C



Threads:
British standard taper, BSPT to ISO7-1 and EN10226-2.

Materials:
Suitable for fire protection, automatic sprinkler systems NFPA 13/24 and fittings for above ground

Fittings tested in accordance to BS EN10241:2000, BS EN1562 and dimensions to BS EN10242.

Media:
Suitable for the flow of wate , steam, gas or other non aggresive media.

Suface Finishing:
Two types are available:

Black:
With an anti-corrosive varnish to protect against rust after installation prior to plant conditioning.

Galvanised:
Hot-dip zinc coated to give additional resistance to corrosion, meeting the requirements of ASTM A153

K-LINE CONNECT

Malleable iron fittings suitable for use with drinking water

WRAS APPROVED PRODUCT

K-Line Connect kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Female Equal Elbow 90° (151)



Black, BSPT

1094	Thread
K-MI90-14N	1/4"
K-MI90-38N	3/8"
K-MI90-12N	1/2"
K-MI90-34N	3/4"
K-MI90-1N	1"
K-MI90-114N	1.1/4"
K-MI90-112N	1.1/2"
K-MI90-2N	2"
K-MI90-212N	2.1/2"
K-MI90-3N	3"
K-MI90-4N	4"
Tech Sheet 20445	

Galvanised, BSPT

1094	Thread
K-MI90-14	1/4"
K-MI90-38	3/8"
K-MI90-12	1/2"
K-MI90-34	3/4"
K-MI90-1	1"
K-MI90-114	1.1/4"
K-MI90-112	1.1/2"
K-MI90-2	2"
K-MI90-212	2.1/2"
K-MI90-3	3"
K-MI90-4	4"
Tech Sheet 20445	

Male x Female Equal Elbow 90° (152)



Black, BSPT

1094	Thread
K-MI92-14N	1/4"
K-MI92-38N	3/8"
K-MI92-12N	1/2"
K-MI92-34N	3/4"
K-MI92-1N	1"
K-MI92-114N	1.1/4"
K-MI92-112N	1.1/2"
K-MI92-2N	2"
K-MI92-212N	2.1/2"
K-MI92-3N	3"
K-MI92-4N	4"
Tech Sheet 20445	

Galvanised, BSPT

1094	Thread
K-MI92-14	1/4"
K-MI92-38	3/8"
K-MI92-12	1/2"
K-MI92-34	3/4"
K-MI92-1	1"
K-MI92-114	1.1/4"
K-MI92-112	1.1/2"
K-MI92-2	2"
K-MI92-212	2.1/2"
K-MI92-3	3"
K-MI92-4	4"
Tech Sheet 20445	

Female Equal Elbow 45° (155)



Black, BSPT

1094	Thread
K-MI120-38N	3/8"
K-MI120-12N	1/2"
K-MI120-34N	3/4"
K-MI120-1N	1"
K-MI120-114N	1.1/4"
K-MI120-112N	1.1/2"
K-MI120-2N	2"
Tech Sheet 20445	

Galvanised, BSPT

1094	Thread
K-MI120-38	3/8"
K-MI120-12	1/2"
K-MI120-34	3/4"
K-MI120-1	1"
K-MI120-114	1.1/4"
K-MI120-112	1.1/2"
K-MI120-2	2"
Tech Sheet 20445	

Male x Female Equal Elbow 45° (156)



Black, BSPT

1094	Thread
K-MI121-38N	3/8"
K-MI121-12N	1/2"
K-MI121-34N	3/4"
K-MI121-1N	1"
K-MI121-114N	1.1/4"
K-MI121-112N	1.1/2"
K-MI121-2N	2"
Tech Sheet 20445	

Galvanised, BSPT

1094	Thread
K-MI121-38	3/8"
K-MI121-12	1/2"
K-MI121-34	3/4"
K-MI121-1	1"
K-MI121-114	1.1/4"
K-MI121-112	1.1/2"
K-MI121-2	2"
Tech Sheet 20445	

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Female Reducing Elbow 90°



Black, BSPT

1094	Thread	Thread
K-MI90-38-14N	3/8"	1/4"
K-MI90-12-38N	1/2"	3/8"
K-MI90-12-14N	1/2"	1/4"
K-MI90-34-38N	3/4"	3/8"
K-MI90-34-12N	3/4"	1/2"
K-MI90-34-14N	3/4"	1/4"
K-MI90-1-14N	1"	1/4"
K-MI90-1-38N	1"	3/8"
K-MI90-1-12N	1"	1/2"
K-MI90-1-34N	1"	3/4"
K-MI90-114-38N	1.1/4"	3/8"
K-MI90-114-12N	1.1/4"	1/2"
K-MI90-114-34N	1.1/4"	3/4"
K-MI90-114-1N	1.1/4"	1"
K-MI90-112-12N	1.1/2"	1/2"
K-MI90-112-34N	1.1/2"	3/4"
K-MI90-112-1N	1.1/2"	1"
K-MI90-112-114N	1.1/2"	1.1/4"
K-MI90-2-12N	2"	1/2"
K-MI90-2-34N	2"	3/4"
K-MI90-2-1N	2"	1"
K-MI90-2-114N	2"	1.1/4"
K-MI90-2-112N	2"	1.1/2"
K-MI90-212-12N	2.1/2"	1/2"
K-MI90-212-34N	2.1/2"	3/4"
K-MI90-212-1N	2.1/2"	1"
K-MI90-212-114N	2.1/2"	1.1/4"
K-MI90-212-112N	2.1/2"	1.1/2"
K-MI90-212-2N	2.1/2"	2"
K-MI90-3-34N	3"	3/4"
K-MI90-3-1N	3"	1"
K-MI90-3-114N	3"	1.1/4"
K-MI90-3-112N	3"	1.1/2"
K-MI90-3-2N	3"	2"
K-MI90-3-212N	3"	2.1/2"
K-MI90-4-114N	4"	1.1/4"
K-MI90-4-112N	4"	1.1/2"
K-MI90-4-2N	4"	2"
K-MI90-4-212N	4"	2.1/2"
K-MI90-4-3N	4"	3"



Galvanised, BSPT

1094	Thread	Thread
K-MI90-38-14	3/8"	1/4"
K-MI90-12-38	1/2"	3/8"
K-MI90-12-14	1/2"	1/4"
K-MI90-34-38	3/4"	3/8"
K-MI90-34-12	3/4"	1/2"
K-MI90-34-14	3/4"	1/4"
K-MI90-1-14	1"	1/4"
K-MI90-1-38	1"	3/8"
K-MI90-1-12	1"	1/2"
K-MI90-114-38	1.1/4"	3/8"
K-MI90-114-12	1.1/4"	1/2"
K-MI90-114-34	1.1/4"	3/4"
K-MI90-114-1	1.1/4"	1"
K-MI90-112-12	1.1/2"	1/2"
K-MI90-112-34	1.1/2"	3/4"
K-MI90-112-1	1.1/2"	1"
K-MI90-2-12	2"	1/2"
K-MI90-2-34	2"	3/4"
K-MI90-2-1	2"	1"
K-MI90-2-114	2"	1.1/4"
K-MI90-2-112	2"	1.1/2"
K-MI90-212-12	2.1/2"	1/2"
K-MI90-212-34	2.1/2"	3/4"
K-MI90-212-1	2.1/2"	1"
K-MI90-212-114	2.1/2"	1.1/4"
K-MI90-212-112	2.1/2"	1.1/2"
K-MI90-212-2	2.1/2"	2"
K-MI90-3-34	3"	3/4"
K-MI90-3-1	3"	1"
K-MI90-3-114	3"	1.1/4"
K-MI90-3-112	3"	1.1/2"
K-MI90-3-2	3"	2"
K-MI90-3-212	3"	2.1/2"
K-MI90-4-114	4"	1.1/4"
K-MI90-4-112	4"	1.1/2"
K-MI90-4-2	4"	2"
K-MI90-4-212	4"	2.1/2"
K-MI90-4-3	4"	3"

Female Equal Tee (161)



Black, BSPT

1094	Thread
K-MI130-14N	1/4"
K-MI130-38N	3/8"
K-MI130-12N	1/2"
K-MI130-34N	3/4"
K-MI130-1N	1"
K-MI130-114N	1.1/4"
K-MI130-112N	1.1/2"
K-MI130-2N	2"
K-MI130-212N	2.1/2"
K-MI130-3N	3"
K-MI130-4N	4"
Tech Sheet 20446	

Galvanised, BSPT

1094	Thread
K-MI130-14	1/4"
K-MI130-38	3/8"
K-MI130-12	1/2"
K-MI130-34	3/4"
K-MI130-1	1"
K-MI130-114	1.1/4"
K-MI130-112	1.1/2"
K-MI130-2	2"
K-MI130-212	2.1/2"
K-MI130-3	3"
K-MI130-4	4"
Tech Sheet 20446	

K-LINE CONNECT

Malleable iron fittings suitable for use with drinking water


WRAS APPROVED PRODUCT

K-Line Connect kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Female Unequal Branch Tee (161)



Black, BSPT

1094	Thread A	Thread B
K-MI130-38-14N	3/8"	1/2"
K-MI130-12-14N	1/2"	1/4"
K-MI130-12-38N	1/2"	3/8"
K-MI130-12-34N	1/2"	3/4"
K-MI130-34-14N	3/4"	1/4"
K-MI130-34-12N	3/4"	1/2"
K-MI130-1-38N	1"	3/8"
K-MI130-1-12N	1"	1/2"
K-MI130-1-34N	1"	3/4"
K-MI130-114-12N	1.1/4"	1/2"
K-MI130-114-34N	1.1/4"	3/4"
K-MI130-114-1N	1.1/4"	1"
K-MI130-112-12N	1.1/2"	1/2"
K-MI130-112-34N	1.1/2"	3/4"
K-MI130-112-1N	1.1/2"	1"
K-MI130-112-114N	1.1/2"	1.1/4"
K-MI130-2-12N	2"	1/2"
K-MI130-2-34N	2"	3/4"
K-MI130-2-1N	2"	1"
K-MI130-2-114N	2"	1.1/4"
K-MI130-2-112N	2"	1.1/2"
Tech Sheet 20446		

Galvanised, BSPT

1094	Thread A	Thread B
K-MI130-38-14	3/8"	1/4"
K-MI130-12-14	1/2"	1/4"
K-MI130-12-38	1/2"	3/8"
K-MI130-12-34	1/2"	3/4"
K-MI130-34-38	3/4"	3/8"
K-MI130-34-12	3/4"	1/2"
K-MI130-1-38	1"	3/8"
K-MI130-1-12	1"	1/2"
K-MI130-1-34	1"	3/4"
K-MI130-114-12	1.1/4"	1/2"
K-MI130-114-34	1.1/4"	3/4"
K-MI130-114-1	1.1/4"	1"
K-MI130-112-12	1.1/2"	1/2"
K-MI130-112-34	1.1/2"	3/4"
K-MI130-112-1	1.1/2"	1"
K-MI130-112-114	1.1/2"	1.1/4"
K-MI130-2-12	2"	1/2"
K-MI130-2-34	2"	3/4"
K-MI130-2-1	2"	1"
K-MI130-2-114	2"	1.1/4"
K-MI130-2-112	2"	1.1/2"
Tech Sheet 20446		

Female Equal Cross



Black, BSPT

1094	Thread
K-MI180-14N	1/4"
K-MI180-38N	3/8"
K-MI180-12N	1/2"
K-MI180-34N	3/4"
K-MI180-1N	1"
K-MI180-114N	1.1/4"
K-MI180-112N	1.1/2"
K-MI180-2N	2"
K-MI180-212N	2.1/2"
K-MI180-3N	3"
K-MI180-4N	4'

Galvanised, BSPT

1094	Thread
K-MI180-14	1/4"
K-MI180-38	3/8"
K-MI180-12	1/2"
K-MI180-34	3/4"
K-MI180-1	1"
K-MI180-114	1.1/4"
K-MI180-112	1.1/2"
K-MI180-2	2"
K-MI180-212	2.1/2"
K-MI180-3	3"
K-MI180-4	4'

Female Equal Socket (177)



Black, BSPT

1094	Thread
K-MI220-38N	3/8"
K-MI220-12N	1/2"
K-MI220-34N	3/4"
K-MI220-1N	1"
K-MI220-114N	1.1/4"
K-MI220-112N	1.1/2"
K-MI220-2N	2"
K-MI220-212N	2.1/2"
K-MI220-3N	3"
K-MI220-4N	4"
Tech Sheet 20447	

Galvanised, BSPT

1094	Thread
K-MI220-38	3/8"
K-MI220-12	1/2"
K-MI220-34	3/4"
K-MI220-1	1"
K-MI220-114	1.1/4"
K-MI220-112	1.1/2"
K-MI220-2	2"
K-MI220-212	2.1/2"
K-MI220-3	3"
K-MI220-4	4"
Tech Sheet 20447	

FT PRO®



For **Malleable Iron Foot Valves** see page **1436**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Female Reducing Socket (179)



Black, BSPT

1094	Thread	Thread
K-MI240-38-14N	3/8"	1/4"
K-MI240-12-14N	1/2"	1/4"
K-MI240-12-38N	1/2"	3/8"
K-MI240-34-38N	3/4"	3/8"
K-MI240-34-12N	3/4"	1/2"
K-MI240-1-38N	1"	3/8"
K-MI240-1-12N	1"	1/2"
K-MI240-1-34N	1"	3/4"
K-MI240-114-38N	1.1/4"	3/8"
K-MI240-114-12N	1.1/4"	1/2"
K-MI240-114-34N	1.1/4"	3/4"
K-MI240-114-1N	1.1/4"	1"
K-MI240-112-12N	1.1/2"	1/2"
K-MI240-112-34N	1.1/2"	3/4"
K-MI240-112-1N	1.1/2"	1"
K-MI240-112-114N	1.1/2"	1.1/4"
K-MI240-2-12N	2"	1/2"
K-MI240-2-34N	2"	3/4"
K-MI240-2-1N	2"	1"
K-MI240-2-114N	2"	1.1/4"
K-MI240-2-112N	2"	1.1/2"
Tech Sheet 20447		

Galvanised, BSPT

1094	Thread	Thread
K-MI240-38-14	3/8"	1/4"
K-MI240-12-14	1/2"	1/4"
K-MI240-12-38	1/2"	3/8"
K-MI240-34-38	3/4"	3/8"
K-MI240-34-12	3/4"	1/2"
K-MI240-1-38	1"	3/8"
K-MI240-1-12	1"	1/2"
K-MI240-1-34	1"	3/4"
K-MI240-114-38	1.1/4"	3/8"
K-MI240-114-12	1.1/4"	1/2"
K-MI240-114-34	1.1/4"	3/4"
K-MI240-114-1	1.1/4"	1"
K-MI240-112-12	1.1/2"	1/2"
K-MI240-112-34	1.1/2"	3/4"
K-MI240-112-1	1.1/2"	1"
K-MI240-112-114	1.1/2"	1.1/4"
K-MI240-2-12	2"	1/2"
K-MI240-2-34	2"	3/4"
K-MI240-2-1	2"	1"
K-MI240-2-114	2"	1.1/4"
K-MI240-2-112	2"	1.1/2"
Tech Sheet 20447		

Male x Female Reducing Bush (140)





Black, BSPT

1094	Thread	Thread
K-MI241-38-14N	3/8"	1/4"
K-MI241-12-14N	1/2"	1/4"
K-MI241-12-38N	1/2"	3/8"
K-MI241-34-14N	3/4"	1/4"
K-MI241-34-38N	3/4"	3/8"
K-MI241-34-12N	3/4"	1/2"
K-MI241-1-14N	1"	1/4"
K-MI241-1-38N	1"	3/8"
K-MI241-1-12N	1"	1/2"
K-MI241-1-34N	1"	3/4"
K-MI241-114-12N	1.1/4"	1/2"
K-MI241-114-34N	1.1/4"	3/4"
K-MI241-114-1N	1.1/4"	1"
K-MI241-112-12N	1.1/2"	1/2"
K-MI241-112-34N	1.1/2"	3/4"
K-MI241-112-1N	1.1/2"	1"
K-MI241-112-114N	1.1/2"	1.1/4"
K-MI241-2-12N	2"	1/2"
K-MI241-2-34N	2"	3/4"
K-MI241-2-1N	2"	1"
K-MI241-2-114N	2"	1.1/4"
K-MI241-2-112N	2"	1.1/2"
K-MI241-212-12N	2.1/2"	1/2"
K-MI241-212-34N	2.1/2"	3/4"
K-MI241-212-1N	2.1/2"	1"
K-MI241-212-114N	2.1/2"	1.1/4"
K-MI241-212-112N	2.1/2"	1.1/2"
K-MI241-212-2N	2.1/2"	2"
K-MI241-3-1N	3"	1"
K-MI241-3-112N	3"	1.1/2"
K-MI241-3-2N	3"	2"
K-MI241-3-212N	3"	2.1/2"
K-MI241-4-34N	4"	3/4"
K-MI241-4-1N	4"	1"
K-MI241-4-114N	4"	1.1/4"
K-MI241-4-112N	4"	1.1/2"
K-MI241-4-2N	4"	2"
K-MI241-4-212N	4"	2.1/2"
K-MI241-4-3N	4"	3"
Tech Sheet 20448		

Galvanised, BSPT

1094	Thread	Thread
K-MI241-38-14	3/8"	1/4"
K-MI241-12-14	1/2"	1/4"
K-MI241-12-38	1/2"	3/8"
K-MI241-34-14	3/4"	1/4"
K-MI241-34-38	3/4"	3/8"
K-MI241-34-12	3/4"	1/2"
K-MI241-1-14	1"	1/4"
K-MI241-1-38	1"	3/8"
K-MI241-1-12	1"	1/2"
K-MI241-1-34	1"	3/4"
K-MI241-114-38	1.1/4"	3/8"
K-MI241-114-12	1.1/4"	1/2"
K-MI241-114-34	1.1/4"	3/4"
K-MI241-114-1	1.1/4"	1"
K-MI241-112-12	1.1/2"	1/2"
K-MI241-112-34	1.1/2"	3/4"
K-MI241-112-1	1.1/2"	1"
K-MI241-112-114	1.1/2"	1.1/4"
K-MI241-2-12	2"	1/2"
K-MI241-2-34	2"	3/4"
K-MI241-2-1	2"	1"
K-MI241-2-114	2"	1.1/4"
K-MI241-2-112	2"	1.1/2"
K-MI241-212-12	2.1/2"	1/2"
K-MI241-212-34	2.1/2"	3/4"
K-MI241-212-1	2.1/2"	1"
K-MI241-212-114	2.1/2"	1.1/4"
K-MI241-212-112	2.1/2"	1.1/2"
K-MI241-212-2	2.1/2"	2"
K-MI241-3-1	3"	1"
K-MI241-3-112	3"	1.1/2"
K-MI241-3-2	3"	2"
K-MI241-3-212	3"	2.1/2"
K-MI241-4-34	4"	3/4"
K-MI241-4-1	4"	1"
K-MI241-4-114	4"	1.1/4"
K-MI241-4-112	4"	1.1/2"
K-MI241-4-2	4"	2"
K-MI241-4-212	4"	2.1/2"
K-MI241-4-3	4"	3"
Tech Sheet 20448		

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Plain Plug Hollow (147)



Black, BSPT

1094	Thread
K-MI291-14N	1/4"
K-MI291-38N	3/8"
K-MI291-12N	1/2"
K-MI291-34N	3/4"
K-MI291-1N	1"
K-MI291-114N	1.1/4"
K-MI291-112N	1.1/2"
K-MI291-2N	2"
K-MI291-212N	2.1/2"
K-MI291-3N	3"
K-MI291-4N	4"
Tech Sheet 20450	

Galvanised, BSPT

1094	Thread
K-MI291-14	1/4"
K-MI291-38	3/8"
K-MI291-12	1/2"
K-MI291-34	3/4"
K-MI291-1	1"
K-MI291-114	1.1/4"
K-MI291-112	1.1/2"
K-MI291-2	2"
K-MI291-212	2.1/2"
K-MI291-3	3"
K-MI291-4	4"
Tech Sheet 20450	

Plain Plug Solid (148)




Black, BSPT

1094	Thread
K-MI291S-14N	1/4"
K-MI291S-38N	3/8"
K-MI291S-12N	1/2"
K-MI291S-34N	3/4"
K-MI291S-1N	1"
K-MI291S-114N	1.1/4"
K-MI291S-112N	1.1/2"
K-MI291S-2N	2"
K-MI291S-212N	2.1/2"
K-MI291S-3N	3"
K-MI291S-4N	4"
Tech Sheet 20450	

Galvanised, BSPT

1094	Thread
K-MI291S-14	1/4"
K-MI291S-38	3/8"
K-MI291S-12	1/2"
K-MI291S-34	3/4"
K-MI291S-1	1"
K-MI291S-114	1.1/4"
K-MI291S-112	1.1/2"
K-MI291S-2	2"
K-MI291S-212	2.1/2"
K-MI291S-3	3"
K-MI291S-4	4"
Tech Sheet 20450	

Backnut



Black, BSPT

1094	Thread
K-MI310-14N	1/4"
K-MI310-38N	3/8"
K-MI310-12N	1/2"
K-MI310-34N	3/4"
K-MI310-114N	1.1/4"
K-MI310-112N	1.1/2"
K-MI310-2N	2"
K-MI310-212N	2.1/2"
K-MI310-3N	3"
K-MI310-4N	4"
Tech Sheet 68727	

Galvanised, BSPT

1094	Thread
K-MI310-38	3/8"
K-MI310-12	1/2"
K-MI310-34	3/4"
K-MI310-1	1"
K-MI310-114	1.1/4"
K-MI310-2	2"
K-MI310-212	2.1/2"
K-MI310-3	3"
K-MI310-4	4"
Tech Sheet 68727	

FT PRO



For **Forged Steel Flanges**
see page **1386**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Cap Rounded (185)




Black, BSPT

1094	Thread
K-MI300-38N	3/8"
K-MI300-12N	1/2"
K-MI300-34N	3/4"
K-MI300-1N	1"
K-MI300-114N	1.1/4"
K-MI300-112N	1.1/2"
K-MI300-2N	2"
Tech Sheet 20451	

Galvanised, BSPT

1094	Thread
K-MI300-14	1/4"
K-MI300-38	3/8"
K-MI300-12	1/2"
K-MI300-34	3/4"
K-MI300-1	1"
K-MI300-114	1.1/4"
K-MI300-112	1.1/2"
K-MI300-2	2"
Tech Sheet 20451	

Female Union Flat Seat (290)



Galvanised, BSPT

1094	Thread
K-MI330-38	3/8"
K-MI330-12	1/2"
K-MI330-34	3/4"
K-MI330-1	1"
K-MI330-114	1.1/4"
K-MI330-112	1.1/2"
K-MI330-2	2"
K-MI330-212	2.1/2"
K-MI330-3	3"
K-MI330-4	4"
Tech Sheet 20452	

Black, BSPT

1094	Thread
K-MI330-38N	3/8"
K-MI330-12N	1/2"
K-MI330-34N	3/4"
K-MI330-1N	1"
K-MI330-114N	1.1/4"
K-MI330-112N	1.1/2"
K-MI330-2N	2"
K-MI330-212N	2.1/2"
K-MI330-3N	3"
K-MI330-4N	4"
Tech Sheet 20452	

Female x Male Union Flat Seat (257)



Black, BSPT

1094	Thread
K-MI331-12N	1/2"
K-MI331-34N	3/4"
K-MI331-1N	1"
K-MI331-114N	1.1/4"
K-MI331-112N	1.1/2"
K-MI331-2N	2"
Tech Sheet 20452	

Galvanised, BSPT

1094	Thread
K-MI331-12	1/2"
K-MI331-34	3/4"
K-MI331-1	1"
K-MI331-114	1.1/4"
K-MI331-112	1.1/2"
K-MI331-2	2"
Tech Sheet 20452	

Female Union, Navy, Double Bronze Seat (289)



Black, BSPT

1094	Thread
K-MI342A-12N	1/2"
K-MI342A-34N	3/4"
K-MI342A-1N	1"
K-MI342A-114N	1.1/4"
K-MI342A-112N	1.1/2"
K-MI342A-2N	2"
Tech Sheet 20452	

Galvanised, BSPT

1094	Thread
K-MI342A-12	1/2"
K-MI342A-34	3/4"
K-MI342A-1	1"
K-MI342A-114	1.1/4"
K-MI342A-112	1.1/2"
K-MI342A-2	2"
Tech Sheet 20452	

TOTAL



For **G Clamp**
see page **1740**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Threads:
Threads are British Standard taper to IS07 and BS21.
All male threads are BSPT and female threads are BSPP to EN 10226-1 and EN ISO 228-1

Materials:
Whiteheart malleable cast iron EN-GJMW-400-5 to EN 1562


Media:
Suitable for the flow of wate , steam, gas or other non aggressive media.

Surface Finishing:
Two types are available:

Black:
With an anti-corrosive varnish to protect against rust after installation prior to plant conditioning.

Galvanised:
Hot-dip zinc coated to give additional resistance to corrosion

Maximum Working Pressure:
25 bar @ -20°C to +120°C
20 bar @ -50°C (intermittent) to +300°C



Female x Male Equal Bend, Long (1)



Black, BSPP Female x BSPT Male

0217	Thread
GF1-14N	1/4"
GF1-38N	3/8"
GF1-12N	1/2"
GF1-34N	3/4"
GF1-1N	1"
GF1-114N	1.1/4"
GF1-112N	1.1/2"
GF1-2N	2"
GF1-212N	2.1/2"
GF1-3N	3"
GF1-4N	4"
Tech Sheet 1764	

Galvanised, BSPP Female x BSPT Male

0217	Thread
GF1-14	1/4"
GF1-38	3/8"
GF1-12	1/2"
GF1-34	3/4"
GF1-1	1"
GF1-114	1.1/4"
GF1-112	1.1/2"
GF1-2	2"
GF1-212	2.1/2"
GF1-3	3"
Tech Sheet 1764	

Female x Male Equal Bend, Short (1a)



Black, BSPP Female x BSPT Male

0217	Thread
GF1A-14N	1/4"
GF1A-38N	3/8"
GF1A-12N	1/2"
GF1A-34N	3/4"
GF1A-1N	1"
GF1A-114N	1.1/4"
GF1A-112N	1.1/2"
GF1A-2N	2"
GF1A-212N	2.1/2"
GF1A-3N	3"
GF1A-4N	4"
Tech Sheet 1764	

Galvanised, BSPP Female x BSPT Male

0217	Thread
GF1A-14	1/4"
GF1A-38	3/8"
GF1A-12	1/2"
GF1A-34	3/4"
GF1A-1	1"
GF1A-114	1.1/4"
GF1A-112	1.1/2"
GF1A-2	2"
GF1A-3	3"
GF1A-4	4"
Tech Sheet 1764	

Female Equal Bend, Long (2)



Black, BSPP Female

0217	Thread
GF2-14N	1/4"
GF2-38N	3/8"
GF2-12N	1/2"
GF2-34N	3/4"
GF2-1N	1"
GF2-114N	1.1/4"
GF2-112N	1.1/2"
GF2-2N	2"
GF2-212N	2.1/2"
GF2-3N	3"
GF2-4N	4"
Tech Sheet 1765	

Galvanised, BSPP Female

0217	Thread
GF2-14	1/4"
GF2-38	3/8"
GF2-12	1/2"
GF2-34	3/4"
GF2-1	1"
GF2-114	1.1/4"
GF2-112	1.1/2"
GF2-2	2"
GF2-212	2.1/2"
GF2-3	3"
Tech Sheet 1765	

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

+GF+

Female Equal Bend, Short (2a)



Black, BSPP Female

0217	Thread
GF2A-14N	1/4"
GF2A-38N	3/8"
GF2A-12N	1/2"
GF2A-34N	3/4"
GF2A-1N	1"
GF2A-114N	1.1/4"
GF2A-112N	1.1/2"
GF2A-2N	2"
GF2A-212N	2.1/2"
GF2A-3N	3"
GF2A-4N	4"
Tech Sheet 1765	

Galvanised, BSPP Female

0217	Thread
GF2A-14	1/4"
GF2A-38	3/8"
GF2A-12	1/2"
GF2A-34	3/4"
GF2A-1	1"
GF2A-114	1.1/4"
GF2A-112	1.1/2"
GF2A-2	2"
GF2A-212	2.1/2"
GF2A-3	3"
GF2A-4	4"
Tech Sheet 1765	

Male Equal Bend, Long (3)



Black, BSPT Male

0217	Thread
GF3-12N	1/2"
GF3-34N	3/4"
GF3-1N	1"
GF3-114N	1.1/4"
GF3-112N	1.1/2"
GF3-2N	2"
Tech Sheet 1766	

Galvanised, BSPT Male

0217	Thread
GF3-12	1/2"
GF3-34	3/4"
GF3-1	1"
GF3-114	1.1/4"
GF3-112	1.1/2"
GF3-2	2"
Tech Sheet 1766	

Male x Female Equal Bend, Long (40)



Black, BSPT Male x BSPP Female

0217	Thread
GF40-12N	1/2"
GF40-34N	3/4"
GF40-1N	1"
GF40-114N	1.1/4"
GF40-112N	1.1/2"
GF40-2N	2"
Tech Sheet 1766	

Galvanised, BSPT Male x BSPP Female

0217	Thread
GF40-12	1/2"
GF40-34	3/4"
GF40-1	1"
GF40-114	1.1/4"
GF40-112	1.1/2"
GF40-2	2"
Tech Sheet 1766	

Female Equal Return Bend (60)



Black, BSPP Female

0217	Thread
GF60-12N	1/2"
GF60-34N	3/4"
GF60-1N	1"
GF60-112N	1.1/2"
GF60-2N	2"
Tech Sheet 1767	

Galvanised, BSPP Female

0217	Thread
GF60-12	1/2"
GF60-34	3/4"
GF60-1	1"
GF60-114	1.1/4"
GF60-112	1.1/2"
GF60-2	2"
Tech Sheet 1767	

FT PRO®

Customers who bought from this page also purchased...

Hose Reels
see pages **1448-1453**



FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Female Equal Elbow (90)



Black, BSPP Female

0217	Thread
GF90-18N	1/8"
GF90-14N	1/4"
GF90-38N	3/8"
GF90-12N	1/2"
GF90-34N	3/4"
GF90-1N	1"
GF90-114N	1.1/4"
GF90-112N	1.1/2"
GF90-2N	2"
GF90-212N	2.1/2"
GF90-3N	3"
GF90-4N	4"
GF90-5N	5"
Tech Sheet 1769	

Galvanised, BSPP Female

0217	Thread
GF90-18	1/8"
GF90-14	1/4"
GF90-38	3/8"
GF90-12	1/2"
GF90-34	3/4"
GF90-1	1"
GF90-114	1.1/4"
GF90-112	1.1/2"
GF90-2	2"
GF90-212	2.1/2"
GF90-3	3"
GF90-4	4"
GF90-5	5"
Tech Sheet 1769	

Female Reducing Elbow (90)



Black, BSPP Female x BSPP Female

0217	Thread	Thread
GF90-38-14N	3/8"	1/4"
GF90-12-14N	1/2"	1/4"
GF90-12-38N	1/2"	3/8"
GF90-34-12N	3/4"	1/2"
GF90-10-12N	1"	1/2"
GF90-1-34N	1"	3/4"
GF90-114-1N	1.1/4"	1"
Tech Sheet 1769		

Galvanised, BSPP Female x BSPP Female

0217	Thread	Thread
GF90-12-14	1/2"	1/4"
GF90-12-38	1/2"	3/8"
GF90-34-12	3/4"	1/2"
GF90-10-12	1"	1/2"
GF90-1-34	1"	3/4"
GF90-114-1	1.1/4"	1"
Tech Sheet 1769		

Male x Female Equal Elbow (92)



Black, BSPT Male x BSPP Female

0217	Thread
GF92-18N	1/8"
GF92-14N	1/4"
GF92-38N	3/8"
GF92-12N	1/2"
GF92-34N	3/4"
GF92-1N	1"
GF92-114N	1.1/4"
GF92-112N	1.1/2"
GF92-2N	2"
GF92-212N	2.1/2"
GF92-3N	3"
GF92-4N	4"
Tech Sheet 1768	

Galvanised, BSPT Male x BSPP Female

0217	Thread
GF92-18	1/8"
GF92-14	1/4"
GF92-38	3/8"
GF92-12	1/2"
GF92-34	3/4"
GF92-1	1"
GF92-114	1.1/4"
GF92-112	1.1/2"
GF92-2	2"
GF92-212	2.1/2"
GF92-3	3"
Tech Sheet 1768	

Male x Female Reducing Elbow (92)



Black, BSPT Male x BSPP Female

0217	Female Thread	Male Thread
GF92-34-12N	3/4"	1/2"
GF92-1-34N	1"	3/4"

Galvanised, BSPT Male x BSPP Female

0217	Female Thread	Male Thread
GF92-34-12	3/4"	1/2"
GF92-1-34	1"	3/4"

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

+GF+

Male Equal Elbow (94)



Black, BSPT Male

0217	Thread
GF94-34N	3/4"
GF94-1N	1"
Tech Sheet 1770	

Galvanised, BSPT Male

0217	Thread
GF94-34	3/4"
GF94-1	1"
Tech Sheet 1770	

Female Equal Union Elbow, Taper Seat (96)



Black, BSPP Female

0217	Thread
GF96-12N	1/2"
GF96-34N	3/4"
GF96-1N	1"
GF96-114N	1.1/4"
GF96-112N	1.1/2"
GF96-2N	2"
Tech Sheet 1771	

Galvanised, BSPP Female

0217	Thread
GF96-12	1/2"
GF96-34	3/4"
GF96-1	1"
GF96-114	1.1/4"
GF96-112	1.1/2"
GF96-2	2"
Tech Sheet 1771	

Male x Female Equal Union Elbow, Taper Seat (98)



Black, BSPT Male x BSPP Female

0217	Thread
GF98-12N	1/2"
GF98-34N	3/4"
GF98-1N	1"
GF98-114N	1.1/4"
GF98-112N	1.1/2"
GF98-2N	2"
Tech Sheet 1772	

Galvanised, BSPT Male x BSPP Female

0217	Thread
GF98-12	1/2"
GF98-1	1"
GF98-114	1.1/4"
GF98-112	1.1/2"
GF98-2	2"
Tech Sheet 1772	

Female Equal Elbow 45° (120)



Black, BSPP Female

0217	Thread
GF120-12N	1/2"
GF120-34N	3/4"
GF120-1N	1"
GF120-114N	1.1/4"
GF120-112N	1.1/2"
GF120-2N	2"
GF120-212N	2.1/2"
GF120-3N	3"
Tech Sheet 1773	

Galvanised, BSPP Female

0217	Thread
GF120-12	1/2"
GF120-34	3/4"
GF120-1	1"
GF120-114	1.1/4"
GF120-112	1.1/2"
GF120-2	2"
GF120-3	3"
Tech Sheet 1773	

Male x Female Equal Elbow 45° (121)



Black, BSPT Male x BSPP Female

0217	Thread
GF121-38N	3/8"
GF121-12N	1/2"
GF121-34N	3/4"
GF121-1N	1"
GF121-114N	1.1/4"
GF121-112N	1.1/2"
GF121-2N	2"
Tech Sheet 1774	

Galvanised, BSPT Male x BSPP Female

0217	Thread
GF121-38	3/8"
GF121-12	1/2"
GF121-34	3/4"
GF121-1	1"
GF121-114	1.1/4"
GF121-112	1.1/2"
GF121-2	2"
GF121-212	2.1/2"
GF121-3	3"
Tech Sheet 1774	

FT PRO®

You might also need...

Screwed & Socketed Steel Tubing



...see page **1383**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Female Equal Tee (130)



Black, BSPP Female

0217	Thread
GF130-14N	1/4"
GF130-38N	3/8"
GF130-12N	1/2"
GF130-34N	3/4"
GF130-1N	1"
GF130-114N	1.1/4"
GF130-112N	1.1/2"
GF130-2N	2"
GF130-212N	2.1/2"
GF130-3N	3"
GF130-4N	4"
GF130-5N	5"
GF130-6N	6"
Tech Sheet 1774	

Galvanised, BSPP Female

0217	Thread
GF130-14	1/4"
GF130-38	3/8"
GF130-12	1/2"
GF130-34	3/4"
GF130-1	1"
GF130-114	1.1/4"
GF130-112	1.1/2"
GF130-2	2"
GF130-212	2.1/2"
GF130-3	3"
GF130-5	5"
Tech Sheet 1774	

Unequal Tee, Reducing on Branch (130)



Black, BSPP

0217	Thread A	Thread B
GF130-38-14N	3/8"	1/4"
GF130-12-14N	1/2"	1/4"
GF130-12-38N	1/2"	3/8"
GF130-12-34N	1/2"	3/4"
GF130-34-14N	3/4"	1/4"
GF130-34-38N	3/4"	3/8"
GF130-34-12N	3/4"	1/2"
GF130-34-1N	3/4"	1"
GF130-1-38N	1"	3/8"
GF130-1-12N	1"	1/2"
GF130-1-34N	1"	3/4"
GF130-1-114N	1"	1.1/4"
GF130-1-112N	1"	1.1/2"
GF130-114-12N	1.1/4"	1/2"
GF130-114-34N	1.1/4"	3/4"
GF130-114-1N	1.1/4"	1"
GF130-112-12N	1.1/2"	1/2"
GF130-112-34N	1.1/2"	3/4"
GF130-112-1N	1.1/2"	1"
GF130-112-114N	1.1/2"	1.1/4"
GF130-112-2N	1.1/2"	2"
GF130-2-12N	2"	1/2"
GF130-2-34N	2"	3/4"
GF130-2-1N	2"	1"
GF130-2-114N	2"	1.1/4"
GF130-2-112N	2"	1.1/2"
GF130-2-212N	2"	2.1/2"
GF130-212-12N	2.1/2"	1/2"
GF130-212-34N	2.1/2"	3/4"
GF130-212-1N	2.1/2"	1"
GF130-212-114N	2.1/2"	1.1/4"
GF130-212-112N	2.1/2"	1.1/2"
GF130-212-2N	2.1/2"	2"
GF130-3-34N	3"	3/4"
GF130-3-1N	3"	1"
GF130-3-114N	3"	1.1/4"
GF130-3-112N	3"	1.1/2"
GF130-3-2N	3"	2"
GF130-3-212N	3"	2.1/2"
GF130-4-1N	4"	1"
GF130-4-112N	4"	1.1/2"
GF130-4-2N	4"	2"
GF130-4-212N	4"	2.1/2"
GF130-4-3N	4"	3"
Tech Sheet 1775		



Galvanised, BSPP

0217	Thread A	Thread B
GF130-38-14	3/8"	1/4"
GF130-12-14	1/2"	1/4"
GF130-12-38	1/2"	3/8"
GF130-12-34	1/2"	3/4"
GF130-34-14	3/4"	1/4"
GF130-34-38	3/4"	3/8"
GF130-34-12	3/4"	1/2"
GF130-34-1	3/4"	1"
GF130-1-38	1"	3/8"
GF130-1-12	1"	1/2"
GF130-1-34	1"	3/4"
GF130-1-114	1"	1.1/4"
GF130-1-112	1"	1.1/2"
GF130-114-12	1.1/4"	1/2"
GF130-114-34	1.1/4"	3/4"
GF130-114-1	1.1/4"	1"
GF130-112-12	1.1/2"	1/2"
GF130-112-34	1.1/2"	3/4"
GF130-112-1	1.1/2"	1"
GF130-112-114	1.1/2"	1.1/4"
GF130-112-2	1.1/2"	2"
GF130-2-12	2"	1/2"
GF130-2-34	2"	3/4"
GF130-2-1	2"	1"
GF130-2-114	2"	1.1/4"
GF130-2-112	2"	1.1/2"
GF130-2-212	2"	2.1/2"
GF130-212-12	2.1/2"	1/2"
GF130-212-34	2.1/2"	3/4"
GF130-212-1	2.1/2"	1"
GF130-212-114	2.1/2"	1.1/4"
GF130-212-112	2.1/2"	1.1/2"
GF130-212-2	2.1/2"	2"
GF130-3-34	3"	3/4"
GF130-3-1	3"	1"
GF130-3-114	3"	1.1/4"
GF130-3-112	3"	1.1/2"
GF130-3-2	3"	2"
GF130-3-212	3"	2.1/2"
GF130-4-1	4"	1"
GF130-4-112	4"	1.1/2"
GF130-4-2	4"	2"
GF130-4-3	4"	3"
Tech Sheet 1775		

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Unequal Tee, Reducing on Run/Branch (130)



Black, BSPP

0217	Thread A	Thread B	Thread C
GF130-12-38-38N	1/2"	3/8"	3/8"
GF130-34-12-12N	3/4"	1/2"	1/2"
GF130-34-12-34N	3/4"	1/2"	3/4"
GF130-1-12-1N	1"	1/2"	1"
GF130-1-34-12N	1"	3/4"	1/2"
GF130-1-34-34N	1"	3/4"	3/4"
GF130-1-34-1N	1"	3/4"	1"
GF130-114-12114N	1.1/4"	1/2"	1.1/4"
GF130-114-1-12N	1.1/4"	1"	1/2"
GF130-114-1-34N	1.1/4"	1"	3/4"
GF130-114-1-1N	1.1/4"	1"	1"
GF130-114-1-114N	1.1/4"	1"	1.1/4"
GF130-112-12112N	1.1/2"	1/2"	1.1/2"
GF130-112-1-1N	1.1/2"	1"	1"
GF130-112-1-112N	1.1/2"	1"	1.1/2"
GF130-112-11412N	1.1/2"	1.1/4"	1/2"
GF130-112-114-1N	1.1/2"	1.1/4"	1"
GF130-112114114N	1.1/2"	1.1/4"	1.1/4"
GF130-2-12-2N	2"	1/2"	2"
GF130-2-34-2N	2"	3/4"	2"
GF130-2-1-2N	2"	1"	2"
GF130-2-112-1N	2"	1.1/2"	1"
GF130-2-112-114N	2"	1.1/2"	1.1/4"
GF130-2-112-112N	2"	1.1/2"	1.1/2"
GF130-2-112-2N	2"	1.1/2"	2"
GF130-212112212N	2.1/2"	1.1/2"	2.1/2"
GF130-212-2-2N	2.1/2"	2"	2"
Tech Sheet 1776			



Galvanised, BSPP

0217	Thread A	Thread B	Thread C
GF130-12-38-38	1/2"	3/8"	3/8"
GF130-34-12-12	3/4"	1/2"	1/2"
GF130-34-12-34	3/4"	1/2"	3/4"
GF130-1-12-1	1"	1/2"	1"
GF130-1-34-12	1"	3/4"	1/2"
GF130-1-34-34	1"	3/4"	3/4"
GF130-1-34-1	1"	3/4"	1"
GF130-114-12-114	1.1/4"	1/2"	1.1/4"
GF130-114-1-12	1.1/4"	1"	1/2"
GF130-114-1-34	1.1/4"	1"	3/4"
GF130-114-1-1	1.1/4"	1"	1"
GF130-114-1-114	1.1/4"	1"	1.1/4"
GF130-112-12-112	1.1/2"	1/2"	1.1/2"
GF130-112-1-1	1.1/2"	1"	1"
GF130-112-1-112	1.1/2"	1"	1.1/2"
GF130-112-11412	1.1/2"	1.1/4"	1/2"
GF130-112-114-1	1.1/2"	1.1/4"	1"
GF130-112-114114	1.1/2"	1.1/4"	1.1/4"
GF130-2-12-2	2"	1/2"	2"
GF130-2-34-2	2"	3/4"	2"
GF130-2-1-2	2"	1"	2"
GF130-2-112-1	2"	1.1/2"	1"
GF130-2-112-114	2"	1.1/2"	1.1/4"
GF130-2-112-2	2"	1.1/2"	2"
GF130-212-112212	2.1/2"	1.1/2"	2.1/2"
GF130-212-2-2	2.1/2"	2"	2"
GF130-3-2-2	3"	2"	2"
Tech Sheet 1776			

Female Equal Pitcher Tee (131)



Black, BSPP Female

0217	Thread
GF131-12N	1/2"
GF131-34N	3/4"
GF131-1N	1"
GF131-114N	1.1/4"
GF131-112N	1.1/2"
GF131-2N	2"
GF131-212N	2.1/2"
GF131-3N	3"
GF131-4N	4"
Tech Sheet 1776	

Galvanised, BSPP Female

0217	Thread
GF131-12	1/2"
GF131-34	3/4"
GF131-1	1"
GF131-114	1.1/4"
GF131-112	1.1/2"
GF131-2	2"
GF131-212	2.1/2"
GF131-3	3"
Tech Sheet 1776	

FT PRO®



For **Flexible Rubber Bellows**
see page **1388**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Female Pitcher Tee, Reducing on Branch (131)




Black, BSPP

0217	Thread A	Thread B
GF131-34-12N	3/4"	1/2"
GF131-1-12N	1"	1/2"
GF131-1-34N	1"	3/4"
GF131-114-12N	1.1/4"	1/2"
GF131-114-34N	1.1/4"	3/4"
GF131-114-1N	1.1/4"	1"
GF131-112-34N	1.1/2"	3/4"
GF131-112-1N	1.1/2"	1"
GF131-112-114N	1.1/2"	1.1/4"
GF131-2-34N	2"	3/4"
GF131-2-1N	2"	1"
GF131-2-114N	2"	1.1/4"
GF131-2-112N	2"	1.1/2"
GF131-3-2N	3"	2"
Tech Sheet 1777		

Galvanised, BSPP

0217	Thread A	Thread B
GF131-34-12	3/4"	1/2"
GF131-1-12	1"	1/2"
GF131-1-34	1"	3/4"
GF131-114-12	1.1/4"	1/2"
GF131-114-34	1.1/4"	3/4"
GF131-114-1	1.1/4"	1"
GF131-112-34	1.1/2"	3/4"
GF131-112-1	1.1/2"	1"
GF131-112-114	1.1/2"	1.1/4"
GF131-2-34	2"	3/4"
GF131-2-1	2"	1"
GF131-2-114	2"	1.1/4"
GF131-2-112	2"	1.1/2"
GF131-212-114	2.1/2"	1.1/4"
GF131-3-2	3"	2"
Tech Sheet 1777		

Female Pitcher Tee, Reducing on Run/Branch (131)



Black, BSPP

0217	Thread A	Thread B	Thread C
GF131-34-12-12N	3/4"	1/2"	1/2"
GF131-1-34-34N	1"	3/4"	3/4"
Tech Sheet 1777			

Galvanised, BSPP

0217	Thread A	Thread B	Thread C
GF131-34-12-12	3/4"	1/2"	1/2"
GF131-1-34-34	1"	3/4"	3/4"
Tech Sheet 1777			

Female Equal Twin Elbow (132)



Black, BSPP Female

0217	Thread
GF132-12N	1/2"
GF132-34N	3/4"
GF132-1N	1"
GF132-114N	1.1/4"
GF132-112N	1.1/2"
GF132-2N	2"
Tech Sheet 1778	

Galvanised, BSPP Female

0217	Thread
GF132-12	1/2"
GF132-34	3/4"
GF132-1	1"
GF132-114	1.1/4"
GF132-112	1.1/2"
Tech Sheet 1778	

Female Equal Cross (180)



Black, BSPP Female

0217	Thread
GF180-12N	1/2"
GF180-34N	3/4"
GF180-1N	1"
GF180-114N	1.1/4"
GF180-112N	1.1/2"
GF180-2N	2"
GF180-212N	2.1/2"
GF180-3N	3"
GF180-4N	4"
Tech Sheet 1779	

Galvanised, BSPP Female

0217	Thread
GF180-12	1/2"
GF180-34	3/4"
GF180-1	1"
GF180-114	1.1/4"
GF180-112	1.1/2"
GF180-2	2"
GF180-212	2.1/2"
GF180-3	3"
GF180-4	4"
Tech Sheet 1779	

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Female Reducing Socket (240)



Black, BSPP Female

0217	Thread	Thread
GF240-14-18N *	1/4"	1/8"
GF240-38-14N *	3/8"	1/4"
GF240-12-14N	1/2"	1/4"
GF240-12-38N	1/2"	3/8"
GF240-34-38N	3/4"	3/8"
GF240-34-12N	3/4"	1/2"
GF240-1-12N	1"	1/2"
GF240-1-34N	1"	3/4"
GF240-114-12N	1.1/4"	1/2"
GF240-114-34N	1.1/4"	3/4"
GF240-114-1N	1.1/4"	1"
GF240-112-12N	1.1/2"	1/2"
GF240-112-34N	1.1/2"	3/4"
GF240-112-1N	1.1/2"	1"
GF240-112-114N	1.1/2"	1.1/4"
GF240-2-34N	2"	3/4"
GF240-2-1N	2"	1"
GF240-2-114N	2"	1.1/4"
GF240-2-112N	2"	1.1/2"
GF240-212-112N	2.1/2"	1.1/2"
GF240-212-2N	2.1/2"	2"
GF240-3-112N	3"	1.1/2"
GF240-3-2N	3"	2"
GF240-3-212N	3"	2.1/2"
GF240-4-2N	4"	2"
GF240-4-212N	4"	2.1/2"
GF240-4-3N	4"	3"
	Tech Sheet 1780	



Galvanised, BSPP Female

0217	Thread	Thread
GF240-14-18 *	1/4"	1/8"
GF240-38-14 *	3/8"	1/4"
GF240-12-14	1/2"	1/4"
GF240-34-38	3/4"	3/8"
GF240-34-12	3/4"	1/2"
GF240-1-12	1"	1/2"
GF240-1-34	1"	3/4"
GF240-114-12	1.1/4"	1/2"
GF240-114-34	1.1/4"	3/4"
GF240-114-1	1.1/4"	1"
GF240-112-12	1.1/2"	1/2"
GF240-112-34	1.1/2"	3/4"
GF240-112-1	1.1/2"	1"
GF240-112-114	1.1/2"	1.1/4"
GF240-2-34	2"	3/4"
GF240-2-1	2"	1"
GF240-2-114	2"	1.1/4"
GF240-2-112	2"	1.1/2"
GF240-212-112	2.1/2"	1.1/2"
GF240-212-2	2.1/2"	2"
GF240-3-112	3"	1.1/2"
GF240-3-2	3"	2"
GF240-3-212	3"	2.1/2"
GF240-4-2	4"	2"
GF240-4-212	4"	2.1/2"
GF240-4-3	4"	3"
	Tech Sheet 1780	

***These types of fittings are made of steel (galvanised finish – electro plated) and therefore unsuitable for potable water inst lations.**

FT PRO®



For **Pipeclamps Handrail Systems**
see page **1393**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Male x Female Reducing Bush (241)



Black, BSPT Male x BSPP Female

0217	Thread	Thread
GF241-14-18N*	1/4"	1/8"
GF241-38-18N*	3/8"	1/8"
GF241-38-14N*	3/8"	1/4"
GF241-12-18N	1/2"	1/8"
GF241-12-14N	1/2"	1/4"
GF241-12-38N	1/2"	3/8"
GF241-34-14N	3/4"	1/4"
GF241-34-38N	3/4"	3/8"
GF241-34-12N	3/4"	1/2"
GF241-1-14N	1"	1/4"
GF241-1-38N	1"	3/8"
GF241-1-12N	1"	1/2"
GF241-1-34N	1"	3/4"
GF241-114-38N	1.1/4"	3/8"
GF241-114-12N	1.1/4"	1/2"
GF241-114-34N	1.1/4"	3/4"
GF241-114-1N	1.1/4"	1"
GF241-112-38N	1.1/2"	3/8"
GF241-112-12N	1.1/2"	1/2"
GF241-112-34N	1.1/2"	3/4"
GF241-112-1N	1.1/2"	1"
GF241-112-114N	1.1/2"	1.1/4"
GF241-2-12N	2"	1/2"
GF241-2-34N	2"	3/4"
GF241-2-1N	2"	1"
GF241-2-114N	2"	1.1/4"
GF241-2-112N	2"	1.1/2"
GF241-212-1N	2.1/2"	1"
GF241-212-114N	2.1/2"	1.1/4"
GF241-212-112N	2.1/2"	1.1/2"
GF241-212-2N	2.1/2"	2"
GF241-3-1N	3"	1"
GF241-3-114N	3"	1.1/4"
GF241-3-112N	3"	1.1/2"
GF241-3-2N	3"	2"
GF241-3-212N	3"	2.1/2"
GF241-4-2N	4"	2"
GF241-4-212N	4"	2.1/2"
GF241-4-3N	4"	3"
GF241-6-4N	6"	4"
Tech Sheet 1781		



Galvanised, BSPT Male x BSPP Female

0217	Thread	Thread
GF241-14-18*	1/4"	1/8"
GF241-38-18*	3/8"	1/8"
GF241-38-14*	3/8"	1/4"
GF241-12-18	1/2"	1/8"
GF241-12-14	1/2"	1/4"
GF241-12-38	1/2"	3/8"
GF241-34-14	3/4"	1/4"
GF241-34-38	3/4"	3/8"
GF241-34-12	3/4"	1/2"
GF241-1-14	1"	1/4"
GF241-1-38	1"	3/8"
GF241-1-12	1"	1/2"
GF241-1-34	1"	3/4"
GF241-114-38	1.1/4"	3/8"
GF241-114-12	1.1/4"	1/2"
GF241-114-34	1.1/4"	3/4"
GF241-114-1	1.1/4"	1"
GF241-112-38	1.1/2"	3/8"
GF241-112-12	1.1/2"	1/2"
GF241-112-34	1.1/2"	3/4"
GF241-112-1	1.1/2"	1"
GF241-112-114	1.1/2"	1.1/4"
GF241-2-12	2"	1/2"
GF241-2-34	2"	3/4"
GF241-2-1	2"	1"
GF241-2-114	2"	1.1/4"
GF241-2-112	2"	1.1/2"
GF241-212-1	2.1/2"	1"
GF241-212-114	2.1/2"	1.1/4"
GF241-212-2	2.1/2"	2"
GF241-3-1	3"	1"
GF241-3-114	3"	1.1/4"
GF241-3-112	3"	1.1/2"
GF241-3-2	3"	2"
GF241-3-212	3"	2.1/2"
GF241-4-2	4"	2"
GF241-4-212	4"	2.1/2"
GF241-4-3	4"	3"
Tech Sheet 1781		

Male Reducing Hexagon Nipple (245)



Black, BSPT Male x BSPT Male

0217	Thread	Thread
GF245-14-18N*	1/4"	1/8"
GF245-38-14N*	3/8"	1/4"
GF245-12-14N	1/2"	1/4"
GF245-12-38N	1/2"	3/8"
GF245-34-38N	3/4"	3/8"
GF245-34-12N	3/4"	1/2"
GF245-1-12N	1"	1/2"
GF245-1-34N	1"	3/4"
GF245-114-34N	1.1/4"	3/4"
GF245-114-1N	1.1/4"	1"
GF245-112-1N	1.1/2"	1"
GF245-112-114N	1.1/2"	1.1/4"
GF245-2-1N	2"	1"
GF245-2-114N	2"	1.1/4"
GF245-2-112N	2"	1.1/2"
GF245-3-2N	3"	2"
Tech Sheet 1782		

Galvanised, BSPT Male x BSPT Male

0217	Thread	Thread
GF245-14-18*	1/4"	1/8"
GF245-38-14*	3/8"	1/4"
GF245-12-14	1/2"	1/4"
GF245-12-38	1/2"	3/8"
GF245-34-38	3/4"	3/8"
GF245-34-12	3/4"	1/2"
GF245-1-12	1"	1/2"
GF245-1-34	1"	3/4"
GF245-114-34	1.1/4"	3/4"
GF245-114-1	1.1/4"	1"
GF245-112-1	1.1/2"	1"
GF245-112-114	1.1/2"	1.1/4"
GF245-2-1	2"	1"
GF245-2-114	2"	1.1/4"
GF245-2-112	2"	1.1/2"
Tech Sheet 1782		

***These types of fittings are made of steel (galvanised finish – electro plated) and therefore unsuitable for potable water inst lations.**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Male x Female Reducing Socket (246)



Black, BSPT Male x BSPP Female

0217	Female Thread	Male Thread
GF246-34-12N	3/4"	1/2"
GF246-1-34N	1"	3/4"
GF246-114-1N	1.1/4"	1"
Tech Sheet 1783		

Galvanised, BSPT Male x BSPP Female

0217	Female Thread	Male Thread
GF246-1-34	1"	3/4"
GF246-114-1	1.1/4"	1"
Tech Sheet 1783		

Female Reducing Socket, Eccentric (260)



Black, BSPP Female x BSPP Female

0217	Thread	Thread
GF260-34-12N	3/4"	1/2"
GF260-1-12N	1"	1/2"
GF260-1-34N	1"	3/4"
GF260-114-12N	1.1/4"	1/2"
GF260-114-34N	1.1/4"	3/4"
GF260-114-1N	1.1/4"	1"
GF260-112-1N	1.1/2"	1"
GF260-112-114N	1.1/2"	1.1/4"
GF260-2-12N	2"	1/2"
GF260-2-1N	2"	1"
GF260-2-114N	2"	1.1/4"
GF260-2-112N	2"	1.1/2"
Tech Sheet 1784		

Galvanised, BSPP Female x BSPP Female

0217	Thread	Thread
GF260-34-12	3/4"	1/2"
GF260-1-12	1"	1/2"
GF260-1-34	1"	3/4"
GF260-114-12	1.1/4"	1/2"
GF260-114-34	1.1/4"	3/4"
GF260-114-1	1.1/4"	1"
GF260-112-1	1.1/2"	1"
GF260-112-114	1.1/2"	1.1/4"
GF260-2-12	2"	1/2"
GF260-2-1	2"	1"
GF260-2-114	2"	1.1/4"
GF260-2-112	2"	1.1/2"
Tech Sheet 1784		

Female Equal Socket (270)



Black, BSPP Female

0217	Thread
GF270-18N*	1/8"
GF270-14N*	1/4"
GF270-38N	3/8"
GF270-12N	1/2"
GF270-34N	3/4"
GF270-1N	1"
GF270-114N	1.1/4"
GF270-112N	1.1/2"
GF270-2N	2"
GF270-212N	2.1/2"
GF270-3N	3"
GF270-4N	4"
Tech Sheet 1785	

Galvanised, BSPP Female

0217	Thread
GF270-18*	1/8"
GF270-14*	1/4"
GF270-38	3/8"
GF270-12	1/2"
GF270-34	3/4"
GF270-1	1"
GF270-114	1.1/4"
GF270-112	1.1/2"
GF270-2	2"
GF270-212	2.1/2"
GF270-3	3"
GF270-4	4"
Tech Sheet 1785	

***These types of fittings are made of steel (galvanised finish – electro plated) and therefore unsuitable for potable water inst lations.**

FT PRO®



For **Disability Access** see page **1398**

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Male Equal Hexagon Nipple (280)




Black, BSPT Male

0217	Thread
GF280-18N*	1/8"
GF280-14N*	1/4"
GF280-38N	3/8"
GF280-12N	1/2"
GF280-34N	3/4"
GF280-1N	1"
GF280-114N	1.1/4"
GF280-112N	1.1/2"
GF280-2N	2"
GF280-212N	2.1/2"
GF280-3N	3"
GF280-4N	4"
Tech Sheet 1786	

Galvanised, BSPT Male

0217	Thread
GF280-18*	1/8"
GF280-14*	1/4"
GF280-38	3/8"
GF280-12	1/2"
GF280-34	3/4"
GF280-1	1"
GF280-114	1.1/4"
GF280-112	1.1/2"
GF280-2	2"
GF280-212	2.1/2"
GF280-3	3"
GF280-4	4"
Tech Sheet 1786	

Plug, Beaded Hollow (290)



Black

0217	Thread
GF290-14N	1/4"
GF290-38N	3/8"
GF290-12N	1/2"
GF290-34N	3/4"
GF290-1N	1"
GF290-114N	1.1/4"
GF290-112N	1.1/2"
GF290-2N	2"
Tech Sheet 1787	

Galvanised

0217	Thread
GF290-14	1/4"
GF290-38	3/8"
GF290-12	1/2"
GF290-34	3/4"
GF290-1	1"
GF290-114	1.1/4"
GF290-112	1.1/2"
GF290-2	2"
Tech Sheet 1787	

Plug, Plain Hollow (291)



Black, BSPT

0217	Thread
GF291-12N	1/2"
GF291-34N	3/4"
GF291-1N	1"
GF291-114N	1.1/4"
GF291-112N	1.1/2"
GF291-2N	2"
GF291-212N	2.1/2"
GF291-3N	3"
GF291-4N	4"
Tech Sheet 1788	

Galvanised, BSPT

0217	Thread
GF291-12	1/2"
GF291-34	3/4"
GF291-1	1"
GF291-114	1.1/4"
GF291-112	1.1/2"
GF291-2	2"
GF291-212	2.1/2"
GF291-3	3"
GF291-4	4"
Tech Sheet 1788	

***These types of fittings are made of steel (galvanised finish – electro plated) and therefore unsuitable for potable water installations.**

NORMA



For **Pipe Repair Couplings** see page **1557**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

+GF+

Plug, Plain Solid (291S)




Black, BSPT

0217	Thread
GF291S-18N*	1/8"
GF291S-14N*	1/4"
GF291S-12N	1/2"
GF291S-34N	3/4"
GF291S-1N	1"
GF291S-114N	1.1/4"
GF291S-112N	1.1/2"
GF291S-2N	2"
Tech Sheet 1788	

Galvanised, BSPT

0217	Thread
GF291S-14	1/4"
GF291S-38	3/8"
GF291S-12	1/2"
GF291S-34	3/4"
GF291S-1	1"
GF291S-114	1.1/4"
GF291S-112	1.1/2"
GF291S-2	2"
Tech Sheet 1788	

Cap (300)



Black, BSPP

0217	Thread
GF300-14N	1/4"
GF300-38N	3/8"
GF300-12N	1/2"
GF300-34N	3/4"
GF300-1N	1"
GF300-114N	1.1/4"
GF300-112N	1.1/2"
GF300-2N	2"
GF300-212N	2.1/2"
GF300-3N	3"
GF300-4N	4"
Tech Sheet 1789	

Galvanised, BSPP

0217	Thread
GF300-14	1/4"
GF300-12	1/2"
GF300-34	3/4"
GF300-1	1"
GF300-114	1.1/4"
GF300-112	1.1/2"
GF300-2	2"
GF300-212	2.1/2"
GF300-3	3"
GF300-4	4"
Tech Sheet 1789	

Backnut, Recessed (312)




Black

0217	Thread
GF312-14N*	1/4"
GF312-12N	1/2"
GF312-34N	3/4"
GF312-1N	1"
GF312-114N	1.1/4"
GF312-112N	1.1/2"
GF312-2N	2"
Tech Sheet 1790	

Galvanised

0217	Thread
GF312-38*	3/8"
GF312-12	1/2"
GF312-34	3/4"
GF312-1	1"
GF312-114	1.1/4"
GF312-112	1.1/2"
GF312-2	2"
Tech Sheet 1790	

Flange, Undrilled (321)



Black

0217	Thread
GF321-12N	1/2"
GF321-1N	1"
GF321-114N	1.1/4"
GF321-112N	1.1/2"
GF321-2N	2"
Tech Sheet 1790	

Galvanised

0217	Thread
GF321-34	3/4"
GF321-1	1"
GF321-114	1.1/4"
GF321-112	1.1/2"
Tech Sheet 1790	

***These types of fittings are made of steel (galvanised finish – electro plated) and therefore unsuitable for potable water installations.**

M-Press Fittings Ltd



For **Stainless Steel Press Fit Piping System**
see pages **1118-1126**

FAC
Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

Plug, Recessed (596)




Black, BSPT

0217	Thread
GF596-14N	1/4"
GF596-38N	3/8"
GF596-12N	1/2"
GF596-34N	3/4"
GF596-1N	1"
GF596-114N	1.1/4"
GF596-112N	1.1/2"
GF596-2N	2"
Tech Sheet 20758	

Galvanised, BSPT

0217	Thread
GF596-14	1/4"
GF596-38	3/8"
GF596-12	1/2"
GF596-34	3/4"
GF596-1	1"
GF596-114	1.1/4"
GF596-112	1.1/2"
Tech Sheet 20758	

Female Equal Union, Flat Seat (330)




Black, BSPP Female

0217	Thread
GF330-12N	1/2"
GF330-34N	3/4"
GF330-1N	1"
GF330-114N	1.1/4"
GF330-112N	1.1/2"
GF330-2N	2"
Tech Sheet 1791	

Galvanised, BSPP Female

0217	Thread
GF330-12	1/2"
GF330-34	3/4"
GF330-1	1"
GF330-114	1.1/4"
GF330-112	1.1/2"
GF330-2	2"
Tech Sheet 1791	

Female Equal Union, Iron to Iron, Taper Seat (340)



Black, BSPP Female

0217	Thread
GF340-14N	1/4"
GF340-38N	3/8"
GF340-12N	1/2"
GF340-34N	3/4"
GF340-1N	1"
GF340-114N	1.1/4"
GF340-112N	1.1/2"
GF340-2N	2"
GF340-212N	2.1/2"
GF340-4N	4"
Tech Sheet 1792	

Galvanised, BSPP Female

0217	Thread
GF340-14	1/4"
GF340-38	3/8"
GF340-12	1/2"
GF340-34	3/4"
GF340-1	1"
GF340-114	1.1/4"
GF340-112	1.1/2"
GF340-2	2"
GF340-212	2.1/2"
GF340-3	3"
GF340-4	4"
Tech Sheet 1792	

Male x Female Equal Union, Iron to Iron, Taper Seat (341)




Black, BSPT Male x BSPP Female

0217	Thread
GF341-14N	1/4"
GF341-38N	3/8"
GF341-12N	1/2"
GF341-34N	3/4"
GF341-1N	1"
GF341-114N	1.1/4"
GF341-112N	1.1/2"
GF341-2N	2"
GF341-3N	3"
Tech Sheet 1792	

Galvanised, BSPT Male x BSPP Female

0217	Thread
GF341-14	1/4"
GF341-38	3/8"
GF341-12	1/2"
GF341-34	3/4"
GF341-1	1"
GF341-114	1.1/4"
GF341-112	1.1/2"
GF341-2	2"
GF341-212	2.1/2"
GF341-3	3"
Tech Sheet 1792	

FT PRO®




For **Wrought Iron Sockets** see page **1385**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

+GF+

Female Equal Union, Bronze to Iron, Spherical Seat (342)




Black, BSPP Female

0217	Thread
GF342-12N	1/2"
GF342-34N	3/4"
GF342-1N	1"
GF342-114N	1.1/4"
GF342-112N	1.1/2"
GF342-2N	2"
Tech Sheet 1793	

Galvanised, BSPP Female

0217	Thread
GF342-12	1/2"
GF342-34	3/4"
GF342-1	1"
GF342-114	1.1/4"
GF342-112	1.1/2"
GF342-2	2"
Tech Sheet 1793	

Female Equal Mac Union, 2 Spherical Seats (346)




Black, BSPP Female

0217	Thread
GF346-12N	1/2"
GF346-34N	3/4"
GF346-1N	1"
GF346-114N	1.1/4"
GF346-112N	1.1/2"
GF346-2N	2"
Tech Sheet 1794	

Galvanised, BSPP Female

0217	Thread
GF346-12	1/2"
GF346-34	3/4"
GF346-1	1"
GF346-114	1.1/4"
GF346-112	1.1/2"
GF346-2	2"
Tech Sheet 1794	

Female Equal Union, Navy Pattern, Bronze to Bronze, Spherical Seat (342a)



Black, BSPP Female

0217	Thread
GF342A-12N	1/2"
GF342A-34N	3/4"
GF342A-1N	1"
GF342A-114N	1.1/4"
GF342A-112N	1.1/2"
GF342A-2N	2"
Tech Sheet 1793	

Galvanised, BSPP Female

0217	Thread
GF342A-12	1/2"
GF342A-34	3/4"
GF342A-1	1"
GF342A-114	1.1/4"
GF342A-112	1.1/2"
GF342A-2	2"
Tech Sheet 1793	

RUST-OLEUM®



For **X1 Maintenance Sprays**
see page **1568**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

CRANE


Material:
Crane malleable iron is of the Blackheart type ideally suited to pipe fitting and manufacture and conforms to BSEN1562 Designation EN-GJMB-300-6, ASTM A197 and ISO 5922.

Galvanised Finish:
Hot dip zinc coated (galvanised) prior to machining. Coating conforms to BSEN ISO1461 1998 and ASTM 153.

Thread:
Taper threads to BS21 (ISO 7)

Media:
Suitable for transfer or flow of wate , steam, gas and other non aggressive media.

- BSI Kitemark approved
- PN25



Hexagon Nipple (Fig 144)




Black, BSPT

1091	Thread
C144-12N	1/2"
C144-34N	3/4"
C144-1N	1"
C144-114N	1.1/4"
C144-112N	1.1/2"
C144-2N	2"
C144-212N	2.1/2"
C144-3N	3"
C144-4N	4"
Tech Sheet 10655	

Galvanised, BSPT

1091	Thread
C144-14	1/4"
C144-38	3/8"
C144-12	1/2"
C144-34	3/4"
C144-1	1"
C144-114	1.1/4"
C144-112	1.1/2"
C144-2	2"
C144-212	2.1/2"
C144-3	3"
C144-4	4"
Tech Sheet 10655	

Hexagon Reducing Nipple (Fig 145)



Black, BSPT

1091	Thread	Thread
C145-34-12N	3/4"	1/2"
C145-1-12N	1"	1/2"
C145-1-34N	1"	3/4"
C145-114-1N	1.1/4"	1"
C145-2-114N	2"	1.1/4"
C145-2-112N	2"	1.1/2"
Tech Sheet 10655		

Galvanised, BSPT

1091	Thread	Thread
C145-34-12	3/4"	1/2"
C145-1-12	1"	1/2"
C145-1-34	1"	3/4"
C145-114-1	1.1/4"	1"
C145-112-114	1.1/2"	1.1/4"
C145-2-1	2"	1"
C145-2-112	2"	1.1/2"
Tech Sheet 10655		

Male x Female Equal Union (Fig 257)



Black, BSPT

1091	Thread
C257-12N	1/2"
C257-34N	3/4"
C257-1N	1"
C257-114N	1.1/4"
C257-112N	1.1/2"
C257-2N	2"
Tech Sheet 20764	

Galvanised, BSPT

1091	Thread
C257-12	1/2"
C257-34	3/4"
C257-1	1"
C257-114	1.1/4"
C257-112	1.1/2"
C257-2	2"
Tech Sheet 20764	

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS


CRANE

Hexagon Bush (Fig 140)



Black, BSPT

1091	Male Thread	Female Thread
C140-12-18N	1/2"	1/8"
C140-12-14N	1/2"	1/4"
C140-12-38N	1/2"	3/8"
C140-34-18N	3/4"	1/8"
C140-34-14N	3/4"	1/4"
C140-34-38N	3/4"	3/8"
C140-34-12N	3/4"	1/2"
C140-1-14N	1"	1/4"
C140-1-38N	1"	3/8"
C140-1-12N	1"	1/2"
C140-1-34N	1"	3/4"
C140-114-34N	1.1/4"	3/4"
C140-114-1N	1.1/4"	1"
C140-112-12N	1.1/2"	1/2"
C140-112-34N	1.1/2"	3/4"
C140-112-1N	1.1/2"	1"
C140-112-114N	1.1/2"	1.1/4"
C140-2-12N	2"	1/2"
C140-2-34N	2"	3/4"
C140-2-1N	2"	1"
C140-2-114N	2"	1.1/4"
C140-2-112N	2"	1.1/2"
C140-212-12N	2.1/2"	1/2"
C140-212-1N	2.1/2"	1"
C140-212-114N	2.1/2"	1.1/4"
C140-212-112N	2.1/2"	1.1/2"
C140-212-2N	2.1/2"	2"
C140-3-114N	3"	1.1/4"
C140-3-112N	3"	1.1/2"
C140-3-2N	3"	2"
C140-3-212N	3"	2.1/2"
C140-4-2N	4"	2"
C140-4-212N	4"	2.1/2"
C140-4-3N	4"	3"
Tech Sheet 10671		




Galvanised, BSPT

1091	Male Thread	Female Thread
C140-14-18	1/4"	1/8"
C140-38-18	3/8"	1/8"
C140-12-18	1/2"	1/8"
C140-12-14	1/2"	1/4"
C140-12-38	1/2"	3/8"
C140-34-18	3/4"	1/8"
C140-34-14	3/4"	1/4"
C140-34-38	3/4"	3/8"
C140-34-12	3/4"	1/2"
C140-1-14	1"	1/4"
C140-1-38	1"	3/8"
C140-1-12	1"	1/2"
C140-1-34	1"	3/4"
C140-114-12	1.1/4"	1/2"
C140-114-34	1.1/4"	3/4"
C140-114-1	1.1/4"	1"
C140-112-12	1.1/2"	1/2"
C140-112-34	1.1/2"	3/4"
C140-112-1	1.1/2"	1"
C140-112-114	1.1/2"	1.1/4"
C140-2-12	2"	1/2"
C140-2-34	2"	3/4"
C140-2-1	2"	1"
C140-2-114	2"	1.1/4"
C140-2-112	2"	1.1/2"
C140-212-12	2.1/2"	1/2"
C140-212-114	2.1/2"	1.1/4"
C140-212-112	2.1/2"	1.1/2"
C140-212-2	2.1/2"	2"
C140-3-1	3"	1"
C140-3-112	3"	1.1/2"
C140-3-2	3"	2"
C140-3-212	3"	2.1/2"
C140-4-2	4"	2"
C140-4-3	4"	3"
Tech Sheet 10671		

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Female Equal Socket (Fig 176)



Black, BSPP

1091	Thread
C176-12N	1/2"
C176-34N	3/4"
C176-1N	1"
C176-114N	1.1/4"
C176-112N	1.1/2"
C176-2N	2"
Tech Sheet 10670	

Galvanised, BSPP

1091	Thread
C176-12	1/2"
C176-34	3/4"
C176-1	1"
C176-114	1.1/4"
C176-112	1.1/2"
C176-2	2"
Tech Sheet 10670	

Female Equal Socket (Fig 177)



Black, BSPT

1091	Thread
C177-12N	1/2"
C177-34N	3/4"
C177-1N	1"
C177-114N	1.1/4"
C177-112N	1.1/2"
C177-2N	2"
C177-212N	2.1/2"
C177-3N	3"
Tech Sheet 10670	


Galvanised, BSPT

1091	Thread
C177-12	1/2"
C177-34	3/4"
C177-1	1"
C177-114	1.1/4"
C177-112	1.1/2"
C177-2	2"
Tech Sheet 10670	

MALLEABLE IRON FITTINGS

CRANE

Reducing Socket (Fig 179)



Black, BSPT

1091	Thread	Thread
C179-34-12N	3/4"	1/2"
C179-1-12N	1"	1/2"
C179-1-34N	1"	3/4"
C179-114-12N	1.1/4"	1/2"
C179-114-1N	1.1/4"	1"
C179-112-1N	1.1/2"	1"
C179-112-114N	1.1/2"	1.1/4"
C179-2-1N	2"	1"
C179-2-114N	2"	1.1/4"
C179-2-112N	2"	1.1/2"
Tech Sheet 20774		

Galvanised, BSPT

1091	Thread	Thread
C179-12-38	1/2"	3/8"
C179-34-12	3/4"	1/2"
C179-1-12	1"	1/2"
C179-1-34	1"	3/4"
C179-114-34	1.1/4"	3/4"
C179-114-1	1.1/4"	1"
C179-112-1	1.1/2"	1"
C179-112-114	1.1/2"	1.1/4"
C179-2-1	2"	1"
C179-2-114	2"	1.1/4"
C179-2-112	2"	1.1/2"
Tech Sheet 20774		

Female Equal Union, Spherical Seat Iron to Iron (Fig 256)



Black, BSPT

1091	Thread
C256-12N	1/2"
C256-34N	3/4"
C256-1N	1"
C256-114N	1.1/4"
C256-112N	1.1/2"
C256-2N	2"
C256-212N	2.1/2"
C256-3N	3"
Tech Sheet 20765	

Galvanised, BSPT

1091	Thread
C256-12	1/2"
C256-34	3/4"
C256-1	1"
C256-114	1.1/4"
C256-112	1.1/2"
C256-2	2"
C256-212	2.1/2"
C256-3	3"
Tech Sheet 20765	

Female Equal Union, Spherical Seat Bronze to Bronze (Fig 289)



Black, BSPT

1091	Thread
C289-12N	1/2"
C289-34N	3/4"
C289-1N	1"
C289-114N	1.1/4"
C289-112N	1.1/2"
C289-2N	2"
C289-212N	2.1/2"
Tech Sheet 20768	

Galvanised, BSPT

1091	Thread
C289-12	1/2"
C289-34	3/4"
C289-1	1"
C289-112	1.1/2"
C289-2	2"
Tech Sheet 20768	

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

FT PRO®

For **Ball Valves** see pages **922-926**




Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

CRANE

Plain Plug, Hollow (Fig 147)



Black, BSPT

1091	Thread
C147-12N	1/2"
C147-34N	3/4"
C147-1N	1"
C147-114N	1.1/4"
C147-112N	1.1/2"
C147-2N	2"
C147-212N	2.1/2"
C147-3N	3"
C147-4N	4"
Tech Sheet 10672	

Galvanised, BSPT

1091	Thread
C147-12	1/2"
C147-34	3/4"
C147-1	1"
C147-114	1.1/4"
C147-112	1.1/2"
C147-2	2"
C147-212	2.1/2"
C147-3	3"
C147-4	4"
Tech Sheet 10672	

Cap (Fig 185)



Black, BSPT

1091	Thread
C185-12N	1/2"
C185-34N	3/4"
C185-1N	1"
C185-114N	1.1/4"
C185-112N	1.1/2"
C185-2N	2"
C185-212N	2.1/2"
Tech Sheet 10646	

Galvanised, BSPT

1091	Thread
C185-12	1/2"
C185-34	3/4"
C185-1	1"
C185-112	1.1/2"
C185-2	2"
Tech Sheet 10646	

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Male x Female Equal Elbow (Fig 152)



Black, BSPT

1091	Thread
C152-14N	1/4"
C152-12N	1/2"
C152-34N	3/4"
C152-1N	1"
C152-114N	1.1/4"
C152-112N	1.1/2"
C152-2N	2"
C152-212N	2.1/2"
C152-3N	3"
Tech Sheet 10673	

Galvanised, BSPT

1091	Thread
C152-12	1/2"
C152-34	3/4"
C152-1	1"
C152-114	1.1/4"
C152-112	1.1/2"
C152-2	2"
Tech Sheet 10673	

Male x Female Reducing Elbow (Fig 152)



Black, BSPT

1091	Male Thread	Female Thread
C152-34-12N	3/4"	1/2"
Tech Sheet 20759		

Galvanised, BSPT

1091	Male Thread	Female Thread
C152-34-12	3/4"	1/2"
Tech Sheet 20759		

MALLEABLE IRON FITTINGS

CRANE

Female Equal Elbow (Fig 151)



Black, BSPT

1091	Thread
C151-12N	1/2"
C151-34N	3/4"
C151-1N	1"
C151-114N	1.1/4"
C151-112N	1.1/2"
C151-2N	2"
C151-212N	2.1/2"
C151-3N	3"
C151-4N	4"
Tech Sheet 10675	

Galvanised, BSPT

1091	Thread
C151-12	1/2"
C151-34	3/4"
C151-1	1"
C151-114	1.1/4"
C151-112	1.1/2"
C151-2	2"
C151-212	2.1/2"
C151-3	3"
Tech Sheet 10675	

Female Reducing Elbow (Fig 151)



Black, BSPT

1091	Thread	Thread
C151-1-12N	1"	1/2"
Tech Sheet 20760		

Galvanised, BSPT

1091	Thread	Thread
C151-1-12	1"	1/2"
C151-114-1	1.1/4"	1"
Tech Sheet 20760		

Male x Female Equal Bend (Fig 192)



Black, BSPT

1091	Thread
C192-12N	1/2"
C192-34N	3/4"
C192-1N	1"
C192-114N	1.1/4"
C192-112N	1.1/2"
C192-2N	2"
Tech Sheet 10643	

Galvanised, BSPT

1091	Thread
C192-14	1/4"
Tech Sheet 10643	

Female Equal Bend (Fig 193)




Black, BSPT

1091	Thread
C193-12N	1/2"
C193-34N	3/4"
C193-1N	1"
C193-112N	1.1/2"
C193-2N	2"
C193-212N	2.1/2"
Tech Sheet 10643	

Galvanised, BSPT

1091	Thread
C193-12	1/2"
C193-34	3/4"
C193-1	1"
C193-114	1.1/4"
C193-112	1.1/2"
C193-2	2"
C193-212	2.1/2"
C193-3	3"
Tech Sheet 10643	

Male x Female Equal 45º (Fig 156)



Black, BSPT

1091	Thread
C156-12N	1/2"
C156-34N	3/4"
C156-1N	1"
C156-114N	1.1/4"
C156-112N	1.1/2"
C156-2N	2"
Tech Sheet 10644	

Galvanised, BSPT

1091	Thread
C156-12	1/2"
C156-34	3/4"
C156-1	1"
C156-114	1.1/4"
C156-112	1.1/2"
C156-2	2"
Tech Sheet 10644	

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

CRANE

Female Equal 45º (Fig 155)



Black, BSPT

1091	Thread
C155-12N	1/2"
C155-34N	3/4"
C155-1N	1"
C155-114N	1.1/4"
C155-112N	1.1/2"
C155-2N	2"
C155-3N	3"
Tech Sheet 10674	

Galvanised, BSPT

1091	Thread
C155-12	1/2"
C155-34	3/4"
C155-1	1"
C155-114	1.1/4"
C155-112	1.1/2"
C155-2	2"
Tech Sheet 10674	

Female Equal Tee (Fig 161)




Black, BSPT

1091	Thread
C161-14N	1/4"
C161-38N	3/8"
C161-12N	1/2"
C161-34N	3/4"
C161-1N	1"
C161-114N	1.1/4"
C161-112N	1.1/2"
C161-212N	2.1/2"
C161-3N	3"
C161-4N	4"
Tech Sheet 10650	

Galvanised, BSPT

1091	Thread
C161-12	1/2"
C161-34	3/4"
C161-1	1"
C161-114	1.1/4"
C161-112	1.1/2"
C161-2	2"
C161-212	2.1/2"
C161-3	3"
C161-4	4"
Tech Sheet 10650	

Unequal Reducing Branch Tee (Fig 161)



Black, BSPT

1091	Thread A	Thread B
C161-12-14N	1/2"	1/4"
C161-1-12N	1"	1/2"
C161-1-34N	1"	3/4"
C161-114-12N	1.1/4"	1/2"
C161-114-1N	1.1/4"	1"
C161-112-12N	1.1/2"	1/2"
C161-112-34N	1.1/2"	3/4"
C161-112-1N	1.1/2"	1"
C161-112-114N	1.1/2"	1.1/4"
C161-2-1N	2"	1"
C161-2-114N	2"	1.1/4"
Tech Sheet 10650		

Galvanised, BSPT

1091	Thread A	Thread B
C161-34-12	3/4"	1/2"
C161-1-12	1"	1/2"
C161-1-34	1"	3/4"
C161-114-12	1.1/4"	1/2"
C161-114-34	1.1/4"	3/4"
C161-114-1	1.1/4"	1"
C161-112-12	1.1/2"	1/2"
C161-112-34	1.1/2"	3/4"
C161-112-1	1.1/2"	1"
C161-2-12	2"	1/2"
C161-2-1	2"	1"
C161-2-114	2"	1.1/4"
C161-2-112	2"	1.1/2"
C161-3-2	3"	2"
Tech Sheet 10650		

CRANE

Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT

Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

FT PRO



For **Fire Hose Reels & Accessories** see page **1466**

MALLEABLE IRON FITTINGS

CRANE


Twin Elbow (Fig 197)



Black, BSPT

1091	Thread
C197-12N	1/2"
C197-34N	3/4"
C197-1N	1"
C197-112N	1.1/2"
C197-2N	2"
Tech Sheet 10643	

Female Equal Pitcher Tee (Fig 199) BS EN 10242



Black, BSPT

1091	Thread
C199-12N	1/2"
C199-34N	3/4"
C199-1N	1"
C199-112N	1.1/2"
C199-2N	2"
Tech Sheet 10649	

Galvanised, BSPT

1091	Thread
C199-12	1/2"
C199-34	3/4"
C199-1	1"
C199-114	1.1/4"
C199-112	1.1/2"
C199-2	2"
Tech Sheet 10649	

School Board Pipe Bracket (Fig 501)



Black

1091	Tube Nominal
CSB14N	1/4"
CSB12N	1/2"
CSB34N	3/4"
CSB1N	1"
CSB112N	1.1/2"
CSB2N	2"
CSB212N	2.1/2"
CSB3N	3"
CSB4N	4"

Galvanised

1091	Tube Nominal
CSB14	1/4"
CSB38	3/8"
CSB12	1/2"
CSB34	3/4"
CSB1	1"
CSB114	1.1/4"
CSB112	1.1/2"
CSB2	2"
CSB3	3"
CSB4	4"

Single Metric Tapping Pipe Ring (Fig 529M)



Black, BS3643

1091	Tube Nominal	Thread
C529M-38N	3/8"	M10
C529M-12N	1/2"	M10
C529M-34N	3/4"	M10
C529M-1N	1"	M10
C529M-114N	1.1/4"	M10
C529M-112N	1.1/2"	M10
C529M-2N	2"	M10
C529M-212N	2.1/2"	M12
C529M-3N	3"	M12
C529M-4N	4"	M12

Galvanised, BS3643

1091	Tube Nominal	Thread
C529M-38	3/8"	M10
C529M-12	1/2"	M10
C529M-1	1"	M10
C529M-114	1.1/4"	M10
C529M-112	1.1/2"	M10
C529M-2	2"	M10
C529M-212	2.1/2"	M12
C529M-3	3"	M12
C529M-4	4"	M12

Double Metric Tapping Pipe Ring (Fig 530M)



Black, BS3643

1091	Tube Nominal	Thread
C530M-34N	3/4"	M10
C530M-1N	1"	M10
C530M-114N	1.1/4"	M10

Galvanised, BS3643

1091	Tube Nominal	Thread
C530M-1	1"	M10
C530M-114	1.1/4"	M10
C530M-112	1.1/2"	M10

CRANE Malleable Iron Fittings Suitable for Use with Drinking Water.

WRAS APPROVED PRODUCT Crane kitemarked fittings are deemed to satisfy the requirements of the United Kingdom Water Regulations (Byelaws).

Fluid-Air Components Ltd

RIDGID




See pages 1742-1746

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Medium-duty Malleable Iron Barrel Nipples



Galvanised, BSPT

0305	Thread	Length mm
MIB-18X60	1/8"	60
MIB-18X80	1/8"	80
MIB-14X40	1/4"	40
MIB-14X60	1/4"	60
MIB-14X80	1/4"	80
MIB-14X100	1/4"	100
MIB-14X120	1/4"	120
MIB-14X150	1/4"	150
MIB-14X180	1/4"	180
MIB-14X200	1/4"	200
MIB-14X250	1/4"	250
MIB-14X300	1/4"	300
MIB-38X40	3/8"	40
MIB-38X50	3/8"	50
MIB-38X60	3/8"	60
MIB-38X80	3/8"	80
MIB-38X100	3/8"	100
MIB-38X120	3/8"	120
MIB-38X150	3/8"	150
MIB-38X180	3/8"	180
MIB-38X200	3/8"	200
MIB-38X250	3/8"	250
MIB-38X300	3/8"	300
MIB-12X30	1/2"	30
MIB-12X40	1/2"	40
MIB-12X50	1/2"	50
MIB-12X60	1/2"	60
MIB-12X80	1/2"	80
MIB-12X100	1/2"	100

0305	Thread	Length mm
MIB-12X120	1/2"	120
MIB-12X150	1/2"	150
MIB-12X180	1/2"	180
MIB-12X200	1/2"	200
MIB-12X250	1/2"	250
MIB-12X300	1/2"	300
MIB-34X30	3/4"	30
MIB-34X40	3/4"	40
MIB-34X60	3/4"	60
MIB-34X70	3/4"	70
MIB-34X80	3/4"	80
MIB-34X100	3/4"	100
MIB-34X120	3/4"	120
MIB-34X150	3/4"	150
MIB-34X180	3/4"	180
MIB-34X200	3/4"	200
MIB-34X250	3/4"	250
MIB-34X300	3/4"	300
MIB-34X1000	3/4"	1000
MIB-34X1500	3/4"	1500
MIB-1X30	1"	30
MIB-1X40	1"	40
MIB-1X50	1"	50
MIB-1X60	1"	60
MIB-1X70	1"	70
MIB-1X80	1"	80
MIB-1X100	1"	100
MIB-1X120	1"	120
MIB-1X150	1"	150

0305	Thread	Length mm
MIB-1X180	1"	180
MIB-1X200	1"	200
MIB-1X250	1"	250
MIB-1X300	1"	300
MIB-114X80	1.1/4"	80
MIB-114X100	1.1/4"	100
MIB-114X120	1.1/4"	120
MIB-114X125	1.1/4"	125
MIB-114X150	1.1/4"	150
MIB-114X180	1.1/4"	180
MIB-114X200	1.1/4"	200
MIB-114X250	1.1/4"	250
MIB-114X300	1.1/4"	300
MIB-112X80	1.1/2"	80
MIB-112X100	1.1/2"	100
MIB-112X120	1.1/2"	120
MIB-112X150	1.1/2"	150
MIB-112X180	1.1/2"	180
MIB-112X200	1.1/2"	200
MIB-112X250	1.1/2"	250
MIB-112X300	1.1/2"	300
MIB-2X80	2"	80
MIB-2X100	2"	100
MIB-2X120	2"	120
MIB-2X150	2"	150
MIB-2X180	2"	180
MIB-2X200	2"	200
MIB-2X250	2"	250
MIB-2X300	2"	300

You might also need...


PORTWEST

For **Portwest PPE**
see pages **1752-1760**



Fluid-Air Components Ltd

Medium-duty Malleable Iron Barrel Nipples



Black, BSPT


0305	Thread	Length mm
MIB-14X40N	1/4"	40
MIB-14X60N	1/4"	60
MIB-14X80N	1/4"	80
MIB-14X100N	1/4"	100
MIB-14X120N	1/4"	120
MIB-14X150N	1/4"	150
MIB-14X180N	1/4"	180
MIB-14X200N	1/4"	200
MIB-14X250N	1/4"	250
MIB-14X300N	1/4"	300
MIB-38X30N	3/8"	30
MIB-38X40N	3/8"	40
MIB-38X60N	3/8"	60
MIB-38X80N	3/8"	80
MIB-38X100N	3/8"	100
MIB-38X120N	3/8"	120
MIB-38X150N	3/8"	150
MIB-38X180N	3/8"	180
MIB-38X200N	3/8"	200
MIB-38X250N	3/8"	250
MIB-38X300N	3/8"	300
MIB-12X30N	1/2"	30
MIB-12X40N	1/2"	40
MIB-12X60N	1/2"	60
MIB-12X80N	1/2"	80
MIB-12X100N	1/2"	100
MIB-12X120N	1/2"	120
MIB-12X150N	1/2"	150
MIB-12X180N	1/2"	180
MIB-12X200N	1/2"	200
MIB-12X250N	1/2"	250
MIB-12X300N	1/2"	300
MIB-34X40N	3/4"	40

0305	Thread	Length mm
MIB-34X60N	3/4"	60
MIB-34X80N	3/4"	80
MIB-34X100N	3/4"	100
MIB-34X120N	3/4"	120
MIB-34X150N	3/4"	150
MIB-34X180N	3/4"	180
MIB-34X200N	3/4"	200
MIB-34X250N	3/4"	250
MIB-34X300N	3/4"	300
MIB-1X40N	1"	40
MIB-1X60N	1"	60
MIB-1X80N	1"	80
MIB-1X100N	1"	100
MIB-1X120N	1"	120
MIB-1X150N	1"	150
MIB-1X180N	1"	180
MIB-1X200N	1"	200
MIB-1X250N	1"	250
MIB-1X300N	1"	300
MIB-114X60N	1.1/4"	60
MIB-114X80N	1.1/4"	80
MIB-114X100N	1.1/4"	100
MIB-114X120N	1.1/4"	120
MIB-114X150N	1.1/4"	150
MIB-114X180N	1.1/4"	180
MIB-114X200N	1.1/4"	200
MIB-114X250N	1.1/4"	250
MIB-114X300N	1.1/4"	300
MIB-112X60N	1.1/2"	60
MIB-112X80N	1.1/2"	80
MIB-112X100N	1.1/2"	100
MIB-112X120N	1.1/2"	120
MIB-112X150N	1.1/2"	150

0305	Thread	Length mm
MIB-112X180N	1.1/2"	180
MIB-112X200N	1.1/2"	200
MIB-112X250N	1.1/2"	250
MIB-112X300N	1.1/2"	300
MIB-2X80N	2"	80
MIB-2X100N	2"	100
MIB-2X120N	2"	120
MIB-2X150N	2"	150
MIB-2X180N	2"	180
MIB-2X200N	2"	200
MIB-2X250N	2"	250
MIB-2X300N	2"	300
MIB-212X100N	2.1/2"	100
MIB-212X120N	2.1/2"	120
MIB-212X150N	2.1/2"	150
MIB-212X180N	2.1/2"	180
MIB-212X200N	2.1/2"	200
MIB-212X250N	2.1/2"	250
MIB-212X300N	2.1/2"	300
MIB-3X100N	3"	100
MIB-3X120N	3"	120
MIB-3X150N	3"	150
MIB-3X180N	3"	180
MIB-3X200N	3"	200
MIB-3X250N	3"	250
MIB-3X300N	3"	300
MIB-4X100N	4"	100
MIB-4X120N	4"	120
MIB-4X150N	4"	150
MIB-4X180N	4"	180
MIB-4X200N	4"	200
MIB-4X250N	4"	250
MIB-4X300N	4"	300

Customers who bought from this page also purchased…

Brass Hose Tails see page **1141**



Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MALLEABLE IRON FITTINGS

Heavy-duty Malleable Iron Nipples



Galvanised, BSPT

0305	Thread	Length mm
HBN18-40	1/8"	40
HBN18-60	1/8"	60
HBN18-80	1/8"	80
HBN18-100	1/8"	100
HBN14-40	1/4"	40
HBN14-60	1/4"	60
HBN14-80	1/4"	80
HBN14-100	1/4"	100
HBN14-120	1/4"	120
HBN14-150	1/4"	150
HBN14-180	1/4"	180
HBN14-200	1/4"	200
HBN14-250	1/4"	250
HBN14-300	1/4"	300
HBN38-40	3/8"	40
HBN38-50	3/8"	50
HBN38-60	3/8"	60
HBN38-70	3/8"	70
HBN38-80	3/8"	80
HBN38-100	3/8"	100
HBN38-120	3/8"	120
HBN38-150	3/8"	150
HBN38-180	3/8"	180
HBN38-200	3/8"	200
HBN12-30	1/2"	30
HBN12-40	1/2"	40
HBN12-50	1/2"	50
HBN12-60	1/2"	60
HBN12-80	1/2"	80
HBN12-100	1/2"	100
HBN12-120	1/2"	120
HBN12-150	1/2"	150
HBN12-180	1/2"	180
HBN12-200	1/2"	200
HBN12-250	1/2"	250
HBN12-300	1/2"	300
HBN34-40	3/4"	40
HBN34-60	3/4"	60
HBN34-70	3/4"	70
HBN34-80	3/4"	80
HBN34-100	3/4"	100
HBN34-120	3/4"	120
HBN34-150	3/4"	150

0305	Thread	Length mm
HBN34-180	3/4"	180
HBN34-200	3/4"	200
HBN34-250	3/4"	250
HBN34-300	3/4"	300
HBN1-50	1"	50
HBN1-60	1"	60
HBN1-70	1"	70
HBN1-80	1"	80
HBN1-100	1"	100
HBN1-120	1"	120
HBN1-150	1"	150
HBN1-180	1"	180
HBN1-200	1"	200
HBN1-300	1"	300
HBN114-80	1.1/4"	80
HBN114-100	1.1/4"	100
HBN114-120	1.1/4"	120
HBN114-150	1.1/4"	150
HBN114-200	1.1/4"	200
HBN114-250	1.1/4"	250
HBN114-300	1.1/4"	300
HBN112-80	1.1/2"	80
HBN112-100	1.1/2"	100
HBN112-120	1.1/2"	120
HBN112-150	1.1/2"	150
HBN112-180	1.1/2"	180
HBN112-200	1.1/2"	200
HBN112-300	1.1/2"	300
HBN2-80	2"	80
HBN2-120	2"	120
HBN2-150	2"	150
HBN2-180	2"	180
HBN2-250	2"	250
HBN2-300	2"	300
HBN212-100	2.1/2"	100
HBN212-200	2.1/2"	200
HBN212-300	2.1/2"	300
HBN3-100	3"	100
HBN3-200	3"	200
HBN3-300	3"	300
HBN4-100	4"	100
HBN4-200	4"	200
HBN4-300	4"	300



For **Jointing Paste** see page **1391**

Fluid-Air Components Ltd

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Barrel Nipples to BS EN 10241

Material: BS EN 10241
Dimensions: BS EN 10241
Threads: ISO 7/1
Schedule: Medium/Heavy-duty



Galvanised, BSPT

0357	Thread	Length mm
ENBN-18X40	1/8"	40
ENBN-18X60	1/8"	60
ENBN-14X40	1/4"	40
ENBN-14X60	1/4"	60
ENBN-14X80	1/4"	80
ENBN-14X100	1/4"	100
ENBN-14X200	1/4"	200
ENBN-14X250	1/4"	250
ENBN-38X40	3/8"	40
ENBN-38X50	3/8"	50
ENBN-38X60	3/8"	60
ENBN-38X80	3/8"	80
ENBN-38X100	3/8"	100
ENBN-38X150	3/8"	150
ENBN-38X200	3/8"	200
ENBN-12X30	1/2"	30
ENBN-12X40	1/2"	40
ENBN-12X50	1/2"	50
ENBN-12X60	1/2"	60
ENBN-12X80	1/2"	80
ENBN-12X100	1/2"	100
ENBN-12X150	1/2"	150
ENBN-12X200	1/2"	200
ENBN-12X250	1/2"	250
ENBN-12X300	1/2"	300
ENBN-34X40	3/4"	40
ENBN-34X60	3/4"	60
ENBN-34X80	3/4"	80
ENBN-34X100	3/4"	100
ENBN-34X150	3/4"	150
ENBN-34X200	3/4"	200
ENBN-34X300	3/4"	300
ENBN-1X40	1"	40
ENBN-1X50	1"	50

0357	Thread	Length mm
ENBN-1X60	1"	60
ENBN-1X80	1"	80
ENBN-1X100	1"	100
ENBN-1X150	1"	150
ENBN-1X200	1"	200
ENBN-1X300	1"	300
ENBN-114X80	1.1/4"	80
ENBN-114X100	1.1/4"	100
ENBN-114X150	1.1/4"	150
ENBN-114X200	1.1/4"	200
ENBN-114X300	1.1/4"	300
ENBN-112X80	1.1/2"	80
ENBN-112X100	1.1/2"	100
ENBN-112X150	1.1/2"	150
ENBN-112X200	1.1/2"	200
ENBN-112X300	1.1/2"	300
ENBN-2X80	2"	80
ENBN-2X100	2"	100
ENBN-2X150	2"	150
ENBN-2X200	2"	200
ENBN-2X300	2"	300
ENBN-212X100	2.1/2"	100
ENBN-212X150	2.1/2"	150
ENBN-212X200	2.1/2"	200
ENBN-212X300	2.1/2"	300
ENBN-3X100	3"	100
ENBN-3X150	3"	150
ENBN-3X200	3"	200
ENBN-3X300	3"	300
ENBN-4X100	4"	100
ENBN-4X150	4"	150
ENBN-4X200	4"	200
ENBN-4X300	4"	300

Page Tech Sheet 20569

Carbon Steel Pipe Nipple Medium/Heavy, Welded/Seamless

Pipe Size	Pipe O.D.	Length Close	Pipe Nipple Lengths (mm)														
mm	mm	mm															
6	10.3	19	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
8	13.7	27	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
10	17.1	28	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
15	21.3	37	X	40	50	60	80	100	150	180	200	250	300	350	400	450	500
20	26.7	39	X	40	50	60	80	100	150	180	200	250	300	350	400	450	500
25	33.4	46	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
32	42.2	51	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
40	48.3	51	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
50	60.3	60	X	X	X	60	80	100	150	180	200	250	300	350	400	450	500
65	76.1	69	X	X	X	X	80	100	150	180	200	250	300	350	400	450	500
80	88.9	75	X	X	X	X	80	100	150	180	200	250	300	350	400	450	500
100	114.3	87	X	X	X	X	X	100	150	180	200	250	300	350	400	450	500
125	141.3	96	X	X	X	X	X	X	150	180	200	250	300	350	400	450	500
150	168.3	96	X	X	X	X	X	X	150	180	200	250	300	350	400	450	500

MALLEABLE IRON FITTINGS

K-LINE CONNECT

Barrel Nipples to BS EN 10241

Material: BS EN 10241
Dimensions: BS EN 10241
Threads: ISO 7/1
Schedule: Medium/Heavy-duty



Black, BSPT

0357	Thread	Length mm
ENBN-18X40N	1/8"	40
ENBN-18X60N	1/8"	60
ENBN-14X40N	1/4"	40
ENBN-14X60N	1/4"	60
ENBN-14X80N	1/4"	80
ENBN-14X100N	1/4"	100
ENBN-14X200N	1/4"	200
ENBN-14X250N	1/4"	250
ENBN-38X40N	3/8"	40
ENBN-38X50N	3/8"	50
ENBN-38X60N	3/8"	60
ENBN-38X80N	3/8"	80
ENBN-38X100N	3/8"	100
ENBN-38X150N	3/8"	150
ENBN-38X200N	3/8"	200
ENBN-12X30N	1/2"	30
ENBN-12X40N	1/2"	40
ENBN-12X50N	1/2"	50
ENBN-12X60N	1/2"	60
ENBN-12X80N	1/2"	80
ENBN-12X100N	1/2"	100
ENBN-12X150N	1/2"	150
ENBN-12X200N	1/2"	200
ENBN-12X250N	1/2"	250
ENBN-12X300N	1/2"	300
ENBN-34X40N	3/4"	40
ENBN-34X60N	3/4"	60
ENBN-34X80N	3/4"	80
ENBN-34X100N	3/4"	100
ENBN-34X150N	3/4"	150
ENBN-34X200N	3/4"	200
ENBN-34X300N	3/4"	300
ENBN-1X40N	1"	40
ENBN-1X50N	1"	50

0357	Thread	Length mm
ENBN-1X60N	1"	60
ENBN-1X80N	1"	80
ENBN-1X100N	1"	100
ENBN-1X150N	1"	150
ENBN-1X200N	1"	200
ENBN-1X300N	1"	300
ENBN-114X80N	1.1/4"	80
ENBN-114X100N	1.1/4"	100
ENBN-114X150N	1.1/4"	150
ENBN-114X200N	1.1/4"	200
ENBN-114X300N	1.1/4"	300
ENBN-112X80N	1.1/2"	80
ENBN-112X100N	1.1/2"	100
ENBN-112X150N	1.1/2"	150
ENBN-112X200N	1.1/2"	200
ENBN-112X300N	1.1/2"	300
ENBN-2X80N	2"	80
ENBN-2X100N	2"	100
ENBN-2X150N	2"	150
ENBN-2X200N	2"	200
ENBN-2X300N	2"	300
ENBN-212X100N	2.1/2"	100
ENBN-212X150N	2.1/2"	150
ENBN-212X200N	2.1/2"	200
ENBN-212X300N	2.1/2"	300
ENBN-3X100N	3"	100
ENBN-3X150N	3"	150
ENBN-3X200N	3"	200
ENBN-3X300N	3"	300
ENBN-4X100N	4"	100
ENBN-4X150N	4"	150
ENBN-4X200N	4"	200
ENBN-4X300N	4"	300

Page Tech Sheet 20569

Carbon Steel Pipe Nipple Medium/Heavy, Welded/Seamless

Pipe Size	Pipe O.D.	Length Close	Pipe Nipple Lengths (mm)														
mm	mm	mm															
6	10.3	19	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
8	13.7	27	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
10	17.1	28	30	40	50	60	80	100	150	180	200	250	300	350	400	450	500
15	21.3	37	X	40	50	60	80	100	150	180	200	250	300	350	400	450	500
20	26.7	39	X	40	50	60	80	100	150	180	200	250	300	350	400	450	500
25	33.4	46	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
32	42.2	51	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
40	48.3	51	X	X	50	60	80	100	150	180	200	250	300	350	400	450	500
50	60.3	60	X	X	X	60	80	100	150	180	200	250	300	350	400	450	500
65	76.1	69	X	X	X	X	80	100	150	180	200	250	300	350	400	450	500
80	88.9	75	X	X	X	X	80	100	150	180	200	250	300	350	400	450	500
100	114.3	87	X	X	X	X	X	100	150	180	200	250	300	350	400	450	500
125	141.3	96	X	X	X	X	X	X	150	180	200	250	300	350	400	450	500
150	168.3	96	X	X	X	X	X	X	150	180	200	250	300	350	400	450	500

Fluid-Air Components Ltd

EN10255, EN10217-1 & BS1387 STEEL TUBE

Screwed & Socketed Steel Tubing



EN10255, EN10217-1 & BS1387 - Medium Grade, Red Oxide Primed, 3.2m Lengths,

0193	Thread
NC-TUBE12N	1/2" (15mm)
NC-TUBE34N	3/4" (20mm)
NC-TUBE1N	1" (25mm)
NC-TUBE114N	1.1/4" (32mm)
NC-TUBE112N	1.1/2" (40mm)
NC-TUBE2N	2" (50mm)
NC-TUBE212N	2.1/2" (65mm)
NC-TUBE3N	3" (80mm)
NC-TUBE4N	4" (100mm)
Tech Sheet 10639	

6.4m Lengths, BSPP

0193	Thread
NC-TUBE12N-6.5	1/2" (15mm)
NC-TUBE34N-6.5	3/4" (20mm)
NC-TUBE1N-6.5	1" (25mm)
NC-TUBE114N-6.5	1.1/4" (32mm)
NC-TUBE112N-6.5	1.1/2" (40mm)
NC-TUBE2N-6.5	2" (50mm)
NC-TUBE212N-6.5	2.1/2" (65mm)
NC-TUBE3N-6.5	3" (80mm)
NC-TUBE4N-6.5	4" (100mm)
Tech Sheet 10639	

EN10255, EN10217-1 & BS1387 - Heavy Grade, Red Oxide Primed, 3.2m Lengths, BSPP

0193	Thread
NC-HTUBE12N	1/2" (15mm)
NC-HTUBE34N	3/4" (20mm)
NC-HTUBE1N	1" (25mm)
NC-HTUBE114N	1.1/4" (32mm)
NC-HTUBE2N	2" (50mm)
Tech Sheet 10639	

6.4m Lengths, BSPP

0193	Thread
NC-HTUBE12N-6.5	1/2" (15mm)
NC-HTUBE34N-6.5	3/4" (20mm)
NC-HTUBE1N-6.5	1" (25mm)
NC-HTUBE114N-6.5	1.1/4" (32mm)
NC-HTUBE112N-6.5	1.1/2" (40mm)
NC-HTUBE2N-6.5	2" (50mm)
Tech Sheet 10639	



EN10255, EN10217-1 & BS1387 - Medium Grade, Galvanised, 3.2m Lengths, BSPP

0193	Thread
NC-TUBE12	1/2" (15mm)
NC-TUBE34	3/4" (20mm)
NC-TUBE1	1" (25mm)
NC-TUBE114	1.1/4" (32mm)
NC-TUBE112	1.1/2" (40mm)
NC-TUBE2	2" (50mm)
NC-TUBE212	2.1/2" (65mm)
NC-TUBE3	3" (80mm)
NC-TUBE4	4" (100mm)
Tech Sheet 10639	

6.4m Lengths, BSPP

0193	Thread
NC-TUBE12-6.5	1/2" (15mm)
NC-TUBE34-6.5	3/4" (20mm)
NC-TUBE1-6.5	1" (25mm)
NC-TUBE114-6.5	1.1/4" (32mm)
NC-TUBE112-6.5	1.1/2" (40mm)
NC-TUBE2-6.5	2" (50mm)
NC-TUBE212-6.5	2.1/2" (65mm)
NC-TUBE3-6.5	3" (80mm)
NC-TUBE4-6.5	4" (100mm)
Tech Sheet 10639	

EN10255, EN10217-1 & BS1387 - Heavy Grade, Galvanised, 3.2m Lengths, BSPP

0193	Thread
NC-HTUBE12	1/2" (15mm)
NC-HTUBE34	3/4" (20mm)
NC-HTUBE1	1" (25mm)
NC-HTUBE114	1.1/4" (32mm)
NC-HTUBE112	1.1/2" (40mm)
NC-HTUBE2	2" (50mm)
Tech Sheet 10639	

6.4m Lengths, BSPP

0193	Thread
NC-HTUBE12-6.5	1/2" (15mm)
NC-HTUBE34-6.5	3/4" (20mm)
NC-HTUBE1-6.5	1" (25mm)
NC-HTUBE114-6.5	1.1/4" (32mm)
NC-HTUBE112-6.5	1.1/2" (40mm)
NC-HTUBE2-6.5	2" (50mm)
Tech Sheet 10639	

Dual Certified Tubes EN10255 and 10217-1

Universal Steel Mill based in UAE ia a major producer of steel tubes across the world. As a major supplier to the world market Universal strives to ensure the products it produces meet the stringent standards of todays markets. To that end they have produced a dual certified tube that can be supplied into the HVAC, Mechanical and Fire Protection industries within the UK.

Certification - all tubes can be supplied with MTC (mill test certificates), certifying that the tubes comply to the relevant standard.

Tubes are available from an extensive stock range:

Standard full lengths or half randoms
Threaded and plain ended
Medium or heavy weight
Red and galvanised finishes

Technical Specification

Leak Tightness Test
- Online NDT machines
- Hydro static pressure testing to 50 bar

Chemical Testing
- Complete chemical laboratory at the mill
- Elco meters
- Hydrometers

Galvanising
- Hot dipped galvanising/zinc coating to EN10240 quality A.1
- Quality checked hourly with Elco meters to ensure a 55-70 micron thickness across tube length

Material
- Fully killed steel
- Tensile tested
- Internal weld seam shall not have a height exceeding 60% of the wall thickness



6.4 metre lengths are available on 2-5 working day delivery service. Specified delivery dates and times cannot be guaranteed. Additional carriage charges may apply, based on weight and location. Please speak to our Business Development Team for full details.

Please note: The UK market has moved away from black tube and has been replaced by primed red oxide tube.

FLANGE BOLT KITS

Bright Zinc Plated Bolt Kits

4 x Bolts
4 x Nuts
4 x Washers
Steel Zinc Plated



M10 Thread

1096	Thread	Length mm
2034-8942	M10	40
2034-8959	M10	45

M12 Thread

1096	Thread	Length mm
2034-9007	M12	25
2034-9015	M12	30
2034-9098	M12	70
2034-9122	M12	90

M16 Thread

1096	Thread	Length mm
2034-9148	M16	50
2034-9155	M16	55
2034-9163	M16	60
2034-9171	M16	65
2034-9189	M16	70
2034-9197	M16	75
2034-9205	M16	80
2034-9221	M16	100
2034-9239	M16	110

M20 Thread

1096	Thread	Length mm
2034-9254	M20	55
2034-9262	M20	60
2034-9270	M20	65
2034-9288	M20	70
2034-9296	M20	75
2034-9312	M20	80
2034-9320	M20	90
2034-9361	M20	120

MALLEABLE IRON ACCESSORIES

School Board Pipe Brackets



Black

1092	Nominal Bore OD
MISB14N	1/4"
MISB38N	3/8"
MISB12N	1/2"
MISB34N	3/4"
MISB1N	1"
BSB20	1.1/4"
MISB112N	1.1/2"
MISB2N	2"
BSB48	3"
BSB64	4"



Galvanised

1092	Nominal Bore OD
MISB14	1/4"
MISB38	3/8"
MISB12	1/2"
MISB34	3/4"
MISB1	1"
MISB114	1.1/4"
MISB112	1.1/2"
MISB2	2"
MISB212	2.1/2"
MISB4	4"

Girder Clamp



Metric Thread

1092	Thread
MIGCM8	M8
MIGCM10	M10
MIGCM12	M12

Fluid-Air Components Ltd

MALLEABLE IRON ACCESSORIES

Single M10 Tapping Pipe Ring



Black

1092	Nominal Bore OD
MISTP14N	1/4"
MISTP38N	3/8"
MISTP12N	1/2"
MISTP34N	3/4"
MISTP1N	1"
MISTP114N	1.1/4"
MISTP2N	2"
Tech Sheet 10641	

Galvanised

1092	Nominal Bore OD
MISTP38	3/8"
MISTP12	1/2"
MISTP34	3/4"
MISTP1	1"
MISTP114	1.1/4"
MISTP112	1.1/2"
MISTP2	2"
Tech Sheet 10641	

Double M10 Tapping Pipe Ring



Black


1092	Nominal Bore OD	Nominal Bore mm
MIDTP14N	1/4"	8
MIDTP38N	3/8"	18
MIDTP12N	1/2"	15
MIDTP1N	1"	25
MIDTP114N	1.1/4"	32

Galvanised

1092	Nominal Bore OD	Nominal Bore mm
MIDTP14	1/4"	8
MIDTP12	1/2"	15
MIDTP34	3/4"	20
MIDTP1	1"	25
MIDTP114	1.1/4"	32
MIDTP112	1.1/2"	51
MIDTP2	2"	50

Wrought Iron Sockets

Maximum Working Pressure:
16 bar



Black, BSPP

1099	Thread
MIWRSB-18N	1/8"
MIWRSB-14N	1/4"
MIWRSB-38N	3/8"
MIWRSB-12N	1/2"
MIWRSB-34N	3/4"
MIWRSB-1N	1"
MIWRSB-114N	1.1/4"
MIWRSB-112N	1.1/2"
MIWRSB-2N	2"
MIWRSB-212N	2.1/2"
MIWRSB-3N	3"
MIWRSB-4N	4"
MIWRSB-6N	6"

Galvanised, BSPP

1099	Thread
MIWRSG-18	1/8"
MIWRSG-14	1/4"
MIWRSG-38	3/8"
MIWRSG-12	1/2"
MIWRSG-34	3/4"
MIWRSG-1	1"
MIWRSG-114	1.1/4"
MIWRSG-112	1.1/2"
MIWRSG-2	2"
MIWRSG-212	2.1/2"
MIWRSG-3	3"
MIWRSG-4	4"

M10 Tapping Back Plate



Black

1092	Thread
MIBPM10N	M10
MIBPM12N	M12

Galvanised

1092	Thread
MIBPM10	M10
MIBPM12	M12

Studding



1092	Thread	Length Metres
MISDM8	M8 x 1.25	1
MISDM10	M10 x 1.5	1
MISDM10X1.0/3M	M10 x 1	3
MISDM12X1.0	M12 x 1	1

Repair Coupling

Working Temperature:
-10°C to +60°C

Maximum Working Pressure: 10 bar



BSPP

1092	Thread	Length mm
MIRC-12	1/2"	76
MIRC-34	3/4"	76
MIRC-1	1"	88
MIRC-112	1.1/2"	102
MIRC-2	2"	102

Supports



Cantilever Arms

1092	Length mm
CA150HDG	150
CA300HDG	300
CA450HDG	450
CA600HDG	600
CA750HDG	750

FORGED STEEL FLANGES

Weld Neck



PN16/111, BS4504: 1989, Table 16

1098	ID
FSFWB-1	1"
FSFWB-114	1.1/4"
FSFWB-112	1.1/2"
FSFWB-2	2"
FSFWB-212	2.1/2"
FSFWB-3	3"
FSFWB-4	4"
Tech Sheet 1500	

PN40/111, BS4505: 1989, Table 40

1098	ID
FSFWB-1-300	1"
FSFWB-112-300	1.1/2"
FSFWB-2-300	2"
FSFWB-212-300	2.1/2"
FSFWB-4-300	4"
Tech Sheet 1500	

150lb, ANSI B16.5a/1992, ASA 150

1098	ID
FSFWA-1	1"
FSFWA-114	1.1/4"
FSFWA-112	1.1/2"
FSFWA-2	2"
FSFWA-212	2.1/2"
FSFWA-3	3"
FSFWA-4	4"
Tech Sheet 1500	

300lb, ANSI B16.5a/1992, ASA 300

1098	ID
FSFWA-212-300	2.1/2"
FSFWA-3-300	3"
FSFWA-4-300	4"
Tech Sheet 1500	

Slip-on



PN16/112, BS4504: 1989, Table 16

1098	ID
FSFSOB-12	1/2"
FSFSOB-34	3/4"
FSFSOB-1	1"
FSFSOB-114	1.1/4"
FSFSOB-112	1.1/2"
FSFSOB-2	2"
FSFSOB-212	2.1/2"
FSFSOB-3	3"
FSFSOB-4	4"
Tech Sheet 1500	

PN40/112, BS4504: 1989, Table 40

1098	ID
FSFSOB-12-300	1/2"
FSFSOB-112-300	1.1/2"
FSFSOB-2-300	2"
FSFSOB-212-300	2.1/2"
FSFSOB-3-300	3"
FSFSOB-4-300	4"
Tech Sheet 1500	

150lb, ANSI B16.5a/1992, ASA 150

1098	ID
FSFSOA-12	1/2"
FSFSOA-34	3/4"
FSFSOA-1	1"
FSFSOA-112	1.1/2"
FSFSOA-2	2"
FSFSOA-3	3"
FSFSOA-4	4"
Tech Sheet 1500	

300lb, ANSI B16.5a/1992, ASA 300

1098	ID
FSFSOA-34-300	3/4"
FSFSOA-114-300	1.1/4"
FSFSOA-2-300	2"
FSFSOA-4-300	4"
Tech Sheet 1500	

Screwed



PN16/113, BS4504: 1989, Table 16, BSPP

1098	Thread
FSFSB-12	1/2"
FSFSB-34	3/4"
FSFSB-1	1"
FSFSB-114	1.1/4"
FSFSB-112	1.1/2"
FSFSB-2	2"
FSFSB-212	2.1/2"
FSFSB-3	3"
FSFSB-4	4"
Tech Sheet 1500	

PN40/113, BS4504: 1989, Table 40, BSPP

1098	Thread
FSFSB-12-300	1/2"
FSFSB-34-300	3/4"
FSFSB-1-300	1"
FSFSB-114-300	1.1/4"
FSFSB-112-300	1.1/2"
FSFSB-2-300	2"
FSFSB-212-300	2.1/2"
FSFSB-3-300	3"
FSFSB-4-300	4"
Tech Sheet 1500	

150lb, ANSI B16.5a/1992, ASA 150, BSPP

1098	Thread
FSFSA-112	1.1/2"
FSFSA-2	2"
FSFSA-212	2.1/2"
FSFSA-3	3"
Tech Sheet 1500	

300lb, ANSI B16.5a/1992, ASA 300, BSPP

1098	Thread
FSFSA-12-300	1/2"
FSFSA-34-300	3/4"
FSFSA-1-300	1"
FSFSA-112-300	1.1/2"
FSFSA-2-300	2"
Tech Sheet 1500	

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

Carbon Steel Flanges



Slip-On Plate Flanges, Table D

0264	ID mm
FPSOTD-32	32
FPSOTD-50	50
FPSOTD-65	65
FPSOTD-80	80
FPSOTD-100	100
FPSOTD-125	125
FPSOTD-150	150
FPSOTD-200	200
FPSOTD-250	250
FPSOTD-300	300
Tech Sheet 1500	

Note: I.D. = Nominal bore of tube



Blank Flanges, Table D

0264	To Suit mm
FPBLTD-15	15
FPBLTD-20	20
FPBLTD-25	25
FPBLTD-32	32
FPBLTD-50	50
FPBLTD-65	65
FPBLTD-80	80
FPBLTD-100	100
FPBLTD-150	150
FPBLTD-200	200
FPBLTD-250	250
FPBLTD-300	300
Tech Sheet 1500	



Screwed Boss Flanges, Table D, BSPP

0264	Thread
FBSTD-12	1/2"
FBSTD-34	3/4"
FBSTD-1	1"
FBSTD-114	1.1/4"
FBSTD-2	2"
FBSTD-212	2.1/2"
FBSTD-3	3"
FBSTD-4	4"
FBSTD-6	6" (6.1/2")
Tech Sheet 1500	



Slip-On Boss Flanges, Table D

0264	ID mm
FBSOTD-2	50
FBSOTD-3	80
FBSOTD-4	100
FBSOTD-612	150 (6.1/2")
FBSOTD-658	150 (6.5/8")
FBSOTD-8	200
FBSOTD-10	250
FBSOTD-300	300
Tech Sheet 1500	



Slip-On Plate Flanges, Table E

0264	ID mm
FPSOTE-15	15
FPSOTE-20	20
FPSOTE-25	25
FPSOTE-32	32
FPSOTE-40	40
FPSOTE-50	50
FPSOTE-65	65
FPSOTE-80	80
FPSOTE-100	100
FPSOTE-125	125
FPSOTE-150	150
FPSOTE-200	200
FPSOTE-250	250
FPSOTE-300	300
Tech Sheet 1500	



Blank Flanges, Table E

0264	To Suit mm
FPBLTE-15	15
FPBLTE-25	25
FPBLTE-32	32
FPBLTE-40	40
FPBLTE-50	50
FPBLTE-65	65
FPBLTE-80	80
FPBLTE-100	100
FPBLTE-125	125
FPBLTE-150	150
FPBLTE-200	200
FPBLTE-250	250
FPBLTE-300	300
Tech Sheet 1500	



Screwed Boss Flanges, Table E, BSPP

0264	Thread
FBSTE-12	1/2"
FBSTE-34	3/4"
FBSTE-1	1"
FBSTE-114	1.1/4"
FBSTE-112	1.1/2"
FBSTE-2	2"
FBSTE-212	2.1/2"
FBSTE-3	3"
FBSTE-4	4"
FBSTE-5	5"
FBSTE-6	6" (6.1/2")
Tech Sheet 1500	



Slip-On Boss Flanges, Table E

0264	ID mm
FBSOTE-12	15
FBSOTE-34	20
FBSOTE-1	25
FBSOTE-114	32
FBSOTE-112	40
FBSOTE-2	50
FBSOTE-212	65
FBSOTE-3	80
FBSOTE-4	100
FBSOTE-5	125
FBSOTE-612	150 (6.1/2")
FBSOTE-658	150 (6.5/8")
FBSOTE-8	200
FBSOTE-10	250
Tech Sheet 1500	



For **Stainless Steel Flanges** see page **1195**

FLEXIBLE RUBBER BELLOWS

Moulded Rubber Bellows are designed to compensate for misalignment, neutralise movement and reduce noise through vibration in pipelines. They effectively dampen the transmission of sound and vibration and can be used in many applications with various medias including water, oils, chemicals and gases when the correct body material is specified.

Other body materials available on request:
- Butyl
- Nitrile
- Hypalon

Other flange drillings are also available on request.

Working Temperature: -30°C to +110°C

Maximum Working Pressure: 16 bar

PN16 Flanged Connector, BS4504



Nitrile

0388	Flange Size	ID mm	Length mm
FRB-PN16-114NBR	1.1/4"	32	130
FRB-PN16-112NBR	1.1/2"	40	130
FRB-PN16-2NBR	2"	50	130
FRB-PN16-212NBR	2.1/2"	65	130
FRB-PN16-3NBR	3"	80	130
FRB-PN16-4NBR	4"	100	130
FRB-PN16-5NBR	5"	125	130
FRB-PN16-6NBR	6"	150	130
FRB-PN16-8NBR	8"	200	130
FRB-PN16-10NBR	10"	250	130
FRB-PN16-12NBR	12"	300	130
Tech Sheet 10305			



EPDM

0388	Flange Size	ID mm	Length mm
FRB-PN16-114EPDM	1.1/4"	32	130
FRB-PN16-112EPDM	1.1/2"	40	130
FRB-PN16-2EPDM	2"	50	130
FRB-PN16-212EPDM	2.1/2"	65	130
FRB-PN16-3EPDM	3"	80	130
FRB-PN16-4EPDM	4"	100	130
FRB-PN16-5EPDM	5"	125	130
FRB-PN16-6EPDM	6"	150	130
FRB-PN16-8EPDM	8"	200	130
FRB-PN16-10EPDM	10"	250	130
FRB-PN16-12EPDM	12"	300	130
Tech Sheet 10305			



Nitrile, Tied

0388	Flange Size	ID mm	Length mm
RBT-PN16-114NBR	1.1/4"	32	130
RBT-PN16-112NBR	1.1/2"	40	130
RBT-PN16-2NBR	2"	50	130
RBT-PN16-212NBR	2.1/2"	65	130
RBT-PN16-3NBR	3"	80	130
RBT-PN16-4NBR	4"	100	130
RBT-PN16-5NBR	5"	125	130
RBT-PN16-6NBR	6"	150	130
RBT-PN16-8NBR	8"	200	130
RBT-PN16-10NBR	10"	250	130
RBT-PN16-12NBR	12"	300	130
Tech Sheet 10305			



EPDM, Tied

0388	Flange Size	ID mm	Length mm
RBT-PN16-114EPDM	1.1/4"	32	130
RBT-PN16-112EPDM	1.1/2"	40	130
RBT-PN16-2EPDM	2"	50	130
RBT-PN16-212EPDM	2.1/2"	65	130
RBT-PN16-3EPDM	3"	80	130
RBT-PN16-4EPDM	4"	100	130
RBT-PN16-5EPDM	5"	125	130
RBT-PN16-6EPDM	6"	150	130
RBT-PN16-8EPDM	8"	200	130
RBT-PN16-10EPDM	10"	250	130
RBT-PN16-12EPDM	12"	300	130
Tech Sheet 10305			

BSPP Threaded Connector, Double Sphere



Nitrile

0388	Thread	ID mm	Length mm
FRB-BSP-1/2NBR	1/2"	15	203
FRB-BSP-3/4NBR	3/4"	20	203
FRB-BSP-1NBR	1"	25	203
FRB-BSP-114NBR	1.1/4"	32	203
FRB-BSP-112NBR	1.1/2"	40	203
FRB-BSP-2NBR	2"	50	203
FRB-BSP-212NBR	2.1/2"	65	240
FRB-BSP-3NBR	3"	80	240
Tech Sheet 10306			



EPDM

0388	Thread	ID mm	Length mm
FRB-BSP-1/2EPDM	1/2"	15	203
FRB-BSP-3/4EPDM	3/4"	20	203
FRB-BSP-1EPDM	1"	25	203
FRB-BSP-114EPDM	1.1/4"	32	203
FRB-BSP-112EPDM	1.1/2"	40	203
FRB-BSP-2EPDM	2"	50	203
FRB-BSP-212EPDM	2.1/2"	65	240
FRB-BSP-3EPDM	3"	80	240
Tech Sheet 10306			

Fluid-Air Components Ltd

Mild Steel Flanged Hose Tails



Table E, Mild Steel

0297	To Suit Hose ID
FEHT2	2"
FEHT3	3"
FEHT4	4"
Tech Sheet 20469	

NP16, Mild Steel

0297	To Suit Hose ID
FNP16HT112	1.1/2"
FNP16HT2	2"
FNP16HT212	2.1/2"
FNP16HT3	3"
FNP16HT4	4"
FNP16HT6	6"
FNP16HT8	8"
Tech Sheet 20469	

Flanged Hose Tail Table D, Mild Steel

0297	To Suit Hose ID
FDHT2	2"
FDHT3	3"
FDHT4	4"
FDHT5	5"
FDHT6	6"
Tech Sheet 20469	

ASA150, Mild Steel

0297	To Suit Hose ID
FASA150HT2	2"
Tech Sheet 20469	

Stainless Steel Flanged Hose Tails

stainless steel

Table E, Stainless Steel

0297	To Suit Hose ID
FHSESS2	2"
Tech Sheet 20469	

NP16, Stainless Steel

0297	To Suit Hose ID
FHSNP16SS2	2"
FHSNP16SS3	3"
Tech Sheet 20469	

ASA 150, Stainless Steel

0297	To Suit Hose ID
FHSASASS2	2"
Tech Sheet 20469	

Rubber Gaskets




Table D, Full Face

0296	ID
GRD2	2"
GRD3	3"
GRD4	4"
GRD6	6"
GRD8	8"



IBC PN16

0296	ID
GRIBCNP162	2"
GRIBCNP163	3"
GRIBCNP164	4"
GRIBCNP166	6"
GRIBCNP168	8"




IBC PN16 & Table D

0296	ID
GKIBCNP162	2"
GKIBCNP163	3"
GKIBCNP164	4"
GKIBCNP166	6"



PN16, Full Face

0296	ID
GRNP162	2"
GRNP163	3"
GRNP164	4"
GRNP166	6"
GRNP168	8"



PN16, Full Face (Klinger)

0296	ID
GKNP163	3"
GKNP166	6"

Fibre Gaskets





Table D, Full Face, (Top Graph Araflex)

0296	ID
GKD2	2"
GKD3	3"

For **Stainless Steel Flanges** see page **1195**



Fluid-Air Components Ltd

NONE ASBESTOS FLANGE GASKETS

IBC Gaskets

Maximum temperature/ pressure can't be used simultaneously and are dependant on thickness.



N34 150lb, ASME B16.5/B16.21

0296	ID
GS12-150	1/2"
GS34-150	3/4"
GS1-150	1"
GS114-150	1.1/4"
GS112-150	1.1/2"
GS2-150	2"
GS212-150	2.1/2"
GS3-150	3"
GS4-150	4"
Tech Sheet 2023	

N34 300lb, ASME B16.5/B16.21

0296	ID
GS12-300	1/2"
GS1-300	1"
GS112-300	1.1/2"
GS3-300	3"
Tech Sheet 2023	

N34 PN16, DIN Standard DIN-DVGW 96.01 e-845

0296	ID
GSPN16-34	3/4"
GSPN16-1	1"
GSPN16-114	1.1/4"
GSPN16-112	1.1/2"
GSPN16-2	2"
GSPN16-212	2.1/2"
GSPN16-3	3"
GSPN16-4	4"
Tech Sheet 2023	

N34 PN40, DIN Standard DIN-DVGW 96.01 e-845

0296	ID
GSPN40-2	2"
GSPN40-3	3"
Tech Sheet 2023	

Full Face Gaskets

Maximum temperature/ pressure can't be used simultaneously and are dependant on thickness.



N34 150lb, ASME B16.5/B16.21

0296	ID
GSFF12-150	1/2"
GSFF1-150	1"
GSFF114-150	1.1/4"
GSFF112-150	1.1/2"
GSFF2-150	2"
GSFF212-150	2.1/2"
GSFF3-150	3"
Tech Sheet 2023	

N34 300lb, ASME B16.5/B16.21

0296	ID
GSFF1-300	1"
GSFF2-300	2"
Tech Sheet 2023	

N34 PN16, DIN Standard DIN-DVGW 96.01 e-845

0296	ID
GSFF16-12	1/2"
GSFF16-1	1"
GSFF16-114	1.1/4"
GSFF16-112	1.1/2"
GSFF16-2	2"
GSFF16-212	2.1/2"
GSFF16-3	3"
GSFF16-4	4"
Tech Sheet 2023	

N34 PN40, DIN Standard DIN-DVGW 96.01 e-845

0296	ID
GSFF40-1	1"
GSFF40-112	1.1/2"
GSFF40-2	2"
GSFF40-4	4"
Tech Sheet 2023	

Customers who bought from this page also purchased...

TOTAL



Pipe Wrenches...see page **1734**

Fluid-Air Components Ltd

JOINTING COMPOUNDS & SEALANTS

PTFE Thread Sealing Tape



To BS4375

1000	Size
PTFE	0.075mm x 1/2" x 10 Metres x 0.24g/cm
PTF-40	0.100mm x 1/2" x 10 Metres x 0.40g/cm
PTF-80	0.100mm x 19mm x 10 Metres x 0.80g/cm

Non flammable thread sealant. Resistant to all acids, alkalis and solvents. Suitable for use with oxygen and potable water.



WRAS, 0.075mm Gauge, 12 Metres, Pack of 10

0241	Colour	Width mm
M700WHI1212	White	12

For use with gas & potable water



Gas Approved, 5 Metres

0241	Colour	Width mm
PTFE-GAS	White	12

PTFE Thread Seal Tape



1000	Description	Width mm	Roll Length Metres
TAPE	Tape White	12	12
PTFE25MM	Tape White	25	12

Jointing Paste

Resistant to gas, steam, water, petrol, oil and mineral acids

- Easy break
- Lead free
- Complies to BS6956 Part 5 1992

Temperature Resistance:
A: -40°C to 400°C
B: -40°C to 650°C



Stag A

1092	Volume Grams
STAGA	400
Tech Sheet 10798	



Stag B

1092	Volume Grams
STAGB	500
Tech Sheet 10798	

Plate Tapes

Gas board approved to PRS10 high temperature gas flue closure plate sealing tape.



PRS10 Closure Plate Tape, 25 Metres

0241	Colour	Width mm
M293GAS5025	Grey	50

Boss White

BOSS White Pipe Jointing Compound: For steam, air, natural gas and non-potable water applications.

Conforms to BS6956 Part 5: 1992.



White

1092	Volume Grams
MIBOSSW400	400

Cloth Tapes

High tack adhesive for polythene sheet joining, lagging, heating, ventilation and packaging.



Standard Duct Cloth Tape, 50 Metres

0241	Colour	Width mm
M24SSIL4850	Silver	48
M24SBLA4850	Black	48
M24SWHI4850	White	48
M24SSIL7250	Silver	72
M24SSIL9650	Silver	96

Hank Dressed Hemp



To be used with suitable Jointing Paste.

1092	Weight
2046-1687	1/2lb

55 Thread Sealing Cord

Particularly suitable for metal and plastic threaded fittings.

Potable water:
WRC listed for use with potable water up to 85°C.

Meets BS 6920.KTW recommendation for hot and cold water.

Gas and water: Carries the German DVGW approval (No.DV-5142 AUO 166), together with DIN 30660.

- Tested in accordance with EN751-2 Class Arp.
- Replaces hemp/tapes and pastes
- Disassembly can be achieved easily with normal tools



0753	Length Metres
LOC-483283	50
LOC-270153	160
Tech Sheet 80	

Thread Sealant



For B85-E85 & Diesel

1092	Volume Millilitres
GASOILA2	280

BUTT WELD FITTINGS BS1640/ASTM A234WPB

45º Long Radius Bend



1097	ID	OD mm	Wall Thickness mm
BWF1-34	3/4"	26.7	2.87
BWF1-1	1"	33.4	3.38
BWF1-114	1.1/4"	42.2	3.56
BWF1-112	1.1/2"	48.3	3.68
BWF1-2	2"	60.3	3.91
BWF1-212	2.1/2"	73	5.16
BWF1-3	3"	88.9	5.49
BWF1-4	4"	114.3	6.02
Tech Sheet 543			

90º Long Radius Elbow



1097	ID	OD mm	Wall Thickness mm
BWF2-34	3/4"	26.7	2.87
BWF2-1	1"	33.4	3.38
BWF2-114	1.1/4"	42.2	3.56
BWF2-112	1.1/2"	48.3	3.68
BWF2-2	2"	60.3	3.91
BWF2-212	2.1/2"	73	5.16
BWF2-3	3"	88.9	5.49
BWF2-4	4"	114.3	6.02
Tech Sheet 543			

180º Long Radius Return Bend



1097	ID	OD mm	Wall Thickness mm
BWF3-1	1"	33.4	3.38
BWF3-114	1.1/4"	42.2	3.56
BWF3-112	1.1/2"	48.3	3.68
BWF3-2	2"	60.3	3.91
BWF3-3	3"	88.9	5.49
BWF3-4	4"	114.3	6.02
Tech Sheet 543			

Equal Tee



1097	ID	OD mm	Wall Thickness mm
BWF4-1	1"	33.4	3.38
BWF4-112	1.1/2"	48.3	3.68
BWF4-2	2"	60.3	3.91
BWF4-212	2.1/2"	73	5.16
BWF4-3	3"	88.9	5.49
BWF4-4	4"	114.3	6.02
Tech Sheet 543			

Reducing Branch Tee




1097	ID A	ID B
BWF5-12-34	1/2"	3/4"
BWF5-112-114	1.1/2"	1.1/4"
BWF5-2-12	2"	1/2"
BWF5-2-114	2"	1.1/4"
BWF5-212-114	2.1/2"	1.1/4"
BWF5-212-112	2.1/2"	1.1/2"
BWF5-3-112	3"	1.1/2"
BWF5-3-2	3"	2"
BWF5-4-212	4"	2.1/2"
Tech Sheet 543		

Caps



1097	ID
BWF8-12	1/2"
BWF8-1	1"
BWF8-114	1.1/4"
BWF8-112	1.1/2"
BWF8-4	4"
Tech Sheet 543	

Concentric Reducers




Concentric Reducer



1097	ID	ID
BWF6-34-12	3/4"	1/2"
BWF6-114-34	1.1/4"	3/4"
BWF6-112-12	1.1/2"	1/2"
BWF6-112-1	1.1/2"	1"
BWF6-112-114	1.1/2"	1.1/4"
BWF6-2-1	2"	1"
BWF6-2-114	2"	1.1/4"
BWF6-2-112	2"	1.1/2"
BWF6-212-114	2.1/2"	1.1/4"
BWF6-212-112	2.1/2"	1.1/2"
BWF6-212-2	2.1/2"	2"
BWF6-3-114	3"	1.1/4"
BWF6-3-112	3"	1.1/2"
BWF6-3-2	3"	2"
BWF6-3-212	3"	2.1/2"
BWF6-4-2	4"	2"
BWF6-4-212	4"	2.1/2"
BWF6-4-3	4"	3"
Tech Sheet 543		

Eccentric Reducers



Eccentric Reducer



1097	ID	ID
BWF7-112-12	1.1/2"	1/2"
BWF7-112-34	1.1/2"	3/4"
BWF7-112-1	1.1/2"	1"
BWF7-112-114	1.1/2"	1.1/4"
BWF7-2-114	2"	1.1/4"
BWF7-212-112	2.1/2"	1.1/2"
BWF7-3-2	3"	2"
BWF7-3-212	3"	2.1/2"
BWF7-4-212	4"	2.1/2"
BWF7-4-3	4"	3"
Tech Sheet 543		

Fluid-Air Components Ltd

PIPECLAMPS HANDRAIL SYSTEMS

Using standard tube and pipeclamp fittings, imagination is your only limitation to what can be built.
From industry to retail from safety to play all can use the pipeclamp system.


Manufactured to BS EN 1562 1997
Galvanised to BS EN 1461 1999

Applications:

- Safety railings
- Storage bays
- Handrails
- Support framework
- Racking
- Compounds
- Cycle racks
- Hanging rails
- Access and invalid ramps
- Door access and entry guarding

Pipeclamp Size	Tube OD mm	Tube OD inch	Nom Bore mm	Nom Bore inch
1	26.9	1.1/16	20	3/4"
2	33.7	1.11/32	25	1"
3	42.4	1.11/16	32	1.1/4"
4	48.3	1.29/32	40	1.1/2"
5	60.3	2.3/8	50	2"

Short Tee (101)



1089	Pipeclamp Size A	Pipeclamp Size B
PCLAMPS-101-1	1	1
PCLAMPS-101-2	2	2
PCLAMPS-101-3	3	3
PCLAMPS-101-4	4	4
PCLAMPS-101-4/3	4	3
PCLAMPS-101-5	5	5
PCLAMPS-101-5/4	5	4
Tech Sheet 1		

Long Tee (104)




1089	Pipeclamp Size
PCLAMPS-104-1	1
PCLAMPS-104-2	2
PCLAMPS-104-3	3
PCLAMPS-104-4	4
PCLAMPS-104-5	5
Tech Sheet 1	

3 Way Through (116)



1089	Pipeclamp Size
PCLAMPS-116-1	1
PCLAMPS-116-2	2
PCLAMPS-116-3	3
PCLAMPS-116-4	4
PCLAMPS-116-5	5
Tech Sheet 1	

2 Socket Cross (119)



1089	Pipeclamp Size A	Pipeclamp Size B
PCLAMPS-119-1	1	1
PCLAMPS-119-2	2	2
PCLAMPS-119-3	3	3
PCLAMPS-119-4	4	4
PCLAMPS-119-5	5	5
Tech Sheet 1		

90º 2 Way Elbow (125)



1089	Pipeclamp Size
PCLAMPS-125-1	1
PCLAMPS-125-2	2
PCLAMPS-125-3	3
PCLAMPS-125-4	4
PCLAMPS-125-5	5
Tech Sheet 1	

90º 2 Way Swivel Elbow (125H)



1089	Pipeclamp Size
PCLAMPS-125H-3	3
PCLAMPS-125H-4	4

90° 3 Way Elbow (128)



1089	Pipeclamp Size
PCLAMPS-128-1	1
PCLAMPS-128-2	2
PCLAMPS-128-3	3
PCLAMPS-128-4	4
Tech Sheet 1	

Adjustable Tee (129)



1089	Pipeclamp Size
PCLAMPS-129-2	2
PCLAMPS-129-3	3
PCLAMPS-129-4	4
Tech Sheet 1	

Adjustable Cross (130)



1089	Pipeclamp Size
PCLAMPS-130-2	2
PCLAMPS-130-3	3
Tech Sheet 1	

PIPECLAMPS HANDRAIL SYSTEMS

Wall Plate (131)



1089	Pipeclamp Size
PCLAMPS-131-1	1
PCLAMPS-131-2	2
PCLAMPS-131-3	3
PCLAMPS-131-4	4
PCLAMPS-131-5	5
Tech Sheet 1	

Base Plate (132)



1089	Pipeclamp Size
PCLAMPS-132-1	1
PCLAMPS-132-2	2
PCLAMPS-132-3	3
PCLAMPS-132-4	4
PCLAMPS-132-5	5
Tech Sheet 1	

Plastic Plug (133)



1089	Pipeclamp Size
PCLAMPS-133-1	1
PCLAMPS-133-2	2
PCLAMPS-133-3	3
PCLAMPS-133-4	4
PCLAMPS-133-5	5
Tech Sheet 1	

Ground Socket (134)



1089	Pipeclamp Size
PCLAMPS-134-2	2
PCLAMPS-134-3	3
PCLAMPS-134-4	4
Tech Sheet 1	

Retro Fit Clamp (135)



1089	Pipeclamp Size
PCLAMPS-135-2	2
PCLAMPS-135-3	3
PCLAMPS-135-4	4
Tech Sheet 1	

Gate Eye (138)



1089	Pipeclamp Size
PCLAMPS-138-1	1
PCLAMPS-138-2	2
PCLAMPS-138-3	3
PCLAMPS-138-4	4
Tech Sheet 1	

Gate Hinge (140)



1089	Pipeclamp Size
PCLAMPS-140-1	1
PCLAMPS-140-2	2
PCLAMPS-140-3	3
Tech Sheet 1	

Wall Mounted Handrail Bracket (143)



1089	Pipeclamp Size
PCLAMPS-143-1	1
PCLAMPS-143-2	2
PCLAMPS-143-3	3
PCLAMPS-143-4	4
Tech Sheet 1	

Structural Offset Side Palm Fixing (144)



1089	Pipeclamp Size
PCLAMPS-144-2	2
PCLAMPS-144-3	3
PCLAMPS-144-4	4
Tech Sheet 1	

Non Structural Offset Side Palm Fixing (145)



1089	Pipeclamp Size
PCLAMPS-145-2	2
PCLAMPS-145-3	3
PCLAMPS-145-4	4
Tech Sheet 1	

Structural Flush Side Palm Fixing (146)



1089	Pipeclamp Size
PCLAMPS-146-2	2
PCLAMPS-146-3	3
PCLAMPS-146-4	4
Tech Sheet 1	

Offset Swivel Tee (147)



1089	Pipeclamp Size
PCLAMPS-147-2	2
PCLAMPS-147-3	3
PCLAMPS-147-4	4
Tech Sheet 1	

Fluid-Air Components Ltd

Short Swivel In-line Tee (148)



1089	Pipeclamp Size
PCLAMPS-148-1	1
PCLAMPS-148-2	2
PCLAMPS-148-3	3
PCLAMPS-148-4	4
Tech Sheet 1	

In-line External Tube Connector (149)



1089	Pipeclamp Size
PCLAMPS-149-1	1
PCLAMPS-149-2	2
PCLAMPS-149-3	3
PCLAMPS-149-4	4
PCLAMPS-149-5	5
Tech Sheet 1	

In-line Internal Tube Connector (150)



1089	Pipeclamp Size
PCLAMPS-150-2	2
PCLAMPS-150-3	3
PCLAMPS-150-4	4
Tech Sheet 1	

4 Way Cross (158)




1089	Pipeclamp Size
PCLAMPS-158-2	2
PCLAMPS-158-3	3
PCLAMPS-158-4	4
Tech Sheet 1	

Retro Fit Clamp on Tee (160)



1089	Pipeclamp Size A	Pipeclamp Size B
PCLAMPS-160-2	2	2
PCLAMPS-160-3	3	3
PCLAMPS-160-4	4	4
PCLAMPS-160-5	5	5
Tech Sheet 1		

Offset 90° Crossover (161)



1089	Pipeclamp Size A	Pipeclamp Size B
PCLAMPS-161-1	1	1
PCLAMPS-161-2	2	2
PCLAMPS-161-3	3	3
PCLAMPS-161-3/2	3	2
PCLAMPS-161-4	4	4
PCLAMPS-161-4/2	4	2
Tech Sheet 1		

Combination Socket (165)



1089	Pipeclamp Size
PCLAMPS-165-1	1
PCLAMPS-165-3	3
PCLAMPS-165-5	5
Tech Sheet 1	

Pipeclamp Rails

Galvanised rail, plain end



Pipeclamp Size	Tube OD mm	Tube OD inch	Nom Bore mm	Nom Bore inch
1	26.9	1.1/16	20	3/4"
2	33.7	1.11/32	25	1"
3	42.4	1.11/16	32	1.1/4"
4	48.3	1.29/32	40	1.1/2"
5	60.3	2.3/8	50	2"

6.4 Metre Lengths

1089	Pipeclamp Size
PCLAMP-TUBE1-6.5	1
PCLAMP-TUBE2-6.5	2
PCLAMP-TUBE3-6.5	3
PCLAMP-TUBE4-6.5	4
PCLAMP-TUBE5-6.5	5
Tech Sheet 1	

3.2 Metre Lengths

1089	Pipeclamp Size
PCLAMP-TUBE1-325	1
PCLAMP-TUBE2-325	2
PCLAMP-TUBE3-325	3
PCLAMP-TUBE4-325	4
PCLAMP-TUBE5-325	5
Tech Sheet 1	

DIRECT DELIVERY

6.4 metre lengths are available on 2-5 working day delivery service. Specified delivery dates and times cannot be guaranteed.
Additional carriage charges may apply, based on weight and location. Please speak to our Business Development Team for full details.

Fluid-Air Components Ltd

THE SWIVEL RANGE

The swivel range is constructed using female and male parts. 173F is common to all combinations. Lugs on fittings sizes 1 to 5 have the same dimensions, and sizes can be mixed if required, ie: 173F-1 with 173M-4. In addition to being used with 173F to make the combination, all 'M' fittings can also be used to secure various types of infill in place.

WARNING: An entire structure should not be built just using swivel fittings.

Manufactured to BS EN 1562 1997
Galvanised to BS EN 1461 1999

Pipe- clamp Size	Tube OD mm	Tube OD inch	Nom Bore mm	Nom Bore inch
1	26.9	1.1/16	20	3/4"
2	33.7	1.11/32	25	1"
3	42.4	1.11/16	32	1.1/4"
4	48.3	1.29/32	40	1.1/2"
5	60.3	2.3/8	50	2"

Double In-line Swivel Combination (167)



1089	Pipeclamp Size
PCLAMPS-167-1	1
PCLAMPS-167-2	2
PCLAMPS-167-3	3
PCLAMPS-167-4	4
PCLAMPS-167-5	5

Tech Sheet 1

Double Male In-line Swivel (167M)



1089	Pipeclamp Size
PCLAMPS-167M-3	3
PCLAMPS-167M-4	4

90º Corner Swivel (168)



1089	Pipeclamp Size
PCLAMPS-168-2	2
PCLAMPS-168-3	3
PCLAMPS-168-4	4

Tech Sheet 1

90º Male Corner Swivel (168M)



1089	Pipeclamp Size
PCLAMPS-168M-4	2

Swivel Locating Flange (169)



1089	Pipeclamp Size
PCLAMPS-169-1	1
PCLAMPS-169-2	2
PCLAMPS-169-3	3
PCLAMPS-169-4	4

Tech Sheet 1

Male Swivel Locating Flange (169M)



1089
PCLAMPS-169M

Tech Sheet 1

Single Sided Mesh Panel Clip (170)



1089	Pipeclamp Size
PCLAMPS-170-1	1
PCLAMPS-170-2	2
PCLAMPS-170-3	3
PCLAMPS-170-4	4
PCLAMPS-170-5	5

Tech Sheet 1

Double Sided Mesh Panel Clip (171)



1089	Pipeclamp Size
PCLAMPS-171-1	1
PCLAMPS-171-2	2
PCLAMPS-171-3	3
PCLAMPS-171-4	4
PCLAMPS-171-5	5

Tech Sheet 1

Single Swivel (173)



1089	Pipeclamp Size
PCLAMPS-173-2	2
PCLAMPS-173-3	3
PCLAMPS-173-4	4

Female Swivel (173F)



1089	Pipeclamp Size
PCLAMPS-173F-1	1
PCLAMPS-173F-2	2
PCLAMPS-173F-3	3
PCLAMPS-173F-5	5

Tech Sheet 1

Fluid-Air Components Ltd

THE SWIVEL RANGE

Single Male Swivel (173M)



1089	Pipeclamp Size
PCLAMPS-173M-2	2
PCLAMPS-173M-3	3
PCLAMPS-173M-4	4
PCLAMPS-173M-5	5

Tech Sheet 1

3 Way Outlet Tee (176)



1089	Pipeclamp Size
PCLAMPS-176-2	2
PCLAMPS-176-3	3
PCLAMPS-176-4	4
PCLAMPS-176-5	5

Tech Sheet 1

Locking Collar (179)



1089	Pipeclamp Size
PCLAMPS-179-1	1
PCLAMPS-179-2	2
PCLAMPS-179-3	3
PCLAMPS-179-4	4

Tech Sheet 1

Hook (182)



1089	Pipeclamp Size
PCLAMPS-182-2	2
PCLAMPS-182-3	3
PCLAMPS-182-4	4

Tech Sheet 1

Cover (184)



1089	Pipeclamp Size
PCLAMPS-184-2	2
PCLAMPS-184-4	4

Saddle Clamp (198)



1089	Pipeclamp Size
PCLAMPS-198-2	2
PCLAMPS-198-3	3
PCLAMPS-198-4	4

Single Pipe Clamp (199)



1089	Pipeclamp Size
PCLAMPS-199-3	3
PCLAMPS-199-4	4

Slope Range Short Tee (201)



1089	Pipeclamp Size
PCLAMPS-201-2	2
PCLAMPS-201-4	4

Slope Range Long Tee (204)



1089	Pipeclamp Size
PCLAMPS-204-2	2
PCLAMPS-204-4	4

Slope Range Socket Cross (219)



1089	Pipeclamp Size
PCLAMPS-219-2	2
PCLAMPS-219-4	4

Variable Angle In-line Connector (224)



1089	Pipeclamp Size
PCLAMPS-224-2	2
PCLAMPS-224-3	3
PCLAMPS-224-4	4

Slope Range Elbow (225)



1089	Pipeclamp Size
PCLAMPS-225-2	2
PCLAMPS-225-4	4

Tech Sheet 1

THE SWIVEL RANGE

Spare Grubscrews (GS)



1089	Pipeclamp Size
PCLAMPS-GS3-1-2	1-2
PCLAMPS-GS3-4-5	3-4-5
Tech Sheet 1	

Dual Ratchet (233)



1089	Pipeclamp Size
PCLAMPS-233	1-5
Tech Sheet 1	

Allen Keys (235)



1089	Pipeclamp Size	Hex Size
PCLAMPS-235-1-2	1-2	1/4"
PCLAMPS-2353-4-5	3-4-5	3/8"
Tech Sheet 1		

DISABILITY ACCESS

Elbow (DDA1)



1089	Pipeclamp Size
DDA1	3

Post Connector (DDA3)



1089	Pipeclamp Size
DDA3	3

Variable Elbow (DDA5)



1089	Pipeclamp Size
DDA5	3

End Plate (DDA2)



1089	Pipeclamp Size
DDA2	3

Post End Connector (DDA4)



1089	Pipeclamp Size
DDA4	3

Wall Plate (DDA6)



1089	Pipeclamp Size
DDA6	3

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 12

Hose, Couplings, Ducting & Hose Reels

12.01 Hose 1399-1422

12.02 Suction, Delivery Hose & Accessories 1423-1436

12.03 Ducting 1437-1447

12.04 Hose Reels 1448-1466

12.05 Cam & Groove Quick Couplings 1467-1472

12.06 Claw Couplings 1473-1479

12.07 Clamps & Stem Couplings 1480-1482

12.08 Shot Blast & Unicone Fittings 1483-1484

12.09 Storz DIN Couplings 1485-1486

12.10 Trench Pump & Tanker Couplings 1487-1490

12.11 IBC Mortar & Instantaneous Fire Couplings 1491-1496

12.12 Combination Nipples 1497

12.13 Modular Coolant Systems 1498-1502

12.14 Lever Lock Water Couplings 1503-1510

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 12

12.01 Hose

FT PRO | Copely | Parker | RECTUS | TEMA

1399-1422

- Braided PVC Hose
- Reinforced PVC Hose
- Hi-Vis Air & Water RPVC Hose
- Superior Rubber Alloy Air Hose & Assemblies
- Safety Compressed Air Hose Assemblies
- Compressed Air Hose
- Specialist Hose & Tubing
- Automotive Tubing & Hose
- Gas Hose
- Welding Hose Sets
- Oxy/Acetylene Equipment
- Water Hoses



12.02 Suction, Delivery Hose & Accessories

FT PRO | JAYMAC Industrial Hose & Accessories | HOZELOCK TRICOFLEX

1423-1436

- Layflat Delivery Hos & Assemblies
- Suction Hose
- Oil Resistant Suction Hose
- Water Suction Hose
- Water Delivery Hose
- Wire Reinforced Suction Hose
- Hozelock Tricofle
- Contractors Hose
- Industrial Hose
- XLPE Chemical Suction & Delivery Hose
- Anti-static Hose
- Foot Valves & Strainers



12.03 Ducting

FT PRO | NORRES

1437-1447

- Abrasion-resistant, Anti-static Industrial PUR Ducting
- Antistatic PUR Medium & Heavy-duty Ducting
- Food Grade PUR Ducting
- Suction & Delivery Hoses
- Neoprene & Silicone Ducting
- Industrial Vacuum Hoses & Accessories
- Specialist Clamping Equipment



12.04 Hose Reels

FT PRO | JAMEC PEM | JAYMAC Industrial Hose & Accessories | Nederman | Redashe

1448-1466

- Air & Water Hose Reels
- Hi-Vis Hose Reels
- Mountable Hose Reels
- Reelworks Hose Reels
- Heavy-duty Hose Reels
- Spring Rewind Cable Reels
- Self-retracting Hose Reels
- Fire Hose Reels & Accessories



12.05 Cam & Groove Quick Couplings

FT PRO

1467-1472

- Aluminium Couplings
- 316 Stainless Steel Couplings
- Polypropylene Couplings
- Brass Couplings
- Cam & Groove Seals & Spares



12.06 Claw Couplings

FT PRO | LÜDECKE

1473-1479

- Quick Release Pneumatic Hose Couplings
- Quick Release Water Hose Couplings
- Clamps, Hose Clamps & Fasteners



12.07 Clamps and Stem Couplings

FT PRO

1480-1482

- Clamps, Nuts & Bolts
- Steel Air & Steam Couplings & Clamps
- Steam Couplings
- Steam Hose & Assemblies



Hose, Couplings, Ducting & Hose Reels

12.08 Shot Blast and Unicone Fittings

FT PRO

1483-1484

- Shot Blast Couplings, Hose & Nozzle Holders
- Genuine Unicone Fittings



12.09 Storz DIN Couplings

FT PRO

1485-1486

- Storz Din Suction Couplings



12.10 Trench Pump & Tanker Couplings

FT PRO

1487-1490

- Trench Pump Hose Couplings - Lug Type
- Tanker Couplings & Adaptors



12.11 IBC Motar and Instantaneous Fire Couplings

FT PRO JAYMAC

1491-1496

- IBC Off Load System
- Mortar Hose Couplings & Plugs
- Flanges
- Fire Hose & Instantaneous Fire Hose Couplings
- Standpipes, Manhole & Drain Keys



12.12 Combination Nipples

FT PRO

1497

- Combination Steel Nipples & Hose Joiners
- Hexagon Nuts & Tails



12.13 Modular Coolant Systems

FT PRO

1498-1502

- Modular Coolant Hose System



12.14 Lever Lock Water Couplings

FT PRO

1503-1510

- Lever Lock Water Pump Couplings



FAC
Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c


FT PRO®

BRAIDED PVC HOSE

Reinforced PVC Braided Hose, Type RPVC & HDPVC (to BS6066)

Manufactured from top quality crystal clear 'virgin' PVC compound, and ideal for factory airlines, fluid systems and many industrial applications. Reinforced with a high tensile quality polyester yarn, it offers high working pressures and extreme flexibility.

The hose is resistant to a wide range of chemicals (please consult our Business Development Team for further details).



1402

Fluid-Air Components Ltd


ef nkl i r oi r p c c c a c c

BRAIDED PVC HOSE

Reinforced PVC Braided Hose, Type RPVC & HDPVC (to BS6066)
















Characteristics:

- Excellent abrasion resistance
- High resistance to alkalis and acids
- Silicone free
- Cadmium free
- Low toxicity
- Excellent transparency
- Manufactured to comply with BS6066 and ISO5774
- Produced from FDA approved materials
- Durable, anti-cold proof, non-inflated
- Highly flexible, lightweight and easy to handle
- No fissure phenomenon by ultraviolet rays and direct rays of the sun
- Little expansion or contraction

Applications:

- Water supply and draining
- Transfer of various fluids and powder
- Supplying water, gas, oil, etc. in agriculture and industry
- Compressed air
- Other special purposes

Length*	15 metres	30 metres	100 metres
Size	From 3/16" ID to 2" ID		
Temperature	Min -20°C	Max +65°C	


*Other lengths available on request.

Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

BRAIDED PVC HOSE

Reinforced PVC Braided Hose, Type RPVC (to BS6066)




Medium-duty, 30 Metre Coils

5000	ID mm	ID	OD mm	Colour	Max Pressure Bar
RPVC316	5	3/16"	10	Transparent	13
RPVC316N	5	3/16"	10	Black	13
RPVC14	6	1/4"	11	Transparent	15
RPVC14N	6	1/4"	11	Black	15
RPVC14R	6	1/4"	11	Red	15
RPVC14B	6	1/4"	11	Blue	15
RPVC14G	6	1/4"	11	Green	15
RPVC14Y	6	1/4"	11	Yellow	15
RPVC516	8	5/16"	13	Transparent	15
RPVC516N	8	5/16"	13	Black	15
RPVC516R	8	5/16"	13	Red	15
RPVC516B	8	5/16"	13	Blue	15
RPVC516G	8	5/16"	13	Green	15
RPVC38	10	3/8"	15	Transparent	12
RPVC38N	10	3/8"	15	Black	12
RPVC38R	10	3/8"	15	Red	12
RPVC38B	10	3/8"	15	Blue	12
RPVC38G	10	3/8"	15	Green	12
RPVC38Y	10	3/8"	15	Yellow	12
RPVC12	13	1/2"	18	Transparent	12
RPVC12N	13	1/2"	18	Black	12
RPVC12R	13	1/2"	18	Red	12
RPVC12B	13	1/2"	18	Blue	12
RPVC12G	13	1/2"	18	Green	12
RPVC12Y	13	1/2"	18	Yellow	12
RPVC58	16	5/8"	21	Transparent	10
RPVC58N	16	5/8"	21	Black	10
RPVC34	19	3/4"	25	Transparent	10
RPVC34N	19	3/4"	25	Black	10
RPVC34R	19	3/4"	25	Red	10
RPVC34B	19	3/4"	25	Blue	10
RPVC1	25	1"	31	Transparent	9
RPVC1N	25	1"	31	Black	9
RPVC114	32	1.1/4"	40	Transparent	6
RPVC112	38	1.1/2"	42	Transparent	6
RPVC2	50	2"	60	Transparent	3
Tech Sheet 1884					

Medium-duty, 15 Metre Coils

5000	ID mm	ID	OD mm	Colour	Max Pressure Bar
RPVC12-15	13	1/2"	18	Transparent	12
RPVC34-15	19	3/4"	25	Transparent	10
RPVC114-15	32	1.1/4"	40	Transparent	6
RPVC112-15	38	1.1/2"	42	Transparent	6
RPVC2-15	50	2"	60	Transparent	3
Tech Sheet 1884					





You might also need **Brass Hose Tails**
see page **1141**

Clips & Clamps



...see pages **1513-1558**

Fluid-Air Components Ltd

BRAIDED PVC HOSE

Reinforced PVC Braided Hose, Type RPVC (to BS6066)



Medium-duty, 100 Metre Coils


5000	ID mm	ID	OD mm	Colour	Max Pressure Bar
RPVC14-100	6	1/4"	11	Transparent	15
RPVC14N-100	6	1/4"	11	Black	15
RPVC14R-100	6	1/4"	11	Red	15
RPVC14B-100	6	1/4"	11	Blue	15
RPVC14G-100	6	1/4"	11	Green	15
RPVC14Y-100	6	1/4"	11	Yellow	15
RPVC516-100	8	5/16"	13	Transparent	15
RPVC516N-100	8	5/16"	13	Black	15
RPVC516R-100	8	5/16"	13	Red	15
RPVC516B-100	8	5/16"	13	Blue	15
RPVC38-100	10	3/8"	15	Transparent	12
RPVC38N-100	10	3/8"	15	Black	12
RPVC38R-100	10	3/8"	15	Red	12
RPVC38B-100	10	3/8"	15	Blue	12
RPVC38Y-100	10	3/8"	15	Yellow	12
RPVC12-100	13	1/2"	18	Transparent	12
RPVC12N-100	13	1/2"	18	Black	12
RPVC12R-100	13	1/2"	18	Red	12
RPVC12B-100	13	1/2"	18	Blue	12
RPVC12Y-100	13	1/2"	18	Yellow	12
RPVC34-100	19	3/4"	25	Transparent	10
RPVC1-100	25	1"	31	Transparent	9
Tech Sheet 1884					

Heavy-duty, 30 Metre Coils

5000	ID mm	ID	OD mm	Colour	Max Pressure Bar
HDPVC14	6.5	1/4"	11.5	Transparent	16
HDPVC14B	6.5	1/4"	11.5	Blue	16
HDPVC14N	6.5	1/4"	11.5	Black	16
HDPVC14R	6.5	1/4"	11.5	Red	16
HDPVC516	8	5/16"	13.5	Transparent	16
HDPVC516B	8	5/16"	13.5	Blue	16
HDPVC516N	8	5/16"	13.5	Black	16
HDPVC516Y	8	5/16"	13.5	Yellow	16
HDPVC38	10	3/8"	16	Transparent	15
HDPVC38B	10	3/8"	16	Blue	15
HDPVC38N	10	3/8"	16	Black	15
HDPVC38R	10	3/8"	16	Red	15
HDPVC38Y	10	3/8"	16	Yellow	15
HDPVC12	12.5	1/2"	18.5	Transparent	12
HDPVC12B	12.5	1/2"	18.5	Blue	12
HDPVC12N	12.5	1/2"	18.5	Black	12
HDPVC12R	12.5	1/2"	18.5	Red	12
HDPVC12Y	12.5	1/2"	18.5	Yellow	12
HDPVC58	16	5/8"	23	Transparent	10
HDPVC34	20	3/4"	26	Transparent	10
HDPVC34B	20	3/4"	26	Blue	10
HDPVC34N	20	3/4"	26	Black	10
HDPVC1	25	1"	33	Transparent	10
HDPVC114	32	1.1/4"	41	Transparent	6
HDPVC112	40	1.1/2"	49	Transparent	6
HDPVC2	50	2"	62	Transparent	3
Tech Sheet 1884					

For **Wash Down Equipment** see pages **1666-1678**





FOOD GRADE BRAIDED PVC HOSE
BS6066 & ISO5774



Food Certified Reinforced PVC Braided Hose

This flexible, smooth, corrosion resistant, non-aging, and non-oxidising food gradevinyl plastic tubing is produced from raw materials meeting the FDA approved material requirement.

This braided PVC hose offers the same basic performance as clear PVC hose with more strength and flexibility making it ideal for tight installations where hose flattening and kinking may occur.

Hose is fully tested, certified and carries the food safe logos.

Applications:

- Food stuffs
- Beers
- Cool fluids
- Oils and gases
- Dry powders and granules

Available Lengths:

30 and 100 metres

Sizes from: 1/4" to 2"

Characteristics:

- Excellent abrasion resistance
- Good flexibility
- High resistance to alkalis/acids
- Silicone free
- Cadmium free
- Non toxic
- Excellent transparency
- Manufactured to comply with BS6066 and ISO5774
- Produced with FDA approved materials
- Durable, non-inflated
- High-flexibility, lightweight and easy to handle
- Non fissure phenomenon by ultraviolet rays and direct rays of the sun
- Little expansion or contraction
- Phthalate free

Hose compliant with European regulation (EU) No. 10/2011



Working Temperature:
-20°C to +65°C

Heavy-duty, 30 Metre Coils


5004	ID mm	ID	OD mm	Max Pressure Bar
FHDPVC14	6.5	1/4"	11.5	16
FHDPVC516	8	5/16"	13.5	16
FHDPVC38	10	3/8"	16	15
FHDPVC12	12.5	1/2"	18.5	12
FHDPVC34	20	3/4"	26	10
FHDPVC1	25	1"	33	10
FHDPVC114	32	1.1/4"	41	6
FHDPVC112	40	1.1/2"	49	6
FHDPVC2	50	2"	62	3
Tech Sheet 10168				

Heavy-duty, 100 Metre Coils

5004	ID mm	ID	OD mm	Max Pressure Bar
FHDPVC14-100	6.5	1/4"	11.5	16
FHDPVC516-100	8	5/16"	13.5	16
FHDPVC38-100	10	3/8"	16	15
FHDPVC12-100	12.5	1/2"	18.5	12
FHDPVC34-100	20	3/4"	26	10
FHDPVC1-100	25	1"	33	10
Tech Sheet 10168				

Fluid-Air Components Ltd

Lightweight Flexible Reinforced PVC Hose



- **Lightweight – 30% lighter than standard PVC**
- **Superior kink resistance compared to standard PVC and rubber**
- **Extremely flexible, making it ideal for use with air tools**

Working Temperature:
-15°C to +60°C

Flexible Lightweight PVC Hose

30 Metre Coils

5080	ID mm	OD mm	Colour	Max Pressure Bar	Max Pressure PSI
FLP-06B	6	10.5	Blue	18	260
FLP-08B	8	12.5	Blue	15	220
FLP-10B	10	14	Blue	13	190
FLP-12B	12	17	Blue	11	160

Tech Sheet 20203

BRAIDED PVC HOSE

Reinforced PVC Braided Hose

Reinforced PVC Braided Hose, Natural, 30 Metre Coils

5081	ID mm	ID	OD
PVC03	3	1/8"	8
PVC05	5	3/16"	10
PVC06	6.3	1/4"	10.5
PVC08	8	5/16"	12
PVC10	10	3/8"	14
PVC12	12.5	1/2"	17.5
PVC12HD	12	1/2"	18
PVC16	16	5/8"	20.25
PVC19	19	3/4"	24
PVC25	25	1"	31
PVC32	32	1.1/4"	42
PVC38	38	1.1/2"	48
PVC50	50	2"	60




Fluid-Air Components Ltd

HI-VIS AIR & WATER RPVC HOSE

FT PRO

Hi-Vis Air & Water RPVC Hose



The Hi-Vis properties of this hose are fully compliant with Health & Safety (Chromaticity Luminance) BS EN ISO 5774 and EN471:2003. A must for all professional facilities and applications.

Features:

- 20 bar rated
- -20°C to +80°C
- Suitable for potable drinking water
- Self-extinguishing
- High visibility
- Flexible PVC
- UV stable
- Multi-use
- White inner, yellow fluorescent outer
- Material softness BSS50/BSS65

Applications:

- Industrial
- Food
- Wash down
- Garage forecourt
- Workshops
- Vending
- Window cleaning/ high rise
- Festivals and outdoor public events

The components used in production of this hose are compliant with EC and FDA requirements

Applicable Standards BS EN ISO 5774 (plastic hoses, textile-reinforced types for compressed air applications.) Tested in accordance with EN471 : 2003 : Section 5.1,5.1.1 and Table 2 for both chromaticity and luminance.

Hi-Vis Medium-duty, 30 Metre Coils

0349	ID mm	OD mm	Bend Radius mm	Max Pressure Bar
HVIS06-30	6.3	11.5	28	20
HVIS08-30	8	13.5	34	20
HVIS10-30	10	16	40	20
HVIS12-30	12.5	18.5	55	20
Tech Sheet 10091				

Hi-Vis Medium-duty, 50 Metre Coils

0349	ID mm	OD mm	Bend Radius mm	Max Pressure Bar
HVIS06-50	6.3	11.5	28	20
HVIS08-50	8	13.5	34	20
HVIS10-50	10	16	40	20
HVIS12-50	12.5	18.5	55	20
Tech Sheet 10091				

Hi-Vis Medium-duty, 100 Metre Coils

0349	ID mm	OD mm	Bend Radius mm	Max Pressure Bar
HVIS06-100	6.3	11.5	28	20
HVIS08-100	8	13.5	34	20
HVIS10-100	10	16	40	20
HVIS12-100	12.5	18.5	55	20
Tech Sheet 10091				

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PVC HOSE & ASSEMBLIES

Reinforced PVC Hose Assemblies

Schrader Standard Series Interchange.



Rectus 17 Series Hose Assemblies

1710	Length Metres	ID
HOSE17/06MM/3M	3	1/4"
HOSE17/06MM/5M	5	1/4"
HOSE17/06MM/10M	10	1/4"
HOSE17/10MM/3M	3	3/8"
HOSE17/10MM/5M	5	3/8"
HOSE17/10MM/10M	10	3/8"
HOSE17/12MM/3M	3	1/2"
HOSE17/12MM/5M	5	1/2"
HOSE17/12MM/10M	10	1/2"

PCL Standard Series Interchange.



Rectus 19 Series Hose Assemblies

1910	Length Metres	ID
HOSE19/06MM/3M	3	1/4"
HOSE19/06MM/5M	5	1/4"
HOSE19/06MM/10M	10	1/4"
HOSE19/10MM/3M	3	3/8"
HOSE19/10MM/5M	5	3/8"
HOSE19/10MM/10M	10	3/8"
HOSE19/12MM/3M	3	1/2"
HOSE19/12MM/5M	5	1/2"
HOSE19/12MM/10M	10	1/2"

- Twist release type coupling.

Schrader Standard Series Interchange.



AP97 Series Hose Assemblies

0097	Length Metres	ID
HOSE97/06MM/3M	3	1/4"
HOSE97/06MM/5M	5	1/4"
HOSE97/06MM/10M	10	1/4"
HOSE97/10MM/3M	3	3/8"
HOSE97/10MM/5M	5	3/8"
HOSE97/10MM/10M	10	3/8"
HOSE97/12MM/3M	3	1/2"
HOSE97/12MM/5M	5	1/2"
HOSE97/12MM/10M	10	1/2"



Rectus 25 Series Hose Assemblies

2510	Length Metres	ID
HOSE25/06MM/3M	3	1/4"
HOSE25/06MM/5M	5	1/4"
HOSE25/06MM/10M	10	1/4"
HOSE25/10MM/3M	3	3/8"
HOSE25/10MM/5M	5	3/8"
HOSE25/10MM/10M	10	3/8"
HOSE25/12MM/3M	3	1/2"
HOSE25/12MM/5M	5	1/2"
HOSE25/12MM/10M	10	1/2"

Clear Un-reinforced PVC Hose, Type CPVC



Temperature Range:
-15°C to +60°C

Standard Coil Length: 30 Metres

Manufactured from top quality crystal clear "virgin" PVC compound, this hose is ideal for conveying fluids, gases, powders and granules at low pressure

Full chemical resistance information is available from our Business Development Team.

All the hoses are made from USF and DA approved material, suitable for food and drink.

All materials used have FDA and BGA, UK S.I. No.1523 and EEC Directive 78/142/EEC Approval for use in food contact applications.

Please note: No recommended burst pressures/ working pressures due to hose being un-reinforced.

Light-duty, 30 Metre Coils

5000	ID mm	ID	OD mm
CPVC18/15	3	1/8"	5
CPVC532/10	4	5/32"	6
CPVC316/15	5	3/16"	7
CPVC14/15	6	1/4"	8
CPVC516/15	8	5/16"	11
CPVC38/15	10	3/8"	12
CPVC12/15	12	1/2"	15
CPVC58/15	15	5/8"	19
CPVC34/15	19	3/4"	22.5
Tech Sheet 20204			

Medium-duty, 30 Metre Coils

5000	ID mm	ID	OD mm
CPVC5/11	5	3/16"	11
CPVC6/12	6	1/4"	12
CPVC8/14	8	5/16"	14
CPVC10/16	10	3/8"	16
CPVC12/18	12	1/2"	18
CPVC16/22	16	5/8"	22
CPVC19/25	19	3/4"	25
CPVC25/31	25	1"	31
Tech Sheet 20205			

FT PRO®



For **Water Guns**
see pages **1657-1658**

Fluid-Air Components Ltd

SUPERIOR RUBBER ALLOY AIR HOSE & ASSEMBLIES

FT PRO

Superior Rubber Alloy Air Hose & Assemblies

The superior rubber alloy hose is the result of years of research and development to find the optimum compound used to manufacture a hose with the total feel and capabilities of a rubber hose but without the associated disadvantages.





Hose can be ordered in various lengths.
Please contact Sales with your application requirements.

Rubber Alloy Air Hose

30 Metre Coils

0410	ID	ID mm	OD mm
SRAH06X	1/4"	6.3	14
SRAH08X	5/16"	8	17
SRAH10X	3/8"	10	19
SRAH13X	1/2"	12.5	23
SRAH19X	3/4"	19	30
SRAH25X	1"	25	37
Tech Sheet 20738			

100 Metre Coils

0410	ID	ID mm	OD mm
SRAH06X-100	1/4"	6.3	14
SRAH08X-100	5/16"	8	17
SRAH10X-100	3/8"	10	19
SRAH13X-100	1/2"	12.5	23
SRAH19X-100	3/4"	19	30
SRAH25X-100	1"	25	37
Tech Sheet 20738			

- **Braided reinforcement:** high tensile polyester braid
- **Highly flexible:** excellent bend radius with anti-kink capabilities
- **Durable:** excellent abrasion resistance, plus oil and fuel resistant outer cover
- **Silicone free**
- **Safe:** highly visible green stripe for safety against becoming a trip hazard
- **Ideal for outside:** excellent ozone resistance, making it a number one choice for outdoor applications
- **Smooth bore:** consistent internal and external dimensions, with a smooth bore for optimum flow

Working Temperature: -20°C to +60°C

Maximum Working Pressure: 20 bar

Fluid-Air Components Ltd

SUPERIOR RUBBER ALLOY AIR HOSE & ASSEMBLIES

Rubber Alloy Hose Assemblies

The new superior rubber alloy hose comes from years of research and development to find the optimum compound used to manufacture a hose with the total feel and capabilities of a rubber hose but without the associated negative aspects.

- High tensile polyester braid for reinforcement
- Excellent bend radius with anti kink capabilities
- Excellent abrasion resistance
- Oil resistant outer cover
- Fuel resistant outer cover
- Silicone free
- Highly visible green stripe for safety against becoming a trip hazard
- Excellent ozone resistance, making it a number one choice for outdoor applications
- Consistent on both internal and external dimensions, with a smooth bore for optimum flow

Each end fitting is brass BSPP female with a 60° sealing cone fixed to the hose via a brass ferrule, giving a full mechanical seal.

Working Temperature:
-20°C to +60°C

Maximum Working Pressure:
20 bar



Female Thread, BSPP

0410	ID	Thread	Length Metres
SRAH06-5	1/4"	1/4"	5
SRAH06-10	1/4"	1/4"	10
SRAH06-15	1/4"	1/4"	15
SRAH06-20	1/4"	1/4"	20
SRAH08-5	5/16"	1/4"	5
SRAH08-10	5/16"	1/4"	10
SRAH08-15	5/16"	1/4"	15
SRAH08-20	5/16"	1/4"	20
SRAH10-5	3/8"	3/8"	5
SRAH10-10	3/8"	3/8"	10
SRAH10-15	3/8"	3/8"	15
SRAH10-20	3/8"	3/8"	20
SRAH13-5	1/2"	1/2"	5
SRAH13-10	1/2"	1/2"	10
SRAH13-15	1/2"	1/2"	15
SRAH13-20	1/2"	1/2"	20



Rectus Series 19

0410	ID	Length Metres
SRAH19/8-5	5/16"	5
SRAH19/10-5	3/8"	5
SRAH19/8-10	5/16"	10
SRAH19/10-10	3/8"	10
SRAH19/8-15	5/16"	15
SRAH19/10-15	3/8"	15
SRAH19/8-20	5/16"	20
SRAH19/10-20	3/8"	20



Rectus Series 100

0410	ID	Length Metres
SRAH100/13-10	1/2"	10
SRAH100/13-15	1/2"	15
SRAH100/13-20	1/2"	20
SRAH100/13-30	1/2"	30



Rectus Series 25

0410	ID	Length Metres
SRAH25/10-5	3/8"	5
SRAH25/10-10	3/8"	10
SRAH25/10-15	3/8"	15
SRAH25/10-20	3/8"	20



Rectus Series 19 Plug x 1/4" Male Thread, BSPT

0410	ID	Length Metres
SRAH08X1/4X19-10	5/16"	10
SRAH08X1/4X19-20	5/16"	20
SRAH10X1/4X19-10	3/8"	10
SRAH10X1/4X19-20	3/8"	20



Rectus Series 100 Plug x 1/2" Male Thread, BSPT

0410	ID	Length Metres
SRAH1/2X100-10	1/2"	10
SRAH1/2X100-20	1/2"	20




Leader Hose, Plug x Male Thread, BSPT, 0.6 Metre Length

0410	ID	Thread	To Suit
LDSRAH06X0.6	1/4"	1/4"	Rectus Series 19
LDSRAH10X0.6	3/8"	3/8"	Rectus Series 19
LDSRAH10X0.6-19	1/2"	1/2"	Rectus Series 19
LDSRAH13X0.6	3/8"	1/4"	Rectus Series 100
LDSRAH10X0.6-XF	3/8"	1/4"	Rectus Series 25

Superior Safety Compressed Air Hose Assemblies





DCH hose is manufactured with a special formula which will outperform PVC and rubber in all application requirements.

- Greater temperature range for all weather and environment applications
- Improved abrasion compared to both PVC and rubber
- Tensile strength 10% better than rubber up to 150kg
- Coupling retention tried and tested up to 200kg
- Excellent flexibility, even in sub zero temperatures
- Full hose traceability

All assemblies are supplied complete with FT Pro safety claw couplings, rubber sealing ring and anti-vibration nuts.

Working Temperature:
-30°C to +60°C

Maximum Working Pressure:
20 bar
3:1 ratio

15 Metre

5995	ID mm	OD mm	Bend Radius mm
DCH-3/4-15SAFETY	19	29	60
	Tech Sheet 20541		

Fluid-Air Components Ltd

SAFETY COMPRESSED AIR HOSE ASSEMBLIES

SAFETY Compressed Air Hose Assembly, 300psi

- Supplied complete with Jaymac safety claw couplings and clamps, which have fitted as standard anti-vibration nyloc style nuts
- High quality mandrel built rubber hose (RTH only)



Rubber, 15 Metre Coils

5995	ID mm	OD mm
RTH-3/4-15SAFETY	19	29
Tech Sheet 20207		



PVC, 15 Metre Coils

5995	ID mm	OD mm
PTH-3/4-15SAFE	19	29
Tech Sheet 20207		

Compressed Air Hose

HOSE ONLY



Hose Only Rubber, 15 Metre Coils

5995	ID mm	OD mm
RTH-3/4-15M	19	29

Safety Valves

The HoseGuard® is a simple, but efficient protection of a broken compressed-air hose. The air supply is shut off immediately by the HoseGuard®, should the volume of air exceed a set value. This "value" is preset by the manufacturer and is of course, set in a way that allows normal air consumption when using air tools. The HoseGuard® is made so that it ensures a constant bleeding through a tiny nozzle, making the hoseguard return to zero position, once the broken hose has been repaired. The HoseGuard® remains closed until the connection to the mains pipe has been disconnected.


Protection of personnel, machinery and equipment EU 983 and ISO 4414 standard conformity



Air Fuses, BSPP

0093	Thread	Inlet	Outlet	LPM
281A0211	1/4"	Female	Female	0-740
281A0221	1/4"	Male	Female	0-740
281A0311	3/8"	Female	Female	0-2400
281A0321	3/8"	Male	Female	0-2400
281A0411	1/2"	Female	Female	0-4000
281A0421	1/2"	Male	Female	0-4000
281A0511	3/4"	Female	Female	0-5300
281A0611	1"	Female	Female	0-11000
281A0911	2"	Female	Female	0-37000
Tech Sheet 1350				

Whip Check Hose Safety Device



We recommend the use of whip checks on all compressor hose assemblies.

Whip Check Hose Safety Device

0019	OD	Kg
WCSD-1332	1/2" to 1.1/4"	560
WCSD-3876	1.1/2" to 3"	2300
Tech Sheet 10247		

Compressed Air Plant Hose 300psi



PVC Hose

5995	ID	OD mm	Length Metres
PTH-1/2-100	1/2"	22	100
PTH-3/4-90	3/4"	29	90
PTH-1-60	1"	35	60
Tech Sheet 20206			

COMPRESSED AIR HOSE & ASSEMBLIES

Rubber Air Hose Assemblies



1/4" Male Thread, BSPT

6000	ID	Length Feet	Length Metres
RUB14-25	1/4"	25	7.6
RUB14-50	1/4"	50	15.2
RUB38-25	3/8"	25	7.6
RUB38-50	3/8"	50	15.2



1/4" Male Thread BSPT x Blow Gun

6000	ID	Length Feet	Length Metres	Blow Gun Type
RUB14-25ASG	1/4"	25	7.6	ASG-1
RUB14-50ASG	1/4"	50	15.2	ASG-1
RUB38-25ASG	3/8"	25	7.6	ASG-1
RUB14-25BG5	1/4"	25	7.6	BG5
RUB38-25BG5	3/8"	25	7.6	BG5
RUB38-50BG5	3/8"	50	15.2	BG5
RUB38-25BG718	3/8"	25	7.6	BG718
RUB38-50BG718	3/8"	50	15.2	BG718

Compressed Air Hoses

Black smooth abrasion resistant rubber cover with black oil mist resistant rubber tube.

Single braid of synthetic cord reinforcement conforming to BS5118/1 (300psi W.P.) and to the physical requirements of BS ISO 2398 Type 3 Class A 1995.

Maximum Working Pressure:
20 bar



300psi Compressed Air Plant Hose, 100 Metre Coils

6013	ID	ID mm	OD mm
PTL-3/16-100	3/16"	5	13
PTL-1/4-100	1/4"	6	14
PTL-5/16-100	5/16"	8	16
PTL-3/8-100	3/8"	10	18
PTL-1/2-100	1/2"	13	22
PTL-3/4-100	3/4"	19	29

175psi Rubber Compressed Air Hose

Manufactured to BS5119/1,
BS ISO 2398 Type 3, Class A 1995

Maximum Working Pressure:
12 bar



25 Metre Coils

6000	ID	ID mm	OD mm
2020-8294	1/4"	6.3	12.5
2020-8369	5/16"	8	16
2020-8377	3/8"	10	17
2020-8385	1/2"	13	22
2044-1028	5/8"	16	27
2044-1036	3/4"	19	30
2044-1044	1"	25	38
Tech Sheet 20180			

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Aqua Vend - Water Vending Hose

Reinforced PVC hose. Ideal for the conveyance of potable cold and hot water. Mirror smooth inner layers for improved flow rates. WRC approved material, will not support microbiological growth. Manufactured to BS EN ISO 9002.



10 Metre Coils

6010	ID mm	OD mm	Max Pressure PSI	Max Pressure Bar
AQV-12-10	6.3	12	300	20.5
AQV-16-10	10	16	221	15
AQV-19-10	12.5	19	216	15
AQV-26-10	19	26	191	13
AQV-33-10	25	33	147	10
Tech Sheet 10266				

30 Metre Coils

6010	ID mm	OD mm	Max Pressure PSI	Max Pressure Bar
AQV-12-30	6.3	12	300	20.5
AQV-16-30	10	16	221	15
AQV-19-30	12.5	19	216	15
AQV-26-30	19	26	191	13
Tech Sheet 10266				

150 psi Non Marking Wash Down Hose

White smooth rubber cover and white rubber tube with single braid of synthetic cord reinforcement suitable for use with hot water up to 100ºC and a maximum operating pressure of 150psi. The non marking cover is animal fat resistant.



50 Metre Coils

5998	ID	OD mm
WDH-1/2-50	1/2"	21

Dairy Steam Hose, FDA Approved

Tube: White EPDM food quality, taste and odour free
Reinforcement: High tensile textile cord
Cover: EPDM blue smooth with cloth impression
Application: Dairy washdown hose, resistant against alcohol and bacteria, FDA approved material

Working Temperature:
-35°C to +170°C

Maximum Working Pressure:
7 bar



40 Metre Coils

0429	ID	ID mm	OD mm	Bend Radius mm
DWH-12	1/2"	13	23	91
DWH-34	3/4"	19	31	133
DWH-1	1"	25	37	175
Tech Sheet 10545				

Tiger Tail Effluent Hose

Working Temperature:
-40°C to +60°C



With Cuffs, 15 Metre Coils

0437	ID	ID mm
TIGERTAIL-51-15	2"	51

AUTOMOTIVE TUBING & HOSE

Corrugated Radiator Hose

Lining: Black heat resistant EPDM rubber.
Reinforcement: Synthetic textile fabric, with steel wire helix, embedded between the layers.
Cover: Black, heat, weather, ozone resistant EPDM rubber.

Temperature Range: -40°C to +120°C

Maximum Working Pressure: 2 bar



1 Metre Lengths

6014	ID	ID mm	OD mm	Max Pressure PSI
CRH-78	7/8"	22	30	30
CRH-1	1"	25	34	30
CRH-118	1.1/8"	28	36	30
CRH-114	1.1/4"	32	41	30
CRH-138	1.3/8"	35	45	30
CRH-112	1.1/2"	38	47	30
CRH-134	1.3/4"	44.5	55	30
CRH-2	2"	51	61	30

Radiator Hose

Tube: Black SBR (anti-freeze) resistant rubber.
Reinforcement: Polyester type cord 2 ply.
Safety Factor: 3:1
Cover: Black SBR heat abrasion and weather resistant.
Application: Vehicle radiator hose ethylene glycol (anti-freeze) resistant.

Temperature Range: -30°C to +100°C

Maximum Working Pressure: 3 bar



1 Metre Lengths

6000	ID	ID mm	OD mm	Max Pressure PSI
RH-78	7/8"	22	30	45
RH-1	1"	25	34	45
RH-118	1.1/8"	28	36	45
RH-1316	1.3/16"	30	38	45
RH-114	1.1/4"	32	41	45
RH-138	1.3/8"	35	45	45
RH-112	1.1/2"	38	47	45
RH-1916	1.9/16"	40	49	45
RH-158	1.5/8"	42	52	45
RH-134	1.3/4"	45	55	45
RH-178	1.7/8"	48	58	45
RH-2	2"	51	61	45
RH-214	2.1/4"	57	67	45
RH-238	2.3/8"	60	70	45
RH-212	2.1/2"	63	73	45
RH-3	3"	76	86	45
RH-4	4"	102	112	45

Car Heater Hose SAEJ20R3

Tube: Black coolant and heat resistant rubber.
Reinforcement: High Strength Polyester yarn 2 Ply.
Cover: Abrasion ozone and heat resistant rubber.
Application: Automotive O.E.M. and replacement market for under bonnet use.

Temperature Range: -35°C to +100°C

Maximum Working Pressure: 9 bar



20 Metre Coils

6012	ID	ID mm	OD mm	Max Pressure PSI
2020-9276	3/8"	9.53	19	132
2020-9284	1/2"	12.5	21	132
2020-9292	5/8"	16	23	132
2020-9300	3/4"	19	27	132
2035-3637	1"	25	36	132

Cotton Overbraid Fuel Hose DIN 73379 Type B 1983

Tube: Black fuel and oil resistant rubber.
Cover: Cotton
Application: Fuel hose for automotive use (including unleaded)
Safety Factor: 3:1

Temperature Range: -40°C to +85°C Max Peak

Maximum Working Pressure: 145 psi (10 bar)



20 Metre Coils

6015	ID mm	OD mm
COF-3.2	3.2	7
COF-3.5	3.5	7.5
COF-4.0	4	9
COF-4.5	4.5	9.5
COF-5.0	5	10
COF-5.5	5.5	10.5
COF-6.0	6	11
COF-7.0	7	12
COF-7.5	7.5	12.5
COF-8.0	8	13
COF-9.0	9	14
COF-10	10	15
COF-12	12	18

Tech Sheet 10267

Petrol Hose, SAEJ30R6

Tube: Black fuel and oil resistant rubber.
Reinforcement: Polyester yarn 2 ply.
Cover: Black abrasion oil and ozone weather resistant.
Application: Delivery of petrol/diesel and petroleum based product. For the replacement automotive market.
Safety Factor: 3:1 minimum

Working Temperature: -30°C to +100°C



10 Metre Coils

6021	ID	ID mm	OD mm	Max Pressure PSI
2020-9318	3/16"	5	11	290
2020-9326	1/4"	6	12	290
2020-9334	5/16"	8	14	290
2020-9359	3/8"	10	18	290
2035-3645	1/2"	13	23	290

Diesel Drop Hose

Application: Diesel, air and water delivery up to 20 bar
Tube: Oil resistant rubber alloy
Reinforcement: Synthetic textile braid
Cover: Black weather and ozone resistant with purple stripe
Safety Factor: 3-1



50 Metre Coils

6016	ID	OD mm
P6320/019	3/4"	28
P6320/025	1"	34

Tech Sheet 10801

Bio Diesel Hose ISO 1307

Tube: Fuel and oil Resistant, smooth NBR rubber.
Reinforcement: High tensile synthetic textile.
Cover: Abrasion, ozone, weather and oil resistant special synthetic rubber.
Application: Delivery of fuels in internal combustion engines for lubrication and greasing services.

Working Temperature: -35°C to +70°C

Maximum Working Pressure: 10 bar

Burst Pressure: 30 bar
Minimum Bend Radius: 8mm-50mm and 10mm-65mm
Weight: 8mm-145 g/m and 10mm 170 g/m
Cut to Length: Max length 50 metres



Cut to Length, Per Metre

6000	ID mm	OD mm
OTR445-10NL-08	8	14
OTR445-10NL-10	10	16

Fluid-Air Components Ltd

Radiator Hose

Tube: Heat resistant EPDM rubber
Reinforcement: High tensile synthetic textile
Cover: Heat, aging and weather resistant EPDM based rubber
Application: Cooling systems of automotive and stationary engines.

Working Temperature:
-40°C to +125°C

Maximum Working Pressure: 4 bar



90° Bend, 8" Legs

0276	ID mm
RAD-90-10	10
RAD-90-13	13
RAD-90-16	16
RAD-90-19	19
RAD-90-22	22
RAD-90-25	25
RAD-90-28	28
RAD-90-32	32
RAD-90-35	35
RAD-90-38	38
RAD-90-51	51
RAD-90-63	63
RAD-90-76	76

Bio Diesel Delivery Hose

Tube: Flexible smooth oil resistant PVC/NBR compound
Reinforcement: Synthetic textile
Cover: Black weather and ozone resistant
Application: For the transfer of diesel, fuels, water and air in more demanding service environments.

Working Temperature:
-10°C to +60°C

Maximum Working Pressure: 20 bar



50 Metre

0277	ID	ID mm	OD mm
BIODDH-34	3/4"	19	28
BIODDH-1	1"	25	34

Coolant & Heater Hose (SAE J20 Class A)

Working Temperature:
-50°C to +170°C

Maximum Working Pressure:
5 bar

- 3 ply polyester reinforced silicone; colour blue.
- Wall thickness 4.5mm ± 0.5mm.
- Smooth finish inner and outer.
- 1 metre long.



Straight

0276	ID mm
CHS8	8
CHS95	9.5
CHS11	11
CHS13	13
CHS16	16
CHS19	19
CHS22	22
CHS25	25
CHS28	28
CHS32	32
CHS35	35
CHS38	38
CHS41	41
CHS45	45
CHS48	48
CHS51	51
CHS54	54
CHS57	57
CHS60	60
CHS63	63
CHS70	70
CHS76	76
CHS89	89
CHS102	102

- 3 ply polyester reinforced silicone; colour blue.
- Both leg lengths 102mm unless otherwise stated.
- Wall thickness 4.5mm ± 0.5mm.
- Finish smooth inside, fabric wrapped rubber finish on the outside.



45° Angled Elbows

0276	ID mm
CH4513	13
CH4516	16
CH4519	19
CH4522	22
CH4525	25
CH4528	28
CH4532	32
CH4535	35
CH4538	38
CH4541	41
CH4545	45
CH4548	48
CH4551	51
CH4554	54
CH4557	57
CH4560	60
CH4563	63
CH4570	70
CH4576	76

- 3 ply polyester reinforced silicone for 9.5 to 70 bore, 4 ply for 76 bore and above; colour blue.
- Leg length 102mm.
- Wall thickness 3 ply 4.5mm ± 0.5mm. 4 ply 6mm ± 0.5mm.
- Smooth finish inner and outer.



90° Elbows Bus & Truck

0276	ID mm
CH9013	13
CH9016	16
CH9019	19
CH9022	22
CH9025	25
CH9028	28
CH9032	32
CH9035	35
CH9038	38
CH9041	41
CH9045	45
CH9048	48
CH9051	51
CH9054	54
CH9057	57
CH9060	60
CH9063	63
CH9070	70
CH9076	76
CH9089	89
CH90102	102



135° Elbows

0276	ID mm
CH13513	13
CH13522	22
CH13535	35
CH13538	38
CH13541	41
CH13551	51
CH13554	54
CH13557	57

GAS HOSE

Orange Propane Hose

Orange smooth pin pricked rubber cover and black rubber tube with a single braid of synthetic cord reinforcement. Conforms to EN5591995.

Please note:
For assemblies please contact Technical Sales.

Working Temperature: -40°C to +90°C

Maximum Working Pressure: 20 bar



25 Metre Coils

6000	ID	OD mm
GWH-1/4-250	1/4"	14
GWH-5/16-250	5/16"	16
GWH-3/8-250	3/8"	18

15 Metre Coils

6000	ID	OD mm
GWH-1/4-15	1/4"	14
GWH-5/16-15	5/16"	16
GWH-3/8-15	3/8"	18

10 Metre Coils

6000	ID	OD mm
GWH-1/4-10	1/4"	14
GWH-5/16-10	5/16"	16
GWH-3/8-10	3/8"	18

Galvanised Overbraid Propane Hose

Working Temperature: -30°C to +70°C

Maximum Working Pressure: 20 bar



Propane 25 Metre Coils

6000	ID	OD mm
GGWH-1/4-25	1/4"	13.3
GGWH-3/8-25	3/8"	17

Blue Oxygen/Red Acetylene Twin Hose

Working Temperature: -35°C to +90°C

Maximum Working Pressure: 20 bar



50 Metre Coils

6000	ID	OD mm
GWH-1/4-50-TWIN	1/4"	13
GWH-5/16-50-TWIN	5/16"	15
GWH-3/8-50-TWIN	3/8"	17

Tech Sheet 10046

FT PRO

For **Welding Gauges**



...see page **412**

Gas Welding Hose

Single line oxy-acetylene hose with red or blue smooth rubber cover with black rubber tube. Single braid of synthetic cord reinforcement. Conforms to EN 559 1995.

Please note:
For assemblies please contact Technical Sales.

Working Temperature: -35°C to +90°C

Maximum Working Pressure: 20 bar



Blue Oxygen, 25 Metre Coils

6000	ID	OD mm
GWH-1/4-25B	1/4"	13
GWH-5/16-25B	5/16"	15
GWH-3/8-25B	3/8"	17

Blue Oxygen, 100 Metre Coils

6000	ID	OD mm
GWH-1/4-100B	1/4"	13
GWH-5/16-100B	5/16"	15
GWH-3/8-100B	3/8"	17

Working Temperature: -35°C to +90°C

Maximum Working Pressure: 20 bar



Red Acetylene, 25 Metre Coils

6000	ID	OD mm
GWH-1/4-25R	1/4"	13
GWH-5/16-25R	5/16"	15
GWH-3/8-25R	3/8"	17

Red Acetylene, 100 Metre Coils

6000	ID	OD mm
GWH-1/4-100R	1/4"	13
GWH-5/16-100R	5/16"	15
GWH-3/8-100R	3/8"	17

Fluid-Air Components Ltd

WELDING HOSE SETS & COUPLINGS

Oxygen Hose Sets

Swaged hose sets conforming to EN559 Hose and BS6158 check valves. All hoses tested.

Sets consists of two lengths of hose oxygen and acetylene complete with double safety check valve, nuts and tails.



Acetylene

0085	ID	Length Metres	Check Valve
2050-2217	1/4"	5	1/4" BSPP
2050-2225	1/4"	10	1/4" BSPP
2050-2233	1/4"	15	1/4" BSPP
2050-2241	1/4"	20	1/4" BSPP
2050-2258	1/4"	5	3/8" BSPP
2050-2266	1/4"	10	3/8" BSPP
2050-2274	1/4"	15	3/8" BSPP
2050-2282	1/4"	20	3/8" BSPP
2050-2290	5/16"	5	3/8" BSPP
2050-2308	5/16"	10	3/8" BSPP
2050-2316	5/16"	15	3/8" BSPP
2050-2324	5/16"	20	3/8" BSPP
2050-2332	3/8"	5	3/8" BSPP
2050-2340	3/8"	10	3/8" BSPP
2050-2357	3/8"	15	3/8" BSPP
2050-2365	3/8"	20	3/8" BSPP

Swaged hose sets conforming to EN559 Hose and BS6158 check valve. All hoses tested.

Sets consists of two lengths of hose oxygen and propane complete with double safety check valve, nuts and tails.



Propane

0085	ID	Length Metres	Check Valve
2050-2373	1/4"	5	1/4" BSPP
2050-2381	1/4"	10	1/4" BSPP
2050-2415	1/4"	5	3/8" BSPP
2050-2506	3/8"	10	3/8" BSPP
2050-2522	3/8"	20	3/8" BSPP

OXY/ACETYLENE EQUIPMENT

Oxy/Acetylene Couplings



Hex Nipples

0121	Description
OEMC14	1/4" BSPP Right Hand
AEMC14	1/4" BSPP Left Hand
OEMC38	3/8" BSPP Right Hand
AEMC38	3/8" BSPP Left Hand
OEMC3814	3/8" x 1/4" BSPP Right Hand
AEMC3814	3/8" x 1/4" BSPP Left Hand



Tails

0121	Description
OT1414	1/4" Tail for 1/4" Nuts
OT1438	1/4" Tail for 3/8" Nuts
OT516	5/16" Tails
OT38	3/8" Tails



Double Check Safety Valve

0121	Description
ODSCV3838	3/8" Tail with 3/8" Oxy Nut Right Hand
ADSCV3838	3/8" Tail with 3/8" Acet Nut Left Hand
ODSCV51638	5/16" Tail with 3/8" Oxy Nut Right Hand
ADSCV51638	5/16" Tail with 3/8" Acet Nut Left Hand
ODSCV1438	1/4" Tail with 3/8" Oxy Nut Right Hand
ADSCV1438	1/4" Tail with 3/8" Acet Nut Left Hand
ODSCV1414	1/4" Tail with 1/4" Oxy Nut Right Hand
ADSCV1414	1/4" Tail with 1/4" Acet Nut Left Hand




Nuts, BSPP

0121	Description
ON14	1/4" Right Hand
AN14	1/4" Left Hand
ON38	3/8" Right Hand
AN38	3/8" Left Hand

OVER BRAIDED HOSE & FITTINGS

Due to changed regulations, the supplied fittings may differ from the images shown, brass nickel-plated versions will be phased out and replaced by brass

EPDM Rubber Hose, 304 Stainless Steel Overbraid




Working Temperature:
-20°C to +100°C

30 Metres

5003	ID mm	OD mm	Max Pressure Bar
BX-8	8	12	15
BX-10	10	14	15
BX-13	13	18	15
BX-19	19	27	10

Nitrile Rubber Hose, Galvanised Steel Overbraid



Working Temperature:
-20°C to +80°C

50 Metres

5003	ID mm	OD mm	Max Pressure Bar
BR-6	6	10	15
BR-8	8	13	15
BR-10	10	15	15
BR-13	13	19	10

Straight Hose Tail Fittings, Brass



Male Thread, BSPT

5003	To Suit Hose ID	Thread
MC1/8-6	6mm (1/4")	1/8"
MC1/4-6	6mm (1/4")	1/4"
MC1/4-8	8mm (5/16")	1/4"
MC3/8-8	8mm (5/16")	3/8"
MC3/8-10	10mm (3/8")	3/8"
MC1/2-10	10mm (3/8")	1/2"
MC3/8-13	13mm (1/2")	3/8"
MC1/2-13	13mm (1/2")	1/2"
MC3/4-13	13mm (1/2")	3/4"
MC1/2-16	16mm (5/8")	1/2"
MC3/4-19	19mm (3/4")	3/4"
MC1-25	25mm (1")	1"
MC11/4-32	32mm (1.1/4")	1.1/4"



Female Thread, Coned Seat, BSPP

5003	To Suit Hose ID	Thread
FO1/8-6	6mm (1/4")	1/8"
FO1/4-6	6mm (1/4")	1/4"
FO3/8-6	6mm (1/4")	3/8"
FO1/4-8	8mm (5/16")	1/4"
FO3/8-10	10mm (3/8")	3/8"
FO3/8-13	13mm (1/2")	3/8"
FO1/2-13	13mm (1/2")	1/2"
FO3/4-16	16mm (5/8")	3/4"
FO3/4-19	19mm (3/4")	3/4"
FO11/4-32	32mm (1.1/4")	1.1/4"

Not supplied with washers.
For washers see page 1421



Female Thread, Flat Faced Seat, BSPP

5003	To Suit Hose ID	Thread
FP3/8-10BX	10mm (3/8")	3/8"
FP1/2-10BX	10mm (3/8")	1/2"
FP3/4-10BX	10mm (3/8")	3/4"
FP3/8-13BX	13mm (1/2")	3/8"
FP1/2-13BX	13mm (1/2")	1/2"
FP3/4-13BX	13mm (1/2")	3/4"
FP3/4-16BX	16mm (5/8")	3/4"
FP3/4-19BX	19mm (3/4")	3/4"
FP1-19BX	19mm (3/4")	1"
FP1-25BX	25mm (1")	1"
FP11/2-40BX	40mm (1.1/2")	1.1/2"



Metric Compression, Brass/Nickel Plated

5003	To Suit Hose ID	OD mm
MB15-10BX	10mm (3/8")	15
MB15-13BX	13mm (1/2")	15
MB22-13BX	13mm (1/2")	22
MB22-19BX	19mm (3/4")	22

Fluid-Air Components Ltd

OVER BRAIDED HOSE & FITTINGS

90º Elbow Hose Tail Fittings, Brass

Not supplied with washers.



Female Thread, Flat Face, BSPP

5003	To Suit Hose ID	Thread
FPN1/2-8	8mm (5/16")	1/2"
FPN3/8-10	10mm (3/8")	3/8"
FPN1/2-10	10mm (3/8")	1/2"
FPN3/4-10	10mm (3/8")	3/4"
FPN1/2-13	13mm (1/2")	1/2"
FPN3/4-13	13mm (1/2")	3/4"
FPN3/4-16	16mm (5/8")	3/4"
FPN3/4-19	19mm (3/4")	3/4"



Female Thread, Coned Seat, BSPP


5003	Material	To Suit Hose ID	Thread
FON1/4-6	Steel	6mm (1/4")	1/4"
FON1/4-8	Steel	8mm (5/16")	1/4"
FON3/8-10	Brass	10mm (3/8")	3/8"
FON1/2-13	Brass	13mm (1/2")	1/2"
FON3/4-16	Brass	16mm (5/8")	3/4"
FON3/4-19	Brass	19mm (3/4")	3/4"
FON1-25	Brass	25mm (1")	1"

Metric Standpipe, Brass/Nickel Plated



5003	To Suit Hose ID	OD mm
HCL8-6	6mm (1/4")	8
HCL10-10	10mm (3/8")	10
HCL12-10	10mm (3/8")	12
HCL15-13	13mm (1/2")	15
HCL22-19	19mm (3/4")	22

Aluminium Crimping Ferrules



5003	ID mm A	ID mm B	OD mm	Length mm
B12X14	9	12	14	17
B13X15	9	13	15	17
B14X16	9.5	14	16	20
B16X18	12	16	18	20
B18X20	13	18	20	23
B20X22	15	20	22	25
B21X23	15	21	23	26
B23X25	17	23	25	26
B26X28	20	26	28	30
B28X30	19	28	30	30
B33X35	26	33	35	33
B36X38	26	36	38	35
B46X50	37	46.5	50	53
B67X70	52	67	70	56

Imperial Standpipe, Brass



5003	To Suit Hose ID	OD
E5/16-20	8mm (5/16")	5/16"
E3/8-20	10mm (3/8")	3/8"


EDPM Rubber & Fibre Washers



5003	Material	Thread
15-8-2MM	EPDM	3/8"
19-10-2MM	EPDM	1/2"
24-14-2MM	EPDM	3/4"
G12	FIBRE	1/2"
G1	FIBRE	1"
G112	FIBRE	1.1/2"
G2	FIBRE	2"

Stainless Steel Crimping Ferrules

stainless steel



5003	ID mm A	ID mm B	OD mm	Length mm
B11X12SS	8	11	12	18
B13X14SS	9.3	13	14	18
B18.5X19.5SS	14	18.5	19.5	23
B15X16SS	11	15	16	20
B23X25SS	17	23	25	29
B29X30SS	21	29	30.5	31
B36X38SS	26	36	37.6	36

Hose Crimper, Manual



5003	OD mm
UPS1	10-22

Tech Sheet 10647

WATER HOSES

WATER FLEX
Flexible PVC Water Hose

Applications:
- Market gardens
- Truck cleaning
- Glass houses
- Water spraying/sprinklers

Features:
- Durable PVC cover
- Abrasion resistant
- Polyester high tensile fibre reinforcement
- Outstanding kink resistance
- Thick layer structure







Working Temperature:
-15°C to +60°C

25 Metre Coils

5080	ID mm	OD mm	Max Pressure Bar
GH12	12.5	17.5	11
GH19	19	25.5	7
GH25	25	32.5	6

Tech Sheet 20215

50 Metre Coils

5080	ID mm	OD mm	Max Pressure Bar
GH12-50	12.5	17.5	11
GH19-50	19	25.5	7
GH25-50	25	32.5	6

Tech Sheet 20215

100 Metre Coils


5080	ID mm	OD mm	Max Pressure Bar
GH12-100	12.5	17.5	11
GH19-100	19	25.5	7
GH25-100	25	32.5	6

Tech Sheet 20215

Heavy-duty 4 Layer Agricultural Water Hose

A high quality 4 layer agricultural hose with excellent flexibility and abrasive qualities enables this hose to be used in various applications:
- Agricultural • Industrial • Domestic

Working Temperature:
-10°C to +80°C



50 Metre Coils

5000	ID	ID mm	OD mm	Pressure Bar	Max Pressure Bar
HDAWH12	1/2"	12.5	17.5	9	50
HDAWH34	3/4"	19	25	8	45

Tech Sheet 20215

TRICOFLEX
Tricoflex Watering Hose

Applications:
- Market gardens
- Truck cleaning
- Glass houses
- Water spraying/sprinklers

Features:
- Durable PVC cover
- Abrasion resistant
- Polyester high tensile fibre reinforcement
- Outstanding kink resistance
- Thick layer structure

Working Temperature:
-15°C to +60°C







25 Metre Coils

5082	ID mm	Max Pressure Bar
TRICO12	12.5	30
TRICO19	19	23
TRICO25	25	22

Tech Sheet 20215

100 Metre Coils

5082	ID mm	Max Pressure Bar
TRICO12-100M	12.5	30
TRICO19-100	19	23
TRICO25-100	25	22

Tech Sheet 20215

Fluid-Air Components Ltd

FT PRO® Essential for Engineers



FT Pro understands how critical it is having the right components for fluid power applications. That's why we offer an extensive range of products that are meticulously chosen to suit the unique requirements of all industries.

Our experienced team carefully evaluates each product to ensure that it meets our stringent quality standards and can withstand the requirements of daily use in demanding industrial environments.

Our product ranges continuously evolve to keep up with technological advancements and industry changes. We strive to exceed our customers expectations by offering the range of components for your needs. Whether you're looking for compressed air hoses, hydraulic hoses, couplings, valves, or other fluid power components, we have the products you need when you need them.

At **FT Pro**, our customers can quickly source the essential products they need for their projects and be confident that they are of the highest quality.

We take pride in offering exceptional customer service and technical support to ensure our customers receive the best possible experience when selecting our products.

1423

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

LAYFLAT HOSE

Layflat Delivery Hos

Applications: Conveyance and discharge of water etc. Particularly suitable for irrigation and water supply applications. However, can also be used in general industries, civil and construction engineering.

Pressures: Values given are based on the short term burst pressure of the hose at 20°C based on a 3:1 safety factor.


This product is only suitable for open ended discharge applications. Pressure ratings are based on discharge pressure from the pump unit.

Note: Any increase in temperature above 20°C will result in a decline in working pressure values.

Chemical Resistance: Resistant to the oils and greases as above. These hoses are not suitable for use with benzene, petrol, spirits, xylol, toluol or solvents containing aromatics. For more detailed information please contact technical sales.

Temperature Range:
-15°C to +55°C





Blue, 10 Metre Coils

5993	ID	ID mm	Max Pressure Bar
LFH1-10	1"	25	4.5
LFH114-10	1.1/4"	32	4.5
LFH112-10	1.1/2"	38	4.5
LFH2-10	2"	51	4.5
LFH212-10	2.1/2"	64	4.5
LFH3-10	3"	76	4.5
LFH4-10	4"	102	4.5
LFH6-10	6"	150	4.5
LFH8-10	8"	200	4.5
Tech Sheet 20208			

Blue, 100 Metre Coils

5993	ID	ID mm	Max Pressure Bar
LFH1-100	1"	25	4.5
LFH114-100	1.1/4"	32	4.5
LFH112-100	1.1/2"	38	4.5
LFH2-100	2"	51	4.5
LFH212-100	2.1/2"	64	4.5
LFH3-100	3"	76	4.5
LFH4-100	4"	102	4.5
LFH6-100	6"	150	4.5
LFH8-100	8"	200	4.5
Tech Sheet 20208			





Yellow, 10 Metre Coils

5993	ID	ID mm	Max Pressure Bar
YLH-1-10	1"	25	6
YLH-114-10	1.1/4"	32	6
YLH-112-10	1.1/2"	38	6
YLH-2-10	2"	51	6
YLH-3-10	3"	76	6
YLH-4-10	4"	102	6
YLH-5-10	5"	127	6
YLH-6-10	6"	152	6
YLH-8-10	8"	203	6
Tech Sheet 20212			

Yellow, 100 Metre Coils

5993	ID	ID mm	Max Pressure Bar
YLH-1	1"	25	6
YLH-114	1.1/4"	32	6
YLH-112	1.1/2"	38	6
YLH-2	2"	51	6
YLH-3	3"	76	6
YLH-4	4"	102	6
YLH-5	5"	127	6
YLH-6	6"	152	6
YLH-8	8"	203	6
Tech Sheet 20212			

Layflat Hose Coupling

Male Coupling

Female Coupling



Please note:
two items are needed to make a coupling set.



Male

6000	To Suit Hose ID
LMC-1	1"
LMC-114	1.1/4"
LMC-112	1.1/2"
LMC-2	2"
LMC-212	2.1/2"
LMC-3	3"
LMC-4	4"
LMC-5	5"
Tech Sheet 20209	

Female

6000	To Suit Hose ID
LFC-1	1"
LFC-114	1.1/4"
LFC-112	1.1/2"
LFC-2	2"
LFC-212	2.1/2"
LFC-3	3"
LFC-4	4"
Tech Sheet 20209	


You might also need...

Individual Couplings



see page **1505**

Fluid-Air Components Ltd



LAYFLAT HOSE

JAYMAC
Industrial Hose & Accessories

High Pressure Layflat Delivery Hose

Application:
Conveyance and discharge of fluids under pressure. Particularly suitable for irrigation and water supply applications in general industries, civil and construction engineering, agricultural and ship building.

Pressures:
Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.


This product is only suitable for open-ended discharge applications. Pressure ratings are based on discharge pressure from the pump unit.

Note:
Any increase in temperature above +20°C will result in a decline in working pressure values.

Chemical Resistance:
Resistant to oils and greases. These hoses are not suitable for use with benzene, petrol, spirits, xylol, or solvents containing aromatics. For more detailed information please contact Technical Sales.

Benefits:
Layflat hoses provide high performance whilst being lightweight compared with the same size of spiral PVC delivery hoses and rubber discharge hoses. Additionally they are easier to store, handle and transport.

Cut down lengths are available upon request.



Working Temperature:
-5°C to +65°C

Maximum Working Pressure: 10 bar

Blue, 10 Metre Coils

5993	ID	ID mm	Max Pressure Bar
HPLFH1-10	1"	25	10
HPLFH114-10	1.1/4"	32	10
HPLFH112-10	1.1/2"	38	10
HPLFH2-10	2"	51	10
HPLFH212-10	2.1/2"	64	8
HPLFH3-10	3"	76	8
HPLFH4-10	4"	102	8
Tech Sheet 20210			

Blue, 100 Metre Coils

5993	ID	ID mm	Max Pressure Bar
HPLFH1-100	1"	25	10
HPLFH114-100	1.1/4"	32	10
HPLFH112-100	1.1/2"	38	10
HPLFH2-100	2"	51	10
HPLFH212-100	2.1/2"	64	8
HPLFH3-100	3"	76	8
HPLFH4-100	4"	102	8
Tech Sheet 20210			

1425

YELLOW PVC LAYFLAT ASSEMBLIES



Yellow PVC Layfla is manufactured with a smooth and seamless inner surface and smooth PVC cover. A very high adhesion between inner and outer layers assembled with Band-It clamps male/female lever lock couplings.

This product is only suitable for open ended discharge applications. Pressure ratings are based on discharge pressure from the pump unit.



Maximum Working Pressure: 6 bar
Bursting Pressure: 18 bar

Assemblies


0180	Coupling Size	ID mm	Weight Kg	Length Metres
YLH2-25M-ASSY	2"	51	10	25
YLH2-50M-ASSY	2"	51	19	50
YLH2-100M-ASSY	2"	51	37	100
YLH3-25M-ASSY	3.1/2"	76	15	25
YLH3-50M-ASSY	3.1/2"	76	29	50
YLH3-100M-ASSY	3.1/2"	76	57	100
YLH4-25M-ASSY	4"	102	22	25
YLH4-50M-ASSY	4"	102	41	50
YLH4-100M-ASSY	4"	102	78	100
YLH6-25M-ASSY	6"	152	47	25
YLH6-50M-ASSY	6"	152	87	50
YLH6-100M-ASSY	6"	152	167	100
YLH8-25M-ASSY	8"	203	62	25
YLH8-50M-ASSY	8"	203	112	50

Non-returnable

Bespoke lengths are available upon request


Please note: Due to transportation difficulties and the nature of this product, additional carriage charges may apply, based on weight, dimensions and location of delivery. Please speak to our Business Development Team for full details of carriage costs.

BLUE PVC LAYFLAT ASSEMBLIES



Blue PVC Layfla is manufactured with a smooth and seamless inner surface and smooth PVC cover. A very high adhesion between inner and outer layers assembled with Band-It clamps male/female lever lock couplings.

This product is only suitable for open ended discharge applications. Pressure ratings are based on discharge pressure from the pump unit.



Maximum Working Pressure:
2"–4 bar
3"–3 bar
4"–3 bar
6"–2.5 bar
8"–3 bar
Bursting Pressure: 3:1

Assemblies

0180	Coupling Size	ID mm	Weight Kg	Length Metres
BLH2-25M-ASSY	2"	51	7	25
BLH2-50M-ASSY	2"	51	14	50
BLH3-25M-ASSY	3.1/2"	76	10	25
BLH3-50M-ASSY	3.1/2"	76	17	50
BLH3-100M-ASSY	3.1/2"	76	33	100
BLH4-25M-ASSY	4"	102	17	25
BLH4-50M-ASSY	4"	102	31	50
BLH4-100M-ASSY	4"	102	59	100
BLH6-25M-ASSY	6"	152	32	25
BLH6-50M-ASSY	6"	152	57	50
BLH6-100M-ASSY	6"	152	107	100

Non-returnable

Bespoke lengths are available upon request

Please note: Due to transportation difficulties and the nature of this product, additional carriage charges may apply, based on weight, dimensions and location of delivery. Please speak to our Business Development Team for full details of carriage costs.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SUCTION HOSE



Medium-duty Suction Hose

Cold Bend: -45°C

Vacuum: 680mm Hg = 90% at +20°C

Approximately 15% lighter than heavy-duty suction hose.


Applications: General pumping and suction applications in agricultural and construction industries. Conveyance of water, sludge, slurry, chemicals and other waste matter.

Pressures: Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.

Note: Any increase in temperature above +20°C will result in a decline in working pressure values.

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis.

For more detailed information please contact Technical Sales.



Working Temperature: -5°C to +65°C

Olive Green, 6 Metre Coil, Straight Length

5996	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
MDS6-6	6"	7.5	3	800
		Tech Sheet 20211		

Olive Green, 10 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
MDS1-10	1"	3.8	7	125
MDS114-10	1.1/4"	4	7	160
MDS112-10	1.1/2"	4.4	6	190
MDS2-10	2"	4.8	5	250
MDS212-10	2.1/2"	5.2	4.5	315
MDS3-10	3"	5.2	5	300
MDS312-10	3.1/2"	5.5	4	375
MDS4-10	4"	6.3	4	400
MDS6-10	6"	7.5	3	800
		Tech Sheet 20211		

Olive Green, 30 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
MDS34-30	3/4"	3.6	7	100
MDS1-30	1"	3.8	7	125
MDS114-30	1.1/4"	4	7	160
MDS112-30	1.1/2"	4.4	6	190
MDS2-30	2"	4.8	5	250
MDS212-30	2.1/2"	5.2	4.5	315
MDS3-30	3"	5.2	5	300
MDS312-30	3.1/2"	5.5	4	375
MDS4-30	4"	6.3	4	400
MDS6-30	6"	7.5	3	800
		Tech Sheet 20211		

GREEN SUCTION HOSE ASSEMBLIES



Green PVC Suction Hose Assemblies

are manufactured in an opaque green flexible PVC containing a white spiral helix. All assemblies are fitted with male/female lever lock couplings, attached with Band-It clamps.



Working Temperature: -10°C to +60°C

Cold Blend: -45°C

Vacuum: 680mm Hg = 90% at 20°C

Maximum Working Pressure: 2", 3", 4" – 3 bar 6" and 8" – 2 bar

Bursting Pressure: 3:1

Assemblies

0180	Coupling Size	ID mm	Weight Kg	Length Metres
GMDSLLC2-6M	2"	51	5	6
GMDSLLC3312-6M	3.1/2"	76	10	6
GMDSLLC4-6M	4"	102	16	6
GMDSLLC6-6M	6"	152	32	6
GMDSLLC8-6M	8"	203	48	6
		Tech Sheet 2089		

Non-returnable

Bespoke lengths are available upon request

Please note: Due to transportation difficulties and the nature of this product, additional carriage charges may apply, based on weight, dimensions and location of delivery. Please speak to our Business Development Team for full details of carriage costs.

Larger sizes available upon request

SUCTION HOSE



Superflexible Medium-duty Suction Hos

Superflexible medium-duty suction hose is a robust general purpose hose. It has excellent weathering and crush resistance and is extremely easy to handle due to its extra flexibilit . It has a white helix spiral encased in a superflexible green pvc.

Industries: Suitable for general pumping and suction applications within the agricultural, construction and water treatment industries.

Applications: Conveyance of water, sludge, slurry, and other waste matter. Can also be used to convey small particles like animal feed and plastic pellets.

Working Temperature:
-5°C to +60°C

Vacuum: 680mm Hg = 90% at +20°C

Pressure: Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis

For more details please contact Technical Sales.

Note: Any increase in temperature above +20°C will result in a decline in working pressure values.



Dark Olive Green, 10 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
SFMDS34-10	3/4"	3.3	8	100
SFMDS1-10	1"	3.5	8	110
SFMDS114-10	1.1/4"	3.7	7	135
SFMDS112-10	1.1/2"	4	7	150
SFMDS2-10	2"	4.3	6.5	200
SFMDS212-10	2.1/2"	5.2	7	250
SFMDS3-10	3"	5	4.5	300
SFMDS312-10	3.1/2"	5.5	5	350
SFMDS4-10	4"	6	5	400
SFMDS6-10	6"	7.5	2	600
Tech Sheet 10222				

Dark Olive Green, 30 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
SFMDS34-30	3/4"	3.3	8	100
SFMDS1-30	1"	3.5	8	110
SFMDS114-30	1.1/4"	3.7	7	135
SFMDS112-30	1.1/2"	4	7	150
SFMDS2-30	2"	4.3	6.5	200
SFMDS212-30	2.1/2"	5.2	7	250
SFMDS3-30	3"	5	4.5	300
SFMDS312-30	3.1/2"	5.5	5	350
SFMDS4-30	4"	6	5	400
SFMDS6-30	6"	7.5	2	600
Tech Sheet 10222				

SUCTION HOSE



Heavy-duty Suction Hose

Smooth inside and outside non-restricting tube. The ridged PVC spiral resists crushing impact. High abrasion resistance makes it ideal to transfer powder.

Industries: Suitable for construction, civil engineering, agriculture and ships.

Applications: Suction discharge for sand, gravel, cement and iron fittings, suction and press-transfer of various grains.

Pressure: Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis.
For more details please contact Technical Sales.

Note: Any increase in temperature above +20°C will result in a decline in working pressure values.

Working Temperature:
-5°C to +65°C



10 Metres

5996	ID	Max Pressure Bar	Bend Radius mm
HDSH2-10	2"	7	300
HDSH3-10	3"	5	450
HDSH4-10	4"	5	630
HDSH6-10	6"	4	1100
Tech Sheet 60441			

30 Metres

5996	ID	Max Pressure Bar	Bend Radius mm
HDSH2-30	2"	7	300
HDSH3-30	3"	5	450
HDSH4-30	4"	5	630
HDSH6-30	6"	4	1100
Tech Sheet 60441			

Fluid-Air Components Ltd

OIL RESISTANT SUCTION HOSE





Oil resistant medium-duty suction hose is a robust general purpose oil hose. It has a smooth bore for minimum flow resistance. Excellent weathering and crush resistance. It has a white helix spiral encased in an oil resistant blue pvc.

Applications: Designed for the use of transporting fuel/oils, and is suitable for many industrial areas.

Vacuum: 680mm Hg = 90% at +20°C

Pressure: Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.

Chemical Resistance: Suitable for low aromatic content including oil, diesel, paraffin, hydraulic oils, mineral based oils, lubricating oils and greases.

Working Temperature:
-15°C to +60°C

For more details please contact our Technical Sales.

Note: Any increase in temperature above +20°C will result in a decline in working pressure values.

Blue, 10 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar
BORS34-10	3/4"	3.5	8
BORS1-10	1"	4	8
BORS114-10	1.1/4"	4	7
BORS112-10	1.1/2"	4.5	7
BORS2-10	2"	4.5	6.5
BORS212-10	2.1/2"	4.5	5
BORS3-10	3"	5	4.5
Tech Sheet 10223			

Blue, 30 Metre Coils

5996	ID	Wall Thickness mm	Max Pressure Bar
BORS34-30	3/4"	3.5	8
BORS1-30	1"	4	8
BORS114-30	1.1/4"	4	7
BORS112-30	1.1/2"	4.5	7
BORS2-30	2"	4.5	6.5
BORS212-30	2.1/2"	4.5	5
BORS3-30	3"	5	4.5
Tech Sheet 10223			

FT PRO®



For **Cam & Groove Quick Couplings** see pages **1467-1472**

10 BAR WATER SUCTION HOSE

Hose Assemblies & Hose

- Hose assemblies are manufactured with black SBR tubes and ozone-resistant SBR covers.
- The reinforcement is manufactured from high tensile textile cords embedded with steel helix wires for vacuum resistance.
- All assemblies are fitted with male/female lever lock couplings.
- Assemblies are available with any combination of fittings including flange, cam and groove.



Please contact our Business Development Team for a quote.
Material and test certification can be supplied.

Working Temperature:
-30°C to +70°C

Maximum Working Pressure:
150 psi



Hose Assemblies (Ultra-lok Bands)

0180	Coupling Size	ID mm	OD mm	Length Metres	Assembly Max Working Pressure
WALLC2-3M	2"	51	62	3	10
WALLC2-6M	2"	51	62	6	10
WALLC3312-3M	3.1/2"	76	89	3	10
WALLC3312-6M	3.1/2"	76	89	6	10
WALLC4-3M	4"	102	115	3	10
WALLC4-6M	4"	102	115	6	10
WALLC6-3M	6"	152	168	3	7
WALLC6-6M	6"	152	168	6	7

Hose Only

0180	ID mm	OD mm	Length Metres
WA2-6M	51	62	6
WA3-6M	76	89	6
WA4-6M	102	115	6
WA6-3M	152	168	3
WA8-3M	203	222	3

Fluid-Air Components Ltd

WATER DELIVERY HOSE



Cold Bend: -45°C

Vacuum: 570mm Hg = 75% at +20°C

Applications: Delivery and light suction of water, slurry, chemicals, some granules, sewage and other waste matter. Particularly suitable for the horticultural and marine industries.


Pressures: Values given are based on the short term burst pressure of the hose at +20°C based on a 3:1 safety factor.

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis.

For more detailed information please contact Technical Sales.

Note: Any increase in temperature above +20°C will result in a decline in working pressure values.

Working Temperature: -15°C to +65°C



Translucent Green, 10 Metre Coils

5994	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
WDH34-10	3/4"	2.4	8	110
WDH1-10	1"	2.4	8	140
WDH114-10	1.1/4"	2.6	8	180
WDH112-10	1.1/2"	3	8	210
WDH2-10	2"	3.6	7	270
WDH212-10	2.1/2"	3.7	6	350
WDH3-10	3"	4.1	5	500
WDH4-10	4"	5.6	5	330
Tech Sheet 20213				

Translucent Green, 30 Metre Coils

5994	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
WDH34-30	3/4"	2.4	8	110
WDH1-30	1"	2.4	8	140
WDH114-30	1.1/4"	2.6	8	180
WDH112-30	1.1/2"	3	8	210
WDH2-30	2"	3.6	7	270
WDH212-30	2.1/2"	3.7	6	350
WDH3-30	3"	4.1	5	500
WDH4-30	4"	5.6	5	330
Tech Sheet 20213				

WIRE REINFORCED SUCTION HOSE



Wire Reinforced Suction Hose

Clear PVC reinforced with a tensile steel helix

Applications: Suitable for the suction and discharge of water, slurry, chemicals, sewage, granules and other waste materials; can also be used for suction and discharge of foodstuffs.

Pressures: Values given are based on the short term burst pressure of the hose at 20°C based on a 3:1 safety factor.

Note: Any increase in temperature above 20°C will result in a decline in working pressure values.

Working Temperature: -5°C to +65°C

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis.

For more detailed information please contact technical sales.

Approvals: Hose complies fully to EU No.10/201 on plastic materials and articles intended to come into contact with food.

Cold bend: -45°C

Vacuum: 711mm Hg = 94% at 20°C



Clear with Blue Wire Spiral, 10 Metre Coils

5997	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
FX075-10	3/4"	3.4	6	80
FX100-10	1"	3.5	6	100
FX125-10	1.1/4"	3.5	5	130
FX150-10	1.1/2"	4.0	5	155
FX200-10	2"	4.5	5	200
FX250-10	2.1/2"	5.5	4	260
FX300-10	3"	7.5	4	320
FX400-10	4"	8	4	430
Tech Sheet 20214				

Clear with Blue Wire Spiral, 30 Metre Coils

5997	ID	Wall Thicknes mm	Max Pressure Bar	Bend Radius mm
FX050-30	1/2"	3	6	50
FX075-30	3/4"	3.5	6	80
FX100-30	1"	3.5	6	100
FX125-30	1.1/4"	4.0	5	130
FX150-30	1.1/2"	4.5	5	155
FX200-30	2"	5.5	5	200
FX250-30	2.1/2"	7	4	260
FX300-30	3"	7.5	4	320
FX400-30	4"	8	4	430
Tech Sheet 20214				

HOZELOCK TRICOFLEX

Thermoclean 100, 15 bar

Bursting Pressure: at 23°C = 30 bar
Application:
Food quality industrial cleaning
Grease and cleaning agent resistant

Working Temperature:
-15°C up to +100°C max

Maximum Working Pressure:
100°C 15 bar



Blue, 20 Metre Coils

5082	ID mm	OD mm	Wall Thickness mm
TRI-145571	13	22	4.5
TRI-145655	16	25	4.5
TRI-145671	19	28	4.5
TRI-145597	25	34	4.5
Tech Sheet 890			

Thermoclean AL20, 20 bar

Bursting Pressure: at 23°C = 100 bar
Application:
Food quality industrial cleaning
Grease and cleaning agent resistant

Working Temperature:
-15°C up to +70°C max

Maximum Working Pressure:
70°C 20 bar



Blue, 25 Metre Coils

5082	ID mm	OD mm	Wall Thickness mm
TRI-100236	12	20	4
TRI-100284	19	28	5
Tech Sheet 889			

Reinforced Breathing Hose

- Breathing air hose with reinforcement
- Complies with EN 139
- Heat resistant, with an oil resistant cover
- Anti-static resistance 10-6 in accordance with NF EN ISO8031

50 metre coils available upon request.



Nobelair AS EN139, Blue, 25 Metre Coils

5082	ID mm	Max Pressure Bar	Burst Pressure Bar	Wall Thickness mm
TRI-092856	8	15	60	3
TRI-092872	10	15	60	3
Tech Sheet 884				

CONTRACTORS HOSE

Un-reinforced PVC Hose

Standard Coil Lengths: 75 Metres

For delivering water at tap pressure.

- Low cost alternative
- Used extensively on construction sites
- Bespoke lengths available

Colour: Black

Not recommended working or burst pressures due to the hose being un-reinforced.

Working Temperature:
-10°C to +60°C

Black, 75 Metre Coils

0384	ID mm	OD mm
CH-13/19-75	13	19
CH-19/25-75	19	25
CH-25/34-75	25	34
Tech Sheet 10260		

Manufactured from a high quality PVC compound this un-reinforced hose is an excellent hose solution with great flexibility, ideal for conveying fluids, gases, granules and powders at low pressure.

- Excellent abrasion resistance
- Durable
- Resistant to a wide range of chemicals
- Flexible
- Excellent UV resistance



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c


INDUSTRIAL HOSE

Marine Fuel Hose

Type A1 Specification: ISO 7840 A1.
Type A2 Specification: ISO 7840 A2.
Application: Fuel hose for marine craft.
Tube: Black, fuel resistant NBR rubber.
Type A1 Reinforcement: Synthetic textile.

Working Temperature:
-35°C to +100°C

Type A2 Reinforcement: Synthetic textile fabric, twin steel wire helix.
Cover: Black, abrasion, ozone, weather, heat and oil resistant neoprene rubber.
Safety Factor: 3-1.



Type A1, 10 Metre Coils, 10 bar

6018	ID mm	OD mm
L633.4/005X10	5	12
L633.4/006X10	6	13
L633.4/008X10	8	16
L633.4/010X10	10	18
L633.4/013X10	13	22
L633.4/016X10	16	25
L633.4/019X10	19	29

Type A2, 10 Metre Coils, 5 bar

6018	ID mm	OD mm
T633.4/025X10	25	35
T633.4/038X10	38	48

Type A1, 40 Metre Coils, 10 bar

6018	ID mm	OD mm
L633.4/005X40	5	12
L633.4/006X40	6	13
L633.4/008X40	8	16
L633.4/010X40	10	18
L633.4/013X40	13	22
L633.4/016X40	16	25
L633.4/019X40	19	29

Type A2, 40 Metre Coils, 5 bar

6018	ID mm	OD mm
T633.4/025X40	25	35
T633.4/032X40	32	42
T633.4/038X40	38	48

XLPE CHEMICAL SUCTION & DELIVERY HOSE

DESCRIPTION:
Chemical suction and delivery hose with XLPE tube for tank trucks and storage tanks. Suitable for handling a wide range of chemical products.

INNER TUBE:
XLPE clear, smooth and resistant to a wide range of chemicals, with black rubber backing.

REINFORCEMENT:
High tensile textile cord, steel wire helix, anti-static wire.

COVER:
Green, smooth with cloth impression. Abrasion, weather and ozone resistant.

Working Temperature:
-30°C to +90°C

Maximum Working Pressure:
16 bar



40 Metre Coils

0464	ID	ID mm	OD mm	Bend Radius mm
XLPECSDH-13-40	1/2"	13	25	65
XLPECSDH-19-40	3/4"	19	32	95
XLPECSDH-25-40	1"	25	39	125
XLPECSDH-32-40	1.1/4"	32	47	160
XLPECSDH-38-40	1.1/2"	38	53	190
XLPECSDH-51-40	2"	51	67	255
Tech Sheet 60132				

10 Metre Coils

0464	ID	ID mm	OD mm	Bend Radius mm
XLPECSDH-13-10	1/2"	13	25	65
XLPECSDH-19-10	3/4"	19	32	95
XLPECSDH-25-10	1"	25	39	125
XLPECSDH-32-10	1.1/4"	32	47	160
XLPECSDH-38-10	1.1/2"	38	53	190
XLPECSDH-51-10	2"	51	67	255
Tech Sheet 60132				

INDUSTRIAL HOSE

Marine Exhaust Hose

Lloyds Approved
Specification: SAEJ2006R1
Application: Wet exhaust hose for marine craft.
Tube: Black, exhaust gas, salt water resistant EPDM rubber.
Reinforcement: Synthetic textile fabrics, steel wire helix.
Cover: Black, corrugated, resistant to heat, salt water, ozone and abrasion EPDM rubber.
Safety Factor: 3-1

Working Temperature:
-30°C to +100°C



10 Metre Coils

6017	ID mm	OD mm
SAJ2006R1/032X10	32	41
SAJ2006R1/038X10	38	47
SAJ2006R1/045X10	45	54

40 Metre Coils

6017	ID mm	OD mm
SAJ2006R1/051X40	51	60

Diesel Drop Hose

Application: For diesel, air, water delivery up to 20 Bar
Reinforcement: Synthetic textile braid
Cover: Black weather and ozone resistant with purple stripe
Safety Factor: 3-1




50 Metre Coils

5999	ID mm	OD mm	Max Pressure Bar
DDRH19X-50	3/4"	28	20
DDRH25X-50	1"	34	20

Non-toxic Suction Discharge Hose

Cold Bend: -45°C
Vacuum: 570mm Hg = 75% at 20°C
Raw materials used have FDA approval for use with foodstuffs.
Applications: Suction and discharge applications of liquids and solids.
Pressures: Values given are based on the short term burst pressure of the hose at 20°C based on a 3:1 safety factor.
Note: Any increase in temperature above 20°C will result in a decline in working pressure values.
Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis.
For more detailed information please contact technical sales.

Working Temperature:
-15°C to +65°C



Clear with White Spiral, 5 Metre Coils

6020	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
FQSD1-5	1"	2.8	5	130
FQSD114-5	1.1/4"	3	5	155
FQSD112-5	1.1/2"	3.4	5	182
FQSD2-5	2"	4.1	5	235
FQSD212-5	2.1/2"	4.2	5	290
FQSD3-5	3"	4.7	5	340
FQSD4-5	4"	6	4	470


Clear with White Spiral, 10 Metre Coils

6020	ID	Wall Thickness mm	Max Pressure Bar	Bend Radius mm
FQSD1-10	1"	2.8	5	130
FQSD114-10	1.1/4"	3	5	155
FQSD112-10	1.1/2"	3.4	5	182
FQSD2-10	2"	4.1	5	235
FQSD212-10	2.1/2"	4.2	5	290
FQSD3-10	3"	4.7	5	340
FQSD4-10	4"	6	4	470

Medusa Super Elastic Hose

Strong, flexible and smooth, shock and crush resistant PVC spiral. Good in cold climates.
Applications: Medium-duty suction and delivery of water, salt water, light chemicals, liquids, sewer purging, sludge, sand and gravel.
Reinforcement: Blue nylon spiral.

Working Temperature:
-20°C to +60°C



Medium-duty Suction & Delivery, 10 Metre Coils

6019	ID mm	Burst Pressure Bar	Bend Radius mm
GSE-51-10	2"	15	200
GSE-63-10	2.1/2"	14	275
GSE-76-10	3"	12	310
GSE-102-10	4"	10	410
GSE-152-10	6"	9	610

Medium-duty Suction & Delivery, 30 Metre Coils

6019	ID mm	Burst Pressure Bar	Bend Radius mm
GSE-51	2"	15	200
GSE-63	2.1/2"	14	275
GSE-76	3"	12	310
GSE-102	4"	10	410
GSE-152	6"	9	610

Fluid-Air Components Ltd

Multipurpose Hose

This blue multipurpose fuel and oil hose is manufactured with a smooth NBR/PVC cover and a smooth NBR/SBR liner, and is reinforced with high tensile polyester yarn.


Key Features:
- Good resistance to abrasion, weather and oil
- Resistant to petroleum products and certain solvents

Application:
- Low pressure applications, for air, oil and water

Construction:
- Inner tube: oil resistant NBR
- Reinforcement: polyester yarn
- Cover: smooth blue, oil and weather resistant NBR/PVC blended
- Safety factor 3-1

Working Temperature: -20°C to +70°C

Working Pressure: 20 bar



100 Metre Coils

0525	ID	OD mm
MPAOW-04-100	1/4"	13
MPAOW-05-100	5/16"	15
MPAOW-06-100	3/8"	17
MPAOW-08-100	1/2"	21
MPAOW-12-100	3/4"	29
MPAOW-16-100	1"	35.5
Tech Sheet 68079		

50 Metre Coils

0525	ID	OD mm
MPAOW-10-50	5/8"	25
Tech Sheet 68079		

Buhar Steam Hose

Applications: For saturated steam service where non-marking is required. BS5122/A2.

Reinforcement: High tensile synthetic textile.

Cover: Abrasion, heat, steam ozone and weather resistant, pin-pricked special synthetic rubber.

Tube: EPM rubber, resistant to steam up to 170°C.

Working Temperature: -40°C to +170°C



White Steam Non-marking, 10 Metres

0429	ID	Bend Radius mm
SHW-13-10	1/2"	80
SHW-19-10	3/4"	135
SHW-25-10	1"	170

White Steam Non-marking, 40 Metres

0429	ID	Bend Radius mm
SHW-13	1/2"	80
SHW-19	3/4"	135
SHW-25	1"	170

Brewflex 10

Applications: For delivery of beverages such as mineral water, beer, fruit juices, wine and liqueurs.

Reinforcement: High tensile synthetic textile.

Cover: Weather, ozone, and abrasion resistant coloured synthetic rubber.

Tube: White non-toxic, taste and odour free synthetic EPDM rubber.

Working Temperature: -40°C to +80°C



Brewers Delivery, 10 Metres

6011	ID	Bend Radius mm
BDH-19-10	3/4"	190
BDH-25-10	1"	254
BDH-32-10	1.1/4"	320
BDH-32-10	1.1/4"	320

Brewers Delivery, 40 Metres

6011	ID	Bend Radius mm
BDH-19	3/4"	190
BDH-25	1"	254
BDH-32	1.1/4"	320
BDH-38	1.1/2"	380

ANTI-STATIC HOSE

Air & Water

Durable all rubber constructed hose, fully complying with the requirement of BS 2050 specification for 20 bar working pressure.

- Suitable for all compressed air application
- Suitable for use where anti-static properties are preferred e.g. refineries, offshore oil and gas applications

Electrical Resistance Ω:
Min 3 x 10^5 per m - max 10^6

Construction:
Lining: Electrically conductive SBR rubber.
Cover: Smooth black SBR rubber.

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar



BS2050, 20 Metre Coils

0387	ID	OD mm	Max Pressure Bar	Burst Pressure Bar
ASAH-1/4-20	1/4"	14	20	60
ASAH-5/16-20	5/16"	16	20	60
ASAH-3/8-20	3/8"	18	20	60
ASAH-1/2-20	1/2"	22	20	60
ASAH-5/8-20	5/8"	26	20	60
ASAH-3/4-20	3/4"	30	20	60
ASAH-1-20	1"	36	20	60
Tech Sheet 10304				

FOOT VALVES & STRAINERS

FT PRO

Foot Valves



Foot Valves, Hose Tail

0019	To Suit Hose ID
NFV-2	2"
NFV-3	3"
NFV-4	4"
NFV-6	6"



Malleable Iron Foot Valves, BSPP

0019	Thread
FOOT150	1.1/2"
FOOT200	2"
FOOT250	2.1/2"
FOOT300	3"
FOOT400	4"
FOOT600	6"

Strainers



Foot Valve Strainer, Hose Tail

0019	To Suit Hose ID
FVS-112	1.1/2"
FVS-3	3"
FVS-4	4"



Strainer - Hose Tail, Zinc Plated Steel

0121	To Suit Hose ID
TCSHT1	1"
TCSHT114	1.1/4"
TCSHT112	1.1/2"
TCSHT2	2"
TCSHT212	2.1/2"
TCSHT3	3"
TCSHT4	4"
TCSHT6	6"
TCSHT8	8"



Strainer - Screwed Female BSPP, Zinc Plated Steel

0121	Thread
TCSBSP112	1.1/2"
TCSBSP2	2"
TCSBSP3	3"
TCSBSP4	4"

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FT PRO®

INDUSTRIAL PUR DUCTING

This high performance ducting range is produced in Europe and is made from premium-grade ester polyurethane compound, reinforced with a copper-coated spring steel helix.

Applications:

Transport hose for abrasive solids including: dust, powder, fibres, etc. Also suitable for extracting gaseous media such as oil vapours and welding fume.

- Excellent abrasion resistance
- Wire spiral reinforcement can be earthed
- Super flexible, low weight
- Small bend radius
- Good resistance to oil, petrol and chemicals
- High tensile strength and tear resistance

Advanced Features:

- Anti-static wall – electrical and surface resistance, $<10^9\Omega$
- Flame retardant
- Microbe resistant

Working Temperature:
-40°C to +90°C
Intermittent to:
+125°C



1437

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

INDUSTRIAL PUR DUCTING

Lightweight High Performance Polyurethane

Wall Thickness: 0.4mm approx.
Supplied in compressed form (4:1) to save space and cost
Use clamp type 212/212EC (refer to page 1447).



0.4mm Wall Thickness, 10 Metres

0391	ID mm	OD mm
PURLW-38	38	46
PURLW-50	50	58
PURLW-60	60	68
PURLW-65	65	73
PURLW-75	75	83
PURLW-80	80	88
PURLW-90	90	98
PURLW-100	100	108
PURLW-115	115	123
PURLW-120	120	128
PURLW-125	125	133
PURLW-130	130	138
PURLW-140	140	148
PURLW-150	150	158
PURLW-160	160	168
PURLW-180	180	188
PURLW-200	200	208
PURLW-225	225	234
PURLW-250	250	259
Tech Sheet 110820		

Medium Weight High Performance Polyurethane

Wall Thickness: 0.6mm approx.
Supplied in compressed form (3:1) to save space and cost
Use clamp type 212/212EC (refer to page 1447).



0.6mm Wall Thickness, 10 Metres

0391	ID mm	OD mm
PURMW-38	38	45
PURMW-50	50	58
PURMW-60	60	68
PURMW-65	65	73
PURMW-75	75	83
PURMW-80	80	88
PURMW-90	90	98
PURMW-100	100	108
PURMW-115	115	123
PURMW-120	120	128
PURMW-125	125	133
PURMW-130	130	138
PURMW-140	140	148
PURMW-150	150	158
PURMW-160	160	168
PURMW-180	180	188
PURMW-200	200	208
PURMW-225	225	233
PURMW-250	250	258
PURMW-300	300	309
PURMW-350	350	359
PURMW-400	400	409
Tech Sheet 68801		

Smooth Bore PU Ducting

Colour:
Clear with grey spiral

Working Temperature:
-20°C to +80°C

Construction:

- Ester based PU
- Shock resistant PVC spiral, crushing, chemical agents, abrasion and weather resistant, corrugated outside
- Smooth bore for optimal flow

Applications:

Suction and transportation of abrasive media such as powders, pellets, granulates, fibres, industrial ventilation and airflow systems. Also dust, gases, liquids and powders.

- Food grade according to (EU) No 10/2011



20 Metre Coils

6023	ID mm	Bend Radius mm
PUSB-25-20	25	60
PUSB-38-20	38	78
PUSB-51-20	51	100
PUSB76-20	76	145
PUSB-102-20	102	200
PUSB-127-20	127	250
Tech Sheet 20559		

10 Metre Coils

6023	ID mm	Bend Radius mm
PUSB-25-10	25	60
PUSB-38-10	38	78
PUSB-51-10	51	100
PUSB76-10	76	145
PUSB-102-10	102	200
PUSB-127-10	127	250
PUSB-152-10	152	305
PUSB-203-10	203	410
Tech Sheet 20559		

Medium-duty Smooth Bore PVC Ducting

- Extremely light and flexible plasticised PVC.
- Shock resistant PVC spiral.
- Abrasion, crushing, chemical agents and weather resistant corrugated outside.
- Industrial ventilation and airflow systems, suction of dust, air, gases, powders, liquids etc.

Working Temperature:
-10°C to + 60°C



General Purpose, 10 Metre Coils

6023	ID mm	Bend Radius mm
URU-25-10	25	30
URU-32-10	32	35
URU-38-10	38	45
URU-51-10	51	60
URU-76-10	76	100
URU-102-10	102	140
URU-152-10	152	180
URU-203-10	203	400
Tech Sheet 10509		

Available per metre, contact sales for more information.


Fluid-Air Components Ltd



NORRES | Baggerman
Better. Stronger. Together

Hf o ma y p ioa e

- Food & pharma
- Automotive/vehicle industry
- Plastics industry
- Industrial vacuum cleaners
- Fume & dust extraction
- Shot blasting/sand blasting
- Wood processing industry
- Agricultural industry
- Sweeping & cleaning machines
- Oil & Gas
- Robotics



Rubber & PVC hoses

- PU hoses
- Full plastic hoses
- Rubber hoses
- Fabric hoses
- Compost hoses
- Connection

1439

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

ABRASION-RESISTANT, ANTI-STATIC INDUSTRIAL PUR DUCTING

PROTAPE PUR 301 AS





Made from premium-grade ester Pre-PUR polyurethane, reinforced with a copper-coated spring steel wire helix.

Wall Thickness: 0.4mm approx.

Applications: Suction and transport hose for abrasive materials, e.g. dust, chippings, powder, granules, fibres, etc

Also suitable for fume extraction, e.g. oil mist, welding fumes and chemical vapours.

- Permanently anti-static wall, <10⁹Ω
- Super lightweight, highly flexibl
- Flame retardant to DIN 4102-B1 and UL94-HB
- Microbe resistant
- Supplied poly-sleeved in compressed form
- Excellent abrasion resistance
- High tensile strength and tear resistance
- Optimised flow (observe direction of flow arro
- Small bend radius
- Good resistance to oil, petrol and chemicals
- Wire spiral reinforcement can be earthed

Use clamp type 212/212EC (refer to page 1447).


Working Temperature:
-40°C to +90°C
Intermittent to:
+125°C approx



Lightweight, 0.4mm Wall, Flame Retardant, Anti-static, 10 Metres

0392	ID mm	OD mm
301-0038-0000	38	46
301-0050-0000	50	58
301-0065-0000	65	73
301-0075-0000	75	83
301-0100-0000	100	108
301-0125-0000	125	133
301-0150-0000	150	158
301-0160-0000	160	168
301-0200-0000	200	208
301-0225-0000	225	234
301-0250-0000	250	259
301-0300-0000	300	309
Tech Sheet 20017		

PROTAPE PUR 330 AS





Made from premium-grade ester Pre-PUR polyurethane, reinforced with a copper-coated spring steel wire helix.

Wall Thickness: 0.6mm approx.

Applications: Suction and transport hose for abrasive material, e.g. dust, chippings, powder, granules, fibres, etc

Also suitable for fume extraction, e.g. oil mist, welding fumes and chemical vapours.

- Permanently anti-static wall, <10⁹Ω
- Super lightweight, highly flexibl
- High tensile strength and tear resistance
- Flame retardant to DIN 4102-B1 and UL94-HB
- Optimised flow (observe direction of flow arro
- Microbe resistant
- Supplied poly-sleeved in compressed form
- Small bend radius
- Good resistance to oil, petrol and chemicals
- Wire spiral reinforcement can be earthed

Use clamp type 212/212EC (refer to page 1447).

Working Temperature:
-40°C to +90°C
Intermittent to:
+125°C



Light/Medium Weight, 0.6mm Wall, Flame Retardant, Anti-static, 10 Metres

0392	ID mm	OD mm
330-0038-1002	38	45
330-0050-1002	50	58
330-0065-1002	65	73
330-0075-1002	75	83
330-0100-1002	100	108
330-0125-1002	125	133
330-0150-1002	150	158
330-0160-1002	160	168
330-0200-1002	200	208
330-0225-1002	225	233
330-0250-1002	250	258
330-0300-1002	300	309
330-0350-1002	350	359
330-0400-1002	400	409
Tech Sheet 60192		

AIRDUC PUR 350 AS





Made from premium-grade ester Pre-PUR polyurethane, reinforced with a thicker gauge spring steel wire helix.

Wall Thickness: 0.7mm approx.

Applications: Suction and transport hose for highly abrasive materials, e.g. dust, powder, granules, chippings, pellets, fibres, shot blast recovery, etc. Also suitable for fumes or gaseous media.

- Permanently anti-static wall, <10⁹Ω
- Flame retardant to DIN 4102-B1 and UL94-V2
- Microbe resistant
- Excellent abrasion resistance
- High tensile strength and tear resistance
- Smooth bore, optimised flow (observe direction of flow arrow
- Small bend radius
- Good resistance to oil, petrol and chemicals
- Wire spiral reinforcement can be earthed

Working Temperature:
-40°C to +90°C
Intermittent to: +125°C



Medium Weight, 0.7mm Wall, Flame Retardant, Anti-static, 10 Metres

0392	ID mm	OD mm
350-0038-1002	38	45
350-0050-1002	50	57
350-0065-1002	65	70
350-0075-1002	75	82
350-0100-1002	100	107
350-0125-1002	125	132
350-0150-1002	150	157
350-0160-1002	160	167
350-0175-1002	175	182
350-0200-1002	200	207
350-0225-1002	225	232
350-0250-1002	250	257
350-0300-1002	300	307
Tech Sheet 60188		

Other size and length options are available for all hoses shown here - please enquire.

Fluid-Air Components Ltd

ANTISTATIC PUR MEDIUM & HEAVY DUTY DUCTING

PROTAPE® PUR 333 AS

Wall Thickness: 0.9mm approx.

Applications: Flexible hose/ducting for high throughput of abrasive powder, bulk material, granulate and for gases, extraction unit, dedusting system, filter system, oil mist extraction, compresso , side channel blower, vacuum pump, pressure pump.
Municipal vehicle: sweeper, sweeping machine, lawn mower, slope mower, leaf blower/ eaf collector.

new product

- Medium/heavy-duty
- Highly abrasion resistant
- Increased pressure and vacuum resistance
- Microbe resistant
- Good resistance to oil, gasoline and chemicals
- Very good low temperature flexibilit
- Permanently antistatic wall: in accordance with ISO 8031 electrical and surface resistance approx. $10^9\Omega$
- Conforms to RoHS guideline



Working Temperature:
-40°C to +90°C

Medium/Heavy-duty, 0.9mm Wall, Flame Retardant, Anti-static, 10 Metres


0392	ID mm	OD mm
333-0050-0007	50	59.5
333-0065-0007	65	73.5
333-0075-0007	75	84.5
333-0080-0007	80	89
333-0100-0007	100	113.5
333-0125-0007	125	138.5
333-0150-0007	150	163.5
333-0160-0007	160	172
333-0180-0007	180	192
333-0200-0007	200	214.5
333-0250-0007	250	263
Tech Sheet 71699		

AIRDUC PUR 355 AS

Made from premium-grade ester Pre-PUR polyurethane, reinforced with a heavy-duty spring steel wire helix.

Wall Thickness: 1.5mm approx.

Applications: Suction and transport hose for highly abrasive materials using high flow rates, e.g. powder, granules, chippings, etc.
Also suitable for fumes or gaseous media.






- Permanently anti-static wall, $<10^9\Omega$
- Excellent abrasion resistance
- Flame retardant to DIN 4102-B1 and UL94-V2
- Microbe resistant
- Wire spiral reinforcement can be earthed
- High tensile strength and tear resistance
- Smooth bore, optimised flow (observe direction of flow arrow
- Good resistance to oil, petrol and chemicals
- Heavyweight, increased pressure and vacuum

Use clamp type 212/212EC, 216
(refer to page 1447).

Working Temperature:
-40°C to +90°C
Intermittent to: +125°C



Heavyweight, 1.5mm Wall, Flame Retardant, Anti-static, 10 Metres

0392	ID mm	OD mm
355-0050-0000	50	60
355-0065-0000	65	75
355-0075-0000	75	86
355-0100-0000	100	111
355-0125-0000	125	136
355-0150-0000	150	161
355-0160-0000	160	171
355-0200-0000	200	213
355-0250-0000	250	263
355-0300-0000	300	313
Tech Sheet 10395		

AIRDUC® PUR 356 AS

Applications:

- Super/heavy-duty
- Extremely abrasion-resistant with reinforcement underneath wire and narrow hose pitch microbe resistant
- Good resistance to oil, gasoline and chemicals
- Very good low temperature flexibilit
- Permanently antistatic wall: according to ISO 8031 electrical and surface resistance.
- According to DIN 26057 Type 4
- In accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside), aspiration of combustible dusts (Zone 22 inside),
- In accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: for conveying for flammable liquids (inside zone 0, 1, 2), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in zone 0 (gases)
- Conforms to RoHS guideline

Working Temperature:
-40°C to +90°C

Wall Thickness:

- 2 to 2.5 mm approx.

new product




Super/Heavy-duty, 2mm-2.5mm Wall, Anti-static, 10 Metres

0392	ID mm	OD mm
356-0050-0000	50	61
356-0065-0000	65	76
356-0075-0000	75	87
356-0080-0000	80	92
356-0100-0000	100	113
356-0125-0000	125	138
356-0150-0000	150	163
356-0160-0000	160	173
356-0180-0000	180	193
356-0200-0000	200	214
Tech Sheet 71700		

Other size and length options are available for all hoses shown here - please enquire.

FOOD GRADE PUR DUCTING

PROTAPE PUR 330 FOOD





Made from premium food grade ether Pre-PUR polyurethane, reinforced with a spring steel wire helix.

Wall Thickness: 0.6mm approx.


Applications: Suction and transport hose for abrasive materials including food products e.g. powders, granulates etc.

Also suitable for gaseous media and liquids.

- Food grade wall (refer to Tech Sheet for food approvals information)
- Lightweight, high abrasion resistance
- High tensile strength and tear resistance
- Optimised flow (observe direction of flow arro
- Small bend radius
- Good resistance to microbes and hydrolysis
- Good resistance to oil, petrol and chemicals
- Wire spiral reinforcement can be earthed

Use clamp type 212/212EC (refer to page 1447)


Working Temperature:
-40°C to +90°C
Intermittent to: +125°C



Light/Medium Weight, 0.6mm Wall, Food Grade, 10 Metres

0392	ID mm	OD mm
330-0038-0000	38	45
330-0050-0000	50	58
330-0065-0000	65	73
330-0075-0000	75	83
330-0100-0000	100	108
330-0125-0000	125	133
330-0150-0000	150	158
330-0200-0000	200	208
Tech Sheet 60193		

AIRDUC PUR 350 FOOD AS





Made from premium food grade ether Pre-PUR polyurethane, reinforced with a spring steel wire helix.

Wall Thickness: 0.7mm approx.

Applications: Suction and transport hose for abrasive materials including food products, e.g. powders, granulates, seeds, grain, etc.

Also suitable for liquid media.

- Food grade wall (refer to Tech Sheet for food approvals information)
- Permanently anti-static wall, <10⁹Ω
- Good resistance to microbes and hydrolysis
- Wire spiral reinforcement can be earthed
- Good resistance to oil, petrol and chemicals
- High tensile strength and tear resistance
- Smooth bore, optimised flo (observe direction of flow arrow
- Small bend radius
- Excellent low temperature flexibilit

Use clamp type 212/212EC/216 (refer to page 1447).


Working Temperature:
-40°C to +90°C
Intermittent to: +125°C



Medium Weight, 0.7mm Wall, Anti-static, Food Grade, 10 Metres

0392	ID mm	OD mm
350-0038-0000	38	45
350-0050-0000	50	57
350-0065-0000	65	70
350-0075-0000	75	82
350-0100-0000	100	107
350-0125-0000	125	132
350-0150-0000	150	157
350-0160-0000	160	167
350-0175-0000	175	182
350-0200-0000	200	207
350-0225-0000	225	232
350-0250-0000	250	257
350-0300-0000	300	307
Tech Sheet 10394		

AIRDUC PUR 351 FOOD





Made from premium food grade ether Pre-PUR polyurethane, reinforced with a spring steel wire helix.

Wall Thickness: 1.0mm approx.


Applications: Suction and transport hose for abrasive materials including food products, e.g. powders, granulates, seeds, grain, etc.

Also suitable for liquid media.

- Food grade wall (refer to Tech Sheet for food approvals information)
- Good resistance to microbes and hydrolysis
- Wire spiral reinforcement can be earthed
- Good resistance to oil, petrol and chemicals
- High tensile strength and tear resistance
- Smooth bore, optimised flow (observe direction of flow arrow
- Small bend radius
- Excellent low temperature flexibilit
- Flame retardant to UL94-HB

Use clamp type 212/212EC (refer to page 1447).

Working Temperature:
-40°C to +90°C
Intermittent to: +125°C




Medium/Heavy Weight, 1.0mm Wall, Food Grade, 10 Metres

0392	ID mm	OD mm
351-0038-0000	38	46
351-0050-0000	50	58
351-0065-0000	65	73
351-0075-0000	75	84
351-0100-0000	100	109
351-0125-0000	125	134
351-0150-0000	150	159
351-0175-0000	175	184
351-0200-0000	200	209
351-0250-0000	250	259
351-0300-0000	300	309
Tech Sheet 10405		

Fluid-Air Components Ltd

FOOD GRADE HOSE & DUCTING

BARDUC PVC 381 FOOD



Made from high-grade PVC with smooth exterior and bore, and spring steel wire reinforcement embedded into wall. For use when very high pressure, vacuum or compression resistance is required.

Applications: conveying powders, chips and pellets, also gaseous and liquid media, e.g. industrial, agricultural and food.

- Phthalates free
- Wire spiral reinforcement can be earthed
- Smooth bore and exterior
- High axial strength
- Good resistance to chemicals, acids and alkalis
- Food grade wall – refer to Tech Sheet for Food Approvals information

Use clamp type 211 (please enquire).





Working Temperature:
-20°C to +70°C
Intermittent to: +80°C

Super Heavy, Vacuum Proof, Clear PVC, Suction & Delivery, 30 Metres

0392	ID mm	OD mm
381-0012-0000	12	18
381-0016-0000	16	22
381-0018-0000	18	24
381-0020-0000	20	27
381-0025-0000	25	32
381-0032-0000	32	40
381-0038-0000	38	46
381-0050-0000	50	59
381-0065-0000	65	76
381-0076-0000	76	88
Tech Sheet 10421		

Super Heavy, Vacuum Proof, Clear PVC, Suction & Delivery, 20 Metres

0392	ID mm	OD mm
381-0102-0000	102	115
Tech Sheet 10421		

4483 Armoflex®/PU/FOOD

Applications: Certified transparent food suction/discharge hose for liquid and dry food such as fruit juices, milk, sugar and milk powder up to 40°C. The hose is also suitable for transport of other wear resistant materials such as PVC granulate, grit, lime powder and other granulates. Hose can be used for transport of extremely wear resistant materials.

Working Temperature:
-25°C to 85°C


new product



Polyurethane, 4.5mm-5mm Wall (approx.), Food Grade, 30 Metres

0392	ID mm	OD mm
448-3038-000	38	47
448-3040-000	40	49
448-3050-000	51	61
Tech Sheet 71701		

AIRDUC PUR 355 FOOD



Made from premium-grade ether Pre-PUR polyurethane, reinforced with a spring steel wire helix.

Wall thickness: 1.5mm approx.


Applications: heavy-duty suction and transport hose for highly abrasive materials including food products, using high flowrates, particularly in food and pharmaceutical sectors, e.g. powders, granulates, grains, seeds, fibres, etc.

- Also suitable for liquid media, as well as fume extraction
- Heavy-duty, reinforced food grade wall (refer to Tech Sheet for food approvals information)
- Flame retardant to UL94-V2
- Good resistance to microbe and hydrolysis
- Wire spiral reinforcement can be earthed
- Good resistance to oil, petrol and chemicals
- High tensile strength and tear resistance
- Smooth bore, optimised flow (observe direction of flow arrow)
- Small bend radius
- Excellent low temperature flexibility

Use clamp type 212/212EC/216 (refer to page 1447).



Working Temperature:
-40°C to +90°C
Intermittent to:
+125°C




Heavyweight, 1.5mm Wall, Food Grade, 10 Metres

0392	ID mm	OD mm
355-0038-1001	38	48
355-0050-1001	50	60
355-0065-1001	65	75
355-0075-1001	75	86
355-0100-1001	100	111
355-0125-1001	125	136
355-0150-1001	150	161
355-0180-1001	180	191
355-0200-1001	200	213
355-0250-1001	250	263
355-0300-1001	300	313
Tech Sheet 68735		

HIGH PERFORMANCE ANTI-STATIC SUCTION & DELIVERY HOSES

NORPLAST PUR 385 AS




Made from premium-grade anti-static Pre-PUR polyurethane, reinforced with a tough, flexible PVC helix.

Applications: multipurpose suction and delivery hose. For abrasive materials, e.g. dust, powders, granules, fibres and pellets.


Suitable for plastics industries, abrasive recovery, blown insulation, woodworking, etc.

- Gas and liquid tight
- Permanently anti-static wall, <$10^9\Omega$
- Phthalates free
- Lightweight, highly flexible, smooth bore
- Excellent abrasion resistance
- High tensile strength and tear resistance
- Small bend radius
- Good resistance to chemicals
- Flame retardant to DIN 4102-B1

Use clamp type 208/211 (please enquire).



Working Temperature:
-20°C to +70°C
Intermittent to:
+80°C



Polyurethane, Flame Retardant, Anti-static Suction & Delivery Hose, 10 Metres


0392	ID mm	OD mm
385-0025-0000	25	31
385-0032-0000	32	38
385-0038-0000	38	45
385-0040-0000	40	47
385-0050-0000	50	58
385-0060-0000	60	68
385-0075-0000	75	84
385-0100-0000	100	110
Tech Sheet 20020		

NORPLAST® PVC 384 SCIROPPO® AS

Applications:

- For foodstuff liquids and grain shaped mediums, like granulates and wooden pellets
- PVC inner/outer layer
- Slightly corrugated construction cover
- Rigid PVC spiral
- With copper stranded wire
- Smooth interior


Working Temperature:
-15°C to +60°C



PVC, Alimentary Suction/Discharge Hose, Anti-static, 50 Metres

0392	ID mm	OD mm
4411-025-000	25	31
4411-032-000	32	37
4411-038-000	38	45
4411-040-000	40	47
4411-050-000	50	59
4411-060-000	60	69
4411-065-000	65	74
4411-080-000	80	92
Tech Sheet 71702		

Other size and length options are available for all hoses shown here - please enquire.



Permanently Anti-static

In the past, hoses with an anti-static wall were generally manufactured using an additive that migrated out over time, so that the material's anti-static performance was gradually lost.

Thanks to a unique, innovative material developed by **NORRES**, we are able to offer hoses and ductings which are genuinely **permanently anti-static.**

These are indicated by 'AS' as a suffix in our product name.

Fluid-Air Components Ltd

HIGH TEMPERATURE NEOPRENE & SILICONE DUCTING

new product

A premium quality neoprene-coated fabric ducting with cord reinforcement and spring steel helix.

Applications: for air movement and fume extraction where extremes of temperature are involved, e.g. plastic granulate dryers and printing machinery.

- High/low temperature range
- Lightweight and highly flexible
- Leak proof and kink proof

Use clamp type 208/211 (please enquire).

Working Temperature: -35°C to +135°C
Intermittent to: +150°C



NEO 1

Single Ply Neoprene-coated Glass Fabric, 4 Metres

0392	ID mm	OD mm
390-0038-0000	38	42
390-0051-0000	51	55
390-0063-0000	63	67
390-0076-0000	76	80
390-0102-0000	102	106
390-0127-0000	127	132
390-0152-0000	152	157
390-0203-0000	203	208
Tech Sheet 10424		

NEO 2

- Double ply construction to give a higher working pressure



Double Ply, Neoprene-coated Glass Fabric, 4 Metres

0392	ID mm	OD mm
390-0038-2005	38	43
390-0051-2005	51	56
390-0063-2005	63	68
390-0076-2005	76	81
390-0102-2005	102	107
390-0127-2005	127	133
390-0152-2005	152	158
390-0203-2005	203	209
Tech Sheet 71703		

A premium quality silicone-coated fabric ducting with cord reinforcement and spring steel helix.

Applications: for air movement and fume extraction where extremes of temperature are involved, e.g. plastic granulate dryers and printing machinery.

- Extreme temperature range
- Lightweight and highly flexible
- Leak proof and kink proof
- Smooth bore

Use clamp type 208/211 (please enquire).

Working Temperature: -70°C to +260°C
Intermittent to: +280°C



SIL 1

Single Ply, Silicone-coated Glass Fabric, 4 Metres

0392	ID mm	OD mm
391-0038-0000	38	42
391-0051-0000	51	55
391-0063-0000	63	67
391-0076-0000	76	80
391-0102-0000	102	106
391-0127-0000	127	132
391-0152-0000	152	157
391-0203-0000	203	208
Tech Sheet 71704		

SIL 2

- Double ply construction to give a higher working pressure



Double Ply Silicone-coated Glass Fabric, Smooth Bore, 4 Metres

0392	ID mm	OD mm
391-0038-2005	38	43
391-0051-2005	51	56
391-0063-2005	63	68
391-0076-2005	76	81
391-0102-2005	102	107
391-0127-2005	127	133
391-0152-2005	152	158
391-0203-2005	203	209
Tech Sheet 10427		

Other ID sizes are available in NEO & SIL - please enquire.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL VACUUM HOSES & ACCESSORIES

new product

SUPERFLEX PVC 372

Lightweight suction and blast hose made from high-grade, yarn-reinforced PVC with PVC-coated spring steel wire helix.

Working Temperature: 0°C to +85°C

Applications: Industrial/domestic vacuum cleaners, air movement, drier and weld fume extraction.
Suitable for dust, powders, gases and liquids.

- Good resistance to chemicals, alkalis and acids
- Wire helix can be earthed
- Highly flexibl

Use clamp type 208 (please enquire).



Lightweight, Yarn-reinforced PVC, Suction & Blower Hose, 15 Metres

0392	ID mm	OD mm
372-0025-0000	25	31
372-0032-0000	32	38
372-0038-0000	38	44
372-0051-0000	51	57
372-0063-0000	63	69
372-0076-0000	76	82
Tech Sheet 10418		

EVA 373 AS, BLACK

High quality, durable black suction hose made from anti-static EVA.

Working Temperature: -45°C to +65°C

Applications: Industrial/domestic vacuum cleaners and blowing machines for cavity wall insulation.

- Good resistance to alkalis and acids
- Floatable
- Crush-proof
- Permanently anti-static wall, $<10^{11}\Omega$

Use clamp type 208 (please enquire).



Anti-static Black EVA, Crush-proof Suction Hose, 30 Metres

0392	ID mm	OD mm
373-0032-1002	32	40.4
373-0038-1002	38	47.2
373-0050-1002	50	60.4
Tech Sheet 10417		

EVA 373

Working Temperature: -45°C to +65°C

Applications:

- Flexible hose/ducting for gases and for dust, powder, fibre
- Industrial vacuum cleaners, vacuum cleaners
- Swimming pool cleaning
- Scrubber, floor cleaning machin
- Light weight
- Highly flexibl
- Crush resistant
- Floatable
- Good resistance to alkalis and acids
- Conforms to RoHS guideline



Crush-proof EVA Vacuum Cleaner Hose, Grey, 30 Metres

0392	ID mm	OD mm
373-0032-0000	32	40
373-0038-0000	38	47
373-0050-0000	50	60
Tech Sheet 71707		

CONNECT 226

Working Temperature: -20°C to 70°
Intermittent to: +80°C

- Easily and quickly fitte
- Re-usable (threaded version)
- Good resistance to alkalis and acids
- Good resistance to chemicals
- Conforms to RoHS guideline
- Suitable for Hose SuperFlex: 372



Soft Sleeve for SuperFlex Hoses, High Grade Soft PVC,

0392	To Suit Hose ID mm
226-0025-0000	25
226-0032-0000	32
226-0038-0000	38
226-0051-0000	51
226-0063-0000	63
226-0076-0000	76
Tech Sheet 71705	

CONNECT 227

Working Temperature: -20°C to 70°

- Easily and quickly fitte
- Re-usable (threaded version)
- Good resistance to alkalis and acids
- Good resistance to chemicals
- Conforms to RoHS guideline



- Suitable for Hose EVA: 373; 373 (AS/EC)

Grey Soft Sleeve for EVA Hoses, High Grade Soft PVC

0392	To Suit Hose ID mm	Color
227-0032-0000	32	Grey
227-0038-0000	38	Grey
227-0050-0000	50	Grey
Tech Sheet 71706		

- Suitable for Hose EVA: 373; 373 (AS/EC), Electrically Conductive <106)

Black Soft Sleeve for EVA Hoses, High Grade Soft PVC

0392	To Suit Hose ID mm	Color
227-0032-1003	32	Black
227-0038-1003	38	Black
227-0050-1003	50	Black
Tech Sheet 71706		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SPECIALIST CLAMPING EQUIPMENT FOR INDUSTRIAL HOSE & DUCTING

Worm Drive Bridge Clamp 212

- Stainless Steel Band
- Zinc Plated Worm Drive



Offset Bridge Clamp for Wire Helix Ductings

0392	To Suit Hose ID mm
212-0035-0000	38-44
212-0045-0000	50-55
212-0055-0000	60-65
212-0065-0000	70-75
212-0075-0000	80-85
212-0085-0000	90-95
212-0095-0000	100-105
212-0105-0000	110-115
212-0115-0000	120-127
212-0125-0000	130-135
212-0135-0000	140-145
212-0145-0000	150-155
212-0155-0000	160-165
212-0165-0000	170-175
212-0175-0000	180-185
212-0195-0000	200-205
212-0215-0000	220-225
212-0245-0000	250-255
212-0295-0000	300-305
212-0315-0000	320-325
212-0345-0000	350-355
212-0395-0000	400-405
Tech Sheet 10430	

The upgraded 212EC is available on request.

CLAMP 216

- Watertight and tensile connection at very low overpressure due to special spiral geometry
- Easily and quickly fitte
- Re-usable
- Conforms to RoHS guideline



- For AIRDUC® 345, 355, 356 Hoses with ID of >=50mm

Stainless Steel Sealing Clamp

0392	To Suit Hose ID mm
216-0050-0000	50
216-0055-0000	55
216-0060-0000	60
216-0065-0000	65
216-0070-0000	70
216-0075-0000	75
216-0080-0000	80
216-0090-0000	90
216-0100-0000	100
216-0102-0000	102
216-0110-0000	110
216-0115-0000	115
216-0120-0000	120
216-0125-0000	125
216-0127-0000	127
216-0130-0000	130
216-0140-0000	140
216-0150-0000	150
216-0152-0000	152
216-0160-0000	160
216-0175-0000	175
216-0180-0000	180
216-0200-0000	200
Tech Sheet 71708	

- For AIRDUC® 345, 355 Hoses with ID of <50mm

Stainless Steel Sealing Clamp

0392	To Suit Hose ID mm
216-0032-2872	32
216-0038-2872	38
216-0040-2872	40
Tech Sheet 71708	

TOTAL



For **Industrial Grade Hand Tools & Accessories** see pages **1730-1741**

Further sizes are available for all clamps shown here - please enquire.

Fluid-Air Components Ltd

FT PRO

HOSE REELS



Reduced wear and damage
Increased efficiency
Ease of handling and storage
Safety first – avoids slips and trips
Compact units for applications with restricted space
Build a Reel – bespoke reels built to your specification

Features:

- Plastic, metal and stainless steel hose reels
- To suit low, medium and high pressure applications, from 12 bar to 270 bar
- All high pressure hose reels are assembled by BFPA trained technicians
- Hose assemblies made to order
- Floor, wall or ceiling mounting options
- Plastic and metal hose reels come complete with anti-locking mechanism








1448

Air & Water Hi-Vis Hose, Hose Reels

- Hi-Vis reinforced PVC hose
- Tough impact resistant polypropylene construction
- 180º swivel
- Self-layering hose guide for perfectly even hose rewinding
- Speed-controlled return spring
- Auto-locking mechanism allows easy use of hose at any length
- Carry handle
- Lightweight





Maximum Working Pressure:
Air: 17 bar

10 Metre Hi-Vis Hose Length

0800	Length Metres	ID	Inlet Thread	Outlet Thread
ZA04-10B-HIVIS	10	3/8"	1/4" BSPT	1/4" BSPT



Maximum Working Pressure:
Air: 17 bar

15 Metre Hi-Vis Hose Length

0800	Length Metres	ID	Inlet Thread	Outlet Thread
ZA05-15-HIVIS	15	3/8"	1/4" BSPT	1/4" BSPT
ZA05-15-38-HIVIS	15	3/8"	3/8" BSPT	3/8" BSPT

The connection termination on all FT Pro hose reels can be adapted to suit specific requirements. For further details, contact our business development team.



Maximum Working Pressure:
Air: 17 bar

20 Metre Hi-Vis Hose Length

0800	Length Metres	ID	Inlet Thread	Outlet Thread
ZA05-20B-HIVIS	20	1/2"	3/8" BSPT	3/8" BSPT
ZA05-20B12-HIVIS	20	1/2"	1/2" BSPT	1/2" BSPT

Air Hose Reel

- Reinforced PU hose
- Tough impact-resistant polypropylene construction
- 180º swivel
- Self-layering hose guide for perfectly even hose rewinding
- Speed-controlled return spring
- Auto-locking mechanism allows easy use of hose at any length
- Lightweight



Maximum Working Pressure:
12 bar

9 Metre Hose Length

0800	Length Metres	ID	Inlet Thread	Outlet Thread
ZA02-9	9	5/16"	1/4" BSPT	1/4" BSPT
Tech Sheet 10179				


Fluid-Air Components Ltd

HOSE REELS

Mountable Steel Air Hose Reel


- Heavy ribbed steel plate to ensure strong support
- Spring located in the middle to ensure stability
- Four direction non-snag rollers to reduce hose wear abrasion
- Adjustable guide arm for multi position mounting
- Special swivel joint for easy maintenance and repair
- Ball bearing swivel joint structure, largely reducing friction

Maximum Working Pressure:
20 bar




Rubber Air Hose, Spring Rewind, 3/8"

0840	Male Thread	Length Metres	To Suit	Capacity Metres
SAHR-15-38	3/8" BSPT	15	-	-
SAHR-15N-38	-	No Hose	3/8" 1 Wire	15
		Tech Sheet 10183		



Hi-Vis, Spring Rewind, 3/8"

0840	Male Thread	Length Metres
SAHR-15-38SHV06T	3/8" BSPT	15
	Tech Sheet 10184	



Rubber Tech, Spring Rewind, 1/2"

0840	Female Thread	Length Metres
SAHR-15-38SRT06F	3/8" BSPP	15
	Tech Sheet 10188	



Swivel Bracket


0840	To Suit
SAHR-15-12-SB	SAHR-15-12

Fluid-Air Components Ltd

Mountable Steel Air Hose Reel


- Heavy ribbed steel plate to ensure strong support
- Spring located in the middle to ensure stability
- Four direction non-snag rollers to reduce hose wear abrasion
- Adjustable guide arm for multi position mounting
- Special swivel joint for easy maintenance and repair
- Ball bearing swivel joint structure, largely reducing friction

Maximum Working Pressure: 28 bar




Rubber Air Hose, Spring Rewind, 1/2"

0840	Male Thread	Length Metres	To Suit	Capacity Metres
SAHR-15-12	1/2" BSPT	15	-	-
SAHR-15N-12	-	No Hose	1/2'	15
		Tech Sheet 10185		




Hi-Vis, Spring Rewind, 1/2"

0840	Male Thread	Length Metres
SAHR-20-12SHV06T	3/8" BSPT	20
	Tech Sheet 10186	



R6, Spring Rewind, 1/2"

0840	Female Thread	Length Metres
SAHR-15-12SR608F	1/2" BSPP	15
	Tech Sheet 10187	



Spring Rewind Without Hose, 3/4"

0840	To Suit	Capacity Metres
SAHR-40N-34	3/4" Rubber Hose	40
	Tech Sheet 10195	


Fluid-Air Components Ltd

HOSE REELS

Mountable High Pressure Water Steel Hose Reels


- Compact for applications with critical space requirement
- Heavy-duty steel construction with corrosion resistant powder coating
- Four direction non-snag rollers to reduce hose wear abrasion
- Multi position ratchet lock and easy tension adjustment
- Spring fully closed and lubricated
- Full flow swivel
- Adjustable guide arm for multi positional mounting

Maximum Working Pressure: 150 bar



Black 1 Wire Pressure Wash, Spring Rewind, 3/8"


0840	Inlet Thread	Outlet Thread	Length Metres	To Suit	Capacity Metres
SWHR-15-38	3/8" BSP	M22 X 1.5	15	-	-
SWHR-15N-38	-	-	No Hose	3/8" 1 wire	15
Tech Sheet 10189					



Blue 1 Wire Pressure Wash, Spring Rewind, 3/8"

0840	Female Thread	Length Metres
SWHR-15-38SB122K	M22 x 1.5	15
Tech Sheet 10190		

Maximum Working Pressure: 270 bar



Blue 2 Wire Pressure Wash, Manual Rewind, 3/8"

0840	Female Thread	Length Metres
SWHR-30-38MB222K	M22 x 1.5	30
Tech Sheet 10191		



Black 2 Wire Pressure Wash, Manual Rewind, 3/8"

0840	Female Thread	Length Metres	To Suit	Capacity Metres
SWHR-30-38	M22 x 1.5	30	-	-
SWHR-30N-38	-	No Hose	3/8" 2 Wire	30
Tech Sheet 10192				


Fluid-Air Components Ltd

FT PRO new product

Mountable Stainless Steel Hose Reels

- All stainless steel 304 spring rewind hose reels are designed for harsh, corrosive environments or where hygiene is of primary importance
- Ideally suited for wash down applications in food processing, also for marine and offshore application
- All stainless steel swivel assemblies with PTFE washer and viton O-ring for high pressure and high temperature
- Spring fully enclosed and lubricated
- Guide arm adjustable for handling up to 6 positions
- Multi-position ratchet lock keeps hose at desired length

Other configurations available on request.




Spring Rewind without Hose, 1/2" BSPP Inlet

0890	Capacity Metres
SSHR-15N-12	15
Tech Sheet 71762	

Maximum Working Temperature: +155°C

Maximum Working Pressure: 175 bar




Blue 3/8", 1 Wire Pressure Wash, Spring Rewind

0890	Female Thread	Length Metres
SSHR-15-12SB106F	3/8" BSP	15
Tech Sheet 71763		

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 20 bar




Hi-Vis 3/8", Air & Water, Spring Rewind

0890	Female Thread	Length Metres
SSHR-15-12SHV06T	3/8" BSPT	15
SSHR-15-12SHV08T	1/2" BSPT	15
Tech Sheet 71764		

Maximum Working Temperature: +100°C

Maximum Working Pressure: 10 bar



Non Marking 1/2" Wash Down Hose, Spring Rewind

0890	Male Thread	Length Metres
SSHR-15-12SWD08T	1/2"	15
Tech Sheet 71765		



Swivel Bracket

0890	To Suit
SSHR-12-SB	SSHR-15
Tech Sheet 71766	

HOSE REELS

JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

Air/Water Hose Reels



Controlled retraction speed mechanism

20 Metre Heavy-duty Retractable 3/8" Air & Water Hose Reel

1470	Hose ID	Length Metres	Inlet	Outlet
HR5-320B	3/8" (9.2mm)	20	1/4" BSP Male	1/4" BSP Swivel Male



Controlled retraction speed mechanism

20 Metre Heavy-duty 10 bar 1/2" Water Hose Reel

1470	Hose ID	Length Metres	Inlet	Outlet
58.10450S	11.5mm (1/2")	20	3/8" BSP Male	Water Gun



Controlled retraction speed mechanism

30 Metre Heavy-duty Retractable 3/8" Air & Water Hose Reel

1470	Hose ID	Length Metres	Inlet	Outlet
58.30230S	9.2mm (3/8")	30	1/4"	1/4" Swivel



Controlled retraction speed mechanism

30 Metre Heavy-duty Retractable 1/2" Water Hose Reel

1470	Hose ID	Length Metres	Inlet	Outlet
58.30450S	11.5mm (1/2")	30	1/4" BSP Male	1/4" Swivel Check Unit



Controlled retraction speed mechanism

15 Metre Heavy-duty Retractable 1/2" Air & Water Hose Reel

1470	Hose ID	Length Metres	Inlet	Outlet
HR8-315B	1/2" (12.5mm)	15	3/8" BSP Male	3/8" BSP Swivel Male

JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION



For **Jamec Pem Tyre Inflation** see page **1722**

FAC
Fluid-Air Components Ltd


Redashe

Stainless Steel Hose Reels




Heavy Duty Stainless Steel Retractable Hose Reel c/w 15 Mtrs Food Quality Hose

- Heavy gauge 304 stainless steel.
- Designed for harsh corrosive environments.
- Ideal for use in food processing, chemical, offshore and marine applications.



CRWM-SS Series Stainless Steel Manual Rewind Hose Reel Range

- 304 grade st/steel
- Ideally suited for food industry, chemical processing, offshore and marine applications.
- Hose lengths: 20m - 40m.
- Hose Sizes: 1/2" - 1".
- Pressures: up to 700psi.



CCRHA-SS Series Stainless Steel Spring Rewind Hose Reel Range

- 304 grade st/steel
- Ideally suited for food industry washdown, offshore & marine applications.
- Hose lengths: 20m - 30m.
- Hose Sizes: 1/2" - 1".
- Pressures: up to 2500psi

1455

Fluid-Air Components Ltd

HOSE REELS

Redashe

Reelworks Hose Reels

This compact, spring rewind hose reel is constructed in durable impact-resistant polypropylene. Supplied complete with 15m super flexible hybrid polymer hose, 1.5m inlet hose and integral pivoting wall bracket. The compact size makes this reel ideal for use in smaller workshops where space is limited.

Features:

- Supplied with 15m flexible, premium hybrid polymer hose
- Hose has no memory and lays flat when in us
- Integral pivoting wall bracket, swivels through 180°
- Latching of hose at any length
- Latching system can be set to free run if required

Maximum Working Temperature: +60°C



Automatic Spring Rewind Hose Reels, suitable for Air & Water

0122	ID	Length Metres	Max Pressure Bar
C2753	1/2"	15	20
C2752	3/8"	15	20
Tech Sheet 68740			

This multifunctional, hi-vis, safety, spring rewind air hose reel has an automatic rewind system which prevents the hose from bunching when retracting the hose back; the system layers the hose back onto the reel from side to side, neat and tidy every time. The reel is supplied complete with a hybrid polymer hose which lays flat whe in use with no recoil effect, and stays flexible even in extremely cold conditions. Manufactured from high impact UV-stabilised polypropylene which makes this reel tough, lightweight, and corrosion free. Two-year limited warranty.

Features:

- Automatic guide system – no bunching of hose. Layers hose from side to side, neat and tidy every time
- Slow retraction system – prevents hose from speeding back to the reel if the hose is let go – safe operation
- Low tension spring
- Latching of hose at any length



Hi-Vis, Automatic Spring Rewind Hose Reels, suitable for Air

0122	ID	Length Metres	Max Pressure Bar
C2783	1/2"	15	20
C2782	3/8"	15	20
Tech Sheet 68739			

The compact spring rewind reel operates with a normal retraction system but should the operator lose grip on the hose, then the system senses the over-speed reaction and slows the hose to a safe speed by means of a centrifugal brake.

Features:

- Constructed in high impact UV stabilised polypropylene
- Powder coated, integral wall/ceiling bracket
- Latching of cable at any length or free run option
- Fully automatic spring rewind
- Low effort easy to use rewind tension
- Lightweight design
- Supplied with fitted hos
- Virtually maintenance free
- 12 month manufacturer's warranty



RA Series Compact Reel for Air

0122	Hose ID mm	Length Metres	Inlet/Outlet BSPP
RA100	6	10	1/4"
RA200	8	9	1/4"

AIR CONTROL JWL AirBoy®



For **JWL AirBoy Tyre Inflation Equipmen** see page **1723**

FAC Fluid-Air Components Ltd

ef nkl i roi r p c c c a c c

A Brand New Concept in Hose Reel Technology

FEATURES & BENEFITS OF THE CONCEPT:

- Eliminates the use of a fixed guide arm in wall/ceiling mount position
- Easy to install with no need for post installation adjustments
- Unique, automatic, 90° vertical rotational span
- Covers various mounting positions
- Balanced clock spring produces enough torque to displace the weight of the guide arm
- Allowing the guide arm to move vertically up and down in a smooth, effortless and fully automatic manner
- The roller guide and arm/s will always be directly facing the user, giving total control on payout and retrieval
- Allows the units to be mounted at an increased height
- Removes the possibility of harm to the operator, passing personnel or damage to machinery compared to low-level units
- Roller guide arm returns to its rest position after use
- Sets the reel ready for the next operator

STANDARD FEATURES:

- Constructed in heavy gauge powder coated steel
- Finished in a durable, white powder coated gloss finis
- Latching of hose at any length
- Fully automatic hose rewind for neat, tidy storage
- Extended roller guide aperture to ease hose stacking
- Externally mounted swivel assemblies
- Viton seals and nylon backup rings as standard
- Low, medium and high pressure applications
- Double supported 1", solid steel axle
- Pathfinde ® self-adjusting roller guide arm
- All working parts fully accessible for servicing
- Floor, wall or ceiling mounting options
- Suitable for air, water, oil, diesel and grease delivery
- 2-year manufacturer's warranty
- Swivels 180° through the X axis and 90° through the Y axis
- Supplied as a bare reel, hose to suit application at extra cost









Low Pressure, Hose Reel Only

0122	ID	Length Metres	Max Pressure Bar
PFS-915L	3/8"	15	20
PFS-920L	3/8"	20	20
PFS-1315L	1/2"	15	20
PFS-1320L	1/2"	20	20

Medium Pressure, Hose Reel Only

0122	ID	Length Metres	Max Pressure Bar
PFS-915M	3/8"	15	155
PFS-920M	3/8"	20	155
PFS-1315M	1/2"	15	137
PFS-1320M	1/2"	20	137

High Pressure, Hose Reel Only

0122	ID	Length Metres	Max Pressure Bar
PFS-615H	1/4"	15	344
PFS-915H	3/8"	15	275

HOSE REELS

E-Zy Reels

Features:

- Lightweight and durable, just 12.5kg
- Constructed in high-impact UV-stabilised polypropylene
- Supplied with correct type of hose for specific applicatio
- Fully assembled, includes 3 connecting hose
- Suitable for air or water depending on model



E-Zy Reel 701/705, Air/Water, BSPT

0122	Length Metres	ID	Thread	Max Pressure Bar
C705-100	10	1/4"	1/4"	12
C705-200	8	5/16"	1/4"	12

808 Series Open Frame Reel & Hose for Air/Water



0122	Hose ID	Length Feet/Metres	Inlet/Outlet BSPP
C808-466L	1/2"	66/20	1/2"



0122	Hose ID	Length Feet/Metres	Inlet/Outlet BSPP
C809-325L	3/8"	25/8	3/8"

Retracta Standard Hose Reels

Redashe Retracta spring rewind hose reels offer performance, reliability and versatility for all popular hose applications. Constructed in high impact UV stabilized polypropylene for all-purpose corrosion free, durability. Retracta reels can be installed indoors or out. They are particularly suited to washdown applications in food processing as an alternative to conventional stainless steel reels. Suitable for wall, floo , bench or overhead installations.

Features:

- Superior positive latching mechanism allows the reel to be mounted in any position, with latching of the hose at any length
- Tough, corrosion free polypropylene construction
- Lightweight-average just 12kg, easy to install
- Fully automatic hose rewind for neat and tidy storage
- Low rewind tension allows for easy hose "pull out"
- Virtually maintenance free
- Completely serviceable-all parts readily available
- 5 year warranty (conditions apply)
- Safe storage system that keeps hoses off the floo

5 YEAR WARRANTY

Excluding Hose

Note: Available for many other applications, with or without hose.



Cold Wash 40°C, Reinforced PVC Hose

0122	Length Metres	ID mm	Inlet BSPP	Outlet Bare Hose	Max Pressure Bar	Colour
CW100	15	12.5	3/8' Female	Bare End	10	Blue

Hot Wash 90°C, Reinforced Rubber Hose

0122	Length Metres	ID mm	Inlet BSPP	Outlet BSPP	Max Pressure Bar	Colour
HW100	12	12.5	3/8" Female	3/8" Male	10	Red

Food Quality Water 95°C, Reinforced Rubber Hose

0122	Length Metres	ID mm	Inlet BSPP	Outlet BSPP	Max Pressure Bar	Colour
FQ100	12	12.5	3/8" Female	1/2" Male	20	Red

Garden Reel, PVC Hose

0122	Length Metres	ID mm	Inlet BSPP	Outlet	Max Pressure Bar	Colour
DR100	18	12.5	3/4" Male	Blank/Nozzle	7	Green

Breathing Air (EN139), Reinforced NBR/PVC Hose

0122	Length Metres	ID mm	Inlet BSPP	Outlet BSPP	Max Pressure Bar	Colour
BH100	15	10	3/8" Female	3/8" Male	12	Red

Compressed Air (16 bar)

0122	Length Metres	ID mm	Outlet BSPP	Working Pressure (bar)
AR100	20	10	1/4"	16
AR200	15	12.5	3/8"	16

Fluid-Air Components Ltd

HOSE REELS

Redashe

Heavy-duty Hose Reel

Features:

- Supplied with 15 metres of food quality hose.
- Heavy gauge 304 stainless steel.
- Designed for harsh corrosive environments.
- Ideal for use in food processing, chemical, offshore & marine applications.



15 Metres

0122	Description
CTWA-1315SSH	1/2" x 15m Hose Reel (including 15m Food Quality Hose)

820 Series Jet Washer Reel with Hose



0122	Hose ID mm	Length Metres
C820-358	10	15

Retracta Welding Reels with Hoses



0122	Application	Hose ID mm	Length Metres
HOP200	Oxy-Propane	10	10
HOA200	Oxy-Acetylene	10	10

808 Series Welding Reels with Hoses



0122	Application	Hose ID mm	Length Metres
C808-WELD-OP	Oxy-Propane	10	15
C808-WELD-OA	Oxy-Acetylene	10	15

Safety Cable Reel

Features:

- Slow retraction system - prevents hose from speeding back to the reel if the hose is let go - Safe Operation.
- Supplied with 15m of 3 core, 1.5mm2 cable.
- Integral wall mounting swivel bracket.
- Latching of cable at any length.
- Fitted circuit breaker
- Electricity indicator LED light.
- 1.5m Fitted inlet cable.
- Supplied with fitted UK plug & sockets.
- For indoor use only.



15 Metre 230V

0122	Voltage	Cable Length Metres	Amps In/Out
C2681	230V	15	3/10

E-Zy Reels

Features:

- Compact, lightweight design
- Fully automatic spring rewind
- Supplied with 15m of 3 core, 1.5mm cable
- Low effort, easy to use rewind tension
- Fitted inlet cable for connection to supply
- Virtually maintenance free
- Integral wall mounting swivel bracket
- 240V
- Latching of cable at any length



Electrical Cable Reel

0122
C605-100

RC25/50 Series



Compact Electrical Cable Reels 240V

0122	Cable Length Metres	Cores	Amps In/Out
YRC25	5 + 1	3 x 1.5mm	3/10
YRC50	7 + 1	2 x 1mm	3/10

Heavy-duty Static Safety Grounding Reel

Features:

- Heavy-duty steel compact design
- Slow retraction system – prevents cable from speeding back to the reel if the cable is let go - safe operation
- Latching of cable at any length
- Fitted with Alligator static grounding clamp
- High visibility cable with orange vinyl cover
- Operating temperature: -65°F to 125°F (-54°C to 52°C)
- RoHS and REACH compliant
- ATEX II 2G Ex h IIC T6 Gb / 11 2D Ex h IIIC T85°C Db
- Applications: refuelling stations, fuel tanks, fuel trucks, airplane static grounding and any hazardous areas with potentially dangerous static electricity.



Max Resistance: 10 Ohm

SR101 Series, Static Safety Grounding Reel

0122	Hose Capacity Metres	Max Resistance Ohm	Cable OD mm
SR101-01	23	10	4
Tech Sheet 71686			

HOSE REELS

Redashe

Spring Rewind Cable Reels



110V

0122	Cable Length Metres	Voltage	Amps In/Out
YZ6185/IP65	15	110V Max	8/16
YZ7325	15	110V Max	8/16

Hose Reel for Oil



0122	Length Metres
HRO15.12C	15

Hose Reel for Diesel



0122	Length Metres
HRO8.25	8

E-Zy Reel 208 Series Manual Rewind Hose Reels

Features:

- Excellent design, constructed from tubular and formed steel, which delivers superior strength and durability
- Corrosion resistant powder-coated finish, black as standard
- Full flow, brass swivel assembly, ensures maximum product delivery
- Suitable for wall, floor or workbench mounting, ideal for mobile vehicle applications and pressure washers
- Spring loaded locking pin prevents the hose from de-reeling
- Only 9.5kg (bare reel)

Maximum Working Pressure for Reel:
206 bar (3000 psi)





Hose Reel Only

0122	To Suit	Thread
C208-3-100H	30 Metres x 10mm	3/8"
C208-4-65H	20 Metres x 12.5mm	1/2"

E-Zy Reel 460 Series Manual Rewind Hose Reels

Features:

- Designed for industrial applications here longer length of hose are required
- Open hose slot drum design, Oillite self-lubricating bearings
- Spring loaded lock pin prevents hose from de-reeling
- Constructed in heavy gauge powder coated steel
- Full flow swivel joint

Maximum Working Pressure for Reel:
206 (3,000 psi)



Hose Reel Only

0122	To Suit	Thread
C460-3-350H	105 Metres x 10mm	3/8"
C460-4-270H	80 Metres x 12.5mm	1/2"

Warning Tape Barrier Reels

Features:

- Constructed in high impact UV stabilised polypropylene
- Ideal for preventing people entering an unsafe or restricted area
- The tape is manufactured from a strong durable woven textile (width 48mm)
- Equipped with a slow retraction system preventing the tape from speeding back to the reel if the tape is let go (safe operation)

new product



1 YEAR WARRANTY

SR100 Tape Barrier Reels

0122	Tape Capacity Metres	Colour
SR100-05	16	Yellow/Black
SR100-06	16	Red/White

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HOSE REELS


Redashe

Compact Stainless Steel Hose Reels

Features:

- Heavy gauge 304 grade stainless steel
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Floor and wall mounting options
- Smooth and positive crank design
- Supplied as bare reel, hose available at extra cost

stainless steel



CRWM-SS Stainless Steel, Manual Rewind Series, High Capacity, Hose Reel Only

0122	Length Metres	ID	OD	Max Pressure Bar
CRWM-1920SS	20	3/4"	1.1/8"	48
CRWM-2520SS	20	1"	1.1/2"	48

Steel Spring Rewind Reels

Features:

- Corrosion-resistant powder coating
- Guide arm adjustable handling up to nine positions
- Multi-position ratchet lock
- Spring fully enclosed and lubricated
- Wall, ceiling or floor mounte



808 Series, Spring Rewind Hose Reels

0122	Length Metres	ID	Thread	Max Pressure Bar
C808-350L	15	3/8"	3/8"	20
C808-450L	15	1/2"	1/2"	20
C808-350M	15	3/8"	3/8"	155
C808-450M	15	1/2"	1/2"	138

Features:

- 304-grade stainless steel construction
- Large four-way roller guide to reduce hose wear
- Supplied as bare reel
- Externally mounted, fully lubricated spring canister
- Externally mounted swivel assembly for easy maintenance
- 2-year manufacturers warranty



CCRHA-SS Series, Spring Rewind Hose Reels

0122	Length Metres	ID	OD	Max Pressure psi
CCRHA-1320SS	20	1/2"	7/8"	2500
CCRHA-1330SS	30	1/2"	7/8"	2500
CCRHA-1920SS	20	3/4"	1.1/8"	1500
CCRHA-1930SS	30	3/4"	1.1/8"	1500
CCRHA-2520SS	20	1"	1.1/2"	1200

High Capacity, High Visibility Rewind Hose Reels

Features:

- Constructed in heavy gauge mild steel
- Highly visible yellow powder coated finis
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Externally mounted spring canister and swivel assembly for easy maintenance
- Floor and wall mounting options
- Capacities up to 30m
- Two-year manufacturer's warranty
- Supplied as bare reel, hose available at extra cost

Maximum Working Pressure for Reel:
Up to 2700 psi (186 bar)





CRHA Spring Rewind, Air, Oil, Water & Diesel

0122	Length Metres	ID	OD	Max Pressure Bar
CRHA-920	20	3/8"	5/8"	186
CRHA-930	30	3/8"	5/8"	186
CRHA-1320	20	1/2"	7/8"	172
CRHA-1920	20	3/4"	1.1/8"	103
CRHA-1930	30	3/4"	1.1/8"	103
CRHA-2520	20	1"	1.1/2"	82

Features:

- Constructed in heavy gauge mild steel
- Highly visible yellow powder-coated finis
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Floor or wall mounting options
- Smooth and positive direct crank design
- Capacities up to 40m
- Two-year manufacturer's warranty
- Supplied as bare reel, hose available at extra cost

Maximum Working Pressure for Reel:
700 psi (48 bar)





CRWM Manual Rewind, Air, Oil, Water & Diesel

0122	Length Metres	ID	OD	Max Pressure Bar
CRWM-1320	20	1/2"	7/8"	48
CRWM-1340	40	1/2"	7/8"	48
CRWM-1920	20	3/4"	1.1/8"	48
CRWM-1940	40	3/4"	1.1/8"	48
CRWM-2520	20	1"	1.1/2"	48
CRWM-2530	30	1"	1.1/2"	48

HOSE REELS

Heavy-duty Safety Spring Rewind Reel

Features:
- Constructed in heavy gauge powder coated carbon steel
- Double arm structure for stability and versatile adjustments
- Slow retraction system - prevents hose from speeding back to the reel if the hose is let go - safe operation.
- Latching hose at any length.
- Supplied as bare reel, hose available at extra cost (application required)



Maximum Working Pressure:
300 psi (20 bar)

2 YEAR WARRANTY

HR826 Series, Hose Reel Only

0122	Hose Capacity Metres	Max Pressure psi/Bar	Hose ID	Inlet/Outlet BSPP
CHR826-12-366L	20	300/20	3/8"	3/8" Female
CHR826-14-466L	20	300/20	1/2"	1/2" Female
Tech Sheet 71681				

Heavy-duty Spring Rewind ATEX Approved Reel

Features:
- Constructed in heavy gauge powder coated carbon steel
- Double arm structure for stability and versatile adjustments
- RoHS and REACH compliant
- Ex h IIB T4 Gb. Ta = -20°C to +60°C
- Latching of hose at any length
- Supplied as bare reel, hose available at extra cost (application required)



Maximum Working Pressure:
150 psi (10 bar)

5 YEAR WARRANTY

HR213 Series, Hose Reel Only

0122	Hose Capacity Metres	Max Pressure psi/Bar	Hose ID	Inlet/Outlet BSPP
C213-2520EX	20	150/10	1/2"	1" Female
Tech Sheet 71682				

Heavy-duty Stainless Steel Spring Rewind ATEX Approved Reel

Features:
- Constructed in heavy-duty 304 stainless steel
- Double arm structure for stability and versatile adjustments
- RoHS and REACH compliant
- Ex h IIB T4 Gb. Ta = -20°C to +60°C
- Latching of hose at any length
- Supplied as bare reel, hose available at extra cost (application required)



Maximum Working Pressure:
150 psi (10 bar)

5 YEAR WARRANTY

HR223 Series, Hose Reel Only

0122	Hose Capacity Metres	Max Pressure psi/Bar	Hose ID	Inlet/Outlet BSPP
C223-2530SSEX	30	150/10	1/2"	1" Female
Tech Sheet 71683				

Spring Rewind Reel

Features:
- Corrosion resistant powder coating
- Compact design for easy installation
- Spring fully enclosed and lubricated
- Latching of hose at any length
- High quality stress free swivel assembly
- Supplied with 1.5m feeder hose
- Optional swivelling bracket CP-2910



Maximum Working Pressure:
2320 psi (160 bar)

3 YEAR WARRANTY

2919 Series, Reel with Hose

0122	Hose Capacity Metres	Max Pressure psi/Bar	Hose ID	Inlet/Outlet BSPP
C2910-7153	10	300/20	3/8"	3/8" Female
C2910-8104	10	2320/160	1/2"	1/2" Female
Tech Sheet 71684				

C2910 Series Reel Wall Bracket



110° Pivoting Wall Bracket, Powder Coated Steel

0122	To Suit
CP-2910	C2910 Series

Heavy-duty Hand Crank Reel

Features:
- Designed for industrial applications where longer lengths of hose are required
- Constructed in heavy gauge powder coated carbon steel
- Wider drum opening (5"/125mm) making for easier hose installation
- New handle and swivel design for less labour-intensive use (70% more efficient)
- Spring loaded lock pin prevents hose from de-reeling
- Supplied as bare reel, hose available at extra cost (application required)



Maximum Working Pressure:
4000 psi (276 bar)

5 YEAR WARRANTY

HR116 Series, Hose Reel Only

0122	Hose Capacity Metres	Max Pressure psi/Bar	Hose ID	Inlet/Outlet BSPP
CHR11602	30	4000/276	3/4"	3/4" Female
Tech Sheet 71685				

Fluid-Air Components Ltd

Nederman

SAFE AND REALLY EASY...



NEDERMAN REELS.

DISCOVER THE BENEFITS OF KEEPING AIR, WATER, ELECTRICAL POWER, LUBRICANTS OR VACUUM CLOSE AT HAND WITH NEDERMAN'SPROVEN RANGE OF SELF-RETRACTING REELS.

WHY REELS?

- ✓ Reduce wear and damage
- ✓ Ease handling and storage
- ✓ Ensure a clean environment
- ✓ Increase efficiency
- ✓ Safety first – avoids "slips and trips"

FEATURES:

- Ball bearings for easy operation
- High quality seals
- Optimised to retract evenly
- Factory pre-tensioned
- Easy to mount – wall or ceiling
- Manufactured to meet ISO 9001 and ISO 14001
- Stainless and EX approved options

COMPREHENSIVE RANGE - OPEN, CLOSED, STAINLESS AND EX

1463

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

SELF-RETRACTING HOSE REELS

Nederman

Hose Reel, Series H20 & H30

- Safe and functional cable reels for industrial use, professional tradesmen or do-it-yourself workshops
- Snap-on wall bracket
- Unique safety latch
- Drum with ball bearings on both sides
- Degree of protection code, IP55
- Rubber power cable
- Cable easily replaced
- Hose Type A

Maximum Working Pressure:
1.2MPa (12 bar)



Air

0290	ID	Length Metres	Type
30800230	5/16"	12	With Hose
30800430	3/8"	10	With Hose
Tech Sheet 20365			

Maximum Working Pressure:
1.5MPa (15 bar)

Air/Water

- Hose Type A

0290	ID	Length Metres	Type
30800220	1/4"	12	With Hose
30800420	5/16"	8	With Hose

Hose Reel, Series 883

- A fully enclosed and robust, medium sized hose reel. Highly suitable for applications in vehicle repair and maintenance workshops
- Spring tension easily adjustable from the outside
- Fast and easy to service
- Simple hose replacement without dismantling the reel
- Connection hoses are 1 metre long
- Hose Type B



Maximum Working Pressure:
1.5MPa (15 bar)

Air & Water

0290	ID	Length Metres	Type
30800783	3/8"	15	Without Hose
30800883	3/8"	15	With Hose
30800983	1/2"	10	Without Hose
30801083	1/2"	10	With Hose
Tech Sheet 20366			

Maximum Working Pressure:
7.5MPa (75 bar)

Oil

- Hose Type I

0290	ID	Length Metres	Type
30801183	1/2"	10	Without Hose
30801283	1/2"	10	With Hose
Tech Sheet 20366			

Maximum Working Pressure:
25MPa (205 bar)

Maximum Working Temperature: 150°C

High Pressure Water

- Hose Type G

0290	ID	Length Metres	Type
30802183	3/8"	13	Without Hose
30802283	3/8"	13	With Hose
Tech Sheet 20366			

Maximum Working Pressure:
35MPa (350 bar)

Grease

- Hose Type J

0290	ID	Length Metres	Type
30801383	1/4"	15	Without Hose
30801883	1/4"	15	With Hose
Tech Sheet 20366			

Hose Type	Hose Specification	Temp. Range Min °C	Temp. Range Max °C
A	Cover in PVC & inner tube in PUR. Synthetic textile braid.	-10	+60
B	Cover in NBR / PVC & inner tube in NBR. Synthetic textile braid.	-30	+100
D	Cover in NBR / PVC & inner tube in NBR. Synthetic textile braid.	-30	+100
E	Cover in NBR / PVC & inner tube in food grade quality NBR. Synthetic textile braid.	-20	+100
F	Cover in NBR / PVC & inner tube in food grade quality NBR. Synthetic textile braid.	-20	+100
G	Cover & inner tube in synthetic rubber. Single steel braid.	-40	+155
H	Cover & inner tube in synthetic rubber. Single steel braid.	-40	+155
I	Cover & inner tube in SBR based rubber. Single steel braid.	-40	+100
J	Cover & inner tube in synthetic, oil resistant rubber. Double steel braid.	-40	+100
K	Cover & inner tube in rubber. Synthetic textile braid (acc. to EN-559).	-20	+80
L	Corrugated ethyl-vinyl-acetate (EVA). Electrically conductive.	-40	+70
M	Cover in CR & inner tube in NBR. Synthetic textile braid. Electrically conductive.	-30	+80

Fluid-Air Components Ltd

SELF-RETRACTING HOSE REELS

Nederman

Hose Reel, Series 884

- Heavy-duty hose reel for long and heavy hoses. Made of epoxy-coated die-cast aluminium. Ball bearings in drum and swivel. Fully protected inner mechanisms
- Strong, durable and highly corrosion resistant
- Smooth hose operation
- Adjustable outlet arm minimises friction
- Connection hoses are 1 metre long
- Hose Type D

Maximum Working Pressure:
1.5MPa (15 bar)



Air & Water

0290	ID	Length Metres	Type
30810284	1/2"	20	With Hose
30817384	1/2"	30	Without Hose
30817484	1/2"	30	With Hose
30810384	3/4"	15	Without Hose
30810484	3/4"	15	With Hose
30810584	1"	10	Without Hose
30810684	1"	10	With Hose
Tech Sheet 20367			

- Hose Type E.

Maximum Working Pressure:
2.5MPa (25 bar)

Water - Food Grade

0290	ID	Length Metres	Type
30810884	1/2"	20	With Hose
30811284	3/4"	15	With Hose
30811484	1"	10	With Hose
Tech Sheet 20367			

- Hose Type I

Maximum Working Pressure:
20m and 30m hose reels 7.5MPa (75 bar)
10m and 15m hose reels 5.0MPa (50 bar)

Oil

0290	ID	Length Metres	Type
30811784	1/2"	20	Without Hose
30811884	1/2"	20	With Hose
30813584	1/2"	30	Without Hose
30813684	1/2"	30	With Hose
30812284	3/4"	15	With Hose
30813484	1"	10	With Hose
Tech Sheet 20367			

- Hose Type E for water-food grade
- Hose Type I for oil

Water - Food Grade & Oil

0290	ID	Length Metres	Type
30812184	3/4"	15	Without Hose
30813384	1"	10	Without Hose
Tech Sheet 20367			

Maximum Working Pressure:
5MPa (50 bar)

Diesel

0290	ID	Length Metres	Type
30814584	3/4"	15	Without Hose
Tech Sheet 20367			

- Hose Type G

Maximum Working Pressure:
25MPa (250 bar)

Maximum Working Temperature: 150°C

High Pressure Water

0290	ID	Length Metres	Type
30811584	3/8"	25	Without Hose
30811684	3/8"	25	With Hose
Tech Sheet 20367			

- Hose Type J.

Maximum Working Pressure:
35MPa (350 bar)

Grease

0290	ID	Length Metres	Type
30813284	1/4"	25	With Hose
Tech Sheet 20367			

Hose Reel, Series 881

- The vacuum hose reel facilitates the handling of long and heavy vacuum hoses, and provides tidy and safe storage when they are not in use. Keeps hoses out of the way of forklifts and mobile workshop equipment. Separate suspension brackets make mounting of the reel simple and safe
- Antistatic reel and vacuum hose
- Supplied with automatic damper
- Integrated micro-switch
- Delivered without connection hose
- Maximum suction: 45kPa (psi)
- Hose Type L



Vacuum Cleaning

0290	ID	Length Metres	Type
30804981	-	10	Without Hose
30805081	1.1/2"	10	With Hose
30804881	2"	10	With Hose
Tech Sheet 20368			

Hose Reel, Series 886 Ex Approved

- Series 886 Ex is a hose reel with large hose capacity for heavy-duty industrial use. It is constructed for environments where high hygiene and corrosion resistance is required. All components are made of stainless steel and conductive composite material. Approved for use in zones 1, 2 and 22 in accordance with ATEX 94/9/EC, equipment group II, category 2G D
- Connection hoses are 1 metre long
- Hose Type M

Maximum Working Pressure:
2.0MPa (20 bar)

stainless steel



Ex Approved

0290	ID	Length Metres	Type
30804886	3/4"	15	With Hose
30804686	1/2"	25	With Hose
Tech Sheet 20369			

FIRE HOSE REELS & ACCESSORIES

These reels are designed to provide a controlled water supply to suppress any possible fire ris involving Class A combustible solids.

Either the water mains or water tanks can be utilised to provide the pressurised supply required.

Hose Reel Flow Rates:
- 3/4" – 27 lpm
- 1" – 35 lpm

Manufactured to comply with the stringent requirements set out under BS EN 671-1, the hose reels are extremely durable and offer superb performance to the operative. The side plates are protected with a polyester powder coating that complies with the 240 hour salt spray test requirements specified by ISO 9227

ALL REELS COME COMPLETE WITH WALL MOUNTING BRACKETS

Fire Hose Reel



Manual Fixed, Reel Only

0463	To Suit Hose ID mm
FHROMF19	19
FHROMF25	25
Tech Sheet 60138	

Automatic Fixed, Reel Only

0463	To Suit Hose ID mm
FHROAF19	19
FHROAF25	25
Tech Sheet 60138	

Manual Swivel, Reel Only

0463	To Suit Hose ID mm
FHROMS19	19
FHROMS25	25
Tech Sheet 60138	

Automatic Swivel, Reel Only

0463	To Suit Hose ID mm
FHROAS19	19
FHROAS25	25
Tech Sheet 60138	

Fire Hose Reel Assembly



Manual Fixed, with Hose

0463	ID mm	Length Metres
FHRAMF19	19	30
FHRAMF25	25	30
Tech Sheet 60138		

Automatic Fixed, with Hose

0463	ID mm	Length Metres
FHRAAF19	19	30
FHRAAF25	25	30
Tech Sheet 60138		

Manual Swivel, with Hose

0463	ID mm	Length Metres
FHRAMS19	19	30
FHRAMS25	25	30
Tech Sheet 60138		

Automatic Swivel, with Hose

0463	ID mm	Length Metres
FHRAAS19	19	30
FHRAAS25	25	30
Tech Sheet 60138		

Accessories

Standards: EN 694.

Cover: Red, ozone and UV resistant, elastomeric rubber/ PVC blended.

Reinforcement: textile braids.

Liner: seamless rubber/PVC.

Working Temperature: -20°C to +60°C

Maximum Working Pressure: 12 bar



Fire Hose

0463	ID mm	Length Metres
FHO1930	19	30
FHO2530	25	30
Tech Sheet 60138		



Reel Nozzles

0463	To Suit Hose ID mm
FHN1900	19
FHN2500	25
Tech Sheet 60138	

For **Fire Hose & Instantaneous Fire Hose Couplings** see page **1494**



Fluid-Air Components Ltd

FT PRO®

Cam & Groove Quick Couplings



Aluminium



Stainless Steel



Brass



Polypropylene



1467

Fluid-Air Components Ltd

efnkliroirp c cc acc

CAM & GROOVE QUICK COUPLINGS

Aluminium Couplings

See page 1472 for spare seals.

A


Female Threaded Plug, BSPP

0281	Thread
A12-AU	1/2"
A34-AU	3/4"
A1-AU	1"
A114-AU	1.1/4"
A112-AU	1.1/2"
A2-AU	2"
A212-AU	2.1/2"
A3-AU	3"
A4-AU	4"
A6-AU	6"

Tech Sheet 532

Female Threaded Plug, NPT

0282	Thread
A12-AU-NPT	1/2"
A34-AU-NPT	3/4"
A1-AU-NPT	1"
A114-AU-NPT	1.1/4"
A112-AU-NPT	1.1/2"
A2-AU-NPT	2"
A212-AU-NPT	2.1/2"
A3-AU-NPT	3"
A4-AU-NPT	4"

Tech Sheet 532

B


Male Threaded Lever Coupling, BSPT

0281	Thread
B12-AU	1/2"
B34-AU	3/4"
B1-AU	1"
B114-AU	1.1/4"
B112-AU	1.1/2"
B2-AU	2"
B212-AU	2.1/2"
B3-AU	3"
B4-AU	4"

Tech Sheet 532

Male Threaded Lever Coupling, NPT

0282	Thread
B34-AU-NPT	3/4"
B1-AU-NPT	1"
B114-AU-NPT	1.1/4"
B112-AU-NPT	1.1/2"
B2-AU-NPT	2"
B212-AU-NPT	2.1/2"
B3-AU-NPT	3"
B4-AU-NPT	4"

Tech Sheet 532

C


Hose Tail Lever Coupling

0281	Body
C12-AU	1/2"
C34-AU	3/4"
C1-AU	1"
C114-AU	1.1/4"
C112-AU	1.1/2"
C2-AU	2"
C212-AU	2.1/2"
C3-AU	3"
C4-AU	4"
C6-AU	6"

Tech Sheet 532

D


Female Lever Coupling, BSPP

0281	Thread
D12-AU	1/2"
D34-AU	3/4"
D1-AU	1"
D114-AU	1.1/4"
D112-AU	1.1/2"
D2-AU	2"
D212-AU	2.1/2"
D3-AU	3"
D4-AU	4"
D6-AU	6"

Tech Sheet 532

Female Lever Coupling, NPT

0282	Thread
D12-AU-NPT	1/2"
D34-AU-NPT	3/4"
D1-AU-NPT	1"
D114-AU-NPT	1.1/4"
D112-AU-NPT	1.1/2"
D2-AU-NPT	2"
D212-AU-NPT	2.1/2"
D3-AU-NPT	3"
D4-AU-NPT	4"
D6-AU-NPT	6"

Tech Sheet 532



Dust Plug

0281	Body
DP12-AU	1/2"
DP34-AU	3/4"
DP1-AU	1"
DP114-AU	1.1/4"
DP112-AU	1.1/2"
DP2-AU	2"
DP212-AU	2.1/2"
DP3-AU	3"
DP4-AU	4"
DP6-AU	6"

Tech Sheet 532



Lever Stop

0281	Body
DC12-AU	1/2"
DC34-AU	3/4"
DC1-AU	1"
DC114-AU	1.1/4"
DC112-AU	1.1/2"
DC2-AU	2"
DC212-AU	2.1/2"
DC3-AU	3"
DC4-AU	4"
DC6-AU	6"

Tech Sheet 532

E


Hose Tail

0281	Body
E12-AU	1/2"
E34-AU	3/4"
E1-AU	1"
E114-AU	1.1/4"
E112-AU	1.1/2"
E2-AU	2"
E212-AU	2.1/2"
E3-AU	3"
E4-AU	4"
E6-AU	6"

Tech Sheet 532

F


Male Threaded Plug, BSPT

0281	Thread
F12-AU	1/2"
F34-AU	3/4"
F1-AU	1"
F114-AU	1.1/4"
F112-AU	1.1/2"
F2-AU	2"
F212-AU	2.1/2"
F3-AU	3"
F4-AU	4"
F6-AU	6"

Tech Sheet 532

Male Threaded Plug, NPT

0282	Thread
F12-AU-NPT	1/2"
F34-AU-NPT	3/4"
F1-AU-NPT	1"
F114-AU-NPT	1.1/4"
F112-AU-NPT	1.1/2"
F2-AU-NPT	2"
F212-AU-NPT	2.1/2"
F3-AU-NPT	3"
F4-AU-NPT	4"
F6-AU-NPT	6"

Tech Sheet 532

Please note: 1/2" sizes are only supplied with one locking arm.

Fluid-Air Components Ltd

CAM & GROOVE QUICK COUPLINGS

stainless steel

FT PRO

316 Stainless Steel Couplings

See page 1472 for spare seals.



A

Female Threaded Plug, BSPP

0285	Thread
A12-SS	1/2"
A34-SS	3/4"
A1-SS	1"
A114-SS	1.1/4"
A112-SS	1.1/2"
A2-SS	2"
A212-SS	2.1/2"
A3-SS	3"
A4-SS	4"
A6-SS	6"
Tech Sheet 532	

Female Threaded Plug, NPT

0286	Thread
A12-SS-NPT	1/2"
A34-SS-NPT	3/4"
A1-SS-NPT	1"
A114-SS-NPT	1.1/4"
A112-SS-NPT	1.1/2"
A2-SS-NPT	2"
A212-SS-NPT	2.1/2"
A3-SS-NPT	3"
A4-SS-NPT	4"
Tech Sheet 532	



B

Male Threaded Lever Coupling, BSPT

0285	Thread
B12-SS	1/2"
B34-SS	3/4"
B1-SS	1"
B114-SS	1.1/4"
B112-SS	1.1/2"
B2-SS	2"
B212-SS	2.1/2"
B3-SS	3"
B4-SS	4"
Tech Sheet 532	

Male Threaded Lever Coupling, NPT

0286	Thread
B12-SS-NPT	1/2"
B34-SS-NPT	3/4"
B1-SS-NPT	1"
B114-SS-NPT	1.1/4"
B112-SS-NPT	1.1/2"
B2-SS-NPT	2"
B3-SS-NPT	3"
B4-SS-NPT	4"
Tech Sheet 532	



C

Hose Tail Lever Coupling

0285	Body
C12-SS	1/2"
C34-SS	3/4"
C1-SS	1"
C114-SS	1.1/4"
C112-SS	1.1/2"
C2-SS	2"
C212-SS	2.1/2"
C3-SS	3"
C4-SS	4"
Tech Sheet 532	



D

Female Lever Coupling, BSPP

0285	Thread
D12-SS	1/2"
D34-SS	3/4"
D1-SS	1"
D114-SS	1.1/4"
D112-SS	1.1/2"
D2-SS	2"
D212-SS	2.1/2"
D3-SS	3"
D4-SS	4"
Tech Sheet 532	

Female Lever Coupling, NPT

0286	Thread
D12-SS-NPT	1/2"
D34-SS-NPT	3/4"
D1-SS-NPT	1"
D114-SS-NPT	1.1/4"
D112-SS-NPT	1.1/2"
D2-SS-NPT	2"
D212-SS-NPT	2.1/2"
D3-SS-NPT	3"
D4-SS-NPT	4"
Tech Sheet 532	



Dust Plug

0285	Body
DP12-SS	1/2"
DP34-SS	3/4"
DP1-SS	1"
DP112-SS	1.1/2"
DP2-SS	2"
DP212-SS	2.1/2"
DP3-SS	3"
Tech Sheet 532	



Lever Stop

0285	Body
DC34-SS	3/4"
DC1-SS	1"
DC114-SS	1.1/4"
DC112-SS	1.1/2"
DC2-SS	2"
DC3-SS	3"
DC4-SS	4"
Tech Sheet 532	



E

Hose Tail

0285	Thread
E12-SS	1/2"
E34-SS	3/4"
E1-SS	1"
E114-SS	1.1/4"
E112-SS	1.1/2"
E2-SS	2"
E212-SS	2.1/2"
E3-SS	3"
E4-SS	4"
Tech Sheet 532	



F

Male Threaded Plug, BSPT

0285	Thread
F12-SS	1/2"
F34-SS	3/4"
F1-SS	1"
F114-SS	1.1/4"
F112-SS	1.1/2"
F2-SS	2"
F212-SS	2.1/2"
F3-SS	3"
F4-SS	4"
Tech Sheet 532	

Male Threaded Plug, NPT

0286	Body
F12-SS-NPT	1/2"
F34-SS-NPT	3/4"
F1-SS-NPT	1"
F114-SS-NPT	1.1/4"
F112-SS-NPT	1.1/2"
F2-SS-NPT	2"
F212-SS-NPT	2.1/2"
F3-SS-NPT	3"
F4-SS-NPT	4"
Tech Sheet 532	

Please note: 1/2" sizes are only supplied with one locking arm.

CAM & GROOVE QUICK COUPLINGS

Polypropylene Couplings

See page 1472 for spare seals.



A

Female Threaded Plug, BSPP

0287	Thread
A12-PP	1/2"
A34-PP	3/4"
A1-PP	1"
A114-PP	1.1/4"
A112-PP	1.1/2"
A2-PP	2"
A3-PP	3"
A4-PP	4"

Tech Sheet 532

Female Threaded Plug, NPT

0288	Thread
A12/34-PP-NPT	1/2"
A34-PP-NPT	3/4"
A1-PP-NPT	1"
A114-PP-NPT	1.1/4"
A112-PP-NPT	1.1/2"
A2-PP-NPT	2"
A3-PP-NPT	3"
A4-PP-NPT	4"

Tech Sheet 532



B

Male Threaded Lever Coupling, BSPT

0287	Thread
B12-PP	1/2"
B34-PP	3/4"
B1-PP	1"
B114-PP	1.1/4"
B112-PP	1.1/2"
B2-PP	2"
B3-PP	3"

Tech Sheet 532

Male Threaded Lever Coupling, NPT

0288	Thread
B12/34-PP-NPT	1/2"
B34-PP-NPT	3/4"
B1-PP-NPT	1"
B114-PP-NPT	1.1/4"
B112-PP-NPT	1.1/2"
B2-PP-NPT	2"
B3-PP-NPT	3"
B4-PP-NPT	4"

Tech Sheet 532



C

Hose Tail Lever Coupling

0287	Body
C12-PP	1/2"
C34-PP	3/4"
C1-PP	1"
C114-PP	1.1/4"
C112-PP	1.1/2"
C2-PP	2"
C3-PP	3"
C4-PP	4"

Tech Sheet 532



D

Female Lever Coupling, BSPP

0287	Thread
D12-PP	1/2"
D34-PP	3/4"
D1-PP	1"
D114-PP	1.1/4"
D112-PP	1.1/2"
D2-PP	2"
D3-PP	3"
D4-PP	4"

Tech Sheet 532

Female Lever Coupling, NPT

0288	Thread
D12/34-PP-NPT	1/2"
D34-PP-NPT	3/4"
D1-PP-NPT	1"
D114-PP-NPT	1.1/4"
D112-PP-NPT	1.1/2"
D2-PP-NPT	2"
D3-PP-NPT	3"
D4-PP-NPT	4"

Tech Sheet 532



Dust Plug

0287	Body
DP34-PP	3/4"
DP1-PP	1"
DP114-PP	1.1/4"
DP112-PP	1.1/2"
DP2-PP	2"
DP3-PP	3"

Tech Sheet 532



Lever Stop

0287	Body
DC34-PP	3/4"
DC1-PP	1"
DC114-PP	1.1/4"
DC112-PP	1.1/2"
DC2-PP	2"
DC3-PP	3"

Tech Sheet 532



E

Hose Tail

0287	Body
E12-PP	1/2"
E34-PP	3/4"
E1-PP	1"
E114-PP	1.1/4"
E112-PP	1.1/2"
E2-PP	2"
E3-PP	3"
E4-PP	4"

Tech Sheet 532



F

Male Threaded Plug, BSPT

0287	Thread
F12-PP	1/2"
F34-PP	3/4"
F1-PP	1"
F114-PP	1.1/4"
F112-PP	1.1/2"
F2-PP	2"
F3-PP	3"
F4-PP	4"

Tech Sheet 532

Male Threaded Plug, NPT

0288	Thread
F12/34-PP-NPT	1/2"
F34-PP-NPT	3/4"
F1-PP-NPT	1"
F112-PP-NPT	1.1/2"
F2-PP-NPT	2"
F3-PP-NPT	3"
F4-PP-NPT	4"

Tech Sheet 532

Please note: 1/2" sizes are only supplied with one locking arm.

Fluid-Air Components Ltd

CAM & GROOVE QUICK COUPLINGS

Brass Couplings

See page 1472 for spare seals.

A



Female Threaded Plug, BSPP

0283	Thread
A12-BR	1/2"
A34-BR	3/4"
A1-BR	1"
A114-BR	1.1/4"
A112-BR	1.1/2"
A2-BR	2"
A212-BR	2.1/2"
A3-BR	3"
A4-BR	4"
Tech Sheet 532	

Female Threaded Plug, NPT

0284	Thread
A12-BR-NPT	1/2"
A34-BR-NPT	3/4"
A1-BR-NPT	1"
A112-BR-NPT	1.1/2"
A2-BR-NPT	2"
A212-BR-NPT	2.1/2"
A3-BR-NPT	3"
A4-BR-NPT	4"
A5-BR-NPT	5"
A6-BR-NPT	6"
Tech Sheet 532	

B



Male Threaded Lever Coupling, BSPT

0283	Thread
B12-BR	1/2"
B34-BR	3/4"
B1-BR	1"
B114-BR	1.1/4"
B112-BR	1.1/2"
B2-BR	2"
B212-BR	2.1/2"
B3-BR	3"
B4-BR	4"
Tech Sheet 532	

Male Threaded Lever Coupling, NPT

0284	Thread
B12-BR-NPT	1/2"
B34-BR-NPT	3/4"
B1-BR-NPT	1"
B114-BR-NPT	1.1/4"
B112-BR-NPT	1.1/2"
B2-BR-NPT	2"
B212-BR-NPT	2.1/2"
B3-BR-NPT	3"
B4-BR-NPT	4"
B6-BR-NPT	6"
Tech Sheet 532	

C



Hose Tail Lever Coupling

0283	Body
C12-BR	1/2"
C34-BR	3/4"
C1-BR	1"
C114-BR	1.1/4"
C112-BR	1.1/2"
C2-BR	2"
C212-BR	2.1/2"
C3-BR	3"
C4-BR	4"
Tech Sheet 532	

D



Female Lever Coupling, BSPP

0283	Thread
D12-BR	1/2"
D34-BR	3/4"
D1-BR	1"
D114-BR	1.1/4"
D112-BR	1.1/2"
D2-BR	2"
D212-BR	2.1/2"
D3-BR	3"
D4-BR	4"
Tech Sheet 532	

Female Lever Coupling, NPT

0284	Thread
D12-BR-NPT	1/2"
D34-BR-NPT	3/4"
D1-BR-NPT	1"
D114-BR-NPT	1.1/4"
D112-BR-NPT	1.1/2"
D2-BR-NPT	2"
D212-BR-NPT	2.1/2"
D3-BR-NPT	3"
D4-BR-NPT	4"
D5-BR-NPT	5"
D6-BR-NPT	6"
Tech Sheet 532	



Dust Plug

0283	Body
DP12-BR	1/2"
DP1-BR	1"
DP114-BR	1.1/4"
DP112-BR	1.1/2"
DP2-BR	2"
DP212-BR	2.1/2"
DP3-BR	3"
DP4-BR	4"
DP6-BR	6"
Tech Sheet 532	



Lever Stop

0283	Body
DC12-BR	1/2"
DC1-BR	1"
DC112-BR	1.1/2"
DC2-BR	2"
DC212-BR	2.1/2"
DC3-BR	3"
DC6-BR	6"
Tech Sheet 532	

E



Hose Tail

0283	Body
E12-BR	1/2"
E34-BR	3/4"
E1-BR	1"
E114-BR	1.1/4"
E112-BR	1.1/2"
E2-BR	2"
E212-BR	2.1/2"
E3-BR	3"
E4-BR	4"
Tech Sheet 532	

F



Male Threaded Plug, BSPT

0283	Thread
F12-BR	1/2"
F34-BR	3/4"
F1-BR	1"
F114-BR	1.1/4"
F112-BR	1.1/2"
F2-BR	2"
F212-BR	2.1/2"
F3-BR	3"
F4-BR	4"
F6-BR	6"
Tech Sheet 532	

Male Threaded Plug, NPT

0284	Thread
F12-BR-NPT	1/2"
F1-BR-NPT	1"
F114-BR-NPT	1.1/4"
F112-BR-NPT	1.1/2"
F2-BR-NPT	2"
F212-BR-NPT	2.1/2"
F3-BR-NPT	3"
F4-BR-NPT	4"
Tech Sheet 532	

Please note: 1/2" sizes are only supplied with one locking arm.

Fluid-Air Components Ltd

CAM & GROOVE SEALS & SPARES

Cam & Groove Seals

Seals suitable for cam and groove quick couplings.



Viton Seals

0060	To Suit Coupling Size
VITON-12	1/2"
VITON-34	3/4"
VITON-1	1"
VITON-114	1.1/4"
VITON-112	1.1/2"
VITON-2	2"
VITON-212	2.1/2"
VITON-3	3"

EPDM Seals

0060	To Suit Coupling Size
EPDM-12	1/2"
EPDM-34	3/4"
EPDM-1	1"
EPDM-114	1.1/4"
EPDM-112	1.1/2"
EPDM-2	2"
EPDM-212	2.1/2"
EPDM-3	3"
EPDM-4	4"

Buna Seals

0060	To Suit Coupling Size
BUNA-12	1/2"
BUNA-34	3/4"
BUNA-1	1"
BUNA-114	1.1/4"
BUNA-112	1.1/2"
BUNA-2	2"
BUNA-212	2.1/2"
BUNA-3	3"
BUNA-4	4"
BUNA-6	6"

Tech Sheet 20356

PTFE Seals



0060	To Suit Coupling Size
PTFE-12	1/2"
PTFE-34	3/4"
PTFE-1	1"
PTFE-114	1.1/4"
PTFE-112	1.1/2"
PTFE-2	2"
PTFE-212	2.1/2"
PTFE-3	3"

Stainless Arm, Pin & Ring



Spare Arm, Pin & Ring for Cam & Groove Couplings

0060	To Suit Coupling Size
CGS-12-34	1/2" & 3/4"
CGS-1	1"
CGS-114-212	1.1/4" & 2.1/2"
CGS-3-4	3" & 4"

Chain & Ring for Cam Lock Caps



0060	Description
BRC6	6" Brass
SSC6	6" Stainless Steel
BRC12	12" Brass
SSC12	12" Stainless Steel

You might also need...

JAYMAC Industrial Hose & Accessories

10 bar Water Suction Hose
see page **1430**



FAC Fluid-Air Components Ltd

QUICK RELEASE PNEUMATIC HOSE COUPLINGS

European Execution Double Lock Claw Couplings

Maximum Working Pressure: 10 bar



Q1 Hose Tails, Plated

0108	To Suit Hose ID
Q1DLP14	1/4"
Q1DLP38	3/8"
Q1DLP12	1/2"
Q1DLP58	5/8"
Q19SDLP34	3/4" (Q19S)
Q1DLP1	1"
Q1DLP114	1.1/4"
Tech Sheet 20303	

Maximum Working Pressure: 7 bar



Q2 Female Thread, Plated, BSPP

0108	Thread
Q2DLP14	1/4"
Q2DLP38	3/8"
Q2DLP12	1/2"
Q2DLP34	3/4"
Q2DLP1	1"
Q2DLP114	1.1/4"
Tech Sheet 20304	



Q4 Blanking Off End

0108
Q4
Tech Sheet 20306

Maximum Working Pressure: 7 bar



Q3 Male Thread, Plated, BSPP

0108	Thread
Q3DLP14	1/4"
Q3DLP38	3/8"
Q3DLP12	1/2"
Q3DLP34	3/4"
Q3DLP1	1"
Q3DLP114	1.1/4"
Tech Sheet 20305	



Q Rubbers

0108	Material
QRNIT	Nitrile
QR	Neoprene
Tech Sheet 20307	

Double Lock QC Claw Couplings

Maximum Working Pressure: 7 bar



QC1 Hose Tails, Plated

0108	To Suit Hose ID
QC112	1/2"
QC134	3/4"
QC11	1"



QC2 Female Thread, Plated, BSPP

0108	Thread
QC212	1/2"
QC234	3/4"
QC21	1"



QC3 Male Thread, Plated, BSPP

0108	Thread
QC312	1/2"
QC334	3/4"
QC31	1"



QC2 Female Thread, Gunmetal, BSPP

0108	Thread
QC2GM34	3/4"



QC Rubber

0108
QCR

Due to the change of finishes used by our supplier, the product you receive may be different to that illustrated.

QUICK RELEASE PNEUMATIC HOSE COUPLINGS

QAY US Execution Claw Couplings

- US execution with bore for safety clip

Maximum Working Pressure: 12 bar



QAY 1
Hose Tails

0108	To Suit Hose ID
QAY138	3/8"
QAY112	1/2"
QAY134	3/4"
QAY11	1"



QAY 2
Female Thread, NPT

0108	Thread
QAY238	3/8"
QAY212	1/2"
QAY234	3/4"
QAY21	1"



QAY 3
Male Thread, NPT

0108	Thread
QAY338	3/8"
QAY312	1/2"
QAY334	3/4"
QAY31	1"



QAY 4,
Hose Tail with Ferrule

0108	To Suit Hose ID
QAY412	1/2"
QAY434	3/4"
QAY41	1"



QAY Blank End

0108
QAYBE



Safety Locking Pins

0108
PINS

Tech Sheet 20179



QAY
Spare Rubber

0108
QAYR

QAC Claw Couplings

Maximum Working Pressure: 9.5 bar



QAC 1 Hose Tail, Forged Steel

0108	To Suit Hose ID
QAC138	3/8"
QAC112	1/2"
QAC134	3/4"
QAC11	1"

Tech Sheet 20308



QAC 2 Female Thread, Forged Steel, BSPP

0108	Thread
QAC212	1/2"
QAC234	3/4"
QAC21	1"

Tech Sheet 20309



QAC 3 Male Thread, Forged Steel, BSPP

0108	Thread
QAC312	1/2"
QAC334	3/4"
QAC31	1"

Tech Sheet 20310



QAC 4 Hose Tail, Forged Steel

0108	To Suit Hose ID
QAC412	1/2"
QAC434	3/4"

Tech Sheet 20311

SS Claw Couplings

Maximum Working Pressure: 9.5 bar



SS1 Hose Tail

0108	To Suit Hose ID
SS112	1/2"
SS134	3/4"
SS11	1"

Tech Sheet 20316



SS2 Female Thread, BSPP

0108	Thread
SS212	1/2"
SS234	3/4"
SS21	1"

Tech Sheet 20317



SS3 Male Thread, BSPP

0108	Thread
SS312	1/2"
SS334	3/4"
SS31	1"

Tech Sheet 20318

Due to the change of finishes used by our supplier, the product you receive may be different to that illustrated.

Fluid-Air Components Ltd

QUICK RELEASE WATER HOSE COUPLINGS

Series GK, Brass Water Couplings



Hose Tail

0278	To Suit Hose ID
GT38	3/8"
GT58	5/8"
GK-TF13	1/2"
GK-TF19	3/4"
GK-TF25	1"
GK-TF31	1.1/4"
GK-TF38	1.1/2"
Tech Sheet 20333	



Female Thread, BSPP

0101	Thread
GK-IW21	1/2"
GK-IW26	3/4"
GK-IW33	1"
GK-IW42	1.1/4"
GK-IW50	1.1/2"



Male Thread, BSPP

0278	Thread
GM38	3/8"
GK-AW21	1/2"
GK-AW26	3/4"
GK-AW33	1"
GK-AW42	1.1/4"
GK-AW50	1.1/2"

Safety Couplings



0278	To Suit Hose ID
GTLC12	1/2"
GTLC34	3/4"
GTLC1	1"

Spray Nozzles



0101	Thread
GK-SP34	3/4"

Blanking Cap



0101
GK-BC

Triple Outlet Connector



0101
GK-3Y




Replacement Seal

0101	Description
GK-GASKET	Suits All Sizes

FT PRO

For **FT Pro Clamps**
see page **1480**



CLAW COUPLINGS

LÜDECKE new product

US Execution Claw Couplings



Female, NPT

6295	Thread
KIA 38	3/8"
KIA 12	1/2"
KIA 34	3/4"
KIA 10	1"

Female, BSP

6295	Thread
KIA 38 BSP	3/8"
KIA 12 BSP	1/2"
KIA 34 BSP	3/4"
KIA 10 BSP	1"



Male, NPT

6295	Thread
KAA 38	3/8"
KAA 12	1/2"
KAA 34	3/4"
KAA 10	1"

Male, BSP

6295	Threa"d
KAA 38 BSP	3/8
KAA 12 BSP	1/2"
KAA 34 BSP	3/4"
KAA 10 BSP	1"



Hose Tail

6295	Thread mm
SKA 11	10
SKA 13	13
SKA 19	19
SKA 25	25



Blank End Cap

6295
UDM



Original Rubber Ring

6295
GOOR

CLAMPS, HOSE CLAMPS & FASTENERS

LÜDECKE new product

US Execution Hose



Hose Clamp

6295	To Suit Hose OD Range mm
LB-4	21-27
SKA 34	30-35
LBU-9	30-33
LB-9	33-38
LB 10	38-43
SKA 10	34-45
LBU 29	63-70



Hose Clamp, DIN 20039

6295	To Suit Hose OD Range mm
S 22	17-22
SL 29	22-29
SL 34	28-34
SL 49	39-49
SL 72	56-72
SL 94	77-94
SL 400	89-101
SL 115	94-115
SL 525	113-127
SL 145	115-145
SL 550	127-140
SL 600	135-155
SL 675	155-175
SL 769	175-195
SL 875	210-225
SL 988	227-250

stainless steel



Hose Clamp, Stainless Steel

6295	To Suit Hose OD Range mm
SLE 13	17-22
SLE 19	22-29
SLE 25	28-34

Fluid-Air Components Ltd

CLAW COUPLINGS

LÜDECKE

Claw Couplings DIN 3489

Working Temperature: -40°C to +95°C

Maximum Working Pressure: 10 bar

Universal system for compressed air in construction and industry.

Material: Malleable iron/steel
Seal: Nitrile

Media: Compressed air
Claw Distance: 42 mm



Hose Tail (formerly DIN 3483)

6295	To Suit Hose ID mm
SKG6	6
SKG10	10
SKG13	13
SKG15	15
SKG19	19
SKG25	25
SKG32	32



Hose Tail with Safety Collar

6295	To Suit Hose ID mm
SKB13	13
SKB19	19
SKB25	25



Female Thread, BSPP (formally DIN 3482)

6295	Thread
KIG14	1/4'
KIG38	3/8'
KIG12	1/2'
KIG34	3/4'
KIG10	1'
KIG54	1.1/4'



Male Thread, BSPP (formally DIN 3481)

6295	Thread
KAG14	1/4'
KAG38	3/8'
KAG12	1/2'
KAG34	3/4'
KAG1	1'
KAG54	1.1/4'



Blank End (formerly DIN 3483)

6295	Description
VKO	Blank End
VKM	Blank End with Chain
VKM-K	Spare Chain 200mm



Original DIN 3489 Seals

6295	Medium	Colour	Material	Max Temp°C
GOER	Compressed Air	Black	Nitrile	95°C
GPOR	Food	Natural	EPDM	130°C
GVOR	Chemicals	Green	FKM	200°C
GDOR	Steam	Red	TFEP	200°C

MODY Safety-Screwing Claw Couplings DIN 3238

Working Temperature: -40°C to +95°C

Maximum Working Pressure: 16 bar

Secured by locking nut to prevent unintentional opening, for safe air lines in construction and industry.

Material: Malleable iron/ steel, brass locking nut
Seal: Nitrile

Media: Compressed air
Claw Distance: 42 mm



Hose Tail

6295	To Suit Hose ID mm
SSG10	10
SSG13	13
SSG15	15
SSG19	19
SSG25	25
SSG32	32



Hose Tail with Safety Collar

6295	To Suit Hose ID mm
SSG10S	10
SSG13S	13
SSG15S	15
SSG19S	19
SSG25S	25



Hose Tail, Hydraulic Crimping

6295	To Suit Hose ID mm
SSG19PH	19



Female Thread, BSPP

6295	Thread
SSGI38	3/8"
SSGI12	1/2"
SSGI34	3/4"
SSGI10	1"



Male Thread, BSPP with LÜDSY Sealing

6295	Thread
SSGA38	3/8"
SSGA12	1/2"
SSGA34	3/4"
SSGA10	1"



Original MODY Seal

6295	Medium	Colour	Material	Max Temp °C
SGOR-N	Compressed Air	Black	Nitrile	95°C

Fluid-Air Components Ltd

CLAW COUPLINGS

LÜDECKE

Safety Claw Couplings with Bore

Working Temperature: -40°C to +95°C

Maximum Working Pressure: 10 bar

Universal system, mainly used in mining and tunneling. Additional security by using the safety-clips DIN 11024 to prevent unintentional opening.

Material: Malleable iron/steel
Seal: Nitrile

Media: Compressed air
Claw Distance: 42 mm



Hose Clamps DIN 20039 B, to suit Couplings with Hose Tail & Safety Collar

6295	To Suit Hose ID mm	Hose OD Range mm
SK29-CLAMP	13	22-29
SK34-CLAMP	19	28-32
SK60	42	55-60



Universal Safety Clip DIN 11024

6295
USC-1

ACK Claw Couplings, Forged Steel

Working Temperature: -40°C to +95°C

Maximum Working Pressure: 16 bar

High quality coupling for compressed air in construction and industry, equivalent to Atlas Copco.

Material: Forged steel, hardened
Seal: Nitrile

Media: Compressed air
Claw Distance: 42 mm



Hose Tail

6295	To Suit Hose ID mm
ACK38T	10
ACK12T	12.5
ACK34T	20
ACK10T	25



Female Thread, BSPP

6295	Thread
ACK38I	3/8"
ACK12I	1/2"
ACK34I	3/4"
ACK10I	1"



Male Thread, BSPP

6295	Thread
ACK38A	3/8"
ACK12A	1/2"
ACK34A	3/4"
ACK10A	1"

FT PRO

For **Pumps & Pump Kits** see pages **1632-1636**





Fluid-Air Components Ltd

CLAW COUPLINGS

LÜDECKE

Claw Couplings DIN 3489, Stainless Steel

Working Temperature: -30°C to +200°C

Maximum Working Pressure: 16 bar

Universal system for aggressive fluids in chemical or petrochemical industry, as well as food or drinking water applications.
Use original DIN 3489 Seal GPOR (EPDM) food or drinking water applications.

Material: Stainless steel 1.4401/1.4404
Seal: FKM
Media: Chemical substances
Claw Distance: 42 mm

stainless steel



Hose Tail

6295	To Suit Hose ID mm
EKT10V	10
EKT13V	13
EKT19V	19
EKT25V	25

stainless steel



Female Thread, BSPP

6295	Thread
EKI38V	3/8'
EKI12V	1/2"
EKI34V	3/4"
EKI10V	1"

stainless steel



Male Thread, BSPP

6295	Thread
EKA12V	1/2'
EKA34V	3/4"
EKA10V	1"

stainless steel



Blank End

6295	Description
EKOV	Blank End
EKMV	Blank End with Chain
EKMV-K	Spare Chain 200mm

WaterProfi Claw Coupling

Working Temperature: +95°C

Maximum Working Pressure: 25 bar

Universal coupling of forged brass for water lines in industry, construction, agriculture or civil installations.

Material: Forged brass CW617N
Seal: EPDM

Media: Water
Claw Distance: 40 mm



Hose Tail

6295	To Suit Hose ID mm
GSK10	10
GSK13	13
GSK16	16
GSK19	19
GSK25	25
GSK32	32
GSK38	38



Female Thread, BSPP with O-Ring

6295	Thread
GKI14	1/4'
GKI38	3/8'
GKI12	1/2'
GKI34	3/4'
GKI10	1'
GKI54	1.1/4'
GKI15	1.1/2'



Male Thread, BSPP

6295	Thread
GKA14	1/4'
GKA38	3/8'
GKA12	1/2'
GKA34	3/4"
GKA10	1'
GKA54	1.1/4'
GKA15	1.1/2'



Blank End

6295
GKO



Original WaterProfi Sea

6295	Medium	Colour	Material	Max Temp °C
GKOR	Water	Black	EPDM	95°C

Fluid-Air Components Ltd

CLAMPS, NUTS & BOLTS

Clamps

Note: All sizes are for guidance only. Nuts and bolts included.



Golden Range Clamps, Zinc & Gold Passivated

0108	Min Size mm	Max Size mm
HD.000	17	22
HD.001	20	29
HD.002	28	35
HD.003	32	40
HD.004	39	49
HD.005	48	60
HD.006	60	76
HD.007	77	94
HD.1	89	101
HD.2	101	113
HD.3	113	127
HD.5	140	154
HD.6	154	175
HD.7	175	194
HD.9	210	225



SK Clamps, Zinc & Gold Passivated

0108	ID	Min Size mm	Max Size mm
SK34	3/4"	29	34
SK39	1"	33	40
SK44	1.1/4"	41	49
SK51	1.1/2"	47	60
SK73	2"	60	77



IL Clamps, Zinc & Gold Passivated

0108	ID	Min Size mm	Max Size mm
CILP12	1/2"	17	22
CILP34	3/4"	27	32
Tech Sheet 20393			

Note: To suit Staysafe couplings



Staysafe Clamps, Zinc & Gold Passivated

0108	ID	Min Size mm	Max Size mm
JA2	1/2"	21	25
JA3	3/4"	29	33
JA4	3/4"	31	35
Tech Sheet 20395			



Clamps - Type A /Q19S/SWC, Unplated

0108	ID	OD mm	To Suit Hose OD
CA12	1/2"	19	-
CA34	3/4"	28	-
CA34Q19S/DL	3/4"	29-33	3/4" Q19S DL Coupling
CA1	1"	35	-
CA112	1.1/2"	49-56	1.1/2" A Nut & Tail
CSWC112	1.1/2"	52-55	1.1/2" SWC Nut & Tail
CSWC2	2"	64-71	2" SWC Nut & Tail
CA234	2.3/4"	65-70	2" Nut & Tail
Tech Sheet 20392			



T-Bar Clamps

0108	ID
TBAR2	2"
TBAR3	3"
TBAR4	4"
Tech Sheet 2155	



Plain Type Clamps, Zinc & Gold Passivated

0108	ID	OD mm
CP78	7/8"	-
CP112	1.1/2"	-
CP218	2.1/8"	51
CP234	2.3/4"	70
Tech Sheet 20394		

Nuts & Bolts



0108	Description
NBM840	M8 x 40mm Long
NBM1050	M10 x 50mm Long
NBM1060	M10 x 60mm Long

Malleable Iron Air & Steam Clamp



0108	ID	OD mm	Bolts
SA1	1/4"	14-17	2 Bolt
SA2	3/8"	17-21	2 Bolt
SA4	1/2"	24-27	2 Bolt
SA5	1/2"	27-30	2 Bolt
SA6	3/4"	30-33	2 Bolt
SA7	3/4"	33-38	2 Bolt
SA8	3/4"	38-43	2 Bolt
SA9	1"	38-43	2 Bolt
SA10	1"	39-44	4 Bolt
SA14	1.1/4"	52-57	4 Bolt
SA15	1.1/2"	52-57	4 Bolt
SA18	1.1/2"	63-69	4 Bolt
SA19	2"	63-69	4 Bolt
SA20	2"	64-71	4 Bolt

Fluid-Air Components Ltd

STEEL AIR & STEAM COUPLINGS & CLAMPS

Male Stem Only



0019	Thread	To Suit Hose ID
GMS-12	1/2"	1/2"
GMS-34	3/4"	3/4"
GMS-1	1"	1"
GMS-114	1.1/4"	1.1/4"
GMS-112	1.1/2"	1.1/2"
GMS-2	2"	2"

Ground Joint Couplings Complete



0019	Thread	To Suit Hose ID
GJS-12	1/2"	1/2"
GJS-34	3/4"	3/4"
GJS-1	1"	1"
GJS-114	1.1/4"	1.1/4"
GJS-112	1.1/2"	1.1/2"
GJS-2	2"	2"

Female Spud Only



0019	Thread
GSP-34	3/4"
GSP-1	1"
GSP-114	1.1/4"
GSP-112	1.1/2"
GSP-2	2"

Heavy-duty, 2 & 4 Bolt Clamps



0019	Bolts	To Suit Hose OD mm
SBC-12	2 Bolt	24-27
2052-9228	2 Bolt	27-30
SBC-34	2 Bolt	30-33
2052-9236	2 Bolt	33-38
2052-9244	2 Bolt	38-43
SBC-1	4 Bolt	39-43.5
2052-9251	4 Bolt	41-47
2052-9269	4 Bolt	48-52
2052-9277	4 Bolt	52-57
2052-9285	4 Bolt	53-58
SBC-2	4 Bolt	63.5-71
2052-9293	4 Bolt	89-100
	Tech Sheet 20396	

STEAM COUPLINGS

Steam Couplings

Heavy robust female and male thread screwings of zinc plated or brass, including forged safety clamps of brass for steam hoses. Female thread screwing two parts, swivelling. Connecting nut flat sealing with thread sealing ring.

Working Temperature: up to 210°C

Maximum Working Pressure: 18 bar

Male Steel Zinc Plated



0428	Thread	To Suit Hose ID mm	Wall Thickness mm
DAK12-13ST	1/2"	13	6
DAK34-19ST	3/4"	19	7
DAK10-25ST	1"	25	7.5
DAK15-38ST	1.1/2"	38	8

Female Steel Zinc Plated



0428	Thread	To Suit Hose ID mm	Wall Thickness mm
DIK12-13ST	1/2"	13	6
DIK34-19ST	3/4"	19	7
DIK10-25ST	1"	25	7.5
DIK15-38ST	1.1/2"	38	8

Male Brass




0428	Thread	To Suit Hose ID mm	Wall Thickness mm
DAK12-13MS	1/2"	13	6
DAK34-19MS	3/4"	19	7
DAK10-25MS	1"	25	7.5

Female Brass



0428	Thread	To Suit Hose ID mm	Wall Thickness mm
DIK12-13MS	1/2"	13	6
DIK34-19MS	3/4"	19	7
DIK15-38MS	1.1/2"	38	8

Female Sealing Ring



0428	Size
DGI12	1/2"
DGI34	3/4"
DGI10	1"
DGI15	1.1/2"
DGI20	2"

STEAM HOSE & ASSEMBLIES

Black Nylon Ply Steam Hose & Assemblies

- Manufactured to BS5122 Type A2 and ISO 6134

Maximum Working Temperature with Steam: +170°C



7 bar Hose, 20 Metre Coils

1370	ID mm	OD mm
BSH-3/4	19	31
BSH-1	25	39



7 bar Assemblies, 20 Metre Coils

1370	ID mm	OD mm
BSHA-3/4	19	31

Red Steel Reinforced Steam Hose & Assemblies

- Manufactured to BS5342 Type 2A

Maximum Working Temperature with Steam: +232°C



17 bar Hose, 20 Metre Coils

1370	ID mm	OD mm
RSH-3/4	19	32
RSH-1	25	38

Parker

Low Pressure Fluid Handling Solutions



legris

RECTUS



ENGINEERING YOUR SUCCESS.

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SHOT BLAST COUPLINGS, HOSE & NOZZLE HOLDERS

FT PRO

Shot Blast Couplings



Malleable Iron

0355	To Suit Hose OD mm
SHOT3101	39
SHOT3102	48
SHOT3103	56
SHOT3104	60

These couplings are designed for use on sandblast and cement placing hose.
Supplied with screws.

Maximum Working Pressure: 150 psi



Brass

6000	ID	OD mm
SBQ-34	3/4"	39



Nylon

0355	OD mm
SHOTCQP1	39
SHOTCQP2	48
SHOTCQP4	60

Threaded Couplings



Female Thread, Malleable Iron, BSPP

0355	Thread
SHOT3111	1.1/4"
SHOT3110	1.1/2"



Female Thread, Nylon, BSPP

0355	Thread
SHOTCFP	1.1/4"

Nozzle Holders



Alloy

0355	Thread
SD50-32A	48mm Coarse Thread
SD32-32A	48mm x 1.1/4" BSPP



Nylon

0355	Thread
NHP-34	33mm Coarse Thread
NHP-1	39mm Coarse Thread
HEP-1	39mm x 1.1/4" BSPP

Shot Blast Screws



0355
SHOTS

Safety Clips



0019	Description
LUE-USC-1	3mm Wire Clip

Rubber Rings



0355	Size
SHOTRSDKD	SKD Standard Seals
SHOTRSDR2	SDR2 for CQP-1
SHOTRSDR3	SDR-3 for CQP-2/3/4, CFP/CFP-50

Spare Rubber Seal



Suits All Sizes

0019
LUE-SKD-SEAL

SHOT BLAST COUPLINGS, HOSE & NOZZLE HOLDERS

Thread Stem Adaptors

Thread stem adaptors – to adapt your standard threaded stainless steel camlocks to plain stem types, for use with KSA range of clamps.



Part Code	Clamp Size
LUE-GTI 20-50 SS	KSA-63-67
LUE-GTI 30-75 SS	KSA-89-93

Female

0019	To Suit Hose ID	Thread
LUE-GTI 20-50 SS	50 x 8 (2")	2"
LUE-GTI 30-75 SS	75 x 8 (3")	3"

KSA Safety Clamps

Forged aluminium safety clamps, high quality and robust, easy to install and re-usable.



0019	To Suit Hose OD mm
LUE-KSA 36-39	36-39
LUE-KSA 63-67	63-67

Shot Blast Hose

Reinforcement: Textile wrapped.
Tube: NR/SBR/BR, Black smooth, antistatic abrasion resistant.
Cover: SBR, black, smooth, anti-static cloth impression.
Suitable for blasting sand and other media such as quartz sand, steel shot, corundum, glass, etc.
The hose has added security against electrical shocks by electrically-conductive lining.

Working Temperature:
-35°C to +80°C
(ambient temperature)



40 Metre Coils, 12 bar Hose

0101	ID mm	OD mm
SBH12-39	25	39
SBH12-48	32	48

GENUINE UNICONE FITTINGS

Genuine Unicone Fittings



Instantaneous Joints with Drab Rubbers

0439	ID mm
UIJ3	80
UIJ4	100
UIJ6	150
Tech Sheet 1936	



Serrated Hose Adaptors

0439	ID mm
USHT3	80
USHT4	100
Tech Sheet 1936	



Neoprene Rings

0439	ID mm
UNR3	80
UNR4	100
Tech Sheet 1936	



Plain Hose Tails

0439	ID mm
UPT3	80
UPT4	100
UPT6	150
Tech Sheet 1936	

Flange Adaptors D/E NP10/16

0439	ID mm
UFA4	100
Tech Sheet 1936	



Blank Ends

0439	ID mm
UBE3	80
UBE4	100
Tech Sheet 1936	

Drab Rubber Rings

0439	ID mm
UDR4	100
UDR5	125
UDR6	150
Tech Sheet 1936	

Weld On Pieces

0439	ID mm
UW4	100
Tech Sheet 1936	

Screwed Male Adaptors x 3 Long

0439	ID mm
USMT4	100
Tech Sheet 1936	

Fluid-Air Components Ltd

STORZ DIN SUCTION COUPLINGS

Adaptors



Female, BSPP, Aluminium

0148	Storz Size	Thread	Ka
SZ-21-031050-10	25-D	1/2"	31
SZ-21-031075-10	25-D	3/4"	31
SZ-21-031100-10	25-D	1"	31
SZ-21-044100-10	32	1"	44
SZ-21-044125-10	32	1.1/4"	44
SZ-21-051150-10	38	1.1/2"	51
SZ-21-051200-10	38	2"	51
SZ-21-066100-15	52-C	1"	66
SZ-21-066150-15	52-C	1.1/2"	66
SZ-21-066200-15	52-C DIN 14 307	2"	66
SZ-21-066250-15	52-C	2.1/2"	66
SZ-21-081200-10	65	2"	81
SZ-21-081250-10	65	2.1/2"	81
SZ-21-089200-15	75-B	2"	89
SZ-21-089250-15	75-B DIN 14 308	2.1/2"	89
SZ-21-089300-15	75-B	3"	89
SZ-21-105300-10	90	3"	105
SZ-21-115400-10	100	4"	115
SZ-21-133400-10	110-A	4"	133
SZ-21-133450-10	110-A DIN 14 309	4.1/2"	133
SZ-21-220800-10	205	8"	220
Tech Sheet 60474			



Female, BSPP, Copper Alloy (Brass)

0148	Storz Size	Thread	Ka
SZ-21-031100-30	25-D	1"	31
SZ-21-051200-30	38	2"	51
SZ-21-066200-35	52-C DIN 86 204	2"	66
SZ-21-066250-30	52-C	2.1/2"	66
SZ-21-081200-30	65	2"	81
Tech Sheet 60474			



Female with Safety Latch, Aluminium

0148	Storz Size	Thread	Ka
SZ-27-066200-10	52-C	2"	66
SZ-27-089300-10	75-B	3"	89
SZ-27-133400-10	110-A	4"	133
SZ-27-148500-10	125	5"	148
SZ-27-160600-10	150	6"	160
Tech Sheet 60474			



Male, BSPP, Copper Alloy (Brass)


0148	Storz Size	Thread	Ka
SZ-22-066200-30	52-C	2"	66
Tech Sheet 60475			



Male, BSPP, Aluminium


0148	Storz Size	Thread	Ka
SZ-22-031100-10	25-D	1"	31
SZ-22-044100-10	32	1"	44
SZ-22-051150-10	38	1.1/2"	51
SZ-22-066125-15	52-C	1.1/4"	66
SZ-22-066150-15	52-C	1.1/2"	66
SZ-22-066200-15	52-C	2"	66
SZ-22-081250-10	65	2.1/2"	81
SZ-22-089250-15	75-B	2.1/2"	89
SZ-22-089300-15	75-B	3"	89
SZ-22-133400-10	110-A	4"	133
Tech Sheet 60475			

Hose Tails



Aluminium

0148	Storz Size	To Suit Hose ID	Ka	Length mm
SZ-12-031025-10	25-D	25	31	53
SZ-12-044019-10	32	19	44	70
SZ-12-044025-10	32	25	44	70
SZ-12-044032-10	32	32	44	70
SZ-12-051038-10	38	38	51	90
SZ-12-066025-10	52-C	25	66	90
SZ-12-066032-10	52-C	32	66	90
SZ-12-066045-10	52-C	45	66	90
SZ-12-066052-10	52-C	52	66	90
SZ-12-066060-10	52-C	60	66	90
SZ-12-081065-10	65	65	81	95
SZ-12-089065-10	75-B	65	89	125
SZ-12-089070-10	75-B	70	89	125
SZ-12-089075-10	75-B	75	89	125
SZ-12-089080-10	75-B	80	89	125
SZ-12-105090-10	90	90	105	160
SZ-12-115100-10	100	100	115	150
SZ-12-133100-10	110-A	100	133	170
SZ-12-133110-10	110-A	110	133	170
SZ-12-160150-10	150	150	160	180
SZ-12-220205-10	205	205	220	375
Tech Sheet 60465				



Copper Alloy (Brass)


0148	Storz Size	To Suit Hose ID mm	Ka	Length mm
SZ-12-031025-30	25-D	25	31	25
SZ-12-066025-30	52-C	25	66	90
SZ-12-066045-30	52-C	45	66	90
SZ-12-066052-30	52-C	52	66	90
Tech Sheet 60473				



Aluminium, Smooth, DIN 2817

0148	Storz Size	To Suit Hose ID mm	Ka	Length mm
SZ-13-166050-10	52-C	50	66	95
SZ-13-089075-10	75-B	75	89	105
Tech Sheet 60473				

Couplings with Safety Latch



Aluminium

0148	Storz Size	To Suit Hose ID mm	Ka	Length mm
SZ-12-066045-19	52-C	45	66	90
SZ-12-066052-19	52-C DIN 14 321	52	66	90
SZ-12-081065-19	65	65	81	95
SZ-12-089065-19	75-B	65	89	125
SZ-12-089075-19	75-B DIN 14 322	75	89	125
SZ-12-115100-19	100	100	115	150
SZ-12-160150-19	150	150	160	180
Tech Sheet 60466				

STORZ DIN SUCTION COUPLINGS

Safety Clamps DIN 2817



Aluminium

0148	Size
SZ-13-800050-10	50 x 8
SZ-13-800075-10	75 x 8
SZ-13-800100-10	100 x 8
Tech Sheet 60467	

Reducers



Aluminium

0148	Storz Size	Ka	Ka
SZ-35-066044-10	52-C/32	66	44
SZ-35-081066-10	65/52-C	81	66
SZ-35-115089-10	100/75-B	115	89
SZ-35-160133-10	150/110-A	160	133
Tech Sheet 60468			

Blank Caps



With Chains, Aluminium

0148	Storz Size	Ka
SZ-31-031000-10	25-D DIN 14 310	31
SZ-31-044000-10	32	44
SZ-31-051000-10	38	51
SZ-31-066000-10	52-C DIN 14 311	66
SZ-31-081000-10	65	81
SZ-31-089000-10	75-B DIN 14 312	89
SZ-31-105000-10	90	105
SZ-31-115000-10	100	115
SZ-31-133000-10	110-A DIN 14 313	133
SZ-31-148000-10	125	148
SZ-31-160000-10	150	160
Tech Sheet 60469		

With Chains, Copper Alloy (Brass)

0148	Storz Size	Ka
SZ-31-031000-30	25-D	31
SZ-31-066000-30	52-C	66
Tech Sheet 60469		



With Lock, Aluminium

0148	Storz Size	Ka
SZ-31-500089-10	75-B	89
SZ-31-500133-10	110-A	133
Tech Sheet 60470		

Seals



Nitrile, Silicone & Viton

0148	Storz Size	Ka	Material
SZ-91-002031-00	25-D	31	Nitrile
SZ-91-002044-00	32	44	Nitrile
SZ-91-002051-00	38	51	Nitrile
SZ-91-002066-00	52-C	66	Nitrile
SZ-91-002081-00	65	81	Nitrile
SZ-91-002089-00	75-B	89	Nitrile
SZ-91-002133-00	110-A	133	Nitrile
SZ-91-002148-00	125	148	Nitrile
SZ-91-002160-00	150	160	Nitrile
SZ-91-002220-00	205	220	Nitrile
SZ-91-002031-02	25-D	31	Silicone
SZ-91-002044-02	32	44	Silicone
SZ-91-002051-02	38	51	Silicone
SZ-91-002066-02	52-C	66	Silicone
SZ-91-002081-02	65	81	Silicone
SZ-91-002089-02	75-B	89	Silicone
SZ-91-002115-02	100	115	Silicone
SZ-91-002133-02	110-A	133	Silicone
SZ-91-002066-03	52-C	66	Viton
Tech Sheet 60471			

Storz Coupling Spanners

- Size D shown



0148	Description
SZ-71-031031-50	Steel Spanner Size D
SZ-71-081051-50	Steel Spanner Size 65/38
SZ-71-089066-20	Cast Iron Spanner Size B C
SZ-71-133066-20	Cast Iron Spanner Size A B C
Tech Sheet 60472	

PORTWEST

For **Hand Protection**
see pages **1756-1758**



Fluid-Air Components Ltd

TRENCH PUMP HOSE COUPLINGS - LUG TYPE

Male BSPP



Malleable Iron, BSPP

0438	Thread
MIMT112	1.1/2"
MIMT2	2"
MIMT212	2.1/2"
MIMT3	3"
MIMT4	4"

Tech Sheet 20399

Male URT



Alloy, URT

0438	Thread
AMT3URT	3"
AMT4URT	4"

Tech Sheet 20397



Polypropylene, URT

0438	Thread
PMT3URT	3"
PMT4URT	4"

Female BSPP

- Leather washer included



Alloy, BSPP

0438	Thread
AMT112	1.1/2"
AMT2	2"
AMT212	2.1/2"
AMT3BSP	3"
AMT4BSP	4"



Malleable Iron, BSPP

0438	Thread	To Suit Hose ID
MICT112	1.1/2"	1.1/2"
MICT2	2"	2"
MICT212	2.1/2"	2.1/2"
MICT3	3"	3"
MICT4	4"	4"

Tech Sheet 20398

stainless steel



Stainless Steel, BSPP

0438	Thread	To Suit Hose ID
SSCT1	1"	1"
SSCT114	1.1/4"	1.1/4"
SSCT112	1.1/2"	1.1/2"
SSCT2	2"	2"
SSCT212	2.1/2"	2.1/2"



Polypropylene, BSPP

0438	Thread
PMT112	1.1/2"
PMT2	2"
PMT212	2.1/2"
PMT3BSP	3"
PMT4BSP	4"



Polypropylene, BSPP

0438	Thread	To Suit Hose ID
PCT112	1.1/2"	1.1/2"
PCT2	2"	2"
PCT212	2.1/2"	2.1/2"
PCT3BSP	3"	3"
PCT4BSP	4"	4"



Alloy, BSPP

0438	Thread	To Suit Hose ID
ACT112	1.1/2"	1.1/2"
ACT2	2"	2"
ACT212	2.1/2"	2.1/2"
ACT3BSP	3"	3"
ACT4BSP	4"	4"

TRENCH PUMP HOSE COUPLINGS - LUG TYPE

Female URT

- Poly washer included



Alloy, URT

0438	Thread	To Suit Hose ID
ACT3URT	3"	3"
ACT4URT	4"	4"

Tech Sheet 20400

- Poly washer included



Polypropylene, URT

0438	Thread	To Suit Hose ID
PCT3URT	3"	3"
PCT4URT	4"	4"

- Poly washer included



stainless steel

Stainless Steel, URT

0438	Thread	To Suit Hose ID
SSCT3URT	3"	3"

- Poly washer included



Gunmetal, URT

0438	Thread	To Suit Hose ID
GMCT3URT	3"	3"
GMCT4URT	4"	4"

Key Spanners



Aluminium

0438	To Suit	Description
KEY2	2"	Double Ended Spanner
KEY3	3"	Single Ended Spanner
KEY4	4"	Single Ended Spanner

Brass, Lugged, Screw-together Couplings



Brass Cap & Tail

0019	Thread	To Suit Hose ID
STCAS-12	1/2"	1/2"
STCAS-34	3/4"	3/4"
STCAS-1-12	1"	1/2"
STCAS-1-34	1"	3/4"
STCAS-1	1"	1"
STCAS-114-1	1.1/4"	1"
STCAS-114	1.1/4"	1.1/4"
STCAS-112-114	1.1/2"	1.1/4"
STCAS-112	1.1/2"	1.1/2"
STCAS-2	2"	2"
STCAS-3	3"	3"
STCAS-4	4"	4"



Female Linings

0019	To Suit Hose ID	To Suit Collar
STCL-12	1/2"	1/2"
STCL-1-12	1/2"	1"
STCL-34	3/4"	3/4"
STCL-1-34	3/4"	1"
STCL-1	1"	1"
STCL-114-1	1"	1.1/4"
STCL-114	1.1/4"	1.1/4"
STCL-112-114	1.1/4"	1.1/2"
STCL-112	1.1/2"	1.1/2"
STCL-2	2"	2"
STCL-3	3"	3"
STCL-4	4"	4"

Tech Sheet 20334



Male Threaded Half, BSPP

0019	Thread	To Suit Hose ID
STCM-12	1/2"	1/2"
STCM-34	3/4"	3/4"
STCM-1	1"	1"
STCM-114	1.1/4"	1.1/4"
STCM-112	1.1/2"	1.1/2"
STCM-2	2"	2"
STCM-3	3"	3"
STCM-4	4"	4"




Collar

0019	Thread
STCC-12	1/2"
STCC-34	3/4"
STCC-1	1"
STCC-114	1.1/4"
STCC-112	1.1/2"
STCC-2	2"
STCC-3	3"
STCC-4	4"

Customers who bought from this page also purchased...

JAYMAC Industrial Hose & Accessories



Layflat Hose
see page **1424**

Fluid-Air Components Ltd

TRENCH PUMP HOSE COUPLINGS - LUG TYPE

Blanking Caps

Alloy, BSPP/URT with Chain



0438	Thread
ABCC112	1.1/2" BSPP
ABCC2	2" BSPP
ABCC212	2.1/2" BSPP
ABCCBSP3	3" BSPP
ABCCURT3	3" URT
ABCCBSP4	4" BSPP
ABCCURT4	4" URT

Polypropylene, BSPP/URT without Chain



0438	Thread
PBCWOC112	1.1/2" BSPP
PBCWOC2	2" BSPP
PBCWOC212	2.1/2" BSPP
PBCWOCBSP3	3" BSPP
PBCWOCURT3	3" URT
PBCWOCBSP4	4" BSPP
PBCWOCURT4	4" URT

Polypropylene, URT with Chain



0438	Thread
PBCCURT3	3"
PBCCURT4	4"

Gunmetal, BSPP/URT with Chain



0438	Thread
GMBCC112	1.1/2" BSPP
GMBCC2	2" BSPP
GMBCC212	2.1/2" BSPP
GMBCCBSP3	3" BSPP
GMBCCURT3	3" URT
GMBCCBSP4	4" BSPP

Blanking Plugs



Alloy, BSPP/URT with Chain

0438	Thread
ABPC2	2" BSPP
ABPC212	2.1/2" BSPP
ABPCBSP3	3" BSPP
ABPCURT3	3" URT



Polypropylene, BSPP/URT without Chain

0438	Thread
PBPWOC112	1.1/2" BSPP
PBPWOC2	2" BSPP
PBPWOC212	2.1/2" BSPP
PBPWOCBSP3	3" BSPP
PBPWOCURT3	3" URT
PBPWOCURT4	4" URT

Spare Chains



0438
CHAIN

Washers

Note: To suit malleable iron, brass and poly trench pump couplings, steel flat face nuts and tail



Leather

0438	Size
WL14	1/4"
WL38	3/8"
WL12	1/2"
WL34	3/4"
WL1	1"
WL114	1.1/4"
WL112	1.1/2"
WL2	2"
WL212	2.1/2"
WL3	3"
WL4	4"

Note: To suit malleable iron, brass and poly trench pump couplings, steel flat face nuts and tail



Rubber

0438	Size
WR114	1.1/4"
WR112	1.1/2"
WR2	2"
WR212	2.1/2"
WR3	3"
WR4	4"



Rubber URT

0438	Size
WR3URT	3"
WR4URT	4"

Note: To suit malleable iron, brass and poly trench pump couplings, steel flat face nuts and tail



Poly URT

0438	Size
WP3URT	3"
WP4URT	4"

Fluid-Air Components Ltd

TANKER COUPLINGS & ADAPTORS

Tanker Coupling Adaptors



Alloy

0436	Size
AAMF112112	1.1/2" M x 1.1/2" F
AAMF1122	1.1/2" M x 2" F
AAMF1123	1.1/2" M x 3" F
AAMM22	2" M x 2" M
AAMF22	2" M x 2" F
AAMF2212	2" M x 2.1/2" F
AAMF23	2" M x 3" F
AAMF2122	2.1/2" M x 2" F
AAMF212212	2.1/2" M x 2.1/2" F
AAMF2123	2.1/2" M x 3" F
AAMF32	3" M x 2" F
AAMF3212	3" M x 2.1/2" F
AAMM33	3" M x 3" M
AAMF33	3" M x 3" F
AAMF34	3" M x 4" F
AAMF43	4" M x 3" F
AAMM43	4" M x 3" M



Gunmetal

0436	Size
GMAMF1122	1.1/2" M x 2" F
GMAMF112212	1.1/2" M x 2.1/2" F
GMAMF1123	1.1/2" M x 3" F
GMAMF2112	2" M x 1.1/2" F
GMAMM22	2" M x 2" M
GMAMF2212	2" M x 2.1/2" F
GMAMF23	2" M x 3" F
GMAMF2122	2.1/2" M x 2" F
GMAMM212212	2.1/2" M x 2.1/2" M
GMAMF212212	2.1/2" M x 2.1/2" F
GMAMF2123	2.1/2" M x 3" F
GMAMF32	3" M x 2" F
GMAMF3212	3" M x 2.1/2" F
GMAMM33	3" M x 3" M
GMAMF33	3" M x 3" F
GMAMF34	3" M x 4" F
GMAMF43	4" M x 3" F

Thread Adaptors



Alloy, URT

0436	Size
AAMFURTURT34	3" URT M x 4" URT F (Lug)
AAMMBSPURT33	3" BSPP M x 3" URT M (Hex)



Gunmetal, URT

0436	Size
GMAMFURTURT34	3" URT M x 4" URT F (Lug)
GMAMMBSPURT33	3" BSPP M x 3" URT M (Hex)



Polypropylene, URT

0436	Size
PAMFURTURT34	3" URT M x 4" URT F (Lug)

Threaded Alloy Flanged Adaptors



Table D, URT

0436	Thread
AAFDURT3	3"
AAFDURT4	4"

NP16, URT

0436	Thread
AAFNP16URT3	3"

For **Tank Gauges** see page **1654**



Fluid-Air Components Ltd

IBC Off Load System



Cam Male Adaptor x Female Thread - Part A

0501	Size	Thread
IBCAS6062	2"	S60 x 6
IBCAS606112	1.1/2"	S60 x 6
IBCAS6061	1"	S60 x 6
IBCA2NPS	2"	NPSM
IBCAS10083	3"	S100 x 8



Fixed Male Thread x Female Thread - Part HA

0501	Male Thread	Female Thread
IBCHAS6062BSP	2" BSPP	S60 x 6
IBCHAS606112BSP	1.1/2" BSPP	S60 x 6
IBCHAS6061BSP	1" BSPP	S60 x 6
IBCHAS60X34BSP	3/4" BSPP	S60 x 6
IBCHAS6062NPS	2" NPSM	S60 x 6
IBCHAS10083	3" BSPP	S100 x 8
IBCHAS606S1008	S60 x 6	S100 x 8
IBCHAS606NPSM2	S60 x 6	2" NPSM
IBCHAS6062BSPCWS	S60 x 6	2" BSPP with Seal



Cam Female Coupler x Hose Tail - Part C

0501	Size	To Suit Hose ID
IBCC21	2"	1" (25mm)
IBCC2114	2"	1.1/4" (32mm)
IBCC2112	2"	1.1/2" (38mm)
IBCC22	2"	2" (50mm)
IBCC33	3"	3" (75mm)



Female Coupler x Female Thread - Part D

0501	Size	Thread
IBCD112112BSP	1.1/2"	1.1/2" BSPP
IBCD22BSP	2"	2" BSPP
IBCDS6062	2"	S60 x 6



Swivel Hose Tail x Female Thread - Part HC

0501	To Suit Hose ID	Thread
IBCHCS6061	1" (25mm)	S60 x 6
IBCHCS606114	1.1/4" (32mm)	S60 x 6
IBCHCS606112	1.1/2" (38mm)	S60 x 6
IBCHCS6062	2" (50mm)	S60 x 6



Female Thread x Female Thread - Part HD

0501	Size
IBCHDS6062BSP	2" BSPP x S60 x 6
IBCHDS606112BSP	1.1/2" BSPP x S60 x 6
IBCHDS6062NPS	2" NPSM x S60 x 6



Dust Plug

0501	Size
IBCDP112	1.1/2"
IBCDP2	2"



Dust Cap

0501	Size
IBCDC112	1.1/2"
IBCDC2	2"
IBCDC3	3"



EPDM, Seal to suit S60 x 6 Thread

0501
IBC-SEAL

Fluid-Air Components Ltd

MORTAR HOSE COUPLINGS & PLUGS

Lever Couplings



Male Threaded, BSPP

0353	Size	Thread
MAG 10/25	25	1"
MAG 20/50	50	2"

Tech Sheet 20469



Female Threaded, BSPP

0353	Size	Thread
MIG 10/25	25	1"
MIG 15/35	35	1.1/2"
MIG 20/50	50	2"

Tech Sheet 20469



Hose Tail, BSPP

0353	Size	To Suit Hose ID mm
MST 38/35	35	38
MST 50	50	50

Tech Sheet 20469

Plugs



Male Threaded, BSPP

0353	Size	Thread
VAG 10/25	25	1"
VAG 20/50	50	2"

Tech Sheet 20469



Female Threaded, BSPP

0353	Size	Thread
VIG 10/25	25	1"
VIG 15/35	35	1.1/2"
VIG 20/50	50	2"

Tech Sheet 20469



Hose Tail

0353	Size	To Suit Hose ID mm
VST 38/35	35	38
VST 50	50	50

Tech Sheet 20469

FLANGES

Mild Steel Flanged Hose Tails

Table E, Mild Steel

0297	To Suit Hose ID
FEHT2	2"
FEHT3	3"
FEHT4	4"

Tech Sheet 20469

NP16, Mild Steel

0297	To Suit Hose ID
FNP16HT112	1.1/2"
FNP16HT2	2"
FNP16HT212	2.1/2"
FNP16HT3	3"
FNP16HT4	4"
FNP16HT6	6"
FNP16HT8	8"

Tech Sheet 20469



Flanged Hose Tail Table D, Mild Steel

0297	To Suit Hose ID
FDHT2	2"
FDHT3	3"
FDHT4	4"
FDHT5	5"
FDHT6	6"

Tech Sheet 20469

ASA150, Mild Steel

0297	To Suit Hose ID
FASA150HT2	2"

Tech Sheet 20469

Stainless Steel Flanged Hose Tails

stainless steel

Table E, Stainless Steel

0297	To Suit Hose ID
FHSESS2	2"

Tech Sheet 20469

NP16, Stainless Steel

0297	To Suit Hose ID
FHSNP16SS2	2"
FHSNP16SS3	3"

Tech Sheet 20469

ASA 150, Stainless Steel

0297	To Suit Hose ID
FHSASASS2	2"

Tech Sheet 20469

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FIRE HOSE & INSTANTANEOUS FIRE HOSE COUPLINGS

Adaptors



Aluminium Unpolished

0279	ID
FHAMIMI212212	2.1/2" M.I. x 2.1/2" M.I.
FHAFIFI212212	2.1/2" F.I. x 2.1/2" F.I.
FHAMIFBSP2122	2.1/2" M.I. x 2" F.BSPP
FHAMIFBSP212212	2.1/2" M.I. x 2.1/2" F.BSPP
FHAFIMBSP2122	2.1/2" F.I. x 2" M.BSPP
FHAFIMBSP212212	2.1/2" F.I. x 2.1/2" M.BSPP
FHAMIMBSP2122	2.1/2" M.I. x 2" M.BSPP
FHAMIMBSP212212	2.1/2" M.I. x 2.1/2" M.BSPP
FHAFIFBSP2122	2.1/2" F.I. x 2" F.BSPP
FHAFIFBSP212212	2.1/2" F.I. x 2.1/2" F.BSPP

Tech Sheet 20196

Rubber Gasket



0279	Size
FHCG	2.1/2"

Instantaneous Couplings



Aluminium Unpolished

0279	Size
FHCC212112	2.1/2" inst x 1.1/2" DR Hose Tail
FHCC212134	2.1/2" inst x 1.3/4" DR Hose Tail
FHCC2122	2.1/2" inst x 2" DR Hose Tail
FHCC212212	2.1/2" inst x 2.1/2" DR Hose Tail
FHCC2123	2.1/2" inst x 3" MS Hose Tail

Tech Sheet 20197



Male Half Instantaneous Couplings - Aluminium Unpolished

0279	Size
FHCC112MALE	2.1/2" inst x 1.1/2" DR Hose Tail
FHCC134MALE	2.1/2" inst x 1.3/4" DR Hose Tail
FHCC2MALE	2.1/2" inst x 2" DR Hose Tail
FHCC212MALE	2.1/2" inst x 2.1/2" DR Hose Tail
FHCC3MALE	2.1/2" inst x 3" MS Hose Tail

Tech Sheet 20201



Female Half Instantaneous Couplings - Aluminium Unpolished

0279	Size
FHCC112FEMALE	2.1/2" inst x 1.1/2" DR Hose Tail
FHCC134FEMALE	2.1/2" inst x 1.3/4" DR Hose Tail
FHCC2FEMALE	2.1/2" inst x 2" DR Hose Tail
FHCC212FEMALE	2.1/2" inst x 2.1/2" DR Hose Tail
FHCC234FEMALE	2.1/2" inst x 2.3/4" DR Hose Tail
FHCC3FEMALE	2.1/2" inst x 3" MS Hose Tail

Tech Sheet 20199

Blank Caps & Plugs



Aluminium Unpolished Blank Cap complete with Chain

0279	Size
FHCC212	2.1/2" F.I.

Tech Sheet 20198



Aluminium Unpolished Blank Plug complete with Chain

0279	Size
FHPC212	2.1/2" M.I.

Tech Sheet 20198

Standard Collecting Breeching



Unpolished

0279	Size
FHSCBMMF212	2.1/2" inst M x M x F

Tech Sheet 20202

Standard Dividing Breeching



Unpolished

0279	Size
FHSDBFFM212	2.1/2" inst F x F x M

Tech Sheet 20202

FIRE HOSE & INSTANTANEOUS FIRE HOSE COUPLINGS

JAYMAC Industrial Hose & Accessories

Ribblelite Plain Fire Hose

- Uncoated hose to BS6391
- Type 1

Maximum Working Pressure: 10 bar



White Uncoated Hose supplied without Couplings

0279	ID mm	Length Metres
FIRE-FHR4518	45	18
FIRE-FHR4523	45	23
FIRE-FHR4530	45	30
FIRE-FHR6418	64	18
FIRE-FHR6423	64	23
FIRE-FHR6430	64	30
Tech Sheet 20323		

White Uncoated Hose fitted with Light Alloy Instantaneous Couplings, Wired On

0279	ID mm	Length Metres
FIRE-FHR4518LA	45	18
FIRE-FHR4523LA	45	23
FIRE-FHR6418LA	64	18
FIRE-FHR6423LA	64	23
FIRE-FHR6430LA	64	30
Tech Sheet 20324		

Ribblelite Coated Fire Hose

- Coated hose to BS6391
- Type 2

Maximum Working Pressure: 10 bar



Red Coated Hose supplied without Couplings

0279	ID mm	Length Metres
FIRE-FHC4518	45	18
FIRE-FHC4523	45	23
FIRE-FHC6418	64	18
FIRE-FHC6423	64	23
FIRE-FHC6430	64	30
Tech Sheet 20321		

Red Coated Hose fitted with Light Alloy Instantaneous Couplings, Wired On

0279	ID mm	Length Metres
FIRE-FHC4518LA	45	18
FIRE-FHC4523LA	45	23
FIRE-FHC4530LA	45	30
FIRE-FHC6418LA	64	18
FIRE-FHC6423LA	64	23
FIRE-FHC6430LA	64	30
Tech Sheet 20322		

Brigadier Heavy-duty Fire Hose

- Red to BS6391
- Type 3

Maximum Working Pressure: 15 bar



Red supplied without Couplings

0279	ID mm	Length Metres
FIRE-FHB4518	45	18
FIRE-FHB4523	45	23
FIRE-FHB4530	45	30
FIRE-FHB6418	64	18
FIRE-FHB6423	64	23
FIRE-FHB6430	64	30
Tech Sheet 20319		

Red fitted with Light Alloy Instantaneous Couplings, Wired On

0279	ID mm	Length Metres
FIRE-FHB4518LA	45	18
FIRE-FHB4523LA	45	23
FIRE-FHB6418LA	64	18
FIRE-FHB6423LA	64	23
FIRE-FHB6430LA	64	30
Tech Sheet 20320		

FT PRO

For **Fire Sleeve** see pages **44-45**



FAC Fluid-Air Components Ltd

FIRE HOSE & INSTANTANEOUS FIRE HOSE COUPLINGS

Aquaflex Potable/Drinking Water Hose



Blue Rubber Covered supplied without Couplings

0279	ID mm	Length Metres
FIRE-FHQ4518	45	18
FIRE-FHQ4523	45	23
FIRE-FHQ6423	64	23
FIRE-FHQ6430	64	30
Tech Sheet 20330		

Blue Rubber Covered fitted with Light Alloy Instantaneous Couplings, Wired On

0279	ID mm	Length Metres
FIRE-FHQ4518LA	45	18
FIRE-FHQ4523LA	45	23
FIRE-FHQ4530LA	45	30
FIRE-FHQ6418LA	64	18
FIRE-FHQ6423LA	64	23
FIRE-FHQ6430LA	64	30
Tech Sheet 20331		

Fire Hose



Type 1, Uncoated Plain White Canvas B.P.40 bar, Cut to Length, per Metre

0279	ID
FHT12	2"
FHT1212	2.1/2"
Tech Sheet 20326	

Type 2, Lightweight Coated Red B.P.40 bar, Cut to Length, per Metre

0279	ID
FHT22	2"
FHT2212	2.1/2"
Tech Sheet 20327	

Type 3, Rubber Covered Red B.P.50 bar, Cut to Length, per Metre

0279	ID
FHT32	2"
Tech Sheet 20328	

Fire Hose Wire Whipped



Type 2, complete with Male/Female Couplings - 2.1/2"

0279	Length Metres
FHWT22125	5
FHWT221210	10
FHWT221215	15
FHWT221220	20
Tech Sheet 20329	

Red Fire Hose Nozzles Adjustable

Maximum Working Pressure: 10 bar



Plastic

0279	To Suit Hose ID
FHN34	3/4"
FHN1	1"

Branchpipes Lever Operated



Light Alloy

0279	Description
BPLODIN9	DIN Pattern Jet/Spray 9mm
BPLOBP113	British Pattern No.1 Jet/Spray 13mm
BPLOBP219	British Pattern No.2 Jet/Spray 19mm
BPLOWC13	Jet Spray Nozzle c/w Water Curtain 13mm
BPLOWC19	Jet Spray Nozzle c/w Water Curtain 19mm
Tech Sheet 20325	

Instantaneous Branchpipe & Nozzles



Aluminium Unpolished

0279	Description
BPS212	Standard Branchpipe (2.1/2" inst)
SNO12JET	(1/2" Jet) Nozzle Adaptor
SNO58JET	(5/8" Jet) Nozzle Adaptor
SNO34JET	(3/4" Jet) Nozzle Adaptor
BD212	Diffuser Branchpipe (2.1/2" inst)
Tech Sheet 20200	

STANDPIPES, MANHOLE & DRAIN KEYS

Standpipes



STANDW STANDB STANDC STANDS

Unpolished

0427	Description
STANDW	Anti Siphon Double Check Valve (Water Board)
STANDB	Single Swivel Head with HRT Base (Brigade)
STANDC	Contractors Standpipe 3/4"
STANDDS	Double Swivel Head with HRT Base
STANDSP	Single Plug-in Head with HRT Base
STANDS	Contractors Standpipe 3/4" Steel Tap BS10 c/w Double Check Valve to BS6282
STANDBG	Spare Standpipe Bottom Gasket

Customers who bought from this page also purchased...

FT PRO

Water Flex Flexible PVC Water Hose
see page **1422**




Manhole Lifting Keys



0427	Size
MAN6	6"
MAN12	12"
MAN20	20"
MAN24	24"

Drain Key & Bar T Handle



Unpolished

0427
DKBT

Hydrant Keys & Bars



Unpolished

0427	Description
HYDKB	Aluminium Key & Aluminium Bar
HYDK	Key Only
HYDB	Bar Only

Fluid-Air Components Ltd

COMBINATION STEEL NIPPLES & HOSE JOINERS

Combination Swaged Hose Nipples

NPT Plated Steel



0121	Thread	To Suit Hose ID mm
NCSNPT12	1/2"	12
NCSNPT34	3/4"	19
NCSNPT1	1"	25
NCSNPT114	1.1/4"	32
NCSNPT112	1.1/2"	38
NCSNPT2	2"	50
NCSNPT212	2.1/2"	63
NCSNPT3	3"	75
NCSNPT4	4"	100
NCSNPT6	6"	150

NPT Plated Steel, Long Tail



0121	Thread	To Suit Hose ID mm
NCLNPT6	6"	150

BSPT Plated Steel



1011	Thread
CNS-12	1/2"
CNS-34	3/4"
CNS-1	1"
CNS-114	1.1/4"
CNS-112	1.1/2"
CNS-2	2"
CNS-212	2.1/2"
CNS-3	3"
CNS-4	4"
CNS-5	5"
CNS-6	6"

stainless steel

BSPT Stainless Steel



1011	Thread
SCN-12	1/2"
SCN-34	3/4"
SCN-1	1"
SCN-114	1.1/4"
SCN-112	1.1/2"
SCN-2	2"
SCN-3	2"

Hose Joiners

Alloy



0289	To Suit Hose ID
JALL114	1.1/4"
JALL112	1.1/2"
JALL2	2"
JALL212	2.1/2"
JALL3	3"
JALL4	4"

stainless steel

Stainless Steel



0289	To Suit Hose ID
JSS34	3/4"
JSS1	1"
JSS114	1.1/4"
JSS112	1.1/2"
JSS2	2"
JSS3	3"
JSS4	4"

Plated Steel



1011	To Suit Hose ID
SHM-38	3/8"
SHM-12	1/2"
SHM-34	3/4"
SHM-1	1"
SHM-114	1.1/4"
SHM-112	1.1/2"
SHM-2	2"
SHM-212	2.1/2"
SHM-3	3"
SHM-4	4"
SHM-5	5"
SHM-6	6"
SHM-8	8"
SHM-10	10"

Steel Hose Menders, Long Length

Zinc Plated Steel



0289	To Suit Hose ID	Length mm
SV10R	3/8" (10mm)	75
SV13R	1/2" (13mm)	80
SV15R	5/8" (15mm)	105
SV19R	3/4" (19mm)	105
SV25R	1" (25mm)	160
SV32R	1.1/4" (32mm)	175
SV38R	1.1/2" (38mm)	215
SV50R	2" (50mm)	225

Safety Steel Hose Menders, Long Length

Zinc Plated Steel with Safety Collar



0289	To Suit Hose ID	Length mm
SV13R/S	1/2" (13mm)	80
SV15R/S	5/8" (15mm)	105
SV19R/S	3/4" (19mm)	105
SV25R/S	1" (25mm)	160
SV32R/S	1.1/4" (32mm)	175
SV38R/S	1.1/2" (38mm)	215
SV50R/S	2" (50mm)	225
SV75R/S	3" (75mm)	250

HEXAGON NUTS & TAILS

Hexagon Nuts & Tails

'A' Hex Nuts & Tails, BSPP Mild Steel



0298	Thread	To Suit Hose ID	Max Pressure PSI
NTA1	1"	1"	250
NTA114	1.1/4"	1.1/4"	150
NTA112	1.1/2"	1.1/2"	150
NTA2	2"	2"	150

'C' Plain Hex Nuts & Tails, BSPP Mild Steel



0298	Thread	To Suit Hose ID	Max Pressure PSI
NTC12	1/2"	1/2"	150
NTC34	3/4"	3/4"	150
NTC1	1"	1"	150
NTC114	1.1/4"	1.1/4"	150
NTC112	1.1/2"	1.1/2"	150
NTC2	2"	2"	150

SWC Nuts & Tails, BSPP Mild Steel



0298	Thread	To Suit Hose ID	Max Pressure PSI
NTSWC112	1.1/2"	1.1/2"	150
NTSWC2	2"	2"	150

MODULAR COOLANT HOSE SYSTEMS

Compatibility:
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: Polyoxymethylene (POM).
Recommended Maximum Line Pressure: 20-30 psi.
Recommended Maximum Flow Rate: 1,800 litres per hour.
Interchangeable with: Loc-Line.

Maximum Operating Temperature: +76°C
Repeated exposure to this temperature will cause fatigue.

Features:
- Unique ball and socket design, fully hand-adjustable in both position and length
- Will not kink or fatigue; bending does not decrease the inside diameter
- Will not damage machine tool cutters if contact occurs, unlike metal hoses
- Electrically non-conductive; ideal for EDM flushing
- No internal positioning rod that can break or restrict fluid flow
- Stays in position; repeated positioning is easy
- Creep due to machine vibration is eliminated

1/4" Series



Round Nozzles

0518	Nozzle Hole Size
28015	1/16"
28016	1/8"
28017	1/4"
Tech Sheet 68071	



Flat Nozzle

0518	Nozzle Hole Size
28027	Size 60
Tech Sheet 68071	



Swivel Nozzle

0518	Nozzle Hole Size
28029	Size 40
Tech Sheet 68071	



90° Round Nozzles

0518	Nozzle Hole Size
28019	1/16"
28020	1/8"
28021	1/4"
Tech Sheet 68071	



Flare Nozzle

0518	Nozzle Hole Size
28028	1"
Tech Sheet 68071	



Male Connectors, NPT

0518	Thread
28032	1/8"
28033	1/4"
Tech Sheet 68071	



90° Spray Bar Nozzle

0518	Nozzle Hole Size
28022	Size 60
Tech Sheet 68071	

ambersil
FOOD PROCESSING SAFE


For **Tufcut Metal Cutting Lubricant** see page **1575**

Fluid-Air Components Ltd

MODULAR COOLANT HOSE SYSTEMS

Compatibility:
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: Polyoxymethylene (POM).
Recommended Maximum Line Pressure: 20-30 psi.
Recommended Maximum Flow Rate: 1,800 litres per hour.
Interchangeable with: Loc-Line.

Maximum Operating Temperature: +76°C
Repeated exposure to this temperature will cause fatigue.

1/4" Series



Y Connector

0518
28034
Tech Sheet 68071



90° Elbow Connector

0518
28035
Tech Sheet 68071



Valve, In-line

0518
28043
Tech Sheet 68071



T Connector

0518
28036
Tech Sheet 68071



Valve, Tube x Male, NPT

0518	Thread
28049	1/4"
Tech Sheet 68071	



Check Valve, In-line

0518
28051
Tech Sheet 68071



End Cap

0518
28038
Tech Sheet 68071



Valve, Tube x Female, NPT

0518	Thread
28050	1/4"
Tech Sheet 68071	

RIDGID



You might also need...
RIDGID PC 116 Powered Tubing Cutter
...see page **1743**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MODULAR COOLANT HOSE SYSTEMS

Compatibility:
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: Polyoxymethylene (POM).
Recommended Maximum Line Pressure: 20-30 psi.
Recommended Maximum Flow Rate: 1,800 litres per hour.
Interchangeable with: Loc-Line.

Maximum Operating Temperature: +76°C
Repeated exposure to this temperature will cause fatigue.

1/4" Series



Extended Element

0518	Length mm
28011	90

Tech Sheet 68071



Extended Element Clamp

0518
28042

Tech Sheet 68071



Hose Coil

0518	Length Metres
28012	15.24

Tech Sheet 68071




Hose Only Kit

0518	Quantity	Length mm
XS2001	4	150

Tech Sheet 68071

Contents:
- 1 x 1/8" NPT male connector
- 1 x 1/4" NPT female connector
- 1 x 1/16", 1/8" and 1/4" round nozzles
- 280mm hose




Hose Kit

0518
28003

Tech Sheet 68071

Contents:
- 1 x 1/4" NPT connector
- 1 x 1/8" round nozzle, assembled



Hose Kit Assembly

0518	Length mm
28002	300

Tech Sheet 68071



Hose Assembly Pliers

0518
28008

Tech Sheet 68071



Circle Flow Nozzle Kit

0518	ID mm	Length mm
28013	92	446

Tech Sheet 68071

You might also need…

PORTWEST

PPE
see pages **1752-1760**



Fluid-Air Components Ltd

MODULAR COOLANT HOSE SYSTEMS

Compatibility:
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: Polyoxymethylene (POM).
Recommended Maximum Line Pressure: 30 psi
Recommended Maximum Flow Rate: 2,150 litres per hour.
Interchangeable with: Loc-Line.

Maximum Operating Temperature: +76°C
Repeated exposure to this temperature will cause fatigue.

1/2" Series



Round Nozzles

0518	Nozzle Hole Size
48013	1/4"
48014	3/8"
48015	1/2"
Tech Sheet 68071	



Flare Nozzles

0518	Nozzle Hole Size
48026	1.1/4"
48027	2.1/2"
Tech Sheet 68071	



Male Connectors, NPT

0518	Thread
48030	3/8"
48031	1/2"
Tech Sheet 68071	



Flat Nozzle

0518	Nozzle Hole Size
48024	Size 80
Tech Sheet 68071	



Flat Holed Nozzles

0518	Nozzle
48022	5 Holes
48023	7 Holes
Tech Sheet 68071	



Y Connector

0518
48032
Tech Sheet 68071

For **Reinforced PVC Braided Hose** see pages **1404-1405**





90° Elbow Connector

0518
48034
Tech Sheet 68071

Fluid-Air Components Ltd

MODULAR COOLANT HOSE SYSTEMS

Compatibility:
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: Polyoxymethylene (POM).
Recommended Maximum Line Pressure: 30 psi
Recommended Maximum Flow Rate: 2,150 litres per hour.
Interchangeable with: Loc-Line.

Maximum Operating Temperature: +76°C
Repeated exposure to this temperature will cause fatigue.

1/2" Series



Valve, Tube x Male, NPT

0518	Thread
48041	1/2"

Tech Sheet 68071



Valve, Tube x Female, NPT

0518	Thread
48042	1/2"

Tech Sheet 68071



Valve, In-line

0518
48043

Tech Sheet 68071



Hose Only Kit

0518	Quantity	Length mm
XS4001	4	150

Tech Sheet 68071




Hose Coil

0518	Length Metres
48010	15.24

Tech Sheet 68071

Contents:
- 1 x 3/8" NPT male connector
- 1 x 1/2" NPT female connector
- 1 x 1/4", 3/8" and 1/2" round nozzles
- 280mm hose



Hose Kit

0518
48003

Tech Sheet 68071

Contents:
- 1 x 1/2" NPT connector
- 1 x 3/8" round nozzle, assembled



Hose Kit Assembly

0518	Length mm
48002	300

Tech Sheet 68071



Hose Assembly Pliers

0518
48006

Tech Sheet 68071



Extended Element Kit

0518
48008

Tech Sheet 68071

Fluid-Air Components Ltd

LEVER LOCK WATER PUMP COUPLINGS

FT Pro couplings provide a quick and easy way to join many lengths of hose together. They are commonly used for the pumping and transfer of water in the construction, road maintenance and general irrigation industries. They can also be used for loading and unloading road tankers.

Interchangeable with: BAUER

Maximum Working Temperature: +80°C

Maximum Working Pressure:
2" to 3.1/2" 20 bar
4" to 8" 12 bar



Galvanised with Standard Rubber Sealing Ring

0372	Coupling Size mm	To Suit Hose ID
LLZDUTY-LLC2	50	2"
LLZDUTY-LLC3	76	3"
LLZDUTY-LLC3312	89	3" Tail x 3.1/2"
LLZDUTY-LLC4	108	4"
LLZDUTY-LLC6	159	6"
LLZDUTY-LLC8	194	8"
Tech Sheet 20540		



For **Hydraulic Hand Pumps** see pages **229-230**

FT Pro four bolt hole MZ flange couplings are commonly used on a wide range of agricultural slurry tankers and spreaders.

FT Pro couplings provide a quick and easy way to join many lengths of hose together.

They are commonly used for the pumping and transfer of water in the construction, road maintenance and general irrigation industries. They can also be used for loading and unloading road tankers.

Male Square MZ Flange



With Closure Ring, Galvanised

0372	Coupling Size mm
LLZD-MZLLM89	89
LLZD-MZLLM108	108
LLZD-MZLLM133	133
LLZD-MZLLM159	159
LLZD-MZLLM194	194
Tech Sheet 68126	

Female Square MZ Flange



With Sealing Ring

0372	Coupling Size mm
LLZD-MZFF89	89
LLZD-MZFF108	108
LLZD-MZFF133	133
LLZD-MZFF159	159
LLZD-MZFF194	194
Tech Sheet 68127	

Lever Closure Ring



Galvanised

0372	Coupling Size mm
LLZD-LLCR2	50
LLZD-LLCR33	76
LLZD-LLCR3312	89
LLZD-LLC4	108
LLZD-LLCR5	133
LLZD-LLCR6	159
LLZD-LLCR8	194

Interchangeable with: BAUER.

Maximum Working Temperature: +80°C

Maximum Working Pressure:
2" to 3.1/2": 20 bar
4" to 8": 12 bar

Male x Male BSPT Pipe Thread



With Closure Ring, Galvanised

0372	Coupling Size mm	Thread
LLZD-LLMBSP2	50	2"
LLZD-LLMBSP212	76	2.5"
LLZD-LLMBSP33	76	3"
LLZD-LLMBSP4	108	4"
LLZD-LLMBSP5	133	5"
LLZD-LLMBSP6	159	6"
LLZD-LLMBSP8	194	8"

Female x Male BSPT Pipe Thread



Galvanised

0372	Coupling Size mm	Thread
LLZD-LLFBSP2	50	2"
LLZD-LLFBSP212	76	2.5"
LLZD-LLFBSP33	76	3"
LLZD-LLFBSP4	108	4"
LLZD-LLFBSP5	133	5"
LLZD-LLFBSP6	159	6"
LLZD-LLFBSP8	194	8"

Male Weld End



Ungalvanised

0372	Coupling Size mm
LLZD-LLMWE33	76
LLZD-LLMWE3312	89
LLZD-LLMWE4	108
LLZD-LLMWE5	133
LLZD-LLMWE6	159
LLZD-LLMWE8	194

LEVER LOCK WATER PUMP COUPLINGS

FT Pro four bolt hole MZ flange couplings are commonly used on a wide range of agricultural slurry tankers and spreaders.

FT Pro couplings provide a quick and easy way to join many lengths of hose together.

They are commonly used for the pumping and transfer of water in the construction, road maintenance and general irrigation industries. They can also be used for loading and unloading road tankers.

Interchangeable with: BAUER.

Maximum Working Temperature: +80°C

Maximum Working Pressure:
2" to 3.1/2": 20 bar
4" to 8": 12 bar

Female Weld End



Ungalvanised

0372	Coupling Size mm
LLZD-LLFWE2	50
LLZD-LLFWE33	76
LLZD-LLFWE3312	89
LLZD-LLFWE4	108
LLZD-LLFWE5	133
LLZD-LLFWE6	159
LLZD-LLFWE8	194

Female End Caps



Galvanised

0372	Coupling Size mm
LLZD-LLFEC2	50
LLZD-LLFEC33	76
LLZD-LLFEC3312	89
LLZD-LLFEC4	108
LLZD-LLFEC5	133
LLZD-LLFEC6	159
LLZD-LLFEC8	194

Strainers



G.P. Strainers, Steel Galvanised

0372	Coupling Size mm
LLZD-LLGP2	50
LLZD-LLGP3312	89
LLZD-LLGP4	108
LLZD-LLGP5	133
LLZD-LLGP6	159
LLZD-LLGP8	194

Male End Cap



Galvanised

0372	Coupling Size mm
LLZD-LLMEC2	50
LLZD-LLMEC33	76
LLZD-LLMEC3312	89
LLZD-LLMEC4	108
LLZD-LLMEC5	133
LLZD-LLMEC6	159
LLZD-LLMEC8	194

90° Bends




Galvanised

0372	Coupling Size mm
LLZD-LL90B2	50
LLZD-LL90B33	76
LLZD-LL90B3312	89
LLZD-LL90B4	108
LLZD-LL90B5	133
LLZD-LL90B6	159
LLZD-LL90B8	194

Customers who bought from this page also purchased...

JAYMAC Industrial Hose & Accessories

Heavy-duty Suction Hose
see page **1428**



Fluid-Air Components Ltd

STAINLESS STEEL LEVER LOCK WATER PUMP COUPLINGS

Complete Connection Set

Maximum Working Pressure:
2" to 3.1/2" 20 bar
4" to 8" 12 bar



Galvanised with Standard Rubber Sealing Ring

0120	Coupling Size mm	To Suit Hose ID
LLC2	50	2"
LLC33	76	3 Tail x 3"
LLC3312	89	3 Tail x 3.1/2"
LLC4	108	4"
LLC5	133	5"
LLC6	159	6"
LLC8	194	8"

Galvanised with Oil Resistant Rubber Sealing Ring

0120	Coupling Size mm	To Suit Hose ID
LLC2OROR	50	2"
LLC33OROR	76	3 Tail x 3"
LLC4OROR	108	4"
LLC8ORORO	194	8"

Male x Hose Connector

stainless steel



0120	Coupling Size mm	To Suit Hose ID
LLSSMT2	50	2"
LLSSMT33	76	3"
LLSSMT3312	89	3" Tail x 3.1/2"
LLSSMT4	108	4"
LLSSMT6	159	6"
LLSSMT8	194	8"

Female x Hose Connector

stainless steel



0120	Coupling Size mm	To Suit Hose ID
LLSSFT2	50	2"
LLSSFT3312	89	3" Tail x 3.1/2"
LLSSFT4	108	4"
LLSSFT6	159	6"
LLSSFT8	194	8"

Male Weld End

Other sizes available on request.
Minimum quantity order may apply.

stainless steel



0120	Coupling Size mm
LLSSMWE2	50
LLSSMWE3312	89
LLSSMWE4	108
LLSSMWE6	159

Female Weld End

stainless steel



0120	Coupling Size mm
LLSSFWE2	50
LLSSFWE33	76
LLSSFWE3312	89
LLSSFWE4	108
LLSSFWE6	159

Male x Male BSPP Pipe Thread

Other sizes available on request.
Minimum quantity order may apply.

stainless steel



With Lever Closure Ring, BSPP

0120	Coupling Size mm	To Suit Hose ID
LLSSMBSP2	50	2"
LLSSMBSP33	76	3"
LLSSMBSP3312	89	3" BSPP x 3.1/2"
LLSSMBSP4	108	4"

Female complete with BSPP Male Pipe Thread

Other sizes available on request.
Minimum quantity order may apply.

stainless steel



0120	Coupling Size mm	Thread
LLSSFBSP2	50	2"
LLSSFBSP33	76	3"
LLSSFBSP3312	89	3" BSPP x 3.1/2"
LLSSFBSP4	108	4"
LLSSFBSP5	133	5"
LLSSFBSP6	159	6"

Male End Cap

stainless steel



0120	Coupling Size mm
LLSSMEC2	50
LLSSMEC33	76
LLSSMEC3312	89
LLSSMEC4	108
LLSSMEC5	133
LLSSMEC6	159

Female End Cap

Other sizes available on request.
Minimum quantity order may apply.

stainless steel



0120	Coupling Size mm
LLSSFEC3312	89
LLSSFEC4	108
LLSSFEC6	159

LEVER LOCK WATER PUMP COUPLINGS

Male x Hose Connector



Galvanised

0120	Coupling Size mm	To Suit Hose ID
LLMT2	50	2"
LLMT33	76	3" Tail x 3"
LLMT3312	89	3" Tail x 3.1/2"
LLMT4	108	4"
LLMT5	133	5"
LLMT6	159	6"
LLMT8	194	8"

Female x Hose Connector



Galvanised

0120	Coupling Size mm	To Suit Hose ID
LLFT2	50	2"
LLFT33	76	3" Tail x 3"
LLFT3312	89	3" Tail x 3.1/2"
LLFT4	108	4"
LLFT5	133	5"
LLFT6	159	6"
LLFT8	194	8"

Lever Closure Ring



Galvanised

0120	Coupling Size mm	To Suit Hose ID
LLCR2	50	2"
LLCR33	76	3" Tail x 3"
LLCR3312	89	3" Tail x 3.1/2"
LLCR4	108	4"
LLCR5	133	5"
LLCR6	159	6"
LLCR8	194	8"

Rubber Sealing Ring

Natural Rubber (NR)



0120	Coupling Size mm
LLOR2	50
LLOR33	76
LLOR3312	89
LLOR4	108
LLOR5	133
LLOR6	159
LLOR8	194

Oil Resistant Rubber Sealing Ring

Nitrile Rubber (NBR)



0120	Coupling Size mm
LLOROR2	50
LLOROR33	76
LLOROR3312	89
LLOROR4	108
LLOROR5	133
LLOROR6	159
LLOROR8	194

Male x Male BSPT Pipe Thread



With Lever Closure Ring, Galvanised

0120	Coupling Size mm	Thread	To Suit Hose ID
LLMBSP112	50	-	1.1/2"
LLMBSP2	50	-	2"
LLMBSP212	76	-	2.1/2"
LLMBSP33	76	3" BSPP	3"
LLMBSP3312	89	3" BSPP	3.1/2"
LLMBSP4	108	-	4"
LLMBSP5	133	-	5"
LLMBSP6	159	-	6"
LLMBSP8	194	-	8"

Male complete with URT Male/Female Thread



With Lever Closure Ring, Ungalvanised, URT

0120	Coupling Size mm	Thread
LLM44URTM	4" Male	4" Male
LLM44URTF	4" Male	4" Female

Female complete with BSPP Male Pipe Thread



Galvanised

0120	Coupling Size mm	Thread	To Suit Hose ID
LLFBSP112	50	-	1.1/2"
LLFBSP2	50	-	2"
LLFBSP212	76	-	2.1/2"
LLFBSP33	76	3" BSPP	3"
LLFBSP3312	89	3" BSPP	3.1/2"
LLFBSP4	108	-	4"
LLFBSP5	133	-	5"
LLFBSP6	159	-	6"
LLFBSP8	194	-	8"

Female complete with URT Male/Female Thread



Ungalvanised

0120	Coupling Size mm	Thread
LLF333URTF	3" Female	3" Female
LLF33123URTF	3.1/2" Female	3" Female
LLF44URTM	4" Female	4" Male
LLF44URTF	4" Female	4" Female

Fluid-Air Components Ltd

LEVER LOCK WATER PUMP COUPLINGS

Male Weld End



Ungalvanised

0120	Coupling Size mm
LLMWE2	50
LLMWE33	76
LLMWE3312	89
LLMWE4	108
LLMWE5	133
LLMWE6	159
LLMWE8	194

Female Weld End



Ungalvanised

0120	Coupling Size mm
LLFWE2	50
LLFWE33	76
LLFWE3312	89
LLFWE4	108
LLFWE5	133
LLFWE6	159
LLFWE8	194

Flanged Male, Table D



Galvanised

0120	Coupling Size mm
LLMFD2	50
LLMFD33	76
LLMFD3312	89
LLMFD4	108
LLMFD46	108 x 6"
LLMFD5	133
LLMFD6	159
LLMFD8	194

Flanged Female, Table D



Galvanised

0120	Coupling Size mm
LLFFD2	50
LLFFD33	76
LLFFD3312	89
LLFFD4	108
LLFFD6	159
LLFFD8	194

Flanged Male, Table E



Galvanised

0120	Coupling Size mm
LLMFE162	50
LLMFE1633	76
LLMFE163312	89
LLMFE164	108
LLMFE1646	108 x 6"
LLMFE165	133
LLMFE166	159
LLMFE168	194

Flanged Female, Table E



Galvanised

0120	Coupling Size mm
LLFFE162	50
LLFFE1633	76
LLFFE163312	89
LLFFE164	108
LLFFE1646	108 x 6"
LLFFE165	133
LLFFE166	159
LLFFE168	194

Lever Closure Ring



Ungalvanised

0120	Coupling Size mm
LCRB2	50
LCRB33	76
LCRB3312	89
LCRB4	108
LCRB5	133
LCRB6	159
LCRB8	194

Y Unions



Y Union with Female Outlet, Galvanised

0120	Coupling Size mm
LLYMMF2	50
LLYMMF33	76
LLYMMF3312	89
LLYMMF4	108
LLYMMF6	159



Y Union with Male Outlet, Galvanised

0120	Coupling Size mm
LLYFFM2	50
LLYFFM33	76
LLYFFM3312	89
LLYFFM4	108
LLYFFM6	159

Male End Cap



With Lever Closure

0120	Coupling Size mm
LLMEC2	50
LLMEC33	76
LLMEC3312	89
LLMEC4	108
LLMEC5	133
LLMEC6	159
LLMEC8	194

Female End Caps



Galvanised

0120	Coupling Size mm
LLFEC2	50
LLFEC33	76
LLFEC3312	89
LLFEC4	108
LLFEC5	133
LLFEC6	159
LLFEC8	194

LEVER LOCK WATER PUMP COUPLINGS

Female x Male Reducer



Galvanised

0120	Description
LLFM332	76 Female x 50 Male
LLFM33122	89 Female x 50 Male
LLFM331233	89 Female x 76 Male
LLFM433	108 Female x 76 Male
LLFM43312	108 Female x 89 Male
LLFM54	133 Female x 108 Male
LLFM64	159 Female x 108 Male
LLFM65	159 Female x 133 Male
LLFM86	194 Female x 159 Male

T Unions



T Union with Female Outlet, Galvanised

0120	Coupling Size mm
LLTMFF2	50
LLTMFF4	108
LLTMFF6	159



T Union with Male Outlet, Galvanised

0120	Coupling Size mm
LLTMMF2	50
LLTMMF33	76
LLTMMF3312	89
LLTMMF4	108
LLTMMF5	133
LLTMMF6	159
LLTMMF8	194

Male x Female Riser



Galvanised

0120	Description
LLFM233	50 Female x 76 Male
LLFM23312	50 Female x 89 Male
LLFM333312	76 Female x 89 Male
LLFM334	76 Female x 108 Male
LLFM33124	89 Female x 108 Male
LLFM45	108 Female x 133 Male
LLFM46	108 Female x 159 Male
LLFM56	133 Female x 159 Male
LLFM68	159 Female x 194 Male

Safety Pins



Galvanised Steel

0120	To Suit Coupling Size mm
LLMSSPIN50	50
LLMSSPIN76	76
LLMSSPIN89108	89 - 108
LLMSSPIN133	133
LLMSSPIN159194	159 - 194

30° Bends



30° Bend, Galvanised

0120	Coupling Size mm
LL30B2	50
LL30B3	76
LL30B33	89
LL30B4	108
LL30B5	133
LL30B6	159
LL30B8	194

45º Bends



45° Bend, Galvanised

0120	Coupling Size mm
LL45B2	50
LL45B33	76
LL45B3312	89
LL45B4	108
LL45B5	133
LL45B6	159
LL45B8	194



Male Flanged 45° Bend - NP16, Galvanised

0120	Coupling Size mm
LL45MF4	108
LL45MF6	159



Female Flanged 45° Bend - NP16, Galvanised

0120	Coupling Size mm
LL45FF4	108
LL45FF6	159

Fluid-Air Components Ltd

LEVER LOCK WATER PUMP COUPLINGS

90º Bends



90° Bend, Galvanised

0120	Coupling Size mm
LL90B2	50
LL90B33	76
LL90B3312	89
LL90B4	108
LL90B5	133
LL90B6	159
LL90B8	194



Male Flanged 90° Bend - NP16, Galvanised

0120	Coupling Size mm
LL90MF33	76
LL90MF3312	89
LL90MF4	108
LL90MF6	159
LL90MF8	194



Female Flanged 90° Bend - NP16, Galvanised

0120	Coupling Size mm
LL90FF33	76
LL90FF3312	89
LL90FF4	108
LL90FF6	159
LL90FF8	194



Male Flanged 90° Bend - Table D, Galvanised

0120	Coupling Size mm
LL90MF3312TD	89
LL90MF4TD	108
LL90MF6TD	159



Female Flanged 90° Bend - Table D, Galvanised

0120	Coupling Size mm
LL90FF2TD	50
LL90FF4TD	108

Customers who bought from this page also purchased...



FTPRO

Carbon Steel Flanges
see page **1387**

Strainers



G.P. Strainers, Steel Galvanised

0120	Coupling Size mm
LLGP2	50
LLGP3312	89
LLGP4	108
LLGP6	159
LLGP8	194



Sewage Strainers, Steel Galvanised

0120	Coupling Size mm
LLSS4	108
LLSS6	159



Male Foot Valve Strainer, Galvanised

0120	Coupling Size mm
LLFVSM2	50
LLFVSM33	76
LLFVSM3312	89
LLFVSM4	108
LLFVSM5	133
LLFVSM6	159
LLFVSM8	194



Hose Tail Foot Valve Strainer, Galvanised

0120	To Suit Hose ID
LLFVSHT2	2"
LLFVSHT3	3"
LLFVSHT4	4"
LLFVSHT5	5"
LLFVSHT6	6"
LLFVSHT8	8"
LLFVSHT12	12"

LEVER LOCK WATER PUMP COUPLINGS

Large Bore Dallai Couplings



Male Hose Tail

0120	Coupling Size mm
LLMT10	10"
LLMT12	12"



Female Hose Tail

0120	Coupling Size mm
LLFT10	10"
LLFT12	12"



Flanged Male

0120	Coupling Size mm
LLMF10	10"
LLMF12	12"



Flanged Female

0120	Coupling Size mm
LLFF10	10"
LLFF12	12"



Male x Female 90° Bend

0120	Coupling Size mm
LL90B10	10"
LL90B12	12"



Male x Female 45° Bend

0120	Coupling Size mm
LL45B10	10"
LL45B12	12"



Male Blank Ends

0120	Coupling Size mm
LLMEC10	10"
LLMEC12	12"



Male Weld Ends

0120	Coupling Size mm
LLMWE12	12"




Female Weld Ends

0120	Coupling Size mm
LLFWE10	10"
LLFWE12	12"

JAYMAC Industrial Hose & Accessories

For **Water Delivery Hose** see page **1431**



Fluid-Air Components Ltd

1	Hydraulics	3-284
2	Hydraulic Quick Release Couplings	285-320
3	Pneumatic Quick Release Couplings	321-406
4	Monitor & Test	407-446
5	Pneumatic & Vacuum	447-762
6	Push-in Fittings & Tubing	763-918
7	Valves & Actuation	919-1060
8	Ring Main	1061-1136
9	Hose Tails, Adaptors, Fittings & Manifolds	1137-1224
10	Stainless Steel	1225-1332
11	Malleable Iron	1333-1398
12	Hose, Couplings, Ducting & Hose Reels	1399-1510
13	**Clips & Clamps**	**1511-1558**
14	Paint, Sprays & Adhesives	1559-1590
15	Blow Guns, Vacuum & Nozzles	1591-1616
16	Fuelling, Lubrication, Wash Down & Misting	1617-1696
17	Compressors & Air Tools	1697-1726
18	Hand Tools & PPE	1727-1765

SECTION 13

Clips & Clamps

13.01	Worm Drive Clamps & Clips	**1511-1535**
13.02	O Clips & Pliers	**1536-1539**
13.03	P Clips	**1536-1539**
13.04	Pipe Clips & Fixing Systems	**1545-1551**
13.05	Banding Systems & Cable Ties	**1552-1555**
13.06	Ferrules & Pipe Repair Couplings	**1556-1558**

Fluid-Air Components Ltd

SECTION 13

13.01 Worm Drive Clamps & Clips

1511-1535

- Worm Drive Hose Clamps & U Bolts
- Pipe Clamps
- Clamps & Clips Kits
- Clamps & Hose Clips
- Hose Clips
- Clip Packs
- Counter Dispensers
- Worm Drive Hose Clamps
- Clamps & Hose Clips
- Clamps, Clips & Fasteners



13.02 O Clips & Pliers

1536-1539

- O Clips & Pliers
- Hose Clamps
- Hose & Pipe Cleaning Kits
- Service Plugs



13.03 P Clips

1540-1544

- Pipe Clips & Tool Clips
- Clamps & Hose Clips
- Clips
- Clip Packs
- Clamps & Hose Clips



13.04 Pipe Clips & Fixing Systems

1545-1551

- Metric Pipe Clips & Back Plates
- BSP Pipe Clips & Back Plates
- Pipe Saddle Clips
- Pipe Fixings
- Pipe Clips & Fixing Systems



13.05 Banding Systems & Cable Ties

1552-1555

- Quick Release Band Straps & Banding
- Banding System & Tie Wraps
- Steel Strapping & Accessories



13.06 Ferrules & Pipe Repair Couplings

1556-1558

- Ferrules
- Pipe Repair Couplings
- Circlips Kits
- Tool Clips, Pen & Tool Holders
- Hose Crimper



Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

WORM DRIVE HOSE CLAMPS & U BOLTS

Hi-grip Mini Clamps

For fuel pipes and small hoses.

stainless steel



Mild Steel

5559	Min Size mm	Max Size mm
505-9	7	9
505-10	8	10
505-11	9	11
505-12	10	12
505-13	11	13
505-14	12	14
505-15	13	15
505-16	14	16
505-17	15	17
505-18	16	18
Tech Sheet 20459		

Stainless Steel

5559	Min Size mm	Max Size mm
505-9SS	7	9
505-10SS	8	10
505-11SS	9	11
505-12SS	10	12
505-13SS	11	13
505-14SS	12	14
505-15SS	13	15
505-16SS	14	16
505-17SS	15	17
505-18SS	16	18
Tech Sheet 20459		

All Stainless Steel Worm Drive Hose Clamps

stainless steel

304 stainless steel.




All Stainless Steel Worm Drive Hose Clamps

5555	Band Width	Min Size mm	Max Size mm
HCS12	9	8	12
HCS16	9	10	16
HCS20	9	12	20
HCS25	9	16	25
HCS32	9	20	32
HCS40	9	25	40
HCS50	9	32	50
HCS60	9	40	60
HCS70	9	50	70
Tech Sheet 20402			

Hose Clamps

Material: Band and Housing: AISI 430 stainless steel.
Screw: V6 free plated carbon steel.

Dimensions:	9mm Band Width	12mm Band Width
Band Width **(W)**:	9mm	12mm
Band Thickness **(T)**:	0.6mm	0.7mm
Housing Width **(B)**:	12mm	15mm
Housing Height **(H)**:	11mm	11mm
Width across flats **(SW)**:	7mm	7mm





9mm Band Width

5555	Min Size mm	Max Size mm	Size Ref
HC8-12	8	12	000
HC10-16	10	16	M00
HC12-20	12	20	00
HC16-25	16	25	0X
HC20-32	20	32	1A
HC25-40	25	40	1
HC32-50	32	50	2A
HC35-45	35	45	-
HC40-60	40	60	2
Tech Sheet 20401			

12mm Band Width

5555	Min Size mm	Max Size mm	Size Ref
HC50-70	50	70	3
HC60-80	60	80	3X
HC70-90	70	90	4
HC80-100	80	100	4X
HC90-110	90	110	-
HC100-120	100	120	5
HC110-130	110	130	-
HC120-140	120	140	6 and 6X
HC130-150	130	150	-
HC140-160	140	160	7
Tech Sheet 20401			

Tri-torque Heavy-duty Clamps, 16mm Band

stainless steel



Stainless Steel

5559	Min Size mm	Max Size mm
T850-175	25	44
T850-200	32	54
T850-250	44	67
T850-300	57	80
T850-350	70	92
T850-400	83	105
T850-500	108	130
T850-550	121	143
T850-600	133	156
T850-650	146	168
T850-800	184	206
T850-850	197	219
Tech Sheet 20462		

Quick Release Hose Clamps, 12.7mm Band

stainless steel



Stainless Steel

5559	Min Size mm	Max Size mm
G76028	25	57
G76048	38	89
G76056	25	101
G76072	51	127
G76088	52	152
G76104	45	177
G76128	45	217
G76152	50	254
G76188	52	312
G76216	258	355
G76248	45	406
G76280	361	457
G76344	45	559
Tech Sheet 20460		

WORM DRIVE HOSE CLAMPS & U BOLTS

Spiral Wrap Hose Clamps

Designed for spiral ducting hose, this clamp is unique to the market. It always has two points of contact, making it an ideal clamp for this style of hose.



Right Hand (Clockwise) Wound

5559	ID mm
SWCRT-2	50
SWCRT-3	75
SWCRT-4	100
SWCRT-5	125
SWCRT-6	150
Tech Sheet 67958	

Left Hand (Anticlockwise) Wound

5559	ID mm
SWCLT-2	50
SWCLT-3	75
SWCLT-4	100
SWCLT-5	125
SWCLT-6	150
Tech Sheet 67958	

Spiral Clamps



Right Hand (Clockwise) Wound

5555	ID
SCR-112	1.1/2"
SCR-2	2"
SCR-212	2.1/2"
SCR-3	3"
SCR-4	4"
SCR-5	5"
SCR-6	6"
SCR-12	12"

Left Hand (Anticlockwise) Wound

5555	ID
SCL-212	2.1/2"
SCL-3	3"
SCL-5	5"
SCL-8	8"

U Bolt Clamps



Complete with Saddle, Mild Steel

5559	To Suit Tube OD mm
U780280	28
U780320	32
U780350	35
U780380	38
U780410	41
U780430	43
U780450	45
U780480	48
U780510	51
U780540	54
U780580	58
U780600	60
U780640	64
U780670	67
U780700	70
U780750	75
U780770	77
U780790	79
U780800	80
U780890	89
U780920	92
U780950	95
U781000	100
U781020	102
U781100	110
U781200	120
U781250	125
Tech Sheet 20463	

Easy Grip Hose Clamp



Steel, 9mm Band Width

5555	Min Size mm	Max Size mm
EGHC8-12	8	12
EGHC10-16	10	16
EGHC12-20	12	20
EGHC16-25	16	25
EGHC20-32	20	32
EGHC25-40	25	40
EGHC32-50	32	50
EGHC35-45	35	45
EGHC40-60	40	60
EGHC50-70	50	70
EGHC60-80	60	80
EGHC70-90	70	90
EGHC80-100	80	100
Tech Sheet 20410		

FT PRO

For **Braided PVC Hose** see page **1403**



Fluid-Air Components Ltd

PIPE CLAMPS

Heavy-duty Steel Hose Clamps



Zinc Yellow Plated

5555	Min Size mm	Max Size mm
HDSHS-1719	17	19
HDSHS-2022	20	22
HDSHS-2325	23	25
HDSHS-2628	26	28
HDSHS-2931	29	31
HDSHS-3235	32	35
HDSHS-3639	36	39
HDSHS-4043	40	43
HDSHS-4447	44	47
HDSHS-4851	48	51
HDSHS-5255	52	55
HDSHS-5659	56	59
HDSHS-6063	60	63
HDSHS-6467	64	67
HDSHS-6873	68	73
HDSHS-7479	74	79
HDSHS-8085	80	85
HDSHS-8691	86	91
HDSHS-9297	92	97
HDSHS-98103	98	103
HDSHS-104112	104	112
HDSHS-113121	113	121
HDSHS-122130	122	130
HDSHS-131139	131	139
HDSHS-140148	140	148
HDSHS-149161	149	161
HDSHS-162174	162	174
HDSHS-175187	175	187
HDSHS-188200	188	200
HDSHS-201213	201	213
HDSHS-214226	214	226
HDSHS-227239	227	239
HDSHS-240252	240	252

Tech Sheet 20403

Stainless Steel Superior Clamps



Grade 304 Stainless Steel Band, Housing & Screw

5555	Min Size mm	Max Size mm
SHC17-19	17	19
SHC20-22	20	22
SHC23-25	23	25
SHC26-28	26	28
SHC29-31	29	31
SHC32-35	32	35
SHC36-39	36	39
SHC40-43	40	43
SHC44-47	44	47
SHC48-51	48	51
SHC52-55	52	55
SHC56-59	56	59
SHC60-63	60	63
SHC64-67	64	67
SHC68-73	68	73
SHC74-79	74	79
SHC80-85	80	85
SHC86-91	86	91
SHC92-97	92	97
SHC98-103	98	103
SHC104-112	104	112
SHC113-121	113	121
SHC122-130	122	130
SHC131-139	131	139
SHC140-148	140	148
SHC149-161	149	161
SHC162-174	162	174
SHC175-187	175	187
SHC188-200	188	200
SHC201-213	201	213
SHC214-226	214	226
SHC227-239	227	239
SHC240-252	240	252

Tech Sheet 20405

Constant Tension Clamps



304 Stainless Steel, 15.8mm Band Width

5555	Min Size mm	Max Size mm
CTC25-45	25	45
CTC32-54	32	54
CTC45-67	45	67
CTC57-79	57	79
CTC70-92	70	92
CTC83-105	83	105
CTC95-117	95	117
CTC108-130	108	130
CTC121-143	121	143
CTC133-155	133	155
CTC146-168	146	168
CTC184-206	184	206

Tech Sheet 20409

For **Black Nylon Ply Steam Hose**
see page **1482**



Fluid-Air Components Ltd

CLAMPS & CLIPS KITS

Assorted Kits

Contents:

Size	Quantity
8-12mm	14
10-16mm	10
12-22mm	10
16-27mm	8
20-32mm	7
25-40mm	6





Hose Clamps

5559	Material
HC-KIT-MS	Mild Steel
HC-KIT-SS	Stainless Steel
Tech Sheet 20468	

Contents:

Size	Quantity
7-9mm	21
8-10mm	20
9-11mm	15
10-12mm	15
11-13mm	14
12-14mm	8
13-15mm	10
15-17mm	7
16-18mm	6





Mini Hose Clamps

5559	Material
HCMINI-KIT-MS	Mild Steel
HCMINI-KIT-SS	Stainless Steel
Tech Sheet 20468	

Screwdriver



5555
HC1

FT PRO



For **Heavy-duty Tube Cutter** see page **905**

Fluid-Air Components Ltd

CLAMPS & HOSE CLIPS

INDUSTRY RECOMMENDED SYMBOLS

Agricultural · Food · Ventilation · Electrical · Oil/Gas
Industrial · Marine · Hardware/DIY · Automotive

Jubilee® Hose Clips

- Precision engineered for quality, Jubilee clips are Kitemark approved to BS 5315:1991 and manufactured under the BS EN ISO 9002 quality system accepted by the British Standards Institution
- The mild steel range is zinc plated for corrosion resistance and the stainless steel range is all 304 (A2) material



stainless steel

Mild Steel, Zinc Plated

6666	Size No	Min Size mm	Max Size mm
000-MS	000	9.5	12
M00-MS	M00	11	16
00-MS	00	13	20
0-MS	0	16	22
0X-MS	0X	18	25
1A-MS	1A	22	30
1-MS	1	25	35
1X-MS	1X	30	40
1M-MS	1M	32	45
2A-MS	2A	35	50
2-MS	2	40	55
2X-MS	2X	45	60
3-MS	3	55	70
3X-MS	3X	60	80
4-MS	4	70	90
4X-MS	4X	85	100
5-MS	5	90	120
6-MS	6	110	140
6X-MS	6X	120	150
7-MS	7	135	165
71/2-MS	7.1/2	158	190
81/2-MS	8.1/2	184	216
91/2-MS	9.1/2	210	242
101/2-MS	10.1/2	235	267
111/2-MS	11.1/2	260	292
121/2-MS	12.1/2	286	318
Tech Sheet 591			

304 Stainless Steel

6666	Size No	Min Size mm	Max Size mm
000-SS	000	9.5	12
M00-SS	M00	11	16
00-SS	00	13	20
0-SS	0	16	22
0X-SS	0X	18	25
1A-SS	1A	22	30
1-SS	1	25	35
1X-SS	1X	30	40
1M-SS	1M	32	45
2A-SS	2A	35	50
2-SS	2	40	55
2X-SS	2X	45	60
3-SS	3	55	70
3X-SS	3X	60	80
4-SS	4	70	90
4X-SS	4X	85	100
5-SS	5	90	120
6-SS	6	110	140
6X-SS	6X	120	150
7-SS	7	135	165
71/2-SS	7.1/2	158	190
81/2-SS	8.1/2	184	216
91/2-SS	9.1/2	210	242
101/2-SS	10.1/2	235	267
111/2-SS	11.1/2	260	292
121/2-SS	12.1/2	286	318
Tech Sheet 591			

Boxed Mild Steel, 10 Clips per Box

6666	Size No	Min Size mm	Max Size mm
000-MS-BOX	000	9.5	12
M00-MS-BOX	M00	11	16
00-MS-BOX	00	13	20
0-MS-BOX	0	16	22
0X-MS-BOX	0X	18	25
1A-MS-BOX	1A	22	30
1-MS-BOX	1	25	35
1X-MS-BOX	1X	30	40
1M-MS-BOX	1M	32	45
2A-MS-BOX	2A	35	50
2-MS-BOX	2	40	55
2X-MS-BOX	2X	45	60
3-MS-BOX	3	55	70
Tech Sheet 591			

Jubilee® Clipdrivers



6666	Length mm
2025-3753	95
Tech Sheet 1940	

CLAMPS & HOSE CLIPS

Jubilee® Light Range Clips

With a narrower band than the original Jubilee® clip, this lightweight clip is designed to offer an excellent seal at slightly lower torques.

The Jubilee® Light Range is manufactured to DIN 3017 and, like the original Jubilee® clip, they are continuously threaded to enable extra flexibility when adjusting to the required size.

This clip is most suited to applications where space or weight is restricted and is often used in car and light commercial vehicle applications.



Mild Steel, Zinc Plated, W1

6666	Min Size mm	Max Size mm
LR022MS	12	22
LR032MS	22	32
LR040MS	25	40
LR050MS	32	50
LR060MS	40	60
LR070MS	50	70
LR080MS	60	80
LR090MS	70	90
LR100MS	80	100
LR110MS	90	110
LR120MS	100	120
LR130MS	110	130
LR140MS	120	140
LR150MS	130	150
LR160MS	140	160

Tech Sheet 60246

stainless steel



304 Stainless Steel, W4


6666	Min Size mm	Max Size mm
LR022SS	12	22
LR032SS	22	32
LR040SS	25	40
LR045SS	30	45
LR050SS	32	50
LR060SS	40	60
LR070SS	50	70
LR080SS	60	80
LR090SS	70	90
LR100SS	80	100
LR110SS	90	110
LR120SS	100	120
LR140SS	120	140
LR150SS	130	150
LR160SS	140	160

Tech Sheet 60246

Jubilee® Stainless Steel High Torque Hose Clips

Jubilee® high torque clips for applications that require additional high levels of tightening torque; twice the tightening torque of standard worm drive clips.

- Recommended tightening torque: 17Nm (150in-lb)
- All stainless steel construction



stainless steel

Jubilee® 304 Stainless Steel, High Torque Hose Clips

6666	Min Size mm	Max Size mm
JHT35	20	35
JHT40	25	40
JHT45	25	45
JHT50	30	50
JHT70	40	70
JHT80	60	80
JHT95	70	95
JHT100	80	100
JHT120	90	120
JHT140	110	140
JHT160	130	160
JHT180	150	180
JHT200	170	200
JHT220	190	220
JHT240	210	240
JHT260	230	260
JHT280	250	280
JHT300	270	300
JHT320	290	320
JHT340	310	340
JHT360	330	360
JHT380	350	380
JHT400	370	400
JHT420	390	420
JHT440	410	440
JHT480	450	480
JHT500	470	500

Tech Sheet 1941

Jubilee® Stainless Steel High Torque Hose Clips

Jubilee® High Torque clips are made of all 304 or 316 stainless steel, with a two-part housing and cut-through and keeping the band straight at the point of engagement and fully engaging the screw thread, giving a superior tightening torque.

Although not suitable for use on soft hoses, where the high forces and the perforated band may cut into the hose; they are ideal where a high clamping force is required, and with a flexible band material, they can achieve a high level of friction even against smooth surfaces.



Jubilee® 316 Stainless Steel, High Torque Hose Clips

6666	Min Size mm	Max Size mm
HT035SS316	20	35
HT040SS316	25	40
HT045SS316	25	45
HT050SS316	30	50
HT055SS316	35	55
HT060SS316	40	60
HT065SS316	45	65
HT070SS316	40	70
HT080SS316	60	80
HT095SS316	70	95
HT100SS316	80	100
HT120SS316	90	120
HT140SS316	110	140
HT160SS316	130	160
HT180SS316	150	180
HT200SS316	170	200
HT220SS316	190	220
HT240SS316	210	240
HT260SS316	230	260
HT280SS316	250	280
HT300SS316	270	300
HT320SS316	290	320
HT340SS316	310	340
HT360SS316	330	360
HT380SS316	350	380
HT400SS316	370	400
HT420SS316	390	420
HT440SS316	410	440
HT460SS316	430	460
HT480SS316	450	480
HT500SS316	470	500
HT520SS316	490	520

Fluid-Air Components Ltd

CLAMPS & HOSE CLIPS

Jubilee® Flexiband

Tool used to apply Jubilee® Flexiband bands and buckles.



Flexiband Tool

6666
FBT
Tech Sheet 68252

304 stainless steel banding and buckles, used for applications such as sign fixing where the tamper-proof nature of the product is of paramount importance.

stainless steel



Flexiband Banding, 304 Stainless Steel, 30 Metre Lengths

6666	Band Width mm	Band Thickness mm
FB09B	9	0.65
FB13B	13	0.75
FB16B	16	0.75
FB19B	19	0.75
Tech Sheet 68252		

stainless steel



Flexiband Buckles, 304 Stainless Steel, Pack of 25

6666	Band Width mm
FB13H	13
FB19H	19
Tech Sheet 68252	

Jubilee® Juniors Nut & Bolt Clips

To suit petrol pipe, heaters and small bore hoses.



Mild Steel, Zinc Plated

6666	Min Size mm	Max Size mm
NB0709	7	9
NB0810	8	10
NB0911	9	11
NB1012	10	12
NB1113	11	13
NB1214	12	14
NB1315	13	15
NB1416	14	16
NB1517	15	17
NB1618	16	18
Tech Sheet 10310		

Jubilee® Handy Packs

The most popular sizes of premium brand Jubliee® hose clips, individually boxed and handily packed in their own outer display carton.

Pack consists of ten of each size: 000, M00, 00, 0, 0X,1A,1, 1X, 1M and 2A.



Mild Steel, Zinc Plated

6666
HP100MS
Tech Sheet 10584



stainless steel

304 Stainless Steel

6666
HP100SS

Jubilee® Pocket Packs

Never again be caught out without that essential Jubilee® clip to complete the job. The compact container holds a useful selection of clips for all those necessary hose jointing applications as well as holding nuts and bolt clips for joining small bore hoses and petrol pipes.

Pack consists of four each of 00, 0, 0X, NB0709 and NB1113, and two of each of 1 and 1X.



Mild Steel, Zinc Plated

6666
PPAUTO

Working Temperature: -50°C to +150°C

See data sheet for pack contents



Pocket Pack, 32 Pieces

6666	Material
PP-MS	Mild Steel
PP-SS	304 Stainless Steel
Tech Sheet 60241	

DIN 3017

Fluid-Air Components Ltd

CLAMPS & HOSE CLIPS

Jubilee® Clip Dispensers

These essential dispensers are easily re-stockable and also carries the extremely useful Flexidriver tool for easy adjustment of Jubliee clips. This can be wall mounted or left free standing.

Contents:

Size	Quantity
000	10
M00	10
00	10
0	10
0X	10
1A	10
1	10
1X	10
1M	10
2A	10
Jubilee Flexidriver®	3



Mild Steel, Zinc Plated

6666

CD-100MS



stainless steel

304 Stainless Steel

6666

CD-100SS

Jubilee® Workshop Pack

- Assorted Jubilee mild steel clips in a plastic re-usable box

Contents:

Size	Quantity
000	24
M00	32
00	28
0	13
0X	14
1A	12
1	13
1X	7



Mild Steel

6666

HCP143

Tech Sheet 1938

stainless steel

304 Stainless Steel

6666

HCP143SS

Tech Sheet 1938

stainless steel

316 Stainless Steel

6666

HCP143SS316

Tech Sheet 1938

Jubilee® Junior Assortment Pack

- 165 Assorted nut and bolt clips (for use on small bore hoses) in a plastic re-usable box

Contents:

Size	Quantity
07-09mm	25
08-10mm	25
09-11mm	25
10-12mm	30
11-13mm	30
12-14mm	30



Mild Steel

6666

JA165

Tech Sheet 1938

stainless steel

304 Stainless Steel

6666

JA165SS

Tech Sheet 1938

Fluid-Air Components Ltd

CLAMPS & HOSE CLIPS

Jubilee® Superclamps

Jubilee® Superclamps are manufactured in mild steel zinc plated, all 304 stainless and all 316 stainless steel and the later are predominantly suitable for applications where high corrosion resistance is required. These powerful clamps are ideal for marine and offshore oil and gas applications, as well as the food and chemical industries.

These clamps can also be used in place of SAE J1508 type TB or T-Bolt style clamps.

Superclamps are particularly suitable for delivery and suction hoses requiring a very tight seal and agricultural applications, waste water extraction, mining, quarrying or in other sectors where a heavy-duty clamp is required.

- Single nut adjustment
- Smooth band protects hose
- Bridge piece ensures 360° seal
- Solid trunion maximises torque
- Assembly by manual or automatic tools
- Chromium VI free finish on all materials



Mild Steel, Zinc Plated

6666	Min Size mm	Max Size mm
JSC19	17	19
JSC22	20	22
JSC25	23	25
JSC28	26	28
JSC31	29	31
JSC35	32	35
JSC39	36	39
JSC43	40	43
JSC47	44	47
JSC51	48	51
JSC55	52	55
JSC59	56	59
JSC63	60	63
JSC67	64	67
JSC73	68	73
JSC79	74	79
JSC85	80	85
JSC91	86	91
JSC97	92	97
JSC103	98	103
JSC112	104	112
JSC121	113	121
JSC130	122	130
JSC139	131	139
JSC148	140	148
JSC161	149	161
JSC174	162	174
JSC187	175	187
JSC200	188	200
JSC226	214	226
JSC239	227	239
Tech Sheet 590		



stainless steel

304 Stainless Steel

6666	Min Size mm	Max Size mm
JSC19SS304	17	19
JSC22SS304	20	22
JSC25SS304	23	25
JSC28SS304	26	28
JSC31SS304	29	31
JSC35SS304	32	35
JSC39SS304	36	39
JSC43SS304	40	43
JSC47SS304	44	47
JSC51SS304	48	51
JSC55SS304	52	55
JSC59SS304	56	59
JSC63SS304	60	63
JSC67SS304	64	67
JSC73SS304	68	73
JSC79SS304	74	79
JSC85SS304	80	85
JSC91SS304	86	91
JSC97SS304	92	97
JSC103SS304	98	103
JSC112SS304	104	112
JSC121SS304	113	121
JSC130SS304	122	130
JSC139SS304	131	139
JSC148SS304	140	148
JSC161SS304	149	161
JSC174SS304	162	174
JSC187SS304	175	187
JSC200SS304	188	200
JSC213SS304	201	213
JSC226SS304	214	226
JSC239SS304	227	239
Tech Sheet 590		




stainless steel

316 Stainless Steel

6666	Min Size mm	Max Size mm
JSC19SS316	17	19
JSC22SS316	20	22
JSC25SS316	23	25
JSC28SS316	26	28
JSC31SS316	29	31
JSC35SS316	32	35
JSC39SS316	36	39
JSC43SS316	40	43
JSC47SS316	44	47
JSC51SS316	48	51
JSC55SS316	52	55
JSC59SS316	56	59
JSC63SS316	60	63
JSC67SS316	64	67
JSC73SS316	68	73
JSC79SS316	74	79
JSC85SS316	80	85
JSC91SS316	86	91
JSC97SS316	92	97
JSC103SS316	98	103
JSC112SS316	104	112
JSC121SS316	113	121
JSC130SS316	122	130
JSC139SS316	131	139
JSC148SS316	140	148
JSC161SS316	149	161
JSC174SS316	162	174
JSC187SS316	175	187
JSC213SS316	201	213
JSC226SS316	214	226
Tech Sheet 590		

JAYMAC Industrial Hose & Accessories

For **Suction Hose**
see page **1427**



DIN 3017

SAE INTERNATIONAL

MIKALOR

UK MARKET LEADERS


ASFA HIGH TORQUE
16 mm bandwidth



No PERFORATIONS

Available in W3 / W4

Top PERFORMANCE



SUPRA
heavy duty clamp



LEADERS
IN
INNOVATION
AND
QUALITY

EAR CLIPS





FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HOSE CLIPS

MIKALOR

Mikalor Hose Clamps & Clips

Mikalor is a leading European manufacturer of hose clamps and clips based in Barcelona, Spain. Famous for the market-leading Supra clamp, Mikalor manufactures an extensive range of DIN 3017 clamps which are IATF 16949 approved for automotive use, DIN 3016 P-clips as well as a growing range of constant tension clamps, spring clips, O-clips etc.

Mikalor was the first company to design and produce heavy-duty hose clamp, and since then the **Super clamp** has gone from strength to strength.

The high strength 8.8 grade steel nut and T-bolt mean that Super can be tightened up hard using many different kinds of tools, while the bevelled edges protect the hose from harm.



The Super clamp is in its element in agricultural applications, waste water extraction, mining, quarrying or in other sectors where a rugged yet competitively priced heavy-duty clamp is required.

Material:

Band and bridge: Stainless Steel X6Cr17 AISI-430

Screw: Qst 34-3 Steel (DIN 1.0213) 8.8 Grade Steel

Finish: Stainless Steel

Super Heavy-duty Clamp

5556	Min Size mm	Max Size mm
SBC1719	17	19
SBC2022	20	22
SBC2325	23	25
SBC2628	26	28
SBC2931	29	31
SBC3235	32	35
SBC3639	36	39
SBC4043	40	43
SBC4447	44	47
SBC4851	48	51
SBC5255	52	55
SBC5659	56	59
SBC6063	60	63
SBC6467	64	67
SBC6873	68	73
SBC7479	74	79
SBC8085	80	85
SBC8691	86	91
SBC9297	92	97
SBC98103	98	103
SBC104112	104	112
SBC113121	113	121
SBC122130	122	130
SBC131139	131	139
SBC140148	140	148
SBC149161	149	161
SBC162174	162	174
SBC175187	175	187
SBC188200	188	200
SBC201213	201	213
SBC214226	214	226
SBC227239	227	239
SBC240252	240	252
Tech Sheet 1739		

Due to its revolutionary swivelling bridge, the **Supra Clamp** can be mounted in the most awkward applications without having to remove the hose. It can be opened and fastened again when in place without dislodging any other parts of the clamp, making assembly much easier.

The high-strength bolt, designed and manufactured by **Mikalor** specifically for this clamp, together with the captive nut and spacer system allow you to clamp the most demanding of hose assemblies. This is the clamp of choice for professionals in the industrial hose, automotive and agricultural machinery sectors as well as in all industrial applications where an outstanding and above all reliable heavy-duty clamp is required.



Material:

Band and bridge: Stainless Steel X6Cr17 AISI-430

Screw: Qst 34-3 Steel (DIN 1.0213) 8.8 Grade Steel

Finish: Stainless Steel

Supra Heavy-duty Clamp W2

5556	Min Size mm	Max Size mm
MS1901	17	19
MS1902	19	21
MS1903	21	23
MS1904	23	25
MS1905	25	27
MS1906	27	29
MS1907	29	31
MS1908	31	34
MS1909	34	37
MS1910	37	40
MS1911	40	43
MS1912	43	47
MS1913	47	51
MS1914	51	55
MS1915	55	59
MS1916	59	63
MS1917	63	68
MS1918	68	73
MS1919	73	79
MS1920	79	85
MS1921	85	91
MS1922	91	97
MS1923	97	104
MS1924	104	112

5556	Min Size mm	Max Size mm
MS1925	112	121
MS1926	121	130
MS1927	130	140
MS1928	140	150
MS1929	150	162
MS1930	162	174
MS1931	174	187
MS1932	187	200
MS1933	200	213
MS1934	213	226
MS1935	226	239
MS1936	239	252
MS1937	252	265
MS1938	265	278
MS1939	278	291
MS1940	291	304
MS1941	304	317
MS1942	317	330
MS1943	330	343
MS1944	343	356
MS1945	356	369
MS1946	369	382
MS1947	382	395
MS1948	395	408
Tech Sheet 1740		

Available in the following material qualities:

W2	W4	W5
AISI 430 STAINLESS STEEL	**AISI 304** STAINLESS STEEL	**AISI 316** STAINLESS STEEL

HOSE CLAMPS

MIKALOR

This top of the range heavy-duty clamp is ideal for marine applications, foodstuff manufacture, pharmaceutical and petrochemical industries and other applications where AISI 316 stainless steel fittings are required

Supra Heavy-duty Clamp W4

Material:
Band and bridge: Stainless Steel X5CrNI 18010 AISI-304
Screw: AISI-304 Stainless Steel
Finish: Stainless Steel

stainless steel



5556	Min Size mm	Max Size mm
SS1301	17	19
SS1302	19	21
SS1303	21	23
SS1304	23	25
SS1305	25	27
SS1306	27	29
SS1307	29	31
SS1308	31	34
SS1309	34	37
SS1310	37	40
SS1311	40	43
SS1312	43	47
SS1313	47	51
SS1314	51	55
SS1315	55	59
SS1316	59	63
SS1317	63	68
SS1318	68	73
SS1319	73	79
SS1320	79	85
SS1321	85	91
SS1322	91	97
SS1323	97	104
SS1324	104	112

5556	Min Size mm	Max Size mm
SS1325	112	121
SS1326	121	130
SS1327	130	140
SS1328	140	150
SS1329	150	162
SS1330	162	174
SS1331	174	187
SS1332	187	200
SS1333	200	213
SS1334	213	226
SS1335	226	239
SS1336	239	252
SS1337	252	265
SS1338	265	278
SS1339	278	291
SS1340	291	304
SS1341	304	317
SS1342	317	330
SS1343	330	343
SS1344	343	356
SS1345	356	369
SS1346	369	382
SS1347	382	395
SS1348	395	408

Tech Sheet 1741

Supra Heavy-duty Clamp W5

Material:
Band and bridge:
Stainless Steel X5CrNI
MO 1712 AISI-316
Screw:
Stainless Steel
AISI-316 Cu
Finish: Stainless Steel



5556	Min Size mm	Max Size mm
03013614	17	19
03013622	19	21
03013630	21	23
03013649	23	25
03013657	25	27
03013665	27	29
03013673	29	31
03013681	31	34
03013690	34	37
03013702	37	40
03013710	40	43
03013729	43	47
03013737	47	51
03013745	47	51
03013753	55	59
03013761	59	63
03013770	63	68
03013788	68	73
03013796	73	79
03013809	79	85
03013817	85	91
03013825	91	97
03013833	97	104
03013841	104	112
03013850	112	121
03013868	121	130
03013876	130	140
03013884	140	150
03013892	150	162
03013905	162	174
03013913	174	187
03013921	187	200
03013930	200	213
03013948	213	226
03013956	226	239
03013964	239	252
03013971	252	265
03013981	265	278
03013982	278	291
03013983	291	304
03013984	304	317
03013985	317	330
03013986	330	343
03013991	343	356
03013992	356	369
03013993	369	382
03013994	382	395
03013995	395	408

FT PRO®

For **Automotive Tubing**
see page **910**



Available in the following material qualities:

W2 **AISI 430** STAINLESS STEEL
W4 **AISI 304** STAINLESS STEEL
W5 **AISI 316** STAINLESS STEEL

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HOSE CLIPS

MIKALOR

Supra Constant Tension Heavy-duty Clamp



The hose clamp that adapts itself to variations of pressure and temperature.



The Supra CT clamp incorporates a bespoke bolt and a series of conical washers to the already outstanding Supra clamp. This specialized version of the Supra clamp is used in applications subject to vibration and/or great variations in temperature which can cause the spring washer system, the Supra CT maintains constant pressure around the hose despite variations in temperature or vibration.

This clamp is generally fitted in combustion engines in construction machinery, trucks, tractors, buses, marine engines, military vehicles and diesel-powered generators. The bevelled edges protect the hose from damage.

Supra CT

Material:

Band and bridge:
Stainless Steel X8Cr17 AISI-430

Screw: 8.8 Grade Steel

Washers and Trunnions:
Stainless Steel AISI-304

Finish: Stainless Steel

Supra Constant Tension Heavy-duty Clamp W2

5556	Min Size mm	Max Size mm
CT0302021-4	43	47
CT0302023-0	51	55
CT0302025-7	59	63
CT0302029-0	79	85
CT0302030-2	85	91
CT0302031-0	91	97
CT0302034-5	112	121
Tech Sheet 1742		

Other sizes available on request

Available in the following material qualities:

W2 — **AISI 430** STAINLESS STEEL

W4 — **AISI 304** STAINLESS STEEL

W5 — **AISI 316** STAINLESS STEEL

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

HOSE CLIPS

MIKALOR new product

Supra 2-Bolt Range

The **SUPRA 2-bolt** heavy-duty clamp is an ideal solution for applications where increased performance and improved distribution of radial forces around the circumference of the band are required.

To ensure maximum clamping force, our bolts are manufactured in-house by **Mikalor** with an exclusively designed the outer hexagonal head, which guarantees the highest clamping force on the market.

The bevelled band edges avoid damage to the hose, making Supra safe and reliable to use.

This 2-bolt version of the Supra clamp is recommended for applications with an outer diameter (OD) over 270mm for use in sectors such as oil and gas, marine, agriculture, foodstuffs, hydraulics and chemicals, amongst others.



2 Bolt Supra Heavy-duty Hose Clamps W2

5556	Min Size mm	Max Size mm
03170001	270	280
03170003	280	290
03170005	285	295
03170007	315	325
03170009	345	355
03170011	370	385
03170013	395	410
03170015	420	435
03170017	445	460
03170019	470	485
03170021	495	510
03170023	520	535
03170025	545	560
03170027	570	585
03170029	595	610
03170031	620	635
03170033	650	665
03170035	680	695
03170037	715	730
03170039	740	755
03170041	765	780
03170043	790	805
03170045	820	835

Tech Sheet 17125

Supra, W4



2 Bolt Supra Heavy-duty Hose Clamps W4

5556	Min Size mm	Max Size mm
03180001	270	280
03180003	280	290
03180005	285	295
03180007	315	325
03180009	345	355
03180011	370	385
03180013	395	410
03180015	420	435
03180017	445	460
03180019	470	485
03180021	495	510
03180023	520	535
03180025	545	560
03180027	570	585
03180029	595	610
03180031	620	635
03180033	650	665
03180035	680	695
03180037	715	730
03180039	740	755
03180041	765	780
03180043	790	805
03180045	820	835

Supra, W5




2 Bolt Supra Heavy-duty Hose Clamps W5

5556	Min Size mm	Max Size mm
03190001	270	280
03190003	280	290
03190005	285	295
03190007	315	325
03190009	345	355
03190011	370	385
03190013	395	410
03190015	420	435
03190017	445	460
03190019	470	485
03190021	495	510
03190023	520	535
03190025	545	560
03190027	570	585
03190029	595	610
03190031	620	635
03190033	650	665
03190035	680	695
03190037	715	730
03190039	740	755
03190041	765	780
03190043	790	805
03190045	820	835

Available in the following material qualities:

W2	W4	W5
AISI 430 STAINLESS STEEL	**AISI 304** STAINLESS STEEL	**AISI 316** STAINLESS STEEL

FT PRO



For **Heavy-duty Agricultural Water Hose** see page **1422**

FAC Fluid-Air Components Ltd

HOSE CLIPS

The Mikalor ASFA Worm-drive Clip Range

The **Mikalor DIN 3017 ASFA worm-drive clip range** is manufactured in material qualities ranging from W1 (zinc-plated mild steel) up to W5 (AISI 316 stainless steel) and in band widths ranging from 7mm up to 16mm. The range includes ASFA-CT constant tension clips with a spring insert and a also a black version with a Delta-Seal surface treatment. For extreme applications ASFA is also available in titanium with a PTFE surface treatment. The entire ASFA range is manufactured according to IATF 16949 and is fully compliant with the requirements of the automotive sector.

ASFA LW2 Worm-drive Clip

Material:
Band and Housing: Stainless Steel (AISI 430)
Screw: Steel Qst 36-3 (DIN 1.0214)
Finish:
Band and Housing: Stainless Steel
Screw: Grey-White Cr3 Zinc-Plated



430 Stainless Steel, 9mm Band Width

5556	Min Size mm	Max Size mm
0301650-8	8	12
0301651-6	8	16
0301652-4	12	22
0301653-2	16	27
0301654-0	20	32
0301655-9	25	40
0301656-7	30	45
0301657-5	32	50
0301658-3	40	60
0301659-1	50	70
0301660-4	60	80
0301661-2	70	90
0301662-0	80	100
0301663-9	90	110
0301667-1	130	150
0301668-0	140	160
Tech Sheet 68770		

ASFA LW4 Worm-drive Clip

Material:
Band and Housing: Stainless Steel X5Cr Ni1810 (AISI 304)
Screw: Stainless Steel (AISI 304)
Finish: Stainless Steel

stainless steel



Stainless Steel, 9mm Band Width

5556	Min Size mm	Max Size mm
0301401-9	8	16
0301402-7	12	22
0301403-5	16	27
0301404-3	20	32
0301405-1	25	40
0301406-0	30	45
0301407-8	32	50
0301408-6	40	60
0301409-4	50	70
0301410-7	60	80
0301411-5	70	90
0301412-3	80	100
0301414-0	90	110
0301415-8	100	120
0301416-6	110	130
0301417-4	120	140
0301418-2	130	150
0301419-0	140	160
Tech Sheet 68184		

ASFA W5 Worm-drive Clip

Material: Stainless Steel AISI 316
Finish: Stainless Steel

stainless steel



316 Stainless Steel, 9mm/12mm Band Width

5556	Min Size mm	Max Size mm
0301575-9	8	16
0301576-7	12	22
0301772-0	16	27
0301750-0	20	32
0301751-9	25	40
0301773-8	30	45
0301752-7	32	50
0301753-5	40	60
0301754-3	50	70
0301755-1	60	80
0301756-0	70	90
0301757-8	80	100
0301758-6	90	110
0301759-4	100	120
0301760-7	110	130
0301761-5	120	140
0301762-3	130	150
0301763-1	140	160
0301764-0	150	170
0301765-8	160	180
0301766-6	170	190
0301767-4	180	200
0301768-2	190	210
0301769-0	200	220
0301770-3	210	230
0301771-1	220	240
Tech Sheet 68185		

Available in W1, W2, W3, W4 and W5

Fluid-Air Components Ltd

HOSE CLIPS

MIKALOR

ASFA SW1 Worm-drive Clip

Material:
Band and housing: Galvanized Steel (DIN 1.0935)
Screw: Steel Qst 36-3 (DIN 1.0214)
Finish:
Band and housing: Galvanized Steel
Screw: Grey-White Cr3 Zinc-Plated



Galvanised Steel, 12mm Band Width

5556	Min Size mm	Max Size mm
0300900-1	16	27
0300900-2	20	32
0300900-3	25	40
0300900-4	30	45
0300900-5	32	50
0300900-6	40	60
0300900-7	50	70
0300900-8	60	80
0300900-9	70	90
0300901-0	80	100
0300901-1	90	110
0300901-2	100	120
0300901-3	110	130
0300901-4	120	140
0300901-5	130	150
0300901-6	140	160
0300901-7	150	170
0300901-8	160	180
0300901-9	170	190
0300902-0	180	200
0300902-1	190	210
0300902-3	210	230
0300902-4	220	240
Tech Sheet 68183		

ASFA SW4 Worm-drive Clip

Material:
Band and Housing: Stainless Steel X5Cr Ni1810 (AISI 304)
Screw: Stainless Steel (AISI 304)
Finish: Stainless Steel



304 Stainless Steel, 12mm Band Width

5556	Min Size mm	Max Size mm
0301473-0	16	27
0301451-0	20	32
0301452-9	25	40
0301474-8	30	45
0301453-7	32	50
0301454-5	40	60
0301455-3	50	70
0301456-1	60	80
0301457-0	70	90
0301458-8	80	100
0301459-6	90	110
0301460-9	100	120
0301461-7	110	130
0301462-5	120	140
0301463-3	130	150
0301464-1	140	160
0301465-0	150	170
0301466-8	160	180
0301467-6	170	190
0301468-4	180	200
0301469-2	190	210
0301471-3	210	230
0301472-1	220	240
Tech Sheet 68186		

ASFA LW3 Worm-drive Clip (Black Finish)

This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance. Thanks to the surface treatment, this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications.

Screw: AISI 430 stainless steel
Band and Housing: Stainless steel X6Cr-17 (DIN 1.4016) (AISI-430)
Finish: Black

stainless steel



430 Stainless Steel, 9mm Band Width

5556	Min Size mm	Max Size mm
73016011	8	16
73016020	12	22
73016038	16	27
73016046	20	32
73016062	25	40
73016070	30	45
73016089	32	50
73016095	40	60
73016100	50	70
73016118	60	80
Tech Sheet 20467		

FT PRO

For **Automotive Hose & Tube**
see page **1417**



Available in W1, W2, W3, W4 and W5

Fluid-Air Components Ltd

HOSE CLIPS

MIKALOR new product

ASFA SW3 Constant Tension Worm-drive Clips

12mm band width **Constant Tension worm-drive clips** are designed to be used primarily in the automotive sector. The main advantage of this clip over the standard Mikalor worm drive is to be found in the spring-loaded insert, fitted on a semi-circular support to the inside of the band.

The use of this spring-loaded insert guarantees constant pressure around the hose and the optimum performance of the clamp in case of variations in temperature, pressure or vibration. For this reason, constant tension worm-drive clips are used mainly with tubes or hoses carrying hot air or on engine refrigeration systems, as clamps used in these applications are subject to expansion and contraction due to frequent changes in temperature. ASFA CT worm-drive clips are manufactured entirely from stainless steel, thereby ensuring good corrosion resistance.

W3 S-Band Constant Tension Worm-drive Clips

Material: AISI-430 Stainless Steel
Spring-loaded insert: AISI-410 Stainless Steel
Finish: Stainless Steel

stainless steel



5556	Min Size mm	Max Size mm
03017800	16	27
03017818	20	32
03017834	30	45
03017842	32	50
03017850	40	60
03017869	50	70
03017877	60	80
03017885	70	90
03017893	80	100
03017906	90	110
03017914	100	120
03017922	110	130

Tech Sheet 20096

ASFA High-Torque (16 mm) Hose Clamp

Mikalor High-Torque Clamps were designed to guarantee maximum performance in the most demanding applications. Thanks to the use of an M8 screw and the choice of 16mm bandwidth, torque values can be applied which are far higher than those used with the standard ASFA range, thereby ensuring perfect performance in high-pressure applications.

The High-Torque clamp is particularly popular in industrial and automotive applications due to its outstanding performance. The perfectly rounded bevelled band edges avoid the clamp cutting into or damaging the hose.

Material:
Band and Housing: Stainless Steel X6Cr17 (AISI 430)
Screw: Stainless Steel (AISI 304 CU)
Finish: Stainless Steel



ASFA High-Torque W3 Worm-drive Hose Clip

5556	Min Size mm	Max Size mm
03066001	25	45
03066002	32	54
03066003	45	67
03066004	57	79
03066005	70	92
03066006	83	105
03066007	95	118
03066008	108	130
03066009	121	143
03066010	133	156
03066011	146	168
03066012	159	181
03066013	172	194
03066014	184	206
03066015	197	219
03066016	210	232

High Torque Worm-drive Clips



High Torque Worm-drive Hose Clip W4

5556	Min Size mm	Max Size mm
03067001	25	45
03067002	32	54
03067003	45	67
03067004	57	79
03067005	70	92
03067006	83	105
03067007	95	118
03067008	108	130
03067009	121	143
03067010	133	156
03067011	146	168
03067012	159	181
03067013	172	194
03067014	184	206
03067015	197	219
03067016	210	232

Worm-drive Accessories



Safety Collars

5556	Colour
02170371	Red
02170380	Blue



Safety Cap

5556	Size mm	Colour
02170401	9mm	Red
02170411	9mm	Blue
02170441	12mm	Red
02170451	12mm	Blue

Available in W1, W2, W3, W4 and W5

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

HOSE CLIPS

MIKALOR new product

Assortment Box

- Includes No.7 flexible screwdrive .

Contents (ASFA-L):

Size	Quantity
8-16mm	20
12-22mm	20
16-27mm	20
20-32mm	20
25-40mm	15
32-50mm	10
40-60mm	5

Contents (ASFA-S):

Size	Quantity
16-27mm	20
20-32mm	15
25-40mm	15
30-45mm	10
32-50mm	8
40-60mm	5



ASFA Worm-drive Assortment Boxes

5556	Description	Kit Quantity
03503201	ASFA-L W1	110
03503211	ASFA-L W2	110
03503221	ASFA-L W4	110
03503231	ASFA-S W1	73
03503241	ASFA-S W2	73
03503251	ASFA-S W4	73
03503261	ASFA-S W5	73

- Includes clamping pliers.

Contents:

Size	Quantity	Size	Quantity
5-7mm	50	15-18mm	50
7-9mm	50	17-20mm	30
9-11mm	50	20-23mm	25
11-13mm	50	22-25mm	20
13-15mm	50		



Ear Clips

5556	Description
03503116	Assortment 2-Ear Clip W1
03503124	Assortment 2-Ear Clip W4

Contents (W1):

Size	Quantity
6/15	12
8/15	10
10/15	10
12/15	8
14/15	6
15/15	6
16/15	6
20/15	4

Contents (W4):

Size	Quantity
6/15	12
8/15	10
10/15	10
12/15	8
14/15	8
15/15	6
16/15	6
18/15	4



P Clips

5556	Description
03503271	Assortment DIN 3016 P-Clip W1 (62 Pieces)
03503281	Assortment DIN 3016 P-Clip W4 (64 Pieces)

Available in W1 and W4

Tools



Pliers

5556	Description
03011096	Side-Closing Ear Clip Pliers
03011088	Front-Closing Ear Clip Pliers

The 7mm hex-socket flexidriver is ideal for tightening Mikalor ASFA Clamps.



7mm Hex-Socket Flexidriver

5556
03091036

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CLIP PACKS

Hi-Grip Mild Steel Assorted Pack

- Size ranging from 12mm up to 50mm



135 Assorted, Mild Steel Zinc Plated Clips

5557
HGZAB1

Hi-Grip Stainless Steel Assorted Pack

- Size ranging from 12mm up to 50mm

stainless steel



135 Assorted, 18/8 Marine, Quality BS304 Stainless Steel Clips

5557
HGSAB1

Zinc Plated Mini Clips Assorted Pack

- **Diameter Ranges:** 7mm-9mm, 8mm-10mm, 9mm-11mm, 10mm-12mm, 11mm-13mm, 12mm-14mm, 13mm-15mm, 14mm-16mm, 15mm-17mm, 16-18mm



157 Assorted, Zinc Plated Mini Clips

5557
MCZAB1

Flexible Driver

Purpose made for all HI-GRIP hose clips with stainless steel shaft and socket.



5557
DHG2BG

T-Bar Driver

Suitable for all HI-TORQUE fittings



5557
DHT3BG

COUNTER DISPENSERS

These new counter dispensers are an ideal point of sale unit for the Automotive, Food, Pharmaceutical and Industrial markets.

Hi-Grip, Zinc Plated

100 Clips sizes:
12mm - 50mm x 10
1 x Flexible Driver



100 Clip Dispenser

5557
DISPKZ1

160 Clips sizes:
12mm - 100mm x 10
1 x Flexible Driver



160 Clip Dispenser

5557
DISPKZ2

Hi-Grip, Stainless Steel

100 Clips sizes:
12mm - 50mm x 10
1 x Flexible Driver

stainless steel



100 Clip Dispenser

5557
DISPKS1

160 Clips sizes:
12mm - 100mm x 10
1 x Flexible Driver

stainless steel



160 Clip Dispenser

5557
DISPKS2

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

WORM DRIVE HOSE CLAMPS

Hi-Torque Heavy-duty

Material:
Band and Housing BS304, Screw Hardened to BS410.
Hi-Torque 18/8 Marine available upon request.

stainless steel



5557	Min Size mm	Max Size mm
HT27	20	27
HT30	20	30
HT35	20	35
HT40	25	40
HT45	25	45
HT50	30	50
HT60	40	60
HT65	45	65
HT70	50	70
HT80	60	80
HT90	70	90
HT95	75	95
HT100	80	100
HT120	90	120
HT140	110	140
HT160	130	160
HT180	150	180
HT200	170	200
HT220	190	220
HT240	210	240
HT260	230	260
HT280	250	280
HT320	290	320
HT340	310	340
HT360	330	360
HT380	350	380
HT400	370	400
HT420	390	420
HT440	410	440
HT460	430	460
HT480	450	480
HT500	470	500

Hi-Grip Worm-drive Hose Clip

Material:
Mild Steel, Zinc Plated.



Wing Screw to BS5315

5557	Min Size mm	Max Size mm
510-12	9.5	12
510-16	11	16
510-20	13	20
510-22	14	22
510-25	17	25
510-30	22	30
510-35	25	35
510-40	30	40
510-45	35	45
510-50	35	50
510-55	40	55
510-60	45	60
510-80	60	80

Hi-Grip WDHC



Hi-Grip Mild Steel

5557	Min Size mm	Max Size mm
WDHC000	9.5	12
WDHCM00	11	16
WDHC00	13	20
WDHC0	14	22
WDHC0X	17	25
WDHC1A	22	30
WDHC1	25	35
WDHC1X	30	40
WDHC45	35	45
WDHC2A	35	50
WDHC2	40	55
WDHC2X	45	60
WDHC3	50	70
WDHC3X	60	80
WDHC4	70	90
WDHC4X	80	100
WDHC5	90	120
WDHC6	110	140
WDHC7	130	160
WDHC8	150	180
WDHC200	170	200
WDHC220	190	220
WDHC240	210	240
WDHC260	230	260
WDHC280	250	280
WDHC300	270	300

stainless steel

Hi-Grip Stainless Steel

5557	Min Size mm	Max Size mm
WDHC000-SS	9.5	12
WDHCM00-SS	11	16
WDHC00-SS	13	20
WDHC0-SS	14	22
WDHC0X-SS	17	25
WDHC1A-SS	22	30
WDHC1-SS	25	35
WDHC1X-SS	30	40
WDHC45-SS	35	45
WDHC2A-SS	35	50
WDHC2-SS	40	55
WDHC2X-SS	45	60
WDHC3-SS	50	70
WDHC3X-SS	60	80
WDHC4-SS	70	90
WDHC4X-SS	80	100
WDHC5-SS	90	120
WDHC6-SS	110	140
WDHC7-SS	130	160
WDHC180-SS	150	180
WDHC200-SS	170	200
WDHC220-SS	190	220
WDHC240-SS	210	240
WDHC260-SS	230	260

FT PRO®



For **Hi-Vis Air & Water RPVC Hose** see page **1408**

CLAMPS & HOSE CLIPS

A World Leader in the design & supply of sealing, connecting & clamping solutions.

High performance products specified by the world's leading manufacturers for all their hose, tube and pipe applications.

- Specially designed for the perfect seal
- Quality Assured engineering and manufacture to ISO 9002, QS 9000 and ISO 14001.
- Over 3 million parts produced EVERY day allows us to give the customer exceptional value.

NORMA® Hose Clips

- Top Sealing Performance through its Unique Design



Mild Steel Alu-Zinc Plated

7777	Min Size mm	Max Size mm	Band Width mm
NOR-000	8	12	9
NOR-M00	10	16	9
NOR-00	12	22	9
NOR-0	16	27	12
NOR-1A	20	32	12
NOR-1	25	40	12
NOR-2A	35	50	12
NOR-2	40	60	12
NOR-2X	40	60	12
NOR-3	50	70	12
NOR-3X	60	80	12
NOR-4	70	90	12
NOR-4X	80	100	12
NOR-5	90	110	12

- Top Sealing Performance through its Unique Design

stainless steel



All Stainless Steel

7777	Min Size mm	Max Size mm	Band Width mm
NOR-SS-75-12	8	12	7.5
NOR-SS-75-16	10	16	7.5
NOR-SS-75-18	12	18	7.5
NOR-SS-000	8	16	9
NOR-SS-M00	8	16	9
NOR-SS-00	12	22	9
NOR-SS-0	16	27	12
NOR-SS-1A	20	32	12
NOR-SS-1	25	40	12
NOR-SS-1X	25	40	12
NOR-SS-2A	32	50	12
NOR-SS-2	40	60	12
NOR-SS-2X	40	60	12
NOR-SS-3	50	70	12
NOR-SS-3X	60	80	12
NOR-SS-4	70	90	12
NOR-SS-4X	80	100	12
NOR-SS-5	90	110	12

NORMA® High Torque Hose Clips

- Recommended Tightening Torque 17 Nm (150lb in)

stainless steel



All Stainless Steel, 16mm Band Width

7777	Min Size mm	Max Size mm
NOR-HD45	25	45
NOR-HD54	32	54
NOR-HD67	45	67
NOR-HD79	57	79
NOR-HD92	70	92
NOR-HD118	95	118
NOR-HD130	108	130
NOR-HD143	121	143
NOR-HD168	146	168
NOR-HD181	159	181
NOR-HD194	172	194

WRAS APPROVED PRODUCT



For **Polyethylene Pipe Insulation** see page **1215**

NORMA® Clamp GBS M Heavy-duty Clamp

- Up to 70% higher band tension than leading competitor
- Wide clamping range 17mm to 252mm
- Environmentally friendly - Chrome VI Free
- Mechanically locked so no spot weld weakness
- Rounded band edges for hose protection
- DIN 3017 Accredited



Clamps Supplied in W2 Material

7777	Min Size mm	Max Size mm
NOR-05917182018	17	19
NOR-05917182020	19	21
NOR-05917182022	21	23
NOR-05917182024	23	25
NOR-05917182026	25	27
NOR-05917182028	27	29
NOR-05917182030	29	31
NOR-05917182033	31	34
NOR-05917182036	34	37
NOR-05917182039	37	40
NOR-05917182042	40	43
NOR-05917202045	43	47
NOR-05917202049	47	51
NOR-05917202053	51	55
NOR-05917202057	55	59
NOR-05917202061	59	63
NOR-05917202066	63	68
NOR-05917252071	68	73
NOR-05917252076	73	79
NOR-05917252082	79	85
NOR-05917252088	85	91
NOR-05917252094	91	97
NOR-05917252101	97	104
NOR-05917252108	104	112
NOR-05917252117	112	121
NOR-05917252126	121	130
NOR-05917302135	130	140
NOR-05917302145	140	150
NOR-05917302156	150	162
NOR-05917302168	162	174
NOR-05917302181	174	187
NOR-05917302194	187	200
NOR-05917302207	200	213
NOR-05917302220	213	226
NOR-05917302233	226	239
NOR-05917302246	239	252

Fluid-Air Components Ltd

CLAMPS, CLIPS & FASTENERS

NORMA® Hose Clamps & Clips



Normaclamp Worm-drive Quick Lock W2B

7777	Clamp Range mm
8156120050	32-50
8156120060	40-60
8156120145	60-145
8156120170	60-170
8156120270	60-270
8156120325	60-325
8156120380	60-380
8156130135	60-135

NORMA® Quick Assembly 1 Piece Cobra Hose Clips

- Low Profile, Easy Fit Hose Clip

stainless steel



Stainless Steel

7777	To Suit Hose OD mm	Band Width mm
NOR-COBRA75	7.5	7
NOR-COBRA8	8	7
NOR-COBRA9	9	7
NOR-COBRA10	10	7
NOR-COBRA105	10.5	7
NOR-COBRA11	11	7
NOR-COBRA115	11.5	7
NOR-COBRA12	12	8
NOR-COBRA13	13	8
NOR-COBRA14	14	8
NOR-COBRA15	15	8
NOR-COBRA16	16	8
NOR-COBRA17	17	8
NOR-COBRA18	18	8
NOR-COBRA19	19	8
NOR-COBRA20	20	8
NOR-COBRA21	21	8
NOR-COBRA24	24	8
NOR-COBRA26	26	8
NOR-COBRA27	27	8
NOR-COBRA28	28	8
NOR-COBRA29	29	8

Cobra Clip Hand Tool



7777
1108420000

FT PRO®









For **Jointing Compounds & Sealants** see page **1391**

Fluid-Air Components Ltd

O CLIPS

O Clips





Mild Steel

5559	Nominal Size	Min Size mm	Max Size mm
NO5-7	1/4"	5	7
NO7-9	5/16"	7	9
NO9-11	7/16"	9	11
NO9-12	7/16"	9	12
NO11-13	1/2"	11	13
NO13-15	9/16"	13	15
NO14-17	19/32"	14	17
NO15-18	5/8"	15	18
NO17-20	3/4"	17	20
NO19-22	13/16"	19	21
NO20-23	7/8"	20	23
NO22-25	15/16"	22	25
NO23-27	1"	23	27
NO25-28	1.1/16"	25	28
NO28-31	1.3/16"	28	31
NO31-34	1.5/16"	31	34
NO34-37	1.7/16"	34	37
NO37-40	1.1/2"	37	40
NO40-43	1.5/8"	40	43

Tech Sheet 588

Assorted Kits

Contents:

Size	Quantity
9-11mm	34
11-13mm	26
13-15mm	18
14-17mm	14
15-18mm	24
17-20mm	20
18-21mm	20
22-25mm	12
Pincers	1





O Clips

5559	Material
OC-KIT-MS	Mild Steel

Tech Sheet 20468

Single Ear O Clips



Mild Steel

5559	Min Size mm	Max Size mm
2019-1080	7	9
2019-1084	8	10
2019-1093	11	13
2019-1094	12	14
2019-1096	14	16
2019-1098	16	18

Snap Clip, Acetal



0497	Min Size mm	Max Size mm
PC8-10	8	10
PC10-12	10	12
PC11-13	11	13
PC13-15	13	15
PC14-16	14	16
PC15-17	15	17
PC16-18	16	18
PC17-19	17	19
PC18-20	18	20
PC21-23	21	23
PC23-25	23	25
PC26-28	26	28
PC30-32	30	32

O Clip Pliers



5555
OP1



Clip Tools

6666	Function
P1099	Side Closing

Single Ear Hose Clamp

stainless steel



Stainless Steel, 5mm Band Width

5555	Min Size mm	Max Size mm
SEHC6.5	5	6.5
SEHC7	5.8	7
SEHC8	6.8	8
SEHC8.7	7	8.7
SEHC9.5	7.8	9.5
SEHC10.5	8.8	10.5

Tech Sheet 20411



Stainless Steel, 7mm Band Width

5555	Min Size mm	Max Size mm
SEHC11.3	9.6	11.3
SEHC11.9	10.2	11.9
SEHC12.3	10.6	12.3
SEHC13.3	10.8	13.3
SEHC14	11.5	14
SEHC14.5	12	14.5
SEHC15.3	12.8	15.3
SEHC16.2	13.7	16.2
SEHC17.5	15	17.5
SEHC18.5	15.3	18.5
SEHC19.2	16	19.2
SEHC22.6	19.4	22.6
SEHC23.5	20.4	23.6
SEHC24.1	20.9	24.1
SEHC27.1	23.9	27.1
SEHC32.1	28.9	32.1
SEHC34.6	31.4	34.6
SEHC41	37.8	41
SEHC42.5	39.3	42.5
SEHC44	40.8	44
SEHC51.5	48.3	51.5
SEHC63.5	60.3	63.5

Tech Sheet 20412

Fluid-Air Components Ltd

HOSE CLAMPS

MIKALOR

Mikalor O Clips

The use of one ear clips is an economical solution for many simple hose assemblies carrying air or fluids. They are ideal for use with simple hose assemblies which do not require high clamping force. The practical design of ear clips means that they are easy, fast and safe to mount. They are also tamper-proof once mounted. The edges are rounded to avoid damage to the hose.



Steel, Zinc Plated, 1 Ear

5556	Min Size mm	Max Size mm
03012072	8	10
03012013	9	11
03012021	10	12
03012030	11	12
03012048	12	14
03012056	14	16
03012064	16	18.5
Tech Sheet 1743		

Stainless Steel, 1 Ear

stainless steel

5556	Min Size mm	Max Size mm
23012440	7	9
23012087	8	10
23012010	9	11
23012028	10	12
23012036	11	13
23012044	12	14
23012079	12	15
23012052	14	16
23012458	15	17
23012060	16	18
23012423	17	19
23012431	18	20
Tech Sheet 1744		

The use of two ear clips is an economical solution for leaktight, simple hose assemblies on hoses transporting air, gas or other fluids

The two ears give the clip extra grip and help to maintain constant pressure around the hose. The edges are rounded to avoid damage to the hose and the assembly of this clamp is fast, safe and easy. The clamping range is greater than the one ear clip, meaning that the two-ear clip can be used on larger bore hoses. The practical design of two ear clips means that they clamp firmly onto the assembly and are tamper proof once mounted.



Steel, Zinc Plated, 2 Ear

5556	Min Size mm	Max Size mm
03012101	5	7
03012110	7	9
03012128	9	11
03012136	11	12
03012144	13	15
03012152	14	17
03012160	15	18
03012179	17	20
03012187	18	21
03012195	20	23
03012208	22	25
03012216	23	27
03012224	25	28
03012232	28	31
03012240	31	34
03012259	34	37
03012267	37	40
03012275	40	43
03012283	43	46
Tech Sheet 1743		

Stainless Steel, 2 Ear

stainless steel

5556	Min Size mm	Max Size mm
23012108	5	7
23012116	7	9
23012124	9	11
23012132	11	13
23012140	12	15
23012159	14	17
23012167	15	18
23012175	17	20
23012183	18	21
23012191	20	23
23012204	22	25
Tech Sheet 1744		

Mikalor O Clips with Stainless Steel Inner Ring

The fact that these clamps are used on very small-bore hoses means that the material of the tube or hose can sometimes be very flexible, making it more difficul to ensure a leaktight assembly due to the possible deformation of the hose. In these cases, the inner-ring is key in helping to guarantee leaktightness as well as protecting the hose from being pinched during assembly.



Steel, Zinc Plated, 1 Ear

5556	Min Size mm	Max Size mm
03011010	7.5	9.5
03011029	8.5	10.5
03011037	9.5	11.5
03011045	10.4	12.4
03011053	11.4	13.4
03011061	13.4	15.4
03011070	15.4	17.4
Tech Sheet 1745		

Stainless Steel, 1 Ear

stainless steel

5556	Min Size mm	Max Size mm
23012300	6.5	8.5
23012319	8.2	9.5
23012327	8.5	10.4
23012335	9.5	11.4
23012343	10.4	12.4
23012351	11.4	13.4
23012360	12.4	14.4
23012378	13.4	15.4
23012386	14.4	16.4
23012394	15.4	17.4
23012407	16.4	18.4
23012415	17.4	19.4
Tech Sheet 1745		

Available in W1 and W4

O CLIPS

2 Ear Clamp



Steel Zinc Plated DIN 1.0338

5562	Min Size mm	Max Size mm
OET0041	3.1	4.1
OET0045	3.5	4.5
OET0305	3	5
OET0507	5	7
OET0709	7	9
OET0811	8	11
OET0911	9	11
OET1113	11	13
OET1315	13	15
OET1517	15	17
OET1518	15	18
OET1619	16	19
OET1720	17	20
OET1922	19	22
OET2023	20	23
OET2225	22	25
OET2327	23	27
OET2528	25	28
OET2731	27	31
OET2831	28	31
OET3134	31	34
OET3437	34	37
OET3740	37	40
OET4043	40	43
Tech Sheet 10445		



Stainless Steel DIN 1.4301

5562	Min Size mm	Max Size mm
0045R	3.5	4.5
0305R	3	5
0507R	5	7
0709R	7	9
0811R	8	11
0911R	9	11
1113R	11	13
1315R	13	15
1517R	15	17
1518R	15	18
1720R	17	20
1922R	19	22
2023R	20	23
2225R	22	25
2327R	23	27
2528R	25	28
2731R	27	31
2831R	28	31
3134R	31	34
3437R	34	37
3740R	37	40
4043R	40	43
4346R	43	46
Tech Sheet 10445		

1 Ear Clamp



308 Stainless Steel DIN 1.4301

5562	Min Size mm	Max Size mm
061R	5.1	6.1
087R	7.5	8.7
090R	7.5	9
095R	8.1	9.5
105R	9.1	10.5
110R	9.3	11
113R	9.6	11.3
120R	10.1	12
128R	10.8	12.8
133R	11.3	13.3
138R	11.8	13.8
140R	12	14
145R	12.5	14.5
150R	13	15
168R	14.6	16.8
175R	15.3	17.5
185R	16.3	18.5
195R	17.2	19.5
200R	17.7	20
207R	17.9	20.7
210R	18.7	21
225R	19.9	22.5
245R	21.7	24.5
307R	27.2	30.7
Tech Sheet 10445		

Oetiker 1-Ear Adjustable Clamps Stainless Steel



8mm Band

5562	Size Range mm
15900007	40.0 - 110.0

FT PRO



For **Thermoplastic SAE 100R7 Hose**
see page **13**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

O CLIPS

1 Ear Stepless® Clamps, Stainless Steel 1.4301/UNS S30400

Narrow band - Concentrates transmission of clamping force, less weight.
Stepless over 360° - Uniform compression or uniform surface pressure.

Clamp ear - Compensates for component tolerances, adjustable surface pressure
Dimple - Increases clamping force, spring-effect compensates for changes in diameter due to thermal expansion

Burr-free strip edges - Reduced risk of damage to parts being clamped



Band Width 5mm, Thickness 0.5mm

5562	Min Size mm	Max Size mm
16702488	5.3	6.5
16700001	5.8	7
16700002	6.8	8
16700003	7	8.7
16702491	7.3	9
16700004	7.8	9.5
16700005	8.3	10
16700006	8.8	10.5
16702492	9.2	10.9
16700007	9.6	11.3
16700008	10	11.8
Tech Sheet 10445		

Band Width 7mm, Thickness 0.6mm

5562	Min Size mm	Max Size mm
16702951	9.4	11.9
16700009	9.8	12.3
16702493	10.3	12.8
16700010	10.8	13.3
16700011	11.3	13.8
16700012	11.5	14
16702864	11.7	14.2
16700013	12	14.5
16700014	12.3	14.8
16700015	12.8	15.3
16700016	13.2	15.7
16702998	13.5	16
16702494	13.7	16.2
16702495	14.1	16.6
16702496	14.3	16.8
16700017	14.5	17
16702497	15	17.5
16700018	14.6	17.8
16700019	14.8	18
16700020	15.3	18.5
16700110	16	19.2
16702498	16.6	19.8
16700024	17.8	21
16700026	19.4	22.6
16700028	20.3	23.5
16700029	20.9	24.1
16702148	22.4	25.6
16700033	23.9	27.1
16700055	40.8	44
16700037	26.9	30.1
16702993	27.6	30.8
16700040	28.4	31.6

5562	Min Size mm	Max Size mm
16700042	29.9	33.1
16700044	31.4	34.6
16700046	32.9	36.1
16700048	34.4	37.6
16700050	34.9	38.1
16700052	36.4	39.6
16700053	37.8	41
16700054	39.3	42.5
16704055	25.4	28.6
16700055	40.8	44
16700056	42.3	45.5
16700057	43.8	47
16700058	45.3	48.5
16700059	46.8	50
16700061	49.8	53
16700063	52.8	56
16700065	55.8	59
16700067	58.8	62
16700069	61.8	65
16700071	64.8	68
16700073	67.8	71
16700075	70.8	74
16700077	73.8	77
16700079	76.8	80
16700081	79.8	83
16700086	87.3	90.5
16700092	96.3	99.5
16700094	96.3	102.5
Tech Sheet 10445		

FT PRO



For **Hose Tails**
see pages **1140-1148**

PIPE CLIPS & TOOL CLIPS

P Clips, 12.7mm Band, M6 Fixing Hole



Mild Steel, EPDM Liner

5559	Min Size mm
A980045	4
A980060	6
A980080	8
A980090	9
A980100	10
A980110	11
A980120	12
A980130	13
A980140	14
A980150	15
A980160	16
A980180	18
A980190	19
A980200	20
A980210	21
A980220	22
A980230	23
A980240	24
A980250	25
A980270	27
A980280	28
A980290	29
A980300	30
A980320	32
A980330	33
A980350	35
A980380	38
A980400	40
A980420	42
A980440	44
A980470	47
A980480	48
A980500	50
A980540	54
A980550	55
A980560	56
A980600	60
A980640	64
A980700	70
Tech Sheet 20458	

stainless steel



Stainless Steel, EPDM Liner

5559	Min Size mm
D980050	5
D980060	6
D980080	8
D980090	9
D980100	10
D980120	12
D980130	13
D980140	14
D980160	16
D980180	18
D980200	20
D980210	21
D980220	22
D980250	25
D980280	28
D980300	30
D980320	32
D980340	34
D980380	38
D980400	40
D980440	44
D980480	48
D980500	50
D980520	52
D980550	55
D980560	56
D980570	57
D980600	60
D980660	66
D980700	70
D980800	80
D981000	100
D981100	110
Tech Sheet 20458	

Tool Clips



Narrow Base

5559	Diameter mm
A270060	6
A270120	12
A270160	16
A270200	20
A270250	25
A270280	28
A270320	32
A270380	38
A270450	45
A270500	50
A270630	63
Tech Sheet 20461	



Wide Base

5559	Diameter mm
A280060	6
A280100	10
A280120	12
A280160	16
A280200	20
A280250	25
A280280	28
A280320	32
A280380	38
A280500	50
Tech Sheet 20461	

TOTAL



For **Hand Tools**
see pages **1729-1739**

Fluid-Air Components Ltd

CLAMPS & HOSE CLIPS

Jubilee® P Clips

Jubilee® P Clips are suitable for retaining pipes, cables and hoses. Jubilee® P Clips are manufactured from a flexible steel or stainless steel one-piece band with an ethylene-propylene-diene monomer (EPDM) rubber liner.

Working Temperature:
-50°C to +150°C

- The band features a stepped design allowing the clip to sit flush with the rubber line . The single-piece construction means there are no joins, which makes the clip very strong.
- The upper hole has an elongated design allowing easy fitting of the clip.
- The rubber liner is manufactured in a corresponding profile to be secure in its position on the clip and ensures a tight fit as well as vibration damping and sound insulation. EPDM rubber offers several advantages over alternatives, such as a wide operating temperature range, resistance to UV (ultraviolet) weathering and resistance to creep.

new product

stainless steel



316 Stainless Steel (W5) EPDM Liner, M6.

Quality assurance: DIN3016
Corrosion resistance: 72-hour NSS test
Material: mild steel zinc-plated



Mild Steel Zinc Plated (W1), EPDM Liner, M5

Quality assurance: DIN3016
Corrosion resistance: 1,000-hour NSS test
Material: 304 stainless steel

stainless steel



304 Stainless Steel (W4), EPDM Liner, M6

6666	OD mm
JPC005SS316	5
JPC006SS316	6
JPC008SS316	8
JPC009SS316	9
JPC010SS316	10
JPC012SS316	12
JPC013SS316	13
JPC014SS316	14
JPC015SS316	15
JPC016SS316	16
JPC017SS316	17
JPC018SS316	18
JPC019SS316	19
JPC020SS316	20
JPC021SS316	21
JPC022SS316	22
JPC025SS316	25
JPC027SS316	27
JPC028SS316	28
JPC029SS316	29
JPC030SS316	30
JPC032SS316	32
JPC035SS316	35
JPC040SS316	40
JPC044SS316	44
JPC048SS316	48
JPC052SS316	52

6666	Min Size mm
JPC005MS	5
JPC006MS	6
JPC008MS	8
JPC010MS	10
JPC012MS	12
JPC013MS	13
JPC014MS	14
JPC015MS	15
JPC016MS	16
JPC017MS	17
JPC018MS	18
JPC019MS	19
JPC020MS	20
JPC021MS	21
JPC022MS	22
JPC025MS	25
JPC027MS	27
JPC028MS	28
JPC029MS	29
JPC030MS	30
JPC035MS	35
JPC040MS	40
JPC044MS	44
Tech Sheet 60241	

6666	Min Size mm
JPC005SS	5
JPC006SS	6
JPC008SS	8
JPC009SS	9
JPC010SS	10
JPC012SS	12
JPC013SS	13
JPC014SS	14
JPC015SS	15
JPC016SS	16
JPC017SS	17
JPC018SS	18
JPC019SS	19
JPC020SS	20
JPC021SS	21
JPC022SS	22
JPC025SS	25
JPC028SS	28
JPC030SS	30
JPC035SS	35
JPC040SS	40
JPC044SS	44
Tech Sheet 60241	

Jubilee® P Clip Kits

Contains 110 x P Clips of the most accepted sizes in a versatile, re-usable plastic container suitable for any challenging environment.

Jubilee® P Clips are manufactured from one piece of steel band with an EPDM rubber liner.



P Clip Kits

6666	Material
JPCK110MS	Mild Steel
JPCK110SS	304 Stainless Steel
Tech Sheet 60243	

FAC
Fluid-Air Components Ltd

CLIPS

M6 P Clips, 12mm Band

Material:
Mild Steel, Zinc Plated.
EPDM Rubber lined.



Mild Steel, Standard Liner

5557	Min size mm
500-05	5
500-06	6
500-08	8
500-09	9
500-10	10
500-12	12
500-13	13
500-16	16
500-19	19
500-21	21
500-22	22
500-25	25
500-28	28
500-29	29
500-32	32
500-35	35
500-40	40
500-44	44
500-48	48
500-52	52
500-56	56
500-60	60
Tech Sheet 589	

Material: Mild Steel, Zinc Plated.
Standard Liner:
TPE -30°C to +60°C High temperature rubber liner.
TPE 160: -50°C to +160°C.



Mild Steel, High Temperature Liner

5557	Min Size mm
501-5	5
501-6	6
501-8	8
501-9	9
501-10	10
501-12	12
501-13	13
501-16	16
501-19	19
501-21	21
501-22	22
501-25	25
501-28	28
501-29	29
501-32	32
501-35	35
501-40	40
501-48	48
501-52	52
501-56	56
501-60	60
Tech Sheet 589	

304 Stainless Steel, P Clips, 12mm Band

stainless steel



Stainless Steel, Standard Liner

5557	Min Size mm
500-5SS	5
500-6SS	6
500-8SS	8
500-10SS	10
500-13SS	13
500-16SS	16
500-19SS	19
500-21SS	21
500-22SS	22
500-25SS	25
500-28SS	28
500-29SS	29
500-32SS	32
500-35SS	35
500-40SS	40
500-44SS	44
500-48SS	48
500-52SS	52
500-56SS	56
500-60SS	60
Tech Sheet 589	

Material: 304 (A2) Stainless Steel. High temperature rubber liner.
TPE 160:
-50°C to +160°C.

stainless steel



Stainless Steel, High Temperature Liner

5557	Min Size mm
501-6SS	6
501-8SS	8
501-9SS	9
501-10SS	10
501-12SS	12
501-13SS	13
501-16SS	16
501-19SS	19
501-28SS	28
501-32SS	32
501-35SS	35
501-40SS	40
501-60SS	60
Tech Sheet 589	

M10 P Clips, 20mm Band

Material: Mild Steel Zinc Plated.
High temperature rubber liner.
TPE 160: -50°C to +160°C.



Mild Steel Zinc Plated, High Temperature Liner

5557	Min Size mm
601-6	6
601-8	8
601-10	10
601-13	13
601-16	16
601-19	19
601-22	22
601-25	25
601-28	28
601-32	32
601-36	36
601-40	40
601-44	44
601-48	48
601-52	52
Tech Sheet 589	

Material: Stainless Steel (BS304).
High temperature rubber liner.
TPE 160:
-50°C to +160°C.

stainless steel



Stainless Steel, High Temperature Liner

5557	Min Size mm
601-6SS	6
601-8SS	8
601-10SS	10
601-13SS	13
601-16SS	16
601-19SS	19
601-22SS	22
601-25SS	25
601-28SS	28
601-32SS	32
601-36SS	36
601-40SS	40
601-44SS	44
601-48SS	48
601-52SS	52
Tech Sheet 589	

Fluid-Air Components Ltd

CLIP PACKS

P Clips Mild Steel Assorted Pack

- **Diameters:** 5mm, 6mm, 8mm, 10mm, 13mm, 16mm, 19mm, 21mm, 25mm, 29mm and 35mm

Standard Liner: TPE -30°C to +60°C



104 Assorted, Mild Steel Zinc Plated Clips

5557
PCZRAB1

P Clips Stainless Steel Assorted Pack

- **Diameters:** 5mm, 6mm, 8mm, 10mm, 13mm, 16mm, 19mm, 21mm, 25mm, 29mm and 35mm

Standard Liner: TPE -30°C to +60°C

stainless steel



104 Assorted, 18/8 Marine, Quality BS304 Stainless Steel Clips

5557
PCSRAB1

Assorted Kits

Contents:

Mild Steel

Size	Quantity
4-5mm	10
6mm	10
8mm	7
9mm	7
10mm	6
12mm	3
14mm	3
16mm	3
18mm	2
20mm	2



Stainless Steel

Size	Quantity
5mm	10
6mm	9
8mm	7
9mm	6
10mm	6
12mm	3
14mm	3
16mm	3
18mm	2
20mm	2



P Clips

5559	Material
PCLIP-KIT-MS	Mild Steel
PCLIP-KIT-SS	Stainless Steel
Tech Sheet 20468	

NORMA



For **Pipe Repair Couplings** see page **1557**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

CLAMPS & HOSE CLIPS

NORMA® P Type Pipe Clip

- EPDM Rubber Sleeve
- Vibration Damping
- Fixing Hole For M6 Bolt



Mild Steel Alu-Zinc Plated, 12mm Band Width

7777	To Suit Hose OD mm
NOR-RLGUP-5	5
NOR-RLGUP-6	6
NOR-RLGUP-8	8
NOR-RLGUP-9	9
NOR-RLGUP-10	10
NOR-RLGUP-12	12
NOR-RLGUP-13	13
NOR-RLGUP-16	16
NOR-RLGUP-19	19
NOR-RLGUP-22	22
NOR-RLGUP-25	25
NOR-RLGUP-28	28
NOR-RLGUP-29	29
NOR-RLGUP-32	32
NOR-RLGUP-35	35
NOR-RLGUP-40	40
NOR-RLGUP-44	44

NORMA® P Type HD Pipe Clip



Mild Steel Zinc Plated, 15mm Band Width

7777	To Suit Hose OD mm
NOR-RSGUP-6	6
NOR-RSGUP-8	8
NOR-RSGUP-10	10
NOR-RSGUP-12	12
NOR-RSGUP-13	13
NOR-RSGUP-16	16
NOR-RSGUP-19	19
NOR-RSGUP-21	21
NOR-RSGUP-22	22
NOR-RSGUP-25	25
NOR-RSGUP-28	28
NOR-RSGUP-30	30
NOR-RSGUP-32	32
NOR-RSGUP-35	35

Wall Mounted Display Dispenser

Part No.	Min Size	Max Size	Band Width mm	Qty
NOR-OOO	8	12	9	10
NOR-MOO	10	16	9	10
NOR-OO	12	22	9	10
NOR-O	16	27	12	8
NOR-1A	20	32	12	8
NOR-1	25	40	12	8
NOR-2A	35	50	12	8
NOR-2	40	60	12	8
NOR-3	50	70	12	8



With 78 Clips

7777
NOR-8880000080

NORMA® U Type HD Pipe Clip



Mild Steel Zinc Plated, 15mm Band Width

7777	To Suit Hose OD mm
NOR-RSGUU-6	6
NOR-RSGUU-12	12
NOR-RSGUU-13	13
NOR-RSGUU-16	16
NOR-RSGUU-19	19
NOR-RSGUU-21	21
NOR-RSGUU-22	22
NOR-RSGUU-25	25
NOR-RSGUU-28	28
NOR-RSGUU-30	30
NOR-RSGUU-35	35

Box Set Clips

Part No.	Min Size	Max Size	Band Width mm	Qty
NOR-OOO	8	12	9	24
NOR-MOO	10	16	9	22
NOR-OO	12	22	9	24
NOR-OX	16	27	12	24
NOR-1A	20	32	12	10
NOR-1	25	40	12	16



With 120 Clips

7777
NOR-8880000003

Fluid-Air Components Ltd

METRIC PIPE CLIPS & BACK PLATES

Pipe Clips

Die Cast.



Screw to Wall, Brass

0245	OD mm
EPS-SO15-S	15
EPS-SO22-S	22
EPS-SO28-S	28
EPS-SO35-S	35
EPS-SO42-S	42
EPS-SO54-S	54

Die Cast.



Screw to Wall, Chrome Plated, Brass

0245	OD mm
EPS-SO15CP-S	15
EPS-SO22CP-S	22
EPS-SO28CP-S	28
EPS-SO35CP-S	35
EPS-SO42CP-S	42
EPS-SO54CP-S	54



Pressed Screw-On, Brass

0245	OD mm
EPS-SOPB12-S	12
EPS-SOPB15-S	15
EPS-SOPB22-S	22
EPS-SOPB28-S	28
EPS-SOPB35-S	35



Pressed Screw-On, Chrome Plated

0245	OD mm
EPS-SOPB15CP-S	15
EPS-SOPB22CP-S	22
EPS-SOPB28CP-S	28
EPS-SOPB35CP-S	35

M10 Threads.



Hospital, Brass

0245	OD mm
EPS-HB15-S	15
EPS-HB22-S	22
EPS-HB28-S	28
EPS-HB35-S	35
EPS-HB42-S	42
EPS-HB54-S	54

M10 Threads.



Hospital, Chrome Plated

0245	OD mm
EPS-HB15CP-S	15
EPS-HB22CP-S	22
EPS-HB28CP-S	28
EPS-HB42CP-S	42

Die Cast
M10 Threads.



Single Munsen Ring, Brass

0245	OD mm
EPS-MR15-S	15
EPS-MR22-S	22
EPS-MR28-S	28
EPS-MR35-S	35
EPS-MR42-S	42
EPS-MR54-S	54
EPS-MR67-S	67
EPS-MR76-S	76

Die Cast
M10 Threads.



Single Munsen Ring, Chrome Plated

0245	OD mm
EPS-MR15CP-S	15
EPS-MR22CP-S	22
EPS-MR28CP-S	28
EPS-MR35CP-S	35
EPS-MR42CP-S	42
EPS-MR54CP-S	54

Die Cast
M10 Threads.



Double Munsen Ring, Brass

0245	OD mm
EPS-MR15D-S	15
EPS-MR22D-S	22
EPS-MR35D-S	35
EPS-MR54D-S	54

Back Plates



M10, Male

0245	Finish
EPS-MP10-S	Brass
EPS-MP10CP-S	Chrome Plated



M10, Female

0245	Finish
EPS-FP10-S	Brass
EPS-FP10CP-S	Chrome Plated

Fluid-Air Components Ltd

BSP PIPE CLIPS & BACK PLATES

Pipe Clips



1/4" BSPP, Dual Purpose, Brass

0245	OD mm
EPS-DPBSP15-S	15
EPS-DPBSP22-S	22
EPS-DPBSP28-S	28
EPS-DPBSP35-S	35
EPS-DPBSP42-S	42
EPS-DPBSP54-S	54



1/4" BSPP, Dual Purpose, Chrome Plated

0245	OD mm
EPS-DPBSP15CP-S	15
EPS-DPBSP28CP-S	28
EPS-DPBSP35CP-S	35



Single Munsen Ring, Brass, BSPP

0245	OD mm	Thread
EPS-MRBSP15-S	15	1/4"
EPS-MRBSP22-S	22	1/4"
EPS-MRBSP28-S	28	1/4"
EPS-MRBSP35-S	35	1/4"
EPS-MRBSP67-S	67	3/8"
EPS-MRBSP76-S	76	1/2"



1/4" BSPP, Single Munsen Ring, Chrome Plated

0245	OD mm
EPS-MRBSP35CP-S	35



Double Munsen Ring, Brass, BSPP

0245	OD mm	Thread
EPS-MRBSP35D-S	35	1/4"
EPS-MRBSP54D-S	54	3/4"

Copper Saddle Clips



0245	OD mm	Description
EPS-CS10-S	10	-
EPS-CS15-S	15	-
EPS-CS215-S	15	2 Piece
EPS-CS22-S	22	-
EPS-CS28-S	28	-
EPS-CS35-S	35	-
EPS-CS42-S	42	-
EPS-CS54-S	54	-

Chrome Plated Saddle Clips



1 Piece

0245	OD mm
CS15CP-S	15
CS22CP-S	22



2 Piece

0245	OD mm
CS215CP-S	15

Steel Saddle Clips



0245	Nominal Bore OD
SSB12-S	1/2"
SSB34-S	3/4"
SSB1-S	1"
SSB114-S	1.1/4"
SSB112-S	1.1/2"
SSB2-S	2"

For **Copper Tube** see page **1213**



Fluid-Air Components Ltd

PIPE SADDLE CLIPS

Mild Steel Saddle Clips


- Bag of 100
- Mild steel zinc plated
- Sizes up to 10mm have 4.8mm fixing hole



Half Saddles – Light, Bag of 100

5559	OD mm	No of Tubes
A940040-1	4	1
A940050-1	5	1
A940060-1	6	1
A940070-1	7	1
A940080-1	8	1
A940100-1	10	1
A940120-1	12	1
A940160-1	16	1
A940040-2	4	2
A940050-2	5	2
A940060-2	6	2
A940080-2	8	2
A940100-2	10	2
A940120-2	12	2
Tech Sheet 20456		

- Sizes 12mm and 16mm have 5.8mm fixing hole
- DIN 72571 or 72573



Full Saddles – Light, Bag of 100

5559	OD mm	No of Tubes
C940040-1	4	1
C940050-1	5	1
C940060-1	6	1
C940070-1	7	1
C940080-1	8	1
C940100-1	10	1
C940120-1	12	1
C940040-2	4	2
C940050-2	5	2
C940080-2	8	2
C940100-2	10	2
Tech Sheet 20456		

- Mild steel zinc plated
- Sizes up to 19mm have 6.6mm fixing hole
- Sizes 23mm to 33mm have 9.0mm fixing hole
- DIN 1596



Half Saddles – Heavy

5559	OD mm	No of Tubes	Quantity
H940070-1	7	1	50
H940090-1	9	1	50
H940130-1	13	1	50
H940155-1	15.5	1	50
H940190-1	19	1	50
H940230-1	23	1	25
H940260-1	26	1	25
H940285-1	28.5	1	25
H940310-1	31	1	25
Tech Sheet 20456			

PIPE FIXINGS

Pipe Clips



Snap-in Open, Single, Pack of 100

5559	Bore Size mm
OPS-15	15
OPS-22	22
OPS-28	28

Tube Clips



Nylon, 10 per Strip


0224	To Suit Plastic Pipe OD mm
1824431001	8

Nail Clips



Universal, White, Pack of 100

5559	Bore Size mm	Nail Size mm
NCW-15	15	Ø2.5 x 45
NCW-22	22	Ø2.5 x 50
NCW-28	28	Ø2.5 x 55



Universal, Grey, Pack of 100

5559	Bore Size mm	Nail Size mm
NCG-22	22	Ø2.5 x 50

PIPE CLIPS & FIXING SYSTEMS

Pipe Clamps



Unlined, M8/M10/M12

5555	Bore Size mm	Thread
APPC20	20-25	M10
APPC31	31-38	M10
APPC40	40-46	M10
APPC52	52-56	M8
APPC57	57-62	M10
APPC63	63-66	M10
APPC67	67-71	M10
APPC72	72-75	M10
APPC76	76-81	M10
APPC89	89-94	M10
APPC95	95-102	M10
APPC108	108-117	M10
APPC176	176-182	M12

Unlined Duel M8/M10 Thread

5555	Bore Size mm	Thread
ULC38/43	38-43	M8/M10
ULC47/51	47-51	M8/M10
ULC159/166	159-166	M8/M10

Fire resistance- Class B2
Insulating Lining According to DIN4109
Max Recommended Load- 200Kg

Working Temperature:
-40°C to +100°C



EPDM Rubber Lined, M8/M10

5559	Bore Size mm	Thread
APIPC14	15-19	M10
APIPC20	20-24	M8
APIPC26	23-28	M10
APIPC32	31-36	M10
APIPC40	38-44	M10
APIPC48	44-50	M10
APIPC54	54-58	M10
APIPC58	59-65	M8
APIPC68	62-67	M10
APIPC72	74-80	M10
APIPC88	83-93	M10
APIPC112	108-118	M10
APIPC137	133-143	M10
APIPC159	159-169	M10
Tech Sheet 20406		

EPDM Rubber Lined Duel M8/M10 Thread

5555	Bore Size mm	Thread
RLC125/130	125-130	M8/M10
RLC148/152	148-152	M8/M10
Tech Sheet 20406		

Fire resistance- Class B2
Insulating Lining According to DIN4109



Rapid EPDM Rubber Lined, M8/M10

5559	Bore Size mm
APRC13	12-16
APRC20	20-23
APRC25	26-30

stainless steel



Swivel Hanger

5555	Thread
APSHM10	M10
Tech Sheet 20751	

For **Studding**
see page **1385**



Fluid-Air Components Ltd

Wall or Ceiling Mounted Pipe Clips

Advantages

- With retaining ring
- Close fitting possibl
- Suitable for high loads and temperatures
- Electrolytically zinc plated
- BSU clips are designed for mounting steel pipes to the wall or ceiling



BSF Clip

0713	Thread	Bore Size mm
38671	M8-M10	13-17.5
38672	M8-M10	21-25.5
38673	M8-M10	26.5-30.5
38674	M8-M10	33.5-38.5
38675	M8-M10	41.5-47
38676	M8-M10	48-54
38677	M8-M10	56-62.5
38678	M8-M10	62.5-69.5
38679	M8-M10	69.5-76.5
38680	M8-M10	77.5-84
38681	M8-M10	85-92.5
38682	M8-M10	93-100.5
38683	M8-M10	101.5-110
38684	M8-M10	110-117.5
38685	M8-M10	119.5-127.5
38686	M8-M10	127.5-133.5

- BSI clips are rubber lined universal clips for mounting pipes to the wall or ceiling

Working Temperature:
-40°C to +120°C

Advantages:

- Fitted with two bolts with anti-loss ring
- Bolt with slot and cross head
- Reinforcement grooves ensure that BSI clips maintain their shape
- Noise suppression up to 17dB(A)
- Electrolytically zinc plated



BSI, EPDM Rubber Lined

0713	Thread	Bore Size mm
39000	M8-M10	12-14
39001	M8-M10	15-19
39002	M8-M10	20-25
39003	M8-M10	26-30
39004	M8-M10	32-36
39005	M8-M10	38-43
39006	M8-M10	44-49
39007	M8-M10	50-55
39008	M8-M10	56-61
39009	M8-M10	62-67
39010	M8-M10	68-73
39011	M8-M10	75-80
39012	M8-M10	82-86
39013	M8-M10	87-92
39014	M8-M10	95-102
39015	M8-M10	108-116
39016	M8-M10	121-127
39017	M8-M10	131-141
39018	M8-M10	159-163
39019	M8-M10	165-168
39020	M8-M10	192-202
39022	M8-M10	210-220
Tech Sheet 68173		

Advantages:

- With retaining ring
- Close fitting possibl
- Bolt with slot and cross head
- Suitable for high loads and temperatures
- Electrolytically zinc plated



BSU, Unlined

0713	Thread	Bore Size mm
38270	M8-M10	15-18
38271	M8-M10	20-25
38272	M8-M10	26-30
38273	M8-M10	32-36
38274	M8-M10	38-43
38275	M8-M10	44-49
38276	M8-M10	56-61
38277	M8-M10	75-80
38278	M8-M10	87-92
38279	M8-M10	108-116
38282	M10-M12	108-116
38283	M10-M12	131-141
38284	M10-M12	165-169
Tech Sheet 68177		

- Stainless steel universal clips with rubber strips for mounting pipes to the wall or ceiling
- For use in situations where stainless steel mounting material is desired or required, such as food processing facilities, laboratories, the chemical industry, etc.

Working Temperature:
-40°C to +120°C

Advantages:

- Suitable for short-distance mounting
- Noise suppression up to 17dB(A)
- Electrolytically zinc plated

stainless steel



BRS-A, EPDM Rubber Lined, Stainless Steel

0713	Thread	Bore Size mm
38451	M8-M10	12-14
38452	M8-M10	15-19
38453	M8-M10	20-25
38454	M8-M10	26-30
38455	M8-M10	32-36
38456	M8-M10	38-43
38457	M8-M10	44-49
38458	M8-M10	50-55
38459	M8-M10	56-61
38460	M8-M10	62-67
38461	M8-M10	68-73
38462	M8-M10	75-80
38463	M8-M10	82-86
38464	M8-M10	87-92
38465	M8-M10	95-102
38467	M8-M10	121-127
38468	M8-M10	131-141
38469	M8-M10	159-163
38470	M8-M10	165-169
38471	M8-M10	192-202
38473	M8-M10	210-220
Tech Sheet 68175		

Fluid-Air Components Ltd

PIPE CLIPS & FIXING SYSTEMS

Flamco
Flow of Innovation

Wall or Ceiling Mounted Pipe Clips

- Stainless steel universal clips for mounting stainless steel pipes to the wall or ceiling
- For use in situations where stainless steel mounting material is desired or required, such as food processing facilities, laboratories, the chemical industry, etc.

Advantages:

- Suitable for short-distance mounting

stainless steel



BRS, Unlined, Stainless Steel

0713	Thread	Bore Size mm
38475	M8-M10	8-10
38476	M8-M10	12-14
38477	M8-M10	15-19
38478	M8-M10	20-25
38479	M8-M10	26-30
38480	M8-M10	32-36
38481	M8-M10	38-42
38482	M8-M10	44-49
38483	M8-M10	50-55
38484	M8-M10	56-61
38485	M8-M10	62-67
38486	M8-M10	68-73
38487	M8-M10	75-80
38488	M8-M10	82-86
38489	M8-M10	87-92
38490	M8-M10	95-102
38491	M8-M10	108-116
38492	M8-M10	121-127
38493	M8-M10	131-141
38494	M8-M10	159-163
38495	M8-M10	165-169
38496	M8-M10	192-202
38497	M8-M10	210-220
Tech Sheet 68176		

BSK-I clips are designed for plastic pipes with special TPE (thermoplastic elastomer) lining.
The BSK-I clip has easily removable plastic spacers between the two clip halves and can be transformed into a clenching clip without the need for tools.

Advantages:

- Special TPE lining with excellent low friction properties
- Transformable from sliding to clamping with easily removable spacer
- Fast assembly thanks to the patented click-spring locking system
- Noise reduction: 20 dB(A) with spacer, 18 dB(A) without spacer
- UV resistant
- Electronically zinc plated

Working Temperature:
-20°C to +100°C



BSK-I Clip Range

0713	Thread	Bore Size mm
37307	M8	63
37359	M10	75
37368	M10	250
Tech Sheet 68756		

- BSI-HDI clips are rubber lined, hot dip galvanized universal clips for mounting pipes to the wall or ceiling

Working Temperature:
-40°C to +120°C

Advantages:

- The clip has one or more strengthening ribs to achieve a strong working load
- Close fitting possible
- Noise suppression up to 17dB(A)



BSI-HDI, Hot Dipped Galvanized

0713	Thread	Bore Size mm
38571	M8-M10	12-14
38572	M8-M10	15-19
38573	M8-M10	20-25
38574	M8-M10	26-30
38575	M8-M10	32-36
38576	M8-M10	38-43
38579	M8-M10	56-61
38580	M8-M10	62-67
38581	M8-M10	68-73
38582	M8-M10	75-80
38584	M8-M10	87-92
38586	M8-M10	108-116
38587	M8-M10	121-127
38588	M8-M10	131-141
38590	M8-M10	165-168
38592	M8-M10	210-220
Tech Sheet 68174		

FT PRO®



For **Hydraulic Tubing**
see page **183**

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c


PIPE CLIPS & FIXING SYSTEMS

Flamco
Flow of Innovation

Mounting

Advantages of Flamco Rail:

- Short installation height, thanks to the flat grooved construction
- The ergonomic design of the rail ensures that sliding nuts and similar components slide easily into place
- Flamco fittings and components are compatible across the entire Flamco Rail range



R1 Mounting Rail

0713	Length mm
50010	2000
	Tech Sheet 68180

- Neatly finishes off the ends of all types of Flamco Rail
- Quick and easy to push into position



RD1 Mounting Rail End Cap

0713	To Suit
50501	50010

Product Features:

- Easy mounting by pushing and turning the unit in the rail 45° clockwise
- No-return stop
- Reduced installation time
- Electrolytically zinc plated
- No loose parts such as studs, washers and nuts



Wall Mounting Rail Connection

0713	Breaking Strain
71806	1000 Newton
	Tech Sheet 68179



ClickEasy Sliding Nut

0713	Thread
80360	M6
80361	M8
80362	M10



ClickEasy HBS

0713	Thread	Length mm
80381	M10	50

For mounting Flamco rail to steel without welding or drilling



RB1 Rail Girder Clip

0713	Thread	Max Extended mm
80601	M8 x 55	15

RIDGID



For **Ridgid Strut Slayer**
see page **1744**

QUICK RELEASE BAND STRAPS & BANDING

Jubilee® Quick Release Band Straps

Jubilee® quick release straps are used in a wide range of applications where a closed installation requires the clamp to be opened fully for positioning.

Examples include sign fixing, cable retention, repairs and heating, ventilatio and air conditioning.



Mild Steel, Zinc Plated, 11mm Wide

6666	Min Size mm	Max Size mm
CAS050MS	35	50
CAS075MS	45	75
CAS100MS	50	100
CAS120MS	50	120
CAS150MS	50	150
CAS200MS	50	200
CAS225MS	50	225
CAS250MS	50	250
CAS275MS	50	275
CAS300MS	50	300
CAS330MS	50	330
CAS355MS	50	355
CAS380MS	50	380
CAS405MS	50	405
CAS455MS	50	455
CAS505MS	50	505
CAS555MS	50	555
CAS605MS	50	605
CAS710MS	50	710
CAS910MS	50	910
CAS965MS	50	965



304 Stainless Steel, 7mm Wide

6666	Min Size mm	Max Size mm
FLS050SS	35	50
FLS075SS	45	75
FLS100SS	50	100
FLS120SS	50	120
FLS150SS	50	150
FLS225SS	50	225
FLS250SS	50	250
FLS275SS	50	275
FLS300SS	50	300
FLS330SS	50	330
FLS380SS	50	380
FLS405SS	50	405



304 Stainless Steel, 11mm Wide, W4

6666	Min Size mm	Max Size mm
CAS050SS	35	50
CAS075SS	45	75
CAS100SS	50	100
CAS120SS	50	120
CAS150SS	50	150
CAS175SS	50	175
CAS225SS	50	225
CAS250SS	50	250
CAS275SS	50	275
CAS300SS	50	300
CAS330SS	50	330
CAS355SS	50	355
CAS380SS	50	380
CAS405SS	50	405
CAS555SS	50	555
CAS605SS	50	605
CAS710SS	50	710
CAS810SS	50	810
CAS910SS	50	910
CAS965SS	50	965
Tech Sheet 60247		

Jubilee® Multiband

Construct your own fastener – cut to size and choose from a choice of standard slotted screw or captive screw.
Banding available in 11mm mild steel zinc-plated or 11mm stainless steel (304).

10 Metre Lengths

6666	Band Width mm
2025-3720	11
Tech Sheet 1942	



30 Metre Lengths

6666	Band Width mm
2025-3738	11
Tech Sheet 1942	



Housing & Screws, 25 Sets, 11mm

6666
2025-3746





7mm Stainless Steel 304

6666	Description	Length m/Sets
MB1601	7mm Multiband	25
MB1603	Flip Lock Housing/Screws	25 Sets

11mm Mild Steel Zinc Plated

6666	Description	Length m/Sets
MB1705	Housing/Allen Socket Screws	25 Sets
MB1708	11mm Handy Pack	10m + 25 x Housings/ Screws

11mm Stainless Steel

6666	Description	Length m/Sets
MB1802	11mm Multiband	30 (m)
MB1803	Housing/Screws	25 Sets
MB1804	Housing/Allen Socket Screws	25 Sets
MB1806	11mm Handy Pack	10m + 25 x Housings/ Screws

Fluid-Air Components Ltd

BANDING SYSTEM & TIE WRAPS


304 Stainless Steel Banding System

To use, take one end of the cut banding and bend back 1/2". Take a self locking head and slide it the entire length of the band until it reaches the bend. Bend the tail flat against the bottom of the banding head to complete assembly.



0040	Type	Length Metres	Width mm	Box Quantity
SBS-76L	Band	76	4.6	1
SBS-76H	Band	76	7.9	1
SBH-L	Locking Head	-	4.6	100
SBH-H	Locking Head	-	7.9	100

304 Stainless Steel Cable Ties



0040	Length mm	Width mm
STW-201L	201	4.6
STW-362L	362	4.6
STW-838H	838	7.9

Polyamide 6/6 Nylon, Cable Ties

Resistant to UV, oils, grease, salt (DNV Marine approved) and light acids. UL approved (E97527).



Natural, Pack of 100

0040	Width mm	Length mm
GP-025-0100N	2.5	100
GP-025-0200N	2.5	200
GP-036-0140N	3.6	140
GP-036-0200N	3.6	200
GP-036-0300N	3.6	300
GP-048-0120N	4.8	120
GP-048-0160N	4.8	160
GP-048-0200N	4.8	200
GP-048-0300N	4.8	300
GP-048-0368N	4.8	368
GP-076-0200N	7.6	200
GP-076-0240N	7.6	240
GP-076-0300N	7.6	300
GP-076-0368N	7.6	368
GP-090-0430N	9	430
GP-090-0530N	9	530
Tech Sheet 20413		



Black, Pack of 100

0040	Width mm	Length mm
GP-025-0100B	2.5	100
GP-025-0200B	2.5	200
GP-036-0140B	3.6	140
GP-036-0200B	3.6	200
GP-036-0300B	3.6	300
GP-048-0120B	4.8	120
GP-048-0160B	4.8	160
GP-048-0200B	4.8	200
GP-048-0300B	4.8	300
GP-048-0368B	4.8	368
GP-076-0200B	7.6	200
GP-076-0240B	7.6	240
GP-076-0300B	7.6	300
GP-076-0368B	7.6	368
GP-090-0430B	9	430
GP-090-0530B	9	530
Tech Sheet 20413		

FT PRO®



For **ISO 15552 Cylinders**
see pages **478-486**

STEEL STRAPPING & ACCESSORIES

Band-It patented easy scale makes the **Band-It** clamping system the industry's favourite for over 60 years.
All **Band-It** sizes feature fully rounded smooth edges for safety and easy installation.

Band-It Clamping Tool

Used to apply Band-It Band, Tote and Buckles.



Built-in Cutter

5561
C001

Junior Preformed Clamp Tool

For use with Band-It Junior smooth ID preformed clamps.





Built-in Cutter

5561
C00269

201 Band-It Band Stainless Steel Strapping

stainless steel



30.5 Metres

5561	Band Width mm	Band Thickness mm
C202	6.35	0.51
C203	9.53	0.63
C204	12.70	0.76
C205	15.88	0.76
C206	19.05	0.76

201 Band-It Band Buckles

Designed to accommodate both single and double wrap clamps.

stainless steel



Stainless Steel, Standard, Pack of 100

5561	Band Width mm
C252	6.35
C253	9.53
C254	12.70
C255	15.88
C256	19.05

201 Band-It Tote Stainless Steel Strapping

Supplied in handy waterproof packaging. Colour coded for easy identification

stainless steel



30.5 Metres

5561	Band Width mm	Band Thickness mm
C203Y	9.53	0.63
C204B	12.70	0.76
C205G	15.88	0.76
C206R	19.05	0.76

Band-It Valustrap

Non-magnetic stainless steel strapping used with Valuclips for securing signs, cable-bundling, pipe insulation and a variety of other lightweight applications.

stainless steel



30.5 Metres

5561	Band Width mm	Band Thickness mm
C133	9.60	0.38
C134	12.70	0.38
C135	15.90	0.38
C136	19.10	0.38

Valuclips



Pack of 100

5561	Band Width mm
C153	9.53
C154	12.70
C156	19.05

Fluid-Air Components Ltd

STEEL STRAPPING & ACCESSORIES

BAND-IT THE CLAMPING EXPERTS

Junior Preformed Clamps

Band-It patented easy scale makes the Band-It clamping system the industry's favourite for over 60 years.

All Band-It sizes feature fully rounded smooth edges for safety and easy installation.

stainless steel



201 Stainless Steel

5561	ID	Band Width mm	Band Thickness mm
JS240	3/4"	6.4	0.51
JS242	1"	6.4	0.51
JS241	1.3/8"	6.4	0.51
JS252	1.1/2"	6.4	0.51
JS253	2"	6.4	0.51
JS256	2.3/4"	6.4	0.51
JS244	3"	6.4	0.51
JS257	3.1/2"	6.4	0.51
JS259	4.1/2"	6.4	0.51
JS201	13/16"	9.5	0.64
JS243	1"	9.5	0.64
JS202	1.3/8"	9.5	0.64
JS245	2"	9.5	0.64
JS246	3"	9.5	0.64
JS255	3.1/4"	9.5	0.64
JS203	1"	12.7	0.76
JS204	1.1/4"	12.7	0.76
JS236	1.3/4"	12.7	0.76
JS230	2.3/4"	12.7	0.76
JS205	1.1/2"	15.9	0.76
JS206	1.3/4"	15.9	0.76
JS207	2"	15.9	0.76
JS208	2.1/4"	15.9	0.76
JS209	2.1/2"	15.9	0.76
JS227	2"	19.1	0.76
JS210	2.3/4"	19.1	0.76
JS211	3"	19.1	0.76
JS212	3.1/2"	19.1	0.76
JS213	4"	19.1	0.76
JS214	4.1/2"	19.1	0.76
JS215	5"	19.1	0.76
JS216	6"	19.1	0.76

All Purpose Band

Band-It All Purpose Band offers versatility within varying temperatures and applications.

All Purpose Band is ideal for bending and forming around virtually any section or shape. Resistant to physical abrasion, UV light and corrosive environments for many applications where plastic cable ties are simply inadequate or even dangerous.

- 316 stainless steel or galvanised carbon steel
- Pre-punched holes make fastening quick and easy
- Easy to form around any section
- Flame retardant low smoke PPA 571 coating
- Thick coating; kind to hands and cables
- Halogen free
- Simple fastening with nuts, bolts or screws
- Three widths available
- Standard black coating; other colours are available on request





316 Stainless Steel, Coated

stainless steel

5561	Band Width mm	Band Thickness mm	Dia of Hole mm	Length mm
AE466	17	1.3	7	10
AE467	26	1.3	8	10
AE475	12	1.3	5	25
AE476	17	1.3	7	25
AE477	26	1.3	8	25
		Tech Sheet 68231		

316 Stainless Steel, Uncoated

stainless steel

5561	Band Width mm	Band Thickness mm	Dia of Hole mm	Length mm
AE407	26	0.76	8	10
AE425	12	0.76	5	25
AE426	17	0.76	7	25
AE427	26	0.76	8	25
		Tech Sheet 68231		

Galvanised Carbon Steel, Coated


5561	Band Width mm	Band Thickness mm	Dia of Hole mm	Length mm
AE566	17	1.3	7	10
AE567	26	1.3	8	10
AE575	12	1.3	5	25
AE576	17	1.3	7	25
AE577	26	1.3	8	25
		Tech Sheet 68231		

Galvanised Carbon Steel, Uncoated

5561	Band Width mm	Band Thickness mm	Dia of Hole mm	Length mm
AE505	12	0.76	5	10
AE506	17	0.76	7	10
AE507	26	0.76	8	10
		Tech Sheet 68231		


FERRULES

Mild Steel Hose Ferrules



5563	Length (D) mm	Length (A) mm	Length (D2) mm
SHF-10	10.1	20	7.5
SHF-11	11.1	20	8.5
SHF-12	12.1	20	8.5
SHF-13	13.1	20	8.8
SHF-14	14.1	20	11
SHF-15	15.1	20	12.5
SHF-16	16.1	20	12.5
SHF-17	17.1	20	14.5
SHF-18	18.1	20	14.5
SHF-19	19.1	21	14.8
SHF-20	20.1	22	14.8
SHF-28	28.1	32	20.5


stainless steel



Grade 303

5563	Length (D) mm	Length (A) mm	Length (D2) mm
STF-11	11.1	20	8.5
STF-12	12.1	20	8.5
STF-13	13.1	20	8.8
STF-14	14.1	20	11
STF-15	15.1	20	12.5
STF-17	17.1	20	14.5
STF-18	18.1	20	14.5
STF-22	22.1	22	15.5

Brass Hose Ferrules




Type HF

5555	Length (D) mm	Length (A) mm	Length (D2) mm
HF7322	12.7	25.4	8.7
HF3588	14.3	19	9.4
HF7325	14.4	25.4	10.9
HF7326	15.1	25.4	11
HF7327	15.9	25.4	11.1
HF7328	16.7	25.4	11.1
HF7329	17.4	25.4	12.7
HF7330	18.2	25.4	12.7
HF7331	19.1	25.4	12.7
HF7332	19.8	25.4	12.7
HF7333	20.6	25.4	15.8
HF7244	22.2	22.5	17.6
HF1275	31.9	31.9	22.2

Ferrules for Low Pressure Hoses

- Red hot steel, zinc-plated and yellow chromated
- Easy, fast and safe hose crimping with hand-operated assembly machines: SPR 333 (use LPH-12.5 to LPH-23) and SPR 500 (use LPH-25 to LPH-41)
- No danger of hurt, closed and unremovable connection
- For crimping of various hoses and fittings for different fluids

Maximum Working Pressure: 16 Bar



Steel

5555	I.D. Ø	To Suit Hose DIN20018	To Suit Hose Water	To Suit Hose PVC	l	d	Weight g
LPH-12.5	12.5	-	-	-	17	8.5	3
LPH-13.5	13.5	-	-	6 x 3	20	9.3	5
LPH-14.5	14.5	6 x 3.5	-	-	17	10	5
LPH-16	16.0	-	-	8 x 3	17	11.5	5
LPH-18	18.0	9 x 3.4	-	10 x 3	20	13.5	7
LPH-19	19.0	-	-	12 x 3	20	13.9	9
LPH-19.5	19.5	-	-	-	26	14.5	10
LPH-22	22.0	-	-	-	32	17.0	16
LPH-23	23.0	-	12 x 3	-	32	17.0	18
LPH-28	28.0	15 x 6	-	-	32	20.5	22
LPH-30	30.5	-	19 x 4	-	33	24.3	24
LPH-33	33.0	19 x 6	-	-	35	24.8	40
LPH-38	38.0	-	25 x 4.5	-	35	28.0	47
LPH-41	41.0	25 x 7	-	-	40	30.0	64

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PIPE REPAIR COUPLINGS

NORMA

A World Leader in the design & supply of sealing, connecting & clamping solutions.



High Specification Stainless Steel Coupling for Repairing Leaks to Pressure Pipe

- Nitrile Sealing Sleeve
- Double Lip Seal Design
- Upto 16 bar Pressure Rating
- Suitable for Metal and Most Plastic Pipes

Pipe Repair Couplings

- Easy assembly and disassembly
- Re-useable
- Patented double-lip seal
- Standard steel strip insert
- Suitable for both high pressure and vacuum applications



7788	Min Size mm	Max Size mm
NOR-FGRR355	34.5	35.5
NOR-FGRR429	39	42.9
NOR-FGRR45	43	45
NOR-FGRR488	45.5	48.8
NOR-FGRR549	53.6	54.9
NOR-FGRR576	55	57.6
NOR-FGRR609	57.7	60.9
NOR-FGRR74	72.6	74
NOR-FGRR769	74	76.9
NOR-FGRR85	83	85
NOR-FGRR896	85.1	89.8
NOR-FGRR1029	101	102.9
NOR-FGRR106	103	106
NOR-FGRR111	109	111
NOR-FGRR1154	112	115.4
NOR-FGRR156	153	156
NOR-FGRR170	166	170

Connect Grip Pipe Couplings

- Axial pipe coupling for connecting unrestrained metal pipes
- Strip insert included as standard for seal protection
- Unique double lip sealing system
- Progressive locking effect
- Rapid installation time
- Up to 16 bar (nominal) pressure rating



stainless steel

Clamps Supplied in W2 Material

7788	Min Size mm	Max Size mm
NOR-05788400026	26.4	27.5
NOR-05788400033	33	34.3
NOR-05788400048	47.6	50.5
NOR-05788400060	59.5	61
NOR-05788400076	75.2	77
NOR-05788400088	87	89.9
NOR-05788400114	113	115
NOR-05788400139	138.1	141.6
NOR-05788400168	166.5	170.1
NOR-05778400219	216	221

Connect Flex Pipe Couplings

- Axial pipe coupling for connecting restrained metal and/or plastic pipes
- Strip insert included as standard for seal protection
- Unique double lip sealing system
- Accommodates changes in pipe length and misalignment
- Rapid installation time
- Up to 16 bar (nominal) pressure rating



stainless steel

Clamps Supplied in W2 Material

7788	Min Size mm	Max Size mm
NOR-05738400026	26.5	27.4
NOR-05738400033	33	34.3
NOR-05738400042	41.7	43
NOR-05738400048	47.6	50.5
NOR-05738400060	59.5	61
NOR-05738400076	75.2	77
NOR-05738400088	87	89.9
NOR-05738400114	113	115.5
NOR-05738400139	138.1	141.6
NOR-05738400168	166.5	170.1
NOR-05738400180	178	182
NOR-05738400193	192	196
NOR-05738400206	202	208
NOR-05738400219	216	221
NOR-05738400267	264	269
NOR-05738400355	352	359
NOR-05738400406	402	410
NOR-05738400508	505	510
NOR-05738400609	606	613

CIRCLIPS KITS

MIKALOR

Circlip Kits

- NBR 70 material
- 1mtr lengths various sizes
- Cutting and bonding accessories included



Assorted, 140 Pieces

5556	Description
0350003-8	External Circlips
0350004-6	Internal Circlips

Ref 0350003-8

Ø Nominal	Quantity	Ø Nominal	Quantity	Ø Nominal	Quantity
–	–	–	–	24	20
5	200	15	100	25	20
8	200	16	100	28	20
9	200	17	50	30	20
10	200	18	50	30	20
11	100	19	50	38	10
12	100	20	50	40	10
13	100	21	50	42	10
14	100	22	20	45	10

Ref 0350004-6

Ø Nominal	Quantity	Ø Nominal	Quantity	Ø Nominal	Quantity
–	–	–	–	30	20
8	200	17	100	32	20
9	200	19	100	35	20
10	200	20	50	40	20
12	200	21	50	40	20
13	200	21	50	42	10
14	100	24	50	47	10
15	100	26	50	58	10
16	100	28	20	60	10

TOOL CLIPS, PEN & TOOL HOLDERS

Tool Clips

- Steel Zinc Plated



Closed Type

0108	Min Size mm	Max Size mm
TERR-80.06-2	6	7
TERR-80.10-2	10	12
TERR-80.13-2	13	14
TERR-80.16-2	16	19
TERR-80.19-2	19	21
TERR-80.25-2	25	27
TERR-80.28-2	28	31
TERR-80.38-3	38	40



Open Type

0108	Min Size mm	Max Size mm
TERR-81.06-2	6	7
TERR-81.10-2	10	12
TERR-81.16-2	16	19
TERR-81.19-2	19	21
TERR-81.25-2	25	27
TERR-81.38-3	38	40

Worm Drive Clips

- Powergrip range of high performance hose clamps manufactured to BS5315 - 1991 standard
- Kitemark accredited
- Mild steel with Alu-zinc coating for improved corrosion resistance



Mild Steel

7777	Size Ref	Min Size mm	Max Size mm
WDC000	000	9.5	12
WDCM00	M00	11	16
WDC00	00	13	20
WDC0	0	16	22
WDC0X	0X	18	25
WDC1A	1A	22	30
WDC1	1	25	35
WDC1X	1X	30	40
WDC2A	2A	35	50
WDC2	2	40	55
WDC2X	2X	45	60
WDC3	3	55	70
WDC3X	3X	60	80
WDC4	4	70	90
WDC4X	4X	85	100
WDC5	5	90	120
WDC6	6	110	140
WDC7	7	130	160
WDC8	8	150	180
WDC9	9	175	205
WDC10	10	200	230
WDC11	11	225	255
WDC12	12	250	288
WDC13	13	275	305

Pen & Pencil Clips

- Nickel Plated Steel
- These are used for Pens, Pencils and Special Measuring Tools in Brief Cases, Tool Boxes and Pockets



0108	Size mm	Type
TERR-90.02-2	7-15	Double

HOSE CRIMPER

Hose Crimper

Crimps 7/8" to 1.1/2" OD hose (1/2" to 1" ID).
This crimper is sold without dies.





Large Bore Hose Crimper

0108
CV501

FT PRO



For **Thinking Sticks**
see page **262**

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 14

Paint, Sprays & Adhesives

14.01 Maintenance Paints 1559-1567

14.02 Maintenance Sprays 1568-1583

14.03 Thread Lockers, Sealants & Adhesives 1584-1587

14.04 Adhesive & Barrier Tapes 1588-1590

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 14 Paint, Sprays & Adhesives

14.01 Maintenance Paints

RUST-OLEUM

1559-1567

- Floor Coating
- Hard Hat® Maintenance Aerosols
- Marking Aerosols
- LEAKSEAL™
- Hard Hat® Topcoats
- CombiColor Paints



14.02 Maintenance Sprays

RUST-OLEUM LOCTITE Ambersil

1568-1583

- X1 Maintenance Sprays
- Professional Lubricants
- Cleaning & Specialist Products
- Lubrication
- Anti-Corrosion
- Inspection/Detection
- Welding
- Food Grade Cleaning & Lubrication
- Moulding Range
- Paint & Surface Preparation
- Paint Marker Pens
- Specialist Products



14.03 Thread Lockers, Sealants & Adhesives

LOCTITE

1584-1587

- Thread Sticks & Threadlockers
- Retainer & Tape
- Sealants
- Super Glue & Adhesives



14.04 Adhesive & Barrier Tapes

Scapa

1588-1590

- Adhesive Tapes
- Barrier Tapes
- Sealants, Fillers & Guns



FAC
Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

MAINTENANCE PAINTS

RUST-OLEUM®

Floor Coating

- A ready to use solution for preparing your surface.
- Removes grease, oil and other contaminations.
- Virtually odour free.
- Non-flammable
- 6-8 m²/l coverage.



EpoxyShield® Cleaner/Degreaser, 5 Litre Tub

0209
RU-2901.5
Tech Sheet 60558

- Creates a surface profile that allows for maximum penetration and adhesion for the EpoxyShield® coatings.
- Uses citric etch formula to avoid producing dangerous acids or fumes.
- Will not harm grass or plants.



EpoxyShield® Etching Solution, 5 Litre Tub

0209
RU-108.5
Tech Sheet 60557

Multi-use epoxy resin repair mortar for concrete or stone. Unequalled hardness and epoxy bonding power. Epoxy Repair Mortar allows fast setting (3-6 hours), granite-hard permanent repairs to be made to badly cracked and worn concrete or stone floors. For use where conventional mortar or other fillers will loosen or fail. Anglo Epoxy Repair Mortar is virtually indestructible and ideal for repairs to factory floors, driveways, worn and broken steps, garage floors, sills, grouting in bolts and railings etc.



Epoxy Repair Mortar

0209	Volume Kilograms
RUS-5180.2.5	2.5
RUS-5180.5.0	5
RUS-5180.25	25
Tech Sheet 60560	

Speed Patch gives a durable, fast setting repair to damaged floors, frost spalled, eroded and cracked concrete, steps, troughs, ramps covering etc.



Speed Patch

0209	Volume Kilograms
RUS-5150.1	10
RUS-5150.2	20
Tech Sheet 71767	

A quick easy way to fill holes in heavily used concrete floors inside and outside. No primer is required - just mix powder with water and pour into the hole. The rapid setting concrete repair bonds to damp or dry surfaces and can be applied at a thickness from feather edge to 100mm.



Speed Patch Pourable Grade 25kg

0209
RUS-AXPSP25
Tech Sheet 60562

Speed Screed smooths uneven, damaged or worn concrete floors. A pour on durable re-surfacing material Suitable for interior or exterior use.



Speed Screed 25kg

0209
RUS-AXSS25
Tech Sheet 60563

- Solvent-free Epoxy (2 part)
- For repairing fine cracks up to 3mm wide.
- Dry in 3-4 hours.

Coverage:
25 linear metres
(2mm wide, 5mm deep).



EpoxyShield® Fine Crack Repair Mortar, 500ml Tub

0209
RU-203010.05
Tech Sheet 60628

- Mineral-Acrylic.
- Easy to use - Add water, stir and ready.
- Traffic allowed after 24hrs
- 10kg (1 part) 0.4m².
- Recoatable after 48 hrs.

Please note: to be recoated with 7100 Floor coating.



EpoxyShield® Concrete Repair Mortar, 10kg Tub

0209
RU-203012.10
Tech Sheet 60559

Rust-Oleum® Asphalt Repair is a durable bitumen-based patch repair product for use on exterior potholed asphalt and concrete. Ideal for potholes in roads, car parks, paths and other bituminous and concrete surfaces.

- Simple to use - no mixing required
- Repairs can be driven over immediately after application
- Ideal for repairs 10mm – 70mm
- Coverage approx. 0.5m² per 25kg at 24mm thick
- Withstands heavy traffic



Asphalt Repair 25kg

0209
RUS-5410.25
Tech Sheet 60561

MAINTENANCE PAINTS

RUST-OLEUM®

Floor Coating

- For use on concrete, metal and wood.
- Single pack, pedestrian grade floor coating
- Great gloss appearance.
- High film build in one coat
- Touch dry after 6 hours.
- Resistant to oil, lubricants and petrol.
- Easy to apply with brush and roller.
- 8m² per litre (two coats recommended).
- Easy to clean with a neutral cleaner.

Important: Not suitable for car traffic or for car park areas



Standard Colours, 5 Litre

0209	Colour	RAL Code
RUS-7179	Black	RAL 9005
RUS-7181	Light Grey	RAL 7035
RUS-7168	English Red	-
RUS-7137	Moss Green	RAL 6005
Tech Sheet 60565		



Anti-slip Version, Standard Colours, 5 Litre

0209	Colour	RAL Code
RUS-7182NS	Steel Grey	RAL 7001
RUS-7179NS	Black	RAL 9005
RUS-7181NS	Light Grey	RAL 7035
RUS-7110NS	Transparent	-
Tech Sheet 60565		

Floor Coating Colours (7100 & 7100NS)

Standard Colours

RAL 7001 7182/7182NS

● **RAL 1015** 7142

RAL 9005 7179/7179NS

RAL 7035 7181/7181NS

English Red 7168

Transparent 7110/7110NS

● **RAL 6005** 7137

● Anti-slip version not available.

- Slip resistant aggregate is pre-mixed in the coating.
- Unique uniform appearance.



Line Marking & Safety Colours, 5 Litre

0209	Colour	RAL Code
RUS-7124	Traffic Blue	RAL 5017
RUS-7192	White	RAL 9010
RUS-7144	Traffic Yellow	RAL 1023

Anti-slip Version, Line Marking & Safety Colours, 5 Litre

0209	Colour
RUS-7144NS	Traffic Yellow

Floor Coating Colours (7100 & 7100NS)

Line Markings & Safety Colours

Traffic Blu **White** **Traffic ellow**

Dustproofs, seals and transforms drab concrete floors. It is easy to apply and dries quickly to a tough, mid gloss finish



Polyurethane Floor Paint Single Pack, 5 Litre

0209	Colour
RUS-AFP5WHI	White
RUS-AFP5BUF	Buff
RUS-AFP5MGY	Mid Grey
RUS-AFP5LGY	Light Grey
RUS-AFP5DGY	Dark Grey
RUS-AFP5BLU	Mid Blue
RUS-AFP5GRN	Mid Green
Tech Sheet 60567	

Asphalt restorer provides an 'as new' appearance that will mask old line markings and repairs and will hide ingrained dust from building works, etc.



Asphalt Restorer, 5 Litre

0209	Colour
RUS-AAR5	White
Tech Sheet 60566	

A tough, flexible acrylic paint for tarmac or asphalt.

Colour and protect asphalt and tarmac drives, paths and playgrounds using this easy to apply coating.

Solvent free.



Tarmacoat, 5 Litre

0209	Colour
RUS-6192.5	White
RUS-6181.5	Light Grey
RUS-6183.5	Mid Grey
RUS-6168.5	Tile Red
RUS-6136.5	Mid Green
RUS-6143.5	Signal Yellow
Tech Sheet 60564	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MAINTENANCE PAINTS

RUST-OLEUM®

Hard Hat® Maintenance Aerosols

- The quick anti-rust protector
- Ready to recoat after just 10 minutes, to handle after 30 minutes
- For new or slightly rusty surfaces
- Penetrates deeply into the surface and does not give rust a chance
- Lead and chromate free



Anti-rust Primer, 500ml

0209	Colour
RUS-2169	Red
RUS-2182	Grey
Tech Sheet 60575	

PORTWEST



For **Disposable Gloves** see page **1758**

Hard Hat® Galvanizing Zincs

- Cathodic protection of bare and galvanized steel
- Resists 500 hours of salt spray testing (DIN 50021 SS)
- To recoat within one hour, brush version after 4 hours
- To recoat with Hard Hat® metallic sprays



Galva Zinc

0209	Volume Grams	Volume Millilitres
RUS-1085.1	1000	-
RUS-2185	-	500
Tech Sheet 60572		

- The super-fast zinc primer
- Tack free after just 5 minutes, to handle after 10 minutes
- Ideal for production and construction environments
- Resists 400 hours of salt spray testing (DIN 50021 SS)



Galva Expresse, 500ml

0209
RUS-2180
Tech Sheet 60576

- Zinc coating with sparkling aluminium particles
- The best compromise between a zinc spray and an aluminium spray
- Resists 340 hours of salt spray testing (DIN 50021 SS)



Galva Zinc-aluminium

0209	Volume Grams	Volume Millilitres
RUS-1017.1	1000	-
RUS-2117	-	500
Tech Sheet 60571		

- Appearance similar to new galvanized
- For touching up new galvanized
- Resists 310 hours of salt spray testing (DIN 50021 SS)
- Lower zinc contents, more aluminium



Galva Plus, 500ml

0209	Colour
RUS-2120	Zinc Gloss
Tech Sheet 60574	

	2185/1085.1 Galva Zinc	2180 Galva Expresse	2117/1017.1 Galva Zinc-Alu	2120 Galva Plus
Appearance	Matt Grey	Matt Grey	Sparkling Aluminium	Aluminium Gloss
Zinc %	90%	68%	80%	54%
Aluminium %	0%	1%	10%	23%
Salt Spray Test	500 hrs	400 hrs	340 hrs	310 hrs
Tack Free	10 min / 15 min	5 min	20 min / 30 min	15 min
To Handle	30 min / 2 hrs	10 min	60 min / 3 hrs	60 min
Heat-resistant	450°C / 100°C	350°C	450°C / 100°C	150°C
Main Advantage	Best protection	Quick drying	Good protection and finish	Finish like new galvanised

Fluid-Air Components Ltd

MAINTENANCE PAINTS

RUST-OLEUM®

Hard Hat® Topcoats

For use on engines, heat cannons, steam pipes, boilers, radiators, vents, barbecues and stoves.
750°C maximum temperature for short periods.





Heat-resistant, 500ml

0209	Colour
RUS-7778	Black Satin Gloss
RUS-7715	Aluminium
Tech Sheet 60579	

Adheres to metal, wood, concrete, tile floors and parquet Very quick drying (5 to 10 minutes).
For use on floors, steps, thresholds, etc
Makes every surface non-skid in a second.



Anti-slip, 500ml

0209	Colour
RUS-2410	Transparent
RUS-2444	Safety Yellow
RUS-2479	Black

TIP: for maximum efficiency of fluorescen colours, spray over matt white and finish with Hard Hat® clear coat.





Fluorescent Top Coats, 500ml

0209	Colour
RUS-2222	Blue
RUS-2255	Orange
RUS-2264	Red
RUS-2242	Yellow
Tech Sheet 60578	

Hard Hat® Metallics

Metallic sprays combine a bright metallic appearance with the durable protection of a standard topcoat.

- Gloss or sparkling metallic appearance
- To restore the metallic appearance
- For use on bare metal, galvanized, zinc primers or anti-rust primers





Durable Protection, 500ml

0209	Colour
RUS-2111	Sparkling Aluminium
RUS-2115	Silver Aluminium
Tech Sheet 60577	

- Greater abrasion resistance
- Better anti-corrosion properties than other metallics
- Excellent UV resistance (does not discolour)
- Resists acids, chemicals and alkalis



Stainless Steel Coating, 500ml

0209
RUS-2116
Tech Sheet 60577

Marking Aerosols

- For marking difficult substrate
- Best hiding power, weather-resistant and watertight
- For use on metal, concrete, asphalt, gravel, soil, grass, wood, etc
- Works even on slightly wet surfaces
- Upside down spraying system
- Up to 70m marking (3cm width)



Hard Hat® High Performance, 500ml

0209	Colour	RAL Code
RUS-2358	Red Orange	-
Tech Sheet 60580		

- For use with line applicators
- Adjustable line width 5 to 10cm
- Light traffic possible after just 4 hours
- Adheres to asphalt, concrete, grass, metal and wood, etc
- Up to 120m marking (5cm width).



Hard Hat® Line Marking, 500ml

0209	Colour
RUS-2391	White
Tech Sheet 60581	

LEAKSEAL™

LEAKSEAL™ is an easy-to-use, rubberised protective coating designed to fill and seal leaks and cracks.
It provides a watertight, flexible seal

- Seals leaks and cracks
- Watertight semi-smooth finis
- Can be top-coated with latex or oil-based paints
- For use on metal, aluminium, PVC, concrete, masonry, asphalt roofing materials, etc



Flexible Rubber Coating

0209	Colour	Volume Millilitres
RUS-3410	Transparent	500
RUS-3478	Black	500
RUS-3490	White	500
Tech Sheet 20132		

Pipeline Identification Colour

Pipe Contents	RAL Code	CombiColor® Metal Protection	Hard Hat® Aerosols
Gas	RAL 1004	7349	2149
Fire Fighting	RAL 3000	7365	2165
Air	RAL 5012	7323	2123
Combustable Liquids	RAL 8001	7373	2173
Acids & Alkalis	RAL 4001	7363	2163
Water	RAL 6010	7334	2138
Other Liquids	RAL 9005	7379	2179
Steam	RAL 9006	7315	2114

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

MAINTENANCE PAINTS

RUST-OLEUM®

Hard Hat® Topcoats

- Goes further: more paint in the can, resulting in a higher coverage: 3-4m².
- One Hard Hat® aerosol equals up to 2-3 standard aerosols.
- Works quicker: a higher film build without drips or runs.






Advantage, 500ml

0209	Colour	RAL Code
RUS-2114	Aluminium White	RAL 9006
RUS-2123	Light Blue	RAL 5012
RUS-2124	Signal Blue	RAL 5005
RUS-2125	National Blue	–
RUS-2126	Gentian Blue	RAL 5010
RUS-2127	Ultramarine Blue	RAL 5002
RUS-2128	Sapphire Blue	RAL 5003
RUS-2133	Yellow Green	RAL 6018
RUS-2134	Signal Green	RAL 6032
RUS-2135	Reseda Green	RAL 6011
RUS-2136	Emerald Green	RAL 6001
RUS-2137	Moss Green	RAL 6005
RUS-2138	Grass Green	RAL 6010
RUS-2141	Pearl White	RAL 1013
RUS-2142	Light Ivory	RAL 1015

0209	Colour	RAL Code
RUS-2143	Light Yellow	RAL 1018
RUS-2144	Traffic Yellow	RAL 1023
RUS-2145	Melon Yellow	RAL 1028
RUS-2146	Cole Seed Yellow	RAL 1021
RUS-2147	Signal Yellow	RAL 1003
RUS-2148	Safety Yellow	RAL 1007
RUS-2149	Golden Yellow	RAL 1004
RUS-2151	Pastel Orange	RAL 2003
RUS-2152	International Orange	RAL 2002
RUS-2154	Yellow Orange	RAL 2000
RUS-2163	Red Lilac	RAL 4001
RUS-2165	Bright Red	RAL 3000
RUS-2166	Traffic Red	RAL 3020
RUS-2174	Signal Brown	RAL 8002

0209	Colour	RAL Code
RUS-2176	Black Satin Gloss	RAL 9005
RUS-2178	Black Matt	RAL 9005
RUS-2179	Black	RAL 9005
RUS-2181	Light Grey	RAL 7035
RUS-2184	Steel Grey	RAL 7001
RUS-2186	Marine Grey	RAL 7005
RUS-2187	Stone Grey	RAL 7032
RUS-2189	Anthracite Grey	RAL 7016
RUS-2190	White Matt	RAL 9010
RUS-2192	White	RAL 9010
RUS-2193	White Satin Gloss	RAL 9010
RUS-2194	Cream	RAL 9001
RUS-2500	Transparent	–
	Tech Sheet 10532	

Hard Hat® Colours



Machine Colours

2126 Ford Blue, agricultural machinery
2133 Deutz Green, agricultural machinery
2136 John Deere Green, agricultural machinery
2143 John Deere Yellow, agricultural machinery
2145 Caterpillar Orange, excavators, dredging cranes
2148 JCB excavators
2152 Linde Orange, excavators
2154 STILL Orange, fork-lift trucks
2165 Massey Ferguson and New Holland Red, agricultural machinery
2186 Deutz Grey, agricultural machinery

Identification Colours

(See pipeline identification colours on page 796)

2114 Steam
2123 Air
2138 Water
2149 Gas
2163 Acids
2173 Liquid spirits
2179 Other liquids

Safety Colours

2126 Fresh water
2134 Safe place, escape routes, showers, exits
2143 Danger
2148 Take care/warning of danger, poison, explosion, radio-active radiation
2165 Stop/forbidden/fire extinguishe

Fluid-Air Components Ltd

MAINTENANCE PAINTS

RUST-OLEUM®

CombiColor Paints

- The first coating t combine the functions of a rust-preventive primer and gloss finish in one
- One coat maintenance system for metal, can be applied directly to rust
- Long-lasting protection
- Interior and exterior use
- Sag resistant, no brush strokes
- White spirit dilutable
- Low odour
- Applicable from +5°C
- Remains flexible under all conditions







Smooth, 750ml

0209	Colour	RAL Code
RUS-7314	Gold	-
RUS-7315	White Aluminium	RAL 9006
RUS-7323	Light Blue	RAL 5012
RUS-7326	Gentian Blue	RAL 5010
RUS-7328	Ultramarine Blue	RAL 5002
RUS-7329	Steel Blue	RAL 5011
RUS-7339	Fir Green	RAL 6009
RUS-7342	Light Ivory	RAL 1015
RUS-7343	Light Yellow	RAL 1018

0209	Colour	RAL Code
RUS-7348	Safety Yellow	RAL 1007
RUS-7349	Golden Yellow	RAL 1004
RUS-7365	Bright Red	RAL 3000
RUS-7366	Traffic Red	RAL 3020
RUS-7377	Chestnut Brown	RAL 8011
RUS-7379	Black	RAL 9005
RUS-7381	Light Grey	RAL 7035
RUS-7382	Steel Grey	RAL 7001
RUS-7386	Navy Grey	RAL 7005
RUS-7392	White	RAL 9010
Tech Sheet 10369		

Smooth, 2.5 Litre

0209	Colour	RAL Code
RUS-7315-2.5L	White Aluminium	RAL 9006
RUS-7322-2.5L	Marlin Blue	-
RUS-7326-2.5L	Gentian Blue	RAL 5010
RUS-7328-2.5L	Ultramarine Blue	RAL 5002
RUS-7335-2.5L	Reseda Green	RAL 6011
RUS-7336-2.5L	Emerald Green	RAL 6001
RUS-7337-2.5L	Moss Green	RAL 6005
RUS-7342-2.5L	Light Ivory	RAL 1015
RUS-7346-2.5L	Cole Seed Yellow	RAL 1021
RUS-7348-2.5L	Safety Yellow	RAL 1007
RUS-7349-2.5L	Golden Yellow	RAL 1004
RUS-7354-2.5L	Yellow Orange	RAL 2000
RUS-7365-2.5L	Bright Red	RAL 3000
RUS-7366-2.5L	Traffic Red	RAL 3020
RUS-7377-2.5L	Chestnut Brown	RAL 8011
RUS-7379-2.5L	Black	RAL 9005
RUS-7381-2.5L	Light Grey	RAL 7035
RUS-7382-2.5L	Steel Grey	RAL 7001
RUS-7386-2.5L	Marine Grey	RAL 7005
RUS-7392-2.5L	White	RAL 9010
Tech Sheet 10369		

CombiColor Colours

7314	**RAL 9006** 7315 ●	7322	**RAL 5012** 7323 ●	**RAL 5015** 7324	**RAL 5010** 2126	**RAL 5002** 7328	**RAL 5011** 7329	**RAL 6018** 7333	**RAL 6010** 7334 ●	**RAL 6011** 7335	**RAL 6001** 7336	**RAL 6005** 7337	**RAL 6009** 7339	**RAL 1015** 7342	**RAL 1018** 7343
RAL 1021 7346	**RAL 1007** 7348	**RAL 1004** 7349 ●	**RAL 2000** 7354	**RAL 4001** 7363 ●	**RAL 3000** 7365 ●	**RAL 3020** 7366	**RAL 8001** 7373 ●	**RAL 8011** 7377	**RAL 9005** 7379 ●	**RAL 7035** 7381	**RAL 7001** 7382	7383	**RAL 7005** 7386	**RAL 9010** 7392	7330

Machine Colours

7326 Ford Blue
7333 Deutz Green
7336 John Deere Green
7343 John Deere Yellow
7348 JCB excavators
7354 STILL Orange
7365 Massey Ferguson
7365 New Holland Red
7386 Deutz Grey

● Identification Colours

(See pipeline identification colours on page 796)

7315 Steam
7323 Air
7334 Water
7349 Gas
7363 Acids
7365 Fire-fightin
7373 Liquid spirits
7379 Other liquids

⚠ Safety Colours

7326 Fresh water
7343 Danger
7348 Danger warning of poison, explosion, radio-active radiation
7365 Stop/forbidden/fire extinguishe

Fluid-Air Components Ltd

MAINTENANCE PAINTS

RUST-OLEUM®

CombiColor Paints

CombiColor Colours

Satin


7375


7394

Matt


7378


7390

Hammertones Colours

750ml & 2.5 Litre Tin


7321


7332


7345


7362


7364


7374


7376


7384


7388



Satin, 750ml

0209	Colour	RAL Code
RUS-7375	Black	RAL 9005
Tech Sheet 10369		

Satin, 2.5 Litre

0209	Colour	RAL Code
RUS-7375-2.5L	Black	RAL 9005
RUS-7394-2.5L	White	RAL 9010
Tech Sheet 10369		

Matt, 750ml

0209	Colour	RAL Code
RUS-7378	Black	RAL 9005
Tech Sheet 10369		

Matt, 2.5 Litre

0209	Colour	RAL Code
RUS-7378-2.5L	Black	RAL 9005
RUS-7390-2.5L	White	RAL 9010
Tech Sheet 10369		

With their masking effect, hammertone finishes are ideal for use on steel constructions, machines, cable channels, electric tools, work and switch boxes, ventilation ducts and other surfaces requiring a glossy and hammertone look.



Hammertones, 750ml

0209	Colour
RUS-7338	Dark Green
RUS-7345	Gold
RUS-7362	Copper
RUS-7374	Brown
RUS-7388	Dark Grey
Tech Sheet 10369	

Hammertones, 2.5 Litre

0209	Colour
RUS-7321-2.5L	Light Blue
RUS-7332-2.5L	Light Green
RUS-7376-2.5L	Black
RUS-7384-2.5L	Light Grey
RUS-7388-2.5L	Dark Grey
Tech Sheet 10369	

CombiColor Primers & Thinners

- Recoatable after 2 hours
- Red for dark coloured topcoats
- Grey for light coloured topcoats
- Lead and chromate free
- For even longer anti-rust protection





Anti-corrosion Primer, 750ml

0209	Colour
RUS-3369	Red
RUS-3380	Grey
Tech Sheet 10369	



Anti-corrosion Primer, 2.5 Litre Tin

0209	Colour
RUS-3369-2.5L	Red
RUS-3380-2.5L	Grey
Tech Sheet 10369	

CombiColor coatings are ready for immediate use with brush or roller. For spray application however it is advised to use a CombiColor thinner. The thinners are ideal for surface preparation as well.



Thinners, 1 Litre

0209	To Suit
RUS-7301.1	Smooth
Tech Sheet 10369	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

X1 MAINTENANCE SPRAYS

RUST-OLEUM®



X1 Cutting/Tapping Spray

500ml

0209
RUS-1611
Tech Sheet 20108

X1 Multi Purpose Welding Spray

500ml

0209
RUS-1613
Tech Sheet 20110

X1 Silicone Spray

500ml

0209
RUS-1615
Tech Sheet 20112

X1 Chain Drive Spray

500ml

0209
RUS-1612
Tech Sheet 20109

X1 White Grease Spray

500ml

0209
RUS-1617
Tech Sheet 20115

PROFESSIONAL LUBRICANTS

WD-40

WD-40 Lubricant

- Cleans – WD-40's ultra-high surface attraction enables it to get under dirt, grime and grease to clean and dissolve adhesive
- Displaces moisture – WD-40 covers surfaces and microscopic irregularities to eliminate moisture and dry out electrical systems



100ml Can

9036
44201

- Penetrates – WD-40's super penetrating action loosens stuck, frozen or rusted metal parts
- Lubricates – WD-40 contains no silicone or other additives that attract dust and dirt which means it clings to moving parts preventing them from jamming



450ml Can with Smart Straw

9036
44037

- Protects – WD-40 deposits corrosion resistant ingredients to shield metal surfaces against moisture and rust



600ml Can

9036
44116



5 Litre with Spray Applicator

9036
44506



25 Litre Plastic Drum

9036
44025

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CLEANING & SPECIALIST PRODUCTS

7063 Cleaner & Degreaser

General parts cleaner which leaves no residue – ideal for use prior to adhesive bonding and sealing applications. Compatible with metal, glasses rubber, most plastics and painted surfaces.

- Clean products prior to using Loctite adhesives/sealants



0753	Volume Millilitres
LOC-195814	400
Tech Sheet 67949	

7840 Cleaner & Degreaser

A concentrated, biodegradable cleaner/degreaser that contains no hazardous solvents and dilutes with water to meet a wide range of industrial cleaning applications.

- Typical applications for this product include engines, motors, castings, valves, bearings, tanks, machinery, exterior siding, windows, carpets, concrete floors, asphalt, vehicles etc
- Substances it can remove include grease, lubricants, cutting oils, fuel oils, tar, road salt, light carbon, food stains, wax, animal fat, mildew and soot
- This product has a pine odour but is also available fragrance-free



0753	Volume Millilitres
LOC-235330	750
Tech Sheet 67950	

7850 Fast Orange Hand Cleaner with Pumice

Natural hand cleaner made from Citrus rinds. Contains no synthetic solvents, mineral oils or petroleum distillate. Contains fine pumice for deep cleansing


- Contains Jojoba oil, lanolin and aloe to moisturise the skin
- pH balanced
- Easy pump dispenser
- Biodegradable



0753	Volume
LOC-234228	400ml
LOC-234258	3 Litres
Tech Sheet 67951	

8040 Freeze & Release

- This product is a special mineral oil formulation to free rusted, corroded and seized parts
- The shock-freezing effect will cool parts instantly down to -43°C and cause microscopic cracks in the layer of rust
- This allows the lubricating ingredients to wick directly into the rust by capillary action
- Released parts remain lubricated and protected from corrosion



Lubricant

0753	Volume Millilitres
LOC-760225	400
Tech Sheet 67952	

Superlube Oiler



0753	Volume Millilitres
LOC-399422	7

Manual Hand Gun

- 50ml Dual cartridge application
- Manually operated dispenser
- Used for 1:1 and 2:1 mix ratio products
- Cartridges for use with this gun are 4090 and 3430 adhesives

Cartridges not included



0753
LOC-267452

PORTWEST



For **Knee Protection** see page **1759**

Fluid-Air Components Ltd



FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

CLEANING

Amberclens Anti-static Foaming Cleaner

Use to remove general grime and soiling on all hard surfaces or on upholstery to gently lift out grime. Particularly effective as a post-maintenance cleaner for removing finger marks and oil residues. Anti-static formulation inhibits dust attraction.



0229	Volume
6160001000	400ml
6160001200	750ml

Tech Sheet 20636

Ambersolv Citrus Based Foaming Cleaner

Formulated from a blend of high-grade citrus oils and surfactants. An ideal alternative to traditional solvents and highly alkaline cleaners. Suitable for use in industrial, aerospace and general industrial applications.
Biodegradable, water-based formulation.
Non-flammable.



0229	Volume
6160005000	400ml
6330061005	5 Litre

Tech Sheet 20637

Amberklene FE10

General degreasing of machinery including chains, gears, cogs, drives, motors, bearings, and more. Particularly suitable for removing grease from bearing housings and gear teeth and copper paste from threaded fasteners.
Also used for stain removal on textiles.



Fast Drying Solvent

0229	Volume Millilitres
6130002500	400

Tech Sheet 20638

Amberklene ME20

For tough and old grease deposits which require a longer contact time. Use on pumps, gearboxes, drives exposed to the elements or with longer service intervals.



Heavy-duty Solvent

0229	Volume Millilitres
6130002600	400

Tech Sheet 20639

Amberklene LO30

Use for general degreasing on bearings, drive, motors, gears and chains but without the traditional odour associated with solvent degreasers.



Low Odour Solvent

0229	Volume
6130002700	400ml
6230003705	5 Litre

Tech Sheet 20640

BA40 Solvent

For removal of uncured sealants and adhesives, particularly during aircraft maintenance. Extremely fast evaporating solvent degreaser.



Water Soluble Solvent

0229	Volume Millilitres
6130002800	400

Tech Sheet 20641

Ambertron Contact Cleaner

For use on critical electronic components where only the purest contact cleaners can be used. Removes light oils and contamination safely on PCB's, relays, all electrical contacts, switches and more.



0229	Volume Millilitres
6130001500	400

Tech Sheet 10528

Lec-Klene

For use on electronic and aviation components requiring a powerful yet ultra-safe solvent degreaser.Powerful solvent degreaser that removes oil, grease, grime, wax and tar.
Suitable for use in confined or enclosed spaces, and areas where high flash point is required.



High Flash Point Solvent

0229	Volume Millilitres
6130002900	400

Tech Sheet 20642

Ambersolv SB1

Dissolves grease and grime from bearings, removes old lubricant from drives, slides, and guide rails.
Effective on a wide range of soiling such as oil, grease, tar, bitumen, silicones, rubber-based adhesives, oil-based paints, inks and dyes.



Citrus Based Solvent Cleaner

0229	Volume
6190003000	400ml
6330062005	5 Litre

Tech Sheet 20644

Fluid-Air Components Ltd

CLEANING

Brake Cleaner

Brake Cleaner is a strong non-chlorinated solvent blend to quickly and safely remove brake fluid, grease, oil and other contaminants from brake and clutch parts.



0229	Volume Millilitres
6170030000	500
Tech Sheet 20645	

GS5 Gasket Stripper

Removes in-place gaskets from engines, gearboxes, drive and chain enclosures.

Use to remove thread locking compounds, silicone sealant, and mastics.



0229	Volume Millilitres
63700M7028	400
Tech Sheet 20646	

Fast Clean 200 & 201

Advanced degreasing solvent that is both exceptionally fast drying and very powerful.



Super Fast Degreaser

0229	Volume Millilitres
63700M7019	400
Tech Sheet 20648	

EPP Hard Surface Cleaner

An environmentally preferred product that can be used on all floors as a cleaner to remove grease, grime, bitumen and other soiling types.

Removes a wide variety of soiling including: grease, oil, wax, and polish.



0229	Volume Litres
6330007005	5
Tech Sheet 20649	

N F Precision Cleaner

An advanced solvent contact cleaner that is non-flammable and ideal for servicing lifts and critical electronics that cannot be switched off.

Excellent materials compatibility. Specifically formulated for cleaning delicate electronics.



Non-flammabl

0229	Volume Millilitres
6130001560	400
Tech Sheet 20651	

IPA

Ideal for cleaning optical devices, switches and PCB's. Use where a safe solvent is required on delicate electronics.

Excellent material compatibility, safe to use on plastics and rubber.



Isopropyl Alcohol Electronic Cleaning Solvent

0229	Volume Millilitres
6130012000	400
Tech Sheet 20652	

CCL100

A versatile product for use on electrical contacts and switchgear.

Cleans, lubricates and prevents corrosion all in one application.



Contact Cleaner & Lubricant

0229	Volume Millilitres
63700M7018	400
Tech Sheet 20653	

EPP Degreaser

Use to degrease components when a regular solvent cleaner cannot be used. Use on gearboxes, hydraulic systems, open gears, chains and pumps to remove a variety of heavy soiling types.

An environmentally preferred product that is a non-flammable water based degreaser.

- 750ml are trigger bottles
- 5 Litre are bulk tubs



Biodegradable Cleaner Degreaser

0229	Volume
6060001570	750ml
6330001005	5 Litre
Tech Sheet 20654	

Universal Screen Cleaner

Removes grime and finger marks from control VDU s, online status screens and all monitors.
Ideal for cleaning thermal imaging camera screens.

Can be used on most screen types including LCD, TFT and Plasma.



0229	Volume Millilitres
6130004050	400
Tech Sheet 20655	

Fluid-Air Components Ltd

CLEANING

Anti-static Spray

Use on plastic surfaces prone to static charge prior to maintenance or as part of a static control program.



0229	Volume Millilitres
6130004020	400
Tech Sheet 20656	

Invertible Air Duster

Non-flammable dry air blast for removing loose dry contamination from electronics.

360° Spray system for all angle use.



0229	Volume Millilitres
6130004000	200
Tech Sheet 20657	

Ambersil Wipes

Super high absorbency hand wipes over-layered with an effective polymer web to give all the cleaning power of pumice without the scratching.

Contains anti-pathogen agents highly effective against common bacteria and viruses such as Weil's Disease, MRSA, Salmonella, Listeria and E. Coli. Passes BS 12054 (hand sanitising) and BS 1276 (surface sanitising).



High Absorbency Cleaning Wipes

0229	Quantity
6330272100	100
Tech Sheet 20658	

Glass Cleaner

Use on all glazed and ceramic surfaces to remove light soiling and marks.



0229	Volume Millilitres
6160004000	400
Tech Sheet 20660	

Multi-surface Polish

Developed to cut through and remove industrial soiling which is more tenacious than domestic or office soiling



0229	Volume Millilitres
6190010000	400
Tech Sheet 20661	

Air Duster

A liquefied propellant which provides a powerful blast for the easy removal of dust and loose contamination from precision equipment such as cameras and printed circuit boards to general cleaning in areas where the use of a liquid cleaner may be undesirable.

Non-flammable



0229	Volume Millilitres
6130012100	400
Tech Sheet 20662	

Label Remover

Removes all types of self-adhesive labels from equipment.

Fast and effective removal of self-adhesive paper labels, reducing scraping.



0229	Volume Millilitres
6190012000	200
Tech Sheet 20663	



For **Cleaning Stations** see page **1764**

Fluid-Air Components Ltd

LUBRICATION

40+

A true multi-purpose treatment: it can be used as a penetrant, a lubricant, an anti-corrosion coating to prevent flash rusting on steel, and as a moisture displacer in high humidity environments.

- 400ml are aerosols
- 5 Litre are bulk tubs



Multi-purpose, Industrial Protective Lubricant

0229	Volume
6130007000	400ml
6230005100	5 Litre

Tech Sheet 20664

AGL1

Use to displace moisture and protect electrical contacts from corrosion.

Provides precision lubrication by its thin, high dielectric strength, lubricating film



Greaseless Lubricant

0229	Volume Millilitres
6130009000	400

Tech Sheet 20665

Amberglide

Use where temperatures regularly reach a sustained 120°C to 160°C such as photocopier fuser units and moving parts near heat sourced e.g. conveyors, sideways and chutes. Particularly suitable to rapidly oscillating packaging equipment arms.

Cleans, lubricates and waterproofs.



PTFE Lubricant

0229	Volume Millilitres
6130013000	400

Tech Sheet 20666

AMS4

Use on high voltage and 3-phase connector casing and joints to seal against moisture ingress, assist assembly/ disassembly and prevent cracking of rubber seals.

Insulates high voltage parts against leaking or arcing, Waterproofs electronics in damp or humid conditions.



Multi-purpose Silicone Grease

0229	Volume Millilitres
6130008500	400

Tech Sheet 20667

Chainspray & FLT Chain Spray

Use on all types of chain and drives including conveyors, door mechanisms, quarry plant, drying ovens doors, and forklift trucks. Ideal for fast moving or exposed chains.

Offers maximum adhesion to chain links with excellent penetration.

Separate version specifically developed for Fork Lift Trucks (500ml).



Chain & Drive Lubricant

0229	Volume Millilitres
6150001100	400
6170030010	500

Tech Sheet 20668

Gear & Wire Rope

Ideal for open gears in dusty environments (e.g. quarries) where the dry film will not attract dust. Use all wire ropes subjected to tension and/or movement.

Forms a dry non-peeling film that overcomes the limitations of grease lubrication and pressure cushions.



Heavy-duty Lubricant

0229	Volume Millilitres
6150007000	400

Tech Sheet 20669

Rust Flash

For use on all seized fasteners, particularly those corroded or rusted. Ideal for bolts on equipment located outside and subjected to adverse conditions.

Rust is shock-cooled, cracking it and allowing penetrating oils to work, Very fast acting for rapid job turnaround.



Rust Loosener with Freeze Shock Effect

0229	Volume Millilitres
6150003601	500

Tech Sheet 20670

Penetrating Oil

Use as a highly effective release agent for seized fasteners, particularly bolts and grub screws.

Frees seized components rapidly.

FOOD PROCESSING SAFE



Penetrant for Seized Parts

0229	Volume Millilitres
6150003600	400

Tech Sheet 20671

Dry Film Anti-stick

Use on guide rails on production lines to prevent jams; ideal for use as a non-tainting lubricant on packing and cardboard folding machines.

Forms a dry non-staining film, exhibits excellent friction retardant properties.



Dry PTFE Lubricant

0229	Volume Millilitres
6140003500	400

Tech Sheet 20672

Fluid-Air Components Ltd

LUBRICATION

Copper Anti-seize

Use on threaded fasteners to prevent seizing during prolonged maintenance intervals, in hostile/high humidity environments and areas subjected to high torque and/or temperatures.

Reduces friction and wear, good corrosion protection even in highly corrosive environments, Operational temperature range: -30°C to +1100°C.

- 400ml are aerosols
- 500gm are containers





High Temperature Anti-seize

0229	Volume
6190014010	400ml
6150001030	500g
Tech Sheet 20673	

Silicone Lubricant

Use for plastic-to-plastic lubrication, extra slip on chutes or slides, and on push fit pipes. Can also be used as a general mould release agent or as a cutting aid on paper/textile blades. Use on printing lines to reduce ink adhesion.



General Purpose

0229	Volume Millilitres
6190015000	500
Tech Sheet 20674	

Ambergrease EXL

Use on critical and high load bearings and sliding surfaces. Suitable for use in applications where a longer service interval is required.

Exceptional load carrying capacity: 4-ball weld load >800Kg, Mean Hertz Load 125kg, Timken OK load: 25Kg, Highly visible red, NLGI type 2 grease, Lithium-Calcium Complex thickener.



Extended Life, High Performance Bearing Grease

0229	Volume Millilitres
6150001010	400
Tech Sheet 20675	

Silicone Anti-stick

High concentration silicone lubricant for more demanding applications with higher loads or increased speeds e.g. robotic picking lines, conveyors, pallet guide rails and close tolerance fitting of large bore pipes.

Ideal for use where high standards of purity are essential, helps prevent line jams, inhibits adhesive build up on blades and sealers.



Concentrated Silicone Lubricant

0229	Volume Millilitres
6140001500	400
Tech Sheet 20676	

Dry Moly

Use in higher load applications where PTFE lubricants would fail, but a dry film is still required. Use as a running-in treatment on rolling and sliding bearings.

Use as a lubricant for guides and joints; on wheel bearings on kiln carts; or lubrication of open gears.

Operational temperature range:

-150°C to +400°C.



Molybdenum Disulphide Lubricant

0229	Volume Millilitres
6150002000	400
Tech Sheet 20677	

Multi-lube

Versatile lubricant for use in mechanical handling maintenance, cleans, lubricates and protects against corrosion.



Multi-purpose Lubricant

0229	Volume Millilitres
6170030020	500
Tech Sheet 20678	

White Spray Grease

Ideal for use on automotive door hinges. Use on runners, guide tracks, and other moving parts, NLGI grade 2 grease in an aerosol



Multi-purpose White Grease

0229	Volume Millilitres
6170030040	500
Tech Sheet 20679	

Tufcut

Tufcut is a range of specialist metal cutting lubricants based on a mixture of lubricants, extreme pressure additives and anti-oxidants. The range has been formulated to offer instant, ready-to-use metal machining products that provide exceptional performance in demanding applications. All the products are suitable for use on a wide range of metals, including stainless and high carbon steels where "right first time" results are required



Metal Cutting Lubricant

0229	Volume
6150006000	350ml Liquid
6150005500	400ml Spray
6150006500	300ml Foam
6150006100	500g Compound
Tech Sheet 10365	

Fluid-Air Components Ltd

ANTI-CORROSION



Corrosion Inhibitor

Use on ferrous metal as a long-term protective coating for stored equipment. Film will not harden or crack, forms a 'self repairing' waxy film.
Will not stain or mark components.



Waxy Anti-corrosion Treatment

0229	Volume Millilitres
6190011600	400
Tech Sheet 20680	

Cold Galvanise Spray

Provides Cathodic protection to steel.
Ideal for pipes, housings, and structural metal exposed to the weather.
Sacrificial coating protects metalwork and steels from corrosion.



Zinc-Rich Protective Coating

0229	Volume Millilitres
6190011001	400
Tech Sheet 20681	

Bright Cold Galvanise

Bright, Cold Galvanise weathers naturally, mimicking the natural hot-dip galvanise finish. Barrier coating protects metalwork and steels from corrosion.



Repair Coating for Hot-Dip Steel

0229	Volume Millilitres
6190011501	400
Tech Sheet 20682	

Galva Shine

Offers an exact colour match to aesthetic architectural hybrid zinc galvanised metal supports.Resists weathering, retaining a super bright finish



Aesthetic Protective Coating

0229	Volume Millilitres
6190011510	400
Tech Sheet 20683	

Inox 200

Use on glass pearl blasted stainless steel as a touch-up and anti-corrosion paint. Heat resistant up to 300°C.



Protective Coating for Stainless Steel

0229	Volume Millilitres
6190011513	400
Tech Sheet 20684	

Alu Hi Temp

Use on furnace doors, boiler casings, drying ovens, foundry manipulators, and equipment subjected to continuous high temperatures. Continuous protection up to 600°C.



High Temperature Corrosion Protection

0229	Volume Millilitres
6190011511	400
Tech Sheet 20685	

Zinc Primer

Zinc phosphate primer promotes adhesion of top-coat paint to 'difficult' substrates.
Dry to touch in 30 minutes, dry to paint in 1 hour (recommended 24 hours for best results).



Multi-purpose Metal Primer

0229	Volume Millilitres
6190011512	400
Tech Sheet 20686	

Battery Terminal Protector

Protects battery terminals on forklift trucks, generators, and UPS from wear and corrosion and seals out damp from battery connections.
Highly visible dye gives early warning of acid leakage by changing from yellow to red.



Anti-corrosion Terminal Treatment

0229	Volume Millilitres
6170030050	500
Tech Sheet 20687	

Acrylic Conformal Coating

Apply to PCB's and electronics to protect against arcing, dust, moisture and contamination.
Colourless conformal coating, insulates and seals out moisture and dust, flexible lacquer will not crack or chip.



0229	Volume Millilitres
6130004030	400
Tech Sheet 20688	

SV 100

Apply to electric motors as an insulation and protective coating to the windings.
Insulates all types of electrical systems against high humidity.



Anti-tracking Insulating Film

0229	Volume Millilitres
63700M7036	400
Tech Sheet 20689	

Fluid-Air Components Ltd

INSPECTION/DETECTION

Leak Detector

Spray on gaseous pipes and joins to identify leaks. Ideal for preventative maintenance checks, new installation checks, and on all HVAC systems.

Water-based formulation, no oils, silicones or harmful solvents; no 'run off' hazard, non-flammable and completely odourless.

- 400ml aerosols
- 5 Litre bulk tubs



Water Based

0229	Volume
6190019000	400ml
Tech Sheet 20690	

Flaw Detectors, Cleaner, Penetrant & Developer

Use as a highly accurate check for weld quality. Ideal for use on military vehicle repair, boiler maintenance, and storage tank fabrication.

Fast acting visual results.

Highly effective system that can be used anywhere, simply, and without complicated test equipment.

Can be applied direct to the component to be tested without the need for dismantling the equipment.



Dye Penetrant Non-destructive Testing System

0229	Volume Millilitres	Description
6190005600	400	Part 1 - Cleaner
6190006510	400	Part 2 - Penetrant
6190007510	400	Part 3 - Developer
Tech Sheet 20692		

WELDING

Spatter Release

Traditional, non-flammable, solvent based spatter release formulation.

Prevents spatter adhesion on welding equipment, work pieces, surfaces, jigs and surrounding areas.



Non-flammable Weld Anti-spatter

0229	Volume Millilitres
6190004150	400
Tech Sheet 20693	

Bioweld

A water-based spatter release agent which gives exceptional results without the use of harmful solvents, silicones or mineral oils.

Allows post welding operations, painting, plating, galvanising etc to be undertaken without interference.

Contains a rust inhibiting agent.



Water Based Anti-spatter

0229	Volume Millilitres
6190004600	400
Tech Sheet 20694	

Easy Weld

Easy Weld provides a quick, easy way to prevent adherence of spatter to metal surfaces, and eliminates the need for chiselling, grinding or wire brushing after welding.

A workshop spatter release based on biodegradable oil.



Biodegradable Spatter Release

0229	Volume Millilitres
6190004650	400
Tech Sheet 20695	

PORTWEST

For **Respiratory Protection** see page **1755**



FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Perma-Lock®
2-WAY INTEGRATED ACTUATOR

PREVENTION. NOT DETECTION.™



Available from Ambersil

LOCKED IN FOR SAFETY

INTEGRATED DESIGN BENEFITS:

- Secure spray straw locks in place
- Non-slip grip
- Traditional spray in the “down” position
- Precision application in the “up” position
- Useful catch curb - prevents oily can

Ambersil have upgraded their Food Processing range under the new “Perma-Lock®” design. Perma-Lock® is a unique, non-detachable spray system with dual position spray. There are no detachable pieces that can fall off, leading to contamination of goods and exposing food manufactures and processors to costly recalls. Perma-Lock® reduces the need for expensive x-ray or metal detection equipment: preventing loss is better than detecting loss.

1578

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

FOOD GRADE CLEANING & LUBRICATION

Silicone FG

Use where reduced friction is required, particularly on plastic-to-plastic components. Use on guide rails in 'finished product' lines or as a guide rail and labelling equipment anti-stick treatment to dramatically reduce label and adhesive build-up.

NSF H1 registered (N°138000) for use in the food and beverage industry.

Eliminates squeaking, binding and sticking.



NSF H1 Registered Silicone Lubricant

0229	Volume Millilitres
6150009350	400
Tech Sheet 20706	

Ambergrease FG1

Ideal for all types of bearings and sliding rails/surfaces in low temperature areas (e.g. chiller/freezer), moist or wet environments, and where a longer re-lubrication interval is required.

NSF H1 registered (N°138264).

White, NLGI type 2, aluminium complex grease.

Operational temperature range: -50°C to +165°C.



Performance Grease for Food Processing Equipment

0229	Volume Grams
6150009370	400
Tech Sheet 20708	

Dry PTFE Lube FG

Use for the lubrication of chutes, slides, and pins. Where silicone cannot be used.

NSF H1 (No. 139899) registered for use in the food industry.

Particularly suitable in low load, low speed applications.

Operational temperature range: -150°C to +26°C.



NSF H1 Registered Dry Lubricant

0229	Volume Millilitres
6150009520	400
Tech Sheet 20713	

Chain Lube FG

Ideal for conveyor chains, chain drives, pulleys, rollers, transfer belts, hoists and overhead door drives. Can be used above the food line.

NSF H1 registered (N°137998).

Excellent penetration and lubrication properties, can be used as a general, heavy-duty, PTFE lubricant.



NSF H1 Chain Lubricant with PTFE

0229	Volume Millilitres
6150009330	400
Tech Sheet 20705	

Food Grease FG

Use on plain bearings, hinges, and moving parts. Particularly useful for limited access areas where regular grease penetration may be difficult.

NSF H1 registered (N° 140258) for use in the food industry, NLGI type 2 white grease, aluminium complex thickened.

Operational temperature range: -20°C to +140°C.



NSF Registered Spray Grease

0229	Volume Millilitres
6150009500	400
Tech Sheet 20711	

Belt Dressing FG

Apply to all types of belts to increase grip, reduce squeak and prolong life. Use on conveyor drive transfer belts, conveyor belts, and belts subjected to wet environments.

Belt Dressing FG is NSF H1 registered (N° 140257).

Protects belts from deterioration through oxidation and heat.



Adhesive Belt Lubricant

0229	Volume Millilitres
6150009480	400
Tech Sheet 20714	

Penetrating Oil FG

For use in the food and drink industry on seized fasteners seized by heat, corrosion, over-tightening, and contamination.

NSF H1 registered (N° 140260) for use in the food industry.

Assists quick disassembly of mechanical components, fittings, and close tolerance fasteners.



NSF H1 Registered Penetrant for Seized Parts

0229	Volume Millilitres
6150009470	400
Tech Sheet 20715	

Assembly Paste FG

For lubrication of bushes, sliding surfaces and small open gears. Prevents damage at start-up and protects during running-in. Protects against seizing of threaded components.

Effective from -30°C to +150°C as a lubricant and to +1100°C as an anti-seize.

Please note: Images used are to indicate type of container for products.



NSF H1 Assembly Paste & Anti-seize Compound

0229	Volume Millilitres
6150009400	400
Tech Sheet 20717	

Machine Oil FG

For use in the food industry on metal-to-metal moving parts such as hinges, gimbal-mounts, safety latches, and threaded parts.

NSF H1 registered (N°137999 and 140249).

Creates a highly effective lubricating and anti-friction film. Can be used as an anti-corrosion coating for metal parts in high-humidity conditions.



NSF H1 General Purpose Lubricant

0229	Volume Millilitres
6150009340	400
Tech Sheet 20707	

FOOD GRADE CLEANING & LUBRICATION

Amberclens FG

Developed for general cleaning in the food industry.
Use to remove grime or soiling from equipment post-maintenance.
NSF A1 registered (N° 137995).
Stable, non-dripping foam. Foaming action helps break down soiling for effective cleaning.



NSF A1 Foam Cleaner

0229	Volume Millilitres
6150009300	500
Tech Sheet 20696	

Amberklene FG

Developed for general degreasing in the food industry. Use to remove grease and heavy oils from bearings, conveyor drives, and chains and hydraulic oil seepage. Removes wax-based anti-corrosion (transportation) coatings and metal cutting lubricant.
NSF A8 and C1 registered (N° 137996 and 140261) meets guidelines for use in the food industry.
High flash point of 40°C for application safety. Penetrates quickly and removes dirt and moisture. Does not a leave residue.



NSF A8 & C1 Biodegradable Cleaner/Degreaser

0229	Volume Millilitres
6150009310	500
Tech Sheet 20698	

Stainless Steel Cleaner FG

For use on all types of stainless steel and shiny surfaces to remove light dirt, finger prints and water marks
NSF A7 and C1 registered (N°138212) for use in food industry.
Cleans and inhibits re-staining of stainless steel in one application.



NSF A7 & C1 Stainless Steel Cleaner

0229	Volume Millilitres
6150009360	500
Tech Sheet 20700	

Degreaser FG

Use to degrease components when a regular solvent cleaner cannot be used.
NSF A1 registered (N°137997).
Effective in both cold and warm water, use on gearboxes, hydraulic systems, open gears, chains and pumps to remove a variety of heavy soiling types.



NSF A1 Water Based Degreaser

0229	Volume Millilitres
6150009320	750
Tech Sheet 20697	

Industrial Degreaser FG

Use where a fast drying time and high solvency power is required. Dissolves grease and grime from bearings, removes old lubricant from drives, slides, and guide rails.
NSF A8 and K1 registered (N° 140255 and 140250) for use in food industry.
Use for degreasing and over-hauling electric motors.
Can also be used to remove adhesives.



NSF A8 & K1 Registered Heavy-duty Degreaser

0229	Volume Millilitres
6150009420	500
Tech Sheet 20701	

Contact Cleaner FG

Specifically designed for electrical maintenance in the food industry, particularly production line electronics, automated systems and optical readers.
NSF K2 registered (N° 139627) for use in the food industry.
Use to remove grime and contamination from PCB's and contacts.



NSF Registered Electrical Contact Cleaner

0229	Volume Millilitres
6150009510	400
Tech Sheet 20699	

Label & Adhesive Remover FG

Use to remove labels from shipping containers, packing boxes and bulk storage (intermediate) drums.
NSF K3 registered (N° 140259) for use in the food industry.
Removes adhesives and paper labels in 3 minutes.
Improves packaging line efficiency by reducing jamming caused by label and adhesive build-up.



NSF K3 Registered Label & Adhesive Remover

0229	Volume Millilitres
6150009450	200
Tech Sheet 20704	

Ambergrease FG2

Use on bearings subjected to high temperatures such as oven conveyors, oven fan bearings, bakery lines, drying ovens and in food container moulding operations.
NSF H1 registered (N°138265).
Translucent white NLGI type 2 silicone grease.
Operational temperature range: -20°C to +220°C.



NFS H1 High Temperature Bearing Grease

0229	Volume Grams
6150009380	400
Tech Sheet 20709	

Fluid-Air Components Ltd

FOOD GRADE CLEANING & LUBRICATION

Ambergrease FG3

For use on all types of bearing in food, drinks, and consumables processing. Ideal for end-of-line conveyor lubrication, conveyor drive motors, and packing areas.

NSF H1 registered (N° 140248) for use in the food industry.

Provides stable, long-term lubrication.

Operational temperature range: -20°C to +140°C.



NSF H1 Multi-purpose Bearing Grease

0229	Volume Grams
6150009490	400
Tech Sheet 20710	

Assembly Grease FG

Use in the same manner as a Copper Anti-Seize (as a general anti-seize) but also aids with the running in of bearings whilst grease is worked. Particularly effective as an anti-seize on oven fans. Can be used as a high temperature ejector pin lube for moulding white plastic food cartons.

NSF H1 registered (N°138266 and 139900).

Resists water wash-out, extending re-lubrication intervals when used as a service lubricant.

Operational temperature range: -30°C to +1100°C.



NSF H1 Assembly Lubricant & Anti-seize Compound

0229	Volume Grams
6150009390	500
Tech Sheet 20712	

Moisture Remover FG

For use on equipment to displace moisture, particularly after wash-down or because of water ingress. Ideal for use on electronics.

NSF H2 registered (No.142299) for use in the food and beverage industry.

Provides precision lubrication by its thin, high dielectric strength, lubricating film, can be used as a multi-purpose lubricant.



NSF H2 Registered Dewatering Fluid

0229	Volume Millilitres
6150009530	500
Tech Sheet 20716	

MOULDING RANGE

HD-Sil Release

Exhibits excellent anti stick and slip properties. Particularly effective in mould release and injection moulding operations.

Ideal for use where a clean, colourless lubrication is required.

Operational up to +200°C.

Easily removed with solvent cleaners.



Heavy-duty Silicone Release Agent

0229	Volume Millilitres
31631-AD	500
Tech Sheet 20718	

Mould Solv

Ideal for removing general mould residues and release coatings

Highly effective low odour, degreasing agent that also removes anti-corrosion, storage coatings

Efficiently cleans plastic, ferrous and non ferrous coatings.



Cleaner for Moulds & Tools

0229	Volume Millilitres
31970-AA	500
Tech Sheet 20720	

Mould Protective

Non-silicone corrosion inhibitor for injection moulding tools and dies.

Repels and displaces moisture, leaving a durable, non-greasy, protective film



Mould Corrosion Inhibitor

0229	Volume Millilitres
6120005000	400
Tech Sheet 20722	

No-Sil Release

Provides a wet, heavy-duty film for the release of plastic and rubber parts.

For use in injection moulding, vacuum forming and many other moulding and forming processes.

Operational up to +170°C.



Heavy-duty Non-silicone Release Agent

0229	Volume Millilitres
31971-AA	500
Tech Sheet 20719	

Tool Guard

A light green, viscous, protective coating for use on mould tools. Remove moisture and provides long term protection to surfaces.

Easy identification with total coverage assured.

Will not penetrate or creep into mould tool.

Resists the effects of high humidity and acid finger marking

Excellent corrosion protection.



Highly Visible Corrosion Inhibitor

0229	Volume Millilitres
31972-AA	500
Tech Sheet 20721	

Clear Mould Protective

Use on mould tools as a long-term protective coating for storage.

Repels and displaces moisture, leaving a durable, clear, protective film



Transparent Corrosion Inhibitor

0229	Volume Millilitres
6120005500	400
Tech Sheet 20723	

PAINT & SURFACE PREPARATION

Acrylic Paints

Ambersil Acrylic Paint is a high quality paint designed for use in a wide variety of industrial, automotive and home and garden applications. It is also recommended as a protecting paint for repairs on all kinds of lacquered surfaces, or where a colour matched anti-corrosion finish is required.

When combined with Ambersil Cold Galvanize as a base coat, superior and long lasting anti-corrosion protection is achieved even when the surface is damaged.

- Fast drying
- Good hardening and resistance to wear
- Excellent flexibility
- High UV resistance once dry
- Good adhesion to metal, wood, glass, paintable plastics, concrete and stone
- Excellent coverage and opacity

Standard

0229	Volume Millilitres	Colour	RAL Code
6180400004	400	Bright Red	RAL 3002
6180400005	400	Blue	RAL 5015
6180400007	400	Green	RAL 6002
6180400008	400	Bright Yellow	RAL 1018
6180400006	400	Battleship Grey	RAL 7032
6180400010	400	Grey Primer	-
6180400011	400	Chrome Silver	-
Tech Sheet 20725			





Fluorescent

0229	Volume Millilitres	Colour
6180400012	400	Green
6180400013	400	Yellow
6180400014	400	Red
Tech Sheet 20725		



Matt

0229	Volume Millilitres	Colour	RAL Code
6180400000	400	Black	RAL 9011
6180400001	400	White	RAL 9010
Tech Sheet 20725			



Gloss

0229	Volume Millilitres	Colour	RAL Code
6180400002	400	Black	RAL 9005
6180400003	400	White	RAL 9016
Tech Sheet 20725			

PAINT MARKER PENS

Brilliant Paint Marker Pens

- Vibrant, long lasting paint pens for all surface marking.
- The pens come in 7 colours.
- They can write on almost any surface, including metal, glass, rubber, plastics, paint, card, concrete and wood.



3mm Nib

0229	Colour
6190050001	White
6190050002	Green
6190050003	Yellow
6190050004	Blue

0229	Colour
6190050005	Red
6190050006	Orange
6190050007	Black
Tech Sheet 20729	

Fluid-Air Components Ltd

PAINT & SURFACE PREPARATION

2-in-1 Primer & Paint

- Quicker than separate primer and paint.
- Fast drying time.
- Up to 3m2 coverage from single can.



Galva Colour

0229	Volume Millilitres	Colour	RAL Code
6190011530	500	Yellow	1004
6190011531	500	Red	3000
6190011533	500	Blue	5012
Tech Sheet 20732			

0229	Volume Millilitres	Colour	RAL Code
6190011536	500	Black	9005
6190011537	500	Silver	9006
6190011538	500	White	9010
Tech Sheet 20732			

SPECIALIST PRODUCTS

Paint & Graffiti Remove

- Dissolves marker pens instantly, softens acrylic paint in 3 minutes and Galva Colour in 10 minutes
- For use on hard non-porous surfaces
- Fast and effective on graffiti paint, inks and other common graffiti type
- Excellent pre-painting surface treatment



0229	Volume Millilitres
31630-AA	400
Tech Sheet 20733	

5005A Clear Silicone Sealant

- A ready to use one-part silicone sealant suitable for use as a general-purpose sealing and bonding agent.
- Offers excellent adhesion to metal, glass, and glazed ceramics.



0229	Volume Millilitres
6260020700	75
Tech Sheet 20734	

Adhesive QS900

- Especially useful for vertical surfaces where instant grab avoids slippage.
- Tack time approximately 30 seconds, instant 'grab and hold'



Spray Adhesive

0229	Volume Millilitres
6190009400	500
Tech Sheet 20735	

Adblue®



For **Adblue Fuelling Equipment**
see pages **1623-1624**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

THREAD STICKS & THREADLOCKERS

Threadlocker Sticks

- Effective on all types of metal threaded fasteners. Recommended where disassembly is required. Machine tools and presses, pumps and compressors, mounting bolts and gear boxes.
- For use on threads up to M50
- Functional strength 6 hours
- Long term temperature resistance +150°C



248, Medium Strength

0753	Volume Grams
LOC-248	19
Tech Sheet 67925	

- Effective on all types of metal threaded fasteners. Recommended for use where regular removal for maintenance is not required. Suspension bolts, motor transmission and pump mounts, bearing cap bolts and studs.
- For use on threads up to M50
- Functional strength 24 hours
- Long term temperature resistance +150°C



268, High Strength

0753	Volume Grams
LOC-268	19
Tech Sheet 67926	

Thread Sealant Stick

- Recommended for all coarse metal pipe threads where disassembly is required. Ideal for use in a broad range of industries including chemical, processing, waste water treatment and automotive.
- For use on threads up to 3"
- Substrate to be sealed: Metal
- Instant low pressure seal
- Low disassembly strength
- Long term temperature resistance +150°C



561, Instant Bonding

0753	Volume Grams
LOC-561	19
Tech Sheet 67927	

Anti-Seize Sticks

- Copper based anti-seize for screws, nuts, pipes, heat exchangers etc.
- Sold lubricating agent containing copper and graphite
- N.L.G.I. Class 1

Working Temperature: -30°C to +930°C



8065, C5-A Copper, High Temperature

0753	Volume Grams
LOC-8065	20
Tech Sheet 67928	

243 Threadlocker

Particularly suitable on all metal threaded fasteners. Prevents loosening on vibrating parts such as pumps, motor mounting bolts, gear boxes or presses. Recommended for use where disassembly with hand tools is required for servicing and where parts are contaminated with oil.

- Resists vibration
- Single part – clean and easy to apply
- Can be used on all sizes of fasteners – reduces inventory costs
- Seals threads allows through-hole tapping



Medium Strength

0753	Volume Millilitres
LOC-135279	10
LOC-135278	50
Tech Sheet 67929	

270 Threadlocker

Particularly suitable for use on all metal fasteners (including stainless steels and those with protective coatings such as Zinc) where regular removal for maintenance is not required. Recommended for permanently locking studs on engine blocks and pump housings.

- Resists vibration
- Single part – clean and easy to apply
- Can be used on all sizes of fasteners – reduces inventory costs
- Seals threads allows through-hole tapping



High Strength

0753	Volume Millilitres
LOC-267380	10
LOC-232515	50
Tech Sheet 67930	

276 Threadlocker High Strength Fast Fixture

- High strength, even on passive metals
- European gas approval (EN 751-1)
- Excellent chemical and thermal resistance of cured product
- Reliable cure even at low temperatures



0753	Volume Millilitres
LOC-1266117	50
Tech Sheet 67931	

577 Thread Sealant

Particularly suitable for all coarse metal threads. Suitable for past applications at low temperatures e.g. outdoor plant maintenance. Carries the German DVGW Approval (No 96.04e 125). Tested in accordance to EN 751-1. Meets BS 6956 type B for sealing gas fittings

- Replaces hemp/tapes and pastes
- Liquids ensure complete contact between threads provides 100% seal
- Liquids will not creep, shrink or block systems (including filters) by shreddin
- Disassembly can be achieved easily with normal tools



General Purpose

0753	Volume Millilitres
LOC-229342	50
Tech Sheet 68057	

542 Thread Sealant

Particularly suitable for fine threaded fittings as used in hydraulic and pneumatic installations and small fittings in general. Carries the German DVGW approval (No.96.02E 125). Tested in accordance to EN 751-1. Meets BS 6956 type A for sealing gas fittings

- Replaces hemp/tapes and pastes
- Liquids ensure complete contact between threads provides 100% seal
- Liquids will not creep, shrink or block systems (including filters) by shredding
- Disassembly can be achieved easily with normal tools



Hydraulic & Pneumatic

0753	Volume Millilitres
LOC-135483	10
LOC-267431	50
LOC-267432	250
Tech Sheet 67932	

2701 High Strength Oil Resistance

- For the high strength locking and sealing of studs, nails and bolts
- Vibration proof
- Ideal for use on inactive substrates and/or where maximum resistance to hot oil is required



0753	Volume Millilitres
LOC-234853	50
Tech Sheet 67933	

Fluid-Air Components Ltd

SEALANT, RETAINER, SUPER GLUE & TAPE

572 Low Strength Slow Cure Pipeseal

- This product is designed for the locking and sealing of metal pipes and fitting
- The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration
- The thrixotropic nature reduces the migration of liquid product after application to the substrate



0753	Volume Millilitres
LOC-229360	50
Tech Sheet 67941	

574 Flange Sealant

- Seals close fitting joints between rigid metal faces and flange
- The product cures when confined in the absence of air between close fitting metal surface
- Provides resistance to low pressures immediately after assembly of flange
- Typically used as a form-in-place gasket on rigid flanged connections e.g. gearbox and engine casings, etc.
- The thrixotropic nature reduces the migration of liquid product after application to the substrate



0753	Volume Millilitres
LOC-267437	50
LOC-234573	250
Tech Sheet 67942	

518 Flexible Fast Cure

- This product is a single component, medium strength, anaerobic sealant which cures when in the absence of air between close fitting metal surface
- Typical applications include sealing close fitting joints between rigid metal faces and flange
- Provides resistance to low pressures immediately after assembly of flange
- Typically used as a form-in-place gasket on ridged flanged connections, e.g. gearbox and engine casings, etc.
- The thrixotropic natures reduces the migration of liquid product after application to the substrate



0753	Volume Millilitres
LOC-229875	50
Tech Sheet 67943	

5400 Health & Safety Pipe Sealant

- No hazard symbols, no risk phrases
- White material safety data sheet
- No need for COSHH assessment
- WRAS Approved



0753	Volume Millilitres
LOC-1545634	50
LOC-1546964	250
Tech Sheet 67944	

603 Retainer

Particularly suitable for retaining close fitting cylindrical parts (up to 0.1mm gap), and for use on cylindrical fitting parts where thorough degreasing is not possible.
Tested and approved for use on bearings.

- High and moderate strength products – can carry high loads and eliminate fretting
- Fill all voids – prevent corrosion
- Reduce the need for close tolerances
- 100% contact – load and stress is distributed evenly over the joint



For Retaining Cylindrical Parts

0753	Volume Millilitres
LOC-229873	10
LOC-135280	50
Tech Sheet 67945	

638 Retainer

Particularly suitable where dynamic axial and radial loads are present. Recommended for retaining shafts, gears, pulleys and similar cylindrical parts.

- High and moderate strength products – can carry high loads and eliminate fretting
- Fill all voids – prevent corrosion
- 100% contact – load and stress is distributed evenly over the joint



For Retaining Cylindrical Parts

0753	Volume Millilitres
LOC-234795	50
Tech Sheet 67946	

641 Bearing Fit Retainer

Particularly suitable for retaining parts such as bearings, and when later dismantling will be needed.

- High and moderate strength products – can carry high loads and eliminate fretting
- Fill all voids – prevent corrosion
- Reduce the need for close tolerances
- 100% contact – load and stress is distributed evenly over the joint



0753	Volume Millilitres
LOC-267442	10
LOC-135522	50
Tech Sheet 67947	

Super Glue



Bottle, Brush Application

0753	Volume Grams
LOC-272597	5



Tube, Squeeze Application

0753	Volume Grams
LOC-272602	3

Duct Tape



0753	Width mm	Length Metres
LOC-260499	50	25

FAC Fluid-Air Components Ltd

SEALANT, RETAINER, SUPER GLUE & TAPE

Power Tape

Power Tape is no ordinary multi-purpose cloth tape. Manufactured to include advanced tape technology, three power layers are combined to form an outstanding, heavy-duty, fabric-reinforced power tape.

Power Tape is 100% weatherproof* and uses a unique super strong adhesive that sticks firmly to most surfaces offering up to 50% stronger adhesion than standard cloth tapes.

Power Tape is suitable for both interior and exterior use, and has hundreds of uses around the home, garden, garage and workplace.

*Not suitable for total immersion in water.

Not intended for permanent repairs.



0753	Width mm	Length Metres	Colour
LOC-297328	50	25	Silver
LOC-298392	50	25	Black

5075 Insulating Sealing Wrap

Insulating and emergency sealing wrap.

- Can be applied to wet surfaces
- Non-sticky self fusing tape
- Temperature from -54°C to +260°C



0753	Width mm	Length Metres	Colour
LOC-1684617	10	4.27	Red
LOC-1808110	10	4.27	Black
Tech Sheet 67948			

SEALANTS & ADHESIVES

55 Pipe Sealing Cord



55 Thread Sealing Cord

0753	Length Metres
LOC-483283	50
LOC-270153	160

567 PTFE Pipe Sealant



567 PTFE Thread Sealant

0753	Volume Millilitres
LOC-234458	250

Threadlocker



290 High Strength Threadlocker

0753	Volume Millilitres
LOC-233733	50



6300 H&S Retainer

0753	Volume Millilitres
LOC-1546952	50

Magic Metal Stick



3463 Magic Metal Stick

0753	Volume Grams
LOC-265628	114

Anti-Seize



8009 Heavy-duty Anti-Seize "Brush in Lid"

0753	Volume Grams
LOC-504219	454

Fluid-Air Components Ltd

ADHESIVES

LOCTITE

435 Instant Adhesive

- A rubber-toughened adhesive with increased flexibility and peel strength, along with enhanced resistance to shock
- The product provides rapid bonding on a wide range of materials including metals, plastic and elastomers, as well as porous and absorbent materials like wood, paper, leather and fabric



Clear Toughened

0753	Volume Grams
LOC-871787	20
Tech Sheet 10367	

401 Adhesive

Particularly suitable for bonding rubber and plastics.

- Fixtures in seconds
- Clear bond line – good cosmetic appearance
- Versatile – dissimilar materials can be bonded
- High strength – often giving a bond stronger than the materials being bonded
- Small parts bonding



Instant Bonding

0753	Volume Grams
LOC-135428	20
Tech Sheet 67934	

454 Instant Adhesive

- Designed for the assembly of difficult-to-bond materials which require uniform stress distribution and strong tension and/or shear strength
- The product provides rapid bonding of a wide range of materials including metals, plastics and elastomers
- This product is particularly suited for bonding porous or absorbent materials such as wood, paper, leather and fabric
- The gel consistency prevents adhesive flo , even on vertical surfaces



Gel

0753	Volume Grams
LOC-195678	20
Tech Sheet 67935	

406 Adhesive

Particularly suitable for difficult-to-bond rubber or plastics, e.g. polyethylene, polypropylene, PTFE, or thermoplastic rubbers such as Santoprene.

- Fixtures in seconds
- Clear bond line – good cosmetic appearance
- Versatile – dissimilar materials can be bonded
- High strength – often giving a bond stronger than the materials being bonded
- Small parts bonding



Instant Bonding

0753	Volume Grams
LOC-233695	20
Tech Sheet 67936	

3430 Twin Syringe Ultra Clear, Fast Cure

- Ultra-clear bond line
- Medium viscosity
- Fast cure



0753	Volume Millilitres
LOC-142517	24
Tech Sheet 67938	

Teroson MS939

A gun-grade, one-component adhesive/sealant based on silane modified polymers, which cures by reaction with moisture to an elastic product. It can be used for elastic bonding of metals and plastics, elastic, interior and/or exterior seam and joint sealing.

- Pasty and thixotropic
- 1-part, low modulus, flexibl
- UV resistant, sag-resistant
- Non-corrosive and free of solvents
- Isocyanates, silicones and PVC

new product



Silane-modified Polyme

0753	Volume Millilitres
2436358	290
2436359	570
Tech Sheet 71758	

3090 Two Component Gel

- Handling strength in seconds
- Gap filling up to 5m
- Gel based, non-drip formula
- Cures quickly, independently of gap and substrate
- Excellent bonding characteristics on a broad variety of substrates: metals, most plastics, rubber, porous/absorbent materials such as wood, paper, cardboard, leather and fabric

Working Temperature:
-20°C to +80°C



0753	Volume Grams
LOC-1379599	10
Tech Sheet 67939	

4090 Two Component Gel, High Temperature

- High moisture resistance
- Up to +150°C
- Impact and vibration resistant
- Gap filling up to 5m



0753	Volume Grams
LOC-1778011	50
Tech Sheet 67940	

4070 Structural Bonder

HY 4070 is a two-part, transparent, cloudy, colourless to pale yellow cyanoacrylate/acrylic hybrid gel adhesive that provides a fast fixture at room temperature. Suitable for various substrates including most plastics, rubbers and metals.

- Non-sag
- Gel consistency prevents adhesive flo , even on vertical surfaces
- Gap filling up to 5m
- Temperature and moisture resistant



0753	Volume Grams
LOC-2237457	11
Tech Sheet 68733	

FAC
Fluid-Air Components Ltd

ADHESIVE TAPES

Tapes



Pipework Identification PVC apes

0137	Description	Colour	Background
PTB5920000	Compressed Air	Black	Light Blue
PTB5920003	Gas	Black	Yellow Ochre
PTB5920005	Nitrogen	Black	Yellow Ochre
PTB5920006	Steam	Black	Silver
PTB5920008	Water	Silver	Green



Magtape Utility Gaffer Tape

0137	Description	Width mm	Roll Length Metres
CTMAGUT48BK	Black	50	50
CTMAGUT48W	White	50	50



Magtape Utility Gaffer Tape, Colours

0137	Description	Width mm	Roll Length Metres
CTMAGUT50S.BLUE	Blue	50	50
CTMAGUT50Y	Yellow	50	50



Kraken Silicone Repair Tape

0137	Description	Width mm	Roll Length Metres
RT24BK	Black	24	3.6
RT24C	Clear	24	3.6



Masking Tape

0137	Description	Width mm	Roll Length Metres
MT77724	Natural	24	50
MT77748	Natural	48	50



Velcro Hook & Loop Tape

0137	Description	Roll Length Metres
VT9012525BKHOOK	Black Hook Tape 25mm Width	25



Reflective Hazard arning PVC Tape

0137	Description	Width mm	Roll Length Metres
REFBKY50	Black/Yellow	50	10
REFRW50	Red/White	50	10



Slipway Cable Cover Tape

0137	Description	Width mm	Roll Length Metres
SW14530PBK	Matt Black	145	30



Tape Residue Remover

0137	Volume Millilitres
AR250	250



Anti Slip Primer

0137	Volume Litres
ST2238	1

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ADHESIVE TAPES & BARRIER TAPES

PVC Tapes

- Nominal Thickness 0.13mm+0.025mm
- Available in a wide range of colours
- No lead content
- Good electrical properties, tough, flexible and conformabl
- Approved by BS3924, IMQ, VDE, OVE
- Self extinguishing

Applications:
Electrical insulating tape
General purpose




ISOLSINT/2702 Tape, 33 Metre Rolls

0137	Size mm	Colour
2702BLACK12	12	Black
2702RED12	12	Red
2702BLUE12	12	Blue
2702DGREEN12	12	Dark Green
2702BLACK19	19	Black
2702WHITE19	19	White
2702RED19	19	Red
2702BLUE19	19	Blue
2702YELLOW19	19	Yellow
2702BROWN19	19	Brown
2702ORANGE19	19	Orange
2702YELLGRE19	19	Yellow & Green
2702BLACK25	25	Black
2702RED25	25	Red
2702BLACK50	50	Black
2702YELLOW50	50	Yellow
2702ORANGE50	50	Orange
Tech Sheet 20416		

- Nominal Thickness 0.16mm+0.025mm
- Available in a wide range of colours
- Lead free
- Easy tearability

Applications: Line marking and hazard warning



2721 Tapes, 33 Metre Rolls

0137	Size mm	Colour
2721YELLBLACK50	50	Yellow & Black
2721YELLBLACK75	75	Yellow & Black
Tech Sheet 20414		

31075 Foam Tapes

- Double sided polyethylene foam tape
- Heavy-duty packaging tape



30 Metre Rolls

0137	Size mm	Colour
5474WHITE2X10	2 x 10	White
Tech Sheet 20418		

Packaging Tapes

- Economical carton sealing tape
- General purpose packaging tape



Polypropylene Buff Packaging Tapes, 66 Metre Rolls

0137	Size mm	Quantity
SHBPT50X66	50	1
SHBPT50X66BOX	50	36

- Available in mono or crossweave format

Application: Heavy-duty packaging tape.



Filament Packaging Tapes, 50 Metre Rolls

0137	Size mm	Format
SHMT25X50	25	Mono
SHMT50X50	50	Mono
SHCT25X50	25	Crossweave
SHCT50X50	50	Crossweave
Tech Sheet 20419		

- The low-tack adhesive allows easy unwinding from the roll, avoiding distortion of the fil
- Easy, clean removal from the protected article after use
- Resistant to moisture, many chemicals, such as diluted acids and alkalis, and salt solutions
- Suitable for indoors or outdoors
- Used as a protection film for the transport of window frames and ladders
- The tape performs well on mild steel, stainless steel and aluminium



2903/1102 Outdoor Low-Tack Protection Tape, 100 Metre Rolls

0137	Size mm	Colour
2903BLACKBLACK50	50	Black/Black
2903BLACKBLACK75	75	Black/Black
Tech Sheet 20417		

Self Amalgamating Tapes

- Compatible with a wide range of rubber and plastic dielectric cable insulation
- Highly resistant to prolonged immersion in water and has excellent resistance to ozone

Applications: Used for making watertight seals at polyethylene sleeve joints on polyethylene-sleeved telephone cables, both above and below ground.
Used for jointing (splicing) and repair of a wide range of power and distribution cables up to 46 kV.



Black PIB Self Amalgamating Tape, 10 Metre Rolls

0137	Size mm
2501BLACK19	19
2501BLACK25	25
Tech Sheet 20415	

Non-adhesive Barrier Tapes

- This range of economical barrier tapes can be used to section off areas



Barrier Tapes, 500 Metre Rolls

0137	Size mm	Colour
SHBTR/W-75X500	75	Red & White
SHBTB/Y-75X500	75	Black & Yellow

Waterproof Cloth Tapes

- A polyethylene coated waterproof cloth tape with a pressure sensitive adhesive
- Economy grade waterproof cloth tape
- Excellent adhesion and strength

Applications: General purpose waterproof cloth tape.
Used for sealing, bundling, masking and protecting.
Excellent for joining polyethylene sheeting in asbestos removal applications.



3160 Waterproof Cloth Tape, 50 Metre Rolls

0137	Size mm	Colour
3160BLACK50	50	Black
3160WHITE50	50	White
3160SILVER50	50	Silver
3160BLACK75	75	Black
3160BLACK100	100	Black
3160WHITE100	100	White
3160SILVER100	100	Silver
Tech Sheet 20420		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ADHESIVE TAPES & BARRIER TAPES

PVC Tapes

- Nominal Thickness 0.13mm+0.025mm
- Available in a wide range of colours
- No lead content
- Good electrical properties, tough, flexible and conformabl
- Approved by BS3924, IMQ, VDE, OVE
- Self extinguishing

Applications: Electrical insulating tape, general purpose



33 Metre Rolls

0137	Size mm	Colour
LEMPVC19G	19	Green
LEMPVC19GY	19	Grey
LEMPVC25B	25	Blue
LEMPVC25G	25	Green
LEMPVC25BR	25	Brown

- Nominal Thickness 0.16mm+0.025mm
- Available in a wide range of colours
- Lead free
- Easy tearability

Applications: Line marking and hazard warning



33 Metre Rolls

0137	Size mm	Colour
PVC50RW008	50	Red & White

RUST-OLEUM®



For **Leak Seal** see page **1564**

SPRAYS & SEALANTS

Sealants, Fillers & Guns



Professional Cartridge Gun

0755
2017-6442



All with anti-fungicide.

Polyurethane Expanding Filler & Cleaner

0755	Colour	Volume Millilitres
2017-6467	Black	300
2017-6475	Brown	300
2017-6483	Clear	300
2017-6491	White	300
Tech Sheet 20094		



Low Modulus Acetoxy Silicone

0755	Colour	Volume Millilitres
2017-6335	White	300
Tech Sheet 20093		



Polyurethane Expanding Filler & Cleaner

0755	Type	Volume Millilitres
2017-6418	Gun Foam	750
2017-6434	Hand Held	750
Tech Sheet 20095		

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 **Blow Guns, Vacuum & Nozzles** 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 15

Blow Guns, Vacuum & Nozzles

15.01 Blow Guns **1591-1610**

15.02 Air Jets, Movers, Knives & Amplifier **1611-1616**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 15 Blow Guns, Vacuum & Nozzles

15.01 Blow Guns

1591-1610

- Blow Guns
- Air Blow Guns
- Extended Air Blow Guns
- Blow Guns & Air Nozzles
- Blow/Vacuum Guns & Kits
- Drag-in Pump Kit



15.02 Air Jets, Movers, Knives & Amplifier

1611-1616

- Air Jets
- Blow Guns & Air Nozzles
- Air Movers
- Air Knives & Amplifier



Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

BLOW GUN ACCESSORIES FOR ASG-1

Blow Guns



Features:

The FT Pro ASG-1 safety air blow gun has been developed to comply with all aspects of the OSHA standard for compressed air used for cleaning.

This standard reads: 'Today, the most common way to comply to this standard is to fit a tamper-proof regulator set at 29 PSI ahead of the blow gun. However, this is costly and can only be used when also using a safety nozzle'.

The FT Pro ASG-1 safety air gun provides an extremely cost effective solution; it is designed with Venturi holes in the nozzle which increase air volume and allow air to escape if the nozzle is dead-ended. This specially designed feature ensures less than 30 PSI passes through the nozzle, complying with the standard set by OSHA.

In addition, all the internal components are brass, ensuring a rust-free operation. Blow gun repairs are not necessary as O-rings are self-lubricating, preventing valve leakage.

Working Temperature:
-32°F to +275°F

Maximum Working Pressure
150 PSI

ASG-1 Safety Air Blow Gun

Red Handle, BSPT

0424	Thread
ASG-1	1/4"

Construction:

Body:	Die cast zinc
Internal Components:	Nickel-plated brass
Nozzle:	Brass
Decibel:	97
Thumb Grip:	Vinyl
Inlet:	R1/4
Flow:	310 L/min

WARNING – Blow Guns
Compressed air shall not be used for cleaning purposes except where reduced to less than 30 psi and then only with effective chip guarding and personal protective equipment.

Safety Nozzle


- Standard safety nozzle



0424
ST10
Tech Sheet 20332

Safety Booster

- Increases air volume by up to 33%, and still conforms to OSHA



0424
ST11
Tech Sheet 20332

Extension Nozzles



0424	Length
ST203	3"
ST206	6"
ST208	8"
ST210	10"
ST212	12"
ST216	16"
ST218	18"
ST224	24"
ST230	30"
ST236	36"

Rubber Tip


- Non safety nozzle
- For delicate surfaces that brass may damage



0424
SAT13

Fluid-Air Components Ltd

Air Blow Guns



BG5 (-PVC)

- Lightweight plastic, ergonomically designed for hand comfort
- Adjustable airflow controlled by trigger
- Suitable for use with air and water
- (-PVC) includes rubber-protected tip nozzle

DG-10

- Lightweight aluminium construction
- Adjustable airflow controlled by trigger
- Suitable for use with air, water and cleaning degreasers

BG-718

- Heavy-duty brass construction suitable for use in harsh environments
- Suitable for use with air and water

Working Temperature:
0°C to +60°C

Maximum Working Pressure
10 bar (150 PSI)

Air Blow Guns



BG5-PVC

BSPP Inlet

1305	Thread	Information
BG5	1/4"	–
BG5-PVC	1/4"	Includes PVC Tip
Tech Sheet 20335		

Heavy-duty Brass Blow Gun



BG-718

BSPP Inlet

1305	Thread
BG-718	1/4"

2/2 Brass Lever/Spring Poppet Valves



BSPP

0090	Thread
PBBLH-3/8	3/8"

Fluid-Air Components Ltd

AIR BLOW GUNS

Air Blow Guns



BSPT Male

1305	Thread
DG-10	1/4"
Tech Sheet 10726	

Air or Water Gun



3/4" Hose Tail Connection

1305
ASW-1
Tech Sheet 60464

Air Engine Cleaning Guns



0.6 Litre Capacity, BSPT

1305	Thread
DG-10-EC	1/4"
Tech Sheet 20337	



90°, BSPT

1305	Thread
DG-10-EK	1/4"
Tech Sheet 20338	

EXTENDED AIR BLOW GUNS



- Plastic air inlet
- Plastic body
- Steel nozzle
- Thread: 1/4"
- BSPT Female

Maximum Pressure:
11 bar
Working Pressure:
6 bar

Air Blow Guns

1305	Length
LD04-1	4"
LD10-1	10"
LD13-1	13"
LD20-1	20"
LD40-1	40"
Tech Sheet 20421	



PVC Tip for Extended Air Blow Gun

1305
144194

Fluid-Air Components Ltd

BLOW GUNS

Extension Nozzles



Plastic, BSPP Inlet

1308	Thread	Length mm
AK-13	1/4"	100
AK-300	1/4"	300
AK-600	1/4"	600
Tech Sheet 10783		

Standard Nozzles



Plastic, BSPP Inlet

1308	Thread
AN-13	1/4"
Tech Sheet 20789	

Safety Nozzles



Plastic, BSPP Inlet

1308	Thread
AL-13	1/4"
Tech Sheet 10784	

Nozzle 1/8" BSP



Plastic, 1/4" BSPP Inlet

1308
AI-13
Tech Sheet 20788

Low Noise Level Nozzles (63-73 DB)




Plastic, BSPP Inlet

1308	Thread
AF-13	1/4"
Tech Sheet 20790	

Replacement Nozzle

1308	To Suit
AR-12	AF-13

Safety Nozzles



Aluminium, BSPP Inlet

1308	Thread
AV-13	1/4"
Tech Sheet 10788	

Replacement Nozzle

1308	To Suit
VR-12	AV-13



Aluminium, BSPP Inlet

1308	To Suit
AA-13	1/4"

Replacement Nozzle

1308	To Suit
KD-12	AA-13
Tech Sheet 10786	



Aluminium, BSPP Inlet

1308	Thread
AS-13	1/4"
Tech Sheet 10785	

Replacement Nozzle

1308	To Suit
SD-12	AS-13



Aluminium, High Powered, Energy Saving Gun, BSPP Inlet

1308	Thread
AT-13	1/4"
Tech Sheet 20787	



Aluminium, BSPP Inlet

1308	Thread
AR-13	1/4"
Tech Sheet 20791	

Pressure Reducer



Fits Inlet on all Blow Guns, BSPP

1308	Thread	Air Pressure bar
DRV13/30	1/4"	3
DRV13/40	1/4"	4
DRV13/50	1/4"	5
DRV13/60	1/4"	6
Tech Sheet 1963		

Fluid-Air Components Ltd

BLOW GUNS

25 year warranty on the Air Boy® valve system

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 16 bar

Advised Working Pressure: 8 bar

Air Boy® Classic



1/4" BSPP, Bent Pipe

1307	Nozzle OD mm	LPM
140101-000	8	380
140102-000	6	330
Tech Sheet 60024		



Trade Counter, 10 Pack

1307
140900-000



1/4" BSPP, Bent Pipe & Air Adjustment Screw

1307	Nozzle OD mm	LPM
140103-000	8	380
140104-000	6	330
Tech Sheet 60025		



1/4" BSPP, Extended Bent Pipe

1307	Nozzle OD mm	Nozzle Length mm	LPM
140112B-000	8	300	380
140113B-000	8	500	380
140114B-000	8	1000	380
Tech Sheet 60026			



1307
140100-000



1/4" BSPP, Extended Straight Pipe

1307	Nozzle OD mm	Nozzle Length mm	LPM
140112-000	8	300	380
140113-000	8	500	380
140114-000	8	1000	380
Tech Sheet 60026			

Air Boy® Stainless



1/4" BSPP, Stainless Steel Bent Pipe

1307	Nozzle OD mm	LPM
140120-159	8	380
Tech Sheet 60027		



1/4" BSPP, Stainless Steel Bent Pipe

1307	Nozzle OD mm	LPM
140120-000	8	380
Tech Sheet 60024		

Super Silent Air Boy®



Working Temperature: -10°C to +60°C

Maximum Working Pressure: 12 bar

High blowing force, low noise level

1/4" BSPP, Unblockable Stainless Steel Bent Pipe

1307	Nozzle OD mm	LPM
140141-000	8	330
Tech Sheet 60033		

PORTWEST

For **Ear Protection** see page **1753**



Fluid-Air Components Ltd

BLOW GUNS


25 year warranty on the Air Boy® valve system

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 16 bar

Advised Working Pressure: 8 bar

Silent Air Boy®



Working Temperature: -10°C to +60°C

Low noise level

1/4" BSPP, Unblockable Bent Pipe


1307	Nozzle OD mm	LPM
140125-000	8	260
Tech Sheet 60031		



Low noise level

8mm, Bent Pipe with Shut Off

1307
140128-000



Working Temperature: -10°C to +60°C

Low noise level

1/4" BSPP, Unblockable Bent Pipe & Air Adjustment Screw

1307	Nozzle OD mm	LPM
140135-000	8	260
Tech Sheet 60032		



Working Temperature: -10°C to +60°C

Low noise level

1/4" BSPP, Unblockable Straight Pipe

1307	Nozzle OD mm	LPM
140126-000	6	260
Tech Sheet 60031		



Working Temperature: -10°C to +60°C

Low noise level

1/4" BSPP, Unblockable Straight Pipe & Air Adjustment Screw

1307	Nozzle OD mm	LPM
140136-000	8	260
Tech Sheet 60032		



8mm with Extended Pipe & Shut Off

1307	Nozzle Length mm
140129-000	500

Air Boy® Anti-Block



1/4" BSPP, Unblockable Bent Pipe

1307	Nozzle OD mm	LPM
140106-000	6	330
Tech Sheet 60029		

Safety Air Boy®



1/4" BSPP, Bent Pipe, Automatic Pressure Reduction

1307	Nozzle OD mm	Pressure Reduction	LPM
140161-000	8	2	140
140171-000	8	3.5	220
Tech Sheet 60030			



1/4" BSPP, Straight Pipe, Automatic Pressure Reduction

1307	Nozzle OD mm	Pressure Reduction	LPM
140160-000	8	2	140
140170-000	8	3.5	220
Tech Sheet 60030			

PORTWEST



For **Respiratory Pretection** see page **1755**

Fluid-Air Components Ltd

BLOW GUNS

25 year warranty on the Air Boy® valve system

Working Temperature: -10°C to +80°C

Maximum Working Pressure: 16 bar

Advised Working Pressure: 8 bar

Air Boy® Turbo



1/4" BSPP, Unblockable Bent Pipe & Venturi Nozzle

1307	OD mm	LPM
140110-000	6	300
140111-000	8	300
Tech Sheet 60028		



Venturi Nozzle for 8mm Pipe

1307
144116
Tech Sheet 60037

Air Boy® Non Scratch



8mm, Bent Nozzle

1307
140021-000

Air Boy® Junior



Blow Gun Junior & Rubber Nozzle

1307
140023-000

Jet Air Boy®



High blowing force, low noise level

1/4" BSPP, Unblockable Jet Air, 1 Nozzle

1307	Nozzle	LPM
140026-134	Flat	580
Tech Sheet		



Jet Air Boy® with Flat Nozzle & Volume Control

1307
140027-134



1/4" BSPP, Threaded Blow Gun for Jet Air Nozzles

1307	Nozzle	LPM
140858-000	1/4" BSPP	380
Tech Sheet 60024		



1/4" BSPP, Jet Air, 1 Nozzle

1307	Colour	Material	LPM
141000-000	Black	POM	580
Tech Sheet 60036			



1/4" BSPP, Jet Air, 2 Nozzles

1307	Colour	Material	LPM
141001-000	Grey	ULTEM 1000 200°C	580
Tech Sheet 20428			

Precision Nozzle



Hardened Steel

1307	Thread ID
145950-000	1/4"

Wide Nozzle



Pack of 3

1307	To Suit
145955-000	Sodablaster V2

Fluid-Air Components Ltd

BLOW GUNS

Sodablasting



Sodablasting Media

1307	Litres
320103-000	5

Sodablasting Set




Air Blow Gun with Hose & Feeder Tube

1307	Thread ID
145110-000	1/4"

Brake Bleeders

- Air supply: 6-12 bar, 180 L/min at 8 bar



The safety valve prevents the fluid to atomize when the container is full.



1/4" BSPP Inlet, Complete with Safety Valve

1307	Capacity Litres
143103-000	1.2
Tech Sheet 20436	



1/4" BSPP Inlet

1307	Capacity Litres
143102-000	1.2

Oil Extractor

Ideal for changing oil on tractors, cars, boats, motorcycles, garden machinery and other types of engines.

Oil flow is infinitely adjustable and easily regulated with the trigger.

Also suitable for the removal of various types of oils, e.g. hydraulic, cutting and engine oils.

Made of impact-resistant materials and extremely corrosion resistant.

Maximum Working Pressure:
12 bar



1/4" BSPP

1307	Capacity Litres	LPM
147150-134	1.2	180
Tech Sheet 60401		

Automotive Tools

To ensure the optimum operation of your cooling system it is important to secure that the coolant is not polluted with abrasive particles and foreign materials.

With the **Jet Flusher** you can flush the whole system without use of solvents and harsh chemicals. It uses a combination of water and compressed air, which increases the water pressure without damaging the surface.

The **Jet Flusher** is equipped with adjustments for both air and water flow, which easily can be set for the required output.

- Optimum flushing of cooling systems - without solvent or harsh chemicals
- Individual adjustments for both air and water flow
- Combines water with compressed air for increased efficiency
- Multi-functional - possible to change the nozzle

Features:

- Effective flushing - without use of harsh chemicals
- Multi-functional - replaceable nozzle
- Individual regulations of both air and water flow
- Great mobility

Maximum Working Pressure:
6-10 bar 87-145 PSI, min 200 L/min



Jet Flusher

1307	Water Connection	Air Connection
102185-000	1/2" Nipple Water Connection, 3/4" GHT Water Hose Thread	1/4" Internal Thread (BSP)

The **Jet Washer** is a powerful washing gun which allows you to wash effectively without damaging the surface with high pressure.

The combination of compressed air and water gives ideal conditions for washing, where more power, than a regular water supply can provide, is needed.

The **Jet Washer** is designed to allow operators to come close without getting wet. There is no splash back.

- Effective cleaning without damage and splash back
- Multi-functional - possible to change the nozzle to the Jet Flusher nozzle
- Infinite adjustment of air and water flow
- Great mobility - built-in swivel
- Perfect for cleaning hard to reach places

Features:

- Effective cleaning
- No splash back
- Multi-functional - possible to change the nozzle
- Adjustable air and water flow
- Great mobility - built-in swivel
- Perfect for cleaning hard to reach places

Maximum Working Pressure:
6-10 bar 87-145 PSI, min 200 L/min,



Jet Washer

1307	Water Connection	Air Connection
102010-000	1/2" Nipple water Connection, 3/4" GHT Water Hose Thread	1/4" Internal Thread (BSP)

Fluid-Air Components Ltd

BLOW GUNS

Air Boy® Thrust Blow Gun

Air Boy® Thrust very high airflow The Air Bo ® Thrust blowgun provides a very high airflow and the thrust nozzle is unblockable. The Thrust nozzle increases the airflow by 100% due to the venturi principle. The Air Boy® Thrust blowgun is well suited for commercial vehicles, trade and industry and cleaning areas.

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 12 bar, 600 L/min (8 bar)



Air Boy® Thrust Blow Gun only

1307	Connection
140001-000	1/4" BSP

The Air Boy® Thrust blowgun provides a very high airflow and the thrust nozzle is unblockable

The Air Boy® Thrust blowgun comes with both a venturi nozzle (Thrust) and a 90° angle nozzle. The Thrust nozzle increases the airflow by 100% due to the venturi principle. The 90° angle nozzle is ideal for cleaning inside cylindrical objects or hard to reach places.

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 12 bar, 600 L/min (8 bar)



Air Boy® Thrust Blow Gun with 1 Metre & 90° Nozzle with 4 x 3 holes

1307	Connection
140009-000	1/4" BSP

The Air Boy® Thrust blowgun comes with both a venturi nozzle (Thrust) and an angle nozzle. The Thrust nozzle increases the airflow by 100% due to the venturi principle. The angle nozzle is ideal for hard to reach places. The counter nut makes sure that the user themselves can choose the direction to blow.

Working Temperature: -20°C to +80°C

Maximum Working Pressure: 12 bar, 600 L/min (8 bar)



Air Boy® Thrust Blow Gun with 1 Metre & Directional Nozzle with 1 Hole

1307	Connection
140074-000	1/4" BSP

Air Boy® Inflating Gun

Working Temperature: -10°C to +60°C



1/4' BSPP, for Footballs

1307	Nozzle	LPM
140108-000	Inflating Needle	200
	Tech Sheet 20793	

Working Temperature: -10°C to +60°C



1/4" BSPP, for Bicycles (Dunlop & Presta Valves)

1307	Nozzle OD mm	LPM
140118-000	8	380
	Tech Sheet 20424	

Blow Gun Accessories



Accessories

1307	Size mm	Type
144180	8	Protective Shield
	Tech Sheet 20430	

Cleaning Guns



Metal Nozzle

1307	Capacity Litres	Nozzle Length mm
142101-000	1.2	145

Maximum Working Pressure: 6 to 12 bar



1/4" BSPP, Cleaning Gun

1307	Capacity Litres	Nozzle Length mm	LPM
142130-000	1.2	150	100
142135-000	1.2	200	100
	Tech Sheet 20431		

Maximum Working Pressure: 6 to 12 bar



1/4" BSPP, Cleaning Gun with 1.5 Metre Suction Hose

1307	Nozzle Length mm	LPM
142131-000	150	100
	Tech Sheet 20431	

Sandblasting

Maximum Working Pressure: 6 to 12 bar



1/4" BSPP, Sandblasting Gun

1307	Capacity Litres	LPM
145100-000	1.2	450

Sandblasting Gun Accessories



Nozzle for Sandblasting Gun

1307	To Suit
145219	145102-000

Fluid-Air Components Ltd

BLOW GUNS

Blow Guns

Designed in Australia and sold for over 30 years, the Jamec Pem range is used globally in all automotive and industrial applications.

Features

- Variable air flow trigge
- Robust and durable ABS plastic handle
- Long reach with angle nozzle
- Ergonomic handle for maximum comfort
- Ideal for cleaning work areas and equipment



JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

230mm Angled Tipped Nozzle

1470	Description
171.078OS	230mm Angled Tipped Nozzle

Designed in Australia and sold for over 30 years, the Jamec Pem range is used globally in all automotive and industrial applications.

Features

- Strong rubber tipped nozzle, ideal for close delicate work
- Tough and durable ABS plastic
- Variable trigger airflo
- 1/4" Brass insert female connection
- Tough industrial quality



JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

100mm Rubber Tipped Angled Nozzle

1470	Description
171.034RTOS	100mm Rubber Tip Angled Nozzle

With a flexible 600 mm nozzle, the new Flex Nozzle blow gun from Jamec Pem provides the flexibilit , innovation and convenience to make it the best hand tool in any workshop.

Features

- Durable ABS plastic handle
- Pistol grip
- 600mm flexible nozzl
- 1/4" brass inlet



JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

600mm Flex Nozzle

1470	Description
171.067OS	600mm Flex Nozzle

Energy Save Blow Gun Kit

Ready for use, simple and ergonomic, the Parker Legris blow gun kit remains an essential item of equipment for any blowing or spraying operation in the industrial environment.

Parker legris



Kit

1012	Thread	ID mm	OD mm	Length Metres
LE-0631 00 23	1/4"	4	6	4

Universal Blow Gun

Fluid Carried: Compressed air.
Maximum Flow Pressure: 10 bar.
Safety Pressure at 6 bar: 0.5 bar.
Output at 6 bar: 255 Nl/min.
Force of Air Jet at 6 bar: 0,145 daN.
Noise Level (Norm. NFS 31 031): 83,3 dbA.

Parker legris



Dynamic Safety Blow Gun

1012	Thread
LE-0654 00 13	G1/4"
	Tech Sheet 20792

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DRIVEN BY AIR.

PCL







ERGO & ERGO EXTREME Blowgun Ranges

Design-engineered in the UK, with comfort and style in mind.

1603

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

BLOW GUNS

ERGO Blow Guns

Design-engineered in the UK, with comfort and style in mind, this range has the PCL DNA running right through it, from handle to tip. A sturdy product made from durable plastic that looks and feels good in your hand, it replaces the current 'best' range of blowguns, building on the high quality and performance for which PCL is renowned.

Features

- Newly designed air release valve built into the body, enabling trigger/air flow to be feathered
- Re-enforced webbing – Robust design gives strength and confidenc
- Easy to store with multiple hanging points
- 1/4" BSPP female brass inlet for increased durability



Blow Gun with Standard Nozzle

7002	Airflow	Sound	Conformity
BG7001	11.8 cfm/334 L/min	94 dBA	N/A



Designed to reduce the risk associated with noise exposure.

Low Noise Blow Gun

7002	Airflow	Sound	Conformity
BG7006	9.8 cfm/277 L/min	80 dBA	EU/2003/10/CE



Ideal when increased airflow is required.

TURBO Blow Gun

7002	Airflow	Sound	Conformity
BG7008	18.4 cfm/521 L/min	114 dBA	OSHA 1910.95 OSHASTD 1-13.1



Ideal when a larger dispersal of air is required.

Aircurtain Blow Gun

7002	Airflow	Sound	Conformity
BG7005	8.8 cfm/249 L/min	94 dBA	OSHA 1910.95 OSHASTD 1-13.1



Extended Conical Nozzle allows the operator to reach small areas.

Blow Gun with Extended Nozzle

7002	Airflow	Sound	Conformity
BG7002	11.8 cfm/334 L/min	94 dBA	N/A



Safety valve restricts airflow to the recommended 2 bar eliminating user error.

2 bar Regulated Safety Blow Gun with Standard Nozzle

7002	Airflow	Sound	Conformity
BG8001	8.9 cfm/252 L/min	90 dBA	EU/2003/10/CE



Safety valve restricts airflow to the recommended 2 bar eliminating user error.

2 bar Regulated Safety Blow Gun with Extended Nozzle

7002	Airflow	Sound	Conformity
BG8002	8.9 cfm/252 L/min	90 dBA	EU/2003/10/CE

Fluid-Air Components Ltd

BLOW GUNS

Ergo Extreme Blow Guns

Design-engineered in the UK, with comfort and style in mind.

Features

- Newly designed air release valve built into the body, enabling trigger/air flow to be feathere
- Re-enforced webbing – Robust design gives strength and confidenc
- Easy to store with multiple hanging points
- 1/4" BSPP female brass inlet for increased durability
- Additional cushioning with a flexible, rubber grip on the handle, which also offers increased strengt



Blow Gun with Standard Nozzle

7002	Airflow	Sound	Conformity
BG7501	11.8 cfm/334 L/min	94 dBA	N/A

Designed to reduce the risk associated with noise exposure.



Low Noise Blow Gun

7002	Airflow	Sound	Conformity
BG7506	9.8 cfm/521 L/min	80 dBA	EU/2003/10/CE

Ideal when increased airflow is required.



TURBO Blow Gun

7002	Airflow	Sound	Conformity
BG7508	18.4 cfm/521 L/min	114 dBA	OSHA 1910.95 OSHASTD 1-13.1

Ideal when a larger dispersal of air is required.



Aircurtain Blow Gun

7002	Airflow	Sound	Conformity
BG7505	8.8 cfm/249 L/min	94 dBA	OSHA 1910.95 OSHASTD 1-13.1

Extended conical nozzle allows the operator to reach small areas.



Blow Gun with Extended Nozzle

7002	Airflow	Sound	Conformity
BG7502	11.8 cfm/334 L/min	94 dBA	N/A

Safety valve restricts airflow to the recommended 2 bar eliminating user error.



2 bar Regulated Safety Blow Gun with Standard Nozzle

7002	Airflow	Sound	Conformity
BG8501	8.9 cfm/252 L/min	90 dBA	EU/2003//10/CE

Safety valve restricts airflow to the recommended 2 bar, eliminating user error.



2 bar Regulated Safety Blow Gun with Extended Nozzle

7002	Airflow	Sound	Conformity
BG8502	8.9 cfm/252 L/min	90 dBA	EU/2003//10/CE

Fluid-Air Components Ltd

BLOW GUNS

Metal Blow Gun with Safety Nozzle

This robust blowgun with 1/4" BSPP air inlet is manufactured from high quality die-cast alloy for a long, trouble-free life.



7002	Description
BG106	1/4" BSPP Inlet

Palm Blow Gun

The robust palm blowgun with 1/4" BSPP air inlet is manufactured from high quality die-cast alloy and is supplied with a safety nozzle and conical nozzle.

Features


- 1/4" Female connection
- Max W.P: 10 bar
- Airflow: 247 L/min (8.9 cfm



7002	Description
BG605	Blow Gun with Safety & Conical Nozzle

Palm Blow Gun 9" Extension Nozzle

BGN466 extension nozzle.
9" extension will screw directly into the BG605 blow gun.



7002	Description
BGN466	9" Extension to Suit BG605

Pistol Grip Blow Gun with Safety Nozzle

PCL's 1/4" BSPP pistol grip blowgun is manufactured from high quality die-cast alloy, giving the tool a long trouble-free life. Supplied with a conical and safety nozzle.



7002	Description
BG405	1/4" BSPP Inlet

Plastic Blow Gun

Manufactured from chemical and impact resistant acetal resin, PCL's range of entry level 1/4" BSPP pistol grip plastic blowguns are suitable for use with both air and water.



7002	Description
BG5002	Blow Gun with Standard 100mm Nozzle
BG5007	Blow Gun with 9" Extension Nozzle

Plastic Blow Gun with Safety Nozzle

PCL's entry level 1/4" BSPP pistol grip plastic blowgun is suitable for use with both air and water. It features an innovative safety nozzle design which ensures the airflow cannot be blocked.



7002	Description
BG5004	1/4" BSPP Blow Gun

Water Dispenser

Designed to dispense water in such applications as a radiator or windscreen water bottle fille .
The sturdy design incorporates a lever for instant flow and cut-off



7002	Description
RF104	Water Dispenser

PORTWEST

For **Hand Protection** see pages **1756-1758**




Fluid-Air Components Ltd

BLOW GUNS & AIR NOZZLES

Fully meets the EU Machine Directive's noise limitation requirements and OSHA's safety regulations.
A = nozzle length.

Silvent Safety Air Guns

Fitted with a Laval nozzle, this gun provides superior cleaning performance and optimal utilization of the compressed air.



1/4" BSPP 007-L Series Air Gun, Stainless Steel Laval Nozzle

0165	A mm
SIL-007-L	94
SIL-007-L-250	250
SIL-007-L-400	400
SIL-007-L-600	600
SIL-007-L-800	800
SIL-007-L-1000	1000
Tech Sheet 10747	


The zinc slotted nozzle allows powerful, quiet and efficient cleaning. Suitable for general purpose use.



1/4" BSPP 007-Z Series Air Gun, Zinc Slotted Nozzle

0165	A mm
SIL-007-Z	100
SIL-007-Z-250	250
SIL-007-Z-400	400
SIL-007-Z-600	600
SIL-007-Z-800	800
SIL-007-Z-1000	1000
Tech Sheet 20785	

This gun is fitted with a zinc slotted nozzle and is suitable for general purpose cleaning where the nozzle is subject to little or no mechanical wear.



1/4" BSPP 500 Series Air Gun, Zinc Slotted Nozzle

0165	A mm
SIL-500-Z	94
SIL-500-Z-250	250
SIL-500-Z-400	400
SIL-500-Z-600	600
SIL-500-Z-800	800
Tech Sheet 10749	

Pro One's specially designed nozzle makes it possible to combine effective blowing power and a low noise level. Pro One's unique design reduces the turbulence that is generated when blowing with compressed air. This means the noise level can often be reduced by over 10 dB (A) when blowing.

Blowing Force: 2.8 N (9.9 oz).

Sound Level: 78 dB (A).

Air Consumption: 14Nm3/h (8.2 scfm).



1/4" BSPP Pro One Model, Stainless Steel Blow Guns

0165	A mm
SIL-PRO-ONE	30
Tech Sheet 67994	


Fluid-Air Components Ltd

BLOW GUNS & AIR NOZZLES

Fully meets the EU Machine Directive's noise limitation requirements and OSHA's safety regulations.
A = nozzle length.

Silvent Safety Air Guns

Fitted with a stainless steel Laval nozzle, this gun creates a highly concentrated air stream that moves at supersonic speed.



1/4" BSPP 500-L Series Air Gun, Stainless Steel Laval Nozzle

0165	A mm
SIL-500-L	94
SIL-500-L-250	250
SIL-500-L-800	800
SIL-500-L-1000	1000
Tech Sheet 10748	

Fitted with a new generation of zinc Laval nozzle, this gun has a mix of divergent slots and holes surrounding the central Laval orifice, providing quiet, powerful and laminar air flo . This safety air gun is especially suitable for sweeping large areas or general purpose cleaning of parts and machines. The fin design of the nozzle prevents direct contact with skin.

Sound Level:
78 dB (A).

Maximum Pressure:
0.7 MPa.



1/4" BSPP 501-L Series Air Gun, Zinc Hole Nozzle

0165	A mm
SIL-501-L	30
Tech Sheet 67992	

An air gun with a flat nozzle for applications where the air system needs to strike a wider surface, providing quick and efficient blow-off



1/4" BSPP 5920 Series Air Gun, Zinc Flat Nozzle

0165	A mm
SIL-5920	92
Tech Sheet 10764	

An air gun fitted with an aerodynamic aluminium nozzle that offers a blowing force equivalent to five conventional air guns.



3/8" BSPP 2000 Series Aluminium Air Gun, Slotted Nozzle

0165	A mm
SIL-2055-A	49
SIL-2055-A-500	513
SIL-2055-A-1000	1013
Tech Sheet 20786	

Silvent Air Nozzles

Fitted with a stainless steel Laval nozzle. A core stream travelling at supersonic speed, surrounded by a protective sheath of air moving parallel to the central jet, makes optimal use of your compressed air. Around the Laval orifice there are divergent slots that generate a quiet, powerful and laminar air stream. The blowing force is approximately five times that of an ordinary air gun. Despite the high blowing force, both the noise level and air consumption are low. Frequently used in the glass industry, paper mills, foundries, steel mills, etc.

Sound Level: 92.6 dB (A).

Maximum Pressure:
0.7 MPa.



1/2" BSPP 750 Series Heavy-duty, Air Gun & Nozzle, All Stainless Steel

0165
SIL-755-L
Tech Sheet 67995

The 511 and 512 slot nozzles generate a directed air jet. The nozzles are well suited to all-purpose blowing, and blowing in confined spaces



Slot Nozzles, BSPP & Metric

0165	Thread	Length mm
SIL-511	1/8"	55.8
SIL-512	1/8"	30.3
SIL-5001	M7 x 0.75 Female	18.3
SIL-5003	M7 x 0.75 Male	23.3
Tech Sheet 10751		

An aluminium nozzle designed with aerodynamic slots, producing a strong, quiet and effective air stream.



3/8" BSPP High Blast Aluminium Nozzle

0165	Length mm
SIL-2005	46
Tech Sheet 10760	

PORTWEST

For **Eye Protection**
see page **1754**





Fluid-Air Components Ltd

BLOW/VACUUM GUNS & KITS

Wonder Gun

Wonder Gun is a robust, made of aluminium tool that helps to maintain cleanliness in workplace. It can be used as traditional blow gun as well as vacuum gun sucking contaminants to the bag (sold separately).



BSPP Inlet

0025	Thread
WG-9	1/4"
Tech Sheet 10766	

Wonder Gun Kit

High powered blow or vacuum gun.

Kit consists of:

1 x wonder gun
1 x dust collection bag
1 x round extension nozzle
1 x flat nozzle
1 x brush nozzle
1 x miniature nozzle
1 x 1 metre suction hose



BSPP Inlet

0025	Thread
WG-900KIT	1/4"
Tech Sheet 10767	

Spare Parts for Wonder Gun Kit



0025	Type
WGS-01	Air Hose
WGS-02	Bag
WGS-03	Round Nozzle
WGS-04	Flat Nozzle
WGS-05	Brush Nozzle
WGS-06	Tiny Nozzle
HC25-40	Hose Clip

Vacuum Guns

Deep hole air cleaning gun.

The BV22D/H has been designed with EYE SAFETY in mind.

The BV22D/H is designed to blow the chip up and vacuum it away simultaneously.



Deep Hole Cleaning Gun, BSPP

0025	Thread
BV22D/H	1/4"
Tech Sheet 10782	

Simple, safe and incredibly efficient

Air Pumps are used in industry to remove waste material from around working machinery by vacuum recovery, or by high powered air blasting. Using a unique spiral exhaust air flow principle, the AP22 gives greater vertical and horizontal conveying distances.

Being air-powered means no electrical breakdowns or maintenance costs and makes wet vacuuming completely safe.



Nylon Air Pump, 6mm Push-in

0025	Thread
AP22	1/4"
Tech Sheet 10780	

Accessories for Vacuum Guns



0025	Type
BV22-2	Vacuum Head
BV22-4	Long Reach Wand
BV22-5	Crevice Tool
BV22-6	Round Brush


Fluid-Air Components Ltd

Drag-in pump kit

FT PRO®

The drag-in pump kit will remove liquids from lathes, milling machines, sumps, etc, including metal chips, in seconds.

Simply attach the kit to a standard, seated 45 gallon drum and connect to an air supply.



- Easy set-up and operation
- Heavy-duty construction
- No moving parts
- Auto shut off

Drag-in Pump Kit

0025
DPK-1



Pressure	**Kg/cm²**	4	5	6	7	8
	psi	56.89	71.11	85.33	99.56	113.78
Air Consumption	**M³/min**	0.26	0.32	0.37	0.5	0.6
	cfm	9.18	11.29	13.06	17.65	21.18
Total Discharge	**mm Hg**	1.90	2.00	2.30	3.5	3.8
	cfm	67.08	70.62	81.21	123.85	134.17
Vacuum	**mm Hg**	220	272	314	335	375
	in Hg	8.66	10.70	12.36	13.2	14.8
Water	**Litres per second**	1.42	1.66	2.00	2.5	3.4
Oil SAE30	**Litres per second**	1	1.3	1.6	2	2.5

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

AIR JETS

Air Jets

- Drying/removing liquid films from surfaces
- Controlling the coating of surfaces
- Blowing off/removing dust and debris
- Cooling or heating of materials
- Separating different weights or sizes



BSPP

0424	Thread	Material
PFFN-1/4	1/4"	Plastic
AFFN-1/4	1/4"	Aluminium

AIR JETS

Air jets utilise the Coanda effect (wall attachment of a high velocity fluid) to produce air motion in their surroundings. A small amount of compressed air is forced through an internal ring nozzle above sonic velocity. A vacuum is produced, pulling large volumes of surrounding or free air through the jet.

Multi-channel Flat Fan Nozzle

Powerful air jet, acting upon areas. Low noise level, low air consumption.

Applications: blowing off and blowing out, cleaning, drying, cooling, conveying with air.



BSPP

0025	Thread	Material
60013056AC	1/4"	Plastic/Pom
60028342AC	1/4"	Aluminium
Tech Sheet 20087		

Multi-channel Round Jet Nozzle

The multi-channel round jet nozzles of the 600.326 series generate a powerful, circular air jet. The noise level and air consumption remain low even at higher air pressures. The special geometry at the nozzle outlet prevents air penetration into human skin. These nozzles comply with the OSHA standards.

Applications: targeted blowing out and blowing off with compressed air guns.

Reduction of noise level of up to 12db(a).



Plastic/Pom



Zinc

BSPP

0025	Thread	Material
60032656AC	1/4"	Plastic/Pom
6003263WAC	1/4"	Zinc
Tech Sheet 20087		

Mini Round Jet Nozzle

Applications: especially for blowing out pocket holes.



BSPP

0025	Thread	Material
60038830AA	1/8"	Brass/Pom
Tech Sheet 20087		

Fluid-Air Components Ltd

BLOW GUNS & AIR NOZZLES

Silvent Air Nozzles

These popular nozzles are installed in thousands of different applications. The protective flanges prevent direct contact between skin and exhaust ports.



1/4" BSPP Hole Nozzles

0165	Nozzle
SIL-208	Female Zinc
SIL-209	Male Zinc
SIL-210	Female Aluminium
SIL-211	Male Aluminium
SIL-215	Female Nickel
SIL-216	Male Nickel
SIL-218	Male Rilsan
Tech Sheet 10752	

Its aerodynamic slots achieve optimal utilization of the compressed air while keeping the noise level to a minimum.

stainless steel



1/2" BSPP, 700 Series Stainless Steel Nozzle

0165	Length mm
SIL-705	29
Tech Sheet 10762	

These flat nozzles are designed to generate a broad and efficient fan of air. They are outstanding for use wherever a wide but thin striking surface is required.



900 Series Flat Nozzle, BSPP

0165	Thread	Material	Nozzle
SIL-921	1/8"	Zinc	Flat Male
SIL-920B	1/8"	Zinc	Flat Female
SIL-920A	1/4"	Zinc	Flat Male
SIL-9002W	1/4"	Zytel	Flat Male
Tech Sheet 10763			

Available with or without flow regulation. Built-in flo regulation allows optimal utilization of compressed air. Adjusting the blowing force minimizes both energy consumption and noise level.

stainless steel



900 Series Flat Nozzle, Stainless Steel, BSPP

0165	Thread	Nozzle
SIL-973	1/4"	Flat Male
SIL-973F	1/4"	Flat Male with Regulation
Tech Sheet 10768		

A small angled flat nozzle that generates a broad but thin air cone. The small mounting dimensions are especially suitable for machine designs where space is limited.



1/8" Angled Flat Nozzle

0165
SIL-961
Tech Sheet 10753

Allows quick and easy adjustment to the blowing angle. Maintains the desired position, even at high pressures. Available in six standard lengths.

Sound Level: 78 dB(A).

Maximum Pressure: 1 MPa.



3/8" BSPP, Magnetic Base with Single Flexbow Hose

0165	Length mm
SIL-221-L	200
SIL-231-L	300
SIL-241-L	490
SIL-251-L	590
Tech Sheet 67993	

Silvent Air Knives

Aluminium manifolds are used to build the air knives. The length of the manifold and the number of nozzles can be tailored to each customer's specific needs



3/8" BSPP Flat Nozzle Air Knives

0165	Nozzle
SIL-392	2
SIL-394	4
SIL-396	6
Tech Sheet 10765	



Angled Nozzle Air Knives

0165	Nozzle
SIL-362	2
SIL-364	4
SIL-366	6
Tech Sheet 10756	

Blow Gun Pressure Reducers



0165	Thread In/Out	Outlet Pressure
DRV13/30	1/4"	3
PR04/04	1/4"	4
DRV13/50	1/4"	5
DRV13/60	1/4"	6

Nozzle Ball Joints



0165	Material	Thread BSPP
092.024.30.AC	Brass	1/4" MF

Test Equipment

Simply insert the end of the blow gun into the rubber tip and operate the gun to give test reading.



OSHA Gauge

0165
SIL-OSH
Tech Sheet 10757

Fluid-Air Components Ltd

AIR MOVERS

BRAUER
Tooling • Automation • Measurement

Brauer airmovers have many uses such as: drying wet surfaces, blowing off and cleaning mechanical parts, cooling moulds, fume extraction and venting tanks.

Material: zinc alloy.
Standard Gap: 0.05mm (0.15mm for AM125).
DBA Quoted at: 5.5 bar.

Air Movers

Note: BR-AM35 shims not required.
BR-AM75 cpare shims available.



Standard Fixed Gap Air Movers, BSPP

0119	Thread	DBA
BR-AM10	1/8"	72
BR-AM20	1/4"	79
BR-AM35	3/8"	80
BR-AM40	3/8"	80
BR-AM75	1/2"	80
Tech Sheet 2046		

Strip air movers produce a curtain of air along the length of the application. The strip air mover uses the same Coanda effect utilised in our other air amplifiers.

No moving parts – compressed air from a local production line source can be utilised. Output volumes almost twenty times higher.

Highly efficient – significant compressed air savings ca be achieved with short investment paybacks. Low noise levels. Stainless steel options.


Manufactured in any length from a combination of our standard sizes.

Material: aluminium/zinc-plated steel.
Standard Gap: 0.05-0.10mm.
DBA at 5.5 bar: 80
Shims: not required.
Standard Inlet Thread: 1/4" BSPP.



Strip Air Movers, BSPP

0119	Length mm	Thread
BR-SE150	150	1/4"
BR-SE300	300	1/4"
BR-SE450	450	1/4"
BR-SE600	600	1/4"
Tech Sheet 10790		



Spare Shims

0119	To Suit	Size mm
BR-SH10/1.5	BR-AM10	1.5
BR-SH10/2	BR-AM10	2
BR-SH10/3	BR-AM10	3
BR-SH20/1.5	BR-AM20	1.5
BR-SH20/2	BR-AM20	2
BR-SH40/1.5	BR-AM40	1.5
BR-SH40/2	BR-AM40	2
BR-SH40/3	BR-AM40	3



Universal Connector Joints

0119	Thread
BR-AM40UJ	3/8"
Tech Sheet 10793	



Magnetic Base

0119
BR-MAGNETICBASEM

Adjustable Air Movers

Note: shims not applicable.



Aluminium Alloy, BSPP

0119	Thread	DBA
BR-AM10A	1/8"	73
BR-AM20A	1/4"	79
BR-AM35A	3/8"	80
BR-AM60A	3/8"	80
BR-AM75A	1/2"	80
Tech Sheet 20370		

stainless steel



Stainless Steel, BSPP

0119	Thread	DBA
BR-SS60A	3/8"	80
BR-SS75A	1/2"	81
Tech Sheet 20371		

Blow Guns



Trigger Action, BSPP

0119	Thread
BR-AG32LC	1/4"
Tech Sheet 20374	

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR KNIVES & AMPLIFIERS

Neublade Airstrip

The Neublade from Beckair utilises innovative technology developed to give the highest performance, lowest noise and lowest air consumption compared to any other product.

The powerful, whisper-quiet blade of air is ideal for drying, cleaning, cooling or containing in all kinds of process, food and manufacturing applications.


The key to its performance is our flow straightening technology (patent applied for) which provides an exceptionally laminar sheet of air. The low levels of turbulence also mean extremely low noise (65dB).

- No moving parts – the Neublade is maintenance free
- Ultra low air consumption – significantly lower running costs than standard nozzles and strips
- Ultra-quiet operation (typically 65 dB) for an improved working environment
- Easily mounted onto existing installations
- Choice of air entry for maximum flexibilit

The Neublade is manufactured from extruded, anodised aluminium and comes complete with quick fit hose connector. Because of the method of construction, we are able to offer the Neublade in any length up to 2m long. Please call our sales team for further information.

Applications

- Drying: printing, paints, coatings, components, conveyor belts
- Cleaning: components, conveyors, instruments lens, dust removal, waste removal
- Cooling: components
- Air curtain: fume containment, heat containment from ovens and furnaces



How Neublade can reduce your operating costs

Type of Airstrip	Type of Airstrip		Noise Level	Power Required	Running Costs
	SLPM	SCFM	Db(A) at 1M	kW SLPM	per Year*
5 holes in 50mm length of pipe (3mm or 1/8")	1980	70	95	10.0	£960
Standard air wipe (50mm)	450	16	85	2.3	£220
Neublade (50mm)	124	4.5	65	0.65	£62

*Based on 40 hours per week, 48 weeks per year with an energy cost of around £0.05 per kWh.

BSP Ports

9039	Length		Inlet	Air Consumption @ 4 bar		Noise Db (A) at 1M
	mm	Inches		SLPM	SCFM	
BNEUBLADE/80	80	3"	1/4" BSP + Push-in Fitting	198	7	65
BNEUBLADE/150	150	6"	1/4" BSP + Push-in Fitting	368	13	65
BNEUBLADE/300	300	12"	1/4" BSP + Push-in Fitting	736	26	65
BNEUBLADE/450	450	18"	1/4" BSP + Push-in Fitting	1104	39	65
BNEUBLADE/600	600	24"	1/4" BSP + Push-in Fitting	1471	52	65
BNEUBLADE/750	750	30"	1/4" BSP + Push-in Fitting	1839	65	65
BNEUBLADE/900	900	36"	1/4" BSP + Push-in Fitting	2207	78	65



Ringjet Air Amplifier


Ringjets air amplifiers are bladeless, motorless fans which can be used for cooling, extracting, drying and ventilating in process, food and manufacturing industries.

Using a small volume of compressed air as the power source, Ringjets utilise the 'Coanda' effect to draw larger volumes of ambient air into the device to amplify the air flow by up to 25 times

- No moving parts – Ringjet is maintenance free
- No electricity required – safe to use in wet locations
- Adjustable flow control using air gap and inlet pressur
- Energy efficient – low running cost
- Low cost
- Quiet operation (less than 80 dB (A))
- Also available in stainless steel

Applications

- Cooling: components, mouldings, extrusions, people, components on test
- Extraction: fumes, water, dust, waste material
- Drying: components, printing, material



BSP Ports

9039	Throat Diameter mm	Air Inlet BSP	Air Consumption @ 4 bar		Outlet Airflow		Hose Size for Ducting		OD mm	Length mm	Material
			SLPM	SCFM	SLPM	SCFM	mm	Inches			
BRJ12A	12	G1/8"	170	6	5,666	200	19	3/4"	25	63	Anodised Alloy
BRJ20A	20	G1/8"	283	10	6,800	240	32	1.1/4"	40	63	Anodised Alloy
BRJ25A	25	G1/4"	397	14	11,333	400	38	1.1/2"	50	90	Anodised Alloy
BRJ40A	40	G1/4"	510	18	14,150	500	50	2"	63	95	Anodised Alloy
BRJ50A	50	G3/8"	962	34	20,666	730	76	3"	90	135	Anodised Alloy
BRJ75A	75	G1/2"	1416	50	33,333	1,178	100	4"	132	165	Anodised Alloy
BRJ12S/S	12	G1/8"	170	6	5,666	200	19	3/4"	25	63	Stainless Steel (316)
BRJ20S/S	20	G1/8"	283	10	6,800	240	32	1.1/4"	40	63	Stainless Steel (316)
BRJ25S/S	25	G1/4"	397	14	11,333	400	38	1.1/2"	50	90	Stainless Steel (316)
BRJ40S/S	40	G1/4"	510	18	14,150	500	50	2"	63	95	Stainless Steel (316)
BRJ50S/S	50	G3/8"	962	34	20,666	730	76	3"	90	135	Stainless Steel (316)



Fluid-Air Components Ltd

AIR KNIVES & AMPLIFIERS


Ringjet Air Conveyors

Ringjets air conveyors are bladeless, motorless fans which connect to flexible hose and are ideal for conveying and extracting all kinds of materials in process, food and manufacturing industries. Using a small volume of compressed air as the power source, Ringjets utilise the 'Coanda' effect to draw larger volumes of ambient air into the device to amplify the air by up to 25 times. Ringjet conveyors are capable of moving material over long distances and this can be increased by adding additional conveyors into the line.

- No moving parts – Ringjet is maintenance free
- No electricity required – safe to use with liquids and wet material
- Adjustable flow control using air gap and inlet pressur
- Energy efficient – low running cost
- Ideal for conveying over long distances
- Quiet operation (less than 80 dB (A))

Applications

- Conveying: plastic pellets, waste removal, food products, pills and tablets, small components, dust, liquids, paper trim
- Extraction: fumes, liquids, dust, waste material



HOW THE RING JET AIR CONVEYORS WORKS



BSP Ports

9039	Throat Diameter mm	Air Inlet BSP	Air Consumption @ 5 bar		Outlet Airflow		Hose Size for Ducting		OD mm	Length mm	Material
			SLPM	SCFM	SLPM	SCFM	mm	Inches			
BRJ12C	12	G1/8"	170	6	5,666	200	19	3/4"	25	95	Anodised Alloy
BRJ20C	20	G1/8"	283	10	6,800	240	32	1.1/4"	40	95	Anodised Alloy
BRJ25C	25	G1/4"	397	14	11,333	400	38	1.1/2"	50	135	Anodised Alloy
BRJ40C	40	G1/4"	510	18	14,150	500	50	2"	63	135	Anodised Alloy
BRJ50C	50	G3/8"	962	34	20,666	730	76	3"	90	203	Anodised Alloy


Airmiser Nozzles

The Airmiser uses a series of annular nozzles instead of a single hole to create a safer, more efficient, lower noise alternative to open tubes and pipes. A small volume of compressed air is amplified up to 25 times by utilising the 'Coanda' effect to induce a higher flow of ambient air into the air stream.

Because of the risk of serious injury from compressed air entering the bloodstream from single open pipes at high pressure, the multi-nozzle arrangement of the Airmiser is designed to be much safer alternative.

Replacing open jets with Airmisers will give significantly reduced air consumption and lower noise levels and, in most cases, it is a simple operation to install Airmiser nozzles. Airmisers are suitable for use individually or in multiple arrays to create a much greater effect.

- No moving parts – Airmiser is maintenance free
- Low air consumption – significantly lower running costs than open holes and pipes
- Quieter operation (below 80 DB (A) at 1m) for an improved working environment
- Easily mounted onto existing installations



HOW THE AIRMISER WORKS



BSP Ports

9039	Air Inlet BSP	Air Consumption @ 5 bar		Thrust		Noise Level Db (A) at 1M
		SLPM	SCFM	N	LBF	
BAMSA	G1/8"	225	8	1.8	0.4	65
BAMBH	G1/4"	566	20	5.2	1.2	74
BAMSASS	G1/8"	225	8	1.8	0.4	65
BAMBHSS	G1/4"	566	20	5.2	1.2	74

AIR KNIVES & AMPLIFIERS

Pneu-Power Air Conveyors

The Beckair Pneu-Power is a bladeless, motorless fan which connects to flexible hose and gives high vacuum or high flow for conveying and extracting all kinds of materials in process, food and manufacturing industries.

Using a small volume of compressed air as the power source, the Pneu-Power utilises the 'Coanda' effect to draw larger volumes of ambient air into the device to amplify the air flow by up to 25 times

The Pneu-Power has very high performance and is capable of moving material over very long distances. The Pneu-Power is extremely robust, being manufactured from cast aluminium and is designed for use in harsh environments.

For applications where extraction only is required, the silencer (supplied) diffuses the air and reduces the noise from the device.


- Type A offers higher flows, type B offers higher suctio
- No moving parts – Pneu-Power is maintenance free
- No electricity required – safe to use with liquids and wet material
- Adjustable flow control using air valve and inlet pressur
- Energy efficient – low running cost
- Quiet operation (less than 80 dB (A))


Applications

- Conveying tank filling/emptying, hopper loading, powde , granules, swarf removal, dust, liquids
- Extraction fumes, liquids, dust, waste material









BSP Ports

9039	Air Inlet BSP	Air Consumption @ 6 bar		Outlet Airflow		Vacuum		
		SLPM	SCFM	SLPM	SCFM	mm WG	Inch WG	Inch HG
BNEUPOWERA	G1/4"	885	31	2250	80	2072	82"	6"

Clustajet Ventilators

Clustajet ventilators are a compressed air operated fan which utilise our Ringjet technology to create a robust, maintenance free, high performance ventilator.

Because the Clustajet uses compressed air, no electrical supply is needed making it suitable for safe use in damp or wet locations.

Multiple Ringjets are positioned inside a steel casing to create a space rocket jet effect which gives the unit its high performance. For a given airflo , Clustajets are lighter in weight and smaller than equivalent electric fans.

- No moving parts – Clustajet is maintenance free
- No electricity required – safe to use in damp or wet locations
- Adjustable flow control using the control valv
- Standard Clustajets are manufactured from a strong welded steel casing
- Other options include:
- Plastic
- Flexible hose

Applications

- Extraction: welding fumes, solvent vapours, dust
- Ventilating: confined spaces, tanks, sewers, tunnel
- Cooling: components, pipework



BSP Ports

9039	Hose Size		Air Inlet BSP Inches	Airflow Consumption @ 4 bar		Outlet Air Flow		Dimensions					
	SLPM	SCFM		SLPM	SLPM	SPLM	SCFM	mm	Inches	mm	Inches	mm	Inches
BCJ425	102	4"	G1/4"	395	14	12,700	450	102	4"	180	7"	230	9"
BCJ620	150	6"	G1/2"	1130	40	18,400	650	152	6"	254	10"	356	14"
BCJ825	203	8"	G1"	2265	80	34,800	1230	203	8"	305	12"	457	18"
BCJ1250	305	12"	G1"	5375	190	87,750	3100	305	12"	406	16"	508	20"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 16

Fuelling, Lubrication, Wash Down & Misting

16.01 Fuelling Triggers, Nozzles & Meters 1617-1626

16.02 Fuelling Filtration 1627-1631

16.03 Transfer Pumps 1632-1638

16.04 Greasing & Lubrication Equipment 1639-1649

16.05 Oil Drain Plugs 1650-1653

16.06 Tank Level Gauges 1654

16.07 Workshop Fluid Transfer 1655-1656

16.08 Water Guns & Couplings 1657-1665

16.09 Pressure Wash Lances & Triggers 1666-1672

16.10 Pressure Wash Adaptors, Nozzles & Irrigation Equipment 1673-1680

16.11 Pressure Sprays & Vehicle Cleaning Equipment 1681-1683

16.12 Diaphragm Pumps 1684-1685

16.13 Misting Systems 1686-1696

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 16

16.01 Fuelling Triggers, Nozzles & Meters

1617-1626

- Fuelling Equipment & Accessories
- Fuelling Equipment & Accessories
- Fuel Dispensing Hose & Gravity Hose Kits



16.02 Fuelling Filtration

1627-1631

- Fuelling Filtration
- Diesel Oil Filters



16.03 Transfer Pumps

1632-1638

- Barrel Pumps
- Rotary Pumps & Diaphragm
- Manual Transfer Pumps
- Dosing Pumps
- Electrical Transfer Pumps
- Air Operated Transfer Pump
- Manual & Compressed Air Transfer Pumps & Kits
- Fuelling Equipment & Accessories



16.04 Greasing & Lubrication Equipment

1639-1649

- Greasing & Lubrication Equipment
- Pressure Hoses



16.05 Oil Drain Plugs

1650-1653

- Quick Oil Drain Plugs



16.06 Tank Level Gauges

1654

- Tank Gauges



16.07 Workshop Fluid Transfer

1655-1656

- Workshop Fluid Transfer



Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

Fuelling, Lubrication, Wash Down & Misting

16.08 Water Guns & Couplings

1657-1665

- Heavy-duty, Brass Water Guns
- Washdown & Cleaning Products
- Water Gun
- 1/2" System
- 3/4" System
- 1" System
- Click™ System
- Stainless Steel



16.09 Pressure Wash Lances & Triggers

1666-1672

- Wash Down Equipment



16.10 Pressure Wash Adaptors, Nozzles & Irrigation Equipment

1673-1680

- Wash Down Equipment
- Spray Guns & Accessories
- Sprinkler



16.11 Pressure Sprays & Vehicle Cleaning Equipment

1681-1683


- Pressure Spray Equipment
- Pressure Sprayers
- Commercial & Domestic Vehicle Cleaning Equipment



16.12 Diaphragm Pumps

1684-1685

- Pumps & Process Equipment



16.13 Misting Systems

1686-1696

- Misting Systems - Pump Kits
- Misting Systems - Air Injection Dry Fog System
- Misting Systems - Fans
- FO-500 Ultra-low Volume Fogger
- Misting Systems - Adaptors
- Misting Systems - Filters
- Misting Systems - Controllers



Fluid-Air Components Ltd

FUELLING EQUIPMENT & ACCESSORIES

Ultra High Speed Auto Nozzle

- Only suitable with diesel or biodiesel up to B30.
- Automatically shuts-off the flow of fuel when vehicle tank is full
- Ideal for refuelling very large vehicles and heavy plant equipment
- Cast aluminium body
- 3 position stay open latch
- Complete with 1.1/2" BSPF swivel inlet

Maximum Flow: 250 L/min.

For use with electric pumps only

Maximum Working Pressure:
72 psi (5 bar)



BSPP

0225	Thread	LPM
NOZA.250S	1.1/2"	250

Trigger Nozzles

- Manual trigger nozzle for use with diesel, HVO and biodiesel up to B30. For use with gravity or electric pumps up to 80L/min. Not automatic shut off.

Body: Aluminium
Seals: Nitrile

Maximum Working Pressure:
50psi (3.5bar)

2 YEAR WARRANTY



BSPP

0225	Thread
2019-9295	1"

- Suitable with diesel, HVO and oils to SAE 90.
- Aluminium body enclosed in a plastic shell making it comfortable even when used at low temperatures.
- 1" BSPF swivel inlet.
- Can be used with gravity feed tanks or electric pumps.
- Integral hook for tidy storage when not in use.

Maximum Flow: 150 L/min.

Maximum Working Pressure:
142 psi (10 bar)



Manual

0225	LPM
NOZ.S3000	150

Nozzle Holder



0225
HANG.P

Polypropylene Manual Nozzle

- Suitable with diesel, HVO and water.
- Polyethylene body. 3/4" hose tail.
- Can be used with gravity feed tanks or electric pumps.
- Integral hook for tidy storage when not in use.

NOZ.C
Nitrile seals, mild steel spring.
Max. Flow: 60 L/min.

Maximum Working Pressure:
29 psi (2 bar)



0225	Seal
NOZ.C	Nitrile

Automatic Trigger Nozzles

- Suitable with diesel, HVO or biodiesel up to B30.
- Automatically shuts-off the flow of fuel when vehicle tank is full.
- 3 position stay open latch. 20-80 L/min, max. pressure 50 psi (3.5 bar).

For use with electric pumps only.
Not suitable for vehicles with small filler necks.

Body: Aluminium

Maximum Working Pressure:
50 psi (3.5 bar)



BSPP

0225	Thread	LPM
2019-9311	3/4"	80
2019-9303	1"	80



Economy, BSPP

0225	Thread	LPM	Colour
NOZA.60S	1"	60	Red
NOZA.120S	1"	120	Blue

Universal Reducing Bush



0225	Thread A	Thread B
BSH.4.3A	1" Male	3/4" Female

Trigger Gun with Electronic In-line Flow Meter

- Manual trigger nozzle for use with diesel gasoline, B100 biodiesel and oils to SAE 90.

Flow Meter Technical Data
Material: Aluminium
Seal Material: Viton and florinated silicone rubber



1" BSPP Trigger Gun & Flow Meter

0225	Thread	Max Pressure Bar	LPM
CD-OG01	1"	20	10-60
Tech Sheet 60124			

Professional Automatic Nozzle for Diesel


- Suitable with diesel, HVO and biodiesel up to B30.
- Automatically shuts-off the flow of fuel when vehicle tank is full.
- 3 position stay open latch, which may be disabled if required.
- 1" BSPF swivel inlet.

For use with electric pumps only.
Not approved for use on resale dispensers.

Max. Flow: Standard 10-80 L/min
High Speed 80-140 L/min

Standard version only

Maximum Working Pressure:
NOZA.X - 0.4-5 bar
NOZA.X25 - 0.4-3 bar



0225	Description	LPM
NOZA.X	Standard (ATEX)	80
NOZA.X25	Hi-speed	140

Stainless Steel Automatic Nozzle

- Suitable for use with diesel or Adblue®. Automatically shuts-off the flow of fuel when vehicle tank is full.
- 3 position stay open latch.
- 304 stainless steel body, viton seals.
- Flow rate up to 45 L/min.

For use with electric pumps only.
Inlet: 3/4" (20mm) Hose barb.
Maximum Flow: 60 L/min.

Maximum Working Pressure:
50 psi (3.5 bar)

Working Temperature:
-10°C to +50°C

Adblue®



0225	Seal
NOZA.SS	Viton
Tech Sheet 20033	

Fluid-Air Components Ltd

FUELLING EQUIPMENT & ACCESSORIES

Redashe

Automatic Trigger Nozzles



BSP

0122	Thread
ZFN34	3/4"

Auto Shut-off Nozzle Petrol & Diesel



0122	Thread
J1789022-1	3/4"

High Volume Auto Nozzle Petrol & Diesel



0122	Thread
J1789023-1	1"



0122	Thread
J18312002-1	3/4"

Oil Guns

- Semi-automatic Tip



Digital Oil Gun with Rigid & Flexible Hose, BSPP

0122	Thread
JDA-01	1/2"
Tech Sheet 2054	



Digital Preset Oil Gun

0122
J18133512

- 5-Digit easy to read LCD display powered by 3V CR2 battery
- Low battery indicator
- Rubber protection shroud for meter

Working Pressure:
5 - 50 bar



Digital High Flow Oil Gun, BSP

0122	Inlet Female BSP
J18128003	3/4"
Tech Sheet 71695	

- Semi-automatic Tip



Manual Oil Gun with Flexible Hose, BSPP

0122	Thread
JA-01	1/2"
Tech Sheet 2055	

- Manual Tip



Manual Oil Gun with Rigid Tube, BSPP

0122	Thread
JM-01	1/2"

FUEL DISPENSING HOSE & GRAVITY HOSE KITS




Rubber Alloy Dispensing Hoses

Oil resistant rubber alloy, suitable for use with diesel, air and water delivery.

Cover: black, weather and ozone resistant with purple strip.

Safety Factor: 3-1.

Maximum Working Pressure: 20 bar



3/4" BSPP Male/Male x 3/4" ID Replacement Hose

0225	Length Metres
RTDH-34-3	3
RTDH-34-4	4
RTDH-34-5	5
RTDH-34-6	6


1" BSPP Male/Male x 1" ID Replacement Hose

0225	Length Metres
RTDH-1-3	3
RTDH-1-4	4
RTDH-1-5	5
RTDH-1-6	6
RTDH-1-8	8
RTDH-1-10	10
RTDH-1-12	12

1" BSPP Male/Male x 1" ID Super Flexible Deluxe Replacement Hose

0225	Length Metres
DRTDH-1-3	3
DRTDH-1-4	4
DRTDH-1-5	5
DRTDH-1-6	6
DRTDH-1-8	8
DRTDH-1-10	10
DRTDH-1-12	12

Gravity Hose Kits



Gravity Hose Kit

Deluxe Gravity Hose Kit

Hose Info Maximum Working Pressure: 20 bar

Oil resistant rubber alloy, suitable for use with diesel, air and water delivery.

Cover: black, weather and ozone resistant with purple strip.

Safety Factor: 3-1

Nozzle Info. Maximum Working Pressure: 142 psi (10 bar)

Maximum Flow: 150 L/min

Manual trigger, suitable for use with diesel, biodiesel up to B100 and oils to SAE 90.

Working Temperature: -20°C to +60°C

Maximum Working Pressure: 58 psi (4 bar)

Maximum Flow: 80 L/min

Manual trigger, suitable for use with diesel.

1" BSPP Male/Male x 1" ID Deluxe Gravity Hose Kits

0225	Length Metres
DASS-RTDH-1-3	3
DASS-RTDH-1-4	4
DASS-RTDH-1-5	5
DASS-RTDH-1-6	6
DASS-RTDH-1-8	8
DASS-RTDH-1-10	10
DASS-RTDH-1-12	12
DASS-RTDH-1-15	15

1" BSPP Male/Male x 1" ID Gravity Hose Kits

0225	Length Metres
ASS-RTDH-1-3	3
ASS-RTDH-1-4	4
ASS-RTDH-1-5	5
ASS-RTDH-1-6	6
ASS-RTDH-1-8	8
ASS-RTDH-1-10	10
ASS-RTDH-1-12	12
ASS-RTDH-1-15	15

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

FUELLING EQUIPMENT & ACCESSORIES

Brass Drum Tap



BSPP

0225	Thread
2019-9394	3/4"

Drum Taps - Polyethylene

- Polyethylene drum taps can be used with a wide range of oils, acids and caustics
- Huge 2" version can be used with thick liquids
- BSPP male threads with sealing washer



BSPP

0225	Thread	Description
DTJ	2"	Full Bore Drum Tap
DT3P	3/4"	Drum Tap

Drum Wrenches



Aluminium

0225
DW-ALUMINIUM

Adblue® is a water-based chemical solution that is required for some commercial vehicles to help reduce pollution and comply to the Euro 4/5 directive.

Adblue® consumption is 5% of diesel, so for every one hundred litres of diesel, 5 litres of Adblue® is used.

You must not use a normal fuel pump to dispense Adblue®.

Adblue® Manual Nozzle

- Suitable for use with Adblue®
- Inlet 3/4" hose tail
- Spout diameter (OD) 18.8mm
- Wetted components: (Nylon 6, 30% glass filled), stainless steel, viton
- Can be used with gravity feed or electric pumps
- Integral hook for tidy storage when not in use

Maximum Flow: 80 L/min

Maximum Working Pressure
5 bar

Maximum Working Temperature:
+60°C



0225	LPM
NOZ-MAB	80
Tech Sheet 20032	

Lever Hand Pump & Accessories

- Suitable for use with Adblue® and other water-based fluids, antifreeze, windscreen washer fluid, herbicide, pesticides, insecticides and fertilizers.
- Wetted components polyacetal, polypropylene, polyethylene, viton
- Capable of up to 500ml per stroke
- 2" BSPM drum adaptor
- 2 piece suction pipe with one part telescopic (extends to 98cm)
- 2m x 3/4" outlet hose (flexible corrugated PVC hose)
- Temperature range: +5°C (23°F) to +45°C (115°F)
- Option (AD.HPGO) Trisure/Valorex container adaptor



0225
AB.HPPK
Tech Sheet 20031

Adblue® Hose

- Suitable with Adblue® and antifreeze made in the UK
- PVC, polyester braided
- For suction or delivery

Specification:
BS EN ISO 6224/2001,
BS EN ISO 5774/2008

- Bore 19mm

Maximum Working Pressure:
7 bar (102psi)

Made in the UK



3/4" Adblue® Delivery Hose (Hose only)

0225	Length Metres
ABH.4.3/4	4
ABH.6.3/4	6

Fluid-Air Components Ltd

FUELLING EQUIPMENT & ACCESSORIES

IBC Pump Kit

- Intermediate bulk container (IBC) side mounted, easy to use pump kit
- Suitable with Adblue®
- Capable of up to 25 L/min
- Manual Adblue® nozzle with stainless steel tip
- 1.5 metre flexible suction hose with CDS connector
- 4 metre outlet hose
- Designed for indoor use



MSS.AB



J10302504

0225	Nozzle
MSS.AB	Manual
J10302504	Auto
Tech Sheet 20030	

Rechargable Adblue® Pumps

- Pump complete with control nozzle, telescopic suction tube and 1.5m flexible hose.
- 2900mAh Rechargeable Lithium-ion battery. Rechargeable via USB 2.0 type B connector (USB cable included)
- Charge Time: 3hrs
- Flow Rate: Up to 11.5 LPM
- Duty Cycle: Maximum 15 mins on and 30 mins off
- Fully charged battery can discharge up to 300ltrs (Tested using water)
- Wetted components: polypropylene, polyethylene, PVC and acetal
- Recommended use: gasoline, diesel, kerosene, light Oils, AdBlue, DEF, water, antifreeze, windshield Fluid, mild detergents and agricultural chemicals.
- Do not use with: acids, acetone, Benzene, cresol, ethyl, phenol, methyl ethyl, thinnersm solvents, etc.



1 YEAR WARRANTY

new product

Rechargable DEF/AdBlue Pump

0122
ZBOP60
Tech Sheet 71689

Lever Action Barrel Pump

Features:

- Supplied complete with suction tube for use with 50-205ltr drums and 1.2m 3/4" flexible discharge hose.
- Comes complete with ZDBC - drum bung converter Trisure/Valorex.
- Delivers approx. 500cc per stroke.
- Wetted components: polyproohylene, polyethylene, acetal.
- For use with: Urea/DEF, water, lubricants, windshield washer fluid, antifreeze, mild detergents, agricultural chemicals.
- Do not use with: any media not compatible with materials used in the pump construction. These pumps must not be used for fuel transfer or with solvent thinners etc.



2 YEAR WARRANTY

new product

Lubework Lever Adblue Pump

0122
J17210241
Tech Sheet 71691

Fluid-Air Components Ltd

Swivel Hose Fittings

- Greatly eases handling and reduces hose wear and kinking.
- All have parallel threads except (SWIV.15A) which has a taper male and parallel female.

Maximum Working Pressure:
87 psi (6 bar)



0225	Female Thread	Male Thread
SWIV.3A	3/4"	3/4"
SWIV.13A	1"	3/4"
SWIV.31A	3/4"	1"
SWIV.1A	1"	1"
SWIV.15A	1.1/2"	1.1/2"

Jointing Compound

- General purpose jointing and thread sealing compound.
- Recommended for diesel, oil, water and steam.
- **NOT** suitable with ethanol.
- Fully waterproof and MOD approved.
- 250ml screw top tins with brush applicator.
- 500ml tins without brush applicator.



0225	Millilitres
HELD	250
HELD.500	500

Fuel Lockout Valve



BSPP

0225	Thread
FLV-1	1"

Continental Softwall Diesel Hoses

- Suitable with diesel, HVO or biodiesel up to B20.
- Ideal for use on economy fuel dispensers.
- Machine swaged ends for long life.
- Electrically bonded.
- 3/4" or 1" BSPT male ends.

Not steel braided.

Not suitable for use with petrol.

Maximum Working Pressure:
50 psi (3.5 bar)

Continental

Made in the UK



BSPT

0225	Length Metres	Thread
CH4.19	4	3/4"
CH6.19	6	3/4"
CH4.25	4	1"
CH6.25	6	1"

Continental Steel Braided Fuel Hoses

- Suitable with diesel, HVO, kerosene and petrol.
- Tested and approved to EN1360
- BSP parallel chrome plated "swaged for life" end fittings
- Smooth wipe clean covering.
- Excellent fuel and weather resistance.
- Steel braiding provides excellent protection against vandalism and the theft of nozzles by cutting through the hoses.

Maximum Working Pressure:
230 psi (15.8 bar)

Continental

Made in the UK



BSPP

0225	Length Metres	Thread
PH12.3/4	3.66	3/4"
PH20.3/4	6.1	3/4"
PH12.1	3.66	1"
PH20.1	6.1	1"

Gravity Dispensing Hose

- Gravity dispensing hoses 25mm (1") bore, excellent flexibility to ease handling and strong enough to resist kinking. Supplied with 1" BSPT male end fittings are machine banded on to the hose.

Maximum Temperature:
-15°C to +60°C

Maximum Working Pressure:
43.5 psi



1" BSPT

0225	Length Metres
GDH-4	4
GDH-5	5
GDH-6	6
Tech Sheet 1173	

Gravity Fuel Kits

- Only suitable with diesel or biodiesel up to B30.
- Provides simple and quick diesel dispensing from gravity tanks.

Kit includes: hose, valve, nozzle and PTFE tape. 25mm bore delivery hose.

Working Temperature:
-25°C to +45°C

Maximum Working Pressure:
50 psi (3.5 bar)



For use with Diesel/Gasoil

0225	Length Metres
2019-9337	3
2019-9360	5
Tech Sheet 1170	

FAC
Fluid-Air Components Ltd

FUELLING EQUIPMENT & ACCESSORIES

Fuelling Meters

- Suitable with diesel, HVO and biodiesel up to B30.
- Robust nutating disc flow meter shows up to 9999 litres.
- 20 -76 L/min. 1" BSPF ports. Aluminium housing.
- 4 digit register. 8 digit non resettable totaliser.
- Front face can be rotated in 90° increments.

Accuracy: +/-2%
(with adjustable calibration)
Operating Range: 20 - 76 L/min

Maximum Working Pressure:
50 psi (3.5 bar)



2 YEAR WARRANTY

Flow Meter without Strainer, BSPP

0225	Thread
FM4	1"

- Suitable with diesel, HVO, petrol, Kerosene and biodiesel up to B30.
- Robust nutating disc flow meter shows up to 999 litres.
- 19-75 L/min. 1" BSPF ports.
- Accuracy of +/- 2% with adjustable calibration.
- Aluminium housing and cover.
- 3 digit register. 6 digit non resettable totaliser.
- Front face can be rotated in 90° increments.

Accuracy: +/-2%
Operating Range: 19-75 L/min

Maximum Working Pressure:
50 psi (3.5 bar)



Ex

2 YEAR WARRANTY

Without Strainer, BSP Female

0225	Thread
807CL	1"
Tech Sheet 1168	

This mechanical fuel meter has a flow rate of 20-120 L/min, with a resettable 4 digit totaliser, and a non-resettable 8 digit totaliser, which registers up to 9,999,999.9 Litres.

Features:
- Aluminium metering chamber with polybutylene nutating disk.
- 1" inlet/outlet
- Accuracy +/-1%

Maximum Working Pressure:
3.5 bar



2 YEAR WARRANTY

8 Digit Non-resettable

0122
J1581400
Tech Sheet 2141

Features:
- Measures diesel, kerosene and petrol.
- Oval gear design.
- Low pressure drop allows for gravity and pump (in-line) applications.
- Supplied with a wire mesh strainer.

Redashe

10 YEAR WARRANTY

Conditions apply.



6 Digit Non-resettable

0122
DM100
Tech Sheet 60368

Digital In-line Turbine Flow Meters

LCD display has a 5 digit register, 7 digit non resettable totalizer. 10 - 100 L/min. 1" BSPF ports. Max pressure: 145 psi (10 bar). Accuracy: +/- 1%. Polypropylene turbine. Designed to fit in line with the delivery hose or pipework. Front can be rotated in 90° increments.



2 YEAR WARRANTY

For Diesel and HVO

0225
K24
Tech Sheet 10554

Adblue®



For Adblue®

0225
K24.AB
Tech Sheet 10555



Replacement Battery

0225	To Suit
K24.BATTERY	K24 & K24.AB

Electronic In-line Flow Meters

Material: Aluminium
Seal material viton and florinated silicone rubber



Female Thread, BSPP

0225	Thread	Max Pressure Bar	M^3/HR
CD-OG01-1	1"	20	200

Fluid-Air Components Ltd

FUELLING FILTRATION

Fuel Bowl Filters

- Fully interchangeable with other filter elements.
- Suitable with diesel, HVO or biodiesel up to B30.
- Choose particle only or water and particle kit/spare elements both remove particles to 10 micron.
- Fits on the outlet side only. 1"BSPF ports.



BSPP

0225	Thread	Description
FFILT.KIT	1"	Fuel Filter Kit, Particles Only
FFILT.KITW	1"	Fuel Filter Kit, Water/Particles
FFILT.EL	-	Spare Particle Only Element
FFILT.ELW	-	Spare Water/Particle Element

Fuel Filter Kit

- Suitable with diesel, HVO or biodiesel up to B7.
- Removes particle and water contamination to 30 micron.
- Fits on the outlet side only. 1" BSPF ports.
- Kit = aluminium head with disposable spin on element.
- Max flow. 45 litres/min gravity, pump 100 litres/min.
- Buy a complete kit or separate element and head.



BSPP

0225	Thread	Description
HYD.GK	1"	Filter Kit Water & Particles
HYD.ELG	-	Spare Water/Particle Filter

Depuroil Portable Filter & Oil Transfer Unit

The ideal tool for decontaminating oil by removing suspended particles. The filtering unit is composed of a volumetric vane pump that extracts the oil to be purified, sending it through a high-filtering capacity cartridge filter that removes the impurities.

- Suitable for use with oils up to SAE90.
- 230V transfer pump
- Complete with suction and outlet hose.

Maximum Flow:
25 litres/min



10 Micron

0225	Description
WO.DEP	Transfer Unit
WO.DEPF	Spare Element

In-line Fuel Filter Elements



Paper Filter, 6mm OD

0225
25-200



Nylon Filter, 9mm OD Barb

0225
25-202



Nylon Filter, 8mm OD

0225
25-204



Paper Filter, 9mm OD Barb

0225
25-201



Nylon Filter, Elbow 8mm OD

0225
25-203

Fluid-Air Components Ltd

FUELLING FILTRATION

Fuel Filters & Elements



Fuel Filter

0225	Micron
ZFFL02B	10



Water Block Fuel Filter Element

0225	Micron
ZFEWB	10



Fuel Filter Spin On Cartridge

0225	Micron
ZFFS10BSP	10



Replacement Fuel Filter Element

0225	Micron
ZFE10	10

FT PRO









For **Tank Gauges**
…see page **1154**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

DIESEL OIL FILTERS

Diesel Oil Filters - Series 20100-20150

Maximum Working Pressure: 1 bar



Aluminium, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20103/AL-100UM	1/4"	100	48
20101/AL-100UM	3/8"	100	48
20103AL4-44UM	1/4"	44	48
20101AL4-44UM	3/8"	44	48
20103CAL-15UM	1/4"	15	228
20101CAL-15UM	3/8"	15	228
20151/AL-100UM	3/8"	100	24

Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20103/PL-100UM	1/4"	100	48
20101/PL-100UM	3/8"	100	48
20103PL4-44UM	1/4"	44	48
20101PL4-44UM	3/8"	44	48
20103CPL-15UM	1/4"	15	228
20101CPL-15UM	3/8"	15	228
20151/PL-100UM	3/8"	100	24

Maximum Working Pressure: 1 bar



Plastic Superior Metocene Bowl, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20103/PE-100UM	1/4"	100	48
20101/PE-100UM	3/8"	100	48
20103CPE-15UM	1/4"	15	228
20101CPE-15UM	3/8"	15	228
20153/PE-100UM	1/4"	100	24
20151/PE-100UM	3/8"	100	24

Diesel Oil Filters - Series 20200

Maximum Working Pressure: 2 bar



Aluminium, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20201/AL-100UM	3/8"	100	105
20202/AL-100UM	1/2"	100	105
20201AL4-44UM	3/8"	44	105
20202AL4-44UM	1/2"	44	105
20201CAL-15UM	3/8"	15	235
20202CAL-15UM	1/2"	15	235

Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20201/PL-100UM	3/8"	100	105
20202/PL-100UM	1/2"	100	105
20201PL4-44UM	3/8"	44	105
20202PL4-44UM	1/2"	44	105
20201CPL-15UM	3/8"	15	235
20202CPL-15UM	1/2"	15	235

Diesel Oil Filters - Series 20210

Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl with Water Drain Valve, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20211/PL-100UM	3/8"	100	105
20212/PL-100UM	1/2"	100	105
20212PL4-44UM	1/2"	44	105
20211CPL-15UM	3/8"	15	235
20212CPL-15UM	1/2"	15	235

Diesel Oil Filters with Cock & Check Valve - Series 20250

Maximum Working Pressure: 2 bar



Aluminium, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20250ALAL4-44UM	3/8"	44	105
20250CAL-15UM	3/8"	15	235

Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20250/PL-100UM	3/8"	100	105
20250PL4-44UM	3/8"	44	105
20250CPL-15UM	3/8"	15	235

Please note: Oil viton seal filters are available upon request.

DIESEL OIL FILTERS

Diesel Oil Filters with Cock - Series 20230

Maximum Working Pressure:
2 bar



Aluminium, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20232/AL-100UM	1/2"	100	105
20231AL4-44UM	3/8"	44	105
20232AL4-44UM	1/2"	44	105
20231CAL-15UM	3/8"	15	235
20232CAL-15UM	1/2"	15	235

Maximum Working Pressure:
1 bar



Plastic Standard Tenite Bowl, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20231/PL-100UM	3/8"	100	105
20231PL4-44UM	3/8"	44	105
20232PL4-44UM	1/2"	44	105
20231CPL-15UM	3/8"	15	235
20232CPL-15UM	1/2"	15	235

Fuel Oil Filters - Series 20300-20350

- Cover and bowl made out of aluminium.

Maximum Working Pressure:
2 bar



Without Heating Element, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20306/10-100UM	1/2"	100	300
20306/20-200UM	1/2"	200	300
20306/30-300UM	1/2"	300	530
20304/10-100UM	3/4"	100	300
20304/20-200UM	3/4"	200	300
20301/10-100UM	1"	100	300
20301/20-200UM	1"	200	300
20301/30-300UM	1"	300	530

- Cover and bowl made out of aluminium.
- Heating element PTC 20351/03 T150°C - 230 Volts.

Maximum Working Pressure:
2 bar



With Heating Element, BSPP

0270	Thread	Micron Rating	Filter Surface Area cm²
20356/20-200UM	1/2"	200	300
20356/30-300UM	1/2"	300	530
20354/10-100UM	3/4"	100	300
20354/30-300UM	3/4"	300	500
20351/10-100UM	1"	100	300
20351/20-200UM	1"	200	300
20351/30-300UM	1"	300	500

Fuel Oil Filters - Series 20400-20450

Maximum Working Pressure:
2 bar



Without Heating Element

0270	Thread	Micron Rating	Filter Surface Area cm²
20401/10-100UM	1"	100	670
20401/30-300UM	1"	300	1130
20402/10-100UM	1.1/4"	100	670
20402/20-200UM	1.1/4"	200	670
20403/10-100UM	1.1/2"	100	670
20403/20-200UM	1.1/2"	200	670
20403/30-300UM	1.1/2"	300	1130

Maximum Working Pressure:
2 bar



With Heating Element

0270	Thread	Micron Rating	Filter Surface Area cm²
20451/10-100UM	1"	100	670
20453/10-100UM	1.1/4"	100	670
20453/20-200UM	1.1/4"	200	670
20453/30-300UM	1.1/4"	300	1130
20452/30-300UM	1.1/2"	300	1130

Fluid-Air Components Ltd

DIESEL OIL FILTERS

Oil Filter Spare Cartridges



To suit Series 20150

0270	Material	Type	Micron Rating
20151/C1-100	Stainless Steel	Smooth	100



To suit Series 20100

0270	Material	Type	Micron Rating
20101/C1-100	Stainless Steel	Pleated	100
20101/C4-44	Stainless Steel	Pleated	44
20101CC5	Paper	-	15



To suit Series 20200

0270	Material	Type	Micron Rating
20201/C1-100	Stainless Steel	Pleated	100
20201/C4-44	Stainless Steel	Pleated	44
20201CC5-15	Stainless Steel	Pleated	15



To suit Series 20300-20350

0270	Material	Micron Rating
20301/C1-100	Stainless Steel	100
20301/C2-200	Stainless Steel	200
20301/C3-300	Galvanized Iron	300




To suit Series 20400-20450

0270	Material	Micron Rating
20401/C1-100	Stainless Steel	100
20401/C3-300	Galvanized Iron	300

Electrical Heater



0270	Material	Voltage	Micron Rating
20351/03	100	230V/50Hz	220
20451/01	300	230V/50Hz	200



0270	To Suit
SET20100	Series 20100
SET20200	Series 20200
SET20250	Series 20250
SET20300	Series 20300
SET20400	Series 20400

For **Diesel Drop Hose**
...see page **1434**



BARREL PUMPS

Piston Oil Pump

- With 1.5m outlet hose, anti-drip 13mm 90° spout, nozzle storage facility.
- Designed to fit awkward access filler points.
- 2" BSPP male thread, pumps on down stroke.



0225	To Suit
J9023SE	20 & 25 Litre Drums

Gear Oil Bucket Pump

- With fully reversible hand rotary pump, clear PVC hose and nozzle.
- 10.5L approx.
- Robust steel base with hard powder coat finish as standard.
- Delivers and retrieves.



0225	Volume Litres
A6000SE	10.5

Syphon Pump




0225	To Suit
J2653	205 Litre Barrels

Manual Syphon Pumps

- Suitable for pumping most liquids: acids, alkalines, antifreeze, de-greaser, distilled water, diesel, biodiesel B100, light oils and solvents.
- Includes delivery hose and suction pipe.

HPS25 fits 5-25L containers, delivery hose 534mm (21"), suction 380mm (15").

HPS205 fits 205L container, thread 2" BSPM, delivers 30 L/min, delivery hose 1295mm (51"), suction 850mm (33.1/2").




Drum Pumps

0225	To Suit
HPS25	5-25 Litre Drum
HPS205	205 Litre Drum

Battery Operated Syphon Pump

- Unique battery operated pump (2 x D size batteries not supplied).
- Suitable with water, diesel, HVO, light oils & mild / non corrosive chemicals.

Flow Rate: 4 - 7 L/min
Suction Tube: 375mm (15").
Discharge Tube: 660mm (26").
Total Length: 675mm (27").




Drum Pump

0225	LPM
HPSB	8-10

Z Swivel

- 1/4" BSPP Male and female




BSPP

0225	Thread
M8090	1/4"

Lever Barrel Pumps

- Suitable with diesel, HVO, biodiesel up to B30 and oils to SAE 90.
- Metal lever action drum pump.
- Capable of up to 20 L/min. 2" BSPM drum adaptor.
- Telescopic suction tube 450 - 900mm.

Note:
pumping speed 20 L/min



0225
2019-9386
Tech Sheet 1171

WHALE Urchin - Diaphragm Hand Pump

- Suitable with clean or dirty diesel, HVO, water and oils to SAE 90.
- Pumps dirty and contaminated liquids with up to 10mm solids
- Made from glass filled polypropylene complete with nitrile seals
- Hose tails accept both 1" and 1.1/2" hoses

Flow Rate:
47 L/min for 1"
68 L/min for 1.1/2"



0225
HPW
Tech Sheet 20034

Lockable Drum Taps



3/4" BSPP

0225
J4175

- All metal



Self Closing, 3/4" BSPP

0225
J4177

Fluid-Air Components Ltd

ROTARY PUMPS & DIAPHRAGM

Rotary Barrel Pumps

- A robust cast iron rotary barrel pump capable of up to 25 L/min for dispensing fuel or oils. Supplied complete with 1 metre sectioned metal suction pipe and 2" BSP barrel adaptor.



Cast Iron

0225
2042-5658
Tech Sheet 1172

- Suitable with most chemicals and acid based products.
- PVC construction with PTFE vanes and Hastelloy springs.
- 3 piece suction pipe. Capable of up to 25 L/min.

Adblue®



PVC Rotary Hand Pump

0225
MSSPVC

Semi Rotary Pumps

- Suitable with diesel, light oils and water.
- Semi rotary double acting.
- Cast iron body with brass internals.
- Flanged inline threaded ports.

Choose from:

- 1/2" K0 version
- 3/4" K1 version
- 1" K2 version
- 1.1/2" K5 version

Note: never mount horizontally.



Semi Rotary Hand Pumps

0121	Size	Thread
SEMI0	0	1/2"
SEMI1	1	3/4"
SEMI2	2	1"
SEMI3	3	1.1/4"

- Kit fits into 2" socket, for use on 205 litre drums and tanks up to 1.5 metre deep.
- 1" semi-rotary hand pump.
- Manual nozzle.
- Tank/pump connector.
- 4 metre x 3/4" outlet hose.



Semi Rotary Pump Kit

0121	Description
SRG2A.KIT	1" BSP Hand Pump Kit

Fluid-Air Components Ltd

MANUAL TRANSFER PUMPS

Gear Oil Pump

- Suitable with high viscosity oils, ideal for filling gear boxes. Telescopic suction tube 300 - 500mm.
- Polypropylene pump, mild steel piston and nitrile seals.
- Dispenses approximately 100ml per stroke.
- Has a 1.5m outlet hose with spout.
- Spout can be drained by locating back into pump body.
- Supplied with two adaptors as standard: One fits most 25L external Plysu threads (60mm dia). The other fits most 25L Trisure/Valorex thread (56mm dia).

Option: Universal adaptor, locks onto any external thread that is less than 61mm dia.



0225	Description
HPGO	Pump
ADAPT.UNI.L	Adaptor

Oil Suction Gun

For getting oil in/out of gearboxes, transfer cases and differentials.

- Suitable for use with non corrosive liquids.
- Capacity 500cc with 300mm PVC hose.
- Deluxe lip seal provides maximum suction.
- Steel barrel in premium powder coated finish.
- Fully serviceable.
- No priming required.



0225
OSG

Liquid Suction/Extraction Units

- Novel device that both sucks and stores extracted liquids.
- Suitable for fuels, water, oils and many other liquids.

Removes: Oil from vehicles, lawn mowers, motorbikes, hydraulic reservoirs without draining, simply insert the suction pipes in the dipstick hole. Water from bunded fuel tank cabinets, fish tanks, bilges and otherwise inaccessible areas. Fuel spillages from bunded tanks/fill point cabinets.

- Can even suck up surface puddles.
- Prime the handle and watch it work.
- Supplied with suction probes to fit most applications.
- Lightweight and portable. 17 litre version has castors.
- When full, remove top plug to pour out the contents.

A must have for any engineers/site van multipurpose pump.



Suction/Extraction Units

0225	Capacity Litres
HP.SUC2	2.7
HP.SUC6	6.5
HP.SUC17	17

DOSING PUMPS

MixRite 3.5 Series

Tefen's MixRite line of water driven proportional dosing pumps, are used to ensure precise additive injection directly into the water or fluid line under various flow rates, feed ratios and different ranges of pressure.

Features

- Mixes additive and water precisely
- The dosage can be adjusted easily and quickly
- Repair is simple and inexpensive
- Key internal parts are from the highest quality material available (Hastelloy spring. Viton Rubber seal)

Working Temperature: 4°C to +40°C

Maximum Working Pressure: 8 bar



3/4" BSPT Male

0471	LPH	Max Pressure Bar	Dosage Rate
MRDP-1	10-3500	0.2-8	1:333 - 1:500
MRDP-2	10-3500	0.2-8	1:1000 - 1:111
MRDP-3	10-3500	0.2-8	1:333 - 1:50
MRDP-4	10-3500	0.2-8	1:200 - 1:20
MRDP-5	50-3500	0.2-8	1:100 - 1:10
Tech Sheet 60239			

Fluid-Air Components Ltd

ELECTRICAL TRANSFER PUMPS

12V Submersible Transfer Pump

- Only suitable with diesel, biodiesel B30 and water to 80°C.
- Maximum Flow: 18 L/min. Length 145mm, diameter 47.5mm.
- 12V centrifugal submersible pump.
- 3m outlet hose (1/2"). (500 hour life expectancy).
- 4m long battery cable and clips. Weight 0.6kgs.
- Continuously rated for periods up to 1 hour.

NOTE: DO NOT RUN DRY

Maximum Working Pressure:
15 psi (1 bar)



0225	Voltage	LPM
12SP18	12V	18

Electric Oil Transfer Pump

Designed for pumping and transferring all grades of oils up to SAE 90. Suitable for lubricating oils, hydraulic oils, gear oils etc. Complete with on/off switch and internal bypass, it has 3/4" BSPP threaded ports and is also supplied with a pair of 1" hose tails. Pumping rate depends on grade of oil and temperature.

- IP55 rated



2033-5279



VISCO.110

0225	Voltage
2033-5279	230V
VISCO.110	110V
Tech Sheet 1174	

On-demand Diaphragm Pumps

- Only suitable for use with agricultural chemicals or water
- For spraying and transferring liquids
- With pressure switch and fittings
- Self priming to 2m
- EPDM diaphragm
- 1/2" and 3/4" barb plug-in ports



12V

0225	Description
DP12.17	17L/min, 40 psi (2.8 bar)

Portable Diesel Pump Kits

- Suitable with diesel, HVO, and biodiesel up to B30.
- Choice 12V or 24V. 40 L/min pumping speed.
- 40 L/min pumping speed.
- Sturdy steel case complete with carry handle
- On/off switch and bypass valve.
- 4m long battery cable with crocodile clips.
- UK made 6m of suction/delivery hose.
- Brass foot valve and strainer must be fitted or warranty void.

Maximum Run Time:
30 mins.



Manual, BSPP

0225	Thread	Voltage
12PA.KIT1C	1"	12V
24PA.KIT1C	1"	24V

Professional Battery Diesel Pump Kits

- Suitable with diesel, HVO, empties a 205L drum in 5 mins.
- 40L/min, 4m battery cable with crocodile clips.
- Carry handle, on/off switch, bypass valve.
- UK made suction/delivery hose 6 metres in total.
- Aluminium nozzle with hose swivel.
- Complete kit for barrel/portable transfer.


Maximum Run Time:
30 mins.



0225	Voltage	LPM
12PA.KIT1B	12V	40
24PA.KIT1B	24V	40

High Speed Battery Diesel Pump Kits

- Suitable with diesel, HVO or biodiesel up to B30.
- Maximum Flow: 70 L/min. 12V.
- 1" BSPF inlet and outlet flanges.
- PIUSI Direct drive vane pumping unit with bypass valve.
- Switch, 4m long battery cable and crocodile clips.
- Weatherproof for outdoor use.
- Maximum run time: 30 mins.
- Kit includes 7m suction/delivery hose, foot valve and strainer.
- Choose manual or automatic nozzle kit.



0225	Nozzle
12BIKIT	Manual
12BIKIT2	Automatic

Battery Diesel Transfer Pumps

- Suitable with diesel, HVO and biodiesel up to B30.
- Ideal for mounting into plant equipment, excavators etc.
- Maximum Flow: 40 L/min.
- 3/4" BSPF ports.
- Choose 12V or 24V. 3/4" BSPF ports.
- Direct drive vane pumping unit with bypass valve.
- Foot mounting plate.
- Weatherproof to IP54 for outdoor use.
- Complete with switch, carry handle.
- 4m long battery cable and crocodile clips.

Maximum Run Time: 30 mins.



0225	Voltage
12PA.BARE	12V
24PA.BARE	24V

ELECTRICAL TRANSFER PUMPS

Professional Diesel Transfer Pumps

- Suitable with diesel, HVO and biodiesel up to B30.
- Pumping speeds 50, 80 or 100 L/min. 230V.
- Direct drive, self priming, vane pumping units.
- 1" BSPF ports. Switch and 2m long mains cable.
- Integral filter and bypass.
- Weatherproof to IP55 for outdoor use.
- Continuously rated motor with thermal cut out.
- Full range of spares available.



2 YEAR WARRANTY

0225	Voltage	LPM
SPT60A	230V	50
SPT80A	230V	80
SPT100A	230V	100

230V Professional Diesel Pump Kits With Automatic Nozzle

- Suitable for use with diesel, HVO or biodiesel up to B30.
- Manual operated on/off switch.
- Pumping speeds choose 45 or 75 L/min option.
- Meter accuracy of +/- 2%. 4 digit resettable register.
- 8 digit non resettable totaliser.
- Weatherproof to IP55. Integral filter and bypass valve.
- 230V continuously rated motor with thermal cut out.
- 4m delivery hose.
- Supplied with automatic nozzle.
- Self priming pump unit.
- Dimensions 300mm H x 350mm W x 500mm D (including nozzle).

45 Litres per Minute: Ideal to fill cars/vans vehicles with small fuel tanks.
75 Litres per Minute: Ideal to fill vehicles with large fuel tanks.



2 YEAR WARRANTY

45 Litres per Minute

0225	Nozzle
ECON45	Automatic

75 Litres per Minute

0225	Nozzle
ECON75	Automatic

AIR OPERATED TRANSFER PUMP

Polypropylene Air Operated Diaphragm Pump

- 1:1 ratio. Max operating pressure 116 psi/8 bar.
- Rugged Polypropylene body.
- Viton diaphragm.
- Maximum solids pumped = 3mm diameter.
- Air inlet 1/4".
- Suitable for Adblue® and antifreeze.



Adblue®

BSPP

0225	Thread	LPM	Seal
ADP.60PV	3/4"	60	Viton

Aluminium Air Operated Diaphragm Pump

- 1:1 ratio. Max operating pressure 116 psi/8 bar.
- Rugged aluminium body.
- Nitrile diaphragm.
- Maximum solids pumped = 3mm dia.
- Air inlet 1/4". 325mm H x 255mm W x 210mm D



BSPP

0225	Thread	LPM	Seal
ADP.60AV	3/4"	60	Viton
ADP.90AN	1"	90	Nitrile

Tech Sheet 10578

Pneumatic Pumps



Oil Pumps

0122	Ratio	Description
J100	01:01	940mm Suction Tube
J300S	03:01	270mm Suction Tube
J500S	05:01	270mm Suction Tube

Tech Sheet 2053

Fluid-Air Components Ltd

MANUAL & COMPRESSED AIR TRANSFER PUMPS & KITS

Redashe

Hand Operated Fuel Oil & Liquid Pumps



Lubeworks

Lubeworks Lever Hand Pump Fuel Oil

0122	Description
J1703001	Lever Hand Pump



Lift Pump Polypropylene Fuel Oils

0122	Description
HPLP	Lift Pump

Pneumatic Oil Pumps & Dispensers



Pneumatic Oil Pump Kit

0122	Description
J100TDG	Oil Pump Kit



Lubeworks

Wall Mounted Oil Dispensing Kit

0122	Description
C808MODK	Oil Dispensing kit

Driven Fuel Transfer Pumps



Portable Fuel Transfer Pump Kit 12V & 24V

0122	Voltage
J10304022	12V
J10304024	24V



Fully Enclosed Fuel Transfer Pump

0122	Description
J1500450	Transfer Pump



Fuel Transfer Pump

0122	Description
J1500451	Transfer Pump



Break Couplers for Fuel

0122	Size
ZBKV34N	3/4"
ZBKV01N	1"

FUELLING EQUIPMENT & ACCESSORIES

Oil Delivery

- Mobile oil dispensing units suitable for dispensing oil at medium/high viscosity, for mobile installations and fixed systems at medium distances. The drum trolley allows the system to be moved around the workshop with ease, giving increased efficiency. All items are available separately or in kit form.

JOS200



C080-OKMD



Oil Delivery System

0225	Description
JOS200	Oil Delivery System with Hose Reel
JOS100	Oil Delivery System without Hose Reel
	Tech Sheet 60363

- Self-contained oil pump supplied with a 16 litre (4.23 gallon) container with handle. Fitted with a 48"(4ft) fuel-resistant soft PVC hose with nozzle for clean discharge.

Features:

- 16 litre powder-coated container
- Variable handle setting for light or heavy fluids
- Recommended for transmission differentials and heavier oils
- Not suitable for water-based fluids or other corrosive media



Oil Delivery System

0225	Capacity Litres
ZOLP16	16
	Tech Sheet 60365

- Pneumatic oil dispenser equipped with level gauge and delivery gun with flexible end.
- Works autonomously without the requirement of continuous connection to air supply.

Maximum Working Pressure:
10 bar



Oil Delivery System

0225	Capacity Litres	Max Pressure Bar
JPOD030	30	10
JPOD065	65	10
	Tech Sheet 60364	

Oil Drum Transportation

J1708003



J1708001



Drum Trolleys

0225	To Suit
J1708001	12.5-50kg Drums
J1708003	205 Litre/180kg Drums
	Tech Sheet 60362

Fluid-Air Components Ltd

GREASING & LUBRICATION EQUIPMENT

Grease Guns

- Universal gun for use with cartridges (400cc) or bulk grease (500cc).



Side Lever Gun

0088
2017-3506

- Rigid tube and locknut, 4-jaw connector and filler/bleed nipple
- Universal gun for use with cartridges (400cc) or bulk grease (500cc)
- Heavy-duty follower



Heavy-duty Lever Gun

0088
2017-3514

- One hand pistol grip with rigid tube and 4-jaw connector
- Universal gun for use with cartridges (400cc) or bulk (500cc)



Pistol Grip Gun

0088
2017-3555

Grease Hoses

Maximum Working Pressure:
400 bar
Burst Pressure:
900 bar



Single Steel Braid Rubber Hose, Male Thread, BSPP

0088	Thread	Length
2017-3654	1/8"	12"
2017-3662	1/8"	18"



Nylon Braid Hoses Polyamide Coated, Male Thread, BSPP

0088	Thread	Length
2017-3670	1/8"	12"
2017-3688	1/8"	18"



Rigid Stem with 4 Jaw Connector

0088
2017-3720

Lithium No.2 Grease Cartridge

Multi purpose bearing grease No.2 consistency for conventional applications.



0088	Volume Grams
2017-6780	400

Fluid-Air Components Ltd

GREASING & LUBRICATION EQUIPMENT

Redashe

Heavy-duty Lever Grease Gun



0122
J1786004

Pistol Grip Grease Gun



0122
J1786501

Groz Dual Pistol/Lever Handle Grease Gun

Features:

- 2 way operating telescopic handle
- **Pistol type:** Ideal for use in confined space
- **Lever type:** For high pressure and high volume application
- Integrated high volume/high pressure adjustable mechanism
- Aluminium die cast head fitted wit bulk loader and air bleeder valve
- Non-slip comfortable vinyl grip handle
- Filling options: 400gm (14oz.) grease cartridge, bulk, suction or filler pum
- Suitable for use with NLGI 1, 2 and 3 grease

new product

1 YEAR WARRANTY



0122
ZG77
Tech Sheet 71693

Quick Grease Filler Gun

Features:

- Simple method of filling grease reservoir
- Reduces the chances of cross contamination
- Suitable for use with 400g grease cartridges or bulk grease
- Barrel manufactured from high quality zinc plated steel

new product



1 YEAR WARRANTY

0122	Barrel Length	Barrel Diameter
ZSGGR400T	370mm	56mm
Tech Sheet 71690		

Grease Filler Pumps



Air Operated Grease Pump Kit

0122	Description
J1708001	Optional Drum Trolley

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

GREASING & LUBRICATION EQUIPMENT

Grease Guns

A unique single hand operated grease gun of superior quality for the professionals.
The short stroke operation delivers 52,000kPa/7,500 psi/520 bar whilst the flexible extension allows you to access nipples that are normally hard to reach.
The gun can be filled by one of three ways: cartridge, bulk or J2 grease pump.



Features:
- Short stroke operation
- Easy one hand operation
- Flexible outlet with Supergrip KY Coupler
- Delivers 0.8gm per shot
- Filler/bleeder nipple 1/4" BSP (M)

Professional Flexi Grease Gun

0122
K32

A high quality lever grease gun for the professionals. This lever gun is engineered for high pressure greasing providing up to 69,000kPa/10,000 psi/690 bar. The lever gun can be filled by one of three ways: cartridge, bulk or J2 grease pump.

Features:
- Rigid outlet with Supergrip KY Coupler
- Delivers 1.5gms per shot
- Filler/bleeder nipple 1/8" BSP (M)
- Fully repairable



Professional Lever Grease Gun

0122
K40
Tech Sheet 10579

For fast and easy loading of grease guns. The pump allows you to buy grease more economically whilst the fully sealed system keeps out any contaminants.

Features:
- Suitable for 12.5 kegs
- Delivers 54gms per stroke
- Fully sealed system keeps grease clean



J2 Grease Pump

0122
J2

The P3 power-lube is the ultimate economical, high pressure air powered greasing system. To suit 12.5kg grease pails. At the recommended air pressure of 690kPa/100 psi/ 7 bar the 50:1 ratio air motor provides fast and continuous greasing at 34,500kPa/5,000 PSI/345 bar. The grease pressure can be boosted to 69,000kPa/ 10,000 psi/690 bar simply by squeezing the gun trigger several times.

Features:
- Non corroding air motor
- 4m delivery hose
- Handles up to NLG1 No2 greases
- Delivers 460gms of grease per minute
- Suitable for 12.5kg grease kegs



P3 Air Operated Power-Lube

0122
P3
Tech Sheet 10580

The P6 Maxi-Lube is the ultimate in economical high pressure air powered greasing systems. To suit 50kg grease pails. 690kPa/100 psi/7 bar the 50:1 ratio air motor provides fast and continuous greasing at 34,500kPa/5,000 psi/345 bar. The grease pressure can be boosted to 69,000kPa/10,000 psi/690 bar simply by squeezing the gun trigger several times.

Features:
- Non corroding air motor
- 4m delivery hose
- Handles up to NLG1 No2 greases
- Delivers 460gms of grease per minute
- Suitable for 50kg grease kegs



P6 Air Operated Maxi-Lube

0122
P6

Refillable Bearing Lubricator

The refillable automatic bearing lubricators are high quality, mechanical, chemical and thermal resistant. Designed to provide constant lubrication to bearings, bushings, joints, articulated joints or wherever constant greasing is required.

Features:
- Supplied with medium tension springs
- Suitable for all types of grease NLGI 0-1-2-3-4
- Setting dial (1, 3, 6 and 12 months) supply duration

Material Body: Transparent lexan

Working Temperature: -30°C to +132°C

Maximum Working Pressure: 200 psi



0122	Capacity Millilitres
MCGL100	100
MCGL220	220
Tech Sheet 2143	

GREASING & LUBRICATION EQUIPMENT

Redashe

Pneumatic Pumps

JG-50 Drum cover, 385mm/50-60kg. Follower plate 370mm/50-60kg, Connection hose SAE R2 13" x 1/4", grease gun, Z swivel. JG-12 Drum cover, 280mm/12kg. Follower plate 265mm/12kg. Connection hose SAE R2 13" x 1/4", grease gun, Z swivel.



Grease Pumps

0122	Ratio	Description
JG-50	50:1	740mm Suction Tube
JG-12	50:1	480mm Suction Tube

Grease Pumps

GR.H12.L High pressure, direct feed grease pump. Fits directly onto 12.5Kg keg. Rubber edged follower plate. 1.2m high pressure outlet hose. 4 jaw connector. GR.BFILL.L Low pressure high volume grease pump. Pumps grease up to NGLI2, fits 12.5kg kegs. 1.2m outlet hose and quick release female connector.



High Pressure

0225
GR.H12.L

Low Pressure

0225
GR.BFILL.L

For filling grease guns with bulk grease, up to NGLI2. Fits directly onto 12.5kg kegs. Fills grease guns fast. Enables you to buy grease in bulk, saving money.




Grease Gun Filler Pump

0225
GR.GGFILL.L

Mobile Grease Dispensers


50:1 ratio air operated grease pump. 4 wheeled trolley. 4m of 1/4" bore delivery hose. Grease gun complete with straight swivel. GR.AM12.5C fits 12.5kg grease keg. 280mm diameter drum cover. 265mm diameter follower plate. GR.AM50C fits 50kg grease keg. 385mm diameter drum cover. 370mm diameter follower plate.



0225	To Suit
GR.AM12.5C	12.5kg Keg
GR.AM50C	50kg Keg

Grease Control Gun & Accessories

For use with air operated grease pumps. Inlet connection 1/4" BSPF straight swivel. Supplied complete with rigid spout and flexible outlet hos with 4 jaw connection. Option Z swivel. Spare straight swivel available.



Grease Gun

0225
GR.AGUNC

1/4" Z Swivel

0225
GR.ASWIVC

1/4" Straight Swivel

0225
GR.ASWIVS

High Volume Side Lever Grease Gun

Designed for ease of use with min effort that any gun can offer. Delivers 1.1/2 times more grease than most grease guns and generates pressure up to 10,000 psi (690 bar). Machined to precision tolerances (die cast head, 1.2mm barrel). Accepts either 400cc cartridges or 500cc bulk fill. Supplied with rigid spout 4 jaw connector and bulk filling loade .



0225
GR.G3HV

High Volume Pistol Grip Grease Gun

Industrial pistol grip/one handed grease gun. Used for greasing in confined spaces/restricted access. Unique variable stroke feature allows increased pressure from short strokes and high volumes from full strokes (7500 psi 517 bar). Machined to precision tolerances (die cast head, 1.2mm barrel). Accepts either 400cc cartridges or 500cc bulk fill.
Supplied with 225mm flexible spout and 4 jaw connecto .
Fitted with unique bulk filling loade , doubles as an air bleed.



0225
GR.G6HV

Grease Fitting Unblocker

Opens clogged grease fittings/loosens hardened grease joints. Maintains and protects bearings, control arms, joints, king pins etc. Tap with a hammer to force light viscosity oil through the tool into the coupler and finall , into the grease joint - breaking up and removing dirt and debris. Built in hand guard for added safety. Flexible hose attachment reaches fittings in difficult areas. Comes with a greas coupler for connection onto the grease fitting and 2 spare piston|seal for replacing as they wear out.



0225
GR.FU

Portable Greasing System

Ideal for heavy plant and site use. Foot operated. Suitable for grease up to and including NLGI 2. Foot operated by pressing on the spring loaded system. Hose is then charged with grease ready for dispensing. A single charge dispenses 30 shots of grease. Super dispensing gun has high pressure and high volume settings. High pressure 0.45gm per shot, high volume 1.25gms per shot. High pressure feature is useful to open blocked grease fittings. Comes with drum cover (dia 216mm) rubber lined follower plate, 1.5m hose and 5kg plastic grease bucket/drum.



0225
GR.PGS

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

Grease Nipples, Stainless Steel



45° Angle, Male Thread

0088	Thread
SSGN0245	1/8" BSPT
SSGN0245N	1/8" NPT
SSGN0445	1/4" BSPT
SSGNM645	M6 x 1
SSGNM845	M8 x 1
SSGNU0445	1/4" UNF



90° Angle, Male Thread

0088	Thread
SSGN0290	1/8" BSPT
SSGN0290N	1/8" NPT
SSGN0490	1/4" BSPT
SSGNM690	M6 x 1
SSGNM890	M8 x 1
SSGNU0490	1/4" UNF



Straight, Male Thread

0088	Thread
SSGN02	1/8" BSPT
SSGN02N	1/8" NPT
SSGN04	1/4" BSPT
SSGN04N	1/4" NPT
SSGNM6	M6 x 1
SSGNM8	M8 x 1
SSGNU04	1/4" UNF

Grease Nipple Covers



0225
PNR

Grease Nipples

80 piece assorted straight and angled grease nipples.
Imperial contains BSP/BSF/UNF.
Metric contains M6/M8/M10.



Box of Assorted Grease Nipples

0225	Thread
J9130/80	BSP/BSF/UNF
J9131/80	M6/M8/M10



For **Manual Grease System**
…see page **1647**

GREASING & LUBRICATION EQUIPMENT

Grease Nipples



Angled Male Thread, BSPT

0088	Angle	Thread
2017-3829	45°	1/8"
2017-3845	45°	1/4"
2017-3811	65°	1/8"
2017-3787	90°	1/8"
2017-3795	90°	1/4"

Angled Male Thread, Metric

0088	Angle	Thread
GNM645	45°	M6 x 1
GNM845	45°	M8 x 1
GNM690	90°	M6 x 1
GNM890	90°	M8 x 1

Angled Male Thread, NPT

0088	Angle	Thread
GN0245N	45°	1/8"
GN0445N	45°	1/4"
GN0290N	90°	1/8"
GN0490N	90°	1/4"

Angled Male Thread, UNF

0088	Angle	Thread
GNU0445	45°	1/4"
GNU0490	90°	1/4"



Straight Male Thread, BSPT

0088	Thread
2017-3738	1/8"
2017-3746	1/4"

Straight Male Thread, Metric

0088	Thread
GNM6	M6 x 1
GNM8	M8 x 1

Straight Male Thread, NPT

0088	Thread
GN02N	1/8"
GN04N	1/4"

Straight Male Thread, UNF

0088	Thread
GNU04	1/4"



16mm Double Hexagon Head (15mm A/F) Male Thread, BSPP

0088	Thread
2017-3860	1/8"
2017-3878	1/4"

16mm Double Hexagon Head (15mm A/F) Male Thread, NPT

0088	Thread
GNTH02N	1/8"
GNTH04N	1/4"



16mm Round Head Male Thread, BSPP

0088	Thread
2017-3886	1/8"
2017-3894	1/4"

For use with greasing units on hydraulic type nipples (DIN 71412). Precision fit jaws are hardened for extended life.

Maximum Working Pressure: 500 bar



Jaw Grease Connectors

0088	Length mm	Type
2017-3621	37	Valved
2017-3639	37	Unvalved

For use with greasing units on button and hexagon head grease nipples.

Maximum Working Pressure: 400 bar



Slide-on Connector

0088
2017-3647

For use with greasing units on button and hexagon head grease nipples.

Maximum Working Pressure: 400 bar



Hook-on Connector

0088
2017-3696

For use with greasing units on button and hexagon head grease nipples.

Maximum Working Pressure: 400 bar



Knuckle Jointed Slide-on Connector

0088
2017-3712

Fluid-Air Components Ltd

Adaptors



Straight, Male Connector

0382	Male Thread	Female Thread
SMF04U/02	1/4" UNF	1/8"
SMFM6/02	M6 x 1 Taper	1/8"
SMFM8/02	M8 x 1 Taper	1/8"




Battery Plate Adaptor, Brass, BSPP

0382	Female Thread	Tube OD mm
BPAM02-06-1	1/8"	6
BPAM02-06-2	1/8"	8



Anchor Block (One Way), Female Thread, BSPP

0382	Thread	Length mm	Width mm	Depth mm
ABS02-1	1/8"	30	15	15



Multi Point Anchor, Female Thread, BSPP

0382	Thread	Length mm	Ports
ABS02-2	1/8"	62	2
ABS02-4	1/8"	108	4
ABS02-6	1/8"	154	6

Lubrication Compression Fittings, Type LL

Suitable for oil and grease applications



Straights, Steel Zinc Plated

0382	OD mm	Thread
LU-1130	4	M6 x 1
LU-1140	4	M8 x 1
LU-1150	4	M10 x 1
LU-1160	4	1/8"
LU-1170	6	M6 x 1
LU-1180	6	M8 x 1
LU-1190	6	M10 x 1
LU-1200	6	1/8"
LU-1210	6	1/4"

stainless steel



Straights, 304 Stainless Steel

0382	OD mm	Thread
LU-1220SS	6	M6 x 1
LU-1230SS	6	M8 x 1
LU-1240SS	6	M10 x 1
LU-1250SS	6	1/8"



Elbows, Steel Zinc Plated

0382	OD mm	Thread
LU-1000	4	M6 x 1
LU-1010	4	M8 x 1
LU-1020	4	M10 x 1
LU-1030	4	1/8"
LU-1040	6	M6 x 1
LU-1050	6	M8 x 1
LU-1060	6	M10 x 1
LU-1070	6	1/8"
LU-1080	6	1/4"

Maximum Working Pressure: 100 bar

stainless steel



Elbows, 304 Stainless Steel

0382	OD mm	Thread
LU-1090SS	6	M6 x 1
LU-1100SS	6	M8 x 1
LU-1120SS	6	1/8"



Unions, Steel Zinc Plated

0382	OD mm
LU-1260	4
LU-1270	6

stainless steel



Unions, 304 Stainless Steel

0382	OD mm
LU-1290SS	6



Compression Nuts, Steel Zinc Plated

0382	OD mm
LU-1300	4
LU-1310	6

stainless steel



Compression Nuts, 304 Stainless Steel

0382	OD mm
LU-1340SS	6



Compression Rings, Steel Zinc Plated

0382	OD mm
LU-1320	4
LU-1330	6

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

GREASING & LUBRICATION EQUIPMENT

Lubrication Push-in Fittings

Material: Brass plated.
Suitable for use with oil and grease.



Straights

0382	OD mm	Thread
LU-1360	4	M6 x 1
LU-1370	4	M8 x 1
LU-1380	4	M10 x 1
LU-1390	4	1/8"
LU-1400	6	M6 x 1
LU-1410	6	M8 x 1
LU-1420	6	M10 x 1
LU-1430	6	1/8"

Maximum Working Pressure:
60 bar



Elbows

0382	OD mm	Thread
LU-1440	4	M6 x 1
LU-1450	4	M8 x 1
LU-1460	4	M10 x 1
LU-1470	4	1/8"
LU-1480	6	M6 x 1
LU-1490	6	M8 x 1
LU-1500	6	M10 x 1
LU-1510	6	1/8"



Unions

0382	OD mm
LU-1520	4
LU-1530	6



Swivel Unions, Metric

0382	OD mm	Thread
LU-1540	6	M6 x 1
LU-1550	6	M8 x 1
LU-1560	6	M10 x 1



Swivel Unions, BSPT

0382	OD mm	Thread
LU-1570	6	1/8"

Lubrication Adaptors

Material: Galvanised steel.
Suitable for use with oil and grease.



45° Male/Female Elbows, Metric

0382	Thread
LU-1580	M8 x 1
LU-1590	M10 x 1



45° Male/Female Elbows, BSPT

0382	Thread
LU-1600	1/8"



90° Male/Female Elbows, Metric

0382	Thread
LU-1610	M6 x 1
LU-1620	M8 x 1
LU-1630	M10 x 1



90° Male/Female Elbows, BSPT

0382	Thread
LU-1640	1/8"

Material: Brass.
Suitable for use with oil and grease.



Banjo Male/Female Elbows, Metric

0382	OD mm	Thread
LU-1650	4	M8 x 1
LU-1670	6	M6 x 1
LU-1680	6	M8 x 1
LU-1690	6	M10 x 1



Banjo Male/Female Elbows, BSPT

0382	OD mm	Thread
LU-1700	6	1/8"

Fluid-Air Components Ltd

High Pressure Hose & Accessories



Non-filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382	ID mm	OD mm
LU-1710	4	8.75
LU-1730	6.3	11.3

Grease Filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382	ID mm	OD mm
LU-1720	4	8.75



Straight Inserts, Steel Zinc Plated

0382	ID mm	OD mm
LU-1740	4	8.75
LU-1750	6	8.75



stainless steel

Straight Inserts, Stainless Steel

0382	ID mm	OD mm
LU-1760SS	6	8.75



90° Inserts, Steel Zinc Plated

0382	ID mm	OD mm
LU-1780	6	8.75
LU-1790	8	11.3



Ferrule, Zinc Plated

0382	OD mm
LU-1800	8.75
LU-1810	11.3



stainless steel

Ferrule, Stainless Steel

0382	OD mm
LU-1820SS	8.75
LU-1830SS	11.3

Lubrication & Pumping Equipment

Three inch air motor, provides more power to create better flow.

NXT Air Valve, designed to reduce icing in continuous use applications and uses less air than competitive pumps for better efficiency. Easy to repair or replace without tearing down internal pump components for less downtime.

Modular air valve, air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle free installations.

Built-in thermal relief and inlet strainer, built-in thermal relief protects your equipment from thermal expansion without the need to buy and install an additional kit.

Inlet strainer (oil only) is built-in to protect pump from containments that can damage your pump.

Connections:

Air line 1/4" BSP
Fluid outlet 1/2" BSP
Inlet 1" BSP
900mm plastic down tube
(can be cut down as required).



LD Range Oil Pumps

0382	Ratio	LPM
24G581	3:1	9.8
24G593	5:1	7.6



Wall Mount Bracket

0382	To Suit
24F910	24G5 Series Pumps

Remote Grease Systems

Contents:

- 1 x 1/8" BSP 2 way block
- 2 x 1/8" BSP straight grease nipples
- 4 x 1/8" BSP x 6mm straights
- 2 x M8 x 1 straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube



2 Point

0382
BAT03

Contents:

- 1 x 1/8" BSP 6 way block
- 6 x 1/8" BSP straight grease nipples
- 6 x M6 x 1 x 6mm straight compression fittings
- 6 x 1/8" BSP x 6mm straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube



6 Point

0382
BAT06

Manual Grease System

Contents:

- 1 x 1 litre manual pump
- 1 x 4 way grease block
- 1 x 81-5261-1/4 x 6mm straight
- 8 x 1/8" BSP x 6mm fitting
- 30 metre coils of 6 x 3 semi rigid black nylon tube
- 6 x 1 way pipe clips

- Suitable for soft grease NLGI NO 000,00,0
- For use on small machinery, direct feed on to bearings
- 1.00cc delivery per stroke
- Max discharge pressure 150 bar



4 Point

0382
PROG12

Fluid-Air Components Ltd

GREASING & LUBRICATION EQUIPMENT

Grease Coupler & Bracket

- This quick disconnect grease coupler is designed for quick and convenient disengagement of the coupler from the grease/zerk fittings under pressure.

Maximum Working Pressure:
550 bar



Quick Disconnect Coupler

0088	Thread
ZHC203B	1/8"
Tech Sheet 60358	

- Simple snap-action clamp for safe storage of grease guns and suction guns.



Grease Gun Bracket

0225	To Suit
ZGGH01	Barrel Diameter 57mm
Tech Sheet 60380	

Hydraulic Swivel Adaptor

- Professional 360º hydraulic adaptor, three jaw, 1/8" BSPT thread and hex nut.

Maximum Working Pressure:
483 bar




360º Swivel

0088	Thread
ZHCSW3B	1/8"
Tech Sheet 60359	

Thread Gauge

Threads:
NPT: 1/8", 1/4", 3/8"
Metric: M6 x 1, M6 x 0.75, M8 x 1, M8 x 1.25, M10 x 1, M10 x 1.5
BSPT: 1/8", 1/4"
UNF/ANF: 1/4", 5/16", 3/8"
BSW: 1/4", 5/16", 1/2", 3/8"
BSF: 3/16", 1/4", 5/16"



To suit Grease Nipples

0382
ZTHT01
Tech Sheet 60361

Extra Long Grease Coupler

The coupler will not move thus allowing a hands free operation

- Suitable for battery, air and manual operated grease guns
- Slim line diameter 17mm
- Unique 6 point contact design
- Length: 80mm



Extra Long Quick Disconnect Coupler

0122	Thread BSPTF	Max Pressure PSI/Bar
ZHC21XL	1/8"	8000/550
Tech Sheet 71692		

alliedhygiene



For **Hand Wet Wipes** ...see page **1761**

Fluid-Air Components Ltd

PRESSURE HOSES

Pressure Hoses

Working Temperature:
-40°C to +100°C



For use with Oil, 1/2" BSPP Male/Female x 1/2" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
1BMF0808-600	2320	600
1BMF0808-800	2320	800
1BMF0808-2000	2320	2000
1BMF0808-4000	2320	4000
1BMF0808-10000	2320	10000



For use with Grease, 1/4" BSPP Male/Female x 1/4" ID 2 Wire Hose

0300	Max Pressure PSI	Length mm
2BMF0404-600	5800	600
2BMF0404-1500	5800	1500
2BMF0404-4000	5800	4000
2BMF0404-10000	5800	10000



For use with Air & Water, 3/8" BSPP Male/Female x 3/8" ID Hose

0300	Max Pressure PSI	Length mm
AW-R6-600	1620	600
AW-R6-2000	1620	2000
AW-R6-4000	1620	4000
AW-R6-10000	1620	10000

Long Life Flexible Oil Lines

Working Temperature:
-40°C to +100°C



R1, 1/4" BSPP Female/ Female x 1/4" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
1BFF0404-600	3260	600
1BFF0404-750	3260	750
1BFF0404-1000	3260	10000

Working Temperature:
-40°C to +90°C



Thermoplastic, 1/4" BSPP Female/ Female x 1/4" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
7BFF0404-600	2755	600
7BFF0404-750	2755	750
7BFF0404-1000	2755	10000

Workshop Manual Pressure Test Pump

Designed for pressure testing hoses, pipework radiators and boilers etc. Can use with water or oil for testing. Comes with a gauge to monitor the pressure in the line. Fills the line you are testing with fluid from the reservoir. Comes complete with 2m delivery hose. 1/2" BSPM connector.

- Brass pump with anodised aluminium piston
- Housed in a 5 litre capacity steel reservoir
- Delivery per stroke: 12cc



Maximum Working Pressure:
209psi (20 bar).

0225
PTP

QUICK, CLEAN AND SAFE OIL CHANGES

DRAINTECHNOLOGY
Femco® Est. 1983
AUTHORISED DEALER



WHAT ARE THE ADVANTAGES OF THE FEMCO DRAINAGE SYSTEMS?

- The Femco oil drain plug reduces downtime
- You can drain oil at engine temperature, safely
- You can drain oil in an environmentally friendly way, because oil spillages are prevented
- Oil is contained from sump to container
- Eliminates the risk of stripped threads
- Tool-less oil changing; all you need is the drain hose

HOW DOES THE FEMCO OIL DRAIN PLUG WORK?

1) Remove the dust cover from the drain plug
2) Screw the Femco drain connector with hose onto the drainage system
3) The fluids are captured and flow straight to the container

WHICH OIL DRAIN PLUG SUITS MY APPLICATION THE BEST?

Femco produces a lot of oil drain plugs and they are all specialised for different applications.

- The Standard oil drain plug is installed when there is enough space available
- The Compact oil drain plug is used where space is restricted
- The Click Drain is used for a large number of vehicles
- The XL oil drain plug is used to drain a large amount of oil
- The Quick Drain is used for stationary machinery

WHERE CAN I FIND AN OIL DRAIN PLUG IN THE RIGHT SIZE?

Femco has a product range covering over 500 thread types and sizes. We can also make custom thread sizes. Please call us; we can help you to find the right size.

WHAT ARE THE DRAIN PLUGS MADE FROM?

All our oil drain plugs are made from solid brass.

CAN I USE A FEMCO OIL DRAIN PLUG IN COMBINATION WITH AN OIL EXTRACTOR PUMP?

All Femco oil drainage systems can be connected with an oil extractor pump.

CAN I PERFORM AN OIL CHANGE WHILE THE OIL IS STILL HOT?

All Femco oil drain plugs are produced from solid brass and can be used to drain oil at engine temperature.

IS IT POSSIBLE TO DRAIN FLUIDS OTHER THAN OIL?

The Femco oil drain plugs can be used to drain all kinds of fluid such as engine oil, coolant, gearbox oil and hydraulic oil.

WHAT HAPPENS IF I GET WATER IN MY FUEL TANK?

Femco drain plugs are ideal for draining condensation from fuel tanks.

HOW DO I PERFORM AN OIL CHECK?

Femco has produced various sampling nipples to make it easy to check the viscosity of the oil.

HOW CAN I CHANGE THE OIL IN A DIFFICULT-TO-REACH PLACE?

Femco can provide you with angled and extended drain connectors or special adaptors to drain oil even in the tightest spaces.

CAN A FEMCO OIL DRAIN PLUG BE FITTED WITH A MAGNET?

All Femco oil drain plugs can be provided with a magnet, which can be inspected after draining the oil.

WHO DOES FEMCO ALREADY SUPPLY?

Femco already supplies their drainage systems to companies like:

- Emirates
- MANN
- Hitachi
- Air China
- JCB
- VDL
- Daimler
- Kobelco
- Bell Equipment
- Alfagomma

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

QUICK OIL DRAIN PLUGS

Standard Drain Plugs

The Standard Drain – the original Femco® oil drain plug – was introduced in 1983 to change oil in a quick, clean and environmentally friendly way. The Standard Drain is manufactured out of 100% brass, which makes it easy to change hot oil. Additionally, the oil drain plugs are fitted with a dust cover and a double O-Ring, which protect the plug and ensure a reliable performance.

Application: Engine oil, hydraulic oil, gearbox oil, coolant, lubricating oil
Material: Brass outside and inside, stainless steel spring
Valve: Brass with Viton O-Ring/valve
Dust Cap: Brass, thread size LB: M26 x 1.5/SB: 22 x 1.5
Dust Cap Seal: NBR O-Ring
Body Seal: Viton O-Ring

Working Temperature:



NPT

0710	Thread
6060020141	1/4"
6060020142	3/8"
6060020143	1/2"
6060020140	3/4"
6060020145	1"
Tech Sheet 68080	

UNF

0710	Thread
6080020109	1/2"-20
6080020113	3/4"-16
6080020115	7/8"-14
6080020119	7/8"-20
6080020120	1"-12
Tech Sheet 68080	


Metric

0710	Thread
6090020030	M12 x 1.5
6090020033	M14 x 1.5
6090020036	M16 x 1.5
6090020038	M18 x 1.5
6090020040	M20 x 1.5
6090020046	M22 x 1.5
6090020053	M24 x 1.5
Tech Sheet 68080	

BSPP

0710	Thread
6070020130	1/4"
6070020131	3/8"
6070020132	1/2"
6070020134	3/4"
6070020141	1"
Tech Sheet 68080	

Installing FEMCO® Drain Plugs (Standard and Compact)



Standard Drain Accessories




Straight Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
650103	M26 x 1.5	18	250
Tech Sheet 68080			



90° Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
650108	M26 x 1.5	18	250
Tech Sheet 68080			



Dust Cap & Chain

0710	Thread
650113	M26 x 1.5
Tech Sheet 68080	



45° Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
650121	M26 x 1.5	18	250
Tech Sheet 68080			

For **Hydraulic Oils** ...see page **283**



Fluid-Air Components Ltd

QUICK OIL DRAIN PLUGS

Compact Drain Plugs

The Compact Drain is the smallest Femco® oil drain plug, and is the perfect choice for oil changes in tight spaces. The Compact plug only extends 12 millimetres from the sump, and is often used in vehicles with a low ground clearance such as cars, buses and motorcycles. You can install the compact plug on any vehicle without worrying about the available space.

Application: Engine oil, hydraulic oil, gearbox oil, coolant, lubricating oil
Material: Brass outside and inside, stainless steel spring
Valve: Brass with Viton O-Ring/valve
Dust Cap: Brass, thread size LB: M24 x 1,5/SB: 20 x 1.5
Dust Cap Seal: NBR O-Ring
Body Seal: Viton O-Ring

Working Temperature: -20°C to +200°C



NPT

0710	Thread
7060020406	1/4"
7060020407	3/8"
7060020408	1/2"
7090020411	3/4"
7060020413	1"
Tech Sheet 68080	

	1/2"-20
7080020360	7/8"-14
7080020363	7/8"-18
7080020378	11/8"-12
7080020372	5/16"-12
Tech Sheet 68080	


Metric

0710	Thread
7090020178	M12 x 1.5
7090020181	M14 x 1.5
7090020184	M16 x 1.5
7090020186	M18 x 1.5
7090020189	M20 x 1.5
7090020195	M22 x 1.5
7090020203	M24 x 1.5
Tech Sheet 68080	

BSPP

0710	Thread
7070020395	1/4"
7070020397	3/8"
7070020398	1/2"
7070020399	3/4"
7070020401	1"
Tech Sheet 68080	

Installing FEMCO® Drain Plugs (Standard and Compact)



Compact Drain Accessories



Straight Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
750005	M24 x 1.5	18	250
Tech Sheet 68080			



45° Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
750013	M24 x 1.5	18	250
Tech Sheet 68080			



90° Drainer, with Hose

0710	Thread	To Suit Hose ID mm	Length mm
750010	M24 x 1.5	18	250
Tech Sheet 68080			



Dust Cap

0710	Thread
750028	M24 x 1.5
Tech Sheet 68080	

Fluid-Air Components Ltd

QUICK OIL DRAIN PLUGS

Click Drain Plugs

The Click Drain enables you to perform quick, clean and environmentally friendly oil changes. The Click Drain is manufactured out of solid brass. This material is heat resistant, ensuring you can safely change hot fluids such as engine oil. You can use the oil drain valve without using any specialist tools. In addition to this, it is easy to take oil samples using the Click Drain. The Click Drain oil drain valve also incorporates a locking system to ensure an effective seal, creating a clean working environment.

Click Drain plugs make oil changes on your vehicles and machines quick and easy. This oil drain system consists of a plug and a clicker. When it is time for an oil change, you simply click the clicker onto the plug to start draining the oil. The Click Drain plug is often used in combination with the Femco® oil extractor pump, and is the ideal solution for small maintenance tasks on fleets of vehicles

Applications: engine oil, hydraulic oil, gearbox oil, coolant, lubricating oil
Material: brass outside and inside, stainless steel spring
Valve: Brass with viton O-Ring/valve
Dust Cap: brass, thread size LB: M26 x 1.5/SB: 22 x 1.5
Dust Cap Seal: NBR O-Ring
Body Seal: Viton O-Ring

Advantages of the Quick Drain oil drain valve:

- Reduction of downtime
- Easy operation
- Clean oil changes
- Change hot oil safely
- No tools required
- Easy way to sample oil



Working Temperature:
-20°C to +200°C

NPT

0710	Thread
8060020511	1/4"
8060020512	3/8"
8060020513	1/2"
8060020514	3/4"
8060020516	1"
Tech Sheet 68080	

BSPP

0710	Thread
8080020501	3/8"
8080020502	1/2"
8080020504	3/4"
8080020505	3/4" (Extended thread length)
8080020506	1"
Tech Sheet 68080	


UNF

0710	Thread
8080020482	3/4"-16
8080020483	7/8"-14
8080020486	7/8"-18
8080020487	7/8"-20
8080020489	1"-14
8080020492	1.1/2"-12
Tech Sheet 68080	


Metric

0710	Thread
8090020420	M12 x 1.5
8090020423	M14 x 1.5
8090020425	M16 x 1.25
8090020428	M18 x 1.5
8090020430	M20 x 1.5
8090020436	M22 x 1.5
8090020443	M24 x 1.5
Tech Sheet 68080	

Installing FEMCO® Drain Plugs (Click Drain)




Click Drain Accessories



Drain Connector, Solo Click, BSPP

1

0710	Thread
851000	1/2"
Tech Sheet 68080	



Drain Connectors, Double Click, BSPP

0710	Thread
851017	1/2"
851013	3/4"
851019	1"
Tech Sheet 68080	

Fluid-Air Components Ltd

TANK LEVEL GAUGES

FT PRO new product

Tank Gauge - Ideal For Domestic Tanks

- Reads the oil level and sends the reading to an indoor receiver
- Suitable with diesel, HVO, kerosene, oil, biodiesel, water, antifreeze and Adblue®
- Fits plastic tanks up to 3 metres deep. Easy to retrofit
- The transmitter needs a 20mm or 32mm hole on top of the tank
- No power required at the gauge, has a long-life lithium battery
- Comes with an electronic receiver that plugs into a 230V socket
- Receiver can be up to 200 metres away from the tank
- Tank level is displayed in ten graduations

Adblue®



0225	Length Metres
APOL.1	3

Tank Gauge - Float

- Suitable for diesel, heating oil, lube oils or water, antifreeze and biodiesel up to B100.
- Gauge provides a simple, rough indication of tank contents
- Shows EMPTY 1/4, 1/2, 3/4 or FULL
- Mounts directly into the top of tank
- Accuracy +/- 5%
- Now suitable with HVO.



0225	Thread	Length Metres
FG4E	1.1/2"	1.2
FG6E	1.1/2"	1.8

Tank Gauge - Remote Reading

- Simple hydrostatic tank contents gauge
- Suitable with diesel, biodiesel, HVO, oils, water and Adblue®
- UNITOP suits tanks from 0.9 metre to 3.2 metre high
- Probe has 1/2" BSP male tank fitting
- Readout can be sited up to 20 metres away from the tank
- Shows percentage of full tank contents
- Calibrate on site to suit tank
- Pull the plunger and release to show tank contents

Adblue®



0225	Description
UNITOP	Rectangular/Cylinder Tanks

Tank Gauge - Float

- Commonly used on oil and fuel drums, the float has a polyethylene construction which allows it to be used with a wide range of liquids including water, coolants etc.
- Face of indicator is fitted with a display marked from 0 to 210 litres. Reversing the display gives graduations from 0 to 55 gallons.
- Note that this is not a precise measuring device. The gauge is only to give an approximate level of liquid in the drum to know when to arrange a new drum.

1 YEAR WARRANTY



Drum Level Indicator

0122	Thread
ZDLI34N	3/4"
	Tech Sheet 71696

FAC Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

WORKSHOP FLUID TRANSFER

Funnels & Measures



Plastic Funnel

0225	Capacity Litres
ZFNL8	1.75
ZFNL9B	3



Flexible Spout Measure

0225	Capacity Litres
ZFSM1	1
ZFSM5	5

Fluid Drain Pans

Capacity: 17 Litres
Approx. Diameter: 460mm
Height: 150mm

Redashe



Oil/Fluid Drain Pan, 17 Litre

0261
DRP03
Tech Sheet 1144

Oil Drain Pans





Oil Drain Pans

0225	Capacity Litres
OPAN6	6
OPAN14	14

Features:

- High density polyethylene construction
- Closed design for safe and spill free disposal
- Large 8" (200mm) opening with catch all basket to hold small parts and filters.
- Integrated handle for easy carrying and handling
- Stores upright or flat without any leakage
- Complete with wheels for slosh and spill free mobility
- Recommended to be used with oil and antifreeze
- Approx. size (457mm x 406mm x 127mm)

1 YEAR WARRANTY



High Density Polyethylene Oil Drain Pan

0122	Capacity Litres
ZODP15	14
	Tech Sheet 71694

Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

WORKSHOP FLUID TRANSFER

Chemical Pressure Sprayer

- Brake cleaner and chemical pressure sprayer.



0225	Capacity Millilitres
J0002	1000

Garage Funnel

- 12" (260 x 170) HDPE with universal filter box.



Garage Funnel Complete with Filter

0225
J8055/12SE

UK Type Funnels

- HDPE Anti-Spill Funnel with filter and flexispout.



Complete with Strainer

0225	Size
J8055/6	6"
J8055/9	9"

- HDPE Flexispout oil measures



Complete with Measure & Flexible Spout

0225	Capacity Litres
J8057/1N	1
J8057/2N	2
J8057/3N	3
J8057/5N	5

4 Piece Plastic Funnel Set

- Capacity: 430ml (15oz), 245ml (8.5oz), 120ml (4.2oz) and 40ml (1.4oz)
- Diameter: 125mm (5''), 100mm (4''), 75mm (3'') and 50mm (2'')
- High rim works as an effective splash guard
- Recommended use: Diesel, Gasoline, Kerosene, Urea, Oils, Antifreeze and other water based media
- Do not use with: Acids and other media at temperatures above 60°C (140°F)

Redashe

1 YEAR WARRANTY



0122
ZFNL4ST
Tech Sheet 71688

R Grip

- Single coil "R" grips with bright zinc plate finish.



Pack of 100

0225	Bore Size mm
J0787	2
J1181	3
J1373	3.5
J1574	4
J1968	5
J2362	6

Linch Pins

- Linch pins with 3.5mm wire dia O-Ring.
- Bright zinc plate and gold passivate finish.



Linch Pins, Pack of 100

0225	Bore Size mm
J0250	6
J0312	8
J0437	11

- Safety linch pin with
- O-Ring 54mm usable length.



Safety Linch Pins, Pack of 100

0225	Bore Size mm
J7502	9

Fluid-Air Components Ltd

FT PRO

Heavy-duty, Brass Water Guns



- Inlet connection: 1/2" BSPP
- Automatic shut-off
- Adjustable spray pattern
- Rubber insulated body and handle
- Scuff resistant
- Trigger lock

Note: not suitable for use with steam.

Maximum Working Temperature:
+50°C

Maximum Working Pressure
25 bar

BSPP Inlet, Brass

1369	Thread	Colour
WASH-GUN	1/2"	Blue
REDWASH-GUN	1/2"	Red

1657

Heavy-duty, Stainless Steel Hygienic Water Guns



- Colour coded for use in hygienic zone systems
- Inlet connection: 1/2" BSPP
- Automatic shut-off
- Adjustable spray pattern
- Non-marking rubber insulated body and handle
- Trigger lock

Maximum Working Temperature:
+90°C (intermittent use)

Maximum Working Pressure
25 bar

BSPP Inlet, Stainless Steel

1369	Thread	Colour
HYGWASH-GUN	1/2"	White
HYGWASH-GUNR	1/2"	Red
HYGWASH-GUNG	1/2"	Green

1658

Fluid-Air Components Ltd

WASHDOWN & CLEANING PRODUCTS

Water Guns



Water Gun

1369	Inlet BSPP
WG02	1/2"

- Blue available to order



Stainless Steel Water Gun

1369	Colour	Female Inlet BSP	Flow Rate
XGNSS	White	1/2"	25
XGNSSR	Red	1/2"	25

WASHDOWN & CLEANING PRODUCTS

High Pressure Water Quick Release Coupling & Plug

Interchangeable with:
Nito High Pressure Water Coupling
40 Series water coupling

Maximum Working Pressure:
210 bar



Female Coupling, BSPP

1369	Thread
PWQRC-38	3/8"



Female Plug, BSPP

1369	Thread
PWQRP-38	3/8"

Couplings to suit A Series Nozzles



1/4" BSPP Female Quick Release Coupling

1369
CDC-14F-14M-B



1/4" BSPP Male Quick Release Coupling

1369
CDC-14M-14M-B

Coupling & Adaptor



1/4" Brass Bayonet, Female

1369
CDAX

WATER GUN

NiTO Ergo Water Gun

Hot-water gun with an elegant design with focus on ergonomics, quality and functionality. The shape ensures a thermal protection of the handle. The trigger is protected against unintentional activation for safety, and can be locked for prolonged use. Infinitely variable flow regulatio optimises the water quantity, whatever the task. Made of impact-resistant composite material with a high resistance to chemicals.

Maximum Working Temperature: +40°C

Maximum Working Pressure: 6 bar



1068	Coupling Size
40525A3	1/2"
40500A3	3/4"

NiTO II Industry Water Gun

Maximum Working Temperature: +90°C

Maximum Working Pressure: 25 bar



BSPP

1068	Thread
30550A3	3/4"

NiTO II Spray Nozzles



For 15mm & 20mm Hose

1068	Nozzle
20000A4	1/2"



3/4" Female Thread

1068	Nozzle
20300A9	3/4"

NiTO I Water Gun



Maximum Working Temperature: +40°C

Maximum Working Pressure: 6 bar

With On/Off & Linear Flow Control

1068	Thread
53800A1	1/2"
63820A1	3/4"

NiTO Safety Couplings

Note: 6151SA8 suitable for NiTO II industry water gun.



1068	ID
6151SA8	1/2"
6150SA8	3/4"

NiTO Safety Plugs

Note: 61640A8 suitable for NiTO II industry water gun.



1068	ID
61640A8	1/2"
61650A3	3/4"

NiTO O-Rings for High Pressure Couplings



1068	Description
1107A8	Viton 20 Shore
1108A8	Viton 17 Shore

NiTO High Pressure Water Couplings

Maximum Working Temperature: +100°C

Maximum Working Pressure: 250 bar

Material: Brass and chromium plated

- Coupling set suitable for KEW high pressure cleaners



Complete Coupling, Female, BSPP

1068	Thread
65506B3	3/8"
	Tech Sheet 20361



Female, BSPP

1068	Thread
65500B3	3/8"
	Tech Sheet 20361



Male, BSPP

1068	Thread
6550NB3	M22 x 1.5
	Tech Sheet 20361

NiTO High Pressure Water Plugs

Maximum Working Temperature: +100°C

Maximum Working Pressure: 250 bar

Material: Brass and chromium plated



Female Metric & BSPP

1068	Thread
65610B9	3/8"
65632B9	M22 x 1.5

Fluid-Air Components Ltd

NITO Original Water Couplings

Wide range of couplings that solve all thread and hose combination.



WATER

MAX 25 BAR

-30 / +80 °C

NITO
THE STRONGEST CONNECTION

1661

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

1/2" SYSTEM

Working Temperature: -30°C to +80°C

Maximum Working Pressure: 25 bar

Material: Brass nickel plating

Seal: Nitrile

Couplings



Male, BSPP

1068	Thread	Operation
5350NA3	1/2"	No Valve
5353NA3	1/2"	Valved
5352NA3	3/4"	No Valve



Female, Metric & BSPP

1068	Thread	Operation
53500A3	1/2"	No Valve
53520A3	3/4"	No Valve
53530A3	3/4"	Valved
5353GA3	M22 x 1	Valved



Hose Tail

1068	To Suit Hose ID	Operation
5349SA3	3/8"	No Valve
5350SA3	1/2"	No Valve
5351SA3	3/4"	No Valve
5353SA3	1/2"	Valved
5354SA3	3/4"	Valved

Plugs



Male, Metric & BSPP

1068	Thread
5364BA3	3/8"
53640A3	1/2"
5364AA3	3/4"



Female, Metric & BSPP

1068	Thread
53610A3	1/2"
5361AA3	3/4"
53620A3	M22 x 1



Hose Tail

1068	ID	ID mm
5360DA3	1/4"	6
5360BA3	3/8"	8
53600A3	1/2"	13
5360CA3	5/8"	16



Equal

1068
53650A3



Double Hose Tail

1068	ID
5360AA3	1/2" & 3/4"



To suit Water Gun, BSPP

1068	Thread
53611A3	1/2"

Adaptors



Reducing Bush

1068	Male Thread	Female Thread
53690A3	1/2"	3/4"
63690A3	3/4"	1"
53700A3	1/2"	M22 x 1



Reducing Bush

1068	Male Thread	Female Thread
5371AA3	3/4"	1/2"



Reducing Bush

1068	Male Thread	Female Thread
5349BA8	1/2"	3/8"
53490A8	3/4"	1/2"

Hose Union



BSPP

1068	Thread	To Suit Hose ID
53670A3	1/2"	1/2"

Adjustable Nozzle



1068	ID
53750A3	1/2"

Fluid-Air Components Ltd

1/2" SYSTEM

Working Temperature: -30°C to +80°C
Maximum Working Pressure: 25 bar
Material: Brass nickel plating
Seal: Nitrile

Hose Union Washer



1068
1-290A8

NiTO O-Rings



1068
53470A8

NiTO Washers



1068	Description
53440A8	1/2"

3/4" SYSTEM

Working Temperature: -30°C to +80°C
Maximum Working Pressure: 25 bar
Material: Brass nickel plating
Seal: Nitrile

Couplings



Female, BSPP

1068	Thread	Operation
63500A3	3/4"	No Valve
63530A3	3/4"	Valved



Hose Tail

1068	To Suit Hose ID	Operation
6353SA3	3/4"	Valved
6350SA3	3/4"	No Valve



Hose Union

1068	To Suit Hose ID	ID
6367AA3	3/4"	1/2"
63670A3	3/4"	3/4"



Adjustable Nozzle

1068	ID
63750A3	3/4"

Plugs



Male, BSPP

1068	Thread
6364AA3	1/2"
63640A3	3/4"



Female, BSPP

1068	Thread
6361AA3	1/2"
63610A3	3/4"



Hose Tail

1068	To Suit Hose ID	To Suit Hose ID mm
6360BA3	1/2"	13
63600A3	3/4"	16



Double Hose Tail

1068	To Suit Hose ID
6360AA3	1" & 3/4"

NiTO O-Rings



1068
63470A8

NiTO Washers



1068
63440A8

Redashe



For **Hose Reels** see pages **1456-1462**

1" SYSTEM

Working Temperature: -30°C to +80°C

Maximum Working Pressure: 25 bar

Material: Brass nickel plating

Seal: Nitrile

Couplings



Female, BSPP

1068	Thread	Operation
73500A3	1"	No Valve
73530A3	1"	Valved

Plugs



Male, BSPP

1068	Thread
73640A3	1"



Female, BSPP

1068	Thread
73610A3	1"



Hose Tail

1068	To Suit Hose ID
7360BA3	3/4"
73600A3	1"

CLICK™ SYSTEM

Working Temperature: -30°C to +80°C

Maximum Working Pressure: 25 bar

- Click™ coupling system for the professional market - compatible with the most popular plastic couplings
- The same high quality as the original NiTO couplings
- 5 year function guarantee
- Complete programme for the trade and industry, house and garden

Couplings



Male, BSPP

1068	Thread
5950NA3	1/2"



Female, BSPP

1068	Thread
5952GA3	1/2"



Hose Tail

1068	To Suit Hose ID
5949SA3	3/8"
5950SA3	1/2"
5951SA3	3/4"



Hose Tail with Valve

1068	To Suit Hose ID
5953SA3	1/2"

Plugs



Male, BSPP

1068	Thread
59640A3	1/2"



Female, BSPP

1068	Thread
5961GA3	1/2"



Hose Tail

1068	To Suit Hose ID
59600A3	1/2"



Double Hose Tail

1068	To Suit Hose ID
5960AA3	1/2" & 3/4"

Fluid-Air Components Ltd

STAINLESS STEEL

NiTO Original Stainless Steel Quick Release Couplings

stainless steel



Coupler to Female, BSPP

1068	Thread	Coupling Size
54500A3	1/2"	1/2"
54520A3	3/4"	1/2"
64500A3	3/4"	3/4"

stainless steel



Coupler to Hose Tail

1068	To Suit Hose ID	Coupling Size
5450SA3	1/2"	1/2"
6450SA3	3/4"	3/4"

stainless steel



Valve Couplers to Female, BSPP

1068	To Suit Hose ID	Coupling Size
54530A3	3/4"	1/2" with Valve
64530A3	3/4"	3/4" with Valve

stainless steel



Valve Couplers to Hose Tail

1068	To Suit Hose ID	Coupling Size
5453SA3	1/2"	1/2" with Stop Valve
6453SA3	3/4"	3/4" with Stop Valve

stainless steel



Nipple Couplers to Female, BSPP

1068	Thread	Coupling Size
54610A3	1/2"	1/2"
5461AA3	3/4"	1/2"
64610A3	3/4"	3/4"

stainless steel



Nipple Couplers to Male, BSPP

1068	Thread	Coupling Size
54611A3	1/2"	1/2"
64611A3	3/4"	3/4"

stainless steel



Nipple Coupler to Double Hose Tail

1068	To Suit Hose ID	Coupling Size
5460AA3	1/2" & 3/4"	1/2"

stainless steel



Nipple Couplers to Hose Tail

1068	To Suit Hose ID	Coupling Size
54600A3	1/2"	1/2"
64600A3	3/4"	3/4"


stainless steel



Male to Hose Tail, BSPP

1068	Thread	To Suit Hose ID
64670A3	3/4"	3/4"

FT PRO



For **Food Certified Reinforced PVC Braided Hose** see page **1406**

WASH DOWN EQUIPMENT

Pressure Washer Lances

- Inlet connection: 3/8" BSPP
- Maximum flow: 25 L/min
- 15° spray pattern nozzle

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Hand grip options: moulded or vented.
Lance style options: straight or 15° bend.
Length options: 430-900mm.



Short Straight, Moulded Grip



Straight, Moulded Grip



15° Moulded Grip



Straight, Vented Grip



15° Vented Grip



Straight Moulded Grip

1369	Thread	Length mm	Max Pressure Bar
PRESSURE-LANCESH	3/8"	430	250
PRESSURE-LANCE	3/8"	900	280

15° Moulded Grip


1369	Thread	Length mm	Max Pressure Bar
PRESSURE-LANCE15	3/8"	900	280

Straight, Vented Grip

1369	Thread	Length mm	Max Pressure Bar
PRESSURE-L500V	3/8"	500	280
PRESSURE-L635V	3/8"	635	280
PRESSURE-L760V	3/8"	760	280
PRESSURE-L900V	3/8"	900	280

15° Vented Grip

1369	Thread	Length mm	Max Pressure Bar
PRESSURE-L15500V	3/8"	500	280
PRESSURE-L15635V	3/8"	635	280
PRESSURE-L15760V	3/8"	760	280
PRESSURE-L15900V	3/8"	900	280



Adjustable

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

- Inlet connection: 3/8" BSPP
- Maximum flow: 40 L/min
- Solid moulded or vented hand grips
- Nozzle holder and protector
- 15° spray pattern nozzle
- 900mm lance length
- Adjustable high/low pressure nozzle
- Extra hand grip allows the user more control of the spray



Solid Moulded Hand Grip



Vented Moulded Hand Grip

Solid Moulded Hand Grip, BSPP

1369	Thread	Length mm
CD-2502	3/8"	900

Vented Moulded Hand Grip, BSPP

1369	Thread	Length mm
CD-2501	3/8"	900

Fluid-Air Components Ltd

Pressure Washer Trigger & Lance Assemblies

Maximum Working Temperature: +150°C

Flow: 40 L/min

High Flow, Short Lance, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA1	3/8"	400	310

Flow: 40 L/min

High Flow, Long Lance, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA2	3/8"	900	250

Flow: 25 L/min

Low Flow, Twin Lance with Top Control, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA3	3/8"	1060	280

Flow: 30 L/min

High Flow, Twin Lance with Top Control, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA4	3/8"	1060	310

Flow: 25 L/min

Low Flow, Twin Lance with Handle, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA5	3/8"	1060	280

Flow: 40 L/min

High Flow, Twin Lance with Handle, BSPP



1369	Thread	Length mm	Max Pressure Bar
PWLA6	3/8"	1060	345

Flow: 25 L/min

stainless steel

Low Flow, Twin Stainless Steel Lance with Top Control, BSPP



1369	Thread	Max Pressure Bar
PWLA7	3/8"	280

Flow: 40 L/min

stainless steel

High Flow, Twin Stainless Steel Lance with Handle, BSPP



1369	Thread	Max Pressure Bar
PWLA8	3/8"	250

Flow: 25 L/min

stainless steel

Low Flow, Twin Stainless Steel Lance with Handle, BSPP



1369	Thread	Max Pressure Bar
PWLA9	3/8"	280

Flow: 40 L/min

stainless steel

High Flow, Twin Stainless Steel Lance, with Top Control, BSPP



1369	Thread	Max Pressure Bar
PWLA10	3/8"	250

Wash Down Lance & Trigger

Our high pressure water assembly has a 900mm zinc plated straight lance, single moulded hand grip, nozzle holder and protector.

Maximum Flow: 40

Maximum Working Temperature: +150°C

Maximum Working Pressure: 310 bar



High Pressure, High Flow, Long Lance, BSPP

1369	Thread	Length mm	Max Pressure Bar
1002-0038	3/8"	900	310

Please note: Nozzles not included. See page 1674 for nozzles.

Fluid-Air Components Ltd

Pressure Lance Configurator


PWAA-14F


PWAA-14M

See page 1673


PWAB-14M


21-051


21-049


PWAB-14F


PWAB-22MM


PWAB-22FF

See page 1673


CDQ1500


CDQ1900


CDQ1600


CDQ2100


ST7


ST900


SW-ST4


SW-ST6

See page 1670


CDE

See page 1675


BC-13


BA-16


BD-20


CDBB-20


BMG-20


CDBJ-20


CDBU-42

CDBV-42

See page 1671


CDAZ

See page 1675

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c




See page 1675



See page 1672




See page 1675



See page 1672



See pages 1659 & 1674



See pages 1673-1674

WASH DOWN EQUIPMENT

Pressure Wash Lance Triggers

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



BSPP, 25 L/min

1369	Inlet Thread	Outlet Thread
ST900	3/8"	1/4"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



BSPP, 25 L/min

1369	Inlet Thread	Outlet Thread
CDQ1900	3/8"	1/4"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



BSPP, 40 L/min, Soft Grip

1369	Inlet Thread	Outlet Thread
CDQ1500	3/8"	1/4"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 345 bar



BSPP, 45 L/min, In-line

1369	Inlet Thread	Outlet Thread
CDQ2100	3/8"	1/4"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 310 bar



BSPP, 30 L/min, High Pressure

1369	Inlet Thread	Outlet Thread
ST-5	3/8"	1/4"

Maximum Working Temperature: +150°C


Maximum Working Pressure: 345 bar



BSPP, 45 L/min

1369	Inlet Thread	Outlet Thread
CDQ1600	3/8"	1/4"

Pressure Wash Lance Swivel Triggers



Maximum Working Temperature: +150°C

Maximum Working Pressure: 345 bar



Metric, 40 L/min

1369	Inlet Thread	Outlet Thread
ST-7	M22 x 1.5 Female	M22 x 1.5 Female

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



BSPP, 25 L/min

1369	Inlet Thread	Outlet Thread
SW-ST4	3/8"	1/4"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



BSPP, 40 L/min

1369	Inlet Thread	Outlet Thread
SW-ST6	M22 x 1.5 Male	1/4"

Fluid-Air Components Ltd

Extended Lances, 1/4" BSPT Male Inlet/Outlet



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Straight Vented Grip, 30 L/min

1369	Length mm
BD-20	500
BD-25	635
BD-30	760
BD-36	900



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Angled Vented Grip, 45 L/min

1369	Length mm
CDBB-20	500
CDBB-25	635
CDBB-30	760
CDBB-36	900



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Straight Moulded Grip, 45 L/min

1369	Length mm
BMG-20	500
BMG-25	635
BMG-30	760
BMG-36	900



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Angled Moulded Grip, 45 L/min

1369	Length mm
CDBJ-20	500
CDBJ-25	635
CDBJ-30	760
CDBJ-36	900



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Angled Twin Moulded Grip, 30 L/min

1369	Length mm
CDBU-42	1065
CDBU-47	1190
CDBU-50	1270



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Straight Twin Moulded Grip, 80 L/min

1369	Length mm
CDBV-42	1065
CDBV-47	1190
CDBV-50	1270

Extended Lances, 1/4" Male Inlet x M22 Female Outlet



Maximum Working Temperature: +150°C

Maximum Working Pressure: 250 bar

Straight Vented Grip, 80 L/min

1369	Length mm
BA-16	405
BA-18	457
BA-20	508



Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar

Straight Moulded Grip, 45 L/min

1369	Length mm
BC-13	330
BC-15	380
BC-18	457
BC-20	508

M22 Extension & Nozzle



Maximum Working Temperature: +60°C

Maximum Working Pressure: 150 bar

Adjustable M22 Male Extension, 25 L/min

1369	Length mm
CDBL-15	375

WASH DOWN EQUIPMENT

Twin Pressure Washer Lances

Maximum Working Temperature: +60°C

Maximum Working Pressure: 250 bar

Flow: 35 L/min

stainless steel



Stainless Steel Twin Lance with Top Control, BSPP

1369	Thread
SSTLTC	1/4"

Flow: 45 L/min

stainless steel



Stainless Steel Twin Lance with Handle, BSPP

1369	Thread
SSTLH	1/4"

Flow: 45 L/min



Zinc Plated Twin Lance with Handle, BSPP

1369	Thread
ZPTLH	1/4"

Flow: 45 L/min



Zinc Plated Twin Lance with Top Control, BSPP

1369	Thread
ZPTLTC	1/4"

Pressure Washer Lances

All supplied with 1/4" female thread nozzle holder and protector. 1/4" male thread inlet.

Maximum Working Temperature: +150°C

Maximum Working Pressure: 250 bar

Maximum Flow: 40 L/min



Straight with Moulded Grip Zinc Plated

1369	Length mm	No of Grips
SL-2	900	1



Bent End with Moulded Grip Zinc Plated

1369	Length mm	No of Grips
SL-3	900	1
SL-4	1200	2



Bent End with Hollow Grip Zinc Plated

1369	Length mm	No of Grips
SL-5	700	1



Bent End with Vented Grip Zinc Plated

1369	Length mm	No of Grips
SL-7	900	1
SL-8	900	2



stainless steel

Bent End with Moulded Grip Stainless Steel

1369	Length mm	No of Grips
SL-11	1200	1



stainless steel

Straight with Moulded Grip Stainless Steel

1369	Guard Type	Length mm	No of Grips
SL-13	Slide on	900	1

Heavy-duty Foam Injection Bottle

- Heavy-duty foam injection bottle connects easily to your existing pressure washer lance or gun.
- Foam bottle sprays foam all over the vehicle creating the "snow bath effect".
- 1/4" BSPP male inlet connection.
- 1 litre bottle.
- 1/4" x 1/4" adaptor removable for ease. Other adpators can be fitted.
- Variable angle spray pattern nozzle.
- Adjustable detergent displacement.

Maximum Working Temperature: +60°C

Maximum Working Pressure: 275 bar



Male, BSPP

1369	Thread
FGB-1	1/4"

Fluid-Air Components Ltd

Pressure Washer Adaptors

Maximum Flow: 40 L/min

Maximum Working Temperature: +140°C

Maximum Working Pressure: 210 bar



BSPP Male x Female M22 x 1.5

1369	Thread
PWAB-14M	1/4"
PWAB-38M	3/8"
PWAB-12M	1/2"

Maximum Flow: 40 L/min

Maximum Working Temperature: +140°C

Maximum Working Pressure: 210 bar



BSPP Female x Male M22 x 1.5

1369	Thread
PWAA-14F	1/4"
PWAA-38F	3/8"
PWAA-12F	1/2"
PWAA-22F	M22 x 1.5

Maximum Working Temperature: +90°C

Maximum Working Pressure: 250 bar



Compact Swivel Coupling Brass, 3/8" BSPP

1369
21-049

Maximum Flow: 40 L/min

Maximum Working Temperature: +140°C

Maximum Working Pressure: 210 bar



BSPP Female x M22 x 1.5 Female

1369	Thread
PWAB-14F	1/4"
PWAB-38F	3/8"

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



M22 x 1.5 Male

1369	Thread
PWAB-22MM	M22 x 1.5

Maximum Working Temperature: +150°C

Maximum Working Pressure: 280 bar



M22 x 1.5 Female

1369	Thread
PWAB-22FF	M22 x 1.5

Maximum Working Temperature: +130°C

Maximum Working Pressure: 250 bar



Brass Swivel Coupling Standard, BSPP

1369	Thread
21-051	1/4"
21-050	3/8"
21-052	1/2"

Maximum Working Temperature: +130°C

Maximum Working Pressure: 250 bar



stainless steel

Stainless Steel Swivel Coupling Standard, BSPP

1369	Thread
21-055	1/4"
21-056	3/8"
21-057	1/2"

Maximum Flow: 40 L/min

Maximum Working Temperature: +140°C

Maximum Working Pressure: 210 bar



BSPT Male x M22 x 1.5 Male

1369	Thread
PWAA-14M	1/4"
PWAA-38M	3/8"

Maximum Working Temperature: +130°C

Maximum Working Pressure: 250 bar



M22 x 1.5 Male Hose Coupling with Insulated Grip

1369	Thread
30-028	M22 x 1.5

Maximum Working Temperature: +130°C

Maximum Working Pressure: 250 bar



Foam Thickener

1369	Thread
26-0021	1/4"

High Pressure Spray Nozzles

Stainless steel, 1/4" male thread with a hardened steel insert for longer life and better accuracy, suitable for single and double lances.



Stainless Steel, 1/4" NPT Male

1369	Spray Pattern	LPM @ 50 Bar	LPM @ 100 Bar	LPM @ 150 Bar
2020-2982	0°	8	11.3	13.8
2020-2990	0°	8.7	12.4	15.2
2020-3014	0°	9.6	13.6	16.7
2020-3089	15°	8	11.3	13.8
2020-3105	15°	8.7	12.4	15.2
2020-3113	15°	9.6	13.6	16.7
2020-3139	25°	8	11.3	13.8
2020-3147	25°	8.7	12.4	15.2
2020-3154	25°	9.6	13.6	16.7
2020-3162	40°	8	11.3	13.8
2020-3188	40°	8.7	12.4	15.2
2020-3204	40°	9.6	13.6	16.7



Brass, 1/4" BSPT Male

1369
2021-8061

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

WASH DOWN EQUIPMENT

Rotating Head Nozzle

Flow: 45 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 345 bar



1/4" Female, BSPP

1369
9202L

Fixed Head Nozzle

Flow: 45 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 280 bar



1/4" Female, BSPP

1369
9203L

1/4" High Pressure Quick Release Nozzles



A Series Nozzles

1369	Spray Pattern	LPM @ 50 Bar	LPM @ 100 Bar	LPM @ 150 Bar	Colour
A00050	0°	8	11.3	13.8	Red
A00055	0°	8.7	12.4	15.2	Red
A00060	0°	9.6	13.6	16.7	Red
A15050	15°	8	11.3	13.8	Yellow
A15055	15°	8.7	12.4	15.2	Yellow
A15060	15°	9.6	13.6	16.7	Yellow
A25050	25°	8	11.3	13.8	Green
A25055	25°	8.7	12.4	15.2	Green
A25060	25°	9.6	13.6	16.7	Green
A40050	40°	8	11.3	13.8	White
A40055	40°	8.7	12.4	15.2	White
A40060	40°	9.6	13.6	16.7	White

Adjustable Pressure Nozzle

Flow: 25 L/min

Maximum Working Temperature: +60°C

Maximum Working Pressure: 200 bar



1/4" Female, BSPP

1369
CDQC-14

Fixed Jet Pressure Nozzle

Maximum Working Temperature: +90°C

Maximum Working Pressure: 385 bar



Sewer Drain Cleaning Head, 1 Forward 3 Rear, 1/4" Female, BSPP

1369	Nozzle	Flow @ 380 Bar
CDQP045-14	0.70mm-045	20 LPM
CDQP001-14	1.0mm-080	35 LPM

Drain Nozzles

Maximum Working Temperature: +95°C

Maximum Working Pressure: 385 bar



Fixed, BSPP

1369	Thread	Nozzle Dia mm
SJN-2-045	1/8"	0.7
SJN-2-050	1/8"	0.75
SJN-2-055	1/8"	0.8
SJN-4-045	1/4"	0.7
SJN-4-050	1/4"	0.75
SJN-4-055	1/4"	0.8
SJN-6-045	3/8"	0.7
SJN-6-050	3/8"	0.75
SJN-6-055	3/8"	0.8

Maximum Working Temperature: +95°C

Maximum Working Pressure: 280 bar



Rotating, BSPP

1369	Thread	Nozzle Dia mm
RSJN-2-045	1/8"	0.7
RSJN-2-050	1/8"	0.75
RSJN-2-055	1/8"	0.8
RSJN-4-045	1/4"	0.7
RSJN-4-050	1/4"	0.75
RSJN-4-055	1/4"	0.8
RSJN-6-045	3/8"	0.7
RSJN-6-050	3/8"	0.75

Nozzle Holders

Flow: 36 L/min

Maximum Working Temperature: +60°C

Maximum Working Pressure: 250 bar



Steel, 1/4" Female x 1/4" Female, BSPP

1369
CDH005

Flow: 36 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 250 bar



Steel, 1/4" Female x 1/4" Female, Adjustable with Protector, BSPP

1369
CDH004

Flow: 36 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 250 bar



Brass, 1/4" Female x 1/4" Female, BSPP

1369
CDH002

Flow: 36 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 250 bar



Brass, 1/4" Female x 1/4" Female, Adjustable with Protector, BSPP

1369
CDH006

Flow: 36 L/min

Maximum Working Temperature: +90°C

Maximum Working Pressure: 250 bar



Short Brass, 1/4" Female x 1/4" Female, BSPP

1369
CDH001

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

WASH DOWN EQUIPMENT

Pressure Wash Floor Cleaner

- 20"/500mm diameter
- 3/8" BSPP inlet
- Stainless steel construction
- 280 bar/4,000 psi maximum pressure
- 40 litres per minute at +100°C
- Maximum flow complete with 3 x 25° nozzles

Maximum Working Temperature: +100°C





20" Stainless Steel Floor Cleaning Tool

0363	Thread
PWFC-20	3/8"

Pressure Wash Accessories

Maximum Working Temperature: +100°C

Maximum Working Pressure: 190 bar



Spare Handle

1369
CDAZ



Hand Scrubbing Brush

1369
CDN



Rotating Scrubbing Brush

1369
CDM



Rotating Floor Scrubbing Brush

1369
CDO

Tools Adaptors



Lance M22 to CDL Adaptor

1369	Thread
CDE	M22



CDE to Tools Adaptor

1369
CDL

Cleaning Fluids

- PowerWash TFR is used in conjunction with mobile pressure washers, fixed arch moving gantries, and ultrasonic low pressure equipment.
- Specially designed for use in hot or cold pressure wash equipment.
- Highly economical to use and best results are obtained at very low concentration.



General Purpose Pressure Wash Detergent

0088	Volume Litres
59603-25	25

- Methanol free non-toxic concentrated screen wash designed for year round use.
- Leaves windscreens clean and smear free.



Screenwash

0088	Volume Litres
54027-25	25

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.

Fluid-Air Components Ltd


WASH DOWN EQUIPMENT

Blue Jet Wash Pressure Washer Hose



- Oil, abrasion, ozone and weather resistant synthetic pin-pricked rubber.
- High tensile 1 and 2 wire steel braid.

Working Temperature:
-40°C to +155°C



1 Wire 2 Wire

1 Wire, 10 Metre Coils

0303	ID	Max Pressure Bar
PWBLUE-04-10-R1	1/4"	225
PWBLUE-05-10-R1	5/16"	215
PWBLUE-06-10-R1	3/8"	180
Tech Sheet 3105		

2 Wire, 10 Metre Coils

0303	ID	Max Pressure Bar
PWBLUE-06-10-R2	3/8"	330
Tech Sheet 3105		

1 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
PWBLUE-04-25-R1	1/4"	225
PWBLUE-05-25-R1	5/16"	215
PWBLUE-06-25-R1	3/8"	180
Tech Sheet 3105		

2 Wire, 100 Metre Coils

0303	ID	Max Pressure Bar
PWBLUE-04-100-R2	1/4"	400
PWBLUE-06-100-R2	3/8"	330
Tech Sheet 3105		

2 Wire, Cut to Length, per Metre

1369	ID	Max Pressure Bar
2144-9681	1/4"	400
2144-9699	5/16"	350
2052-1423	3/8"	330
Tech Sheet 3105		

Black Jet Wash Pressure Washer Hose



- Oil, abrasion, ozone and weather resistant synthetic pin-pricked rubber.
- High tensile 1 and 2 wire steel braid.

Working Temperature
-40°C to +155°C





1 Wire 2 Wire

1 Wire, 10 Metre Coils

0303	ID	Max Pressure Bar
PWBLACK-04-10-R1	1/4"	225
PWBLACK-05-10-R1	5/16"	215
PWBLACK-06-10-R1	3/8"	180
Tech Sheet 3105		

1 Wire, 100 Metre Coils

0303	ID	Max Pressure Bar
PWBLACK-04-100R1	1/4"	225
Tech Sheet 3105		

1 Wire, Cut to Length, per Metre

1369	ID	Max Pressure Bar
2144-9657	1/4"	225
2144-9665	5/16"	215
2144-9673	3/8"	180
Tech Sheet 3105		

1 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
PWBLACK-04-25-R1	1/4"	225
PWBLACK-05-25-R1	5/16"	215
PWBLACK-06-25-R1	3/8"	180
Tech Sheet 3105		

2 Wire, 100 Metre Coils

0303	ID	Max Pressure Bar
PWBLACK-04-100R2	1/4"	400
PWBLACK-05-100R2	5/16"	350
PWBLACK-06-100R2	3/8"	330
Tech Sheet 3105		

2 Wire, Cut to Length, per Metre


1369	ID	Max Pressure Bar
2144-9715	1/4"	400
2144-9723	5/16"	350
2144-9731	3/8"	330
Tech Sheet 3105		

Fluid-Air Components Ltd

Blue Cold Water Pressure Wash Hose



Working Temperature:
-40°C to +100°C



1 Wire, 50 Metre Coils

0303	ID	Max Pressure Bar
CWBLUE04-50-R1	1/4"	190
CWBLUE05-50-R1	5/16"	175
CWBLUE06-50-R1	3/8"	157
Tech Sheet 10262		

1 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
CWBLUE04-25-R1	1/4"	190
CWBLUE05-25-R1	5/16"	175
CWBLUE06-25-R1	3/8"	157
Tech Sheet 10262		

2 Wire, 50 Metre Coils

0303	ID	Max Pressure Bar
CWBLUE04-50-R2	1/4"	350
CWBLUE05-50-R2	5/16"	297
CWBLUE06-50-R2	3/8"	280
Tech Sheet 10262		

2 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
CWBLUE04-25-R2	1/4"	350
CWBLUE05-25-R2	5/16"	297
CWBLUE06-25-R2	3/8"	280
Tech Sheet 10262		

Black Cold Water Pressure Wash Hose



Working Temperature:
-40°C to +100°C



1 Wire, 50 Metre Coils

0303	ID	Max Pressure Bar
CWBLACK04-50-R1	1/4"	190
CWBLACK05-50-R1	5/16"	175
CWBLACK06-50-R1	3/8"	157
Tech Sheet 10262		

1 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
CWBLACK04-25-R1	1/4"	190
CWBLACK05-25-R1	5/16"	175
CWBLACK06-25-R1	3/8"	157
Tech Sheet 10262		

2 Wire, 50 Metre Coils

0303	ID	Max Pressure Bar
CWBLACK04-50-R2	1/4"	350
CWBLACK05-50-R2	5/16"	297
CWBLACK06-50-R2	3/8"	280
Tech Sheet 10262		

2 Wire, 25 Metre Coils

0303	ID	Max Pressure Bar
CWBLACK04-25-R2	1/4"	350
CWBLACK05-25-R2	5/16"	297
CWBLACK06-25-R2	3/8"	280
Tech Sheet 10262		

Fluid-Air Components Ltd

WASH DOWN EQUIPMENT

Pressure Washer Hose Assemblies

- Oil and water resistant synthetic pin-pricked rubber.
- Special high temperature synthetic rubber cover.
- Blue suitable where non marking hose is required.
- Black suitable to handle pressure washer service.



1 Wire Braid 3/8" ID, 10 Metre Hose, 3/8" BSPP Male x Female

1369	ID	Max Pressure Bar	Colour
1PWLA-M-F-38N	3/8"	180	Black

1 Wire Braid 1/4" ID, 10 Metre Hose, 1/4" BSPP Female

1369	ID	Max Pressure Bar	Colour
1PWLA-14N	1/4"	225	Black

1 Wire Braid 3/8" ID, 10 Metre Hose, 3/8" BSPP Female

1369	ID	Max Pressure Bar	Colour
1PWLA-38B	3/8"	180	Blue
1PWLA-38N	3/8"	180	Black



2 Wire Braid 3/8" ID, 10 Metre Hose, 3/8" BSPP Female

1369	ID	Max Pressure Bar	Colour
2PWLA-38B	3/8"	330	Blue
2PWLA-38N	3/8"	330	Black

2 Wire Braid 3/8" ID, 10 Metre Hose, M22 x 1.5 x M22 x 1.5

1369	ID	Max Pressure Bar	Colour
2PWLA-K-K-38B	3/8"	330	Blue
2PWLA-K-K-38N	3/8"	330	Black

2 Wire Braid 3/8" ID, 10 Metre Hose, M22 x 1.5 x 3/8" BSPP Female

1369	ID	Max Pressure Bar	Colour
2PWLA-K-F-38B	3/8"	330	Blue
2PWLA-K-F-38N	3/8"	330	Black

2 Wire Braid 3/8" ID, 10 Metre Hose, M22 x 1.5 x 3/8" BSPP Male

1369	ID	Max Pressure Bar	Colour
2PWLA-K-M-38B	3/8"	330	Blue
2PWLA-K-M-38N	3/8"	330	Black

Bend Restrictor Assembly



Brass M22 x 1.5 Female, with Steel Tail & Ferrule

0300	To Suit Hose ID
M22-CUFF-4	1/4"
M22-CUFF-5	5/16"
M22-CUFF-6	3/8"

Jet Wash Female Hose Couplings




M22 x 1.5 Female Thread

0300	To Suit Hose ID
JWF-22-04	1/4"
JWF-22-05	5/16"
JWF-22-06	3/8"

Stainless Steel, M22 x 1.5 Female Thread

0044	To Suit Hose ID
DKO-KA-DN06	1/4"
DKO-KA-DN08	5/16"
DKO-KA-DN10	3/8"
DKO-KA-DN12	1/2"
Tech Sheet 60627	

End Cuff



Suitable for 1 & 2 Wire

0303	Colour	To Suit Hose ID
1/4-BLUE-CUFF	Blue	1/4"
1/4-BLACK-CUFF	Black	1/4"
3/8-BLUE-CUFF	Blue	3/8"
3/8-BLACK-CUFF	Black	3/8"

Jet Wash Male Hose Couplings



Male Adaptor

0300	To Suit Hose ID
JWM-04	1/4"
JWM-05	5/16"
JWM-06	3/8"

Fluid-Air Components Ltd

SPRAY GUNS & ACCESSORIES

Spray Guns

9 spray patterns. Supplied with 1/2" quick connect male to 3/4" BSPP connector.



Spray Lance

0399	Size mm
TOOL-371756	770



Metal Spray Gun

0399
KA-03-94-76



Metal 6 Function Spray Gun

0399
KA-03-94-79

Metal Soft Rain Lance



0399	Length mm
KA-15-20-00	600
KA-15-20-09	900
KA-15-20-12	1200

Water Guns



TOTAL

Water Gun

1369
THWS010901

Roses



Large Alloy Rose, BSPP

0399	Thread
KA-15-00-07F	3/4"

Water Nozzles



Brass Jet Nozzles

0399	ID
BJN12	1/2"
BJN34	3/4"
BJN1	1"

Spray Gun Display Packs

Display box of 50 plastic 1/2" male to 1/2" male quick connectors.



1/2" 2 Way Connector

0399	Quantity
TOOL-656601	50

5 piece plastic hose fitting set 1 x 1/2" quick connect without water stop, 3/4" BSP tap connector and 100mm spray nozzle with infinite spray pattern.



4 Piece Hose Connector Set

0399
TOOL-394989

Spray Gun Accessories

Solid brass 1/2" quick connect male to 3/4" BSPP.



Brass Internal Adaptor

0399
TOOL-244973

Solid brass 3/4" BSPP-1/2" quick connect male. 3/4" BSPP fits 1/2" outside tap.



Brass Tap Connector

0399
TOOL-598438

Solid brass 1/2" quick connect female to 1/2" compression. Auto stop.



Brass Quick Connector with Auto Stop

0399
TOOL-196506

Solid brass 1/2" quick connect female to 1/2" compression without auto stop.



Brass Quick Connector without Auto Stop

0399
TOOL-868573

Solid brass 100mm spray nozzle, 2 x 1/2" quick connectors with water stop. 3/4" BSP tap adaptor fits 1/2" outdoor tap. Infinite spray patterns.



Brass Fitting Set

0399
TOOL-793753

Fluid-Air Components Ltd

SPRINKLERS

Sprinklers

Unique lower pressure sprinkler featuring butterfly type rotating spinner and rotary frame which provides even water distribution.



Pope Rotoframe Sprinkler, BSPP

0399	Thread	OD mm
KA-59-00-10	1/2"	4.5

Part circle brass sprinkler with fingertip adjustment for watering full 26m circle or any part of it. Baffle deflector controls height of jet and diameter of circle. Diffuser pin adjusts from heavy to fine stream.



Part Circle Metal Sprinkler, BSPP

0399	Thread	OD mm
KA-60-04-23-40	1/2"	4

Heavy-duty metal construction. Large part circle sprinkler with stainless steel springs and axle. Easy fingertip adjustment to any part of circle. 28m coverage.



Large Part Circle Metal Sprinkler, BSPP

0399	Thread	OD mm
KA-62-33-00	3/4"	3.9

Impulse sprinkler covers 360° diameter with full of half circle adjustable pattern. 1/2" quick connector. Daisy-chain facility.



Spike Sprinkler

0399	Type
TOOL-868552	1/2" Quick Connector

Sprinkler Stands

Made from coated steel complete with riser. Supplied complete with a quick coupling to connect to any Geka type fitting.



Metal Sled Base, BSPP

0399	Height mm	Thread
KA-68-25-05	300	1/2"

Porous Pipe

Used for various irrigation purposes. It should be used at pressures between 4-12 psi. The maximum run length is 50 metres and the output is 4 litres per hour per metre.



0399	Description
KA-92-10-30	30m Retail Pack Porous Pipe complete with 16mm Fittings
KA-92-15-50	50m Roll Porous Pipe

Fluid-Air Components Ltd

PRESSURE SPRAY EQUIPMENT

MESTO

Pressure Sprayers

Mesto is a European market leading manufacturer of professional cleaning equipment and has been providing innovation for the industry since 1919.

Product description:
- Tank: Plastic, with filling scal
- Seals: FPM
- Nozzle: Plastic, adjustable

Applications:
- Construction work
- Cleaning industry
- Professional pest control
- Handicraft

Special features of the product:
- Safety valve



Maximum Working Temperature:
+30°C

Maximum Working Pressure:
3 bar

UNIVERSAL PLUS, Hand Pump Sprayer

0465	Capacity Litres	Material
3132PG	1.5	Polyethylene
	Tech Sheet 60139	

Product description:
- Tank: Plastic with filling scal
- Seals FPM (Viton®)
- Nozzle: Plastic, adjustable
- Plastic jacket wand to protect the non-return valve

Applications:
- Foaming cleaning industry

Special features of the product:
- Safety valve
- Specially coated spring



Maximum Working Temperature:
+30°C

Maximum Working Pressure:
3 bar

FOAMER, Heavy-duty Hand Pump

0465	Capacity Litres	Material
3132FO	1.5	Polyethylene
	Tech Sheet 60140	











Large selection of models for various application are available on request.

BEFORE USE, CHECK CAREFULLY WHETHER THE MATERIAL IS RESISTANT TO THE LIQUID BEING USED.

Fluid-Air Components Ltd

PRESSURE SPRAY EQUIPMENT

MESTO

Compression Sprayers

Mesto is a European market leading manufacturer of professional cleaning equipment and has been providing innovation for the industry since 1919.

Device description:
- Tank: Plastic with large pressure reservoir
- Carried at the side
- Seals: FPM (Viton®)
- Nozzle: adjustable plastic nozzle
- Spray wand: Plastic, 48 cm, 360° rotatable
- Hose: 2.0 m, transparent oil resistant

Applications:
- Construction work
- Cleaning industry

Maximum Working Temperature: +30°C

Maximum Working Pressure: 3 bar

Special features of the product:
- Professional pump
- Integrated dirt filte



FIX PLUS, Professional

0465	Capacity Litres	Material
3237FM	5	Polyethylene
	Tech Sheet 60141	

Device description:
- Tank: Plastic, with large pressure reservoir
- Carried at the side
- Seals: FPM (Viton®)
- Nozzle: Plastic flat jet nozzl
- Spray wand: Plastic 48 cm, 360° rotatable
- Hose: 2.0 m
- Ergonomically formed shut-off valve with fine filt

Applications:
- Cleaning industry
- Vehicle cleaning
- Disinfection
- Corrosion protection
- Impregnation

Maximum Working Temperature: +40°C

Maximum Working Pressure: 3 bar

Special features of the product:
- Professional pump with specially coated piston rod
- Large filling funne
- With specially coated spring



CLEANER, Heavy-duty

0465	Capacity Litres	Material
3270PP	10	Polyethylene
	Tech Sheet 60142	

Device description:
- Tank: Stainless steel
- Carried on the back – padded carrying straps
- Seals: FPM (Viton®)
- Nozzle: Brass flat jet nozzle with fine filt
- Spray wand: Brass 50cm, 360° rotatable
- Hose: Spiral hose 2.5 m with safety interlock

Applications:
- Construction work
- Cleaning industry
- Professional pest control

Maximum Working Temperature: +50°C

Maximum Working Pressure: 6 bar

Special features of the product:
- Safety valve and pressure gauge are exchangeable
- Spare parts compartment on the device
- Pump holder
- Spray and extension wand bracket
- Funnel cover



INOX PLUS, Stainless Steel

0465	Capacity Litres	Material
3615P	10	Stainless Steel
	Tech Sheet 60143	

Applications:
- General purpose
- Gardening
- Horticulture
- Domestic cleaning
- Integrated safety valve and strap

Maximum Working Temperature: +30°C

Maximum Working Pressure: 3 bar



GARANT, General Purpose

0465	Capacity Litres	Material
3195E	5	Polyethylene
	Tech Sheet 60144	

Large selection of models for various application are available on request.

BEFORE USE, CHECK CAREFULLY WHETHER THE MATERIAL IS RESISTANT TO THE LIQUID BEING USED.

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PRESSURE SPRAYERS

Manual



5 Litre Pressure Sprayer

0088
TOOL-675108



8 Litre Pressure Sprayer

0088
TOOL-868593



10 Litre Pressure Sprayer

0088
TOOL-630070



20 Litre Backpack

0088
TOOL-633595

COMMERCIAL & DOMESTIC VEHICLE CLEANING EQUIPMENT

Vehicle Brushes

The shape design gives more cleaning productivity, as the brush is in constant contact with the surface, when used as either a waterfed or a dip brush.



Hi-Lo Waterfed Brush

0143	Description
VIK-524752	Rubber Edged

Effective all surface water-fed bodywork brush for large areas, up to 3 metres in height.



Bodywork Brushes

0143	Width mm	Description
VIK-475552	250	Rubber Edged
VIK-475752	400	-

Brush for cleaning wheel rims on trucks and buses.



Wheel Brush

0143	Width mm
VIK-545252	230



Hand Waterfed Brushes

0143	Length mm
VIK-525452	350

Vehicle Brush Handles

Handles to suit all vehicle brushes.




Vehicle Brush Handles

0143	Length Metres	Description
VIK-299152	1.5	Waterfed Handle
VIK-297352	1.5-2.75	Telescopic Waterfed Handle
VIK-297552	1.5-2.75	Telescopic Handle

Cleaning Brushes

- Features on/off water control and quick connect attachment.
- Ideal for cleaning vehicles, boats, paintwork and conservatories.



Telescopic Car Cleaning Brush

0088	Length mm
TOOL-719788	1070-1760

Fluid-Air Components Ltd

PUMPS & PROCESS EQUIPMENT

Air Operated Double Diaphragm Pumps

Typical Applications:
- OEMs
- Printing
- Wastewater
- Plating/surface finishin

Typical Fluids Handled:
- Waterborne materials, some HHC's
- Paints, coatings, inks and dyes
- Car wash chemicals
- Laundry chemicals and detergents
- Chemicals

Features:
- 1/4" (6.35 mm) end-porting
- Low-cost, compact design
- Spring check valves for superior priming in any mounting configuratio
- True-formed PTFE and Santoprene diaphragms for enhanced performance
- Can also be remotely-controlled using an external controller
- Delivery up to 5 gpm (18.93 L/min)



Husky 205, BSPP

0074	Body	Balls	Diaphragms
D11021	Acetal	Acetal	PTFE
D12096	Polypropylene	Polypropylene	Santoprene

Typical Applications:
- Drum transfer for fluids up to 1000 centipoise
- Circulation of low viscosity inks, stains and dyes
- Coolant circulation and evacuation
- Waste fluid remova
- On-demand batch chemical metering
- Low viscosity adhesive supply
- Consistent low pressure air spray or HVLP supply

Typical Fluids Handled:
- Paints
- Lubricants
- Inks
- Stains
- Solvents
- Coatings
- Dyes

Features:
- 3/8" (9.52 mm) end porting
- Fully-groundable acetal model
- Operates on as little as 20 psi (1.4 bar, 0.14 MPa) air pressure
- Delivery up to 7 gpm (26.5 L/min)
- Easy-to-service air valve and ball checks
- Quiet operation – 75 dBa at 50 psi (3.5 bar, 0.35 MPa) and 60 cpm



Husky 307, BSPP

0074	Body	Seats	Balls	Diaphragms
D3A211	Acetal	Acetal	PTFE	PTFE
D3B911	Polypropylene	Polypropylene	PTFE	PTFE
D3B955	Polypropylene	Polypropylene	Hytrel	Hytrel
D3A255	Acetal	Acetal	Hytrel	Hytrel

Typical Applications:
- Machine lube servicing
- Drum evacuation
- Plating and dip tanks
- Water treatment

Typical Fluids Handled:
- Cleaning fluids and detergent
- Chemicals
- Ceramic glazes
- Inks
- Solvents and flammable
- Acids and bases

Features:
- 1/2" (12.7 mm) centre-porting and 3/4 in. (19.05 mm) end-porting
- Quiet running – less than 85 dBa with easy-to-use remote muffler capability for even lower noise levels
- No seals to leak or fail
- High flow rates in a small, portable packag
- Can also be remotely-controlled using an external controller
- Delivery up to 15 gpm (56.88 L/min)



Husky 515, BSPP

0074	Body	Seats	Balls	Diaphragms
D5B911	Polypropylene	Polypropylene	PTFE	PTFE
D5A211	Acetal	Acetal	PTFE	PTFE
D5A277	Acetal	Acetal	Buna	Buna
		Tech Sheet 10288		

Typical Applications:
- Machine lube servicing
- Cleaning fluids and detergent
- Plating and dip tanks
- Water treatment

Typical Fluids Handled:
- Oil
- Water
- Most solvents

Features:
- 3/4" (19.05 mm) centre and end-porting
- Quiet running – less than 85 dBa with easy-to-use remote muffler capability for even lower noise levels
- High flow rates in a small, portable packag
- No seals to leak or fail
- Can also be remotely-controlled using an external controller
- Delivery up to 16 gpm (60.87 L/min)



Husky 716, BSPP

0074	Body	Seats	Balls	Diaphragms
D5C277	Aluminium	Acetal	Buna-N	Buna-N
D5D311	Stainless	Stainless	PTFE	PTFE
		Tech Sheet 10288		

Fluid-Air Components Ltd

Air Operated Double Diaphragm Pumps

Typical Applications:
- Drum fluid transfe
- Unloading fluid
- Bilge pumping
- Chemical evacuation
- Dewatering and sump evacuation
- Tank and sump drainage

Typical Fluids Handled:
- Chemicals
- Contaminated surface water
- Adhesives, varnishes, dispersions, solvents and stains
- Resins, latexes, wood preservative stains, concrete and primers

Features:
- 1" (25.4 mm) ANSI end-porting
- High flow – 50 gpm (189 L/min) in a compact, portable size
- Fluid pressure to 120 psi (8.6 bar, 0.86 MPa)
- E-coated centre section for corrosive environments
- Equipped with an effective and reliable air valve system
- Can also be remotely-controlled using an external controller



Husky 1050, BSPP

0074	Body	Seats	Balls	Diaphragms
647121	Aluminium	Geolast	Geolast	Geolast
647109	Aluminium	Stainless	PTFE	PTFE

Typical Applications:
- Filter press
- Tank stripping
- Bilge pumping
- Sand and ball mill pumping
- Oil transfer and oil skimming
- Chemical plating

Typical Fluids Handled:
- Latex
- Corrosive fluid
- Acids: hydrochloric, ferric, sulfuric, nitric and phosphoric
- Slurries: petroleum, lime, clay, ferrite, salt/brine and pumice
- Sludge: secondary and clarifie
- Pottery slip

Features:
- 1.1/2" (38.1 mm) ANSI end-porting
- High flow – 100 gpm (378 L/min) in a compact, portable size
- Fluid pressure to 120 psi (8.4 bar, 0.84 MPa)
- Lube-free operation
- Patented, high-reliability "closed centre" air valve is "online" serviceable
- Epoxy-coated air section for tough environmental conditions
- Can also be remotely-controlled using an external controller



Husky 1590, BSPP

0074	Body	Seats	Balls	Diaphragms
DBCGGG	Aluminium	Geolast	Geolast	Geolast
DBD311	Stainless	Stainless	PTFE	PTFE
DB2911	Polypropylene	Polypropylene	PTFE	PTFE

Typical Applications:
- Drum fluid transfe
- Bulk fluid suppl
- Chemical evacuation
- Ground water and sump evacuation
- Waste fluid remova
- Tank and bilge drainage
- Slurry and sludge transfer
- Filter press feed

Typical Fluids Handled:
- Acids, alkalies, solvents, suspensions, dispersions, electroplating baths, paints, varnishes, resins, latex, adhesives, effluent sludge and stabiliser
- Ship cleaning and stripping chemicals

Features:
- 2" (50.8 mm) ANSI end-porting
- Larger ports for more flow – up to 150 gpm (568 L/min)
- Fluid pressure to 120 psi (8.4 bar, 0.84 MPa)
- Lube-free operation
- Patented, high-reliability "closed centre" air valve is "online" serviceable
- Epoxy-coated air section for tough environmental conditions
- Can also be remotely-controlled using an external controller



Husky 2150, BSPP

0074	Body	Seats	Balls	Diaphragms
DFCGGG	Aluminium	Geolast	Geolast	Geolast
DFC666	Aluminium	Santoprene	Santoprene	Santoprene
DF2911	Polypropylene	Polypropylene	PTFE	PTFE

Typical Applications:
- Chemical transfers
- Filter press-feed
- Dewatering

Typical Fluids Handled
- Chemicals
- Bulk paint resins
- Ceramic slip

Features:
- 3" (76.2 mm) ANSI centre porting
- Bolted leak-free flanged connections – no clamp bands used
- Easy air valve maintenance
- Large flow paths can handle high viscosities
- Heavy-duty construction
- Fluid flow up to 275 gpm (1040 L/min



Husky 3275, BSPP

0074	Body	Seats	Balls	Diaphragms
652021	Aluminium	Stainless	PTFE	PTFE

MISTING SYSTEMS

Fogco Environmental is a recognised industry leading manufacturer of high quality misting equipment for residential, commercial and industrial markets.



Pump Kits

See page 1687



Pumps

See page 1689



Fans

See page 1690



Air Injection Dry Fog System

See page 1691



Slip Lok Push-in Fittings

See page 1692



Nozzles

See page 1693



Adaptors

See page 1694



Filters

See page 1695



Controllers

See page 1696

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

MISTING SYSTEMS - PUMP KITS

Direct Drive Kit

This kit range includes a 1,000 psi Fogco direct drive misting pump with either a flexible nylon, pre-fabricated copper or stainless steel tubing mist line, a filter assembly with water supply connections, plus all of the necessary fittings and components to complete a mist system installation for the listed lengths. These Fogco misting kits include a direct drive 230V mist pump and a standard brass and stainless steel misting nozzle with 24" spacing.






Key:
LPM: Litres per minute
HP: Horse power
FLA: Full load amperage


With Nylon Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Direct Pump Ref. no
				LPM	HP	FLA	
8N20215	20	10	0.76	0.8	1	7.1	8100215
8N30215	30	15	1.14	1.6	1	7.1	8200215
8N40215	40	20	1.52	1.6	1	7.1	8200215
8N50215	50	25	1.9	3.5	1	7.1	8300215
8N60215	60	30	2.28	3.5	1	7.1	8300215
8N70215	70	35	2.66	3.5	1	7.1	8300215
8N80215	80	40	3.04	3.5	1	7.1	8300215
8N90215	90	45	3.42	3.5	1	7.1	8300215



With Copper Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Direct Pump Ref. no
				LPM	HP	FLA	
8C20215	20	10	0.76	0.8	1	7.1	8100215
8C30215	30	15	1.14	1.6	1	7.1	8200215
8C40215	40	20	1.52	1.6	1	7.1	8200215
8C50215	50	25	1.9	3.5	1	7.1	8300215
8C60215	60	30	2.28	3.5	1	7.1	8300215
8C70215	70	35	2.66	3.5	1	7.1	8300215
8C80215	80	40	3.04	3.5	1	7.1	8300215
8C90215	90	45	3.42	3.5	1	7.1	8300215



With Stainless Steel Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Direct Pump Ref. no
				LPM	HP	FLA	
8S20215	20	10	0.76	0.8	1	7.1	8100215
8S30215	30	15	1.14	1.6	1	7.1	8200215
8S40215	40	20	1.52	1.6	1	7.1	8200215
8S50215	50	25	1.9	3.5	1	7.1	8300215
8S60215	60	30	2.28	3.5	1	7.1	8300215
8S70215	70	35	2.66	3.5	1	7.1	8300215
8S80215	80	40	3.04	3.5	1	7.1	8300215
8S90215	90	45	3.42	3.5	1	7.1	8300215



Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

MISTING SYSTEMS - PUMP KITS

Pulley Drive Kit


This kit range includes a 1,000 psi Fogco pulley drive misting pump with either a flexible nylon, copper or stainless steel tubing mist line, a filter assembly with water supply connections, plus all of the necessary fittings and components to complete a mist system installation for the listed lengths. These Fogco misting kits include our pulley drive 230V mist pump and our standard brass and stainless steel misting nozzle with 24" spacing.



Key:
LPM: Litres per minute
HP: Horse power
FLA: Full load amperage


With Nylon Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Pulley Pump Ref. no
				LPM	HP	FLA	
7N20215	20	10	0.76	1	1	7.1	7100215
7N30215	30	15	1.14	2	1	7.1	7200215
7N40215	40	20	1.52	2	1	7.1	7200215
7N50215	50	25	1.9	4	1	7.1	7400215
7N60215	60	30	2.28	4	1	7.1	7400215
7N70215	70	35	2.66	4	1	7.1	7400215
7N80215	80	40	3.04	4	1	7.1	7400215
7N90215	90	45	3.42	4	1	7.1	7400215



With Copper Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Pulley Pump Ref. no
				LPM	HP	FLA	
7C20215	20	10	0.76	1	1	7.1	7100215
7C30215	30	15	1.14	2	1	7.1	7200215
7C40215	40	20	1.52	4	1	7.1	7200215
7C50215	50	25	1.9	4	1	7.1	7400215
7C60215	60	30	2.28	4	1	7.1	7400215
7C70215	70	35	2.66	4	1	7.1	7400215
7C80215	80	40	3.04	4	1	7.1	7400215
7C90215	90	45	3.42	4	1	7.1	7400215



With Stainless Steel Tube

9583	Tube Length Feet	No. of Nozzles	Total LPM	Pump Specification			Pulley Pump Ref. no
				LPM	HP	FLA	
7S20215	20	10	0.76	1	1	7.1	7100215
7S30215	30	15	1.14	2	1	7.1	7200215
7S40215	40	20	1.52	4	1	7.1	7200215
7S50215	50	25	1.9	4	1	7.1	7400215
7S60215	60	30	2.28	4	1	7.1	7400215
7S70215	70	35	2.66	4	1	7.1	7400215
7S80215	80	40	3.04	4	1	7.1	7400215
7S90215	90	45	3.42	4	1	7.1	7400215



Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

Fluid-Air Components Ltd

MISTING SYSTEMS - PUMP KITS

FOGCO

Direct Drive Pump

The 50Hz direct drive mist pump range are medium duty outdoor rated units, designed to operate at 70 bar for 8 hours per day, seven days a week under normal operating conditions. This range is ideal for light to medium duty mist applications. These pumps provide quality components in a small and convenient platform.

This mist pump range is available in 230V and includes:

- Direct drive pump
- On/off switch
- Inlet solenoid
- Adjustable regulator with bypass thermal relief valve
- Glycerine filled pressure gaug
- Rubber isolation feet
- Filter assembly



Key:
LPM: Litres per minute
HP: Horse power
FLA: Full load amperage

230V/50Hz


9583	Description			Weight Kg	Dimensions cm		
	LPM	HP	FLA		L	W	H
8100215	0.8	1	7.1	27.7	59.7	31.8	26.7
8200215	1.6	1	7.1	27.7	59.7	31.8	26.7
8300215	3.5	1	7.1	27.7	58.4	31.8	26.7
8400215	4.4	1	7.1	27.7	58.4	31.8	26.7
8700215	6.6	1.5	11.3	29.9	58.4	37.8	26.7

Pulley Driven Pump

The 50Hz pulley drive mist pumps are industrial duty outdoor rated units, designed to operate at 70 bar for 24/7 use, under normal operating conditions. This range is ideal for industrial and commercial applications that includes UL compliant thermal and short circuit protection, as well as a low water pressure cut-off switch.

This mist pump range is available in 230V and includes:

- Pulley drive pump
- Exhaust fan
- Panel mount switch
- Inlet solenoid
- Adjustable regulator with bypass thermal relief valve
- Hour meter
- Glycerine filled pressure gaug
- Rubber isolation feet
- Filter assembly



Key:
LPM: Litres per minute
HP: Horse power
FLA: Full load amperage
RPM: Revs per minute

230V/50Hz

9583	Description				Weight Kg	Dimensions cm		
	LPM	HP	FLA	RPM		L	W	H
7100215	1	1	7.1	770	49.9	66.0	30.5	40.6
7200215	2	1	7.1	598	49.9	66.0	30.5	40.6
7400215	4	1	7.1	486	49.9	66.0	30.5	40.6
7800215	8	1.5	11.3	973	53.5	66.0	30.5	40.6
7120215	12	3	13	1450	59.0	66.0	30.5	40.6

DIRECT DELIVERY

Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MISTING SYSTEMS - FANS

FOGCO

Revolution

The **Revolution** misting fan provides improved evaporative cooling and humidification, compared to traditional misting fans. Its unique design allows a more uniformed distribution of the fog and improved absorption of the moisture.

By integrating a focused horizontal air stream into the fog, the water droplets can cover more surface area. This allows the mist system to cool or humidify up to 5 times the amount of air, compared to static line misting systems. This mist fan can cover up to 3,600 sq.ft. or 36,000 cu.ft.

This misting fan is available in 230V and uses 0.8 amps. The unit includes a stainless steel fog ring with 10 nozzle fittings



230V Ceiling Mount Fan

9583	Fan Specification		Weight Kg	Dimensions cm		
	HP	FLA		L	W	H
93820	0.25	0.9	18.1	61.0	61.0	25.4

Revolution II

The **Revolution II** misting fan is a smaller version of the **Revolution** and provides improved evaporative cooling and humidification.
Its unique design allows a more uniformed distribution of the fog and improved absorption of the moisture.

Similar to the **Revolution**, integrating a focused horizontal air stream into the fog, the water droplets can cover more surface area. This allows the mist system to cool or humidify up to 5 times the amount of air compared to static line misting systems. This mist fan can cover up to 900 sq.ft. or 9,000 cu.ft.

This misting fan provides 250 cfm and is available in 230V and uses 0.12 amps. The unit includes 10ft of 18 gauge insulated power cord, 10ft of flexible high pressure feed line and a rustproof treated and powder coated housing with a 6 nozzle stainless steel fog ring. Custom fog rings are also available.



Ceiling Mount Fan

9583	Fan Specification		Weight Kg	Dimensions cm		
	HP	FLA		L	W	H
94820	0.25	0.12	2.0	30.5	30.5	8.9



Evolution Mini

The **Evolution Mini** does not include the cannon shaped housing, so it requires a shorter distance for the absorption of the fog compared to the projection that is capable with the standard **Evolution**.

Because of this characteristic, the **Evolution Mini** is well suited for low ceilings and restricted or confined applications. Due to the reduced noise level and low profile design, this fan can be used in an office or warehouse environment

The **Evolution Mini** uses a single misting nozzle but multiple nozzle configurations are also available, if increased moisture is required.

The **Evolution Mini** requires a 6 Watt 12V DC power supply. Once the unit is wall mounted, with the provided bracket, it can be adjusted both horizontally and vertically.

The power supply includes a DIN rail and is designed to be mounted in a cabinet or enclosure.



12V DC Wall Mount Fan

9583	Weight Kg	Dimensions cm		
		L	W	H
93000-12VDC	2.7	24.1	20.3	20.3

Key:
HP : Horse power
FLA : Full load amperage

DIRECT DELIVERY

Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

MISTING SYSTEMS - AIR INJECTION DRY FOG SYSTEM

The Fogco Air Injection Dry Fog System utilises the proprietary control box, capable of producing over 150 lbs of dry fog per hour. It includes the FOGCOntroller II microprocessor.

The box allows on-site adjustments to the system performance and output. The Drip Free air injection nozzles prevent dripping when the system shuts down and to prevent the water supply from running if there is a loss of air pressure.

The air injection nozzles are capable of producing flow rates from 8 lbs/hr to 16 lbs/hr while providing droplets as small as 1 micron and achieving humidity levels up to 99%.

The Fogco Air Injection System requires the availability of compressed air of at least 80 psi and 25 cfm and water pressure of 60 psi to produce the maximum output of 150 lbs/hr.

The system utilises directionally adjustable dry fog nozzles on a magnetic base or hung using an 3/8" mount.



Air Injection Control Box



Includes FOGCOntroller II Microprocessor

9583	Weight Kg	Dimensions cm L	W	H
96100	13.6	30.5	30.5	25.4

Drip Free Adjustable Air Nozzle



With All-Thread Mount

9583	Flow
96081	8lbs/hr - 16lbs/hr



With Magnetic Base

9583	Flow
96080	8lbs/hr - 16lbs/hr

FO-500 ULTRA-LOW VOLUME FOGGER

- Disinfection
- Pest Control
- Odour Control
- Plant Protection



ULV Fogger 240V

9584
FO-500

Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

Fluid-Air Components Ltd

MISTING SYSTEMS - AIR INJECTION DRY FOG SYSTEM

FOGCO

The Fogco line of industrial Slip Lok fittings are rated at 1,500 psi and have been used successfully in industrial applications for over 20 years.

The fittings include a heavy-duty bod , thicker locking ferrule and an over sized viton o-ring. Their unique design allows them to be easily removed, replaced or re-installed anytime after the initial installation. No special tools or crimping procedures are required.

- Standard threads are 10/24 UNC.



Male Stud



Male Thread, NPT x Tube

9583	Tube OD	Thread
94853	1/4"	1/4"
92707	3/8"	3/8"

Mistscaping Adaptor



Tube x UNC

9583	Tube OD	Thread
92923	3/8"	10/24

Equal Elbow



Tube x Tube

9583	Tube OD
92703	3/8"

Mistscaping Equal Joiner



Tube x UNC

9583	Tube OD	Thread
94630	1/4"	10/24
92630	3/8"	10/24

Joiners



Tube x Tube

9583	Tube OD
92702	3/8"

Equal Cross



Tube x Tube

9583	Tube OD
92711	3/8"

End Plug



Tube

9583	Material	Tube OD
94706	Plastic	1/4"
92706	Brass	3/8"

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MISTING SYSTEMS - ADAPTORS

FOGCO

Standard Mist Nozzle

These misting nozzles are available in brass with stainless steel orifices.
The sizes range from 0.008" to 0.020" with flow rates from 0.020 gpm to 0.055 gpm

- Spray patterns vary from 60° to 90°.
- Standard threads are 10/24 UNC.
- All stainless steel and 12/24 UNC are available on request.






Brass

9583	Orifice Size Inches	LPM	Spray Pattern	O-Ring Colour	Weight g	Dimensions cm L	W	H
93508	0.008	0.76	60°	Red	9.1	2.5	1.0	1.0
93512	0.012	0.110	70°	Black	9.1	2.5	1.0	1.0
80450	0.016	0.167	80°	Brown	9.1	2.5	1.0	1.0
93520	0.020	0.208	90°	Green	9.1	2.5	1.0	1.0

Cleanable Anti-drip Nozzle

All cleanable misting nozzles include an anti-drip adaptor. This range is available in brass with a stainless steel orifice or all stainless steel design.
The sizes range from 0.006" to 0.020" with flow rate from 0.01 gpm to 0.045 gpm.

- Spray patterns from 45° to 85°.
- Larger orifice sizes and different threads are also available as special order items.
- Standard threads are 10/24 UNC.
- All stainless steel and 12/24 UNC are available on request.





Brass

9583	Orifice Size Inches	LPM	Spray Pattern	O-Ring Colour	Weight g	Dimensions cm L	W	H
95031	0.006	0.037	45°	Yellow	9.1	2.5	1.0	1.0
95037	0.008	0.060	55°	Red	9.1	2.5	1.0	1.0
95038	0.012	0.095	65°	Black	9.1	2.5	1.0	1.0
95039	0.016	0.136	75°	Brown	9.1	2.5	1.0	1.0
95040	0.020	0.170	85°	Green	9.1	2.5	1.0	1.0

Stainless Steel

9583	Orifice Size Inches	LPM	Spray Pattern	O-Ring Colour	Weight g	Dimensions cm L	W	H
95032	0.006	0.037	45°	Brown	9.1	2.5	1.0	1.0
95033	0.008	0.060	55°	Brown	9.1	2.5	1.0	1.0
95034	0.012	0.095	65°	Brown	9.1	2.5	1.0	1.0
95035	0.016	0.136	75°	Brown	9.1	2.5	1.0	1.0
95036	0.020	0.170	85°	Brown	9.1	2.5	1.0	1.0

PORTWEST

For **Knee Protection**
...see page **1759**



Fluid-Air Components Ltd

MISTING SYSTEMS - ADAPTORS

FOGCO

The nozzle adaptor range includes extensions, clusters and adaptors to provide more options in the designing and installation of a mist system.
Clusters allow 3 or 5 nozzles to be placed in a single nozzle fitting
Extensions allow the fog to be directed in a specific wa , while extending the fog up to 12 inches from the line.

Nozzle Extensions



Stainless Steel, UNC

9583	Nozzle Length Inches	Male Thread	Female Thread
94506	6	10/24	10/24
94512	12	10/24	10/24

Nozzle Cluster



Stainless Steel, UNC

9583	Male Thread	Female Thread
93019	10/24	5 x 10/24

Nozzle Swivel Adaptor



Nickel-plated, UNC

9583	Male Thread	Female Thread
95041	10/24	10/24

Nozzle Adaptor



Brass

9583	Male Thread	Female Thread
92519	1/8" NPT	10/24 UNC

Nozzle Plug



Brass, UNC

9583	Male Thread
93505	10/24

Nozzle Removal Tool



Plastic

9583
92100

Nozzle O-Rings



Plastic

9583	Material
10252	Nitrile
93598	Viton

Replacement Spring



For Cleanable Anti-drip Nozzle

9583
92788

Replacement Stemmed Ball



For Cleanable Anti-drip Nozzle

9583
93354

PORTWEST








For **Eye Protection**
...see page **1754**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MISTING SYSTEMS - FILTERS

FOGCO

Filtration is highly recommended for every mist system. Fogco offer a full range of filter cartridges and housing. From their smallest 'hose end' calcium inhibitor filter to the larger 10" filter housing with varying micron cartridges

Fogco's filter range also includes a special phosphate cartridge for the 10" filter housing. This cartridge helps eliminate the adverse effects of calcium and dissolved solids present in the water supply.

For very high flow rates, Fogco offers an increased capacity filtration option that includes a larger housin and a dual stage cartridge. This filter housing include 1" ports for maximum flo .

Water Pretreatment Kit



With Cartridges

9583	Type
93613	Polyphosphate
93614	Scalex

10" Dual Filter Cartridge



For 92611

9583	Pre-filter Micron µm	Filter Micron µm	GPM
92612	25	1	30

Mounting Bracket



For 92609

9583
95022

10" Filter Housing



1" Ports, High Flow

9583
92611

Filter Cartridges



Particle Removal Filter

9583	Micron µm
92603	1
92608	2



Limescale/Corrosion Inhibiting Filter

9583	Type
93039	Polyphosphate
92613	Scalex

Replacement O-Ring



For 92609

9583
95024

10" Blue Slimline Filter Housing



1/2" Ports

9583
92609

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

MISTING SYSTEMS - CONTROLLERS

FOGCOntroller

The FOGCOntroller is a 2 zone 24V AC microprocessor that accepts input from two separate sensors. The controller has 5 independent programmable relays that can control a series of fans, zone valves, and pumps.

The controller also includes a programmable time delay NC contact that can be used to terminate all output signals from the controller if a defined condition develops with the system.

The humidity settings range from 30% to 99% with a hysteresis range between 1 and 9. The temperature settings range from 70° to 99° with a hysteresis range between 1 and 9.

The standard sensor will have an accuracy of +/- 2% from 10% to 70% humidity. It is recommended that the high humidity sensor be used for applications requiring humidity levels above 70%.

- The controller requires a 50 Watt 24V AC transformer as a power supply.



2 Zone Microprocessor

9583	Weight g	Dimensions cm		
		L	W	H
92910	454	15.2	8.9	5.7

FOGCOntroller II

The FOGCOntroller II is a humidity controller, with an internal humidity sensor that provides automated operation of a fog system. The unit can operate based on its internal sensor or it can be wired to an external sensor for high humidity applications.

The humidity settings range from 10% to 99% with a hysteresis range between 1 and 5. It is recommended to use the external sensor for humidity levels above 50% and our high humidity sensor for humidity levels above 70%.

The FOGCOntroller II is a single zone microprocessor and has two output relays with a programmable delay start and stop.

The internal and external sensors are fully calibrated re-flow humidity sensors with digital output that send binary data over RS485 protocol. The sensor will have an accuracy of +/- 2%.

- The controller requires a 50 Watt 24V AC transformer as a power supply.



Single Zone Microprocessor

9583	Weight g	Dimensions cm		
		L	W	H
94160	182	14	7.6	2.5

Sensor



For High Humidity

9583	Detection Range	Weight g	Dimensions cm		
			L	W	H
92906	0 to 99%	137	10.2	10.2	2.5

Remote Sensor



For Temperature/Humidity

9583	Detection Range	Weight g	Dimensions cm		
			L	W	H
92909	0 to 70%	91	10.2	5.1	2.5

4 Pin Connector



To Suit FOGCOntroller & FOGCOntroller II

9583	Weight g	Dimensions cm		
		L	W	H
92908	10	2.5	2.5	2.5

DIRECT DELIVERY

Direct Delivery to Mainland UK only. All include a 2-3 day delivery charge for Mainland UK.
For Next Day Delivery, please contact our sales office for a quote.

Fluid-Air Components Ltd

1 Hydraulics 3-284

2 Hydraulic Quick Release Couplings 285-320

3 Pneumatic Quick Release Couplings 321-406

4 Monitor & Test 407-446

5 Pneumatic & Vacuum 447-762

6 Push-in Fittings & Tubing 763-918

7 Valves & Actuation 919-1060

8 Ring Main 1061-1136

9 Hose Tails, Adaptors, Fittings & Manifolds 1137-1224

10 Stainless Steel 1225-1332

11 Malleable Iron 1333-1398

12 Hose, Couplings, Ducting & Hose Reels 1399-1510

13 Clips & Clamps 1511-1558

14 Paint, Sprays & Adhesives 1559-1590

15 Blow Guns, Vacuum & Nozzles 1591-1616

16 Fuelling, Lubrication, Wash Down & Misting 1617-1696

17 Compressors & Air Tools 1697-1726

18 Hand Tools & PPE 1727-1765

SECTION 17

Compressors & Air Tools

17.01 Compressors **1697-1703**

17.02 Air Tools & Accessories **1704-1720**

17.03 Tyre Inflation Equipmen **1721-1726**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 17 Compressors & Air Tools

17.01 Compressors

1697-1703

- Compressors



17.02 Air Tools & Accessories

1704-1720

- Pneumatic Power Tools
- Pneumatic Spraying Equipment & Accessories
- Spray Guns
- Paint Spray Guns
- Air Tools
- Multi-swivel Air Couplings
- Pneumatic Power Tools & Accessories



17.03 Tyre Inflation Equipmen

1721-1726

- Professional Tyre Inflato
- Tyre Inflation Equipmen



Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

COMPRESSORS

Portable Direct Drive Oil Free - Traditional Series 1.1 to 1.5 kW



SO1/6 HP 1.5 VENTO Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-A6BB304FPS534	1.1/1.5	6.7	8/115
Tech Sheet 71795			



VENTO OM200/6 SILENCED Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-A2BB104NUA	1.1/1.5	4.1	8/116
Tech Sheet 71795			



ROLL CAGE OM 195/6 Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-8213885FPS505	1.1/1.5	7.1	8/116
Tech Sheet 71795			



SO2/24 & 50CM2 Piston Compressor

0610	kW/HP	CFM	Bar/PSI	Capacity Litres
S-A3CC404FPS501	1.5/2	8.1	8/116	24
S-A3DV404FPS536	1.5/2	8.1	8/116	50
Tech Sheet 71795				

Portable Direct Drive Oil Free - 110 Volt Series 1.1 kW



ROLL CAGE OM195/6 - 110 V Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-8213885FPS566	1.1/1.5	7.1	8/116
Tech Sheet 71795			



OM197/24 TECH - 110V Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-A8CA3C4FPS567	1.1/1.5	7.1	8/116
Tech Sheet 71795			

Portable Direct Drive Lubricated - Tech Series 1.5 to 1.8 kW



F1-241/24 TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-6SCA404FPS506	1.5/2	8.5	10/145
Tech Sheet 71795			



F1-260/50 TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-75DA4G4FPS507	1.8/2.5	9.2	10/145
Tech Sheet 71795			

Portable Direct Drive Lubricated - Traditional Series 1.1 to 2.2 kW



ND2/24 & 50CM2 Piston Compressor

0610	kW/HP	CFM	Bar/PSI	Capacity Litres
S-FCCC404FPS502	1.5/2	7.4	8/116	24
S-FCDC404FPS503	1.5/2	7.4	8/116	50
Tech Sheet 71795				



NDV/50CM3 Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-SXDL504FPS504	2.2/3	12.6	8/116
Tech Sheet 71795			

Portable Belt Driven Lubricated - Tech Series 1.5 to 2.2 kW



NB2800B/50/2M TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28DA404FPS008	1.5/2	9	10/145
Tech Sheet 71795			



N2800B/50/2M TECH 110 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28DA4C4FPS060	1.5/2	9	10/145
Tech Sheet 71795			

Fluid-Air Components Ltd

COMPRESSORS

Portable Belt Driven Lubricated - Tech Series 1.5 to 2.2 kW



NB2800B/50/3M TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28DA504FPS032	2.2/3	12.5	10/145
Tech Sheet 71795			



NB2800B/100/3M TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28FA504FPS009	2.2/3	12.5	10/145
Tech Sheet 71795			



N2800B/150/3M TECH Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28HA504FPS051	2.2/3	12.5	10/145
Tech Sheet 71795			

FT PRO



For **FRL's** see page **637**

Belt Driven Lubricated - Blue Star Series 1.5 to 7.5 kW



NB28C/50 FM2 230 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28DC404FPS039	1.5/2	9	10/145
Tech Sheet 71795			



NB28C/100 FM3 230 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-28FN504FPS040	2.2/3	12.5	10/145
Tech Sheet 71795			



NB38C/150 & 200 FM3 230 Volt Piston Compressors

0610	kW/HP	CFM	Bar/PSI	Capacity Litres
S-36HN504FPS012	2.2/3	13.95	10/145	150
S-36LN504FPS014	2.2/3	13.95	10/145	200
S-36LN684FPS075	3/4	18	10/145	200
Tech Sheet 71795				



NB38C/150 & 200 FT3 400 Volt Piston Compressors

0610	kW/HP	CFM	Bar/PSI	Capacity Litres
S-36HN541FPS013	2.2/3	13.95	10/145	150
S-36LN541FPS015	2.2/3	13.95	10/145	200
Tech Sheet 71795				



NB38/270 TDT Tandem 400 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-36NW541FPS037	2 x 2.2/3	27.9	10/145
Tech Sheet 71795			



NB7/200 FT 5 400 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-N7LN701FPS044	4/5.5	24	10/145
Tech Sheet 71795			



NB7/270 FT 7 400 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-N7NN801FPS018	5.5/7.5	29.7	10/145
Tech Sheet 71795			



NB10/270 FT 10 400 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-N1NN905FPS019	7.5/10	38.1	10/145
Tech Sheet 71795			



NB38/270 TD Tandem 230 Volt Piston Compressor

0610	kW/HP	CFM	Bar/PSI
S-36NW505FPS038	2 x 2.2/3	27.9	10/145
Tech Sheet 71795			

Fluid-Air Components Ltd

COMPRESSORS

Belt Driven Vertical Series



Vertical Series Piston Compressors

0610	Voltage	kW/HP	CFM	Bar/PSI	Capacity Litres
S-36HY504FPS068	230V	2.2 / 3	13.95	10 / 145	150
S-36HY541FPS069	400V	2.2 / 3	13.95	10 / 145	150
S-36HY684FPS074	230V	3/4	18	10 / 145	150
S-N5NY701FPS070	400V	4 / 5.5	22.9	11 / 160	270
Tech Sheet 71795					

Direct Drive Silent Compressors



ROLLCAGE 6L OL244 Silenced Compressor 230 Volt

0610	kW/HP	CFM	Bar/PSI	Capacity Litres	dB(A)
S-B4BA304FPS571	1.1 / 1.5	7.1	8 / 116	6	60
Tech Sheet 71795					



PIONEER 10L OL244 Silenced Compressor 230 Volt

0610	kW/HP	CFM	Bar/PSI	Capacity Litres	dB(A)
S-B4PP304FPS573	1.1 / 1.5	7.1	8 / 116	10	62
Tech Sheet 71795					



OL244/24 TECH SE Silenced Compressor 230 Volt

0610	kW/HP	CFM	Bar/PSI	Capacity Litres	dB(A)
S-B4CA304FPS572	1.1 / 1.5	7.1	8 / 116	24	62
Tech Sheet 71795					

Belt Driven Lubricated Low Noise Series 1.5 to 7.5 kW



Low Noise Portable Fully Enclosed Piston Compressors

0610	Voltage	kW/HP	CFM	Bar/PSI	Capacity Litres
S-28FR404FPS078	230V	1.5 / 2	9	10 / 145	100
S-28FR504FPS079	230V	2.2 / 3	11.6	10 / 145	100
S-28FR541FPS080	400V	2.2 / 3	11.6	10 / 145	100
Tech Sheet 71795					



Low Noise Portable Piston Compressors

0610	Voltage	kW/HP	CFM	Bar/PSI	Capacity Litres
S-36FR504FPS076	230V	2.2 / 3	11.6	10 / 145	100
S-36FR541FPS077	400V	2.2 / 3	11.6	10 / 145	100
Tech Sheet 71795					



Low Noise Receiver Mounted Piston Compressors

0610	Voltage	kW/HP	CFM	Bar/PSI	Capacity Litres
S-N5NT701FPS083	400V	4 / 5.5	22.6	11 / 160	270
S-N7NT801FPS084	400V	5.5 / 7.5	29.7	11 / 160	270
S-N1TT905FPS086	400V	7.5 / 10	43.4	11 / 160	500
Tech Sheet 71795					



Low Noise Free Standing Piston Compressors

0610	Voltage	kW/HP	CFM	Bar/PSI
S-N5AT701FPS081	400V	4 / 5.5	22.6	11 / 160
S-N7AT801FPS082	400V	5.5 / 7.5	29.7	11 / 160
S-N1AT905FPS085	400V	7.5 / 10	43.4	11 / 160
Tech Sheet 71795				

Fluid-Air Components Ltd

COMPRESSORS

MICRO Fixed Speed Flexonic Belt Driven Screw Compressors 2.2 to 5.5 kW



MICRO Series Receiver Mounted Screw Compressors

0620	Volt	kW/HP	CFM	Bar/PSI
F-V77JT60FNM501	230	2.2/3	10.2	10/145
F-V77JS72FNM701	400	3/4	15.2	8/116
F-V77JQ72FNM701	400	3/4	13.6	10
F-V77JR72FNM701	400	4/5.5	20.5	8/116
F-V77JP72FNM701	400	4/5.5	17.1	10/145
F-V91JW92FNM701	400	5.5/7.5	25.4	8/116
F-V91JO92FNM701	400	5.5/7.5	22.9	10/145
Tech Sheet 71794				



MICRO Series Receiver Mounted c/w Dryer - Screw Compressors

0620	Volt	kW/HP	CFM	Bar/PSI
F-V77JT60FNM601	230	2.2/3	10.2	10/145
F-V77JS72FNM801	400	3/4	15.2	8/116
F-V77JQ72FNM801	400	3/4	13.6	10/145
F-V77JR72FNM801	400	4/5.5	20.5	8/116
F-V77JP72FNM801	400	4/5.5	17.1	10/145
F-V91JW92FNM801	400	5.5/7.5	25.4	8/116
F-V91JO92FNM801	400	5.5/7.5	22.9	10/145
Tech Sheet 71794				

FT PRO®

For **Long Life Compressor Oil**
...see page **434**



FINI PLUS Fixed Speed Flexonic Belt Driven Screw Compressors 7.5 to 15 kW



FINI PLUS Series Receiver Mounted Screw Compressors

0620	Capacity Litres	kW/HP	CFM	Bar/PSI
F-V91NG92FNM701	270	7.5/10	44.1	8/116
F-V91NH92FNM701	270	7.5/10	35.3	10/145
F-V91NL92FNM701	270	11/15	58.2	8/116
F-V91NM92FNM701	270	11/15	53	10/145
F-V83NP92FNM701	500	15/20	75.9	8/116
F-V83NQ92FNM701	500	15/20	65.3	10/145
Tech Sheet 71794				



FINI PLUS Series Receiver Mounted c/w Dryer - Screw Compressors

0620	Capacity Litres	kW/HP	CFM	Bar/PSI
F-V91NG92FNM801	270	7.5/10	44.1	8/116
F-V91NH92FNM801	270	7.5/10	35.3	10/145
F-V91NL92FNM801	270	11/15	58.2	8/116
F-V91NM92FNM801	270	11/15	53	10/145
F-V83NP92FNM801	500	15/20	83	8/116
F-V83NQ92FNM801	500	15/20	72.4	10/145
Tech Sheet 71794				

Fluid-Air Components Ltd

COMPRESSORS

Bambi Compressors



Silent Air Compressor, 9 Litre Tank

0630	Litres per Minute	Pressure Bar	Voltage
BB8	50	8	240/50
	Tech Sheet 71793		



Silent Air Compressor, 24 Litre Tank

0630	Litres per Minute	Pressure Bar	Voltage
BB24	50	8	240/50
	Tech Sheet 71793		



Silent Air Compressor, 15 Litre Tank

0630	Litres per Minute	Pressure Bar	Voltage
BB15	50	8	240/50
	Tech Sheet 71793		



Silent Air Compressor, 50 Litre Tank

0630	Litres per Minute	Pressure Bar	Voltage
BB50D	100	8	240/50
	Tech Sheet 71793		



Silent Air Wheel Kit (BB24 & BB50)

0630	Description
BPB0157	Wheel Kit suits BB24 & BB50D
	Tech Sheet 71793

FT PRO



For **Automatic Drain Valves**
...see pages **1024-1025**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AEROPRO

ENGINEERED FOR PROFESSIONALS

FEATURES & BENEFITS

Design: attractive, lightweight and comfortable composite grip handle.

Quality: designed with superior technology, manufactured with precision and high quality to deliver more power and a longer life.

Robust: heat treated components for increased durability, fully hardened planetary gears and reduced friction for extended tool productivity.

Warranty: 12 months manufacturer's warranty.



www.aeropro-eu.com

1704

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PNEUMATIC POWER TOOLS







SAFETY TIPS:

A few tips to increase safety awareness and help avoid accident and injury in the workplace.

(These are not a substitute to the AEROPRO safety/instruction manuals.)

VISUAL INSPECTION PRIOR TO USE

Conduct a visual check of the tool, including hoses and fittings for signs of damage/excess wear or defect parts. Ensure tool is fully oiled.

USE THE CORRECT ACCESSORIES

Always use recommended accessories with **AEROPRO** tools, e.g. never use hand sockets with impact wrenches. Always disconnect air supply prior to changing an accessory.

SAFETY WEAR

Always adhere to workplace safety workwear regulations. In addition when operating equipment always wear goggles and ear plugs as well as gloves, apron, helmet and dust mask when required. When working with materials that may produce harmful airborne particles, use other equipment such as dust extractors to control exposure.

MAINTAIN A SAFE WORKING AREA

Make other people aware of your working area and ensure they are kept at a safe distance. Manage your floor space keeping it free of trip hazards, trailing hoses, etc. Direct exhaust gases away from yourself and others, do not use in explosive atmospheres and always keep away from electrical wiring.

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

Ratchet Wrenches

- Designed with superior technology and manufactured with precision and high quality to deliver more power and a longer life
- Ball bearing mounted air motor produces enough power for most requirements
- Fully hardened planetary gears reduce friction for extended tool productivity
- Comfortable composite grip handle
- Ball socket retainer provides fast and easy socket replacement
- Heat treated components for increased durability
- Lightweight aluminium body
- Compact head design allows flexibility in tight areas
- Forward/reverse lever located behind the ratchet head for quick change of direction
- Side exhaust
- Recommended air pressure: 90 PSI



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
		Imp	Met mm		Ft-Lb	N.m	In	mm			cfm	l/min	Lbs	Kgs
AP17411	3/8"	1/2	13	160	50	68	10.8	275	1/4"	3/8"	3	85.5	2.5	1.15

3/8" Square Drive

0373
AP17411-3/8
Tech Sheet 10236



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
		Imp	Met mm		Ft-Lb	N.m	In	mm			cfm	l/min	Lbs	Kgs
AP17411	1/2"	1/2"	13	160	50	68	10	254	1/4"	3/8"	2.7	77	2.4	1.1

1/2" Square Drive

0373
AP17411-1/2
Tech Sheet 10236

Air Impact Wrenches

- Twin hammer mechanism has two identical hammers that deliver an instantaneous balanced blow, reducing vibration and transferring more torque to the drive than any other mechanism on the market
- Provides more power and smooth balanced blows
- Screened filter air inlet keeps dirt and debris from damaging the tool
- Rear exhaust
- Recommended air pressure: 90 PSI



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
		Imp	Met mm		Ft-Lb	N.m	In	mm			cfm	l/min	Lbs	Kgs
AP7451	1/2"	5/8"	16	7,500	450	610	7.48	190	1/4"	3/8"	6.5	183.9	4.2	1.9

1/2" Square Drive

0373
AP7451
Tech Sheet 10235

Colour may vary.



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
		Imp	Met mm		Ft-Lb	N.m	In	mm			cfm	l/min	Lbs	Kgs
AP7460	3/4"	1"	25	7000	1000	1355	8.2	208	3/8	1/2	9.5	269	6.6	3.0

3/4" Square Drive

0373
AP7460
Tech Sheet 10237

FAC
Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

Air Impact Wrench Kit

- Twin hammer mechanism has two identical hammers that deliver an instantaneous balanced blow, reducing vibration and transferring more torque to the drive than any other mechanism on the market
- Provides more power and smooth balanced blows
- Screened filter air inlet keeps dirt an debris from damaging the tool
- Rear exhaust
- Recommended air pressure: 90 PSI

Contents:

1 x AP17407 1/2" impact wrench
10 x impact sockets
(9, 10, 11, 13, 14, 17, 19, 22, 24, 27mm)
1 x 5" extension bar
1 x oil pot
1 x hex wrench
1 x mini oiler
1 x nipple
1 x blow moulded case



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
		Imp	Met mm		Ft-Lb	N.m	In	mm			cfm	l/min	Lbs	Kgs
AP17407	1/2"	5/8"	16	7,500	450	610	7.30	187.4	1/4"	3/8"	6.5	183.5	4.9	2.26

1/2" Square Drive, 17 Piece Kit

0373
AP17808
Tech Sheet 10238

Air Impact Wrench

- Ergonomic design handle, central gravity for steady control
- Alloy steel strike structure, strong, anti-fatigue, long life and excellent torque/weight ratios
- 45° air inlet design to decrease hose twisting
- Extended drive shaft for easy accessibility to concave restricted access
- Four speed forward and reverse setting



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight		Suggested Air Comp
		Imp	Met mm		Ft-Lb	N.m	Imp	Met mm			cfm	l/min	Lbs	Kgs	
AP7495	1"	2"	50	2800	2500	3480	25.4	644	1/2"	5/8"	43	1225	41.6	18.9	5 HP

1" Square Drive

0373
AP7495
Tech Sheet 20217

FT PRO



You might also need
Air Hose see page **1410**

FT PRO



You might also need
QRC see page **290**

Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

Straight Grip Drill

- For applications where a compact and low profile tool is require
- Precision machined gearing ensures maximum power transfer and durability
- Lightweight – helps prevent fatigue during prolonged use
- Ideal for confined space
- Recommended air pressure: 90 PSI



Model No.	Chuck Size	Free Speed RPM	Air Inlet	Air Hose (ID)	Overall Length		Average Air Consumption		Net Weight	
					In	mm	cfm	l/min	Lbs	Kgs
AP17111	3/8"	2,600	1/4"	3/8"	8.8	225	4.0	115	1.87	0.85

3/8" Keyed Chuck

0373
AP17111
Tech Sheet 10239

Pistol Grip Reversible Drill

- Suited to compact low profile applications
- Variable speed throttle for easy starts
- Precision machined gearing ensures maximum power transfer and durability
- Convenient one hand push button (forward/reverse)
- Lightweight – helps avoid fatigue during prolonged use
- Quiet operation with rear exhaust directs air away from workplace
- Ball bearing construction
- Recommended air pressure: 90 PSI



Model No.	Chuck Size	Free Speed RPM	Air Inlet	Air Hose (ID)	Overall Length		Average Air Consumption		Net Weight	
					In	mm	cfm	l/min	Lbs	Kgs
AP17101	3/8"	1,800	1/4"	3/8"	7	180	3.7	104	1.98	0.9

3/8" Keyed Chuck

0373
AP17101
Tech Sheet 10240



Model No.	Chuck Size	Free Speed RPM	Air Inlet	Air Hose (ID)	Overall Length		Average Air Consumption		Net Weight	
					In	mm	cfm	l/min	Lbs	Kgs
AP17107	1/2"	700	1/4"	3/8"	7.68	195	4	115	1.18	1.19

1/2" Keyed Chuck

0373
AP17107
Tech Sheet 10241

Air Impact Hammer

- Ergonomic grip for comfort and stability
- Heat treated impact parts for enhanced durability
- Positive action trigger and built-in air regulator for simple power and speed control
- Screened filter air inlet to keep dirt and debris from damaging the tool
- Standard quick change spring for speed and ease of chisel change
- Front exhaust
- Recommended air pressure: 90 PSI
- 4 piece chisel set included



Model No.	Chisel Shank mm	Blows per min	Air Inlet	Air Hose (ID)	Overall Length		Average Air Consumption		Net Weight	
					In	mm	cfm	l/min	Lbs	Kgs
AP17621	10.2	4,500	1/4"	3/8"	6.10	155	2.8	79.8	2.65	1.2

Heavy-duty

0373
AP17621
Tech Sheet 10242

2 in 1 Air Nailer & Stapler

- Strong and lightweight aluminium die-casting gun body
- Multidirectional exhaust port directs air away from the operator and work surface
- Hardened one piece drive blade for professional application
- Teflon O-ring to protect the piston from wearing
- Tool free depth-of-drive adjustment for exact setting of nail head
- Adjustable knob for either sequential or contact firin
- Designed for Ga18 style nails and staples up to 50mm in length
- Includes nailer, wrenches, oil, operating manual and rugged carrying case



Model No.	Dimensions (mm)	Required Pressure		Max Pressure		Nail Capacity	Weight	
		PSI	Bar	PSI	Bar		lbs	kgs
APSF5040RC	283x256x60	70-110	4.8-7.5	120	8.3	100 Pcs	3.52	1.6

0373
APSF5040RC
Tech Sheet 20219

PORTWEST



For **Eye Glasses**
see page **1754**

FAC Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

Die Grinder

- Lightweight aluminium body
- Safety lever prevents accidental starts
- Rear exhaust
- Can be used with all types of accessories for porting, weld breaking and smoothing sharp edges, as well as deburring, polishing and grinding
- Recommended air pressure: 90 PSI



Model No.	Grinder Cap	Free Speed RPM	Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
					cfm	l/min	Lbs	Kgs
AP17313	1/4"	20,000	1/4"	3/8"	3	86.25	0.70	0.32

Straight, 1/4"

0373
AP17313
Tech Sheet 10243

- Angle head provides easy access into confined space
- Lightweight aluminium body
- Safety lever prevents accidental starts
- Rear exhaust
- Can be used with accessories for porting, weld breaking and smoothing sharp edges, as well as deburring, polishing and grinding
- Recommended air pressure: 90 PSI



Model No.	Grinder Cap	Free Speed RPM	Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
					cfm	l/min	Lbs	Kgs
AP17315	1/4"	20,000	1/4"	3/8"	2.2	62	0.99	0.45

Angled, 1/4"

0373
AP17315
Tech Sheet 10244

Angle Die Grinder Kit

- Angled head provides easy access into confined space
- Lightweight aluminium body
- Safety lever prevents accidental starts
- Rear exhaust
- Can be used with all types of accessories for porting, weld breaking and smoothing sharp edges as well as deburring, polishing and grinding
- Recommended air pressure: 90 PSI

Kit contains:

1 x angle die grinder (AP17315)
2 x hand wrenches
10 x grinding stones
1 x nipple
1 x collet
1 x blow case



Model No.	Grinder Cap	Free Speed RPM	Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
					cfm	l/min	Lbs	Kgs
AP17315	1/4"	20,000	1/4"	3/8"	2.2	62	0.99	0.45

16 Piece Kit

0373
AP17803-A
Tech Sheet 20220

4" Angle Grinder

- Built-in regulator to control speed
- Planetary gearing balances load on bearings and gears for greater power
- Side exhaust
- Recommended air pressure: 90 PSI



Model No.	Sanding Pad		Free Speed RPM	Air Inlet	Air Hose (ID)	Average Air Consumption		Net Weight	
	In	mm				cfm	l/min	Lbs	Kgs
AP7319	4"	100	10,000	1/4"	3/8"	5	140	2.86	1.3

Heavy-duty

0373
AP7319
Tech Sheet 10245

Basic Air Tool Kit

Kit contains:

- Paint spray gun
- Blow gun
- Tyre inflation gun
- Wash gun
- 5mm recoil air hose



5 Piece Set

0373
AP8031K5G
Tech Sheet 20753

PORTWEST



For **Impact Gloves** see page **1758**

FAC
Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

1/2" Impact Socket Set

- Contains hexagon sizes: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16" and 1"
- Hardened steel for robust use
- Steel case for safe storage



Imperial, 11 Piece Set

0373
AP7007

7" Chisel Kit

Kit contains:

- Flat chisel
- Tapered punch chisel
- V chisel
- Claw chisel



4 Piece Kit, suitable for AP17621

0373
AP7002-7

Replacement Keyless Chuck



3/8" & 1/2"

0373	To Suit
APKLC38	3/8"
APKLC12	1/2"

Chisel Spring Retainer

To suit AP17621.



Replacement Spring

0373
AP7001

Airline Oil

High quality mineral oil with excellent lubricating properties for machine and power tools.

Due to restrictions imposed by the Transport of Dangerous Goods Act, this product is available for delivery to **MAINLAND UK ONLY**.
For further information please contact our customer service department.



Airline Lubricant

0088	Litres
2020-6009	5
	Tech Sheet 1224

Universal Tool Oil



0088	Volume Millilitres
H0076	100
H0077	220

Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS

AEROPRO
ENGINEERED FOR PROFESSIONALS

Industrial Airless Paint Sprayer

- PC control system can show the working condition of the machine clearly
- Ergonomic design makes it easy to transport
- Long performance motor designed for industrial use

Includes:
1 x AP818C (airless spray gun)
1 x AP8648-15M (15m high pressure paint spraying hose assembly)



Model No.	Voltage	Motor Size	Max Pressure	Standard Nozzle	Discharge Connection	Flow rate L/min	Nett Weight Kg
AP488	220V/50Hz	1.2HP	230 bar	0.017"	1/4"	2.1	16.5

Brushless Motor

0373
AP488
Tech Sheet 20222

PORTWEST



For **Engineers Gloves**
see page **1760**

Airless Spray Gun

- In-handle paint filter reduces tip clogs and improves finis
- Well balanced and lightweight
- Full trigger (four-finger) locks open for flushing and cleanin
- Ergonomic design and easy trigger pivot to reduce operator fatigue



Model No.	Nozzle Size (AP517)		Pattern Width mm	Paint Capacity mm	Type of Feed	Working Pressure (bar)	Paint Inlet Connection	
	Fan Width	Orifice Size					In	Npsm
AP818C	0.017	0.517	254-305	300	Pressure	248	1/4"	18

Four-finger Trigger

0373
AP818C
Tech Sheet 20223

Interchangeable with Titan Graco sprayer.



Airless Spray Gun Switch Tips

0373	Orifice mm	Fan Width
AP313	0.33	152-203
AP415	0.38	203-254
AP515	0.38	254-305
Tech Sheet 20224		



Extension Nozzles

0373	Length mm
AP8641-1	450
AP8641-4	1000

FAC
Fluid-Air Components Ltd

PNEUMATIC SPRAYING EQUIPMENT & ACCESSORIES

AEROPRO
ENGINEERED FOR PROFESSIONALS

Air Powered Diaphragm Pumps

Widely used in paint spraying, chemical, ceramics, biotechnology, medical and food industries.



Model No.	Air Inlet	Paint Inlet	Paint Outlet	Capacity (ml)	Weight (Kg)	Operating Pressure (bar)	Air Consumption (m^3/h)	Flow Rate (Lph)	Pressure Ratio
APA-15	1/4"	3/8"	1/4"	400	7	2-7	10	1080	1:1

0373
APA-15
Tech Sheet 20227

- Diaphragm life up to 18 million cycles
- Patented commutator construction
- 100% transmission efficienc
- Available for 4-6 spray guns simultaneously
- Suitable for conveyance fluid and paint spraying
- Unique air circulation structure which provides stall-free life cycle



Model No.	Air Inlet	Paint Inlet	Paint Outlet	Capacity (ml)	Weight (Kg)	Operating Pressure (bar)	Air Consumption (m^3/h)	Flow Rate (Lph)	Pressure Ratio
APA-25	1/4"	3/4"	3/4"	–	4.5	2-7	40	3060	1:1

0373
APA-25
Tech Sheet 20228

Paint Mixing Tanks

- Used for premixed paint, excellent for larger spray areas
- Compact portable design quick release catches for paint tank
- 3m twin hose set permits easy movement
- Fluid pressure regulator included for accurate setting
- Includes pressure spray gun with 2mm nozzle



Model No.	Capacity (L)	Operating Pressure		Paint Outlet	Mixing Type
		psi	bar		
APR8312	10	20-30	1.4-2.1	1/4"	-

10L Paint Tank with Hose & Spray Gun

0373
APR8312
Tech Sheet 20543

PORTWEST



For **Respiratory Protection** see page **1755**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PNEUMATIC SPRAYING EQUIPMENT & ACCESSORIES

AEROPRO
ENGINEERED FOR PROFESSIONALS

HVLP

High volume, low pressure (HVLP) spray guns are designed similar to conventional spray guns, the only difference being that unlike conventional spray guns, which operate under high pressure, HVLP spray guns operate at a much lower pressure.

- Offers a more accurate way of spray painting, with less chance of overspray
- Produces a more thick and consistent quality of paint finis
- Less pollution compared to conventional spray guns
- Consumes less materials down to minimising overspray

LVLP

Low volume, low pressure (LVLP) spray guns are designed to work similar to the HVLP guns but to consume less air than the HVLP and used mainly in more intricate spraying on smaller areas. Used in auto painting and spraying of furniture, etc.

- More intricate spraying
- Low volume of air is utilised to finely atomize paint creating a very smooth fini
- Increased prevention of overspray and material wastage

Spray Guns

- Stainless steel needle and nozzle to accommodate a variety of coatings
- Brass air cap and adjustable knob
- Includes adjustable fluid, pattern and air control
- Designed to provide equal atomisation and particle size for all kinds of surface painting
- Lightweight, ergonomic design and easy trigger pivot to reduce operator fatigue



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
APH827A	Gravity	600	2.0-3.5	180-250	4.2-7.1	1.4

HVLP, Gravity Feed

0373
APH827A
Tech Sheet 20575



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
APR500	Gravity	600	2.0-3.5	180-250	3.0-3.9	1.5

LVLP, Gravity Feed

0373
APR500
Tech Sheet 20577



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
APR71	Pressure	-	3.0-4.0	180-250	3.5-6.4	1.5

Gravity Feed

0373
APR71
Tech Sheet 20577



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
APAS1005	Suction	1000	2.0-3.5	180-250	4.2-7.1	1.4

HVLP, Suction Feed

0373
APAS1005
Tech Sheet 20576



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
APR200S	Suction	1000	2.0-3.5	180-250	3.0-3.9	1.5

LVLP, Suction Feed

0373
APR200S
Tech Sheet 20578



Model No.	Type of Feed	Paint Capacity (cc)	Operating Pressure (Bar)	Patern Width (mm)	Air Consumption (cfm)	Standard Nozzle (mm)
AP100B	Suction	600	3.0-4.0	180-250	4.2-6.4	1.5

Detailing, Suction Feed

0373
AP100B
Tech Sheet 20580

Nozzles

0373	To Suit	Ø mm
APH827-N1.4	APH827A	1.4
APH827-N1.7	APH827A	1.7
APAS1005-N1.4	APAS1005	1.4
APAS1005-N1.7	APAS1005	1.7
APR500R200S-N1.5	APR500 & APR200S	1.5
APR71-N1.7	APR71	1.7



Nozzle Size (mm)	Application
1.3	Clearcoats
1.4 to 1.7	Basecoats
2.0 to 2.2	Primers

Fluid-Air Components Ltd

SPRAY GUNS

High Pressure Spray Gun

- High pressure spray gun
- Dual action trigger
- Adjustable spray pattern
- External mix nozzle
- 1/4" bayonet quick connect.



0088
TOOL-763556

Expert Gravity Feed Spray Gun

- High performance, well balanced, spray gun
- For use in automotive spraying
- Separate flow and pattern controls
- 125ml nylon cup
- 1.2mm nozzle
- 1/4" bayonet quick connect



0088
TOOL-580420

Suction Feed Spray Gun

- Suction feed spray gun
- Dual action trigger
- Adjustable spray pattern
- External 1.5mm mix nozzle
- 750cc capacity
- 1/4" bayonet quick connect



0088
TOOL-196536

Gravity Feed Spray Gun

- Gravity feed spray gun
- Separate flow and pattern controls
- Dual action trigger control
- 1.5mm nozzle
- 500ml nylon cup
- 1/4" bayonet quick connect



0088
TOOL-783124

Fluid-Air Components Ltd

PAINT SPRAY GUNS

HVLP Spray Guns

PCL's HVLP suction spray gun utilises a precision engineered brass air cap, stainless steel fluid nozzle and needle which provide a premium quality paint finish. This newly developed 'compliant' spray gun offers the user high transfer efficiency, lower material consumption and is environmentally friendly.

- Suitable for water based paints
- 1.7mm fluid nozzle
- 1 litre aluminium cup

Maximum Working Pressure:
50lbf/in²



Suction Spray Gun

7000
SG01P

PCL's HVLP gravity spray gun utilises a precision engineered brass air cap, stainless steel fluid nozzle and needle which provide a premium quality paint finish. This newly developed 'compliant' spray gun offers the user high transfer efficiency, lower material consumption and is environmentally friendly.

- Suitable for water based paints
- 1.4mm fluid nozzle
- 0.6 litre plastic cup

Maximum Working Pressure:
50lbf/in²



Gravity Spray Gun

7000
SG02P

Lite Air Tools

Key Product Benefits:

- Ergonomic design for comfort
- Lightweight materials
- Ready for immediate use
- Comes complete with cleaning brush and hose tail piece

Key Product Features:

- Tank capacity: 750cc
- Operating pressure: 3 to 4 bar
- Air consumption: 4.2 to7.1 cfm
- Nozzle size: 1.5mm
- Pattern width: 140 to 180mm
- Body and canister material: aluminium



Lite Suction Spray Gun

7000
SG01L
Tech Sheet 2172

Key Product Benefits:

- Tank capacity: 600cc
- Operating pressure: 3 to 4 bar
- Air consumption: 4.2 to 7.1 cfm
- Nozzle size: 1.5mm
- Pattern width: 120 to 250mm
- Body and canister material: aluminium and plastic



Lite Gravity Spray Gun

7000
SG02L
Tech Sheet 2173

ambersil



For **Ambersil Cleaning & Lubrication**
see pages **1571-1575**

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

AIR TOOLS

Impact Wrenches

1/2" Super Duty

Features:
- DYNA-PACT oil bath clutch
- One handed push button forward/reverse with four positive power settings
- Full power in reverse
- Compact and ergonomic with rubber handle
- 425ft-lbs (576Nm) of maximum torque in reverse

Benefits:
- Clutch delivers smooth operation and extreme durability
- Versatile and powerful tool ideal for all general repairs and maintenance applications



0219
CP734H
Tech Sheet 3071

3/8" Compact

Features:
- Steel front cover and aluminium body
- One hand operation forward/reverse by either left or right handed users
- Easily adjustable for either right or left handed operation
- Three setting positions
- Length: 4.4" (112mm)
- Jumbo hammer

Benefits:
- Best power to weight ratio: 306ft-lbs (415Nm)
- Ultra compact
- Easy to use
- Durable



0219
CP7731
Tech Sheet 60195

1/2" Composite

Durable and Powerful:
- Maximum torque: 1,250Nm in reverse
- Working torque: 102-786Nm
- Includes rechargeable torch

Features:
- 922ft-lbs (1,250Nm) of maximum torque in reverse
- Durable aluminium back housing
- Insulated and comfortable grip with rubber-injected composite housing
- Universal and durable twin hammer mechanism

Benefits:
- Maximise work efficienc with great power
- Most powerful 1/2" impact wrench in the range
- Extremely fast run down for quick work
- Reduced operator fatigue



0219
CP7748
Tech Sheet 60251

3/4" Super Duty

Features:
- 3/4" impact wrench with ring retainer
- DYNA-PACT oil bath clutch
- Single handed reverse button with four power settings
- Comfortable handle grip

Benefits:
- General maintenance
- Smooth operation with DYNA-PACT clutch
- Comfortable use with low noise and vibration levels
- Good durability



0219
CP772H
Tech Sheet 60253

1/2" Compact

Features:
- Steel front cover and aluminium body
- One hand operation forward/reverse by either left or right handed users
- Three setting positions
- Length: 4.4" (112mm)
- Jumbo hammer

Benefits:
- Best power to weight ratio: 450ft-lbs (610Nm)
- Ultra compact
- Easy to use
- Durable



0219
CP7732
Tech Sheet 60252

1" Heavy-duty

Features:
- 1" straight impact wrench with 6" extended anvil
- 1,920ft-lbs (2,600Nm) of maximum torque in reverse
- Pinless, closed, reinforced rocking dog impact mechanism
- Dual socket retention, hole and friction ring
- Ergonomic side handle
- Full teasing trigger
- Regulator with integrated forward/reverse, with three position power settings in both directions

Benefits:
- Highly efficient yet economical motor with durable reinforced clutch mechanism
- Durable impact wrench with great power for the toughest jobs on heavy vehicles



0219
CP7782-6
Tech Sheet 60196

Fluid-Air Components Ltd

AIR TOOLS

Chicago Pneumatic

Drills

Features:
- Compact low profile head to get in to confined space
- Reverse valve for easy directional change
- High performance gearing for extended durability

Benefits:
- Compact angle head drill
- Operator control from start up through run down
- Ideal for drilling and screw driving in confined area



3/8" Angle Drill

0219
CP879
Tech Sheet 3074

Features:
- Fast and efficient at 2,900rpm
- Industrial quality Jacob's chuck
- Ergonomic grip

Benefits:
- Productivity and durability
- Maximise operator comfort
- Power suitable for many applications



3/8" Pistol Drill, Heavy-duty

0219
CP9285
Tech Sheet 3076

Ratchet

Features:
- 1/2" ratchet
- Compact head design
- Hardened gears

Benefits:
- Good durability
- Easy grip reverse for simple directional changes



1/2" Ratchet

0219
CP886H
Tech Sheet 60202

Riveters

Features:
- Compact size and composite body
- 3/16" maximum capacity
- Heavy pulling: up to 1,900lbs (865kg)
- Low vibration and low noise level
- Includes: 3/32", 1/8", 5/32" and 3/16" (2.4, 3.2, 4 and 4.8mm) nose pieces

Benefits:
- Broad applications coverage
- Durable, reliable and easy to service
- Maximise operator comfort



3/16" Riveter, Heavy-duty

0219
CP9883
Tech Sheet 3092

Features:
- Air riveter for general maintenance
- Compact size
- 3/16" maximum capacity
- For rivets in aluminium, copper and softer materials
- Heavy pulling: up to 2,200lbs (1,000kg)
- Transparent container with holes for quick release of rivet ends
- Includes nose pieces for rivets: 3/32", 1/8", 5/32" and 3/16" (2.4, 3.2, 4 and 4.8mm)

Benefits:
- Simple construction for easy maintenance
- Great for trailer panels, number plates, and any type of panels maintenance



General Purpose Riveter

0219
CP9882
Tech Sheet 60205

Grinders

Features:
- Keyless adjustable protective guard
- Aluminium alloy housing
- Helical bevel gear design
- 5" (125mm) wheel capacity
- M14 spindle thread
- 0.8hp (600W) governed motor
- Ergonomic side handle

Benefits:
- Suitable for general maintenance applications
- Lightweight but rugged housing
- Durability and performance



5" Angle Grinder

0219
CP9121AR
Tech Sheet 60204

Features:
- 3mm and 1/8" collets included
- Very low noise level – only 71dB(A)
- Good power/size ratio with 60,000rpm high free speed

Benefits:
- Extremely easy to handle, quiet and lightweight
- Ideal for tight access application



Compact Pencil Grinder

0219
CP9104Q
Tech Sheet 3084

Features:
- Powerful 0.8hp (600W) motor
- Adjustable protective guard and aluminium alloy housing
- Spiral bevel gears
- Ergonomic side handle

Benefits:
- Excellent for weld preparation and smoothing, rust removal, deburring and blending of steel, cast iron and aluminium
- Lightweight but rugged housing
- Durability and performance



4" Angle Grinder, Heavy-duty

0219
CP9120CR
Tech Sheet 3089

Features:
- Efficient and powerful 0.32hp (240W) motor
- Low noise level: 80dB(A)
- Easy access speed regulator
- Compact and ergonomic grip
- Rear exhaust
- 1/4" and 6mm collets included

Benefits:
- Maximised operator comfort
- Performance and power
- Increased precision for best operator control
- Ideal for confined access applications



Compact In-line Die Grinder

0219
CP9105QB
Tech Sheet 3086

AIR TOOLS

Chicago Pneumatic

Sanders

Features:
- PSA sanding pad
- Insulated grip and lock-off throttle to prevent accidental start-ups
- Power regulator for precise control

Benefits:
- Excellent for blending and smoothing fille , feather edging and pre-paint preparation
- Operator comfort



Dual Action Sander

0219
CP870
Tech Sheet 3081

Features:
- Quick change belt replacement
- Adjustable sanding arm
- Handle exhaust and swivel air inlet
- Rubber moulded grip

Benefits:
- Excellent for paint removal, weld sanding, smoothing and rust removal in tight areas
- Operator comfort



Belt Sander

0219
CP9779
Tech Sheet 3083

High Speed Cutter

Features:
- Wheel diameter 2.7/8"
- Adjustable speed regulator
- Safety lever to prevent accidental start up
- Rear exhaust

Benefits:
- Ideal for cutting through composite, sheet metal, bolts, etc.
- Precise and safe control



High Speed Cutter, Standard Duty

0219
CP874
Tech Sheet 3095

Hammer Kit

Features:
- Heavy-duty pistol grip hammer
- Standard .401 round shank
- Internal muffle minimises exhaust sound
- Unique vibration damping
- Teasing trigger for slow start-up

Benefits:
- Maximise operator comfort and control
- Smooth operation
- Low vibrations to maximise productivity

Kit Includes:
- Four chisels
- One posi-lock retainer
- Heavy-duty case



Hammer Kit, Heavy-duty

0219
CP7110 KIT
Tech Sheet 60207

FT PRO®



For **BE Couplings** see pages **325-328**

Fluid-Air Components Ltd

MULTI-SWIVEL AIR COUPLINGS

Swivel Connector

The MultiFlex swivel is an ingenious multidirectional connector. Connect your tool and the hose will stay in the ideal position however much you and the tool move around. The MultiFlex bends and rotates 360° in all directions while the hose stays straight. It takes the effort out of working in those cramped spaces, the hose feels almost weightless and it reduces hose wear.

Features and Benefits

- Improved ergonomics; less strength is needed to move around tool and hose
- Reduced hose wear
- High flow capacity and low pressure drop
- Strong and durable for long lifetime



Working Temperature:
-10°C to +70°C

Maximum Working Pressure:
10 bar

BSPP

0454	Thread
MFCB-02	1/8"
MFCB-04	1/4"
MFCB-06	3/8"
MFCB-08	1/2"
Tech Sheet 20443	

NPT

0454	Thread
MFCN-02	1/8"
MFCN-04	1/4"
MFCN-06	3/8"
MFCN-08	1/2"
Tech Sheet 20443	





For **Hose Reels**
see pages **1448-1453**

Fluid-Air Components Ltd

PNEUMATIC POWER TOOLS & ACCESSORIES

Blind Riveter 3/16" Capacity

Features:

- Maximum rivet capacity: 3/16"
- Air pressure: 90 PSI
- Tool length and height: 271mm x 255mm
- Tool weight: 1.75kg
- Air inlet: 1/4" BSPP female
- Air consumption: 4.2 cfm
- Sound pressure: 73 dB (A)
- Sound power: 65 dB (A)
- Vibration level: 0.7 m/s²



0088
2017-0460

Paint Spray Guns



Code	Flow	Bowl Capacity	Inlet	Hose ID
W-97	Suction	1000cc	1/4"	3/8"

	Average Air Consumption		Working Pressure cc		
Code	CFM	Litres/min	psi	kg/cm²	Nozzle mm
W-97	10	280	50-70	3.5-5.0	1.5

High Pressure Spray Gun

0088	Type
W-97	Gun & Bowl
	Tech Sheet 20434

Tool Balancers

Plastic coated steel wire.



0088	Kg	Length Metres
2021-0209	0.6-1.5	1.6
2021-0217	1-2	1.6
2021-0225	1.5-3	1.5
2021-2030	3-5	0.9
	Tech Sheet 20433	

A complete range of balancers, capabilities from 0.4 to 14Kg, available stroke up to 2.5m. To eliminate labour, to cut down idle times, to improve work quality, to reduce hose and cable wear and to avoid both damage to people and tools. For either bench or assembly line jobs, applications ranging from small tools to industrial guns and multiple screwdrivers.

Features:

- Stainless steel cable
- Auxiliary safety suspension
- Adjustable stroke-limiting device
- Adjustable capacity
- Polyamide thimble
- Rugged construction, cast aluminium body
- (Models 2-3) safety device against load dropping due to spring breakage (>3kg)
- Cable guide in anti-friction material



Redashe

For Tools & Weights from 0.4 to 14Kg

0122	Kg	Length Metres
M9311	0.4-1	1.6
M9312	1-2	1.6
M9313	2-3	1.6
M9320	1-2.5	2
M9321	2-4	2
M9322	4-6	2
M9323	6-8	2
M9336	2-4	2.5
M9337	4-6	2.5
M9338	6-8	2.5
M9339	8-10	2.5
M9340	10-14	2.5

Ambersil



For **Paint Marker Pens** see page **1582**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c c a c c

FT PRO®

Professional Tyre Inflator



Features:

- Body: zinc alloy and aluminium, 1/4" female
- Hose: 1/4" x 33cm rubber hose with spring guard
- Chuck: 1/4" female x 6" long with PVC protector
- Chuck material: brass and zinc alloy
- Vibration resistant

Pressure Range:
0-1050 kPa
0-150 PSI, 0-10 kg/cm²

0088
IG400
Tech Sheet 1948

Tyre Inflators



In-line

1305
TG-4



Trigger

1305
TG-3

1721

Fluid-Air Components Ltd

TYRE INFLATION EQUIPMENT

JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

Jamec Auto 1000 Automatic Tyre Inflato



1470	Connector Style
11.06120S2	Single Clip-on

Jamec TDR2000 Tyre Inflato , 500mm/20" Hose



1470	Similar To	Connector Style	Calibration
10.20000S	AFG4H03	Angled Twin Hold-on	0-138 PSI/ 0-960 kPa

Jamec TDR2000 Tyre Inflato , 2.7 Metres/9' Hose



1470	Similar To	Connector Style	Calibration
10.20000S4	AFG4H03	Single Clip-on	0-138 PSI/ 0-960 kPa

Jamec TDR Digital Tyre Inflator Twin Clip-on Connector, 2.7 Metres Hose



1470	Connector Style	Calibration
10.30120S2	Angled Twin Clip-on	+/- 2 PSI at 25 - 75 PSI

Jamec Single Clip-on Connector, Open End



1470	Similar To	Connection	Thread
03.04470S	CO8T73	Single Clip-on	1/4" BSPF

Jamec Twin Hold-on Connector, Open End



1470	Similar To	Connector Style	Thread
03.04650S	CO1A03	Angled Twin Connector	1/4" BSPF

Jamec Twin Hold-on Connector, Closed End



1470	Similar To	Connector Style	Thread
03.04720S	CO1B03	Angled Twin Connector	1/4" BSPF

Jamec Twin Clip-on Connector, Open End



1470	Valve Connection Type	Style
03.0435NSOS	Twin Clip-on	Open Ends

Jamec Twin Clip-on Connector, Closed End



1470	Valve Connection Type	Style
03.0435NOS	Twin Clip-on	Closed Ends

Fluid-Air Components Ltd

TYRE INFLATION EQUIPMENT

AIR CONTROL JWL Air Boy®

new product

Car Tyre Inflator

Maximum Working Pressure:
12 bar



With Clamping Nipple, 1/4" BSPP Inlet

1307	Gauge Ø mm
150120-134	63
150130-134	80
Tech Sheet 20437	



Maximum Working Pressure:
12 bar

With Twin Connector, 1/4" BSPP Inlet

1307	Gauge Ø mm
150123-134	63
150131-134	80
Tech Sheet 20437	

QT Connector for airtight connection

- New cars are fitted with TPMS valves, which requires precise air pressure in the tyre and here the QT Connector is the right solution. It is light and simple to connect and is completely airtight even at 9 bar.
- QT Connector has been tested for over 100,000 activations and is still completely airtight and fully functional.
- You can easily and simply connect the QT Connector to the valve with one push. Pull back the locking ring to release it again.



Tyre Inflator with QT Connecto

1307	Gauge Ø mm
151120-134	63

Precise - Air Boy® eXact
The high measuring accuracy - 0.01 bar combined with the airtight QT-Connector makes the Air Boy® eXact the perfect choice for inflating tyres with TMPS valves.

Durable - Air Boy® eXact
The electronics are protected from impact and the strong construction withstands a free fall from even 2 metres on a concrete floo . Thoroughly tested and approved by Force Technology. Significantly better than the stringent DS/EN 12645:2014 standard for inflating guns. IP65 Approved.



Ergonomic - Air Boy® eXact
The display is easy to read with large numbers and backlighting. Optimal in both left and right hand. Easy to hang from your belt with the inbuilt "eye".

Calibrated - Air Boy® eXact
All guns are individually tested and come together with a calibration certificate. The Air Bo ® eXact measures tyre pressures in the range of 0.2 to 10 bar with a resolution of 0.01 bar.

Air Boy® eXact Digital Inflating Gun with QT Connecto , 1/4"

1307	Gauge
156100-134	Digital

The QT connector is extremely airtight when connected. No air is leaking from the QT connector - even at 9 bar/130 PSI. A tight connection is a must for an accurate pressure reading and with TPMS sensors on all new cars an accurate measurement is more important than ever.

Working Temperature:
-20°C to +60°C

Maximum Working Pressure:
16 bar, 232 PSI



QT Connector

1307	Connection
116002	Internal 1/4"
116021	3/16" (5.5mm) Hose
116022	1/4" (6.5mm) Hose

TYRE INFLATION EQUIPMENT

PCL's handheld tyre inflation products are recognised internationally as the brand to bu , due to their reputation for speed, safety and ease of use and readability.

AIRFORCE MK4 Air Line Gauges (Open End)

A new and improved version of the highly regarded MK3 tyre inflato .

- Open-end: unvalved (air straight through)
- Hold-on: hold onto valve to inflat
- Clip-on: clip slides down to hold on to valve to inflat
- Supplied with a certificate of calibratio



2 YEARS EXTENDED WARRANTY

MK4

Inflation pressures up to 138 PSI / 9.6 bar

7001	Hose Length	Connector
AFG4H03	0.53m (21")	Twin Hold-on Connector
AFG4H04	0.53m (21")	Single Clip-on Connector
	Tech Sheet 60250	

MK4 Tyre Shop

Inflation pressures up to 138 PSI / 9.6 bar

7001	Hose Length	Connector
AFG4H05	1.8m (6ft)	Twin Clip-on Connector
AFG4H06	2.7m (9ft)	Twin Clip-on Connector
AFG4H061	2.7m (9ft)	Single Clip-on Connector
	Tech Sheet 60250	

Forecourt

Inflation pressures up to 138 PSI / 9.6 bar

7001	Hose Length	Connector
AFG4H031	0.36m (14")	Short Stem Twin Hold-on

Truck

Inflation pressures up to 174 PSI / 12 bar

7001	Hose Length	Connector
AFG5H36	3.6m (12ft)	Twin Clip-on
	Tech Sheet 60250	

High Pressure

Inflation pressures up to 300 PSI / 21 bar

7001	Hose Length	Connector
AFG6H04	1.8m (6ft)	Single Clip-on

ACCURA MK4 Digital Tyre Inflato

The ACCURA MK4 tyre inflator marries the ruggedness of a metal analogue inflator wit the lightness, accuracy and ease of use of a digital gauge.

Features:

- Extremely robust aluminium body with protective rubber bumper
- Permanently backlit in use, auto off after 25 seconds no-use (easy to read in dark workshops or at night)
- Three units of calibration toggle as standard (PSI, bar and kPa)
- The lightest digital inflator on the marke
- Higher pressure range for multiple applications
- Individually tested and certified against national approved gauge

Inflation pressures up to 250 PSI / 17.2 bar / 1723 kPa

2 YEARS EXTENDED WARRANTY



7001	Connection	Hose Length
DAC403	Twin Hold-on	0.53m (21")
DAC404	Single Clip-on	0.53m (21")
DAC405	Twin Clip-on	1.8m (6ft)
DAC406	Twin Clip-on	2.7m (9ft)
DAC4061	Single Clip-on	2.7m (9ft)
DAC436	Twin Clip-on	3.6m (12ft)

Analogue AirForce II Handheld Tyre Inflato

Featuring a user-friendly dial display for fast, trouble-free tyre inflation, the AirForce II, with its high performance mechanical dial, boasts industry-standard EC Directive BS EN12645:2014 approvals and certifications for accurac , reliability and robustness.

Inflation pressures up to 170 PSI / 12 bar



7001	Hose Length	Connector
AFG1H08	1.8m (6ft)	Euro Clip-on
AFG1H03	0.53m (21")	Twin Hold-on

Digital ACCURA 1 Handheld Tyre Inflato

PCL's ACCURA 1 broke the mould for handheld units, merging ease of use and readability with rapid, safe and cost-effective tyre inflation

Inflation pressures up to 174 PSI / 12 bar



7001	Hose Length	Connector	Calibration
DAC1C08	1.8m (6ft)	Euro Clip-on	0-12 bar
DAC1A06	2.7m (9ft)	Twin Clip-on	0-174 PSI
DAC1A03	0.53m (21")	Twin Hold-on	0-174 PSI

Alloy Tyre Inflato

This general purpose tyre inflato , with its durable, alloy body and rubber protected gauge, is ideal for lower volume and non-commercial applications.



7001	Hose Length	Connector
ADTG4	0.85m	Euro Clip-on

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

TYRE INFLATION EQUIPMENT

Tyre Valve Connectors

- Open end: unvalved (air straight through)
- Closed end: valved (operates when valve opens tyre valve)
- Hold-on: hold onto valve to inflat
- Clip-on: clip slides down to hold onto valve to inflat



7001	Description
CO1A03	Twin Hold-on Connector (Open End)
CO1B03	Twin Hold-on Connector (Closed End)
CO3A03	Twin Clip-on Connector (Open End)
CO3B03	Twin Clip-on Connector (Closed End)
CO8E72	Euro Style Single Clip-on Connector (Open End) for 4.75mm (3/16") Bore Hose

Straight, Single Clip-on Air Connectors

Features and Benefits

- Once the new PCL Air Connector is on, it stays on - no air leakage
- Simple but effective thumb push button - quickly releases the tyre valve, reducing non-value added time
- 360° swivel motion
- Simply turn clockwise to achieve even more grip
- Open end connector
- Suitable for use in tyre shops



Hose Tailpiece **Inlet**

7001	Thread Size
CH2K01	7.9mm, 5/16" Bore Hose
CH2H01	6.35mm, 1/4" Bore Hose
CH2A01	1/4" BSPP Inlet

Angled, Single Clip-on Air Connectors



Hose Tailpiece **Inlet**

7001	Thread Size
CH4K01	7.9mm, 5/16" Bore Hose
CH4H01	6.35mm, 1/4" Bore Hose
CH4A01	1/4" BSPP Inlet

Tyre Pressure Gauges

Includes integral pocket clip and removable protective cap.

- Complies to BS EN12645:2014
- Accuracy +/- 2 PSI



Pocket Service Type, Dual Calibrated

7001	Calibration	Resolution
TPG4H01	10-120 PSI / 0.8-8.2 bar	2 PSI / 0.2 bar

Includes integral pocket clip and removable protective cap.

- Complies to BS EN12645:2014
- Accuracy +/- 2 PSI



Pocket Type, Angled Head, Dual Calibrated

7001	Calibration	Resolution
TPG3H07	10-120 PSI / 0.8-8.2 bar	2 PSI / 0.2 bar
TPG1H07	6-50 PSI / 0.5-3.4 bar	1 PSI / 0.1 bar

Tread Depth Gauge

PCL's "Made in Sheffield" yre Tread Depth Gauge is manufactured to stringent quality standards and is DVSA (previously VOSA) MOT centre approved.



7001	Description
TDG16C05	1.6mm Marking


PCL Dial Type Tyre Gauge

Designed for simplicity and convenience of use, the dial type "TyreCheck" pressure gauge is the professional's choice of dial pressure gauge for fast, clear and accurate readings.



7001	Description
DPG1H08	0-170 PSI & 0-12 bar, Euro Clip-on Connector

Fluid-Air Components Ltd



Transair: Modular Pipe Systems

- Lower pressure drop
- Air quality class 1-1-1
- Safest connection technologies
- Labour and installation time reduced
- Services to support your project



Parker

ENGINEERING YOUR SUCCESS.

1726

FAC
Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

1	Hydraulics	3-284
2	Hydraulic Quick Release Couplings	285-320
3	Pneumatic Quick Release Couplings	321-406
4	Monitor & Test	407-446
5	Pneumatic & Vacuum	447-762
6	Push-in Fittings & Tubing	763-918
7	Valves & Actuation	919-1060
8	Ring Main	1061-1136
9	Hose Tails, Adaptors, Fittings & Manifolds	1137-1224
10	Stainless Steel	1225-1332
11	Malleable Iron	1333-1398
12	Hose, Couplings, Ducting & Hose Reels	1399-1510
13	Clips & Clamps	1511-1558
14	Paint, Sprays & Adhesives	1559-1590
15	Blow Guns, Vacuum & Nozzles	1591-1616
16	Fuelling, Lubrication, Wash Down & Misting	1617-1696
17	Compressors & Air Tools	1697-1726
18	**Hand Tools & PPE**	**1727-1765**

SECTION 18

Hand Tools & PPE

18.01	Hand Tools	**1727-1749**
18.02	PPE & Safeguarding Equipment	**1750-1765**

Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

SECTION 18 Hand Tools & PPE

18.01 Hand Tools

1727-1749

- Industrial Grade Hand Tools
- Torches Work Lamps & Lighting
- Professional Tools
- Interchangeable Storage & Display System



18.02 PPE & Safeguarding Equipment

1750-1765

- PPE & Safeguarding Equipment
- Industrial Cleaning Equipment
- Engineering Consumables



Fluid-Air Components Ltd

Industrial Grade Hand Tools

TOTAL

Tools designed for ergonomic comfort, ease of use and manufactured to last

- Contoured for effortless performance with textured hard-wearing rubber for an incredibly comfortable grip
- Rigorous testing ensures a superior quality tool every time
- Exceptional quality, competitively priced
- Once you use Total Tools, no other brand will compare

Cutting & Grinding



Wire Cup Brush, 100mm

0455	Wire Diameter mm	Thread
TAC31041	0.3	M14 x 2



Twist Wire Cup Brush, 100mm

0455	Wire Diameter mm	Thread
TAC32041	0.5	M14 x 2



Turbo Diamond Disc Wet & Dry Cut

0455	Diameter mm
TAC2131151	115

Drill Accessories



M2 HSS Individual Drill Bits

0455	Diameter mm	Total Length mm	Useable Length mm
TAC110401	4	75	43
TAC110601	6	93	57
TAC111001	10	133	87
TAC111201	12	151	101
TAC111301	13	151	101

- 6 x HSS twist drill bits, 2, 3, 3.5, 4, 5 and 6mm
- 4 x masonary drill bits, 4, 5, 6 and 8mm
- 6 x 25cm screwdriver bits, SL4.5, SL5.5, PH1, PH2, PZ1 and PZ2
- Packed in a double blister



Drill & Screwdriver Bits Box Set, 16 Pieces

0455	Size mm
TACSD3165	2-6

- 19 x HSS Twist Drill bits: 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5mm, 6, 6.5, 7, 7.5, 8, 8.5, 9, 9.5 and 10mm.
- Packed in a plastic box



19 Piece HSS DIN 338 Twist Drill Bits Set

0455	Size mm
TACSD0195	1-10

- 6 x metal drill bits: 2, 3, 4, 5, 6, 8mm
- Packed in a plastic box



6 Piece HSS DIN 338 Twist Drill Bits Set

0455	Size mm
TACSD0065	2-8

- 5 x SDS PLUS Drill bits: 6 x 110mm, 8 x 110mm, 10 x 110mm, 10 x 160mm and 12 x 160mm.
- Packed in a plastic box



5 Piece Hammer SDS Drill Bits Set

0455	Size mm
TAC190501	6 x 110 to 12 x 160

- 5 x Masonry Drill bits: 5 x 85mm, 6 x 100mm, 6.5 x 120mm, 8 x 120mm, 10 x 120mm
- Packed in a plastic box



5 Piece Masonry Drill Bits Set

0455	Size mm
TACSD5051	5 x 85 to 10 x 120

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL GRADE HAND TOOLS

Jig Saw Blades

- Metal Progressive HSS Wavy set.
- 5 x for Metal
- 12 TPI



Metal Jig Saw Blade Set, 5 Pieces

0455
TAC51118B

- Metal Fast cut HSS Wavy set.
- 2 x for Wood 8 TPI, 2 x for Metal 12 TPI, 2 x for Aluminium 8 TPI.



Assorted Jig Saw Blade Set, 5 Pieces

0455
TAC51051

Hole Saw Set

- Sizes: 20, 22, 25, 32, 35, 38, 44, 48 and 50mm
- 2 piece hole saw arbours
- Supplied in a strong aluminium case




Bi-metal, 12 Pieces

0455	Size mm
TACSH1121	20-50

Hacksaws


- Material: heavy-duty steel frame, aluminium/ABS/TPR handle
- Strong and comfortable with adjustable tension
- Quick release blade changing mechanism
- 1 x 65Mn saw blade



Heavy-duty

0455	Frame Size
THT54106	12"

- Length: 12" (300mm)
- Adjustable handle frame with soft grip
- 1 x 65Mn saw blade
- Supplied on paper card



Standard

0455	Frame Size
THT54166	12"

Saw



12" Back Saw

0455	TPI
THT59126B	11

- Size: 300 x 140 x 80
- Thickness: 20mm
- 1 piece back saw
- Size: 300mm/12" - 11 TPI



Mitre Box & Back Saw Set

0455
THT59126

- Size: 20" / 500mm.
- Material: Taiwan SK57TPI, Heat treated teeth.
- Triple teeth (precision ground on 3 edges).
- Two colour soft grip handle.



20" Hand Saw

0455
THT55206D

Files

- Length: 8" (200mm)
- 1 x flat steel fi
- 1 x half round steel fil
- 1 x round steel fil
- 1 x triangle steel fil
- 1 x square steel fil
- Material: T12 steel
- Packed in a double blister



File Set, 5 Pieces

0455	Length
THT918516	8"



File Set, 6 Pieces

0455	Size
THT91462	6"

Riveter

- Length: 10.5"
- Rivet sizes: 2.4, 3.2, 4.0 and 4.8mm
- Material: Aluminium alloy body



Hand Riveter

0455
THT32105

Wire Brush



0455	Length mm
THT92102	250

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL GRADE HAND TOOLS

TOTAL

Cutting Tools

- Length: 185mm
- 6 x SK5 blades
- Blade locking bolt
- Flat push button
- Material: aluminium body
- Net weight: 220g
- Packed in a double blister



Snap Off Blade Knife

0455	Blade Size mm
TG5121806	18 x 100

- 6 x SK5 blades
- Material: zinc alloy shell
- Net weight: 256g
- Packed in a double blister



Utility Knife

0455	Blade Size mm
TG5126101	19 x 61

15 Functions
- 1 x large knife
- 1 x can opener
- 1 x Phillips screwdriver
- 1 x leather punch
- 1 x bottle opener
- 1 x scissors
- 1 x needle
- 1 x slotted screwdriver
- 1 x fish scale
- 1 x hook remover
- 1 x saw
- 1 x corkscrew
- 1 x nail cleaner
- 1 x nail fil
- 1 x key ring
- Strong aluminium handle
- Length: 9.5cm
- Packed on a plastic hanger



Multifunction Knife

0455
THMFK0156



Folding Knife

0455	Blade Size mm
THT513613	19 x 61

Aviation Snips

- Material: carbon steel
- Supplied on a plastic hanger



Right Handed

0455	Length
THT523106	10"

- Material: carbon steel
- Supplied on a plastic hanger



Straight

0455	Length
THT522106	10"

Pliers

- Length: 8" (200mm)
- Material: Cr-V
- Supplied on a plastic hanger



Wire Stripping Pliers

0455	Length
THT25616	6"

Pipe Cutters

- Material: aluminium
- Packed in a double blister
- Length: 210mm



Basic PVC Pipe Cutter

0455	Range mm
THT53351	3-35

- Material: aluminium
- Packed in a double blister



PVC Pipe Cutter, Automatic Opening

0455	Range mm
THT53422	3-42



Copper & Aluminium Pipe Cutter

0455	Range mm
THT53321	3-32

Cable Cutters

- Length: 6" (154mm)
- Material: Carbon Steel



6" Cable Cutter

0455	Length
THT11561	6"

- Length: 10" (254mm)
- Material: carbon steel
- Packed in a half double blister



Heavy-duty Cable Cutter

0455	Length
THT115102	10"

- Blades Material: 65Mn
- Used for cutting copper and aluminium cable
- Not for cutting ACSR, wire rope, steel or self-supporting strand
- Cutting Area: 450mm²
- Body heat treatment, cutting edges induction quenched



Cable Cutter 36"

0455	Length
THT115242	24"
THT115362	36"

- Cr-V blade
- Black finish and polis
- TPR two colour handle



Bolt Cutter 42"

0455	Description
THT113426	Cr-V 42"

FAC Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

TOTAL

Bolt Cutters

- Length: 8" (200mm)
- Material: Cr-V



8" Mini Bolt Cutter

0455	Length
THT11386	8"


- Length: 14" (355mm)
- Material: Cr-V



14" Bolt Cutter

0455	Length
THT113146	14"

- Material: Cr-V
- Supplied in a poly bag



24" Bolt Cutter

0455	Length
THT113246	24"

Wrecking Bar



48" Wrecking Bar

0455	Size mm
THT431482	1200 x 29 x 15

Sledge Hammer



0455	Description
THT750416	10lb Sledge Hammer

Hammers

- Drop forged head and fibreglass handl



Machinist Hammer

0455	Gram
THT715006	500

- Dropped forged head and fibreglass handl



Stoning Hammer

0455	Gram
THT7215006	1500

- Drop forged head and fibreglass handl



All Steel Claw Hammer

0455	Weight
THT7143166	16oz/450g

- Drop forged head and fibreglass handl



Ball Pein Hammer

0455	Weight
THT74246	24oz/660g

- Fibreglass handle



Rubber Mallet

0455	Weight
THT761616	16oz/450g

- Rubber head with fibreglass handl



Dual Rubber & Plastic Hammer

0455	Size mm
THT77406	40

- Weight: 2lb
- Non-marring plastic faces
- Non-rebounding
- Non-spark



Dead Blow Mallet

0455	Description
THT79021	2lb Dead Blow Mallet

Chisels

- Material: Cr-V
- Blade width: 6, 12, 19 and 25mm



Wood Chisel Set, 4 Pieces

0455	Size mm
THT41K0401	6, 12, 19 & 25

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL GRADE HAND TOOLS

TOTAL

High Leverage Pliers

- 1 x 8" (200mm) combination pliers
- 1 x 7" (180mm) diagonal cutting pliers
- 1 x 6" (154mm) long nose pliers
- Material: Cr-V
- Supplied on a plastic hanger



Combination Plier Set, 3 Pieces

0455
THT2K0301S

- Length: 7" (180mm)
- Material: Cr-V
- Saving 30% strength against standard pliers
- Supplied on a plastic hanger



Combination Pliers

0455	Length
THT210706S	7"
THT210906S	9"

- Length: 8" (200mm)
- Material: Cr-V
- Supplied on a plastic hanger



8" Combination Pliers

0455	Length
THT210806	8"

- Length: 6" (154mm)
- Material: Cr-V
- Supplied on a plastic hanger



Long Nose Pliers

0455	Length
THT220606	6"

- Length: 8" (200mm)
- Material: Cr-V
- Supplied on a plastic hanger



Long Nose Pliers

0455	Length
THT220806S	8"

- Length: 7" (180mm)
- Material: Cr-V
- Supplied on a plastic hanger



Cutting Pliers

0455	Length
THT230706	7"

Pliers

- Length: 6" (154mm)
- Material: Cr-V
- Supplied on a plastic hanger



End Cutting Pliers

0455	Length
THT260606	6"

- Length: 8" (200mm) and 10" (254mm)
- Material: Cr-V
- Supplied on a plastic hanger



Rabbit Pliers

0455	Length
THT2881	8"
THT28101	10"

- Length: 6" (154mm)
- Material: Cr-V
- Supplied on a plastic hanger



Carpenters Pliers

0455	Length
THT290801	8"

- Length: 6" (152mm)
- Material Cr-V
- Supplied on a plastic hanger



Bent Nose Pliers

0455	Length
THT24616	6"

- Length: 10" (254mm)
- Material: Cr-V
- Supplied on a plastic hanger



Pump Pliers

0455	Length
THT281006	10"

- Material: Cr-V nickel plated
- Packed in a half double blister



Curved Jaw Locking Pliers

0455	Length
THT191001	10"


- Material: Cr-V nickel plated
- Supplied on a plastic hanger



Straight Jaw Pliers

0455	Length
THT191002	10"

- Length: 10" (254mm)
- With sharp edge for cutting and push down wire function
- Will strip 6 wire sizes and 5 copper screw sizes
- Supplied on sliding card



Wire Stripping Pliers

0455	Length
THT15101	10"

Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Wrenches


- Supplied on a plastic hanger
- 6" adjustable clamp size diameter 0-24mm
- 8" adjustable clamp size diameter 0-30mm
- 10" adjustable clamp size diameter 0-35mm
- 12" adjustable clamp size diameter 0-41mm



Adjustable Wrenches

0455	Length
THT101066	6"
THT101086	8"
THT101106	10"
THT101126	12"

- Material: heavy-duty carbon steel



90º Swedish Pipe Wrenches

0455	Description
THT172011	1"
THT172021	2"

- Body material: ductile cast iron



Pipe Wrenches

0455	Length	Max. Clamping Diameter mm
THT170806	8"	27
THT171206	12"	42
THT171186	18"	60
THT171246	24"	76
THT171366	36"	85
THT171486	48"	110

- 1 piece double open end wrench: 9-14mm, 15-22mm
- 1 piece single open end wrench, 23-32mm
- Chrome plated
- TPR two colour handle



Bent Wrench Set (2 Pieces)

0455	Length
THT10309328	2 Piece Bent Wrench Set

- Size: 10"/250mm.
- Clamping diameter: 14-40mm.
- Carbon steel.
- Black finish and polish
- Packed by poly bag.



Ratcheting Pipe Wrench 10"

0455	Length mm
THT171102	14-40

- Size: 14"/350mm.
- Clamping diameter: 18-52mm.
- Carbon steel.
- Black finish and polish
- Packed by poly bag.

Ratcheting Pipe Wrench 14"

0455	Length mm
THT171142	18-52

Screwdrivers


- Material: Nickel plated
- 10 piece set: PH2 and SL6.0 (65mm)
- Supplied in a plastic box



Double Ended Bits Set, 10 Pieces

0455
TAC16HL133

- PH1, PH2, PH3, SL4.0, SL5.5, SL6.5, PZ1, PZ2
- 1 x magnetic bit holder with quick release
- Material: S2 industrial steel, magnetic



Screwdriver Set, 9 Pieces complete with Bit Holder

0455
TACSD3091

- Material: Cr-V
- Size: 3/6mm, 6/8mm, 8/11mm, 11/14mm, and 14/18mm
- Supplied in a plastic box



Screw Extractor, 5 Pieces

0455
TACSE0051

- Material: Cr-V



Phillips Head

0455	Size	Diameter mm	Length mm
THT22386	PH2	6	38

Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Screwdrivers


- Material: S2 industrial steel



Go-thru Screwdriver, Slotted Head

0455	Size mm	Length mm
THTGTS8200	8.0	200

- Material: Cr-V
- 1 x SL6.5 - 6" (125mm)
- 1 x Phillips PH2 - 6" (125mm)
- Supplied on a plastic hanger



Screwdriver Set, 2 Pieces

0455
THT250201

- Material: Cr-V
- 1 x SL5.5 (75mm) 1 x SL5.5 (100mm) 1 x SL6.5 (150mm) 1 x PH1 (75mm) 1 x PH1 (100mm) and 1 x PH2 (150mm)
- Supplied on a hanger card



Screwdriver Set, 6 Pieces

0455
THT250606

- Ergonomic comfort-grip handle
- SL2.0 x 50, SL2.5 x 50, SL3.0 x 50, PH00 x 50, PH0 x 50, T6 x 50, T8 x 50
- Material: Cr-V



Precision Screwdriver Set, 7 Pieces

0455
THT250726

- Material: Cr-V
- 1 x SL3.0 (75mm), 1 x SL5.5 (100mm), 1 x SL6.5 (150mm) 1 x SL6.5 (38mm), 1 x PH0 (75mm), 1 x PH1 (75mm), 1 x PH2 (125mm) and 1 x PH2 (38mm)
- Supplied on a hanger card



Screwdriver Set, 8 Pieces

0455
THT250608

- Material: Cr-V
- 1 x SL3.0 (75mm), 1 x SL4.0 (100mm), 1 x SL5.5 (125mm), 1 x SL6.5 (150mm), 1 x SL8.0 (200mm), 1 x SL6.5 (38mm), 1 x PH0 (60mm), 1 x PH1 (80mm), 1 x PH2 (100mm) and 1 x PH3 (150mm)
- Supplied on a hanger card




Screwdriver Set, 10 Pieces

0455
THT250610

8 piece screwdrivers:
- SL5.5 (75mm), SL6.5 (100mm), SL8.0 (150mm), SL6.5 (38mm), PH1 (75mm), PH2 (100mm), PH3 (150mm) and PH2 (38mm)

10 piece precision screwdrivers:
- SL1.5 x 50, SL2 x 50, SL2.5 x 50, SL3 x 50, PH000 x 50, PH00 x 50, PH0 x 50, T6 x 50, T8 x 50 and T10 x 50
- Supplied in a blow moulded case



Screwdriver & Precision Screwdriver Set, 18 Pieces

0455
THT250618

Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Screwdrivers

- 1000V VDE
- Material: Cr-V



Insulated Screwdriver, Slotted Head

0455	Size mm	Length mm
THTIS4100	4.0	100
THTIS5125	5.5	125

- 6 pieces insulated screwdriver set:
  1 x SL3.0 (75mm), 1 x SL4.0 (100mm), 1 x SL6.5 (150mm),
  1 x PH0 (60mm), PH1 (80mm), PH2 (100mm)
- Aluminium frame
- Round shank



Insulated Screwdriver Set, 6 Pieces

0455
THTIS566

- Folding Handle,
- High quality ratchet mechanism.
- 12 pieces 6.35 to 25mm Screwdriver bits.
- Size: SL4, SL5, SL6, SL7, PH0



13 in 1 Ratchet Screwdriver Set

0455	Description
TACSD30136	13 in 1 Ratchet Set

- Material: Cr-V
- 1 x Ratchet Holder,
- 18 x 65mm Screwdriver bit: PH0, PH1, PH2, PH3 PZ1, PZ2, PZ3, SL3, SL4, SL5, SL6, SL7 T10, T15, T20, T25 ,T27 and T30
- Sockets: 5mm, 6mm, 7mm, 8mm, 9mm and 10mm
- Supplied in a bag and double blister



Screwdriver & Bit Set, 26 Pieces

0455
TACSD30266

- 1 x 7 in 1 unique design industrial ratchet handle
- 20 x 6.35 x 25mm screwdriver bits, SL3, SL4, SL5, SL6 x 2, PH0, PH1, PH2, PH3, PZ1, PZ2, T10, T15, T20, T25, T30, HEX3, HEX4, HEX5
- 1 x 4-6mm (25mm) bits adaptor
- 9 x 1/4" x 20.5mm sockets, 4, 5, 6, 7, 8, 9, 10, 11 and 12mm
- 1 x 125mm strong magnetic bits holder
- 1 x 75mm strong magnetic bits holder
- Supplied in a plastic box



Screwdriver & Bit Set, 33 Pieces

0455
TACSD30336

- 1 x T-handle ratchet wrench
- 9 x 6.35 x 25mm screwdriver bits, SL4, SL5, SL6, PH1, PH2, PH3, PZ1, PZ2, PZ3
- 1 x 5 x 100mm strong magnetic bit holder
- 1 x 4-6mm (25mm) adaptor
- 6 x 1/4" sockets, 5, 6, 7, 8, 9 and 10mm
- Supplied in a plastic box



T-handle Wrench Screwdriver Set, 18 Pieces

0455
TACSD30186

- Material: Cr-V
- 20 x 6.35 x 25mm screwdriver bits: PH0, PH1, PH2, PH2, PH3.SL3, SL4, SL5, SL6, SL8. HEX3, HEX4, HEX5.PZ1, PZ2.T10, T15, T20, T25 and T30
- 1 x 4-6mm (25mm) bits adaptor.
- 1 x 1/4"-3/8" socket adaptor.
- 1Pcs 125mm magnetic bits holder.
- 1Pcs 75mm magnetic bits holder.
- 1 x industrial ratchet.
- Supplied in a plastic box



T Handle Wrench Screwdriver Set, 25 Pieces

0455
TACSD30256

Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Hexagonal Keys

- Material: Cr-V
- Heat treated and chrome plated



Metric Pocket Pack, 8 Pieces

0455	Size mm
THT1061826	2-8

- Material:Cr-V.
- Size:1.5 - 10mm.
- Long arm.
- Heat treated and chrome plated.
- Packed by double blister.



Long Arm, Hex Key Set, 9 Pieces

0455	Size mm
THT106191	Cr-V 1.5-10mm

- Material: Cr-V
- Heat treated and chrome plated



Ball Point Pocket Pack, 8 Pieces

0455	Size mm
THT1061836	2-8


- 9 x keys, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0 and 10mm
- Material: Cr-V
- Heat treated and chrome plated



Ball Point Long Arm Set, 9 Pieces

0455	Size mm
THT106291	1.5-10

- Material: Cr-V Size: 1.5-10mm
- Extra-long arm
- Heat treated and chrome plated



9 Piece Ball Point Hex Key Set Extra Long Arm

0455	Size mm
THT106292	1.5-10

- 9 x keys, T10, T15, T20, T25, T27, T30, T40, T45 and T50
- Material: Cr-V
- Heat treated and chrome plated



Torx Key Long Arm Set, 9 Pieces

0455	Size
THT106391	T10-T50

Socket Sets

1/2" drive (33 pieces)

- 19 x 1/2" hex sockets, 8, 10, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 27, 30 and 32mm
- 5 x 1./2" star sockets, W10, E12, E14, E16, E20
- 1 x 1/2" flex handle, 375m
- 2 x 1/2" extension bars, 75mm (3"), 250mm (10")
- 1 x 1/2" universal joint
- 1 x three way adaptor 1/2" to 3/8"
- 2 x spark plug sockets, 16 and 21mm
- 1 x 1/2" L-handle, 250mm (10")
- 1 x 1/2" ratchet wrench (45T)

3/8" drive (19 pieces)

- 15 x 3/8" 12 point sockets, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 17, 18, 19, 21 and 22mm
- 2 x 3/8" extension bars 75mm (3"0, 150mm (6")
- 1 x 3/8" universal joint
- 1 x 3/8" ratchet wrench (45T)

1/4" drive (49 pieces)

- 26 x 1/4" screwdriver bits (25mm) PH0, PH1, PH2, PH2, PH3, PZ0, PZ1, PZ2, PZ3, SL4, SL5.5, SL7, H2, H3, H4, H5, H6, H7, H8, H10, T10H, T15H, T20H, T25H, T27H, T30H and T40H
- 1 x bit holder
- 9 x 1/4" hex sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9 and 10mm
- 5 x 1/4" star sockets E4, E5, E6, E7 and E8
- 3 x 1/4" extension bars 50mm (2"), 100mm (4"), 150mm (6")
- 1 x 1/4" universal joint
- 1 x three way adaptor 3/8" to 1/4"
- 1 x 1/4" spinner handle, 150mm
- 1 x 1/4" flexible extension ba , 150mm
- 1 x 1/4" ratchet wrench (45T)

Other tools (41 pieces)

- 17 x combination spanners, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22 and 24mm
- 5 x flare nut spanners, 8 x 10, 10 x 12, 11 x 13 12 x 14 and 17 x 19mm
- 10 x hex keys, 2.5, 3, 4, 5, 6, 7, 8, 10, 12 and 14mm
- 1 x machinist hammer, 300g
- 1 x combination pliers, 7"
- 1 x curved jaw lock pliers, 10"
- 2 x slotted screwdrivers (S2), SL6.5 x 100mm, SL6.5 x 150mm
- 2 x Phillips screwdrivers (S2), PH2 x 100mm, PH2 x 150mm
- 2 x stubby screwdrivers, PH2 x 38mm, SL6.5 x 38mm
- Supplied in a blow moulded carry case



Combination Socket Set, 142 Pieces

0455
THKTHP21426

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL GRADE HAND TOOLS

Socket Sets



162 Piece Tool Chest Set

0455	Description
THPTCS71621	162 Piece Mobile Tool Chest



120 Piece Tools & Accessories

0455
THKTAC01120

- 13 x 1/4" sockets, 4, 4.5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 and 14mm
- 1 x 1/4" universal joint
- 2 x 1/4" extension bars, 50mm (2"0, 100mm (4")
- 1 x 1/4" spinner handle, 150mm
- 1 x 1/4" ratchet wrench (45T)
- 20 x screwdriver bits, PH1, PH2, PH3, PZ1, PZ2, PZ3, SL4, SL5, SL6, H1.5, H2, H3, H4, H5, H6, T10, T15, T25, T30
- 1 x screwdriver bits holder
- 1 x 1/4" flexible extension ba , 150mm
- 1 x 1/4" sliding T-bar, 114mm
- 4 x hex key wrench, 1.5, 2.0, 2.5, 3.0mm
- Material: Cr-V (50BV30), heat treated
- Supplied in a blow moulded carry case



1/4" Drive Socket Set, 45 Pieces

0455	Size mm
THT141451	4-14

1/4" drive sockets

- 13 x 1/4" sockets, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 and 14mm
- 1 x 1/4" universal joint
- 2 x 1/4" extension bars, 50mm (2"), 100mm (4")
- 1 x 1/4" sliding T bar, 114mm
- 1 x 1/4" flexible extension ba , 150mm
- 1 x 1/4" ratchet wrench (45T)

1/2" drive sockets

- 18 x 1/2" sockets, 8, 10, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30 and 32mm
- 1 x 1/2" universal joint
- 2 x 1/2" extension bars, 125mm (5"), 250mm (10")
- 1 x 1/2" sliding T bar, 250mm (10")
- 2 x spark plug sockets, 16 and 21mm
- 1 x 1/2" ratchet wrench (45T)
- Supplied in a blow moulded carry case



1/4" & 1/2" Drive Socket Set, 44 Pieces

0455	Size mm	Size mm
THT421441	10-24 (1/4")	8-32 (1/2")

- 10 x 1/2" sockets, 10, 11, 12, 13, 14, 15, 17, 19 and 24mm
- 1 x 1/2" quick release soft grip ratchet wrench (72T)
- 1 x 1/2" extension bar, 125mm (5")
- Supplied on a plastic hanger



1/2" Drive Socket Set, 12 Pieces

0455	Size mm
THT141121	10-24

- 18 x 1/2" sockets, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30 and 32mm
- 1 x 1/2" universal joint
- 2 x 1/2" extension bars, 125mm (5"), 250mm (10")
- 2 x spark plug sockets, 16 and 21mm
- 1 x 1/2" ratchet wrench (45T)
- Material: Cr-V (50BV30), heat treated
- Supplied in a blow moulded carry case



1/2" Drive Socket Set, 25 Pieces

0455	Size mm
THT121251	10-32

Socket Drives

- (45T)
- Material: Cr-V + Cr-Mo
- Supplied on a plastic hanger



Rachet Wrench

0455	Size	Length mm
THT106146	1/4"	158
THT106386	3/8"	205
THT106126	1/2"	260

Socket Sets



1/2" Drive 6 Point Sockets

0455	Size mm
THTST12131	13
THTST12211	21
THTST12321	32

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL GRADE HAND TOOLS

Spanner Sets

- 6, 8, 10, 12, 14, 15, 17 and 19mm
- Fine polished
- Supplied on a plastic hanger



Combination Spanner Set, 8 Pieces

0455	Size mm
THT102286	6-19

- 6, 8, 10, 11, 12, 13, 14, 15, 17, 19, 22 and 24mm
- Fine polished
- With roll pouch



Combination Spanner Set, 12 Pieces

0455	Size mm
THT1022121	6-24

- 6, 8, 10, 12, 12, 14, 17, 19, 22, 24, 27, 30 and 32
- Fine polished
- With roll pouch



Combination Spanner Set, 12 Pieces

0455	Size mm
THT1022122	6-32

- 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 27, 25 x 28 and 30 x 32mm
- Fine polished
- With roll pouch



8 Piece Double Open End Spanner Set 6-22mm

0455	Size 1	Size 2
THT102386	6 x 7, 8 x 9, 10 x 11, 12 x 13 mm	14 x 15, 16 x 17, 18 x 19, 20 x 22 mm

- 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 27, 25 x 28 and 30 x 32mm
- Fine polished
- With roll pouch



Double Open End Spanner Set, 12 Pieces

0455	Size mm
THT1023121	6-32

- 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19 and 20 x 22mm
- Fine polished
- Supplied on a plastic hanger



Offset Ring Spanner Set, 8 Pieces

0455	Size mm
THT102486	6-22

- 6 x 7, 8 x 9, 10, x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 27, 25 x 28 and 30 x 32mm
- Fine polished
- With roll pouch



Offset Ring Spanner Set, 12 Pieces

0455	Size mm
THT1024121	6-32

- 19, 22, 24, 27, 30 and 32mm
- Fine polished Cr-V
- With canvas bag




Ratchet Spanner Set, 6 Pieces

0455	Size mm
THT102RK061	19-32

Measuring Equipment


- 3 stop button function
- Metric and inch display
- Rubber cover



Steel Tape Measure

0455	Length Metres	Width mm
TMT126031	3	16
TMT126052	5	25
TMT126101	10	25

- Reading: 0.01mm metric/inch system conversion in any position
- Supplied in a plastic box




Digital Caliper

0455	Range mm
TMT321501	0-150
TMT322001	0-200

FAC
Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Clamps



Bench Vice


0455	Maximum Force Kgs
THT6146	1300
THT6186	2500

- Body material: malleable cast iron
- Thread: T-shaped
- Supplied in a poly bag



G Clamp

0455	Size
THT13141	4"
THT13161	6"



- Clamp size: 50 x 200mm
- Max clamp force: 170kgs
- Thickness and width of iron ruler: 5 x 15mm
- Diameter of screw thread : 11mm

F Clamp, 200mm

0455	Size mm	Force Kgs
THT1320502	200	170

- Clamp Size: 80 x 300mm
- Max Clamp Force: 270kgs
- Thickness and Width of Iron Ruler: 6 x 22mm
- Diameter of Screw Thread: 13mm

F Clamp, 300mm

0455	Size mm	Force Kgs
THT1320801	300	270

- Clamp size: 140 x 1000mm
- Max clamp force: 450KGS
- Thickness and width of iron ruler: 8 x 30mm
- Diameter of screw thread:15.3mm

F Clamp, 1000mm

0455	Size mm	Force Kgs
THT1321401	1000	450

Spirit Levels

- Double side milled
- 0.5mm/m accurate vials
- Aluminium thickness: 1.5mm
- Fitted with 3 powerful magnets
- Double flat surface desig



Magnetic

0455	Length cm
TMT21005M	100

Tool Box

- 495 x 200 x 290mm



Metal Cantilever Tool Box

0455
THT10701

Flashlight

- Material: Aviation grade aluminium alloy: 6N01-T6
- U.S.A. manufactured CREE XPE2 R3 LED 3W
- Lumen: 135
- Beam distance: 200m
- Lifespan: 100000 hours
- Batteries: 3 x AAA
- Runtime: 5 hours
- Tail light switch
- Waterproof grade: IPX-4
- Weight: 105g (without batteries)



Aviation Grade

0455	Diameter mm	Length mm
TFL013AAA1	32	126.5



Headlamp

0455
THL013AAA2

For **Malleable Iron Fittings** see pages **1338-1376**



Fluid-Air Components Ltd

INDUSTRIAL GRADE HAND TOOLS

Grease Gun

- Capacity: 400cc/14oz
- Loading: 14oz cartridge/400cc bulk
- Working pressure: 4500 - 10,000psi
- Burst pressure: 14000psi
- Material: 1.2mm steel tube and aluminium casting
- Standard accessories: 1 x 12" high pressure flexible nylon hose, 1 x metallic bend spout



Heavy-duty

0455
THT111051

Tool Pouches & Bags

- Reinforced plastic base
- Adjustable shoulder strap



24" Rigid Frame Tool Bag

0455
THT16241

- Adjustable belt: 92 -127cm



Single Tools Pouch

0455	Adjustable Belt cm
THT16P2031	92-127



Single Tools Pouch

0455
THT16P1011

Gloves

- For use in an oil environment
- Nitrile coated palm, smooth and rough texture finis
- Packed in a poly bag



Nitrile Gloves XL

0455	Size
TSP12101	10

TORCHES WORK LAMPS & LIGHTING

Redashe Rechargeable Slim Work Light

Features:

- Dimmable operational switch to create a floodlight or focused bea
- Swivelling base with strong built-in scratch proof magnet
- Smooth wand pivot of up to 150°
- Lamp body rotates up to 270°
- Charging time: Approx. 3 hours
- Minimum operation time: 2 hours
- Ergonomic and comfort grip handle
- Micro USB weatherproof charging point complete with charging indicator

new product



Redashe 1 YEAR WARRANTY

0478	Colour
JETW007R	Red
JETW007G	Green
JETW007Y	Yellow
Tech Sheet 71697	

Redashe Rechargeable Headlamp

Features:

- Adjustable zoom headlamp for spotlight or floodlight application
- Infrared manual sensor system for a more convenient operation
- Lithium-ion rechargeable battery for longer life and consistent power
- Built-in battery level indicator on the front of the headlamp
- The lamp head can be adjusted 80° up and down
- Non-slip elastic head strap

new product

Redashe 1 YEAR WARRANTY



0478	Lumens
JK120	400

Intrinsically Safe Polymer Penlight

new product



0712	Lumens	Beam
JXPP-5422B	120	170 Metres

Fluid-Air Components Ltd

the job right the first time, every time. RIDGID Pipe Wrenches are also available in a wide variety of purpose-built configurations, and are available with cast aluminum handles that offer an average 40% weight reduction.

PROFESSIONAL TOOLS

RIDGID® pipe wrenches are world-renowned for their unsurpassed toughness and serviceability. The original heavy-duty pipe wrench, pictured here, has earned the confidence of pipe professionals for over 80 years because it does the job right the first time, every time.

RIDGID® pipe wrenches are also available in a wide variety of purpose-built configurations, and are available with cast aluminium handles that offer an average 40% weight reduction.



Pipe Wrenches

- Sturdy, cast-iron housing
- I-beam handle
- Full floating forged hook ja
- Self cleaning threads with replaceable hook and heel jaws



Heavy-duty Pipe Wrenches

0494	Ø mm	Length mm	Model	Kg
31020	50	350	14	1.6
31025	65	450	18	2.6
31030	80	600	24	4.4
Tech Sheet 60448				


- Features a jaw opening parallel to the handle and a narrower hook jaw head
- Provides easy entry into tight spots



Heavy-duty Offset Pipe Wrenches

0494	Ø mm	Length mm	Model	Kg
89445	80	600	24	4.4
Tech Sheet 60448				

- Jaws and all other parts identical to RIDGID® heavy-duty wrenches
- All the great benefits of the heavy-duty RapidGrip wrenc
- Professional strength in lightweight aluminium
- Nearly 40% lighter than comparable cast iron wrenches
- 35% lighter than heavy-duty models
- Ideal for overhead applications
- Offers the same durability and ease-of-use found in all RIDGID® heavy-duty wrenches



Aluminium Pipe Wrenches

0494	Ø mm	Length mm	Model	Kg
31095	50	350	814	1.1
31100	65	450	818	1.7
31105	80	600	824	2.7
Tech Sheet 60448				

- Features a jaw opening parallel to the handle and a narrower hook jaw head
- Provides easy entry into tight spots



Aluminium Offset Pipe Wrenches

0494	Ø mm	Length mm	Model	Kg
31120	50	350	14	0.9
31125	65	450	18	1.6
31130	80	600	24	2.7
Tech Sheet 60448				

Fluid-Air Components Ltd

PROFESSIONAL TOOLS

RIDGID

new product

Cutting Tool

PC 116 Powered Tubing Cutter

This 4.5" machine saves time and effort thanks to its fast set-up and operating features:

- Quick size adjustment
- Quick-feeding mechanism
- Spark-free
- Cold cutting

High-strength alloy wheels with tool-free replacement. It delivers consistent and accurate cutting in a wide variety of materials, such as:

- Stainless steel
- Steel
- Coated steel
- Aluminium
- Copper



PC116 Powered Tubing Cutter

0494	Capacity mm	Description
68118	12-116	With Plastic & Metallic Cutter Wheels, 110V
70003	12-116	With Plastic & Metallic Cutter Wheels, 230V

Cutting Tool Accessories



PC116 Tube Cutting Stand

0494
64903



PC116

0494	Description
66938	Cutter Wheel without Bearing for Carbon Steel, Stainless Steel & Aluminium.
66943	Cutter Wheel without Bearing for Plastic & Copper.

M-Press Fittings Ltd

For **Stainless Steel Press Fit Piping System** see pages **1118-1126**



Fluid-Air Components Ltd

PROFESSIONAL TOOLS

Press Tools

RP 219 is our Next-Gen 19 kN compact press tool.



Providing the user FULL ACCESS in the most confined spaces with its Lightweight (<2 kg) and Ultra-Slim Inline Design as well as the **full flexible 350° Head Rotatio** .

RP 219 also provides the user FULL ACCESS to super-fast pressing, critical tool information, multiple power sources and a wide range of 19 kN compact press jaws.

The RP 219 also features 'Press-check!', an integrated pressure sensor that monitors and confirms every press cycle and offers the lowest cost-of-ownership.

RP 219 Kits include: Carrying case, 1 x 2.5 Ah Li-Ion battery and 1x 230V fast-charger, 1 x car charging cord

RP 219 Press Tool

0494	Description	Weight (kG)
69073	RP 219 without Press Jaws	5.2
69078	RP 219 with M15-18-22 Press Jaws	9.2
69083	RP 219 with M15-22-28 Press Jaws	9.2

The **RIDGID RP 350** features a brushless motor capable of over 100,000 press cycles and requires no scheduled maintenance. Get access to hard-to-reach locations with endless 360° swivel. The RP 350 has been upgraded from top to bottom with the most advanced LED interface and lighting.

RP 350-B Tool Kits include:
1 x 2.5Ah battery, 1 x fast-charger and Carrying Case



RP 350 Press Tool

0494	Description
67088	RP 350-B Tool Kit (No Jaws)
69818	RP 350-B Kit + M15-18-22
69823	RP 350-B Kit + M15-22-28



Jaws for M Standard Pressfit System

0494	Press Jaw Type
69868	M12
69873	M15
69878	M18
69883	M22
69888	M28
69893	M35

The **RP 351** Inline Design Press Tool is designed for speed and continued operation in the most confined spaces. Optimally balanced for one-handed use and reduced job site fatigue. Driven by the new RIDGID Brushless Motor Technology, RP 351 reaches over 100,000 press cycles and requires no scheduled maintenance.

RP 351-B Tool Kits include: 1 x 2.5AH battery, 1 x fast-charger and carrying case



RP 351 Press Tool

0494	Description
67228	RP 351-B + Case + Battery + Charger
69838	RP 351-B Tool Kit + M15-18-22
69843	RP 351-B Tool Kit + M15-22-28

The NEW **RIDGID® StrutSlayr** is the latest accessory, making the world's most popular press tool even more valuable. StrutSlayr attaches to RIDGID® 32kN press tools to deliver a fab shop quality, burr-free cut in 5 seconds or less. No grinding or sawing sparks - just a clean, consistent SHEAR cut with a pull of a trigger.

Fab Shop Quality: Burr-free cuts eliminate the need for extra filin

Increased Efficiency: Clean, consistent cuts in 5 seconds or less

Shear Cut: no grinding or sawing sparks

Portable: Easy to move around the job site and mounts to RIDGID TRISTANDs

Built-in Measuring Guide: allows the accuracy of cut-on application.



Strut Shear Head

0494	Capacity mm	Weight (Kg)	Tool Compatibility
64053	41 x 21	8.96	RP350, RP340, RP330
64058	41 x 41	8.96	RP350, RP340, RP330

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PROFESSIONAL TOOLS

Pipe/Tube Cutting & Preparation

- Specifically designed for use in restricted spaces on small diamete , hard and soft copper, aluminium, brass and plastic tubing
- Rollers include grooves for close-to-flare cut
- Strong, lightweight slide and wheel housing
- Large knurled feed screw knob gives easy control of cutting pressure for clean cuts
- Models 117 and 118 include a self-feeding cutter wheel that automatically cuts after tightening the knob once (AUTOFEED®)
- Model 118 features a special knob for easier tightening of the feed screw
- Model 101-ML is for multi-layer tubing only



Midget Cutters for Close Quarters Tubing

0494	Capacity mm	Description	Model	Kg
40617	6 -28	Midget Cutter	101	0.23
32975	3-16	Midget Cutter	103	0.15
32985	5-24	Midget Cutter	104	0.15
32933	–	Ratchet Handle only for 118 & 101 Midget Cutters	118	0.26
21938	6-28	Midget Cutter for Multilayer Tubing	101-ML	0.15
		Tech Sheet 60451		

- For plastic (PVC, CPVC, PP, PEX, PE) and multilayer tubing
- Spring-loaded handles for faster positioning
- Single stroke, easy cut
- Durable aluminium construction for heavy-duty use
- Easy attachable ML adaptor for improved multi-layer cutting and instant re-rounding of tubing



Plastic & Multi-layer Pipe Cutters

0494	Capacity mm	Description	Model	Kg
23493	6 - 25	Single Stroke Tubing Cutter	PC-1375 ML	0.34
		Tech Sheet 60451		

- Ergonomic grips on bottom handle are spaced at 1/2" increments to act as a quick pipe-measuring scale
- X-CEL® quick-change blade
- Burr-less cutting operation provides a square cut
- For plastic (PVC, CPVC, PP, PEX, PE), rubber hose and multi-layer tubing



Ratchet Cutters with Ergonomic Grips

0494	Capacity mm	Description	Model	Kg
23498	3-42	Ratchet Action Plastic Pipe & Tubing Cutter	RC-1625	0.52
		Tech Sheet 60451		

C-Style cutters cut 15mm/22mm or 28mm copper tubing while offering unique features that take copper tube cutting to a whole new level.

new product



C Style Cutter

0494	Capacity mm	Model	Kg
57018	15- 22	C15/22	0.23
60668	28	C28	0.21

FT PRO®

For **PVC Braided Hose** see pages **1402-1405**



Fluid-Air Components Ltd

PROFESSIONAL TOOLS

Pipe/Tube Cutting & Preparation

X-CEL® Means Speed

Many of our most popular tubing cutters now include several X-CEL® features to make your job quicker and easier:

- X-CEL® Knob – cut tubing more quickly and easily with our larger, more ergonomic designs
- X-CEL Wheel Pin – change your cutter wheel quickly using our new ball detent design…no tool needed…no lost clips!
- Spare cutter wheels included for maximum uptime

PIPE/TUBE CUTTING & PREPARATION

X-CEL® Means Speed

Many of our most popular tubing cutters now include several X-CEL® features to make your job quicker and easier.


- X-CEL® Knob – cut tubing more quickly and easily with our larger, more ergonomic designs
- X-CEL Wheel Pin – change your cutter wheel quickly using our new ball detent design…no tool needed…no lost clips!
- Spare cutter wheels included for maximum uptime


Enclosed Feed Tubing Cutters with New X-CEL® Features

- Telescoping feed screw design keeps the cutter at the same length regardless of tubing diameter - good for tight spaces.
- Enclosed feed screw to eliminate clogging and jamming
- Grooved rollers for close-to-flare cut
- Fold-away reamer
- Now includes X-CEL® Knob and X-CEL® Pin for quicker cutting and wheel replacement
- Made from high-strength zinc alloy
- Spare cutter wheel included in the knob
- Cuts hard/soft copper, aluminium, brass and multilayer tubes
- Model 205 / 205S have quick acting mechanism for faster size adjustments

Enclosed Feed Tubing Cutters with New X-CEL Features

- Telescoping feed screw design keeps the cutter at the same length regardless of tubing diameter - good for tight spaces.
- Features an enclosed feed screw to eliminate clogging and jamming, grooved rollers for close-to-flare cuts, and a fold-away reamer.
- Now includes X-CEL Knob and X-CEL Pin for quicker cutting and wheel replacement.
- Made from high-strength zinc alloy
- Spare cutter wheel included in the knob.
- Cuts hard / soft copper, aluminium, brass and multilayer tubes.
- Model 205 / 205S have quick acting mechanism for faster size adjustments.







Catalog No.	Model No.	Description	Std. Wheel	Capacity mm
For Copper Tubing				
66737	150L	Enclosed Feed Cutter	E-3469	6 - 35
33055	205*	Ratcheting Enclosed Feed Cutter	E3469	6 - 60
For Steel Tubing				
66742	150LS	Above with Heavy Duty Wheel	E4546	6 - 35
41070	205S**	Above with Heavy Duty Wheel	E-4546	6 - 60

Model 205 has an additional quick-acting mechanism
** Model 205S is suitable for stainless steel.

Enclosed Feed Tubing Cutters, X-CEL Features, for Copper Tube

0494	Capacity mm	Description	Model	Kg
66737	6 - 35	Enclosed Feed Cutter	150L	0.44
33055	6 - 60	Ratcheting Enclosed Feed Cutter	205L	0.91
Tech Sheet 60451				

Enclosed Feed Tubing Cutters, X-CEL Features, for Stainless Steel Tube

0494	Capacity mm	Description	Model	Kg
29963	6 - 35	Enclosed Feed Cutter	150L	0.47
31803	6 - 60	Ratcheting Enclosed Feed Cutter	205L	0.91
Tech Sheet 60451				

Pipe Bending Equipment

- Combines accuracy with easy operation
- Designed for bending copper, steel and stainless steel (≤1.5mm) to a maximum of 180°
- Offset cushion grip handles for comfort when forming 180° bends
- A 90° start angle and unique oil-absorbing shoe minimise bending effort while forming accurate bends in copper and steel tubing



400 Series Instrument Benders

0494	OD mm	Bend Radius mm	Model	Kg
36112	6	16	406M	0.68
36092	8	24	408M	1.18
36127	12	38	412M	2.45
Tech Sheet 60458				

- The stainless steel specialist
- High quality bending performance on stainless steel and other hard tubing such as steel and titanium
- Two-stage design allows for in-place bending from 90° to 180° without ever crossing handles
- Lock/unlock with a half-turn rotation of the bending handle
- Extra long 16" (40cm) handles increase leverage, and roll dies in the bending form reduce force needed
- Vice clamp built into bending form for extra stability



600 Series Heavy-duty Instrument Benders

0494	OD mm	Bend Radius mm	Model	Kg
38053	6	16	606M	0.76
38058	10	24	610M	1.84
38063	12	38	612M	2.76
Tech Sheet 60458				

Fluid-Air Components Ltd

INTERCHANGEABLE STORAGE & DISPLAY SYSTEMS

FT PRO new product

Component Organisers

Big drawer quantity: 4
Big drawer dimensions:
Length 153mm x width 127mm x height 58mm
Small drawer quantity: 8
Small drawer dimensions:
Length 153mm x width 62mm x height 37mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene



Recyclable

12 Drawer Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 12	245	293	164
Tech Sheet 20173			

Drawer quantity: 18
Drawer dimension:
Length 153mm x width 127mm x height 58mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene




Recyclable

18 Drawer Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 18	457	424	164
Tech Sheet 20173			

Big drawer quantity: 8
Big drawer dimension:
Length 153mm x width 127mm x height 58mm
Small drawer quantity: 14
Small drawer dimension:
Length 153mm x width 62mm x height 37mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene



Recyclable

22 Drawer Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 22	245	555	164
Tech Sheet 20173			

Small drawer quantity: 30
Small drawer dimensions:
Length 153mm x width 62 x height 37mm
Big drawer quantity: 9
Big drawer dimensions:
Length 153mm x width 127 x height 58mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene




Recyclable

39 Drawer Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 39	457	424	164
Tech Sheet 20173			

Drawer quantity: 60
Drawer dimension:
Length 153mm x width 62mm x height 37mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene



Recyclable

60 Drawer Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 60	457	424	164
Tech Sheet 20173			

Drawer quantity: 9
Drawer dimension:
Length 153mm x width 127mm x height 58mm
Bin quantity: 9
Bin drawer dimension:
Length 153mm x width 127mm x height 65mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene



Recyclable

9 Drawer, 9 Bins Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 9B9D	457	424	164
Tech Sheet 20173			

Drawer qty: 30
Drawer dimension:
Length 153mm x width 62mm x height 37mm
Bin drawer quantity: 30
Bin drawer dimensions:
Length 153mm x width 127mm x height 65mm
Wall mounting key holes: 4
Partition with gripper: Yes
Tight-fitted partition: Yes
Cabinet material: Polypropylene
Drawer material: Clear polypropylene




Recyclable

30 Drawer, 9 Bins Storage Cabinet

0426	Height mm	Width mm	Depth mm
V-ACO 9B30D	460	426	166
Tech Sheet 20173			

Pocket qty: 12
Side pocket Inner dimensions:
Length x 125mm x width 100mm x height 70mm
Centre pocket inner dimensions:
Length x 125mm x width 123mm x height 68mm
Wall mounting key holes: 4
Body and frame: Polypropylene
Lid: Polycarbonate



Recyclable | Body & frame | Lid

12 Pockets with Transparent Lid Storage Cabinet


0426	Height mm	Width mm	Depth mm
V-ACO 12 PTL	460	426	166
Tech Sheet 20173			

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INTERCHANGEABLE STORAGE & DISPLAY SYSTEMS

Supra Storage Bins

- Impact resistant.
- Strong rear lip for use with louvred panels. Integral label holder.
- Clear access to contents.
- Manufactured from high density polypropylene.
- High and low temperature tolerant.
- Resistant to most individual solvents.
- Easy to stack on top of each other.
- Incorporates a safety stop feature at the back in SB4/5/6 for use in shelves.



Red, Blue, Yellow or Grey


0128	Colour	Height mm	Length mm	Width mm	Pack Qty
SB-1-RED-P60	Red	60	125	100	60
SB-1-BLUE-P60	Blue	60	125	100	60
SB-2-RED-P60	Red	85	170	100	60
SB-2-BLUE-P60	Blue	85	170	100	60
SB-2-YELLOW-P60	Yellow	85	170	100	60
SB-3-RED-P50	Red	125	220	130	50
SB-3-BLUE-P50	Blue	125	220	130	50
SB-3-YELLOW-P50	Yellow	125	220	130	50
SB-4-RED-P10	Red	143	290	178	10
SB-4-BLUE-P10	Blue	143	290	178	10
SB-5-BLUE-P5	Blue	145	290	363	5
SB-6-BLUE-P10	Blue	145	440	180	10
SB-7-BLUE-P6	Blue	215	435	400	6
SB-8-BLUE-P6	Blue	300	600	425	6
Tech Sheet 20172					

Accessories – Partitions

0128	Description
HP/SB4/6	Horizontal Partition for SB-4 & SB-6
VP/SB4/5	Vertical Partition for SB-4 & SB-5
VP/SB7	Vertical Partition for SB-7
VP/SB8	Vertical Partition for SB-8
Tech Sheet 20172	

Shop Floor Stands

- Free standing stands come complete with louvred panels on one side
- Easy to assemble
- Storage bins ordered separately



Free Standing Louvred Panel Stands

0128	Length mm	Width mm	Height mm	Type
FSS/L/1	457	630	1560	Single Span
FSS/L/2	914	630	1560	Double Span
FSS/L/3	1371	630	1560	Triple Span
Tech Sheet 20170				

Ideal for component storage and transfer to assembly or production areas. Unit comprises of base unit with aluminium chequered top plate fitted with castors and a frame on which four louvre panels can be fitted (supplied).

Example: trolley can hold 16 x SB-1, 32 x SB-2, 12 x SB-3, 10 x SB-4 on the panels with the base free for different sizes of bins as per your requirement.

Storage bins not supplied.

- Robust construction
- Epoxy powder coated
- Easy assembly




Mobile Louvred Panel Stand

0128	Length mm	Width mm	Height mm
SFT	970	600	1100
Tech Sheet 20171			

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INTERCHANGEABLE STORAGE & DISPLAY SYSTEMS


FT PRO



Tool Trays

Can be screwed to walls, workstations or for use with louvred panels.

Note: tools not included.



Red, Blue or Grey

0128
TTH-RED
TTH-BLUE
TTH-GREY
Tech Sheet 20173

Multi-purpose Display Board

- 451 hanging holes
- 38 strong hooks (two sizes) and 38 locks

Note: tools not included.



Red or Blue

0128	Width mm	Height mm
MDB500-RED	505	390
MDB500-BLUE	505	390
Tech Sheet 20174		

Poly Bins & Rails

Each bin is 5" x 4" x 3".





Set of 20 Bins & 5 Rails

0128
PBR205
Tech Sheet 20175

Louvred Wall Panels

The louvred panels are made from powder-coated 1.5mm CRCA steel and come in four sizes.

These louvre panels can be easily fitted on walls or on a stand.

Note: tool tray, tools and Supra bin not included.



For Use with Supra Bins

0128	Width mm	Height mm
SB/LP1	457	457
SB/LP2	457	610
SB/LP3	457	915
SB/LP6	457	1830
Tech Sheet 20176		

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PORTWEST

On celebrating 120 years of peak protection Portwest has possessed an unrelenting ambition to produce the world's most trusted and requested protective wear. Through the decades, they have continuously proven their dedication to quality, producing world-beating safety garments, foot protection, hand protection and PPE, while pushing the boundaries in protection technologies.

Technologies that make the workplace a safer place.



1750

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRY INSPIRED DESIGN

For 120 years, Portwest's product designers have been developing a deep understanding of the safety needs of workers across many industries. This understanding has enabled them to create industry-focused safety wear solutions tailored to the specific risks faced by professionals across a multitude of industries, allowing workers to perform at the height of their ability.



Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

PPE & SAFEGUARDING EQUIPMENT

PORTWEST new product

HEAD PROTECTION

The rapidly expanding Portwest head protection range aims to benefit wearers by combining the most up-to-date styles with the highest standards in head protection, irrespective of job or location. A wide selection of compatible accessories is also available.



Head Protection

- Specially designed for working at height
- Electrical insulation up to 1000V AC or 1500V DC (EN50365)
- Unvented helmet shell for safe use with electrical applications
- 6-point textile suspension harness for enhanced wearer comfort and safety
- Size adjustable headband via wheel ratchet system
- Chin strap included



Height Endurance Helmet

0352	Colour
PS53BKR	Black
PS53ORR	Orange
PS53RBR	Royal Blue
PS53WHR	White
PS53YER	Yellow

- Specially designed for working at height
- Size adjustable headband via wheel ratchet system
- Hi-visibility colour for visibility in daylight
- Y-style 4-point chin strap
- Light and robust



Height Endurance Helmet

0352	Colour
PS73ORR	Orange
PS73RBR	Royal Blue
PS73RER	Red
PS73WHR	White
PS73YER	Yellow

BEST SELLER

- Unvented helmet shell for safe use with electrical applications
- Electrical insulation up to 1000V AC or 1500V DC (EN 50365)
- Size adjustable headband via wheel ratchet system
- 4-point textile suspension harness for enhanced wearer comfort and safety
- Soft foam sweat band included



Safety Helmet

0352	Colour
PS57ORR	Orange
PS57RBR	Royal Blue
PS57RER	Red
PS57WHR	White
PS57YER	Yellow

- Portwest exclusive design and patented model
- Translucent shell to see through peak and sides
- 6-point textile suspension harness for enhanced wearing comfort and safety
- Vented helmet shell to allow air circulation cooling the wearer's head
- Size adjustable headband via wheel ratchet system
- UV 400 stabilised



Peak View Ratchet Hard Hat, Vented

0352	Colour
PV60BLU	Blue
PV60GNR	Green
PV60ORR	Orange
PV60SKR	Smoke
PV60YER	Yellow

- Premium style bump cap with innovative plastic shell
- Durable and impact resistant PE shell
- EPP foam liner for maximum impact protection
- Lightweight for enhanced wearer comfort
- Reflective piping for increased visibility
- Multiple ventilation holes in plastic shell and top mesh on cap
- Short peak
- Brightness 150 lumens



Bump Cap

0352	Colour
PS79BKR	Black
PS79NAR	Navy
PS79ORR	Orange
PS79YER	Yellow

- Equipped with a removable and USB rechargeable light
- Inner ABS shell and soft pad for shock absorption
- Durable high density EVA protects and gives comfort to the wearer
- USB rechargeable Li-ion battery



Bump Cap with LED Light

0352	Colour	Brightness
PW29NAR	Navy	150 Lumens

Light only

- Magnetic housing makes it easy to put on and remove
- Adhesive backing to attach housing to helmets
- Compatible with most hard hats
- USB rechargeable Li-ion battery
- Function high-medium-flash
- Brightness 150 lumens



Magnetic Helmet Light

0352	Brightness
HV29BKR	150 Lumens

FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

PORTWEST

new product

EAR PROTECTION



Portwest's hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. This new range of earmuffs offer a variety of models and colours allowing a personalised choice.

Ear Protection

- Padded headband for comfort
- Adjustable dual pin system provides multiple positioning for better fit
- SNR 34dB attenuation level
- Light and robust



CE UKCA CE CAT III

Premium Ear Defenders

0352	Colour
PS46GRR	Grey

- Colour coded cups for easy identification of attenuation levels
- Reflective headband for better visibility and premium look
- Padded headband for comfort
- Adjustable dual pin system provides multiple positioning for better fit
- PW72GGN Grey/Green Trim 26db
- PW73GYR Grey/Yellow Trim 28db
- PW78GOR Grey/Orange Trim 32db



CE UKCA CE CAT III

HV Extreme Ear Defenders

0352	Colour
PW72GGN	Grey
PW73GYR	Grey/Navy
PW78GOR	Grey/Orange

- Folds to palm size for better carriage and to keep clean
- Lightweight and comfortable
- Padded headband for comfort
- Adjustable length for a secure and comfortable fit
- SNR 32db



CE UKCA CE CAT III

Top Ear Defenders

0352	Colour
PS44BKR	Black

- Ultra lightweight for long uses
- Padded headband for comfort
- Adjustable length for a secure and comfortable fit
- 100% metal free
- SNR 28db



CE UKCA CE CAT III

Classic Ear Defenders

0352	Colour
PW48RER	Red
PW48YER	Yellow

- Disposable ear plugs made from soft PU foam
- Excellent attenuation rate
- Easy to fit



CE UKCA CE CAT III

- **Box Quantity - 200 pairs**

Foam Ear Plugs

0352	Colour
EP02ORR	Orange

- Disposable ear plugs made from soft PU foam
- Ergonomically designed for comfort and ease of use
- Excellent attenuation rate



CE UKCA CE CAT III

- **Box Quantity - 200 pairs**

Bell Comfort Foam Ear Plugs

0352	Colour
EP06ORR	Orange

- Reusable earplugs to support sustainability
- Each pair individually wrapped in re-closable zip bag for hygiene purposes
- Supplied in a handy portable dispenser box



CE UKCA CE CAT III

- **Box Quantity - 50 pairs**

Reusable TPR Ear Plugs

0352	Colour
EP10ORR	Orange

- Disposable ear plugs made from soft PU foam
- Corded for safe keeping
- Easy to fit



CE UKCA CE CAT III

- **Box Quantity - 200 pieces**

Comfort Foam Corded Ear Plugs

0352	Colour
EP09ORR	Orange

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PPE & SAFEGUARDING EQUIPMENT

PORTWEST

new product

EYE PROTECTION

Portwest's eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injury during work activities



Eye Protection

Pack Qty: 1

- Single wrap around lens
- Co-injected TPE brow guard for extra protection from particles, impact and glare
- Soft rubber temple tips for non-slip fi
- KN certified lens coatings (anti-scratch/anti-fog
- Non-magnetic - nickel and ferrous free
- Exceptionally good, universal fi
- Ideal fit for smaller face shape
- Ultra lightweight for long uses



Dynamic KN Safety Glasses

0352	Colour
PS10CLR	Clear
PS10SKR	Smoke

- Wrap around style for panoramic view
- Co-injected TPE brow guard for extra protection from particles, impact and glare
- Soft rubber temple tips for non-slip fi
- KN certified lens coatings (anti-scratch/anti-fog
- Non-magnetic - nickel and ferrous free
- Soft TPR nose piece for universal fi
- Soft rubber temple tips for non-slip fi



Dynamic Plus KN Safety Glasses

0352	Colour
PS20CLR	Clear
PS20SKR	Smoke

- Suitable for wearing over most prescription glasses
- Adjustable elastic headband for a perfect fi
- Protects from fluid and splashe
- Anti-scratch coating for added durability
- Anti-fog coating for additional comfort to the wearer



Over Safety Glasses

0352	Colour
PS24CLR	Clear

- Lightweight premium design wrap-around design
- Superior front and side face protection
- Back foam ventilation and lens treatment prevents misting and fogging of the ocular
- Adjustable dual pin system provides multiple positioning for better fi
- Adjustable elastic headband for a perfect fi
- Protects from fluid and splashe



Slim Safety Goggles

0352	Colour
PW26CLR	Clear

- Supplied in a handy portable dispenser box
- Low linting construction for minimal contamination
- Each towelette individually wrapped

Box Qty: 100

Lens Cleaning Wipes

0352	Colour	Box Quantity
PA01WHR	White	100

- Single panoramic lens glasses
- Detachable foam offers additional protection against shocks and dust
- Lightweight wrap-around design
- Flexible arms for ultra comfort
- Soft arms tips for ultra comfort
- Anti-scratch/anti-fog
- 99% UV Protection
- Excellent side protection

Best seller



Wrap Around Spectacles

0352	Colour
PS32AMR	Amber
PS32CLR	Clear
PS32MIR	Mirror
PS32SKR	Smoke

- Single panoramic lens glasses
- Extendable side arms for secure and comfortable fi
- Anti-scratch coating for added durability
- Moulded side shield and brow guard for optimised protection against impacts
- Excellent side protection
- 99% UV protection



Welding Safety Spectacles

0352	Colour
PW68BGR	Bottle Green

- Silicone free - Ideal for manufacturing, paint applications, electronics and glass handling where silicone is problematic
- Anti-static and anti-fog formula



FAC Fluid-Air Components Ltd
ef nkl i roi r p c c c a c c

PORTWEST

new product

RESPIRATORY PROTECTION

Portwest's range of face masks is designed to offer the most comfortable and best fitting product. A user-friendly range, including disposable masks, half masks and filters. Breathe easier with Portwest.



Respiratory Protection

- Ultrasonic welded head straps
- Foam padding around the nose bridge for additional comfort
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Comfortable cup style respirator
- **Pack of 20**



FFP1 Respirator

0352	Colour	Quantity
P100WHR	White	20

- Ultrasonic welded head straps
- Foam padding around the nose bridge for additional comfort
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Comfortable cup style respirator
- **Pack of 10**



FFP1 Valved Respirator

0352	Colour	Quantity
P101WHR	White	10

- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- Ultrasonic welded head straps
- Comfortable cup style respirator
- **Pack of 10**



FFP2 Valved Respirator

0352	Colour	Quantity
P201WHR	White	10

- Special compact vertical fold-flat design
- Ultrasonic welded head straps
- Foam padding around the nose bridge for additional comfort
- **Pack of 20**



FFP2 Flat Fold Respirator

0352	Colour	Quantity
P250WHR	White	20

- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Special compact vertical fold-flat design
- Ultrasonic welded head straps
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- **Pack of 20**



FFP2 Valved Flat Fold Respirator

0352	Colour	Quantity
P251WHR	White	20

- Special compact vertical fold-flat design
- Ultrasonic welded head straps
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- **Pack of 20**



FFP3 Flat Fold Respirator

0352	Colour	Quantity
P350WHR	White	20

- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Ultrasonic welded head straps
- **Pack of 10**



FFP3 Light Cut Respirator

0352	Colour	Quantity
P304WHR	White	10

- Dual bayonet filter connections
- Quick and easy to disassemble for cleaning
- 4-point plastic suspension harness for wearer comfort, safety and easy cleaning
- Adjustable strap fastening for flexible sizing

Filters sold separately



TPR Half Mask

0352	Colour	Size
P421GRRS/M	Grey	M
P421GRRM/L	Grey	L

- Dual bayonet filter connections
- Quick and easy to disassemble for cleaning
- 4-point plastic suspension harness for wearer comfort, safety and easy cleaning
- Adjustable strap fastening for flexible sizing

Filters sold separately



Silicone Half Mask

0352	Colour	Size
P431BLUS/M	Blue	M
P431BLUM/L	Blue	L

- Class 2 thermoplastic rubber full face mask
- Durable polycarbonate visor provides all round visibility
- Adjustable 6-point quick release harness for a uniform face seal
- Dual bayonet filter connections
- Anti-scratch & anti-fog coating

Filters sold separately



Protective film for P500 also available

Vienna Full Face Mask

0352	Colour
P500BKR	Black

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PPE & SAFEGUARDING EQUIPMENT

PORTWEST

new product



HAND PROTECTION

A newly expanded range of hand protection products caters for all work and safety needs. Only the best materials and manufacturing methods are used in the production of this extensive and highly specialised range.

Cut Gloves

Pack Qty: 1 pair

- Level F cut resistance
- 13 gauge liner for a perfect fit
- Nitrile foam coating for excellent grip in wet and dry conditions
- Reinforced thumb crotch for extra protection and durability
- This glove can be used with most mobile touch screen devices
- Reflective label for improved visibility



Nitrile Cut Glove

0352	Size	Colour
A672K8RXS	XS	Black
A672K8RS	S	Black
A672K8RM	M	Black
A672K8RL	L	Black
A672K8RXL	XL	Black
A672K8RXXL	XXL	Black

- Level F cut resistance
- Seamless 13 gauge liner
- Smooth PU coating for increased abrasion resistance
- Reinforced thumb crotch for extra protection and durability
- This glove can be used with most mobile touch screen devices
- Reflective label for improved visibility
- Protection against contact heat up to 100°



PU Cut Glove

0352	Size	Colour
A670K8RXS	XS	Black
A670K8RS	S	Black
A670K8RM	M	Black
A670K8RL	L	Black
A670K8RXL	XL	Black
A670K8RXXL	XXL	Black

- Level D cut resistance
- Seamless 13 gauge liner
- Liquid Pro offers maximum liquid protection
- Dual latex coating
- Prevents grease, oil and water penetration
- Excellent for jobs requiring high dexterity



Liquid Pro Cut Glove

0352	Size	Colour
AP81B4RXS	XS	Blue
AP81B4RS	S	Blue
AP81B4RM	M	Blue
AP81B4RL	L	Blue
AP81B4RXL	XL	Blue
AP81B4RXXL	XXL	Blue

- Level C cut resistance
- 13 gauge liner for a perfect fit
- Smooth PU coating for increased abrasion resistance
- Palm dipped to increase dexterity and ventilation
- Breathable seamless liner
- Medium risk cut protection
- Protection against contact heat up to 100°



Impact Cut Resistant Glove

0352	Size	Colour
A622G7RXS	XS	Grey/Black
A622G7RS	S	Grey/Black
A622G7RM	M	Grey/Black
A622G7RL	L	Grey/Black
A622G7RXL	XL	Grey/Black
A622G7RXXL	XXL	Grey/Black
A622G7RXXXL	XXXL	Grey/Black

- Level D cut resistance
- Seamless 13 gauge liner
- Protects against cuts and abrasion
- Double dipping for maximum liquid repellency
- Sandy finish for exceptional grip in water, grease or oil
- Prevents grease, oil and water penetration



Aqua Pro Cut Glove

0352	Size	Colour
AP50B8RS	S	Black
AP50B8RM	M	Black
AP50B8RL	L	Black
AP50B8RXL	XL	Black
AP50B8RXXL	XXL	Black

BEST SELLER

- Nitrile foam coating for excellent grip in wet and dry conditions
- Palm dipped to increase dexterity and ventilation
- 15 gauge liner for extra dexterity
- Breathable seamless liner
- Lightweight and comfortable
- Maximum EN level 4 abrasion



Dermiflex Glove

0352	Size	Colour
A350BKRXS	XS	Black
A350BKRS	S	Black
A350BKRM	M	Black
A350BKRL	L	Black
A350BKRXL	XL	Black
A350BKRXXL	XXL	Black
A350BKRXXXL	XXXL	Black

Fluid-Air Components Ltd

PPE & SAFEGUARDING EQUIPMENT

PORTWEST

new product

Gloves

Pack Qty: 1 pair

BEST SELLER

- Smooth PU coating for increased abrasion resistance
- Palm dipped to increase dexterity and ventilation
- 13 gauge liner for a perfect fi
- Perfect for intricate tasks
- Maximum dexterity
- Superb abrasion and tear resistance



PU Palm Glove

0352	Size	Colour
A120BKRXXS	XXS	Black
A120BKRXS	XS	Black
A120BKRS	S	Black
A120BKRM	M	Black
A120BKRL	L	Black
A120BKRXL	XL	Black
A120BKRXXL	XXL	Black
A120BKRXXXL	XXXL	Black

- Made using a sustainable bamboo liner
- 15 gauge liner for extra dexterity
- Palm dipped to increase dexterity and ventilation
- Nitrile foam coating for excellent grip in wet and dry conditions



Foam Nitrile Bamboo Gloves

0352	Size	Colour
AP10K8RXS	XS	Black
AP10K8RS	S	Black
AP10K8RM	M	Black
AP10K8RL	L	Black
AP10K8RXL	XL	Black
AP10K8RXL	XL	Black

BEST SELLER

- Latex foam coating for excellent grip in wet and dry conditions
- Crinkle latex grip offers excellent grip
- Tough 10 gauge liner
- Breathable seamless liner
- Premium quality work glove
- Open back for breathability



Latex Grip Glove

0352	Size	Colour
A100G4RS	S	Grey/Blue
A100G4RM	M	Grey/Blue
A100G4RL	L	Grey/Blue
A100G4RXL	XL	Grey/Blue
A100G4RXXL	XXL	Grey/Blue
A100GNRM	M	Green
A100GNRL	L	Green
A100GNRXL	XL	Green
A100GNRXXL	XXL	Green
A100K8RM	M	Black
A100K8RL	L	Black
A100K8RXL	XL	Black
A100K8RXXL	XXL	Black
A100ORRS	S	Orange
A100ORRM	M	Orange
A100ORRL	L	Orange
A100ORRXL	XL	Orange
A100ORRXXL	XXL	Orange
A100R8RM	M	Red/Black
A100R8RL	L	Red/Black
A100R8RXL	XL	Red/Black
A100R8RXXL	XXL	Red/Black

- Specially designed for use in cold conditions
- Palm dipped to increase dexterity and ventilation
- Crinkle latex grip offers excellent grip
- Warm 10 gauge acrylic liner for cold protection
- Breathable seamless liner
- Ergonomically designed for comfort and ease of use



Thermal Grip Glove

0352	Size	Colour
A140BKRXS	XS	Black
A140BKRS	S	Black
A140BKRM	M	Black
A140BKRL	L	Black
A140BKRXL	XL	Black
A140BKRXXL	XXL	Black
A140ORBM	M	Orange/Black
A140ORBL	L	Orange/Black
A140ORBXL	XL	Orange/Black
A140ORBXXL	XXL	Orange/Black

- Fully coated for maximum liquid protection
- Nitrile foam coating for excellent grip in wet and dry conditions
- Superb abrasion and tear resistance
- 13 gauge liner for a perfect fi
- Lightweight and comfortable
- Elasticated cuffs for a secure fi



Dermi Pro Glove

0352	Size	Colour
AP30O8RXS	XS	Orange/Black
AP30O8RS	S	Orange/Black
AP30O8RM	M	Orange/Black
AP30O8RL	L	Orange/Black
AP30O8RXL	XL	Orange/Black
AP30O8RXXL	XXL	Orange/Black

- Liquid Pro offers maximum liquid protection
- Latex foam coating for excellent grip in wet and dry conditions
- Dual latex coating for additional protection in tough conditions
- 13 gauge liner for a perfect fi
- Lightweight and comfortable
- Elasticated cuffs for a secure fi



Liquid Pro Glove

0352	Size	Colour
AP80B4RS	S	Blue
AP80B4RM	M	Blue
AP80B4RL	L	Blue
AP80B4RXL	XL	Blue
AP80B4RXXL	XXL	Blue

Fluid-Air Components Ltd

PPE & SAFEGUARDING EQUIPMENT

PORTWEST

new product

Gloves

- High performance multi-purpose glove
- Reinforced thumb crotch for extra protection and durability
- This glove can be used with most mobile touch screen devices
- Lightweight and comfortable
- Wrist strap for secure fittin
- Specially engineered high visibility material



PW3 General Utility Glove

0352	Size	Colour
A770BKYS	S	Black/Yellow
A770BKYM	M	Black/Yellow
A770BKYL	L	Black/Yellow
A770BKYXL	XL	Black/Yellow
A770BKYXXL	XXL	Black/Yellow

- Level B cut resistance
- High performance multi-purpose glove
- Reinforced thumb crotch for extra protection and durability
- This glove can be used with most mobile touch screen devices
- Wrist strap for secure fittin
- Lightweight and comfortable



DX4 Cut Glove

0352	Size	Colour
A774K2RS	S	Black/Yellow
A774K2RM	M	Black/Yellow
A774K2RL	L	Black/Yellow
A774K2RXL	XL	Black/Yellow
A774K2RXXL	XXL	Black/Yellow
A774MBRS	S	Metro Blue
A774MBRM	M	Metro Blue
A774MBRL	L	Metro Blue
A774MBRXL	XL	Metro Blue
A774MBRXXL	XXL	Metro Blue

- High performance multi-purpose glove
- Reinforced panels in high wear areas for maximum durability
- Additional knuckle padding for extra protection
- Durable synthetic leather palm
- Reinforced padded palms
- Wrist strap for secure fittin



Impact Performance Glove

0352	Size	Colour
A720NARM	M	Navy
A720NARL	L	Navy
A720NARXL	XL	Navy
A720NARXXL	XXL	Navy

BEST SELLER

- Premium full grain cow leather
- Breathable leather for use in mild and hot climates
- Classic leather driver
- Superb abrasion and tear resistance
- Increased puncture resistance properties
- Durable leather



Lined Drivers Glove

0352	Size	Colour
A271TARL	L	Tan
A271TARXL	XL	Tan

- Silicone free - Ideal for manufacturing, paint applications, electronics and glass handling where silicone is problematic
- Suitable for use in chemical, oil and food industries
- Textured pattern for enhanced grip
- Flock lined for added comfort
- 0.38mm thickness
- 330mm length



Nitrosafe Chemical Gauntlets

0352	Size	Colour
A812GNRXS	XS	Green
A812GNRS	S	Green
A812GNRM	M	Green
A812GNRL	L	Green
A812GNRXL	XL	Green
A812GNRXXL	XXL	Green

Disposable Gloves

Manufactured from synthetic nitrile rubber our disposable nitrile gloves eliminate the risk of allergic reaction associated with latex gloves. Textured finish provides enhanced fingertip gri and dexterity in both wet and dry conditions.

- Suited for food processing plants and resistant to greases, animal fats and oils
- Disposable nitrile gloves eliminate the risk of allergic reaction associated with latex gloves
- Smooth and non-textured with a beaded cuff
- Acceptable quality limit (AQL) 1.5
- 240mm length
- 0.07mm thickness
- Retail box which aids presentation for retail sales
- CE certifie
- CE foodsafe

100 gloves per box.

Materials: Nitrile



A925 Powder Free Nitrile Disposable Gloves

0352	Size	Colour	Box Quantity
A925BLUS	S	Blue	100
A925BLUM	M	Blue	100
A925BLUL	L	Blue	100
A925BLUXL	XL	Blue	100

Premium high strength disposable gloves using innovative crystal grip technology. 7mm thickness for exceptional strength. Highly durable synthetic nitrile compound make this glove three times stronger than standard nitrile.

- Silicone Free
- Idea for auto manufacture, electronics and glass sectors
- Crystal grip technology
- Silicone free. Ideal for manufacturing, paint applications, electronics and glass handling where silicone is problematic
- Suited for food processing plants and resistant to greases, animal fats and oils
- Three times stronger than standard nitrile
- 7mm/0.18mm thickness for exceptional strength
- 240mm length
- Highly durable synthetic nitirile compound
- Retail box which aids presentation for retail sales
- Ideal for auto repair, construction and other sectors
- Acceptable quality limit (AQL) 1.5
- This product is sold in inner boxes
- CE certifie
- CE foodsafe

100 gloves per box.

Materials: Nitrile



HD Disposable Gloves

0352	Size	Colour	Box Quantity
A930ORRM	M	Orange	100
A930ORRL	L	Orange	100
A930ORRXL	XL	Orange	100

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PORTWEST

new product



KNEE PROTECTION

All Portwest knee pads use premium high density material to provide the user with the best protection possible for their knees no matter what the hazard.

Knee Pads

- Ergonomically designed and tested straps ensure no pinching to the back of the wearers leg
- A strong and durable outer shell makes for a long lasting tough knee pad
- Silicone gel inserts protect joints and ensure great wearer comfort



Super Gel Knee Pads

0352	Colour
KP30BKR	Black

- Tough abrasion resistant PVC shell
- Thick silicone gel adapts to your kneecap
- Ergonomically designed and tested straps ensure no pinching to the back of the wearers leg



Ultimate Gel Knee Pads


0352	Colour
KP40BKR	Black

- Lightweight EVA foam cushioning
- Reduces knee and back strain
- Integral carry handle



Kneeling Pad

0352	Colour
KP05BKR	Black



LUGGAGE

The essential collection of versatile luggage pieces, suitable for travel, work or general everyday use. Robustly constructed with strong materials.

Duffle Bag

- Ideal for carrying tools, equipment or for use as a travel bag
- Two zipped compartments
- Robust base panel
- Adjustable shoulder strap for added comfort
- 65cm x 25cm x 35cm
- 60 litres



0352	Colour	Size Litres
B960BKR	Black	60

Boot Bag

- Generous storage to fit most work boots
- Carry handle for added convenience
- Integrated changing mat
- 35cm x 30 cm x 12 cm
- 12 litres



0352	Colour	Size Litres
B914BKR	Black	12

Rucksacks

- Heat applied segmented reflective tape for added visibility
- Pull string front provides extra storage
- Two mesh water bottle pockets double as multi-use pockets
- 38cm/15" laptop sleeve
- Padded mesh back panel and a breathable lumbar panel for comfortable ventilated support
- 47cm x 30cmx 19.5 cm
- 25 litres



PW3 Hi-Vis Rucksack

0352	Colour	Size Litres
B955YER	Yellow	25

- Padded double straps for added support
- Reflective tape for increased visibility
- Padded back panel for wearer comfort
- Phone pocket
- 28cm x 21cm x 43 cm
- 25 litres



Hi-Vis Rucksack

0352	Colour	Size Litres
B905ORR	Orange	25
B905YER	Yellow	25

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PPE & SAFEGUARDING EQUIPMENT

PORTWEST new product

Overalls

- Elasticated hood, ankles, cuffs and waist
- Two way front zip and sealable front fla
- Anti static
- Excellent liquid and particulate barrier protection



Microporus Overall

0352	Size	Colour
ST40WHRS	S	White
ST40WHRM	M	White
ST40WHRL	L	White
ST40WHRXL	XL	White
ST40WHRXXL	XXL	White
ST40WHRXXXL	XXXL	White

Sleeve

- Elasticated cuffs for a secure fi
- Designed for a comfortable fi
- Box of 150 pairs



Microporous Sleeve

0352	Colour
ST43WHR	White

Cut level D



Cut Resistant Sleeve

0352	Colour
A690GRR	Grey
A690YER	Yellow

Overshoes

- Disposable boot covers for superior protection against cross contamination
- Elasticated cuffs for a secure fi
- Box of 200 pairs



Microporous Shoe Cover

0352	Colour
ST44WHR	White

PPE & SAFEGUARDING EQUIPMENT

Engineers Gloves



Superior Nitrile Gloves, Orange, 50 Singles Pack

0086	Size
5300-207	S (7)
5300-208	M (8)
5300-209	L (9)
5300-210	XL (10)



Superior Nitrile Gloves, Black, 50 Singles Pack

0086	Size
5300-107	S (7)
5300-108	M (8)
5300-109	L (9)
5300-110	XL (10)
5300-111	XXL (11)

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

INDUSTRIAL CLEANING EQUIPMENT

alliedhygiene

Hand Wet Wipes

The moist wipes require no additional liquids as the low alcohol base anti-bacterial cleaning solutions helps clear all stains and marks leaving the skin cleansed as well as dry thanks to rapid evaporation.
Each tub contains 150 perforated sheets.



Degreasing Wipes

0212	Quantity
IPGM	150 Wipes

A powerful alcohol based cleaning solution that quickly gets to work on paint and related stains cleaning fast. Each tub contains 150 perforated sheets.



Paint & Mastic Removing Wipes

0212	Quantity
IPGP	150 Wipes

In todays food preparation areas, hygiene guidelines are tough and the risk of cross contamination through neglecting these requirements puts many people at risk. With the surface wipes, killing off all potentially lethal bacteria from passing from one product to another.





Sani Safe Disinfectant Wipes

0212	Quantity
IPSS4	200 Wipes

These handy wipes are an ideal size to keep handy and give off a pleasant fragrance that also identifies when the product is actively killing off bacteria.





Office Wipe

0212	Quantity
BA035	150 Wipes

Non-woven Dry Wipes

A strong, low lint, solent resistant, absorbent cloth. Supplied in a handy dispenser box, suitable for all applications.



Super Strong Low Lint Rag Replacement

0212	Quantity
DWTWDP	150 Wipes

An industrial 2 ply centre feed roll.



Wiper Rolls

0212	Length Metres	Quantity
CF14BE	140	6 Rolls
MR74	140	2 Rolls

A retail branded quality 2 ply toilet roll.



Toilet Rolls

0212	Quantity	Colour
CT402839	40 Rolls x 220 Sheets	White

A high volume toilet roll suitable for volume use areas. 76mm core.



Jumbo Toilet Rolls

0212	Quantity
JT04	12 Rolls

A quality soft hand towel white C-fold.



Hand Towels

0212	Quantity
HT24	2400 Towels

Dispensers

Lockable.



C-Fold Hand Towel Dispenser

0212
HTD534



Mini Jumbo Toilet Roll Dispenser

0212
JTD202



Standard Centrefeed Roll Dispenser

0212
CFD216

Portable free standing dispenser.



Floor Stand Dispenser

0212
MRD522

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ENGINEERING CONSUMABLES

Lockout & Tagout Products



Universal Circuit Breaker Lockout

0086	Description
LOK043	Universal MCB Lockout



Mini Circuit Breaker Lockout

0086	Type	Colour
LOK020-L	Pin Out	Yellow



Electrical/Pneumatic Plug Lockout

0086
LOK030



Lockout Kit, Medium

0086
LOK116



Maintenance Electrical Lockout Kit

0086
LOK230



Electrical Lockout Kit

0086
LOK229



Lockout Board, 5 Station

0086
LOK172



Lockout Board, 10 Station

0086
LOK173



Multi-purpose Cable Lockout

0086	Cable Type
LOK014	2.5 Metre Nylon Cable

FT PRO



For **Spill Absorbents & Spill Prevention** see pages **279-282**

FAC Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ENGINEERING CONSUMABLES

Lockout & Tagout Products



Ball Valve Lockouts

0086	Size mm	Maximum Handle Length mm
LOK023	9.5-31	190
LOK024	32-76	254



Ladder Tag Kit, 10 Pieces

0086	Description
TG04BOX	10 Piece Ladder Tag Kit



Lockout Tags, Double Sided, 10 Pack

0086	Description
LOK073	Do Not Use/Do Not Open - Double Sided, 10 Pack



Safety Lockout Padlocks

0086	Colour
LOK011-L	Black
LOK010-L	Blue
LOK007-L	Red
LOK008-L	Yellow
LOK009-L	Green



Dielectric Safety Lockout Padlock, Non-conductive

0086	Colour
LOK068	Yellow

First Protection



Fire Extinguisher - Powder

0086	Description
14364	600kg Dry Powder Extinguisher
14365	800kg Dry Powder Extinguisher



Fire Extinguisher - Powder

0086	Description
14366	1kg Dry Powder Extinguisher

First Aid



Travel Pouch 1 Person First Aid Kit

0086
254810



Van & Truck Drivers First Aid Kit

0086
254809

FAC
Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

ENGINEERING CONSUMABLES

Shadowboard Cleaning Stations

Style A



0086	Colour
SB-BD01-BL	Blue
SB-BD01-GR	Green
SB-BD01-RD	Red
SB-BD01-YL	Yellow

Style B



0086	Colour
SB-BD02-BL	Blue
SB-BD02-GR	Green
SB-BD02-RD	Red
SB-BD02-YL	Yellow

Style C



0086	Colour
SB-BD03-BL	Blue
SB-BD03-GR	Green
SB-BD03-RD	Red
SB-BD03-YL	Yellow

Style D



0086	Colour
SB-BD04-BL	Blue
SB-BD04-GR	Green
SB-BD04-RD	Red
SB-BD04-YL	Yellow

Duracell Industrial Batteries

AA Batteries, 10 Pack



0086
DPB2A

AAA Batteries, 10 Pack



0086
DPB3A

9V Battery



0086
DPB9V

Padlocks

Standard Brass Padlocks



0088	Size mm
SP24L	30
SP26L	40

Brass 4 Wheel Combi Padlock



0088	Size mm
SP162P	30

Weather Resistant Padlock



0088	Size mm
SP160P	30

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

PEAK INDUSTRIAL



Cost effective on-site nitrogen gas generation

- Economical, on-demand N2 solution that saves you money
- Highly efficient & reliable technology, for maximum productivity
- Future-proof, expandable design to meet your growing demands
- Expert consultation & system design, backed by world-class support

Contact us today to discover more!

Tel: +44 (0)141 812 8100
Email: marketing@peakindustrial.com
Web: www.peakindustrial.com

1765

Fluid-Air Components Ltd

Brand Index

ADBLUE
Fuelling Equipment & Accessories 1623-1624

AEROPRO
Pneumatic Power Tools & Spraying Equipment 1704-1713

AIGNEP
Adaptors & Fittings 1209-1211
Ball Valves 928, 942
Digital Flow & Pressure Sensor 420
Hose Adaptors 1148
Manifolds 1220
Push-in Fittings 817-820, 852-861, 878-879
Pneumatic Quick Release Couplings & Plugs 391
Ring Main 1081-1084
Valves 627

AIRCOM
Ring Main 1068-1080

AIRCOMP
Valves 629

AIRNET
Ring Main 1085-1086

ALLIED HYGIENE
Industrial Cleaning Equipment 1761

AIR TORQUE
Actuation 1015

ALWITCO
Mufflers 632

AMBERSIL
Aerosols & Cleaning 1570-1583

BAMBI
Compressors 1703

BAND-IT
Steel Strapping & Accessories 1554-1555

BECK AIR
Air Knives & Amplifiers 1614-1616

BETABITE HYDRAULICS
Hydraulic Imperial Compression Fittings 141-143

BRAUER
Air Movers 1613

BROWNALL
Air Vents & Valves 979

BVA HYDRAULICS
Hydraulic Tooling & Lifting Equipment 274-278

BURNETT & HILLMAN
Hydraulic Adaptors 52-81

CAMOZZI
Air Preparation 691-698
Brass Fittings (Truck) 890-894
Directional Control Valves 621-622, 636
Manual & Mechanical Valves 559-563
Pilot Valves Pneumatic & Accessories 607
Pneumatic Cylinders & Accessories 475, 507-511
Push-in Fittings 832-834, 870-874
Solenoid Valves & Accessories 592-596

CHICAGO PNEUMATIC
Air Tools 1716-1718

COMER
Ball Valves 937, 945
Pipe Systems 1097-1115

CRANE
Malleable Iron Fittings 1370-1376

CROUZET
Pneumatic Control 613

DANFOSS
CETOP 3 Valves 209-213
CETOP 5 Valves 214-218
CETOP Coils 219
Flange Couplings 135
Hydraulic Fittings & Couplings 116-134
Reinforcing Tube Inserts 182
Vane & Piston Pumps 221-225
Valves 136-137
Walform Machine 115

DALLAI
Lever Lock Water Pump Couplings 1505-1510

DNP
Hydraulic Quick Release Couplings & Plugs 295-307

DONALDSON
Condensate Management 432

EE
Malleable Iron Fittings 1338-1348

ELETTROTEC
Float Level Switches 441-442
Flow Indicators 438
Flow Meters 439-440
Flow Switches 437
Pressure Switches 423-424
Pressure Transducers 422
Temperature Switches 421
Vacuum Switches 425

ENOLGAS
Actuation 993-994, 1005-1006
Ball Valves 935

ETI
Thermometers 446

FESTO
Actuation 1017, 1020, 1023
Air Preparation 657-662
Angle Seat Valves 1050
Cylinder Sensors 426
Flow Sensors 427
Pneumatic Cylinders & Accessories 461-468, 487-490, 521-531, 543-544
Pressure Sensors 428
Push-in Fittings 808-816
Solenoid Valves & Accessories 578-582, 1035-1036
Tubing 911-912

FEMCO
Quick Oil Drain Plugs 1650-1653

FINI
Compressors 1702

FLAMCO
Pipe Clips & Fixing Systems 1549-1551

FLARETITE
Hydraulic Seals 111

FOGCO
Misting Systems 1687-1696

FT PRO
Actuation 1002-1004, 1013-1014, 1020, 1022
Adaptors & Fittings 1165-1177, 1196-1202, 1206-1208
Air Jets 1611
Air Preparation 637-656
Air Receivers & Accessories 433-434
Air Vents 979
Angle Seat Valves 1049
Balancing Valves 978
Ball Valves 922-926, 937-939, 937-939, 946, 952
Blow Guns 1593-1595, 1609
Breaker Hose Assemblies 15
Butt Weld Fittings 1392
Butterfly Valves 967-971
Cam & Groove Quick Couplings 1467-1472
CETOP Directional Control Valves 202-208
Check & Non-return Valves 242, 627, 960-961, 965
Cleaning Kits Hose & Pipe 49
Clips & Clamps 1513-1516, 1536, 1540, 1545-1548
Condensate Management 435
Coolant Hose Systems 1498-1502
Counters 614
Couplings Clamps & Accessories 1480-1493, 1496-1497
Diesel Filters 1629-1631
Drain Valves 1024-1025
Ducting 1437-1438
Filter Elements 762
Fire Sleeve 44-45
Flanges & Gaskets 1386-1390
Flow Regulators 1160
Fuelling Equipment & Accessories 1620, 1622, 1625-1627, 1638
Gate Valves 957-958
Globe Valves 975
Greasing & Lubrication Equipment 1639
Hand Rail Systems 1393-1398
Hose Ferrules 1556
Hose Reels 1448-1453
Hose, Tube & Assemblies 895-905, 909-910, 913-917, 1383, 1402-1408, 1409-1422, 1433-1436, 1482, 1484
Hose Tails 1140-1147, 1149, 1154-1155
Hydraulic Accessories 255-256, 260-262

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Hydraulic Ball Valves 238-240
Hydraulic Ball Valves Stainless Steel 242, 956, 957
Hydraulic Control Valves 241
Hydraulic Hose Connectors 17-27
Hydraulic Hose Ferrules 16
Hydraulic Hose Range 6-14
Hydraulic Oils 283
Hydraulic Pressure Gauges Stainless Steel 263, 267
Hydraulic Push Style Hose System 38-40
Hydraulic Quick Release Couplings & Plugs 290-294
Hydraulic Reusable Fittings 41
Hydraulic Valves 243
Hydraulic Valves Threaded 244-246
Hygienic Valves Stainless Steel 967
Knife Gate Valves 959
Logic Valves 611
Malleable Iron Fittings 1378-1380, 1384-1385
Manual & Mechanical Valves 545-549
Needle Valves 982
Paint Spraying Equipment 1714
Pilot Valves Pneumatic & Accessories 600-601
Pipe Fittings 1180, 1186-1189, 1191-1195
Pneumatic Cylinders & Accessories 450-460, 478-486, 516-520, 542
Pneumatic Power Tools & Accessories 1720
Pneumatic Quick Release Couplings 321-329, 1473-1474
Pneumatic Vibrators 625
Polyethylene Pipe System 1093-1096
Pressure Gauges 410-412, 414-415
Pressure Relief Valves 985-986
Pressure Hoses 1649
Protective Hose Sleeves 45-46
Pumps & Pump Kit 1610, 1632-1636
Push-in Fittings 766-792, 843-847, 875-877
Quick Fittings 1156-1159
Rotating & Swivel Joints 1224
Sight Glasses 436
Silencers 630-631
Solenoid Valves & Accessories 575-577, 1026-1029, 1043-1046
Spill Absorbents & Spill Prevention 279-284
Spiral Hose Guard 47-48
Spray Guns 1679
Sprinklers 1680
Standpipe Adaptors 137
Storage & Display 1747-1749
Swivel Air Couplings 1719
Tank Gauges 1654
Thermometers 417
Tyre Inflation Equipment 1721
Valves & Accessories 615-616, 1056-1060
Wash Down Equipment 1666-1678
Washers Fibre 110
Water Couplings 1475, 1503-1504
Water Guns 1657-1658
Workshop Fluid Transfer 1655-1656
Y Strainers 972, 974

GENEBRE
Ball Valves 951
Check Valves 964, 966
Float Valves 1059
Needle Valves 982-983
Actuation 997

GF
Malleable Iron Fittings 1356-1369

GRACO
Pumps & Process Equipment 1684-1685

GROZ
Fuelling Equipment & Accessories 1628

HAITIMA
Actuation 993-1003, 1008-1112, 1015, 1022
Ball Valves 947-955
Check Valves 963
Gate Valves 958
Globe Valves 977
Pipe Fittings 1181-1185
Y Strainers 973

HAVIT
SAE Flanges 101-108

HOZELOCK
Hose 1432

ICP VALVES
Ball Valves 936
Check Valves 965
Gate Valves 959
Globe Valves 976-977

IMPULSE AUTOMATION
Counters 614
High Precision Regulators 704
Pneumatic Cylinders & Transmitters 537

ITAP
Ball Valves 927, 929-931, 940, 958
Check Valves 962
Drain Valves 1058
Manifolds 1214
Pressure Reducing Valves 980
Push-in Fittings 885-886
Strainers 962
Y Strainers 973

JAMEC PEM
Blow Guns 1602
Hose Reels 1454
Tyre Inflation Equipment 1722

J+J
Actuation 1005-1014, 1018-1019

JAYMAC
Hose & Assemblies 1424-1432, 1494-1495
Hose Reels 1466

JCS
Clips & Clamps 1531-1533, 1543

JOHN GUEST
Push-in Fittings 836-842, 880-884
Fast Track Ring Main System 961-963
Ring Main 1088-1092

JUBILEE
Clips & Clamps 1517-1521, 1541, 1552

JWL
Blow Guns 1597-1601
Tyre Inflation Equipment 1723

K-LINE CONNECT
Malleable Iron Fittings 1349-1355, 1381-1382

KR
High Pressure Hydraulic Fittings & Couplings 138-140
Hydraulic Adaptors 82-84

LECHLER
Air Jets 1611

LOCTITE
Cleaning & Specialist Products 1569
Adhesives & Sealants 1584-1587

LUDECKE
Quick Release Couplings 1476-1479

M&M
Angle Seat Valves 1052-1053
Solenoid Valves 1040-1042
Pressure Switches 1054

MESTO
Pressure Spray Equipment 1681-1682

METAL WORK
Adaptors & Fittings 1212
Air Preparation 663-682, 705
Dump Valves 1161
ISO Valves & Accessories 617-620
Logic Valves 612
Manual & Mechanical Valves 550-556
Pilot Valves Pneumatic & Accessories 602-606
Pneumatic Cylinders & Accessories 469-472, 491-504, 532-533, 538-540
Pressure & Vacuum Switches 624
Push-in Fittings 821-831, 865-869
Quick Fittings 1162
Solenoid Valves & Accessories 583-589
Special Purpose Valves 623-624

MIKALOR
Clips & Clamps 1523-1530, 1537, 1557

M-PRESS
Press Fit Pipe Systems 1116-1134

NABIC
Pressure Relief Valves 990-992
Safety Valves 988-989

NEDERMAN
Self Retracting Hose 1463-1465

NITO
Water Gun & Couplings 1660-1665

NORGREN
Adaptors & Fittings 1203-1205
Air Preparation 683-690

Fluid-Air Components Ltd

Exhaust Valves 633-635
Manual & Mechanical Valves 557-558
Pneumatic Cylinders & Accessories 474, 505-506, 534-535, 541
Pressure Switches 429
Push-in Fittings 862-864
Solenoid Valves & Accessories 590-591
Visual Indicators 445
Vacuum 749

NORMA
Clips & Clamps 1534-1535, 1544
Hose Tails 1153
Pipe Repair Couplings 1557

NORRES
Ducting 1440-1447

NUAIR
Compressors 1699-1701

OETIKER
Clips & Clamps 1538-1539
Swing Couplings 404

OMAL
Actuation 1055
Angle Seat Valves 1055

PANAM
10,000 psi Rated Adaptors Stainless Steel 90-94
37° JIC Flare Fittings Stainless Steel 95-100
Ball Valves 956
Check Valves 963
Hydraulic Adaptors Stainless Steel 86-87
Instrumentation Manifolds 981
Precision Instrumentation Fittings St. St. 88-89
Twin Ferrule Tube Fittings St. Steel 165-178

PARKER
Actuation 1021
Air Preparation 699
Angle Seat Valves 1051
Hydraulic Filtration 247-251
Hydraulic Flow Metering 252-254
Hydraulic Valves CETOP 3 & 5 220
Multiclamp 201
Pneumatic Cylinders & Accessories 512-513
Pneumatic Valves & Accessories 564-566, 597, 608
Solenoid Valves & Accessories 1036-1038

PARKER DOMINIC HUNTER
Filters & Drains 430

PARKER LEGRIS
Ball & Check Valves 628, 933-935
Blow Guns 1596, 1602
Push-in Fittings 793-807, 848-851
Quick Release Couplings & Plugs 389
Tubing 906-908

PARKER OLAER
Hydraulic Accumulators & Accessories 227-228
Hydraulic Oil Coolers 273

PARKER RECTUS
Hose 1409
Quick Release Couplings & Plugs 330-388, 390

PARKER SNAP-TITE
Quick Release Couplings & Plugs 318-320

PARKER TRANSAIR
Ring Main 1063-1067

PCL
Air Preparation 703
Blow Guns 1604-1606
Hose Tails 1154
Paint Spray Guns 1715
Pneumatic Quick Release Couplings & Plugs 393-403
Tyre Inflation Equipment 1724-1725

PEAK
Nitrogen Gas Generation 1765

PORTWEST
PPE & Safeguarding Equipment 1752-1760

PH INDUSTRIE
Hydraulic Stainless Steel Adaptors & Hose Fittings 30-36
Hydraulic Stainless Steel Ferrules 29
Hydraulic DIN Stainless Steel Fittings 144-164

PLUGTITE
Service Plugs 50-51

PNEUMAX
Air Preparation 700-702, 706
Pneumatic Cylinders & Accessories 476-477, 514-515, 536
Pneumatic Valves & Accessories 567-574, 598-599, 609-610
Vacuum 748-749

PRISMA
Actuation 1016, 1022

PVL
Float Level Switches 442

REDASHE
Fuelling Equipment & Accessories 1621, 1655-1656
Hose Reels 1455-1462
Lubrication & Pumping Equipment 1637, 1640-1642
Tool Balancers 1720
Torches & Lamps 1741
Washdown & Cleaning 1659

RHODES
Sight Glasses 436

RIDGID
Professional Tools 1742-1746

ROQUET
Gear Motors 234-235
Gear Pumps 231-233, 236
Hydraulic Control Valves 237

RSB
Hydraulic Tube Clamps 186-200

ROTORK
Actuation 1023

RUB
Actuation 993-994, 1005, 1007
Ball Valves 932, 943-944

RUST-OLEUM
Maintenance Paints & Sprays 1561-1568

SCAPA
Adhesive Tapes & Barrier Tapes 1589

SANHA
Press Fit Pipe Systems 1135-1136

SEETRU
Liquid Level Gauges 443-444
Pressure Relief Valves 987

SILVENT
Blow Guns & Air Nozzles 1607-1608, 1612

SIRAI
Solenoid Valves 1031-1034

SIRIT
Air Brake Fittings 887-889

SNAP-TITE
Hydraulic Quick Release Couplings & Plugs 318-320

SPRADOW
Test Point Couplings 269-272

STOPFLEX
Retention System for Pressure Hose 42-43

SYNFLEX
Tubing 918

TECHMATIC
Solenoid Valves 1030

TEFEN
Nylon Fittings 1150-1151, 1178
Polypropylene Fittings 1163
PVDF Fittings 1152, 1164, 1179
Quick Release Couplings Acetal Resin 392

TERRY
Tool Clips, Pen & Tool Holders 1558

TOMCO
Pneumatic Quick Release Couplings & Plugs 405

TOTAL
Drilling & Cutting 1729
Industrial Hand Tools & Accessories 1730-1741
Water Gun 1679

TVL
Ball Valves 932, 941

UFI
Filtration 257-259

VMECA
Vacuum Technology 707-747, 750-761

VIBTEC
Industrial Vibrators 626

VICKERS
CETOP 3 Valves 210-213
CETOP 5 Valves 214-218
CETOP Coils 219
Vane & Piston Pumps 221-225

WD40
Lubricants 1568

WIKA
Pressure & Temperature Gauges 265-266, 413, 416-417

Fluid-Air Components Ltd

Product Index

1

10,000psi Stainless Steel Adaptors **90-94**
100R1AT Hose **6**
100R2AT Hose **7, 10**
100R4 Suction & Delivery Hose **14**
100R6 Push Style Hose **38-39**
100R7 Thermoplastic Hose **13**
150lb Fittings **1181-1185**
150lb Flanges **1195**
1SC Compact Hose **8**

2

2SC Compact Hose **9**

3

3000lb
Forged Fittings **1180**
Stainless Steel Fittings **1186-1189**

4

4SH Multi Spiral Hose **12**
4SP Multi Spiral Hose **11**

A

Accumulators & Accessories
Accessories **228**
Accumulator Bladder **227**
Accumulator Charging Kit **228**
Diaphragm Accumulator **227**
Hydra-Cushions **227**
Safety Block **227**
Thermoswitches **227**

Actuation
Accessories **1022-1023**
Electric **1005-1014, 1018-1019**
Mounting Brackets **1013**
Pneumatic **993-1004, 1015-1017, 1055**

Adaptors
Adaptors **54-81**
High Pressure Adaptors **81-84**
JIC Adaptors **72-80**
JIC Stainless Steel Adaptors **95-100**
ORFS Adaptors **81**
Stainless Steel Adaptors **85-87**

Adaptors, Hose Tails
Aluminium **1147**
Brass **1140-1146, 1148, 1154-1155, 1419**
Combination Steel Nipples & Hose Joiners **1497**
Ferrules Low Pressure **1556**
Hexagon Nuts & Tails **1497**
Kits **1154**
Plastic **1149-1151, 1153**
PVDF **1152**

Adaptors General Use
Brass **1165, 1176**
Plastic **1177-1178**
PVDF **1179**

Adblue
Fuelling Meter **1626**
Nozzles, Pumps & Hose **1623-1624, 1633, 1636**
Stainless Steel Auto Nozzle **1620-1621**
Tank Gauges **1654**

Adhesives
Adhesive Spray **1583**
Glues & Bonding **1587**
Plate & Cloth Tape **1391**
Retainers **1585-1586**
Sealants **1585-1586**
Self Amalgamating Tape **45**
Super Glue **1585**
Thread Lock Adhesives **1584, 1586**

ABS Imperial Flanges & Gaskets **1099**
Air Brake Fittings **406, 887-894**
Air Couplings **329, 393-403**
Air Knives & Amplifiers **1612, 1614-1616**
Air Movers **1613**
Air Operated Pumps **1636-1637**

Air Preparation
Air Preparation **637-706**
Accessories **644-646, 648, 651, 654, 656, 662, 672, 675, 676, 681, 683, 688, 690, 694-695, 698-699, 702**
Breathe Air Set **677**
Drain Bowl **646, 648, 676**
Filters **642, 647, 650, 653, 655, 663-664, 666-667, 673, 678, 684, 687, 689, 690, 692-693, 697, 699, 702-703**
Lubricators **641, 647, 651, 654, 655, 663, 669, 674, 679, 684, 686, 690, 693, 698, 699, 701, 703**
Filter/Regulator **639, 649, 652, 655, 658, 659, 660, 669, 674, 683, 686, 697, 700-701, 703**
Filter + Regulator + Lubricator **637, 643, 647, 658, 660, 663 -664, 675, 680-681, 682, 683, 691, 696, 700**
Filter/Regulator + Lubricator **638, 649, 650, 653, 655, 671, 677, 683, 686, 689, 696, 699, 703**
Porting Block **644-645, 661, 671, 694, 698, 702**
Pressure Boosters & Accessories **705-706**
Pressure Switch/Valve **671, 685**
Regulators **640, 647, 649, 652, 655, 663, 668, 674, 678, 679, 684, 687, 689, 690, 695, 699, 701, 703-704**
Shut Off Valve **644, 670, 675, 680, 685, 687, 702**

Air Receiver & Kits **433-434**
Air Treatment Unit **682**

Air Tools
Air Couplings **1719**
Air Tool Accessories **1710**
Cutter **1718**
Drills **1708, 1717**
Grinders & Kits **1709, 1717**
Impact Hammer **1708, 1718**
Impact Wrenches **1706-1707, 1716**
Impact Wrench Kit **1707**
Nailer & Stapler **1708**
Ratchet Wrenches **1706, 1717**
Riveters **1717, 1720**
Sanders **1718**
Tool Balancers **1720**
Tyre Inflators & Adaptors **1721-1725**

Air Systems
Accessories **1079, 1087, 1092, 1094, 1100, 1106, 1107, 1113**
Aluminium Tube **1063, 1069, 1077, 1082, 1085, 1090**
Fittings & Adaptors **1063, 1065-1067, 1071-1072, 1075-1077, 1082-1086, 1091**
Manifolds **1078, 1084**
Nylon Pipe **1090, 1096**
Plastic Fittings & Adaptors **1090, 1093, 1096, 1115**
Plastic Pipe & Tube **1069, 1094, 1100, 1106, 1112-1113**
Press Fit Copper **1130-1134**
Press Fit Stainless Steel **1118-1127, 1135-1136**
Valves **1065-1066, 1073, 1077, 1084, 1086, 1096, 1100, 1106, 1112**
Air Vents & Eliminators **979**
Allen Keys **1737**
Angle Seat Valves **1048-1053, 1055**
Anti Bloc Grease **164**
Anti-Seize Paste **1586**
Anti-static Hose **1436**
Automotive Hose & Tube **1416-1417**

Automotive Tools
Brake Bleeder **1600**
Jet Flusher Gun **1600**
Jet Washer Gun **1600**
Oil Extractor **1600**

B

Bags **1741, 1759**
Balancing Valves **978**

Fluid-Air Components Ltd

Ball Valves
- *3-Way Valves* **924, 928, 930, 934-935, 937, 941, 951-952, 954**
- *Actuation* **993-1001, 1005-1012**
- *Bibcock* **931-932**
- *Brass* **922-935, 938-944**
- *Cast Iron Ball Valve* **936**
- *Compression Ball Valves* **137, 938-939, 944**
- *Drain Ball Valves* **929-930**
- *Direct Mount ISO 5211* **935-936, 944, 950-956**
- *Fire Safe Ball Valves* **953-955**
- *Hydraulic Ball Valves* **238-240**
- *Hygienic Ball Valves* **952**
- *Mini Ball Valves* **926-928, 935, 939, 940, 946**
- *Panel Mount Ball Valves* **933-934**
- *Plastic Ball Valves* **937, 945**
- *Pneumatic Ball Valves* **628-629**
- *Stainless Steel* **242, 946-956**
- *Vented Ball Valve* **932-933**
- *WRAS & GAS Ball Valves* **938-945**

Banding Systems & Tie Wraps **1519, 1552-1554**
Batteries **1764**
Barrel Nipples **1378-1382**
Bellows Flanges **1388**
Bending Spring **884**
Blow Guns
- *Air Blow Guns & Nozzles* **1593-1608, 1611-1612**
- *Air Jet Nozzles* **1611- 1612**
- *Air Knives & Amplifiers* **1612, 1614-1616**
- *Air Movers* **1613**
- *Automotive* **1600**
- *Blow/Vacuum Guns & Kits* **1609**
- *Safety Blow Guns & Nozzles* **1596, 1605-1608**
- *Test Equipment* **1612**

Bibcock **931-932**
Boiler Vent Valves **979**
Bolt Cutters **1732**
Bolt Kits
- *Flange Bolt Kit* **1384**

Bonded Seals & Kits **109-112**
Bottle Jack **278**
Brake Bleeder **1600**
Brass
- *Adaptors* **1165, 1176**
- *Compression Imperial* **1200-1202, 1205-1208**
- *Compression Metric* **1197-1199, 1203-1204, 1209-1212, 1216-1217**
- *Needle Valves* **243, 982-983**
- *Ball Valves* **922-935, 938-944**

Breathers **261**
Breathing Hose **1432**
Brushes & Handles
- *Cleaning Brush* **1683**
- *Glue Brush* **1107**
- *Pressure Wash Brush* **1675**
- *Vehicle Brushes* **1683**
- *Wire Brush* **1729-1730**

Bundy **1215**
Butt Weld Fittings **1392**
Butterfly Valves
- *Accessories* **971**
- *Actuation* **1002-1003, 1013-1014**
- *Hygienic Butterfly Valves* **967**
- *Lugged & Tapped* **970**
- *Wafer Pattern* **968-969**

C

Caliper **1739**
Cam & Groove Couplings **1467-1472**
- *Accessories* **1472**
- *Aluminium Couplings* **1468**
- *Brass Couplings* **1471**
- *Polypropylene Couplings* **1470**
- *Stainless Steel Couplings* **1469**

Caps & Plugs Plastic **113-114**
Carbon Steel Flanges **1387**
CETOP Directional Control Valves
- *CETOP 3 Manifolds* **208**
- *CETOP 3 Valves* **203-204, 207, 210-213, 220**
- *CETOP 5 Manifolds* **208**
- *CETOP 5 Valves* **205-207, 215-218, 220**
- *CETOP Coils & DIN Plugs* **205, 219**

Check Valves
- *Accessories* **960, 962, 964, 966**
- *Ball Check* **966**
- *Cromax* **964**
- *Double Check* **960**
- *Dual Plate* **964-966**
- *Hydraulic* **136, 241-243, 246, 963**
- *Cast Iron* **965**
- *Pneumatic* **792, 864**
- *Flanged* **963, 965-966**
- *Spring* **960-962, 964, 966**
- *Swing* **960-965**
- *Wafer Pattern* **961**

Chisel **1732**
Clamps (Tubing)
- *Clamping Rail* **190**
- *Clamping Rail Nuts* **190, 192**
- *Complete Clamps* **186**
- *Multiclamp* **201**
- *Noise & Vibration Protection* **187**
- *Steel & Flat Clamps* **199**
- *Series A Clamp Components* **188-192**
- *Series B Clamp Components* **190, 192-194**
- *Series C Clamp Components* **190, 195-197**
- *Series O Clamps* **200**
- *U-bolts & Saddles* **198**

Clamps & Clips
- *Banding Systems & Tie Wraps* **1519, 1552-1554**
- *Circlip Kits* **1557**
- *Counter Display Units* **1520, 1532, 1544**
- *Heavy-duty Pipe Clamps* **1515, 1524-1526, 1534-1535**
- *Hose Clips* **1517-1519**
- *Hose Crimper* **1558**
- *Kits* **1516, 1519-1520, 1530, 1531, 1544**
- *O-Clips* **1536-1539**
- *P-Clips* **1540-1544**
- *Pen & Pencil Clip* **1558**
- *Pipe Clips & Back Plates* **1545-1546**
- *Pipe Clips & Fixing Systems* **1548-1551**
- *Pipe Saddle Clips* **1547**
- *Quick Release Band Straps* **1552**
- *Steel Strapping & Accessories* **1555**
- *Super Clamps* **1521, 1523**
- *U Bolt Clamps* **1514**
- *Worm Drive* **1513-1514, 1527-1529, 1535, 1558**

Clamps & Stem Couplings **1480-1481**
Claw Couplings
- *ACK Claw Coupling* **1478**
- *DIN 3238 Claw Couplings* **1477**
- *DIN 3489 Claw Couplings* **1477**
- *DIN 3489 Stainless Steel Claw Couplings* **1479**
- *Double Lock QC Claw Coupling* **1473**
- *European Execution Double Lock Claw Coupling* **1473**
- *QAC Claw Couplings* **1474**
- *QAY US Execution Claw Couplings* **1474**
- *Safety Claw Coupling with Bore* **1478**
- *Series GK Brass Water Couplings* **1475**
- *SS Claw Couplings* **1474**
- *US Execution Claw Couplings* **1476**
- *Water Claw Couplings* **1479**

Cleaning Kit Hose **49, 184**
Cleaning Products
- *Cleaning Aerosols* **1571-1573**
- *Degreaser* **1569**
- *Food Grade Cleaning & Lubrication* **1578-1581**
- *Hand Cleaner* **1569**
- *Injection Moulding Sprays* **1581**
- *Paint Remover* **1583**
- *Wipes* **1573**

Cleaning Stations **1764**

Fluid-Air Components Ltd

Clogging Indicator 259
Commissioning Valves 978
Compressed Air Systems
Accessories 1079, 1087, 1092, 1094, 1100, 1106, 1107, 1113
Aluminium Tube 1063, 1069, 1077, 1082, 1085, 1090
Fittings & Adaptors 1063, 1065-1067, 1071-1072, 1075-1077, 1082-1086, 1091
Manifolds 1078, 1084
Nylon Pipe 1090, 1096
Plastic Fittings & Adaptors 1093, 1096, 1115
Plastic Pipe & Tube 1069, 1094, 1100, 1106, 1112-1113
Press Fit Copper 1130-1134
Press Fit Stainless Steel 1118-1127, 1135-1136
Valves 1065-1066, 1073, 1077, 1084, 1086, 1096, 1100, 1106, 1112
Compressed Air Ventilators 1616
Compression DIN Fittings
DIN Fittings 116-134
High Pressure Metric Tube Couplings 138-140
Stainless Steel 144-164
Standpipe Adaptors Metric 137
Compression Fittings Stainless Steel Twin Ferrule
Imperial 166-172
Metric 173-178
Compressor Oil 434
Compressors
Belt Driven Compressors 1699, 1701-1702
Direct Drive Compressors 1699-1701
Low Noise Compressors 1701, 1703
Condensate Management 432, 435
Coolant Hose System
Accessories 1500, 1502
Adaptors 1499, 1501
Hose Coil 1500, 1502
Nozzles 1498, 1501
Valves 1499, 1502
Copper Solder Fittings 1218-1219
Copper Washers 110
Counter Display Units 1520, 1532, 1544
Counters 614
Crimper 1558
Crowbar 1732
Cutting Tools 905, 913, 1729, 1731, 1743, 1745
Cylinders
Compact Cylinders 516-536
Grippers 542
ISO 15552 Cylinders & Accessories 478-515
Pencil Cylinder 537
Pneumatic Cylinders & Accessories 450-477
Rotary Drives 543-544
Round Cylinders 538-541

D

Dairy Hose 1415
Degreaser 1569
Diesel Oil Filters & Accessories 1629-1631
DIN Compression 116-134, 138-140, 144-164,137
DIN Connectors & Moulded Plugs 1043-1046
Dipsticks 262
Directional Control Valves
CETOP 3 Manifolds 208
CETOP 3 Valves 203-204, 207, 210-213, 220
CETOP 5 Manifolds 208
CETOP 5 Valves 205-207, 215-218, 220
CETOP Coils & DIN Plugs 205, 219
Display Boards 1749
Dosing Pumps 1634
Dome Oil Level Sight Glass 260
Dowty Seals & Kits 109-112
Drain Bowl 646, 648, 676
Drain Plugs & Accessories 1650-1653
Drain Pans & Funnels 1655-1656
Drain Filters 430
Drain Valves & Timers 1024-1025
Accessories 1025
Drain & Bleeder Valves 1058
Drill Accessories 1729
Drum Trolley 1638
Ducting 1437-1447
Anti-static Ducting 1440-1442
Clamps 1447
Food Grade Ducting 1438, 1442
High Temperature Ducting 1445
Industrial Ducting 1437-1444
Duct Tape 1585
Dust Caps & Plugs
Plastic Caps 113-114
Plastic Plugs 113-114
DKO Type Hydraulic Fittings 152, 160-162
Deburrer 1067, 1083, 1087
Counter Display Units 1520, 1532, 1544
Drum Tap 1623

E

Ear Defenders & Plugs 1753
Effluent Hose 1415
Elbow Flange Coupling 135
Electric Actuation 1002-1003, 1013-1014
Electric Actuator Kits 1013
Electrical Pumps 1635-1636
Elements 762, 247-248, 257-258
Engineering Consumables
Batteries 1764
Cleaning Stations 1764
Fire Extinguisher 1763
First Aid Kits 1763
Lockouts 1762-1763
EPDM Overbraid Hose 1420
Exhaust Valves 634-636
Eye Protection 1754

F

Face Masks 1755
Ferrules Hydraulic Hose
4SH 25
Hydraulic Hose Ferrules 16, 25, 30
Stainless Steel Ferrules 29
Files 1730
Filler Breather 261
Filter Elements 762, 247-248, 257-258
Filter Regulator Lubricator
Accessories 644-646, 648, 651, 654, 656, 662, 672, 675, 676, 681, 683, 688, 690, 694-695, 698-699, 702
Air Preparation 637-706
Breathe Air Set 677
Drain Bowl 646, 648, 676
Filters 642, 647, 650, 653, 655, 663-664, 666-667, 673, 678, 684, 687, 689, 690, 692-693, 697, 699, 702-703
Filter/Regulator 639, 649, 652, 655, 658, 659, 660, 669, 674, 683, 686, 697, 700-701, 703
Filter + Regulator + Lubricator 637, 643, 647, 658, 660, 663 -664, 675, 680-681, 682, 683, 691, 696, 700
Filter/Regulator + Lubricator 638, 649, 650, 653, 655, 671, 677, 683, 686, 689, 696, 699, 703
Porting Block 644-645, 661, 671, 694, 698, 702
Lubricators 641, 647, 651, 654, 655, 663, 669, 674, 679, 684, 686, 690, 693, 698, 699, 701, 703
Pressure Boosters & Accessories 705-706
Pressure Switch/Valve 671, 685
Regulators 640, 647, 649, 652, 655, 663, 668, 674, 678, 679, 684, 687, 689, 690, 695, 699, 701, 703-704
Shut Off Valve 644, 670, 675, 680, 685, 687, 702
Filters & Accessories Hydraulic 247-251
Filters Drain 430
Fire
Fire Extinguisher 1763
Fire Hose 1494-1495
Fire Hose Couplings 1494-1495
Fire Safe Ball Valves 953-955
Fire Sleeve Hose 44-45

Fluid-Air Components Ltd

- *Gate Valve* **957**
- *Instantaneous Fire Hose Couplings* **1493-1495**

Fire Sleeve **44-45**
First Aid Kits **1763**
Flange Couplings & Accessories **135**
Flange Seal Kits **112**

Flanges
- *150lb Flanges* **1195**
- *ABS Imperial Flanges & Gaskets* **1099**
- *Bolts & Washers* **108**
- *Carbon Steel Flanges* **1387**
- *CAT Style Flange Inserts* **27**
- *Expansion Bellows Flanges* **1388**
- *Flange Bolt Kits* **1384**
- *Flange Gaskets* **1389-1390**
- *Flanged Coupling* **135**
- *Flanged Hose Tails* **1492**
- *Forged Steel Flanges* **1386**
- *Malleable Iron Flanges* **1348, 1367**
- *O-Rings/Seals* **108, 112**
- *Poclain Style Flange Insert* **26**
- *SAE 3000 Flanged Hose Insert* **24, 27, 36**
- *SAE 6000 Flanged Hose Insert* **24, 27, 36**
- *SAE Butt Weld 3000* **106-107**
- *SAE Butt Weld 6000* **106-107**
- *SAE Socket Weld Flanges 3000* **105-106, 108**
- *SAE Socket Weld Flanges 6000* **105-106, 108**
- *SAE Threaded Flanges 3000* **102-104**
- *SAE Threaded Flanges 6000* **102-104**
- *Split Flange Half* **24, 102**
- *Stainless Steel Flanged Hose Tails* **1492**
- *Stainless Steel Flanges 150lb* **1195**
- *Stainless Steel SAE 3000 Flanged Hose Insert* **1235**
- *Stainless Steel SAE 6000 Flanged Hose Insert* **1235**
- *Stainless Steel Split Flange Half* **1235**
- *UPVC Flanges & Gaskets* **1105, 1111**

Flanges & Accessories Hydraulic **101-108**
Flaretite Seal **111**
Float Level Switches **441-442**
Float Valve & Accessories **1059**
Floor Paint & Repairs **1561-1562**
Flow Control Regulator **628, 634, 804-807, 814-816**
Flow Control Valve In-line **634-636**
Flow Control Valves **241, 207, 213, 218, 220**
Flow Indicators **438**

Flow Meters
- *Compressed Air Flow Meters* **254**
- *Flow Meters* **252, 439-440, 445**
- *Oil & Water* **254**
- *Water Meter* **1057, 445**

Flow Sensor **420, 427**
Flow Switches **437**
Fluid Level Gauge **261, 443-444**
Fluid Level Temperature Gauge **252**
Foam Pellets **49, 184**
Foot Valves & Strainers **962, 1436**

Fuelling Equipment & Accessories
- *Accessories* **1623, 1625**
- *Adblue Fuelling Meter* **1626**
- *Adblue Nozzles, Pumps & Hose* **1623-1624, 1633, 1636**
- *Adblue Stainless Steel Auto Nozzle* **1620-1621**
- *Adblue Tank Gauges* **1654**
- *Air Operated Pumps* **1636-1637**
- *Diesel Oil Filters & Accessories* **1629-1631**
- *Dosing Pumps* **1634**
- *Electrical Pumps* **1635-1636**
- *Filter & Transfer Unit* **1627**
- *Filtration* **1627-1628**
- *Fuel Dispensing Hose Kits* **1622, 1625**
- *Fuelling Meters* **1626**
- *Manual Pumps* **1632-1634, 1637**
- *Oil Delivery* **1638**
- *Pump Kits* **1624, 1636-1637**
- *Trigger Guns & Nozzles* **1620-1621**

Funnels & Drain Pans **1655-1656**

G

Galvanized Overbraid Rubber Hose **1420**

Garden Hose & Accessories
- *Alloy Roses* **1679**
- *Hose Connector Sets* **1679**
- *Irrigation Pipe* **1680**
- *Rain Lance* **1679**
- *Spray Guns* **1679**
- *Sprinklers* **1680**
- *Water Guns* **1679**
- *Water Nozzles* **1679**

Gas Hose **1418**
Gaskets **1389-1390**
Gate Valves & Accessories **957-959**

Gauges
- *Dry Gauges & Accessories* **410-413**
- *Glycerine Filled Gauges & Accessories* **264, 266-267, 414-416**
- *HVAC Gauges & Accessories* **418**
- *Temperature* **265, 417**
- *Vacuum Gauges* **411-412, 415-416**

Gear Motor **234-235**

Gear Pump
- *Cast Iron Gear Pump* **236**
- *Gear Pump* **231-233**

Globe Valves **975-977**
Gloves **1756-1758, 1760**

Glue & Bonding
- *Adhesive Spray* **1583**
- *Glues & Bonding* **1587**
- *Plate & Cloth Tape* **1391**
- *Sealants* **1585-1586**
- *Self Amalgamating Tape* **45**
- *Super Glue* **1585**
- *Thread Lock Adhesives* **1584, 1586**

Go/No Go Gauge **16**
Grease Coupler & Adaptors **1648**
Grease Filler Gun **1640**
Grease Guns **1639-1641**
Grease Hose **1639**
Grease Nipples **1643-1644**
Grease Nipple Kits **1643**
Grease Pump Kit **1640-1642**
Grease Systems Manual **1647**
Grease Systems Remote **1647**

Greasing & Lubrication Equipment
- *Compression Fittings & Adaptors* **1645-1646**
- *Grease Coupler & Adaptors* **1648**
- *Grease Filler Gun* **1640**
- *Grease Guns* **1639-1641**
- *Grease Hose* **1639**
- *Grease Nipples* **1643-1644**
- *Grease Nipple Kits* **1643**
- *Grease Pump Kit* **1640-1642**
- *High Pressure Hose & Accessories* **1647, 1649**
- *Lubrication & Pumping Equipment* **1647**
- *Manual Grease Systems* **1647**
- *Push-in Fittings* **1646**
- *Refillable Bearing Indicator* **1641**
- *Remote Grease Systems* **1647**
- *Thread Gauge* **1648**

H

Hand Cleaner & Wipes **1569, 1573**

Hand Rail System
- *Fittings & Tube* **1393-1395, 1398**
- *Swivel Style* **1396-1398**

Hand Tools
- *Allen Keys* **1737**
- *Brushes* **1729, 1730**
- *Bolt Cutters* **1732**
- *Chisel* **1732**
- *Cutting Tools* **1729, 1731**
- *Drill Accessories* **1729**
- *Files* **1730**
- *G & F Clamps* **1740**
- *Hammers* **1732**
- *Lamps & Torches* **1740-1741**

Fluid-Air Components Ltd

- *Measuring Equipment* **1739**
- *Pliers* **1731, 1733**
- *Pipe Cutters* **1731**
- *Saws* **1730**
- *Screwdrivers* **1734-1736**
- *Spirit Levels* **1740**
- *Tool Sets* **1737-1739**
- *Wrecking Bar* **1732**
- *Wrenches* **1734**

Hank Hemp **1391**

Hard Hats **1752**

Head Protection **1752**

Hose
- *Automotive Hose & Tube* **1416-1417**
- *Breathing Hose* **1432**
- *Dairy Hose* **1415**
- *Effluent Hose* **1415**
- *EPDM Overbraid Hose* **1420**
- *GAS Hose* **1418**
- *Layflat* **1424-1426**
- *Layflat Assemblies* **1426**
- *Overbraid Hose* **1420**
- *Overbraid Hose Accessories* **1420, 1421**
- *Oxygen Hose* **1419**
- *Propane Hose* **1419**
- *PVC Braided/Reinforced* **1403-1405, 1407**
- *PVC Food Grade* **1406, 1432**
- *PVC Hi-Vis* **1408**
- *PVC Hose* **1409, 1432, 1432**
- *PVC Hose Assemblies* **1409**
- *Rubber Air Hose* **1410, 1411, 1414**
- *Rubber Air Hose Assemblies* **1411, 1414**
- *Safety Compressed Air Hose* **1412-1413**
- *Safety Compressed Air Hose Assemblies* **1413**
- *Suction Hose* **1427-1431**
- *Wash Down Hose* **1415**
- *Water Hose* **1415, 1422**
- *Welding Hose* **1418-1419**

Hose Anti-static **1436**

Hose Assemblies
- *Air Hose* **1411**
- *Breaker Hose* **15**
- *Compressed Air Hose* **1412-1414**
- *Layflat Hose* **1426**
- *Leader Hose* **334, 338, 355**
- *Pneumatic Hose Assemblies* **900-903, 910, 916**
- *PVC Hose* **1409**
- *Steam Hose & Assemblies* **1482**
- *Suction Hose* **1427**
- *Test Point Hose Assemblies* **270**
- *Water Suction Hose* **1430**

Hose Cleaning Kits
- *Pellet Launcher Kits* **49, 184**
- *Foam Pellets* **184**

Hose Crimper **1421, 1558**

Hose Fire Sleeve **44-45**

Hose Foot Valves & Strainers **1436**

Hose Guard
- *Hose Burst Guard* **46**
- *Hose Protection Sleeve* **46**
- *Hose Wrap Sleeve* **46**
- *Spiral Hose Guard* **47-48**
- *Steel Spring Guard* **45**
- *Fire Sleeve* **44-45**

Hose Industrial **1433-1435**
- *Brewflex Hose* **1435**
- *Diesel Hose* **1434**
- *Marine Exhaust Hose* **1434**
- *Marine Fuel Hose* **1433**
- *Multipurpose Hose* **1435**
- *Steam Hose* **1435**
- *Suction Hose* **1434**
- *XLPE Chemical Hose* **1433**

Hose Reels **1448-1466**
- *ATEX Hose Reels* **1462, 1465**
- *Electrical Reels* **1459-1460**
- *Fire Hose Reels & Accessories* **1466**
- *Heavy-duty Hose Reels* **1456, 1462, 1464**
- *Hi -Vis Hose Reels* **1449-1451, 1453, 1456, 1461**
- *Mountable Steel Air Hose Reels* **1450-1453, 1457, 1459-1462, 1465**
- *Mountable Steel High Pressure Water Reels* **1452-1453, 1457**
- *Petro-chemical Hose Reels* **1460**
- *Safety Reels* **1459-1460**
- *Stainless Steel Hose Reels* **1461-1462**
- *Standard Hose Reels* **1458**
- *Welding Hose Reels* **1459**
- *Water Jet Reels* **1459**

Hose Tails
- *Aluminium* **1147**
- *Brass* **1140-1146, 1148, 1154-1155, 1419**
- *Combination Steel Nipples & Hose Joiners* **1497**
- *Ferrules Low Pressure* **1556**
- *Hexagon Nuts & Tails* **1497**
- *Emergency Connector Set* **1154**
- *Plastic* **1149-1151, 1153**
- *PVDF* **1152**
- *Hose Tail Flanges* **1492**

HVAC Gauges & Accessories **418**

Hydraulic Adaptors
- *Adaptors* **54-81**
- *High Pressure Adaptors* **81-84**
- *JIC Adaptors* **72-80**
- *JIC Stainless Steel Adaptors* **95-100**
- *ORFS Adaptors* **81**
- *Stainless Steel Adaptors* **85-87**

Hydraulic Ball Valves **238-240**

Hydraulic Check Valves **136, 241-243, 246**

Hydraulic Compression DIN Fittings
- *DIN Fittings* **116-134**
- *High Pressure Metric Tube Couplings* **138-140**
- *Stainless Steel* **144-164**
- *Standpipe Adaptors Metric* **137**

Hydraulic Control Valves
- *Mono Block* **237**
- *Sectional* **237**

Hydraulic Directional Control Valves
- *CETOP 3 Manifolds* **208**
- *CETOP 3 Valves* **203-204, 207, 210-213, 220**
- *CETOP 5 Manifolds* **208**
- *CETOP 5 Valves* **205-207, 215-218, 220**
- *CETOP Coils & DIN Plugs* **205, 219**

Hydraulic Filtration
- *Filtration & Accessories* **247-251, 255-259**

Hydraulic Flow Control Valves **241**

Hydraulic Flow Metering
- *Flow Meters* **252**
- *Test & Flow Indicators* **252-253**

Hydraulic Gauges & Accessories **263-267**

Hydraulic Hose
- *1SC Compact* **8**
- *2SC Compact* **9**
- *4SH Multi Spiral* **12**
- *4SP Multi Spiral* **11**
- *100R1AT* **6**
- *100R2AT* **7, 10**
- *100R4 Suction & Delivery* **14**
- *100R6 Push Style* **38-39**
- *100R7 Thermoplastic* **13**
- *MSHA Hose* **10**

Hydraulic Hose Connectors/Inserts
- *Banjo Bolt* **23**
- *Banjo Insert* **23**
- *BSPP* **17-18**
- *BSPT* **18**
- *Hose Joint* **23**
- *JIC* **19**
- *Metric* **20-21**
- *NPT* **23**
- *ORFS* **22**
- *SAE 3000* **24**
- *SAE 6000* **24**
- *Split Flange Half* **24**

Hydraulic Hose Ferrules
- *4SH* **25**

Fluid-Air Components Ltd

- *Hydraulic Hose Ferrules* **16, 25, 30**
- *Stainless Steel Ferrules* **29**

Hydraulic Imperial Compression Fittings
- *OD & Nominal Bore* **141-143**

Hydraulic Interlock Hose Connectors
- *BSPP* **25**
- *CAT Style Flange* **27**
- *JIC* **25**
- *Metric* **26**
- *ORFS* **26**
- *Poclain Style Flange* **26**
- *SAE 3000* **27**
- *SAE 6000* **27**

Hydraulic Lifting Equipment
- *Accessories* **278**
- *Bottle Jack* **278**
- *Cylinders & Kits* **275, 277**
- *Pumps* **276**
- *Toe Jack* **278**
- *Trolley Jack* **1739**

Hydraulic Manifold **208**

Hydraulic Needle Valves **243, 982-983**

Hydraulic Oils **283**

Hydraulic Oil Coolers **273**
- *Air Blast* **273**
- *Motor Inline* **273**
- *Compact Cooler Oil/Water* **273**

Hydraulic Pumps
- *Hydraulic Cast Iron Gear Pump* **236**
- *Hydraulic Gear Pump* **231-233**
- *Hydraulic Hand Pumps & Accessories* **229-230**
- *Hydraulic Piston Pump* **224-225**
- *Industrial Vane Pumps & Accessories* **222-223**

Hydraulic Quick Release Couplings
- *70KB Series* **317, 320**
- *71 Series* **319-320**
- *75 Series* **319**
- *H Series* **318, 320**
- *ISO 16028 Interchange, Flat Face* **292-293, 299, 301**
- *ISO A Interchange* **290, 296-298, 309**
- *ISO B Interchange* **291, 297, 300, 310**
- *Nordic Interchange* **297**
- *Parker Profile FF Series* **311**
- *PLT Colour Safe System* **302-303**
- *Screw on* **294, 304, 306-307, 402**
- *T Series* **293**
- *T2300 Series* **313**
- *T2500 Series* **313**
- *T3800 Series* **314**
- *T5000 Series* **314**
- *T7500 Series* **315**
- *T10000 Series* **315**
- *T15000 Series* **316**
- *THP Series* **316**
- *TFF Series* **312**
- *TIF Series* **313**
- *Trailer Brake Interchange* **292**
- *TDG Swivel Joints* **312**
- *Ultra High Pressure* **305**

Hydraulic Reusable Fittings
- *Ferrules* **41**
- *Inserts* **41**

Hydraulic SAE Flanges & Accessories **101-108**
- *Bolts* **108**
- *Spring Washers* **108**
- *O-Rings* **108**

Hydraulic Seals & Kits **109-112**

Seal Kits **112**

Hydraulic Spill Kits
- *Kits* **281-282**
- *Prevention & Absorption* **279-284**

Hydraulic Stainless Steel Hose Connectors/ Inserts
- *Banjo Bolt* **34**
- *Banjo Insert* **34**
- *BSPP* **30**
- *BSPT* **30**
- *Jet Wash Female* **34**
- *JIC* **31**
- *Metric* **32-33, 35**
- *ORFS* **34**
- *SAE 3000* **36**
- *SAE 6000* **36**
- *Split Flange Half* **36**

Hydraulic Stainless Steel Reusable Fittings
- *Inserts* **41**
- *Ferrules* **41**

Hydraulic Tank Accessories
- *Dip Sticks* **260**
- *Magnetic Tank Cleaner* **260**
- *Sight Glasses* **260-262**
- *Breathers* **261**
- *Fluid Level Guage* **261**

Hydraulic Test Point Couplings
- *Test Point Accessories* **269-272**
- *Test Point Couplings* **269-272**
- *Test Point Hose Assemblies* **270**
- *Test Point Kits* **272**

Hydraulic Threaded Valves
- *Check Valve* **246**
- *Control Valves* **246**
- *Diverter Valve* **245**
- *Flow Dividers* **246**
- *Hose Burst Valve* **245**
- *Pilot Operated Vales* **244**
- *Pressure Reducing Valves* **244**
- *Overcentre Valves* **244**
- *Shuttle Valve* **244**
- *Swivel Joints* **245**

Hydraulic Tube
- *Imperial* **182**
- *Metric* **180, 181**
- *Stainless Steel Metric & Imperial* **183, 1185**

Hydraulic Tube Clamps
- *Clamping Rail* **190**
- *Clamping Rail Nuts* **190, 192**
- *Complete Clamps* **186**
- *Multiclamp* **201**
- *Noise & Vibration Protection* **187**
- *Steel & Flat Clamps* **199**
- *Series A Clamp Components* **188-192**
- *Series B Clamp Components* **190, 192-194**
- *Series C Clamp Components* **190, 195-197**
- *Series O Clamps* **200**
- *U-bolts & Saddles* **198**

Hydraulic Twin Ferrule Stainless Steel Compression Fittings
- *Imperial* **166-172**
- *Metric* **173-178**

Hygienic BS Type Stainless Steel
- *Accessories* **1192**
- *Clamps* **1193**
- *Pipe Fittings* **1191-1192**
- *Tube* **1192**

I

IBC Off Load System **1491**

Imperial Tube **182**

Industrial Cleaning Equipment
- *Dispensers* **1761**
- *Wipes* **1761**
- *Wiper Rolls* **1761**

Industrial Hose **1433-1435**

Injection Moulding Couplings **390-391**

Injection Moulding Sprays **1581**

Inserts Hydraulic Hose Connectors
- *Banjo Bolt* **23**
- *Banjo Insert* **23**
- *BSPP* **17-18**
- *BSPT* **18**
- *Hose Joint* **23**
- *JIC* **19**
- *Metric* **20-21**
- *NPT* **23**
- *ORFS* **22**
- *SAE 3000* **24**
- *SAE 6000* **24**
- *Split Flange Half* **24**

Fluid-Air Components Ltd

Inserts Hydraulic Stainless Steel Hose Connectors
- *Banjo Bolt* **34**
- *Banjo Insert* **34**
- *BSPP* **30**
- *BSPT* **30**
- *Jet Wash Female* **34**
- *JIC* **31**
- *Metric* **32-33, 35**
- *ORFS* **34**
- *SAE 3000* **36**
- *SAE 6000* **36**
- *Split Flange Half* **36**

Instrumentation Fittings
- *Stainless Steel* **88-89**

Instrumentation Manifold Valve **981**
Integrated Compressed Air Treatment Unit **682**

Interlock Hose Connectors
- *BSPP* **25**
- *CAT Style Flange* **27**
- *JIC* **25**
- *Metric* **26**
- *ORFS* **26**
- *Poclain Style Flange* **26**
- *SAE 3000* **27**
- *SAE 6000* **27**

Irrigation Pipe **1680**

J

Jet Flusher Gun **1600**
Jet Washer Gun **1600**
Jubilee Clips **1517-1521, 1541, 1552**
Jointing Compound **1391**

K

Knife Gate Valve **959**
Knife Gate Valves Actuated **1004**
Knee Pads **1759**

L

Lamps & Torches **1740-1741**
Leader Hose **334, 338, 355**
Leak Detection Spray **1577**
Level Gauge **261, 443-444**
Level Temperature Guage **252**
Lever Lock Water Pump Couplings **1503-1510**

Lifting Equipment
- *Accessories* **278**
- *Bottle Jack* **278**
- *Cylinders & Kits* **275, 277**
- *Pumps* **276**
- *Toe Jack* **278**
- *Trolley Jack* **1739**

Lifting Equipment & Accessories **274-278**
Lithium Grease Cartridge **1639**
Logic Elements **613**
Logic Valves **611-612**

Lubrication Equipment
- *Compression Fittings & Adaptors* **1645-1646**
- *High Pressure Hose & Accessories* **1647, 1649**
- *Grease Coupler & Adaptors* **1648**
- *Grease Filler Gun* **1640**
- *Grease Guns* **1639-1641**
- *Grease Hose* **1639**
- *Grease Nipples* **1643-1644**
- *Grease Nipple Kits* **1643**
- *Grease Pump Kit* **1640-1642**
- *Lubrication & Pumping Equipment* **1647**
- *Manual Grease Systems* **1647**
- *Push-in Fittings* **1646**
- *Refillable Bearing Indicator* **1641**
- *Remote Grease Systems* **1647**
- *Thread Gauge* **1648**

Luggage **1759**

M

Magnetic Tank Cleaner **260**

Maintenance Paints & Sprays
- *Anti-Corrosion* **1563, 1576**
- *Anti-Slip* **1564**
- *Fillers* **1590**
- *Flooring* **1561-1562, 1572**
- *Fluorescent Top Coats* **1564**
- *Heat Resistant* **1564**
- *Lubricants* **1568-1569, 1574-1575**
- *Maintenance Sprays* **1568**
- *Marking* **1564**
- *Metallics* **1564**
- *Paint* **1565-1567**
- *Rubber Coating Spray* **1564**

Malleable Iron Fittings
- *Accessories* **1384-1385**
- *Barrel Nipples* **1378-1382**
- *Flanges* **1348, 1367**
- *Girder Clamps* **1384**
- *Pipe Fittings* **1336-1382**
- *School Board Pipe Bracket* **1376, 1384**
- *Studding* **1385**
- *Tapping Pipe Rings* **1376, 1385**

Manifolds
- *Aluminium* **1220-1221, 1223**
- *Brass* **1222**
- *Stainless Steel* **1223**
- *Hydraulic* **208**

Manual & Mechanical Valves **545-574**
- *Foot Valves* **549, 560, 565, 574**
- *Lever Valves* **545,547-549, 554-556, 558, 561-563, 565-570, 572-574**
- *Push Button Valves* **546-547, 557-558, 560-561, 564, 567-573**
- *Roller Valves* **545, 548, 550-553, 557-559, 565, 569-570, 572-573**
- *Slide Valves* **549, 563**

Manual Pumps **1632-1634, 1637**
Marine Hose **1433-1434**
Metric Hydraulic Tubing **180, 181**
Miniature Fittings M3-M6 **1155**

Misting Systems
- *Dry Fog Systems* **1691**
- *Fans* **1690**
- *Filters* **1695**
- *Fogger* **1691**
- *Misting System Controllers* **1696**
- *Nozzles & Adaptors* **1692-1694**
- *Pump Kits* **1687-1689**

Modular Coolant Hose System **1498-1502**
- *Accessories* **1500, 1502**
- *Adaptors* **1499, 1501**
- *Hose Coil* **1500, 1502**
- *Nozzles* **1498, 1501**
- *Valves* **1499, 1502**

Mono Block Control Valve **237**
Mortar Hose Couplings & Plugs **1492**
MSHA Mining Hose **10**
Mufflers & Silencers **630-635**
Multi Spiral Hose 4SH **12**
Multi Spiral Hose 4SP **11**

N

NAMUR Solenoid Valves **1020-1021**
Nail Clips **884**
NBR Overbraid Hose **1420**

Needle Valve
- *Brass* **982**
- *Hydraulic* **243, 982-983**
- *Stainless Steel* **982-983**

Nominal Bore
- *Hydraulic Imperial Compression Fittings* **141-143**

Nominal Bore Fittings **141-143**

Non-return Valves
- *Hydraulic* **136, 241-243, 246**
- *Pneumatic* **864**

O

O-Rings
- *Hydraulic Seals & Kits* **109-112**

O-Clips **1536-1539**

Oil Cooler
- *Air Blast* **273**
- *Compact Cooler Oil/Water* **273**
- *Motor Inline* **273**

Oil Delivery System **1638**
Oil Drain Plugs & Accessories **1650, 1653**
Oil Drum Transportation **1638**

Fluid-Air Components Ltd

Oil Extractor 1600
Oil Hydraulic 283
Oil, Compressor 434
Over & Out Switch 546-547
Overbraid Hose Accessories 1420, 1421
Oxy/Acetylene Couplings 1419
Oxygen Hose Sets 1419

P

Padlocks 1763
Paint & Sprays
Anti-Corrosion 1563
Acrylic Spray Paints 1582
Paint Marker Pens 1582
Primer 1583, 1588
Paint Remover 1583
Paint Spraying Equipment
Air Powered Diaphragm Pumps 1712
Airless Spray Gun & Accessories 1711
Industrial Airless Paint Sprayer 1711
Paint Mixing Tank 1712
Spray Guns & Nozzles 1713-1715, 1720
Paper Products 1761
P-Clips 1540-1544
Pellet Launcher Kits 49, 184
Pen & Pencil Clip 1558
Pilot Valves 600-606, 608-610
DIN Connectors & Moulded Plugs 1043-1046
Pilot Operated Check Valves 207, 213, 218
Pilot Operated Solenoid Valves 1026-1042
Pinch Valves 627, 1050
Pipe Benders 182, 1079, 1746
Pipe Clips & Back Plates 1545-1546
Pipe Clips & Fixing Systems 1548-1551
Pipe Cutters 882, 905, 1731, 1745
Pipe Jointing Compound 1391
Pipe Lagging 1215
Pipe Repair Couplings 1557
Pipe Saddle Clips 1547
Plastic Caps 113-114
Plastic Plugs 113-114
Pliers 1731, 1733
Pneumatic Actuation 993-1004, 1015-1017
Accessories 1022-1023
Axial Flow 1055
Pneumatic Ball Valves 628-629
Pneumatic Check Valves 627-629
Check & Non-return Valves 627-629
Pinch Valves 627
Pneumatic Counters 614
Pneumatic Cylinders
Compact Cylinders 516-536
Grippers 542
ISO 15552 Cylinders & Accessories 478-515
Pencil Cylinder 537
Pneumatic Cylinders & Accessories 450-477
Rotary Drives 543-544
Round Cylinders 538-541
Pneumatic Flow Control Valve In-line 634-636
Pneumatic Flow Regulators 656
Quick-Fit 1160
Pneumatic ISO 5599 Valves 617-622
Pneumatic Logic Valves 611-612
Pneumatic Manual & Mechanical Valves 545-574
Pneumatic Quick Release Couplings
2 Series 330
13 Series 331
14 Series 332-333
17 Series 325, 334
18 Series 335-336
19 Series 325, 337-338, 404
20 Series 339-340
21 Series 326, 341-349
22 Series 350
23 Series 326, 351, 404
24 Series 352
25 Series 327, 353-356, 358-361, 404
26 Series 362-365, 404
27 Series 328, 366-367
30 Series 369
33 Series 370
34 Series 371
40 Series 372
41 Series 373
45 Series 374
48 Series 375-376, 392
51 Series 377
52 Series 378
57 Series 379
68 Series 328, 380
86 Series 381-382
87 Series 383
95 Series 384
1100 Series 386
1300 Series 387
1600 Series 357
1700 Series 368
1800 Series 388
Air Brake 406
Air Couplings 329, 393-403
Injection Moulding 390-391
Safety Couplings 389
Schrader 385
ST Series 405
Pneumatic Safety Unit 616
Pneumatic Silencers & Mufflers 630-635
Stainless Steel Silencers 630
Pneumatic Solenoid Valves 575-599, 607, 617-622
Pneumatic Specialist Valves 615-616, 623-624
Pneumatic Tubing
Air Brake Tube 910
Hose Assemblies 900-903, 910, 916
Nylon Tube 913-917
Nylon Recoil Hoses 916
Polyamide High Resistant Tubing 906
Polyurethane Tube 898-904, 906-909, 912, 918
Polyurethane Recoil Hoses 899-904
Tube Cutters 905, 908, 913
Pneumatic Vacuum Switches 425
Pneumatic Vibrators 625-626
Ball Vibrators 625-626
Piston Vibrators 625-626
Turbine Vibrators 625-626
Poclain Style Flange Insert 26
Polypropylene Plastic Adaptors 1177-1178
Pothole & Tarmac Repair 1561-1562
PPE
Accessories 1754
Ear Protection 1753
Eye Protection 1754
Hand Protection 1756-1758, 1760
Head Protection 1752
Knee Protection 1759
Overalls & Sleeves 1760
Overshoes 1760
Respiratory Protection 1755
Press Fit
Press Fit Copper 1130-1134
Press Fit Stainless Steel 1118-1127, 1135-1136
Press Fit Tools 1744
Pressure Reducing Valves
Hydraulic 244, 207, 213, 218
Industrial 980
Pressure Relief Valves
Hydraulic 207, 213, 218
Industrial 985-987, 990-992
Pneumatic 985-987
Pressure Sensors 420, 428-429, 864
Pressure Spray Equipment 1681-1683
Pressure Switches 420, 423-424, 429, 613, 624, 1054
Pressure Transducers 422
Pressure Washers Equipment
Accessories 1675
Extended Lances 1671

Fluid-Air Components Ltd

- *Foam Injection Bottle* **1672**
- *Lances* **1672**
- *Pressure Lance Configurator* **1668-1669**
- *Pressure Washer Floor Cleaner* **1675**
- *Pressure Washer Hose* **1676-1677**
- *Pressure Washer Hose Assemblies* **1678**
- *Pressure Washer Lances* **1666**
- *Pressure Washer Lance Triggers* **1670**
- *Pressure Washer Nozzles & Adaptors* **1673-1674**
- *Pressure Washer Triggers & Lance Assemblies* **1667**
- *Twin Lances* **1672**

Professional Tools
- *Accessories* **1744**
- *Compact Press Tools* **1744**
- *Press Tool* **1744**
- *StrutSlayr Shear Heads* **1744**

Propane Hose Set **1419**

Protective Hose Sleeve
- *Fire Sleeve* **44-45**
- *Heat Shrink* **45**
- *Hose Burst Guard* **46**
- *Hose Protection Sleeve* **46**
- *Hose Wrap Sleeve* **46**
- *Steel Spring Hose Guard* **45**
- *Self Amalgamating Tape* **45**
- *Spiral Hose Guard* **47-48**

PTFE Tape & Sealant **1391**

Pump Kit
- *Drag-in Pump Kit* **1610**

Pumps
- *Air Operated Diaphragm Pumps* **1684-1685**
- *Cast Iron Gear Pump* **236**
- *Dosing Pumps* **1634**
- *Electrical Pumps* **1635-1636**
- *Gear Pump* **231-233**
- *Hydraulic Cast Iron Gear Pump* **236**
- *Hydraulic Gear Pump* **231-233**
- *Hydraulic Piston Pump* **224-225**
- *Hydraulic Hand Pumps & Accessories* **229-230**
- *Industrial Vane Pumps & Accessories* **222-223**
- *Manual Pumps* **1632-1634, 1637**
- *Pump Valve 5 Way* **930, 1058**

Pumps Hydraulic
- *Hydraulic Cast Iron Gear Pump* **236**
- *Hydraulic Gear Pump* **231-233**
- *Hydraulic Hand Pumps & Accessories* **229-230**
- *Hydraulic Piston Pump* **224-225**
- *Industrial Vane Pumps & Accessories* **222-223**

Push Button Tap **1060**

Push In Fittings
- *Air Brake Push In Fittings* **887-894**
- *Check Valves* **792**
- *Flow Regulators & Function Fittings* **804-807, 814-816, 824-831, 864**
- *Kits* **767, 781, 823, 844**
- *Metal Push in Fittings Imperial* **856-857, 863**
- *Metal Push In Fittings Metric* **844-851, 860-862, 865-866, 870-874**
- *Plastic Push In Fittings Imperial* **774-779, 790-791, 800-801, 840-842**
- *Plastic Push In Fittings Metric* **768-773, 780-786, 787-789, 793-799, 802-803, 808-813, 817-822, 832-839, 852-855, 858-859, 868-869**
- *Plumbing Push In Fittings & Accessories* **880-886**
- *Stainless Steel Push In Fittings* **875-879**

Push Style Hose System
- *Push Style Hose* **38-39**
- *Push Style Inserts* **40**

PVC Braided/Reinforced Hose **1403-1405, 1407**

PVC Food Grade Hose **1406, 1432**

PVC Hi-Vis Hose **1408**

PVC Hose **1409, 1432**

PVC Hose Assemblies **1409**

PVDF Adaptors **1179**

Proportional Valves **635**

Q

Quick-fit Fittings
- *Brass* **1156-1159, 1162**
- *Flow Regulators* **1160**
- *Plastic* **1163**
- *PVDF* **1164**

Quick Oil Drain Plugs **1650-1653**

Quick Release Couplings, Hydraulic
- *70KB Series* **317, 320**
- *71 Series* **319-320**
- *75 Series* **319**
- *H Series* **318, 320**
- *ISO 16028 Interchange, Flat Face* **292-293, 299, 301**
- *ISO A Interchange* **290, 296-298, 309**
- *ISO B Interchange* **291, 297, 300, 310**
- *Nordic Interchange* **297**
- *Parker Profile FF Series* **311**
- *PLT Colour Safe System* **302-303**
- *Screw on* **294, 304, 306-307, 402**
- *T Series* **293**
- *T2300 Series* **313**
- *T2500 Series* **313**
- *T3800 Series* **314**
- *T5000 Series* **314**
- *T7500 Series* **315**
- *T10000 Series* **315**
- *T15000 Series* **316**
- *THP Series* **316**
- *TFF Series* **312**
- *TIF Series* **313**
- *Trailer Brake Interchange* **292**
- *TDG Swivel Joints* **312**
- *Ultra High Pressure* **305**

Quick Release Couplings Pneumatic
- *2 Series* **330**
- *13 Series* **331**
- *14 Series* **332-333**
- *17 Series* **325, 334**
- *18 Series* **335-336**
- *19 Series* **325, 337-338, 404**
- *20 Series* **339-340**
- *21 Series* **326, 341-349**
- *22 Series* **350**
- *23 Series* **326, 351, 404**
- *24 Series* **352**
- *25 Series* **327, 353-356, 358-361, 404**
- *26 Series* **362-365, 404**
- *27 Series* **328, 366-367**
- *30 Series* **369**
- *33 Series* **370**
- *34 Series* **371**
- *40 Series* **372**
- *41 Series* **373**
- *45 Series* **374**
- *48 Series* **375-376, 392**
- *51 Series* **377**
- *52 Series* **378**
- *57 Series* **379**
- *68 Series* **328, 380**
- *86 Series* **381-382**
- *87 Series* **383**
- *95 Series* **384**
- *1100 Series* **386**
- *1300 Series* **387**
- *1600 Series* **357**
- *1700 Series* **368**
- *1800 Series* **388**
- *Air Brake* **406**
- *Air Couplings* **329, 393-403**
- *Injection Moulding* **390-391**
- *Safety Couplings* **389**
- *Schrader* **385**
- *ST Series* **405**

R

Radiator Key **883**

Rain Lance **1679**

Receiver & Kits **433-434**

Reinforcing Tube Insert/Ring **182**

Repair Couplings **1557**

Fluid-Air Components Ltd

Retainer **1585-1586**
Retention System for Pressure Hoses **42-43**
Reusable Fittings Hydraulic
Ferrules **41**
Inserts **41**
Reusable Stainless Steel Fittings
Inserts **41**
Ferrules **41**
Ring Main
Accessories **1079, 1087, 1092, 1094, 1100, 1106, 1107, 1113**
Aluminium Tube **1063, 1069, 1077, 1082, 1085, 1090**
Fittings & Adaptors **1063, 1065-1067, 1071-1072, 1075-1077, 1082-1086, 1091**
Manifolds **1078, 1084**
Nylon Pipe **1090, 1096**
Plastic Fittings & Adaptors **1090, 1093, 1096, 1115**
Plastic Pipe & Tube **1069, 1094, 1100, 1106, 1112-1113**
Press Fit Copper **1130-1134**
Press Fit Stainless Steel **1118-1127, 1135-1136**
Valves **1065-1066, 1073, 1077, 1084, 1086, 1096, 1100, 1106, 1112**
RJT Couplings Stainless Steel **1194**
Rotating & Swivel Joints **1224**
Rubber Air Hose **1410, 1411, 1414, 1420**
Rubber Air Hose Assemblies **1411, 1414**

S

SAE 3000 Flanged Hose Insert **24, 27, 36**
SAE 6000 Flanged Hose Insert **24, 27, 36**
SAE Threaded Flanges 3000 **102-104**
SAE Threaded Flanges 6000 **102-104**
SAE Socket Weld Flanges 3000 **105-106, 108**
SAE Socket Weld Flanges 6000 **105-106, 108**
SAE Butt Weld 3000 **106-107**
SAE Butt Weld 6000 **106-107**
Safety Blow Guns & Nozzles **1596, 1605-1608**
Safety Compressed Air Hose **1412-1413**
Safety Compressed Air Hose Assemblies **1413**
Safety Glasses **1754**
Safety Quick Release Couplings **389**
Safety Relief Valves **988-989**
Sand Blasting **1601**
Saws **1730**
Schrader Couplings **385**
Screwdrivers **1734-1736**
Screwed & Socketed Steel Tubing **1383**
Sealant Guns **1569, 1590**
Sealants **1391, 1585-1586**
Sectional Control Valve **237**
Service Plugs **50-51**
Shot Blast Hose & Couplings **1483-1484**
Shuttle Valve **136, 245, 633, 636**
Sight Glasses **260, 436**
Silencers & Mufflers **630-635**
Silicone **1583, 1590**
Sledge Hammer **1732**
Slide Valve **549, 563, 1056**
Soda Blaster & Media **1600**
Solder Fittings Copper **1218-1219**
Solenoid Valves **575-599, 617-622**
DIN Connectors & Moulded Plugs **1043-1046**
Hydraulic Solenoid Valves **203-206, 210-212, 215-217**
Pilot Operated Solenoid Valves **1026-1042**
Pilot Valves **600-606, 608-610**
Stainless Steel **1030-1031, 1035, 1037, 1041**
Solenoid Valves NAMUR **1020-1021**
Timer **1028**
Speed Control Regulator **628, 634, 804-807, 814-816**
Spill Kits
Kits **281-282**
Prevention & Absorption **279-284**
Spiral Hose Guard **47-48**
Spirit Levels **1740**
Splicing Kit **112**
Split Flange Half **24, 102**
Spray Guns & Nozzles **1713-1715, 1720**
Air Powered Diaphragm Pumps **1712**
Airless Spray Gun & Accessories **1711**
Industrial Airless Paint Sprayer **1711**
Paint Mixing Tank **1712**
Sprinklers **1680**
Square Plug **957, 1185**
ST Series Couplings **405**
Stainless Steel 150lb
Fittings **1181-1185**
Stainless Steel 3000lb Flanges **1195**
Stainless Steel Adaptors 10,000psi **90-94**
Stainless Steel Angle Seat Valves **1049-1051**
Stainless Steel Ball Valves **242, 946-954, 956**
Stainless Steel Butterfly Valves **967-970**
Stainless Steel Check/Non-return Valve **242, 961, 963-965**
Stainless Steel DIN Compression Fittings **144-164**
Stainless Steel Flanged Hose Tails **1492**
Stainless Steel Float Valves **1059**
Stainless Steel Flow Meters **253**
Stainless Steel Gate Valves **957-959**
Stainless Steel Gauges
Glycerine Filled **264-267**
Stainless Steel Globe Valves **975-977**
Stainless Steel Hose Clamps & Clips **1513, 1517-1521, 1524, 1527-1529, 1531-1543, 1548-1550, 1552-1555, 1557**
Stainless Steel Hose Connectors/Inserts
Banjo Bolt **34**
Banjo Insert **34**
BSPP **30**
BSPT **30**
Jet Wash Female **34**
JIC **31**
Metric **32-33, 35**
ORFS **34**
SAE 3000 **36**
SAE 6000 **36**
Split Flange Half **36**
Stainless Steel Hydraulic Adaptors **85-87**
Stainless Steel Hydraulic Twin Ferrule Compression Fittings
Imperial **166-172**
Metric **173-178**
Stainless Steel Hygienic BS Type
Pipe Fittings **1191-1192**
Tube **1192**
Clamps **1193**
Accessories **1192**
Stainless Steel Instrumentation Fittings **88-89**
Stainless Steel JIC Adaptors **95-100**
Stainless Steel Lever Lock Water Pump Couplings **1505**
Stainless Steel Manifold Valves **981**
Stainless Steel Metric & Imperial Tube **183, 1185**
Stainless Steel Needle Valves **982-983**
Stainless Steel Overbraid Rubber Hose **1420**
Stainless Steel Pinch Valve **1050**
Stainless Steel Pneumatic Actuator **1016**
Stainless Steel Pneumatic Check Valves **628**
Stainless Steel Quick Release Couplings
Series 25 **360**
Series 95 **384**
ST Series **405**
Stainless Steel Quick Release Couplings Hydraulic
ISO A **290, 297**
ISO B **291, 297**
Flat Face **299**
H Series **320**
Stainless Steel Reusable Fittings
Inserts **41**
Ferrules **41**
Stainless Steel Ferrules **29**
Stainless Steel RJT Couplings **1194**
Stainless Steel Sight Glasses **436**

Fluid-Air Components Ltd

Stainless Steel Switches
- *Float Level Switches* **442**
- *Flow Switch* **437**

Stainless Steel Test Point **269-270**

Stainless Steel Trench Hose Couplings **1487-1488**

Stainless Steel Tube Clamp Components
- *Clamping Rail* **190**
- *Clamping Rail Nuts* **190, 192**
- *Series A Clamp Components* **191-192**
- *Series B Clamp Components* **194**
- *Series C Clamp Components* **197**

Stainless Steel Twin Ferrule Compression Fittings
- *Imperial* **166-172**
- *Metric* **173-178**

Standpipe Adaptors Metric **137**

Standpipes Manhole & Drain Keys **1496**

Stanley Knife **1731**

Steam Couplings **1481**

Steam Hose & Assemblies **1482**

Steel Spring Guard **45**

Stem Couplings **1480-1481**

Storage & Display Systems
- *Accessories* **1748**
- *Bins & Rails* **1749**
- *Component Organisers* **1747**
- *Display Boards* **1749**
- *Multi-Purpose Display Boards* **1749**
- *Stands* **1748**
- *Storage Bins* **1748**
- *Tool Trays* **1749**
- *Wall Panels* **1749**

STORZ DIN Suction Couplings **1485-1486**

Straight Flange Coupling **135**

Strainers
- *Strainer Baskets* **962, 964, 972**
- *Plastic Strainer* **962**
- *Y Strainers* **972-974**

Strainers & Foot Valves **1436**

StrutSlayr Shear Heads **1744**

Studding **1385**

Suction Hose **1427-1431**

Super Glue **1585**

Super Clamps **1521, 1523**

Switch Box Pneumatic **1022-1023**

Swivel Joints **1224**

Swivel Joints Hydraulic **245**

T

Tank Cleaner **260**

Tank Gauges **1654**

Tanker Couplings & Adaptors **1490-1491**

Tape
- *Adhesive Tapes & Barrier Tapes* **1588-1590**
- *Duct Tape* **1585**
- *Plate & Cloth Tape* **1391, 1586**
- *PTFE Tape* **1391**
- *Self Amalgamating Tape* **45**

Tarmac & Pothole Repair **1561-1562**

Temperature Gauge **252, 265, 417-418**

Temperature Switches **421**

Test & Flow Indicators **252-253**

Test Point Couplings
- *Test Point Accessories* **269-272**
- *Test Point Couplings* **269-272**
- *Test Point Hose Assemblies* **270**
- *Test Point Kits* **272**

Thermometers **446**

Thinking Sticks **262**

Thread Gauge **1648**

Thread Lock Adhesives **1584, 1586**

Timers **613-614, 1024-1025, 1028**

Toe Jack **278**

Toilet Paper **1761**

Tool Bags **1741, 1759**

Tools Automotive
- *Brake Bleeder* **1600**
- *Jet Flusher Gun* **1600**
- *Jet Washer Gun* **1600**
- *Oil Extractor* **1600**

Tools Hand/Workshop
- *Allen Keys* **1737**
- *Bolt Cutters* **1732**
- *Brushes* **1729, 1730**
- *Chisel* **1732**
- *Cutting Tools* **1729, 1731**
- *Deburrer* **1067, 1083, 1087**
- *Drill Accessories* **1729**
- *Files* **1730**
- *G & F Clamps* **1740**
- *Hammers* **1732**
- *Lamps & Torches* **1740-1741**
- *Measuring Equipment* **1739**
- *Pipe Cutters* **1731**
- *Pipe Wrench* **1742**
- *Pliers* **1731, 1733**
- *Saws* **1730**
- *Screwdrivers* **1734-1736**
- *Spirit Levels* **1740**
- *Tool Sets* **1737-1739**
- *Wrecking Bar* **1732**
- *Wrenches* **1742**

Tools Pneumatic/Air
- *Air Couplings* **1719**
- *Air Tool Accessories* **1710**
- *Cutter* **1718**
- *Drills* **1708, 1717**
- *Grinders & Kits* **1709, 1717**
- *Impact Hammer* **1708, 1718**
- *Impact Wrenches* **1706-1707, 1716**
- *Impact Wrench Kit* **1707**
- *Nailer & Stapler* **1708**
- *Ratchet Wrenches* **1706, 1717**
- *Riveters* **1717, 1720**
- *Sanders* **1718**
- *Tool Balancers* **1720**
- *Tyre Inflators & Adaptors* **1721-1725**

Torches & Lamps **1740-1741**

Tread Depth Gauge **1725**

Trench Pump Hose Couplings **1487-1489**

Trigger Guns & Nozzles, Fuel **1620-1621**

Trolley
- *Drum* **1638**
- *Grease Filler Pumps* **1638, 1642**
- *Oil Delivery* **1638**
- *Transfer Unit* **1627**

Trolley Jack **1739**

Tube
- *Copper* **1213**
- *Bundy* **1215**
- *Imperial Steel Tube* **182**
- *Metric Steel Tube* **180, 181**
- *PVC Covered Copper Tube* **1215**
- *Screwed & Socketed Steel Tubing* **1383**
- *Stainless Steel Metric & Imperial* **183, 1185, 1190**
- *Stainless Steel NB Tube* **1185**

Tube Benders **1746, 182**

Tube Clamps
- *Clamping Rail* **190**
- *Clamping Rail Nuts* **190, 192**
- *Complete Clamps* **186**
- *Multiclamp* **201**
- *Noise & Vibration Protection* **187**
- *Steel & Flat Clamps* **199**
- *Series A Clamp Components* **188-192**
- *Series B Clamp Components* **190, 192-194**
- *Series C Clamp Components* **190, 195-197**
- *Series O Clamps* **200**
- *U-bolts & Saddles* **198**

Tube Cutter
- *Cutting Tool Accessories* **905, 913, 1743, 1745-1746**
- *Powered Tubing Cutter* **1743**

Tube Reinforcing Insert/Ring **182**

Tubing, Pneumatic
- *Air Brake Tube* **910**
- *Hose Assemblies* **900-903, 910, 916**
- *Nylon Recoil Hoses* **916**

Fluid-Air Components Ltd

Nylon Tube **913-917**
Polyamide High Resistant Tubing **906**
Polyurethane Tube **898-904, 906-909, 912, 918**
Polyurethane Recoil Hoses **899-904**
Tube Cutters **905, 908, 913**

Twin Ferrule Stainless Steel Compression Fittings
Imperial **166-172**
Metric **173-178**

Tyre Inflators & Adaptors **1721-1725**
Tyre Pressure Gauges **1725**

U

U Bolt Clamps **1514**
UPVC Flanges & Gaskets **1105, 1111**
Unicone Fittings **1484**

V

Vacuum Gauges **411-412, 415-416**
Vacuum Hose & Accessories, Industrial **1446**
Vacuum Switches Pneumatic **425**

Vacuum Technology
Filters **761**
Fittings **750-754**
Pumps **755-757**
Grippers **758- 760**
Suction Cups **707-749**

Vacuum/Guns & Kits **1609**
Valve Timer **1028**

Valves
Ball Valves **238-240**
CETOP 3 Valves **203-204, 207, 210-213, 220**
CETOP 3 Manifolds **208**
CETOP 5 Valves **205-207, 215-218, 220**
CETOP 5 Manifolds **208**
CETOP Coils & DIN Plugs **205, 219**
Spring Loaded Tap Valve **1,060**
3-Way Valves **924, 928, 930, 934-935, 937, 941, 951-952, 954**
Actuation **993-1001, 1005-1012**
Bibcock **931-932**
Brass **922-935, 938-944**
Cast Iron Ball Valve **936**
Compression Ball Valves **137, 938-939, 944**
Drain Ball Valves **929-930**
Direct Mount ISO 5211 **935-936, 944, 950-956**
Fire Safe Ball Valves **953-955**
Hydraulic Ball Valves **238-240**
Hygienic Ball Valves **952**
Mini Ball Valves **926-928, 935, 939, 940, 946**
Panel Mount Ball Valves **933-934**
Plastic Ball Valves **937, 945**
Stainless Steel **242, 946-956**
Vented Ball Valve **932-933**
WRAS & GAS Ball Valves **938-945**
Gate Valves & Accessories **957-959**
Globe Valves **975-977**
Needle Valves **243, 982-983**
Instrumentation Manifold Valve **981**

Valves & Timers, Drain **1024-1025**
Accessories **1025**
Drain & Bleeder Valves **1058**

Valves (Logic) **611-612**

Valves Butterfly
Accessories **971**
Actuation **1002-1003, 1013-1014**
Hygienic Butterfly Valves **967**
Lugged & Tapped **970**
Wafer Pattern **968-969**

Valves Hydraulic Threaded
Check Valve **246**
Control Valves **246**
Diverter Valve **245**
Flow Dividers **246**
Hose Burst Valve **245**
Pilot Operated Vales **244**
Pressure Reducing Valves **244**
Overcentre Valves **244**
Shuttle Valve **244**
Swivel Joints **245**

Valves/Check
Accessories **960, 962, 964, 966**
Ball Check **966**
Commissioning Valves **978**
Cromax **964**
Double Check **960**
Dual Plate **964-966**
Exhaust Valves **634-636**
Hydraulic **136, 241-243, 246, 963**
Piston **965**
Pneumatic **792, 864**
Spring **960-962, 964, 966**
Swing **960-965**
Wafer Pattern **961**

Vane Pumps & Accessories **222-223**
Vent Valves **979**
Ventilators **1616**
Vernier Gauges **1739**

Vibrators
Pneumatic Vibrators **625-626**

Visual indicator **256-257, 259, 445, 437-438, 613**

W

Walform Machine **115**
Wall Panels **1749**

Wash Down Equipment
Accessories **1675**
Extended Lances **1671**
Foam Injection Bottle **1672**
Lances **1672**
Pressure Washer Hose **1676-1677**
Pressure Washer Hose Assemblies **1678**
Pressure Lance Configurator **1668-1669**
Pressure Washer Nozzles & Adaptors **1673-1674**
Pressure Washer Floor Cleaner **1675**
Pressure Washer Lances **1666**
Pressure Washer Triggers & Lance Assemblies **1667**
Pressure Washer Lance Triggers **1670**
Twin Lances **1672**

Wash Down Hose **1415**

Washers
Bonded Seals & Kits **109-112**

Water Delivery Hose **1431**
Water Filter **665**

Water Guns
1" System Couplings **1664**
1/2" System Couplings **1662-1663**
3/4" System Couplings **1663**
Click System Couplings **1664**
Couplings & Adaptors **1659-1660**
Heavy-duty Brass **1657, 1659**
Heavy-duty Stainless Steel **1658, 1659**
Water Guns **1660, 1679**
Stainless Steel Couplings **1665**

Water Hose **1415, 1422**
Water Meter **1057, 445**

Water Misting Systems
Dry Fog Systems **1691**
Fans **1690**
Filters **1695**
Fogger **1691**
Misting System Controllers **1696**
Nozzles & Adaptors **1692-1694**
Pump Kits **1687-1689**

Water Nozzles **1679**
Water Regulator **665**
Water Sprinklers **1680**
Water Valves & Accessories **1057**
WD-40 **1568**
Welding Hose **1418-1419**
Welding Hose Sets **1419**
Welding Sprays **1577**
Wipes **1573**
Worm Drive **1513-1514, 1527-1529,1535, 1558**
Wrecking Bar **1732**
Wrenches **1734**

Y

Y Strainers **972-974, 1303**

Fluid-Air Components Ltd
ef nkl i r oi r p c c c a c c

Code	Page
0	
00100	**54**
00101	**54**
00102	**54**
00103	**54**
00104	**54**
00106	**54**
00109	**54**
00110	**54**
00111	**54**
00112	**54**
00113	**54**
00114	**54**
00115	**54**
00116	**54**
00117	**54**
00118	**54**
00119	**54**
00120	**54**
00125	**54**
00129	**54**
00225	**78**
00226	**78**
00227	**78**
00228	**78**
00229	**78**
00230	**78**
00231	**78**
00232	**78**
00233	**78**
00234	**78**
00236	**78**
00313-JIS	**55**
0045R	**1538**
00780	**59**
00781	**59**
00782	**59**
00783	**59**
00784	**59**
00785	**59**
00786	**59**
00787	**59**
00788	**59**
00789	**59**
00790	**59**
00791	**59**
00792	**59**
00793	**59**
00794	**59**
00795	**59**
00796	**59**
00801	**59**
00802	**59**
00805	**59**
00806	**59**
00807	**59**
00808	**59**
00809	**59**
00810	**59**
00820	**58**
00821	**58**
00822	**58**
00823	**58**
00824	**58**
00825	**58**
00826	**58**
00829	**58**
00831	**58**
00841	**58**
00842	**58**
00843	**58**
00844	**58**
00849	**58**
00850	**58**
008ABK	**887**
0090320502	**496**
0090400502	**496**
0090500502	**496**
0090630502	**496**
0090800502	**496**
0091000502	**496**
0091250502	**496**
01001	**59**
01002	**59**
01003	**59**
01004	**59**
01005	**59**
01006	**59**
01007	**59**
01008	**59**
01009	**59**
01010	**59**
01011	**59**
01012	**59**
01013	**59**
01014	**59**
01015	**59**
01016	**59**
01017	**59**
01018	**59**
01019	**59**
01021	**59**
01022	**59**
01023	**59**
01024	**59**
01025	**59**
01026	**59**
01027	**59**
01028	**59**
01029	**59**
01030	**59**
01031	**59**
01032	**59**
01033	**59**
01050	**57**
01052	**57**
01054	**57**
01056	**57**
01057	**57**
01058	**57**
01060	**57**
01061	**57**
01062	**57**
01063	**57**
01064	**57**
01065	**57**
01066	**57**
01067	**57**
01-06L04J	**73**
01-06S04J	**73**
01-08L04J	**73**
01-08S04J	**73**
01-08S06J	**73**
01-10L06J	**73**
01-10S06J	**73**
01-10S08J	**73**
01-12L06J	**73**
01-12L08J	**73**
01-12S08J	**73**
01-14S08J	**73**
01-15L08J	**73**
01-15L12J	**73**
0121001	**632**
0121005	**632**
0121007	**632**
0121010	**632**
0121015	**632**
0121030	**632**
01-22LX212J	**74**
01-25SX212J	**74**
01265	**73**
01267	**73**
01268	**73**
01270	**73**
01272	**73**
01274	**73**
01275	**73**
01276	**73**
01277	**73**
01278	**73**
01279	**73**
01280	**73**
01281	**73**
01282	**73**
01283	**73**
01284	**73**
01285	**73**
01286	**73**
01287	**73**
01288	**73**
01289	**73**
01290	**73**
01291	**73**
01292	**73**
01294	**73**
01295	**73**
01297	**73**
01298	**73**
01299	**73**
01300	**57**
01301	**57**
01302	**57**
01303	**57**
01304	**57**
01305	**57**
01306	**57**
01307	**57**
01308	**57**
01309	**57**
01-30SX220J	**74**
01310	**57**
01311	**57**
01312	**57**
01313	**57**
01314	**57**
01315	**57**
01316	**57**
01317	**57**
01318	**57**
01319	**57**
01320	**57**
01321	**57**
01322	**57**
01323	**57**
01324	**57**
01325	**57**
01326	**57**
01327	**57**
01328	**57**
01329	**57**
01330	**57**
01331	**57**
01332	**57**
01333	**57**
01335	**57**
01337	**57**
01338	**57**
01339	**57**
01340	**57**
01341	**57**
01342	**57**
01343	**57**
01344	**57**
01345	**57**
01346	**57**
01348	**57**
01350	**74**
01351	**74**
01352	**74**
01353	**74**
01354	**74**
01355	**74**
01356	**74**
01357	**74**
01358	**74**
01-35LX216J	**74**
01-35LX216J	**73**
01361	**74**
01362	**74**
01363	**74**
01364	**74**
01365	**74**
01366	**74**
01367	**74**
01368	**74**
01369	**74**
01370	**74**
01371	**74**
01373	**74**
01377	**74**
01378	**74**
01379	**74**
01380	**74**
01381	**74**
01383	**74**
01384	**74**
01385	**74**
01386	**74**
01387	**74**
01388	**74**
01389	**74**
01-38SX220J	**74**
01391	**74**
01392	**74**
01394	**74**
01395	**74**
01396	**74**
01397	**74**
01425-TP-B02	**71**
01427-TP-B02	**71**
01434-TP-B02	**71**
01440-TP-B02	**71**
01451-TP-B02	**71**
01458-TP-B02	**71**
0152018	**632**
0152038	**632**
0152048	**632**
0152068	**632**
0153028	**632**
0153038	**632**
0153068	**632**
0153108	**632**
0153128	**632**
0153168	**632**
015AA	**430**
015AC	**430**
01625	**75**
01626	**75**
01627	**75**
01628	**75**
01631	**75**
01651	**75**
01652	**75**
01653	**75**
01654	**75**
01655	**75**
01656	**75**
01657	**75**
01659	**75**
01661	**75**
01662	**75**
01663	**75**
01664	**75**
01775	**62**
01776	**62**
01777	**62**
01778	**62**
01779	**62**
01780	**62**
01781	**62**
01782	**62**
01783	**62**
01784	**62**
01785	**62**
01875	**61**
01876	**61**
01877	**61**
01878	**61**
01879	**61**
01880	**61**

Code	Page
01881	**61**
01882	**61**
01883	**61**
01884	**61**
01885	**61**
01886	**61**
01887	**61**
01888	**61**
01889	**61**
01913	**67**
01998	**67**
01999	**67**
01C00A-00	**227**
02013	**67**
02014	**67**
02017	**66**
02018	**66**
02022	**66**
02023	**66**
02031	**66**
02032	**66**
02035	**66**
02036	**66**
02037	**66**
02039	**66**
020AA	**430**
02-102532	**223**
02-102533	**223**
02-102534	**223**
02-102535	**223**
02-102552	**223**
02-102553	**223**
02-102554	**223**
02-102555	**223**
02-102572	**223**
02-102574	**223**
02-102575	**223**
02-137109-CR	**222**
02-137110-CR	**222**
02-137113-CR	**222**
02-137117-CR	**222**
02-137124-CR	**222**
02-137126-CR	**222**
02-137129-CR	**222**
02-137132-CR	**222**
02-137140-CR	**222**
02-137144-CR	**222**
02-137146-CR	**222**
02-137560	**223**
02-137561	**223**
02-137562	**223**
02-137563	**223**
02-137565	**223**
02-137566	**223**
02-137567	**223**
02-139074	**212**
02-144961	**212**
02-145162	**212**
02-146111	**211**
02170371	**1529**
02170380	**1529**
02170401	**1529**
02170411	**1529**
02170441	**1529**
02170451	**1529**
0223000201	**589**
0223000301	**589**
0223000401	**589**
0223000501	**589**
0223000601	**589**
0223000701	**589**
0224000201	**589**
0224000401	**589**
0224000501	**589**
0224000601	**589**
0224000701	**589**
0226004500	**589**
0226005500	**589**
0227700000	**624**
0228000100	**620**
0228000150	**620**
0228000155	**620**
0228000200	**620**
0228000210	**620**
0228000300	**620**
0228000301	**620**
0228000400	**620**
0228000500	**620**
0228000700	**620**
0228001100	**620**
0228001150	**620**
0228001155	**620**
0228001200	**620**
0228001210	**620**
0228001300	**620**
0228001301	**620**
0228001400	**620**
0228001500	**620**
0228001700	**620**
02-341552	**224**
02-341576	**224**
02-341644	**224**
02-341685	**224**
02-341949	**224**
02-348243	**224**
02-348259	**224**
02-348260	**224**
02-353298	**212**
02-466861	**224**
025AA	**430**
02KAAM03MPX	**330**
02KATF02MPX	**330**
02SFAM03MXX	**330**
02SFTF03MXX	**330**
03.0435NOS	**1722**
03.0435NSOS	**1722**
03.0447OS	**1722**
03.0465OS	**1722**
03.0472OS	**1722**
03000	**70**
03001	**70**
03002	**70**
03003	**70**
03004	**70**
03005	**70**
03006	**70**
03007	**70**
0300900-1	**1528**
0300900-2	**1528**
0300900-3	**1528**
0300900-4	**1528**
0300900-5	**1528**
0300900-6	**1528**
0300900-7	**1528**
0300900-8	**1528**
0300900-9	**1528**
0300901-0	**1528**
0300901-1	**1528**
0300901-2	**1528**
0300901-3	**1528**
0300901-4	**1528**
0300901-5	**1528**
0300901-6	**1528**
0300901-7	**1528**
0300901-8	**1528**
0300901-9	**1528**
0300902-0	**1528**
0300902-1	**1528**
0300902-3	**1528**
0300902-4	**1528**
0300A-00	**227**
03011010	**1537**
03011029	**1537**
03011037	**1537**
03011045	**1537**
03011053	**1537**
03011061	**1537**
03011070	**1537**
03011088	**1530**
03011096	**1530**
03012013	**1537**
03012021	**1537**
03012030	**1537**
03012048	**1537**
03012056	**1537**
03012064	**1537**
03012072	**1537**
03012101	**1537**
03012110	**1537**
03012128	**1537**
03012136	**1537**
03012144	**1537**
03012152	**1537**
03012160	**1537**
03012179	**1537**
03012187	**1537**
03012195	**1537**
03012208	**1537**
03012216	**1537**
03012224	**1537**
03012232	**1537**
03012240	**1537**
03012259	**1537**
03012267	**1537**
03012275	**1537**
03012283	**1537**
03013614	**1524**
03013622	**1524**
03013630	**1524**
03013649	**1524**
03013657	**1524**
03013665	**1524**
03013673	**1524**
03013681	**1524**
03013690	**1524**
03013702	**1524**
03013710	**1524**
03013729	**1524**
03013737	**1524**
03013745	**1524**
03013753	**1524**
03013761	**1524**
03013770	**1524**
03013788	**1524**
03013796	**1524**
03013809	**1524**
03013817	**1524**
03013825	**1524**
03013833	**1524**
03013841	**1524**
03013850	**1524**
03013868	**1524**
03013876	**1524**
03013884	**1524**
03013892	**1524**
03013905	**1524**
03013913	**1524**
03013921	**1524**
03013930	**1524**
03013948	**1524**
03013956	**1524**
03013964	**1524**
03013971	**1524**
03013981	**1524**
03013982	**1524**
03013983	**1524**
03013984	**1524**
03013985	**1524**
03013986	**1524**
03013991	**1524**
03013992	**1524**
03013993	**1524**
03013994	**1524**
03013995	**1524**
0301401-9	**1527**
0301402-7	**1527**
0301403-5	**1527**
0301404-3	**1527**
0301405-1	**1527**
0301406-0	**1527**
0301407-8	**1527**
0301408-6	**1527**
0301409-4	**1527**
0301410-7	**1527**
0301411-5	**1527**
0301412-3	**1527**
0301414-0	**1527**
0301415-8	**1527**
0301416-6	**1527**
0301417-4	**1527**
0301418-2	**1527**
0301419-0	**1527**
0301451-0	**1528**
0301452-9	**1528**
0301453-7	**1528**
0301454-5	**1528**
0301455-3	**1528**
0301456-1	**1528**
0301457-0	**1528**
0301458-8	**1528**
0301459-6	**1528**
0301460-9	**1528**
0301461-7	**1528**
0301462-5	**1528**
0301463-3	**1528**
0301464-1	**1528**
0301465-0	**1528**
0301466-8	**1528**
0301467-6	**1528**
0301468-4	**1528**
0301469-2	**1528**
0301471-3	**1528**
0301472-1	**1528**
0301473-0	**1528**
0301474-8	**1528**
0301575-9	**1527**
0301576-7	**1527**
0301650-8	**1527**
0301651-6	**1527**
0301652-4	**1527**
0301653-2	**1527**
0301654-0	**1527**
0301655-9	**1527**
0301656-7	**1527**
0301657-5	**1527**
0301658-3	**1527**
0301659-1	**1527**
0301660-4	**1527**
0301661-2	**1527**
0301662-0	**1527**
0301663-9	**1527**
0301667-1	**1527**
0301668-0	**1527**
0301750-0	**1527**
0301751-9	**1527**
0301752-7	**1527**
0301753-5	**1527**
0301754-3	**1527**
0301755-1	**1527**
0301756-0	**1527**
0301757-8	**1527**
0301758-6	**1527**
0301759-4	**1527**
0301760-7	**1527**
0301761-5	**1527**
0301762-3	**1527**
0301763-1	**1527**
0301764-0	**1527**
0301765-8	**1527**
0301766-6	**1527**
0301767-4	**1527**
0301768-2	**1527**
0301769-0	**1527**
0301770-3	**1527**
0301771-1	**1527**
0301772-0	**1527**
0301773-8	**1527**
03017800	**1529**
03017818	**1529**
03017834	**1529**

Code	Page
03017842	1529
03017850	1529
03017869	1529
03017877	1529
03017885	1529
03017893	1529
03017906	1529
03017914	1529
03017922	1529
03029302	558
03029402	558
03030	79
03031	79
03032	79
03033	79
03034	79
03035	79
03036	79
03036602	558
03036702	558
03036802	558
03037	79
03040002	558
03040202	558
03040302	558
03040402	558
03040502	558
03040602	558
03040802	558
03041402	558
03041502	558
03041602	558
03042502	558
03042602	558
03043202	558
03043702	558
03043802	558
03051FDPOS	63
03051FDPOS-45	65
03053FDPOS	63
03053FDPOS-45	65
03054FDPOS	63
03054FDPOS-45	65
03056FDPOS	63
03056FDPOS-45	65
03057FDPOS	63
03057FDPOS-45	65
03058FDPOS	63
0305R	1538
03060002	558
03060202	558
03060402	558
03061102	558
03062502	558
03063702	558
03063802	558
03066001	1529
03066002	1529
03066003	1529
03066004	1529
03066005	1529
03066006	1529
03066007	1529
03066008	1529
03066009	1529
03066010	1529
03066011	1529
03066012	1529
03066013	1529
03066014	1529
03066015	1529
03066016	1529
03067001	1529
03067002	1529
03067003	1529
03067004	1529
03067005	1529
03067006	1529
03067007	1529
03067008	1529
03067009	1529
03067010	1529
03067011	1529
03067012	1529
03067013	1529
03067014	1529
03067015	1529
03067016	1529
03085FD	76
03085FDPOS	77
03085FDPOS-45	78
03086FD	76
03087FD	76
03087FDPOS	77
03087FDPOS-45	78
03088FD	76
03088FDPOS	77
03088FDPOS-45	78
03089FD	76
03089FDPOS	77
03089FDPOS-45	78
03090FD	76
03090FDPOS	77
03090FDPOS-45	78
03091036	1530
03091FD	76
03092FDPOS	77
03092FDPOS-45	78
03170001	1526
03170003	1526
03170005	1526
03170007	1526
03170009	1526
03170011	1526
03170013	1526
03170015	1526
03170017	1526
03170019	1526
03170021	1526
03170023	1526
03170025	1526
03170027	1526
03170029	1526
03170031	1526
03170033	1526
03170035	1526
03170037	1526
03170039	1526
03170041	1526
03170043	1526
03170045	1526
03180001	1526
03180003	1526
03180005	1526
03180007	1526
03180009	1526
03180011	1526
03180013	1526
03180015	1526
03180017	1526
03180019	1526
03180021	1526
03180023	1526
03180025	1526
03180027	1526
03180029	1526
03180031	1526
03180033	1526
03180035	1526
03180037	1526
03180039	1526
03180041	1526
03180043	1526
03180045	1526
03190001	1526
03190003	1526
03190005	1526
03190007	1526
03190009	1526
03190011	1526
03190013	1526
03190015	1526
03190017	1526
03190019	1526
03190021	1526
03190023	1526
03190025	1526
03190027	1526
03190029	1526
03190031	1526
03190033	1526
03190035	1526
03190037	1526
03190039	1526
03190041	1526
03190043	1526
03190045	1526
0350003-8	1557
0350004-6	1557
03503116	1530
03503124	1530
03503201	1530
03503211	1530
03503221	1530
03503231	1530
03503241	1530
03503251	1530
03503261	1530
03503271	1530
03503281	1530
0351000050	550
03C00A-00	227
0400A-00	227
04016100	1203
04048	76
04050	76
04050FD	76
04051	76
04052	76
04053	76
04053/45FD	78
04053FD	76
04054	76
04055	76
04056	76
04057	76
04057100	633
04057200	633
04057300	633
04057400	633
04058	76
04059	76
04059/45FD	78
04059FD	76
04060	76
04060/45FD	78
04060FD	76
04061	76
04062	76
04063	76
04064	76
04065	76
04065/45FD	78
04065FD	76
04066	76
04066/45FD	78
04070	76
04071	76
04072	76
04073	76
04073/45FD	78
04073FD	76
04074	76
04075	76
04076	76
04076/45FD	78
04076FD	76
04077	76
04078	76
04079	76
04080	76
04081	76
04082	76
04083	76
04084	76
04085	76
04086	76
04087	76
04088	76
04089	76
05000/45FD	65
05000FD	64
05001/45FD	65
05001FD	64
05002/45FD	65
05002FD	64
05004/45FD	65
05004FD	64
05005/45FD	65
05005FD	64
05007FD	64
05018FD	64
05026FD	64
05027FD	64
05028FD	64
05030FD	64
05031FD	64
05050/45	78
05050/45FD	78
05050FD	76
05051FD	76
05052/45	78
05052/45FD	78
05052FD	76
05053/45	78
05053/45FD	78
05053FD	76
05054/45FD	78
05054FD	76
05055/45	78
05055/45FD	78
05055FD	76
05056/45	78
05056/45FD	78
05056FD	76
05059/45	78
0507R	1538
0523053000000000	429
0523058000000000	429
0523447000000000	429
0523449000000000	429
0554018	632
0554048	632
0554068	632
061R	1538
07000	67
07001	67
07002	67
07003	67
07004	67
07005	67
07006	67
07007	67
07008	67
07020	76
07021	76
07022	76
07023	76
07024	76
07025	76
07026	76
07027	76
07028	76
07029	76
07030	76
07031	76
07059	66
07060	66
07061	66
07062	66

Code	Page
07063	66
07064	66
07065	66
07066	66
07080	66
07081	66
07083	66
07084	66
07085	66
07086	66
0709R	1538
08010	66
08011	66
08012	66
08013	66
08014	66
08015	66
08016	66
0811R	1538
081ABK	887
08550	77
08551	77
08552	77
08553	77
08554	77
08555	77
08556	77
08557	77
08558	77
08559	77
08560	77
08561	77
08562	77
08564	77
08565	77
08566	77
08567	77
08568	77
08569	77
08570	77
08571	77
08572	77
08573	77
08574	77
08575	77
08576	77
08577	77
08578	77
08579	77
08580	77
08581	77
08582	77
08584	77
08585	77
085ABK	887
086ABK	887
087R	1538
0880160000000000	429
0880260000000000	429
0880460000000000	429
0880600000000000	429
09025-02-SPG	69
09026-04-SPG	69
09027-06-SPG	69
09028-08-SPG	69
09030-12-SPG	69
090R	1538
09100/HD	69
09101/HD	69
09102/HD	69
09103/HD	69
09105/HD	69
09106/HD	69
0911R	1538
09168	69
09169	69
09170-M16-SPG	69
09173-M14-SPG	69
09176-M22-SPG	69
09179	69
09179-M10-SPG	69
092.024.30.AC	1612
09220	60
09221	60
09222	60
09223	60
09224	60
09240	60
09241	60
09242	60
09243	60
09244	60
09245	60
09250	60
09251	60
09252	60
09253	60
09255	60
09258	60
09280	63
09281	63
09282	63
09283	63
09284	63
09285	63
09300	79
09301	79
09302	79
09303	79
09304	79
09305	79
09320	79
09321	79
09322	79
09323	79
09324	79
09397	64
09398	64
09399	64
09400	64
09401	64
09402	64
09403	64
09404	64
09405	64
09406	64
09407	64
09408	64
09409	64
09410	64
09411	64
09412	64
09500	68
09501	68
09502	68
09503	68
09504	68
09505	68
09506	68
09507	68
09508	68
09509	68
09510	68
09511	68
09512	68
09513	68
09514	68
09515	68
09516	68
0951602093	496
09517	68
09521	68
09550	68
09551	68
09552	68
09553	68
09554	68
09555	68
09556	68
095R	1538
09605	77
09606	77
09607	77
09608	77
09609	77
09610	77
09612	77
09700	79
09701	79
09702	79
09703	79
09704	79
09705	79
09707	79
09711	79
09712	79
0B00A-00	227
0F00A-00	227
1	
1/2EPW	884
1/2-ORING	108
1/4-BLACK-CUFF	1678
1/4-BLUE-CUFF	1678
10.2000OS	1722
10.2000OS4	1722
10.3012OS2	1722
1000A-00	227
1001E.250001	1066
1001E.250004	1066
1002-0038	1667
100200400	862
100200600	862
100200800	862
100201000	862
100201200	862
1002501	1050
1002503	1050
1002505	1050
1002507	1050
1002509	1050
1002511	1050
1002513	1050
1002515	1050
1002517	1050
1002519	1050
1002521	1050
1002523	1050
100290400	862
100290600	862
100290800	862
100291000	862
100291200	862
10031-S03	228
1003A.17.04.00	1063
1003A.25.04.00	1063
1003A.40.04.00	1063
1003A.50.04	1063
1003A.63.04	1063
100400400	862
100400600	862
100400800	862
100401000	862
100401200	862
10053-S03	228
100600400	862
100600600	862
100600800	862
100601000	862
100601200	862
1006A.25.04.00	1063
1006A.40.04.00	1063
1006A.50.04	1063
1006A.63.04	1063
100R1AT-03-100	6
100R1AT-04-100	6
100R1AT-05-100	6
100R1AT-06-100	6
100R1AT-08-100	6
100R1AT-10-100	6
100R1AT-12-100	6
100R1AT-16-100	6
100R1AT-20-40	6
100R1AT-24-40	6
100R1AT-32-40	6
100R2AT-03-100	7
100R2AT-04-100	7
100R2AT-05-100	7
100R2AT-06-100	7
100R2AT-08-100	7
100R2AT-10-100	7
100R2AT-12-100	7
100R2AT-16-100	7
100R2AT-20-40	7
100R2AT-24-40	7
100R2AT-32-40	7
100R4-102-10	14
100R4-102-20	14
100R4-115-10	14
100R4-127-10	14
100R4-127-20	14
100R4-152-10	14
100R4-152-20	14
100R4-19-10	14
100R4-19-20	14
100R4-19-40	14
100R4-25-10	14
100R4-25-20	14
100R4-25-40	14
100R4-32-10	14
100R4-32-20	14
100R4-32-40	14
100R4-38-10	14
100R4-38-20	14
100R4-38-40	14
100R4-51-10	14
100R4-51-20	14
100R4-51-40	14
100R4-64-10	14
100R4-64-20	14
100R4-76-10	14
100R4-76-20	14
100R4-89-10	14
100R4-89-20	14
100R6-04-50	38
100R6-04-B-50	39
100R6-04-G-50	39
100R6-04-R-50	38
100R6-05-50	38
100R6-06-50	38
100R6-06-B-50	39
100R6-06-G-50	39
100R6-06-R-50	38
100R6-08-50	38
100R6-08-B-50	39
100R6-08-G-50	39
100R6-08-R-50	38
100R6-10-50	38
100R6-12-25	38
100R6-12-B-25	39
100R6-12-G-25	39
100R6-12-R-25	38
100R6-16-25	38
100R6-16-B-25	39
100R6-16-G-25	39
100R6-16-R-25	38
100R7-03-25	13
100R7-03-75	13
100R7-04-25	13
100R7-04-25-TWIN	13
100R7-04-75	13
100R7-04-75-TWIN	13
100R7-05-25	13
100R7-05-25-TWIN	13
100R7-05-75	13
100R7-05-75-TWIN	13
100R7-06-25	13
100R7-06-25-TWIN	13
100R7-06-75	13
100R7-06-75-TWIN	13
100R7-08-25	13

Code	Page
100R7-08-25-TWIN	**13**
100R7-08-75	**13**
100R7-08-75-TWIN	**13**
101/2-MS	**1517**
101/2-SS	**1517**
1010-1000	**203**
1010-1001	**203**
1010-1002	**203**
1010-1003	**203**
1010-1004	**204**
1010-1005	**204**
1010-1006	**204**
1010-1007	**204**
1010-1008	**204**
1010-1009	**204**
1010-1010	**204**
1010-1011	**204**
1010-1012	**204**
1010-1013	**204**
1010-1014	**204**
1010-1015	**205**
1010-1016	**205**
1010-1017	**206**
1010-1018	**206**
1010-1019	**206**
1010-1020	**206**
1010-1021	**206**
1010-1022	**207**
1010-1023	**207**
1010-1024	**207**
1010-1025	**207**
1010-1026	**207**
1010-1027	**207**
1010-1028	**207**
1010-1029	**207**
1010-1030	**207**
1010-1031	**207**
1010-1032	**207**
1010-1033	**207**
1010-1034	**207**
1010-1035	**207**
1010-1036	**205**
1010-1037	**205**
1010-1038	**205**
1010-1039	**205**
1010-1040	**205**
1010-1041	**205**
1010-1042	**205**
1010-1043	**205**
1010-1044	**203**
1010-1045	**203**
1010-1046	**203**
1010-1047	**203**
1010-1050	**207**
1010-1051	**207**
1010-1052	**207**
1010-1053	**207**
1010-1054	**206**
1010-1055	**206**
1010-1056	**206**
1010-1057	**207**
1010-1058	**203**
1010-1059	**203**
1010-1060	**204**
1010-1061	**204**
1010-1062	**204**
1010-1063	**205**
1010-1064	**205**
1010-1065	**206**
1010-1066	**206**
1010-1067	**206**
1010-1068	**206**
1010-1069	**205**
1010-1070	**206**
1010-1071	**205**
1010-1072	**205**
10104	**113**
10114	**114**
101150418	**862**
101150618	**862**
101150628	**862**
101150818	**862**
101150828	**862**
101151028	**862**
101151038	**862**
101151238	**862**
1012-0001	**1186**
1012-0002	**1186**
1012-0003	**1186**
1012-0004	**1186**
1012-0005	**1186**
1012-0006	**1186**
1012-0007	**1186**
1012-0008	**1186**
1012-0009	**1186**
1012-0010	**1186**
1012-0011	**1186**
1012-0012	**1186**
1012-0013	**1186**
1012-0014	**1186**
1012-0016	**1186**
1012-0017	**1186**
1012-0018	**1186**
1012-0019	**1186**
1012-0021	**1186**
1012-0022	**1186**
1012-0023	**1186**
1012-0024	**1186**
1012-0025	**1186**
1012-0027	**1186**
1012-0028	**1186**
1012-0029	**1186**
1012-0030	**1186**
1012-0031	**1186**
1012-0032	**1186**
1012-0033	**1186**
1012-0034	**1186**
1012-0035	**1186**
1012-0036	**1186**
1012-0037	**1186**
1012-0038	**1186**
1012-0039	**1186**
1012-0041	**1186**
1012-0042	**1186**
1012-0043	**1186**
1012-0044	**1186**
1012-0045	**1186**
1012-0046	**1186**
1012-0047	**1186**
1012-0048	**1186**
1012-0049	**1186**
1012-0050	**1186**
1012-0051	**1186**
1012-0052	**1186**
1012-0053	**1186**
1012-0054	**1186**
1012-0055	**1186**
1012-0056	**1186**
1012-0057	**1186**
1012-0058	**1186**
1012-0059	**1186**
1012-0060	**1186**
1012-0061	**1186**
1012-0062	**1186**
1012-0063	**1186**
1012-0064	**1186**
1012-0065	**1186**
1012-0066	**1186**
1012-0067	**1186**
1012-0068	**1186**
1012-0069	**1186**
1012-0070	**1186**
1012-0071	**1186**
1012-0072	**1186**
1012-0073	**1187**
1012-0074	**1187**
1012-0075	**1187**
1012-0076	**1187**
1012-0077	**1187**
1012-0078	**1187**
1012-0079	**1187**
1012-0080	**1187**
1012-0082	**1187**
1012-0083	**1187**
1012-0084	**1187**
1012-0085	**1187**
1012-0086	**1187**
1012-0087	**1187**
1012-0088	**1187**
1012-0089	**1187**
1012-0090	**1187**
1012-0091	**1187**
1012-0092	**1187**
1012-0093	**1187**
1012-0094	**1187**
1012-0095	**1187**
1012-0096	**1187**
1012-0097	**1187**
1012-0098	**1187**
1012-0099	**1187**
1012-0100	**1187**
1012-0101	**1187**
1012-0102	**1187**
1012-0103	**1187**
1012-0104	**1187**
1012-0106	**1187**
1012-0107	**1187**
1012-0108	**1187**
1012-0109	**1187**
1012-0110	**1187**
1012-0111	**1187**
1012-0112	**1187**
1012-0113	**1187**
1012-0114	**1187**
1012-0115	**1187**
1012-0116	**1187**
1012-0117	**1187**
1012-0118	**1187**
1012-0119	**1187**
1012-0120	**1187**
1012-0121	**1187**
1012-0122	**1187**
1012-0123	**1187**
1012-0124	**1187**
1012-0125	**1187**
1012-0126	**1187**
1012-0127	**1187**
1012-0128	**1187**
1012-0129	**1187**
1012-0130	**1187**
1012-0131	**1187**
1012-0132	**1187**
1012-0133	**1187**
1012-0134	**1187**
1012-0135	**1187**
1012-0136	**1187**
1012-0137	**1187**
1012-0138	**1187**
1012-0139	**1187**
1012-0140	**1187**
1012-0141	**1187**
1012-0142	**1187**
1012-0143	**1187**
1012-0144	**1187**
1012-0145	**1188**
1012-0146	**1188**
1012-0147	**1188**
1012-0148	**1188**
1012-0149	**1188**
1012-0150	**1188**
1012-0151	**1188**
1012-0152	**1188**
1012-0153	**1188**
1012-0154	**1188**
1012-0155	**1188**
1012-0156	**1188**
1012-0157	**1188**
1012-0158	**1188**
1012-0159	**1188**
1012-0160	**1188**
1012-0161	**1188**
1012-0162	**1188**
1012-0163	**1188**
1012-0164	**1188**
1012-0165	**1188**
1012-0166	**1188**
1012-0167	**1188**
1012-0168	**1188**
1012-0169	**1188**
1012-0170	**1188**
1012-0171	**1188**
1012-0172	**1188**
1012-0173	**1188**
1012-0174	**1188**
1012-0175	**1188**
1012-0176	**1188**
1012-0177	**1188**
1012-0178	**1188**
1012-0179	**1188**
1012-0180	**1188**
1012-0181	**1188**
1012-0182	**1188**
1012-0183	**1188**
1012-0184	**1188**
1012-0185	**1188**
1012-0186	**1188**
1012-0187	**1188**
1012-0188	**1188**
1012-0189	**1188**
1012-0190	**1188**
1012-0191	**1188**
1012-0192	**1188**
1012-0193	**1188**
1012-0194	**1188**
1012-0195	**1188**
1012-0196	**1188**
1012-0197	**1188**
1012-0198	**1188**
1012-0199	**1188**
1012-0200	**1188**
1012-0201	**1188**
1012-0202	**1188**
1012-0203	**1188**
1012-0204	**1188**
1012-0205	**1188**
1012-0206	**1188**
1012-0208	**1188**
1012-0209	**1188**
1012-0210	**1188**
1012-0211	**1188**
1012-0212	**1188**
1012-0213	**1188**
1012-0214	**1188**
1012-0215	**1188**
1012-0216	**1188**
1012-0217	**1188**
1012-0218	**1188**
1012-0219	**1188**
1012-0220	**1188**
1012-0221	**1188**
1012-0222	**1188**
1012-0223	**1188**
1012-0224	**1188**
1012-0225	**1188**
1012-0226	**1188**
1012-0228	**1188**
1012-0229	**1189**
1012-0231	**1189**
1012-0232	**1189**
1012-0233	**1189**
1012-0234	**1189**
1012-0235	**1189**
1012-0236	**1189**
1012-0237	**1189**
1012-0238	**1189**
1012-0239	**1189**
1012-0240	**1189**
1012-0241	**1189**
1012-0242	**1189**
1012-0243	**1189**

Code	Page
1012-0244	1189
1012-0245	1189
1012-0246	1189
1012-0247	1189
1012-0248	1189
1012-0249	1189
1012-0250	1189
1012-0252	1189
1012-0253	1189
1012-0254	1189
1012-0255	1189
1012-0256	1189
1012-0257	1189
1012-0258	1189
1012-0259	1189
1012-0260	1189
1012-0261	1189
1012-0262	1189
1012-0263	1189
1012-0264	1189
1012-0265	1189
1012-0266	1189
1012-0267	1189
1012-0268	1189
1012-0269	1189
1012-0270	1189
1012-0271	1189
1012-0272	1189
1012-0273	1189
1012-0274	1189
1012-0275	1189
1012-0276	1189
1012-0277	1189
1012-0278	1189
1012-0279	1189
1012-0280	1189
1012-0281	1189
1012-0282	1189
1012-0283	1189
1012-0284	1189
1012-0285	1189
1012-0286	1189
1012-0287	1189
1012-0288	1189
1012-0289	1189
1012-0290	1189
1012-0291	1189
1012-0292	1189
1012-0293	1189
1012-0294	1189
1012-0295	1189
1012-0296	1189
1012-0297	1189
1012-0298	1189
1012-0299	1189
1012-0300	1189
1012-0301	1189
1012-0302	1189
1012-0303	1189
1012-0304	1189
1012-0305	1189
1012-0306	1189
1012-0307	1189
1012-0308	1189
1012-0309	1189
1012-0310	1189
1012-0311	1189
1012-0312	1189
1012-0313	1189
1012-0314	1189
1012-0315	1189
1012-0316	1189
1012-0317	1189
1012-0318	1189
1012-0319	1189
1012-0320	1189
1012-0321	1189
1012-0322	1189
1012-0323	1189
1012-0324	1189
1012-0325	1189
1012-0326	1189
1012-0327	1189
1012-0328	1189
1012-0329	1189
1012-0330	1189
1012-0331	1189
1012-0332	1189
1012-0333	1189
101250418	862
101250428	862
101250618	862
101250628	862
101250818	862
101250828	862
101250838	862
101251018	862
101251028	862
101251038	862
101251228	862
101251238	862
10128	113
1013-0003	1180
1013-0005	1180
1013-0008	1180
1013-0009	1180
1013-0011	1180
1013-0013	1180
1013-0016	1180
1013-0025	1180
1013-0027	1180
1013-0028	1180
1013-0029	1180
1013-0030	1180
1013-0032	1180
1013-0034	1180
1013-0035	1180
1013-0038	1180
1013-0039	1180
1013-0040	1180
1013-0041	1180
1013-0042	1180
1013-0043	1180
1013-0044	1180
1013-0048	1180
1013-0050	1180
1013-0051	1180
1013-0052	1180
1013-0053	1180
1013-0054	1180
1013-0056	1180
10136	114
101470418	862
101470428	862
101470618	862
101470628	862
101470638	862
101470818	862
101470828	862
101470838	862
101471018	862
101471028	862
101471038	862
101471228	862
101471238	862
10151	113
10163	113
10167	113
10181	114
10198	113
102010-000	1600
10204	113
10205	113
102150418	862
102150618	862
102150838	862
102151028	862
102151038	862
102151248	862
102185-000	1600
102250405	862
102250418	862
102250428	862
102250605	862
102250618	862
102250628	862
102250818	862
102250828	862
102250838	862
102251018	862
102251028	862
102251038	862
102251228	862
102251238	862
10251	113
10252	1694
1025L04 01 25	851
1025L06 01	851
1025L08 01	851
1025L08 01 05	851
10272	114
10289	114
102GA1818	864
102GA2828	864
102GA3838	864
102GA4848	864
102GB1818	864
102GB2828	864
102GB3838	864
102GB4848	864
102GD0418	864
102GD0428	864
102N1PA12D	237
102N1PA12I	237
102N22PA12D	237
102N22PA12I	237
102N2PA12D	237
102N2PA12I	237
102N35RA12D	237
102N35RA12I	237
10326	113
10332	113
10342	114
10375-04	78
10375-05	78
10375-06	78
10375-08	78
10375-10	78
10375-16	78
10392	113
10394	114
104.22.6.30.PC	568
104.32.0.1.LC	567
104.32.0.1.PA	567
104.32.2.1.LA	567
104.32.2.1.LC	567
104.32.2.1.PA	567
104.32.2.1/1.LA	567
104.32.3.1.PC	567
104.32.6.22/2.PC	568
104.32.6.22/3.LC	567
104.32.6.23/1.LC	567
104.32.6.23/3.LC	567
104.32.6.23/3.PC	567
104.32.6.23/4.PC	567
104.32.6.25.PA	567
104.32.6.27.LC	568
104.32.6.28.PC	568
104.32.6.30.LC	568
104.32.6.30.PC	568
104.32.6.31.LA	568
104.52.6.22/1.L	571
104.52.6.22/2.P	571
104.52.6.25.L	571
104.52.6.27.P	571
104.52.6.28.L	571
104.52.6.30.L	571
104.52.6.30.P	571
104.52.6.31.L	571
10424	114
10432	113
10438	114
10458	113
10459	113
10460	113
10485	114
10491	114
105.32.6.40C	567
10500	278
10511	113
10525-03	76
10525-04	76
10525-05	76
10525-06	76
10525-08	76
10525-10	76
10525-12	76
10525-16	76
10528	113
10541	56
10542	56
10543	56
10544	56
10545	56
10546	56
10548	56
10549	114
1054EL-12	385
10559	113
10575	113
10588	113
10590	113
10597-01	228
10597-02	228
10597-03	228
105R	1538
1063-1	938
1063-112	938
1063-114	938
1063-12	938
1063-14	938
1063-2	938
1063-212	938
1063-3	938
1063-34	938
1063-38	938
1063-4	938
10651	113
10653	113
10668	113
10671	113
10685	113
10692	113
10696	113
1071-1	938
1071-112	938
1071-114	938
1071-12	938
1071-14	938
1071-2	938
1071-212	938
1071-3	938
1071-34	938
1071-38	938
1071-4	938
10715-04-04-04	79
10715-05-05-05	79
10715-06-06-06	79
10715-08-08-08	79
10715-10-10-10	79
10715-12-12-12	79
10716-04-04-04	78
10716-05-05-05	78
10716-06-06-06	78
10716-08-08-08	78
10716-10-10-10	78
10716-12-12-12	78
1072-1	939
1072-12	939
1072-14	939

Code	Page
1072-34	939
1072-38	939
10727	114
10731	113
1073-1	938
1073-112	938
1073-114	938
1073-12	938
1073-14	938
10732	114
1073-2	938
1073-34	938
1073-38	938
1074-1	939
1074-12	939
1074-14	939
1074-34	939
1074-38	939
10750	114
10763	113
10810	113
10900	77
10902	77
10903	77
10904	77
10905	77
10907	77
10908	77
10940	113
10958	228
10959	228
1095EL-12	385
10960	228
10961	228
10962	228
10968	113
1096B-11	385
1097-11	385
1098-11	385
10990	278
10991	114
10996	113
10BPEX-25C	882
10BPEX-50C	882
10BV	881
10EPR	884
10HSV	881
10J-10J-MM-10K	90
10J-12J-MM-10K	90
10J-16J-MM-10K	90
10J-8J-MF-10K	91
10J-8N-MF-A-10K	91
10J-C-10K	94
10J-E-MF-10K	93
10JITS	80
10JMTS	80
10J-P-10K	94
10J-T-MM-10K	93
10JTN	80
10MC	883
10SCV	884
10W OIL	283
11.0612OS2	1722
11/2-ORING	108
11/4-ORING	108
110177	113
110178	113
110179	113
110180	113
110181	113
110182	113
110183	113
110184	113
110228	113
1102N1PA12D	237
1102N1PA12I	237
1102N22PA12D	237
1102N22PA12I	237
1102N2PA12D	237
1102N2PA12I	237
1102N35RA12D	237
1102N35RA12I	237
11041	113
1107A8	1660
1108420000	1535
11089	113
1108A8	1660
110R	1538
111/2-MS	1517
111/2-SS	1517
1110100010XN	469
1110100025XN	469
1110100050XN	469
1110120010CN	469
1110120025CN	469
1110120050CN	469
1110160010CN	469
1110160025CN	469
1110160050CN	469
1110200010CN	469
1110200025CN	469
1110200050CN	469
1110250010CN	469
1110250025CN	469
1110250050CN	469
11139	114
1113R	1538
11157	113
11201	74
1120160010CN	469
1120160025CN	469
1120160050CN	469
1120160080CN	469
1120160100CN	469
1120160125CN	469
1120160160CN	469
1120160200CN	469
11202	74
1120200010CN	469
1120200025CN	469
1120200050CN	469
1120200080CN	469
1120200100CN	469
1120200125CN	469
1120200160CN	469
1120200200CN	469
1120200250CN	469
1120250010CN	469
1120250025CN	469
1120250050CN	469
1120250080CN	469
1120250100CN	469
1120250125CN	469
1120250160CN	469
1120250200CN	469
1120250250CN	469
1120250320CN	469
11203	74
1120320025CN	538
1120320050CN	538
1120320080CN	538
1120320100CN	538
1120320125CN	538
1120320160CN	538
1120320200CN	538
1120320250CN	538
11204	74
1120400025CN	538
1120400050CN	538
1120400080CN	538
1120400100CN	538
1120400125CN	538
1120400160CN	538
1120400200CN	538
1120400250CN	538
11-204-004	689
11-204-006	689
11205	74
1120500025CN	538
1120500050CN	538
1120500080CN	538
1120500100CN	538
1120500125CN	538
1120500160CN	538
1120500200CN	538
1120500250CN	538
11242	113
113R	1538
11506	113
116002	1723
116021	1723
116022	1723
11752	113
11755	113
11-808-960	689
11-818-100	690
11-818-110	690
11-818-999	690
11874	62
11875	62
11876	62
11877	62
11878	62
11880	62
11881	62
11882	62
11883	62
11884	62
11885	62
11905	78
11907	78
1193-1	939
1193-12	939
1193-14	939
1193-34	939
1193-38	939
11975	67
11976	67
11977	67
11978	67
11979	67
11980	67
11981	67
11982	67
11984	67
11985	67
11PN07	1060
11PP07	1060
1200.12.04	477
1200.25.04/1	477
1200.32.03	477
1200.8.01	477
1200.8.02	477
1200.8.05	477
120001515	1121
120002222	1121
120002828	1121
120003535	1121
120004242	1121
120005454	1121
12001000	631
12001300	631
12001700	631
12002100	631
12002700	631
12003200	631
1201015012	1120
1201015034	1120
1201015038	1120
1201022012	1120
1201022034	1120
1201022100	1120
1201028034	1120
1201028100	1120
1201035100	1120
1201035114	1120
1201042112	1120
1201054200	1120
12011	113
12012	113
12013	113
12017	113
12018	113
12019	113
12020	113
1202002	674
1202003	674
120200400	863
120200600	863
1202015012	1120
1202015034	1120
1202022012	1120
1202022034	1120
1202022100	1120
1202028034	1120
1202028100	1120
1202035100	1120
1202035114	1120
1202042112	1120
12020507	630
1202054200	1120
12021	113
12021007	630
12021307	630
12021707	630
12022	113
12022107	630
12022707	630
12023	113
12023207	630
120290400	863
120290600	863
1203-1010	243
1203-1313	243
1203-1717	243
1203-2121	243
120400400	863
120400600	863
120401515	1121
120402222	1121
120402828	1121
120403535	1121
120404242	1121
120405454	1121
12041000	631
12041300	631
12041700	631
12042100	631
12042700	631
12043200	631
120600300	863
120600400	863
120600600	863
12075	113
1208015012	1120
1208022034	1120
1208028100	1120
1208035114	1120
1208042112	1120
1208054200	1120
12090500	631
12091000	631
12091300	631
12091700	631
12092100	631
12092700	631
12093200	631
120R	1538
121/2-MS	1517
121/2-SS	1517
12100	113
1210013	674
1210014	674
12100151515	1123
12100222222	1123
12100282828	1123
12100353535	1123
12100424242	1123
12100500	631
12100545454	1123

Code	Page
12101	113
12101000	631
12101300	631
12102	113
12103	113
12104	113
12105	113
12106	113
12107	113
12109	113
12110	113
12110221522	1123
12110281528	1123
12110282228	1123
12110352235	1123
12110352835	1123
12110422242	1123
12110422842	1123
12110423542	1123
12110542254	1123
12110542854	1123
12110543554	1123
12110544254	1123
12120151215	1123
12120153815	1123
12120221222	1123
12120223422	1123
12120281228	1123
12120283428	1123
12120351235	1123
12120353435	1123
12120421242	1123
12120423442	1123
12120541254	1123
12120543454	1123
12122	113
12123	113
12124	113
121250118	863
121250418	863
121250428	863
121250628	863
121250638	863
12126	113
1213320025BL	500
1213320025CN	491
1213320050BL	500
1213320050CN	491
1213320080BL	500
1213320080CN	491
1213320100BL	500
1213320100CN	491
1213320125BL	500
1213320125CN	491
1213320160BL	500
1213320160CN	491
1213320200BL	500
1213320200CN	491
1213320250BL	500
1213320250CN	491
1213320320BL	500
1213320320CN	491
1213320400BL	500
1213320400CN	491
1213320500BL	500
1213320500CN	491
1213400025BL	500
1213400025CN	491
1213400050BL	500
1213400050CN	491
1213400080BL	500
1213400080CN	491
1213400100BL	500
1213400100CN	491
1213400125BL	500
1213400125CN	491
1213400160BL	500
1213400160CN	491
1213400200BL	500
1213400200CN	491
1213400250BL	500
1213400250CN	491
1213400320BL	500
1213400320CN	491
1213400400BL	500
1213400400CN	491
1213400500BL	500
1213400500CN	491
1213500025BL	500
1213500025CN	491
1213500050BL	500
1213500050CN	491
1213500080BL	500
1213500080CN	491
1213500100BL	500
1213500100CN	491
1213500125BL	500
1213500125CN	491
1213500160BL	500
1213500160CN	491
1213500200BL	500
1213500200CN	491
1213500250BL	500
1213500250CN	491
1213500320BL	500
1213500320CN	491
1213500400BL	500
1213500400CN	491
1213500500BL	500
1213500500CN	491
1213630025BL	500
1213630025CN	492
1213630050BL	500
1213630050CN	492
1213630080BL	500
1213630080CN	492
1213630100BL	500
1213630100CN	492
1213630125BL	500
1213630125CN	492
1213630160BL	500
1213630160CN	492
1213630200BL	500
1213630200CN	492
1213630250BL	500
1213630250CN	492
1213630320BL	500
1213630320CN	492
1213630400BL	500
1213630400CN	492
1213630500BL	500
1213630500CN	492
1213800025AN	492
1213800025WL	500
1213800050AN	492
1213800050WL	500
1213800080AN	492
1213800080WL	500
1213800100AN	492
1213800100WL	500
1213800125AN	492
1213800125WL	500
1213800160AN	492
1213800160WL	500
1213800200AN	492
1213800200WL	500
1213800250AN	492
1213800250WL	500
1213800320AN	492
1213800320WL	500
1213800400AN	492
1213800400WL	500
1213800500AN	492
1213800500WL	500
1213A10025AN	492
1213A10025WL	500
1213A10050AN	492
1213A10050WL	500
1213A10080AN	492
1213A10080WL	500
1213A10100AN	492
1213A10100WL	500
1213A10125AN	492
1213A10125WL	500
1213A10160AN	492
1213A10160WL	500
1213A10200AN	492
1213A10200WL	500
1213A10250AN	492
1213A10250WL	500
1213A10320AN	492
1213A10320WL	500
1213A10400AN	492
1213A10400WL	500
1213A10500AN	492
1213A10500WL	500
1213A20100AN	492
1213A20100WL	500
1213A20125AN	492
1213A20125WL	500
1213A20160AN	492
1213A20160WL	500
1213A20200AN	492
1213A20200WL	500
1213A20250AN	492
1213A20250WL	500
1213A20320AN	492
1213A20320WL	500
1213A20400AN	492
1213A20400WL	500
1213A20500AN	492
1213A20500WL	500
121470418	863
121470428	863
121470628	863
121470638	863
121670418	863
122	1034
122001515	1124
122002222	1124
122002828	1124
122003535	1124
122004242	1124
122005454	1124
1221006	673
122101515	1125
122102222	1125
122102828	1125
122103535	1125
122104242	1125
122105454	1125
1223001	674
122301515	1122
122302222	1122
122302828	1122
122303535	1122
122304242	1122
122305454	1122
122401515	1122
122402222	1122
122402828	1122
1224030	675
122403535	1122
122404242	1122
1224054	675
122405454	1122
1225030	674
1225054	674
1226030	675
1226054	675
123-030	446
123-046	446
1231015012	1124
1231015038	1124
1231022034	1124
1231028100	1124
1231035114	1124
1231042112	1124
1231054200	1124
1232012038	1124
1232015012	1124
1232022012	1124
1232022034	1124
1232028012	1124
1232028100	1124
1232035012	1124
1232035114	1124
123-212	446
1234015012	1125
1234022034	1125
123501515	1126
123502222	1126
123502828	1126
123503535	1126
123504242	1126
123505454	1126
123601515	1126
123602222	1126
123602828	1126
123603535	1126
123604242	1126
123605454	1126
123801515	1126
123802222	1126
123802828	1126
123803535	1126
123804242	1126
123805454	1126
123AL02012A	225
123AL02054A	225
123AL02056A	225
123AL02062A	225
123AL02070A	225
123AL02074A	225
123AL02090A	225
123AL02150A	225
123AL02241A	225
123AL02356A	225
123AL02398A	225
123AL02399A	225
12-3DVL	243
12-3DVT	243
124.3	1058
124.4	1058
124.8	1058
1240022	1125
1240028	1125
1240035	1125
1240042	1125
1240054	1125
1241015	1122
1241022	1122
1241028	1122
1241035	1122
1241042	1122
1241054	1122
124302215	1121
124302815	1121
124302822	1121
124303522	1121
124303528	1121
124304222	1121
124304228	1121
124304235	1121
124305422	1121
124305428	1121
124305435	1121
124305442	1121
12-4DVOC	243
1251-1010	243
1251-1313	243
1251-1717	243
1251-2121	243
1252-2010	243
1252-2013	243
1252-2017	243
1252-2021	243
1253-3013	243
1253-3017	243
1253-3021	243

Code	Page
1261L-11	385
12650	113
12652	113
1270001	675
12785	113
1280.10.100.M	476
1280.10.15.M	476
1280.12.100.M	476
1280.12.15.M	476
1280.12.250.M	476
1280.12.300.M	476
1280.12.50.M	476
1280.16.100.M	476
1280.16.150.M	476
1280.16.160.M	476
1280.16.200.M	476
1280.16.50.M	476
1280.16.75.M	476
1280.16.80.M	476
1280.16.F	477
1280.20.15.M	476
1280.20.150.M	476
1280.20.200.M	476
1280.20.25.M	476
1280.20.250.M	476
1280.20.300.M	476
1280.20.350.M	476
1280.20.50.M	476
1280.20.75.M	476
1280.20.80.M	476
1280.25.100.M	476
1280.25.125.M	476
1280.25.15.M	476
1280.25.200.M	476
1280.25.25.M	476
1280.25.250.M	476
1280.25.300.M	476
1280.25.400.M	476
1280.25.50.M	476
1280.25.75.M	476
1280.25.80.M	476
1280.32.150.M	476
1280.32.250.M	476
1280.32.400.M	476
1280.32.50.M	476
1280.8.FS	477
1281.12.150.M	476
1281.16.150.M	476
1281.16.80.M	476
1281.20.200.M	476
1281.20.50.M	476
1281.25.160.M	476
1281.25.50.M	476
1281.25.75.M	476
1281.32.200.M	476
1281.32.300.M	476
1281.32.50.M	476
1281.32.75.M	476
12826	113
12827	113
12845	113
12847	113
128R	1538
129001510	1126
129001510-3MTR	1126
129002212	1126
129002212-3MTR	1126
129002812	1126
129002812-3MTR	1126
129003515	1126
129003515-3MTR	1126
129004215	1126
129004215-3MTR	1126
129005415	1126
129005415-3MTR	1126
1-290A8	1663
129501506	1126
129501506-3MTR	1126
129502207	1126
129502207-3MTR	1126
129502808	1126
129502808-3MTR	1126
129503510	1126
129503510-3MTR	1126
129504211	1126
129505412	1126
129505412-3MTR	1126
12967	113
12BIKIT	1635
12BIKIT2	1635
12-DVCC	243
12G-10J-MF-10K	91
12G-10J-MM-10K	90
12G-12G-FF-10K	92
12G-12G-MF-A-10K	91
12G-12G-MM-10K	90
12G-12J-MF-10K	91
12G-12J-MM-10K	90
12G-12N-MM-10K	90
12G-16G-MF-A-10K	91
12G-16G-MM-10K	90
12G-16J-MF-10K	91
12G-16J-MM-10K	90
12G-16N-MM-10K	90
12G-2G-MF-B-10K	92
12G-4G-MF-B-10K	92
12G-6G-MF-B-10K	92
12G-8G-MF-B-10K	92
12G-8J-MM-10K	90
12G-C-10K	94
12G-E-FF-10K	93
12G-E-MF-10K	93
12G-E-MM-10K	92
12G-P-10K	94
12G-T-FF-10K	94
12G-T-MM-10K	93
12J-12J-FF-10K	92
12J-12J-MF-10K	91
12J-12N-MF-A-10K	91
12J-16J-MM-10K	90
12J-8J-MF-10K	91
12J-8N-MF-A-10K	91
12J-C-10K	94
12J-E-FF-10K	93
12J-E-MF-10K	93
12JITS	80
12JMTS	80
12J-P-10K	94
12J-T-FF-10K	94
12J-T-MM-10K	93
12JTN	80
12N-12J-E-MF-10K	93
12N-12J-MF-10K	91
12N-12J-MM-10K	90
12N-12N-FF-10K	92
12N-12N-MF-A-10K	91
12N-12N-MM-10K	90
12N-14J-MF-10K	91
12N-16J-MF-10K	91
12N-16J-MM-10K	90
12N-16N-FF-10K	92
12N-16N-MF-A-10K	91
12N-2N-MF-B-10K	92
12N-2N-MM-10K	90
12N-4N-MF-B-10K	92
12N-4N-MM-10K	90
12N-6N-MF-B-10K	92
12N-6N-MM-10K	90
12N-8J-MM-10K	90
12N-8N-MF-B-10K	92
12N-8N-MM-10K	90
12N-C-10K	94
12N-E-10K	93
12N-E-MF-10K	93
12N-E-MM-10K	92
12N-P-10K	94
12N-T-10K	94
12N-T-MM-10K	93
12N-X-10K	94
12PA.BARE	1635
12PA.KIT1B	1635
12PA.KIT1C	1635
12PS10BTV1R2B	250
12SP18	1635
130.2	264
130.3	264
130.4	264
13020	70
1302002	674
1302003	674
13021	70
13022	70
13023	70
13024	70
13025	70
13026	70
130606	810
130607	810
130608	810
130610	811
130611	811
130612	811
130613	811
130614	811
130615	811
130616	811
130622	811
130623	811
130624	811
130642	810
130643	810
130644	810
130698	811
130709	808
130710	808
130711	808
130712	808
130713	808
130714	808
130715	808
130716	808
130717	808
13080	54
13081	54
13082	54
13083	54
13084	54
13085	54
13086	54
13088	54
13089	54
130AA	1034
130AC	1034
130AE	1034
130AL	1034
131.2	264
131.3	264
131.4	264
131.8	264
1310013	674
1310014	674
1315R	1538
131B04-230AC	1038
131B04-24DC	1038
131B14-230AC	1038
131B14-24DC	1038
1320.100.13/1F	515
1320.100.13F	515
1320.32.13/1F	515
1320.32.18F	515
1320.32.32F	515
1320.32.33F	515
1320.40.05/1F	515
1320.40.13/1F	515
1320.40.13F	515
1320.40.32F	515
1320.40.33F	515
1320.50.13/1F	515
1320.50.13F	515
1320.50.32F	515
1320.63.13/1F	515
1320.63.32F	515
1320.80.13/1F	515
1320.80.13F	515
13200	55
13200-10	1210
13200-12	1210
13200-14	1210
13200-22	1210
13200-4	1210
13200-6	1210
13200-8	1210
1321006	673
13220-10-12	1210
13220-10-14	1210
13220-10-38	1210
13220-12-38	1210
13220-14-12	1210
13220-15-12	1210
13220-22-34	1210
13220-4-18	1210
13220-6-14	1210
13220-6-18	1210
13220-8-14	1210
13220-8-18	1210
13220-8-38	1210
13230	72
1323001	674
13231	72
13232	72
13233	72
1324030	675
1324054	675
1325030	674
1325054	674
132600	812
13260-10	1209
13260-12	1209
13260-15	1209
13260-22	1209
1326030	675
13260-4	1209
1326054	675
13260-6	1209
13260-8	1209
13280-10-12	1209
13280-10-14	1209
13280-10-38	1209
13280-12-12	1209
13280-12-14	1209
13280-12-38	1209
13280-14-12	1209
13280-15-12	1209
13280-22-34	1209
13280-4-18	1209
13280-6-14	1209
13280-6-18	1209
13280-8-14	1209
13280-8-18	1209
13280-8-38	1209
132981	811
132999	808
133R	1538
13460-10	1209
13460-12	1209
13460-15	1209
13460-22	1209
13460-4	1209
13460-6	1209
13460-8	1209
13465-10	1209
13465-12	1209
13465-14	1209
13465-4	1209
13465-6	1209
13465-8	1209
13480-10-12	1209
13480-10-14	1209
13480-10-38	1209
13480-12-12	1209

Code	Page
13480-12-14	1209
13480-12-38	1209
13480-14-12	1209
13480-15-12	1209
13480-22-12	1209
13480-22-34	1209
13480-4-14	1209
13480-4-18	1209
13480-6-14	1209
13480-6-18	1209
13480-6-38	1209
13480-8-14	1209
13480-8-18	1209
13480-8-38	1209
13485-10-14	1209
13485-10-38	1209
13485-22-1	1209
13485-22-34	1209
13485-4-18	1209
13485-6-14	1209
13485-6-18	1209
13485-8-14	1209
13485-8-18	1209
13485-8-38	1209
134AA	1034
134AC	1034
134AE	1034
13500-10-12	1209
13500-10-14	1209
13500-10-38	1209
13500-12-12	1209
13500-12-14	1209
13500-12-38	1209
13500-14-12	1209
13500-15-12	1209
13500-22-34	1209
13500-4-14	1209
13500-4-18	1209
13500-6-14	1209
13500-6-18	1209
13500-8-14	1209
13500-8-18	1209
13500-8-38	1209
13510-10	1210
13510-12	1210
13510-6	1210
13510-8	1210
13530-10-14	1209
13530-10-38	1209
13530-6-14	1209
13530-6-18	1209
13530-8-14	1209
13530-8-38	1209
13540-10-10	1210
13540-12-10	1210
13540-12-13	1210
13540-6-7	1210
13540-8-10	1210
13540-8-7	1210
13550-10-14	1210
13550-10-38	1210
13550-4-18	1210
13550-6-14	1210
13550-6-18	1210
13550-8-14	1210
13550-8-18	1210
13550-8-38	1210
1359980	531
13600-10-12	1210
13600-4-6	1210
13600-6-8	1210
13600-8-10	1210
1360248	531
1366948	448
1366949	448
1366950	448
1366951	448
1366952	448
1366953	448
1366954	448
1366955	448
1366956	448
1366957	448
1366958	448
1366959	448
13680-10	1210
13680-12	1210
13680-14	1210
13680-15	1210
13680-4	1210
13680-6	1210
13680-8	1210
1370001	675
13740-10	1210
13740-12	1210
13740-14	1210
13740-15	1210
13740-22	1210
13740-4	1210
13740-6	1210
13740-8	1210
1376301	489
1376304	489
1376305	489
1376306	489
1376307	489
1376308	489
1376309	489
1376310	489
1376311	489
1376312	489
1376313	489
1376314	489
1376422	448
1376423	448
1376424	448
1376425	448
1376426	448
1376427	448
1376428	448
1376429	448
1376430	448
1376431	448
1376432	448
1376433	448
1376467	489
1376468	489
1376469	489
1376470	489
1376471	489
1376472	489
1376473	489
1376474	489
1376475	489
1376476	489
1376477	489
1376478	489
1376656	448
1376657	448
1376658	448
1376659	448
1376660	448
1376661	448
1376662	448
1376663	448
1376664	448
1376665	448
1376666	448
1376667	448
1376903	489
1376904	489
1376905	489
1376906	489
1376907	489
1376908	489
1376909	489
1376910	489
1376911	489
1376912	489
1376913	489
1376914	489
13780-10	1210
13780-12	1210
13780-14	1210
13780-15	1210
13780-22	1210
13780-4	1210
13780-6	1210
13780-8	1210
1380.100.08F	515
1380.100.09/1F	515
1380.100.09F	515
1380.100.11F	515
1380.100.35F	515
1380.32.09F	515
1380.32.10F	515
1380.32.15F	515
1380.32.35F	515
1380.40.09/1F	515
1380.40.09F	515
1380.40.11F	515
1380.40.15F	515
1380.50.08F	515
1380.50.09/1F	515
1380.50.09F	515
1380.50.11F	515
1380.50.15F	515
1380.63.08F	515
1380.63.09/1F	515
1380.63.09F	515
1380.63.11F	515
1380.63.35F	515
1380.80.09F	515
1380.80.15F	515
1380.80.30F	515
1380.80.35F	515
1383333	448
1383334	448
1383335	448
1383336	448
1383337	448
1383338	448
1383339	448
1383340	448
1383341	448
1383342	448
1383343	448
1383344	448
1383366	489
1383367	489
1383368	489
1383369	489
1383370	489
1383371	489
1383372	489
1383373	489
1383374	489
1383375	489
1383376	489
1383377	489
1383578	448
1383579	448
1383580	448
1383581	448
1383582	448
1383583	448
1383584	448
1383585	448
1383586	448
1383587	448
1383588	448
1383589	448
1383632	489
1383633	489
1383634	489
1383635	489
1383636	489
1383637	489
1383638	489
1383639	489
1383640	489
1383641	489
1383642	489
1383643	489
138R	1538
1390.100.03F	515
1390.63.03F	515
1390.80.03F	515
1390.A	515
1391.100.125.01	514
1391.100.150.01	514
1391.100.200.01	514
1391.100.25.01	514
1391.100.250.01	514
1391.100.300.01	514
1391.100.350.01	514
1391.100.400.01	514
1391.100.450.01	514
1391.100.50.01	514
1391.100.500.01	514
1391.100.600.01	514
1391.100.75.01	514
1391.100.800.01	514
1391.125.300.01	514
1391.160.700.01	514
1391.32.100.01	514
1391.32.125.01	514
1391.32.150.01	514
1391.32.200.01	514
1391.32.250.01	514
1391.32.300.01	514
1391.32.350.01	514
1391.32.450.01	514
1391.32.50.01	514
1391.32.500.01	514
1391.40.100.01	514
1391.40.150.01	514
1391.40.200.01	514
1391.40.250.01	514
1391.40.300.01	514
1391.40.350.01	514
1391.40.400.01	514
1391.40.50.01	514
1391.40.500.01	514
1391.40.600.01	514
1391.50.100.01	514
1391.50.1000.01	514
1391.50.125.01	514
1391.50.150.01	514
1391.50.200.01	514
1391.50.25.01	514
1391.50.250.01	514
1391.50.300.01	514
1391.50.350.01	514
1391.50.400.01	514
1391.50.50.01	514
1391.50.500.01	514
1391.50.75.01	514
1391.63.100.01	514
1391.63.150.01	514
1391.63.200.01	514
1391.63.25.01	514
1391.63.250.01	514
1391.63.300.01	514
1391.63.350.01	514
1391.63.450.01	514
1391.80.1000.01	514
1391.80.200.01	514
1391.80.250.01	514
1391.80.300.01	514
1391.80.500.01	514
1395606	531
1-3DVL	243
13KAAK13MPX	331
13KAAK17MPX	331
13KAAK21MPX	331
13KAIW13MPX	331
13KAIW17MPX	331
13KAIW21MPX	331
13KATF06MPX	331

Code	Page
13KATF08MPX	331
13KATF10MPX	331
13KATF13MPX	331
13MHH-0.5	1193
13MHH-1	1193
13MHH-2	1193
13MHH-2.5	1193
13MHH-3	1193
13MHH-4	1193
13MHHM-1	1193
13MHHM-2	1193
13MHHM-2.5	1193
13MHHM-3	1193
13MHHM-4	1193
13PG-0.5	1193
13PG-0.75	1193
13PG-1	1193
13PG-1.5	1193
13PG-2	1193
13PG-2.5	1193
13PG-3	1193
13PG-4	1193
13PNA110DG09R	236
13PNA36DG09R	236
13PNA45DG09R	236
13PNA54DG09R	236
13PNA66DG09R	236
13PNA84DG09R	236
13PNA96DG09R	236
13SFAK13SXN	331
13SFAK17SXN	331
13SFAK21SXN	331
13SFIW13SXN	331
13SFIW17SXN	331
13SFIW21SXN	331
13SFTF06SXN	331
13SFTF08SXN	331
13SFTF10SXN	331
13SFTF13SXN	331
140001-000	1601
140001515	1121
140002222	1121
140002828	1121
140003535	1121
140004242	1121
140005454	1121
140009-000	1601
140021-000	1599
140023-000	1599
140026-134	1599
140027-134	1599
140074-000	1601
140100-000	1597
140101-000	1597
1401015012	1120
1401015034	1120
1401015038	1120
140102-000	1597
1401022012	1120
1401022034	1120
1401022100	1120
1401028034	1120
1401028100	1120
140103-000	1597
1401035100	1120
1401035114	1120
140104-000	1597
1401042112	1120
1401054200	1120
140106-000	1598
140108-000	1601
140110-000	1599
140111-000	1599
140112-000	1597
140112B-000	1597
140113-000	1597
140113B-000	1597
140114-000	1597
140114B-000	1597
140118-000	1601
140120-000	1597
140120-159	1597
140125-000	1598
140126-000	1598
140128-000	1598
140129-000	1598
140135-000	1598
140136-000	1598
140141-000	1597
140160-000	1598
140161-000	1598
140170-000	1598
140171-000	1598
1402002	674
1402003	674
1402015012	1120
1402015034	1120
1402015038	1120
1402022012	1120
1402022034	1120
1402022100	1120
1402028034	1120
1402028100	1120
1402035100	1120
1402035114	1120
1402042112	1120
1402054200	1120
140401515	1121
140402222	1121
140402828	1121
140403535	1121
140404242	1121
140405454	1121
1406N1PA12D	237
1406N1PA12I	237
1406N22PA12D	237
1406N22PA12I	237
1406N2PA12D	237
1406N2PA12I	237
1406N35RA12D	237
1406N35RA12I	237
1408015012	1120
1408022034	1120
1408028100	1120
1408035114	1120
1408042112	1120
1408054200	1120
140858-000	1599
140900-000	1597
140R	1538
141000-000	1599
141001-000	1599
1410013	674
1410014	674
14100151515	1123
14100222222	1123
14100282828	1123
14100353535	1123
14100424242	1123
14100545454	1123
14110221522	1123
14110281528	1123
14110282228	1123
14110352235	1123
14110352835	1123
14110422242	1123
14110422842	1123
14110423542	1123
14110542254	1123
14110542854	1123
14110543554	1123
14110544254	1123
1412000	278
14120151215	1123
14120153815	1123
14120221222	1123
14120223422	1123
14120281218	1123
14120283428	1123
14120351235	1123
14120353435	1123
14120421242	1123
14120423442	1123
14120541254	1123
14120543454	1123
1420000	278
142001515	1124
142002222	1124
142002828	1124
142003535	1124
142004242	1124
142005454	1124
1421006	673
142101-000	1601
142101515	1125
142102222	1125
142102828	1125
142103535	1125
142104242	1125
142105454	1125
142130-000	1601
142131-000	1601
142135-000	1601
1422002	673
1423001	674
142301515	1122
142302222	1122
142302828	1122
142303535	1122
142304242	1122
142305454	1122
142401515	1122
142402222	1122
142402828	1122
1424030	675
142403535	1122
142404242	1122
1424054	675
142405454	1122
1425030	674
1425054	674
1426030	675
1426054	675
1427379	531
1430000	278
143-1	980
1431015012	1124
1431015038	1124
143102-000	1600
1431022034	1124
1431028100	1124
143103-000	1600
1431035114	1124
1431042112	1124
1431054200	1124
143-112	980
143-114	980
143-12	980
143-2	980
1432015012	1124
1432015038	1124
1432022012	1124
1432022034	1124
1432028012	1124
1432028100	1124
1432035012	1124
1432035114	1124
143-212	980
143-3	980
143-34	980
143-4	980
1434015012	1125
1434022034	1125
14364	1763
14365	1763
14366	1763
1440022	1125
1440028	1125
1440035	1125
1440042	1125
1440054	1125
1441015	1122
1441022	1122
1441028	1122
1441035	1122
1441042	1122
1441054	1122
144116	1599
144180	1601
144194	1595
144302215	1121
144302815	1121
144302822	1121
144303522	1121
144303528	1121
144304222	1121
144304228	1121
144304235	1121
144305422	1121
144305428	1121
144305435	1121
144305442	1121
145100-000	1601
145110-000	1600
145219	1601
145950-000	1599
145955-000	1599
145R	1538
1461EL-12	385
1462B-11	385
1462EL-12	385
1470001	675
147150-134	1600
1492110	1035
1492111	1035
1492112	1035
1492113	1035
1492114	1035
1492118	1035
1492119	1035
1492120	1035
1492121	1035
1492122	1035
1492206	1035
1492207	1035
1492208	1035
1492209	1035
1492210	1035
1492214	1035
1492215	1035
1492216	1035
1492217	1035
1492218	1035
1492302	1035
1492303	1035
1492304	1035
1492305	1035
1492306	1035
1492310	1035
1492311	1035
1492312	1035
1492313	1035
1492314	1035
14J-12J-MF-10K	91
14JMTS	80
14J-T-MM-10K	93
14KAAW13MPX	332
14KAAW17MPX	332
14KAAW21MPX	332
14KAIW13MPX	332
14KAIW17MPX	332
14KAIW21MPX	332
14KATF06MPX	332
14KATF08MPX	332
14KATF09MPX	332
14KATF10MPX	332
14KATF13MPX	332
14KEAK13MPN	333
14KEAK21MPN	333
14KEIW13MPN	333

Code	Page
14KEIW17MPN	333
14KEIW21MPN	333
14KETF06MPN	333
14KETF08MPN	333
14KETF09MPN	333
14KETF10MPN	333
14KETF13MPN	333
14MMP-0.5	1193
14MMP-0.75	1193
14MMP-1	1193
14MMP-1.5	1193
14MMP-2	1193
14MMP-2.5	1193
14MMP-3	1193
14MMP-4	1193
1500.U	477
1500-2	1148
1500-3	1148
1500-4	1148
1500-6	1148
150120-134	1723
150123-134	1723
150130-134	1723
150131-134	1723
1502003	674
15026	64
15027	64
15028	64
15030	64
15031	64
15032	64
1503269	531
1504-22	1148
1504-32	1148
1504-33	1148
1504-43	1148
1504-44	1148
1504-64	1148
1504-66	1148
150HIT 04	936
150HIT 05	936
150HIT 06	936
150HIT 07	936
150HIT 08	936
150HIT 09	936
150HIT 10	936
150HIT 11	936
150HIT 12	936
150HIT 13	936
150HIT 14	936
150HIT 16	936
150R	1538
151120-134	1723
1513-2	1148
1513-3	1148
1513-4	1148
1513-6	1148
151687	581
1517R	1538
1518R	1538
1521006	673
1523001	674
1523-2	1148
1523-3	1148
1523-4	1148
1523-6	1148
1524030	675
1526825	531
1526986	531
153001	808
153002	808
153003	808
153004	808
153005	808
153006	808
153007	808
153008	808
153009	808
153010	808
153012	808
153013	808
153014	808
153015	808
153016	808
153017	808
153018	808
153019	808
153020	808
153021	808
153022	808
153023	808
153024	808
153025	808
153026	808
153027	808
153028	808
153029	808
153030	808
153031	810
153032	810
153033	810
153034	810
153035	810
153037	810
153038	810
153039	810
153040	810
153041	811
153042	811
153043	811
153044	811
153045	809
153046	809
153047	809
153048	809
153049	809
153050	809
153051	809
153052	809
153053	809
153054	809
153056	811
153057	811
153058	811
153059	811
153060	811
153061	811
153062	811
153063	811
153065	811
153066	811
153067	811
153068	811
153069	811
153070	811
153071	811
153072	811
153073	811
153074	811
153076	809
153077	809
153078	809
153079	809
153080	809
153081	809
153082	809
153083	809
153084	809
153085	809
153086	810
153087	810
153088	810
153089	810
153090	810
153091	810
153092	810
153093	810
153094	810
153095	810
153106	809
153107	809
153108	809
153109	809
153110	809
153111	809
153112	809
153113	809
153114	809
153115	809
153117	809
153118	809
153119	809
153120	809
153121	809
153122	809
153123	809
153124	809
153125	809
153126	809
153128	811
153129	811
153130	811
153131	811
153132	811
153134	811
153135	811
153136	811
153137	811
153138	810
153139	810
153140	810
153141	810
153142	810
153143	810
153144	810
153145	810
153146	810
153147	810
153148	811
153149	811
153150	811
153151	811
153152	811
153153	811
153154	811
153155	811
153156	811
153157	810
153158	810
153159	810
153160	810
153161	810
153172	810
153173	810
153174	810
153175	810
153176	810
153177	810
153178	810
153179	810
153180	810
153181	810
153262	811
153263	811
153264	811
153265	811
153266	811
153267	811
153268	811
153269	811
153270	811
153271	811
153273	809
153274	809
153275	809
153276	809
153277	809
153278	809
153279	809
153280	809
153303	812
153304	812
153305	812
153306	812
153307	812
153314	812
153315	812
153316	812
153317	812
153318	812
153319	812
153321	812
153324	813
153325	813
153326	813
153327	813
153328	813
153329	813
153332	812
153333	812
153334	812
153335	812
153336	812
153344	813
153345	813
153347	813
153348	813
153349	813
153350	813
153366	813
153367	813
153368	813
153369	813
153371	813
153372	813
153373	813
153374	813
153376	813
153377	813
153498	816
153499	816
153500	816
153501	816
153502	816
153503	816
153504	816
153505	816
153506	816
153507	816
153508	816
153509	816
153510	816
153511	816
153512	816
153513	816
153514	816
153515	816
153516	816
153517	816
153518	816
153519	816
153520	816
153521	816
1540.100.80.01.1	536
1540.20.03F	536
1540.20.05/1F	536
1540.20.15.01.1	536
1540.20.50.01.1	536
1540.25.50.01.1	536
1540.25.60.01.1	536
1540.32.15.01.1	536
1540.32.20.01.1	536
1540.32.200.01.1	536
1540.32.30.01.1	536
1540.32.60.01.1	536
1540.40.75.01.1	536
1540.50.100.01.1	536
1540.50.30.01.1	536
1540.50.35.01.1	536
1540.50.50.01.1	536

Code	Page
1540.63.100.01.1	**536**
1540.63.25.01.1	**536**
1540.63.50.01.1	**536**
1547102	**531**
156100-134	**1723**
1577238	**531**
1578512	**531**
1578518	**531**
1580U	**477**
15-8-2MM	**1421**
15900007	**1538**
15APT-B	**881**
15BDC	**881**
15BPB-100C	**882**
15BPB-25C	**882**
15BPB-50C	**882**
15BPEX-100C	**882**
15BPEX-20X2L	**882**
15BPEX-20X3L	**882**
15BPEX-25C	**882**
15BPEX-50C	**882**
15BSC	**881**
15BV	**881**
15DCV	**881**
15ESOT	**881**
15HSV	**881**
15ISV	**881**
15JMTS	**80**
15MC	**883**
15PTSV	**881**
15RA	**1091**
15STV	**881**
15WB	**880**
1600KEAK13SPN	**357**
1600KEIW13SPN	**357**
1600KEIW17SPN	**357**
1600KEIW21SPN	**357**
1600KETF09SPN	**357**
1600KETF10SPN	**357**
1600KETF13SPN	**357**
1602003	**674**
16060	**58**
16061	**58**
16062	**58**
16063	**58**
16065	**58**
16066	**58**
16067	**58**
16068	**58**
16069	**58**
16070	**58**
16071	**58**
16072	**58**
16073	**58**
16075	**58**
16082	**58**
16083	**58**
16084	**58**
16085	**58**
16089	**58**
16090	**58**
16091	**58**
16092	**58**
16093	**58**
16094	**58**
16095	**58**
16096	**58**
16102	**58**
16103	**58**
16117	**59**
16121	**59**
16122	**59**
16123	**59**
16124	**59**
16125	**59**
16126	**59**
16127	**59**
16128	**59**
16136	**59**
16137	**59**
16142	**59**
16169	**58**
16170	**58**
16171	**58**
16172	**58**
16173	**58**
16174	**58**
16175	**58**
16176	**58**
16178	**58**
16180	**59**
16181	**59**
16182	**59**
16183	**59**
16184	**59**
16186	**59**
16187	**59**
16190	**59**
16191	**59**
1621006	**673**
1623001	**674**
1624030	**675**
16249	**74**
16250	**74**
16251	**74**
16252	**74**
16253	**74**
16254	**74**
16255	**74**
16256	**74**
16257	**74**
16258	**74**
16261	**74**
16301	**60**
16302	**60**
16350	**59**
16351	**59**
16352	**59**
163529	**490**
16354	**59**
16355	**59**
16356	**59**
16359	**59**
16360	**59**
16365	**59**
16366	**58**
1644389	**531**
164980	**808**
164981	**809**
16601	**59**
16700001	**1539**
16700002	**1539**
16700003	**1539**
16700004	**1539**
16700005	**1539**
16700006	**1539**
16700007	**1539**
16700008	**1539**
16700009	**1539**
16700010	**1539**
16700011	**1539**
16700012	**1539**
16700013	**1539**
16700014	**1539**
16700015	**1539**
16700016	**1539**
16700017	**1539**
16700018	**1539**
16700019	**1539**
16700020	**1539**
16700024	**1539**
16700026	**1539**
16700028	**1539**
16700029	**1539**
16700033	**1539**
16700037	**1539**
16700040	**1539**
16700042	**1539**
16700044	**1539**
16700046	**1539**
16700048	**1539**
16700050	**1539**
16700052	**1539**
16700053	**1539**
16700054	**1539**
16700055	**1539**
16700056	**1539**
16700057	**1539**
16700058	**1539**
16700059	**1539**
16700061	**1539**
16700063	**1539**
16700065	**1539**
16700067	**1539**
16700069	**1539**
16700071	**1539**
16700073	**1539**
16700075	**1539**
16700077	**1539**
16700079	**1539**
16700081	**1539**
16700086	**1539**
16700092	**1539**
16700094	**1539**
16700110	**1539**
16702148	**1539**
16702488	**1539**
16702491	**1539**
16702492	**1539**
16702493	**1539**
16702494	**1539**
16702495	**1539**
16702496	**1539**
16702497	**1539**
16702498	**1539**
16702864	**1539**
16702951	**1539**
16702993	**1539**
16702998	**1539**
16704055	**1539**
168R	**1538**
16AMP-0.5	**1193**
16AMP-1	**1193**
16AMP-2	**1193**
16AMP-2.5	**1193**
16AMP-3	**1193**
16AMP-4	**1193**
16G-10J-MM-10K	**90**
16G-12G-MF-B-10K	**92**
16G-12J-MF-10K	**91**
16G-12J-MM-10K	**90**
16G-16G-FF-10K	**92**
16G-16G-MF-A-10K	**91**
16G-16G-MM-10K	**90**
16G-16J-MF-10K	**91**
16G-16J-MM-10K	**90**
16G-16N-MM-10K	**90**
16G-2G-MF-B-10K	**92**
16G-4G-MF-B-10K	**92**
16G-6G-MF-B-10K	**92**
16G-8G-MF-B-10K	**92**
16G-C-10K	**94**
16G-E-FF-10K	**93**
16G-E-MF-10K	**93**
16G-E-MM-10K	**92**
16G-P-10K	**94**
16G-T-FF-10K	**94**
16G-T-MM-10K	**93**
16J-12J-MF-10K	**91**
16J-16J-FF-10K	**92**
16J-16J-MF-10K	**91**
16J-16J-MM-10K	**90**
16J-16N-MF-A-10K	**91**
16J-C-10K	**94**
16J-E-FF-10K	**93**
16J-E-MF-10K	**93**
16JITS	**80**
16JMTS	**80**
16J-P-10K	**94**
16J-T-FF-10K	**94**
16J-T-MM-10K	**93**
16JTN	**80**
16N-12J-MM-10K	**90**
16N-12N-MF-B-10K	**92**
16N-12N-MM-10K	**90**
16N-16J-MF-10K	**91**
16N-16J-MM-10K	**90**
16N-16N-FF-10K	**92**
16N-16N-MF-A-10K	**91**
16N-16N-MM-10K	**90**
16N-2N-MF-B-10K	**92**
16N-2N-MM-10K	**90**
16N-4N-MF-B-10K	**92**
16N-4N-MM-10K	**90**
16N-6N-MF-B-10K	**92**
16N-6N-MM-10K	**90**
16N-8N-MF-B-10K	**92**
16N-8N-MM-10K	**90**
16N-C-10K	**94**
16N-E-10K	**93**
16N-E-MF-10K	**93**
16N-E-MM-10K	**92**
16N-P-10K	**94**
16N-T-MM-10K	**93**
16N-X-10K	**94**
170001515	**1121**
170002222	**1121**
170002828	**1121**
170003535	**1121**
170004242	**1121**
170005454	**1121**
17001	**74**
17004	**74**
1700KEAW17SPN	**368**
1700KEAW21SPN	**368**
1700KEAW26SPN	**368**
1700KEIW21SPN	**368**
1700KEIW26SPN	**368**
1701015012	**1120**
1701015034	**1120**
1701015038	**1120**
1701022012	**1120**
1701022034	**1120**
1701022100	**1120**
1701028034	**1120**
1701028100	**1120**
1701035100	**1120**
1701035114	**1120**
1701042112	**1120**
1701054200	**1120**
1702015012	**1120**
1702015034	**1120**
1702015038	**1120**
1702022012	**1120**
1702022034	**1120**
1702022100	**1120**
1702028034	**1120**
1702028100	**1120**
1702035100	**1120**
1702035114	**1120**
1702042112	**1120**
1702054200	**1120**
170401515	**1121**
170402222	**1121**
170402828	**1121**
170403535	**1121**
170404242	**1121**
170405454	**1121**
1708015012	**1120**
1708022034	**1120**
1708028100	**1120**
1708035114	**1120**
1708042112	**1120**
1708054200	**1120**
170824	**528**
170825	**528**
170826	**528**
170827	**528**
170828	**528**
170829	**528**

Code	Page
170830	528
170831	528
170832	528
170833	528
170834	528
170835	528
170836	528
170837	528
170838	528
170839	528
170840	528
170841	528
170842	528
170843	528
170844	528
170845	528
170846	528
170847	528
170848	528
170849	528
170850	528
170851	528
170852	528
170853	528
170854	528
170855	528
170856	528
170857	528
170858	528
170859	528
170860	528
170861	528
170862	528
170863	528
170864	528
170865	528
170866	528
170867	528
170868	528
170869	528
170870	528
170871	528
170872	528
170873	528
170874	528
170875	528
170876	528
170877	528
170878	528
170879	528
170880	528
170881	528
170882	528
170883	528
170884	528
170899	529
170900	529
170901	529
170902	529
170903	529
170904	529
170905	529
170906	529
170907	529
170908	529
170909	529
170910	529
170911	529
170912	529
170913	529
170914	529
170915	529
170916	529
170917	529
170918	529
170919	529
170920	529
170921	529
170922	529
170923	529
170924	529
170925	529
170926	529
170927	529
170928	529
170929	529
170930	529
170931	529
170932	529
170933	529
170934	529
170935	529
170936	529
170937	529
170938	529
170939	529
170940	529
170941	529
170942	529
170943	529
170944	529
170945	529
170946	529
170947	529
170948	529
170949	529
170950	529
170951	529
170952	529
170953	529
170954	529
170955	529
170956	529
170957	529
170958	529
170959	529
171.034RTOS	1602
171.067OS	1602
171.078OS	1602
17100.04	706
17100.125.NR	706
17100151515	1123
17100222222	1123
17100282828	1123
17100353535	1123
17100424242	1123
17100545454	1123
17110221522	1123
17110281528	1123
17110282228	1123
17110352235	1123
17110352835	1123
17110422242	1123
17110422842	1123
17110423542	1123
17110542254	1123
17110542854	1123
17110543554	1123
17110544254	1123
17120151215	1123
17120153815	1123
17120221222	1123
17120223422	1123
17120281228	1123
17120283428	1123
17120351235	1123
17120353435	1123
17120421242	1123
17120423442	1123
17120541254	1123
17120543454	1123
172001515	1124
172002222	1124
172002828	1124
172003535	1124
172004242	1124
172005454	1124
1720R	1538
172101515	1125
172102222	1125
172102828	1125
172103535	1125
172104242	1125
172105454	1125
172301515	1122
172302222	1122
172302828	1122
172303535	1122
172304242	1122
172305454	1122
172401515	1122
172402222	1122
172402828	1122
172403535	1122
172404242	1122
172405454	1122
1731015012	1124
1731015038	1124
1731022034	1124
1731028100	1124
1731035114	1124
1731042112	1124
1731054200	1124
1732015012	1124
1732015034	1124
1732015038	1124
1732028012	1124
1732028100	1124
1732035012	1124
1732035114	1124
1734015012	1125
1734022034	1125
1740.02	706
1740.50.NR	706
1740022	1125
1740028	1125
1740035	1125
1740042	1125
1740054	1125
1741015	1122
1741022	1122
1741028	1122
1741035	1122
1741042	1122
1741054	1122
174302215	1121
174302815	1121
174302822	1121
174303522	1121
174303528	1121
174304222	1121
174304228	1121
174304235	1121
174305422	1121
174305428	1121
174305435	1121
174305442	1121
174369	490
174370	490
174371	490
174372	490
174373	490
174383	490
174384	490
174385	490
174386	490
174387	490
174390	490
174391	490
174392	490
174393	490
174394	490
174397	490
174398	490
174399	490
174400	490
174401	490
174404	490
174405	490
174406	490
174407	490
174408	490
175091	468
175092	468
175093	468
175094	468
175095	468
175096	468
175097	468
175098	468
175099	468
175100	468
175R	1538
1763.03	706
1763.80.NR	706
1776K-0-05	986
1776K-0-10	986
1776K-0-15	986
1776K-0-20	986
1776K-0-25	986
1776K-0-30	986
1776K-0-40	986
1776K-0-50	986
1776K-0-60	986
1776K-0-75	986
17-816-998	690
17-816-999	690
17KAAK13SPN	334
17KAAK17SPN	334
17KAAK21SPN	334
17KAIW13SPN	334
17KAIW17SPN	334
17KAIW21SPN	334
17KATF06SPN	334
17KATF08SPN	334
17KATF10SPN	334
17KATF13SPN	334
17SFAK10SXN	334
17SFAK13SXN	334
17SFAK17SXN	334
17SFAK21SXN	334
17SFIW10SXN	334
17SFIW13SXN	334
17SFIW17SXN	334
17SFIW21SXN	334
17SFTF06SXN	334
17SFTF08SXN	334
17SFTF10SXN	334
17SFTF13SXN	334
17W	334
17Y	334
18001	71
18003	71
1801001	762
1801006	762
1801021	762
1801047	762
18-013-013	683
18-013-989	690
18-013-990	690
1802003	762
1802011	762
1803002	762
18121208	903
18121510	903
18121913	903
182	1034
1824431001	1547
1845706	544
1845707	544
1845708	544
1845709	544
1845710	544
1845711	544
1845712	544
1845713	544
1845714	544
1845715	544
1845716	544
1845717	544

Code	Page
1845718	**544**
1845719	**544**
1845720	**544**
1845721	**544**
1845722	**544**
1845723	**544**
1845724	**544**
18530-1	**937**
18530-2	**937**
18530-3	**937**
18560-1	**937**
18560-2	**937**
18560-3	**937**
18560-4	**937**
18560-5	**937**
18560-6	**937**
18563-1	**937**
18563-2	**937**
18563-3	**937**
18563-4	**937**
18570-1	**937**
18570-2	**937**
18570-3	**937**
185R	**1538**
186095	**808**
186096	**808**
186097	**808**
186098	**808**
186099	**808**
186100	**808**
186101	**808**
186102	**808**
186103	**808**
186104	**808**
186106	**808**
186107	**808**
186108	**808**
186109	**808**
186110	**808**
186111	**808**
186112	**808**
186113	**808**
186114	**808**
186115	**808**
186116	**809**
186117	**809**
186118	**809**
186119	**809**
186120	**809**
186121	**809**
186122	**809**
186123	**809**
186124	**809**
186125	**809**
186137	**810**
186138	**810**
186139	**810**
186140	**810**
186141	**810**
186142	**810**
186143	**810**
186144	**810**
186145	**810**
186146	**810**
186264	**812**
186265	**812**
186266	**812**
186267	**812**
186268	**812**
186269	**812**
186350	**808**
186351	**809**
186352	**812**
186353	**812**
18-867	**406**
18-867/1	**406**
18-868	**406**
18-868/1	**406**
18-978/1	**406**
18-979/1	**406**
18-980/1	**406**
18-981/1	**406**
18-982/1	**406**
18-983/1	**406**
18A511028	**1204**
18A511048	**1204**
18A511238	**1204**
18JMTS	**80**
18KAAK13MPN	**335**
18KAAK17MPN	**335**
18KAAK21MPN	**335**
18KAIW13MPN	**335**
18KAIW17MPN	**335**
18KAIW21MPN	**335**
18KATF06MPN	**335**
18KATF08MPN	**335**
18KEIW21SPN	**336**
18SFAK13SXN	**335**
18SFIW13SXN	**335**
18SFIW17SXN	**335**
18SFTF06SXN	**335**
18SFTF08SXN	**335**
18SFTF10SXN	**335**
1-906-22-11-600	**270**
1-906-23-11-600	**270**
1-906-24-11-600	**270**
1-906-28-11-600	**270**
1-906-29-11-600	**270**
1-906-30-11-600	**270**
1-906-39-30-600	**270**
1-906-40-30-600	**270**
190643	**808**
1-906-43-00-600	**270**
190644	**808**
1-906-44-00-600	**270**
190645	**808**
190646	**808**
190647	**808**
190648	**808**
190649	**808**
190650	**808**
190651	**808**
190652	**808**
190653	**808**
190654	**808**
190658	**809**
190659	**809**
190660	**809**
190661	**809**
190662	**809**
190663	**809**
190664	**809**
190666	**810**
190667	**809**
190668	**809**
190669	**809**
190670	**809**
190672	**809**
190673	**810**
190674	**810**
190675	**810**
190708	**811**
1-908-00-20-600	**270**
1-908-02-20-600	**270**
1-908-03-20-600	**270**
1-908-04-20-600	**270**
1-908-05-20-600	**270**
1-908-06-20-600	**270**
1-908-07-20-600	**270**
1908255	**463**
1908256	**463**
1908257	**463**
1908258	**463**
1908259	**463**
1908260	**463**
1908261	**463**
1908262	**463**
1908263	**463**
1908264	**463**
1908265	**463**
1908266	**464**
1908267	**464**
1908268	**464**
1908269	**464**
1908270	**464**
1908271	**464**
1908272	**464**
1908273	**464**
1908274	**465**
1908275	**465**
1908276	**465**
1908277	**465**
1908278	**465**
1908279	**465**
1908280	**465**
1908281	**465**
1908282	**463**
1908283	**463**
1908284	**463**
1908285	**463**
1908286	**463**
1908287	**463**
1908288	**463**
1908289	**464**
1908290	**464**
1908291	**464**
1908292	**464**
1908293	**464**
1908294	**464**
1908295	**464**
1908296	**464**
1908297	**465**
1908298	**465**
1908299	**465**
1908300	**465**
1908301	**465**
1908302	**465**
1908303	**465**
1908304	**465**
1908305	**463**
1908306	**463**
1908307	**463**
1908308	**463**
1908309	**463**
1908310	**463**
1908311	**463**
1908312	**464**
1908313	**464**
1908314	**464**
1908315	**464**
1908316	**464**
1908317	**464**
1908318	**464**
1908319	**464**
1908320	**465**
1908321	**465**
1908322	**465**
1908323	**465**
1908324	**465**
1908325	**465**
1908326	**465**
1908327	**465**
19-10-2MM	**1421**
1-912-28-12-660	**269**
1-912-29-12-660	**269**
19150	**70**
19151	**70**
19152	**70**
19153	**70**
19154	**70**
19155	**70**
19156	**70**
19157	**70**
19158	**70**
19159	**70**
19160	**70**
19162	**70**
1-918-29-01-240	**269**
1-918-31-01-240	**269**
19189	**463**
19190	**463**
19191	**463**
19192	**463**
19193	**463**
19194	**463**
19195	**463**
19196	**463**
19197	**463**
19198	**463**
19199	**463**
19200	**463**
19201	**463**
19202	**463**
19203	**463**
19204	**463**
19205	**463**
19206	**463**
19207	**463**
19208	**463**
19209	**463**
19210	**463**
19211	**463**
192-112-STRAINER	**972**
192-114-STRAINER	**972**
19212	**463**
192-12-STRAINER	**972**
19213	**463**
19214	**463**
19215	**463**
19216	**463**
19217	**463**
19218	**463**
19219	**463**
192-1-STRAINER	**972**
19220	**463**
19221	**463**
192-212-STRAINER	**972**
19222	**463**
19223	**463**
19224	**463**
19225	**463**
19226	**463**
19227	**463**
19228	**463**
19229	**464**
1922R	**1538**
192-2-STRAINER	**972**
19230	**464**
19231	**464**
19232	**464**
19233	**464**
19234	**464**
192-34-STRAINER	**972**
19235	**464**
19236	**464**
19237	**464**
19238	**464**
19239	**464**
192-3-STRAINER	**972**
19240	**464**
19241	**464**
19242	**464**
19243	**464**
19244	**464**
19245	**464**
19246	**464**
19247	**464**
19248	**464**
19249	**464**
192-4-STRAINER	**972**
19250	**464**
19251	**464**
19252	**464**
19253	**464**
1-927-29-01-020	**269**
1-927-31-01-020	**269**
19280	**65**
19281	**65**
19282	**65**
19283	**65**

Code	Page
19284	65
19285	65
193137	815
193138	815
193139	815
193142	815
193143	815
193144-FESTO	815
193145	815
193146	815
193147	815
193148	815
193149	815
193150	815
193151	815
193152	815
193153	815
193154	815
193155	815
193156	815
193157	815
193158	815
193159	815
1-940-31-22-080	269
195R	1538
1-970-02-04-010	270
1-970-02-04-030	270
1-970-02-04-050	270
1-970-02-04-060	270
1-970-02-04-080	270
1-970-02-04-090	270
1-970-02-04-100	270
1-970-02-04-110	270
1-970-02-04-120	270
1-970-02-04-140	270
1-970-04-04-010	270
1-970-04-04-040	270
1-970-04-04-060	270
1-970-04-04-080	270
1-970-04-04-090	270
1-970-04-04-100	270
1-970-04-04-110	270
1-970-04-04-120	270
1-970-04-04-130	270
1-970-04-04-140	270
1-970-04-25-090	270
1-970-04-25-100	270
1-970-04-25-110	270
197376	912
197377	912
197383	912
197384	912
197390	912
197391	912
197576	815
197577	815
197578	815
197579	815
197580	815
197581	815
19800	58
19801	58
19802	58
19803	58
19804	58
1-980-48-60-040	270
19920	60
19921	60
19922	60
19923	60
19924	60
19925	60
19927	60
19930	60
19931	60
19932	60
19933	60
19934	60
19935	60
19951	70
19953	70
19955	70
199M10U916	97
199M12U34	97
199M16U78	97
199M18U1116	97
199M22U1316	97
199M25U1516	97
199M32U158	97
199M38U178	97
199M6U716	97
199M8U12	97
19FAAK13	338
19FAAK17	338
19FAAK21	338
19FAIW13	338
19KAAK13MPX	337
19KAAK17MPX	337
19KAAK21MPX	337
19KAIW13MPX	337
19KAIW17MPX	337
19KAIW21MPX	337
19KATF06MPX	337
19KATF08MPX	337
19KATF10MPX	337
19KATF13MPX	337
19SFAK13SXN	337
19SFAK17SXN	337
19SFAK21SXN	337
19SFIW13SXN	337
19SFIW17SXN	337
19SFIW21SXN	337
19SFTF05SXN	337
19SFTF06SXN	337
19SFTF08SXN	337
19SFTF10SXN	337
19SFTF13SXN	337
19VRN.G.12.RXS00	749
19VRN.G.14.FXR00	749
19VRN.G.14.HXN00	749
19VTF.S.05.02000	748
19VTF.S.05.02500	748
19VTF.S.14.03500	748
19VTF.S.14.05000	748
19VTN.G.04000	749
19VTN.G.06400	749
19VTS.P14.04025	748
19VTS.P18.03025	748
19VTS.P38.05025	748
19VTS.P38.07025	748
19VTS.S.12.05035	748
19VTS.S.14.03035	748
19VTS.S.38.04035	748
19W	338
19Y	338
1A-MS	1517
1A-MS-BOX	1517
1A-SS	1517
1BFF0404-1000	1649
1BFF0404-600	1649
1BFF0404-750	1649
1BJP0207	73
1BJP0208	73
1BJP0209	73
1BJP0407	73
1BJP0408	73
1BJP0409	73
1BJP0412	73
1BJP0414	73
1BJP0417	73
1BJP0421	73
1BJP0607	73
1BJP0608	73
1BJP0609	73
1BJP0612	73
1BJP0614	73
1BJP0617	73
1BJP0621	73
1BJP0807	73
1BJP0808	73
1BJP0809	73
1BJP0812	73
1BJP0814	73
1BJP0817	73
1BJP0821	73
1BJP1009	73
1BJP1012	73
1BJP1014	73
1BJP1017	73
1BJP1019	73
1BJP1021	73
1BJP1207	73
1BJP1208	73
1BJP1209	73
1BJP1212	73
1BJP1214	73
1BJP1217	73
1BJP1219	73
1BJP1221	73
1BJP1226	73
1BJP1230	73
1BJP1612	73
1BJP1614	73
1BJP1617	73
1BJP1619	73
1BJP1621	73
1BJP1626	73
1BJP1630	73
1BJP2017	73
1BJP2021	73
1BJP2026	73
1BJP2030	73
1BJP2040	73
1BJP2421	73
1BJP2426	73
1BJP2430	73
1BJP2440	73
1BJP3230	73
1BJP3240	73
1BMF0808-10000	1649
1BMF0808-2000	1649
1BMF0808-4000	1649
1BMF0808-600	1649
1BMF0808-800	1649
1BNT0204	55
1BNT0402	55
1BNT0404	55
1BNT0406	55
1BNT0604	55
1BNT0606	55
1BNT0808	55
1BNT1212	55
1BNT1616	55
1BNT2420	55
1BNT2424	55
1BNT3232	55
1BNT4040	55
1BP0202	54
1BP0204	54
1BP0206	54
1BP0208	54
1BP02T02	55
1BP02T04	55
1BP02T06	55
1BP0404	54
1BP0406	54
1BP0408	54
1BP0410	54
1BP0412	54
1BP0416	54
1BP0420	54
1BP0432	54
1BP04T02	55
1BP04T04	55
1BP04T06	55
1BP04T08	55
1BP04T12	55
1BP0606	54
1BP0608	54
1BP0610	54
1BP0612	54
1BP0616	54
1BP0620	54
1BP0624	54
1BP06T02	55
1BP06T04	55
1BP06T06	55
1BP06T08	55
1BP06T12	55
1BP06T16	55
1BP0808	54
1BP0810	54
1BP0812	54
1BP0816	54
1BP0820	54
1BP0824	54
1BP0832	54
1BP08T02	55
1BP08T04	55
1BP08T06	55
1BP08T08	55
1BP08T10	55
1BP08T12	55
1BP08T16	55
1BP08T20	55
1BP1010	54
1BP1012	54
1BP1016	54
1BP1020	54
1BP10T06	55
1BP10T08	55
1BP10T10	55
1BP10T12	55
1BP1212	54
1BP1216	54
1BP1220	54
1BP1224	54
1BP1232	54
1BP12T04	55
1BP12T06	55
1BP12T08	55
1BP12T12	55
1BP12T16	55
1BP12T20	55
1BP12T24	55
1BP1616	54
1BP1620	54
1BP1624	54
1BP1632	54
1BP1640	54
1BP16T06	55
1BP16T08	55
1BP16T12	55
1BP16T16	55
1BP16T20	55
1BP16T24	55
1BP16T32	55
1BP2020	54
1BP2024	54
1BP2032	54
1BP20T16	55
1BP20T20	55
1BP20T24	55
1BP20T32	55
1BP2424	54
1BP2428	54
1BP2432	54
1BP2440	54
1BP24T16	55
1BP24T20	55
1BP24T24	55
1BP24T32	55
1BP2828	54
1BP2832	54
1BP3232	54
1BP32T16	55
1BP32T20	55
1BP32T24	55
1BP32T32	55
1BP32T40	55

Code	Page
1BP32T48	55
1BP4040	54
1BP40T40	55
1BP4848	54
1BP6464	54
1BPA0202	54
1BPA0204	54
1BPA0404	54
1BPA0406	54
1BPA0408	54
1BPA0606	54
1BPA0608	54
1BPA0808	54
1BPA0812	54
1BPA0816	54
1BPA1212	54
1BPA1216	54
1BPA1616	54
1BPA1620	54
1BPA1624	54
1BPA2020	54
1BPA2024	54
1BPA2424	54
1BPA2432	54
1BPA3232	54
1BPR0404-1	54
1BPR0404-1/16	54
1BPR0404-1/32	54
1BPR0406-1	54
1BPR0406-1/16	54
1BPR0406-1/32	54
1BPR0408-1/16	54
1BPR0408-1/32	54
1BPR0606-1	54
1BPR0606-1/16	54
1BPR0606-1/32	54
1BPR0608-1	54
1BPR0608-1/32	54
1BPR0608-3	54
1BPR0612-1/16	54
1BPR0808-1	54
1BPR0808-1/16	54
1BPR0808-1/32	54
1BT0202	55
1BT0204	55
1BT0404	55
1BT0406	55
1BT0408	55
1BT0606	55
1BT0608	55
1BT0808	55
1BT0812	55
1BT1212	55
1BT1216	55
1BT1220	55
1BT1616	55
1BT1620	55
1BT1624	55
1BT2032	55
1BT2424	55
1BT2432	55
1BT3232	55
1BT4040	55
1BT4848	55
1BTJ0207	72
1BTJ0208	72
1BTJ0209	72
1BTJ0407	72
1BTJ0408	72
1BTJ0409	72
1BTJ0412	72
1BTJ0607	72
1BTJ0608	72
1BTJ0609	72
1BTJ0612	72
1BTJ0809	72
1BTJ0812	72
1BTJ0814	72
1BTJ0817	72
1BTJ1212	72
1BTJ1214	72
1BTJ1217	72
1BTJ1219	72
1BTJ1221	72
1BTJ1612	72
1BTJ1617	72
1BTJ1621	72
1BTJ1626	72
1BTJ2021	72
1BTJ2026	72
1BTJ2426	72
1BTJ2430	72
1BTJ3230	72
1BTJ3240	72
1G11CDE10R	232
1G11CDG09R	232
1G11CDJ23F	232
1G12CDE10R	232
1G12CDG09R	232
1G12CDJ23F	232
1G15CDE10R	232
1G15CDG09R	232
1G15CDJ23F	232
1G16CDE10R	232
1G16CDG09R	232
1G16CDJ23F	232
1G18CDE10R	232
1G18CDG09R	232
1G18CDJ23F	232
1G23CDE10R	232
1G23CDG09R	232
1G23CDJ23F	232
1G27CDE10R	232
1G27CDG09R	232
1G27CDJ23F	232
1G4CDG09R	232
1G4CDJ23F	232
1G6CDE10R	232
1G6CDG09R	232
1G6CDJ23F	232
1G8CDE10R	232
1G8CDG09R	232
1G8CDJ23F	232
1JP0505	72
1JP0507	72
1JP0707	72
1JP0709	72
1JP0807	72
1JP0808	72
1JP0809	72
1JP0812	72
1JP0814	72
1JP0909	72
1JP0914	72
1JP0917	72
1JP0919	72
1JP1207	72
1JP1209	72
1JP1212	72
1JP1214	72
1JP1414	72
1JP1417	72
1JP1421	72
1JP1717	72
1JP1721	72
1JP1919	72
1JP2121	72
1JP2126	72
1JP2130	72
1JP2626	72
1JP3030	72
1JP4040	72
1L01.5DE10R	232
1L010DE10R	232
1L03DE10R	232
1L05DE10R	232
1L07.5DE10R	232
1MBP1004	57
1MBP1202	57
1MBP1204	57
1MBP1206	57
1MBP1208	57
1MBP1402	57
1MBP1404	57
1MBP1406	57
1MBP1408	57
1MBP1410	57
1MBP1604	57
1MBP1606	57
1MBP1608	57
1MBP1610	57
1MBP1612	57
1MBP1804	57
1MBP1806	57
1MBP1808	57
1MBP1810	57
1MBP1812	57
1MBP1816	57
1MBP2004	57
1MBP2006	57
1MBP2008	57
1MBP2012	57
1MBP2204	57
1MBP2206	57
1MBP2208	57
1MBP2212	57
1MBP2216	57
1MBP2406	57
1MBP2408	57
1MBP2412	57
1MBP2608	57
1MBP2610	57
1MBP2612	57
1MBP2616	57
1MBP3012	57
1MBP3016	57
1MBP3020	57
1MBP3616	57
1MBP3816	57
1MBP3820	57
1MG11CDE10R	235
1MG12CDE10R	235
1MG15CDE10R	235
1MG16CDE10R	235
1MG18CDE10R	235
1MG23CDE10R	235
1MG27CDE10R	235
1MG4CDE10R	235
1MG6CDE10R	235
1MG8CDE10R	235
1ML01.5DE10R	235
1ML010DE10R	235
1ML03DE10R	235
1ML05DE10R	235
1ML07.5DE10R	235
1M-MS	1517
1M-MS-BOX	1517
1MP1010	56
1MP1012	56
1MP1014	56
1MP1212	56
1MP1214	56
1MP1216	56
1MP1414	56
1MP1416	56
1MP1418	56
1MP1420	56
1MP1616	56
1MP1618	56
1MP1620	56
1MP1622	56
1MP1626	56
1MP1818	56
1MP1820	56
1MP1822	56
1MP1824	56
1MP1826	56
1MP2020	56
1MP2022	56
1MP2024	56
1MP2026	56
1MP2222	56
1MP2224	56
1MP2226	56
1MP2230	56
1MP2424	56
1MP2626	56
1MP3030	56
1MP3038	56
1MP3838	56
1MPLA27DE10R	235
1MPLA36DE10R	235
1MPLA45DE10R	235
1MPLA54DE10R	235
1MPLA66DE10R	235
1MPLA84DE10R	235
1MPLC100DE10M	235
1MPLC100DJ23M	235
1MPLC125DE10M	235
1MPLC125DJ23M	235
1MPLC150DE10M	235
1MPLC150DJ23M	235
1MPLC175DE10M	235
1MPLC175DJ23M	235
1MPLC200DE10M	235
1MPLC200DJ23M	235
1MPLC225DE10M	235
1MPLC225DJ23M	235
1MPLC80DE10M	235
1MPLC80DJ23M	235
1-MS	1517
1-MS-BOX	1517
1M-SS	1517
1N0202	56
1N0204	56
1N0208	56
1N0404	56
1N0406	56
1N0408	56
1N0412	56
1N0606	56
1N0608	56
1N0808	56
1N0812	56
1N0816	56
1N0820	56
1N0824	56
1N1212	56
1N1216	56
1N1220	56
1N1616	56
1N1620	56
1N2020	56
1N2024	56
1N2032	56
1N4040	56
1NB0202	56
1NB0204	56
1NB0206	56
1NB0208	56
1NB0402	56
1NB0404	56
1NB0406	56
1NB0408	56
1NB0412	56
1NB0602	56
1NB0604	56
1NB0606	56
1NB0608	56
1NB0610	56
1NB0612	56
1NB0802	56
1NB0804	56
1NB0806	56
1NB0808	56
1NB0810	56
1NB0812	56
1NB0816	56
1NB1204	56
1NB1206	56

Code	Page
1NB1208	56
1NB1210	56
1NB1212	56
1NB1216	56
1NB1224	56
1NB1604	56
1NB1606	56
1NB1608	56
1NB1612	56
1NB1616	56
1NB1620	56
1NB2012	56
1NB2016	56
1NB2020	56
1NB2024	56
1NB2032	56
1NB2416	56
1NB2420	56
1NB2424	56
1NB2432	56
1NB3216	56
1NB3224	56
1NB3232	56
1NB3240	56
1NB4032	56
1NB4040	56
1NB4832	56
1NB4840	56
1NJ0207	72
1NJ0208	72
1NJ0209	72
1NJ0407	72
1NJ0408	72
1NJ0409	72
1NJ0412	72
1NJ0414	72
1NJ0607	72
1NJ0608	72
1NJ0609	72
1NJ0612	72
1NJ0614	72
1NJ0807	72
1NJ0809	72
1NJ0812	72
1NJ0814	72
1NJ0817	72
1NJ0821	72
1NJ1207	72
1NJ1209	72
1NJ1214	72
1NJ1217	72
1NJ1226	72
1NJ1612	72
1NJ1614	72
1NJ1621	72
1NJ1626	72
1NJ1630	72
1NJ2017	72
1NJ2021	72
1NJ2030	72
1NJ2040	72
1NJ2417	72
1NJ2421	72
1NJ2426	72
1NJ2430	72
1NJ2440	72
1NJ3226	72
1NJ3230	72
1NJ3240	72
1-ORING	108
1PLA27DE10R	233
1PLA27DG09R	233
1PLA27DJ23F	233
1PLA36DE10R	233
1PLA36DG09R	233
1PLA36DJ23F	233
1PLA45DE10R	233
1PLA45DG09R	233
1PLA45DJ23F	233
1PLA54DE10R	233
1PLA54DG09R	233
1PLA54DJ23F	233
1PLA66DE10R	233
1PLA66DG09R	233
1PLA66DJ23F	233
1PLA84DE10R	233
1PLA84DG09R	233
1PLA84DJ23F	233
1PLC100DE10M	233
1PLC100DJ23M	233
1PLC125DE10M	233
1PLC125DJ23M	233
1PLC150DE10M	233
1PLC150DJ23M	233
1PLC175DE10M	233
1PLC175DJ23M	233
1PLC200DE10M	233
1PLC200DJ23M	233
1PLC225DE10M	233
1PLC225DJ23M	233
1PLC80DE10M	233
1PLC80DJ23M	233
1PNC100DE10M	236
1PNC125DE10M	236
1PNC150DE10M	236
1PNC175DE10M	236
1PNC200DE10M	236
1PNC225DE10M	236
1PNC80DE10M	236
1PWLA-14N	1678
1PWLA-38B	1678
1PWLA-38N	1678
1PWLA-M-F-38N	1678
1SC-04-100	8
1SC-06-100	8
1SC-08-100	8
1SC-12-100	8
1-SS	1517
1X-MS	1517
1X-MS-BOX	1517
1X-SS	1517
1-Z06-22-11-600	269
1-Z06-23-11-600	269
1-Z06-24-11-600	269
1-Z06-28-11-600	269
1-Z06-29-11-600	269
1-Z06-30-11-600	269
1-Z06-39-30-600	269
1-Z06-40-30-600	269
1-Z06-43-00-600	269
1-Z06-44-00-600	269
1-Z08-00-10-600	269
1-Z08-02-10-600	269
1-Z08-03-10-600	269
1-Z08-04-10-600	269
1-Z08-05-10-600	269
1-Z08-06-10-600	269
1-Z08-07-10-600	269
1-Z10-68-00-600	269
1-Z10-69-00-600	269
1-Z10-70-00-600	269
1-Z10-72-00-600	269
1-Z10-73-00-600	269
1-Z80-48-60-040	269
2	
20000A4	1660
2000A-00	227
2001005	868
2001006	868
2001014	868
2001015	868
2001016	868
2001017	868
2001019	868
2002003	868
2002004	868
2003002	868
2003006	868
2003007	868
2004002	868
2004006	868
2004007	868
2005002	868
2005006	868
2005007	868
2006000	869
2006001	869
2006002	869
2006003	869
2006004	869
2006005	869
2006006	869
2006007	869
2006008	869
2006009	869
2006010	869
2006011	869
2006012	869
2006013	869
2006014	869
2006015	869
2006016	869
2006017	869
2006019	869
2006-1	947
2006-12	947
2006-14	947
2006-34	947
2006-38	947
2006FW-1	949
2006FW-112	949
2006FW-114	949
2006FW-12	949
2006FW-12W	947
2006FW-14	949
2006FW-14W	947
2006FW-2	949
2006FW-212	949
2006FW-3	949
2006FW-34	949
2006FW-38	949
2006FW-38W	947
2006S-1	947
2006S-112	947
2006S-112N	947
2006S-114	947
2006S-114N	947
2006S-12	947
2006S-12N	947
2006S-14	947
2006S-14N	947
2006S-1N	947
2006S-2	947
2006S-2N	947
2006S-34	947
2006S-34N	947
2006S-38	947
2006S-38N	947
2006SD-1	950
2006SD-112	950
2006SD-114	950
2006SD-12	950
2006SD-14	950
2006SD-2	950
2006SD-34	950
2006SD-38	950
2007001	869
2007002	869
2007003	869
2007005	869
2007006	869
2007007	869
2008001	869
2008003	869
2008005	869
2008009	869
2008010	869
2008011	869
2008014	869
2008015	869
2008017	869
2008018	869
200R	1538
2010002	821
2010007	821
20101/AL-100UM	1629
20101/C1-100	1631
20101/C4-44	1631
20101/PE-100UM	1629
20101/PL-100UM	1629
20101AL4-44UM	1629
20101CAL-15UM	1629
20101CC5	1631
20101CPE-15UM	1629
20101CPL-15UM	1629
20101PL4-44UM	1629
20103/AL-100UM	1629
20103/PE-100UM	1629
20103/PL-100UM	1629
20103AL4-44UM	1629
20103CAL-15UM	1629
20103CPE-15UM	1629
20103CPL-15UM	1629
20103PL4-44UM	1629
2011002	868
2011006	868
2011007	868
2011FW-1	949
2011FW-112	949
2011FW-114	949
2011FW-12	949
2011FW-14	949
2011FW-2	949
2011FW-212	949
2011FW-3	949
2011FW-34	949
2011FW-38	949
2011FW-4	949
2011KMD-1	953
2011KMD-112	953
2011KMD-112C	955
2011KMD-114	953
2011KMD-114C	955
2011KMD-12	953
2011KMD-12C	955
2011KMD-1C	955
2011KMD-2	953
2011KMD-2C	955
2011KMD-34	953
2011KMD-34C	955
2011ND-1	950
2011ND-112	950
2011ND-114	950
2011ND-12	950
2011ND-2	950
2011ND-212	950
2011ND-3	950
2011ND-34	950
2011ND-4	950
2012CD-1	952
2012CD-112	952
2012CD-12	952
2012CD-2	952
2012CD-212	952
2012CD-3	952
2012CD-34	952
2012CD-4	952
2012FW-1	949
2012FW-112	949
2012FW-114	949
2012FW-12	949
2012FW-14	949
2012FW-2	949
2012FW-212	949
2012FW-3	949
2012FW-34	949
2012FW-38	949
2012FW-4	949
2012KMD-1	953
2012KMD-112	953

Code	Page
2012KMD-112C	955
2012KMD-12	953
2012KMD-12C	955
2012KMD-1C	955
2012KMD-2	953
2012KMD-2C	955
2012KMD-34	953
2012KMD-34C	955
2012ND-1	950
2012ND-112	950
2012ND-114	950
2012ND-12	950
2012ND-2	950
2012ND-212	950
2012ND-3	950
2012ND-34	950
2012ND-4	950
2013CD-1	952
2013CD-112	952
2013CD-12	952
2013CD-2	952
2013CD-212	952
2013CD-3	952
2013CD-34	952
2013CD-4	952
2013FW-1	949
2013FW-112	949
2013FW-112N	949
2013FW-114	949
2013FW-114N	949
2013FW-12	949
2013FW-12N	949
2013FW-14	949
2013FW-14N	949
2013FW-1N	949
2013FW-2	949
2013FW-212	949
2013FW-212N	949
2013FW-2N	949
2013FW-3	949
2013FW-34	949
2013FW-34N	949
2013FW-38	949
2013FW-38N	949
2013FW-3N	949
2013FW-4	949
2013FW-4N	949
2013KMD-1	953
2013KMD-112	953
2013KMD-112C	955
2013KMD-112CN	955
2013KMD-112N	953
2013KMD-114	953
2013KMD-114C	955
2013KMD-114CN	955
2013KMD-114N	953
2013KMD-12	953
2013KMD-12C	955
2013KMD-12CN	955
2013KMD-12N	953
2013KMD-1C	955
2013KMD-1CN	955
2013KMD-1N	953
2013KMD-2	953
2013KMD-212	953
2013KMD-212C	955
2013KMD-2C	955
2013KMD-2CN	955
2013KMD-2N	953
2013KMD-3	953
2013KMD-34	953
2013KMD-34C	955
2013KMD-34CN	955
2013KMD-34N	953
2013KMD-3C	955
2013KMD-3CN	955
2013KMD-3N	953
2013ND-1	950
2013ND-112	950
2013ND-112N	950
2013ND-114	950
2013ND-114N	950
2013ND-12	950
2013ND-12N	950
2013ND-14	950
2013ND-1N	950
2013ND-2	950
2013ND-212	950
2013ND-2N	950
2013ND-3	950
2013ND-34	950
2013ND-34N	950
2013ND-38	950
2013ND-4	950
2014GB 09	971
2014GB 10	971
2014GB 11	971
2014GB 12	971
2014GB 13	971
2014GB 14	971
2014GB 16	971
2014GB 18	971
2014GB 20	971
2014GB 22	971
2014LB 08Y	970
2014LB 09Y	970
2014LB 10Y	970
2014LB 11Y	970
2014LB 12Y	970
2014LB 13Y	970
2014LB 14Y	970
2014LB 16Y	970
2014LB 18Y	970
2014LB 20G	970
2014LB 22G	970
2014LB 24G	970
2014LB 26G	970
2014LB 28G	970
2014LB 30G	970
2014LD 09	970
2014LD 10	970
2014LD 11	970
2014LD 12	970
2014LD 13	970
2014LD 14	970
2014LD 16	970
2014LD 18	970
2014LH 08	970
2014LH 09	970
2014LH 10	970
2014LH 11	970
2014LH 12	970
2014LH 13	970
2014LI 08	970
2014LI 09	970
2014LI 10	970
2014LI 11	970
2014LI 12	970
2014LI 13	970
2014LI 14	970
2014LI 16	970
2014LSB 08	971
2014LSB 09	971
2014LSB 10	971
2014LSB 11	971
2014LSB 12	971
2014LSB 13	971
2014LSB 14	971
2014LSB 16	971
2014LSB 18	971
2014LV 08	970
2014LV 09	970
2014LV 10	970
2014LV 11	970
2014LV 12	970
2014LV 13	970
2014LV 14	970
2014LV 16	970
2014LW 08	970
2014LW 09	970
2014LW 10	970
2014LW 11	970
2014LW 12	970
2014LW 13	970
2014LW 14	970
2014LW 16	970
2014LW 16G	970
2014LW 18	970
2014LW 18G	970
2014LW 20G	970
2014LW 22G	970
2014LW 24G	970
2014LW 26G	970
2014LW 28G	970
2014LW 30G	970
2014WB 08	968
2014WB 09	968
2014WB 10	968
2014WB 11	968
2014WB 12	968
2014WB 13	968
2014WB 14	968
2014WB 16	968
2014WB 18	968
2014WB 20G	968
2014WB 22G	968
2014WB 24G	968
2014WB 26G	968
2014WB 28G	968
2014WB 30G	968
2014WC 09	969
2014WC 10	969
2014WC 11	969
2014WC 12	969
2014WC 13	969
2014WC 14	969
2014WC 16	969
2014WC 18	969
2014WD 09	969
2014WD 10	969
2014WD 11	969
2014WD 12	969
2014WD 13	969
2014WD 14	969
2014WD 16	969
2014WD 18	969
2014WG 09	968
2014WG 10	968
2014WG 11	968
2014WG 12	968
2014WG 13	968
2014WG 14	968
2014WG 16	968
2014WG 18	968
2014WH 08	968
2014WH 09	968
2014WH 10	968
2014WH 11	968
2014WH 12	968
2014WH 13	968
2014WH 14G	968
2014WH 16G	968
2014WH 18G	968
2014WH 20G	968
2014WI 08	969
2014WI 09	969
2014WI 10	969
2014WI 11	969
2014WI 12	969
2014WI 13	969
2014WI 14	969
2014WI 16	969
2014WI 18G	969
2014WI 20G	969
2014WP 09	969
2014WP 10	969
2014WP 11	969
2014WP 12	969
2014WP 13	969
2014WP 14G	969
2014WP 16G	969
2014WP 18G	969
2014WP 20G	969
2014WS 08	969
2014WS 09	969
2014WS 10	969
2014WS 11	969
2014WS 12	969
2014WS 13	969
2014WS 14	969
2014WS 16	969
2014WS 18	969
2014WS 20G	969
2014WT 08	969
2014WT 09	969
2014WT 10	969
2014WT 11	969
2014WT 12	969
2014WT 13	969
2014WT 14	969
2014WT 16	969
2014WT 18	969
2014WU 09	969
2014WU 10	969
2014WU 11	969
2014WU 12	969
2014WU 13	969
2014WU 14G	969
2014WU 16G	969
2014WU 18G	969
2014WU 20G	969
2014WW 08	968
2014WW 09	968
2014WW 10	968
2014WW 11	968
2014WW 12	968
2014WW 13	968
2014WW 14	968
2014WW 16	968
2014WW 18	968
2014WW 18G	968
2014WW 20G	968
2014WW 22G	968
2014WW 24G	968
2014WW 26G	968
2014WW 28G	968
2014WW 30G	968
20151/AL-100UM	1629
20151/C1-100	1631
20151/PE-100UM	1629
20151/PL-100UM	1629
20153/PE-100UM	1629
2017001	822
2017-0460	1720
2017-3506	1639
2017-3514	1639
2017-3555	1639
2017-3621	1644
2017-3639	1644
2017-3647	1644
2017-3654	1639
2017-3662	1639
2017-3670	1639
2017-3688	1639
2017-3696	1644
2017-3712	1644
2017-3720	1639
2017-3738	1644
2017-3746	1644
2017-3787	1644
2017-3795	1644
2017-3811	1644
2017-3829	1644
2017-3845	1644
2017-3860	1644
2017-3878	1644
2017-3886	1644
2017-3894	1644
2017-6335	1590
2017-6418	1590

Code	Page
2017-6434	1590
2017-6442	1590
2017-6467	1590
2017-6475	1590
2017-6483	1590
2017-6491	1590
2017-6780	1639
2017FW-1	949
2017FW-112	949
2017FW-114	949
2017FW-12	949
2017FW-14	949
2017FW-2	949
2017FW-34	949
2017FW-38	949
2018-1681	410
2018-1699	410
2018-1707	410
2018-1723	410
2018-1731	410
2018-1749	410
2018-1756	410
2018-1764	410
2018-1772	410
2018-1780	410
2018-1798	410
2018-1806	410
2018-1814	410
2018-1822	410
2018-1830	411
2018-1848	411
2018-1913	440
2018-1947	440
2018-1970	440
2018-2473	1165
2018-2481	1165
2018-2499	1165
2018-2515	1165
2018-2523	1165
2018-2531	1165
2018-2549	1165
2018-2556	1165
2018-2564	1165
2018-2572	1165
2018-2580	1165
2018-2598	1165
2018-2606	1165
2018-2614	1165
2018-2622	1165
2018-2838	440
2018-2853	440
2018-2887	440
2018-2903	440
2018-2911	440
2018-2929	440
2018-2937	440
2018-2938	440
2018-3001	1211
2018-3002	1211
2018-3003	1211
2018-3004	1211
2018-3005	1211
2018-3009	1211
2018-3022	1211
2018-3023	1211
2018-3024	1211
2018-3025	1211
2018-3026	1211
2018-3029	1211
2018-3031	1211
2018-3041	1211
2018-3042	1211
2018-3044	1211
2018-5336	1211
2018-5344	1211
2018-5351	1211
2018-5369	1211
2018-5377	1211
2018-5385	1211
2018-5393	1211
2018-5401	1211
2018-5419	1211
2018-5435	1211
2018-5436	1211
2018-5468	1211
2018-5476	1211
2018-5484	1211
2018-5492	1211
2018-5500	1211
2018-5518	1211
2018-5526	1211
2018-5534	1211
2018-5542	1211
2018-5559	1211
2018-5567	1211
2018-5575	1211
2018-5583	1211
2018-5591	1211
2018-5609	1211
2018-5617	1211
2018-5625	1211
2018-5626	1211
2018-5666	1211
2018-5674	1211
2018-5682	1211
2018-5690	1211
2018-5708	1211
2018-5716	1211
2018-5724	1211
2018-5732	1211
2018-5740	1211
2018-5757	1211
2018-5765	1211
2018-5766	1211
2018-5767	1211
2018-5773	1211
2018-5880	1211
2018-5914	1211
2018-5915	1211
2018-5916	1211
2018-5922	1211
2018-5930	1211
2018-5948	1211
2018-5951	1211
2018-5971	1211
2018-5989	1211
2018-5997	1211
2018-6003	1211
2018-6045	1211
2018-6060	1211
2018-6094	1211
2018-6128	1211
2018-6151	1211
2018-6169	1211
2018-6177	1211
2018-6185	1211
2018-6193	1211
2018-6201	1211
2018-6243	1211
2018-6250	1211
2018-6268	1211
2018-6276	1211
2018-6284	1211
2018-6292	1211
2018-6296	1211
2018-6938	983
2018-6946	983
2018-6953	983
2018-MM05	1165
2018-MM08	1165
2018-MM10	1165
2018-MM12	1165
2018-MM14	1165
2018-MM16	1165
2018-MM18	1165
2018-MM20	1165
2018-MM22	1165
2019001	821
2019-0010	768
2019-0011	768
2019-0012	768
2019-0013	768
2019-0014	768
2019-0015	768
2019-0016	768
2019-0017	768
2019-0018	768
2019-0019	768
2019002	821
2019-0020	768
2019-0021	768
2019-0022	768
2019-0023	768
2019-0024	768
2019-0025	768
2019-0026	768
2019-0027	768
2019-0028	768
2019-0029	768
2019003	821
2019-0030	768
2019-0031	768
2019-0032	768
2019004	821
2019005	821
2019006	821
2019-0210	769
2019-0211	769
2019-0220	772
2019-0226	772
2019-1080	1536
2019-1084	1536
2019-1093	1536
2019-1094	1536
2019-1096	1536
2019-1098	1536
2019-2639	245
2019-3629	245
2019-3637	245
2019-3645	245
2019-3652	245
2019-3653	245
2019-3654	245
2019-3655	245
2019-3660	245
2019-3678	245
2019-3686	245
2019-3694	245
2019-3702	245
2019-3703	245
2019-3704	245
2019-3705	245
2019-4890	768
2019-4932	768
2019-4940	768
2019-4957	768
2019-4965	768
2019-4973	768
2019-4981	768
2019-4999	768
2019-5004	768
2019-5012	768
2019-5020	768
2019-5038	768
2019-5046	768
2019-5053	768
2019-5061	768
2019-5076	768
2019-5087	768
2019-5095	768
2019-5096	768
2019-5097	768
2019-5103	769
2019-5111	769
2019-5129	769
2019-5145	769
2019-5152	769
2019-5160	769
2019-5178	769
2019-5186	769
2019-5194	769
2019-5202	769
2019-5210	769
2019-5228	769
2019-5236	769
2019-5244	769
2019-5251	769
2019-5269	769
2019-5277	769
2019-5278	769
2019-5279	769
2019-5293	770
2019-5301	770
2019-5335	770
2019-5541	770
2019-5749	770
2019-5764	770
2019-5772	770
2019-5780	770
2019-5798	770
2019-5806	770
2019-5814	770
2019-5822	769
2019-5830	770
2019-5848	770
2019-5855	770
2019-5863	770
2019-5871	770
2019-5889	770
2019-5897	770
2019-5905	769
2019-5913	769
2019-5939	769
2019-5947	769
2019-5954	769
2019-5970	769
2019-5988	769
2019-6135	769
2019-6150	769
2019-6192	769
2019-6200	769
2019-6325	768
2019-6366	768
2019-6416	768
2019-6432	768
2019-6440	768
2019-6465	768
2019-6721	768
2019-6739	768
2019-6754	768
2019-6911	768
2019-6929	768
2019-7018	768
2019-7059	768
2019-7083	768
2019-7125	768
2019-7133	768
2019-7166	768
2019-7182	768
2019-7299	768
2019-7307	768
2019-7315	768
2019-7497	768
2019-7513	770
2019-7547	770
2019-7554	770
2019-7570	770
2019-7596	770
2019-7604	770
2019-7612	770
2019-7620	770
2019-7638	770
2019-7646	770
2019-7653	770
2019-7950	770
2019-7968	770
2019-7976	770
2019-7984	770
2019-7992	770
2019-8008	770

Code	Page
2019-8010	770
2019-8012	770
2019-8032	770
2019-8040	770
2019-8057	770
2019-8065	770
2019-8073	770
2019-8081	770
2019-8089	770
2019-8107	770
2019-8115	770
2019-8123	770
2019-8156	770
2019-8164	770
2019-8172	772
2019-8180	772
2019-8198	772
2019-8206	772
2019-8214	772
2019-8222	772
2019-8230	772
2019-8248	772
2019-8255	772
2019-8263	772
2019-8271	772
2019-8289	772
2019-8297	771
2019-8305	771
2019-8313	771
2019-8321	771
2019-8339	771
2019-8340	771
2019-8347	771
2019-8354	771
2019-8362	771
2019-8370	771
2019-8388	771
2019-8392	771
2019-8396	771
2019-8404	771
2019-8412	771
2019-8420	771
2019-8438	771
2019-8439	771
2019-8446	771
2019-8453	771
2019-8461	771
2019-8479	771
2019-8487	771
2019-8495	771
2019-8503	771
2019-8511	771
2019-8529	771
2019-8537	771
2019-8545	771
2019-8552	771
2019-8560	771
2019-8578	771
2019-8579	771
2019-8974	771
2019-8982	771
2019-8990	771
2019-9006	771
2019-9014	771
2019-9022	773
2019-9035	773
2019-9048	773
2019-9055	773
2019-9063	773
2019-9071	773
2019-9089	773
2019-9097	773
2019-9139	771
2019-9162	771
2019-9170	771
2019-9188	771
2019-9295	1620
2019-9303	1620
2019-9311	1620
2019-9337	1625
2019-9360	1625
2019-9386	1632
2019-9394	1623
2019D 04	954
2019D 04C	955
2019D 05	954
2019D 05C	955
2019D 06	954
2019D 06C	955
2019D 07	954
2019D 08	954
2019D 08C	955
2019D 09	954
2019D 09C	955
2019D 10	954
2019D 10C	955
2019D 11	954
2019D 11C	955
2019D 12	954
2019D 12C	955
2019D 13	954
2019D 14	954
2019D 14C	955
2019D 16	954
2019D4 10	954
2019D4 11	954
2019D4 12	954
2019S 04	953
2019S 05	953
2019S 06	953
2019S 07	953
2019S 08	953
2019S 09	953
2019S 10	953
2019S 11	953
2019S 12	953
2019S 14	953
201M10U916	100
201M12U34	100
201M16U78	100
201M20U1116	100
201M22U1316	100
201M25U1516	100
201M32U158	100
201M38U178	100
201M6U716	100
201M8U12	100
2020-0333	283
2020-0340	267
2020-0341	267
2020-0342	267
2020-0343	267
2020-0344	267
2020-0424	937
2020-0432	937
2020-0440	937
2020-0457	937
2020-0465	937
2020-0473	937
2020-0481	960
2020-0499	960
2020-0507	960
2020-0515	960
2020-0523	960
2020-0531	960
20201/AL-100UM	1629
20201/C1-100	1631
20201/C4-44	1631
20201/PL-100UM	1629
2020-1372	183
2020-1372-6M	183
2020-1380	183
2020-1380-6M	183
2020-1406	183
2020-1406-6M	183
2020-1414	183
2020-1414-6M	183
2020-1422	183
2020-1422-6M	183
2020-1430	183
2020-1430-6M	183
2020-1901	1144
2020-1919	1144
2020-1927	1144
2020-1935	1144
2020-1940	1144
2020-1943	1144
2020-1950	1144
2020-1968	1144
2020-1976	1144
20201AL4-44UM	1629
20201CAL-15UM	1629
20201CC5-15	1631
20201CPL-15UM	1629
20201PL4-44UM	1629
20202/AL-100UM	1629
20202/PL-100UM	1629
2020-2982	1673
2020-2990	1673
20202AL4-44UM	1629
20202CAL-15UM	1629
20202CPL-15UM	1629
20202PL4-44UM	1629
2020-3014	1673
2020-3089	1673
2020-3105	1673
2020-3113	1673
2020-3139	1673
2020-3147	1673
2020-3154	1673
2020-3162	1673
2020-3188	1673
2020-3204	1673
2020-6009	1710
2020-6025	434
2020-8294	1414
2020-8369	1414
2020-8377	1414
2020-8385	1414
2020-8860	985
2020-8864	985
2020-8872	985
2020-8880	985
2020-8898	985
2020-8906	985
2020-8914	985
2020-8922	985
2020-8930	985
2020-8948	985
2020-8955	985
2020-8971	985
2020-8989	985
2020-8997	985
2020-9003	985
2020-9011	985
2020-9029	985
2020-9045	985
2020-9052	985
2020-9060	985
2020-9086	985
2020-9094	985
2020-9102	985
2020-9110	985
2020-9128	985
2020-9136	985
2020-9144	985
2020-9151	985
2020-9169	985
2020-9177	985
2020-9193	985
2020-9201	985
2020-9219	985
2020-9276	1416
2020-9284	1416
2020-9292	1416
2020-9300	1416
2020-9318	1416
2020-9326	1416
2020-9334	1416
2020-9359	1416
2020D 04	954
2020D 04C	955
2020D 05	954
2020D 05C	955
2020D 06	954
2020D 06C	955
2020D 07	954
2020D 08	954
2020D 08C	955
2020D 09	954
2020D 09C	955
2020D 10	954
2020D 10C	955
2020D 11	954
2020D 11C	955
2020D 12	954
2020D 12C	955
2020D 14	954
2020D 14C	955
2020S 04	953
2020S 05	953
2020S 06	953
2020S 08	953
2020S 09	953
2020S 10	953
2020S 11	953
2020S 12	953
2020S 14	953
2021002	821
2021005	821
2021006	821
2021-0209	1720
2021-0217	1720
2021-0225	1720
20211/PL-100UM	1629
2021-1330	436
2021-1348	436
2021-1355	436
20211CPL-15UM	1629
20212/PL-100UM	1629
2021-2030	1720
20212CPL-15UM	1629
20212PL4-44UM	1629
2021-5224	903
2021-5232	903
2021-5240	903
2021-5257	903
2021-5265	903
2021-5273	903
2021-5281	903
2021-5299	903
2021-7303	1042
2021-7329	1042
2021-8061	1673
2022002	821
2022005	821
2022006	821
2022-9720	773
2022-9746	773
2022-9753	773
2022-9761	773
2022-9779	773
2022-9829	773
2022-9837	773
2022-9845	773
2022-9852	773
2022-9860	773
2022-9878	773
2022-9886	773
2022-9894	773
2022-9902	773
2022-9910	773
2022-9928	773
2022-9936	773
2022-9944	773
2022-9951	773
2022-9969	773
2022-9977	773
2023001	821
2023002	821

Code	Page
2023003	821
2023004	821
2023-0439	922
2023-0447	922
2023-0454	922
2023-0462	922
2023-0470	922
2023-0488	922
2023-0496	922
2023-0504	922
2023-0512	922
2023-0520	922
2023-0538	922
2023-0637	773
20231/PL-100UM	1630
20231AL4-44UM	1630
20231CAL-15UM	1630
20231CPL-15UM	1630
20231PL4-44UM	1630
20232/AL-100UM	1630
20232AL4-44UM	1630
20232CAL-15UM	1630
20232CPL-15UM	1630
20232PL4-44UM	1630
2023-9901-3MTR	1126
2023R	1538
2024001	822
2024003	822
2024-1808	922
2024-1816	922
2024-1824	922
2024-1832	922
2024-1840	922
2024-1857	922
2024-1865	922
2024-1873	922
2024-1915	923
2024-1923	923
2024-1949	923
2024-1964	923
2024-1980	923
2024-2079	923
2024-2087	923
2024-2095	923
2024-2103	923
2024-2111	923
2024-2566	772
2024-2574	772
2024-2582	772
2024-2590	772
2024-2608	772
2024-2616	772
2024-2624	772
2024-2632	772
2024-2640	772
2024-2657	772
2024-2673	772
2024-2699	772
2024-2731	772
2024-8746	41
2024-8761	41
2024-8779	41
2024-8787	41
2024-8795	41
2024-8803	41
2024-8811	41
2024-8829	41
2024-8837	41
2024-8845	41
2024-8852	41
2024-8860	41
2024-8878	41
2024-8886	41
2024-8894	41
2024-8902	41
2024-8910	41
2024-8928	41
2024-8944	41
2024-8951	41
2024-8969	41
2024-8993	41
2024-9009	41
2024-9017	41
2024-9025	41
2024-9033	41
2024-9041	41
2024SL150 06	963
2024SL150 08	963
2024SL150 09	963
2024SL150 11	963
2024SL150 12	963
2024SL150 14	963
2024SL16 06	963
2024SL16 08	963
2024SL16 09	963
2024SL16 10	963
2024SL16 11	963
2024SL16 12	963
2024SL16 14	963
20250/PL-100UM	1629
20250ALAL4-44UM	1629
20250CAL-15UM	1629
20250CPL-15UM	1629
20250PL4-44UM	1629
2025-1401	86
2025-1419	86
2025-1427	86
2025-1435	86
2025-1443	86
2025-1450	86
2025-1468	86
2025-1476	86
2025-1484	86
2025-1495	86
2025-1505	86
2025-1520	86
2025-1526	86
2025-1534	86
2025-1538	86
2025-1559	86
2025-1567	86
2025-1572	86
2025-1583	86
2025-1591	86
2025-1595	86
2025-1600	86
2025-1609	86
2025-1611	86
2025-1615	86
2025-1617	86
2025-1620	86
2025-1625	86
2025-1633	86
2025-1636	86
2025-1639	86
2025-1641	86
2025-1643	86
2025-1656	86
2025-1658	86
2025-1661	86
2025-1671	86
2025-1674	86
2025-1677	86
2025-1679	86
2025-1681	86
2025-1682	86
2025-1684	86
2025-1687	86
2025-1690	86
2025-1700	86
2025-1708	86
2025-1710	86
2025-1715	86
2025-1720	86
2025-1724	86
2025-1727	86
2025-1732	86
2025-1740	86
2025-1845	86
2025-1852	86
2025-1856	86
2025-1865	86
2025-1881	86
2025-1885	86
2025-1889	86
2025-1894	86
2025-1898	86
2025-1905	86
2025-1910	86
2025-1915	86
2025-1920	86
2025-1925	86
2025-1930	86
2025-1931	86
2025-1935	86
2025-1940	86
2025-1945	86
2025-1948	86
2025-1950	86
2025-1955	86
2025-1956	86
2025-1960	86
2025-1961	86
2025-1963	86
2025-1965	86
2025-1971	86
2025-1989	86
2025-1997	86
2025-2003	86
2025-2020	86
2025-2029	86
2025-2037	86
2025-2043	86
2025-2060	86
2025-2078	87
2025-2082	87
2025-2086	87
2025-2089	87
2025-2093	87
2025-2094	87
2025-2100	87
2025-2110	87
2025-2122	87
2025-2128	87
2025-2132	87
2025-2136	87
2025-2151	87
2025-2169	87
2025-2185	87
2025-2193	87
2025-2201	87
2025-2219	87
2025-2223	87
2025-2227	87
2025-2232	87
2025-2240	87
2025-2245	87
2025-2250	87
2025-2258	87
2025-2263	87
2025-2273	87
2025-2283	87
2025-2293	87
2025-2321	87
2025-2326	87
2025-2334	87
2025-2342	87
2025-2354	87
2025-2391	87
2025-2409	87
2025-2417	87
2025-2425	87
2025-2433	87
2025-2441	87
2025-2445	87
2025-2449	87
2025-2450	87
2025-2466	87
2025-2474	87
2025-2482	87
2025-2490	87
2025-2508	87
2025-2516	87
2025-2524	87
2025-2532	87
2025-2540	87
2025-2557	87
2025-2565	87
2025-2573	87
2025-2582	87
2025-2592	87
2025-2602	87
2025-2763	900
2025-3720	1552
2025-3738	1552
2025-3746	1552
2025-3753	1517
2025-4001	87
2025-4011	87
2025-4021	87
2025-4031	87
2025-4041	87
2025-4051	87
2025-4501	87
2025-4511	87
2025-4521	87
2025-4531	87
2025-4541	87
2025-4551	87
2025-8121	86
2025-8131	86
2025-8142	86
2025-8151	86
2025-8161	86
2025-8171	86
2025-8181	86
2025-8191	86
2025-8201	86
2025-8211	86
2025-8221	86
2025-8231	86
2025-8241	86
2025-8251	86
2025-8261	86
2025-8271	86
2025-8281	86
2025-8291	86
2025-8301	86
2025-8311	86
2025-8321	86
2025-8331	86
2025-8341	86
2025-8351	86
2025-8361	86
2026 04	961
2026 05	961
2026 06	961
2026 07	961
2026 08	961
2026 09	961
2026 10	961
2026 11	961
2026 12	961
2026C-1	961
2026C-112	961
2026C-114	961
2026C-12	961
2026C-2	961
2026C-212	961
2026C-3	961
2026C-34	961
2026C-4	961
2027-3967	900
2027-3975	900
2027-4007	900
2027-4015	900
2027-4023	900
2027-4049	900
2027-4056	900
2027-4064	900

Code	Page
2027-4072	900
2027-5384	1042
2027-5392	1042
2027-5400	1042
2027-5418	1042
2028-1	975
2028-112	975
2028-114	975
2028-12	975
2028-2	975
2028-34	975
2028-5078	41
2028-5086	41
2028-5094	41
2028-5102	41
2028-5110	41
2028-5128	41
2028-5839	1185
2028-5854	1185
2028-5862	1185
2028-5870	1185
2028-5953	1185
2028-5961	1185
2028-5979	1185
2028-5987	1185
2028-5995	1185
2028-7736	768
2028-7793	768
2028-7819	768
2028-7843	768
2028-7868	768
2028-7876	768
2028-7884	768
2028-7900	768
2028-7918	768
2028-7926	768
2028-7934	768
2028-7942	768
2028-7959	768
2028-7967	768
2028-7975	768
2028-7983	768
2028-7986	768
2028-7987	768
2028-8007	770
2028-8023	770
2028-8031	770
2028-8049	770
2028-8056	770
2028-8064	770
2028-8072	770
2028-8122	770
2028-8130	770
2028-8148	770
2028-8155	770
2028-8163	770
2028-8189	770
2028-8205	770
2028-8213	770
2028-8221	769
2028-8239	769
2028-8247	769
2028-8254	769
2028-8262	769
2028-8270	769
2028-8288	769
2028-8296	769
2028-8304	769
2028-8312	769
2028-8320	769
2028-8338	769
2028-8379	769
2028-8403	769
2028-8411	769
2028-8429	769
2028-8437	772
2028-8445	772
2028-8452	772
2028-8460	772
2028-8478	772
2028-8486	772
2028-8494	772
2028-8502	772
2028-8510	772
2028-8528	772
2028-8536	772
2028-8544	772
2028-8551	772
2028-8569	772
2028-8577	772
2028-8585	772
2028-8593	772
2028-8601	772
2028-8619	772
2028-8627	772
2028-8635	772
2028-8643	772
2028-8668	772
2028-8684	772
2029-1	957
2029-112	957
2029-114	957
2029-12	957
2029-14	957
2029-2	957
2029-34	957
2029-38	957
20300A9	1660
2030-1	961
20301/10-100UM	1630
20301/20-200UM	1630
20301/30-300UM	1630
20301/C1-100	1631
20301/C2-200	1631
20301/C3-300	1631
2030-112	961
2030-114	961
2030-12	961
2030-2	961
2030-212	961
2030-3	961
2030-34	961
20304/10-100UM	1630
20304/20-200UM	1630
20306/10-100UM	1630
20306/20-200UM	1630
20306/30-300UM	1630
2031004	869
2031005	869
2031006	869
2031016	869
2031017	869
2031018	869
2031019	869
2031-7020	985
2031C15	869
2031C16	869
2032005	869
2032017	869
2032018	869
2032019	869
2033-4002	87
2033-4012	87
2033-4022	87
2033-4032	87
2033-4042	87
2033-4052	87
2033-4062	87
2033-4072	87
2033-4082	87
2033-4092	87
2033-5279	1635
2033-8301	87
2033-8311	87
2033-8321	87
2033-8331	87
2033-8341	87
2033-8351	87
2033-8505	772
2033-8513	772
2033-8521	772
2033-8539	772
2033-8547	772
2033-8570	770
2033-8588	770
2033-8612	770
2033-8729	769
2033-8737	769
2033-8745	769
2033-8752	769
2033-8778	769
2033-8786	769
2033-9107	769
2033-9115	769
2033-9131	769
2033-9149	769
2033-9156	769
2033-9180	769
2033-9693	86
2033-9719	86
2033-9727	86
2033-9735	86
2033-9761	86
2033-9862	86
2033-9867	86
2033-9875	86
2033-9883	86
2033-9891	86
2033-9896	86
2033-9922	87
2033-9933	87
2033-9941	87
2033-9958	87
2033-9962	87
2033-9963	87
2033-9974	87
2033-9982	87
2033-9992	87
2034-8942	1384
2034-8959	1384
2034-9007	1384
2034-9015	1384
2034-9098	1384
2034-9122	1384
2034-9148	1384
2034-9155	1384
2034-9163	1384
2034-9171	1384
2034-9189	1384
2034-9197	1384
2034-9205	1384
2034-9221	1384
2034-9239	1384
2034-9254	1384
2034-9262	1384
2034-9270	1384
2034-9288	1384
2034-9296	1384
2034-9312	1384
2034-9320	1384
2034-9361	1384
2035-0773	985
20351/03	1631
20351/10-100UM	1630
20351/20-200UM	1630
20351/30-300UM	1630
2035-3637	1416
2035-3645	1416
20354/10-100UM	1630
20354/30-300UM	1630
20356/20-200UM	1630
20356/30-300UM	1630
2036-7330	41
2036-7355	41
2036-7405	41
2036-7413	41
2036-7439	41
2036-7447	41
2036-7454	41
2036-7504	41
2036-7520	41
2036-7538	41
2036-7579	41
2038-8435	267
2038-8443	267
2038-8450	267
2038-8476	267
2038-8484	412
2038-8492	412
2038-8526	412
2038-8534	267
2038-8567	267
2038-8575	267
2039-9119	440
2039-9184	440
2039-9200	440
2039-9218	440
2039-9432	440
203M10	100
203M12	100
203M14	100
203M15	100
203M15Z58	100
203M16Z58	100
203M18	100
203M20	100
203M25	100
203M30	100
203M32	100
203M38Z112	100
203M6	100
203M8	100
203Z1	100
203Z12	100
203Z14	100
203Z34	100
203Z38	100
203Z516	100
2040-1	951
20401/10-100UM	1630
20401/30-300UM	1630
20401/C1-100	1631
20401/C3-300	1631
2040-112	951
2040-114	951
2040-12	951
2040-14	951
2040-1626	440
2040-1634	440
2040-2	951
20402/10-100UM	1630
20402/20-200UM	1630
2040-212	951
20403/10-100UM	1630
20403/20-200UM	1630
20403/30-300UM	1630
2040-34	951
2040-38	951
2041-1	951
2041-112	951
2041-114	951
2041-12	951
2041-14	951
2041-2	951
2041-212	951
2041-34	951
2041-38	951
2042-2887	985
2042-2895	985
2042-2903	985
2042-2911	985
2042-2929	985
2042-2937	985
2042-2945	985
2042-2952	985
2042-2960	985
2042-2978	985
2042-2986	985
2042-2994	985
2042-3000	985

Code	Page
2042-3018	**985**
2042-3026	**985**
2042-3034	**985**
2042-3042	**985**
2042-3059	**985**
2042-3067	**985**
2042-3075	**985**
2042-3083	**985**
2042-3091	**985**
2042-3109	**985**
2042-5336	**922**
2042-5337	**922**
2042-5338	**922**
2042-5339	**922**
2042-5340	**922**
2042-5341	**922**
2042-5342	**922**
2042-5343	**922**
2042-5344	**922**
2042-5345	**922**
2042-5346	**922**
2042-5658	**1633**
2044-1028	**1414**
2044-1036	**1414**
2044-1044	**1414**
20451/01	**1631**
20451/10-100UM	**1630**
20452/30-300UM	**1630**
20453/10-100UM	**1630**
20453/20-200UM	**1630**
20453/30-300UM	**1630**
2046-1687	**1391**
2046-1695	**922**
2046-1703	**922**
2046-1711	**922**
2046-1729	**922**
2046-1737	**922**
2046-1745	**922**
2046-1752	**922**
2046-1760	**922**
2046-7163	**768**
2046-7164	**768**
2046-7165	**768**
2046-7166	**768**
2046-7167	**768**
2046-7168	**768**
2046-7169	**768**
2046-7170	**769**
2046-7171	**769**
2046-7172	**769**
2046-7175	**770**
2046-7181	**773**
2046-7182	**773**
2046-7183	**772**
2046-7185	**772**
2046-7186	**772**
2046-7188	**772**
2046-7189	**772**
2046-7191	**769**
2046-7194	**768**
2046-7196	**768**
2046-7197	**768**
2046-7198	**768**
2046-7199	**768**
2046-7200	**768**
2046-7201	**768**
2046-7202	**768**
2046-7203	**768**
2046-7204	**768**
2046-7205	**768**
2049-1	**972**
2049-112	**972**
2049-112N	**972**
2049-114	**972**
2049-114N	**972**
2049-12	**972**
2049-12N	**972**
2049-1460	**1146**
2049-1478	**1146**
2049-1502	**1146**
2049-1528	**1146**
2049-1536	**1146**
2049-1537	**1146**
2049-1538	**1146**
2049-1539	**1146**
2049-1540	**1146**
2049-1544	**1146**
2049-1551	**1146**
2049-1577	**1146**
2049-1585	**1146**
2049-1593	**1146**
2049-1601	**1146**
2049-1619	**1146**
2049-1630	**1146**
2049-1633	**1146**
2049-1638	**1146**
2049-1640	**1146**
2049-1643	**1146**
2049-1668	**1146**
2049-1684	**1146**
2049-1N	**972**
2049-2	**972**
2049-2N	**972**
2049-34	**972**
2049-34N	**972**
2049-38	**972**
2049SL150 04	**973**
2049SL150 05	**973**
2049SL150 06	**973**
2049SL150 08	**973**
2049SL150 09	**973**
2049SL150 10	**973**
2049SL150 11	**973**
2049SL150 12	**973**
2049SL150 13	**973**
2049SL150 14	**973**
2049SL16 04	**973**
2049SL16 05	**973**
2049SL16 06	**973**
2049SL16 07	**973**
2049SL16 08	**973**
2049SL16 09	**973**
2049SL16 10	**973**
2049SL16 11	**973**
2049SL16 12	**973**
2049SL16 13	**973**
2049SL16 14	**973**
204M10U916	**97**
204M12U34	**97**
204M16U78	**97**
204M18U1116	**97**
204M22U1316	**97**
204M25U1516	**97**
204M32U158	**97**
204M38U178	**97**
204M6U716	**97**
204M8U12	**97**
20500307	**404**
20500308	**404**
20500309	**404**
20500314	**404**
20500315	**404**
20500316	**404**
20500320	**404**
20500321	**404**
20500322	**404**
20500345	**404**
20500346	**404**
20500347	**404**
20500351	**404**
20500352	**404**
20500353	**404**
20500356	**404**
20500357	**404**
20500358	**404**
20500434	**404**
20500438	**404**
20500439	**404**
20500440	**404**
20500441	**404**
20500442	**404**
20500443	**404**
20500444	**404**
20500445	**404**
2050-2217	**1419**
2050-2225	**1419**
2050-2233	**1419**
2050-2241	**1419**
2050-2258	**1419**
2050-2266	**1419**
2050-2274	**1419**
2050-2282	**1419**
2050-2290	**1419**
2050-2308	**1419**
2050-2316	**1419**
2050-2324	**1419**
2050-2332	**1419**
2050-2340	**1419**
2050-2357	**1419**
2050-2365	**1419**
2050-2373	**1419**
2050-2381	**1419**
2050-2415	**1419**
2050-2506	**1419**
2050-2522	**1419**
2052-1423	**1676**
2052-8774	**417**
2052-8782	**417**
2052-8790	**417**
2052-8808	**417**
2052-8816	**417**
2052-8824	**417**
2052-8840	**417**
2052-8873	**417**
2052-8907	**417**
2052-8915	**417**
2052-8923	**417**
2052-8998	**1146**
2052-9020	**1146**
2052-9038	**1146**
2052-9046	**1146**
2052-9053	**1146**
2052-9228	**1481**
2052-9236	**1481**
2052-9244	**1481**
2052-9251	**1481**
2052-9269	**1481**
2052-9277	**1481**
2052-9285	**1481**
2052-9293	**1481**
2053-5613	**390**
2053-5621	**390**
2053-5639	**390**
2053-5662	**390**
2053-5696	**390**
2053-5712	**390**
2053-5746	**390**
2053-5761	**390**
2053-5787	**390**
2053-5795	**390**
2053SL150 06	**977**
2053SL150 08	**977**
2053SL150 09	**977**
2053SL150 10	**977**
2053SL150 11	**977**
2053SL150 12	**977**
2053SL16 06	**977**
2053SL16 08	**977**
2053SL16 09	**977**
2053SL16 10	**977**
2053SL16 11	**977**
2053SL16 12	**977**
2053SL16 14	**977**
2054SL150 04	**958**
2054SL150 05	**958**
2054SL150 06	**958**
2054SL150 08	**958**
2054SL150 09	**958**
2054SL150 10	**958**
2054SL150 11	**958**
2054SL150 12	**958**
2054SL150 14	**958**
2054SL16 04	**958**
2054SL16 05	**958**
2054SL16 06	**958**
2054SL16 07	**958**
2054SL16 08	**958**
2054SL16 09	**958**
2054SL16 11	**958**
2054SL16 12	**958**
2054SL16 14	**958**
2057CBL-1	**952**
2057CBL-112	**952**
2057CBL-12	**952**
2057CBL-2	**952**
2057CBL-212	**952**
2057CBL-3	**952**
2057CBL-4	**952**
2057CBT-1	**952**
2057CBT-112	**952**
2057CBT-12	**952**
2057CBT-2	**952**
2057CBT-212	**952**
2057CBT-3	**952**
2057CBT-4	**952**
2059DL150 04	**954**
2059DL150 06	**954**
2059DL150 08	**954**
2059DL150 09	**954**
2059DL150 11	**954**
2059DL150 12	**954**
2059DL150 14	**954**
2059DL16 04	**954**
2059DL16 06	**954**
2059DL16 08	**954**
2059DL16 09	**954**
2059DL16 10	**954**
2059DL16 11	**954**
2059DL16 12	**954**
2059DL16 14	**954**
2059DT150 04	**954**
2059DT150 06	**954**
2059DT150 08	**954**
2059DT150 09	**954**
2059DT150 11	**954**
2059DT150 12	**954**
2059DT150 14	**954**
2059DT16 04	**954**
2059DT16 06	**954**
2059DT16 08	**954**
2059DT16 09	**954**
2059DT16 10	**954**
2059DT16 11	**954**
2059DT16 12	**954**
2059DT16 14	**954**
205BM10	**95**
205BM12	**95**
205BM16	**95**
205BM20	**95**
205BM22	**95**
205BM25	**95**
205BM32	**95**
205BM6	**95**
205BM8	**95**
2064-7889	**922**
2064-7897	**922**
2064-7905	**922**
2064-7913	**922**
2064-7921	**922**
2064-7939	**922**
2064-7947	**922**
2064-7954	**922**
2064-7962	**922**
2064-7970	**922**
2064-7988	**922**
2064-7996	**922**
2064-8002	**922**
206BM12	**97**
206BM20	**97**
206BM22	**97**

Code	Page
206BM25	97
206BM32	97
206BM38	97
206BM6	97
206BM8	97
206M10R12	97
206M10R14	97
206M10R18	97
206M10R38	97
206M12R12	97
206M12R14	97
206M12R34	97
206M12R38	97
206M16R12	97
206M16R34	97
206M16R38	97
206M18R1	97
206M18R34	97
206M22R34	97
206M25R1	97
206M25R34	97
206M32R1	97
206M32R114	97
206M38R112	97
206M38R114	97
206M6R12	97
206M6R14	97
206M6R18	97
206M8R14	97
206M8R18	97
207BM10	98
207BM12	98
207BM16	98
207BM20	98
207BM22	98
207BM25	98
207BM32	98
207BM6	98
207BM8	98
207R	1538
2085-9179	621
2085-9195	621
2085-9203	621
2085-9211	621
2085-9229	621
2085-9245	621
2085-9252	621
2085-9260	621
2085-9278	621
2085-9286	621
2085-9294	621
2085-9310	621
2085-9328	621
2085-9336	621
2085-9344	621
2085-9351	621
2085-9369	621
2085-9377	621
2085-9385	621
2085-9393	621
2085-9401	621
2085-9419	621
2085-9435	621
2085-9443	621
2085-9450	621
2085-9468	621
2085-9476	621
2085-9484	621
2085-9492	621
2085-9500	621
2085-9518	621
2085-9526	621
2085-9534	621
2089-3731	614
2089-3764	614
2095-13/10	1172
2095-17/10	1172
2095-17/13	1172
2095-21/13	1172
2095-21/17	1172
2095-26/21	1172
2095-33/21	1172
2095-33/26	1172
2098969	448
2098970	448
2098972	448
2098973	448
2098974	448
2098975	448
20AG-X4G-PH100	689
20AG-X4G-PJ100	689
20JITS	80
20JMTS	80
20JTN	80
20KAAM05MPN	339
20KAAW10MPN	339
20KAIM05MPN	339
20KAIW10MPN	339
20KAKO04MPN	339
20KAKO06MPN	339
20KAKS04MPN	339
20KAKS06MPN	339
20KATF03MPN	339
20KATF04MPN	339
20KATF05MPN	339
20KBAM05MPX	340
20KBAW10MPX	340
20KBIM05MPX	340
20KBIW10MPX	340
20KBKO06MPX	340
20KBTF03MPX	340
20KBTF04MPX	340
20SBAM05MPX	340
20SBAW10MPX	340
20SBIM05MPX	340
20SBIW10MPX	340
20SBKO06MPX	340
20SBTF04MPX	340
20SFAM05MXN	339
20SFAW10MXN	339
20SFIM05MXN	339
20SFIW10MXN	339
20SFKO04MXN	339
20SFKO05MXN	339
20SFKS06MXN	339
20SFTF03MXN	339
20SFTF04MXN	339
20SFTF05MXN	339
20SFTS03MXN	339
21/2-ORING	108
2101-7991	137
2101-8007	137
2101-8023	137
2101-8031	137
2101-8049	137
2101-8064	137
2101-8072	137
2101-8080	137
2101-8098	137
2101-8114	137
2101-8122	137
2101-8130	137
2101-8148	137
2101-8163	137
2101-8189	137
2101-8197	137
2101-8205	137
2101-8213	137
2101-8221	137
2101-8239	137
2101-8247	156
2101-8254	156
2101-8262	156
2101-8270	156
2101-8288	156
2101-8296	156
2101-8304	156
2101-8312	156
2101-8338	156
2101-8346	156
2101-8353	156
2101-8361	156
2101-8379	156
2101-8387	156
2101-8395	156
2101-8403	156
2101-8411	156
2101-8429	156
2101-8437	156
2101-8445	156
2102628	489
2102629	489
2102630	489
2102631	489
2102632	489
2102633	489
21-049	1673
21-050	1673
21-051	1673
21-052	1673
21-055	1673
21-056	1673
21-057	1673
210BM10R12	95
210BM10R14	95
210BM10R18	95
210BM10R38	95
210BM12R12	95
210BM12R14	95
210BM12R38	95
210BM16R12	95
210BM16R34	95
210BM20R1	95
210BM20R12	95
210BM20R34	95
210BM22R34	95
210BM25R1	95
210BM25R34	95
210BM32R1	95
210BM32R114	95
210BM38R112	95
210BM6R12	95
210BM6R14	95
210BM6R18	95
210BM8R14	95
210BM8R18	95
210R	1538
210SM10G12	95
210SM10G14	95
210SM10G18	95
210SM10G38	95
210SM12G12	95
210SM12G14	95
210SM12G34	95
210SM12G38	95
210SM16G12	95
210SM16G34	95
210SM16G38	95
210SM20G1	95
210SM20G12	95
210SM20G34	95
210SM22G34	95
210SM25G1	95
210SM25G114	95
210SM25G34	95
210SM32G1	95
210SM32G114	95
210SM38G112	95
210SM38G114	95
210SM6G12	95
210SM6G14	95
210SM6G18	95
210SM6G38	95
210SM8G14	95
210SM8G18	95
210SM8G38	95
2110-14	1172
2110-18	1172
2110-38	1172
2110-7776	775
2110-7800	775
2110-7826	775
2110-7834	775
2110-7842	775
2110-7859	775
2110-7875	775
2110-7909	775
2110-7925	775
2110-7933	775
2110-7941	775
2110-7958	775
2110-7966	775
2110-7974	775
2110-7982	775
2110-7990	775
2110-8006	775
2110-8014	775
2110-8022	775
2110-8063	775
2110-8071	775
2110-8089	775
2110-8097	775
2110-8105	775
2110-8113	775
2110-8121	775
2110-8139	775
2110-8147	775
2110-8154	775
2110-8188	775
2110-8204	775
2110-8220	775
2110-8238	775
2110-8246	775
2110-8253	775
2110-8279	775
2110-8287	775
2110-8295	775
2110-8303	775
2110-8311	775
2110-8329	775
2110-8337	775
2110-8345	775
2110-8352	775
2110-8360	775
2110-8378	775
2110-8386	775
2110-8394	775
2110-8402	775
2110-8410	775
2110-8428	775
2110-8436	775
2110-8444	775
2110-8451	775
2110-8469	775
2110-8477	775
2110-8485	775
2110-8493	775
2110-8519	775
2110-8527	775
2110-8535	775
2110-8543	775
2110-8550	775
2110-8568	775
2110-8576	775
2110-8584	776
2110-8592	776
2110-8600	776
2110-8618	776
2110-8626	776
2110-8634	776
2110-8659	776
2110-8667	776
2110-8691	776
2110-8709	776
2110-8717	776
2110-8725	776
2110-8733	776
2110-8741	776
2110-8758	776
2110-8766	776

Code	Page
2110-8774	776
2110-8782	776
2110-8790	776
2110-8808	776
2110-8816	776
2110-8824	776
2110-8832	776
2110-8840	776
2110-8857	776
2110-8865	776
2110-8881	776
2110-8907	776
2110-8915	776
2110-8923	776
2110-8931	776
2110-8949	776
2110-8956	776
2110-8964	776
2110-8972	776
2110-8980	776
2110-8998	776
2110-9004	776
2110-9020	776
2110-9038	776
2110-9046	776
2110-9053	776
2110-9061	776
2110-9087	776
2110-9095	776
2110-9111	776
2110-9129	776
2110-9137	776
2110-9145	776
2110-9178	776
2110-9186	776
2110-9194	776
2110-9202	776
2110-9228	776
2110-9236	776
2110-9251	776
2110-9269	776
2110-9277	776
2110-9285	776
2110-9293	776
2111-0093	776
2111-0101	776
2111-0119	776
2111-2420	778
2111-2446	778
2111-2453	778
2111-2461	778
2111-2479	778
2111-2487	778
2111-2495	778
2111-2503	778
2111-2511	778
2111-2529	778
2111-2537	778
2111-2545	778
2111-2552	778
2111-2560	778
2111-2578	778
2111-2586	778
2111-2594	778
2111-2602	778
2111-2610	778
2111-2628	778
2111-2636	778
2111-2644	778
2111-2651	778
2111-2669	778
2111-2677	778
2111-2685	778
2111-2693	778
2111-2701	778
2111-2719	778
2111-2727	778
2111-2735	778
2111-2743	778
2111-2750	778
2111-2768	778
2111-2776	778
2111-2784	778
2111-2792	778
2111-2800	778
2111-2818	778
2111-2826	778
2111-2834	778
2111-2842	778
2111-2859	778
2111-2867	778
2111-2875	778
2111-2883	778
2111-2891	778
2111-2909	778
2111-2917	778
2111-2925	778
2111-2933	778
2111-2941	778
2111-2958	778
2111-2966	778
2111-2974	778
2111-2982	778
2111-3006	778
2111-3014	778
2111-3030	778
2111-3048	778
2111-3055	778
2111-3063	778
2111-3071	778
2111-3089	778
2111-3097	778
2111-3105	778
2111-3113	778
2111-3121	778
2111-3139	778
2111-3147	778
2111-3154	778
2111-3162	778
2111-3170	778
2111-3196	778
2111-3204	778
2111-3212	778
2111-3220	778
2111-3238	778
2111-3246	778
2111-3253	778
2111-3261	778
2111-3279	778
2111-3287	778
2111-3295	778
2111-3303	778
2111-3311	778
2111-3329	778
2111-3337	778
2111-3345	778
2111-3352	778
2111-3360	778
2111-3378	778
2111-3386	778
2111-3394	778
2111-3402	778
2111-3410	778
2111-3428	778
2111-3436	778
2111-3485	779
2111-3519	779
2111-3527	779
2111-3535	779
2111-3568	779
2111-3576	779
2111-3584	779
2111-3592	779
2111-3600	779
2111-3618	779
2111-3626	779
2111-3634	779
2111-3642	779
2111-3659	779
2111-3667	779
2111-3675	779
2111-3683	779
2111-3691	779
2111-3709	779
2111-3717	779
2111-3725	779
2111-3733	779
2111-3758	779
2111-3766	779
2111-3774	779
2111-3782	779
2111-3790	779
2111-3808	779
2111-3816	779
2111-3832	779
2111-3840	779
2111-3857	779
2111-3865	779
2111-3873	779
2111-3881	779
2111-3899	779
2111-3907	779
2111-3915	779
2111-3923	779
2111-3931	779
2111-3949	779
2111-3956	779
2111-3964	779
2111-3972	779
2111-3980	779
2111-3998	779
2111-4004	779
2111-4012	779
2111-4020	779
2111-4038	779
2111-4053	779
2111-4061	779
2111-4079	779
2111-4087	779
2111-4095	779
2111-4111	779
2111-4137	779
2111-4145	779
2111-4152	779
2111-4160	779
2111-4178	779
2111-4186	779
2111-4202	779
2111-4210	779
2111-4228	779
2111-4236	779
2111-4244	779
2111-4251	779
2111-4277	779
2111-4285	779
2111-4293	779
2111-4301	779
2111-4319	779
2111-4327	779
2111-4335	779
2111-4343	779
2111-4350	779
2111-4368	779
2111-4376	779
2111-4384	779
2111-4392	779
2111-4400	779
2111-4418	779
2111-4426	779
2111-4434	779
2111-4442	779
2111-4459	779
2111-4467	779
2111-4475	779
2111-4483	779
2111-4491	779
2115-14	1172
2115-18	1172
2115-38	1172
212.32.9.1	570
212.52.9	573
212.53.31.9	574
212.53.31.9.1	574
212/2.32.11.1	609
212/2.32.11.11	609
212/2.52.11.1	610
212/2.52.11.12	610
212-0035-0000	1447
212-0045-0000	1447
212-0055-0000	1447
212-0065-0000	1447
212-0075-0000	1447
212-0085-0000	1447
212-0095-0000	1447
212-0105-0000	1447
212-0115-0000	1447
212-0125-0000	1447
212-0135-0000	1447
212-0145-0000	1447
212-0155-0000	1447
212-0165-0000	1447
212-0175-0000	1447
212-0195-0000	1447
212-0215-0000	1447
212-0245-0000	1447
212-0295-0000	1447
212-0315-0000	1447
212-0345-0000	1447
212-0395-0000	1447
2123069	448
2123070	448
2123071	448
2123072	448
2123073	448
2123074	448
2123085	489
2123086	489
2123087	489
2123088	489
2123089	489
2123090	489
2123166	448
2123167	448
2123224	448
2123225	448
2123226	448
2123227	448
2123780	489
2123781	489
2123782	489
2123783	489
2123784	489
2123785	489
2125490	448
2125491	448
2125492	448
2125493	448
2125494	448
2125495	448
2126594	448
2126595	448
2126597	448
2126598	448
2126599	448
2126600	448
2126636	489
2126637	489
2126638	489
2126639	489
2126640	489
2126641	489
2126684	489
2126685	489
2126686	489
2126687	489
2126688	489
2126689	489
21300	57
21301	57
21302	57

Code	Page
21303	57
21304	57
21305	57
21307	57
21308	57
21310	57
21311	57
21312	57
21313	57
2135-2869	137
2135-2885	137
2135-2893	137
2135-2901	137
2135-3206	137
2135-3214	137
2135-3222	137
2135-3230	137
2135-3321	137
2135-3339	137
2135-3347	137
2135-3354	137
2135-3362	137
2135-3388	137
2135-3396	137
2135-3404	137
2135-3412	137
214.52.10.1/1	573
2144-9657	1676
2144-9665	1676
2144-9673	1676
2144-9681	1676
2144-9699	1676
2144-9715	1676
2144-9723	1676
2144-9731	1676
214BM10N12	95
214BM10N14	95
214BM10N18	95
214BM10N38	95
214BM12N12	95
214BM12N14	95
214BM12N34	95
214BM12N38	95
214BM16N12	95
214BM20N1	95
214BM20N12	95
214BM20N34	95
214BM25N1	95
214BM25N34	95
214BM32N1	95
214BM32N114	95
214BM38N112	95
214BM38N114	95
214BM6N14	95
214BM6N18	95
214BM8N14	95
214BM8N18	95
216-0032-2872	1447
216-0038-2872	1447
216-0040-2872	1447
216-0050-0000	1447
216-0055-0000	1447
216-0060-0000	1447
216-0065-0000	1447
216-0070-0000	1447
216-0075-0000	1447
216-0080-0000	1447
216-0090-0000	1447
216-0100-0000	1447
216-0102-0000	1447
216-0110-0000	1447
216-0115-0000	1447
216-0120-0000	1447
216-0125-0000	1447
216-0127-0000	1447
216-0130-0000	1447
216-0140-0000	1447
216-0150-0000	1447
216-0152-0000	1447
216-0160-0000	1447
216-0175-0000	1447
216-0180-0000	1447
216-0200-0000	1447
216SM10G38	98
216SM12G12	98
216SM12G14	98
216SM12G34	98
216SM12G38	98
216SM16G12	98
216SM16G14	98
216SM16G34	98
216SM16G38	98
216SM20G12	98
216SM20G34	98
216SM22G1	98
216SM22G12	98
216SM22G34	98
216SM25G1	98
216SM25G12	98
216SM32G1	98
216SM38G112	98
216SM6G14	98
216SM6G18	98
216SM8G18	98
2174-1001	784
2174-1002	784
2174-1005	784
2174-1010	784
2174-1015	784
2174-1020	784
2174-1030	784
2174-1031	784
2174-1032	784
2174-1033	784
2174-1040	785
2174-1070	785
2174-1081	785
2174-2000	785
2174-2001	785
2174-2002	785
2174-2003	785
2174-2004	785
2174-2006	785
2174-2008	785
2174-3000	786
2174-3001	786
2174-3002	786
2174-3003	786
2174-3004	786
2174-3005	786
2174-3006	786
2174-3007	786
2175-0849	782
2175-0850	782
2175-0851	782
2175-0852	782
2175-0853	782
2175-0854	782
2175-0855	782
2175-0856	782
2175-0857	782
2175-0858	782
2175-0859	782
2175-0860	782
2175-0861	782
2175-0862	782
2175-0863	782
2175-0864	782
2175-0865	782
2175-0866	782
2175-0867	782
2175-0868	782
2175-0869	782
2175-0870	782
2175-0871	782
2175-0872	782
2175-0873	782
2175-0874	782
2175-0875	782
2175-0876	782
2175-0877	782
2175-0878	782
2175-0879	782
2175-0880	782
2175-0881	782
2175-0882	782
2175-0883	782
2175-0884	782
2175-0885	782
2175-0886	782
2175-0887	782
2175-0888	782
2175-0889	782
2175-0890	782
2175-0891	782
2175-0892	782
2175-0893	782
2175-0894	782
2175-0895	782
2175-0896	782
2175-0897	782
2175-0898	782
2175-0899	782
2175-0900	782
2175-0901	782
2175-0902	782
2175-0903	782
2175-0904	782
2175-0905	782
2175-0906	782
2175-0907	782
2175-0908	782
2175-0909	782
2175-0910	782
2175-0911	782
2175-0912	782
2175-0913	782
2175-0914	782
2175-0915	782
2175-0916	782
2175-0917	782
2175-0918	782
2175-0919	782
2175-0920	782
2175-0921	782
2175-0922	782
2175-0923	782
2175-0924	782
2175-0925	782
2175-0926	782
2175-0927	782
2175-0928	782
2175-0929	782
2175-0930	782
2175-0931	782
2175-0932	782
2175-0933	782
2175-0934	782
2175-0935	782
2175-0936	782
2175-0937	782
2175-0938	782
2175-0939	782
2175-0940	783
2175-0941	783
2175-0942	783
2175-0943	783
2175-0944	783
2175-0945	783
2175-0946	783
2175-0947	783
2175-0948	783
2175-0949	783
2175-0950	783
2175-0951	783
2175-0952	783
2175-0953	783
2175-0954	783
2175-0956	783
2175-0957	783
2175-0958	783
2175-0959	783
2175-0960	783
2175-0961	783
2175-0962	783
2175-0963	783
2175-0964	783
2175-0965	783
2175-0966	783
2175-0967	783
2175-0968	783
2175-0969	783
2175-0970	783
2175-0971	783
2175-0972	783
2175-0973	783
2175-0974	783
2175-0975	783
2175-0976	783
2175-0977	783
2175-0978	783
2175-0979	783
2175-0980	783
2175-0981	783
2175-0982	783
2175-0983	783
2175-0984	783
2175-0985	783
2175-0986	783
2175-0987	783
2175-0988	783
2175-0989	784
2175-0990	784
2175-0991	784
2175-0992	784
2175-0993	784
2175-0994	784
2175-0995	784
2175-0996	784
2175-0997	784
2175-0998	784
2175-0999	784
2175-1000	784
2175-1001	784
2175-1002	784
2175-1003	784
2175-1004	784
2175-1005	784
2175-1006	784
2175-1007	784
2175-1008	784
2175-1009	784
2175-1010	784
2175-1011	784
2175-1012	784
2175-1013	784
2175-1014	784
2175-1015	784
2175-1016	784
2175-1017	784
2175-1018	784
2175-1019	784
2175-1020	784
2175-1021	784
2175-1022	784
2175-1023	784
2175-1024	784
2175-1025	784
2175-1026	784
2175-1027	784
2175-1028	784
2175-1029	784
2175-1030	784
2175-1031	784
2175-1032	784
2175-1033	784
2175-1034	784
2175-1035	784
2175-1036	784
2175-1037	784

Code	Page
2175-1038	784
2175-1039	784
2175-1040	784
2175-1041	784
2175-1042	784
2175-1043	784
2175-1044	784
2175-1045	784
2175-1046	784
2175-1047	784
2175-1048	784
2175-1049	784
2175-1050	784
2175-1051	785
2175-1052	785
2175-1053	785
2175-1054	785
2175-1055	785
2175-1056	785
2175-1057	785
2175-1058	785
2175-1059	785
2175-1060	785
2175-1061	785
2175-1062	785
2175-1063	785
2175-1064	785
2175-1065	785
2175-1066	785
2175-1067	785
2175-1068	785
2175-1069	785
2175-1070	785
2175-1071	785
2175-1072	785
2175-1073	785
2175-1074	785
2175-1075	785
2175-1076	785
2175-1077	785
2175-1078	785
2175-1079	785
2175-1080	785
2175-1081	785
2175-1082	785
2175-1083	785
2175-1084	785
2175-1085	785
2175-1086	785
2175-1087	785
2175-1088	785
2175-1089	785
2175-1090	785
2175-1091	785
2175-1092	785
2175-1093	785
2175-1094	785
2175-1095	785
2175-1096	785
2175-1097	786
2175-1098	786
2175-1099	786
2175-1100	786
2175-1101	786
2175-1102	786
2175-1103	786
2175-1104	786
2175-1105	786
2175-1106	786
2175-1107	786
2175-1108	786
2175-1109	786
2175-1110	786
2175-1111	786
2175-1112	786
2175-1113	786
2175-1114	786
2175-1115	786
2175-1116	786
2175-1117	786
2175-1118	786
2175-1119	786
2175-1120	786
2175-1121	786
2175-1122	786
2175-1123	786
2175-1124	786
2175-1125	786
2175-1126	786
2175-1127	786
2175-1128	786
2175-1129	786
2175-1130	786
2175-1131	786
2175-1132	786
2175-1133	786
2175-1134	786
2175-1135	786
2175-1136	786
2175-1137	786
2175-1138	786
2175-1139	786
2175-1140	786
2175-1141	786
2175-1142	786
2175-1143	786
2175-1144	786
2175-1145	786
2175-1146	786
2175-1147	786
2175-1148	786
2175-1149	786
2175-1150	786
2175-1151	786
2175-1152	786
2175-1153	786
2175-1154	786
2175-1155	786
2175-1160	783
2175-1170	783
2175-1171	783
2175-1172	783
2175-1173	783
2175-1174	783
2175-1175	783
2175-1176	783
2175-1177	783
2175-1178	783
2175-1179	783
2175-1180	783
2175-1181	783
2175-1182	783
2175-1183	783
2175-1184	783
2175-1185	783
2175-1186	783
2175-1187	783
2175-1188	783
2176-0001	783
2176-0002	783
2176-0003	783
2176-0004	783
2176-0005	783
2176-0006	783
2176-0007	783
2176-0009	783
2176-0011	783
2176-0012	783
2176-0015	783
2176-0016	783
2176-0018	783
2176-0019	783
2176-0020	783
2176-0021	783
2182-7977	41
2182-7985	41
2182-7993	41
2182-8009	41
2182-8025	41
2182-8033	41
2182-8041	41
2182-8058	41
2182-8066	41
2182-8074	41
2182-8082	41
2182-8108	41
2182-8116	41
2182-8124	41
2182-8132	41
2182-8140	41
2182-8157	41
2182-8173	41
2182-8181	41
2182-8199	41
2182-8207	41
2182-8215	41
2182-8223	41
2182-8231	41
2182-8249	41
2182-8256	41
2182-8272	41
2182-8280	41
2182-8306	41
21938	1745
2196-4229	901
2196-4230	901
2196-4231	901
2196-4232	901
2196-4233	901
2196-4234	901
2196-4235	901
2196-4236	901
2196-4237	901
2196-4238	901
2196-4239	901
2196-4240	901
2196-4241	901
2196-4242	901
2196-4243	901
2196-4244	901
2196-4245	901
2196-4246	901
2196-4247	901
2196-4248	901
2196-4249	901
2196-4250	901
2196-4251	901
2196-4252	901
2196-4253	901
2196-4254	901
2196-4255	901
2196-4256	901
2196-4257	901
2196-4258	901
2196-4259	901
2196-4260	901
2196-4261	901
2196-4262	901
2196-4263	901
2196-4264	901
2196-4265	901
2196-4266	901
2196-4267	901
2196-4268	901
2196-4269	901
2196-4270	901
2196-4271	901
2196-4272	901
2196-4273	901
2196-4275	901
2196-4276	901
2196-4277	901
2196-4278	901
2196-4279	901
2196-4280	901
2196-4281	901
2196-4282	901
2196-4283	901
2196-4284	901
2196-4285	901
2196-4286	901
2196-4287	901
2196-4288	901
2196-4289	901
2196-4290	901
2196-4291	901
2196-4292	901
2196-4293	901
2196-4294	901
2196-4295	901
2196-4296	901
2196-4297	901
2196-4298	901
2196-4299	901
2196-4300	901
2196-4301	901
2196-4302	901
2196-4303	901
2196-4304	901
2196-4305	901
2196-4306	901
2196-4307	901
2196-4308	901
2196-4309	901
2196-4310	901
2196-4311	901
2196-4312	901
2196-4313	901
2196-4314	901
2196-4315	901
2196-4316	901
2196-4317	901
2196-4318	901
2196-4319	901
2196-4320	901
21KAAS13MPN	341
21KAAW10MPN	341
21KAAW10MPN0	346
21KAAW10MPN3	346
21KAAW10MPN6	346
21KAAW10MPN8	346
21KAAW13MPN	341
21KAAW13MPN0	346
21KAAW13MPN3	346
21KAAW13MPN6	346
21KAAW13MPN8	346
21KAAW17MPN	341
21KAIW10MPN	341
21KAIW10MPN0	346
21KAIW10MPN6	346
21KAIW10MPN8	346
21KAIW13MPN	341
21KAIW13MPN0	346
21KAIW13MPN6	346
21KAIW13MPN8	346
21KAIW17MPN	341
21KAKK06MPN	341
21KAKK08MPN	341
21KAKO06MPN	341
21KAKO08MPN	341
21KAKS06MPN	341
21KAKS08MPN	341
21KARP06MPN	343
21KARP08MPN	343
21KATF04MPN	341
21KATF06MPN	341
21KATF08MPN	341
21KATF09MPN	341
21KATF10MPN	341
21KATF10MPN8	346
21KATS04MPN	341
21KATS06MPN	341
21KATS08MPN	341
21KBAW10DPX	347
21KBAW10MPX	344
21KBAW13DPX	347
21KBAW13MPX	344
21KBIW10DPX	347
21KBIW10FVX	347
21KBIW10MPX	344

Code	Page
21KBIW13DPX	347
21KBIW13MPX	344
21KBKE06DPX	349
21KBKE06FVX	349
21KBKO06DPX	347
21KBKO06FVX	347
21KBKO06MPX	344
21KBKO08MPX	344
21KBKS06DPX	347
21KBTE04DPX	349
21KBTF04DPX	347
21KBTF04MPX	344
21KBTF06DPX	347
21KBTF06MPX	344
21KBTF08MPX	344
21KSAW10MPN	345
21KSAW13MPN	345
21KSIW10MPN	345
21KSIW13MPN	345
21KSTF06MPN	345
21KSTF08MPN	345
21KSTF10MPN	345
21SBAW10DPX	349
21SBAW10MPX	344
21SBAW13DPX	349
21SBIW10DPX	349
21SBIW10MPX	344
21SBIW13DPX	349
21SBKO06DPX	349
21SBKO06MPX	344
21SBKO08FVX	349
21SBKO08MPX	344
21SBKS06DPX	349
21SBTF08MPX	344
21SFAW10DXX	348
21SFAW10MXN	342
21SFAW10MXN0	346
21SFAW10MXN3	346
21SFAW10MXN6	346
21SFAW10MXN8	346
21SFAW13DXX	348
21SFAW13MXN	342
21SFAW13MXN0	346
21SFAW13MXN3	346
21SFAW13MXN6	346
21SFAW13MXN8	346
21SFAW17MXN	342
21SFIW10MXN	342
21SFIW10MXN0	346
21SFIW10MXN3	346
21SFIW10MXN6	346
21SFIW10MXN8	346
21SFIW13DXX	348
21SFIW13FXX	348
21SFIW13MXN	342
21SFIW13MXN0	346
21SFIW13MXN3	346
21SFIW13MXN6	346
21SFIW13MXN8	346
21SFIW17MXN	342
21SFKK06MXN	342
21SFKK08MXN	342
21SFKO06DXX	348
21SFKO06MXN	342
21SFKO08FXX	348
21SFKO08MXN	342
21SFKS06MXN	342
21SFKS08MXN	342
21SFRP06MPN	343
21SFRP08MPN	343
21SFTF04MXN	342
21SFTF04MXN0	346
21SFTF04MXN6	346
21SFTF05MXN	342
21SFTF06DXX	348
21SFTF06MXN	342
21SFTF06MXN8	346
21SFTF08MXN	342
21SFTF09MXN	342
21SFTF10MXN	342
21SFTS04FXX	348
21SFTS04MXN	342
21SFTS06MXN	342
21SFTS09MXN	342
21SSAW10MXN	345
21SSAW13MXN	345
21SSIW10MXN	345
21SSIW13MXN	345
21SSTF06MXN	345
21SSTF08MXN	345
21SSTF10MXN	345
2201	250
2201001	1212
2201002	1212
2201003	1212
2201004	1212
2201005	1212
2202	250
2202001	1212
2202002	1212
2202004	1212
2202005	1212
2202006	1212
2202007	1212
2203	250
2203001	1212
2203002	1212
2203003	1212
2203004	1212
2203005	1212
2203006	1212
2204001	1212
2204002	1212
2204003	1212
2204004	1212
2205001	1212
2205002	1212
2205003	1212
2205004	1212
2205005	1212
2205007	1212
2205008	1212
2205009	1212
2205010	1212
2205011	1212
2205012	1212
2206001	1212
2206002	1212
2206003	1212
2206004	1212
2206005	1212
2206006	1212
2207001	1212
2207002	1212
2207003	1212
2207004	1212
2207005	1212
2207006	1212
2207008	1212
2207011	1212
2207-0684	782
2207-0685	782
2207-0686	782
2207-0687	782
2207-0688	782
2207-0689	782
2207-0690	782
2207-0691	782
2207-0692	782
2207-0693	782
2207-0694	782
2207-0695	782
2207-0696	782
2207-0697	782
2207-0698	782
2207-0699	782
2207-0700	782
2207-0701	782
2207-0702	782
2207-0703	782
2207-0704	784
2207-0705	784
2207-0706	784
2207-0707	784
2207-0708	784
2207-0709	784
2207-0710	784
2207-0711	784
2207-0714	782
2207-0800	782
2207-0801	782
2207-0802	782
2207-0803	782
2207-0804	782
2207-0805	782
2207-0806	782
2207-0807	782
2207-0808	782
2207-0809	782
2207-0810	782
2207-0811	782
2207-0812	782
2207-0813	782
2207-0814	782
2207-0815	782
2207-0816	782
2208002	1212
2208003	1212
2208005	1212
2208006	1212
2208007	1212
2208009	1212
2208010	1212
2208011	1212
2209001	1212
2209002	1212
2209003	1212
2209004	1212
2209005	1212
2209006	1212
2210	250
2211001	1212
2211002	1212
2211003	1212
2211004	1212
2211005	1212
2212001	1212
2212002	1212
2212003	1212
2212004	1212
2212005	1212
2213233	490
2214899	490
2214909	490
2214971	490
221G13-230AC	1038
221G13-24DC	1038
221G1530-24DC	1038
221G16-230AC	1038
221G16-24DC	1038
221G17-24DC	1038
221G21-230AC	1038
221G2130-24DC	1038
221G6106-230AC	1037
221G6136-24DC	1037
221G6306-230AC	1037
221G6506-230AC	1037
221G6536-24DC	1037
221G6606-230AC	1037
2225-1	982
2225-12	982
2225-14	982
2225-34	982
2225-38	982
2225R	1538
224.32.11.1	609
224.32.11.11	609
224.32.8.1	570
224.32.9.1/1	570
224.32.9.1/2	570
224.32.9.2	570
224.32.9.3	570
224.52.11.1	610
224.52.11.11	610
224.52.8.1	573
224.52.9.1/1	573
224.52.9.1/2	573
224.52.9.1/3	573
224.52.9.2	573
224.53.31.11.11	610
224.53.31.9.1/2	574
224.53.31.9.1/3	574
224.53.31.9.2	574
2250	1042
225R	1538
226-0025-0000	1446
226-0032-0000	1446
226-0038-0000	1446
226-0051-0000	1446
226-0063-0000	1446
226-0076-0000	1446
227-0032-0000	1446
227-0032-1003	1446
227-0038-0000	1446
227-0038-1003	1446
227-0050-0000	1446
227-0050-1003	1446
228.32.0.1	570
228.32.1.1	570
228.32.10.2/1	570
228.32.10/1	570
228.32.11.1	609
228.32.11.11	609
228.32.11.12	609
228.32.13.1	609
228.32.2.1	570
228.32.2.1/1	570
228.32.2.1/2	570
228.32.4.1	570
228.32.6.1/1	570
228.32.6.1/2	570
228.32.6.1/3	570
228.32.6.13/1	570
228.32.6.13/3	570
228.32.6.25	570
228.32.6.27	570
228.32.6.28	570
228.32.9.1/2	570
228.32.9/2	570
228.52.1.1	573
228.52.10.1	573
228.52.10.1/1	573
228.52.10.1P	573
228.52.11.1	610
228.52.11.11	610
228.52.11.12	610
228.52.13.1	610
228.52.2.1	573
228.52.2.1/1	573
228.52.2.1/2	573
228.52.4.1	573
228.52.55/1	573
228.52.55/2	573
228.52.55/3	573
228.52.6.25	573
228.52.6.27	573
228.52.6.28	573
228.52.9/2	573
228.53.31.9.1/1	574
228.53.31.9.1/2	574
228.53.31.9/1	574
228.53.31.9/2	574
228.53.32.10.1	574
228.53.32.9.1/2	574
22BLKCON-25C	884
22BPB-25C	882
22BPB-50C	882
22BPEX-20X2L	882
22BPEX-20X3L	882
22BPEX-25C	882

Code	Page
22BPEX-50C	882
22BV	881
22CFA	882
22CMA	882
22HSV	881
22KAAK13MPN	350
22KAAK17MPN	350
22KAIW13MPN	350
22KAIW21MPN	350
22KATF06MPN	350
22KATF08MPN	350
22KATF13MPN	350
22MC	883
22RA	1091
22SFAK13SXN	332
22SFAK17SXN	332
22SFAK21SXN	332
22SFIW13SXN	332
22SFIW17SXN	332
22SFIW21SXN	332
22SFTF06SXN	332
22SFTF08SXN	332
22SFTF10SXN	332
22SFTF13SXN	332
22STV	881
22WB	880
2301001	1162
2301002	1162
2301003	1162
2301004	1162
2301005	1162
2301006	1162
2301007	1162
2301008	1162
2301009	1162
2301010	1162
23012010	1537
23012028	1537
23012036	1537
23012044	1537
23012052	1537
23012060	1537
23012079	1537
23012087	1537
23012108	1537
23012116	1537
23012124	1537
23012132	1537
23012140	1537
23012159	1537
23012167	1537
23012175	1537
23012183	1537
23012191	1537
23012204	1537
23012300	1537
23012319	1537
23012327	1537
23012335	1537
23012343	1537
23012351	1537
23012360	1537
23012378	1537
23012386	1537
23012394	1537
23012407	1537
23012415	1537
23012423	1537
23012431	1537
23012440	1537
23012458	1537
2302002	1162
2302004	1162
2302005	1162
2302006	1162
2302007	1162
2302008	1162
2303001	1162
2303002	1162
2303003	1162
2303004	1162
2304001	1162
2304002	1162
2305001	1162
2305002	1162
2305003	1162
2305004	1162
2305005	1162
2305006	1162
2305007	1162
2305008	1162
2305009	1162
2305010	1162
2306001	1162
2306003	1162
2306004	1162
2307001	1162
2307002	1162
2307003	1162
2307004	1162
2307005	1162
2307008	1162
2307009	1162
2307010	1162
2308001	1162
2308002	1162
2308004	1162
2308005	1162
2308006	1162
2308007	1162
2308008	1162
2308009	1162
2308010	1162
2308012	1162
2309001	1162
2309002	1162
2309004	1162
230BM10G12	96
230BM10G14	96
230BM10G18	96
230BM10G38	96
230BM12G12	96
230BM12G14	96
230BM12G34	96
230BM12G38	96
230BM16G12	96
230BM16G34	96
230BM16G38	96
230BM18G1	96
230BM22G34	96
230BM25G1	96
230BM25G34	96
230BM32G1	96
230BM32G114	96
230BM38G112	96
230BM38G114	96
230BM6G12	96
230BM6G14	96
230BM6G18	96
230BM8G14	96
2311001	1162
2311002	1162
2311003	1162
231A0210	704
231A0220	704
231A0230	704
231A0240	704
231A0250	704
231A0260	704
231A0270	704
231A0280	704
231M10R12	96
231M10R14	96
231M10R18	96
231M10R38	96
231M12R12	96
231M12R14	96
231M12R34	96
231M12R38	96
231M16R12	96
231M16R34	96
231M16R38	96
231M18R1	96
231M18R34	96
231M22R34	96
231M25R1	96
231M25R34	96
231M32R1	96
231M32R114	96
231M38R112	96
231M38R114	96
231M6R12	96
231M6R14	96
231M6R18	96
231M8R14	96
231M8R18	96
232-101	446
2327R	1538
232A0220	704
232A0230	704
232A0240	704
232A0260	704
232A0270	704
232A0280	704
232A0340	704
232A0360	704
232A0380	704
232BM10N14	96
232BM10N38	96
232BM12N12	96
232BM20N12	96
232BM20N34	96
232BM25N1	96
232BM32N114	96
232BM38N112	96
232BM6N14	96
232BM6N18	96
232BM8N14	96
232F0220	704
232F0230	704
232F0240	704
232F0260	704
232F0280	704
234 895	560
234 904	560
234 905	560
234 9054	563
234 925	560
234 945	559
234 955	559
234 965	559
234 970	560
234 972	560
234 975	560
234 985	559
234 990	560
23493	1745
23498	1745
235 895	560
235 904	560
235 905	560
235 925	560
235 945	559
235 955	559
235 965	559
235 970	560
235 972	560
235 975	560
235 985	559
235 990	560
2351001	1162
2351002	1162
2351003	1162
2351004	1162
2351005	1162
2351006	1162
2351007	1162
2351008	1162
2351009	1162
2351010	1162
2351011	1162
2351012	1162
2352002	1162
2356001	1162
238929	223
239751	223
23KAAK13MPN	351
23KAAK17MPN	351
23KAAK21MPN	351
23KAIW13MPN	351
23KAIW17MPN	351
23KAIW21MPN	351
23KATF06MPN	351
23KATF08MPN	351
23KATF09MPN	351
23KATF10MPN	351
23KATF13MPN	351
23SFAK10SXN	351
23SFAK13SXN	351
23SFAK17SXN	351
23SFAK21SXN	351
23SFIW10SXN	351
23SFIW13SXN	351
23SFIW17SXN	351
23SFIW21SXN	351
23SFTF06SXN	351
23SFTF08SXN	351
23SFTF09SXN	351
23SFTF10SXN	351
23SFTF13SXN	351
2400	1042
2401 09	966
2401 10	966
2401 11	966
2401 12	966
2401 13	966
2401 14	966
2401 16	966
2401 18	966
2401 20	966
2402 09	964
2402 10	964
2402 11	964
2402 12	964
2402 13	964
2402 14	964
2402 16	964
2406 08	964
2406 09	964
2406 10	964
2406 11	964
2406 12	964
2406 13	964
2406 14	964
2406 16	964
2406 18	964
2406 20	964
2413-1	961
2413-112	961
2413-114	961
2413-12	961
2413-14	961
2413-2	961
2413-34	961
2413-38	961
24-14-2MM	1421
242287	223
242885	223
2436358	1587
2436359	1587
2440-1	964
2440-112	964
2440-114	964
2440-12	964
2440-14	964
2440-2	964
2440-34	964
2440-38	964
2445-1	964
2445-112	964

Code	Page
2445-114	964
2445-12	964
2445-14	964
2445-2	964
2445-34	964
2445-38	964
2447-1	964
2447-112	964
2447-114	964
2447-12	964
2447-2	964
2447-212	964
2447-3	964
2447-34	964
2447-4	964
2450 09	966
2450 10	966
2450 11	966
2450 12	966
2450 13	966
2450 14	966
2450 16	966
2451 09	966
2451 10	966
2451 11	966
2451 12	966
2451 13	966
2451 14	966
2451 16	966
2453 09	966
2453 10	966
2453 11	966
2453 12	966
2453 13	966
2453 14	966
2453 16	966
2453 18	966
245R	1538
2465321	660
24F910	1647
24G581	1647
24G593	1647
24JITS	80
24JTN	80
24KAAW13MPX	352
24KAAW17MPX	352
24KAAW21MPX	352
24KAIW13MPX	352
24KAIW17MPX	352
24KAIW21MPX	352
24KATF06MPX	352
24KATF08MPX	352
24KATF10MPX	352
24KATF13MPX	352
24N2A16A010	475
24N2A16A025	475
24N2A16A040	475
24N2A16A050	475
24N2A16A080	475
24N2A16A100	475
24N2A16A125	475
24N2A16A160	475
24N2A16A200	475
24N2A20A010	475
24N2A20A025	475
24N2A20A040	475
24N2A20A050	475
24N2A20A080	475
24N2A20A100	475
24N2A20A125	475
24N2A20A160	475
24N2A20A200	475
24N2A20A250	475
24N2A20A300	475
24N2A25A010	475
24N2A25A025	475
24N2A25A040	475
24N2A25A050	475
24N2A25A080	475
24N2A25A100	475
24N2A25A125	475
24N2A25A160	475
24N2A25A200	475
24N2A25A250	475
24N2A25A300	475
24N2A25A320	475
24N2A25A400	475
24N2A25A500	475
24PA.BARE	1635
24PA.KIT1B	1635
24PA.KIT1C	1635
2501010	1162
2501011	1162
2501012	1162
2501BLACK19	1589
2501BLACK25	1589
25-200	1627
25-201	1627
25-203	1627
25-204	1627
2528R	1538
254809	1763
254810	1763
2570-13	243
2570-17	243
2570-21	243
2570-26	243
25FAAK13SPN	355
25JMTS	80
25KAAK13MPN	353
25KAAK17MPN	353
25KAAK21MPN	353
25KAAW13RVX	360
25KAAW17RVX	360
25KAIW13MPN	353
25KAIW13RVX	360
25KAIW17MPN	353
25KAIW17RVX	360
25KAIW21MPN	353
25KAIW21RVX	360
25KAKK08MPN	353
25KAKK10MPN	353
25KAKO08MPN	353
25KATF08MPN	353
25KATF09BPX6	358
25KATF09BPX8	358
25KATF09MPN	353
25KATF10MPN	353
25KATF10RVX	360
25KATF13MPN	353
25KATF13RVX	360
25KATS08MPN	353
25KATS10MPN	353
25KBAK17BPX	356
25KBTF06BPX	356
25KDAK13BPNS	361
25KDIW13BPNS	361
25KDIW21BPNS	361
25KDTF08BPNS	361
25KSAK13SPN	359
25KSTF10SPN	359
25KSTF13SPN	359
25SBTF10MPX	356
25SDAW13MPN	361
25SDAW17MPN	361
25SDAW21MPN	361
25SDIW13MPN	361
25SDIW17MPN	361
25SDIW21MPN	361
25SDTF08MPN	361
25SDTF10MPN	361
25SDTF13MPN	361
25SFAK10SXN	354
25SFAK13SXN	354
25SFAK17SXN	354
25SFAK21SXN	354
25SFAW10MXX	362
25SFAW13MXX	362
25SFAW13MXX8	358
25SFAW13RXX	360
25SFAW17MXX	362
25SFAW17RXX	360
25SFAW21MXX	362
25SFAW21RXX	360
25SFIW10MXX	362
25SFIW10SXN	354
25SFIW13MXX	362
25SFIW13MXX3	358
25SFIW13MXX6	358
25SFIW13RXX	360
25SFIW13SXN	354
25SFIW17MXX	362
25SFIW17MXX8	358
25SFIW17RXX	360
25SFIW17SXN	354
25SFIW21MXX	362
25SFIW21RXX	360
25SFIW21SXN	354
25SFTF06MXX	362
25SFTF06RXX	360
25SFTF06SXN	354
25SFTF08MXX	362
25SFTF08RXX	360
25SFTF08SXN	354
25SFTF09MXX	362
25SFTF09SXN	354
25SFTF10MXX	362
25SFTF10RXX	360
25SFTF10SXN	354
25SFTF13MXX	362
25SFTF13RXX	360
25SFTF13SXN	354
25SRTF10SXN	355
25SSAK13SXN	359
25SSAK17SXN	359
25SSAK21SXN	359
25SSIW13SXN	359
25SSIW17SXN	359
25SSTF08SXN	359
25SSTF10SXN	359
25SSTF13SXN	359
25W	354
25Y	354
26-0021	1673
2619969	544
265M10U916	98
265M12U34	98
265M16U78	98
265M18U1116	98
265M22U1316	98
265M25U1516	98
265M32U158	98
265M38U178	98
265M6U716	98
265M8U12	98
26KAAW10MPX	362
26KAAW13MPX	362
26KAAW17MPX	362
26KAAW21MPX	362
26KAIW13MPX	362
26KAIW17MPX	362
26KAIW21MPX	362
26KATF06MPX	362
26KATF08MPX	362
26KATF09MPX	362
26KATF10MPX	362
26KATF13MPX	362
26KBTF10MPX	363
26KEAW13MPN	364
26KEAW17MPN	364
26KEAW21MPN	364
26KEIW13MPN	364
26KEIW17MPN	364
26KEIW21MPN	364
26KETF06MPN	364
26KETF08MPN	364
26KETF09MPN	364
26KETF10MPN	364
26KETF13MPN	364
26KPAW13APX	365
26KPAW17APX	365
26KPAW21APX	365
26KPIW13APX	365
26KPIW17APX	365
26KPIW21APX	365
26KPTF06APX	365
26KPTF08APX	365
26KPTF10APX	365
26KPTF13APX	365
26W	362
26Y	362
2700	1042
27000216	905
27000825	905
27010216	905
27010825	905
2702BLACK12	1589
2702BLACK19	1589
2702BLACK25	1589
2702BLACK50	1589
2702BLUE12	1589
2702BLUE19	1589
2702BROWN19	1589
2702DGREEN12	1589
2702ORANGE19	1589
2702ORANGE50	1589
2702RED12	1589
2702RED19	1589
2702RED25	1589
2702WHITE19	1589
2702YELLGRE19	1589
2702YELLOW19	1589
2702YELLOW50	1589
27070FDPOS	76
27072FDPOS	76
27073FDPOS	76
27074FDPOS	76
27075FDPOS	76
27076FDPOS	76
27077FDPOS	76
27079FDPOS	76
2721YELLBLACK50	1589
2721YELLBLACK75	1589
2731R	1538
273M10G14	96
273M10G38	96
273M10R14	96
273M10U716	96
273M10U916	96
273M12G38	96
273M12R14	96
273M12R38	96
273M12U916	96
273M16G12	96
273M16R12	96
273M16U34	96
273M18U1116	96
273M18U34	96
273M20G34	96
273M20R12	96
273M20R34	96
273M22G34	96
273M22R34	96
273M22U1116	96
273M25G1	96
273M25R1	96
273M25R34	96
273M25U1116	96
273M25U1516	96
273M32G114	96
273M32R114	96
273M38G112	96
273M38R112	96
273M6G18	96
273M6R18	96
273M6U716	96
273M8G14	96
273M8G18	96
273M8R14	96
273M8U12	96

Code	Page
273M8U716	96
275M10N12	98
275M10N14	98
275M10N18	98
275M10N38	98
275M10U916	98
275M12N12	98
275M12N14	98
275M12N34	98
275M12N38	98
275M12U34	98
275M16N12	98
275M16N34	98
275M16N38	98
275M16U78	98
275M18N1	98
275M18N34	98
275M18U1116	98
275M22N34	98
275M22U1316	98
275M25N1	98
275M25N34	98
275M25U1516	98
275M32N1	98
275M32N114	98
275M32U158	98
275M38N112	98
275M38N114	98
275M38U178	98
275M6N12	98
275M6N14	98
275M6N18	98
275M6U716	98
275M8N14	98
275M8N18	98
275M8U12	98
276M10N14	96
276M10N38	96
276M12N38	96
276M16N12	96
276M20N12	96
276M20N34	96
276M22N34	96
276M25N1	96
276M25N34	96
276M32N114	96
276M38N112	96
276M6N14	96
276M6N18	96
276M8N14	96
276M8N18	96
27KAAK13MPN	366
27KAAK17MPN	366
27KAAK21MPN	366
27KAAK26MPN	366
27KAIW13MPN	366
27KAIW17MPN	366
27KAIW21MPN	366
27KAIW26MPN	366
27KATF06MPN	366
27KATF09MPN	366
27KATF10MPN	366
27KATF13MPN	366
27KATF16MPN	366
27KATF19MPN	366
27KBTF19BPX	367
27SBAK26MPX	367
2800100005AP	532
2800100010AP	532
2800100015AP	532
2800100020AP	532
2800100025AP	532
2800100040AP	532
2800100050AP	532
28002	1500
2800200005XP	532
2800200010XP	532
2800200015XP	532
2800200020XP	532
2800200025XP	532
2800200040XP	532
2800200050XP	532
2800250005XP	532
2800250010XP	532
2800250015XP	532
2800250020XP	532
2800250025XP	532
2800250040XP	532
2800250050XP	532
28003	1500
2800320005CP	532
2800320010CP	532
2800320015CP	532
2800320020CP	532
2800320025CP	532
2800320040CP	532
2800320050CP	532
2800400005CP	532
2800400010CP	532
2800400015CP	532
2800400020CP	532
2800400025CP	532
2800400040CP	532
2800400050CP	532
2800500005CP	532
2800500010CP	532
2800500015CP	532
2800500020CP	532
2800500025CP	532
2800500040CP	532
2800500050CP	532
2800630005CP	532
2800630010CP	532
2800630015CP	532
2800630020CP	532
2800630025CP	532
2800630040CP	532
2800630050CP	532
28008	1500
2800800005AP	532
2800800010AP	532
2800800015AP	532
2800800020AP	532
2800800025AP	532
2800800040AP	532
2800800050AP	532
2800A-00	227
28011	1500
28012	1500
28013	1500
28015	1498
28016	1498
28017	1498
28019	1498
28020	1498
28021	1498
28022	1498
28027	1498
28028	1498
28029	1498
28032	1498
28033	1498
28034	1499
28035	1499
28036	1499
28038	1499
28042	1500
28043	1499
28049	1499
28050	1499
28051	1499
2810-0036-10	1087
2810-0038-10	1087
2810-0141-00	1087
2810-0148-00	1087
2810-0540-80	1087
2810-0641-00	1087
2810-8028-00	1087
2811-0025-80	1085
2811-0045-00	1087
2811-1002-80	1085
2811-1003-80	1086
2811-1005-80	1086
2811-1006-80	1085
2811-1008-80	1086
2811-1017-80	1085
2811-1022-20	1087
2811-1023-80	1085
2811-1025-80	1085
2811-1028-00	1087
2811-1051-81	1086
2811-1067-05	1085
2811-1152-81	1086
2811-2002-80	1085
2811-2003-80	1086
2811-2004-80	1086
2811-2005-80	1086
2811-2006-80	1085
2811-2008-80	1086
2811-2011-80	1086
2811-2022-20	1087
2811-2023-80	1085
2811-2051-81	1086
2811-2067-05	1085
2811-2108-80	1086
2811-2110-80	1086
2811-2117-80	1085
2811-2121-80	1085
2811-2217-80	1085
2811-2252-81	1086
2811-4000-05	1085
2811-4002-80	1085
2811-4003-80	1086
2811-4004-80	1086
2811-4005-80	1086
2811-4006-80	1085
2811-4022-20	1087
2811-4051-81	1086
2811-4107-80	1086
2811-4110-80	1086
2811-4207-80	1086
2811-4208-80	1086
2811-4221-80	1085
2811-4417-80	1085
2811-4452-81	1086
2811-5002-80	1085
2811-5003-80	1086
2811-5006-80	1085
2811-5208-80	1086
2811-5417-80	1085
2811-5517-80	1085
2811-6003-80	1086
2811-6028-00	1087
2811-6517-80	1085
2811-6617-80	1085
2811-7717-80	1085
281A0211	1413
281A0221	1413
281A0311	1413
281A0321	1413
281A0411	1413
281A0421	1413
281A0511	1413
281A0611	1413
281A0911	1413
2831R	1538
284 870	560
285 870	560
285M10N12	97
285M12N18	97
285M16N14	97
285M18N18	97
285M22N14	97
285M25N38	97
285M32N12	97
285M38N14	97
285M6N18	97
285M8N14	97
289M10U916	100
289M12U34	100
289M16U78	100
289M22U1316	100
289M25U1516	100
289M32U158	100
289M38U178	100
289M6U716	100
289M8U12	100
28BPEX-10X3L	882
28PHA01	1149
28PHA04	1149
28PHA05	1149
28PHA06	1149
28PHA08	1149
28PHA09	1149
28PHA10	1149
28PHA11	1149
28PHA12	1149
28PHA13	1149
28PHA14	1149
28PHA15	1149
28PHA16	1149
28PHA17	1149
28PHA18	1149
28PHA18A	1149
28PHA19	1149
28PHA20	1149
28PHA21	1149
28PHA22	1149
28PHA22A	1149
28PHA23	1149
28PHA24	1149
28PHA25B1	1149
28PHA25C	1149
28PHA25D	1149
28PHA25E	1149
28PHA25F	1149
28PHA38	1149
28PHA39	1149
28PHA40	1149
28PHA40A	1149
28PHA40B	1149
28PHA40C	1149
28PHA41A	1149
28PHA41B	1149
28PHA42	1149
28PHA42A	1149
28PHA42B	1149
28PHA43	1149
28PHA43A	1149
28PHA44	1149
28PHA45A	1149
28PHA45B	1149
28PHA45C	1149
28PHA46	1149
28PHA47A	1149
28PHA47B	1149
28PHA47BC	1149
28PHA47C	1149
28PHA47D	1149
28PHA50	1149
28PHA51	1149
28PHA52	1149
28PHA53	1149
28PHA53B	1149
28PHA53C	1149
28PHA54	1149
28PHA55	1149
28PHLA01	1149
28PHLA02	1149
28PHLB03	1149
28PHLB05	1149
28PHLB06	1149
28PHLB07	1149
28PHLB08	1149
28PHLB09A	1149
28PHM01A	1149
28PHM03	1149
28PHM04B	1149
28PHM05	1149
28PHM06	1149

Code	Page
28PHM07	1149
28PHM08	1149
28PHM09A	1149
28PHMR04B	1149
28PHMR04C	1149
28PHMR05	1149
28PHMR06	1149
28PHMR08	1149
28PHMR09	1149
28PHMR10	1149
2900100005AP	533
2900100010AP	533
2900100015AP	533
2900100020AP	533
2900100025AP	533
2900100040AP	533
2900100050AP	533
2900200005XP	533
2900200010XP	533
2900200015XP	533
2900200020XP	533
2900200025XP	533
2900200040XP	533
2900200050XP	533
2900250005XP	533
2900250010XP	533
2900250015XP	533
2900250020XP	533
2900250025XP	533
2900250040XP	533
2900250050XP	533
2900320005CP	533
2900320010CP	533
2900320015CP	533
2900320020CP	533
2900320025CP	533
2900320040CP	533
2900320050CP	533
2900400005CP	533
2900400010CP	533
2900400015CP	533
2900400020CP	533
2900400025CP	533
2900400040CP	533
2900400050CP	533
2900500005CP	533
2900500010CP	533
2900500015CP	533
2900500020CP	533
2900500025CP	533
2900500040CP	533
2900500050CP	533
2900630005CP	533
2900630010CP	533
2900630015CP	533
2900630020CP	533
2900630025CP	533
2900630040CP	533
2900630050CP	533
2900800005AP	533
2900800010AP	533
2900800015AP	533
2900800020AP	533
2900800025AP	533

Code	Page
2900800040AP	533
2900800050AP	533
2903BLACKBLACK50	1589
2903BLACKBLACK75	1589
2931678	1050
2931681	1050
2931682	1050
2931683	1050
29500FDPOS	77
29501FDPOS	77
29502FDPOS	77
29503FDPOS	77
29505FDPOS	77
29506FDPOS	77
29507FDPOS	77
29508FDPOS	77
29509FDPOS	77
2-971-02-02-004	271
2-971-02-04-004	271
2-971-03-02-001	271
2-971-04-02-001	271
2-971-04-04-001	271
2-971-09-02-001	271
2-971-10-02-001	271
2-971-10-04-001	271
2-971-12-02-001	271
2-971-12-04-001	271
2-971-13-00-001	271
2-971-13-04-001	271
2-971-15-00-001	271
2-971-15-04-001	271
2-971-19-02-001	271
2-971-19-04-001	271
2-971-20-02-001	271
2-971-20-04-001	271
2-971-21-02-001	271
2-971-21-04-001	271
2-971-22-02-001	271
2-971-22-04-001	271
2-971-23-02-001	271
2-971-23-04-001	271
2-971-24-02-001	271
2-971-24-04-001	271
2-971-25-02-001	271
2-971-25-04-001	271
2-971-26-00-001	271
2-971-26-04-001	271
2-971-27-00-001	271
2-971-27-04-001	271
2-971-33-00-001	271
2-971-33-04-001	271
2-971-41-02-001	271
2-971-41-04-001	271
2-971-44-02-001	271
2-971-44-04-001	271
2-971-45-02-001	271
2-971-45-04-001	271
2-971-46-02-001	271
2-971-46-04-001	271
2-971-48-02-001	271
2-971-48-04-001	271
2-971-50-02-001	271
2-971-50-04-001	271
2-971-54-02-001	271

Code	Page
2-971-54-04-001	271
2-971-57-02-001	271
2-971-57-04-001	271
2-971-58-02-001	271
2-971-58-04-001	271
2-971-75-00-001	271
2-971-75-04-001	271
29963	1746
299M10	100
299M12	100
299M16	100
299M20	100
299M22	100
299M25	100
299M32	100
299M38	100
299M6	100
299M8	100
29PHA27	1149
29PHA28	1149
29PHA29	1149
29PHA30	1149
29PHA31	1149
29PHA32A	1149
29PHA33	1149
29PHA34	1149
29PHA35	1149
29PHA36	1149
29PHA37	1149
2A-MS	1517
2A-MS-BOX	1517
2A-SS	1517
2B0202	61
2B0204	61
2B0206	61
2B0402	61
2B0404	61
2B0406	61
2B0408	61
2B0412	61
2B0602	61
2B0604	61
2B0606	61
2B0608	61
2B0610	61
2B0612	61
2B0616	61
2B0804	61
2B0806	61
2B0808	61
2B0810	61
2B0812	61
2B0816	61
2B1004	61
2B1006	61
2B1008	61
2B1010	61
2B1012	61
2B1204	61
2B1206	61
2B1208	61
2B1210	61
2B1212	61
2B1216	61

Code	Page
2B1220	61
2B1224	61
2B1606	61
2B1608	61
2B1612	61
2B1616	61
2B1620	61
2B1624	61
2B1632	61
2B2008	61
2B2012	61
2B2016	61
2B2020	61
2B2024	61
2B2416	61
2B2420	61
2B2424	61
2B2432	61
2B3224	61
2B3232	61
2BJ0207	74
2BJ0407	74
2BJ0408	74
2BJ0409	74
2BJ0412	74
2BJ0607	74
2BJ0608	74
2BJ0609	74
2BJ0612	74
2BJ0614	74
2BJ0807	74
2BJ0808	74
2BJ0809	74
2BJ0812	74
2BJ0814	74
2BJ0817	74
2BJ1012	74
2BJ1014	74
2BJ1017	74
2BJ1212	74
2BJ1214	74
2BJ1217	74
2BJ1219	74
2BJ1221	74
2BJ1617	74
2BJ1619	74
2BJ1621	74
2BJ1626	74
2BJ2021	74
2BJ2026	74
2BJ3230	74
2BM0412	61
2BM0414	61
2BM0416	61
2BM0418	61
2BM0614	61
2BM0616	61
2BM0618	61
2BM0620	61
2BM0622	61
2BM0816	61
2BM0818	61
2BM0820	61
2BM0822	61

Code	Page
2BM0824	61
2BM0826	61
2BM1022	61
2BM1222	61
2BMF0404-10000	1649
2BMF0404-1500	1649
2BMF0404-4000	1649
2BMF0404-600	1649
2F01000	865
2F01001	865
2F01002	865
2F01003	865
2F01007	865
2F01008	865
2F01009	865
2F01010	865
2F01011	865
2F01012	865
2F01013	865
2F01022	865
2F01C02	865
2F01C07	865
2F01C08	865
2F01C09	865
2F01C10	865
2F01C11	865
2F01C13	865
2F01C14	865
2F02001	866
2F02005	866
2F02006	866
2F02007	866
2F02008	866
2F02011	866
2F03001	865
2F03003	865
2F03004	865
2F03005	865
2F04001	866
2F04003	866
2F04004	866
2F04005	866
2F05001	865
2F05003	865
2F05004	865
2F05005	865
2F06000	866
2F06001	866
2F06002	866
2F06003	866
2F06007	866
2F06008	866
2F06009	866
2F06010	866
2F06011	866
2F06012	866
2F06013	866
2F11001	866
2F11003	866
2F11004	866
2F11005	866
2F31001	866
2F31002	866
2F31003	866

Code	Page
2F31007	866
2F31008	866
2F31009	866
2F31010	866
2F31011	866
2F31012	866
2F31013	866
2F31014	866
2F31015	866
2F31C02	866
2F31C03	866
2F31C08	866
2F31C09	866
2F31C10	866
2F31C11	866
2F31C12	866
2F31C13	866
2F31C14	866
2F32002	866
2F32008	866
2F32009	866
2F32010	866
2F32011	866
2F32012	866
2F32013	866
2F32014	866
2F39C02	866
2F39C08	866
2F39C09	866
2F39C10	866
2F39C11	866
2F39C12	866
2F39C13	866
2G-12G-MF-A-10K	91
2G-12G-MM-10K	90
2G-12N-MM-10K	90
2G-16G-MM-10K	90
2G-16N-MM-10K	90
2G-2G-MF-A-10K	91
2G-2G-MM-10K	90
2G-2N-MM-10K	90
2G-4G-MF-A-10K	91
2G-4G-MM-10K	90
2G-4J-MM-10K	90
2G-4N-MM-10K	90
2G-6G-MF-A-10K	91
2G-6G-MM-10K	90
2G-6J-MM-10K	90
2G-6N-MM-10K	90
2G-8G-MF-A-10K	91
2G-8G-MM-10K	90
2G-8N-MM-10K	90
2G-C-10K	94
2G-E-FF-10K	93
2G-E-MF-10K	93
2G-E-MM-10K	92
2G-P-10K	94
2G-T-FF-10K	94
2G-T-MM-10K	93
2J0707	75
2J0709	75
2J0712	75
2J0714	75
2J0808	75
2J0809	75
2J0907	75
2J0908	75
2J0909	75
2J0912	75
2J0914	75
2J1209	75
2J1212	75
2J1214	75
2J1217	75
2J1412	75
2J1414	75
2J1417	75
2J1712	75
2J1714	75
2J1717	75
2J1721	75
2J1919	75
2J2126	75
2J2626	75
2J2630	75
2JB0702	75
2JB0704	75
2JB0706	75
2JB0708	75
2JB0804	75
2JB0806	75
2JB0808	75
2JB0904	75
2JB0906	75
2JB1206	75
2JB1208	75
2JB1210	75
2JB1212	75
2JB1406	75
2JB1408	75
2JB1410	75
2JB1412	75
2JB1712	75
2JB2116	75
2JB2620	75
2J-E-FF-10K	93
2J-T-FF-10K	94
2L01000	868
2L01001	868
2L01002	868
2L01003	868
2L01007	868
2L01008	868
2L01009	868
2L01010	868
2L01011	868
2L01012	868
2L01013	868
2L01018	868
2L01C02	868
2L01C07	868
2L01C08	868
2L01C09	868
2L01C10	868
2L01C11	868
2L02001	868
2L02002	868
2L02005	868
2L02006	868
2L02007	868
2L02008	868
2L02009	868
2L02010	868
2L02011	868
2L02012	868
2L03001	868
2L03003	868
2L03004	868
2L03005	868
2L03301	868
2L03302	868
2L03303	868
2L03304	868
2L03305	868
2L03306	868
2L03307	868
2L03308	868
2L04001	868
2L04003	868
2L04004	868
2L04005	868
2L05001	868
2L05003	868
2L05004	868
2L05005	868
2L07004	869
2L08002	869
2L08004	869
2L08006	869
2L08007	869
2L08008	869
2L10001	821
2L10003	821
2L10004	821
2L10005	821
2L10006	821
2L11001	868
2L11003	868
2L11004	868
2L11005	868
2L11301	868
2L11302	868
2L11303	868
2L11304	868
2L11305	868
2L11306	868
2L11307	868
2L11308	868
2L21001	821
2L21003	821
2L21004	821
2L22001	821
2L22003	821
2L22004	821
2L23005	821
2L23006	821
2L23402	821
2L23403	821
2L23406	821
2L23407	821
2L23409	821
2L23410	821
2L23412	821
2L24004	822
2L24005	822
2L24006	822
2L25003	822
2L25004	822
2L25005	822
2L25008	822
2L25009	822
2L31001	869
2L31002	869
2L31003	869
2L31007	869
2L31008	869
2L31009	869
2L31010	869
2L31011	869
2L31012	869
2L31013	869
2L31014	869
2L31C02	869
2L31C03	869
2L31C08	869
2L31C09	869
2L31C10	869
2L31C11	869
2L31C12	869
2L31C13	869
2L31C14	869
2L32002	869
2L32003	869
2L32008	869
2L32009	869
2L32010	869
2L32011	869
2L32012	869
2L32013	869
2L32014	869
2L34001	821
2L34002	821
2L34003	821
2L34006	821
2L34007	821
2L34008	821
2L34009	821
2L34010	821
2L34011	821
2L34013	821
2L34014	821
2L34016	821
2L34017	821
2L34F01	821
2L34F05	821
2L34F06	821
2L34F07	821
2L34F08	821
2L34F09	821
2L34F10	821
2L35001	821
2L35002	821
2L35003	821
2L35006	821
2L35007	821
2L35008	821
2L35009	821
2L35010	821
2L35011	821
2L35013	821
2L35014	821
2L35016	821
2L35017	821
2L39C02	869
2L39C08	869
2L39C09	869
2L39C10	869
2L39C11	869
2L39C13	869
2L40003	868
2L40004	868
2L42001	822
2L42002	822
2L42004	822
2L42005	822
2L43001	822
2L43002	822
2L43003	822
2L43008	822
2L43009	822
2L46001	822
2L46002	822
2L46003	822
2L46004	822
2M1414	62
2M1616	62
2M1618	62
2M1818	62
2M2020	62
2M2022	62
2M2218	62
2M2220	62
2M2222	62
2MB1204	62
2MB1404	62
2MB1406	62
2MB1604	62
2MB1606	62
2MB1608	62
2MB1612	62
2MB1806	62
2MB1808	62
2MB2006	62
2MB2008	62
2MB2012	62
2MB2208	62
2MB2212	62
2MB2606	62
2MB3008	62
2-MS	1517
2-MS-BOX	1517
2N-12N-FF-10K	92
2N-12N-MF-A-10K	91
2N-16N-FF-10K	92
2N-2J-MM-10K	90
2N-2N-FF-10K	92
2N-2N-MF-A-10K	91
2N-2N-MM-10K	90
2N-4J-MM-10K	90
2N-4N-FF-10K	92

Code	Page
2N-4N-MF-A-10K	91
2N-4N-MM-10K	90
2N-6N-FF-10K	92
2N-6N-MF-A-10K	91
2N-8N-FF-10K	92
2N-8N-MF-A-10K	91
2N-C-10K	94
2N-E-10K	93
2N-E-MF-10K	93
2N-E-MM-10K	92
2N-P-10K	94
2N-T-10K	94
2N-T-MM-10K	93
2N-X-10K	94
2-ORING	108
2PWLA-38B	1678
2PWLA-38N	1678
2PWLA-K-F-38B	1678
2PWLA-K-F-38N	1678
2PWLA-K-K-38B	1678
2PWLA-K-K-38N	1678
2PWLA-K-M-38B	1678
2PWLA-K-M-38N	1678
2SC-04-100	9
2SC-06-100	9
2SC-08-100	9
2SC-12-100	9
2SC-16-100	9
2-SS	1517
2X-MS	1517
2X-MS-BOX	1517
2X-SS	1517
3	
3/4-ORING	108
3/8-BLACK-CUFF	1678
3/8-BLUE-CUFF	1678
300/V	1224
30-028	1673
3005-2	311
3005-3	311
3009-2	311
3009-3	311
301-0038-0000	1440
301-0050-0000	1440
301-0065-0000	1440
301-0075-0000	1440
301-0100-0000	1440
301-0125-0000	1440
301-0150-0000	1440
301-0160-0000	1440
3010-2	311
301-0200-0000	1440
301-0225-0000	1440
301-0250-0000	1440
3010-3	311
301-0300-0000	1440
302/V	1224
3022829	1050
3022833	1050
3022834	1050
3022835	1050
3025-1	1175
3025-1/2	1175
3025-1/4	1175
3025-1/8	1175
3025-3/4	1175
3025-3/8	1175
3026-1/2	1175
3026-1/4	1175
3026-1/8	1175
3026-3/4	1175
3026-3/8	1175
303/V	1224
303M10U1116	100
303M10U1316	100
303M10U1516	100
303M10U34	100
303M10U78	100
303M12U1116	100
303M12U1516	100
303M12U178	100
303M16U1316	100
303M16U1516	100
303M18U1516	100
303M18U158	100
303M18U178	100
303M25U158	100
303M25U178	100
303M6U1116	100
303M6U1516	100
303M6U34	100
303M6U716	100
303M6U78	100
304/V	1224
3040-10-1/2	1145
3040-10-1/4	1145
3040-10-1/8	1145
3040-10-3/8	1145
3040-12-1/2	1145
3040-12-1/4	1145
3040-12-3/8	1145
3040-14-1/2	1145
3040-14-3/8	1145
3040-15-1/2	1145
3040-16-1/2	1145
3040-16-3/4	1145
3040-16-3/8	1145
3040-17-1/2	1145
3040-17-3/8	1145
3040-18-1/2	1145
3040-18-3/4	1145
3040-18-3/8	1145
3040-20-1/2	1145
3040-20-3/4	1145
3040-20-3/8	1145
3040-25-1	1145
3040-25-3/4	1145
3040-4-1/8	1145
3040-6-1/4	1145
3040-6-1/8	1145
3040-7-1/4	1145
3040-7-1/8	1145
3040-8-1/4	1145
3040-8-1/8	1145
3040-8-3/8	1145
3040-9-1/2	1145
3040-9-1/4	1145
3040-9-1/8	1145
3040-9-3/8	1145
3045-12-1/2	1145
3045-12-1/4	1145
3045-12-3/8	1145
3045-15-1/2	1145
3045-17-1/2	1145
3045-17-3/8	1145
3045-4.5-M5	1145
3045-4-1/8	1145
3045-6-1/4	1145
3045-6-1/8	1145
3045-7-1/4	1145
3045-7-1/8	1145
3045-8-1/4	1145
3045-8-1/8	1145
3045-9-1/2	1145
3045-9-1/4	1145
3045-9-1/8	1145
3045-9-3/8	1145
305.11.00	599
305.11.01L	599
305.11.02L	599
305.11.03L	599
305.M1	599
305.M1/1	599
305/V	1224
3050-2	311
3050-3	311
30550A3	1660
3055-6-1/4	1145
3055-6-1/8	1145
3055-9-1/4	1145
3060-1	1172
3060-1/2	1172
3060-1/4	1172
3060-1/8	1172
3060-3/4	1172
3060-3/8	1172
3060-M5	1172
307/V	1224
307M10N12	98
307M10N14	98
307M10N18	98
307M10N38	98
307M12N12	98
307M12N14	98
307M12N34	98
307M12N38	98
307M16N12	98
307M16N34	98
307M16N38	98
307M18N1	98
307M18N34	98
307M22N34	98
307M25N1	98
307M25N34	98
307M32N1	98
307M32N114	98
307M38N112	98
307M38N114	98
307M6N12	98
307M6N14	98
307M6N18	98
307M8N14	98
307M8N18	98
307R	1538
30800220	1464
30800230	1464
30800420	1464
30800430	1464
30800783	1464
30800883	1464
30800983	1464
30801083	1464
30801183	1464
30801283	1464
30801383	1464
30801883	1464
30802183	1464
30802283	1464
30804686	1465
30804881	1465
30804886	1465
30804981	1465
30805081	1465
30810284	1465
30810384	1465
30810484	1465
30810584	1465
30810684	1465
30810884	1465
30811284	1465
30811484	1465
30811584	1465
30811684	1465
30811784	1465
30811884	1465
30812184	1465
30812284	1465
30813284	1465
30813384	1465
30813484	1465
30813584	1465
30813684	1465
30814584	1465
30817384	1465
30817484	1465
308M10G14	99
308M10G38	99
308M12G12	99
308M12G14	99
308M12G34	99
308M12G38	99
308M16G12	99
308M16G14	99
308M16G34	99
308M16G38	99
308M20G12	99
308M20G34	99
308M22G1	99
308M22G12	99
308M22G34	99
308M25G1	99
308M25G34	99
308M32G1	99
308M32G114	99
308M38G112	99
308M38G114	99
308M6G14	99
308M6G18	99
308M8G14	99
308M8G18	99
309M10N12	99
309M10N14	99
309M10N18	99
309M10N38	99
309M12N12	99
309M12N14	99
309M12N34	99
309M12N38	99
309M16N12	99
309M16N34	99
309M16N38	99
309M18N1	99
309M18N34	99
309M22N34	99
309M25N1	99
309M25N34	99
309M32N1	99
309M32N114	99
309M38N112	99
309M38N114	99
309M6N12	99
309M6N14	99
309M6N18	99
309M8N14	99
309M8N18	99
30JMTS	80
30KAAW13SPN	369
30KAAW17SPN	369
30KAAW21SPN	369
30KAIW13SPN	369
30KAIW17SPN	369
30KAIW21SPN	369
30KATF08SPN	369
30KATF10SPN	369
30SFAW13SXN	369
30SFAW17SXN	369
30SFAW21SXN	369
30SFIW13SXN	369
30SFIW17SXN	369
30SFIW21SXN	369
30SFTF06SXN	369
30SFTF08SXN	369
30SFTF10SXN	369
30SFTF13SXN	369
31/2-ORING	108
31020	1742
31025	1742
31030	1742
31095	1742
310M10U916	99
310M12U34	99
310M16U78	99
310M18U1116	99
310M22U1316	99
310M25U1516	99
310M32U158	99
310M38U178	99
310M6U716	99
310M8U12	99
3110	490

Code	Page
31100	1742
31105	1742
3111	490
31120	1742
31125	1742
31130	1742
312/V	1224
312M10U916	99
312M12U34	99
312M16U78	99
312M18U1116	99
312M22U1316	99
312M25U1516	99
312M32U158	99
312M38U178	99
312M6U716	99
312M8U12	99
3132FO	1681
3132PG	1681
3134R	1538
31427	61
31429	61
31433	61
31434	61
314M10U916	99
314M12U34	99
314M16U78	99
314M18U1116	99
314M22U1316	99
314M25U1516	99
314M32U158	99
314M38U178	99
314M6U716	99
314M8U12	99
3160BLACK100	1589
3160BLACK50	1589
3160BLACK75	1589
3160SILVER100	1589
3160SILVER50	1589
3160WHITE100	1589
3160WHITE50	1589
31630-AA	1583
31631-AD	1581
31803	1746
3195E	1682
31970-AA	1581
31971-AA	1581
31972-AA	1581
31-PEIND	259
320103-000	1600
3206001	679
3206002	679
3206003	679
3206004	679
320M10U916	99
320M12U34	99
320M16U78	99
320M18U1116	99
320M22U1316	99
320M25U1516	99
320M32U158	99
320M38U178	99
320M6U716	99
320M8U12	99
321K3106-230AC	1038
321K3106-24DC	1038
321K3306-230AC	1038
321K3306-24DC	1038
321K3506-230AC	1038
321K3506-24DC	1038
321K3606-230AC	1038
321K3606-24DC	1038
321K3706-230AC	1038
321K3706-24DC	1038
32-2110AR	513
322K4106-24DC	1038
322K4506-230AC	1038
322K4506-24DC	1038
322K4606-230AC	1038
322K4606-24DC	1038
3237FM	1682
3270PP	1682
32933	1745
32975	1745
32985	1745
330-0038-0000	1442
330-0038-1002	1440
330-0050-0000	1442
330-0050-1002	1440
330-0065-0000	1442
330-0065-1002	1440
330-0075-0000	1442
330-0075-1002	1440
330-0100-0000	1442
330-0100-1002	1440
330-0125-0000	1442
330-0125-1002	1440
330-0150-0000	1442
330-0150-1002	1440
330-0160-1002	1440
330-0200-0000	1442
330-0200-1002	1440
330-0225-1002	1440
330-0250-1002	1440
330-0300-1002	1440
330-0350-1002	1440
330-0400-1002	1440
33055	1746
331.01.04.18	629
331.01.06.14	629
331.01.06.18	629
331.01.08.14	629
331.01.08.18	629
331.01.10.38	629
331.01.12.12	629
331.01.12.38	629
331.02.04.18	629
331.02.06.14	629
331.02.06.18	629
331.02.08.14	629
331.02.08.18	629
331.02.10.38	629
331.02.12.12	629
331.02.12.38	629
331.05.04	629
331.05.06	629
331.05.08	629
331.05.10	629
331.05.12	629
333-0050-0007	1441
333-0065-0007	1441
333-0075-0007	1441
333-0080-0007	1441
333-0100-0007	1441
333-0125-0007	1441
333-0150-0007	1441
333-0160-0007	1441
333-0180-0007	1441
333-0200-0007	1441
333-0250-0007	1441
334 011 02	594
334 011 02 U72	594
334 011 02 U73	594
334 011 02 U74	594
334 011 02 U76	594
334 011 02 U77	594
334 011 02 U7H	594
334 011 02 U7J	594
334 011 02 U7K	594
334 015 02	594
334 015 02 U72	594
334 015 02 U73	594
334 015 02 U74	594
334 015 02 U76	594
334 015 02 U77	594
334 015 02 U7H	594
334 015 02 U7J	594
334 015 02 U7K	594
334 033	607
334 035	607
334 E11 02	594
334 E11 02 U72	594
334 E11 02 U73	594
334 E11 02 U74	594
334 E11 02 U76	594
334 E11 02 U77	594
334 E11 02 U7H	594
334 E11 02 U7J	594
334 E11 02 U7K	594
334 E15 02	594
334 E15 02 U72	594
334 E15 02 U73	594
334 E15 02 U74	594
334 E15 02 U76	594
334 E15 02 U77	594
334 E15 02 U7H	594
334 E15 02 U7J	594
334 E15 02 U7K	594
338 011 02 U72	593
338 011 02 U73	593
338 011 02 U74	593
338 011 02 U76	593
338 011 02 U77	593
338 011 02 U7H	593
338 011 02 U7J	593
338 011 02 U7K	593
338 015 02	593
338 015 02 U72	593
338 015 02 U73	593
338 015 02 U74	593
338 015 02 U76	593
338 015 02 U77	593
338 015 02 U7H	593
338 015 02 U7J	593
338 015 02 U7K	593
338 033	607
338 035	607
338 895	561
338 896	561
338 897	561
338 900	561
338 905	561
338 910	561
338 915	561
338 945	559
338 955	559
338 965	559
338 975	561
338 976	561
338 977	561
338 990	561
33890	490
33891	490
33892	490
33893	490
33894	490
338D 015 02	593
338D 015 02 U72	593
338D 015 02 U73	593
338D 015 02 U74	593
338D 015 02 U76	593
338D 015 02 U77	593
338D 015 02 U7H	593
338D 015 02 U7J	593
338D 015 02 U7K	593
338L 033	607
338L 035	607
33973	464
33974	464
33975	464
33KAAK13SPN	370
33KAAK17SPN	370
33KAAK21SPN	370
33KAIW13SPN	370
33KAIW17SPN	370
33KAIW21SPN	370
33KATF06SPN	370
33KATF08SPN	370
33KATF13SPN	370
33SFAK13SXN	370
33SFAK17SXN	370
33SFAK21SXN	370
33SFIW13SXN	370
33SFIW17SXN	370
33SFIW21SXN	370
33SFTF06SXN	370
33SFTF08SXN	370
33SFTF10SXN	370
33SFTF13SXN	370
34000303	1205
34000304	1205
34000704	1205
34000705	1205
34000706	1205
34000707	1205
34002104	1205
34003604	1205
34005607	1205
34005704	1205
34005706	1205
34005707	1205
3402003	678
34022302	1205
34022303	1205
34027803	1205
34027804	1205
34027805	1205
34027806	1205
34027903	1205
34027904	1205
34027905	1205
34027906	1205
34027907	1205
34027909	1205
34033009	1205
34033016	1205
34033018	1205
34033019	1205
34033026	1205
34033027	1205
34034416	1205
34034610	1205
34034616	1205
34034617	1205
34034618	1205
34034619	1205
34034626	1205
34034635	1205
34034636	1205
34034809	1205
341N35-4818653D	1021
341N35-481865C2	1021
341N35-4958703D	1021
341N35-495870C2	1021
341N35-495905C2	1021
3437R	1538
34-3DVL	243
345.M1	599
34583	1020
3470001	680
3471009	1023
34718	463
34719	463
34720	464
34721	465
348 015 02	593
348 015 02 U72	593
348 015 02 U73	593
348 015 02 U74	593
348 015 02 U76	593
348 015 02 U77	593
348 015 02 U7H	593
348 015 02 U7J	593
348 015 02 U7K	593
3480002	678
3481001	679
3482008	680
3482805	1023
3482807	1023
3483008	679

Code	Page
3484008	681
348D 015 02	593
348D 015 02 U72	593
348D 015 02 U73	593
348D 015 02 U74	593
348D 015 02 U76	593
348D 015 02 U77	593
348D 015 02 U7H	593
348D 015 02 U7J	593
348D 015 02 U7K	593
34D-BRKT-ANGLED	429
34D-P016G-DA1-AA	429
34D-P016G-DD1-AA	429
34D-V101G-DA1-AA	429
34D-V101G-DD1-AA	429
34D-V110G-DA1-AA	429
34D-V110G-DD1-AA	429
34KAAK17SPN	371
34KAAK21SPN	371
34KAAK26SPN	371
34KAIW21SPN	371
34KAIW26SPN	371
34KATF10SPN	371
34KATF13SPN	371
34SFAK13SXN	371
34SFAK17SXN	371
34SFAK21SXN	371
34SFIW17SXN	371
34SFIW21SXN	371
34SFTF10SXN	371
34SFTF13SXN	371
34SFTF16SXN	371
350 000 1109	750
350 000 1209	750
350 000 1312	751
350 000 1405	752
350 000 2304	751
350 000 2311	750
350 000 3000	750
350 000 3100	750
350 000 3101	750
350 000 3102	750
350 000 3209	750
350 000 3239	750
350 000 3310	750
350 000 3311	750
350 000 3312	751
350 000 3321	750
350 000 3323	752
350 000 3331	751
350 000 3341	751
350 000 3342	751
350 000 3404	751
350 000 3405	751
350 000 3423	752
350 000 3441	751
350 000 3443	752
350 000 3504	751
350 000 3505	751
350 000 3523	752
350 000 3543	752
350 000 3614	752
350 000 3615	752
350 000 3616	752
350 000 3623	752
350 000 3660	753
350 000 3804	751
350 000 3805	751
350 000 3823	752
350 000 3841	751
350 000 3843	752
350 000 3904	751
350 000 3905	751
350 000 3923	752
350 000 3943	752
350 000 4014	752
350 000 4015	752
350 000 4016	752
350 000 4023	752
350 000 4304	751
350 000 4310	750
350 000 4311	750
350 000 4312	751
350 000 4323	752
350 000 4341	751
350 000 4811	750
350 000 4912	751
350 000 5209	750
350 002 1012	753
350 002 1112	753
350 002 3021	753
350 002 3022	753
350 002 3121	753
350 002 3122	753
350 005 0101	753
350 005 0103	753
350 005 0202	753
350 005 0204	753
350 005 0302	753
350 005 0304	753
350 007 0101	753
350 007 0102	753
350 007 0103	753
350 010 1209	750
350 010 1312	751
350 010 2304	751
350 010 3102	750
350 010 3310	750
350 010 3311	750
350 010 3312	751
350 010 3341	751
350 010 3342	751
350 010 3404	751
350 010 3405	751
350 010 3441	751
350 010 3504	751
350 010 3505	751
350 010 3543	752
350 010 4209	750
350 020 3310	750
350 020 3311	750
350 020 3323	752
350 020 3614	752
350 020 3615	752
350 020 4209	750
350-0038-0000	1442
350-0038-1002	1440
350-0050-0000	1442
350-0050-1002	1440
350-0065-0000	1442
350-0065-1002	1440
350-0075-0000	1442
350-0075-1002	1440
350-0100-0000	1442
350-0100-1002	1440
350-0125-0000	1442
350-0125-1002	1440
350-0150-0000	1442
350-0150-1002	1440
350-0160-0000	1442
350-0160-1002	1440
350-0175-0000	1442
350-0175-1002	1440
350-0200-0000	1442
350-0200-1002	1440
350-0225-0000	1442
350-0225-1002	1440
350-0250-0000	1442
350-0250-1002	1440
350-0300-0000	1442
350-0300-1002	1440
3502003	678
351.01.06.06	629
351.01.08.08	629
351.01.10.10	629
351.01.12.12	629
351.03.06.14	629
351.03.06.18	629
351.03.08.14	629
351.03.08.18	629
351.03.08.38	629
351.03.10.12	629
351.03.10.14	629
351.03.10.38	629
351.03.12.12	629
351.03.12.38	629
351.04.06.06	629
351.04.08.08	629
351.04.12.12	629
351.06.06.14	629
351.06.06.18	629
351.06.08.14	629
351.06.08.18	629
351.06.08.38	629
351.06.10.12	629
351.06.10.14	629
351.06.10.38	629
351.06.12.12	629
351.06.12.38	629
351-0038-0000	1442
351-0050-0000	1442
351-0065-0000	1442
351-0075-0000	1442
351-0100-0000	1442
351-0125-0000	1442
351-0150-0000	1442
351-0175-0000	1442
351-0200-0000	1442
351-0250-0000	1442
351-0300-0000	1442
354 011 02	595
354 011 02 U72	595
354 011 02 U73	595
354 011 02 U74	595
354 011 02 U76	595
354 011 02 U77	595
354 011 02 U7H	595
354 011 02 U7J	595
354 011 02 U7K	595
354 015 02	595
354 015 02 U72	595
354 015 02 U73	595
354 015 02 U74	595
354 015 02 U76	595
354 015 02 U77	595
354 015 02 U7H	595
354 015 02 U7J	595
354 015 02 U7K	595
354 033	607
354 035	607
354 E11 02	595
354 E11 02 U72	595
354 E11 02 U73	595
354 E11 02 U74	595
354 E11 02 U76	595
354 E11 02 U77	595
354 E11 02 U7H	595
354 E11 02 U7J	595
354 E11 02 U7K	595
354 E15 02	595
354 E15 02 U72	595
354 E15 02 U73	595
354 E15 02 U74	595
354 E15 02 U76	595
354 E15 02 U77	595
354 E15 02 U7H	595
354 E15 02 U7J	595
354 E15 02 U7K	595
355-0038-1001	1443
355-0050-0000	1441
355-0050-1001	1443
355-0065-0000	1441
355-0065-1001	1443
355-0075-0000	1441
355-0075-1001	1443
355-0100-0000	1441
355-0100-1001	1443
355-0125-0000	1441
355-0125-1001	1443
355-0150-0000	1441
355-0150-1001	1443
355-0160-0000	1441
355-0180-1001	1443
355-0200-0000	1441
355-0200-1001	1443
355-0250-0000	1441
355-0250-1001	1443
355-0300-0000	1441
355-0300-1001	1443
356-0050-0000	1441
356-0065-0000	1441
356-0075-0000	1441
356-0080-0000	1441
356-0100-0000	1441
356-0125-0000	1441
356-0150-0000	1441
356-0160-0000	1441
356-0180-0000	1441
356-0200-0000	1441
3570001	680
358 011 02	593
358 011 02 U72	593
358 011 02 U73	593
358 011 02 U74	593
358 011 02 U76	593
358 011 02 U77	593
358 011 02 U7H	593
358 011 02 U7J	593
358 011 02 U7K	593
358 015 02	593
358 015 02 U72	593
358 015 02 U73	593
358 015 02 U74	593
358 015 02 U76	593
358 015 02 U77	593
358 015 02 U7H	593
358 015 02 U7J	593
358 015 02 U7K	593
358 033	607
358 035	607
358 895	561
358 896	561
358 897	561
358 900	562
358 905	562
358 910	561
358 915	561
358 945	559
358 955	559
358 965	559
358 975	561
358 976	561
358 977	561
358 990	561
3580002	678
3581001	679
3582008	680
3583008	679
3584008	681
36000502	1204
36000504	1204
36000505	1204
36000508	1204
36000510	1204
36000511	1204
36000512	1204
36000513	1204
36000520	1204
36000521	1204
36000529	1204
36000530	1204
3602003	678
36050002	1204
36050003	1204
36050004	1204
36050005	1204
36050006	1204
36050007	1204
36050008	1204
36050102	1204

Code	Page
36050103	**1204**
36050105	**1204**
36050106	**1204**
36050107	**1204**
36050108	**1204**
36050302	**1203**
36050304	**1203**
36050305	**1203**
36050306	**1203**
36050307	**1203**
36050402	**1204**
36050404	**1204**
36050405	**1204**
36050411	**1204**
36050412	**1204**
36050413	**1204**
36050420	**1204**
36050421	**1204**
36050428	**1204**
36050429	**1204**
36050430	**1204**
36050502	**1204**
36050510	**1204**
36050511	**1204**
36050512	**1204**
36050521	**1204**
36050530	**1204**
36050804	**1203**
36050805	**1203**
36050806	**1203**
36050807	**1203**
36050902	**1203**
36050905	**1203**
36050906	**1203**
36050907	**1203**
36051104	**1204**
36051107	**1204**
36051404	**1204**
36051405	**1204**
36051406	**1204**
36051407	**1204**
36051727	**1203**
36051728	**1203**
36051747	**1203**
36051749	**1203**
36051757	**1203**
36052001	**1203**
36052003	**1203**
36052005	**1203**
36052006	**1203**
36052007	**1203**
36052105	**1203**
36052111	**1203**
36052424	**1203**
36052425	**1203**
36052442	**1203**
36053002	**1204**
36053004	**1204**
36053005	**1204**
36053006	**1204**
36053008	**1204**
36053010	**1204**
36053011	**1204**
36053012	**1204**
36053013	**1204**
36053019	**1204**
36053020	**1204**
36053028	**1204**
36053029	**1204**
36053030	**1204**
36053044	**1204**
36053104	**1203**
36053110	**1203**
36053111	**1203**
36053112	**1203**
36054804	**1204**
36054805	**1204**
36054905	**1204**
36055104	**1204**
36055105	**1204**
36055106	**1204**
36055107	**1204**
36055205	**1203**
36055502	**1204**
36055510	**1204**
36055512	**1204**
36055520	**1204**
36055605	**1203**
36055611	**1203**
36055711	**1203**
36055712	**1203**
36055721	**1203**
36062507	**1203**
36092	**1746**
36112	**1746**
36127	**1746**
3615P	**1682**
361760	**223**
364 011 02	**595**
364 011 02 U72	**595**
364 011 02 U73	**595**
364 011 02 U74	**595**
364 011 02 U76	**595**
364 011 02 U77	**595**
364 011 02 U7H	**595**
364 011 02 U7J	**595**
364 011 02 U7K	**595**
364 033	**607**
364 E11 02	**595**
364 E11 02 U72	**595**
364 E11 02 U73	**595**
364 E11 02 U74	**595**
364 E11 02 U76	**595**
364 E11 02 U77	**595**
364 E11 02 U7H	**595**
364 E11 02 U7J	**595**
364 E11 02 U7K	**595**
3670001	**680**
368 011 02	**594**
368 011 02 U72	**594**
368 011 02 U73	**594**
368 011 02 U74	**594**
368 011 02 U76	**594**
368 011 02 U77	**594**
368 011 02 U7H	**594**
368 011 02 U7J	**594**
368 011 02 U7K	**594**
368 033	**607**
368 900	**562**
368 905	**562**
3680002	**678**
3681001	**679**
3682008	**680**
3683008	**679**
3684008	**681**
37000	**70**
37001	**70**
37002	**70**
37004	**70**
37006	**70**
3700A-00	**227**
372-0025-0000	**1446**
372-0032-0000	**1446**
372-0038-0000	**1446**
372-0051-0000	**1446**
372-0063-0000	**1446**
372-0076-0000	**1446**
373-0032-0000	**1446**
373-0032-1002	**1446**
373-0038-0000	**1446**
373-0038-1002	**1446**
373-0050-0000	**1446**
373-0050-1002	**1446**
37307	**1550**
37359	**1550**
37368	**1550**
374 011 02	**595**
374 011 02 U72	**595**
374 011 02 U73	**595**
374 011 02 U74	**595**
374 011 02 U76	**595**
374 011 02 U77	**595**
374 011 02 U7H	**595**
374 011 02 U7J	**595**
374 011 02 U7K	**595**
374 033	**607**
374 E11 02	**595**
374 E11 02 U72	**595**
374 E11 02 U73	**595**
374 E11 02 U74	**595**
374 E11 02 U76	**595**
374 E11 02 U77	**595**
374 E11 02 U7H	**595**
374 E11 02 U7J	**595**
374 E11 02 U7K	**595**
3740R	**1538**
378 011 02	**594**
378 011 02 U72	**594**
378 011 02 U73	**594**
378 011 02 U74	**594**
378 011 02 U76	**594**
378 011 02 U77	**594**
378 011 02 U7H	**594**
378 011 02 U7J	**594**
378 011 02 U7K	**594**
378 033	**607**
378 900	**562**
378 905	**562**
38053	**1746**
38058	**1746**
38063	**1746**
381-0012-0000	**1443**
381-0016-0000	**1443**
381-0018-0000	**1443**
381-0020-0000	**1443**
381-0025-0000	**1443**
381-0032-0000	**1443**
381-0038-0000	**1443**
381-0050-0000	**1443**
381-0065-0000	**1443**
381-0076-0000	**1443**
381-0102-0000	**1443**
38270	**1549**
38271	**1549**
38272	**1549**
38273	**1549**
38274	**1549**
38275	**1549**
38276	**1549**
38277	**1549**
38278	**1549**
38279	**1549**
38282	**1549**
38283	**1549**
38284	**1549**
38-3DVL	**243**
38-3DVT	**243**
384 033	**607**
38451	**1549**
38452	**1549**
38453	**1549**
38454	**1549**
38455	**1549**
38456	**1549**
38457	**1549**
38458	**1549**
38459	**1549**
38460	**1549**
38461	**1549**
38462	**1549**
38463	**1549**
38464	**1549**
38465	**1549**
38467	**1549**
38468	**1549**
38469	**1549**
38470	**1549**
38471	**1549**
38473	**1549**
38475	**1550**
38476	**1550**
38477	**1550**
38478	**1550**
38479	**1550**
38480	**1550**
38481	**1550**
38482	**1550**
38483	**1550**
38484	**1550**
38485	**1550**
38486	**1550**
38487	**1550**
38488	**1550**
38489	**1550**
38490	**1550**
38491	**1550**
38492	**1550**
38493	**1550**
38494	**1550**
38495	**1550**
38496	**1550**
38497	**1550**
38-4DVOC	**243**
385-0025-0000	**1444**
385-0032-0000	**1444**
385-0038-0000	**1444**
385-0040-0000	**1444**
385-0050-0000	**1444**
385-0060-0000	**1444**
385-0075-0000	**1444**
385-0100-0000	**1444**
38571	**1550**
38572	**1550**
38573	**1550**
38574	**1550**
38575	**1550**
38576	**1550**
38579	**1550**
38580	**1550**
38581	**1550**
38582	**1550**
38584	**1550**
38586	**1550**
38587	**1550**
38588	**1550**
38590	**1550**
38592	**1550**
38671	**1549**
38672	**1549**
38673	**1549**
38674	**1549**
38675	**1549**
38676	**1549**
38677	**1549**
38678	**1549**
38679	**1549**
38680	**1549**
38681	**1549**
38682	**1549**
38683	**1549**
38684	**1549**
38685	**1549**
38686	**1549**
3869-02-SPG	**69**
3869-04-SPG	**69**
3869-06-SPG	**69**
3869-08-SPG	**69**
3869-12-SPG	**69**
3869-M10-SPG	**69**
3869-M14-SPG	**69**
3869-M16-SPG	**69**
3869-M22-SPG	**69**
3869-M26-SPG	**69**
388 011 02	**594**
388 011 02 U72	**594**
388 011 02 U73	**594**
388 011 02 U74	**594**
388 011 02 U76	**594**
388 011 02 U77	**594**
388 011 02 U7H	**594**

Code	Page
388 011 02 U7J	594
388 011 02 U7K	594
388 033	607
38-DVCC	243
38JMTS	80
39000	1549
390-0038-0000	1445
390-0038-2005	1445
390-0051-0000	1445
390-0051-2005	1445
390-0063-0000	1445
390-0063-2005	1445
390-0076-0000	1445
390-0076-2005	1445
39001	1549
390-0102-0000	1445
390-0102-2005	1445
390-0127-0000	1445
390-0127-2005	1445
390-0152-0000	1445
390-0152-2005	1445
39002	1549
390-0203-0000	1445
390-0203-2005	1445
39003	1549
39004	1549
39005	1549
39006	1549
39007	1549
39008	1549
39009	1549
39010	1549
39011	1549
39012	1549
39013	1549
39014	1549
39015	1549
39016	1549
39017	1549
39018	1549
39019	1549
39020	1549
39022	1549
391-0038-0000	1445
391-0038-2005	1445
391-0051-0000	1445
391-0051-2005	1445
391-0063-0000	1445
391-0063-2005	1445
391-0076-0000	1445
391-0076-2005	1445
391-0102-0000	1445
391-0102-2005	1445
391-0127-0000	1445
391-0127-2005	1445
391-0152-0000	1445
391-0152-2005	1445
391-0203-0000	1445
391-0203-2005	1445
392669	223
393536	223
3968922	1050
3968924	1050
3968926	1050
3990296	660
3992150	660
3B0202	62
3B0204	62
3B0206	62
3B0404	62
3B0406	62
3B0606	62
3B0612	62
3B0616	62
3B0804	62
3B0806	62
3B0808	62
3B0810	62
3B0812	62
3B1006	62
3B1010	62
3B1210	62
3B1212	62
3B1216	62
3B1608	62
3B1616	62
3B1620	62
3B1624	62
3B2012	62
3B2020	62
3B2424	62
3B2432	62
3B3232	62
3BJ0407	75
3BJ0408	75
3BJ0409	75
3BJ0607	75
3BJ0608	75
3BJ0609	75
3BJ0612	75
3BJ0614	75
3BJ0809	75
3BJ0812	75
3BJ0814	75
3BJ0817	75
3BJ1014	75
3BJ1212	75
3BJ1217	75
3BJ1221	75
3BJ1617	75
3BJ1621	75
3BJ2026	75
3BM0412	62
3BM0414	62
3BM0612	62
3BM0614	62
3BM0616	62
3BM0618	62
3BM0620	62
3BM0622	62
3BM0816	62
3BM0818	62
3BM0822	62
3EV10V10	597
3EV10V20-110	597
3FCVP06	246
3FCVP08	246
3FCVP12	246
3FCVP16	246
3FCVT06	246
3FCVT08	246
3FCVT12	246
3J0707	75
3J0709	75
3J0712	75
3J0808	75
3J0809	75
3J0909	75
3J0912	75
3J1212	75
3J1409	75
3J1412	75
3J1414	75
3J1717	75
3J1721	75
3J1919	75
3J2121	75
3J2626	75
3-MS	1517
3-MS-BOX	1517
3-ORING	108
3-SS	1517
3WAY-14	1163
3WAY-18	1163
3WAY-8MM	1163
3X-MS	1517
3X-SS	1517
4	
400-3012	1090
400-3015	1090
400-3018	1090
400-3022	1090
400-3028	1090
400T-40-1	992
400T-40-2	992
400T-40-3	992
400T-40-4	992
400T-40-5	992
400T-40-6	992
40-2110AR	513
4043R	1538
4046082	1017
40500A3	1660
405-1015	1090
405-1022	1090
405-1028	1090
40525A3	1660
40617	1745
406N1PA12D	237
406N1PA12I	237
406N22PA12D	237
406N22PA12I	237
406N2PA12D	237
406N2PA12I	237
406N35RA12D	237
406N35RA12I	237
4092.17.00	1066
4092.25.00	1066
4092.40.00	1066
4092.50.00	1066
4092.63.00	1066
40KAIW17MPX	372
40KAIW21MPX	372
40M2L160A0050	509
40M2L160A0080	509
40M2L160A0100	509
40M2L160A0150	509
40M2L160A0200	509
40M2L160A0250	509
40M2L160A0300	509
40M2L160A0400	509
40M2L160A0500	509
40M2L160A0600	509
40M2L160A0700	509
40M2L160A0800	509
40M2L160A0900	509
40M2L160A1000	509
40M2L160A1250	509
40M2L160A1500	509
40M2L160A1750	509
40M2L160A2000	509
40M2L200A0050	509
40M2L200A0080	509
40M2L200A0100	509
40M2L200A0150	509
40M2L200A0200	509
40M2L200A0250	509
40M2L200A0300	509
40M2L200A0400	509
40M2L200A0500	509
40M2L200A0600	509
40M2L200A0700	509
40M2L200A0800	509
40M2L200A0900	509
40M2L200A1000	509
40M2L200A1250	509
40M2L200A1500	509
40M2L200A1750	509
40M2L200A2000	509
40SFAK17SXN	372
40SFIW17SXN	372
40SFIW21SXN	372
40SFTF08SXN	372
40SFTF10SXN	372
40SFTF13SXN	372
410-1522	1090
412/2.52.0.0.M2	598
412/2.52.0.1.M2	598
4121	252
412-1/4	391
41262-28	73
41270-20	73
41270-22	73
41275-10	73
4149944	528
4149945	528
4149946	528
4149947	528
415-08	391
415-10	391
415-12	391
4154768	528
4154769	528
4154770	528
4154799	528
416-08	391
416-12	391
418-10	391
418-12	391
41KFAW21MPN	373
41KFIW21MPN	373
41KFTF13MPN	373
41KFTF16MPN	373
41KFTF19MPN	373
41SFAW21MXN	373
41SFAW26MXN	373
41SFIW21MXN	373
41SFIW26MXN	373
41SFTF10MXN	373
41SFTF13MXN	373
41SFTF16MXN	373
41SFTF19MXN	373
422-12	391
425-13	391
425-16	391
43030	228
434 900	562
434 905	562
434 910	562
434 915	562
4346R	1538
4402002	678
44025	1568
44037	1568
4411-025-000	1444
4411-032-000	1444
4411-038-000	1444
4411-040-000	1444
4411-050-000	1444
4411-060-000	1444
4411-065-000	1444
4411-080-000	1444
44116	1568
44201	1568
44506	1568
4470001	680
4480002	678
4481001	679
4482005	680
4483005	679
448-3038-000	1443
448-3040-000	1443
448-3050-000	1443
4484005	681
4500400100	909
4500600100	909
4502002	678
454 900	563
454 905	563
454 910	562
454 915	562
4570001	680
457911	219
457942	219
457977	219
4580002	678
4581001	679
4582005	680
4583005	679
4584005	681

Code	Page
4589003	**676**
459215	**215**
45KFIW17MVX	**374**
45SFAW17SXN	**374**
45SFIW17SXN	**374**
4600952159	**909**
4601000100	**909**
4602002	**678**
464 900	**563**
464 905	**563**
4670001	**680**
467087	**114**
467088	**114**
467089	**114**
467090	**114**
467091	**114**
467092	**114**
467093	**114**
467094	**114**
467095	**114**
467096	**114**
467114	**114**
467115	**114**
467116	**114**
467117	**114**
467118	**114**
467119	**114**
467120	**114**
467121	**114**
467127	**114**
467128	**114**
467129	**114**
467130	**114**
467131	**114**
467133	**114**
467134	**114**
4680002	**678**
4681001	**679**
4682005	**680**
4683005	**679**
4684005	**681**
469.23-5.0BAR	**986**
469.24-7.0BAR	**986**
469.24-9.0BAR	**986**
469.25-11.0BAR	**986**
469.26-16.0BAR	**986**
469.27-20.0BAR	**986**
469.33-5.0BAR	**986**
469.34-7.0BAR	**986**
469.34-9.0BAR	**986**
469.35-11.0BAR	**986**
469.36-16.0BAR	**986**
469.37-20.0BAR	**986**
474 900	**563**
474 905	**563**
475 05	**977**
475 06	**977**
475 07	**977**
475 08	**977**
475 09	**977**
475 10	**977**
475 11	**977**
475 12	**977**
475 13	**977**
475 14	**977**
475 16	**977**
476 04	**977**
476 05	**977**
476 06	**977**
476 07	**977**
476 08	**977**
476 09	**977**
476 10	**977**
476 11	**977**
476 12	**977**
476 13	**977**
476 14	**977**
476 16	**977**
479 04	**975**
479 05	**975**
479 06	**975**
479 07	**975**
479 08	**975**
479 09	**975**
479 10	**975**
479 11	**975**
479 12	**975**
479 13	**975**
479 14	**975**
479 16	**975**
48.250.00.10.00	**704**
48.250.00.10.10	**704**
48.250.00.50.00	**704**
48.250.00.50.10	**704**
48002	**1502**
48003	**1502**
48006	**1502**
48008	**1502**
48010	**1502**
48013	**1501**
48014	**1501**
48015	**1501**
48022	**1501**
48023	**1501**
48024	**1501**
48026	**1501**
48027	**1501**
48030	**1501**
48031	**1501**
48032	**1501**
48034	**1501**
48041	**1502**
48042	**1502**
48043	**1502**
48473-A00	**228**
48KBAW13FVX	**375**
48KBAW17DPX	**375**
48KBAW17FVX	**375**
48KBAW21DPX	**375**
48KBIW13DPX	**375**
48KBIW17DPX	**375**
48KBIW21FVX	**375**
48KBTF06DPX	**375**
48KBTF06FVX	**375**
48KBTF09DPX	**375**
48KBTF13DPX	**375**
48KBTF13FVX	**375**
48SBIW17DPX	**376**
48SBIW21FVX	**376**
48SBTF06DPX	**376**
48SBTF09DPX	**376**
48SFAW13DXX	**376**
48SFAW13FXX	**376**
48SFAW17FXX	**376**
48SFIW13DXX	**376**
48SFIW17DXX	**376**
48SFTF09FXX	**376**
48SFTF13DXX	**376**
4-946-00-05-020	**271**
4-999-03-01-160	**271**
4B0602	**59**
4B0802	**59**
4B0804	**59**
4B1204	**59**
4B1206	**59**
4B1604	**59**
4B1606	**59**
4B1608	**59**
4B2008	**59**
4B2012	**59**
4B2016	**59**
4B2408	**59**
4B2412	**59**
4B2416	**59**
4B3216	**59**
4B3220	**59**
4B3224	**59**
4B4024	**59**
4B4032	**59**
4B4832	**59**
4BG02	**60**
4BG0204	**60**
4BG0206	**60**
4BG04	**60**
4BG0402	**60**
4BG0406	**60**
4BG0408	**60**
4BG06	**60**
4BG0602	**60**
4BG0604	**60**
4BG0608	**60**
4BG08	**60**
4BG0804	**60**
4BG0806	**60**
4BG0812	**60**
4BG0816	**60**
4BG1208	**60**
4BG1612	**60**
4BN0802	**59**
4BN0804	**59**
4BN1206	**59**
4BN1604	**59**
4BN1608	**59**
4BN2016	**59**
4BN2416	**59**
4BN4032	**59**
4BN4832	**59**
4BX02	**58**
4BX0204	**58**
4BX0206	**58**
4BX0208	**58**
4BX04	**58**
4BX0402	**58**
4BX0406	**58**
4BX0408	**58**
4BX0412	**58**
4BX06	**58**
4BX0604	**58**
4BX0608	**58**
4BX0612	**58**
4BX08	**58**
4BX0806	**58**
4BX0812	**58**
4BX0816	**58**
4BX0820	**58**
4BX12	**58**
4BX1208	**58**
4BX1216	**58**
4BX1224	**58**
4BX16	**58**
4BX1612	**58**
4BX1620	**58**
4BX1624	**58**
4BX2020	**58**
4BX2024	**58**
4BX2032	**58**
4BX24	**58**
4BX2420	**58**
4G-12G-MF-A-10K	**91**
4G-12G-MM-10K	**90**
4G-12N-MM-10K	**90**
4G-16G-MF-A-10K	**91**
4G-16G-MM-10K	**90**
4G-16N-MM-10K	**90**
4G-2G-MF-B-10K	**92**
4G-2N-MM-10K	**90**
4G-4G-FF-10K	**92**
4G-4G-MF-A-10K	**91**
4G-4G-MM-10K	**90**
4G-4J-MF-10K	**91**
4G-4J-MM-10K	**90**
4G-4N-MM-10K	**90**
4G-5J-MF-10K	**91**
4G-6G-FF-10K	**92**
4G-6G-MF-A-10K	**91**
4G-6G-MM-10K	**90**
4G-6J-MF-10K	**91**
4G-6J-MM-10K	**90**
4G-6N-MM-10K	**90**
4G-8G-FF-10K	**92**
4G-8G-MF-A-10K	**91**
4G-8G-MM-10K	**90**
4G-8J-MM-10K	**90**
4G-8N-MM-10K	**90**
4G-C-10K	**94**
4G-E-FF-10K	**93**
4G-E-MF-10K	**93**
4G-E-MM-10K	**92**
4G-P-10K	**94**
4G-T-FF-10K	**94**
4G-T-MM-10K	**93**
4J-2N-MF-A-10K	**91**
4J-4J-FF-10K	**92**
4J-4J-MF-10K	**91**
4J-4J-MM-10K	**90**
4J-4N-MF-A-10K	**91**
4J-6J-FF-10K	**92**
4J-6J-MF-10K	**91**
4J-6J-MM-10K	**90**
4J-6N-MF-A-10K	**91**
4J-8J-FF-10K	**92**
4J-8J-MF-10K	**91**
4J-8J-MM-10K	**90**
4J-C-10K	**94**
4J-E-FF-10K	**93**
4J-E-MF-10K	**93**
4JITS	**80**
4J-P-10K	**94**
4J-T-FF-10K	**94**
4J-T-MM-10K	**93**
4JTN	**80**
4-MS	**1517**
4N-12N-FF-10K	**92**
4N-12N-MF-A-10K	**91**
4N-16N-FF-10K	**92**
4N-16N-MF-A-10K	**91**
4N-2N-MF-B-10K	**92**
4N-4J-E-MF-10K	**93**
4N-4J-MF-10K	**91**
4N-4J-MM-10K	**90**
4N-4N-FF-10K	**92**
4N-4N-MF-A-10K	**91**
4N-4N-MM-10K	**90**
4N-6J-MM-10K	**90**
4N-6N-FF-10K	**92**
4N-6N-MF-A-10K	**91**
4N-6N-MM-10K	**90**
4N-8J-MM-10K	**90**
4N-8N-FF-10K	**92**
4N-8N-MF-A-10K	**91**
4N-8N-MM-10K	**90**
4N-C-10K	**94**
4N-E-10K	**93**
4N-E-MF-10K	**93**
4N-E-MM-10K	**92**
4N-P-10K	**94**
4N-T-10K	**94**
4N-T-MM-10K	**93**
4N-X-10K	**94**
4-ORING	**108**
4SH-12-40	**12**
4SH-16-40	**12**
4SP-04-40	**11**
4SP-06-40	**11**
4SP-08-40	**11**
4SP-10-40	**11**
4SP-12-40	**11**
4SP-16-40	**11**
4SP-20-40	**11**
4SP-24-40	**11**
4SP-32-40	**11**
4-SS	**1517**
4X-MS	**1517**
4X-SS	**1517**
5	
5/16SCV	**884**
50.780.00.10.00	**704**
50.780.00.10.10	**704**
50.780.00.25.00	**704**
50.780.00.80.00	**704**

Code	Page
50.880.00.40.00	**704**
500-05	**1542**
500-06	**1542**
500-08	**1542**
500-09	**1542**
50010	**1551**
500-10	**1542**
500-10SS	**1542**
500-12	**1542**
500-13	**1542**
500-13SS	**1542**
500-15-1	**988**
500-15-10	**988**
500-15-10.5	**988**
500-15-11	**988**
500-15-11.5	**988**
500-15-3	**988**
500-15-4	**988**
500-15-5	**988**
500-15-5.5	**988**
500-15-6	**988**
500-15-6.5	**988**
500-15-7	**988**
500-15-7.5	**988**
500-15-8.5	**988**
500-16	**1542**
500-16SS	**1542**
500-19	**1542**
500-19SS	**1542**
5002000N01	**817**
5002000N02	**817**
5002000N03	**817**
5002000N04	**817**
5002000N05	**817**
5002000N06	**817**
5002000N07	**817**
5002000N08	**817**
5002000N09	**817**
5002000N11	**817**
5002000N12	**817**
5002000N13	**817**
5002000N14	**817**
5002000N17	**817**
5002000N18	**817**
5002000N19	**817**
5002000N20	**817**
5002000N22	**817**
5002000N23	**817**
5002000N24	**817**
5002000N25	**817**
5002000N27	**817**
5002000N28	**817**
5002000N29	**817**
5002000N31	**817**
5002000N32	**817**
500-20-1.5	**988**
500-20-10	**988**
500-20-11	**988**
500-20-11.5	**988**
500-20-12	**988**
500-20-12.5	**988**
500-20-2.5	**988**
500-20-3	**988**
500-20-3.5	**988**
500-20-4	**988**
500-20-5	**988**
500-20-5.5	**988**
500-20-6	**988**
500-20-6.5	**988**
500-20-7	**988**
500-20-7.5	**988**
500-20-8	**988**
500-20-8.5	**988**
500-20-9	**988**
500-21	**1542**
500-21SS	**1542**
500-22	**1542**
500-22SS	**1542**
500-25	**1542**
500-25-1.5	**988**
500-25-11	**988**
500-25-12.5	**988**
500-25-2	**988**
500-25-2.5	**988**
500-25-3	**988**
500-25-3.5	**988**
500-25-4	**988**
500-25-5.5	**988**
500-25-7	**988**
500-25-7.5	**988**
500-25-8	**988**
500-25-8.5	**988**
500-25SS	**1542**
500-28	**1542**
500-28SS	**1542**
500-29	**1542**
500-29SS	**1542**
5003000N01	**817**
5003000N02	**817**
5003000N03	**817**
5003000N04	**817**
5003000N05	**817**
5003000N06	**817**
5003000N08	**817**
5003000N09	**817**
5003000N10	**817**
5003000N11	**817**
5003000N12	**817**
5003000N13	**817**
5003000N14	**817**
5003000N15	**817**
500-32	**1542**
500-32-10	**988**
500-32-11	**988**
500-32-3	**988**
500-32-3.5	**988**
500-32-5	**988**
500-32-7.5	**988**
500-32-8.5	**988**
500-32SS	**1542**
500-35	**1542**
500-35SS	**1542**
500-40	**1542**
500-40-1.5	**988**
500-40-12	**988**
500-40-3	**988**
500-40-3.5	**988**
500-40-4	**988**
500-40-7	**988**
500-40-7.5	**988**
50040N10	**856**
50040N10-8	**856**
50040N12	**856**
50040N12-10	**856**
50040N4	**856**
50040N6	**856**
50040N6-4	**856**
50040N8	**856**
50040N8-6	**856**
500-40SS	**1542**
500-44	**1542**
500-44SS	**1542**
500-48	**1542**
500-48SS	**1542**
5005000N01	**817**
5005000N02	**817**
5005000N03	**817**
5005000N04	**817**
5005000N05	**817**
5005000N06	**817**
500-50-12.5	**988**
500-50-3.5	**988**
500-50-7	**988**
500-52	**1542**
500-52SS	**1542**
500-56	**1542**
500-56SS	**1542**
500-5SS	**1542**
500-60	**1542**
500-60SS	**1542**
500-6SS	**1542**
500-8SS	**1542**
500L-10-1	**989**
500L-10-1.5	**989**
500L-10-10	**989**
500L-10-11	**989**
500L-10-12	**989**
500L-10-12.5	**989**
500L-10-2	**989**
500L-10-2.5	**989**
500L-10-3	**989**
500L-10-3.5	**989**
500L-10-4	**989**
500L-10-5	**989**
500L-10-5.5	**989**
500L-10-6	**989**
500L-10-6.5	**989**
500L-10-8	**989**
500L-10-9.5	**989**
500L-15-1	**989**
500L-15-10	**989**
500L-15-10.5	**989**
500L-15-11	**989**
500L-15-11.5	**989**
500L-15-3	**989**
500L-15-4	**989**
500L-15-5	**989**
500L-15-5.5	**989**
500L-15-6	**989**
500L-15-6.5	**989**
500L-15-7	**989**
500L-15-7.5	**989**
500L-15-8.5	**989**
500L-20-1.5	**989**
500L-20-10	**989**
500L-20-11	**989**
500L-20-11.5	**989**
500L-20-12	**989**
500L-20-12.5	**989**
500L-20-2.5	**989**
500L-20-3	**989**
500L-20-3.5	**989**
500L-20-4	**989**
500L-20-5	**989**
500L-20-5.5	**989**
500L-20-6	**989**
500L-20-6.5	**989**
500L-20-7	**989**
500L-20-7.5	**989**
500L-20-8	**989**
500L-20-8.5	**989**
500L-20-9	**989**
500L-25-1.5	**989**
500L-25-11	**989**
500L-25-12.5	**989**
500L-25-2	**989**
500L-25-2.5	**989**
500L-25-3	**989**
500L-25-3.5	**989**
500L-25-4	**989**
500L-25-5.5	**989**
500L-25-7	**989**
500L-25-7.5	**989**
500L-25-8	**989**
500L-25-8.5	**989**
500L-32-10	**989**
500L-32-11	**989**
500L-32-3	**989**
500L-32-3.5	**989**
500L-32-5	**989**
500L-32-7.5	**989**
500L-32-8.5	**989**
500L-40-1.5	**989**
500L-40-12	**989**
500L-40-3	**989**
500L-40-3.5	**989**
500L-40-4	**989**
500L-40-7	**989**
500L-40-7.5	**989**
500L-50-12.5	**989**
500L-50-3.5	**989**
500L-50-7	**989**
500T-15-1	**992**
500T-15-2	**992**
500T-15-3	**992**
500T-15-4	**992**
500T-15-5	**992**
500T-15-6	**992**
500T-20-1	**992**
500T-20-2	**992**
500T-20-3	**992**
500T-20-4	**992**
500T-20-5	**992**
500T-20-6	**992**
500T-25-1	**992**
500T-25-2	**992**
500T-25-3	**992**
500T-25-4	**992**
500T-25-5	**992**
500T-25-6	**992**
500T-32-1	**992**
500T-32-2	**992**
500T-32-3	**992**
500T-32-4	**992**
500T-32-5	**992**
500T-32-6	**992**
500T-50-1	**992**
500T-50-2	**992**
500T-50-3	**992**
500T-50-4	**992**
500T-50-5	**992**
500T-50-6	**992**
50106N4-1/4	**856**
50106N4-1/8	**856**
50106N6-1/4	**856**
50106N6-1/8	**856**
50106N8-1/4	**856**
50106N8-1/8	**856**
50106N8-3/8	**856**
501-10	**1542**
501-10SS	**1542**
50111N10-1/2	**856**
50111N10-1/4	**856**
50111N10-3/8	**856**
50111N12-1/2	**856**
50111N12-3/8	**856**
50111N14-1/2	**856**
50111N14-3/8	**856**
50111N4-1/4	**856**
50111N4-1/8	**856**
50111N6-1/4	**856**
50111N6-1/8	**856**
50111N8-1/2	**856**
50111N8-1/4	**856**
50111N8-1/8	**856**
50111N8-3/8	**856**
501-12	**1542**
501-12SS	**1542**
501-13	**1542**
501-13SS	**1542**
501-16	**1542**
501-16SS	**1542**
501-19	**1542**
501-19SS	**1542**
501-21	**1542**
501-22	**1542**
501-25	**1542**
501-28	**1542**
501-28SS	**1542**
501-29	**1542**
50130N10	**856**
50130N12	**856**
50130N14	**856**
50130N4	**856**
50130N6	**856**
50130N8	**856**
501-32	**1542**
501-32SS	**1542**
501-35	**1542**
501-35SS	**1542**

Code	Page
501-40	1542
501-40SS	1542
501-48	1542
501-5	1542
501-52	1542
501-56	1542
501-6	1542
501-60	1542
501-60SS	1542
501-6SS	1542
501-8	1542
501-8SS	1542
501-9	1542
501-9SS	1542
50211N10-1/2	856
50211N10-1/4	856
50211N10-3/8	856
50211N12-1/2	856
50211N12-3/8	856
50211N14-1/2	856
50211N14-3/8	856
50211N4-1/4	856
50211N4-1/8	856
50211N6-1/4	856
50211N6-1/8	856
50211N8-1/2	856
50211N8-1/4	856
50211N8-1/8	856
50211N8-3/8	856
50223N10-1/2	856
50223N10-1/4	856
50223N10-3/8	856
50223N12-1/2	856
50223N12-3/8	856
50223N4-1/4	856
50223N4-1/8	856
50223N6-1/4	856
50223N6-1/8	856
50223N8-1/2	856
50223N8-1/4	856
50223N8-1/8	856
50223N8-3/8	856
50230N10	856
50230N12	856
50230N14	856
50230N4	856
50230N6	856
50230N8	856
5025-3PR	309
5029-3PR	309
50310N10	856
50310N4	856
50310N6	856
50310N8	856
50501	1551
5050-1/2	1174
505-10	1513
505-10SS	1513
505-11	1513
505-11SS	1513
505-12	1513
505-12SS	1513
505-13	1513
505-13SS	1513
505-14	1513
505-14SS	1513
505-15	1513
505-15SS	1513
505-16	1513
505-16SS	1513
505-17	1513
505-17SS	1513
505-18	1513
505-18SS	1513
50550N10-1/4	856
50550N10-3/8	856
50550N12-3/8	856
50550N4-1/8	856
50550N4-M5	856
50550N6-1/4	856
50550N6-1/8	856
50550N6-M5	856
50550N8-1/4	856
50550N8-1/8	856
50550N8-3/8	856
505-9	1513
505-9SS	1513
50700N10-4	856
50700N10-6	856
50700N10-8	856
50700N12-10	856
50700N12-8	856
50700N6-4	856
50700N8-4	856
50700N8-6	856
507825	219
507826	219
507833	219
507834	219
507847	219
507848	219
507852	219
507855	219
5101001	663
5101002	663
5101002F	665
510-12	1533
510-16	1533
510-20	1533
510-22	1533
510-25	1533
510-30	1533
5103001	663
510-35	1533
510-40	1533
5104008	663
5104011	663
510-45	1533
510-50	1533
5105008	663
5105011	663
5105111F	665
510-55	1533
510-60	1533
5106008	664
5106011	664
5107003	663
5107004	663
510-80	1533
5108001F	665
5108002F	665
5108003F	665
5108004F	665
5110003	663
5110004	663
511-14	391
511-18	391
511-38	391
5125	468
5126	468
5127	468
5128	468
513-BLUE	391
513-RED	391
51KBIW13SPN	377
51KBIW17SPN	377
51SFAW13SXN	377
51SFIW13SXN	377
51SFIW17SXN	377
5201001	663
5201002	663
5201002F	665
52021	54
5203001	663
5204008	663
5205008	663
5205011	663
5205102F	665
5205105F	665
5205111F	665
5205-4M	309
5206008	664
5206011	664
5207003	663
5207004	663
5208001F	665
5208002F	665
5208003F	665
5208004F	665
5209-4M	309
5210003	663
5210004	663
521-12	391
5211896	466
5211897	466
5211898	466
5211899	466
5211900	466
5211901	466
5211903	466
5211904	466
5211905	466
5211906	466
5211908	466
5211909	466
5212001	664
521-38	391
5216087	466
5216088	466
5216089	466
5216090	466
5216091	466
5216093	466
5216094	466
5216095	466
5216096	466
5216098	466
5216099	466
5216100	466
5216101	466
5217238	467
5217239	467
5217240	467
5217241	467
5217242	467
5217243	467
5217244	467
5217245	467
5217246	467
5217248	467
5224633	466
5224634	466
5224635	466
5224636	466
5224637	466
5224639	466
5224641	466
5224642	466
5224643	466
5224644	466
5224645	466
5224646	466
5224647	466
5225836	467
5225837	467
5225838	467
5225839	467
5225840	467
5225841	467
5225842	467
5225843	467
5225844	467
5225846	467
5228001F	665
5228002F	665
5228003F	665
5228004F	665
5228227	466
5228228	466
5228229	466
5228230	466
5228231	466
5228232	466
5228233	466
5228234	466
5228235	466
5228236	466
5228237	466
5228238	466
5228239	466
5228452	467
5228453	467
5228454	467
5228455	467
5228456	467
5228457	467
5228458	467
5228459	467
5228460	467
5228461	467
523-RED	391
526060	662
526063	662
526064	662
526069	662
526073	662
526074	662
526075	662
526082	662
526083	662
529144	659
529146	659
529148	659
529150	659
529152	659
529156	659
529158	659
529176	659
529178	659
529180	659
529182	659
529184	659
529188	659
529190	659
529192	659
529194	659
529415	659
529417	659
529419	659
529531	661
529761	211
529762	210
529763	210
529764	212
529765	212
529817	661
529853	662
529989	659
529991	659
529993	659
52KBAW13SPN	378
52KBAW17SPN	378
52KBAW21SPN	378
52KBIW13SPN	378
52KBIW17SPN	378
52KBIW21SPN	378
52KBTF11SPN	378
52SFAW17SXN	378
52SFTF06SXN	378
5300-107	1760
5300-108	1760
5300-109	1760
5300-110	1760
5300-111	1760
5300-207	1760
5300-208	1760
5300-209	1760
5300-210	1760
530029	816
530030	816

Code	Page
530031	**816**
530032	**816**
530033	**816**
530038	**816**
530039	**816**
530040	**816**
530041	**816**
530042	**816**
530043	**816**
530044	**816**
530045	**816**
530244	**658**
530338	**659**
530340	**659**
530AA	**1034**
530AC	**1034**
530AL	**1034**
531117	**658**
532184	**662**
532185	**662**
532186	**662**
532195	**662**
532196	**662**
532800	**662**
532801	**662**
533534-001	**1031**
533534-003	**1031**
533534-011	**1031**
533534-024	**1031**
533593-003	**1031**
533593-011	**1031**
533593-020	**1031**
534-1	**924**
534-112	**924**
534-114	**924**
534-12	**924**
534-14	**924**
534-2	**924**
534-3	**924**
534337	**815**
534338	**815**
534339	**815**
534-34	**924**
534340	**815**
534341	**815**
534342	**815**
534343	**815**
534344	**815**
534-38	**924**
53440A8	**1663**
53470A8	**1663**
53490A8	**1662**
5349BA8	**1662**
5349SA3	**1662**
534AA	**1034**
534AC	**1034**
534AE	**1034**
53500A3	**1662**
5350NA3	**1662**
5350SA3	**1662**
5351SA3	**1662**
53520A3	**1662**
5352NA3	**1662**
53530A3	**1662**

Code	Page
5353GA3	**1662**
5353NA3	**1662**
5353SA3	**1662**
5354SA3	**1662**
535615	**1020**
535720	**659**
535722	**659**
535724	**659**
53600A3	**1662**
5360AA3	**1662**
5360BA3	**1662**
5360CA3	**1662**
5360DA3	**1662**
53610A3	**1662**
53611A3	**1662**
5361AA3	**1662**
536204	**523**
536205	**523**
536206	**523**
536207	**523**
536208	**523**
536209	**523**
53620A3	**1662**
536210	**523**
536211	**523**
536212	**523**
536213	**523**
536214	**523**
536215	**523**
536216	**523**
536217	**523**
536219	**523**
536220	**523**
536221	**523**
536222	**523**
536223	**523**
536224	**523**
536225	**523**
536226	**523**
536227	**523**
536228	**523**
536229	**523**
536230	**523**
536231	**523**
536232	**523**
536234	**523**
536235	**523**
536236	**523**
536237	**523**
536238	**523**
536239	**523**
536240	**523**
536241	**523**
536242	**523**
536243	**523**
536244	**523**
536245	**523**
536246	**523**
536247	**523**
536248	**523**
536249	**523**
536251	**523**
536252	**523**
536253	**523**

Code	Page
536254	**523**
536255	**523**
536256	**523**
536257	**523**
536258	**523**
536259	**523**
536260	**523**
536261	**523**
536262	**523**
536263	**523**
536264	**523**
536265	**523**
536266	**523**
536268	**524**
536269	**524**
536270	**524**
536271	**524**
536272	**524**
536273	**524**
536274	**524**
536275	**524**
536276	**524**
536277	**524**
536278	**524**
536279	**524**
536280	**524**
536281	**524**
536282	**524**
536283	**524**
536284	**524**
536285	**524**
536286	**524**
536287	**524**
536289	**524**
536290	**524**
536291	**524**
536292	**524**
536293	**524**
536294	**524**
536295	**524**
536296	**524**
536297	**524**
536298	**524**
536299	**524**
536300	**524**
536301	**524**
536302	**524**
536303	**524**
536304	**524**
536305	**524**
536306	**524**
536307	**524**
536308	**524**
536310	**524**
536311	**524**
536312	**524**
536313	**524**
536314	**524**
536315	**524**
536316	**524**
536317	**524**
536318	**524**
536319	**524**
536320	**524**

Code	Page
536321	**524**
536322	**524**
536323	**524**
536324	**524**
536325	**524**
536326	**524**
536327	**524**
536328	**524**
536329	**524**
536331	**523**
536332	**524**
536333	**524**
536334	**524**
536335	**524**
536336	**524**
536337	**524**
536338	**524**
536339	**524**
536340	**524**
536341	**523**
536342	**524**
536343	**524**
536344	**524**
536345	**524**
536346	**524**
536347	**524**
536348	**524**
536349	**524**
536350	**524**
536352	**523**
536353	**524**
536354	**524**
536355	**524**
536356	**524**
536357	**524**
536358	**524**
536359	**524**
536360	**524**
536361	**524**
536362	**523**
536363	**524**
536364	**524**
536365	**524**
536366	**524**
536367	**524**
536368	**524**
536369	**524**
536370	**524**
536371	**524**
536373	**523**
536383	**523**
53640A3	**1662**
5364AA3	**1662**
5364BA3	**1662**
53650A3	**1662**
53670A3	**1662**
53690A3	**1662**
53700A3	**1662**
537075	**815**
537076	**815**
5371AA3	**1662**
53750A3	**1662**
53800A1	**1660**
5400A-00	**227**

Code	Page
54027-25	**1675**
5407772	**468**
5407787	**468**
5407847	**468**
541258	**661**
541259	**661**
541267	**661**
541268	**661**
541272	**661**
541333	**526**
541334	**468**
541338	**526**
541341	**526**
542-15-1	**990**
542-15-1.5	**990**
542-15-10	**990**
542-15-10.5	**990**
542-15-2	**990**
542-15-2.5	**990**
542-15-3	**990**
542-15-3.5	**990**
542-15-4	**990**
542-15-4.5	**990**
542-15-5	**990**
542-15-5.5	**990**
542-15-6	**990**
542-15-7	**990**
542-15-7.5	**990**
542-15-8	**990**
542-15-8.5	**990**
542-15-9	**990**
542-15-9.5	**990**
542-20-1	**990**
542-20-1.5	**990**
542-20-10	**990**
542-20-10.5	**990**
542-20-2	**990**
542-20-2.5	**990**
542-20-3	**990**
542-20-3.5	**990**
542-20-4	**990**
542-20-4.5	**990**
542-20-5	**990**
542-20-5.5	**990**
542-20-6	**990**
542-20-7	**990**
542-20-7.5	**990**
542-20-8	**990**
542-20-8.5	**990**
542-20-9	**990**
542-25-1	**990**
542-25-1.5	**990**
542-25-10	**990**
542-25-10.5	**990**
542-25-2	**990**
542-25-2.5	**990**
542-25-3	**990**
542-25-3.5	**990**
542-25-4	**990**
542-25-4.5	**990**
542-25-5	**990**
542-25-6	**990**
542-25-7	**990**
542-25-7.5	**990**

Code	Page
542-25-8	990
542-25-8.5	990
542-25-9	990
542-25-9.5	990
542-32-1	990
542-32-10	990
542-32-2.5	990
542-32-3	990
542-32-3.5	990
542-32-4	990
542-32-4.5	990
542-32-5	990
542-32-6.5	990
542-32-7	990
542-32-8	990
542-32-8.5	990
542-32-9	990
542-32-9.5	990
542-40-1	990
542-40-1.5	990
542-40-10	990
542-40-10.5	990
542-40-2	990
542-40-3.5	990
542-40-4	990
542-40-5	990
542-40-6	990
542-40-7	990
542-40-7.5	990
542-40-8	990
542-50-10	990
542-50-10.5	990
542-50-2	990
542-50-3.5	990
542-50-6	990
542-50-7	990
542-50-7.5	990
542-50-8	990
542578	661
542582	661
542598	661
542602	661
542-65-3	990
542-65-4	990
542-65-7.5	990
542F-32-1	992
542F-32-2	992
542F-32-3	992
542F-32-4	992
542F-32-6	992
542F-40-1	992
542F-40-2	992
542F-40-3	992
542F-40-4	992
542F-40-6	992
542F-50-1	992
542F-50-2	992
542F-50-3	992
542F-50-4	992
542F-50-6	992
542F-63-1	992
542F-63-2	992
542F-63-3	992
542F-63-4	992
542F-63-6	992
542F-80-1	992
542F-80-2	992
542F-80-3	992
542F-80-4	992
542F-80-6	992
542L-15-1	991
542L-15-1.5	991
542L-15-10	991
542L-15-10.5	991
542L-15-2	991
542L-15-2.5	991
542L-15-3	991
542L-15-3.5	991
542L-15-4	991
542L-15-4.5	991
542L-15-5	991
542L-15-6	991
542L-15-7	991
542L-15-8.5	991
542L-20-1	991
542L-20-1.5	991
542L-20-10	991
542L-20-2	991
542L-20-2.5	991
542L-20-3	991
542L-20-3.5	991
542L-20-5	991
542L-20-6	991
542L-20-6.5	991
542L-20-7	991
542L-20-8	991
542L-20-9	991
542L-25-1	991
542L-25-1.5	991
542L-25-10	991
542L-25-10.5	991
542L-25-2	991
542L-25-2.5	991
542L-25-3	991
542L-25-3.5	991
542L-25-4	991
542L-25-5	991
542L-25-6	991
542L-25-7	991
542L-25-8	991
542L-32-10	991
542L-32-10.5	991
542L-32-3	991
542L-32-4	991
542L-32-8	991
542L-40-1.5	991
542L-40-10	991
542L-40-2.5	991
542L-40-5	991
542L-40-6	991
542L-40-7	991
542L-50-1.5	991
542L-50-10	991
542L-50-10.5	991
542L-50-2	991
542L-50-4	991
542L-50-7.5	991
542L-50-8.5	991
542L-50-9.5	991
542L-65-2	991
542L-65-3	991
542L-65-3.5	991
542L-65-5	991
542L-80-4.5	991
542L-80-7	991
543211881300	682
543861	526
543862	526
543863	526
543872	526
54500A3	1665
5450SA3	1665
54520A3	1665
54530A3	1665
5453SA3	1665
54600A3	1665
5460AA3	1665
54610A3	1665
54611A3	1665
546146	1035
546147	1035
546148	1035
546149	1035
546150	1035
546151	1035
546152	1035
546153	1035
546162	1035
546163	1035
546164	1035
546165	1035
546166	1035
546167	1035
546168	1035
546169	1035
5461AA3	1665
546799	526
5474WHITE2X10	1589
549903	1036
549904	1036
549905	1036
549906	1036
549907	1036
549908	1036
54D-P016G-DA1-AA	429
54D-P016G-DD0-AA	429
54D-V101G-DA1-AA	429
54D-V101G-DD0-AA	429
54D-V110G-DA1-AA	429
54D-V110G-DD0-AA	429
5500000001	817
5500000002	817
5500000003	817
5500000004	817
5500000005	817
5500000006	817
5500000007	817
5500000008	817
5500000009	817
5500000010	817
5500000011	817
5500000012	817
5500000013	817
5500000014	817
5500000015	817
5500000016	817
5500000017	817
5500000018	817
5500000019	817
5500000020	817
550000DIS	1037
550001DIS	1037
550002DIS	1037
550003DIS	1037
550004DIS	1037
550005DIS	1037
550009DIS	1037
550010DIS	1037
550011DIS	1037
550013DIS	1037
550014DIS	1037
550015DIS	1037
550016DIS	1037
550017DIS	1037
550026DIS	1039
550029DIS	1039
550030DIS	1039
550031DIS	1039
550033DIS	1039
550034DIS	1039
550035DIS	1039
550036DIS	1039
550037DIS	1039
550039DIS	1039
550046DIS	1039
550047DIS	1039
550049DIS	1039
550050DIS	1039
550051DIS	1039
550052DIS	1039
550057DIS	1039
550067	1036
550072DIS	1039
550076DIS	1039
5501000001	817
5501000002	817
5501000003	817
5501000004	817
5501000005	817
550198DIS	1039
550218DIS	1039
55040-10	818
55040-10-6	818
55040-10-8	818
55040-12	818
55040-12-10	818
55040-14	818
55040-4	818
55040-5	818
55040-6	818
55040-6-4	818
55040-8	818
55040-8-6	818
55111-10-1/2	818
55111-10-1/4	818
55111-10-3/8	818
55111-12-1/2	818
55111-12-1/4	818
55111-12-3/8	818
55111-14-1/2	818
55111-14-3/8	818
55111-4-1/4	818
55111-4-1/8	818
55111-5-1/8	818
55111-6-1/2	818
55111-6-1/4	818
55111-6-1/8	818
55111-6-3/8	818
55111-8-1/2	818
55111-8-1/4	818
55111-8-1/8	818
55111-8-3/8	818
55116-10-1/2	818
55116-10-1/4	818
55116-10-3/8	818
55116-12-1/2	818
55116-12-1/4	818
55116-12-3/8	818
55116-14-1/2	818
55116-14-3/8	818
55116-4-1/4	818
55116-4-1/8	818
55116-4-M3X0.5	818
55116-4-M5	818
55116-4-M7X1	818
55116-5-1/8	818
55116-5-M5	818
55116-6-1/2	818
55116-6-1/4	818
55116-6-1/8	818
55116-6-3/8	818
55116-6-M5	818
55116-8-1/2	818
55116-8-1/4	818
55116-8-1/8	818
55116-8-3/8	818
55130-10	818
55130-12	818
55130-14	818
55130-4	818
55130-5	818
55130-6	818
55130-8	818
551365	526
551367	526
551369	526
551373	526
551375	526
551377	526
551379	526
551382	526
55140-10	818
55140-10-12	818
55140-12	818
55140-4	818
55140-4-6	818
55140-6	818
55140-6-4	818
55140-8	818
55140-8-10	818

Code	Page
55230-10	819
55230-12	819
55230-14	819
55230-4	819
55230-5	819
55230-6	819
55230-8	819
55240-10	819
55240-10-12	819
55240-12	819
55240-4	819
55240-4-6	819
55240-6	819
55240-6-4	819
55240-8	819
55240-8-10	819
552950	662
55310-10	819
55310-12	819
55310-4	819
55310-6	819
55310-8	819
55330-4-4	819
55330-4-6	819
55330-6-6	819
55330-6-8	819
55340-4-1/4	819
55340-4-1/8	819
55340-6-1/4	819
55340-6-1/8	819
55345-4-1/4	819
55345-4-1/8	819
55345-6-1/4	819
55345-6-1/8	819
55350-10-6	819
55350-10-8	819
55350-6-4	819
55350-8-4	819
55350-8-6	819
553534-002	1031
55410-1/2	820
55410-1/4	820
55410-1/8	820
55410-3/8	820
55410-M12X1.5	820
55410-M5	820
55410-M6	820
55420-1/2	820
55420-1/4	820
55420-1/8	820
55420-3/8	820
55430-1/2	820
55430-1/4	820
55430-1/8	820
55430-3/8	820
55500-10-3/8	819
55500-12-1/2	819
55500-12-3/8	819
55500-4-1/8	819
55500-4-M5	819
55500-4-M6	819
55500-5-1/4	819
55500-5-1/8	819
55500-5-M5	819
55500-5-M6	819
55500-6-1/4	819
55500-6-1/8	819
55500-6-M5	819
55500-6-M6	819
55500-8-1/4	819
55500-8-1/8	819
55500-8-3/8	819
55510-4-M5	819
55510-5-1/4	819
55510-5-1/8	819
55510-6-1/4	819
55510-6-1/8	819
55510-8-1/4	819
55510-8-1/8	819
558278	912
558279	912
559263	465
559264	465
559265	465
559266	465
559267	465
559268	465
559269	465
559270	465
559271	465
559272	465
559273	465
559274	465
559275	465
559276	465
559277	465
559278	465
559279	465
559280	465
559281	465
559282	465
559283	465
559284	465
559285	465
559286	465
559287	465
559288	465
559289	465
559290	465
559291	465
559292	465
5611A701	671
5611B241	669
5611B24L101	671
5611B261	669
5611B541	669
5611B54L101	671
5611B561	669
5611C101	667
5611D101	667
5611F201	666
5611F501	666
5611L101	669
5611R141	668
5611R161	668
5611R241	668
5611R261	668
5611S201	671
5611V101	670
5611V201	670
5611V701	670
5612A702	671
5612B242	669
5612B24L102	671
5612B262	669
5612B542	669
5612B54L102	671
5612B562	669
5612C102	667
5612D102	667
5612F202	666
5612F502	666
5612L102	669
5612R142	668
5612R162	668
5612R242	668
5612R262	668
5612S202	671
5612V102	670
5612V202	670
5612V702	670
5613A703	671
5613B243	669
5613B24L103	671
5613B263	669
5613B543	669
5613B54L103	671
5613B563	669
5613C103	667
5613D103	667
5613F203	666
5613F503	666
5613L103	669
5613R143	668
5613R163	668
5613R243	668
5613R263	668
5613S203	671
5613V103	670
5613V203	670
5613V703	670
56144010	411
56145010	411
5623A703	671
5623B243	669
5623B24L103	671
5623B263	669
5623B543	669
5623B54L103	671
5623B563	669
5623C103	667
5623D103	667
5623F203	666
5623F503	666
5623L103	669
5623R143	668
5623R163	668
5623R243	668
5623R263	668
5623S203	671
5623V103	670
5623V203	670
5623V703	670
5624A704	671
5624B244	669
5624B24L104	671
5624B264	669
5624B544	669
5624B54L104	671
5624B564	669
5624C104	667
5624D104	667
5624F204	666
5624F504	666
5624L104	669
5624R144	668
5624R164	668
5624R244	668
5624R264	668
5624S204	671
5624V104	670
5624V204	670
5624V704	670
5625A705	671
5625B245	669
5625B24L105	671
5625B265	669
5625B545	669
5625B54L105	671
5625B565	669
5625C105	667
5625D105	667
5625F205	666
5625F505	666
5625L105	669
5625R145	668
5625R165	668
5625R245	668
5625R265	668
5625S205	671
5625V105	670
5625V205	670
5625V705	670
5626A706	671
5626B246	669
5626B24L106	671
5626B266	669
5626B546	669
5626B54L106	671
5626B566	669
5626D106	667
5626F206	666
5626F506	666
5626L106	669
5626R146	668
5626R166	668
5626R246	668
5626R266	668
5626S206	671
5626V106	670
5626V206	670
5626V706	670
564930	427
564932	427
564934	427
564936	427
564938	427
564940	427
565401	427
565402	427
565405	427
565406	427
565465	211
57018	1745
571061	1020
5711114-1/2	846
5711114-3/8	846
572576	428
572577	428
572646	525
572647	525
572648	525
572649	525
572650	525
572651	525
572652	525
572653-FESTO	525
572654	525
572655	525
572656	525
572657	525
572658	525
572659	525
572660	525
572661	525
572662	525
572663	525
572664	525
572665	525
572666	525
572667	525
572668	525
572669	525
572670	525
572671	525
572672	525
572673	525
572674	525
572675	525
572676	525
572677	525
572678	525
572679	525
572680	525
572681	525
572682	525
572683	525
572684	525
572685	525
572686	525
572687	525
572688	525
572689	525
572690	525
572691	525
572692	525
572693	525
572694	525
572695	525
572696	525

Code	Page
572697	525
572698	525
572699	525
572700	525
572701	525
572702	525
572703	525
572704	525
572705	525
572706	525
572707	525
572708	525
572709	525
572710	525
572711	525
572712	525
572713	525
572714	525
572715	525
572716	525
572717	525
572718	525
572719	525
572720	525
572721	525
572722	525
572723	525
572724	525
572725	525
572726	525
572727	525
572728	525
572729	525
572730	525
572731	525
572732	525
572733	525
572734	525
572735	525
573346	427
573347	427
573348	427
573349	427
573350	427
573351	427
574334	468
574335	526
574336	526
574337	526
574338	526
574339	468
574340	526
574341	526
575263	580
575264	580
575265	580
575266	582
575268	580
575274	580
575475	580
575477	580
575481	582
575503	580
575511	580
575513	582
575518	580
575520	582
575525	580
575527	582
575541	582
575568	580
575570	580
575574	582
575596	580
575604	580
575606	582
575611	580
575613	582
575618	580
575620	582
576363	581
576365	581
576367	581
576369	581
576371	581
576409	581
576410	581
576411	581
576417	581
576419	581
576421	581
576423	581
576425	581
576465	581
576467	581
576469	581
576471	581
576473	581
577257	1020
57KBAW26SPN	379
57KBAW33SPN	379
57KBIW21SPN	379
57KBIW26SPN	379
57KBIW33SPN	379
57KBTF19SPN	379
57SBAW21SPN	379
57SBAW26SPN	379
57SBAW33SPN	379
57SBIW21SPN	379
57SBIW26SPN	379
58.1045OS	1454
58.3023OS	1454
58.3045OS	1454
58000-4-1/8	858
58000-4-M10	858
58000-4-M6	858
58000-4-M8	858
58000-6-1/8	858
58000-6-M10	858
58000-6-M6	858
58000-6-M8	858
58040-4	858
58040-6	858
58100-4-1/8	858
58100-4-M10	858
58100-4-M6	858
58100-4-M8	858
58100-6-1/8	858
58100-6-M10X1	858
58100-6-M6X1	858
58100-6-M8X1	858
58110-4-1/8	858
58110-4-M10	858
58110-4-M6	858
58110-4-M8	858
58110-6-1/8	858
58110-6-M10	858
58110-6-M6	858
58110-6-M8	858
5949SA3	1664
5950NA3	1664
5950SA3	1664
5951SA3	1664
5952GA3	1664
5953SA3	1664
59600A3	1664
59603-25	1675
5960AA3	1664
5961GA3	1664
59640A3	1664
598261	227
598262	227
598263	227
598264	227
598265	227
5986572-001	224
5986574-001	224
5986576-001	224
5E-PBIND	257
5F-PBIND	257
5JITS	80
5J-T-MM-10K	93
5JTN	80
5-MS	1517
5-ORING	108
5-SS	1517
5VS-401-800	445
5VS-402-800	445
5VS-410-800	445
5VS-412-800	445
5VS-420-800	445
5VS-421-800	445
6	
6000/06/G/5.5	985
6000/06/H/9.0	985
60000-10-1/4	878
60000-10-3/8	878
60000-12-1/2	878
60000-12-3/8	878
60000-4-1/4	878
60000-4-1/8	878
60000-6-1/4	878
60000-6-1/8	878
60000-8-1/4	878
60000-8-1/8	878
600-1008	1144
60013056AC	1611
600-1306	1144
600-1308	1144
600-1310	1144
600-1708	1144
600-1710	1144
60020-10-1/2	878
60020-10-1/4	878
60020-10-3/8	878
60020-12-1/2	878
60020-12-3/8	878
60020-14-1/2	878
60020-4-1/4	878
60020-4-1/8	878
60020-4-M5	878
60020-6-1/4	878
60020-6-1/8	878
60020-6-M5	878
60020-8-1/4	878
60020-8-1/8	878
60028342AC	1611
6003263WAC	1611
60032656AC	1611
60038830AA	1611
60040-10	879
60040-10-12	879
60040-12	879
60040-14	879
60040-4	879
60040-4-6	879
60040-6	879
60040-6-8	879
60040-8	879
60040-8-10	879
60050-10	879
60050-12	879
60050-4	879
60050-6	879
60050-8	879
601-10	1542
601-10SS	1542
60110X-10-12	878
60110X-10-14	878
60110X-10-38	878
60110X-12-12	878
60110X-12-38	878
60110X-4-14	878
60110X-4-18	878
60110X-6-14	878
60110X-6-18	878
60110X-8-14	878
60110X-8-18	878
601-13	1542
601-13SS	1542
60115X-10-12	878
60115X-10-14	878
60115X-10-38	878
60115X-12-12	878
60115X-12-38	878
60115X-14-12	878
60115X-4-14	878
60115X-4-18	878
60115X-4-M5	878
60115X-6-14	878
60115X-6-18	878
60115X-6-38	878
60115X-6-M5	878
60115X-8-14	878
60115X-8-18	878
60115X-8-38	878
601-16	1542
601-16SS	1542
601-19	1542
601-19SS	1542
601-22	1542
601-22SS	1542
601-25	1542
601-25SS	1542
601-28	1542
601-28SS	1542
60130X-10	879
60130X-12	879
60130X-14	879
60130X-4	879
60130X-6	879
60130X-8	879
601-32	1542
601-32SS	1542
601-36	1542
601-36SS	1542
601-40	1542
601-40SS	1542
601-44	1542
601-44SS	1542
601-48	1542
601-48SS	1542
601-52	1542
601-52SS	1542
601-6	1542
601-6SS	1542
601-8	1542
601-8SS	1542
60210X-10-12	878
60210X-10-14	878
60210X-10-38	878
60210X-12-12	878
60210X-12-38	878
60210X-4-14	878
60210X-4-18	878
60210X-6-14	878
60210X-6-18	878
60210X-8-14	878
60210X-8-18	878
60215X-10-12	878
60215X-10-14	878
60215X-10-38	878
60215X-12-12	878
60215X-12-38	878
60215X-14-12	878
60215X-4-14	878
60215X-4-M5	878
60215X-6-14	878
60215X-6-18	878
60215X-6-M5	878
60215X-8-14	878
60215X-8-18	878
60230X-10	879
60230X-12	879
60230X-14	879
60230X-4	879
60230X-6	879
60230X-8	879
60310X-4	879
60310X-6	879

Code	Page
60310X-8	879
60500	56
605006250	430
605006520	430
605009902	430
6050-1	627
6050-12	627
6050-14	627
6050-18	627
6050-34	627
6050-38	627
6050-M5	627
6058	468
6059	468
6060001570	1572
60600-10-14	879
60600-10-38	879
60600-12-12	879
60600-12-38	879
6060020140	1651
6060020141	1651
6060020142	1651
6060020143	1651
6060020145	1651
60600-6-18	879
60600-8-14	879
6060-12	1056
6060-14	1056
6060-18	1056
6060-38	1056
6062-12	627
6062-14	627
6062-18	627
6062-38	627
6062-M5	627
6063-12	627
6063-14	627
6063-18	627
6063-38	627
6064-4	627
6064-6	627
6064-8	627
60668	1745
6070020130	1651
6070020131	1651
6070020132	1651
6070020134	1651
6070020141	1651
6070-1/4	1174
6070-1/8	1174
6080020109	1651
6080020113	1651
6080020115	1651
6080020119	1651
6080020120	1651
6080-1/4	1174
6080-1/8	1174
6090020030	1651
6090020033	1651
6090020036	1651
6090020038	1651
6090020040	1651
6090020046	1651
6090020053	1651
6090-1/4	1159
6090-1/8	1159
60D-P100G-DD1-AA	429
60D-V110G-DD1-AA	429
60S-P010G-A42-AA	429
60S-P016G-A42-AA	429
60S-V110G-A42-AA	429
610AA	1034
610AC	1034
610AE	1034
610AL	1034
610B012012	885
610B012014	885
610B012015	885
610B012016	885
610B012018	885
610B012020	885
610B034018	885
610B034022	885
610B034025	885
610B038012	885
610B100028	885
6120005000	1581
6120005500	1581
6130001500	1571
6130001560	1572
6130002500	1571
6130002600	1571
6130002700	1571
6130002800	1571
6130002900	1571
6130004000	1573
6130004020	1573
6130004030	1576
6130004050	1572
6130007000	1574
6130008500	1574
6130009000	1574
6130012000	1572
6130012100	1573
6130013000	1574
61400	61
6140001500	1575
6140003500	1574
61402	61
61403	61
61404	61
61405	61
61406	61
61410	61
61411	61
61417	61
61419	61
61420	61
61429	61
61432	61
61433	61
61434	61
61436	61
61437	61
61438	61
61439	61
6144	490
61443	61
61444	61
61445	61
61448	61
61449	61
6145	490
6146	490
6147	490
614AA	1034
614AC	1034
614AE	1034
6150001010	1575
6150001030	1575
6150001100	1574
6150002000	1575
6150003600	1574
6150003601	1574
6150005500	1575
6150006000	1575
6150006100	1575
6150006500	1575
6150007000	1574
6150009300	1580
6150009310	1580
6150009320	1580
6150009330	1579
6150009340	1579
6150009350	1579
6150009360	1580
6150009370	1579
6150009380	1580
6150009390	1581
6150009400	1579
6150009420	1580
6150009450	1580
6150009470	1579
6150009480	1579
6150009490	1581
6150009500	1579
6150009510	1580
6150009520	1579
6150009530	1581
6150SA8	1660
6151SA8	1660
615500ABF	889
615B012012	885
615B012014	885
615B012015	885
615B012016	885
615B012018	885
615B012020	885
615B034018	885
615B034022	885
615B034025	885
615B038012	885
615B038014	885
615B100028	885
6160001000	1571
6160001200	1571
6160004000	1573
6160005000	1571
61640A8	1660
6165OA3	1660
616769	215
616773	217
616777	216
616781	216
616785	217
616789	216
6170030000	1572
6170030010	1574
6170030020	1575
6170030040	1575
6170030050	1576
617470	219
617471	219
617475	219
617476	219
617477	219
617499	219
617500	219
6180400000	1582
6180400001	1582
6180400002	1582
6180400003	1582
6180400004	1582
6180400005	1582
6180400006	1582
6180400007	1582
6180400008	1582
6180400010	1582
6180400011	1582
6180400012	1582
6180400013	1582
6180400014	1582
6190003000	1571
6190004150	1577
6190004600	1577
6190004650	1577
6190005600	1577
6190006510	1577
6190007510	1577
6190009400	1583
6190010000	1573
6190011001	1576
6190011501	1576
6190011510	1576
6190011511	1576
6190011512	1576
6190011513	1576
6190011530	1583
6190011531	1583
6190011533	1583
6190011536	1583
6190011537	1583
6190011538	1583
6190011600	1576
6190012000	1573
6190014010	1575
6190015000	1575
6190019000	1577
6190050001	1582
6190050002	1582
6190050003	1582
6190050004	1582
6190050005	1582
6190050006	1582
6190050007	1582
61M2P032A0025	507
61M2P032A0050	507
61M2P032A0075	507
61M2P032A0080	507
61M2P032A0100	507
61M2P032A0125	507
61M2P032A0150	507
61M2P032A0160	507
61M2P032A0200	507
61M2P032A0250	507
61M2P032A0300	507
61M2P032A0320	507
61M2P032A0400	507
61M2P032A0500	507
61M2P032A0600	507
61M2P032A0700	507
61M2P032A0800	507
61M2P032A0900	507
61M2P032A1000	507
61M2P040A0025	507
61M2P040A0050	507
61M2P040A0075	507
61M2P040A0080	507
61M2P040A0100	507
61M2P040A0125	507
61M2P040A0150	507
61M2P040A0160	507
61M2P040A0200	507
61M2P040A0250	507
61M2P040A0300	507
61M2P040A0320	507
61M2P040A0400	507
61M2P040A0500	507
61M2P040A0600	507
61M2P040A0700	507
61M2P040A0800	507
61M2P040A0900	507
61M2P040A1000	507
61M2P050A0025	507
61M2P050A0050	507
61M2P050A0075	507
61M2P050A0080	507
61M2P050A0100	507
61M2P050A0125	507
61M2P050A0150	507
61M2P050A0160	507
61M2P050A0200	507
61M2P050A0250	507
61M2P050A0300	507
61M2P050A0320	507
61M2P050A0400	507
61M2P050A0500	507
61M2P050A0600	507
61M2P050A0800	507
61M2P050A0900	507
61M2P050A1000	507
61M2P063A0025	507
61M2P063A0050	507
61M2P063A0075	507
61M2P063A0080	507
61M2P063A0100	507
61M2P063A0125	507
61M2P063A0150	507
61M2P063A0160	507
61M2P063A0200	507

Code	Page
61M2P063A0250	507
61M2P063A0300	507
61M2P063A0320	507
61M2P063A0400	507
61M2P063A0500	507
61M2P063A0600	507
61M2P063A0700	507
61M2P063A0800	507
61M2P063A0900	507
61M2P063A1000	507
61M2P080A0025	507
61M2P080A0050	507
61M2P080A0075	507
61M2P080A0080	507
61M2P080A0100	507
61M2P080A0125	507
61M2P080A0150	507
61M2P080A0160	507
61M2P080A0200	507
61M2P080A0250	507
61M2P080A0300	507
61M2P080A0320	507
61M2P080A0500	507
61M2P080A0600	507
61M2P080A0700	507
61M2P080A0800	507
61M2P080A0900	507
61M2P080A1000	507
61M2P100A0025	507
61M2P100A0050	507
61M2P100A0080	507
61M2P100A0100	507
61M2P100A0125	507
61M2P100A0150	507
61M2P100A0160	507
61M2P100A0200	507
61M2P100A0250	507
61M2P100A0300	507
61M2P100A0320	507
61M2P100A0400	507
61M2P100A0500	507
61M2P100A0600	507
61M2P100A0700	507
61M2P100A0800	507
61M2P100A0900	507
61M2P100A1000	507
61M2P125A0025	507
61M2P125A0050	507
61M2P125A0075	507
61M2P125A0080	507
61M2P125A0100	507
61M2P125A0125	507
61M2P125A0150	507
61M2P125A0160	507
61M2P125A0200	507
61M2P125A0250	507
61M2P125A0300	507
61M2P125A0320	507
61M2P125A0400	507
61M2P125A0500	507
61M2P125A0600	507
61M2P125A0700	507
61M2P125A0800	507
61M2P125A0900	507
61M2P125A1000	507
620-2108	1144
620-2110	1144
620-2112	1144
620C000012	886
620C000014	886
620C000015	886
620C000016	886
620C000018	886
620C000020	886
620C000022	886
620C000025	886
620C000028	886
6230003705	1571
6230005100	1574
625500ABF	889
625C000012	886
625C000014	886
625C000015	886
625C000016	886
625C000018	886
625C000020	886
625C000022	886
6260020700	1583
628-1006	1144
628-1305	1144
628-1306	1144
628-1308	1144
628-1310	1144
628-1706	1144
628-1708	1144
628-1710	1144
628-2110	1144
628-2112	1144
6300-12	942
6300-14	942
6300-18	942
6300-38	942
6302001	678
630C000012	886
630C000014	886
630C000015	886
630C000016	886
630C000018	886
630C000020	886
630C000022	886
630C000025	886
630C000028	886
6310-12-12	942
6310-14-14	942
6310-14-18	942
6310-18-18	942
6310-34-34	942
6310-38-38	942
6320-12-12	942
6320-14-14	942
6320-14-18	942
6320-18-18	942
6320-38-38	942
6330001005	1572
6330007005	1572
6330061005	1571
6330062005	1571
6330-12-12	942
6330-14-14	942
6330-18-14	942
6330-18-18	942
6330272100	1573
6340-10-38	942
6340-15-12	942
6340-6-18	942
6340-8-14	942
6340-8-18	942
63440A8	1663
63470A8	1663
63500A3	1663
6350-12-15	942
6350-14-6	942
6350-14-8	942
6350-18-6	942
6350-18-8	942
6350-38-10	942
6350-38-12	942
6350SA3	1663
63530A3	1663
6353SA3	1663
635500ABF	889
635B012014	885
635B012015	885
635B012016	885
635B012018	885
635B012020	885
635B034018	885
635B034022	885
635B034025	885
635B100028	885
63600A3	1663
6360AA3	1663
6360BA3	1663
63610A3	1663
6361AA3	1663
63640A3	1663
6364AA3	1663
63670A3	1663
6367AA3	1663
63690A3	1662
63700M7018	1572
63700M7019	1572
63700M7028	1572
63700M7036	1576
63750A3	1663
6380002	678
6381001	679
63820A1	1660
63MP2C032A0025	508
63MP2C032A0050	508
63MP2C032A0075	508
63MP2C032A0080	508
63MP2C032A0100	508
63MP2C032A0125	508
63MP2C032A0150	508
63MP2C032A0160	508
63MP2C032A0200	508
63MP2C032A0250	508
63MP2C032A0300	508
63MP2C032A0320	508
63MP2C032A0400	508
63MP2C032A0500	508
63MP2C032A0600	508
63MP2C032A0700	508
63MP2C032A0800	508
63MP2C032A0900	508
63MP2C040A0025	508
63MP2C040A0050	508
63MP2C040A0075	508
63MP2C040A0080	508
63MP2C040A0100	508
63MP2C040A0125	508
63MP2C040A0150	508
63MP2C040A0160	508
63MP2C040A0200	508
63MP2C040A0250	508
63MP2C040A0300	508
63MP2C040A0320	508
63MP2C040A0400	508
63MP2C040A0500	508
63MP2C040A0600	508
63MP2C040A0700	508
63MP2C040A0800	508
63MP2C040A0900	508
63MP2C050A0025	508
63MP2C050A0050	508
63MP2C050A0075	508
63MP2C050A0080	508
63MP2C050A0100	508
63MP2C050A0125	508
63MP2C050A0150	508
63MP2C050A0160	508
63MP2C050A0200	508
63MP2C050A0250	508
63MP2C050A0300	508
63MP2C050A0320	508
63MP2C050A0400	508
63MP2C050A0500	508
63MP2C050A0600	508
63MP2C050A0700	508
63MP2C050A0800	508
63MP2C050A0900	508
63MP2C063A0025	508
63MP2C063A0050	508
63MP2C063A0075	508
63MP2C063A0080	508
63MP2C063A0100	508
63MP2C063A0125	508
63MP2C063A0150	508
63MP2C063A0160	508
63MP2C063A0200	508
63MP2C063A0250	508
63MP2C063A0300	508
63MP2C063A0320	508
63MP2C063A0400	508
63MP2C063A0500	508
63MP2C063A0600	508
63MP2C063A0700	508
63MP2C063A0800	508
63MP2C063A0900	508
63MP2C080A0025	508
63MP2C080A0050	508
63MP2C080A0075	508
63MP2C080A0080	508
63MP2C080A0100	508
63MP2C080A0125	508
63MP2C080A0150	508
63MP2C080A0160	508
63MP2C080A0200	508
63MP2C080A0250	508
63MP2C080A0300	508
63MP2C080A0320	508
63MP2C080A0400	508
63MP2C080A0500	508
63MP2C080A0600	508
63MP2C080A0700	508
63MP2C080A0800	508
63MP2C080A0900	508
63MP2C080A0985	508
63MP2C100A0025	508
63MP2C100A0050	508
63MP2C100A0075	508
63MP2C100A0080	508
63MP2C100A0100	508
63MP2C100A0125	508
63MP2C100A0150	508
63MP2C100A0160	508
63MP2C100A0200	508
63MP2C100A0250	508
63MP2C100A0300	508
63MP2C100A0320	508
63MP2C100A0400	508
63MP2C100A0500	508
63MP2C100A0600	508
63MP2C100A0700	508
63MP2C100A0800	508
63MP2C100A0900	508
63MP2C125A0025	508
63MP2C125A0050	508
63MP2C125A0075	508
63MP2C125A0080	508
63MP2C125A0100	508
63MP2C125A0125	508
63MP2C125A0150	508
63MP2C125A0160	508
63MP2C125A0200	508
63MP2C125A0250	508
63MP2C125A0300	508
63MP2C125A0320	508
63MP2C125A0400	508
63MP2C125A0500	508
63MP2C125A0600	508
63MP2C125A0700	508
63MP2C125A0800	508
63MP2C125A0900	508
6402001	678
64053	1744
64058	1744
640B012012	885
640B012014	885
640B012015	885
640B012016	885
640B012018	885
640B012020	885
640B034018	885
640B034022	885
640B034025	885
640B038012	885
640B100028	885
6420-12-12	942

Code	Page
6420-14-14	**942**
6420-18-14	**942**
6420-18-18	**942**
6420-38-14	**942**
6420-38-38	**942**
6432 10 1/4	**871**
6432 10 3/8	**871**
6432 12 1/4	**871**
6432 12 3/8	**871**
6432 4 1/8	**871**
6432 4 M5	**871**
6432 5 M5	**871**
6432 6 1/4	**871**
6432 6 1/8	**871**
6432 8 1/4	**871**
6432 8 1/8	**871**
6432 8 3/8	**871**
6440-12-12	**942**
6440-12-15	**942**
6440-14-10	**942**
6440-14-6	**942**
6440-14-8	**942**
6440-18-6	**942**
6440-18-8	**942**
6440-34-15	**942**
6440-38-10	**942**
6440-38-15	**942**
6440-38-8	**942**
6442 10 1/4	**871**
6442 10 3/8	**871**
6442 12 1/4	**871**
6442 12 3/8	**871**
6442 4 1/8	**871**
6442 4 M5	**871**
6442 5 M5	**871**
6442 6 1/4	**871**
6442 6 1/8	**871**
6442 8 1/4	**871**
6442 8 1/8	**871**
6442 8 3/8	**871**
64500A3	**1665**
6450SA3	**1665**
6451 4 M5	**872**
64530A3	**1665**
6453SA3	**1665**
645500ABF	**889**
645B012012	**885**
645B012014	**885**
645B012015	**885**
645B012016	**885**
645B012018	**885**
645B012020	**885**
645B034018	**885**
645B034022	**885**
645B034025	**885**
645B038012	**885**
645B100028	**885**
64600A3	**1665**
64610A3	**1665**
64611A3	**1665**
6463 10 1/4	**870**
6463 4 1/8	**870**
6463 4 M5	**870**
6463 5 1/8	**870**
6463 6 1/4	**870**
6463 6 1/8	**870**
6463 8 1/4	**870**
6463 8 1/8	**870**
646500ABF	**889**
64670A3	**1665**
647109	**1685**
647121	**1685**
6480002	**678**
6481001	**679**
648B012012	**885**
648B012014	**885**
648B012015	**885**
648B012016	**885**
648B012018	**885**
648B012020	**885**
648B034018	**885**
648B034022	**885**
648B038012	**885**
64903	**1743**
6500-8	**942**
650-1003	**1142**
650-1004	**1142**
650-1005	**1142**
650-1006	**1142**
650-1008	**1142**
650-1010	**1142**
650103	**1651**
650108	**1651**
650113	**1651**
650121	**1651**
650-1305	**1142**
650-1306	**1142**
650-1308	**1142**
650-1310	**1142**
650-1312	**1142**
650-1706	**1142**
650-1708	**1142**
650-1710	**1142**
650-1713	**1142**
650-1716	**1142**
650-1719	**1142**
650-2106	**1142**
650-2108	**1142**
650-2110	**1142**
650-2113	**1142**
650-2116	**1142**
650-2119	**1142**
650-2125	**1142**
650-2612	**1142**
650-2616	**1142**
650-2625	**1142**
650-2632	**1142**
650-3312	**1142**
650-3316	**1142**
650-3319	**1142**
650-3325	**1142**
650-3332	**1142**
650-4219	**1142**
650-4225	**1142**
650-4232	**1142**
650-4238	**1142**
650-4838	**1142**
650C000012	**886**
650C000014	**886**
650C000015	**886**
650C000016	**886**
650C000018	**886**
650C000020	**886**
650C000022	**886**
650C000025	**886**
650C000028	**886**
6512 10 1/4	**870**
6512 10 3/8	**870**
6512 12 1/4	**870**
6512 12 3/8	**870**
6512 4 1/4	**870**
6512 4 1/8	**870**
6512 4 M5	**870**
6512 4 M6	**870**
6512 5 M5	**870**
6512 6 1/4	**870**
6512 6 1/8	**870**
6512 6 M5	**870**
6512 8 1/4	**870**
6512 8 1/8	**870**
6512 8 3/8	**870**
652021	**1685**
6522 10 1/4	**870**
6522 10 3/8	**870**
6522 12 1/4	**870**
6522 12 3/8	**870**
6522 4 1/4	**870**
6522 4 1/8	**870**
6522 4 M5	**870**
6522 5 M5	**870**
6522 6 1/4	**870**
6522 6 1/8	**870**
6522 6 M5	**870**
6522 8 1/4	**870**
6522 8 1/8	**870**
6522 8 3/8	**870**
6540 10	**872**
6540 12	**872**
6540 14	**872**
6540 4	**872**
6540 5	**872**
6540 6	**872**
6540 8	**872**
6550 10	**872**
6550 12	**872**
6550 14	**872**
6550 4	**872**
6550 5	**872**
6550 6	**872**
6550 8	**872**
65500B3	**1660**
65506B3	**1660**
6550NB3	**1660**
6555 10 10	**872**
6555 4 4	**872**
6555 6 6	**872**
6555 8 8	**872**
655BU012110	**886**
655BU012180	**886**
655BU012200	**886**
655BU015180	**886**
655BU015250	**886**
655BU016150	**886**
655BU016180	**886**
655BU016200	**886**
655BU018200	**886**
655BU020190	**886**
655BU020280	**886**
655BU022200	**886**
655BU025230	**886**
655BU025250	**886**
655BU028280	**886**
655BU028300	**886**
6560 10	**872**
6560 4	**872**
6560 6	**872**
6560 8	**872**
6560-4	**928**
6560-6	**928**
6560-8	**928**
65610B9	**1660**
65632B9	**1660**
656EP012	**886**
656EP014	**886**
656EP015	**886**
656EP016	**886**
656EP018	**886**
656EP020	**886**
656EP022	**886**
656EP025	**886**
656EP028	**886**
6570-14-6	**928**
6570-14-8	**928**
6570-18-4	**928**
6570-18-6	**928**
6570-18-8	**928**
657DI012	**886**
657DI014	**886**
657DI015	**886**
657DI016	**886**
657DI018	**886**
657DI020	**886**
657DI022	**886**
657DI025	**886**
657DI028	**886**
6580 10	**872**
6580 12	**872**
6580 14	**872**
6580 4	**872**
6580 5	**872**
6580 6	**872**
6580 8	**872**
658AG012	**886**
658AG014	**886**
658AG015	**886**
658AG016	**886**
658AG018	**886**
658AG020	**886**
658AG022	**886**
658AG025	**886**
658AG028	**886**
6590 10	**872**
6590 12	**872**
6590 14	**872**
6590 4	**872**
6590 5	**872**
6590 6	**872**
6590 8	**872**
6600 10	**872**
6600 12	**872**
6600 4	**872**
6600 5	**872**
6600 6	**872**
6600 8	**872**
660-1010	**1165**
660-1313	**1165**
660-1717	**1165**
6602.17.00	**1066**
6602.25.00	**1066**
6602.40.00	**1066**
6602.50.00	**1066**
6602.63.00	**1066**
660-2121	**1165**
660-2626	**1165**
6603-12-12	**309**
6603-16-16	**309**
660-3333	**1165**
6603-4-4	**309**
6603-6-6	**309**
6603-8-10	**309**
6604.17.00	**1066**
6604.25.00	**1066**
6604.40.00	**1066**
6604.50.00	**1066**
6604.50.25	**1066**
6604.50.40	**1066**
6604.63.00	**1066**
6605.17.13	**1065**
6605.17.21	**1065**
6605.25.21	**1065**
6605.25.27	**1065**
6605.25.34	**1065**
6605.40.34	**1065**
6605.40.42	**1065**
6605.40.49	**1065**
6605.50.48	**1065**
6605.50.49	**1065**
6605.63.48	**1065**
660502ABF	**889**
660504ABF	**889**
660510ABF	**889**
6605-12-12	**309**
660512ABF	**889**
660514ABF	**889**
6605-16-16	**309**
660516ABF	**889**
660522ABF	**889**
660526ABF	**889**
6605-4-4	**309**
6605-6-6	**309**
6605-8-10	**309**
6606.17.00	**1065**
6606.25.00	**1065**
6606.40.00	**1065**
6606.50.00	**1065**
6606.63.00	**1065**
6609.17.13	**1066**
6609.17.21	**1066**
6609.25.21	**1066**
6609.25.27	**1066**

Code	Page
6609.25.34	1066
6609.40.34	1066
6609.40.42	1066
6609.50.48	1066
6609.50.49	1066
6609.63.48	1066
6612.25.00	1066
6612.40.00	1066
6612.63.00	1066
6615.50.48	1065
6615.50.49	1065
6622 10 1/4	871
6622 4 1/8	871
6622 4 M5	871
6622 6 1/4	871
6622 6 1/8	871
6622 8 1/4	871
6622 8 1/8	871
6625.17.00	1066
6625.25.00	1066
6625.40.00	1066
6625.50.00	1066
6625.63.00	1066
6632 10 1/4	871
6632 4 1/8	871
6632 6 1/8	871
6632 8 1/4	871
6632 8 1/8	871
6637.25.21	1063
6639.17.21	1063
6639.25.21	1063
6657-12PL	309
6657-16PL	309
6657-6PL	309
6657-8PL	309
6659-12PL	309
6659-16PL	309
6659-6PL	309
6659-8PL	309
6661.25.21	1063
6661.40.21	1063
6661.40.27	1063
6661.50.21	1063
6661.50.27	1063
6662.25.00	1065
6662.25.17	1065
6662.40.17	1065
6662.40.25	1065
6662.50.25	1065
6662.63.21	1063
6662.63.25	1065
6666.17.25	1065
6666.25.40	1065
6666.40.50	1065
6666.50.63	1065
6669.25.21	1065
6669.40.21	1065
6669.40.27	1065
6669.50.21	1065
6669.50.27	1065
6669.63.21	1065
6669.63.27	1065
66737	1746
6678.17.21	1063
6678.25.21	1063
6681.17.21	1063
6681.25.21	1063
6682.17.21	1063
6682.25.21	1063
6690.21.21	1063
6693.17.21	1063
6693.25.21	1063
66938	1743
66943	1743
6695.25.21	1063
6697.00.02	1067
6697.00.03	1067
6697.17.00	1067
6697.25.00	1067
6697.40.00	1067
6697.50.00	1067
6697.63.00	1067
6698.00.05	1067
6698.01.03	1067
6698.02.01	1067
6698.02.02	1067
6698.03.01	1067
6698.04.01	1067
6698.04.02	1067
6698.04.03	1067
6698.05.03	1067
6699.03.01	1067
6700 4	872
6700 5	872
6700 6	872
6700-14	928
6700-18	928
6700-38	928
67088	1744
671012	885
671014	885
6710-14	928
671015	885
671016	885
671018	885
6710-18	928
671020	885
671022	885
671025	885
671028	885
6710-38	928
6720-14	928
6720-18	928
6720-38	928
67228	1744
6750 12	872
6750 4	872
6750 6	872
6750 8	872
6800 10 12	872
6800 10 14	872
6800 12 14	872
6800 4 5	872
6800 4 6	872
6800 4 8	872
6800 5 6	872
6800 5 8	872
6800 6 10	872
6800 6 12	872
6800 6 8	872
6800 8 10	872
6800 8 12	872
680001515	1130
680002222	1130
680002828	1130
680003535	1130
680004242	1130
680005454	1130
6801015012	1129
6801015034	1129
6801022012	1129
6801022034	1129
6801022100	1129
6801028034	1129
6801028100	1129
6801035114	1129
6801042112	1129
6801054200	1129
6802015012	1129
6802015034	1129
6802022012	1129
6802022034	1129
6802022100	1129
6802028034	1129
6802028100	1129
6802035114	1129
6802042112	1129
6802054200	1129
6808015012	1129
6808022034	1129
6808028100	1129
6808035114	1129
6808042112	1129
6808054200	1129
68100151515	1132
68100222222	1132
68100282828	1132
68100353535	1132
68100424242	1132
68100545454	1132
6811 10 1/4	871
6811 10 3/8	871
6811 12 3/8	871
6811 14 1/2	871
6811 4 1/8	871
6811 4 M5	871
6811 5 1/4	871
6811 5 1/8	871
6811 6 1/4	871
6811 6 1/8	871
6811 8 1/4	871
6811 8 1/8	871
68110221522	1132
68110282228	1132
68110352235	1132
68110352835	1132
6811-04-04	72
68110422242	1132
68110422842	1132
68110423542	1132
68110542254	1132
68110542854	1132
68110543554	1132
68110544254	1132
6811-06-06	72
6811-08-08	72
68118	1743
68120151215	1132
68120221222	1132
68120223422	1132
68120281228	1132
68120283428	1132
68120351235	1132
68120421242	1132
68120541254	1132
682001515	1133
682002222	1133
682002828	1133
682003535	1133
682004242	1133
682005454	1133
682101515	1134
682102222	1134
682102828	1134
682103535	1134
682104242	1134
682105454	1134
682301515	1131
682302222	1131
682302828	1131
682303535	1131
682304242	1131
682305454	1131
682401515	1131
682402222	1131
682402828	1131
682403535	1131
682404242	1131
682405454	1131
6831015012	1133
6831022034	1133
6831028100	1133
6832015012	1133
6832022034	1133
6832028100	1133
6841015	1131
6841022	1131
6841028	1131
6841035	1131
6841042	1131
6841054	1131
684302215	1130
684302815	1130
684302822	1130
684303522	1130
684303528	1130
684304222	1130
684304228	1130
684304235	1130
684305435	1130
684305442	1130
685012028	885
68KAAW17SPN	380
68KAAW21SPN	380
68KAAW26SPN	380
68KAIW13SPN	380
68KAIW17SPN	380
68KAIW21SPN	380
68KAIW26SPN	380
68KATF10SPN	380
68KATF13SPN	380
68KATF19SPN	380
6900 10MM	872
6900 12MM	872
6900 14MM	872
6900 4MM	872
6900 5MM	872
6900 6MM	872
6900 8MM	872
69001	68
69001A15	1136
69001A22	1136
69001A28	1136
69001A35	1136
69001A42	1136
69001A54	1136
69001L15	1136
69001L22	1136
69001L28	1136
69001L35	1136
69001L42	1136
69001L54	1136
69002	68
69002A15	1136
69002A22	1136
69002A28	1136
69002A35	1136
69002A42	1136
69002A54	1136
69002AG1512	1136
69002AG2234	1136
69002G1512	1136
69002G2234	1136
69003	68
69005	68
69006	68
69009	68
6904015	1136
6904022	1136
6904028	1136
6904035	1136
6904042	1136
6904054	1136
6904115	1136
6904122	1136
6904128	1136
6904135	1136
6904142	1136
6904154	1136
69073	1744
69078	1744
69083	1744
69090IG1512	1136
69090IG2234	1136
69092AG1512	1136
69092AG2234	1136
69092AG281	1136
6910-A	928
6910-B	928
6913015	1136

Code	Page
6913022	1136
69130221522	1136
6913028	1136
69130281528	1136
6913035	1136
69130352235	1136
69130352835	1136
6913042	1136
69130422242	1136
69130422842	1136
69130423542	1136
6913054	1136
69130542254	1136
69130542854	1136
69130543554	1136
69130544254	1136
69130G151215	1136
69130G221222	1136
69130G223422	1136
69130G281228	1136
69130G283428	1136
69130G351235	1136
69130G353435	1136
69130G421242	1136
69130G541254	1136
6920-A-B	928
6920-A-G	928
6920-A-R	928
6920-A-W	928
6920-A-Y	928
6920-B-B	928
6920-B-G	928
6920-B-R	928
6920-B-W	928
6920-B-Y	928
692432215	1135
692432815	1135
692432822	1135
692433522	1135
692433528	1135
692434228	1135
692434235	1135
692435428	1135
692435435	1135
692435442	1135
69243G1512	1135
69243G1534	1135
69243G221	1135
69243G2212	1135
69243G2234	1135
69243G281	1135
69243G2834	1135
69243G351	1135
69243G35114	1135
69243G42112	1135
69243G542	1135
69246G1512	1135
69246G2212	1135
69246G2234	1135
69246G2834	1135
6927015	1135
6927022	1135
6927028	1135
6927035	1135
6927042	1135
6927054	1135
69270G1512	1135
69270G2212	1135
69270G2234	1135
69270G281	1135
69270G2834	1135
69270G35114	1135
69270G42112	1135
69270G542	1135
69270S15	1135
69270S22	1135
69270S28	1135
69270S35	1135
69270S42	1135
69270S54	1135
69280G1512	1135
69280G2212	1135
69280G2234	1135
69280G281	1135
6930115	1135
6930122	1135
6930128	1135
6930135	1135
69359M1512	1135
69359M1534	1135
69359M221	1135
69359M28114	1135
69359M35112	1135
69359M42134	1135
694400	213
694412	213
694414	213
694415	213
694419	213
6960015	1135
6960022	1135
6960028	1135
6960035	1135
6960042	1135
6960054	1135
69818	1744
69823	1744
69838	1744
69843	1744
698523	219
69868	1744
69873	1744
69878	1744
69883	1744
69888	1744
69893	1744
6-999-03-01-010	271
6BC02	68
6BC04	68
6BC06	68
6BC08	68
6BC10	68
6BC12	68
6BC16	68
6BC20	68
6BC24	68
6BC32	68
6BC40	68
6BS02	68
6BS04	68
6BS06	68
6BS08	68
6BS10	68
6BS12	68
6BS16	68
6BS20	68
6BS24	68
6BS32	68
6BT02	69
6BT04	69
6BT06	69
6BT08	69
6BT10	69
6BT12	69
6BT16	69
6BT24	69
6BT32	69
6E-PBIND	257
6F-PBIND	257
6G-10J-MF-10K	91
6G-10J-MM-10K	90
6G-12G-MF-A-10K	91
6G-12G-MM-10K	90
6G-12J-MM-10K	90
6G-12N-MM-10K	90
6G-16G-MF-A-10K	91
6G-16G-MM-10K	90
6G-16N-MM-10K	90
6G-2G-MF-B-10K	92
6G-4G-MF-B-10K	92
6G-4J-MM-10K	90
6G-4N-MM-10K	90
6G-6G-FF-10K	92
6G-6G-MF-A-10K	91
6G-6G-MM-10K	90
6G-6J-MF-10K	91
6G-6J-MM-10K	90
6G-6N-MM-10K	90
6G-8G-FF-10K	92
6G-8G-MF-A-10K	91
6G-8G-MM-10K	90
6G-8J-MF-10K	91
6G-8J-MM-10K	90
6G-8N-MM-10K	90
6G-C-10K	94
6G-E-FF-10K	93
6G-E-MF-10K	93
6G-E-MM-10K	92
6G-P-10K	94
6G-T-FF-10K	94
6G-T-MM-10K	93
6J05	79
6J07	79
6J08	79
6J09	79
6J-10J-MM-10K	90
6J12	79
6J14	79
6J17	79
6J19	79
6J21	79
6J26	79
6J30	79
6J40	79
6J-4J-MF-10K	91
6J-4N-MF-A-10K	91
6J-6J-FF-10K	92
6J-6J-MF-10K	91
6J-6J-MM-10K	90
6J-6N-MF-A-10K	91
6J-8J-FF-10K	92
6J-8J-MF-10K	91
6J-8J-MM-10K	90
6J-C-10K	94
6J-E-FF-10K	93
6J-E-MF-10K	93
6JITS	80
6JMTS	80
6J-P-10K	94
6J-T-FF-10K	94
6J-T-MM-10K	93
6JTN	80
6M10	69
6M12	69
6M14	69
6M16	69
6M18	69
6M20	69
6M22	69
6M24	69
6M26	69
6-MS	1517
6N02	69
6N04	69
6N06	69
6N08	69
6N12	69
6N-12J-MM-10K	90
6N-12N-FF-10K	92
6N-12N-MF-A-10K	91
6N16	69
6N-16N-FF-10K	92
6N-16N-MF-A-10K	91
6N20	69
6N24	69
6N-2N-MF-B-10K	92
6N-2N-MM-10K	90
6N32	69
6N40	69
6N48	69
6N-4J-MM-10K	90
6N-4N-MF-B-10K	92
6N-6J-E-MF-10K	93
6N-6J-MF-10K	91
6N-6J-MM-10K	90
6N-6N-FF-10K	92
6N-6N-MF-A-10K	91
6N-6N-MM-10K	90
6N-8J-MF-10K	91
6N-8J-MM-10K	90
6N-8N-FF-10K	92
6N-8N-MF-A-10K	91
6N-8N-MM-10K	90
6N-C-10K	94
6N-E-10K	93
6N-E-MF-10K	93
6N-E-MM-10K	92
6N-P-10K	94
6N-T-10K	94
6N-T-MM-10K	93
6N-X-10K	94
6SCV	884
6-SS	1517
6X-MS	1517
6X-SS	1517
7	
7000-1	631
7000-1/2	631
7000-1/4	631
7000-1/8	631
70003	1743
7000-3/4	631
7000-3/8	631
7001000100	551
7001000110	551
7001000200	552
7001000210	552
7001000400	552
7001000410	552
7001000500	551
7001000510	551
7001000600	551
7001000610	551
7001000700	552
7001000710	552
7001000900	553
7001000910	553
70020-10-1/4	861
70020-10-3/8	861
70020-12-3/8	861
70020-4-1/8	861
70020-4-M5	861
70020-6-1/4	861
70020-6-1/8	861
70020-8-1/4	861
70020-8-1/8	861
70040-10	861
70040-12	861
70040-4	861
70040-6	861
70040-8	861
7010000100	555
7010000200	555
7010000300	555
7010000400	555
7010001200	554
7010001300	554
7010001400	554
7010001500	554
7010001600	554
7010001700	554
7010001800	553
7010001900	553
7010010100	603
7010010200	603
7010011100	604
7010011200	604
7010012100	605
7010012200	605
7010012300	606

Code	Page
7010020200	584
7010020400	583
7010021100	585
7010021200	586
7010022100	587
7010022200	588
7010022300	587
7010-1	631
7010-1/2	631
7010-1/4	631
7010-1/8	631
7010-3/4	631
7010-3/8	631
7010-M5	631
70116-10-1/4	861
70116-10-3/8	861
70116-12-3/8	861
70116-4-1/8	861
70116-4-M5	861
70116-6-1/4	861
70116-6-1/8	861
70116-8-1/4	861
70116-8-1/8	861
7020000100	555
7020000200	555
7020000300	555
7020000400	555
7020000500	556
7020000600	556
7020000700	556
7020000900	556
7020001000	556
7020001100	556
7020001400	554
7020001700	554
7020010100	603
7020010200	603
7020011100	604
7020011200	604
7020012100	605
7020012200	605
7020012300	606
7020020200	584
7020020400	583
7020021100	585
7020021200	586
7020022100	587
7020022200	588
7020022300	587
7020-1/2	631
7020-1/4	631
7020-1/8	631
7020-3/4	631
7020-3/8	631
7020-M5	631
7021020100	583
7021020200	583
70216-4-1/8	861
70216-6-1/4	861
70216-6-1/8	861
70216-8-1/4	861
70216-8-1/8	861
70230-10	861
70230-12	861
70230-4	861
70230-6	861
70230-8	861
7030000100	555
7030000200	555
7030000300	555
7030000400	555
7030000500	556
7030000600	556
7030000700	556
7030000900	556
7030001000	556
7030001100	556
7030011100	604
7030011200	604
7030012100	605
7030012200	605
7030012300	606
7030020200	584
7030020400	583
7030021100	585
7030021200	586
7030022100	587
7030022200	588
7030022300	587
7030-1	631
7030-1/2	631
7030-1/2NPT	631
7030-1/4	631
7030-1/4NPT	631
7030-1/8	631
7030-1/8NPT	631
7030-1NPT	631
7030-3/4	631
7030-3/4NPT	631
7030-3/8	631
7030-3/8NPT	631
7030-M5	631
703222ABF	887
703322ABF	887
703522ABF	887
7040010100	603
7040010200	603
7040010400	603
7040011100	604
7040011200	604
7040011300	604
7040012100	605
7040012200	605
7040012300	606
7040020100	584
7040020200	584
7040020300	584
7040020400	583
7040020500	584
7040020600	584
7040021100	585
7040021200	586
7040021300	586
7040021500	585
7040021600	586
7040022100	587
7040022200	588
7040022300	587
7040022400	588
7040022500	588
7040022600	588
7040-1/2	631
7040-1/4	631
7040-1/8	631
7040-3/4	631
7040-3/8	631
7050-1/2	631
7050-1/4	631
7050-1/8	631
7050-3/8	631
7051011100	617
7051011200	617
7051012100	617
7051012200	617
7051012300	617
7051021100	618
7051021200	618
7051022100	618
7051022200	618
7051022300	618
7052011100	617
7052011200	617
7052012100	617
7052012200	617
7052012300	617
7052021100	618
7052021200	618
7052022100	618
7052022200	618
7052022300	618
7057021100	619
7057021400	619
7058021100	619
7058021400	619
7059021100	619
7059021400	619
7060020406	1652
7060020407	1652
7060020408	1652
7060020413	1652
706996-C	222
706997-C	222
706998-C	222
7070020395	1652
7070020397	1652
7070020398	1652
7070020399	1652
7070020401	1652
7070-1	630
7070-1/2	630
7070-1/4	630
7070-1/8	630
7070-3/4	630
7070-3/8	630
707277-C	222
707278-C	222
7080020354	1652
7080020360	1652
7080020363	1652
7080020372	1652
7080020378	1652
7080-1	630
7080-1/2	630
7080-1/4	630
7080-1/8	630
708021	71
708023	71
708024	71
708025	71
708026	71
708027	71
708028	71
708029	71
7080-3/4	630
7080-3/8	630
708049	71
708050	71
708051	71
708053	71
708075	79
708076	79
708077	79
708078	79
708079	79
708080	79
708081	79
708082	79
708083	79
708084	79
708085	79
708219-C	222
708371-C	222
708397-C	222
708398-C	222
708784-C	222
708785-C	222
708786-C	222
708787-C	222
7090020178	1652
7090020181	1652
7090020184	1652
7090020186	1652
7090020189	1652
7090020195	1652
7090020203	1652
7090020411	1652
71/2-MS	1517
71/2-SS	1517
7100215	1689
710312ABF	888
710316ABF	888
710322ABF	888
710516ABF	888
710522ABF	888
710722ABF	888
7120215	1689
71-3C12-12RP	319
71-3C16-16RP	319
71-3C4-4RP	319
71-3C6-6RP	319
71-3C8-8RP	319
71-3N12-12RP	319
71-3N16-16RP	319
71-3N4-4RP	319
71-3N6-6RP	319
71-3N8-8RP	319
718000	71
718002	71
718004	71
718005	71
718007	71
718008	71
718009	71
71806	1551
71KBIW10DPX	317
71KBIW10MVX	317
71KBIW10RVX	320
71SBIW10DPX	317
71SBIW10MVX	317
71SBIW10RVX	320
720-01AC110	1024
720-01AC110-VIS	1024
720-01AC220	1024
720-01AC220-VIS	1024
7200215	1689
720-02AC110	1024
720-02AC110-VIS	1024
720-02AC220	1024
720-02AC220-VIS	1024
720-02AC24	1024
720-02AC24-VIS	1024
720-02DC24	1024
720-02DC24-VIS	1024
720-03AC110	1024
720-03AC110-VIS	1024
720-03AC220	1024
720-03AC220-VIS	1024
720-03AC24	1024
720-03AC24-VIS	1024
720-03DC24	1024
720-03DC24-VIS	1024
720-04AC110	1024
720-04AC110-VIS	1024
720-04AC220	1024
720-04AC220-VIS	1024
720-04AC24	1024
720-04AC24-VIS	1024
720-04DC24	1024
720-04DC24-VIS	1024
720312ABF	888
720316ABF	888
720322ABF	888
720516ABF	888
720522ABF	888
720722ABF	888
7238-04	69
7238-05	69
7238-06	69
7238-08	69
7238-10	69
7238-12	69
7238-14	69
7238-16	70
7250	1042
7251	1042
728A-04AC110	1024
728A-04AC220	1024
728A-04AC24	1024
728A790-04AC220	1025
728A790-04DC24	1025

Code	Page
72KBIW13DPX	**317**
72KBIW13MVX	**317**
72KBIW13RVX	**320**
72SBIW13DPX	**317**
72SBIW13MVX	**317**
72SBIW13RVX	**320**
73016011	**1528**
73016020	**1528**
73016038	**1528**
73016046	**1528**
73016062	**1528**
73016070	**1528**
73016089	**1528**
73016095	**1528**
73016100	**1528**
73016118	**1528**
730312ABF	**888**
730316ABF	**888**
730322ABF	**888**
7304106	**822**
7304112	**822**
730516ABF	**888**
730522ABF	**888**
7306206	**822**
7306212	**822**
730722ABF	**888**
7308306	**822**
7308312	**822**
73500A3	**1664**
73530A3	**1664**
73600A3	**1664**
7360BA3	**1664**
73610A3	**1664**
73640A3	**1664**
73KBIW17DPX	**317**
73KBIW17MVX	**317**
73SBIW17DPX	**317**
73SBIW17MVX	**317**
7400	**1042**
74000	**55**
74001	**55**
74002	**55**
7400215	**1689**
74003	**55**
74004	**55**
74005	**55**
74006	**55**
74007	**55**
74008	**55**
74009	**55**
7401	**1042**
74010	**55**
74011	**55**
74012	**55**
74014	**55**
74015	**55**
740516ABF	**888**
740722ABF	**888**
7432 10-1/2	**832**
7432 10-1/4	**832**
7432 10-3/8	**832**
7432 12-1/2	**832**
7432 12-1/4	**832**
7432 12-3/8	**832**
7432 16-1/2	**832**
7432 16-3/4	**832**
7432 4-1/8	**832**
7432 4-M5	**832**
7432 6-1/4	**832**
7432 6-1/8	**832**
7432 6-M5	**832**
7432 8-1/4	**832**
7432 8-1/8	**832**
7432 8-3/8	**832**
743516ABF	**888**
7442 10-1/4	**832**
7442 10-3/8	**832**
7442 12-1/2	**832**
7442 12-3/8	**832**
7442 16-1/2	**832**
7442 16-3/4	**832**
7442 4-1/8	**832**
7442 6-1/4	**832**
7442 6-1/8	**832**
7442 8-1/4	**832**
7442 8-1/8	**832**
7442 8-3/8	**832**
74KBIW21DPX	**317**
74KBIW21MVX	**317**
74SBIW21DPX	**317**
74SBIW21MVX	**317**
750005	**1652**
750010	**1652**
750013	**1652**
750028	**1652**
750300ABF	**887**
750500ABF	**887**
750700ABF	**887**
7522 10-1/2	**832**
7522 10-1/4	**832**
7522 10-3/8	**832**
7522 12-1/2	**832**
7522 12-1/4	**832**
7522 12-3/8	**832**
7522 16-1/2	**832**
7522 16-3/4	**832**
7522 4-1/4	**832**
7522 4-1/8	**832**
7522 4-M5	**832**
7522 4-M7	**832**
7522 6-1/4	**832**
7522 6-1/8	**832**
7522 6-M5	**832**
7522 6-M7	**832**
7522 8-1/4	**832**
7522 8-1/8	**832**
7522 8-3/8	**832**
7526 4-1/8	**832**
7526 6-1/4	**832**
7526 6-1/8	**832**
7526 8-1/4	**832**
7526 8-1/8	**832**
7540 10	**833**
7540 12	**833**
7540 16	**833**
7540 4	**833**
7540 6	**833**
7540 8	**833**
7542 10-8-1/4	**833**
7542 10-8-3/8	**833**
7542 6-4-1/4	**833**
7542 6-4-1/8	**833**
7542 8-6-1/4	**833**
7542 8-6-1/8	**833**
7545 10-8	**833**
7545 6-4	**833**
7545 8-6	**833**
7550 10	**833**
7550 12	**833**
7550 16	**833**
7550 4	**833**
7550 6	**833**
7550 8	**833**
7555 10-10	**833**
7555 12-12	**833**
7555 4-4	**833**
7555 6-6	**833**
7555 8-8	**833**
7560 10	**833**
7560 10-8	**833**
7560 4	**833**
7560 6	**833**
7560 6-4	**833**
7560 8	**833**
7560 8-6	**833**
7562 10-1/4	**832**
7562 10-3/8	**832**
7562 4-1/8	**832**
7562 6-1/4	**832**
7562 6-1/8	**832**
7562 8-1/4	**832**
7562 8-1/8	**832**
7572 4-1/4	**832**
7572 4-1/8	**832**
7572 6-1/4	**832**
7572 6-1/8	**832**
7575 6-4	**833**
7575 8-6	**833**
7580 10	**833**
7580 12	**833**
7580 4	**833**
7580 6	**833**
7580 8	**833**
75C12-12RP	**319**
75C16-16RP	**319**
75C20-20RP	**319**
75C24-24RP	**319**
75KBIW26DPX	**317**
75KBIW26MVX	**317**
75MDC-12	**319**
75MDC-16	**319**
75MDC-20	**319**
75MDC-24	**319**
75MDC-32	**319**
75MDP-12	**319**
75MDP-16	**319**
75MDP-20	**319**
75MDP-24	**319**
75MDP-32	**319**
75N12-12RP	**319**
75N16-16RP	**319**
75N20-20RP	**319**
75N24-24RP	**319**
75SBIW26DPX	**317**
75SBIW26MVX	**317**
760300ABF	**888**
760500ABF	**888**
760700ABF	**888**
7610 10-1/4	**834**
7610 10-3/8	**834**
7610 12-3/8	**834**
7610 4-1/8	**834**
7610 6-1/4	**834**
7610 6-1/8	**834**
7610 8-1/4	**834**
7610 8-1/8	**834**
7612 02-10-1/4	**834**
7612 02-10-3/8	**834**
7612 02-12-3/8	**834**
7612 02-4-1/8	**834**
7612 02-6-1/4	**834**
7612 02-6-1/8	**834**
7612 02-8-1/4	**834**
7612 02-8-1/8	**834**
7612 03-10-1/4	**834**
7612 03-4-1/8	**834**
7612 03-6-1/4	**834**
7612 03-6-1/8	**834**
7612 03-8-1/4	**834**
7612 03-8-1/8	**834**
7622 10-1/4	**834**
7622 10-3/8	**834**
7622 12-3/8	**834**
7622 4-1/8	**834**
7622 6-1/4	**834**
7622 6-1/8	**834**
7622 8-1/4	**834**
7622 8-1/8	**834**
7632 02-1/4	**834**
7632 02-1/8	**834**
7632 02-3/8	**834**
7632 03-1/4	**834**
7632 03-1/8	**834**
7640 10-1/4	**834**
7640 4-1/8	**834**
7640 6-1/4	**834**
7640 6-1/8	**834**
7640 8-1/4	**834**
7640 8-1/8	**834**
7642 02-10-1/4	**834**
7642 02-4-1/8	**834**
7642 02-6-1/4	**834**
7642 02-6-1/8	**834**
7642 02-8-1/4	**834**
7642 02-8-1/8	**834**
7642 03-10-1/4	**834**
7642 03-4-1/8	**834**
7642 03-6-1/4	**834**
7642 03-6-1/8	**834**
7642 03-8-1/4	**834**
7642 03-8-1/8	**834**
765-0610	**183**
765-0610-6M	**183**
765-0810-6M	**183**
765-0813	**183**
765-1013	**183**
765-1013-6M	**183**
765-10X1.5	**183**
765-10X1.5-6M	**183**
765-10X2	**183**
765-1213	**183**
765-12X1.5	**183**
765-12X1.5-6M	**183**
765-12X2	**183**
765-1513	**183**
765-1515-6M	**183**
765-15X1.5	**183**
765-15X2	**183**
765-1602-6M	**183**
765-16X1.5	**183**
765-16X1.5-6M	**183**
765-16X2	**183**
765-18X1.5	**183**
765-18X2	**183**
7652 10-1/4	**834**
7652 10-3/8	**834**
7652 4-1/8	**834**
7652 6-1/4	**834**
7652 6-1/8	**834**
7652 8-1/4	**834**
7652 8-1/8	**834**
765-20X1.5	**183**
765-20X2	**183**
765-20X2-6M	**183**
765-20X3	**183**
765-22X1.5	**183**
765-22X2	**183**
765-25X1.5	**183**
765-25X2	**183**
765-25X2.5	**183**
765-25X2.5-6M	**183**
765-25X3	**183**
765-28X2	**183**
765-30X3	**183**
765-30X3-6M	**183**
765-35X3	**183**
765-42X3	**183**
765-6X1.5	**183**
765-6X1.5-6M	**183**
765-6X2	**183**
765-8X1.5	**183**
765-8X1.5-6M	**183**
765-8X2	**183**
7681-04	**70**
7681-06	**70**
7681-08	**70**
7681-12	**70**
7691-04	**71**
7691-06	**71**
7691-08	**71**
7691-12	**71**
76KBIW33DPX	**317**
76KBIW33MVX	**317**
76SBIW33MVX	**317**
7700	**1042**
770-0606	**158**
770-0808	**158**
7701	**1042**
770-1010	**158**
770-1212	**158**

Code	Page
770-1515	**158**
770-1818	**158**
770-2222	**158**
770-2828	**158**
770300ABF	**888**
770-3535	**158**
770-4242	**158**
770500ABF	**888**
770700ABF	**888**
771 04	**956**
771 05	**956**
771 06	**956**
771 07	**956**
771 08	**956**
771 09	**956**
771 10	**956**
771 11	**956**
771 12	**956**
771 13	**956**
771 14	**956**
7710061	**434**
7710062	**434**
7710063	**434**
7710064	**434**
7800 10-12	**833**
7800 4-6	**833**
7800 4-8	**833**
7800 6-10	**833**
7800 6-12	**833**
7800 6-8	**833**
7800 8-10	**833**
7800 8-12	**833**
7800215	**1689**
7801-04-04	**55**
7801-06-06	**55**
7801-08-08	**55**
7801-12-12	**55**
789-1	**946**
789-112	**946**
789-114	**946**
789-12	**946**
789-14	**946**
789-2	**946**
789-34	**946**
789-38	**946**
790001515	**1130**
790002222	**1130**
790002828	**1130**
790003535	**1130**
790004242	**1130**
790005454	**1130**
790-01AC110	**1025**
790-01AC110-VIS	**1025**
790-01AC220	**1025**
790-01AC220-VIS	**1025**
790-01DC24	**1025**
790-01DC24-VIS	**1025**
790-02AC110	**1025**
790-02AC110-VIS	**1025**
790-02AC220	**1025**
790-02AC220-VIS	**1025**
790-02AC24	**1025**
790-02AC24-VIS	**1025**
790-02DC24	**1025**
790-02DC24-VIS	**1025**
790-03AC110	**1025**
790-03AC110-VIS	**1025**
790-03AC220	**1025**
790-03AC220-VIS	**1025**
790-03AC24	**1025**
790-03AC24-VIS	**1025**
790-03DC24	**1025**
790-03DC24-VIS	**1025**
790-04AC110	**1025**
790-04AC110-VIS	**1025**
790-04AC220	**1025**
790-04AC220-VIS	**1025**
790-04AC24	**1025**
790-04AC24-VIS	**1025**
790-04DC24	**1025**
790-04DC24-VIS	**1025**
7901015012	**1129**
7901015034	**1129**
7901022012	**1129**
7901022034	**1129**
7901028100	**1129**
7901035100	**1129**
7901035114	**1129**
7901042112	**1129**
7901054200	**1129**
7901066212	**1129**
7902015012	**1129**
7902015034	**1129**
7902022012	**1129**
7902022034	**1129**
7902022100	**1129**
7902028034	**1129**
7902028100	**1129**
7902035114	**1129**
7902042112	**1129**
7902054200	**1129**
7908015012	**1129**
7908022034	**1129**
7908028100	**1129**
7908035114	**1129**
7908042112	**1129**
7908054200	**1129**
79100151515	**1132**
79100222222	**1132**
79100282828	**1132**
79100353535	**1132**
79100424242	**1132**
79100545454	**1132**
79110221522	**1132**
79110282228	**1132**
79110352235	**1132**
79110352835	**1132**
79110422842	**1132**
79110423542	**1132**
79110542254	**1132**
79110542854	**1132**
79110543554	**1132**
79110544254	**1132**
79120151215	**1132**
79120221222	**1132**
79120223422	**1132**
79120281228	**1132**
79120283428	**1132**
79120351235	**1132**
79120421242	**1132**
79120541254	**1132**
792101515	**1134**
792102222	**1134**
792102828	**1134**
792103535	**1134**
792104242	**1134**
792105454	**1134**
792301515	**1131**
792302222	**1131**
792302828	**1131**
792303535	**1131**
792304242	**1131**
792305454	**1131**
792401515	**1131**
792402222	**1131**
792402828	**1131**
792403535	**1131**
792404242	**1131**
792405454	**1131**
7931015012	**1133**
7931022034	**1133**
7931028100	**1133**
7932015012	**1133**
7932022034	**1133**
7932028100	**1133**
7941015	**1131**
7941022	**1131**
7941028	**1131**
7941035	**1131**
7941042	**1131**
7941054	**1131**
794302215	**1130**
794302815	**1130**
794302822	**1130**
794303522	**1130**
794303528	**1130**
794304222	**1130**
794304228	**1130**
794304235	**1130**
794305435	**1130**
794305442	**1130**
7950 10	**833**
7950 12	**833**
7950 4	**833**
7950 6	**833**
7950 8	**833**
7B02	**62**
7B0204	**62**
7B04	**62**
7B0406	**62**
7B0408	**62**
7B06	**62**
7B0608	**62**
7B08	**62**
7B0810	**62**
7B0812	**62**
7B10	**62**
7B12	**62**
7B1216	**62**
7B16	**62**
7B20	**62**
7B24	**62**
7B32	**62**
7BFF0404-1000	**1649**
7BFF0404-600	**1649**
7BFF0404-750	**1649**
7BSBC02	**71**
7BSBC04	**71**
7BSBC06	**71**
7BSBC08	**71**
7BSBC10	**71**
7BSBC12	**71**
7BSBC16	**71**
7BSBC20	**71**
7BSBC24	**71**
7BSBC32	**71**
7C20215	**1688**
7C30215	**1688**
7C40215	**1688**
7C50215	**1688**
7C60215	**1688**
7C70215	**1688**
7C80215	**1688**
7C90215	**1688**
7E-PBIND	**257**
7F-PBIND	**257**
7J07	**79**
7J08	**79**
7J09	**79**
7J12	**79**
7J14	**79**
7J17	**79**
7J19	**79**
7J21	**79**
7J26	**79**
7J30	**79**
7J40	**79**
7M12	**71**
7M14	**71**
7M16	**71**
7M18	**71**
7M20	**71**
7M22	**71**
7-MS	**1517**
7N02	**62**
7N04	**62**
7N06	**62**
7N08	**62**
7N12	**62**
7N16	**62**
7N20215	**1688**
7N24	**62**
7N30215	**1688**
7N40215	**1688**
7N50215	**1688**
7N60215	**1688**
7N70215	**1688**
7N80215	**1688**
7N90215	**1688**
7S20215	**1688**
7S30215	**1688**
7S40215	**1688**
7S50215	**1688**
7S60215	**1688**
7S70215	**1688**
7S80215	**1688**
7S90215	**1688**
7-SS	**1517**
8	
80001	**63**
80002	**63**
80003	**63**
80004	**63**
80005	**63**
80006	**63**
80008	**63**
800-100	**446**
8001469	**661**
800212ABF	**887**
800216ABF	**887**
800312ABF	**887**
800316ABF	**887**
800322ABF	**887**
8003354	**428**
800412ABF	**887**
800416ABF	**887**
800422ABF	**887**
800516ABF	**887**
800522ABF	**887**
800622ABF	**887**
800722ABF	**887**
800822ABF	**887**
800826ABF	**887**
800-950	**446**
800-951	**446**
8025330	**581**
8025331	**581**
8025335	**581**
8025336	**581**
8025337	**581**
8025354	**658**
8025355	**658**
8025356	**658**
8025357	**658**
8025358	**658**
8025359	**658**
8026208	**581**
8026209	**581**
8026210	**581**
8026219	**581**
8026221	**581**
8026223	**581**
8026225	**581**
8026227	**581**
8026261	**581**
8026263	**581**
8026265	**581**
8026267	**581**
8026269	**581**
8026297	**581**
8026299	**581**
8026301	**581**
8026303	**581**
8026334	**581**
8026335	**581**
8026336	**581**
8029134	**1020**
8029135	**1020**
8029136	**1020**
8029137	**1020**

Code	Page
8029138	**1020**
8029139	**1020**
8029144	**1020**
803-232	**446**
803-233	**446**
8035533	**428**
8035536	**428**
8035539	**428**
8035541	**428**
8035544	**428**
8035547	**428**
8035550	**428**
8035552	**428**
8035563	**428**
80360	**1551**
80361	**1551**
80362	**1551**
80381	**1551**
8043213	**579**
8043214	**579**
8043215	**579**
8043217	**579**
8043218	**579**
8043219	**579**
80450	**1693**
8047613	**1017**
8047614	**1017**
8047615	**1017**
8047616	**1017**
8047617	**1017**
8047618	**1017**
8047619	**1017**
8047620	**1017**
8047622	**1017**
8047624	**1017**
8047626	**1017**
8047631	**1017**
8047642	**1017**
8047646	**1017**
8048123	**1017**
8048124	**1017**
8048125	**1017**
8048126	**1017**
8048127	**1017**
8048128	**1017**
8048129	**1017**
8048130	**1017**
8048131	**1017**
8048132	**1017**
8048134	**1017**
8048136	**1017**
8048138	**1017**
8048140	**1017**
8048142	**1017**
8048143	**1017**
8048145	**1017**
8048147	**1017**
8048149	**1017**
8048151	**1017**
8048671	**912**
8048673	**912**
8048675	**912**
8048677	**912**
8048679	**912**

Code	Page
8048681	**912**
8048683	**912**
8048685	**912**
8048687	**912**
8048689	**912**
8048691	**912**
8048693	**912**
8048695	**912**
8048697	**912**
8048699	**912**
8048701	**912**
8048703	**912**
8048705	**912**
8048707	**912**
8048709	**912**
8048711	**912**
8048713	**912**
8048715	**912**
8048717	**912**
8048719	**912**
8049880	**579**
8049881	**579**
8049882	**579**
8050B-11	**385**
8051B-11	**385**
8060020511	**1653**
8060020512	**1653**
8060020513	**1653**
8060020514	**1653**
8060020516	**1653**
80601	**1551**
8060527	**1050**
8060528	**1050**
8060530	**1050**
8060533	**1050**
8060536	**1050**
8060538	**1050**
8065261	**1017**
8065262	**1017**
8065263	**1017**
8065264	**1017**
8065265	**1017**
8065266	**1017**
8065267	**1017**
8065268	**1017**
8065269	**1017**
8065270	**1017**
8065271	**1017**
8065272	**1017**
8065273	**1017**
8065274	**1017**
8065275	**1017**
8065276	**1017**
8068723	**815**
8068724	**815**
8068725	**815**
8068726	**815**
8068727	**815**
8068728	**815**
8068729	**815**
8068732	**815**
8068734	**815**
8068735	**815**
8068736	**815**

Code	Page
8068747	**815**
8068748	**815**
8068749	**815**
8068750	**815**
8068751	**815**
8068752	**815**
807CL	**1626**
8080020482	**1653**
8080020483	**1653**
8080020486	**1653**
8080020487	**1653**
8080020489	**1653**
8080020492	**1653**
8080020501	**1653**
8080020502	**1653**
8080020504	**1653**
8080020505	**1653**
8080020506	**1653**
8086641	**660**
8086642	**660**
8086643	**660**
8086644	**660**
8086645	**660**
8086646	**660**
8090020420	**1653**
8090020423	**1653**
8090020425	**1653**
8090020428	**1653**
8090020430	**1653**
8090020436	**1653**
8090020443	**1653**
8098254	**659**
8098256	**659**
8098257	**659**
8098258	**659**
8098259	**659**
8098264	**659**
8098265	**659**
8098266	**659**
8098300	**659**
8098302	**659**
8098304	**659**
8098305	**659**
8098307	**659**
8098309	**659**
8098310	**659**
8098312	**659**
81/2-MS	**1517**
81/2-SS	**1517**
81000	**392**
8100215	**1689**
810212ABF	**887**
810216ABF	**887**
810312ABF	**887**
810316ABF	**887**
810322ABF	**887**
810412ABF	**887**
810416ABF	**887**
810422ABF	**887**
810516ABF	**887**
810522ABF	**887**
810622ABF	**887**
810722ABF	**887**
810822ABF	**887**

Code	Page
8119201	**662**
8119204	**662**
81400	**392**
81500	**392**
815200ABF	**889**
815300ABF	**889**
815400ABF	**889**
815500ABF	**889**
8156120050	**1535**
8156120060	**1535**
8156120145	**1535**
8156120170	**1535**
8156120270	**1535**
8156120325	**1535**
8156120380	**1535**
8156130135	**1535**
8157910	**660**
8157911	**660**
81606	**392**
81608	**392**
81610	**392**
81612	**392**
820014-51KIT	**688**
820014-52KIT	**688**
8200215	**1689**
820024-50KIT	**688**
820048-89KIT	**688**
820068-51KIT	**688**
823AA	**1034**
823AC	**1034**
823AL	**1034**
829AN00100A	**216**
829AN00101A	**216**
829AN00102A	**215**
829AN00103A	**217**
829AN00105A	**217**
829AN00132A	**216**
829AN00158A	**216**
829AN00165A	**217**
829AN00176A	**215**
829AN00221A	**217**
83000	**64**
83001	**64**
83002	**64**
8300215	**1689**
83003	**64**
83004	**64**
83005	**64**
830AE	**1034**
840014-51KIT	**688**
840014-52KIT	**688**
8400215	**1689**
840024-50KIT	**688**
840048-01KIT	**688**
840068-51KIT	**688**
8432 4-1/8	**873**
8432 6-1/8	**873**
8432 8-1/4	**873**
8432 8-1/8	**873**
850200ABF	**888**
850300ABF	**888**
850400ABF	**888**
850600ABF	**888**
850700ABF	**888**

Code	Page
850800ABF	**888**
851000	**1653**
851013	**1653**
851017	**1653**
851019	**1653**
8512 10-1/4	**873**
8512 10-3/8	**873**
8512 12-1/2	**873**
8512 12-3/8	**873**
8512 4-1/8	**873**
8512 6-1/4	**873**
8512 6-1/8	**873**
8512 8-1/4	**873**
8512 8-1/8	**873**
8522 10-1/4	**873**
8522 10-3/8	**873**
8522 12-1/2	**873**
8522 12-3/8	**873**
8522 4-1/8	**873**
8522 6-1/4	**873**
8522 6-1/8	**873**
8522 8-1/4	**873**
8522 8-1/8	**873**
8540 4	**873**
8540 6	**873**
8540 8	**873**
8550 4	**873**
8550 6	**873**
8550 8	**873**
8580 4	**873**
8580 6	**873**
8580 8	**873**
859160	**210**
859172	**211**
859177	**211**
859195	**210**
859197	**212**
860110ABF	**888**
860200ABF	**888**
860300ABF	**888**
860400ABF	**888**
860500ABF	**888**
860600ABF	**888**
860700ABF	**888**
860800ABF	**888**
860900ABF	**888**
8624B-11	**385**
865637	**219**
865638	**219**
865882	**219**
865884	**219**
867332	**218**
867335	**218**
867339	**218**
867340	**218**
867364	**218**
868300	**218**
868314	**218**
868651	**218**
869628	**213**
869641	**213**
869951	**210**
869952	**211**
869953	**211**

Code	Page
869959	210
869960	212
86KBAW13MVX	381
86KBIW13MVX	381
86KBTF06MVX	381
86KBTF09MVX	381
86KBTH09MVX	381
86KBTR09MVX	381
86KFAW13MVX	381
86KFIW13MVX	381
86KFTF09MVX	381
86KFTR09MVX	381
86SBAK13MVX	382
86SFAK10MXX	382
86SFAK13MXX	382
86SFAK17MXX	382
86-SILICONE	382
86-VITON	382
8700215	1689
870024	213
870036	213
870038	213
870043	213
8701-04-14	74
8701-06-18	74
8701-08-22	74
8701-12-30	74
8701-16-33	74
870177	211
870200ABF	888
870221	210
870300ABF	888
870378	211
870400ABF	888
870500ABF	888
870518	212
870600ABF	888
870804	210
871358	210
871505	210
8751-04-14	72
8751-06-18	72
8751-08-22	72
8751-10-24	72
8751-12-30	72
8751-16-33	72
877-0004	1209
877-0006	1209
877-0008	1209
877-0009	1209
877-0010	1209
877-0012	1209
877-0013	1209
877-0015	1209
877-0016	1209
877-0018	1209
877-0027	1209
877-0125	1209
8787-11	385
8788-11	385
879046	218
879342	218
87KBTF09MVX	383
87KBTF13MVX	383
87KBTH09MVX	383
87KBTH13MVX	383
87KFTF09MVX	383
87KFTF13MVX	383
87KFTH09MVX	383
87KFTH13MVX	383
87KFTR09MVX	383
87KFTR13MVX	383
87SBAK17MVX	383
87SBAK21MVX	383
87SFAK13MXX	383
87SFAK17MXX	383
87SFAK21MXX	383
87SFIW13SXN	383
87SFIW17SXN	383
87-SILICONE	383
87-VITON	383
880001515	1130
880002222	1130
880002828	1130
880003535	1130
880004242	1130
880005454	1130
8801015012	1129
8801015034	1129
8801022012	1129
8801022034	1129
8801028100	1129
8801035100	1129
8801035114	1129
8801042112	1129
8801054200	1129
8801066212	1129
8802015012	1129
8802015034	1129
8802022012	1129
8802022034	1129
8802022100	1129
8802028034	1129
8802028100	1129
8802035114	1129
8802042112	1129
8802054200	1129
880401515	1130
880402222	1130
880402828	1130
880403535	1130
880404242	1130
880405454	1130
880553	218
8807-11	385
8808015012	1129
8808022034	1129
8808028100	1129
8808035114	1129
8808042112	1129
8808054200	1129
88100151515	1132
88100222222	1132
88100282828	1132
88100353535	1132
88100424242	1132
88100545454	1132
88110221522	1132
88110282228	1132
88110352235	1132
88110352835	1132
88110422242	1132
88110422842	1132
88110423542	1132
88110542254	1132
88110542854	1132
88110543554	1132
88110544254	1132
88120151215	1132
88120221222	1132
88120223422	1132
88120281228	1132
88120283428	1132
88120351235	1132
88120421242	1132
88120541254	1132
882001515	1131
882002222	1131
882002828	1131
882003535	1131
882004242	1131
882005454	1131
882301515	1131
882302222	1131
882302828	1131
882303535	1131
882304242	1131
882305454	1131
8831015012	1133
8831022034	1133
8831028100	1133
8832015012	1133
8832022034	1133
8832028100	1133
8841015	1131
8841022	1131
8841028	1131
8841035	1131
8841042	1131
8841054	1131
884302215	1130
884302815	1130
884302822	1130
884303522	1130
884303528	1130
884304222	1130
884304228	1130
884304235	1130
884305435	1130
884305442	1130
888	599
888.02	599
888.03	599
888.04	599
888.05	599
888.06	599
888.07	599
888.08	599
888.09	599
888.10	599
888.11.01	599
888.11.02	599
888.11.03	599
8880.32.C.39.F00	598
88801	905
88802	905
8880520035F00	598
8880520039F00	598
8884.32.A.39.F00	598
8884.32.C.39.F00	598
8884520035F00	598
8884520039F00	598
8900000001	859
8900000002	859
8900000003	859
8900000004	859
8900000005	859
8900000006	859
8900000007	859
8900000008	859
8900000009	859
8900000010	859
8900000011	859
8900000012	859
8900000013	859
8900000014	859
8900000015	859
8900000016	859
8900000017	859
8900000018	859
8900-1/4	1160
8903000001	859
8903000002	859
8903000003	859
8903000004	859
8903000005	859
8903000006	859
8903000007	859
8903000008	859
8904000001	860
8904000002	860
8904000003	860
8904000004	860
8904000005	860
8904000006	860
8904000007	860
8904000008	860
8904000009	860
8905000001	860
8905000003	860
8905000004	860
8905000005	860
8905000006	860
8910600001	859
8910600002	859
8910600003	859
8910600004	859
8910600005	859
8910600006	859
8910-M5	1160
8911100001	859
8911100002	859
8911100003	859
8911100004	859
8911100005	859
8911100006	859
8911100007	859
8911100008	859
8911100009	859
8911100011	859
8911100012	859
8911100013	859
8911100014	859
8911100015	859
8911100016	859
8911100017	859
8913000001	860
8913000002	860
8913000003	860
8913000004	860
8913000005	860
8913000006	860
8915-M5	1160
8920-1/4	1160
8920-1/8	1160
8921100001	859
8921100005	859
8921100006	859
8921100007	859
8921100008	859
8921100009	859
8921100010	859
8921100011	859
8921100012	859
8921100013	859
8921100014	859
8923000001	860
8923000003	860
8923000004	860
8923000005	860
8923000006	860
8925-1/4	1160
8925-M5	1160
89445	1742
8950-4/2.7-1/8	1160
8950-6/4-1/4	1160
8950-6/4-M5	1160
8950-8/6-1/4	1160
8950-8/6-1/8	1160
8952-1/4	1160
8952-1/8	1160
8952DL-12	385
8955-10/8-1/4	1160
8955-6/4-1/4	1160
8955-6/4-1/8	1160
8955-8/6-1/8	1160
8957-1/4	1160
8957-1/8	1160
8960-6/4-1/8	1160
8960-8/6-1/8	1160
8962-1/8	1160
8965-10/8-1/4	1160
8965-4/2.7-M5	1160
8965-6/4-M5	1160
8965-8/6-1/8	1160
8967-1/4	1160
8967-1/8	1160
8970000001	860
8970000002	860
8970000003	860

Code	Page
8970000004	860
8970000005	860
8970-6/4-1/4	1160
8970-6/4-M5	1160
8970-8/6-1/4	1160
8972-1/4	1160
8972-1/8	1160
8975-4/2.7-1/8	1160
8975-6/4-1/8	1160
8977-1/4	1160
8977-1/8	1160
8BP0202	68
8BP0404	68
8BP0406	68
8BP0604	68
8BP0606	68
8BP0608	68
8BP0806	68
8BP0808	68
8BP0812	68
8BP1010	68
8BP1208	68
8BP1212	68
8BP1616	68
8BP2020	68
8BP2424	68
8BP3232	68
8BPX0404	68
8BPX0606	68
8BPX0608	68
8BPX0806	68
8BPX0808	68
8BPX1010	68
8BPX1208	68
8BPX1212	68
8BPX1616	68
8C20215	1687
8C30215	1687
8C40215	1687
8C50215	1687
8C60215	1687
8C70215	1687
8C80215	1687
8C90215	1687
8G-10J-MF-10K	91
8G-10J-MM-10K	90
8G-12G-MF-A-10K	91
8G-12G-MM-10K	90
8G-12J-MF-10K	91
8G-12J-MM-10K	90
8G-12N-MM-10K	90
8G-16G-MF-A-10K	91
8G-16G-MM-10K	90
8G-16J-MM-10K	90
8G-16N-MM-10K	90
8G-2G-MF-B-10K	92
8G-4G-MF-B-10K	92
8G-4J-MM-10K	90
8G-4N-MM-10K	90
8G-6G-MF-B-10K	92
8G-6J-MF-10K	91
8G-6N-MM-10K	90
8G-8G-FF-10K	92
8G-8G-MF-A-10K	91
8G-8G-MM-10K	90
8G-8J-MF-10K	91
8G-8J-MM-10K	90
8G-8N-MM-10K	90
8G-C-10K	94
8G-E-FF-10K	93
8G-E-MF-10K	93
8G-E-MM-10K	92
8G-P-10K	94
8G-T-FF-10K	94
8G-T-MM-10K	93
8J-10J-MM-10K	90
8J-12J-MM-10K	90
8J-4J-MF-10K	91
8J-6J-MF-10K	91
8J-6N-MF-A-10K	91
8J-8J-FF-10K	92
8J-8J-MM-10K	90
8J-8N-MF-A-10K	91
8J-C-10K	94
8J-E-FF-10K	93
8J-E-MF-10K	93
8JITS	80
8JMTS	80
8JP0707	78
8JP0808	78
8JP0909	78
8J-P-10K	94
8JP1212	78
8JP1414	78
8JP1717	78
8JP2121	78
8J-T-FF-10K	94
8J-T-MM-10K	93
8JTN	80
8MP1212	68
8MP1414	68
8MP1616	68
8MP1818	68
8MP2020	68
8MP2222	68
8MP2424	68
8N-10J-MF-10K	91
8N-12J-MF-10K	91
8N-12J-MM-10K	90
8N-12N-FF-10K	92
8N-12N-MF-A-10K	91
8N-16N-FF-10K	92
8N-16N-MF-A-10K	91
8N20215	1687
8N-2N-MF-B-10K	92
8N-2N-MM-10K	90
8N30215	1687
8N40215	1687
8N-4J-MM-10K	90
8N-4N-MF-B-10K	92
8N50215	1687
8N60215	1687
8N-6J-MM-10K	90
8N-6N-MF-B-10K	92
8N70215	1687
8N80215	1687
8N-8J-E-MF-10K	93
8N-8J-MM-10K	90
8N-8N-FF-10K	92
8N-8N-MF-A-10K	91
8N-8N-MM-10K	90
8N90215	1687
8N-C-10K	94
8N-E-10K	93
8N-E-MF-10K	93
8N-E-MM-10K	92
8N-P-10K	94
8N-T-10K	94
8N-T-MM-10K	93
8N-X-10K	94
8S20215	1687
8S30215	1687
8S40215	1687
8S50215	1687
8S60215	1687
8S70215	1687
8S80215	1687
8S90215	1687
9	
900.18.8E	702
900000011J4B5	1082
900000011J9B5	1082
900000011K4B5	1082
900000011W0B5	1082
900000011W3B5	1082
900000011Y9B5	1082
900006020BL	1082
900006025BL	1082
900006032BL	1082
900006040BL	1082
900006050BL	1082
900006063BL	1082
9000401	624
9000402	624
9000600	624
9000802	672
9000803	664
9001000001	1082
9001000002	1082
9001000003	1082
9001000004	1082
9001000005	1082
9001000006	1082
9001000007	1082
9001000008A	1082
9001000009	1082
9001000011	1082
9001000012	1082
9001000013	1082
9001000014	1082
9001001C	824
9001002C	824
9001003	762
9001004	762
9001004/0	762
9001007C	824
9001008	762
9001009	762
9001010	762
9001011C	824
9001012C	824
9001016	762
9001020C	824
9001021C	824
9001022C	824
9001030	762
9001069	762
9001070	762
9001101V	824
9001102V	824
9001103V	824
9001104V	824
9001115V	824
9001120V	824
9001121V	824
9001122V	824
9001609B	824
9001610B	824
9001620B	824
9001621B	824
9001622B	824
9001623B	824
9001624B	824
9001625B	824
9002100	705
9002180	705
9002300	705
9002380	705
9003000001	1082
9003000002	1082
9003000003	1082
9003000004	1082
9004000001	1082
9004000002	1082
9004000003	1082
9004000004	1082
9004000006	1082
901 C1A	622
901 F1A	622
901 G1A	622
901 H1	622
902 C2A	622
902 F2A	622
902 G2A	622
902 H2	622
9011001C	824
9011003C	824
9011004C	824
9011005C	824
9011006C	824
9011007C	824
9011008C	824
9011009C	824
9011011C	824
9011014C	824
9011015C	824
9011016C	824
9011101V	824
9011102V	824
9011103V	824
9011104V	824
9011105V	824
9011106V	824
9011107V	825
9011110V	824
9011111V	824
9011114V	824
9011123V	824
9011124V	824
9011125V	824
9011601B	824
9011602B	824
9011605B	824
9011606B	824
9011607B	824
9011608B	824
9011609B	824
9011610B	824
9011612B	824
9011623B	824
9011624B	824
9011625B	824
9013000001	1083
9013000002	1083
9013000003	1083
9013000004	1083
9013000005	1083
9013000006	1083
9014000001	1083
9014000002	1083
9014000003	1083
9014000004	1083
9014000005	1083
9015000001	1082
9015000002	1082
9015000003	1082
9015-04-06AS	80
9015-04-12AS	80
9015-06-08AS	80
9015-06-12AS	80
9015-08-10AS	80
9015-10-12AS	80
9015-12-16AS	80
9015-16-20AS	80
9016000001	1082
9016000002	1082
9016000003	1082
9016000004	1082
9021001C	825
9021002C	825
9021005C	825
9021006C	825
9021007C	825
9021008C	825
9021009C	825
9021011C	825
9021012C	825
9021014C	825
9021015C	825
9021016C	825
9021101V	825
9021102V	825
9021105V	825
9021106V	825
9021108V	825
9021109V	825
9021111V	825
9021112V	825
9021114V	825
9021115V	825

Code	Page
9021116V	**825**
9021201B	**825**
9021202B	**825**
9021205B	**825**
9021206B	**825**
9021207B	**825**
9021208B	**825**
9021209B	**825**
9021211B	**825**
9021212C	**825**
9021214B	**825**
9021215B	**825**
9021216B	**825**
9023000001	**1083**
9023000002	**1083**
9023000003	**1083**
9023000004	**1083**
9023000005	**1083**
9023000006	**1083**
9023500001	**1083**
9023500002	**1083**
9023500003	**1083**
9023500004	**1083**
9023500005	**1083**
9023500008	**1083**
9023500013	**1083**
9023600001	**1082**
9023600002	**1082**
9023600003	**1082**
9023600005	**1082**
9023600006	**1082**
9023600007	**1082**
9023600008	**1082**
9023600017A	**1082**
9023600018A	**1082**
9024000004	**1084**
9024000006	**1084**
9024000007	**1084**
9024000010	**1084**
9024000011	**1084**
9024100001	**1084**
9024100002	**1084**
9024200001	**1084**
9024200002	**1084**
9024200004	**1084**
9025000017A	**1082**
9025900001	**1083**
9025900002	**1083**
9025900003	**1083**
9025900004	**1083**
9025900005	**1083**
903 C3A	**622**
903 F3A	**622**
903 G3A	**622**
903 H3	**622**
9031	**385**
9031001C	**825**
9031002C	**825**
9031003C	**825**
9031004C	**825**
9031005C	**825**
9031006C	**825**
9031007C	**825**
9031008C	**825**
9031009C	**825**
9031010C	**825**
9031011C	**825**
9031012C	**825**
9031014C	**825**
9031015C	**825**
9031016C	**825**
9031101V	**825**
9031102V	**825**
9031103V	**825**
9031104V	**825**
9031105V	**825**
9031106V	**825**
9031107V	**825**
9031108V	**825**
9031109V	**825**
9031110V	**825**
9031111V	**825**
9031112V	**825**
9031114V	**825**
9031115V	**825**
9031116V	**825**
9031201B	**825**
9031202B	**825**
9031203B	**825**
9031204B	**825**
9031205B	**825**
9031206B	**825**
9031207B	**825**
9031208B	**825**
9031209B	**825**
9031210B	**825**
9031211B	**825**
9031212B	**825**
9031214B	**825**
9031215B	**825**
9031216B	**825**
9031301C	**825**
9031302C	**825**
9031303C	**825**
9031401V	**825**
9031402V	**825**
9031403V	**825**
9031501B	**825**
9031502B	**825**
9031503B	**825**
9041001	**827**
9041002	**827**
9041003	**827**
9041004	**827**
9041005	**827**
9041201	**827**
9041202	**827**
9041203	**827**
9041204	**827**
9041205	**827**
9041301	**827**
9041316	**827**
9041324	**827**
9041401	**827**
9041402	**827**
9041408	**827**
9041409	**827**
9041410	**827**
9041411	**827**
9041412	**827**
9041501	**827**
9041502	**827**
9041508	**827**
9041509	**827**
9041510	**827**
9041511	**827**
9041512	**827**
9042	**385**
9060000001	**1082**
9060000002	**1082**
9060000003	**1082**
9060200001	**1083**
9060200002	**1083**
9061000001	**1083**
9061000002	**1083**
9061000003	**1083**
9061000004	**1083**
9061000006	**1083**
9061316	**829**
9061324	**829**
9061601	**623**
9062000001	**1083**
9062000002	**1083**
9062000003	**1083**
9062000005	**1083**
9062000006	**1083**
9062000007	**1083**
9062000008	**1083**
9062000009A	**1083**
9062000010A	**1083**
9062000011	**1083**
9062110	**831**
9062216	**831**
9062224	**831**
9063016	**829**
9063024	**829**
9063116	**829**
9063124	**829**
9063308	**829**
9063309	**829**
9063310	**829**
9063311	**829**
9064016	**829**
9064024	**829**
9064200001	**1083**
9064200002	**1083**
9064400001	**1083**
9064400002	**1083**
9065016	**830**
9065024	**830**
9065116	**830**
9065124	**830**
9066016	**830**
9066024	**830**
9066116	**830**
9066124	**830**
9067016	**830**
9067024	**830**
9067108	**830**
9067109	**830**
9067110	**830**
9067111	**830**
9068016	**830**
9068024	**830**
9068216	**830**
9068224	**830**
9069016	**831**
9069024	**831**
9069224	**831**
9069408	**831**
9069409	**831**
9069410	**831**
9069411	**831**
9069610	**831**
9069611	**831**
9070000001	**1084**
9070000002	**1084**
9070000003	**1084**
9070000004	**1084**
9070000005	**1084**
9070000006	**1084**
9072000001	**1084**
9072000002	**1084**
9081500001	**1083**
9081500002	**1083**
9081500003	**1083**
9081500004	**1083**
9081500005	**1083**
9081500006	**1083**
9081700001	**1083**
9088000001	**1083**
9090001	**824**
9090002	**824**
9090003	**824**
91/2-MS	**1517**
91/2-SS	**1517**
910.04.SDP011414	**1223**
910.04.SDP012828	**1223**
910.04.SDP030606	**1223**
910.04.SDP032727	**1223**
910.04.SDP062727	**1223**
910.04.SDP142828	**1223**
910.06.SDP011414	**1223**
910.06.SDP030606	**1223**
910.06.SDP062727	**1223**
910.06.SDP142828	**1223**
910.10.SDP011414	**1223**
910.10.SDP012828	**1223**
9101201	**827**
9126344341	**513**
9126344342	**513**
9129-04	**81**
9129-06	**81**
9129-08	**81**
9129-10	**81**
9129-12	**81**
9129-16	**81**
9129-20	**81**
9129-24	**81**
9170301	**664**
919191	**224**
919262	**223**
919632	**223**
919656	**223**
919682	**224**
919772	**223**
919805	**223**
919850	**223**
9200 10	**978**
9200 11	**978**
9200 12	**978**
9200 13	**978**
9200 14	**978**
9200 16	**978**
9200401	**675**
9200601	**676**
9200701	**664**
9200703	**624**
9201 10	**978**
9201 11	**978**
9201 12	**978**
9201 13	**978**
9201 14	**978**
9201 16	**978**
9201 18	**978**
9201001	**676**
9201201	**827**
920227	**224**
9202L	**1674**
9203L	**1674**
92100	**1694**
9210000	**672**
9210001	**672**
9210002	**672**
9210003	**672**
9210010	**672**
9210011	**672**
9210012	**672**
9210013	**672**
9210014	**672**
9210150	**672**
9210151	**672**
9210155	**672**
9210156	**672**
9210160	**672**
9210161	**672**
9210165	**672**
9210166	**672**
922733	**223**
922850	**223**
922851	**223**
923468	**223**
923469	**223**
923470	**223**
923471	**223**
923496	**223**
923497	**223**
923498	**223**
923548	**223**
923AL	**1034**
923EA	**1034**
923EC	**1034**
923EE	**1034**
9250102	**676**
9250103	**676**
9251708	**664**
9251709	**664**
9251712	**664**
92519	**1694**
9254	**490**

Code	Page
9255	**490**
9255201	**676**
92603	**1695**
92608	**1695**
92609	**1695**
9261	**490**
92611	**1695**
92612	**1695**
92613	**1695**
9262	**490**
9263	**490**
92630	**1692**
9264	**490**
926501	**250**
92702	**1692**
92703	**1692**
92706	**1692**
92707	**1692**
92711	**1692**
92788	**1694**
92906	**1696**
92908	**1696**
92909	**1696**
92910	**1696**
92923	**1692**
93000	**63**
930000140	**248**
930000141	**248**
930000142	**248**
930000149	**248**
930000150	**248**
930000151	**248**
93000-12VDC	**1690**
93001	**63**
93002	**63**
93003	**63**
93004	**63**
93005	**63**
93006	**63**
93019	**1694**
93039	**1695**
9305-04	**80**
9305-06	**80**
9305-08	**80**
9305-10	**80**
9305-12	**80**
9305-16	**80**
9305-20	**80**
93100	**60**
93101	**60**
93102	**60**
93103	**60**
93104	**60**
93105	**60**
93107	**60**
93108	**60**
9325-04	**80**
9325-06	**80**
9325-08	**80**
9325-10	**80**
9325-12	**80**
9325-16	**80**
9325-20	**80**
93354	**1694**
934AA	**1034**
934AC	**1034**
934AE	**1034**
93505	**1694**
93508	**1693**
93512	**1693**
93520	**1693**
9356-04-04	**81**
9356-06-06	**81**
9356-08-08	**81**
9356-10-10	**81**
9356-12-12	**81**
9356-16-16	**81**
9356-20-20	**81**
9356-24-24	**81**
93598	**1694**
93613	**1695**
93614	**1695**
93820	**1690**
9400401	**675**
9400601	**676**
9400701	**672**
9400702	**681**
9401001	**676**
9401002	**676**
9401201	**827**
9402-12-M16	**891**
9402-12-M22	**891**
9410-05-02	**892**
9410-6-02	**892**
9412-10/7-M12	**892**
9412-10/7-M16	**892**
9412-10/7-M22	**892**
9412-10-M12	**892**
9412-10-M16	**892**
9412-10-M22	**892**
9412-12-M12	**892**
9412-12-M16	**892**
9412-12-M22	**892**
9412-15/11-M16	**892**
9412-15/11-M22	**892**
9412-15-M16	**892**
9412-15-M22	**892**
9412-6-M10	**892**
9412-6-M12	**892**
9412-6-M16	**892**
9412-8-M12	**892**
9412-8-M16	**892**
9412-8-M22	**892**
94160	**1696**
9420-05-02	**892**
9420-6-02	**892**
9422-10-M16	**892**
9422-10-M22	**892**
9422-12-M12	**892**
9422-12-M16	**892**
9422-12-M22	**892**
9422-15-M16	**892**
9422-15-M22	**892**
9422-6-M10	**892**
9422-6-M12	**892**
9422-6-M16	**892**
9422-8-M12	**892**
9422-8-M16	**892**
9422-8-M22	**892**
9450102	**676**
9450103	**676**
9450105	**676**
9450-12-M16	**892**
9450-12-M22	**892**
94505	**65**
94506	**1694**
9450-8-M16	**892**
94512	**1694**
9455201	**676**
94630	**1692**
9463-6-M10	**891**
9463-6-M16	**891**
9463-8-M10	**891**
94706	**1692**
94820	**1690**
94853	**1692**
9500-05-02	**891**
9500-6-02	**891**
9502-10/7-M12	**891**
9502-10/7-M16	**891**
9502-10/7-M22	**891**
9502-10-M12	**891**
9502-10-M16	**891**
9502-10-M22	**891**
9502-12-M12	**891**
9502-12-M16	**891**
9502-12-M22	**891**
9502-15-M16	**891**
9502-15-M22	**891**
9502-16/12-M16	**891**
9502-16/12-M22	**891**
9502-16-M22	**891**
9502-18-M22	**891**
95022	**1695**
95024	**1695**
9502-6-M10	**891**
9502-6-M12	**891**
9502-6-M16	**891**
9502-6-M22	**891**
9502-8-M10	**891**
9502-8-M12	**891**
9502-8-M14	**891**
9502-8-M16	**891**
9502-8-M22	**891**
95031	**1693**
95032	**1693**
95033	**1693**
95034	**1693**
95035	**1693**
95036	**1693**
95037	**1693**
95038	**1693**
95039	**1693**
95040	**1693**
95041	**1694**
9505-04-04	**81**
9505-06-06	**81**
9505-08-08	**81**
9505-1	**978**
9505-10-10	**81**
9505-112	**978**
9505-114	**978**
9505-12	**978**
9505-12-12	**81**
9505-16-16	**81**
9505-2	**978**
9505-34	**978**
9506-04-04	**81**
9506-06-06	**81**
9506-08-08	**81**
9506-10-10	**81**
9506-12-12	**81**
9506-16-16	**81**
9506-20-20	**81**
9506-24-24	**81**
951 000 33	**622**
951 000 34	**622**
951 000 35	**622**
951 000 P11 23	**621**
951 000 P15 23	**621**
951 P11 23 U72	**621**
951 P11 23 U73	**621**
951 P11 23 U74	**621**
951 P11 23 U76	**621**
951 P11 23 U77	**621**
951 P11 23 U7H	**621**
951 P11 23 U7J	**621**
951 P11 23 U7K	**621**
9510-05-02	**891**
9510-6-02	**891**
9512-10/7-M12	**891**
9512-10/7-M16	**891**
9512-10/7-M22	**891**
9512-10-M12	**891**
9512-10-M16	**891**
9512-10-M18	**891**
9512-10-M22	**891**
9512-12-M12	**891**
9512-12-M14	**891**
9512-12-M16	**891**
9512-12-M22	**891**
9512-15/11-M16	**891**
9512-15-M16	**891**
9512-15-M22	**891**
9512-16/12-M16	**891**
9512-16/12-M22	**891**
9512-16-M22	**891**
9512-18-M22	**891**
9512-6-M10	**891**
9512-6-M12	**891**
9512-6-M14	**891**
9512-6-M16	**891**
9512-8-M10	**891**
9512-8-M12	**891**
9512-8-M14	**891**
9512-8-M16	**891**
9512-8-M22	**891**
9515-04-04	**81**
9515-04-04B	**81**
9515-04-06	**81**
9515-06-06	**81**
9515-08-06B	**81**
9515-08-08	**81**
9515-1	**978**
9515-10-08B	**81**
9515-10-10	**81**
9515-10-12	**81**
9515-112	**978**
9515-114	**978**
9515-12	**978**
9515-12-08	**81**
9515-12-12	**81**
9515-12-12B	**81**
9515-16-16	**81**
9515-16-16B	**81**
9515-2	**978**
9515-34	**978**
952 000 33	**622**
952 000 34	**622**
952 000 35	**622**
952 000 P11 23	**621**
952 000 P15 23	**621**
952 P11 23 U72	**621**
952 P11 23 U73	**621**
952 P11 23 U74	**621**
952 P11 23 U76	**621**
952 P11 23 U77	**621**
952 P11 23 U7H	**621**
952 P11 23 U7J	**621**
952 P11 23 U7K	**621**
9525-04-04	**81**
9525-06-06	**81**
9525-08-08	**81**
9525-10-10	**81**
9525-12-12	**81**
953 000 33	**622**
953 000 34	**622**
953 000 35	**622**
953 000 P15 23	**621**
953 P11 23 U72	**621**
953 P11 23 U73	**621**
953 P11 23 U74	**621**
953 P11 23 U76	**621**
953 P11 23 U77	**621**
953 P11 23 U7H	**621**
953 P11 23 U7J	**621**
953 P11 23 U7K	**621**
953-000-P11-23	**621**
9540-10	**892**
9540-12	**892**
9540-12-12-8	**892**
9540-15/11	**892**
9540-6	**892**
9540-8	**892**
9540-8-8-6	**892**
9550-10	**892**
9550-12	**892**
9550-6	**892**
9550-8	**892**
9580-10	**892**
9580-12	**892**
9580-15/11	**892**
9580-16/12	**892**
9580-18/14	**892**
9580-6	**892**
9580-8	**892**
9590-12-M18	**892**
9590-12-M18-S01	**892**
9590-8-M18	**892**
9590-8-M18-S01	**892**

Code	Page
9592-12-8-M18	**892**
9592-8-8-M18	**892**
95KSAK13BPN	**384**
95KSAK17BPN	**384**
95KSAK21BPN	**384**
95KSIW13BPN	**384**
95KSIW17BPN	**384**
95KSTF08BPN	**384**
95KSTF09BPN	**384**
95KSTF13BPN	**384**
96000	**70**
96001	**70**
96002	**70**
96003	**70**
96004	**70**
9600401	**675**
96005	**70**
9600601	**676**
96080	**1691**
96081	**1691**
961 000 33	**622**
96100	**1691**
962 000 33	**622**
963 000 33	**622**
96400	**61**
96410	**61**
96420	**61**
96430	**61**
96440	**61**
96450	**61**
96460	**61**
96470	**61**
96480	**61**
96490	**61**
96500	**61**
9650102	**676**
9650103	**676**
96SSAK13EXX	**384**
96SSAK13MXN	**384**
96SSAK17MXN	**384**
96SSIW13MXN	**384**
96SSIW17MXN	**384**
96SSTF06MXN	**384**
96SSTF09MXN	**384**
96SSTF10EXX	**384**
9700109	**672**
9700110	**672**
9705-04-04-04	**81**
9705-06-06-06	**81**
9705-08-08-08	**81**
9705-10-10-10	**81**
9705-12-12-12	**81**
9705-16-16-16	**81**
9706-04-04-04	**81**
9706-06-06-06	**81**
9706-08-08-08	**81**
9706-10-10-10	**81**
9706-12-12-12	**81**
9706-16-16-16	**81**
9706-20-20-20	**81**
9707-04-04-04	**81**
9707-06-06-06	**81**
9707-08-08-08	**81**
9707-10-10-10	**81**
9707-12-12-12	**81**
9707-16-16-16	**81**
9707-20-20-20	**81**
971 000 33	**622**
971-05-251	**1223**
971-05-256	**1223**
971-10-251	**1223**
971-10-256	**1223**
971-10-263	**1223**
971-10-266	**1223**
9711-14	**70**
9711-18	**70**
9711-22	**70**
9711-24	**70**
9711-30	**70**
9715-06-06-06	**81**
9715-08-08-08	**81**
9715-10-10-10	**81**
9715-12-12-12	**81**
9716-04-04-04	**81**
9716-06-06-06	**81**
9716-08-08-08	**81**
9716-10-10-10	**81**
9716-12-12-12	**81**
972 000 33	**622**
9721-14	**71**
9721-18	**71**
9721-22	**71**
9721-24	**71**
9721-30	**71**
973 000 33	**622**
9739-11	**385**
9741-14	**55**
9741-18	**55**
9741-22	**55**
9741-24	**55**
9741-30	**55**
9741-33	**55**
9750-11	**385**
975-05-272	**1223**
975-10-272	**1223**
9792D-12	**385**
9793D-12	**385**
99001	**76**
9900224-002	**224**
9900224-003	**224**
9925-04	**80**
9925-06	**80**
9925-08	**80**
9925-10	**80**
9925-12	**80**
9925-16	**80**
9925-20	**80**
9-946-02-00-012	**271**
9-946-02-00-020	**271**
9-946-02-01-020	**271**
9-946-04-00-010	**271**
A	
A00050	**1674**
A00055	**1674**
A00060	**1674**
A100G4RL	**1757**
A100G4RM	**1757**
A100G4RS	**1757**
A100G4RXL	**1757**
A100G4RXXL	**1757**
A100GNRL	**1757**
A100GNRM	**1757**
A100GNRXL	**1757**
A100GNRXXL	**1757**
A100K8RL	**1757**
A100K8RM	**1757**
A100K8RXL	**1757**
A100K8RXXL	**1757**
A100ORRL	**1757**
A100ORRM	**1757**
A100ORRS	**1757**
A100ORRXL	**1757**
A100ORRXXL	**1757**
A100R8RL	**1757**
A100R8RM	**1757**
A100R8RXL	**1757**
A100R8RXXL	**1757**
A10AA	**1034**
A10AC	**1034**
A10AE	**1034**
A10AL	**1034**
A112-AU	**1468**
A112-AU-NPT	**1468**
A112-BR	**1471**
A112-BR-NPT	**1471**
A112-PP	**1470**
A112-PP-NPT	**1470**
A112-SS	**1469**
A112-SS-NPT	**1469**
A114-AU	**1468**
A114-AU-NPT	**1468**
A114-BR	**1471**
A114-PP	**1470**
A114-PP-NPT	**1470**
A114-SS	**1469**
A114-SS-NPT	**1469**
A12/34-PP-NPT	**1470**
A120BKRL	**1757**
A120BKRM	**1757**
A120BKRS	**1757**
A120BKRXL	**1757**
A120BKRXS	**1757**
A120BKRXXL	**1757**
A120BKRXXS	**1757**
A120BKRXXXL	**1757**
A12-AU	**1468**
A12-AU-NPT	**1468**
A12-BR	**1471**
A12-BR-NPT	**1471**
A12-PP	**1470**
A12-SS	**1469**
A12-SS-NPT	**1469**
A140BKRL	**1757**
A140BKRM	**1757**
A140BKRS	**1757**
A140BKRXL	**1757**
A140BKRXS	**1757**
A140BKRXXL	**1757**
A140ORBL	**1757**
A140ORBM	**1757**
A140ORBXL	**1757**
A140ORBXXL	**1757**
A15050	**1674**
A15055	**1674**
A15060	**1674**
A1-AU	**1468**
A1-AU-NPT	**1468**
A1-BR	**1471**
A1-BR-NPT	**1471**
A1N2H2 09	**1004**
A1N2H2 10	**1004**
A1N2H2 11	**1004**
A1N2H2 12	**1004**
A1N2H2 13	**1004**
A1N2H2 14	**1004**
A1N2H2 16	**1004**
A1N2H2 18	**1004**
A1N2H2 20	**1004**
A1-PP	**1470**
A1-PP-NPT	**1470**
A1-SS	**1469**
A1-SS-NPT	**1469**
A1V2H2 09	**959**
A1V2H2 10	**959**
A1V2H2 11	**959**
A1V2H2 12	**959**
A1V2H2 13	**959**
A1V2H2 14	**959**
A1V2H2 16	**959**
A1V2H2 18	**959**
A1V2H2 20	**959**
A2000-BRKT	**651**
A212-AU	**1468**
A212-AU-NPT	**1468**
A212-BR	**1471**
A212-BR-NPT	**1471**
A212-SS	**1469**
A212-SS-NPT	**1469**
A25050	**1674**
A25055	**1674**
A25060	**1674**
A270060	**1540**
A270120	**1540**
A270160	**1540**
A270200	**1540**
A270250	**1540**
A270280	**1540**
A270320	**1540**
A270380	**1540**
A270450	**1540**
A270500	**1540**
A270630	**1540**
A271TARL	**1758**
A271TARXL	**1758**
A280060	**1540**
A280100	**1540**
A280120	**1540**
A280160	**1540**
A280200	**1540**
A280250	**1540**
A280280	**1540**
A280320	**1540**
A280380	**1540**
A280500	**1540**
A2-AU	**1468**
A2-AU-NPT	**1468**
A2-BR	**1471**
A2-BR-NPT	**1471**
A2-PP	**1470**
A2-PP-NPT	**1470**
A2-SS	**1469**
A2-SS-NPT	**1469**
A3000-BRKT	**651**
A321 0C2	**592**
A321 0C2 U72	**592**
A321 0C2 U73	**592**
A321 0C2 U74	**592**
A321 0C2 U76	**592**
A321 0C2 U7H	**592**
A321 0C2 U7J	**592**
A321 0C2 U7K	**592**
A321 1C2	**592**
A321 1C2 U72	**592**
A321 1C2 U73	**592**
A321 1C2 U74	**592**
A321 1C2 U76	**592**
A321 1C2 U7H	**592**
A321 1C2 U7J	**592**
A321 1C2 U7K	**592**
A321 1D2	**592**
A321 1D2 U72	**592**
A321 1D2 U73	**592**
A321 1D2 U74	**592**
A321 1D2 U76	**592**
A321 1D2 U7H	**592**
A321 1D2 U7J	**592**
A321 1D2 U7K	**592**
A321 1E2	**592**
A321 1E2 U72	**592**
A321 1E2 U73	**592**
A321 1E2 U74	**592**
A321 1E2 U76	**592**
A321 1E2 U7H	**592**
A321 1E2 U7J	**592**
A321 1E2 U7K	**592**
A322 0C2	**592**
A322 0C2 U72	**592**
A322 0C2 U73	**592**
A322 0C2 U74	**592**
A322 0C2 U76	**592**
A322 0C2 U7H	**592**
A322 0C2 U7J	**592**
A322 0C2 U7K	**592**
A322 1C2	**592**
A322 1C2 U72	**592**
A322 1C2 U73	**592**
A322 1C2 U74	**592**
A322 1C2 U76	**592**
A322 1C2 U7H	**592**
A322 1C2 U7J	**592**
A322 1C2 U7K	**592**
A331 0C2	**592**
A331 0C2 U72	**592**
A331 0C2 U73	**592**
A331 0C2 U74	**592**
A331 0C2 U76	**592**
A331 0C2 U7H	**592**
A331 0C2 U7J	**592**
A331 0C2 U7K	**592**
A331 1C2	**592**

Code	Page
A331 1C2 U72	592
A331 1C2 U73	592
A331 1C2 U74	592
A331 1C2 U76	592
A331 1C2 U7H	592
A331 1C2 U7J	592
A331 1C2 U7K	592
A332 0C2	592
A332 0C2 U72	592
A332 0C2 U73	592
A332 0C2 U74	592
A332 0C2 U76	592
A332 0C2 U7H	592
A332 0C2 U7J	592
A332 0C2 U7K	592
A332 1C2	592
A332 1C2 U72	592
A332 1C2 U73	592
A332 1C2 U74	592
A332 1C2 U76	592
A332 1C2 U7H	592
A332 1C2 U7J	592
A332 1C2 U7K	592
A34-AU	1468
A34-AU-NPT	1468
A34-BR	1471
A34-BR-NPT	1471
A34-PP	1470
A34-PP-NPT	1470
A34-SS	1469
A34-SS-NPT	1469
A350BKRL	1756
A350BKRM	1756
A350BKRS	1756
A350BKRXL	1756
A350BKRXS	1756
A350BKRXXL	1756
A350BKRXXXL	1756
A3-AU	1468
A3-AU-NPT	1468
A3-BR	1471
A3-BR-NPT	1471
A3N2H2 16	1004
A3N2H2 18	1004
A3N2H2 20	1004
A3-PP	1470
A3-PP-NPT	1470
A3-SS	1469
A3-SS-NPT	1469
A40050	1674
A40055	1674
A40060	1674
A400T	651
A4-AU	1468
A4-AU-NPT	1468
A4-BR	1471
A4-BR-NPT	1471
A4-PP	1470
A4-PP-NPT	1470
A4-SS	1469
A4-SS-NPT	1469
A5000-BRKT	651
A5-BR-NPT	1471
A6000SE	1632
A622G7RL	1756
A622G7RM	1756
A622G7RS	1756
A622G7RXL	1756
A622G7RXS	1756
A622G7RXXL	1756
A622G7RXXXL	1756
A670K8RL	1756
A670K8RM	1756
A670K8RS	1756
A670K8RXL	1756
A670K8RXS	1756
A670K8RXXL	1756
A672K8RL	1756
A672K8RM	1756
A672K8RS	1756
A672K8RXL	1756
A672K8RXS	1756
A672K8RXXL	1756
A690GRR	1760
A690YER	1760
A6-AU	1468
A6-BR-NPT	1471
A6-SS	1469
A720NARL	1758
A720NARM	1758
A720NARXL	1758
A720NARXXL	1758
A770BKYL	1758
A770BKYM	1758
A770BKYS	1758
A770BKYXL	1758
A770BKYXXL	1758
A774K2RL	1758
A774K2RM	1758
A774K2RS	1758
A774K2RXL	1758
A774K2RXXL	1758
A774MBRL	1758
A774MBRM	1758
A774MBRS	1758
A774MBRXL	1758
A774MBRXXL	1758
A812GNRL	1758
A812GNRM	1758
A812GNRS	1758
A812GNRXL	1758
A812GNRXS	1758
A812GNRXXL	1758
A83	596
A84	596
A86	596
A8B	596
A8D	596
A8E	596
A925BLUL	1758
A925BLUM	1758
A925BLUS	1758
A925BLUXL	1758
A930ORRL	1758
A930ORRM	1758
A930ORRXL	1758
A940040-1	1547
A940040-2	1547
A940050-1	1547
A940050-2	1547
A940060-1	1547
A940060-2	1547
A940070-1	1547
A940080-1	1547
A940080-2	1547
A940100-1	1547
A940100-2	1547
A940120-1	1547
A940120-2	1547
A940160-1	1547
A980045	1540
A980060	1540
A980080	1540
A980090	1540
A980100	1540
A980110	1540
A980120	1540
A980130	1540
A980140	1540
A980150	1540
A980160	1540
A980180	1540
A980190	1540
A980200	1540
A980210	1540
A980220	1540
A980230	1540
A980240	1540
A980250	1540
A980270	1540
A980280	1540
A980290	1540
A980300	1540
A980320	1540
A980330	1540
A980350	1540
A980380	1540
A980400	1540
A980420	1540
A980440	1540
A980470	1540
A980480	1540
A980500	1540
A980540	1540
A980550	1540
A980560	1540
A980600	1540
A980640	1540
A980700	1540
AA1106	396
AA1109	396
AA11AF	396
AA11AM	396
AA11CF	396
AA11CM	396
AA-13	1596
AA5102	402
AA5103	402
AA5106	402
AA5107	402
AA5110	402
AA5111	402
AA5112	402
AA5302	402
AA5303	402
AA5306	402
AA5307	402
AA5310	402
AA5312	402
AA5904	403
AA5908	403
AA5913	403
AA7101	397
AA7102	397
AA7103	397
AA7104	397
AA7105	397
AA7106	397
AA7107	397
AA7108	397
AA7109	397
AA7110	397
AA7111	397
AA7112	397
AA7113	397
AA7114	397
AA7502	399
AA7503	399
AA7504	399
AA7506	399
AA7507	399
AA7510	399
AA7512	399
AA7513	399
AA7702	398
AA7703	398
AA7706	398
AA7707	398
AA7710	398
AA7711	398
AA7712	398
AA7802	401
AA7803	401
AA7804	401
AA7806	401
AA7807	401
AA7808	401
AA7810	401
AA7811	401
AA7812	401
AA7813	401
AAFDURT3	1490
AAFDURT4	1490
AAFNP16URT3	1490
AAMF112112	1490
AAMF1122	1490
AAMF1123	1490
AAMF2122	1490
AAMF212212	1490
AAMF2123	1490
AAMF22	1490
AAMF2212	1490
AAMF23	1490
AAMF32	1490
AAMF3212	1490
AAMF33	1490
AAMF34	1490
AAMF43	1490
AAMFURTURT34	1490
AAMM22	1490
AAMM33	1490
AAMM43	1490
AAMMBSPURT33	1490
AAV-12	979
AAV-38	979
AB.HPPK	1623
AB10730	910
AB129035B	910
AB129035R	910
AB129035Y	910
AB129050B	910
AB129050R	910
AB129050Y	910
AB12930	910
AB161230	910
AB181430	910
AB1N2H2 09	1004
AB1N2H2 10	1004
AB1N2H2 11	1004
AB1N2H2 12	1004
AB1N2H2 13	1004
AB1N2H2 14	1004
AB1N2H2 16	1004
AB1N2H2 18	1004
AB1N2H2 20	1004
AB1V2H2 09	959
AB1V2H2 10	959
AB1V2H2 11	959
AB1V2H2 12	959
AB1V2H2 13	959
AB1V2H2 14	959
AB1V2H2 16	959
AB1V2H2 18	959
AB1V2H2 20	959
AB4230	910
AB6430	910
AB68118	249
AB98210011UC	249
AB98410101UC	249
AB98810011UC	249
ABCC112	1489
ABCC2	1489
ABCC212	1489
ABCCBSP3	1489
ABCCBSP4	1489
ABCCURT3	1489
ABCCURT4	1489
ABH.4.3/4	1623
ABH.6.3/4	1623
ABPC2	1489
ABPC212	1489
ABPCBSP3	1489
ABPCURT3	1489
ABS	1100
ABS/CTUBE-3-1	1100
ABS/CTUBE-3-112	1100
ABS/CTUBE-3-114	1100
ABS/CTUBE-3-2	1100
ABS/CTUBE-3-212	1100
ABS/CTUBE-3-3	1100

Code	Page
ABS/CTUBE-3-4	1100
ABS/CTUBE-3-6	1100
ABS/CTUBE-3-8	1100
ABS/CTUBE-6-1	1100
ABS/CTUBE-6-112	1100
ABS/CTUBE-6-114	1100
ABS/CTUBE-6-2	1100
ABS/CTUBE-6-212	1100
ABS/CTUBE-6-3	1100
ABS/CTUBE-6-4	1100
ABS/ETUBE-3-1	1100
ABS/ETUBE-3-112	1100
ABS/ETUBE-3-114	1100
ABS/ETUBE-3-12	1100
ABS/ETUBE-3-2	1100
ABS/ETUBE-3-3	1100
ABS/ETUBE-3-34	1100
ABS/ETUBE-3-4	1100
ABS/ETUBE-6-1	1100
ABS/ETUBE-6-112	1100
ABS/ETUBE-6-114	1100
ABS/ETUBE-6-12	1100
ABS/ETUBE-6-2	1100
ABS/ETUBE-6-3	1100
ABS/ETUBE-6-34	1100
ABS02-1	1645
ABS02-2	1645
ABS02-4	1645
ABS02-6	1645
ABSB-06B	261
ABSB-08B	261
ABSB-12B	261
ABSB-16B	261
ABU-1000-1000AN	170
ABU-250-250AN	170
ABU-375-375AN	170
ABU-500-500AN	170
ABU-750-750AN	170
AC015CBFI	430
AC1106	396
AC1109	396
AC11AF	396
AC11AM	396
AC11CF	396
AC11CM	396
AC2010-01	650
AC2010-02	650
AC2010-02D	650
AC21CF02	393
AC21CM02	393
AC21EF02	393
AC21EM02	393
AC21JF02	393
AC21JM02	393
AC21R02	393
AC21S02	393
AC21T02	393
AC3010-02	650
AC3010-02D	650
AC4010-04	650
AC4010-04D	650
AC4CF02	395
AC4CM02	395
AC4EF02	395
AC4EM02	395
AC4JF02	395
AC4JM02	395
AC5010-06D	650
AC5010-10D	650
AC51CF	402
AC51CM	402
AC51EF	402
AC51EM	402
AC51JF	402
AC51JM	402
AC51R	402
AC51S	402
AC51T	402
AC52CF	403
AC52CM	403
AC59JF	403
AC59JM	403
AC59V	403
AC5EF02	395
AC5EM02	395
AC5JF02	395
AC5JM02	395
AC6103	393
AC61CF	400
AC61CM	400
AC61EF	400
AC61EM	400
AC61JF	400
AC61JM	400
AC61R	400
AC61S	400
AC61T	400
AC7106	397
AC7108	397
AC7109	397
AC7110	397
AC7113	397
AC71CF	397
AC71CM	397
AC71EF	397
AC71EM	397
AC71JF	397
AC71JM	397
AC7306	401
AC7308	401
AC7310	401
AC7313	401
AC73CF	401
AC73CM	401
AC73EF	401
AC73EM	401
AC73JF	401
AC73JM	401
AC7506	399
AC7508	399
AC7510	399
AC7513	399
AC75CF	399
AC75CM	399
AC75EF	399
AC75EM	399
AC75JF	399
AC75JM	399
AC7706	398
AC7708	398
AC7710	398
AC7713	398
AC77CF	398
AC77CM	398
AC77EF	398
AC77EM	398
AC77JF	398
AC77JM	398
AC7806	401
AC7808	401
AC7810	401
AC7813	401
AC78CF	401
AC78CM	401
AC78EF	401
AC78EM	401
AC78JF	401
AC78JM	401
AC901-15D	655
AC901-20D	655
AC91CF	393
AC91CM	393
AC91EF	393
AC91EM	393
AC91JF	393
AC91JM	393
AC91R	393
AC91S	393
AC91T	393
ACA1793	394
ACA2487	394
ACA2488	394
ACA2593	394
ACA2653	395
ACA2654	395
ACA2657	395
ACA2658	395
ACA2659	395
ACA2660	395
ACA2661	395
ACA2746	394
ACA2994	395
ACA2999	395
ACA3035	395
ACA3036	395
ACA3037	395
ACA6582	394
ACA6583	394
ACA6584	394
ACA6909	394
ACA6912	400
ACA6922	400
ACA6923	400
ACA6924	400
ACA6930	400
ACC00005	418
ACC00006	418
ACC00007	418
ACC00022	418
ACC01582	418
ACC01583	418
ACC02082	418
ACC02083	418
ACK10A	1478
ACK10I	1478
ACK10T	1478
ACK12A	1478
ACK12I	1478
ACK12T	1478
ACK34A	1478
ACK34I	1478
ACK34T	1478
ACK38A	1478
ACK38I	1478
ACK38T	1478
ACKIT01	394
ACT112	1487
ACT2	1487
ACT212	1487
ACT3BSP	1487
ACT3URT	1488
ACT4BSP	1487
ACT4URT	1488
ACTMKEASYFIP-1	1019
ACTMKEASYFIP-112	1019
ACTMKEASYFIP-114	1019
ACTMKEASYFIP-12	1019
ACTMKEASYFIP-2	1019
ACTMKEASYFIP-34	1019
ACTMKEASYGF-1	1019
ACTMKEASYGF-112	1019
ACTMKEASYGF-12	1019
ACTMKEASYGF-2	1019
AD32-10-UPVC	1110
AD32-11-UPVC	1110
AD32-12-UPVC	1110
AD32-13-UPVC	1110
AD32-15-UPVC	1110
AD32-17-UPVC	1110
AD32-19-UPVC	1110
AD32-3-UPVC	1110
AD32-4-UPVC	1110
AD32-5-UPVC	1110
AD32-6-UPVC	1110
AD32-7-UPVC	1110
AD32-8-UPVC	1110
AD32-9-UPVC	1110
AD42-112112-UPVC	1110
AD42-112114-UPVC	1110
AD42-1122-UPVC	1110
AD42-114114-UPVC	1110
AD42-1141-UPVC	1110
AD42-11-UPVC	1110
AD42-1212-UPVC	1110
AD42-1234-UPVC	1110
AD42-134-UPVC	1110
AD42-2112-UPVC	1110
AD42-212212-UPVC	1110
AD42-2122-UPVC	1110
AD42-2123-UPVC	1110
AD42-22-UPVC	1110
AD42-3212-UPVC	1110
AD42-33-UPVC	1110
AD42-3412-UPVC	1110
AD42-341-UPVC	1110
AD42-3434-UPVC	1110
AD42-34-UPVC	1110
AD42-43-UPVC	1110
AD42-44-UPVC	1110
ADAPT.UNI.L	1634
ADCH-16	318
ADCH-20	318
ADCH-32	318
ADCH-4	318
ADCH-6	318
ADP	198
ADP.60AV	1636
ADP.60PV	1636
ADP.90AN	1636
ADSCV1414	1419
ADSCV1438	1419
ADSCV3838	1419
ADSCV51638	1419
ADTG4	1724
AE407	1555
AE425	1555
AE426	1555
AE427	1555
AE466	1555
AE467	1555
AE475	1555
AE476	1555
AE477	1555
AE505	1555
AE506	1555
AE566	1555
AE567	1555
AE575	1555
AE576	1555
AE577	1555
AE-A	979
AE-B	979
AE-C	979
AEMC14	1419
AEMC38	1419
AEMC3814	1419
AE-SP-ABD	979
AE-SP-C	979
AF-13	1596
AF2000-01	650
AF2000-02	650
AF3000-02	650
AF3000-02D	650
AF4000-04	650
AF4000-04D	650
AF4000-06D	650
AF5000-06D	650
AF5000-10D	650
AF900-15D	655
AF900-20D	655
AFBV-12	932
AFBV-34	932
AFC080	102
AFC100	102
AFC102	102
AFC104	102
AFC106	102
AFC108	102
AFC110	102
AFC112	102

Code	Page
AFC114	102
AFC116	102
AFC118	102
AFC401	102
AFC402	102
AFC403	102
AFC404	102
AFC405	102
AFC406	102
AFC407	102
AFFN-1/4	1611
AFG1H03	1724
AFG1H08	1724
AFG4H03	1724
AFG4H031	1724
AFG4H04	1724
AFG4H05	1724
AFG4H06	1724
AFG4H061	1724
AFG5H36	1724
AFG6H04	1724
AFR900-15D	655
AFR900-20D	655
AFS/90G	102
AFS080/90G-038	102
AFS080/90S	106
AFS080/90S-038	106
AFS080G	103
AFS080G-038	103
AFS080N	103
AFS080N-038	103
AFS080S	105
AFS080S-038	105
AFS080S-A20	105
AFS080ST	106
AFS080ST-038	106
AFS100/90G	102
AFS100/90S	106
AFS100G	103
AFS100G-012	103
AFS100N-012	103
AFS100S	105
AFS100S-A25	105
AFS100ST	106
AFS102/90G	102
AFS102G	103
AFS102G-012	103
AFS102G-034	103
AFS102N	103
AFS102N-034	103
AFS102S	105
AFS102S-A30	105
AFS102ST	106
AFS104/90G	102
AFS104G	103
AFS104G-034	103
AFS104G-100	103
AFS104N	103
AFS104N-100	103
AFS104S-A38	105
AFS104ST	106
AFS106/90G	102
AFS106/90S	106
AFS106G	103
AFS106G-034	103
AFS106G-100	103
AFS106G-114	103
AFS106N	103
AFS106N-114	103
AFS106S	105
AFS106S-A50	105
AFS106ST	106
AFS108G	103
AFS108G-100	103
AFS108G-112	103
AFS108G-114	103
AFS108N	103
AFS108N-112	103
AFS108S	105
AFS108ST	106
AFS110G	103
AFS110G-200	103
AFS110N	103
AFS110S	105
AFS110ST	106
AFS112G	103
AFS112G-212	103
AFS112N	103
AFS112ST	106
AFS114G	103
AFS114G-300	103
AFS114N	103
AFS114S	105
AFS114ST	106
AFS116G	103
AFS116G-312	103
AFS116N	103
AFS116S	105
AFS116ST	106
AFS200/90ST	106
AFS202/90ST	106
AFS204/90ST	106
AFS206/90ST	106
AFS208/90ST	106
AFS401/90G-012	102
AFS401/90G-038	102
AFS401/90S-012	106
AFS401/90S-038	106
AFS401G-012	103
AFS401G-038	103
AFS401N-012	103
AFS401N-038	103
AFS401S-012	105
AFS401S-038	105
AFS401S-A20	105
AFS401ST-012	106
AFS401ST-038	106
AFS402/90G	102
AFS402/90S	106
AFS402G	103
AFS402G-012	103
AFS402N	103
AFS402N-012	103
AFS402S	105
AFS402S-A25	105
AFS402ST	106
AFS403/90G	102
AFS403/90S	106
AFS403G	103
AFS403G-034	103
AFS403N	103
AFS403N-034	103
AFS403S	105
AFS403S-A30	105
AFS403ST	106
AFS404/90S	106
AFS404G	103
AFS404G-100	103
AFS404N-100	103
AFS404S	105
AFS404S-A38	105
AFS404ST	106
AFS405/90G	102
AFS405/90S	106
AFS405G	103
AFS405G-114	103
AFS405N	103
AFS405N-114	103
AFS405S	105
AFS405S-A50	105
AFS405ST	106
AFS406/90G	102
AFS406/90S	106
AFS406G	103
AFS406G-112	103
AFS406N	103
AFS406N-112	103
AFS406S	105
AFS406ST	106
AFS700/90ST	106
AFS702/90ST	106
AFS704/90ST	106
AFS706/90ST	106
AFS708/90ST	106
AG50-0015	412
AGJ-1/2-DN05	31
AGJ-1/2-DN06	31
AGJ-1/2-DN08	31
AGJ-11/16-DN12	31
AGJ-11/16-DN16	31
AGJ-11/16-DN19	31
AGJ-15/16-DN19	31
AGJ-15/16-DN25	31
AGJ-15/8-DN25	31
AGJ-15/8-DN31	31
AGJ-17/8-DN31	31
AGJ-17/8-DN38	31
AGJ-21/2-DN38	31
AGJ-21/2-DN51	31
AGJ-3/4-DN10	31
AGJ-3/4-DN12	31
AGJ-7/16-DN05	31
AGJ-7/16-DN06	31
AGJ-7/8-DN10	31
AGJ-7/8-DN12	31
AGJ-7/8-DN16	31
AGJ-9/16-DN05	31
AGJ-9/16-DN06	31
AGJ-9/16-DN08	31
AGJ-9/16-DN10	31
AGRK-1/2-DN10	30
AGRK-1/2-DN12	30
AGRK-1/2-DN19	30
AGRK-1/4-DN05	30
AGRK-1/4-DN06	30
AGRK-1/4-DN08	30
AGRK-1/4-DN10	30
AGRK-1/8-DN05	30
AGRK-1/8-DN06	30
AGRK-11/2-DN38	30
AGRK-11/4-DN31	30
AGRK-1-DN19	30
AGRK-1-DN25	30
AGRK-2-DN51	30
AGRK-3/4-DN12	30
AGRK-3/4-DN16	30
AGRK-3/4-DN19	30
AGRK-3/4-DN25	30
AGRK-3/8-DN06	30
AGRK-3/8-DN08	30
AGRK-3/8-DN10	30
AGRK-3/8-DN12	30
AGT13/06K	1147
AGT13/08K	1147
AGT13/09K	1147
AGT13/13K	1147
AGT17/09K	1147
AGT17/13K	1147
AGT21/13K	1147
AGT21/19K	1147
AGT26/19K	1147
AGT33/25K	1147
AHK-1000B	433
AHK-100B	433
AHK-10B	433
AHK-1500B	433
AHK-150B	433
AHK-15B	433
AHK-2000B	433
AHK-200B	433
AHK-24B	433
AHK-270B	433
AHK-3000B	433
AHK-500B	433
AHK-50B	433
AHK-5B	433
AHK-720B	433
AHK-900B	433
AI-13	1596
AIRTU020S	1069
AIRTU025S	1069
AIRTU032S	1069
AIRTU040S	1069
AK-13	1596
AK-300	1596
AK-600	1596
AK-MM08	1170
AK-MM10	1170
AK-MM12	1170
AK-MM14	1170
AK-MM16	1170
AK-MM18	1170
AK-MM20	1170
AK-MM22	1170
AK-MM24	1170
AKN02NP	1176
AKN04NP	1176
AKN06NP	1176
AKN08NP	1176
AK-NN12	1170
AK-NN14	1170
AK-NN18	1170
AK-NN38	1170
AK-PP12	1170
AK-PP14	1170
AK-PP18	1170
AK-PP38	1170
AK-TT1	1170
AK-TT12	1170
AK-TT14	1170
AK-TT18	1170
AK-TT34	1170
AK-TT38	1170
AK-VV12	1170
AK-VV14	1170
AK-VV18	1170
AL-13	1596
AL2000-02	651
AL3000-02	651
AL4000-04	651
AL900-15	655
AL900-20	655
AL-RM1210-3M-20B	1090
AL-RM1513-3M-20B	1090
AL-RM1816-3M-20B	1090
AL-RM2220-3M-20B	1090
AL-RM2826-3M-10B	1090
ALU-CUTTER15	882
ALU-CUTTER22	882
ALU-CUTTER28	882
AM1915W	884
AMPH-16	318
AMPH-20	318
AMPH-24	318
AMPH-32	318
AMPH-8	318
AMT112	1487
AMT2	1487
AMT212	1487
AMT3BSP	1487
AMT3URT	1487
AMT4BSP	1487
AMT4URT	1487
AN-13	1596
AN14	1419
AN38	1419
ANTI-BLOC 100G	164
ANTI-BLOC 1KG	164
AP100B	1713
AP10K8RL	1757
AP10K8RM	1757
AP10K8RS	1757
AP10K8RXL	1757
AP10K8RXS	1757
AP17101	1708
AP17107	1708
AP17111	1708
AP17313	1709
AP17315	1709
AP17411-1/2	1706

Code	Page
AP17411-3/8	1706
AP17621	1708
AP17803-A	1709
AP17808	1707
AP22	1609
AP30O8RL	1757
AP30O8RM	1757
AP30O8RS	1757
AP30O8RXL	1757
AP30O8RXS	1757
AP30O8RXXL	1757
AP313	1711
AP415	1711
AP488	1711
AP50B8RL	1756
AP50B8RM	1756
AP50B8RS	1756
AP50B8RXL	1756
AP50B8RXXL	1756
AP515	1711
AP7001	1710
AP7002-7	1710
AP7007	1710
AP7319	1709
AP7451	1706
AP7460	1706
AP7495	1707
AP8031K5G	1709
AP80B4RL	1757
AP80B4RM	1757
AP80B4RS	1757
AP80B4RXL	1757
AP80B4RXXL	1757
AP818C	1711
AP81B4RL	1756
AP81B4RM	1756
AP81B4RS	1756
AP81B4RXL	1756
AP81B4RXS	1756
AP81B4RXXL	1756
AP8641-1	1711
AP8641-4	1711
APA-15	1712
APA-25	1712
APAS1005	1713
APAS1005-N1.4	1713
APAS1005-N1.7	1713
AP-B1	194
AP-B1-SS	194
AP-B2	194
AP-B2-SS	194
AP-B3	194
AP-B3-SS	194
AP-B4	194
AP-B4-SS	194
AP-B5	194
AP-B5-SS	194
APBN-12	1206
APBN-14	1206
APBN-38	1206
APBO-12	1206
APBO-14	1206
APBO-38	1206
APBO-516	1206
AP-C1	197
AP-C1-SS	197
AP-C2	197
AP-C2-SS	197
AP-C3	197
AP-C3-SS	197
AP-C4	197
AP-C4-SS	197
AP-C5	197
AP-C5-SS	197
AP-C6	197
AP-C6-SS	197
AP-C7	197
AP-C7-SS	197
AP-C8-SS	197
APD-A0	191
APD-A1	191
APD-A2	191
APD-A3	191
APD-A5	191
APD-A6	191
APD-C1	197
APD-C2	197
APD-C3	197
APD-C5	197
APDL-A1	191
APDL-A2	191
APDL-A3	191
APEC-12	1206
APEC-14	1206
APEC-38	1206
APEC-516	1206
APEE-12	1206
APEE-14	1206
APEE-38	1206
APEE-516	1206
APET-12	1206
APET-14	1206
APET-38	1206
APET-516	1206
APFE-14-14	1206
APFE-38-38	1206
APFE-516-14	1206
APFS-12-12	1206
APFS-12-14	1206
APFS-12-38	1206
APFS-14-12	1206
APFS-14-14	1206
APFS-14-18	1206
APFS-14-38	1206
APFS-38-12	1206
APFS-38-14	1206
APFS-38-38	1206
APFS-516-12	1206
APFS-516-14	1206
APFS-516-38	1206
APH827A	1713
APH827-N1.4	1713
APH827-N1.7	1713
APIPC112	1548
APIPC137	1548
APIPC14	1548
APIPC159	1548
APIPC20	1548
APIPC26	1548
APIPC32	1548
APIPC40	1548
APIPC48	1548
APIPC54	1548
APIPC58	1548
APIPC68	1548
APIPC72	1548
APIPC88	1548
APK-A0	191
APK-A0-SS	191
APK-A1	191
APK-A1-SS	191
APK-A2	191
APK-A2-SS	191
APK-A3	191
APK-A3-SS	191
APK-A4	191
APK-A4-SS	191
APK-A5	191
APK-A5-SS	191
APK-A6	191
APK-A6-SS	191
APK-A7-SS	191
APK-A8-SS	191
APKLC12	1710
APKLC38	1710
APL-A0	191
APL-A1	191
APL-A1-SS	191
APL-A2	191
APL-A2-SS	191
APL-A3	191
APL-A3-SS	191
APL-A4	191
APL-A4-SS	191
APL-A5	191
APL-A5-SS	191
APL-A6	191
APL-A6-SS	191
APLALL048	1078
APLALL068	1078
APLALLMUL068038	1078
APLALLMUL068048	1078
APL-C1	197
APL-C2	197
APL-C3	197
APL-C4	197
APL-C5	197
APMS-12-12	1206
APMS-12-14	1206
APMS-12-38	1206
APMS-14-12	1206
APMS-14-14	1206
APMS-14-18	1206
APMS-14-38	1206
APMS-38-12	1206
APMS-38-14	1206
APMS-38-18	1206
APMS-38-38	1206
APMS-516-12	1206
APMS-516-14	1206
APMS-516-18	1206
APMS-516-38	1206
APOL.1	1654
APPC108	1548
APPC176	1548
APPC20	1548
APPC31	1548
APPC40	1548
APPC52	1548
APPC57	1548
APPC63	1548
APPC67	1548
APPC72	1548
APPC76	1548
APPC89	1548
APPC95	1548
APR200S	1713
APR500	1713
APR500R200S-N1.5	1713
APR71	1713
APR71-N1.7	1713
APR8312	1712
APR-A0	191
APR-A1	191
APR-A2	191
APR-A3	191
APR-A4	191
APR-A5	191
APR-A6	191
APR-B1	194
APR-B2	194
APR-B3	194
APR-B4	194
APR-B5	194
APRC13	1548
APRC20	1548
APRC25	1548
APRL-A1	191
APRL-A2	191
APRL-A3	191
APSE-12-12	1206
APSE-12-14	1206
APSE-12-38	1206
APSE-14-12	1206
APSE-14-14	1206
APSE-14-18	1206
APSE-14-38	1206
APSE-38-12	1206
APSE-38-14	1206
APSE-38-18	1206
APSE-38-38	1206
APSE-516-14	1206
APSE-516-18	1206
APSE-516-38	1206
APSF5040RC	1708
APSHM10	1548
APST-12-14	1206
APST-14-14	1206
APST-14-18	1206
APST-38-14	1206
APST-516-14	1206
AQM-SEALANT	1107
AQV-12-10	1415
AQV-12-30	1415
AQV-16-10	1415
AQV-16-30	1415
AQV-19-10	1415
AQV-19-30	1415
AQV-26-10	1415
AQV-26-30	1415
AQV-33-10	1415
AR100	1458
AR-12	1596
AR-13	1596
AR200	1458
AR2000-01	649
AR250	1588
AR3000-02	649
AR4000-04	649
AR4000-06	649
AR5000-06	649
AR5000-10	649
AR900-15	655
AR900-20	655
AS-10L	156
AS-10S	156
AS-12L	156
AS-12S	156
AS-13	1596
AS-14S	156
AS-15L	156
AS-16S	156
AS-18L	156
AS-20S	156
AS-22L	156
AS-25S	156
AS-28L	156
AS-6L	156
AS-6S	156
AS71CF	397
AS71CM	397
AS71EF	397
AS71EM	397
AS71JF	397
AS71JM	397
AS-8L	156
AS-8S	156
AS-A0/A1	192
AS-A0/A1-SS	192
AS-A2	192
AS-A2-SS	192
AS-A3	192
AS-A3-SS	192
AS-A4	192
AS-A4-SS	192
AS-A5	192
AS-A5-SS	192
AS-A6	192
AS-A6-SS	192
ASAFG-20	1105
ASAFG-25	1105
ASAFG-32	1105
ASAFG-50	1105
ASAFG-63	1105
ASAFG-75	1105
ASAFG-90	1105
ASAH-1/2-20	1436
ASAH-1/4-20	1436
ASAH-1-20	1436
ASAH-3/4-20	1436

Code	Page
ASAH-3/8-20	1436
ASAH-5/16-20	1436
ASAH-5/8-20	1436
AS-B1	194
AS-B1-SS	194
AS-B2	194
AS-B2-SS	194
AS-B3	194
AS-B3-SS	194
AS-B4	194
AS-B4-SS	194
AS-B5	194
AS-B5-SS	194
AS-C1	197
AS-C1-SS	197
AS-C2	197
AS-C2-SS	197
AS-C3	197
AS-C3-SS	197
AS-C4	197
AS-C4-SS	197
AS-C5	197
ASG-1	1593
ASK-106	156
ASK-107	156
ASK-108	156
ASK-127	156
ASK-128	156
ASK-129	156
ASK-1610	156
ASK-1611	156
ASK-1612	156
ASK-2012	156
ASK-2014	156
ASK-2015	156
ASK-2016	156
ASK-2515	156
ASK-2517	156
ASK-2519	156
ASS-RTDH-1-10	1622
ASS-RTDH-1-12	1622
ASS-RTDH-1-15	1622
ASS-RTDH-1-3	1622
ASS-RTDH-1-4	1622
ASS-RTDH-1-5	1622
ASS-RTDH-1-6	1622
ASS-RTDH-1-8	1622
ASV10L	127
ASV12L	127
ASV12S	127
ASV14S	127
ASV15L	127
ASV16S	127
ASV18L	127
ASV20S	127
ASV22L	127
ASV25S	127
ASV28L	127
ASV30S	127
ASV35L	127
ASV38S	127
ASV42L	127
ASV6L	127
ASV6S	127

Code	Page
ASV8L	127
ASV8S	127
ASW-1	1595
AT051	1015
AT051S10	1015
AT101	1015
AT101S12	1015
AT-13	1596
AT201	1015
AT201S10	1015
AT251	1015
AT251S09	1015
AT301	1015
AT301S10	1015
AT351	1015
AT351S09	1015
AT401	1015
AT401S12	1015
AT451S11	1015
AT501S09	1015
ATC12	703
ATC6	703
ATCFRL12	703
ATCFRL6	703
ATF II	283
ATF12	703
ATF6	703
ATL12	703
ATL6	703
ATR12	703
ATR6	703
AV-13	1596
AVK-1000B	433
AVK-1000G	434
AVK-100B	433
AVK-100G	434
AVK-1500B	433
AVK-150B	433
AVK-2000B	433
AVK-2000G	434
AVK-200B	433
AVK-200G	434
AVK-24B	433
AVK-270B	433
AVK-270G	434
AVK-3000B	433
AVK-3000G	434
AVK-500B	433
AVK-500G	434
AVK-50B	433
AVK-720B	433
AVK-720G	434
AVK-900B	433
AVK-900G	434
AW2000-01	649
AW2000-02	649
AW2000-02D	649
AW3000-02	649
AW3000-02D	649
AW4000-04	649
AW4000-04D	649
AW5000-06D	649
AW5000-10D	649
AW-R6-10000	1649

Code	Page
AW-R6-2000	1649
AW-R6-4000	1649
AW-R6-600	1649
B	
B 12/16	510
B 20/25	510
B 41 100	510
B 41 125	510
B 41 160	510
B 41 200	510
B 41 32	510
B 41 40	510
B 41 50	510
B 41 63	510
B 41 80	510
B00KM-10F	577
B00KM-1F	577
B00KM-2F	577
B00KM-3F	577
B00KM-4F	577
B00KM-5F	577
B00KM-6F	577
B00KM-8F	577
B00KM-B	577
B0203CF	23
B0204CF	23
B0403CF	23
B0404CF	23
B0405CF	23
B0406CF	23
B0604CF	23
B0605CF	23
B0606CF	23
B0608CF	23
B0806CF	23
B0808CF	23
B1008CF	23
B1010CF	23
B10AA	1034
B10AC	1034
B10AE	1034
B10AL	1034
B112-AU	1468
B112-AU-NPT	1468
B112-BR	1471
B112-BR-NPT	1471
B112-PP	1470
B112-PP-NPT	1470
B112-SS	1469
B112-SS-NPT	1469
B114-AU	1468
B114-AU-NPT	1468
B114-BR	1471
B114-BR-NPT	1471
B114-PP	1470
B114-PP-NPT	1470
B114-SS	1469
B114-SS-NPT	1469
B11X12SS	1421
B12/34-PP-NPT	1470
B1210CF	23
B1212CF	23
B12-AU	1468
B12-BR	1471

Code	Page
B12-BR-NPT	1471
B12-PP	1470
B12-SS	1469
B12-SS-NPT	1469
B12X14	1421
B13X14SS	1421
B13X15	1421
B14X16	1421
B15X16SS	1421
B1612CF	23
B1616CF	23
B16X18	1421
B1702FP	325
B1702MP	325
B1704F	325
B1704FP	325
B1704H	325
B1704HP	325
B1704M	325
B1704MP	325
B1705H	325
B1705HP	325
B1706F	325
B1706FP	325
B1706H	325
B1706HP	325
B1706M	325
B1706MP	325
B1708F	325
B1708H	325
B1708HP	325
B1708M	325
B1708MP	325
B18.5X19.5SS	1421
B18X20	1421
B1902MP	325
B1904F	325
B1904FP	325
B1904H	325
B1904HP	325
B1904M	325
B1904MP	325
B1905H	325
B1905HP	325
B1906F	325
B1906FP	325
B1906H	325
B1906HP	325
B1906M	325
B1906MP	325
B1908F	325
B1908FP	325
B1908H	325
B1908HP	325
B1908M	325
B1908MP	325
B1-AU	1468
B1-AU-NPT	1468
B1-BR	1471
B1-BR-NPT	1471
B1-PP	1470
B1-PP-NPT	1470
B1-SS	1469
B1-SS-NPT	1469

Code	Page
B203L	565
B203P	608
B20X22	1421
B2102BH	326
B2102F	326
B2102FP	326
B2102M	326
B2102MP	326
B2103HP	326
B2104BH	326
B2104F	326
B2104FP	326
B2104H	326
B2104HP	326
B2104M	326
B2104MP	326
B2105H	326
B2105HP	326
B2106H	326
B2106Q	326
B2106QBH	326
B2106QP	326
B2108Q	326
B2108QBH	326
B2108QP	326
B212-AU	1468
B212-AU-NPT	1468
B212-BR	1471
B212-BR-NPT	1471
B212-SS	1469
B21X23	1421
B2304F	326
B2304FP	326
B2304HP	326
B2304M	326
B2304MP	326
B2304MPS	326
B2305H	326
B2306F	326
B2306FP	326
B2306H	326
B2306HP	326
B2306M	326
B2308F	326
B2308HP	326
B2308M	326
B23X25	1421
B23X25SS	1421
B2502FP	327
B2502MP	327
B2504F	327
B2504FP	327
B2504H	327
B2504HP	327
B2504M	327
B2504MP	327
B2505H	327
B2505HP	327
B2506F	327
B2506FP	327
B2506H	327
B2506HP	327
B2506M	327
B2506MP	327

Code	Page
B2506MPS	327
B2508F	327
B2508FP	327
B2508H	327
B2508HP	327
B2508M	327
B2508MP	327
B25B04F	327
B25B04HP	327
B25B04M	327
B25B04MP	327
B25B05H	327
B25B05HP	327
B25B06F	327
B25B06H	327
B25B06HP	327
B25B06M	327
B25B06MP	327
B25B08F	327
B25B08H	327
B25B08HP	327
B25B08M	327
B25B08MP	327
B26X28	1421
B2704MP	328
B2706F	328
B2706H	328
B2706HP	328
B2708F	328
B2708FP	328
B2708H	328
B2708M	328
B2708MP	328
B2710HP	328
B28X30	1421
B29X30SS	1421
B2-AU	1468
B2-AU-NPT	1468
B2-BR	1471
B2-BR-NPT	1471
B2-PP	1470
B2-PP-NPT	1470
B2-SS	1469
B2-SS-NPT	1469
B326CVCMK110VAC	1053
B326CVCMK240VAC	1053
B326CVCMK24VAC	1053
B326CVCMK24VDC	1053
B33X35	1421
B345000XXH	566
B34-AU	1468
B34-AU-NPT	1468
B34-BR	1471
B34-BR-NPT	1471
B34-PP	1470
B34-PP-NPT	1470
B34-SS	1469
B34-SS-NPT	1469
B356CVCMK110VAC	1053
B356CVCMK240VAC	1053
B356CVCMK24VAC	1053
B356CVCMK24VDC	1053
B36X38	1421
B36X38SS	1421
B3-AU	1468
B3-AU-NPT	1468
B3-BR	1471
B3-BR-NPT	1471
B3-PP	1470
B3-PP-NPT	1470
B3-SS	1469
B3-SS-NPT	1469
B43003BXS	565
B43003CS	565
B43003ES	565
B43003FS	565
B43003HXS	565
B43003LS	565
B43003RS	565
B43003RTS	565
B43004HXS	565
B43004LS	565
B46X50	1421
B4-AU	1468
B4-AU-NPT	1468
B4-BR	1471
B4-BR-NPT	1471
B4-PP-NPT	1470
B4-SS	1469
B4-SS-NPT	1469
B53003FS	565
B53003HX	565
B53003LT	565
B53004FS	565
B53004HXS	565
B53004LT	565
B64G-NNK-AD3-RMN	684
B64G-NNK-MD3-RMN	684
B67X70	1421
B6804F	328
B6804FP	328
B6804MP	328
B6806FP	328
B6806H	328
B6806HP	328
B6806MP	328
B6808F	328
B6808FP	328
B6808H	328
B6808HP	328
B6808M	328
B6808MP	328
B6812F	328
B6812H	328
B6812M	328
B6812MP	328
B68G-NNK-AR3-RLN	684
B6-BR-NPT	1471
B82G-2GK-AP3-RMG	686
B82G-2GK-QP3-RMG	686
B84G-3GK-AP3-RMG	686
B84G-3GK-QP3-RMG	686
B84G-4GK-AP3-RMG	686
B84G-4GK-QP3-RMG	686
B905ORR	1759
B905YER	1759
B914BKR	1759
B955YER	1759
B960BKR	1759
BA035	1761
BA-16	1671
BA-18	1671
BA-20	1671
BAMBH	1615
BAMBHSS	1615
BAMSA	1615
BAMSASS	1615
BASA150-110-UPVC	1105
BASA150-32-UPVC	1105
BASA150-40-UPVC	1105
BASA150-50-UPVC	1105
BASA150-63-UPVC	1105
BASA150-75-UPVC	1105
BASA150-90-UPVC	1105
BAT03	1647
BAT06	1647
BB02CF	23
BB04CF	23
BB06CF	23
BB08CF	23
BB10CF	23
BB12CF	23
BB15	1703
BB16CF	23
BB24	1703
BB50D	1703
BB8	1703
BBJM-10-15	23
BBJM-12-15	23
BBJM-14-15	23
BBJM-16-15	23
BBJM-18-15	23
BBJM-20-15	23
BBJM-22-15	23
BBJM-26-15	23
BBJM-30-15	23
BC-110-UPVC	1103
BC-125-UPVC	1103
BC-13	1671
BC-140-UPVC	1103
BC-15	1671
BC-160-UPVC	1103
BC-16-UPVC	1103
BC-18	1671
BC-20	1671
BC-200-UPVC	1103
BC-20-UPVC	1103
BC-225-UPVC	1103
BC-25-UPVC	1103
BC-32-UPVC	1103
BC-40-UPVC	1103
BC-50-UPVC	1103
BC-63-UPVC	1103
BC-75-UPVC	1103
BC-90-UPVC	1103
BCJ1250	1616
BCJ425	1616
BCJ620	1616
BCJ825	1616
BD-20	1671
BD212	1495
BD-25	1671
BD-30	1671
BD-36	1671
BDH-19	1435
BDH-19-10	1435
BDH-25	1435
BDH-25-10	1435
BDH-32	1435
BDH-32-10	1435
BDH-38	1435
BE-112-DN38	35
BE-114-DN31	35
BE-12-DN12	35
BE-14-DN06	35
BE-1-DN25	35
BE33-112-ABS	1097
BE33-112-UPVC	1109
BE33-114-ABS	1097
BE33-114-UPVC	1109
BE33-12-ABS	1097
BE33-12-UPVC	1109
BE33-1-ABS	1097
BE33-1-UPVC	1109
BE33-212-ABS	1097
BE33-212-UPVC	1109
BE33-2-ABS	1097
BE33-2-UPVC	1109
BE33-34-ABS	1097
BE33-34-UPVC	1109
BE33-3-ABS	1097
BE33-3-UPVC	1109
BE33-4-ABS	1097
BE33-4-UPVC	1109
BE-34-DN19	35
BE-38-DN10	35
BE-516-DN08	35
BE-58-DN16	35
BEL-06-45-DN05	35
BEL-06-45-DN06	35
BEL-06-90-DN05	35
BEL-06-90-DN06	35
BEL-06-DN05	35
BEL-06-DN06	35
BEL-08-45-DN06	35
BEL-08-90-DN06	35
BEL-08-DN05	35
BEL-08-DN06	35
BEL-08-DN08	35
BEL-10-45-DN06	35
BEL-10-45-DN08	35
BEL-10-45-DN10	35
BEL-10-90-DN06	35
BEL-10-90-DN08	35
BEL-10-90-DN10	35
BEL-10-DN08	35
BEL-10-DN10	35
BEL-12-45-DN08	35
BEL-12-45-DN10	35
BEL-12-90-DN08	35
BEL-12-90-DN10	35
BEL-12-90-DN12	35
BEL-12-DN10	35
BEL-12-DN12	35
BEL-15-45-DN12	35
BEL-15-90-DN12	35
BEL-15-DN10	35
BEL-15-DN12	35
BEL-18-45-DN16	35
BEL-18-90-DN16	35
BEL-18-DN12	35
BEL-18-DN16	35
BEL-22-45-DN19	35
BEL-22-90-DN19	35
BEL-22-DN16	35
BEL-22-DN19	35
BEL-28-45-DN25	35
BEL-28-90-DN25	35
BEL-28-DN25	35
BEL-35-45-DN31	35
BEL-35-90-DN31	35
BEL-35-DN31	35
BEL-42-45-DN38	35
BEL-42-90-DN38	35
BEL-42-DN38	35
BES-06-45-DN05	35
BES-06-45-DN06	35
BES-06-90-DN05	35
BES-06-90-DN06	35
BES-06-DN05	35
BES-06-DN06	35
BES-08-45-DN06	35
BES-08-90-DN06	35
BES-08-DN06	35
BES-08-DN08	35
BES-10-45-DN06	35
BES-10-45-DN08	35
BES-10-45-DN10	35
BES-10-90-DN06	35
BES-10-90-DN08	35
BES-10-90-DN10	35
BES-10-DN06	35
BES-10-DN08	35
BES-10-DN10	35
BES-12-45-DN08	35
BES-12-90-DN08	35
BES-12-90-DN10	35
BES-12-DN06	35
BES-12-DN08	35
BES-12-DN10	35
BES-12-DN12	35
BES-14-45-DN10	35
BES-14-90-DN10	35
BES-14-DN10	35
BES-16-45-DN12	35
BES-16-90-DN12	35
BES-16-DN12	35
BES-20-45-DN16	35
BES-20-90-DN16	35
BES-20-DN12	35
BES-20-DN16	35
BES-20-DN19	35
BES-25-45-DN19	35
BES-25-90-DN19	35
BES-25-DN19	35
BES-25-DN25	35
BES-30-45-DN25	35
BES-30-90-DN25	35
BES-30-DN25	35
BES-38-45-DN31	35

Code	Page
BES-38-90-DN31	35
BES-38-DN31	35
BF 100 125	511
BF 160 200	511
BF 40 50	511
BF 63 80	511
BF00-112-UPVC	1111
BF00-1-UPVC	1111
BF00-2-UPVC	1111
BF00-3-UPVC	1111
BF00-4-UPVC	1111
BF00-5-UPVC	1111
BF0203CF	17
BF0204CF	17
BF0206CF	17
BF024503CF	17
BF024504CF	17
BF029003CF	17
BF029004CF	17
BF0403CF	17
BF0404CF	17
BF0404CF-OR	18
BF0405CF	17
BF0406CF	17
BF044503CF	17
BF044504CF	17
BF044505CF	17
BF049003CF	17
BF049004CF	17
BF049005CF	17
BF049006CF	17
BF0490C04CF	17
BF0604CF	17
BF0604CF-OR	18
BF0605CF	17
BF0606CF	17
BF0606CF-OR	18
BF0608CF	17
BF064504CF	17
BF064505CF	17
BF064506CF	17
BF064508CF	17
BF069004CF	17
BF069005CF	17
BF069006CF	17
BF069008CF	17
BF0690C06CF	17
BF0804CF	17
BF0805CF	17
BF0806CF	17
BF0806CF-OR	18
BF0808CF	17
BF0808CF-OR	18
BF084506CF	17
BF084508CF	17
BF084510CF	17
BF089006CF	17
BF089008CF	17
BF0890C08CF	17
BF-10	178
BF-1000	172
BF1008CF	17
BF1008CF-OR	18
BF1010CF	17
BF1010CF-OR	18
BF10-212-ABS	1099
BF104505CF	17
BF104508CF	17
BF104510CF	17
BF109008CF	17
BF109010CF	17
BF-12	178
BF1208CF	17
BF1210CF	17
BF1212CF	17
BF1212CF-OR	18
BF124508CF	17
BF124510CF	17
BF124512CF	17
BF-125	172
BF129008CF	17
BF129010CF	17
BF129012CF	17
BF1290C12CF	17
BF-14	178
BF-15	178
BF-16	178
BF1612CF	17
BF1616CF	17
BF1616CF-OR	18
BF164516CF	17
BF169012CF	17
BF169016CF	17
BF1690C16CF	17
BF-18	178
BF-187	172
BF-20	178
BF2016CF	17
BF2020CF	17
BF204520CF	17
BF209016CF	17
BF209020CF	17
BF-22	178
BF2420CF	17
BF2424CF	17
BF244524CF	17
BF249020CF	17
BF249024CF	17
BF-25	178
BF-250	172
BF-3	178
BF-312	172
BF3232CF	17
BF324532CF	17
BF329032CF	17
BF-375	172
BF-4	178
BF-500	172
BF-6	178
BF-625	172
BF-750	172
BF-8	178
BF-875	172
BFC-1000-1000N	167
BFC-10-250N	174
BFC-12-375N	174
BFC-12-500N	174
BFC-125-125N	167
BFC-187-125N	167
BFC-250-125N	167
BFC-250-250N	167
BFC-312-125N	167
BFC-375-250N	167
BFC-500-375N	167
BFC-500-500N	167
BFC-6-125N	174
BFC-6-250N	174
BFC-625-500N	167
BFC-750-750N	167
BFC-8-125N	174
BFC-875-750N	167
BFCV04	246
BFCV06	246
BFCV08	246
BFCV12	246
BFCV16	246
BFCVC04	246
BFCVC06	246
BFCVC08	246
BFCVC12	246
BFCVC16	246
BFF0404CF	18
BFF0406CF	18
BFF044504CF	18
BFF049004CF	18
BFF0604CF	18
BFF0605CF	18
BFF0606CF	18
BFF0608CF	18
BFF064506CF	18
BFF069006CF	18
BFF0806CF	18
BFF0808CF	18
BFF084508CF	18
BFF089008CF	18
BFF1008CF	18
BFF1010CF	18
BFF1208CF	18
BFF1210CF	18
BFF1212CF	18
BFF124512CF	18
BFF129012CF	18
BFF1612CF	18
BFF1616CF	18
BFF164516CF	18
BFF169016CF	18
BFF2020CF	18
BFF2424CF	18
BFF3232CF	18
BG106	1606
BG405	1606
BG5	1594
BG5002	1606
BG5004	1606
BG5007	1606
BG5-PVC	1594
BG605	1606
BG7001	1604
BG7002	1604
BG7005	1604
BG7006	1604
BG7008	1604
BG-718	1594
BG7501	1605
BG7502	1605
BG7505	1605
BG7506	1605
BG7508	1605
BG8001	1604
BG8002	1604
BG8501	1605
BG8502	1605
BGN466	1606
BH08-08M08M-06MT	15
BH08-08M08M-09MT	15
BH08-08Q08M-.5MT	15
BH08-08Q08P-06MT	15
BH08-08Q08P-09MT	15
BH10	142
BH100	1458
BH12	142
BH1-60	310
BH1-60-BSPP	310
BH1-61	310
BH1-61-BSPP	310
BH2-60	310
BH2-60-BSPP	310
BH2-61	310
BH2-61-BSPP	310
BH3-60	310
BH3-60-BSPP	310
BH3-61	310
BH3-61-BSPP	310
BH4-60	310
BH4-60-BSPP	310
BH4-61	310
BH4-61-BSPP	310
BH6	142
BH6-60	310
BH6-60-BSPP	310
BH6-61	310
BH6-61-BSPP	310
BH8	142
BH8-60	310
BH8-60-BSPP	310
BH8-61	310
BH8-61-BSPP	310
BIODDH-1	1417
BIODDH-34	1417
BJ10-8	142
BJ4-4	142
BJ6-4	142
BJ6-6	142
BJ8-6	142
BJ8-8	142
BJM-03-10	23
BJM-03-12	23
BJM-04-10	23
BJM-04-12	23
BJM-04-14	23
BJM-05-14	23
BJM-05-16	23
BJM-05-18	23
BJM-06-14	23
BJM-06-16	23
BJM-06-18	23
BJM-06-22	23
BJM-08-16	23
BJM-08-18	23
BJM-08-22	23
BJM-10-22	23
BJM-10-26	23
BJM-12-22	23
BJM-12-26	23
BJM-16-30	23
BJN1	1679
BJN12	1679
BJN34	1679
BL07-201	689
BL5040-N	723
BL5040-S3	723
BL5040-S5	723
BL5040-WS3	723
BL5040-WS3-FDA	723
BL5040-WS5	723
BL5040-WS5-FDA	723
BL64-401	683
BL64-408	683
BL64-421	683
BL64-428	683
BL64-608	683
BL82-201G	686
BL82-221G	686
BL84-301G	686
BL84-321G	686
BL84-401G	686
BL84-421G	686
BLH2-25M-ASSY	1426
BLH2-50M-ASSY	1426
BLH3-100M-ASSY	1426
BLH3-25M-ASSY	1426
BLH3-50M-ASSY	1426
BLH4-100M-ASSY	1426
BLH4-25M-ASSY	1426
BLH4-50M-ASSY	1426
BLH6-100M-ASSY	1426
BLH6-25M-ASSY	1426
BLH6-50M-ASSY	1426
BLN02	70
BLN04	70
BLN06	70
BLN08	70
BLN10	70
BLN-1000	172
BLN-10-FT	178
BLN12	70
BLN-125	172
BLN-12-FT	178
BLN-14	178
BLN16	70
BLN-16-FT	178
BLN-18	178
BLN-187	172
BLN20	70
BLN-20-FT	178
BLN24	70
BLN-250	172
BLN-3	178
BLN-312	172
BLN32	70

Code	Page
BLN-375	172
BLN-4	178
BLN-500	172
BLN-6	178
BLN-625	172
BLN-750	172
BLN-8	178
BLN-875	172
BM0203CF	17
BM0204CF	17
BM0403CF	17
BM0404CF	17
BM0405CF	17
BM0406CF	17
BM0604CF	17
BM0605CF	17
BM0606CF	17
BM0608CF	17
BM0804CF	17
BM0806CF	17
BM0808CF	17
BM0810CF	17
BM1008CF	17
BM1010CF	17
BM1208CF	17
BM1210CF	17
BM1212CF	17
BM1612CF	17
BM1616CF	17
BM2016CF	17
BM2020CF	17
BM2420CF	17
BM2424CF	17
BM3232CF	17
BMC-1000-750N	167
BMC-10-250N	174
BMC-10-375N	174
BMC-10-500N	174
BMC-12-250N	174
BMC-12-375N	174
BMC-12-500N	174
BMC-125-125N	167
BMC-187-125N	167
BMC-250-125N	167
BMC-250-250N	167
BMC-250-375N	167
BMC-250-500N	167
BMC-312-125N	167
BMC-312-250N	167
BMC-375-125N	167
BMC-375-250N	167
BMC-375-375N	167
BMC-500-250N	167
BMC-500-375N	167
BMC-500-500N	167
BMC-500-750N	167
BMC-6-125N	174
BMC-6-250N	174
BMC-625-375N	167
BMC-625-500N	167
BMC-750-500N	167
BMC-750-750N	167
BMC-8-125N	174
BMC-8-250N	174
BMC-875-750N	167
BMG-20	1671
BMG-25	1671
BMG-30	1671
BMG-36	1671
BMT0203CF	18
BMT0204CF	18
BMT0403CF	18
BMT0404CF	18
BMT0405CF	18
BMT0406CF	18
BMT0604CF	18
BMT0605CF	18
BMT0606CF	18
BMT0608CF	18
BMT0806CF	18
BMT0808CF	18
BMT0810CF	18
BMT1010CF	18
BMT1208CF	18
BMT1210CF	18
BMT1212CF	18
BMT1612CF	18
BMT1616CF	18
BMT2016CF	18
BMT2020CF	18
BMT2420CF	18
BMT2424CF	18
BMT3224CF	18
BMT3232CF	18
BN-1	1181
BN11-112-ABS	1097
BN11-112-UPVC	1108
BN11-114-ABS	1097
BN11-114-UPVC	1108
BN11-12-ABS	1097
BN11-12-UPVC	1108
BN11-14-UPVC	1108
BN11-1-ABS	1097
BN11-1-UPVC	1108
BN-112	1181
BN11-212-ABS	1097
BN11-212-UPVC	1108
BN11-2-ABS	1097
BN11-2-UPVC	1108
BN11-34-ABS	1097
BN11-34-UPVC	1108
BN11-38-UPVC	1108
BN11-3-ABS	1097
BN11-3-UPVC	1108
BN-114	1181
BN11-4-ABS	1097
BN11-4-UPVC	1108
BN-12	1181
BN12-112-ABS	1097
BN12-112-UPVC	1108
BN12-114-ABS	1097
BN12-114-UPVC	1108
BN12-12-ABS	1097
BN12-12-UPVC	1108
BN12-1-ABS	1097
BN12-1-UPVC	1108
BN12-212-ABS	1097
BN12-212-UPVC	1108
BN12-2-ABS	1097
BN12-2-UPVC	1108
BN12-34-ABS	1097
BN12-34-UPVC	1108
BN12-38-UPVC	1108
BN12-3-ABS	1097
BN12-3-UPVC	1108
BN12-4-ABS	1097
BN12-4-UPVC	1108
BN-12X80	1181
BN-14	1181
BN-14X80	1181
BN-18	1181
BN-18X30	1181
BN-1X100	1181
BN-1X150	1181
BN-2	1181
BN-212	1181
BN-3	1181
BN-34	1181
BN-34X80	1181
BN-38	1181
BN-38X80	1181
BN-4	1181
BNEUBLADE/150	1614
BNEUBLADE/300	1614
BNEUBLADE/450	1614
BNEUBLADE/600	1614
BNEUBLADE/750	1614
BNEUBLADE/80	1614
BNEUBLADE/900	1614
BNEUPOWERA	1616
BNTM03/015	915
BNTM04/025	915
BNTM04/025-100	915
BNTM04/025B	915
BNTM04/025G	915
BNTM04/025N	915
BNTM04/025R	915
BNTM04/2	915
BNTM05/030	915
BNTM05/030-100	915
BNTM05/030B	915
BNTM05/030N	915
BNTM06/040	915
BNTM06/040-100	915
BNTM06/040B	915
BNTM06/040B-100	915
BNTM06/040G	915
BNTM06/040G-100	915
BNTM06/040N	915
BNTM06/040N-100	915
BNTM06/040R	915
BNTM06/040R-100	915
BNTM06/040Y	915
BNTM06/040Y-100	915
BNTM060/030	915
BNTM08/060	915
BNTM08/060-100	915
BNTM08/060B	915
BNTM08/060B-100	915
BNTM08/060G	915
BNTM08/060G-100	915
BNTM08/060N	915
BNTM08/060N-100	915
BNTM08/060R	915
BNTM08/060R-100	915
BNTM08/060Y	915
BNTM08/060Y-100	915
BNTM10/070	915
BNTM10/070B	915
BNTM10/070N	915
BNTM10/070R	915
BNTM10/080	915
BNTM10/080-100	915
BNTM10/080B	915
BNTM10/080B-100	915
BNTM10/080N	915
BNTM10/080N-100	915
BNTM10/080R	915
BNTM10/080R-100	915
BNTM12/090	915
BNTM12/090B	915
BNTM12/090N	915
BNTM12/090R	915
BNTM12/100	915
BNTM12/100N	915
BNTM14/110	915
BNTM14/110N	915
BOR-10KG	281
BORS1-10	1429
BORS112-10	1429
BORS112-30	1429
BORS114-10	1429
BORS114-30	1429
BORS1-30	1429
BORS2-10	1429
BORS212-10	1429
BORS212-30	1429
BORS2-30	1429
BORS3-10	1429
BORS3-30	1429
BORS34-10	1429
BORS34-30	1429
BP12	143
BP12B	889
BP16B	889
BP20	143
BP2-205	284
BP22B	889
BP4	143
BP4-205	284
BP6	143
BP8	143
BPAM02-06-1	1645
BPAM02-06-2	1645
BPB0157	1703
BPHC12-12RP	318
BPHC16-16RP	318
BPHC24-24RP	318
BPHC4-4RP	318
BPHC6-6RP	318
BPHC8-8RP	318
BPHN12-12RP	318
BPHN16-16RP	318
BPHN32-32RP	318
BPHN4-4RP	318
BPHN6-6RP	318
BPHN8-8RP	318
BPLOBP113	1495
BPLOBP219	1495
BPLODIN9	1495
BPLOWC13	1495
BPLOWC19	1495
BPN16-110-UPVC	1105
BPN16-20-UPVC	1105
BPN16-25-UPVC	1105
BPN16-32-UPVC	1105
BPN16-40-UPVC	1105
BPN16-50-UPVC	1105
BPN16-63-UPVC	1105
BPN16-75-UPVC	1105
BPS212	1495
BPU065/100B	903
BPU080/120B	903
BPU100/145B	903
BR-1000	171
BR-125	171
BR-250	171
BR-375	171
BR-500	171
BR-625	171
BR-AG32LC	1613
BR-AM10	1613
BR-AM10A	1613
BR-AM20	1613
BR-AM20A	1613
BR-AM35	1613
BR-AM35A	1613
BR-AM40	1613
BR-AM40UJ	1613
BR-AM60A	1613
BR-AM75	1613
BR-AM75A	1613
BRC12	1472
BRC6	1472
BRJ12A	1614
BRJ12C	1615
BRJ12S/S	1614
BRJ20A	1614
BRJ20C	1615
BRJ20S/S	1614
BRJ25A	1614
BRJ25C	1615
BRJ25S/S	1614
BRJ40A	1614
BRJ40C	1615
BRJ40S/S	1614
BRJ50A	1614
BRJ50C	1615
BRJ50S/S	1614
BRJ75A	1614
BR-MAGNETICBASEM	1613
BR-SE150	1613
BR-SE300	1613
BR-SE450	1613
BR-SE600	1613
BR-SH10/1.5	1613
BR-SH10/2	1613
BR-SH10/3	1613
BR-SH20/1.5	1613
BR-SH20/2	1613

Code	Page
BR-SH40/1.5	1613
BR-SH40/2	1613
BR-SH40/3	1613
BR-SS60A	1613
BR-SS75A	1613
BS-1	110
BS-1116JIC	110
BS-1-116JIC	110
BS-112	110
BS-112N	110
BS-112V	110
BS-114	110
BS-1-14JIC	110
BS-114N	110
BS-1-18JIC	110
BS-12	110
BS-12JIC	110
BS-12N	110
BS-12V	110
BS-14	110
BS-14JIC	110
BS-14N	110
BS-14V	110
BS-1516JIC	110
BS-18	110
BS-18N	110
BS-1N	110
BS-1V	110
BS-2	110
BS-2BA	110
BS-2N	110
BS2WCL-316-1	1191
BS2WCL-316-1.5	1191
BS2WCL-316-2	1191
BS2WCL-316-2.5	1191
BS2WCL-316-3	1191
BS2WCL-316-4	1191
BS-34	110
BS-34JIC	110
BS-34N	110
BS-34V	110
BS-38	110
BS-38N	110
BS-38V	110
BS-4BA	110
BS-516JIC	110
BS-58JIC	110
BS-6BA	110
BS-716JIC	110
BS7WWO-316-1	1191
BS7WWO-316-1.5	1191
BS7WWO-316-2	1191
BS7WWO-316-2.5	1191
BS7WWO-316-3	1191
BS7WWO-316-4	1191
BS7WWW-316-1	1191
BS7WWW-316-1.5	1191
BS7WWW-316-2	1191
BS7WWW-316-2.5	1191
BS7WWW-316-3	1191
BS7WWW-316-34	1191
BS-916JIC	110
BSB20	1384
BSB48	1384
BSB64	1384
BSH.4.3A	1620
BSH-1	1482
BSH-3/4	1482
BSHA-3/4	1482
BSIDF-13H-1	1192
BSIDF-13H-1.5	1192
BSIDF-13H-2	1192
BSIDF-13H-2.5	1192
BSIDF-13H-3	1192
BSIDF-14-1	1192
BSIDF-14-1.5	1192
BSIDF-14-2	1192
BSIDF-14-2.5	1192
BSIDF-14-3	1192
BSIDF-14-4	1192
BSIDF-15-1	1192
BSIDF-15-1.5	1192
BSIDF-15-2	1192
BSIDF-15-2.5	1192
BSIDF-15-3	1192
BSIDF-15-4	1192
BSIDF-SEAL-1	1192
BSIDF-SEAL-1.5	1192
BSIDF-SEAL-2	1192
BSIDF-SEAL-2.5	1192
BSIDF-SEAL-3	1192
BSIDF-SEAL-4	1192
BSJ-IW13	1143
BSJ-TF06	1143
BSJ-TF08	1143
BSJ-TF10	1143
BSK-1	112
BSK-2	112
BSL2KS-316-1	1191
BSL2KS-316-1.5	1191
BSL2KS-316-2	1191
BSL2KS-316-2.5	1191
BSL2KS-316-3	1191
BSL2KS-316-4	1191
BSL2S-316-1	1191
BSL2S-316-1.5	1191
BSL2S-316-2	1191
BSL2S-316-2.5	1191
BSL2S-316-3	1191
BSL2S-316-4	1191
BSL31-316-1.5X1	1191
BSL31-316-1X0.5	1191
BSL31-316-2.5X1	1191
BSL31-316-2.5X15	1191
BSL31-316-2.5X2	1191
BSL31-316-2X1	1191
BSL31-316-2X1.5	1191
BSL31-316-3X2	1191
BSL31-316-3X2.5	1191
BSL31-316-4X1.5	1191
BSL31-316-4X2	1191
BSL31-316-4X2.5	1191
BSL31-316-4X3	1191
BSL32-316075X0.5	1191
BSL32-316-2.5X2	1191
BSL32-316-2X1	1191
BSL32-316-2X1.5	1191
BSL32-316-3X2	1191
BSL32-316-3X2.5	1191
BSL32-316-4X1.5	1191
BSL32-316-4X2	1191
BSL32-316-4X3	1191
BS-M10	110
BS-M12	110
BS-M14	110
BS-M16	110
BS-M18	110
BS-M22	110
BS-M8	110
BSP-112-BR	957
BSP-114-BR	957
BSP-1-BR	957
BSP-2-BR	957
BSP-34-BR	957
BSRJT-13H-1	1192
BSRJT-13H-1.5	1192
BSRJT-13H-2	1192
BSRJT-13H-2.5	1192
BSRJT-13H-3	1192
BSRJT-13H-4	1192
BSRJT-13HBN-1	1192
BSRJT-13HBN-1.5	1192
BSRJT-13HBN-2	1192
BSRJT-13HBN-2.5	1192
BSRJT-13HBN-3	1192
BSRJT-13HBN-4	1192
BSRJT-14-1	1192
BSRJT-14-1.5	1192
BSRJT-14-2	1192
BSRJT-14-2.5	1192
BSRJT-14-3	1192
BSRJT-14-4	1192
BSRJT-15-1	1192
BSRJT-15-1.5	1192
BSRJT-15-2	1192
BSRJT-15-2.5	1192
BSRJT-15-3	1192
BSRJT-15-4	1192
BSRJT-SEAL-1	1192
BSRJT-SEAL-1.5	1192
BSRJT-SEAL-2	1192
BSRJT-SEAL-2.5	1192
BSRJT-SEAL-3	1192
BSRJT-SEAL-4	1192
BSV-1	110
BSV-112	110
BSV-114	110
BSV-12	110
BSV-14	110
BSV-18	110
BSV-2	110
BSV-34	110
BSV-38	110
BSV-58	110
BTI03	1215
BTI04	1215
BTI05	1215
BTI06	1215
BTI08	1215
BTM06	1215
BTM08	1215
BTM10	1215
BU-10	175
BU-1000	168
BU-125	168
BU-12-FT	175
BU-14	175
BU-15	175
BU-16	175
BU-18	175
BU-187	168
BU-20	175
BU-250	168
BU-312	168
BU-375	168
BU-3-FT	175
BU-4	175
BU-500	168
BU-6	175
BU-625	168
BU-750	168
BU-8	175
BUNA-1	1472
BUNA-112	1472
BUNA-114	1472
BUNA-12	1472
BUNA-2	1472
BUNA-212	1472
BUNA-3	1472
BUNA-34	1472
BUNA-4	1472
BUNA-6	1472
BUSLEEVE-31	46
BUSLEEVE-31-10	46
BUSLEEVE-36	46
BUSLEEVE-36-10	46
BUSLEEVE-42	46
BUSLEEVE-42-10	46
BUSLEEVE-46	46
BUSLEEVE-46-10	46
BUSLEEVE-54	46
BUSLEEVE-54-10	46
BUTVCE-1	967
BUTVCE-112	967
BUTVCE-2	967
BUTVRJT-1	967
BUTVRJT-112	967
BUTVRJT-2	967
BUTVRJT-212	967
BUTVRJT-3	967
BUTVRJT-4	967
BUTVWE-1	967
BUTVWE-112	967
BUTVWE-2	967
BUTVWE-212	967
BUTVWE-3	967
BUTVWE-4	967
BV07-1	924
BV07-12	924
BV07-34	924
BV1021-14	935
BV1021-38	935
BV1070-1	935
BV1070-112	935
BV1070-114	935
BV1070-12	935
BV1070-14	935
BV1070-2	935
BV1070-34	935
BV1070-38	935
BV1071-1	935
BV1071-112	935
BV1071-114	935
BV1071-12	935
BV1071-14	935
BV1071-2	935
BV1071-34	935
BV1071-38	935
BV12-12W	924
BV12-14W	924
BV12-1W	924
BV12-34W	924
BV12-38W	924
BV13-1	923
BV13-12	923
BV13-12W	924
BV13-14	923
BV13-14W	924
BV13-1W	924
BV13-34	923
BV13-34W	924
BV13-38	923
BV13-38W	924
BV210-1	925
BV210-12	925
BV210-34	925
BV210-38	925
BV215-1	932
BV215-112	932
BV215-114	932
BV215-12	932
BV215-2	932
BV215-34	932
BV22-2	1609
BV22-4	1609
BV22-5	1609
BV22-6	1609
BV22D/H	1609
BV23-1	924
BV23-12	924
BV23-34	924
BV28-15	944
BV28-22	944
BV28-28	944
BV28-35	944
BV28-42	944
BV28-54	944
BV35-12	926
BV35-12M	926
BV35-14	926
BV35-14M	926
BV35-18	926
BV35-18M	926
BV35-38	926
BV35-38M	926
BV50-12NPT	925
BV50-34NPT	925
BV538-1	923
BV538-12	923
BV538-34	923

Code	Page
BV538-38	**923**
BV548-1	**924**
BV548-12	**924**
BV548-34	**924**
BV548-38	**924**
BV581-1	**925**
BV581-12	**925**
BV581-34	**925**
BV581-38	**925**
BV6000-12	**956**
BV6000-18	**956**
BV620-12	**924**
BV620-34	**924**
BV64-1	**944**
BV64-112	**944**
BV64-114	**944**
BV64-12	**944**
BV64-2	**944**
BV64-34	**944**
BV84-1	**943**
BV84-112	**943**
BV84-112L	**943**
BV84-112W	**943**
BV84-112WL	**943**
BV84-114	**943**
BV84-114L	**943**
BV84-114W	**943**
BV84-114WL	**943**
BV84-12	**943**
BV84-12L	**943**
BV84-12W	**943**
BV84-12WL	**943**
BV84-14	**943**
BV84-14L	**943**
BV84-14W	**943**
BV84-14WL	**943**
BV84-1L	**943**
BV84-1W	**943**
BV84-1WL	**943**
BV84-2	**943**
BV84-212	**943**
BV84-212L	**943**
BV84-2L	**943**
BV84-2W	**943**
BV84-2WL	**943**
BV84-3	**943**
BV84-34	**943**
BV84-34L	**943**
BV84-34W	**943**
BV84-34WL	**943**
BV84-38	**943**
BV84-38L	**943**
BV84-38W	**943**
BV84-38WL	**943**
BV84-3L	**943**
BV84-4	**943**
BV84-4L	**943**
BV90-1	**923**
BV90-112	**923**
BV90-114	**923**
BV90-12	**923**
BV90-14	**923**
BV90-2	**923**
BV90-34	**923**
BV90-38	**923**
BV93-112L	**932**
BV93-114L	**932**
BV93-12L	**932**
BV93-14L	**932**
BV93-1L	**932**
BV93-2L	**932**
BV93-34L	**932**
BV93-38L	**932**
BVBS-6	**1113**
BVD13-112-PVC	**937**
BVD13-114-PVC	**937**
BVD13-12-PVC	**937**
BVD13-1-PVC	**937**
BVD13-212-PVC	**937**
BVD13-2-PVC	**937**
BVD13-34-PVC	**937**
BVD13-3-PVC	**937**
BVD13-4-PVC	**937**
BVDUS-1	**1100**
BVDUS-112	**1100**
BVDUS-12	**1100**
BVDUS-2	**1100**
BVDUS-212	**1100**
BVHC12-12RP	**318**
BVHC16-16RP	**318**
BVHC20-20RP	**318**
BVHC24-24RP	**318**
BVHC32-32RP	**318**
BVHC4-4RP	**318**
BVHC6-6RP	**318**
BVHC8-8RP	**318**
BVHN12-12RP	**318**
BVHN16-16RP	**318**
BVHN20-20RP	**318**
BVHN24-24RP	**318**
BVHN32-32RP	**318**
BVHN4-4RP	**318**
BVHN6-6RP	**318**
BVHN8-8RP	**318**
BVI13-112-ABS	**945**
BVI13-112-PVC	**945**
BVI13-114-ABS	**945**
BVI13-114-PVC	**945**
BVI13-12-ABS	**945**
BVI13-12-PVC	**945**
BVI13-1-ABS	**945**
BVI13-1-PVC	**945**
BVI13-212-ABS	**945**
BVI13-212-PVC	**945**
BVI13-2-ABS	**945**
BVI13-2-PVC	**945**
BVI13-34-ABS	**945**
BVI13-34-PVC	**945**
BVI13-38-PVC	**945**
BVI13-3-ABS	**945**
BVI13-3-PVC	**945**
BVI13-4-ABS	**945**
BVI13-4-PVC	**945**
BVL13-112-PVC	**937**
BVL13-114-PVC	**937**
BVL13-12-PVC	**937**
BVL13-1-PVC	**937**
BVL13-2-PVC	**937**
BVL13-34-PVC	**937**
BVSU-1	**1113**
BVSU-112	**1113**
BVSU-114	**1113**
BVSU-34	**1113**
BVT13-112-PVC	**937**
BVT13-114-PVC	**937**
BVT13-12-PVC	**937**
BVT13-1-PVC	**937**
BVT13-2-PVC	**937**
BVT13-34-PVC	**937**
BWF1-1	**1392**
BWF1-112	**1392**
BWF1-114	**1392**
BWF1-2	**1392**
BWF1-212	**1392**
BWF1-3	**1392**
BWF1-34	**1392**
BWF1-4	**1392**
BWF2-1	**1392**
BWF2-112	**1392**
BWF2-114	**1392**
BWF2-2	**1392**
BWF2-212	**1392**
BWF2-3	**1392**
BWF2-34	**1392**
BWF2-4	**1392**
BWF3-1	**1392**
BWF3-112	**1392**
BWF3-114	**1392**
BWF3-2	**1392**
BWF3-3	**1392**
BWF3-4	**1392**
BWF4-1	**1392**
BWF4-112	**1392**
BWF4-2	**1392**
BWF4-212	**1392**
BWF4-3	**1392**
BWF4-4	**1392**
BWF5-112-114	**1392**
BWF5-12-34	**1392**
BWF5-2-114	**1392**
BWF5-2-12	**1392**
BWF5-212-112	**1392**
BWF5-212-114	**1392**
BWF5-3-112	**1392**
BWF5-3-2	**1392**
BWF5-4-212	**1392**
BWF6-112-1	**1392**
BWF6-112-114	**1392**
BWF6-112-12	**1392**
BWF6-114-34	**1392**
BWF6-2-1	**1392**
BWF6-2-112	**1392**
BWF6-2-114	**1392**
BWF6-212-112	**1392**
BWF6-212-114	**1392**
BWF6-212-2	**1392**
BWF6-3-112	**1392**
BWF6-3-114	**1392**
BWF6-3-2	**1392**
BWF6-3-212	**1392**
BWF6-34-12	**1392**
BWF6-4-2	**1392**
BWF6-4-212	**1392**
BWF6-4-3	**1392**
BWF7-112-1	**1392**
BWF7-112-114	**1392**
BWF7-112-12	**1392**
BWF7-112-34	**1392**
BWF7-2-114	**1392**
BWF7-212-112	**1392**
BWF7-3-2	**1392**
BWF7-3-212	**1392**
BWF7-4-212	**1392**
BWF7-4-3	**1392**
BWF8-1	**1392**
BWF8-112	**1392**
BWF8-114	**1392**
BWF8-12	**1392**
BWF8-4	**1392**
BX-10	**1420**
BX-13	**1420**
BX-19	**1420**
BX-8	**1420**
C	
C 41 32	**510**
C 41 40	**510**
C 41 50	**510**
C 41 63	**510**
C H 41 100	**510**
C H 41 125	**510**
C H 41 160	**510**
C H 41 200	**510**
C H 41 80	**510**
C001	**1554**
C00269	**1554**
C00KM-10F	**577**
C00KM-1F	**577**
C00KM-2F	**577**
C00KM-3F	**577**
C00KM-4F	**577**
C00KM-5F	**577**
C00KM-6F	**577**
C00KM-8F	**577**
C00KM-B	**577**
C-10	**177**
C-1000	**172**
C10-10/8-M14	**1157**
C10-15/12.5-M20	**1157**
C10-4/2.7-M6	**1157**
C10-5/3-M7	**1157**
C10-6/4-M10	**1157**
C10-6/4-M8	**1157**
C10-8/6-M12	**1157**
C10X-10/8	**1157**
C10X-12/10	**1157**
C10X-6/4	**1157**
C10X-8/6	**1157**
C1-10/8-1/2	**1156**
C1-10/8-1/4	**1156**
C1-10/8-1/8	**1156**
C1-10/8-3/8	**1156**
C11-12/10	**1159**
C11-15/12.5	**1159**
C1-12/10-1/2	**1156**
C1-12/10-3/8	**1156**
C112-AU	**1468**
C112-BR	**1471**
C112-PP	**1470**
C112-SS	**1469**
C114-AU	**1468**
C114-BR	**1471**
C114-PP	**1470**
C114-SS	**1469**
C1-15/12.5-1/2	**1156**
C11-6/4	**1159**
C11-8/6	**1159**
C-12	**177**
C-125-FT	**172**
C12-AU	**1468**
C12-BR	**1471**
C12-PP	**1470**
C12-SS	**1469**
C133	**1554**
C134	**1554**
C135	**1554**
C136	**1554**
C-14	**177**
C1-4/2.7-1/8	**1156**
C140-1-12	**1371**
C140-112-1	**1371**
C140-112-114	**1371**
C140-112-114N	**1371**
C140-112-12	**1371**
C140-112-12N	**1371**
C140-112-1N	**1371**
C140-112-34	**1371**
C140-112-34N	**1371**
C140-1-12N	**1371**
C140-1-14	**1371**
C140-114-1	**1371**
C140-114-12	**1371**
C140-114-1N	**1371**
C140-114-34	**1371**
C140-114-34N	**1371**
C140-1-14N	**1371**
C140-12-14	**1371**
C140-12-14N	**1371**
C140-12-18	**1371**
C140-12-18N	**1371**
C140-12-38	**1371**
C140-12-38N	**1371**
C140-1-34	**1371**
C140-1-34N	**1371**
C140-1-38	**1371**
C140-1-38N	**1371**
C140-14-18	**1371**
C140-2-1	**1371**
C140-2-112	**1371**
C140-2-112N	**1371**
C140-2-114	**1371**
C140-2-114N	**1371**
C140-2-12	**1371**
C140-212-112	**1371**
C140-212-112N	**1371**
C140-212-114	**1371**
C140-212-114N	**1371**
C140-212-12	**1371**
C140-212-12N	**1371**
C140-212-1N	**1371**
C140-212-2	**1371**

Code	Page
C140-212-2N	1371
C140-2-12N	1371
C140-2-1N	1371
C140-2-34	1371
C140-2-34N	1371
C140-3-1	1371
C140-3-112	1371
C140-3-112N	1371
C140-3-114N	1371
C140-3-2	1371
C140-3-212	1371
C140-3-212N	1371
C140-3-2N	1371
C140-34-12	1371
C140-34-12N	1371
C140-34-14	1371
C140-34-14N	1371
C140-34-18	1371
C140-34-18N	1371
C140-34-38	1371
C140-34-38N	1371
C140-38-18	1371
C140-4-2	1371
C140-4-212N	1371
C140-4-2N	1371
C140-4-3	1371
C140-4-3N	1371
C144-1	1370
C144-112	1370
C144-112N	1370
C144-114	1370
C144-114N	1370
C144-12	1370
C144-12N	1370
C144-14	1370
C144-1N	1370
C144-2	1370
C144-212	1370
C144-212N	1370
C144-2N	1370
C144-3	1370
C144-34	1370
C144-34N	1370
C144-38	1370
C144-3N	1370
C144-4	1370
C144-4N	1370
C145-1-12	1370
C145-112-114	1370
C145-1-12N	1370
C145-114-1	1370
C145-114-1N	1370
C145-1-34	1370
C145-1-34N	1370
C145-2-1	1370
C145-2-112	1370
C145-2-112N	1370
C145-2-114N	1370
C145-34-12	1370
C145-34-12N	1370
C147-1	1373
C147-112	1373
C147-112N	1373
C147-114	1373
C147-114N	1373
C147-12	1373
C147-12N	1373
C147-1N	1373
C147-2	1373
C147-212	1373
C147-212N	1373
C147-2N	1373
C147-3	1373
C147-34	1373
C147-34N	1373
C147-3N	1373
C147-4	1373
C147-4N	1373
C-15	177
C1-5/3-1/8	1156
C151-1	1374
C151-112	1374
C151-1-12	1374
C151-112N	1374
C151-1-12N	1374
C151-114	1374
C151-114-1	1374
C151-114N	1374
C151-12	1374
C151-12N	1374
C151-1N	1374
C151-2	1374
C151-212	1374
C151-212N	1374
C151-2N	1374
C151-3	1374
C151-34	1374
C151-34N	1374
C151-3N	1374
C151-4N	1374
C152-1	1373
C152-112	1373
C152-112N	1373
C152-114	1373
C152-114N	1373
C152-12	1373
C152-12N	1373
C152-14N	1373
C152-1N	1373
C152-2	1373
C152-212N	1373
C152-2N	1373
C152-34	1373
C152-34-12	1373
C152-34-12N	1373
C152-34N	1373
C152-3N	1373
C153	1554
C154	1554
C155-1	1375
C155-112	1375
C155-112N	1375
C155-114	1375
C155-114N	1375
C155-12	1375
C155-12N	1375
C155-1N	1375
C155-2	1375
C155-2N	1375
C155-34	1375
C155-34N	1375
C155-3N	1375
C156	1554
C156-1	1374
C156-112	1374
C156-112N	1374
C156-114	1374
C156-114N	1374
C156-12	1374
C156-12N	1374
C156-1N	1374
C156-2	1374
C156-2N	1374
C156-34	1374
C156-34N	1374
C-16	177
C1-6/4-1/4	1156
C1-6/4-1/8	1156
C1-6/4-3/8	1156
C161-1	1375
C161-112	1375
C161-1-12	1375
C161-112-1	1375
C161-112-114N	1375
C161-112-12	1375
C161-112-12N	1375
C161-112-1N	1375
C161-112-34	1375
C161-112-34N	1375
C161-112N	1375
C161-1-12N	1375
C161-114	1375
C161-114-1	1375
C161-114-12	1375
C161-114-12N	1375
C161-114-1N	1375
C161-114-34	1375
C161-114N	1375
C161-12	1375
C161-12-14N	1375
C161-12N	1375
C161-1-34	1375
C161-1-34N	1375
C161-14N	1375
C161-1N	1375
C161-2	1375
C161-2-1	1375
C161-2-112	1375
C161-2-114	1375
C161-2-114N	1375
C161-212	1375
C161-2-12	1375
C161-212N	1375
C161-2-1N	1375
C161-3	1375
C161-3-2	1375
C161-34	1375
C161-34-12	1375
C161-34N	1375
C161-38N	1375
C161-3N	1375
C161-4	1375
C161-4N	1375
C176-1	1371
C176-112	1371
C176-112N	1371
C176-114	1371
C176-114N	1371
C176-12	1371
C176-12N	1371
C176-1N	1371
C176-2	1371
C176-2N	1371
C176-34	1371
C176-34N	1371
C177-1	1371
C177-112	1371
C177-112N	1371
C177-114	1371
C177-114N	1371
C177-12	1371
C177-12N	1371
C177-1N	1371
C177-2	1371
C177-212N	1371
C177-2N	1371
C177-34	1371
C177-34N	1371
C177-3N	1371
C179-1-12	1372
C179-112-1	1372
C179-112-114	1372
C179-112-114N	1372
C179-112-1N	1372
C179-1-12N	1372
C179-114-1	1372
C179-114-12N	1372
C179-114-1N	1372
C179-114-34	1372
C179-12-38	1372
C179-1-34	1372
C179-1-34N	1372
C179-2-1	1372
C179-2-112	1372
C179-2-112N	1372
C179-2-114	1372
C179-2-114N	1372
C179-2-1N	1372
C179-34-12	1372
C179-34-12N	1372
C-18	177
C1-8/6-1/4	1156
C1-8/6-1/8	1156
C1-8/6-3/8	1156
C185-1	1373
C185-112	1373
C185-112N	1373
C185-114N	1373
C185-12	1373
C185-12N	1373
C185-1N	1373
C185-2	1373
C185-212N	1373
C185-2N	1373
C185-34	1373
C185-34N	1373
C-187	172
C192-112N	1374
C192-114N	1374
C192-12N	1374
C192-14	1374
C192-1N	1374
C192-2N	1374
C192-34N	1374
C193-1	1374
C193-112	1374
C193-112N	1374
C193-114	1374
C193-12	1374
C193-12N	1374
C193-1N	1374
C193-2	1374
C193-212	1374
C193-212N	1374
C193-2N	1374
C193-3	1374
C193-34	1374
C193-34N	1374
C197-112N	1376
C197-12N	1376
C197-1N	1376
C197-2N	1376
C197-34N	1376
C199-1	1376
C199-112	1376
C199-112N	1376
C199-114	1376
C199-12	1376
C199-12N	1376
C199-1N	1376
C199-2	1376
C199-2N	1376
C199-34	1376
C199-34N	1376
C1-AU	1468
C1-BR	1471
C1-PP	1470
C1-SS	1469
C1X-12/10-3/8	1156
C1X-6/4-1/4	1156
C1X-8/6-1/4	1156
C1X-8/6-1/8	1156
C1Y-10/6.5-1/4	1156
C1Y-10/8-1/4	1156
C1Y-12/10-3/8	1156
C1Y-6/4-1/4	1156
C1Y-6/4-1/8	1156
C1Y-8/6-1/4	1156
C1Y-8/6-1/8	1156
C1Z-10/8-1/2	1156
C1Z-10/8-1/4	1156
C1Z-10/8-1/8	1156
C1Z-10/8-3/8	1156
C1Z-12/10-1/2	1156
C1Z-12/10-3/8	1156
C1Z-4/2.7-1/8	1156
C1Z-4/2.7-5M	1156
C1Z-4/2.7-6M	1156
C1Z-5/3-1/8	1156
C1Z-5/3-5M	1156

Code	Page
C1Z-5/3-6M	1156
C1Z-6/4-1/2	1156
C1Z-6/4-1/4	1156
C1Z-6/4-1/8	1156
C1Z-6/4-3/8	1156
C1Z-6/4-5M	1156
C1Z-6/4-6M	1156
C1Z-8/6-1/4	1156
C1Z-8/6-1/8	1156
C1Z-8/6-3/8	1156
C-20	177
C202	1554
C203	1554
C203Y	1554
C204	1554
C204B	1554
C205	1554
C205G	1554
C206	1554
C206R	1554
C208-3-100H	1460
C208-4-65H	1460
C2-10/8-1/4	1156
C2-12/10-3/8	1156
C212-AU	1468
C212-BR	1471
C212-SS	1469
C213-2520EX	1462
C-22	177
C223-2530SSEX	1462
C-25	177
C-250	172
C252	1554
C253	1554
C254	1554
C255	1554
C256	1554
C256-1	1372
C256-112	1372
C256-112N	1372
C256-114	1372
C256-114N	1372
C256-12	1372
C256-12N	1372
C256-1N	1372
C256-2	1372
C256-212	1372
C256-212N	1372
C256-2N	1372
C256-3	1372
C256-34	1372
C256-34N	1372
C256-3N	1372
C257-1	1370
C257-112	1370
C257-112N	1370
C257-114	1370
C257-114N	1370
C257-12	1370
C257-12N	1370
C257-1N	1370
C257-2	1370
C257-2N	1370
C257-34	1370
C257-34N	1370
C2-6/4-1/4	1156
C2-6/4-1/8	1156
C2-6/4-3/8	1156
C2681	1459
C2752	1456
C2753	1456
C2782	1456
C2783	1456
C2-8/6-1/2	1156
C2-8/6-1/4	1156
C2-8/6-1/8	1156
C2-8/6-3/8	1156
C289-1	1372
C289-112	1372
C289-112N	1372
C289-114N	1372
C289-12	1372
C289-12N	1372
C289-1N	1372
C289-2	1372
C289-212N	1372
C289-2N	1372
C289-34	1372
C289-34N	1372
C2910-7153	1462
C2910-8104	1462
C2-AU	1468
C2-BR	1471
C2-PP	1470
C2-SS	1469
C2X-10/8-1/4	1157
C2X-6/4-1/4	1157
C2X-8/6-1/4	1157
C2X-8/6-3/8	1157
C-3	177
C3-10/8	1156
C3-10/8-8/6	1156
C-312	172
C3-12/10	1156
C3-15/12.5	1156
C3-4/2.7	1156
C34-AU	1468
C34-BR	1471
C34-PP	1470
C34-SS	1469
C3-5/3	1156
C3-6/4	1156
C3-6/4-5/3	1156
C-375	172
C3-8/6	1156
C3-8/6-6/4	1156
C3-AU	1468
C3-BR	1471
C3-PP	1470
C3-SS	1469
C-4	177
C4-10/8	1156
C4-12/10	1156
C4-4/2.7	1156
C4-6/4	1156
C4-6/4-5/3	1156
C460-3-350H	1460
C460-4-270H	1460
C4-8/6	1156
C4-8/6-6/4	1156
C4-AU	1468
C4-BR	1471
C4-PP	1470
C4-SS	1469
C-500	172
C5-10/8-1/2	1158
C5-10/8-1/4	1158
C5-10/8-1/8	1158
C5-10/8-3/8	1158
C5-12/10-1/2	1158
C5-12/10-3/8	1158
C5-15/12.5-1/2	1158
C529M-1	1376
C529M-112	1376
C529M-112N	1376
C529M-114	1376
C529M-114N	1376
C529M-12	1376
C529M-12N	1376
C529M-1N	1376
C529M-2	1376
C529M-212	1376
C529M-212N	1376
C529M-2N	1376
C529M-3	1376
C529M-34N	1376
C529M-38	1376
C529M-38N	1376
C529M-3N	1376
C529M-4	1376
C529M-4N	1376
C530M-1	1376
C530M-112	1376
C530M-114	1376
C530M-114N	1376
C530M-1N	1376
C530M-34N	1376
C5-4/2.7-1/8	1158
C5-5/3-1/8	1158
C5-6/4-1/4	1158
C5-6/4-1/8	1158
C5-8/6-1/2	1158
C5-8/6-1/4	1158
C5-8/6-1/8	1158
C5-8/6-3/8	1158
C5F-10/8-1/4	1158
C5F-10/8-3/8	1158
C5F-5/3-1/8	1158
C5F-6/4-1/4	1158
C5F-6/4-1/8	1158
C5F-8/6-1/4	1158
C5F-8/6-1/8	1158
C5X-10/8-1/4	1158
C5X-4/2.7-1/8	1158
C5X-6/4-1/4	1158
C5X-6/4-1/8	1158
C5X-8/6-1/4	1158
C5X-8/6-1/8	1158
C5Y-10/8-1/4	1158
C5Y-4/2.7-1/8	1158
C5Y-6/4-1/4	1158
C5Y-6/4-1/8	1158
C5Y-6/4-M5	1158
C5Y-8/6-1/4	1158
C5Y-8/6-1/8	1158
C-6	177
C605-100	1459
C6-10/8	1158
C6-12/10	1158
C-625	172
C6-4/2.7	1158
C6-5/3	1158
C6-6/4	1158
C6-8/6	1158
C6-AU	1468
C705-100	1458
C705-200	1458
C7-10/8-1/4	1158
C7-12/10-3/8	1158
C7-15/12.5-1/2	1158
C7-4/2.7-1/8	1158
C-750	172
C7-6/4-1/4	1158
C7-6/4-1/8	1158
C7-8/6-1/4	1158
C7-8/6-1/8	1158
C7X-10/8-1/4	1158
C7X-6/4-1/4	1158
C7X-6/4-1/8	1158
C7X-8/6-1/4	1158
C7X-8/6-1/8	1158
C7Y-6/4-1/8	1158
C7Y-8/6-1/4	1158
C7Y-8/6-1/8	1158
C-8	177
C800C-1	965
C800C-112	965
C800C-112S	965
C800C-114	965
C800C-114S	965
C800C-12	965
C800C-12S	965
C800C-1S	965
C800C-2	965
C800C-2S	965
C800C-34	965
C800C-34S	965
C800S-1	965
C800S-112	965
C800S-112S	965
C800S-114	965
C800S-114S	965
C800S-12	965
C800S-12S	965
C800S-1S	965
C800S-2	965
C800S-2S	965
C800S-34	965
C800S-34S	965
C808-350L	1461
C808-350M	1461
C808-450L	1461
C808-450M	1461
C808-466L	1458
C808MODK	1637
C808-WELD-OA	1459
C808-WELD-OP	1459
C809-325L	1458
C8-10/8-1/4	1158
C820-358	1459
C8-6/4-1/4	1158
C8-6/4-1/8	1158
C-875	172
C8-8/6-1/4	1158
C8-8/6-1/8	1158
C9-10/8	1158
C9-10/8-8/6	1158
C9-12/10	1158
C9-4/2.7	1158
C940040-1	1547
C940040-2	1547
C940050-1	1547
C940050-2	1547
C940060-1	1547
C940070-1	1547
C940080-1	1547
C940080-2	1547
C940100-1	1547
C940100-2	1547
C940120-1	1547
C9-5/3	1158
C9-6/4	1158
C9-8/6	1158
CA1	1480
CA112	1480
CA12	1480
CA150HDG	1385
CA234	1480
CA300HDG	1385
CA34	1480
CA34Q19S/DL	1480
CA450HDG	1385
CA600HDG	1385
CA73-112-ABS	1098
CA73-112-UPVC	1110
CA73-114-ABS	1098
CA73-114-UPVC	1110
CA73-12-ABS	1098
CA73-12-UPVC	1110
CA73-1-ABS	1098
CA73-1-UPVC	1110
CA73-212-ABS	1098
CA73-212-UPVC	1110
CA73-2-ABS	1098
CA73-2-UPVC	1110
CA73-34-ABS	1098
CA73-34-UPVC	1110
CA73-3-ABS	1098
CA73-3-UPVC	1110
CA73-4-ABS	1098
CA73-4-UPVC	1110
CA73-5-UPVC	1110
CA73-6-UPVC	1110
CA73-8-UPVC	1110
CA750HDG	1385
CAP04NP	1176
CAP06NP	1176
CAP08NP	1176
CAP16NP	1176
CAP54-1	425

Code	Page
CAP54-10	425
CAP54-12	425
CAP54-16	425
CAP65-13	425
CAP65-3	425
CAP67-M12	425
CARMKIT-1	1088
CARMKIT-2	1088
CARMKIT-3	1088
CAS050MS	1552
CAS050SS	1552
CAS075MS	1552
CAS075SS	1552
CAS100MS	1552
CAS100SS	1552
CAS120MS	1552
CAS120SS	1552
CAS150MS	1552
CAS150SS	1552
CAS175SS	1552
CAS200MS	1552
CAS225MS	1552
CAS225SS	1552
CAS250MS	1552
CAS250SS	1552
CAS275MS	1552
CAS275SS	1552
CAS300MS	1552
CAS300SS	1552
CAS330MS	1552
CAS330SS	1552
CAS355MS	1552
CAS355SS	1552
CAS380MS	1552
CAS380SS	1552
CAS405MS	1552
CAS405SS	1552
CAS455MS	1552
CAS505MS	1552
CAS555MS	1552
CAS555SS	1552
CAS605MS	1552
CAS605SS	1552
CAS710MS	1552
CAS710SS	1552
CAS810SS	1552
CAS910MS	1552
CAS910SS	1552
CAS965MS	1552
CAS965SS	1552
CAT-KIT01	112
CBP-03	208
CBP-05	208
CCOP-PA-03	208
CCOP-PA-05	208
CCOP-PB-03	208
CCOP-PB-05	208
CCRHA-1320SS	1461
CCRHA-1330SS	1461
CCRHA-1920SS	1461
CCRHA-1930SS	1461
CCRHA-2520SS	1461
CD-100MS	1520
CD-100SS	1520
CD-2501	1666
CD-2502	1666
CDAX	1659
CDAZ	1675
CDBB-20	1671
CDBB-25	1671
CDBB-30	1671
CDBB-36	1671
CDBJ-20	1671
CDBJ-25	1671
CDBJ-30	1671
CDBJ-36	1671
CDBL-15	1671
CDBU-42	1671
CDBU-47	1671
CDBU-50	1671
CDBV-42	1671
CDBV-47	1671
CDBV-50	1671
CDC-14F-14M-B	1659
CDC-14M-14M-B	1659
CDE	1675
CDH001	1674
CDH002	1674
CDH004	1674
CDH005	1674
CDH006	1674
CDL	1675
CDM	1675
CDN	1675
CDO	1675
CD-OG01	1620
CD-OG01-1	1626
CDQ1500	1670
CDQ1600	1670
CDQ1900	1670
CDQ2100	1670
CDQC-14	1674
CDQP001-14	1674
CDQP045-14	1674
CEL-06-DN05	32
CEL-06-DN06	32
CEL-08-DN05	32
CEL-08-DN06	32
CEL-10-DN06	32
CEL-10-DN08	32
CEL-10-DN10	32
CEL-12-DN06	32
CEL-12-DN08	32
CEL-12-DN10	32
CEL-12-DN12	32
CEL-15-DN10	32
CEL-15-DN12	32
CEL-18-DN12	32
CEL-18-DN16	32
CEL-18-DN19	32
CEL-22-DN16	32
CEL-22-DN19	32
CEL-28-DN19	32
CEL-28-DN25	32
CEL-35-DN31	32
CEL-42-DN38	32
CES-06-DN06	33
CES-08-DN06	33
CES-10-DN06	33
CES-10-DN08	33
CES-10-DN10	33
CES-12-DN08	33
CES-12-DN10	33
CES-14-DN08	33
CES-14-DN10	33
CES-16-DN10	33
CES-16-DN12	33
CES-20-DN12	33
CES-20-DN16	33
CES-20-DN19	33
CES-25-DN19	33
CES-25-DN25	33
CES-30-DN25	33
CES-38-DN31	33
CF1	762
CF14BE	1761
CF4	762
CF5	762
CF6	762
CF8	762
CF9	762
CFD0610	246
CFD0620	246
CFD063	246
CFD0632	246
CFD066	246
CFD0840	246
CFD0860	246
CFD0880	246
CFD216	1761
CFFRT-15-15-12	1217
CFFRT-22-22-12	1217
CFFRT-22-22-34	1217
CFRT-15-15-22	1217
CFRT-22-15-15	1217
CFRT-22-15-22	1217
CFRT-22-22-15	1217
CFRT-28-28-22	1217
CFRT-35-35-15	1217
CFV1B-N	438
CFV2B-N	438
CFV3B-N	438
CFV4B-N	438
CFV5B-N	438
CFVC04	246
CFVC06	246
CFVC08	246
CG16	280
CG1N02000C022	1044
CG1N02VL1C022	1045
CG1N02VL2C022	1045
CG1N02VL3C022	1045
CG205CTW00	1053
CG205STW00	1053
CG206CTX00	1053
CG206STX00	1053
CG207CTY00	1053
CG207STY00	1053
CG208STZ00	1053
CG209STK00	1053
CG210STJ00	1053
CG63-100B	412
CG63-250B	412
CG63-400B	412
CG63-600B	412
CGS-1	1472
CGS-114-212	1472
CGS-12-34	1472
CGS-3-4	1472
CH-13/19-75	1432
CH13513	1417
CH13522	1417
CH13535	1417
CH13538	1417
CH13541	1417
CH13551	1417
CH13554	1417
CH13557	1417
CH-19/25-75	1432
CH-25/34-75	1432
CH2A01	1725
CH2H01	1725
CH2K01	1725
CH38	278
CH4.19	1625
CH4.25	1625
CH4513	1417
CH4516	1417
CH4519	1417
CH4522	1417
CH4525	1417
CH4528	1417
CH4532	1417
CH4535	1417
CH4538	1417
CH4541	1417
CH4545	1417
CH4548	1417
CH4551	1417
CH4554	1417
CH4557	1417
CH4560	1417
CH4563	1417
CH4570	1417
CH4576	1417
CH4A01	1725
CH4H01	1725
CH4K01	1725
CH6.19	1625
CH6.25	1625
CH90102	1417
CH9013	1417
CH9016	1417
CH9019	1417
CH9022	1417
CH9025	1417
CH9028	1417
CH9032	1417
CH9035	1417
CH9038	1417
CH9041	1417
CH9045	1417
CH9048	1417
CH9051	1417
CH9054	1417
CH9057	1417
CH9060	1417
CH9063	1417
CH9070	1417
CH9076	1417
CH9089	1417
CHAIN	1489
CHEMC-1000	1107
CHR11602	1462
CHR826-12-366L	1462
CHR826-14-466L	1462
CHS102	1417
CHS11	1417
CHS13	1417
CHS16	1417
CHS19	1417
CHS22	1417
CHS25	1417
CHS28	1417
CHS32	1417
CHS35	1417
CHS38	1417
CHS41	1417
CHS45	1417
CHS48	1417
CHS51	1417
CHS54	1417
CHS57	1417
CHS60	1417
CHS63	1417
CHS70	1417
CHS76	1417
CHS8	1417
CHS89	1417
CHS95	1417
CI02/02	1200
CI03/02	1200
CI03/04	1200
CI04/02	1200
CI04/04	1200
CI05/02	1200
CI05/04	1200
CI05/06	1200
CI05/08	1200
CI06/02	1200
CI06/04	1200
CI06/06	1200
CI06/08	1200
CI08/04	1200
CI08/06	1200
CI08/08	1200
CI08/12	1200
CI10/08	1200
CI12/08	1200
CI12/12	1200
CIA04/02	1200
CIA05/04	1200
CIA06/04	1200
CIA06/06	1200
CIA08/08	1200
CIBH03	1201
CIBH04	1201
CIBH05	1201
CIBH06	1201
CIBH08	1201

Code	Page
CIBT03	1202
CIF03/02	1200
CIF03/04	1200
CIF04/02	1200
CIF04/04	1200
CIF05/04	1200
CIF06/04	1200
CIF06/06	1200
CIF08/08	1200
CIF10/08	1200
CIL04	1201
CIL05	1201
CIL06	1201
CIL08	1201
CILF06/06	1201
CILF08/06	1201
CILF08/08	1201
CILM03/02	1201
CILM03/04	1201
CILM04/02	1201
CILM04/04	1201
CILM05/02	1201
CILM05/04	1201
CILM05/06	1201
CILM06/04	1201
CILM06/06	1201
CILP12	1480
CILP34	1480
CILS03	1201
CILS04	1201
CILS05	1201
CILS06	1201
CILS08	1201
CIMB08/04	1202
CIMFB04/03	1201
CIMFB05/04	1201
CIMFB06/04	1201
CIMFB06/05	1201
CIMFB08/05	1201
CIMFB08/06	1201
CINC08	1201
CINF03/02	1200
CINF05/04	1200
CINF06/06	1200
CINF08/06	1200
CINF08/08	1200
CIP03/02	1200
CIP04	1200
CIP04/02	1200
CIP04/04	1200
CIP05	1200
CIP06	1200
CIP06/06	1200
CIP08	1200
CIP08/06	1200
CIS03	1201
CIS04	1201
CIS05	1201
CIS06	1201
CIS08	1201
CIS12	1201
CISP04/04	1202
CISP04/05	1202
CISPH03/03	1202
CISPH04/04	1202
CISPH05/05	1202
CISPH06/06	1202
CISPH08/08	1202
CISPN03/03	1202
CISPN04/04	1202
CISPN05/05	1202
CISPN06/06	1202
CIT03	1202
CIT04	1202
CIT05	1202
CIT06	1202
CIT08	1202
CIT12	1202
CITM04/02	1202
CITM06/04	1202
CITR06/04	1202
CITRS04	1202
CITS04	1202
CITS06	1202
CIUSL05	1201
CIUSL06	1201
CIUST04	1202
CIUST06	1202
CIX06	1202
CIY06	1202
CIY08	1202
CKA210-06-NC	600
CKA210-06-NO	600
CKA210-08-NC	600
CKA210-08-NO	600
CKA220-06	600
CKA220-08	600
CKA310-10-NC	600
CKA310-10-NO	600
CKA320-10	600
CKL110-06	547
CKL210-08	547
CKL310-10	547
CKV210-06-NC	575
CKV210-06-NO	575
CKV210-08-NC	575
CKV210-08-NO	575
CKV220-06	575
CKV220-08	575
CKV310-10-NC	575
CKV310-10-NO	575
CKV320-10	575
CL15-10	1144
CM04/02	1197
CM04/04	1197
CM05/02	1197
CM05/04	1197
CM06/02	1197
CM06/04	1197
CM06/06	1197
CM0715S	881
CM0722S	881
CM0728S	881
CM08/02	1197
CM08/04	1197
CM08/06	1197
CM08/08	1197
CM10/02	1197
CM10/04	1197
CM10/06	1197
CM10/08	1197
CM12/04	1197
CM12/06	1197
CM12/08	1197
CM12/12	1197
CM15/08	1197
CM16/06	1197
CM16/08	1197
CM16/12	1197
CM1815B	884
CM1815R	884
CM1N02000A022	1045
CM1N02000B022	1045
CM1N02VL1A022	1046
CM1N02VL1B022	1046
CM1N02VL2A022	1046
CM1N02VL2B022	1046
CM1N02VL3A022	1046
CM1N02VL3B022	1046
CM22/08	1197
CM22/12	1197
CM3-1G	208
CM3-1G/ALU	208
CM3-1G-ADJ	208
CM3-2G	208
CM3-2G/ALU	208
CM3-2G-ADJ	208
CM3-3G	208
CM3-3G/ALU	208
CM3-3G-ADJ	208
CM3-4G	208
CM3-4G/ALU	208
CM3-4G-ADJ	208
CM3-5G	208
CM3-5G/ALU	208
CM3-5G-ADJ	208
CM3-6G	208
CM3-6G/ALU	208
CM3-6G-ADJ	208
CM5-1G	208
CM5-1G-ADJ	208
CM5-2G	208
CM5-2G-ADJ	208
CM5-3G	208
CM5-3G-ADJ	208
CM5-4G	208
CM5-4G-ADJ	208
CM5-5G	208
CM5-5G-ADJ	208
CM5-6G	208
CM5-6G-ADJ	208
CMA05/02	1197
CMA06/02	1197
CMA06/04	1197
CMA08/04	1197
CMA08/06	1197
CMA12/08	1197
CMBH04	1198
CMBH05	1198
CMBH06	1198
CMBH08	1198
CMBH10	1198
CMBH12	1198
CMBH16	1198
CMBL10	1198
CMBT06	1199
CMBT08	1199
CMBT10	1199
CMF04/02	1197
CMF05/02	1197
CMF05/04	1197
CMF06/02	1197
CMF06/04	1197
CMF08/02	1197
CMF08/04	1197
CMF08/06	1197
CMF10/04	1197
CMF10/06	1197
CMF12/06	1197
CMF12/08	1197
CMF16/08	1197
CML04	1198
CML05	1198
CML06	1198
CML08	1198
CML10	1198
CML12	1198
CML16	1198
CMLF06/04	1198
CMLF08/04	1198
CMLF10/04	1198
CMLF10/06	1198
CMLM04/02	1198
CMLM04/04	1198
CMLM05/02	1198
CMLM05/04	1198
CMLM06/02	1198
CMLM06/04	1198
CMLM06/06	1198
CMLM08/02	1198
CMLM08/04	1198
CMLM08/06	1198
CMLM08/08	1198
CMLM10/04	1198
CMLM10/06	1198
CMLM12/06	1198
CMLM12/08	1198
CMLM16/08	1198
CMLM16/12	1198
CMLS06	1199
CMLS08	1199
CMLS10	1199
CMLS12	1199
CMLS16	1199
CMMB12/08	1199
CMMB16/10	1199
CMMFB05/04	1198
CMMFB08/06	1198
CMMFB10/06	1198
CMMFB10/08	1198
CMMFB12/06	1198
CMMFB12/08	1198
CMMFB12/10	1198
CMMFB16/08	1198
CMMFB16/12	1198
CMNC05	1198
CMNC06	1198
CMNC08	1198
CMNF04/02	1197
CMNF05/02	1197
CMNF06/02	1197
CMNF06/04	1197
CMNF08/04	1197
CMNF10/04	1197
CMNF12/06	1197
CMNF12/08	1197
CMP04	1197
CMP04/02	1197
CMP04/04	1197
CMP05	1197
CMP05/02	1197
CMP05/04	1197
CMP06	1197
CMP06/02	1197
CMP06/04	1197
CMP08	1197
CMP08/02	1197
CMP08/04	1197
CMP08/06	1197
CMP08/08	1197
CMP10	1197
CMP10/04	1197
CMP10/06	1197
CMP10/08	1197
CMP12	1197
CMP12/06	1197
CMP12/08	1197
CMP16/08	1197
CMP22	1197
CMS04	1198
CMS05	1198
CMS06	1198
CMS08	1198
CMS10	1198
CMS12	1198
CMS16	1198
CMS22	1198
CM-SC-15S	883
CMSP02/08	1199
CMSP04/06	1199
CMSP04/08	1199
CMSP06/10	1199
CMSP06/12	1199
CMSP08/12	1199
CMSPH04/03	1199
CMSPH06/04	1199
CMSPH08/04	1199
CMSPH12/06	1199
CMSPN12/12	1199
CMT04	1199
CMT05	1199
CMT06	1199
CMT08	1199
CMT10	1199
CMT12	1199
CMT16	1199
CMTM04/02	1199
CMTM06/02	1199
CMTM08/04	1199
CMTM10/04	1199

Code	Page
CMTR06/02	1199
CMTRS06	1199
CMTRS10	1199
CMTRS12	1199
CMTS08	1199
CMTS10	1199
CMTS12	1199
CMTS16	1199
CMX06	1199
CNS-1	1497
CNS-112	1497
CNS-114	1497
CNS-12	1497
CNS-2	1497
CNS-212	1497
CNS-3	1497
CNS-34	1497
CNS-4	1497
CNS-5	1497
CNS-6	1497
CO1A03	1725
CO1B03	1725
CO3A03	1725
CO3B03	1725
CO8E72	1725
COF-10	1416
COF-12	1416
COF-3.2	1416
COF-3.5	1416
COF-4.0	1416
COF-4.5	1416
COF-5.0	1416
COF-5.5	1416
COF-6.0	1416
COF-7.0	1416
COF-7.5	1416
COF-8.0	1416
COF-9.0	1416
COP-100	281
CP112	1480
CP218	1480
CP234	1480
CP-2910	1462
CP7110 KIT	1718
CP734H	1716
CP772H	1716
CP7731	1716
CP7732	1716
CP7748	1716
CP7782-6	1716
CP78	1480
CP870	1718
CP874	1718
CP879	1717
CP886H	1717
CP9104Q	1717
CP9105QB	1717
CP9120CR	1717
CP9121AR	1717
CP9285	1717
CP9779	1718
CP9882	1717
CP9883	1717
CPN-1	1183
CPN-112	1183
CPN-114	1183
CPN-12	1183
CPN-14	1183
CPN-2	1183
CPN-212	1183
CPN-34	1183
CPN-38	1183
CPOM2DDV	220
CPOM3DDV	220
CPVC10/16	1409
CPVC12/15	1409
CPVC12/18	1409
CPVC14/15	1409
CPVC16/22	1409
CPVC18/15	1409
CPVC19/25	1409
CPVC25/31	1409
CPVC316/15	1409
CPVC34/15	1409
CPVC38/15	1409
CPVC5/11	1409
CPVC516/15	1409
CPVC532/10	1409
CPVC58/15	1409
CPVC6/12	1409
CPVC8/14	1409
CR1	1208
CR12	1208
CR14	1208
CR143B	557
CR143C	557
CR144A	557
CR18	1208
CR316	1208
CR33-112-UPVC	1110
CR33-114-UPVC	1110
CR33-12-ABS	1098
CR33-12-UPVC	1110
CR33-1-ABS	1098
CR33-1-UPVC	1110
CR33-212-UPVC	1110
CR33-2-ABS	1098
CR33-2-UPVC	1110
CR33-34-ABS	1098
CR33-34-UPVC	1110
CR34	1208
CR38	1208
CR516	1208
CRH-1	1416
CRH-112	1416
CRH-114	1416
CRH-118	1416
CRH-134	1416
CRH-138	1416
CRH-2	1416
CRH-78	1416
CRHA-1320	1461
CRHA-1920	1461
CRHA-1930	1461
CRHA-2520	1461
CRHA-920	1461
CRHA-930	1461
CRWM-1320	1461
CRWM-1340	1461
CRWM-1920	1461
CRWM-1920SS	1461
CRWM-1940	1461
CRWM-2520	1461
CRWM-2520SS	1461
CRWM-2530	1461
CS13-364-10GG	685
CS13-664-10GG	685
CS15CP-S	1546
CS1-M-10	455
CS1-M-12	455
CS1-M-16	455
CS1-M-20	455
CS1-M-25	455
CS1-M-32	455
CS1-M-40	455
CS1-M-8	455
CS215CP-S	1546
CS22CP-S	1546
CS3814-1	278
CS3814-2	278
CS3814-3	278
CS3814-4	278
CS3814-6	278
CS-720W-01	1025
CS-720W-02	1025
CS-720W-03	1025
CS-720W-04	1025
CSB1	1376
CSB112	1376
CSB112N	1376
CSB114	1376
CSB12	1376
CSB12N	1376
CSB14	1376
CSB14N	1376
CSB1N	1376
CSB2	1376
CSB212N	1376
CSB2N	1376
CSB3	1376
CSB34	1376
CSB34N	1376
CSB38	1376
CSB3N	1376
CSB4	1376
CSB4N	1376
CSM-E020	485
CSM-E050	485
CSP-03	208
CSP-05	208
CSR-2-40	281
CSS-20	281
CS-S95-01	1025
CS-S95-02	1025
CS-S95-03	1025
CS-S95-04	1025
CST 220	475
CST 232	475
CST 250	475
CST 262	475
CST 332	475
CST 362	475
CSWC112	1480
CSWC2	1480
CT0302021-4	1525
CT0302023-0	1525
CT0302025-7	1525
CT0302029-0	1525
CT0302030-2	1525
CT0302031-0	1525
CT0302034-5	1525
CT-12-2	1107
CT402839	1761
CTC1	905
CTC108-130	1515
CTC121-143	1515
CTC133-155	1515
CTC146-168	1515
CTC184-206	1515
CTC2	905
CTC25-45	1515
CTC32-54	1515
CTC45-67	1515
CTC57-79	1515
CTC70-92	1515
CTC83-105	1515
CTC95-117	1515
CTMAGUT48BK	1588
CTMAGUT48W	1588
CTMAGUT50S.BLUE	1588
CTMAGUT50Y	1588
CTP-AB-03	208
CTP-AB-05	208
CTP-PT-03	208
CTP-PT-05	208
CTR1	905
CTWA-1315SSH	1459
CUPVC/TUBE-11022	1106
CUPVC/TUBE-11053	1106
CUPVC/TUBE-12525	1106
CUPVC/TUBE-14028	1106
CUPVC/TUBE-16032	1106
CUPVC/TUBE-16047	1106
CUPVC/TUBE2015	1106
CUPVC/TUBE2515	1106
CUPVC/TUBE3218	1106
CUPVC/TUBE3224	1106
CUPVC/TUBE4020	1106
CUPVC/TUBE4030	1106
CUPVC/TUBE5018	1106
CUPVC/TUBE6318	1106
CUPVC/TUBE6330	1106
CUPVC/TUBE6347	1106
CUPVC/TUBE-7518	1106
CUPVC/TUBE-7536	1106
CUPVC/TUBE-9018	1106
CV100-1	960
CV100-112	960
CV100-114	960
CV100-12	960
CV100-2	960
CV100-34	960
CV100-38	960
CV105-1	960
CV105-112	960
CV105-114	960
CV105-12	960
CV105-34	960
CV105-38	960
CV12M-1	960
CV12M-112	960
CV12M-114	960
CV12M-12	960
CV12M-2	960
CV12M-34	960
CV12R-1	960
CV12R-112	960
CV12R-114	960
CV12R-12	960
CV12R-2	960
CV12R-34	960
CV130-1	962
CV130-112	962
CV130-114	962
CV130-12	962
CV130-2	962
CV130-212	962
CV130-3	962
CV130-34	962
CV130-38	962
CV130-4	962
CV501	1558
CVBZ384-1	960
CVBZ384-112	960
CVBZ384-114	960
CVBZ384-12	960
CVBZ384-2	960
CVBZ384-34	960
CVD13-112-ABS	1100
CVD13-112-PVC	1112
CVD13-114-ABS	1100
CVD13-114-PVC	1112
CVD13-12-ABS	1100
CVD13-12-PVC	1112
CVD13-1-ABS	1100
CVD13-1-PVC	1112
CVD13-2-ABS	1100
CVD13-2-PVC	1112
CVD13-34-ABS	1100
CVD13-34-PVC	1112
CW1	110
CW100	1458
CW112	110
CW114	110
CW12	110
CW14	110
CW18	110
CW2	110
CW34	110
CW38	110
CWBLACK04-25-R1	1677
CWBLACK04-25-R2	1677
CWBLACK04-50-R1	1677
CWBLACK04-50-R2	1677
CWBLACK05-25-R1	1677
CWBLACK05-25-R2	1677
CWBLACK05-50-R1	1677
CWBLACK05-50-R2	1677
CWBLACK06-25-R1	1677
CWBLACK06-25-R2	1677

Code	Page
CWBLACK06-50-R1	**1677**
CWBLACK06-50-R2	**1677**
CWBLUE04-25-R1	**1677**
CWBLUE04-25-R2	**1677**
CWBLUE04-50-R1	**1677**
CWBLUE04-50-R2	**1677**
CWBLUE05-25-R1	**1677**
CWBLUE05-25-R2	**1677**
CWBLUE05-50-R1	**1677**
CWBLUE05-50-R2	**1677**
CWBLUE06-25-R1	**1677**
CWBLUE06-25-R2	**1677**
CWBLUE06-50-R1	**1677**
CWBLUE06-50-R2	**1677**
CWM10	**110**
CWM12	**110**
CWM14	**110**
CWM16	**110**
CWM18	**110**
CWM22	**110**
CWM8	**110**
CZT-81 501 025	**613**
CZT-81 503 025	**613**
CZT-81 503 710	**613**
CZT-81 503 720	**613**
CZT-81 503 725	**613**
CZT-81 504 025	**613**
CZT-81 506 025	**613**
CZT-81 506 710	**613**
CZT-81 506 720	**613**
CZT-81 507 540	**613**
CZT-81 507 720	**613**
CZT-81 513 052	**613**
CZT-81 513 501	**613**
CZT-81 513 502	**613**
CZT-81 513 510	**613**
CZT-81 513 552	**613**
CZT-81 519 032	**613**
CZT-81 519 632	**613**
CZT-81 521 501	**613**
CZT-81 522 501	**613**
CZT-81 532 001	**613**
CZT-81 532 102	**613**
CZT-81 532 104	**613**
CZT-81 540 001	**613**
CZT-81 540 005	**613**
CZT-81 541 001	**613**
CZT-81 541 005	**613**
CZT-81 545 001	**613**
CZT-84 150 201	**613**
CZT-84 150 202	**613**
CZT-84 150 203	**613**
D	
D E 41 100	**510**
D E 41 125	**510**
D E 41 160	**510**
D E 41 200	**510**
D E 41 32	**510**
D E 41 40	**510**
D E 41 50	**510**
D E 41 63	**510**
D E 41 80	**510**
D00KM-1F	**577**
D00KM-2F	**577**
D00KM-3F	**577**
D00KM-4F	**577**
D00KM-5F	**577**
D00KM-6F	**577**
D00KM-8F	**577**
D00KM-B	**577**
D02 09	**957**
D02 10	**957**
D02 11	**957**
D02 12	**957**
D02 13	**957**
D02 14	**957**
D02 16	**957**
D1045	**1059**
D1060	**1059**
D1080	**1059**
D1100	**1059**
D11021	**1684**
D11-1	**1159**
D11-1/2	**1159**
D11-1/4	**1159**
D11-1/8	**1159**
D11-11/2	**1159**
D11-2	**1159**
D1120	**1059**
D112-AU	**1468**
D112-AU-NPT	**1468**
D112-BR	**1471**
D112-BR-NPT	**1471**
D112-PP	**1470**
D112-PP-NPT	**1470**
D112-SS	**1469**
D112-SS-NPT	**1469**
D11-3/4	**1159**
D11-3/8	**1159**
D114-AU	**1468**
D114-AU-NPT	**1468**
D114-BR	**1471**
D114-BR-NPT	**1471**
D114-PP	**1470**
D114-PP-NPT	**1470**
D114-SS	**1469**
D114-SS-NPT	**1469**
D11-5M	**1159**
D11X-1/2	**110**
D11X-1/4	**110**
D11X-1/8	**110**
D11X-3/4	**110**
D11X-3/8	**110**
D11X-5M	**110**
D11Z-1/4	**1159**
D12/34-PP-NPT	**1470**
D12096	**1684**
D12-AU	**1468**
D12-AU-NPT	**1468**
D12-BR	**1471**
D12-BR-NPT	**1471**
D12-PP	**1470**
D12-SS	**1469**
D12-SS-NPT	**1469**
D13-1/2	**1159**
D13-1/4	**1159**
D1-AU	**1468**
D1-AU-NPT	**1468**
D1-BR	**1471**
D1-BR-NPT	**1471**
D1-PP	**1470**
D1-PP-NPT	**1470**
D1-SS	**1469**
D1-SS-NPT	**1469**
D1VW001CNJW	**220**
D2003-M16	**893**
D2003-M16-S01	**893**
D2003-M22	**893**
D2022-M16XM16	**893**
D2022-M16XM22	**893**
D2022-M22XM22	**893**
D2032-M16	**893**
D2062-M16XM12	**893**
D2062-M16XM16	**893**
D2062-M16XM22	**893**
D2062-M22XM22	**893**
D2072-M16XM12	**893**
D2072-M16XM16	**893**
D2072-M16XM22	**893**
D2072-M22XM22	**893**
D2077-M16M22S01	**893**
D2077-M16-S01	**893**
D212-AU	**1468**
D212-AU-NPT	**1468**
D212-BR	**1471**
D212-BR-NPT	**1471**
D212-SS	**1469**
D212-SS-NPT	**1469**
D2502-M22XM22	**893**
D2512-M22XM16	**893**
D2602-10-M16-L30	**894**
D2602-11.5M16L35	**894**
D2602-12-M16X1.5	**894**
D2612-M12X1.5	**894**
D2612-M16X1.5	**894**
D2612-M22X1.5	**894**
D288DBW-110/50	**1041**
D288DBW-230/50	**1041**
D288DBW-24	**1041**
D289BW-110/50	**1041**
D289BW-230/50	**1041**
D289BW-24	**1041**
D290DBW-110/50	**1041**
D290DBW-230/50	**1041**
D290DBW-24	**1041**
D293DBY-110/50	**1041**
D293DBY-230/50	**1041**
D293DBY-24	**1041**
D2-AU	**1468**
D2-AU-NPT	**1468**
D2-BR	**1471**
D2-BR-NPT	**1471**
D2-PP	**1470**
D2-PP-NPT	**1470**
D2-SS	**1469**
D2-SS-NPT	**1469**
D3043-M16-2D-S01	**893**
D34-AU	**1468**
D34-AU-NPT	**1468**
D34-BR	**1471**
D34-BR-NPT	**1471**
D34-PP	**1470**
D34-PP-NPT	**1470**
D34-SS	**1469**
D34-SS-NPT	**1469**
D3A211	**1684**
D3A255	**1684**
D3-AU	**1468**
D3-AU-NPT	**1468**
D3B911	**1684**
D3B955	**1684**
D3-BR	**1471**
D3-BR-NPT	**1471**
D3-PP	**1470**
D3-PP-NPT	**1470**
D3-SS	**1469**
D3-SS-NPT	**1469**
D3W008CNJW	**220**
D400LB-04	**654**
D45BTOR	**1059**
D4-AU	**1468**
D4-AU-NPT	**1468**
D4-BR	**1471**
D4-BR-NPT	**1471**
D4-PP	**1470**
D4-PP-NPT	**1470**
D4-SS	**1469**
D4-SS-NPT	**1469**
D5-10/8-1/2	**1159**
D5-10/8-1/4	**1159**
D5-10/8-3/8	**1159**
D5-12/10-3/8	**1159**
D5-4/2.7-5M	**1159**
D5-5/3-5M	**1159**
D5-6/4-1/4	**1159**
D5-6/4-1/8	**1159**
D5-6/4-5M	**1159**
D5-8/6-1/4	**1159**
D5-8/6-1/8	**1159**
D5-8/6-3/8	**1159**
D5A211	**1684**
D5A277	**1684**
D5B911	**1684**
D5-BR-NPT	**1471**
D5C277	**1684**
D5D311	**1684**
D606DTY110VAC	**1042**
D606DTY240VAC	**1042**
D606DTY24VAC	**1042**
D60BTOR	**1059**
D6-10/8-1/2	**1159**
D6-10/8-1/8	**1159**
D622DTY110VAC	**1042**
D622DTY240VAC	**1042**
D622DTY24VAC	**1042**
D634DTT110VAC	**1042**
D634DTT240VAC	**1042**
D634DTT24VAC	**1042**
D635DTT110VAC	**1042**
D635DTT240VAC	**1042**
D635DTT24VAC	**1042**
D636DTT110VAC	**1042**
D636DTT240VAC	**1042**
D636DTT24VAC	**1042**
D6-4/2.7-1/8	**1159**
D6512-4-M10	**894**
D6-8/6-1/2	**1159**
D6-8/6-1/4	**1159**
D6-8/6-1/8	**1159**
D6-AU	**1468**
D6-AU-NPT	**1468**
D6-BR-NPT	**1471**
D7-1/2	**1159**
D7-1/4	**1159**
D7-1/8	**1159**
D7-3/8	**1159**
D7-5M-L	**1159**
D7-6M	**1159**
D7-M12X1.5	**1159**
D80BTOR	**1059**
D8-1/2	**1159**
D8-1/4	**1159**
D8-1/8	**1159**
D8-3/8	**1159**
D884DVU-110/50	**1041**
D884DVU-230/50	**1041**
D885DVU-230/50	**1041**
D885DVU-24	**1041**
D886DVU-110/50	**1041**
D886DVU-230/50	**1041**
D886DVU-24	**1041**
D910BTOR	**1059**
D912BTOR	**1059**
D980050	**1540**
D980060	**1540**
D980080	**1540**
D980090	**1540**
D980100	**1540**
D980120	**1540**
D980130	**1540**
D980140	**1540**
D980160	**1540**
D980180	**1540**
D980200	**1540**
D980210	**1540**
D980220	**1540**
D980250	**1540**
D980280	**1540**
D980300	**1540**
D980320	**1540**
D980340	**1540**
D980380	**1540**
D980400	**1540**
D980440	**1540**
D980480	**1540**
D980500	**1540**
D980520	**1540**
D980550	**1540**
D980560	**1540**
D980570	**1540**
D980600	**1540**
D980660	**1540**
D980700	**1540**
D980800	**1540**
D981000	**1540**
D981100	**1540**
DAC1A03	**1724**
DAC1A06	**1724**
DAC1C08	**1724**
DAC403	**1724**

Code	Page
DAC404	1724
DAC405	1724
DAC406	1724
DAC4061	1724
DAC436	1724
DAK10-25MS	1481
DAK10-25ST	1481
DAK12-13MS	1481
DAK12-13ST	1481
DAK15-38ST	1481
DAK34-19MS	1481
DAK34-19ST	1481
DAPGO45FAL020048	1078
DAPGO45FAL025048	1078
DAPGO45FAL025068	1078
DAR4	626
DASS-RTDH-1-10	1622
DASS-RTDH-1-12	1622
DASS-RTDH-1-15	1622
DASS-RTDH-1-3	1622
DASS-RTDH-1-4	1622
DASS-RTDH-1-5	1622
DASS-RTDH-1-6	1622
DASS-RTDH-1-8	1622
DASV06	244
DASV08	244
DASV12	244
DB-1000	261
DB-1500	261
DB-2400	261
DB2911	1685
DBCGGG	1685
DBD311	1685
DBL101A	1059
DBL141	1059
DBL161	1059
DBL171	1059
DBL181	1059
DBL305	1059
DC112-AU	1468
DC112-BR	1471
DC112-PP	1470
DC112-SS	1469
DC114-AU	1468
DC114-PP	1470
DC114-SS	1469
DC-12	1058
DC12-AU	1468
DC12-BR	1471
DC1-AU	1468
DC1-BR	1471
DC1-PP	1470
DC1-SS	1469
DC201-01	653
DC201-02	653
DC201-02D	653
DC201-03D	653
DC212-AU	1468
DC212-BR	1471
DC2-AU	1468
DC2-BR	1471
DC2-PP	1470
DC2-SS	1469
DC34-AU	1468
DC34-PP	1470
DC34-SS	1469
DC3-AU	1468
DC3-BR	1471
DC3-PP	1470
DC3-SS	1469
DC400JK	654
DC401-01	653
DC401-02	653
DC401-02D	653
DC401-03D	653
DC4-AU	1468
DC4-SS	1469
DC601-06	653
DC601-08D	653
DC6-AU	1468
DC6-BR	1471
DCH-3/4-15SAFETY	1412
DCRV012/180	244
DCRV04/180	244
DCRV06/180	244
DCRV08/180	244
DDA1	1398
DDA2	1398
DDA3	1398
DDA4	1398
DDA5	1398
DDA6	1398
DDRH19X-50	1434
DDRH25X-50	1434
DF200-02	653
DF200-02D	653
DF200-03D	653
DF2911	1685
DF400-03D	653
DF400-04	653
DF400-04D	653
DF400-06	653
DF600-06	653
DF600-08	653
DF600-08D	653
DFC666	1685
DFCGGG	1685
DFI900	252
DFR200-01	652
DFR200-02	652
DFR200-02D	652
DFR200-03D	652
DFR400-03D	652
DFR400-04	652
DFR400-04D	652
DFR400-06	652
DFR400-06D	652
DFR600-06	652
DFR600-08D	652
DFS080SM	108
DFS080SM-038	108
DFS080SM-A20	108
DFS080SU	108
DFS080SU-038	108
DFS080SU-A20	108
DFS100SM	108
DFS100SM-A25	108
DFS100SU	108
DFS100SU-A25	108
DFS102SM	108
DFS102SM-A30	108
DFS102SU	108
DFS102SU-A30	108
DFS104SM	108
DFS104SM-A38	108
DFS104SU	108
DFS104SU-A38	108
DFS106SM	108
DFS106SM-A50	108
DFS106SU	108
DFS106SU-A50	108
DFS108SM	108
DFS108SU	108
DFS110SM	108
DFS110SU	108
DFS112SM	108
DFS112SU	108
DFS114SM	108
DFS114SU	108
DFS116SM	108
DFS116SU	108
DFS401SM-012	108
DFS401SM-038	108
DFS401SM-A20	108
DFS401SU-012	108
DFS401SU-038	108
DFS401SU-A20	108
DFS402SM	108
DFS402SM-A25	108
DFS402SU	108
DFS402SU-A25	108
DFS403SM	108
DFS403SM-A30	108
DFS403SU	108
DFS403SU-A30	108
DFS404SM	108
DFS404SM-A38	108
DFS404SU	108
DFS404SU-A38	108
DFS405SM	108
DFS405SM-A50	108
DFS405SU	108
DFS405SU-A50	108
DFS406SM	108
DFS406SU	108
DFT980	253
DG-10	1595
DG-10-EC	1595
DG-10-EK	1595
DGI10	1481
DGI12	1481
DGI15	1481
DGI20	1481
DGI34	1481
DGWEV10LR3/8WD	126
DGWEV10LRWD	126
DGWEV10SRWD	126
DGWEV12LR1/2WD	126
DGWEV12LRWD	126
DGWEV12SRWD	126
DGWEV15LRWD	126
DGWEV16SRWD	126
DGWEV18LRWD	126
DGWEV20SRWD	126
DGWEV22LRWD	126
DGWEV25SRWD	126
DGWEV28LRWD	126
DGWEV30SRWD	126
DGWEV35LRWD	126
DGWEV38SRWD	126
DGWEV42LRWD	126
DGWEV6LR1/4WD	126
DGWEV6LRWD	126
DGWEV6SRWD	126
DGWEV8LRWD	126
DGWEV8SRWD	126
DGWV10L	126
DGWV10S	126
DGWV12L	126
DGWV14S	126
DGWV16S	126
DGWV18L	126
DGWV20S	126
DGWV22L	126
DGWV25S	126
DGWV28L	126
DGWV30S	126
DGWV35L	126
DGWV38S	126
DGWV42L	126
DGWV6L	126
DGWV6S	126
DGWV8L	126
DGWV8S	126
DHG2BG	1531
DHT3BG	1531
DIK10-25ST	1481
DIK12-13MS	1481
DIK12-13ST	1481
DIK15-38MS	1481
DIK15-38ST	1481
DIK34-19MS	1481
DIK34-19ST	1481
DIRAPFRLAL048048	1078
DIRAPLAL048048	1078
DIRAPLAL068068	1078
DIRAPMAL048048	1078
DIRCALML016025	1079
DIRDERFF025048	1072
DIRDERFF032048	1072
DIRDERFF040048	1072
DIRDERFF040068	1072
DIRDERFF050048	1072
DIRDERFF050068	1072
DIRDERFF063048	1072
DIRDERFF063068	1072
DIRDERFF063088	1072
DIRDERFF080048	1072
DIRDERFF080068	1072
DIRDERFF080088	1072
DIRDERFF110068	1072
DIRDERFF110088	1072
DIRDIL168DIN	1077
DIRFC110DIN	1076
DIRFEM10168CF	1077
DIRFEM8016CF	1079
DIRFEM8020CF	1079
DIRFEM8025CF	1079
DIRFEM8032CF	1079
DIRFEM8040CF	1079
DIRFEM8050CF	1079
DIRFEM8063CF	1079
DIRFEM8080CF	1079
DIRFEM8110CF	1079
DIRLUB0750	1079
DIRLUBGEL0950	1079
DIRMOLMLEST016	1079
DIRMOLMLEST020	1079
DIRMOLMLEST025	1079
DIRMOLMLINT016	1079
DIRMOLMLINT020	1079
DIRMOLMLINT025	1079
DIRPIEGTMLS1625	1079
DIRPMUAL120	1078
DIRPMUAL200	1078
DIRRULLUNI	1077
DIRSBVUNI	1079
DIRSM016050	1079
DIRSM063110	1079
DIRSPE020032	1079
DIRSPE040063	1079
DIRVSP028	1078
DISPKS1	1532
DISPKS2	1532
DISPKZ1	1532
DISPKZ2	1532
DKA210-06	600
DKA210-08	600
DKA220-06	600
DKA220-08	600
DKA230C-06	601
DKA230C-08	601
DKA230E-06	601
DKA230E-08	601
DKA230P-06	601
DKA230P-08	601
DKA310-10	600
DKA320-10	600
DKA330C-10	601
DKA330E-10	601
DKA330P-10	601
DKA410-15	600
DKA420-15	600
DKA430C-15	601
DKA430E-15	601
DKA430P-15	601
DKBT	1496
DKF210-08	549
DKF210-08G	549
DKF210-08L	549
DKF210-08LG	549
DKH210-06	549
DKH230-C-06	549
DKH230-C-08	549
DKH310-08	549
DKH310-10	549
DKH330-C-10	549
DKHA230-C-06	549
DKHA230-C-08	549
DKHA330-C-10	549

Code	Page
DKHV210-06-S	548
DKHV230-C-06-S	548
DKHV310-08-S	548
DKHV310-10-S	548
DKHV330-C-08-S	548
DKHV330-C-10-S	548
DKHV410-15-S	548
DKHV410-20-S	548
DKHV430-C-15-S	548
DKHV430-C-20-S	548
DKJ1.5/8-90-DN25	31
DKJ-1/2-45-DN06	31
DKJ-1/2-45-DN08	31
DKJ1/2-90-DN05	31
DKJ1/2-90-DN06	31
DKJ1/2-90-DN08	31
DKJ1/2-DN05	31
DKJ1/2-DN06	31
DKJ1/2-DN08	31
DKJ11/16-90-DN12	31
DKJ11/16-90-DN16	31
DKJ11/16-90-DN19	31
DKJ11/16-DN12	31
DKJ11/16-DN16	31
DKJ11/16-DN19	31
DKJ11/16-DN25	31
DKJ-1116-45-DN12	31
DKJ-1116-45-DN16	31
DKJ-1116-45-DN19	31
DKJ15/16-90-DN19	31
DKJ15/16-90-DN25	31
DKJ15/16-DN16	31
DKJ15/16-DN25	31
DKJ-15/8-45-DN25	31
DKJ-15/8-45-DN31	31
DKJ15/8-90-DN31	31
DKJ15/8-DN25	31
DKJ15/8-DN31	31
DKJ-1516-45-DN19	31
DKJ-1516-45-DN25	31
DKJ-17/8-45-DN31	31
DKJ-17/8-45-DN38	31
DKJ17/8-90-DN31	31
DKJ17/8-90-DN38	31
DKJ17/8-DN31	31
DKJ17/8-DN38	31
DKJ-21/2-45-DN38	31
DKJ-21/2-45-DN51	31
DKJ21/2-90-DN38	31
DKJ21/2-90-DN51	31
DKJ21/2-DN38	31
DKJ21/2-DN51	31
DKJ-3/4-45-DN10	31
DKJ-3/4-45-DN12	31
DKJ3/4-90-DN10	31
DKJ3/4-90-DN12	31
DKJ3/4-DN06	31
DKJ3/4-DN08	31
DKJ3/4-DN10	31
DKJ3/4-DN12	31
DKJ3/4-DN16	31
DKJ3/4-DN19	31
DKJ-7/16-45-DN06	31
DKJ7/16-90-DN05	31
DKJ7/16-90-DN06	31
DKJ7/16-DN05	31
DKJ7/16-DN06	31
DKJ-7/8-45-DN10	31
DKJ-7/8-45-DN12	31
DKJ-7/8-45-DN16	31
DKJ7/8-90-DN10	31
DKJ7/8-90-DN12	31
DKJ7/8-90-DN16	31
DKJ7/8-DN10	31
DKJ7/8-DN12	31
DKJ7/8-DN16	31
DKJ7/8-DN19	31
DKJ-9/16-45-DN06	31
DKJ-9/16-45-DN08	31
DKJ-9/16-45-DN10	31
DKJ9/16-90-DN05	31
DKJ9/16-90-DN06	31
DKJ9/16-90-DN08	31
DKJ9/16-90-DN10	31
DKJ9/16-DN05	31
DKJ9/16-DN06	31
DKJ9/16-DN08	31
DKJ9/16-DN10	31
DKJ9/16-DN12	31
DKL110-06	549
DKL210-08	549
DKL310-10	549
DKM310-08	577
DKM310-10	577
DKM320-08	577
DKM320-10	577
DKO-KA-DN06	34
DKO-KA-DN08	34
DKO-KA-DN10	34
DKO-KA-DN12	34
DKOL-06-45-DN05	32
DKOL-06-45-DN06	32
DKOL-06-90-DN05	32
DKOL-06-90-DN06	32
DKOL-06-DN05	32
DKOL-06-DN06	32
DKOL-08-45-DN05	32
DKOL-08-45-DN06	32
DKOL-08-45-DN08	32
DKOL-08-90-DN06	32
DKOL-08-90-DN08	32
DKOL-08-DN05	32
DKOL-08-DN06	32
DKOL-08-DN08	32
DKOL-08-DN10	32
DKOL-10-45-DN06	32
DKOL-10-45-DN08	32
DKOL-10-45-DN10	32
DKOL-10-90-DN06	32
DKOL-10-90-DN08	32
DKOL-10-90-DN10	32
DKOL-10-DN06	32
DKOL-10-DN08	32
DKOL-10-DN10	32
DKOL-12-45-DN06	32
DKOL-12-45-DN08	32
DKOL-12-45-DN10	32
DKOL-12-45-DN12	32
DKOL-12-90-DN06	32
DKOL-12-90-DN08	32
DKOL-12-90-DN10	32
DKOL-12-90-DN12	32
DKOL-12-DN06	32
DKOL-12-DN08	32
DKOL-12-DN10	32
DKOL-12-DN12	32
DKOL-15-45-DN10	32
DKOL-15-45-DN12	32
DKOL-15-90-DN10	32
DKOL-15-90-DN12	32
DKOL-15-DN06	32
DKOL-15-DN08	32
DKOL-15-DN10	32
DKOL-15-DN12	32
DKOL-15-DN16	32
DKOL-18-45-DN12	32
DKOL-18-45-DN16	32
DKOL-18-90-DN12	32
DKOL-18-90-DN16	32
DKOL-18-DN10	32
DKOL-18-DN12	32
DKOL-18-DN16	32
DKOL-18-DN19	32
DKOL-22-45-DN16	32
DKOL-22-45-DN19	32
DKOL-22-90-DN16	32
DKOL-22-90-DN19	32
DKOL-22-DN12	32
DKOL-22-DN16	32
DKOL-22-DN19	32
DKOL-22-DN25	32
DKOL-28-45-DN19	32
DKOL-28-45-DN25	32
DKOL-28-90-DN19	32
DKOL-28-90-DN25	32
DKOL-28-DN16	32
DKOL-28-DN19	32
DKOL-28-DN25	32
DKOL-35-45-DN31	32
DKOL-35-90-DN31	32
DKOL-35-DN25	32
DKOL-35-DN31	32
DKOL-42-45-DN38	32
DKOL-42-90-DN38	32
DKOL-42-DN31	32
DKOL-42-DN38	32
DKOS-06-45-DN06	33
DKOS-06-90-DN06	33
DKOS-06-DN05	33
DKOS-06-DN06	33
DKOS-08-45-DN06	33
DKOS-08-45-DN08	33
DKOS-08-90-DN06	33
DKOS-08-90-DN08	33
DKOS-08-DN05	33
DKOS-08-DN06	33
DKOS-08-DN08	33
DKOS-08-DN10	33
DKOS-10-45-DN06	33
DKOS-10-45-DN08	33
DKOS-10-45-DN10	33
DKOS-10-90-DN06	33
DKOS-10-90-DN08	33
DKOS-10-90-DN10	33
DKOS-10-DN06	33
DKOS-10-DN08	33
DKOS-10-DN10	33
DKOS-12-45-DN06	33
DKOS-12-45-DN08	33
DKOS-12-45-DN10	33
DKOS-12-45-DN12	33
DKOS-12-90-DN06	33
DKOS-12-90-DN08	33
DKOS-12-90-DN10	33
DKOS-12-90-DN12	33
DKOS-12-DN06	33
DKOS-12-DN08	33
DKOS-12-DN10	33
DKOS-12-DN12	33
DKOS-14-45-DN10	33
DKOS-14-90-DN10	33
DKOS-14-DN08	33
DKOS-14-DN10	33
DKOS-16-45-DN10	33
DKOS-16-45-DN12	33
DKOS-16-90-DN10	33
DKOS-16-90-DN12	33
DKOS-16-DN06	33
DKOS-16-DN08	33
DKOS-16-DN10	33
DKOS-16-DN12	33
DKOS-16-DN16	33
DKOS-20-45-DN12	33
DKOS-20-45-DN16	33
DKOS-20-45-DN19	33
DKOS-20-90-DN12	33
DKOS-20-90-DN16	33
DKOS-20-90-DN19	33
DKOS-20-DN10	33
DKOS-20-DN12	33
DKOS-20-DN16	33
DKOS-20-DN19	33
DKOS-25-45-DN19	33
DKOS-25-45-DN25	33
DKOS-25-90-DN19	33
DKOS-25-90-DN25	33
DKOS-25-DN12	33
DKOS-25-DN16	33
DKOS-25-DN19	33
DKOS-25-DN25	33
DKOS-30-45-DN19	33
DKOS-30-45-DN25	33
DKOS-30-90-DN19	33
DKOS-30-90-DN25	33
DKOS-30-DN19	33
DKOS-30-DN25	33
DKOS-38-45-DN25	33
DKOS-38-45-DN31	33
DKOS-38-90-DN25	33
DKOS-38-90-DN31	33
DKOS-38-DN25	33
DKOS-38-DN31	33
DKOS-50-DN38	33
DKR-1/2-45-DN10	30
DKR-1/2-45-DN12	30
DKR-1/2-45-DN16	30
DKR-1/4-45-DN05	30
DKR-1/4-45-DN06	30
DKR-1/4-45-DN08	30
DKR-1/4-45-DN10	30
DKR-1/8-45-DN05	30
DKR-1/8-45-DN06	30
DKR-11/2-45-DN31	30
DKR-11/2-45-DN38	30
DKR-11/4-45-DN25	30
DKR-11/4-45-DN31	30
DKR-12RG	159
DKR-1-45-DN19	30
DKR-1-45-DN25	30
DKR-16RG	159
DKR-20RG	159
DKR-2-45-DN38	30
DKR-2-45-DN51	30
DKR-24RG	159
DKR-2RG	159
DKR-3/4-45-DN12	30
DKR-3/4-45-DN16	30
DKR-3/4-45-DN19	30
DKR-3/8-45-DN06	30
DKR-3/8-45-DN08	30
DKR-3/8-45-DN10	30
DKR-3/8-45-DN12	30
DKR-4RG	159
DKR-5/8-45-DN12	30
DKR-5/8-45-DN16	30
DKR-6RG	159
DKR-8RG	159
DKRI-4RG	159
DKRI-8RG	159
DKRR1/2MANOM.A3L	130
DKRR1/4MANOM.A3L	130
DKV210-06	576
DKV210-08	576
DKV220-06	576
DKV220-08	576
DKV230C-06	576
DKV230C-08	576
DKV230E-06	576
DKV230E-08	576
DKV230P-06	576
DKV230P-08	576
DKV310-10	576
DKV320-10	576
DKV330C-10	576
DKV330E-10	576
DKV330P-10	576
DKV410-15	576
DKV420-15	576
DKV430C-15	576
DKV430E-15	576
DKV430P-15	576
DL100-M5	654
DL200-01	654
DL200-02	654
DL200-03	654
DL400-03	654
DL400-04	654
DM100	1626
DM13/3	1220
DM13/4	1220

Code	Page
DM13/5	1220
DM13/6	1220
DN05/05	1171
DN05/10	1171
DN10/10	1171
DN10/10K	1171
DN10/13	1171
DN10/13K	1171
DN10/17	1171
DN10/17K	1171
DN10/21K	1171
DN13/13	1171
DN13/13K	1171
DN13/17	1171
DN13/17K	1171
DN13/21	1171
DN13/21K	1171
DN17/17	1171
DN17/17K	1171
DN17/21	1171
DN17/21K	1171
DN21/21	1171
DN21/21K	1171
DN21/26	1171
DN21/26K	1171
DN26/26	1171
DN26/26K	1171
DN26/33	1171
DN26/33K	1171
DN33/33	1171
DN33/33K	1171
DN33/42	1171
DN33/42K	1171
DN42/42	1171
DN42/42K	1171
DN42/50	1171
DN42/50K	1171
DN50/50	1171
DN50/50K	1171
DN50/55	1171
DN50/55K	1171
DN55/55	1171
DO-17	1169
DO-21	1169
DOCV06	244
DOCV08	244
DOCV12	244
DP-01	199
DP-02	199
DP-03	199
DP-04	199
DP112-AU	1468
DP112-BR	1471
DP112-PP	1470
DP112-SS	1469
DP114-AU	1468
DP114-BR	1471
DP114-PP	1470
DP12.17	1635
DP12-AU	1468
DP12-BR	1471
DP12-SS	1469
DP1-AU	1468
DP1-BR	1471
DP1-PP	1470
DP1-SS	1469
DP212-AU	1468
DP212-BR	1471
DP212-SS	1469
DP2-AU	1468
DP2-BR	1471
DP2-PP	1470
DP2-SS	1469
DP34-AU	1468
DP34-PP	1470
DP34-SS	1469
DP3-AU	1468
DP3-BR	1471
DP3-PP	1470
DP3-SS	1469
DP4-AU	1468
DP4-BR	1471
DP6-AU	1468
DP6-BR	1471
DP-A0	191
DP-A0-SS	191
DP-A1	191
DP-A1-SS	191
DP-A2	191
DP-A2-SS	191
DP-A3	191
DP-A3-SS	191
DP-A4	191
DP-A4-SS	191
DP-A5	191
DP-A5-SS	191
DP-A6	191
DP-A6-SS	191
DP-A7-SS	191
DP-A8-SS	191
DP-B1	194
DP-B1-SS	194
DP-B2	194
DPB2A	1764
DP-B2-SS	194
DP-B3	194
DPB3A	1764
DP-B3-SS	194
DP-B4	194
DP-B4-SS	194
DP-B5	194
DP-B5-SS	194
DPB9V	1764
DP-C1	197
DP-C1-SS	197
DP-C2	197
DP-C2-SS	197
DP-C3	197
DP-C3-SS	197
DP-C4	197
DP-C4-SS	197
DP-C5	197
DP-C5-SS	197
DP-C6	197
DP-C6-SS	197
DP-C7	197
DP-C7-SS	197
DP-C8-SS	197
DPD-C1	197
DPD-C2	197
DPD-C3	197
DPD-C4	197
DPD-C5	197
DPG1H08	1725
DPK-1	1610
DPOCV04	244
DPOCV06	244
DPOCV08	244
DPR-10L	159
DPR-10S	159
DPR-12L	159
DPR-12S	159
DPR-14S	159
DPR-15L	159
DPR-16S	159
DPR-18L	159
DPR-20S	159
DPR-22L	159
DPR-25S	159
DPR-28L	159
DPR-30S	159
DPR-35L	159
DPR-38S	159
DPR-42L	159
DPR-6L	159
DPR-6S	159
DPR-8L	159
DPR-8S	159
DR100	1458
DR200-01	652
DR200-02	652
DR200-03	652
DR400-03	652
DR400-04	652
DR600-06	652
DR600-08	652
DRK 10	894
DRK 12	894
DRK 15	894
DRK 16	894
DRK 18	894
DRK 6	894
DRK 8	894
DRP03	1655
DRTDH-1-10	1622
DRTDH-1-12	1622
DRTDH-1-3	1622
DRTDH-1-4	1622
DRTDH-1-5	1622
DRTDH-1-6	1622
DRTDH-1-8	1622
DRV13/30	1596
DRV13/40	1596
DRV13/50	1596
DRV13/60	1596
DS04/04	1144
DS05/05	1144
DS06/06	1144
DS06-SS	1181
DS08/08	1144
DS08-SS	1181
DS09/06	1144
DS09/09	1144
DS10-SS	1181
DS13/06	1144
DS13/08	1144
DS13/09	1144
DS13/13	1144
DS13-SS	1181
DS16/09	1144
DS16/13	1144
DS16/16	1144
DS19/09	1144
DS19/13	1144
DS19/16	1144
DS19/19	1144
DS25/19	1144
DS25/25	1144
DS31/31	1144
DS38/38	1144
DS50/50	1144
DSM-EN020	485
DSM-EN050	485
DSM-EP020	485
DSM-EP050	485
DT3P	1623
DTJ	1623
DUBV-110-UPVC	1106
DUBV-16-UPVC	1106
DUBV-20-UPVC	1106
DUBV-25-UPVC	1106
DUBV-32-UPVC	1106
DUBV-40-UPVC	1106
DUBV-50-UPVC	1106
DUBV-63-UPVC	1106
DUBV-75-UPVC	1106
DUBV-90-UPVC	1106
DUCV-110-UPVC	1106
DUCV-20-UPVC	1106
DUCV-25-UPVC	1106
DUCV-32-UPVC	1106
DUCV-40-UPVC	1106
DUCV-50-UPVC	1106
DUCV-63-UPVC	1106
DUCV-75-UPVC	1106
DUCV-90-UPVC	1106
DUFV-110-UPVC	1106
DUFV-20-UPVC	1106
DUFV-25-UPVC	1106
DUFV-40-UPVC	1106
DUFV-50-UPVC	1106
DUFV-63-UPVC	1106
DUFV-75-UPVC	1106
DUFV-90-UPVC	1106
DV306	245
DV308	245
DV312	245
DV406	245
DV408	245
DV412	245
DW-ALUMINIUM	1623
DWH-1	1415
DWH-12	1415
DWH-34	1415
DWTWDP	1761
DX1-606-BN	608
DX1-621-BN	608
DX2-606-BN	608
DX2-621-BN	608
E	
E 12/16	510
E 20/25	510
E007-1515-013611	227
E016-1515-013611	227
E02 09	957
E02 10	957
E02 11	957
E02 12	957
E02 13	957
E02 14	957
E02 16	957
E03 09	965
E03 10	965
E03 11	965
E03 12	965
E03 14	965
E03 16	965
E032-1515-013611	227
E050-1515-023611	227
E075-1515-093611	227
E10	142
E100-1515-123611	227
E1-10/8-1/2	1157
E1-10/8-1/4	1157
E1-10/8-1/8	1157
E1-10/8-3/8	1157
E112-AU	1468
E112-BR	1471
E112-PP	1470
E112-SS	1469
E114-AU	1468
E114-BR	1471
E114-PP	1470
E114-SS	1469
E12	142
E12-AU	1468
E12-BR	1471
E12-PP	1470
E12-SS	1469
E14	142
E140-1515-113511	227
E16	142
E1-6/4-1/4	1157
E1-6/4-1/8	1157
E1-8/6-1/4	1157
E1-8/6-3/8	1157
E1-AU	1468
E1-BR	1471
E1-PP	1470
E1-SS	1469
E1X-10/6.5-1/4	1157
E1X-10/8-1/4	1157
E1X-12/8-3/8	1157
E1X-6/4-1/4	1157
E1X-6/4-1/8	1157
E1X-8/6-1/4	1157
E1Y-10/6.5-1/4	1157
E1Y-6/4-1/4	1157
E1Y-6/4-1/8	1157
E1Y-8/6-1/4	1157

Code	Page
E1Z-10/8-3/8	1157
E1Z-12/10-3/8	1157
E1Z-6/4-1/4	1157
E1Z-6/4-1/8	1157
E1Z-8/6-1/4	1157
E20	142
E200-1515-063411	227
E200-1515-063611	227
E21 09	974
E21 10	974
E21 11	974
E21 12	974
E21 13	974
E21 14	974
E21 16	974
E212-AU	1468
E212-BR	1471
E212-SS	1469
E24	142
E280-1515-032611	227
E2-AU	1468
E2-BR	1471
E2-PP	1470
E2-SS	1469
E3/8-20	1421
E34-AU	1468
E34-BR	1471
E34-PP	1470
E34-SS	1469
E350-1515-092611	227
E3-AU	1468
E3-BR	1471
E3-PP	1470
E3-SS	1469
E4	142
E4-AU	1468
E4-BR	1471
E4-PP	1470
E4-SS	1469
E5	142
E5/16-20	1421
E6	142
E6-AU	1468
E8	142
EA98.50.04	1065
EB12	1207
EB14	1207
EB14/2	1207
EB18	1207
EB316	1207
EB38	1207
EB-45-32-UPVC	1102
EB-45-40-UPVC	1102
EB-45-63-UPVC	1102
EB-45-75-UPVC	1102
EB-45-90-UPVC	1102
EB516	1207
EB-90-110-UPVC	1102
EB-90-20-UPVC	1102
EB-90-25-UPVC	1102
EB-90-32-UPVC	1102
EB-90-40-UPVC	1102
EB-90-50-UPVC	1102
EB-90-63-UPVC	1102
EB-90-75-UPVC	1102
EBC50B	421
EBC50C	421
EBC60B	421
EBC60C	421
EBC70B	421
EBC70C	421
EBF04	63
EBF06	63
EBF08	63
EBF10	63
EBF12	63
EBF16	63
EBF20	63
EBF24	63
EBM04	63
EBM06	63
EBM08	63
EBM10	63
EBM12	63
EBM16	63
EBM32	63
EBMF04	63
EBMF06	63
EBMF08	63
EBMF10	63
EBMF12	63
EBMF16	63
EBMF20	63
EBMF24	63
EBMF32	63
EC-1	1181
EC-112	1181
EC-114	1181
EC-12	1181
EC-14	1181
EC-18	1181
EC-2	1181
EC-34	1181
EC-38	1181
ECA12-01-L-N	227
ECON45	1636
ECON75	1636
ED3004-G230	430
ED3007-G230	430
EE-1	1183
EE-112	1183
EE-114	1183
EE-12	1183
EE-14	1183
EE-18	1183
EE-2	1183
EE-206/406	187
EE-208/408	187
EE-210/410	187
EE-212	1183
EE-212.7/412.7	187
EE-212/412	187
EE-214/414	187
EE-215/415	187
EE-216/416	187
EE-217.2/417.2	187
EE-218/418	187
EE-219/419	187
EE25-12	199
EE25-15	199
EE-3	1183
EE30-20	199
EE-320/620	187
EE-321.3/621.3	187
EE-322/622	187
EE-323/623	187
EE-325/625	187
EE-326.9/626.9	187
EE-328/628	187
EE-330/630	187
EE-332/632	187
EE-34	1183
EE35-25	199
EE-38	1183
EE-4	1183
EE42-30	199
EE-432	187
EE-433.7	187
EE-435	187
EE-438	187
EE-440	187
EE-442	187
EE-445	187
EE-448	187
EE-451	187
EE-45-110-UPVC	1102
EE-45-125-UPVC	1102
EE-45-140-UPVC	1102
EE-45-16-UPVC	1102
EE-45-200-UPVC	1102
EE-45-225-UPVC	1102
EE-45-25-UPVC	1102
EE-453.4	187
EE-45-32-UPVC	1102
EE-45-40-UPVC	1102
EE-45-50-UPVC	1102
EE-456.4	187
EE-45-63-UPVC	1102
EE-45-75-UPVC	1102
EE-45-90-UPVC	1102
EE-90-110-UPVC	1102
EE-90-125-UPVC	1102
EE-90-140-UPVC	1102
EE-90-160-UPVC	1102
EE-90-16-UPVC	1102
EE-90-200-UPVC	1102
EE-90-20-UPVC	1102
EE-90-225-UPVC	1102
EE-90-25-UPVC	1102
EE-90-32-UPVC	1102
EE-90-40-UPVC	1102
EE-90-50-UPVC	1102
EE-90-63-UPVC	1102
EE-90-75-UPVC	1102
EE-90-90-UPVC	1102
EEC1	1207
EEC12	1207
EEC14	1207
EEC18	1207
EEC316	1207
EEC34	1207
EEC38	1207
EEC516	1207
EE-MI1-1	1344
EE-MI1-112	1344
EE-MI1-112N	1344
EE-MI1-114	1344
EE-MI1-114N	1344
EE-MI1-12	1344
EE-MI1-12N	1344
EE-MI1-14	1344
EE-MI1-14N	1344
EE-MI1-1N	1344
EE-MI1-2	1344
EE-MI120-1	1343
EE-MI120-12	1343
EE-MI120-12N	1343
EE-MI120-1N	1343
EE-MI120-34	1343
EE-MI120-34N	1343
EE-MI1-212	1344
EE-MI1-212N	1344
EE-MI1-2N	1344
EE-MI1-3	1344
EE-MI130-1	1345
EE-MI130-1-112	1346
EE-MI130-1-112N	1346
EE-MI130-1-114	1346
EE-MI130-1-114N	1346
EE-MI130-112	1345
EE-MI130-1-12	1346
EE-MI130-112-1	1346
EE-MI130-112-114	1346
EE-MI130-112114N	1346
EE-MI130-112-12	1346
EE-MI130-112-12N	1346
EE-MI130-112-1N	1346
EE-MI130-112-2	1346
EE-MI130-112-2N	1346
EE-MI130-112-34	1346
EE-MI130-112-34N	1346
EE-MI130-112N	1345
EE-MI130-1-12N	1346
EE-MI130-114	1345
EE-MI130-114-1	1346
EE-MI130-114-112	1346
EE-MI130-114112N	1346
EE-MI130-114-12	1346
EE-MI130-114-12N	1346
EE-MI130-114-1N	1346
EE-MI130-114-2	1346
EE-MI130-114-2N	1346
EE-MI130-114-34	1346
EE-MI130-114-34N	1346
EE-MI130-114N	1345
EE-MI130-12	1345
EE-MI130-12-1	1346
EE-MI130-12-14	1346
EE-MI130-12-14N	1346
EE-MI130-12-1N	1346
EE-MI130-12-34	1346
EE-MI130-12-34N	1346
EE-MI130-12-38	1346
EE-MI130-12-38N	1346
EE-MI130-12N	1345
EE-MI130-1-34	1346
EE-MI130-1-34N	1346
EE-MI130-1-38	1346
EE-MI130-1-38N	1346
EE-MI130-14	1345
EE-MI130-14N	1345
EE-MI130-1N	1345
EE-MI130-2	1345
EE-MI130-2-1	1346
EE-MI130-2-112	1346
EE-MI130-2-112N	1346
EE-MI130-2-114	1346
EE-MI130-2-114N	1346
EE-MI130-212	1345
EE-MI130-2-12	1346
EE-MI130-212-1	1346
EE-MI130-212-112	1346
EE-MI130-212112N	1346
EE-MI130-212114N	1346
EE-MI130-212-1N	1346
EE-MI130-212-2	1346
EE-MI130-212-2N	1346
EE-MI130-212-34	1346
EE-MI130-2-12N	1346
EE-MI130-2-1N	1346
EE-MI130-2-212	1346
EE-MI130-2-212N	1346
EE-MI130-2-3	1346
EE-MI130-2-34	1346
EE-MI130-2-34N	1346
EE-MI130-2-3N	1346
EE-MI130-2N	1345
EE-MI130-3	1345
EE-MI130-3-112	1346
EE-MI130-3-112N	1346
EE-MI130-3-2	1346
EE-MI130-3-212	1346
EE-MI130-3-212N	1346
EE-MI130-3-2N	1346
EE-MI130-34	1345
EE-MI130-34-1	1346
EE-MI130-34-12	1346
EE-MI130-34-12N	1346
EE-MI130-34-14	1346
EE-MI130-34-14N	1346
EE-MI130-34-1N	1346
EE-MI130-34-38	1346
EE-MI130-34-38N	1346
EE-MI130-34N	1345
EE-MI130-38	1345
EE-MI130-38-12	1346
EE-MI130-38-12N	1346
EE-MI130-38-14	1346
EE-MI130-38-14N	1346
EE-MI130-38N	1345
EE-MI130-3N	1345
EE-MI130-4	1345
EE-MI130-4-2	1346
EE-MI130-4-2N	1346
EE-MI130-4-3	1346
EE-MI130-4-3N	1346
EE-MI130-4N	1345
EE-MI131-1	1345
EE-MI131-112	1345
EE-MI131-112N	1345

Code	Page
EE-MI131-114	1345
EE-MI131-114N	1345
EE-MI131-12	1345
EE-MI131-12N	1345
EE-MI131-1N	1345
EE-MI131-2	1345
EE-MI131-2N	1345
EE-MI131-34	1345
EE-MI131-34N	1345
EE-MI1-34	1344
EE-MI1-34N	1344
EEMI135-1	1347
EEMI135-1N	1347
EE-MI1-38	1344
EE-MI1-38N	1344
EE-MI1-3N	1344
EE-MI1-4	1344
EE-MI165-1	1347
EE-MI165-112	1347
EE-MI165-112N	1347
EE-MI165-114	1347
EE-MI165-114N	1347
EE-MI165-12	1347
EE-MI165-12N	1347
EE-MI165-1N	1347
EE-MI165-2N	1347
EE-MI165-34	1347
EE-MI165-34N	1347
EE-MI180-1	1348
EE-MI180-112	1348
EE-MI180-1-12	1348
EE-MI180-112N	1348
EE-MI180-1-12N	1348
EE-MI180-114	1348
EE-MI180-114-12	1348
EE-MI180-114-12N	1348
EE-MI180-114N	1348
EE-MI180-12	1348
EE-MI180-12-38	1348
EE-MI180-12-38N	1348
EE-MI180-12N	1348
EE-MI180-1-34	1348
EE-MI180-1-34N	1348
EE-MI180-1N	1348
EE-MI180-2	1348
EE-MI180-2-34	1348
EE-MI180-2-34N	1348
EE-MI180-2N	1348
EE-MI180-3	1348
EE-MI180-34	1348
EE-MI180-34-12	1348
EE-MI180-34-12N	1348
EE-MI180-34-38	1348
EE-MI180-34-38N	1348
EE-MI180-34N	1348
EE-MI180-38	1348
EE-MI180-38N	1348
EE-MI1A-1	1344
EE-MI1A-112	1344
EE-MI1A-112N	1344
EE-MI1A-114	1344
EE-MI1A-114N	1344
EE-MI1A-12	1344
EE-MI1A-12N	1344
EE-MI1A-1N	1344
EE-MI1A-2	1344
EE-MI1A-2N	1344
EE-MI1A-34	1344
EE-MI1A-34N	1344
EE-MI1A-38	1344
EE-MI1A-38N	1344
EE-MI2-1	1344
EE-MI2-112	1344
EE-MI2-112N	1344
EE-MI2-114	1344
EE-MI2-114N	1344
EE-MI2-12	1344
EE-MI2-12N	1344
EE-MI2-14	1344
EE-MI2-14N	1344
EE-MI2-1N	1344
EE-MI2-2	1344
EE-MI220-1	1347
EE-MI220-12	1347
EE-MI220-12N	1347
EE-MI220-1N	1347
EE-MI220-34	1347
EE-MI220-34N	1347
EE-MI221-1	1343
EE-MI221-112	1343
EE-MI221-112N	1343
EE-MI221-114	1343
EE-MI221-114N	1343
EE-MI221-12	1343
EE-MI221-12N	1343
EE-MI221-1N	1343
EE-MI221-2	1343
EE-MI2-212	1344
EE-MI221-2N	1343
EE-MI221-34	1343
EE-MI221-34N	1343
EE-MI221-38	1343
EE-MI221-38N	1343
EE-MI2-2N	1344
EE-MI2-3	1344
EE-MI2-34	1344
EE-MI2-34N	1344
EE-MI2-38	1344
EE-MI2-38N	1344
EE-MI2-3N	1344
EE-MI2-4	1344
EE-MI240-1-12	1340
EE-MI240-112-1	1340
EE-MI240-112-114	1340
EE-MI240-112114N	1340
EE-MI240-112-12	1340
EE-MI240-112-12N	1340
EE-MI240-112-1N	1340
EE-MI240-112-34	1340
EE-MI240-112-34N	1340
EE-MI240-1-12N	1340
EE-MI240-114-1	1340
EE-MI240-114-12	1340
EE-MI240-114-12N	1340
EE-MI240-114-1N	1340
EE-MI240-114-34	1340
EE-MI240-114-34N	1340
EE-MI240-114-38	1340
EE-MI240-114-38N	1340
EE-MI240-12-14	1340
EE-MI240-12-14N	1340
EE-MI240-12-38	1340
EE-MI240-12-38N	1340
EE-MI240-1-34	1340
EE-MI240-1-34N	1340
EE-MI240-1-38	1340
EE-MI240-1-38N	1340
EE-MI240-2-1	1340
EE-MI240-2-112	1340
EE-MI240-2-112N	1340
EE-MI240-2-114	1340
EE-MI240-2-114N	1340
EE-MI240-2-12	1340
EE-MI240-212-1	1340
EE-MI240-212112N	1340
EE-MI240-212114N	1340
EE-MI240-212-2	1340
EE-MI240-212-2N	1340
EE-MI240-2-12N	1340
EE-MI240-2-1N	1340
EE-MI240-2-34	1340
EE-MI240-2-34N	1340
EE-MI240-3-112	1340
EE-MI240-3-112N	1340
EE-MI240-3-2	1340
EE-MI240-3-212	1340
EE-MI240-3-212N	1340
EE-MI240-3-2N	1340
EE-MI240-34-12	1340
EE-MI240-34-12N	1340
EE-MI240-34-38	1340
EE-MI240-34-38N	1340
EE-MI240-38-14	1340
EE-MI240-38-14N	1340
EE-MI240-4-2	1340
EE-MI240-4-3	1340
EE-MI241-1-12	1339
EE-MI241-112-1	1339
EE-MI241-112-114	1339
EE-MI241-112114N	1339
EE-MI241-112-12	1339
EE-MI241-112-12N	1339
EE-MI241-112-1N	1339
EE-MI241-112-34	1339
EE-MI241-112-34N	1339
EE-MI241-1-12N	1339
EE-MI241-114-1	1339
EE-MI241-114-12	1339
EE-MI241-114-12N	1339
EE-MI241-114-1N	1339
EE-MI241-114-34	1339
EE-MI241-114-34N	1339
EE-MI241-114-38	1339
EE-MI241-12-14	1339
EE-MI241-12-14N	1339
EE-MI241-12-38	1339
EE-MI241-12-38N	1339
EE-MI241-1-34	1339
EE-MI241-1-34N	1339
EE-MI241-1-38	1339
EE-MI241-1-38N	1339
EE-MI241-2-1	1339
EE-MI241-2-112	1339
EE-MI241-2-112N	1339
EE-MI241-2-114	1339
EE-MI241-2-114N	1339
EE-MI241-2-12	1339
EE-MI241-212-1	1339
EE-MI241-212-112	1339
EE-MI241-212112N	1339
EE-MI241-212-114	1339
EE-MI241-212-1N	1339
EE-MI241-212-2	1339
EE-MI241-212-2N	1339
EE-MI241-2-12N	1339
EE-MI241-2-1N	1339
EE-MI241-2-34	1339
EE-MI241-2-34N	1339
EE-MI241-3-1	1339
EE-MI241-3-112	1339
EE-MI241-3-112N	1339
EE-MI241-3-114N	1339
EE-MI241-3-2	1339
EE-MI241-3-212	1339
EE-MI241-3-212N	1339
EE-MI241-3-2N	1339
EE-MI241-34-12	1339
EE-MI241-34-12N	1339
EE-MI241-34-14	1339
EE-MI241-34-14N	1339
EE-MI241-34-38	1339
EE-MI241-34-38N	1339
EE-MI241-38-14	1339
EE-MI241-38-14N	1339
EE-MI241-4-2	1339
EE-MI241-4-212	1339
EE-MI241-4-2N	1339
EE-MI241-4-3	1339
EE-MI245-1-12	1338
EE-MI245-112-1	1338
EE-MI245-112-114	1338
EE-MI245-112114N	1338
EE-MI245-112-12N	1338
EE-MI245-112-1N	1338
EE-MI245-112-34	1338
EE-MI245-112-34N	1338
EE-MI245-1-12N	1338
EE-MI245-114-1	1338
EE-MI245-114-12	1338
EE-MI245-114-12N	1338
EE-MI245-114-1N	1338
EE-MI245-114-34	1338
EE-MI245-114-34N	1338
EE-MI245-12-14	1338
EE-MI245-12-14N	1338
EE-MI245-12-38	1338
EE-MI245-12-38N	1338
EE-MI245-1-34	1338
EE-MI245-1-34N	1338
EE-MI245-14-18	1338
EE-MI245-2-1	1338
EE-MI245-2-112	1338
EE-MI245-2-112N	1338
EE-MI245-2-114	1338
EE-MI245-2-114N	1338
EE-MI245-212-112	1338
EE-MI245-212112N	1338
EE-MI245-212114N	1338
EE-MI245-212-2	1338
EE-MI245-212-2N	1338
EE-MI245-2-1N	1338
EE-MI245-3-2	1338
EE-MI245-3-212	1338
EE-MI245-3-212N	1338
EE-MI245-3-2N	1338
EE-MI245-34-12	1338
EE-MI245-34-12N	1338
EE-MI245-34-38	1338
EE-MI245-34-38N	1338
EE-MI245-38-14	1338
EE-MI245-38-14N	1338
EE-MI246-1-12	1339
EE-MI246-112-1	1339
EE-MI246-112-114	1339
EE-MI246-112114N	1339
EE-MI246-112-1N	1339
EE-MI246-1-12N	1339
EE-MI246-114-1	1339
EE-MI246-114-1N	1339
EE-MI246-114-34	1339
EE-MI246-114-34N	1339
EE-MI246-12-14	1339
EE-MI246-12-14N	1339
EE-MI246-12-38	1339
EE-MI246-12-38N	1339
EE-MI246-1-34	1339
EE-MI246-1-34N	1339
EE-MI246-2-112	1339
EE-MI246-2-112N	1339
EE-MI246-2-114	1339
EE-MI246-2-114N	1339
EE-MI246-34-12	1339
EE-MI246-34-12N	1339
EE-MI246-34-38	1339
EE-MI246-34-38N	1339
EE-MI246-38-14	1339
EE-MI246-38-14N	1339
EE-MI270-1	1340
EE-MI270-112	1340
EE-MI270-112N	1340
EE-MI270-114	1340
EE-MI270-114N	1340
EE-MI270-12	1340
EE-MI270-12N	1340
EE-MI270-14	1340
EE-MI270-14N	1340
EE-MI270-1N	1340
EE-MI270-2	1340
EE-MI270-212	1340
EE-MI270-212N	1340
EE-MI270-2N	1340
EE-MI270-3	1340
EE-MI270-34	1340
EE-MI270-34N	1340
EE-MI270-38	1340
EE-MI270-38N	1340
EE-MI270-3N	1340
EE-MI270-4	1340
EE-MI270-4N	1340
EE-MI280-1	1338

Code	Page
EE-MI280-112	1338
EE-MI280-112N	1338
EE-MI280-114	1338
EE-MI280-114N	1338
EE-MI280-12	1338
EE-MI280-12N	1338
EE-MI280-14	1338
EE-MI280-14N	1338
EE-MI280-1N	1338
EE-MI280-2	1338
EE-MI280-212	1338
EE-MI280-212N	1338
EE-MI280-2N	1338
EE-MI280-3	1338
EE-MI280-34	1338
EE-MI280-34N	1338
EE-MI280-38	1338
EE-MI280-38N	1338
EE-MI280-3N	1338
EE-MI280-4	1338
EE-MI280-4N	1338
EE-MI290-1	1341
EE-MI290-112	1341
EE-MI290-112N	1341
EE-MI290-114	1341
EE-MI290-114N	1341
EE-MI290-12	1341
EE-MI290-12N	1341
EE-MI290-14	1341
EE-MI290-14N	1341
EE-MI290-1N	1341
EE-MI290-2	1341
EE-MI290-212	1341
EE-MI290-212N	1341
EE-MI290-2N	1341
EE-MI290-3	1341
EE-MI290-34	1341
EE-MI290-34N	1341
EE-MI290-38	1341
EE-MI290-38N	1341
EE-MI290-3N	1341
EE-MI290-4	1341
EE-MI290-4N	1341
EE-MI2A-1	1344
EE-MI2A-112	1344
EE-MI2A-112N	1344
EE-MI2A-114	1344
EE-MI2A-114N	1344
EE-MI2A-12	1344
EE-MI2A-12N	1344
EE-MI2A-1N	1344
EE-MI2A-2	1344
EE-MI2A-2N	1344
EE-MI2A-34	1344
EE-MI2A-34N	1344
EE-MI2A-38N	1344
EE-MI300-1	1341
EE-MI300-112	1341
EE-MI300-112N	1341
EE-MI300-114	1341
EE-MI300-114N	1341
EE-MI300-12	1341
EE-MI300-12N	1341
EE-MI300-14	1341

Code	Page
EE-MI300-14N	1341
EE-MI300-1N	1341
EE-MI300-2	1341
EE-MI300-212	1341
EE-MI300-212N	1341
EE-MI300-2N	1341
EE-MI300-3	1341
EE-MI300-34	1341
EE-MI300-34N	1341
EE-MI300-38	1341
EE-MI300-38N	1341
EE-MI300-3N	1341
EE-MI300-4	1341
EE-MI300-4N	1341
EE-MI301-1	1341
EE-MI301-112	1341
EE-MI301-112N	1341
EE-MI301-12	1341
EEMI30-1-12-1	1346
EEMI30112114112	1346
EEMI30112114112N	1346
EEMI30-1-12-1N	1346
EE-MI301-12N	1341
EEMI301141114	1346
EEMI301141114N	1346
EEMI3011434114	1346
EEMI3011434114N	1346
EE-MI301-1N	1341
EE-MI301-2	1341
EEMI30-12-38-12	1346
EEMI30-12-38-12N	1346
EE-MI301-2N	1341
EE-MI301-34	1341
EEMI30-1-34-1	1346
EEMI30-1-34-1N	1346
EE-MI301-34N	1341
EE-MI301-38	1341
EE-MI301-38N	1341
EEMI30-34-12-34	1346
EEMI30-34-12-34N	1346
EEMI30C11211	1347
EEMI30C1121114	1347
EEMI30C1121114N	1347
EEMI30C112114114	1347
EEMI30C11211N	1347
EEMI30C11212	1347
EEMI30C1121234	1347
EEMI30C1121234N	1347
EEMI30C11212N	1347
EEMI30C112134	1347
EEMI30C112134N	1347
EEMI30C11234	1347
EEMI30C11234N	1347
EEMI30C11411	1347
EEMI30C11411N	1347
EEMI30C114121	1347
EEMI30C114121N	1347
EEMI30C114341	1347
EEMI30C114341N	1347
EEMI30C1143434	1347
EEMI30C1143434N	1347
EEMI30C123838	1347
EEMI30C123838N	1347
EEMI30C13412	1347

Code	Page
EEMI30C13434	1347
EEMI30C13434N	1347
EEMI30C2112112	1347
EEMI30C2112112N	1347
EEMI30C341212	1347
EEMI30C341212N	1347
EEMI30C343812	1347
EEMI30C343812N	1347
EE-MI3-1	1344
EE-MI310-1	1342
EE-MI310-112	1342
EE-MI310-112N	1342
EE-MI310-114	1342
EE-MI310-114N	1342
EE-MI310-12	1342
EE-MI310-12N	1342
EE-MI310-14	1342
EE-MI310-14N	1342
EE-MI310-1N	1342
EE-MI310-2	1342
EE-MI310-212	1342
EE-MI310-212N	1342
EE-MI310-2N	1342
EE-MI310-3	1342
EE-MI310-34	1342
EE-MI310-34N	1342
EE-MI310-38	1342
EE-MI310-38N	1342
EE-MI310-3N	1342
EE-MI3-12	1344
EE-MI3-12N	1344
EE-MI3-1N	1344
EE-MI321-1	1348
EE-MI321-112	1348
EE-MI321-112-N	1348
EE-MI321-114	1348
EE-MI321-114-N	1348
EE-MI321-12	1348
EE-MI321-12-N	1348
EE-MI321-1-N	1348
EE-MI321-2	1348
EE-MI321-212	1348
EE-MI321-212-N	1348
EE-MI321-2-N	1348
EE-MI321-3	1348
EE-MI321-34	1348
EE-MI321-34-N	1348
EE-MI321-38	1348
EE-MI321-38-N	1348
EE-MI321-3-N	1348
EE-MI321-4	1348
EE-MI321-4-N	1348
EE-MI326-1	1348
EE-MI326-112	1348
EE-MI326-112-N	1348
EE-MI326-114	1348
EE-MI326-114-N	1348
EE-MI326-1-N	1348
EE-MI326-34	1348
EE-MI326-34-N	1348
EE-MI3-34	1344
EE-MI3-34N	1344
EE-MI340-1	1341
EE-MI340-112	1341

Code	Page
EE-MI340-112N	1341
EE-MI340-114	1341
EE-MI340-114N	1341
EE-MI340-12	1341
EE-MI340-12N	1341
EE-MI340-1N	1341
EE-MI340-2	1341
EE-MI340-212	1341
EE-MI340-212N	1341
EE-MI340-2N	1341
EE-MI340-3	1341
EE-MI340-34	1341
EE-MI340-34N	1341
EE-MI340-38	1341
EE-MI340-38N	1341
EE-MI340-3N	1341
EE-MI340-4	1341
EE-MI341-1	1339
EE-MI341-112	1339
EE-MI341-112N	1339
EE-MI341-114	1339
EE-MI341-114N	1339
EE-MI341-12	1339
EE-MI341-12N	1339
EE-MI341-1N	1339
EE-MI341-2	1339
EE-MI341-212	1339
EE-MI341-212N	1339
EE-MI341-2N	1339
EE-MI341-3	1339
EE-MI341-34	1339
EE-MI341-34N	1339
EE-MI341-38	1339
EE-MI341-38N	1339
EE-MI341-3N	1339
EE-MI341-4	1339
EEMI3C112114114N	1347
EE-MI40-1	1345
EE-MI40-112	1345
EE-MI40-112N	1345
EE-MI40-114	1345
EE-MI40-114N	1345
EE-MI40-12	1345
EE-MI40-12N	1345
EE-MI40-14	1345
EE-MI40-14N	1345
EE-MI40-1N	1345
EE-MI40-2	1345
EE-MI40-212	1345
EE-MI40-2N	1345
EE-MI40-3	1345
EE-MI40-34	1345
EE-MI40-34N	1345
EE-MI40-38	1345
EE-MI40-38N	1345
EE-MI40-4	1345
EE-MI41-1	1345
EE-MI41-112	1345
EE-MI41-112N	1345
EE-MI41-114	1345
EE-MI41-114N	1345
EE-MI41-12	1345
EE-MI41-12N	1345
EE-MI41-1N	1345

Code	Page
EE-MI41-2	1345
EE-MI41-212	1345
EE-MI41-212N	1345
EE-MI41-2N	1345
EE-MI41-3	1345
EE-MI41-34	1345
EE-MI41-34N	1345
EE-MI41-38	1345
EE-MI41-38N	1345
EE-MI471-12	1343
EE-MI471-12N	1343
EE-MI471-34	1343
EE-MI471-34N	1343
EE-MI529A-1	1339
EE-MI529A-12	1339
EE-MI529A-34	1339
EE-MI85-12	1348
EE-MI85-12N	1348
EE-MI85-34	1348
EE-MI85-34N	1348
EE-MI90-1	1342
EE-MI90-112	1342
EE-MI90-1-12	1343
EE-MI90-112-1	1343
EE-MI90-112-114	1343
EE-MI90-112-114N	1343
EE-MI90-112-1N	1343
EE-MI90-112-34	1343
EE-MI90-112N	1342
EE-MI90-1-12N	1343
EE-MI90-114	1342
EE-MI90-114-1	1343
EE-MI90-114-1N	1343
EE-MI90-114N	1342
EE-MI90-12	1342
EE-MI90-12-38	1343
EE-MI90-12-38N	1343
EE-MI90-12N	1342
EE-MI90-1-34	1343
EE-MI90-1-34N	1343
EE-MI90-14	1342
EE-MI90-14N	1342
EE-MI90-1N	1342
EE-MI90-2	1342
EE-MI90-2-1	1343
EE-MI90-2-112	1343
EE-MI90-2-112N	1343
EE-MI90-2-114	1343
EE-MI90-2-114N	1343
EE-MI90-212	1342
EE-MI90-212N	1342
EE-MI90-2N	1342
EE-MI90-3	1342
EE-MI90-34	1342
EE-MI90-34-12	1343
EE-MI90-34-12N	1343
EE-MI90-34-38	1343
EE-MI90-34N	1342
EE-MI90-38	1342
EE-MI90-38N	1342
EE-MI90-3N	1342
EE-MI90-4	1342
EE-MI90-4N	1342
EE-MI92-1	1342

Code	Page
EE-MI92-112	1342
EE-MI92-112N	1342
EE-MI92-114	1342
EE-MI92-114N	1342
EE-MI92-12	1342
EE-MI92-12-38	1343
EE-MI92-12-38N	1343
EE-MI92-12N	1342
EE-MI92-1-34	1343
EE-MI92-1-34N	1343
EE-MI92-14	1342
EE-MI92-14N	1342
EE-MI92-1N	1342
EE-MI92-2	1342
EE-MI92-212	1342
EE-MI92-212N	1342
EE-MI92-2N	1342
EE-MI92-3	1342
EE-MI92-34	1342
EE-MI92-34-12	1343
EE-MI92-34-12N	1343
EE-MI92-34N	1342
EE-MI92-38	1342
EE-MI92-38N	1342
EE-MI92-3N	1342
EE-MI92-4	1342
EE-MI92-4N	1342
EE-MI94-1	1342
EE-MI94-12	1342
EE-MI94-12N	1342
EE-MI94-1N	1342
EE-MI94-34	1342
EE-MI94-34N	1342
EE-MI96-1	1343
EE-MI96-112	1343
EE-MI96-112N	1343
EE-MI96-114	1343
EE-MI96-114N	1343
EE-MI96-12	1343
EE-MI96-12N	1343
EE-MI96-1N	1343
EE-MI96-2	1343
EE-MI96-2N	1343
EE-MI96-34	1343
EE-MI96-34N	1343
EE-MI96-38	1343
EE-MI96-38N	1343
EE-MI98-1	1342
EE-MI98-112	1342
EE-MI98-112N	1342
EE-MI98-114	1342
EE-MI98-114N	1342
EE-MI98-12	1342
EE-MI98-12N	1342
EE-MI98-1N	1342
EE-MI98-2	1342
EE-MI98-2N	1342
EE-MI98-34	1342
EE-MI98-34N	1342
EE-MI98-38	1342
EE-MI98-38N	1342
EF1	430
EFA-410/210	187
EFA-422	187
EFA-425	187
EFA-428	187
EFA-430	187
EFA-435	187
EFA-510	187
EFA-512	187
EFA-515	187
EFA-535	187
EFA-538	187
EFA-542	187
EFA-548.3	187
EFA-560.3	187
EFA-610/310	187
EFA-612/312	187
EFA-615/315	187
EFA-618	187
EFA-618/318	187
EFA-620	187
EFA-620/320	187
EFA-622	187
EFA-625	187
EFA-628	187
EFA-630	187
EFC56014	1022
EFC5601W	1022
EFL0301	252
EFL0501	252
EFL1001	252
EFL1501	252
EFW0152	252
EFW0302	252
EFW0502	252
EFW1002	252
EFW1502	252
EGE-DKO-06L-2EO	162
EGE-DKO-06L-4EO	162
EGE-DKO-06L6EO	162
EGE-DKO-06S-4EO	162
EGE-DKO-08L-2EO	162
EGE-DKO-08L-4EO	162
EGE-DKO-08L6EO	162
EGE-DKO-08L8EO	162
EGE-DKO-08S-4EO	162
EGE-DKO-08S-6EO	162
EGE-DKO-10L-2EO	162
EGE-DKO-10L-4EO	162
EGE-DKO-10L6EO	162
EGE-DKO-10L8EO	162
EGE-DKO-10S-4EO	162
EGE-DKO-10S-6EO	162
EGE-DKO-10S-8EO	162
EGE-DKO-12L-2EO	162
EGE-DKO-12L-4EO	162
EGE-DKO-12L6EO	162
EGE-DKO-12L8EO	162
EGE-DKO-12S-4EO	162
EGE-DKO-12S-6EO	162
EGE-DKO-12S-8EO	162
EGE-DKO-14S-8EO	162
EGE-DKO-15L-12EO	162
EGE-DKO-15L6EO	162
EGE-DKO-15L8EO	162
EGE-DKO-16S-12EO	162
EGE-DKO-16S-6EO	162
EGE-DKO-16S-8EO	162
EGE-DKO-18L-12EO	162
EGE-DKO-18L6EO	162
EGE-DKO-18L8EO	162
EGE-DKO-20S-12EO	162
EGE-DKO-20S-16EO	162
EGE-DKO-20S-8EO	162
EGE-DKO-22L-12EO	162
EGE-DKO-22L-16EO	162
EGE-DKO-22L8EO	162
EGE-DKO-25S-12EO	162
EGE-DKO-25S-16EO	162
EGE-DKO-28L-12EO	162
EGE-DKO-28L-16EO	162
EGE-DKO-30S-16EO	162
EGE-DKO-30S-20EO	162
EGE-DKO-35L-20EO	162
EGE-DKO-38S-24EO	162
EGE-DKO-42L-20EO	162
EGE-DKO-42L-24EO	162
EGESD10L1/4NPT	128
EGESD10LMWD	128
EGESD10LRWD	128
EGESD10S3/8NPT	128
EGESD10SMWD	128
EGESD10SRWD	128
EGESD12L3/8NPT	128
EGESD12LMWD	128
EGESD12LRWD	128
EGESD12S3/8NPT	128
EGESD12SMWD	128
EGESD12SR1/2WD	128
EGESD12SRWD	128
EGESD14SMWD	128
EGESD14SRWD	128
EGESD15L1/2NPT	128
EGESD15LMWD	128
EGESD15LRWD	128
EGESD16S1/2NPT	128
EGESD16SMWD	128
EGESD16SRWD	128
EGESD18L1/2NPT	128
EGESD18LMWD	128
EGESD18LRWD	128
EGESD20S3/4NPT	128
EGESD20SMWD	128
EGESD20SRWD	128
EGESD22L3/4NPT	128
EGESD22LMWD	128
EGESD22LRWD	128
EGESD25S1NPT	128
EGESD25SMWD	128
EGESD25SRWD	128
EGESD28L1NPT	128
EGESD28LMWD	128
EGESD28LRWD	128
EGESD30S11/4NPT	128
EGESD30SMWD	128
EGESD30SRWD	128
EGESD35LMWD	128
EGESD35LRWD	128
EGESD38S11/2NPT	128
EGESD38SMWD	128
EGESD38SRWD	128
EGESD42LMWD	128
EGESD42LRWD	128
EGESD6L1/8NPT	128
EGESD6LMWD	128
EGESD6LRWD	128
EGESD6S1/4NPT	128
EGESD6SMWD	128
EGESD6SRWD	128
EGESD8L1/4NPT	128
EGESD8LMWD	128
EGESD8LRWD	128
EGESD8S1/4NPT	128
EGESD8SMWD	128
EGESD8SRWD	128
EGHC10-16	1514
EGHC12-20	1514
EGHC16-25	1514
EGHC20-32	1514
EGHC25-40	1514
EGHC32-50	1514
EGHC35-45	1514
EGHC40-60	1514
EGHC50-70	1514
EGHC60-80	1514
EGHC70-90	1514
EGHC80-100	1514
EGHC8-12	1514
EH10MS	182
EH12MS	182
EH13MS	182
EH15MS	182
EH16MS	182
EH18MS	182
EH19MS	182
EH20MS	182
EH24MS	182
EH25MS	182
EH4MS	182
EH5MS	182
EH6MS	182
EH7MS	182
EH8MS	182
EH9MS	182
EHCVG1	241
EHCVG1/2	241
EHCVG1/4	241
EHCVG3/4	241
EHCVG3/8	241
EHRVG-1	241
EHRVG-112	241
EHRVG-112-3CP	241
EHRVG-112-5CP	241
EHRVG-114	241
EHRVG-114-3CP	241
EHRVG-114-5CP	241
EHRVG-12	241
EHRVG-12-3CP	241
EHRVG-12-5CP	241
EHRVG-1-3CP	241
EHRVG-14	241
EHRVG-14-3CP	241
EHRVG-14-5CP	241
EHRVG-1-5CP	241
EHRVG-2	241
EHRVG-34	241
EHRVG-34-3CP	241
EHRVG-34-5CP	241
EHRVG-38	241
EHRVG-38-3CP	241
EHRVG-38-5CP	241
EHT-12-10	1144
EHT-12-13	1144
EHT-12-8	1144
EHT-14-10	1144
EHT-14-13	1144
EHT-14-6	1144
EHT-14-8	1144
EHT-18-10	1144
EHT-18-6	1144
EHT-18-8	1144
EHT-38-10	1144
EHT-38-13	1144
EHT-38-6	1144
EHT-38-8	1144
EHTVG1	241
EHTVG1/2	241
EHTVG1/4	241
EHTVG3/4	241
EHTVG3/8	241
EKA10V	1479
EKA12V	1479
EKA34V	1479
EKI10V	1479
EKI12V	1479
EKI34V	1479
EKI38V	1479
EKMV	1479
EKMV-K	1479
EKOV	1479
EKT10V	1479
EKT13V	1479
EKT19V	1479
EKT25V	1479
EL12	1208
EL14	1208
EL18	1208
EL316	1208
EL34	1208
EL38	1208
EL516	1208
EL53-112-ABS	1097
EL53-112-UPVC	1109
EL53-114-ABS	1097
EL53-114-UPVC	1109
EL53-12-ABS	1097
EL53-12-UPVC	1109
EL53-1-ABS	1097
EL53-1-UPVC	1109
EL53-212-ABS	1097
EL53-212-UPVC	1109
EL53-2-ABS	1097
EL53-2-UPVC	1109
EL53-34-ABS	1097
EL53-34-UPVC	1109
EL53-3-ABS	1097
EL53-3-UPVC	1109
EL53-4-ABS	1097
EL53-4-UPVC	1109

Code	Page
EL53-5-ABS	1097
EL53-5-UPVC	1109
EL53-6-ABS	1097
EL53-6-UPVC	1109
EL53-8-UPVC	1109
EL-DKOL-06	161
EL-DKOL-08	161
EL-DKOL-10	161
EL-DKOL-12	161
EL-DKOL-15	161
EL-DKOL-18	161
EL-DKOL-22	161
EL-DKOL-28	161
EL-DKOL-35	161
EL-DKOL-42	161
EL-DKOS-06	161
EL-DKOS-08	161
EL-DKOS-10	161
EL-DKOS-12	161
EL-DKOS-14	161
EL-DKOS-16	161
EL-DKOS-20	161
EL-DKOS-25	161
EL-DKOS-30	161
EL-DKOS-38	161
ELSD 10 L	134
ELSD 10 S	134
ELSD 12 L	134
ELSD 12 S	134
ELSD 14 S	134
ELSD 15 L	134
ELSD 16 S	134
ELSD 18 L	134
ELSD 20 S	134
ELSD 22 L	134
ELSD 25 S	134
ELSD 28 L	134
ELSD 30 S	134
ELSD 35 L	134
ELSD 38 S	134
ELSD 42 L	134
ELSD 6 L	134
ELSD 6 S	134
ELSD 8 L	134
ELSD 8 S	134
ELVD10L	129
ELVD10S	129
ELVD12L	129
ELVD12S	129
ELVD14S	129
ELVD15L	129
ELVD16S	129
ELVD18L	129
ELVD20S	129
ELVD22L	129
ELVD25S	129
ELVD28L	129
ELVD30S	129
ELVD35L	129
ELVD38S	129
ELVD42L	129
ELVD6L	129
ELVD6S	129
ELVD8L	129
ELVD8S	129
EMASD10LR	130
EMASD10SR	130
EMASD12LR	130
EMASD12SR	130
EMASD6LR	130
EMASD6SR	130
EMASD8LR	130
EMASD8SR	130
ENBN-112X100	1381
ENBN-112X100N	1382
ENBN-112X150	1381
ENBN-112X150N	1382
ENBN-112X200	1381
ENBN-112X200N	1382
ENBN-112X300	1381
ENBN-112X300N	1382
ENBN-112X80	1381
ENBN-112X80N	1382
ENBN-114X100	1381
ENBN-114X100N	1382
ENBN-114X150	1381
ENBN-114X150N	1382
ENBN-114X200	1381
ENBN-114X200N	1382
ENBN-114X300	1381
ENBN-114X300N	1382
ENBN-114X80	1381
ENBN-114X80N	1382
ENBN-12X100	1381
ENBN-12X100N	1382
ENBN-12X150	1381
ENBN-12X150N	1382
ENBN-12X200	1381
ENBN-12X200N	1382
ENBN-12X250	1381
ENBN-12X250N	1382
ENBN-12X30	1381
ENBN-12X300	1381
ENBN-12X300N	1382
ENBN-12X30N	1382
ENBN-12X40	1381
ENBN-12X40N	1382
ENBN-12X50	1381
ENBN-12X50N	1382
ENBN-12X60	1381
ENBN-12X60N	1382
ENBN-12X80	1381
ENBN-12X80N	1382
ENBN-14X100	1381
ENBN-14X100N	1382
ENBN-14X200	1381
ENBN-14X200N	1382
ENBN-14X250	1381
ENBN-14X250N	1382
ENBN-14X40	1381
ENBN-14X40N	1382
ENBN-14X60	1381
ENBN-14X60N	1382
ENBN-14X80	1381
ENBN-14X80N	1382
ENBN-18X40	1381
ENBN-18X40N	1382
ENBN-18X60	1381
ENBN-18X60N	1382
ENBN-1X100	1381
ENBN-1X100N	1382
ENBN-1X150	1381
ENBN-1X150N	1382
ENBN-1X200	1381
ENBN-1X200N	1382
ENBN-1X300	1381
ENBN-1X300N	1382
ENBN-1X40	1381
ENBN-1X40N	1382
ENBN-1X50	1381
ENBN-1X50N	1382
ENBN-1X60	1381
ENBN-1X60N	1382
ENBN-1X80	1381
ENBN-1X80N	1382
ENBN-212X100	1381
ENBN-212X100N	1382
ENBN-212X150	1381
ENBN-212X150N	1382
ENBN-212X200	1381
ENBN-212X200N	1382
ENBN-212X300	1381
ENBN-212X300N	1382
ENBN-2X100	1381
ENBN-2X100N	1382
ENBN-2X150	1381
ENBN-2X150N	1382
ENBN-2X200	1381
ENBN-2X200N	1382
ENBN-2X300	1381
ENBN-2X300N	1382
ENBN-2X80	1381
ENBN-2X80N	1382
ENBN-34X100	1381
ENBN-34X100N	1382
ENBN-34X150	1381
ENBN-34X150N	1382
ENBN-34X200	1381
ENBN-34X200N	1382
ENBN-34X300	1381
ENBN-34X300N	1382
ENBN-34X40	1381
ENBN-34X40N	1382
ENBN-34X60	1381
ENBN-34X60N	1382
ENBN-34X80	1381
ENBN-34X80N	1382
ENBN-38X100	1381
ENBN-38X100N	1382
ENBN-38X150	1381
ENBN-38X150N	1382
ENBN-38X200	1381
ENBN-38X200N	1382
ENBN-38X40	1381
ENBN-38X40N	1382
ENBN-38X50	1381
ENBN-38X50N	1382
ENBN-38X60	1381
ENBN-38X60N	1382
ENBN-38X80	1381
ENBN-38X80N	1382
ENBN-3X100	1381
ENBN-3X100N	1382
ENBN-3X150	1381
ENBN-3X150N	1382
ENBN-3X200	1381
ENBN-3X200N	1382
ENBN-3X300	1381
ENBN-3X300N	1382
ENBN-4X100	1381
ENBN-4X100N	1382
ENBN-4X150	1381
ENBN-4X150N	1382
ENBN-4X200	1381
ENBN-4X200N	1382
ENBN-4X300	1381
ENBN-4X300N	1382
EP02ORR	1753
EP06ORR	1753
EP10ORR	1753
EPB12NFA	257
EPB12NFB	257
EPB12NFC	257
EPB12NFD	257
EPB13NFA	257
EPB13NFB	257
EPB13NFC	257
EPB13NFD	257
EPB21NFA	257
EPB21NFB	257
EPB21NFC	257
EPB21NFD	257
EPB22NFA	258
EPB22NFB	258
EPB22NFC	258
EPB22NFD	258
EPB31NFA	257
EPB31NFB	257
EPB31NFC	257
EPB31NFD	257
EPB33NFA	257
EPB33NFB	257
EPB33NFC	257
EPB33NFD	257
EPB34NFA	257
EPB34NFB	257
EPB34NFC	257
EPB34NFD	257
EPDM-1	1472
EPDM-112	1472
EPDM-114	1472
EPDM-12	1472
EPDM-2	1472
EPDM-212	1472
EPDM-3	1472
EPDM-34	1472
EPDM-4	1472
EPF1105QIBPMG081	247
EPF1110QIBPMG081	247
EPF1-12-10	247
EPF1-12-2	247
EPF1-12-20	247
EPF1-12-5	247
EPF2205QIBPMG121	247
EPF2210QIBPMG121	247
EPF2-34-10	247
EPF2-34-2	247
EPF2-34-20	247
EPF2-34-5	247
EPF3-1-10	247
EPF3-1-2	247
EPF3-1-5	247
EPF3205QIBPMG161	247
EPF3210QIBPMG161	247
EPF4-114-10	247
EPF4-114-5	247
EPF4205QIBPMG201	247
EPF4210QIBPMG201	247
EPF5105QIBPMG241	247
EPF5110QIBPMG241	247
EPF5-112-20	247
EPFSK001	247
EPFSK002	247
EPFSK003	247
EPFSK004	247
EPG20NFA	258
EPG20NFB	258
EPG20NFC	258
EPG20NFD	258
EPG21NFA	258
EPG21NFB	258
EPG21NFC	258
EPG21NFD	258
EPG22NFA	258
EPG22NFB	258
EPG22NFC	258
EPG22NFD	258
EPG31NFA	258
EPG31NFB	258
EPG31NFC	258
EPG31NFD	258
EPS-102100	938
EPS-102105	938
EPS-102110	938
EPS-102115	938
EPS-102120	938
EPS-102125	938
EPS-102150	938
EPS-102155	938
EPS-102160	938
EPS-102165	938
EPS-102170	938
EPS-102175	938
EPS-102200	938
EPS-102205	938
EPS-102210	938
EPS-102215	938
EPS-102220	938
EPS-102225	938
EPS-102420	939
EPS-102425	939
EPS-102430	939
EPS-102450	939
EPS-102455	939
EPS-102460	939
EPS-102470	939
EPS-102475	939
EPS-102480	939
EPS-CFBO-10	1217
EPS-CFBO-12	1217

Code	Page
EPS-CFBO-15	1217
EPS-CFBO-20	1217
EPS-CFBO-22	1217
EPS-CFBO-25	1217
EPS-CFBO-28	1217
EPS-CFBO-3/4	1217
EPS-CFBO-35	1217
EPS-CFBO-42	1217
EPS-CFBO-54	1217
EPS-CFBO-8	1217
EPS-CFBTC-15-12	1217
EPS-CFCO-10	1217
EPS-CFCO-12	1217
EPS-CFCO-15	1217
EPS-CFCO-20	1217
EPS-CFCO-22	1217
EPS-CFCO-25	1217
EPS-CFCO-28	1217
EPS-CFCO-3/4	1217
EPS-CFCO-35	1217
EPS-CFCO-42	1217
EPS-CFCO-54	1217
EPS-CFCO-8	1217
EPS-CFE-10	1216
EPS-CFE-12	1216
EPS-CFE-15	1216
EPS-CFE-22	1216
EPS-CFE-22-15	1216
EPS-CFE-28	1216
EPS-CFE-35	1216
EPS-CFE-42	1216
EPS-CFE-54	1216
EPS-CFE-6	1216
EPS-CFE-8	1216
EPS-CFET-10	1217
EPS-CFET-12	1217
EPS-CFET-15	1217
EPS-CFET-22	1217
EPS-CFET-28	1217
EPS-CFET-35	1217
EPS-CFET-42	1217
EPS-CFET-54	1217
EPS-CFET-6	1217
EPS-CFET-8	1217
EPS-CFF-10-12	1216
EPS-CFF-10-14	1216
EPS-CFF-10-38	1216
EPS-CFF-15-12	1216
EPS-CFF-15-14	1216
EPS-CFF-15-34	1216
EPS-CFF-15-38	1216
EPS-CFF-22-1	1216
EPS-CFF-22-12	1216
EPS-CFF-22-34	1216
EPS-CFF-28-1	1216
EPS-CFF-28-34	1216
EPS-CFF-35-114	1216
EPS-CFF-42-112	1216
EPS-CFF-54-2	1216
EPS-CFF-6-14	1216
EPS-CFF-8-14	1216
EPS-CFF-8-38	1216
EPS-CFFE-10-12	1216
EPS-CFFE-10-14	1216
EPS-CFFE-10-38	1216
EPS-CFFE-15-12	1216
EPS-CFFE-15-14	1216
EPS-CFFE-15-34	1216
EPS-CFFE-22-1	1216
EPS-CFFE-22-12	1216
EPS-CFFE-22-34	1216
EPS-CFFE-28-1	1216
EPS-CFFE-35-114	1216
EPS-CFFE-54-2	1216
EPS-CFFE-8-14	1216
EPS-CFM-10-12	1216
EPS-CFM-10-14	1216
EPS-CFM-10-38	1216
EPS-CFM-12-14	1216
EPS-CFM-12-38	1216
EPS-CFM-15-12	1216
EPS-CFM-15-14	1216
EPS-CFM-15-34	1216
EPS-CFM-15-38	1216
EPS-CFM-22-1	1216
EPS-CFM-22-12	1216
EPS-CFM-22-34	1216
EPS-CFM-28-1	1216
EPS-CFM-28-34	1216
EPS-CFM-35-114	1216
EPS-CFM-42-112	1216
EPS-CFM-54-2	1216
EPS-CFM-6-14	1216
EPS-CFM-8-12	1216
EPS-CFM-8-14	1216
EPS-CFM-8-38	1216
EPS-CFME-10-12	1216
EPS-CFME-10-14	1216
EPS-CFME-10-38	1216
EPS-CFME-15-12	1216
EPS-CFME-15-14	1216
EPS-CFME-15-34	1216
EPS-CFME-22-1	1216
EPS-CFME-22-34	1216
EPS-CFME-28-1	1216
EPS-CFME-35-114	1216
EPS-CFME-42-112	1216
EPS-CFME-54-2	1216
EPS-CFME-8-14	1216
EPS-CFME-8-38	1216
EPS-CFN-10	1217
EPS-CFN-15	1217
EPS-CFN-22	1217
EPS-CFN-28	1217
EPS-CFN-8	1217
EPS-CFR-10-8	1216
EPS-CFR-12-10	1216
EPS-CFR-15-10	1216
EPS-CFR-15-12	1216
EPS-CFR-15-8	1216
EPS-CFR-22-15	1216
EPS-CFR-28-15	1216
EPS-CFR-28-22	1216
EPS-CFR3-10-6	1217
EPS-CFR3-10-8	1217
EPS-CFR3-15-10	1217
EPS-CFR3-15-12	1217
EPS-CFR3-15-8	1217
EPS-CFR3-28-15	1217
EPS-CFR3-28-22	1217
EPS-CFR3-35-15	1217
EPS-CFR3-35-22	1217
EPS-CFR3-42-15	1217
EPS-CFR3-42-28	1217
EPS-CFR3-54-28	1217
EPS-CFR3-54-42	1217
EPS-CFS-10	1216
EPS-CFS-12	1216
EPS-CFS-15	1216
EPS-CFS-22	1216
EPS-CFS-28	1216
EPS-CFS-35	1216
EPS-CFS-42	1216
EPS-CFS-54	1216
EPS-CFS-6	1216
EPS-CFS-8	1216
EPS-CFSE-10	1217
EPS-CFSE-12	1217
EPS-CFSE-15	1217
EPS-CFSE-22	1217
EPS-CFSE-28	1217
EPS-CFSE-35	1217
EPS-CFSE-42	1217
EPS-CFSE-54	1217
EPS-CFSE-8	1217
EPS-CFSTC-15-12	1217
EPS-CFSTC-15-34	1217
EPS-CFSTC-22-34	1217
EPS-CFTC-15	1217
EPS-CFTC-22	1217
EPS-CFTC-28	1217
EPS-CFTC-35	1217
EPS-CFTC-42	1217
EPS-CFTC-54	1217
EPS-CFWE-15-12	1216
EPS-CFWE-22-12	1216
EPS-CFWE-22-34	1216
EPS-CS10-S	1546
EPS-CS15-S	1546
EPS-CS215-S	1546
EPS-CS22-S	1546
EPS-CS28-S	1546
EPS-CS35-S	1546
EPS-CS42-S	1546
EPS-CS54-S	1546
EPS-DPBSP15CP-S	1546
EPS-DPBSP15-S	1546
EPS-DPBSP22-S	1546
EPS-DPBSP28CP-S	1546
EPS-DPBSP28-S	1546
EPS-DPBSP35CP-S	1546
EPS-DPBSP35-S	1546
EPS-DPBSP42-S	1546
EPS-DPBSP54-S	1546
EPS-FP10CP-S	1545
EPS-FP10-S	1545
EPS-HB15CP-S	1545
EPS-HB15-S	1545
EPS-HB22CP-S	1545
EPS-HB22-S	1545
EPS-HB28CP-S	1545
EPS-HB28-S	1545
EPS-HB35-S	1545
EPS-HB42CP-S	1545
EPS-HB42-S	1545
EPS-HB54-S	1545
EPS-MP10CP-S	1545
EPS-MP10-S	1545
EPS-MR15CP-S	1545
EPS-MR15D-S	1545
EPS-MR15-S	1545
EPS-MR22CP-S	1545
EPS-MR22D-S	1545
EPS-MR22-S	1545
EPS-MR28CP-S	1545
EPS-MR28-S	1545
EPS-MR35CP-S	1545
EPS-MR35D-S	1545
EPS-MR35-S	1545
EPS-MR42CP-S	1545
EPS-MR42-S	1545
EPS-MR54CP-S	1545
EPS-MR54D-S	1545
EPS-MR54-S	1545
EPS-MR67-S	1545
EPS-MR76-S	1545
EPS-MRBSP22-S	1546
EPS-MRBSP28-S	1546
EPS-MRBSP35CP-S	1546
EPS-MRBSP35D-S	1546
EPS-MRBSP35-S	1546
EPS-MRBSP54D-S	1546
EPS-MRBSP67-S	1546
EPS-MRBSP76-S	1546
EPS-SO15CP-S	1545
EPS-SO15-S	1545
EPS-SO22CP-S	1545
EPS-SO22-S	1545
EPS-SO28CP-S	1545
EPS-SO28-S	1545
EPS-SO35CP-S	1545
EPS-SO35-S	1545
EPS-SO42CP-S	1545
EPS-SO42-S	1545
EPS-SO54CP-S	1545
EPS-SO54-S	1545
EPS-SOPB12-S	1545
EPS-SOPB15CP-S	1545
EPS-SOPB15-S	1545
EPS-SOPB22CP-S	1545
EPS-SOPB22-S	1545
EPS-SOPB28CP-S	1545
EPS-SOPB28-S	1545
EPS-SOPB35CP-S	1545
EPS-SOPB35-S	1545
ER99.06.02	1067
ER99.06.03	1067
ERA21NFC	259
ERA21NFD	259
ERA31NFC	259
ERA31NFD	259
ERA32NFC	259
ERA32NFD	259
ERA41NFC	259
ERA41NFD	259
ERA51NFC	259
ERA51NFD	259
ERA53NFC	259
ERA53NFD	259
ES12	1208
ES14	1208
ES316	1208
ES34	1208
ES38	1208
ES4-L-06-WD	152
ES4-L-08-WD	152
ES4-L-10-WD	152
ES4-L-12-WD	152
ES4-L-15-WD	152
ES4-L-18-WD	152
ES4-L-22-WD	152
ES4-L-28-WD	152
ES4-L-35-WD	152
ES4-L-42-WD	152
ES4-S-06-WD	152
ES4-S-08-WD	152
ES4-S-10-WD	152
ES4-S-12-WD	152
ES4-S-14-WD	152
ES4-S-16-WD	152
ES4-S-20-WD	152
ES4-S-25-WD	152
ES4-S-30-WD	152
ES4-S-38-WD	152
ES516	1208
ESE11NFA	259
ESE11NFB	259
ESE11NFC	259
ESE11NFD	259
ESE12NFA	259
ESE12NFB	259
ESE12NFC	259
ESE12NFD	259
ESE21NFA	259
ESE21NFB	259
ESE21NFC	259
ESE21NFD	259
ESE22NFA	259
ESE22NFB	259
ESE22NFC	259
ESE22NFD	259
ESI-1	1113
ESI-112	1113
ESI-114	1113
ESI-12	1113
ESI-2	1113
ESI-34	1113
ESR12	631
ESR14	631
ESR18	631
ESR38	631
ESRI-1	1113
ESRI-12	1113
ESRI-2	1113
ESRI-34	1113
ESV10L	127
ESV-10L-FT	155
ESV10S	127
ESV-10S-FT	155
ESV12L	127

Code	Page
ESV-12L-FT	**155**
ESV12S	**127**
ESV-12S-FT	**155**
ESV14S	**127**
ESV-14S-FT	**155**
ESV15L	**127**
ESV-15L-FT	**155**
ESV16S	**127**
ESV-16S-FT	**155**
ESV18L	**127**
ESV-18L-FT	**155**
ESV-20L-FT	**155**
ESV20S	**127**
ESV-20S-FT	**155**
ESV22L	**127**
ESV25S	**127**
ESV-25S-FT	**155**
ESV28L	**127**
ESV-28L-FT	**155**
ESV30S	**127**
ESV35L	**127**
ESV38S	**127**
ESV42L	**127**
ESV6L	**127**
ESV-6L-FT	**155**
ESV-6S-FT	**155**
ESV8L	**127**
ESV-8L-FT	**155**
ESV8S	**127**
ESV-8S-FT	**155**
ET-1	**1181**
ET-112	**1181**
ET-114	**1181**
ET-12	**1181**
ET-14	**1181**
ET-18	**1181**
ET-2	**1181**
ET-212	**1181**
ET-3	**1181**
ET-34	**1181**
ET-38	**1181**
ET-38-5	**1107**
ET-4	**1181**
ET-DKOL-06	**161**
ET-DKOL-08	**161**
ET-DKOL-10	**161**
ET-DKOL-12	**161**
ET-DKOL-15	**161**
ET-DKOL-18	**161**
ET-DKOL-22	**161**
ET-DKOL-28	**161**
ET-DKOL-35	**161**
ET-DKOL-42	**161**
ET-DKOS-06	**161**
ET-DKOS-08	**161**
ET-DKOS-10	**161**
ET-DKOS-12	**161**
ET-DKOS-14	**161**
ET-DKOS-16	**161**
ET-DKOS-20	**161**
ET-DKOS-25	**161**
ET-DKOS-30	**161**
ET-DKOS-38	**161**
ETSD 10 L	**134**
ETSD 10 S	**134**
ETSD 12 L	**134**
ETSD 12 S	**134**
ETSD 14 S	**134**
ETSD 15 L	**134**
ETSD 16 S	**134**
ETSD 18 L	**134**
ETSD 20 S	**134**
ETSD 22 L	**134**
ETSD 25 S	**134**
ETSD 28 L	**134**
ETSD 30 S	**134**
ETSD 35 L	**134**
ETSD 38 S	**134**
ETSD 42 L	**134**
ETSD 6 L	**134**
ETSD 6 S	**134**
ETSD 8 L	**134**
ETSD 8 S	**134**
ETVD10L	**129**
ETVD10S	**129**
ETVD12L	**129**
ETVD12S	**129**
ETVD14S	**129**
ETVD15L	**129**
ETVD16S	**129**
ETVD18L	**129**
ETVD20S	**129**
ETVD22L	**129**
ETVD25S	**129**
ETVD28L	**129**
ETVD30S	**129**
ETVD35L	**129**
ETVD38S	**129**
ETVD42L	**129**
ETVD6L	**129**
ETVD6S	**129**
ETVD8L	**129**
ETVD8S	**129**
EV-12	**982**
EV-14	**982**
EV-18	**982**
EV-38	**982**
EV-DKOL-06	**152**
EV-DKOL-08	**152**
EV-DKOL-10	**152**
EV-DKOL-12	**152**
EV-DKOL-15	**152**
EV-DKOL-18	**152**
EV-DKOL-22	**152**
EV-DKOL-28	**152**
EV-DKOL-35	**152**
EV-DKOL-42	**152**
EVGE-10L-14MEO	**148**
EVGE-10L-4EO	**148**
EVGE-10L-6EO	**148**
EVGE-10L-8EO	**148**
EVGE-10S-16MEO	**148**
EVGE-10S-4EO	**148**
EVGE-10S-6EO	**148**
EVGE-10S-8EO	**148**
EVGE-12L-4EO	**148**
EVGE-12L-6EO	**148**
EVGE-12L-8EO	**148**
EVGE-12S-18MEO	**148**
EVGE-12S-4EO	**148**
EVGE-12S-6EO	**148**
EVGE-12S-8EO	**148**
EVGE-14S-20MEO	**148**
EVGE-14S-8EO	**148**
EVGE-15L-18MEO	**148**
EVGE-15L-6EO	**148**
EVGE-15L-8EO	**148**
EVGE-16S-12EO	**148**
EVGE-16S-22MEO	**148**
EVGE-16S-6EO	**148**
EVGE-16S-8EO	**148**
EVGE-18L-12EO	**148**
EVGE-18L-22MEO	**148**
EVGE-18L-6EO	**148**
EVGE-18L-8EO	**148**
EVGE-20S-12EO	**148**
EVGE-20S-27MEO	**148**
EVGE-20S-8EO	**148**
EVGE-22L-12EO	**148**
EVGE-22L-26MEO	**148**
EVGE-22L-6EO	**148**
EVGE-22L-8EO	**148**
EVGE-25S-12EO	**148**
EVGE-25S-16EO	**148**
EVGE-28L-12EO	**148**
EVGE-28L-16EO	**148**
EVGE-28L-33MEO	**148**
EVGE-30S-20EO	**148**
EVGE-30S-42MEO	**148**
EVGE-35L-20EO	**148**
EVGE-35L-42MEO	**148**
EVGE-38S-24EO	**148**
EVGE-38S-48MEO	**148**
EVGE-42L-24EO	**148**
EVGE-42L-48MEO	**148**
EVGE-6L-10MEO	**148**
EVGE-6L-2EO	**148**
EVGE-6S-12MEO	**148**
EVGE-6S-2EO	**148**
EVGE-6S-4EO	**148**
EVGE-8L-12MEO	**148**
EVGE-8L-4EO	**148**
EVGE-8L-6EO	**148**
EVGE-8S-14MEO	**148**
EVGE-8S-4EO	**148**
EVGE-8S-6EO	**148**
EVL-10L	**149**
EVL-10S	**149**
EVL-12L	**149**
EVL-12S	**149**
EVL-14S	**149**
EVL-15L	**149**
EVL-16S	**149**
EVL-18L	**149**
EVL-20S	**149**
EVL-22L	**149**
EVL-25S	**149**
EVL-28L	**149**
EVL-30S	**149**
EVL-35L	**149**
EVL-38S	**149**
EVL-42L	**149**
EVL6L	**149**
EVL6S	**149**
EVL8L	**149**
EVL8S	**149**
EVMM-12	**982**
EVMM-14	**982**
EVMM-18	**982**
EVMM-38	**982**
EVT-10L	**148**
EVT-10S	**148**
EVT-12L	**148**
EVT-12S	**148**
EVT-14S	**148**
EVT-15L	**148**
EVT-16S	**148**
EVT-18L	**148**
EVT-20S	**148**
EVT-22L	**148**
EVT-25S	**148**
EVT-28L	**148**
EVT-30S	**148**
EVT-35L	**148**
EVT-38S	**148**
EVT-42L	**148**
EVT-6L	**148**
EVT-6S	**148**
EVT-8L	**148**
EVT-8S	**148**
EVW-10L	**151**
EVW-10S	**151**
EVW-12L	**151**
EVW-12S	**151**
EVW-14S	**151**
EVW-15L	**151**
EVW-16S	**151**
EVW-18L	**151**
EVW-20S	**151**
EVW-22L	**151**
EVW-25S	**151**
EVW-28L	**151**
EVW-30S	**151**
EVW-35L	**151**
EVW-38S	**151**
EVW-42L	**151**
EVW-6L	**151**
EVW-6S	**151**
EVW-8L	**151**
EVW-8S	**151**
EW-DKOL-06	**161**
EW-DKOL-08	**161**
EW-DKOL-10	**161**
EW-DKOL-12	**161**
EW-DKOL-15	**161**
EW-DKOL-18	**161**
EW-DKOL-22	**161**
EW-DKOL-28	**161**
EW-DKOL-35	**161**
EW-DKOL-42	**161**
EW-DKOS-06	**161**
EW-DKOS-08	**161**
EW-DKOS-10	**161**
EW-DKOS-12	**161**
EW-DKOS-14	**161**
EW-DKOS-16	**161**
EW-DKOS-20	**161**
EW-DKOS-25	**161**
EW-DKOS-30	**161**
EW-DKOS-38	**161**
EWSD 10 L	**134**
EWSD 10 S	**134**
EWSD 12 L	**134**
EWSD 12 S	**134**
EWSD 14 S	**134**
EWSD 15 L	**134**
EWSD 16 S	**134**
EWSD 18 L	**134**
EWSD 20 S	**134**
EWSD 22 L	**134**
EWSD 25 S	**134**
EWSD 28 L	**134**
EWSD 30 S	**134**
EWSD 35 L	**134**
EWSD 38 S	**134**
EWSD 42 L	**134**
EWSD 45 10 L	**134**
EWSD 45 10 S	**134**
EWSD 45 12 L	**134**
EWSD 45 12 S	**134**
EWSD 45 15 L	**134**
EWSD 45 16 S	**134**
EWSD 45 18 L	**134**
EWSD 45 20 S	**134**
EWSD 45 22 L	**134**
EWSD 45 25 S	**134**
EWSD 45 28 L	**134**
EWSD 45 30 S	**134**
EWSD 45 35 L	**134**
EWSD 45 38 S	**134**
EWSD 45 42 L	**134**
EWSD 45 6 L	**134**
EWSD 45 6 S	**134**
EWSD 45 8 L	**134**
EWSD 45 8 S	**134**
EWSD 6 L	**134**
EWSD 6 S	**134**
EWSD 8 L	**134**
EWSD 8 S	**134**
EWVD10L	**129**
EWVD10S	**129**
EWVD12L	**129**
EWVD12S	**129**
EWVD14S	**129**
EWVD15L	**129**
EWVD16S	**129**
EWVD18L	**129**
EWVD20S	**129**
EWVD22L	**129**
EWVD25S	**129**
EWVD28L	**129**
EWVD30S	**129**
EWVD35L	**129**
EWVD38S	**129**
EWVD42L	**129**
EWVD6L	**129**
EWVD6S	**129**
EWVD8L	**129**
EWVD8S	**129**
EX12	**1208**

Code	Page
EX14	1208
EX516	1208
EY53-112-ABS	1097
EY53-112-UPVC	1109
EY53-114-ABS	1097
EY53-114-UPVC	1109
EY53-12-ABS	1097
EY53-12-UPVC	1109
EY53-1-ABS	1097
EY53-1-UPVC	1109
EY53-212-ABS	1097
EY53-212-UPVC	1109
EY53-2-ABS	1097
EY53-2-UPVC	1109
EY53-34-ABS	1097
EY53-34-UPVC	1109
EY53-3-ABS	1097
EY53-3-UPVC	1109
EY53-4-ABS	1097
EY53-4-UPVC	1109
EY53-5-UPVC	1109
EY53-6-ABS	1097
EY53-6-UPVC	1109
EY53-8-UPVC	1109
F	
F 100	511
F 125	511
F 160	511
F 200	511
F 32	511
F 40	511
F 50	511
F 61 100	511
F 61 125	511
F 61 32	511
F 61 40	511
F 61 50	511
F 61 80	511
F 63	511
F 63 100	511
F 63 125	511
F 63 32	511
F 63 40	511
F 63 50	511
F 63 63	511
F 63 80	511
F 80	511
F07-100-A3TG	690
F07-200-A3TG	690
F10	141
F112-AU	1468
F112-AU-NPT	1468
F112-BR	1471
F112-BR-NPT	1471
F112-PP	1470
F112-PP-NPT	1470
F112-SS	1469
F112-SS-NPT	1469
F114-AU	1468
F114-AU-NPT	1468
F114-BR	1471
F114-BR-NPT	1471
F114-PP	1470
F114-SS	1469

Code	Page
F114-SS-NPT	1469
F12	141
F12/34-PP-NPT	1470
F12-AU	1468
F12-AU-NPT	1468
F12-BR	1471
F12-BR-NPT	1471
F12-PP	1470
F12-SS	1469
F12-SS-NPT	1469
F133-14-110	1040
F133-14-230	1040
F133-14-24	1040
F133-18-110	1040
F133-18-230	1040
F133-18-24	1040
F133-38-110	1040
F133-38-230	1040
F133-38-24	1040
F16	141
F180-1-110	1040
F180-112-110	1040
F180-112-230	1040
F180-112-24	1040
F180-12-110	1040
F180-12-230	1040
F180-12-24	1040
F180-1-230	1040
F180-1-24	1040
F180-2-110	1040
F180-2-230	1040
F180-2-24	1040
F180-34-110	1040
F180-34-230	1040
F180-34-24	1040
F180-38-110	1040
F180-38-230	1040
F180-38-24	1040
F1-AU	1468
F1-AU-NPT	1468
F1-BR	1471
F1-BR-NPT	1471
F1-PP	1470
F1-PP-NPT	1470
F1-SS	1469
F1-SS-NPT	1469
F20	141
F212-AU	1468
F212-AU-NPT	1468
F212-BR	1471
F212-BR-NPT	1471
F212-SS	1469
F212-SS-NPT	1469
F24	141
F280-1-110	1040
F280-112-230	1040
F280-112-24	1040
F280-12-110	1040
F280-12-230	1040
F280-12-24	1040
F280-1-230	1040
F280-1-24	1040
F280-2-110	1040
F280-2-230	1040

Code	Page
F280-2-24	1040
F280-34-110	1040
F280-34-230	1040
F280-34-24	1040
F280-38-110	1040
F280-38-230	1040
F280-38-24	1040
F2-AU	1468
F2-AU-NPT	1468
F2-BR	1471
F2-BR-NPT	1471
F2-PP	1470
F2-PP-NPT	1470
F2SC-04	16
F2SC-06	16
F2SC-08	16
F2SC-12	16
F2SC-16	16
F2-SS	1469
F2-SS-NPT	1469
F333-14-110	1041
F333-14-230	1041
F333-14-24	1041
F333-18-110	1041
F333-18-230	1041
F333-18-24	1041
F34-AU	1468
F34-AU-NPT	1468
F34-BR	1471
F34-PP	1470
F34-PP-NPT	1470
F34-SS	1469
F34-SS-NPT	1469
F39-100-A0TG	689
F39-200-M0MG	689
F39-200-M0TG	689
F3-AU	1468
F3-AU-NPT	1468
F3-BR	1471
F3-BR-NPT	1471
F3-PP	1470
F3-PP-NPT	1470
F3-SS	1469
F3-SS-NPT	1469
F4	141
F4-AU	1468
F4-AU-NPT	1468
F4-BR	1471
F4-BR-NPT	1471
F4-PP	1470
F4-PP-NPT	1470
F4-SS	1469
F4-SS-NPT	1469
F5	141
F6	141
F64G-NNN-AD3	684
F64G-NNN-MD3	684
F64H-3GD-MD0	684
F64H-4GD-MD0	684
F68G-NNN-AR3	684
F68G-NNN-MR3	684
F68H-8GD-MU0	684
F6-AU	1468
F6-AU-NPT	1468

Code	Page
F6-BR	1471
F8	141
F82C-2GD-AP0	687
F82C-2GD-QP0	687
F82G-2GN-AP3	687
F82G-2GN-QP3	687
F84C-3GD-AP0	687
F84C-3GD-QP0	687
F84C-4GD-AP0	687
F84C-4GD-QP0	687
F84G-3GN-AP3	687
F84G-3GN-QP3	687
F84G-4GN-AP3	687
F84G-4GN-QP3	687
FA13A13ISPN	355
FA17A17ISPN	355
FASA150-110-UPVC	1105
FASA150-25-UPVC	1105
FASA150-32-UPVC	1105
FASA150-40-UPVC	1105
FASA150-50-UPVC	1105
FASA150-63-UPVC	1105
FASA150-90-UPVC	1105
FASA150HT2	1492
FB09B	1519
FB13B	1519
FB13H	1519
FB16B	1519
FB19B	1519
FB19H	1519
FBP1	1208
FBP12	1208
FBP14	1208
FBP18	1208
FBP34	1208
FBP38	1208
FBSOTD-10	1387
FBSOTD-2	1387
FBSOTD-3	1387
FBSOTD-300	1387
FBSOTD-4	1387
FBSOTD-612	1387
FBSOTD-658	1387
FBSOTD-8	1387
FBSOTE-1	1387
FBSOTE-10	1387
FBSOTE-112	1387
FBSOTE-114	1387
FBSOTE-12	1387
FBSOTE-2	1387
FBSOTE-212	1387
FBSOTE-3	1387
FBSOTE-34	1387
FBSOTE-4	1387
FBSOTE-5	1387
FBSOTE-612	1387
FBSOTE-658	1387
FBSOTE-8	1387
FBSTD-1	1387
FBSTD-114	1387
FBSTD-12	1387
FBSTD-2	1387
FBSTD-212	1387
FBSTD-3	1387

Code	Page
FBSTD-34	1387
FBSTD-4	1387
FBSTD-6	1387
FBSTE-1	1387
FBSTE-112	1387
FBSTE-114	1387
FBSTE-12	1387
FBSTE-2	1387
FBSTE-212	1387
FBSTE-3	1387
FBSTE-34	1387
FBSTE-4	1387
FBSTE-5	1387
FBSTE-6	1387
FBT	1519
FBT-1000-1000N	169
FBT-1000-750N	169
FBT-10-250N	175
FBT-12-250N	175
FBT-12-375N	175
FBT-125-125N	169
FBT-16-500N	175
FBT-250-125N	169
FBT-250-250N	169
FBT-375-250N	169
FBT-375-375N	169
FBT-375-500N	169
FBT-500-250N	169
FBT-500-375N	169
FBT-500-500N	169
FBT-6-125N	175
FBT-6-250N	175
FBT-625-500N	169
FBT-750-750N	169
FBT-8-125N	175
FBT-8-250N	175
FBU-112	1113
FBU-112-ABS	1098
FBU-114-ABS	1098
FBU-12-ABS	1098
FBU-1-ABS	1098
FBU-2-ABS	1098
FBU-34-ABS	1098
FC04	355
FC10	1174
FC-1000-1000N	167
FC-1000-750N	167
FC-10-125RT	174
FC-10-250N	174
FC-10-250RG	174
FC-10-250RT	174
FC-10-375N	174
FC-10-375RG	174
FC-10-375RT	174
FC-10-500N	174
FC-10-500RG	174
FC-10-500RT	174
FC10-8	141
FC12-12	141
FC-12-125RT	174
FC-12-250N	174
FC-12-250RG	174
FC-12-250RT	174
FC-12-375N	174

Code	Page
FC-12-375RG	174
FC-12-375RT	174
FC-12-500N	174
FC-12-500RG	174
FC-12-500RT	174
FC-125-125N	167
FC-125-250N	167
FC-12-750RT	174
FC13	1174
FC14-12	141
FC-15-375RT	174
FC-15-500N	174
FC-15-500RT	174
FC16-16	141
FC-16-500N	174
FC17	1174
FC-187-125N	167
FC20-20	141
FC-20-500N	174
FC-20-500RG	174
FC-20-500RT	174
FC-20-750N	174
FC-20-750RT	174
FC21	1174
FC-22-1000N	174
FC-22-1000RT	174
FC-22-500RG	174
FC-22-750N	174
FC-22-750RT	174
FC24-24	141
FC-250-125N	167
FC-250-125RT	167
FC-250-250N	167
FC-250-250RG	167
FC-250-250RT	167
FC-250-375N	167
FC-250-375RG	167
FC-250-375RT	167
FC-250-500N	167
FC-250-500RG	167
FC-250-500RT	167
FC-25-1000N	174
FC-25-1000RT	174
FC-25-750N	174
FC-25-750RT	174
FC-312-125N	167
FC-312-250N	167
FC-312-250RG	167
FC-312-375N	167
FC-312-500RG	167
FC-3-125N	174
FC-3-125RT	174
FC-3-250N	174
FC-3-250RG	174
FC-375-125N	167
FC-375-250N	167
FC-375-250RG	167
FC-375-250RT	167
FC-375-375N	167
FC-375-375RG	167
FC-375-375RT	167
FC-375-500N	167
FC-375-500RG	167
FC-375-500RT	167
FC-375-750N	167
FC-4-125N	174
FC4-4	141
FC-500-250N	167
FC-500-250RT	167
FC-500-375N	167
FC-500-375RG	167
FC-500-375RT	167
FC-500-500N	167
FC-500-500RG	167
FC-500-500RT	167
FC-500-750N	167
FC-6-125N	174
FC-6-125RT	174
FC-6-250N	174
FC-6-250RG	174
FC-6-250RT	174
FC-625-375N	167
FC-625-500N	167
FC-625-750N	167
FC-6-375N	174
FC-6-375RG	174
FC-6-375RT	174
FC6-4	141
FC-6-500N	174
FC-6-500RG	174
FC-6-500RT	174
FC6-6	141
FC6-8	141
FC-750-500N	167
FC-750-750N	167
FC-8-125N	174
FC-8-125RT	174
FC-8-250N	174
FC-8-250RG	174
FC-8-250RT	174
FC-8-375N	174
FC-8-375RG	174
FC-8-375RT	174
FC8-4	141
FC-8-500N	174
FC-8-500RG	174
FC-8-500RT	174
FC8-6	141
FC-875-750N	167
FC8-8	141
FD10	1174
FD13	1174
FD17	1174
FD21	1174
FDHT2	1492
FDHT3	1492
FDHT4	1492
FDHT5	1492
FDHT6	1492
FE10	1174
FE-1000-1000N	169
FE-1000-750N	169
FE101	355
FE-10-125N	176
FE-10-250N	176
FE-12-250N	176
FE-12-375N	176
FE-12-500N	176
FE-125-125N	169
FE-125-250N	169
FE13	1174
FE-16-500N	176
FE17	1174
FE-187-125N	169
FE21	1174
FE-250-125N	169
FE-250-250N	169
FE-250-375N	169
FE-250-500N	169
FE-312-125N	169
FE-312-250N	169
FE-375-125N	169
FE-375-250N	169
FE-375-375N	169
FE-375-500N	169
FE-500-250N	169
FE-500-375N	169
FE-500-500N	169
FE-6-125N	176
FE-6-250N	176
FE-625-375N	169
FE-625-500N	169
FE-6-500N	176
FE-750-500N	169
FE-750-750N	169
FE-8-250N	176
FE-875-750N	169
FEHT2	1492
FEHT3	1492
FEHT4	1492
FET14-38	1144
FET14-516	1144
FET38-12	1144
FET38-38	1144
FF-10	178
FF-1000	172
FF10-CS-M5M	740
FF10-N-M5M	740
FF10-S-M5M	740
FF10-WS-M5M	740
FF10-WS-M5M-FDA	740
FF-12	178
FF-125	172
FF13267	111
FF13268	111
FF13269	111
FF13270	111
FF13271	111
FF13272	111
FF13273	111
FF13570	111
FF13571	111
FF-14	178
FF-15	178
FF15-CS	740
FF15-N	740
FF15-S	740
FF15-WS	740
FF15-WS-FDA	740
FF15X-CS	740
FF15X-N	740
FF15X-S	740
FF15X-WS	740
FF15X-WS-FDA	740
FF-16	178
FF-18	178
FF-187	172
FF-20	178
FF20-CS	741
FF20-N	741
FF20-S	741
FF20-WS	741
FF20-WS-FDA	741
FF20X-CS	741
FF20X-N	741
FF20X-S	741
FF20X-WS	741
FF20X-WS-FDA	741
FF-22	178
FF-25	178
FF-250	172
FF2510	311
FF2516	311
FF2520	311
FF2526	311
FF25-CS	741
FF25-N	741
FF25-S	741
FF25-WS	741
FF25-WS-FDA	741
FF-3	178
FF30-112-ABS	1099
FF30-112-UPVC	1111
FF30-114-ABS	1099
FF30-114-UPVC	1111
FF30-12-ABS	1099
FF30-12-UPVC	1111
FF30-1-ABS	1099
FF30-1-UPVC	1111
FF30-2-ABS	1099
FF30-2-UPVC	1111
FF30-34-ABS	1099
FF30-34-UPVC	1111
FF30-3-ABS	1099
FF30-3-UPVC	1111
FF30-4-ABS	1099
FF30-4-UPVC	1111
FF30-CS	741
FF30-N	741
FF30-S	741
FF30-WS	741
FF30-WS-FDA	741
FF-312	172
FF31-2-ABS	1099
FF-375	172
FF-4	178
FF-500	172
FF-6	178
FF-625	172
FF-750	172
FF-8	178
FF-875	172
FFA02/02NP	1175
FFA04/04NP	1175
FFA06/06NP	1175
FFA08/08NP	1175
FFA12/12NP	1175
FFA16/16NP	1175
FFDC-04	292
FFDC-06	292
FFDC-08	292
FFDC-12	292
FFDC-16	292
FFDP-04	292
FFDP-06	292
FFDP-08	292
FFDP-12	292
FFDP-16	292
FFH02/03	1143
FFH02/04	1143
FFH02/05	1143
FFH02/06	1143
FFH04/03	1143
FFH04/04	1143
FFH04/05	1143
FFH04/06	1143
FFH06/04	1143
FFH06/05	1143
FFH06/06	1143
FFH06/08	1143
FFH08/04	1143
FFH08/05	1143
FFH08/06	1143
FFH08/08	1143
FFH08/10	1143
FFH08/12	1143
FFH08/16	1143
FFILT.EL	1627
FFILT.ELW	1627
FFILT.KIT	1627
FFILT.KITW	1627
FFR04/02NP	1176
FFR06/04NP	1176
FFR08/04NP	1176
FFR08/06NP	1176
FFR12/04NP	1176
FFR12/06NP	1176
FFR12/08NP	1176
FFR16/08NP	1176
FFR16/12NP	1176
FFTA-50-112-UPVC	1107
FG4E	1654
FG6E	1654
FGB-1	1672
FGR-1-18	280
FGR-3-18	280
FGSG-10	48
FGSG-12	48
FGSG-14	48
FGSG-16	48
FGSG-20	48
FGSG-25	48
FGSG-32	48
FGSG-42	48
FGSG-50	48
FGSG-60	48
FH10/14FF	1143
FH10/18	1143
FH10/18FF	1143
FH10/316	1143

Code	Page
FH10/316FF	1143
FH13/14	1143
FH13/14FF	1143
FH13/14SS	1181
FH13/18	1143
FH13/316	1143
FH13/316FF	1143
FH13/38	1143
FH13/38FF	1143
FH13/516	1143
FH13/516FF	1143
FH17/12	1143
FH17/12FF	1143
FH17/14	1143
FH17/14FF	1143
FH17/38	1143
FH17/38FF	1143
FH17/38SS	1181
FH17/516	1143
FH17/516FF	1143
FH21/12	1143
FH21/12FF	1143
FH21/12SS	1181
FH21/14	1143
FH21/14FF	1143
FH21/38	1143
FH21/38FF	1143
FH21/516	1143
FH21/516FF	1143
FH21/58FF	1143
FH26/12	1143
FH26/12FF	1143
FH26/34	1143
FH26/34FF	1143
FH26/34SS	1181
FH26/58FF	1143
FH3001	24
FH3002	24
FH3003	24
FH3004	24
FH3005	24
FH3006	24
FH3007	24
FH3011	24
FH33/1	1143
FH33/12	1143
FH33/12FF	1143
FH33/19SS	1181
FH33/1FF	1143
FH33/34	1143
FH33/34FF	1143
FH33/58	1143
FH42/114	1143
FH42/114FF	1143
FH48/112	1143
FH48/112FF	1143
FH48/114	1143
FH48/38SS	1181
FH52/2	1143
FH52/2FF	1143
FH52/50SS	1181
FH6001	24
FH6002	24
FH6003	24
FH6004	24
FH6005	24
FH6006	24
FH6013	24
FH6044	24
FHA-1-ABS	1098
FHAFIFBSP2122	1493
FHAFIFBSP212212	1493
FHAFIFI212212	1493
FHAFIMBSP2122	1493
FHAFIMBSP212212	1493
FHAMIFBSP2122	1493
FHAMIFBSP212212	1493
FHAMIMBSP2122	1493
FHAMIMBSP212212	1493
FHAMIMI212212	1493
FHCC112FEMALE	1493
FHCC112MALE	1493
FHCC134FEMALE	1493
FHCC134MALE	1493
FHCC212	1493
FHCC212112	1493
FHCC212134	1493
FHCC2122	1493
FHCC212212	1493
FHCC2123	1493
FHCC212FEMALE	1493
FHCC212MALE	1493
FHCC234FEMALE	1493
FHCC2FEMALE	1493
FHCC2MALE	1493
FHCC3FEMALE	1493
FHCC3MALE	1493
FHCG	1493
FHDPVC1	1406
FHDPVC1-100	1406
FHDPVC112	1406
FHDPVC114	1406
FHDPVC12	1406
FHDPVC12-100	1406
FHDPVC14	1406
FHDPVC14-100	1406
FHDPVC2	1406
FHDPVC34	1406
FHDPVC34-100	1406
FHDPVC38	1406
FHDPVC38-100	1406
FHDPVC516	1406
FHDPVC516-100	1406
FHN1	1495
FHN1900	1466
FHN2500	1466
FHN34	1495
FHO1930	1466
FHO2530	1466
FHPC212	1493
FHRAAF19	1466
FHRAAF25	1466
FHRAAS19	1466
FHRAAS25	1466
FHRAMF19	1466
FHRAMF25	1466
FHRAMS19	1466
FHRAMS25	1466
FHROAF19	1466
FHROAF25	1466
FHROAS19	1466
FHROAS25	1466
FHROMF19	1466
FHROMF25	1466
FHROMS19	1466
FHROMS25	1466
FHSASASS2	1492
FHSCBMMF212	1493
FHSDBFFM212	1493
FHSESS2	1492
FHSNP16SS2	1492
FHSNP16SS3	1492
FHT10/13	1145
FHT10/17	1145
FHT12	1495
FHT12/17	1145
FHT12/21	1145
FHT1212	1495
FHT22	1495
FHT2212	1495
FHT32	1495
FHT6/10	1145
FHT6/13	1145
FHT7/10	1145
FHT7/13	1145
FHT8/13	1145
FHT9/13	1145
FHT9/17	1145
FHWT221210	1495
FHWT221215	1495
FHWT221220	1495
FHWT22125	1495
FIRE-FHB4518	1494
FIRE-FHB4518LA	1494
FIRE-FHB4523	1494
FIRE-FHB4523LA	1494
FIRE-FHB4530	1494
FIRE-FHB6418	1494
FIRE-FHB6418LA	1494
FIRE-FHB6423	1494
FIRE-FHB6423LA	1494
FIRE-FHB6430	1494
FIRE-FHB6430LA	1494
FIRE-FHC4518	1494
FIRE-FHC4518LA	1494
FIRE-FHC4523	1494
FIRE-FHC4523LA	1494
FIRE-FHC4530LA	1494
FIRE-FHC6418	1494
FIRE-FHC6418LA	1494
FIRE-FHC6423	1494
FIRE-FHC6423LA	1494
FIRE-FHC6430	1494
FIRE-FHC6430LA	1494
FIRE-FHQ4518	1495
FIRE-FHQ4518LA	1495
FIRE-FHQ4523	1495
FIRE-FHQ4523LA	1495
FIRE-FHQ4530LA	1495
FIRE-FHQ6418LA	1495
FIRE-FHQ6423	1495
FIRE-FHQ6423LA	1495
FIRE-FHQ6430	1495
FIRE-FHQ6430LA	1495
FIRE-FHR4518	1494
FIRE-FHR4518LA	1494
FIRE-FHR4523	1494
FIRE-FHR4523LA	1494
FIRE-FHR4530	1494
FIRE-FHR6418	1494
FIRE-FHR6418LA	1494
FIRE-FHR6423	1494
FIRE-FHR6423LA	1494
FIRE-FHR6430	1494
FIRE-FHR6430LA	1494
F-KA12FA	454
F-KA12LB	455
F-KA12SDB	455
F-KA12TC	454
F-KA20FA	454
F-KA20LB	455
F-KA20SDB	455
F-KA20TC	454
F-KA32LB	455
F-KA32SDB	455
F-KA32TC	454
F-KA40LB	455
F-KA40SDB	455
F-KA40TC	454
F-KA8FA	454
F-KA8LB	455
F-KA8SDB	455
F-KA8TC	454
F-KASS16FA	460
F-KASS16LB	460
F-KASS16LN	460
F-KASS16PLN	460
F-KASS16SDB	460
F-KASS16Y	460
F-KASS20FA	460
F-KASS20LB	460
F-KASS20LN	460
F-KASS20PLN	460
F-KASS20SDB	460
F-KASS20Y	460
F-KASS25PLN	460
F-KASS25Y	460
F-KF100CA	484
F-KF100CB	484
F-KF100CR	484
F-KF100FA	484
F-KF100FTC	484
F-KF100LB	484
F-KF125CA	484
F-KF125CB	484
F-KF125CR	484
F-KF125FA	484
F-KF125LB	484
F-KF125TF	484
F-KF125TM	484
F-KF160CA	484
F-KF160CB	484
F-KF160CR	484
F-KF160FTC	484
F-KF160LB	484
F-KF160TM	484
F-KF200CA	484
F-KF200CB	484
F-KF200CR	484
F-KF32CA	484
F-KF32CB	484
F-KF32CR	484
F-KF32FA	484
F-KF32FTC	484
F-KF32LB	484
F-KF32TF	484
F-KF32TM	484
F-KF40CA	484
F-KF40CB	484
F-KF40CR	484
F-KF40FA	484
F-KF40FTC	484
F-KF40LB	484
F-KF40TF	484
F-KF40TM	484
F-KF50CA	484
F-KF50CB	484
F-KF50CR	484
F-KF50FA	484
F-KF50FTC	484
F-KF50LB	484
F-KF63CA	484
F-KF63CB	484
F-KF63CR	484
F-KF63FA	484
F-KF63FTC	484
F-KF63LB	484
F-KF63TF	484
F-KF63TM	484
F-KF80CA	484
F-KF80CB	484
F-KF80CR	484
F-KF80FA	484
F-KF80FTC	484
F-KF80LB	484
FL1	762
FL111	252
FL112	252
FL2	762
FL211	252
FL212	252
FL3	762
FL311	252
FL312	252
FL4	762
FL5	762
FL6	762
FL64-608	683
FL64-628	683
FL8	762
FL9	762
FLEX-15	1091
FLEX-22	1091
FLGS-127	261
FLGS-127-10	261
FLGS-254	261
FLGS-254-10	261
FLGS-76	261
FLGS-76-10	261
FLH-3-1	36

Code	Page
FLH-3-1.1/2	36
FLH-3-1.1/4	36
FLH-3-1/2	36
FLH-3-2	36
FLH-3-3/4	36
FLH-6-1	36
FLH-6-1.1/2	36
FLH-6-1.1/4	36
FLH-6-1/2	36
FLH-6-2	36
FLH-6-3/4	36
FLP-06B	1407
FLP-08B	1407
FLP-10B	1407
FLP-12B	1407
FLS050SS	1552
FLS075SS	1552
FLS100SS	1552
FLS120SS	1552
FLS150SS	1552
FLS225SS	1552
FLS250SS	1552
FLS275SS	1552
FLS300SS	1552
FLS330SS	1552
FLS380SS	1552
FLS405SS	1552
FLT112	252
FLT121	252
FLT212	252
FLT221	252
FLT312	252
FLT321	252
FLTGS-127	261
FLTGS-127-10	261
FLTGS-254	261
FLTGS-254-10	261
FLTGS-76	261
FLTGS-76-10	261
FLV-1	1625
FLX15	882
FLX16	882
FLX17	882
FLX18	882
FLX19	882
FLX20	882
FLX21	882
FLX22	882
FLX24	882
FLX26	882
FLX27	882
FLX33	882
FLX36	882
FLX37	882
F-M04070U	455
F-M04070YE	455
F-M06100II	455
F-M06100U	455
F-M06100YE	455
F-M08125F	455
F-M08125II	455
F-M08125U	455
F-M08125YE	455
F-M10125F	455
F-M10125II	455
F-M10125U	455
F-M10125YI	484
F-M1025YE	455
F-M12125F	455
F-M12125II	455
F-M12125U	455
F-M12125YI	484
F-M16150F	485
F-M16150U	485
F-M16150YI	484
F-M20150F	485
F-M20150U	485
F-M20150YI	484
FM2-20-01-C	647
FM2-20-01-F	647
FM2-20-01-L	647
FM2-20-01-R	647
FM2-20-01-W	647
FM2-20-20UM	648
FM2-20-MB	648
FM2-20-N	648
FM2-21-01-C	647
FM2-30-02-C	647
FM2-30-02-F	647
FM2-30-02-L	647
FM2-30-02-R	647
FM2-30-02-W	647
FM2-30-20UM	648
FM2-30-MB	648
FM2-30-N	648
FM2-31-02-C	647
FM2-40-03-C	647
FM2-40-03-F	647
FM2-40-03-L	647
FM2-40-03-R	647
FM2-40-03-W	647
FM2-40-04-C	647
FM2-40-04-F	647
FM2-40-04-L	647
FM2-40-04-R	647
FM2-40-04-W	647
FM2-40-20UM	648
FM2-40-MB	648
FM2-40-N	648
FM2-41-03-C	647
FM2-41-04-C	647
FM2-50-06-C	647
FM2-50-06-F	647
FM2-50-06-L	647
FM2-50-06-R	647
FM2-50-06-W	647
FM2-50-10-C	647
FM2-50-10-F	647
FM2-50-10-L	647
FM2-50-10-R	647
FM2-50-10-W	647
FM2-50-20UM	648
FM2-50-MB	648
FM2-51-06-C	647
FM2-51-10-C	647
FM26122212	254
FM26222112	254
FM26223132	254
FM26223232	254
FM26322112	254
FM26322212	254
FM26332112	253
FM26332122	253
FM26332212	253
FM26332222	253
F-M27200U	485
F-M27200YI	484
FM2DDSV	220
F-M36200U	485
F-M36200YI	484
FM3DDSV	220
FM4	1626
FM-402-04-S	648
FMP01VG1	439
FMP02VG6	439
FMP03VL100	439
FMP04VL160	439
FMP06VG10	439
FMP06VL4	439
FMP07VG16	439
FMP07VL7	439
FMP08VG25	439
FMP08VL11	439
FMP09VG40	439
FMP09VL18	439
FMP10VG100	439
FMP10VL35	439
FMP11VG100	439
FMP11VL50	439
FMP12VG160	439
FMP12VL70	439
FMP13VG250	439
FMP14VG300	439
FMP15VG350	439
FMP15VL170	439
FMUM3KVMS08	248
FMUM3MVMS08	247
FMUT1KVMS08	248
FMUT1MVMS08	247
FN14	1208
FN18	1208
FN38	1208
FNF14	1208
FNF18	1208
FNF38	1208
FNP14	1208
FNP16HT112	1492
FNP16HT2	1492
FNP16HT212	1492
FNP16HT3	1492
FNP16HT4	1492
FNP16HT6	1492
FNP16HT8	1492
FNP18	1208
FNT14	1208
FNT516	1208
FO1/2-13	1420
FO1/4-6	1420
FO1/4-8	1420
FO1/8-6	1420
FO11/4-32	1420
FO3/4-16	1420
FO3/4-19	1420
FO3/8-10	1420
FO3/8-13	1420
FO3/8-6	1420
FO-500	1691
FON1/2-13	1421
FON1/4-6	1421
FON1/4-8	1421
FON1-25	1421
FON3/4-16	1421
FON3/4-19	1421
FON3/8-10	1421
FOOT150	1436
FOOT200	1436
FOOT250	1436
FOOT300	1436
FOOT400	1436
FOOT600	1436
FOR-1-18	280
FOR-3-18	280
FP1/2-10BX	1420
FP1/2-13BX	1420
FP11/2-40BX	1420
FP1-19BX	1420
FP1-25BX	1420
FP12M	626
FP25M	626
FP3/4-10BX	1420
FP3/4-13BX	1420
FP3/4-16BX	1420
FP3/4-19BX	1420
FP3/8-10BX	1420
FP3/8-13BX	1420
FP35M	626
FPB12B04CNFA03EX	257
FPB12B04CNFB03EX	257
FPB12B04CNFC03EX	257
FPB12B04CNFD03EX	257
FPB13B06CNFA03EX	257
FPB13B06CNFB03EX	257
FPB13B06CNFC03EX	257
FPB13B06CNFD03EX	257
FPB21B08CNFA03EX	257
FPB21B08CNFB03EX	257
FPB21B08CNFC03EX	257
FPB21B08CNFD03EX	257
FPB31B10CNFA03EX	257
FPB31B10CNFB03EX	257
FPB31B10CNFC03EX	257
FPB31B10CNFD03EX	257
FPB33B12CNFA03EX	257
FPB33B12CNFB03EX	257
FPB33B12CNFC03EX	257
FPB33B12CNFD03EX	257
FPB34B12CNFA03EX	257
FPB34B12CNFB03EX	257
FPB34B12CNFC03EX	257
FPB34B12CNFD03EX	257
FPBLTD-100	1387
FPBLTD-15	1387
FPBLTD-150	1387
FPBLTD-20	1387
FPBLTD-200	1387
FPBLTD-25	1387
FPBLTD-250	1387
FPBLTD-300	1387
FPBLTD-32	1387
FPBLTD-50	1387
FPBLTD-65	1387
FPBLTD-80	1387
FPBLTE-100	1387
FPBLTE-125	1387
FPBLTE-15	1387
FPBLTE-150	1387
FPBLTE-200	1387
FPBLTE-25	1387
FPBLTE-250	1387
FPBLTE-300	1387
FPBLTE-32	1387
FPBLTE-40	1387
FPBLTE-50	1387
FPBLTE-65	1387
FPBLTE-80	1387
FPE11B06BNFC31XX	259
FPE12B06BNFC31XX	259
FPE21B10BNFC31XX	259
FPE22B10BNFC31XX	259
FPE31B12BNFC31XX	259
FPE32B12BNFC31XX	259
FPE41B12BNFC31XX	259
FPE42B12BNFC31XX	259
FPG20B06DNFC03CX	258
FPG20B06DNFD03CX	258
FPG21B06DNFC03CX	258
FPG21B06DNFD03CX	258
FPG22B08DNFC03CX	258
FPG22B08DNFD03CX	258
FPG31B10DNFC03CX	258
FPG31B10DNFD03CX	258
FPL.1E	437
FPL.2E	437
FPL1E-1	437
FPL1E-112	437
FPL1E-114	437
FPL1E-12	437
FPL1E-2	437
FPL1E-34	437
FPM21B04CNFA03XX	258
FPM21B04CNFB03XX	258
FPM21B04CNFC03XX	258
FPM21B04CNFD03XX	258
FPM22B06CNFA03XX	258
FPM22B06CNFB03XX	258
FPM22B06CNFC03XX	258
FPM22B06CNFD03XX	258
FPM22B08CNFA03XX	258
FPM22B08CNFB03XX	258
FPM22B08CNFC03XX	258
FPM22B08CNFD03XX	258
FPN1/2-10	1421
FPN1/2-13	1421
FPN1/2-8	1421
FPN16-110-UPVC	1105
FPN16-20-UPVC	1105
FPN16-25-UPVC	1105
FPN16-32-UPVC	1105
FPN16-40-UPVC	1105
FPN16-50-UPVC	1105

Code	Page
FPN16-63-UPVC	1105
FPN16-75-UPVC	1105
FPN16-90-UPVC	1105
FPN3/4-10	1421
FPN3/4-13	1421
FPN3/4-16	1421
FPN3/4-19	1421
FPN3/8-10	1421
FPSLEEVE-017	46
FPSLEEVE-020	46
FPSLEEVE-023	46
FPSLEEVE-027	46
FPSLEEVE-031	46
FPSLEEVE-036	46
FPSLEEVE-040	46
FPSLEEVE-044	46
FPSLEEVE-055	46
FPSLEEVE-060	46
FPSLEEVE-066	46
FPSLEEVE-073	46
FPSLEEVE-093	46
FPSLEEVE-112	46
FPSOTD-100	1387
FPSOTD-125	1387
FPSOTD-150	1387
FPSOTD-200	1387
FPSOTD-250	1387
FPSOTD-300	1387
FPSOTD-32	1387
FPSOTD-50	1387
FPSOTD-65	1387
FPSOTD-80	1387
FPSOTE-100	1387
FPSOTE-125	1387
FPSOTE-15	1387
FPSOTE-150	1387
FPSOTE-20	1387
FPSOTE-200	1387
FPSOTE-25	1387
FPSOTE-250	1387
FPSOTE-300	1387
FPSOTE-32	1387
FPSOTE-40	1387
FPSOTE-50	1387
FPSOTE-65	1387
FPSOTE-80	1387
FQ100	1458
FQSD1-10	1434
FQSD112-10	1434
FQSD112-5	1434
FQSD114-10	1434
FQSD114-5	1434
FQSD1-5	1434
FQSD2-10	1434
FQSD212-10	1434
FQSD212-5	1434
FQSD2-5	1434
FQSD3-10	1434
FQSD3-5	1434
FQSD4-10	1434
FQSD4-5	1434
FR79-03	16
FR79-04	16
FR79-05	16
FR79-06	16
FR79-08	16
FR79-12	16
FRA21B04BNFC32WX	259
FRA21B04BNFD32WX	259
FRA31B06BNFC32WX	259
FRA31B06BNFD32WX	259
FRA32B08BNFC32WX	259
FRA32B08BNFD32WX	259
FRA41B10BNFC32WX	259
FRA41B10BNFD32WX	259
FRA51B12BNFC32WX	259
FRA51B12BNFD32WX	259
FRA53B16BNFC32WX	259
FRA53B16BNFD32WX	259
FRB-12-ABS	1098
FRB-34-ABS	1098
FRB-BSP-1/2EPDM	1388
FRB-BSP-1/2NBR	1388
FRB-BSP-112EPDM	1388
FRB-BSP-112NBR	1388
FRB-BSP-114EPDM	1388
FRB-BSP-114NBR	1388
FRB-BSP-1EPDM	1388
FRB-BSP-1NBR	1388
FRB-BSP-212EPDM	1388
FRB-BSP-212NBR	1388
FRB-BSP-2EPDM	1388
FRB-BSP-2NBR	1388
FRB-BSP-3/4EPDM	1388
FRB-BSP-3/4NBR	1388
FRB-BSP-3EPDM	1388
FRB-BSP-3NBR	1388
FRB-PN16-10EPDM	1388
FRB-PN16-10NBR	1388
FRB-PN16-112EPDM	1388
FRB-PN16-112NBR	1388
FRB-PN16-114EPDM	1388
FRB-PN16-114NBR	1388
FRB-PN16-12EPDM	1388
FRB-PN16-12NBR	1388
FRB-PN16-212EPDM	1388
FRB-PN16-212NBR	1388
FRB-PN16-2EPDM	1388
FRB-PN16-2NBR	1388
FRB-PN16-3EPDM	1388
FRB-PN16-3NBR	1388
FRB-PN16-4EPDM	1388
FRB-PN16-4NBR	1388
FRB-PN16-5EPDM	1388
FRB-PN16-5NBR	1388
FRB-PN16-6EPDM	1388
FRB-PN16-6NBR	1388
FRB-PN16-8EPDM	1388
FRB-PN16-8NBR	1388
FRDS-108A	199
FRDS-115A	199
FRDS-133A	199
FRDS-169A	199
FRDS-20A	199
FRDS-22A	199
FRDS-25A	199
FRDS-27A	199
FRDS-30A	199
FRDS-34A	199
FRDS-38A	199
FRDS-43A	199
FRDS-45A	199
FRDS-49A	199
FRDS-57A	199
FRDS-61A	199
FRDS-77A	199
FRDS-89A	199
FRDZ-115A	199
FRDZ-159A	199
FRDZ-169A	199
FRDZ-194A	199
FRDZ-220A	199
FRDZ-22A	199
FRDZ-25A	199
FRDZ-30A	199
FRDZ-34A	199
FRDZ-38A	199
FRDZ-43A	199
FRDZ-45A	199
FRDZ-49A	199
FRDZ-57A	199
FRDZ-61A	199
FRDZ-77A	199
FRDZ-89A	199
FRL-MX2-1/2-KIT	691
FRL-MX2-3/4-KIT	691
FRL-MX2-3/8-KIT	691
FRL-MX3-1-KIT	691
FRL-MX3-3/4-KIT	691
FR-MX2-1/2-KIT	691
FR-MX2-3/4-KIT	691
FR-MX2-3/8-KIT	691
FR-MX3-1-KIT	691
FR-MX3-3/4-KIT	691
FRS-1-12	1183
FRS-112-1	1183
FRS-112-114	1183
FRS-112-34	1183
FRS-1-14	1183
FRS-114-1	1183
FRS-114-12	1183
FRS-114-34	1183
FRS-12-14	1183
FRS-12-18	1183
FRS-12-38	1183
FRS-1-34	1183
FRS-1-38	1183
FRS-14-18	1183
FRS-2-1	1183
FRS-2-112	1183
FRS-2-114	1183
FRS-212-114	1183
FRS-212-2	1183
FRS-2-34	1183
FRS-3-114	1183
FRS-3-2	1183
FRS-3-212	1183
FRS-34-12	1183
FRS-34-14	1183
FRS-34-38	1183
FRS-38-14	1183
FRS-38-18	1183
FRS-4-2	1183
FRS-4-3	1183
FRT-1000-1000N	169
FRT-1000-750N	169
FRT-10-250N	175
FRT-12-250N	175
FRT-12-375N	175
FRT-125-125N	169
FRT-16-500N	175
FRT-250-125N	169
FRT-250-250N	169
FRT-375-250N	169
FRT-500-375N	169
FRT-500-500N	169
FRT-6-125N	175
FRT-6-250N	175
FRT-750-750N	169
FRT-8-125N	175
FRT-8-250N	175
FS-06-R	45
FS-06-R-15	45
FS-1	1185
FS-102-R	45
FS-102-R-15	45
FS-10-R	45
FS-10-R-15	45
FS-112	1185
FS-114	1185
FS-114-R	45
FS-114-R-15	45
FS-12	1185
FS-127-R	45
FS-127-R-15	45
FS-12-R	45
FS-12-R-15	45
FS-14	1185
FS-14-R	45
FS-14-R-15	45
FS-16-R	45
FS-16-R-15	45
FS-18	1185
FS-19-R	45
FS-19-R-15	45
FS-2	1185
FS-212	1185
FS-22-R	45
FS-22-R-15	45
FS-25-R	45
FS-25-R-15	45
FS-28-R	45
FS-28-R-15	45
FS-3	1185
FS-32-R	45
FS-32-R-15	45
FS-34	1185
FS-35-R	45
FS-35-R-15	45
FS-38	1185
FS-38-R	45
FS-38-R-15	45
FS-4	1185
FS-41-R	45
FS-41-R-15	45
FS-44-R	45
FS-44-R-15	45
FS-51-R	45
FS-51-R-15	45
FS-57-R	45
FS-57-R-15	45
FS-63-R	45
FS-63-R-15	45
FS-70-R	45
FS-70-R-15	45
FS-76-R	45
FS-76-R-15	45
FS-83-R	45
FS-83-R-15	45
FS-89-R	45
FS-89-R-15	45
FS-95-R	45
FS-95-R-15	45
FSC1-1	1207
FSC12-12	1207
FSC12-14	1207
FSC14-12	1207
FSC14-14	1207
FSC14-18	1207
FSC14-38	1207
FSC18-14	1207
FSC18-18	1207
FSC316-14	1207
FSC316-18	1207
FSC316-38	1207
FSC34-12	1207
FSC34-34	1207
FSC38-12	1207
FSC38-14	1207
FSC38-18	1207
FSC38-38	1207
FSC516-12	1207
FSC516-14	1207
FSC516-18	1207
FSC516-38	1207
FSE12-12	1208
FSE14-14	1208
FSE14-18	1208
FSE316-18	1208
FSE38-12	1208
FSE38-14	1208
FSE38-38	1208
FSE516-14	1208
FSFSA-112	1386
FSFSA-112-300	1386
FSFSA-12-300	1386
FSFSA-1-300	1386
FSFSA-2	1386
FSFSA-212	1386
FSFSA-2-300	1386
FSFSA-3	1386
FSFSA-34-300	1386
FSFSB-1	1386
FSFSB-112	1386
FSFSB-112-300	1386
FSFSB-114	1386
FSFSB-114-300	1386
FSFSB-12	1386
FSFSB-12-300	1386
FSFSB-1-300	1386

Code	Page
FSFSB-2	1386
FSFSB-212	1386
FSFSB-212-300	1386
FSFSB-2-300	1386
FSFSB-3	1386
FSFSB-3-300	1386
FSFSB-34	1386
FSFSB-34-300	1386
FSFSB-4	1386
FSFSB-4-300	1386
FSFSOA-1	1386
FSFSOA-112	1386
FSFSOA-114-300	1386
FSFSOA-12	1386
FSFSOA-2	1386
FSFSOA-2-300	1386
FSFSOA-3	1386
FSFSOA-34	1386
FSFSOA-34-300	1386
FSFSOA-4	1386
FSFSOA-4-300	1386
FSFSOB-1	1386
FSFSOB-112	1386
FSFSOB-112-300	1386
FSFSOB-114	1386
FSFSOB-12	1386
FSFSOB-12-300	1386
FSFSOB-2	1386
FSFSOB-212	1386
FSFSOB-212-300	1386
FSFSOB-2-300	1386
FSFSOB-3	1386
FSFSOB-3-300	1386
FSFSOB-34	1386
FSFSOB-4	1386
FSFSOB-4-300	1386
FSFWA-1	1386
FSFWA-112	1386
FSFWA-114	1386
FSFWA-2	1386
FSFWA-212	1386
FSFWA-212-300	1386
FSFWA-3	1386
FSFWA-3-300	1386
FSFWA-4	1386
FSFWA-4-300	1386
FSFWB-1	1386
FSFWB-112	1386
FSFWB-112-300	1386
FSFWB-114	1386
FSFWB-1-300	1386
FSFWB-2	1386
FSFWB-212	1386
FSFWB-212-300	1386
FSFWB-2-300	1386
FSFWB-3	1386
FSFWB-4	1386
FSFWB-4-300	1386
FSG-10	48
FSG-100	48
FSG-12	48
FSG-130	48
FSG-14	48
FSG-150	48
FSG-16	48
FSG-20	48
FSG-200	48
FSG-25	48
FSG-32	48
FSG-42	48
FSG-50	48
FSG-60	48
FSG-74	48
FSG-80	48
FSG-88	48
FSS/L/1	1748
FSS/L/2	1748
FSS/L/3	1748
FSS-14-110	1041
FSS-14-230	1041
FSS-14-24	1041
FSS-18-24	1041
FS-TAPE-25-N-11	45
FS-TAPE-25-R-11	45
FT3-12-03CF	16
FT3-12-04CF	16
FT3-12-05CF	16
FT3-12-06CF	16
FT3-12-08CF	16
FT3-12-10CF	16
FT3-12-12CF	16
FT3-12-16CF	16
FT3-12-20CF	16
FT3-12-24CF	16
FT3-12-32CF	16
FTA-110-3-UPVC	1104
FTA-110-4-UPVC	1104
FTA-16-12-UPVC	1104
FTA-16-38-UPVC	1104
FTA-20-12-UPVC	1104
FTA-20-34-UPVC	1104
FTA-25-12-UPVC	1104
FTA-25-1-UPVC	1104
FTA-25-34-UPVC	1104
FTA-32-1-UPVC	1104
FTA-32-34-UPVC	1104
FTA-40-114-UPVC	1104
FTA-40-1-UPVC	1104
FTA-50-112-UPVC	1104
FTA-50-114-UPVC	1104
FTA-50-2-UPVC	1104
FTA-63-112-UPVC	1104
FTA-63-2-UPVC	1104
FTA-75-212-UPVC	1104
FTA-75-2-UPVC	1104
FTA-90-212-UPVC	1104
FTA-90-3-UPVC	1104
FTA-90-4-UPVC	1104
FTB1A10QV25G16X	251
FTBE2A20Q	251
FTP-06MMBOX-M	844
FTP-06MMBOX-OTP	781
FTP-06MMBOX-P	767
FTP-08MMBOX-M	844
FTP-08MMBOX-OTP	781
FTP-08MMBOX-P	767
FTP-10MMBOX-M	844
FTP-10MMBOX-OTP	781
FTP-10MMBOX-P	767
FULL-KIT	49
F-V77JP72FNM701	1702
F-V77JP72FNM801	1702
F-V77JQ72FNM701	1702
F-V77JQ72FNM801	1702
F-V77JR72FNM701	1702
F-V77JR72FNM801	1702
F-V77JS72FNM701	1702
F-V77JS72FNM801	1702
F-V77JT60FNM501	1702
F-V77JT60FNM601	1702
F-V83NP92FNM701	1702
F-V83NP92FNM801	1702
F-V83NQ92FNM701	1702
F-V83NQ92FNM801	1702
F-V91JO92FNM701	1702
F-V91JO92FNM801	1702
F-V91JW92FNM701	1702
F-V91JW92FNM801	1702
F-V91NG92FNM701	1702
F-V91NG92FNM801	1702
F-V91NH92FNM701	1702
F-V91NH92FNM801	1702
F-V91NL92FNM701	1702
F-V91NL92FNM801	1702
F-V91NM92FNM701	1702
F-V91NM92FNM801	1702
FVS-112	1436
FVS-3	1436
FVS-4	1436
FW1	110
FW112	110
FW114	110
FW12	110
FW14	110
FW18	110
FW2	110
FW34	110
FW38	110
FW5M	110
FX050-30	1431
FX075-10	1431
FX075-30	1431
FX100-10	1431
FX100-30	1431
FX125-10	1431
FX125-30	1431
FX150-10	1431
FX150-30	1431
FX200-10	1431
FX200-30	1431
FX250-10	1431
FX250-30	1431
FX300-10	1431
FX300-30	1431
FX400-10	1431
FX400-30	1431
FXKE1	430
FXKE3	430
FYSG-10	48
FYSG-12	48
FYSG-16	48
FYSG-20	48
FYSG-25	48
FYSG-32	48
FYSG-42	48
FYSG-50	48
FYSG-60	48
G	
G 12/16	510
G 160/200	510
G 20	510
G 25/32	510
G 40	510
G 41 125	510
G 50/63	510
G 80/100	510
G1	1421
G100-04B	410
G100-06B	410
G100-10B	410
G100-14B	410
G10-UL	151
G10-US	151
G112	1421
G12	1421
G12-UL	151
G12-US	151
G14-US	151
G15-UL	151
G16-US	151
G18-UL	151
G1NU2000	620
G1TU2VL1	1044
G1TU2VL2	1044
G1TU2VL3	1044
G2	1421
G20-US	151
G22-UL	151
G256121S-23050	1033
G256C113S-24VDC	1031
G256C121S-11050	1033
G256C121S-2450	1033
G256C121S-24DC	1033
G256C129S-11050	1031
G256C129S-23050	1031
G256C129S-2450	1031
G256C136S-11050	1033
G256C136S-23050	1033
G256C136S-24	1033
G256C136S-2450	1033
G256C145S-11050	1031
G256C145S-23050	1031
G256C145S-2450	1031
G256C145S-24VDC	1031
G25-US	151
G28-UL	151
G30-US	151
G356C136S-11050	1033
G356C136S-23050	1033
G356C136S-24	1033
G356C136S-2450	1033
G35-UL	151
G38-US	151
G40-01R	410
G40-02R	410
G40-04R	410
G40-06R	410
G40-07R	410
G40-10R	410
G40-12R	410
G40-16R	410
G40-20R	410
G42-UL	151
G50-01B	410
G50-01C	410
G50-01R	410
G50-025C	410
G50-02B	410
G50-02C	410
G50-02R	410
G50-02T	410
G50-04B	410
G50-04C	410
G50-04R	410
G50-04T	410
G50-06B	410
G50-06C	410
G50-06R	410
G50-06T	410
G50-10B	410
G50-10C	410
G50-10R	410
G50-10T	410
G50-12B	410
G50-12C	410
G50-12PM	411
G50-12R	410
G50-12T	410
G50-16C	410
G50-16R	410
G50-16T	410
G50-20R	410
G50-20T	410
G63-001BG	264
G63-001RG	264
G63-002BG	264
G63-002RG	264
G63-004BG	264
G63-004RG	264
G63-006BG	264
G63-006RG	264
G63-010RG	264
G63-012BG	264
G63-012RG	264
G63-01D	410
G63-020BG	264
G63-020RG	264
G63-025BG	264
G63-025RG	264
G63-040BG	264
G63-040RG	264
G63-04D	410
G63-060BG	264
G63-060RG	264
G63-10T	410
G63-120BG	264
G63-120RG	264
G63-12T	410
G63-16T	410
G63-200BG	264

Code	Page
G63-200RG	264
G63-250BG	264
G63-250RG	264
G63-400BG	264
G63-400RG	264
G63-600BG	264
G63-600RG	264
G63-CB	264
G63-OB	264
G63-PM	264
G63-PM-RHOMB	264
G6-UL	151
G6-US	151
G72	596
G73	596
G76	596
G76028	1513
G76048	1513
G76056	1513
G76072	1513
G76088	1513
G76104	1513
G76128	1513
G76152	1513
G76188	1513
G76216	1513
G76248	1513
G76280	1513
G76344	1513
G77	596
G79	596
G7H	596
G7J	596
G7K	596
G8-UL	151
G8-US	151
G93	596
GA 12/16	510
GA 160/200	510
GA 20	510
GA 25/32	510
GA 40	510
GA 41 125	510
GA 50/63	510
GA 8/10	510
GA 80/100	510
GA04/04	1154
GA06/04	1154
GA06/05	1154
GA06/06	1154
GA800C-1	959
GA800C-112	959
GA800C-112S	959
GA800C-114	959
GA800C-114S	959
GA800C-12	959
GA800C-12S	959
GA800C-1S	959
GA800C-2	959
GA800C-2S	959
GA800C-34	959
GA800C-34S	959
GA800S-1	959
GA800S-112	959
GA800S-112S	959
GA800S-114	959
GA800S-114S	959
GA800S-12	959
GA800S-12S	959
GA800S-1S	959
GA800S-2	959
GA800S-2S	959
GA800S-34	959
GA800S-34S	959
GAI-10L-2RG	147
GAI-10L-4N	147
GAI-10L-4RG	147
GAI-10L-6N	147
GAI-10L-6RG	147
GAI-10L-8N	147
GAI-10L-8RG	147
GAI-10S-6N	147
GAI-10S-6RG	147
GAI-10S-8RG	147
GAI-12L-4N	147
GAI-12L-4RG	147
GAI-12L-6N	147
GAI-12L-6RG	147
GAI-12L-8N	147
GAI-12L-8RG	147
GAI-12S-4RG	147
GAI-12S-6N	147
GAI-12S-6RG	147
GAI-12S-8N	147
GAI-12S-8RG	147
GAI-14S-6RG	147
GAI-14S-8N	147
GAI-14S-8RG	147
GAI-15L-12RG	147
GAI-15L-6RG	147
GAI-15L-8N	147
GAI-15L-8RG	147
GAI-16S-6N	147
GAI-16S-6RG	147
GAI-16S-8N	147
GAI-16S-8RG	147
GAI-18L-12RG	147
GAI-18L-6RG	147
GAI-18L-8N	147
GAI-18L-8RG	147
GAI-20S-12N	147
GAI-20S-12RG	147
GAI-20S-8RG	147
GAI-22L-12N	147
GAI-22L-12RG	147
GAI-22L-8RG	147
GAI-25S-12RG	147
GAI-25S-16N	147
GAI-25S-16RG	147
GAI-28L-16N	147
GAI-28L-16RG	147
GAI-30S-20N	147
GAI-30S-20RG	147
GAI-35L-20N	147
GAI-35L-20RG	147
GAI-38S-24N	147
GAI-38S-24RG	147
GAI-42L-24N	147
GAI-42L-24RG	147
GAI-6L-2N	147
GAI-6L-2RG	147
GAI-6L-4N	147
GAI-6L-4RG	147
GAI-6L-6RG	147
GAI-6L-8RG	147
GAI-6S-4N	147
GAI-6S-4RG	147
GAI-8L-2RG	147
GAI-8L-4N	147
GAI-8L-4RG	147
GAI-8L-6RG	147
GAI-8L-8RG	147
GAI-8S-4N	147
GAI-8S-4RG	147
GAI-8S-6RG	147
GAI-8S-8RG	147
GAS 10 LR	133
GAS 10 SR	133
GAS 12 LR	133
GAS 12 LR 1/4	133
GAS 12 SR	133
GAS 14 SR	133
GAS 15 LR	133
GAS 16 SR	133
GAS 18 LR	133
GAS 20 SR	133
GAS 22 LR	133
GAS 25 SR	133
GAS 28 LR	133
GAS 30 SR	133
GAS 35 LR	133
GAS 38 SR	133
GAS 42 LR	133
GAS 6 LR	133
GAS 6 SR	133
GAS 8 LR	133
GAS 8 SR	133
GASOILA2	1391
GAV10LM	130
GAV10LR	130
GAV10SM	130
GAV10SR	130
GAV12LM	130
GAV12LR	130
GAV12LR1/4	130
GAV12SM	130
GAV12SR	130
GAV14SM	130
GAV14SR	130
GAV15LM	130
GAV15LR	130
GAV16SM	130
GAV16SR	130
GAV18LM	130
GAV18LR	130
GAV20SM	130
GAV20SR	130
GAV22LM	130
GAV22LR	130
GAV25SR	130
GAV28LR	130
GAV30SR	130
GAV35LR	130
GAV38SR	130
GAV42LR	130
GAV6LM	130
GAV6LR	130
GAV6SM	130
GAV6SR	130
GAV8LM	130
GAV8LR	130
GAV8SM	130
GAV8SR	130
GB-1	1107
GB16-1	1099
GB16-112	1099
GB16-114	1099
GB16-12	1099
GB16-2	1099
GB16-212	1099
GB16-3	1099
GB16-34	1099
GB16-4	1099
GB16-5	1099
GB16-6	1099
GB16-8	1111
GBP-1	1142
GBP-114	1142
GBP-2	1142
GBP-34	1142
GBR-110	1105
GBR-25	1105
GBR-32	1105
GBR-40	1105
GBR-50	1105
GBR-63	1105
GBR-75	1105
GBR-90	1105
GBV-1	975
GBV100/06	415
GBV100/06D	412
GBV-112	975
GBV-114	975
GBV-12	975
GBV-2	975
GBV-34	975
GBV63/04	415
GBV63/04D	412
GBVMF-3434	941
GCPM4010	411
GCPM4014	411
GCPM402	411
GCPM4020	411
GCPM404	411
GCPM407	411
GCPM5010	411
GCPM5014	411
GCPM502	411
GCPM504	411
GCPM507	411
GCV100/06	415
GCV100/06D	412
GCV63/04	415
GCV63/04D	412
GCVPM40/02	411
GCVPM50/02	411
GDH-4	1625
GDH-5	1625
GDH-6	1625
GDM2011-G	219
GDML2011-GB1-B	219
GDML2011LED-120B	219
GDML2011LED-230B	219
GDML2011LED-24-B	219
GDML2011LED-24HH	219
GDML2011LED-48HH	219
GDOR	1477
GE-10L-1/2UNF	147
GE-10L-10MEO	144
GE-10L-10MPB	145
GE-10L-12EO	144
GE-10L-12MEO	144
GE-10L-12MPB	145
GE-10L-12N	146
GE-10L-12RP	145
GE-10L-14MEO	144
GE-10L-14MPB	145
GE-10L-16MEO	144
GE-10L-16MPB	145
GE-10L-18MEO	144
GE-10L-18MPB	145
GE-10L-22MEO	144
GE-10L-22MPB	145
GE-10L-2EO	144
GE-10L-2N	146
GE-10L-2RP	145
GE-10L-2RT	146
GE-10L-3/4UNF	147
GE-10L-4EO	144
GE-10L-4N	146
GE-10L-4RP	145
GE-10L-4RT	146
GE-10L-6EO	144
GE-10L-6N	146
GE-10L-6RP	145
GE-10L-6RT	146
GE-10L-7/16UNF	147
GE-10L-8EO	144
GE-10L-8N	146
GE-10L-8RP	145
GE-10L-8RT	146
GE-10L-9/16UNF	147
GE-10S-12EO	144
GE-10S-12N	146
GE-10S-12RP	145
GE-10S-14MEO	144
GE-10S-16MEO	144
GE-10S-16MPB	145
GE-10S-18MEO	144
GE-10S-18MPB	145
GE-10S-2EO	144
GE-10S-2N	146
GE-10S-2RP	145
GE-10S-3/4UNF	147
GE-10S-4EO	144
GE-10S-4N	146
GE-10S-4RP	145
GE-10S-4RT	146
GE-10S-6EO	144
GE-10S-6N	146

Code	Page
GE-10S-6RP	145
GE-10S-6RT	146
GE-10S-8EO	144
GE-10S-8N	146
GE-10S-8RP	145
GE-12L-12EO	144
GE-12L-12MEO	144
GE-12L-12MPB	145
GE-12L-12N	146
GE-12L-12RP	145
GE-12L-12RT	146
GE-12L-14MEO	144
GE-12L-14MPB	145
GE-12L-16MEO	144
GE-12L-16MPB	145
GE-12L-18MEO	144
GE-12L-18MPB	145
GE-12L-22MEO	144
GE-12L-22MPB	145
GE-12L-2EO	144
GE-12L-2N	146
GE-12L-2RP	145
GE-12L-2RT	146
GE-12L-3/4UNF	147
GE-12L-4EO	144
GE-12L-4N	146
GE-12L-4RP	145
GE-12L-4RT	146
GE-12L-6EO	144
GE-12L-6N	146
GE-12L-6RP	145
GE-12L-6RT	146
GE-12L-7/8UNF	147
GE-12L-8EO	144
GE-12L-8N	146
GE-12L-8RP	145
GE-12L-8RT	146
GE-12L-9/16UNF	147
GE-12S-12EO	144
GE-12S-12N	146
GE-12S-12RP	145
GE-12S-14MEO	144
GE-12S-14MPB	145
GE-12S-16MEO	144
GE-12S-16MPB	145
GE-12S-18MEO	144
GE-12S-18MPB	145
GE-12S-20MEO	144
GE-12S-22MEO	144
GE-12S-22MPB	145
GE-12S-3/4UNF	147
GE-12S-4EO	144
GE-12S-4N	146
GE-12S-4RP	145
GE-12S-4RT	146
GE-12S-6EO	144
GE-12S-6N	146
GE-12S-6RP	145
GE-12S-6RT	146
GE-12S-7/8UNF	147
GE-12S-8EO	144
GE-12S-8N	146
GE-12S-8RP	145
GE-12S-8RT	146
GE-12S-9/16UNF	147
GE-14S-12EO	144
GE-14S-12N	146
GE-14S-12RP	145
GE-14S-20MEO	144
GE-14S-20MPB	145
GE-14S-22MEO	144
GE-14S-3/4UNF	147
GE-14S-4RP	145
GE-14S-6EO	144
GE-14S-6N	146
GE-14S-6RP	145
GE-14S-6RT	146
GE-14S-8EO	144
GE-14S-8N	146
GE-14S-8RP	145
GE-14S-8RT	146
GE-15L-12EO	144
GE-15L-12N	146
GE-15L-12RP	145
GE-15L-12RT	146
GE-15L-16EO	144
GE-15L-16MEO	144
GE-15L-16MPB	145
GE-15L-18MEO	144
GE-15L-18MPB	145
GE-15L-22MEO	144
GE-15L-22MPB	145
GE-15L-3/4UNF	147
GE-15L-4EO	144
GE-15L-4N	146
GE-15L-4RP	145
GE-15L-4RT	146
GE-15L-6EO	144
GE-15L-6N	146
GE-15L-6RP	145
GE-15L-6RT	146
GE-15L-7/8UNF	147
GE-15L-8EO	144
GE-15L-8N	146
GE-15L-8RP	145
GE-15L-8RT	146
GE-15L-9/16UNF	147
GE-16S-11/16UNF	147
GE-16S-12EO	144
GE-16S-12N	146
GE-16S-12RP	145
GE-16S-12RT	146
GE-16S-16EO	144
GE-16S-16N	146
GE-16S-16RP	145
GE-16S-18MEO	144
GE-16S-18MPB	145
GE-16S-22MEO	144
GE-16S-22MPB	145
GE-16S-3/4UNF	147
GE-16S-4EO	144
GE-16S-4RP	145
GE-16S-6EO	144
GE-16S-6N	146
GE-16S-6RP	145
GE-16S-6RT	146
GE-16S-7/8UNF	147
GE-16S-8EO	144
GE-16S-8N	146
GE-16S-8RP	145
GE-16S-8RT	146
GE-18L-11/16UNF	147
GE-18L-12EO	144
GE-18L-12N	146
GE-18L-12RP	145
GE-18L-12RT	146
GE-18L-16EO	144
GE-18L-16N	146
GE-18L-16RP	145
GE-18L-18MEO	144
GE-18L-18MPB	145
GE-18L-22MEO	144
GE-18L-22MPB	145
GE-18L-26MEO	144
GE-18L-26MPB	145
GE-18L-3/4UNF	147
GE-18L-6EO	144
GE-18L-6N	146
GE-18L-6RP	145
GE-18L-6RT	146
GE-18L-7/8UNF	147
GE-18L-8EO	144
GE-18L-8N	146
GE-18L-8RP	145
GE-18L-8RT	146
GE-20S-11/16UNF	147
GE-20S-12EO	144
GE-20S-12N	146
GE-20S-12RP	145
GE-20S-12RT	146
GE-20S-15/16UNF	147
GE-20S-16EO	144
GE-20S-16N	146
GE-20S-16RP	145
GE-20S-20EO	144
GE-20S-20N	146
GE-20S-20RP	145
GE-20S-27MEO	144
GE-20S-27MPB	145
GE-20S-3/4UNF	147
GE-20S-6EO	144
GE-20S-6N	146
GE-20S-6RP	145
GE-20S-7/8UNF	147
GE-20S-8EO	144
GE-20S-8RP	145
GE-20S-8RT	146
GE-22L-11/16UNF	147
GE-22L-12EO	144
GE-22L-12N	146
GE-22L-12RP	145
GE-22L-12RT	146
GE-22L-15/16UNF	147
GE-22L-16EO	144
GE-22L-16N	146
GE-22L-16RP	145
GE-22L-16RT	146
GE-22L-20EO	144
GE-22L-20N	146
GE-22L-20RP	145
GE-22L-22MEO	144
GE-22L-22MPB	145
GE-22L-26MEO	144
GE-22L-26MPB	145
GE-22L-3/4UNF	147
GE-22L-6EO	144
GE-22L-6N	146
GE-22L-6RP	145
GE-22L-6RT	146
GE-22L-7/8UNF	147
GE-22L-8EO	144
GE-22L-8N	146
GE-22L-8RP	145
GE-22L-8RT	146
GE-25S-11/16UNF	147
GE-25S-12EO	144
GE-25S-12N	146
GE-25S-12RP	145
GE-25S-12RT	146
GE-25S-15/16UNF	147
GE-25S-16EO	144
GE-25S-16N	146
GE-25S-16RP	145
GE-25S-16RT	146
GE-25S-20EO	144
GE-25S-20N	146
GE-25S-20RP	145
GE-25S-33MEO	144
GE-25S-33MPB	145
GE-25S-8EO	144
GE-25S-8N	146
GE-25S-8RP	145
GE-28L-11/16UNF	147
GE-28L-12EO	144
GE-28L-12N	146
GE-28L-12RP	145
GE-28L-12RT	146
GE-28L-15/16UNF	147
GE-28L-15/8UNF	147
GE-28L-16EO	144
GE-28L-16N	146
GE-28L-16RP	145
GE-28L-16RT	146
GE-28L-20EO	144
GE-28L-20N	146
GE-28L-20RP	145
GE-28L-20RT	146
GE-28L-24EO	144
GE-28L-24RP	145
GE-28L-33MEO	144
GE-28L-33MPB	145
GE-28L-8EO	144
GE-28L-8N	146
GE-28L-8RP	145
GE-28L-8RT	146
GE-30S-11/16UNF	147
GE-30S-12EO	144
GE-30S-12N	146
GE-30S-12RP	145
GE-30S-15/16UNF	147
GE-30S-15/8UNF	147
GE-30S-16EO	144
GE-30S-16N	146
GE-30S-16RP	145
GE-30S-20EO	144
GE-30S-20N	146
GE-30S-20RP	145
GE-30S-20RT	146
GE-30S-24EO	144
GE-30S-24N	146
GE-30S-24RP	145
GE-30S-42MEO	144
GE-30S-42MPB	145
GE-35L-12EO	144
GE-35L-12RP	145
GE-35L-15/16UNF	147
GE-35L-15/8UNF	147
GE-35L-16EO	144
GE-35L-16N	146
GE-35L-16RP	145
GE-35L-16RT	146
GE-35L-20EO	144
GE-35L-20N	146
GE-35L-20RP	145
GE-35L-20RT	146
GE-35L-24EO	144
GE-35L-24N	146
GE-35L-24RP	145
GE-35L-24RT	146
GE-35L-42MEO	144
GE-35L-42MPB	145
GE-38S-15/8UNF	147
GE-38S-16EO	144
GE-38S-16N	146
GE-38S-16RP	145
GE-38S-17/8UNF	147
GE-38S-20EO	144
GE-38S-20N	146
GE-38S-20RP	145
GE-38S-24EO	144
GE-38S-24N	146
GE-38S-24RP	145
GE-38S-24RT	146
GE-38S-48MEO	144
GE-38S-48MPB	145
GE-42L-15/8UNF	147
GE-42L-16EO	144
GE-42L-16N	146
GE-42L-16RP	145
GE-42L-17/8UNF	147
GE-42L-20EO	144
GE-42L-20N	146
GE-42L-20RP	145
GE-42L-20RT	146
GE-42L-24EO	144
GE-42L-24N	146
GE-42L-24RP	145
GE-42L-24RT	146
GE-42L-32EO	144
GE-42L-48MEO	144
GE-42L-48MPB	145
GE-6L-1/2UNF	147
GE-6L-10MEO	144
GE-6L-10MPB	145
GE-6L-12MEO	144
GE-6L-12MPB	145
GE-6L-14MEO	144
GE-6L-14MPB	145
GE-6L-2EO	144
GE-6L-2N	146

Code	Page
GE-6L-2RP	145
GE-6L-2RT	146
GE-6L-4EO	144
GE-6L-4N	146
GE-6L-4RP	145
GE-6L-4RT	146
GE-6L-6EO	144
GE-6L-6N	146
GE-6L-6RP	145
GE-6L-6RT	146
GE-6L-7/16UNF	147
GE-6L-8EO	144
GE-6L-8N	146
GE-6L-8RP	145
GE-6L-8RT	146
GE-6L-9/16UNF	147
GE-6S-12MEO	144
GE-6S-12MPB	145
GE-6S-14MEO	144
GE-6S-14MPB	145
GE-6S-2EO	144
GE-6S-2N	146
GE-6S-2RP	145
GE-6S-2RT	146
GE-6S-4EO	144
GE-6S-4N	146
GE-6S-4RP	145
GE-6S-4RT	146
GE-6S-6EO	144
GE-6S-6N	146
GE-6S-6RP	145
GE-6S-6RT	146
GE-6S-7/16UNF	147
GE-6S-8EO	144
GE-6S-8N	146
GE-6S-8RP	145
GE-8L-1/2UNF	147
GE-8L-10MEO	144
GE-8L-10MPB	145
GE-8L-12MEO	144
GE-8L-12MPB	145
GE-8L-14MEO	144
GE-8L-14MPB	145
GE-8L-16MEO	144
GE-8L-16MPB	145
GE-8L-18MEO	144
GE-8L-18MPB	145
GE-8L-2EO	144
GE-8L-2N	146
GE-8L-2RP	145
GE-8L-2RT	146
GE-8L-4EO	144
GE-8L-4N	146
GE-8L-4RP	145
GE-8L-4RT	146
GE-8L-6EO	144
GE-8L-6N	146
GE-8L-6RP	145
GE-8L-6RT	146
GE-8L-7/16UNF	147
GE-8L-8EO	144
GE-8L-8N	146
GE-8L-8RP	145
GE-8L-8RT	146
GE-8L-9/16UNF	147
GE-8S-1/2UNF	147
GE-8S-12MEO	144
GE-8S-14MEO	144
GE-8S-14MPB	145
GE-8S-16MEO	144
GE-8S-2EO	144
GE-8S-2N	146
GE-8S-2RP	145
GE-8S-2RT	146
GE-8S-4EO	144
GE-8S-4N	146
GE-8S-4RP	145
GE-8S-4RT	146
GE-8S-6EO	144
GE-8S-6N	146
GE-8S-6RP	145
GE-8S-6RT	146
GE-8S-7/16UNF	147
GE-8S-8EO	144
GE-8S-8N	146
GE-8S-8RP	145
GE-8S-9/16UNF	147
GES 10 LR	132
GES 10 LR 1/2	132
GES 10 LR 1/2-WD	132
GES 10 LR 3/8	132
GES 10 LR 3/8-WD	132
GES 10 LR-WD	132
GES 10 SR	132
GES 10 SR 1/2	132
GES 10 SR 1/2-WD	132
GES 10 SR 1/4	132
GES 10 SR 1/4-WD	132
GES 10 SR-WD	132
GES 12 LR	132
GES 12 LR 1/2	132
GES 12 LR 1/2-WD	132
GES 12 LR 1/4	132
GES 12 LR 1/4-WD	132
GES 12 LR-WD	132
GES 12 SR	132
GES 12 SR 1/2	132
GES 12 SR 1/2-WD	132
GES 12 SR 1/4	132
GES 12 SR 1/4-WD	132
GES 12 SR-WD	132
GES 14 SR	132
GES 14 SR-WD	132
GES 15 LR	132
GES 15 LR 3/4	132
GES 15 LR-WD	132
GES 16 SR	132
GES 16 SR 3/4	132
GES 16 SR 3/4-WD	132
GES 16 SR 3/8	132
GES 16 SR 3/8-WD	132
GES 16 SR-WD	132
GES 18 LR	132
GES 18 LR-WD	132
GES 20 SR	132
GES 20 SR 1/2	132
GES 20 SR-WD	132
GES 22 LR	132
GES 22 LR 1/2	132
GES 22 LR-WD	132
GES 25 SR	132
GES 25 SR 3/4	132
GES 25 SR 3/4-WD	132
GES 25 SR-WD	132
GES 28 LR	132
GES 28 LR 3/4	132
GES 28 LR-WD	132
GES 30 SR	132
GES 30 SR-WD	132
GES 35 LR	132
GES 35 LR-WD	132
GES 38 SR	132
GES 38 SR 1.1/4	132
GES 38 SR-WD	132
GES 42 LR	132
GES 42 LR-WD	132
GES 6 LR	132
GES 6 LR 1/4	132
GES 6 LR 1/4-WD	132
GES 6 LR-WD	132
GES 6 SR	132
GES 6 SR-WD	132
GES 8 LR	132
GES 8 LR 1/8	132
GES 8 LR 1/8-WD	132
GES 8 LR 3/8	132
GES 8 LR 3/8-WD	132
GES 8 LR-WD	132
GES 8 SR	132
GES 8 SR 3/8	132
GES 8 SR 3/8-WD	132
GES 8 SR-WD	132
GES10 LR 1/2FOA	132
GES10 LR 3/8FOA	132
GES10 LRFOA	132
GES10 SR 1/4FOA	132
GES10 SRFOA	132
GES12 LR 1/2FOA	132
GES12 LR 1/4FOA	132
GES12 LRFOA	132
GES12 SR 1/2FOA	132
GES12 SR 1/4FOA	132
GES12 SRFOA	132
GES14 SRFOA	132
GES15 LR 3/8FOA	132
GES15 LRFOA	132
GES16 SR 3/4FOA	132
GES16 SR 3/8FOA	132
GES16 SRFOA	132
GES18 LR 3/4FOA	132
GES18 LRFOA	132
GES20 SR 1/2FOA	132
GES20 SRFOA	132
GES22 LR 1/2FOA	132
GES22 LRFOA	132
GES25 SR 3/4FOA	132
GES25 SRFOA	132
GES28 LR 3/4FOA	132
GES28 LRFOA	132
GES30 SR 1FOA	132
GES35 LRFOA	132
GES38 SR 11/4FOA	132
GES38 SR 1FOA	132
GES6 LR 1/4FOA	132
GES6 LR 3/8FOA	132
GES6 LRFOA	132
GES8 LR 1/8FOA	132
GES8 LR 3/8FOA	132
GES8 LRFOA	132
GES8 SRFOA	132
GEV10L1/4NPT	121
GEV10L3/8NPT	121
GEV10L7/16-20UNF	121
GEV10L9/16-18UNF	121
GEV10LM	119
GEV10LM16X1.5	119
GEV10LM18X1.5	119
GEV10LM22X1.5	119
GEV10LMWD	120
GEV10LR	120
GEV10LR1/2	120
GEV10LR1/2FOA	119
GEV10LR1/2WD	120
GEV10LR3/8	120
GEV10LR3/8FOA	119
GEV10LR3/8K	119
GEV10LR3/8WD	120
GEV10LRFOA	119
GEV10LRK	119
GEV10LRWD	120
GEV10S1/4NPT	121
GEV10S3/8NPT	121
GEV10S9/16-18UNF	121
GEV10SM	119
GEV10SMWD	120
GEV10SR	120
GEV10SR1/2	120
GEV10SR1/2WD	120
GEV10SR1/4	120
GEV10SR1/4FOA	119
GEV10SR1/4WD	120
GEV10SRFOA	119
GEV10SRWD	120
GEV12L1/2NPT	121
GEV12L1/4NPT	121
GEV12L3/4-16UNF	121
GEV12L3/8NPT	121
GEV12L7/8-14UNF	121
GEV12L9/16-18UNF	121
GEV12LM	119
GEV12LM18X1.5	119
GEV12LM18X1.5WD	120
GEV12LM22X1.5	119
GEV12LM22X1.5WD	120
GEV12LMWD	120
GEV12LR	120
GEV12LR1/2	120
GEV12LR1/2FOA	119
GEV12LR1/2WD	120
GEV12LR1/4	120
GEV12LR1/4FOA	119
GEV12LR1/4K	119
GEV12LR1/4WD	120
GEV12LRFOA	119
GEV12LRK	119
GEV12LRWD	120
GEV12S1/2NPT	121
GEV12S1/4NPT	121
GEV12S3/4-16UNF	121
GEV12S3/8NPT	121
GEV12SM	119
GEV12SMWD	120
GEV12SR	120
GEV12SR1/2	120
GEV12SR1/2FOA	119
GEV12SR1/2WD	120
GEV12SR1/4	120
GEV12SR1/4FOA	119
GEV12SR1/4WD	120
GEV12SRFOA	119
GEV12SRWD	120
GEV14S1/2NPT	121
GEV14SM	119
GEV14SMWD	120
GEV14SR	120
GEV14SR3/8	120
GEV14SRFOA	119
GEV14SRWD	120
GEV15L1/2NPT	121
GEV15L3/4-16UNF	121
GEV15L7/8-14UNF	121
GEV15LM	119
GEV15LM22X1.5	119
GEV15LM22X1.5WD	120
GEV15LMD	120
GEV15LR	120
GEV15LR3/4	120
GEV15LR3/8	120
GEV15LR3/8FOA	119
GEV15LR3/8WD	120
GEV15LRFOA	119
GEV15LRK	119
GEV15LRWD	120
GEV16S1/2NPT	121
GEV16S3/4-16UNF	121
GEV16S7/8-14UNF	121
GEV16SM	119
GEV16SM18X1.5	119
GEV16SMWD	120
GEV16SR	120
GEV16SR3/4	120
GEV16SR3/4FOA	119
GEV16SR3/4WD	120
GEV16SR3/8	120
GEV16SR3/8FOA	119
GEV16SR3/8WD	120
GEV16SRFOA	119
GEV16SRWD	120
GEV18L1/2NPT	121
GEV18L3/4-16UNF	121
GEV18L7/8-14UNF	121
GEV18LM	119
GEV18LM18X1.5	119
GEV18LM18X1.5WD	120
GEV18LMWD	120
GEV18LR	120
GEV18LR3/4	120
GEV18LR3/4FOA	119
GEV18LR3/4WD	120
GEV18LR3/8	120

Code	Page
GEV18LRFOA	119
GEV18LRWD	120
GEV20S11/16-12UN	121
GEV20S3/4-16UNF	121
GEV20S7/8-14UNF	121
GEV20SM	119
GEV20SMWD	120
GEV20SR	120
GEV20SR1	120
GEV20SR1/2	120
GEV20SR1/2FOA	119
GEV20SRFOA	119
GEV20SRWD	120
GEV22L11/16-12UN	121
GEV22L3/4NPT	121
GEV22L7/8-14UNF	121
GEV22LM	119
GEV22LMWD	120
GEV22LR	120
GEV22LR1	120
GEV22LR1/2	120
GEV22LR1/2FOA	119
GEV22LRFOA	119
GEV22LRWD	120
GEV25S1NPT	121
GEV25SM	119
GEV25SMWD	120
GEV25SR	120
GEV25SR3/4	120
GEV25SR3/4FOA	119
GEV25SR3/4WD	120
GEV25SRFOA	119
GEV25SRWD	120
GEV28L15/16-12UN	121
GEV28L1NPT	121
GEV28L7/8-14UNF	121
GEV28LM	119
GEV28LMWD	120
GEV28LR	120
GEV28LR3/4	120
GEV28LR3/4FOA	119
GEV28LRFOA	119
GEV28LRWD	120
GEV30S15/8-12UN	121
GEV30SM	119
GEV30SMWD	120
GEV30SR	120
GEV30SR1	120
GEV30SR11/4FOA	119
GEV30SR1FOA	119
GEV30SR3/4	120
GEV30SRWD	120
GEV35L11/4NPT	121
GEV35L15/16-12UN	121
GEV35L15/8-12UN	121
GEV35LM	119
GEV35LMWD	120
GEV35LR1	120
GEV35LRFOA	119
GEV35LRWD	120
GEV38S11/2NPT	121
GEV38SM	119
GEV38SMWD	120
GEV38SR	120
GEV38SR11/4	120
GEV38SR11/4FOA	119
GEV38SR1FOA	119
GEV38SRFOA	119
GEV38SRWD	120
GEV42L11/2NPT	121
GEV42LM	119
GEV42LR	120
GEV42LRWD	120
GEV4LL1/8NPT	121
GEV4LLRK	119
GEV6L1/4NPT	121
GEV6L1/8NPT	121
GEV6LL1/8NPT	121
GEV6LLRK	119
GEV6LM12X1.5	119
GEV6LMWD	120
GEV6LR	120
GEV6LR1/4	120
GEV6LR1/4FOA	119
GEV6LR1/4WD	120
GEV6LR3/8	120
GEV6LR3/8FOA	119
GEV6LRFOA	119
GEV6LRWD	120
GEV6SM	119
GEV6SMWD	120
GEV6SR	120
GEV6SRWD	120
GEV8L1/4NPT	121
GEV8L7/16-20UNF	121
GEV8L9/16-18UNF	121
GEV8LL1/8NPT	121
GEV8LLRK	119
GEV8LM	119
GEV8LM16X1.5	119
GEV8LMWD	120
GEV8LR	120
GEV8LR1/2	120
GEV8LR1/8	120
GEV8LR1/8FOA	119
GEV8LR1/8WD	120
GEV8LR3/8	120
GEV8LR3/8FOA	119
GEV8LR3/8WD	120
GEV8LRFOA	119
GEV8LRK	119
GEV8LRWD	120
GEV8S1/4NPT	121
GEV8SM	119
GEV8SMWD	120
GEV8SR	120
GEV8SR1/2	120
GEV8SR3/8	120
GEV8SR3/8WD	120
GEV8SRFOA	119
GEV8SRWD	120
GF1-1	1356
GF1-112	1356
GF1-112N	1356
GF1-114	1356
GF1-114N	1356
GF1-12	1356
GF1-12N	1356
GF1-14	1356
GF1-14N	1356
GF1-1N	1356
GF1-2	1356
GF120-1	1359
GF120-112	1359
GF120-112N	1359
GF120-114	1359
GF120-114N	1359
GF120-12	1359
GF120-12N	1359
GF120-1N	1359
GF120-2	1359
GF120-212N	1359
GF120-2N	1359
GF120-3	1359
GF120-34	1359
GF120-34N	1359
GF120-3N	1359
GF121-1	1359
GF121-112	1359
GF121-112N	1359
GF121-114	1359
GF121-114N	1359
GF121-12	1359
GF121-12N	1359
GF121-1N	1359
GF121-2	1359
GF1-212	1356
GF121-212	1359
GF121-2N	1359
GF1-212N	1356
GF121-3	1359
GF121-34	1359
GF121-34N	1359
GF121-38	1359
GF121-38N	1359
GF1-2N	1356
GF1-3	1356
GF130-1	1360
GF130-1-112	1360
GF130-1-112N	1360
GF130-1-114	1360
GF130-1-114N	1360
GF130-112	1360
GF130-1-12	1360
GF130-112-1	1360
GF130-1-12-1	1361
GF130-112-1-1	1361
GF130-112-1-112	1361
GF130-112-1-112N	1361
GF130-112-114	1360
GF130-112-114-1	1361
GF130-112-114114	1361
GF130-112114114N	1361
GF130-112-11412	1361
GF130-112-11412N	1361
GF130-112-114-1N	1361
GF130-112-114N	1360
GF130-112-1-1N	1361
GF130-112-12	1360
GF130-112-12-112	1361
GF130-112-12112N	1361
GF130-112-12N	1360
GF130-112-1N	1360
GF130-1-12-1N	1361
GF130-112-2	1360
GF130-112-2N	1360
GF130-112-34	1360
GF130-112-34N	1360
GF130-112N	1360
GF130-1-12N	1360
GF130-114	1360
GF130-114-1	1360
GF130-114-1-1	1361
GF130-114-1-114	1361
GF130-114-1-114N	1361
GF130-114-1-12	1361
GF130-114-1-12N	1361
GF130-114-1-1N	1361
GF130-114-12	1360
GF130-114-12-114	1361
GF130-114-12114N	1361
GF130-114-12N	1360
GF130-114-1-34	1361
GF130-114-1-34N	1361
GF130-114-1N	1360
GF130-114-34	1360
GF130-114-34N	1360
GF130-114N	1360
GF130-12	1360
GF130-12-14	1360
GF130-12-14N	1360
GF130-12-34	1360
GF130-12-34N	1360
GF130-12-38	1360
GF130-12-38-38	1361
GF130-12-38-38N	1361
GF130-12-38N	1360
GF130-12N	1360
GF130-1-34	1360
GF130-1-34-1	1361
GF130-1-34-12	1361
GF130-1-34-12N	1361
GF130-1-34-1N	1361
GF130-1-34-34	1361
GF130-1-34-34N	1361
GF130-1-34N	1360
GF130-1-38	1360
GF130-1-38N	1360
GF130-14	1360
GF130-14N	1360
GF130-1N	1360
GF130-2	1360
GF130-2-1	1360
GF130-2-112	1360
GF130-2-112-1	1361
GF130-2-112-112N	1361
GF130-2-112-114	1361
GF130-2-112-114N	1361
GF130-2-112-1N	1361
GF130-2-112-2	1361
GF130-2-112-2N	1361
GF130-2-112N	1360
GF130-2-114	1360
GF130-2-114N	1360
GF130-212	1360
GF130-2-12	1360
GF130-2-1-2	1361
GF130-212-1	1360
GF130-212-112	1360
GF130-212-112212	1361
GF130-212112212N	1361
GF130-212-112N	1360
GF130-212-114	1360
GF130-212-114N	1360
GF130-212-12	1360
GF130-212-12N	1360
GF130-212-1N	1360
GF130-212-2	1360
GF130-2-12-2	1361
GF130-212-2-2	1361
GF130-212-2-2N	1361
GF130-212-2N	1360
GF130-2-12-2N	1361
GF130-212-34	1360
GF130-212-34N	1360
GF130-212N	1360
GF130-2-12N	1360
GF130-2-1-2N	1361
GF130-2-1N	1360
GF130-2-212	1360
GF130-2-212N	1360
GF130-2-34	1360
GF130-2-34-2	1361
GF130-2-34-2N	1361
GF130-2-34N	1360
GF130-2N	1360
GF130-3	1360
GF130-3-1	1360
GF130-3-112	1360
GF130-3-112N	1360
GF130-3-114	1360
GF130-3-114N	1360
GF130-3-1N	1360
GF130-3-2	1360
GF130-3-212	1360
GF130-3-212N	1360
GF130-3-2-2	1361
GF130-3-2N	1360
GF130-3-34	1360
GF130-3-34N	1360
GF130-34	1360
GF130-34-1	1360
GF130-34-12	1360
GF130-34-12-12	1361
GF130-34-12-12N	1361
GF130-34-12-34	1361
GF130-34-12-34N	1361
GF130-34-12N	1360
GF130-34-14	1360
GF130-34-14N	1360
GF130-34-1N	1360
GF130-34-38	1360
GF130-34-38N	1360
GF130-34N	1360
GF130-38	1360
GF130-38-14	1360
GF130-38-14N	1360
GF130-38N	1360
GF130-3N	1360
GF130-4-1	1360

Code	Page
GF130-4-112	1360
GF130-4-112N	1360
GF130-4-1N	1360
GF130-4-2	1360
GF130-4-212N	1360
GF130-4-2N	1360
GF130-4-3	1360
GF130-4-3N	1360
GF130-4N	1360
GF130-5	1360
GF130-5N	1360
GF130-6N	1360
GF131-1	1361
GF131-112	1361
GF131-1-12	1362
GF131-112-1	1362
GF131-112-114	1362
GF131-112-114N	1362
GF131-112-1N	1362
GF131-112-34	1362
GF131-112-34N	1362
GF131-112N	1361
GF131-1-12N	1362
GF131-114	1361
GF131-114-1	1362
GF131-114-12	1362
GF131-114-12N	1362
GF131-114-1N	1362
GF131-114-34	1362
GF131-114-34N	1362
GF131-114N	1361
GF131-12	1361
GF131-12N	1361
GF131-1-34	1362
GF131-1-34-34	1362
GF131-1-34-34N	1362
GF131-1-34N	1362
GF131-1N	1361
GF131-2	1361
GF131-2-1	1362
GF131-2-112	1362
GF131-2-112N	1362
GF131-2-114	1362
GF131-2-114N	1362
GF131-212	1361
GF131-212-114	1362
GF131-212N	1361
GF131-2-1N	1362
GF131-2-34	1362
GF131-2-34N	1362
GF131-2N	1361
GF131-3	1361
GF131-3-2	1362
GF131-3-2N	1362
GF131-34	1361
GF131-34-12	1362
GF131-34-12-12	1362
GF131-34-12-12N	1362
GF131-34-12N	1362
GF131-34N	1361
GF131-3N	1361
GF131-4N	1361
GF132-1	1362
GF132-112	1362
GF132-112N	1362
GF132-114	1362
GF132-114N	1362
GF132-12	1362
GF132-12N	1362
GF132-1N	1362
GF132-2	1362
GF132-2N	1362
GF132-34	1362
GF132-34N	1362
GF1-34	1356
GF1-34N	1356
GF1-38	1356
GF1-38N	1356
GF1-3N	1356
GF1-4N	1356
GF180-1	1362
GF180-112	1362
GF180-112N	1362
GF180-114	1362
GF180-114N	1362
GF180-12	1362
GF180-12N	1362
GF180-1N	1362
GF180-2	1362
GF180-212	1362
GF180-212N	1362
GF180-2N	1362
GF180-3	1362
GF180-34	1362
GF180-34N	1362
GF180-3N	1362
GF180-4	1362
GF180-4N	1362
GF1A-1	1356
GF1A-112	1356
GF1A-112N	1356
GF1A-114	1356
GF1A-114N	1356
GF1A-12	1356
GF1A-12N	1356
GF1A-14	1356
GF1A-14N	1356
GF1A-1N	1356
GF1A-2	1356
GF1A-212N	1356
GF1A-2N	1356
GF1A-3	1356
GF1A-34	1356
GF1A-34N	1356
GF1A-38	1356
GF1A-38N	1356
GF1A-3N	1356
GF1A-4	1356
GF1A-4N	1356
GF2-1	1356
GF2-112	1356
GF2-112N	1356
GF2-114	1356
GF2-114N	1356
GF2-12	1356
GF2-12N	1356
GF2-14	1356
GF2-14N	1356
GF2-1N	1356
GF2-2	1356
GF2-212	1356
GF2-212N	1356
GF2-2N	1356
GF2-3	1356
GF2-34	1356
GF2-34N	1356
GF2-38	1356
GF2-38N	1356
GF2-3N	1356
GF240-1-12	1363
GF240-112-1	1363
GF240-112-114	1363
GF240-112-114N	1363
GF240-112-12	1363
GF240-112-12N	1363
GF240-112-1N	1363
GF240-112-34	1363
GF240-112-34N	1363
GF240-1-12N	1363
GF240-114-1	1363
GF240-114-12	1363
GF240-114-12N	1363
GF240-114-1N	1363
GF240-114-34	1363
GF240-114-34N	1363
GF240-12-14	1363
GF240-12-14N	1363
GF240-12-38N	1363
GF240-1-34	1363
GF240-1-34N	1363
GF240-14-18	1363
GF240-14-18N	1363
GF240-2-1	1363
GF240-2-112	1363
GF240-2-112N	1363
GF240-2-114	1363
GF240-2-114N	1363
GF240-212-112	1363
GF240-212-112N	1363
GF240-212-2	1363
GF240-212-2N	1363
GF240-2-1N	1363
GF240-2-34	1363
GF240-2-34N	1363
GF240-3-112	1363
GF240-3-112N	1363
GF240-3-2	1363
GF240-3-212	1363
GF240-3-212N	1363
GF240-3-2N	1363
GF240-34-12	1363
GF240-34-12N	1363
GF240-34-38	1363
GF240-34-38N	1363
GF240-38-14	1363
GF240-38-14N	1363
GF240-4-2	1363
GF240-4-212	1363
GF240-4-212N	1363
GF240-4-2N	1363
GF240-4-3	1363
GF240-4-3N	1363
GF241-1-12	1364
GF241-112-1	1364
GF241-112-114	1364
GF241-112-114N	1364
GF241-112-12	1364
GF241-112-12N	1364
GF241-112-1N	1364
GF241-112-34	1364
GF241-112-34N	1364
GF241-112-38	1364
GF241-112-38N	1364
GF241-1-12N	1364
GF241-1-14	1364
GF241-114-1	1364
GF241-114-12	1364
GF241-114-12N	1364
GF241-114-1N	1364
GF241-114-34	1364
GF241-114-34N	1364
GF241-114-38	1364
GF241-114-38N	1364
GF241-1-14N	1364
GF241-12-14	1364
GF241-12-14N	1364
GF241-12-18	1364
GF241-12-18N	1364
GF241-12-38	1364
GF241-12-38N	1364
GF241-1-34	1364
GF241-1-34N	1364
GF241-1-38	1364
GF241-1-38N	1364
GF241-14-18	1364
GF241-14-18N	1364
GF241-2-1	1364
GF241-2-112	1364
GF241-2-112N	1364
GF241-2-114	1364
GF241-2-114N	1364
GF241-2-12	1364
GF241-212-1	1364
GF241-212-112N	1364
GF241-212-114	1364
GF241-212-114N	1364
GF241-212-1N	1364
GF241-212-2	1364
GF241-212-2N	1364
GF241-2-12N	1364
GF241-2-1N	1364
GF241-2-34	1364
GF241-2-34N	1364
GF241-3-1	1364
GF241-3-112	1364
GF241-3-112N	1364
GF241-3-114	1364
GF241-3-114N	1364
GF241-3-1N	1364
GF241-3-2	1364
GF241-3-212	1364
GF241-3-212N	1364
GF241-3-2N	1364
GF241-34-12	1364
GF241-34-12N	1364
GF241-34-14	1364
GF241-34-14N	1364
GF241-34-38	1364
GF241-34-38N	1364
GF241-38-14	1364
GF241-38-14N	1364
GF241-38-18	1364
GF241-38-18N	1364
GF241-4-2	1364
GF241-4-212	1364
GF241-4-212N	1364
GF241-4-2N	1364
GF241-4-3	1364
GF241-4-3N	1364
GF241-6-4N	1364
GF245-1-12	1364
GF245-112-1	1364
GF245-112-114	1364
GF245-112-114N	1364
GF245-112-1N	1364
GF245-1-12N	1364
GF245-114-1	1364
GF245-114-1N	1364
GF245-114-34	1364
GF245-114-34N	1364
GF245-12-14	1364
GF245-12-14N	1364
GF245-12-38	1364
GF245-12-38N	1364
GF245-1-34	1364
GF245-1-34N	1364
GF245-14-18	1364
GF245-14-18N	1364
GF245-2-1	1364
GF245-2-112	1364
GF245-2-112N	1364
GF245-2-114	1364
GF245-2-114N	1364
GF245-2-1N	1364
GF245-3-2N	1364
GF245-34-12	1364
GF245-34-12N	1364
GF245-34-38	1364
GF245-34-38N	1364
GF245-38-14	1364
GF245-38-14N	1364
GF246-114-1	1365
GF246-114-1N	1365
GF246-1-34	1365
GF246-1-34N	1365
GF246-34-12N	1365
GF2-4N	1356
GF260-1-12	1365
GF260-112-1	1365
GF260-112-114	1365
GF260-112-114N	1365
GF260-112-1N	1365
GF260-1-12N	1365
GF260-114-1	1365
GF260-114-12	1365
GF260-114-12N	1365
GF260-114-1N	1365
GF260-114-34	1365
GF260-114-34N	1365
GF260-1-34	1365

Code	Page
GF260-1-34N	1365
GF260-2-1	1365
GF260-2-112	1365
GF260-2-112N	1365
GF260-2-114	1365
GF260-2-114N	1365
GF260-2-12	1365
GF260-2-12N	1365
GF260-2-1N	1365
GF260-34-12	1365
GF260-34-12N	1365
GF270-1	1365
GF270-112	1365
GF270-112N	1365
GF270-114	1365
GF270-114N	1365
GF270-12	1365
GF270-12N	1365
GF270-14	1365
GF270-14N	1365
GF270-18	1365
GF270-18N	1365
GF270-1N	1365
GF270-2	1365
GF270-212	1365
GF270-212N	1365
GF270-2N	1365
GF270-3	1365
GF270-34	1365
GF270-34N	1365
GF270-38	1365
GF270-38N	1365
GF270-3N	1365
GF270-4	1365
GF270-4N	1365
GF280-1	1366
GF280-112	1366
GF280-112N	1366
GF280-114	1366
GF280-114N	1366
GF280-12	1366
GF280-12N	1366
GF280-14	1366
GF280-14N	1366
GF280-18	1366
GF280-18N	1366
GF280-1N	1366
GF280-2	1366
GF280-212	1366
GF280-212N	1366
GF280-2N	1366
GF280-3	1366
GF280-34	1366
GF280-34N	1366
GF280-38	1366
GF280-38N	1366
GF280-3N	1366
GF280-4	1366
GF280-4N	1366
GF290-1	1366
GF290-112	1366
GF290-112N	1366
GF290-114	1366
GF290-114N	1366
GF290-12	1366
GF290-12N	1366
GF290-14	1366
GF290-14N	1366
GF290-1N	1366
GF290-2	1366
GF290-2N	1366
GF290-34	1366
GF290-34N	1366
GF290-38	1366
GF290-38N	1366
GF291-1	1366
GF291-112	1366
GF291-112N	1366
GF291-114	1366
GF291-114N	1366
GF291-12	1366
GF291-12N	1366
GF291-1N	1366
GF291-2	1366
GF291-212	1366
GF291-212N	1366
GF291-2N	1366
GF291-3	1366
GF291-34	1366
GF291-34N	1366
GF291-3N	1366
GF291-4	1366
GF291-4N	1366
GF291S-1	1367
GF291S-112	1367
GF291S-112N	1367
GF291S-114	1367
GF291S-114N	1367
GF291S-12	1367
GF291S-12N	1367
GF291S-14	1367
GF291S-14N	1367
GF291S-18N	1367
GF291S-1N	1367
GF291S-2	1367
GF291S-2N	1367
GF291S-34	1367
GF291S-34N	1367
GF291S-38	1367
GF2A-1	1357
GF2A-112	1357
GF2A-112N	1357
GF2A-114	1357
GF2A-114N	1357
GF2A-12	1357
GF2A-12N	1357
GF2A-14	1357
GF2A-14N	1357
GF2A-1N	1357
GF2A-2	1357
GF2A-212	1357
GF2A-212N	1357
GF2A-2N	1357
GF2A-3	1357
GF2A-34	1357
GF2A-34N	1357
GF2A-38	1357
GF2A-38N	1357
GF2A-3N	1357
GF2A-4	1357
GF2A-4N	1357
GF300-1	1367
GF300-112	1367
GF300-112N	1367
GF300-114	1367
GF300-114N	1367
GF300-12	1367
GF300-12N	1367
GF300-14	1367
GF300-14N	1367
GF300-1N	1367
GF300-2	1367
GF300-212	1367
GF300-212N	1367
GF300-2N	1367
GF300-3	1367
GF300-34	1367
GF300-34N	1367
GF300-38N	1367
GF300-3N	1367
GF300-4	1367
GF300-4N	1367
GF3-1	1357
GF3-112	1357
GF3-112N	1357
GF3-114	1357
GF3-114N	1357
GF3-12	1357
GF312-1	1367
GF312-112	1367
GF312-112N	1367
GF312-114	1367
GF312-114N	1367
GF312-12	1367
GF312-12N	1367
GF312-14N	1367
GF312-1N	1367
GF312-2	1367
GF312-2N	1367
GF312-34	1367
GF312-34N	1367
GF312-38	1367
GF3-12N	1357
GF3-1N	1357
GF3-2	1357
GF321-1	1367
GF321-112	1367
GF321-112N	1367
GF321-114	1367
GF321-114N	1367
GF321-12N	1367
GF321-1N	1367
GF321-2N	1367
GF321-34	1367
GF3-2N	1357
GF330-1	1368
GF330-112	1368
GF330-112N	1368
GF330-114	1368
GF330-114N	1368
GF330-12	1368
GF330-12N	1368
GF330-1N	1368
GF330-2	1368
GF330-2N	1368
GF330-34	1368
GF330-34N	1368
GF3-34	1357
GF3-34N	1357
GF340-1	1368
GF340-112	1368
GF340-112N	1368
GF340-114	1368
GF340-114N	1368
GF340-12	1368
GF340-12N	1368
GF340-14	1368
GF340-14N	1368
GF340-1N	1368
GF340-2	1368
GF340-212	1368
GF340-212N	1368
GF340-2N	1368
GF340-3	1368
GF340-34	1368
GF340-34N	1368
GF340-38	1368
GF340-38N	1368
GF340-4	1368
GF340-4N	1368
GF341-1	1368
GF341-112	1368
GF341-112N	1368
GF341-114	1368
GF341-114N	1368
GF341-12	1368
GF341-12N	1368
GF341-14	1368
GF341-14N	1368
GF341-1N	1368
GF341-2	1368
GF341-212	1368
GF341-2N	1368
GF341-3	1368
GF341-34	1368
GF341-34N	1368
GF341-38	1368
GF341-38N	1368
GF341-3N	1368
GF342-1	1369
GF342-112	1369
GF342-112N	1369
GF342-114	1369
GF342-114N	1369
GF342-12	1369
GF342-12N	1369
GF342-1N	1369
GF342-2	1369
GF342-2N	1369
GF342-34	1369
GF342-34N	1369
GF342A-1	1369
GF342A-112	1369
GF342A-112N	1369
GF342A-114	1369
GF342A-114N	1369
GF342A-12	1369
GF342A-12N	1369
GF342A-1N	1369
GF342A-2	1369
GF342A-2N	1369
GF342A-34	1369
GF342A-34N	1369
GF346-1	1369
GF346-112	1369
GF346-112N	1369
GF346-114	1369
GF346-114N	1369
GF346-12	1369
GF346-12N	1369
GF346-1N	1369
GF346-2	1369
GF346-2N	1369
GF346-34	1369
GF346-34N	1369
GF40-1	1357
GF40-112	1357
GF40-112N	1357
GF40-114	1357
GF40-114N	1357
GF40-12	1357
GF40-12N	1357
GF40-1N	1357
GF40-2	1357
GF40-2N	1357
GF40-34	1357
GF40-34N	1357
GF596-1	1368
GF596-112	1368
GF596-112N	1368
GF596-114	1368
GF596-114N	1368
GF596-12	1368
GF596-12N	1368
GF596-14	1368
GF596-14N	1368
GF596-1N	1368
GF596-2N	1368
GF596-34	1368
GF596-34N	1368
GF596-38	1368
GF596-38N	1368
GF60-1	1357
GF60-112	1357
GF60-112N	1357
GF60-114	1357
GF60-12	1357
GF60-12N	1357
GF60-1N	1357
GF60-2	1357
GF60-2N	1357
GF60-34	1357
GF60-34N	1357
GF90-1	1358
GF90-10-12	1358
GF90-10-12N	1358
GF90-112	1358
GF90-112N	1358
GF90-114	1358
GF90-114-1	1358

Code	Page
GF90-114-1N	1358
GF90-114N	1358
GF90-12	1358
GF90-12-14	1358
GF90-12-14N	1358
GF90-12-38	1358
GF90-12-38N	1358
GF90-12N	1358
GF90-1-34	1358
GF90-1-34N	1358
GF90-14	1358
GF90-14N	1358
GF90-18	1358
GF90-18N	1358
GF90-1N	1358
GF90-2	1358
GF90-212	1358
GF90-212N	1358
GF90-2N	1358
GF90-3	1358
GF90-34	1358
GF90-34-12	1358
GF90-34-12N	1358
GF90-34N	1358
GF90-38	1358
GF90-38-14N	1358
GF90-38N	1358
GF90-3N	1358
GF90-4	1358
GF90-4N	1358
GF90-5	1358
GF90-5N	1358
GF92-1	1358
GF92-112	1358
GF92-112N	1358
GF92-114	1358
GF92-114N	1358
GF92-12	1358
GF92-12N	1358
GF92-1-34	1358
GF92-1-34N	1358
GF92-14	1358
GF92-14N	1358
GF92-18	1358
GF92-18N	1358
GF92-1N	1358
GF92-2	1358
GF92-212	1358
GF92-212N	1358
GF92-2N	1358
GF92-3	1358
GF92-34	1358
GF92-34-12	1358
GF92-34-12N	1358
GF92-34N	1358
GF92-38	1358
GF92-38N	1358
GF92-3N	1358
GF92-4N	1358
GF94-1	1359
GF94-1N	1359
GF94-34	1359
GF94-34N	1359
GF96-1	1359
GF96-112	1359
GF96-112N	1359
GF96-114	1359
GF96-114N	1359
GF96-12	1359
GF96-12N	1359
GF96-1N	1359
GF96-2	1359
GF96-2N	1359
GF96-34	1359
GF96-34N	1359
GF98-1	1359
GF98-112	1359
GF98-112N	1359
GF98-114	1359
GF98-114N	1359
GF98-12	1359
GF98-12N	1359
GF98-1N	1359
GF98-2	1359
GF98-2N	1359
GF98-34N	1359
GFS080GM	104
GFS080GM-038	104
GFS080GU-038	104
GFS080SM	105
GFS080SM-038	105
GFS080SM-A20	105
GFS080STM	107
GFS080STM-038	107
GFS080STU	107
GFS080STU-038	107
GFS080SU	105
GFS080SU-038	105
GFS080SU-A20	105
GFS100GM	104
GFS100GM-012	104
GFS100GU	104
GFS100GU-012	104
GFS100SM	105
GFS100SM-A25	105
GFS100STM	107
GFS100STU	107
GFS100SU	105
GFS100SU-A25	105
GFS102GM	104
GFS102GM-034	104
GFS102GU	104
GFS102GU-034	104
GFS102SM	105
GFS102SM-A30	105
GFS102STM	107
GFS102STU	107
GFS102SU	105
GFS102SU-A30	105
GFS104GM	104
GFS104GM-100	104
GFS104GU	104
GFS104GU-100	104
GFS104SM	105
GFS104SM-A38	105
GFS104STM	107
GFS104STU	107
GFS104SU	105
GFS104SU-A38	105
GFS106GM	104
GFS106GM-114	104
GFS106GU	104
GFS106GU-114	104
GFS106SM	105
GFS106SM-A50	105
GFS106STM	107
GFS106STU	107
GFS106SU	105
GFS106SU-A50	105
GFS108GM	104
GFS108GM-112	104
GFS108GU	104
GFS108GU-112	104
GFS108S	105
GFS108STM	107
GFS108STU	107
GFS108SU	105
GFS110GM	104
GFS110GM-200	104
GFS110GU	104
GFS110GU-200	104
GFS110SM	105
GFS110STM	107
GFS110STU	107
GFS110SU	105
GFS112GM	104
GFS112GM-212	104
GFS112GU	104
GFS112GU-212	104
GFS112SM	105
GFS112STM	107
GFS112STU	107
GFS112SU	105
GFS114GM	104
GFS114GM-300	104
GFS114GU	104
GFS114GU-300	104
GFS114SM	105
GFS114STM	107
GFS114STU	107
GFS114SU	105
GFS116GM	104
GFS116GM-312	104
GFS116GU	104
GFS116GU-312	104
GFS116SM	105
GFS116STM	107
GFS116STU	107
GFS116SU	105
GFS401GM-012	104
GFS401GM-038	104
GFS401GU-012	104
GFS401GU-038	104
GFS401SM-012	105
GFS401SM-038	105
GFS401SM-A20	105
GFS401STM-012	107
GFS401STM-038	107
GFS401STU-012	107
GFS401STU-038	107
GFS401SU-012	105
GFS401SU-038	105
GFS401SU-A20	105
GFS402GM	104
GFS402GM-012	104
GFS402GU	104
GFS402GU-012	104
GFS402SM	105
GFS402SM-A25	105
GFS402STM	107
GFS402STU	107
GFS402SU	105
GFS402SU-A25	105
GFS403GM	104
GFS403GU	104
GFS403SM	105
GFS403SM-A30	105
GFS403STM	107
GFS403STU	107
GFS403SU	105
GFS403SU-A30	105
GFS404GM	104
GFS404GM-100	104
GFS404GU	104
GFS404GU-100	104
GFS404SM	105
GFS404SM-A38	105
GFS404STM	107
GFS404STU	107
GFS404SU	105
GFS404SU-A38	105
GFS405GM	104
GFS405GM-114	104
GFS405GU	104
GFS405GU-114	104
GFS405SM	105
GFS405SM-A50	105
GFS405STM	107
GFS405STU	107
GFS405SU	105
GFS405SU-A50	105
GFS406GM	104
GFS406GM-112	104
GFS406GU	104
GFS406GU-112	104
GFS406SM	105
GFS406STM	107
GFS406STU	107
GFS406SU	105
GFS407SM	105
GFV10L35	135
GFV12L35	135
GFV15L35	135
GFV15L40	135
GFV16L35	135
GFV18L40	135
GFV20S55	135
GFV22L40	135
GFV28L40	135
GG08B3C25050	475
GGWH-1/4-25	1418
GGWH-3/8-25	1418
GH12	1422
GH12-100	1422
GH12-50	1422
GH19	1422
GH19-100	1422
GH19-50	1422
GH203	755
GH25	1422
GH25-100	1422
GH252	755
GH253	755
GH25-50	1422
GH302	755
GHL302	755
GI1414	249
GJS-1	1481
GJS-112	1481
GJS-114	1481
GJS-12	1481
GJS-2	1481
GJS-34	1481
GK 125	510
GK 160 200	510
GK 25 32	510
GK 40	510
GK 50 63	510
GK 80 100	510
GK-3Y	1475
GKA10	1479
GKA12	1479
GKA14	1479
GKA15	1479
GKA34	1479
GKA38	1479
GKA54	1479
GK-AW21	1475
GK-AW26	1475
GK-AW33	1475
GK-AW42	1475
GK-AW50	1475
GK-BC	1475
GKD2	1389
GKD3	1389
GK-GASKET	1475
GKI10	1479
GKI12	1479
GKI14	1479
GKI15	1479
GKI34	1479
GKI38	1479
GKI54	1479
GKIBCNP162	1389
GKIBCNP163	1389
GKIBCNP164	1389
GKIBCNP166	1389
GK-IW21	1475
GK-IW26	1475
GK-IW33	1475
GK-IW42	1475
GK-IW50	1475
GKNP163	1389
GKNP166	1389
GKO	1479
GKOR	1479
GK-SP34	1475
GK-TF13	1475
GK-TF19	1475
GK-TF25	1475

Code	Page
GK-TF31	1475
GK-TF38	1475
GL800C-1	976
GL800C-112	976
GL800C-112S	976
GL800C-114	976
GL800C-114S	976
GL800C-12	976
GL800C-12S	976
GL800C-1S	976
GL800C-2	976
GL800C-2S	976
GL800C-34	976
GL800C-34S	976
GL800S-1	976
GL800S-112	976
GL800S-112S	976
GL800S-114	976
GL800S-114S	976
GL800S-12	976
GL800S-12S	976
GL800S-1S	976
GL800S-2	976
GL800S-2S	976
GL800S-34	976
GL800S-34S	976
GM-27	648
GM38	1475
GMAMF1122	1490
GMAMF112212	1490
GMAMF1123	1490
GMAMF2112	1490
GMAMF2122	1490
GMAMF212212	1490
GMAMF2123	1490
GMAMF2212	1490
GMAMF23	1490
GMAMF32	1490
GMAMF3212	1490
GMAMF33	1490
GMAMF34	1490
GMAMF43	1490
GMAMFURTURT34	1490
GMAMM212212	1490
GMAMM22	1490
GMAMM33	1490
GMAMMBSPURT33	1490
GMBCC112	1489
GMBCC2	1489
GMBCC212	1489
GMBCCBSP3	1489
GMBCCBSP4	1489
GMBCCURT3	1489
GMCT3URT	1488
GMCT4URT	1488
GMDSLLC2-6M	1427
GMDSLLC3312-6M	1427
GMDSLLC4-6M	1427
GMDSLLC6-6M	1427
GMDSLLC8-6M	1427
GMF2110QIVPKG164	248
GMF2210QIVPKG164	248
GMF3110QIVPKG244	248
GMF3210QIVPKG244	248
GMF321-112-10	248
GMF4110QIVPKG324	248
GMF411-2-10	248
GMF4210QIVPKG324	248
GMS-1	1481
GMS-112	1481
GMS-114	1481
GMS-12	1481
GMS-2	1481
GMS-34	1481
GN0245N	1644
GN0290N	1644
GN02N	1644
GN0445N	1644
GN0490N	1644
GN04N	1644
GN172AHHS	700
GN174BHHS	700
GNM6	1644
GNM645	1644
GNM690	1644
GNM8	1644
GNM845	1644
GNM890	1644
GNTH02N	1644
GNTH04N	1644
GNU04	1644
GNU0445	1644
GNU0490	1644
GO04/04	1154
GO06/04	1154
GO06/05	1154
GO06/06	1154
GOER	1477
GOOR	1476
GP-025-0100B	1553
GP-025-0100N	1553
GP-025-0200B	1553
GP-025-0200N	1553
GP-036-0140B	1553
GP-036-0140N	1553
GP-036-0200B	1553
GP-036-0200N	1553
GP-036-0300B	1553
GP-036-0300N	1553
GP-048-0120B	1553
GP-048-0120N	1553
GP-048-0160B	1553
GP-048-0160N	1553
GP-048-0200B	1553
GP-048-0200N	1553
GP-048-0300B	1553
GP-048-0300N	1553
GP-048-0368B	1553
GP-048-0368N	1553
GP-076-0200B	1553
GP-076-0200N	1553
GP-076-0240B	1553
GP-076-0240N	1553
GP-076-0300B	1553
GP-076-0300N	1553
GP-076-0368B	1553
GP-076-0368N	1553
GP-090-0430B	1553
GP-090-0430N	1553
GP-090-0530B	1553
GP-090-0530N	1553
GP60015PP	1134
GP60022PP	1134
GP60028PP	1134
GP60035PP	1134
GP60042PP	1134
GP60054PP	1134
GP73ME31.000	1054
GP73PE31.000	1054
GPE1-12	230
GPE1-38	230
GPE2-12	230
GPE2-34	230
GPOR	1477
GR.AGUNC	1642
GR.AM12.5C	1642
GR.AM50C	1642
GR.ASWIVC	1642
GR.ASWIVS	1642
GR.BFILL.L	1642
GR.FU	1642
GR.G3HV	1642
GR.G6HV	1642
GR.GGFILL.L	1642
GR.H12.L	1642
GR.PGS	1642
GR-10L-6L	151
GR-10L-8L	151
GR-10S-6S	151
GR-10S-8S	151
GR-12L-10L	151
GR-12L-6L	151
GR-12L-8L	151
GR-12S-10S	151
GR-12S-6S	151
GR-12S-8S	151
GR-14S-10S	151
GR-14S-12S	151
GR-14S-6S	151
GR-14S-8S	151
GR-15L-10L	151
GR-15L-12L	151
GR-15L-6L	151
GR-15L-8L	151
GR-16S-10S	151
GR-16S-12S	151
GR-16S-14S	151
GR-16S-6S	151
GR-16S-8S	151
GR-18L-10L	151
GR-18L-12L	151
GR-18L-15L	151
GR-18L-8L	151
GR-20S-10S	151
GR-20S-12S	151
GR-20S-14S	151
GR-20S-16S	151
GR-20S-6S	151
GR-20S-8S	151
GR-22L-10L	151
GR-22L-12L	151
GR-22L-15L	151
GR-22L-18L	151
GR-22L-8L	151
GR-25S-10S	151
GR-25S-12S	151
GR-25S-14S	151
GR-25S-16S	151
GR-25S-20S	151
GR-25S-8S	151
GR-28L-10L	151
GR-28L-12L	151
GR-28L-15L	151
GR-28L-18L	151
GR-28L-22L	151
GR-30S-10S	151
GR-30S-12S	151
GR-30S-14S	151
GR-30S-16S	151
GR-30S-20S	151
GR-30S-25S	151
GR-35L-15L	151
GR-35L-18L	151
GR-35L-22L	151
GR-35L-28L	151
GR-38S-10S	151
GR-38S-12S	151
GR-38S-14S	151
GR-38S-16S	151
GR-38S-20S	151
GR-38S-25S	151
GR-38S-30S	151
GR-42L-15L	151
GR-42L-18L	151
GR-42L-22L	151
GR-42L-28L	151
GR-42L-35L	151
GR-8L-6L	151
GR-8S-6S	151
GRD2	1389
GRD3	1389
GRD4	1389
GRD6	1389
GRD8	1389
GRI-12-16RG	148
GRI-12-20RG	148
GRI-12-24RG	148
GRI-12-2RG	148
GRI-12-4RG	148
GRI-12-6RG	148
GRI-12-8RG	148
GRI-16-12RG	148
GRI-16-20RG	148
GRI-16-24RG	148
GRI-16-4RG	148
GRI-16-6RG	148
GRI-16-8RG	148
GRI-20-12RG	148
GRI-20-16RG	148
GRI-20-24RG	148
GRI-20-6RG	148
GRI-20-8RG	148
GRI-24-12RG	148
GRI-24-16RG	148
GRI-24-20RG	148
GRI-24-8RG	148
GRI-2-4RG	148
GRI-2-6RG	148
GRI-32-12RG	148
GRI-32-16RG	148
GRI-32-20RG	148
GRI-32-24RG	148
GRI-32-8RG	148
GRI-4-12RG	148
GRI-4-2RG	148
GRI-4-6RG	148
GRI-4-8RG	148
GRI-6-12RG	148
GRI-6-16RG	148
GRI-6-2RG	148
GRI-6-4RG	148
GRI-6-8RG	148
GRI-8-12RG	148
GRI-8-16RG	148
GRI-8-20RG	148
GRI-8-2RG	148
GRI-8-4RG	148
GRI-8-6RG	148
GRIBCNP162	1389
GRIBCNP163	1389
GRIBCNP164	1389
GRIBCNP166	1389
GRIBCNP168	1389
GRNP162	1389
GRNP163	1389
GRNP164	1389
GRNP166	1389
GRNP168	1389
GS 10 L	133
GS 10 S	133
GS 12 L	133
GS 12 S	133
GS 14 S	133
GS 15 L	133
GS 16 S	133
GS 18 L	133
GS 20 S	133
GS 22 L	133
GS 25 S	133
GS 28 L	133
GS 30 S	133
GS 35 L	133
GS 38 S	133
GS 42 L	133
GS 6 L	133
GS 6 S	133
GS 8 L	133
GS 8 S	133
GS112-150	1390
GS112-300	1390
GS114-150	1390
GS1-150	1390
GS12-150	1390
GS12-300	1390
GS1-300	1390
GS203	755
GS212-150	1390
GS2-150	1390
GS252	755
GS253	755

Code	Page
GS302	755
GS3-150	1390
GS3-300	1390
GS34-150	1390
GS-40	648
GS4-150	1390
GS-50	648
GSE-102	1434
GSE-102-10	1434
GSE-152	1434
GSE-152-10	1434
GSE-51	1434
GSE-51-10	1434
GSE-63	1434
GSE-63-10	1434
GSE-76	1434
GSE-76-10	1434
GSFF112-150	1390
GSFF114-150	1390
GSFF1-150	1390
GSFF12-150	1390
GSFF1-300	1390
GSFF16-1	1390
GSFF16-112	1390
GSFF16-114	1390
GSFF16-12	1390
GSFF16-2	1390
GSFF16-212	1390
GSFF16-3	1390
GSFF16-4	1390
GSFF212-150	1390
GSFF2-150	1390
GSFF2-300	1390
GSFF3-150	1390
GSFF40-1	1390
GSFF40-112	1390
GSFF40-2	1390
GSFF40-4	1390
GSK10	1479
GSK13	1479
GSK16	1479
GSK19	1479
GSK25	1479
GSK32	1479
GSK38	1479
GSL302	755
GSP-1	1481
GSP-112	1481
GSP-114	1481
GSP-2	1481
GSP-34	1481
GSPN16-1	1390
GSPN16-112	1390
GSPN16-114	1390
GSPN16-2	1390
GSPN16-212	1390
GSPN16-3	1390
GSPN16-34	1390
GSPN16-4	1390
GSPN40-2	1390
GSPN40-3	1390
GSS 10 L	133
GSS 10 S	133
GSS 12 L	133
GSS 12 S	133
GSS 14 S	133
GSS 15 L	133
GSS 16 S	133
GSS 18 L	133
GSS 20 S	133
GSS 22 L	133
GSS 25 S	133
GSS 28 L	133
GSS 30 S	133
GSS 35 L	133
GSS 38 S	133
GSS 42 L	133
GSS 6 L	133
GSS 6 S	133
GSS 8 L	133
GSS 8 S	133
GSV10L	125
GSV10S	125
GSV12L	125
GSV12S	125
GSV14S	125
GSV15L	125
GSV16S	125
GSV18L	125
GSV20S	125
GSV22L	125
GSV25S	125
GSV28L	125
GSV30S	125
GSV35L	125
GSV38S	125
GSV42L	125
GSV6L	125
GSV6S	125
GSV8L	125
GSV8S	125
GT05/03	1142
GT05/04	1142
GT06/04	1142
GT10	626
GT10/04	1142
GT10/04K	1141
GT10/04KNP	1141
GT10/05	1142
GT10/05K	1141
GT10/05KNP	1141
GT10/06	1142
GT10/06K	1141
GT10/06KNP	1141
GT10/08	1142
GT10/08K	1141
GT10/08KNP	1141
GT10/09	1142
GT10/09K	1141
GT10/09KNP	1141
GT10/13K	1141
GT13	626
GT13/04	1142
GT13/04K	1141
GT13/04KNP	1141
GT13/05	1142
GT13/05K	1141
GT13/05KNP	1141
GT13/06	1142
GT13/06K	1141
GT13/06KNP	1141
GT13/08	1142
GT13/08K	1141
GT13/08KNP	1141
GT13/09	1142
GT13/09K	1141
GT13/09KNP	1141
GT13/13	1142
GT13/13K	1141
GT13/13KNP	1141
GT13/16K	1141
GT13/16KNP	1141
GT13/19K	1141
GT16	626
GT17/05K	1141
GT17/05KNP	1141
GT17/06	1142
GT17/06K	1141
GT17/06KNP	1141
GT17/08	1142
GT17/08K	1141
GT17/08KNP	1141
GT17/09	1142
GT17/09K	1141
GT17/09KNP	1141
GT17/13	1142
GT17/13K	1141
GT17/13KNP	1141
GT17/16	1142
GT17/16K	1141
GT17/16KNP	1141
GT17/19	1142
GT17/19K	1141
GT17/19KNP	1141
GT171BHH	700
GT172BHH	700
GT172BHHS	700
GT173BHH	700
GT173BHHS	700
GT20	626
GT21/05K	1141
GT21/06	1142
GT21/06K	1141
GT21/06KNP	1141
GT21/08	1142
GT21/08K	1141
GT21/08KNP	1141
GT21/09	1142
GT21/09K	1141
GT21/09KNP	1141
GT21/13	1142
GT21/13K	1141
GT21/13KNP	1141
GT21/16	1142
GT21/16K	1141
GT21/16KNP	1141
GT21/19	1142
GT21/19K	1141
GT21/19KNP	1141
GT21/25	1142
GT21/25K	1141
GT21/25KNP	1141
GT23/16K	1141
GT25	626
GT26/06	1142
GT26/06K	1141
GT26/08	1142
GT26/08K	1141
GT26/09K	1141
GT26/09KNP	1141
GT26/10	1142
GT26/13	1142
GT26/13K	1141
GT26/13KNP	1141
GT26/16	1142
GT26/16K	1141
GT26/16KNP	1141
GT26/19	1142
GT26/19K	1141
GT26/19KNP	1141
GT26/25	1142
GT26/25K	1141
GT26/25KNP	1141
GT26/31K	1141
GT30	626
GT33/13	1142
GT33/13K	1141
GT33/13KNP	1141
GT33/16K	1141
GT33/19	1142
GT33/19K	1141
GT33/19KNP	1141
GT33/25	1142
GT33/25K	1141
GT33/25KNP	1141
GT33/31K	1141
GT33/31KNP	1141
GT33/32	1142
GT33/38K	1141
GT33/38KNP	1141
GT38	1475
GT4	626
GT42/19K	1141
GT42/25	1142
GT42/25K	1141
GT42/25KNP	1141
GT42/31K	1141
GT42/31KNP	1141
GT42/32	1142
GT42/38	1142
GT48/31K	1141
GT48/38	1142
GT48/38K	1141
GT48/38KNP	1141
GT48/50K	1141
GT48/50KNP	1141
GT52/38K	1141
GT52/38KNP	1141
GT52/50	1142
GT52/50K	1141
GT52/50KNP	1141
GT56/53K	1141
GT58	1475
GT6	626
GT60/58K	1141
GT8	626
GTB-12-10	261
GTB-12-25	261
GTB-20-10	261
GTB-20-25	261
GTLC1	1475
GTLC12	1475
GTLC34	1475
GV10/6L	125
GV10/8L	125
GV-10L	125
GV10S	125
GV12/10L	125
GV12/6L	125
GV12/8L	125
GV12-1	957
GV12-112	957
GV12-114	957
GV12-12	957
GV12-2	957
GV12-212	957
GV12-3	957
GV12-34	957
GV12-38	957
GV12-4	957
GV-12L	125
GV12S	125
GV14S	125
GV15/10L	125
GV15/12L	125
GV157-1	957
GV157-112	957
GV157-114	957
GV157-12	957
GV157-2	957
GV157-212	957
GV157-3	957
GV157-34	957
GV157-38	957
GV-15L	125
GV16/12S	125
GV16S	125
GV18/10L	125
GV18/12L	125
GV18/15L	125
GV-18L	125
GV20/16S	125
GV20S	125
GV22/15L	125
GV22/18L	125
GV-22L	125
GV25/16S	125
GV25/20S	125
GV25S	125
GV-28L	125
GV30S	125
GV-35L	125
GV38S	125
GV-42L	125
GV4LL	125
GV6/4LL	125
GV-6L	125
GV6LL	125
GV6S	125
GV8/6L	125

Code	Page
GV-8L	125
GV8LL	125
GV8S	125
GVBZ375LS-1	958
GVBZ375LS-112	958
GVBZ375LS-114	958
GVBZ375LS-12	958
GVBZ375LS-2	958
GVBZ375LS-34	958
GV-DKOL-06	160
GV-DKOL-08	160
GV-DKOL-10	160
GV-DKOL-12	160
GV-DKOL-15	160
GV-DKOL-18	160
GV-DKOL-22	160
GV-DKOL-28	160
GV-DKOL-35	160
GV-DKOL-42	160
GV-DKOS-06	160
GV-DKOS-08	160
GV-DKOS-10	160
GV-DKOS-12	160
GV-DKOS-14	160
GV-DKOS-16	160
GV-DKOS-20	160
GV-DKOS-25	160
GV-DKOS-30	160
GV-DKOS-38	160
GVOR	1477
GVR-DKO-06L/06S	160
GVR-DKO-08L/06L	160
GVR-DKO-08L/06S	160
GVR-DKO-08L/08S	160
GVR-DKO-08S/06S	160
GVR-DKO-10L/06L	160
GVR-DKO-10L/08L	160
GVR-DKO-10L/10S	160
GVR-DKO-10S/06S	160
GVR-DKO-10S/08L	160
GVR-DKO-10S/08S	160
GVR-DKO-12L/06L	160
GVR-DKO-12L/08L	160
GVR-DKO-12L/10L	160
GVR-DKO-12L/10S	160
GVR-DKO-12L/12S	160
GVR-DKO-12S/06S	160
GVR-DKO-12S/08L	160
GVR-DKO-12S/08S	160
GVR-DKO-12S/10L	160
GVR-DKO-12S/10S	160
GVR-DKO-15L/08L	160
GVR-DKO-15L/10L	160
GVR-DKO-15L/12L	160
GVR-DKO-15L/12S	160
GVR-DKO-15L/14S	160
GVR-DKO-16S/10L	160
GVR-DKO-16S/10S	160
GVR-DKO-16S/12L	160
GVR-DKO-16S/12S	160
GVR-DKO-16S/14S	160
GVR-DKO-16S/15L	160
GVR-DKO-18L/10L	160
GVR-DKO-18L/12L	160
GVR-DKO-18L/15L	160
GVR-DKO-18L/16S	160
GVR-DKO-20S/12S	160
GVR-DKO-20S/14S	160
GVR-DKO-20S/16S	160
GVR-DKO-20S/18L	160
GVR-DKO-22L/12L	160
GVR-DKO-22L/15L	160
GVR-DKO-22L/18L	160
GVR-DKO-22L/20S	160
GVR-DKO-25S/16S	160
GVR-DKO-25S/18L	160
GVR-DKO-25S/20S	160
GVR-DKO-25S/22L	160
GVR-DKO-28L/15L	160
GVR-DKO-28L/18L	160
GVR-DKO-28L/22L	160
GVR-DKO-28L/25S	160
GVR-DKO-30S/16S	160
GVR-DKO-30S/20S	160
GVR-DKO-30S/25S	160
GVR-DKO-30S/28L	160
GVR-DKO-35L/18L	160
GVR-DKO-35L/22L	160
GVR-DKO-35L/28L	160
GVR-DKO-35L/30S	160
GVR-DKO-38S/20S	160
GVR-DKO-38S/25S	160
GVR-DKO-38S/30S	160
GVR-DKO-38S/35L	160
GVR-DKO-42L/22L	160
GVR-DKO-42L/28L	160
GVR-DKO-42L/35L	160
GVR-DKO-42L/38S	160
GWH-1/4-10	1418
GWH-1/4-100B	1418
GWH-1/4-100R	1418
GWH-1/4-15	1418
GWH-1/4-250	1418
GWH-1/4-25B	1418
GWH-1/4-25R	1418
GWH-1/4-50-TWIN	1418
GWH-3/8-10	1418
GWH-3/8-100B	1418
GWH-3/8-100R	1418
GWH-3/8-15	1418
GWH-3/8-250	1418
GWH-3/8-25B	1418
GWH-3/8-25R	1418
GWH-3/8-50-TWIN	1418
GWH-5/16-10	1418
GWH-5/16-100B	1418
GWH-5/16-100R	1418
GWH-5/16-15	1418
GWH-5/16-250	1418
GWH-5/16-25B	1418
GWH-5/16-25R	1418
GWH-5/16-50-TWIN	1418
GY 32	510
GY 40	510
GY 50 63	510
GY 80 100	510
H	
H 41 32	511
H 41 40	511
H 41 50	511
H 60 63	511
H0076	1710
H0077	1710
H0503	275
H0505	275
H0507	275
H0509	275
H10 1021-14	1005
H10 1021-38	1005
H10 1070-12	1006
H10 1070-14	1006
H10 1070-34	1006
H10 1070-38	1006
H10 1071-12	1006
H10 1071-14	1006
H10 1071-34	1006
H10 1071-38	1006
H10 6400-1	1005
H10 6400-114	1005
H10 6400-12	1005
H10 6400-34	1005
H1001	275
H1002	275
H1004	275
H1006	275
H1008	275
H1010	275
H1012	275
H1014	275
H1501	275
H1502	275
H1504	275
H1506	275
H1508	275
H1510	275
H1512	275
H1514	275
H1-62-BSPP	310
H1-63-BSPP	310
H1-65	310
H1-65M	310
H1-66	310
H1-66M	310
H2501	275
H2502	275
H2504	275
H2506	275
H2508	275
H2510	275
H2512	275
H2514	275
H2-62-BSPP	310
H2-63-BSPP	310
H2-65	310
H2-65M	310
H2-66	310
H2-66M	310
H2852 110	1059
H2852 160	1059
H2852 200	1059
H2856-1	1059
H2856-112	1059
H2856-114	1059
H2856-12	1059
H2856-2	1059
H2856-212	1059
H2856-34	1059
H3-62-BSPP	310
H3-63-BSPP	310
H3-65	310
H3-65M	310
H3-66	310
H3-66M	310
H4-62-BSPP	310
H4-63-BSPP	310
H4-65	310
H4-65M	310
H4-66	310
H4-66M	310
H5502	275
H5504	275
H5506	275
H5510	275
H5513	275
H6-62-BSPP	310
H6-63-BSPP	310
H6-65	310
H6-65M	310
H6-66	310
H6-66M	310
H8512 10-1/2-V	874
H8512 10-1/4-V	874
H8512 10-1/8-V	874
H8512 10-3/8-V	874
H8512 12-1/2-V	874
H8512 12-1/4-V	874
H8512 12-3/8-V	874
H8512 14-1/2-V	874
H8512 14-3/8-V	874
H8512 16-1/2-V	874
H8512 16-3/8-V	874
H8512 4-1/8-V	874
H8512 6-1/4-V	874
H8512 6-1/8-V	874
H8512 8-1/4-V	874
H8512 8-1/8-V	874
H8512 8-3/8-V	874
H8522 10-1/2-V	874
H8522 10-1/4-V	874
H8522 10-1/8-V	874
H8522 10-3/8-V	874
H8522 12-1/2-V	874
H8522 12-1/4-V	874
H8522 12-3/8-V	874
H8522 14-1/2-V	874
H8522 14-3/8-V	874
H8522 4-1/8-V	874
H8522 6-1/4 -V	874
H8522 6-1/8-V	874
H8522 8-1/4-V	874
H8522 8-1/8-V	874
H8522 8-3/8-V	874
H8540 10-V	874
H8540 12-V	874
H8540 14-V	874
H8540 4-V	874
H8540 6-V	874
H8540 8-V	874
H8550 10-V	874
H8550 12-V	874
H8550 14-V	874
H8550 4-V	874
H8550 6-V	874
H8550 8-V	874
H8580 10-V	874
H8580 12-V	874
H8580 14-V	874
H8580 4-V	874
H8580 6-V	874
H8580 8-V	874
H8-62-BSPP	310
H8-63-BSPP	310
H8-65	310
H8-65M	310
H8-66	310
H8-66M	310
H940070-1	1547
H940090-1	1547
H940130-1	1547
H940155-1	1547
H940190-1	1547
H940230-1	1547
H940260-1	1547
H940285-1	1547
H940310-1	1547
HANDYFIT-4	823
HANDYFIT-6	823
HANDYFIT-6/8	823
HANDYFIT-8	823
HANG.P	1620
HBBVSS-1	242
HBBVSS-12	242
HBBVSS-12-LK	242
HBBVSS-14	242
HBBVSS-14-LK	242
HBBVSS-1-LK	242
HBBVSS-34	242
HBBVSS-34-LK	242
HBBVSS-38	242
HBBVSS-38-LK	242
HBC-1	1184
HBC-112	1184
HBC-114	1184
HBC-12	1184
HBC-14	1184
HBC-18	1184
HBC-2	1184
HBC-212	1184
HBC-3	1184
HBC-34	1184
HBC-38	1184
HBC-4	1184
HBN1-100	1380
HBN1-120	1380
HBN112-100	1380
HBN112-120	1380
HBN112-150	1380
HBN112-180	1380
HBN112-200	1380
HBN112-300	1380

Code	Page
HBN112-80	1380
HBN114-100	1380
HBN114-120	1380
HBN114-150	1380
HBN114-200	1380
HBN114-250	1380
HBN114-300	1380
HBN114-80	1380
HBN1-150	1380
HBN1-180	1380
HBN1-200	1380
HBN12-100	1380
HBN12-120	1380
HBN12-150	1380
HBN12-180	1380
HBN12-200	1380
HBN12-250	1380
HBN12-30	1380
HBN12-300	1380
HBN12-40	1380
HBN12-50	1380
HBN12-60	1380
HBN12-80	1380
HBN1-300	1380
HBN14-100	1380
HBN14-120	1380
HBN14-150	1380
HBN14-180	1380
HBN14-200	1380
HBN14-250	1380
HBN14-300	1380
HBN14-40	1380
HBN14-60	1380
HBN14-80	1380
HBN1-50	1380
HBN1-60	1380
HBN1-70	1380
HBN1-80	1380
HBN18-100	1380
HBN18-40	1380
HBN18-60	1380
HBN18-80	1380
HBN2-120	1380
HBN212-100	1380
HBN212-200	1380
HBN212-300	1380
HBN2-150	1380
HBN2-180	1380
HBN2-250	1380
HBN2-300	1380
HBN2-80	1380
HBN3-100	1380
HBN3-200	1380
HBN3-300	1380
HBN34-100	1380
HBN34-120	1380
HBN34-150	1380
HBN34-180	1380
HBN34-200	1380
HBN34-250	1380
HBN34-300	1380
HBN34-40	1380
HBN34-60	1380
HBN34-70	1380
HBN34-80	1380
HBN38-100	1380
HBN38-120	1380
HBN38-150	1380
HBN38-180	1380
HBN38-200	1380
HBN38-40	1380
HBN38-50	1380
HBN38-60	1380
HBN38-70	1380
HBN38-80	1380
HBN4-100	1380
HBN4-200	1380
HBN4-300	1380
HBVC04	245
HBVC06	245
HBVC08	245
HBVC12	245
HBVF04	245
HBVF06	245
HBVF08	245
HBVF12	245
HBVF16	245
HBVMF04	245
HBVMF06	245
HBVMF08	245
HBVMF12	245
HBVMF16	245
HBVSS-1	242
HBVSS-12	242
HBVSS-14	242
HBVSS-34	242
HBVSS-38	242
HC0100A-00-17	227
HC0200A-00-17	227
HC0400A-00-17	227
HC1	1516
HC100-120	1513
HC10-16	1513
HC110-130	1513
HC120-140	1513
HC12-20	1513
HC130-150	1513
HC140-160	1513
HC16-25	1513
HC20-32	1513
HC25-40	1513
HC32-50	1513
HC35-45	1513
HC40-60	1513
HC50-70	1513
HC60-80	1513
HC70-90	1513
HC80-100	1513
HC8-12	1513
HC90-110	1513
HCKIT01	1154
HC-KIT-MS	1516
HC-KIT-SS	1516
HCL10-10	1421
HCL12-10	1421
HCL15-13	1421
HCL22-19	1421
HCL8-6	1421
HCMINI-KIT-MS	1516
HCMINI-KIT-SS	1516
HCP143	1520
HCP143SS	1520
HCP143SS316	1520
HCS12	1513
HCS16	1513
HCS20	1513
HCS25	1513
HCS32	1513
HCS40	1513
HCS50	1513
HCS60	1513
HCS70	1513
HCVSS-1	242
HCVSS-1/2	242
HCVSS-3/4	242
HCVSS-3/8	242
HD.000	1480
HD.001	1480
HD.002	1480
HD.003	1480
HD.004	1480
HD.005	1480
HD.006	1480
HD.007	1480
HD.1	1480
HD.2	1480
HD.3	1480
HD.5	1480
HD.6	1480
HD.7	1480
HD.9	1480
HDA 1021-14	993
HDA 1021-38	993
HDA 1070-1	994
HDA 1070-112	994
HDA 1070-114	994
HDA 1070-12	994
HDA 1070-14	994
HDA 1070-2	994
HDA 1070-34	994
HDA 1070-38	994
HDA 1071-1	994
HDA 1071-112	994
HDA 1071-114	994
HDA 1071-12	994
HDA 1071-14	994
HDA 1071-2	994
HDA 1071-34	994
HDA 1071-38	994
HDA 150HIT 04	1000
HDA 150HIT 05	1000
HDA 150HIT 06	1000
HDA 150HIT 07	1000
HDA 150HIT 08	1000
HDA 150HIT 09	1000
HDA 150HIT 10	1000
HDA 150HIT 11	1000
HDA 150HIT 12	1000
HDA 150HIT 13	1000
HDA 150HIT 14	1000
HDA 150HIT 16	1000
HDA 2006SD-1	994
HDA 2006SD-112	994
HDA 2006SD-114	994
HDA 2006SD-12	994
HDA 2006SD-14	994
HDA 2006SD-2	994
HDA 2006SD-34	994
HDA 2006SD-38	994
HDA 2011KMD-1	996
HDA 2011KMD-112	996
HDA 2011KMD-114	996
HDA 2011KMD-12	996
HDA 2011KMD-2	996
HDA 2011KMD-34	996
HDA 2011ND-1	995
HDA 2011ND-112	995
HDA 2011ND-114	995
HDA 2011ND-12	995
HDA 2011ND-2	995
HDA 2011ND-212	995
HDA 2011ND-3	995
HDA 2011ND-34	995
HDA 2011ND-4	995
HDA 2012CD-1	998
HDA 2012CD-112	998
HDA 2012CD-12	998
HDA 2012CD-2	998
HDA 2012CD-212	998
HDA 2012CD-3	998
HDA 2012CD-34	998
HDA 2012CD-4	998
HDA 2012KMD-1	996
HDA 2012KMD-112	996
HDA 2012KMD-12	996
HDA 2012KMD-2	996
HDA 2012KMD-34	996
HDA 2012ND-1	995
HDA 2012ND-112	995
HDA 2012ND-114	995
HDA 2012ND-12	995
HDA 2012ND-2	995
HDA 2012ND-212	995
HDA 2012ND-3	995
HDA 2012ND-34	995
HDA 2012ND-4	995
HDA 2013CD-1	998
HDA 2013CD-112	998
HDA 2013CD-12	998
HDA 2013CD-2	998
HDA 2013CD-212	998
HDA 2013CD-3	998
HDA 2013CD-34	998
HDA 2013CD-4	998
HDA 2013KMD-1	996
HDA 2013KMD-112	996
HDA 2013KMD-112C	996
HDA 2013KMD-114	996
HDA 2013KMD-114C	996
HDA 2013KMD-12	996
HDA 2013KMD-12C	996
HDA 2013KMD-1C	996
HDA 2013KMD-2	996
HDA 2013KMD-212	996
HDA 2013KMD-212C	996
HDA 2013KMD-2C	996
HDA 2013KMD-3	996
HDA 2013KMD-34	996
HDA 2013KMD-34C	996
HDA 2013KMD-3C	996
HDA 2013ND-1	995
HDA 2013ND-112	995
HDA 2013ND-114	995
HDA 2013ND-12	995
HDA 2013ND-14	995
HDA 2013ND-2	995
HDA 2013ND-212	995
HDA 2013ND-3	995
HDA 2013ND-34	995
HDA 2013ND-38	995
HDA 2013ND-4	995
HDA 2014LA 08	1003
HDA 2014LA 09	1003
HDA 2014LA 10	1003
HDA 2014LA 11	1003
HDA 2014LA 12	1003
HDA 2014LA 13	1003
HDA 2014LA 14	1003
HDA 2014LA 16	1003
HDA 2014LA 18	1003
HDA 2014LA 20	1003
HDA 2014LB 08	1003
HDA 2014LB 09	1003
HDA 2014LB 10	1003
HDA 2014LB 11	1003
HDA 2014LB 12	1003
HDA 2014LB 13	1003
HDA 2014LB 14	1003
HDA 2014LB 16	1003
HDA 2014LB 18	1003
HDA 2014LB 20	1003
HDA 2014WA 08	1002
HDA 2014WA 09	1002
HDA 2014WA 10	1002
HDA 2014WA 11	1002
HDA 2014WA 12	1002
HDA 2014WA 13	1002
HDA 2014WA 14	1002
HDA 2014WA 16	1002
HDA 2014WA 18	1002
HDA 2014WA 20	1002
HDA 2014WB 08	1002
HDA 2014WB 09	1002
HDA 2014WB 10	1002
HDA 2014WB 11	1002
HDA 2014WB 12	1002
HDA 2014WB 13	1002
HDA 2014WB 14	1002
HDA 2014WB 16	1002
HDA 2014WB 18	1002
HDA 2014WB 20	1002
HDA 2014WC 09	1002
HDA 2014WC 10	1002
HDA 2014WC 11	1002
HDA 2014WC 12	1002
HDA 2014WC 13	1002
HDA 2014WC 14	1002
HDA 2014WC 16	1002
HDA 2014WC 18	1002
HDA 2014WC 20	1002

Code	Page
HDA 2014WD 09	1002
HDA 2014WD 10	1002
HDA 2014WD 11	1002
HDA 2014WD 12	1002
HDA 2014WD 13	1002
HDA 2014WD 14	1002
HDA 2014WD 16	1002
HDA 2014WD 18	1002
HDA 2014WD 20	1002
HDA 2014WP 09	1003
HDA 2014WP 10	1003
HDA 2014WP 11	1003
HDA 2014WP 12	1003
HDA 2014WP 13	1003
HDA 2014WP 14	1003
HDA 2014WP 16	1003
HDA 2014WP 18	1003
HDA 2014WP 20	1003
HDA 2019D 04	999
HDA 2019D 05	999
HDA 2019D 06	999
HDA 2019D 07	999
HDA 2019D 08	999
HDA 2019D 09	999
HDA 2019D 10	999
HDA 2019D 11	999
HDA 2019D 12	999
HDA 2019D 13	999
HDA 2019D 14	999
HDA 2019D 16	999
HDA 2019D4 10	999
HDA 2019D4 11	999
HDA 2019D4 12	999
HDA 2020D 04	1000
HDA 2020D 05	1000
HDA 2020D 06	1000
HDA 2020D 07	1000
HDA 2020D 08	1000
HDA 2020D 09	1000
HDA 2020D 10	1000
HDA 2020D 11	1000
HDA 2020D 12	1000
HDA 2020D 14	1000
HDA 2040-1	997
HDA 2040-112	997
HDA 2040-114	997
HDA 2040-12	997
HDA 2040-14	997
HDA 2040-2	997
HDA 2040-212	997
HDA 2040-34	997
HDA 2040-38	997
HDA 2041-1	997
HDA 2041-112	997
HDA 2041-114	997
HDA 2041-12	997
HDA 2041-14	997
HDA 2041-2	997
HDA 2041-212	997
HDA 2041-34	997
HDA 2041-38	997
HDA 2057CBL-1	998
HDA 2057CBL-112	998
HDA 2057CBL-12	998
HDA 2057CBL-2	998
HDA 2057CBL-212	998
HDA 2057CBL-3	998
HDA 2057CBL-4	998
HDA 2057CBT-1	998
HDA 2057CBT-112	998
HDA 2057CBT-12	998
HDA 2057CBT-2	998
HDA 2057CBT-212	998
HDA 2057CBT-3	998
HDA 2057CBT-4	998
HDA 2059DL150 04	1001
HDA 2059DL150 06	1001
HDA 2059DL150 08	1001
HDA 2059DL150 09	1001
HDA 2059DL150 11	1001
HDA 2059DL150 12	1001
HDA 2059DL150 14	1001
HDA 2059DL16 04	1001
HDA 2059DL16 06	1001
HDA 2059DL16 08	1001
HDA 2059DL16 09	1001
HDA 2059DL16 10	1001
HDA 2059DL16 11	1001
HDA 2059DL16 12	1001
HDA 2059DL16 14	1001
HDA 2059DT150 04	1001
HDA 2059DT150 06	1001
HDA 2059DT150 08	1001
HDA 2059DT150 09	1001
HDA 2059DT150 11	1001
HDA 2059DT150 12	1001
HDA 2059DT150 14	1001
HDA 2059DT16 04	1001
HDA 2059DT16 06	1001
HDA 2059DT16 08	1001
HDA 2059DT16 09	1001
HDA 2059DT16 10	1001
HDA 2059DT16 11	1001
HDA 2059DT16 12	1001
HDA 2059DT16 14	1001
HDA 6400-1	993
HDA 6400-112	993
HDA 6400-114	993
HDA 6400-12	993
HDA 6400-2	993
HDA 6400-34	993
HDAWH12	1422
HDAWH34	1422
HDOP-100	280
HDPVC1	1405
HDPVC112	1405
HDPVC114	1405
HDPVC12	1405
HDPVC12B	1405
HDPVC12N	1405
HDPVC12R	1405
HDPVC12Y	1405
HDPVC14	1405
HDPVC14B	1405
HDPVC14N	1405
HDPVC14R	1405
HDPVC2	1405
HDPVC34	1405
HDPVC34B	1405
HDPVC34N	1405
HDPVC38	1405
HDPVC38B	1405
HDPVC38N	1405
HDPVC38R	1405
HDPVC38Y	1405
HDPVC516	1405
HDPVC516B	1405
HDPVC516N	1405
HDPVC516Y	1405
HDPVC58	1405
HDSH2-10	1428
HDSH2-30	1428
HDSH3-10	1428
HDSH3-30	1428
HDSH4-10	1428
HDSH4-30	1428
HDSH6-10	1428
HDSH6-30	1428
HDSHS-104112	1515
HDSHS-113121	1515
HDSHS-122130	1515
HDSHS-131139	1515
HDSHS-140148	1515
HDSHS-149161	1515
HDSHS-162174	1515
HDSHS-1719	1515
HDSHS-175187	1515
HDSHS-188200	1515
HDSHS-201213	1515
HDSHS-2022	1515
HDSHS-214226	1515
HDSHS-227239	1515
HDSHS-2325	1515
HDSHS-240252	1515
HDSHS-2628	1515
HDSHS-2931	1515
HDSHS-3235	1515
HDSHS-3639	1515
HDSHS-4043	1515
HDSHS-4447	1515
HDSHS-4851	1515
HDSHS-5255	1515
HDSHS-5659	1515
HDSHS-6063	1515
HDSHS-6467	1515
HDSHS-6873	1515
HDSHS-7479	1515
HDSHS-8085	1515
HDSHS-8691	1515
HDSHS-9297	1515
HDSHS-98103	1515
HELD	1625
HELD.500	1625
HEP-1	1483
HESV-06	230
HESV-08	230
HEXSMBV1	946
HEXSMBV12	946
HEXSMBV12M	946
HEXSMBV14	946
HEXSMBV14M	946
HEXSMBV1M	946
HEXSMBV34	946
HEXSMBV34M	946
HEXSMBV38	946
HEXSMBV38M	946
HF0503B	277
HF1005B	277
HF1275	1556
HF2005B	277
HF3005B	277
HF3588	1556
HF5006B	277
HF7244	1556
HF7322	1556
HF7325	1556
HF7326	1556
HF7327	1556
HF7328	1556
HF7329	1556
HF7330	1556
HF7331	1556
HF7332	1556
HF7333	1556
HFBFC9810	294
HFBFC98112	294
HFBFC98114	294
HFBFC9834	294
HFBFP9810	294
HFBFP98112	294
HFBFP98114	294
HFBFP9834	294
HFL3-08-08CF	24
HFL3-08-12CF	24
HFL3-10-12CF	24
HFL3-12-12CF	24
HFL3-12-16CF	24
HFL3-16-16CF	24
HFL3-16-20CF	24
HFL3-20-20CF	24
HFL3-20-24CF	24
HFL3-24-24CF	24
HFL3-24-32CF	24
HFL3-32-32CF	24
HFL345-12-12CF	24
HFL345-16-12CF	24
HFL345-16-16CF	24
HFL345-16-20CF	24
HFL345-20-20CF	24
HFL345-20-24CF	24
HFL345-24-24CF	24
HFL345-24-32CF	24
HFL345-32-32CF	24
HFL390-08-08CF	24
HFL390-08-12CF	24
HFL390-12-12CF	24
HFL390-12-16CF	24
HFL390-16-16CF	24
HFL390-16-20CF	24
HFL390-20-20CF	24
HFL390-20-24CF	24
HFL390-24-24CF	24
HFL390-24-32CF	24
HFL390-32-32CF	24
HFL6-08-08CF	24
HFL6-12-12CF	24
HFL6-12-16CF	24
HFL6-16-16CF	24
HFL6-16-20CF	24
HFL6-20-20CF	24
HFL6-20-24CF	24
HFL6-24-24CF	24
HFL6-32-32CF	24
HFL645-08-08CF	24
HFL645-08-12CF	24
HFL645-12-12CF	24
HFL645-12-16CF	24
HFL645-16-16CF	24
HFL645-16-20CF	24
HFL645-20-20CF	24
HFL645-20-24CF	24
HFL645-24-24CF	24
HFL645-32-32CF	24
HFL690-08-08CF	24
HFL690-08-12CF	24
HFL690-12-12CF	24
HFL690-12-16CF	24
HFL690-16-16CF	24
HFL690-16-20CF	24
HFL690-20-20CF	24
HFL690-20-24CF	24
HFL690-24-24CF	24
HFL690-32-32CF	24
HFP-01	230
HFSFC-14-DP	294
HFSFC-38-DP	294
HFSFC6512	292
HFSFC6518	292
HFSFC6522	292
HFSFC6538	292
HFSFC8814	294
HFSFC8838	294
HFSFP-14-DC	294
HFSFP-38-DC	294
HFSFP6512	292
HFSFP6518	292
HFSFP6522	292
HFSFP6538	292
HFSFP8814	294
HFSFP8838	294
HFSSFC7310-V	290
HFSSFC7312-V	290
HFSSFC7314-V	290
HFSSFC7334-V	290
HFSSFC7338-V	290
HFSSFP7310-V	290
HFSSFP7312-V	290
HFSSFP7314-V	290
HFSSFP7334-V	290
HFSSFP7338-V	290
HG100-002B	267
HG100-002G	267
HG100-004B	267
HG100-004G	267
HG100-006B	267
HG100-006G	267
HG100-010B	267
HG100-010G	267
HG100-016B	267
HG100-016G	267

Code	Page
HG100-040B	267
HG100-040G	267
HG100-100B	267
HG100-100G	267
HG100-160B	267
HG100-160G	267
HG100-250B	267
HG100-250G	267
HG100-400B	267
HG100-400G	267
HGSAB1	1531
HGU020-0100	497
HGU020-0200	497
HGU020-0250	497
HGU020-0320	497
HGU020-0400	497
HGU020-0500	497
HGU032-0100	497
HGU032-0200	497
HGU032-0250	497
HGU032-0320	497
HGU032-0400	497
HGU032-0500	497
HGU040-0100	497
HGU040-0200	497
HGU040-0250	497
HGU040-0320	497
HGU040-0400	497
HGU040-0500	497
HGU050-0100	497
HGU050-0200	497
HGU050-0250	497
HGU050-0320	497
HGU050-0400	497
HGU050-0500	497
HGU063-0100	497
HGU063-0200	497
HGU063-0250	497
HGU063-0320	497
HGU063-0400	497
HGU063-0500	497
HGZAB1	1531
HHP-01	229
HHP-02	229
HHP-03	229
HHP-04	229
HHP-05	230
HHPDV-06	230
HHPDV-08	230
HHPDV-12	230
HHP-OL	230
HHPT-01	230
HHPT-02	230
HHPT-03	230
HHPT-05	230
HHPT-07	230
HJ0404CF	23
HJ0505CF	23
HJ0606CF	23
HJ0808CF	23
HJ1010CF	23
HJ1212CF	23
HJ1616CF	23
HKP02B	291
HKP02B-V	291
HKP02SS	291
HKP02SS-V	291
HKP04B	291
HKP04B-V	291
HKP04CS	291
HKP04CS-NPT	291
HKP04SS	291
HKP04SS-NPT	291
HKP04SS-V	291
HKP06B	291
HKP06B-V	291
HKP06CS	291
HKP06CS-NPT	291
HKP06SS	291
HKP06SS-NPT	291
HKP06SS-V	291
HKP08B	291
HKP08B-V	291
HKP08CS	291
HKP08CS-NPT	291
HKP08SS	291
HKP08SS-NPT	291
HKP08SS-V	291
HKP12B	291
HKP12B-V	291
HKP12CS	291
HKP12CS-NPT	291
HKP12SS	291
HKP12SS-NPT	291
HKP12SS-V	291
HKP16B	291
HKP16B-V	291
HKP16CS	291
HKP16CS-NPT	291
HKP16SS	291
HKP16SS-NPT	291
HKP16SS-V	291
HKPA04CS	290
HKPA04CS-NPT	290
HKPA04CS-V	290
HKPA04SS-NPT	290
HKPA06CS	290
HKPA06CS-NPT	290
HKPA06CS-V	290
HKPA06SS-NPT	290
HKPA08CS	290
HKPA08CS-NPT	290
HKPA08CS-V	290
HKPA08SS-NPT	290
HKPA12CS	290
HKPA12CS-NPT	290
HKPA12CS-V	290
HKPA12SS-NPT	290
HKPA16CS	290
HKPA16CS-NPT	290
HKPA16CS-V	290
HKPA16SS-NPT	290
HKPA20CS	290
HKPA20CS-NPT	290
HKPA20CS-V	290
HKPA24CS	290
HKPA24CS-NPT	290
HKPA24CS-V	290
HKPA32CS	290
HKPA32CS-NPT	290
HKPA32CS-V	290
HKPFF04CS	292
HKPFF0608CS	292
HKPFF06CS	292
HKPFF08CS	292
HKPFF1212CS	292
HKPFF12CS	292
HKPFF1616CS	292
HKPFF16CS	292
HKPFF2016CS	292
HKS02B	291
HKS02B-V	291
HKS02CS-NPT	291
HKS02SS	291
HKS02SS-V	291
HKS04B	291
HKS04B-V	291
HKS04CS	291
HKS04CS-NPT	291
HKS04SS	291
HKS04SS-NPT	291
HKS04SS-V	291
HKS06B	291
HKS06B-V	291
HKS06CS	291
HKS06CS-NPT	291
HKS06SS	291
HKS06SS-NPT	291
HKS06SS-V	291
HKS08B	291
HKS08B-V	291
HKS08CS	291
HKS08CS-NPT	291
HKS08SS	291
HKS08SS-NPT	291
HKS08SS-V	291
HKS12B	291
HKS12B-V	291
HKS12CS	291
HKS12CS-NPT	291
HKS12SS	291
HKS12SS-NPT	291
HKS12SS-V	291
HKS16B	291
HKS16B-V	291
HKS16CS	291
HKS16CS-NPT	291
HKS16SS	291
HKS16SS-NPT	291
HKS16SS-V	291
HKSA04CS	290
HKSA04CS-V	290
HKSA04SS-NPT	290
HKSA06CS	290
HKSA06CS-NPT	290
HKSA06CS-V	290
HKSA06SS-NPT	290
HKSA08CS	290
HKSA08CS-NPT	290
HKSA08CS-V	290
HKSA08SS-NPT	290
HKSA12CS	290
HKSA12CS-NPT	290
HKSA12CS-V	290
HKSA12SS-NPT	290
HKSA16CS	290
HKSA16CS-NPT	290
HKSA16CS-V	290
HKSA16SS-NPT	290
HKSA20CS	290
HKSA20CS-V	290
HKSA24CS	290
HKSA24CS-NPT	290
HKSA24CS-V	290
HKSA32CS	290
HKSA32CS-NPT	290
HKSA32CS-V	290
HKSFF04CS	292
HKSFF0608CS	292
HKSFF06CS	292
HKSFF08CS	292
HKSFF1212CS	292
HKSFF12CS	292
HKSFF1616CS	292
HKSFF16CS	292
HKSFF2016CS	292
HL-1001-D	277
HM10	432
HM18	432
HM30	432
HM34	432
HMBV-1	923
HMBV-112	923
HMBV-114	923
HMBV-12	923
HMBV-14	923
HMBV-2	923
HMBV-212	923
HMBV-3	923
HMBV-34	923
HMBV-38	923
HMBV-4	923
HMFL03-45-M12CF	20
HMFL0390-M12CF	20
HMFL03-M12CF	20
HMFL04-45-M12CF	20
HMFL04-45-M14CF	20
HMFL04-45-M16CF	20
HMFL0490-M12CF	20
HMFL0490-M14CF	20
HMFL0490-M16CF	20
HMFL0490-M18CF	20
HMFL04-M12CF	20
HMFL04-M14CF	20
HMFL04-M16CF	20
HMFL04-M18CF	20
HMFL05-45-M16CF	20
HMFL05-45-M18CF	20
HMFL0590-M18CF	20
HMFL05-M16CF	20
HMFL06-45-M16CF	20
HMFL06-45-M18CF	20
HMFL0690-M16CF	20
HMFL0690-M18CF	20
HMFL06-M16CF	20
HMFL06-M18CF	20
HMFL06-M22CF	20
HMFL08-45-M22CF	20
HMFL08-45-M26CF	20
HMFL0890-M22CF	20
HMFL0890-M26CF	20
HMFL08-M22CF	20
HMFL08-M26CF	20
HMFL10-45-M26CF	20
HMFL1090-M26CF	20
HMFL1090-M30CF	20
HMFL10-M26CF	20
HMFL10-M30CF	20
HMFL12-45-M30CF	20
HMFL1290-M26CF	20
HMFL1290-M30CF	20
HMFL12-M30CF	20
HMFL12-M36CF	20
HMFL16-45-M36CF	20
HMFL1690-M36CF	20
HMFL16-M36CF	20
HMFL20-45-M45CF	20
HMFL2090-M45CF	20
HMFL20-M45CF	20
HMFL24-45-M52CF	20
HMFL2490-M52CF	20
HMFL24-M52CF	20
HMFS03-45-M16CF	21
HMFS0390-M16CF	21
HMFS03-M16CF	21
HMFS04-45-M14CF	21
HMFS04-45-M16CF	21
HMFS04-45-M18CF	21
HMFS0490-M14CF	21
HMFS0490-M16CF	21
HMFS0490-M18CF	21
HMFS0490-M20CF	21
HMFS04-M14CF	21
HMFS04-M16CF	21
HMFS04-M18CF	21
HMFS05-45-M18CF	21
HMFS05-45-M20CF	21
HMFS0590-M18CF	21
HMFS0590-M20CF	21
HMFS05-M18CF	21
HMFS05-M20CF	21
HMFS06-45-M20CF	21
HMFS06-45-M22CF	21
HMFS0690-M18CF	21
HMFS0690-M20CF	21
HMFS0690-M22CF	21
HMFS06-M16CF	21
HMFS06-M18CF	21
HMFS06-M20CF	21
HMFS06-M22CF	21
HMFS08-45-M24CF	21
HMFS0890-M24CF	21
HMFS08-M22CF	21
HMFS08-M24CF	21
HMFS08-M30CF	21
HMFS10-45-M30CF	21
HMFS1090-M24CF	21
HMFS1090-M30CF	21
HMFS10-M24CF	21
HMFS10-M30CF	21

Code	Page
HMFS12-45-M30CF	21
HMFS12-45-M36CF	21
HMFS1290-M30CF	21
HMFS1290-M36CF	21
HMFS12-M30CF	21
HMFS12-M36CF	21
HMFS16-45-M36CF	21
HMFS16-45-M42CF	21
HMFS1690-M36CF	21
HMFS1690-M42CF	21
HMFS16-M36CF	21
HMFS16-M42CF	21
HMFS20-45-M52CF	21
HMFS2090-M52CF	21
HMFS20-M52CF	21
HMFS24-45-M52CF	21
HMFS2490-M52CF	21
HMFS24-M52CF	21
HMML03-M12CF	20
HMML04-M12CF	20
HMML04-M14CF	20
HMML04-M16CF	20
HMML04-M18CF	20
HMML05-M14CF	20
HMML05-M16CF	20
HMML05-M18CF	20
HMML05-M22CF	20
HMML06-M16CF	20
HMML06-M18CF	20
HMML06-M22CF	20
HMML08-M18CF	20
HMML08-M22CF	20
HMML08-M26CF	20
HMML10-M22CF	20
HMML10-M26CF	20
HMML10-M30CF	20
HMML12-M26CF	20
HMML12-M30CF	20
HMML16-M36CF	20
HMML20-M45CF	20
HMML24-M45CF	20
HMML24-M52CF	20
HMMS03-M16CF	21
HMMS04-M14CF	21
HMMS04-M16CF	21
HMMS04-M18CF	21
HMMS05-M18CF	21
HMMS05-M20CF	21
HMMS06-M18CF	21
HMMS06-M20CF	21
HMMS06-M22CF	21
HMMS06-M24CF	21
HMMS08-M24CF	21
HMMS10-M30CF	21
HMMS12-M30CF	21
HMMS12-M36CF	21
HMMS16-M36CF	21
HMMS16-M42CF	21
HMMS20-M42CF	21
HMMS20-M52CF	21
HMMS24-M52CF	21
HN-1	1183
HN-112	1183
HN-114	1183
HN-12	1183
HN-14	1183
HN-18	1183
HN-2	1183
HN-212	1183
HN-3	1183
HN-34	1183
HN-38	1183
HN-4	1183
HN50-1212-UPVC	1107
HN50-1616-UPVC	1107
HN50-2020-UPVC	1107
HN50-2525-UPVC	1107
HN50-3232-UPVC	1107
HN50-5050-UPVC	1107
HN50-6060-UPVC	1107
HN63-112-UPVC	1111
HN63-114-UPVC	1111
HN63-12-UPVC	1111
HN63-1-UPVC	1111
HN63-2-UPVC	1111
HN63-34-UPVC	1111
HN64-11230-UPVC	1111
HN64-11425-UPVC	1111
HN64-120-UPVC	1111
HN64-21450-UPVC	1111
HN64-23460-UPVC	1111
HN64-240-UPVC	1111
HN64-3416-UPVC	1111
HNRV-1	243
HNRV-12	243
HNRV-14	243
HNRV-34	243
HNRV-38	243
HOA200	1459
HOP200	1459
HOSE17/06MM/10M	1409
HOSE17/06MM/3M	1409
HOSE17/06MM/5M	1409
HOSE17/10MM/10M	1409
HOSE17/10MM/3M	1409
HOSE17/10MM/5M	1409
HOSE17/12MM/10M	1409
HOSE17/12MM/3M	1409
HOSE17/12MM/5M	1409
HOSE19/06MM/10M	1409
HOSE19/06MM/3M	1409
HOSE19/06MM/5M	1409
HOSE19/10MM/10M	1409
HOSE19/10MM/3M	1409
HOSE19/10MM/5M	1409
HOSE19/12MM/10M	1409
HOSE19/12MM/3M	1409
HOSE19/12MM/5M	1409
HOSE25/06MM/10M	1409
HOSE25/06MM/3M	1409
HOSE25/06MM/5M	1409
HOSE25/10MM/10M	1409
HOSE25/10MM/3M	1409
HOSE25/10MM/5M	1409
HOSE25/12MM/10M	1409
HOSE25/12MM/3M	1409
HOSE25/12MM/5M	1409
HOSE97/06MM/10M	1409
HOSE97/06MM/3M	1409
HOSE97/06MM/5M	1409
HOSE97/10MM/10M	1409
HOSE97/10MM/3M	1409
HOSE97/10MM/5M	1409
HOSE97/12MM/10M	1409
HOSE97/12MM/3M	1409
HOSE97/12MM/5M	1409
HOSEMAND-1	16
HOSEMAND-12	16
HOSEMAND-14	16
HOSEMAND-34	16
HOSEMAND-38	16
HOSEMAND-58	16
HPSUC17	1634
HPSUC2	1634
HPSUC6	1634
HP/SB4/6	1748
HP-1	1184
HP100MS	1519
HP100SS	1519
HP-112	1184
HP-114	1184
HP-12	1184
HP-14	1184
HP-18	1184
HP-2	1184
HP-212	1184
HP-3	1184
HP-34	1184
HP-38	1184
HPA1619100	250
HPA1719100	250
HPA1819100	250
HPBVLD-1	242
HPBVLD-2	242
HPBVLD-3	242
HPGO	1634
HPLFH1-10	1425
HPLFH1-100	1425
HPLFH112-10	1425
HPLFH112-100	1425
HPLFH114-10	1425
HPLFH114-100	1425
HPLFH2-10	1425
HPLFH2-100	1425
HPLFH212-10	1425
HPLFH212-100	1425
HPLFH3-10	1425
HPLFH3-100	1425
HPLFH4-10	1425
HPLFH4-100	1425
HPLP	1637
HPPFF00608CS	293
HPPFF01212CS	293
HPPFF04CS	293
HPPFF06CS	293
HPPFF08CS	293
HPPFF12CS	293
HPPFF1616CS	293
HPPFF16CS	293
HPPFF2016CS	293
HPR1619	250
HPR1719	250
HPR1819	250
HPS205	1632
HPS25	1632
HPSB	1632
HPSFF00608CS	293
HPSFF01212CS	293
HPSFF04CS	293
HPSFF06CS	293
HPSFF08CS	293
HPSFF12CS	293
HPSFF1616CS	293
HPSFF16CS	293
HPSFF2016CS	293
HPW	1632
HR5-320B	1454
HR8-315B	1454
HRCT12	1144
HRO15.12C	1460
HRO8.25	1460
HS-1	1185
HS-112	1185
HS-114	1185
HS-12	1185
HS-14	1185
HS-18	1185
HS-2	1185
HS-212	1185
HS2T-10-N-50	45
HS2T-10-R-50	45
HS2T-13-N-50	45
HS2T-13-R-50	45
HS2T-16-N-50	45
HS2T-16-R-50	45
HS2T-19-N-50	45
HS2T-19-R-50	45
HS2T-25-N-30	45
HS2T-25-R-30	45
HS2T-38-N-30	45
HS2T-38-R-30	45
HS2T-51-N-30	45
HS2T-51-R-30	45
HS2T-6-N-50	45
HS2T-6-R-50	45
HS2T-8-N-50	45
HS2T-8-R-50	45
HS-3	1185
HS-34	1185
HS-38	1185
HS-4	1185
HSA 1021-14	993
HSA 1021-38	993
HSA 1070-1	994
HSA 1070-112	994
HSA 1070-114	994
HSA 1070-12	994
HSA 1070-14	994
HSA 1070-2	994
HSA 1070-34	994
HSA 1070-38	994
HSA 1071-1	994
HSA 1071-112	994
HSA 1071-114	994
HSA 1071-12	994
HSA 1071-14	994
HSA 1071-2	994
HSA 1071-34	994
HSA 1071-38	994
HSA 150HIT 04	1000
HSA 150HIT 05	1000
HSA 150HIT 06	1000
HSA 150HIT 07	1000
HSA 150HIT 08	1000
HSA 150HIT 09	1000
HSA 150HIT 10	1000
HSA 150HIT 11	1000
HSA 150HIT 12	1000
HSA 150HIT 13	1000
HSA 150HIT 14	1000
HSA 150HIT 16	1000
HSA 2006SD-1	994
HSA 2006SD-112	994
HSA 2006SD-114	994
HSA 2006SD-12	994
HSA 2006SD-14	994
HSA 2006SD-2	994
HSA 2006SD-34	994
HSA 2006SD-38	994
HSA 2011KMD-1	996
HSA 2011KMD-112	996
HSA 2011KMD-114	996
HSA 2011KMD-12	996
HSA 2011KMD-2	996
HSA 2011KMD-34	996
HSA 2011ND-1	995
HSA 2011ND-112	995
HSA 2011ND-114	995
HSA 2011ND-12	995
HSA 2011ND-2	995
HSA 2011ND-212	995
HSA 2011ND-3	995
HSA 2011ND-34	995
HSA 2011ND-38	995
HSA 2011ND-4	995
HSA 2012CD-1	998
HSA 2012CD-112	998
HSA 2012CD-12	998
HSA 2012CD-2	998
HSA 2012CD-212	998
HSA 2012CD-3	998
HSA 2012CD-34	998
HSA 2012CD-4	998
HSA 2012KMD-1	996
HSA 2012KMD-112	996
HSA 2012KMD-12	996
HSA 2012KMD-2	996
HSA 2012KMD-34	996
HSA 2012ND-1	995
HSA 2012ND-112	995
HSA 2012ND-114	995
HSA 2012ND-12	995
HSA 2012ND-2	995
HSA 2012ND-212	995
HSA 2012ND-3	995
HSA 2012ND-34	995
HSA 2012ND-4	995
HSA 2013CD-1	998
HSA 2013CD-112	998
HSA 2013CD-12	998

Code	Page
HSA 2013CD-2	998
HSA 2013CD-212	998
HSA 2013CD-3	998
HSA 2013CD-34	998
HSA 2013CD-4	998
HSA 2013KMD-1	996
HSA 2013KMD-112	996
HSA 2013KMD-112C	996
HSA 2013KMD-114	996
HSA 2013KMD-114C	996
HSA 2013KMD-12	996
HSA 2013KMD-12C	996
HSA 2013KMD-1C	996
HSA 2013KMD-2	996
HSA 2013KMD-212	996
HSA 2013KMD-212C	996
HSA 2013KMD-2C	996
HSA 2013KMD-3	996
HSA 2013KMD-34	996
HSA 2013KMD-34C	996
HSA 2013KMD-3C	996
HSA 2013ND-1	995
HSA 2013ND-112	995
HSA 2013ND-114	995
HSA 2013ND-12	995
HSA 2013ND-14	995
HSA 2013ND-2	995
HSA 2013ND-212	995
HSA 2013ND-3	995
HSA 2013ND-34	995
HSA 2013ND-38	995
HSA 2013ND-4	995
HSA 2014LA 08	1003
HSA 2014LA 09	1003
HSA 2014LA 10	1003
HSA 2014LA 11	1003
HSA 2014LA 12	1003
HSA 2014LA 13	1003
HSA 2014LA 14	1003
HSA 2014LA 16	1003
HSA 2014LA 18	1003
HSA 2014LA 20	1003
HSA 2014LB 08	1003
HSA 2014LB 09	1003
HSA 2014LB 10	1003
HSA 2014LB 11	1003
HSA 2014LB 12	1003
HSA 2014LB 13	1003
HSA 2014LB 14	1003
HSA 2014LB 16	1003
HSA 2014LB 18	1003
HSA 2014LB 20	1003
HSA 2014WA 08	1002
HSA 2014WA 09	1002
HSA 2014WA 10	1002
HSA 2014WA 11	1002
HSA 2014WA 12	1002
HSA 2014WA 13	1002
HSA 2014WA 14	1002
HSA 2014WA 16	1002
HSA 2014WA 18	1002
HSA 2014WA 20	1002
HSA 2014WB 08	1002
HSA 2014WB 09	1002
HSA 2014WB 10	1002
HSA 2014WB 11	1002
HSA 2014WB 12	1002
HSA 2014WB 13	1002
HSA 2014WB 14	1002
HSA 2014WB 16	1002
HSA 2014WB 18	1002
HSA 2014WB 20	1002
HSA 2014WC 09	1002
HSA 2014WC 10	1002
HSA 2014WC 11	1002
HSA 2014WC 12	1002
HSA 2014WC 13	1002
HSA 2014WC 14	1002
HSA 2014WC 16	1002
HSA 2014WC 18	1002
HSA 2014WC 20	1002
HSA 2014WD 09	1002
HSA 2014WD 10	1002
HSA 2014WD 11	1002
HSA 2014WD 12	1002
HSA 2014WD 13	1002
HSA 2014WD 14	1002
HSA 2014WD 16	1002
HSA 2014WD 18	1002
HSA 2014WD 20	1002
HSA 2014WP 09	1003
HSA 2014WP 10	1003
HSA 2014WP 11	1003
HSA 2014WP 12	1003
HSA 2014WP 13	1003
HSA 2014WP 14	1003
HSA 2014WP 16	1003
HSA 2014WP 18	1003
HSA 2014WP 20	1003
HSA 2019D 04	999
HSA 2019D 05	999
HSA 2019D 06	999
HSA 2019D 07	999
HSA 2019D 08	999
HSA 2019D 09	999
HSA 2019D 10	999
HSA 2019D 11	999
HSA 2019D 12	999
HSA 2019D 13	999
HSA 2019D 14	999
HSA 2019D 16	999
HSA 2019D4 10	999
HSA 2019D4 11	999
HSA 2019D4 12	999
HSA 2020D 04	1000
HSA 2020D 05	1000
HSA 2020D 06	1000
HSA 2020D 07	1000
HSA 2020D 08	1000
HSA 2020D 09	1000
HSA 2020D 10	1000
HSA 2020D 11	1000
HSA 2020D 12	1000
HSA 2020D 14	1000
HSA 2040-1	997
HSA 2040-112	997
HSA 2040-114	997
HSA 2040-12	997
HSA 2040-14	997
HSA 2040-2	997
HSA 2040-212	997
HSA 2040-34	997
HSA 2040-38	997
HSA 2041-1	997
HSA 2041-112	997
HSA 2041-114	997
HSA 2041-12	997
HSA 2041-14	997
HSA 2041-2	997
HSA 2041-212	997
HSA 2041-34	997
HSA 2041-38	997
HSA 2057CBL-1	998
HSA 2057CBL-112	998
HSA 2057CBL-12	998
HSA 2057CBL-2	998
HSA 2057CBL-212	998
HSA 2057CBL-3	998
HSA 2057CBL-4	998
HSA 2057CBT-1	998
HSA 2057CBT-112	998
HSA 2057CBT-12	998
HSA 2057CBT-2	998
HSA 2057CBT-212	998
HSA 2057CBT-3	998
HSA 2057CBT-4	998
HSA 2059DL150 04	1001
HSA 2059DL150 06	1001
HSA 2059DL150 08	1001
HSA 2059DL150 09	1001
HSA 2059DL150 11	1001
HSA 2059DL150 12	1001
HSA 2059DL150 14	1001
HSA 2059DL16 04	1001
HSA 2059DL16 06	1001
HSA 2059DL16 08	1001
HSA 2059DL16 09	1001
HSA 2059DL16 10	1001
HSA 2059DL16 11	1001
HSA 2059DL16 12	1001
HSA 2059DL16 14	1001
HSA 2059DT150 04	1001
HSA 2059DT150 06	1001
HSA 2059DT150 08	1001
HSA 2059DT150 09	1001
HSA 2059DT150 11	1001
HSA 2059DT150 12	1001
HSA 2059DT150 14	1001
HSA 2059DT16 04	1001
HSA 2059DT16 06	1001
HSA 2059DT16 08	1001
HSA 2059DT16 09	1001
HSA 2059DT16 10	1001
HSA 2059DT16 11	1001
HSA 2059DT16 12	1001
HSA 2059DT16 14	1001
HSA 6400-1	993
HSA 6400-112	993
HSA 6400-114	993
HSA 6400-12	993
HSA 6400-2	993
HSA 6400-34	993
HSBVCE-1	952
HSBVCE-2	952
HSBVWE-112	952
HSBVWE-12	952
HSBVWE-2	952
HS-G1/2	34
HS-G1/4	34
HS-G1/8	34
HS-G3/4	34
HS-G3/8	34
HS-M10X1	34
HS-M12X1.5	34
HS-M14X1.5	34
HS-M16X1.5	34
HS-M18X1.5	34
HS-M22X1.5	34
HS-M26X1.5	34
HSP04-45-06CF	20
HSP04-90-06CF	20
HSP04-90-08CF	20
HSP05-45-08CF	20
HSP05-45-10CF	20
HSP06-45-08CF	20
HSP06-45-10CF	20
HSP06-45-12CF	20
HSP06-45-15CF	20
HSP06-90-10CF	20
HSP06-90-12CF	20
HSP08-45-15CF	20
HSP08-45-18CF	20
HSP08-90-15CF	20
HSP08-90-18CF	20
HSP10-45-18CF	20
HSP10-45-22CF	20
HSP10-90-18CF	20
HSP12-45-22CF	20
HSP12-90-22CF	20
HSP16-45-28CF	20
HSP16-90-28CF	20
HSP20-45-35CF	20
HSP20-90-35CF	20
HSRS-25	199
HSRS-30	199
HSRS-35	199
HSRS-38	199
HSRS-42	199
HSSP04-06CF	20
HSSP04-08CF	20
HSSP04-10CF	21
HSSP04-45-08CF	21
HSSP04-45-10CF	21
HSSP04-45-12CF	21
HSSP04-90-08CF	21
HSSP04-90-10CF	21
HSSP05-45-12CF	21
HSSP06-10CF	20
HSSP06-12CF	20
HSSP06-14CF	21
HSSP06-15CF	20
HSSP06-45-14CF	21
HSSP06-90-14CF	21
HSSP08-15CF	20
HSSP08-16CF	21
HSSP08-18CF	20
HSSP08-45-14CF	21
HSSP08-45-16CF	21
HSSP08-90-16CF	21
HSSP10-18CF	20
HSSP10-20CF	21
HSSP10-22CF	20
HSSP10-45-16CF	21
HSSP10-45-20CF	21
HSSP10-90-20CF	21
HSSP12-20CF	21
HSSP12-22CF	20
HSSP12-25CF	21
HSSP12-45-20CF	21
HSSP12-45-25CF	21
HSSP12-90-20CF	21
HSSP12-90-25CF	21
HSSP16-25CF	21
HSSP16-28CF	20
HSSP16-30CF	21
HSSP16-45-25CF	21
HSSP16-45-30CF	21
HSSP16-45-38CF	21
HSSP16-90-25CF	21
HSSP16-90-30CF	21
HSSP20-35CF	20
HSSP20-38CF	21
HSSP20-45-30CF	21
HSSP20-45-38CF	21
HSSP24-42CF	20
HST1.1/2X16G-3M	182
HST1.1/2X16G-6M	182
HST1.1/4X16G-3M	182
HST1.1/4X16G-6M	182
HST1/2X16G-3M	182
HST1/2X16G-6M	182
HST1/4X16G-3M	182
HST1/4X16G-6M	182
HST10X1.0-C6F	181
HST10X1.0-C6F-6M	181
HST10X1.5-C6F	181
HST10X1.5-C6F-6M	181
HST10X2.0-C6F	181
HST10X2.0-C6F-6M	181
HST12X1.0-C6F	181
HST12X1.0-C6F-6M	181
HST12X1.5-C6F	181
HST12X1.5-C6F-6M	181
HST12X2.0-C6F	181
HST12X2.0-C6F-6M	181
HST12X2.5	180
HST12X2.5-6M	180
HST14X1.5	180
HST14X1.5-6M	180
HST14X1.5-C6F	181
HST14X1.5-C6F-6M	181
HST14X2.0	180
HST14X2.0-6M	180
HST14X2.0-C6F	181
HST14X2.0-C6F-6M	181
HST15X1.5-C6F	181
HST15X1.5-C6F-6M	181
HST15X2.0-C6F	181
HST15X2.0-C6F-6M	181
HST16X1.5-C6F	181

Code	Page
HST16X1.5-C6F-6M	181
HST16X2.0-C6F	181
HST16X2.0-C6F-6M	181
HST16X2.5	180
HST16X2.5-6M	180
HST16X2.5-C6F	181
HST16X2.5-C6F-6M	181
HST16X3.0-C6F	181
HST16X3.0-C6F-6M	181
HST18X1.5-C6F	181
HST18X1.5-C6F-6M	181
HST18X2.0	180
HST18X2.0-6M	180
HST18X2.0-C6F	181
HST18X2.0-C6F-6M	181
HST18X2.5	180
HST18X2.5-6M	180
HST18X2.5-C6F	181
HST18X2.5-C6F-6M	181
HST1X16G-3M	182
HST1X16G-6M	182
HST20X2.0-C6F	181
HST20X2.0-C6F-6M	181
HST20X2.5	180
HST20X2.5-6M	180
HST20X2.5-C6F	181
HST20X2.5-C6F-6M	181
HST20X3.0	180
HST20X3.0-6M	180
HST20X3.0-C6F	181
HST20X3.0-C6F-6M	181
HST20X3.5	180
HST20X3.5-6M	180
HST20X3.5-C6F	181
HST20X3.5-C6F-6M	181
HST20X4.0-C6F	181
HST20X4.0-C6F-6M	181
HST22X1.5	180
HST22X1.5-6M	180
HST22X1.5-C6F	181
HST22X1.5-C6F-6M	181
HST22X2.0	180
HST22X2.0-6M	180
HST22X2.0-C6F	181
HST22X2.0-C6F-6M	181
HST22X2.5-C6F	181
HST22X2.5-C6F-6M	181
HST25X1.5	180
HST25X1.5-6M	180
HST25X1.5-C6F	181
HST25X1.5-C6F-6M	181
HST25X2.0	180
HST25X2.0-6M	180
HST25X2.0-C6F	181
HST25X2.0-C6F-6M	181
HST25X2.5	180
HST25X2.5-6M	180
HST25X2.5-C6F	181
HST25X2.5-C6F-6M	181
HST25X3.0	180
HST25X3.0-6M	180
HST25X3.0-C6F	181
HST25X3.0-C6F-6M	181
HST25X4.0-C6F	181
HST25X4.0-C6F-6M	181
HST28X1.5	180
HST28X1.5-6M	180
HST28X1.5-C6F	181
HST28X1.5-C6F-6M	181
HST28X2.0-C6F	181
HST28X2.0-C6F-6M	181
HST28X2.5	180
HST28X2.5-6M	180
HST28X2.5-C6F	181
HST28X2.5-C6F-6M	181
HST28X3.0	180
HST28X3.0-6M	180
HST28X3.0-C6F	181
HST28X3.0-C6F-6M	181
HST3/4X16G-3M	182
HST3/4X16G-6M	182
HST3/8X16G-3M	182
HST3/8X16G-6M	182
HST30X2.5	180
HST30X2.5-6M	180
HST30X2.5-C6F	181
HST30X2.5-C6F-6M	181
HST30X3.0-C6F	181
HST30X3.0-C6F-6M	181
HST30X4.0	180
HST30X4.0-6M	180
HST30X4.0-C6F	181
HST30X4.0-C6F-6M	181
HST35X2.0	180
HST35X2.0-6M	180
HST35X2.0-C6F	181
HST35X2.0-C6F-6M	181
HST35X2.5	180
HST35X2.5-6M	180
HST35X2.5-C6F	181
HST35X2.5-C6F-6M	181
HST35X3.0	180
HST35X3.0-6M	180
HST35X3.0-C6F	181
HST35X3.0-C6F-6M	181
HST35X5.0	180
HST35X5.0-6M	180
HST35X5.0-C6F	181
HST35X5.0-C6F-6M	181
HST38X3.0	180
HST38X3.0-6M	180
HST38X3.0-C6F	181
HST38X3.0-C6F-6M	181
HST38X4.0-C6F	181
HST38X4.0-C6F-6M	181
HST38X5.0	180
HST38X5.0-6M	180
HST42X3.0	180
HST42X3.0-6M	180
HST42X3.0-C6F	181
HST42X3.0-C6F-6M	181
HST42X4.0	180
HST42X4.0-6M	180
HST42X4.0-C6F	181
HST42X4.0-C6F-6M	181
HST4X1.0	180
HST4X1.0-6M	180
HST4X1.0-C6F	181
HST4X1.0-C6F-6M	181
HST5/8X16G-3M	182
HST5/8X16G-6M	182
HST50X3.0-C6F	181
HST50X3.0-C6F-6M	181
HST50X5.0-C6F	181
HST50X5.0-C6F-6M	181
HST50X6.0-C6F	181
HST50X6.0-C6F-6M	181
HST6X1.0	180
HST6X1.0-6M	180
HST6X1.0-C6F	181
HST6X1.0-C6F-6M	181
HST6X1.5	180
HST6X1.5-6M	180
HST6X1.5-C6F	181
HST6X1.5-C6F-6M	181
HST6X2.0	180
HST6X2.0-6M	180
HST6X2.0-C6F	181
HST6X2.0-C6F-6M	181
HST8X1.0-C6F	181
HST8X1.0-C6F-6M	181
HST8X1.5-C6F	181
HST8X1.5-C6F-6M	181
HST8X2.0	180
HST8X2.0-6M	180
HST8X2.0-C6F	181
HST8X2.0-C6F-6M	181
HT035SS316	1518
HT040SS316	1518
HT045SS316	1518
HT050SS316	1518
HT055SS316	1518
HT060SS316	1518
HT065SS316	1518
HT070SS316	1518
HT080SS316	1518
HT095SS316	1518
HT-1	1181
HT100	1533
HT100SS316	1518
HT-112	1181
HT-114	1181
HT-1-19	1181
HT-12	1181
HT120	1533
HT-12-06	1181
HT120SS316	1518
HT-12-10	1181
HT-12-16	1181
HT-12-19	1181
HT-12-25	1181
HT-1-31	1181
HT-14	1181
HT140	1533
HT-14-08	1181
HT140SS316	1518
HT-14-10	1181
HT-14-13	1181
HT160	1533
HT160SS316	1518
HT180	1533
HT-18-06	1181
HT180SS316	1518
HT-2	1181
HT200	1533
HT200SS316	1518
HT-212	1181
HT220	1533
HT220SS316	1518
HT24	1761
HT240	1533
HT240SS316	1518
HT260	1533
HT260SS316	1518
HT27	1533
HT280	1533
HT280SS316	1518
HT-3	1181
HT30	1533
HT300SS316	1518
HT320	1533
HT320SS316	1518
HT-34	1181
HT340	1533
HT340SS316	1518
HT-34-13	1181
HT35	1533
HT360	1533
HT360SS316	1518
HT-38	1181
HT380	1533
HT-38-08	1181
HT380SS316	1518
HT-38-13	1181
HT-4	1181
HT40	1533
HT400	1533
HT400SS316	1518
HT420	1533
HT420SS316	1518
HT440	1533
HT440SS316	1518
HT45	1533
HT460	1533
HT460SS316	1518
HT480	1533
HT480SS316	1518
HT50	1533
HT500	1533
HT500SS316	1518
HT520SS316	1518
HT60	1533
HT65	1533
HT70	1533
HT80	1533
HT90	1533
HT95	1533
HTD-032	1015
HTD-052	1015
HTD-063	1015
HTD-075	1015
HTD-083	1015
HTD-092	1015
HTD-105	1015
HTD-125	1015
HTD-140	1015
HTD-160	1015
HTD-190	1015
HTD-210	1015
HTD-240	1015
HTD534	1761
HTS-040-2	1015
HTS-052-12	1015
HTS-063-12	1015
HTS-075-12	1015
HTS-083-12	1015
HTS-092-12	1015
HTS-105-12	1015
HTS-125-12	1015
HTS-140-12	1015
HTS-160-12	1015
HTS-190-12	1015
HTS-210-12	1015
HTS-240-12	1015
HU-1	1184
HU-112	1184
HU-114	1184
HU-12	1184
HU-14	1184
HU-18	1184
HU-2	1184
HU-212	1184
HU-3	1184
HU-34	1184
HU-38	1184
HU-4	1184
HUK5153W 09	965
HUK5153W 10	965
HUK5153W 11	965
HUK5153W 12	965
HUK5153W 14	965
HUK5153W 16	965
HUK5153W 18	965
HUK5153W 20	965
HUK5163 09	957
HUK5163 10	957
HUK5163 11	957
HUK5163 12	957
HUK5163 14	957
HUK5163 16	957
HUK5163 18	957
HUK5163 20	957
HUK5163CT 12	957
HUK5163CT 14	957
HUKDCV-1	960
HUKDCV-112	960
HUKDCV-114	960
HUKDCV-12	960
HUKDCV-2	960
HUKDCV-34	960
HUKDPC 09W	965
HUKDPC 10W	965
HUKDPC 11W	965
HUKDPC 12W	965
HUKDPC 13W	965
HUKDPC 14W	965
HUKDPC 16W	965
HUKDPC 18W	965
HUKDPC 20W	965
HUKNAM110VAC	1020

Code	Page
HUKNAM230VAC	1020
HUKNAM24VAC	1020
HUKNAM24VDC	1020
HUKSBOX	1022
HUKTP-12	978
HUKTP-14B	978
HUKTP-14R	978
HUKYS 09W	974
HUKYS 10W	974
HUKYS 11W	974
HUKYS 12W	974
HUKYS 13W	974
HUKYS 14W	974
HUKYS 16W	974
HUKYS 18W	974
HUKYS 20W	974
HV29BKR	1752
HVFF06-06	773
HVFF08-06	773
HVFF08-08	773
HVFF10-10	773
HVFF12-10	773
HVFF12-12	773
HVFS6-01	773
HVFS6-02	773
HVFS6-03	773
HVFS8-01	773
HVFS8-02	773
HVFS8-03	773
HVIS06-100	1408
HVIS06-30	1408
HVIS06-50	1408
HVIS08-100	1408
HVIS08-30	1408
HVIS08-50	1408
HVIS10-100	1408
HVIS10-30	1408
HVIS10-50	1408
HVIS12-100	1408
HVIS12-30	1408
HVIS12-50	1408
HVSS-01-01	773
HVSS-02-01	773
HVSS-02-02	773
HVSS-02-03	773
HVSS-03-03	773
HVSS-04-03	773
HVSS-04-04	773
HW100	1458
HYD.ELG	1627
HYD.GK	1627
HYDB	1496
HYDK	1496
HYDKB	1496
HYD-KIT1	272
HYD-KIT2	272
HYD-KIT3	272
HYD-KIT4	272
HYD-KIT5	272
HYD-KIT6	272
HYGWASH-GUN	1658
HYGWASH-GUNG	1658
HYGWASH-GUNR	1658

Code	Page
I	
I 12/16	511
I 20/25	511
IBCA2NPS	1491
IBCAS10083	1491
IBCAS6061	1491
IBCAS606112	1491
IBCAS6062	1491
IBCC21	1491
IBCC2112	1491
IBCC2114	1491
IBCC22	1491
IBCC33	1491
IBCD112112BSP	1491
IBCD22BSP	1491
IBCDC112	1491
IBCDC2	1491
IBCDC3	1491
IBCDP112	1491
IBCDP2	1491
IBCDS6062	1491
IBCHAS10083	1491
IBCHAS606112BSP	1491
IBCHAS6061BSP	1491
IBCHAS6062BSP	1491
IBCHAS6062BSPCWS	1491
IBCHAS6062NPS	1491
IBCHAS606NPSM2	1491
IBCHAS606S1008	1491
IBCHAS60X34BSP	1491
IBCHCS6061	1491
IBCHCS606112	1491
IBCHCS606114	1491
IBCHCS6062	1491
IBCHDS606112BSP	1491
IBCHDS6062BSP	1491
IBCHDS6062NPS	1491
IBC-SEAL	1491
IBR10-50	903
IBR10-75	903
IBR12-50	903
IBR12-75	903
ICT-12	1213
ICT-12/30	1213
ICT-12/30-18SWG	1213
ICT-14	1213
ICT-14/30	1213
ICT-14/30-20SWG	1213
ICT-18	1213
ICT-18/30	1213
ICT-316	1213
ICT-316/30	1213
ICT-38	1213
ICT-38/30	1213
ICT-38/30-18SWG	1213
ICT-516	1213
ICT-516/30	1213
ICT-58	1213
ICT-58/30	1213
IF-14	656
IF1V1/A-M6	438
IF1V1/A-M7	438
IF1V1/A-M8	438
IF1VE1/A-M6	437
IF1VE1/A-M7	437

Code	Page
IF1VE1/A-M8	437
IF2V3/A-M6	438
IF2V3/A-M7	438
IF2V3/A-M8	438
IF2VE3/A-M6	437
IF2VE3/A-M8	437
IF3V6/A-M6	438
IF3V6/A-M7	438
IF3V6/A-M8	438
IF3VE6/A-M6	437
IF3VE6/A-M7	437
IF3VE6/A-M8	437
IF4V16/A-M6	438
IF4V16/A-M7	438
IF4V16/A-M8	438
IF4VE16/A-M6	437
IF4VE16/A-M7	437
IF4VE16/A-M8	437
IF5V60/A-M6	438
IF5V60/A-M7	438
IF5V60/A-M8	438
IF5VE60/A-M6	437
IF5VE60/A-M7	437
IF5VE60/A-M8	437
IFE0.5R2.5	437
IFE1R3	437
IFE2R9	437
IFE3R18	437
IFE4R24	437
IFE5R35	437
IFE6R60	437
IG400	1721
IL1151	251
IL1251	251
ILF-14	656
ILF-38	656
ILFE-1-10	255
ILFE-1-25	255
ILFE-2-10	255
ILFE-2-25	255
ILFE-3-10	255
ILFE-3-25	255
ILR-14	656
ILRF1-08-10	255
ILRF1-08-25	255
ILRF2-12-10	255
ILRF2-12-25	255
ILRF2-16-10	255
ILRF2-16-25	255
ILRF3-20-10	255
ILRF3-20-25	255
ILRF3-24-10	255
ILRF3-24-25	255
IMC38-10	1207
INV-1	243
INV-12	243
INV-14	243
INV-34	243
INV-38	243
IOK-1	112
IPGM	1761
IPGP	1761
IPPCLIP-1	1113
IPPCLIP-112	1113

Code	Page
IPPCLIP-114	1113
IPPCLIP-12	1113
IPPCLIP-2	1113
IPPCLIP-212	1113
IPPCLIP-3	1113
IPPCLIP-34	1113
IPPCLIP-4	1113
IPPCLIP-5	1113
IPPSB-1	1113
IPPSB-2	1113
IPSS4	1761
IS-A0/A1	192
IS-A2	192
IS-A3	192
IS-A4	192
IS-A5	192
IS-A6	192
IS-B1	194
IS-B2	194
IS-B3	194
IS-B5	194
IS-C1	197
IS-C2	197
IS-C3	197
IS-C4	197
IS-C5	197
ISCT-12	1215
ISCT-14	1215
ISCT-38	1215
ISO 46	283
ISOADC-12	290
ISOADC-16	290
ISOADC-4	290
ISOADC-6	290
ISOADC-8	290
ISOADP-12	290
ISOADP-16	290
ISOADP-4	290
ISOADP-6	290
ISOADP-8	290
ISOBDP-12	291
ISOBDP-16	291
ISOBDP-4	291
ISOBDP-6	291
ISOBDP-8	291
IT060-12	940
IT066-1	940
IT066-112	940
IT066-114	940
IT066-12	940
IT066-14	940
IT066-2	940
IT066-34	940
IT066-38	940
IT067-1	940
IT067-112	940
IT067-114	940
IT067-12	940
IT067-14	940
IT067-2	940
IT067-34	940
IT067-38	940
IT068-1	940
IT068-12	940

Code	Page
IT068-14	940
IT068-34	940
IT068-38	940
IT069-1	940
IT069-12	940
IT069-14	940
IT069-34	940
IT069-38	940
IT070-1	940
IT070-112	940
IT070-114	940
IT070-12	940
IT070-2	940
IT070-34	940
IT071-1	940
IT071-112	940
IT071-114	940
IT071-12	940
IT071-2	940
IT071-34	940
IT072-1	940
IT072-12	940
IT072-34	940
IT073-1	940
IT073-12	940
IT073-34	940
IT090-1	929
IT090-112	929
IT090-114	929
IT090-12	929
IT090-14	929
IT090-2	929
IT090-212	929
IT090-3	929
IT090-34	929
IT090-38	929
IT090-4	929
IT091-1	929
IT091-112	929
IT091-114	929
IT091-12	929
IT091-14	929
IT091-2	929
IT091-34	929
IT091-38	929
IT092-1	930
IT092-12	930
IT092-14	930
IT092-34	930
IT092-38	930
IT093-1	930
IT093-12	930
IT093-14	930
IT093-34	930
IT093-38	930
IT098-1	930
IT098-112	930
IT098-114	930
IT098-12	930
IT098-2	930
IT098-34	930
IT099-1	929
IT099-112	929
IT099-114	929

Code	Page
IT099-12	929
IT099-2	929
IT099-34	929
IT100-1	962
IT100-112	962
IT100-114	962
IT100-12	962
IT100-2	962
IT100-212	962
IT100-3	962
IT100-34	962
IT100-38	962
IT100-4	962
IT101-1	962
IT101-112	962
IT101-114	962
IT101-12	962
IT101-2	962
IT101-34	962
IT102-1	962
IT102-112	962
IT102-114	962
IT102-12	962
IT102-2	962
IT102-212	962
IT102-3	962
IT102-34	962
IT102-38	962
IT102-4	962
IT103-1	962
IT103-112	962
IT103-114	962
IT103-12	962
IT103-2	962
IT103-212	962
IT103-3	962
IT103-34	962
IT103-38	962
IT103-4	962
IT104-1	962
IT104-112	962
IT104-114	962
IT104-12	962
IT104-2	962
IT104-34	962
IT104-38	962
IT107-1	962
IT107-12	962
IT107-2	962
IT107-34	962
IT108-1	962
IT108-112	962
IT108-114	962
IT108-12	962
IT108-2	962
IT108-212	962
IT108-3	962
IT108-34	962
IT108-38	962
IT108-4	962
IT110-1	930
IT115-1	929
IT115-112	929
IT115-114	929
IT115-12	929
IT115-2	929
IT115-34	929
IT125-12	927
IT125-12N	927
IT125-14	927
IT125-14N	927
IT125-34	927
IT125-34N	927
IT125-38	927
IT125-38N	927
IT126-12	927
IT126-12N	927
IT126-14	927
IT126-14N	927
IT126-34	927
IT126-34N	927
IT126-38	927
IT126-38N	927
IT128-112L	930
IT128-112T	930
IT128-114L	930
IT128-114T	930
IT128-12L	930
IT128-12T	930
IT128-14L	930
IT128-14T	930
IT128-1L	930
IT128-1T	930
IT128-2L	930
IT128-2T	930
IT128-34L	930
IT128-34T	930
IT128-38L	930
IT128-38T	930
IT1300-112M	962
IT1300-114M	962
IT1300-12M	962
IT1300-1M	962
IT1300-2M	962
IT1300-34M	962
IT132-1	931
IT132-12	931
IT132-34	931
IT132-38	931
IT134-1	931
IT134-12	931
IT134-34	931
IT134-38	931
IT139-12	930
IT139-34	930
IT139-38	930
IT144-12	931
IT144-34	931
IT156-1	958
IT156-112	958
IT156-114	958
IT156-12	958
IT156-2	958
IT156-212	958
IT156-3	958
IT156-34	958
IT156-4	958
IT174-12	931
IT174-34	931
IT192-1	973
IT192-112	973
IT192-114	973
IT192-12	973
IT192-14	973
IT192-2	973
IT192-212	973
IT192-3	973
IT192-34	973
IT192-38	973
IT192-4	973
IT193-1	973
IT193-112	973
IT193-114	973
IT193-12	973
IT193-14	973
IT193-2	973
IT193-34	973
IT193-38	973
IT216-1	929
IT216-112	929
IT216-114	929
IT216-12	929
IT216-14	929
IT216-2	929
IT216-34	929
IT216-38	929
IT217-1	929
IT217-112	929
IT217-114	929
IT217-12	929
IT217-14	929
IT217-2	929
IT217-34	929
IT217-38	929
IT243-1	980
IT243-112	980
IT243-114	980
IT243-12	980
IT243-2	980
IT243-34	980
IT266-1	940
IT266-112	940
IT266-114	940
IT266-12	940
IT266-14	940
IT266-2	940
IT266-34	940
IT266-38	940
IT267-1	940
IT267-112	940
IT267-114	940
IT267-12	940
IT267-14	940
IT267-2	940
IT267-34	940
IT267-38	940
IT298-1	930
IT298-12	930
IT298-34	930
ITS-1-16SWG	1213
ITS-118-16SWG	1213
ITS-118-18SWG	1213
ITS-1-18SWG	1213
ITS-12	1213
ITS-12-10SWG	1213
ITS-12-16SWG	1213
ITS-12-18SWG	1213
ITS-14	1213
ITS-18	1213
ITS-316	1213
ITS-34	1213
ITS-34-18SWG	1213
ITS-38	1213
ITS-516	1213
ITS-58	1213
ITS-78-16SWG	1213
J	
J0002	1656
J0250	1656
J0312	1656
J0437	1656
J0787	1656
J100	1636
J100TDG	1637
J10302504	1624
J10304022	1637
J10304024	1637
J1181	1656
J13060	278
J13120	278
J13200	278
J13300	278
J1373	1656
J1500450	1637
J1500451	1637
J1574	1656
J1581400	1626
J1703001	1637
J1708001	1638
J1708003	1638
J17210241	1624
J1786004	1640
J1786501	1640
J1789022-1	1621
J1789023-1	1621
J18128003	1621
J18133512	1621
J18312002-1	1621
J1968	1656
J2	1641
J2362	1656
J2653	1632
J2H10	1018
J2L10	1018
J300S	1636
J4175	1632
J4177	1632
J4CPG1604	1055
J4CPG1605	1055
J4CPG1806	1055
J4CS140	1018
J4CS20	1018
J4CS300	1018
J4CS35	1018
J4CS55	1018
J4CS85	1018
J4CSBSR1	1019
J4CSBSR2	1019
J4CSDPS1	1019
J4CSDPS2	1019
J500S	1636
J7502	1656
J8055/12SE	1656
J8055/6	1656
J8055/9	1656
J8057/1N	1656
J8057/2N	1656
J8057/3N	1656
J8057/5N	1656
J9023SE	1632
J9130/80	1643
J9131/80	1643
J9CPG1603	1055
J9CPG1604	1055
J9CPG1605	1055
J9CPG1806	1055
JA-01	1621
JA165	1520
JA165SS	1520
JALL112	1497
JALL114	1497
JALL2	1497
JALL212	1497
JALL3	1497
JALL4	1497
JDA-01	1621
JETW007G	1741
JETW007R	1741
JETW007Y	1741
JF0403CF	19
JF0404CF	19
JF0406CF	19
JF044503CF	19
JF044504CF	19
JF049003CF	19
JF049004CF	19
JF0490K04CF	19
JF0503CF	19
JF0504CF	19
JF0505CF	19
JF0506CF	19
JF054504CF	19
JF054505CF	19
JF054506CF	19
JF059003CF	19
JF059004CF	19
JF059005CF	19
JF059006CF	19
JF0604CF	19
JF0605CF	19
JF0606CF	19
JF064504CF	19
JF064505CF	19
JF064506CF	19
JF069004CF	19
JF069005CF	19
JF069006CF	19
JF0690K04CF	19
JF0690K06CF	19
JF0805CF	19

Code	Page
JF0806CF	19
JF0808CF	19
JF084506CF	19
JF084508CF	19
JF089005CF	19
JF089006CF	19
JF089008CF	19
JF0890K06CF	19
JF0890K08CF	19
JF1006CF	19
JF1008CF	19
JF1010CF	19
JF1012CF	19
JF104506CF	19
JF104508CF	19
JF104510CF	19
JF104512CF	19
JF109006CF	19
JF109008CF	19
JF109010CF	19
JF109012CF	19
JF1090K08CF	19
JF1090K10CF	19
JF1208CF	19
JF1210CF	19
JF1212CF	19
JF1216CF	19
JF124508CF	19
JF124510CF	19
JF124512CF	19
JF124516CF	19
JF129008CF	19
JF129010CF	19
JF129012CF	19
JF129016CF	19
JF1290K12CF	19
JF1412CF	19
JF1416CF	19
JF144512CF	19
JF144516CF	19
JF149012CF	19
JF149016CF	19
JF1612CF	19
JF1616CF	19
JF164512CF	19
JF164516CF	19
JF169012CF	19
JF169016CF	19
JF1690K16CF	19
JF2016CF	19
JF2020CF	19
JF204516CF	19
JF204520CF	19
JF209016CF	19
JF209020CF	19
JF2420CF	19
JF2424CF	19
JF244524CF	19
JF249020CF	19
JF249024CF	19
JF3232CF	19
JF324532CF	19
JF329032CF	19
JG-12	1642
JG-50	1642
JG603B	883
JG-BS15	884
JG-HDC	882
JG-L-WSK	1092
JG-TSP	905
JGWALLBOX 1/2	1092
JGWALLBOX 3/4	1092
JHT100	1518
JHT120	1518
JHT140	1518
JHT160	1518
JHT180	1518
JHT200	1518
JHT220	1518
JHT240	1518
JHT260	1518
JHT280	1518
JHT300	1518
JHT320	1518
JHT340	1518
JHT35	1518
JHT360	1518
JHT380	1518
JHT40	1518
JHT400	1518
JHT420	1518
JHT440	1518
JHT45	1518
JHT480	1518
JHT50	1518
JHT500	1518
JHT70	1518
JHT80	1518
JHT95	1518
JK120	1741
JLN07	79
JLN08	79
JLN09	79
JLN12	79
JLN14	79
JLN17	79
JLN21	79
JLN26	79
JLN30	79
JM-01	1621
JM10	625
JM13	625
JM16	625
JM20	625
JM25	625
JM30	625
JM36	625
JM8	625
JMBSPF-12-12CF	25
JMBSPF-16-12CF	25
JMBSPF-16-16CF	25
JMBSPF-20-16CF	25
JMBSPF45-12-12CF	25
JMBSPF45-16-12CF	25
JMBSPF45-16-16CF	25
JMBSPF45-20-16CF	25
JMBSPF90-12-12CF	25
JMBSPF90-16-12CF	25
JMBSPF90-16-16CF	25
JMBSPF90-20-16CF	25
JMBSPM-12-12CF	25
JMBSPM-16-12CF	25
JMBSPM-16-16CF	25
JMBSPM-20-16CF	25
JMCAT12-12CF	27
JMCAT16-12CF	27
JMCAT16-16CF	27
JMCAT20-16CF	27
JMCAT4512-12CF	27
JMCAT4516-12CF	27
JMCAT4516-16CF	27
JMCAT4520-16CF	27
JMCAT9012-12CF	27
JMCAT9016-12CF	27
JMCAT9016-16CF	27
JMCAT9020-16CF	27
JMDKOS45-36-12CF	26
JMDKOS45-42-16CF	26
JMDKOS90-26-12CF	26
JMDKOS90-42-16CF	26
JMDKOSF-36-12CF	26
JMDKOSF-42-16CF	26
JMDKOSM-26-12CF	26
JMDKOSM-42-16CF	26
JMF4SH-12CF	16
JMF4SH-16CF	16
JMF57-06CF	16
JMF57-08CF	16
JMF57-10CF	16
JMF57-12CF	16
JMF57-16CF	16
JMF57-20CF	16
JMF57-24CF	16
JMF57-32CF	16
JMFL3-12-12CF	27
JMFL3-16-12CF	27
JMFL3-16-16CF	27
JMFL3-20-16CF	27
JMFL345-12-12CF	27
JMFL345-16-12CF	27
JMFL345-16-16CF	27
JMFL345-20-12CF	27
JMFL390-12-12CF	27
JMFL390-16-12CF	27
JMFL390-16-16CF	27
JMFL390-20-16CF	27
JMFL6-12-12CF	27
JMFL6-16-12CF	27
JMFL6-16-16CF	27
JMFL6-20-16CF	27
JMFL645-12-12CF	27
JMFL645-16-12CF	27
JMFL645-16-16CF	27
JMFL645-20-12CF	27
JMFL690-12-12CF	27
JMFL690-16-12CF	27
JMFL690-16-16CF	27
JMFL690-20-16CF	27
JMJICF-17-12CF	25
JMJICF-21-12CF	25
JMJICF-26-16CF	25
JMJICF45-17-12CF	25
JMJICF45-21-12CF	25
JMJICF45-21-16CF	25
JMJICF45-26-16CF	25
JMJICF90-17-12CF	25
JMJICF90-21-12CF	25
JMJICF90-21-16CF	25
JMJICF90-26-16CF	25
JMJICM-21-16CF	25
JMJICMM-17-12CF	25
JMJICMM-21-12CF	25
JMJICMM-21-16CF	25
JMJICMM-26-16CF	25
JMORFSF1212CF	26
JMORFSF1616CF	26
JMORFSF451212CF	26
JMORFSF451616CF	26
JMORFSF901212CF	26
JMORFSF901616CF	26
JMPOCF-12-12CF	26
JMPOCF-16-16CF	26
JMPOCM-12-12CF	26
JMPOCM-16-16CF	26
JMT10	625
JMT13	625
JMT16	625
JMT20	625
JMT25	625
JMT30	625
JMT36	625
JMT8	625
JOS100	1638
JOS200	1638
JPC005MS	1541
JPC005SS	1541
JPC005SS316	1541
JPC006MS	1541
JPC006SS	1541
JPC006SS316	1541
JPC008MS	1541
JPC008SS	1541
JPC008SS316	1541
JPC009SS	1541
JPC009SS316	1541
JPC010MS	1541
JPC010SS	1541
JPC010SS316	1541
JPC012MS	1541
JPC012SS	1541
JPC012SS316	1541
JPC013MS	1541
JPC013SS	1541
JPC013SS316	1541
JPC014MS	1541
JPC014SS	1541
JPC014SS316	1541
JPC015MS	1541
JPC015SS	1541
JPC015SS316	1541
JPC016MS	1541
JPC016SS	1541
JPC016SS316	1541
JPC017MS	1541
JPC017SS	1541
JPC017SS316	1541
JPC018MS	1541
JPC018SS	1541
JPC018SS316	1541
JPC019MS	1541
JPC019SS	1541
JPC019SS316	1541
JPC020MS	1541
JPC020SS	1541
JPC020SS316	1541
JPC021MS	1541
JPC021SS	1541
JPC021SS316	1541
JPC022MS	1541
JPC022SS	1541
JPC022SS316	1541
JPC025MS	1541
JPC025SS	1541
JPC025SS316	1541
JPC027MS	1541
JPC027SS316	1541
JPC028MS	1541
JPC028SS	1541
JPC028SS316	1541
JPC029MS	1541
JPC029SS316	1541
JPC030MS	1541
JPC030SS	1541
JPC030SS316	1541
JPC032SS316	1541
JPC035MS	1541
JPC035SS	1541
JPC035SS316	1541
JPC040MS	1541
JPC040SS	1541
JPC040SS316	1541
JPC044MS	1541
JPC044SS	1541
JPC044SS316	1541
JPC048SS316	1541
JPC052SS316	1541
JPCK110MS	1541
JPCK110SS	1541
JPOD030	1638
JPOD065	1638
JS201	1555
JS202	1555
JS203	1555
JS204	1555
JS205	1555
JS206	1555
JS207	1555
JS208	1555
JS209	1555
JS210	1555
JS211	1555
JS212	1555
JS213	1555
JS214	1555
JS215	1555
JS216	1555
JS227	1555
JS230	1555
JS236	1555
JS240	1555

Code	Page
JS241	1555
JS242	1555
JS243	1555
JS244	1555
JS245	1555
JS246	1555
JS252	1555
JS253	1555
JS255	1555
JS256	1555
JS257	1555
JS259	1555
JSC103	1521
JSC103SS304	1521
JSC103SS316	1521
JSC112	1521
JSC112SS304	1521
JSC112SS316	1521
JSC121	1521
JSC121SS304	1521
JSC121SS316	1521
JSC130	1521
JSC130SS304	1521
JSC130SS316	1521
JSC139	1521
JSC139SS304	1521
JSC139SS316	1521
JSC148	1521
JSC148SS304	1521
JSC148SS316	1521
JSC161	1521
JSC161SS304	1521
JSC161SS316	1521
JSC174	1521
JSC174SS304	1521
JSC174SS316	1521
JSC187	1521
JSC187SS304	1521
JSC187SS316	1521
JSC19	1521
JSC19SS304	1521
JSC19SS316	1521
JSC200	1521
JSC200SS304	1521
JSC213SS304	1521
JSC213SS316	1521
JSC22	1521
JSC226	1521
JSC226SS304	1521
JSC226SS316	1521
JSC22SS304	1521
JSC22SS316	1521
JSC239	1521
JSC239SS304	1521
JSC25	1521
JSC25SS304	1521
JSC25SS316	1521
JSC28	1521
JSC28SS304	1521
JSC28SS316	1521
JSC31	1521
JSC31SS304	1521
JSC31SS316	1521
JSC35	1521
JSC35SS304	1521
JSC35SS316	1521
JSC39	1521
JSC39SS304	1521
JSC39SS316	1521
JSC43	1521
JSC43SS304	1521
JSC43SS316	1521
JSC47	1521
JSC47SS304	1521
JSC47SS316	1521
JSC51	1521
JSC51SS304	1521
JSC51SS316	1521
JSC55	1521
JSC55SS304	1521
JSC55SS316	1521
JSC59	1521
JSC59SS304	1521
JSC59SS316	1521
JSC63	1521
JSC63SS304	1521
JSC63SS316	1521
JSC67	1521
JSC67SS304	1521
JSC67SS316	1521
JSC73	1521
JSC73SS304	1521
JSC73SS316	1521
JSC79	1521
JSC79SS304	1521
JSC79SS316	1521
JSC85	1521
JSC85SS304	1521
JSC85SS316	1521
JSC91	1521
JSC91SS304	1521
JSC91SS316	1521
JSC97	1521
JSC97SS304	1521
JSC97SS316	1521
JSS1	1497
JSS112	1497
JSS114	1497
JSS2	1497
JSS3	1497
JSS34	1497
JSS4	1497
JT04	1761
JTD202	1761
JWF-22-04	1678
JWF-22-05	1678
JWF-22-06	1678
JWM-04	1678
JWM-05	1678
JWM-06	1678
JXPP-5422B	1741
K	
K006AC	430
K009AA	430
K030AA	430
K030AO	430
K10	626
K100-06	549
K10-UCL	153
K10-UCS	153
K-110AC	577
K-12DC	577
K12-UCL	153
K12-UCS	153
K13	626
K145AA	430
K145AO	430
K14-UCS	153
K15-UCL	153
K16	626
K16-UCS	153
K18-UCL	153
K20	626
K200-08	549
K20-UCS	153
K-220AC	577
K225-03-110AC-NC	1027
K225-03-110AC-NO	1028
K225-03-12DC-NC	1027
K225-03-12DC-NO	1028
K225-03-230AC-NC	1027
K225-03-230AC-NO	1028
K225-03-24AC-NC	1027
K225-03-24AC-NO	1028
K225-03-24DC-NC	1027
K225-03-24DC-NO	1028
K225-04-110AC-NC	1027
K225-04-110AC-NO	1028
K225-04-12DC-NC	1027
K225-04-12DC-NO	1028
K225-04-230AC-NC	1027
K225-04-230AC-NO	1028
K225-04-24AC-NC	1027
K225-04-24AC-NO	1028
K225-04-24DC-NC	1027
K225-04-24DC-NO	1028
K225-06-110AC-NC	1027
K225-06-110AC-NO	1028
K225-06-12DC-NC	1027
K225-06-12DC-NO	1028
K225-06-230AC-NC	1027
K225-06-230AC-NO	1028
K225-06-24AC-NC	1027
K225-06-24AC-NO	1028
K225-06-24DC-NC	1027
K225-06-24DC-NO	1028
K225-08-110AC-NC	1027
K225-08-110AC-NO	1028
K225-08-12DC-NC	1027
K225-08-12DC-NO	1028
K225-08-230AC-NC	1027
K225-08-230AC-NO	1028
K225-08-24AC-NC	1027
K225-08-24AC-NO	1028
K225-08-24DC-NC	1027
K225-08-24DC-NO	1028
K225-110/50AC-NC	1027
K225-110/50AC-NO	1028
K225-12-110AC-NC	1027
K225-12-110AC-NO	1028
K225-12-12DC-NC	1027
K225-12-12DC-NO	1028
K225-12-230AC-NC	1027
K225-12-230AC-NO	1028
K225-12-24AC-NC	1027
K225-12-24AC-NO	1028
K225-12-24DC-NC	1027
K225-12-24DC-NO	1028
K225-12DC-NC	1027
K225-12DC-NO	1028
K225-14-110AC-NC	1027
K225-14-110AC-NO	1028
K225-14-12DC-NC	1027
K225-14-12DC-NO	1028
K225-14-230AC-NC	1027
K225-14-230AC-NO	1028
K225-14-24AC-NC	1027
K225-14-24AC-NO	1028
K225-14-24DC-NC	1027
K225-14-24DC-NO	1028
K225-20-110AC-NC	1027
K225-20-110AC-NO	1028
K225-20-12DC-NC	1027
K225-20-12DC-NO	1028
K225-20-230AC-NC	1027
K225-20-230AC-NO	1028
K225-20-24AC-NC	1027
K225-20-24AC-NO	1028
K225-20-24DC-NC	1027
K225-20-24DC-NO	1028
K225-230/50AC-NC	1027
K225-230/50AC-NO	1028
K225-24/50AC-NC	1027
K225-24/50AC-NO	1028
K225-24DC-NC	1027
K225-24DC-NO	1028
K22-UCL	153
K24	1626
K24.AB	1626
K24.BATTERY	1626
K-24AC	577
K-24DC	577
K25	626
K25-UCS	153
K28-UCL	153
K2W025-06-110AC	1029
K2W025-06-12DC	1029
K2W025-06-230AC	1029
K2W025-06-24AC	1029
K2W025-06-24DC	1029
K2W025-08-110AC	1029
K2W025-08-12DC	1029
K2W025-08-230AC	1029
K2W025-08-24AC	1029
K2W025-08-24DC	1029
K2W040-10-110AC	1029
K2W040-10-12DC	1029
K2W040-10-230AC	1029
K2W040-10-24AC	1029
K2W040-10-24DC	1029
K2W-040-110/50AC	1029
K2W-040-12DC	1029
K2W-040-230/50AC	1029
K2W-040-24/50AC	1029
K2W-040-24DC	1029
K2W-08-110/50AC	1029
K2W-08-12DC	1029
K2W-08-230/50AC	1029
K2W-08-24/50AC	1029
K2W-08-24DC	1029
K2WH012-06-110AC	1029
K2WH012-06-12DC	1029
K2WH012-06-230AC	1029
K2WH012-06-24AC	1029
K2WH012-06-24DC	1029
K2WH012-08-110AC	1029
K2WH012-08-12DC	1029
K2WH012-08-230AC	1029
K2WH012-08-24AC	1029
K2WH012-08-24DC	1029
K2WH020-10-110AC	1029
K2WH020-10-12DC	1029
K2WH020-10-230AC	1029
K2WH020-10-24AC	1029
K2WH020-10-24DC	1029
K30	626
K300-10	549
K300-15	549
K30-UCS	153
K32	1641
K35-UCL	153
K36	626
K38-UCS	153
K3M3B-05	545
K3M3B-06	545
K3M3B-08	545
K3M3HS05	546
K3M3HS06	546
K3M3HS08	546
K3M3L-05	545
K3M3L-06	545
K3M3L-08	545
K3M3PF-05-B	546
K3M3PF-05-G	546
K3M3PF-05-R	546
K3M3PF-06-B	546
K3M3PF-06-G	546
K3M3PF-06-R	546
K3M3PF-08-B	546
K3M3PF-08-G	546
K3M3PF-08-R	546
K3M3PL-05-R	546
K3M3PL-06-R	546
K3M3PL-08-R	546
K3M3PM-05-B	546
K3M3PM-05-G	546
K3M3PM-05-R	546
K3M3PM-06-B	546
K3M3PM-06-G	546
K3M3PM-06-R	546
K3M3PM-08-B	546
K3M3PM-08-G	546
K3M3PM-08-R	546
K3M3PP-05-B	546
K3M3PP-05-G	546
K3M3PP-05-R	546
K3M3PP-06-B	546
K3M3PP-06-G	546
K3M3PP-06-R	546
K3M3PP-08-B	546

Code	Page
K3M3PP-08-G	546
K3M3PP-08-R	546
K3M3R-05	545
K3M3R-06	545
K3M3R-08	545
K3M3V-05	545
K3M3V-06	545
K3M3V-08	545
K3M3Y-05	545
K3M3Y-06	545
K3M3Y-08	545
K40	1641
K42-UCL	153
K56001076	261
K56001127	261
K56002076	261
K56002127	261
K5604120014	260
K56041201415	260
K5604122038	260
K56041221615	260
K56041251815	260
K5604128012	260
K56041282015	260
K5604135034	260
K5604143100	260
K5604151114	260
K5604158112	260
K5604174200	260
K5604222038	260
K56042221615	260
K56042251815	260
K5604228012	260
K56042282015	260
K5604235034	260
K5604243100	260
K5604251114	260
K5604258112	260
K5604274200	260
K56062420	260
K56063026	260
K56063632	260
K56064238	260
K56064440	260
K560822038	260
K560828012	260
K560835034	260
K560842100	260
K561020014	260
K561024038	260
K561029012	260
K5618012	262
K5618014	262
K5618018	262
K5618034	262
K5618038	262
K5618100	262
K562213020	262
K562213030	262
K562223018	262
K562323020	262
K562423026	262
K562621014	262
K562624038	262
K562630012	262
K562636034	262
K562642100	262
K5634136038	262
K56341361615	262
K5634141012	262
K56341411815	262
K56341412015	262
K56341412215	262
K5634147034	262
K5634152100	262
K5634163112	262
K5634163114	262
K5634236038	262
K56342361615	262
K5634241012	262
K56342411815	262
K56342412215	262
K5634247034	262
K5634252100	262
K5634263112	262
K5634263114	262
K563630012	262
K563630014	262
K563630038	262
K563830012	262
K563830014	262
K563830038	262
K564020014	262
K564024038	262
K564030012	262
K564220014	262
K564224038	262
K564230012	262
K5654236038	262
K5654241012	262
K56542412015	262
K5654247034	262
K5654252100	262
K5670706020	261
K6-UCL	153
K6-UCS	153
K8	626
K8-UCL	153
K8-UCS	153
KA-03-94-76	1679
KA-03-94-79	1679
KA-10X100-S-CA	453
KA-10X10-S-CA	453
KA-10X125-S-CA	453
KA-10X150-S-CA	453
KA-10X15-S-CA	453
KA-10X160-S-CA	453
KA-10X175-S-CA	453
KA-10X200-S-CA	453
KA-10X20-S-CA	453
KA-10X25-S-CA	453
KA-10X30-S-CA	453
KA-10X40-S-CA	453
KA-10X50-S-CA	453
KA-10X60-S-CA	453
KA-10X75-S-CA	453
KA-10X80-S-CA	453
KA-12X100-S-CA	453
KA-12X10-S-CA	453
KA-12X125-S-CA	453
KA-12X150-S-CA	453
KA-12X15-S-CA	453
KA-12X175-S-CA	453
KA-12X200-S-CA	453
KA-12X20-S-CA	453
KA-12X250-S-CA	453
KA-12X25-S-CA	453
KA-12X30-S-CA	453
KA-12X40-S-CA	453
KA-12X50-S-CA	453
KA-12X60-S-CA	453
KA-12X75-S-CA	453
KA-12X80-S-CA	453
KA132000A9	596
KA132000B9	596
KA132V54T9	596
KA132V55T9	596
KA132V56T9	596
KA-15-00-07F	1679
KA-15-20-00	1679
KA-15-20-09	1679
KA-15-20-12	1679
KA200-06	645
KA200-08	645
KA200U-P1	645
KA201-P1	645
KA300-08	645
KA300-10	645
KA300U-P1	645
KA301-P1	645
KA-32-40-24-AC	1057
KA-35-20-10-MF	1057
KA-35-25-05	1057
KA-35-25-12	1057
KA-35-40-10	1057
KA-35-40-18	1057
KA-35-75-20	1057
KA-36-00-25	1057
KA-36-00-40	1057
KA-39-00-10	1057
KA-39-10-10	1057
KA400-10	645
KA400-15	645
KA400U-P1	645
KA401-P1	645
KA-59-00-10	1680
KA600-20	645
KA600-25	645
KA-60-04-23-40	1680
KA600U-P1	645
KA601-P1	645
KA-62-33-00	1680
KA-68-25-05	1680
KA-8X100-S-CA	453
KA-8X125-S-CA	453
KA-8X150-S-CA	453
KA-8X15-S-CA	453
KA-8X20-S-CA	453
KA-8X25-S-CA	453
KA-8X30-S-CA	453
KA-8X40-S-CA	453
KA-8X50-S-CA	453
KA-8X60-S-CA	453
KA-8X75-S-CA	453
KA-8X80-S-CA	453
KA-92-10-30	1680
KA-92-15-50	1680
KAA 10	1476
KAA 10 BSP	1476
KAA 12	1476
KAA 12 BSP	1476
KAA 34	1476
KAA 34 BSP	1476
KAA 38	1476
KAA 38 BSP	1476
KAG1	1477
KAG12	1477
KAG14	1477
KAG34	1477
KAG38	1477
KAG54	1477
KASS-16X100-S-CA	459
KASS-16X10-S-CA	459
KASS-16X125-S-CA	459
KASS-16X160-S-CA	459
KASS-16X200-S-CA	459
KASS-16X250-S-CA	459
KASS-16X25-S-CA	459
KASS-16X320-S-CA	459
KASS-16X50-S-CA	459
KASS-16X80-S-CA	459
KASS-20X100-S-CA	459
KASS-20X10-S-CA	459
KASS-20X125-S-CA	459
KASS-20X160-S-CA	459
KASS-20X200-S-CA	459
KASS-20X250-S-CA	459
KASS-20X25-S-CA	459
KASS-20X320-S-CA	459
KASS-20X50-S-CA	459
KASS-20X80-S-CA	459
KASS-25X100-S-CA	459
KASS-25X10-S-CA	459
KASS-25X125-S-CA	459
KASS-25X160-S-CA	459
KASS-25X200-S-CA	459
KASS-25X250-S-CA	459
KASS-25X25-S-CA	459
KASS-25X320-S-CA	459
KASS-25X50-S-CA	459
KASS-25X80-S-CA	459
KASV-SSP-112-NC	1049
KASV-SSP-112-NO	1049
KASV-SSP-114-NC	1049
KASV-SSP-114-NO	1049
KASV-SSP-12-NC	1049
KASV-SSP-12-NO	1049
KASV-SSP-1-NC	1049
KASV-SSP-1-NO	1049
KASV-SSP-212-NC	1049
KASV-SSP-212-NO	1049
KASV-SSP-2-NC	1049
KASV-SSP-2-NO	1049
KASV-SSP-34-NC	1049
KASV-SSP-34-NO	1049
KASV-SSP-38-NC	1049
KASV-SSP-38-NO	1049
KASV-SSSS-112-NC	1049
KASV-SSSS-114-NC	1049
KASV-SSSS-12-NC	1049
KASV-SSSS-12-NO	1049
KASV-SSSS-1-NC	1049
KASV-SSSS-1-NO	1049
KASV-SSSS-212-NC	1049
KASV-SSSS-2-NC	1049
KASV-SSSS-2-NO	1049
KASV-SSSS-34-NC	1049
KASV-SSSS-34-NO	1049
KASV-SSSS-38-NC	1049
KASV-SSSS-38-NO	1049
KB132000B9	596
KB132V54T9	596
KB132V55T9	596
KB132V56T9	596
KB-16X100-S-CA	453
KB-16X10-S-CA	453
KB-16X125-S-CA	453
KB-16X150-S-CA	453
KB-16X15-S-CA	453
KB-16X160-S-CA	453
KB-16X175-S-CA	453
KB-16X200-S-CA	453
KB-16X20-S-CA	453
KB-16X250-S-CA	453
KB-16X25-S-CA	453
KB-16X300-S-CA	453
KB-16X30-S-CA	453
KB-16X40-S-CA	453
KB-16X50-S-CA	453
KB-16X60-S-CA	453
KB-16X75-S-CA	453
KB-16X80-S-CA	453
KB-20X100-S-CA	453
KB-20X10-S-CA	453
KB-20X125-S-CA	453
KB-20X150-S-CA	453
KB-20X15-S-CA	453
KB-20X160-S-CA	453
KB-20X175-S-CA	453
KB-20X200-S-CA	453
KB-20X20-S-CA	453
KB-20X250-S-CA	453
KB-20X25-S-CA	453
KB-20X300-S-CA	453
KB-20X30-S-CA	453
KB-20X350-S-CA	453
KB-20X400-S-CA	453
KB-20X40-S-CA	453
KB-20X450-S-CA	453
KB-20X500-S-CA	453
KB-20X50-S-CA	453
KB-20X60-S-CA	453
KB-20X75-S-CA	453
KB-20X80-S-CA	453
KB-25X100-S-CA	453
KB-25X10-S-CA	453
KB-25X125-S-CA	453
KB-25X150-S-CA	453
KB-25X15-S-CA	453
KB-25X160-S-CA	454

Code	Page
KB-25X175-S-CA	454
KB-25X200-S-CA	454
KB-25X20-S-CA	453
KB-25X250-S-CA	454
KB-25X25-S-CA	453
KB-25X300-S-CA	454
KB-25X30-S-CA	453
KB-25X350-S-CA	454
KB-25X400-S-CA	454
KB-25X40-S-CA	453
KB-25X450-S-CA	454
KB-25X500-S-CA	454
KB-25X50-S-CA	453
KB-25X600-S-CA	454
KB-25X60-S-CA	453
KB-25X75-S-CA	453
KB-25X80-S-CA	453
KB-32X100-S-CM	454
KB-32X10-S-CM	454
KB-32X125-S-CM	454
KB-32X150-S-CM	454
KB-32X15-S-CM	454
KB-32X160-S-CM	454
KB-32X175-S-CM	454
KB-32X200-S-CM	454
KB-32X20-S-CM	454
KB-32X250-S-CM	454
KB-32X25-S-CM	454
KB-32X300-S-CM	454
KB-32X30-S-CM	454
KB-32X350-S-CM	454
KB-32X400-S-CM	454
KB-32X40-S-CM	454
KB-32X450-S-CM	454
KB-32X500-S-CM	454
KB-32X50-S-CM	454
KB-32X600-S-CM	454
KB-32X60-S-CM	454
KB-32X75-S-CM	454
KB-32X80-S-CM	454
KB-40X100-S-CM	454
KB-40X10-S-CM	454
KB-40X125-S-CM	454
KB-40X150-S-CM	454
KB-40X15-S-CM	454
KB-40X160-S-CM	454
KB-40X175-S-CM	454
KB-40X200-S-CM	454
KB-40X20-S-CM	454
KB-40X250-S-CM	454
KB-40X25-S-CM	454
KB-40X300-S-CM	454
KB-40X30-S-CM	454
KB-40X350-S-CM	454
KB-40X400-S-CM	454
KB-40X40-S-CM	454
KB-40X450-S-CM	454
KB-40X500-S-CM	454
KB-40X50-S-CM	454
KB-40X600-S-CM	454
KB-40X60-S-CM	454
KB-40X75-S-CM	454
KB-40X80-S-CM	454
KC-10X10-S-CA	452
KC-10X15-S-CA	452
KC-10X20-S-CA	452
KC-10X25-S-CA	452
KC-10X30-S-CA	452
KC-10X40-S-CA	452
KC-10X50-S-CA	452
KC-12X10-S-CA	452
KC-12X15-S-CA	452
KC-12X20-S-CA	452
KC-12X25-S-CA	452
KC-12X30-S-CA	452
KC-12X40-S-CA	452
KC-12X50-S-CA	452
KC-16X100-S-CA	452
KC-16X10-S-CA	452
KC-16X15-S-CA	452
KC-16X20-S-CA	452
KC-16X25-S-CA	452
KC-16X30-S-CA	452
KC-16X40-S-CA	452
KC-16X50-S-CA	452
KC-16X60-S-CA	452
KC-16X75-S-CA	452
KC-16X80-S-CA	452
KC200-06	644
KC200-08	644
KC-20X100-S-CA	452
KC-20X10-S-CA	452
KC-20X125-S-CA	452
KC-20X150-S-CA	452
KC-20X15-S-CA	452
KC-20X20-S-CA	452
KC-20X25-S-CA	452
KC-20X30-S-CA	452
KC-20X40-S-CA	452
KC-20X50-S-CA	452
KC-20X60-S-CA	452
KC-20X75-S-CA	452
KC-20X80-S-CA	452
KC-25X100-S-CA	452
KC-25X10-S-CA	452
KC-25X125-S-CA	452
KC-25X150-S-CA	452
KC-25X20-S-CA	452
KC-25X25-S-CA	452
KC-25X30-S-CA	452
KC-25X40-S-CA	452
KC-25X50-S-CA	452
KC-25X60-S-CA	452
KC-25X75-S-CA	452
KC-25X80-S-CA	452
KC300-08	644
KC300-10	644
KC300-15	644
KC-32X100-S-CM	452
KC-32X10-S-CM	452
KC-32X125-S-CM	452
KC-32X150-S-CM	452
KC-32X15-S-CM	452
KC-32X20-S-CM	452
KC-32X25-S-CM	452
KC-32X30-S-CM	452
KC-32X40-S-CM	452
KC-32X50-S-CM	452
KC-32X60-S-CM	452
KC-32X75-S-CM	452
KC-32X80-S-CM	452
KC400-10	644
KC400-15	644
KC-40X100-S-CM	452
KC-40X10-S-CM	452
KC-40X125-S-CM	452
KC-40X150-S-CM	452
KC-40X15-S-CM	452
KC-40X20-S-CM	452
KC-40X25-S-CM	452
KC-40X30-S-CM	452
KC-40X40-S-CM	452
KC-40X50-S-CM	452
KC-40X60-S-CM	452
KC-40X75-S-CM	452
KC-40X80-S-CM	452
KC-8X10-S-CA	452
KC-8X15-S-CA	452
KC-8X20-S-CA	452
KC-8X25-S-CA	452
KC-8X30-S-CA	452
KC-8X40-S-CA	452
KC-8X50-S-CA	452
KCAS300-15-A-F-3	643
KCAS300-15-F-3	643
KCAS400-15-A-F-3	643
KCAS400-15-F-3	643
KCB-06	548
KCS200-06-F-3	637
KCS200-08-F-3	637
KCS300-08-A-F-3	637
KCS300-08-F-3	637
KCS300-10-A-F-3	637
KCS300-10-F-3	637
KCS300-15-A-F-3	637
KCS300-15-F-3	637
KCS400-10-A-F-3	637
KCS400-10-F-3	637
KCS400-15-A-F-3	637
KCS400-15-F-3	637
KCS600-20-A-F-3	637
KCS600-20-F-3	637
KCS600-25-A-F-3	637
KCS600-25-F-3	637
KCV1-06-A	575
KCV1-06-B	575
KCV1-06-C	575
KCV1-M5-A	575
KCV1-M5-B	575
KCV1-M5-C	575
KCV1-P30	575
KCV1-P31	575
KCV1-P32	575
KD-12	1596
KDS1-H-020	542
KDS1-H-030	542
KDS1-H-050	542
KDS1-H-C08	542
KDS1-HL-020	542
KDS1-HL-030	542
KDS1-HL-050	542
KDS1-HL-C08	542
KDS1-HL-N-020	542
KDS1-HL-N-030	542
KDS1-HL-N-050	542
KDS1-HL-N-C08	542
KDS1-HL-P-020	542
KDS1-HL-P-030	542
KDS1-HL-P-050	542
KDS1-HL-P-C08	542
KDS1-H-N-020	542
KDS1-H-N-030	542
KDS1-H-N-050	542
KDS1-H-N-C08	542
KDS1-H-P-020	542
KDS1-H-P-030	542
KDS1-H-P-050	542
KDS1-H-P-C08	542
KEY2	1488
KEY3	1488
KEY4	1488
KF200-004-1	646
KF200-004-2	646
KF200-P3	646
KF200-P6	646
KF300-004-1	646
KF300-004-2	646
KF300-P4	646
KF300-P5	646
KF300-P6	646
KF400-004-1	646
KF400-004-2	646
KF400-P10	646
KF400-P11	646
KF400-P9	646
KF600-004-1	646
KF600-004-2	646
KF600-P1	646
KF600-P2	646
KF600-P3	646
KFCS200-06-F-3	638
KFCS200-08-F-3	638
KFCS300-08-A-F-3	638
KFCS300-08-F-3	638
KFCS300-10-A-F-3	638
KFCS300-10-F-3	638
KFCS300-15-A-F-3	638
KFCS300-15-F-3	638
KFCS400-10-A-F-3	638
KFCS400-10-F-3	638
KFCS400-15-A-F-3	638
KFCS400-15-F-3	638
KFCS600-20-A-F-3	638
KFCS600-20-F-3	638
KFCS600-25-A-F-3	638
KFCS600-25-F-3	638
KFP-12-M	625
KFP-18-M	625
KFP-25-M	625
KFP-35-M	625
KFRS200-06-F-3	639
KFRS200-08-F-3	639
KFRS300-08-A-F-3	639
KFRS300-08-F-3	639
KFRS300-10-A-F-3	639
KFRS300-10-F-3	639
KFRS300-15-A-F-3	639
KFRS300-15-F-3	639
KFRS400-10-A-F-3	639
KFRS400-10-F-3	639
KFRS400-15-A-F-3	639
KFRS400-15-F-3	639
KFRS600-20-A-F-3	639
KFRS600-20-F-3	639
KFRS600-25-A-F-3	639
KFRS600-25-F-3	639
KFS200-06	642
KFS200-08	642
KFS300-08	642
KFS300-08-A	642
KFS300-10	642
KFS300-10-A	642
KFS300-15	642
KFS300-15-A	642
KFS400-10	642
KFS400-10-A	642
KFS400-15	642
KFS400-15-A	642
KFS600-20	642
KFS600-20-A	642
KFS600-25	642
KFS600-25-A	642
KG3043.20	498
KG3043.32	498
KG3043.40	498
KG3043.50	498
KG3043.63	498
KG40-10R	646
KG50-10R	646
KGA-1/4	646
KGA-1/8	646
KH3KV10L-LPORT	137
KH3KV10L-TPORT	137
KH3KV12L-LPORT	137
KH3KV12L-TPORT	137
KH3KV15L-LPORT	137
KH3KV15L-TPORT	137
KH3KV8L-LPORT	137
KHB-10L	238
KHB-10L-LK	239
KHB-10S	238
KHB-10S-LK	239
KHB-12L	238
KHB-12L-LK	239
KHB-12S	238
KHB-12S-LK	239
KHB-15L	238
KHB-15L-LK	239
KHB-16S	238
KHB-16S-LK	239
KHB-20S	238
KHB-20S-LK	239
KHB-22L	238
KHB-22L-LK	239
KHB-25S	238
KHB-25S-LK	239
KHB-28L	238
KHB-28L-LK	239
KHB-30S	238
KHB-30S-LK	239

Code	Page
KHB3K-G1	240
KHB3K-G1/2	240
KHB3K-G1/2-LK	240
KHB3K-G1/4	240
KHB3K-G1/4-LK	240
KHB3K-G11/2	240
KHB3K-G11/2-LK	240
KHB3K-G11/4	240
KHB3K-G11/4-LK	240
KHB3K-G1-LK	240
KHB3K-G3/4	240
KHB3K-G3/4-LK	240
KHB3K-G3/8	240
KHB3K-G3/8-LK	240
KHB3T-G1	240
KHB3T-G1/2	240
KHB3T-G1/2-LK	240
KHB3T-G1/4	240
KHB3T-G1/4-LK	240
KHB3T-G11/2	240
KHB3T-G11/2-LK	240
KHB3T-G11/4	240
KHB3T-G11/4-LK	240
KHB3T-G1-LK	240
KHB3T-G3/4	240
KHB3T-G3/4-LK	240
KHB3T-G3/8	240
KHB3T-G3/8-LK	240
KHB-8L	238
KHB-8L-LK	239
KHBF3-1	238
KHBF3-1.1/2	238
KHBF3-1.1/2-LK	239
KHBF3-1.1/4	238
KHBF3-1.1/4-LK	239
KHBF3-1/2	238
KHBF3-1/2-LK	239
KHBF3-1-LK	239
KHBF3-2	238
KHBF3-2-LK	239
KHBF3-3/4	238
KHBF3-3/4-LK	239
KHBF6-1	238
KHBF6-1.1/2	238
KHBF6-1.1/2-LK	239
KHBF6-1.1/4	238
KHBF6-1.1/4-LK	239
KHBF6-1/2	238
KHBF6-1/2-LK	239
KHBF6-1-LK	239
KHBF6-2-LK	239
KHBF6-3/4	238
KHBF6-6/4-LK	239
KHB-G1	238
KHB-G1/2	238
KHB-G1/2-LK	239
KHB-G1/4	238
KHB-G1/4-LK	239
KHB-G11/2	238
KHB-G11/2-LK	239
KHB-G11/4	238
KHB-G11/4-LK	239
KHB-G1-LK	239
KHB-G3/4	238
KHB-G3/4-LK	239
KHB-G3/8	238
KHB-G3/8-LK	239
KHBHANDLE-114-2	240
KHBHANDLE-14-12	240
KHBHANDLE-34-1	240
KHBSM-G1	238
KHBSM-G1/2	238
KHBSM-G1/2-LK	239
KHBSM-G1/4	238
KHBSM-G1/4-LK	239
KHBSM-G11/2	238
KHBSM-G11/2-LK	239
KHBSM-G11/4	238
KHBSM-G11/4-LK	239
KHBSM-G1-LK	239
KHBSM-G3/4	238
KHBSM-G3/4-LK	239
KHBSM-G3/8	238
KHBSM-G3/8-LK	239
KHBTM-G1	238
KHBTM-G1/2	238
KHBTM-G1/4	238
KHBTM-G11/2	238
KHBTM-G11/4	238
KHBTM-G3/4	238
KHBTM-G3/8	238
KHFY10	542
KHFY16	542
KHFY20	542
KHFY25	542
KHFY32	542
KHFY6	542
KHFZ10	542
KHFZ16	542
KHFZ20	542
KHFZ25	542
KHV10L	137
KHV10S	137
KHV12L	137
KHV12S	137
KHV14S	137
KHV15L	137
KHV16S	137
KHV18L	137
KHV20S	137
KHV22L	137
KHV25S	137
KHV28L	137
KHV30S	137
KHV35L	137
KHV38S	137
KHV42L	137
KHV6L	137
KHV8L	137
KHV8S	137
KI-100BX1000-S-G	483
KI-100BX100-S-G	483
KI-100BX125-S-G	483
KI-100BX150-S-G	483
KI-100BX160-S-G	483
KI-100BX175-S-G	483
KI-100BX200-S-G	483
KI-100BX250-S-G	483
KI-100BX25-S-G	483
KI-100BX300-S-G	483
KI-100BX350-S-G	483
KI-100BX400-S-G	483
KI-100BX450-S-G	483
KI-100BX500-S-G	483
KI-100BX50-S-G	483
KI-100BX600-S-G	483
KI-100BX700-S-G	483
KI-100BX75-S-G	483
KI-100BX800-S-G	483
KI-100BX80-S-G	483
KI-100BX900-S-G	483
KI-100X1000-S-G	481
KI-100X100-S-G	481
KI-100X125-S-G	481
KI-100X150-S-G	481
KI-100X160-S-G	481
KI-100X175-S-G	481
KI-100X200-S-G	481
KI-100X250-S-G	481
KI-100X25-S-G	481
KI-100X300-S-G	481
KI-100X350-S-G	481
KI-100X400-S-G	481
KI-100X450-S-G	481
KI-100X500-S-G	481
KI-100X50-S-G	481
KI-100X600-S-G	481
KI-100X700-S-G	481
KI-100X75-S-G	481
KI-100X800-S-G	481
KI-100X80-S-G	481
KI-100X900-S-G	481
KI-125BX1000-S-G	483
KI-125BX100-S-G	483
KI-125BX125-S-G	483
KI-125BX150-S-G	483
KI-125BX160-S-G	483
KI-125BX175-S-G	483
KI-125BX200-S-G	483
KI-125BX250-S-G	483
KI-125BX25-S-G	483
KI-125BX300-S-G	483
KI-125BX350-S-G	483
KI-125BX400-S-G	483
KI-125BX450-S-G	483
KI-125BX500-S-G	483
KI-125BX50-S-G	483
KI-125BX600-S-G	483
KI-125BX700-S-G	483
KI-125BX75-S-G	483
KI-125BX800-S-G	483
KI-125BX80-S-G	483
KI-125BX900-S-G	483
KI-125X1000-S-G	481
KI-125X100-S-G	481
KI-125X125-S-G	481
KI-125X150-S-G	481
KI-125X160-S-G	481
KI-125X175-S-G	481
KI-125X200-S-G	481
KI-125X250-S-G	481
KI-125X25-S-G	481
KI-125X300-S-G	481
KI-125X350-S-G	481
KI-125X400-S-G	481
KI-125X450-S-G	481
KI-125X500-S-G	481
KI-125X50-S-G	481
KI-125X600-S-G	481
KI-125X700-S-G	481
KI-125X75-S-G	481
KI-125X800-S-G	481
KI-125X80-S-G	481
KI-125X900-S-G	481
KI-32BX100-S-G	482
KI-32BX125-S-G	482
KI-32BX150-S-G	482
KI-32BX160-S-G	482
KI-32BX175-S-G	482
KI-32BX200-S-G	482
KI-32BX250-S-G	482
KI-32BX25-S-G	482
KI-32BX300-S-G	482
KI-32BX350-S-G	482
KI-32BX400-S-G	482
KI-32BX450-S-G	482
KI-32BX500-S-G	482
KI-32BX50-S-G	482
KI-32BX75-S-G	482
KI-32BX80-S-G	482
KI-32X100-S-G	480
KI-32X125-S-G	480
KI-32X150-S-G	480
KI-32X160-S-G	480
KI-32X175-S-G	480
KI-32X200-S-G	480
KI-32X250-S-G	480
KI-32X25-S-G	480
KI-32X300-S-G	480
KI-32X350-S-G	480
KI-32X400-S-G	480
KI-32X450-S-G	480
KI-32X500-S-G	480
KI-32X50-S-G	480
KI-32X75-S-G	480
KI-32X80-S-G	480
KI-40BX100-S-G	482
KI-40BX125-S-G	482
KI-40BX150-S-G	482
KI-40BX160-S-G	482
KI-40BX175-S-G	482
KI-40BX200-S-G	482
KI-40BX250-S-G	482
KI-40BX25-S-G	482
KI-40BX300-S-G	482
KI-40BX350-S-G	482
KI-40BX400-S-G	482
KI-40BX450-S-G	482
KI-40BX500-S-G	482
KI-40BX50-S-G	482
KI-40BX600-S-G	482
KI-40BX700-S-G	482
KI-40BX75-S-G	482
KI-40BX800-S-G	482
KI-40BX80-S-G	482
KI-40X100-S-G	480
KI-40X125-S-G	480
KI-40X150-S-G	480
KI-40X160-S-G	480
KI-40X175-S-G	480
KI-40X200-S-G	480
KI-40X250-S-G	480
KI-40X25-S-G	480
KI-40X300-S-G	480
KI-40X350-S-G	480
KI-40X400-S-G	480
KI-40X450-S-G	480
KI-40X500-S-G	480
KI-40X50-S-G	480
KI-40X600-S-G	480
KI-40X700-S-G	480
KI-40X75-S-G	480
KI-40X800-S-G	480
KI-40X80-S-G	480
KI-50BX1000-S-G	482
KI-50BX100-S-G	482
KI-50BX125-S-G	482
KI-50BX150-S-G	482
KI-50BX160-S-G	482
KI-50BX175-S-G	482
KI-50BX200-S-G	482
KI-50BX250-S-G	482
KI-50BX25-S-G	482
KI-50BX300-S-G	482
KI-50BX350-S-G	482
KI-50BX400-S-G	482
KI-50BX450-S-G	482
KI-50BX500-S-G	482
KI-50BX50-S-G	482
KI-50BX600-S-G	482
KI-50BX700-S-G	482
KI-50BX75-S-G	482
KI-50BX800-S-G	482
KI-50BX80-S-G	482
KI-50BX900-S-G	482
KI-50X1000-S-G	480
KI-50X100-S-G	480
KI-50X125-S-G	480
KI-50X150-S-G	480
KI-50X160-S-G	480
KI-50X175-S-G	480
KI-50X200-S-G	480
KI-50X250-S-G	480
KI-50X25-S-G	480
KI-50X300-S-G	480
KI-50X350-S-G	480
KI-50X400-S-G	480
KI-50X450-S-G	480
KI-50X500-S-G	480
KI-50X50-S-G	480
KI-50X600-S-G	480
KI-50X700-S-G	480
KI-50X75-S-G	480
KI-50X800-S-G	480
KI-50X80-S-G	480
KI-50X900-S-G	480
KI-63BX1000-S-G	482
KI-63BX100-S-G	482
KI-63BX125-S-G	482
KI-63BX150-S-G	482

Code	Page
KI-63BX160-S-G	482
KI-63BX175-S-G	482
KI-63BX200-S-G	482
KI-63BX250-S-G	482
KI-63BX25-S-G	482
KI-63BX300-S-G	482
KI-63BX350-S-G	482
KI-63BX400-S-G	482
KI-63BX450-S-G	482
KI-63BX500-S-G	482
KI-63BX50-S-G	482
KI-63BX600-S-G	482
KI-63BX700-S-G	482
KI-63BX75-S-G	482
KI-63BX800-S-G	482
KI-63BX80-S-G	482
KI-63BX900-S-G	482
KI-63X1000-S-G	480
KI-63X100-S-G	480
KI-63X125-S-G	480
KI-63X150-S-G	480
KI-63X160-S-G	480
KI-63X175-S-G	480
KI-63X200-S-G	480
KI-63X250-S-G	480
KI-63X25-S-G	480
KI-63X300-S-G	480
KI-63X350-S-G	480
KI-63X400-S-G	480
KI-63X450-S-G	480
KI-63X500-S-G	480
KI-63X50-S-G	480
KI-63X600-S-G	480
KI-63X700-S-G	480
KI-63X75-S-G	480
KI-63X800-S-G	480
KI-63X80-S-G	480
KI-63X900-S-G	480
KI-80BX1000-S-G	483
KI-80BX100-S-G	482
KI-80BX125-S-G	482
KI-80BX150-S-G	482
KI-80BX160-S-G	482
KI-80BX175-S-G	482
KI-80BX200-S-G	482
KI-80BX250-S-G	482
KI-80BX25-S-G	482
KI-80BX300-S-G	482
KI-80BX350-S-G	482
KI-80BX400-S-G	482
KI-80BX450-S-G	483
KI-80BX500-S-G	483
KI-80BX50-S-G	482
KI-80BX600-S-G	483
KI-80BX700-S-G	483
KI-80BX75-S-G	482
KI-80BX800-S-G	483
KI-80BX80-S-G	482
KI-80BX900-S-G	483
KI-80X1000-S-G	481
KI-80X100-S-G	480
KI-80X125-S-G	480
KI-80X150-S-G	480
KI-80X160-S-G	480
KI-80X175-S-G	480
KI-80X200-S-G	480
KI-80X250-S-G	480
KI-80X25-S-G	480
KI-80X300-S-G	480
KI-80X350-S-G	480
KI-80X400-S-G	480
KI-80X450-S-G	481
KI-80X500-S-G	481
KI-80X50-S-G	480
KI-80X600-S-G	481
KI-80X700-S-G	481
KI-80X75-S-G	480
KI-80X800-S-G	481
KI-80X80-S-G	480
KI-80X900-S-G	481
KIA 10	1476
KIA 10 BSP	1476
KIA 12	1476
KIA 12 BSP	1476
KIA 34	1476
KIA 34 BSP	1476
KIA 38	1476
KIA 38 BSP	1476
KIG10	1477
KIG12	1477
KIG14	1477
KIG34	1477
KIG38	1477
KIG54	1477
KKS-100X10	519
KKS-100X100	519
KKS-100X125	519
KKS-100X15	519
KKS-100X150	519
KKS-100X175	519
KKS-100X20	519
KKS-100X200	519
KKS-100X25	519
KKS-100X250	519
KKS-100X30	519
KKS-100X35	519
KKS-100X40	519
KKS-100X45	519
KKS-100X5	519
KKS-100X50	519
KKS-100X60	519
KKS-100X70	519
KKS-100X75	519
KKS-100X80	519
KKS-100X90	519
KKS-12X10	518
KKS-12X20	518
KKS-12X25	518
KKS-12X30	518
KKS-12X40	518
KKS-12X5	518
KKS-12X50	518
KKS-16X10	518
KKS-16X15	518
KKS-16X25	518
KKS-16X30	518
KKS-16X35	518
KKS-16X5	518
KKS-16X50	518
KKS-16X55	518
KKS-16X60	518
KKS-20X10	518
KKS-20X100	518
KKS-20X15	518
KKS-20X20	518
KKS-20X25	518
KKS-20X30	518
KKS-20X40	518
KKS-20X45	518
KKS-20X5	518
KKS-20X50	518
KKS-20X70	518
KKS-20X80	518
KKS-20X90	518
KKS-25X10	518
KKS-25X100	518
KKS-25X15	518
KKS-25X20	518
KKS-25X25	518
KKS-25X30	518
KKS-25X35	518
KKS-25X40	518
KKS-25X45	518
KKS-25X5	518
KKS-25X50	518
KKS-25X60	518
KKS-25X70	518
KKS-25X75	518
KKS-25X80	518
KKS-25X90	518
KKS-32X10	518
KKS-32X100	518
KKS-32X125	518
KKS-32X15	518
KKS-32X150	518
KKS-32X20	518
KKS-32X25	518
KKS-32X30	518
KKS-32X35	518
KKS-32X40	518
KKS-32X45	518
KKS-32X5	518
KKS-32X50	518
KKS-32X60	518
KKS-32X70	518
KKS-32X75	518
KKS-32X80	518
KKS-40X10	518
KKS-40X100	518
KKS-40X125	518
KKS-40X15	518
KKS-40X20	518
KKS-40X25	518
KKS-40X30	518
KKS-40X35	518
KKS-40X40	518
KKS-40X45	518
KKS-40X5	518
KKS-40X50	518
KKS-40X60	518
KKS-40X75	518
KKS-50X10	518
KKS-50X100	518
KKS-50X125	519
KKS-50X15	518
KKS-50X150	519
KKS-50X20	518
KKS-50X25	518
KKS-50X250	519
KKS-50X30	518
KKS-50X40	518
KKS-50X45	518
KKS-50X50	518
KKS-50X60	518
KKS-50X70	518
KKS-50X75	518
KKS-50X80	518
KKS-50X90	518
KKS-63X100	519
KKS-63X125	519
KKS-63X15	519
KKS-63X150	519
KKS-63X20	519
KKS-63X25	519
KKS-63X250	519
KKS-63X30	519
KKS-63X35	519
KKS-63X5	519
KKS-63X50	519
KKS-63X60	519
KKS-63X75	519
KKS-63X80	519
KKS-80X10	519
KKS-80X100	519
KKS-80X125	519
KKS-80X15	519
KKS-80X150	519
KKS-80X175	519
KKS-80X20	519
KKS-80X200	519
KKS-80X25	519
KKS-80X250	519
KKS-80X30	519
KKS-80X35	519
KKS-80X40	519
KKS-80X45	519
KKS-80X5	519
KKS-80X50	519
KKS-80X60	519
KKS-80X70	519
KKS-80X75	519
KKS-80X80	519
KKS-80X90	519
KKSRK-12	520
KKSRK-12-V	520
KKSRK-16	520
KKSRK-20	520
KKSRK-20-V	520
KKSRK-25	520
KKSRK-32	520
KKSRK-40	520
KKSRK-50	520
KKSRK-50-V	520
KKSRK-63	520
KKSRK-80	520
KLS200-06	641
KLS200-08	641
KLS300-08	641
KLS300-10	641
KLS300-15	641
KLS400-10	641
KLS400-15	641
KLS600-20	641
KLS600-25	641
KLS-820M	1022
KM10WN	1175
KM13WN	1175
KM17WN	1175
KM21WN	1175
KM26WN	1175
KMDS-1/2	1220
KMDS-1/4	1220
KMDS-1/8	1220
KMDS-3/8	1220
K-MI120-1	1350
K-MI120-112	1350
K-MI120-112N	1350
K-MI120-114	1350
K-MI120-114N	1350
K-MI120-12	1350
K-MI120-12N	1350
K-MI120-1N	1350
K-MI120-2	1350
K-MI120-2N	1350
K-MI120-34	1350
K-MI120-34N	1350
K-MI120-38	1350
K-MI120-38N	1350
K-MI121-1	1350
K-MI121-112	1350
K-MI121-112N	1350
K-MI121-114	1350
K-MI121-114N	1350
K-MI121-12	1350
K-MI121-12N	1350
K-MI121-1N	1350
K-MI121-2	1350
K-MI121-2N	1350
K-MI121-34	1350
K-MI121-34N	1350
K-MI121-38	1350
K-MI121-38N	1350
K-MI130-1	1351
K-MI130-112	1351
K-MI130-1-12	1352
K-MI130-112-1	1352
K-MI130-112-114	1352
K-MI130-112-114N	1352
K-MI130-112-12	1352
K-MI130-112-12N	1352
K-MI130-112-1N	1352
K-MI130-112-34	1352
K-MI130-112-34N	1352
K-MI130-112N	1351
K-MI130-1-12N	1352
K-MI130-114	1351
K-MI130-114-1	1352
K-MI130-114-12	1352
K-MI130-114-12N	1352
K-MI130-114-1N	1352

Code	Page
K-MI130-114-34	1352
K-MI130-114-34N	1352
K-MI130-114N	1351
K-MI130-12	1351
K-MI130-12-14	1352
K-MI130-12-14N	1352
K-MI130-12-34	1352
K-MI130-12-34N	1352
K-MI130-12-38	1352
K-MI130-12-38N	1352
K-MI130-12N	1351
K-MI130-1-34	1352
K-MI130-1-34N	1352
K-MI130-1-38	1352
K-MI130-1-38N	1352
K-MI130-14	1351
K-MI130-14N	1351
K-MI130-1N	1351
K-MI130-2	1351
K-MI130-2-1	1352
K-MI130-2-112	1352
K-MI130-2-112N	1352
K-MI130-2-114	1352
K-MI130-2-114N	1352
K-MI130-212	1351
K-MI130-2-12	1352
K-MI130-212N	1351
K-MI130-2-12N	1352
K-MI130-2-1N	1352
K-MI130-2-34	1352
K-MI130-2-34N	1352
K-MI130-2N	1351
K-MI130-3	1351
K-MI130-34	1351
K-MI130-34-12	1352
K-MI130-34-12N	1352
K-MI130-34-14	1352
K-MI130-34-14N	1352
K-MI130-34-38	1352
K-MI130-34N	1351
K-MI130-38	1351
K-MI130-38-14	1352
K-MI130-38-14N	1352
K-MI130-38N	1351
K-MI130-3N	1351
K-MI130-4	1351
K-MI130-4N	1351
K-MI180-1	1352
K-MI180-112	1352
K-MI180-112N	1352
K-MI180-114	1352
K-MI180-114N	1352
K-MI180-12	1352
K-MI180-12N	1352
K-MI180-14	1352
K-MI180-14N	1352
K-MI180-1N	1352
K-MI180-2	1352
K-MI180-212	1352
K-MI180-212N	1352
K-MI180-2N	1352
K-MI180-3	1352
K-MI180-34	1352
K-MI180-34N	1352
K-MI180-38	1352
K-MI180-38N	1352
K-MI180-3N	1352
K-MI180-4	1352
K-MI180-4N	1352
K-MI220-1	1352
K-MI220-112	1352
K-MI220-112N	1352
K-MI220-114	1352
K-MI220-114N	1352
K-MI220-12	1352
K-MI220-12N	1352
K-MI220-1N	1352
K-MI220-2	1352
K-MI220-212	1352
K-MI220-212N	1352
K-MI220-2N	1352
K-MI220-3	1352
K-MI220-34	1352
K-MI220-34N	1352
K-MI220-38	1352
K-MI220-38N	1352
K-MI220-3N	1352
K-MI220-4	1352
K-MI220-4N	1352
K-MI240-1-12	1353
K-MI240-112-1	1353
K-MI240-112-114	1353
K-MI240-112-114N	1353
K-MI240-112-12	1353
K-MI240-112-12N	1353
K-MI240-112-1N	1353
K-MI240-112-34	1353
K-MI240-112-34N	1353
K-MI240-1-12N	1353
K-MI240-114-1	1353
K-MI240-114-12	1353
K-MI240-114-12N	1353
K-MI240-114-1N	1353
K-MI240-114-34	1353
K-MI240-114-34N	1353
K-MI240-114-38	1353
K-MI240-114-38N	1353
K-MI240-12-14	1353
K-MI240-12-14N	1353
K-MI240-12-38	1353
K-MI240-12-38N	1353
K-MI240-1-34	1353
K-MI240-1-34N	1353
K-MI240-1-38	1353
K-MI240-1-38N	1353
K-MI240-2-1	1353
K-MI240-2-112	1353
K-MI240-2-112N	1353
K-MI240-2-114	1353
K-MI240-2-114N	1353
K-MI240-2-12	1353
K-MI240-2-12N	1353
K-MI240-2-1N	1353
K-MI240-2-34	1353
K-MI240-2-34N	1353
K-MI240-34-12	1353
K-MI240-34-12N	1353
K-MI240-34-38	1353
K-MI240-34-38N	1353
K-MI240-38-14	1353
K-MI240-38-14N	1353
K-MI241-1-12	1353
K-MI241-112-1	1353
K-MI241-112-114	1353
K-MI241-112-114N	1353
K-MI241-112-12	1353
K-MI241-112-12N	1353
K-MI241-112-1N	1353
K-MI241-112-34	1353
K-MI241-112-34N	1353
K-MI241-1-12N	1353
K-MI241-1-14	1353
K-MI241-114-1	1353
K-MI241-114-12	1353
K-MI241-114-12N	1353
K-MI241-114-1N	1353
K-MI241-114-34	1353
K-MI241-114-34N	1353
K-MI241-114-38	1353
K-MI241-1-14N	1353
K-MI241-12-14	1353
K-MI241-12-14N	1353
K-MI241-12-38	1353
K-MI241-12-38N	1353
K-MI241-1-34	1353
K-MI241-1-34N	1353
K-MI241-1-38	1353
K-MI241-1-38N	1353
K-MI241-2-1	1353
K-MI241-2-112	1353
K-MI241-2-112N	1353
K-MI241-2-114	1353
K-MI241-2-114N	1353
K-MI241-2-12	1353
K-MI241-212-1	1353
K-MI241-212-112	1353
K-MI241-212-112N	1353
K-MI241-212-114	1353
K-MI241-212-114N	1353
K-MI241-212-12	1353
K-MI241-212-12N	1353
K-MI241-212-1N	1353
K-MI241-212-2	1353
K-MI241-212-2N	1353
K-MI241-212-34	1353
K-MI241-212-34N	1353
K-MI241-2-12N	1353
K-MI241-2-1N	1353
K-MI241-2-34	1353
K-MI241-2-34N	1353
K-MI241-3-1	1353
K-MI241-3-112	1353
K-MI241-3-112N	1353
K-MI241-3-1N	1353
K-MI241-3-2	1353
K-MI241-3-212	1353
K-MI241-3-212N	1353
K-MI241-3-2N	1353
K-MI241-34-12	1353
K-MI241-34-12N	1353
K-MI241-34-14	1353
K-MI241-34-14N	1353
K-MI241-34-38	1353
K-MI241-34-38N	1353
K-MI241-38-14	1353
K-MI241-38-14N	1353
K-MI241-4-1	1353
K-MI241-4-112	1353
K-MI241-4-112N	1353
K-MI241-4-114	1353
K-MI241-4-114N	1353
K-MI241-4-1N	1353
K-MI241-4-2	1353
K-MI241-4-212	1353
K-MI241-4-212N	1353
K-MI241-4-2N	1353
K-MI241-4-3	1353
K-MI241-4-34	1353
K-MI241-4-34N	1353
K-MI241-4-3N	1353
K-MI245-1-12	1349
K-MI245-112-1	1349
K-MI245-112-114	1349
K-MI245-112-114N	1349
K-MI245-112-12	1349
K-MI245-112-12N	1349
K-MI245-112-1N	1349
K-MI245-112-34	1349
K-MI245-112-34N	1349
K-MI245-1-12N	1349
K-MI245-114-1	1349
K-MI245-114-12	1349
K-MI245-114-12N	1349
K-MI245-114-1N	1349
K-MI245-114-34	1349
K-MI245-114-34N	1349
K-MI245-12-14	1349
K-MI245-12-14N	1349
K-MI245-12-38	1349
K-MI245-12-38N	1349
K-MI245-1-34	1349
K-MI245-1-34N	1349
K-MI245-1-38	1349
K-MI245-2-1	1349
K-MI245-2-112	1349
K-MI245-2-112N	1349
K-MI245-2-114	1349
K-MI245-2-114N	1349
K-MI245-2-12	1349
K-MI245-212-112	1349
K-MI245-212-112N	1349
K-MI245-212-2	1349
K-MI245-212-2N	1349
K-MI245-2-12N	1349
K-MI245-2-1N	1349
K-MI245-2-34	1349
K-MI245-2-34N	1349
K-MI245-3-2	1349
K-MI245-3-212	1349
K-MI245-3-212N	1349
K-MI245-3-2N	1349
K-MI245-34-12	1349
K-MI245-34-12N	1349
K-MI245-34-14	1349
K-MI245-34-14N	1349
K-MI245-34-38	1349
K-MI245-34-38N	1349
K-MI245-38-14	1349
K-MI245-38-14N	1349
K-MI245-4-3	1349
K-MI245-4-3N	1349
K-MI280-1	1349
K-MI280-112	1349
K-MI280-112N	1349
K-MI280-114	1349
K-MI280-114N	1349
K-MI280-12	1349
K-MI280-12N	1349
K-MI280-14	1349
K-MI280-14N	1349
K-MI280-1N	1349
K-MI280-2	1349
K-MI280-212	1349
K-MI280-212N	1349
K-MI280-2N	1349
K-MI280-3	1349
K-MI280-34	1349
K-MI280-34N	1349
K-MI280-38	1349
K-MI280-38N	1349
K-MI280-3N	1349
K-MI280-4	1349
K-MI280-4N	1349
K-MI291-1	1354
K-MI291-112	1354
K-MI291-112N	1354
K-MI291-114	1354
K-MI291-114N	1354
K-MI291-12	1354
K-MI291-12N	1354
K-MI291-14	1354
K-MI291-14N	1354
K-MI291-1N	1354
K-MI291-2	1354
K-MI291-212	1354
K-MI291-212N	1354
K-MI291-2N	1354
K-MI291-3	1354
K-MI291-34	1354
K-MI291-34N	1354
K-MI291-38	1354
K-MI291-38N	1354
K-MI291-3N	1354
K-MI291-4	1354
K-MI291-4N	1354
K-MI291S-1	1354
K-MI291S-112	1354
K-MI291S-112N	1354
K-MI291S-114	1354
K-MI291S-114N	1354
K-MI291S-12	1354
K-MI291S-12N	1354
K-MI291S-14	1354
K-MI291S-14N	1354
K-MI291S-1N	1354
K-MI291S-2	1354
K-MI291S-212	1354
K-MI291S-212N	1354
K-MI291S-2N	1354
K-MI291S-3	1354

Code	Page
K-MI291S-34	1354
K-MI291S-34N	1354
K-MI291S-38	1354
K-MI291S-38N	1354
K-MI291S-3N	1354
K-MI291S-4	1354
K-MI291S-4N	1354
K-MI300-1	1355
K-MI300-112	1355
K-MI300-112N	1355
K-MI300-114	1355
K-MI300-114N	1355
K-MI300-12	1355
K-MI300-12N	1355
K-MI300-14	1355
K-MI300-1N	1355
K-MI300-2	1355
K-MI300-2N	1355
K-MI300-34	1355
K-MI300-34N	1355
K-MI300-38	1355
K-MI300-38N	1355
K-MI310-1	1354
K-MI310-112N	1354
K-MI310-114	1354
K-MI310-114N	1354
K-MI310-12	1354
K-MI310-12N	1354
K-MI310-14N	1354
K-MI310-2	1354
K-MI310-212	1354
K-MI310-212N	1354
K-MI310-2N	1354
K-MI310-3	1354
K-MI310-34	1354
K-MI310-34N	1354
K-MI310-38	1354
K-MI310-38N	1354
K-MI310-3N	1354
K-MI310-4	1354
K-MI310-4N	1354
K-MI330-1	1355
K-MI330-112	1355
K-MI330-112N	1355
K-MI330-114	1355
K-MI330-114N	1355
K-MI330-12	1355
K-MI330-12N	1355
K-MI330-1N	1355
K-MI330-2	1355
K-MI330-212	1355
K-MI330-212N	1355
K-MI330-2N	1355
K-MI330-3	1355
K-MI330-34	1355
K-MI330-34N	1355
K-MI330-38	1355
K-MI330-38N	1355
K-MI330-3N	1355
K-MI330-4	1355
K-MI330-4N	1355
K-MI331-1	1355
K-MI331-112	1355
K-MI331-112N	1355
K-MI331-114	1355
K-MI331-114N	1355
K-MI331-12	1355
K-MI331-12N	1355
K-MI331-1N	1355
K-MI331-2	1355
K-MI331-2N	1355
K-MI331-34	1355
K-MI331-34N	1355
K-MI342A-1	1355
K-MI342A-112	1355
K-MI342A-112N	1355
K-MI342A-114	1355
K-MI342A-114N	1355
K-MI342A-12	1355
K-MI342A-12N	1355
K-MI342A-1N	1355
K-MI342A-2	1355
K-MI342A-2N	1355
K-MI342A-34	1355
K-MI342A-34N	1355
K-MI90-1	1350
K-MI90-112	1350
K-MI90-1-12	1351
K-MI90-112-1	1351
K-MI90-112-114N	1351
K-MI90-112-12	1351
K-MI90-112-12N	1351
K-MI90-112-1N	1351
K-MI90-112-34	1351
K-MI90-112-34N	1351
K-MI90-112N	1350
K-MI90-1-12N	1351
K-MI90-114	1350
K-MI90-1-14	1351
K-MI90-114-1	1351
K-MI90-114-12	1351
K-MI90-114-12N	1351
K-MI90-114-1N	1351
K-MI90-114-34	1351
K-MI90-114-34N	1351
K-MI90-114-38	1351
K-MI90-114-38N	1351
K-MI90-114N	1350
K-MI90-1-14N	1351
K-MI90-12	1350
K-MI90-12-14	1351
K-MI90-12-14N	1351
K-MI90-12-38	1351
K-MI90-12-38N	1351
K-MI90-12N	1350
K-MI90-1-34N	1351
K-MI90-1-38	1351
K-MI90-1-38N	1351
K-MI90-14	1350
K-MI90-14N	1350
K-MI90-1N	1350
K-MI90-2	1350
K-MI90-2-1	1351
K-MI90-2-112	1351
K-MI90-2-112N	1351
K-MI90-2-114	1351
K-MI90-2-114N	1351
K-MI90-212	1350
K-MI90-2-12	1351
K-MI90-212-1	1351
K-MI90-212-112	1351
K-MI90-212-112N	1351
K-MI90-212-114	1351
K-MI90-212-114N	1351
K-MI90-212-12	1351
K-MI90-212-12N	1351
K-MI90-212-1N	1351
K-MI90-212-2	1351
K-MI90-212-2N	1351
K-MI90-212-34	1351
K-MI90-212-34N	1351
K-MI90-212N	1350
K-MI90-2-12N	1351
K-MI90-2-1N	1351
K-MI90-2-34	1351
K-MI90-2-34N	1351
K-MI90-2N	1350
K-MI90-3	1350
K-MI90-3-1	1351
K-MI90-3-112	1351
K-MI90-3-112N	1351
K-MI90-3-114	1351
K-MI90-3-114N	1351
K-MI90-3-1N	1351
K-MI90-3-2	1351
K-MI90-3-212	1351
K-MI90-3-212N	1351
K-MI90-3-2N	1351
K-MI90-3-34	1351
K-MI90-3-34N	1351
K-MI90-34	1350
K-MI90-34-12	1351
K-MI90-34-12N	1351
K-MI90-34-14	1351
K-MI90-34-14N	1351
K-MI90-34-38	1351
K-MI90-34-38N	1351
K-MI90-34N	1350
K-MI90-38	1350
K-MI90-38-14	1351
K-MI90-38-14N	1351
K-MI90-38N	1350
K-MI90-3N	1350
K-MI90-4	1350
K-MI90-4-112	1351
K-MI90-4-112N	1351
K-MI90-4-114	1351
K-MI90-4-114N	1351
K-MI90-4-2	1351
K-MI90-4-212	1351
K-MI90-4-212N	1351
K-MI90-4-2N	1351
K-MI90-4-3	1351
K-MI90-4-3N	1351
K-MI90-4N	1350
K-MI92-1	1350
K-MI92-112	1350
K-MI92-114	1350
K-MI92-12	1350
K-MI92-14	1350
K-MI92-2	1350
K-MI92-212	1350
K-MI92-3	1350
K-MI92-34	1350
K-MI92-38	1350
K-MI92-4	1350
KOR-10L-6L	154
KOR-10L-8L	154
KOR-10S-6S	154
KOR-10S-8S	154
KOR-12L-10L	154
KOR-12L-6L	154
KOR-12L-8L	154
KOR-12S-10S	154
KOR-12S-6S	154
KOR-12S-8S	154
KOR-14S-10S	154
KOR-14S-12S	154
KOR-14S-6S	154
KOR-14S-8S	154
KOR-15L-10L	154
KOR-15L-12L	154
KOR-15L-6L	154
KOR-15L-8L	154
KOR-16S-10S	154
KOR-16S-12S	154
KOR-16S-14S	154
KOR-16S-6S	154
KOR-16S-8S	154
KOR-18L-10L	154
KOR-18L-12L	154
KOR-18L-15L	154
KOR-18L-6L	154
KOR-18L-8L	154
KOR-20S-10S	154
KOR-20S-12S	154
KOR-20S-14S	154
KOR-20S-16S	154
KOR-20S-6S	154
KOR-20S-8S	154
KOR-22L-10L	154
KOR-22L-12L	154
KOR-22L-15L	154
KOR-22L-18L	154
KOR-22L-6L	154
KOR-22L-8L	154
KOR-25S-10S	154
KOR-25S-12S	154
KOR-25S-14S	154
KOR-25S-16S	154
KOR-25S-20S	154
KOR-25S-6S	154
KOR-25S-8S	154
KOR-28L-10L	154
KOR-28L-12L	154
KOR-28L-15L	154
KOR-28L-18L	154
KOR-28L-22L	154
KOR-28L-6L	154
KOR-28L-8L	154
KOR-30S-10S	154
KOR-30S-12S	154
KOR-30S-14S	154
KOR-30S-16S	154
KOR-30S-20S	154
KOR-30S-25S	154
KOR-30S-6S	154
KOR-30S-8S	154
KOR-35L-10L	154
KOR-35L-12L	154
KOR-35L-15L	154
KOR-35L-18L	154
KOR-35L-22L	154
KOR-35L-28L	154
KOR-35L-6L	154
KOR-35L-8L	154
KOR-38S-10S	154
KOR-38S-12S	154
KOR-38S-14S	154
KOR-38S-16S	154
KOR-38S-20S	154
KOR-38S-25S	154
KOR-38S-30S	154
KOR-38S-6S	154
KOR-38S-8S	154
KOR-42L-10L	154
KOR-42L-12L	154
KOR-42L-15L	154
KOR-42L-18L	154
KOR-42L-22L	154
KOR-42L-28L	154
KOR-42L-35L	154
KOR-8L-6L	154
KOR-8S-6S	154
KP000744	616
KP010444	615
KP010464	615
KP040034	611
KP05BKR	1759
KP080214	611
KP080254	611
KP080394	611
KP080494	611
KP081564	616
KP100014	615
KP100094	615
KP100354	615
KP2005	616
KP30BKR	1759
KP40BKR	1759
KPBU081564	616
KPMB40R	410
KPMB50R	410
K-PR010B-P1	646
KR10-12SSAR	84
KR10-6SSAR	84
KR10-8SSAR	84
KR12-12SSAR	84
KR12-8SSAR	84
KR14-12SSAR	84
KR14-16SSAR	84
KR14-8SSAR	84
KR16-12SSAR	84
KR16-16SSAR	84
KR200-010-4490	140
KR200-010-9790	140
KR200-011-4490	140
KR200-011-9790	140
KR200-114-4490	140
KR200-114-9790	140

Code	Page
KR200-211-4490	140
KR200-211-9790	140
KR200-212-4490	140
KR200-212-9790	140
KR200-214-4490	140
KR200-214-9790	140
KR200-217-4490	140
KR200-217-9790	140
KR200-222-4490	140
KR200-222-9790	140
KR200-613-4490	140
KR200-613-9790	140
KR200-614-4490	140
KR200-614-9790	140
KR20-12SSAR	84
KR20-16SSAR	84
KR20-20SSAR	84
KR207-071-4490	140
KR207-071-9790	140
KR32-24SSAR	84
KR32-32SSAR	84
KR4-2SSAR	84
KR4-4SSAR	84
KR5-2SSAR	84
KR5-4SSAR	84
KR5-6SSAR	84
KR6-4SSAR	84
KR6-6SSAR	84
KR8-4SSAR	84
KR8-6SSAR	84
KR8-8SSAR	84
KRA12-12BJ	84
KRA4-4BJ	84
KRA6-6BJ	84
KRA8-8BJ	84
KRAB12T-12	83
KRAB16T-16	83
KRAB24T-24	83
KRAB4T-4	83
KRAB6T-4	83
KRAB6T-6	83
KRAB8T-8	83
KRAM10-4MSCR	139
KRAM10-6BHR	139
KRAM10-6BJR	139
KRAM10-6FOTR	139
KRAM10-6MSCR	139
KRAM10-8MSCR	139
KRAM10BCR	139
KRAM10BPR	138
KRAM10CR	138
KRAM10ER	138
KRAM10-M6RNR	140
KRAM10-M8RNR	140
KRAM10TR	138
KRAM12-12MSCR	139
KRAM12-4MSCR	139
KRAM12-6BHR	139
KRAM12-6BJR	139
KRAM12-6FOTR	139
KRAM12-6FSCR	139
KRAM12-6MSCR	139
KRAM12-8MSCR	139
KRAM12BCR	139

Code	Page
KRAM12BPR	138
KRAM12CR	138
KRAM12ER	138
KRAM12-M10RNR	140
KRAM12-M8RNR	140
KRAM12-M8ROTR	138
KRAM12TR	138
KRAM16-12MSCR	139
KRAM16-6MSCR	139
KRAM16-8BHR	139
KRAM16-8BJR	139
KRAM16-8FOTR	139
KRAM16-8FSCR	139
KRAM16-8MSCR	139
KRAM16BCR	139
KRAM16BPR	138
KRAM16CR	138
KRAM16ER	138
KRAM16-M12RNR	140
KRAM16-M8RNR	140
KRAM16-M8ROTR	138
KRAM16TR	138
KRAM20-12BHR	139
KRAM20-12BJR	139
KRAM20-12FSCR	139
KRAM20-12MSCR	139
KRAM20-16MSCR	139
KRAM20-8MSCR	139
KRAM20BCR	139
KRAM20BPR	138
KRAM20CR	138
KRAM20ER	138
KRAM20-M10RNR	140
KRAM20-M12RNR	140
KRAM20-M16RNR	140
KRAM20-M8ROTR	138
KRAM20TR	138
KRAM22BCR	139
KRAM22BPR	138
KRAM22CR	138
KRAM22ER	138
KRAM22TR	138
KRAM25-12MSCR	139
KRAM25-16BHR	139
KRAM25-16BJR	139
KRAM25-16FSCR	139
KRAM25-16MSCR	139
KRAM25-20MSCR	139
KRAM25BCR	139
KRAM25BPR	138
KRAM25CR	138
KRAM25ER	138
KRAM25-M12RNR	140
KRAM25-M12ROTR	138
KRAM25-M16RNR	140
KRAM25-M16ROTR	138
KRAM25-M20RNR	140
KRAM25TR	138
KRAM30-16MSCR	139
KRAM30-20BJR	139
KRAM30-20FOTR	139
KRAM30-20FSCR	139
KRAM30-20MSCR	139
KRAM30BCR	139

Code	Page
KRAM30BPR	138
KRAM30CR	138
KRAM30ER	138
KRAM30-M16ROTR	138
KRAM30-M25RNR	140
KRAM30TR	138
KRAM38-16MSCR	139
KRAM38-20BHR	139
KRAM38-20FOTR	139
KRAM38-20MSCR	139
KRAM38-24BHR	139
KRAM38-24BJR	139
KRAM38-24FOTR	139
KRAM38-24FSCR	139
KRAM38-24MSCR	139
KRAM38BCR	139
KRAM38BPR	138
KRAM38CR	138
KRAM38ER	138
KRAM38-M20RNR	140
KRAM38-M20ROTR	138
KRAM38-M25RNR	140
KRAM38-M30RNR	140
KRAM38TR	138
KRAM50-20MSCR	139
KRAM50-24FOTR	139
KRAM50-24MSCR	139
KRAM50-32FSCR	139
KRAM50-32MSCR	139
KRAM50BCR	139
KRAM50BPR	138
KRAM50CR	138
KRAM50ER	138
KRAM50-M25RNR	140
KRAM50-M30RNR	140
KRAM50-M38RNR	140
KRAM50TR	138
KRAM6-2MSCR	139
KRAM6-4BJR	139
KRAM6-4FSCR	139
KRAM6-4MSCR	139
KRAM6-6MSCR	139
KRAM6BPR	138
KRAM6CR	138
KRAM6ER	138
KRAM6TR	138
KRAM8-2MSCR	139
KRAM8-4BHR	139
KRAM8-4BJR	139
KRAM8-4MSCR	139
KRAM8-6FSCR	139
KRAM8-6MSCR	139
KRAM8BCR	139
KRAM8BPR	138
KRAM8CR	138
KRAM8ER	138
KRAM8TR	138
KRBV2	82
KREFE12	83
KREFE16	83
KREFE2	83
KREFE20	83
KREFE24	83
KREFE32	83

Code	Page
KREFE4	83
KREFE6	83
KREFE8	83
KREFT12	83
KREFT16	83
KREFT2	83
KREFT20	83
KREFT24	83
KREFT32	83
KREFT4	83
KREFT6	83
KREFT8	83
KREME12	83
KREME16	83
KREME20	83
KREME24	83
KREME4	83
KREME6	83
KREME8	83
KREU10	82
KREU12	82
KREU16	82
KREU2	82
KREU20	82
KREU24	82
KREU32	82
KREU4	82
KREU6	82
KREU8	82
KREUBH10	82
KREUBH12	82
KREUBH16	82
KREUBH20	82
KREUBH24	82
KREUBH4	82
KREUBH6	82
KREUBH8	82
KREUPAT12	82
KREUPAT16	82
KREUPAT2	82
KREUPAT20	82
KREUPAT4	82
KREUPAT6	82
KREUPAT8	82
KREUPT12	82
KREUPT16	82
KREUPT2	82
KREUPT20	82
KREUPT24	82
KREUPT32	82
KREUPT4	82
KREUPT6	82
KREUPT8	82
KRF-100X100-0	486
KRF-100X100-1	486
KRF-100X160-0	486
KRF-100X160-1	486
KRF-100X200-0	486
KRF-100X200-1	486
KRF-100X250-0	486
KRF-100X250-1	486
KRF-100X320-0	486
KRF-100X320-1	486
KRF-100X400-0	486

Code	Page
KRF-100X400-1	486
KRF-100X50-0	486
KRF-100X500-0	486
KRF-100X500-1	486
KRF-100X50-1	486
KRF-16X100-0	456
KRF-16X100-1	456
KRF-16X160-0	456
KRF-16X160-1	456
KRF-16X200-0	456
KRF-16X200-1	456
KRF-16X250-0	456
KRF-16X250-1	456
KRF-16X320-0	456
KRF-16X320-1	456
KRF-16X400-0	456
KRF-16X400-1	456
KRF-16X50-0	456
KRF-16X500-0	456
KRF-16X500-1	456
KRF-16X50-1	456
KRF-20X100-0	456
KRF-20X100-1	456
KRF-20X160-0	456
KRF-20X160-1	456
KRF-20X200-0	456
KRF-20X200-1	456
KRF-20X250-0	456
KRF-20X250-1	456
KRF-20X320-0	456
KRF-20X320-1	456
KRF-20X400-0	456
KRF-20X400-1	456
KRF-20X50-0	456
KRF-20X500-0	456
KRF-20X500-1	456
KRF-20X50-1	456
KRF-25X100-0	456
KRF-25X100-1	456
KRF-25X160-0	456
KRF-25X160-1	456
KRF-25X200-0	456
KRF-25X200-1	456
KRF-25X250-0	456
KRF-25X250-1	456
KRF-25X320-0	456
KRF-25X320-1	456
KRF-25X400-0	456
KRF-25X400-1	456
KRF-25X50-0	456
KRF-25X500-0	456
KRF-25X500-1	456
KRF-25X50-1	456
KRF-32X100-0	486
KRF-32X100-1	486
KRF-32X160-0	486
KRF-32X160-1	486
KRF-32X200-0	486
KRF-32X200-1	486
KRF-32X250-0	486
KRF-32X250-1	486
KRF-32X320-0	486
KRF-32X320-1	486
KRF-32X400-0	486

Code	Page
KRF-32X400-1	486
KRF-32X50-0	486
KRF-32X500-0	486
KRF-32X500-1	486
KRF-32X50-1	486
KRF-40X100-0	486
KRF-40X100-1	486
KRF-40X160-0	486
KRF-40X160-1	486
KRF-40X200-0	486
KRF-40X200-1	486
KRF-40X250-0	486
KRF-40X250-1	486
KRF-40X320-0	486
KRF-40X320-1	486
KRF-40X400-0	486
KRF-40X400-1	486
KRF-40X50-0	486
KRF-40X500-0	486
KRF-40X500-1	486
KRF-40X50-1	486
KRF-50X100-0	486
KRF-50X100-1	486
KRF-50X160-0	486
KRF-50X160-1	486
KRF-50X200-0	486
KRF-50X200-1	486
KRF-50X250-0	486
KRF-50X250-1	486
KRF-50X320-0	486
KRF-50X320-1	486
KRF-50X400-0	486
KRF-50X400-1	486
KRF-50X50-0	486
KRF-50X500-0	486
KRF-50X500-1	486
KRF-50X50-1	486
KRF-63X100-0	486
KRF-63X100-1	486
KRF-63X160-0	486
KRF-63X160-1	486
KRF-63X200-0	486
KRF-63X200-1	486
KRF-63X250-0	486
KRF-63X250-1	486
KRF-63X320-0	486
KRF-63X320-1	486
KRF-63X400-0	486
KRF-63X400-1	486
KRF-63X50-0	486
KRF-63X500-0	486
KRF-63X500-1	486
KRF-63X50-1	486
KRF-80X100-0	486
KRF-80X100-1	486
KRF-80X160-0	486
KRF-80X160-1	486
KRF-80X200-0	486
KRF-80X200-1	486
KRF-80X250-0	486
KRF-80X250-1	486
KRF-80X320-0	486
KRF-80X320-1	486
KRF-80X400-0	486
KRF-80X400-1	486
KRF-80X50-0	486
KRF-80X500-0	486
KRF-80X500-1	486
KRF-80X50-1	486
KRFA12-12	83
KRFA16-16	83
KRFA20-20	83
KRFA4-2	83
KRFA4-4	83
KRFA6-2	83
KRFA6-4	83
KRFA6-6	83
KRFA8-2	83
KRFA8-4	83
KRFA8-6	83
KRFA8-8	83
KRFOMT12	83
KRFOMT16	83
KRFOMT20	83
KRFOMT24	83
KRFOMT4	83
KRFOMT6	83
KRFOMT8	83
KRGA4-4	84
KRGA6-4	84
KRGA8-4	84
KRM10-4SSAR	84
KRM10-6SSAR	84
KRM10BPGR	140
KRM10NCR	140
KRM10R	140
KRM10W	140
KRM12-4SSAR	84
KRM12-6SSAR	84
KRM12-8SSAR	84
KRM12NCR	140
KRM12R	140
KRM12W	140
KRM16-12SSAR	84
KRM16-6SSAR	84
KRM16-8SSAR	84
KRM16NCR	140
KRM16R	140
KRM16W	140
KRM20-12SSAR	84
KRM20-8SSAR	84
KRM20BPGR	140
KRM20NCR	140
KRM20R	140
KRM20W	140
KRM22-12SSAR	84
KRM22-16SSAR	84
KRM22-8SSAR	84
KRM22BPGR	140
KRM22NCR	140
KRM22R	140
KRM22W	140
KRM25-12SSAR	84
KRM25-16SSAR	84
KRM25BPGR	140
KRM25NCR	140
KRM25R	140
KRM25W	140
KRM30-12SSAR	84
KRM30-16SSAR	84
KRM30-20SSAR	84
KRM30BPGR	140
KRM30NCR	140
KRM30R	140
KRM30W	140
KRM38-16SSAR	84
KRM38-20SSAR	84
KRM38-24SSAR	84
KRM38BPGR	140
KRM38NCR	140
KRM38R	140
KRM38W	140
KRM50-24SSAR	84
KRM50-32SSAR	84
KRM50BPGR	140
KRM50NCR	140
KRM50R	140
KRM50W	140
KRM6-2SSAR	84
KRM6-4SSAR	84
KRM6BPGR	140
KRM6NCR	140
KRM6R	140
KRM6W	140
KRM8-2SSAR	84
KRM8-4SSAR	84
KRM8-6SSAR	84
KRM8BPGR	140
KRM8NCR	140
KRM8R	140
KRM8W	140
KRP10	84
KRP12	84
KRP16	84
KRP2	84
KRP20	84
KRP24	84
KRP2AB	84
KRP32	84
KRP4	84
KRP6	84
KRP8	84
KRPT12	84
KRPT16	84
KRPT2	84
KRPT20	84
KRPT4	84
KRPT6	84
KRPT8	84
KRRB10-8	82
KRRB12-4	82
KRRB12-6	82
KRRB12-8	82
KRRB16-12	82
KRRB16-4	82
KRRB16-6	82
KRRB16-8	82
KRRB20-12	82
KRRB20-16	82
KRRB20-4	82
KRRB20-6	82
KRRB20-8	82
KRRB24-12	82
KRRB24-16	82
KRRB24-20	82
KRRB24-8	82
KRRB32-16	82
KRRB32-20	82
KRRB32-24	82
KRRB4-2	82
KRRB6-2	82
KRRB6-4	82
KRRB8-2	82
KRRB8-4	82
KRRB8-6	82
KRS-2.5	460
KRS200-06	640
KRS200-06-F-3	640
KRS200-08	640
KRS200-08-F-3	640
KRS300-08-F-3	640
KRS300-10-F-3	640
KRS300-15-F-3	640
KRS400-10-F-3	640
KRS400-15-F-3	640
KRS600-20-F-3	640
KRS600-25-F-3	640
KRUU10-4	82
KRUU10-6	82
KRUU10-8	82
KRUU12-10	82
KRUU12-6	82
KRUU12-8	82
KRUU16-10	82
KRUU16-12	82
KRUU16-14	82
KRUU16-8	82
KRUU20-12	82
KRUU20-16	82
KRUU24-16	82
KRUU24-20	82
KRUU32-16	82
KRUU32-20	82
KRUU32-24	82
KRUU4-2	82
KRUU6-4	82
KRUU8-4	82
KRUU8-6	82
KSCHS-06-B	547
KSCHS-06-G	547
KSCHS-06-R	547
KSCL-06	548
KSCPF-06-B	547
KSCPF-06-G	547
KSCPF-06-R	547
KSCPL-06-R	547
KSCPM-06-B	547
KSCPM-06-G	547
KSCPM-06-R	547
KSCPP-06-B	547
KSCPP-06-G	547
KSCPP-06-R	547
KSCR-06	548
KSCV-06	548
KSS-100-LB	520
KSS-12-FAFB	520
KSS-12-LB	520
KSS-16-FAFB	520
KSS1-G	520
KSS-20-CB	520
KSS-20-FAFB	520
KSS-20-LB	520
KSS-20-LBS-P1	520
KSS-25-FAFB	520
KSS-25-LB	520
KSS-25-LBS-P1	520
KSS-32-CB	520
KSS-32-FAFB	520
KSS-32-LB	520
KSS-40-CB	520
KSS-40-FAFB	520
KSS-40-LB	520
KSS-50-CB	520
KSS-50-FAFB	520
KSS-50-LB	520
KSS-50-LBS-P1	520
KSS-63-CB	520
KSS-63-FAFB	520
KSS-63-LB	520
KSS-80-CB	520
KSS-80-FAFB	520
KSV-06	549
KSV-08	549
KSV-10	549
KSV-15	549
KSV-20	549
KSV-25	549
KSY-06	547
KTC-1	905
KU-33.006	537
KU-33.21.326	537
KU-40.100	537
KU-50.670	614
KU-50.680	614
KU-51.020.03.00	614
KU-51.020.30.00	614
KU-54.022	614
KU-54.023	614
KU-54.024	614
KUNL-100/108	198
KUNL-100/114.3	198
KUNL-20/25	198
KUNL-20/26.9	198
KUNL-25/30	198
KUNL-25/33.7	198
KUNL-32/38	198
KUNL-40/44.5	198
KUNL-40/48.3	198
KUNL-50/57	198
KUNL-50/60.3	198
KUNL-65/76.1	198
KUNL-80/88.9	198
KUPL-100/108	198
KUPL-100/114.3	198
KUPL-15/17.2	198
KUPL-15/21.3	198
KUPL-20/25	198
KUPL-20/26.9	198
KUPL-25/30	198
KUPL-25/33.7	198

Code	Page
KUPL-32/38	198
KUPL-32/42.4	198
KUPL-40/44.5	198
KUPL-40/48.3	198
KUPL-50/57	198
KUPL-50/60.3	198
KUPL-65/76.1	198
KUPL-80/88.9	198
KV10L	125
KV10S	125
KV12L	125
KV12S	125
KV14S	125
KV15L	125
KV16S	125
KV18L	125
KV20S	125
KV22L	125
KV25S	125
KV28L	125
KV30S	125
KV35L	125
KV38S	125
KV42L	125
KV4LL	125
KV6L	125
KV6LL	125
KV6S	125
KV8L	125
KV8LL	125
KV8S	125
KVT	1028
KZ200-06	644
KZ200-08	644
KZ300-08	644
KZ300-10	644
KZ300-15	644
KZ400-10	644
KZ400-15	644
L	
L 41 125	510
L 41 160	510
L 41 200	510
L 41 32	510
L 41 40	510
L 41 50	510
L 41 63	510
L 41 80	510
L07-100-MPQG	690
L10 1021-14	1005
L10 1021-38	1005
L10 1070-12	1006
L10 1070-14	1006
L10 1070-34	1006
L10 1070-38	1006
L10 1071-12	1006
L10 1071-14	1006
L10 1071-34	1006
L10 1071-38	1006
L10 6400-1	1005
L10 6400-114	1005
L10 6400-12	1005
L10 6400-34	1005
L133B06-1-110	1033
L133B06-1-230	1033
L133B06-1-24	1033
L133B06-1-2450	1033
L133B07-34-110	1033
L133B07-34-230	1033
L133B07-34-24	1033
L133B07-34-2450	1033
L133B16-12-110	1033
L133B16-12-230	1033
L133B16-12-24	1033
L133B16-12-2450	1033
L133B16-38-110	1033
L133B16-38-230	1033
L133B16-38-24	1033
L133B16-38-2450	1033
L145R2-1-110	1033
L145R2-12-110	1033
L145R2-12-230	1033
L145R2-12-24	1033
L145R2-1-230	1033
L145R4-34-110	1033
L145R4-34-230	1033
L153D07-12-110*	1034
L153D07-12-230*	1034
L153D07-12-24*	1034
L153D07-34-110	1034
L153D07-34-230	1034
L153D07-34-24	1034
L153D5-1-110	1034
L153D5-1-230	1034
L153D5-1-24	1034
L182D01-1-110	1032
L182D01-12-110	1032
L182D01-12-230	1032
L182D01-12-24	1032
L182D01-12-2450	1032
L182D01-1-230	1032
L182D01-1-24	1032
L182D01-1-2450	1032
L182D01-34-110	1032
L182D01-34-230	1032
L182D01-34-24	1032
L182D01-34-2450	1032
L182D01-38-110	1032
L182D01-38-230	1032
L182D01-38-24	1032
L182D01-38-2450	1032
L182D48-112-110	1032
L182D48-112-230	1032
L182D48-112-24	1032
L182D48-112-2450	1032
L182D48-114-110	1032
L182D48-114-230	1032
L182D48-114-24	1032
L182D48-114-2450	1032
L182D48-2-110	1032
L182D48-2-230	1032
L182D48-2-24	1032
L182D48-2-2450	1032
L182V09-1-11050	1031
L182V09-12-11050	1031
L182V09-12-23050	1031
L182V09-12-24	1031
L182V09-12-2450	1031
L182V09-1-23050	1031
L182V09-1-24	1031
L182V09-1-2450	1031
L182V09-34-11050	1031
L182V09-34-23050	1031
L182V09-34-24	1031
L182V09-34-2450	1031
L182V09-38-11050	1031
L182V09-38-23050	1031
L182V09-38-24	1031
L182V09-38-2450	1031
L282D01-1-110	1032
L282D01-112-110	1032
L282D01-112-230	1032
L282D01-112-24	1032
L282D01-112-2450	1032
L282D01-12-110	1032
L282D01-12-230	1032
L282D01-12-24	1032
L282D01-12-2450	1032
L282D01-1-230	1032
L282D01-1-24	1032
L282D01-1-2450	1032
L282D01-2-110	1032
L282D01-2-230	1032
L282D01-2-24	1032
L282D01-2-2450	1032
L282D01-34-110	1032
L282D01-34-230	1032
L282D01-34-24	1032
L282D01-34-2450	1032
L282D01-38-110	1032
L282D01-38-230	1032
L282D01-38-24	1032
L282D01-38-2450	1032
L282D48-114-110	1032
L282D48-114-230	1032
L282D48-114-24	1032
L282D48-114-2450	1032
L282V09-1-11050	1031
L282V09-12-11050	1031
L282V09-12-23050	1031
L282V09-12-24	1031
L282V09-12-2450	1031
L282V09-1-23050	1031
L282V09-1-24	1031
L282V09-1-2450	1031
L282V09-34-11050	1031
L282V09-34-23050	1031
L282V09-34-24	1031
L282V09-34-2450	1031
L282V09-38-11050	1031
L282V09-38-23050	1031
L282V09-38-24	1031
L282V09-38-2450	1031
L321B02C-14-110	1033
L321B02C-14-230	1033
L321B02C-14-24	1033
L321B02C-14-2450	1033
L633.4/005X10	1433
L633.4/005X40	1433
L633.4/006X10	1433
L633.4/006X40	1433
L633.4/008X10	1433
L633.4/008X40	1433
L633.4/010X10	1433
L633.4/010X40	1433
L633.4/013X10	1433
L633.4/013X40	1433
L633.4/016X10	1433
L633.4/016X40	1433
L633.4/019X10	1433
L633.4/019X40	1433
L64M-2GP-EDN	684
L64M-3GP-EDN	684
L64M-4GP-EDN	684
L64M-6GP-EDN	684
L68M-NNP-ERN	684
L82M-2GP-EPN	686
L84M-3GP-EPN	686
L84M-4GP-EPN	686
LAC-1	273
LAC-3	273
LAC-6	273
LAC-7	273
LB 10	1476
LB-4	1476
LB-9	1476
LBS-120	905
LBS-25	905
LBS-63N	905
LBU 29	1476
LBU-9	1476
LCRB2	1507
LCRB33	1507
LCRB3312	1507
LCRB4	1507
LCRB5	1507
LCRB6	1507
LCRB8	1507
LD04-1	1595
LD10/10K	1169
LD10-1	1595
LD13/13K	1169
LD13-1	1595
LD17/17K	1169
LD20-1	1595
LD21/21K	1169
LD26/26K	1169
LD33/33K	1169
LD40-1	1595
LDC-1	273
LDC-2	273
LDC-3	273
LDC-4	273
LDC-5	273
LDC-6	273
LDF21/21K	1169
LDF26/26K	1169
LDF33/33K	1169
LDF42/42K	1169
LDF48/48K	1169
LDF52/52K	1169
LDP04/025	909
LDP05/030	909
LDP06/040	909
LDP08/060	909
LDP10/080	909
LDP12/100	909
LDSRAH06X0.6	1411
LDSRAH10X0.6	1411
LDSRAH10X0.6-19	1411
LDSRAH10X0.6-XF	1411
LDSRAH13X0.6	1411
LE-0138 08 00	851
LE-0138 10 00	851
LE-0138 12 00	851
LE-0432 10 17	934
LE-0432 13 21	934
LE-0432 20 27	934
LE-0432 23 34	934
LE-0437 10 17	934
LE-0437 13 21	934
LE-0437 18 27	934
LE-0437 23 34	934
LE-0438 12 21	934
LE-0439 07 13	934
LE-0439 10 17	934
LE-0439 13 21	934
LE-0439 18 27	934
LE-0439 23 34	934
LE-0446 04 10	933
LE-0446 07 13	933
LE-0446 10 17	933
LE-0446 13 21	933
LE-0448 06 13	934
LE-0448 09 17	934
LE-0448 12 21	934
LE-0449 07 13	933
LE-0449 10 17	933
LE-0449 13 21	933
LE-0452 04 10	934
LE-0452 06 13	934
LE-0469 04 10	933
LE-0469 07 13	933
LE-0469 10 17	933
LE-0469 13 21	933
LE-0469 18 27	933
LE-0469 23 34	933
LE-0482 06 13	934
LE-0482 09 17	934
LE-0482 12 21	934
LE-0482 23 34	934
LE-0483 04 10	934
LE-0483 06 13	934
LE-0483 09 17	934
LE-0483 12 21	934
LE-0489 07 13	933
LE-0489 10 17	933
LE-0489 13 21	933
LE-0489 18 27	933
LE-0489 23 34	933
LE-0631 00 23	1602
LE-0654 00 13	1602
LE-0677 00 10	631
LE-0677 00 13	631
LE-0677 00 17	631
LE-0677 00 21	631
LE-0677 00 34	631
LE-1010P04 00M04	917
LE-1010P04 00M07	917
LE-1010P06 00M04	917

Code	Page
LE-1010P06 00M07	917
LE-1010P08 00M02	917
LE-1015Y06F00	907
LE-1015Y06F01	907
LE-1015Y06F04	907
LE-1015Y08F00	907
LE-1015Y08F01	907
LE-1015Y08F04	907
LE-1015Y10F00	907
LE-1015Y10F01	907
LE-1015Y10F04	907
LE-1025P06V01	908
LE-1025P06V04	908
LE-1025P08V01	908
LE-1025P08V04	908
LE-1025P10V01	908
LE-1025P10V04	908
LE-1025P12V01	908
LE-1025U04R01	908
LE-1025U04R04	908
LE-1025U04R08	908
LE-1025U04R12	906
LE-1025U04R13	906
LE-1025U04R14	906
LE-1025U04R17	906
LE-1025U05R08	908
LE-1025U06R01	908
LE-1025U06R04	908
LE-1025U06R08	908
LE-1025U06R12	906
LE-1025U06R13	906
LE-1025U06R14	906
LE-1025U06R17	906
LE-1025U08R01	908
LE-1025U08R04	908
LE-1025U08R08	908
LE-1025U08R12	906
LE-1025U08R13	906
LE-1025U08R14	906
LE-1025U08R17	906
LE-1025U10R01	908
LE-1025U10R04	908
LE-1025U10R08	908
LE-1025U10R14	906
LE-1025U12R01	908
LE-1025U12R04	908
LE-1025U12R08	908
LE-1025U12R14	906
LE-1025U14R0495	908
LE-1025U14R0895	908
LE-1075Y12F00	907
LE-1075Y12F01	907
LE-1075Y12F04	907
LE-1096Y62F00	907
LE-1096Y62F01	907
LE-1096Y62F04	907
LE-1098Y56F00	907
LE-1098Y56F01	907
LE-1098Y56F03	907
LE-1098Y56F04	907
LE-1098Y60F00	907
LE-1098Y60F01	907
LE-1098Y60F04	907
LE-1100P04R00	906
LE-1100P04R01	906
LE-1100P04R04	906
LE-1100P06R00	906
LE-1100P06R01	906
LE-1100P06R04	906
LE-1100P06V01	908
LE-1100P08R00	906
LE-1100P08R01	906
LE-1100P08R04	906
LE-1100P08V01	908
LE-1100P08V04	908
LE-1100P10R00	906
LE-1100P10R01	906
LE-1100P10R04	906
LE-1100P12R00	906
LE-1100P12R01	906
LE-1100U03A01	908
LE-1100U04R12	906
LE-1100U04R13	906
LE-1100U04R14	906
LE-1100U04R17	906
LE-1100U06A01	908
LE-1100U06R12	906
LE-1100U06R13	906
LE-1100U06R14	906
LE-1100U06R17	906
LE-1100U08A01	908
LE-1100U08R12	906
LE-1100U08R13	906
LE-1100U08R14	906
LE-1100U08R17	906
LE-1100U10A01	908
LE-1100U10R14	906
LE-1100U12R14	906
LE-1420U04 11	908
LE-1420U04 41	908
LE-1420U04 44	908
LE-1420U06 11	908
LE-1420U06 41	908
LE-1420U06 44	908
LE-1420U08 41	908
LE-3091 04 10	799
LE-3091 06 10	799
LE-3091 08 13	799
LE-3101 03 09	793
LE-3101 03 19	793
LE-3101 04 09	793
LE-3101 04 13	793
LE-3101 04 19	793
LE-3101 04 55	793
LE-3101 06 10	793
LE-3101 06 13	793
LE-3101 06 17	793
LE-3101 06 19	793
LE-3101 06 21	793
LE-3101 06 55	793
LE-3101 08 10	793
LE-3101 08 13	793
LE-3101 08 17	793
LE-3101 10 13	793
LE-3101 10 17	793
LE-3101 10 21	793
LE-3101 12 13	793
LE-3101 12 17	793
LE-3101 12 21	793
LE-3101 14 21	793
LE-3101 16 17	793
LE-3101 16 21	793
LE-3102 04 00	797
LE-3102 04 06	797
LE-3102 06 00	797
LE-3102 06 08	797
LE-3102 08 00	797
LE-3102 08 10	797
LE-3102 10 00	797
LE-3102 10 12	797
LE-3102 12 00	797
LE-3102 14 00	797
LE-3102 16 00	797
LE-3103 04 13	796
LE-3103 06 10	796
LE-3103 08 10	796
LE-3103 08 13	796
LE-3103 10 13	796
LE-3103 10 21	796
LE-3103 12 13	796
LE-3103 12 17	796
LE-3104 03 00	797
LE-3104 04 00	797
LE-3104 04 06	797
LE-3104 06 00	797
LE-3104 06 04	797
LE-3104 06 08	797
LE-3104 08 00	797
LE-3104 08 06	797
LE-3104 08 10	797
LE-3104 10 00	797
LE-3104 10 08	797
LE-3104 10 12	797
LE-3104 12 00	797
LE-3104 12 10	797
LE-3104 14 00	797
LE-3104 16 00	797
LE-3104 16 12	797
LE-3106 03 00	797
LE-3106 03 04	797
LE-3106 04 00	797
LE-3106 04 06	797
LE-3106 04 08	797
LE-3106 06 00	797
LE-3106 06 08	797
LE-3106 06 10	797
LE-3106 08 00	797
LE-3106 08 10	797
LE-3106 10 00	797
LE-3106 10 12	797
LE-3106 12 00	797
LE-3106 12 14	797
LE-3106 12 16	797
LE-3106 14 00	797
LE-3106 16 00	797
LE-3107 06 00	798
LE-3108 04 10	796
LE-3108 04 13	796
LE-3108 06 10	796
LE-3108 06 13	796
LE-3108 08 10	796
LE-3108 08 13	796
LE-3108 10 13	796
LE-3108 10 17	796
LE-3108 10 21	796
LE-3108 12 13	796
LE-3108 12 17	796
LE-3108 12 21	796
LE-3108 14 21	796
LE-3108 16 17	796
LE-3108 16 21	796
LE-3109 04 10	795
LE-3109 04 13	795
LE-3109 06 10	795
LE-3109 06 13	795
LE-3109 06 17	795
LE-3109 06 21	795
LE-3109 08 10	795
LE-3109 08 13	795
LE-3109 08 17	795
LE-3109 08 21	795
LE-3109 10 13	795
LE-3109 10 17	795
LE-3109 10 21	795
LE-3109 12 13	795
LE-3109 12 17	795
LE-3109 12 21	795
LE-3109 14 17	795
LE-3109 14 21	795
LE-3109 16 17	795
LE-3109 16 21	795
LE-3110 04 04	799
LE-3110 06 03	799
LE-3110 06 04	799
LE-3110 12 04	799
LE-3110 14 00	799
LE-3110 14 02	799
LE-3110 14 03	799
LE-3110 14 04	799
LE-3110 14 05	799
LE-3112 06 13	796
LE-3113 04 10	795
LE-3113 06 10	795
LE-3113 06 13	795
LE-3113 08 13	795
LE-3113 08 17	795
LE-3113 10 13	795
LE-3113 10 17	795
LE-3113 12 17	795
LE-3114 04 10	793
LE-3114 04 13	793
LE-3114 04 19	793
LE-3114 06 10	793
LE-3114 06 13	793
LE-3114 08 10	793
LE-3114 08 13	793
LE-3114 08 17	793
LE-3114 10 13	793
LE-3114 10 17	793
LE-3114 10 21	793
LE-3114 12 17	793
LE-3114 12 21	793
LE-3116 04 00	797
LE-3116 06 00	797
LE-3116 08 00	797
LE-3116 10 00	797
LE-3116 12 00	797
LE-3116 14 00	797
LE-3119 04 19	796
LE-3119 08 13	796
LE-3120 04 00	798
LE-3120 06 00	798
LE-3120 08 00	798
LE-3120 10 00	798
LE-3121 04 13	796
LE-3121 06 13	796
LE-3121 10 17	796
LE-3122 04 53	798
LE-3122 06 05	798
LE-3122 08 56	798
LE-3122 10 08	798
LE-3122 12 10	798
LE-3122 12 62	798
LE-3126 04 00	798
LE-3126 06 00	798
LE-3126 08 00	798
LE-3126 10 00	798
LE-3126 12 00	798
LE-3126 14 00	798
LE-3126 16 00	798
LE-3129 04 13	795
LE-3129 06 10	795
LE-3129 06 13	795
LE-3129 08 10	795
LE-3129 08 13	795
LE-3129 08 17	795
LE-3129 10 17	795
LE-3129 12 13	795
LE-3129 12 17	795
LE-3129 12 21	795
LE-3129 14 21	795
LE-3131 08 13	796
LE-3131 12 21	796
LE-3131 14 17	796
LE-3132 06 13	796
LE-3133 04 19	795
LE-3133 06 10	795
LE-3133 06 19	795
LE-3136 04 10	797
LE-3136 06 10	797
LE-3136 06 13	797
LE-3136 08 10	797
LE-3136 08 13	797
LE-3136 10 17	797
LE-3136 12 17	797
LE-3139 04 00	797
LE-3139 06 00	797
LE-3139 08 00	797
LE-3139 10 00	797
LE-3139 12 00	797
LE-3140 04 00	797
LE-3140 04 06	797
LE-3140 06 00	797
LE-3140 06 08	797
LE-3140 08 00	797
LE-3140 08 10	797
LE-3140 10 00	797
LE-3140 10 12	797
LE-3140 12 00	797
LE-3142 04 06	798

Code	Page
LE-3142 06 08	798
LE-3142 08 10	798
LE-3143 04 06	798
LE-3144 04 04	797
LE-3144 04 06	797
LE-3144 06 06	797
LE-3144 06 08	797
LE-3146 04 00	797
LE-3146 06 00	797
LE-3149 04 10	796
LE-3149 06 10	796
LE-3149 06 13	796
LE-3149 08 13	796
LE-3149 08 17	796
LE-3159 04 10	799
LE-3159 06 10	799
LE-3159 06 13	799
LE-3159 08 10	799
LE-3159 08 13	799
LE-3166 03 04	799
LE-3166 04 06	799
LE-3166 04 08	799
LE-3166 04 10	799
LE-3166 06 08	799
LE-3166 06 10	799
LE-3166 06 12	799
LE-3166 06 14	799
LE-3166 08 10	799
LE-3166 08 12	799
LE-3166 08 14	799
LE-3166 10 12	799
LE-3166 10 14	799
LE-3166 12 14	799
LE-3168 06 04	798
LE-3168 08 06	798
LE-3168 10 08	798
LE-3168 12 10	798
LE-3169 04 13	795
LE-3169 04 19	795
LE-3169 06 10	795
LE-3169 06 13	795
LE-3169 06 19	795
LE-3175 04 10	793
LE-3175 04 13	793
LE-3175 06 10	793
LE-3175 06 13	793
LE-3175 06 17	793
LE-3175 06 21	793
LE-3175 08 10	793
LE-3175 08 13	793
LE-3175 08 17	793
LE-3175 08 21	793
LE-3175 10 13	793
LE-3175 10 17	793
LE-3175 10 21	793
LE-3175 12 13	793
LE-3175 12 17	793
LE-3175 12 21	793
LE-3175 14 17	793
LE-3175 14 21	793
LE-3175 16 17	793
LE-3175 16 21	793
LE-3180 04 00	798
LE-3180 08 00	798
LE-3182 04 00	798
LE-3182 04 06	798
LE-3182 06 00	798
LE-3182 06 04	798
LE-3182 06 08	798
LE-3182 08 00	798
LE-3182 08 10	798
LE-3182 10 00	798
LE-3182 10 12	798
LE-3182 12 00	798
LE-3183 06 00	798
LE-3183 08 00	798
LE-3184 08 10	798
LE-3184 12 00	798
LE-3188 06 00	798
LE-3188 08 00	798
LE-3189 04 19	799
LE-3189 06 10	799
LE-3189 06 13	799
LE-3189 06 19	799
LE-3189 08 10	799
LE-3189 08 17	799
LE-3189 10 13	799
LE-3189 10 17	799
LE-3192 04 10	795
LE-3192 04 13	795
LE-3192 06 10	795
LE-3192 06 13	795
LE-3192 08 10	795
LE-3192 08 13	795
LE-3192 08 17	795
LE-3192 10 13	795
LE-3192 10 17	795
LE-3192 12 13	795
LE-3192 12 17	795
LE-3192 12 21	795
LE-3193 04 10	796
LE-3193 04 19	796
LE-3193 06 10	796
LE-3193 06 19	796
LE-3193 08 10	796
LE-3193 08 17	796
LE-3193 10 13	796
LE-3193 12 17	796
LE-3193 14 21	796
LE-3199 03 19	795
LE-3199 04 09	795
LE-3199 04 10	795
LE-3199 04 13	795
LE-3199 04 19	795
LE-3199 04 55	795
LE-3199 06 10	795
LE-3199 06 13	795
LE-3199 06 17	795
LE-3199 06 19	795
LE-3199 06 21	795
LE-3199 06 55	795
LE-3199 08 10	795
LE-3199 08 13	795
LE-3199 08 17	795
LE-3199 08 21	795
LE-3199 10 13	795
LE-3199 10 17	795
LE-3199 10 21	795
LE-3199 12 13	795
LE-3199 12 21	795
LE-3199 14 17	795
LE-3199 14 21	795
LE-3199 16 17	795
LE-3199 16 21	795
LE-3306 06 04	798
LE-3306 08 04	798
LE-3306 08 06	798
LE-3306 10 06	798
LE-3306 10 08	798
LE-3310 04 13	798
LE-3310 06 13	798
LE-3310 08 17	798
LE-3320 04 00 04	799
LE-3320 04 00 07	799
LE-3320 04 00 12	799
LE-3320 06 00 04	799
LE-3320 06 00 07	799
LE-3321 04 00 04	799
LE-3321 04 00 07	799
LE-3321 04 00 12	799
LE-3321 06 00 04	799
LE-3321 06 00 07	799
LE-3329 00 02	799
LE-3379 08 00	799
LE-3391 10 17	799
LE-3524 00 10	796
LE-3524 00 13	796
LE-3527 00 10	796
LE-3527 00 13	796
LE-3527 00 17	796
LE-3528 00 13	796
LE-3529 00 10	796
LE-3529 00 13	796
LE-3538 06 10	796
LE-3538 06 13	796
LE-3538 08 13	796
LE-3601 04 10	848
LE-3601 04 13	848
LE-3601 04 52	848
LE-3601 04 56	848
LE-3601 06 10	848
LE-3601 06 13	848
LE-3601 06 19	848
LE-3601 06 60	848
LE-3601 08 10	848
LE-3601 08 13	848
LE-3601 08 17	848
LE-3601 10 13	848
LE-3601 10 17	848
LE-3601 10 21	848
LE-3601 12 13	848
LE-3601 12 17	848
LE-3601 12 21	848
LE-3601 14 17	848
LE-3601 14 21	848
LE-3602 04 00	850
LE-3602 06 00	850
LE-3602 08 00	850
LE-3602 10 00	850
LE-3602 12 00	850
LE-3602 14 00	850
LE-3603 06 10	849
LE-3603 06 13	849
LE-3603 08 13	849
LE-3603 10 13	849
LE-3604 04 00	850
LE-3604 06 00	850
LE-3604 08 00	850
LE-3604 10 00	850
LE-3604 12 00	850
LE-3604 14 00	850
LE-3606 04 00	849
LE-3606 06 00	849
LE-3606 08 00	849
LE-3606 10 00	849
LE-3606 12 00	849
LE-3606 14 00	849
LE-3608 06 10	849
LE-3608 06 13	849
LE-3608 08 13	849
LE-3608 10 13	849
LE-3608 12 17	849
LE-3608 14 21	849
LE-3609 04 10	848
LE-3609 04 13	848
LE-3609 06 10	848
LE-3609 06 13	848
LE-3609 08 10	848
LE-3609 08 13	848
LE-3609 08 17	848
LE-3609 10 13	848
LE-3609 10 17	848
LE-3609 12 13	848
LE-3609 12 17	848
LE-3609 12 21	848
LE-3609 14 21	848
LE-3614 04 10	849
LE-3614 04 13	849
LE-3614 06 10	849
LE-3614 06 13	849
LE-3614 08 10	849
LE-3614 08 13	849
LE-3614 10 17	849
LE-3614 12 17	849
LE-3614 12 21	849
LE-3616 04 00	850
LE-3616 06 00	850
LE-3616 08 00	850
LE-3616 10 00	850
LE-3616 12 00	850
LE-3616 14 00	850
LE-3618 04 10	849
LE-3618 04 19	849
LE-3618 06 10	849
LE-3618 06 13	849
LE-3618 06 19	849
LE-3618 08 10	849
LE-3618 08 13	849
LE-3618 10 17	849
LE-3620 04 00	850
LE-3620 06 00	850
LE-3620 08 00	850
LE-3620 10 00	850
LE-3620 12 00	850
LE-3621 04 10	848
LE-3621 06 10	848
LE-3621 06 13	848
LE-3621 08 10	848
LE-3621 08 13	848
LE-3621 10 13	848
LE-3621 10 17	848
LE-3621 12 17	848
LE-3621 12 21	848
LE-3622 04 05	850
LE-3622 04 53	850
LE-3622 06 05	850
LE-3622 08 08	850
LE-3622 08 56	850
LE-3622 10 08	850
LE-3622 10 56	850
LE-3622 12 08	850
LE-3622 12 10	850
LE-3622 12 62	850
LE-3626 04 00	850
LE-3626 06 00	850
LE-3626 08 00	850
LE-3626 10 00	850
LE-3626 12 00	850
LE-3629 04 10	849
LE-3629 06 10	849
LE-3629 06 13	849
LE-3629 08 10	849
LE-3629 08 13	849
LE-3631 04 10	848
LE-3631 04 19	848
LE-3631 06 10	848
LE-3631 06 13	848
LE-3631 08 13	848
LE-3631 10 13	848
LE-3631 10 17	848
LE-3631 10 21	848
LE-3631 12 17	848
LE-3631 12 21	848
LE-3631 14 21	848
LE-3636 06 10	850
LE-3636 06 13	850
LE-3636 08 10	850
LE-3636 08 13	850
LE-3636 10 17	850
LE-3636 12 21	850
LE-3639 04 00	850
LE-3639 06 00	850
LE-3639 08 00	850
LE-3639 10 00	850
LE-3639 12 00	850
LE-3666 04 06	850
LE-3666 04 08	850
LE-3666 06 08	850
LE-3666 06 10	850
LE-3666 08 10	850
LE-3666 08 12	850
LE-3666 10 12	850
LE-3666 12 14	850
LE-3667 06 56	850
LE-3668 06 04	850
LE-3669 04 10	848
LE-3669 04 19	848
LE-3669 06 10	848
LE-3669 06 13	848
LE-3669 08 10	848

Code	Page
LE-3669 08 13	848
LE-3669 10 13	848
LE-3669 10 17	848
LE-3669 12 17	848
LE-3669 14 21	848
LE-3675 04 10	848
LE-3675 04 13	848
LE-3675 06 10	848
LE-3675 06 13	848
LE-3675 08 10	848
LE-3675 08 13	848
LE-3675 08 17	848
LE-3675 10 13	848
LE-3675 10 17	848
LE-3675 10 21	848
LE-3675 12 13	848
LE-3675 12 17	848
LE-3675 12 21	848
LE-3675 14 17	848
LE-3675 14 21	848
LE-3681 04 19	848
LE-3693 06 10	849
LE-3693 08 13	849
LE-3698 04 10	849
LE-3698 06 13	849
LE-3698 08 13	849
LE-3698 14 21	849
LE-3699 04 13	849
LE-3699 04 19	849
LE-3699 04 52	849
LE-3699 04 56	849
LE-3699 06 10	849
LE-3699 06 13	849
LE-3699 06 60	849
LE-3699 08 10	849
LE-3699 08 13	849
LE-3699 08 17	849
LE-3699 10 13	849
LE-3699 10 17	849
LE-3699 12 13	849
LE-3699 12 17	849
LE-3699 12 21	849
LE-3699 14 17	849
LE-4020 56 00W	801
LE-4020 60 00W	801
LE-4021 56 14W	801
LE-4021 60 18W	801
LE-4022 56 14W	801
LE-4022 60 18W	801
LE-4890 10 10	628
LE-4890 13 13	628
LE-4890 17 17	628
LE-4890 21 21	628
LE-4890 27 27	628
LE-4890 34 34	628
LE-4891 10 10	628
LE-4891 13 13	628
LE-4891 17 17	628
LE-4891 21 21	628
LE-4891 27 27	628
LE-4891 34 34	628
LE-4892 10 10	628
LE-4892 13 13	628
LE-4892 17 17	628
LE-4892 21 21	628
LE-4892 27 27	628
LE-4892 34 34	628
LE-4895 11 11	628
LE-4895 14 14	628
LE-4895 18 18	628
LE-4895 22 22	628
LE-60007100	908
LE-6101 06 60	851
LE-6101 06 65	851
LE-6104 04 00	851
LE-6105 04 10	851
LE-6105 04 13	851
LE-6105 04 52	851
LE-6105 04 56	851
LE-6105 04 57	851
LE-6105 04 60	851
LE-6105 06 10	851
LE-6105 06 13	851
LE-6105 06 60	851
LE-6106 04 00	851
LE-6106 06 00	851
LE-6106 08 00	851
LE-6114 04 56	851
LE-6114 06 56	851
LE-6179 04 10	851
LE-6179 04 13	851
LE-6179 04 52	851
LE-6179 04 56	851
LE-6179 04 57	851
LE-6179 04 60	851
LE-6179 06 10	851
LE-6179 06 13	851
LE-6179 06 65	851
LE-6179 08 65	851
LE-6302 04 00W	803
LE-6302 06 00W	803
LE-6302 08 00W	803
LE-6302 10 00W	803
LE-6302 12 00W	803
LE-6302 56 00W	800
LE-6302 60 00W	800
LE-6302 62 00W	800
LE-6304 04 00W	802
LE-6304 06 00W	802
LE-6304 08 00W	802
LE-6304 10 00W	802
LE-6304 12 00W	802
LE-6304 56 00W	800
LE-6304 60 00W	800
LE-6304 62 00W	800
LE-6305 56 14W	800
LE-6306 04 00W	803
LE-6306 06 00W	803
LE-6306 08 00W	803
LE-6306 10 00W	803
LE-6306 12 00W	803
LE-6306 56 00W	800
LE-6306 56 60W	800
LE-6306 60 00W	800
LE-6306 60 62W	800
LE-6306 62 00W	800
LE-6315 06 10W	802
LE-6315 06 13W	802
LE-6315 08 13W	802
LE-6315 08 17W	802
LE-6315 56 14W	800
LE-6315 60 18W	800
LE-6316 04 00W	803
LE-6316 06 00W	803
LE-6316 08 00W	803
LE-6316 10 00W	803
LE-6316 12 00W	803
LE-6316 56 00W	800
LE-6316 60 00W	800
LE-6316 62 00W	800
LE-6322 56 56W	801
LE-6322 60 08W	801
LE-6322 60 56W	801
LE-6322 60 60W	801
LE-6322 62 60W	801
LE-6326 04 00W	803
LE-6326 06 00W	803
LE-6326 08 00W	803
LE-6326 10 00W	803
LE-6326 12 00W	803
LE-6326 56 00W	801
LE-6340 04 00W	803
LE-6340 06 00W	803
LE-6340 08 00W	803
LE-6340 10 00W	803
LE-6340 12 00W	803
LE-6340 56 00W	800
LE-6340 60 00W	800
LE-6340 62 00W	800
LE-6351 04 00W	803
LE-6351 06 00W	803
LE-6351 08 00W	803
LE-6351 10 00W	803
LE-6351 12 00W	803
LE-6351 56 00W	800
LE-6351 60 00W	800
LE-6366 04 06W	803
LE-6366 06 08W	803
LE-6366 08 10W	803
LE-6366 56 08W	801
LE-6366 56 60W	801
LE-6366 60 62W	801
LE-6382 04 00W	803
LE-6382 06 00W	803
LE-6382 08 00W	803
LE-6382 10 00W	803
LE-6382 12 00W	803
LE-6382 56 00W	801
LE-6382 60 00W	801
LE-6382 62 00W	801
LE-6388 04 00W	803
LE-6388 06 00W	803
LE-6388 08 00W	803
LE-6388 10 00W	803
LE-6388 56 00W	801
LE-6388 60 00W	801
LE-6402 04 10	933
LE-6402 07 13	933
LE-6402 10 17	933
LE-6402 13 21	933
LE-6402 20 27	933
LE-6402 23 34	933
LE-6503 06 13W	802
LE-6503 08 10W	802
LE-6503 08 13W	802
LE-6503 08 17W	802
LE-6503 12 17W	802
LE-6503 12 21W	802
LE-6505 04 10W	802
LE-6505 04 13W	802
LE-6505 06 10W	802
LE-6505 06 13W	802
LE-6505 08 10W	802
LE-6505 08 13W	802
LE-6505 08 17W	802
LE-6505 10 13W	802
LE-6505 10 17W	802
LE-6505 10 21W	802
LE-6505 12 17W	802
LE-6505 12 21W	802
LE-6508 06 10W	802
LE-6508 06 13W	802
LE-6508 06 17W	802
LE-6508 08 13W	802
LE-6508 08 17W	802
LE-6508 10 13W	802
LE-6508 10 17W	802
LE-6508 10 21W	802
LE-6508 12 17W	802
LE-6508 12 21W	802
LE-6509 06 10W	802
LE-6509 06 13W	802
LE-6509 06 17W	802
LE-6509 08 10W	802
LE-6509 08 13W	802
LE-6509 08 17W	802
LE-6509 10 13W	802
LE-6509 10 17W	802
LE-6509 10 21W	802
LE-6509 12 17W	802
LE-6509 12 21W	802
LE-6521 06 10W	802
LE-6521 06 13W	802
LE-6521 06 17W	802
LE-6521 08 10W	802
LE-6521 08 13W	802
LE-6521 08 17W	802
LE-6521 10 13W	802
LE-6521 10 17W	802
LE-6521 10 21W	802
LE-6521 12 17W	802
LE-6521 12 21W	802
LE-6579 06 10W	802
LE-6579 06 13W	802
LE-6579 06 17W	802
LE-7010 04 10	805
LE-7010 04 19	805
LE-7010 06 10	805
LE-7010 06 13	805
LE-7010 06 19	805
LE-7010 08 10	805
LE-7010 08 13	805
LE-7010 10 13	805
LE-7010 10 17	805
LE-7011 06 10	805
LE-7011 06 13	805
LE-7011 06 19	805
LE-7011 08 13	805
LE-7011 10 13	805
LE-7012 04 19	805
LE-7030 08 00	804
LE-7031 06 00	804
LE-7031 08 00	804
LE-7040 08 10	805
LE-7045 08 17	805
LE-7060 06 10	804
LE-7060 06 13	804
LE-7060 08 10	804
LE-7060 08 13	804
LE-7060 08 17	804
LE-7060 10 13	804
LE-7060 10 17	804
LE-7060 12 17	804
LE-7060 12 21	804
LE-7061 04 10	804
LE-7061 06 10	804
LE-7061 06 13	804
LE-7061 08 13	804
LE-7061 08 17	804
LE-7061 10 17	804
LE-7061 12 21	804
LE-7062 04 10	804
LE-7062 06 10	804
LE-7062 06 13	804
LE-7062 08 10	804
LE-7062 08 13	804
LE-7100 06 13	805
LE-7100 08 10	805
LE-7100 08 13	805
LE-7100 12 21	805
LE-7100 14 21	805
LE-7101 06 13	805
LE-7110 13 13	806
LE-7110 17 17	806
LE-7110 21 21	806
LE-7111 13 13	806
LE-7130 04 10	806
LE-7130 04 19	806
LE-7130 06 10	806
LE-7130 06 13	806
LE-7130 06 19	806
LE-7130 08 10	806
LE-7130 08 13	806
LE-7130 08 17	806
LE-7130 10 13	806
LE-7130 10 17	806
LE-7130 12 17	806
LE-7130 12 21	806
LE-7140 10 10	806
LE-7140 13 13	806
LE-7140 17 17	806
LE-7140 19 19	806
LE-7140 21 21	806
LE-7180 04 10	806
LE-7180 04 19	806
LE-7180 06 10	806
LE-7180 08 10	806
LE-7190 10 10	806
LE-7190 19 19	806
LE-7649 04 19	805

Code	Page
LE-7649 06 10	805
LE-7649 06 19	805
LE-7660 03 19	804
LE-7660 04 10	804
LE-7660 04 19	804
LE-7660 06 10	804
LE-7660 06 13	804
LE-7660 06 19	804
LE-7660 08 10	804
LE-7660 08 13	804
LE-7660 08 17	804
LE-7669 03 09	804
LE-7669 04 10	804
LE-7669 04 19	804
LE-7669 06 10	804
LE-7669 06 19	804
LE-7669 08 13	804
LE-7740 06 10	805
LE-7770 04 00	805
LE-7770 06 00	805
LE-7770 08 00	805
LE-7770 10 00	805
LE-7770 12 00	805
LE-7771 10 10	805
LE-7771 13 13	805
LE-7771 17 17	805
LE-7771 21 21	805
LE-7772 04 00	805
LE-7772 06 00	805
LE-7772 08 00	805
LE-7776 04 00	805
LE-7776 06 00	805
LE-7776 08 00	805
LE-7776 10 00	805
LE-7776 12 00	805
LE-7800 04 10	807
LE-7800 06 10	807
LE-7800 06 13	807
LE-7800 08 13	807
LE-7802 06 10	807
LE-7802 06 13	807
LE-7802 08 10	807
LE-7802 08 13	807
LE-7810 13 13	806
LE-7810 17 17	806
LE-7812 10 10	806
LE-7812 13 13	806
LE-7818 04 10	807
LE-7818 04 13	807
LE-7818 04 17	807
LE-7818 04 19	807
LE-7818 04 21	807
LE-7818 19 10	807
LE-7818 19 13	807
LE-7820 00 10	628
LE-7820 00 13	628
LE-7820 00 17	628
LE-7820 00 21	628
LE-7822 00 10	628
LE-7822 00 13	628
LE-7822 00 17	628
LE-7822 00 21	628
LE-7880 06 10	806
LE-7880 06 13	806
LE-7880 08 13	806
LE-7880 08 17	806
LE-7880 10 17	806
LE-7880 12 21	806
LE-7881 13 10	806
LE-7881 13 13	806
LE-7881 17 17	806
LE-7881 21 21	806
LE-7883 06 10	806
LE-7883 06 13	806
LE-7883 08 13	806
LE-7892 06 10	807
LE-7892 06 13	807
LE-7892 08 10	807
LE-7892 08 13	807
LE-7892 08 17	807
LE-7894 06 10	807
LE-7894 06 13	807
LE-7894 08 10	807
LE-7894 08 13	807
LE-7894 08 17	807
LE-7910 04 00	935
LE-7910 06 00	935
LE-7910 08 00	935
LE-7910 10 00	935
LE-7910 12 00	935
LE-7911 06 10	935
LE-7911 10 17	935
LE-7911 12 21	935
LE-7913 04 00	935
LE-7913 06 00	935
LE-7913 08 00	935
LE-7913 10 00	935
LE-7913 12 00	935
LE-7914 06 10	935
LE-7914 08 13	935
LE-7914 12 21	935
LE-7926 05 06	807
LE-7926 05 08	807
LE-7926 07 10	807
LE-7930 10 10	628
LE-7930 13 13	628
LE-7930 17 17	628
LE-7931 10 10	628
LE-7931 13 13	628
LE-7931 17 17	628
LE-7960 05 06	807
LE-7960 05 08	807
LE-7960 07 10	807
LE-7984 06 10	806
LE-7984 06 13	806
LE-7984 08 10	806
LE-7984 08 13	806
LE-7985 06 13	806
LE-7985 08 13	806
LE-7992 56 00W	801
LE-7992 60 00W	801
LE-7996 04 00	807
LE-7996 06 00	807
LE-7996 08 00	807
LE-7996 10 00	807
LE-7996 12 00	807
LE-9086 23 13	389
LE-9086 23 21	389
LE-9086 25 13	389
LE-9086 25 17	389
LE-9086 25 21	389
LE-9087E07 17	389
LE-9087E07 21	389
LE-9087U06 13	389
LE-9087U06 17	389
LE-9087U06 21	389
LE-9094E07 08	389
LE-9094E07 10	389
LE-9094E07 13	389
LE-9094U06 06	389
LE-9094U06 08	389
LE-9094U06 10	389
LE-9401E07 13	389
LE-9401E07 17	389
LE-9401E07 21	389
LE-9401U06 13	389
LE-9401U06 17	389
LE-9401U06 21	389
LE-9405U06 13	389
LE-9405U06 17	389
LE-9405U06 21	389
LE-9414E07 13	389
LE-9414E07 17	389
LE-9414E07 21	389
LE-9414U06 13	389
LE-9414U06 17	389
LE-9414U06 21	389
LE-9421E07 10	389
LE-9421E07 13	389
LE-9421U06 06	389
LE-9421U06 08	389
LE-9421U06 10	389
LE-CLIP 04 00	799
LE-CLIP 06 00	799
LE-CLIP 08 00	799
LE-CLIP 10 00	799
LE-CLIP 12 00	799
LE-CLIP 14 00	799
LEM7A	442
LEM7NC	442
LEMPVC19G	1590
LEMPVC19GY	1590
LEMPVC25B	1590
LEMPVC25BR	1590
LEMPVC25G	1590
LF1002	253
LF1009	253
LF1090	253
LF150-N-12F	736
LF150-S-12F	736
LF150-WS-12F	736
LF150-WS-12FDA	736
LF200-N-12F	736
LF200-S-12F	736
LF200-WS-12F	736
LF200-WS-12FDA	736
LF2020	253
LF2100	253
LF2220	253
LF250-N-12F	736
LF250-S-12F	736
LF250-WS-12F	736
LF250-WS-12FDA	736
LF3007E	253
LF300-N-12F	736
LF300-S-12F	736
LF300-WS-12F	736
LF300-WS-12FDA	736
LF3050E	253
LF3135E	253
LF3330E	253
LF3720E	253
LFC-1	1424
LFC-112	1424
LFC-114	1424
LFC-2	1424
LFC-212	1424
LFC-3	1424
LFC-4	1424
LFH1-10	1424
LFH1-100	1424
LFH112-10	1424
LFH112-100	1424
LFH114-10	1424
LFH114-100	1424
LFH2-10	1424
LFH2-100	1424
LFH212-10	1424
LFH212-100	1424
LFH3-10	1424
LFH3-100	1424
LFH4-10	1424
LFH4-100	1424
LFH6-10	1424
LFH6-100	1424
LFH8-10	1424
LFH8-100	1424
LGSLEEVE-18	46
LGSLEEVE-21	46
LGSLEEVE-25	46
LGSLEEVE-31	46
LGSLEEVE-36	46
LGSLEEVE-40	46
LGSLEEVE-45	46
LGSLEEVE-52	46
LGSLEEVE-60	46
LGSLEEVE-73	46
LGSLEEVE-85	46
LGSLEEVE-93	46
LH17/13K	334
LH17/17K	334
LH17/21K	334
LH19/13K	338
LH19/17K	338
LH19/21K	338
LH25/13K	355
LH25/17K	355
LHC-1	273
LHC-2	273
LHC-3	273
LHC-4	273
LHC-5	273
LHC-6	273
LL30B2	1508
LL30B3	1508
LL30B33	1508
LL30B4	1508
LL30B5	1508
LL30B6	1508
LL30B8	1508
LL45B10	1510
LL45B12	1510
LL45B2	1508
LL45B33	1508
LL45B3312	1508
LL45B4	1508
LL45B5	1508
LL45B6	1508
LL45B8	1508
LL45FF4	1508
LL45FF6	1508
LL45MF4	1508
LL45MF6	1508
LL90B10	1510
LL90B12	1510
LL90B2	1509
LL90B33	1509
LL90B3312	1509
LL90B4	1509
LL90B5	1509
LL90B6	1509
LL90B8	1509
LL90FF2TD	1509
LL90FF33	1509
LL90FF3312	1509
LL90FF4	1509
LL90FF4TD	1509
LL90FF6	1509
LL90FF8	1509
LL90MF33	1509
LL90MF3312	1509
LL90MF3312TD	1509
LL90MF4	1509
LL90MF4TD	1509
LL90MF6	1509
LL90MF6TD	1509
LL90MF8	1509
LLC2	1505
LLC2ORROR	1505
LLC33	1505
LLC3312	1505
LLC33ORROR	1505
LLC4	1505
LLC4ORROR	1505
LLC5	1505
LLC6	1505
LLC8	1505
LLC8ORROR	1505
LLCR2	1506
LLCR33	1506
LLCR3312	1506
LLCR4	1506
LLCR5	1506
LLCR6	1506
LLCR8	1506
LLF33123URTF	1506
LLF333URTF	1506
LLF44URTF	1506
LLF44URTM	1506
LLFBSP112	1506

Code	Page
LLFBSP2	1506
LLFBSP212	1506
LLFBSP33	1506
LLFBSP3312	1506
LLFBSP4	1506
LLFBSP5	1506
LLFBSP6	1506
LLFBSP8	1506
LLFEC2	1507
LLFEC33	1507
LLFEC3312	1507
LLFEC4	1507
LLFEC5	1507
LLFEC6	1507
LLFEC8	1507
LLFF10	1510
LLFF12	1510
LLFFD2	1507
LLFFD33	1507
LLFFD3312	1507
LLFFD4	1507
LLFFD6	1507
LLFFD8	1507
LLFFE162	1507
LLFFE1633	1507
LLFFE163312	1507
LLFFE164	1507
LLFFE1646	1507
LLFFE165	1507
LLFFE166	1507
LLFFE168	1507
LLFM233	1508
LLFM23312	1508
LLFM33122	1508
LLFM331233	1508
LLFM33124	1508
LLFM332	1508
LLFM333312	1508
LLFM334	1508
LLFM433	1508
LLFM43312	1508
LLFM45	1508
LLFM46	1508
LLFM54	1508
LLFM56	1508
LLFM64	1508
LLFM65	1508
LLFM68	1508
LLFM86	1508
LLFT10	1510
LLFT12	1510
LLFT2	1506
LLFT33	1506
LLFT3312	1506
LLFT4	1506
LLFT5	1506
LLFT6	1506
LLFT8	1506
LLFVSHT12	1509
LLFVSHT2	1509
LLFVSHT3	1509
LLFVSHT4	1509
LLFVSHT5	1509
LLFVSHT6	1509
LLFVSHT8	1509
LLFVSM2	1509
LLFVSM33	1509
LLFVSM3312	1509
LLFVSM4	1509
LLFVSM5	1509
LLFVSM6	1509
LLFVSM8	1509
LLFWE10	1510
LLFWE12	1510
LLFWE2	1507
LLFWE33	1507
LLFWE3312	1507
LLFWE4	1507
LLFWE5	1507
LLFWE6	1507
LLFWE8	1507
LLGP2	1509
LLGP3312	1509
LLGP4	1509
LLGP6	1509
LLGP8	1509
LLM44URTF	1506
LLM44URTM	1506
LLMBSP112	1506
LLMBSP2	1506
LLMBSP212	1506
LLMBSP33	1506
LLMBSP3312	1506
LLMBSP4	1506
LLMBSP5	1506
LLMBSP6	1506
LLMBSP8	1506
LLMEC10	1510
LLMEC12	1510
LLMEC2	1507
LLMEC33	1507
LLMEC3312	1507
LLMEC4	1507
LLMEC5	1507
LLMEC6	1507
LLMEC8	1507
LLMF10	1510
LLMF12	1510
LLMFD2	1507
LLMFD33	1507
LLMFD3312	1507
LLMFD4	1507
LLMFD46	1507
LLMFD5	1507
LLMFD6	1507
LLMFD8	1507
LLMFE162	1507
LLMFE1633	1507
LLMFE163312	1507
LLMFE164	1507
LLMFE1646	1507
LLMFE165	1507
LLMFE166	1507
LLMFE168	1507
LLMSSPIN133	1508
LLMSSPIN159194	1508
LLMSSPIN50	1508
LLMSSPIN76	1508
LLMSSPIN89108	1508
LLMT10	1510
LLMT12	1510
LLMT2	1506
LLMT33	1506
LLMT3312	1506
LLMT4	1506
LLMT5	1506
LLMT6	1506
LLMT8	1506
LLMWE12	1510
LLMWE2	1507
LLMWE33	1507
LLMWE3312	1507
LLMWE4	1507
LLMWE5	1507
LLMWE6	1507
LLMWE8	1507
LLOR2	1506
LLOR33	1506
LLOR3312	1506
LLOR4	1506
LLOR5	1506
LLOR6	1506
LLOR8	1506
LLOROR2	1506
LLOROR33	1506
LLOROR3312	1506
LLOROR4	1506
LLOROR5	1506
LLOROR6	1506
LLOROR8	1506
LLSS4	1509
LLSS6	1509
LLSSFBSP2	1505
LLSSFBSP33	1505
LLSSFBSP3312	1505
LLSSFBSP4	1505
LLSSFBSP5	1505
LLSSFBSP6	1505
LLSSFEC3312	1505
LLSSFEC4	1505
LLSSFEC6	1505
LLSSFT2	1505
LLSSFT3312	1505
LLSSFT4	1505
LLSSFT6	1505
LLSSFT8	1505
LLSSFWE2	1505
LLSSFWE33	1505
LLSSFWE3312	1505
LLSSFWE4	1505
LLSSFWE6	1505
LLSSMBSP2	1505
LLSSMBSP33	1505
LLSSMBSP3312	1505
LLSSMBSP4	1505
LLSSMEC2	1505
LLSSMEC33	1505
LLSSMEC3312	1505
LLSSMEC4	1505
LLSSMEC5	1505
LLSSMEC6	1505
LLSSMT2	1505
LLSSMT33	1505
LLSSMT3312	1505
LLSSMT4	1505
LLSSMT6	1505
LLSSMT8	1505
LLSSMWE2	1505
LLSSMWE3312	1505
LLSSMWE4	1505
LLSSMWE6	1505
LLTMFF2	1508
LLTMFF4	1508
LLTMFF6	1508
LLTMMF2	1508
LLTMMF33	1508
LLTMMF3312	1508
LLTMMF4	1508
LLTMMF5	1508
LLTMMF6	1508
LLTMMF8	1508
LLYFFM2	1507
LLYFFM33	1507
LLYFFM3312	1507
LLYFFM4	1507
LLYFFM6	1507
LLYMMF2	1507
LLYMMF33	1507
LLYMMF3312	1507
LLYMMF4	1507
LLYMMF6	1507
LLZD-LL90B2	1504
LLZD-LL90B33	1504
LLZD-LL90B3312	1504
LLZD-LL90B4	1504
LLZD-LL90B5	1504
LLZD-LL90B6	1504
LLZD-LL90B8	1504
LLZD-LLC4	1503
LLZD-LLCR2	1503
LLZD-LLCR33	1503
LLZD-LLCR3312	1503
LLZD-LLCR5	1503
LLZD-LLCR6	1503
LLZD-LLCR8	1503
LLZD-LLFBSP2	1503
LLZD-LLFBSP212	1503
LLZD-LLFBSP33	1503
LLZD-LLFBSP4	1503
LLZD-LLFBSP5	1503
LLZD-LLFBSP6	1503
LLZD-LLFBSP8	1503
LLZD-LLFEC2	1504
LLZD-LLFEC33	1504
LLZD-LLFEC3312	1504
LLZD-LLFEC4	1504
LLZD-LLFEC5	1504
LLZD-LLFEC6	1504
LLZD-LLFEC8	1504
LLZD-LLFWE2	1504
LLZD-LLFWE33	1504
LLZD-LLFWE3312	1504
LLZD-LLFWE4	1504
LLZD-LLFWE5	1504
LLZD-LLFWE6	1504
LLZD-LLFWE8	1504
LLZD-LLGP2	1504
LLZD-LLGP3312	1504
LLZD-LLGP4	1504
LLZD-LLGP5	1504
LLZD-LLGP6	1504
LLZD-LLGP8	1504
LLZD-LLMBSP2	1503
LLZD-LLMBSP212	1503
LLZD-LLMBSP33	1503
LLZD-LLMBSP4	1503
LLZD-LLMBSP5	1503
LLZD-LLMBSP6	1503
LLZD-LLMBSP8	1503
LLZD-LLMEC2	1504
LLZD-LLMEC33	1504
LLZD-LLMEC3312	1504
LLZD-LLMEC4	1504
LLZD-LLMEC5	1504
LLZD-LLMEC6	1504
LLZD-LLMEC8	1504
LLZD-LLMWE33	1503
LLZD-LLMWE3312	1503
LLZD-LLMWE4	1503
LLZD-LLMWE5	1503
LLZD-LLMWE6	1503
LLZD-LLMWE8	1503
LLZD-MZFF108	1503
LLZD-MZFF133	1503
LLZD-MZFF159	1503
LLZD-MZFF194	1503
LLZD-MZFF89	1503
LLZD-MZLLM108	1503
LLZD-MZLLM133	1503
LLZD-MZLLM159	1503
LLZD-MZLLM194	1503
LLZD-MZLLM89	1503
LLZDUTY-LLC2	1503
LLZDUTY-LLC3	1503
LLZDUTY-LLC3312	1503
LLZDUTY-LLC4	1503
LLZDUTY-LLC6	1503
LLZDUTY-LLC8	1503
LM010411	836
LM0104M5	836
LM0203E	836
LM0303E	836
LM0904M5	838
LM1FA100-T40	441
LM1FA100-T50	441
LM1FA100-T60	441
LM1FA100-T70	441
LM1FA100-T80	441
LM1FA150-T40	441
LM1FA150-T50	441
LM1FA150-T60	441
LM1FA150-T70	441
LM1FA150-T80	441
LM1FA200-T40	441
LM1FA200-T50	441
LM1FA200-T60	441
LM1FA200-T70	441
LM1FA200-T80	441
LM1FA250-T40	441
LM1FA250-T50	441

Code	Page
LM1FA250-T60	441
LM1FA250-T70	441
LM1FA250-T80	441
LM1FA300-T40	441
LM1FA300-T50	441
LM1FA300-T60	441
LM1FA300-T70	441
LM1FA300-T80	441
LM1FA350-T40	441
LM1FA350-T50	441
LM1FA350-T60	441
LM1FA350-T70	441
LM1FA350-T80	441
LM1FA400-T40	441
LM1FA400-T50	441
LM1FA400-T60	441
LM1FA400-T70	441
LM1FA400-T80	441
LM1FA450-T40	441
LM1FA450-T50	441
LM1FA450-T60	441
LM1FA450-T70	441
LM1FA450-T80	441
LM1FA500-T40	441
LM1FA500-T50	441
LM1FA500-T60	441
LM1FA500-T70	441
LM1FA500-T80	441
LM1TB-0500	441
LM1TB-1000	441
LM2FA100	441
LM2FA150	441
LM2FA200	441
LM2FA250	441
LM2FA300	441
LM2FA350	441
LM2FA400	441
LM2FA450	441
LM2FA500	441
LMBV-1	923
LMBV-112	923
LMBV-114	923
LMBV-12	923
LMBV-2	923
LMBV-34	923
LMC-1	1424
LMC-1000-1312SE	166
LMC-112	1424
LMC-114	1424
LMC-2	1424
LMC-212	1424
LMC-250-437SE	166
LMC-3	1424
LMC-312-500SE	166
LMC-375-562SE	166
LMC-4	1424
LMC-5	1424
LMC-500-750SE	166
LMC-625-875SE	166
LMC-750-1062SE	166
LMC-875-1187SE	166
LN02NP	1176
LN04NP	1176
LN06NP	1176
LN08NP	1176
LN-1	1184
LN-112	1184
LN-114	1184
LN12	1201
LN-12	1184
LN12NP	1176
LN-14	1184
LN16	1201
LN16NP	1176
LN-18	1184
LN-2	1184
LN-212	1184
LN-3	1184
LN-34	1184
LN-38	1184
LN-4	1184
LNM15NP	1176
LNM20NP	1176
LNM24NP	1176
LNM26NP	1176
LNM28NP	1176
LOC-1	273
LOC-1266117	1584
LOC-135278	1584
LOC-135279	1584
LOC-135280	1585
LOC-135428	1587
LOC-135483	1584
LOC-135522	1585
LOC-1379599	1587
LOC-142517	1587
LOC-1545634	1585
LOC-1546952	1586
LOC-1546964	1585
LOC-1684617	1586
LOC-1778011	1587
LOC-1808110	1586
LOC-195678	1587
LOC-195814	1569
LOC-2	273
LOC-2237457	1587
LOC-229342	1584
LOC-229360	1585
LOC-229873	1585
LOC-229875	1585
LOC-232515	1584
LOC-233695	1587
LOC-233733	1586
LOC-234228	1569
LOC-234258	1569
LOC-234458	1586
LOC-234573	1585
LOC-234795	1585
LOC-234853	1584
LOC-235330	1569
LOC-248	1584
LOC-260499	1585
LOC-265628	1586
LOC-267380	1584
LOC-267431	1584
LOC-267432	1584
LOC-267437	1585
LOC-267442	1585
LOC-267452	1569
LOC-268	1584
LOC-270153	1391
LOC-272597	1585
LOC-272602	1585
LOC-297328	1586
LOC-298392	1586
LOC-3	273
LOC-399422	1569
LOC-4	273
LOC-483283	1391
LOC-5	273
LOC-504219	1586
LOC-561	1584
LOC-6	273
LOC-760225	1569
LOC-8065	1584
LOC-871787	1587
LOK007-L	1763
LOK008-L	1763
LOK009-L	1763
LOK010-L	1763
LOK011-L	1763
LOK014	1762
LOK020-L	1762
LOK023	1763
LOK024	1763
LOK030	1762
LOK043	1762
LOK068	1763
LOK073	1763
LOK116	1762
LOK172	1762
LOK173	1762
LOK229	1762
LOK230	1762
LOL1	262
LPH-12.5	1556
LPH-13.5	1556
LPH-14.5	1556
LPH-16	1556
LPH-18	1556
LPH-19	1556
LPH-19.5	1556
LPH-22	1556
LPH-23	1556
LPH-28	1556
LPH-30	1556
LPH-33	1556
LPH-38	1556
LPH-41	1556
LR022MS	1518
LR022SS	1518
LR032MS	1518
LR032SS	1518
LR040MS	1518
LR040SS	1518
LR045SS	1518
LR050MS	1518
LR050SS	1518
LR060MS	1518
LR060SS	1518
LR070MS	1518
LR070SS	1518
LR080MS	1518
LR080SS	1518
LR090MS	1518
LR090SS	1518
LR100MS	1518
LR100SS	1518
LR110MS	1518
LR110SS	1518
LR120MS	1518
LR120SS	1518
LR130MS	1518
LR140MS	1518
LR140SS	1518
LR150MS	1518
LR150SS	1518
LR160MS	1518
LR160SS	1518
LU-1000	1645
LU-1010	1645
LU-1020	1645
LU-1030	1645
LU-1040	1645
LU-1050	1645
LU-1060	1645
LU-1070	1645
LU-1080	1645
LU-1090SS	1645
LU-1100SS	1645
LU-1120SS	1645
LU-1130	1645
LU-1140	1645
LU-1150	1645
LU-1160	1645
LU-1170	1645
LU-1180	1645
LU-1190	1645
LU-1200	1645
LU-1210	1645
LU-1220SS	1645
LU-1230SS	1645
LU-1240SS	1645
LU-1250SS	1645
LU-1260	1645
LU-1270	1645
LU-1290SS	1645
LU-1300	1645
LU-1310	1645
LU-1320	1645
LU-1330	1645
LU-1340SS	1645
LU-1360	1646
LU-1370	1646
LU-1380	1646
LU-1390	1646
LU-1400	1646
LU-1410	1646
LU-1420	1646
LU-1430	1646
LU-1440	1646
LU-1450	1646
LU-1460	1646
LU-1470	1646
LU-1480	1646
LU-1490	1646
LU-1500	1646
LU-1510	1646
LU-1520	1646
LU-1530	1646
LU-1540	1646
LU-1550	1646
LU-1560	1646
LU-1570	1646
LU-1580	1646
LU-1590	1646
LU-1600	1646
LU-1610	1646
LU-1620	1646
LU-1630	1646
LU-1640	1646
LU-1650	1646
LU-1670	1646
LU-1680	1646
LU-1690	1646
LU-1700	1646
LU-1710	1647
LU-1720	1647
LU-1730	1647
LU-1740	1647
LU-1750	1647
LU-1760SS	1647
LU-1780	1647
LU-1790	1647
LU-1800	1647
LU-1810	1647
LU-1820SS	1647
LU-1830SS	1647
LUE-GTI 20-50 SS	1484
LUE-GTI 30-75 SS	1484
LUE-KSA 36-39	1484
LUE-KSA 63-67	1484
LUE-SKD-SEAL	1483
LUE-USC-1	1483
M	
M/1511	635
M/1512	635
M/1514	635
M/1516	635
M/1518	635
M/1525/125	506
M/1525/200	506
M/1525/75	506
M/1540/125	506
M/1540/200	506
M/1540/75	506
M/1553/14	557
M/1553/8	557
M/48/MAZ13J	591
M/48/MAZ19J	591
M/49/MAZ13J	591
M/49/MAZ14J	591
M/49/MAZ18J	591
M/49/MAZ19J	591
M/50/LSU/10V	506
M/50/LSU/2V	506
M/50/LSU/5V	506
M/58301/01	749
M/58303/01	749
M/58304/01	749

Code	Page
M/58305/01	749
M/58306/01	749
M/58307/01	749
M/58403/01	749
M/58405/01	749
M/58408/01	749
M/58410/01	749
M/P1501/60	541
M/P1501/89	541
M/P1501/90	541
M/P19063	591
M/P35598/1	590
M/P35598/10	590
M/P35598/2	590
M/P35598/3	590
M/P35598/4	590
M/P35598/5	590
M/P35598/6	590
M/P35598/8	590
M/P35598/9	590
M/S1	635
M/S2	635
M/S3	635
M/S4	635
M-10L	117
M-10L-FT	159
M10S	117
M-10S-FT	159
M-10X2	111
M-10X2.5	111
M10X30	108
M10X35	108
M10X40	108
M10X45	108
M-11X2.5	111
M-12L	117
M-12L-FT	159
M12S	117
M-12S-FT	159
M-12X2.5	111
M12X35	108
M12X45	108
M12X50	108
M12X70	108
M14S	117
M-14S-FT	159
M-14X2.5	111
M14X45	108
M14X50	108
M-15L	117
M-15L-FT	159
M16S	117
M-16S-FT	159
M-16X2.5	111
M16X55	108
M-17X2.5	111
M-18L	117
M18L-1.4571AGP	164
M-18L-FT	159
M-19X2.5	111
M-19X3	111
M1NS2000	620
M1TS2VL1	1045
M1TS2VL2	1045
M1TS2VL3	1045
M20S	117
M20S-1.4571AGP	164
M-20S-FT	159
M20X110	108
M-20X3	111
M20X60	108
M20X65	108
M20X70	108
M2-14	1220
M-22L	117
M22L-1.4571AGP	164
M-22L-FT	159
M-22X3	111
M24SBLA4850	1391
M24SSIL4850	1391
M24SSIL7250	1391
M24SSIL9650	1391
M24SWHI4850	1391
M-24X3	111
M25S	117
M25S-1.4571AGP	164
M-25S-FT	159
M-25X3	111
M-27X3	111
M-28L	117
M28L-1.4571AGP	164
M-28L-FT	159
M-28X3	111
M293GAS5025	1391
M2NS2000	1046
M2TS2VL1	1046
M2TS2VL2	1046
M2TS2VL3	1046
M30S	117
M30S-1.4571AGP	164
M-30S-FT	159
M-30X3	111
M3122	757
M3123	757
M3124	757
M3132	757
M3133	757
M3134	757
M3-14	1220
M3-19	338
M3-25	354
M-32X3	111
M-33X3	111
M-35L	117
M35L-1.4571AGP	164
M-35L-FT	159
M-35X3	111
M-36X3	111
M38S	117
M38S-1.4571AGP	164
M-38S-FT	159
M-38X3	111
M-38X4	111
M3-TA	329
M-3X2	111
M-41X4	111
M-42L	117
M-42L-FT	159
M-44X4	111
M-4X2	111
M53004L-10A	565
M-5X2	111
M-6L	117
M-6L-FT	159
M6S	117
M-6S-FT	159
M-6X2	111
M700WHI1212	1391
M-7X2	111
M8090	1632
M837	635
M-8L	117
M-8L-FT	159
M8S	117
M-8S-FT	159
M-8X2	111
M8X25	108
M8X30	108
M9311	1720
M9312	1720
M9313	1720
M9320	1720
M9321	1720
M9322	1720
M9323	1720
M9336	1720
M9337	1720
M9338	1720
M9339	1720
M9340	1720
MA001B	635
MA002B	635
MA003B	635
MA004B	635
MA006B	635
MA010C	635
MA012C	635
MA016C	635
MA634V54PA05100	1043
MA634V54PA05300	1043
MA634V54PA05500	1043
MA634V55PA05100	1043
MA634V55PA05300	1043
MA634V55PA05500	1043
MA634V56PA05100	1043
MA634V56PA05300	1043
MA634V56PA05500	1043
MAG 10/25	1492
MAG 20/50	1492
MAL1/2-75-IMP	918
MAL1/4-25-IMP	918
MAL1/4-75-IMP	918
MAL10-25	918
MAL12-25	918
MAL3/8-75-IMP	918
MAL6-25	918
MAL8-25	918
MAN12	1496
MAN-145.2	1221
MAN-145.3	1221
MAN-145.4	1221
MAN-145.8	1221
MAN-151.02	1221
MAN-151.03	1221
MAN-151.04	1221
MAN-151.05	1221
MAN-151.06	1221
MAN-151.22	1221
MAN-151.33	1221
MAN-151.44	1221
MAN-151.55	1221
MAN-152.02	1221
MAN-152.03	1221
MAN-152.04	1221
MAN-152.05	1221
MAN-152.06	1221
MAN-152.22	1221
MAN-152.33	1221
MAN-152.44	1221
MAN-152.55	1221
MAN-153.03	1221
MAN-153.04	1221
MAN-153.05	1221
MAN-153.06	1221
MAN-153.33	1221
MAN-153.44	1221
MAN-153.55	1221
MAN-154.02	1221
MAN-154.03	1221
MAN-154.04	1221
MAN-154.05	1221
MAN-154.06	1221
MAN-154.22	1221
MAN-154.33	1221
MAN-154.44	1221
MAN-154.55	1221
MAN-155.02	1221
MAN-155.06	1221
MAN-155.22	1221
MAN-156.02	1221
MAN-156.03	1221
MAN-156.04	1221
MAN-156.05	1221
MAN-156.06	1221
MAN-156.44	1221
MAN-156.55	1221
MAN-157.02	1221
MAN-157.03	1221
MAN-157.04	1221
MAN-157.05	1221
MAN-157.22	1221
MAN-157.33	1221
MAN-157.44	1221
MAN-157.55	1221
MAN20	1496
MAN24	1496
MAN6	1496
MAS-G1/2-WD	270
MAS-G1/4-WD	270
MAS-G1/8-WD	270
MAS-G3/8-WD	270
MAV10LR	130
MAV10SR	130
MAV12LR	130
MAV12SR	130
MAV6LR	130
MAV6SR	130
MAV8LR	130
MAV8SR	130
MB001B	635
MB002B	635
MB003B	635
MB004B	635
MB006B	635
MB008B	635
MB02/04	1222
MB02/06	1222
MB02/08	1222
MB04/02	1222
MB04/04	1222
MB04/06	1222
MB04/08	1222
MB04/10	1222
MB06/04	1222
MB06/04/04	1222
MB06/04/06	1222
MB06/04/08	1222
MB06/06	1222
MB06/08	1222
MB08/04	1222
MB08/06	1222
MB08/08	1222
MB1	1167
MB112	1167
MB114	1167
MB12	1167
MB12/04	1222
MB12/06	1222
MB12/08/04	1222
MB14	1167
MB15-10BX	1420
MB15-13BX	1420
MB1601	1552
MB1603	1552
MB1705	1552
MB1708	1552
MB18	1167
MB1802	1552
MB1803	1552
MB1804	1552
MB1806	1552
MB2	1167
MB22-13BX	1420
MB22-19BX	1420
MB34	1167
MB38	1167
MB4	599
MB5	599
MB56	599
MB57	599
MB58	599
MB635V54PA05100	1043
MB635V54PA05300	1043
MB635V54PA05500	1043
MB635V55PA05100	1043
MB635V55PA05300	1043
MB635V55PA05500	1043
MB635V56PA05100	1043
MB635V56PA05300	1043
MB635V56PA05500	1043

Code	Page
MB9	599
MB-D200	654
MB-D400	654
MB-D600	654
MBM1	1167
MBM12	1167
MBM14	1167
MBM18	1167
MBM34	1167
MBM38	1167
MBT-10-250N	175
MBT-12-250N	175
MBT-12-375N	175
MBT-12-500N	175
MBT-125-125N	168
MBT-125-250N	168
MBT-16-500N	175
MBT-187-125N	168
MBT-250-125N	168
MBT-250-250N	168
MBT-312-125N	168
MBT-375-250N	168
MBT-375-375N	168
MBT-500-375N	168
MBT-500-500N	168
MBT-6-125N	175
MBT-6-250N	175
MBT-625-500N	168
MBT-750-750N	168
MBT-8-125N	175
MBT-8-250N	175
MBTP-1000-1000PR	168
MBTP-1000-1312SE	168
MBTP-10-250PR	175
MBTP-12-375PR	175
MBTP-12-500PR	175
MBTP-250-125PR	168
MBTP-250-250PR	168
MBTP-250-437SE	168
MBTP-375-250PR	168
MBTP-375-562SE	168
MBTP-500-375PR	168
MBTP-500-500PR	168
MBTP-500-750SE	168
MBTP-6-125PR	175
MBTP-6-250PR	175
MBTP-625-500PR	168
MBTP-750-1062SE	168
MBTP-750-500PR	168
MBTP-750-750PR	168
MBTP-8-125PR	175
MBTP-8-250PR	175
MBU-1	1113
MBU-112-ABS	1098
MBU-1-ABS	1098
MBV12	926
MBV12S	926
MBV14	926
MBV14S	926
MBV18	926
MBV18S	926
MBV34	926
MBV34S	926
MBV38	926
MBV38S	926
MBVM12	926
MBVM12S	926
MBVM14	926
MBVM14S	926
MBVM18	926
MBVM18S	926
MBVM34	926
MBVM34S	926
MBVM38	926
MBVM38S	926
MC1/2-10	1420
MC1/2-13	1420
MC1/2-16	1420
MC1/4-6	1420
MC1/4-8	1420
MC1/8-6	1420
MC-1000-1000N	166
MC-1000-1000RS	167
MC-1000-1000RT	166
MC-1000-1062SE	166
MC-1000-1312SE	166
MC-1000-500N	166
MC-1000-500RS	167
MC-1000-750N	166
MC101	201
MC10-12	141
MC-10-125N	173
MC-10-125RT	173
MC1016	201
MC102	201
MC-10-250N	173
MC-10-250RS	173
MC-10-250RT	173
MC-10-375N	173
MC-10-375RS	173
MC-10-375RT	173
MC-10-500N	173
MC-10-500RS	173
MC-10-500RT	173
MC-10-750N	173
MC10-8	141
MC10-8T	142
MC10A1-20	758
MC10A1-40	758
MC10A2-20	758
MC10A2-40	758
MC10B1-20	758
MC10B1-40	758
MC10B2-20	758
MC10B2-40	758
MC10C1-20	759
MC10C1-40	759
MC10C2-20	759
MC10C2-40	759
MC10D1-20	759
MC10D1-40	759
MC10D2-20	759
MC10D2-40	759
MC11/4-32	1420
MC12-12	141
MC-12-125N	173
MC-12-125RT	173
MC12-12T	142
MC-12-250N	173
MC-12-250RS	173
MC-12-250RT	173
MC-12-375N	173
MC-12-375RS	173
MC-12-375RT	173
MC1-25	1145
MC-12-500N	173
MC-12-500RS	173
MC-12-500RT	173
MC-125-125N	166
MC-125-125RS	167
MC-125-125RT	166
MC-125-250N	166
MC-125-250RS	167
MC-125-250RT	166
MC-125-312SE	166
MC-125-375N	166
MC-125-375RS	167
MC-125-500N	166
MC-125-562SE	166
MC-12-750N	173
MC-12-750RS	173
MC-12-750RT	173
MC12-8	141
MC12-8T	142
MC14-12	141
MC-14-250N	173
MC-14-375N	173
MC-14-500N	173
MC-15-500N	173
MC-15-500RT	173
MC161	201
MC1612	201
MC16-12	141
MC16-12T	142
MC16-16	141
MC16-16T	142
MC162	201
MC16-20	141
MC-16-250RT	173
MC-16-375N	173
MC-16-375RS	173
MC-16-375RT	173
MC-16-500N	173
MC-16-500RS	173
MC-16-500RT	173
MC-16-750N	173
MC-16-750RT	173
MC-18-500N	173
MC-18-500RS	173
MC-18-500RT	173
MC-187-125N	166
MC-187-250N	166
MC-18-750N	173
MC-18-750RS	173
MC-18-750RT	173
MC20-16	141
MC20-16T	142
MC20-20	141
MC20-24	141
MC-20-500N	173
MC-20-500RS	173
MC-20-500RT	173
MC-20-750N	173
MC-20-750RS	173
MC-20-750RT	173
MC20A1-40	758
MC20A1-60	758
MC20A2-40	758
MC20A2-60	758
MC20B1-40	758
MC20B1-60	758
MC20B2-40	758
MC20B2-60	758
MC20C1-40	759
MC20C1-60	759
MC20C2-40	759
MC20C2-60	759
MC20D1-40	759
MC20D1-60	759
MC20D2-40	759
MC20D2-60	759
MC-22-1000N	173
MC-22-1000RS	173
MC-22-1000RT	173
MC-22-750N	173
MC-22-750RS	173
MC-22-750RT	173
MC23A1-40	758
MC23A1-60	758
MC23A2-40	758
MC23A2-60	758
MC23B1-40	758
MC23B1-60	758
MC23B2-40	758
MC23B2-60	758
MC23C1-40	759
MC23C1-60	759
MC23C2-40	759
MC23C2-60	759
MC23D1-40	759
MC23D1-60	759
MC23D2-40	759
MC23D2-60	759
MC24-20	141
MC24-24	141
MC24-24T	142
MC-250-125N	166
MC-250-125RS	167
MC-250-125RT	166
MC-250-250N	166
MC-250-250RS	167
MC-250-250RT	166
MC-250-375N	166
MC-250-375RS	167
MC-250-375RT	166
MC-250-437SE	166
MC-250-500N	166
MC-250-500RS	167
MC-250-500RT	166
MC-250-750N	166
MC-250-750SE	166
MC-250-875SE	166
MC-25-1000N	173
MC-25-1000RS	173
MC-25-1000RT	173
MC-25-500N	173
MC-25-750N	173
MC-25-750RS	173
MC-25-750RT	173
MC25A1-40	758
MC25A1-60	758
MC25A2-40	758
MC25A2-60	758
MC25B1-40	758
MC25B1-60	758
MC25B2-40	758
MC25B2-60	758
MC25C1-40	759
MC25C1-60	759
MC25C2-40	759
MC25C2-60	759
MC3/4-13	1420
MC3/4-19	1145
MC3/8-10	1420
MC3/8-13	1420
MC3/8-8	1420
MC-312-125N	166
MC-312-125RT	166
MC-312-250N	166
MC-312-250RT	166
MC-312-375N	166
MC-312-500N	166
MC-312-500SE	166
MC-3-125N	173
MC-3-125RS	173
MC-3-125RT	173
MC321	201
MC3216	201
MC322	201
MC-3-250N	173
MC-3-250RS	173
MC-3-250RT	173
MC-375-125N	166
MC-375-125RT	166
MC-375-250N	166
MC-375-250RS	167
MC-375-250RT	166
MC-375-375N	166
MC-375-375RS	167
MC-375-375RT	166
MC-375-437SE	166
MC-375-500N	166
MC-375-500RS	167
MC-375-500RT	166
MC-375-562SE	166
MC-375-750N	166
MC-375-750SE	166
MC-375-875SE	166
MC-4-125N	173
MC-4-125RS	173
MC-4-125RT	173
MC4-2	141
MC-4-250N	173
MC-4-250RT	173
MC4-4	141
MC4-4T	142
MC4-6	141
MC-500-1000N	166
MC-500-1062SE	166
MC-500-125N	166

Code	Page
MC-500-250N	166
MC-500-250RS	167
MC-500-250RT	166
MC-500-375N	166
MC-500-375RS	167
MC-500-375RT	166
MC-500-500N	166
MC-500-500RS	167
MC-500-500RT	166
MC-500-562SE	166
MC-500-750N	166
MC-500-750RT	166
MC-500-750SE	166
MC-500-875SE	166
MC-6-125N	173
MC-6-125RS	173
MC-6-125RT	173
MC-6-250N	173
MC-6-250RS	173
MC-6-250RT	173
MC-625-375N	166
MC-625-500N	166
MC-625-750N	166
MC-625-750SE	166
MC-625-875SE	166
MC-6-375N	173
MC-6-375RS	173
MC-6-375RT	173
MC6-4	141
MC6-4T	142
MC-6-500N	173
MC-6-500RS	173
MC-6-500RT	173
MC6-6	141
MC6-6T	142
MC6-8	141
MC-750-1000N	166
MC-750-1062SE	166
MC-750-500N	166
MC-750-500RS	167
MC-750-750N	166
MC-750-750RS	167
MC-750-750RT	166
MC-750-750SE	166
MC8-12	141
MC-8-125N	173
MC-8-125RS	173
MC-8-125RT	173
MC-8-250N	173
MC-8-250RS	173
MC-8-250RT	173
MC-8-375N	173
MC-8-375RS	173
MC-8-375RT	173
MC8-4	141
MC8-4T	142
MC-8-500N	173
MC-8-500RS	173
MC-8-500RT	173
MC8-6	141
MC8-6T	142
MC-875-1000N	166
MC-875-1187SE	166
MC-875-750N	166
MC8-8	141
MC8-8T	142
MCG1010	201
MCG1012	201
MCG105	201
MCG106	201
MCG108	201
MCG1610	201
MCG1612	201
MCG1614	201
MCG1616	201
MCG1618	201
MCG164	201
MCG166	201
MCG168	201
MCG3210	201
MCG3212	201
MCG3214	201
MCG3218	201
MCG3220	201
MCG3224	201
MCG3226	201
MCG3232	201
MCG326	201
MCG328	201
MCGL100	1641
MCGL220	1641
MCH1	701
MCN10	201
MCN16	201
MCN32	201
MCS10	201
MCS32	201
MCSB10	201
MCSB32	201
MCT-10	1213
MCT-10/30	1213
MCT-12	1213
MCT-12/30	1213
MCT-15/30	1213
MCT-4	1213
MCT-4/30	1213
MCT-5	1213
MCT-6	1213
MCT-6/30	1213
MCT-6-4/30	1213
MCT-8	1213
MCT-8/30	1213
MCWP10	201
MCWP32	201
MCZAB1	1531
MD1-000014-1/4	696
MD1-000014-1/8	696
MD1-000014-10	696
MD1-000014-3/8	696
MD1-000014-6	696
MD1-000014-8	696
MD1-000015-1/4	696
MD1-000015-1/8	696
MD1-000015-10	696
MD1-000015-3/8	696
MD1-000015-6	696
MD1-000015-8	696
MD1-000016-1/4	696
MD1-000016-1/8	696
MD1-000016-10	696
MD1-000016-3/8	696
MD1-000016-6	696
MD1-000016-8	696
MD1-A-1/4	698
MD1-A-1/8	698
MD1-A-10	698
MD1-A-3/8	698
MD1-A-6	698
MD1-A-8	698
MD1-AV	698
MD1-B	698
MD1-B00	698
MD1-C	698
MD1-F000	697
MD1-F001	697
MD1-F050	697
MD1-F051	697
MD1-F100	697
MD1-F101	697
MD1-F150	697
MD1-F151	697
MD1-FC000	697
MD1-FC001	697
MD1-FC050	697
MD1-FC051	697
MD1-FC100	697
MD1-FC101	697
MD1-FC150	697
MD1-FC151	697
MD1-FCA0	697
MD1-FCA1	697
MD1-FR0000	697
MD1-FR0500	697
MD1-FR0800	697
MD1-L00	698
MD1-R000	697
MD1-R010	697
MD1-R200	697
MD1-R210	697
MD1-R400	697
MD1-R410	697
MD1-R700	697
MD1-R710	697
MD1-ST/1	698
MD1-V01	698
MD1-V36	698
MD-2	1220
MD-3	1220
MD-4	1220
MD-5	1220
MDB500-BLUE	1749
MDB500-RED	1749
MDC03	284
MDPT40.2R.A	706
MDS1-10	1427
MDS112-10	1427
MDS112-30	1427
MDS114-10	1427
MDS114-30	1427
MDS1-30	1427
MDS2-10	1427
MDS212-10	1427
MDS212-30	1427
MDS2-30	1427
MDS3-10	1427
MDS312-10	1427
MDS312-30	1427
MDS3-30	1427
MDS34-30	1427
MDS4-10	1427
MDS4-30	1427
MDS6-10	1427
MDS6-30	1427
MDS6-6	1427
ME-1000-1000N	169
ME-1000-750N	169
ME-10-250N	176
ME-10-250RT	176
ME-10-375N	176
ME-10-375RT	176
ME-10-500N	176
ME-10-500RT	176
ME10-8	142
ME12-12	142
ME-12-250N	176
ME-12-250RT	176
ME-12-375N	176
ME-12-375RT	176
ME-12-500N	176
ME-12-500RT	176
ME-125-125N	169
ME-125-250N	169
ME-12-750N	176
ME-12-750RT	176
ME12-8	142
ME12-8T	142
ME-15-500N	176
ME16-12T	142
ME16-16T	142
ME-16-375N	176
ME-16-375RT	176
ME-16-500N	176
ME-16-500RT	176
ME-16-750N	176
ME-18-500N	176
ME-18-500RT	176
ME-187-125N	169
ME-187-250N	169
ME-18-750N	176
ME-18-750RT	176
ME-20-500N	176
ME-20-500RT	176
ME-20-750RT	176
ME-22-1000N	176
ME-22-1000RT	176
ME-22-750N	176
ME-22-750RT	176
ME-250-125N	169
ME-250-125RT	169
ME-250-250N	169
ME-250-250RT	169
ME-250-375N	169
ME-250-375RT	169
ME-250-500N	169
ME-250-500RT	169
ME-25-1000N	176
ME-25-1000RT	176
ME-25-750N	176
ME-25-750RT	176
ME-312-125N	169
ME-312-250N	169
ME-312-250RT	169
ME-312-375N	169
ME-3-125RT	176
ME-3-250N	176
ME-3-250RT	176
ME-375-125N	169
ME-375-250N	169
ME-375-250RT	169
ME-375-375N	169
ME-375-375RT	169
ME-375-500N	169
ME-375-750N	169
ME-4-125N	176
ME-4-125RT	176
ME4-2	142
ME-4-250N	176
ME-4-250RT	176
ME4-2T	142
ME4-4	142
ME4-4T	142
ME-500-250N	169
ME-500-375N	169
ME-500-500N	169
ME-500-750N	169
ME-6-125N	176
ME-6-125RT	176
ME-6-250N	176
ME-6-250RT	176
ME-625-375N	169
ME-625-500N	169
ME-625-750N	169
ME-6-375N	176
ME-6-375RT	176
ME6-4T	142
ME-6-500N	176
ME-6-500RT	176
ME6-6T	142
ME-750-500N	169
ME-750-750N	169
ME-8-125N	176
ME-8-125RT	176
ME-8-250N	176
ME-8-250RT	176
ME-8-375N	176
ME-8-375RT	176
ME-8-500N	176
ME-8-500RT	176
ME8-6	142
ME8-6T	142
ME-875-750N	169
ME8-8	142
M-EF45E-22	1219
M-EF45E-42	1219
M-EF90E-10	1219
M-EF90E-15	1219
M-EF90E-22	1219
M-EFCOP-15	1219
M-EFET-10	1219
M-EFET-15	1219

Code	Page
M-EFET-35	1219
M-EFET-42	1219
M-EFET-54	1219
M-EFET-8	1219
M-EFRBT-22-15	1219
M-EFRBT-28-22	1219
M-EFRBT-35-15	1219
M-EFRBT-35-22	1219
M-EFRBT-35-28	1219
M-EFRBT-42-15	1219
M-EFRBT-42-22	1219
M-EFRBT-42-28	1219
M-EFRBT-42-35	1219
M-EFRBT-54-28	1219
M-EFRBT-54-35	1219
M-EFRBT-54-42	1219
M-EFSC-28	1219
M-EFSC-35	1219
M-EFSC-42	1219
M-EFSC-54	1219
M-EFTC-22	1219
M-EFTC-28	1219
M-EFTC-8	1219
M-EFTCB-15-12	1219
M-EFTCB-15-34	1219
M-EFTCB-22-34	1219
M-EFTCS-15-12	1219
M-EFTCS-22-34	1219
MEK-TIN	1100
MEP-1000-1000PR	169
MEP-1000-1312SE	169
MEP-1000-750PR	169
MEP-10-250PR	176
MEP-10-375PR	176
MEP-12-250PR	176
MEP-12-375PR	176
MEP-12-500PR	176
MEP-12-750PR	176
MEP-250-125PR	169
MEP-250-250PR	169
MEP-250-437SE	169
MEP-250-562SE	169
MEP-312-500SE	169
MEP-375-250PR	169
MEP-375-375PR	169
MEP-375-562SE	169
MEP-375-750SE	169
MEP-500-250PR	169
MEP-500-375PR	169
MEP-500-500PR	169
MEP-500-750SE	169
MEP-6-125PR	176
MEP-6-250PR	176
MEP-625-500PR	169
MEP-625-875SE	169
MEP-750-1062SE	169
MEP-750-500PR	169
MEP-750-750PR	169
MEP-8-125PR	176
MEP-8-250PR	176
MEP-875-1187SE	169
MF4	599
MF5	599
MF56	599
MF57	599
MF58	599
MFA1-112-ABS	1098
MFA1-1-ABS	1098
MFA1-2-ABS	1098
MFA1-34-ABS	1098
MFA2-12-ABS	1098
MFA2-1-ABS	1098
MFA2-2-ABS	1098
MFA2-34-ABS	1098
MFA2-3-ABS	1098
MFCB-02	1719
MFCB-04	1719
MFCB-06	1719
MFCB-08	1719
MFCN-02	1719
MFCN-04	1719
MFCN-06	1719
MFCN-08	1719
MFL02	1168
MFL04	1168
MFL06	1168
MFL08	1168
MFL12	1168
MFL16	1168
MFL20	1168
MFL24	1168
MFL32	1168
MFS10-N1-2	442
MFS17-C-2	442
MFTA-50-112-UPVC	1107
MFU-1	1184
MFU-112	1184
MFU-114	1184
MFU-12	1184
MFU-14	1184
MFU-2	1184
MFU-34	1184
MFU-38	1184
MFU-4	1184
MH04/04S	1146
MHA-34-ABS	1098
MHM10/04	1142
MHM10/05	1142
MHM10/06	1142
MHM12/04	1142
MHM12/05	1142
MHM12/06	1142
MHM14/06	1142
MHM16/06	1142
MHM16/08	1142
MHM18/06	1142
MHM18/08	1142
MHM22/08	1142
MHM22/12	1142
MHM5/03	1142
MHM5/04	1142
MHM6/04	1142
MHM8/04	1142
MIB-112X100	1378
MIB-112X100N	1379
MIB-112X120	1378
MIB-112X120N	1379
MIB-112X150	1378
MIB-112X150N	1379
MIB-112X180	1378
MIB-112X180N	1379
MIB-112X200	1378
MIB-112X200N	1379
MIB-112X250	1378
MIB-112X250N	1379
MIB-112X300	1378
MIB-112X300N	1379
MIB-112X60N	1379
MIB-112X80	1378
MIB-112X80N	1379
MIB-114X100	1378
MIB-114X100N	1379
MIB-114X120	1378
MIB-114X120N	1379
MIB-114X125	1378
MIB-114X150	1378
MIB-114X150N	1379
MIB-114X180	1378
MIB-114X180N	1379
MIB-114X200	1378
MIB-114X200N	1379
MIB-114X250	1378
MIB-114X250N	1379
MIB-114X300	1378
MIB-114X300N	1379
MIB-114X60N	1379
MIB-114X80	1378
MIB-114X80N	1379
MIB-12X100	1378
MIB-12X100N	1379
MIB-12X120	1378
MIB-12X120N	1379
MIB-12X150	1378
MIB-12X150N	1379
MIB-12X180	1378
MIB-12X180N	1379
MIB-12X200	1378
MIB-12X200N	1379
MIB-12X250	1378
MIB-12X250N	1379
MIB-12X30	1378
MIB-12X300	1378
MIB-12X300N	1379
MIB-12X30N	1379
MIB-12X40	1378
MIB-12X40N	1379
MIB-12X50	1378
MIB-12X60	1378
MIB-12X60N	1379
MIB-12X80	1378
MIB-12X80N	1379
MIB-14X100	1378
MIB-14X100N	1379
MIB-14X120	1378
MIB-14X120N	1379
MIB-14X150	1378
MIB-14X150N	1379
MIB-14X180	1378
MIB-14X180N	1379
MIB-14X200	1378
MIB-14X200N	1379
MIB-14X250	1378
MIB-14X250N	1379
MIB-14X300	1378
MIB-14X300N	1379
MIB-14X40	1378
MIB-14X40N	1379
MIB-14X60	1378
MIB-14X60N	1379
MIB-14X80	1378
MIB-14X80N	1379
MIB-18X60	1378
MIB-18X80	1378
MIB-1X100	1378
MIB-1X100N	1379
MIB-1X120	1378
MIB-1X120N	1379
MIB-1X150	1378
MIB-1X150N	1379
MIB-1X180	1378
MIB-1X180N	1379
MIB-1X200	1378
MIB-1X200N	1379
MIB-1X250	1378
MIB-1X250N	1379
MIB-1X30	1378
MIB-1X300	1378
MIB-1X300N	1379
MIB-1X40	1378
MIB-1X40N	1379
MIB-1X50	1378
MIB-1X60	1378
MIB-1X60N	1379
MIB-1X70	1378
MIB-1X80	1378
MIB-1X80N	1379
MIB-212X100N	1379
MIB-212X120N	1379
MIB-212X150N	1379
MIB-212X180N	1379
MIB-212X200N	1379
MIB-212X250N	1379
MIB-212X300N	1379
MIB-2X100	1378
MIB-2X100N	1379
MIB-2X120	1378
MIB-2X120N	1379
MIB-2X150	1378
MIB-2X150N	1379
MIB-2X180	1378
MIB-2X180N	1379
MIB-2X200	1378
MIB-2X200N	1379
MIB-2X250	1378
MIB-2X250N	1379
MIB-2X300	1378
MIB-2X300N	1379
MIB-2X80	1378
MIB-2X80N	1379
MIB-34X100	1378
MIB-34X1000	1378
MIB-34X100N	1379
MIB-34X120	1378
MIB-34X120N	1379
MIB-34X150	1378
MIB-34X1500	1378
MIB-34X150N	1379
MIB-34X180	1378
MIB-34X180N	1379
MIB-34X200	1378
MIB-34X200N	1379
MIB-34X250	1378
MIB-34X250N	1379
MIB-34X30	1378
MIB-34X300	1378
MIB-34X300N	1379
MIB-34X40	1378
MIB-34X40N	1379
MIB-34X60	1378
MIB-34X60N	1379
MIB-34X70	1378
MIB-34X80	1378
MIB-34X80N	1379
MIB-38X100	1378
MIB-38X100N	1379
MIB-38X120	1378
MIB-38X120N	1379
MIB-38X150	1378
MIB-38X150N	1379
MIB-38X180	1378
MIB-38X180N	1379
MIB-38X200	1378
MIB-38X200N	1379
MIB-38X250	1378
MIB-38X250N	1379
MIB-38X300	1378
MIB-38X300N	1379
MIB-38X30N	1379
MIB-38X40	1378
MIB-38X40N	1379
MIB-38X50	1378
MIB-38X60	1378
MIB-38X60N	1379
MIB-38X80	1378
MIB-38X80N	1379
MIB-3X100N	1379
MIB-3X120N	1379
MIB-3X150N	1379
MIB-3X180N	1379
MIB-3X200N	1379
MIB-3X250N	1379
MIB-3X300N	1379
MIB-4X100N	1379
MIB-4X120N	1379
MIB-4X150N	1379
MIB-4X180N	1379
MIB-4X200N	1379
MIB-4X250N	1379
MIB-4X300N	1379
MIBOSSW400	1391
MIBPB4-M5	1155
MIBPM10	1385
MIBPM10N	1385
MIBPM12	1385
MIBPM12N	1385
MICT112	1487
MICT2	1487
MICT212	1487
MICT3	1487
MICT4	1487

Code	Page
MIDTP1	1385
MIDTP112	1385
MIDTP114	1385
MIDTP12	1385
MIDTP14	1385
MIDTP2	1385
MIDTP34	1385
MIEHT3-M3	1155
MIEHT3-M5	1155
MIEHT4-M3	1155
MIEHT4-M5	1155
MIEHT6-M5	1155
MIFF-M5	1155
MIFT-M5	1155
MIG 10/25	1492
MIG 15/35	1492
MIG 20/50	1492
MIGCM10	1384
MIGCM12	1384
MIGCM8	1384
MIMF-M5	1155
MIMHT2-M3	1155
MIMHT3-M5	1155
MIMHT4-M3	1155
MIMHT4-M5	1155
MIMHT6-M5	1155
MIMM-M5	1155
MIMT112	1487
MIMT2	1487
MIMT212	1487
MIMT3	1487
MIMT4	1487
MIPC3-M5	1155
MIPC4-M3	1155
MIPC4-M5	1155
MIPC4-M6	1155
MIPC5-M5	1155
MIPC6-M6	1155
MIPL4-M3	1155
MIPL4-M5	1155
MIPL5-M6	1155
MIPP-M5	1155
MIRB18-M5	1155
MIRC-1	1385
MIRC-112	1385
MIRC-12	1385
MIRC-2	1385
MIRC-34	1385
MISB1	1384
MISB112	1384
MISB112N	1384
MISB114	1384
MISB12	1384
MISB12N	1384
MISB14	1384
MISB14N	1384
MISB1N	1384
MISB2	1384
MISB212	1384
MISB2N	1384
MISB34	1384
MISB34N	1384
MISB38	1384
MISB38N	1384
MISB4	1384
MISDM10	1385
MISDM10X1.0/3M	1385
MISDM12X1.0	1385
MISDM8	1385
MISTP1	1385
MISTP112	1385
MISTP114	1385
MISTP114N	1385
MISTP12	1385
MISTP12N	1385
MISTP14N	1385
MISTP1N	1385
MISTP2	1385
MISTP2N	1385
MISTP34	1385
MISTP34N	1385
MISTP38	1385
MISTP38N	1385
MIUT-M5	1155
MIWRSB-112N	1385
MIWRSB-114N	1385
MIWRSB-12N	1385
MIWRSB-14N	1385
MIWRSB-18N	1385
MIWRSB-1N	1385
MIWRSB-212N	1385
MIWRSB-2N	1385
MIWRSB-34N	1385
MIWRSB-38N	1385
MIWRSB-3N	1385
MIWRSB-4N	1385
MIWRSB-6N	1385
MIWRSG-1	1385
MIWRSG-112	1385
MIWRSG-114	1385
MIWRSG-12	1385
MIWRSG-14	1385
MIWRSG-18	1385
MIWRSG-2	1385
MIWRSG-212	1385
MIWRSG-3	1385
MIWRSG-34	1385
MIWRSG-38	1385
MIWRSG-4	1385
MK150HIT-1	936
MK150HIT-2	936
MK150HIT-3	936
MK150HIT-4	936
MK150HIT-5	936
MK150HIT-6	936
MLN12	70
MLN14	70
MLN16	70
MLN18	70
MLN20	70
MLN22	70
MLN24	70
MM010411	836
MM010611	836
MM011504N	1091
MM012206N	1091
MM012808N	1091
MM051504N	1091
MM052206N	1091
MM052228N	1091
MM052818N	1091
MM052828N	1091
MM501514N	1091
MM502216N	1091
MML16	1167
MNSE10-G02	846
MNSE10-G03	846
MNSE10-G04	846
MNSE12-G02	846
MNSE12-G03	846
MNSE12-G04	846
MNSE4-G01	846
MNSE4-G02	846
MNSE4-M5	846
MNSE6-G01	846
MNSE6-G02	846
MNSE8-G01	846
MNSE8-G02	846
MNSE8-G03	846
MNSF04	846
MNSF06	846
MNSF08	846
MNSF10	846
MNSF12	846
MO-14	656
MOBI-KIT	49
MOK-1	112
MOO-MS	1517
MOO-MS-BOX	1517
MOO-SS	1517
MP12-3-M5	820
MP1-2-M3	820
MP1-2-M5	820
MP1-3-M3	820
MP1-3-M5	820
MP7-2-M3	820
MP7-2-M5	820
MP7-3-M3	820
MP7-3-M5	820
MPAOW-04-100	1435
MPAOW-05-100	1435
MPAOW-06-100	1435
MPAOW-08-100	1435
MPAOW-10-50	1435
MPAOW-12-100	1435
MPAOW-16-100	1435
MPB10-G02	846
MPB10-G03	846
MPB10-G04	846
MPB12-G03	846
MPB12-G04	846
MPB14-G03	846
MPB14-G04	846
MPB4-G01	846
MPB4-G02	846
MPB4-M5	846
MPB6-G01	846
MPB6-G02	846
MPB6-M5	846
MPB8-G01	846
MPB8-G02	846
MPB8-G03	846
MPB8-G04	846
MPC10-02	845
MPC10-03	845
MPC10-04	845
MPC10-G02	845
MPC10-G03	845
MPC10-G04	845
MPC12-02	845
MPC12-03	845
MPC12-04	845
MPC12-G02	845
MPC12-G03	845
MPC12-G04	845
MPC14-G03	845
MPC14-G04	845
MPC4-01	845
MPC4-02	845
MPC4-G01	845
MPC4-G02	845
MPC4-M5	845
MPC4-M6	845
MPC6-01	845
MPC6-02	845
MPC6-G01	845
MPC6-G02	845
MPC6-G03	845
MPC6-G04	845
MPC6-M5	845
MPC6-M6	845
MPC8-01	845
MPC8-02	845
MPC8-03	845
MPC8-G01	845
MPC8-G02	845
MPC8-G03	845
MPC8-G04	845
MPCF10-G02	845
MPCF10-G03	845
MPCF10-G04	845
MPCF12-G02	845
MPCF12-G03	845
MPCF12-G04	845
MPCF4-G01	845
MPCF4-G02	845
MPCF6-G01	845
MPCF6-G02	845
MPCF8-G01	845
MPCF8-G02	845
MPCF8-G03	845
MPCFJ10-G02	846
MPCFJ10-G03	846
MPCFJ10-G04	846
MPCFJ12-G02	846
MPCFJ12-G03	846
MPCFJ12-G04	846
MPCFJ4-G01	846
MPCFJ4-G02	846
MPCFJ6-G01	846
MPCFJ6-G02	846
MPCFJ8-G02	846
MPCFJ8-G03	846
MPCFJ8-G04	846
MPCJ10-G02	846
MPCJ10-G03	846
MPCJ10-G04	846
MPCJ12-G02	846
MPCJ12-G03	846
MPCJ12-G04	846
MPCJ4-G01	846
MPCJ4-G02	846
MPCJ6-G01	846
MPCJ6-G02	846
MPCJ8-G02	846
MPCJ8-G03	846
MPCJ8-G04	846
MPCS10-G02	845
MPCS10-G03	845
MPCS10-G04	845
MPCS12-G02	845
MPCS12-G03	845
MPCS12-G04	845
MPCS14-G03	845
MPCS14-G04	845
MPCS4-01	845
MPCS4-G01	845
MPCS4-G02	845
MPCS4-M5	845
MPCS6-01	845
MPCS6-02	845
MPCS6-G01	845
MPCS6-G02	845
MPCS6-G03	845
MPCS6-G04	845
MPCS6-M5	845
MPCS8-01	845
MPCS8-02	845
MPCS8-G01	845
MPCS8-G02	845
MPCS8-G03	845
MPCS8-G04	845
MPG10-8	846
MPG12-10	846
MPG6-4	846
MPG8-6	846
MPH4-G01	846
MPH4-M5	846
MPH6-G01	846
MPH8-G01	846
MPH8-G02	846
MPJG10-4	846
MPJG10-6	846
MPJG10-8	846
MPJG12-10	846
MPJG12-8	846
MPJG6-4	846
MPJG8-4	846
MPJG8-6	846
MPL10-02	846
MPL10-03	846
MPL10-04	846
MPL10-G02	846
MPL10-G03	846
MPL10-G04	846
MPL12-02	846
MPL12-03	846
MPL12-04	846
MPL12-G02	846
MPL12-G03	846

Code	Page
MPL12-G04	846
MPL14-G03	846
MPL14-G04	846
MPL4-01	846
MPL4-G01	846
MPL4-G02	846
MPL4-M5	846
MPL6-01	846
MPL6-02	846
MPL6-G01	846
MPL6-G02	846
MPL6-M5	846
MPL8-01	846
MPL8-02	846
MPL8-03	846
MPL8-04	846
MPL8-G01	846
MPL8-G02	846
MPL8-G03	846
MPL8-G04	846
MPLF10-G02	845
MPLF4-G01	845
MPLF6-G01	845
MPLF6-G02	845
MPLF8-G02	845
MPLF8-G04	845
MPLL10-G02	846
MPLL10-G03	846
MPLL10-G04	846
MPLL12-G02	846
MPLL12-G03	846
MPLL12-G04	846
MPLL4-G01	846
MPLL6-G01	846
MPLL6-G02	846
MPLL8-G01	846
MPLL8-G02	846
MPLL8-G03	846
MPM-10	846
MPM-12	846
MPM303X10	756
MPM303X12	756
MPM303X14	756
MPM303X16	756
MPM303X6	756
MPM303X8	756
MPM-4	846
MPM-6	846
MPM-8	846
MPMF6-G01	845
MPMF6-G02	845
MPP007	49
MPP008	49
MPP010	49
MPP012	49
MPP014	49
MPP016	49
MPP018	49
MPP020	49
MPP022	49
MPP024	49
MPP026	49
MPP028	49
MPP030	49
MPP033	49
MPP035	49
MPP040	49
MPP045	49
MPP050	49
MPP055	49
MPP060	49
MPUC-10	846
MPUC-12	846
MPUC-14	846
MPUC-4	846
MPUC-6	846
MPUC-8	846
MPUL-10	846
MPUL-12	846
MPUL-14	846
MPUL-4	846
MPUL-6	846
MPUL-8	846
MPUT-10	846
MPUT-12	846
MPUT-14	846
MPUT-4	846
MPUT-6	846
MPUT-8	846
MPY-6	846
MPY-8	846
MR74	1761
MRD522	1761
MRDP-1	1634
MRDP-2	1634
MRDP-3	1634
MRDP-4	1634
MRDP-5	1634
MRT-12-250N	175
MRT-12-375N	175
MRT-12-500N	175
MRT-125-125N	168
MRT-125-250N	168
MRT-16-500N	175
MRT-187-125N	168
MRT-250-125N	168
MRT-250-250N	168
MRT-312-125N	168
MRT-375-250N	168
MRT-375-375N	168
MRT-500-375N	168
MRT-500-500N	168
MRT-6-125N	175
MRT-6-250N	175
MRT-625-500N	168
MRT-750-750N	168
MRT-8-250N	175
MRTP-1000-1000PR	169
MRTP-1000-1312SE	169
MRTP-10-250PR	175
MRTP-12-375PR	175
MRTP-12-500PR	175
MRTP-250-125PR	169
MRTP-250-250PR	169
MRTP-250-437SE	169
MRTP-375-250PR	169
MRTP-375-562SE	169
MRTP-500-375PR	169
MRTP-500-500PR	169
MRTP-500-750SE	169
MRTP-6-125PR	175
MRTP-6-250PR	175
MRTP-625-500PR	169
MRTP-750-1062SE	169
MRTP-750-500PR	169
MRTP-750-750PR	169
MRTP-8-125PR	175
MRTP-8-250PR	175
MS100SC-BNT14K	424
MS10SC-BNT14K	424
MS1901	1523
MS1902	1523
MS1903	1523
MS1904	1523
MS1905	1523
MS1906	1523
MS1907	1523
MS1908	1523
MS1909	1523
MS1910	1523
MS1911	1523
MS1912	1523
MS1913	1523
MS1914	1523
MS1915	1523
MS1916	1523
MS1917	1523
MS1918	1523
MS1919	1523
MS1920	1523
MS1921	1523
MS1922	1523
MS1923	1523
MS1924	1523
MS1925	1523
MS1926	1523
MS1927	1523
MS1928	1523
MS1929	1523
MS1930	1523
MS1931	1523
MS1932	1523
MS1933	1523
MS1934	1523
MS1935	1523
MS1936	1523
MS1937	1523
MS1938	1523
MS1939	1523
MS1940	1523
MS1941	1523
MS1942	1523
MS1943	1523
MS1944	1523
MS1945	1523
MS1946	1523
MS1947	1523
MS1948	1523
MS20-A	760
MS20-B	760
MS20-C	760
MS20-D	760
MS2SC-BNT14K	424
MS40-A	760
MS40-B	760
MS40-C	760
MS40-D	760
MS50SC-BNT14K	424
MS60-A	760
MS60-B	760
MS60-C	760
MS60-D	760
MSB12-12	1207
MSB14-14	1207
MSB14-18	1207
MSB38-14	1207
MSB38-38	1207
MSCT-10	1215
MSCT-12	1215
MSCT-6	1215
MSCT-8	1215
MSE12-12	1208
MSE12-14	1208
MSE12-38	1208
MSE14-14	1208
MSE14-18	1208
MSE14-38	1208
MSE18-18	1208
MSE316-14	1208
MSE316-18	1208
MSE34-34	1208
MSE38-14	1208
MSE38-18	1208
MSE38-38	1208
MSE516-14	1208
MSE516-18	1208
MSHAR2AT-04-100	10
MSHAR2AT-06-100	10
MSHAR2AT-08-100	10
MSHAR2AT-12-50	10
MSHAR2AT-16-50	10
MSP1-1	1207
MSP12-12	1207
MSP12-34	1207
MSP12-38	1207
MSP14-14	1207
MSP14-18	1207
MSP14-38	1207
MSP18-14	1207
MSP18-18	1207
MSP316-14	1207
MSP316-18	1207
MSP316-38	1207
MSP34-12	1207
MSP34-34	1207
MSP38-12	1207
MSP38-14	1207
MSP38-18	1207
MSP38-38	1207
MSP516-12	1207
MSP516-14	1207
MSP516-18	1207
MSP516-38	1207
MSR14-14	1208
MSR14-18	1208
MSR38-38	1208
M-SR45EL-15	1218
M-SR45EL-22	1218
M-SR45EL-35	1218
M-SR45EL-45	1218
MSR516-14	1208
M-SR90-10	1218
M-SR90-15	1218
M-SR90-22	1218
M-SR90-28	1218
M-SR90-35	1218
M-SR90-42	1218
M-SR90-54	1218
M-SR90-8	1218
M-SRBTC-15-12	1218
M-SREC-15	1218
M-SREC-22	1218
M-SRET-10	1218
M-SRET-15	1218
M-SRET-22	1218
M-SRET-28	1218
M-SRET-42	1218
M-SRRB-22-15	1218
M-SRRB-28-15	1218
M-SRRB-28-22	1218
M-SRRB-42-15	1218
M-SRRB-42-22	1218
M-SRRB-42-28	1218
M-SRRB-42-35	1218
M-SRRB-54-15	1218
M-SRRB-54-22	1218
M-SRRB-54-28	1218
M-SRRB-54-35	1218
M-SRRB-54-42	1218
M-SRRC-10-8	1218
M-SRRC-15-10	1218
M-SRRC-22-15	1218
M-SRRC-28-22	1218
M-SRRF-22-15	1218
M-SRRF-28-15	1218
M-SRRF-28-22	1218
M-SRRF-35-22	1218
M-SRRF-35-28	1218
M-SRRF-42-15	1218
M-SRRF-42-28	1218
M-SRRF-42-35	1218
M-SRRF-54-22	1218
M-SRRF-54-35	1218
M-SRRF-54-42	1218
M-SRSC10	1218
M-SRSC-22	1218
M-SRSC-28	1218
M-SRSC-35	1218
M-SRSC-42	1218
M-SRSC-54	1218
M-SRST90-15	1218
M-SRST90-22	1218
M-SRST90-28	1218
M-SRTC-15-12	1218
M-SRTC-15-34	1218
M-SRTC-22-34	1218
MSS.AB	1624
MSSPVC	1633
MST 38/35	1492
MST 50	1492

Code	Page
MST12-12	1207
MST12-14	1207
MST12-38	1207
MST14-12	1207
MST14-14	1207
MST14-18	1207
MST14-38	1207
MST18-14	1207
MST18-18	1207
MST316-14	1207
MST316-18	1207
MST34-12	1207
MST34-34	1207
MST38-12	1207
MST38-14	1207
MST38-18	1207
MST38-38	1207
MST516-14	1207
MST516-18	1207
MST516-38	1207
MT77724	1588
MT77748	1588
MTA-110-3-UPVC	1104
MTA-110-4-UPVC	1104
MTA-110-5-UPVC	1104
MTA-12-38-UPVC	1104
MTA-16-12-UPVC	1104
MTA-16-38-UPVC	1104
MTA-20-12-UPVC	1104
MTA-20-34-UPVC	1104
MTA-20-38-UPVC	1104
MTA-25-12-UPVC	1104
MTA-25-1-UPVC	1104
MTA-25-34-UPVC	1104
MTA-32-114-UPVC	1104
MTA-32-1-UPVC	1104
MTA-32-34UPVC	1104
MTA-40-112-UPVC	1104
MTA-40-114-UPVC	1104
MTA-40-1-UPVC	1104
MTA-50-112-UPVC	1104
MTA-50-114-UPVC	1104
MTA-50-2-UPVC	1104
MTA-63-112-UPVC	1104
MTA-63-212-UPVC	1104
MTA-63-2-UPVC	1104
MTA-75-212-UPVC	1104
MTA-75-2-UPVC	1104
MTA-75-3-UPVC	1104
MTA-90-212-UPVC	1104
MTA-90-3-UPVC	1104
MTA-90-4-UPVC	1104
MTC-300	260
MTC-450	260
MTC-525	260
MTC-600	260
MTP/B02-M16/2S	71
MTS-10	1213
MTS-12	1213
MTS-15	1213
MTS-16	1213
MTS-18	1213
MTS-22	1213
MTS-28	1213
MTS-4	1213
MTS-6	1213
MTS-8	1213
MU05	1172
MU05/10	1172
MU10	1172
MU10/13	1172
MU10/17	1172
MU10/21	1172
MU13	1172
MU13/17	1172
MU13/21	1172
MU17	1172
MU17/21	1172
MU17/26	1172
MU21	1172
MU21/26	1172
MU21/33	1172
MU26	1172
MU26/33	1172
MU33	1172
MV-10L-4N	157
MV-10L-4RG	157
MV-10L-8N	157
MV-10L-8RG	157
MV-10S-4RG	157
MV-10S-8N	157
MV-10S-8RG	157
MV-12L-4N	157
MV-12L-4RG	157
MV-12L-8N	157
MV-12L-8RG	157
MV-12S-4RG	157
MV-12S-8N	157
MV-12S-8RG	157
MV-6L-4N	157
MV-6L-4RG	157
MV-6L-8N	157
MV-6L-8RG	157
MV-6S-8N	157
MV-6S-8RG	157
MV-8L-4N	157
MV-8L-4RG	157
MV-8L-8N	157
MV-8L-8RG	157
MV-8S-4RG	157
MV-8S-8N	157
MV-8S-8RG	157
MVC04	246
MVC06	246
MVC08	246
MVC12	246
MVC16	246
MVC20	246
MVC24	246
MVC32	246
MVS-12	926
MVS-14	926
MVS-38	926
MVSM-12	926
MVSM-14	926
MVSM-18	926
MVSM-38	926
MW011504N	883
MW012206N	883
MW012808N	883
MW012818N	883
MW052206N	883
MW052818N	883
MW502216N	883
MWC-1000-1000	171
MWC-10-250	177
MWC-10-500	177
MWC-12-250	177
MWC-12-375	177
MWC-12-500	177
MWC-125-125	171
MWC-14-375	177
MWC-15-500	177
MWC-16-500	177
MWC-18-500	177
MWC-187-125	171
MWC-250-125	171
MWC-250-250	171
MWC-312-125	171
MWC-312-250	171
MWC-3-125	177
MWC-375-250	171
MWC-375-375	171
MWC-375-500	171
MWC-375-750	171
MWC-4-125	177
MWC-500-375	171
MWC-500-500	171
MWC-500-750	171
MWC-6-125	177
MWC-6-250	177
MWC-625-500	171
MWC-750-750	171
MWC-8-125	177
MWC-8-250	177
MWC-8-500	177
MWE-250-125	171
MWE-250-250	171
MWE-375-250	171
MWE-500-500	171
MWE-750-750	171
MX1518410X4	250
MX1591.4.10X4	250
MX2-1/2-AV	694
MX2-1/2-B00	694
MX2-1/2-F00	692
MX2-1/2-F03	692
MX2-1/2-FC00	692
MX2-1/2-FC03	692
MX2-1/2-FCA	693
MX2-1/2-FL	694
MX2-1/2-L00	693
MX2-1/2-R004	691
MX2-1/2-R014	691
MX2-1/2-V01	693
MX2-1/2-V16	693
MX2-1/2-V36	694
MX2-3/4-AV	694
MX2-3/4-F00	692
MX2-3/4-F03	692
MX2-3/4-FC00	692
MX2-3/4-FC03	692
MX2-3/4-FCA	693
MX2-3/4-FL	694
MX2-3/4-L00	693
MX2-3/4-R004	691
MX2-3/4-R014	691
MX2-3/4-V01	693
MX2-3/4-V16	693
MX2-3/4-V36	694
MX2-3/8-AV	694
MX2-3/8-F00	692
MX2-3/8-F03	692
MX2-3/8-FC00	692
MX2-3/8-FC03	692
MX2-3/8-FCA	693
MX2-3/8-FL	694
MX2-3/8-L00	693
MX2-3/8-R004	691
MX2-3/8-R014	691
MX2-3/8-V01	693
MX2-3/8-V16	693
MX2-3/8-V36	694
MX2-S	694
MX2-X	695
MX2-Y	695
MX3-1-AV	694
MX3-1-B00	694
MX3-1-F00	692
MX3-1-F03	692
MX3-1-FC00	692
MX3-1-FC03	692
MX3-1-FCA	693
MX3-1-FL	694
MX3-1-L00	693
MX3-1-R004	691
MX3-1-R014	691
MX3-1-V01	693
MX3-1-V16	693
MX3-1-V36	694
MX3-3/4-AV	694
MX3-3/4-F00	692
MX3-3/4-F03	692
MX3-3/4-FC00	692
MX3-3/4-FC03	692
MX3-3/4-FCA	693
MX3-3/4-FL	694
MX3-3/4-L00	693
MX3-3/4-R004	691
MX3-3/4-R014	691
MX3-3/4-V01	693
MX3-3/4-V16	693
MX3-3/4-V36	694
MX3-S	694
MX3-X	695
MX3-Y	695
MXA9511424	250
MXA9551424	250
MXR8550	250
MXR9550	250
MXR9560	250
N	
N10	141
N-10	178
N-1000	172
N12	141
N-12	178
N-125-FT	172
N12C1008010MB	916
N12C1008010MR	916
N12C1008015MB	916
N12C1008015MR	916
N12C100802.5MB	916
N12C100802.5MR	916
N12C100805MB	916
N12C100805MR	916
N12C1209010MB	916
N12C1209010MB12	916
N12C1209010MR	916
N12C1209010MR12	916
N12C1209015MB	916
N12C1209015MB12	916
N12C1209015MR	916
N12C1209015MR12	916
N12C120902.5MB	916
N12C120902.5MB12	916
N12C120902.5MR	916
N12C120902.5MR12	916
N12C120905MB	916
N12C120905MB12	916
N12C120905MR	916
N12C120905MR12	916
N12C604010MB	916
N12C604010MR	916
N12C604015MB	916
N12C604015MR	916
N12C60402.5MB	916
N12C60402.5MR	916
N12C60405MB	916
N12C60405MR	916
N12C806010MB	916
N12C806010MR	916
N12C806015MB	916
N12C806015MR	916
N12C80602.5MB	916
N12C80602.5MR	916
N12C80605MB	916
N12C80605MR	916
N14	141
N-15	178
N16	141
N-16	178
N171AEBD	700
N171AEMBD	700
N171AEPBDA	701
N174BEBD	700
N174BEMBD	700
N174BEPBDA	701
N174BL	701
N174BRMA	701
N174BRMD	701
N-18	178
N-187	172
N20	141
N-20	178
N-25	178
N-250	172
N-3	178
N-312	172
N-375	172

Code	Page
N4	141
N-4	178
N-500	172
N6	141
N-6	178
N-625	172
N-750	172
N8	141
N-8	178
N-875	172
NB0709	1519
NB0810	1519
NB0911	1519
NB1012	1519
NB1113	1519
NB1214	1519
NB1315	1519
NB1416	1519
NB1517	1519
NB1618	1519
NBJ2-2	143
NBJ8-8	143
NBM1050	1480
NBM1060	1480
NBM840	1480
NBP12	143
NBP4	143
NBP6	143
NBP8	143
NC2239	883
NC448	883
NC471	883
NC473	883
NCG-22	1547
NC-HTUBE1	1383
NC-HTUBE112	1383
NC-HTUBE112-6.5	1383
NC-HTUBE112N-6.5	1383
NC-HTUBE114	1383
NC-HTUBE114-6.5	1383
NC-HTUBE114N	1383
NC-HTUBE114N-6.5	1383
NC-HTUBE12	1383
NC-HTUBE12-6.5	1383
NC-HTUBE12N	1383
NC-HTUBE12N-6.5	1383
NC-HTUBE1-6.5	1383
NC-HTUBE1N	1383
NC-HTUBE1N-6.5	1383
NC-HTUBE2	1383
NC-HTUBE2-6.5	1383
NC-HTUBE2N	1383
NC-HTUBE2N-6.5	1383
NC-HTUBE34	1383
NC-HTUBE34-6.5	1383
NC-HTUBE34N	1383
NC-HTUBE34N-6.5	1383
NCLNPT6	1497
NCSNPT1	1497
NCSNPT112	1497
NCSNPT114	1497
NCSNPT12	1497
NCSNPT2	1497
NCSNPT212	1497
NCSNPT3	1497
NCSNPT34	1497
NCSNPT4	1497
NCSNPT6	1497
NC-TUBE1	1383
NC-TUBE112	1383
NC-TUBE112-6.5	1383
NC-TUBE112N	1383
NC-TUBE112N-6.5	1383
NC-TUBE114	1383
NC-TUBE114-6.5	1383
NC-TUBE114N	1383
NC-TUBE114N-6.5	1383
NC-TUBE12	1383
NC-TUBE12-6.5	1383
NC-TUBE12N	1383
NC-TUBE12N-6.5	1383
NC-TUBE1-6.5	1383
NC-TUBE1N	1383
NC-TUBE1N-6.5	1383
NC-TUBE2	1383
NC-TUBE2-6.5	1383
NC-TUBE2N	1383
NC-TUBE2N-6.5	1383
NC-TUBE3	1383
NC-TUBE34	1383
NC-TUBE34-6.5	1383
NC-TUBE34N	1383
NC-TUBE34N-6.5	1383
NC-TUBE3-6.5	1383
NC-TUBE3N	1383
NC-TUBE3N-6.5	1383
NC-TUBE4	1383
NC-TUBE4-6.5	1383
NC-TUBE4N	1383
NC-TUBE4N-6.5	1383
NCV-1	243
NCV-12	243
NCV-14	243
NCV-34	243
NCV-38	243
NCW-15	1547
NCW-22	1547
NCW-28	1547
NE12	143
NE16	143
NE20	143
NE4	143
NE6	143
NE8	143
NF12	141
NF16	141
NF20	141
NF4	141
NF6	141
NF8	141
NFC16-16	141
NFC4-2	141
NFC4-8	141
NFC6-8	141
NFC8-12	141
NFC8-6	141
NFC8-8	141
NFV-2	1436
NFV-3	1436
NFV-4	1436
NFV-6	1436
NHP-1	1483
NHP-34	1483
NMC12-12	142
NMC12-12T	142
NMC12-16T	142
NMC16-12	142
NMC16-16	142
NMC16-16T	142
NMC16-20	142
NMC20-16	142
NMC20-20	142
NMC20-20T	142
NMC24-24	142
NMC24-24T	142
NMC4-4	142
NMC4-4T	142
NMC4-6	142
NMC4-8T	142
NMC6-4	142
NMC6-6	142
NMC6-6T	142
NMC8-12	142
NMC8-12T	142
NMC8-16	142
NMC8-6	142
NMC8-6T	142
NMC8-8	142
NMC8-8T	142
NME4-4T	143
NME4-6T	143
NME6-6	142
NME6-6T	143
NME8-8	142
NN12	141
NN16	141
NN20	141
NN4	141
NN6	141
NN8	141
NO11-13	1536
NO13-15	1536
NO14-17	1536
NO15-18	1536
NO17-20	1536
NO19-22	1536
NO20-23	1536
NO22-25	1536
NO23-27	1536
NO25-28	1536
NO28-31	1536
NO31-34	1536
NO34-37	1536
NO37-40	1536
NO40-43	1536
NO5-7	1536
NO7-9	1536
NO9-11	1536
NO9-12	1536
NOR-05738400026	1557
NOR-05738400033	1557
NOR-05738400042	1557
NOR-05738400048	1557
NOR-05738400060	1557
NOR-05738400076	1557
NOR-05738400088	1557
NOR-05738400114	1557
NOR-05738400139	1557
NOR-05738400168	1557
NOR-05738400180	1557
NOR-05738400193	1557
NOR-05738400206	1557
NOR-05738400219	1557
NOR-05738400267	1557
NOR-05738400355	1557
NOR-05738400406	1557
NOR-05738400508	1557
NOR-05738400609	1557
NOR-05778400219	1557
NOR-05788400026	1557
NOR-05788400033	1557
NOR-05788400048	1557
NOR-05788400060	1557
NOR-05788400076	1557
NOR-05788400088	1557
NOR-05788400114	1557
NOR-05788400139	1557
NOR-05788400168	1557
NOR-05917182018	1534
NOR-05917182020	1534
NOR-05917182022	1534
NOR-05917182024	1534
NOR-05917182026	1534
NOR-05917182028	1534
NOR-05917182030	1534
NOR-05917182033	1534
NOR-05917182036	1534
NOR-05917182039	1534
NOR-05917182042	1534
NOR-05917202045	1534
NOR-05917202049	1534
NOR-05917202053	1534
NOR-05917202057	1534
NOR-05917202061	1534
NOR-05917202066	1534
NOR-05917252071	1534
NOR-05917252076	1534
NOR-05917252082	1534
NOR-05917252088	1534
NOR-05917252094	1534
NOR-05917252101	1534
NOR-05917252108	1534
NOR-05917252117	1534
NOR-05917252126	1534
NOR-05917302135	1534
NOR-05917302145	1534
NOR-05917302156	1534
NOR-05917302168	1534
NOR-05917302181	1534
NOR-05917302194	1534
NOR-05917302207	1534
NOR-05917302220	1534
NOR-05917302233	1534
NOR-05917302246	1534
NOR-1	1534
NOR-1A	1534
NOR-2	1534
NOR-2A	1534
NOR-2X	1534
NOR-3	1534
NOR-3X	1534
NOR-4	1534
NOR-4X	1534
NOR-5	1534
NOR-8880000003	1544
NOR-8880000080	1544
NOR-COBRA10	1535
NOR-COBRA105	1535
NOR-COBRA11	1535
NOR-COBRA115	1535
NOR-COBRA12	1535
NOR-COBRA13	1535
NOR-COBRA14	1535
NOR-COBRA15	1535
NOR-COBRA16	1535
NOR-COBRA17	1535
NOR-COBRA18	1535
NOR-COBRA19	1535
NOR-COBRA20	1535
NOR-COBRA21	1535
NOR-COBRA24	1535
NOR-COBRA26	1535
NOR-COBRA27	1535
NOR-COBRA28	1535
NOR-COBRA29	1535
NOR-COBRA75	1535
NOR-COBRA8	1535
NOR-COBRA9	1535
NOR-FGRR1029	1557
NOR-FGRR106	1557
NOR-FGRR111	1557
NOR-FGRR1154	1557
NOR-FGRR156	1557
NOR-FGRR170	1557
NOR-FGRR355	1557
NOR-FGRR429	1557
NOR-FGRR45	1557
NOR-FGRR488	1557
NOR-FGRR549	1557
NOR-FGRR576	1557
NOR-FGRR609	1557
NOR-FGRR74	1557
NOR-FGRR769	1557
NOR-FGRR85	1557
NOR-FGRR896	1557
NOR-GES10R14	1153
NOR-GES10R38	1153
NOR-GES12R12	1153
NOR-GES12R38	1153
NOR-GES14R12	1153
NOR-GES16R12	1153
NOR-GES16R34	1153
NOR-GES19R34	1153
NOR-GES25R1	1153
NOR-GES4R14	1153
NOR-GES4R18	1153

Code	Page
NOR-GES5R14	1153
NOR-GES6R14	1153
NOR-GES6R18	1153
NOR-GES6R38	1153
NOR-GES8R12	1153
NOR-GES8R14	1153
NOR-GES8R38	1153
NOR-GRS10-6	1153
NOR-GRS10-8	1153
NOR-GRS12-10	1153
NOR-GRS12-8	1153
NOR-GRS4-3	1153
NOR-GRS5-4	1153
NOR-GRS6-4	1153
NOR-GRS8-4	1153
NOR-GRS8-6	1153
NOR-GS10	1153
NOR-GS12	1153
NOR-GS13	1153
NOR-GS14	1153
NOR-GS16	1153
NOR-GS19	1153
NOR-GS25	1153
NOR-GS3	1153
NOR-GS4	1153
NOR-GS5	1153
NOR-GS6	1153
NOR-GS8	1153
NOR-HD118	1534
NOR-HD130	1534
NOR-HD143	1534
NOR-HD168	1534
NOR-HD181	1534
NOR-HD194	1534
NOR-HD45	1534
NOR-HD54	1534
NOR-HD67	1534
NOR-HD79	1534
NOR-HD92	1534
NOR-KS12	1153
NOR-KS4	1153
NOR-KS5	1153
NOR-KS6	1153
NOR-MOO	1534
NOR-O	1534
NOR-OO	1534
NOR-OOO	1534
NOR-RLGUP-10	1544
NOR-RLGUP-12	1544
NOR-RLGUP-13	1544
NOR-RLGUP-16	1544
NOR-RLGUP-19	1544
NOR-RLGUP-22	1544
NOR-RLGUP-25	1544
NOR-RLGUP-28	1544
NOR-RLGUP-29	1544
NOR-RLGUP-32	1544
NOR-RLGUP-35	1544
NOR-RLGUP-40	1544
NOR-RLGUP-44	1544
NOR-RLGUP-5	1544
NOR-RLGUP-6	1544
NOR-RLGUP-8	1544
NOR-RLGUP-9	1544
NOR-RSGUP-10	1544
NOR-RSGUP-12	1544
NOR-RSGUP-13	1544
NOR-RSGUP-16	1544
NOR-RSGUP-19	1544
NOR-RSGUP-21	1544
NOR-RSGUP-22	1544
NOR-RSGUP-25	1544
NOR-RSGUP-28	1544
NOR-RSGUP-30	1544
NOR-RSGUP-32	1544
NOR-RSGUP-35	1544
NOR-RSGUP-6	1544
NOR-RSGUP-8	1544
NOR-RSGUU-12	1544
NOR-RSGUU-13	1544
NOR-RSGUU-16	1544
NOR-RSGUU-19	1544
NOR-RSGUU-21	1544
NOR-RSGUU-22	1544
NOR-RSGUU-25	1544
NOR-RSGUU-28	1544
NOR-RSGUU-30	1544
NOR-RSGUU-35	1544
NOR-RSGUU-6	1544
NOR-SS-1	1534
NOR-SS-1A	1534
NOR-SS-1X	1534
NOR-SS-2	1534
NOR-SS-2A	1534
NOR-SS-2X	1534
NOR-SS-3	1534
NOR-SS-3X	1534
NOR-SS-4	1534
NOR-SS-4X	1534
NOR-SS-5	1534
NOR-SS-75-12	1534
NOR-SS-75-16	1534
NOR-SS-75-18	1534
NOR-SS-MOO	1534
NOR-SS-O	1534
NOR-SS-OO	1534
NOR-SS-OOO	1534
NOR-TES10R38	1153
NOR-TES6R18	1153
NOR-TES8R14	1153
NOR-TRS10-13-10	1153
NOR-TRS10-6-10	1153
NOR-TRS10-8-10	1153
NOR-TRS12-10-12	1153
NOR-TRS12-6-12	1153
NOR-TRS12-8-12	1153
NOR-TRS15-6-15	1153
NOR-TRS15-8-15	1153
NOR-TRS18-10-18	1153
NOR-TRS4-6-4	1153
NOR-TRS6-4-6	1153
NOR-TRS8-4-8	1153
NOR-TRS8-6-8	1153
NOR-TS10	1153
NOR-TS12	1153
NOR-TS13	1153
NOR-TS14	1153
NOR-TS15	1153
NOR-TS16	1153
NOR-TS19	1153
NOR-TS25	1153
NOR-TS3	1153
NOR-TS4	1153
NOR-TS5	1153
NOR-TS6	1153
NOR-TS7	1153
NOR-TS8	1153
NOR-WES10R14	1153
NOR-WES10R38	1153
NOR-WES12R12	1153
NOR-WES12R38	1153
NOR-WES19R34	1153
NOR-WES25R1	1153
NOR-WES4R14	1153
NOR-WES4R18	1153
NOR-WES6R14	1153
NOR-WES6R18	1153
NOR-WES6R38	1153
NOR-WES8R12	1153
NOR-WES8R14	1153
NOR-WS10	1153
NOR-WS12	1153
NOR-WS13	1153
NOR-WS16	1153
NOR-WS19	1153
NOR-WS25	1153
NOR-WS3	1153
NOR-WS4	1153
NOR-WS5	1153
NOR-WS6	1153
NOR-WS8	1153
NOR-YRS4-6-4	1153
NOR-YRS6-8-6	1153
NOR-YS10	1153
NOR-YS12	1153
NOR-YS13	1153
NOR-YS14	1153
NOR-YS16	1153
NOR-YS19	1153
NOR-YS3	1153
NOR-YS4	1153
NOR-YS5	1153
NOR-YS6	1153
NOR-YS8	1153
NOZ.C	1620
NOZ.S3000	1620
NOZA.120S	1620
NOZA.250S	1620
NOZA.60S	1620
NOZA.SS	1620
NOZA.X	1620
NOZA.X25	1620
NOZ-MAB	1623
NPC15	884
NPT62000114	1183
NPT62001010	1183
NPT62001313	1183
NPT62001717	1183
NPT62002121	1183
NPT62002727	1183
NPT62003232	1183
NPT62004242	1183
NPT62004848	1183
NPT62006060	1183
NPT62007676	1183
NPT62008989	1183
NPT62041310	1184
NPT62041713	1184
NPT62042117	1184
NPT62042721	1184
NPT62043227	1184
NPT62044232	1184
NPT62044842	1184
NPT62046048	1184
NPT62047660	1184
NPT62048976	1184
NPT62060114	1185
NPT62061010	1185
NPT62061313	1185
NPT62061717	1185
NPT62062121	1185
NPT62062727	1185
NPT62063232	1185
NPT62064242	1185
NPT62064848	1185
NPT62066060	1185
NPT62067676	1185
NPT62068989	1185
NPT62181000	1184
NPT62181300	1184
NPT62181700	1184
NPT62182100	1184
NPT62182700	1184
NPT62183200	1184
NPT62184200	1184
NPT62184800	1184
NPT62186000	1184
NPT62187600	1184
NPT62188900	1184
NPTM0203CF	23
NPTM0204CF	23
NPTM0403CF	23
NPTM0404CF	23
NPTM0405CF	23
NPTM0406CF	23
NPTM0604CF	23
NPTM0605CF	23
NPTM0606CF	23
NPTM0608CF	23
NPTM0805CF	23
NPTM0806CF	23
NPTM0808CF	23
NPTM0810CF	23
NPTM0812CF	23
NPTM1208CF	23
NPTM1210CF	23
NPTM1212CF	23
NPTM1616CF	23
NPTM1620CF	23
NPTM2016CF	23
NPTM2020CF	23
NPTM2424CF	23
NPTM3232CF	23
NSA12-12	143
NSA12-16	143
NSA12-8	143
NSA16-16	143
NSA16-20	143
NSA20-16	143
NSA20-20	143
NSA4-4	143
NSA6-4	143
NSA6-6	143
NSA8-6	143
NSA8-8	143
NSC12	141
NSC16	141
NSC24	141
NSC4	141
NSC6	141
NSC8	141
NSE1/4-U10C	791
NSE1/8-U10C	791
NSE5/32-U10C	791
NSP007	49
NSP008	49
NSP010	49
NSP012	49
NSP014	49
NSP016	49
NSP018	49
NSP020	49
NSP022	49
NSP024	49
NSP026	49
NSP028	49
NSP030	49
NSP033	49
NSP035	49
NSP040	49
NSP045	49
NSP050	49
NSP055	49
NSP060	49
NT12	143
NT20	143
NT24	143
NT4	143
NT6	143
NT8	143
NTA1	1497
NTA112	1497
NTA114	1497
NTA2	1497
NTB100BA	421
NTB100CA	421
NTB105BA	421
NTB105CA	421
NTB25BA	421
NTB25CA	421
NTB31BA	421
NTB31CA	421
NTB38BA	421
NTB38CA	421
NTB47BA	421
NTB47CA	421
NTB60BA	421
NTB60CA	421
NTB70BA	421
NTB70CA	421

Code	Page
NTB80BA	421
NTB80CA	421
NTB90BA	421
NTB90CA	421
NTC1	1497
NTC112	1497
NTC114	1497
NTC12	1497
NTC2	1497
NTC34	1497
NTI1/813	914
NTI12/375	914
NTI12/375B	914
NTI12/375G	914
NTI12/375N	914
NTI12/375R	914
NTI12/375Y	914
NTI14/170	914
NTI14/170B	914
NTI14/170G	914
NTI14/170N	914
NTI14/170R	914
NTI14/170Y	914
NTI18/075	914
NTI316/117	914
NTI316/117N	914
NTI34/594	914
NTI38/250	914
NTI38/250B	914
NTI38/250G	914
NTI38/250N	914
NTI38/250R	914
NTI38/250Y	914
NTI516/212	914
NTI516/212B	914
NTI516/212N	914
NTI516/212R	914
NTI532/096	914
NTI58/500	914
NTM04/025	913
NTM04/025B	913
NTM04/025G	913
NTM04/025N	913
NTM04/025R	913
NTM04/025Y	913
NTM04/030	913
NTM05/030	913
NTM05/030B	913
NTM05/030G	913
NTM05/030N	913
NTM05/030R	913
NTM05/030Y	913
NTM06/040	913
NTM06/040-100	913
NTM06/040B	913
NTM06/040B-100	913
NTM06/040G	913
NTM06/040G-100	913
NTM06/040N	913
NTM06/040N-100	913
NTM06/040R	913
NTM06/040R-100	913
NTM06/040Y	913
NTM06/040Y-100	913
NTM08/055	913
NTM08/055N	913
NTM08/060	913
NTM08/060-100	913
NTM08/060B	913
NTM08/060B-100	913
NTM08/060G	913
NTM08/060N	913
NTM08/060N-100	913
NTM08/060R	913
NTM08/060Y	913
NTM10/070	913
NTM10/070B	913
NTM10/070G	913
NTM10/070N	913
NTM10/070R	913
NTM10/070Y	913
NTM10/080	913
NTM10/080-100	913
NTM10/080B	913
NTM10/080B-100	913
NTM10/080G	913
NTM10/080N	913
NTM10/080N-100	913
NTM10/080R	913
NTM10/080Y	913
NTM12/090	913
NTM12/090B	913
NTM12/090G	913
NTM12/090N	913
NTM12/090R	913
NTM12/090Y	913
NTM12/100	913
NTM12/100N	913
NTM12/100R	913
NTM14/110	913
NTM14/110N	913
NTM15/120	913
NTM16/130	913
NTM18/140	913
NTM22/170	913
NTSWC112	1497
NTSWC2	1497
NU-1000-1000AN	170
NU-125-125AN	170
NU-125-250AN	170
NU-250-250AN	170
NU-312-312AN	170
NU-375-250AN	170
NU-375-375AN	170
NU-500-500AN	170
NU-750-750AN	170
NV6000-1	983
NV6000-12	983
NV6000-14	983
NV6000-18	983
NV6000-34	983
NV6000-38	983
O	
OC-KIT-MS	1536
ODSCV1414	1419
ODSCV1438	1419
ODSCV3838	1419
ODSCV51638	1419
ODT316L-W-H-1.0	1192
ODT316L-W-H-1.5	1192
ODT316L-W-H-2	1192
ODT316L-W-H-2.5	1192
ODT316L-W-H-3	1192
ODT316L-W-H-4	1192
OE-1	1183
OE-112	1183
OE-114	1183
OE-12	1183
OE-14	1183
OE-18	1183
OE-2	1183
OE-212	1183
OE-3	1183
OE-34	1183
OE-38	1183
OE-4	1183
OEMC14	1419
OEMC38	1419
OEMC3814	1419
OET0041	1538
OET0045	1538
OET0305	1538
OET0507	1538
OET0709	1538
OET0811	1538
OET0911	1538
OET1113	1538
OET1315	1538
OET1517	1538
OET1518	1538
OET1619	1538
OET1720	1538
OET1922	1538
OET2023	1538
OET2225	1538
OET2327	1538
OET2528	1538
OET2731	1538
OET2831	1538
OET3134	1538
OET3437	1538
OET3740	1538
OET4043	1538
OG50-010	412
OG50-050	412
OI02	1200
OI04	1200
OI05	1200
OI06	1200
OI08	1200
OI10	1200
OI12	1200
OIB02	1200
OIB03	1200
OIB04	1200
OIB05	1200
OIB06	1200
OIB08	1200
OM04	1197
OM06	1197
OM08	1197
OM10	1197
OM12	1197
OM15	1197
OM16	1197
OM18	1197
OM22	1197
OM28	1197
OMB04	1197
OMB05	1197
OMB06	1197
OMB08	1197
OMB10	1197
OMB12	1197
OMB15	1197
OMB16	1197
OMC-1000-1312SE	166
OMC-10-250EO	173
OMC-10-375EO	173
OMC-10-500EO	173
OMC-12-250EO	173
OMC-12-375EO	173
OMC-12-500EO	173
OMC-125-312SE	166
OMC-187-375SE	166
OMC-250-250EO	166
OMC-250-437SE	166
OMC-250-500EO	166
OMC-312-500SE	166
OMC-375-375EO	166
OMC-375-562SE	166
OMC-500-250EO	166
OMC-500-375EO	166
OMC-500-500EO	166
OMC-500-750SE	166
OMC-6-125EO	173
OMC-6-250EO	173
OMC-6-375EO	173
OMC-6-500EO	173
OMC-750-1062SE	166
OMC-750-750EO	166
O-MS	1517
O-MS-BOX	1517
ON14	1419
ON38	1419
OO-MS	1517
OO-MS-BOX	1517
OOO-MS	1517
OOO-MS-BOX	1517
OOO-SS	1517
OO-SS	1517
OP1	1536
OPAN14	1655
OPAN6	1655
OPS-15	1547
OPS-22	1547
OPS-28	1547
OR-2-40	280
ORFSF0404CF	22
ORFSF0404SS	34
ORFSF044504CF	22
ORFSF044504SS	34
ORFSF049004CF	22
ORFSF049004SS	34
ORFSF0604CF	22
ORFSF0604SS	34
ORFSF0605CF	22
ORFSF0605SS	34
ORFSF0606CF	22
ORFSF0606SS	34
ORFSF064504CF	22
ORFSF064504SS	34
ORFSF064505CF	22
ORFSF064505SS	34
ORFSF064506CF	22
ORFSF064506SS	34
ORFSF069004CF	22
ORFSF069004SS	34
ORFSF069005CF	22
ORFSF069005SS	34
ORFSF069006CF	22
ORFSF069006SS	34
ORFSF0806CF	22
ORFSF0806SS	34
ORFSF0808CF	22
ORFSF0808SS	34
ORFSF084506CF	22
ORFSF084506SS	34
ORFSF084508CF	22
ORFSF084508SS	34
ORFSF089006CF	22
ORFSF089006SS	34
ORFSF089008CF	22
ORFSF089008SS	34
ORFSF1008CF	22
ORFSF1008SS	34
ORFSF1010CF	22
ORFSF1010SS	34
ORFSF1012CF	22
ORFSF1012SS	34
ORFSF104508CF	22
ORFSF104510CF	22
ORFSF104510SS	34
ORFSF104512CF	22
ORFSF104512SS	34
ORFSF109008CF	22
ORFSF109010CF	22
ORFSF109010SS	34
ORFSF109012CF	22
ORFSF109012SS	34
ORFSF1208CF	22
ORFSF1208SS	34
ORFSF1210CF	22
ORFSF1210SS	34
ORFSF1212CF	22
ORFSF1212SS	34
ORFSF124508CF	22
ORFSF124510CF	22
ORFSF124512CF	22
ORFSF124512SS	34
ORFSF129008CF	22
ORFSF129010CF	22
ORFSF129012CF	22
ORFSF129012SS	34
ORFSF1612CF	22
ORFSF1612SS	34
ORFSF1616CF	22
ORFSF1616SS	34
ORFSF164512CF	22
ORFSF164516CF	22

Code	Page
ORFSF164516SS	34
ORFSF169012CF	22
ORFSF169012SS	34
ORFSF169016CF	22
ORFSF169016SS	34
ORFSF2020CF	22
ORFSF2020SS	34
ORFSF204520CF	22
ORFSF204520SS	34
ORFSF204524SS	34
ORFSF209016CF	22
ORFSF209020CF	22
ORFSF209020SS	34
ORFSF209024SS	34
ORFSF2424CF	22
ORFSF2424SS	34
ORFSF244524CF	22
ORFSF249024CF	22
ORFS-KIT01	112
ORFSM0404CF	22
ORFSM0404SS	34
ORFSM0604CF	22
ORFSM0605CF	22
ORFSM0606CF	22
ORFSM0606SS	34
ORFSM0806CF	22
ORFSM0808CF	22
ORFSM0808SS	34
ORFSM1008CF	22
ORFSM1010CF	22
ORFSM1010SS	34
ORFSM1208CF	22
ORFSM1210CF	22
ORFSM1212CF	22
ORFSM1212SS	34
ORFSM1612CF	22
ORFSM1616CF	22
ORFSM1616SS	34
ORFSM2020CF	22
ORFSM2020SS	34
ORFSM2424CF	22
ORFSM2424SS	34
ORING-BS006N	111
ORING-BS006V	111
ORING-BS007N	111
ORING-BS008N	111
ORING-BS008V	111
ORING-BS009N	111
ORING-BS009V	111
ORING-BS010N	111
ORING-BS010V	111
ORING-BS011N	111
ORING-BS011V	111
ORING-BS012N	111
ORING-BS012V	111
ORING-BS110N	111
ORING-BS110V	111
ORING-BS111N	111
ORING-BS112N	111
ORING-BS112V	111
ORING-BS113N	111
ORING-BS114N	111
ORING-BS115N	111
ORING-BS116N	111
ORING-BS116V	111
ORING-BS210N	111
ORING-BS211N	111
ORING-BS211V	111
ORING-BS212N	111
ORING-BS212V	111
ORING-BS213N	111
ORING-BS214N	111
ORING-BS215N	111
ORING-BS216N	111
ORING-BS217N	111
ORING-BS218N	111
ORING-BS218V	111
ORING-BS219N	111
ORING-BS220N	111
ORING-BS221N	111
ORING-BS221V	111
ORING-BS222N	111
ORING-BS325N	111
ORING-BS326N	111
ORING-BS327N	111
OSC-12	406
OSG	1634
O-SS	1517
OT1414	1419
OT1438	1419
OT38	1419
OT516	1419
OTR445-10NL-08	1416
OTR445-10NL-10	1416
OX-MS	1517
OX-MS-BOX	1517
OX-SS	1517
OXYBV-1	932
OXYBV-112	932
OXYBV-114	932
OXYBV-12	932
OXYBV-14	932
OXYBV-2	932
OXYBV-34	932
OXYBV-38	932
P	
P-10	178
P1000	276
P-1000	172
P100WHR	1755
P10-10-1/4	853
P10-12-1/4	853
P10-12-3/8	853
P101WHR	1755
P10-4-1/8	853
P10-5-1/8	853
P10-6-1/8	853
P10-8-1/4	853
P10-8-1/8	853
P1099	1536
P1-10-1/2	852
P1-10-1/4	852
P1-10-3/8	852
P11-10-1/2	853
P11-10-1/4	853
P11-10-3/8	853
P11-12-1/2	853
P11-12-3/8	853
P11-14-1/2	853
P11-14-3/8	853
P1-12-1/2	852
P1-12-1/4	852
P1-12-3/8	852
P1-14-1/2	852
P1-14-3/8	852
P11-5-1/8	853
P11-6-1/4	853
P11-6-1/8	853
P11-8-1/2	853
P11-8-1/4	853
P11-8-1/8	853
P11-8-3/8	853
P-12	178
P12-10-1/2	853
P12-10-1/4	853
P12-10-3/8	853
P12-12-1/2	853
P12-12-3/8	853
P12-14-1/2	853
P12-14-3/8	853
P12-4-1/8	853
P12-4-M5	853
P-125	172
P12-5-1/8	853
P12-5-M5	853
P12-6-1/4	853
P12-6-1/8	853
P12-6-M5	853
P12-8-1/2	853
P12-8-1/4	853
P12-8-1/8	853
P12-8-3/8	853
P1-4-1/4	852
P1-4-1/8	852
P14-4-14	853
P14-4-18	853
P14-6-14	853
P14-6-18	853
P14-8-14	853
P14-8-18	853
P14-8-38	853
P-15	178
P1-5-1/4	852
P1-5-1/8	852
P15-N6	760
P15-S3	760
P15-W3	760
P-16	178
P1-6-1/2	852
P1-6-1/4	852
P1-6-1/8	852
P16-10	854
P16-12	854
P16-14	854
P16-3	854
P1-6-3/8	852
P16-4	854
P16-5	854
P16-6	854
P16-8	854
P17-10-1/4	855
P17-12-3/8	855
P17-4-1/8	855
P17-4-M5	855
P17-6-1/4	855
P17-6-1/8	855
P17-6-M5	855
P17-8-1/4	855
P17-8-1/8	855
P17-8-3/8	855
P17-N6	760
P17-S3	760
P17-W3	760
P-18	178
P1-8-1/2	852
P1-8-1/4	852
P1-8-1/8	852
P1-8-3/8	852
P-187	172
P1C-4KMB	513
P1C-4KMCA	513
P1C-4KMD	513
P1C-4KME	513
P1C-4LME	513
P1C-4LMF	513
P1C-4LMT	513
P1C-4NME	513
P1C-4NMT	513
P1D-6KRN	513
P1D-6LRN	513
P1D-6MRN	513
P1D-6NRN	513
P1D-6PRN	513
P1D-6RRN	513
P1F-S032MS-0050	512
P1F-S032MS-0080	512
P1F-S032MS-0100	512
P1F-S032MS-0125	512
P1F-S032MS-0160	512
P1F-S040MS-0050	512
P1F-S040MS-0125	512
P1F-S050MS-0080	512
P1F-S050MS-0100	512
P1F-S063MS-0100	512
P1F-S063MS-0200	512
P1F-S063MS-0500	512
P1F-S080MS-0100	512
P1F-S080MS-0200	512
P1F-S100MS-0025	512
P1F-S100MS-0200	512
P1F-S125MS-0250	512
P1NZ3000	1046
P-20	178
P201WHR	1755
P20-3-M5	852
P20-4-1/8	852
P20-4-M5	852
P20-6-1/4	852
P20-6-1/8	852
P20-6-M5	852
P20-8-1/4	852
P20-8-1/8	852
P20-N6	760
P20-S3	760
P20-W3	760
P2-10-1/2	852
P2-10-1/4	852
P2-10-3/8	852
P21-10	854
P2-12-1/2	852
P2-12-1/4	852
P2-12-3/8	852
P21-3	854
P21-4	854
P2-14-1/2	852
P2-14-3/8	852
P21-5	854
P21-6	854
P21-8	854
P-22	178
P22-10-1/4	855
P22-10-3/8	855
P22-12-3/8	855
P22-4-1/8	855
P22-4-M5	855
P22-5-1/8	855
P22-5-M5	855
P22-6-1/4	855
P22-6-1/8	855
P22-6-M5	855
P22-8-1/4	855
P22-8-1/8	855
P22-8-3/8	855
P2301M	276
P23-10-1/4	855
P23-12-3/8	855
P23-4-1/8	855
P23-6-1/4	855
P23-6-1/8	855
P23-8-1/4	855
P23-8-1/8	855
P23-8-3/8	855
P2-3-M5	852
P2-4-1/4	852
P2-4-1/8	852
P24-6-1/4	855
P24-6-1/8	855
P24-8-1/4	855
P2-4-M5	852
P-25	178
P-250	172
P250WHR	1755
P2-5-1/8	852
P251WHR	1755
P2-5-M5	852
P2-6-1/2	852
P2-6-1/4	852
P2-6-1/8	852
P2-6-3/8	852
P26-6-1/4	855
P26-8-1/4	855
P2-6-M5	852
P27-8-1/4	855
P27-N6	760
P27-S3	760
P27-W3	760
P2-8-1/2	852
P2-8-1/4	852
P2-8-1/8	852
P28-10-1/4	855

Code	Page
P2-8-3/8	852
P28-4-1/8	855
P28-4-M5	855
P28-5-1/4	855
P28-5-1/8	855
P28-5-M5	855
P28-6-1/4	855
P28-6-1/8	855
P28-6-M5	855
P28-8-1/4	855
P28-8-1/8	855
P29-4-1/8	855
P29-6-1/8	855
P2E-KV32B2	597
P2E-KV32C2	597
P2FCB449	597
P2FCB453	597
P2FCB457	597
P2LAX511VS	566
P2LAX511VV	566
P2LAZ511ESNDCN	597
P2LBX61211	566
P2LBX61222	566
P2LBX81211	566
P2LBZ312ESNDCN	597
P2LBZ512EENDCN	597
P2LBZ512ESNDCN	597
P2LDX314PS	608
P2LDX514ESNXXX	608
P2LDX514VS	566
P2N-EM512MD	608
P2VM-SS-8-R	981
P2VM-SS-8-RM	981
P3	1641
P30-10-1/4	854
P30-10-3/8	854
P30-12-1/4	854
P30-12-3/8	854
P30-4-1/8	854
P30-4-M5	854
P304WHR	1755
P30-5-1/4	854
P30-5-1/8	854
P30-5-M5	854
P30-6-1/4	854
P30-6-1/8	854
P30-6-M5	854
P30-8-1/4	854
P30-8-1/8	854
P30-8-3/8	854
P3-10-1/2	852
P3-10-1/4	852
P3-10-3/8	852
P-312	172
P3-12-1/2	852
P3-12-3/8	852
P32-10-8	854
P32-12-10	854
P32-12-8	854
P32-4-3	854
P32-5-4	854
P32-6-4	854
P32-6-5	854
P32-8-6	854
P32-N6	760
P32-S3	760
P32-W3	760
P3-3-M5	852
P3-4-1/4	852
P3-4-1/8	852
P3-4-M5	852
P350	276
P350WHR	1755
P3-5-1/8	852
P3-6-1/4	852
P3-6-1/8	852
P-375	172
P3-8-1/4	852
P3-8-1/8	852
P3-8-3/8	852
P39-4-1/8	855
P39-6-1/4	855
P39-6-1/8	855
P39-8-1/4	855
P-3-FT	178
P3LCA12PESNGLNW	699
P3LEA12EPSBNNP	699
P3LFA12APPN	699
P3LFA12CPPN	699
P3LFA12EPSN	699
P3LKA00CB1	699
P3LKA00CB2	699
P3LKA00CB3	699
P3LKA00CB4	699
P3LKA00MM	699
P3LKA00MP	699
P3LKA00MR	699
P3LKA00MW	699
P3LLA12LPNN	699
P3LMA12020C	699
P3LRA12BNNP	699
P3LRX12BNNP	699
P3VM-SS-8-R	981
P-4	178
P40	1016
P40S	1016
P4-10	854
P4-12	854
P4-14	854
P421GRRM/L	1755
P421GRRS/M	1755
P43	855
P4-3	854
P431BLUM/L	1755
P431BLUS/M	1755
P4-4	854
P44-10-3/8	854
P44-12-3/8	854
P44-4-1/8	854
P44-6-1/4	854
P44-6-1/8	854
P44-8-1/4	854
P44-8-1/8	854
P4-5	854
P45-4-M5	854
P45-5-1/8	854
P45-6-1/4	854
P45-6-1/8	854
P45-6-M5	854
P45-8-1/4	854
P45-8-1/8	854
P4-6	854
P4-6-4	854
P4-8	854
P4-8-6	854
P48-N6	760
P48-S3	760
P48-W3	760
P-500	172
P500BKR	1755
P50-10-38	852
P50-4-18	852
P50-6-14	852
P50-6-18	852
P50-8-14	852
P50-8-18	852
P5-10	854
P5-12	854
P51-6-14	852
P51-6-18	852
P51-8-14	852
P51-8-38	852
P5-3	854
P5-4	854
P5-5	854
P5-6	854
P5-8	854
P6	1641
P601S	276
P60-N6	760
P60-S3	760
P60-W3	760
P6-10-1/4	852
P6-10-3/8	852
P6-12-1/4	852
P6-12-3/8	852
P-625	172
P6320/019	1416
P6320/025	1416
P6-4-1/8	852
P64F-NNC-PZN	685
P6-4-M5	852
P6-5-1/8	852
P6-6-1/4	852
P6-6-1/8	852
P6-8-1/4	852
P6-8-1/8	852
P-6-FT	178
P7-10-1/2	853
P7-10-1/4	853
P7-10-3/8	853
P7-12-1/2	853
P7-12-3/8	853
P7-14-1/2	853
P7-14-3/8	853
P7-4-1/4	853
P7-4-1/8	853
P-750	172
P7-5-1/8	853
P7-6-1/4	853
P7-6-1/8	853
P7-8-1/2	853
P7-8-1/4	853
P7-8-1/8	853
P7-8-3/8	853
P-8	178
P8-10-1/2	853
P8-10-1/4	853
P8-10-3/8	853
P8-12-1/2	853
P8-12-1/4	853
P8-12-3/8	853
P8-14-1/2	853
P8-14-3/8	853
P8-3-M5	853
P8-4-1/4	853
P8-4-1/8	853
P8-4-M5	853
P8-5-1/8	853
P8-5-M5	853
P85-S3	760
P8-6-1/4	853
P8-6-1/8	853
P8-6-3/8	853
P8-6-M5	853
P-875	172
P8-8-1/2	853
P8-8-1/4	853
P8-8-1/8	853
P8-8-3/8	853
P8C-D	597
P8S-GPFLX	513
P8S-GPMHX	513
P8S-GSFLX	513
P9-10	854
P9-12	854
P9-14	854
P9-3	854
P9-4	854
P9-5	854
P9-6	854
P9-8	854
PA00	1016
PA00S	1016
PA01WHR	1754
PA05	1016
PA05S	1016
PA10	1016
PA10C1G3R032S	1051
PA10C2G3R032S	1051
PA10S	1016
PA10S1G3R050S	1051
PA10S2G3R050S	1051
PA10SAG3R050S	1051
PA15	1016
PA1500	276
PA15C1G4R032S	1051
PA15C2G4R032S	1051
PA15S	1016
PA15S1G4R040S	1051
PA15S1G4R050A	1051
PA15S1G4R050S	1051
PA15S2G4R050S	1051
PA15SAG4R050A	1051
PA15SAG4R050S	1051
PA20	1016
PA20C1G5R032S	1051
PA20C2G5R032S	1051
PA20S	1016
PA20S1G5R050A	1051
PA20S1G5R050S	1051
PA20S2G5R050S	1051
PA20SAG5R050A	1051
PA20SAG5R050S	1051
PA25	1016
PA25S	1016
PA25S1G6R050S	1051
PA25S1G6R063S	1051
PA25S2G6R063S	1051
PA25SAG6R063A	1051
PA25SAG6R063S	1051
PA30	1016
PA30S	1016
PA32S1G7R063S	1051
PA32S2G7R063S	1051
PA32SAG7R080S	1051
PA50	1016
PA50S	1016
PA60	1016
PA60S	1016
PA70	1016
PA70S	1016
PAMFURTURT34	1490
PAV1.0606.002	296
PAV1.0606.002 V	296
PAV1.0606.003	296
PAV1.0606.003 V	296
PAV1.0606.012	296
PAV1.0606.013	296
PAV1.1010.002	296
PAV1.1010.002 V	296
PAV1.1010.003	296
PAV1.1010.003 V	296
PAV1.1010.012	296
PAV1.1010.013	296
PAV1.1313.002	296
PAV1.1313.002 V	296
PAV1.1313.003	296
PAV1.1313.003 V	296
PAV1.1313.012	296
PAV1.1313.013	296
PAV1.2019.002	296
PAV1.2019.002 V	296
PAV1.2019.003	296
PAV1.2019.003 V	296
PAV1.2019.012	296
PAV1.2019.013	296
PAV1.2525.002	296
PAV1.2525.002 V	296
PAV1.2525.003	296
PAV1.2525.003 V	296
PAV1.2525.012	296
PAV1.2525.013	296
PAV1.3031.002	296
PAV1.3031.002 V	296
PAV1.3031.003	296
PAV1.3031.003 V	296
PAV1.3031.012	296
PAV1.3031.013	296
PAV1.3939.002	296

Code	Page
PAV1.3939.002 V	296
PAV1.3939.003	296
PAV1.3939.003 V	296
PAV1.3939.012	296
PAV1.3939.013	296
PAV1.5051.002	296
PAV1.5051.002 V	296
PAV1.5051.003	296
PAV1.5051.003 V	296
PAV1.5051.012	296
PAV1.5051.013	296
PAVX.0606.002	297
PAVX.0606.003	297
PAVX.1010.002	297
PAVX.1010.003	297
PAVX.1313.002	297
PAVX.1313.003	297
PAVX.2019.002	297
PAVX.2019.003	297
PAVX.2525.002	297
PAVX.2525.003	297
PAVX.3031.002	297
PAVX.3031.003	297
PAVX.3939.002	297
PAVX.3939.003	297
PAVX.5051.002	297
PAVX.5051.003	297
PAW	1016
PAWS-F04	1016
PB1/2-02	777
PB1/4-01	777
PB1/4-02	777
PB1/4-N02	777
PB1/8-N01	777
PB3/8-02	777
PBBLH-3/8	1594
PBCCURT3	1489
PBCCURT4	1489
PBCWOC112	1489
PBCWOC2	1489
PBCWOC212	1489
PBCWOCBSP3	1489
PBCWOCBSP4	1489
PBCWOCURT3	1489
PBCWOCURT4	1489
PBFA13	944
PBFA16	944
PBFA19	944
PBFA20	944
PBFG13	944
PBFG16	944
PBFG19	944
PBFG20	944
PBP02SNP	1176
PBP06SNP	1176
PBP08SNP	1176
PBPWOC112	1489
PBPWOC2	1489
PBPWOC212	1489
PBPWOCBSP3	1489
PBPWOCURT3	1489
PBPWOCURT4	1489
PBR205	1749
PBT-02	89
PBT02SNP	1176
PBT-04	89
PBT04SNP	1176
PBT-06	89
PBT06SNP	1176
PBT-08	89
PBV1.0404.002	300
PBV1.0404.003	300
PBV1.0606.002	300
PBV1.0606.003	300
PBV1.1010.002	300
PBV1.1010.003	300
PBV1.1313.002	300
PBV1.1313.003	300
PBV1.2019.002	300
PBV1.2019.003	300
PBV1.2525.002	300
PBV1.2525.003	300
PBV1.3931.002	300
PBV1.3931.003	300
PBV1.3939.002	300
PBV1.3939.003	300
PBV1.5051.002	300
PBV1.5051.003	300
PBV-2-S-02-FF	956
PBV-2-S-04-FF	956
PBV-2-S-06-FF	956
PBV-2-S-08-FF	956
PBV-2-S-12-FF	956
PBV-2-S-16-FF	956
PBVM.0404.002	300
PBVM.0404.003	300
PBVM.0606.002	300
PBVM.0606.003	300
PBVM.1010.002	300
PBVM.1010.003	300
PBVM.1313.002	300
PBVM.1313.003	300
PBVM.2019.002	300
PBVM.2019.003	300
PBVM.2525.002	300
PBVM.2525.003	300
PBVM.3931.002	300
PBVM.3931.003	300
PBVM.3939.002	300
PBVM.3939.003	300
PBVM.5051.002	300
PBVM.5051.003	300
PBVX.0404.002	297
PBVX.0404.003	297
PBVX.0606.002	297
PBVX.0606.003	297
PBVX.1010.002	297
PBVX.1010.003	297
PBVX.1313.002	297
PBVX.1313.003	297
PBVX.2019.002	297
PBVX.2019.003	297
PBVX.2525.002	297
PBVX.2525.003	297
PBVX.3931.002	297
PBVX.3931.003	297
PBVX.3939.002	297
PBVX.3939.003	297
PBVX.5051.002	297
PBVX.5051.003	297
PC03-M3C	788
PC03-M5C	788
PC03-M6C	788
PC04-01C	788
PC04-G01C	788
PC04-M3C	788
PC04-M5C	788
PC04-M6C	788
PC06-01C	788
PC06-G01C	788
PC06-M5C	788
PC06-M6C	788
PC1/2-03	777
PC1/2-04	777
PC1/4-01	777
PC1/4-02	777
PC1/4-N00C	790
PC1/4-N01C	790
PC1/4-U10C	790
PC1/8-N00C	790
PC1/8-N01C	790
PC1/8-U10C	790
PC-10	177
PC-1000	171
PC10-12	1536
PC11-13	1536
PC-125	171
PC-12-FT	177
PC13-15	1536
PC14-16	1536
PC15-17	1536
PC15E	1092
PC-15-FT	177
PC15W	884
PC-16	177
PC16-18	1536
PC17-19	1536
PC18-20	1536
PC-18-FT	177
PC-20	177
PC21-23	1536
PC22E	1092
PC22W	884
PC23-25	1536
PC-25	177
PC-250	171
PC26-28	1536
PC28E	1092
PC28W	884
PC-3	177
PC3/8-01	777
PC3/8-02	777
PC3/8-04	777
PC30-32	1536
PC-312	171
PC-375	171
PC5/32-N00C	790
PC5/32-N01C	790
PC5/32-U10C	790
PC-500	171
PC-6	177
PC-750	171
PC-8	177
PC8-10	1536
PCF03-M3C	788
PCF03-M5C	788
PCF03-M6C	788
PCF04-01C	788
PCF04-G01C	788
PCF04-M3C	788
PCF04-M5C	788
PCF04-M6C	788
PCF06-01C	788
PCF06-G01C	788
PCF06-M5C	788
PCF06-M6C	788
PCF1/2-03	777
PCF1/2-04	777
PCF1/4-01	777
PCF1/4-02	777
PCF1/4-N00C	790
PCF1/4-N01C	790
PCF1/4-U10C	790
PCF1/8-N01C	790
PCF1/8-U10C	790
PCF3/8-02	777
PCF3/8-04	777
PCF5/32-N00C	790
PCF5/32-N01C	790
PCF5/32-U10C	790
PCFF01-01	792
PCFF02-02	792
PCFF03-03	792
PCFF04-04	792
PCJ5.0606.002	305
PCJ5.0606.003	305
PCJ5.0606.012	305
PCJ5.0606.013	305
PCJ5.0610.002	305
PCJ5.0610.003	305
PCJ5.0610.012	305
PCJ5.0610.013	305
PCJ6.0606.002	305
PCJ6.0606.003	305
PCJ6.0606.012	305
PCJ6.0606.013	305
PCLAMPS-101-1	1393
PCLAMPS-101-2	1393
PCLAMPS-101-3	1393
PCLAMPS-101-4	1393
PCLAMPS-101-4/3	1393
PCLAMPS-101-5	1393
PCLAMPS-101-5/4	1393
PCLAMPS-104-1	1393
PCLAMPS-104-2	1393
PCLAMPS-104-3	1393
PCLAMPS-104-4	1393
PCLAMPS-104-5	1393
PCLAMPS-116-1	1393
PCLAMPS-116-2	1393
PCLAMPS-116-3	1393
PCLAMPS-116-4	1393
PCLAMPS-116-5	1393
PCLAMPS-119-1	1393
PCLAMPS-119-2	1393
PCLAMPS-119-3	1393
PCLAMPS-119-4	1393
PCLAMPS-119-5	1393
PCLAMPS-125-1	1393
PCLAMPS-125-2	1393
PCLAMPS-125-3	1393
PCLAMPS-125-4	1393
PCLAMPS-125-5	1393
PCLAMPS-125H-3	1393
PCLAMPS-125H-4	1393
PCLAMPS-128-1	1393
PCLAMPS-128-2	1393
PCLAMPS-128-3	1393
PCLAMPS-128-4	1393
PCLAMPS-129-2	1393
PCLAMPS-129-3	1393
PCLAMPS-129-4	1393
PCLAMPS-130-2	1393
PCLAMPS-130-3	1393
PCLAMPS-131-1	1394
PCLAMPS-131-2	1394
PCLAMPS-131-3	1394
PCLAMPS-131-4	1394
PCLAMPS-131-5	1394
PCLAMPS-132-1	1394
PCLAMPS-132-2	1394
PCLAMPS-132-3	1394
PCLAMPS-132-4	1394
PCLAMPS-132-5	1394
PCLAMPS-133-1	1394
PCLAMPS-133-2	1394
PCLAMPS-133-3	1394
PCLAMPS-133-4	1394
PCLAMPS-133-5	1394
PCLAMPS-134-2	1394
PCLAMPS-134-3	1394
PCLAMPS-134-4	1394
PCLAMPS-135-2	1394
PCLAMPS-135-3	1394
PCLAMPS-135-4	1394
PCLAMPS-138-1	1394
PCLAMPS-138-2	1394
PCLAMPS-138-3	1394
PCLAMPS-138-4	1394
PCLAMPS-140-1	1394
PCLAMPS-140-2	1394
PCLAMPS-140-3	1394
PCLAMPS-143-1	1394
PCLAMPS-143-2	1394
PCLAMPS-143-3	1394
PCLAMPS-143-4	1394
PCLAMPS-144-2	1394
PCLAMPS-144-3	1394
PCLAMPS-144-4	1394
PCLAMPS-145-2	1394
PCLAMPS-145-3	1394
PCLAMPS-145-4	1394
PCLAMPS-146-2	1394
PCLAMPS-146-3	1394
PCLAMPS-146-4	1394
PCLAMPS-147-2	1394
PCLAMPS-147-3	1394
PCLAMPS-147-4	1394
PCLAMPS-148-1	1395
PCLAMPS-148-2	1395

Code	Page
PCLAMPS-148-3	1395
PCLAMPS-148-4	1395
PCLAMPS-149-1	1395
PCLAMPS-149-2	1395
PCLAMPS-149-3	1395
PCLAMPS-149-4	1395
PCLAMPS-149-5	1395
PCLAMPS-150-2	1395
PCLAMPS-150-3	1395
PCLAMPS-150-4	1395
PCLAMPS-158-2	1395
PCLAMPS-158-3	1395
PCLAMPS-158-4	1395
PCLAMPS-160-2	1395
PCLAMPS-160-3	1395
PCLAMPS-160-4	1395
PCLAMPS-160-5	1395
PCLAMPS-161-1	1395
PCLAMPS-161-2	1395
PCLAMPS-161-3	1395
PCLAMPS-161-3/2	1395
PCLAMPS-161-4	1395
PCLAMPS-161-4/2	1395
PCLAMPS-165-1	1395
PCLAMPS-165-3	1395
PCLAMPS-165-5	1395
PCLAMPS-167-1	1396
PCLAMPS-167-2	1396
PCLAMPS-167-3	1396
PCLAMPS-167-4	1396
PCLAMPS-167-5	1396
PCLAMPS-167M-3	1396
PCLAMPS-167M-4	1396
PCLAMPS-168-2	1396
PCLAMPS-168-3	1396
PCLAMPS-168-4	1396
PCLAMPS-168M-4	1396
PCLAMPS-169-1	1396
PCLAMPS-169-2	1396
PCLAMPS-169-3	1396
PCLAMPS-169-4	1396
PCLAMPS-169M	1396
PCLAMPS-170-1	1396
PCLAMPS-170-2	1396
PCLAMPS-170-3	1396
PCLAMPS-170-4	1396
PCLAMPS-170-5	1396
PCLAMPS-171-1	1396
PCLAMPS-171-2	1396
PCLAMPS-171-3	1396
PCLAMPS-171-4	1396
PCLAMPS-171-5	1396
PCLAMPS-173-2	1396
PCLAMPS-173-3	1396
PCLAMPS-173-4	1396
PCLAMPS-173F-1	1396
PCLAMPS-173F-2	1396
PCLAMPS-173F-3	1396
PCLAMPS-173F-5	1396
PCLAMPS-173M-2	1397
PCLAMPS-173M-3	1397
PCLAMPS-173M-4	1397
PCLAMPS-173M-5	1397
PCLAMPS-176-2	1397
PCLAMPS-176-3	1397
PCLAMPS-176-4	1397
PCLAMPS-176-5	1397
PCLAMPS-179-1	1397
PCLAMPS-179-2	1397
PCLAMPS-179-3	1397
PCLAMPS-179-4	1397
PCLAMPS-182-2	1397
PCLAMPS-182-3	1397
PCLAMPS-182-4	1397
PCLAMPS-184-2	1397
PCLAMPS-184-4	1397
PCLAMPS-198-2	1397
PCLAMPS-198-3	1397
PCLAMPS-198-4	1397
PCLAMPS-199-3	1397
PCLAMPS-199-4	1397
PCLAMPS-201-2	1397
PCLAMPS-201-4	1397
PCLAMPS-204-2	1397
PCLAMPS-204-4	1397
PCLAMPS-219-2	1397
PCLAMPS-219-4	1397
PCLAMPS-224-2	1397
PCLAMPS-224-3	1397
PCLAMPS-224-4	1397
PCLAMPS-225-2	1397
PCLAMPS-225-4	1397
PCLAMPS-233	1398
PCLAMPS-235-1-2	1398
PCLAMPS-2353-4-5	1398
PCLAMPS-GS3-1-2	1398
PCLAMPS-GS3-4-5	1398
PCLAMP-TUBE1-325	1395
PCLAMP-TUBE1-6.5	1395
PCLAMP-TUBE2-325	1395
PCLAMP-TUBE2-6.5	1395
PCLAMP-TUBE3-325	1395
PCLAMP-TUBE3-6.5	1395
PCLAMP-TUBE4-325	1395
PCLAMP-TUBE4-6.5	1395
PCLAMP-TUBE5-325	1395
PCLAMP-TUBE5-6.5	1395
PCLIP-KIT-MS	1543
PCLIP-KIT-SS	1543
PCP-02	89
PCP-04	89
PCP-06	89
PCP-08	89
PCP-12	89
PCP-16	89
PCSE	1092
PCSRAB1	1543
PCSW	884
PCT112	1487
PCT2	1487
PCT212	1487
PCT3BSP	1487
PCT3URT	1488
PCT4BSP	1487
PCT4URT	1488
PCU15	1134
PCU22	1134
PCU28	1134
PCU35	1134
PCU42	1134
PCU54	1134
PCU67	1134
PCV-02-SS-FF	963
PCV-04-SS-FF	963
PCV-06-SS-FF	963
PCV-08-SS-FF	963
PCV-12-SS-FF	963
PCV-16-SS-FF	963
PCVC04-01	792
PCVC04-02	792
PCVC06-01	792
PCVC06-02	792
PCVC08-01	792
PCVC08-02	792
PCVC10-02	792
PCVC10-03	792
PCVC12-02	792
PCVC12-03	792
PCVF01-01	792
PCVF02-02	792
PCVF03-03	792
PCVF04-04	792
PCVU04	792
PCVU06	792
PCVU08	792
PCVU10	792
PCZRAB1	1543
PDCP-4	318
PDCP-6	318
PE-000.715	1095
PE-04025-0100M-B	918
PE-04025-0100M-E	918
PE-04025-0100M-N	918
PE-0604-0100M-B	918
PE-0604-0100M-E	918
PE-0604-0100M-N	918
PE-0604-0100M-R	918
PE-0806-100M-B	918
PE-0806-100M-E	918
PE-0806-100M-N	918
PE1/2	777
PE1/4	777
PE1/8	777
PE-1007-100M-B	918
PE-1007-100M-E	918
PE-1007-100M-N	918
PE-1007-100M-R	918
PE-1209-100M-B	918
PE-1209-100M-E	918
PE-1209-100M-R	918
PE-140020CX	1096
PE-140025CX	1096
PE-140025U	1096
PE-140031U	1096
PE-140032CX	1096
PE-140040CX	1096
PE-140040U	1096
PE-140050CX	1096
PE-140063CX	1096
PE-141020C	1096
PE-141024CU	1096
PE-141025C	1096
PE-141030UM	1096
PE-141031CU	1096
PE-141031UM	1096
PE-141032C	1096
PE-141032UM	1096
PE-141040C	1096
PE-141040CU	1096
PE-141041UM	1096
PE-141050C	1096
PE-141063C	1096
PE-142020C	1096
PE-142024UM	1096
PE-142025C	1096
PE-142025UM	1096
PE-142030UM	1096
PE-142031UM	1096
PE-142032C	1096
PE-142032UM	1096
PE-142040C	1096
PE-142040UM	1096
PE-142041UM	1096
PE-142050C	1096
PE-142063C	1096
PE3/8	777
PE-701.016	1093
PE-701.020	1093
PE-701.025	1093
PE-701.032	1093
PE-701.040	1093
PE-701.050	1093
PE-701.063	1093
PE-701.075	1093
PE-701.110	1093
PE-702.020	1093
PE-702.025	1093
PE-702.031	1093
PE-702.032	1093
PE-702.040	1093
PE-702.049	1093
PE-702.063	1093
PE-703.016	1093
PE-703.020	1093
PE-703.022	1093
PE-703.024	1093
PE-703.025	1093
PE-703.027	1093
PE-703.031	1093
PE-703.032	1093
PE-703.039	1093
PE-703.040	1093
PE-703.050	1093
PE-703.063	1093
PE-703.075	1093
PE-703.090	1093
PE-703.110	1093
PE-704.016	1093
PE-704.020	1093
PE-704.021	1093
PE-704.024	1093
PE-704.025	1093
PE-704.026	1093
PE-704.031	1093
PE-704.032	1093
PE-704.033	1093
PE-704.039	1093
PE-704.040	1093
PE-704.041	1093
PE-704.049	1093
PE-704.050	1093
PE-704.051	1093
PE-704.063	1093
PE-704.074	1093
PE-704.075	1093
PE-704.090	1093
PE-705.020	1093
PE-705.025	1093
PE-705.032	1093
PE-705.050	1093
PE-705.063	1093
PE-706.016	1093
PE-706.020	1093
PE-706.025	1093
PE-706.032	1093
PE-706.040	1093
PE-706.050	1093
PE-706.063	1093
PE-706.090	1093
PE-707.020	1093
PE-707.024	1093
PE-707.025	1093
PE-707.031	1093
PE-707.032	1093
PE-707.050	1093
PE-707.063	1093
PE-708.020	1093
PE-708.024	1093
PE-708.025	1093
PE-708.031	1093
PE-708.032	1093
PE-708.050	1093
PE-708.063	1093
PE-709.020	1094
PE-709.025	1094
PE-709.032	1094
PE-709.040	1094
PE-709.050	1094
PE-709.063	1094
PE-709.075	1094
PE-710.020	1094
PE-710.024	1094
PE-710.025	1094
PE-710.031	1094
PE-710.032	1094
PE-710.040	1094
PE-710.050	1094
PE-710.090	1094
PE-711.020	1094
PE-711.025	1094
PE-711.032	1094
PE-711.050	1094
PE-711.063	1094
PE-712.020	1094
PE-712.025	1094
PE-713.025	1094
PE-713.032	1094
PE-713.063	1094
PE-714.050	1094
PE-714.063	1094

Code	Page
PE-714.075	1094
PE-714.090	1094
PE-715.020	1095
PE-715.025	1095
PE-715.032	1095
PE-716016	1095
PE-716020	1095
PE-716025	1095
PE-716032	1095
PE-716040	1095
PE-717020	1095
PE-717025	1095
PE-717032	1095
PE-717040	1095
PE-717050	1095
PE-718025	1095
PE-718032	1095
PE-718040	1095
PE-718050	1095
PE-718063	1095
PE-719032	1095
PE-719040	1095
PE-719050	1095
PE-719063	1095
PE-720020	1095
PE-720021	1095
PE-720022	1095
PE-720026	1095
PE-720032	1095
PE-720033	1095
PE-720041	1095
PE-721020	1095
PE-721021	1095
PE-721022	1095
PE-721025	1095
PE-721026	1095
PE-721027	1095
PE-721032	1095
PE-721033	1095
PE-721034	1095
PE-721040	1095
PE-721041	1095
PE-721042	1095
PE-722020	1095
PE-722025	1095
PE-722032	1095
PE-722040	1095
PE-723020	1095
PE-723021	1095
PE-723025	1095
PE-723026	1095
PE-723033	1095
PE-723121	1095
PE-723132	1095
PE-723221	1095
PE-723226	1095
PE-723232	1095
PE-723233	1095
PE-724001	1096
PE-724002	1096
PE-724003	1096
PE-724004	1096
PE-724005	1096
PE-724006	1096
PE-724007	1096
PE-724008	1096
PE-724010	1096
PE-724011	1096
PE-724012	1096
PE-724013	1096
PE-724014	1096
PE-724016	1096
PE-724120	1096
PE-724121	1096
PE-724125	1096
PE-724126	1096
PE-724132	1096
PE-724133	1096
PE-724221	1096
PE-724226	1096
PE-724233	1096
PE-725020	1094
PE-725025	1094
PE-725032	1094
PE-725050	1094
PE-725075	1094
PE-776001	1094
PE-776002	1094
PE-776003	1094
PE-776004	1094
PE-780020	1094
PE-780025	1094
PE-780032	1094
PEM0210W	880
PEM0228W	880
PEM0310W	880
PEM03228W	880
PEM0410W	880
PEM0428W	880
PEM061510W	881
PEM062215W	881
PEM062815W	881
PEM062822W	881
PEM221010W	880
PEM3015AW	880
PEM3015BW	880
PEM302210AW	880
PEM3022BW	880
PEM3028AW	880
PEM3028DW	880
PEM3201W	880
PEM3202W	880
PEM3203W	880
PEM3210W	880
PEM532210W	883
PEM532215W	883
PEM571515W	883
PEM572222W	883
PEMBTC1514	883
PE-MDPE20BLK	1094
PE-MDPE20BLU	1094
PE-MDPE25BLK	1094
PE-MDPE25BLU	1094
PE-MDPE32BLK	1094
PE-MDPE32BLU	1094
PE-MDPE63BLK	1094
PE-MDPE63BLU	1094
PEN1-1	1177
PEN112-112	1177
PEN114-114	1177
PEN12-12	1177
PEN2-2	1177
PEN3-3	1177
PEN34-34	1177
PES1-1	1177
PES112-112	1177
PES114-114	1177
PES12-12	1177
PES2-2	1177
PES3-3	1177
PES34-34	1177
PF0406-14	902
PF0406-14-NG	902
PF0508-14	902
PF0508-14-NG	902
PF0610-14	902
PF0610-14-NG	902
PF0812-14	902
PF0812-14-NG	902
PF0812-38	902
PF0812-38-NG	902
PFFN-1/4	1611
PFS-1315L	1457
PFS-1315M	1457
PFS-1320L	1457
PFS-1320M	1457
PFS-615H	1457
PFS-915H	1457
PFS-915L	1457
PFS-915M	1457
PFS-920L	1457
PFS-920M	1457
PFT-02	89
PFT-04	89
PFT-06	89
PFT-08	89
PFT1.1310.002	306
PFT1.1313.002	306
PFT1.1318.102	306
PFT-12	89
PFT-16	89
PFT3.1313.213	306
PFT3.1318.503	306
PFT3.1322.503	306
PG001-VB-1/4	695
PG001-VB-1/8	695
PG010-PB-1/4	695
PG010-PB-1/8	695
PG1/2-3/8	777
PG205CTW00	1052
PG205STW00	1052
PG206CTX00	1052
PG206STX00	1052
PG207STY00	1052
PG208STZ00	1052
PG209STK00	1052
PG210STJ00	1052
PG63-001BG	264
PG63-001RG	264
PG63-002BG	264
PG63-002RG	264
PG63-004BG	264
PG63-004RG	264
PG63-006BG	264
PG63-006RG	264
PG63-012BG	264
PG63-012RG	264
PG63-014BG	264
PG63-020BG	264
PG63-020RG	264
PG63-025BG	264
PG63-025RG	264
PG63-040BG	264
PG63-040RG	264
PG63-060BG	264
PG63-060RG	264
PG63-120BG	264
PG63-120RG	264
PG63-200BG	264
PG63-200RG	264
PG63-250BG	264
PG63-250RG	264
PG63-400BG	264
PG63-400RG	264
PG63-600BG	264
PG63-600RG	264
PGA-04-04	88
PGA-06-06	88
PGA-08-08	88
PGB050114	411
PGB050118	411
PGB050314	411
PGB050318	411
PGB050414	411
PGB050418	411
PGB050614	411
PGB050618	411
PGB051014	411
PGB051018	411
PGB051214	411
PGB051414	411
PGB051418	411
PGB052014	411
PGB052018	411
PGB060114	411
PGB060314	411
PGB060414	411
PGB061014	411
PGB061214	411
PGB062014	411
PGB100138	411
PGB100338	411
PGB100438	411
PGB100638	411
PGB101038	411
PGB101238	411
PGB102038	411
PGBP040418	411
PGBP040618	411
PGBP041018	411
PGBP041218	411
PGBP060414	411
PGBP060614	411
PGBP061014	411
PGBP061214	411
PGBU040418	411
PGBU061014	411
PGR050114	410
PGR050314	410
PGR050414	410
PGR050614	410
PGR051014	410
PGR051214	410
PGR052014	410
PGR060114	410
PGR061014	410
PGR061214	410
PGR062014	410
PH12.1	1625
PH12.3/4	1625
PH20.1	1625
PH20.3/4	1625
PHC-02	88
PHC-04	88
PHC-06	88
PHC-08	88
PHC-12	88
PHC12-12RP	318
PHC-16	88
PHC16-16RP	318
PHC20-20RP	318
PHC4-4RP	318
PHC6-6RP	318
PHC8-8RP	318
PHN-01	88
PHN-02	88
PHN-04	88
PHN-06	88
PHN-08	88
PHN-12	88
PHN12-12RP	318
PHN-16	88
PHN16-16RP	318
PHN4-4RP	318
PHN6-6RP	318
PHN8-8RP	318
PHNL-02-L1.5	88
PHNL-02-L2	88
PHNL-02-L3	88
PHNL-02-L4	88
PHNL-02-L6	88
PHNL-04-L1.5	88
PHNL-04-L2	88
PHNL-04-L3	88
PHNL-04-L4	88
PHNL-04-L6	88
PHNL-06-L1.5	88
PHNL-06-L2	88
PHNL-06-L3	88
PHNL-06-L4	88
PHNL-06-L6	88
PHNL-08-L1.5	88
PHNL-08-L2	88
PHNL-08-L3	88
PHNL-08-L4	88
PHNL-08-L6	88
PHNL-12-L2	88
PHNL-12-L3	88
PHNL-12-L4	88
PHNL-12-L6	88

Code	Page
PHNL-16-L1.5	88
PHNL-16-L2	88
PHNL-16-L3	88
PHNL-16-L4	88
PHNL-16-L6	88
PI00	1016
PI00S	1016
PI010601S	840
PI010621S	840
PI010801S	840
PI010802S	840
PI010812S	840
PI010821S	840
PI010822S	840
PI010823S	840
PI011202S	840
PI011203S	840
PI011212S	840
PI011221S	840
PI011222S	840
PI011223S	840
PI011224S	840
PI011603S	840
PI011604S	840
PI011623S	840
PI011624S	840
PI012026S	840
PI0206S	840
PI0208S	840
PI0212S	840
PI0216S	840
PI0306S	841
PI0308S	841
PI0312S	841
PI0316S	841
PI0406S	840
PI0408S	840
PI0412S	840
PI0416S	840
PI050621S	840
PI050801S	840
PI050802S	840
PI050821S	840
PI050822S	840
PI050823S	840
PI051202S	840
PI051203S	840
PI051212S	840
PI051213S	840
PI051222S	840
PI051223S	840
PI051603S	840
PI051604S	840
PI051623S	840
PI051624S	840
PI060605S	841
PI061006S	841
PI061008S	841
PI061206S	841
PI061208S	841
PI061210S	841
PI061610S	841
PI061612S	841
PI0806S	841
PI0808S	841
PI0812S	841
PI0816S	841
PI090621S	841
PI090801S	841
PI090802S	841
PI090822S	841
PI091202S	841
PI091203S	841
PI091603S	841
PI091604S	841
PI091623S	841
PI091624S	841
PI10	1016
PI100802S	840
PI10S	1016
PI1206S	840
PI1208S	840
PI121208S	840
PI1212S	840
PI1216S	840
PI131012S	842
PI131216S	842
PI1908S	842
PI1916S	842
PI20	1016
PI200806S	842
PI201006S	842
PI201008S	842
PI201206S	842
PI201208S	842
PI201210S	842
PI201610S	842
PI201612S	842
PI20S	1016
PI211006S	841
PI211008S	841
PI211206S	841
PI211208S	841
PI211210S	841
PI211610S	841
PI211612S	841
PI220606S	841
PI220808S	841
PI221206S	841
PI221208S	841
PI221210S	841
PI221212S	841
PI221616S	841
PI2308S	842
PI2312S	842
PI2316S	842
PI241210S	842
PI250806S	842
PI250808S	842
PI250810S	842
PI251006S	842
PI251008S	842
PI251012S	842
PI251208S	842
PI251210S	842
PI251212S	842
PI251216S	842
PI251612S	842
PI251616S	842
PI290808S	842
PI290810S	842
PI291008S	842
PI291208S	842
PI291210S	842
PI30	1016
PI301208S	840
PI301612S	840
PI30S	1016
PI40	1016
PI40S	1016
PI450822S	841
PI451014FS	841
PI451213S	841
PI451214FS	841
PI451222S	841
PI451613S	841
PI4608S	842
PI4612S	842
PI4712S	842
PI480821S	841
PI480822S	841
PI480823S	841
PI481022S	841
PI481023S	841
PI481222S	841
PI481223S	841
PI482024S	841
PI491612S	842
PIC1808R	842
PIC1812R	842
PINCH-AP6252	627
PINCH-AP6304	627
PINCH-AP6372	627
PINS	1474
PISV0412S	884
PISV0416S	884
PIUB16S	842
PKM0215W	880
PKM0222W	880
PKM0315W	880
PKM0322W	880
PKM0415W	880
PKM0422W	880
PKM201510W	880
PKM202215W	880
PKM221515W	880
PKM222222W	880
PKM3022AW	880
PKM3022CW	880
PKM3022DW	880
PKM4615W	880
PKM4622W	880
PKMSTC1514	881
PKMSTC1516	881
PKMSTC2216	881
PL03-M3C	788
PL03-M5C	788
PL03-M6C	788
PL04-01C	788
PL04-G01C	788
PL04-M3C	788
PL04-M5C	788
PL04-M6C	788
PL06-01C	788
PL06-G01C	788
PL06-M5C	788
PL06-M6C	788
PL1/2-03	777
PL1/2-04	777
PL1/4-01	777
PL1/4-02	777
PL1/4-N00C	790
PL1/4-N01C	790
PL1/4-U10C	790
PL1/8-N00C	790
PL1/8-N01C	790
PL1/8-U10C	790
PL3/8-01	777
PL3/8-02	777
PL5/32-N00C	790
PL5/32-N01C	790
PL5/32-U10C	790
PLK4.0606.113	301
PLK4.1310.113	301
PLK4.1313.113	301
PLK4.2013.113	301
PLK4.2019.113	301
PLK4.2519.113	301
PLK4.2525.113	301
PLK4.3025.113	301
PLK4.3031.113	301
PLK4.3939.113	301
PLK4.5051.113	301
PLL03-M3C	788
PLL03-M5C	788
PLL03-M6C	788
PLL04-01C	788
PLL04-M3C	788
PLL04-M5C	788
PLL04-M6C	788
PLL06-01C	788
PLL06-G01C	788
PLL06-M5C	788
PLL06-M6C	788
PLL1/4-N00C	790
PLL1/4-N01C	790
PLL1/4-U10C	790
PLL1/8-N00C	790
PLL1/8-N01C	790
PLL1/8-U10C	790
PLL5/32-N00C	790
PLL5/32-N01C	790
PLL5/32-U10C	790
PLM04C	789
PLM06C	789
PLM1/4C	791
PLM1/8C	791
PLM5/32C	791
PLS1.0606.112	299
PLS1.0606.113	299
PLS1.1010.112	299
PLS1.1010.113	299
PLS1.1013.112	299
PLS1.1013.113	299
PLS1.1313.112	299
PLS1.1313.113	299
PLS1.2019.112	299
PLS1.2019.113	299
PLS1.2525.112	299
PLS1.2525.113	299
PLS1.2531.112	299
PLS1.2531.113	299
PLSX.0606.112	299
PLSX.0606.113	299
PLSX.1010.112	299
PLSX.1010.113	299
PLSX.1013.112	299
PLSX.1013.113	299
PLSX.1313.112	299
PLSX.1313.113	299
PLSX.2019.112	299
PLSX.2019.113	299
PLSX.2525.112	299
PLSX.2525.113	299
PLSX.2531.112	299
PLSX.2531.113	299
PLT.006.802	302
PLT.006.803	303
PLT.006.812	302
PLT.006.813	303
PLT.006.822	302
PLT.006.832	302
PLT.006.833	303
PLT.006.852	302
PLT.006.853	303
PLT.006.862	302
PLT.006.863	303
PLT.006.873	303
PLT.006.882	302
PLT.006.883	303
PLT.006.892	302
PLT.006.893	303
PLT.013.802	302
PLT.013.812	302
PLT.013.822	302
PLT.013.832	302
PLT.013.852	302
PLT.013.862	302
PLT.013.872	302
PLT.013.882	302
PLT.013.892	302
PLT.019.802	302
PLT.019.803	303
PLT.019.812	302
PLT.019.813	303
PLT.019.822	302
PLT.019.823	303
PLT.019.832	302
PLT.019.833	303
PLT.019.852	302
PLT.019.853	303
PLT.019.862	302
PLT.019.863	303
PLT.019.872	302
PLT.019.873	303
PLT.019.882	302
PLT.019.883	303
PLT.019.892	302
PLT.019.893	303
PLT.025.802	302

Code	Page
PLT.025.803	303
PLT.025.812	302
PLT.025.813	303
PLT.025.822	302
PLT.025.823	303
PLT.025.832	302
PLT.025.833	303
PLT.025.842	302
PLT.025.843	303
PLT.025.872	302
PLT.025.873	303
PLT.030.802	302
PLT.030.803	303
PLT.030.812	302
PLT.030.813	303
PLT.030.822	302
PLT.030.823	303
PLT.030.832	302
PLT.030.833	303
PLT.030.843	303
PLT.030.872	302
PLT.030.873	303
PLT.613.803	303
PLT.613.813	303
PLT.613.823	303
PLT.613.833	303
PLT.613.843	303
PLT.613.853	303
PLT.613.873	303
PLT.613.893	303
PLT1.0606.002	301
PLT1.0606.003	301
PLT1.1310.002	301
PLT1.1310.003	301
PLT1.1313.002	301
PLT1.1313.003	301
PLT1.2013.002	301
PLT1.2013.003	301
PLT1.2019.002	301
PLT1.2019.003	301
PLT1.2519.002	301
PLT1.2519.003	301
PLT1.2525.002	301
PLT1.2525.003	301
PLT1.3031.002	301
PLT1.3031.003	301
PLT1.3939.002	301
PLT1.3939.003	301
PLT1.5051.112	301
PLT4.0606.112	301
PLT4.0606.113	301
PLT4.1310.112	301
PLT4.1310.113	301
PLT4.1313.112	301
PLT4.1313.113	301
PLT4.1319.032	301
PLT4.1319.033	301
PLT4.2013.112	301
PLT4.2013.113	301
PLT4.2019.112	301
PLT4.2019.113	301
PLT4.2027.032	301
PLT4.2027.033	301
PLT4.2519.112	301
PLT4.2519.113	301
PLT4.2525.112	301
PLT4.2525.113	301
PLT4.3025.112	301
PLT4.3025.113	301
PLT4.3031.112	301
PLT4.3031.113	301
PLTX.0606.112	299
PLTX.0606.113	299
PLTX.1310.112	299
PLTX.1310.113	299
PLTX.1313.112	299
PLTX.1313.113	299
PLTX.2013.112	299
PLTX.2013.113	299
PLTX.2019.112	299
PLTX.2019.113	299
PLTX.2519.112	299
PLTX.2519.113	299
PLTX.2525.112	299
PLTX.2525.113	299
PLTX.3031.112	299
PLTX.3031.113	299
PLTX.3939.112	299
PLTX.3939.113	299
PLTX.5051.112	299
PLTX.5051.113	299
PLUGTITE-MAX-4	51
PLUGTITE-MINI-20	51
PLUGTITE-MIX-9	51
PLUGTITE-STD-10	51
PM010401E	836
PM010401S	840
PM010402E	836
PM010402S	840
PM010411E	836
PM010412E	836
PM010421S	840
PM010422S	840
PM010501E	836
PM010502E	836
PM010511E	836
PM010512E	836
PM010601E	836
PM010602E	836
PM010611E	836
PM010612E	836
PM010801E	836
PM010801S	840
PM010802E	836
PM010802S	840
PM010803E	836
PM010803S	840
PM010811E	836
PM010812E	836
PM010813E	836
PM010821S	840
PM010822S	840
PM010823S	840
PM011002E	836
PM011003E	836
PM011004E	836
PM011012E	836
PM011013E	836
PM011014E	836
PM011203E	836
PM011204E	836
PM011213E	836
PM011214E	1090
PM011514E	836
PM011516E	1090
PM011814E	1090
PM012216E	1090
PM0204E	836
PM0204S	840
PM0205E	836
PM0206E	836
PM0208E	836
PM0208S	840
PM0210E	836
PM0212E	836
PM0215E	836
PM0218E	1090
PM0222E	1090
PM03018AE	1090
PM0304E	836
PM0304S	841
PM0305E	836
PM0306E	836
PM0308E	836
PM0308S	841
PM0310E	836
PM0312E	836
PM0315E	836
PM0318E	1090
PM0322E	1090
PM0328E	1090
PM0404E	837
PM0404S	840
PM0405E	837
PM0406E	837
PM0408E	837
PM0408S	840
PM0410E	837
PM0412E	1091
PM0415E	1091
PM0418E	1091
PM0422E	1091
PM0428E	1091
PM050401E	837
PM050402E	837
PM050411E	837
PM050412E	837
PM050421S	840
PM050422S	840
PM050501E	837
PM050502E	837
PM050511E	837
PM050512E	837
PM050601E	837
PM050602E	837
PM050611E	837
PM050612E	837
PM050801E	837
PM050801S	840
PM050802E	837
PM050802S	840
PM050803E	837
PM050811E	837
PM050812E	837
PM050813E	837
PM050821S	840
PM050822S	840
PM050823S	840
PM051002E	837
PM051003E	837
PM051004E	837
PM051012E	837
PM051013E	837
PM051014E	837
PM051203E	837
PM051204E	837
PM051213E	837
PM051214E	837
PM051513E	1090
PM051514E	1090
PM051814E	1090
PM052214E	1090
PM052216E	1090
PM060504E	838
PM060604E	838
PM060605E	838
PM060804E	838
PM060805E	838
PM060806E	838
PM061006E	838
PM061008E	838
PM061208E	838
PM061210E	838
PM061510E	838
PM061512E	1091
PM061815E	1091
PM062215E	1091
PM062218E	1091
PM062815E	1091
PM0804R	838
PM0804S	841
PM0805R	838
PM0806R	838
PM0808R	838
PM0808S	841
PM0810R	838
PM0812R	838
PM0815E	1091
PM0815R	838
PM0818E	1091
PM0822E	1091
PM0828E	1091
PM090401E	838
PM090402E	838
PM090411E	838
PM090412E	838
PM090421S	841
PM090501E	838
PM090502E	838
PM090511E	838
PM090512E	838
PM090601E	838
PM090602E	838
PM090611E	838
PM090612E	838
PM090801E	838
PM090801S	841
PM090802E	838
PM090803E	838
PM090803S	841
PM090811E	838
PM090812E	838
PM090813E	838
PM091002E	838
PM091003E	838
PM091004E	838
PM091012E	838
PM091013E	838
PM091014E	838
PM091203E	838
PM091204E	838
PM091213E	838
PM091214E	838
PM100401E	839
PM100402E	839
PM100411E	839
PM100412E	839
PM100502E	839
PM100511E	839
PM100512E	839
PM100601E	839
PM100602E	839
PM100611E	839
PM100612E	839
PM100801E	839
PM100802E	839
PM100803E	839
PM100811E	839
PM100812E	839
PM100813E	839
PM101002E	839
PM101003E	839
PM101004E	839
PM101012E	839
PM101013E	839
PM101014E	839
PM101203E	839
PM101204E	839
PM101213E	839
PM101214E	839
PM110411E	837
PM110511E	837
PM110512E	837
PM110601E	837
PM110611E	837
PM110612E	837
PM110801S	840
PM110802E	837
PM110811E	837
PM110812E	837
PM110813E	837
PM111003E	837
PM111012E	837
PM111013E	837
PM111014E	837
PM111203E	837
PM111204E	837
PM111213E	837
PM111214E	837
PM1-12	1165

Code	Page
PM112-114	1165
PM114-1	1165
PM1-1FF	1165
PM1204E	838
PM1206E	838
PM1208E	838
PM1208S	840
PM1210E	838
PM12-12	1165
PM1212E	838
PM12-12FF	1165
PM12-38	1165
PM1-34	1165
PM1-38	1165
PM14-14	1165
PM14-14FF	1165
PM14-18	1165
PM15WB	1091
PM18-18	1165
PM18-18FF	1165
PM1904E	839
PM1904S	842
PM1905E	839
PM1908S	842
PM1910E	839
PM1912E	839
PM1915B	884
PM1915E	839
PM1922E	839
PM200604E	837
PM200804E	837
PM200804S	842
PM200806E	837
PM201004E	837
PM201006E	837
PM201008E	837
PM201208E	837
PM201210E	837
PM210604E	836
PM210804E	836
PM210804S	841
PM210806E	836
PM211004E	836
PM211006E	836
PM211008E	836
PM211208E	836
PM211210E	836
PM220404E	837
PM220404S	841
PM220505E	837
PM220606E	837
PM220808E	837
PM220808S	841
PM221010E	837
PM221212E	837
PM221515E	837
PM221818E	1090
PM222222E	1090
PM22WB	1091
PM2304E	837
PM2310E	837
PM250604E	839
PM250806E	839
PM250808S	842
PM251008E	839
PM2608S	842
PM2610S	842
PM290808S	842
PM3/8	777
PM3022AE	1090
PM303X1	756
PM303X2	756
PM303X3	756
PM303X4	756
PM34-12	1165
PM34-34	1165
PM34-34FF	1165
PM34-38	1165
PM38-14	1165
PM38-18	1165
PM38-38FF	1165
PM450411E	837
PM450611E	837
PM450612E	837
PM450812E	837
PM451015FE	837
PM4612E	1092
PM4615E	1092
PM4622E	1092
PMC10	423
PMC1815R	839
PMC2	423
PMC25	423
PMC5	423
PMC80	423
PMM1/4C	791
PMM1/8C	791
PMM5/32C	791
PMN10A-BN14K	423
PMN10C-BN14K	423
PMN150A-FN14K	423
PMN150C-FN14K	423
PMN1A-BN14K	423
PMN1C-BN14K	423
PMN20C-BN14K	423
PMN250A-FN14K	423
PMN250C-FN14K	423
PMN2A-BN14K	423
PMN2C-BN14K	423
PMN300A-FN14K	423
PMN300C-FN14K	423
PMN50A-BN14K	423
PMN50C-BN14K	423
PMN5A-BN14K	423
PMN5C-BN14K	423
PMN80A-BN14K	423
PMN80C-BN14K	423
PMT-02	89
PMT-04	89
PMT-06	89
PMT-08	89
PMT112	1487
PMT2	1487
PMT212	1487
PMT3BSP	1487
PMT3URT	1487
PMT4BSP	1487
PMT4URT	1487
PMTT22E	1092
PMUB15E	1090
PMV-H-S-4-FF-V	983
PMV-H-S-4-MF-V	983
PN10-12	1178
PN10-14	1178
PN10-18	1178
PN10-38	1178
PN11-14-18	1178
PN1-12-14	1178
PN1-12-38	1178
PN11-38-14	1178
PN1-14-18	1178
PN12-12	1150
PN12-14	1150
PN12-18	1150
PN12-34	1150
PN12-38	1150
PN13-12	1150
PN13-14	1150
PN13-18	1150
PN13-34	1150
PN13-38	1150
PN1-38-14	1178
PN14-10-12	1150
PN14-10-34	1150
PN14-10-38	1150
PN14-12-12	1150
PN14-12-34	1150
PN14-14-12	1150
PN14-14-34	1150
PN14-16-34	1150
PN14-19-34	1150
PN14-4-14	1150
PN14-4-18	1150
PN14-5-14	1150
PN14-5-18	1150
PN14-5-38	1150
PN14-6-12	1150
PN14-6-14	1150
PN14-6-38	1150
PN14-8-12	1150
PN14-8-14	1150
PN14-8-38	1150
PN15-10-12	1150
PN15-10-14	1150
PN15-10-34	1150
PN15-10-38	1150
PN15-12-12	1150
PN15-12-14	1150
PN15-12-34	1150
PN15-12-38	1150
PN15-14-12	1150
PN15-14-34	1150
PN15-14-38	1150
PN15-16-12	1150
PN15-16-34	1150
PN15-19-1	1150
PN15-19-12	1150
PN15-19-34	1150
PN15-25-34	1150
PN15-4-14	1150
PN15-4-18	1150
PN15-5-14	1150
PN15-5-18	1150
PN15-6-12	1150
PN15-6-14	1150
PN15-6-18	1150
PN15-6-34	1150
PN15-6-38	1150
PN15-8-12	1150
PN15-8-14	1150
PN15-8-18	1150
PN15-8-38	1150
PN16-10-12	1151
PN16-10-14	1151
PN16-10-34	1151
PN16-10-38	1151
PN16-12-12	1151
PN16-12-14	1151
PN16-12-34	1151
PN16-12-38	1151
PN16-14-12	1151
PN16-14-34	1151
PN16-14-38	1151
PN16-16-12	1151
PN16-16-34	1151
PN16-19-12	1151
PN16-19-34	1151
PN16-4-14	1151
PN16-4-18	1151
PN16-5-12	1151
PN16-5-14	1151
PN16-5-18	1151
PN16-6-12	1151
PN16-6-14	1151
PN16-6-18	1151
PN16-6-38	1151
PN16-8-12	1151
PN16-8-14	1151
PN16-8-18	1151
PN16-8-38	1151
PN17-10-6	1151
PN17-10-8	1151
PN17-12-10	1151
PN17-16-14	1151
PN17-19-16	1151
PN17-5-4	1151
PN17-6-5	1151
PN17-8-6	1151
PN18-10	1151
PN18-12	1151
PN18-14	1151
PN18-16	1151
PN18-19	1151
PN18-4	1151
PN18-5	1151
PN18-6	1151
PN18-8	1151
PN19-10-6	1150
PN19-10-8	1150
PN19-12-10	1150
PN19-12-8	1150
PN19-14-10	1150
PN19-14-12	1150
PN19-16-12	1150
PN19-16-14	1150
PN19-19-14	1150
PN19-19-16	1150
PN19-5-4	1150
PN19-6-4	1150
PN19-6-5	1150
PN19-8-5	1150
PN19-8-6	1150
PN20-10	1150
PN20-12	1150
PN20-14	1150
PN20-16	1150
PN20-19	1150
PN20-4	1150
PN20-5	1150
PN20-6	1150
PN20-8	1150
PN21-10	1151
PN2-12	1178
PN21-4	1151
PN2-14	1178
PN21-6	1151
PN21-8	1151
PN2-18	1178
PN22-10-12	1151
PN22-10-14	1151
PN22-10-38	1151
PN22-12-12	1151
PN22-12-14	1151
PN22-12-34	1151
PN22-12-38	1151
PN22-14-38	1151
PN22-16-12	1151
PN22-16-34	1151
PN22-19-12	1151
PN22-19-34	1151
PN22-4-14	1151
PN22-4-18	1151
PN22-5-14	1151
PN22-5-18	1151
PN22-6-12	1151
PN22-6-14	1151
PN22-6-18	1151
PN22-6-38	1151
PN22-8-14	1151
PN22-8-18	1151
PN22-8-38	1151
PN23-10	1151
PN23-12	1151
PN23-14	1151
PN23-16	1151
PN23-19	1151
PN23-4	1151
PN23-5	1151
PN23-6	1151
PN23-8	1151
PN2-38	1178
PN24-10-8	1151
PN24-12-10	1151
PN24-16-14	1151
PN24-19-16	1151
PN24-5-4	1151
PN24-6-5	1151
PN24-8-6	1151
PN25-10-12	1150
PN25-12-12	1150

Code	Page
PN25-14-12	1150
PN25-19-12	1150
PN25-5-18	1150
PN25-6-18	1150
PN25-8-12	1150
PN3-12-12	1178
PN3-12-14	1178
PN3-12-38	1178
PN3-14-14	1178
PN3-14-18	1178
PN3-14-38	1178
PN3-18-12	1178
PN3-18-14	1178
PN3-38-12	1178
PN3-38-14	1178
PN3-38-18	1178
PN3-38-38	1178
PN4-12-14	1178
PN4-12-38	1178
PN4-14-18	1178
PN4-34-12	1178
PN4-34-14	1178
PN4-34-38	1178
PN4-38-14	1178
PN4-38-18	1178
PN5-12	1178
PN5-14	1178
PN5-18	1178
PN5-38	1178
PN6-12-14	1178
PN6-12-38	1178
PN6-14-18	1178
PN6-34-14	1178
PN6-38-14	1178
PN6-38-18	1178
PN7-12	1178
PN7-14	1178
PN7-38	1178
PNFG-110	1105
PNFG-20	1105
PNFG-25	1105
PNFG-32	1105
PNFG-40	1105
PNFG-50	1105
PNFG-63	1105
PNFG-75	1105
PNFG-90	1105
PNR	1643
PNV-HP-S-12-MF	983
PNV-HP-S-16-FF	983
PNV-HP-S-16-MF	983
PNV-HP-S-2-FF	983
PNV-HP-S-2-MF	983
PNV-HP-S-4-FF	983
PNV-HP-S-4-MF	983
PNV-HP-S-6-FF	983
PNV-HP-S-6-MF	983
PNV-HP-S-8-FF	983
PNV-HP-S-8-MF	983
PNV-IB-S-12-FF	983
PNV-IB-S-12-MF	983
PNV-IB-S-16-FF	983
PNV-IB-S-16-MF	983
PNV-IB-S-2-FF	983
PNV-IB-S-2-MF	983
PNV-IB-S-4-FF	983
PNV-IB-S-4-MF	983
PNV-IB-S-6-FF	983
PNV-IB-S-6-MF	983
PNV-IB-S-8-FF	983
PNV-IB-S-8-MF	983
POC03-M3C	788
POC03-M5C	788
POC03-M6C	788
POC04-01C	788
POC04-G01C	788
POC04-M3C	788
POC04-M5C	788
POC04-M6C	788
POC06-01C	788
POC06-G01C	788
POC06-M5C	788
POC06-M6C	788
POC1/4-N00C	790
POC1/4-N01C	790
POC1/4-U10C	790
POC1/8-N00C	790
POC1/8-N01C	790
POC1/8-U10C	790
POC5/32-N00C	790
POC5/32-N01C	790
POC5/32-U10C	790
POCV04	244
POCV06	244
POCV08	244
POLY15X13	1215
POLY15X19	1215
POLY15X25	1215
POLY15X9	1215
POLY22X13	1215
POLY22X19	1215
POLY22X25	1215
POLY22X9	1215
POLY28X13	1215
POLY28X19	1215
POLY28X25	1215
POLY28X9	1215
POLY-STATION	284
PP00	1016
PP00S	1016
PP-01	89
PP-02	89
PP-04	89
PP-06	89
PP-08	89
PP1/2	777
PP1/4	777
PP1/8	777
PP10	1016
PP10-8-8-18	1163
PP10S	1016
PP1-12-12	1163
PP1-12-14	1163
PP1-12-38	1163
PP-12	89
PP13-14	1163
PP-16	89
PP1-6-14	1163
PP1-6-18	1163
PP1-8-14	1163
PP1-8-18	1163
PP20	1016
PP20S	1016
PP2-6-14	1163
PP2-6-18	1163
PP2-8-14	1163
PP3/8	777
PP3-12	1163
PP3-6	1163
PP3-8	1163
PP4-8-6	1163
PP5-12	1163
PP5-6	1163
PP5-8	1163
PP6-12-12	1163
PP6-12-14	1163
PP6-12-38	1163
PP6-6-14	1163
PP6-6-18	1163
PP6-8-14	1163
PP6-8-18	1163
PP6-8-38	1163
PP7-12-12	1163
PP7-12-14	1163
PP7-12-38	1163
PP7-6-14	1163
PP7-8-14	1163
PP8-12-12	1163
PP8-12-14	1163
PP8-6-14	1163
PP9-12	1163
PP9-6	1163
PP9-8	1163
PPA-02	88
PPA-04	88
PPA-06	88
PPA-08	88
PPA-12	88
PPA-16	88
PPAUTO	1519
PPC-02	89
PPC-04	89
PPC-06	89
PPC-08	89
PPC-12	89
PPC150	423
PPC-16	89
PPC300	423
PPCF150	423
PPCF300	423
PPCLIP-110	1106
PPCLIP-16	1106
PPCLIP-160	1106
PPCLIP-20	1106
PPCLIP-225	1106
PPCLIP-25	1106
PPCLIP-32	1106
PPCLIP-40	1106
PPCLIP-50	1106
PPCLIP-63	1106
PPCLIP-75	1106
PPCLIP-90	1106
PPF1/2	777
PPFE-02	89
PPFE-04	89
PPFE-06	89
PPFE-08	89
PPFE-12	89
PPFE-16	89
PPME-02	89
PPME-04	89
PPME-06	89
PPME-08	89
PP-MS	1519
PPMSV040606W	884
PPMSV041010W	884
PPRO03	944
PPRO06	944
PPRO09	944
PP-SS	1519
PPSV010822W	884
PPSV011223W	884
PPSV040808W	884
PPSV041212W	884
PPSV500822W	884
PPV1-12-38	1164
PPV14-10-12	1152
PPV14-12-12	1152
PPV14-5-14	1152
PPV14-5-18	1152
PPV14-5-38	1152
PPV14-6-12	1152
PPV14-6-14	1152
PPV14-6-38	1152
PPV14-8-14	1152
PPV14-8-38	1152
PPV15-10-12	1152
PPV15-10-14	1152
PPV15-10-34	1152
PPV15-10-38	1152
PPV15-12-12	1152
PPV15-12-34	1152
PPV15-12-38	1152
PPV15-16-12	1152
PPV15-19-12	1152
PPV15-19-34	1152
PPV15-4-18	1152
PPV15-5-14	1152
PPV15-6-12	1152
PPV15-6-14	1152
PPV15-6-18	1152
PPV15-6-38	1152
PPV15-8-12	1152
PPV15-8-14	1152
PPV15-8-38	1152
PPV16-10-12	1152
PPV16-10-14	1152
PPV16-10-34	1152
PPV16-10-38	1152
PPV16-12-12	1152
PPV16-12-14	1152
PPV16-12-34	1152
PPV16-12-38	1152
PPV16-16-12	1152
PPV16-16-34	1152
PPV1-6-18	1164
PPV16-19-12	1152
PPV16-19-34	1152
PPV16-4-14	1152
PPV16-4-18	1152
PPV16-5-14	1152
PPV16-5-18	1152
PPV16-6-12	1152
PPV16-6-14	1152
PPV16-6-18	1152
PPV16-6-38	1152
PPV16-8-12	1152
PPV16-8-14	1152
PPV16-8-18	1152
PPV16-8-38	1152
PPV1-8-14	1164
PPV22-10-14	1152
PPV22-12-12	1152
PPV22-12-14	1152
PPV22-12-38	1152
PPV22-16-34	1152
PPV22-19-34	1152
PPV22-6-14	1152
PPV22-6-18	1152
PPV22-8-14	1152
PPV2-6-14	1164
PPV2-6-18	1164
PPV2-8-14	1164
PPV3.0606.112	298
PPV3.0606.113	298
PPV3.1010.112	298
PPV3.1010.113	298
PPV3.1012.302	298
PPV3.1012.303	298
PPV3.1012.502	298
PPV3.1012.503	298
PPV3.1014.302	298
PPV3.1014.303	298
PPV3.1014.502	298
PPV3.1014.503	298
PPV3.1016.302	298
PPV3.1016.303	298
PPV3.1016.402	298
PPV3.1016.403	298
PPV3.1016.502	298
PPV3.1016.503	298
PPV3.1016.603	298
PPV3.1018.302	298
PPV3.1018.303	298
PPV3.1018.402	298
PPV3.1018.403	298
PPV3.1018.502	298
PPV3.1018.503	298
PPV3.1018.603	298
PPV3.1020.402	298
PPV3.1020.403	298
PPV3.1020.603	298
PPV3.1313.112	298
PPV3.1313.113	298
PPV3.1314.302	298
PPV3.1314.303	298
PPV3.1314.503	298
PPV3.1316.302	298
PPV3.1316.303	298
PPV3.1316.503	298

Code	Page
PPV3.1318.302	**298**
PPV3.1318.303	**298**
PPV3.1318.402	**298**
PPV3.1318.403	**298**
PPV3.1318.503	**298**
PPV3.1318.603	**298**
PPV3.1320.402	**298**
PPV3.1320.403	**298**
PPV3.1320.603	**298**
PPV3.1322.302	**298**
PPV3.1322.303	**298**
PPV3.1322.402	**298**
PPV3.1322.403	**298**
PPV3.1322.503	**298**
PPV3.1322.603	**298**
PPV3.1324.402	**298**
PPV3.1324.403	**298**
PPV3.1324.603	**298**
PPV3.1326.302	**298**
PPV3.1326.303	**298**
PPV3.1326.503	**298**
PPV3.1330.402	**298**
PPV3.1330.403	**298**
PPV3.1330.603	**298**
PPV3.2019.112	**298**
PPV3.2019.113	**298**
PPV3.2525.112	**298**
PPV3.2525.113	**298**
PPV3-12	**1164**
PPV3-6	**1164**
PPV3-8	**1164**
PPV5-12	**1164**
PPV5-6	**1164**
PPV5-8	**1164**
PPV6-12-38	**1164**
PPV6-6-18	**1164**
PPV6-8-14	**1164**
PPV9-12	**1164**
PPV9-6	**1164**
PPV9-8	**1164**
PPW	**1016**
PPWS	**1016**
PR030103P1	**420**
PR030103P2	**420**
PR030203P1	**420**
PR030203P2	**420**
PR030505P1	**420**
PR030505P2	**420**
PR032007P1	**420**
PR032007P2	**420**
PR03B01	**420**
PR03B05	**420**
PR03B20	**420**
PR04/04	**1612**
PR101-01	**655**
PR102-01	**655**
PR104-M02	**695**
PR104-M04	**695**
PR104-M07	**695**
PR200-02	**655**
PR201-02	**655**
PR302-04	**655**
PRA/802032/M/100	**505**
PRA/802032/M/125	**505**
PRA/802032/M/160	**505**
PRA/802032/M/200	**505**
PRA/802032/M/25	**505**
PRA/802032/M/250	**505**
PRA/802032/M/320	**505**
PRA/802032/M/50	**505**
PRA/802032/M/80	**505**
PRA/802040/M/100	**505**
PRA/802040/M/160	**505**
PRA/802040/M/200	**505**
PRA/802040/M/50	**505**
PRA/802040/M/80	**505**
PRA/802050/M/100	**505**
PRA/802050/M/125	**505**
PRA/802050/M/160	**505**
PRA/802050/M/200	**505**
PRA/802050/M/25	**505**
PRA/802050/M/250	**505**
PRA/802050/M/320	**505**
PRA/802050/M/50	**505**
PRA/802050/M/80	**505**
PRA/802063/M/100	**505**
PRA/802063/M/125	**505**
PRA/802063/M/160	**505**
PRA/802063/M/200	**505**
PRA/802063/M/25	**505**
PRA/802063/M/250	**505**
PRA/802063/M/320	**505**
PRA/802063/M/50	**505**
PRA/802063/M/80	**505**
PRA/802080/M/160	**505**
PRA/802080/M/200	**505**
PRA/802080/M/25	**505**
PRA/802080/M/250	**505**
PRA/802080/M/50	**505**
PRA/802080/M/80	**505**
PRA/802100/M/100	**505**
PRA/802100/M/125	**505**
PRA/802100/M/160	**505**
PRA/802100/M/250	**505**
PRA/802100/M/320	**505**
PRA/802100/M/50	**505**
PRA-02-01	**88**
PRA-04-02	**88**
PRA-06-02	**88**
PRA-06-04	**88**
PRA-08-02	**88**
PRA-08-04	**88**
PRA-08-06	**88**
PRA-12-04	**88**
PRA-12-06	**88**
PRA-12-08	**88**
PRA-16-04	**88**
PRA-16-08	**88**
PRA-16-12	**88**
PRB-02-01	**89**
PRB-04-02	**89**
PRB-06-02	**89**
PRB-06-04	**89**
PRB-08-02	**89**
PRB-08-04	**89**
PRB-08-06	**89**
PRB1-12	**1177**
PRB112-1	**1177**
PRB112-114	**1177**
PRB112-34	**1177**
PRB114-1	**1177**
PRB114-12	**1177**
PRB114-34	**1177**
PRB-12-04	**89**
PRB-12-06	**89**
PRB-12-08	**89**
PRB1-34	**1177**
PRB-16-04	**89**
PRB-16-06	**89**
PRB-16-08	**89**
PRB-16-12	**89**
PRB2-1	**1177**
PRB2-112	**1177**
PRB2-114	**1177**
PRB212-2	**1177**
PRB2-34	**1177**
PRB3-2	**1177**
PRB3-212	**1177**
PRB34-12	**1177**
PRC-04-02	**88**
PRC-06-04	**88**
PRC-08-02	**88**
PRC-08-04	**88**
PRC-08-06	**88**
PRC-12-04	**88**
PRC-12-08	**88**
PRC-16-08	**88**
PRE1-12	**1177**
PRE112-114	**1177**
PRE114-1	**1177**
PRE12-38	**1177**
PRE1-34	**1177**
PRE2-112	**1177**
PRE34-12	**1177**
PREDV06	**244**
PREDV08	**244**
PRESSURE-L15500V	**1666**
PRESSURE-L15635V	**1666**
PRESSURE-L15760V	**1666**
PRESSURE-L15900V	**1666**
PRESSURE-L500V	**1666**
PRESSURE-L635V	**1666**
PRESSURE-L760V	**1666**
PRESSURE-L900V	**1666**
PRESSURE-LANCE	**1666**
PRESSURE-LANCE15	**1666**
PRESSURE-LANCESH	**1666**
PRHN-02-01	**88**
PRHN-04-02	**88**
PRHN-06-02	**88**
PRHN-06-04	**88**
PRHN-08-02	**88**
PRHN-08-04	**88**
PRHN-08-06	**88**
PRHN-12-06	**88**
PRHN-12-08	**88**
PRHN-16-08	**88**
PRHN-16-12	**88**
PR-M 10 L	**117**
PR-M 10 S	**117**
PR-M 12 L	**117**
PR-M 12 S	**117**
PR-M 14 S	**117**
PR-M 15 L	**117**
PR-M 16 S	**117**
PR-M 18 L	**117**
PR-M 20 S	**117**
PR-M 22 L	**117**
PR-M 25 S	**117**
PR-M 28 L	**117**
PR-M 30 S	**117**
PR-M 35 L	**117**
PR-M 38 S	**117**
PR-M 42 L	**117**
PR-M 6 L	**117**
PR-M 6 S	**117**
PR-M 8 L	**117**
PR-M 8 S	**117**
PRN112-114	**1177**
PRN114-1	**1177**
PRN1-34	**1177**
PRN2-112	**1177**
PRN212-2	**1177**
PRN34-12	**1177**
PROG12	**1647**
PRS112-114	**1177**
PRS114-1	**1177**
PRS1-34	**1177**
PRS2-112	**1177**
PRS34-12	**1177**
P-RSTV10LM-WD	**126**
P-RSTV10LR-WD	**126**
P-RSTV10SR-WD	**126**
P-RSTV12LM-WD	**126**
P-RSTV12LR-WD	**126**
P-RSTV12SR-WD	**126**
P-RSTV15LM-WD	**126**
P-RSTV15LR-WD	**126**
P-RSTV16SM-WD	**126**
P-RSTV16SR-WD	**126**
P-RSTV18LM-WD	**126**
P-RSTV18LR-WD	**126**
P-RSTV20SM-WD	**126**
P-RSTV20SR-WD	**126**
P-RSTV22LM-WD	**126**
P-RSTV25SM-WD	**126**
P-RSTV25SR-WD	**126**
P-RSTV28LM-WD	**126**
P-RSTV30SM-WD	**126**
P-RSTV30SR-WD	**126**
P-RSTV35LM-WD	**126**
P-RSTV35LR-WD	**126**
P-RSTV38SM-WD	**126**
P-RSTV38SR-WD	**126**
P-RSTV42LR-WD	**126**
P-RSTV6LM-WD	**126**
P-RSTV6LR-WD	**126**
P-RSTV6SM-WD	**126**
P-RSTV6SR-WD	**126**
P-RSTV8LM-WD	**126**
P-RSTV8LR-WD	**126**
P-RSTV8SM-WD	**126**
P-RSTV8SR-WD	**126**
PS/666/1/G	**557**
PS/666/1/N	**557**
PS/666/1/R	**557**
PS10CLR	**1754**
PS10SKR	**1754**
PS-12	**630**
PS-14	**630**
PS150SC-FNT14K	**424**
PS-18	**630**
PS20CLR	**1754**
PS20SKR	**1754**
PS24CLR	**1754**
PS300SC-FNT14K	**424**
PS32AMR	**1754**
PS32CLR	**1754**
PS32MIR	**1754**
PS32SKR	**1754**
PS-34	**630**
PS-38	**630**
PS44BKR	**1753**
PS46GRR	**1753**
PS53BKR	**1752**
PS53ORR	**1752**
PS53RBR	**1752**
PS53WHR	**1752**
PS53YER	**1752**
PS57ORR	**1752**
PS57RBR	**1752**
PS57RER	**1752**
PS57WHR	**1752**
PS57YER	**1752**
PS73ORR	**1752**
PS73RBR	**1752**
PS73RER	**1752**
PS73WHR	**1752**
PS73YER	**1752**
PS79BKR	**1752**
PS79NAR	**1752**
PS79ORR	**1752**
PS79YER	**1752**
PSBF0404CF	**40**
PSBF044504CF	**40**
PSBF049004CF	**40**
PSBF0606CF	**40**
PSBF064506CF	**40**
PSBF069006CF	**40**
PSBF0808CF	**40**
PSBF084508CF	**40**
PSBF089008CF	**40**
PSBF1212CF	**40**
PSBF124512CF	**40**
PSBF129012CF	**40**
PSBF1616CF	**40**
PSBF164516CF	**40**
PSBF169016CF	**40**
PSE-01	**89**
PSE-02	**89**
PSE-04	**89**
PSE-06	**89**
PSE-08	**89**
PSE-12	**89**
PSE-16	**89**
PSE4610W	**880**
PSJF0404CF	**40**
PSJF044504CF	**40**
PSJF049004CF	**40**
PSJF0606CF	**40**

Code	Page
PSJF064506CF	40
PSJF069006CF	40
PSJF0808CF	40
PSJF084508CF	40
PSJF089008CF	40
PSJF1212CF	40
PSJF124512CF	40
PSJF129012CF	40
PSK10	423
PSK100	423
PSK360	423
PSM100-BN14K	424
PSM10-BN14K	424
PSM2-BN14K	424
PS-M5	630
PSM50-BN14K	424
PSM5-BN14K	424
PSMFL06-04CF	40
PSMFL06-45-04CF	40
PSMFL06-90-04CF	40
PSMFL08-04CF	40
PSMFL08-45-04CF	40
PSMFL08-90-04CF	40
PSMFL10-06CF	40
PSMFL10-45-06CF	40
PSMFL10-90-06CF	40
PSMFL12-06CF	40
PSMFL12-45-06CF	40
PSMFL12-90-06CF	40
PSMFL15-08CF	40
PSMFL15-45-08CF	40
PSMFL15-90-08CF	40
PSMFL22-12CF	40
PSMFL22-45-12CF	40
PSMFL22-90-12CF	40
PSP150-FN14K	424
PSP300-FN14K	424
PST03-M3C	789
PST03-M5C	789
PST03-M6C	789
PST04-01C	789
PST04-G01C	789
PST04-M3C	789
PST04-M5C	789
PST04-M6C	789
PST06-01C	789
PST06-G01C	789
PST06-M5C	789
PST06-M6C	789
PST1/4-N00C	791
PST1/4-N01C	791
PST1/4-U10C	791
PST1/8-N00C	791
PST1/8-N01C	791
PST1/8-U10C	791
PST4.0606.112	304
PST4.0606.113	304
PST4.1310.112	304
PST4.1310.113	304
PST4.1313.112	304
PST4.1313.113	304
PST4.2013.112	304
PST4.2013.113	304
PST4.2019.112	304
PST4.2019.113	304
PST4.2519.112	304
PST4.2519.113	304
PST4.2525.112	304
PST4.2525.113	304
PST4.3025.112	304
PST4.3025.113	304
PST4.3031.112	304
PST4.3031.113	304
PST4.3939.112	304
PST4.3939.113	304
PST5/32-N00C	791
PST5/32-U10C	791
PT03-M3C	788
PT03-M5C	788
PT03-M6C	788
PT04-01C	788
PT04-G01C	788
PT04-M3C	788
PT04-M5C	788
PT04-M6C	788
PT06-01C	788
PT06-G01C	788
PT06-M5C	788
PT06-M6C	788
PT1	1165
PT1/4-N00C	791
PT1/4-N01C	791
PT1/4-U10C	791
PT1/8-N00C	791
PT1/8-N01C	791
PT1/8-U10C	791
PT112	1165
PT114	1165
PT12	1165
PT14	1165
PT18	1165
PT2	1165
PT2110QBPGG124	251
PT2210QBPGG124	251
PT38	1165
PT4110QBPGG164	251
PT4210QBPGG164	251
PT5/32-N00C	791
PT5/32-N01C	791
PT5/32-U10C	791
PTB5920000	1588
PTB5920003	1588
PTB5920005	1588
PTB5920006	1588
PTB5920008	1588
PTC1	1177
PTC112	1177
PTC114	1177
PTC12	1177
PTC2	1177
PTC34	1177
PTE100GA-IMDMR14	422
PTE100GA-IMR14	422
PTE100GA-VMDMR14	422
PTE100GA-VMR14	422
PTE10GA-IMDMR14	422
PTE10GA-IMR14	422
PTE10GA-VMDMR14	422
PTE10GA-VMR14	422
PTE1GA-IMDMR14	422
PTE1GA-IMR14	422
PTE1GA-VMDMR14	422
PTE1GA-VMR14	422
PTE200GA-IMDMR14	422
PTE200GA-IMR14	422
PTE200GA-VMDMR14	422
PTE200GA-VMR14	422
PTE20GA-IMDMR14	422
PTE20GA-IMR14	422
PTE20GA-VMDMR14	422
PTE20GA-VMR14	422
PTE2GA-IMDMR14	422
PTE2GA-IMR14	422
PTE2GA-VMDMR14	422
PTE2GA-VMR14	422
PTE400GA-IMDMR14	422
PTE400GA-IMR14	422
PTE400GA-VMDMR14	422
PTE400GA-VMR14	422
PTE4GA-IMDMR14	422
PTE4GA-IMR14	422
PTE4GA-VMDMR14	422
PTE4GA-VMR14	422
PTE50GA-IMDMR14	422
PTE50GA-IMR14	422
PTE50GA-VMDMR14	422
PTE50GA-VMR14	422
PTE5GA-IMDMR14	422
PTE5GA-IMR14	422
PTE5GA-VMDMR14	422
PTE5GA-VMR14	422
PTF-40	1391
PTF-80	1391
PTFE	1391
PTFE-1	1472
PTFE-112	1472
PTFE-114	1472
PTFE-12	1472
PTFE-2	1472
PTFE-212	1472
PTFE25MM	1391
PTFE-3	1472
PTFE-34	1472
PTFEF-03	16
PTFEF-04	16
PTFEF-05	16
PTFEF-06	16
PTFEF-08	16
PTFEF-10	16
PTFEF-12	16
PTFEF-16	16
PTFE-GAS	1391
PTH-1/2-100	1413
PTH-1-60	1413
PTH-3/4-15SAFE	1413
PTH-3/4-90	1413
PTL-1/2-100	1414
PTL-1/4-100	1414
PTL-3/16-100	1414
PTL-3/4-100	1414
PTL-3/8-100	1414
PTL-5/16-100	1414
PTP	1649
PTP1	1177
PTP112	1177
PTP114	1177
PTP12	1177
PTP2	1177
PTP212	1177
PTP34	1177
PTS-112-ABS	1098
PTS-12-ABS	1098
PTS-1-ABS	1098
PTS-212-ABS	1098
PTS-2-ABS	1098
PTS-3-ABS	1098
PTS-4-ABS	1098
PTV1.1010.002	297
PTV1.1010.003	297
PTV1.1313.002	297
PTV1.1313.003	297
PTV1.2019.002	297
PTV1.2019.003	297
PTV1.2525.002	297
PTV1.2525.003	297
PU03/020B	898
PU03/020CB	898
PU04/025	898
PU04/025-100	899
PU04/025B	898
PU04/025B-100	899
PU04/025CB	898
PU04/025CB-100	899
PU04/025G	898
PU04/025G-100	899
PU04/025N	898
PU04/025N-100	899
PU04/025R	898
PU04/025R-100	899
PU04/025Y	898
PU04/025Y-100	899
PU05/030B	898
PU05/030CB	898
PU05/030N	898
PU06/040	898
PU06/040-100	899
PU06/040B	898
PU06/040B-100	899
PU06/040CB	898
PU06/040CB-100	899
PU06/040G	898
PU06/040G-100	899
PU06/040N	898
PU06/040N-100	899
PU06/040R	898
PU06/040R-100	899
PU06/040Y	898
PU06/040Y-100	899
PU08/055	898
PU08/055-100	899
PU08/055B	898
PU08/055B-100	899
PU08/055CB	898
PU08/055CB-100	899
PU08/055G	898
PU08/055G-100	899
PU08/055N	898
PU08/055N-100	899
PU08/055R	898
PU08/055R-100	899
PU08/055Y	898
PU08/055Y-100	899
PU08/060	898
PU08/060-100	899
PU08/060B	898
PU08/060B-100	899
PU08/060CB	898
PU08/060CB-100	899
PU08/060G	898
PU08/060G-100	899
PU08/060N	898
PU08/060N-100	899
PU08/060R	898
PU08/060R-100	899
PU08/060Y	898
PU08/060Y-100	899
PU1/2	777
PU1/4	777
PU1/8	777
PU10/065	898
PU10/065-100	899
PU10/065B	898
PU10/065B-100	899
PU10/065CB	898
PU10/065CB-100	899
PU10/065G	898
PU10/065G-100	899
PU10/065N	898
PU10/065N-100	899
PU10/065R	898
PU10/065R-100	899
PU10/065Y	898
PU10/065Y-100	899
PU10/080	898
PU10/080-100	899
PU10/080B	898
PU10/080B-100	899
PU10/080CB	898
PU10/080CB-100	899
PU10/080N	898
PU10/080N-100	899
PU12/080	898
PU12/080-100	899
PU12/080B	898
PU12/080B-100	899
PU12/080CB	898
PU12/080CB-100	899
PU12/080G	898
PU12/080G-100	899
PU12/080N	898
PU12/080N-100	899
PU12/080R	898
PU12/080R-100	899
PU12/080Y	898
PU16/110B	898
PU16/110CB	898
PU20M4N01B	276
PU3/8	777
PUC03C	789
PUC04C	789
PUC06C	789
PUC1/4C	791
PUC1/8C	791
PUC4/1	902
PUC4/1-14	902
PUC4/1-18	902
PUC4/1B	902
PUC4/1CB	902
PUC4/2	902
PUC4/2-14	902
PUC4/2-18	902
PUC4/2B	902
PUC4/2CB	902
PUC5/32C	791
PUC6/1	902
PUC6/1-14	902
PUC6/1-18	902
PUC6/1B	902
PUC6/1CB	902
PUC6/2	902

Code	Page
PUC6/2-14	902
PUC6/2-18	902
PUC6/2B	902
PUC6/2CB	902
PUC6/3	902
PUC6/3-14	902
PUC6/3-18	902
PUC6/3B	902
PUC6/3CB	902
PUC8/2	902
PUC8/2-14	902
PUC8/2-38	902
PUC8/2B	902
PUC8/2CB	902
PUC8/3	902
PUC8/3-14	902
PUC8/3B	902
PUC8/3CB	902
PUC8/5	902
PUC8/5-14	902
PUC8/5B	902
PUC8/5CB	902
PUET04/025-100	900
PUET04/025-25	900
PUET04/025B-100	900
PUET04/025B-25	900
PUET04/025CB-100	900
PUET04/025CB-25	900
PUET04/025N-100	900
PUET04/025N-25	900
PUET05/030-25	900
PUET05/030B-25	900
PUET05/030CB-25	900
PUET05/030N-25	900
PUET06/040-100	900
PUET06/040-25	900
PUET06/040B-100	900
PUET06/040B-25	900
PUET06/040CB-100	900
PUET06/040CB-25	900
PUET06/040N-100	900
PUET06/040N-25	900
PUET08/055-100	900
PUET08/055-25	900
PUET08/055B-100	900
PUET08/055B-25	900
PUET08/055CB-100	900
PUET08/055CB-25	900
PUET08/055N-100	900
PUET08/055N-25	900
PUET10/070-100	900
PUET10/070-25	900
PUET10/070B-100	900
PUET10/070B-25	900
PUET10/070CB-100	900
PUET10/070CB-25	900
PUET10/070N-100	900
PUET10/070N-25	900
PUET12/080-100	900
PUET12/080-25	900
PUET12/080B-100	900
PUET12/080B-25	900
PUET12/080CB-100	900
PUET12/080CB-25	900
PUET12/080N-100	900
PUET12/080N-25	900
PUL03C	789
PUL04C	789

Code	Page
PUL06C	789
PUL1/4C	791
PUL1/8C	791
PUL5/32C	791
PURLW-100	1438
PURLW-115	1438
PURLW-120	1438
PURLW-125	1438
PURLW-130	1438
PURLW-140	1438
PURLW-150	1438
PURLW-160	1438
PURLW-180	1438
PURLW-200	1438
PURLW-225	1438
PURLW-250	1438
PURLW-38	1438
PURLW-50	1438
PURLW-60	1438
PURLW-65	1438
PURLW-75	1438
PURLW-80	1438
PURLW-90	1438
PURMW-100	1438
PURMW-115	1438
PURMW-120	1438
PURMW-125	1438
PURMW-130	1438
PURMW-140	1438
PURMW-150	1438
PURMW-160	1438
PURMW-180	1438
PURMW-200	1438
PURMW-225	1438
PURMW-250	1438
PURMW-300	1438
PURMW-350	1438
PURMW-38	1438
PURMW-400	1438
PURMW-50	1438
PURMW-60	1438
PURMW-65	1438
PURMW-75	1438
PURMW-80	1438
PURMW-90	1438
PUSB-102-10	1438
PUSB-102-20	1438
PUSB-127-10	1438
PUSB-127-20	1438
PUSB-152-10	1438
PUSB-203-10	1438
PUSB-25-10	1438
PUSB-25-20	1438
PUSB-38-10	1438
PUSB-38-20	1438
PUSB-51-10	1438
PUSB-51-20	1438
PUSB76-10	1438
PUSB76-20	1438
PUT03C	789
PUT04C	789
PUT06C	789
PUT1/4C	791
PUT1/8C	791
PUT5/32C	791
PV1/2	777
PV1/4	777
PV1/8	777

Code	Page
PV10-12	1179
PV10-38	1179
PV1-12-14	1179
PV1-12-38	1179
PV1-14-18	1179
PV12-12	1179
PV12-14	1179
PV12-18	1179
PV12-38	1179
PV13-12	1179
PV13-14	1179
PV13-38	1179
PV1-38-14	1179
PV17-10-8	1152
PV17-12-10	1152
PV17-6-5	1152
PV17-8-6	1152
PV18-10	1152
PV18-12	1152
PV18-5	1152
PV18-8	1152
PV20-10	1152
PV20-12	1152
PV20-5	1152
PV20-6	1152
PV2-12	1179
PV2-14	1179
PV2-18	1179
PV23-10	1152
PV23-12	1152
PV23-5	1152
PV23-6	1152
PV23-8	1152
PV2-38	1179
PV3/8	777
PV3-12-14	1179
PV3-14-14	1179
PV3-14-18	1179
PV3-14-38	1179
PV3-18-38	1179
PV3-38-12	1179
PV3-38-14	1179
PV3-38-18	1179
PV4-12-14	1179
PV4-12-18	1179
PV4-12-38	1179
PV4-14-18	1179
PV4-38-14	1179
PV4-38-18	1179
PV5-12	1179
PV5-14	1179
PV5-18	1179
PV5-38	1179
PV60BLU	1752
PV60GNR	1752
PV60ORR	1752
PV60SKR	1752
PV60YER	1752
PV6-12-14	1179
PV6-14-18	1179
PV6-38-14	1179
PV7-14	1179
PV7-18	1179
PVC	1107
PVC03	1407
PVC05	1407
PVC06	1407
PVC08	1407

Code	Page
PVC1	1115
PVC10	1407
PVC112	1115
PVC114	1115
PVC12	1407
PVC12-CAP	1115
PVC12HD	1407
PVC16	1407
PVC19	1407
PVC2	1115
PVC212	1115
PVC25	1407
PVC250	1107
PVC3	1115
PVC32	1407
PVC34	1115
PVC38	1407
PVC38-CAP	1115
PVC4	1115
PVC50	1407
PVC50RW008	1590
PVE1	1115
PVE1.2019.002	307
PVE1.2019.003	307
PVE1.2525.002	307
PVE1.2525.003	307
PVE112	1115
PVE114	1115
PVE12	1115
PVE2	1115
PVE212	1115
PVE3	1115
PVE34	1115
PVE45-1	1115
PVE45-112	1115
PVE45-114	1115
PVE45-12	1115
PVE45-2	1115
PVE45-212	1115
PVE45-3	1115
PVE45-34	1115
PVE45-38	1115
PVE45-4	1115
PVEN1-114	1114
PVEN112-2	1114
PVEN114-112	1114
PVEN12-34	1114
PVEN212-3	1114
PVEN2-212	1114
PVEN3-4	1114
PVEN34-1	1114
PVEN38-12	1114
PVEP1	1109
PVEP112	1109
PVEP114	1109
PVEP12	1109
PVEP2	1109
PVEP212	1109
PVEP3	1109
PVEP34	1109
PVEP4	1109
PVEP45-1	1109
PVEP45-112	1109
PVEP45-114	1109
PVEP45-12	1109
PVEP45-2	1109
PVEP45-212	1109
PVEP45-3	1109

Code	Page
PVEP45-34	1109
PVEP45-4	1109
PVHTM1	1111
PVHTM1-114	1111
PVHTM112-2	1111
PVHTM114-112	1111
PVHTM12	1111
PVHTM12-34	1111
PVHTM14-12	1111
PVHTM2-212	1111
PVHTM34	1111
PVHTM34-1	1111
PVHTM38-58	1111
PVLN1	1113
PVLN112	1115
PVLN114	1113
PVLN12	1113
PVLN2	1115
PVLN212	1115
PVLN3	1115
PVLN34	1115
PVLN38	1115
PVLN4	1115
PVN1	1113
PVN112	1114
PVN114	1114
PVN12	1114
PVN2	1113
PVN212	1114
PVN34	1114
PVN38	1114
PVN4	1114
PVP1	1115
PVP112	1115
PVP12	1115
PVP2	1115
PVP212	1115
PVP3	1115
PVP34	1115
PVP38	1115
PVP4	1115
PVR1-12	1114
PVR112-1	1113
PVR112-34	1114
PVR114-1	1114
PVR114-12	1114
PVR114-34	1114
PVR12-38	1114
PVR1-34	1114
PVR1-38	1114
PVR2-1	1113
PVR2-112	1114
PVR2-114	1114
PVR212-112	1113
PVR212-2	1114
PVR3-112	1114
PVR3-2	1114
PVR3-212	1114
PVR34-12	1114
PVR34-38	1114
PVR4-2	1114
PVR4-212	1114
PVR4-3	1114
PVRB112-114	1113
PVRB114-1	1113
PVRB1-34	1113
PVRB2-112	1113
PVRB212-2	1114

Code	Page
PVRB3-212	1114
PVRB34-12	1113
PVRB4-3	1114
PVRN112-114	1113
PVRN114-1	1114
PVRN1-34	1113
PVRN212-2	1114
PVRN3-212	1114
PVRN34-12	1114
PVRN4-3	1114
PVRS112-114	1114
PVRS114-1	1114
PVRS12-38	1114
PVRS1-34	1114
PVRS2-112	1114
PVRS3-212	1114
PVRS34-12	1114
PVRS4-3	1114
PVS1	1114
PVS1.0606.013	306
PVS1.1006.013	306
PVS1.1010.013	306
PVS112	1114
PVS114	1114
PVS12	1114
PVS2	1114
PVS3.0606.022	306
PVS3.1006.022	306
PVS3.1010.022	306
PVS34	1114
PVT1	1115
PVT112	1115
PVT114	1115
PVT12	1115
PVT2	1115
PVT3	1115
PVT34	1115
PVT38	1115
PVT4	1115
PVTP1	1109
PVTP112	1109
PVTP114	1109
PVTP12	1109
PVTP2	1109
PVTP212	1109
PVTP3	1109
PVTP34	1109
PVTP4	1109
PVU1	1115
PVU112	1115
PVU114	1115
PVU12	1115
PVU2	1115
PVU212	1115
PVU3	1115
PVU34	1115
PVU38	1115
PVU4	1115
PVUPF1	1110
PVUPF112	1110
PVUPF114	1110
PVUPF12	1110
PVUPF2	1110
PVUPF212	1110
PVUPF3	1110
PVUPF34	1110
PVUPF4	1110
PVUPM112	1110
PVUPM2	1110
PVUPM2-112	1110
PVV3.0606.112	304
PVV3.0606.113	304
PVV3.1010.112	304
PVV3.1010.113	304
PVV3.1313.112	304
PVV3.1313.113	304
PVV3.2019.112	304
PVV3.2019.113	304
PVV3.2525.112	304
PVV3.2525.113T	304
PVV3.3031.112	304
PVV3.3031.113T	304
PVV3.3039.112	304
PVV3.3039.113T	304
PW26CLR	1754
PW29NAR	1752
PW48RER	1753
PW48YER	1753
PW68BGR	1754
PW72GGN	1753
PW73GYR	1753
PW78GOR	1753
PWAA-12F	1673
PWAA-14F	1673
PWAA-14M	1673
PWAA-22F	1673
PWAA-38F	1673
PWAA-38M	1673
PWAB-12M	1673
PWAB-14F	1673
PWAB-14M	1673
PWAB-22FF	1673
PWAB-22MM	1673
PWAB-38F	1673
PWAB-38M	1673
PWBLACK-04-100R1	1676
PWBLACK-04-100R2	1676
PWBLACK-04-10-R1	1676
PWBLACK-04-25-R1	1676
PWBLACK-05-100R2	1676
PWBLACK-05-10-R1	1676
PWBLACK-05-25-R1	1676
PWBLACK-06-100R2	1676
PWBLACK-06-10-R1	1676
PWBLACK-06-25-R1	1676
PWBLUE-04-100-R2	1676
PWBLUE-04-10-R1	1676
PWBLUE-04-25-R1	1676
PWBLUE-05-10-R1	1676
PWBLUE-05-25-R1	1676
PWBLUE-06-100-R2	1676
PWBLUE-06-10-R1	1676
PWBLUE-06-10-R2	1676
PWBLUE-06-25-R1	1676
PWFC-20	1675
PWLA1	1667
PWLA10	1667
PWLA2	1667
PWLA3	1667
PWLA4	1667
PWLA5	1667
PWLA6	1667
PWLA7	1667
PWLA8	1667
PWLA9	1667
PWO-1	273
PWO-10	273
PWO-11	273
PWO-2	273
PWO-3	273
PWO-4	273
PWO-5	273
PWO-6	273
PWO-7	273
PWO-8	273
PWO-9	273
PWQRC-38	1659
PWQRP-38	1659
PXB-B4131BA2	564
PXB-B4131BC2	564
PXB-B4131BD2	564
PXB-B4131BT4	564
PXB-B4931	565
PXC10	884
PXC-M121	565
PXC-M521	565
PXC-M601A110	565
PY04C	789
PY06C	789
PY1/4C	791
PY5/32C	791
Q	
Q19SDLP34	1473
Q1DLP1	1473
Q1DLP114	1473
Q1DLP12	1473
Q1DLP14	1473
Q1DLP38	1473
Q1DLP58	1473
Q2DLP1	1473
Q2DLP114	1473
Q2DLP12	1473
Q2DLP14	1473
Q2DLP34	1473
Q2DLP38	1473
Q3DLP1	1473
Q3DLP114	1473
Q3DLP12	1473
Q3DLP14	1473
Q3DLP34	1473
Q3DLP38	1473
Q4	1473
QA/192020/22	535
QA/192025/22	535
QA/192032/21	535
QA/192040/21	535
QA/192050/21	535
QA/192063/21	535
QA/192080/21	535
QA/192100/21	535
QA/8032/00	506
QA/8032/21	506
QA/8032/22	535
QA/8032/23	506
QA/8040/00	506
QA/8040/22	535
QA/8040/23	506
QA/8050/00	506
QA/8050/21	506
QA/8050/22	535
QA/8050/23	506
QA/8063/00	506
QA/8063/21	506
QA/8063/22	535
QA/8063/23	506
QA/8080/21	506
QA/8080/22	535
QA/8080/23	506
QA/8100/00	506
QA/8100/21	506
QA/8100/22	535
QA/8100/23	506
QAC11	1474
QAC112	1474
QAC134	1474
QAC138	1474
QAC21	1474
QAC212	1474
QAC234	1474
QAC31	1474
QAC312	1474
QAC334	1474
QAC412	1474
QAC434	1474
QAY11	1474
QAY112	1474
QAY134	1474
QAY138	1474
QAY21	1474
QAY212	1474
QAY234	1474
QAY238	1474
QAY31	1474
QAY312	1474
QAY334	1474
QAY338	1474
QAY41	1474
QAY412	1474
QAY434	1474
QAYBE	1474
QAYR	1474
QC11	1473
QC112	1473
QC134	1473
QC21	1473
QC212	1473
QC234	1473
QC2GM34	1473
QC31	1473
QC312	1473
QC334	1473
QCR	1473
QHPA13-D6X2-C	311
QHPA13-D6X3-C	311
QHPA13-D7X3-C	311
QHPA13-D7X4-C	311
QHPA13-F4B3-C	311
QHPA14-D6X4-C	311
QHPA14-D7X5-C	311
QHPA14-D7X6-C	311
QHPA14-F4B4-C	311
QHPA16-D6X6-C	311
QHPA16-D6X7-C	311
QHPA16-D7X7-C	311
QHPA53-D6X2-C	311
QHPA53-D6X3-C	311
QHPA53-D7X3-C	311
QHPA53-D7X4-C	311
QHPA53-F4B3-C	311
QHPA54-D6X4-C	311
QHPA54-D6X5-C	311
QHPA54-D7X5-C	311
QHPA54-D7X6-C	311
QHPA54-F4B4-C	311
QHPA56-D6X6-C	311
QHPA56-D6X7-C	311
QHPA56-D7X7-C	311
QLCAAL020	1076
QLCAAL025	1076
QLCAAL032	1076
QLCAAL040	1076
QLCAAL050	1076
QLCAAL063	1076
QLCAAL080	1076
QLCAAL168	1077
QLCAPA016	1072
QLCAPA020	1072
QLCAPA025	1072
QLCAPA032	1072
QLCAPA040	1072
QLCAPA050	1072
QLCAPA063	1072
QLCLE16020	1072
QLCLE25032	1072
QLCLE40050	1072
QLCLE63	1072
QLCLEAL020025	1076
QLCLEAL032040	1076
QLCLEAL050	1076
QLCLEAL063	1076
QLCLEAL080	1076
QLDERAL025020	1076
QLDERAL032020	1076
QLDERAL040020	1076
QLDERAL040025	1076
QLDERAL050020	1076
QLDERAL050025	1076
QLDERAL063020	1076
QLDERAL063025	1076
QLDERAL063032	1076
QLDERAL080020	1076
QLDERAL080025	1076
QLDERAL080032	1076
QLDERAL110020	1076
QLDERAL110025	1076
QLDERAL110032	1076
QLDERPA025016	1072
QLDERPA025020	1072
QLDERPA032016	1072
QLDERPA032020	1072
QLDERPA040016	1072
QLDERPA040020	1072
QLDERPA040025	1072
QLDERPA050016	1072
QLDERPA050020	1072
QLDERPA050025	1072
QLDERPA063020	1072
QLDERPA063025	1072
QLDERPA063032	1072
QLDERPA080020	1072
QLDERPA080025	1072
QLDERPA080032	1072
QLDERPA110025	1072
QLDERPA110032	1072
QLFLA168480DIN	1077
QLFLEX020	1079
QLFLEX025	1079
QLFLEX032	1079
QLFLEX040	1079
QLFLEX063	1079

Code	Page
QLGO45AL020	1075
QLGO45AL025	1075
QLGO45AL032	1075
QLGO45AL040	1075
QLGO45AL168	1077
QLGO45FAL020048	1075
QLGO45FAL025048	1075
QLGO45FAL025068	1075
QLGO45PA020	1071
QLGO45PA025	1071
QLGO45PA032	1071
QLGO45PA040	1071
QLGO45PA050	1071
QLGO45PA063	1071
QLGO90AL020	1075
QLGO90AL025	1075
QLGO90AL032	1075
QLGO90AL040	1075
QLGO90AL050	1075
QLGO90AL063	1075
QLGO90AL080	1075
QLGO90AL110	1075
QLGO90AL168	1077
QLGO90MAL020048	1075
QLGO90MAL025048	1075
QLGO90MAL025068	1075
QLGO90PA016	1071
QLGO90PA020	1071
QLGO90PA025	1071
QLGO90PA032	1071
QLGO90PA040	1071
QLGO90PA050	1071
QLGO90PA063	1071
QLGO90PM020048	1071
QLGO90PM025048	1071
QLGO90PM025068	1071
QLMAAL020	1075
QLMAAL025	1075
QLMAAL032	1075
QLMAAL040	1075
QLMAAL050	1075
QLMAAL063	1075
QLMAAL080	1075
QLMAAL110	1075
QLMAAL168	1077
QLMAPA016	1071
QLMAPA020	1071
QLMAPA025	1071
QLMAPA032	1071
QLMAPA040	1071
QLMAPA050	1071
QLMAPA063	1071
QLMASAL032	1075
QLMASAL040	1075
QLMASAL050	1075
QLMASAL063	1075
QLMASAL080	1075
QLMASPA032	1071
QLMASPA040	1071
QLMASPA050	1071
QLMASPA063	1071
QLMFLAL080248DIN	1076
QLMFLAL110328DIN	1076
QLMIS016080	1072
QLMISAL020110	1076
QLMNMAL020048	1075
QLMNMAL020068	1075
QLMNMAL025068	1075
QLMNMAL025088	1075
QLMNMAL032108	1075
QLMNMAL040128	1075
QLMNMAL050168	1075
QLMNMAL063168	1075
QLMNMAL063208	1075
QLMNMAL080208	1075
QLMNMAL080248	1075
QLMNPA016048	1071
QLMNPA020048	1071
QLMNPA020068	1071
QLMNPA025048	1071
QLMNPA025068	1071
QLMNPA025088	1071
QLMNPA032088	1071
QLMNPA032108	1071
QLMNPA040088	1071
QLMNPA040108	1071
QLMNPA040128	1071
QLMNPA050128	1071
QLMNPA050168	1071
QLMNPA063168	1071
QLMPMAL020048	1075
QLMPMAL020068	1075
QLMPMAL025068	1075
QLMPMAL025088	1075
QLMPMAL032108	1075
QLMPMAL040128	1075
QLMPMAL050168	1075
QLMPMAL063208	1075
QLPUNM016038	1079
QLPUNM020048	1079
QLPUNM020068	1079
QLPUNM025088	1079
QLPUNM032108	1079
QLPUNM040128	1079
QLPUNM050168	1079
QLPUNM063168	1079
QLPUNM080248	1079
QLRIDPA025020	1071
QLRIDPA032025	1071
QLRIDPA040025	1071
QLRIDPA040032	1071
QLRIDPA050040	1071
QLRIDTU025020	1079
QLRIDTU032020	1079
QLRIDTU032025	1079
QLRIDTU040025	1079
QLRIDTU040032	1079
QLRIDTU050032	1079
QLRIDTU050040	1079
QLRIDTU063040	1079
QLRIDTU063050	1079
QLRIDTU080050	1079
QLRIDTU080063	1079
QLRIDTU110050	1079
QLRIDTU110063	1079
QLRIDTU110080	1079
QLSCI016	1069
QLSCI020	1069
QLSCI025	1069
QLTEAL020	1076
QLTEAL025	1076
QLTEAL032	1076
QLTEAL040	1076
QLTEAL050	1076
QLTEAL063	1076
QLTEAL080	1076
QLTEAL110	1076
QLTEAL168	1077
QLTEPA016	1072
QLTEPA020	1072
QLTEPA025	1072
QLTEPA032	1072
QLTEPA040	1072
QLTEPA050	1072
QLTEPA063	1072
QLTFLAL110328DIN	1076
QLTFLAL80248DIN	1076
QLTPAL020048	1076
QLTPAL025068	1076
QLTPAL032088	1076
QLTPAL040108	1076
QLTPAL050128	1076
QLTPAL063168	1076
QLTPAL080208	1076
QLTPAL110248	1076
QLTPPA020048	1072
QLTPPA025048	1072
QLTRAL025020	1076
QLTRAL032020	1076
QLTRAL040020	1076
QLTRAL040025	1076
QLTRPA020016	1072
QLTRPA025016	1072
QLTRPA025020	1072
QLTRPA032020	1072
QLTRPA032025	1072
QLTRPA040020	1072
QLTRPA040025	1072
QLTRPA040032	1072
QLTRPA050020	1072
QLTRPA050025	1072
QLTRPA050032	1072
QLTRPA050040	1072
QLTRPA063020	1072
QLTRPA063025	1072
QLTRPA063040	1072
QLTRPA063050	1072
QLTUAL020S	1069
QLTUAL025S	1069
QLTUAL032S	1069
QLTUAL040S	1069
QLTUAL050S	1069
QLTUAL063S	1069
QLTUAL080S	1069
QLTUAL110S	1069
QLTUAL168S	1077
QLTUAL4016S	1069
QLTUAL4020S	1069
QLTUAL4025S	1069
QLTUAL4032S	1069
QLTUAL4040S	1069
QLTUAL4050S	1069
QLTUAL4063S	1069
QLTUALG020S	1069
QLTUALG025S	1069
QLTUALG040S	1069
QLTUALG063S	1069
QLTUALGY020S	1069
QLTUALGY025S	1069
QLTUALGY032S	1069
QLTUALGY040S	1069
QLTUALGY050S	1069
QLTUALGY063S	1069
QLTUALGY080S	1069
QLTUMLST016	1069
QLTUMLST020	1069
QLTUMLST025	1069
QLVAF016048	1073
QLVAF020048AL	1073
QLVAF025068AL	1073
QLVAINOX025	1073
QLVAINOX032	1073
QLVAINOX040	1073
QLVAINOX050	1073
QLVAINOX063	1073
QLVAINOX080	1073
QLVAINOXMF025088	1073
QLVAINOXMF032128	1073
QLVAINOXMF040128	1073
QLVAINOXMF050168	1073
QLVAINOXMF063168	1073
QLVAINOXMF080248	1073
QLVALFAR110	1073
QLVALFAR168	1077
QLVAM016048	1073
QLVAM020048AL	1073
QLVAM025068AL	1073
QM/192020/21	535
QM/192025/21	535
QM/33/032/22	541
QM/33/040/22	541
QM/48/13J/21	591
QM/48/14J/21	591
QM/48/18J/21	591
QM/48/19J/21	591
QM/57016/25	541
QM/57020/25	541
QM/57025/24	541
QM/57025/25	541
QM/57032/25	541
QM/57040/24	541
QM/57063/25	534
QM/8010/25	474
QM/8010/32	474
QM/8012/24	474
QM/8012/25	474
QM/8012/32	474
QM/8020/24	474
QM/8020/25	474
QM/8020/32	474
QM/8025/25	474
QM/8025/32	474
QM/8032/35	535
QM/8040/25	535
QM/8040/32	541
QM/8050/25	506
QM/8050/32	506
QM/8080/25	506
QM/8080/32	506
QM/90016/22	534
QM/90025/22	534
QM/90040/22	534
QM/90050/22	534
QM/90063/22	534
QM/90080/22	534
QM/90100/22	534
QM/946	541
QM/947	474
QR	1473
QRNIT	1473
QSC-250	1107

R

Code	Page
R 41 100	511
R 41 125	511
R 41 32	511
R 41 40	511
R 41 50	511
R 41 63	511
R 41 80	511
R07-100-RNKG	689
R07-200-RNKG	689
R-10-12	177
R-10-15	177
R-10-18	177
R-10-375	177
R1-04SS	41
R-10-500	177
R-10-6	177
R1-06SS	41
R1-08SS	41
R1-16SS	41
R-12-10	177
R-12-16	177
R-12-18	177
R-12-20	177
R-12-22	177
R-12-25	177
R-12-500	177
R-125-125	171
R-125-187	171
R-125-250	171
R-125-375	171
R-125-500	171
R-12-6	177
R-12-750	177
R-12-8	177
R-16-12	177
R16-200-R30G	690
R-18-12	177
R-18-16	177
R-18-20	177
R-18-22	177
R-18-25	177
R-187-125	171
R-187-250	171
R-18-750	177
R18-B00-RNXD	689
R18-C00-RNXD	689
R-20-16	177
R-20-22	177
R-20-25	177
R-22-18	177
R-22-20	177
R-22-25	177
R-250-125	171
R-250-187	171
R-250-250	171
R-250-312	171
R-250-375	171
R-250-500	171
R-250-625	171
R-250-750	171
R-25-1000	177
R-25-18	177
R-25-20	177
R-3-10	177
R-312-375	171
R-3-125	177
R-312-500	171
R-3-250	177

Code	Page
R-3-4	**177**
R-3-6	**177**
R-375-250	**171**
R-375-375	**171**
R-375-500	**171**
R-375-625	**171**
R-375-750	**171**
R-4-250	**177**
R-4-6	**177**
R4F2-12	**16**
R4F2-16	**16**
R4F2-20	**16**
R4F2-24	**16**
R4F2-32	**16**
R-500-1000	**171**
R-500-250	**171**
R-500-375	**171**
R-500-500	**171**
R-500-625	**171**
R-500-750	**171**
R-6-10	**177**
R-6-12	**177**
R-6-125	**177**
R-6-18	**177**
R-6-250	**177**
R-625-1000	**171**
R-625-750	**171**
R-625-875	**171**
R-6-3	**177**
R-6-312	**177**
R-6-375	**177**
R64G-4GK-RMN	**684**
R64G-NNK-RMN	**684**
R-6-500	**177**
R-6-8	**177**
R68G-NNK-RLN	**684**
R-750-1000	**171**
R-750-500	**171**
R76115	**251**
R76125	**251**
R-8-10	**177**
R-8-12	**177**
R82G-2GK-RMG	**687**
R-8-375	**177**
R84G-3GK-RMG	**687**
R84G-4GK-RMG	**687**
R-8-500	**177**
R-8-6	**177**
RA/192020/MX/10	**535**
RA/192020/MX/15	**535**
RA/192020/MX/20	**535**
RA/192020/MX/25	**535**
RA/192020/MX/30	**535**
RA/192020/MX/40	**535**
RA/192020/MX/50	**535**
RA/192025/MX/10	**535**
RA/192025/MX/15	**535**
RA/192025/MX/20	**535**
RA/192025/MX/25	**535**
RA/192025/MX/30	**535**
RA/192025/MX/40	**535**
RA/192025/MX/50	**535**
RA/192032/MX/10	**535**
RA/192032/MX/15	**535**
RA/192032/MX/20	**535**
RA/192032/MX/25	**535**
RA/192032/MX/30	**535**
RA/192032/MX/40	**535**
RA/192032/MX/50	**535**
RA/192032/MX/60	**535**
RA/192032/MX/80	**535**
RA/192040/MX/10	**535**
RA/192040/MX/15	**535**
RA/192040/MX/20	**535**
RA/192040/MX/25	**535**
RA/192040/MX/30	**535**
RA/192040/MX/40	**535**
RA/192040/MX/50	**535**
RA/192050/MX/10	**535**
RA/192050/MX/15	**535**
RA/192050/MX/20	**535**
RA/192050/MX/25	**535**
RA/192050/MX/30	**535**
RA/192050/MX/40	**535**
RA/192050/MX/50	**535**
RA/192050/MX/60	**535**
RA/192063/M/15	**535**
RA/192063/M/25	**535**
RA/192063/M/40	**535**
RA/192063/M/50	**535**
RA/192063/M/60	**535**
RA/192063/M/80	**535**
RA/192080/M/15	**535**
RA/192080/M/25	**535**
RA/192080/M/40	**535**
RA/192080/M/50	**535**
RA/192080/M/60	**535**
RA/192080/M/80	**535**
RA/192100/M/15	**535**
RA/192100/M/25	**535**
RA/192100/M/40	**535**
RA/192100/M/50	**535**
RA/192100/M/60	**535**
RA/192100/M/80	**535**
RA/802032/M/100	**505**
RA/802032/M/125	**505**
RA/802032/M/160	**505**
RA/802032/M/200	**505**
RA/802032/M/25	**505**
RA/802032/M/250	**505**
RA/802032/M/320	**505**
RA/802032/M/50	**505**
RA/802032/M/80	**505**
RA/802040/M/100	**505**
RA/802040/M/125	**505**
RA/802040/M/200	**505**
RA/802040/M/25	**505**
RA/802040/M/250	**505**
RA/802040/M/320	**505**
RA/802040/M/50	**505**
RA/802040/M/80	**505**
RA/802050/M/160	**505**
RA/802050/M/200	**505**
RA/802050/M/25	**505**
RA/802050/M/250	**505**
RA/802050/M/50	**505**
RA/802050/M/80	**505**
RA/802063/M/100	**505**
RA/802063/M/25	**505**
RA/802063/M/250	**505**
RA/802063/M/320	**505**
RA/802063/M/50	**505**
RA/802080/M/100	**505**
RA/802080/M/160	**505**
RA/802080/M/200	**505**
RA/802080/M/25	**505**
RA/802080/M/50	**505**
RA/802080/M/80	**505**
RA100	**1456**
RA200	**1456**
RA65.50.04	**1065**
RA65.50.08	**1065**
RA69.50.25	**1065**
RAAR-106	**189**
RAAR-106.4	**189**
RAAR-108	**189**
RAAR-109.5	**189**
RAAR-110	**189**
RAAR-112	**189**
RAAR-212.7	**189**
RAAR-213.5	**189**
RAAR-214	**189**
RAAR-215	**189**
RAAR-216	**189**
RAAR-217.2	**189**
RAAR-218	**189**
RAAR-319	**189**
RAAR-320	**189**
RAAR-321.3	**189**
RAAR-322	**189**
RAAR-323	**189**
RAAR-325	**189**
RAAR-426.9	**189**
RAAR-430	**189**
RAAR-532	**189**
RAAR-533.7	**189**
RAAR-535	**189**
RAAR-538	**189**
RAAR-540	**189**
RAAR-542	**189**
RAAR-648	**189**
RAAR-650	**189**
RAD-90-10	**1417**
RAD-90-13	**1417**
RAD-90-16	**1417**
RAD-90-19	**1417**
RAD-90-22	**1417**
RAD-90-25	**1417**
RAD-90-28	**1417**
RAD-90-32	**1417**
RAD-90-35	**1417**
RAD-90-38	**1417**
RAD-90-51	**1417**
RAD-90-63	**1417**
RAD-90-76	**1417**
RANG-106	**189**
RANG-106.4	**189**
RANG-108	**189**
RANG-109.5	**189**
RANG-110	**189**
RANG-112	**189**
RANG-212.7	**189**
RANG-213.5	**189**
RANG-214	**189**
RANG-215	**189**
RANG-216	**189**
RANG-217.2	**189**
RANG-218	**189**
RANG-319	**189**
RANG-320	**189**
RANG-321.3	**189**
RANG-322	**189**
RANG-323	**189**
RANG-325	**189**
RANG-426.9	**189**
RANG-428	**189**
RANG-430	**189**
RANG-532	**189**
RANG-533.7	**189**
RANG-535	**189**
RANG-538	**189**
RANG-540	**189**
RANG-542	**189**
RANG-644.5	**189**
RANG-645	**189**
RANG-648	**189**
RANG-650	**189**
RANG-650.8	**189**
RANG-652	**189**
RANG-655	**189**
RANG-657	**189**
RANR-006	**189**
RANR-008	**189**
RANR-009.5	**189**
RANR-012	**189**
RANR-106	**189**
RANR-106.4	**189**
RANR-110	**189**
RANR-112	**189**
RANR-212.7	**189**
RANR-214	**189**
RANR-215	**189**
RANR-216	**189**
RANR-217.2	**189**
RANR-218	**189**
RANR-320	**189**
RANR-321.3	**189**
RANR-325	**189**
RANR-426.9	**189**
RANR-532	**189**
RANR-533.7	**189**
RANR-538	**189**
RANR-540	**189**
RANR-542	**189**
RANR-644.5	**189**
RANR-650.8	**189**
RANS-540	**190**
RAPAE-6	**187**
RAPE-4	**187**
RAPE-5	**187**
RAPE-6	**187**
RAPG-106	**188**
RAPG-106.4	**188**
RAPG-108	**188**
RAPG-109.5	**188**
RAPG-110	**188**
RAPG-112	**188**
RAPG-212.7	**188**
RAPG-213.5	**188**
RAPG-214	**188**
RAPG-215	**188**
RAPG-216	**188**
RAPG-217.2	**188**
RAPG-218	**188**
RAPG-319	**188**
RAPG-320	**188**
RAPG-321.3	**188**
RAPG-322	**188**
RAPG-323	**188**
RAPG-325	**188**
RAPG-426.9	**188**
RAPG-428	**188**
RAPG-430	**188**
RAPG-532	**188**
RAPG-533.7	**188**
RAPG-535	**188**
RAPG-538	**188**
RAPG-540	**188**
RAPG-542	**188**
RAPG-644.5	**188**
RAPG-645	**188**
RAPG-648	**188**
RAPG-650	**188**
RAPG-650.8	**188**
RAPG-652	**188**
RAPG-655	**188**
RAPG-657	**188**
RAPR-006	**188**
RAPR-006.4	**188**
RAPR-008	**188**
RAPR-009.5	**188**
RAPR-010	**188**
RAPR-012	**188**
RAPR-106	**188**
RAPR-106.4	**188**
RAPR-108	**188**
RAPR-109.5	**188**
RAPR-110	**188**
RAPR-112	**188**
RAPR-212.7	**188**
RAPR-213.5	**188**
RAPR-214	**188**
RAPR-215	**188**
RAPR-216	**188**
RAPR-217.2	**188**
RAPR-218	**188**
RAPR3-006	**186**
RAPR3-006.4	**186**
RAPR3-008	**186**
RAPR3-009.5	**186**
RAPR3-010	**186**
RAPR3-012	**186**
RAPR3-106	**186**
RAPR3-106.4	**186**
RAPR3-108	**186**
RAPR3-109.5	**186**
RAPR3-110	**186**
RAPR3-112	**186**
RAPR-319	**188**
RAPR-320	**188**
RAPR-321.3	**188**
RAPR3-212.7	**186**
RAPR3-213.5	**186**
RAPR3-214	**186**
RAPR3-215	**186**
RAPR3-216	**186**
RAPR3-217.2	**186**
RAPR3-218	**186**
RAPR-322	**188**
RAPR-323	**188**
RAPR-325	**188**
RAPR3-319	**186**
RAPR3-320	**186**
RAPR3-321.3	**186**
RAPR3-322	**186**
RAPR3-323	**186**
RAPR3-325	**186**
RAPR3-426.9	**186**
RAPR3-428	**186**
RAPR3-430	**186**

Code	Page
RAPR3-532	186
RAPR3-533.7	186
RAPR3-535	186
RAPR3-538	186
RAPR3-540	186
RAPR3-542	186
RAPR3-644.5	186
RAPR3-645	186
RAPR3-648	186
RAPR3-650	186
RAPR3-650.8	186
RAPR3-652	186
RAPR3-655	186
RAPR3-657	186
RAPR-426.9	188
RAPR-428	188
RAPR-430	188
RAPR-532	188
RAPR-533.7	188
RAPR-535	188
RAPR-538	188
RAPR-540	188
RAPR-542	188
RAPR-644.5	188
RAPR-645	188
RAPR-648	188
RAPR-650	188
RAPR-650.8	188
RAPR-652	188
RAPR-655	188
RAPR-657	188
RAPS-540	190
RAVG-106	189
RAVG-108	189
RAVG-109.5	189
RAVG-110	189
RAVG-112	189
RAVG-212.7	189
RAVG-213.5	189
RAVG-214	189
RAVG-215	189
RAVG-216	189
RAVG-217.2	189
RAVG-218	189
RAVG-319	189
RAVG-320	189
RAVG-321.3	189
RAVG-322	189
RAVG-323	189
RAVG-325	189
RAVG-426.9	189
RAVG-428	189
RAVG-430	189
RAVG-532	189
RAVG-533.7	189
RAVG-535	189
RAVG-538	189
RAVG-540	189
RAVG-542	189
RAVG-644.5	189
RAVG-645	189
RAVG-648	189
RAVG-650	189
RAVG-650.8	189
RAVG-652	189
RAVG-655	189
RAVG-657	189
RB-11063-UPVC	1101
RB-11075-UPVC	1101
RB-11090-UPVC	1101
RB-1-12	1184
RB-112-1	1184
RB-112-114	1184
RB-112-12	1184
RB-112-34	1184
RB-1-14	1184
RB-114-1	1184
RB-114-12	1184
RB-114-34	1184
RB-12-14	1184
RB-12-18	1184
RB-12-38	1184
RB-125110-UPVC	1101
RB-12575-UPVC	1101
RB-12590-UPVC	1101
RB-1-34	1184
RB-1-38	1184
RB-140110-UPVC	1101
RB-140125-UPVC	1101
RB-14090-UPVC	1101
RB-14-18	1184
RB-160110-UPVC	1101
RB-160125-UPVC	1101
RB-160140-UPVC	1101
RB-180125-UPVC	1101
RB-180140-UPVC	1101
RB-180160-UPVC	1101
RB-200160-UPVC	1101
RB-200180-UPVC	1101
RB-2016-UPVC	1101
RB-2-1	1184
RB-2-112	1184
RB-2-114	1184
RB-212-1	1184
RB-212-112	1184
RB-212-114	1184
RB-212-2	1184
RB-225160-UPVC	1101
RB-225200-UPVC	1101
RB-2-34	1184
RB-2516-UPVC	1101
RB-2520-UPVC	1101
RB30-1121-UPVC	1108
RB30-112-UPVC	1108
RB30-11434-UPVC	1108
RB30-1214-UPVC	1108
RB30-1238-UPVC	1108
RB30-2114-UPVC	1108
RB30-212112-UPVC	1108
RB30-3212-UPVC	1108
RB30-3438-UPVC	1108
RB30-3814-UPVC	1108
RB30-43-UPVC	1108
RB-3-1	1184
RB-3-112	1184
RB-3-2	1184
RB-3-212	1184
RB-3216-UPVC	1101
RB-3220-UPVC	1101
RB-3225-UPVC	1101
RB-34-12	1184
RB-34-14	1184
RB-34-18	1184
RB-34-38	1184
RB-38-14	1184
RB-38-18	1184
RB-4020-UPVC	1101
RB-4025-UPVC	1101
RB-4032-UPVC	1101
RB-4-3	1184
RB-5025-UPVC	1101
RB-5032-UPVC	1101
RB-5040-UPVC	1101
RB-6325-UPVC	1101
RB-6332-UPVC	1101
RB-6340-UPVC	1101
RB-6350-UPVC	1101
RB-7532-UPVC	1101
RB-7540-UPVC	1101
RB-7550-UPVC	1101
RB-7563-UPVC	1101
RB-9050-UPVC	1101
RB-9063-UPVC	1101
RB-9075-UPVC	1101
RB93-112114-ABS	1097
RB93-112114-UPVC	1108
RB93-1121-ABS	1097
RB93-1121-UPVC	1108
RB93-11234-ABS	1097
RB93-11234-UPVC	1108
RB93-112-ABS	1097
RB93-112-UPVC	1108
RB93-11412-ABS	1097
RB93-11412-UPVC	1108
RB93-1141-ABS	1097
RB93-1141-UPVC	1108
RB93-11434-ABS	1097
RB93-11434-UPVC	1108
RB93-134-ABS	1097
RB93-134-UPVC	1108
RB93-2112-ABS	1097
RB93-2112-UPVC	1108
RB93-2114-ABS	1097
RB93-2114-UPVC	1108
RB93-212112-UPVC	1108
RB93-2122-ABS	1097
RB93-2122-UPVC	1108
RB93-21-ABS	1097
RB93-21-UPVC	1108
RB93-3112-ABS	1097
RB93-3112-UPVC	1108
RB93-3212-ABS	1097
RB93-3212-UPVC	1108
RB93-32-ABS	1097
RB93-32-UPVC	1108
RB93-3412-ABS	1097
RB93-3412-UPVC	1108
RB93-4212-ABS	1097
RB93-4212-UPVC	1108
RB93-42-ABS	1097
RB93-42-UPVC	1108
RB93-43-ABS	1097
RB93-43-UPVC	1108
RB93-53-UPVC	1108
RB93-54-ABS	1097
RB93-54-UPVC	1108
RB93-64-UPVC	1108
RB93-86-UPVC	1108
RBNG-106	193
RBNG-106.4	193
RBNG-108	193
RBNG-109.5	193
RBNG-110	193
RBNG-112	193
RBNG-212.7	193
RBNG-213.5	193
RBNG-214	193
RBNG-215	193
RBNG-216	193
RBNG-217.2	193
RBNG-218	193
RBNG-319	193
RBNG-320	193
RBNG-321.3	193
RBNG-322	193
RBNG-325	193
RBNG-426.9	193
RBNG-428	193
RBNG-430	193
RBNG-532	193
RBNG-533.7	193
RBNG-535	193
RBNG-538	193
RBNG-542	193
RBNR-106.4	193
RBNR-109.5	193
RBNR-212.7	193
RBNR-213.5	193
RBNR-214	193
RBNR-215	193
RBNR-218	193
RBNR-320	193
RBNR-322	193
RBNR-325	193
RBNR-428	193
RBNR-533.7	193
RBNR-535	193
RBPG-106	193
RBPG-106.4	193
RBPG-108	193
RBPG-109.5	193
RBPG-110	193
RBPG-112	193
RBPG-212.7	193
RBPG-213.5	193
RBPG-214	193
RBPG-215	193
RBPG-216	193
RBPG-217.2	193
RBPG-218	193
RBPG-319	193
RBPG-320	193
RBPG-321.3	193
RBPG-322	193
RBPG-325	193
RBPG-426.9	193
RBPG-428	193
RBPG-430	193
RBPG-532	193
RBPG-533.7	193
RBPG-535	193
RBPG-538	193
RBPG-540	193
RBPG-542	193
RBPR-106	193
RBPR-106.4	193
RBPR-108	193
RBPR-109.5	193
RBPR-110	193
RBPR1-106	186
RBPR1-106.4	186
RBPR1-108	186
RBPR1-109.5	186
RBPR1-110	186
RBPR1-112	186
RBPR-112	193
RBPR1-212.7	186
RBPR1-213.5	186
RBPR1-214	186
RBPR1-215	186
RBPR1-216	186
RBPR1-217.2	186
RBPR1-218	186
RBPR1-319	186
RBPR1-320	186
RBPR1-321.3	186
RBPR1-322	186
RBPR1-325	186
RBPR1-426.9	186
RBPR1-428	186
RBPR1-430	186
RBPR1-532	186
RBPR1-533.7	186
RBPR1-535	186
RBPR1-538	186
RBPR1-540	186
RBPR1-542	186
RBPR-212.7	193
RBPR-213.5	193
RBPR-214	193
RBPR-215	193
RBPR-216	193
RBPR-217.2	193
RBPR-218	193
RBPR-319	193
RBPR-320	193
RBPR-321.3	193
RBPR-322	193
RBPR-325	193
RBPR-426.9	193
RBPR-428	193
RBPR-430	193
RBPR-532	193
RBPR-533.7	193
RBPR-535	193
RBPR-538	193
RBPR-540	193
RBPR-542	193
RBT-PN16-10EPDM	1388
RBT-PN16-10NBR	1388
RBT-PN16-112EPDM	1388
RBT-PN16-112NBR	1388
RBT-PN16-114EPDM	1388
RBT-PN16-114NBR	1388
RBT-PN16-12EPDM	1388
RBT-PN16-12NBR	1388
RBT-PN16-212EPDM	1388
RBT-PN16-212NBR	1388
RBT-PN16-2EPDM	1388
RBT-PN16-2NBR	1388
RBT-PN16-3EPDM	1388
RBT-PN16-3NBR	1388
RBT-PN16-4EPDM	1388
RBT-PN16-4NBR	1388
RBT-PN16-5EPDM	1388
RBT-PN16-5NBR	1388
RBT-PN16-6EPDM	1388
RBT-PN16-6NBR	1388
RBT-PN16-8EPDM	1388
RBT-PN16-8NBR	1388

Code	Page
RBU-250-125	170
RBU-375-250	170
RBU-500-250	170
RBVG-106	194
RBVG-106.4	194
RBVG-108	194
RBVG-109.5	194
RBVG-110	194
RBVG-112	194
RBVG-212.7	194
RBVG-213.5	194
RBVG-214	194
RBVG-215	194
RBVG-216	194
RBVG-217.2	194
RBVG-218	194
RBVG-319	194
RBVG-320	194
RBVG-321.3	194
RBVG-322	194
RBVG-325	194
RBVG-426.9	194
RBVG-428	194
RBVG-430	194
RBVG-532	194
RBVG-533.7	194
RBVG-535	194
RBVG-538	194
RBVG-542	194
RC-1	1185
RC-112	1185
RC-114	1185
RC-12	1185
RC-14	1185
RC-18	1185
RC-2	1185
RC-212	1185
RC-3	1185
RC-34	1185
RC-38	1185
RCAR-110	195
RCAR-220	195
RCAR-221.3	195
RCAR-222	195
RCAR-226.9	195
RCAR-230	195
RCAR-330	195
RCAR-332	195
RCAR-333.7	195
RCAR-338	195
RCAR-340	195
RCAR-448.3	195
RCAR-450	195
RCAR-455	195
RCAR-460.3	195
RCAR-470	195
RCG205CTW00	1053
RCG205STW00	1053
RCG206CTX00	1053
RCG206STX00	1053
RCG207CTY00	1053
RCG207STY00	1053
RCG208STZ00	1053
RCG209STK00	1053
RCG210STJ00	1053
RCNR-106	195
RCNR-108	195
RCNR-110	195
RCNR-112	195
RCNR-112.7	195
RCNR-113.5	195
RCNR-114	195
RCNR-115	195
RCNR-116	195
RCNR-117.2	195
RCNR-118	195
RCNR-220	195
RCNR-221.3	195
RCNR-222	195
RCNR-223	195
RCNR-225	195
RCNR-226.9	195
RCNR-228	195
RCNR-230	195
RCNR-330	195
RCNR-332	195
RCNR-333.7	195
RCNR-335	195
RCNR-338	195
RCNR-340	195
RCNR-342	195
RCNR-438	195
RCNR-440	195
RCNR-442	195
RCNR-445	195
RCNR-448.3	195
RCNR-450	195
RCNR-451	195
RCNR-452	195
RCNR-455	195
RCNR-457	195
RCNR-460.3	195
RCNR-463	195
RCNR-465	195
RCNR-470	195
RCNR-570	195
RCNR-573	195
RCNR-575	195
RCNR-576.1	195
RCNR-580	195
RCNR-582.5	195
RCNR-588.9	195
RCNR-590	195
RCPE-2	187
RCPE-3	187
RCPE-4	187
RCPE-5	187
RCPG-106	196
RCPG-108	196
RCPG-110	196
RCPG-112	196
RCPG-112.7	196
RCPG-114	196
RCPG-115	196
RCPG-116	196
RCPG-117.2	196
RCPG-118	196
RCPG-219	196
RCPG-220	196
RCPG-221.3	196
RCPG-222	196
RCPG-225	196
RCPG-226.9	196
RCPG-230	196
RCPG-330	196
RCPG-332	196
RCPG-333.7	196
RCPG-335	196
RCPG-338	196
RCPG-340	196
RCPG-342	196
RCPG-438	196
RCPG-440	196
RCPG-442	196
RCPG-445	196
RCPG-448.3	196
RCPG-450	196
RCPG-452	196
RCPG-455	196
RCPG-457	196
RCPG-460.3	196
RCPG-465	196
RCPG-470	196
RCPG-560.3	196
RCPG-573	196
RCPG-576.1	196
RCPG-580	196
RCPG-588.9	196
RCPG-6100	196
RCPG-6101.6	196
RCPG-6114.3	196
RCPG-7108	196
RCPG-7168.3	196
RCPG-8168.3	196
RCPR-106	195
RCPR-108	195
RCPR-110	195
RCPR-112	195
RCPR-112.7	195
RCPR-113.5	195
RCPR-114	195
RCPR-115	195
RCPR-116	195
RCPR-117.2	195
RCPR-118	195
RCPR-219	195
RCPR-220	195
RCPR-221.3	195
RCPR-222	195
RCPR-223	195
RCPR-225	195
RCPR-226.9	195
RCPR-228	195
RCPR-230	195
RCPR3-106	186
RCPR3-108	186
RCPR3-110	186
RCPR3-112	186
RCPR3-112.7	186
RCPR3-113.5	186
RCPR3-114	186
RCPR3-115	186
RCPR3-116	186
RCPR3-117.2	186
RCPR3-118	186
RCPR3-219	186
RCPR3-220	186
RCPR3-221.3	186
RCPR3-222	186
RCPR3-223	186
RCPR3-225	186
RCPR3-226.9	186
RCPR3-228	186
RCPR3-230	186
RCPR-330	195
RCPR-332	195
RCPR-333.7	195
RCPR3-330	186
RCPR3-332	186
RCPR3-333.7	186
RCPR3-335	186
RCPR3-338	186
RCPR3-340	186
RCPR3-342	186
RCPR-335	195
RCPR-338	195
RCPR-340	195
RCPR-342	195
RCPR3-438	186
RCPR3-440	186
RCPR3-442	186
RCPR3-445	186
RCPR3-448.3	186
RCPR3-450	186
RCPR3-451	186
RCPR3-452	186
RCPR3-455	186
RCPR3-457	186
RCPR3-460.3	186
RCPR3-463	186
RCPR3-465	186
RCPR3-470	186
RCPR3-570	186
RCPR3-573	186
RCPR3-575	186
RCPR3-576.1	186
RCPR3-580	186
RCPR3-582.5	186
RCPR3-588.9	186
RCPR3-590	186
RCPR3-6101.6	186
RCPR3-6114.3	186
RCPR3-6127	186
RCPR3-7130	186
RCPR3-7140	186
RCPR3-7168.3	186
RCPR-438	195
RCPR-440	195
RCPR-442	195
RCPR-445	195
RCPR-448.3	195
RCPR-450	195
RCPR-451	195
RCPR-452	195
RCPR-455	195
RCPR-457	195
RCPR-460.3	195
RCPR-463	195
RCPR-465	195
RCPR-470	195
RCPR-570	195
RCPR-573	195
RCPR-575	195
RCPR-576.1	195
RCPR-580	195
RCPR-582.5	195
RCPR-588.9	195
RCPR-590	195
RCPR-6101.6	195
RCPR-6114.3	195
RCPR-6127	195
RCPR-7130	195
RCPR-7140	195
RCPR-7168.3	195
RD-10S	158
RD12.A	432
RD-12S	158
RD-14S	158
RD-16S	158
RD18.A	432
RD-20S	158
RD25.A	432
RD-25S	158
RD-30S	158
RD32.A	432
RD-38S	158
RD43.A	432
RD52.A	432
RD6.A	432
RD63.A	432
RD-6S	158
RD80.A	432
RD-8S	158
RD9.A	432
RDC12-14	1207
RDC12-38	1207
RDC12-516	1207
RDC14-18	1207
RDC14-316	1207
RDC316-18	1207
RDC38-14	1207
RDC38-516	1207
RDC516-14	1207
RDC516-316	1207
RED-DKOL-08/06	162
RED-DKOL-10/06	162
RED-DKOL-10/08	162
RED-DKOL-12/06	162
RED-DKOL-12/08	162
RED-DKOL-12/10	162
RED-DKOL-15/06	162
RED-DKOL-15/08	162
RED-DKOL-15/10	162
RED-DKOL-15/12	162
RED-DKOL-18/06	162
RED-DKOL-18/08	162
RED-DKOL-18/10	162
RED-DKOL-18/12	162
RED-DKOL-18/15	162
RED-DKOL-22/06	162
RED-DKOL-22/08	162
RED-DKOL-22/10	162
RED-DKOL-22/12	162
RED-DKOL-22/15	162
RED-DKOL-22/18	162
RED-DKOL-28/06	162
RED-DKOL-28/08	162
RED-DKOL-28/10	162
RED-DKOL-28/12	162
RED-DKOL-28/15	162
RED-DKOL-28/18	162
RED-DKOL-28/22	162
RED-DKOL-35/06	162
RED-DKOL-35/08	162
RED-DKOL-35/10	162
RED-DKOL-35/12	162
RED-DKOL-35/15	162
RED-DKOL-35/18	162
RED-DKOL-35/22	162
RED-DKOL-35/28	162

Code	Page
RED-DKOL-42/06	162
RED-DKOL-42/08	162
RED-DKOL-42/10	162
RED-DKOL-42/12	162
RED-DKOL-42/15	162
RED-DKOL-42/18	162
RED-DKOL-42/22	162
RED-DKOL-42/28	162
RED-DKOL-42/35	162
RED-DKOS-08/06	162
RED-DKOS-10/06	162
RED-DKOS-10/08	162
RED-DKOS-12/06	162
RED-DKOS-12/08	162
RED-DKOS-12/10	162
RED-DKOS-14/06	162
RED-DKOS-14/08	162
RED-DKOS-14/10	162
RED-DKOS-14/12	162
RED-DKOS-16/06	162
RED-DKOS-16/08	162
RED-DKOS-16/10	162
RED-DKOS-16/12	162
RED-DKOS-16/14	162
RED-DKOS-20/06	162
RED-DKOS-20/08	162
RED-DKOS-20/10	162
RED-DKOS-20/12	162
RED-DKOS-20/14	162
RED-DKOS-20/16	162
RED-DKOS-25/06	162
RED-DKOS-25/08	162
RED-DKOS-25/10	162
RED-DKOS-25/12	162
RED-DKOS-25/14	162
RED-DKOS-25/16	162
RED-DKOS-25/20	162
RED-DKOS-30/06	162
RED-DKOS-30/08	162
RED-DKOS-30/10	162
RED-DKOS-30/12	162
RED-DKOS-30/14	162
RED-DKOS-30/16	162
RED-DKOS-30/20	162
RED-DKOS-30/25	162
RED-DKOS-38/06	162
RED-DKOS-38/08	162
RED-DKOS-38/10	162
RED-DKOS-38/12	162
RED-DKOS-38/14	162
RED-DKOS-38/16	162
RED-DKOS-38/20	162
RED-DKOS-38/25	162
RED-DKOS-38/30	162
REDR1/2X1	122
REDR1/2X1/4	122
REDR1/2X1/8	122
REDR1/2X3/4	122
REDR1/2X3/8	122
REDR1/4X1/2	122
REDR1/4X1/8	122
REDR1/4X3/4	122
REDR1/4X3/8	122
REDR1/8X1/4	122
REDR1/8X3/8	122
REDR11/2X1	122
REDR11/2X1/2	122
REDR11/2X11/4	122
REDR11/2X3/4	122
REDR11/4X1	122
REDR11/4X1/2	122
REDR11/4X11/2	122
REDR11/4X3/4	122
REDR1X1/2	122
REDR1X1/4	122
REDR1X11/2	122
REDR1X11/4	122
REDR1X3/4	122
REDR1X3/8	122
REDR3/4X1	122
REDR3/4X1/2	122
REDR3/4X1/4	122
REDR3/4X11/2	122
REDR3/4X11/4	122
REDR3/4X3/8	122
REDR3/8X1/2	122
REDR3/8X1/4	122
REDR3/8X1/8	122
REDR3/8X3/4	122
REDVDN10/6L	131
REDVDN10/6S	131
REDVDN10/8L	131
REDVDN10/8S	131
REDVDN12/10L	131
REDVDN12/10S	131
REDVDN12/6L	131
REDVDN12/6S	131
REDVDN12/8L	131
REDVDN12/8S	131
REDVDN14/10S	131
REDVDN14/12S	131
REDVDN14/6S	131
REDVDN14/8S	131
REDVDN15/10L	131
REDVDN15/12L	131
REDVDN15/6L	131
REDVDN15/8L	131
REDVDN16/10S	131
REDVDN16/12S	131
REDVDN16/14S	131
REDVDN16/6S	131
REDVDN16/8S	131
REDVDN18/10L	131
REDVDN18/12L	131
REDVDN18/15L	131
REDVDN18/6L	131
REDVDN18/8L	131
REDVDN20/10S	131
REDVDN20/12S	131
REDVDN20/14S	131
REDVDN20/16S	131
REDVDN20/6S	131
REDVDN20/8S	131
REDVDN22/10L	131
REDVDN22/12L	131
REDVDN22/15L	131
REDVDN22/18L	131
REDVDN22/8L	131
REDVDN25/10S	131
REDVDN25/12S	131
REDVDN25/14S	131
REDVDN25/16S	131
REDVDN25/20S	131
REDVDN25/8S	131
REDVDN28/10L	131
REDVDN28/12L	131
REDVDN28/15L	131
REDVDN28/18L	131
REDVDN28/22L	131
REDVDN30/12S	131
REDVDN30/14S	131
REDVDN30/16S	131
REDVDN30/20S	131
REDVDN30/25S	131
REDVDN35/15L	131
REDVDN35/18L	131
REDVDN35/22L	131
REDVDN35/28L	131
REDVDN38/10S	131
REDVDN38/16S	131
REDVDN38/20S	131
REDVDN38/25S	131
REDVDN38/30S	131
REDVDN42/15L	131
REDVDN42/18L	131
REDVDN42/22L	131
REDVDN42/35L	131
REDVDN8/6L	131
REDVDN8/6S	131
REDWASH-GUN	1657
REDWV10L-6L	123
REDWV10L-8L	123
REDWV10S-6S	123
REDWV10S-8S	123
REDWV12L-10L	123
REDWV12L-6L	123
REDWV12L-8L	123
REDWV12S-10S	123
REDWV12S-6S	123
REDWV12S-8S	123
REDWV14S-10S	123
REDWV14S-12S	123
REDWV14S-6S	123
REDWV14S-8S	123
REDWV15L-10L	123
REDWV15L-12L	123
REDWV15L-6L	123
REDWV15L-8L	123
REDWV16S-10S	123
REDWV16S-12S	123
REDWV16S-14S	123
REDWV16S-6S	123
REDWV16S-8S	123
REDWV18L-10L	123
REDWV18L-12L	123
REDWV18L-15L	123
REDWV18L-6L	123
REDWV18L-8L	123
REDWV20S-10S	123
REDWV20S-12S	123
REDWV20S-14S	123
REDWV20S-16S	123
REDWV20S-6S	123
REDWV20S-8S	123
REDWV22L-10L	123
REDWV22L-12L	123
REDWV22L-15L	123
REDWV22L-18L	123
REDWV22L-8L	123
REDWV25S-10S	123
REDWV25S-12S	123
REDWV25S-14S	123
REDWV25S-16S	123
REDWV25S-20S	123
REDWV25S-8S	123
REDWV28L-10L	123
REDWV28L-12L	123
REDWV28L-15L	123
REDWV28L-18L	123
REDWV28L-22L	123
REDWV30S-12S	123
REDWV30S-14S	123
REDWV30S-16S	123
REDWV30S-20S	123
REDWV30S-25S	123
REDWV35-28L	123
REDWV35L-15L	123
REDWV35L-18L	123
REDWV35L-22L	123
REDWV38S-10S	123
REDWV38S-16S	123
REDWV38S-20S	123
REDWV38S-25S	123
REDWV38S-30S	123
REDWV42L-15L	123
REDWV42L-18L	123
REDWV42L-22L	123
REDWV42L-35L	123
REDWV8L-6L	123
REDWV8S-6S	123
REFBKY50	1588
REFRW50	1588
RF104	1606
RFO 344	636
RFO 346	636
RFO 352	636
RFO 382	636
RFO 383	636
RFS-12P-2-SUS304	442
RFU 429	636
RFU 444	636
RFU 446	636
RFU 452	636
RFU 482	636
RFU 483	636
RGN-1/2-DN10	34
RGN-1/2-DN12	34
RGN-1/4-DN06	34
RGN-10-DN06	34
RGN-10-DN08	34
RGN-12-DN06	34
RGN-12-DN08	34
RGN-14-DN06	34
RGN-14-DN08	34
RGN-14-DN10	34
RGN-16-DN08	34
RGN-16-DN10	34
RGN-16-DN12	34
RGN-18-DN10	34
RGN-18-DN12	34
RGN-22-DN12	34
RGN-22-DN16	34
RGN-26-DN19	34
RH-1	1416
RH-112	1416
RH-114	1416
RH-118	1416
RH-1316	1416
RH-134	1416
RH-138	1416
RH-158	1416
RH-178	1416
RH-1916	1416
RH-2	1416
RH-212	1416
RH-214	1416
RH-238	1416
RH-3	1416
RH-4	1416
RH-78	1416
RHN-1-12	1185
RHN-112-1	1185
RHN-112-114	1185
RHN-112-12	1185
RHN-112-34	1185
RHN-1-14	1185
RHN-114-1	1185
RHN-114-12	1185
RHN-114-34	1185
RHN-12-14	1185
RHN-12-18	1185
RHN-12-38	1185
RHN-1-34	1185
RHN-1-38	1185
RHN-14-18	1185
RHN-2-1	1185
RHN-2-112	1185
RHN-2-114	1185
RHN-2-12	1185
RHN-2-34	1185
RHN-3-2	1185
RHN-34-12	1185
RHN-34-14	1185
RHN-34-18	1185
RHN-34-38	1185
RHN-38-14	1185
RHN-38-18	1185
RHO-FIG-170300-1	436
RHO-FIG-170300-2	436
RHO-FIG-170305-1	436
RHO-FIG-170305-2	436
RHO-FIG-170310-1	436
RHO-FIG-170310-2	436
RHO-FIG-170315-1	436
RHO-FIG-170315-2	436
RHO-FIG-170320-1	436
RHO-FIG-170320-2	436
RHO-FIG-176600-1	436
RHO-FIG-176600-2	436
RHO-FIG-176605-1	436
RHO-FIG-176610-1	436
RHO-FIG-176610-2	436
RHO-FIG-176615-1	436
RHO-FIG-176615-2	436
RHO-FIG-176615-3	436
RHO-FIG-176620-1	436
RHO-FIG-176620-2	436
RHO-FIS-140300-1	436
RHO-FIS-140305-1	436
RHO-FIS-140305-2	436
RHO-FIS-140310-1	436
RHO-FIS-140310-2	436
RHO-FIS-140315-1	436
RHO-FIS-140320-1	436
RHO-FIS-146410-1	436
RHO-FIS-146510-1	436
RHO-FIS-146510-2	436
RHO-FIS-146515-2	436
RJ-14	1224
RJTA1	1194

Code	Page
RJTA112	1194
RJTA3	1194
RJTBL1	1194
RJTBL112	1194
RJTBL2	1194
RJTBL212	1194
RJTBL3	1194
RJTD2	1194
RJTHL1	1194
RJTHL112	1194
RJTHL2	1194
RJTHL212	1194
RJTHL3	1194
RJTN1	1194
RJTN112	1194
RJTN2	1194
RJTN3	1194
RJTRWL2112	1194
RJTS1	1194
RJTS112	1194
RJTS2	1194
RJTS3	1194
RJT-SPANNER-1.0	1192
RJT-SPANNER-1.5	1192
RJT-SPANNER-2	1192
RJT-SPANNER-2.5	1192
RJT-SPANNER-3	1192
RJT-SPANNER-4	1192
RJTWL1	1194
RJTWL112	1194
RJTWL2	1194
RJTWL212	1194
RJTWL3	1194
RJTWM1	1194
RJTWM112	1194
RJTWM2	1194
RJTWM3	1194
RK05/10	1172
RK05/10K	1172
RK05/13	1172
RK10/13	1172
RK10/13K	1172
RK10/17	1172
RK10/17K	1172
RK10/21	1172
RK10/21K	1172
RK13/17	1172
RK13/17K	1172
RK13/21	1172
RK13/21K	1172
RK13/26	1172
RK13/26K	1172
RK13/33K	1172
RK17/21	1172
RK17/21K	1172
RK17/26	1172
RK17/26K	1172
RK17/33	1172
RK17/33K	1172
RK1C	883
RK21/26	1172
RK21/26K	1172
RK21/33	1172
RK21/33K	1172
RK21/42K	1172
RK26/33	1172
RK26/33K	1172
RK26/42K	1172
RK33/42	1172
RK33/42K	1172
RK33/50K	1172
RK33/55K	1172
RK42/50	1172
RK42/55	1172
RK42/55K	1172
RK50/55	1172
RK50/55K	1172
RL05/05	1171
RL05/05X	1171
RL05/10	1171
RL10/10	1171
RL10/10K	1171
RL10/10KN	1171
RL10/10N	1171
RL10/10X	1171
RL10/10Y	1171
RL10/13	1171
RL10/13K	1171
RL10/17	1171
RL10/17K	1171
RL13/13	1171
RL13/13K	1171
RL13/13KN	1171
RL13/13N	1171
RL13/13X	1171
RL13/13Y	1171
RL13/17	1171
RL13/17K	1171
RL13/21	1171
RL13/21K	1171
RL17/17	1171
RL17/17K	1171
RL17/17KN	1171
RL17/17N	1171
RL17/17X	1171
RL17/21	1171
RL17/21K	1171
RL17/26	1171
RL17/26K	1171
RL21/21	1171
RL21/21K	1171
RL21/21N	1171
RL21/21X	1171
RL21/26	1171
RL21/26K	1171
RL21/33	1171
RL21/33K	1171
RL26/26	1171
RL26/26K	1171
RL26/26X	1171
RL26/33	1171
RL26/33K	1171
RL33/33	1171
RL33/33K	1171
RL33/33X	1171
RLC125/130	1548
RLC148/152	1548
RLD-12	255
RLD-16	255
RLD-20	255
RLD-24	255
RLD-32	255
RLD-40	255
RLD-48	255
RLP-16	198
RLP-22	198
RM/28010/M/10	474
RM/28010/M/25	474
RM/28010/M/50	474
RM/28020/M/10	474
RM/28020/M/25	474
RM/28020/M/50	474
RM/28025/M/10	474
RM/28025/M/25	474
RM/28025/M/50	474
RM/8010/M/100	474
RM/8010/M/25	474
RM/8010/M/50	474
RM/8010/M/80	474
RM/8012/M/25	474
RM/8012/M/50	474
RM/8016/M/100	474
RM/8016/M/25	474
RM/8016/M/50	474
RM/8020/M/100	474
RM/8020/M/25	474
RM/8020/M/50	474
RM/8020/M/80	474
RM/8025/M/100	474
RM/8025/M/25	474
RM/8025/M/50	474
RM/8025/M/80	474
RM/91032/M/25	534
RM/91040/M/25	534
RM/92012/M/10	534
RM/92016/M/10	534
RM/92016/M/15	534
RM/92016/M/20	534
RM/92020/M/10	534
RM/92020/M/15	534
RM/92020/M/25	534
RM/92020/M/30	534
RM/92020/M/40	534
RM/92020/M/50	534
RM/92025/M/10	534
RM/92025/M/20	534
RM/92025/M/25	534
RM/92025/M/30	534
RM/92025/M/40	534
RM/92025/M/50	534
RM/92032/M/10	534
RM/92032/M/15	534
RM/92032/M/20	534
RM/92032/M/25	534
RM/92032/M/30	534
RM/92032/M/40	534
RM/92032/M/50	534
RM/92032/M/60	534
RM/92032/M/80	534
RM/92040/M/10	534
RM/92040/M/20	534
RM/92040/M/25	534
RM/92040/M/30	534
RM/92040/M/5	534
RM/92040/M/50	534
RM/92050/M/10	534
RM/92050/M/100	534
RM/92050/M/20	534
RM/92050/M/25	534
RM/92050/M/30	534
RM/92050/M/40	534
RM/92050/M/50	534
RM/92063/M/15	534
RM/92063/M/25	534
RM/92063/M/40	534
RM/92080/M/25	534
RM/92080/M/40	534
RM/92080/M/50	534
RM/92080/M/60	534
RM/92080/M/80	534
RM/92100/M/30	534
RM/92100/M/50	534
RM/925/100	506
RM/925/150	506
RM/925/75	506
RM/930/100	506
RM/930/150	506
RM/930/300	506
RM/930/75	506
RM/940/100	506
RM/940/150	506
RM/940/300	506
RM010411	836
RM0104M5	836
RM010511	836
RM010512	836
RM010611	836
RM010612	836
RM0106M5	836
RM010811	836
RM010812	836
RM010813	836
RM011012	836
RM011013	836
RM011014	836
RM011213	836
RM011214	836
RM050411	837
RM050412	837
RM0504M5	837
RM050512	837
RM050611	837
RM050612	837
RM0506M5	837
RM051013	837
RM051014	837
RM051213	837
RM070612	837
RM090412	838
RM0904M5	838
RM0905M5	838
RM090611	838
RM090612	838
RM0906M5	838
RM090811	838
RM090812	838
RM091013	838
RM091213	838
RM091214	838
RM100611	839
RM100612	839
RM150411E	838
RM150511E	838
RM150811E	838
RM151013E	838
RM151214E	838
RM1611	838
RM1614	838
RM1711	838
RM1712	838
RM1713	838
RM1714	838
RM2306E	837
RM2308E	837
RON-106	200
RON-106.4	200
RON-108	200
RON-208	200
RON-209.5	200
RON-210	200
RON-212	200
RON-212.7	200
RON-312	200
RON-312.7	200
RON-313.5	200
RON-314	200
RON-315	200
RON-316	200
RON-414	200
RON-415	200
RON-416	200
RON-417.2	200
RON-418	200
RON-419	200
RON-420	200
RON-421.3	200
RON-422	200
ROND-106	200
ROND-106.4	200
ROND-108	200
ROND-208	200
ROND-209.5	200
ROND-210	200
ROND-212	200
ROND-212.7	200
ROND-310	200
ROND-312	200
ROND-312.7	200
ROND-313.5	200
ROND-314	200
ROND-315	200
ROND-316	200
ROND-414	200
ROND-415	200
ROND-416	200
ROND-417.2	200
ROND-418	200
ROND-419	200
ROND-420	200
ROND-421.3	200
ROND-422	200
ROP-106	200
ROP-106.4	200
ROP-108	200
ROP-208	200
ROP-209.5	200
ROP-210	200
ROP-212	200
ROP-212.7	200
ROP-310	200
ROP-312	200
ROP-312.7	200
ROP-313.5	200
ROP-314	200
ROP-315	200
ROP-316	200
ROP-415	200
ROP-416	200
ROP-417.2	200
ROP-418	200

Code	Page
ROP-419	200
ROP-420	200
ROP-421.3	200
ROP-422	200
ROPD-106	200
ROPD-106.4	200
ROPD-108	200
ROPD-208	200
ROPD-209.5	200
ROPD-210	200
ROPD-212	200
ROPD-212.7	200
ROPD-310	200
ROPD-312	200
ROPD-312.7	200
ROPD-313.5	200
ROPD-314	200
ROPD-315	200
ROPD-316	200
ROPD-414	200
ROPD-415	200
ROPD-416	200
ROPD-417.2	200
ROPD-418	200
ROPD-419	200
ROPD-420	200
ROPD-421.3	200
ROPD-422	200
ROV-10L	158
ROV-10S	158
ROV-12L	158
ROV-12S	158
ROV-14S	158
ROV-15L	158
ROV-16S	158
ROV-18L	158
ROV-20S	158
ROV-22L	158
ROV-25S	158
ROV-28L	158
ROV-30S	158
ROV-35L	158
ROV-38S	158
ROV-42L	158
ROV-6L	158
ROV-6S	158
ROV-8L	158
ROV-8S	158
RPC-1000-500	171
RPC-1000-750	171
RPC-10-6	177
RPC-10-8	177
RPC-12-10	177
RPC-12-6	177
RPC-12-8	177
RPC-16-12	177
RPC-250-125	171
RPC-375-125	171
RPC-375-250	171
RPC-500-250	171
RPC-6-3	177
RPC-750-500	171
RPC-8-6	177
RPG205CTW00	1052
RPG205STW00	1052
RPG206CTX00	1052
RPG206STX00	1052
RPG207STY00	1052
RPG208STZ00	1052
RPG209STK00	1052
RPG210STJ00	1052
RPVC1	1404
RPVC1-100	1405
RPVC112	1404
RPVC112-15	1404
RPVC114	1404
RPVC114-15	1404
RPVC12	1404
RPVC12-100	1405
RPVC12-15	1404
RPVC12B	1404
RPVC12B-100	1405
RPVC12G	1404
RPVC12N	1404
RPVC12N-100	1405
RPVC12R	1404
RPVC12R-100	1405
RPVC12Y	1404
RPVC12Y-100	1405
RPVC14	1404
RPVC14-100	1405
RPVC14B	1404
RPVC14B-100	1405
RPVC14G	1404
RPVC14G-100	1405
RPVC14N	1404
RPVC14N-100	1405
RPVC14R	1404
RPVC14R-100	1405
RPVC14Y	1404
RPVC14Y-100	1405
RPVC1N	1404
RPVC2	1404
RPVC2-15	1404
RPVC316	1404
RPVC316N	1404
RPVC34	1404
RPVC34-100	1405
RPVC34-15	1404
RPVC34B	1404
RPVC34N	1404
RPVC34R	1404
RPVC38	1404
RPVC38-100	1405
RPVC38B	1404
RPVC38B-100	1405
RPVC38G	1404
RPVC38N	1404
RPVC38N-100	1405
RPVC38R	1404
RPVC38R-100	1405
RPVC38Y	1404
RPVC38Y-100	1405
RPVC516	1404
RPVC516-100	1405
RPVC516B	1404
RPVC516B-100	1405
RPVC516G	1404
RPVC516N	1404
RPVC516N-100	1405
RPVC516R	1404
RPVC516R-100	1405
RPVC58	1404
RPVC58N	1404
RS-12	630
RS13-112112-UPVC	1108
RS13-112114-ABS	1097
RS13-1141-ABS	1097
RS13-1141-UPVC	1108
RS13-134-ABS	1097
RS13-134-UPVC	1108
RS13-2112-ABS	1097
RS13-2112-UPVC	1108
RS13-2122-UPVC	1108
RS13-3212-ABS	1097
RS13-3212-UPVC	1108
RS13-3412-ABS	1097
RS13-3412-UPVC	1108
RS13-43-ABS	1097
RS13-43-UPVC	1108
RS-14	630
RS-18	630
RS-38	630
RSG-10	48
RSG-12	48
RSG-16	48
RSG-20	48
RSG-25	48
RSG-32	48
RSG-42	48
RSG-50	48
RSG-60	48
RSH-1	1482
RSH-3/4	1482
RSJN-2-045	1674
RSJN-2-050	1674
RSJN-2-055	1674
RSJN-4-045	1674
RSJN-4-050	1674
RSJN-4-055	1674
RSJN-6-045	1674
RSJN-6-050	1674
RSMC16	460
RSMC20	460
RSMC25	460
RSO-11050-UPVC	1101
RSO-11063-UPVC	1101
RSO-11075-UPVC	1101
RSO-11090-UPVC	1101
RSO-125110-UPVC	1101
RSO-12590-UPVC	1101
RSO-140110-UPVC	1101
RSO-140125-UPVC	1101
RSO-14090-UPVC	1101
RSO-160110-UPVC	1101
RSO-160140-UPVC	1101
RSO-2016-UPVC	1101
RSO-2516-UPVC	1101
RSO-2520-UPVC	1101
RSO-3220-UPVC	1101
RSO-3225-UPVC	1101
RSO-4020-UPVC	1101
RSO-4025-UPVC	1101
RSO-4032-UPVC	1101
RSO-5025-UPVC	1101
RSO-5032-UPVC	1101
RSO-5040-UPVC	1101
RSO-6340-UPVC	1101
RSO-6350-UPVC	1101
RSO-7540-UPVC	1101
RSO-7550-UPVC	1101
RSO-7563-UPVC	1101
RSO-9040-UPVC	1101
RSO-9050-UPVC	1101
RSO-9063-UPVC	1101
RSO-9075-UPVC	1101
RSWV10LM	126
RSWV10LR	126
RSWV10SM	126
RSWV10SR	126
RSWV12LM	126
RSWV12LM18X1.5	126
RSWV12LR	126
RSWV12SM	126
RSWV12SR	126
RSWV14SM	126
RSWV14SR	126
RSWV15LM	126
RSWV15LR	126
RSWV16SM	126
RSWV16SR	126
RSWV18LM	126
RSWV18LR	126
RSWV20SM	126
RSWV20SR	126
RSWV22LM	126
RSWV22LR	126
RSWV25SM	126
RSWV25SR	126
RSWV28LM	126
RSWV28LR	126
RSWV30SM	126
RSWV30SR	126
RSWV35LM	126
RSWV35LR	126
RSWV38SM	126
RSWV38SR	126
RSWV42LM	126
RSWV42LR	126
RSWV6LM	126
RSWV6LR	126
RSWV6SM	126
RSWV6SR	126
RSWV8LM	126
RSWV8LR	126
RSWV8SM	126
RSWV8SR	126
RT/57116/M/25	541
RT/57116/MC/25	541
RT/57120/M/25	541
RT/57125/M/25	541
RT/57125/M/50	541
RT/57132/M/50	541
RT/57140/M/50	541
RT/57216/M/25	541
RT/57216/M/80	541
RT/57216/MF/10	541
RT/57220/M/10	541
RT/57220/M/100	541
RT/57220/M/25	541
RT/57220/MF/50	541
RT/57225/M/100	541
RT/57225/M/160	541
RT/57225/M/25	541
RT/57225/M/50	541
RT/57225/M/80	541
RT/57225/MF/25	541
RT/57225/MF/50	541
RT/57232/M/100	541
RT/57232/M/160	541
RT/57232/M/25	541
RT/57232/M/50	541
RT/57232/M/80	541
RT/57240/M/100	541
RT/57240/M/50	541
RT/57240/M/80	541
RT/57240/MF/80	541
RT12-14	1208
RT12-38	1208
RT14-316	1208
RT24BK	1588
RT24C	1588
RT38-14	1208
RT38-516	1208
RT516-14	1208
RTDH-1-10	1622
RTDH-1-12	1622
RTDH-1-3	1622
RTDH-1-4	1622
RTDH-1-5	1622
RTDH-1-6	1622
RTDH-1-8	1622
RTDH-34-3	1622
RTDH-34-4	1622
RTDH-34-5	1622
RTDH-34-6	1622
RTH-3/4-15M	1413
RTH-3/4-15SAFETY	1413
RU0404FSS	41
RU0606FSS	41
RU0808FSS	41
RU-1000-500	168
RU-1000-750	168
RU-10-6	175
RU-10-8	175
RU-12-10	175
RU-12-6	175
RU-12-8	175
RU-16-10	175
RU-16-12	175
RU1616FSS	41
RU-18-12	175
RU-187-125	168
RU-203010.05	1561
RU-203012.10	1561
RU-250-125	168
RU-250-187	168
RU-25-18	175
RU-25-20	175
RU-2901.5	1561
RU-312-125	168
RU-312-250	168
RU-375-125	168
RU-375-250	168
RU-375-312	168
RU-500-125	168
RU-500-250	168
RU-500-375	168
RU-625-375	168
RU-625-500	168
RU-6-3	175
RU-6-4	175
RU-750-250	168
RU-750-375	168
RU-750-500	168
RU-750-625	168
RU-8-6	175
RUB14-25	1414
RUB14-25ASG	1414
RUB14-25BG5	1414

Code	Page
RUB14-50	1414
RUB14-50ASG	1414
RUB38-25	1414
RUB38-25ASG	1414
RUB38-25BG5	1414
RUB38-25BG718	1414
RUB38-50	1414
RUB38-50BG5	1414
RUB38-50BG718	1414
RUBLS-100/120	198
RUBLS-125/148	198
RUBLS-15/24	198
RUBLS-20/30	198
RUBLS-25/38	198
RUBLS-32/46	198
RUBLS-50/64	198
RUBLS-65/82	198
RUBLS-80/94	198
RUBLZ-100/120	198
RUBLZ-125/148	198
RUBLZ-20/30	198
RUBLZ-32/46	198
RUBLZ-50/64	198
RUBLZ-65/82	198
RUBLZ-80/94	198
RUBS-100/120	198
RUBS-125/148	198
RUBS-15/24	198
RUBS-150/176	198
RUBS-20/30	198
RUBS-25/38	198
RUBS-32/46	198
RUBS-40/52	198
RUBS-50/64	198
RUBS-65/82	198
RUBS-80/94	198
RUBZ-100/120	198
RUBZ-15/24	198
RUBZ-150/176	198
RUBZ-175/202	198
RUBZ-20/30	198
RUBZ-25/38	198
RUBZ-250/282	198
RUBZ-32/46	198
RUBZ-40/52	198
RUBZ-50/64	198
RUBZ-65/82	198
RUBZ-80/94	198
RUE-1000-500	170
RUE-1000-750	170
RUE-187-125	170
RUE-250-125	170
RUE-312-125	170
RUE-312-250	170
RUE-375-125	170
RUE-375-250	170
RUE-375-312	170
RUE-500-250	170
RUE-500-312	170
RUE-500-375	170
RUE-625-375	170
RUE-625-500	170
RUE-750-250	170
RUE-750-375	170
RUE-750-500	170
RUE-875-250	170
RUS-1017.1	1563
RUS-1085.1	1563
RUS-1611	1568
RUS-1612	1568
RUS-1613	1568
RUS-1615	1568
RUS-1617	1568
RUS-2111	1564
RUS-2114	1565
RUS-2115	1564
RUS-2116	1564
RUS-2117	1563
RUS-2120	1563
RUS-2123	1565
RUS-2124	1565
RUS-2125	1565
RUS-2126	1565
RUS-2127	1565
RUS-2128	1565
RUS-2133	1565
RUS-2134	1565
RUS-2135	1565
RUS-2136	1565
RUS-2137	1565
RUS-2138	1565
RUS-2141	1565
RUS-2142	1565
RUS-2143	1565
RUS-2144	1565
RUS-2145	1565
RUS-2146	1565
RUS-2147	1565
RUS-2148	1565
RUS-2149	1565
RUS-2151	1565
RUS-2152	1565
RUS-2154	1565
RUS-2163	1565
RUS-2165	1565
RUS-2166	1565
RUS-2169	1563
RUS-2174	1565
RUS-2176	1565
RUS-2178	1565
RUS-2179	1565
RUS-2180	1563
RUS-2181	1565
RUS-2182	1563
RUS-2184	1565
RUS-2185	1563
RUS-2186	1565
RUS-2187	1565
RUS-2189	1565
RUS-2190	1565
RUS-2192	1565
RUS-2193	1565
RUS-2194	1565
RUS-2222	1564
RUS-2242	1564
RUS-2255	1564
RUS-2264	1564
RUS-2358	1564
RUS-2391	1564
RUS-2410	1564
RUS-2444	1564
RUS-2479	1564
RUS-2500	1565
RUS-3369	1567
RUS-3369-2.5L	1567
RUS-3380	1567
RUS-3380-2.5L	1567
RUS-3410	1564
RUS-3478	1564
RUS-3490	1564
RUS-5150.1	1561
RUS-5150.2	1561
RUS-5180.2.5	1561
RUS-5180.5.0	1561
RUS-5410.25	1561
RUS-6136.5	1562
RUS-6143.5	1562
RUS-6168.5	1562
RUS-6181.5	1562
RUS-6183.5	1562
RUS-6192.5	1562
RUS-7110NS	1562
RUS-7124	1562
RUS-7137	1562
RUS-7144	1562
RUS-7144NS	1562
RUS-7168	1562
RUS-7179	1562
RUS-7179NS	1562
RUS-7181	1562
RUS-7181NS	1562
RUS-7182NS	1562
RUS-7192	1562
RUS-7301.1	1567
RUS-7314	1566
RUS-7315	1566
RUS-7315-2.5L	1566
RUS-7321-2.5L	1567
RUS-7322-2.5L	1566
RUS-7323	1566
RUS-7326	1566
RUS-7326-2.5L	1566
RUS-7328	1566
RUS-7328-2.5L	1566
RUS-7329	1566
RUS-7332-2.5L	1567
RUS-7335-2.5L	1566
RUS-7336-2.5L	1566
RUS-7337-2.5L	1566
RUS-7338	1567
RUS-7339	1566
RUS-7342	1566
RUS-7342-2.5L	1566
RUS-7343	1566
RUS-7345	1567
RUS-7346-2.5L	1566
RUS-7348	1566
RUS-7348-2.5L	1566
RUS-7349	1566
RUS-7349-2.5L	1566
RUS-7354-2.5L	1566
RUS-7362	1567
RUS-7365	1566
RUS-7365-2.5L	1566
RUS-7366	1566
RUS-7366-2.5L	1566
RUS-7374	1567
RUS-7375	1567
RUS-7375-2.5L	1567
RUS-7376-2.5L	1567
RUS-7377	1566
RUS-7377-2.5L	1566
RUS-7378	1567
RUS-7378-2.5L	1567
RUS-7379	1566
RUS-7379-2.5L	1566
RUS-7381	1566
RUS-7381-2.5L	1566
RUS-7382	1566
RUS-7382-2.5L	1566
RUS-7384-2.5L	1567
RUS-7386	1566
RUS-7386-2.5L	1566
RUS-7388	1567
RUS-7388-2.5L	1567
RUS-7390-2.5L	1567
RUS-7392	1566
RUS-7392-2.5L	1566
RUS-7394-2.5L	1567
RUS-7715	1564
RUS-7778	1564
RUS-AAR5	1562
RUS-AFP5BLU	1562
RUS-AFP5BUF	1562
RUS-AFP5DGY	1562
RUS-AFP5GRN	1562
RUS-AFP5LGY	1562
RUS-AFP5MGY	1562
RUS-AFP5WHI	1562
RUS-AXPSP25	1561
RUS-AXSS25	1561
RUT-1000-375	170
RUT-1000-500	170
RUT-1000-750	170
RUT-375-250	170
RUT-500-250	170
RUT-500-375	170
RUT-625-375	170
RUT-750-375	170
RUT-750-500	170
RV06/180	244
RV08/180	244
RV10L	136
RV-10L-4RG	158
RV10S	136
RV-10S-4RG	158
RV12/180	244
RV12L	136
RV-12L-6RG	158
RV12S	136
RV-12S-6RG	158
RV14S	136
RV-14S-8RG	158
RV15L	136
RV-15L-8RG	158
RV16S	136
RV-16S-8RG	158
RV18L	136
RV-18L-8RG	158
RV20S	136
RV-20S-12RG	158
RV22L	136
RV-22L-12RG	158
RV25S	136
RV-25S-16RG	158
RV28L	136
RV-28L-16RG	158
RV30S	136
RV-30S-20RG	158
RV35L	136
RV-35L-20RG	158
RV38S	136
RV-38S-24RG	158
RV42L	136
RV-42L-24RG	158
RV6L	136
RV-6L-2RG	158
RV6S	136
RV-6S-2RG	158
RV8L	136
RV-8L-4RG	158
RV8S	136
RV-8S-4RG	158
RVV10LRWD	136
RVV10SRWD	136
RVV12LRWD	136
RVV12SRWD	136
RVV14SRWD	136
RVV15LRWD	136
RVV16SRWD	136
RVV18LRWD	136
RVV20SRWD	136
RVV22LRWD	136
RVV25SRWD	136
RVV28LRWD	136
RVV30SRWD	136
RVV35LRWD	136
RVV38SRWD	136
RVV42LRWD	136
RVV6LRWD	136
RVV6SRWD	136
RVV8LRWD	136
RVV8SRWD	136
RVZ10LMWD	136
RVZ10LRWD	136
RVZ10SMWD	136
RVZ10SRWD	136
RVZ12LMWD	136
RVZ12LRWD	136
RVZ12SMWD	136
RVZ12SRWD	136
RVZ14SMWD	136
RVZ14SRWD	136
RVZ15LMWD	136
RVZ15LRWD	136
RVZ16SMWD	136
RVZ16SRWD	136
RVZ18LMWD	136
RVZ18LRWD	136
RVZ20SMWD	136
RVZ20SRWD	136
RVZ22LMWD	136
RVZ22LRWD	136
RVZ25SMWD	136
RVZ25SRWD	136
RVZ28LMWD	136
RVZ28LRWD	136
RVZ30SMWD	136
RVZ30SRWD	136
RVZ35LMWD	136
RVZ35LRWD	136
RVZ38SMWD	136
RVZ38SRWD	136
RVZ42LMWD	136
RVZ42LRWD	136
RVZ6LMWD	136
RVZ6LRWD	136
RVZ6SRWD	136
RVZ8LMWD	136
RVZ8LRWD	136

Code	Page
RVZ8SMWD	136
RVZ8SRWD	136
RZ-10L-4RG	158
RZ-10S-4RG	158
RZ-12L-6RG	158
RZ-12S-6RG	158
RZ-14S-8RG	158
RZ-15L-8RG	158
RZ-16S-8RG	158
RZ-18L-8RG	158
RZ-20S-12RG	158
RZ-22L-12RG	158
RZ-25S-16RG	158
RZ-28L-16RG	158
RZ-30S-20RG	158
RZ-35L-20RG	158
RZ-38S-24RG	158
RZ-42L-24RG	158
RZ-6L-2RG	158
RZ-6S-2RG	158
RZ-8L-4RG	158
RZ-8S-4RG	158
RZMB0402BS	67
RZMB0604BS	67
RZMB0804BS	67
RZMB1008BS	67
RZMB1204BS	67
RZMB1208BS	67
RZMB1612BS	67
RZMB2012BS	67
RZMB2016BS	67
S	
S 100	511
S 125	511
S 160 200	511
S 22	1476
S 32	511
S 40	511
S 50	511
S 63	511
S 80	511
S/666/1	557
S/666/108	557
S/666/117	557
S/666/14	557
S/666/6	557
S/666/7	557
S/666/8	557
S/667/14	557
S/667/8	557
S/S6	635
S03STPI-6	630
S03WBPI-8	630
S04STPI-10	630
S05STPI-12	630
S128050MBU	904
S128050MGY	904
S128050MY	904
S140 150HIT 12	1012
S140 2011ND-4	1008
S140 2012ND-4	1008
S140 2013KMD-3	1009
S140 2013KMD-3C	1009
S140 2013ND-4	1008
S140 2014LA 14	1014
S140 2014LB 14	1014
S140 2014WA 14	1013
S140 2014WB 14	1013
S140 2014WC 14	1013
S140 2014WP 13	1013
S140 2014WP 14	1013
S140 2019D4 12	1011
S140 2057CBL-3	1010
S140 2057CBL-4	1010
S140 2057CBT-3	1010
S140 2057CBT-4	1010
S140 2059DL16 10	1012
S140 2059DT16 10	1012
S20 1070-1	1007
S20 1070-114	1007
S20 1070-12	1007
S20 1070-14	1007
S20 1070-34	1007
S20 1070-38	1007
S20 1071-1	1007
S20 1071-114	1007
S20 1071-12	1007
S20 1071-14	1007
S20 1071-34	1007
S20 1071-38	1007
S20 150HIT 04	1012
S20 150HIT 05	1012
S20 150HIT 06	1012
S20 150HIT 07	1012
S20 2006SD-1	1008
S20 2006SD-112	1008
S20 2006SD-114	1008
S20 2006SD-12	1008
S20 2006SD-14	1008
S20 2006SD-34	1008
S20 2006SD-38	1008
S20 2011KMD-1	1009
S20 2011KMD-114	1009
S20 2011KMD-12	1009
S20 2011KMD-34	1009
S20 2011ND-1	1008
S20 2011ND-114	1008
S20 2011ND-12	1008
S20 2011ND-34	1008
S20 2012CD-1	1010
S20 2012CD-112	1010
S20 2012CD-12	1010
S20 2012CD-34	1010
S20 2012KMD-1	1009
S20 2012KMD-12	1009
S20 2012KMD-34	1009
S20 2012ND-1	1008
S20 2012ND-114	1008
S20 2012ND-12	1008
S20 2012ND-34	1008
S20 2013CD-1	1010
S20 2013CD-112	1010
S20 2013CD-12	1010
S20 2013CD-34	1010
S20 2013KMD-1	1009
S20 2013KMD-114	1009
S20 2013KMD-114C	1009
S20 2013KMD-12	1009
S20 2013KMD-12C	1009
S20 2013KMD-1C	1009
S20 2013KMD-34	1009
S20 2013KMD-34C	1009
S20 2013ND-1	1008
S20 2013ND-114	1008
S20 2013ND-12	1008
S20 2013ND-14	1008
S20 2013ND-34	1008
S20 2013ND-38	1008
S20 2014LA 08	1014
S20 2014LA 09	1014
S20 2014LA 10	1014
S20 2014LB 08	1014
S20 2014LB 09	1014
S20 2014LB 10	1014
S20 2014WA 08	1013
S20 2014WA 09	1013
S20 2014WA 10	1013
S20 2014WB 08	1013
S20 2014WB 09	1013
S20 2014WB 10	1013
S20 2014WC 09	1013
S20 2014WC 10	1013
S20 2014WP 09	1013
S20 2019D 04	1011
S20 2019D 04C	1011
S20 2019D 05	1011
S20 2019D 05C	1011
S20 2019D 06	1011
S20 2019D 06C	1011
S20 2019D 07	1011
S20 2019D 07C	1011
S20 2020D 04	1011
S20 2020D 04C	1011
S20 2020D 05	1011
S20 2020D 05C	1011
S20 2020D 06	1011
S20 2020D 06C	1011
S20 2020D 07	1011
S20 2020D 07C	1011
S20 2040-1	1009
S20 2040-12	1009
S20 2040-14	1009
S20 2040-34	1009
S20 2040-38	1009
S20 2041-1	1009
S20 2041-12	1009
S20 2041-14	1009
S20 2041-34	1009
S20 2041-38	1009
S20 2057CBL-1	1010
S20 2057CBL-112	1010
S20 2057CBL-12	1010
S20 2057CBT-1	1010
S20 2057CBT-112	1010
S20 2057CBT-12	1010
S20 2059DL150 04	1012
S20 2059DL16 04	1012
S20 2059DT150 04	1012
S20 2059DT16 04	1012
S20 6400-1	1007
S20 6400-112	1007
S20 6400-114	1007
S20 6400-12	1007
S20 6400-2	1007
S20 6400-34	1007
S-28DA404FPS008	1699
S-28DA4C4FPS060	1699
S-28DA504FPS032	1700
S-28DC404FPS039	1700
S-28FA504FPS009	1700
S-28FN504FPS040	1700
S-28FR404FPS078	1701
S-28FR504FPS079	1701
S-28FR541FPS080	1701
S-28HA504FPS051	1700
S300 150HIT 13	1012
S300 150HIT 14	1012
S300 2014LA 16	1014
S300 2014LB 16	1014
S300 2014WA 16	1013
S300 2014WB 16	1013
S300 2014WC 16	1013
S300 2019D 13	1011
S300 2059DL16 11	1012
S300 2059DL16 12	1012
S300 2059DT16 11	1012
S300 2059DT16 12	1012
S35 1070-112	1007
S35 1071-112	1007
S35 150HIT 08	1012
S35 2011KMD-112	1009
S35 2011ND-112	1008
S35 2012CD-2	1010
S35 2012KMD-112	1009
S35 2012ND-112	1008
S35 2013CD-2	1010
S35 2013KMD-112	1009
S35 2013KMD-112C	1009
S35 2013ND-112	1008
S35 2014LA 11	1014
S35 2014LB 11	1014
S35 2014WA 11	1013
S35 2014WB 11	1013
S35 2014WC 11	1013
S35 2014WP 10	1013
S35 2019D 08	1011
S35 2019D 08C	1011
S35 2019D 09	1011
S35 2019D 09C	1011
S35 2020D 08	1011
S35 2020D 08C	1011
S35 2020D 09	1011
S35 2020D 09C	1011
S35 2040-114	1009
S35 2041-114	1009
S35 2057CBL-2	1010
S35 2057CBT-2	1010
S35 2059DL150 06	1012
S35 2059DL16 06	1012
S35 2059DT150 06	1012
S35 2059DT16 06	1012
S-36FR504FPS076	1701
S-36FR541FPS077	1701
S-36HN504FPS012	1700
S-36HN541FPS013	1700
S-36HY504FPS068	1701
S-36HY541FPS069	1701
S-36HY684FPS074	1701
S-36LN504FPS014	1700
S-36LN541FPS015	1700
S-36LN684FPS075	1700
S-36NW505FPS038	1700
S-36NW541FPS037	1700
S55 1070-2	1007
S55 1071-2	1007
S55 150HIT 09	1012
S55 150HIT 10	1012
S55 2006SD-2	1008
S55 2011KMD-2	1009
S55 2011ND-2	1008
S55 2011ND-212	1008
S55 2012CD-212	1010
S55 2012CD-3	1010
S55 2012KMD-2	1009
S55 2012ND-2	1008
S55 2012ND-212	1008
S55 2013CD-212	1010
S55 2013CD-3	1010
S55 2013KMD-2	1009
S55 2013KMD-2C	1009
S55 2013ND-2	1008
S55 2013ND-212	1008
S55 2014LA 12	1014
S55 2014LB 12	1014
S55 2014WA 12	1013
S55 2014WB 12	1013
S55 2014WC 12	1013
S55 2014WP 11	1013
S55 2019D 10	1011
S55 2019D 10C	1011
S55 2019D 11	1011
S55 2019D 11C	1011
S55 2019D4 10	1011
S55 2019D4 11	1011
S55 2020D 10	1011
S55 2020D 10C	1011
S55 2020D 11	1011
S55 2020D 11C	1011
S55 2040-112	1009
S55 2041-112	1009
S55 2059DL150 08	1012
S55 2059DL16 08	1012
S55 2059DT150 08	1012
S55 2059DT16 08	1012
S604050MBU	904
S604050MGY	904
S604050MY	904
S6430 10 1/4	871
S6430 10 3/8	871
S6430 12 1/2	871
S6430 12 1/4	871
S6430 12 3/8	871
S6430 14 1/2	871
S6430 4 1/8	871
S6430 5 1/4	871
S6430 5 1/8	871
S6430 6 1/4	871
S6430 6 1/8	871
S6430 8 1/4	871
S6430 8 1/8	871
S6430 8 3/8	871
S6440 10 1/4	871
S6440 10 3/8	871
S6440 12 3/8	871
S6440 14 1/2	871
S6440 4 1/8	871
S6440 5 1/8	871
S6440 6 1/4	871
S6440 6 1/8	871
S6440 8 1/4	871
S6440 8 1/8	871
S6440 8 3/8	871
S6450 4 1/8	872
S6450 6 1/8	872
S6450 8 1/4	872
S6450 8 1/8	872
S6500 10 1/4	870
S6500 10 3/8	870
S6500 12 1/4	870
S6500 12 3/8	870

Code	Page
S6500 4 1/4	870
S6500 4 1/8	870
S6500 5 1/4	870
S6500 5 1/8	870
S6500 6 1/4	870
S6500 6 1/8	870
S6500 8 1/4	870
S6500 8 1/8	870
S6500 8 3/8	870
S6510 10 1/2	870
S6510 10 1/4	870
S6510 10 3/8	870
S6510 12 1/2	870
S6510 12 1/4	870
S6510 12 3/8	870
S6510 14 1/2	870
S6510 14 3/8	870
S6510 4 1/4	870
S6510 4 1/8	870
S6510 5 1/4	870
S6510 5 1/8	870
S6510 6 1/4	870
S6510 6 1/8	870
S6510 8 1/4	870
S6510 8 1/8	870
S6510 8 3/8	870
S6520 10 1/2	870
S6520 10 1/4	870
S6520 10 3/8	870
S6520 12 1/2	870
S6520 12 1/4	870
S6520 12 3/8	870
S6520 14 1/2	870
S6520 14 3/8	870
S6520 4 1/4	870
S6520 4 1/8	870
S6520 5 1/4	870
S6520 5 1/8	870
S6520 6 1/4	870
S6520 6 1/8	870
S6520 8 1/4	870
S6520 8 1/8	870
S6520 8 3/8	870
S-6SCA404FPS506	1699
S70-1	630
S70-12	630
S70-14	630
S70-18	630
S70-34	630
S70-38	630
S71-3C12-12RP	320
S71-3C16-16RP	320
S71-3C4-4RP	320
S71-3C6-6RP	320
S71-3C8-8RP	320
S71-3N12-12RP	320
S71-3N16-16RP	320
S71-3N4-4RP	320
S71-3N6-6RP	320
S71-3N8-8RP	320
S-75DA4G4FPS507	1699
S805050MBU	904
S805050MGY	904
S805050MY	904
S-8213885FPS505	1699
S-8213885FPS566	1699
S85 150HIT 11	1012
S85 2011ND-3	1008

Code	Page
S85 2012CD-4	1010
S85 2012ND-3	1008
S85 2013CD-4	1010
S85 2013KMD-212	1009
S85 2013KMD-212C	1009
S85 2013ND-3	1008
S85 2014LA 13	1014
S85 2014LB 13	1014
S85 2014WA 13	1013
S85 2014WB 13	1013
S85 2014WC 13	1013
S85 2014WP 12	1013
S85 2019D 12	1011
S85 2019D 12C	1011
S85 2020D 12	1011
S85 2020D 12C	1011
S85 2040-2	1009
S85 2040-212	1009
S85 2041-2	1009
S85 2041-212	1009
S85 2057CBL-212	1010
S85 2057CBT-212	1010
S85 2059DL150 09	1012
S85 2059DL16 09	1012
S85 2059DT150 09	1012
S85 2059DT16 09	1012
SA1	1480
SA10	1480
SA12-12	143
SA12-16	143
SA14	1480
SA15	1480
SA16-16	143
SA18	1480
SA19	1480
SA2	1480
SA20	1480
SA20-20	143
S-A2BB104NUA	1699
S-A3CC404FPS501	1699
S-A3DV404FPS536	1699
SA4	1480
SA4-4	143
SA4-6	143
SA5	1480
SA6	1480
SA6005	762
SA6025	762
SA6058	762
SA6059	762
SA6060	762
SA6061	762
SA6091	762
SA6095	762
SA6096	762
SA6120	762
SA6122	762
SA6-6	143
SA6647	762
SA6648	762
SA6649	762
SA6650	762
SA6651	762
SA6652	762
SA6654	762
SA6715	762
SA6749	762
SA6750	762

Code	Page
SA6-8	143
SA6952	762
S-A6BB304FPS534	1699
SA7	1480
SA8	1480
SA8-12	143
SA8-8	143
S-A8CA3C4FPS567	1699
SA9	1480
SAB6101	249
SAB7101	249
SAE-KIT01	112
SAHR-15-12	1451
SAHR-15-12-SB	1450
SAHR-15-12SR608F	1451
SAHR-15-38	1450
SAHR-15-38SHV06T	1450
SAHR-15-38SRT06F	1450
SAHR-15N-12	1451
SAHR-15N-38	1450
SAHR-20-12SHV06T	1451
SAHR-40N-34	1451
SAJ2006R1/032X10	1434
SAJ2006R1/038X10	1434
SAJ2006R1/045X10	1434
SAJ2006R1/051X40	1434
SAK02	1176
SAK04	1176
SAK06	1176
SAK08	1176
SAT13	1593
SB/LP1	1749
SB/LP2	1749
SB/LP3	1749
SB/LP6	1749
SB-04B	261
SB-08B	261
SB-12B	261
SB-1-BLUE-P60	1748
SB-1-RED-P60	1748
SB201-1	1025
SB256-0543AC110	1025
SB256-0543AC220	1025
SB256-0543AC24	1025
SB257-0545DC24	1025
SB-2-BLUE-P60	1748
SB-2-RED-P60	1748
SB-2-YELLOW-P60	1748
SB-3-BLUE-P50	1748
SB-3-RED-P50	1748
SB-3-YELLOW-P50	1748
S-B4BA304FPS571	1701
SB-4-BLUE-P10	1748
S-B4CA304FPS572	1701
S-B4PP304FPS573	1701
SB-4-RED-P10	1748
SB-5-BLUE-P5	1748
SB-6-BLUE-P10	1748
SB-7-BLUE-P6	1748
SB-8-BLUE-P6	1748
SB-B1	194
SB-B2	194
SB-BD01-BL	1764
SB-BD01-GR	1764
SB-BD01-RD	1764
SB-BD01-YL	1764
SB-BD02-BL	1764
SB-BD02-GR	1764

Code	Page
SB-BD02-RD	1764
SB-BD02-YL	1764
SB-BD03-BL	1764
SB-BD03-GR	1764
SB-BD03-RD	1764
SB-BD03-YL	1764
SB-BD04-BL	1764
SB-BD04-GR	1764
SB-BD04-RD	1764
SB-BD04-YL	1764
SBC-1	1481
SBC104112	1523
SBC113121	1523
SBC-12	1481
SBC122130	1523
SBC131139	1523
SBC140148	1523
SBC149161	1523
SBC162174	1523
SBC1719	1523
SBC175187	1523
SBC188200	1523
SBC-2	1481
SBC201213	1523
SBC2022	1523
SBC214226	1523
SBC227239	1523
SBC2325	1523
SBC240252	1523
SBC2628	1523
SBC2931	1523
SBC3235	1523
SBC-34	1481
SBC3639	1523
SBC4043	1523
SBC4447	1523
SBC4851	1523
SBC5255	1523
SBC5659	1523
SBC6063	1523
SBC6467	1523
SBC6873	1523
SBC7479	1523
SBC8085	1523
SBC8691	1523
SBC9297	1523
SBC98103	1523
SBH12-39	1484
SBH12-48	1484
SBH-H	1553
SBH-L	1553
SBQ-34	1483
SBR-A	191
SBR-A-SS	191
SBS-76H	1553
SBS-76L	1553
SBVO-612	182
SBVO-618	182
SC/LV/G1003-1	975
SC/LV/G1003-12	975
SC/LV/G1003-34	975
SC10	141
SC10654MBU	904
SC12	141
SC14	141
SC16	141
SC20	141
SC21CF	394

Code	Page
SC21CM	394
SC21EF	394
SC21EM	394
SC21JF	394
SC21JM	394
SC4	141
SC5	141
SC6	141
SC60404MBU	904
SC8	141
SC80504MBU	904
SCFPTFE-06	29
SCFPTFE-08	29
SCFPTFE-10	29
SCFPTFE-12	29
SCFPTFE-16	29
SCFPTFE-20	29
SCFPTFE-25	29
SCL-212	1514
SCL-3	1514
SCL-5	1514
SCL-8	1514
SCN-1	1497
SCN-112	1497
SCN-114	1497
SCN-12	1497
SCN-2	1497
SCN-3	1497
SCN-34	1497
SCR-112	1514
SCR-12	1514
SCR-2	1514
SCR-212	1514
SCR-3	1514
SCR-4	1514
SCR-5	1514
SCR-6	1514
SCS 668	636
S-CST 02	475
S-CST 03	475
S-CST 04	475
S-CST 25	475
S-CST 26	475
SD-12	1596
SD32-32A	1483
SD50-32A	1483
SE-035-10-12	256
SE-035-10A-12	256
SE-035-25-12	256
SE-070-10-12	256
SE-070-10A-12	256
SE-070-25-12	256
SE-1	1183
SE-100-10-12	256
SE-100-10A-12	256
SE-100-25-12	256
SE-112	1183
SE-114	1183
SE-12	1183
SE1219	249
SE1221	249
SE1319	249
SE1320	249
SE1323	249
SE1324	249
SE1326	249
SE-14	1183
SE1457	249

Code	Page
SE-150-10-20	256
SE-150-25-20	256
SE-18	1183
SE-2	1183
SE-200-10-20	256
SE-200-25-20	256
SE-212	1183
SE-3	1183
SE-34	1183
SE-38	1183
SE-4	1183
SE5100	249
SE5101	249
SE5102	249
SE5103	249
SE5104	249
SE5105	249
SE5106	249
SE5107	249
SE5108	249
SEBF04	65
SEBF06	65
SEBF08	65
SEBF10	65
SEBF12	65
SEBF16	65
SEBF20	65
SEBF24	65
SEBF32	65
SEBM04	65
SEBM06	65
SEBM08	65
SEBM10	65
SEBM24	65
SEBMF04	65
SEBMF06	65
SEBMF08	65
SEBMF10	65
SEBMF12	65
SEBMF16	65
SEBMF20	65
SEBMF24	65
SEBMF32	65
SEE0106A1B	987
SEE0107A1B	987
SEE010EA1B	987
SEE0116A1B	987
SEE0117A1B	987
SEE011EA1B	987
SEE0216A1B	987
SEE021DA1B	987
SEE021PA1B	987
SEE0326A1B	987
SEE0327A1B	987
SEE032EA1B	987
SEE0436A1B	987
SEE0447A1B	987
SEE0546A1B	987
SEE221000P	444
SEE221000P12	444
SEE221125P12	444
SEE221250P12	444
SEE221300P	444
SEE221400P	444
SEE221500P12	444
SEE221600P12	444
SEE221700P12	444
SEE22280P	444
SEE22400P	444
SEE22500P	444
SEE22500P12	444
SEE22550P12	444
SEE22600P	444
SEE22600P12	444
SEE22610P	444
SEE22650P12	444
SEE22700P12	444
SEE22710P	444
SEE22750P	444
SEE22750P12	444
SEE22770P	444
SEE22800P	444
SEE22800P12	444
SEE22825P	444
SEE22850P	444
SEE22850P12	444
SEE22880P	444
SEE22900P	444
SEE22900P12	444
SEE22950P	444
SEE22950P12	444
SEE22S1000B	444
SEE22S1000P	444
SEE22S2800B	444
SEE22S2800P	444
SEE22S4200P	444
SEE22S500B	444
SEE22S500P	444
SEE22S550B	444
SEE22S550P	444
SEE22S600B	444
SEE22S600P	444
SEE22S650B	444
SEE22S700B	444
SEE22S750B	444
SEE22S800B	444
SEE22S850B	444
SEE22S900B	444
SEE27100	443
SEE271000	443
SEE27150	443
SEE27200	443
SEE27250	443
SEE27300	443
SEE27350	443
SEE27400	443
SEE27450	443
SEE27500	443
SEE27600	443
SEE27650	443
SEE27700	443
SEE27800	443
SEE27850	443
SEE27900	443
SEE27950	443
SEE29100	443
SEE291000	443
SEE29150	443
SEE29200	443
SEE29250	443
SEE29300	443
SEE29350	443
SEE29400	443
SEE29450	443
SEE29500	443
SEE29600	443
SEE29650	443
SEE29700	443
SEE29800	443
SEE29850	443
SEE29900	443
SEE29950	443
SEE31100	443
SEE311000	443
SEE31150	443
SEE31200	443
SEE31250	443
SEE31300	443
SEE31350	443
SEE31400	443
SEE31450	443
SEE31500	443
SEE31600	443
SEE31650	443
SEE31700	443
SEE31800	443
SEE31850	443
SEE31900	443
SEE31950	443
SEE80100	443
SEE801000	443
SEE80125	443
SEE80150	443
SEE80200	443
SEE80250	443
SEE80300	443
SEE80350	443
SEE80400	443
SEE80450	443
SEE80500	443
SEE80600	443
SEE80650	443
SEE80700	443
SEE80750	443
SEE80800	443
SEE80850	443
SEE80900	443
SEE80950	443
SEE82100	443
SEE821000	443
SEE82125	443
SEE82150	443
SEE82200	443
SEE82250	443
SEE82300	443
SEE82350	443
SEE82400	443
SEE82450	443
SEE82500	443
SEE82600	443
SEE82650	443
SEE82700	443
SEE82750	443
SEE82800	443
SEE82900	443
SEE84100	443
SEE841000	443
SEE84125	443
SEE84150	443
SEE84200	443
SEE84250	443
SEE84300	443
SEE84350	443
SEE84400	443
SEE84450	443
SEE84500	443
SEE84600	443
SEE84650	443
SEE84700	443
SEE84750	443
SEE84800	443
SEE84900	443
SEE9111A1B	987
SEE9112A1B	987
SEE9113A1B	987
SEE9114A1B	987
SEE9115A1B	987
SEE9116A1B	987
SEE9117A1B	987
SEE9118A1B	987
SEE9119A1B	987
SEE911AA1B	987
SEE911BA1B	987
SEE911CA1B	987
SEE911EA1B	987
SEE911FA1B	987
SEE911GA1B	987
SEE911HA1B	987
SEE911JA1B	987
SEE911LA1B	987
SEE911MA1B	987
SEE911NA1B	987
SEE911PA1B	987
SEE911XA1B	987
SEE9216A1B	987
SEE9218A1B	987
SEE921FA1B	987
SEE921HA1B	987
SEE921LA1B	987
SEE921PA1B	987
SEE921XA1B	987
SEE9320A1B	987
SEE9322A1B	987
SEE9324A1B	987
SEE9326A1B	987
SEE9327A1B	987
SEE9328A1B	987
SEE9329A1B	987
SEE932AA1B	987
SEE932BA1B	987
SEE932DA1B	987
SEE932EA1B	987
SEE932FA1B	987
SEE932GA1B	987
SEE932HA1B	987
SEE932JA1B	987
SEE932LA1B	987
SEE932MA1B	987
SEE932NA1B	987
SEE932PA1B	987
SEE932RA1B	987
SEE932XA1B	987
SEE932YA1B	987
SEE9426A1B	987
SEE9427A1B	987
SEE9428A1B	987
SEE942FA1B	987
SEE942HA1B	987
SEE95100	444
SEE951000	444
SEE95150	444
SEE95200	444
SEE95250	444
SEE95300	444
SEE95350	444
SEE95400	444
SEE95450	444
SEE95500	444
SEE95600	444
SEE95650	444
SEE95700	444
SEE95800	444
SEE95850	444
SEE95900	444
SEE95950	444
SEE97100	444
SEE971000	444
SEE97150	444
SEE97200	444
SEE97250	444
SEE97300	444
SEE97350	444
SEE97400	444
SEE97450	444
SEE97500	444
SEE97600	444
SEE97650	444
SEE97700	444
SEE97800	444
SEE97850	444
SEE97900	444
SEE97950	444
SEE99000	444
SEE99100	444
SEE991000	444
SEE99150	444
SEE99200	444
SEE99250	444
SEE99300	444
SEE99350	444
SEE99400	444
SEE99450	444
SEE99500	444
SEE99600	444
SEE99650	444
SEE99700	444
SEE99800	444
SEE99850	444
SEE99950	444
SEHC10.5	1536
SEHC11.3	1536
SEHC11.9	1536
SEHC12.3	1536
SEHC13.3	1536
SEHC14	1536
SEHC14.5	1536
SEHC15.3	1536
SEHC16.2	1536
SEHC17.5	1536
SEHC18.5	1536
SEHC19.2	1536
SEHC22.6	1536
SEHC23.5	1536
SEHC24.1	1536
SEHC27.1	1536
SEHC32.1	1536
SEHC34.6	1536
SEHC41	1536
SEHC42.5	1536
SEHC44	1536

Code	Page
SEHC51.5	1536
SEHC6.5	1536
SEHC63.5	1536
SEHC7	1536
SEHC8	1536
SEHC8.7	1536
SEHC9.5	1536
SEI05-14	30
SEI05-18	30
SEI06-14	30
SEI06-18	30
SEI06-38	30
SEI08-14	30
SEI08-38	30
SEI10-12	30
SEI10-14	30
SEI10-38	30
SEI12-12	30
SEI12-38	30
SEI12-58	30
SEI16-12	30
SEI16-34	30
SEI16-58	30
SEI20-1	30
SEI20-34	30
SEI25-1	30
SEI25-114	30
SEI31-112	30
SEI31-114	30
SEI38-112	30
SEI38-2	30
SEI51-2	30
SEMI0	1633
SEMI1	1633
SEMI2	1633
SEMI3	1633
SET20100	1631
SET20200	1631
SET20250	1631
SET20300	1631
SET20400	1631
SF10	1172
SF10-1	1099
SF10-112	1099
SF10-114	1099
SF10-12	1099
SF10-2	1099
SF10-212	1099
SF10-3	1099
SF10-34	1099
SF10-4	1099
SF10-6	1099
SF-110-UPVC	1105
SF13	1172
SF16-1	1099
SF16-112	1099
SF16-114	1099
SF16-12	1099
SF16-2	1099
SF16-3	1099
SF16-34	1099
SF16-4	1099
SF16-6	1099
SF17	1172
SF-20-UPVC	1105
SF21	1172
SF-25-UPVC	1105
SF-32-UPVC	1105
SF-40-UPVC	1105
SF-50-UPVC	1105
SF-63-UPVC	1105
SF-75-UPVC	1105
SF-90-UPVC	1105
SFB-3-40	261
SFB-6-40	261
SFB-6-40-HN	261
SFB-6-40-SM	261
SFBV-1	941
SFBV-112	941
SFBV-114	941
SFBV-12	941
SFBV-2	941
SFBV-34	941
SFBVT-1	941
SFBVT-12	941
SFBVT-34	941
S-FCCC404FPS502	1699
S-FCDC404FPS503	1699
SFD0610	246
SFD0620	246
SFD0840	246
SFD0860	246
SFG-110	1105
SFG-20	1105
SFG-32	1105
SFG-40	1105
SFG-50	1105
SFG-63	1105
SFG-75	1105
SFG-90	1105
SFHT10/06	1181
SFHT13/06	1181
SFHT13/09	1181
SFHT17/10	1181
SFHT21/13	1181
SFHT26/19	1181
SFHT33/25	1181
SFHT42/32	1181
SFHT48/38	1181
SFHT52/51	1181
SFI05-14	30
SFI05-18	30
SFI06-12	30
SFI06-14	30
SFI06-18	30
SFI06-38	30
SFI08-12	30
SFI08-14	30
SFI08-38	30
SFI10-12	30
SFI10-14	30
SFI10-38	30
SFI12-12	30
SFI12-38	30
SFI12-58	30
SFI16-12	30
SFI16-34	30
SFI16-58	30
SFI20-1	30
SFI20-114	30
SFI20-12	30
SFI20-34	30
SFI25-1	30
SFI25-114	30
SFI25-34	30
SFI31-1	30
SFI31-112	30
SFI31-114	30
SFI38-112	30
SFI38-2	30
SFI51-2	30
SFL3-1/2-45-DN12	36
SFL3-1/2-45-DN16	36
SFL3-1/2-90-DN12	36
SFL3-1/2-90-DN16	36
SFL3-1/2-DN12	36
SFL3-1/2-DN16	36
SFL3-11/2-DN31	36
SFL3-11/2-DN38	36
SFL3-11/4-DN25	36
SFL3-11/4-DN31	36
SFL3-112-45-DN31	36
SFL3-112-45-DN38	36
SFL3-112-90-DN31	36
SFL3-112-90-DN38	36
SFL3-114-45-DN25	36
SFL3-114-45-DN31	36
SFL3-114-90-DN25	36
SFL3-114-90-DN31	36
SFL3-1-45-DN19	36
SFL3-1-45-DN25	36
SFL3-1-90-DN19	36
SFL3-1-90-DN25	36
SFL3-1-DN19	36
SFL3-1-DN25	36
SFL3-2-45-DN38	36
SFL3-2-45-DN51	36
SFL3-2-90-DN38	36
SFL3-2-90-DN51	36
SFL3-2-DN38	36
SFL3-2-DN51	36
SFL3-3/4-45-DN12	36
SFL3-3/4-45-DN16	36
SFL3-3/4-45-DN19	36
SFL3-3/4-90-DN12	36
SFL3-3/4-90-DN16	36
SFL3-3/4-90-DN19	36
SFL3-3/4-DN12	36
SFL3-3/4-DN16	36
SFL3-3/4-DN19	36
SFM512210S	883
SFM522210S	883
SFM522215S	883
SFMDS1-10	1428
SFMDS112-10	1428
SFMDS112-30	1428
SFMDS114-10	1428
SFMDS114-30	1428
SFMDS1-30	1428
SFMDS2-10	1428
SFMDS212-10	1428
SFMDS212-30	1428
SFMDS2-30	1428
SFMDS3-10	1428
SFMDS312-10	1428
SFMDS312-30	1428
SFMDS3-30	1428
SFMDS34-10	1428
SFMDS34-30	1428
SFMDS4-10	1428
SFMDS4-30	1428
SFMDS6-10	1428
SFMDS6-30	1428
SFPTFE-05	29
SFPTFE-06	29
SFPTFE-08	29
SFPTFE-10	29
SFPTFE-12	29
SFPTFE-16	29
SFPTFE-20	29
SFPTFE-25	29
SFR1-05	29
SFR1-06	29
SFR1-06SC	29
SFR1-08	29
SFR1-08SC	29
SFR1-10	29
SFR1-10SC	29
SFR1-12	29
SFR1-12SC	29
SFR1-16	29
SFR1-20	29
SFR1-25	29
SFR1-31	29
SFR1-38	29
SFR1-51	29
SFR2-05	29
SFR2-06	29
SFR2-06SC	29
SFR2-08	29
SFR2-08SC	29
SFR2-10	29
SFR2-10SC	29
SFR2-12	29
SFR2-12SC	29
SFR2-16	29
SFR2-16SC	29
SFR2-20	29
SFR2-20SC	29
SFR2-25	29
SFR2-25SC	29
SFR2-31	29
SFR2-38	29
SFR2-51	29
SFR3-06	29
SFR3-08	29
SFR3-10	29
SFR3-12	29
SFR3-16	29
SFR3-20	29
SFR3-25	29
SFS6-1/2-45-DN12	36
SFS6-1/2-45-DN16	36
SFS6-1/2-90-DN12	36
SFS6-1/2-90-DN16	36
SFS6-1/2-DN12	36
SFS6-1/2-DN16	36
SFS6-11/2-DN31	36
SFS6-11/2-DN38	36
SFS6-11/4-DN25	36
SFS6-11/4-DN31	36
SFS6-112-45-DN31	36
SFS6-112-45-DN38	36
SFS6-112-90-DN31	36
SFS6-112-90-DN38	36
SFS6-114-45-DN25	36
SFS6-114-45-DN31	36
SFS6-114-90-DN25	36
SFS6-114-90-DN31	36
SFS6-1-45-DN19	36
SFS6-1-45-DN25	36
SFS6-1-90-DN19	36
SFS6-1-90-DN25	36
SFS6-1-DN19	36
SFS6-1-DN25	36
SFS6-2-45-DN38	36
SFS6-2-45-DN51	36
SFS6-2-90-DN38	36
SFS6-2-90-DN51	36
SFS6-2-DN38	36
SFS6-2-DN51	36
SFS6-3/4-45-DN12	36
SFS6-3/4-45-DN16	36
SFS6-3/4-45-DN19	36
SFS6-3/4-90-DN12	36
SFS6-3/4-90-DN16	36
SFS6-3/4-90-DN19	36
SFS6-3/4-DN12	36
SFS6-3/4-DN16	36
SFS6-3/4-DN19	36
SFT	1748
SG01L	1715
SG01P	1715
SG02L	1715
SG02P	1715
SG-12	260
SG-16	260
SG-20	260
SG-24	260
SG50-112-ABS	1099
SG50-114-ABS	1099
SG50-1-ABS	1099
SG50-212-ABS	1099
SG50-2-ABS	1099
SG50-3-ABS	1099
SG50-4-ABS	1099
SG50-5-ABS	1099
SGK-30	282
SGK-30-REFILL	282
SGK-50	281
SGK-50-REFILL	282
SGOR-N	1477
SGP-200	280
SGR-2-40	280
SGS-20	280
SH2-62	310
SH2-62-BSPP	310
SH2-63	310
SH3-62	310
SH3-62-BSPP	310
SH3-63	310
SH4-62	310
SH4-62-BSPP	310
SH4-63	310
SH6-62	310
SH6-62-BSPP	310
SH6-63	310
SH8-62	310
SH8-62-BSPP	310
SH8-63	310
SHBPT50X66	1589
SHBPT50X66BOX	1589
SHBTB/Y-75X500	1589
SHBTR/W-75X500	1589
SHC104-112	1515
SHC113-121	1515
SHC122-130	1515
SHC131-139	1515
SHC140-148	1515
SHC149-161	1515

Code	Page
SHC162-174	1515
SHC17-19	1515
SHC175-187	1515
SHC188-200	1515
SHC201-213	1515
SHC20-22	1515
SHC214-226	1515
SHC227-239	1515
SHC23-25	1515
SHC240-252	1515
SHC26-28	1515
SHC29-31	1515
SHC32-35	1515
SHC36-39	1515
SHC40-43	1515
SHC44-47	1515
SHC48-51	1515
SHC52-55	1515
SHC56-59	1515
SHC60-63	1515
SHC64-67	1515
SHC68-73	1515
SHC74-79	1515
SHC80-85	1515
SHC86-91	1515
SHC92-97	1515
SHC98-103	1515
SHCT25X50	1589
SHCT50X50	1589
SHF-10	1556
SHF-12	1556
SHF-13	1556
SHF-14	1556
SHF-15	1556
SHF-16	1556
SHF-17	1556
SHF-18	1556
SHF-19	1556
SHF-20	1556
SHF-28	1556
SHG100-002BG	267
SHG100-006BG	267
SHG100-016BG	267
SHG100-040BG	267
SHG100-100BG	267
SHG100-250BG	267
SHG100-600BG	267
SHG-18	45
SHG-20	45
SHG-22	45
SHG-24	45
SHG-25	45
SHG-26	45
SHG-29	45
SHG-31	45
SHG-33	45
SHG-37	45
SHG-41	45
SHG-43	45
SHG-45	45
SHG-49	45
SHG-51	45
SHG-54	45
SHG-56	45
SHG-60	45
SHG-63	45
SHG-70	45
SHM-1	1497
SHM-10	1497
SHM-112	1497
SHM-114	1497
SHM-12	1497
SHM-2	1497
SHM-212	1497
SHM-3	1497
SHM-34	1497
SHM-38	1497
SHM-4	1497
SHM-5	1497
SHM-6	1497
SHM-8	1497
SHMT25X50	1589
SHMT50X50	1589
SHOT3101	1483
SHOT3102	1483
SHOT3103	1483
SHOT3104	1483
SHOT3110	1483
SHOT3111	1483
SHOTCFP	1483
SHOTCQP1	1483
SHOTCQP2	1483
SHOTCQP4	1483
SHOTRSDKD	1483
SHOTRSDR2	1483
SHOTRSDR3	1483
SHOTS	1483
SHRC04/04	1146
SHRC05/05	1146
SHW-13	1435
SHW-13-10	1435
SHW-19	1435
SHW-19-10	1435
SHW-25	1435
SHW-25-10	1435
SI4	762
SI5	762
SI6	762
SI8	762
SIL-007-L	1607
SIL-007-L-1000	1607
SIL-007-L-250	1607
SIL-007-L-400	1607
SIL-007-L-600	1607
SIL-007-L-800	1607
SIL-007-Z	1607
SIL-007-Z-1000	1607
SIL-007-Z-250	1607
SIL-007-Z-400	1607
SIL-007-Z-600	1607
SIL-007-Z-800	1607
SIL-2005	1608
SIL-2055-A	1608
SIL-2055-A-1000	1608
SIL-2055-A-500	1608
SIL-208	1612
SIL-209	1612
SIL-210	1612
SIL-211	1612
SIL-215	1612
SIL-216	1612
SIL-218	1612
SIL-221-L	1612
SIL-231-L	1612
SIL-241-L	1612
SIL-251-L	1612
SIL-362	1612
SIL-364	1612
SIL-366	1612
SIL-392	1612
SIL-394	1612
SIL-396	1612
SIL-5001	1608
SIL-5003	1608
SIL-500-L	1608
SIL-500-L-1000	1608
SIL-500-L-250	1608
SIL-500-L-800	1608
SIL-500-Z	1607
SIL-500-Z-250	1607
SIL-500-Z-400	1607
SIL-500-Z-600	1607
SIL-500-Z-800	1607
SIL-501-L	1608
SIL-511	1608
SIL-512	1608
SIL-5920	1608
SIL-705	1612
SIL-755-L	1608
SIL-9002W	1612
SIL-920A	1612
SIL-920B	1612
SIL-921	1612
SIL-961	1612
SIL-973	1612
SIL-973F	1612
SIL-OSH	1612
SIL-PRO-ONE	1607
SJN-2-045	1674
SJN-2-050	1674
SJN-2-055	1674
SJN-4-045	1674
SJN-4-050	1674
SJN-4-055	1674
SJN-6-045	1674
SJN-6-050	1674
SJN-6-055	1674
SK12S	384
SK23S	384
SK29-CLAMP	1478
SK34	1480
SK34-CLAMP	1478
SK39	1480
SK44	1480
SK51	1480
SK60	1478
SK73	1480
SKA 10	1476
SKA 11	1476
SKA 13	1476
SKA 19	1476
SKA 25	1476
SKA 34	1476
SKA-106	156
SKA-107	156
SKA-108	156
SKA-127	156
SKA-128	156
SKA-129	156
SKA-1610	156
SKA-1611	156
SKA-1612	156
SKA-1613	156
SKA-2012	156
SKA-2014	156
SKA-2015	156
SKA-2016	156
SKA-2515	156
SKA-2517	156
SKA-2519	156
SKAR-10-6	156
SKAR-10-8	156
SKAR-12-10	156
SKAR-12-8	156
SKAR-16-12	156
SKAR-20-12	156
SKAR-20-16	156
SKAR-25-15	156
SKAR-25-16	156
SKAR-25-20	156
SKB13	1477
SKB19	1477
SKB25	1477
SKG10	1477
SKG13	1477
SKG15	1477
SKG19	1477
SKG25	1477
SKG32	1477
SKG6	1477
SL 115	1476
SL 145	1476
SL 29	1476
SL 34	1476
SL 400	1476
SL 49	1476
SL 525	1476
SL 550	1476
SL 600	1476
SL 675	1476
SL 72	1476
SL 769	1476
SL 875	1476
SL 94	1476
SL 988	1476
SL-11	1672
SL-13	1672
SL-2	1672
SL-3	1672
SL-4	1672
SL-5	1672
SL-7	1672
SL-8	1672
SL-A0/A1	192
SL-A2	192
SL-A3	192
SL-A4	192
SL-A5	192
SL-A6	192
SLD050	630
SLD075	630
SLD150	630
SLD200	630
SLE 13	1476
SLE 19	1476
SLE 25	1476
SLS050	630
SLS075	630
SLS100	630
SLS125	630
SLS150	630
SLS200	630
SLS250	630
SMF04U/02	1645
SMFM6/02	1645
SMFM8/02	1645
SMH01-01	1146
SMH12-12	1146
SMH12-34	1146
SMH12-38	1146
SMH14-12	1146
SMH14-38	1146
SMH18-14	1146
SMH34-12	1146
SMH34-34	1146
SMH38-14	1146
SMI05-14	30
SMI06-12	30
SMI06-14	30
SMI06-18	30
SMI06-38	30
SMI08-12	30
SMI08-14	30
SMI08-38	30
SMI10-12	30
SMI10-14	30
SMI10-38	30
SMI12-12	30
SMI12-34	30
SMI12-38	30
SMI16-12	30
SMI16-34	30
SMI16-58	30
SMI20-1	30
SMI20-34	30
SMI25-1	30
SMI25-114	30
SMI25-34	30
SMI31-112	30
SMI31-114	30
SMI38-112	30
SMI51-2	30
SN02/03	1144
SN04/04	1144
SN04/05	1144
SN06/06	1144
SN08/08	1144
SN10X1.5	127
SN10X2	127
SN12/12	1144
SN12X2.5	127
SN16X2	127
SN16X3	127
S-N1AT905FPS085	1701
S-N1NN905FPS019	1700
S-N1TT905FPS086	1701
SN20X3	127
SN25X3	127
SN25X4	127
SN30X4	127
SN30X5	127
SN38X4	127
SN38X5	127
SN38X6	127
S-N5AT701FPS081	1701
S-N5NT701FPS083	1701
S-N5NY701FPS070	1701
S-N7AT801FPS082	1701
S-N7LN701FPS044	1700
S-N7NN801FPS018	1700

Code	Page
S-N7NT801FPS084	1701
SN8X2	127
SNO12JET	1495
SNO34JET	1495
SNO58JET	1495
SNV10/6L	129
SNV10/6S	129
SNV10/8L	129
SNV10/8S	129
SNV10L	128
SNV10L/10S	129
SNV10S	128
SNV12/10L	129
SNV12/10S	129
SNV12/6L	129
SNV12/6S	129
SNV12/8L	129
SNV12/8S	129
SNV12L	128
SNV12L/12S	129
SNV12S	128
SNV14S	128
SNV15/10L	129
SNV15/12L	129
SNV15/8L	129
SNV15L	128
SNV16/10S	129
SNV16/12S	129
SNV16S	128
SNV16S/15L	129
SNV18/10L	129
SNV18/12L	129
SNV18/15L	129
SNV18L	128
SNV18L/16S	129
SNV20/12S	129
SNV20/16S	129
SNV20S	128
SNV20S/18L	129
SNV22/12L	129
SNV22/15L	129
SNV22L	128
SNV22L/20S	129
SNV25/16S	129
SNV25/20S	129
SNV25S	128
SNV25S/22L	129
SNV28/15L	129
SNV28/18L	129
SNV28/22L	129
SNV28L	128
SNV28L/25S	129
SNV30/16S	129
SNV30/20S	129
SNV30/25S	129
SNV30S	128
SNV30S/28L	129
SNV35/18L	129
SNV35/22L	129
SNV35/28L	129
SNV35L	128
SNV35L/30S	129
SNV38/20S	129
SNV38/25S	129
SNV38/30S	129
SNV38S	128
SNV38S/35L	129
SNV42/22L	129
SNV42/28L	129
SNV42/35L	129
SNV42L	128
SNV42L/38S	129
SNV6L	128
SNV6L/6S	129
SNV6S	128
SNV8/6L	129
SNV8/6S	129
SNV8L	128
SNV8L/8S	129
SNV8S	128
SO-110-UPVC	1101
SO-125-UPVC	1101
SO13-112-ABS	1097
SO13-112-UPVC	1108
SO13-114-ABS	1097
SO13-114-UPVC	1108
SO13-12-ABS	1097
SO13-12-UPVC	1108
SO13-1-ABS	1097
SO13-1-UPVC	1108
SO13-212-ABS	1097
SO13-212-UPVC	1108
SO13-2-ABS	1097
SO13-2-UPVC	1108
SO13-34-ABS	1097
SO13-34-UPVC	1108
SO13-3-ABS	1097
SO13-3-UPVC	1108
SO13-4-ABS	1097
SO13-4-UPVC	1108
SO13-5-UPVC	1108
SO13-6-UPVC	1108
SO13-8-UPVC	1108
SO14-1104-UPVC	1108
SO14-321-UPVC	1108
SO14-3534-UPVC	1108
SO14-40114-UPVC	1108
SO14-50112-UPVC	1108
SO14-632-UPVC	1108
SO14-903-UPVC	1108
SO-160-UPVC	1101
SO-16-UPVC	1101
SO-200-UPVC	1101
SO-20-UPVC	1101
SO-225-UPVC	1101
SO-25-UPVC	1101
SO-32-UPVC	1101
SO-40-UPVC	1101
SO-50-UPVC	1101
SO-63-UPVC	1101
SO-75-UPVC	1101
SO-90-UPVC	1101
SOCV06	244
SOCV08	244
SOCV12	244
SOK-30	282
SOK-30-REFILL	282
SOK-50	281
SOK-50-REFILL	282
SOP-200	280
SOS-20	280
SP-1	1185
SP-112	1185
SP-114	1185
SP-12	1185
SP-14	1185
SP160P	1764
SP162P	1764
SP-18	1185
SP-2	1185
SP-212	1185
SP24L	1764
SP26L	1764
SP-3	1185
SP-34	1185
SP-38	1185
SPAV.06002	296
SPAV.06003	296
SPAV.10002	296
SPAV.10003	296
SPAV.13002	296
SPAV.13003	296
SPAV.20002	296
SPAV.20003	296
SPAV.25002	296
SPAV.25003	296
SPB-08B	261
SPB-12B	261
SPBV.06002	300
SPBV.06003	300
SPBV.10002	300
SPBV.10003	300
SPBV.13002	300
SPBV.13003	300
SPBV.20002	300
SPBV.20003	300
SPBV.25002	300
SPBV.25003	300
SPC06-02	792
SPC08-02	792
SPC08-03	792
SP-C1	197
SPC10-02	792
SPC10-03	792
SPC10-04	792
SPC12-03	792
SPC12-04	792
SP-C1-SS	197
SP-C2	197
SP-C2-SS	197
SP-C3	197
SP-C3-SS	197
SP-C4	197
SP-C4-SS	197
SP-C5	197
SP-C5-SS	197
SP-C6-SS	197
SP-C7-SS	197
SP-C8-SS	197
SPCJ.06002	305
SPCJ.06003	305
SPCJ.06042	305
SPCJ.06043	305
SPE12	1208
SPE38	1208
SPE516	1208
SPHC12-12RP	320
SPHC4-4RP	320
SPHC6-6RP	320
SPHC8-8RP	320
SPHN12-12RP	320
SPHN16-16RP	320
SPHN24-24RP	320
SPHN32-32RP	320
SPHN4-4RP	320
SPHN6-6RP	320
SPHN8-8RP	320
SPLICING-KIT01	112
SPLT.06002	299
SPLT.06003	299
SPLT.13002	299
SPLT.13003	299
SPLT.13302	299
SPLT.13342	299
SPLT.20002	299
SPLT.20003	299
SPLT.25002	299
SPLT.25003	299
SPLT.30003	299
SPN0006	432
SPN0009	432
SPN0012	432
SPN0018	432
SPN0024	432
SPN0036	432
SPN0048	432
SPN0063	432
SPPV.13302	299
SPPV.13312	299
SPPV.13322	299
SPPV.13342	299
SPR08-10-100	256
SPR08-10-35	256
SPR08-10-70	256
SPR08-25-100	256
SPR08-25-35	256
SPR08-25-70	256
SPR12-10-100	256
SPR12-10-35	256
SPR12-10-70	256
SPR12-25-100	256
SPR12-25-35	256
SPR12-25-70	256
SPR16-10-100	256
SPR16-10-35	256
SPR16-10-70	256
SPR16-25-100	256
SPR16-25-35	256
SPR16-25-70	256
SPR20-10-150	256
SPR20-10-200	256
SPR20-25-150	256
SPR20-25-200	256
SPS08-10-100	256
SPS08-10-35	256
SPS08-10-70	256
SPS08-25-100	256
SPS08-25-35	256
SPS08-25-70	256
SPS12-10-100	256
SPS12-10-35	256
SPS12-10-70	256
SPS12-25-100	256
SPS12-25-35	256
SPS12-25-70	256
SPS16-10-100	256
SPS16-10-35	256
SPS16-10-70	256
SPS16-25-100	256
SPS16-25-35	256
SPS16-25-70	256
SPS20-10-150	256
SPS20-10-200	256
SPS20-25-150	256
SPS20-25-200	256
SPST.06202	304
SPST.06203	304
SPST.13202	304
SPST.13203	304
SPST.20202	304
SPST.20203	304
SPST.25202	304
SPST.25203	304
SPST.30202	304
SPST.30203	304
SPST.39202	304
SPST.39203	304
SPT100A	1636
SPT60A	1636
SPT80A	1636
SPU06	792
SPU08	792
SPU10	792
SPU12	792
SPVE.20202	307
SPVE.20203	307
SPVE.25202	307
SPVE.25203	307
SPVS.06100	306
SPVS.06101	306
SPVS.10100 C	306
SPVS.10103 C	306
SPVV.06002	304
SPVV.06003	304
SPVV.10002	304
SPVV.10003	304
SPVV.10202	304
SPVV.10203	304
SPVV.13002	304
SPVV.13003	304
SPVV.13202	304
SPVV.13203	304
SPVV.20002	304
SPVV.20003	304
SPVV.20202	304
SPVV.20203	304
SPVV.25002	304
SPVV.25003	304
SPVV.25202	304
SPVV.25203	304
SPVV.30002	304
SPVV.30003	304
SPVV.30202	304
SPVV.30203	304
SR100-05	1460
SR100-06	1460
SR101-01	1459
SRAH06-10	1411
SRAH06-15	1411
SRAH06-20	1411
SRAH06-5	1411
SRAH06X	1410
SRAH06X-100	1410
SRAH08-10	1411
SRAH08-15	1411
SRAH08-20	1411
SRAH08-5	1411
SRAH08X	1410
SRAH08X1/4X19-10	1411
SRAH08X1/4X19-20	1411

Code	Page
SRAH08X-100	1410
SRAH1/2X100-10	1411
SRAH1/2X100-20	1411
SRAH100/13-10	1411
SRAH100/13-15	1411
SRAH100/13-20	1411
SRAH100/13-30	1411
SRAH10-10	1411
SRAH10-15	1411
SRAH10-20	1411
SRAH10-5	1411
SRAH10X	1410
SRAH10X1/4X19-10	1411
SRAH10X1/4X19-20	1411
SRAH10X-100	1410
SRAH13-10	1411
SRAH13-15	1411
SRAH13-20	1411
SRAH13-5	1411
SRAH13X	1410
SRAH13X-100	1410
SRAH19/10-10	1411
SRAH19/10-15	1411
SRAH19/10-20	1411
SRAH19/10-5	1411
SRAH19/8-10	1411
SRAH19/8-15	1411
SRAH19/8-20	1411
SRAH19/8-5	1411
SRAH19X	1410
SRAH19X-100	1410
SRAH25/10-10	1411
SRAH25/10-15	1411
SRAH25/10-20	1411
SRAH25/10-5	1411
SRAH25X	1410
SRAH25X-100	1410
SRFH-08	256
SRFH-12	256
SRFH-16	256
SRFH-20	256
SRG2A.KIT	1633
SR-L06/2 K-SPH	163
SR-L08/2 K-SPH	163
SR-L10/2 K-SPH	163
SR-L12/2 K-SPH	163
SR-L15/2 K-SPH	163
SR-L18/2 K-SPH	163
SR-L22/2 K-SPH	163
SR-L28/2 K-SPH	163
SR-L35/2 K-SPH	163
SR-L42/2 K-SPH	163
SR-LL04/1 K-SPH	163
SR-LL06/1 K-SPH	163
SR-LL08/1 K-SPH	163
SR-M 4 LL	117
SR-M 6 LL	117
SR-M 8 LL	117
SRN10	917
SRN1012	917
SRN12	917
SRN14	917
SRN15	917
SRN18	917
SRN316	917
SRN38	917
SRN4	917
SRN5	917
SRN516	917
SRN58	917
SRN6	917
SRN8	917
SR-S-06/2 K-SPH	163
SR-S-08/2 K-SPH	163
SR-S-10/2 K-SPH	163
SR-S-12/2 K-SPH	163
SR-S-16/2 K-SPH	163
SR-S-20/2 K-SPH	163
SR-S-25/2 K-SPH	163
SR-S-30/2 K-SPH	163
SR-S-38/2 K-SPH	163
SS020-08	255
SS030-12	255
SS040-16	255
SS080-20	255
SS11	1474
SS112	1474
SS120-24	255
SS1301	1524
SS1302	1524
SS1303	1524
SS1304	1524
SS1305	1524
SS1306	1524
SS1307	1524
SS1308	1524
SS1309	1524
SS1310	1524
SS1311	1524
SS1312	1524
SS1313	1524
SS1314	1524
SS1315	1524
SS1316	1524
SS1317	1524
SS1318	1524
SS1319	1524
SS1320	1524
SS1321	1524
SS1322	1524
SS1323	1524
SS1324	1524
SS1325	1524
SS1326	1524
SS1327	1524
SS1328	1524
SS1329	1524
SS1330	1524
SS1331	1524
SS1332	1524
SS1333	1524
SS1334	1524
SS1335	1524
SS1336	1524
SS1337	1524
SS1338	1524
SS1339	1524
SS134	1474
SS1340	1524
SS1341	1524
SS1342	1524
SS1343	1524
SS1344	1524
SS1345	1524
SS1346	1524
SS1347	1524
SS1348	1524
SS200-24	255
SS200-32	255
SS21	1474
SS212	1474
SS234	1474
SS300-40	255
SS31	1474
SS312	1474
SS334	1474
SS4	762
SS400-48	255
SS5	762
SS6	762
SS60015BH	1126
SS60015YH	1126
SS60022BH	1126
SS60022YH	1126
SS60028BH	1126
SS60028YH	1126
SS60035BH	1126
SS60035YH	1126
SS60042BH	1126
SS60042YH	1126
SS60054BH	1126
SS60054YH	1126
SS8	762
SSA020-08	255
SSA028-12	255
SSA040-16	255
SSA060-20	255
SSA080-24	255
SSA120-24	255
SSA160-32	255
SSA200-32	255
SSA300-40	255
SSA400-40	255
SS-B1	194
SSB112-S	1546
SSB114-S	1546
SSB12-S	1546
SSB1-S	1546
SS-B1-SS	194
SS-B2	194
SSB2-S	1546
SS-B2-SS	194
SS-B3	194
SSB34-S	1546
SS-B3-SS	194
SS-B4	194
SS-B5	194
SSBSM04N	110
SSBSM06N	110
SSBSM08N	110
SSBSM10N	110
SSBSM12N	110
SSBSM14N	110
SSBSM16N	110
SSBSM20N	110
SS-C1	197
SSC12	1472
SS-C1-SS	197
SS-C2	197
SS-C2-SS	197
SS-C3	197
SS-C3-SS	197
SS-C4	197
SS-C4-SS	197
SS-C5	197
SSC-5000-UPVC	1107
SS-C5-SS	197
SSC6	1472
SS-C6	197
SS-C7	197
SSCT1	1487
SSCT112	1487
SSCT114	1487
SSCT2	1487
SSCT212	1487
SSCT3URT	1488
SSFBA-1	1195
SSFBA-12	1195
SSFBA-2	1195
SSFBA-3	1195
SSFBA-34	1195
SSFBB-12	1195
SSFBB-2	1195
SSFBB-3	1195
SSFBSB-1	1195
SSFBSB-112	1195
SSFBSB-114	1195
SSFBSB-34	1195
SSFH-08	256
SSFH-12	256
SSFH-16	256
SSFH-20	256
SSFSA-1	1195
SSFSA-112	1195
SSFSA-12	1195
SSFSA-2	1195
SSFSB-1	1195
SSFSB-112	1195
SSFSB-114	1195
SSFSB-12	1195
SSFSB-2	1195
SSFSB-3	1195
SSFSB-34	1195
SSFWA-2	1195
SSFWA-3	1195
SSFWA-34	1195
SSG10	1477
SSG10S	1477
SSG13	1477
SSG13S	1477
SSG15	1477
SSG15S	1477
SSG19	1477
SSG19PH	1477
SSG19S	1477
SSG25	1477
SSG25S	1477
SSG32	1477
SSG63-001B	412
SSG63-001BG	267
SSG63-004B	412
SSG63-004BG	267
SSG63-012B	412
SSG63-012BG	267
SSG63-025B	412
SSG63-025BG	267
SSG63-060B	412
SSG63-060BG	267
SSG63-200B	412
SSG63-200BG	267
SSG63-250BG	415
SSG63-400B	412
SSG63-400BG	267
SSGA10	1477
SSGA12	1477
SSGA34	1477
SSGA38	1477
SSGI10	1477
SSGI12	1477
SSGI34	1477
SSGI38	1477
SSGN02	1643
SSGN0245	1643
SSGN0245N	1643
SSGN0290	1643
SSGN0290N	1643
SSGN02N	1643
SSGN04	1643
SSGN0445	1643
SSGN0490	1643
SSGN04N	1643
SSGNM6	1643
SSGNM645	1643
SSGNM690	1643
SSGNM8	1643
SSGNM845	1643
SSGNM890	1643
SSGNU04	1643
SSGNU0445	1643
SSGNU0490	1643
SSHR-12-SB	1453
SSHR-15-12SB106F	1453
SSHR-15-12SHV06T	1453
SSHR-15-12SHV08T	1453
SSHR-15-12SWD08T	1453
SSHR-15N-12	1453
SSL-A0/A1	192
SSL-A0/A1-SS	192
SSL-A2	192
SSL-A2-SS	192
SSL-A3	192
SSL-A3-SS	192
SSL-A4	192
SSL-A4-SS	192
SSL-A5	192
SSL-A5-SS	192
SSL-A6	192
SSL-A6-SS	192
SSL-A7	192
SSNSE10-G02	876
SSNSE10-G03	876
SSNSE10-G04	876
SSNSE12-G04	876
SSNSE4-G01	876
SSNSE6-G01	876
SSNSE6-G02	876
SSNSE8-G01	876
SSNSE8-G02	876
SSNSE8-G03	876
SSPB10-G02	876
SSPB10-G03	876
SSPB12-G03	876
SSPB12-G04	876
SSPB4-G01	876
SSPB6-G01	876
SSPB6-G02	876
SSPB8-G01	876
SSPB8-G02	876
SSPC10-02	876
SSPC10-03	876

Code	Page
SSPC10-G02	876
SSPC10-G03	876
SSPC12-04	876
SSPC12-G04	876
SSPC4-01	876
SSPC4-G01	876
SSPC6-01	876
SSPC6-02	876
SSPC6-G01	876
SSPC6-G02	876
SSPC8-01	876
SSPC8-02	876
SSPC8-G01	876
SSPC8-G02	876
SSPCF10-G02	876
SSPCF10-G03	876
SSPCF12-G03	876
SSPCF12-G04	876
SSPCF4-G01	876
SSPCF6-G01	876
SSPCF6-G02	876
SSPCF8-G01	876
SSPCF8-G02	876
SSPG10-6	877
SSPG10-8	877
SSPG12-10	877
SSPG12-8	877
SSPG6-4	877
SSPG8-4	877
SSPG8-6	877
SSPGJ10-6	877
SSPGJ10-8	877
SSPGJ12-10	877
SSPGJ12-8	877
SSPGJ6-4	877
SSPGJ8-4	877
SSPGJ8-6	877
SSPL10-02	876
SSPL10-03	876
SSPL10-G02	876
SSPL10-G03	876
SSPL12-04	876
SSPL12-G04	876
SSPL4-01	876
SSPL4-G01	876
SSPL6-01	876
SSPL6-02	876
SSPL6-G01	876
SSPL6-G02	876
SSPL8-01	876
SSPL8-02	876
SSPL8-G01	876
SSPL8-G02	876
SSPLF10-G02	876
SSPLF10-G03	876
SSPLF12-G03	876
SSPLF12-G04	876
SSPLF4-G01	876
SSPLF6-G01	876
SSPLF6-G02	876
SSPLF8-G01	876
SSPLF8-G02	876
SSPM-10	877
SSPM-12	877
SSPM-4	877
SSPM-6	877
SSPM-8	877
SSPP-10	877
SSPP-12	877
SSPP-4	877
SSPP-6	877
SSPP-8	877
SSPUC-10	877
SSPUC-12	877
SSPUC-4	877
SSPUC-6	877
SSPUC-8	877
SSPUL-10	877
SSPUL-12	877
SSPUL-4	877
SSPUL-6	877
SSPUL-8	877
SSPUT-10	877
SSPUT-12	877
SSPUT-4	877
SSPUT-6	877
SSPUT-8	877
SSPY-10	877
SSPY-12	877
SSPY-4	877
SSPY-6	877
SSPY-8	877
SSTLH	1672
SSTLTC	1672
SSV-12	406
SSVC-12	406
S-SXDL504FPS504	1699
ST10	1593
ST100	284
ST11	1593
ST20	284
ST203	1593
ST206	1593
ST208	1593
ST210	1593
ST212	1593
ST216	1593
ST218	1593
ST2238	1588
ST224	1593
ST230	1593
ST23-112-ABS	1099
ST23-112-UPVC	1111
ST23-114-UPVC	1111
ST23-12-UPVC	1111
ST23-1-ABS	1099
ST23-1-UPVC	1111
ST23-212-ABS	1099
ST23-212-UPVC	1111
ST23-2-ABS	1099
ST23-2-UPVC	1111
ST23-34-ABS	1099
ST23-34-UPVC	1111
ST23-3-ABS	1099
ST23-3-UPVC	1111
ST23-4-ABS	1099
ST23-4-UPVC	1111
ST23-5-ABS	1099
ST23-5-UPVC	1111
ST236	1593
ST23-6-ABS	1099
ST23-6-UPVC	1111
ST23-8-UPVC	1111
ST30	284
ST40	284
ST40WHRL	1760
ST40WHRM	1760
ST40WHRS	1760
ST40WHRXL	1760
ST40WHRXXL	1760
ST40WHRXXXL	1760
ST43WHR	1760
ST44WHR	1760
ST-5	1670
ST60	284
ST-7	1670
ST900	1670
STAGA	1391
STAGB	1391
STANDB	1496
STANDBG	1496
STANDC	1496
STANDDS	1496
STANDS	1496
STANDSP	1496
STANDW	1496
STCAS-1	1488
STCAS-112	1488
STCAS-1-12	1488
STCAS-112-114	1488
STCAS-114	1488
STCAS-114-1	1488
STCAS-12	1488
STCAS-1-34	1488
STCAS-2	1488
STCAS-3	1488
STCAS-34	1488
STCAS-4	1488
STCC-1	1488
STCC-112	1488
STCC-114	1488
STCC-12	1488
STCC-2	1488
STCC-3	1488
STCC-34	1488
STCC-4	1488
STCL-1	1488
STCL-112	1488
STCL-1-12	1488
STCL-112-114	1488
STCL-114	1488
STCL-114-1	1488
STCL-12	1488
STCL-1-34	1488
STCL-2	1488
STCL-3	1488
STCL-34	1488
STCL-4	1488
STCM-1	1488
STCM-112	1488
STCM-114	1488
STCM-12	1488
STCM-2	1488
STCM-3	1488
STCM-34	1488
STCM-4	1488
STF-11	1556
STF-12	1556
STF-13	1556
STF-14	1556
STF-15	1556
STF-17	1556
STF-18	1556
STF-22	1556
STOPFA11115	43
STOPFA12125	43
STOPFA13135	43
STOPFA1415	43
STOPFA1617	43
STOPFA1718	43
STOPFA1819	43
STOPFA2021	43
STOPFA2122	43
STOPFA2223	43
STOPFA2425	43
STOPFA2526	43
STOPFA2627	43
STOPFA2728	43
STOPFA2829	43
STOPFA3031	43
STOPFA3233	43
STOPFA3435	43
STOPFA3637	43
STOPFA3839	43
STOPFA3940	43
STOPFA4041	43
STOPFA4243	43
STOPFA4344	43
STOPFA4445	43
STOPFA4547	43
STOPFA4850	43
STOPFA5153	43
STOPFA5354	43
STOPFA5456	43
STOPFA5759	43
STOPFA6062	43
STOPFA6365	43
STOPFA6668	43
STOPFA6971	43
STOPFA7274	43
STOPFA7577	43
STOPFA7880	43
STOPFA8183	43
STOPFA8486	43
STOPFA8789	43
STOPFA9092	43
STOPFA9395	43
STOPFUDIN145	43
STOPFUDIN17	43
STOPFUDIN185	43
STOPFUDIN205	43
STOPFUDIN225	43
STOPFUDIN245	43
STOPFUDIN265	43
STOPFUDIN305	43
STOPFUDIN34	43
STOPFUDIN365	43
STOPFUDIN425	43
STOPFUDIN455	43
STOPFUDIN49	43
STOPFUDIN525	43
STOPFUDIN60	43
STOPFUJIC115	43
STOPFUJIC132	43
STOPFUJIC148	43
STOPFUJIC195	43
STOPFUJIC228	43
STOPFUJIC275	43
STOPFUJIC307	43
STOPFUJIC34	43
STOPFUJIC415	43
STOPFUJIC48	43
STOPFUJIC64	43
STOPFUSAE085	43
STOPFUSAE105	43
STOPFUSAE125	43
STOPFUSAE145	43
STOPFUSAE165	43
STOPFUSAE205	43
STOPFUVARIE	43
STOPFUVARIES	43
STS15	884
STS22	884
STS28	884
STW-201L	1553
STW-362L	1553
STW-838H	1553
SUBV-32-UPVC	1107
SV04	245
SV06	245
SV08	245
SV-10L	155
SV10R	1497
SV-10S	155
SV12	245
SV-12L	155
SV-12S	155
SV13R	1497
SV13R/S	1497
SV-14S	155
SV-15L	155
SV15R	1497
SV15R/S	1497
SV-16S	155
SV-18L	155
SV19R	1497
SV19R/S	1497
SV-20S	155
SV-22L	155
SV25R	1497
SV25R/S	1497
SV-25S	155
SV-28L	155
SV-30S	155
SV32R	1497
SV32R/S	1497
SV-35L	155
SV38R	1497
SV38R/S	1497
SV-38S	155
SV-42L	155
SV50R	1497
SV50R/S	1497
SV-6L	155
SV-6S	155
SV75R/S	1497
SV-8L	155
SV-8S	155
SVHC12-12RP	320
SVHC16-16RP	320
SVHC24-24RP	320
SVHC32-32RP	320
SVHC4-4RP	320
SVHC6-6RP	320
SVHC8-8RP	320
SVHN12-12RP	320
SVHN16-16RP	320
SVHN20-20RP	320
SVHN24-24RP	320
SVHN32-32RP	320

Code	Page
SVHN4-4RP	320
SVHN6-6RP	320
SVHN8-8RP	320
SVMC-10	884
SW14530PBK	1588
SWCLT-2	1514
SWCLT-3	1514
SWCLT-4	1514
SWCLT-5	1514
SWCLT-6	1514
SWCRT-2	1514
SWCRT-3	1514
SWCRT-4	1514
SWCRT-5	1514
SWCRT-6	1514
SWE-1000	170
SWE-250	170
SWE-375	170
SWE-500	170
SWE-750	170
SWH	190
SWHR-15-38	1452
SWHR-15-38SB122K	1452
SWHR-15N-38	1452
SWHR-30-38	1452
SWHR-30-38MB222K	1452
SWHR-30N-38	1452
SWIV.13A	1625
SWIV.15A	1625
SWIV.1A	1625
SWIV.31A	1625
SWIV.3A	1625
SW-ST4	1670
SW-ST6	1670
SWU-1000	170
SWU-125	170
SWU-250	170
SWU-375	170
SWU-500	170
SWU-750	170
SZ-12-031025-10	1485
SZ-12-031025-30	1485
SZ-12-044019-10	1485
SZ-12-044025-10	1485
SZ-12-044032-10	1485
SZ-12-051038-10	1485
SZ-12-066025-10	1485
SZ-12-066025-30	1485
SZ-12-066032-10	1485
SZ-12-066045-10	1485
SZ-12-066045-19	1485
SZ-12-066045-30	1485
SZ-12-066052-10	1485
SZ-12-066052-19	1485
SZ-12-066052-30	1485
SZ-12-066060-10	1485
SZ-12-081065-10	1485
SZ-12-081065-19	1485
SZ-12-089065-10	1485
SZ-12-089065-19	1485
SZ-12-089070-10	1485
SZ-12-089075-10	1485
SZ-12-089075-19	1485
SZ-12-089080-10	1485
SZ-12-105090-10	1485
SZ-12-115100-10	1485
SZ-12-115100-19	1485
SZ-12-133100-10	1485
SZ-12-133110-10	1485
SZ-12-160150-10	1485
SZ-12-160150-19	1485
SZ-12-220205-10	1485
SZ-13-089075-10	1485
SZ-13-166050-10	1485
SZ-13-800050-10	1486
SZ-13-800075-10	1486
SZ-13-800100-10	1486
SZ-21-031050-10	1485
SZ-21-031075-10	1485
SZ-21-031100-10	1485
SZ-21-031100-30	1485
SZ-21-044100-10	1485
SZ-21-044125-10	1485
SZ-21-051150-10	1485
SZ-21-051200-10	1485
SZ-21-051200-30	1485
SZ-21-066100-15	1485
SZ-21-066150-15	1485
SZ-21-066200-15	1485
SZ-21-066200-35	1485
SZ-21-066250-15	1485
SZ-21-066250-30	1485
SZ-21-081200-10	1485
SZ-21-081200-30	1485
SZ-21-081250-10	1485
SZ-21-089200-15	1485
SZ-21-089250-15	1485
SZ-21-089300-15	1485
SZ-21-105300-10	1485
SZ-21-115400-10	1485
SZ-21-133400-10	1485
SZ-21-133450-10	1485
SZ-21-220800-10	1485
SZ-22-031100-10	1485
SZ-22-044100-10	1485
SZ-22-051150-10	1485
SZ-22-066125-15	1485
SZ-22-066150-15	1485
SZ-22-066200-15	1485
SZ-22-066200-30	1485
SZ-22-081250-10	1485
SZ-22-089250-15	1485
SZ-22-089300-15	1485
SZ-22-133400-10	1485
SZ-27-066200-10	1485
SZ-27-089300-10	1485
SZ-27-133400-10	1485
SZ-27-148500-10	1485
SZ-27-160600-10	1485
SZ-31-031000-10	1486
SZ-31-031000-30	1486
SZ-31-044000-10	1486
SZ-31-051000-10	1486
SZ-31-066000-10	1486
SZ-31-066000-30	1486
SZ-31-081000-10	1486
SZ-31-089000-10	1486
SZ-31-105000-10	1486
SZ-31-115000-10	1486
SZ-31-133000-10	1486
SZ-31-148000-10	1486
SZ-31-160000-10	1486
SZ-31-500089-10	1486
SZ-31-500133-10	1486
SZ-35-066044-10	1486
SZ-35-081066-10	1486
SZ-35-115089-10	1486
SZ-35-160133-10	1486
SZ-71-031031-50	1486
SZ-71-081051-50	1486
SZ-71-089066-20	1486
SZ-71-133066-20	1486
SZ-91-002031-00	1486
SZ-91-002031-02	1486
SZ-91-002044-00	1486
SZ-91-002044-02	1486
SZ-91-002051-00	1486
SZ-91-002051-02	1486
SZ-91-002066-00	1486
SZ-91-002066-02	1486
SZ-91-002066-03	1486
SZ-91-002081-00	1486
SZ-91-002081-02	1486
SZ-91-002089-00	1486
SZ-91-002089-02	1486
SZ-91-002115-02	1486
SZ-91-002133-00	1486
SZ-91-002133-02	1486
SZ-91-002148-00	1486
SZ-91-002160-00	1486
SZ-91-002220-00	1486
T	
T1000C1800	634
T1000C2800	634
T1000C3800	634
T1000C4800	634
T1000M0500	634
T10-UTL	153
T10-UTS	153
T1100C1800	634
T1100C2800	634
T-110-UPVC	1103
T12	142
T-125-UPVC	1103
T12-UTL	153
T12-UTS	153
T-140-UPVC	1103
T14-UTS	153
T15-UTL	153
T16	142
T-160-UPVC	1103
T-16-UPVC	1103
T16-UTS	153
T17150	702
T171BEBD	700
T171BEMBD	700
T171BFB	702
T171BL	701
T171BPA	702
T171BPP	702
T171BRMA	701
T171BRMB	701
T171BRMC	701
T171BRMD	701
T171BVEB2	702
T171X	702
T171Y	702
T17250	702
T172BAP	702
T172BEBD	700
T172BEMBB	700
T172BEMBD	700
T172BEPBDA	701
T172BFB	702
T172BL	701
T172BRMA	701
T172BRMB	701
T172BRMC	701
T172BRMD	701
T172BVEB2	702
T172X	702
T173BEBD	700
T173BEMBD	700
T173BEPBDA	701
T173BFB	702
T173BL	701
T173BRMA	701
T173BRMC	701
T173BRMD	701
T173BVEB2	702
T173Y	702
T1740.01	706
T18-UTL	153
T1S-11-303	405
T1T-10	405
T1T-10-303	405
T-200-UPVC	1103
T20C1800	633
T20C2800	633
T20C3800	633
T20C4800	633
T20M0500	633
T-20-UPVC	1103
T20-UTS	153
T224.32.11.1	609
T224.32.11.11	609
T224.32.8.1	569
T224.32.9.1/2	569
T224.32.9/2	569
T224.32.9/3	569
T224.52.11.1	610
T224.52.11.11	610
T224.52.9.1/2	572
T224.52.9/1	572
T224.52.9/2	572
T224.52.9/3	572
T224.53.31.11.11	610
T224.53.31.9.1/2	574
T224.53.31.9.1/3	574
T224.53.31.9/2	574
T224.53.31.9/3	574
T224.53.32.11.11	610
T224.53.32.9.1/2	574
T224.53.32.9/2	574
T-225-UPVC	1103
T228.32.0.1	569
T228.32.11.1	609
T228.32.11.11	609
T228.32.2.1	569
T228.32.2.1/1	569
T228.32.2.1/2	569
T228.32.6.1/2	569
T228.32.6.1/3	569
T228.32.6.25	569
T228.32.6.27	569
T228.32.6.28	569
T228.32.9/2	569
T228.52.1.1	572
T228.52.11.1	610
T228.52.11.11	610
T228.52.2.1/2	572
T228.52.55/2	572
T228.52.6.25	572
T228.52.6.27	572
T228.52.6.28	572
T228.52.9.1/3	572
T228.52.9/1	572
T228.52.9/2	572
T228.53.31.9/2	574
T228.53.32.9.1/1	574
T228.53.32.9.1/2	574
T228.53.32.9/2	574
T22-UTL	153
T24	142
T-25-UPVC	1103
T25-UTS	153
T28-UTL	153
T2S-15-303	405
T2S-16-303	405
T2T-15-303	405
T2T-16	405
T3010-1	978
T3010-112	978
T3010-114	978
T3010-12	978
T3010-2	978
T3010-34	978
T3020 09	978
T30-UTS	153
T-32-UPVC	1103
T35-UTL	153
T38-UTS	153
T3S-20-303	405
T3T-21	405
T4	142
T401A215A	418
T401A251A	418
T401A251C	418
T401F215A	418
T401F215C	418
T401F251A	418
T401F251C	418
T-40-UPVC	1103
T424.00	599
T424.01	599
T424.52.0.1.E.M2	598
T42-UTL	153
T488.01	599
T488.32.11.1	609
T488.32.11.11	609
T488.52.0.0.M2	598
T488.52.0.1.M2	598
T488.52.0.12E.M2	598
T488.52.0.1E.M2	598
T488.52.11.1	610
T488.52.11.11	610
T488.53.31.11.11	610
T4T-25	405
T5	142
T50P0004	864
T50P0006	864
T50P0008	864
T50P0010	864
T50P0012	864
T-50-UPVC	1103
T6	142
T60C2890	633
T60C3890	633
T60C4890	633
T60C6890	633

Code	Page
T60C8890	633
T633.4/025X10	1433
T633.4/025X40	1433
T633.4/032X40	1433
T633.4/038X10	1433
T633.4/038X40	1433
T-63-UPVC	1103
T64T-4GB-P1N	685
T65C1800	633
T65C2800	633
T68C-6GB-B2N	685
T6T-31	405
T6-UTL	153
T6-UTS	153
T70C1800	634
T70C2800	634
T70C3800	634
T70C4800	634
T-75-UPVC	1103
T8	142
T82T-2GA-B1N	687
T84T-3GA-B1N	687
T84T-4GA-B1N	687
T850-175	1513
T850-200	1513
T850-250	1513
T850-300	1513
T850-350	1513
T850-400	1513
T850-500	1513
T850-550	1513
T850-600	1513
T850-650	1513
T850-800	1513
T850-850	1513
T8-UTL	153
T8-UTS	153
T-90-UPVC	1103
TA10	1173
TA13	1173
TA17	1173
TA21	1173
TA26	1173
TA33	1173
TABLE-D-112	1195
TABLE-D-4	1195
TABLE-E-1	1195
TABLE-E-112	1195
TABLE-E-2	1195
TABLE-E-3	1195
TAC110401	1729
TAC110601	1729
TAC111001	1729
TAC111201	1729
TAC111301	1729
TAC14F	329
TAC14HT	329
TAC14M	329
TAC16HL133	1734
TAC190501	1729
TAC2131151	1729
TAC31041	1729
TAC32041	1729
TAC38F	329
TAC38HT	329
TAC38M	329
TAC51051	1730
TAC51118B	1730
TAC516HT	329
TACSD0065	1729
TACSD0195	1729
TACSD30136	1736
TACSD30186	1736
TACSD30256	1736
TACSD30266	1736
TACSD30336	1736
TACSD3091	1734
TACSD3165	1729
TACSD5051	1729
TACSE0051	1734
TACSH1121	1730
TAP14F	329
TAP14HT	329
TAP14M	329
TAP38F	329
TAP38HT	329
TAP38M	329
TAP516HT	329
TAPE	1391
TAPS14F	329
TAPS14HT	329
TAPS14M	329
TAPS38F	329
TAPS38HT	329
TAPS38M	329
TAPS516HT	329
TB05	1173
TB10	1173
TB13	1173
TB17	1173
TB1S-10	405
TB1S-11	405
TB1T-10	405
TB1T-11	405
TB21	1173
TB26	1173
TB2S-15	405
TB2S-16	405
TB2T-15	405
TB2T-16	405
TB33	1173
TB3S-20	405
TB3S-21	405
TB3T-20	405
TB3T-21	405
TB4S-25	405
TB4S-26	405
TB4T-25	405
TB4T-26	405
TB6S-30	405
TB6S-31	405
TB6T-30	405
TB6T-31	405
TBAR2	1480
TBAR3	1480
TBAR4	1480
TBF-EVO100-C12	421
TBF-EVO100-C38	421
TBF-EVO105-C12	421
TBF-EVO105-C38	421
TBF-EVO110-C12	421
TBF-EVO110-C38	421
TBF-EVO125-C12	421
TBF-EVO125-C38	421
TBF-EVO25-C12	421
TBF-EVO25-C38	421
TBF-EVO35-C12	421
TBF-EVO35-C38	421
TBF-EVO45-C12	421
TBF-EVO45-C38	421
TBF-EVO50-C12	421
TBF-EVO50-C38	421
TBF-EVO55-C12	421
TBF-EVO55-C38	421
TBF-EVO60-C12	421
TBF-EVO60-C38	421
TBF-EVO65-C12	421
TBF-EVO65-C38	421
TBF-EVO70-C12	421
TBF-EVO70-C38	421
TBF-EVO75-C12	421
TBF-EVO75-C38	421
TBF-EVO80-C12	421
TBF-EVO80-C38	421
TBF-EVO85-C12	421
TBF-EVO85-C38	421
TBF-EVO90-C12	421
TBF-EVO90-C38	421
TBF-EVO95-C12	421
TBF-EVO95-C38	421
TC10	1173
TC-10-114-UPVC	1107
TC13	1173
TC17	1173
TC21	1173
TC26	1173
TC-32-1-UPVC	1107
TC33	1173
TC93-112-ABS	1098
TC93-112-UPVC	1111
TC93-114-ABS	1098
TC93-114-UPVC	1111
TC93-12-ABS	1098
TC93-12-UPVC	1111
TC93-1-ABS	1098
TC93-1-UPVC	1111
TC93-212-ABS	1098
TC93-212-UPVC	1111
TC93-2-ABS	1098
TC93-2-UPVC	1111
TC93-34-ABS	1098
TC93-34-UPVC	1111
TC93-3-ABS	1098
TC93-3-UPVC	1111
TC93-4-ABS	1098
TC93-4-UPVC	1111
TCM5	1173
TCS100	435
TCS100-KIT	435
TCS60	435
TCSBSP112	1436
TCSBSP2	1436
TCSBSP3	1436
TCSBSP4	1436
TCSHT1	1436
TCSHT112	1436
TCSHT114	1436
TCSHT2	1436
TCSHT212	1436
TCSHT3	1436
TCSHT4	1436
TCSHT6	1436
TCSHT8	1436
TCUT0001	905
TCUT0101	905
TD10	1173
TD13	1173
TD17	1173
TD21	1173
TD26	1173
TD33	1173
TDG16C05	1725
TE-1000	312
TE-1000 RF	312
TE-10000-PSN	316
TE-10000-PSV	316
TE-10010	315
TE-10010 V	315
TE-10011	315
TE-10016	316
TE-10020	315
TE-10020 RV	315
TE-10020 UV	315
TE-10020 V	315
TE-10021	315
TE-10026	316
TE-1100	386
TE-1100 A	386
TE-11006	386
TE-11410	386
TE12	1207
TE-125	316
TE-1300	387
TE-1300 A	387
TE-1300 B	387
TE-1300 V	387
TE-13010	387
TE-13210	387
TE-1325	387
TE-13410	387
TE14	1207
TE-15010	316
TE-15010 UV	316
TE-15010 V	316
TE-15010 VUV	316
TE-15020	316
TE-15020 UV	316
TE-15020 V	316
TE18	1207
TE-1800	388
TE-1800 A	388
TE-1800 B	388
TE-1800 C	388
TE-18008	388
TE-18110	388
TE-18210	388
TE-18220	388
TE-18405	388
TE-18410	388
TE-18420	388
TE-2310	313
TE-2310 UV	313
TE-2310 V	313
TE-2320	313
TE-2320 UV	313
TE-2320 V	313
TE-250	312
TE-2500-PSN	316
TE-2510	313
TE-2510 RV	313
TE-2510 UV	313
TE-2510 V	313
TE-2516	316
TE-2520	313
TE-2520 RV	313
TE-2520 UV	313
TE-2520 V	313
TE-2526	316
TE316	1207
TE34	1207
TE38	1207
TE-3800-PSN	316
TE-3800-PSV	316
TE-3810	314
TE-3810 H	314
TE-3810 HV	314
TE-3810 RV	314
TE-3810 UV	314
TE-3810 V	314
TE-3811	314
TE-3811 V	314
TE-3816	316
TE-3820	314
TE-3820 RUV	314
TE-3820 RV	314
TE-3820 UV	314
TE-3820 V	314
TE-3821	314
TE-3821 RV	314
TE-3821 V	314
TE-3826	316
TE43-112-ABS	1097
TE43-112-UPVC	1109
TE43-114-ABS	1097
TE43-114-UPVC	1109
TE43-12-ABS	1097
TE43-12-UPVC	1109
TE43-1-ABS	1097
TE43-1-UPVC	1109
TE43-212-ABS	1097
TE43-212-UPVC	1109
TE43-2-ABS	1097
TE43-2-UPVC	1109
TE43-34-ABS	1097
TE43-34-UPVC	1109
TE43-3-ABS	1097
TE43-3-UPVC	1109
TE43-4-ABS	1097
TE43-4-UPVC	1109
TE43-5-ABS	1097
TE43-5-UPVC	1109
TE43-6-ABS	1097
TE43-6-UPVC	1109
TE43-8-UPVC	1109
TE-45-110-UPVC	1102
TE-45-16-UPVC	1102
TE-45-20-UPVC	1102
TE-45-25-UPVC	1102
TE-45-32-UPVC	1102
TE-45-40-UPVC	1102
TE-45-50-UPVC	1102
TE-45-63-UPVC	1102
TE-45-75-UPVC	1102
TE-500	312
TE-500 B	312
TE-5000-PSN	316
TE-5000-PSV	316
TE-5010	314
TE-5010 RV	314
TE-5010 UV	314

Code	Page
TE-5010 V	314
TE-5011	314
TE-5011 RV	314
TE-5011 V	314
TE-5016	316
TE-5020	314
TE-5020 RV	314
TE-5020 UV	314
TE-5020 V	314
TE-5021	314
TE-5021 RV	314
TE-5021 V	314
TE-5026	316
TE516	1207
TE-750	312
TE-750 RF	312
TE-7500-PSN	316
TE-7500-PSV	316
TE-7510	315
TE-7510 RV	315
TE-7510 UV	315
TE-7510 V	315
TE-7510 VUV	315
TE-7511	315
TE-7511 V	315
TE-7516	316
TE-7520	315
TE-7520 S	315
TE-7520 UV	315
TE-7520 V	315
TE-7521	315
TE-7521 V	315
TE-7526	316
TE-90-16-UPVC	1102
TE-90-20-UPVC	1102
TE-90-25-UPVC	1102
TE-90-32-UPVC	1102
TE-90-40-UPVC	1102
TE-90-50-UPVC	1102
TE-90-63-UPVC	1102
TE-90-75-UPVC	1102
TEMBVFF-1/2	927
TEMBVFF-1/4	927
TEMBVFF-3/8	927
TEMBVMF-1/2	927
TEMBVMF-1/4	927
TEMBVMF-3/8	927
TERR-80.06-2	1558
TERR-80.10-2	1558
TERR-80.13-2	1558
TERR-80.16-2	1558
TERR-80.19-2	1558
TERR-80.25-2	1558
TERR-80.28-2	1558
TERR-80.38-3	1558
TERR-81.06-2	1558
TERR-81.10-2	1558
TERR-81.16-2	1558
TERR-81.19-2	1558
TERR-81.25-2	1558
TERR-81.38-3	1558
TERR-90.02-2	1558
TE-TFF10021	312
TE-TFF5010	312
TE-TFF5020	312
TE-TFF7510	312
TE-TFF7520	312
TE-TIF2510	313

Code	Page
TE-TIF2520	313
TE-TIF3810	313
TE-TIF3810-50	313
TE-TIF3811	313
TE-TIF3820	313
TE-TIF3820-50	313
TE-TIF3821	313
TE-TIF5010	313
TE-TIF5010 75	313
TE-TIF5011	313
TE-TIF5020	313
TE-TIF5020 75	313
TE-TIF5021	313
TF1010QLBP2HG24A	251
TF310QLBP2EG121	251
TF610QLBP2EG203	251
TF810QLBP2EG243	251
TFM01VG10	439
TFM01VL4	439
TFM02VG16	439
TFM02VL7	439
TFM03VG40	439
TFM03VL18	439
TFM04VG60	439
TFM05VG160	439
TFM05VL70	439
TFM06VG250	439
TFM07VG350	439
TFM07VL150	439
TFM08VG250	439
TFM09VG350	439
TFM10VG400	439
TFM10VL220	439
TFM11VG500	439
TFM11VL300	439
TFM12VG600	439
TFM12VL360	439
TFM13VG850	439
TFM13VL450	439
TFM14VG1200	439
TFM14VL550	439
TFM15VG1400	439
TFM15VL750	439
TG04BOX	1763
TG-3	1721
TG-4	1721
TG5121806	1731
TG5126101	1731
THKTAC01120	1738
THKTHP21426	1737
THL013AAA2	1740
THMFK0156	1731
THP10104132	316
THP10104172	316
THP1020413	316
THP1020417	316
THP15104132	316
THP1520413	316
THP16	316
THPTCS71621	1738
THT-10	1144
THT101066	1734
THT101086	1734
THT101106	1734
THT101126	1734
THT1022121	1739
THT1022122	1739
THT102286	1739

Code	Page
THT1023121	1739
THT102386	1739
THT1024121	1739
THT102486	1739
THT102RK061	1739
THT10309328	1734
THT106126	1738
THT106146	1738
THT1061826	1737
THT1061836	1737
THT106191	1737
THT106291	1737
THT106292	1737
THT106386	1738
THT106391	1737
THT10701	1740
THT111051	1741
THT113146	1732
THT113246	1732
THT113426	1731
THT11386	1732
THT115102	1731
THT115242	1731
THT115362	1731
THT11561	1731
THT121251	1738
THT-13	1144
THT13141	1740
THT13161	1740
THT1320502	1740
THT1320801	1740
THT1321401	1740
THT141451	1738
THT15101	1733
THT16241	1741
THT16P1011	1741
THT16P2031	1741
THT170806	1734
THT171102	1734
THT171142	1734
THT171186	1734
THT171206	1734
THT171246	1734
THT171366	1734
THT171486	1734
THT172011	1734
THT172021	1734
THT191001	1733
THT191002	1733
THT210706S	1733
THT210806	1733
THT210906S	1733
THT220606	1733
THT220806S	1733
THT22386	1734
THT230706	1733
THT24616	1733
THT250201	1735
THT250606	1735
THT250608	1735
THT250610	1735
THT250618	1735
THT250726	1735
THT25616	1731
THT260606	1733
THT281006	1733
THT28101	1733
THT2881	1733

Code	Page
THT290801	1733
THT2K0301S	1733
THT32105	1730
THT41K0401	1732
THT421441	1738
THT431482	1732
THT-5	1144
THT513613	1731
THT522106	1731
THT523106	1731
THT53321	1731
THT53351	1731
THT53422	1731
THT54106	1730
THT54166	1730
THT55206D	1730
THT59126	1730
THT59126B	1730
THT-6	1144
THT6146	1740
THT6186	1740
THT7143166	1732
THT715006	1732
THT7215006	1732
THT74246	1732
THT750416	1732
THT761616	1732
THT77406	1732
THT79021	1732
THT-8	1144
THT91462	1730
THT918516	1730
THT92102	1730
THTGTS8200	1735
THTIS4100	1736
THTIS5125	1736
THTIS566	1736
THTST12131	1738
THTST12211	1738
THTST12321	1738
THV-06L-2EO-WDS	163
THV-06S-4EO-WDS	163
THV-08L-4EO-WDS	163
THV-08S-4EO-WDS	163
THV-10L-4EO-WDS	163
THV-10S-4EO-WDS	163
THV-10S-6EO-WDS	163
THV-12L-4EO-WDS	163
THV-12L-6EO-WDS	163
THV-12S-6EO-WDS	163
THV-14S-8EO-WDS	163
THV-15L-8EO-WDS	163
THV-16S-8EO-WDS	163
THV-18L-8EO-WDS	163
THV-20S-12EO-WDS	163
THV-22L-12EO-WDS	163
THV-25S-16EO-WDS	163
THV-28L-16EO-WDS	163
THV-30S-20EO-WDS	163
THV-35L-20EO-WDS	163
THV-38S-24EO-WDS	163
THV-42L-24EO-WDS	163
THV-4LL-2EO-WDS	163
THV-6LL-2EO-WDS	163
THV-8LL-2EO-WDS	163
THWS010901	1679
TI10	1173
TI13	1173

Code	Page
TI17	1173
TI21	1173
TI26	1173
TI33	1173
TIGERTAIL-51-15	1415
TIM5	1173
TKL05	1173
TKL10	1173
TKL13	1173
TKL17	1173
TKL21	1173
TKL26	1173
TKL33	1173
TM-A	190
TM-A/B1	190
TM-A/B1SSVISITEC	192
TM-A/B1VISITEC	192
TM-B2	190
TM-B2-SS	190
TM-C1	190
TM-C1-SS	190
TM-C4	190
TM-C4-SS	190
TMT126031	1739
TMT126052	1739
TMT126101	1739
TMT20605M	1740
TMT21005M	1740
TMT321501	1739
TMT322001	1739
TNI02	1200
TNI03	1200
TNI04	1200
TNI05	1200
TNI06	1200
TNI08	1200
TNI10	1200
TNI12	1200
TNM04	1197
TNM05	1197
TNM06	1197
TNM08	1197
TNM10	1197
TNM12	1197
TNM15	1197
TNM16	1197
TNM22	1197
TNM28	1197
TO06NP	1174
TOOL-196506	1679
TOOL-196536	1714
TOOL-244973	1679
TOOL-371756	1679
TOOL-394989	1679
TOOL-580420	1714
TOOL-598438	1679
TOOL-630070	1683
TOOL-633595	1683
TOOL-656601	1679
TOOL-675108	1683
TOOL-719788	1683
TOOL-763556	1714
TOOL-783124	1714
TOOL-793753	1679
TOOL-868552	1680
TOOL-868573	1679
TOOL-868593	1683
TPG1H07	1725

Code	Page
TPG3H07	**1725**
TPG4H01	**1725**
TPM12T	**889**
TPM16T	**889**
TPM22T	**889**
TPR110QLBP2EG12E	**251**
TPR510QLBP2E2G20	**251**
TPR710QLBP2E2G24	**251**
TPTFE-04/025-10M	**909**
TPTFE-04/025-30M	**909**
TPTFE-06/040-10M	**909**
TPTFE-06/040-30M	**909**
TPTFE-08/060-10M	**909**
TPTFE-08/060-30M	**909**
TPTFE-10/080-10M	**909**
TPTFE-10/080-30M	**909**
TPTFE-12/010-10M	**909**
TPTFE-12/010-30M	**909**
TR-10-10-6L	**155**
TR-10-12-10L	**155**
TR-10-15-10L	**155**
TR-10-6-10L	**155**
TR-10-6-10S	**155**
TR-10-8-10L	**155**
TR-10-8-10S	**155**
TR-11050-UPVC	**1103**
TR-11075-UPVC	**1103**
TR-11090-UPVC	**1103**
TR-12-10-10L	**155**
TR-12-10-12L	**155**
TR-12-10-12S	**155**
TR-12-12-10L	**155**
TR-12-15-12L	**155**
TR-12-16-12S	**155**
TR-12-18-12L	**155**
TR-125110-UPVC	**1103**
TR-12563-UPVC	**1103**
TR-12575-UPVC	**1103**
TR-12590-UPVC	**1103**
TR-12-6-12L	**155**
TR-12-6-12S	**155**
TR-12-8-12L	**155**
TR-12-8-12S	**155**
TR-12-8-8L	**155**
TR-12-8-8S	**155**
TR-140110-UPVC	**1103**
TR-140125-UPVC	**1103**
TR-14075-UPVC	**1103**
TR-14090-UPVC	**1103**
TR-14-10-14S	**155**
TR-14-8-14S	**155**
TR-15-10-15L	**155**
TR-15-12-12L	**155**
TR-15-12-15L	**155**
TR-15-15-12L	**155**
TR-15-6-15L	**155**
TR-160110-UPVC	**1103**
TR-160125-UPVC	**1103**
TR-160140-UPVC	**1103**
TR-16090-UPVC	**1103**
TR-16-10-16S	**155**
TR-16-12-16S	**155**
TR-16-14-16S	**155**
TR-16-20-16S	**155**
TR-16-6-16S	**155**
TR-16-8-16S	**155**
TR-18-10-10L	**155**
TR-18-10-18L	**155**
TR-18-12-18L	**155**
TR-18-15-18L	**155**
TR-18-18-10L	**155**
TR-20-10-20S	**155**
TR-20-12-20S	**155**
TR-20-14-20S	**155**
TR-20-16-20S	**155**
TR-2016-UPVC	**1103**
TR-20-25-20S	**155**
TR-20-8-20S	**155**
TR-22-10-22L	**155**
TR-22-12-22L	**155**
TR-22-15-15L	**155**
TR-22-15-22L	**155**
TR-22-18-18L	**155**
TR-22-18-22L	**155**
TR-22-22-18L	**155**
TR-25-10-25S	**155**
TR-25-12-25S	**155**
TR-25-14-25S	**155**
TR-25-16-25S	**155**
TR-2516-UPVC	**1103**
TR-25-20-25S	**155**
TR-2520-UPVC	**1103**
TR-25-30-25S	**155**
TR-28-10-28L	**155**
TR-28-12-28L	**155**
TR-28-15-28L	**155**
TR-28-18-28L	**155**
TR-28-22-22L	**155**
TR-28-22-28L	**155**
TR-28-35-28L	**155**
TR-30-12-30S	**155**
TR-30-16-30S	**155**
TR-30-20-30S	**155**
TR-30-25-30S	**155**
TR-30-38-30S	**155**
TR-3216-UPVC	**1103**
TR-3220-UPVC	**1103**
TR-3225-UPVC	**1103**
TR-35-12-35L	**155**
TR-35-15-35L	**155**
TR-35-18-35L	**155**
TR-35-22-35L	**155**
TR-35-28-35L	**155**
TR-35-42-35L	**155**
TR-38-16-38S	**155**
TR-38-20-38S	**155**
TR-38-25-38S	**155**
TR-38-30-38S	**155**
TR-4016-UPVC	**1103**
TR-4025-UPVC	**1103**
TR-42-15-42L	**155**
TR-42-18-42L	**155**
TR-42-22-42L	**155**
TR-42-28-42L	**155**
TR-42-35-42L	**155**
TR-5020-UPVC	**1103**
TR-5025-UPVC	**1103**
TR-5032-UPVC	**1103**
TR-5040-UPVC	**1103**
TR-6-10-6L	**155**
TR-6325-UPVC	**1103**
TR-6332-UPVC	**1103**
TR-6340-UPVC	**1103**
TR-6350-UPVC	**1103**
TR-6-8-6L	**155**
TR-7532-UPVC	**1103**
TR-7540-UPVC	**1103**
TR-7550-UPVC	**1103**
TR-7563-UPVC	**1103**
TR-8-10-8L	**155**
TR-8-12-8L	**155**
TR-8-6-8L	**155**
TR-8-6-8S	**155**
TR-9040-UPVC	**1103**
TR-9050-UPVC	**1103**
TR-9063-UPVC	**1103**
TR-9075-UPVC	**1103**
TRI-092856	**1432**
TRI-092872	**1432**
TRI-100236	**1432**
TRI-100284	**1432**
TRI-145571	**1432**
TRI-145597	**1432**
TRI-145655	**1432**
TRI-145671	**1432**
TRICO12	**1422**
TRICO12-100M	**1422**
TRICO19	**1422**
TRICO19-100	**1422**
TRICO25	**1422**
TRICO25-100	**1422**
TS 10 L	**133**
TS 10 S	**133**
TS 12 L	**133**
TS 12 S	**133**
TS 14 S	**133**
TS 15 L	**133**
TS 16 S	**133**
TS 18 L	**133**
TS 20 S	**133**
TS 22 L	**133**
TS 25 S	**133**
TS 28 L	**133**
TS 30 S	**133**
TS 35 L	**133**
TS 38 S	**133**
TS 42 L	**133**
TS 6 L	**133**
TS 6 S	**133**
TS 8 L	**133**
TS 8 S	**133**
TS11-A/B1	**190**
TS11-A/B1-SS	**190**
TS11-A/B2	**190**
TS11-A/B2-SS	**190**
TS14-A/B1	**190**
TS14-A/B1-SS	**190**
TS14-A/B2	**190**
TS14-A/B2-SS	**190**
TSC06CS	**293**
TSC06CS-V	**293**
TSC08CS	**293**
TSC08CS-V	**293**
TS-C1	**190**
TSC12CS	**293**
TSC12CS-V	**293**
TSC16CS	**293**
TSC16CS-V	**293**
TS-C1-SS	**190**
TS-C2	**190**
TS-C2-SS	**190**
TSI250S	**842**
TSI312S	**842**
TSI375S	**842**
TSM 1	**954**
TSM 2	**954**
TSM 3	**954**
TSM 4	**954**
TSM 5	**954**
TSM10N	**880**
TSM15N	**880**
TSM22N	**880**
TSM28N	**880**
TSO-110-4-UPVC	**1101**
TSO-125-5-UPVC	**1101**
TSO-16-38-UPVC	**1101**
TSO-20-12-UPVC	**1101**
TSO-25-34-UPVC	**1101**
TSO-32-1-UPVC	**1101**
TSO-40-114-UPVC	**1101**
TSO-50-112-UPVC	**1101**
TSO-63-2-UPVC	**1101**
TSO-75-212-UPVC	**1101**
TSO-90-3-UPVC	**1101**
TSP06CS	**293**
TSP06CS-V	**293**
TSP08CS	**293**
TSP08CS-V	**293**
TSP12101	**1741**
TSP12CS	**293**
TSP12CS-V	**293**
TSP16CS	**293**
TSP16CS-V	**293**
TST-04/020	**909**
TST-06/040	**909**
TST-08/050	**909**
TST-10/080	**909**
TST-12/080	**909**
TT1	**1169**
TT12	**1169**
TT14	**1169**
TT18	**1169**
TT34	**1169**
TT38	**1169**
TT3T	**889**
TTE-08-10	**255**
TTE-08-10-A	**255**
TTE-08-25	**255**
TTE-12-10	**255**
TTE-12-10-A	**255**
TTE-12-25	**255**
TTE-16-10	**255**
TTE-16-10-A	**255**
TTE-16-25	**255**
TTE-20-10	**255**
TTE-20-10-A	**255**
TTE-20-25	**255**
TTF-08B-10	**255**
TTF-08B-25	**255**
TTF-12B-10	**255**
TTF-12B-25	**255**
TTF-16B-10	**255**
TTF-16B-25	**255**
TTF-20B-10	**255**
TTF-20B-25	**255**
TTF-SK-08	**255**
TTF-SK-12	**255**
TTF-SK-16	**255**
TTF-SK-20	**255**
TTH-BLUE	**1749**
TTH-GREY	**1749**
TTH-RED	**1749**
TV10/10/6L	**124**
TV10/10/6S	**124**
TV10/10/8L	**124**
TV10/10/8S	**124**
TV10L	**124**
TV10S	**124**
TV12/12/10L	**124**
TV12/12/10S	**124**
TV12/12/15L	**124**
TV12/12/6L	**124**
TV12/12/6S	**124**
TV12/12/8L	**124**
TV12/12/8S	**124**
TV12L	**124**
TV12S	**124**
TV14/14/10S	**124**
TV14/14/12S	**124**
TV14/14/6S	**124**
TV14/14/8S	**124**
TV14S	**124**
TV15/12/12L	**124**
TV15/15/10L	**124**
TV15/15/12L	**124**
TV15/15/6L	**124**
TV15/15/8L	**124**
TV15L	**124**
TV16/16/10S	**124**
TV16/16/12S	**124**
TV16/16/14S	**124**
TV16/16/6S	**124**
TV16/16/8S	**124**
TV16S	**124**
TV18/18/10L	**124**
TV18/18/12L	**124**
TV18/18/15L	**124**
TV18/18/6L	**124**
TV18/18/8L	**124**
TV18L	**124**
TV20/20/10S	**124**
TV20/20/12S	**124**
TV20/20/14S	**124**
TV20/20/16S	**124**
TV20/20/6S	**124**
TV20/20/8S	**124**
TV20S	**124**
TV22/22/10L	**124**
TV22/22/12L	**124**
TV22/22/15L	**124**
TV22/22/18L	**124**
TV22/22/8L	**124**
TV22L	**124**
TV25/25/10S	**124**
TV25/25/12S	**124**
TV25/25/14S	**124**
TV25/25/16S	**124**
TV25/25/20S	**124**
TV25/25/8S	**124**
TV25S	**124**
TV28/28/10L	**124**
TV28/28/12L	**124**
TV28/28/15L	**124**
TV28/28/18L	**124**
TV28/28/22L	**124**
TV28L	**124**
TV30/30/12S	**124**
TV30/30/14S	**124**
TV30/30/16S	**124**
TV30/30/20S	**124**

Code	Page
TV30/30/25S	124
TV30S	124
TV35/35/15L	124
TV35/35/18L	124
TV35/35/22L	124
TV35/35/28L	124
TV35L	124
TV38/38/10S	124
TV38/38/16S	124
TV38/38/20S	124
TV38/38/25S	124
TV38/38/30S	124
TV38S	124
TV42/42/15L	124
TV42/42/18L	124
TV42/42/22L	124
TV42/42/35L	124
TV42L	124
TV4LL	124
TV6L	124
TV6LL	124
TV6S	124
TV8/8/6L	124
TV8/8/6S	124
TV8L	124
TV8LL	124
TV8S	124
TVI-2	1113
TVR-20B	435
TWIN10656RY	899
TWIN12806RY	899
TWIN80505RY	899
TWV10L	136
TWV12L	136
TWV8L	136
TY-16-UPVC	1103
TY-20-UPVC	1103
TY-25-UPVC	1103
TY-32-UPVC	1103
TY-40-UPVC	1103
TY43-112-UPVC	1109
TY43-114-ABS	1097
TY43-114-UPVC	1109
TY43-12-ABS	1097
TY43-12-UPVC	1109
TY43-1-ABS	1097
TY43-1-UPVC	1109
TY43-2-ABS	1097
TY43-2-UPVC	1109
TY43-34-ABS	1097
TY43-34-UPVC	1109
TY-50-UPVC	1103
TY-63-UPVC	1103
TZLD100	435
TZLD300	435
U	
U 12/16	510
U 160/200	510
U 20	510
U 25/32	510
U 40	510
U 41 125	510
U 50/63	510
U 80/100	510
U-10	175
U-1000	168
U-10-125	168
U-10-250	168
U-10-312	168
U-10-375	168
U-110-UPVC	1104
U-12	175
U-12-312	168
U-12-375	168
U-125	168
U-12-500	168
U-15	175
U-15-500	168
U-16	175
U-16-UPVC	1104
U-18	175
U-187	168
U-18-750	168
U-20-1000	168
U-20-500	168
U-20-FT	175
U-20-UPVC	1104
U-22	175
U-25	175
U-250	168
U-25-1000	168
U25-N6	760
U25-S3	760
U-25-UPVC	1104
U25-W3	760
U-3	175
U30-N6	760
U30-S3	760
U30-W3	760
U-312	168
U-3-125	168
U-32-UPVC	1104
U-375	168
U-4	175
U-40-UPVC	1104
U-4-125	168
U-4-250	168
U45-N6	760
U45-S3	760
U45-W3	760
U-500	168
U-50-UPVC	1104
U55-N6	760
U55-S3	760
U55-W3	760
U-6	175
U-6-125	168
U-625	168
U-6-250	168
U-6-312	168
U-63-UPVC	1104
U65-N6	760
U65-S3	760
U65-W3	760
U71	596
U72	596
U73	596
U74	596
U-750	168
U75-N6	760
U75-S3	760
U-75-UPVC	1104
U75-W3	760
U76	596
U77	596
U780280	1514
U780320	1514
U780350	1514
U780380	1514
U780410	1514
U780430	1514
U780450	1514
U780480	1514
U780510	1514
U780540	1514
U780580	1514
U780600	1514
U780640	1514
U780670	1514
U780700	1514
U780750	1514
U780770	1514
U780790	1514
U780800	1514
U780890	1514
U780920	1514
U780950	1514
U781000	1514
U781020	1514
U781100	1514
U781200	1514
U781250	1514
U7H	596
U7J	596
U7K	596
U-8	175
U-8-250	168
U-8-375	168
U-875	168
U-90-UPVC	1104
UBE3	1484
UBE4	1484
UC-10	176
UC-1000	170
UC-12	176
UC-125	170
UC-16	176
UC-18	176
UC-20	176
UC-25	176
UC-250	170
UC-3	176
UC-312	170
UC-375	170
UC-500	170
UC-6	176
UC-750	170
UC-8	176
UDM	1476
UDR4	1484
UDR5	1484
UDR6	1484
UE-10	176
UE-1000	170
UE-12	176
UE-125	170
UE-14	176
UE-15	176
UE-16	176
UE-18	176
UE-187	170
UE-20	176
UE-22	176
UE-25	176
UE-250	170
UE-3	176
UE-312	170
UE-375	170
UE-4	176
UE-500	170
UE-6	176
UE-625	170
UE-750	170
UE-8	176
UE-875	170
UFA4	1484
UGU020-0100	498
UGU020-0200	498
UGU020-0320	498
UGU020-0400	498
UGU020-0500	498
UGU032-0100	498
UGU032-0200	498
UGU032-0250	498
UGU032-0320	498
UGU032-0400	498
UGU032-0500	498
UGU040-0100	498
UGU040-0200	498
UGU040-0250	498
UGU040-0320	498
UGU040-0400	498
UGU040-0500	498
UGU050-0100	498
UGU050-0200	498
UGU050-0250	498
UGU050-0320	498
UGU050-0400	498
UGU050-0500	498
UGU063-0100	498
UGU063-0200	498
UGU063-0250	498
UGU063-0320	498
UGU063-0400	498
UGU063-0500	498
UIJ3	1484
UIJ4	1484
UIJ6	1484
ULC159/166	1548
ULC38/43	1548
ULC47/51	1548
UN12	1208
UN14	1208
UN18	1208
UN316	1208
UN34	1208
UN38	1208
UN516	1208
UN83-112-ABS	1098
UN83-112-UPVC	1110
UN83-114-ABS	1098
UN83-114-UPVC	1110
UN83-12-ABS	1098
UN83-12-UPVC	1110
UN83-1-ABS	1098
UN83-1-UPVC	1110
UN83-212-ABS	1098
UN83-212-UPVC	1110
UN83-2-ABS	1098
UN83-2-UPVC	1110
UN83-34-ABS	1098
UN83-34-UPVC	1110
UN83-3-ABS	1098
UN83-3-UPVC	1110
UN83-4-ABS	1098
UN83-4-UPVC	1110
UNC1/2X11/2	108
UNC1/2X13/4	108
UNC3/4X21/2	108
UNC3/8X11/2	108
UNC3/8X11/4	108
UNC5/16X11/4	108
UNC5/8X2	108
UNC7/16X11/2	108
UNC7/16X13/4	108
UNH	190
UNITOP	1654
UNR3	1484
UNR4	1484
UP10-14	1168
UP10-18	1168
UP10-38	1168
UP1-1	1165
UP11-112F	1168
UP11-114F	1168
UP1-112	1165
UP11-12F	1168
UP11-14	1169
UP1-114	1165
UP11-18	1169
UP1-12	1165
UP11-2F	1168
UP11-34F	1168
UP1-14	1165
UP1-18	1165
UP1-2	1165
UP12-1	1169
UP12-112	1169
UP12-112F	1169
UP12-114	1169
UP12-114F	1169
UP12-12	1169
UP12-12F	1169
UP12-14	1169
UP12-18	1169
UP12-1F	1169
UP12-32	1169
UP12-34	1169
UP12-34F	1169
UP12-38	1169
UP12-38F	1169
UP12-58	1169
UP12-78	1169
UP12-MM10	1169
UP12-MM12	1169
UP12-MM14	1169
UP12-MM14.1	1169
UP12-MM15	1169
UP12-MM16	1169
UP12-MM18	1169
UP12-MM20	1169
UP12-MM22	1169
UP12-MM24	1169
UP12-MM26	1169
UP12-MM28	1169
UP12-MM30	1169
UP12-MM34	1169
UP12-MM38	1169
UP13-1	1167
UP13-12	1167

Code	Page
UP13-12-34P	1167
UP13-12N	1167
UP13-14	1167
UP13-14-12N	1167
UP13-14-12P	1167
UP13-14-38N	1167
UP13-14-38P	1167
UP13-14N	1167
UP13-18	1167
UP13-18-14N	1167
UP13-18-14P	1167
UP13-18-14U	1167
UP13-18-38N	1167
UP13-18-38P	1167
UP13-18N	1167
UP13-1N	1167
UP13-34	1167
UP13-34-1P	1167
UP13-34N	1167
UP13-38	1167
UP13-38-12N	1167
UP13-38-12P	1167
UP13-38N	1167
UP1-34	1165
UP1-38	1165
UP13-M5-14	1167
UP13-M5-18	1167
UP13-M5-M5	1167
UP13-M6-14	1167
UP13-M6-18	1167
UP14-12	1168
UP14-18	1168
UP14-38	1168
UP15-12	1168
UP15-14	1168
UP15-18	1168
UP15-38	1168
UP16-1	1168
UP16-12	1168
UP16-14	1168
UP16-18	1168
UP16-34	1168
UP16-38	1168
UP17-12	1169
UP17-14	1169
UP17-18	1169
UP17-38	1169
UP18-12	1169
UP18-14	1169
UP18-18	1169
UP18-38	1169
UP19-14	1169
UP19-38	1169
UP20-1	1169
UP20-12	1169
UP20-14	1169
UP20-34	1169
UP20-38	1169
UP21-12	1169
UP21-14	1169
UP2-12-1	1165
UP2-12-14P	1165
UP2-12-34	1165
UP2-12-34P	1165
UP2-12-38P	1165
UP21-38	1169
UP2-14-12	1165
UP2-14-12P	1165
UP2-14-18P	1165
UP2-14-34	1165
UP2-14-38	1165
UP2-14-38P	1165
UP2-18-12	1165
UP2-18-14	1165
UP2-18-14P	1165
UP2-18-38	1165
UP22-12	1168
UP22-14	1168
UP22-18	1168
UP22-34	1168
UP22-38	1168
UP2-34-1	1165
UP2-34-12P	1165
UP2-34-1P	1165
UP2-38-12	1165
UP2-38-12P	1165
UP2-38-14P	1165
UP2-38-34	1165
UP3-1-114	1166
UP3-112-2	1166
UP3-114-112	1166
UP3-114-2	1166
UP3-12-1	1166
UP3-12-1N	1166
UP3-12-1P	1166
UP3-12-34	1166
UP3-12-34N	1166
UP3-12-34P	1166
UP3-14-1	1166
UP3-14-12	1166
UP3-14-12N	1166
UP3-14-12P	1166
UP3-14-1N	1166
UP3-14-1P	1166
UP3-14-34	1166
UP3-14-34N	1166
UP3-14-34P	1166
UP3-14-38	1166
UP3-14-38N	1166
UP3-14-38P	1166
UP3-14-M16	1166
UP3-14-M18	1166
UP3-14-M20	1166
UP3-14-M22	1166
UP3-18-12	1166
UP3-18-12N	1166
UP3-18-12P	1166
UP3-18-14	1166
UP3-18-14N	1166
UP3-18-14P	1166
UP3-18-38	1166
UP3-18-38N	1166
UP3-18-38P	1166
UP3-34-1	1166
UP3-34-114	1166
UP3-34-1N	1166
UP3-34-1P	1166
UP3-38-1	1166
UP3-38-12	1166
UP3-38-12N	1166
UP3-38-12P	1166
UP3-38-1P	1166
UP3-38-34	1166
UP3-38-34N	1166
UP3-38-34P	1166
UP3-38-M22	1166
UP3-M16-M20	1166
UP3-M16-M22	1166
UP3-M5-18	1166
UP4-1-12P	1166
UP4-12-14P	1166
UP4-12-34P	1166
UP4-12-38P	1166
UP4-12N	1166
UP4-12P	1166
UP4-1-34P	1166
UP4-1-38P	1166
UP4-14N	1166
UP4-18-14P	1166
UP4-18N	1166
UP4-18P	1166
UP4-1N	1166
UP4-34-14P	1166
UP4-34-38P	1166
UP4-38-14P	1166
UP4-38-18P	1166
UP4-38N	1166
UP4-MM05	1166
UP4-MM06	1166
UP4-MM08	1166
UP4-MM10	1166
UP4-MM12	1166
UP4-MM14	1166
UP4-MM16	1166
UP4-MM18	1166
UP4-MM20	1166
UP4-MM22	1166
UP4-MM26	1166
UP4-MM30	1166
UP5-12	1167
UP5-12N	1167
UP5-14	1167
UP5-14N	1167
UP5-18	1167
UP5-18N	1167
UP5-1N	1167
UP5-34N	1167
UP5-38	1167
UP6-1	1167
UP6-114	1167
UP6-12	1167
UP6-14	1167
UP6-14N	1167
UP6-18	1167
UP6-34	1167
UP6-34N	1167
UP6-38	1167
UP6-M5	1167
UP7-1	1168
UP7-112	1168
UP7-114	1168
UP7-12	1168
UP7-12C	1168
UP7-14	1168
UP7-14C	1168
UP7-18	1168
UP7-18C	1168
UP7-38	1168
UP7-38C	1168
UP7-MM05	1168
UP8-1	1168
UP8-112	1168
UP8-114	1168
UP8-12	1168
UP8-12N	1168
UP8-14	1168
UP8-14N	1168
UP8-18	1168
UP8-18N	1168
UP8-34	1168
UP8-38	1168
UP9-12	1168
UP9-14	1168
UP9-18	1168
UP9-38	1168
UPS1	1421
UPT3	1484
UPT4	1484
UPT6	1484
UPVC/7TUBE-3-1	1113
UPVC/7TUBE-3-112	1113
UPVC/7TUBE-3-12	1113
UPVC/7TUBE-3-2	1113
UPVC/7TUBE-6-112	1113
UPVC/CTUBE-3-2	1112
UPVC/CTUBE-3-212	1112
UPVC/CTUBE-3-3	1112
UPVC/CTUBE-3-4	1112
UPVC/CTUBE-3-6	1112
UPVC/CTUBE-3-8	1112
UPVC/CTUBE-6-2	1112
UPVC/CTUBE-6-212	1112
UPVC/CTUBE-6-3	1112
UPVC/CTUBE-6-4	1112
UPVC/CTUBE-6-5	1112
UPVC/CTUBE-6-6	1112
UPVC/ETUBE-3-1	1112
UPVC/ETUBE-3-112	1112
UPVC/ETUBE-3-114	1112
UPVC/ETUBE-3-12	1112
UPVC/ETUBE-3-2	1112
UPVC/ETUBE-3-3	1112
UPVC/ETUBE-3-34	1112
UPVC/ETUBE-3-4	1112
UPVC/ETUBE-6-1	1112
UPVC/ETUBE-6-112	1112
UPVC/ETUBE-6-114	1112
UPVC/ETUBE-6-12	1112
UPVC/ETUBE-6-2	1112
UPVC/ETUBE-6-3	1112
UPVC/ETUBE-6-34	1112
UPVC/ETUBE-6-4	1112
UPVC/TUBE-3-110	1106
UPVC/TUBE-3-140	1106
UPVC/TUBE-3-16	1106
UPVC/TUBE-3-160	1106
UPVC/TUBE-3-20	1106
UPVC/TUBE-3-225	1106
UPVC/TUBE-3-25	1106
UPVC/TUBE-3-32	1106
UPVC/TUBE-3-40	1106
UPVC/TUBE-3-50	1106
UPVC/TUBE-3-63	1106
UPVC/TUBE-3-75	1106
UPVC/TUBE-3-90	1106
UPVC/TUBE-6-110	1106
UPVC/TUBE-6-140	1106
UPVC/TUBE-6-16	1106
UPVC/TUBE-6-160	1106
UPVC/TUBE-6-20	1106
UPVC/TUBE-6-225	1106
UPVC/TUBE-6-25	1106
UPVC/TUBE-6-32	1106
UPVC/TUBE-6-40	1106
UPVC/TUBE-6-50	1106
UPVC/TUBE-6-63	1106
UPVC/TUBE-6-75	1106
UPVC/TUBE-6-90	1106
UPVCBR-110	1105
UPVCBR-20	1105
UPVCBR-25	1105
UPVCBR-32	1105
UPVCBR-40	1105
UPVCBR-50	1105
UPVCBR-63	1105
URU-102-10	1438
URU-152-10	1438
URU-203-10	1438
URU-25-10	1438
URU-32-10	1438
URU-38-10	1438
URU-51-10	1438
URU-76-10	1438
US-A	192
US-B2	192
USC-1	1478
USHT3	1484
USHT4	1484
USMT4	1484
UT-10	176
UT-1000	170
UT-110-UPVC	1104
UT-12	176
UT-125	170
UT-14	176
UT-15	176
UT-16	176
UT-16-UPVC	1104
UT-18	176
UT-187	170
UT-20	176
UT-20-UPVC	1104
UT-22	176
UT-25	176
UT-250	170
UT-25-UPVC	1104
UT-3	176
UT-312	170
UT-32-UPVC	1104
UT-375	170
UT-4	176
UT-40-UPVC	1104
UT-500	170
UT-50-UPVC	1104
UT-6	176
UT-625	170
UT-63-UPVC	1104
UT-750	170
UT-75-UPVC	1104
UT-8	176
UT-875	170
UT-90-UPVC	1104
UV-1688-025D	979
UV-1688-032D	979
UV-1688-050D	979
UW4	1484
V	
V03A286J-B613A	590
V03A486J-B613A	590
V03X286A-Q1213	590
V03X486J-B613A	590
V04A286M-B623A	590
V04A286M-B628A	590
V04A286M-B629A	590
V04A386L-B623A	590
V04A386L-B628A	590
V04A386L-B629A	590
V04A486L-B623A	590
V04A486L-B628A	590
V04A486L-B629A	590

Code	Page
V04B286M-B423A	590
V04B286M-B428A	590
V04B286M-B429A	590
V04X286A-Q1228	590
V04X286A-Q1229	590
V04X286M-B623A	590
V04X386L-B623A	590
V04X386L-B628A	590
V04X386L-B629A	590
V04X486L-B623A	590
V04X486L-B628A	590
V04X486L-B629A	590
V05A286M-B633A	590
V05A386M-B633A	590
V05A386M-B638A	590
V05A386M-B639A	590
V05A486M-B633A	590
V05A486M-B638A	590
V05A486M-B639A	590
V05B286M-B433A	590
V05X286A-Q1233	590
V05X286A-Q1238	590
V05X286A-Q1239	590
V05X286M-B633A	590
V05X286M-B638A	590
V05X386M-B633A	590
V05X486M-B633A	590
V05X486M-B638A	590
V05X486M-B639A	590
V07-200-NNLG	690
V10626-A13L	591
V10626-A18L	591
V10626-A19L	591
V604-M22-S01	894
V60A413A-A2000	591
V60A4D7A-XA090	591
V60A511A-A3000	591
V60A513A-A2000	591
V60A5D7A-XA090	591
V60A5DDA-XA020	591
V61B413A-A2000	591
V61B4D7A-XA090	591
V61B511A-A3000	591
V61B513A-A2000	591
V61B5D7A-XA090	591
V61B5DDA-XA020	591
V62C413A-A2000	591
V62C4D7A-XA090	591
V62C511A-A3000	591
V62C513A-A2000	591
V62C5D7A-XA090	591
V62C5DDA-XA020	591
V64H-NND-RMN	685
V68H-NND-RMN	685
V-ACO 12	1747
V-ACO 12 PTL	1747
V-ACO 18	1747
V-ACO 22	1747
V-ACO 39	1747
V-ACO 60	1747
V-ACO 9B30D	1747
V-ACO 9B9D	1747
VAG 10/25	1492
VAG 20/50	1492
VB10-A	709
VB10-CS	709
VB10-N	709
VB10-S	709
VB10-U	709
VB10-WS	709
VB10-WS-FDA	709
VB110-A	713
VB110B-A	714
VB110B-CS	714
VB110B-N	714
VB110B-S	714
VB110B-U	714
VB110B-WS	714
VB110B-WS-FDA	714
VB110-CS	713
VB110-N	713
VB110-S	713
VB110-U	713
VB110-WS	713
VB110-WS-FDA	713
VB12-A	709
VB12-CS	709
VB12-N	709
VB12-S	709
VB12-U	709
VB12-WS	709
VB12-WS-FDA	709
VB150-A	714
VB150-CS	714
VB150-N	714
VB150-S	714
VB150-U	714
VB150-WS	714
VB150-WS-FDA	714
VB15-A	709
VB15-CS	709
VB15-N	709
VB15-PU	709
VB15-S	709
VB15-U	709
VB15-WS	709
VB15-WS-FDA	709
VB17-A	710
VB17-CS	710
VB17-N	710
VB17-S	710
VB17-U	710
VB17-WS	710
VB17-WS-FDA	710
VB20-CS	710
VB20-N	710
VB20-PU	710
VB20-S	710
VB20-U	710
VB20-WS	710
VB20-WS-FDA	710
VB30-A	711
VB30-CS	711
VB30M-A	715
VB30M-CS	715
VB30M-N	715
VB30M-PU	715
VB30M-S	715
VB30M-U	715
VB30M-WS	715
VB30M-WS-FDA	715
VB30-N	711
VB30-PU	711
VB30-S	711
VB30-U	711
VB30-WS	711
VB30-WS-FDA	711
VB40-A	711
VB40-CS	711
VB40-N	711
VB40-PU	711
VB40-S	711
VB40-U	711
VB40-WS	711
VB40-WS-FDA	711
VB50-A	712
VB50-CS	712
VB50M-A	715
VB50M-CS	715
VB50M-N	715
VB50M-PU	715
VB50M-S	715
VB50M-U	715
VB50M-WS	715
VB50M-WS-FDA	715
VB50-N	712
VB50-PU	712
VB50-S	712
VB50-U	712
VB50-WS	712
VB50-WS-FDA	712
VB5-A	708
VB5-CS	708
VB5-N	708
VB5-S	708
VB5-U	708
VB5-WS	708
VB5-WS-FDA	708
VB6X-A	708
VB6X-CS	708
VB6X-N	708
VB6X-S	708
VB6X-U	708
VB6X-WS	708
VB6X-WS-FDA	708
VB75-A	712
VB75B-A	713
VB75B-CS	713
VB75B-N	713
VB75B-S	713
VB75B-U	713
VB75B-WS	713
VB75B-WS-FDA	713
VB75-CS	712
VB75-N	712
VB75-PU	712
VB75-S	712
VB75-U	712
VB75-WS	712
VB75-WS-FDA	712
VB8X-A	708
VB8X-CS	708
VB8X-N	708
VB8X-S	708
VB8X-U	708
VB8X-WS	708
VB8X-WS-FDA	708
VBL10-A	719
VBL10-CS	719
VBL10-N	719
VBL10-S	719
VBL10-U	719
VBL10-WS	719
VBL10-WS-FDA	719
VBL15-A	719
VBL15-CS	719
VBL15-N	719
VBL15-S	719
VBL15-U	719
VBL15-WS	719
VBL15-WS-FDA	719
VBL20-A	720
VBL20-CS	720
VBL20-N	720
VBL20-S	720
VBL20-U	720
VBL20-WS	720
VBL20-WS-FDA	720
VBL30-A	720
VBL30-CS	720
VBL30-N	720
VBL30-S	720
VBL30-U	720
VBL30-WS	720
VBL30-WS-FDA	720
VBL35M-A	721
VBL35M-CS	721
VBL35M-FDA-30	721
VBL35M-FDA-55	721
VBL35M-N	721
VBL35M-S	721
VBL35M-U	721
VBL35M-WS	721
VBL40-A	721
VBL40B-A	722
VBL40B-CS	722
VBL40B-FDA-30	722
VBL40B-FDA-55	722
VBL40B-N	722
VBL40B-S	722
VBL40B-U	722
VBL40B-WS	722
VBL40-CS	721
VBL40-N	721
VBL40-S	721
VBL40-U	721
VBL40-WS	721
VBL40-WS-FDA	721
VBL50-A	722
VBL50-CS	722
VBL50-N	722
VBL50-S	722
VBL50-U	722
VBL50-WS	722
VBL50-WS-FDA	722
VBU35-N	716
VBU35-PU	716
VBU35-S	716
VBU35-WS	716
VBU35-WS-FDA	716
VBU45-N	716
VBU45-PU	716
VBU45-S	716
VBU45-WS	716
VBU45-WS-FDA	716
VBU55-N	717
VBU55-PU	717
VBU55-S	717
VBU55-WS	717
VBU55-WS-FDA	717
VBV-1	925
VBV-12	925
VBV-14	925
VBV-34	925
VBV-38	925
VBX35-PU	718
VBX45-PU	718
VBX55-PU	718
VCAP10	1170
VCAP13	1170
VCAP17	1170
VCAP21	1170
VCAP26	1170
VCAP33	1170
VCAP42	1170
VCAP48	1170
VCN-1988-025	979
VCN-1988-040	979
VCN-1988-050	979
VCN2A-BN14K	425
VCN2C-BN14K	425
VCS102	756
VCS102C	756
VD30-A-18F	742
VD30-A-M10M	742
VD30-A-M8M	742
VD30-CS-18F	742
VD30-CS-M10M	742
VD30-CS-M8M	742
VD30-N-18F	742
VD30-N-M10M	742
VD30-N-M8M	742
VD30-PU-18F	742
VD30-PU-M10M	742
VD30-PU-M8M	742
VD30-S-18F	742
VD30-S-M10M	742
VD30-S-M8M	742
VD30-U-18F	742
VD30-U-M10M	742
VD30-U-M8M	742
VD30-WS-18F	742
VD30-WS-FDA-18F	742
VD30-WS-FDA-M10M	742
VD30-WS-FDA-M8M	742
VD30-WS-M10M	742
VD30-WS-M8M	742
VD40-A-18F	743
VD40-A-M10M	743
VD40-A-M8M	743
VD40-CS-18F	743
VD40-CS-M10M	743
VD40-CS-M8M	743
VD40-N-18F	743
VD40-N-M10M	743
VD40-N-M8M	743
VD40-PU-18F	743
VD40-PU-M10M	743
VD40-PU-M8M	743
VD40-S-18F	743
VD40-S-M10M	743
VD40-S-M8M	743
VD40-U-18F	743
VD40-U-M10M	743
VD40-U-M8M	743
VD40-WS-18F	743
VD40-WS-FDA-18F	743
VD40-WS-FDA-M10M	743
VD40-WS-FDA-M8M	743
VD40-WS-M10M	743
VD40-WS-M8M	743
VD50-A-18F	744
VD50-A-M10M	744
VD50-A-M8M	744
VD50-CS-18F	744
VD50-CS-M10M	744
VD50-CS-M8M	744
VD50-N-18F	744
VD50-N-M10M	744
VD50-N-M8M	744

Code	Page
VD50-PU-18F	744
VD50-PU-M10M	744
VD50-PU-M8M	744
VD50-S-18F	744
VD50-S-M10M	744
VD50-S-M8M	744
VD50-U-18F	744
VD50-U-M10M	744
VD50-U-M8M	744
VD50-WS-18F	744
VD50-WS-FDA-18F	744
VD50-WS-FDA-M10M	744
VD50-WS-FDA-M8M	744
VD50-WS-M10M	744
VD50-WS-M8M	744
VD60-A-18F	745
VD60-A-M10M	745
VD60-A-M8M	745
VD60-CS-18F	745
VD60-CS-M10M	745
VD60-CS-M8M	745
VD60-N-18F	745
VD60-N-M10M	745
VD60-N-M8M	745
VD60-PU-18F	745
VD60-PU-M10M	745
VD60-PU-M8M	745
VD60-S-18F	745
VD60-S-M10M	745
VD60-S-M8M	745
VD60-U-18F	745
VD60-U-M10M	745
VD60-U-M8M	745
VD60-WS-18F	745
VD60-WS-FDA-18F	745
VD60-WS-FDA-M10M	745
VD60-WS-FDA-M8M	745
VD60-WS-M10M	745
VD60-WS-M8M	745
VD70-PU-18F	745
VD70-PU-M10M	745
VD70-PU-M8M	745
VD85-A-12F	746
VD85-A-18F	746
VD85-A-M10M	746
VD85-A-M8M	746
VD85-CS-12F	746
VD85-CS-18F	746
VD85-CS-M10M	746
VD85-CS-M8M	746
VD85-N-12F	746
VD85-N-18F	746
VD85-N-M10M	746
VD85-N-M8M	746
VD85-S-12F	746
VD85-S-18F	746
VD85-S-M10M	746
VD85-S-M8M	746
VD85-U-12F	746
VD85-U-18F	746
VD85-U-M10M	746
VD85-U-M8M	746
VD85-WS-12F	746
VD85-WS-18F	746
VD85-WS-FDA-12F	746
VD85-WS-FDA-18F	746
VD85-WS-FDA-M10M	746
VD85-WS-FDA-M8M	746
VD85-WS-M10M	746
VD85-WS-M8M	746
VD85X-A-18F	747
VD85X-CS-18F	747
VD85X-N-18F	747
VD85X-S-18F	747
VD85X-U-18F	747
VD85X-WS-18F	747
VD85X-WS-FDA-18F	747
VD90F-PU-12F	747
VD90F-PU-14F	747
VD90F-PU-18F	747
VD90F-PU-38F	747
VD90F-PU-H19	747
VD90F-PU-M10M	747
VDA10003	1055
VDA10004	1055
VDA10005	1055
VDA10006	1055
VDA10007	1055
VDA10008	1055
VDA10009	1055
VDA20003	1055
VDA20004	1055
VDA20005	1055
VDA20006	1055
VDA20007	1055
VDA20008	1055
VDA20009	1055
VDC-M22-S01	894
VDK10	1084
VDK138	1084
VDK20	1084
VDK21	1084
VDK30	1084
VDK31	1084
VDK34	1084
VDK35	1084
VE-32-UPVC	1107
VEC00478	433
VEC00493	433
VEC00511	433
VEC00515	433
VEC00518	433
VEC00519	434
VEC00525	433
VEC00528	433
VEC00529	434
VEC00534	433
VEC00535	433
VEC00536	434
VEC00644	433
VEC00645	433
VEC00680	433
VEC00707	433
VEC00709	433
VEC00728	433
VEC00739	433
VEC00873	433
VEC00901	434
VEC00906	434
VEC00908	434
VEC00909	434
VEC01095	433
VEC01237	433
VEC01249	433
VEC01250	433
VEC01251	433
VEC01294	433
VEC01295	433
VEC01296	433
VEC01732	433
VEC01733	433
VEC02139	433
VF110-A	734
VF110-CS	734
VF110-N	734
VF110-S	734
VF110-U	734
VF110-WS	734
VF110-WS-FDA	734
VF150-A	734
VF150-CS	734
VF150-N	734
VF150-S	734
VF150-U	734
VF150-WS	734
VF150-WS-FDA	734
VF15-A	731
VF15-CS	731
VF15-N	731
VF15-S	731
VF15-U	731
VF15-WS	731
VF15-WS-FDA	731
VF200-A	735
VF200-CS	735
VF200-N	735
VF200-S	735
VF200-U	735
VF200-WS	735
VF200-WS-FDA	735
VF20-A	731
VF20-CS	731
VF20-N	731
VF20-S	731
VF20-U	731
VF20-WS	731
VF20-WS-FDA	731
VF25-A	732
VF25-CS	732
VF25-N	732
VF25-S	732
VF25-U	732
VF25-WS	732
VF25-WS-FDA	732
VF300-A-34F	735
VF300-CS-34F	735
VF300-N-34F	735
VF300-S-34F	735
VF300-U-34F	735
VF300-WS-34F	735
VF300-WS-FDA-34F	735
VF30-A	732
VF30-CS	732
VF30-N	732
VF30-S	732
VF30-U	732
VF30-WS	732
VF30-WS-FDA	732
VF40-A	732
VF40-CS	732
VF40-N	732
VF40-PU	732
VF40-S	732
VF40-U	732
VF40-WS	732
VF40-WS-FDA	732
VF50-A	733
VF50-CS	733
VF50-N	733
VF50-PU	733
VF50-S	733
VF50-U	733
VF50-WS	733
VF50-WS-FDA	733
VF50X2-A	733
VF50X2-CS	733
VF50X2-N	733
VF50X2-S	733
VF50X2-U	733
VF50X2-WS	733
VF50X2-WS-FDA	733
VF75-A	733
VF75-CS	733
VF75-N	733
VF75-PU	733
VF75-S	733
VF75-U	733
VF75-WS	733
VF75-WS-FDA	733
VF90-PU	734
VFC100-A	739
VFC100-CS	739
VFC100-N	739
VFC100-PU	739
VFC100-S	739
VFC100-U	739
VFC100-WS	739
VFC100-WS-FDA	739
VFC50-A-1838MF	737
VFC50-CS-1838MF	737
VFC50-N-1838MF	737
VFC50-PU-1838MF	737
VFC50-S-1838MF	737
VFC50-U-1838MF	737
VFC50-WS-1838MF	737
VFC50-WS-FDA	737
VFC60-A-1838MF	737
VFC60-CS-1838MF	737
VFC60-N-1838MF	737
VFC60-PU-1838MF	737
VFC60-S-1838MF	737
VFC60-U-1838MF	737
VFC60-WS-1838MF	737
VFC60-WS-FDA	737
VFC60X1-A-M10M	737
VFC60X1-CS-M10M	737
VFC60X1-N-M10M	737
VFC60X1-PU-M10M	737
VFC60X1-S-M10M	737
VFC60X1-U-M10M	737
VFC60X1-WSA-FDA	737
VFC60X1-WS-M10M	737
VFC75-A-1838MF	738
VFC75-CS-1838MF	738
VFC75-N-1838MF	738
VFC75-PU-1838MF	738
VFC75-S-1838MF	738
VFC75-U-1838MF	738
VFC75-WS-1838MF	738
VFC75-WS-FDA	738
VFC75X1-A-M10M	738
VFC75X1-CS-M10M	738
VFC75X1-N-M10M	738
VFC75X1-S-M10M	738
VFC75X1-U-M10M	738
VFC75X1-WS-FDA	738
VFC75X1-WS-M10M	738
VFC75X2-A-M16M	738
VFC75X2-CS-M16M	738
VFC75X2-N-M16M	738
VFC75X2-S-M16M	738
VFC75X2-U-M16M	738
VFC75X2-WS-FDA	738
VFC75X2-WS-M16M	738
VFC90-PU	739
VFF1.2013.012	307
VFF1.2013.013	307
VFF1.2019.012	307
VFF1.2019.013	307
VFF1.2525.012	307
VFF1.2525.013	307
VFF1.3031.012	307
VFF1.3031.013	307
VFF1.3939.012	307
VFF1.3939.013	307
VFH1.2019.012	307
VFH1.2019.013	307
VFH1.2525.012	307
VFH1.2525.013	307
VFH1.3031.012	307
VFH1.3031.013	307
VFH1.3939.012	307
VFH1.3939.013	307
VFH1.5051.012	307
VFH1.5051.013	307
VFP10	1170
VFP13	1170
VFP17	1170
VFP21	1170
VFP26	1170
VFP33	1170
VFP42	1170
VFP48	1170
VFP52	1170
VFU2.E	627
VFU2.V	627
VFU3.E	627
VFU3.V	627
VFU4.E	627
VFU4.V	627
VFU8.E	627
VFU8.V	627
VG100-01D	412
VG100-01T	412
VG40-01B	412
VG40-01R	412
VG50-01B	412
VG50-01C	412
VG50-01R	412
VG50-01T	412
VG63-01BG	264
VG63-01C	412
VG63-01RG	264
VG63-01T	412
VGBP040118	411
VGBP060114	411
VGBU040118	411
VGBU060114	411
VHC12-12RP	318
VHC16-16RP	318
VHC20-20RP	318
VHC4-4RP	318
VHC6-6RP	318
VHC8-8RP	318
VHN12-12RP	318
VHN16-16RP	318
VHN20-20RP	318
VHN24-24RP	318
VHN4-4RP	318
VHN6-6RP	318

Code	Page
VHN8-8RP	318
VHP1	1170
VHP112P	1170
VHP114	1170
VHP114P	1170
VHP12	1170
VHP12N	1170
VHP12P	1170
VHP14	1170
VHP14N	1170
VHP14P	1170
VHP18	1170
VHP18N	1170
VHP18P	1170
VHP1P	1170
VHP2N	1170
VHP2P	1170
VHP34	1170
VHP34N	1170
VHP34P	1170
VHP38	1170
VHP38N	1170
VHP38P	1170
VHP58	1170
VHP58P	1170
VHPM05	1170
VHPM06	1170
VHPM08	1170
VHPM14	1170
VHPM16	1170
VHPM18	1170
VHPM20	1170
VHPM22	1170
VHPM24	1170
VHPM26	1170
VHPM28	1170
VIG 10/25	1492
VIG 15/35	1492
VIG 20/50	1492
VIK-297352	1683
VIK-297552	1683
VIK-299152	1683
VIK-475552	1683
VIK-475752	1683
VIK-524752	1683
VIK-525452	1683
VIK-545252	1683
VISCO.110	1635
VITON-1	1472
VITON-112	1472
VITON-114	1472
VITON-12	1472
VITON-2	1472
VITON-212	1472
VITON-3	1472
VITON-34	1472
VK10	1175
VK13	1175
VK17	1175
VK21	1175
VK26	1175
VK33	1175
VKA-10L	158
VKA-10S	158
VKA-12L	158
VKA-12S	158
VKA-14S	158
VKA-15L	158
VKA-16S	158
VKA-18L	158
VKA-20S	158
VKA-22L	158
VKA-25S	158
VKA-28L	158
VKA-30S	158
VKA-35L	158
VKA-38S	158
VKA-42L	158
VKA-6L	158
VKA-6S	158
VKA-8L	158
VKA-8S	158
VKM	1477
VKM-K	1477
VKO	1477
VMC1N	425
VMS 105 M5	563
VMS 112 1/2	563
VMS 114 1/4	563
VMS 118 1/8	563
VMS 134 3/4	563
VMS 138 3/8	563
VNC10003	1055
VNC10004	1055
VNC10005	1055
VNC10006	1055
VNC10007	1055
VNC10008	1055
VNC10009	1055
VNC20003	1055
VNC20004	1055
VNC20005	1055
VNC20006	1055
VNC20007	1055
VNC20008	1055
VNC20009	1055
VNR 1/8	636
VNR 843 07	636
VNR M5	636
VOBL35X90-A	727
VOBL35X90-CS	727
VOBL35X90-FDA	727
VOBL35X90-N	727
VOBL35X90-S	727
VOBL35X90-U	727
VOBL35X90-WS	727
VOU10X30-CS	726
VOU10X30-N	726
VOU10X30-S	726
VOU10X30-U	726
VOU10X30-WS	726
VOU10X30-WS-FDA	726
VOU15X45-CS	726
VOU15X45-N	726
VOU15X45-S	726
VOU15X45-U	726
VOU15X45-WS	726
VOU15X45-WS(FDA)	726
VOU20X60-CS	726
VOU20X60-N	726
VOU20X60-S	726
VOU20X60-U	726
VOU20X60-WS	726
VOU20X60-WS(FDA)	726
VOU4X10-CS	724
VOU4X10-N	724
VOU4X10-S	724
VOU4X10-U	724
VOU4X10-WS	724
VOU4X10-WS(FDA)	724
VOU4X20-CS	724
VOU4X20-N	724
VOU4X20-S	724
VOU4X20-U	724
VOU4X20-WS	724
VOU4X20-WS-FDA	724
VOU6X10-CS	724
VOU6X10-N	724
VOU6X10-S	724
VOU6X10-U	724
VOU6X10-WS	724
VOU6X10-WS(FDA)	724
VOU6X20-CS	725
VOU6X20-N	725
VOU6X20-S	725
VOU6X20-U	725
VOU6X20-WS	725
VOU6X20-WS-FDA	725
VOU8X20-CS	725
VOU8X20-N	725
VOU8X20-S	725
VOU8X20-U	725
VOU8X20-WS	725
VOU8X20-WS-FDA	725
VOU8X30-CS	725
VOU8X30-N	725
VOU8X30-S	725
VOU8X30-U	725
VOU8X30-WS	725
VOU8X30-WS-FDA	725
VP/SB4/5	1748
VP/SB7	1748
VP/SB8	1748
VP1204BG101Q00	635
VP1204BG401Q00	635
VP1208BG101Q00	635
VP1208BG401Q00	635
VP5002BJ111H00	635
VP5002BJ411H00	635
VP5006BJ111H00	635
VP5006BJ411H00	635
VP5008BJ411H00	635
VP5010BJ111H00	635
VP5010BJ411H00	635
VPC-M16-M16	894
VPC-M22-M16	894
VPQ1	1170
VPQ112	1170
VPQ114	1170
VPQ12	1170
VPQ14	1170
VPQ2	1170
VPQ34	1170
VPQ38	1170
VPS1	1170
VPS112	1170
VPS112N	1170
VPS112P	1170
VPS114	1170
VPS114N	1170
VPS12	1170
VPS12N	1170
VPS12P	1170
VPS14	1170
VPS14N	1170
VPS14P	1170
VPS18	1170
VPS18N	1170
VPS18P	1170
VPS1N	1170
VPS1P	1170
VPS2	1170
VPS2N	1170
VPS2P	1170
VPS34	1170
VPS34N	1170
VPS34P	1170
VPS38	1170
VPS38N	1170
VPS38P	1170
VPS58	1170
VPS58P	1170
VPS78	1170
VR-12	1596
VRG	256
VSC 522	636
VSC 544	636
VSC 588	636
VSD10L/SMMB	116
VSD12L/SMMB	116
VSD14SMMB	116
VSD15LMMB	116
VSD16SMMB	116
VSD18LMMB	116
VSD20SMMB	116
VSD22LMMB	116
VSD25SMMB	116
VSD28LMMB	116
VSD30SMMB	116
VSD35LMMB	116
VSD38SMMB	116
VSD42LMMB	116
VSD4LLMMB	116
VSD6L/SMMB	116
VSD6LLMMD	116
VSD8L/SMMB	116
VSD8LLMMD	116
VSG	256
VSK10L	116
VSK10S	116
VSK12L	116
VSK12S	116
VSK14S	116
VSK15L	116
VSK16S	116
VSK18L	116
VSK20S	116
VSK22L	116
VSK25S	116
VSK28L	116
VSK30S	116
VSK35L	116
VSK38S	116
VSK42L	116
VSK6L	116
VSK6S	116
VSK8L	116
VSK8S	116
VSM12X1.5WD	116
VSM14X1.5WD	116
VSM16X1.5WD	116
VSM18X1.5WD	116
VSM1-BNR14	425
VSM202	755
VSM203	755
VSM20X1.5WD	116
VSM22X1.5WD	116
VSM26X1.5WD	116
VSM27X2WD	116
VSM2-BNR14	425
VSM303	755
VSM33X2WD	116
VSM42X2WD	116
VSM48X2WD	116
VSM8X1.0WD	116
VSO 425 M5	636
VSO 426 04	636
VSR1/2WD	116
VSR1/4WD	116
VSR1/8WD	116
VSR11/2WD	116
VSR11/4WD	116
VSR1WD	116
VSR3/4WD	116
VSR3/8WD	116
VST 38/35	1492
VST 50	1492
VSTI-10M	158
VSTI-12EO	158
VSTI-12M	158
VSTI-14M	158
VSTI-16EO	158
VSTI-16M	158
VSTI-18M	158
VSTI-20EO	158
VSTI-20M	158
VSTI-22M	158
VSTI-24EO	158
VSTI-26M	158
VSTI-27M	158
VSTI-2EO	158
VSTI-33M	158
VSTI-42M	158
VSTI-48M	158
VSTI-4EO	158
VSTI-6EO	158
VSTI-8EO	158
VT9012525BKHOOK	1588
VTC3021-2	757
VTC3022-2	757
VTC3031-2	757
VTC3032-2	757
VTC3122-2	757
VTC3123-2	757
VTC3124-2	757
VTC3132-2	757
VTC3133-2	757
VTC3134-2	757
VTF01-118	761
VTF01-154	761
VTF02-118	761
VTF02-154	761
VTF-0706	761
VTF-1208	761
VTF12-141	761
VTF12-96	761
VTF34-141	761
VTF34-96	761
VTF38-141	761
VTF38-96	761
VTFE27.5-39096	761
VTFE27.5-39141	761
VTFE47.4-62118	761
VTFE47.4-62154	761
VTFE-B110	714
VTFE-B30	714
VTFE-B40	714
VTFE-B50	714
VTFE-B75	714
VTFE-BL20	722

Code	Page
VTFE-BL30	722
VTFE-BL40	722
VTFE-BL40B	722
VTFE-BL50	722
VTFE-BU35	717
VTFE-BU45	717
VTFE-BU55	717
VTFE-BX35	718
VTFE-BX45	718
VTFE-BX55	718
VTFE-OBL35X90	727
VU1.5X-A	728
VU1.5X-CS	728
VU1.5X-N	728
VU1.5X-S	728
VU1.5X-U	728
VU1.5X-WS	728
VU1.5X-WS(FDA)	728
VU10-A	730
VU10-CS	730
VU10-N	730
VU10-S	730
VU10-U	730
VU10-WS	730
VU10-WS(FDA)	730
VU2-A	728
VU2-CS	728
VU2-N	728
VU2-S	728
VU2-U	728
VU2-WS	728
VU2-WS(FDA)	728
VU2X-A	728
VU2X-CS	728
VU2X-N	728
VU2X-S	728
VU2X-U	728
VU2X-WS	728
VU2X-WS(FDA)	728
VU3-A	729
VU3-CS	729
VU3-N	729
VU3-S	729
VU3-U	729
VU3-WS	729
VU3-WS(FDA)	729
VU4-A	729
VU4-CS	729
VU4-N	729
VU4-S	729
VU4-U	729
VU4-WS	729
VU4-WS-FDA	729
VU4X-A	729
VU4X-CS	729
VU4X-N	729
VU4X-S	729
VU4X-U	729
VU4X-WS	729
VU4X-WS-FDA	729
VU6-A	730
VU6-CS	730
VU6-N	730
VU6-S	730
VU6-U	730
VU6-WS	730
VU6-WS-FDA	730
VU8-A	730
VU8-CS	730
VU8-N	730
VU8-S	730
VU8-U	730
VU8-WS	730
VU8-WS-FDA	730
VUP4.EM	627
VUP4.M	627
VUP4.VM	627
VUP8.EM	627
VUP8.M	627
VUP8.VM	627
VVV1.1010.002	304
VVV1.1010.003	304
VVV1.1313.002	304
VVV1.1313.003	304
VVV1.2019.002	304
VVV1.2019.003	304
VVV1.2525.002	304
VVV1.2525.003	304
VVV1.3031.002	304
VVV1.3031.003	304
VVV1.3939.002	304
VVV1.3939.003	304
VVV1.5051.002	304
VVV1.5051.003	304
VZ05	1175
VZ10	1175
VZ10K	1175
VZ13	1175
VZ13K	1175
VZ17	1175
VZ17K	1175
VZ21	1175
VZ21K	1175
VZ26	1175
VZ26K	1175
VZ33	1175
VZ33K	1175
W	
W0210010100	620
W0210011100	620
W0210012100	620
W0210013100	620
W0215000001	589
W0215000011	589
W0215000021	589
W0215000031	589
W0215000101	589
W0215000111	589
W0215000121	589
W0215000131	589
W0950000132	540
W0950000140	540
W0950000150	540
W0950000201	470
W0950000510	470
W0950000512	470
W0950000516	470
W0950000520	470
W0950000525	470
W0950000711	496
W0950000712	496
W0950000713	496
W0950001100	504
W0950001103	472
W0950060000	496
W0950080001	470
W0950080002	470
W0950080005	470
W0950080010	470
W0950080011	470
W0950080020	470
W0950080025	470
W0950120001	470
W0950120002	470
W0950120005	470
W0950120010	470
W0950120011	470
W0950120020	470
W0950120025	470
W0950200001	470
W0950200002	470
W0950200005	470
W0950200010	470
W0950200011	470
W0950200020	470
W0950200025	470
W0950320002	539
W0950320005	539
W0950320010	539
W0950322001	494
W0950322002	495
W0950322004	494
W0950322010	470
W0950322020	470
W0950322025	470
W0950322030	540
W0950322108	495
W0950326021	540
W0950400002	539
W0950400005	539
W0950400010	539
W0950402001	494
W0950402002	495
W0950402004	494
W0950402010	495
W0950402020	495
W0950402025	496
W0950402030	540
W0950402108	495
W0950406021	540
W0950500002	539
W0950500005	539
W0950500010	539
W0950502001	494
W0950502002	495
W0950502004	494
W0950502010	495
W0950502020	495
W0950502025	496
W0950502030	540
W0950502108	495
W0950506021	540
W0950632001	494
W0950632002	495
W0950632004	494
W0950632108	495
W0950802001	494
W0950802002	495
W0950802004	494
W0950802010	495
W0950802020	495
W0950802025	496
W0950802108	495
W0951002001	494
W0951002002	495
W0951002004	494
W0951002108	495
W0951252001	494
W0951252002	495
W0951252004	494
W0951252008	495
W0951252010	495
W0951252020	495
W0951252025	496
W0951602001	494
W0951602002	495
W0951602004	494
W0951602008	495
W0951602010	495
W0951602020	495
W0952002001	494
W0952002002	495
W0952002004	494
W0952002025	496
W0952022180	504
W0952028184	472
W095X120001	472
W095X120002	472
W095X120005	472
W095X120010	472
W095X120011	472
W095X120020	472
W095X200001	472
W095X200002	472
W095X200005	472
W095X200010	472
W095X200011	472
W095X200020	472
W095X322001	503
W095X322002	504
W095X322003	503
W095X322004	503
W095X322007	504
W095X322008	503
W095X322011	472
W095X322020	472
W095X322050	504
W095X402001	503
W095X402002	504
W095X402003	503
W095X402004	503
W095X402007	504
W095X402008	503
W095X402011	504
W095X402020	504
W095X402050	504
W095X502001	503
W095X502002	504
W095X502003	503
W095X502004	503
W095X502007	504
W095X502008	503
W095X502011	504
W095X502020	504
W095X502050	504
W095X632001	503
W095X632002	504
W095X632003	503
W095X632004	503
W095X632007	504
W095X632008	503
W095X632050	504
W095X802001	503
W095X802002	504
W095X802003	503
W095X802004	503
W095X802007	504
W095X802008	503
W095X802011	504
W095X802020	504
W095X802050	504
W095XA12001	503
W095XA12002	504
W095XA12003	503
W095XA12004	503
W095XA12007	504
W095XA12008	503
W095XA12050	504
W0970512000	831
W10-UEL	153
W10-UES	153
W1211600025	493
W1211600050	493
W1211600080	493
W1211600100	493
W1211600125	493
W1211600160	493
W1211600200	493
W1211600250	493
W1211600320	493
W1211600400	493
W1211600500	493
W1212000025	493
W1212000050	493
W1212000080	493
W1212000100	493
W1212000125	493
W1212000160	493
W1212000200	493
W1212000250	493
W1212000320	493
W1212000400	493
W1212000500	493
W1212500025	493
W1212500050	493
W1212500080	493
W1212500100	493
W1212500125	493
W1212500160	493
W1212500200	493
W1212500250	493
W1212500320	493
W1212500400	493
W1212500500	493
W1213200025	493
W1213200050	493
W1213200080	493
W1213200100	493
W1213200125	493
W1213200160	493
W1213200200	493
W1213200250	493
W1213200320	493
W1213200400	493
W1213200500	493
W12-UEL	153
W12-UES	153
W14-UES	153
W15-UEL	153
W16-UES	153
W1800160010	471
W1800160025	471
W1800160050	471
W1800160080	471
W1800160100	471
W1800160125	471
W1800160160	471
W1800160200	471
W1800160250	471
W1800160320	471

Code	Page
W1800200010	471
W1800200025	471
W1800200050	471
W1800200080	471
W1800200100	471
W1800200125	471
W1800200160	471
W1800200200	471
W1800200250	471
W1800200320	471
W1800200400	471
W1800250010	471
W1800250025	471
W1800250050	471
W1800250080	471
W1800250100	471
W1800250125	471
W1800250160	471
W1800250200	471
W1800250250	471
W1800250320	471
W1800250400	471
W1800250500	471
W1840320025	502
W1840320050	502
W1840320080	502
W1840320100	502
W1840320125	502
W1840320160	502
W1840320200	502
W1840320250	502
W1840320320	502
W1840320400	502
W1840320500	502
W1840400025	502
W1840400050	502
W1840400080	502
W1840400100	502
W1840400125	502
W1840400160	502
W1840400200	502
W1840400250	502
W1840400320	502
W1840400400	502
W1840400500	502
W1840500025	502
W1840500050	502
W1840500080	502
W1840500100	502
W1840500125	502
W1840500160	502
W1840500200	502
W1840500250	502
W1840500320	502
W1840500400	502
W1840500500	502
W1840630025	502
W1840630050	502
W1840630080	502
W1840630100	502
W1840630125	502
W1840630160	502
W1840630200	502
W1840630250	502
W1840630320	502
W1840630400	502
W1840630500	502
W1840800025	502
W1840800050	502
W1840800080	502
W1840800100	502
W1840800125	502
W1840800160	502
W1840800200	502
W1840800250	502
W1840800320	502
W1840800400	502
W1840800500	502
W1841000025	502
W1841000050	502
W1841000080	502
W1841000100	502
W1841000125	502
W1841000160	502
W1841000200	502
W1841000250	502
W1841000320	502
W1841000400	502
W1841000500	502
W18-UEL	153
W20-UES	153
W22-UEL	153
W25-UES	153
W28-UEL	153
W30-UES	153
W3501000100	550
W3501000101	550
W3501000110	550
W3501000111	550
W3501000200	550
W3501000201	550
W3501000210	550
W3501000211	550
W3501000300	550
W3501000311	550
W3501000400	550
W3501000411	550
W3501001100	550
W3501001101	550
W3501001110	550
W3501001111	550
W3501001200	550
W3501001201	550
W3501001210	550
W3501001211	550
W3501001301	550
W3501001311	550
W3501001401	550
W3501001411	550
W35-UEL	153
W3604000001	612
W3604000002	612
W3604000003	612
W3604000004	612
W3604000005	612
W3604000006	612
W3605000001	624
W3606000002	623
W3606000004	623
W38-UES	153
W42-UEL	153
W6001101001	826
W6001101106	826
W6001111011	826
W6001111106	826
W6001111108	826
W6001121021	826
W6001121108	826
W6001121110	826
W6001131112	826
W6-UEL	153
W6-UES	153
W8-UEL	153
W8-UES	153
W-97	1720
WA10	1173
WA13	1173
WA17	1173
WA21	1173
WA26	1173
WA2-6M	1430
WA33	1173
WA3-6M	1430
WA4-6M	1430
WA6-3M	1430
WA8-3M	1430
WAL020102	135
WAL020104	135
WAL020309	135
WAL020324	135
WAL610499	135
WAL610500	135
WAL610519	135
WALLC2-3M	1430
WALLC2-6M	1430
WALLC3312-3M	1430
WALLC3312-6M	1430
WALLC4-3M	1430
WALLC4-6M	1430
WALLC6-3M	1430
WALLC6-6M	1430
WALL-STATION	284
WAM5	1173
WASH-GUN	1657
WATERC1.5D	445
WATERC2.5D	445
WCSD-1332	1413
WCSD-3876	1413
WD-1/2	159
WD-10X1	159
WD-12X1.5	159
WD-14X1.5	159
WD-16X1.5	159
WD-18X1.5	159
WD-20X1.5	159
WD-22X1.5	159
WD-26X1.5	159
WD-27X2	159
WD-3/8	159
WD-33X2	159
WD-42X2	159
WD-48X2	159
WDC1	1558
WDC10	1558
WDC11	1558
WDC12	1558
WDC13	1558
WDC1A	1558
WDC1X	1558
WDC2	1558
WDC2A	1558
WDC2X	1558
WDC3	1558
WDC3X	1558
WDC4	1558
WDC4X	1558
WDC5	1558
WDC6	1558
WDC7	1558
WDC8	1558
WDC9	1558
WDCMOO	1558
WDCO	1558
WDCOO	1558
WDCOOO	1558
WDCOX	1558
WDF-05	1107
WDH-1/2-50	1415
WDH1-10	1431
WDH112-10	1431
WDH112-30	1431
WDH114-10	1431
WDH114-30	1431
WDH1-30	1431
WDH2-10	1431
WDH212-10	1431
WDH212-30	1431
WDH2-30	1431
WDH3-10	1431
WDH3-30	1431
WDH34-10	1431
WDH34-30	1431
WDH4-10	1431
WDH4-30	1431
WDHC1	1533
WDHC180-SS	1533
WDHC1A	1533
WDHC1A-SS	1533
WDHC1-SS	1533
WDHC1X	1533
WDHC1X-SS	1533
WDHC2	1533
WDHC200	1533
WDHC200-SS	1533
WDHC220	1533
WDHC220-SS	1533
WDHC240	1533
WDHC240-SS	1533
WDHC260	1533
WDHC260-SS	1533
WDHC280	1533
WDHC2A	1533
WDHC2A-SS	1533
WDHC2-SS	1533
WDHC2X	1533
WDHC2X-SS	1533
WDHC3	1533
WDHC300	1533
WDHC3-SS	1533
WDHC3X	1533
WDHC3X-SS	1533
WDHC4	1533
WDHC45	1533
WDHC45-SS	1533
WDHC4-SS	1533
WDHC4X	1533
WDHC4X-SS	1533
WDHC5	1533
WDHC5-SS	1533
WDHC6	1533
WDHC6-SS	1533
WDHC7	1533
WDHC7-SS	1533
WDHC8	1533
WDHCMOO	1533
WDHCMOO-SS	1533
WDHCO	1533
WDHCOO	1533
WDHCOOO	1533
WDHCOOO-SS	1533
WDHCOO-SS	1533
WDHCO-SS	1533
WDHCOX	1533
WDHCOX-SS	1533
WE10L-2N	149
WE10L-2RT	149
WE10L-4N	149
WE10L-4RT	149
WE10L-6RT	149
WE10L-8N	149
WE10L-8RT	149
WE10S-4N	149
WE10S-4RT	149
WE10S-6N	149
WE10S-6RT	149
WE10S-8N	149
WE10S-8RT	149
WE12L-2RT	149
WE12L-4N	149
WE12L-4RT	149
WE12L-6N	149
WE12L-6RT	149
WE12L-8N	149
WE12L-8RT	149
WE12S-4N	149
WE12S-4RT	149
WE12S-6N	149
WE12S-6RT	149
WE12S-8N	149
WE12S-8RT	149
WE14S-6N	149
WE14S-6RT	149
WE14S-8N	149
WE14S-8RT	149
WE15L-12N	149
WE15L-12RT	149
WE15L-4RT	149
WE15L-6N	149
WE15L-6RT	149
WE15L-8N	149
WE15L-8RT	149
WE16S-12N	149
WE16S-12RT	149
WE16S-6N	149
WE16S-6RT	149
WE16S-8N	149
WE16S-8RT	149
WE18L-12N	149
WE18L-12RT	149
WE18L-6N	149
WE18L-6RT	149
WE18L-8N	149
WE18L-8RT	149
WE20S-12N	149
WE20S-12RT	149
WE20S-8N	149
WE20S-8RT	149
WE22L-12N	149
WE22L-12RT	149
WE22L-8N	149
WE22L-8RT	149
WE25S-16N	149
WE28L-12N	149
WE28L-16N	149
WE28L-16RT	149
WE30S-20N	149
WE35L-20N	149
WE35L-20RT	149
WE38S-24N	149
WE42L-24N	149

Code	Page
WE6L-2N	149
WE6L-2RT	149
WE6L-4N	149
WE6L-4RT	149
WE6L-6N	149
WE6L-6RT	149
WE6L-8N	149
WE6L-8RT	149
WE6S-2RT	149
WE6S-4N	149
WE6S-4RT	149
WE6S-6N	149
WE6S-6RT	149
WE6S-8N	149
WE6S-8RT	149
WE8L-2N	149
WE8L-2RT	149
WE8L-4N	149
WE8L-4RT	149
WE8L-6N	149
WE8L-6RT	149
WE8L-8N	149
WE8L-8RT	149
WE8S-4N	149
WE8S-4RT	149
WE8S-6N	149
WE8S-6RT	149
WE8S-8N	149
WE8S-8RT	149
WEEV-06L-1/8	152
WEEV-08L-1/4	152
WEEV-10L-1/4	152
WEEV-12L-3/8	152
WEEV-15L-1/2	152
WEEV-18L-1/2	152
WEEV-22L-3/4	152
WEEV-28L-1	152
WEEV-35L-114	152
WEP-12	1183
WES 10 LRK	134
WES 10 LRK 3/8	134
WES 10 SRK	134
WES 12 LRK	134
WES 12 LRK 1/4	134
WES 12 SRK	134
WES 14 SRK	134
WES 15 LRK	134
WES 16 SRK	134
WES 18 LRK	134
WES 6 LRK	134
WES 6 LRK 1/4	134
WES 6 SRK	134
WES 8 LRK	134
WES 8 SRK	134
WEV10L1/4NPT	122
WEV10LMK	122
WEV10LR3/8K	122
WEV10LRK	122
WEV10S3/8NPT	122
WEV10SMK	122
WEV12L1/4NPT	122
WEV12L3/8NPT	122
WEV12LMK	122
WEV12LR1/2K	122
WEV12LR1/4K	122
WEV12LRK	122
WEV12S3/8NPT	122
WEV12SMK	122
WEV12SRK	122
WEV14S1/2NPT	122
WEV14SRK	122
WEV15L1/2NPT	122
WEV15LMK	122
WEV15LR3/8K	122
WEV15LRK	122
WEV16S1/2NPT	122
WEV16SMK	122
WEV16SRK	122
WEV18L1/2NPT	122
WEV18LMK	122
WEV18LRK	122
WEV20S3/4NPT	122
WEV22L3/4NPT	122
WEV25S1NPT	122
WEV28L1NPT	122
WEV4LL1/8NPT	122
WEV4LLMK	122
WEV4LLRK	122
WEV6L1/8NPT	122
WEV6LL1/8NPT	122
WEV6LLMK	122
WEV6LLRK	122
WEV6LMK	122
WEV6LR1/4K	122
WEV6LRK	122
WEV6S1/4NPT	122
WEV6SMK	122
WEV6SRK	122
WEV8L1/4NPT	122
WEV8LL1/8NPT	122
WEV8LLMK	122
WEV8LLRK	122
WEV8LMK	122
WEV8LRK	122
WEV8S1/4NPT	122
WEV8SMK	122
WEV8SRK	122
WF-12	260
WF-16	260
WF-20	260
WF-24	260
WF-M 10 L NBR	118
WF-M 10 L VI	118
WF-M 10 S NBR	118
WF-M 10 S VI	118
WF-M 12 L NBR	118
WF-M 12 L VI	118
WF-M 12 S NBR	118
WF-M 12 S VI	118
WF-M 15 L NBR	118
WF-M 15 L VI	118
WF-M 16 S NBR	118
WF-M 16 S VI	118
WF-M 18 L NBR	118
WF-M 18 L VI	118
WF-M 20 S NBR	118
WF-M 20 S VI	118
WF-M 22 L NBR	118
WF-M 22 L VI	118
WF-M 25 S NBR	118
WF-M 25 S VI	118
WF-M 28 L NBR	118
WF-M 28 L VI	118
WF-M 30 S NBR	118
WF-M 30 S VI	118
WF-M 35 L NBR	118
WF-M 35 L VI	118
WF-M 38 S NBR	118
WF-M 38 S VI	118
WF-M 42 L NBR	118
WF-M 42 L VI	118
WF-M 6 L NBR	118
WF-M 6 L VI	118
WF-M 6 S NBR	118
WF-M 6 S VI	118
WF-M 8 L NBR	118
WF-M 8 L VI	118
WF-M 8 S NBR	118
WF-M 8 S VI	118
WFV10L35	135
WFV12L35	135
WFV15L35	135
WFV15L40	135
WFV16S35	135
WFV18L40	135
WFV20S35	135
WFV20S40	135
WFV20S55	135
WFV22L40	135
WFV22L55	135
WFV25S55	135
WFV28L40	135
WFV30S55	135
WFV35L40	135
WFV35L55	135
WFV42L55	135
WF-WD10L/S	118
WF-WD12L/S	118
WF-WD15L	118
WF-WD16S	118
WF-WD16SVI	118
WF-WD18L	118
WF-WD18LVI	118
WF-WD20S	118
WF-WD20SVI	118
WF-WD22L	118
WF-WD22LVI	118
WF-WD25S	118
WF-WD25SVI	118
WF-WD28L	118
WF-WD28LVI	118
WF-WD30S	118
WF-WD30SVI	118
WF-WD35L	118
WF-WD35LVI	118
WF-WD38S	118
WF-WD38SVI	118
WF-WD42L	118
WF-WD42LVI	118
WF-WD6L/S	118
WF-WD8L/S	118
WG02	1659
WG100-12B-100G	266
WG100-12B-160G	266
WG100-12B-250G	266
WG100-12B-400G	266
WG100-12B-600G	266
WG100-12R-100G	266
WG100-12R-160G	266
WG100-12R-250G	266
WG100-12R-400G	266
WG100-12R-600G	266
WG100-38B-10G	266
WG100-38B-11BAR	413
WG100-38B-14BAR	413
WG100-38B-16G	266
WG100-38B-1BAR	413
WG100-38B-2.5G	266
WG100-38B-20BAR	413
WG100-38B-28BAR	413
WG100-38B-2BAR	413
WG100-38B-40BAR	413
WG100-38B-40G	266
WG100-38B-4BAR	413
WG100-38B-4G	266
WG100-38B-6G	266
WG100-38B-7BAR	413
WG100-38R-10G	266
WG100-38R-16G	266
WG100-38R-2.5G	266
WG100-38R-40G	266
WG100-38R-4G	266
WG100-38R-6G	266
WG40-18B-14BAR	413
WG40-18B-1BAR	413
WG40-18B-2BAR	413
WG40-18R-1	413
WG40-18R-10	413
WG40-18R-16	413
WG40-18R-2.5	413
WG40-18R-25	413
WG40-18R-4	413
WG40-18R-6	413
WG50-18B-11BAR	413
WG50-18B-14BAR	413
WG50-18B-200BAR	413
WG50-18B-20BAR	413
WG50-18B-40BAR	413
WG50-18B-4BAR	413
WG50-18B-70BAR	413
WG50-18B-7BAR	413
WG50-18R-1	413
WG50-18R-10	413
WG50-18R-16	413
WG50-18R-2.5	413
WG50-18R-25	413
WG50-18R-4	413
WG50-18R-6	413
WG63-14B/-30HG	266
WG63-14B-1.6G	266
WG63-14B-100G	266
WG63-14B-10G	266
WG63-14B-11BAR	413
WG63-14B-140BAR	413
WG63-14B-14BAR	413
WG63-14B-160G	266
WG63-14B-16G	266
WG63-14B-1BAR	413
WG63-14B-1G	266
WG63-14B-2.5G	266
WG63-14B-20BAR	413
WG63-14B-250G	266
WG63-14B-25G	266
WG63-14B-28BAR	413
WG63-14B-2BAR	413
WG63-14B-400BAR	413
WG63-14B-400G	266
WG63-14B-40BAR	413
WG63-14B-40G	266
WG63-14B-4BAR	413
WG63-14B-4G	266
WG63-14B-600G	266
WG63-14B-60G	266
WG63-14B-6G	266
WG63-14B-70BAR	413
WG63-14B-7BAR	413
WG63-14FPM-11BAR	413
WG63-14FPM-14BAR	413
WG63-14FPM-1BAR	413
WG63-14FPM-20BAR	413
WG63-14FPM-28BAR	413
WG63-14FPM-2BAR	413
WG63-14FPM-40BAR	413
WG63-14FPM-4BAR	413
WG63-14FPM-7BAR	413
WG63-14R/-30HG	266
WG63-14R-1.6G	266
WG63-14R-100G	266
WG63-14R-10G	266
WG63-14R-160G	266
WG63-14R-16G	266
WG63-14R-1G	266
WG63-14R-2.5G	266
WG63-14R-250G	266
WG63-14R-25G	266
WG63-14R-400G	266
WG63-14R-40G	266
WG63-14R-4G	266
WG63-14R-600G	266
WG63-14R-60G	266
WG63-14R-6G	266
WG63-716B-1/9	265
WG-9	1609
WG-900KIT	1609
WGB-100	413
WGB-63	413
WGS-01	1609
WGS-02	1609
WGS-03	1609
WGS-04	1609
WGS-05	1609
WGS-06	1609
WHV-06L-2EO-WDS	163
WHV-06S-4EO-WDS	163
WHV-08L-4EO-WDS	163
WHV-08S-4EO-WDS	163
WHV-10L-4EO-WDS	163
WHV-10L-4RG	157
WHV-10L-6EO-WDS	163
WHV-10L-6G	157
WHV-10S-4EO-WDS	163
WHV-10S-4RG	157
WHV-10S-6EO-WDS	163
WHV-10S-6G	157
WHV-12L-4EO-WDS	163
WHV-12L-4RG	157
WHV-12L-6EO-WDS	163
WHV-12L-6RG	157
WHV-12L-8EO-WDS	163
WHV-12L-8RG	157
WHV-12S-6EO-WDS	163
WHV-12S-6RG	157
WHV-14S-8EO-WDS	163
WHV-14S-8RG	157
WHV-15L-8EO-WDS	163
WHV-15L-8RG	157
WHV-16S-8EO-WDS	163
WHV-16S-8RG	157
WHV-18L-8EO-WDS	163
WHV-18L-8RG	157
WHV-20S-12EO-WDS	163
WHV-20S-12RG	157
WHV-22L-12EO-WDS	163
WHV-22L-12RG	157
WHV-25S-16EO-WDS	163
WHV-25S-16RG	157
WHV-28L-16EO-WDS	163
WHV-28L-16RG	157
WHV-30S-20EO-WDS	163
WHV-30S-20RG	157

Code	Page
WHV-35L-20EO-WDS	163
WHV-35L-20RG	157
WHV-38S-24EO-WDS	163
WHV-38S-24RG	157
WHV-42L-24EO-WDS	163
WHV-42L-24RG	157
WHV-4LL-2EO-WDS	163
WHV-6L-2RG	157
WHV-6LL-2EO-WDS	163
WHV-6S-4RG	157
WHV-8L-4RG	157
WHV-8LL-2EO-WDS	163
WHV-8S-4RG	157
WI10	1173
WI13	1173
WI17	1173
WI21	1173
WI26	1173
WI33	1173
WIM5	1173
WL1	1489
WL112	1489
WL114	1489
WL12	1489
WL14	1489
WL2	1489
WL212	1489
WL3	1489
WL34	1489
WL38	1489
WL4	1489
WN-1	1185
WN-112	1185
WN-114	1185
WN-12	1185
WN-14	1185
WN-18	1185
WN-2	1185
WN-212	1185
WN-3	1185
WN-34	1185
WN-38	1185
WN-4	1185
WO.DEP	1627
WO.DEPF	1627
WP3URT	1489
WP4URT	1489
WR10LA2M	117
WR10LVIA2M	117
WR10SA2M	117
WR112	1489
WR114	1489
WR12LA2M	117
WR12LVIA2M	117
WR12SA2M	117
WR12SVIA2M	117
WR15LA2M	117
WR15LVIA2M	117
WR16SA2M	117
WR16SVIA2M	117
WR18LA2M	117
WR18LVIA2M	117
WR2	1489
WR20SA2M	117
WR20SVIA2M	117
WR212	1489
WR22LA2M	117
WR22LVIA2M	117
WR25SA2M	117
WR25SVIA2M	117
WR28LA2M	117
WR28LVIA2M	117
WR3	1489
WR30SVIA2M	117
WR35LA2M	117
WR35LVIA2M	117
WR38SA2M	117
WR38SVIA2M	117
WR3URT	1489
WR4	1489
WR42LA2M	117
WR42LVIA2M	117
WR4URT	1489
WR6LA2M	117
WR6LVIA2M	117
WR6SA2M	117
WR6SVIA2M	117
WR8LA2M	117
WR8LVIA2M	117
WR8SVIA2M	117
WRSLEEVE-100	46
WRSLEEVE-125	46
WRSLEEVE-150	46
WRSLEEVE-175	46
WRSLEEVE-200	46
WRSLEEVE-25	46
WRSLEEVE-75	46
WS 10 L	133
WS 12 L	133
WS 12 S	133
WS 15 L	133
WS 16 S	133
WS 18 L	133
WS 20 S	133
WS 22 L	133
WS 25 S	133
WS 28 L	133
WS 30 S	133
WS 35 L	133
WS 38 S	133
WS 42 L	133
WS 6 L	133
WS 6 S	133
WS 8 L	133
WS 8 S	133
WSHOP-STATION	284
WSL10	1173
WSL13	1173
WSL17	1173
WSL21	1173
WSL26	1173
WSL33	1173
WSLM5	1173
WSV10L	123
WSV-10L-FT	156
WSV10S	123
WSV-10S-FT	156
WSV12L	123
WSV-12L-FT	156
WSV12S	123
WSV-12S-FT	156
WSV14S	123
WSV-14S-FT	156
WSV15L	123
WSV-15L-FT	156
WSV16S	123
WSV-16S-FT	156
WSV18L	123
WSV-18L-FT	156
WSV20S	123
WSV-20S-FT	156
WSV22L	123
WSV-22L-FT	156
WSV25S	123
WSV-25S-FT	156
WSV28L	123
WSV-28L-FT	156
WSV30S	123
WSV-30S-FT	156
WSV35L	123
WSV-35L-FT	156
WSV38S	123
WSV-38S-FT	156
WSV42L	123
WSV-42L-FT	156
WSV6L	123
WSV-6L-FT	156
WSV6S	123
WSV-6S-FT	156
WSV8L	123
WSV-8L-FT	156
WSV8S	123
WSV-8S-FT	156
WTC28	1092
WTG100-120	265
WTG100-200	265
WTG100-60	265
WTG100-TE-120	417
WTG100-TE-60	417
WTG160-120	417
WTG160-60	417
WTG63-120	265
WTG63160-120	417
WTG63160-60	417
WTG63-200	265
WTG63-60	265
WV06S	123
WV08S	123
WV10L	123
WV10S	123
WV12L	123
WV12S	123
WV14S	123
WV15L	123
WV16S	123
WV18L	123
WV20S	123
WV22L	123
WV25S	123
WV28L	123
WV30S	123
WV35L	123
WV38S	123
WV42L	123
WV4LL	123
WV6L	123
WV6LL	123
WV8L	123
WV8LL	123
X	
X-110-UPVC	1103
X-16-UPVC	1103
X-20-UPVC	1103
X25-N6	760
X25-S3	760
X-25-UPVC	1103
X25-W3	760
X3039302	558
X3044002	558
X3044302	558
X3044802	558
X3045102	558
X3045502	558
X3046302	558
X3046402	558
X3046502	558
X3047202	558
X3047702	558
X3047802	558
X3048202	558
X3048402	558
X3064002	558
X3064202	558
X3064402	558
X3065102	558
X3066502	558
X3067702	558
X3067802	558
X3068202	558
X3068402	558
X30-N6	760
X30-S3	760
X30-W3	760
X-32-UPVC	1103
X3343702	558
X3343802	558
X3347802	558
X3363702	558
X3363802	558
X3367802	558
X-40-UPVC	1103
X45-N6	760
X45-S3	760
X45-W3	760
X-50-UPVC	1103
X55-N6	760
X55-S3	760
X55-W3	760
X65-N6	760
X65-S3	760
X65-W3	760
X75-N6	760
X75-S3	760
X-75-UPVC	1103
X75-W3	760
X-90-UPVC	1103
XBF0202	64
XBF0204	64
XBF0404	64
XBF0406	64
XBF0408	64
XBF0606	64
XBF0608	64
XBF0808	64
XBF1010	64
XBF1212	64
XBF1216	64
XBF1616	64
XBF2020	64
XBF2424	64
XBF3232	64
XBMBF0202	64
XBMBF0404	64
XBMBF0604	64
XBMBF0606	64
XBMBF0806	64
XBMBF0808	64
XBMBF0812	64
XBMBF1010	64
XBMBF1212	64
XBMBF1616	64
XBMBF2020	64
XBMBF2424	64
XBMBF3232	64
XBMF0402	64
XBMF0404	64
XBMF0406	64
XBMF0604	64
XBMF0606	64
XBMF0608	64
XBMF0612	64
XBMF0806	64
XBMF0808	64
XBMF0812	64
XBMF0816	64
XBMF1212	64
XBMF1216	64
XBMF1612	64
XBMF1616	64
XBMF2424	64
XBMF3232	64
XBMJF0409	77
XBMJF0609	77
XBMJF0612	77
XBMJF0812	77
XBMJF0814	77
XBMJF1014	77
XBMJF1217	77
XFN0202	65
XFN0404	65
XFN0606	65
XFN0608	65
XFN0808	65
XFN1212	65
XFN1616	65
XFN2020	65
XFN2424	65
XFN3232	65
XGNSS	1659
XGNSSR	1659
XJF0707	76
XJF0909	76
XJF1212	76
XJF1414	76
XJF1717	76
XJF1919	76
XJF2121	76
XJMF0707	77
XJMF0808	77
XJMF0909	77
XJMF1212	77
XJMF1414	77
XJMF1717	77
XJMF2121	77
XJMF2626	77
XLPECSDH-13-10	1433
XLPECSDH-13-40	1433
XLPECSDH-19-10	1433
XLPECSDH-19-40	1433
XLPECSDH-25-10	1433
XLPECSDH-25-40	1433
XLPECSDH-32-10	1433
XLPECSDH-32-40	1433
XLPECSDH-38-10	1433
XLPECSDH-38-40	1433
XLPECSDH-51-10	1433
XLPECSDH-51-40	1433
XMB0404	63
XMB0406	63
XMB04J07	77

Code	Page
XMB04J08	77
XMB04J09	77
XMB04N04	64
XMB0606	63
XMB0608	63
XMB06J09	77
XMB06J12	77
XMB06N06	64
XMB0808	63
XMB0812	63
XMB08J12	77
XMB08J14	77
XMB08N08	64
XMB1212	63
XMB12J14	77
XMB12J17	77
XMB1616	63
XMB16J17	77
XMB16J21	77
XMB20J26	77
XMB24J30	77
XMB3232	63
XMBP02T02	63
XMBP04T02	63
XMBP04T04	63
XMBP06T06	63
XMBP08T06	63
XMBP08T08	63
XMBP12T12	63
XMBP16T16	63
XMBS0202	63
XMBS0402	63
XMBS0404	63
XMBS0606	63
XMBS0808	63
XMBS1212	63
XMBS1612	63
XMBS1616	63
XMBS2020	63
XMJ0909	77
XMJ1212	77
XMJ1414	77
XMJ1717	77
XMJ1919	77
XMJ2121	77
XMJ2626	77
XMJ3030	77
XMN04	65
XMN06	65
XMN08	65
XMN12	65
XMN16	65
XMN20	65
XMN24	65
XMN32	65
XNMF0202	65
XNMF0404	65
XNMF0604	65
XNMF0606	65
XNMF0806	65
XNMF0808	65
XNMF1212	65
XNMF1616	65
XNMF2020	65
XNMF2424	65
XO-10	1174
XO-13	1174
XO-17	1174
XO-21	1174
XP73AE61.000	1054
XP73CE61.000	1054
XP73DE61.000	1054
XP73EE61.000	1054
XP83FE61000	1054
XP83GE61000	1054
XS2001	1500
XS4001	1502
XSHC04	557
XY-720	1025
XY-790H	1025
XY-790L	1025
Y	
Y64A-4GA-N1N	685
Y64A-4GA-N2N	685
Y68A-6GN-N1N	685
Y68A-6GN-N2N	685
Y68A-8GN-N1N	685
Y68A-BGN-N1N	685
Y68A-BGN-N2N	685
YLH-1	1424
YLH-1-10	1424
YLH-112	1424
YLH-112-10	1424
YLH-114	1424
YLH-114-10	1424
YLH-2	1424
YLH-2-10	1424
YLH2-100M-ASSY	1426
YLH2-25M-ASSY	1426
YLH2-50M-ASSY	1426
YLH-3	1424
YLH-3-10	1424
YLH3-100M-ASSY	1426
YLH3-25M-ASSY	1426
YLH3-50M-ASSY	1426
YLH-4	1424
YLH-4-10	1424
YLH4-100M-ASSY	1426
YLH4-25M-ASSY	1426
YLH4-50M-ASSY	1426
YLH-5	1424
YLH-5-10	1424
YLH-6	1424
YLH-6-10	1424
YLH6-100M-ASSY	1426
YLH6-25M-ASSY	1426
YLH6-50M-ASSY	1426
YLH-8	1424
YLH-8-10	1424
YLH8-25M-ASSY	1426
YLH8-50M-ASSY	1426
YPS-1	630
YPS-12	630
YPS-14	630
YPS-18	630
YPS-34	630
YPS-38	630
YRC25	1459
YRC50	1459
YS-1	972
YS-112	972
YS-114	972
YS-12	972
YS-2	972
YS-212	972
YS-3	972
YS-34	972
YS-4	972
YT-1000RDM534S00	1023
YT-1000RDN534S01	1023
YZ6185/IP65	1460
YZ7325	1460
Z	
Z29100BREATHE	677
Z4MB02	70
Z4MB04	70
Z4MB06	70
Z4MB08	70
Z4MB10	70
Z4MB12	70
Z4MB16	70
Z4MB20	70
Z4MB24	70
ZA02-9	1449
ZA04-10B-HIVIS	1449
ZA05-15-38-HIVIS	1449
ZA05-15-HIVIS	1449
ZA05-20B12-HIVIS	1449
ZA05-20B-HIVIS	1449
ZBKV01N	1637
ZBKV34N	1637
ZBOP60	1624
ZC 100	511
ZC 125	511
ZC 32	511
ZC 40	511
ZC 50	511
ZC 63	511
ZC 80	511
ZDLI34N	1654
ZFB02	67
ZFB04	67
ZFB06	67
ZFB08	67
ZFB10	67
ZFB12	67
ZFB16	67
ZFB20	67
ZFB24	67
ZFB32	67
ZFE10	1628
ZFEWB	1628
ZFFL02B	1628
ZFFMB04	66
ZFFMB06	66
ZFFMB08	66
ZFFMB10	66
ZFFMB12	66
ZFFMB16	66
ZFFMB20	66
ZFFMJ07	78
ZFFMJ08	78
ZFFMJ09	78
ZFFMJ12	78
ZFFMJ14	78
ZFFMJ17	78
ZFFMJ21	78
ZFFS10BSP	1628
ZFJ07	79
ZFJ08	79
ZFJ09	79
ZFJ12	79
ZFJ14	79
ZFJ17	79
ZFJ21	79
ZFN34	1621
ZFNL4ST	1656
ZFNL8	1655
ZFNL9B	1655
ZFSM1	1655
ZFSM5	1655
ZG77	1640
ZGGH01	1648
ZHC203B	1648
ZHC21XL	1648
ZHCSW3B	1648
ZMB02BS	67
ZMB04	67
ZMB04BS	67
ZMB06	67
ZMB06BS	67
ZMB08	67
ZMB08BS	67
ZMB10BS	67
ZMB12	67
ZMB12BS	67
ZMB16	67
ZMB16BS	67
ZMB24	67
ZMB24BS	67
ZMB32	67
ZMCJ-06-W	548
ZMCP-06-W	548
ZMCR-06-W	548
ZMFFB02	66
ZMFFB04	66
ZMFFB06	66
ZMFFB08	66
ZMFFB10	66
ZMFFB12	66
ZMFFB16	66
ZMFFB20	66
ZMFFJ07	78
ZMFFJ08	78
ZMFFJ09	78
ZMFFJ12	78
ZMFFJ14	78
ZMFFJ17	78
ZMFFJ21	78
ZMFMB02	66
ZMFMB04	66
ZMFMB06	66
ZMFMB08	66
ZMFMB10	66
ZMFMB12	66
ZMFMB16	66
ZMFMB20	66
ZMFMJ07	78
ZMFMJ08	78
ZMFMJ09	78
ZMFMJ12	78
ZMFMJ14	78
ZMFMJ17	78
ZMFMJ21	78
ZMFMJ26	78
ZMFMJ30	78
ZMJ07	79
ZMJ09	79
ZMJ12	79
ZMJ14	79
ZMJ17	79
ZMJ19	79
ZMJ21	79
ZMMFB02	66
ZMMFB04	66
ZMMFB06	66
ZMMFB08	66
ZMMFB12	66
ZMMFB16	66
ZMMFB20	66
ZMMFJ07	79
ZMMFJ09	79
ZMMFJ12	79
ZMMFJ14	79
ZMMFJ17	79
ZMMFJ26	79
ZMN02	67
ZMN04	67
ZMN06	67
ZMN08	67
ZO-10	1174
ZO-13	1174
ZO-17	1174
ZO-21	1174
ZODP15	1655
ZOLP16	1638
ZPTLH	1672
ZPTLTC	1672
ZS 160	511
ZS 200	511
ZS15E1-10L	1030
ZS15E2-10L	1030
ZS15E4-10L	1030
ZS15E7-10L	1030
ZS15VE1-10LS2	1030
ZS15VE2-10LS2	1030
ZS15VE4-10LS2	1030
ZS15VE7-10LS2	1030
ZS20E1	1030
ZS20E2	1030
ZS20E4	1030
ZS20E7	1030
ZS20VE1S2	1030
ZS20VE2S2	1030
ZS20VE4S2	1030
ZS20VE7S2	1030
ZS25E1-25L	1030
ZS25E2	1030
ZS25E4	1030
ZS25E7	1030
ZS25VE1S2	1030
ZS25VE2S2	1030
ZS25VE4S2	1030
ZS25VE7S2	1030
ZSGGR400T	1640
ZTHT01	1648
ZV-05	1175
ZV-05FKM	1175
ZV-10	1175
ZV-10FKM	1175
ZV-13	1175
ZV-13FKM	1175
ZV-17	1175
ZV-17FKM	1175
ZV-21	1175
ZV-21FKM	1175
ZV-26	1175
ZV-33	1175

www.pneumatics.co.uk

NEW WEBSITE!



OVER 60,000 PRODUCTS **AVAILABLE ONLINE**

Order online (Mon-Fri) for next day delivery to any UK location.

LEADING BRANDS
...all leading manufacturer brands supported and supplied.

PRODUCT SEARCH
...use us to source any fluid power product and industrial valves.

PRODUCT CROSS REFERENCE
...use us to find lower-cost alternatives.

TECHNICAL DATA SHEETS
...available for every product.




Fluid-Air Components Ltd

ef nkl i r oi r p c c c a c c

OBSOLETE

Obsolete Product?
Failed Component?



Do you have an obsolete product?
Have you considered repairing or refurbishing?
We can repair or refurbish the following products:

PNEUMATIC & HYDRAULIC
Valves & Cylinders
ELECTRICAL
Power Supplies, Drives, Boards, Motors & Encoders

Need something a little different?
Finding it difficult to get a product or part?

LET US TAKE THE STRAIN OUT OF PRODUCT SOURCING

Our dedicated team can source the products you need from our global network of suppliers.

- *No charge for sourcing*
- *High quality products at competitive prices*
- *Proven track record*

PUT US TO THE TEST
*Email **sales@fluid-air.co.uk** with your product requirments.*

FAC
Fluid-Air Components Ltd

Unit 70, Riverside 3, Sir Thomas Longley Road, Rochester, Kent ME2 4BH
01634 297298
sales@fluid-air.co.uk

VISA MasterCard Maestro
ALL MAJOR CREDIT CARDS ACCEPTED